

Oracle® Solaris Cluster Data Service for Oracle External Proxy Guide

ORACLE®

Part No: E52343
July 2014, E52343-01

Copyright © 2012, 2014, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS. Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Copyright © 2012, 2014, Oracle et/ou ses affiliés. Tous droits réservés.

Ce logiciel et la documentation qui l'accompagne sont protégés par les lois sur la propriété intellectuelle. Ils sont concédés sous licence et soumis à des restrictions d'utilisation et de divulgation. Sauf disposition de votre contrat de licence ou de la loi, vous ne pouvez pas copier, reproduire, traduire, diffuser, modifier, breveter, transmettre, distribuer, exposer, exécuter, publier ou afficher le logiciel, même partiellement, sous quelque forme et par quelque procédé que ce soit. Par ailleurs, il est interdit de procéder à toute ingénierie inverse du logiciel, de le désassembler ou de le décompiler, excepté à des fins d'interopérabilité avec des logiciels tiers ou tel que prescrit par la loi.

Les informations fournies dans ce document sont susceptibles de modification sans préavis. Par ailleurs, Oracle Corporation ne garantit pas qu'elles soient exemptes d'erreurs et vous invite, le cas échéant, à lui en faire part par écrit.

Si ce logiciel, ou la documentation qui l'accompagne, est concédé sous licence au Gouvernement des Etats-Unis, ou à toute entité qui délivre la licence de ce logiciel ou l'utilise pour le compte du Gouvernement des Etats-Unis, la notice suivante s'applique:

U.S. GOVERNMENT END USERS. Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

Ce logiciel ou matériel a été développé pour un usage général dans le cadre d'applications de gestion des informations. Ce logiciel ou matériel n'est pas conçu ni n'est destiné à être utilisé dans des applications à risque, notamment dans des applications pouvant causer des dommages corporels. Si vous utilisez ce logiciel ou matériel dans le cadre d'applications dangereuses, il est de votre responsabilité de prendre toutes les mesures de secours, de sauvegarde, de redondance et autres mesures nécessaires à son utilisation dans des conditions optimales de sécurité. Oracle Corporation et ses affiliés déclinent toute responsabilité quant aux dommages causés par l'utilisation de ce logiciel ou matériel pour ce type d'applications.

Oracle et Java sont des marques déposées d'Oracle Corporation et/ou de ses affiliés. Tout autre nom mentionné peut correspondre à des marques appartenant à d'autres propriétaires qu'Oracle.

Intel et Intel Xeon sont des marques ou des marques déposées d'Intel Corporation. Toutes les marques SPARC sont utilisées sous licence et sont des marques ou des marques déposées de SPARC International, Inc. AMD, Opteron, le logo AMD et le logo AMD Opteron sont des marques ou des marques déposées d'Advanced Micro Devices. UNIX est une marque déposée d'The Open Group.

Ce logiciel ou matériel et la documentation qui l'accompagne peuvent fournir des informations ou des liens donnant accès à des contenus, des produits et des services émanant de tiers. Oracle Corporation et ses affiliés déclinent toute responsabilité ou garantie expresse quant aux contenus, produits ou services émanant de tiers. En aucun cas, Oracle Corporation et ses affiliés ne sauraient être tenus pour responsables des pertes subies, des coûts occasionnés ou des dommages causés par l'accès à des contenus, produits ou services tiers, ou à leur utilisation.

Contents

- Using This Documentation** 7

- 1 Installing and Configuring HA for Oracle External Proxy** 9
 - Overview 9
 - Planning the Installation and Configuration 10
 - Configuration Requirements 10
 - Overview of the Installation and Configuration Process for HA for Oracle External Proxy 14
 - Installing the HA for Oracle External Proxy Package 15
 - ▼ How to Install the HA for Oracle External Proxy Package 15
 - Registering and Configuring HA for Oracle External Proxy 16
 - Setting HA for Oracle External Proxy Extension Properties 16
 - Tools for Registering and Configuring HA for Oracle External Proxy 17
 - ▼ How to Register and Configure HA for Oracle External Proxy 17
 - Setting up Dependencies on Oracle External Proxy Resources 20
 - How to Verify Data Service Installation and Configuration 21
 - Operations By HA for Oracle External Proxy 21
 - Actions in Response to Faults 22
 - Upgrading the ORCL.oracle_external_proxy Resource Type 22
 - Information for Registering the New Resource Type Version 22
 - Information for Migrating Existing Instances of the Resource Type 23

- A HA for Oracle External Proxy Extension Properties** 25

- Index** 29

Using This Documentation

- **Overview** – Explains how to install and configure Oracle Solaris Cluster HA for Oracle External Proxy (HA for Oracle External Proxy).
- **Audience** – Experienced system administrators with extensive knowledge of Oracle software and hardware.
- **Required knowledge** – Knowledge of the Oracle Solaris operating system, of Oracle Solaris Cluster software, and expertise with the volume manager software that is used with Oracle Solaris Cluster software.

This document is not to be used as a planning or presales guide.

Product Documentation Library

Late-breaking information and known issues for this product are included in the documentation library at <http://www.oracle.com/pls/topic/lookup?ctx=E39579>.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program web site at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Feedback

Provide feedback about this documentation at <http://www.oracle.com/goto/docfeedback>.

Installing and Configuring HA for Oracle External Proxy

This chapter describes the steps to install and configure HA for Oracle External Proxy on your Oracle Solaris Cluster servers.

Note - You can install and configure this data service to run in either the global zone or a zone cluster. For updated information about supported configurations of this data service, see the [Oracle Solaris Cluster 4 Compatibility Guide](#).

This chapter contains the following sections:

- “Overview” on page 9
- “Planning the Installation and Configuration” on page 10
- “Overview of the Installation and Configuration Process for HA for Oracle External Proxy” on page 14
- “Installing the HA for Oracle External Proxy Package” on page 15
- “Registering and Configuring HA for Oracle External Proxy” on page 16
- “Operations By HA for Oracle External Proxy” on page 21
- “Upgrading the ORCL.oracle_external_proxy Resource Type” on page 22

You can configure HA for Oracle External Proxy as a failover or a scalable data service. See [Chapter 1, “Planning for Oracle Solaris Cluster Data Services,”](#) in “Oracle Solaris Cluster Data Services Planning and Administration Guide” and the “Oracle Solaris Cluster Concepts Guide” document for an overview of failover and scalable data services.

Overview

The ORCL.oracle_external_proxy resource type interrogates the Oracle Database or the Oracle Real Application Clusters (Oracle RAC) services and interprets the availability of those services as an Oracle Solaris Cluster resource state or status in an Oracle Solaris Cluster configuration.

If the Oracle Database or the Oracle RAC services are unavailable, the Oracle Solaris Cluster resource state will be offline. Similarly, if the Oracle Database or the Oracle RAC services are

available, the Oracle Solaris Cluster resource state will be online. Additionally, appropriate Oracle Solaris Cluster status messages will also be displayed.

For example:

```
# clrs status oep-rs
=== Cluster Resources ===

Resource Name      Node Name      State      Status Message
-----
oep-rs            oephost1      Online    Online - Service orcl is UP
                  oephost2      Online    Online - Service orcl is UP
```

Furthermore, if the Oracle Database and the Oracle RAC services are unavailable, the Oracle Solaris Cluster resource status message will also display the ORA error number and some part of the error message, if known.

For example:

```
# clrs status oep-rs
=== Cluster Resources ===

Resource Name      Node Name      State      Status Message
-----
oep-rs            oephost1      Offline   Offline - Service orcl is DOWN /
[ORA-12514, TNS:listener does not currently ...]
                  oephost2      Offline   Offline - Service orcl is DOWN /
[ORA-12514, TNS:listener does not currently ?]
```

Planning the Installation and Configuration

To register and configure HA for Oracle External Proxy, you must consider or provide information on the following points.

- Decide whether to run HA for Oracle External Proxy as a failover or scalable data service.
- Decide which extension properties to set. See the [“Oracle Solaris Cluster Data Services Planning and Administration Guide”](#) for information about the standard properties and [Appendix A, “HA for Oracle External Proxy Extension Properties”](#) for information about the extension properties.
- Provide the name of the resource type for HA for Oracle External Proxy. This name is `ORCL.oracle_external_proxy`.
- Provide the names of the cluster nodes that will master the data service.

Configuration Requirements

The following sections describe the configuration requirements for Oracle External Proxy.

- [“Remote Database User” on page 11](#)
- [“Secure Remote Database Password” on page 12](#)
- [“tnsnames.ora File” on page 13](#)
- [“Remote Oracle Notification Service” on page 14](#)

Remote Database User

On the Oracle Database or the Oracle RAC database, create a user that will be used by the Oracle External Proxy resource.

EXAMPLE 1-1 Creating a User hauser Using the SQL Commands

This example shows how to create a user hauser with a password hauser by using the SQL commands. You can choose a different username and password. The username and password that you choose will be used later by the Oracle Solaris Cluster resource.

```
-bash-3.00$ sqlplus "/as sysdba"

SQL*Plus: Release 11.2.0.2.0 Production on Fri Nov 4 05:23:31 2011

Copyright (c) 1982, 2010, Oracle. All rights reserved.

Connected to:
Oracle Database 11g Enterprise Edition Release 11.2.0.2.0 - 64bit Production
With the Partitioning, Real Application Clusters, Automatic Storage Management, OLAP,
Data Mining and Real Application Testing options

SQL> create user hauser identified by hauser;

User created.

SQL> grant create session to hauser;

Grant succeeded.

SQL> grant execute on dbms_lock to hauser;

Grant succeeded.

SQL> grant select on v_$instance to hauser;

Grant succeeded.

SQL> create profile hauser limit PASSWORD_LIFE_TIME UNLIMITED;

Profile created.

SQL> alter user hauser identified by hauser profile hauser;
```

User altered.

SQL>

If the Oracle database or the Oracle RAC database is being used as a standby database, then include the following command to [Example 1-1](#).

```
SQL> grant sysdba to hauser;
```

Secure Remote Database Password

The `ORCL.oracle_external_proxy` resource type verifies a connection to the remote Oracle database. There is no requirement for any Oracle Client software on the nodes where the `ORCL.oracle_external_proxy` resource type will execute. You will need to create a secure password to connect to a remote database. [Example 1-2](#) shows how to encrypt the database user password. The example uses `hauser` as the password. However, this password must correspond to the password you used when creating the database user in [“Remote Database User” on page 11](#).

Note - Create `/var/cluster/scoep_key` only once on each node. If you intend to create multiple resources of the `ORCL.oracle_external_proxy` type, use the same key for encryption and decryption. If `/var/cluster/scoep_key` is recreated after an encrypted password has been created, it will not be possible to decrypt the encrypted password using the newly created `/var/cluster/scoep_key`. Consequently, the `ORCL.oracle_external_proxy` resource type will fail to connect to the remote database. Also, the resource will go OFFLINE and you will get the `ORA-01017: invalid username/password; logon denied` message.

If you have recreated `/var/cluster/scoep_key`, you will need to recreate the encrypted password again, and then disable and enable the `ORCL.oracle_external_proxy` resource type for the change to be effective.

EXAMPLE 1-2 Encrypting the Database User Password

Assuming a root role on all Oracle Solaris Cluster nodes, do the following:

```
bash-3.00# dd if=/dev/urandom of=/var/cluster/scoep_key bs=8 count=1
1+0 records in
1+0 records out
bash-3.00#
bash-3.00# echo hauser | /usr/sfw/bin/openssl enc -aes128 -e -pass \
file:/var/cluster/scoep_key -out /opt/ORCLscoep/.oep-rs_passwd
bash-3.00#
```

`oep-rs` in `oep-rs_passwd` represents the resource name that you will create later. However, you can choose a different resource name. Now verify that the password can be decrypted.

```
bash-3.00# /usr/sfw/bin/openssl enc -aes128 -d -pass \
```

```

file:/var/cluster/scoep_key -in /opt/ORCLscoep/.oep-rs_passwd
hauser
bash-3.00# chmod 400 /var/cluster/scoep_key
bash-3.00# chmod 400 /opt/ORCLscoep/.oep-rs_passwd

```

tnsnames.ora File

A valid tnsnames entry for the Oracle Database or Oracle RAC service is required within a tnsnames.ora file. By default, the Oracle External Proxy resource uses the /var/opt/oracle/tnsnames.ora file to determine the tnsnames entry. However, if the default value is not acceptable, then specify the Tns_admin extension property as follows:

```

-p TNS_ADMIN=${ORACLE_HOME}/network/admin
-p TNS_ADMIN=your path to tnsnames.ora

```

The Oracle External Proxy resource can query a remote Oracle data base or a local Oracle database and has the following requirements:

- **Querying a remote Oracle database** - If the Oracle database is a remote Oracle database, then the ADDRESS and the HOST entry in the tnsnames.ora file must specify the SCAN name for either Oracle Database 11g Release 2 or Oracle Database 12c. For Oracle Database 10g Release 2 and Oracle Database 11g Release 1, specify the appropriate listener address entries for each node that runs an instance of the database.
- **Querying a local Oracle database** - If the Oracle database is a local Oracle database then the HOST entry can be omitted. Instead, the PROTOCOL and KEY entries are required within the ADDRESS statement.
- The tnsnames entry and SERVICE_NAME entry must be the same.

The following examples show how to use Oracle External Proxy to query a remote Oracle database and a local Oracle database.

EXAMPLE 1-3 Querying a Remote Oracle Database

In this example, the /var/opt/oracle/tnsnames.ora file is used.

```

bash-3.00# cat /var/opt/oracle/tnsnames.ora
ORCL =
  (DESCRIPTION =
    (ADDRESS = (PROTOCOL = TCP)(HOST = dbhost-scan-lh)(PORT = 1521))
    (CONNECT_DATA =
      (SERVER = DEDICATED)
      (SERVICE_NAME = ORCL)
    )
  )
bash-3.00#

```

The hostname dbhost-scan-lh must be resolvable and within the /etc/hosts file on each node.

```
bash-3.00# grep dbhost-scan-lh /etc/hosts
10.134.84.58 dbhost-scan-lh.us.oracle.com dbhost-scan-lh
bash-3.00#
```

EXAMPLE 1-4 Querying a Local Oracle Database

In this example, the `/var/opt/oracle/tnsnames.ora` file is used.

```
bash-3.00# cat /var/opt/oracle/tnsnames.ora
SALES =
  (DESCRIPTION =
    (ADDRESS = (PROTOCOL = IPC)(KEY = LISTENER))
    (CONNECT_DATA =
      (SERVER = DEDICATED)
      (SERVICE_NAME = SALES)
    )
  )
)
bash-3.00#
```

Remote Oracle Notification Service

Running Oracle Notification Service on every database node reduces the time it takes for the `ORCL.oracle_external_proxy` resource type to connect to the database and to determine the state of the database. To verify that Oracle Notification Service is running on the database nodes, run the following command.

```
bash-3.00# su - oragrid
Oracle Corporation 5.11 11.0 November 2011
-bash-3.00$ crsctl stat res ora.ons -t
-----
NAME TARGET STATE SERVER STATE_DETAILS Local Resources
-----
ora.ons
ONLINE ONLINE dbhost1
ONLINE ONLINE dbhost2
bash-3.00$
```

If Oracle Notification Service fails or stops running on a database node, the `ORCL.oracle_external_proxy` resource will still continue to monitor the remote database. However, it will take longer to connect to the database and determine the state of the database.

Overview of the Installation and Configuration Process for HA for Oracle External Proxy

The following table lists the sections that describe the installation and configuration tasks.

TABLE 1-1 Task Map: Installing and Configuring HA for Oracle External Proxy

Task	Instructions
Install the HA for Oracle External Proxy package	“How to Install the HA for Oracle External Proxy Package” on page 15
Configure and start HA for Oracle External Proxy	“How to Register and Configure HA for Oracle External Proxy” on page 17

Installing the HA for Oracle External Proxy Package

If you did not install the HA for Oracle External Proxy package during your initial Oracle Solaris Cluster installation, perform this procedure to install the package.

▼ How to Install the HA for Oracle External Proxy Package

Perform this procedure on each cluster node where you want the HA for Oracle External Proxy software to run.

1. **On the cluster node where you are installing the data service package, assume the root role.**
2. **Ensure that the data service package is available from the configured publisher and that the `solaris` and `ha-cluster` publishers are valid.**

```
# pkg list -a ha-cluster/data-service/oracle-external-proxy
# pkg publisher
PUBLISHER                TYPE    STATUS  P  LOCATION
solaris                   origin online  F  solaris-repository
ha-cluster                 origin  online  F  ha-cluster-repository
```

For information about setting the `solaris` publisher, see [“Adding, Modifying, or Removing Package Publishers”](#) in [“Adding and Updating Software in Oracle Solaris 11.2”](#).

Tip - Use the `-nv` options whenever you install or update to see what changes will be made, such as which versions of which packages will be installed or updated and whether a new BE will be created. The `-v` option also shows any release notes that apply to this particular install or update operation.

If you do not get any error messages when you use the `-nv` options, run the command again without the `-n` option to actually perform the installation or update. If you do get error messages, run the command again with more `-v` options (for example, `-nvv`) or more of

the package FMRI to get more information to help you diagnose and fix the problem. For troubleshooting information, see [Appendix A, “Troubleshooting Package Installation and Update,”](#) in [“Adding and Updating Software in Oracle Solaris 11.2”](#).

3. Install the HA for Oracle External Proxy software package.

```
# pkg install ha-cluster/data-service/oracle-external-proxy
```

4. Verify that the package installed successfully.

```
$ pkg info ha-cluster/data-service/oracle-external-proxy
```

Installation is successful if output shows that State is Installed.

5. Perform any necessary updates to the Oracle Solaris Cluster software.

For instructions on updating or upgrading your software, see [Chapter 11, “Updating Your Software,”](#) in [“Oracle Solaris Cluster System Administration Guide”](#).

Registering and Configuring HA for Oracle External Proxy

The following sections describe how to register and configure HA for Oracle External Proxy.

- [“Setting HA for Oracle External Proxy Extension Properties”](#) on page 16
- [“Tools for Registering and Configuring HA for Oracle External Proxy”](#) on page 17
- [“How to Register and Configure HA for Oracle External Proxy”](#) on page 17
- [“Setting up Dependencies on Oracle External Proxy Resources”](#) on page 20
- [“How to Verify Data Service Installation and Configuration”](#) on page 21

You can configure HA for Oracle External Proxy as a failover service or as a scalable service.

Setting HA for Oracle External Proxy Extension Properties

The sections that follow contain instructions for registering and configuring HA for Oracle External Proxy resources. For information about the extension properties, see [Appendix A, “HA for Oracle External Proxy Extension Properties”](#). The Tunable entry indicates when you can update a property.

See the [rt_properties\(5\)](#), [r_properties\(5\)](#), and [rg_properties\(5\)](#) man pages for details on all of the Oracle Solaris Cluster extension properties.

To set an extension property of a resource, include the following option in the `clresource` command that creates or modifies the resource:

`-p property=value`

`-p property`

Identifies the extension property that you are setting.

`value`

Specifies the value to which you are setting the extension property.

You can also use the procedures in [Chapter 2, “Administering Data Service Resources,”](#) in [“Oracle Solaris Cluster Data Services Planning and Administration Guide ”](#) to configure resources after the resources are created.

Tools for Registering and Configuring HA for Oracle External Proxy

Oracle Solaris Cluster provides the following tool for registering and configuring HA for Oracle External Proxy:

- **Oracle Solaris Cluster maintenance commands.** For more information, see [“How to Register and Configure HA for Oracle External Proxy”](#) on page 17.

▼ How to Register and Configure HA for Oracle External Proxy

Complete the registration and configuration on any cluster member.

Before You Begin Ensure that you have completed the requirements as described in [“Configuration Requirements”](#) on page 10.

1. **On a cluster member, become an administrator that provides `solaris.cluster.admin` authorization.**
2. **Register the `ORCL.oracle_external_proxy` resource type for the data service.**

```
# clresourcetype register ORCL.oracle_external_proxy
```
3. **Create either a scalable or a failover resource group for the Oracle External Proxy resource.**

For example, to create a scalable resource group, do the following:

```
# clresourcegroup create -S [-n node-zone-list] resource-group
```

resource-group

Specifies the name of the scalable service resource group to add.

-n node-zone-list

Specifies a comma-separated, ordered list of nodes that can master this resource group. This list is optional. If you omit this list, then all the nodes of the global cluster or zone cluster are used to master the resource group.

4. Create an Oracle External Proxy resource in the resource group that you created.

```
# clresource create -g resource-group \  
-t ORCL.oracle_external_proxy \  
-p service_name=service-name \  
-p ons_nodes=ons-nodes \  
-p dbuser=dbuser \  
[-p plugin_name=plugin-name] \  
[-p tns_admin=tns-admin] \  
-d \  
resource
```

-g resource-group

Specifies the name of the resource group .

-t resource-type

Specifies the resource type to add.

-p service_name=service-name

Specifies the Oracle Database or Real Application Clusters (RAC) service name that the Oracle External Proxy uses to connect to the database.

-p ons_nodes=ons-nodes

Specifies the Remote Oracle Notification Service (ONS) nodes that the Oracle External Proxy uses to connect to the database. For a remote Oracle database, specify `ONS_NODES=scan:port` or `ONS_NODES=node:port[node:port]`. For a local Oracle database, specify `ONS_NODES=localhost:port`.

Note - For a remote Oracle Database 11gR2 or later with Grid Infrastructure installed, it is recommended to use `scan_name:port`.

-p dbuser=dbuser

Specifies the server side Oracle database user that the Oracle External Proxy uses to connect to the database. If the database is being used as a standby database, you must grant the `sysdba` privilege to the user, and specify `dbuser="hauser as sysdba"` where `hauser`

represents your entry for dbuser. For information on how to grant the sysdba privilege to the user, see [“Remote Database User” on page 11](#).

`-p plugin_name=plugin-name`

Specifies the plugin module that the Oracle External Proxy uses to connect to the database. You can omit this entry as it will default to `OracleExternalProxy`.

`-p tns_admin=tns-admin`

Specifies the client-side location for the Oracle `tns_admin` path that the Oracle External Proxy uses to connect to the database. Omit this entry so that it defaults to the `/var/opt/oracle` directory.

`-d`

Creates the resource in the disabled state.

`resource`

Specifies your choice for the name of the resource to add.

Note - Optionally, you can set additional extension properties that belong to the Oracle External Proxy data service to override their default values. See [Appendix A, “HA for Oracle External Proxy Extension Properties”](#) for a list of extension properties.

5. Bring the resource group online.

```
# clresourcegroup online -emM resource-group
```

`resource-group`

Specifies the name of the resource group.

The Oracle Solaris Cluster resource is now configured and online, thereby interrogating the state of the remote database.

Example 1-5 Creating an ORCL.oracle_external_proxy Resource

This example shows the commands for performing the following operations which create a scalable multi-master ORCL.oracle_external_proxy resource on a two-node cluster.

- Creating the oep-rg resource group
- Registering the ORCL.oracle_external_proxy resource type
- Adding the oep-rs resource to the oep-rg resource group

This example assumes that default values are being used for the `dbuser`, `tns_admin`, and `plugin_name` extension properties. It also assumes that the `dbuser` password has been encrypted on each cluster node.

```
phys-schost-1# clresource type register ORCL.oracle_external_proxy
phys-schost-1# clresource group create -S oep-rg
phys-schost-1# clresource create -g oep-rg \
-t ORCL.oracle_external_proxy \
-p service_name=orcl \
-p ons_nodes=binks-scan-lh:6200 \
-d \
oep-rs
phys-schost-1# clresource group online -M oep-rg
phys-schost-1# clresource enable oep-rs
```

Example 1-6 Registering Failover HA for Oracle External Proxy

The following example shows how to register a failover Oracle External Proxy service.

```
phys-schost-1# clresource type register ORCL.oracle_external_proxy
phys-schost-1# clresource group create oep-rg
phys-schost-1# clresource create -g oep-rg \
-t ORCL.oracle_external_proxy \
-p service_name=orcl \
-p ons_nodes=binks-scan-lh:6200 \
-d \
oep-rs
phys-schost-1# clresource group online -M oep-rg
phys-schost-1# clresource enable oep-rs
```

Example 1-7 Creating an Oracle External Proxy Resource for a Local Oracle Database

The following example shows how to create an Oracle External Proxy resource for a local Oracle database.

```
phys-schost-1# clresource type register ORCL.oracle_external_proxy
phys-schost-1# clresource group create -S oep-rg
phys-schost-1# clresource create -g oep-rg \
-t ORCL.oracle_external_proxy \
-p service_name=sales \
-p ons_nodes=localhost:6100 \
-d \
oep-rs
phys-schost-1# clresource group online -M oep-rg
phys-schost-1# clresource enable oep-rs
```

Setting up Dependencies on Oracle External Proxy Resources

To use the Oracle Solaris Cluster resource as a dependency for an application resource, set up appropriate dependencies as shown in the following example.

EXAMPLE 1-8 Setting Up Application Resource Group Dependencies

As an example, when the Oracle External Proxy resource is within a scalable resource group and the application resource is within a failover resource group, you can do the following:

```
# clrg set -p RG_Affinities=++oep-rg app-rg
# clrs set -p resource_dependencies_offline_restart=oep-rs{any_node} app-rs
```

As an example, when the Oracle External Proxy resource and the application resource are within the same failover resource group, you can do the following:

```
# clrs set -p resource_dependencies_offline_restart=oep-rs app-rs
```

As an example, when the Oracle External Proxy resource and the application resource are in separate failover resource groups, you can do the following:

```
# clrg set -p RG_Affinities=++oep-rg app-rg
# clrs set -p resource_dependencies_offline_restart=oep-rs app-rs
```

How to Verify Data Service Installation and Configuration

After the Oracle External Proxy resource has been installed, configured, and registered, verify it by enabling the Oracle External Proxy resource. Once the Oracle External Proxy resource has been enabled, the resource status will reflect the state and status of the server-side Oracle database. The presence of a resource status message is verification that the Oracle External Proxy has been installed and configured.

Operations By HA for Oracle External Proxy

The Oracle External Proxy software interrogates an Oracle Database or Oracle RAC service and interprets the availability of that service as an Oracle Solaris Cluster resource state or status. As part of that interrogation, the Oracle External Proxy software uses the Oracle JDBC thin driver to connect to the Oracle Database or Oracle RAC service. The connection is then interpreted by Oracle Solaris Cluster with the Oracle External Proxy resource state and status message.

The Oracle External Proxy writes to a trace file within the `/var/cluster/logs/DS/ORCLSCOEP/message_log.resource` file on each node where three generations are kept. The Oracle External Proxy resource type is responsible for maintaining the generations and automatically removes old generations.

Actions in Response to Faults

If the Oracle External Proxy cannot connect to the Oracle Database or Oracle RAC service, the Oracle Solaris Cluster resource will go offline. An appropriate resource status message will indicate the reason why the connection was not possible. As soon as the Oracle External Proxy can connect to the Oracle Database or Oracle RAC service, the Oracle Solaris Cluster resource will come online.

Upgrading the ORCL.oracle_external_proxy Resource Type

Upgrade the ORCL.oracle_external_proxy resource type if the following conditions apply:

- You are upgrading from an earlier version of the HA for Oracle External Proxy data service.
- You need to use the new features of this data service.

For general instructions that explain how to upgrade a resource type, see [“Upgrading a Resource Type”](#) in [“Oracle Solaris Cluster Data Services Planning and Administration Guide”](#). The information that you require to complete the upgrade of the ORCL.oracle_external_proxy resource type is provided in the following subsections.

- [“Information for Registering the New Resource Type Version”](#) on page 22
- [“Information for Migrating Existing Instances of the Resource Type”](#) on page 23

Information for Registering the New Resource Type Version

The relationship between a resource type version and the release of Oracle Solaris Cluster data services is shown in the following table. The release of Oracle Solaris Cluster data services indicates the release in which the version of the resource type was introduced.

Resource Type Version	Oracle Solaris Cluster Data Services Release
1	1.0

To determine the version of the resource type that is registered, use the `clresourcetype show` command.

The resource type registration (RTR) file for this resource type is `/opt/ORCLscoep/etc/ORCL.oracle_external_proxy`.

Information for Migrating Existing Instances of the Resource Type

The information that you require to edit each instance of the ORCL.oracle_external_proxy resource type is as follows:

- You can perform the migration at any time.

The following example shows the command for modifying an instance of the ORCL.oracle_external_proxy resource type.

EXAMPLE 1-9 Migrating Instances of the ORCL.oracle_external_proxy Resource Type

The following command sets the Type_version property of the ORCL.oracle_external_proxy resource named oep-rs to 2.

```
# clresource set -p Type_version=2 oep-rs
```


HA for Oracle External Proxy Extension Properties

This section describes the extension properties for the resource type `ORCL.oracle_external_proxy`. This resource type represents the Oracle External Proxy application in an Oracle Solaris Cluster configuration.

For details about system-defined properties, see the [r_properties\(5\)](#) and [rg_properties\(5\)](#) man pages.

The extension properties of the `ORCL.oracle_external_proxy` resource type are as follows:

Debug_level

This property indicates the level to which debug messages for the `ORCL.oracle_external_proxy` resources are logged. When the debug level is increased, more debug messages are written to the terminal, the console, and the system log `/var/adm/messages` as follows:

- | | |
|---|--|
| 0 | No debug messages |
| 1 | Function Begin and End messages |
| 2 | All debug messages and function Begin and End messages |

For messages to appear in the system log, perform the following:

1. Edit the `/etc/syslog.conf` file and make sure that the debug is set.

```
*.err;kern.debug;daemon.debug;mail.crit /var/adm/messages
```

2. Disable the system log.

```
bash-3.00# svcadm disable system-log
```

3. Enable the system log.

```
bash-3.00# svcadm enable system-log
```

Data Type Integer

Range	0 - 2
Default	0
Tunable	Any time

Dbuser

This property specifies the server-side Oracle Database user that the proxy monitor uses to connect to the database.

Data Type	String
Default	hauser
Tunable	When disabled

Ons_nodes

This property specifies the Remote Oracle Notification Server (ONS) nodes such as *node:port[,node:port]* that the proxy monitor uses to connect to the database.

Data Type	String
Default	None
Tunable	When disabled

Plugin_name

This property specifies the plugin module name that the proxy monitor uses to connect to the database.

Data Type	String
Default	OracleExternalProxy
Tunable	When disabled

Service_name

This property specifies the Oracle Database or Oracle RAC service name that the proxy monitor uses to connect to the database.

Data Type	String
Default	None
Tunable	When disabled

Tns_admin

This property specifies the client-side location for the Oracle Tns_admin path that the proxy monitor uses to connect to the database.

Data Type	String
Default	/var/opt/oracle
Tunable	When disabled

Index

C

configuring
 Oracle Solaris Cluster HA for Oracle External Proxy, 17

E

extension properties
 ORCL.oracle_external_proxy resource type, 25

F

fault monitor
 HA for Oracle External Proxy, 21
files
 RTR, 22

H

HA for Oracle External Proxy
 fault monitor, 21
 installing, 15
 resource type versions, 22
 software package, installing, 15

I

installing
 HA for Oracle External Proxy, 15

O

Oracle Solaris Cluster HA for Oracle External Proxy
 installation

 verifying, 21

 registering and configuring, 17

 task map, 14

Oracle Solaris Cluster software

 publisher, 15, 15

ORCL.oracle_external_proxy resource type

 extension properties, 25

P

package, 15

properties, 23

See also extension properties

 Type_version, 23

Proxy Server

 installing and configuring, 9

publisher

 Oracle Solaris Cluster software, 15, 15

R

registering

 Oracle Solaris Cluster HA for Oracle External Proxy, 17

resource type registration (RTR) file, 22

RTR (resource type registration) file, 22

S

software package, 15

T

task map

Oracle Solaris Cluster HA for Oracle External
Proxy, 14
Type_version property, 23

V

verifying
Oracle Solaris Cluster HA for Oracle External
Proxy installation, 21
versions
resource types, 22