Oracle® Database

Database Reference

23ai
F46697-05
May 2024

Oracle Database Database Reference, 23ai

F46697-05

Copyright © 2002, 2024, Oracle and/or its affiliates.

Primary Author: Mary Beth Roeser

Contributing Authors: Sarika Surampudi

Contributors: Nipun Agarwal, Nigel Bayliss, Neerja Bhatt, Wilson Chan, Sumanta Chatterjee, Eugene Chong, Thuvan Hoang, Mark Johnson, Jonathan Klein, Sushil Kumar, Tirthankar Lahiri, Bill Lee, Yunrui Li, Juan Loaiza, Rich Long, Catherine Luu, Neil MacNaughton, Gopal Mulagund, Kant Patel, Mark Ramacher, Suvendu Ray, Debbie Steiner, Malai Stalin, Seema Sundara, Murali Thiyagarajah, Alex Tsukerman, Kothanda Umamageswaran, Steve Vivian, Eric Voss, Tak Wang, Steve Wertheimer, Andy Witkowski, Daniel Wong, Qin Yu, Mohamed Ziauddin

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface

Audience xcii
Documentation Accessibility xcii
Diversity and Inclusion xcii
Related Documents xciii
Conventions xciii

1 Changes in This Release for Oracle Database Reference

1.1 New Features 1-1
1.2 Deprecated Features 1-7
1.3 Desupported Features 1-7

Part I Initialization Parameters

2 Initialization Parameters

2.1 Uses of Initialization Parameters 2-1
2.1.1 Types of Initialization Parameters 2-2
2.1.1.1 Derived Parameters 2-2
2.1.1.2 Operating System-Dependent Parameters 2-2
2.1.1.3 Variable Parameters 2-2
2.2 Basic Initialization Parameters 2-3
2.3 Parameter Files 2-3
2.3.1 Server Parameter Files 2-4
2.3.2 Initialization Parameter Files 2-4
2.3.2.1 About the Character Set of Parameter Values 2-5
2.3.2.2 Specifying Values in an Initialization Parameter File 2-5
2.4 Changing Parameter Values in a Parameter File 2-9
2.4.1 Parameters by Functional Category 2-9
2.4.2 Modifiable Parameters 2-19
2.4.3 Displaying Current Parameter Values 2-28

2.4.4 Parameters You Should Not Specify in the Parameter File 2-28
2.4.5 When Parameters Are Set Incorrectly 2-28
2.5 Reading the Parameter Descriptions 2-29
2.6 Initialization Parameter Descriptions 2-30
2.7 ACTIVE_INSTANCE_COUNT 2-30
2.8 ADG_ACCOUNT_INFO_TRACKING 2-31
2.9 ADG_REDIRECT_DML 2-32
2.10 ALLOW_GLOBAL_DBLINKS 2-33
2.11 ALLOW_GROUP_ACCESS_TO_SGA 2-33
2.12 ALLOW_LEGACY_RECO_PROTOCOL 2-34
2.13 ALLOW_ROWID_COLUMN_TYPE 2-35
2.14 APPROX_FOR_AGGREGATION 2-36
2.15 APPROX_FOR_COUNT_DISTINCT 2-36
2.16 APPROX_FOR_PERCENTILE 2-37
2.17 AQ_TM_PROCESSES 2-38
2.18 ARCHIVE_LAG_TARGET 2-39
2.19 ASM_DISKGROUPS 2-40
2.20 ASM_DISKSTRING 2-41
2.21 ASM_IO_PROCESSES 2-42
2.22 ASM_POWER_LIMIT 2-42
2.23 ASM_PREFERRED_READ_FAILURE_GROUPS 2-43
2.24 AUDIT_FILE_DEST 2-44
2.25 AUDIT_SYS_OPERATIONS 2-45
2.26 AUDIT_SYSLOG_LEVEL 2-46
2.27 AUDIT_TRAIL 2-48
2.28 AUTOTASK_MAX_ACTIVE_PDBS 2-50
2.29 AWR_PDB_AUTOFLUSH_ENABLED 2-51
2.30 AWR_PDB_MAX_PARALLEL_SLAVES 2-52
2.31 AWR_SNAPSHOT_TIME_OFFSET 2-52
2.32 BACKGROUND_CORE_DUMP 2-53
2.33 BACKGROUND_DUMP_DEST 2-54
2.34 BACKUP_TAPE_IO_SLAVES 2-55
2.35 BITMAP_MERGE_AREA_SIZE 2-56
2.36 BLANK_TRIMMING 2-56
2.37 BLOCKCHAIN_TABLE_MAX_NO_DROP 2-57
2.38 BLOCKCHAIN_TABLE_RETENTION_THRESHOLD 2-58
2.39 CIRCUITS 2-59
2.40 CLIENT_RESULT_CACHE_LAG 2-59
2.41 CLIENT_RESULT_CACHE_SIZE 2-60
2.42 CLIENT_STATISTICS_LEVEL 2-60
2.43 CLONEDB 2-62

2.44 CLONEDB_DIR 2-63
2.45 CLUSTER_DATABASE 2-63
2.46 CLUSTER_INTERCONNECTS 2-64
2.47 COMMIT_LOGGING 2-65
2.48 COMMIT_POINT_STRENGTH 2-65
2.49 COMMIT_WAIT 2-66
2.50 COMMIT_WRITE 2-67
2.51 COMMON_USER_PREFIX 2-68
2.52 COMPATIBLE 2-69
2.53 CONNECTION_BROKERS 2-70
2.54 CONTAINER_DATA 2-72
2.55 CONTAINERS_PARALLEL_DEGREE 2-73
2.56 CONTROL_FILE_RECORD_KEEP_TIME 2-73
2.57 CONTROL_FILES 2-74
2.58 CONTROL_MANAGEMENT_PACK_ACCESS 2-75
2.59 CORE_DUMP_DEST 2-76
2.60 CPU_COUNT 2-76
2.61 CPU_MIN_COUNT 2-78
2.62 CREATE_BITMAP_AREA_SIZE 2-79
2.63 CREATE_STORED_OUTLINES 2-79
2.64 CURSOR_BIND_CAPTURE_DESTINATION 2-80
2.65 CURSOR_INVALIDATION 2-81
2.66 CURSOR_SHARING 2-82
2.67 CURSOR_SPACE_FOR_TIME 2-82
2.68 DATA_GUARD_MAX_IO_TIME 2-84
2.69 DATA_GUARD_MAX_LONGIO_TIME 2-84
2.70 DATA_GUARD_SYNC_LATENCY 2-85
2.71 DATA_TRANSFER_CACHE_SIZE 2-86
2.72 DB_nK_CACHE_SIZE 2-86
2.73 DB_BIG_TABLE_CACHE_PERCENT_TARGET 2-87
2.74 DB_BLOCK_BUFFERS 2-89
2.75 DB_BLOCK_CHECKING 2-90
2.76 DB_BLOCK_CHECKSUM 2-91
2.77 DB_BLOCK_SIZE 2-92
2.78 DB_CACHE_ADVICE 2-93
2.79 DB_CACHE_SIZE 2-94
2.80 DB_CREATE_FILE_DEST 2-95
2.81 DB_CREATE_ONLINE_LOG_DEST_n 2-96
2.82 DB_DOMAIN 2-97
2.83 DB_FILE_MULTIBLOCK_READ_COUNT 2-98
2.84 DB_FILE_NAME_CONVERT 2-99

2.85 DB_FILES 2-100
2.86 DB_FLASH_CACHE_FILE 2-101
2.87 DB_FLASH_CACHE_SIZE 2-101
2.88 DB_FLASHBACK_LOG_DEST 2-102
2.89 DB_FLASHBACK_LOG_DEST_SIZE 2-103
2.90 DB_FLASHBACK_RETENTION_TARGET 2-104
2.91 DB_INDEX_COMPRESSION_INHERITANCE 2-105
2.92 DB_KEEP_CACHE_SIZE 2-106
2.93 DB_LOST_WRITE_PROTECT 2-106
2.94 DB_NAME 2-108
2.95 DB_PERFORMANCE_PROFILE 2-108
2.96 DB_RECOVERY_AUTO_REKEY 2-109
2.97 DB_RECOVERY_FILE_DEST 2-110
2.98 DB_RECOVERY_FILE_DEST_SIZE 2-110
2.99 DB_RECYCLE_CACHE_SIZE 2-111
2.100 DB_SECUREFILE 2-112
2.101 DB_ULTRA_SAFE 2-113
2.102 DB_UNIQUE_NAME 2-114
2.103 DB_UNRECOVERABLE_SCN_TRACKING 2-115
2.104 DB_WRITER_PROCESSES 2-115
2.105 DBFIPS_140 2-116
2.106 DBNEST_ENABLE 2-117
2.107 DBNEST_PDB_FS_CONF 2-118
2.108 DBWR_IO_SLAVES 2-118
2.109 DDL_LOCK_TIMEOUT 2-119
2.110 DEFAULT_SHARING 2-120
2.111 DEFERRED_SEGMENT_CREATION 2-120
2.112 DG_BROKER_CONFIG_FILEn 2-121
2.113 DG_BROKER_START 2-121
2.114 DIAGNOSTIC_DEST 2-122
2.115 DIAGNOSTICS_CONTROL 2-123
2.116 DISK_ASYNCH_IO 2-124
2.117 DISPATCHERS 2-125
2.118 DISTRIBUTED_LOCK_TIMEOUT 2-127
2.119 DML_LOCKS 2-128
2.120 DNFS_BATCH_SIZE 2-129
2.121 DRCP_DEDICATED_OPT 2-129
2.122 DST_UPGRADE_INSERT_CONV 2-130
2.123 ENABLE_AUTOMATIC_MAINTENANCE_PDB 2-131
2.124 ENABLE_DDL_LOGGING 2-132
2.125 ENABLE_DNFS_DISPATCHER 2-134

2.126 ENABLE_GOLDENGATE_REPLICATION 2-134
2.127 ENABLE_IMC_WITH_MIRA 2-135
2.128 ENABLE_PER_PDB_DRCP 2-136
2.129 ENABLE_PLUGGABLE_DATABASE 2-137
2.130 ENABLED_PDBS_ON_STANDBY 2-137
2.131 ENCRYPT_NEW_TABLESPACES 2-139
2.132 ERROR_MESSAGE_DETAILS 2-140
2.133 EVENT 2-141
2.134 EXTERNAL_KEYSTORE_CREDENTIAL_LOCATION 2-141
2.135 FAL_CLIENT 2-142
2.136 FAL_SERVER 2-143
2.137 FAST_START_MTTR_TARGET 2-143
2.138 FAST_START_PARALLEL_ROLLBACK 2-144
2.139 FILE_MAPPING 2-145
2.140 FILEIO_NETWORK_ADAPTERS 2-145
2.141 FILESYSTEMIO_OPTIONS 2-146
2.142 FIXED_DATE 2-146
2.143 FORWARD_LISTENER 2-147
2.144 GCS_SERVER_PROCESSES 2-148
2.145 GLOBAL_NAMES 2-148
2.146 GLOBAL_TXN_PROCESSES 2-149
2.147 GROUP_BY_POSITION_ENABLED 2-150
2.148 HASH_AREA_SIZE 2-151
2.149 HEARTBEAT_BATCH_SIZE 2-152
2.150 HEAT_MAP 2-152
2.151 HI_SHARED_MEMORY_ADDRESS 2-153
2.152 HS_AUTOREGISTER 2-153
2.153 HYBRID_READ_ONLY 2-154
2.154 IDENTITY_PROVIDER_CONFIG 2-155
2.155 IDENTITY_PROVIDER_TYPE 2-156
2.156 IFILE 2-157
2.157 IGNORE_SESSION_SET_PARAM_ERRORS 2-158
2.158 INMEMORY_ADG_ENABLED 2-159
2.159 INMEMORY_AUTOMATIC_LEVEL 2-160
2.160 INMEMORY_CLAUSE_DEFAULT 2-161
2.161 INMEMORY_DEEP_VECTORIZATION 2-166
2.162 INMEMORY_EXPRESSIONS_USAGE 2-167
2.163 INMEMORY_FORCE 2-168
2.164 INMEMORY_MAX_POPULATE_SERVERS 2-169
2.165 INMEMORY_OPTIMIZED_ARITHMETIC 2-170
2.166 INMEMORY_QUERY 2-171

2.167 INMEMORY_SIZE 2-172
2.168 INMEMORY_TRICKLE_REPOPULATE_SERVERS_PERCENT 2-173
2.169 INMEMORY_VIRTUAL_COLUMNS 2-174
2.170 INSTANCE_ABORT_DELAY_TIME 2-175
2.171 INSTANCE_GROUPS 2-176
2.172 INSTANCE_MODE 2-177
2.173 INSTANCE_NAME 2-177
2.174 INSTANCE_NUMBER 2-178
2.175 INSTANCE_TYPE 2-179
2.176 IORM_LIMIT_POLICY 2-179
2.177 JAVA_JIT_ENABLED 2-181
2.178 JAVA_MAX_SESSIONSPACE_SIZE 2-181
2.179 JAVA_POOL_SIZE 2-182
2.180 JAVA_SOFT_SESSIONSPACE_LIMIT 2-182
2.181 JOB_QUEUE_PROCESSES 2-183
2.182 JSON_BEHAVIOR 2-185
2.183 JSON_EXPRESSION_CHECK 2-186
2.184 LARGE_POOL_SIZE 2-187
2.185 LDAP_DIRECTORY_ACCESS 2-188
2.186 LDAP_DIRECTORY_SYSAUTH 2-190
2.187 LICENSE_MAX_SESSIONS 2-191
2.188 LICENSE_MAX_USERS 2-192
2.189 LICENSE_SESSIONS_WARNING 2-192
2.190 LISTENER_NETWORKS 2-193
2.191 LOB_SIGNATURE_ENABLE 2-194
2.192 LOCAL_LISTENER 2-195
2.193 LOCK_NAME_SPACE 2-195
2.194 LOCK_SGA 2-196
2.195 LOG_ARCHIVE_CONFIG 2-196
2.196 LOG_ARCHIVE_DEST 2-197
2.197 LOG_ARCHIVE_DEST_n 2-199
2.198 LOG_ARCHIVE_DEST_STATE_n 2-203
2.199 LOG_ARCHIVE_DUPLEX_DEST 2-205
2.200 LOG_ARCHIVE_FORMAT 2-205
2.201 LOG_ARCHIVE_MAX_PROCESSES 2-207
2.202 LOG_ARCHIVE_MIN_SUCCEED_DEST 2-207
2.203 LOG_ARCHIVE_TRACE 2-209
2.204 LOG_BUFFER 2-211
2.205 LOG_CHECKPOINT_INTERVAL 2-212
2.206 LOG_CHECKPOINT_TIMEOUT 2-213
2.207 LOG_CHECKPOINTS_TO_ALERT 2-214

2.208 LOG_FILE_NAME_CONVERT 2-214
2.209 LONG_MODULE_ACTION 2-216
2.210 MANDATORY_USER_PROFILE 2-216
2.211 MAX_AUTH_SERVERS 2-217
2.212 MAX_COLUMNS 2-218
2.213 MAX_DATAPUMP_JOBS_PER_PDB 2-219
2.214 MAX_DATAPUMP_PARALLEL_PER_JOB 2-220
2.215 MAX_DISPATCHERS 2-220
2.216 MAX_DUMP_FILE_SIZE 2-221
2.217 MAX_IDLE_BLOCKER_TIME 2-222
2.218 MAX_IDLE_TIME 2-223
2.219 MAX_IOPS 2-223
2.220 MAX_MBPS 2-224
2.221 MAX_PDBS 2-225
2.222 MAX_SAGA_DURATION 2-226
2.223 MAX_SHARED_SERVERS 2-226
2.224 MAX_STRING_SIZE 2-227
2.225 MEMOPTIMIZE_POOL_SIZE 2-232
2.226 MEMOPTIMIZE_WRITE_AREA_SIZE 2-233
2.227 MEMOPTIMIZE_WRITES 2-233
2.228 MEMORY_MAX_SIZE 2-234
2.229 MEMORY_MAX_TARGET 2-235
2.230 MEMORY_SIZE 2-235
2.231 MEMORY_TARGET 2-236
2.232 MIN_AUTH_SERVERS 2-237
2.233 MLE_PROG_LANGUAGES 2-238
2.234 MULTISHARD_QUERY_DATA_CONSISTENCY 2-239
2.235 NLS_CALENDAR 2-240
2.236 NLS_COMP 2-241
2.237 NLS_CURRENCY 2-242
2.238 NLS_DATE_FORMAT 2-243
2.239 NLS_DATE_LANGUAGE 2-244
2.240 NLS_DUAL_CURRENCY 2-245
2.241 NLS_ISO_CURRENCY 2-246
2.242 NLS_LANGUAGE 2-246
2.243 NLS_LENGTH_SEMANTICS 2-248
2.244 NLS_NCHAR_CONV_EXCP 2-249
2.245 NLS_NUMERIC_CHARACTERS 2-249
2.246 NLS_SORT 2-250
2.247 NLS_TERRITORY 2-251
2.248 NLS_TIMESTAMP_FORMAT 2-252

2.249	NLS_TIMESTAMP_TZ_FORMAT	2-253
2.250	NONCDB_COMPATIBLE	2-254
2.251	OBJECT_CACHE_MAX_SIZE_PERCENT	2-255
2.252	OBJECT_CACHE_OPTIMAL_SIZE	2-255
2.253	OFS_THREADS	2-256
2.254	OLAP_PAGE_POOL_SIZE	2-257
2.255	ONE_STEP_PLUGIN_FOR_PDB_WITH_TDE	2-257
2.256	OPEN_CURSORS	2-258
2.257	OPEN_LINKS	2-259
2.258	OPEN_LINKS_PER_INSTANCE	2-260
2.259	OPTIMIZER_ADAPTIVE_PLANS	2-260
2.260	OPTIMIZER_ADAPTIVE_REPORTING_ONLY	2-261
2.261	OPTIMIZER_ADAPTIVE_STATISTICS	2-262
2.262	OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES	2-263
2.263	OPTIMIZER_CAPTURE_SQL_QUARANTINE	2-263
2.264	OPTIMIZER_CROSS_SHARD_RESILIENCY	2-264
2.265	OPTIMIZER_DYNAMIC_SAMPLING	2-264
2.266	OPTIMIZER_FEATURES_ENABLE	2-265
2.267	OPTIMIZER_IGNORE_HINTS	2-267
2.268	OPTIMIZER_IGNORE_PARALLEL_HINTS	2-267
2.269	OPTIMIZER_INDEX_CACHING	2-268
2.270	OPTIMIZER_INDEX_COST_ADJ	2-268
2.271	OPTIMIZER_INMEMORY_AWARE	2-269
2.272	OPTIMIZER_MODE	2-270
2.273	OPTIMIZER_REAL_TIME_STATISTICS	2-271
2.274	OPTIMIZER_SESSION_TYPE	2-271
2.275	OPTIMIZER_USE_INVISIBLE_INDEXES	2-272
2.276	OPTIMIZER_USE_PENDING_STATISTICS	2-272
2.277	OPTIMIZER_USE_SQL_PLAN_BASELINES	2-273
2.278	OPTIMIZER_USE_SQL_QUARANTINE	2-274
2.279	OS_AUTHENT_PREFIX	2-274
2.280	OS_ROLES	2-275
2.281	OUTBOUND_DBLINK_PROTOCOLS	2-276
2.282	PARALLEL_ADAPTIVE_MULTI_USER	2-277
2.283	PARALLEL_DEGREE_LIMIT	2-277
2.284	PARALLEL_DEGREE_POLICY	2-279
2.285	PARALLEL_EXECUTION_MESSAGE_SIZE	2-280
2.286	PARALLEL_FORCE_LOCAL	2-281
2.287	PARALLEL_INSTANCE_GROUP	2-281
2.288	PARALLEL_MAX_SERVERS	2-282
2.289	PARALLEL_MIN_DEGREE	2-283

2.290 PARALLEL_MIN_PERCENT 2-284
2.291 PARALLEL_MIN_SERVERS 2-285
2.292 PARALLEL_MIN_TIME_THRESHOLD 2-286
2.293 PARALLEL_SERVERS_TARGET 2-286
2.294 PARALLEL_THREADS_PER_CPU 2-288
2.295 PDB_FILE_NAME_CONVERT 2-289
2.296 PDB_LOCKDOWN 2-290
2.297 PDB_OS_CREDENTIAL 2-292
2.298 PERMIT_92_WRAP_FORMAT 2-293
2.299 PGA_AGGREGATE_LIMIT 2-294
2.300 PGA_AGGREGATE_TARGET 2-295
2.301 PKCS11_LIBRARY_LOCATION 2-297
2.302 PLSCOPE_SETTINGS 2-298
2.303 PLSQL_CCFLAGS 2-300
2.304 PLSQL_CODE_TYPE 2-300
2.305 PLSQL_DEBUG 2-301
2.306 PLSQL_IMPLICIT_CONVERSION_BOOL 2-302
2.307 PLSQL_OPTIMIZE_LEVEL 2-303
2.308 PLSQL_V2_COMPATIBILITY 2-304
2.309 PLSQL_WARNINGS 2-305
2.310 PMEM_FILESTORE 2-306
2.311 PRE_PAGE_SGA 2-307
2.312 PRIORITY_TXNS_HIGH_WAIT_TARGET 2-308
2.313 PRIORITY_TXNS_MEDIUM_WAIT_TARGET 2-309
2.314 PRIORITY_TXNS_MODE 2-310
2.315 PRIVATE_TEMP_TABLE_PREFIX 2-311
2.316 PROCESSES 2-312
2.317 PROCESSOR_GROUP_NAME 2-313
2.318 QUERY_REWRITE_ENABLED 2-313
2.319 QUERY_REWRITE_INTEGRITY 2-314
2.320 RDBMS_SERVER_DN 2-316
2.321 READ_ONLY 2-317
2.322 READ_ONLY_OPEN_DELAYED 2-317
2.323 RECOVERY_PARALLELISM 2-318
2.324 RECYCLEBIN 2-319
2.325 REDO_TRANSPORT_USER 2-319
2.326 REMOTE_DEPENDENCIES_MODE 2-320
2.327 REMOTE_LISTENER 2-320
2.328 REMOTE_LOGIN_PASSWORDFILE 2-321
2.329 REMOTE_OS_ROLES 2-322
2.330 REMOTE_RECOVERY_FILE_DEST 2-323

2.331 REPLICATION_DEPENDENCY_TRACKING 2-323
2.332 RESOURCE_LIMIT 2-324
2.333 RESOURCE_MANAGE_GOLDENGATE 2-325
2.334 RESOURCE_MANAGER_CPU_ALLOCATION 2-325
2.335 RESOURCE_MANAGER_CPU_SCOPE 2-326
2.336 RESOURCE_MANAGER_PLAN 2-327
2.337 RESULT_CACHE_AUTO_BLOCKLIST 2-329
2.338 RESULT_CACHE_EXECUTION_THRESHOLD 2-330
2.339 RESULT_CACHE_INTEGRITY 2-330
2.340 RESULT_CACHE_MAX_RESULT 2-331
2.341 RESULT_CACHE_MAX_SIZE 2-332
2.342 RESULT_CACHE_MAX_TEMP_RESULT 2-332
2.343 RESULT_CACHE_MAX_TEMP_SIZE 2-333
2.344 RESULT_CACHE_MODE 2-333
2.345 RESULT_CACHE_REMOTE_EXPIRATION 2-335
2.346 RESUMABLE_TIMEOUT 2-335
2.347 ROLLBACK_SEGMENTS 2-336
2.348 SAGA_HIST_RETENTION 2-337
2.349 SEC_MAX_FAILED_LOGIN_ATTEMPTS 2-337
2.350 SEC_PROTOCOL_ERROR_FURTHER_ACTION 2-338
2.351 SEC_PROTOCOL_ERROR_TRACE_ACTION 2-339
2.352 SEC_RETURN_SERVER_RELEASE_BANNER 2-339
2.353 SERIAL_REUSE 2-340
2.354 SERVICE_NAMES 2-341
2.355 SESSION_CACHED_CURSORS 2-342
2.356 SESSION_EXIT_ON_PACKAGE_STATE_ERROR 2-343
2.357 SESSION_MAX_OPEN_FILES 2-344
2.358 SESSIONS 2-344
2.359 SGA_MAX_SIZE 2-345
2.360 SGA_MIN_SIZE 2-346
2.361 SGA_TARGET 2-347
2.362 SHADOW_CORE_DUMP 2-350
2.363 SHARD_ENABLE_RAFT_FOLLOWER_READ 2-351
2.364 SHARD_RAFT_LOGFILE_SIZE 2-351
2.365 SHARED_MEMORY_ADDRESS 2-352
2.366 SHARED_POOL_RESERVED_SIZE 2-352
2.367 SHARED_POOL_SIZE 2-353
2.368 SHARED_SERVER_SESSIONS 2-355
2.369 SHARED_SERVERS 2-355
2.370 SHRD_DUPL_TABLE_REFRESH_RATE 2-356
2.371 SKIP_UNUSABLE_INDEXES 2-357

2.372 SMTP_OUT_SERVER 2-358
2.373 SORT_AREA_RETAINED_SIZE 2-358
2.374 SORT_AREA_SIZE 2-359
2.375 SPATIAL_VECTOR_ACCELERATION 2-361
2.376 SPFILE 2-361
2.377 SQL_ERROR_MITIGATION 2-362
2.378 SQL_HISTORY_ENABLED 2-362
2.379 SQL_TRACE 2-363
2.380 SQL_TRANSPILER 2-364
2.381 SQL92_SECURITY 2-365
2.382 SQLTUNE_CATEGORY 2-365
2.383 STANDBY_DB_PRESERVE_STATES 2-366
2.384 STANDBY_FILE_MANAGEMENT 2-367
2.385 STANDBY_PDB_SOURCE_FILE_DBLINK 2-368
2.386 STANDBY_PDB_SOURCE_FILE_DIRECTORY 2-369
2.387 STAR_TRANSFORMATION_ENABLED 2-369
2.388 STATISTICS_LEVEL 2-370
2.389 STREAMS_POOL_SIZE 2-372
2.390 SYSDATE_AT_DBTIMEZONE 2-373
2.391 TABLESPACE_ENCRYPTION 2-373
2.392 TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM 2-375
2.393 TAPE_ASYNCH_IO 2-376
2.394 TDE_CONFIGURATION 2-377
2.395 TDE_KEY_CACHE 2-379
2.396 TEMP_UNDO_ENABLED 2-380
2.397 THREAD 2-381
2.398 THREADED_EXECUTION 2-382
2.399 TIME_AT_DBTIMEZONE 2-384
2.400 TIMED_OS_STATISTICS 2-385
2.401 TIMED_STATISTICS 2-386
2.402 TIMEZONE_VERSION_UPGRADE_ONLINE 2-387
2.403 TRACE_ENABLED 2-387
2.404 TRACEFILE_IDENTIFIER 2-388
2.405 TRANSACTION_RECOVERY 2-389
2.406 TRANSACTIONS 2-390
2.407 TRANSACTIONS_PER_ROLLBACK_SEGMENT 2-390
2.408 TRUE_CACHE 2-391
2.409 TXN_PRIORITY 2-391
2.410 UNDO_MANAGEMENT 2-392
2.411 UNDO_RETENTION 2-393
2.412 UNDO_TABLESPACE 2-395

2.413 UNIFIED_AUDIT_COMMON_SYSTEMLOG 2-396
2.414 UNIFIED_AUDIT_SYSTEMLOG 2-397
2.415 UNIFORM_LOG_TIMESTAMP_FORMAT 2-398
2.416 USE_DEDICATED_BROKER 2-399
2.417 USE_LARGE_PAGES 2-400
2.418 USER_DUMP_DEST 2-401
2.419 WALLET_ROOT 2-402
2.420 WORKAREA_SIZE_POLICY 2-405
2.421 XML_DB_EVENTS 2-406
2.422 XML_PARAMS 2-407

Part II Static Data Dictionary Views

3 Static Data Dictionary Views: ALL_ALL_TABLES to ALL_OUTLINES

3.1 About Static Data Dictionary Views 3-1
3.2 AWR_PDB_* Views 3-2
3.3 AWR_ROOT_* Views 3-2
3.4 CDB_* Views 3-3
3.5 DBA_HIST_* Views 3-4
3.6 Oracle Database Real Application Security Views 3-4
3.7 Oracle Database Vault Views 3-5
3.8 Oracle Label Security Views 3-5
3.9 Oracle Workspace Manager Views 3-5
3.10 Recovery Catalog Views 3-6
3.11 Static Data Dictionary View Descriptions 3-8
3.12 ALL_ALL_TABLES 3-8
3.13 ALL_ANALYTIC_VIEW_ATTR_CLASS 3-14
3.14 ALL_ANALYTIC_VIEW_ATTR_CLS 3-15
3.15 ALL_ANALYTIC_VIEW_ATTR_CLS_AE 3-15
3.16 ALL_ANALYTIC_VIEW_BAS_MEAS 3-16
3.17 ALL_ANALYTIC_VIEW_BAS_MEAS_AE 3-16
3.18 ALL_ANALYTIC_VIEW_BASE_MEAS 3-17
3.19 ALL_ANALYTIC_VIEW_CALC_MEAS 3-18
3.20 ALL_ANALYTIC_VIEW_CLASS 3-19
3.21 ALL_ANALYTIC_VIEW_CLASS_AE 3-20
3.22 ALL_ANALYTIC_VIEW_CLC_MEAS 3-21
3.23 ALL_ANALYTIC_VIEW_CLC_MEAS_AE 3-21
3.24 ALL_ANALYTIC_VIEW_COLUMNS 3-22
3.25 ALL_ANALYTIC_VIEW_COLUMNS_AE 3-23
3.26 ALL_ANALYTIC_VIEW_DIM_ATRS 3-25

3.27 ALL_ANALYTIC_VIEW_DIM_ATRS_AE 3-25
3.28 ALL_ANALYTIC_VIEW_DIM_ATTRS 3-26
3.29 ALL_ANALYTIC_VIEW_DIM_CLASS 3-27
3.30 ALL_ANALYTIC_VIEW_DIM_CLS 3-28
3.31 ALL_ANALYTIC_VIEW_DIM_CLS_AE 3-28
3.32 ALL_ANALYTIC_VIEW_DIMENSIONS 3-29
3.33 ALL_ANALYTIC_VIEW_DIMS 3-30
3.34 ALL_ANALYTIC_VIEW_DIMS_AE 3-30
3.35 ALL_ANALYTIC_VIEW_FACT_COLS 3-32
3.36 ALL_ANALYTIC_VIEW_FCT_COLS 3-32
3.37 ALL_ANALYTIC_VIEW_FCT_COLS_AE 3-33
3.38 ALL_ANALYTIC_VIEW_HIER_CLASS 3-33
3.39 ALL_ANALYTIC_VIEW_HIER_CLS 3-34
3.40 ALL_ANALYTIC_VIEW_HIER_CLS_AE 3-35
3.41 ALL_ANALYTIC_VIEW_HIERS 3-36
3.42 ALL_ANALYTIC_VIEW_HIERS_AE 3-36
3.43 ALL_ANALYTIC_VIEW_KEYS 3-37
3.44 ALL_ANALYTIC_VIEW_KEYS_AE 3-38
3.45 ALL_ANALYTIC_VIEW_LEVEL_CLASS 3-39
3.46 ALL_ANALYTIC_VIEW_LEVELS 3-40
3.47 ALL_ANALYTIC_VIEW_LEVELS_AE 3-41
3.48 ALL_ANALYTIC_VIEW_LVL_CLS 3-42
3.49 ALL_ANALYTIC_VIEW_LVL_CLS_AE 3-42
3.50 ALL_ANALYTIC_VIEW_LVLGRPS 3-43
3.51 ALL_ANALYTIC_VIEW_LVLGRPS_AE 3-44
3.52 ALL_ANALYTIC_VIEW_MEAS_CLASS 3-45
3.53 ALL_ANALYTIC_VIEW_MEAS_CLS 3-46
3.54 ALL_ANALYTIC_VIEW_MEAS_CLS_AE 3-46
3.55 ALL_ANALYTIC_VIEWS 3-47
3.56 ALL_ANALYTIC_VIEWS_AE 3-48
3.57 ALL_ANNOTATION_VALUES 3-49
3.58 ALL_ANNOTATIONS 3-50
3.59 ALL_ANNOTATIONS_USAGE 3-50
3.60 ALL_APPLY 3-51
3.61 ALL_APPLY_CHANGE_HANDLERS 3-53
3.62 ALL_APPLY_CONFLICT_COLUMNS 3-54
3.63 ALL_APPLY_DML_CONF_HANDLERS 3-55
3.64 ALL_APPLY_DML_HANDLERS 3-56
3.65 ALL_APPLY_ENQUEUE 3-57
3.66 ALL_APPLY_ERROR 3-57
3.67 ALL_APPLY_ERROR_MESSAGES 3-59

3.68 ALL_APPLY_EXECUTE 3-61
3.69 ALL_APPLY_HANDLE_COLLISIONS 3-61
3.70 ALL_APPLY_INSTANTIATED_GLOBAL 3-62
3.71 ALL_APPLY_INSTANTIATED_OBJECTS 3-62
3.72 ALL_APPLY_INSTANTIATED_SCHEMAS 3-63
3.73 ALL_APPLY_KEY_COLUMNS 3-64
3.74 ALL_APPLY_PARAMETERS 3-64
3.75 ALL_APPLY_PROGRESS 3-65
3.76 ALL_APPLY_REPERROR_HANDLERS 3-66
3.77 ALL_APPLY_TABLE_COLUMNS 3-67
3.78 ALL_ARGUMENTS 3-68
3.79 ALL_ASSEMBLIES 3-70
3.80 ALL_ASSOCIATIONS 3-71
3.81 ALL_ATTRIBUTE_DIM_ATTR_CLASS 3-72
3.82 ALL_ATTRIBUTE_DIM_ATTR_CLS 3-73
3.83 ALL_ATTRIBUTE_DIM_ATTR_CLS_AE 3-73
3.84 ALL_ATTRIBUTE_DIM_ATTRS 3-74
3.85 ALL_ATTRIBUTE_DIM_ATTRS_AE 3-75
3.86 ALL_ATTRIBUTE_DIM_CLASS 3-76
3.87 ALL_ATTRIBUTE_DIM_CLASS_AE 3-76
3.88 ALL_ATTRIBUTE_DIM_JN_PTHS 3-77
3.89 ALL_ATTRIBUTE_DIM_JN_PTHS_AE 3-78
3.90 ALL_ATTRIBUTE_DIM_JOIN_PATHS 3-78
3.91 ALL_ATTRIBUTE_DIM_KEYS 3-79
3.92 ALL_ATTRIBUTE_DIM_KEYS_AE 3-80
3.93 ALL_ATTRIBUTE_DIM_LEVEL_ATTRS 3-81
3.94 ALL_ATTRIBUTE_DIM_LEVELS 3-82
3.95 ALL_ATTRIBUTE_DIM_LEVELS_AE 3-83
3.96 ALL_ATTRIBUTE_DIM_LVL_ATRS 3-83
3.97 ALL_ATTRIBUTE_DIM_LVL_ATRS_AE 3-84
3.98 ALL_ATTRIBUTE_DIM_LVL_CLASS 3-85
3.99 ALL_ATTRIBUTE_DIM_LVL_CLS 3-85
3.100 ALL_ATTRIBUTE_DIM_LVL_CLS_AE 3-86
3.101 ALL_ATTRIBUTE_DIM_ORD_ATRS 3-86
3.102 ALL_ATTRIBUTE_DIM_ORD_ATRS_AE 3-87
3.103 ALL_ATTRIBUTE_DIM_ORDER_ATTRS 3-88
3.104 ALL_ATTRIBUTE_DIM_TABLES 3-89
3.105 ALL_ATTRIBUTE_DIM_TABLES_AE 3-90
3.106 ALL_ATTRIBUTE_DIMENSIONS 3-91
3.107 ALL_ATTRIBUTE_DIMENSIONS_AE 3-92
3.108 ALL_ATTRIBUTE_TRANSFORMATIONS 3-93

3.109 ALL_AUDIT_POLICIES 3-94
3.110 ALL_AUDIT_POLICY_COLUMNS 3-96
3.111 ALL_AW_PS 3-96
3.112 ALL_AWS 3-97
3.113 ALL_BASE_TABLE_MVIEWS 3-98
3.114 ALL_BLOCKCHAIN_ROW_VERSION_COLS 3-99
3.115 ALL_BLOCKCHAIN_ROW_VERSION_HISTORY 3-99
3.116 ALL_BLOCKCHAIN_TABLE_CHAINS 3-101
3.117 ALL_BLOCKCHAIN_TABLE_EPOCHS 3-102
3.118 ALL_BLOCKCHAIN_TABLE_HASH_COL_ORDER 3-103
3.119 ALL_BLOCKCHAIN_TABLES 3-104
3.120 ALL_CAPTURE 3-105
3.121 ALL_CAPTURE_EXTRA_ATTRIBUTES 3-108
3.122 ALL_CAPTURE_PARAMETERS 3-108
3.123 ALL_CAPTURE_PREPARED_DATABASE 3-109
3.124 ALL_CAPTURE_PREPARED_SCHEMAS 3-110
3.125 ALL_CAPTURE_PREPARED_TABLES 3-111
3.126 ALL_CATALOG 3-112
3.127 ALL_CERTIFICATES 3-112
3.128 ALL_CLUSTER_HASH_EXPRESSIONS 3-113
3.129 ALL_CLUSTERING_DIMENSIONS 3-113
3.130 ALL_CLUSTERING_JOINS 3-114
3.131 ALL_CLUSTERING_KEYS 3-115
3.132 ALL_CLUSTERING_TABLES 3-116
3.133 ALL_CLUSTERS 3-117
3.134 ALL_CODE_ROLE_PRIVS 3-119
3.135 ALL_COL_COMMENTS 3-120
3.136 ALL_COL_PENDING_STATS 3-120
3.137 ALL_COL_PRIVS 3-121
3.138 ALL_COL_PRIVS_MADE 3-122
3.139 ALL_COL_PRIVS_RECD 3-123
3.140 ALL_COLL_TYPES 3-124
3.141 ALL_CONS_COLUMNS 3-125
3.142 ALL_CONS_OBJ_COLUMNS 3-126
3.143 ALL_CONSTRAINTS 3-127
3.144 ALL_CONTEXT 3-130
3.145 ALL_CREDENTIALS 3-130
3.146 ALL_CUBE_ATTR_VISIBILITY 3-131
3.147 ALL_CUBE_ATTRIBUTES 3-132
3.148 ALL_CUBE_BUILD_PROCESSES 3-134
3.149 ALL_CUBE_CALCULATED_MEMBERS 3-134

3.150 ALL_CUBE_DIM_LEVELS 3-135
3.151 ALL_CUBE_DIM_MODELS 3-136
3.152 ALL_CUBE_DIM_VIEW_COLUMNS 3-136
3.153 ALL_CUBE_DIM_VIEWS 3-137
3.154 ALL_CUBE_DIMENSIONALITY 3-138
3.155 ALL_CUBE_DIMENSIONS 3-139
3.156 ALL_CUBE_HIER_LEVELS 3-140
3.157 ALL_CUBE_HIER_VIEW_COLUMNS 3-140
3.158 ALL_CUBE_HIER_VIEWS 3-141
3.159 ALL_CUBE_HIERARCHIES 3-142
3.160 ALL_CUBE_MEASURES 3-143
3.161 ALL_CUBE_NAMED_BUILD_SPECS 3-144
3.162 ALL_CUBE_SUB_PARTITION_LEVELS 3-145
3.163 ALL_CUBE_VIEW_COLUMNS 3-146
3.164 ALL_CUBE_VIEWS 3-146
3.165 ALL_CUBES 3-147
3.166 ALL_DB_LINKS 3-148
3.167 ALL_DEF_AUDIT_OPTS 3-149
3.168 ALL_DEPENDENCIES 3-150
3.169 ALL_DEQUEUE_QUEUES 3-151
3.170 ALL_DIM_ATTRIBUTES 3-152
3.171 ALL_DIM_CHILD_OF 3-152
3.172 ALL_DIM_HIERARCHIES 3-153
3.173 ALL_DIM_JOIN_KEY 3-154
3.174 ALL_DIM_LEVEL_KEY 3-154
3.175 ALL_DIM_LEVELS 3-155
3.176 ALL_DIMENSIONS 3-156
3.177 ALL_DIRECTORIES 3-156
3.178 ALL_DOMAIN_COLS 3-157
3.179 ALL_DOMAIN_CONSTRAINTS 3-158
3.180 ALL_DOMAINS 3-160
3.181 ALL_EDITION_COMMENTS 3-161
3.182 ALL_EDITIONING_VIEW_COLS 3-162
3.183 ALL_EDITIONING_VIEW_COLS_AE 3-163
3.184 ALL_EDITIONING_VIEWS 3-163
3.185 ALL_EDITIONING_VIEWS_AE 3-164
3.186 ALL_EDITIONS 3-164
3.187 ALL_ENCRYPTED_COLUMNS 3-165
3.188 ALL_ERROR_TRANSLATIONS 3-166
3.189 ALL_ERRORS 3-166
3.190 ALL_ERRORS_AE 3-167

3.191 ALL_EVALUATION_CONTEXT_TABLES 3-168
3.192 ALL_EVALUATION_CONTEXT_VARS 3-169
3.193 ALL_EVALUATION_CONTEXTS 3-170
3.194 ALL_EXPRESSION_STATISTICS 3-170
3.195 ALL_EXTERNAL_LOCATIONS 3-171
3.196 ALL_EXTERNAL_TABLES 3-172
3.197 ALL_GG_AUTO_CDR_COLUMN_GROUPS 3-173
3.198 ALL_GG_AUTO_CDR_COLUMNS 3-174
3.199 ALL_GG_AUTO_CDR_TABLES 3-174
3.200 ALL_GG_INBOUND_PROGRESS 3-176
3.201 ALL_GOLDENGATE_INBOUND 3-177
3.202 ALL_GOLDENGATE_PRIVILEGES 3-177
3.203 ALL_GOLDENGATE_RULES 3-178
3.204 ALL_HEAT_MAP_SEG_HISTOGRAM 3-180
3.205 ALL_HEAT_MAP_SEGMENT 3-180
3.206 ALL_HIER_CLASS 3-181
3.207 ALL_HIER_CLASS_AE 3-182
3.208 ALL_HIER_COLUMNS 3-183
3.209 ALL_HIER_COLUMNS_AE 3-184
3.210 ALL_HIER_HIER_ATTR_CLASS 3-185
3.211 ALL_HIER_HIER_ATTR_CLASS_AE 3-186
3.212 ALL_HIER_HIER_ATTRIBUTES 3-187
3.213 ALL_HIER_HIER_ATTRIBUTES_AE 3-188
3.214 ALL_HIER_JOIN_PATHS 3-189
3.215 ALL_HIER_JOIN_PATHS_AE 3-189
3.216 ALL_HIER_LEVEL_ID_ATTRS 3-190
3.217 ALL_HIER_LEVEL_ID_ATTRS_AE 3-191
3.218 ALL_HIER_LEVELS 3-192
3.219 ALL_HIER_LEVELS_AE 3-192
3.220 ALL_HIERARCHIES 3-193
3.221 ALL_HIERARCHIES_AE 3-194
3.222 ALL_HIST_SAGAS 3-195
3.223 ALL_HISTOGRAMS 3-196
3.224 ALL_HIVE_COLUMNS 3-196
3.225 ALL_HIVE_DATABASES 3-197
3.226 ALL_HIVE_PART_KEY_COLUMNS 3-198
3.227 ALL_HIVE_TAB_PARTITIONS 3-198
3.228 ALL_HIVE_TABLES 3-199
3.229 ALL_IDENTIFIERS 3-200
3.230 ALL_IMMUTABLE_ROW_VERSION_COLS 3-202
3.231 ALL_IMMUTABLE_ROW_VERSION_HISTORY 3-203

3.232 ALL_IMMUTABLE_TABLE_COLUMNS 3-204
3.233 ALL_IMMUTABLE_TABLE_EPOCHS 3-205
3.234 ALL_IMMUTABLE_TABLES 3-206
3.235 ALL_INCOMPLETE_SAGAS 3-207
3.236 ALL_IND_COLUMNS 3-208
3.237 ALL_IND_EXPRESSIONS 3-209
3.238 ALL_IND_PARTITIONS 3-210
3.239 ALL_IND_PENDING_STATS 3-213
3.240 ALL_IND_STATISTICS 3-214
3.241 ALL_IND_SUBPARTITIONS 3-216
3.242 ALL_INDEXES 3-218
3.243 ALL_INDEXTYPE_ARRAYTYPES 3-223
3.244 ALL_INDEXTYPE_COMMENTS 3-224
3.245 ALL_INDEXTYPE_OPERATORS 3-225
3.246 ALL_INDEXTYPES 3-225
3.247 ALL_INTERNAL_TRIGGERS 3-226
3.248 ALL_JAVA_ARGUMENTS 3-227
3.249 ALL_JAVA_CLASSES 3-228
3.250 ALL_JAVA_COMPILER_OPTIONS 3-229
3.251 ALL_JAVA_DERIVATIONS 3-229
3.252 ALL_JAVA_FIELDS 3-230
3.253 ALL_JAVA_IMPLEMENTS 3-231
3.254 ALL_JAVA_INNERS 3-232
3.255 ALL_JAVA_LAYOUTS 3-233
3.256 ALL_JAVA_METHODS 3-234
3.257 ALL_JAVA_NCOMPS 3-235
3.258 ALL_JAVA_RESOLVERS 3-236
3.259 ALL_JAVA_THROWS 3-236
3.260 ALL_JOBS 3-237
3.261 ALL_JOIN_IND_COLUMNS 3-237
3.262 ALL_JSON_COLLECTION_TABLES 3-238
3.263 ALL_JSON_COLLECTIONS 3-239
3.264 ALL_JSON_COLUMNS 3-239
3.265 ALL_JSON_DATAGUIDE_FIELDS 3-241
3.266 ALL_JSON_DATAGUIDES 3-241
3.267 ALL_JSON_DOMAIN_SCHEMA_COLUMNS 3-242
3.268 ALL_JSON_DUALITY_VIEW_LINKS 3-243
3.269 ALL_JSON_DUALITY_VIEW_TAB_COLS 3-244
3.270 ALL_JSON_DUALITY_VIEW_TABS 3-245
3.271 ALL_JSON_DUALITY_VIEWS 3-246
3.272 ALL_JSON_INDEXES 3-247

3.273 ALL_JSON_SCHEMA_COLUMNS 3-248
3.274 ALL_LIBRARIES 3-249
3.275 ALL_LOB_PARTITIONS 3-250
3.276 ALL_LOB_SUBPARTITIONS 3-253
3.277 ALL_LOB_TEMPLATES 3-256
3.278 ALL_LOBS 3-257
3.279 ALL_LOG_GROUP_COLUMNS 3-259
3.280 ALL_LOG_GROUPS 3-260
3.281 ALL_MEASURE_FOLDER_CONTENTS 3-261
3.282 ALL_MEASURE_FOLDER_SUBFOLDERS 3-261
3.283 ALL_MEASURE_FOLDERS 3-262
3.284 ALL_METADATA_PROPERTIES 3-262
3.285 ALL_METHOD_PARAMS 3-263
3.286 ALL_METHOD_RESULTS 3-264
3.287 ALL_MINING_ALGORITHMS 3-265
3.288 ALL_MINING_MODEL_ATTRIBUTES 3-265
3.289 ALL_MINING_MODEL_PARTITIONS 3-267
3.290 ALL_MINING_MODEL_SETTINGS 3-268
3.291 ALL_MINING_MODEL_VIEWS 3-268
3.292 ALL_MINING_MODEL_XFORMS 3-269
3.293 ALL_MINING_MODELS 3-269
3.294 ALL_MLE_ENV_IMPORTS 3-271
3.295 ALL_MLE_ENVS 3-272
3.296 ALL_MLE_MODULES 3-272
3.297 ALL_MLE_PROCEDURES 3-273
3.298 ALL_MVIEW_AGGREGATES 3-275
3.299 ALL_MVIEW_ANALYSIS 3-276
3.300 ALL_MVIEW_COMMENTS 3-277
3.301 ALL_MVIEW_DETAIL_LOGICAL_PARTITION 3-278
3.302 ALL_MVIEW_DETAIL_PARTITION 3-279
3.303 ALL_MVIEW_DETAIL_RELATIONS 3-280
3.304 ALL_MVIEW_DETAIL_SUBPARTITION 3-281
3.305 ALL_MVIEW_JOINS 3-281
3.306 ALL_MVIEW_KEYS 3-282
3.307 ALL_MVIEW_LOGS 3-283
3.308 ALL_MVIEW_REFRESH_TIMES 3-285
3.309 ALL_MVIEWS 3-285
3.310 ALL_NESTED_TABLE_COLS 3-290
3.311 ALL_NESTED_TABLES 3-292
3.312 ALL_OBJ_COLATTRS 3-293
3.313 ALL_OBJECT_TABLES 3-294

3.314 ALL_OBJECTS 3-300
3.315 ALL_OBJECTS_AE 3-302
3.316 ALL_OPANCILLARY 3-304
3.317 ALL_OPARGUMENTS 3-304
3.318 ALL_OPBINDINGS 3-305
3.319 ALL_OPERATOR_COMMENTS 3-306
3.320 ALL_OPERATORS 3-307
3.321 ALL_OUTLINE_HINTS 3-307
3.322 ALL_OUTLINES 3-307

4 Static Data Dictionary Views: ALL_PART_COL_STATISTICS to DATABASE_PROPERTIES

4.1 ALL_PART_COL_STATISTICS 4-1
4.2 ALL_PART_HISTOGRAMS 4-2
4.3 ALL_PART_INDEXES 4-3
4.4 ALL_PART_KEY_COLUMNS 4-6
4.5 ALL_PART_LOBS 4-6
4.6 ALL_PART_TABLES 4-10
4.7 ALL_PARTIAL_DROP_TABS 4-14
4.8 ALL_PENDING_CONV_TABLES 4-15
4.9 ALL_PG_EDGE_RELATIONSHIPS 4-15
4.10 ALL_PG_ELEMENT_LABELS 4-16
4.11 ALL_PG_ELEMENTS 4-17
4.12 ALL_PG_KEYS 4-18
4.13 ALL_PG_LABEL_PROPERTIES 4-18
4.14 ALL_PG_LABELS 4-19
4.15 ALL_PG_PROP_DEFINITIONS 4-20
4.16 ALL_PLSQL_COLL_TYPES 4-21
4.17 ALL_PLSQL_OBJECT_SETTINGS 4-22
4.18 ALL_PLSQL_TYPE_ATTRS 4-23
4.19 ALL_PLSQL_TYPES 4-24
4.20 ALL_POLICIES 4-25
4.21 ALL_POLICY_ATTRIBUTES 4-26
4.22 ALL_POLICY_CONTEXTS 4-27
4.23 ALL_POLICY_GROUPS 4-28
4.24 ALL_PROCEDURES 4-28
4.25 ALL_PROPAGATION 4-30
4.26 ALL_PROPERTY_GRAPHS 4-31
4.27 ALL_QUEUE_EVENT_STREAMS 4-32
4.28 ALL_QUEUE_SCHEDULES 4-32

4.29 ALL_QUEUE_SUBSCRIBERS 4-34
4.30 ALL_QUEUE_TABLES 4-35
4.31 ALL_QUEUES 4-36
4.32 ALL_REFRESH 4-37
4.33 ALL_REFRESH_CHILDREN 4-38
4.34 ALL_REFRESH_DEPENDENCIES 4-39
4.35 ALL_REFS 4-40
4.36 ALL_REGISTERED_MVIEWS 4-41
4.37 ALL_REGISTRY_BANNERS 4-42
4.38 ALL_REPL_DBNAME_MAPPING 4-42
4.39 ALL_REPLICATION_PROCESS_EVENTS 4-42
4.40 ALL_REWRITE_EQUIVALENCES 4-43
4.41 ALL_RULE_SET_RULES 4-44
4.42 ALL_RULE_SETS 4-45
4.43 ALL_RULES 4-45
4.44 ALL_SAGA_BROKERS 4-46
4.45 ALL_SAGA_DETAILS 4-47
4.46 ALL_SAGA_ERRORS 4-48
4.47 ALL_SAGA_FINALIZATION 4-48
4.48 ALL_SAGA_PARTICIPANT_SET 4-49
4.49 ALL_SAGA_PARTICIPANTS 4-50
4.50 ALL_SAGA_PENDING 4-51
4.51 ALL_SAGAS 4-52
4.52 ALL_SCHEDULER_CHAIN_RULES 4-54
4.53 ALL_SCHEDULER_CHAIN_STEPS 4-54
4.54 ALL_SCHEDULER_CHAINS 4-56
4.55 ALL_SCHEDULER_CREDENTIALS 4-56
4.56 ALL_SCHEDULER_DB_DESTS 4-57
4.57 ALL_SCHEDULER_DESTS 4-58
4.58 ALL_SCHEDULER_EXTERNAL_DESTS 4-59
4.59 ALL_SCHEDULER_FILE_WATCHERS 4-59
4.60 ALL_SCHEDULER_GLOBAL_ATTRIBUTE 4-60
4.61 ALL_SCHEDULER_GROUP_MEMBERS 4-61
4.62 ALL_SCHEDULER_GROUPS 4-61
4.63 ALL_SCHEDULER_INCOMPAT_MEMBER 4-62
4.64 ALL_SCHEDULER_INCOMPATS 4-63
4.65 ALL_SCHEDULER_JOB_ARGS 4-63
4.66 ALL_SCHEDULER_JOB_CLASSES 4-64
4.67 ALL_SCHEDULER_JOB_DESTS 4-65
4.68 ALL_SCHEDULER_JOB_LOG 4-66
4.69 ALL_SCHEDULER_JOB_RUN_DETAILS 4-68

4.70 ALL_SCHEDULER_JOBS 4-69
4.71 ALL_SCHEDULER_NOTIFICATIONS 4-73
4.72 ALL_SCHEDULER_PROGRAM_ARGS 4-74
4.73 ALL_SCHEDULER_PROGRAMS 4-75
4.74 ALL_SCHEDULER_REMOTE_DATABASES 4-76
4.75 ALL_SCHEDULER_REMOTE_JOBSTATE 4-77
4.76 ALL_SCHEDULER_RESOURCES 4-78
4.77 ALL_SCHEDULER_RSC_CONSTRAINTS 4-79
4.78 ALL_SCHEDULER_RUNNING_CHAINS 4-79
4.79 ALL_SCHEDULER_RUNNING_JOBS 4-81
4.80 ALL_SCHEDULER_SCHEDULES 4-82
4.81 ALL_SCHEDULER_WINDOW_DETAILS 4-83
4.82 ALL_SCHEDULER_WINDOW_GROUPS 4-84
4.83 ALL_SCHEDULER_WINDOW_LOG 4-84
4.84 ALL_SCHEDULER_WINDOWS 4-85
4.85 ALL_SCHEDULER_WINGROUP_MEMBERS 4-86
4.86 ALL_SEC_RELEVANT_COLS 4-87
4.87 ALL_SECONDARY_OBJECTS 4-87
4.88 ALL_SEQUENCES 4-88
4.89 ALL_SERVICES 4-89
4.90 ALL_SOURCE 4-93
4.91 ALL_SOURCE_AE 4-94
4.92 ALL_SQL_TRANSLATION_PROFILES 4-95
4.93 ALL_SQL_TRANSLATIONS 4-96
4.94 ALL_SQLJ_TYPE_ATTRS 4-97
4.95 ALL_SQLJ_TYPE_METHODS 4-98
4.96 ALL_SQLJ_TYPES 4-99
4.97 ALL_SQLSET 4-100
4.98 ALL_SQLSET_BINDS 4-101
4.99 ALL_SQLSET_PLANS 4-102
4.100 ALL_SQLSET_REFERENCES 4-106
4.101 ALL_SQLSET_STATEMENTS 4-107
4.102 ALL_STAT_EXTENSIONS 4-109
4.103 ALL_STATEMENTS 4-110
4.104 ALL_STORED_SETTINGS 4-111
4.105 ALL_STREAMS_GLOBAL_RULES 4-112
4.106 ALL_STREAMS_MESSAGE_CONSUMERS 4-114
4.107 ALL_STREAMS_NEWLY_SUPPORTED 4-114
4.108 ALL_STREAMS_SCHEMA_RULES 4-115
4.109 ALL_STREAMS_TABLE_RULES 4-116
4.110 ALL_STREAMS_TRANSFORM_FUNCTION 4-118

4.111 ALL_SUBPART_COL_STATISTICS 4-118
4.112 ALL_SUBPART_HISTOGRAMS 4-120
4.113 ALL_SUBPART_KEY_COLUMNS 4-121
4.114 ALL_SUBPARTITION_TEMPLATES 4-121
4.115 ALL_SUMDELTA 4-122
4.116 ALL_SYNC_CAPTURE 4-123
4.117 ALL_SYNC_CAPTURE_PREPARED_TABS 4-123
4.118 ALL_SYNC_CAPTURE_TABLES 4-124
4.119 ALL_SYNONYMS 4-124
4.120 ALL_TAB_COL_STAT_MODELS 4-126
4.121 ALL_TAB_COL_STATISTICS 4-127
4.122 ALL_TAB_COLS 4-128
4.123 ALL_TAB_COLUMNS 4-132
4.124 ALL_TAB_COMMENTS 4-135
4.125 ALL_TAB_HISTGRM_PENDING_STATS 4-136
4.126 ALL_TAB_HISTOGRAMS 4-137
4.127 ALL_TAB_IDENTITY_COLS 4-138
4.128 ALL_TAB_MODIFICATIONS 4-139
4.129 ALL_TAB_PARTITIONS 4-140
4.130 ALL_TAB_PENDING_STATS 4-146
4.131 ALL_TAB_PRIVS 4-147
4.132 ALL_TAB_PRIVS_MADE 4-148
4.133 ALL_TAB_PRIVS_RECD 4-149
4.134 ALL_TAB_STAT_PREFS 4-150
4.135 ALL_TAB_STATISTICS 4-150
4.136 ALL_TAB_STATS_HISTORY 4-152
4.137 ALL_TAB_SUBPARTITIONS 4-153
4.138 ALL_TABLE_ACCESS_STATS 4-157
4.139 ALL_TABLE_VIRTUAL_COLUMNS 4-158
4.140 ALL_TABLES 4-159
4.141 ALL_TRANSFORMATIONS 4-167
4.142 ALL_TRIGGER_COLS 4-168
4.143 ALL_TRIGGER_ORDERING 4-168
4.144 ALL_TRIGGERS 4-169
4.145 ALL_TRIGGERS_AE 4-171
4.146 ALL_TSTZ_TAB_COLS 4-173
4.147 ALL_TSTZ_TABLES 4-174
4.148 ALL_TXEVENTQ_MIGRATION_STATUS 4-175
4.149 ALL_TYPE_ATTRS 4-176
4.150 ALL_TYPE_METHODS 4-177
4.151 ALL_TYPE_VERSIONS 4-178

4.152 ALL_TYPES 4-178
4.153 ALL_UNIFIED_AUDIT_ACTIONS 4-179
4.154 ALL_UNUSED_COL_TABS 4-180
4.155 ALL_UPDATABLE_COLUMNS 4-181
4.156 ALL_USERS 4-181
4.157 ALL_USTATS 4-183
4.158 ALL_VARRAYS 4-184
4.159 ALL_VIEWS 4-184
4.160 ALL_VIEWS_AE 4-186
4.161 ALL_WARNING_SETTINGS 4-188
4.162 ALL_XML_INDEXES 4-189
4.163 ALL_XML_NESTED_TABLES 4-190
4.164 ALL_XML_OUT_OF_LINE_TABLES 4-190
4.165 ALL_XML_SCHEMA_ATTRIBUTES 4-191
4.166 ALL_XML_SCHEMA_COMPLEX_TYPES 4-192
4.167 ALL_XML_SCHEMA_ELEMENTS 4-193
4.168 ALL_XML_SCHEMA_NAMESPACES 4-194
4.169 ALL_XML_SCHEMA_SIMPLE_TYPES 4-195
4.170 ALL_XML_SCHEMA_SUBSTGRP_HEAD 4-195
4.171 ALL_XML_SCHEMA_SUBSTGRP_MBRS 4-196
4.172 ALL_XML_SCHEMAS 4-197
4.173 ALL_XML_TAB_COLS 4-198
4.174 ALL_XML_TABLES 4-199
4.175 ALL_XML_VIEW_COLS 4-200
4.176 ALL_XML_VIEWS 4-201
4.177 ALL_XSTREAM_ADMINISTRATOR 4-202
4.178 ALL_XSTREAM_INBOUND 4-203
4.179 ALL_XSTREAM_INBOUND_PROGRESS 4-204
4.180 ALL_XSTREAM_OUT_SUPPORT_MODE 4-205
4.181 ALL_XSTREAM_OUTBOUND 4-206
4.182 ALL_XSTREAM_OUTBOUND_PROGRESS 4-207
4.183 ALL_XSTREAM_RULES 4-208
4.184 ALL_XSTREAM_TRANSFORMATIONS 4-209
4.185 ALL_XTERNAL_LOC_PARTITIONS 4-210
4.186 ALL_XTERNAL_LOC_SUBPARTITIONS 4-211
4.187 ALL_XTERNAL_PART_TABLES 4-212
4.188 ALL_XTERNAL_TAB_PARTITIONS 4-213
4.189 ALL_XTERNAL_TAB_SUBPARTITIONS 4-214
4.190 ALL_ZONEMAP_MEASURES 4-215
4.191 ALL_ZONEMAPS 4-215
4.192 AUDIT_ACTIONS 4-217

4.193 AUDIT_UNIFIED_CONTEXTS 4-218
4.194 AUDIT_UNIFIED_ENABLED_POLICIES 4-219
4.195 AUDIT_UNIFIED_POLICIES 4-220
4.196 AUDIT_UNIFIED_POLICY_COMMENTS 4-222
4.197 AUDITABLE_SYSTEM_ACTIONS 4-222
4.198 CAT 4-224
4.199 CATALOG 4-224
4.200 CHAINED_ROWS 4-224
4.201 CLIENT_RESULT_CACHE_STATS$ 4-225
4.202 CLU 4-225
4.203 COL 4-226
4.204 COLS 4-226
4.205 DATABASE_EXPORT_OBJECTS 4-226
4.206 DATABASE_PROPERTIES 4-226

5 Static Data Dictionary Views: DBA_2PC_NEIGHBORS to DBA_HIST_JAVA_POOL_ADVICE

5.1 DBA_2PC_NEIGHBORS 5-1
5.2 DBA_2PC_PENDING 5-1
5.3 DBA_ACCHK_EVENTS 5-2
5.4 DBA_ACCHK_EVENTS_SUMMARY 5-3
5.5 DBA_ACCHK_STATISTICS 5-5
5.6 DBA_ACCHK_STATISTICS_SUMMARY 5-6
5.7 DBA_ACL_NAME_MAP 5-8
5.8 DBA_ACTIVITY_CONFIG 5-8
5.9 DBA_ACTIVITY_MVIEW 5-8
5.10 DBA_ACTIVITY_SNAPSHOT_META 5-10
5.11 DBA_ACTIVITY_TABLE 5-11
5.12 DBA_ADDM_FDG_BREAKDOWN 5-13
5.13 DBA_ADDM_FINDINGS 5-13
5.14 DBA_ADDM_INSTANCES 5-15
5.15 DBA_ADDM_PENDING_AUTOTASKS 5-16
5.16 DBA_ADDM_SCHEDULED_AUTOTASKS 5-17
5.17 DBA_ADDM_SYSTEM_DIRECTIVES 5-17
5.18 DBA_ADDM_TASK_DIRECTIVES 5-18
5.19 DBA_ADDM_TASKS 5-18
5.20 DBA_ADVISOR_ACTIONS 5-22
5.21 DBA_ADVISOR_COMMANDS 5-23
5.22 DBA_ADVISOR_DEF_PARAMETERS 5-23
5.23 DBA_ADVISOR_DEFINITIONS 5-25

5.24 DBA_ADVISOR_DIR_DEFINITIONS 5-25
5.25 DBA_ADVISOR_DIR_INSTANCES 5-26
5.26 DBA_ADVISOR_DIR_TASK_INST 5-26
5.27 DBA_ADVISOR_EXEC_PARAMETERS 5-27
5.28 DBA_ADVISOR_EXECUTION_TYPES 5-28
5.29 DBA_ADVISOR_EXECUTIONS 5-28
5.30 DBA_ADVISOR_FDG_BREAKDOWN 5-30
5.31 DBA_ADVISOR_FINDING_NAMES 5-30
5.32 DBA_ADVISOR_FINDINGS 5-31
5.33 DBA_ADVISOR_JOURNAL 5-32
5.34 DBA_ADVISOR_LOG 5-32
5.35 DBA_ADVISOR_OBJECT_TYPES 5-33
5.36 DBA_ADVISOR_OBJECTS 5-34
5.37 DBA_ADVISOR_PARAMETERS 5-36
5.38 DBA_ADVISOR_RATIONALE 5-37
5.39 DBA_ADVISOR_RECOMMENDATIONS 5-38
5.40 DBA_ADVISOR_SQLA_REC_SUM 5-40
5.41 DBA_ADVISOR_SQLA_TABLES 5-41
5.42 DBA_ADVISOR_SQLA_WK_MAP 5-41
5.43 DBA_ADVISOR_SQLA_WK_STMTS 5-42
5.44 DBA_ADVISOR_SQLPLANS 5-44
5.45 DBA_ADVISOR_SQLSTATS 5-46
5.46 DBA_ADVISOR_SQLW_JOURNAL 5-48
5.47 DBA_ADVISOR_SQLW_PARAMETERS 5-49
5.48 DBA_ADVISOR_SQLW_STMTS 5-50
5.49 DBA_ADVISOR_SQLW_SUM 5-52
5.50 DBA_ADVISOR_SQLW_TABLES 5-52
5.51 DBA_ADVISOR_SQLW_TEMPLATES 5-53
5.52 DBA_ADVISOR_TASKS 5-54
5.53 DBA_ADVISOR_TEMPLATES 5-55
5.54 DBA_ADVISOR_USAGE 5-56
5.55 DBA_AIM_PERF_FEATURES 5-56
5.56 DBA_ALERT_HISTORY 5-57
5.57 DBA_ALERT_HISTORY_DETAIL 5-58
5.58 DBA_ALL_TABLES 5-59
5.59 DBA_ANALYTIC_VIEW_ATTR_CLASS 5-60
5.60 DBA_ANALYTIC_VIEW_ATTR_CLS 5-60
5.61 DBA_ANALYTIC_VIEW_ATTR_CLS_AE 5-60
5.62 DBA_ANALYTIC_VIEW_BAS_MEAS 5-60
5.63 DBA_ANALYTIC_VIEW_BAS_MEAS_AE 5-61
5.64 DBA_ANALYTIC_VIEW_BASE_MEAS 5-61

5.65 DBA_ANALYTIC_VIEW_CALC_MEAS 5-61
5.66 DBA_ANALYTIC_VIEW_CLASS 5-61
5.67 DBA_ANALYTIC_VIEW_CLASS_AE 5-62
5.68 DBA_ANALYTIC_VIEW_CLC_MEAS 5-62
5.69 DBA_ANALYTIC_VIEW_CLC_MEAS_AE 5-62
5.70 DBA_ANALYTIC_VIEW_COLUMNS 5-62
5.71 DBA_ANALYTIC_VIEW_COLUMNS_AE 5-63
5.72 DBA_ANALYTIC_VIEW_DIM_ATRS 5-63
5.73 DBA_ANALYTIC_VIEW_DIM_ATRS_AE 5-63
5.74 DBA_ANALYTIC_VIEW_DIM_ATTRS 5-63
5.75 DBA_ANALYTIC_VIEW_DIM_CLASS 5-64
5.76 DBA_ANALYTIC_VIEW_DIM_CLS 5-64
5.77 DBA_ANALYTIC_VIEW_DIM_CLS_AE 5-64
5.78 DBA_ANALYTIC_VIEW_DIMENSIONS 5-64
5.79 DBA_ANALYTIC_VIEW_DIMS 5-65
5.80 DBA_ANALYTIC_VIEW_DIMS_AE 5-65
5.81 DBA_ANALYTIC_VIEW_FACT_COLS 5-65
5.82 DBA_ANALYTIC_VIEW_FCT_COLS 5-65
5.83 DBA_ANALYTIC_VIEW_FCT_COLS_AE 5-66
5.84 DBA_ANALYTIC_VIEW_HIER_CLASS 5-66
5.85 DBA_ANALYTIC_VIEW_HIER_CLS 5-66
5.86 DBA_ANALYTIC_VIEW_HIER_CLS_AE 5-66
5.87 DBA_ANALYTIC_VIEW_HIERS 5-67
5.88 DBA_ANALYTIC_VIEW_HIERS_AE 5-67
5.89 DBA_ANALYTIC_VIEW_KEYS 5-67
5.90 DBA_ANALYTIC_VIEW_KEYS_AE 5-67
5.91 DBA_ANALYTIC_VIEW_LEVEL_CLASS 5-68
5.92 DBA_ANALYTIC_VIEW_LEVELS 5-68
5.93 DBA_ANALYTIC_VIEW_LEVELS_AE 5-68
5.94 DBA_ANALYTIC_VIEW_LVL_CLS 5-68
5.95 DBA_ANALYTIC_VIEW_LVL_CLS_AE 5-69
5.96 DBA_ANALYTIC_VIEW_LVLGRPS 5-69
5.97 DBA_ANALYTIC_VIEW_LVLGRPS_AE 5-69
5.98 DBA_ANALYTIC_VIEW_MEAS_CLASS 5-69
5.99 DBA_ANALYTIC_VIEW_MEAS_CLS 5-70
5.100 DBA_ANALYTIC_VIEW_MEAS_CLS_AE 5-70
5.101 DBA_ANALYTIC_VIEWS 5-70
5.102 DBA_ANALYTIC_VIEWS_AE 5-70
5.103 DBA_ANNOTATION_VALUES 5-71
5.104 DBA_ANNOTATIONS 5-71
5.105 DBA_ANNOTATIONS_USAGE 5-71

5.106 DBA_APP_ERRORS 5-72
5.107 DBA_APP_ERRORS_HISTORY 5-72
5.108 DBA_APP_PATCHES 5-73
5.109 DBA_APP_PDB_STATUS 5-73
5.110 DBA_APP_STATEMENTS 5-73
5.111 DBA_APP_VERSIONS 5-74
5.112 DBA_APPLICATION_ROLES 5-74
5.113 DBA_APPLICATIONS 5-75
5.114 DBA_APPLY 5-75
5.115 DBA_APPLY_CHANGE_HANDLERS 5-76
5.116 DBA_APPLY_CONFLICT_COLUMNS 5-76
5.117 DBA_APPLY_DML_CONF_HANDLERS 5-76
5.118 DBA_APPLY_DML_HANDLERS 5-76
5.119 DBA_APPLY_ENQUEUE 5-77
5.120 DBA_APPLY_ERROR 5-77
5.121 DBA_APPLY_ERROR_MESSAGES 5-77
5.122 DBA_APPLY_EXECUTE 5-78
5.123 DBA_APPLY_HANDLE_COLLISIONS 5-78
5.124 DBA_APPLY_INSTANTIATED_GLOBAL 5-78
5.125 DBA_APPLY_INSTANTIATED_OBJECTS 5-78
5.126 DBA_APPLY_INSTANTIATED_SCHEMAS 5-79
5.127 DBA_APPLY_KEY_COLUMNS 5-79
5.128 DBA_APPLY_OBJECT_DEPENDENCIES 5-79
5.129 DBA_APPLY_PARAMETERS 5-79
5.130 DBA_APPLY_PROGRESS 5-80
5.131 DBA_APPLY_REPERROR_HANDLERS 5-80
5.132 DBA_APPLY_SPILL_TXN 5-80
5.133 DBA_APPLY_TABLE_COLUMNS 5-81
5.134 DBA_APPLY_VALUE_DEPENDENCIES 5-81
5.135 DBA_AQ_AGENT_PRIVS 5-81
5.136 DBA_AQ_AGENTS 5-82
5.137 DBA_ARGUMENTS 5-82
5.138 DBA_ASSEMBLIES 5-82
5.139 DBA_ASSOCIATIONS 5-83
5.140 DBA_ATTRIBUTE_DIM_ATTR_CLASS 5-83
5.141 DBA_ATTRIBUTE_DIM_ATTR_CLS 5-83
5.142 DBA_ATTRIBUTE_DIM_ATTR_CLS_AE 5-83
5.143 DBA_ATTRIBUTE_DIM_ATTRS 5-84
5.144 DBA_ATTRIBUTE_DIM_ATTRS_AE 5-84
5.145 DBA_ATTRIBUTE_DIM_CLASS 5-84
5.146 DBA_ATTRIBUTE_DIM_CLASS_AE 5-84

5.147 DBA_ATTRIBUTE_DIM_JN_PTHS 5-85
5.148 DBA_ATTRIBUTE_DIM_JN_PTHS_AE 5-85
5.149 DBA_ATTRIBUTE_DIM_JOIN_PATHS 5-85
5.150 DBA_ATTRIBUTE_DIM_KEYS 5-85
5.151 DBA_ATTRIBUTE_DIM_KEYS_AE 5-86
5.152 DBA_ATTRIBUTE_DIM_LEVEL_ATTRS 5-86
5.153 DBA_ATTRIBUTE_DIM_LEVELS 5-86
5.154 DBA_ATTRIBUTE_DIM_LEVELS_AE 5-86
5.155 DBA_ATTRIBUTE_DIM_LVL_ATRS 5-87
5.156 DBA_ATTRIBUTE_DIM_LVL_ATRS_AE 5-87
5.157 DBA_ATTRIBUTE_DIM_LVL_CLASS 5-87
5.158 DBA_ATTRIBUTE_DIM_LVL_CLS 5-87
5.159 DBA_ATTRIBUTE_DIM_LVL_CLS_AE 5-88
5.160 DBA_ATTRIBUTE_DIM_ORD_ATRS 5-88
5.161 DBA_ATTRIBUTE_DIM_ORD_ATRS_AE 5-88
5.162 DBA_ATTRIBUTE_DIM_ORDER_ATTRS 5-88
5.163 DBA_ATTRIBUTE_DIM_TABLES 5-89
5.164 DBA_ATTRIBUTE_DIM_TABLES_AE 5-89
5.165 DBA_ATTRIBUTE_DIMENSIONS 5-89
5.166 DBA_ATTRIBUTE_DIMENSIONS_AE 5-89
5.167 DBA_ATTRIBUTE_TRANSFORMATIONS 5-90
5.168 DBA_AUDIT_EXISTS 5-90
5.169 DBA_AUDIT_MGMT_CLEAN_EVENTS 5-93
5.170 DBA_AUDIT_MGMT_CLEANUP_JOBS 5-94
5.171 DBA_AUDIT_MGMT_CONFIG_PARAMS 5-95
5.172 DBA_AUDIT_MGMT_LAST_ARCH_TS 5-96
5.173 DBA_AUDIT_OBJECT 5-97
5.174 DBA_AUDIT_POLICIES 5-99
5.175 DBA_AUDIT_POLICY_COLUMNS 5-100
5.176 DBA_AUDIT_SESSION 5-100
5.177 DBA_AUDIT_STATEMENT 5-102
5.178 DBA_AUDIT_TRAIL 5-105
5.179 DBA_AUTO_CLUSTERING_CONFIG 5-110
5.180 DBA_AUTO_CLUSTERING_RECOMMENDATIONS 5-110
5.181 DBA_AUTO_INDEX_CONFIG 5-112
5.182 DBA_AUTO_MV_ANALYSIS_ACTIONS 5-112
5.183 DBA_AUTO_MV_ANALYSIS_EXECUTIONS 5-113
5.184 DBA_AUTO_MV_ANALYSIS_RECOMMENDATIONS 5-115
5.185 DBA_AUTO_MV_ANALYSIS_REPORT 5-115
5.186 DBA_AUTO_MV_ANALYSIS_TASK 5-115
5.187 DBA_AUTO_MV_CONFIG 5-117

5.188 DBA_AUTO_MV_MAINT_REPORT 5-117
5.189 DBA_AUTO_MV_REFRESH_HISTORY 5-117
5.190 DBA_AUTO_MV_VERIFICATION_REPORT 5-118
5.191 DBA_AUTO_MV_VERIFICATION_STATUS 5-118
5.192 DBA_AUTO_SEGADV_CTL 5-119
5.193 DBA_AUTO_SEGADV_SUMMARY 5-119
5.194 DBA_AUTO_STAT_EXECUTIONS 5-120
5.195 DBA_AUTO_ZONEMAP_CONFIG 5-121
5.196 DBA_AUTOTASK_CLIENT 5-121
5.197 DBA_AUTOTASK_CLIENT_HISTORY 5-122
5.198 DBA_AUTOTASK_CLIENT_JOB 5-123
5.199 DBA_AUTOTASK_JOB_HISTORY 5-123
5.200 DBA_AUTOTASK_OPERATION 5-124
5.201 DBA_AUTOTASK_SCHEDULE 5-124
5.202 DBA_AUTOTASK_SCHEDULE_CONTROL 5-125
5.203 DBA_AUTOTASK_SETTINGS 5-125
5.204 DBA_AUTOTASK_STATUS 5-126
5.205 DBA_AUTOTASK_TASK 5-126
5.206 DBA_AUTOTASK_WINDOW_CLIENTS 5-129
5.207 DBA_AUTOTASK_WINDOW_HISTORY 5-129
5.208 DBA_AW_PS 5-130
5.209 DBA_AWS 5-130
5.210 DBA_BASE_TABLE_MVIEWS 5-130
5.211 DBA_BLOCKCHAIN_ROW_VERSION_COLS 5-131
5.212 DBA_BLOCKCHAIN_ROW_VERSION_HISTORY 5-131
5.213 DBA_BLOCKCHAIN_TABLE_CHAINS 5-131
5.214 DBA_BLOCKCHAIN_TABLE_EPOCHS 5-132
5.215 DBA_BLOCKCHAIN_TABLE_HASH_COL_ORDER 5-132
5.216 DBA_BLOCKCHAIN_TABLES 5-133
5.217 DBA_BLOCKER_RESOLVER_PARAMETERS 5-133
5.218 DBA_BLOCKERS 5-133
5.219 DBA_CAPTURE 5-134
5.220 DBA_CAPTURE_EXTRA_ATTRIBUTES 5-134
5.221 DBA_CAPTURE_PARAMETERS 5-134
5.222 DBA_CAPTURE_PREPARED_DATABASE 5-135
5.223 DBA_CAPTURE_PREPARED_SCHEMAS 5-135
5.224 DBA_CAPTURE_PREPARED_TABLES 5-135
5.225 DBA_CATALOG 5-135
5.226 DBA_CDB_RSRC_PLAN_DIRECTIVES 5-136
5.227 DBA_CDB_RSRC_PLANS 5-137
5.228 DBA_CERTIFICATES 5-137

5.229 DBA_CHANGE_NOTIFICATION_REGS 5-137
5.230 DBA_CHECKED_ROLES 5-138
5.231 DBA_CHECKED_ROLES_PATH 5-139
5.232 DBA_CLU_COLUMNS 5-139
5.233 DBA_CLUSTER_HASH_EXPRESSIONS 5-140
5.234 DBA_CLUSTERING_DIMENSIONS 5-140
5.235 DBA_CLUSTERING_JOINS 5-140
5.236 DBA_CLUSTERING_KEYS 5-141
5.237 DBA_CLUSTERING_TABLES 5-141
5.238 DBA_CLUSTERS 5-141
5.239 DBA_CODE_ROLE_PRIVS 5-142
5.240 DBA_COL_COMMENTS 5-142
5.241 DBA_COL_PENDING_STATS 5-142
5.242 DBA_COL_PRIVS 5-142
5.243 DBA_COLL_TYPES 5-143
5.244 DBA_COMMON_AUDIT_TRAIL 5-143
5.245 DBA_COMPARISON 5-148
5.246 DBA_COMPARISON_COLUMNS 5-149
5.247 DBA_COMPARISON_ROW_DIF 5-149
5.248 DBA_COMPARISON_SCAN 5-150
5.249 DBA_COMPARISON_SCAN_VALUES 5-151
5.250 DBA_CONNECT_ROLE_GRANTEES 5-151
5.251 DBA_CONNECTION_TESTS 5-152
5.252 DBA_CONS_COLUMNS 5-153
5.253 DBA_CONS_OBJ_COLUMNS 5-153
5.254 DBA_CONSTRAINTS 5-153
5.255 DBA_CONTAINER_DATA 5-153
5.256 DBA_CONTEXT 5-154
5.257 DBA_CPOOL_INFO 5-155
5.258 DBA_CPU_USAGE_STATISTICS 5-156
5.259 DBA_CQ_NOTIFICATION_QUERIES 5-157
5.260 DBA_CREDENTIALS 5-157
5.261 DBA_CUBE_ATTR_VISIBILITY 5-158
5.262 DBA_CUBE_ATTRIBUTES 5-158
5.263 DBA_CUBE_BUILD_PROCESSES 5-158
5.264 DBA_CUBE_CALCULATED_MEMBERS 5-158
5.265 DBA_CUBE_DIM_LEVELS 5-159
5.266 DBA_CUBE_DIM_MODELS 5-159
5.267 DBA_CUBE_DIM_VIEW_COLUMNS 5-159
5.268 DBA_CUBE_DIM_VIEWS 5-159
5.269 DBA_CUBE_DIMENSIONALITY 5-160

5.270 DBA_CUBE_DIMENSIONS 5-160
5.271 DBA_CUBE_HIER_LEVELS 5-160
5.272 DBA_CUBE_HIER_VIEW_COLUMNS 5-160
5.273 DBA_CUBE_HIER_VIEWS 5-161
5.274 DBA_CUBE_HIERARCHIES 5-161
5.275 DBA_CUBE_MEASURES 5-161
5.276 DBA_CUBE_NAMED_BUILD_SPECS 5-161
5.277 DBA_CUBE_SUB_PARTITION_LEVELS 5-162
5.278 DBA_CUBE_VIEW_COLUMNS 5-162
5.279 DBA_CUBE_VIEWS 5-162
5.280 DBA_CUBES 5-162
5.281 DBA_DATA_FILES 5-163
5.282 DBA_DATAPUMP_JOBS 5-164
5.283 DBA_DATAPUMP_SESSIONS 5-165
5.284 DBA_DB_LINK_SOURCES 5-166
5.285 DBA_DB_LINKS 5-167
5.286 DBA_DBFS_HS 5-167
5.287 DBA_DBFS_HS_COMMANDS 5-168
5.288 DBA_DBFS_HS_FIXED_PROPERTIES 5-168
5.289 DBA_DBFS_HS_PROPERTIES 5-169
5.290 DBA_DDL_LOCKS 5-169
5.291 DBA_DDL_REGS 5-170
5.292 DBA_DEPENDENCIES 5-171
5.293 DBA_DIGEST_VERIFIERS 5-171
5.294 DBA_DIM_ATTRIBUTES 5-172
5.295 DBA_DIM_CHILD_OF 5-172
5.296 DBA_DIM_HIERARCHIES 5-172
5.297 DBA_DIM_JOIN_KEY 5-172
5.298 DBA_DIM_LEVEL_KEY 5-173
5.299 DBA_DIM_LEVELS 5-173
5.300 DBA_DIMENSIONS 5-173
5.301 DBA_DIRECTORIES 5-173
5.302 DBA_DISCOVERY_SOURCE 5-174
5.303 DBA_DML_LOCKS 5-174
5.304 DBA_DMT_FREE_SPACE 5-175
5.305 DBA_DMT_USED_EXTENTS 5-175
5.306 DBA_DOMAIN_COLS 5-175
5.307 DBA_DOMAIN_CONSTRAINTS 5-176
5.308 DBA_DOMAINS 5-176
5.309 DBA_EDITION_COMMENTS 5-177
5.310 DBA_EDITIONED_TYPES 5-177

5.311 DBA_EDITIONING_VIEW_COLS 5-177
5.312 DBA_EDITIONING_VIEW_COLS_AE 5-178
5.313 DBA_EDITIONING_VIEWS 5-178
5.314 DBA_EDITIONING_VIEWS_AE 5-178
5.315 DBA_EDITIONS 5-178
5.316 DBA_ENABLED_AGGREGATIONS 5-179
5.317 DBA_ENABLED_TRACES 5-179
5.318 DBA_ENCRYPTED_COLUMNS 5-180
5.319 DBA_EPG_DAD_AUTHORIZATION 5-180
5.320 DBA_ERROR_TRANSLATIONS 5-181
5.321 DBA_ERRORS 5-181
5.322 DBA_ERRORS_AE 5-181
5.323 DBA_EVALUATION_CONTEXT_TABLES 5-181
5.324 DBA_EVALUATION_CONTEXT_VARS 5-182
5.325 DBA_EVALUATION_CONTEXTS 5-182
5.326 DBA_EXP_FILES 5-182
5.327 DBA_EXP_OBJECTS 5-182
5.328 DBA_EXP_VERSION 5-183
5.329 DBA_EXPRESSION_STATISTICS 5-183
5.330 DBA_EXTENTS 5-183
5.331 DBA_EXTERNAL_LOCATIONS 5-184
5.332 DBA_EXTERNAL_SCN_ACTIVITY 5-184
5.333 DBA_EXTERNAL_TABLES 5-187
5.334 DBA_FEATURE_USAGE_STATISTICS 5-187
5.335 DBA_FGA_AUDIT_TRAIL 5-188
5.336 DBA_FLASHBACK_ARCHIVE 5-189
5.337 DBA_FLASHBACK_ARCHIVE_TABLES 5-190
5.338 DBA_FLASHBACK_ARCHIVE_TS 5-191
5.339 DBA_FLASHBACK_TXN_REPORT 5-191
5.340 DBA_FLASHBACK_TXN_STATE 5-192
5.341 DBA_FREE_SPACE 5-192
5.342 DBA_FREE_SPACE_COALESCED 5-193
5.343 DBA_GG_AUTO_CDR_COLUMN_GROUPS 5-194
5.344 DBA_GG_AUTO_CDR_COLUMNS 5-194
5.345 DBA_GG_AUTO_CDR_TABLES 5-194
5.346 DBA_GG_INBOUND_PROGRESS 5-195
5.347 DBA_GG_PROC_OBJECT_EXCLUSION 5-195
5.348 DBA_GG_PROCEDURE_ANNOTATION 5-195
5.349 DBA_GG_SUPPORTED_PACKAGES 5-196
5.350 DBA_GG_SUPPORTED_PROCEDURES 5-196
5.351 DBA_GLOBAL_CONTEXT 5-197

5.352 DBA_GOLDENGATE_INBOUND 5-197
5.353 DBA_GOLDENGATE_NOT_UNIQUE 5-197
5.354 DBA_GOLDENGATE_PRIVILEGES 5-198
5.355 DBA_GOLDENGATE_RULES 5-198
5.356 DBA_GOLDENGATE_SUPPORT_MODE 5-198
5.357 DBA_HANG_MANAGER_PARAMETERS 5-200
5.358 DBA_HEAT_MAP_SEG_HISTOGRAM 5-200
5.359 DBA_HEAT_MAP_SEGMENT 5-200
5.360 DBA_HEATMAP_TOP_OBJECTS 5-200
5.361 DBA_HEATMAP_TOP_TABLESPACES 5-201
5.362 DBA_HIER_CLASS 5-202
5.363 DBA_HIER_CLASS_AE 5-202
5.364 DBA_HIER_COLUMNS 5-202
5.365 DBA_HIER_COLUMNS_AE 5-202
5.366 DBA_HIER_HIER_ATTR_CLASS 5-203
5.367 DBA_HIER_HIER_ATTR_CLASS_AE 5-203
5.368 DBA_HIER_HIER_ATTRIBUTES 5-203
5.369 DBA_HIER_HIER_ATTRIBUTES_AE 5-203
5.370 DBA_HIER_JOIN_PATHS 5-204
5.371 DBA_HIER_JOIN_PATHS_AE 5-204
5.372 DBA_HIER_LEVEL_ID_ATTRS 5-204
5.373 DBA_HIER_LEVEL_ID_ATTRS_AE 5-204
5.374 DBA_HIER_LEVELS 5-205
5.375 DBA_HIER_LEVELS_AE 5-205
5.376 DBA_HIERARCHIES 5-205
5.377 DBA_HIERARCHIES_AE 5-205
5.378 DBA_HIGH_WATER_MARK_STATISTICS 5-206
5.379 DBA_HIST_ACTIVE_SESS_HISTORY 5-207
5.380 DBA_HIST_APPLY_SUMMARY 5-213
5.381 DBA_HIST_ASH_SNAPSHOT 5-214
5.382 DBA_HIST_BASELINE 5-215
5.383 DBA_HIST_BASELINE_DETAILS 5-216
5.384 DBA_HIST_BASELINE_METADATA 5-217
5.385 DBA_HIST_BASELINE_TEMPLATE 5-218
5.386 DBA_HIST_BG_EVENT_SUMMARY 5-220
5.387 DBA_HIST_BUFFER_POOL_STAT 5-221
5.388 DBA_HIST_BUFFERED_QUEUES 5-222
5.389 DBA_HIST_BUFFERED_SUBSCRIBERS 5-223
5.390 DBA_HIST_CAPTURE 5-224
5.391 DBA_HIST_CHANNEL_WAITS 5-225
5.392 DBA_HIST_CLUSTER_INTERCON 5-226

5.393 DBA_HIST_COLORED_SQL 5-227
5.394 DBA_HIST_COMP_IOSTAT 5-228
5.395 DBA_HIST_CON_SYS_TIME_MODEL 5-228
5.396 DBA_HIST_CON_SYSMETRIC_HIST 5-229
5.397 DBA_HIST_CON_SYSMETRIC_SUMM 5-230
5.398 DBA_HIST_CON_SYSSTAT 5-231
5.399 DBA_HIST_CON_SYSTEM_EVENT 5-232
5.400 DBA_HIST_CR_BLOCK_SERVER 5-233
5.401 DBA_HIST_CURRENT_BLOCK_SERVER 5-234
5.402 DBA_HIST_DATABASE_INSTANCE 5-235
5.403 DBA_HIST_DATAFILE 5-237
5.404 DBA_HIST_DB_CACHE_ADVICE 5-237
5.405 DBA_HIST_DISPATCHER 5-238
5.406 DBA_HIST_DLM_MISC 5-239
5.407 DBA_HIST_DYN_REMASTER_STATS 5-240
5.408 DBA_HIST_ENQUEUE_STAT 5-241
5.409 DBA_HIST_EVENT_HISTOGRAM 5-242
5.410 DBA_HIST_EVENT_NAME 5-243
5.411 DBA_HIST_FILEMETRIC_HISTORY 5-244
5.412 DBA_HIST_FILESTATXS 5-245
5.413 DBA_HIST_IC_CLIENT_STATS 5-246
5.414 DBA_HIST_IC_DEVICE_STATS 5-247
5.415 DBA_HIST_IM_SEG_STAT 5-248
5.416 DBA_HIST_IM_SEG_STAT_OBJ 5-249
5.417 DBA_HIST_INST_CACHE_TRANSFER 5-249
5.418 DBA_HIST_INSTANCE_RECOVERY 5-252
5.419 DBA_HIST_INTERCONNECT_PINGS 5-254
5.420 DBA_HIST_IOSTAT_DETAIL 5-255
5.421 DBA_HIST_IOSTAT_FILETYPE 5-256
5.422 DBA_HIST_IOSTAT_FILETYPE_NAME 5-257
5.423 DBA_HIST_IOSTAT_FUNCTION 5-258
5.424 DBA_HIST_IOSTAT_FUNCTION_NAME 5-259
5.425 DBA_HIST_JAVA_POOL_ADVICE 5-260

6 Static Data Dictionary Views: DBA_HIST_LATCH to DBA_STORED_SETTINGS

6.1 DBA_HIST_LATCH 6-1
6.2 DBA_HIST_LATCH_CHILDREN 6-2
6.3 DBA_HIST_LATCH_MISSES_SUMMARY 6-3
6.4 DBA_HIST_LATCH_NAME 6-4

6.5 DBA_HIST_LATCH_PARENT 6-5
6.6 DBA_HIST_LIBRARYCACHE 6-6
6.7 DBA_HIST_LOG 6-7
6.8 DBA_HIST_MEM_DYNAMIC_COMP 6-8
6.9 DBA_HIST_MEMORY_RESIZE_OPS 6-10
6.10 DBA_HIST_MEMORY_TARGET_ADVICE 6-11
6.11 DBA_HIST_METRIC_NAME 6-12
6.12 DBA_HIST_MTTR_TARGET_ADVICE 6-12
6.13 DBA_HIST_MUTEX_SLEEP 6-14
6.14 DBA_HIST_OPTIMIZER_ENV 6-14
6.15 DBA_HIST_OPTIMIZER_ENV_DETAILS 6-15
6.16 DBA_HIST_OSSTAT 6-16
6.17 DBA_HIST_OSSTAT_NAME 6-16
6.18 DBA_HIST_PARAMETER 6-17
6.19 DBA_HIST_PARAMETER_NAME 6-18
6.20 DBA_HIST_PDB_IN_SNAP 6-19
6.21 DBA_HIST_PDB_INSTANCE 6-19
6.22 DBA_HIST_PERSISTENT_QMN_CACHE 6-20
6.23 DBA_HIST_PERSISTENT_QUEUES 6-21
6.24 DBA_HIST_PERSISTENT_SUBS 6-23
6.25 DBA_HIST_PGA_TARGET_ADVICE 6-24
6.26 DBA_HIST_PGASTAT 6-26
6.27 DBA_HIST_PLAN_OPERATION_NAME 6-27
6.28 DBA_HIST_PLAN_OPTION_NAME 6-27
6.29 DBA_HIST_PROCESS_MEM_SUMMARY 6-28
6.30 DBA_HIST_PROCESS_WAITTIME 6-29
6.31 DBA_HIST_RECOVERY_PROGRESS 6-29
6.32 DBA_HIST_REPLICATION_TBL_STATS 6-30
6.33 DBA_HIST_REPLICATION_TXN_STATS 6-31
6.34 DBA_HIST_REPORTS 6-32
6.35 DBA_HIST_REPORTS_CONTROL 6-33
6.36 DBA_HIST_REPORTS_DETAILS 6-34
6.37 DBA_HIST_REPORTS_TIMEBANDS 6-35
6.38 DBA_HIST_RESOURCE_LIMIT 6-36
6.39 DBA_HIST_ROWCACHE_SUMMARY 6-37
6.40 DBA_HIST_RSRC_CONSUMER_GROUP 6-38
6.41 DBA_HIST_RSRC_METRIC 6-41
6.42 DBA_HIST_RSRC_PDB_METRIC 6-42
6.43 DBA_HIST_RSRC_PLAN 6-44
6.44 DBA_HIST_RULE_SET 6-46
6.45 DBA_HIST_SAGAS 6-46

6.46 DBA_HIST_SEG_STAT 6-47
6.47 DBA_HIST_SEG_STAT_OBJ 6-50
6.48 DBA_HIST_SERVICE_NAME 6-50
6.49 DBA_HIST_SERVICE_STAT 6-51
6.50 DBA_HIST_SERVICE_WAIT_CLASS 6-52
6.51 DBA_HIST_SESS_SGA_STATS 6-53
6.52 DBA_HIST_SESS_TIME_STATS 6-53
6.53 DBA_HIST_SESSMETRIC_HISTORY 6-54
6.54 DBA_HIST_SGA 6-55
6.55 DBA_HIST_SGA_TARGET_ADVICE 6-56
6.56 DBA_HIST_SGASTAT 6-56
6.57 DBA_HIST_SHARED_POOL_ADVICE 6-57
6.58 DBA_HIST_SHARED_SERVER_SUMMARY 6-58
6.59 DBA_HIST_SNAP_ERROR 6-60
6.60 DBA_HIST_SNAPSHOT 6-61
6.61 DBA_HIST_SQL_BIND_METADATA 6-62
6.62 DBA_HIST_SQL_PLAN 6-63
6.63 DBA_HIST_SQL_SUMMARY 6-65
6.64 DBA_HIST_SQL_WORKAREA_HSTGRM 6-66
6.65 DBA_HIST_SQLBIND 6-67
6.66 DBA_HIST_SQLCOMMAND_NAME 6-68
6.67 DBA_HIST_SQLSTAT 6-69
6.68 DBA_HIST_SQLTEXT 6-74
6.69 DBA_HIST_STAT_NAME 6-74
6.70 DBA_HIST_STREAMS_APPLY_SUM 6-75
6.71 DBA_HIST_STREAMS_CAPTURE 6-77
6.72 DBA_HIST_STREAMS_POOL_ADVICE 6-77
6.73 DBA_HIST_SYS_TIME_MODEL 6-78
6.74 DBA_HIST_SYSMETRIC_HISTORY 6-79
6.75 DBA_HIST_SYSMETRIC_SUMMARY 6-80
6.76 DBA_HIST_SYSSTAT 6-81
6.77 DBA_HIST_SYSTEM_EVENT 6-82
6.78 DBA_HIST_TABLESPACE 6-83
6.79 DBA_HIST_TABLESPACE_STAT 6-83
6.80 DBA_HIST_TBSPC_SPACE_USAGE 6-84
6.81 DBA_HIST_TEMPFILE 6-85
6.82 DBA_HIST_TEMPSTATXS 6-86
6.83 DBA_HIST_THREAD 6-87
6.84 DBA_HIST_TOPLEVELCALL_NAME 6-87
6.85 DBA_HIST_UNDOSTAT 6-88
6.86 DBA_HIST_WAITCLASSMET_HISTORY 6-90

6.87 DBA_HIST_WAITSTAT 6-91
6.88 DBA_HIST_WR_CONTROL 6-92
6.89 DBA_HIST_WR_SETTINGS 6-92
6.90 DBA_HISTOGRAMS 6-93
6.91 DBA_HIVE_COLUMNS 6-93
6.92 DBA_HIVE_DATABASES 6-93
6.93 DBA_HIVE_PART_KEY_COLUMNS 6-94
6.94 DBA_HIVE_TAB_PARTITIONS 6-94
6.95 DBA_HIVE_TABLES 6-94
6.96 DBA_HOST_ACES 6-94
6.97 DBA_HOST_ACLS 6-95
6.98 DBA_IDENTIFIERS 6-95
6.99 DBA_ILMDATAMOVEMENTPOLICIES 6-96
6.100 DBA_ILMEVALUATIONDETAILS 6-97
6.101 DBA_ILMOBJECTS 6-98
6.102 DBA_ILMPARAMETERS 6-100
6.103 DBA_ILMPOLICIES 6-100
6.104 DBA_ILMRESULTS 6-101
6.105 DBA_ILMTASKS 6-102
6.106 DBA_IM_EXPRESSIONS 6-103
6.107 DBA_IMMUTABLE_ROW_VERSION_COLS 6-104
6.108 DBA_IMMUTABLE_ROW_VERSION_HISTORY 6-104
6.109 DBA_IMMUTABLE_TABLE_COLUMNS 6-105
6.110 DBA_IMMUTABLE_TABLE_EPOCHS 6-105
6.111 DBA_IMMUTABLE_TABLES 6-105
6.112 DBA_INCOMPLETE_SAGAS 6-106
6.113 DBA_IND_COLUMNS 6-106
6.114 DBA_IND_EXPRESSIONS 6-106
6.115 DBA_IND_PARTITIONS 6-106
6.116 DBA_IND_PENDING_STATS 6-107
6.117 DBA_IND_STATISTICS 6-107
6.118 DBA_IND_SUBPARTITIONS 6-107
6.119 DBA_INDEX_USAGE 6-107
6.120 DBA_INDEXES 6-109
6.121 DBA_INDEXTYPE_ARRAYTYPES 6-109
6.122 DBA_INDEXTYPE_COMMENTS 6-109
6.123 DBA_INDEXTYPE_OPERATORS 6-109
6.124 DBA_INDEXTYPES 6-110
6.125 DBA_INMEMORY_ADVISOR_RECOMMENDATION 6-110
6.126 DBA_INMEMORY_AIMTASKDETAILS 6-110
6.127 DBA_INMEMORY_AIMTASKS 6-111

6.128 DBA_INTERNAL_TRIGGERS 6-112
6.129 DBA_INVALID_OBJECTS 6-112
6.130 DBA_JAVA_ARGUMENTS 6-114
6.131 DBA_JAVA_CLASSES 6-114
6.132 DBA_JAVA_COMPILER_OPTIONS 6-114
6.133 DBA_JAVA_DERIVATIONS 6-114
6.134 DBA_JAVA_FIELDS 6-115
6.135 DBA_JAVA_IMPLEMENTS 6-115
6.136 DBA_JAVA_INNERS 6-115
6.137 DBA_JAVA_LAYOUTS 6-115
6.138 DBA_JAVA_METHODS 6-116
6.139 DBA_JAVA_NCOMPS 6-116
6.140 DBA_JAVA_POLICY 6-116
6.141 DBA_JAVA_RESOLVERS 6-117
6.142 DBA_JAVA_THROWS 6-117
6.143 DBA_JOBS 6-117
6.144 DBA_JOBS_RUNNING 6-118
6.145 DBA_JOIN_IND_COLUMNS 6-119
6.146 DBA_JOINGROUPS 6-119
6.147 DBA_JSON_COLLECTION_TABLES 6-120
6.148 DBA_JSON_COLLECTIONS 6-121
6.149 DBA_JSON_COLUMNS 6-121
6.150 DBA_JSON_DATAGUIDE_FIELDS 6-121
6.151 DBA_JSON_DATAGUIDES 6-122
6.152 DBA_JSON_DOMAIN_SCHEMA_COLUMNS 6-122
6.153 DBA_JSON_DUALITY_VIEW_LINKS 6-122
6.154 DBA_JSON_DUALITY_VIEW_TAB_COLS 6-123
6.155 DBA_JSON_DUALITY_VIEW_TABS 6-123
6.156 DBA_JSON_DUALITY_VIEWS 6-123
6.157 DBA_JSON_INDEXES 6-124
6.158 DBA_JSON_SCHEMA_COLUMNS 6-124
6.159 DBA_KAFKA_APPLICATIONS 6-124
6.160 DBA_KAFKA_CLUSTERS 6-126
6.161 DBA_KAFKA_LOAD_METRICS 6-127
6.162 DBA_KAFKA_OPS 6-128
6.163 DBA_KAFKA_OPS_RESULTS 6-129
6.164 DBA_KAFKA_PARTITIONS 6-130
6.165 DBA_KGLLOCK 6-131
6.166 DBA_LIBRARIES 6-131
6.167 DBA_LMT_FREE_SPACE 6-131
6.168 DBA_LMT_USED_EXTENTS 6-132

6.169 DBA_LOB_PARTITIONS 6-132
6.170 DBA_LOB_SUBPARTITIONS 6-132
6.171 DBA_LOB_TEMPLATES 6-133
6.172 DBA_LOBS 6-133
6.173 DBA_LOCK 6-133
6.174 DBA_LOCK_INTERNAL 6-134
6.175 DBA_LOCKDOWN_PROFILES 6-134
6.176 DBA_LOCKS 6-136
6.177 DBA_LOG_GROUP_COLUMNS 6-136
6.178 DBA_LOG_GROUPS 6-136
6.179 DBA_LOGMNR_DICTIONARY_BUILDLOG 6-136
6.180 DBA_LOGMNR_LOG 6-137
6.181 DBA_LOGMNR_PURGED_LOG 6-138
6.182 DBA_LOGMNR_SESSION 6-138
6.183 DBA_LOGSTDBY_EVENTS 6-139
6.184 DBA_LOGSTDBY_HISTORY 6-140
6.185 DBA_LOGSTDBY_LOG 6-142
6.186 DBA_LOGSTDBY_NOT_UNIQUE 6-143
6.187 DBA_LOGSTDBY_PARAMETERS 6-144
6.188 DBA_LOGSTDBY_PLSQL_MAP 6-146
6.189 DBA_LOGSTDBY_PLSQL_SUPPORT 6-146
6.190 DBA_LOGSTDBY_PROGRESS 6-147
6.191 DBA_LOGSTDBY_SKIP 6-147
6.192 DBA_LOGSTDBY_SKIP_TRANSACTION 6-148
6.193 DBA_LOGSTDBY_SUPPORT_MODE 6-148
6.194 DBA_LOGSTDBY_UNSUPPORTED 6-149
6.195 DBA_LOGSTDBY_UNSUPPORTED_TABLE 6-150
6.196 DBA_MEASURE_FOLDER_CONTENTS 6-151
6.197 DBA_MEASURE_FOLDER_SUBFOLDERS 6-151
6.198 DBA_MEASURE_FOLDERS 6-152
6.199 DBA_METADATA_PROPERTIES 6-152
6.200 DBA_METHOD_PARAMS 6-152
6.201 DBA_METHOD_RESULTS 6-152
6.202 DBA_MINING_MODEL_ATTRIBUTES 6-153
6.203 DBA_MINING_MODEL_PARTITIONS 6-153
6.204 DBA_MINING_MODEL_SETTINGS 6-153
6.205 DBA_MINING_MODEL_TABLES 6-153
6.206 DBA_MINING_MODEL_VIEWS 6-154
6.207 DBA_MINING_MODEL_XFORMS 6-154
6.208 DBA_MINING_MODELS 6-154
6.209 DBA_MLE_ENV_IMPORTS 6-155

6.210 DBA_MLE_ENVS 6-155
6.211 DBA_MLE_MODULES 6-155
6.212 DBA_MLE_PROCEDURES 6-156
6.213 DBA_MVIEW_AGGREGATES 6-156
6.214 DBA_MVIEW_ANALYSIS 6-157
6.215 DBA_MVIEW_COMMENTS 6-157
6.216 DBA_MVIEW_DETAIL_LOGICAL_PARTITION 6-157
6.217 DBA_MVIEW_DETAIL_PARTITION 6-158
6.218 DBA_MVIEW_DETAIL_RELATIONS 6-158
6.219 DBA_MVIEW_DETAIL_SUBPARTITION 6-158
6.220 DBA_MVIEW_JOINS 6-158
6.221 DBA_MVIEW_KEYS 6-159
6.222 DBA_MVIEW_LOG_FILTER_COLS 6-159
6.223 DBA_MVIEW_LOGS 6-159
6.224 DBA_MVIEW_REFRESH_TIMES 6-159
6.225 DBA_MVIEWS 6-160
6.226 DBA_MVREF_CHANGE_STATS 6-160
6.227 DBA_MVREF_RUN_STATS 6-161
6.228 DBA_MVREF_STATS 6-162
6.229 DBA_MVREF_STATS_PARAMS 6-163
6.230 DBA_MVREF_STATS_SYS_DEFAULTS 6-164
6.231 DBA_MVREF_STMT_STATS 6-164
6.232 DBA_NESTED_TABLE_COLS 6-165
6.233 DBA_NESTED_TABLES 6-165
6.234 DBA_NETWORK_ACL_PRIVILEGES 6-166
6.235 DBA_NETWORK_ACLS 6-166
6.236 DBA_OBJ_AUDIT_OPTS 6-167
6.237 DBA_OBJ_COLATTRS 6-168
6.238 DBA_OBJECT_SIZE 6-169
6.239 DBA_OBJECT_TABLES 6-169
6.240 DBA_OBJECT_USAGE 6-170
6.241 DBA_OBJECTS 6-170
6.242 DBA_OBJECTS_AE 6-171
6.243 DBA_OGG_AUTO_CAPTURED_TABLES 6-171
6.244 DBA_OPANCILLARY 6-171
6.245 DBA_OPARGUMENTS 6-172
6.246 DBA_OPBINDINGS 6-172
6.247 DBA_OPERATOR_COMMENTS 6-172
6.248 DBA_OPERATORS 6-172
6.249 DBA_OPTSTAT_OPERATION_TASKS 6-173
6.250 DBA_OPTSTAT_OPERATIONS 6-174

6.251 DBA_ORPHAN_KEY_TABLE 6-175
6.252 DBA_OUTLINE_HINTS 6-175
6.253 DBA_OUTLINES 6-176
6.254 DBA_OUTSTANDING_ALERTS 6-177
6.255 DBA_PARALLEL_EXECUTE_CHUNKS 6-178
6.256 DBA_PARALLEL_EXECUTE_TASKS 6-179
6.257 DBA_PART_COL_STATISTICS 6-181
6.258 DBA_PART_HISTOGRAMS 6-181
6.259 DBA_PART_INDEXES 6-181
6.260 DBA_PART_KEY_COLUMNS 6-181
6.261 DBA_PART_LOBS 6-182
6.262 DBA_PART_TABLES 6-182
6.263 DBA_PARTIAL_DROP_TABS 6-182
6.264 DBA_PDB_HISTORY 6-182
6.265 DBA_PDB_SAVED_STATES 6-183
6.266 DBA_PDB_SNAPSHOTFILE 6-184
6.267 DBA_PDB_SNAPSHOTS 6-184
6.268 DBA_PDBS 6-185
6.269 DBA_PENDING_CONV_TABLES 6-188
6.270 DBA_PENDING_TRANSACTIONS 6-188
6.271 DBA_PG_EDGE_RELATIONSHIPS 6-188
6.272 DBA_PG_ELEMENT_LABELS 6-189
6.273 DBA_PG_ELEMENTS 6-189
6.274 DBA_PG_KEYS 6-190
6.275 DBA_PG_LABEL_PROPERTIES 6-190
6.276 DBA_PG_LABELS 6-190
6.277 DBA_PG_PROP_DEFINITIONS 6-191
6.278 DBA_PLSQL_COLL_TYPES 6-191
6.279 DBA_PLSQL_OBJECT_SETTINGS 6-191
6.280 DBA_PLSQL_TYPE_ATTRS 6-192
6.281 DBA_PLSQL_TYPES 6-192
6.282 DBA_POLICIES 6-192
6.283 DBA_POLICY_ATTRIBUTES 6-192
6.284 DBA_POLICY_CONTEXTS 6-193
6.285 DBA_POLICY_GROUPS 6-193
6.286 DBA_PRIV_AUDIT_OPTS 6-193
6.287 DBA_PRIV_CAPTURES 6-194
6.288 DBA_PRIVATE_TEMP_TABLES 6-194
6.289 DBA_PROCEDURES 6-195
6.290 DBA_PROFILES 6-195
6.291 DBA_PROPERTY_GRAPHS 6-196

6.292 DBA_PROPAGATION 6-197
6.293 DBA_PROXIES 6-197
6.294 DBA_QUARANTINED_TRANSACTIONS 6-198
6.295 DBA_QUEUE_EVENT_STREAMS 6-199
6.296 DBA_QUEUE_SCHEDULES 6-199
6.297 DBA_QUEUE_SUBSCRIBERS 6-199
6.298 DBA_QUEUE_TABLES 6-199
6.299 DBA_QUEUES 6-200
6.300 DBA_RAT_CAPTURE_SCHEMA_INFO 6-200
6.301 DBA_RCHILD 6-201
6.302 DBA_RECOVERABLE_SCRIPT 6-201
6.303 DBA_RECOVERABLE_SCRIPT_BLOCKS 6-202
6.304 DBA_RECOVERABLE_SCRIPT_ERRORS 6-202
6.305 DBA_RECOVERABLE_SCRIPT_HIST 6-202
6.306 DBA_RECOVERABLE_SCRIPT_PARAMS 6-203
6.307 DBA_RECYCLEBIN 6-203
6.308 DBA_REDEFINITION_ERRORS 6-204
6.309 DBA_REDEFINITION_OBJECTS 6-205
6.310 DBA_REDEFINITION_STATUS 6-206
6.311 DBA_REFRESH 6-207
6.312 DBA_REFRESH_CHILDREN 6-207
6.313 DBA_REFS 6-207
6.314 DBA_REGISTERED_ARCHIVED_LOG 6-207
6.315 DBA_REGISTERED_MVIEWS 6-208
6.316 DBA_REGISTRY 6-208
6.317 DBA_REGISTRY_BACKPORTS 6-209
6.318 DBA_REGISTRY_HIERARCHY 6-210
6.319 DBA_REGISTRY_HISTORY 6-210
6.320 DBA_REGISTRY_LOG 6-211
6.321 DBA_REGISTRY_SCHEMAS 6-211
6.322 DBA_REGISTRY_SQLPATCH 6-212
6.323 DBA_REPAIR_TABLE 6-213
6.324 DBA_REPL_DBNAME_MAPPING 6-214
6.325 DBA_REPLICATION_PROCESS_EVENTS 6-214
6.326 DBA_RESOURCE_INCARNATIONS 6-215
6.327 DBA_RESUMABLE 6-215
6.328 DBA_REWRITE_EQUIVALENCES 6-216
6.329 DBA_RGROUP 6-216
6.330 DBA_ROLE_PRIVS 6-217
6.331 DBA_ROLES 6-218
6.332 DBA_ROLLBACK_SEGS 6-218

6.333 DBA_ROLLING_DATABASES 6-219
6.334 DBA_ROLLING_EVENTS 6-220
6.335 DBA_ROLLING_PARAMETERS 6-221
6.336 DBA_ROLLING_PLAN 6-221
6.337 DBA_ROLLING_STATISTICS 6-222
6.338 DBA_ROLLING_STATUS 6-223
6.339 DBA_ROLLING_SUPPORT_MODE 6-224
6.340 DBA_ROLLING_UNSUPPORTED 6-224
6.341 DBA_RSRC_CATEGORIES 6-225
6.342 DBA_RSRC_CONSUMER_GROUP_PRIVS 6-226
6.343 DBA_RSRC_CONSUMER_GROUPS 6-226
6.344 DBA_RSRC_GROUP_MAPPINGS 6-227
6.345 DBA_RSRC_IO_CALIBRATE 6-227
6.346 DBA_RSRC_MANAGER_SYSTEM_PRIVS 6-228
6.347 DBA_RSRC_MAPPING_PRIORITY 6-228
6.348 DBA_RSRC_PLAN_DIRECTIVES 6-229
6.349 DBA_RSRC_PLANS 6-232
6.350 DBA_RULE_SET_RULES 6-233
6.351 DBA_RULE_SETS 6-233
6.352 DBA_RULES 6-233
6.353 DBA_SAGA_BROKERS 6-234
6.354 DBA_SAGA_DETAILS 6-234
6.355 DBA_SAGA_ERRORS 6-234
6.356 DBA_SAGA_FINALIZATION 6-235
6.357 DBA_SAGA_PARTICIPANT_SET 6-235
6.358 DBA_SAGA_PARTICIPANTS 6-236
6.359 DBA_SAGA_PENDING 6-236
6.360 DBA_SAGAS 6-236
6.361 DBA_SCHEDULER_CHAIN_RULES 6-237
6.362 DBA_SCHEDULER_CHAIN_STEPS 6-237
6.363 DBA_SCHEDULER_CHAINS 6-238
6.364 DBA_SCHEDULER_CREDENTIALS 6-238
6.365 DBA_SCHEDULER_DB_DESTS 6-238
6.366 DBA_SCHEDULER_DESTS 6-239
6.367 DBA_SCHEDULER_EXTERNAL_DESTS 6-239
6.368 DBA_SCHEDULER_FILE_WATCHERS 6-239
6.369 DBA_SCHEDULER_GLOBAL_ATTRIBUTE 6-239
6.370 DBA_SCHEDULER_GROUP_MEMBERS 6-240
6.371 DBA_SCHEDULER_GROUPS 6-240
6.372 DBA_SCHEDULER_IN_MEMORY_TRACE 6-240
6.373 DBA_SCHEDULER_INCOMPAT_MEMBER 6-241

6.374 DBA_SCHEDULER_INCOMPATS 6-241
6.375 DBA_SCHEDULER_JOB_ARGS 6-241
6.376 DBA_SCHEDULER_JOB_CLASSES 6-241
6.377 DBA_SCHEDULER_JOB_DESTS 6-242
6.378 DBA_SCHEDULER_JOB_LOG 6-242
6.379 DBA_SCHEDULER_JOB_ROLES 6-242
6.380 DBA_SCHEDULER_JOB_RUN_DETAILS 6-243
6.381 DBA_SCHEDULER_JOBS 6-244
6.382 DBA_SCHEDULER_NOTIFICATIONS 6-244
6.383 DBA_SCHEDULER_PROGRAM_ARGS 6-244
6.384 DBA_SCHEDULER_PROGRAMS 6-244
6.385 DBA_SCHEDULER_REMOTE_DATABASES 6-245
6.386 DBA_SCHEDULER_REMOTE_JOBSTATE 6-245
6.387 DBA_SCHEDULER_RESOURCES 6-245
6.388 DBA_SCHEDULER_RSC_CONSTRAINTS 6-245
6.389 DBA_SCHEDULER_RUNNING_CHAINS 6-246
6.390 DBA_SCHEDULER_RUNNING_JOBS 6-246
6.391 DBA_SCHEDULER_SCHEDULES 6-246
6.392 DBA_SCHEDULER_WINDOW_DETAILS 6-246
6.393 DBA_SCHEDULER_WINDOW_GROUPS 6-247
6.394 DBA_SCHEDULER_WINDOW_LOG 6-247
6.395 DBA_SCHEDULER_WINDOWS 6-247
6.396 DBA_SCHEDULER_WINGROUP_MEMBERS 6-247
6.397 DBA_SCHEMA_PRIVS 6-248
6.398 DBA_SEC_RELEVANT_COLS 6-248
6.399 DBA_SECONDARY_OBJECTS 6-249
6.400 DBA_SEGMENTS 6-249
6.401 DBA_SEGMENTS_OLD 6-252
6.402 DBA_SENSITIVE_COLUMN_TYPES 6-252
6.403 DBA_SENSITIVE_DATA 6-253
6.404 DBA_SEQUENCES 6-254
6.405 DBA_SERVER_REGISTRY 6-254
6.406 DBA_SERVICES 6-255
6.407 DBA_SOURCE 6-255
6.408 DBA_SOURCE_AE 6-255
6.409 DBA_SQL_ERROR_MITIGATIONS 6-255
6.410 DBA_SQL_FIREWALL_ALLOW_LISTS 6-256
6.411 DBA_SQL_FIREWALL_ALLOWED_IP_ADDR 6-257
6.412 DBA_SQL_FIREWALL_ALLOWED_OS_PROG 6-257
6.413 DBA_SQL_FIREWALL_ALLOWED_OS_USER 6-258
6.414 DBA_SQL_FIREWALL_ALLOWED_SQL 6-258

6.415 DBA_SQL_FIREWALL_CAPTURE_LOGS 6-259
6.416 DBA_SQL_FIREWALL_CAPTURES 6-260
6.417 DBA_SQL_FIREWALL_SESSION_LOGS 6-260
6.418 DBA_SQL_FIREWALL_SQL_LOGS 6-261
6.419 DBA_SQL_FIREWALL_STATUS 6-261
6.420 DBA_SQL_FIREWALL_VIOLATIONS 6-262
6.421 DBA_SQL_MANAGEMENT_CONFIG 6-263
6.422 DBA_SQL_QUARANTINE 6-263
6.423 DBA_SQL_PATCHES 6-264
6.424 DBA_SQL_PLAN_BASELINES 6-265
6.425 DBA_SQL_PLAN_DIR_OBJECTS 6-267
6.426 DBA_SQL_PLAN_DIRECTIVES 6-268
6.427 DBA_SQL_PROFILES 6-269
6.428 DBA_SQL_TRANSLATION_PROFILES 6-270
6.429 DBA_SQL_TRANSLATIONS 6-270
6.430 DBA_SQLJ_TYPE_ATTRS 6-270
6.431 DBA_SQLJ_TYPE_METHODS 6-271
6.432 DBA_SQLJ_TYPES 6-271
6.433 DBA_SQLSET 6-271
6.434 DBA_SQLSET_BINDS 6-271
6.435 DBA_SQLSET_PLANS 6-272
6.436 DBA_SQLSET_REFERENCES 6-272
6.437 DBA_SQLSET_STATEMENTS 6-272
6.438 DBA_SQLTUNE_BINDS 6-274
6.439 DBA_SQLTUNE_PLANS 6-274
6.440 DBA_SQLTUNE_RATIONALE_PLAN 6-277
6.441 DBA_SQLTUNE_STATISTICS 6-278
6.442 DBA_SR_GRP_STATUS 6-279
6.443 DBA_SR_GRP_STATUS_ALL 6-280
6.444 DBA_SR_OBJ 6-282
6.445 DBA_SR_OBJ_ALL 6-282
6.446 DBA_SR_OBJ_STATUS 6-283
6.447 DBA_SR_OBJ_STATUS_ALL 6-284
6.448 DBA_SR_PARTN_OPS 6-285
6.449 DBA_SR_STLOG_EXCEPTIONS 6-286
6.450 DBA_SR_STLOG_STATS 6-286
6.451 DBA_SSCR_CAPTURE 6-287
6.452 DBA_SSCR_RESTORE 6-288
6.453 DBA_STAT_EXTENSIONS 6-289
6.454 DBA_STATEMENTS 6-289
6.455 DBA_STMT_AUDIT_OPTS 6-289

6.456 DBA_STORED_SETTINGS 6-290

7 Static Data Dictionary Views: DBA_STREAMS_ADD_COLUMN to USER_ZONEMAPS

7.1 DBA_STREAMS_ADD_COLUMN 7-1
7.2 DBA_STREAMS_DELETE_COLUMN 7-1
7.3 DBA_STREAMS_GLOBAL_RULES 7-2
7.4 DBA_STREAMS_KEEP_COLUMNS 7-2
7.5 DBA_STREAMS_MESSAGE_CONSUMERS 7-3
7.6 DBA_STREAMS_NEWLY_SUPPORTED 7-3
7.7 DBA_STREAMS_RENAME_COLUMN 7-3
7.8 DBA_STREAMS_RENAME_SCHEMA 7-4
7.9 DBA_STREAMS_RENAME_TABLE 7-4
7.10 DBA_STREAMS_SCHEMA_RULES 7-4
7.11 DBA_STREAMS_TABLE_RULES 7-5
7.12 DBA_STREAMS_TP_COMPONENT 7-5
7.13 DBA_STREAMS_TP_COMPONENT_LINK 7-5
7.14 DBA_STREAMS_TP_COMPONENT_STAT 7-6
7.15 DBA_STREAMS_TP_DATABASE 7-7
7.16 DBA_STREAMS_TP_PATH_BOTTLENECK 7-7
7.17 DBA_STREAMS_TP_PATH_STAT 7-8
7.18 DBA_STREAMS_TRANSFORM_FUNCTION 7-8
7.19 DBA_SUBPART_COL_STATISTICS 7-9
7.20 DBA_SUBPART_HISTOGRAMS 7-9
7.21 DBA_SUBPART_KEY_COLUMNS 7-9
7.22 DBA_SUBPARTITION_TEMPLATES 7-9
7.23 DBA_SUBSCR_REGISTRATIONS 7-10
7.24 DBA_SUPPLEMENTAL_LOGGING 7-11
7.25 DBA_SYNC_CAPTURE 7-12
7.26 DBA_SYNC_CAPTURE_PREPARED_TABS 7-12
7.27 DBA_SYNC_CAPTURE_TABLES 7-12
7.28 DBA_SYNONYMS 7-13
7.29 DBA_SYS_PRIVS 7-13
7.30 DBA_SYS_PRIVS_ALL 7-13
7.31 DBA_TAB_COL_STAT_MODELS 7-14
7.32 DBA_TAB_COL_STATISTICS 7-15
7.33 DBA_TAB_COLS 7-15
7.34 DBA_TAB_COLUMNS 7-18
7.35 DBA_TAB_COMMENTS 7-21
7.36 DBA_TAB_HISTGRM_PENDING_STATS 7-21

7.37 DBA_TAB_HISTOGRAMS 7-22
7.38 DBA_TAB_IDENTITY_COLS 7-22
7.39 DBA_TAB_MODIFICATIONS 7-22
7.40 DBA_TAB_PARTITIONS 7-22
7.41 DBA_TAB_PENDING_STATS 7-23
7.42 DBA_TAB_PRIVS 7-23
7.43 DBA_TAB_STATISTICS 7-24
7.44 DBA_TAB_STAT_PREFS 7-24
7.45 DBA_TAB_STATS_HISTORY 7-24
7.46 DBA_TAB_SUBPARTITIONS 7-24
7.47 DBA_TABLE_ACCESS_STATS 7-25
7.48 DBA_TABLE_VIRTUAL_COLUMNS 7-25
7.49 DBA_TABLES 7-25
7.50 DBA_TABLESPACE_GROUPS 7-26
7.51 DBA_TABLESPACE_THRESHOLDS 7-26
7.52 DBA_TABLESPACE_USAGE_METRICS 7-27
7.53 DBA_TABLESPACES 7-28
7.54 DBA_TEMP_FILES 7-32
7.55 DBA_TEMP_FREE_SPACE 7-32
7.56 DBA_THRESHOLDS 7-33
7.57 DBA_TRANSFORMATIONS 7-34
7.58 DBA_TRIGGER_COLS 7-34
7.59 DBA_TRIGGER_ORDERING 7-35
7.60 DBA_TRIGGERS 7-35
7.61 DBA_TRIGGERS_AE 7-35
7.62 DBA_TS_QUOTAS 7-35
7.63 DBA_TSDP_IMPORT_ERRORS 7-36
7.64 DBA_TSDP_POLICY_CONDITION 7-36
7.65 DBA_TSDP_POLICY_FEATURE 7-37
7.66 DBA_TSDP_POLICY_PARAMETER 7-37
7.67 DBA_TSDP_POLICY_PROTECTION 7-38
7.68 DBA_TSDP_POLICY_TYPE 7-39
7.69 DBA_TSM_DESTINATION 7-39
7.70 DBA_TSM_SOURCE 7-40
7.71 DBA_TSTZ_TAB_COLS 7-40
7.72 DBA_TSTZ_TABLES 7-41
7.73 DBA_TUNE_MVIEW 7-41
7.74 DBA_TXEVENTQ_MIGRATION_STATUS 7-41
7.75 DBA_TYPE_ATTRS 7-42
7.76 DBA_TYPE_METHODS 7-43
7.77 DBA_TYPE_VERSIONS 7-43

7.78 DBA_TYPES 7-43
7.79 DBA_UMF_LINK 7-43
7.80 DBA_UMF_REGISTRATION 7-44
7.81 DBA_UMF_SERVICE 7-45
7.82 DBA_UMF_TOPOLOGY 7-45
7.83 DBA_UNDO_EXTENTS 7-46
7.84 DBA_UNUSED_COL_TABS 7-47
7.85 DBA_UNUSED_GRANTS 7-47
7.86 DBA_UNUSED_OBJPRIVS 7-48
7.87 DBA_UNUSED_OBJPRIVS_PATH 7-49
7.88 DBA_UNUSED_PRIVS 7-50
7.89 DBA_UNUSED_SCHEMA_PRIVS 7-51
7.90 DBA_UNUSED_SCHEMA_PRIVS_PATH 7-52
7.91 DBA_UNUSED_SYSPRIVS 7-53
7.92 DBA_UNUSED_SYSPRIVS_PATH 7-53
7.93 DBA_UNUSED_USERPRIVS 7-54
7.94 DBA_UNUSED_USERPRIVS_PATH 7-55
7.95 DBA_UPDATABLE_COLUMNS 7-56
7.96 DBA_USED_OBJPRIVS 7-56
7.97 DBA_USED_OBJPRIVS_PATH 7-57
7.98 DBA_USED_PRIVS 7-58
7.99 DBA_USED_PUBPRIVS 7-59
7.100 DBA_USED_SCHEMA_PRIVS 7-60
7.101 DBA_USED_SCHEMA_PRIVS_PATH 7-61
7.102 DBA_USED_SYSPRIVS 7-62
7.103 DBA_USED_SYSPRIVS_PATH 7-63
7.104 DBA_USED_USERPRIVS 7-64
7.105 DBA_USED_USERPRIVS_PATH 7-65
7.106 DBA_USERS 7-66
7.107 DBA_USERS_WITH_DEFPWD 7-72
7.108 DBA_USTATS 7-72
7.109 DBA_VARRAYS 7-73
7.110 DBA_VIEWS 7-73
7.111 DBA_VIEWS_AE 7-73
7.112 DBA_WAITERS 7-73
7.113 DBA_WALLET_ACES 7-74
7.114 DBA_WALLET_ACLS 7-74
7.115 DBA_WARNING_SETTINGS 7-75
7.116 DBA_WI_CAPTURE_FILES 7-75
7.117 DBA_WI_JOBS 7-75
7.118 DBA_WI_OBJECTS 7-76

7.119 DBA_WI_PATTERN_ITEMS 7-76
7.120 DBA_WI_PATTERNS 7-77
7.121 DBA_WI_STATEMENTS 7-77
7.122 DBA_WI_TEMPLATE_EXECUTIONS 7-78
7.123 DBA_WI_TEMPLATES 7-78
7.124 DBA_WORKLOAD_ACTIVE_USER_MAP 7-79
7.125 DBA_WORKLOAD_CAPTURE_SQLTEXT 7-79
7.126 DBA_WORKLOAD_CAPTURES 7-80
7.127 DBA_WORKLOAD_CONNECTION_MAP 7-83
7.128 DBA_WORKLOAD_DIV_SUMMARY 7-83
7.129 DBA_WORKLOAD_FILTERS 7-85
7.130 DBA_WORKLOAD_GROUP_ASSIGNMENTS 7-85
7.131 DBA_WORKLOAD_LONG_SQLTEXT 7-86
7.132 DBA_WORKLOAD_REPLAY_CLIENTS 7-86
7.133 DBA_WORKLOAD_REPLAY_DIVERGENCE 7-87
7.134 DBA_WORKLOAD_REPLAY_SCHEDULES 7-88
7.135 DBA_WORKLOAD_REPLAYS 7-89
7.136 DBA_WORKLOAD_SCHEDULE_CAPTURES 7-94
7.137 DBA_WORKLOAD_SCHEDULE_ORDERING 7-96
7.138 DBA_WORKLOAD_SQL_MAP 7-96
7.139 DBA_WORKLOAD_TRACKED_COMMITS 7-97
7.140 DBA_WORKLOAD_USER_MAP 7-97
7.141 DBA_XML_INDEXES 7-98
7.142 DBA_XML_NESTED_TABLES 7-98
7.143 DBA_XML_OUT_OF_LINE_TABLES 7-99
7.144 DBA_XML_SCHEMA_ATTRIBUTES 7-99
7.145 DBA_XML_SCHEMA_COMPLEX_TYPES 7-99
7.146 DBA_XML_SCHEMA_ELEMENTS 7-99
7.147 DBA_XML_SCHEMA_NAMESPACES 7-100
7.148 DBA_XML_SCHEMA_SIMPLE_TYPES 7-100
7.149 DBA_XML_SCHEMA_SUBSTGRP_HEAD 7-100
7.150 DBA_XML_SCHEMA_SUBSTGRP_MBRS 7-100
7.151 DBA_XML_SCHEMAS 7-101
7.152 DBA_XML_TAB_COLS 7-101
7.153 DBA_XML_TABLES 7-101
7.154 DBA_XML_VIEW_COLS 7-101
7.155 DBA_XML_VIEWS 7-102
7.156 DBA_XS_AUDIT_POLICY_OPTIONS 7-102
7.157 DBA_XS_AUDIT_TRAIL 7-102
7.158 DBA_XS_ENABLED_AUDIT_POLICIES 7-104
7.159 DBA_XS_ENB_AUDIT_POLICIES 7-104

7.160 DBA_XSTREAM_ADMINISTRATOR 7-105
7.161 DBA_XSTREAM_INBOUND 7-105
7.162 DBA_XSTREAM_INBOUND_PROGRESS 7-105
7.163 DBA_XSTREAM_OUT_SUPPORT_MODE 7-106
7.164 DBA_XSTREAM_OUTBOUND 7-106
7.165 DBA_XSTREAM_OUTBOUND_PROGRESS 7-106
7.166 DBA_XSTREAM_RULES 7-106
7.167 DBA_XSTREAM_SPLIT_MERGE 7-107
7.168 DBA_XSTREAM_SPLIT_MERGE_HIST 7-108
7.169 DBA_XSTREAM_STMT_HANDLERS 7-110
7.170 DBA_XSTREAM_STMTS 7-110
7.171 DBA_XSTREAM_TRANSFORMATIONS 7-111
7.172 DBA_XTERNAL_LOC_PARTITIONS 7-111
7.173 DBA_XTERNAL_LOC_SUBPARTITIONS 7-111
7.174 DBA_XTERNAL_PART_TABLES 7-112
7.175 DBA_XTERNAL_TAB_PARTITIONS 7-112
7.176 DBA_XTERNAL_TAB_SUBPARTITIONS 7-112
7.177 DBA_ZONEMAP_AUTO_ACTIONS 7-112
7.178 DBA_ZONEMAP_AUTO_FINDINGS 7-113
7.179 DBA_ZONEMAP_MEASURES 7-114
7.180 DBA_ZONEMAPS 7-114
7.181 DBFS_CONTENT 7-114
7.182 DBFS_CONTENT_PROPERTIES 7-116
7.183 DBMS_ALERT_INFO 7-117
7.184 DBMS_KAFKA_APPLICATIONS 7-117
7.185 DBMS_KAFKA_CLUSTERS 7-118
7.186 DBMS_KAFKA_LOAD_METRICS 7-120
7.187 DBMS_KAFKA_MESSAGES 7-121
7.188 DBMS_KAFKA_OPS 7-121
7.189 DBMS_KAFKA_OPS_RESULTS 7-123
7.190 DBMS_KAFKA_PARTITIONS 7-123
7.191 DBMS_KAFKA_SEC_ALLOWED_PROPERTIES 7-124
7.192 DBMS_LOCK_ALLOCATED 7-126
7.193 DBMS_METADATA_PARSE_ITEMS 7-126
7.194 DBMS_METADATA_TRANSFORM_PARAMS 7-127
7.195 DBMS_METADATA_TRANSFORMS 7-127
7.196 DEPTREE 7-128
7.197 DICT 7-128
7.198 DICT_COLUMNS 7-128
7.199 DICTIONARY 7-129
7.200 DICTIONARY_CREDENTIALS_ENCRYPT 7-129

7.201 DM_USER_MODELS 7-129
7.202 DOCUMENT_LINKS 7-131
7.203 ERROR_SIZE 7-132
7.204 EXCEPTIONS 7-132
7.205 FLASHBACK_TRANSACTION_QUERY 7-133
7.206 GLOBAL_CONTEXT 7-133
7.207 GLOBAL_NAME 7-134
7.208 HS_ALL_CAPS 7-134
7.209 HS_ALL_DD 7-134
7.210 HS_ALL_INITS 7-135
7.211 HS_BASE_CAPS 7-135
7.212 HS_BASE_DD 7-135
7.213 HS_CLASS_CAPS 7-136
7.214 HS_CLASS_DD 7-136
7.215 HS_CLASS_INIT 7-136
7.216 HS_FDS_CLASS 7-137
7.217 HS_FDS_INST 7-137
7.218 HS_INST_CAPS 7-137
7.219 HS_INST_DD 7-138
7.220 HS_INST_INIT 7-138
7.221 IDEPTREE 7-139
7.222 IND 7-139
7.223 INDEX_HISTOGRAM 7-139
7.224 INDEX_STATS 7-140
7.225 LOGSTDBY_UNSUPPORTED_TABLES 7-141
7.226 MAP_OBJECT 7-142
7.227 NLS_DATABASE_PARAMETERS 7-142
7.228 NLS_INSTANCE_PARAMETERS 7-142
7.229 NLS_SESSION_PARAMETERS 7-143
7.230 OBJ 7-143
7.231 PATH_VIEW 7-143
7.232 PDB_ALERTS 7-144
7.233 PDB_PLUG_IN_VIOLATIONS 7-144
7.234 PLAN_TABLE 7-145
7.235 PLUGGABLE_SET_CHECK 7-149
7.236 PRODUCT_COMPONENT_VERSION 7-149
7.237 PROXY_USERS 7-150
7.238 PSTUBTBL 7-150
7.239 PUBLIC_DEPENDENCY 7-151
7.240 PUBLICSYN 7-151
7.241 QUEUE_PRIVILEGES 7-151

7.242 RECYCLEBIN 7-152
7.243 REDACTION_COLUMNS 7-152
7.244 REDACTION_EXPRESSIONS 7-153
7.245 REDACTION_POLICIES 7-153
7.246 REDACTION_VALUES_FOR_TYPE_FULL 7-154
7.247 REPORT_COMPONENTS 7-155
7.248 REPORT_FILES 7-155
7.249 REPORT_FORMATS 7-155
7.250 RESOURCE_COST 7-156
7.251 RESOURCE_MAP 7-156
7.252 RESOURCE_VIEW 7-157
7.253 ROLE_ROLE_PRIVS 7-157
7.254 ROLE_SCHEMA_PRIVS 7-158
7.255 ROLE_SYS_PRIVS 7-158
7.256 ROLE_SYS_PRIVS_ALL 7-159
7.257 ROLE_TAB_PRIVS 7-159
7.258 SCHEDULER_BATCH_ERRORS 7-160
7.259 SCHEMA_EXPORT_OBJECTS 7-160
7.260 SEQ 7-161
7.261 SESSION_CONTEXT 7-161
7.262 SESSION_PRIVS 7-161
7.263 SESSION_PRIVS_ALL 7-162
7.264 SESSION_SCHEMA_PRIVS 7-162
7.265 SESSION_ROLES 7-162
7.266 SHARD_RAFT_PARAMETERS 7-163
7.267 SOURCE_SIZE 7-163
7.268 STMT_AUDIT_OPTION_MAP 7-164
7.269 SYN 7-164
7.270 SYNONYMS 7-165
7.271 SYS_OBJECTS 7-165
7.272 SYSCATALOG 7-165
7.273 SYSFILES 7-165
7.274 SYSSEGOBJ 7-165
7.275 SYSTEM_PRIVILEGE_MAP 7-165
7.276 TAB 7-166
7.277 TABLE_EXPORT_OBJECTS 7-166
7.278 TABLE_PRIVILEGE_MAP 7-166
7.279 TABQUOTAS 7-167
7.280 TABS 7-167
7.281 TRUSTED_SERVERS 7-167
7.282 TS_PITR_CHECK 7-168

7.283 TS_PITR_OBJECTS_TO_BE_DROPPED 7-169
7.284 UNI_PLUGGABLE_SET_CHECK 7-169
7.285 UNIFIED_AUDIT_TRAIL 7-170
7.286 USABLE_EDITIONS 7-180
7.287 USER_ADDM_FDG_BREAKDOWN 7-181
7.288 USER_ADDM_FINDINGS 7-181
7.289 USER_ADDM_INSTANCES 7-181
7.290 USER_ADDM_TASK_DIRECTIVES 7-182
7.291 USER_ADDM_TASKS 7-182
7.292 USER_ADVISOR_ACTIONS 7-182
7.293 USER_ADVISOR_DIR_TASK_INST 7-183
7.294 USER_ADVISOR_EXEC_PARAMETERS 7-183
7.295 USER_ADVISOR_EXECUTIONS 7-183
7.296 USER_ADVISOR_FDG_BREAKDOWN 7-183
7.297 USER_ADVISOR_FINDINGS 7-184
7.298 USER_ADVISOR_JOURNAL 7-184
7.299 USER_ADVISOR_LOG 7-184
7.300 USER_ADVISOR_OBJECTS 7-184
7.301 USER_ADVISOR_PARAMETERS 7-185
7.302 USER_ADVISOR_RATIONALE 7-185
7.303 USER_ADVISOR_RECOMMENDATIONS 7-185
7.304 USER_ADVISOR_SQLA_REC_SUM 7-185
7.305 USER_ADVISOR_SQLA_TABLES 7-186
7.306 USER_ADVISOR_SQLA_WK_MAP 7-186
7.307 USER_ADVISOR_SQLA_WK_STMTS 7-186
7.308 USER_ADVISOR_SQLPLANS 7-186
7.309 USER_ADVISOR_SQLSTATS 7-187
7.310 USER_ADVISOR_SQLW_JOURNAL 7-187
7.311 USER_ADVISOR_SQLW_PARAMETERS 7-187
7.312 USER_ADVISOR_SQLW_STMTS 7-187
7.313 USER_ADVISOR_SQLW_SUM 7-188
7.314 USER_ADVISOR_SQLW_TABLES 7-188
7.315 USER_ADVISOR_SQLW_TEMPLATES 7-188
7.316 USER_ADVISOR_TASKS 7-188
7.317 USER_ADVISOR_TEMPLATES 7-189
7.318 USER_ALL_TABLES 7-189
7.319 USER_ANALYTIC_VIEW_ATTR_CLASS 7-189
7.320 USER_ANALYTIC_VIEW_ATTR_CLS 7-189
7.321 USER_ANALYTIC_VIEW_ATTR_CLS_AE 7-190
7.322 USER_ANALYTIC_VIEW_BAS_MEAS 7-190
7.323 USER_ANALYTIC_VIEW_BAS_MEAS_AE 7-190

7.324 USER_ANALYTIC_VIEW_BASE_MEAS 7-190
7.325 USER_ANALYTIC_VIEW_CALC_MEAS 7-191
7.326 USER_ANALYTIC_VIEW_CLASS 7-191
7.327 USER_ANALYTIC_VIEW_CLASS_AE 7-191
7.328 USER_ANALYTIC_VIEW_CLC_MEAS 7-191
7.329 USER_ANALYTIC_VIEW_CLC_MEAS_AE 7-192
7.330 USER_ANALYTIC_VIEW_COLUMNS 7-192
7.331 USER_ANALYTIC_VIEW_COLUMNS_AE 7-192
7.332 USER_ANALYTIC_VIEW_DIM_ATRS 7-192
7.333 USER_ANALYTIC_VIEW_DIM_ATRS_AE 7-193
7.334 USER_ANALYTIC_VIEW_DIM_ATTRS 7-193
7.335 USER_ANALYTIC_VIEW_DIM_CLASS 7-193
7.336 USER_ANALYTIC_VIEW_DIM_CLS 7-193
7.337 USER_ANALYTIC_VIEW_DIM_CLS_AE 7-194
7.338 USER_ANALYTIC_VIEW_DIMENSIONS 7-194
7.339 USER_ANALYTIC_VIEW_DIMS 7-194
7.340 USER_ANALYTIC_VIEW_DIMS_AE 7-194
7.341 USER_ANALYTIC_VIEW_FACT_COLS 7-195
7.342 USER_ANALYTIC_VIEW_FCT_COLS 7-195
7.343 USER_ANALYTIC_VIEW_FCT_COLS_AE 7-195
7.344 USER_ANALYTIC_VIEW_HIER_CLASS 7-195
7.345 USER_ANALYTIC_VIEW_HIER_CLS 7-196
7.346 USER_ANALYTIC_VIEW_HIER_CLS_AE 7-196
7.347 USER_ANALYTIC_VIEW_HIERS 7-196
7.348 USER_ANALYTIC_VIEW_HIERS_AE 7-196
7.349 USER_ANALYTIC_VIEW_KEYS 7-197
7.350 USER_ANALYTIC_VIEW_KEYS_AE 7-197
7.351 USER_ANALYTIC_VIEW_LEVEL_CLASS 7-197
7.352 USER_ANALYTIC_VIEW_LEVELS 7-197
7.353 USER_ANALYTIC_VIEW_LEVELS_AE 7-198
7.354 USER_ANALYTIC_VIEW_LVL_CLS 7-198
7.355 USER_ANALYTIC_VIEW_LVL_CLS_AE 7-198
7.356 USER_ANALYTIC_VIEW_LVLGRPS 7-198
7.357 USER_ANALYTIC_VIEW_LVLGRPS_AE 7-199
7.358 USER_ANALYTIC_VIEW_MEAS_CLASS 7-199
7.359 USER_ANALYTIC_VIEW_MEAS_CLS 7-199
7.360 USER_ANALYTIC_VIEW_MEAS_CLS_AE 7-199
7.361 USER_ANALYTIC_VIEWS 7-200
7.362 USER_ANALYTIC_VIEWS_AE 7-200
7.363 USER_ANNOTATION_VALUES 7-200
7.364 USER_ANNOTATIONS 7-200

7.365 USER_ANNOTATIONS_USAGE 7-201
7.366 USER_APPLICATION_ROLES 7-201
7.367 USER_APPLY_ERROR 7-202
7.368 USER_AQ_AGENT_PRIVS 7-202
7.369 USER_ARGUMENTS 7-202
7.370 USER_ASSEMBLIES 7-203
7.371 USER_ASSOCIATIONS 7-203
7.372 USER_ATTRIBUTE_DIM_ATTR_CLASS 7-203
7.373 USER_ATTRIBUTE_DIM_ATTR_CLS 7-203
7.374 USER_ATTRIBUTE_DIM_ATTR_CLS_AE 7-204
7.375 USER_ATTRIBUTE_DIM_ATTRS 7-204
7.376 USER_ATTRIBUTE_DIM_ATTRS_AE 7-204
7.377 USER_ATTRIBUTE_DIM_CLASS 7-204
7.378 USER_ATTRIBUTE_DIM_CLASS_AE 7-205
7.379 USER_ATTRIBUTE_DIM_JN_PTHS 7-205
7.380 USER_ATTRIBUTE_DIM_JN_PTHS_AE 7-205
7.381 USER_ATTRIBUTE_DIM_JOIN_PATHS 7-205
7.382 USER_ATTRIBUTE_DIM_KEYS 7-206
7.383 USER_ATTRIBUTE_DIM_KEYS_AE 7-206
7.384 USER_ATTRIBUTE_DIM_LEVEL_ATTRS 7-206
7.385 USER_ATTRIBUTE_DIM_LEVELS 7-206
7.386 USER_ATTRIBUTE_DIM_LEVELS_AE 7-207
7.387 USER_ATTRIBUTE_DIM_LVL_ATRS 7-207
7.388 USER_ATTRIBUTE_DIM_LVL_ATRS_AE 7-207
7.389 USER_ATTRIBUTE_DIM_LVL_CLASS 7-207
7.390 USER_ATTRIBUTE_DIM_LVL_CLS 7-208
7.391 USER_ATTRIBUTE_DIM_LVL_CLS_AE 7-208
7.392 USER_ATTRIBUTE_DIM_ORD_ATRS 7-208
7.393 USER_ATTRIBUTE_DIM_ORD_ATRS_AE 7-208
7.394 USER_ATTRIBUTE_DIM_ORDER_ATTRS 7-209
7.395 USER_ATTRIBUTE_DIM_TABLES 7-209
7.396 USER_ATTRIBUTE_DIM_TABLES_AE 7-209
7.397 USER_ATTRIBUTE_DIMENSIONS 7-209
7.398 USER_ATTRIBUTE_DIMENSIONS_AE 7-210
7.399 USER_ATTRIBUTE_TRANSFORMATIONS 7-210
7.400 USER_AUDIT_OBJECT 7-210
7.401 USER_AUDIT_POLICIES 7-211
7.402 USER_AUDIT_POLICY_COLUMNS 7-211
7.403 USER_AUDIT_SESSION 7-212
7.404 USER_AUDIT_STATEMENT 7-212
7.405 USER_AUDIT_TRAIL 7-212

7.406 USER_AW_PS 7-213
7.407 USER_AWS 7-213
7.408 USER_BASE_TABLE_MVIEWS 7-213
7.409 USER_BLOCKCHAIN_ROW_VERSION_COLS 7-213
7.410 USER_BLOCKCHAIN_ROW_VERSION_HISTORY 7-214
7.411 USER_BLOCKCHAIN_TABLE_CHAINS 7-214
7.412 USER_BLOCKCHAIN_TABLE_EPOCHS 7-215
7.413 USER_BLOCKCHAIN_TABLE_HASH_COL_ORDER 7-215
7.414 USER_BLOCKCHAIN_TABLES 7-215
7.415 USER_CATALOG 7-216
7.416 USER_CERTIFICATES 7-216
7.417 USER_CHANGE_NOTIFICATION_REGS 7-216
7.418 USER_CLU_COLUMNS 7-216
7.419 USER_CLUSTER_HASH_EXPRESSIONS 7-217
7.420 USER_CLUSTERING_DIMENSIONS 7-217
7.421 USER_CLUSTERING_JOINS 7-217
7.422 USER_CLUSTERING_KEYS 7-218
7.423 USER_CLUSTERING_TABLES 7-218
7.424 USER_CLUSTERS 7-218
7.425 USER_CODE_ROLE_PRIVS 7-219
7.426 USER_COL_COMMENTS 7-219
7.427 USER_COL_PENDING_STATS 7-219
7.428 USER_COL_PRIVS 7-219
7.429 USER_COL_PRIVS_MADE 7-220
7.430 USER_COL_PRIVS_RECD 7-220
7.431 USER_COLL_TYPES 7-220
7.432 USER_COMPARISON 7-220
7.433 USER_COMPARISON_COLUMNS 7-221
7.434 USER_COMPARISON_ROW_DIF 7-221
7.435 USER_COMPARISON_SCAN 7-221
7.436 USER_COMPARISON_SCAN_VALUES 7-221
7.437 USER_CONS_COLUMNS 7-222
7.438 USER_CONS_OBJ_COLUMNS 7-222
7.439 USER_CONSTRAINTS 7-222
7.440 USER_CQ_NOTIFICATION_QUERIES 7-222
7.441 USER_CREDENTIALS 7-223
7.442 USER_CUBE_ATTR_VISIBILITY 7-223
7.443 USER_CUBE_ATTRIBUTES 7-223
7.444 USER_CUBE_BUILD_PROCESSES 7-223
7.445 USER_CUBE_CALCULATED_MEMBERS 7-224
7.446 USER_CUBE_DIM_LEVELS 7-224

7.447 USER_CUBE_DIM_MODELS 7-224
7.448 USER_CUBE_DIM_VIEW_COLUMNS 7-224
7.449 USER_CUBE_DIM_VIEWS 7-225
7.450 USER_CUBE_DIMENSIONALITY 7-225
7.451 USER_CUBE_DIMENSIONS 7-225
7.452 USER_CUBE_HIER_LEVELS 7-225
7.453 USER_CUBE_HIER_VIEW_COLUMNS 7-226
7.454 USER_CUBE_HIER_VIEWS 7-226
7.455 USER_CUBE_HIERARCHIES 7-226
7.456 USER_CUBE_MEASURES 7-226
7.457 USER_CUBE_NAMED_BUILD_SPECS 7-227
7.458 USER_CUBE_SUB_PARTITION_LEVELS 7-227
7.459 USER_CUBE_VIEW_COLUMNS 7-227
7.460 USER_CUBE_VIEWS 7-227
7.461 USER_CUBES 7-228
7.462 USER_DATAPUMP_JOBS 7-228
7.463 USER_DB_LINKS 7-228
7.464 USER_DBFS_HS 7-228
7.465 USER_DBFS_HS_COMMANDS 7-229
7.466 USER_DBFS_HS_FILES 7-229
7.467 USER_DBFS_HS_FIXED_PROPERTIES 7-229
7.468 USER_DBFS_HS_PROPERTIES 7-230
7.469 USER_DDL_REGS 7-230
7.470 USER_DEPENDENCIES 7-230
7.471 USER_DIM_ATTRIBUTES 7-231
7.472 USER_DIM_CHILD_OF 7-231
7.473 USER_DIM_HIERARCHIES 7-231
7.474 USER_DIM_JOIN_KEY 7-231
7.475 USER_DIM_LEVEL_KEY 7-232
7.476 USER_DIM_LEVELS 7-232
7.477 USER_DIMENSIONS 7-232
7.478 USER_DOMAIN_COLS 7-232
7.479 USER_DOMAIN_CONSTRAINTS 7-233
7.480 USER_DOMAINS 7-233
7.481 USER_EDITIONED_TYPES 7-234
7.482 USER_EDITIONING_VIEW_COLS 7-234
7.483 USER_EDITIONING_VIEW_COLS_AE 7-234
7.484 USER_EDITIONING_VIEWS 7-234
7.485 USER_EDITIONING_VIEWS_AE 7-235
7.486 USER_ENCRYPTED_COLUMNS 7-235
7.487 USER_EPG_DAD_AUTHORIZATION 7-235

7.488 USER_ERROR_TRANSLATIONS 7-235
7.489 USER_ERRORS 7-236
7.490 USER_ERRORS_AE 7-236
7.491 USER_EVALUATION_CONTEXT_TABLES 7-236
7.492 USER_EVALUATION_CONTEXT_VARS 7-236
7.493 USER_EVALUATION_CONTEXTS 7-237
7.494 USER_EXPRESSION_STATISTICS 7-237
7.495 USER_EXTENTS 7-237
7.496 USER_EXTERNAL_LOCATIONS 7-237
7.497 USER_EXTERNAL_TABLES 7-238
7.498 USER_FLASHBACK_ARCHIVE 7-238
7.499 USER_FLASHBACK_ARCHIVE_TABLES 7-238
7.500 USER_FLASHBACK_TXN_REPORT 7-239
7.501 USER_FLASHBACK_TXN_STATE 7-239
7.502 USER_FREE_SPACE 7-239
7.503 USER_GOLDENGATE_PRIVILEGES 7-239
7.504 USER_HEAT_MAP_SEG_HISTOGRAM 7-240
7.505 USER_HEAT_MAP_SEGMENT 7-240
7.506 USER_HIER_CLASS 7-240
7.507 USER_HIER_CLASS_AE 7-240
7.508 USER_HIER_COLUMNS 7-241
7.509 USER_HIER_COLUMNS_AE 7-241
7.510 USER_HIER_HIER_ATTR_CLASS 7-241
7.511 USER_HIER_HIER_ATTR_CLASS_AE 7-241
7.512 USER_HIER_HIER_ATTRIBUTES 7-242
7.513 USER_HIER_HIER_ATTRIBUTES_AE 7-242
7.514 USER_HIER_JOIN_PATHS 7-242
7.515 USER_HIER_JOIN_PATHS_AE 7-242
7.516 USER_HIER_LEVEL_ID_ATTRS 7-243
7.517 USER_HIER_LEVEL_ID_ATTRS_AE 7-243
7.518 USER_HIER_LEVELS 7-243
7.519 USER_HIER_LEVELS_AE 7-243
7.520 USER_HIERARCHIES 7-244
7.521 USER_HIERARCHIES_AE 7-244
7.522 USER_HIST_SAGAS 7-244
7.523 USER_HISTOGRAMS 7-245
7.524 USER_HIVE_COLUMNS 7-245
7.525 USER_HIVE_DATABASES 7-245
7.526 USER_HIVE_PART_KEY_COLUMNS 7-245
7.527 USER_HIVE_TAB_PARTITIONS 7-246
7.528 USER_HIVE_TABLES 7-246

7.529 USER_HOST_ACES 7-246
7.530 USER_IDENTIFIERS 7-247
7.531 USER_ILMDATAMOVEMENTPOLICIES 7-247
7.532 USER_ILMEVALUATIONDETAILS 7-247
7.533 USER_ILMOBJECTS 7-248
7.534 USER_ILMPOLICIES 7-248
7.535 USER_ILMRESULTS 7-249
7.536 USER_ILMTASKS 7-249
7.537 USER_IM_EXPRESSIONS 7-249
7.538 USER_IMMUTABLE_ROW_VERSION_COLS 7-250
7.539 USER_IMMUTABLE_ROW_VERSION_HISTORY 7-250
7.540 USER_IMMUTABLE_TABLE_COLUMNS 7-251
7.541 USER_IMMUTABLE_TABLE_EPOCHS 7-251
7.542 USER_IMMUTABLE_TABLES 7-251
7.543 USER_INCOMPLETE_SAGAS 7-252
7.544 USER_IND_COLUMNS 7-252
7.545 USER_IND_EXPRESSIONS 7-252
7.546 USER_IND_PARTITIONS 7-252
7.547 USER_IND_PENDING_STATS 7-253
7.548 USER_IND_STATISTICS 7-253
7.549 USER_IND_SUBPARTITIONS 7-253
7.550 USER_INDEXES 7-254
7.551 USER_INDEXTYPE_ARRAYTYPES 7-254
7.552 USER_INDEXTYPE_COMMENTS 7-254
7.553 USER_INDEXTYPE_OPERATORS 7-254
7.554 USER_INDEXTYPES 7-255
7.555 USER_INTERNAL_TRIGGERS 7-255
7.556 USER_JAVA_ARGUMENTS 7-255
7.557 USER_JAVA_CLASSES 7-255
7.558 USER_JAVA_COMPILER_OPTIONS 7-256
7.559 USER_JAVA_DERIVATIONS 7-256
7.560 USER_JAVA_FIELDS 7-256
7.561 USER_JAVA_IMPLEMENTS 7-257
7.562 USER_JAVA_INNERS 7-257
7.563 USER_JAVA_LAYOUTS 7-257
7.564 USER_JAVA_METHODS 7-257
7.565 USER_JAVA_NCOMPS 7-258
7.566 USER_JAVA_POLICY 7-258
7.567 USER_JAVA_RESOLVERS 7-258
7.568 USER_JAVA_THROWS 7-258
7.569 USER_JOBS 7-259

7.570 USER_JOIN_IND_COLUMNS 7-259
7.571 USER_JOINGROUPS 7-259
7.572 USER_JSON_COLLECTION_TABLES 7-260
7.573 USER_JSON_COLLECTIONS 7-260
7.574 USER_JSON_COLUMNS 7-260
7.575 USER_JSON_DATAGUIDE_FIELDS 7-261
7.576 USER_JSON_DATAGUIDES 7-261
7.577 USER_JSON_DOMAIN_SCHEMA_COLUMNS 7-261
7.578 USER_JSON_DUALITY_VIEW_LINKS 7-262
7.579 USER_JSON_DUALITY_VIEW_TAB_COLS 7-262
7.580 USER_JSON_DUALITY_VIEW_TABS 7-262
7.581 USER_JSON_DUALITY_VIEWS 7-263
7.582 USER_JSON_INDEXES 7-263
7.583 USER_JSON_SCHEMA_COLUMNS 7-264
7.584 USER_KAFKA_APPLICATIONS 7-264
7.585 USER_KAFKA_CLUSTERS 7-264
7.586 USER_KAFKA_LOAD_METRICS 7-265
7.587 USER_KAFKA_MESSAGES 7-265
7.588 USER_KAFKA_OPS 7-266
7.589 USER_KAFKA_OPS_RESULTS 7-267
7.590 USER_KAFKA_PARTITIONS 7-267
7.591 USER_LIBRARIES 7-268
7.592 USER_LOB_PARTITIONS 7-268
7.593 USER_LOB_SUBPARTITIONS 7-268
7.594 USER_LOB_TEMPLATES 7-268
7.595 USER_LOBS 7-269
7.596 USER_LOG_GROUP_COLUMNS 7-269
7.597 USER_LOG_GROUPS 7-269
7.598 USER_MEASURE_FOLDER_CONTENTS 7-269
7.599 USER_MEASURE_FOLDER_SUBFOLDERS 7-270
7.600 USER_MEASURE_FOLDERS 7-270
7.601 USER_METADATA_PROPERTIES 7-270
7.602 USER_METHOD_PARAMS 7-270
7.603 USER_METHOD_RESULTS 7-271
7.604 USER_MINING_MODEL_ATTRIBUTES 7-271
7.605 USER_MINING_MODEL_PARTITIONS 7-271
7.606 USER_MINING_MODEL_SETTINGS 7-272
7.607 USER_MINING_MODEL_VIEWS 7-272
7.608 USER_MINING_MODEL_XFORMS 7-272
7.609 USER_MINING_MODELS 7-272
7.610 USER_MLE_ENV_IMPORTS 7-273

7.611 USER_MLE_ENVS 7-273
7.612 USER_MLE_MODULES 7-273
7.613 USER_MLE_PROCEDURES 7-274
7.614 USER_MVIEW_AGGREGATES 7-274
7.615 USER_MVIEW_ANALYSIS 7-275
7.616 USER_MVIEW_COMMENTS 7-275
7.617 USER_MVIEW_DETAIL_LOGICAL_PARTITION 7-275
7.618 USER_MVIEW_DETAIL_PARTITION 7-276
7.619 USER_MVIEW_DETAIL_RELATIONS 7-276
7.620 USER_MVIEW_DETAIL_SUBPARTITION 7-276
7.621 USER_MVIEW_JOINS 7-276
7.622 USER_MVIEW_KEYS 7-277
7.623 USER_MVIEW_LOGS 7-277
7.624 USER_MVIEW_REFRESH_TIMES 7-277
7.625 USER_MVIEWS 7-277
7.626 USER_MVREF_CHANGE_STATS 7-278
7.627 USER_MVREF_RUN_STATS 7-278
7.628 USER_MVREF_STATS 7-278
7.629 USER_MVREF_STATS_PARAMS 7-279
7.630 USER_MVREF_STATS_SYS_DEFAULTS 7-279
7.631 USER_MVREF_STMT_STATS 7-279
7.632 USER_NESTED_TABLE_COLS 7-279
7.633 USER_NESTED_TABLES 7-280
7.634 USER_NETWORK_ACL_PRIVILEGES 7-280
7.635 USER_OBJ_AUDIT_OPTS 7-281
7.636 USER_OBJ_COLATTRS 7-281
7.637 USER_OBJECT_SIZE 7-281
7.638 USER_OBJECT_TABLES 7-282
7.639 USER_OBJECT_USAGE 7-282
7.640 USER_OBJECTS 7-282
7.641 USER_OBJECTS_AE 7-282
7.642 USER_OGG_AUTO_CAPTURED_TABLES 7-283
7.643 USER_OPANCILLARY 7-283
7.644 USER_OPARGUMENTS 7-283
7.645 USER_OPBINDINGS 7-283
7.646 USER_OPERATOR_COMMENTS 7-284
7.647 USER_OPERATORS 7-284
7.648 USER_OUTLINE_HINTS 7-284
7.649 USER_OUTLINES 7-284
7.650 USER_PARALLEL_EXECUTE_CHUNKS 7-285
7.651 USER_PARALLEL_EXECUTE_TASKS 7-285

7.652 USER_PART_COL_STATISTICS 7-285
7.653 USER_PART_HISTOGRAMS 7-285
7.654 USER_PART_INDEXES 7-286
7.655 USER_PART_KEY_COLUMNS 7-286
7.656 USER_PART_LOBS 7-286
7.657 USER_PART_TABLES 7-286
7.658 USER_PARTIAL_DROP_TABS 7-287
7.659 USER_PASSWORD_LIMITS 7-287
7.660 USER_PENDING_CONV_TABLES 7-287
7.661 USER_PG_EDGE_RELATIONSHIPS 7-287
7.662 USER_PG_ELEMENT_LABELS 7-288
7.663 USER_PG_ELEMENTS 7-288
7.664 USER_PG_KEYS 7-289
7.665 USER_PG_LABEL_PROPERTIES 7-289
7.666 USER_PG_LABELS 7-289
7.667 USER_PG_PROP_DEFINITIONS 7-290
7.668 USER_PLSQL_COLL_TYPES 7-290
7.669 USER_PLSQL_OBJECT_SETTINGS 7-290
7.670 USER_PLSQL_TYPE_ATTRS 7-291
7.671 USER_PLSQL_TYPES 7-291
7.672 USER_POLICIES 7-291
7.673 USER_POLICY_ATTRIBUTES 7-291
7.674 USER_POLICY_CONTEXTS 7-292
7.675 USER_POLICY_GROUPS 7-292
7.676 USER_PRIVATE_TEMP_TABLES 7-292
7.677 USER_PRIVILEGE_MAP 7-292
7.678 USER_PROCEDURES 7-293
7.679 USER_PROPERTY_GRAPHS 7-293
7.680 USER_PROXIES 7-293
7.681 USER_QUEUE_EVENT_STREAMS 7-294
7.682 USER_QUEUE_SCHEDULES 7-294
7.683 USER_QUEUE_SUBSCRIBERS 7-294
7.684 USER_QUEUE_TABLES 7-294
7.685 USER_QUEUES 7-295
7.686 USER_RECYCLEBIN 7-295
7.687 USER_REFRESH 7-295
7.688 USER_REFRESH_CHILDREN 7-295
7.689 USER_REFS 7-296
7.690 USER_REGISTERED_MVIEWS 7-296
7.691 USER_REGISTRY 7-296
7.692 USER_RESOURCE_LIMITS 7-296

7.693 USER_RESUMABLE 7-297
7.694 USER_REWRITE_EQUIVALENCES 7-297
7.695 USER_ROLE_PRIVS 7-297
7.696 USER_RSRC_CONSUMER_GROUP_PRIVS 7-298
7.697 USER_RSRC_MANAGER_SYSTEM_PRIVS 7-298
7.698 USER_RULE_SET_RULES 7-298
7.699 USER_RULE_SETS 7-299
7.700 USER_RULES 7-299
7.701 USER_SAGA_BROKERS 7-299
7.702 USER_SAGA_DETAILS 7-300
7.703 USER_SAGA_ERRORS 7-300
7.704 USER_SAGA_FINALIZATION 7-300
7.705 USER_SAGA_PARTICIPANT_SET 7-301
7.706 USER_SAGA_PARTICIPANTS 7-301
7.707 USER_SAGA_PENDING 7-302
7.708 USER_SAGAS 7-302
7.709 USER_SCHEDULER_CHAIN_RULES 7-303
7.710 USER_SCHEDULER_CHAIN_STEPS 7-303
7.711 USER_SCHEDULER_CHAINS 7-303
7.712 USER_SCHEDULER_CREDENTIALS 7-303
7.713 USER_SCHEDULER_DB_DESTS 7-304
7.714 USER_SCHEDULER_DESTS 7-304
7.715 USER_SCHEDULER_FILE_WATCHERS 7-304
7.716 USER_SCHEDULER_GROUP_MEMBERS 7-305
7.717 USER_SCHEDULER_GROUPS 7-305
7.718 USER_SCHEDULER_INCOMPAT_MEMBER 7-305
7.719 USER_SCHEDULER_INCOMPATS 7-305
7.720 USER_SCHEDULER_JOB_ARGS 7-306
7.721 USER_SCHEDULER_JOB_DESTS 7-306
7.722 USER_SCHEDULER_JOB_LOG 7-306
7.723 USER_SCHEDULER_JOB_RUN_DETAILS 7-306
7.724 USER_SCHEDULER_JOBS 7-307
7.725 USER_SCHEDULER_NOTIFICATIONS 7-307
7.726 USER_SCHEDULER_PROGRAM_ARGS 7-307
7.727 USER_SCHEDULER_PROGRAMS 7-307
7.728 USER_SCHEDULER_REMOTE_JOBSTATE 7-308
7.729 USER_SCHEDULER_RESOURCES 7-308
7.730 USER_SCHEDULER_RSC_CONSTRAINTS 7-308
7.731 USER_SCHEDULER_RUNNING_CHAINS 7-308
7.732 USER_SCHEDULER_RUNNING_JOBS 7-309
7.733 USER_SCHEDULER_SCHEDULES 7-309

7.734 USER_SCHEMA_PRIVS 7-309
7.735 USER_SEC_RELEVANT_COLS 7-310
7.736 USER_SECONDARY_OBJECTS 7-310
7.737 USER_SEGMENTS 7-310
7.738 USER_SEQUENCES 7-311
7.739 USER_SODA_COLLECTIONS 7-311
7.740 USER_SOURCE 7-311
7.741 USER_SOURCE_AE 7-312
7.742 USER_SQL_TRANSLATION_PROFILES 7-312
7.743 USER_SQL_TRANSLATIONS 7-312
7.744 USER_SQLJ_TYPE_ATTRS 7-312
7.745 USER_SQLJ_TYPE_METHODS 7-313
7.746 USER_SQLJ_TYPES 7-313
7.747 USER_SQLSET 7-313
7.748 USER_SQLSET_BINDS 7-313
7.749 USER_SQLSET_PLANS 7-314
7.750 USER_SQLSET_REFERENCES 7-314
7.751 USER_SQLSET_STATEMENTS 7-314
7.752 USER_SQLTUNE_BINDS 7-314
7.753 USER_SQLTUNE_PLANS 7-315
7.754 USER_SQLTUNE_RATIONALE_PLAN 7-315
7.755 USER_SQLTUNE_STATISTICS 7-315
7.756 USER_SR_GRP_STATUS 7-315
7.757 USER_SR_GRP_STATUS_ALL 7-316
7.758 USER_SR_OBJ 7-316
7.759 USER_SR_OBJ_ALL 7-316
7.760 USER_SR_OBJ_STATUS 7-316
7.761 USER_SR_OBJ_STATUS_ALL 7-317
7.762 USER_SR_PARTN_OPS 7-317
7.763 USER_SR_STLOG_EXCEPTIONS 7-317
7.764 USER_SR_STLOG_STATS 7-317
7.765 USER_STAT_EXTENSIONS 7-318
7.766 USER_STATEMENTS 7-318
7.767 USER_STORED_SETTINGS 7-318
7.768 USER_SUBPART_COL_STATISTICS 7-319
7.769 USER_SUBPART_HISTOGRAMS 7-319
7.770 USER_SUBPART_KEY_COLUMNS 7-319
7.771 USER_SUBPARTITION_TEMPLATES 7-319
7.772 USER_SUBSCR_REGISTRATIONS 7-320
7.773 USER_SYNONYMS 7-320
7.774 USER_SYS_PRIVS 7-320

7.775 USER_SYS_PRIVS_ALL 7-321
7.776 USER_TAB_COL_STAT_MODELS 7-321
7.777 USER_TAB_COL_STATISTICS 7-322
7.778 USER_TAB_COLS 7-322
7.779 USER_TAB_COLUMNS 7-322
7.780 USER_TAB_COMMENTS 7-323
7.781 USER_TAB_HISTGRM_PENDING_STATS 7-323
7.782 USER_TAB_HISTOGRAMS 7-323
7.783 USER_TAB_IDENTITY_COLS 7-324
7.784 USER_TAB_MODIFICATIONS 7-324
7.785 USER_TAB_PARTITIONS 7-324
7.786 USER_TAB_PENDING_STATS 7-325
7.787 USER_TAB_PRIVS 7-325
7.788 USER_TAB_PRIVS_MADE 7-325
7.789 USER_TAB_PRIVS_RECD 7-325
7.790 USER_TAB_STAT_PREFS 7-326
7.791 USER_TAB_STATISTICS 7-326
7.792 USER_TAB_STATS_HISTORY 7-326
7.793 USER_TAB_SUBPARTITIONS 7-326
7.794 USER_TABLE_ACCESS_STATS 7-327
7.795 USER_TABLE_VIRTUAL_COLUMNS 7-327
7.796 USER_TABLES 7-327
7.797 USER_TABLESPACES 7-328
7.798 USER_TRANSFORMATIONS 7-328
7.799 USER_TRIGGER_COLS 7-328
7.800 USER_TRIGGER_ORDERING 7-328
7.801 USER_TRIGGERS 7-329
7.802 USER_TRIGGERS_AE 7-329
7.803 USER_TS_QUOTAS 7-329
7.804 USER_TSTZ_TAB_COLS 7-329
7.805 USER_TSTZ_TABLES 7-330
7.806 USER_TUNE_MVIEW 7-330
7.807 USER_TXEVENTQ_MIGRATION_STATUS 7-330
7.808 USER_TYPE_ATTRS 7-331
7.809 USER_TYPE_METHODS 7-331
7.810 USER_TYPE_VERSIONS 7-331
7.811 USER_TYPES 7-331
7.812 USER_UNUSED_COL_TABS 7-332
7.813 USER_UPDATABLE_COLUMNS 7-332
7.814 USER_USERS 7-332
7.815 USER_USTATS 7-337

7.816 USER_VARRAYS 7-337
7.817 USER_VIEWS 7-338
7.818 USER_VIEWS_AE 7-338
7.819 USER_WALLET_ACES 7-338
7.820 USER_WARNING_SETTINGS 7-338
7.821 USER_XML_INDEXES 7-339
7.822 USER_XML_NESTED_TABLES 7-339
7.823 USER_XML_OUT_OF_LINE_TABLES 7-339
7.824 USER_XML_SCHEMA_ATTRIBUTES 7-339
7.825 USER_XML_SCHEMA_COMPLEX_TYPES 7-340
7.826 USER_XML_SCHEMA_ELEMENTS 7-340
7.827 USER_XML_SCHEMA_NAMESPACES 7-340
7.828 USER_XML_SCHEMA_SIMPLE_TYPES 7-340
7.829 USER_XML_SCHEMA_SUBSTGRP_HEAD 7-341
7.830 USER_XML_SCHEMA_SUBSTGRP_MBRS 7-341
7.831 USER_XML_SCHEMAS 7-341
7.832 USER_XML_TAB_COLS 7-341
7.833 USER_XML_TABLES 7-342
7.834 USER_XML_VIEW_COLS 7-342
7.835 USER_XML_VIEWS 7-342
7.836 USER_XTERNAL_LOC_PARTITIONS 7-342
7.837 USER_XTERNAL_LOC_SUBPARTITIONS 7-343
7.838 USER_XTERNAL_PART_TABLES 7-343
7.839 USER_XTERNAL_TAB_PARTITIONS 7-343
7.840 USER_XTERNAL_TAB_SUBPARTITIONS 7-343
7.841 USER_ZONEMAP_MEASURES 7-344
7.842 USER_ZONEMAPS 7-344

Part III Dynamic Performance Views

8 Dynamic Performance (V$) Views: V$ACCESS to V$HVMASTER_INFO

8.1 About Dynamic Performance Views 8-1
8.1.1 V$ Views 8-2
8.1.2 GV$ Views 8-2
8.2 Oracle Exadata Database Machine Views 8-3
8.3 Dynamic Performance View Descriptions 8-3
8.4 V$ACCESS 8-3
8.5 V$ACTIVE_INSTANCES 8-4
8.6 V$ACTIVE_SERVICES 8-4
8.7 V$ACTIVE_SESS_POOL_MTH 8-7

8.8 V$ACTIVE_SESSION_HISTORY 8-8
8.9 V$ACTIVITY_MVIEW 8-13
8.10 V$ACTIVITY_TABLE 8-15
8.11 V$ADVISOR_PROGRESS 8-17
8.12 V$ALERT_TYPES 8-18
8.13 V$ALL_ACTIVE_SESSION_HISTORY 8-19
8.14 V$ALL_SQL_BIND_CAPTURE 8-25
8.15 V$ALL_SQL_MONITOR 8-26
8.16 V$ALL_SQL_PLAN_MONITOR 8-31
8.17 V$AQ 8-37
8.18 V$AQ_BACKGROUND_COORDINATOR 8-38
8.19 V$AQ_BMAP_NONDUR_SUBSCRIBERS 8-38
8.20 V$AQ_CROSS_INSTANCE_JOBS 8-39
8.21 V$AQ_IPC_ACTIVE_MSGS 8-41
8.22 V$AQ_IPC_MSG_STATS 8-41
8.23 V$AQ_IPC_PENDING_MSGS 8-42
8.24 V$AQ_JOB_COORDINATOR 8-43
8.25 V$AQ_MESSAGE_CACHE 8-43
8.26 V$AQ_MESSAGE_CACHE_ADVICE 8-45
8.27 V$AQ_MESSAGE_CACHE_STAT 8-46
8.28 V$AQ_NONDUR_REGISTRATIONS 8-48
8.29 V$AQ_NONDUR_SUBSCRIBER 8-49
8.30 V$AQ_NONDUR_SUBSCRIBER_LWM 8-50
8.31 V$AQ_NOTIFICATION_CLIENTS 8-51
8.32 V$AQ_PARTITION_STATS 8-52
8.33 V$AQ_REMOTE_DEQUEUE_AFFINITY 8-54
8.34 V$AQ_SERVER_POOL 8-54
8.35 V$AQ_SHARDED_SUBSCRIBER_STAT 8-55
8.36 V$AQ_SUBSCRIBER_LOAD 8-56
8.37 V$ARCHIVE 8-57
8.38 V$ARCHIVE_DEST 8-58
8.39 V$ARCHIVE_DEST_STATUS 8-62
8.40 V$ARCHIVE_GAP 8-65
8.41 V$ARCHIVE_PROCESSES 8-65
8.42 V$ARCHIVED_LOG 8-66
8.43 V$ASM_ACFS_ENCRYPTION_INFO 8-68
8.44 V$ASM_ACFSAUTORESIZE 8-69
8.45 V$ASM_ACFSREPL 8-70
8.46 V$ASM_ACFSREPLTAG 8-72
8.47 V$ASM_ACFSSNAPSHOTS 8-73
8.48 V$ASM_ACFSTAG 8-74

8.49 V$ASM_ACFSVOLUMES 8-75
8.50 V$ASM_ALIAS 8-76
8.51 V$ASM_ATTRIBUTE 8-77
8.52 V$ASM_AUDIT_CLEANUP_JOBS 8-78
8.53 V$ASM_AUDIT_CONFIG_PARAMS 8-79
8.54 V$ASM_AUDIT_LAST_ARCH_TS 8-80
8.55 V$ASM_CLIENT 8-80
8.56 V$ASM_DBCLONE_INFO 8-82
8.57 V$ASM_DISK 8-83
8.58 V$ASM_DISK_IOSTAT 8-88
8.59 V$ASM_DISK_STAT 8-89
8.60 V$ASM_DISKGROUP 8-90
8.61 V$ASM_DISKGROUP_STAT 8-92
8.62 V$ASM_ESTIMATE 8-92
8.63 V$ASM_FILE 8-93
8.64 V$ASM_FILEGROUP 8-95
8.65 V$ASM_FILEGROUP_FILE 8-96
8.66 V$ASM_FILEGROUP_PROPERTY 8-97
8.67 V$ASM_FILESYSTEM 8-99
8.68 V$ASM_OPERATION 8-100
8.69 V$ASM_QUOTAGROUP 8-102
8.70 V$ASM_TEMPLATE 8-103
8.71 V$ASM_USER 8-104
8.72 V$ASM_USERGROUP 8-105
8.73 V$ASM_USERGROUP_MEMBER 8-105
8.74 V$ASM_VOLUME 8-106
8.75 V$ASM_VOLUME_STAT 8-107
8.76 V$AUTHPOOL_STATS 8-108
8.77 V$AUTO_IM_FEATURES 8-109
8.78 V$AW_AGGREGATE_OP 8-109
8.79 V$AW_ALLOCATE_OP 8-110
8.80 V$AW_CALC 8-110
8.81 V$AW_LONGOPS 8-111
8.82 V$AW_OLAP 8-112
8.83 V$AW_SESSION_INFO 8-113
8.84 V$BACKUP 8-114
8.85 V$BACKUP_ARCHIVELOG_DETAILS 8-115
8.86 V$BACKUP_ARCHIVELOG_SUMMARY 8-115
8.87 V$BACKUP_ASYNC_IO 8-116
8.88 V$BACKUP_CONTROLFILE_DETAILS 8-117
8.89 V$BACKUP_CONTROLFILE_SUMMARY 8-118

8.90 V$BACKUP_COPY_DETAILS 8-119
8.91 V$BACKUP_COPY_SUMMARY 8-120
8.92 V$BACKUP_CORRUPTION 8-121
8.93 V$BACKUP_DATAFILE 8-122
8.94 V$BACKUP_DATAFILE_DETAILS 8-124
8.95 V$BACKUP_DATAFILE_SUMMARY 8-125
8.96 V$BACKUP_DEVICE 8-126
8.97 V$BACKUP_FILES 8-126
8.98 V$BACKUP_NONLOGGED 8-129
8.99 V$BACKUP_PIECE 8-130
8.100 V$BACKUP_PIECE_DETAILS 8-131
8.101 V$BACKUP_REDOLOG 8-133
8.102 V$BACKUP_SET 8-134
8.103 V$BACKUP_SET_DETAILS 8-135
8.104 V$BACKUP_SET_SUMMARY 8-137
8.105 V$BACKUP_SPFILE 8-138
8.106 V$BACKUP_SPFILE_DETAILS 8-138
8.107 V$BACKUP_SPFILE_SUMMARY 8-139
8.108 V$BACKUP_SYNC_IO 8-139
8.109 V$BGPROCESS 8-140
8.110 V$BH 8-141
8.111 V$BLOCK_CHANGE_TRACKING 8-143
8.112 V$BLOCKING_QUIESCE 8-144
8.113 V$BT_SCAN_CACHE 8-144
8.114 V$BT_SCAN_OBJ_TEMPS 8-145
8.115 V$BUFFER_POOL 8-146
8.116 V$BUFFER_POOL_STATISTICS 8-147
8.117 V$BUFFERED_PUBLISHERS 8-148
8.118 V$BUFFERED_QUEUES 8-149
8.119 V$BUFFERED_SUBSCRIBERS 8-150
8.120 V$CACHE 8-151
8.121 V$CACHE_LOCK 8-153
8.122 V$CACHE_TRANSFER 8-154
8.123 V$CHUNK_METRIC 8-156
8.124 V$CIRCUIT 8-156
8.125 V$CLASS_CACHE_TRANSFER 8-157
8.126 V$CLEANUP_PROCESS 8-158
8.127 V$CLIENT_SECRETS 8-159
8.128 V$CLIENT_STATS 8-160
8.129 V$CLONEDFILE 8-161
8.130 V$CLUSTER_INTERCONNECTS 8-161

8.131 V$CODE_CLAUSE 8-162
8.132 V$CON_EVENT_HISTOGRAM_MICRO 8-163
8.133 V$CON_SYS_TIME_MODEL 8-164
8.134 V$CON_SYSMETRIC 8-164
8.135 V$CON_SYSMETRIC_HISTORY 8-165
8.136 V$CON_SYSMETRIC_SUMMARY 8-166
8.137 V$CON_SYSSTAT 8-167
8.138 V$CON_SYSTEM_EVENT 8-167
8.139 V$CON_SYSTEM_WAIT_CLASS 8-168
8.140 V$CONFIGURED_INTERCONNECTS 8-169
8.141 V$CONTAINER_TOPOLOGY 8-170
8.142 V$CONTAINERS 8-171
8.143 V$CONTEXT 8-173
8.144 V$CONTROLFILE 8-173
8.145 V$CONTROLFILE_RECORD_SECTION 8-174
8.146 V$COPY_CORRUPTION 8-176
8.147 V$COPY_NONLOGGED 8-176
8.148 V$CORRUPT_XID_LIST 8-177
8.149 V$CPOOL_CC_INFO 8-178
8.150 V$CPOOL_CC_STATS 8-178
8.151 V$CPOOL_CONN_INFO 8-179
8.152 V$CPOOL_STATS 8-180
8.153 V$CR_BLOCK_SERVER 8-181
8.154 V$CURRENT_BLOCK_SERVER 8-183
8.155 V$DATABASE 8-184
8.156 V$DATABASE_BLOCK_CORRUPTION 8-192
8.157 V$DATABASE_INCARNATION 8-192
8.158 V$DATABASE_KEY_INFO 8-193
8.159 V$DATAFILE 8-194
8.160 V$DATAFILE_COPY 8-196
8.161 V$DATAFILE_HEADER 8-198
8.162 V$DATAGUARD_CONFIG 8-200
8.163 V$DATAGUARD_PROCESS 8-201
8.164 V$DATAGUARD_STATS 8-205
8.165 V$DATAGUARD_STATUS 8-206
8.166 V$DATAPUMP_SESSIONWAIT_INFO 8-207
8.167 V$DB_CACHE_ADVICE 8-209
8.168 V$DB_OBJECT_CACHE 8-210
8.169 V$DB_PIPES 8-211
8.170 V$DB_TRANSPORTABLE_PLATFORM 8-212
8.171 V$DBFILE 8-212

8.172 V$DBLINK 8-213
8.173 V$DEAD_CLEANUP 8-214
8.174 V$DELETED_OBJECT 8-215
8.175 V$DG_BROKER_CONFIG 8-216
8.176 V$DG_BROKER_ROLE_CHANGE 8-217
8.177 V$DIAG_ALERT_EXT 8-218
8.178 V$DIAG_APP_TRACE_FILE 8-219
8.179 V$DIAG_INCIDENT 8-220
8.180 V$DIAG_INFO 8-222
8.181 V$DIAG_OPT_TRACE_RECORDS 8-222
8.182 V$DIAG_PROBLEM 8-224
8.183 V$DIAG_SESS_OPT_TRACE_RECORDS 8-225
8.184 V$DIAG_SESS_SQL_TRACE_RECORDS 8-226
8.185 V$DIAG_SQL_TRACE_RECORDS 8-227
8.186 V$DIAG_TRACE_FILE 8-229
8.187 V$DIAG_TRACE_FILE_CONTENTS 8-229
8.188 V$DISPATCHER 8-231
8.189 V$DISPATCHER_CONFIG 8-232
8.190 V$DISPATCHER_RATE 8-232
8.191 V$DNFS_CHANNELS 8-237
8.192 V$DNFS_FILES 8-238
8.193 V$DNFS_SERVERS 8-238
8.194 V$DNFS_STATS 8-239
8.195 V$DYNAMIC_REMASTER_STATS 8-240
8.196 V$EDITIONABLE_TYPES 8-241
8.197 V$EMON 8-242
8.198 V$ENABLEDPRIVS 8-243
8.199 V$ENABLEDSCHEMAPRIVS 8-244
8.200 V$ENCRYPTED_TABLESPACES 8-245
8.201 V$ENCRYPTION_KEYS 8-246
8.202 V$ENCRYPTION_WALLET 8-248
8.203 V$ENQUEUE_LOCK 8-250
8.204 V$ENQUEUE_STAT 8-251
8.205 V$ENQUEUE_STATISTICS 8-251
8.206 V$EQ_CACHED_PARTITIONS 8-252
8.207 V$EQ_CROSS_INSTANCE_JOBS 8-253
8.208 V$EQ_INACTIVE_PARTITIONS 8-255
8.209 V$EQ_MESSAGE_CACHE 8-256
8.210 V$EQ_MESSAGE_CACHE_ADVICE 8-257
8.211 V$EQ_MESSAGE_CACHE_STAT 8-258
8.212 V$EQ_NONDUR_SUBSCRIBER 8-260

8.213 V$EQ_NONDUR_SUBSCRIBER_LWM 8-261
8.214 V$EQ_PARTITION_STATS 8-262
8.215 V$EQ_REMOTE_DEQUEUE_AFFINITY 8-264
8.216 V$EQ_SUBSCRIBER_LOAD 8-264
8.217 V$EQ_SUBSCRIBER_STAT 8-266
8.218 V$EQ_UNCACHED_PARTITIONS 8-267
8.219 V$EVENT_HISTOGRAM 8-267
8.220 V$EVENT_HISTOGRAM_MICRO 8-268
8.221 V$EVENT_NAME 8-269
8.222 V$EVENTMETRIC 8-270
8.223 V$EXADIRECT_ACL 8-270
8.224 V$EXECUTION 8-270
8.225 V$EXP_STATS 8-271
8.226 V$FALSE_PING 8-272
8.227 V$FAST_START_FAILOVER_CONFIG 8-273
8.228 V$FAST_START_SERVERS 8-275
8.229 V$FAST_START_TRANSACTIONS 8-276
8.230 V$FILE_CACHE_TRANSFER 8-277
8.231 V$FILE_HISTOGRAM 8-278
8.232 V$FILEMETRIC 8-278
8.233 V$FILEMETRIC_HISTORY 8-279
8.234 V$FILESPACE_USAGE 8-279
8.235 V$FILESTAT 8-280
8.236 V$FIXED_TABLE 8-281
8.237 V$FIXED_VIEW_DEFINITION 8-281
8.238 V$FLASHBACK_DATABASE_LOG 8-282
8.239 V$FLASHBACK_DATABASE_LOGFILE 8-282
8.240 V$FLASHBACK_DATABASE_STAT 8-283
8.241 V$FLASHBACK_LOG_DEST 8-283
8.242 V$FLASHBACK_TXN_GRAPH 8-284
8.243 V$FLASHBACK_TXN_MODS 8-285
8.244 V$FLASHFILESTAT 8-287
8.245 V$FOREIGN_ARCHIVED_LOG 8-287
8.246 V$FS_FAILOVER_OBSERVERS 8-290
8.247 V$FS_FAILOVER_STATS 8-291
8.248 V$FS_OBSERVER_HISTOGRAM 8-291
8.249 V$GC_ELEMENT 8-293
8.250 V$GC_ELEMENTS_WITH_COLLISIONS 8-293
8.251 V$GCR_ACTIONS 8-294
8.252 V$GCR_LOG 8-295
8.253 V$GCR_METRICS 8-295

8.254 V$GCR_STATUS 8-297
8.255 V$GCSHVMASTER_INFO 8-297
8.256 V$GCSPFMASTER_INFO 8-298
8.257 V$GES_BLOCKING_ENQUEUE 8-298
8.258 V$GES_CONVERT_LOCAL 8-300
8.259 V$GES_CONVERT_REMOTE 8-300
8.260 V$GES_ENQUEUE 8-301
8.261 V$GES_LATCH 8-303
8.262 V$GES_RESOURCE 8-303
8.263 V$GES_STATISTICS 8-303
8.264 V$GG_APPLY_COORDINATOR 8-304
8.265 V$GG_APPLY_READER 8-306
8.266 V$GG_APPLY_RECEIVER 8-308
8.267 V$GG_APPLY_SERVER 8-309
8.268 V$GLOBAL_BLOCKED_LOCKS 8-312
8.269 V$GLOBAL_TRANSACTION 8-312
8.270 V$GOLDENGATE_CAPABILITIES 8-314
8.271 V$GOLDENGATE_CAPTURE 8-314
8.272 V$GOLDENGATE_MESSAGE_TRACKING 8-317
8.273 V$GOLDENGATE_PROCEDURE_STATS 8-318
8.274 V$GOLDENGATE_TABLE_STATS 8-319
8.275 V$GOLDENGATE_TRANSACTION 8-320
8.276 V$HANG_INFO 8-322
8.277 V$HANG_SESSION_INFO 8-324
8.278 V$HANG_STATISTICS 8-325
8.279 V$HEAT_MAP_SEGMENT 8-326
8.280 V$HM_CHECK 8-327
8.281 V$HM_CHECK_PARAM 8-327
8.282 V$HM_FINDING 8-328
8.283 V$HM_INFO 8-329
8.284 V$HM_RECOMMENDATION 8-330
8.285 V$HM_RUN 8-330
8.286 V$HS_AGENT 8-331
8.287 V$HS_PARAMETER 8-332
8.288 V$HS_SESSION 8-332
8.289 V$HVMASTER_INFO 8-333

9 Dynamic Performance (V$) Views: V$IM_COLUMN_LEVEL to V$RULE_SET_AGGREGATE_STATS

9.1 V$IM_COLUMN_LEVEL 9-1

9.2 V$IM_SEGMENTS 9-2
9.3 V$IM_USER_SEGMENTS 9-4
9.4 V$INDEX_USAGE_INFO 9-6
9.5 V$INDEXED_FIXED_COLUMN 9-7
9.6 V$INMEMORY_AREA 9-7
9.7 V$INMEMORY_FASTSTART_AREA 9-8
9.8 V$INMEMORY_SIZE_ADVICE 9-9
9.9 V$INSTANCE 9-10
9.10 V$INSTANCE_CACHE_TRANSFER 9-12
9.11 V$INSTANCE_PING 9-14
9.12 V$INSTANCE_RECOVERY 9-15
9.13 V$IO_CALIBRATION_STATUS 9-16
9.14 V$IO_OUTLIER 9-17
9.15 V$IOFUNCMETRIC 9-17
9.16 V$IOFUNCMETRIC_HISTORY 9-18
9.17 V$IOS_CLIENT 9-18
9.18 V$IOSTAT_CONSUMER_GROUP 9-19
9.19 V$IOSTAT_FILE 9-20
9.20 V$IOSTAT_FUNCTION 9-21
9.21 V$IOSTAT_FUNCTION_DETAIL 9-22
9.22 V$IOSTAT_NETWORK 9-23
9.23 V$IP_ACL 9-24
9.24 V$JAVA_LIBRARY_CACHE_MEMORY 9-24
9.25 V$JAVA_POOL_ADVICE 9-25
9.26 V$KERNEL_IO_OUTLIER 9-26
9.27 V$KEY_VECTOR 9-27
9.28 V$LATCH 9-30
9.29 V$LATCH_CHILDREN 9-31
9.30 V$LATCH_MISSES 9-32
9.31 V$LATCH_PARENT 9-33
9.32 V$LATCHHOLDER 9-33
9.33 V$LATCHNAME 9-33
9.34 V$LCR_CACHE 9-34
9.35 V$LGWRIO_OUTLIER 9-35
9.36 V$LIBCACHE_LOCKS 9-36
9.37 V$LIBRARY_CACHE_MEMORY 9-36
9.38 V$LIBRARYCACHE 9-37
9.39 V$LICENSE 9-38
9.40 V$LOADISTAT 9-39
9.41 V$LOADPSTAT 9-39
9.42 V$LOCK 9-40

9.43 V$LOCK_ACTIVITY 9-42
9.44 V$LOCK_TYPE 9-42
9.45 V$LOCKDOWN_RULES 9-43
9.46 V$LOCKED_OBJECT 9-44
9.47 V$LOG 9-44
9.48 V$LOG_HISTORY 9-45
9.49 V$LOGFILE 9-46
9.50 V$LOGHIST 9-47
9.51 V$LOGMNR_CONTENTS 9-47
9.52 V$LOGMNR_DICTIONARY 9-53
9.53 V$LOGMNR_DICTIONARY_LOAD 9-54
9.54 V$LOGMNR_LATCH 9-55
9.55 V$LOGMNR_LOGS 9-56
9.56 V$LOGMNR_PARAMETERS 9-57
9.57 V$LOGMNR_PROCESS 9-57
9.58 V$LOGMNR_SESSION 9-58
9.59 V$LOGMNR_STATS 9-60
9.60 V$LOGSTDBY 9-62
9.61 V$LOGSTDBY_PROCESS 9-62
9.62 V$LOGSTDBY_PROGRESS 9-63
9.63 V$LOGSTDBY_STATE 9-64
9.64 V$LOGSTDBY_STATS 9-65
9.65 V$LOGSTDBY_TRANSACTION 9-67
9.66 V$MANAGED_STANDBY 9-69
9.67 V$MAP_COMP_LIST 9-70
9.68 V$MAP_ELEMENT 9-71
9.69 V$MAP_EXT_ELEMENT 9-72
9.70 V$MAP_FILE 9-72
9.71 V$MAP_FILE_EXTENT 9-73
9.72 V$MAP_FILE_IO_STACK 9-74
9.73 V$MAP_LIBRARY 9-75
9.74 V$MAP_SUBELEMENT 9-75
9.75 V$MAPPED_SQL 9-76
9.76 V$MEMOPTIMIZE_WRITE_AREA 9-77
9.77 V$MEMORY_CURRENT_RESIZE_OPS 9-77
9.78 V$MEMORY_DYNAMIC_COMPONENTS 9-78
9.79 V$MEMORY_RESIZE_OPS 9-79
9.80 V$MEMORY_TARGET_ADVICE 9-80
9.81 V$METRIC 9-81
9.82 V$METRICGROUP 9-82
9.83 V$METRIC_HISTORY 9-82

9.84 V$METRICNAME 9-83
9.85 V$MTTR_TARGET_ADVICE 9-83
9.86 V$MUTEX_SLEEP 9-85
9.87 V$MUTEX_SLEEP_HISTORY 9-85
9.88 V$MVREFRESH 9-86
9.89 V$MYSTAT 9-86
9.90 V$NFS_CLIENTS 9-87
9.91 V$NFS_LOCKS 9-87
9.92 V$NFS_OPEN_FILES 9-88
9.93 V$NLS_PARAMETERS 9-88
9.94 V$NLS_VALID_VALUES 9-89
9.95 V$NONLOGGED_BLOCK 9-89
9.96 V$OBJECT_DEPENDENCY 9-90
9.97 V$OBJECT_PRIVILEGE 9-91
9.98 V$OBSOLETE_BACKUP_FILES 9-92
9.99 V$OBSOLETE_PARAMETER 9-94
9.100 V$OFFLINE_RANGE 9-94
9.101 V$OFS_STATS 9-95
9.102 V$OFS_THREADS 9-96
9.103 V$OFSMOUNT 9-98
9.104 V$ONLINE_REDEF 9-99
9.105 V$OPEN_CURSOR 9-99
9.106 V$OPTIMIZER_PROCESSING_RATE 9-101
9.107 V$OPTION 9-101
9.108 V$OSSTAT 9-102
9.109 V$PARALLEL_DEGREE_LIMIT_MTH 9-104
9.110 V$PARAMETER 9-104
9.111 V$PARAMETER_VALID_VALUES 9-107
9.112 V$PARAMETER2 9-107
9.113 V$PASSWORDFILE_INFO 9-109
9.114 V$PATCHES 9-110
9.115 V$PDB_INCARNATION 9-111
9.116 V$PDBS 9-111
9.117 V$PERSISTENT_PUBLISHERS 9-114
9.118 V$PERSISTENT_QMN_CACHE 9-114
9.119 V$PERSISTENT_QUEUES 9-116
9.120 V$PERSISTENT_SUBSCRIBERS 9-118
9.121 V$PGA_TARGET_ADVICE 9-119
9.122 V$PGA_TARGET_ADVICE_HISTOGRAM 9-120
9.123 V$PGASTAT 9-122
9.124 V$PKCS11_PATH 9-124

9.125 V$PLSQL_DEBUGGABLE_SESSIONS 9-124
9.126 V$PMEM_FILESTORE 9-125
9.127 V$PQ_SESSTAT 9-126
9.128 V$PQ_SLAVE 9-127
9.129 V$PQ_SYSSTAT 9-127
9.130 V$PQ_TQSTAT 9-129
9.131 V$PROCESS 9-129
9.132 V$PROCESS_MEMORY 9-131
9.133 V$PROCESS_MEMORY_DETAIL 9-131
9.134 V$PROCESS_POOL 9-132
9.135 V$PROPAGATION_RECEIVER 9-133
9.136 V$PROPAGATION_SENDER 9-134
9.137 V$PROXY_ARCHIVEDLOG 9-136
9.138 V$PROXY_ARCHIVELOG_DETAILS 9-137
9.139 V$PROXY_ARCHIVELOG_SUMMARY 9-138
9.140 V$PROXY_COPY_DETAILS 9-139
9.141 V$PROXY_COPY_SUMMARY 9-140
9.142 V$PROXY_DATAFILE 9-141
9.143 V$PROXY_PDB_TARGETS 9-143
9.144 V$PWFILE_USERS 9-144
9.145 V$PX_INSTANCE_GROUP 9-145
9.146 V$PX_PROCESS 9-146
9.147 V$PX_PROCESS_DETAIL 9-146
9.148 V$PX_PROCESS_SYSSTAT 9-147
9.149 V$PX_SERVER 9-149
9.150 V$PX_SESSION 9-150
9.151 V$PX_SESSTAT 9-150
9.152 V$QMON_COORDINATOR_STATS 9-151
9.153 V$QMON_SERVER_STATS 9-152
9.154 V$QMON_TASK_STATS 9-153
9.155 V$QMON_TASKS 9-153
9.156 V$QUARANTINE 9-154
9.157 V$QUARANTINE_SUMMARY 9-154
9.158 V$QUEUE 9-155
9.159 V$QUEUEING_MTH 9-156
9.160 V$RECOVER_FILE 9-156
9.161 V$RECOVERY_AREA_USAGE 9-156
9.162 V$RECOVERY_FILE_DEST 9-157
9.163 V$RECOVERY_FILE_STATUS 9-158
9.164 V$RECOVERY_LOG 9-158
9.165 V$RECOVERY_PROGRESS 9-159

9.166	V$RECOVERY_SLAVE	9-161
9.167	V$RECOVERY_STATUS	9-161
9.168	V$RECOVERY_WORKER	9-162
9.169	V$REDO_DEST_RESP_HISTOGRAM	9-164
9.170	V$REQDIST	9-165
9.171	V$RESERVED_WORDS	9-165
9.172	V$RESOURCE	9-166
9.173	V$RESOURCE_LIMIT	9-166
9.174	V$RESTORE_POINT	9-167
9.175	V$RESULT_CACHE_DEPENDENCY	9-168
9.176	V$RESULT_CACHE_MEMORY	9-169
9.177	V$RESULT_CACHE_OBJECTS	9-169
9.178	V$RESULT_CACHE_STATISTICS	9-171
9.179	V$RESULT_SUBCACHE_STATISTICS	9-172
9.180	V$RMAN_BACKUP_JOB_DETAILS	9-173
9.181	V$RMAN_BACKUP_SUBJOB_DETAILS	9-174
9.182	V$RMAN_BACKUP_TYPE	9-176
9.183	V$RMAN_COMPRESSION_ALGORITHM	9-176
9.184	V$RMAN_CONFIGURATION	9-177
9.185	V$RMAN_ENCRYPTION_ALGORITHMS	9-178
9.186	V$RMAN_OUTPUT	9-178
9.187	V$RMAN_STATUS	9-179
9.188	V$RO_USER_ACCOUNT	9-180
9.189	V$ROLLNAME	9-181
9.190	V$ROLLSTAT	9-182
9.191	V$ROWCACHE	9-183
9.192	V$ROWCACHE_PARENT	9-184
9.193	V$ROWCACHE_SUBORDINATE	9-185
9.194	V$RSRC_CONS_GROUP_HISTORY	9-185
9.195	V$RSRC_CONSUMER_GROUP	9-188
9.196	V$RSRC_CONSUMER_GROUP_CPU_MTH	9-191
9.197	V$RSRC_PDB	9-192
9.198	V$RSRC_PDB_HISTORY	9-194
9.199	V$RSRC_PLAN	9-196
9.200	V$RSRC_PLAN_CPU_MTH	9-198
9.201	V$RSRC_PLAN_HISTORY	9-199
9.202	V$RSRC_SESSION_INFO	9-200
9.203	V$RSRCMGRMETRIC	9-205
9.204	V$RSRCMGRMETRIC_HISTORY	9-207
9.205	V$RSRCPDBMETRIC	9-207
9.206	V$RSRCPDBMETRIC_HISTORY	9-209

9.207 V$RULE 9-210
9.208 V$RULE_SET 9-210
9.209 V$RULE_SET_AGGREGATE_STATS 9-212

10 Dynamic Performance (V$) Views: V$SCHEDULER_IN_MEMORY_TRACE to V$ZONEMAP_USAGE_STATS

10.1 V$SCHEDULER_IN_MEMORY_TRACE 10-1
10.2 V$SCHEDULER_RUNNING_JOBS 10-1
10.3 V$SECUREFILE_SHRINK 10-2
10.4 V$SECUREFILE_TIMER 10-3
10.5 V$SEGMENT_STATISTICS 10-4
10.6 V$SEGSTAT 10-4
10.7 V$SEGSTAT_NAME 10-5
10.8 V$SERV_MOD_ACT_STATS 10-5
10.9 V$SERVICE_DRAIN_TIMEOUT_ADVICE 10-6
10.10 V$SERVICE_EVENT 10-8
10.11 V$SERVICE_REGION_METRIC 10-9
10.12 V$SERVICE_STATS 10-9
10.13 V$SERVICE_WAIT_CLASS 10-10
10.14 V$SERVICEMETRIC 10-11
10.15 V$SERVICEMETRIC_HISTORY 10-12
10.16 V$SERVICES 10-12
10.17 V$SES_OPTIMIZER_ENV 10-15
10.18 V$SESS_IO 10-16
10.19 V$SESS_TIME_MODEL 10-16
10.20 V$SESSION 10-19
10.21 V$SESSION_BLOCKERS 10-26
10.22 V$SESSION_CONNECT_INFO 10-27
10.23 V$SESSION_CURSOR_CACHE 10-28
10.24 V$SESSION_EVENT 10-29
10.25 V$SESSION_FIX_CONTROL 10-30
10.26 V$SESSION_LONGOPS 10-31
10.27 V$SESSION_OBJECT_CACHE 10-32
10.28 V$SESSION_WAIT 10-33
10.29 V$SESSION_WAIT_CLASS 10-35
10.30 V$SESSION_WAIT_HISTORY 10-36
10.31 V$SESSIONS_COUNT 10-36
10.32 V$SESSMETRIC 10-37
10.33 V$SESSTAT 10-37

10.34	V$SGA	10-38
10.35	V$SGA_CURRENT_RESIZE_OPS	10-38
10.36	V$SGA_DYNAMIC_COMPONENTS	10-39
10.37	V$SGA_DYNAMIC_FREE_MEMORY	10-40
10.38	V$SGA_RESIZE_OPS	10-40
10.39	V$SGA_TARGET_ADVICE	10-41
10.40	V$SGAINFO	10-42
10.41	V$SGASTAT	10-42
10.42	V$SHARD_ACK_RECEIVER	10-43
10.43	V$SHARD_ACK_SENDER	10-44
10.44	V$SHARD_APPLY_COORDINATOR	10-45
10.45	V$SHARD_APPLY_LCR_READER	10-47
10.46	V$SHARD_APPLY_READER	10-48
10.47	V$SHARD_APPLY_SERVER	10-49
10.48	V$SHARD_LCR_LOGS	10-51
10.49	V$SHARD_LCR_PERSISTER	10-52
10.50	V$SHARD_LCR_PRODUCER	10-53
10.51	V$SHARD_NETWORK_RECEIVER	10-54
10.52	V$SHARD_NETWORK_SENDER	10-56
10.53	V$SHARD_REPLICATION_UNIT	10-57
10.54	V$SHARED_POOL_ADVICE	10-59
10.55	V$SHARED_POOL_RESERVED	10-59
10.56	V$SHARED_SERVER	10-61
10.57	V$SHARED_SERVER_MONITOR	10-62
10.58	V$SHARED_SERVER_STAT	10-62
10.59	V$SORT_SEGMENT	10-63
10.60	V$SPPARAMETER	10-64
10.61	V$SQL	10-64
10.62	V$SQL_BIND_CAPTURE	10-71
10.63	V$SQL_BIND_DATA	10-73
10.64	V$SQL_BIND_METADATA	10-74
10.65	V$SQL_CS_HISTOGRAM	10-75
10.66	V$SQL_CS_SELECTIVITY	10-75
10.67	V$SQL_CS_STATISTICS	10-76
10.68	V$SQL_CURSOR	10-76
10.69	V$SQL_HISTORY	10-77
10.70	V$SQL_JOIN_FILTER	10-79
10.71	V$SQL_MONITOR	10-80
10.72	V$SQL_MONITOR_SESSTAT	10-86
10.73	V$SQL_MONITOR_STATNAME	10-86
10.74	V$SQL_OPTIMIZER_ENV	10-87

10.75 V$SQL_PLAN 10-88
10.76 V$SQL_PLAN_MONITOR 10-90
10.77 V$SQL_PLAN_STATISTICS 10-96
10.78 V$SQL_PLAN_STATISTICS_ALL 10-98
10.79 V$SQL_REDIRECTION 10-102
10.80 V$SQL_SHARD 10-102
10.81 V$SQL_SHARED_CURSOR 10-103
10.82 V$SQL_SHARED_MEMORY 10-106
10.83 V$SQL_TESTCASES 10-107
10.84 V$SQL_WORKAREA 10-108
10.85 V$SQL_WORKAREA_ACTIVE 10-110
10.86 V$SQL_WORKAREA_HISTOGRAM 10-112
10.87 V$SQLAREA 10-113
10.88 V$SQLAREA_PLAN_HASH 10-117
10.89 V$SQLCOMMAND 10-121
10.90 V$SQLFN_ARG_METADATA 10-121
10.91 V$SQLFN_METADATA 10-122
10.92 V$SQLSTATS 10-123
10.93 V$SQLSTATS_PLAN_HASH 10-127
10.94 V$SQLTEXT 10-127
10.95 V$SQLTEXT_WITH_NEWLINES 10-128
10.96 V$STANDBY_EVENT_HISTOGRAM 10-128
10.97 V$STANDBY_LOG 10-129
10.98 V$STATISTICS_LEVEL 10-130
10.99 V$STATNAME 10-131
10.100 V$STATS_ADVISOR_RULES 10-132
10.101 V$STREAMS_APPLY_COORDINATOR 10-133
10.102 V$STREAMS_APPLY_READER 10-135
10.103 V$STREAMS_APPLY_SERVER 10-137
10.104 V$STREAMS_POOL_ADVICE 10-140
10.105 V$STREAMS_POOL_STATISTICS 10-141
10.106 V$SUBCACHE 10-142
10.107 V$SUBSCR_REGISTRATION_STATS 10-142
10.108 V$SYS_OPTIMIZER_ENV 10-143
10.109 V$SYS_TIME_MODEL 10-144
10.110 V$SYSAUX_OCCUPANTS 10-145
10.111 V$SYSMETRIC 10-145
10.112 V$SYSMETRIC_HISTORY 10-146
10.113 V$SYSMETRIC_SUMMARY 10-147
10.114 V$SYSSTAT 10-147
10.115 V$SYSTEM_CURSOR_CACHE 10-148

10.116 V$SYSTEM_EVENT 10-149
10.117 V$SYSTEM_FIX_CONTROL 10-150
10.118 V$SYSTEM_PARAMETER 10-151
10.119 V$SYSTEM_PARAMETER2 10-153
10.120 V$SYSTEM_WAIT_CLASS 10-154
10.121 V$TABLE_ACCESS_STATS 10-155
10.122 V$TABLESPACE 10-156
10.123 V$TDM_STATS 10-156
10.124 V$TEMP_CACHE_TRANSFER 10-157
10.125 V$TEMP_EXTENT_MAP 10-158
10.126 V$TEMP_EXTENT_POOL 10-159
10.127 V$TEMP_SPACE_HEADER 10-159
10.128 V$TEMPFILE 10-160
10.129 V$TEMPORARY_LOBS 10-161
10.130 V$TEMPSEG_USAGE 10-161
10.131 V$TEMPSTAT 10-162
10.132 V$TEMPUNDOSTAT 10-163
10.133 V$TEXT_WAITING_EVENTS 10-164
10.134 V$THREAD 10-165
10.135 V$THRESHOLD_TYPES 10-166
10.136 V$TIMER 10-166
10.137 V$TIMEZONE_FILE 10-167
10.138 V$TIMEZONE_NAMES 10-167
10.139 V$TOPLEVELCALL 10-167
10.140 V$TRANSACTION 10-168
10.141 V$TRANSACTION_ENQUEUE 10-169
10.142 V$TRANSPORTABLE_PLATFORM 10-170
10.143 V$TRUE_CACHE 10-171
10.144 V$TSDP_SUPPORTED_FEATURE 10-172
10.145 V$TYPE_SIZE 10-173
10.146 V$UNDOSTAT 10-173
10.147 V$UNUSABLE_BACKUPFILE_DETAILS 10-175
10.148 V$VERSION 10-176
10.149 V$VPD_POLICY 10-176
10.150 V$WAIT_CHAINS 10-177
10.151 V$WAITCLASSMETRIC 10-179
10.152 V$WAITCLASSMETRIC_HISTORY 10-179
10.153 V$WAITSTAT 10-180
10.154 V$WALLET 10-180
10.155 V$WORKLOAD_REPLAY_THREAD 10-181
10.156 V$XML_AUDIT_TRAIL 10-183

10.157 V$XSTREAM_APPLY_COORDINATOR 10-185
10.158 V$XSTREAM_APPLY_READER 10-187
10.159 V$XSTREAM_APPLY_RECEIVER 10-190
10.160 V$XSTREAM_APPLY_SERVER 10-191
10.161 V$XSTREAM_CAPTURE 10-194
10.162 V$XSTREAM_MESSAGE_TRACKING 10-197
10.163 V$XSTREAM_OUTBOUND_SERVER 10-199
10.164 V$XSTREAM_TABLE_STATS 10-202
10.165 V$XSTREAM_TRANSACTION 10-203
10.166 V$ZONEMAP_USAGE_STATS 10-205

Part IV Appendixes

A Database Limits

A.1 Datatype Limits A-1
A.2 Physical Database Limits A-3
A.3 Logical Database Limits A-4
A.4 Process and Runtime Limits A-6

B SQL Scripts

B.1 Creating the Data Dictionary B-1
B.2 Creating Additional Data Dictionary Structures B-2
B.3 The "NO" Scripts B-5
B.4 Upgrade Scripts B-6
B.5 Java Scripts B-6

C Oracle Wait Events

C.1 Classes of Wait Events C-1
C.2 Descriptions of Common Wait Event Parameters C-3
C.3 Descriptions of Wait Events C-5
C.3.1 alter system set dispatcher C-5
C.3.2 ARCH Remote Write C-5
C.3.3 ASYNC Remote Write C-5
C.3.4 BFILE check if exists C-6
C.3.5 BFILE check if open C-6
C.3.6 BFILE closure C-6
C.3.7 BFILE get length C-6
C.3.8 BFILE get name object C-6

C.3.9 BFILE get path object C-7
C.3.10 BFILE internal seek C-7
C.3.11 BFILE open C-7
C.3.12 BFILE read C-7
C.3.13 broadcast mesg queue transition C-8
C.3.14 broadcast mesg recovery queue transition C-8
C.3.15 buffer busy waits C-8
C.3.16 buffer deadlock C-9
C.3.17 buffer latch C-9
C.3.18 buffer read retry C-10
C.3.19 checkpoint completed C-10
C.3.20 cleanup of aborted process C-10
C.3.21 control file parallel write C-10
C.3.22 control file sequential read C-11
C.3.23 control file single write C-11
C.3.24 cursor: mutex S C-11
C.3.25 cursor: mutex X C-12
C.3.26 cursor: pin S C-12
C.3.27 cursor: pin S wait on X C-12
C.3.28 cursor: pin X C-13
C.3.29 db file async I/O submit C-13
C.3.30 db file parallel read C-13
C.3.31 db file parallel write C-14
C.3.32 db file scattered read C-14
C.3.33 db file sequential read C-15
C.3.34 db file single write C-15
C.3.35 DFS lock handle C-16
C.3.36 direct path read C-16
C.3.37 direct path sync C-17
C.3.38 direct path write C-17
C.3.39 Disk file operations I/O C-17
C.3.40 dispatcher shutdown C-18
C.3.41 dispatcher timer C-18
C.3.42 dupl. cluster key C-18
C.3.43 enq: OW - initialization C-19
C.3.44 enq: OW - termination C-19
C.3.45 enq: SV - contention C-19
C.3.46 enq: TX - index contention C-20
C.3.47 enq: TX - row lock (HIGH priority) C-20
C.3.48 enq: TX - row lock (LOW priority) C-20
C.3.49 enq: TX - row lock (MEDIUM priority) C-21

C.3.50 enq: TX - row lock contention C-22
C.3.51 enqueue C-22
C.3.52 flashback buf free by RVWR C-22
C.3.53 flashback log file sync C-23
C.3.54 free buffer waits C-23
C.3.55 free global transaction table entry C-23
C.3.56 free process state object C-24
C.3.57 gc buffer busy acquire C-24
C.3.58 gc buffer busy release C-24
C.3.59 gc cr block 2-way C-24
C.3.60 gc cr block 3-way C-25
C.3.61 gc cr block busy C-25
C.3.62 gc cr block congested C-25
C.3.63 gc cr block direct read C-26
C.3.64 gc cr block lost C-26
C.3.65 gc cr grant read-mostly invalidation C-26
C.3.66 gc cr multi block grant C-27
C.3.67 gc cr multi block mixed C-27
C.3.68 gc cr request C-27
C.3.69 gc current block 2-way C-28
C.3.70 gc current block 3-way C-28
C.3.71 gc current block busy C-28
C.3.72 gc current block congested C-29
C.3.73 gc current block direct read C-29
C.3.74 gc current block lost C-29
C.3.75 gc current request C-30
C.3.76 inactive session C-30
C.3.77 inactive transaction branch C-30
C.3.78 index split completion C-31
C.3.79 instance state change C-31
C.3.80 io done C-31
C.3.81 ksxr wait for mount shared C-31
C.3.82 ktm: instance recovery C-32
C.3.83 latch activity C-32
C.3.84 latch free C-32
C.3.85 latch: redo copy C-33
C.3.86 library cache load lock C-33
C.3.87 library cache lock C-33
C.3.88 library cache pin C-34
C.3.89 library cache shutdown C-34
C.3.90 library cache: mutex X C-35

C.3.91 Log archive I/O C-35
C.3.92 log buffer space C-35
C.3.93 log file parallel write C-35
C.3.94 log file sequential read C-36
C.3.95 log file single write C-36
C.3.96 log file switch (archiving needed) C-36
C.3.97 log file switch (checkpoint incomplete) C-36
C.3.98 log file switch (clearing log file) C-37
C.3.99 log file switch (private strand flush incomplete) C-37
C.3.100 log file switch completion C-37
C.3.101 log file sync C-37
C.3.102 log switch/archive C-38
C.3.103 optimizer stats update retry C-38
C.3.104 parallel recovery change buffer free C-38
C.3.105 parallel recovery control message reply C-38
C.3.106 parallel recovery coord send blocked C-38
C.3.107 parallel recovery coord wait for reply C-39
C.3.108 parallel recovery coordinator waits for slave cleanup C-39
C.3.109 parallel recovery read buffer free C-39
C.3.110 parallel recovery slave next change C-39
C.3.111 pending global transaction(s) C-39
C.3.112 pipe get C-39
C.3.113 pipe put C-40
C.3.114 PL/SQL lock timer C-40
C.3.115 pmon timer C-40
C.3.116 prior spawner clean up C-41
C.3.117 process startup C-41
C.3.118 PX Deque wait C-41
C.3.119 PX qref latch C-42
C.3.120 PX server shutdown C-42
C.3.121 PX signal server C-42
C.3.122 rdbms ipc message C-42
C.3.123 rdbms ipc message block C-43
C.3.124 rdbms ipc reply C-43
C.3.125 read by other session C-43
C.3.126 recovery active instance mapping setup C-43
C.3.127 recovery apply pending C-43
C.3.128 recovery cancel C-44
C.3.129 recovery checkpoint C-44
C.3.130 recovery file header update for checkpoint C-44
C.3.131 recovery file header update for fuzziness C-44

C.3.132 recovery marker apply C-44
C.3.133 recovery merge pending C-44
C.3.134 recovery metadata latch C-44
C.3.135 recovery move influx buffers C-44
C.3.136 recovery read C-45
C.3.137 recovery receive buffer free C-45
C.3.138 recovery remote file verification C-45
C.3.139 recovery send buffer free C-45
C.3.140 recovery shutdown C-45
C.3.141 Redo Transport Attach C-45
C.3.142 Redo Transport Close C-46
C.3.143 Redo Transport Detach C-46
C.3.144 Redo Transport Open C-46
C.3.145 Redo Transport Ping C-46
C.3.146 Redo Transport Slave Startup C-47
C.3.147 Redo Writer Remote Sync Complete C-47
C.3.148 Redo Writer Remote Sync Notify C-47
C.3.149 resmgr:become active C-47
C.3.150 resmgr:cpu quantum C-47
C.3.151 resmgr: I/O rate limit C-48
C.3.152 resmgr:pq queued C-48
C.3.153 rolling migration: cluster quiesce C-48
C.3.154 row cache lock C-49
C.3.155 RVWR wait for flashback copy C-49
C.3.156 sbtbufinfo C-49
C.3.157 sbtgetbuf C-49
C.3.158 sbtmapbuf C-50
C.3.159 sbtrelbuf C-50
C.3.160 scginq AST call C-50
C.3.161 SGA: allocation forcing component growth C-50
C.3.162 SGA: MMAN sleep for component shrink C-50
C.3.163 SGA: sga_target resize C-51
C.3.164 Shared IO Pool Memory C-51
C.3.165 shared server idle wait C-51
C.3.166 single-task message C-51
C.3.167 smon timer C-51
C.3.168 SQL*Net break/reset to client C-52
C.3.169 SQL*Net break/reset to dblink C-52
C.3.170 SQL*Net message from client C-52
C.3.171 SQL*Net message from dblink C-53
C.3.172 SQL*Net message to client C-53

C.3.173 SQL*Net message to dblink C-53
C.3.174 SQL*Net more data from client C-54
C.3.175 SQL*Net more data from dblink C-54
C.3.176 SQL*Net more data to client C-54
C.3.177 SQL*Net more data to dblink C-55
C.3.178 Streams AQ: waiting for messages in the queue C-55
C.3.179 switch logfile command C-55
C.3.180 SYNC Remote Write C-55
C.3.181 TCP Socket (KGAS) C-55
C.3.182 timer in sksawat C-56
C.3.183 transaction C-56
C.3.184 unbound tx C-56
C.3.185 undo_retention publish retry C-56
C.3.186 undo segment extension C-57
C.3.187 undo segment recovery C-57
C.3.188 undo segment tx slot C-57
C.3.189 utl_file I/O C-57
C.3.190 virtual circuit wait C-58
C.3.191 WCR: replay client notify C-58
C.3.192 WCR: replay clock C-58
C.3.193 WCR: replay lock order C-58
C.3.194 WCR: replay paused C-59
C.3.195 WCR: Sync context busy C-59
C.3.196 write complete waits C-59

D Oracle Enqueue Names

E Statistics Descriptions

E.1 Displaying Statistics E-1
E.2 Statistics Descriptions E-1

F Background Processes

Index

Preface

This manual provides reference information about database initialization parameters, static data dictionary views, dynamic performance views, database limits, and SQL scripts that are part of the Oracle Database.

This preface contains these topics:

- Audience
- Documentation Accessibility
- Diversity and Inclusion
- Related Documents
- Conventions

Audience

Oracle Database Reference is intended for database administrators, system administrators, and database application developers.

To use this document, you need to be familiar with the following:

- Oracle database management system (DBMS) concepts
- Your operating system environment

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info or visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs if you are hearing impaired.

Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners, we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain

compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

Related Documents

For more information, see these Oracle resources:

- *Oracle Database Concepts* for a comprehensive introduction to the concepts and terminology used in this manual
- *Oracle Database Administrator's Guide* for information about administering the Oracle Database
- *Oracle Database Upgrade Guide* for the procedures for upgrading a previous release of Oracle to the new release
- *Oracle Database SQL Language Reference* for information on Oracle's SQL commands and functions
- *Oracle Database Development Guide* for information about developing database applications within the Oracle Database

To download free release notes, installation documentation, technical briefs, or other collateral, please visit the Oracle Technology Network (OTN). You must register online before using OTN; registration is free and can be done at

`http://www.oracle.com/technetwork`

You can go directly to the documentation section of the OTN Web site at

`http://www.oracle.com/technetwork/documentation`

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
italic	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
`monospace`	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

1

Changes in This Release for Oracle Database Reference

This chapter lists the following changes in *Oracle Database Reference* for Oracle Database 23ai:

- New Features
- Deprecated Features
- Desupported Features

1.1 New Features

- The maximum number of columns allowed in a database table or view has been increased from 1000 to 4096.

  See: MAX_COLUMNS

- The following initialization parameters are new in Oracle Database 23ai:
  - ALLOW_LEGACY_RECO_PROTOCOL
  - BLOCKCHAIN_TABLE_RETENTION_THRESHOLD
  - DB_FLASHBACK_LOG_DEST
  - DB_FLASHBACK_LOG_DEST_SIZE
  - DB_RECOVERY_AUTO_REKEY
  - ERROR_MESSAGE_DETAILS
  - GROUP_BY_POSITION_ENABLED
  - HYBRID_READ_ONLY
  - IDENTITY_PROVIDER_CONFIG
  - IDENTITY_PROVIDER_TYPE
  - IORM_LIMIT_POLICY
  - JSON_BEHAVIOR
  - JSON_EXPRESSION_CHECK
  - MAX_COLUMNS
  - MAX_SAGA_DURATION
  - MEMOPTIMIZE_WRITE_AREA_SIZE
  - MEMOPTIMIZE_WRITES
  - MEMORY_MAX_SIZE
  - MEMORY_SIZE
  - MLE_PROG_LANGUAGES

  - PLSQL_IMPLICIT_CONVERSION_BOOL
  - PRIORITY_TXNS_HIGH_WAIT_TARGET
  - PRIORITY_TXNS_MEDIUM_WAIT_TARGET
  - PRIORITY_TXNS_MODE
  - READ_ONLY
  - RESOURCE_MANAGER_CPU_SCOPE
  - RESULT_CACHE_AUTO_BLOCKLIST
  - RESULT_CACHE_INTEGRITY
  - SAGA_HIST_RETENTION
  - SESSION_EXIT_ON_PACKAGE_STATE_ERROR
  - SHARD_ENABLE_RAFT_FOLLOWER_READ
  - SHARD_RAFT_LOGFILE_SIZE
  - SQL_ERROR_MITIGATION
  - SQL_HISTORY_ENABLED
  - SQL_TRANSPILER
  - TABLESPACE_ENCRYPTION
  - TIME_AT_DBTIMEZONE
  - TRANSACTION_RECOVERY
  - TRUE_CACHE
  - TXN_PRIORITY
  - XML_PARAMS
- The following static data dictionary views are new in Oracle Database 23ai:
  - DBA_ADDM_PENDING_AUTOTASKS
  - DBA_ADDM_SCHEDULED_AUTOTASKS
  - DBA_AIM_PERF_FEATURES
  - ALL_ANNOTATION_VALUES, DBA_ANNOTATION_VALUES, and USER_ANNOTATION_VALUES
  - ALL_ANNOTATIONS, DBA_ANNOTATIONS, and USER_ANNOTATIONS
  - ALL_ANNOTATIONS_USAGE, DBA_ANNOTATIONS_USAGE, and USER_ANNOTATIONS_USAGE
  - DBA_AUTO_CLUSTERING_CONFIG
  - DBA_AUTO_CLUSTERING_RECOMMENDATIONS
  - ALL_BLOCKCHAIN_ROW_VERSION_COLS, DBA_BLOCKCHAIN_ROW_VERSION_COLS, and USER_BLOCKCHAIN_ROW_VERSION_COLS
  - ALL_BLOCKCHAIN_ROW_VERSION_HISTORY, DBA_BLOCKCHAIN_ROW_VERSION_HISTORY, and USER_BLOCKCHAIN_ROW_VERSION_HISTORY

- ALL_BLOCKCHAIN_TABLE_CHAINS, DBA_BLOCKCHAIN_TABLE_CHAINS, and USER_BLOCKCHAIN_TABLE_CHAINS
- ALL_BLOCKCHAIN_TABLE_EPOCHS, DBA_BLOCKCHAIN_TABLE_EPOCHS, and USER_BLOCKCHAIN_TABLE_EPOCHS
- ALL_BLOCKCHAIN_TABLE_HASH_COL_ORDER, DBA_BLOCKCHAIN_TABLE_HASH_COL_ORDER, and USER_BLOCKCHAIN_TABLE_HASH_COL_ORDER
- DBA_BLOCKER_RESOLVER_PARAMETERS
- DBA_DDL_REGS and USER_DDL_REGS
- ALL_DOMAIN_COLS, DBA_DOMAIN_COLS, and USER_DOMAIN_COLS
- ALL_DOMAIN_CONSTRAINTS, DBA_DOMAIN_CONSTRAINTS, and USER_DOMAIN_CONSTRAINTS
- ALL_DOMAINS, DBA_DOMAINS, and USER_DOMAINS
- DBA_HIST_OPTIMIZER_ENV_DETAILS
- ALL_HIST_SAGAS, DBA_HIST_SAGAS, and USER_HIST_SAGAS
- ALL_IMMUTABLE_ROW_VERSION_COLS, DBA_IMMUTABLE_ROW_VERSION_COLS, and USER_IMMUTABLE_ROW_VERSION_COLS
- ALL_IMMUTABLE_ROW_VERSION_HISTORY, DBA_IMMUTABLE_ROW_VERSION_HISTORY, and USER_IMMUTABLE_ROW_VERSION_HISTORY
- ALL_IMMUTABLE_TABLE_COLUMNS, DBA_IMMUTABLE_TABLE_COLUMNS, and USER_IMMUTABLE_TABLE_COLUMNS
- ALL_IMMUTABLE_TABLE_EPOCHS, DBA_IMMUTABLE_TABLE_EPOCHS, and USER_IMMUTABLE_TABLE_EPOCHS
- ALL_INCOMPLETE_SAGAS, DBA_INCOMPLETE_SAGAS, and USER_INCOMPLETE_SAGAS
- DBA_INMEMORY_ADVISOR_RECOMMENDATION
- ALL_JSON_COLLECTION_TABLES, DBA_JSON_COLLECTION_TABLES, and USER_JSON_COLLECTION_TABLES
- ALL_JSON_COLLECTIONS, DBA_JSON_COLLECTIONS, and USER_JSON_COLLECTIONS
- ALL_JSON_DOMAIN_SCHEMA_COLUMNS, DBA_JSON_DOMAIN_SCHEMA_COLUMNS, and USER_JSON_DOMAIN_SCHEMA_COLUMNS
- ALL_JSON_DUALITY_VIEW_LINKS, DBA_JSON_DUALITY_VIEW_LINKS, and USER_JSON_DUALITY_VIEW_LINKS
- ALL_JSON_DUALITY_VIEW_TAB_COLS, DBA_JSON_DUALITY_VIEW_TAB_COLS, and USER_JSON_DUALITY_VIEW_TAB_COLS
- ALL_JSON_DUALITY_VIEW_TABS, DBA_JSON_DUALITY_VIEW_TABS, and USER_JSON_DUALITY_VIEW_TABS
- ALL_JSON_DUALITY_VIEWS, DBA_JSON_DUALITY_VIEWS, and USER_JSON_DUALITY_VIEWS

- ALL_JSON_INDEXES, DBA_JSON_INDEXES, and USER_JSON_INDEXES
- ALL_JSON_SCHEMA_COLUMNS, DBA_JSON_SCHEMA_COLUMNS, and USER_JSON_SCHEMA_COLUMNS
- DBA_KAFKA_APPLICATIONS and USER_KAFKA_APPLICATIONS
- DBA_KAFKA_CLUSTERS and USER_KAFKA_CLUSTERS
- DBA_KAFKA_LOAD_METRICS and USER_KAFKA_LOAD_METRICS
- USER_KAFKA_MESSAGES
- DBA_KAFKA_OPS and USER_KAFKA_OPS
- DBA_KAFKA_OPS_RESULTS and USER_KAFKA_OPS_RESULTS
- DBA_KAFKA_PARTITIONS and USER_KAFKA_PARTITIONS
- ALL_MLE_ENV_IMPORTS, DBA_MLE_ENV_IMPORTS, and USER_MLE_ENV_IMPORTS
- ALL_MLE_ENVS, DBA_MLE_ENVS, and USER_MLE_ENVS
- ALL_MLE_MODULES, DBA_MLE_MODULES, and USER_MLE_MODULES
- ALL_MLE_PROCEDURES, DBA_MLE_PROCEDURES, and USER_MLE_PROCEDURES
- ALL_MVIEW_DETAIL_LOGICAL_PARTITION, DBA_MVIEW_DETAIL_LOGICAL_PARTITION, and USER_MVIEW_DETAIL_LOGICAL_PARTITION
- ALL_PG_EDGE_RELATIONSHIPS, DBA_PG_EDGE_RELATIONSHIPS, and USER_PG_EDGE_RELATIONSHIPS
- ALL_PG_ELEMENT_LABELS, DBA_PG_ELEMENT_LABELS, and USER_PG_ELEMENT_LABELS
- ALL_PG_ELEMENTS, DBA_PG_ELEMENTS, and USER_PG_ELEMENTS
- ALL_PG_KEYS, DBA_PG_KEYS, and USER_PG_KEYS
- ALL_PG_LABEL_PROPERTIES, DBA_PG_LABEL_PROPERTIES, and USER_PG_LABEL_PROPERTIES
- ALL_PG_LABELS, DBA_PG_LABELS, and USER_PG_LABELS
- ALL_PG_PROP_DEFINITIONS, DBA_PG_PROP_DEFINITIONS, and USER_PG_PROP_DEFINITIONS
- ALL_PROPERTY_GRAPHS, DBA_PROPERTY_GRAPHS, and USER_PROPERTY_GRAPHS
- DBA_QUARANTINED_TRANSACTIONS
- ALL_SAGA_BROKERS, DBA_SAGA_BROKERS, and USER_SAGA_BROKERS
- ALL_SAGA_DETAILS, DBA_SAGA_DETAILS, and USER_SAGA_DETAILS
- ALL_SAGA_ERRORS, DBA_SAGA_ERRORS, and USER_SAGA_ERRORS
- ALL_SAGA_FINALIZATION, DBA_SAGA_FINALIZATION, and USER_SAGA_FINALIZATION
- ALL_SAGA_PARTICIPANT_SET, DBA_SAGA_PARTICIPANT_SET, and USER_SAGA_PARTICIPANT_SET

  - ALL_SAGA_PARTICIPANTS, DBA_SAGA_PARTICIPANTS, and USER_SAGA_PARTICIPANTS
  - ALL_SAGA_PENDING, DBA_SAGA_PENDING, and USER_SAGA_PENDING
  - ALL_SAGAS, DBA_SAGAS, and USER_SAGAS
  - DBA_SCHEDULER_IN_MEMORY_TRACE
  - DBA_SCHEMA_PRIVS, ROLE_SCHEMA_PRIVS, SESSION_SCHEMA_PRIVS, and USER_SCHEMA_PRIVS
  - DBA_SQL_ERROR_MITIGATIONS
  - DBA_SQL_FIREWALL_ALLOW_LISTS
  - DBA_SQL_FIREWALL_ALLOWED_IP_ADDR
  - DBA_SQL_FIREWALL_ALLOWED_OS_PROG
  - DBA_SQL_FIREWALL_ALLOWED_OS_USER
  - DBA_SQL_FIREWALL_ALLOWED_SQL
  - DBA_SQL_FIREWALL_CAPTURE_LOGS
  - DBA_SQL_FIREWALL_CAPTURES
  - DBA_SQL_FIREWALL_SESSION_LOGS
  - DBA_SQL_FIREWALL_SQL_LOGS
  - DBA_SQL_FIREWALL_STATUS
  - DBA_SQL_FIREWALL_VIOLATIONS
  - DBA_SYS_PRIVS_ALL, ROLE_SYS_PRIVS_ALL, SESSION_PRIVS_ALL, and USER_SYS_PRIVS_ALL
  - ALL_TABLE_ACCESS_STATS, DBA_TABLE_ACCESS_STATS, and USER_TABLE_ACCESS_STATS
  - ALL_TABLE_VIRTUAL_COLUMNS, DBA_TABLE_VIRTUAL_COLUMNS, and USER_TABLE_VIRTUAL_COLUMNS
  - ALL_TXEVENTQ_MIGRATION_STATUS, DBA_TXEVENTQ_MIGRATION_STATUS and USER_TXEVENTQ_MIGRATION_STATUS
  - DBA_UNUSED_SCHEMA_PRIVS
  - DBA_UNUSED_SCHEMA_PRIVS_PATH
  - DBA_USED_SCHEMA_PRIVS
  - DBA_USED_SCHEMA_PRIVS_PATH
  - SHARD_RAFT_PARAMETERS
- The following tables are new in Oracle Database 23ai:
  - DBMS_KAFKA_APPLICATIONS
  - DBMS_KAFKA_CLUSTERS
  - DBMS_KAFKA_LOAD_METRICS
  - DBMS_KAFKA_MESSAGES
  - DBMS_KAFKA_OPS
  - DBMS_KAFKA_OPS_RESULTS

  - DBMS_KAFKA_PARTITIONS
  - DBMS_KAFKA_SEC_ALLOWED_PROPERTIES
- The following dynamic performance views are new in Oracle Database 23ai:
  - V$AUTO_IM_FEATURES
  - V$DATAPUMP_SESSIONWAIT_INFO
  - V$DG_BROKER_ROLE_CHANGE
  - V$ENABLEDSCHEMAPRIVS
  - V$FAST_START_FAILOVER_CONFIG
  - V$FLASHBACK_LOG_DEST
  - V$INMEMORY_SIZE_ADVICE
  - V$OFS_THREADS
  - V$PX_PROCESS_DETAIL
  - V$PX_SERVER
  - V$RECOVERY_WORKER
  - V$SCHEDULER_IN_MEMORY_TRACE
  - V$SECUREFILE_SHRINK
  - V$SERVICE_DRAIN_TIMEOUT_ADVICE
  - V$SHARD_ACK_RECEIVER
  - V$SHARD_ACK_SENDER
  - V$SHARD_APPLY_COORDINATOR
  - V$SHARD_APPLY_LCR_READER
  - V$SHARD_APPLY_READER
  - V$SHARD_APPLY_SERVER
  - V$SHARD_LCR_LOGS
  - V$SHARD_LCR_PERSISTER
  - V$SHARD_LCR_PRODUCER
  - V$SHARD_NETWORK_RECEIVER
  - V$SHARD_NETWORK_SENDER
  - V$SHARD_REPLICATION_UNIT
  - V$SQL_HISTORY
  - V$TABLE_ACCESS_STATS
  - V$TDM_STATS
  - V$TEXT_WAITING_EVENTS
  - V$TRUE_CACHE

> **See Also:**
>
> *Oracle Database New Features* for a complete list of new features for this release

1.2 Deprecated Features

The following features are deprecated in Oracle Database 23ai, and may be desupported in a future release:

Initialization parameters:

- ENCRYPT_NEW_TABLESPACES
- ONE_STEP_PLUGIN_FOR_PDB_WITH_TDE
- PRE_PAGE_SGA

Static data dictionary views:

- DBA_HANG_MANAGER_PARAMETERS

Dynamic performance views:

- V$FS_FAILOVER_STATS
- V$PQ_SLAVE
- V$RECOVERY_SLAVE

> **See Also:**
>
> *Oracle Database Upgrade Guide* for a complete list of deprecated features for this release

1.3 Desupported Features

The following features are desupported in Oracle Database 23ai:

- The `OPTIMIZER_SECURE_VIEW_MERGING` initialization parameter
- The `V$EMX_USAGE_STATS` view

> **See Also:**
>
> *Oracle Database Upgrade Guide* for a complete list of desupported features for this release

Part I
Initialization Parameters

Database initialization parameters can be specified in a parameter file to start or configure an instance.

This part contains the following chapter:

- Initialization Parameters

> **Note:**
>
> A multitenant container database is the only supported architecture in Oracle Database 21c and later releases. While the documentation is being revised, legacy terminology may persist. In most cases, "database" and "non-CDB" refer to a CDB or PDB, depending on context. In some contexts, such as upgrades, "non-CDB" refers to a non-CDB from a previous release.

2
Initialization Parameters

This chapter contains detailed descriptions (in alphabetical order) of the database initialization parameters.

This chapter contains the following topics:

- Uses of Initialization Parameters
- Basic Initialization Parameters
- Parameter Files
- Changing Parameter Values in a Parameter File
- Reading the Parameter Descriptions
- Initialization Parameter Descriptions

2.1 Uses of Initialization Parameters

Initialization parameters are used to perform various functions.

For example, initialization parameters are used to:

- Set limits for the entire database
- Set user or process limits
- Set limits on database resources
- Affect performance (these are called **variable parameters**)

  Variable parameters are of particular interest to database administrators, because these parameters are used primarily to improve database performance.

Database administrators can use initialization parameters to:

- Optimize performance by adjusting memory structures, such as the number of database buffers in memory
- Set database-wide defaults, such as the amount of space initially allocated for a context area when it is created
- Set database limits, such as the maximum number of database users
- Specify names of files or directories required by the database

Many initialization parameters can be fine-tuned to improve database performance. Other parameters should never be altered or should be altered only under the supervision of Oracle Support Services.

All initialization parameters are optional. Oracle has a default value for each parameter. This value may be operating system-dependent, depending on the parameter.

2.1.1 Types of Initialization Parameters

The Oracle database server has derived parameters, operating system-dependent parameters, and variable parameters.

- Derived Parameters
- Operating System-Dependent Parameters
- Variable Parameters (these can be dynamic parameters or any of the preceding ones)

2.1.1.1 Derived Parameters

Some initialization parameters are **derived**, meaning that their values are calculated from the values of other parameters. Normally, you should not alter values for derived parameters, but if you do, then the value you specify will override the calculated value.

For example, the default value of the `SESSIONS` parameter is derived from the value of the `PROCESSES` parameter. If the value of `PROCESSES` changes, then the default value of `SESSIONS` changes as well, unless you override it with a specified value.

2.1.1.2 Operating System-Dependent Parameters

The valid values or value ranges of some initialization parameters depend upon the host operating system. For example, the parameter `DB_BLOCK_BUFFERS` indicates the number of data buffers in main memory, and its maximum value depends on the operating system. The size of those buffers, set by `DB_BLOCK_SIZE`, has an operating system-dependent default value.

> **See Also:**
>
> Your operating system-specific Oracle documentation for more information on operating system-dependent Oracle parameters and operating system parameters

2.1.1.3 Variable Parameters

The variable initialization parameters offer the most potential for improving system performance. Some variable parameters set capacity limits but do not affect performance. For example, when the value of `OPEN_CURSORS` is 10, a user process attempting to open its eleventh cursor receives an error. Other variable parameters affect performance but do not impose absolute limits. For example, reducing the value of `DB_BLOCK_BUFFERS` does not prevent work even though it may slow down performance.

Increasing the values of variable parameters may improve your system's performance, but increasing most parameters also increases the system global area (SGA) size. A larger SGA can improve database performance up to a point. In virtual memory operating systems, an SGA that is too large can degrade performance if it is swapped in and out of memory. Operating system parameters that control virtual memory

working areas should be set with the SGA size in mind. The operating system configuration can also limit the maximum size of the SGA.

2.2 Basic Initialization Parameters

Most databases should only need to have the database basic initialization parameters set to run properly and efficiently.

Oracle advises you to become familiar with the basic parameters and only use other parameters when directed to by feature documentation or in special circumstances. The following is a list of the database basic initialization parameters:

CLUSTER_DATABASE
COMPATIBLE
CONTROL_FILES
DB_BLOCK_SIZE
DB_CREATE_FILE_DEST
DB_CREATE_ONLINE_LOG_DEST_*n*
DB_DOMAIN
DB_NAME
DB_RECOVERY_FILE_DEST
DB_RECOVERY_FILE_DEST_SIZE
DB_UNIQUE_NAME
INSTANCE_NUMBER
LDAP_DIRECTORY_SYSAUTH
LOG_ARCHIVE_DEST_*n*
LOG_ARCHIVE_DEST_STATE_*n*
NLS_DATE_LANGUAGE
NLS_TERRITORY
OPEN_CURSORS
PGA_AGGREGATE_TARGET
PROCESSES
REMOTE_LISTENER
REMOTE_LOGIN_PASSWORDFILE
SESSIONS
SGA_TARGET
SHARED_SERVERS
STAR_TRANSFORMATION_ENABLED
UNDO_TABLESPACE

2.3 Parameter Files

A **parameter file** is a file that contains a list of initialization parameters and a value for each parameter. You specify initialization parameters in a parameter file that reflect your particular installation.

Oracle supports the following two types of parameter files:

- Server Parameter Files
- Initialization Parameter Files

2.3.1 Server Parameter Files

A **server parameter file** is a binary file that acts as a repository for initialization parameters.

The server parameter file can reside on the computer where the Oracle database server executes. Initialization parameters stored in a server parameter file are persistent, in that any changes made to the parameters while an instance is running can persist across instance shutdown and startup.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for an introduction to and detailed information about managing and using server parameter files and initialization parameter files

2.3.2 Initialization Parameter Files

An **initialization parameter file** is a text file that contains a list of initialization parameters.

> **Note:**
>
> See "About the Character Set of Parameter Values" for more information about the character set to use when specifying values in an initialization parameter file.

The following are sample entries in an initialization parameter file:

```
PROCESSES = 100
OPEN_LINKS = 12
GLOBAL_NAMES = true
```

The name of the initialization parameter file varies depending on the operating system. For example, it can be in mixed case or lowercase, or it can have a logical name or a variation of the name `init.ora`. Also supplied is an `initdw.ora` file, which contains suggested parameter settings for data warehouses and data marts. The database administrator can choose a different file name for the initialization parameter file.

Refer to your operating system-specific Oracle documentation for the default locations and filenames for initialization parameter files on your operating system. The initialization parameter file is read by the client-side tool used to start the server (such as SQL*Plus).

Sample initialization parameter files are provided on the Oracle distribution medium for each operating system. A sample file is sufficient for initial use, but you will probably want to modify the file to tune the database for best performance. Any changes will take effect after you completely shut down and restart the instance.

2.3.2.1 About the Character Set of Parameter Values

Only characters from the default character set of the database platform are supported in parameter values. For all platforms except IBM z/OS and Fujitsu BS2000 the default platform character set is US7ASCII (7-bit ASCII).

The database behavior is undefined when parameter values with unsupported characters are specified. When using the `ALTER SYSTEM` statement to set a parameter value in a server parameter file, make sure only supported characters are used. The database does not always report an error when a value with unsupported characters is specified.

The initialization parameter file is a client-side file. When used, it is located on the host on which you start SQL*Plus to start up a database instance. The initialization parameter file must be written in the client character set as specified by the `NLS_LANG` client setting. However, parameter values should not contain characters not supported by the default character set of the database.

2.3.2.2 Specifying Values in an Initialization Parameter File

This section describes several aspects of setting parameter values in an initialization parameter file.

2.3.2.2.1 Rules Governing Initialization Parameter Files

This section describes the rules that govern the specification of parameters in initialization parameter files.

- An initialization parameter file should contain only parameters and comments. A pound sign (#) starts a comment line. The rest of the line is ignored.
- Comments must use the same character set as parameter values.
- You can specify parameters in any order.
- Case (upper or lower) in filenames is significant only if case is significant on the host operating system.
- To enter several parameters on one line, use spaces between parameter names and values, as in the following example:

  ```
  PROCESSES = 100 CPU_COUNT = 1 OPEN_CURSORS = 10
  ```

- Some parameters, such as `ROLLBACK_SEGMENTS`, accept multiple values. Any of the following represent valid syntax.
  - Enter multiple values enclosed in parentheses and separated by commas. For example:

    ```
    ROLLBACK_SEGMENTS = (SEG1, SEG2, SEG3, SEG4, SEG5)
    ```

  - Enter multiple values without parentheses and commas. For example:

    ```
    ROLLBACK_SEGMENTS = SEG1 SEG2 SEG3 SEG4 SEG5
    ```

  - Enter multiple values, one per line. For example:

    ```
    ROLLBACK_SEGMENTS = SEG1
    ROLLBACK_SEGMENTS = SEG2
    ROLLBACK_SEGMENTS = SEG3
    ROLLBACK_SEGMENTS = SEG4
    ROLLBACK_SEGMENTS = SEG5
    ```

If you enter values for one parameter on multiple lines, then the entries must be on consecutive lines. If they are not, then the first entry will not be processed properly. For example, in the following entry the setting for `SEG3` and `SEG4` will override the setting for `SEG1` and `SEG2`:

```
ROLLBACK_SEGMENTS = SEG1 SEG2
OPEN_CURSORS = 10
ROLLBACK_SEGMENTS = SEG3 SEG4
```

- A backslash (\), also known as an escape character, indicates continuation of the parameter specification. If a backslash continues a line, then the continued line must have no leading spaces. For example:

```
ROLLBACK_SEGMENTS = (SEG1, SEG2, \
SEG3, SEG4, SEG5)
```

- You can use the `IFILE` initialization parameter to embed the contents of another initialization parameter file into the current initialization parameter file.
- Enclose in quotation marks any parameter values that contain spaces or tabs. You can use either single or double quotation marks unless otherwise indicated. For example:

```
NLS_TERRITORY = 'CZECH REPUBLIC'
```

> **Note:**
>
> Listing parameters in alphabetical order in the initialization parameter file can help you to find them and can help ensure that each parameter is specified only once.

- Enclose in quotation marks any parameter value that contains a special character.

> **See Also:**
>
> - Your operating system-specific Oracle documentation for more information on initialization parameter files
> - "IFILE"

2.3.2.2.2 Using Expressions for Parameter Values

You can specify an expression as the value for an initialization parameter.

The optimal value for an initialization parameter can depend on environmental characteristics, such as system configurations, run-time decisions, and the values of other parameters. In previous releases, you were required to specify an absolute value when setting an initialization parameter, which meant that maintaining its optimal value required manual oversight and adjustments. Starting with Oracle Database 21c, you can specify an expression as the value for some initialization parameters, which enables the database to automatically adjust the parameter value in response to environmental changes.

Specifying an expression for a parameter value is also useful in Oracle Real Application Cluster (Oracle RAC) environments. You can specify the same expression for a parameter value across all Oracle RAC instances, but the expression will be evaluated on a per-instance basis, utilizing the environmental characteristics of the current instance. This allows the database to fine-tune the parameter value for each Oracle RAC instance.

You can specify expressions only for initialization parameters of type integer or big integer.

Initialization parameter expressions can contain the following constructs:

1. Integer values

   ```
   OLAP_PAGE_POOL_SIZE = 1073741824
   ```

2. Decimal values, but only when they are part of a numeric operation

   ```
   CPU_COUNT = 8 * 0.6
   ```

   If the operation evaluates to a decimal value, then the result is truncated to an integer value. The above example would set `CPU_COUNT` to `4`.

3. An integer value followed by an indicator that the integer is expressed in kilobytes (`k` or `K`), megabytes (`m` or `M`), gigabytes (`g` or `G`), terabytes (`t` or `T`), petabytes (`p` or `P`), or exabytes (`e` or `E`)

   ```
   OLAP_PAGE_POOL_SIZE = 900m
   MEMORY_TARGET = 2G
   ```

4. Other parameter names

   ```
   JOB_QUEUE_PROCESSES = PROCESSES
   ```

5. The binary operators for multiplication (`*`), division (`/`), modulo (`%`), addition (`+`), and subtraction (`-`)

   ```
   SHARED_SERVERS = MAX_SHARED_SERVERS / 2
   DATA_GUARD_MAX_LONGIO_TIME = DATA_GUARD_MAX_IO_TIME + 10 * 3
   ```

   Operator precedence: the multiplication, division, and modulo operators are evaluated first, from left to right, and then the addition and subtraction operators are evaluated from left to right.

   If the expression evaluates to a decimal value, then the result is truncated to an integer value.

6. Parentheses, which allow you to override operator precedence

   ```
   SHARED_SERVERS = (MAX_SHARED_SERVERS - 1) / 2
   DATA_GUARD_MAX_LONGIO_TIME = (DATA_GUARD_MAX_IO_TIME + 10) * 3
   ```

7. The `MIN` and `MAX` functions. These functions take two operands and return the minimum and maximum value, respectively.

```
AQ_TM_PROCESSES = MIN(40, PROCESSES * .1)
SESSIONS = MAX(200, PROCESSES * 1.5)
```

8. Environment variable values, which must be preceded by the dollar sign (`$`)

```
CPU_COUNT = $SYSTEM_CPU/5
```

You can specify an expression when using any of the following methods to set an initialization parameter:

- In a server parameter file (SPFILE)
- In a text initialization parameter file, for example, `init`*`ORACLE_SID`*`.ora`.

  Note that you cannot use expressions in a client-side text initialization parameter file (PFILE).
- In the SQL statements `ALTER SESSION SET` and `ALTER SYSTEM SET`. In this case you must enclose the expression in single quotation marks. For example:

```
ALTER SESSION SET AQ_TM_PROCESSES = 'MIN(40, PROCESSES * .1)';
ALTER SYSTEM SET JOB_QUEUE_PROCESSES = 'PROCESSES' SCOPE=BOTH;
```

2.3.2.2.3 Using Special Characters in Parameter Values

If a parameter value contains a special character, then the special character must be preceded by a backslash or the entire parameter value must be enclosed in quotation marks.

For example, you can specify special characters using either of the following:

```
DB_DOMAIN = 'JAPAN.ACME#.COM'

DB_DOMAIN = JAPAN.ACME\#.COM
```

Table 2-1 lists the special characters you can use in initialization parameter files.

Table 2-1 Special Characters in Initialization Parameter Files

Character	Name	Description
#	Number sign	Comment
(	Left parenthesis	Start list of values
)	Right parenthesis	End list of values
"	Double quotation mark	Start or end of quoted string
'	Single quotation mark	Start or end of quoted string
=	Equal sign	Separator of keyword and values
,	Comma	Separator of elements
-	Minus sign	Precedes UNIX-style keywords
\	Backslash	Escape character

If a special character must be treated literally in an initialization parameter file, then it must either be preceded by the backslash character, or the entire string containing the special character must be enclosed in quotation marks.

2.3.2.2.4 Using the Escape Character

In an initialization parameter file, a backslash (\) can also signify a line continuation. If the backslash is followed by an alphanumeric character, then the backslash is treated as a normal character in the input.

If it is not followed by an alphanumeric character, then the backslash is treated either as a backslash or as a continuation character.

> **See Also:**
>
> "Rules Governing Initialization Parameter Files"

2.3.2.2.5 Using Quotation Marks

Quotation marks can be nested in two ways in an initialization parameter file.

The first method is to double the quotation marks in the nested string. For example:

```
NLS_DATE_FORMAT = '''Today is'' MM/DD/YYYY'
```

The second method is to alternate single and double quotation marks. For example:

```
NLS_DATE_FORMAT = '"Today is" MM/DD/YYYY'
```

2.4 Changing Parameter Values in a Parameter File

You can change the value of a parameter in a parameter file in several ways.

- By editing an initialization parameter file

  In most cases, the new value takes effect the next time you start an instance of the database.
- By issuing an `ALTER SYSTEM SET ... SCOPE=SPFILE` statement to update a server parameter file
- By issuing an `ALTER SYSTEM RESET` statement to clear an initialization parameter value.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about using the `ALTER SYSTEM RESET` statement to clear initialization parameter values

2.4.1 Parameters by Functional Category

This section lists initialization parameters by their functional category.

- **ANSI Compliance**

BLANK_TRIMMING

- **Backup and Restore**

  BACKUP_TAPE_IO_SLAVES
  DATA_TRANSFER_CACHE_SIZE
  CLONEDB
  CLONEDB_DIR
  RECYCLEBIN
  TAPE_ASYNCH_IO

- **BFILEs**

  SESSION_MAX_OPEN_FILES

- **Buffer Cache and I/O**

  CLIENT_RESULT_CACHE_LAG
  CLIENT_RESULT_CACHE_SIZE
  DB_*n*K_CACHE_SIZE
  DB_BIG_TABLE_CACHE_PERCENT_TARGET
  DB_BLOCK_BUFFERS
  DB_BLOCK_SIZE
  DB_CACHE_ADVICE
  DB_CACHE_SIZE
  DB_FILE_MULTIBLOCK_READ_COUNT
  DB_KEEP_CACHE_SIZE
  DB_RECYCLE_CACHE_SIZE
  DB_WRITER_PROCESSES
  DBWR_IO_SLAVES
  DISK_ASYNCH_IO
  DNFS_BATCH_SIZE
  FILESYSTEMIO_OPTIONS
  IORM_LIMIT_POLICY
  READ_ONLY
  READ_ONLY_OPEN_DELAYED
  RESULT_CACHE_AUTO_BLOCKLIST
  RESULT_CACHE_EXECUTION_THRESHOLD
  RESULT_CACHE_INTEGRITY
  RESULT_CACHE_MAX_RESULT
  RESULT_CACHE_MAX_SIZE
  RESULT_CACHE_MAX_TEMP_RESULT
  RESULT_CACHE_MAX_TEMP_SIZE
  RESULT_CACHE_MODE

- **Cursors and Library Cache**

  CURSOR_BIND_CAPTURE_DESTINATION
  CURSOR_INVALIDATION
  CURSOR_SHARING
  CURSOR_SPACE_FOR_TIME
  OPEN_CURSORS
  SESSION_CACHED_CURSORS

- **Database/Instance Identification**

DB_DOMAIN
DB_NAME
INSTANCE_NAME

- **Diagnostics and Statistics**

  BACKGROUND_CORE_DUMP
  BACKGROUND_DUMP_DEST
  CLIENT_STATISTICS_LEVEL
  CORE_DUMP_DEST
  DB_BLOCK_CHECKING
  DB_BLOCK_CHECKSUM
  DIAGNOSTIC_DEST
  DIAGNOSTICS_CONTROL
  ERROR_MESSAGE_DETAILS
  EVENT
  HEAT_MAP
  MAX_DUMP_FILE_SIZE
  SHADOW_CORE_DUMP
  SQL_ERROR_MITIGATION
  SQL_HISTORY_ENABLED
  STATISTICS_LEVEL
  TIMED_OS_STATISTICS
  TIMED_STATISTICS
  TRACE_ENABLED
  TRACEFILE_IDENTIFIER
  USER_DUMP_DEST

- **Distributed, Replication**

  COMMIT_POINT_STRENGTH
  DISTRIBUTED_LOCK_TIMEOUT
  ENABLE_GOLDENGATE_REPLICATION
  GLOBAL_NAMES
  HS_AUTOREGISTER
  OPEN_LINKS
  OPEN_LINKS_PER_INSTANCE
  REPLICATION_DEPENDENCY_TRACKING

- **File Locations, Names, and Sizes**

  AUDIT_FILE_DEST
  BACKGROUND_CORE_DUMP
  BACKGROUND_DUMP_DEST
  CONTROL_FILES
  CORE_DUMP_DEST
  DB_CREATE_FILE_DEST
  DB_CREATE_ONLINE_LOG_DEST_*n*
  DB_FILES
  DB_RECOVERY_FILE_DEST
  DB_RECOVERY_FILE_DEST_SIZE
  FILE_MAPPING
  IFILE

LOG_ARCHIVE_DEST_*n*
SPFILE

- **Globalization**

  NLS_CALENDAR
  NLS_COMP
  NLS_CURRENCY
  NLS_DATE_FORMAT
  NLS_DATE_LANGUAGE
  NLS_DUAL_CURRENCY
  NLS_ISO_CURRENCY
  NLS_LANGUAGE
  NLS_LENGTH_SEMANTICS
  NLS_NCHAR_CONV_EXCP
  NLS_NUMERIC_CHARACTERS
  NLS_SORT
  NLS_TERRITORY
  NLS_TIMESTAMP_FORMAT
  NLS_TIMESTAMP_TZ_FORMAT
  TIMEZONE_VERSION_UPGRADE_ONLINE

- **Java**

  JAVA_JIT_ENABLED
  JAVA_MAX_SESSIONSPACE_SIZE
  JAVA_POOL_SIZE
  JAVA_SOFT_SESSIONSPACE_LIMIT

- **Job Queues**

  JOB_QUEUE_PROCESSES

- **License Limits**

  LICENSE_MAX_SESSIONS
  LICENSE_MAX_USERS
  LICENSE_SESSIONS_WARNING

- **Memory**

  INMEMORY_ADG_ENABLED
  INMEMORY_AUTOMATIC_LEVEL
  INMEMORY_CLAUSE_DEFAULT
  INMEMORY_DEEP_VECTORIZATION
  INMEMORY_EXPRESSIONS_USAGE
  INMEMORY_FORCE
  INMEMORY_MAX_POPULATE_SERVERS
  INMEMORY_OPTIMIZED_ARITHMETIC
  INMEMORY_QUERY
  INMEMORY_SIZE
  INMEMORY_TRICKLE_REPOPULATE_SERVERS_PERCENT
  INMEMORY_VIRTUAL_COLUMNS
  MEMOPTIMIZE_POOL_SIZE
  MEMOPTIMIZE_WRITE_AREA_SIZE
  MEMOPTIMIZE_WRITES

MEMORY_MAX_SIZE
MEMORY_SIZE
MEMORY_MAX_TARGET
MEMORY_TARGET
PMEM_FILESTORE

- **Miscellaneous**

  ALLOW_ROWID_COLUMN_TYPE
  AQ_TM_PROCESSES
  ASM_IO_PROCESSES
  ASM_PREFERRED_READ_FAILURE_GROUPS
  AWR_SNAPSHOT_TIME_OFFSET
  COMPATIBLE
  DB_INDEX_COMPRESSION_INHERITANCE
  ENABLE_DNFS_DISPATCHER
  FIXED_DATE
  GROUP_BY_POSITION_ENABLED
  IGNORE_SESSION_SET_PARAM_ERRORS
  INSTANCE_ABORT_DELAY_TIME
  JSON_BEHAVIOR
  JSON_EXPRESSION_CHECK
  LDAP_DIRECTORY_SYSAUTH
  MAX_COLUMNS
  MAX_DATAPUMP_JOBS_PER_PDB
  MAX_DATAPUMP_PARALLEL_PER_JOB
  MAX_STRING_SIZE
  MLE_PROG_LANGUAGES
  PRIVATE_TEMP_TABLE_PREFIX
  SPATIAL_VECTOR_ACCELERATION
  TIME_AT_DBTIMEZONE
  UNIFORM_LOG_TIMESTAMP_FORMAT
  XML_DB_EVENTS
  XML_PARAMS

- **Multitenant Architecture**

  AUTOTASK_MAX_ACTIVE_PDBS
  AWR_PDB_AUTOFLUSH_ENABLED
  COMMON_USER_PREFIX
  CONTAINER_DATA
  CONTAINERS_PARALLEL_DEGREE
  CPU_MIN_COUNT
  DB_PERFORMANCE_PROFILE
  DBNEST_ENABLE
  DBNEST_PDB_FS_CONF
  DEFAULT_SHARING
  ENABLE_AUTOMATIC_MAINTENANCE_PDB
  ENABLED_PDBS_ON_STANDBY
  EXTERNAL_KEYSTORE_CREDENTIAL_LOCATION
  HYBRID_READ_ONLY
  MAX_IOPS

MAX_MBPS
MAX_PDBS
NONCDB_COMPATIBLE
PDB_FILE_NAME_CONVERT
PDB_LOCKDOWN
PDB_OS_CREDENTIAL
SGA_MIN_SIZE

- **Networking**

  CONNECTION_BROKERS
  DRCP_DEDICATED_OPT
  ENABLE_PER_PDB_DRCP
  FORWARD_LISTENER
  LOCAL_LISTENER
  MAX_AUTH_SERVERS
  MIN_AUTH_SERVERS
  OFS_THREADS
  REMOTE_LISTENER
  SERVICE_NAMES

- **Objects and LOBs**

  OBJECT_CACHE_MAX_SIZE_PERCENT
  OBJECT_CACHE_OPTIMAL_SIZE

- **OLAP**

  OLAP_PAGE_POOL_SIZE

- **Optimizer**

  APPROX_FOR_AGGREGATION
  APPROX_FOR_COUNT_DISTINCT
  APPROX_FOR_PERCENTILE
  OPTIMIZER_ADAPTIVE_PLANS
  OPTIMIZER_ADAPTIVE_REPORTING_ONLY
  OPTIMIZER_ADAPTIVE_STATISTICS
  OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES
  OPTIMIZER_CAPTURE_SQL_QUARANTINE
  OPTIMIZER_DYNAMIC_SAMPLING
  OPTIMIZER_FEATURES_ENABLE
  OPTIMIZER_IGNORE_HINTS
  OPTIMIZER_IGNORE_PARALLEL_HINTS
  OPTIMIZER_INDEX_CACHING
  OPTIMIZER_INDEX_COST_ADJ
  OPTIMIZER_INMEMORY_AWARE
  OPTIMIZER_MODE
  OPTIMIZER_REAL_TIME_STATISTICS
  OPTIMIZER_SESSION_TYPE
  OPTIMIZER_USE_PENDING_STATISTICS
  OPTIMIZER_USE_SQL_PLAN_BASELINES
  OPTIMIZER_USE_SQL_QUARANTINE
  QUERY_REWRITE_ENABLED

QUERY_REWRITE_INTEGRITY
STAR_TRANSFORMATION_ENABLED

- **Oracle RAC**

  ACTIVE_INSTANCE_COUNT
  CLUSTER_DATABASE
  CLUSTER_INTERCONNECTS
  INSTANCE_NUMBER
  PARALLEL_INSTANCE_GROUP
  THREAD

- **Parallel Execution**

  PARALLEL_ADAPTIVE_MULTI_USER
  PARALLEL_EXECUTION_MESSAGE_SIZE
  PARALLEL_MAX_SERVERS
  PARALLEL_MIN_DEGREE
  PARALLEL_MIN_PERCENT
  PARALLEL_MIN_SERVERS
  PARALLEL_THREADS_PER_CPU

- **PL/SQL**

  LONG_MODULE_ACTION
  PLSQL_IMPLICIT_CONVERSION_BOOL
  PLSQL_V2_COMPATIBILITY
  REMOTE_DEPENDENCIES_MODE
  SESSION_EXIT_ON_PACKAGE_STATE_ERROR

- **PL/SQL Compiler**

  NLS_LENGTH_SEMANTICS
  PERMIT_92_WRAP_FORMAT
  PLSCOPE_SETTINGS
  PLSQL_CCFLAGS
  PLSQL_CODE_TYPE
  PLSQL_DEBUG
  PLSQL_OPTIMIZE_LEVEL
  PLSQL_WARNINGS
  SQL_TRANSPILER

- **Redo Logs, Archiving, and Recovery**

  ADG_ACCOUNT_INFO_TRACKING
  ADG_REDIRECT_DML
  CONTROL_FILE_RECORD_KEEP_TIME
  DATA_GUARD_MAX_IO_TIME
  DATA_GUARD_MAX_LONGIO_TIME
  DATA_GUARD_SYNC_LATENCY
  DB_CREATE_ONLINE_LOG_DEST_*n*
  DB_FLASHBACK_LOG_DEST
  DB_FLASHBACK_LOG_DEST_SIZE
  DB_RECOVERY_FILE_DEST
  DB_RECOVERY_FILE_DEST_SIZE
  DB_UNRECOVERABLE_SCN_TRACKING

FAST_START_MTTR_TARGET
LOG_ARCHIVE_CONFIG
LOG_ARCHIVE_DEST_*n*
LOG_ARCHIVE_DEST_STATE_*n*
LOG_ARCHIVE_DUPLEX_DEST
LOG_ARCHIVE_FORMAT
LOG_ARCHIVE_MAX_PROCESSES
LOG_ARCHIVE_MIN_SUCCEED_DEST
LOG_ARCHIVE_TRACE
LOG_BUFFER
LOG_CHECKPOINT_INTERVAL
LOG_CHECKPOINT_TIMEOUT
LOG_CHECKPOINTS_TO_ALERT
RECOVERY_PARALLELISM
REDO_TRANSPORT_USER
REMOTE_RECOVERY_FILE_DEST

- **Resource Manager**

  MAX_IDLE_BLOCKER_TIME
  MAX_IDLE_TIME
  PROCESSOR_GROUP_NAME
  RESOURCE_LIMIT
  RESOURCE_MANAGER_CPU_ALLOCATION
  RESOURCE_MANAGER_CPU_SCOPE
  RESOURCE_MANAGER_PLAN
  SGA_MIN_SIZE
  STANDBY_DB_PRESERVE_STATES

- **Security and Auditing**

  ALLOW_GLOBAL_DBLINKS
  ALLOW_GROUP_ACCESS_TO_SGA
  ALLOW_LEGACY_RECO_PROTOCOL
  AUDIT_FILE_DEST
  AUDIT_SYS_OPERATIONS
  AUDIT_SYSLOG_LEVEL
  AUDIT_TRAIL
  BLOCKCHAIN_TABLE_MAX_NO_DROP
  BLOCKCHAIN_TABLE_RETENTION_THRESHOLD
  COMMIT_LOGGING
  COMMIT_WAIT
  DBFIPS_140
  ENCRYPT_NEW_TABLESPACES
  HEARTBEAT_BATCH_SIZE
  IDENTITY_PROVIDER_CONFIG
  IDENTITY_PROVIDER_TYPE
  LOB_SIGNATURE_ENABLE
  MANDATORY_USER_PROFILE
  OS_AUTHENT_PREFIX
  OS_ROLES
  OUTBOUND_DBLINK_PROTOCOLS

PKCS11_LIBRARY_LOCATION
RDBMS_SERVER_DN
REMOTE_LOGIN_PASSWORDFILE
REMOTE_OS_ROLES
SEC_MAX_FAILED_LOGIN_ATTEMPTS
SEC_PROTOCOL_ERROR_FURTHER_ACTION
SEC_PROTOCOL_ERROR_TRACE_ACTION
SEC_RETURN_SERVER_RELEASE_BANNER
SQL92_SECURITY
TABLESPACE_ENCRYPTION
TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM
TDE_CONFIGURATION
TDE_KEY_CACHE
UNIFIED_AUDIT_COMMON_SYSTEMLOG
UNIFIED_AUDIT_SYSTEMLOG
WALLET_ROOT

- **Sessions and Processes**

  CPU_COUNT
  CPU_MIN_COUNT
  PROCESSES
  SESSIONS
  THREADED_EXECUTION
  USE_DEDICATED_BROKER

- **SGA Memory**

  DB_*n*K_CACHE_SIZE
  DB_CACHE_SIZE
  HI_SHARED_MEMORY_ADDRESS
  JAVA_POOL_SIZE
  LARGE_POOL_SIZE
  LOCK_SGA
  OLAP_PAGE_POOL_SIZE
  PRE_PAGE_SGA
  SGA_MAX_SIZE
  SGA_MIN_SIZE
  SGA_TARGET
  SHARED_MEMORY_ADDRESS
  SHARED_POOL_RESERVED_SIZE
  SHARED_POOL_SIZE
  STREAMS_POOL_SIZE
  USE_LARGE_PAGES

- **Sharding**

  MULTISHARD_QUERY_DATA_CONSISTENCY
  OPTIMIZER_CROSS_SHARD_RESILIENCY
  SHARD_ENABLE_RAFT_FOLLOWER_READ
  SHARD_RAFT_LOGFILE_SIZE
  SHRD_DUPL_TABLE_REFRESH_RATE

- **Shared Server Architecture**

CIRCUITS
DISPATCHERS
MAX_DISPATCHERS
MAX_SHARED_SERVERS
SHARED_SERVER_SESSIONS
SHARED_SERVERS

- **Standby Database**

  ARCHIVE_LAG_TARGET
  DB_FILE_NAME_CONVERT
  DB_RECOVERY_AUTO_REKEY
  DB_UNIQUE_NAME
  DG_BROKER_CONFIG_FILE*n*
  DG_BROKER_START
  ENABLE_IMC_WITH_MIRA
  FAL_CLIENT
  FAL_SERVER
  LOG_FILE_NAME_CONVERT
  STANDBY_FILE_MANAGEMENT
  STANDBY_PDB_SOURCE_FILE_DBLINK
  STANDBY_PDB_SOURCE_FILE_DIRECTORY

- **Temporary Sort Space**

  BITMAP_MERGE_AREA_SIZE
  CREATE_BITMAP_AREA_SIZE
  HASH_AREA_SIZE
  PGA_AGGREGATE_LIMIT
  PGA_AGGREGATE_TARGET
  SORT_AREA_RETAINED_SIZE
  SORT_AREA_SIZE
  WORKAREA_SIZE_POLICY

- **Transactions**

  COMMIT_LOGGING
  COMMIT_WAIT
  DB_LOST_WRITE_PROTECT
  DDL_LOCK_TIMEOUT
  DML_LOCKS
  FAST_START_PARALLEL_ROLLBACK
  GLOBAL_TXN_PROCESSES
  MAX_SAGA_DURATION
  PRIORITY_TXNS_HIGH_WAIT_TARGET
  PRIORITY_TXNS_MEDIUM_WAIT_TARGET
  PRIORITY_TXNS_MODE
  SAGA_HIST_RETENTION
  TRANSACTION_RECOVERY
  TRANSACTIONS
  TXN_PRIORITY

- **Undo Management**

RESUMABLE_TIMEOUT
ROLLBACK_SEGMENTS
TEMP_UNDO_ENABLED
TRANSACTIONS_PER_ROLLBACK_SEGMENT
UNDO_MANAGEMENT
UNDO_RETENTION
UNDO_TABLESPACE

2.4.2 Modifiable Parameters

You can modify some initialization parameters using the `ALTER SESSION` or `ALTER SYSTEM` statements while an instance is running.

Use the following syntax to modify initialization parameters:

```
ALTER SESSION SET parameter_name = value
ALTER SYSTEM SET parameter_name = value [DEFERRED]
```

Whenever a parameter is modified using the `ALTER SYSTEM` statement, the Oracle Database records the statement that modifies the parameter in the alert log.

The `ALTER SESSION` statement changes the value of the specified parameter for the duration of the session that invokes the statement. The value of the parameter does not change for other sessions in the instance. The value of the following initialization parameters can be changed with `ALTER SESSION`:

ALLOW_ROWID_COLUMN_TYPE
APPROX_FOR_AGGREGATION
APPROX_FOR_COUNT_DISTINCT
APPROX_FOR_PERCENTILE
AQ_TM_PROCESSES
ASM_DISKSTRING
ASM_POWER_LIMIT
COMMIT_LOGGING
COMMIT_WAIT
COMMIT_WRITE
CONTAINER_DATA
CONTAINERS_PARALLEL_DEGREE
CREATE_STORED_OUTLINES
CURSOR_BIND_CAPTURE_DESTINATION
CURSOR_INVALIDATION
CURSOR_SHARING
DB_BLOCK_CHECKING
DB_CREATE_FILE_DEST
DB_CREATE_ONLINE_LOG_DEST_*n*
DB_FILE_MULTIBLOCK_READ_COUNT
DB_FILE_NAME_CONVERT
DB_INDEX_COMPRESSION_INHERITANCE
DB_SECUREFILE
DB_UNRECOVERABLE_SCN_TRACKING
DDL_LOCK_TIMEOUT
DEFAULT_SHARING

DEFERRED_SEGMENT_CREATION
DIAGNOSTICS_CONTROL
DST_UPGRADE_INSERT_CONV
ENABLE_DDL_LOGGING
ERROR_MESSAGE_DETAILS
GLOBAL_NAMES
GROUP_BY_POSITION_ENABLED
HASH_AREA_SIZE
HEAT_MAP
HYBRID_READ_ONLY
IGNORE_SESSION_SET_PARAM_ERRORS
INMEMORY_CLAUSE_DEFAULT
INMEMORY_DEEP_VECTORIZATION
INMEMORY_QUERY
JAVA_JIT_ENABLED
JSON_BEHAVIOR
JSON_EXPRESSION_CHECK
LOG_ARCHIVE_DEST_*n*
LOG_ARCHIVE_DEST_STATE_*n*
LOG_ARCHIVE_MIN_SUCCEED_DEST
MAX_DUMP_FILE_SIZE
MEMOPTIMIZE_WRITES
MLE_PROG_LANGUAGES
MULTISHARD_QUERY_DATA_CONSISTENCY
NLS_CALENDAR
NLS_COMP
NLS_CURRENCY
NLS_DATE_FORMAT
NLS_DATE_LANGUAGE
NLS_DUAL_CURRENCY
NLS_ISO_CURRENCY
NLS_LANGUAGE
NLS_LENGTH_SEMANTICS
NLS_NCHAR_CONV_EXCP
NLS_NUMERIC_CHARACTERS
NLS_SORT
NLS_TERRITORY
NLS_TIMESTAMP_FORMAT
NLS_TIMESTAMP_TZ_FORMAT
OBJECT_CACHE_MAX_SIZE_PERCENT
OBJECT_CACHE_OPTIMAL_SIZE
OLAP_PAGE_POOL_SIZE
OPTIMIZER_ADAPTIVE_PLANS
OPTIMIZER_ADAPTIVE_REPORTING_ONLY
OPTIMIZER_ADAPTIVE_STATISTICS
OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES
OPTIMIZER_CAPTURE_SQL_QUARANTINE
OPTIMIZER_CROSS_SHARD_RESILIENCY
OPTIMIZER_DYNAMIC_SAMPLING

OPTIMIZER_FEATURES_ENABLE
OPTIMIZER_IGNORE_HINTS
OPTIMIZER_IGNORE_PARALLEL_HINTS
OPTIMIZER_INDEX_CACHING
OPTIMIZER_INDEX_COST_ADJ
OPTIMIZER_INMEMORY_AWARE
OPTIMIZER_MODE
OPTIMIZER_REAL_TIME_STATISTICS
OPTIMIZER_SESSION_TYPE
OPTIMIZER_USE_INVISIBLE_INDEXES
OPTIMIZER_USE_PENDING_STATISTICS
OPTIMIZER_USE_SQL_PLAN_BASELINES
OPTIMIZER_USE_SQL_QUARANTINE
PARALLEL_DEGREE_LIMIT
PARALLEL_DEGREE_POLICY
PARALLEL_FORCE_LOCAL
PARALLEL_INSTANCE_GROUP
PARALLEL_MIN_DEGREE
PARALLEL_MIN_PERCENT
PARALLEL_MIN_TIME_THRESHOLD
PDB_FILE_NAME_CONVERT
PDB_LOCKDOWN
PLSCOPE_SETTINGS
PLSQL_CCFLAGS
PLSQL_CODE_TYPE
PLSQL_DEBUG
PLSQL_IMPLICIT_CONVERSION_BOOL
PLSQL_OPTIMIZE_LEVEL
PLSQL_V2_COMPATIBILITY
PLSQL_WARNINGS
QUERY_REWRITE_ENABLED
QUERY_REWRITE_INTEGRITY
READ_ONLY
RECYCLEBIN
REMOTE_DEPENDENCIES_MODE
RESULT_CACHE_MODE
RESULT_CACHE_REMOTE_EXPIRATION
RESUMABLE_TIMEOUT
SESSION_CACHED_CURSORS
SESSION_EXIT_ON_PACKAGE_STATE_ERROR
SHARD_ENABLE_RAFT_FOLLOWER_READ
SHRD_DUPL_TABLE_REFRESH_RATE
SKIP_UNUSABLE_INDEXES
SMTP_OUT_SERVER
SORT_AREA_RETAINED_SIZE
SORT_AREA_SIZE
SPATIAL_VECTOR_ACCELERATION
SQL_ERROR_MITIGATION
SQL_HISTORY_ENABLED

SQL_TRACE
SQL_TRANSPILER
SQLTUNE_CATEGORY
STAR_TRANSFORMATION_ENABLED
STATISTICS_LEVEL
TDE_KEY_CACHE
TEMP_UNDO_ENABLED
TIMED_OS_STATISTICS
TIMED_STATISTICS
TRACEFILE_IDENTIFIER
TXN_PRIORITY
WORKAREA_SIZE_POLICY
XML_DB_EVENTS
XML_PARAMS

The `ALTER SYSTEM` statement without the `DEFERRED` keyword modifies the global value of the parameter for all sessions in the instance, for the duration of the instance (until the database is shut down). The value of the following initialization parameters can be changed with `ALTER SYSTEM`:

ADG_REDIRECT_DML
ALLOW_GLOBAL_DBLINKS
ALLOW_ROWID_COLUMN_TYPE
APPROX_FOR_AGGREGATION
APPROX_FOR_COUNT_DISTINCT
APPROX_FOR_PERCENTILE
AQ_TM_PROCESSES
ASM_IO_PROCESSES
AWR_SNAPSHOT_TIME_OFFSET
ARCHIVE_LAG_TARGET
ASM_DISKGROUPS
ASM_DISKSTRING
ASM_POWER_LIMIT
ASM_PREFERRED_READ_FAILURE_GROUPS
AUTOTASK_MAX_ACTIVE_PDBS
AWR_PDB_AUTOFLUSH_ENABLED
BACKGROUND_CORE_DUMP
BACKGROUND_DUMP_DEST
BLOCKCHAIN_TABLE_MAX_NO_DROP
BLOCKCHAIN_TABLE_RETENTION_THRESHOLD
CIRCUITS
COMMIT_LOGGING
COMMIT_WAIT
COMMIT_WRITE
CONNECTION_BROKERS
CONTAINERS_PARALLEL_DEGREE
CONTROL_FILE_RECORD_KEEP_TIME
CONTROL_MANAGEMENT_PACK_ACCESS
CORE_DUMP_DEST
CPU_COUNT

CPU_MIN_COUNT
CREATE_STORED_OUTLINES
CURSOR_BIND_CAPTURE_DESTINATION
CURSOR_INVALIDATION
CURSOR_SHARING
DATA_GUARD_MAX_IO_TIME
DATA_GUARD_MAX_LONGIO_TIME
DATA_GUARD_SYNC_LATENCY
DATA_TRANSFER_CACHE_SIZE
DB_*n*K_CACHE_SIZE
DB_BIG_TABLE_CACHE_PERCENT_TARGET
DB_BLOCK_CHECKING
DB_BLOCK_CHECKSUM
DB_CACHE_ADVICE
DB_CACHE_SIZE
DB_CREATE_FILE_DEST
DB_CREATE_ONLINE_LOG_DEST_*n*
DB_FILE_MULTIBLOCK_READ_COUNT
DB_FILE_NAME_CONVERT
DB_FLASH_CACHE_FILE
DB_FLASH_CACHE_SIZE
DB_FLASHBACK_LOG_DEST
DB_FLASHBACK_LOG_DEST_SIZE
DB_FLASHBACK_RETENTION_TARGET
DB_INDEX_COMPRESSION_INHERITANCE
DB_KEEP_CACHE_SIZE
DB_LOST_WRITE_PROTECT
DB_PERFORMANCE_PROFILE
DB_RECOVERY_AUTO_REKEY
DB_RECOVERY_FILE_DEST
DB_RECOVERY_FILE_DEST_SIZE
DB_RECYCLE_CACHE_SIZE
DB_SECUREFILE
DB_UNRECOVERABLE_SCN_TRACKING
DDL_LOCK_TIMEOUT
DEFAULT_SHARING
DEFERRED_SEGMENT_CREATION
DG_BROKER_CONFIG_FILE*n*
DG_BROKER_START
DIAGNOSTIC_DEST
DISPATCHERS
DISTRIBUTED_LOCK_TIMEOUT
DRCP_DEDICATED_OPT
DST_UPGRADE_INSERT_CONV
ENABLE_AUTOMATIC_MAINTENANCE_PDB
ENABLE_DDL_LOGGING
ENABLE_GOLDENGATE_REPLICATION
ENABLE_IMC_WITH_MIRA
ENABLED_PDBS_ON_STANDBY

ENCRYPT_NEW_TABLESPACES
ERROR_MESSAGE_DETAILS
FAL_CLIENT
FAL_SERVER
FAST_START_MTTR_TARGET
FAST_START_PARALLEL_ROLLBACK
FILE_MAPPING
FIXED_DATE
FORWARD_LISTENER
GLOBAL_NAMES
GLOBAL_TXN_PROCESSES
GROUP_BY_POSITION_ENABLED
HEAT_MAP
HEARTBEAT_BATCH_SIZE
HS_AUTOREGISTER
HYBRID_READ_ONLY
IDENTITY_PROVIDER_CONFIG
IDENTITY_PROVIDER_TYPE
IGNORE_SESSION_SET_PARAM_ERRORS
INMEMORY_ADG_ENABLED
INMEMORY_AUTOMATIC_LEVEL
INMEMORY_CLAUSE_DEFAULT
INMEMORY_EXPRESSIONS_USAGE
INMEMORY_DEEP_VECTORIZATION
INMEMORY_FORCE
INMEMORY_MAX_POPULATE_SERVERS
INMEMORY_OPTIMIZED_ARITHMETIC
INMEMORY_QUERY
INMEMORY_SIZE
INMEMORY_TRICKLE_REPOPULATE_SERVERS_PERCENT
INMEMORY_VIRTUAL_COLUMNS
IORM_LIMIT_POLICY
JAVA_JIT_ENABLED
JAVA_POOL_SIZE
JOB_QUEUE_PROCESSES
JSON_EXPRESSION_CHECK
LARGE_POOL_SIZE
LDAP_DIRECTORY_ACCESS
LICENSE_MAX_SESSIONS
LICENSE_MAX_USERS
LICENSE_SESSIONS_WARNING
LISTENER_NETWORKS
LOB_SIGNATURE_ENABLE
LOCAL_LISTENER
LOG_ARCHIVE_CONFIG
LOG_ARCHIVE_DEST
LOG_ARCHIVE_DEST_*n*
LOG_ARCHIVE_DEST_STATE_*n*
LOG_ARCHIVE_DUPLEX_DEST

LOG_ARCHIVE_MAX_PROCESSES
LOG_ARCHIVE_MIN_SUCCEED_DEST
LOG_ARCHIVE_TRACE
LOG_CHECKPOINT_INTERVAL
LOG_CHECKPOINT_TIMEOUT
LOG_CHECKPOINTS_TO_ALERT
LOG_FILE_NAME_CONVERT
LONG_MODULE_ACTION
MANDATORY_USER_PROFILE
MAX_AUTH_SERVERS
MAX_DATAPUMP_JOBS_PER_PDB
MAX_DATAPUMP_PARALLEL_PER_JOB
MAX_DISPATCHERS
MAX_DUMP_FILE_SIZE
MAX_IDLE_BLOCKER_TIME
MAX_IDLE_TIME
MAX_IOPS
MAX_MBPS
MAX_PDBS
MAX_SAGA_DURATION
MAX_SHARED_SERVERS
MEMOPTIMIZE_POOL_SIZE
MEMOPTIMIZE_WRITE_AREA_SIZE
MEMORY_SIZE
MEMORY_TARGET
MIN_AUTH_SERVERS
MLE_PROG_LANGUAGES
MULTISHARD_QUERY_DATA_CONSISTENCY
NLS_LENGTH_SEMANTICS
NLS_NCHAR_CONV_EXCP
OFS_THREADS
OPEN_CURSORS
OPTIMIZER_ADAPTIVE_PLANS
OPTIMIZER_ADAPTIVE_REPORTING_ONLY
OPTIMIZER_ADAPTIVE_STATISTICS
OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES
OPTIMIZER_CAPTURE_SQL_QUARANTINE
OPTIMIZER_CROSS_SHARD_RESILIENCY
OPTIMIZER_DYNAMIC_SAMPLING
OPTIMIZER_FEATURES_ENABLE
OPTIMIZER_IGNORE_HINTS
OPTIMIZER_IGNORE_PARALLEL_HINTS
OPTIMIZER_INDEX_CACHING
OPTIMIZER_INDEX_COST_ADJ
OPTIMIZER_INMEMORY_AWARE
OPTIMIZER_MODE
OPTIMIZER_REAL_TIME_STATISTICS
OPTIMIZER_USE_INVISIBLE_INDEXES
OPTIMIZER_USE_PENDING_STATISTICS

OPTIMIZER_USE_SQL_PLAN_BASELINES
OPTIMIZER_USE_SQL_QUARANTINE
OUTBOUND_DBLINK_PROTOCOLS
PARALLEL_ADAPTIVE_MULTI_USER
PARALLEL_DEGREE_LIMIT
PARALLEL_DEGREE_POLICY
PARALLEL_FORCE_LOCAL
PARALLEL_INSTANCE_GROUP
PARALLEL_MAX_SERVERS
PARALLEL_MIN_DEGREE
PARALLEL_MIN_SERVERS
PARALLEL_MIN_TIME_THRESHOLD
PARALLEL_SERVERS_TARGET
PARALLEL_THREADS_PER_CPU
PDB_LOCKDOWN
PGA_AGGREGATE_LIMIT
PGA_AGGREGATE_TARGET
PKCS11_LIBRARY_LOCATION
PLSCOPE_SETTINGS
PLSQL_CCFLAGS
PLSQL_CODE_TYPE
PLSQL_DEBUG
PLSQL_IMPLICIT_CONVERSION_BOOL
PLSQL_OPTIMIZE_LEVEL
PLSQL_V2_COMPATIBILITY
PLSQL_WARNINGS
PRIORITY_TXNS_HIGH_WAIT_TARGET
PRIORITY_TXNS_MEDIUM_WAIT_TARGET
PRIORITY_TXNS_MODE
PROCESSES
QUERY_REWRITE_ENABLED
QUERY_REWRITE_INTEGRITY
RECOVERY_PARALLELISM
REDO_TRANSPORT_USER
REMOTE_DEPENDENCIES_MODE
REMOTE_LISTENER
REMOTE_RECOVERY_FILE_DEST
RESOURCE_LIMIT
RESOURCE_MANAGER_CPU_ALLOCATION
RESOURCE_MANAGER_PLAN
RESULT_CACHE_AUTO_BLOCKLIST
RESULT_CACHE_EXECUTION_THRESHOLD
RESULT_CACHE_INTEGRITY
RESULT_CACHE_MAX_RESULT
RESULT_CACHE_MAX_SIZE
RESULT_CACHE_MAX_TEMP_RESULT
RESULT_CACHE_MAX_TEMP_SIZE
RESULT_CACHE_MODE
RESULT_CACHE_REMOTE_EXPIRATION

RESUMABLE_TIMEOUT
SAGA_HIST_RETENTION
SEC_PROTOCOL_ERROR_FURTHER_ACTION
SEC_PROTOCOL_ERROR_TRACE_ACTION
SERVICE_NAMES
SESSION_EXIT_ON_PACKAGE_STATE_ERROR
SGA_MIN_SIZE
SGA_TARGET
SHADOW_CORE_DUMP
SHARD_ENABLE_RAFT_FOLLOWER_READ
SHARD_RAFT_LOGFILE_SIZE
SHARED_POOL_SIZE
SHARED_SERVER_SESSIONS
SHARED_SERVERS
SHRD_DUPL_TABLE_REFRESH_RATE
SKIP_UNUSABLE_INDEXES
SMTP_OUT_SERVER
SPATIAL_VECTOR_ACCELERATION
SPFILE
SQL_ERROR_MITIGATION
SQL_HISTORY_ENABLED
SQL_TRACE
SQL_TRANSPILER
SQLTUNE_CATEGORY
STANDBY_FILE_MANAGEMENT
STANDBY_PDB_SOURCE_FILE_DBLINK
STANDBY_PDB_SOURCE_FILE_DIRECTORY
STAR_TRANSFORMATION_ENABLED
STATISTICS_LEVEL
STREAMS_POOL_SIZE
TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM
TDE_CONFIGURATION
TDE_KEY_CACHE
TEMP_UNDO_ENABLED
THREAD
TIMED_OS_STATISTICS
TIMED_STATISTICS
TIMEZONE_VERSION_UPGRADE_ONLINE
TRACE_ENABLED
TRANSACTION_RECOVERY
UNDO_RETENTION
UNDO_TABLESPACE
UNIFORM_LOG_TIMESTAMP_FORMAT
USE_DEDICATED_BROKER
USER_DUMP_DEST
WORKAREA_SIZE_POLICY
XML_DB_EVENTS
XML_PARAMS

The `ALTER SYSTEM ... DEFERRED` statement does not modify the global value of the parameter for existing sessions, but the value will be modified for future sessions that connect to the database. The value of the following initialization parameters can be changed with `ALTER SYSTEM ... DEFERRED`:

AUDIT_FILE_DEST
BACKUP_TAPE_IO_SLAVES
CLIENT_STATISTICS_LEVEL
OBJECT_CACHE_MAX_SIZE_PERCENT
OBJECT_CACHE_OPTIMAL_SIZE
OLAP_PAGE_POOL_SIZE
PRIVATE_TEMP_TABLE_PREFIX
RECYCLEBIN
SESSION_CACHED_CURSORS
SORT_AREA_RETAINED_SIZE
SORT_AREA_SIZE

2.4.3 Displaying Current Parameter Values

You can use the SQL*Plus `SHOW PARAMETERS` statement to see the current settings for initialization parameters.

For example:

```
SQL> SHOW PARAMETERS
```

This statement displays all parameters in alphabetical order, along with their current values.

Enter the following text string to display all parameters having `BLOCK` in their names:

```
SQL> SHOW PARAMETERS BLOCK
```

You can use the `SPOOL` command to write the output to a file.

2.4.4 Parameters You Should Not Specify in the Parameter File

You should not specify these types of parameters in your parameter files:

- Parameters that you never alter unless instructed to do so by Oracle to resolve a problem
- Derived parameters, which normally do not need altering because their values are calculated automatically by the Oracle database server

2.4.5 When Parameters Are Set Incorrectly

When a parameter is set incorrectly, the effect can be different for different parameters, or based on how low or high the parameter is set.

Some parameters have a minimum setting below which an Oracle instance will not start. For other parameters, setting the value too low or too high may cause Oracle to perform badly, but it will still run. Also, Oracle may convert some values outside the acceptable range to usable levels.

If a parameter value is too low or too high, or you have reached the maximum for some resource, then Oracle returns an error. Frequently, you can wait a short while and retry the operation when the system is not as busy. If a message occurs repeatedly, then you should shut down the instance, adjust the relevant parameter, and restart the instance.

2.5 Reading the Parameter Descriptions

This section describes the properties that are documented in the initialization parameter descriptions.

PARAMETER_NAME

Property	Description
Parameter type	Specifies the type of the parameter: • A Boolean parameter accepts either `true` or `false` as its value. • A string parameter accepts any sequence of characters as its value, subject to the syntax for the parameter. • An integer parameter accepts a 4-byte value that can range from 0 to 2^{32} - 1. • A parameter file parameter accepts an initialization parameter file specification as its value. • A **big integer** parameter accepts an 8-byte value that can range from 0 to 2^{64} - 1. You specify a value for a big integer as an integer together with an optional modifier such as K, M, or G, which respectively denotes kilobytes, megabytes, or gigabytes. For example, 1000, 100 KB, 50 MB and 2 GB are valid specifications for big integers.
Syntax	For string and big integer parameters, specifies the valid syntax for specifying the parameter.
Default value	Specifies the value that the parameter assumes if a value is not explicitly specified. For most initialization parameters, the value that is documented for the **Default value** property is obtained by querying the `DEFAULT_VALUE` column in the `V$PARAMETER` view for the parameter.
Modifiable	Specifies whether the parameter can be changed for the current session (by an `ALTER SESSION` statement) or for all sessions in the current instance (by an `ALTER SYSTEM` statement): • `ALTER SESSION` overrides the instance-wide setting of the parameter for the current session only. You can restore the instance-wide setting for that session only by issuing another `ALTER SESSION` statement. • `ALTER SYSTEM` can be used to change the value in the server parameter file (SPFILE) of any initialization parameter. Such a change takes effect only in subsequent instances. The parameter descriptions indicate only those parameters that can be modified for the current instance.
Modifiable in a PDB	Specifies whether the parameter can be modified in a PDB (Yes) or not (No) For most initialization parameters, the value that is documented for the **Modifiable in a PDB** property is obtained by querying the `ISPDB_MODIFIABLE` column in the `V$PARAMETER` view for the parameter.
Range of values	Specifies the valid range of values that this parameter can assume, shown as a minimum and maximum value. Not applicable to all parameters.
Basic	Specifies whether the parameter is a basic initialization parameter or not

Property	Description
Oracle RAC	Specifies how the values for this parameter must be specified for multiple instances in an Oracle Real Application Clusters environment. Not applicable to all parameters.

For each parameter, paragraphs following these details further describe the parameter and the effects of different settings.

> **See Also:**
>
> "V$PARAMETER"

2.6 Initialization Parameter Descriptions

The remainder of this chapter describes the initialization parameters in alphabetical order.

Initialization parameter values apply to the entire database, not to an individual user, unless otherwise specified.

> **Note:**
>
> Parameters that have become obsolete are not documented.

> **See Also:**
>
> - *Oracle Database Upgrade Guide* for information about obsolete parameters
> - Your system release bulletins or other operating system-specific Oracle documentation

2.7 ACTIVE_INSTANCE_COUNT

`ACTIVE_INSTANCE_COUNT` enables you to designate one instance in a two-instance cluster as the primary instance and the other instance as the secondary instance. This parameter has no functionality in a cluster with more than two instances.

Property	Description
Parameter type	Integer
Default value	There is no default value.
Modifiable	No

Property	Description
Modifiable in a PDB	No
Range of values	1 or >= the number of instances in the cluster. (Values other than 1 have no effect on the active or standby status of any instances.)
Basic	No
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

> **Note:**
>
> The `ACTIVE_INSTANCE_COUNT` parameter is deprecated. It is retained for backward compatibility only.

When you set this parameter to 1, the first instance you start up becomes the primary instance and accepts client connections. The second instance starts up as a secondary instance and can accept client connections only if the first instance fails. In such an event, the secondary instance becomes the primary instance.

When the failed instance can once again be started up, it starts up as the secondary instance, and will not accept client connections unless the current primary instance fails.

> **Note:**
>
> This parameter functions only in a cluster with only two instances.

2.8 ADG_ACCOUNT_INFO_TRACKING

`ADG_ACCOUNT_INFO_TRACKING` controls login attempts of users on Oracle Active Data Guard standby databases. It extends the control of user account security information.

Property	Description
Parameter type	String
Syntax	`ADG_ACCOUNT_INFO_TRACKING = { LOCAL | GLOBAL }`
Default value	`LOCAL`
Modifiable	No
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	The same value must be used on all instances.

Setting `ADG_ACCOUNT_INFO_TRACKING` to `LOCAL` (the default value) continues to enforce the default behavior, by maintaining a local copy of users account information in the standby's in-memory view. Login failures are only tracked locally on a per database basis, and login is denied when the failure maximum is reached.

Setting the parameter to `GLOBAL` triggers a more secure behavior, by maintaining a single global copy of users account information across all Data Guard databases (primary and standby). Login failures across all databases in the Data Guard configuration count towards the maximum count and logins anywhere will be denied when the count is reached. This setting improves security against login attacks across a production database and all Active Data Guard standby databases.

2.9 ADG_REDIRECT_DML

Use `ADG_REDIRECT_DML` to enable or disable automatic redirection of DML operations from a standby to the primary in Oracle Active Data Guard environments.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SYSTEM` Can be modified at the session level with a special `ALTER SESSION` command. See details below.
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No
Oracle RAC	Different instances can use different values.

Automatic redirection of DML operations to the primary can be configured at the system level or the session level. The session level setting overrides the system level setting.

- To enable automatic redirection of DML operations to the primary at the system level, set `ADG_REDIRECT_DML` to `true`.
- To disable automatic redirection of DML operations to the primary at the system level, set `ADG_REDIRECT_DML` to `false`.
- To enable automatic redirection of DML operations from a standby to the primary for the current session, issue the following SQL statement:

  ```
  ALTER SESSION ENABLE ADG_REDIRECT_DML;
  ```

- To disable automatic redirection of DML operations from a standby to the primary for the current session, issue the following SQL statement:

  ```
  ALTER SESSION DISABLE ADG_REDIRECT_DML;
  ```

See Also:

Oracle Data Guard Concepts and Administration for more information about automatic redirection of DML operations

2.10 ALLOW_GLOBAL_DBLINKS

`ALLOW_GLOBAL_DBLINKS` specifies whether LDAP lookup for database links is allowed for the database.

Property	Description
Parameter type	Boolean
Syntax	`ALLOW_GLOBAL_DBLINKS = { FALSE | TRUE }`
Default value	`FALSE`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No
Oracle RAC	The same value must be used on all instances.

The following values can be set:

- `FALSE`: LDAP lookup for a database link's definition is not allowed for the database.
- `TRUE`: LDAP lookup for a database link's definition is allowed for the database.

2.11 ALLOW_GROUP_ACCESS_TO_SGA

`ALLOW_GROUP_ACCESS_TO_SGA` controls `group` access to shared memory on UNIX platforms.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No
Oracle RAC	The same value must be used on all instances.

The default value is `false`, which means that database shared memory is created with `owner` access only. In Oracle Database releases prior to Oracle Database 12c Release 2 (12.2.0.1), database shared memory was created with `owner` and `group` access.

When this parameter is set to `true`, database shared memory is created with `owner` and `group` access. This behavior grants permissions to DBAs to manage shared memory outside the database, but also allows DBAs to read and write to shared memory, which may not be desirable for certain installations.

2.12 ALLOW_LEGACY_RECO_PROTOCOL

`ALLOW_LEGACY_RECO_PROTOCOL` specifies whether the distributed transactions recovery process RECO uses a legacy recovery protocol or an upgraded recovery protocol.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true	false`
Basic	No
Oracle RAC	All instances must use the same value.

By default, `ALLOW_LEGACY_RECO_PROTOCOL` is set to `true`, which instructs RECO to use the legacy recovery protocol available in releases prior to Oracle Database 23ai.

Setting this parameter to `false` instructs RECO to use an upgraded recovery protocol. In this case, all databases involved in distributed transactions must run Oracle Database 23ai or later. If you set this parameter to `false` and a pre-Oracle Database 23ai database is involved in a distributed transaction, the distributed transaction recovery will fail. To ensure that distributed transaction recovery will complete successfully, the `ALLOW_LEGACY_RECO_PROTOCOL` must remain set to `true` until all databases are upgraded to at least Oracle Database 23ai.

Note:

This parameter is available starting with Oracle Database 23ai.

See Also:

Oracle Database Administrator's Guide for more information about this parameter

2.13 ALLOW_ROWID_COLUMN_TYPE

`ALLOW_ROWID_COLUMN_TYPE` determines whether table columns of data type `ROWID` are allowed to be created.

> **Note:**
>
> This parameter is valid only for Oracle Autonomous Database on dedicated Exadata infrastructure. On other types of Oracle databases, the value of this parameter is ignored and `ROWID` columns are always allowed to be created.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true | false`
Basic	No
Oracle RAC	Multiple instances should use the same value

Values:

- `false`

  Columns of data type `ROWID` are not allowed.

  You cannot specify `ROWID` columns when creating tables, nor can you add `ROWID` columns to existing tables. If the value of this parameter is changed from `true` to `false` at a time when `ROWID` columns exist in the database, then those columns are allowed to remain. However, Oracle recommends that you leave this parameter set to its default value of `false` and avoid introducing `ROWID` columns into Oracle Autonomous Database on dedicated Exadata infrastructure.

- `true`

  Columns of data type `ROWID` are allowed.

  If you choose this setting, be aware that `ROWID` columns are incompatible with rolling upgrade operations and other internal operations that physically move table rows. At a minimum, database activities involving `ROWID` columns should be suspended during upgrades. Applications using `ROWID` columns should introduce correctness validation to mitigate against logical errors in the application if a row relocates.

2.14 APPROX_FOR_AGGREGATION

`APPROX_FOR_AGGREGATION` replaces exact query processing for aggregation queries with approximate query processing.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No
Oracle RAC	Different instances can use different values.

Data analysis applications heavily use aggregate function and analytic function queries. Aggregation functions and analytic functions require sorting of large volumes of data, and exact query answering requires lots of memory, and can be time consuming. With approximate query processing, the results of aggregate function and analytic function queries are returned much faster than with exact query processing. Approximate query processing is useful for situations where a tolerable amount of error is acceptable in order to obtain faster query results.

The values that can be set are:

- `false`:

  Approximate query processing is not used for aggregation queries and analytic queries.
- `true`: Approximate query processing is used for aggregation queries and analytic queries.

> **See Also:**
>
> - "APPROX_FOR_COUNT_DISTINCT"
> - "APPROX_FOR_PERCENTILE"

2.15 APPROX_FOR_COUNT_DISTINCT

`APPROX_FOR_COUNT_DISTINCT` automatically replaces `COUNT (DISTINCT expr)` queries with `APPROX_COUNT_DISTINCT` queries.

Property	Description
Parameter type	Boolean
Default value	`false`

Property	Description
Modifiable	`ALTER SESSION, ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true | false`
Basic	No
Oracle RAC	Different instances can use different values.

Query results for `APPROX_COUNT_DISTINCT` queries are returned faster than the equivalent `COUNT (DISTINCT expr)` queries. `APPROX_COUNT_DISTINCT` queries are useful for situations where a tolerable amount of error is acceptable in order to obtain faster query results than with a `COUNT (DISTINCT expr)` query.

See Also:

- "APPROX_FOR_AGGREGATION"
- "APPROX_FOR_PERCENTILE"

2.16 APPROX_FOR_PERCENTILE

`APPROX_FOR_PERCENTILE` converts exact percentile functions to their approximate percentile function counterparts.

Property	Description
Parameter type	String
Syntax	`APPROX_FOR_PERCENTILE = { NONE | PERCENTILE_CONT | PERCENTILE_CONT DETERMINISTIC | PERCENTILE_DISC | PERCENTILE_DISC DETERMINISTIC | ALL | ALL DETERMINISTIC }`
Default value	`none`
Modifiable	`ALTER SESSION, ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Different instances can use different values.

Approximate percentile function queries are faster than their exact percentile function query counterparts, so they can be useful in situations where a tolerable amount of error is acceptable in order to obtain faster query results.

The values that can be set are:

- `NONE`:

  No queries are converted. This is the default value.

- `PERCENTILE_CONT`:

  Converts `PERCENTILE_CONT` queries to `APPROX_PERCENTILE` queries.

- `PERCENTILE_CONT DETERMINISTIC`:

  Converts `PERCENTILE_CONT` queries to `APPROX_PERCENTILE DETERMINSTIC` queries.

- `PERCENTILE_DISC`:

  Converts `PERCENTILE_DISC` queries to `APPROX_PERCENTILE` queries.

- `PERCENTILE DISC DETERMINISTIC`:

  Converts `PERCENTILE_DISC` queries to `APPROX_PERCENTILE DETERMINISTIC` queries.

- `ALL`:

  Converts both `PERCENTILE_CONT` queries and `PERCENTILE_DISC` queries to `APPROX_PERCENTILE` queries.

- `ALL DETERMINISTIC`:

  Converts both `PERCENTILE_CONT` and `PERCENTILE_DISC` queries to `APPROX_PERCENTILE DETERMINISTIC` queries.

See Also:

- "APPROX_FOR_AGGREGATION"
- "APPROX_FOR_COUNT_DISTINCT"
- *Oracle Database SQL Language Reference* for information about `APPROX_MEDIAN` aggregate functions
- *Oracle Database SQL Language Reference* for information about `APPROX_PERCENTILE` aggregate functions

2.17 AQ_TM_PROCESSES

`AQ_TM_PROCESSES` controls time monitoring on queue messages and controls processing of messages with delay and expiration properties specified.

Property	Description
Parameter type	Integer
Default value	`1`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`0` to `40`
Basic	No

You do not need to specify a value for this parameter because Oracle Database automatically determines the number of processes and autotunes them, as necessary. Therefore, Oracle highly recommends that you leave the `AQ_TM_PROCESSES` parameter unspecified and let the system autotune.

The default value for AQ_TM_PROCESSES is used if the client does not explicitly set a value for the parameter in the init.ora file or using the ALTER SYSTEM statement.

> **Note:**
>
> If you want to disable the Queue Monitor Coordinator, then you must set AQ_TM_PROCESSES to 0 in your parameter file. Oracle strongly recommends that you do NOT set AQ_TM_PROCESSES to 0.

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about this parameter

2.18 ARCHIVE_LAG_TARGET

ARCHIVE_LAG_TARGET forces a log switch after the specified amount of time elapses.

Property	Description
Parameter type	Integer
Default value	0 (disabled)
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	0 or any integer in [60, 7200]
Basic	No
Oracle RAC	Multiple instances should use the same value

A 0 value disables the time-based thread advance feature; otherwise, the value represents the number of seconds. Values larger than 7200 seconds are not of much use in maintaining a reasonable lag in the standby database. The typical, or recommended value is 1800 (30 minutes). Extremely low values can result in frequent log switches, which could degrade performance; such values can also make the archiver process too busy to archive the continuously generated logs.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about setting this parameter

2.19 ASM_DISKGROUPS

`ASM_DISKGROUPS` specifies a list of disk group names that an Oracle ASM instance mounts at startup when the `ALTER DISKGROUP ALL MOUNT` statement is issued.

Property	Description
Parameter type	String
Syntax	`ASM_DISKGROUPS = diskgroup [, diskgroup ] ...`
Default value	There is no default value.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	Comma-separated list of strings, up to 30 characters
Basic	No
Oracle RAC	Multiple instances can have different values.

> **Note:**
>
> This parameter may only be specified in an Oracle Automatic Storage Management (Oracle ASM) instance.

The Oracle ASM instance startup process executes `ALTER DISKGROUP ALL MOUNT` unless the `NOMOUNT` startup option is specified.

The `ASM_DISKGROUPS` parameter is dynamic. If you are using a server parameter file (SPFILE), then you do not have to manually alter the value of `ASM_DISKGROUPS` in most situations. Oracle ASM automatically adds a disk group to the parameter when the disk group is successfully created or mounted. Oracle ASM also automatically removes a disk group from the parameter when the disk group is dropped. However, the SPFILE is not updated on a manual dismount.

Issuing the `ALTER DISKGROUP...ALL MOUNT` or `ALTER DISKGROUP...ALL DISMOUNT` command does not affect the value of this parameter.

Supporting Up to 511 Disk Groups for an Oracle ASM Instance

In Oracle Database 12*c* Release 1 or later, Oracle ASM configurations support up to 511 disk groups. Oracle ASM configurations with Oracle Database releases before 12*c* Release 1 can only support up to 63 disk groups.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for more information about and examples of using this parameter

2.20 ASM_DISKSTRING

ASM_DISKSTRING specifies an operating system-dependent value used by Oracle ASM to limit the set of disks considered for discovery.

Property	Description
Parameter type	String
Syntax	ASM_DISKSTRING = *discovery_string* [, *discovery_string*] ...
Default value	The null string; Oracle Automatic Storage Management discovery finds all disks in an operating system-specific location to which the Oracle Automatic Storage Management instance has read/write access.
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Multiple instances can have different values. Different nodes might see the same disks under different names; however, each instance must be able to use its ASM_DISKSTRING to discover the same physical media as the other nodes in the cluster.

Note:

This parameter may only be specified in an Oracle Automatic Storage Management (Oracle ASM) instance.

When a new disk is added to a disk group, each Oracle ASM instance that has the disk group mounted must be able to discover the new disk using the value of ASM_DISKSTRING.

In most cases, the default value will be sufficient. Using a more restrictive value may reduce the time required for Oracle ASM to perform discovery, and thus improve disk group mount time or the time for adding a disk to a disk group. A "?" at the beginning of the string gets expanded to the Oracle home directory. Depending on the operating system, wildcard characters can be used. It may be necessary to dynamically change ASM_DISKSTRING before adding a disk so that the new disk will be discovered.

An attempt to dynamically modify ASM_DISKSTRING will be rejected and the old value retained if the new value cannot be used to discover a disk that is in a disk group that is already mounted.

See Also:

Oracle Automatic Storage Management Administrator's Guide for more information and examples of using this parameter

2.21 ASM_IO_PROCESSES

ASM_IO_PROCESSES specifies the number of I/O worker processes to be started in an Oracle IOServer instance.

Property	Description
Parameter type	Integer
Default value	20
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	1 – 32
Basic	No
Oracle RAC	Multiple instances can have different values.

This parameter is applicable only in an Oracle IOServer instance, which runs out of an Oracle Grid Infrastructure home.

The default value should work in most cases. However, under heavy I/O load, there may be some delays associated with posting processes out of I/O waits. In this case, a slightly higher value than the default may be appropriate.

2.22 ASM_POWER_LIMIT

ASM_POWER_LIMIT specifies the maximum power on an Oracle ASM instance for disk rebalancing.

Property	Description
Parameter type	Integer
Default value	1
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	No
Range of values	0 to 11[1]
Basic	No
Oracle RAC	Multiple instances can have different values.

[1] Beginning with Oracle Database 11*g* Release 2 (11.2.0.2), if the COMPATIBLE.ASM disk group attribute is set to 11.2.0.2 or higher, then the range of values is 0 to 1024.

Note:

- This parameter may only be specified in an Oracle Automatic Storage Management (Oracle ASM) instance.
- In an Oracle Exadata or Oracle Data Appliance environment, you cannot set this parameter to 0.

The higher the limit, the faster rebalancing will complete. Lower values will take longer, but consume fewer processing and I/O resources.

If the `POWER` clause of a rebalance operation is not specified, then the default power will be the value of `ASM_POWER_LIMIT`.

See Also:

Oracle Automatic Storage Management Administrator's Guide for more information about using this parameter

2.23 ASM_PREFERRED_READ_FAILURE_GROUPS

`ASM_PREFERRED_READ_FAILURE_GROUPS` specifies the failure groups that contain preferred read disks. Preferred disks are instance specific.

Property	Description
Parameter type	String
Syntax	`ASM_PREFERRED_READ_FAILURE_GROUPS = '<diskgroup_name>.<failure_group_name>, ...'`
Default value	NULL
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No
Oracle RAC	The value is different on different nodes

Note:

The `ASM_PREFERRED_READ_FAILURE_GROUPS` initialization parameter is deprecated in Oracle Database 12*c* Release 2 (12.2.0.1) and may be desupported in a future release. It is replaced by the `PREFERRED_READ.ENABLED` disk group attribute.

See *Oracle Automatic Storage Management Administrator's Guide* for more information about the `PREFERRED_READ.ENABLED` disk group attribute.

To reset the parameter value to null, issue the following statement, which updates the server parameter file (SP file), then reboot Oracle ASM so that the change takes effect:

```
alter system reset asm_preferred_read_failure_groups;
```

See Also:

Oracle Automatic Storage Management Administrator's Guide for more information about this parameter

2.24 AUDIT_FILE_DEST

`AUDIT_FILE_DEST` specifies the operating system directory into which the audit trail is written when the `AUDIT_TRAIL` initialization parameter is set to **os**, **xml**, or **xml,extended**.

Note:

This parameter is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored. However, you cannot create new traditional audit settings. You can delete existing traditional audit settings. See *Oracle Database Security Guide* for more information about how this desupport works.

Property	Description
Parameter type	String
Syntax	`AUDIT_FILE_DEST = '`*`directory`*`'`

Property	Description
Default value	The first default value is: *ORACLE_BASE*/admin/*ORACLE_SID*/adump The second default value, which is used if the first default value does not exist or is unusable, is: *ORACLE_HOME*/rdbms/audit Both of these default values are for UNIX systems. Other platforms may have different defaults. In a multitenant container database (CDB), both of these default values will be appended with the GUID of the pluggable database (PDB) to store audit records that belong to the PDB. For example, if the PDB's GUID is 03E1F908EE04252CE053B280E80AAAA3, the first default directory will be: *ORACLE_BASE*/admin/*ORACLE_SID*/adump/03E1F908EE04252CE053B280E80AAAA3 You can use the V$CONTAINERS view to query a PDB's GUID.
Modifiable	ALTER SYSTEM ... DEFERRED
Modifiable in a PDB	No
Basic	No

The audit records will be written in XML format if the AUDIT_TRAIL initialization parameter is set to **xml** or **xml, extended**. It is also the location to which mandatory auditing information is written and, if so specified by the AUDIT_SYS_OPERATIONS initialization parameter, audit records for user SYS.

In a multitenant container database (CDB), the scope of the settings for this initialization parameter is the CDB. Although the audit trail is provided per pluggable database (PDB) in a CDB, this initialization parameter cannot be configured for individual PDBs.

See Also:

- *Oracle Multitenant Administrator's Guide* for conceptual information about CDBs and PDBs
- *Oracle Multitenant Administrator's Guide* for information about managing CDBs and PDBs
- "V$CONTAINERS"
- "V$PDBS"

2.25 AUDIT_SYS_OPERATIONS

AUDIT_SYS_OPERATIONS enables or disables the auditing of directly issued user SQL statements with SYS authorization. These include SQL statements directly issued by users when connected with the SYSASM, SYSBACKUP, SYSDBA, SYSDG, SYSKM, or SYSOPER privileges, as

well as SQL statements that have been executed with SYS authorization using the PL/SQL package DBMS_SYS_SQL.

> **Note:**
>
> This parameter is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored. However, you cannot create new traditional audit settings. You can delete existing traditional audit settings. See *Oracle Database Security Guide* for more information about how this desupport works.

Property	Description
Parameter type	Boolean
Default value	FALSE
Modifiable	No
Modifiable in a PDB	No
Range of values	TRUE | FALSE
Basic	No

The audit records are written to the operating system's audit trail. The audit records will be written in XML format if the AUDIT_TRAIL initialization parameter is set to xml or xml, extended

On UNIX platforms, if the AUDIT_SYSLOG_LEVEL parameter has also been set, then it overrides the AUDIT_TRAIL parameter and SYS audit records are written to the system audit log using the SYSLOG utility.

In a CDB, the scope of the settings for this initialization parameter is the CDB. Although the audit trail is provided per PDB in a CDB, this initialization parameter cannot be configured for individual PDBs.

2.26 AUDIT_SYSLOG_LEVEL

AUDIT_SYSLOG_LEVEL allows SYS and standard OS audit records to be written to the system audit log using the SYSLOG utility.

> **Note:**
>
> This parameter is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored. However, you cannot create new traditional audit settings. You can delete existing traditional audit settings. See *Oracle Database Security Guide* for more information about how this desupport works.

Property	Description
Parameter type	String
Syntax	`AUDIT_SYSLOG_LEVEL = 'facility_clause.priority_clause'`
Syntax	**`facility_clause::=`** `{ USER | LOCAL[0 | 1 | 2 | 3 | 4 | 5 | 6 | 7] | SYSLOG | DAEMON | KERN | MAIL | AUTH | LPR | NEWS | UUCP | CRON }`
Syntax	**`priority_clause::=`** `{ NOTICE | INFO | DEBUG | WARNING | ERR | CRIT | ALERT | EMERG }`
Default value	There is no default value.
Modifiable	No
Modifiable in a PDB	No
Basic	No
Examples	`AUDIT_SYSLOG_LEVEL = 'KERN.EMERG';` `AUDIT_SYSLOG_LEVEL = 'LOCAL1.WARNING';`

If you use this parameter, it is best to assign a file corresponding to every combination of facility and priority (especially `KERN.EMERG`) in `syslog.conf` . Sometimes these are assigned to print to the console in the default `syslog.conf` file. This can become annoying and will be useless as audit logs. Also, if you use this parameter, it is best to set the maximum length of syslog messages in the system to 512 bytes.

Note:

Audit records written to the system audit log could get truncated to 512 bytes, and different parts of the same audit record may not be joined to get the original complete audit record.

See Also:

Oracle Database Security Guide for information about configuring syslog auditing

If `AUDIT_SYSLOG_LEVEL` is set and `SYS` auditing is enabled (`AUDIT_SYS_OPERATIONS` = `TRUE`), then `SYS` audit records are written to the system audit log. If `AUDIT_SYSLOG_LEVEL` is set and standard audit records are being sent to the operating system (`AUDIT_TRAIL` = `os`), then standard audit records are written to the system audit log.

In a CDB, the scope of the settings for this initialization parameter is the CDB. Although the audit trail is provided per PDB in a CDB, this initialization parameter cannot be configured for individual PDBs.

2.27 AUDIT_TRAIL

AUDIT_TRAIL enables or disables database auditing.

> **Note:**
>
> This parameter is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored. However, you cannot create new traditional audit settings. You can delete existing traditional audit settings. See *Oracle Database Security Guide* for more information about how this desupport works.

Property	Description
Parameter type	String
Syntax	AUDIT_TRAIL = { none | os | db [, extended] | xml [, extended] }
Default value	none
Modifiable	No
Modifiable in a PDB	No
Basic	No

Values

- none

  Disables standard auditing. This value is the default if the AUDIT_TRAIL parameter was not set in the initialization parameter file or if you created the database using a method other than Database Configuration Assistant. If you created the database using Database Configuration Assistant, then the default is db.

- os

  Directs all audit records to an operating system file. Oracle recommends that you use the os setting, particularly if you are using an ultra-secure database configuration.

- db

  Directs audit records to the database audit trail (the SYS.AUD$ table), except for records that are always written to the operating system audit trail. Use this setting for a general database for manageability.

  If the database was started in read-only mode with AUDIT_TRAIL set to db, then Oracle Database internally sets AUDIT_TRAIL to os. Check the alert log for details.

- db, extended

  Performs all actions of AUDIT_TRAIL=db, and also populates the SQL bind and SQL text CLOB-type columns of the SYS.AUD$ table, when available. These two

columns are populated only when this parameter is specified. When standard auditing is used with `DB, EXTENDED`, then virtual private database (VPD) predicates and policy names are also populated in the `SYS.AUD$` table.

If the database was started in read-only mode with `AUDIT_TRAIL` set to `db, extended`, then Oracle Database internally sets `AUDIT_TRAIL` to `os`. Check the alert log for details.

- `xml`

  Writes to the operating system audit record file in XML format. Records all elements of the `AuditRecord` node except `Sql_Text` and `Sql_Bind` to the operating system XML audit file.

- `xml, extended`

  Performs all actions of `AUDIT_TRAIL=xml`, and includes SQL text and SQL bind information in the audit trail.

You can use the SQL `AUDIT` statement to set auditing options regardless of the setting of this parameter.

In a CDB, the scope of the settings for this initialization parameter is the CDB. Although the audit trail is provided per PDB in a CDB, this initialization parameter cannot be configured for individual PDBs.

Examples

The following statement sets the `db, extended` value for the `AUDIT_TRAIL` parameter. The new value takes effect after the database is restarted.

```
SQL> alter system set AUDIT_TRAIL=db, extended scope=spfile;

System altered.

SQL>
```

The following statement sets the `xml, extended` value for the `AUDIT_TRAIL` parameter. The new value takes effect after the database is restarted.

```
SQL> alter system set AUDIT_TRAIL=xml, extended scope=spfile;

System altered.

SQL>
```

The following statement sets the `db` value for the `AUDIT_TRAIL` parameter. The new value takes effect after the database is restarted.

```
SQL> alter system set AUDIT_TRAIL=db scope=spfile;

System altered.

SQL>
```

See Also:

- *Oracle Database Security Guide* for information about configuring unified audit policies
- *Oracle Database Upgrade Guide* to learn more about traditional non-unified auditing

2.28 AUTOTASK_MAX_ACTIVE_PDBS

`AUTOTASK_MAX_ACTIVE_PDBS` enables you to specify the maximum number of PDBs that can schedule automated maintenance tasks at the same time (during a maintenance window).

Property	Description
Parameter type	Integer
Default value	`2`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	`0` to the number of PDBs in the CDB
Basic	No
Oracle RAC	The same value should be used on all instances.

This parameter only affects PDBs. The CDB$ROOT container (CDB root) for a CDB can always schedule and run maintenance tasks during a maintenance window.

The default value is 2. Therefore, by default, two PDBs and the CDB root can run tasks at the same time during a maintenance window.

This parameter can be set only in the CDB root, not in a PDB.

See Also:

- "ENABLE_AUTOMATIC_MAINTENANCE_PDB" for information on disabling or enabling the running of automated maintenance tasks for specific PDBs or for all the PDBs in CDB
- *Oracle Database Administrator's Guide* for more information about managing automated database maintenance tasks

2.29 AWR_PDB_AUTOFLUSH_ENABLED

AWR_PDB_AUTOFLUSH_ENABLED enables you to specify whether to enable or disable automatic Automatic Workload Repository (AWR) snapshots for all the PDBs in a CDB or for individual PDBs in a CDB.

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	true | false
Basic	No
Oracle RAC	The same value must be used on all instances.

Note:

The value of this parameter in CDB$ROOT (the root of a CDB) has no effect in the root. Automatic AWR snapshots are always enabled in the root, regardless of the setting of this parameter.

The default value of AWR_PDB_AUTOFLUSH_ENABLED is true. Thus, by default, automatic AWR snapshots are enabled for all the PDBs in a CDB.

When you change the value of AWR_PDB_AUTOFLUSH_ENABLED in the CDB root, the new value takes effect in all the PDBs in the CDB.

Therefore, if you change the value of AWR_PDB_AUTOFLUSH_ENABLED in the CDB root to false, the value of AWR_PDB_AUTOFLUSH_ENABLED is also changed to false in all of the PDBs, so that automatic AWR snapshots are disabled for all the PDBs.

You can also change the value of AWR_PDB_AUTOFLUSH_ENABLED in any of the individual PDBs in a CDB, and the value that is set for each individual PDB will be honored. This enables you to enable or disable automatic AWR snapshots for individual PDBs.

When a new PDB is created, or a PDB from a previous database release is upgraded to the current database release, automatic AWR snapshots are enabled or disabled for the PDB based on the current value of AWR_PDB_AUTOFLUSH_ENABLED in the root.

See Also:

- *Oracle Database Performance Tuning Guide* for more information about Automatic Workload Repository (AWR)
- *Oracle Database Performance Tuning Guide* for more information about AWR snapshots

2.30 AWR_PDB_MAX_PARALLEL_SLAVES

`AWR_PDB_MAX_PARALLEL_SLAVES` enables a DBA to allocate the correct amount of resources to enable quick and timely Automatic Workload Repository (AWR) flushes for multitenant container databases (CDBs).

Property	Description
Parameter type	Integer
Default value	10
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	1 – 30
Basic	No
Oracle RAC	Different instances can use different values.

Use `AWR_PDB_MAX_PARALLEL_SLAVES` to control the amount of resources dedicated to AWR snapshot flushing in pluggable databases (PDBs). With this parameter, a DBA can modify the maximum number of MMON worker processes (M*nnn* background processes) that can concurrently be used to handle AWR flush operations for the entire CDB.

For CDBs with a large number of PDBs enabled to create automatic AWR snapshots, a DBA can increase this parameter to enable timely AWR flushing. For CDBs with a small number of PDBs enabled, the value of this parameter can be decreased to reduce the concurrency and the chance of performance spikes.

Note that this parameter is set in the root of a CDB and determines the maximum degree of parallelism used to create AWR automatic snapshots for PDBs.

See Also:

- "AWR_PDB_AUTOFLUSH_ENABLED" for information about enabling the automatic creation of AWR PDB snapshots
- *Oracle Database Performance Tuning Guide* for an introduction to AWR
- "Background Processes" for more information about the MMON and M*nnn* background processes

2.31 AWR_SNAPSHOT_TIME_OFFSET

`AWR_SNAPSHOT_TIME_OFFSET` specifies an offset for the Automatic Workload Repository (AWR) snapshot start time.

Property	Description
Parameter type	Integer

Property	Description
Default value	There is no offset by default.
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	0 - 3599, or the special value 1000000
Basic	No
Oracle RAC	Multiple instances should use the same value

AWR snapshots normally start at the top of the hour (12:00, 1:00, 2:00, and so on). This parameter allows DBAs to specify an offset for the AWR snapshot start time.

This is a useful parameter to avoid CPU spikes from multiple instances all starting their AWR snapshots at the same time. If you have a large system with many instances on it (like many Exadata installations), and you are experiencing such CPU spikes, this parameter can be very useful.

The parameter is specified in seconds. Normally, you set it to a value less than 3600. If you set the special value 1000000 (1,000,000), you get an automatic mode, in which the offset is based on the database name.

The automatic mode is an effective way of getting a reasonable distribution of offset times when you have a very large number of instances running on the same node.

2.32 BACKGROUND_CORE_DUMP

BACKGROUND_CORE_DUMP specifies whether Oracle includes the SGA in the core file for Oracle background processes.

Property	Description
Parameter type	String
Syntax	BACKGROUND_CORE_DUMP = { partial | full }
Default value	partial
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Basic	No

Values

- partial

  Oracle does not include the SGA in the core dump.

- full

  Oracle includes the SGA in the core dump.

> **See Also:**
>
> "SHADOW_CORE_DUMP"

2.33 BACKGROUND_DUMP_DEST

`BACKGROUND_DUMP_DEST` specifies the pathname (directory or disc) where debugging trace files for the background processes (LGWR, DBW*n*, and so on) are written during Oracle operations.

Property	Description
Parameter type	String
Syntax	`BACKGROUND_DUMP_DEST = { pathname | directory }`
Default value	Operating system-dependent
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	Any valid local path, directory, or disk
Basic	No

> **Note:**
>
> The `BACKGROUND_DUMP_DEST` parameter is deprecated in Oracle Database 12*c* Release 1 (12.1.0.1).

An **alert log** in the directory specified by `BACKGROUND_DUMP_DEST` logs significant database events and messages. Anything that affects the database instance or global database is recorded here. The alert log is a normal text file. Its file name is operating system-dependent. For platforms that support multiple instances, it takes the form `alert_sid.log`, where *sid* is the system identifier. This file grows slowly, but without limit, so you might want to delete it periodically. You can delete the file even when the database is running.

> **Note:**
>
> This parameter is ignored by the diagnosability infrastructure introduced in Oracle Database 11g Release 1 (11.1), which places trace and core files in a location controlled by the `DIAGNOSTIC_DEST` initialization parameter.

> **See Also:**
>
> - *Oracle Database Administrator's Guide* for more information on the DIAGNOSTIC_DEST initialization parameter
> - "USER_DUMP_DEST" for information on setting a destination for server process trace files

2.34 BACKUP_TAPE_IO_SLAVES

`BACKUP_TAPE_IO_SLAVES` specifies whether I/O server processes are used by Recovery Manager to back up, copy, or restore data to tape.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SYSTEM ... DEFERRED`
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No

When the value is set to `true`, Oracle uses an I/O server process to write to or read from a tape device. When the value is set to `false` (the default), Oracle does not use I/O server process for backups. Instead, the shadow process engaged in the backup accesses the tape device.

> **Note:**
>
> You cannot perform duplexed backups unless you enable this parameter. Otherwise, Oracle returns an error. When this parameter is enabled, Recovery Manager will configure as many server processes as needed for the number of backup copies requested.

> **See Also:**
>
> - *Oracle Database Backup and Recovery User's Guide* for more information on duplexed backups
> - "DBWR_IO_SLAVES"

2.35 BITMAP_MERGE_AREA_SIZE

`BITMAP_MERGE_AREA_SIZE` specifies the amount of memory Oracle uses to merge bitmaps retrieved from a range scan of the index.

Property	Description
Parameter type	Integer
Default value	`1048576` (1 MB)
Modifiable	No
Modifiable in a PDB	Yes
Range of values	Operating system-dependent
Basic	No

> **Note:**
>
> Oracle does not recommend using the `BITMAP_MERGE_AREA_SIZE` parameter unless the instance is configured with the shared server option. Oracle recommends that you enable automatic sizing of SQL working areas by setting `PGA_AGGREGATE_TARGET` instead. `BITMAP_MERGE_AREA_SIZE` is retained for backward compatibility.

`BITMAP_MERGE_AREA_SIZE` is relevant only for systems containing bitmap indexes. A larger value usually improves performance, because the bitmap segments must be sorted before being merged into a single bitmap.

> **See Also:**
>
> *Oracle Database SQL Tuning Guide* for more information on using bitmap indexes for performance

2.36 BLANK_TRIMMING

`BLANK_TRIMMING` specifies the data assignment semantics of character datatypes.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	No
Modifiable in a PDB	Yes
Range of values	`true	false`

Property	Description
Basic	No

Values

- `TRUE`

  Allows the data assignment of a source character string or variable to a destination character column or variable even though the source length is longer than the destination length. In this case, however, the additional length over the destination length must be all blanks, else an exception condition is raised. This value complies with the semantics of SQL-92 Transitional Level and above.

- `FALSE`

  Disallows the data assignment if the source length is longer than the destination length and reverts to SQL92 Entry Level semantics.

> **See Also:**
>
> *Oracle Database Globalization Support Guide* for more information on how using this parameter can help prevent data truncation issues during character set migration

2.37 BLOCKCHAIN_TABLE_MAX_NO_DROP

`BLOCKCHAIN_TABLE_MAX_NO_DROP` lets you control the maximum amount of idle time that can be specified when creating a blockchain table or an immutable table. The idle time represents the length of time the table must be inactive before it can be dropped. When explicitly set by a user, the only value allowed for this parameter is `0`.

Property	Description
Parameter type	Integer
Default value	None
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	None or `0`
Basic	No
Oracle RAC	The same value must be used on all instances.

When creating a blockchain table or an immutable table with the SQL statement `CREATE TABLE`, you can specify the clause `NO DROP UNTIL` *`number`* `DAYS IDLE`. This clause specifies the number of days the table must be inactive before it can be dropped, that is, the number of days that must pass after the most recent row insertion before the table can be dropped.

- If `BLOCKCHAIN_TABLE_MAX_NO_DROP` is set to `0`, then when a user creates a blockchain table or an immutable table, and specifies the `NO DROP UNTIL` *`number`* `DAYS IDLE` clause, the value of *`number`* must be `0`:

  ```
  CREATE BLOCKCHAIN TABLE ... NO DROP UNTIL 0 DAYS IDLE ...
  CREATE IMMUTABLE TABLE ... NO DROP UNTIL 0 DAYS IDLE ...
  ```

  This allows the table to be dropped at any time, regardless of how long the table has been inactive.
- If `BLOCKCHAIN_TABLE_MAX_NO_DROP` is not set, then when a user creates a blockchain table or an immutable table, and specifies the `NO DROP UNTIL` *`number`* `DAYS IDLE` clause, any number value can be specified for *`number`*.

> **See Also:**
>
> *Oracle Database SQL Language Reference* for information about the `CREATE TABLE` statement

2.38 BLOCKCHAIN_TABLE_RETENTION_THRESHOLD

`BLOCKCHAIN_TABLE_RETENTION_THRESHOLD` lets you control the maximum amount of idle time that can be specified when a database user without the `TABLE RETENTION` system privilege creates or alters a blockchain table or an immutable table.

Property	Description
Parameter type	Integer
Default value	16
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	0 to 365,000
Basic	No
Oracle RAC	The same value must be used on all instances.

The idle time for a non-empty blockchain table or a non-empty immutable table represents the length of time (in days) the table must be inactive before it can be dropped.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.39 CIRCUITS

`CIRCUITS` specifies the total number of virtual circuits that are available for inbound and outbound network sessions.

Property	Description
Parameter type	Integer
Default value	`4294967295`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No

It is one of several parameters that contribute to the total SGA requirements of an instance.

You should not specify a value for this parameter unless you want to limit the number of virtual circuits.

See Also:

- *Oracle Database Concepts* for more information on memory structures
- *Oracle Database Concepts* for more information on processes

2.40 CLIENT_RESULT_CACHE_LAG

`CLIENT_RESULT_CACHE_LAG` specifies the maximum time (in milliseconds) since the last round trip to the server, before which the OCI client query execute makes a round trip to get any database changes related to the queries cached on the client.

Property	Description
Parameter type	Big integer
Syntax	`CLIENT_RESULT_CACHE_LAG = integer`
Default value	`3000`
Modifiable	No
Modifiable in a PDB	Yes
Range of values	`0` to operating system-dependent
Basic	No

> **See Also:**
>
> *Oracle Call Interface Developer's Guide* for more information about the client query cache feature

2.41 CLIENT_RESULT_CACHE_SIZE

`CLIENT_RESULT_CACHE_SIZE` specifies the maximum size of the client per-process result set cache (in bytes).

Property	Description
Parameter type	Big integer
Syntax	`CLIENT_RESULT_CACHE_SIZE = integer [K | M | G]`
Default value	`0`
Modifiable	No
Modifiable in a PDB	Yes
Range of values	`0` to operating system-dependent
Basic	No

All OCI client processes inherit this maximum size. Setting a nonzero value enables the client query cache feature. This can be overridden by the client configuration parameter `OCI_RESULT_CACHE_MAX_SIZE`.

> **See Also:**
>
> *Oracle Call Interface Developer's Guide* for more information about the client query cache feature

2.42 CLIENT_STATISTICS_LEVEL

`CLIENT_STATISTICS_LEVEL` controls whether database clients report network statistics to the database.

This parameter applies only to clients that use Oracle Call Interface (OCI) to connect to the database.

Property	Description
Parameter type	String
Syntax	`CLIENT_STATISTICS_LEVEL = { TYPICAL | OFF }`
Default value	`TYPICAL`
Modifiable	`ALTER SYSTEM ... DEFERRED`
Modifiable in a PDB	Yes

Property	Description
Basic	No
Oracle RAC	The same value must be used on all instances.

Database clients sometimes have performance issues when interacting with the database over a network (LAN or WAN). You can use this parameter to enable clients to collect network statistics and periodically send them to the database, where the statistics are displayed in `AWR` and `V$` views. These statistics include TCP and SQL*Net statistics. They complement existing database statistics and can be used to analyze, troubleshoot, and tune potential network performance or configuration issues.

Possible values:

- `TYPICAL`

  This setting enables clients to collect network statistics and periodically send them to the database.

- `OFF`

  This setting disables this feature. Clients will not send network statistics to the database.

When you modify this parameter, the new setting applies only to subsequent new connections to database clients.

Note:

To view a complete listing of the statistics that are collected and reported when this feature is enabled, issue the following SQL statement:

```
SELECT name FROM V$STATNAME
  WHERE name LIKE 'Client%' ORDER BY name;

NAME
----------------------------------------------------
Client Advertised Receive Window
Client Advertised Send Window
Client Data Segments In
Client Data Segments Out
Client Lost Packets
Client Path Maximum Transmission Unit(MTU)
Client Send Congestion Window
Client Time (usec) Busy Sending Data
Client Time (usec) Busy Sending Data under Congestion
Client Time (usec) Last Ack Received
Client Time (usec) Last Ack Sent
Client Time (usec) Last Data Received
Client Time (usec) Last Data Sent
Client Time (usec) Limited by Receive Window
Client Time (usec) Limited by Send Buffer
Client Time (usec) Round Trip Time
Client Time (usec) Round Trip Time Variance
Client Total Bytes Acked
Client Total Bytes Received
Client Total Number of Retransmitted Packets
```

2.43 CLONEDB

`CLONEDB` should be set on Direct NFS Client CloneDB databases. When this parameter is set, the CloneDB database uses the database backup as the backing store for the datafiles.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No
Oracle RAC	The same value should be set for all instances.

> **See Also:**
>
> - See *Oracle Database Administrator's Guide* for more information about cloning databases on network attached storage (NAS).
> - "CLONEDB_DIR"

2.44 CLONEDB_DIR

`CLONEDB_DIR` sets the directory path where CloneDB bitmap files should be created and accessed.

Property	Description
Parameter type	String
Syntax	`CLONEDB_DIR = string`
Default value	`$ORACLE_HOME/dbs`
Modifiable	No
Modifiable in a PDB	No
Basic	No
Oracle RAC	In an Oracle RAC environment, this parameter should be set to a shared location that is accessible from all the instances.

By default the CloneDB bitmap file is created under the `$ORACLE_HOME/dbs` directory. This directory may not be in a shared location in an Oracle RAC environment, and therefore this parameter is provided to identify a shared location where CloneDB specific files can be created.

> **See Also:**
>
> "CLONEDB"

2.45 CLUSTER_DATABASE

`CLUSTER_DATABASE` is an Oracle RAC parameter that specifies whether Oracle RAC is enabled.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true | false`

Property	Description
Basic	Yes
Oracle RAC	For all instances, the value must be set to `true`.

> **See Also:**
>
> *Oracle Real Application Clusters Administration and Deployment Guide* for an introduction to Oracle RAC

2.46 CLUSTER_INTERCONNECTS

`CLUSTER_INTERCONNECTS` can be used in Oracle Real Application Clusters environments to indicate cluster interconnects available for use for the database traffic.

Property	Description
Parameter type	String
Syntax	`CLUSTER_INTERCONNECTS = ifn [: ifn ] ...`
Default value	There is no default value.
Modifiable	No
Modifiable in a PDB	No
Range of values	One or more IP addresses, separated by colons
Basic	No

Use this parameter to override the default interconnect configured for the database traffic, which is stored in the cluster registry. This procedure also may be useful with Data Warehouse systems that have reduced availability requirements and high interconnect bandwidth demands.

`CLUSTER_INTERCONNECTS` specifically overrides the following:

- Network classifications stored by `oifcfg` in the OCR.
- The default interconnect chosen by Oracle.

If you want to load-balance the interconnect, then Oracle recommends that you use link-bonding at the operating system level, even if you have two databases on the same server, so that multiple interconnects use the same address. Note that multiple private addresses provide load balancing, but do not provide failover unless bonded. If you specify multiple addresses in init.ora using `CLUSTER_INTERCONNECTS`, instead of bonding multiple addresses at the operating system level, then typically availability is reduced, because each network interface card failure will take down that instance.

Refer to your vendor documentation for information about bonding interfaces. Some vendor bonding architectures may require the use of this parameter.

If you have multiple database instances on Oracle Real Application Clusters nodes and want to use a specific interface for each instance, then you can set the

CLUSTER_INTERCONNECTS initialization parameter to the IP address for each database instance. For example:

```
hr1.init.ora.cluster_interconnects="192.0.2.111"
oltp3.init.ora.cluster_interconnects="192.0.2.112"
```

If the Oracle RAC interconnect is configured to run on a different interface than the Oracle Clusterware interconnect, then this configuration can cause reduced availability, as failovers or instance evictions can be delayed if the Oracle RAC interconnect fails while the Oracle Clusterware NIC remains up.

> **See Also:**
>
> *Oracle Real Application Clusters Administration and Deployment Guide* for additional information about using CLUSTER_INTERCONNECTS

2.47 COMMIT_LOGGING

COMMIT_LOGGING is an advanced parameter used to control how redo is batched by Log Writer.

Property	Description
Parameter type	String
Syntax	COMMIT_LOGGING = { IMMEDIATE | BATCH }
Default value	There is no default value.
Modifiable	Yes (at both session-level and system-level)
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Each instance may have its own setting

If COMMIT_LOGGING is altered after setting COMMIT_WAIT to FORCE_WAIT, then the FORCE_WAIT option is no longer valid.

2.48 COMMIT_POINT_STRENGTH

COMMIT_POINT_STRENGTH specifies a value that determines the **commit point site** in a distributed transaction.

Property	Description
Parameter type	Integer
Default value	1
Modifiable	No
Modifiable in a PDB	Yes
Range of values	0 to 255
Basic	No

> **Note:**
>
> This parameter is relevant only in distributed database systems.

The node in the transaction with the highest value for `COMMIT_POINT_STRENGTH` will be the commit point site.

The commit point site of a database should reflect the amount of critical shared data in the database. For example, a database on a mainframe computer typically shares more data among users than one on a personal computer. Therefore, `COMMIT_POINT_STRENGTH` should be set to a higher value for the mainframe computer.

The commit point site stores information about the status of transactions. Other computers in a distributed transaction require this information during Oracle's two-phase commit, so it is desirable to have machines that are always available as commit point sites. Therefore, set `COMMIT_POINT_STRENGTH` to a higher value on your more available machines.

> **See Also:**
>
> - *Oracle Database Concepts* and *Oracle Database Administrator's Guide* for information on two-phase commit
> - Your operating system-specific Oracle documentation for the default value of this parameter

2.49 COMMIT_WAIT

`COMMIT_WAIT` is an advanced parameter used to control when the redo for a commit is flushed to the redo logs.

Property	Description
Parameter type	String
Syntax	`COMMIT_WAIT = { NOWAIT | WAIT | FORCE_WAIT }`
Default value	There is no default value.
Modifiable	Yes (at both session-level and system-level)
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Each instance may have its own setting

Be aware that the `NOWAIT` option can cause a failure that occurs after the database receives the commit message, but before the redo log records are written. This can falsely indicate to a transaction that its changes are persistent. Also, it can violate the durability of ACID (Atomicity, Consistency, Isolation, Durability) transactions if the database shuts down unexpectedly.

If the parameter is set to FORCE_WAIT, the default behavior (immediate flushing of the redo log buffer with wait) is used. If this is a system setting, the session level and transaction level options will be ignored. If this is a session level setting, the transaction level options will be ignored. If COMMIT_WAIT is altered after it has been set to FORCE_WAIT, then the FORCE_WAIT option is no longer valid.

2.50 COMMIT_WRITE

COMMIT_WRITE is an advanced parameter used to control how redo for transaction commits is written to the redo logs.

Property	Description
Parameter type	String
Syntax	COMMIT_WRITE = '{IMMEDIATE | BATCH},{WAIT |NOWAIT}'
Default value	If this parameter is not explicitly specified, then database commit behavior defaults to writing commit records to disk before control is returned to the client. If only IMMEDIATE or BATCH is specified, but not WAIT or NOWAIT, then WAIT mode is assumed. If only WAIT or NOWAIT is specified, but not IMMEDIATE or BATCH, then IMMEDIATE mode is assumed. Be aware that the NOWAIT option can cause a failure that occurs after the database receives the commit message, but before the redo log records are written. This can falsely indicate to a transaction that its changes are persistent. Also, it can violate the durability of ACID (Atomicity, Consistency, Isolation, Durability) transactions if the database shuts down unexpectedly.
Modifiable	Yes (at both session-level and system-level). Values supplied for COMMIT_WRITE in an ALTER SYSTEM or ALTER SESSION statement must be separated by a comma.
Modifiable in a PDB	Yes
Range of values	Single-quoted, comma-separated list of either IMMEDIATE or BATCH, and either WAIT or NOWAIT.
Basic	No
Oracle RAC	Each instance may have its own setting

The IMMEDIATE and BATCH options control how redo is batched by Log Writer. The WAIT and NOWAIT options control when the redo for a commit is flushed to the redo logs.

> **Note:**
>
> The COMMIT_WRITE parameter is deprecated. It is retained for backward compatibility only. It is replaced by the COMMIT_LOGGING and COMMIT_WAIT parameters.

2.51 COMMON_USER_PREFIX

COMMON_USER_PREFIX specifies a prefix that the names of common users, roles, and profiles in a multitenant container database (CDB) must start with.

Property	Description
Parameter type	String
Syntax	COMMON_USER_PREFIX = prefix
Default value	In a CDB root, C## is the default value. In an application root, the empty string is the default value.
Modifiable	No
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Multiple instances must have the same value

Names of local users, roles, and profiles must not start with the same prefix. A case-insensitive comparison of the prefixes for user, role, and profile names to the value of this parameter is done.

When a value is set for COMMON_USER_PREFIX, Oracle will require that the names of common users, roles, and profiles start with the string assigned to this parameter.

The names of users, roles, and profiles created using this prefix must be valid names.

Regardless of the value of the COMMON_USER_PREFIX parameter, the names of local users, roles, and profiles cannot start with C##. Similarly, the names of application common users and local users in an application PDB cannot start with C##.

> **Caution:**
>
> You can change the value of the COMMON_USER_PREFIX parameter, but do so only with great care.

If COMMON_USER_PREFIX is set to an empty string, Oracle will *not* enforce any restrictions on the names of common or local users, roles, and profiles.

Setting this parameter to an empty string will result in no restrictions being placed on names of common and local users, roles, and profiles, which could lead to conflicts between the names of local and common users, roles, and profiles when a PDB is plugged into a different CDB, or when opening a PDB that was closed when a common user was created.

Note:

COMMON_USER_PREFIX can be set in the context of an application container.

If you set COMMON_USER_PREFIX in the application root to a non-null value, then the application common user should start with that prefix, and a local user created in an application PDB cannot start with that prefix.

By default, COMMON_USER_PREFIX is the empty string in an application root.

Note:

When you query the V$PARAMETER or V$SYSTEM_PARAMETER view, a value of NONE is returned for the DEFAULT_VALUE column for the COMMON_USER_PREFIX parameter.

However, the database enforces a default value of C## for a CDB root and a default value of the empty string for an application root.

See Also:

- *Oracle Database SQL Language Reference* for information about valid user names
- *Oracle Database SQL Language Reference* for information about valid role names
- *Oracle Database SQL Language Reference* for information about valid profile names
- *Oracle Multitenant Administrator's Guide* for more information about the multitenant architecture

2.52 COMPATIBLE

COMPATIBLE enables you to use a new release of Oracle while ensuring the ability to downgrade the database to an earlier release.

Property	Description
Parameter type	String
Syntax	COMPATIBLE = *release_number*
Default value	23.4.0
Modifiable	No
Modifiable in a PDB	No

Property	Description
Range of values	19.0.0 to default release Values must be specified as at least three decimal numbers with each number separated by a dot, such as 23.4.0 or 23.4.0.0
Basic	Yes
Oracle RAC	Multiple instances must have the same value.

The COMPATIBLE parameter specifies the Oracle version number that the database disk format must be compatible with. The database can be downgraded to the version specified in the COMPATIBLE parameter or any later version.

Setting COMPATIBLE ensures that new features do not write data formats or structures to disk that are not compatible with the earlier release, preventing a future downgrade. Features that require a higher value of COMPATIBLE to work correctly may be restricted or disabled to ensure downgrades are possible.

Typically, users keep COMPATIBLE unchanged when upgrading their Oracle software. After upgrade, users will run the new release of the Oracle software for a few weeks to ensure that the new release is working correctly. Afterwards, users can choose to update COMPATIBLE to the latest version to take advantage of the new features.

Notes:

- The value of the COMPATIBLE parameter can be increased to a higher version, but it can never be decreased to a lower version.
- The value of the COMPATIBLE parameter should not be changed for a Release Update (RU) or Release Update Revision (RUR). For example, assume you are running Oracle Database 21c and the value of COMPATIBLE is 21.0.0. You then apply Oracle Database Release Update 21.4.0.0.0. Do not set the value of COMPATIBLE to 21.4.0; leave it set to 21.0.0.
- When using a standby database, this parameter must have the same value on both the primary and standby databases.

See Also:

Oracle Database Upgrade Guide for more information on setting this parameter

2.53 CONNECTION_BROKERS

CONNECTION_BROKERS is used to specify connection broker types, the number of connection brokers of each type, and the maximum number of connections per broker.

Property	Description
Parameter type	String
Syntax	`CONNECTION_BROKERS = broker_description[,...]`
Syntax	**`broker_description::=`** `((type_clause)(brokers_clause)[(broker_options)])`
Syntax	**`type_clause::=`** `TYPE={ DEDICATED | EMON | POOLED }` Indicates the broker type. This is a mandatory parameter.
Syntax	**`brokers_clause::=`** `BROKERS=`*`integer`* Indicates the number of brokers of the specified type. This is a mandatory parameter. The specified integer value must be greater than or equal to 0. If set to 0, brokers will not accept new connections, but existing connections will continue as normal.
Syntax	**`broker_options::=`** `CONNECTIONS=`*`integer`* The maximum number of connections per broker. This is an optional parameter. If the specified integer value is greater than the maximum allowed for the platform, the maximum allowed for the platform is used.
Default value	The default value for the initialization parameter will contain the `DEDICATED` and `EMON` broker types. Certain types of brokers are only started when certain features are enabled, so their configuration will only apply if the broker is needed.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No
Oracle RAC	The same value should be set on all instances

The connection brokers are used in these cases:

- DEDICATED brokers are used by the multiprocess and multithreaded Oracle features. See *Oracle Database Concepts* for more information about these features.

  `DEDICATED` brokers are also used when the `USE_DEDICATED_BROKER` initialization parameter is set to `true`. See "USE_DEDICATED_BROKER" for more information about the `USE_DEDICATED_BROKER` initialization parameter.

- EMON brokers are used when there is a client registered for notification over 12*c* AQ queues. It is not on by default. See *Oracle Database Advanced Queuing User's Guide* for more information about AQ queues.

- POOLED brokers are used whenever a Database Resident Connection Pooling (DRCP) pool is active. See *Oracle Database Concepts* for more information about DRCP pooling.

  The POOLED broker does not appear in the parameter by default. In this case, the DRCP fields are used. If you specify the `POOLED` broker in the parameter, then that specification will override the DRCP fields, and further attempts to set the DRCP fields will then throw an error. Oracle recommends that the parameter be used instead of the DRCP fields.

To make it easier to modify the list, individual entries are indexed using the TYPE so it is not necessary to re-specify the entire list. For example, to adjust the number of DEDICATED brokers:

```
alter system set connection_brokers = '((TYPE=DEDICATED)(BROKERS=2))'
```

2.54 CONTAINER_DATA

Use CONTAINER_DATA to control whether queries on extended data-linked objects from within a PDB return rows from both the root and the PDB, or rows from only the PDB.

Property	Description
Parameter type	String
Syntax	CONTAINER_DATA = { ALL | CURRENT | CURRENT_DICTIONARY }
Default value	ALL
Modifiable	ALTER SESSION
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Different instances can use different values.

This parameter controls the behavior of queries on the following types of objects:

- Extended data-linked application common objects

  This type of object stores shared data in an application root, and also allows application PDBs to store local data that is unique to each application PDB.

  When this type of object is queried from an application root, only the shared data in the application root is returned.

  When this type of object is queried from an application PDB, the value of the CONTAINER_DATA initialization parameter controls the query result as follows:

  - ALL: The query returns both the shared data in the application root and the local data pertaining to the application PDB
  - CURRENT: The query returns only the local data pertaining to the application PDB
  - CURRENT_DICTIONARY: The query returns both the shared data in the application root and the local data pertaining to the application PDB

- Extended data-linked Oracle-supplied data dictionary objects

  This type of object stores data pertaining to the CDB root, as well as data pertaining to individual PDBs.

  When this type of object is queried from the CDB root, only data pertaining to the CDB root is returned.

  When this type of object is queried from a PDB, the value of the CONTAINER_DATA initialization parameter controls the query result as follows:

  - ALL: The query returns data pertaining to both the CDB root and the PDB
  - CURRENT: The query returns only data pertaining to the PDB

- CURRENT_DICTIONARY: The query returns only data pertaining to the PDB

2.55 CONTAINERS_PARALLEL_DEGREE

CONTAINERS_PARALLEL_DEGREE can be used to control the degree of parallelism of a query involving containers().

Property	Description
Parameter type	Integer
Default value	65535
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	Cannot be set to a value lower than 2 or higher than 65535.
Basic	No
Oracle RAC	Different values can be set on different instances.

The value of CONTAINERS_PARALLEL_DEGREE, if set, will override the default DOP for a containers() query.

By default, a containers() query uses a degree of parallelism equal to (1 + number of open PDBs) in the case of CDB root and (1 + number of open application PDBs) in the case of application root.

If the value of CONTAINERS_PARALLEL_DEGREE is lower than 65535, then this value is used as the degree of parallelism of a query involving containers(). Otherwise (when the value is 65535), the default degree of parallelism is (1 + number of open PDBs) or (1 + number of open application PDBs) as described above.

See Also:

- *Oracle Multitenant Administrator's Guide* for more information about CDB roots
- *Oracle Multitenant Administrator's Guide* for more information about application roots

2.56 CONTROL_FILE_RECORD_KEEP_TIME

CONTROL_FILE_RECORD_KEEP_TIME specifies the minimum number of days before a reusable record in the control file can be reused.

Property	Description
Parameter type	Integer
Default value	7 (days)
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No

Property	Description
Range of values	0 to 365 (days)
Basic	No

In the event a new record must be added to a reusable section and the oldest record has not aged enough, the record section expands. If this parameter is set to 0, then reusable sections never expand, and records are reused as needed.

If the number of reusable records in the control file exceeds the circular reuse record limit UB4MAXVAL, then reusable records will be overwritten even if CONTROL_FILE_RECORD_KEEP_TIME has not elapsed. UB4MAXVAL is defined in the oratypes.h header file, which is found in the public directory. Its value may vary according to the operating system you are using.

Note:

This parameter applies only to records in the control file that are circularly reusable (such as archive log records and various backup records). It does not apply to records such as data file, tablespace, and redo thread records, which are never reused unless the corresponding object is dropped from the tablespace.

See Also:

- "CONTROL_FILES"
- *Oracle Database Backup and Recovery User's Guide* for more information about this parameter

2.57 CONTROL_FILES

CONTROL_FILES specifies one or more names of control files, separated by commas.

Property	Description
Parameter type	String
Syntax	CONTROL_FILES = *filename* [, *filename*] ... **Note:** The control file name can be an OMF (Oracle Managed Files) name. This occurs when the control file is re-created using the CREATE CONTROLFILE REUSE statement.
Default value	Operating system-dependent
Modifiable	No
Modifiable in a PDB	No
Range of values	1 to 8 filenames
Basic	Yes

Property	Description
Oracle RAC	Multiple instances must have the same value.

Every database has a **control file**, which contains entries that describe the structure of the database (such as its name, the timestamp of its creation, and the names and locations of its data files and redo files).

Oracle recommends that you multiplex multiple control files on different devices or mirror the file at the operating system level.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for information about specifying control files at database creation

2.58 CONTROL_MANAGEMENT_PACK_ACCESS

`CONTROL_MANAGEMENT_PACK_ACCESS` specifies which of the Server Manageability Packs should be active.

Property	Description
Parameter type	String
Syntax	`CONTROL_MANAGEMENT_PACK_ACCESS = { NONE | DIAGNOSTIC | DIAGNOSTIC+TUNING }`
Default value	Enterprise Edition: `DIAGNOSTIC+TUNING` Oracle Database Free: `DIAGNOSTIC+TUNING` All other editions: `NONE`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No

The following packs are available:

- The `DIAGNOSTIC` pack includes AWR, ADDM, and so on.
- The `TUNING` pack includes SQL Tuning Advisor, SQLAccess Advisor, and so on.

  A license for `DIAGNOSTIC` is required for enabling the `TUNING` pack.

Values

- `NONE`

  Neither pack is available.
- `DIAGNOSTIC`

  Only the `DIAGNOSTIC` pack is available.
- `DIAGNOSTIC+TUNING`

Both packs are available.

> **See Also:**
>
> *Oracle Database Licensing Information User Manual*

2.59 CORE_DUMP_DEST

`CORE_DUMP_DEST` specifies the directory where Oracle dumps core files.

Property	Description
Parameter type	String
Syntax	`CORE_DUMP_DEST = directory`
Default value	*ORACLE_HOME*`/DBS`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No

`CORE_DUMP_DEST` is primarily a UNIX parameter and may not be supported on your platform.

> **Note:**
>
> This parameter is ignored by the new diagnosability infrastructure introduced in Oracle Database 11g Release 1 (11.1), which places trace and core files in a location controlled by the `DIAGNOSTIC_DEST` initialization parameter.

> **See Also:**
>
> "DIAGNOSTIC_DEST"

2.60 CPU_COUNT

`CPU_COUNT` specifies the number of CPUs available for Oracle Database to use.

Property	Description
Parameter type	Integer
Default value	`0`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes

Property	Description
Range of values	0 to unlimited
Basic	No
Oracle RAC	The same value should be used on all instances.

On CPUs with multiple CPU threads, it specifies the total number of available CPU threads. Various components of Oracle Database are configured based on the number of CPUs, such as the Optimizer, Parallel Query, and Resource Manager.

If CPU_COUNT is set to 0 (its default setting), then Oracle Database continuously monitors the number of CPUs reported by the operating system and uses the current count. If CPU_COUNT is set to a value other than 0, then Oracle Database will use this count rather than the actual number of CPUs, thus disabling dynamic CPU reconfiguration.

When Resource Manager is managing CPU (RESOURCE_MANAGER_PLAN is set), then the database's CPU utilization is limited to CPU_COUNT CPU threads. This feature is called Instance Caging. If Resource Manager is enabled at the CDB level, then the PDB's CPU utilization is limited to the PDB's CPU_COUNT.

Note:

Setting CPU_COUNT to a value greater than the current number of CPUs results in an error. However, if CPU_COUNT is set to a value greater than the current number of CPUs in the initialization parameter file, then CPU_COUNT is capped to the current number of CPUs.

Note:

When a value is not explicitly set for CPU_COUNT, the maximum default value for CPU_COUNT is 2 for an Oracle ASM Proxy instance, 4 for an Oracle ASM instance, and 8 for an Oracle IOServer instance.

See Also:

- "CPU_MIN_COUNT"
- *Oracle Database VLDB and Partitioning Guide* for information about how CPU_COUNT is used to determine the default degree of parallelism for a single instance or Oracle RAC configuration when the PARALLEL clause is specified but no degree of parallelism is listed
- *Oracle Database Administrator's Guide* for an example of how CPU resources are allocated if you enable instance caging and set a maximum utilization limit in a resource plan

2.61 CPU_MIN_COUNT

CPU_MIN_COUNT specifies the minimum number of CPUs required by a pluggable database (PDB) at any given time.

Property	Description
Parameter type	String
Syntax	CPU_MIN_COUNT = '*value*'
Default value	The value of CPU_COUNT
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Range of Values	Decimal values from 0.1 through 0.95, where the decimal value is a multiple of 0.05 Integer values from 1 up to and including the value of CPU_COUNT
Basic	No
Oracle RAC	The same value should be used on all instances.

This parameter specifies the minimum number of CPUs required by a PDB at any given time. For multi-threaded CPUs, this number corresponds to CPU threads, not CPU cores.

You can set this parameter at the CDB level, and for each individual PDB. This enables you to control each PDBs minimum share of CPU utilization within a CDB. If the sum of the CPU_MIN_COUNT values across all open PDBs in a CDB is equal to the value of CPU_MIN_COUNT for the CDB, then the CDB instance is considered full. If the sum exceeds the value of CPU_MIN_COUNT for the CDB, then the CDB instance is over-provisioned. Oracle does not prevent you from over-provisioning a CDB.

Resource Manager is enabled at the CDB level by setting the RESOURCE_MANAGER_PLAN at the root level to the name of a CDB resource plan. If the CDB resource plan has no configured CPU directives, that is, the SHARES and UTILIZATION_LIMIT directives are unset, then Resource Manager uses the CPU_COUNT and CPU_MIN_COUNT settings for the PDB to manage CPU utilization.

> **Note:**
>
> Setting this parameter to a very low value can result in insufficient CPU allocation and poor performance.

> **See Also:**
>
> "CPU_COUNT"

2.62 CREATE_BITMAP_AREA_SIZE

CREATE_BITMAP_AREA_SIZE specifies the amount of memory (in bytes) allocated for bitmap creation.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	No
Modifiable in a PDB	Yes
Range of values	Operating system-dependent
Basic	No

This parameter is relevant only for systems containing bitmap indexes.

> **Note:**
>
> Oracle does not recommend using the CREATE_BITMAP_AREA_SIZE parameter unless the instance is configured with the shared server option. Oracle recommends that you enable automatic sizing of SQL working areas by setting PGA_AGGREGATE_TARGET instead. CREATE_BITMAP_AREA_SIZE is retained for backward compatibility.

A larger value may speed up index creation.

Cardinality is the number of unique values in a column in relation to the number of rows in the table. If cardinality is very small, you can set a small value for this parameter. For example, if cardinality is only 2, then the value can be in kilobytes rather than megabytes. As a general rule, the higher the cardinality, the more memory is needed for optimal performance.

> **See Also:**
>
> *Oracle Database SQL Tuning Guide* for more information on using bitmap indexes

2.63 CREATE_STORED_OUTLINES

CREATE_STORED_OUTLINES determines whether Oracle automatically creates and stores an outline for each query submitted during the session.

Property	Description
Parameter type	String

Property	Description
Syntax	CREATE_STORED_OUTLINES = { true | false | *category_name* } [NOOVERRIDE]
Default value	There is no default value.
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No

Values

- `true`

  Enables automatic outline creation for subsequent queries in the same session. These outlines receive a unique system-generated name and are stored in the `DEFAULT` category. If a particular query already has an outline defined for it in the `DEFAULT` category, then that outline will remain and a new outline will not be created.

- `false`

  Disables automatic outline creation during the session. This is the default.

- *`category_name`*

  Enables the same behavior as `true` except that any outline created during the session is stored in the *`category_name`* category.

- `NOOVERRIDE`

  `NOOVERRIDE` specifies that this system setting will not override the setting for any session in which this parameter was explicitly set. If you do not specify `NOOVERRIDE`, then this setting takes effect in all sessions.

> **See Also:**
>
> *Oracle Database SQL Tuning Guide* for more information on setting this parameter

2.64 CURSOR_BIND_CAPTURE_DESTINATION

`CURSOR_BIND_CAPTURE_DESTINATION` determines the location at which bind variables that are captured from SQL cursors are available.

Property	Description
Parameter type	String
Syntax	CURSOR_BIND_CAPTURE_DESTINATION = { off | memory | memory+disk }
Default value	memory+disk

Property	Description
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No

Values

- off

  Bind variables are not captured from SQL cursors.

- memory

  Bind variables are captured from SQL cursors, and are available only in memory (V$ views).

- memory+disk

  Bind variables are captured from SQL cursors, and are available in memory (V$ views) and disk (Automatic Workload Repository tables, SQL Tuning Set tables, and so on).

  When you specify this value with a SQL ALTER SESSION or ALTER SYSTEM statement, enclose the value in single quotes or double quotes. For example:

```
ALTER SESSION SET CURSOR_BIND_CAPTURE_DESTINATION = 'memory+disk';
ALTER SYSTEM SET CURSOR_BIND_CAPTURE_DESTINATION = "memory+disk";
```

2.65 CURSOR_INVALIDATION

CURSOR_INVALIDATION controls whether deferred cursor invalidation or immediate cursor invalidation is used for DDL statements by default.

Property	Description
Parameter type	String
Syntax	CURSOR_INVALIDATION = { DEFERRED | IMMEDIATE }
Default value	IMMEDIATE
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Different instances can have different values.

Deferred invalidation reduces the number of cursor invalidations and spreads the recompilation workload over time. Note that when the recompilation workload is spread over time, a cursor may run with a sub-optimal plan until it is recompiled, and may incur small execution-time overhead.

Prior to Oracle Database 12*c* Release 2 (12.2.0.1), immediate cursor invalidation was used.

This parameter provides system or session level default for the DEFERRED or IMMEDIATE option for the INVALIDATION clause in DDL statements.

When this parameter is set to DEFERRED, an application can take advantage of reduced cursor invalidation without making any other application changes.

When this parameter is set to `IMMEDIATE`, the application will experience the same cursor invalidation behavior as in Oracle Database 12*c* Release 1 (12.1).

2.66 CURSOR_SHARING

`CURSOR_SHARING` determines what kind of SQL statements can share the same cursors.

Property	Description
Parameter type	String
Syntax	`CURSOR_SHARING = { EXACT | FORCE }`
Default value	`EXACT`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

Values

- `FORCE`

  Allows the creation of a new cursor if sharing an existing cursor, or if the cursor plan is not optimal.

- `EXACT`

  Only allows statements with identical text to share the same cursor.

> **See Also:**
>
> *Oracle Database SQL Tuning Guide* before setting the `CURSOR_SHARING` parameter to learn about the performance implications

2.67 CURSOR_SPACE_FOR_TIME

`CURSOR_SPACE_FOR_TIME` lets you use more space for cursors to save time.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No

> **Note:**
>
> The `CURSOR_SPACE_FOR_TIME` parameter is deprecated. It is retained for backward compatibility only.

This parameter affects both the shared SQL area and the client's private SQL area.

Most users will not need to set this parameter because of the significantly enhanced concurrency modifications introduced in Oracle Database 10*g* Release 2 (10.2.0.2) and later.

Values

- `true`

  Shared SQL areas are kept pinned in the shared pool. As a result, shared SQL areas are not aged out of the pool as long as an open cursor references them. Because each active cursor's SQL area is present in memory, execution is faster. However, the shared SQL areas never leave memory while they are in use. Therefore, you should set this parameter to `true` only when the shared pool is large enough to hold all open cursors simultaneously.

  In addition, a setting of `true` retains the private SQL area allocated for each cursor between executions instead of discarding it after cursor execution, saving cursor allocation and initialization time.

- `false`

  Shared SQL areas can be deallocated from the library cache to make room for new SQL statements.

> **Note:**
>
> If this parameter is set to `true`, then the `SERIAL_REUSE` parameter is disabled.

> **See Also:**
>
> - "SERIAL_REUSE"

2.68 DATA_GUARD_MAX_IO_TIME

DATA_GUARD_MAX_IO_TIME sets the maximum number of seconds that can elapse before a process is considered hung while performing a regular I/O operation in an Oracle Data Guard environment. Regular I/O operations include read, write, and status operations.

> **See Also:**
>
> "DATA_GUARD_MAX_LONGIO_TIME," which enables you to set the timeout for long I/O operations, such as open and close operations, in an Oracle Data Guard environment

Property	Description
Parameter type	Integer
Default value	240
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	10 to 7200
Basic	No
Oracle RAC	Different instances can use different values.

2.69 DATA_GUARD_MAX_LONGIO_TIME

DATA_GUARD_MAX_LONGIO_TIME sets the maximum number of seconds that can elapse before a process is considered hung while performing a long I/O operation in an Oracle Data Guard environment. Long I/O operations include open and close operations.

Property	Description
Parameter type	Integer
Default value	240
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	10 to 7200
Basic	No
Oracle RAC	Different instances can use different values.

> **See Also:**
>
> "DATA_GUARD_MAX_IO_TIME"

2.70 DATA_GUARD_SYNC_LATENCY

DATA_GUARD_SYNC_LATENCY controls how many seconds the Log Writer (LGWR) process waits beyond the response of the first in a series of Oracle Data Guard SYNC redo transport mode connections.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	0 to the number of seconds specified by the NET_TIMEOUT attribute for the LOG_ARCHIVE_DEST_n parameter
Basic	No
Oracle RAC	The same value must be used on all instances.

The default value is 0, which means that the LGWR will wait up to the number of seconds specified by the NET_TIMEOUT attribute of the LOG_ARCHIVE_DEST_n parameter for each SYNC standby destination.

For example, in an Oracle Data Guard configuration that has two standbys which receive redo in SYNC mode, you would define LOG_ARCHIVE_DEST_2 and LOG_ARCHIVE_DEST_3 to use SYNC transport with DATA_GUARD_SYNC_LATENCY set to a value of 2 seconds. When redo needs to be sent to the standbys, it is sent to both the LOG_ARCHIVE_DEST_2 and LOG_ARCHIVE_DEST_3 connections in parallel and the LGWR will wait for acknowledgement. If LOG_ARCHIVE_DEST_2 responds with its message acknowledging that the redo has been received first, the LGWR will not wait for LOG_ARCHIVE_DEST_3 to respond for more than 2 extra seconds (DATA_GUARD_SYNC_LATENCY). If LOG_ARCHIVE_DEST_3 does not respond within those 2 seconds the LGWR disconnects from LOG_ARCHIVE_DEST_3, putting it into the error state. Redo continues to be sent to LOG_ARCHIVE_DEST_2 as usual. After the duration of the REOPEN attribute for LOG_ARCHIVE_DEST_3 has elapsed, the LGWR reconnects to LOG_ARCHIVE_DEST_3 and redo transfer continues. In this manner, the maximum impact of having the second SYNC standby would be restricted to 2 seconds more than having only one SYNC standby, while allowing the Oracle Data Guard configuration to maintain the desired protection level.

LGWR will never wait longer than the value of the NET_TIMEOUT attribute of the LOG_ARCHIVE_DEST_n parameter, regardless of the value of DATA_GUARD_SYNC_LATENCY.

See Also:

"LOG_ARCHIVE_DEST_*n*"

2.71 DATA_TRANSFER_CACHE_SIZE

DATA_TRANSFER_CACHE_SIZE sets the size of the data transfer cache (in bytes) used to receive data blocks (typically from a primary database in an Oracle Data Guard environment) for consumption by an instance during execution of an RMAN RECOVER ... NONLOGGED BLOCK command.

Property	Description
Parameter type	Big integer
Syntax	DATA_TRANSFER_CACHE_SIZE = *integer* [K | M | G]
Default value	If SGA_TARGET is set, then if DATA_TRANSFER_CACHE_SIZE is not specified, the default size of the data transfer cache is 0 (internally determined by Oracle Database). If SGA_TARGET is set and DATA_TRANSFER_CACHE_SIZE is specified, then the user-specified value indicates the minimum value for the data transfer cache. If SGA_TARGET is not set, the data transfer cache will not be available.
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	0 – 512M, rounded up to the next granule size
Basic	No
Oracle RAC	Multiple instances can have different values.

This initialization parameter needs to be set only for databases that do not use Automatic Memory Management and that use the RMAN RECOVER ... NONLOGGED BLOCK command.

2.72 DB_*n*K_CACHE_SIZE

DB_*n*K_CACHE_SIZE (where *n* = 2, 4, 8, 16, 32) specifies the size of the cache for the *n*K buffers.

Property	Description
Parameter type	Big integer
Syntax	DB_[2 | 4 | 8 | 16 | 32]K_CACHE_SIZE = *integer* [K | M | G]
Default value	0 (additional block size caches are not configured by default)
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	Minimum: 0 (values greater than zero are automatically modified to be either the granule size * number of processor groups, or 4 MB * number of CPUs, whichever is greater) Maximum: operating system-dependent
Basic	No

You can set this parameter only when DB_BLOCK_SIZE has a value other than *n*K. For example, if DB_BLOCK_SIZE=4096, then you cannot specify the parameter DB_4K_CACHE_SIZE (because the size for the 4 KB block cache is already specified by DB_CACHE_SIZE).

Do not set this parameter to zero if there are any online tablespaces with an *n*K block size.

Operating system-specific block size restrictions apply. For example, you cannot set DB_32K_CACHE_SIZE if the operating system's maximum block size is less than 32 KB. Also, you cannot set DB_2K_CACHE_SIZE if the minimum block size is greater than 2 KB.

See Also:

Your operating system-specific Oracle documentation for more information on block size restrictions

2.73 DB_BIG_TABLE_CACHE_PERCENT_TARGET

DB_BIG_TABLE_CACHE_PERCENT_TARGET specifies the cache section target size for automatic big table caching, as a percentage of the buffer cache.

Property	Description
Parameter type	String
Syntax	DB_BIG_TABLE_CACHE_PERCENT_TARGET = string
Default value	0
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Basic	No
Oracle RAC	Multiple instances can have different values, but it is recommended to keep the big table cache section size uniform.

Automatic big table caching enables parallel queries and serial queries to use the buffer cache, which enhances the in-memory query capabilities of Oracle Database. Automatic big table caching is designed primarily to enhance performance for data warehouse workloads, but it also improves performance in mixed workloads.

Starting in Oracle Database 12*c* Release 1 (12.1.0.2), table scans can use a different algorithm in the following scenarios:

- Parallel queries:

  In single-instance and Oracle Real Application Clusters (Oracle RAC) databases, parallel queries can use the automatic big table cache when the DB_BIG_TABLE_CACHE_PERCENT_TARGET initialization parameter is set to a nonzero value, and the PARALLEL_DEGREE_POLICY initialization parameter is set to AUTO or ADAPTIVE.

- Serial queries:

  In a single-instance configuration only, serial queries can use the automatic big table cache when the DB_BIG_TABLE_CACHE_PERCENT_TARGET initialization parameter is set to a nonzero value.

When a nonzero value is specified for the `DB_BIG_TABLE_CACHE_PERCENT_TARGET` parameter, the value indicates the percentage of the buffer cache to reserve for the big table cache. The largest value that can be specified with the `DB_BIG_TABLE_CACHE_PERCENT_TARGET` parameter is 90, which reserves 10% of the buffer cache for usage besides table scans.

The default value of this parameter is `0`. Therefore, automatic big table caching is not enabled by default. When automatic big table caching is not enabled, queries might run using the least recently used (LRU) mechanism for cached reads, or might decide to use direct reads for the table scan.

If a large table is about the size of the combined size of the big table cache of all instances, the table will be partitioned and cached or mostly cached on all instances. With in-memory parallel query, this could eliminate most disk reads for queries on the table, or the database could intelligently read from disk only for the portion of the table that does not fit in the big table cache. If the big table cache cannot cache all the tables to be scanned, only the most frequently accessed tables will be cached, and the rest will be read via direct read automatically.

Use these guidelines when setting the parameter:

- If you do not enable automatic degree of parallelism (DOP) in your Oracle RAC environment, do not set this parameter because the big table cache is not used in that situation.
- When setting this parameter, consider the workload mix: how much of the workload is for OLTP; insert, update, and random access; and how much of the workload involves table scans. Because data warehouse workloads often perform large table scans, you may consider giving the big table cache section a higher percentage of buffer cache space for data warehouses.
- This parameter can be dynamically changed if the workload changes. The change could take some time to reach the target (depending on the current workload) because buffer cache memory might be actively used at that time.

Note:

Automatic big table caching uses temperature and object-based algorithms to track medium and big tables. Oracle will cache very small tables, but they will not be tracked by automatic big table caching.

See Also:

- "PARALLEL_DEGREE_POLICY"
- See "V$BT_SCAN_CACHE" and "V$BT_SCAN_OBJ_TEMPS" for more information about the big table cache
- *Oracle Database VLDB and Partitioning Guide* for more information about this parameter and about automatic big table caching

2.74 DB_BLOCK_BUFFERS

DB_BLOCK_BUFFERS specifies the number of database buffers in the buffer cache.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	No
Modifiable in a PDB	No
Range of values	50 to an operating system-specific maximum
Basic	No
Oracle RAC	Multiple instances can have different values, and you can change the values as needed.

Note:

DB_BLOCK_BUFFERS cannot be combined with the dynamic DB_CACHE_SIZE parameter; combining these parameters in the same parameter file will produce an error.

DB_BLOCK_BUFFERS is one of several parameters that contribute to the total memory requirements of the SGA of an instance.

This parameter, together with DB_BLOCK_SIZE, determines the total size of the buffer cache. Effective use of the buffer cache can greatly reduce the I/O load on the database. DB_BLOCK_SIZE can be specified only when the database is first created, so you use DB_BLOCK_BUFFERS to control the size of the buffer cache.

Note:

The DB_BLOCK_BUFFERS initialization parameter is deprecated. It is maintained for backward compatibility.

Oracle recommends that you use DB_CACHE_SIZE instead.

See Also:

"DB_CACHE_SIZE"

2.75 DB_BLOCK_CHECKING

DB_BLOCK_CHECKING specifies whether Oracle Database performs block checking for database blocks.

Property	Description
Parameter type	String
Syntax	DB_BLOCK_CHECKING = { FALSE | OFF | LOW | MEDIUM | TRUE | FULL }
Default value	FALSE
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes, with the following restriction: If block checking is enabled for a CDB, then you cannot subsequently disable block checking in any of its PDBs. That is, if the value of DB_BLOCK_CHECKING in a CDB is LOW, MEDIUM, TRUE, or FULL, and you then attempt to set the value of DB_BLOCK_CHECKING in one of its PDBs to FALSE or OFF, an error will occur.
Basic	No

Values

- OFF or FALSE

  No block checking is performed for blocks in user tablespaces. However, semantic block checking for SYSTEM tablespace blocks is always turned on.

- LOW

  Basic block header checks are performed after block contents change in memory (for example, after UPDATE, INSERT or DELETE statements, or after inter-instance block transfers in Oracle RAC).

- MEDIUM

  All LOW checks and full semantic checks are performed for all objects except indexes (whose contents can be reconstructed by a drop+rebuild on encountering a corruption).

- FULL or TRUE

  All LOW and MEDIUM checks and full semantic checks are performed for all objects.

Oracle checks a block by going through the data in the block, making sure it is logically self-consistent. Block checking can often prevent memory and data corruption. Block checking typically causes 1% to 10% overhead in most applications, depending on workload and the parameter value. Specific DML overhead may be higher. The more updates or inserts in a workload, the more expensive it is to turn on block checking. You should set DB_BLOCK_CHECKING to FULL if the performance overhead is acceptable.

For backward compatibility, the use of FALSE (implying OFF) and TRUE (implying FULL) is preserved.

> **Caution:**
>
> Before enabling block checking with this parameter, Oracle recommends that you detect and repair any logical corruptions in the database. Otherwise, a block that contains logical corruption will be marked as "soft corrupt" after block checking is enabled and the block is modified by a DML statement. This will result in `ORA-1578` errors and the block will be unreadable. For more information about detecting and repairing logical corruptions, see *Oracle Database Backup and Recovery User's Guide*.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about this parameter

2.76 DB_BLOCK_CHECKSUM

`DB_BLOCK_CHECKSUM` determines whether `DBWn` and the direct loader will calculate a checksum (a number calculated from all the bytes stored in the block) and store it in the cache header of every data block when writing it to disk.

Property	Description
Parameter type	String
Syntax	`DB_BLOCK_CHECKSUM = { OFF | FALSE | TYPICAL | TRUE | FULL }`
Default value	`TYPICAL`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No

Checksums are verified when a block is read - only if this parameter is `TYPICAL` or `FULL` and the last write of the block stored a checksum. In `FULL` mode, Oracle also verifies the checksum before a change application from update/delete statements and recomputes it after the change is applied. In addition, Oracle gives every log block a checksum before writing it to the current log.

Most of the log block checksum is done by the generating foreground processes, while the LGWR or the LGWR worker processes (LG*nn* processes) perform the rest of the work, for better CPU and cache efficiency.

If this parameter is set to `OFF`, `DBWn` calculates checksums only for the `SYSTEM` tablespace, but not for user tablespaces. In addition, no log checksum is performed when this parameter is set to `OFF`.

Checksums allow Oracle to detect corruption caused by underlying disks, storage systems, or I/O systems. If set to `FULL`, `DB_BLOCK_CHECKSUM` also catches in-memory corruptions and stops them from making it to the disk. Turning on this feature in `TYPICAL` mode causes only

an additional 1% to 2% overhead. In the FULL mode it causes 4% to 5% overhead. Oracle recommends that you set DB_BLOCK_CHECKSUM to TYPICAL.

For backward compatibility the use of TRUE (implying TYPICAL) and FALSE (implying OFF) values is preserved.

> **See Also:**
>
> *Oracle Database Backup and Recovery Reference* for more information about this parameter

2.77 DB_BLOCK_SIZE

DB_BLOCK_SIZE specifies (in bytes) the size of Oracle database blocks.

Property	Description
Parameter type	Integer
Default value	8192
Modifiable	No
Modifiable in a PDB	No
Range of values	2048 to 32768, but your operating system may have a narrower range
Basic	Yes
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

> **Note:**
>
> Set this parameter at the time of database creation. Do not alter it afterward.

Typical values for DB_BLOCK_SIZE are 4096 and 8192. The value of this parameter must be a multiple of the physical block size at the device level.

The value for DB_BLOCK_SIZE in effect at the time you create the database determines the size of the blocks. The value must remain set to its initial value.

For Oracle Real Application Clusters (Oracle RAC), this parameter affects the maximum value of the FREELISTS storage parameter for tables and indexes. Oracle uses one database block for each freelist group. Decision support system (DSS) and data warehouse database environments tend to benefit from larger block size values.

> **Note:**
>
> 64-bit operating systems support a maximum DB_BLOCK_SIZE value of 32768

See Also:

- *Oracle Database Administrator's Guide* for information on setting this parameter
- *Oracle Database SQL Language Reference* for information on freelist groups

2.78 DB_CACHE_ADVICE

DB_CACHE_ADVICE enables or disables statistics gathering used for predicting behavior with different cache sizes through the V$DB_CACHE_ADVICE performance view.

Property	Description
Parameter type	String
Syntax	DB_CACHE_ADVICE = { ON | READY | OFF }
Default value	If STATISTICS_LEVEL is set to TYPICAL or ALL, then ON If STATISTICS_LEVEL is set to BASIC, then OFF
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Basic	No

Values

- OFF

  Advisory is turned off and the memory for the advisory is not allocated.

- READY

  Advisory is turned off but the memory for the advisory remains allocated. Allocating the memory before the advisory is actually turned on avoids the risk of an error when you switch the parameter to ON.

  If the parameter is switched to this state from ON, the contents of the view are preserved and the memory for the advisory is retained.

  If the parameter is switched to this state from OFF, you may get an error.

- ON

  Advisory is turned on. CPU and memory overheads are incurred. Attempting to set the parameter to this state when it is already in the OFF state may result in an error. Otherwise, the view (V$DB_CACHE_ADVICE) is reset and statistics are gathered to the newly refreshed view.

  If the parameter is in the READY state, you can set it to ON without any errors because the memory is already allocated. The view is reset and statistics are displayed in the newly refreshed view.

> **See Also:**
>
> "V$DB_CACHE_ADVICE"

2.79 DB_CACHE_SIZE

DB_CACHE_SIZE specifies the size of the DEFAULT buffer pool for buffers with the primary block size (the block size defined by the DB_BLOCK_SIZE initialization parameter).

Property	Description
Parameter type	Big integer
Syntax	DB_CACHE_SIZE = *integer* [K | M | G]
Default value	If SGA_TARGET is set: If the parameter is not specified, then the default is 0 (internally determined by the Oracle Database). If the parameter is specified, then the user-specified value indicates a minimum value for the memory pool. If SGA_TARGET is not set, then the default is either 48 MB or 4 MB * number of CPUs, whichever is greater
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No

The value must be at least 4M * number of cpus (smaller values are automatically rounded up to this value). A user-specified value larger than this is rounded up to the nearest granule size. A value of zero is invalid because it is needed for the DEFAULT memory pool of the primary block size, which is the block size for the SYSTEM tablespace.

Note:

This parameter is optional for pluggable databases (PDBs). When this parameter is set for a PDB, it indicates a possible minimum value for the PDB usage of the memory pool.

To be able to use Resource Manager in a CDB to control the amount of memory each PDB can use:

- The `NONCDB_COMPATIBLE` initialization parameter must be set to `FALSE` at the CDB level (in the root of the CDB).
- The `MEMORY_TARGET` initialization parameter must not be set at the CDB level.
- If the `SGA_TARGET` initialization parameter is set at the CDB level, then the following requirement must be met:
  - The value of `DB_CACHE_SIZE` set in a PDB must be less than or equal to 50% of the `SGA_TARGET` value at the CDB level.
- If the `SGA_TARGET` initialization parameter is set at the PDB level, then the following requirement must be met:
  - The value of `DB_CACHE_SIZE` set in a PDB must be less than or equal to 50% of the `SGA_TARGET` value at the PDB level.
- If the `SGA_TARGET` initialization parameter is not set, but the `DB_CACHE_SIZE` initialization parameter is set at the CDB level, then the following requirement must be met:
  - The value of `DB_CACHE_SIZE` set in a PDB must be less than or equal to 50% of the `DB_CACHE_SIZE` value at the CDB level.

When you set `DB_CACHE_SIZE` in a PDB to a value that does not meet these requirements, you receive an error.

See Also:

- *Oracle Database Performance Tuning Guide* and *Oracle Database Administrator's Guide* for more information on setting this parameter
- *Oracle Multitenant Administrator's Guide* for more information about the initialization parameters that control the memory usage of PDBs

2.80 DB_CREATE_FILE_DEST

`DB_CREATE_FILE_DEST` specifies the default location for Oracle-managed datafiles.

Property	Description
Parameter type	String
Syntax	`DB_CREATE_FILE_DEST = directory | disk group`

Property	Description
Default value	There is no default value.
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	Yes

This location is also used as the default location for Oracle-managed control files and online redo logs if none of the DB_CREATE_ONLINE_LOG_DEST_*n* initialization parameters are specified.

If a file system directory is specified as the default location, then the directory must already exist; Oracle does not create it. The directory must have appropriate permissions that allow Oracle to create files in it. Oracle generates unique names for the files, and a file thus created is an Oracle Managed File.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information on setting this parameter and on Oracle Managed Files

2.81 DB_CREATE_ONLINE_LOG_DEST_*n*

DB_CREATE_ONLINE_LOG_DEST_*n* (where *n* = 1, 2, 3, ... 5) specifies the default location for Oracle-managed control files and online redo logs.

Property	Description
Parameter type	String
Syntax	DB_CREATE_ONLINE_LOG_DEST_[1 | 2 | 3 | 4 | 5] = *directory* | *disk group*
Default value	There is no default value.
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	Yes

If more than one DB_CREATE_ONLINE_LOG_DEST_*n* parameter is specified, then the control file or online redo log is multiplexed across the locations of the other DB_CREATE_ONLINE_LOG_DEST_*n* parameters. One member of each online redo log is created in each location, and one control file is created in each location.

Specifying at least two parameters provides greater fault tolerance for the control files and online redo logs if one of the locations should fail.

If a file system directory is specified as the default location, then the directory must already exist; Oracle does not create it. The directory must have appropriate permissions that allow Oracle to create files in it. Oracle generates unique names for the files, and a file thus created is an Oracle Managed File.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information on setting this parameter and on Oracle Managed Files

2.82 DB_DOMAIN

In a distributed database system, `DB_DOMAIN` specifies the logical location of the database within the network structure.

Property	Description
Parameter type	String
Syntax	`DB_DOMAIN = domain_name`
Default value	There is no default value.
Modifiable	No
Modifiable in a PDB	Yes
Range of values	Any legal string of name components, separated by periods and up to 128 characters long (including the periods).
Basic	Yes
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

You should set this parameter if this database is or ever will be part of a distributed system. The value consists of the extension components of a global database name, consisting of valid identifiers (any alphanumeric ASCII characters), separated by periods.

> **Note:**
>
> Oracle recommends that you specify `DB_DOMAIN` as a unique string for all databases in a domain.

This parameter allows one department to create a database without worrying that it might have the same name as a database created by another department. If one sales department's `DB_DOMAIN` is `JAPAN.EXAMPLE.COM`, then their `SALES` database (`SALES.JAPAN.EXAMPLE.COM`) is uniquely distinguished from another database with `DB_NAME` = `SALES` but with `DB_DOMAIN` = `US.EXAMPLE.COM`.

If you omit the domains from the name of a database link, Oracle expands the name by qualifying the database with the domain of your local database as it currently exists in the data dictionary, and then stores the link name in the data dictionary. `DB_DOMAIN` should start with an alphabetic character and exclude these characters:

```
"!@%^&*()+=\\|`~[{]};:'\",<>/?"
```

See Also:

- *Oracle Database Administrator's Guide* for more information on setting this parameter
- The data dictionary view "GLOBAL_NAME"

2.83 DB_FILE_MULTIBLOCK_READ_COUNT

`DB_FILE_MULTIBLOCK_READ_COUNT` specifies the maximum number of blocks read in one I/O operation during a sequential scan.

Property	Description
Parameter type	Integer
Default value	The default value corresponds to the maximum I/O size that can be efficiently performed and is platform-dependent
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	Operating system-dependent
Basic	No

`DB_FILE_MULTIBLOCK_READ_COUNT` is one of the parameters you can use to minimize I/O during table scans. The total number of I/Os needed to perform a full table scan depends on such factors as the size of the table, the multiblock read count, and whether parallel execution is being utilized for the operation.

The default value of this parameter is a value that corresponds to the maximum I/O size that can be performed efficiently. This value is platform-dependent and is 1MB for most platforms.

Because the parameter is expressed in blocks, it will be set to a value that is equal to the maximum I/O size that can be performed efficiently divided by the standard block size. Note that if the number of sessions is extremely large the multiblock read count value is decreased to avoid the buffer cache getting flooded with too many table scan buffers.

Even though the default value may be a large value, the optimizer will not favor large I/Os if you do not set this parameter. It will favor large I/Os only if you explicitly set this parameter to a large value.

Online transaction processing (OLTP) and batch environments typically have values in the range of 4 to 16 for this parameter. DSS and data warehouse environments tend to benefit most from maximizing the value of this parameter. The optimizer is more likely to choose a full table scan over an index if the value of this parameter is high.

The maximum value is the operating system's maximum I/O size expressed as Oracle blocks ((max I/O size)/`DB_BLOCK_SIZE`). If you set this parameter to a value greater than the maximum, then Oracle uses the maximum.

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for information about how setting this parameter incorrectly can cause excessive I/O waits for some execution plans

2.84 DB_FILE_NAME_CONVERT

`DB_FILE_NAME_CONVERT` is useful for creating a duplicate database for recovery purposes. It converts the filename of a new datafile on the primary database to a filename on the standby database.

Property	Description
Parameter type	String

Syntax	`DB_FILE_NAME_CONVERT = 'string1' , 'string2' , 'string3' , 'string4' , ...`
	Where:
	• *string1* is the pattern of the primary database filename
	• *string2* is the pattern of the standby database filename
	• *string3* is the pattern of the primary database filename
	• *string4* is the pattern of the standby database filename
	You can enclose each string in single or double quotation marks.
	You can specify as many pairs of primary and standby replacement strings as required. However, starting with Oracle Database 12c Release 2 (12.2), Oracle recommends that you limit the number of pairs to 99.
	Example:
	`DB_FILE_NAME_CONVERT = '/dbs/t1/','/dbs/t1/s','dbs/t2/','dbs/t2/s'`

Default value	There is no default value.
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No

If you add a datafile to the primary database, you must add a corresponding file to the standby database. When the standby database is updated, this parameter converts the datafile name on the primary database to the datafile name on the standby database. The file on the standby database must exist and be writable, or the recovery process will halt with an error.

Set the value of this parameter to one or more pairs of strings. The first string in a pair is the pattern found in the datafile names on the primary database. The second string in a pair is the pattern found in the datafile names on the standby database.

If you specify an odd number of strings (the last string has no corresponding replacement string), an error is returned during startup. If the filename being converted matches more than one pattern in the pattern/replace string list, the first matched pattern takes effect. There is no limit on the number of pairs that you can specify in this parameter (other than the hard limit of the maximum length of multivalue parameters). However, starting with Oracle Database 12c Release 2 (12.2), Oracle recommends that you limit the number of pairs to 99.

You can also use DB_FILE_NAME_CONVERT to rename the datafiles in the clone control file when setting up a clone database during tablespace point-in-time recovery.

See Also:

- *Oracle Database Backup and Recovery User's Guide* for more information about database backup and recovery
- *Oracle Data Guard Concepts and Administration* for more information about Oracle Data Guard

2.85 DB_FILES

DB_FILES specifies the maximum number of database files that can be opened for this database.

Property	Description
Parameter type	Integer
Default value	200
Modifiable	No
Modifiable in a PDB	Yes
Range of values	Minimum: the largest among the absolute file numbers of the datafiles in the database Maximum: operating system-dependent
Basic	No
Oracle RAC	Multiple instances must have the same value.

The maximum valid value is the maximum number of files, subject to operating system constraint, that will ever be specified for the database, including files to be added by ADD DATAFILE statements.

If you increase the value of DB_FILES, then you must shut down and restart all instances accessing the database before the new value can take effect. If you have a primary and standby database, then they should have the same value for this parameter.

See Also:

- *Oracle Real Application Clusters Administration and Deployment Guide* for information on setting this parameter in an Oracle RAC environment
- Your operating system-specific Oracle documentation for the default value of this parameter

2.86 DB_FLASH_CACHE_FILE

DB_FLASH_CACHE_FILE specifies file name(s) for the flash memory or disk group representing a collection of flash memory, for use with Database Smart Flash Cache.

Property	Description
Parameter type	String
Syntax	DB_FLASH_CACHE_FILE = *filename [,filename]... | disk group*
Default value	There is no default value.
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Basic	No

You can specify up to 16 file names for flash memory devices. For example, if there are three flash raw devices:

```
db_flash_cache_file = /dev/raw/sda, /dev/raw/sdb, /dev/raw/sdc
```

Specifying this parameter without also specifying the DB_FLASH_CACHE_SIZE initialization parameter is not allowed.

> **See Also:**
>
> "DB_FLASH_CACHE_SIZE"

2.87 DB_FLASH_CACHE_SIZE

DB_FLASH_CACHE_SIZE specifies the size of the Database Smart Flash Cache (flash cache). This parameter may only be specified at instance startup.

Property	Description
Parameter type	Big integer
Syntax	DB_FLASH_CACHE_SIZE = *integer* [K | M | G] [, *integer* [K | M | G]]...
Default value	0
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	0, 16M to (2048G - DB_BLOCK_SIZE)
Basic	No

You can specify up to 16 file sizes, for each of the flash memory devices specified with DB_FLASH_CACHE_FILE. For example, if there are three flash raw devices, you can specify the sizes of each device as follows:

```
db_flash_cache_file = /dev/raw/sda, /dev/raw/sdb, /dev/raw/sdc
db_flash_cache_size = 32G, 32G, 64G
```

If your flash cache consists of one flash cache device, you can dynamically change this parameter to `0` for that flash cache device (disabling the flash cache) after the database is started. You can then reenable the flash cache by setting this parameter for the device back to the original value when the database was started. Dynamic resizing of `DB_FLASH_CACHE_SIZE` or reenabling flash cache to a different size is not supported.

If your flash cache includes multiple flash cache devices, you can dynamically change the parameter to `0` for a particular flash cache device (turning it off) after the database is started. You can then reenable that flash cache device by setting this parameter for the device back to the original value it had when the database was started (turning it back on).

For example, to turn off the `/dev/raw/sdb` flash cache device:

```
db_flash_cache_file = /dev/raw/sda, /dev/raw/sdb, /dev/raw/sdc
db_flash_cache_size = 32G, 0, 64G
```

And, to turn the `/dev/raw/sdb` flash cache device back on again:

```
db_flash_cache_file = /dev/raw/sda, /dev/raw/sdb, /dev/raw/sdc
db_flash_cache_size = 32G, 32G, 64G
```

See Also:

"DB_FLASH_CACHE_FILE"

2.88 DB_FLASHBACK_LOG_DEST

`DB_FLASHBACK_LOG_DEST` specifies the location for flashback database log storage.

Property	Description
Parameter type	String
Syntax	`DB_FLASHBACK_LOG_DEST = directory | disk group`
Default value	There is no default value.
Modifiable	`ALTER SYSTEM ... SID='*'` See "Modifying DB_FLASHBACK_LOG_DEST with ALTER SYSTEM"
Modifiable in a PDB	No
Basic	No
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

This parameter allows you to specify a location for flashback database logs that is separate from the fast recovery area used by backups. For example, you could place flashback database logs in high-performance storage.

Before assigning a value to this parameter, you must set the DB_FLASHBACK_LOG_DEST_SIZE parameter to a nonzero value.

Modifying DB_FLASHBACK_LOG_DEST with ALTER SYSTEM

When modifying the DB_FLASHBACK_LOG_DEST parameter with the ALTER SYSTEM statement, you must disable and reenable flashback logging. For example:

```
SQL> alter database flashback off;

Database altered.


SQL> alter system set db_flashback_log_dest='/u01/oracle/dbs/ofba2';

System altered.


SQL> alter database flashback on;

Database altered.
```

Note:

This parameter is available starting with Oracle Database 23ai.

See Also:

- "DB_FLASHBACK_LOG_DEST_SIZE"
- "V$FLASHBACK_LOG_DEST"
- *Oracle Database Backup and Recovery User's Guide* for more information about this parameter

2.89 DB_FLASHBACK_LOG_DEST_SIZE

DB_FLASHBACK_LOG_DEST_SIZE specifies the hard limit (in bytes) on the total space to be used by flashback database log files stored in DB_FLASHBACK_LOG_DEST.

Property	Description
Parameter type	Big integer
Syntax	DB_FLASHBACK_LOG_DEST_SIZE = *integer* [K | M | G]
Default value	0
Modifiable	ALTER SYSTEM ... SID='*'
Modifiable in a PDB	No
Range of values	0 to operating system dependent

Property	Description
Basic	No
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DB_FLASHBACK_LOG_DEST"
> - "V$FLASHBACK_LOG_DEST"
> - *Oracle Database Backup and Recovery User's Guide* for more information about this parameter

2.90 DB_FLASHBACK_RETENTION_TARGET

`DB_FLASHBACK_RETENTION_TARGET` specifies the upper limit (in minutes) on how far back in time the database may be flashed back.

Property	Description
Parameter type	Integer
Default value	`1440` (minutes)
Modifiable	`ALTER SYSTEM ... SID='*'`
Modifiable in a PDB	No
Range of values	`0` to $2^{31} - 1$
Basic	No

How far back one can flashback a database depends on how much flashback data Oracle has kept in the fast recovery area.

> **See Also:**
>
> *Oracle Data Guard Broker* for enabling Flashback Database on Oracle Data Guard primary and target standby databases

2.91 DB_INDEX_COMPRESSION_INHERITANCE

DB_INDEX_COMPRESSION_INHERITANCE dictates how index creation inherits compression attributes.

Property	Description
Parameter type	String
Syntax	DB_INDEX_COMPRESSION_INHERITANCE = { TABLESPACE | TABLE | ALL | NONE }
Default value	NONE
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

Values:

- TABLESPACE

  Index inheritance is based on tablespace attributes.

- TABLE

  Index inheritance is based on table attributes.

- ALL

  Index inheritance is based on table settings. However, if the table does not have default compression attributes, then index inheritance is based on tablespace attributes.

- NONE

  There is no index inheritance from the table or tablespace.

If the CREATE INDEX statement specifies compression attributes, then the value of DB_INDEX_COMPRESSION_INHERITANCE is ignored, and there is no inheritance from the table or tablespace. When there is table inheritance or tablespace inheritance (and the tablespace does not have an explicit index compression clause), then the following matrix is used:

Table/Tablespace Level Compression	Inherited Compression for Index
OLTP	ADVANCED LOW
QUERY LOW, QUERY HIGH	ADVANCED HIGH
ARCHIVE LOW, ARCHIVE HIGH	ADVANCED HIGH

> **Note:**
>
> The value of DB_INDEX_COMPRESSION_INHERITANCE is ignored when creating an index owned by SYS. Such indexes do not inherit index compression attributes from tables or tablespaces. If you want to compress an index owned by SYS, you must explicitly specify the index compression attributes in the CREATE INDEX or ALTER INDEX statement.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about index compression

2.92 DB_KEEP_CACHE_SIZE

DB_KEEP_CACHE_SIZE specifies the size of the KEEP buffer pool.

Property	Description
Parameter type	Big integer
Syntax	DB_KEEP_CACHE_SIZE = *integer* [K | M | G]
Default value	0 (DB_KEEP_CACHE_SIZE is not configured by default)
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	Minimum: 0 (values greater than zero are automatically modified to be either the granule size * number of processor groups, or 4 MB * number of CPUs, whichever is greater) Maximum: operating system-dependent
Basic	No

The size of the buffers in the KEEP buffer pool is the primary block size (the block size defined by the DB_BLOCK_SIZE initialization parameter).

> **See Also:**
>
> - "DB_RECYCLE_CACHE_SIZE"
> - *Oracle Database Performance Tuning Guide* for information on setting these parameters and on using multiple buffer pools

2.93 DB_LOST_WRITE_PROTECT

DB_LOST_WRITE_PROTECT enables or disables lost write detection.

Property	Description
Parameter type	String
Syntax	`DB_LOST_WRITE_PROTECT = { AUTO | TYPICAL | FULL | NONE }`
Default value	`AUTO`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No
Oracle RAC	In Oracle RAC instances, this parameter value is system-wide.

A data block lost write occurs when an I/O subsystem acknowledges the completion of the block write, while in fact the write did not occur in the persistent storage.

Values:

- `AUTO`

  When this parameter is set to `AUTO` on a primary database, the instance automatically decides whether it logs buffer cache reads in the redo log or not, depending on the status of the standby databases. Specifically, the primary database only logs buffer cache reads if physical standby databases with real time redo apply exist.

  When this parameter is set to `AUTO` on a standby database, the instance will automatically decide whether it incurs additional performance overhead to perform lost write detection or not, depending on whether apply is keeping up. If apply lag is beyond the reasonable threshold, the standby database will skip lost write protection temporarily until redo apply catches up with primary again, to ensure the lowest Data Guard role transition timings.

  The reasonable threshold is determined as follows:

  – If Fast Start Failover (FSFO) is configured through Data Guard Broker, based on apply lag threshold, then the threshold is the lesser of 60 seconds and two-thirds of the FSFO apply lag threshold.

  – Otherwise, the threshold is 60 seconds.

- `TYPICAL`

  When this parameter is set to `TYPICAL` on a primary database, the instance logs buffer cache reads for read/write tablespaces in the redo log, which is necessary for detection of lost writes.

  When this parameter is set to `TYPICAL` on a standby database, or on a primary database during media recovery, the instance performs lost write detection, regardless of higher redo apply lags that may impact Data Guard role transition timings.

- `FULL`

  When this parameter is set to `FULL` on a primary database, the instance logs reads for read-only tablespaces and read/write tablespaces.

  When this parameter is set to `FULL` on a standby database, or on a primary database during media recovery, the instance performs lost write detection.

- `NONE`

  When this parameter is set to `NONE` on either a primary database or a standby database, no lost write detection functionality is enabled.

2.94 DB_NAME

DB_NAME specifies a database identifier of up to 8 characters.

Property	Description
Parameter type	String
Syntax	DB_NAME = *database_name*
Default value	There is no default value.
Modifiable	No
Modifiable in a PDB	No
Basic	Yes
Oracle RAC	You must set this parameter for every instance. Multiple instances must have the same value.

This parameter must be specified and must correspond to the name specified in the CREATE DATABASE statement.

If you have multiple databases, the value of this parameter should match the Oracle instance identifier of each one to avoid confusion with other databases running on the system. The value of DB_NAME must be the same in both the standby and production initialization parameter files.

The database name specified in either the STARTUP command or the ALTER DATABASE ... MOUNT statement for each instance of the cluster database must correspond to the DB_NAME initialization parameter setting.

The following characters are valid in a database name: alphanumeric characters, underscore (_), number sign (#), and dollar sign ($). No other characters are valid. The database name must start with an alphabetic character. Oracle removes double quotation marks before processing the database name. Therefore you cannot use double quotation marks to embed other characters in the name. The database name is case insensitive.

> **See Also:**
>
> *Oracle Database Administrator's Guide* and *Oracle Real Application Clusters Administration and Deployment Guide* for more information on setting this parameter

2.95 DB_PERFORMANCE_PROFILE

DB_PERFORMANCE_PROFILE specifies the performance profile for a database or a pluggable database (PDB).

Property	Description
Parameter type	String
Syntax	`DB_PERFORMANCE_PROFILE = string`
Default value	There is no default value.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	The same value should be set on all instances.

A performance profile supports easier management for hundreds of databases or PDBs.

On Oracle Exadata, the performance profile for the regular database or CDB is pushed down to the Exadata storage cells. The performance profile is used for the management of Exadata I/O Resource Manager.

A CDB resource plan can specify different resource controls for a performance profile using the `DBMS_RESOURCE_MANAGER.CREATE_CDB_PROFILE_DIRECTIVE` procedure. A PDB with a matching performance profile will use the specified controls.

The value of `DB_PERFORMANCE_PROFILE` can be up to 30 characters and is not case sensitive.

> **See Also:**
>
> *Oracle Database PL/SQL Packages and Types Reference* for information about the `DBMS_RESOURCE_MANAGER.CREATE_CDB_PROFILE_DIRECTIVE` procedure.

2.96 DB_RECOVERY_AUTO_REKEY

Use `DB_RECOVERY_AUTO_REKEY` to enable or disable automatic tablespace rekey recovery on Oracle Data Guard standby instances.

Property	Description
Parameter type	String
Syntax	`DB_RECOVERY_AUTO_REKEY = { ON | OFF }`
Default value	`ON`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No
Oracle RAC	Multiple instances should use the same value.

This parameter is effective when Oracle Data Guard standby recovery encounters a redo that indicates that the primary database performed a tablespace rekey. If the value of this parameter is `ON`, then standby recovery automatically performs the corresponding tablespace rekey. If the value of this parameter is `OFF`, then standby recovery does not perform a tablespace rekey.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.97 DB_RECOVERY_FILE_DEST

`DB_RECOVERY_FILE_DEST` specifies the default location for the fast recovery area.

Property	Description
Parameter type	String
Syntax	`DB_RECOVERY_FILE_DEST = directory | disk group`
Default value	There is no default value.
Modifiable	`ALTER SYSTEM ... SID='*'`
Modifiable in a PDB	No
Basic	Yes
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

The fast recovery area contains multiplexed copies of current control files and online redo logs, as well as archived redo logs, flashback logs, and RMAN backups.

Specifying this parameter without also specifying the `DB_RECOVERY_FILE_DEST_SIZE` initialization parameter is not allowed.

> **See Also:**
>
> - *Oracle Database Backup and Recovery User's Guide* for information on setting up and configuring the fast recovery area
> - "DB_RECOVERY_FILE_DEST_SIZE"

2.98 DB_RECOVERY_FILE_DEST_SIZE

`DB_RECOVERY_FILE_DEST_SIZE` specifies (in bytes) the hard limit on the total space to be used by target database recovery files created in the fast recovery area.

Property	Description
Parameter type	Big integer
Syntax	`DB_RECOVERY_FILE_DEST_SIZE = integer [K | M | G]`
Default value	`0`
Modifiable	`ALTER SYSTEM ... SID='*'`
Modifiable in a PDB	No
Basic	Yes

Property	Description
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

Note that neither block 0 nor the OS block header of each Oracle file is included in this size. Allow an extra 10% for this data when computing the actual disk usage required for the fast recovery area.

See Also:

- *Oracle Database Backup and Recovery User's Guide* for information on setting up and configuring the fast recovery area
- "DB_RECOVERY_FILE_DEST"

2.99 DB_RECYCLE_CACHE_SIZE

`DB_RECYCLE_CACHE_SIZE` specifies the size of the `RECYCLE` buffer pool.

Property	Description
Parameter type	Big integer
Syntax	`DB_RECYCLE_CACHE_SIZE = integer [K | M | G]`
Default value	`0` (`DB_RECYCLE_CACHE_SIZE` is not configured by default)
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	Minimum: `0` (values greater than zero are automatically modified to be either the granule size * number of processor groups, or 4 MB * number of CPUs, whichever is greater) Maximum: operating system-dependent
Basic	No

The size of the buffers in the `RECYCLE` pool is the primary block size (the block size defined by the `DB_BLOCK_SIZE` initialization parameter).

See Also:

- "DB_KEEP_CACHE_SIZE"
- *Oracle Database Performance Tuning Guide* for information on setting these parameters and on using multiple buffer pools

2.100 DB_SECUREFILE

DB_SECUREFILE specifies whether to treat LOB files as SecureFiles.

Property	Description
Parameter type	String
Syntax	DB_SECUREFILE = { NEVER | PERMITTED | PREFERRED | ALWAYS | IGNORE }
Default value	PERMITTED if the COMPATIBLE initialization parameter is set to 11.2.0.1, 11.2.0.2, or 11.2.0.3, or PREFERRED if the COMPATIBLE initialization parameter is set to 12.0.0.0 or higher
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No

Values

- NEVER

  Any LOBs that are specified as SecureFiles are created as BasicFiles LOBs. All SecureFiles-specific storage options and features (for example, compress, encrypt, deduplicate) will cause an exception. The BasicFiles LOB defaults will be used for storage options not specified.

- PERMITTED

  LOBs are allowed to be created as SecureFiles.

- PREFERRED

  All LOBs are created as SecureFiles unless BASICFILE is explicitly specified in the LOB storage clause or the tablespace is a Manual Segment Space Management tablespace. When PREFERRED is set, cases where BASICFILE would otherwise be inherited from the partition or column level LOB storage are ignored; the LOBs will be created as SecureFiles instead.

- ALWAYS

  Attempts to create all LOBs as SecureFiles LOBs but creates any LOBs not in an Automatic Segment Space Managed (ASSM) tablespace as BasicFiles LOBs, unless SECUREFILE is explicitly specified. Any BasicFiles LOB storage options that are specified will be ignored and the SecureFiles LOB defaults will be used for all storage options not specified.

- IGNORE

  The SECUREFILE keyword and all SecureFiles options are ignored.

If the COMPATIBLE initialization parameter is not set to 11.1.0 or higher, then LOBs are not treated as SecureFiles.

If there is a LOB column with two partitions (one that has a tablespace for which ASSM is enabled and one that has a tablespace for which ASSM is not enabled), then

LOBs in the partition with the ASSM-enabled tablespace will be treated as SecureFiles and LOBs in the other partition will be treated as BasicFiles.

If an application is not certified with SecureFiles, the value of the `DB_SECUREFILE` initialization parameter can be set to `PERMITTED` to get the default behavior of Oracle Database 11*g*.

> **See Also:**
>
> *Oracle Database SecureFiles and Large Objects Developer's Guide* for an example of setting this parameter using the `ALTER SYSTEM` statement

2.101 DB_ULTRA_SAFE

`DB_ULTRA_SAFE` sets the default values for other parameters that control protection levels.

Property	Description
Parameter type	String
Syntax	`DB_ULTRA_SAFE = { OFF | DATA_ONLY | DATA_AND_INDEX }`
Default value	`OFF`
Modifiable	No
Modifiable in a PDB	No
Basic	No

Values

- `OFF`

  When any of `DB_BLOCK_CHECKING`, `DB_BLOCK_CHECKSUM`, or `DB_LOST_WRITE_PROTECT` are explicitly set, no changes are made.

- `DATA_ONLY`
  - `DB_BLOCK_CHECKING` will be set to `MEDIUM`.
  - `DB_LOST_WRITE_PROTECT` will be set to `TYPICAL`.
  - `DB_BLOCK_CHECKSUM` will be set to `FULL`.
- `DATA_AND_INDEX`
  - `DB_BLOCK_CHECKING` will be set to `FULL`.
  - `DB_LOST_WRITE_PROTECT` will be set to `TYPICAL`.
  - `DB_BLOCK_CHECKSUM` will be set to `FULL`.

> **See Also:**
>
> - "DB_BLOCK_CHECKING"
> - "DB_BLOCK_CHECKSUM"
> - "DB_LOST_WRITE_PROTECT"

2.102 DB_UNIQUE_NAME

`DB_UNIQUE_NAME` specifies a globally unique name for the database.

Property	Description
Parameter type	String
Syntax	`DB_UNIQUE_NAME = database_unique_name`
Default value	Database instances: the value of `DB_NAME` Oracle Automatic Storage Management instances: `+ASM`
Modifiable	No
Modifiable in a PDB	No
Basic	Yes
Oracle RAC	Multiple instances must have the same value.

Databases with the same `DB_NAME` within the same `DB_DOMAIN` (for example, copies of a database created for reporting or a physical standby) must have a unique `DB_UNIQUE_NAME`. Every database's `DB_UNIQUE_NAME` must be unique within the enterprise.

The value of `DB_UNIQUE_NAME` can be up to 30 characters and is case insensitive. The following characters are valid in a database name: alphanumeric characters, underscore (_), number sign (#), and dollar sign ($).

> **Note:**
>
> `DB_UNIQUE_NAME` is used by several components within an Oracle instance to default file names or file paths, such as the default for the `DG_BROKER_CONFIG_FILE`*n* initialization parameter. In these cases, on UNIX platforms, the dollar sign ($) character will be removed from the path or file name, because the character is used by Oracle to define the start of an environment variable substitution within a path or file name.

> **Note:**
>
> As part of their operations, some database tools or utilities create a string that uniquely identifies a database. The string may include the DB_UNIQUE_NAME for a database, and other identifying information for the database, such as the database SID. Oracle Database restricts some identifiers to 30 characters, so using a short DB_UNIQUE_NAME can help prevent ORA-00972 "identifier is too long" messages from database tools and utilities that create a string that includes the DB_UNIQUE_NAME.

> **See Also:**
>
> *Oracle Data Guard Concepts and Administration* and *Oracle Database Administrator's Guide* for more information on setting this parameter

2.103 DB_UNRECOVERABLE_SCN_TRACKING

DB_UNRECOVERABLE_SCN_TRACKING enables or disables the tracking of unrecoverable (NOLOGGING) direct-path INSERT and direct-path load operations.

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	true | false
Basic	No
Oracle RAC	Multiple instances must have the same value

When the value is set to true, updates are made to the controlfile that maintains the V$DATAFILE.UNRECOVERABLE_CHANGE# and V$DATAFILE.UNRECOVERABLE_TIME columns. When the value is set to false, updates are not made to the controlfile. Setting this parameter to false may improve performance of direct-path NOLOGGING operations.

2.104 DB_WRITER_PROCESSES

DB_WRITER_PROCESSES specifies the initial number of Database Writer Processes for an instance. This parameter is useful for systems that modify data heavily.

Property	Description
Parameter type	Integer

Property	Description
Default value	`1` or `CPU_COUNT` / 8, whichever is greater. If the number of processor groups is less than 100 but greater than the number of Database Writer Processes, then the number of Database Writer Processes is adjusted to be a multiple of the number of processor groups. If the number of Database Writer Processes is greater than or equal to the number of processor groups, then there is no adjustment. For Oracle Solaris on SPARC systems, the default value of this parameter is calculated using an internal algorithm.
Modifiable	No
Modifiable in a PDB	No
Range of values	1 to 100
Basic	No

There can be 1 to 100 Database Writer Processes. The names of the first 36 Database Writer Processes are DBW0-DBW9 and DBWa-DBWz. The names of the 37th through 100th Database Writer Processes are BW36-BW99.

See Also:

- Background Processes for additional information about the Database Writer Process
- *Oracle Database Concepts* for information on when the Database Writer Process writes dirty buffers to disk

2.105 DBFIPS_140

`DBFIPS_140` enables Transparent Data Encryption (TDE) and `DBMS_CRYPTO` PL/SQL package program units to run in a mode compliant to the Federal Information Processing Standard (subsequently known as "FIPS mode").

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true	false`
Basic	No
Oracle RAC	All instances must use the same value.

Set this parameter to `true` to use TDE and `DBMS_CRYPTO` in FIPS mode. This means that only FIPS-compliant algorithms may be used. By default, this parameter is set to `false`. When this parameter is set to `false`, all algorithms (FIPS-compliant or not) may be used.

> **See Also:**
>
> - *Oracle Database Security Guide* for information about configuring Oracle Database FIPS 140 settings
> - *Oracle Database Security Guide* for a table that describes the effect of setting the value of `DBFIPS_140` to `true` or `false` on different platforms

2.106 DBNEST_ENABLE

`DBNEST_ENABLE` allows you to enable or disable dbNest.

> **Note:**
>
> This parameter is applicable only on Linux systems.

Property	Description
Parameter type	String
Syntax	`DBNEST_ENABLE = { NONE | CDB_RESOURCE_PDB_ALL }`
Default value	`NONE`
Modifiable	No
Modifiable in a PDB	No
Basic	No
Oracle RAC	All instances should use the same value.

DbNest provides operating system resource isolation and management, file system isolation, and secure computing for PDBs. The infrastructure is implemented as a Linux-specific package that provides hierarchical containers, called nests. A CDB resides within a single parent nest, while PDBs reside within the individual child nests created within the parent. The isolation and resource management properties of a nest are separate. A full nest includes both isolation and resource management. Alternatively, you can configure a partial nest that includes only resource management.

You can set the following values for this parameter:

- `NONE`: Disables dbNest. This is the default value.
- `CDB_RESOURCE_PDB_ALL`: Enables a resource management-only nest for the CDB and a full nest for each PDB.

> **See Also:**
>
> *Oracle Multitenant Administrator's Guide* for information on securing and isolating resources using dbNest

2.107 DBNEST_PDB_FS_CONF

`DBNEST_PDB_FS_CONF` specifies the dbNest file system configuration file for a PDB.

> **Note:**
>
> This parameter is applicable only on Linux systems.

Property	Description
Parameter type	String
Syntax	`DBNEST_PDB_FS_CONF = '`*`pathname`*`'`
Default value	None
Modifiable	No
Modifiable in a PDB	No
Basic	No
Oracle RAC	Multiple instances can have different values.

A dbNest file system configuration file specifies directories to be mounted inside the nest for a PDB. These directories are mounted in addition to the default directories.

For *`pathname`*, specify the full operating system path for the file.

If you do not set this parameter, then only the default directories are mounted.

> **See Also:**
>
> *Oracle Multitenant Administrator's Guide* for information on dbNest file system configuration files

2.108 DBWR_IO_SLAVES

`DBWR_IO_SLAVES` specifies the number of I/O server processes used by the `DBW0` process.

Property	Description
Parameter type	Integer
Default value	`0`
Modifiable	No
Modifiable in a PDB	No
Range of values	0 to operating system-dependent
Basic	No

DBWR_IO_SLAVES is relevant only on systems with only one database writer process (DBW0). The DBW0 process and its server processes always write to disk. By default, the value is 0 and I/O server processes are not used.

If you set DBWR_IO_SLAVES to a nonzero value, the number of I/O server processes used by the ARCH and LGWR processes is set to 4. However, the number of I/O server processes used by Recovery Manager is set to 4 only if asynchronous I/O is disabled (either your platform does not support asynchronous I/O or disk_asynch_io is set to false).

Typically, I/O server processes are used to simulate asynchronous I/O on platforms that do not support asynchronous I/O or that implement it inefficiently. However, you can use I/O server processes even when asynchronous I/O is being used. In that case the I/O server processes will use asynchronous I/O.

I/O server processes are also useful in database environments with very large I/O throughput, even if asynchronous I/O is enabled.

See Also:

- "BACKUP_TAPE_IO_SLAVES"
- *Oracle Database Performance Tuning Guide* for more information about this parameter

2.109 DDL_LOCK_TIMEOUT

DDL_LOCK_TIMEOUT specifies a time limit for how long DDL statements will wait in a DML lock queue.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	0 to 1,000,000 (in seconds)
Basic	No

A value of zero indicates a status of NOWAIT. The maximum value of 1,000,000 seconds will result in the DDL statement waiting forever to acquire a DML lock.

If a lock is not acquired before the timeout period expires, then an error is returned.

See Also:

- *Oracle Database Administrator's Guide* for more information about the `DDL_LOCK_TIMEOUT` parameter
- *Oracle Database Development Guide* for information about nonblocking and blocking DDL

2.110 DEFAULT_SHARING

`DEFAULT_SHARING` sets the value of the sharing clause in statements creating objects in an application root.

Property	Description
Parameter type	String
Syntax	`DEFAULT_SHARING = { NONE | METADATA | DATA | EXTENDED DATA }`
Default value	For types of objects that support sharing, `METADATA` is the default. For types of objects that do not support sharing, `NONE` is the default.
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	All instances must have the same value

Specifying `SHARING=` in the create DDL overrides the value of the `DEFAULT_SHARING` parameter.

Example

Issuing the following `ALTER SYSTEM` statement in an application root sets the default value of the sharing clause to `NONE` in the server parameter file for the application root:

```
ALTER SYSTEM SET DEFAULT_SHARING = NONE SCOPE = SPFILE;
```

2.111 DEFERRED_SEGMENT_CREATION

`DEFERRED_SEGMENT_CREATION` specifies the semantics of deferred segment creation.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true | false`
Basic	No

If set to `true`, then segments for tables and their dependent objects (LOBs, indexes) will not be created until the first row is inserted into the table.

Before creating a set of tables, if it is known that a significant number of them will not be populated, then consider setting this parameter to `true`. This saves disk space and minimizes install time.

2.112 DG_BROKER_CONFIG_FILE*n*

`DG_BROKER_CONFIG_FILE`*n* (where *n* = 1, 2) specifies the names for the Data Guard broker configuration files.

Property	Description
Parameter type	String
Syntax	`DG_BROKER_CONFIG_FILE[1 | 2] = filename`
Default value	Operating system-dependent
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	One filename
Basic	No

Every database that is part of a Data Guard broker configuration has two broker configuration files, which contain entries that describe the state and properties of the configuration (such as the sites and databases that are part of the configuration, the roles and properties of each of the databases, and the state of each of the elements of the configuration). Two files are provided to always maintain the last known good state of the configuration.

If `DG_BROKER_CONFIG_FILE`*n* is not explicitly defined, then it is set to an operating system-specific default value at instance startup. This parameter can be altered only when the Data Guard broker is not running. See "DG_BROKER_START" for information on how to stop and start the broker.

> **See Also:**
>
> *Oracle Data Guard Broker* for more information about setting this parameter

2.113 DG_BROKER_START

`DG_BROKER_START` enables Oracle to determine whether the Oracle Data Guard broker should be started.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SYSTEM...SID='*'`

Property	Description
Modifiable in a PDB	No
Range of values	`true	false`
Basic	No

The Oracle Data Guard broker consists of background processes, foreground processes, and the system global area (SGA). The background and foreground processes exist as long as the instance exists, whenever this parameter is set to `true`.

If the database is never going to be configured in an Oracle Data Guard broker configuration, then you can leave this parameter unspecified and accept the default value of `false`. If the database is part of an Oracle Data Guard broker configuration, then you can simplify automatic startup of the broker by setting this parameter to `true` in the initialization parameter file.

> **See Also:**
>
> *Oracle Data Guard Broker* for examples of using this parameter to start the Oracle Data Guard broker

2.114 DIAGNOSTIC_DEST

As of Oracle Database 11g Release 1 (11.1), the diagnostics for each database instance are located in a dedicated directory that is specified by the `DIAGNOSTIC_DEST` initialization parameter.

Property	Description
Parameter type	String
Syntax	`DIAGNOSTIC_DEST = { pathname	directory }`
Default value	Derived from the value of the `$ORACLE_BASE` environment variable. If `$ORACLE_BASE` is not set, then derived from `ORACLE_BASE` as set by the Oracle Universal Installer. If `ORACLE_BASE` is not set, then `$ORACLE_HOME/rdbms/log` is used.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No
Oracle RAC	This parameter can be set on each instance. Oracle recommends that each instance in a cluster specify a `DIAGNOSTIC_DEST` directory location that is located on shared disk and that the same value for `DIAGNOSTIC_DEST` be specified for each instance.

The structure of the directory specified by `DIAGNOSTIC_DEST` is as follows:

<diagnostic_dest>/diag/rdbms/*<dbname>*/*<instname>*

This location is known as the Automatic Diagnostic Repository (ADR) Home. For example, if the database name is `proddb` and the instance name is `proddb1`, the ADR home directory would be `<diagnostic_dest>/diag/rdbms/proddb/proddb1`.

The following files are located under the ADR home directory:

- Trace files - located in subdirectory `<adr-home>/trace`
- Alert logs - located in subdirectory `<adr-home>/alert`. In addition, the `alert.log` file is now in XML format, which conforms to the Oracle ARB logging standard.
- Core files - located in the subdirectory `<adr-home>/cdump`
- Incident files - the occurrence of each serious error (for example, ORA-600, ORA-1578, ORA-7445) causes an incident to be created. Each incident is assigned an ID and dumping for each incident (error stack, call stack, block dumps, and so on) is stored in its own file, separated from process trace files. Incident dump files are located in `<adr-home>/incident/<incdir#>`. You can find the incident dump file location inside the process trace file.

See Also:

Oracle Automatic Storage Management Administrator's Guide for an example of the diagnostic directory for an Oracle ASM instance

2.115 DIAGNOSTICS_CONTROL

`DIAGNOSTICS_CONTROL` enables you to control and monitor the users who perform potentially unsafe database diagnostic operations.

Property	Description
Parameter type	String
Syntax	`DIAGNOSTICS_CONTROL = { ERROR | WARNING | IGNORE }`
Default value	`IGNORE`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No
Oracle RAC	The same value must be used on all instances.

When diagnosing Oracle database issues, an Oracle Support Service staff member might instruct you to perform diagnostic operations. Some diagnostic operations are harmless. However, others could have adverse effects if not performed properly with the guidance of an Oracle Support Service staff member. In order to control and monitor who performs such diagnostic operations, Oracle Database 20 introduces the following security controls:

- Potentially unsafe diagnostic operations are internally identified in the database. These operations include setting certain debug events and debug actions with the `ALTER SESSION` or `ALTER SYSTEM` statement. For example:

```
ALTER SESSION SET EVENTS '1357 trace name context forever, level 2';
ALTER SYSTEM SET EVENTS 'trace[vos]';
```

- A user can be authorized to perform potentially unsafe diagnostic operations, either by being granted the `ENABLE DIAGNOSTICS` system privilege, or by being granted the `DBA` role, or by authenticating as `SYSDBA`.
- The `DIAGNOSTICS_CONTROL` initialization parameter enables you to specify how the database responds when an *unauthorized* user attempts to perform these diagnostic operations. The possible values are:
  - `ERROR`: When an unauthorized user attempts to perform a potentially unsafe diagnostic operation, the attempt fails with error `ORA-01031: insufficient privileges`.
  - `WARNING`: When an unauthorized user attempts to perform a potentially unsafe diagnostic operation, the attempt succeeds, but a warning is written to the alert log.
  - `IGNORE`: When an unauthorized user attempts to perform a potentially unsafe diagnostic operation, the attempt succeeds and no error messages or warnings occur. This is the default.

> **Note:**
>
> When altering the `DIAGNOSTICS_CONTROL` initialization parameter, be aware of the following guidelines:
>
> - To modify this parameter with the `ALTER SYSTEM` command, you must be authenticated `AS SYSDBA`.
> - In Oracle RAC environments, it is currently not possible to modify this parameter on remote instances by specifying the `SID` clause in the `ALTER SYSTEM SET` statement.

2.116 DISK_ASYNCH_IO

`DISK_ASYNCH_IO` controls whether I/O to datafiles, control files, and logfiles is asynchronous (that is, whether parallel server processes can overlap I/O requests with CPU processing during table scans).

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	No
Modifiable in a PDB	No

Property	Description
Range of values	`true | false`
Basic	No

If your platform supports asynchronous I/O to disk, Oracle recommends that you leave this parameter set to its default value. However, if the asynchronous I/O implementation is not stable, you can set this parameter to `false` to disable asynchronous I/O. If your platform does not support asynchronous I/O to disk, this parameter has no effect.

If you set `DISK_ASYNCH_IO` to `false`, then you can increase `DB_WRITER_PROCESSES` or use `DBWR_IO_SLAVES` to simulate asynchronous I/O.

See Also:

- "DB_WRITER_PROCESSES"
- "DBWR_IO_SLAVES"
- *Oracle Database Performance Tuning Guide* for more information

2.117 DISPATCHERS

`DISPATCHERS` configures dispatcher processes in the shared server architecture.

Property	Description
Parameter type	String
Syntax	`DISPATCHERS = '`*`dispatch_clause`*`'`

Syntax	**`dispatch_clause::=`**
	`(PROTOCOL =` *`protocol`*`) |`
	`(ADDRESS =` *`address`*`) |`
	`(DESCRIPTION =` *`description`* `)`
	`[options_clause]`

Syntax	**`options_clause::=`**
	`(DISPATCHERS =` *`integer`* `|`
	`SESSIONS =` *`integer`* `|`
	`CONNECTIONS =` *`integer`* `|`
	`MULTIPLEX = {1 | ON | YES | TRUE |`
	`0 | OFF | NO | FALSE | BOTH | IN | OUT} |`
	`LISTENER =` *`tnsname`* `|`
	`SERVICE =` *`service`* `|`
	`INDEX =` *`integer`*`)`

Default value	If `SHARED_SERVERS` is greater than `0`, then `DISPATCHERS` defaults to `'(PROTOCOL=tcp)'`, causing 1 TCP/IP dispatcher to be created.

Property	Description
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Basic	No

The parsing software supports a name-value syntax to enable the specification of attributes in a position-independent, case-insensitive manner. For example:

```
DISPATCHERS = '(PROTOCOL=TCP)(DISPATCHERS=3)'
```

Attributes may be specified using the full attribute name or any substring beginning with the first 3 characters. For example, SESSIONS can be specified as SES, SESS, SESSI, and so on.

Specify only one of the following attributes: PROTOCOL, ADDRESS, or DESCRIPTION. If you specify either ADDRESS or DESCRIPTION, then you can specify additional network attributes. Doing so supports multi-homed hosts.

dispatch_clause

- PROTOCOL

  The network protocol for which the dispatcher generates a listening endpoint.

- ADDRESS

  The network protocol address of the endpoint on which the dispatchers listen.

- DESCRIPTION

  The network description of the endpoint on which the dispatchers listen, including the protocol address.

options_clause

- DISPATCHERS

  The initial number of dispatchers to start. The default is 1.

- SESSIONS

  The maximum number of network sessions to allow for each dispatcher. The default is operating system-specific. Most operating systems have a default of 16 KB.

- CONNECTIONS

  The maximum number of network connections to allow for each dispatcher. The default is operating system-specific.

- MULTIPLEX

  Enables the Oracle Connection Manager session multiplexing feature.

  – The values 1, ON, YES, TRUE, and BOTH indicate that Network Session Multiplex is enabled for both incoming and outgoing network connections.

  – The value IN indicates that Network Session Multiplex is enabled for incoming network connections.

  - The value `OUT` indicates that Network Session Multiplexing is enabled for outgoing network connections.
  - The values `0`, `NO`, `OFF`, and `FALSE` indicate that Network Session Multiplexing is disabled for both incoming and outgoing network connections. This is the default.

- `LISTENER`

  Specifies the network name of an address or address list of the Oracle Net listeners with which the dispatchers will register.

  The `LISTENER` attribute facilitates administration of multi-homed hosts. This attribute specifies the appropriate listeners with which the dispatchers will register. The `LISTENER` attribute takes precedence over the `LOCAL_LISTENER` and `REMOTE_LISTENER` parameters. See "LOCAL_LISTENER" and "REMOTE_LISTENER".

- `SERVICE`

  Specifies one or more names by which clients can connect to the dispatchers. The `SERVICE` attribute takes precedence over any settings configured by using the `SRVCTL` command-line utility, the `GDSCTL` command-line utility, or the `DBMS_SERVICE` PL/SQL package.

- `INDEX`

  Use this attribute in an `ALTER SYSTEM SET DISPATCHERS` statement to indicate which dispatcher configuration you want to modify. (If you specify `INDEX` in the initialization parameter file, the Oracle Database ignores it.) In an `ALTER SYSTEM` statement, `INDEX` specifies the order in which the parameter's values were initialized. The value ranges from `0` (for the first dispatcher configuration) to one less than the total number of dispatcher configurations you define.

  For example, if you specify 3 dispatcher configurations in the initialization parameter file, you would modify the third dispatcher configuration by specifying `INDEX=2` in the `ALTER SYSTEM` statement. You could also add another dispatcher configuration in the `ALTER SYSTEM` statement by specifying `INDEX=3`.

  If `INDEX` is not specified in the `ALTER SYSTEM` statement, then the `PROTOCOL`, `ADDRESS`, or `DESCRIPTION` attributes must be specified, and if a dispatcher configuration matching this `PROTOCOL`, `ADDRESS`, or `DESCRIPTION` exists, then that configuration will be modified. Otherwise, a new configuration will be added.

See Also:

- "SHARED_SERVERS"
- *Oracle Database Net Services Administrator's Guide* and *Oracle Database Administrator's Guide* for more information on setting this parameter

2.118 DISTRIBUTED_LOCK_TIMEOUT

`DISTRIBUTED_LOCK_TIMEOUT` specifies the amount of time (in seconds) for distributed transactions to wait for locked resources.

Property	Description
Parameter type	Integer
Default value	60
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	1 to 2^{31} - 1
Basic	No

> **See Also:**
>
> *Oracle Database Concepts* for more information on data concurrency

2.119 DML_LOCKS

DML_LOCKS specifies the maximum number of DML locks—one for each table modified in a transaction.

Property	Description
Parameter type	Integer
Default value	Derived: 4 * TRANSACTIONS
Modifiable	No
Modifiable in a PDB	No
Range of values	20 to unlimited; a setting of 0 disables enqueues
Basic	No
Oracle RAC	You must set this parameter for every instance, and all instances must have positive values or all must be 0.

A **DML lock** is a lock obtained on a table that is undergoing a DML operation (insert, update, delete). The DML_LOCKS value should equal the grand total of locks on tables currently referenced by all users. For example, if three users are modifying data in one table, then three entries would be required. If three users are modifying data in two tables, then six entries would be required.

The default value assumes an average of four tables referenced for each transaction. For some systems, this value may not be enough.

Enqueues are shared memory structures that serialize access to database resources. If you set the value of DML_LOCKS to 0, enqueues are disabled and performance is slightly increased. However, you should be aware of the following restrictions when you set you DML_LOCKS to 0:

- You cannot use DROP TABLE, CREATE INDEX statements
- You cannot use explicit lock statements such as LOCK TABLE IN EXCLUSIVE MODE
- Enterprise Manager cannot run on any instances for which DML_LOCKS is set to 0

Oracle holds more locks during parallel DML than during serial execution. Therefore, if your database supports a lot of parallel DML, you may need to increase the value of this parameter.

See Also:

- *Oracle Database Concepts* for a discussion of lock and enqueue resources needed for parallel DML
- *Oracle Database Concepts* for more information on data concurrency

2.120 DNFS_BATCH_SIZE

`DNFS_BATCH_SIZE` controls the number of asynchronous I/O's that can be queued by an Oracle process when Direct NFS Client is enabled.

Property	Description
Parameter type	Integer
Default value	`4096`
Modifiable	No
Modifiable in a PDB	No
Range of values	0 - 4096
Basic	No

In environments where the NFS server cannot handle a large number of outstanding asynchronous I/O requests, use this parameter to limit the number of I/O's issued by an Oracle foreground process. The recommended setting for this parameter is to start at 128 and increase or decrease it based on NFS server performance.

See Also:

Oracle Database Performance Tuning Guide for additional information about the `DNFS_BATCH_SIZE` initialization parameter

2.121 DRCP_DEDICATED_OPT

Use `DRCP_DEDICATED_OPT` to enable or disable the use of dedicated optimization with Database Resident Connection Pooling (DRCP).

Dedicated optimization causes DRCP to behave like a dedicated server when the number of connections to the DRCP broker is less than the DRCP maximum size.

Property	Description
Parameter type	String

Property	Description
Syntax	`DRCP_DEDICATED_OPT = { YES | NO }`
Default value	`NO`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes, according to the following guidelines: • When the `ENABLE_PER_PDB_DRCP` initialization parameter is set to `true`, `DRCP_DEDICATED_OPT` can be modified only at the PDB level; it cannot be modified for the CDB root. • When the `ENABLE_PER_PDB_DRCP` initialization parameter is set to `false`, `DRCP_DEDICATED_OPT` can be modified only for the CDB root; it cannot be modified at the PDB level.
Basic	No
Oracle RAC	Different instances can use different values.

When the value of this parameter is set to `YES`, the use of dedicated optimization with DRCP is enabled. When it is set to `NO`, the use of dedicated optimization with DRCP is disabled.

See Also:

- *Oracle Database Administrator's Guide* for more information about setting this parameter
- "ENABLE_PER_PDB_DRCP"

2.122 DST_UPGRADE_INSERT_CONV

`DST_UPGRADE_INSERT_CONV` specifies whether internal operators will be allocated on top of `TIMESTAMP WITH TIME ZONE` (TSTZ) columns of tables which have not been upgraded during the upgrade window of daylight saving time patching for `TIMESTAMP WITH TIME ZONE` data.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true | false`
Basic	No

Values

- `true`

Internal operators will be allocated on top of TSTZ columns of tables which have not been upgraded. This is the default.

- `false`

  Internal operators will not be allocated on top of TSTZ columns of tables which have not been upgraded.

When DST_UPGRADE_INSERT_CONV is set to true during the upgrade window of the daylight saving time patching process:

- `SELECT` queries on tables with TSTZ data which have not been upgraded will use internal operators on top of TSTZ columns to present TSTZ data as if they were recorded using the new time zone translation rules.
- DML on tables with TSTZ data which have not been upgraded will use internal operators on top of TSTZ columns to ensure that the TSTZ data is recorded using the old time zone translation rules in order to be consistent with the existing TSTZ data in the same tables.

> **Note:**
>
> Oracle strongly recommends that this parameter is set to `true` throughout the upgrade window of the daylight saving time patching process. This parameter reduces the performance impact since indexes on TSTZ columns will be disabled whenever internal operators are allocated. If the parameter is set to `false`, then indexes will be used and this may affect performance of queries against TSTZ data during the DST upgrade window. Turning off this parameter during the upgrade window may corrupt data on disk when DMLs occur for tables with TSTZ data which have not yet been upgraded.

> **See Also:**
>
> *Oracle Database Globalization Support Guide* for more information about this parameter

2.123 ENABLE_AUTOMATIC_MAINTENANCE_PDB

`ENABLE_AUTOMATIC_MAINTENANCE_PDB` can be used to enable or disable the running of automated maintenance tasks for all the PDBs in a CDB or for individual PDBs in a CDB.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true | false`
Basic	No
Oracle RAC	The same value should be used for all instances.

> **Note:**
>
> The value of this parameter in CDB$ROOT (the root of a CDB) has no effect in the root. Automated maintenance tasks are always run in the root, regardless of the setting of this parameter.

By default, the value of `ENABLE_AUTOMATIC_MAINTENANCE_PDB` is `true` in CDB$ROOT (the root container in the CDB) and in the individual PDBs in a CDB. This means that by default, automated maintenance tasks are run for the CDB root and all the PDBs in the CDB.

When you change the value of `ENABLE_AUTOMATIC_MAINTENANCE_PDB` in the CDB root, the new value takes effect in the root and in all the PDBs in the CDB.

Therefore, if you change the value of `ENABLE_AUTOMATIC_MAINTENANCE_PDB` in the CDB root to `false`, the value of `ENABLE_AUTOMATIC_MAINTENANCE_PDB` is also changed to `false` in all of the PDBs in the CDB.

You can also change the value of `ENABLE_AUTOMATIC_MAINTENANCE_PDB` in any of the individual PDBs in a CDB, and the value that is set for each individual PDB will be honored. This enables you to enable or disable automated maintenance tasks for individual PDBs.

> **See Also:**
>
> - "AUTOTASK_MAX_ACTIVE_PDBS" for information about specifying the maximum number of PDBs that can schedule automated maintenance tasks at the same time
> - *Oracle Database Administrator's Guide* for more information about managing automated database maintenance tasks

2.124 ENABLE_DDL_LOGGING

`ENABLE_DDL_LOGGING` enables or disables the writing of a subset of data definition language (DDL) statements to a DDL log.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No

The DDL log is a file that has the same format and basic behavior as the alert log, but it only contains the DDL statements issued by the database. The DDL log is created only for the RDBMS component and only if the `ENABLE_DDL_LOGGING` initialization parameter is set to `true`. When this parameter is set to `false`, DDL statements are not included in the DDL log, but they are included in the alert log.

The DDL log contains one log record for each DDL statement issued by the database. The DDL log is included in IPS incident packages.

There are two DDL logs that contain the same information. One is an XML file, and the other is a text file. The DDL log is stored in the `log/ddl` subdirectory of the ADR home.

When `ENABLE_DDL_LOGGING` is set to `true`, the following DDL statements are written to the log:

- `ALTER/CREATE/DROP/TRUNCATE CLUSTER`
- `ALTER/CREATE/DROP FUNCTION`
- `GRANT`
- `ALTER/CREATE/DROP INDEX`
- `ALTER/CREATE/DROP OUTLINE`
- `ALTER/CREATE/DROP PACKAGE`
- `ALTER/CREATE/DROP PACKAGE BODY`
- `ALTER/CREATE/DROP PROCEDURE`
- `ALTER/CREATE/DROP PROFILE`
- `REVOKE`
- `ALTER/CREATE/DROP SEQUENCE`
- `CREATE/DROP SYNONYM`
- `ALTER/CREATE/DROP/RENAME/TRUNCATE TABLE`
- `ALTER/CREATE/DROP TRIGGER`
- `ALTER/CREATE/DROP TYPE`
- `ALTER/CREATE/DROP TYPE BODY`
- `DROP USER`
- `ALTER/CREATE/DROP VIEW`

> **Note:**
>
> The DDL statement written to the log may be truncated. You can use DDL triggers to view the entire DDL statement. See *Oracle Database PL/SQL Language Reference* for more information about DDL triggers.

> **See Also:**
>
> *Oracle Database Licensing Information User Manual* for licensing information for the `ENABLE_DDL_LOGGING` initialization parameter.

2.125 ENABLE_DNFS_DISPATCHER

`ENABLE_DNFS_DISPATCHER` enables dispatcher support for the Oracle Direct NFS client.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true	false`
Basic	No
Oracle RAC	All instances should use the same value.

When this parameter is set to `true` in the initialization parameter file, dispatcher processes will be spawned for the Oracle Direct NFS client.

The number of dispatcher processes spawned is calculated as one-eighth of the value of the `CPU_COUNT` parameter.

> **See Also:**
>
> "CPU_COUNT"

2.126 ENABLE_GOLDENGATE_REPLICATION

`ENABLE_GOLDENGATE_REPLICATION` controls services provided by the RDBMS for Oracle GoldenGate (both capture and apply services).

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	`true	false`
Basic	No
Oracle RAC	All instances must have the same setting

Set this parameter to `true` to enable RDBMS services used by Oracle GoldenGate.

This parameter primarily controls supplemental logging required to support logical replication of new data types and operations. The redo log file is designed to be applied physically to a database, therefore the default contents of the redo log file often do not contain sufficient information to allow logged changes to be converted into SQL statements. Supplemental logging adds extra information into the redo log files so that replication can convert logged changes into SQL statements without having to access the database for each change. Previously these extra changes were controlled by the supplemental logging DDL. Now the `ENABLE_GOLDENGATE_REPLICATION` parameter must also be set to enable the required supplemental logging for any new data types or operations.

All enhancements to supplemental logging required to support logical replication are also controlled by this parameter.

The RDBMS services controlled by this parameter also include (but are not limited to):

- Transparent Data Encryption (including Tablespace Encryption) utilities used by GoldenGate Extract
- Service to read redo logs used by GoldenGate Extract
- Service to suppress triggers used by GoldenGate Replicat
- Service to handle transient duplicate handling used by GoldenGate Replicat
- Service to bypass referential integrity checking used by GoldenGate Replicat
- Services required to run Oracle GoldenGate in Integrated Extract and Integrated Replicat

> **Note:**
>
> You must purchase a license in order to use Oracle GoldenGate. Refer to *Oracle GoldenGate Licensing Information* and ensure that you have obtained the appropriate licensing before setting this parameter to `true`.

2.127 ENABLE_IMC_WITH_MIRA

`ENABLE_IMC_WITH_MIRA` enables or disables the In-Memory Column Store and Oracle Data Guard Multi-Instance Redo Apply, at the same time, on an Active Data Guard standby database.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No
Oracle RAC	Different instances can use different values.

The value of this parameter is relevant only on the instance where MRP0 is spawned at the start of Redo Apply on a standby database.

2.128 ENABLE_PER_PDB_DRCP

ENABLE_PER_PDB_DRCP controls whether Database Resident Connection Pooling (DRCP) configures one connection pool for the entire CDB or one isolated connection pool for each PDB.

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Modifiable in a PDB	No
Range of values	true | false
Basic	No
Oracle RAC	Multiple instances must have the same value.

Possible values:

- true

  DRCP creates one isolated connection pool for each PDB. You can connect to a particular PDB and configure, manage, and monitor its connection pool according to the specific requirements for that PDB. For example, you can set values for the MIN_AUTH_SERVERS, MAX_AUTH_SERVERS, and DRCP_DEDICATED_OPT initialization parameters for a PDB, and you can use the DBMS_CONNECTION_POOL package to manage the connection pool for a PDB.

  When ENABLE_PER_PDB_DRCP is set to true, there is no connection pool for the entire CDB. The values of the MIN_AUTH_SERVERS, MAX_AUTH_SERVERS, and DRCP_DEDICATED_OPT initialization parameters have no meaning in the CDB root and you cannot alter them, nor can you use the DBMS_CONNECTION_POOL package while connected to the CDB root.

- false

  DRCP creates one connection pool for the entire CDB. This connection pool is shared by all PDBs. You can set the MIN_AUTH_SERVERS, MAX_AUTH_SERVERS, and DRCP_DEDICATED_OPT initialization parameters only in the CDB root, and you can use the DBMS_CONNECTION_POOL only while connected to the CDB root.

See Also:

- "MIN_AUTH_SERVERS"
- "MAX_AUTH_SERVERS"
- "DRCP_DEDICATED_OPT"
- *Oracle Database PL/SQL Packages and Types Reference* for more information on the `DBMS_CONNECTION_POOL` package

2.129 ENABLE_PLUGGABLE_DATABASE

`ENABLE_PLUGGABLE_DATABASE` is a bootstrap initialization parameter to create a CDB.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true	false`
Basic	No

This parameter enables a database in `NOMOUNT` startup mode to know that it is a CDB.

Note:

See *Oracle Multitenant Administrator's Guide* for more information about CDBs and PDBs.

2.130 ENABLED_PDBS_ON_STANDBY

`ENABLED_PDBS_ON_STANDBY` specifies which pluggable databases (PDBs) to replicate on an Oracle Data Guard standby database.

Property	Description
Parameter type	String
Syntax	`ENABLED_PDBS_ON_STANDBY = PDB-list`
Default value	`*` if no value is specified for this parameter in the `init.ora` file
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No

Property	Description
Oracle RAC	All instances should use the same value.

> **Note:**
>
> This parameter is meaningful only on standby databases. Its settings are ignored on a primary database.

PDB-list accepts a list of PDB names represented by glob patterns such as “PDB?” or “PDB*a”, “PDB2”. The glob pattern rules are like those of UNIX shells. The asterisk (*) and question mark (?) wildcard characters are supported. The ? wildcard character matches exactly one unknown character, and the * wildcard character matches any number of unknown characters. Also, the minus sign (-) character can be used as the first character in a PDB name to indicate that the PDB should be excluded on the standby database.

The following characters are valid in a PDB name: alphanumeric characters, underscore (_), number sign (#), and dollar sign ($). No other characters are valid. Oracle removes double quotation before processing the PDB name. Therefore you cannot use double quotation marks to embed other characters in the name. The PDB name is case insensitive. These are the same naming conventions as for a database name (as described in the `DB_NAME` initialization parameter description).

These rules apply for the `ENABLED_PDBS_ON_STANDBY` parameter:

- Any PDB names that match glob patterns starting with minus sign (-) will not be part of the standby database.
- If a PDB name matches several patterns in the *PDB-list* at the same time, the rightmost matched pattern has the highest precedence.
- If this parameter is not specified in the `init.ora` file, it is assumed that “*” is specified by default.
- If one or more patterns are specified in this parameter, it is assumed that “-*” is implicitly specified in the leftmost position. For example, `ENABLED_PDBS_ON_STANDBY="PDB1", "PDB2"` is equivalent to `ENABLED_PDBS_ON_STANDBY="-*", "PDB1", "PDB2"`. It means that a PDB name that does not match any patterns is not allowed to be part of the standby.

Examples

These examples assumes that nine new PDBs named PDB1A, PDB1B, PDB1C, PDB2A, PDB2B, PDB2C, PDB3A, PDB3B, and PDB3C are being added to the primary database.

1. If STANDBY1 sets `ENABLED_PDBS_ON_STANDBY="*"` on STANDBY1, then all nine PDBs will be created on STANDBY1.
2. If STANDBY1 sets `ENABLED_PDBS_ON_STANDBY="PDB1*"` on STANDBY1, then PDB1A, PDB1B, and PDB1C will be created on STANDBY1.
3. If STANDBY1 sets `ENABLED_PDBS_ON_STANDBY="PDB*A"` on STANDBY1, then PDB1A, PDB2A, and PDB3A will be created on STANDBY1.

4. If STANDBY1 sets `ENABLED_PDBS_ON_STANDBY="PDB1*", "-PDB*A"` on STANDBY1, then PDB1B and PDB1C will be created on STANDBY1.
5. If STANDBY1 sets `ENABLED_PDBS_ON_STANDBY="*", "-PDB*A", "-PDB*B"` on STANDBY1, then PDB1C, PDB2C and PDB3C will be created on STANDBY1. All other PDBs match "*", and the rightmost pattern has the higher precedence, so they are excluded on the standby.
6. If STANDBY1 sets `ENABLED_PDBS_ON_STANDBY="*", "-PDB*A", "PDB2A"` on STANDBY1, then PDB1A and PDB3A are excluded, but all other PDBs including PDB2A will be created.

2.131 ENCRYPT_NEW_TABLESPACES

`ENCRYPT_NEW_TABLESPACES` specifies whether to encrypt newly created user tablespaces.

Property	Description
Parameter type	String
Syntax	`ENCRYPT_NEW_TABLESPACES = { CLOUD_ONLY | ALWAYS | DDL }`
Default value	`CLOUD_ONLY`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	The same value should be specified for all instances.

The values that can be specified for the `ENCRYPT_NEW_TABLESPACES` parameter have the following meanings:

- `CLOUD_ONLY`:

  When a user tablespace is created in the Oracle Cloud, it will be transparently encrypted if the `ENCRYPTION ... ENCRYPT` clause for the SQL `CREATE TABLESPACE` statement is not specified. The encryption algorithm is determined by the value of the `TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM` initialization parameter. When a user tablespace is created in an on-premises database, the `ENCRYPTION` clause of the `CREATE TABLESPACE` statement determines if the tablespace is encrypted.

  `CLOUD_ONLY` is the default value.

- `ALWAYS`:

  Whether the user tablespace is created in the Oracle Cloud or in an on-premises database, the tablespace will be transparently encrypted if the `ENCRYPTION ... ENCRYPT` clause is not specified in the `CREATE TABLESPACE` statement. The encryption algorithm is determined by the value of the `TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM` initialization parameter.

- `DDL`:

  Whether the user tablespace is created in the Oracle Cloud or in an on-premises database, the `CREATE TABLESPACE` statement follows the specified DDL. If no `ENCRYPTION` clause is specified, then the tablespace will not be encrypted. If the `ENCRYPTION USING ... ENCRYPT` clause is specified, then the specified algorithm will be used to encrypt the tablespace. If `ENCRYPTION ENCRYPT` is specified, but no algorithm is specified, then the

encryption algorithm is determined by the value of the TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM initialization parameter.

Note:

ENCRYPT_NEW_TABLESPACES is deprecated in Oracle Database 23ai and may be removed in a future release. Oracle recommends that you use the TABLESPACE_ENCRYPTION initialization parameter instead.

See Also:

- TABLESPACE_ENCRYPTION
- TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM
- *Oracle Database Advanced Security Guide* for more information about tablespace encryption
- *Oracle Database SQL Language Reference* for more information about the CREATE TABLESPACE statement

2.132 ERROR_MESSAGE_DETAILS

Use ERROR_MESSAGE_DETAILS to control whether the database raises an additional stacked error message, with further details about the data values encountering the error, when displaying error messages.

Property	Description
Parameter type	String
Syntax	ERROR_MESSAGE_DETAILS = { ON | OFF | DISALLOWED }
Default value	ON
Modifiable	ALTER SESSION can be used to set this parameter to ON or OFF. ALTER SYSTEM can be used to set this parameter to ON, OFF, or DISALLOWED.
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Different instances can use different values.

This parameter allows you to instruct the database to show or omit explanatory details about data values causing an error. Providing this information usually makes it easier for the user to understand why the error occurred. If this is not desired, this parameter can be used to omit these additional details.

The detailed error message is being raised as a stacked error, meaning that applications will see the root cause error as the main error and will have to further traverse the stack to gain insights into the details. SQL command line tools will automatically traverse the entire stack and print the entire error message stack.

You can set this parameter for the database instance or PDB with the `ALTER SYSTEM` statement, or for the current session with the `ALTER SESSION` statement, using these values:

- `ON`: The database will provide additional explanatory details when displaying error messages. This is the default.
- `OFF`: The database will not provide additional explanatory details. This is the behavior prior to Oracle Database 23ai.

Additionally, you can set the following value only at the database instance or PDB level with the `ALTER SYSTEM` statement:

- `DISALLOWED`: The database will not provide additional explanatory details, and users cannot override this behavior for the current session with the `ALTER SESSION` statement.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.133 EVENT

`EVENT` is a parameter used only to debug the system.

Property	Description
Parameter type	String
Default value	There is no default value.
Modifiable	No
Modifiable in a PDB	No
Basic	No

Do not alter the value of this parameter except under the supervision of Oracle Support Services staff.

2.134 EXTERNAL_KEYSTORE_CREDENTIAL_LOCATION

`EXTERNAL_KEYSTORE_CREDENTIAL_LOCATION` specifies the location of the secure external keystore.

Property	Description
Parameter type	String
Syntax	`EXTERNAL_KEYSTORE_CREDENTIAL_LOCATION = file-location`
Default value	No default value
Modifiable	No
Modifiable in a PDB	No
Basic	No

Property	Description
Oracle RAC	This parameter can be set on each instance. Oracle recommends that if the instances have a shared location, then use a directory on the shared location for this parameter and set the same value on all Oracle RAC instances. If the database does not have a shared location, then each instance of the database will have its own directory and the value should be set per-instance.

TDE keystore credentials can be stored in a secure external keystore to automate Transparent Data Encryption (TDE) operations.

To automate the setting of the Master Key in a newly-provisioned PDB, set `EXTERNAL_KEYSTORE_CREDENTIAL_LOCATION` so that the CDB knows the location of the secure external keystore.

When a file specification is set with this parameter, the secure external keystore is looked for in that location. If the secure external keystore is not found in that location, then this parameter is ignored.

See Also:

Oracle Database Advanced Security Guide for more information about using TDE

2.135 FAL_CLIENT

`FAL_CLIENT` specifies the FAL (fetch archive log) client name that is used by the FAL service, configured through the `FAL_SERVER` initialization parameter, to refer to the FAL client.

Property	Description
Parameter type	String
Syntax	`FAL_CLIENT = string`
Default value	There is no default value.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No

The value is an Oracle Net service name, which is assumed to be configured properly on the FAL server system to point to the FAL client (standby database).

See Also:

Oracle Data Guard Concepts and Administration for more information about FAL server

2.136 FAL_SERVER

FAL_SERVER specifies the FAL (fetch archive log) server for a standby database.

Property	Description
Parameter type	String
Syntax	FAL_SERVER = *string*
Default value	There is no default value.
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Basic	No

The value is an Oracle Net service name, which is assumed to be configured properly on the standby database system to point to the desired FAL server.

See Also:

Oracle Data Guard Concepts and Administration for more information about FAL server

2.137 FAST_START_MTTR_TARGET

FAST_START_MTTR_TARGET enables you to specify the number of seconds the database takes to perform crash recovery of a single instance.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	0 to 3600 seconds
Basic	No
Oracle RAC	Multiple instances can have different values, and you can change the values at run time.

When specified, FAST_START_MTTR_TARGET is overridden by LOG_CHECKPOINT_INTERVAL.

See Also:

- *Oracle Database Performance Tuning Guide* for an example of setting the lower bound for this parameter
- *Oracle Database Performance Tuning Guide* for an example of setting the upper bound for this parameter
- *Oracle Database Performance Tuning Guide* for an example of selecting a preliminary value for this parameter

2.138 FAST_START_PARALLEL_ROLLBACK

`FAST_START_PARALLEL_ROLLBACK` specifies the degree of parallelism used when recovering terminated transactions.

Property	Description
Parameter type	String
Syntax	`FAST_START_PARALLEL_ROLLBACK = { HIGH | LOW | FALSE }`
Default value	`LOW`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

Terminated transactions are transactions that are active before a system failure. If a system fails when there are uncommitted parallel DML or DDL transactions, then you can speed up transaction recovery during startup by using this parameter.

Values

- `FALSE`

  Parallel rollback is disabled

- `LOW`

  Limits the maximum degree of parallelism to 2 * `CPU_COUNT`

- `HIGH`

  Limits the maximum degree of parallelism to 4 * `CPU_COUNT`

If you change the value of this parameter, then transaction recovery will be stopped and restarted with the new implied degree of parallelism.

See Also:

Oracle Database VLDB and Partitioning Guide for more information about this parameter

2.139 FILE_MAPPING

`FILE_MAPPING` specifies whether file mapping is enabled.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No

> **Note:**
>
> The `FILE_MAPPING` initialization parameter is deprecated. It is still supported for backward compatibility.

The FMON background process is started to manage the mapping information when file mapping is enabled.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about the file mapping feature

2.140 FILEIO_NETWORK_ADAPTERS

`FILEIO_NETWORK_ADAPTERS` specifies a list of network adapters that can be used to access the disk storage.

Property	Description
Parameter type	String
Syntax	`FILEIO_NETWORK_ADAPTERS = adapter_name [, adapter_name ] ...`
Default value	There is no default value.
Modifiable	No
Modifiable in a PDB	No
Range of values	One or more network adapter names, separated by commas
Basic	No

On platforms where the database files reside in network attached storage, this parameter provides the storage access library the list of network adapters that can be used to access the storage.

The network adapter name is a fully qualified address name of the network card that can be accessed through the host name database or using the Network Information Service. The components of the adapter name are separated by periods. For example, the following is a fully qualified adapter name:

```
ib1.oracle.com
```

2.141 FILESYSTEMIO_OPTIONS

`FILESYSTEMIO_OPTIONS` specifies I/O operations for file system files.

Property	Description
Parameter type	String
Syntax	`FILESYSTEMIO_OPTIONS = { none | setall | directIO | asynch }`
Default value	Varies by database version and operating system.
Modifiable	No
Modifiable in a PDB	No
Basic	No

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for information about setting this parameter before running I/O calibration

2.142 FIXED_DATE

`FIXED_DATE` enables you to set a constant date that `SYSDATE` will always return instead of the current date.

Property	Description
Parameter type	String
Syntax	`FIXED_DATE = [YYYY-MM-DD-HH24:MI:SS` (or the default Oracle date format) `| NONE]`
Default value	There is no default value.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

To undo a fixed date setting, specify `FIXED_DATE=NONE`. This parameter is useful primarily for testing. The value can be in the format shown above or in the default Oracle date format, without a time.

2.143 FORWARD_LISTENER

`FORWARD_LISTENER` specifies the name of a listener to which a connection must be forwarded by an existing set of remote listeners.

Property	Description
Parameter type	String
Syntax	`FORWARD_LISTENER = listener-name`
Default value	NULL
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	A different value can be set on different instances.

The parameter is useful when it is difficult to change an existing client connect string, for example, after an offsite database has been moved into the Oracle Cloud. With the `FORWARD_LISTENER` parameter, clients can continue to connect to their offsite listener, and the offsite listener forwards the connection to the Oracle Cloud listener.

Once a forward listener has been configured through the `FORWARD_LISTENER` parameter, the `LOCAL_LISTENER` parameter can be cleared by setting its value to `-oracle-none-` so that all the connections coming to an existing set of remote listeners configured through the `REMOTE_LISTENER` parameter are forwarded only to listeners configured through `FORWARD_LISTENER`.

The `FORWARD_LISTENER` parameter can also be specified in the `LISTENER_NETWORKS` parameter.

Examples

The following setup can be used to forward all the database connections coming to an existing customer SCAN listener to the Oracle Cloud SCAN listener.

```
REMOTE_LISTENER=customer-scan
FORWARD_LISTENER=oracle-cloud-scan
LOCAL_LISTENER=oracle-none-
```

See Also:

- "LOCAL_LISTENER"
- "REMOTE_LISTENER"
- "LISTENER_NETWORKS"
- *Oracle Clusterware Administration and Deployment Guide* for information about SCAN listeners

2.144 GCS_SERVER_PROCESSES

GCS_SERVER_PROCESSES specifies the number of background GCS server processes (LMS*n* and LM*nn*) to serve the inter-instance traffic among Oracle RAC instances.

If there is high Cache Fusion congestion on the system, the number of GCS server processes could be increased to reduce Cluster wait time. Additionally, the number of GCS server processes could be increased to reduce the application brownout time associated with Cluster reconfiguration and Dynamic Re-mastering (DRM).

Property	Description
Parameter type	Integer
Default value	Oracle calculates the default value as follows (in order of precedence): 1. If CLUSTER_DATABASE is set to false, then 0 2. If Oracle ASM, then 1 3. If 1 - 3 CPUS, then 1 4. If 4 - 15 CPUs, then 2 5. If 128 or more CPUs and SGA is 100 GB or more, then (CPUs / 6). If the result includes a fraction, then the fraction is disregarded. 6. Otherwise, the value is 2 + (CPUs / 32). If the result includes a fraction, then the fraction is disregarded. For example, if you have 20 CPUs, then 2 + (20 / 32) would equal 2 GCS processes. 7. On NUMA-enabled systems with 32 or more CPUs, the value is rounded up to a multiple of the number of NUMA processor groups, with a limit of (CPUs / 4) rounded down to a multiple of the number of NUMA processor groups.
Modifiable	No
Modifiable in a PDB	No
Range of values	0 if Oracle RAC is disabled (CLUSTER_DATABASE is set to false) 1 to 100 if Oracle RAC is enabled (CLUSTER_DATABASE is set to true)
Basic	No
Oracle RAC	Multiple instances can have different values.

GCS server processes are only seen in an Oracle RAC environment.

2.145 GLOBAL_NAMES

GLOBAL_NAMES specifies whether a database link is required to have the same name as the database to which it connects.

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SESSION, ALTER SYSTEM

Property	Description
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No

If the value of `GLOBAL_NAMES` is `false`, then no check is performed. If you use or plan to use distributed processing, then Oracle recommends that you set this parameter to `true` to ensure the use of consistent naming conventions for databases and links in a networked environment.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information on setting this parameter

2.146 GLOBAL_TXN_PROCESSES

`GLOBAL_TXN_PROCESSES` specifies the initial number of GTX*n* background processes (GTX0, ... GTX9 and GTXa, ... GTXj) per instance to support global (XA) transactions in an Oracle RAC environment.

Property	Description
Parameter type	Integer
Default value	`1`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	`0` to `20`
Basic	No
Oracle RAC	Multiple instances can have different values.

If you want to disable the GTX*n* background processes, then you must set `GLOBAL_TXN_PROCESSES` to `0` in your parameter file. Setting this parameter to `0` will disable the XA support on an Oracle RAC database. Error `ORA-55712` will be returned if you try to run XA transactions on an Oracle RAC database with this parameter set to `0`. You can change the setting to a nonzero value at run time to turn on the support for XA.

`GLOBAL_TXN_PROCESSES` is useful for systems that process global (XA) transactions heavily. You do not need to specify a value for this parameter since Oracle Database automatically determines the number of processes and autotunes them, as necessary. GTX*n* background processes are only seen in an Oracle RAC environment.

> **See Also:**
>
> *Oracle Database Development Guide* for more information about this parameter

2.147 GROUP_BY_POSITION_ENABLED

`GROUP_BY_POSITION_ENABLED` controls whether a positive integer in a `GROUP BY` clause is treated as the ordinal position of an expression in the select list.

Property	Description
Parameter type	Boolean
Default value	`FALSE`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`TRUE	FALSE`
Basic	No
Oracle RAC	The same value must be used on all instances.

In SQL `SELECT` statements, you can specify the `GROUP BY` clause when you want to group the selected rows that share a common value for an expression and return a single row of summary information for each group.

In previous releases, if you wanted to group rows according to the value of an expression in the select list, you specified the expression as it appeared in the select list. For example:

```
SELECT department_id, COUNT(*)
  FROM employees
  GROUP BY department_id;
```

Starting with Oracle Database 23ai, when `GROUP_BY_POSITION_ENABLED` is set to `TRUE`, you can specify `GROUP BY` *`position`*, where *`position`* is a positive integer that represents the ordinal position of an expression in the select list. For example, the following `SELECT` statement groups the selected rows by the value of `department_id`:

```
SELECT department_id, COUNT(*)
  FROM employees
  GROUP BY 1;
```

The following `SELECT` statement groups the selected rows, first by the value of `manager_id`, and then by the value of `hired_year`:

```
SELECT manager_id, EXTRACT(YEAR FROM hire_date) AS hired_year, COUNT(*)
  FROM employees
  GROUP BY 1, 2;
```

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

> **See Also:**
>
> *Oracle Database SQL Language Reference* for more information about the `GROUP BY` clause of the `SELECT` statement

2.148 HASH_AREA_SIZE

`HASH_AREA_SIZE` specifies the maximum amount of memory, in bytes, to be used for hash joins.

Property	Description
Parameter type	Integer
Default value	Derived: 2 * `SORT_AREA_SIZE`
Modifiable	`ALTER SESSION`
Modifiable in a PDB	No
Range of values	0 to operating system-dependent
Basic	No

> **Note:**
>
> Oracle does not recommend using the `HASH_AREA_SIZE` parameter unless the instance is configured with the shared server option. Oracle recommends that you enable automatic sizing of SQL working areas by setting `PGA_AGGREGATE_TARGET` instead. `HASH_AREA_SIZE` is retained for backward compatibility.

`HASH_AREA_SIZE` is relevant to parallel execution operations and to the query portion of DML or DDL statements.

> **See Also:**
>
> - *Oracle Database Concepts* for information on hash joins in general

2.149 HEARTBEAT_BATCH_SIZE

Use `HEARTBEAT_BATCH_SIZE` to configure the heartbeat batch size, which is the number of heartbeats sent during one heartbeat period.

Property	Description
Parameter type	Integer
Default value	`5`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`2` to `100`
Basic	No
Oracle RAC	Multiple instances must have the same value.

2.150 HEAT_MAP

Use `HEAT_MAP` to enable or disable both the Heat Map and Automatic Data Optimization (ADO) features.

Property	Description
Parameter type	String
Syntax	`HEAT_MAP = { ON | OFF }`
Default value	`OFF`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	If specified, use the same value on all instances

Setting the `HEAT_MAP` initialization parameter to `ON` causes the database to track read and write access of all segments, as well as modification of database blocks, due to DMLs and DDLs. These activities are not tracked for objects in the `SYSTEM` and `SYSAUX` tablespaces.

See Also:

- *Oracle Database VLDB and Partitioning Guide* for more information about enabling and disabling the Heat Map feature
- *Oracle Database VLDB and Partitioning Guide* for more information about Heat Map tracking

2.151 HI_SHARED_MEMORY_ADDRESS

`HI_SHARED_MEMORY_ADDRESS` specifies the starting address at run time of the system global area (SGA).

Property	Description
Parameter type	Integer
Default value	`0`
Modifiable	No
Modifiable in a PDB	No
Basic	No

This parameter is ignored on platforms that specify the SGA's starting address at linktime.

On 64-bit platforms, use `HI_SHARED_MEMORY_ADDRESS` to specify the high-order 32 bits of a 64-bit address. Use `SHARED_MEMORY_ADDRESS` to specify the low-order 32 bits of the address (see "SHARED_MEMORY_ADDRESS"). If both parameters are 0 or unspecified, the SGA address defaults to a platform-specific location.

2.152 HS_AUTOREGISTER

`HS_AUTOREGISTER` enables or disables automatic self-registration of Heterogeneous Services (HS) agents.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	`true	false`
Basic	No

When enabled, information is uploaded into the server's data dictionary to describe a previously unknown agent class or a new agent version.

Oracle recommends that you set this parameter to `true`. Oracle incurs less overhead when establishing subsequent connections through the same agent if self-registered information is available in the server's data dictionary.

> **See Also:**
>
> *Oracle Database Heterogeneous Connectivity User's Guide* for more information about using HS agents

2.153 HYBRID_READ_ONLY

HYBRID_READ_ONLY enables or disables hybrid read-only mode for a pluggable database (PDB).

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	true | false
Basic	No
Oracle RAC	Different instances can use different values.

Hybrid read-only mode allows a PDB to operate in read/write mode or read-only mode, depending on the type of user that is connected to the PDB. The PDB operates in read/write mode for CDB common users, and read-only mode for application common users and local users. Hybrid read-only mode allows CDB common users to perform patching and maintenance operations on an open PDB, while application common users and local users can use the PDB as if it were open in read-only mode.

- To enable hybrid read-only mode for a PDB, connect to the PDB and set HYBRID_READ_ONLY to true. The PDB must be in READ WRITE mode before you enable hybrid read-only mode.
- To disable hybrid read-only mode for a PDB, connect to the PDB and set HYBRID_READ_ONLY to false.

You can determine whether a PDB is in hybrid read-only mode by querying the IS_HYBRID_READ_ONLY column of the V$CONTAINER_TOPOLOGY view.

When a PDB is in hybrid read-only mode, the OPEN_MODE column in the V$CONTAINERS and V$PDBS views reflects the mode for the querying user, that is, the OPEN_MODE column returns READ WRITE when queried by a CDB common user, and READ ONLY when queried by an application common user or a local user.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

> **See Also:**
>
> "V$CONTAINER_TOPOLOGY"

2.154 IDENTITY_PROVIDER_CONFIG

Use `IDENTITY_PROVIDER_CONFIG` to configure the database to use Microsoft Azure Active Directory (Azure AD) as an external identity provider.

Property	Description
Parameter type	String
Syntax	`IDENTITY_PROVIDER_CONFIG = '{ "application_id_uri" : "string", "tenant_id" : "string", "app_id" : "string" }'` Where: • The `application_id_uri` value is obtained from the registered application, to be mapped in the JWT "aud" (audience) claim. It must be domain qualified and start with "https://" to specify the OCI database to access. • The `tenant_id` value is obtained from the tenant configuration and is also available on the database application registration overview page. • The `app_id` value is obtained from the registered resource application and is also available on the database application registration overview page.
Default value	None
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	The same value must be used on all instances.

This parameter is effective only when the database is enabled to use Azure AD as an external identity provider, that is, when the `IDENTITY_PROVIDER_TYPE` initialization parameter is set to `AZURE_AD`. You must use this parameter to specify Azure AD configuration settings.

Example:

```
ALTER SYSTEM SET IDENTITY_PROVIDER_CONFIG =
  '{ "application_id_uri" : "https://example.com/pdb1",
     "tenant_id" : "111a1111-a11a-111a-111111111111a",
     "app_id" : "11aa1a1-aaaa-1111-1111-1111aa111111" }'
   SCOPE=BOTH;
```

> **Note:**
>
> Setting the value of this parameter is only one step in a series of steps for configuring the database to use Azure AD. Refer to *Oracle Database Security Guide* for the complete steps before you set this parameter.

> **Note:**
>
> For additional information about using this parameter with Oracle Autonomous Database, refer to "Use Azure Active Directory (Azure AD) with Autonomous Database".

> **Note:**
>
> This parameter is not available to update directly for Oracle Autonomous Database Serverless.

> **Note:**
>
> This parameter is available in Oracle Database 19c, starting with version 19.16, and in Oracle Database 23ai. This parameter is not available in Oracle Database 21c.

> **See Also:**
>
> "IDENTITY_PROVIDER_TYPE"

2.155 IDENTITY_PROVIDER_TYPE

`IDENTITY_PROVIDER_TYPE` specifies an external identity provider for the database.

Property	Description
Parameter type	String
Syntax	`IDENTITY_PROVIDER_TYPE = { AZURE_AD | OCI_IAM | NONE }`
Default value	`NONE`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	The same value must be used on all instances.

Values:

- `AZURE_AD` - Enables the database to use Microsoft Azure Active Directory (Azure AD) as an external identity provider.

  When you specify this value, you must also specify configuration settings for Azure AD by setting the `IDENTITY_PROVIDER_CONFIG` initialization parameter.

- `OCI_AM` - Enables the database to use Oracle Cloud Infrastructure Identity and Access Management (OCI IAM) as an external identity provider.

  When you specify this value, there is no need to specify configuration settings with the `IDENTITY_PROVIDER_CONFIG` initialization parameter.
- `NONE` - The database will not use Azure AD or OCI IAM as an external identity provider.

Note:

Setting the value of this parameter is only one step in a series of steps for configuring an external identity provider for the database. Refer to *Oracle Database Security Guide* for the complete set of steps for configuring Azure AD or OCI IAM before you set this parameter value.

Note:

The following resources offer additional information about using this parameter with Oracle Autonomous Database:

- "Use Azure Active Directory (Azure AD) with Autonomous Database"
- "Use Identity and Access Management (IAM) Authentication with Autonomous Database"

Note:

This parameter is not available to update directly for Oracle Autonomous Database Serverless.

Note:

This parameter is available in Oracle Database 19c, starting with version 19.16, and in Oracle Database 23ai. This parameter is not available in Oracle Database 21c.

See Also:

"IDENTITY_PROVIDER_CONFIG"

2.156 IFILE

Use `IFILE` to embed another parameter file within the current parameter file.

Property	Description
Parameter type	Parameter file
Syntax	`IFILE = parameter_file_name`
Default value	There is no default value.
Modifiable	No
Modifiable in a PDB	No
Range of values	Valid parameter filenames
Basic	No
Oracle RAC	Multiple instances can have different values.

For example:

```
IFILE = COMMON.ORA
```

You can have up to three levels of nesting. In this example, the file `COMMON.ORA` could contain a second `IFILE` parameter for the file `COMMON2.ORA`, which could contain a third `IFILE` parameter for the file `GCPARMS.ORA`. You can also include multiple parameter files in one parameter file by listing `IFILE` several times with different values:

```
IFILE = DBPARMS.ORA
IFILE = GCPARMS.ORA
IFILE = LOGPARMS.ORA
```

> **Note:**
>
> You must list multiple entries on contiguous lines of the parameter file.

2.157 IGNORE_SESSION_SET_PARAM_ERRORS

`IGNORE_SESSION_SET_PARAM_ERRORS` controls whether the database ignores errors when clients attempt to modify session parameter values.

Property	Description
Parameter type	String
Syntax	`IGNORE_SESSION_SET_PARAM_ERRORS = parameter_name [, parameter_name ] ...`
Default value	None
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Multiple instances should use the same value.

The `IGNORE_SESSION_SET_PARAM_ERRORS` parameter allows you to change the outcome of the following scenario:

1. An Oracle database uses PDB lockdown profiles to prevent certain initialization parameters from being modified with the `ALTER SESSION` statement.
2. A database client attempts to modify one of those parameters with the `ALTER SESSION` statement. The client has no knowledge that the parameter is locked down.
3. The database returns an error to the client.

To prevent the database from returning an error in the preceding scenario, set the value of `IGNORE_SESSION_SET_PARAM_ERRORS` to a comma-separated list of locked down initialization parameters. Thereafter, if a client attempts to modify one of those parameters with the `ALTER SESSION` statement, the database will ignore the modification attempt and indicate to the client that the operation was successful.

You can set the `IGNORE_SESSION_SET_PARAM_ERRORS` parameter while connected to a specific PDB, or you can apply it to all PDBs by setting it in the CDB root.

Example

The `CURSOR_INVALIDATION` and `CURSOR_SHARING` parameters are locked down in one of the PDBs in your database. If a client application attempts to modify either of these parameters, you want the database to ignore the request and allow the application to continue running without incurring an error. To achieve this, you can connect to the PDB and set the `IGNORE_SESSION_SET_PARAM_ERRORS` parameter. For example:

```
ALTER SYSTEM SET IGNORE_SESSION_SET_PARAM_ERRORS = CURSOR_INVALIDATION,
CURSOR_SHARING;
```

2.158 INMEMORY_ADG_ENABLED

`INMEMORY_ADG_ENABLED` indicates whether in-memory for Active Data Guard is enabled in addition to the in-memory cache size.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No
Oracle RAC	The same value should be used on all instances. If the value for this parameter is changed on one instance, the parameter's value should be changed to the same value on the other instances.

For Active Data Guard, media recovery needs to retrieve in-memory objects when applying redo and to invalidate the related objects after the query advance. This parameter controls whether media recovery does the retrieving and invalidating.

This parameter should be set on standby databases. The value of this parameter is meaningless on a primary database.

If the standby is an Oracle RAC instance, then all the different standby instances must have this parameter set to the same value.

This parameter is a dynamic system-modifiable parameter whose value can be changed only when Active Data Guard recovery is not running.

If you start multi-instance redo apply (MIRA) Active Data Guard recovery, all instances involved in MIRA must have the parameter set to the same value, otherwise MIRA will signal an error.

Example

If the standby is an Oracle RAC instance, this parameter should be set to the same value on all the Oracle RAC instances:

```
SQL> alter system set inmemory_adg_enabled=true sid='*';
```

See Also:

- "INMEMORY_SIZE"
- *Oracle Database In-Memory Guide* for more information about deploying an In-Memory Column Store (IM column store) in an Active Data Guard environment

2.159 INMEMORY_AUTOMATIC_LEVEL

`INMEMORY_AUTOMATIC_LEVEL` is used to enable the Automatic In-Memory feature, which automates the management of the In-Memory Column Store (IM column store) to help ensure that the working data set is in the IM column store at all times.

Property	Description
Parameter type	String
Syntax	`INMEMORY_AUTOMATIC_LEVEL = { LOW | MEDIUM | HIGH | OFF }`
Default value	`OFF`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	All instances should use the same value.

Typically, among all the IM enabled segments, only a subset is actively queried at any time. This subset is known as the working data set. The working data set is expected to change over time for many applications.

`INMEMORY_AUTOMATIC_LEVEL` attempts to keep the working data set in the IM column store at all times by moving segments in and out of the IM column store based on access patterns.

Oracle recommends that you provision enough memory for the working data set to fit in the IM column store.

The following values can be set:

- `LOW`: The database evicts cold segments from the IM column store when it is under memory pressure.
- `MEDIUM`: The database evicts cold segments from the IM column store when it is under memory pressure. This level includes an additional optimization that ensures that any hot segment that was not populated because of memory pressure is populated first.
- `HIGH`: All segments in the database are enabled for the IM column store, except segments belonging to Oracle-maintained users and segments from external tables. Automatic In-Memory manages all segments enabled for the IM column store, keeping hot segments in the IM column store and evicting cold segments. This level includes an additional optimization that ensures that any hot segment that was not populated because of memory pressure is populated first.
- `OFF`: Automatic In-Memory is disabled. This value returns the IM column store to the behavior that existed prior to Oracle Database 18c, when the Automatic In-Memory features was introduced. If you do not expect a stable working data set, set the parameter to `OFF`. This is the default value.

See Also:

- *Oracle Database Licensing Information User Manual* to learn which database offerings support the Automatic In-Memory feature
- *Oracle Database In-Memory Guide* for more information about configuring the Automatic In-Memory feature

2.160 INMEMORY_CLAUSE_DEFAULT

`INMEMORY_CLAUSE_DEFAULT` enables you to specify a default In-Memory Column Store (IM column store) clause for new tables and materialized views.

Note:

The setting of his parameter has no effect on In-Memory external tables or hybrid partitioned tables.

Property	Description
Parameter type	String
Syntax	`INMEMORY_CLAUSE_DEFAULT = '[INMEMORY] [NO INMEMORY] [other-clauses]'`
Syntax	**other-clauses::=** `[compression-clause] [priority-clause] [rac-clause]`
Syntax	**compression-clause::=** `NO MEMCOMPRESS | MEMCOMPRESS FOR { DML | QUERY [ LOW | HIGH ] | CAPACITY [LOW | HIGH] }`[1]

Property	Description
Syntax	**priority-clause::=** `PRIORITY { LOW | MEDIUM | HIGH | CRITICAL | NONE }`[1]
Syntax	**rac-clause::=** `[distribute-clause] [duplicate-clause]`[1]
Syntax	**distribute-clause::=** `DISTRIBUTE [ AUTO | BY ROWID RANGE ]`[1]
Syntax	**duplicate-clause::=** `NO DUPLICATE | DUPLICATE [ ALL ]`[1]
Default value	An empty string
Modifiable	`ALTER SESSION, ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	All instances should use the same value

1 See Table 2-2 for more information about this clause.

If the `INMEMORY_CLAUSE_DEFAULT` parameter is unset or set to an empty string (the default), only tables and materialized views explicitly specified as `INMEMORY` will be populated into the IM column store. Setting the value of the `INMEMORY_CLAUSE_DEFAULT` parameter to `NO INMEMORY` has the same effect as setting it to the default value.

If the `INMEMORY_CLAUSE_DEFAULT` parameter is set, then any *newly created* table or materialized view specified as `INMEMORY` will inherit unspecified attributes from this parameter. This can force certain in-memory options by default that are not explicitly specified in the syntax. For example, if the `INMEMORY_CLAUSE_DEFAULT` parameter is set to `MEMCOMPRESS FOR CAPACITY LOW` and a table is created as `INMEMORY PRIORITY HIGH`, then the table is treated as if it was declared as `INMEMORY MEMCOMPRESS FOR CAPACITY LOW PRIORITY HIGH`.

If `INMEMORY` is specified as part of this parameter, then all newly created tables and materialized views will be populated into the IM column store, except tables and materialized views explicitly specified as `NO INMEMORY`. For example, if this parameter is set to `INMEMORY MEMCOMPRESS FOR CAPACITY HIGH`, then all new tables will be created as if this clause were present in the SQL `CREATE TABLE` statement. If there is a default `INMEMORY` value for the tablespace for a given segment, then it will override the value for this parameter.

Table 2-2 Meaning of INMEMORY_CLAUSE_DEFAULT Parameter Values

Syntax	Description
`INMEMORY`	Specifies that all newly-created tables and materialized views populate the IM column store unless they are specified as `NO INMEMORY` in the SQL `CREATE TABLE` or `CREATE MATERIALIZED VIEW` statement
`NO INMEMORY`	Specifies that only tables and materialized views explicitly specified as `INMEMORY` in the SQL `CREATE TABLE` or `CREATE MATERIALIZED VIEW` statements populate the IM column store

Table 2-2 (Cont.) Meaning of INMEMORY_CLAUSE_DEFAULT Parameter Values

Syntax	Description
compression-clause	Specifies that in-memory compression should be used for the instance. Use the MEMCOMPRESS FOR values to specify the in-memory compression level.
NO MEMCOMPRESS	When NO MEMCOMPRESS is specified, no in-memory compression is done in the IM column store.
MEMCOMPRESS FOR	MEMCOMPRESS FOR is used to indicate the in-memory compression level for the IM column store.
DML	When DML is specified, the IM column store is optimized for DML operations, and some lightweight in-memory compression may be done.
QUERY	When QUERY is specified, the in-memory compression level is for high performance. If QUERY is specified without LOW or HIGH, it defaults to QUERY LOW.
QUERY LOW	When QUERY LOW is specified, the in-memory compression level provides the highest performance.
QUERY HIGH	When QUERY HIGH is specified, the in-memory compression level provides a balance between compression and performance, weighted toward performance.
CAPACITY	When CAPACITY is specified without LOW or HIGH, it defaults to CAPACITY LOW.
CAPACITY LOW	When CAPACITY LOW is specified, the in-memory compression level is a balance between compression and performance, weighted toward capacity.
CAPACITY HIGH	When CAPACITY HIGH is specified, the in-memory compression level is for highest capacity.
priority-clause	Specifies the priority to use when populating tables in the IM column store. Use the PRIORITY values to specify the priority. By default, the population of a table in the IM column store can be delayed until the database determines it is useful. On database instance startup, tables are populated in priority order.
PRIORITY NONE	When PRIORITY NONE is specified, the population of a table in the IM column store can be delayed until the database determines it is useful. This is the default value when no priority is specified.
PRIORITY LOW	When PRIORITY LOW is specified for a table or tables, the population of those tables in the IM column store is done before tables that have no priority specified.
PRIORITY MEDIUM	When PRIORITY MEDIUM is specified for a table or tables, the population of those tables in the IM column store is done before tables that have no priority and PRIORITY LOW specified.
PRIORITY HIGH	When PRIORITY HIGH is specified for a table or tables, the population of those tables in the IM column store is done before tables that have no priority, PRIORITY LOW, and PRIORITY MEDIUM specified.

Table 2-2 (Cont.) Meaning of INMEMORY_CLAUSE_DEFAULT Parameter Values

Syntax	Description
PRIORITY CRITICAL	When PRIORITY CRITICAL is specified for a table or tables, the population of those tables in the IM column store is done before tables that have no priority, PRIORITY LOW, PRIORITY MEDIUM, and PRIORITY HIGH specified.
rac-clause	Specifies how tables in the IM column store will be managed among Oracle Real Application Clusters (Oracle RAC) instances. Use the distribute-clause and duplicate-clause to specify how tables in the IM store will be managed in Oracle RAC instances. For a non-Oracle RAC database, these settings have no effect, because the whole table or partition has to be on the single instance.
distribute-clause	Specifies how a table is distributed among Oracle RAC instances.
DISTRIBUTE AUTO	Specifies that the database will automatically decide how to distribute tables in the IM column store across the Oracle RAC instances based on the type of partitioning and the value of the duplicate-clause. DISTRIBUTE AUTO is the default, and it is also used when DISTRIBUTE is specified by itself.
DISTRIBUTE BY ROWID RANGE	Specifies that the tables in the IM column store will be distributed by rowid range to different Oracle RAC instances.
duplicate-clause	Specifies how many copies of each In-Memory Compression Unit (IMCU) of the tables in the IM column store will be spread across all the Oracle RAC instances. **Note:** The duplicate-clause is only applicable if you are using Oracle Real Application Clusters (Oracle RAC) on an engineered system. Otherwise, the duplicate-clause is ignored and there is only one copy of each IMCU in memory.
NO DUPLICATE	Data is not duplicated across Oracle RAC instances. This is the default.
DUPLICATE	Data is duplicated on another Oracle RAC instance, resulting in data existing on a total of two Oracle RAC instances.
DUPLICATE ALL	Data is duplicated across all Oracle RAC instances. If you specify DUPLICATE ALL, then the database uses the DISTRIBUTE AUTO setting, regardless of whether or how you specify the distribute-clause.

Examples

The following statement causes no tables to populate the IM column store:

```
alter system set INMEMORY_CLAUSE_DEFAULT='NO INMEMORY'
scope=both;
```

The following statement causes new tables and materialized views (except those specified as NO INMEMORY) to populate the IM column store at the high capacity compression level:

```
alter system set
INMEMORY_CLAUSE_DEFAULT='INMEMORY MEMCOMPRESS FOR CAPACITY HIGH'
scope=both;
```

The following statement causes new tables (even those specified as `NO INMEMORY`) to populate the IM column store at the highest performance compression level at `LOW` priority:

```
alter system set
INMEMORY_CLAUSE_DEFAULT='INMEMORY MEMCOMPRESS FOR QUERY LOW PRIORITY LOW'
scope=both;
```

The following statement causes new tables (even those specified as `NO INMEMORY`) to populate the IM column store without any in-memory compression:

```
alter system set
INMEMORY_CLAUSE_DEFAULT='INMEMORY NO MEMCOMPRESS'
scope=both;
```

The following statement causes tables in the IM column store to be duplicated on every Oracle RAC instance, unless on a non-engineered system. For a non-engineered system, the `duplicate-clause` (`DUPLICATE ALL`) will be ignored and tables in the column store will be automatically distributed across the Oracle RAC instance, with only one copy of each IMCU in the tables in the IM column store:

```
alter system set
INMEMORY_CLAUSE_DEFAULT='INMEMORY MEMCOMPRESS FOR QUERY
DISTRIBUTE AUTO DUPLICATE ALL'
scope=both;
```

The following statement sets the value of the `INMEMORY_CLAUSE_DEFAULT` parameter back to its default value, the empty string:

```
alter system set
INMEMORY_CLAUSE_DEFAULT=''
scope=both;
```

See Also:

- "INMEMORY_FORCE"
- "INMEMORY_QUERY"
- "INMEMORY_SIZE"
- "V$IM_SEGMENTS"
- "V$IM_USER_SEGMENTS"
- "QUERY_REWRITE_INTEGRITY"
- *Oracle Database In-Memory Guide* for an introduction to the IM column store
- *Oracle Database In-Memory Guide* for more information about the IM column store
- *Oracle Database In-Memory Guide* for more information on IM column store compression methods
- *Oracle Database In-Memory Guide* for more information on priority levels for populating a database object in the IM column store
- *Oracle Database SQL Language Reference* for more information on the CREATE TABLE statement
- *Oracle Database SQL Language Reference* for more information on the CREATE MATERIALIZED VIEW statement

2.161 INMEMORY_DEEP_VECTORIZATION

`INMEMORY_DEEP_VECTORIZATION` enables or disables the deep vectorization framework.

Property	Description
Parameter type	Boolean
Default value	`TRUE`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`TRUE	FALSE`
Basic	No

Deep vectorization can optimize complex SQL operations (such as joins) by pipelining physical operators inside each SQL operator and vectorizing them.

See Also:

Oracle Database In-Memory Guide for information about deep vectorization

2.162 INMEMORY_EXPRESSIONS_USAGE

INMEMORY_EXPRESSIONS_USAGE controls which In-Memory Expressions (IM expressions) are populated into the In-Memory Column Store (IM column store) and are available for queries.

Property	Description
Parameter type	String
Syntax	INMEMORY_EXPRESSIONS_USAGE = { STATIC_ONLY | DYNAMIC_ONLY | ENABLE | DISABLE }
Default value	ENABLE
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	The same value must be used on all instances.

The four values for this parameter are:

- STATIC_ONLY: Tables enabled for in-memory and containing certain data types such as Oracle numbers or JSON will have these columns populated in the IM column store using a more efficient representation. Note that this setting will increase the in-memory footprint for some tables. A static configuration enables the IM column store to cache OSON (binary JSON) columns, which are marked with an IS_JSON check constraint. Internally, an OSON column is a hidden virtual column named SYS_IME_OSON. In contrast, a dynamic configuration automatically creates and populates frequently used expressions.
- DYNAMIC_ONLY: IM expressions will be automatically created and populated into the IM column store, if used in conjunction with PL/SQL procedure DBMS_INMEMORY.IME_CAPTURE_EXPRESSIONS. Note that setting this value will increase the in-memory footprint for some tables.
- ENABLE: Both static and dynamic IM expressions will be populated into the IM column store and available to be used by queries. Note that setting this value will increase the in-memory footprint for some tables. This is the default value.
- DISABLE: No IM expressions of any kind will be populated into the IM column store.

Changing the mode of a parameter does not have an immediate effect on existing in-memory data. For example, if the inmemory_expressions_usage clause is changed from DYNAMIC_ONLY to DISABLE, the stored IM expressions are not immediately removed. The next repopulation will not bring back the expressions in memory, thereby effectively removing the expressions.

See Also:

- "INMEMORY_VIRTUAL_COLUMNS"
- *Oracle Database In-Memory Guide* for more information about IM expressions
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_INMEMORY PL/SQL package

2.163 INMEMORY_FORCE

INMEMORY_FORCE allows you to specify whether objects, such as tables, materialized views, and partitions, that are specified as INMEMORY are populated into the In-Memory Column Store (IM column store) or not.

Property	Description
Parameter type	String
Syntax	INMEMORY_FORCE = { DEFAULT | OFF | BASE_LEVEL | CELLMEMORY_LEVEL }
Default value	DEFAULT
Modifiable	You can use ALTER SYSTEM to dynamically modify this parameter setting as follows: • From DEFAULT to OFF • From OFF to DEFAULT • From BASE_LEVEL to DEFAULT • From CELLMEMORY_LEVEL to DEFAULT • From CELLMEMORY_LEVEL to OFF All other modifications of this parameter require you to update the initialization file and restart the instance.
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	All instances should use the same value.

The following values can be set:

- DEFAULT

  The IM column store is populated with objects that are specified as INMEMORY.

- OFF

  Even if the IM column store is configured on this instance, no objects are populated in memory.

- BASE_LEVEL

  Enables Database In-Memory Base Level. The Base Level lets you to experiment with Oracle Database In-Memory features without purchasing the Oracle Database In-Memory option.

  When the Base Level is enabled, the value of the INMEMORY_SIZE initialization parameter is limited to 16 GB for a CDB. In an Oracle RAC environment, the value of INMEMORY_SIZE is limited to 16 GB for each instance. The compression level for all objects and columns is automatically and transparently set to QUERY LOW. Automatic In-Memory is disabled, and In-Memory Column Store feature tracking is tracked for "In-Memory Base Level" rather than "In-Memory Column Store." The CellMemory feature is disabled for Oracle Exadata.

- CELLMEMORY_LEVEL

  CellMemory is an Exadata feature that allows you to use Exadata Smart Flash Cache to populate data in in-memory columnar format. In older releases of Oracle

Database, in order to use the CellMemory feature, you were required to enable the IM column store (by setting `INMEMORY_SIZE` to a value greater than `0`), even if you had no intention of using the IM column store. This incurred the overhead of enabling the IM column store without any benefit. Starting with Oracle Database release 19c, version 19.8, you can use the CellMemory feature without enabling the IM column store by setting `INMEMORY_FORCE=CELLMEMORY_LEVEL` and `INMEMORY_SIZE=0`. With these settings, the IM column store is not enabled and queries can use CellMemory to scan objects.

Note that if the value of `INMEMORY_SIZE` is greater than `0`, then setting `INMEMORY_FORCE=CELLMEMORY_LEVEL` is equivalent to setting `INMEMORY_FORCE=DEFAULT`. The IM column store is enabled, even if you only use CellMemory.

See Also:

- "INMEMORY_CLAUSE_DEFAULT"
- "INMEMORY_MAX_POPULATE_SERVERS"
- "INMEMORY_QUERY"
- "INMEMORY_SIZE"
- *Oracle Database In-Memory Guide* for an introduction to the IM column store
- *Oracle Database In-Memory Guide* for more information about the IM column store
- *Oracle Database Licensing Information User Manual* to learn which database offerings support the Database In-Memory Base Level feature

2.164 INMEMORY_MAX_POPULATE_SERVERS

`INMEMORY_MAX_POPULATE_SERVERS` specifies the maximum number of background populate servers to use for In-Memory Column Store (IM column store) population, so that these servers do not overload the rest of the system.

Property	Description
Parameter type	Integer
Default value	Half of the value of `CPU_COUNT` or the `PGA_AGGREGATE_TARGET` value divided by 512M, whichever is less. See the "CPU_COUNT" description for information about how `CPU_COUNT` is calculated.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	0 to a value based on the number of cores in the system.
Basic	No
Oracle RAC	All instances should use the same value.

This parameter has meaning only if the `INMEMORY_SIZE` parameter is also set to a positive value.

The value to use for this parameter depends on the number of cores in the system. A certain percentage of CPU should be allocated for in-memory background population, and this parameter should be set accordingly. You can also set this parameter to `0` to temporarily disable populate tasks on the system from executing.

Note:

Be careful not to set the value of this parameter too high. If it is set close to the number of cores or higher, no CPU could be left for the rest of the system to run.

Note:

The IM column store is not populated if this parameter is set to 0.

See Also:

- "INMEMORY_CLAUSE_DEFAULT"
- "INMEMORY_FORCE"
- "INMEMORY_QUERY"
- "INMEMORY_SIZE"
- *Oracle Database In-Memory Guide* for an introduction to the IM column store
- *Oracle Database In-Memory Guide* for more information about the IM column store

2.165 INMEMORY_OPTIMIZED_ARITHMETIC

`INMEMORY_OPTIMIZED_ARITHMETIC` encodes the `NUMBER` data type in in-memory tables compressed with `QUERY LOW` as a fixed-width native integer scaled by a common exponent.

Property	Description
Parameter type	String
Syntax	`INMEMORY_OPTIMIZED_ARITHMETIC = { ENABLE | DISABLE }`
Default value	`DISABLE`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Different values can be specified on different instances.

The Oracle Database NUMBER format can incur a significant performance overhead when executing queries because arithmetic operations cannot be performed natively in hardware.

When INMEMORY_OPTIMIZED_ARITHMETIC is set to ENABLE, for tables compressed with QUERY LOW, NUMBER columns are encoded as a fixed-width native integer scaled by a common exponent. This In-Memory optimized number format enables fast calculations using SIMD hardware. By using SIMD vector processing, arithmetic operations, simple aggregations, and group-by aggregations can benefit significantly.

Not all row sources in the query processing engine have support for the In-Memory optimized number format. Therefore, the IM column store must store both the traditional Oracle Database NUMBER data type and the In-Memory optimized number type. This means that the acceleration in analytic query performance comes at a cost of increased space overhead.

When INMEMORY_OPTIMIZED_ARITHMETIC is set to DISABLE (the default), the database does not use the optimized encoding.

If INMEMORY_OPTIMIZED_ARITHMETIC is set to ENABLE and then to DISABLE, the optimized number format for existing IMCUs is not dropped immediately. Instead, as the IM column store repopulates IMCUs, the new IMCUs do not use the optimized encoding.

See Also:

Oracle Database In-Memory Guide for details about the improved performance and increased space overhead when INMEMORY_OPTIMIZED_ARITHMETIC is enabled

2.166 INMEMORY_QUERY

INMEMORY_QUERY is used to enable or disable in-memory queries for the entire database at the session or system level.

Property	Description
Parameter type	String
Syntax	INMEMORY_QUERY = { ENABLE | DISABLE }
Default value	ENABLE
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	All instances should use the same value.

This parameter is helpful when you want to test workloads with and without the use of the In-Memory Column Store (IM column store).

This parameter enables in-memory queries for the entire database by default when the INMEMORY_SIZE parameter is specified.

Set this parameter to DISABLE if you want to disable in-memory queries.

See Also:

- "INMEMORY_CLAUSE_DEFAULT"
- "INMEMORY_FORCE"
- "INMEMORY_MAX_POPULATE_SERVERS"
- "INMEMORY_SIZE"
- *Oracle Database In-Memory Guide* for an introduction to the IM column store
- *Oracle Database In-Memory Guide* for more information about the IM column store

2.167 INMEMORY_SIZE

`INMEMORY_SIZE` sets the size of the In-Memory Area, which contains the IM Column Store (IM column store) on a database instance.

Property	Description
Parameter type	Big integer
Syntax	`INMEMORY_SIZE = integer [K | M | G]`
Default value	`0`
Modifiable	You can use `ALTER SYSTEM` to increase or decrease the value of this parameter. However, the value of this parameter must always be greater than or equal to its value at instance startup.
Modifiable in a PDB	Yes
Range of values	`0` to the amount of memory left in the SGA after other allocations A value of `0` specifies that the IM column store is not allocated and no In-Memory features are enabled. A value greater than `0` and less than `100M` specifies that the IM column store is enabled for future growth, but no memory is currently provisioned to the In-Memory Area.
Basic	No
Oracle RAC	All instances should use the same value.

The database must be restarted after setting this parameter to enable the IM column store.

Typically this parameter should be set to at least the size needed to accommodate all the tables that will use the IM column store. It can be set higher to allow for growth of those tables or to accommodate other tables that will use the IM column store in the future.

This parameter can also be set per PDB to limit the maximum size of the IM column store for that PDB. Note that the sum of the PDB values do not have to equal the CDB value, and the sum of the PDB values may even be greater than the CDB value.

Unless this parameter is specifically set on a PDB, each PDB inherits the CDB value, which means they can use all of the available IM column store.

The value specified for this parameter counts toward `SGA_TARGET`. For example, if you set `SGA_TARGET` to 10 GB and you set `INMEMORY_SIZE` to 2 GB, then 20% of the `SGA_TARGET` setting is allocated to the In-Memory Area.

Starting with Oracle Database 23ai, Automatic In-Memory Sizing can automatically grow or shrink the In-Memory Area based on the benefits of the column store if the following conditions are true:

- `SGA_TARGET` > `0`
- `INMEMORY_AUTOMATIC_LEVEL` = `MEDIUM` or `HIGH`
- `VECTOR_MEMORY_SIZE` is set to `0` or not specified

In-Memory Dynamic Scans require the Resource Manager. Therefore, the Resource Manager is automatically enabled when you change the value of `INMEMORY_SIZE` from `0` to a non-zero value. No specific resource plan is required.

Database In-Memory Base Level allows a maximum of 16 GB for the size of the In-Memory Area. Therefore, if Database In-Memory Base Level is enabled (the value of the `INMEMORY_FORCE` initialization parameter is set to `BASE_LEVEL`), then the value of `INMEMORY_SIZE` cannot exceed 16 GB for a CDB. In an Oracle RAC environment, the value of `INMEMORY_SIZE` is limited to 16 GB for each instance.

See Also:

- "INMEMORY_CLAUSE_DEFAULT"
- "INMEMORY_FORCE"
- "INMEMORY_MAX_POPULATE_SERVERS"
- "INMEMORY_QUERY"
- *Oracle Database In-Memory Guide* for an introduction to the IM column store
- *Oracle Database In-Memory Guide* for more information about the IM column store
- *Oracle Database In-Memory Guide* for an example of using the `INMEMORY_SIZE` parameter

2.168 INMEMORY_TRICKLE_REPOPULATE_SERVERS_PERCENT

`INMEMORY_TRICKLE_REPOPULATE_SERVERS_PERCENT` limits the maximum number of background populate servers used for In-Memory Column Store (IM column store) repopulation, as trickle repopulation is designed to use only a small percentage of the populate servers.

Property	Description
Parameter type	Integer

Property	Description
Default value	1
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	0 to 50
Basic	No
Oracle RAC	All instances should use the same value.

The value for this parameter is a percentage of the INMEMORY_MAX_POPULATE_SERVERS initialization parameter value.

For example, if this parameter is set to 5 and INMEMORY_MAX_POPULATE_SERVERS is set to 10, then on average half of a core is used for trickle repopulation.

The default value of 1 is good in most cases. In some cases, if you want to disable trickle repopulate, this parameter can be set to 0. If you want to keep the system more aggressively up to date (at the expense of more background CPU), you can set the parameter to higher values such as 5 or 10.

A value of greater than 50 is not allowed, so that at least half of the populate servers are available for other (re)populate tasks. On some systems, a value of less than 50 can be problematic, depending on other workload.

This parameter has meaning only if the INMEMORY_SIZE parameter is also set to a positive value.

2.169 INMEMORY_VIRTUAL_COLUMNS

INMEMORY_VIRTUAL_COLUMNS controls which user-defined virtual columns are stored as In-Memory virtual columns (IM columns).

Property	Description
Parameter type	String
Syntax	INMEMORY_VIRTUAL_COLUMNS = { ENABLE | MANUAL | DISABLE }
Default value	MANUAL
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	The same value must be used on all instances.

IM virtual columns improve query performance by avoiding the necessity of repeated calculations. Also, the database can scan and filter IM virtual columns using techniques such as SIMD vector processing.

These values can be set for the parameter:

- ENABLE: For a table or partition that has been enabled for in-memory storage, all virtual columns will be stored in-memory at the default table or partition memcompress level unless:
  - They have been explicitly excluded using the no inmemory syntax.
  - They have been altered to have a different memcompress level than the base table or partition, in which case they will be stored at the specified memcompress level.
- MANUAL: This is the default value for the parameter. For a table or partition that has been enabled for in-memory storage, no virtual columns will be stored in-memory unless:
  - They have been explicitly marked for inmemory, in which case they will be stored in-memory at the table or partition memcompress level.
  - They have been marked for inmemory with a different memcompress level than the base table or partition, in which case they will be stored at the specified memcompress level.
- DISABLE: For a table or partition that has been enabled for in-memory storage, no virtual columns will ever be stored in-memory. Any changes to the inmemory_column_clause for a virtual column including changes in memcompress level will be recorded, but not acted upon with regards to population of virtual columns.

See Also:

- "INMEMORY_EXPRESSIONS_USAGE"
- *Oracle Database In-Memory Guide* for more information about IM virtual columns

2.170 INSTANCE_ABORT_DELAY_TIME

INSTANCE_ABORT_DELAY_TIME specifies how much time to delay an internal initiated instance termination (in seconds), such as when an irrecoverable process dies or an irrecoverable instance error occurs.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	0 and higher
Basic	No
Oracle RAC	Different instances should use the same value.

This parameter does not apply to a SHUTDOWN ABORT operation or any instance termination necessary to implement a user command.

Setting this parameter to a value greater than 0 enables a DBA to take some actions before a termination occurs due to an irrecoverable error. Note that since the instance is in an irrecoverable state, the DBA should not be too ambitious with the actions taken because

some processes and/ or resources may be corrupted or unavailable, making complex actions impossible. Oracle does not guarantee what it is possible when an instance is in this state. A message is written to the alert log when the delayed termination is initiated. The value will not apply in the case of PMON death.

The larger the specified value, the longer the instance stays up, and the potential increases for other problems to occur. If you set this parameter, Oracle recommends setting it to a value between 0 and 60.

2.171 INSTANCE_GROUPS

Used with the `PARALLEL_INSTANCE_GROUP` parameter, `INSTANCE_GROUPS` lets you restrict parallel query operations to a limited number of instances.

Property	Description
Parameter type	String
Syntax	`INSTANCE_GROUPS = group_name [, group_name ] ...`
Default value	There is no default value.
Modifiable	No
Modifiable in a PDB	No
Range of values	One or more instance group names, separated by commas
Basic	No
Oracle RAC	Multiple instances can have different values.

> **Note:**
>
> The `INSTANCE_GROUPS` parameter is deprecated. It is retained for backward compatibility only.

`INSTANCE_GROUPS` is an Oracle RAC parameter that you can specify only in parallel mode.

This parameter specifies one or more instance groups and assigns the current instance to those groups. If one of the specified groups is also specified in the `PARALLEL_INSTANCE_GROUP` parameter, then Oracle allocates query processes for a parallel operation from this instance.

> **See Also:**
>
> - *Oracle Real Application Clusters Administration and Deployment Guide* for more information on parallel query execution in a Real Application Clusters environment
> - "PARALLEL_INSTANCE_GROUP"

2.172 INSTANCE_MODE

INSTANCE_MODE indicates whether the instance is read-write, read-only, or read-mostly.

Property	Description
Parameter type	String
Syntax	INSTANCE_MODE = { READ-WRITE | READ-ONLY | READ-MOSTLY }
Default value	READ-WRITE
Modifiable	No
Basic	No
Oracle RAC	See the Oracle RAC restrictions in the initialization parameter description below.

A READ-WRITE instance is a regular Oracle instance.

A READ-ONLY instance is an Oracle instance that can only be opened in read-only mode.

A READ-MOSTLY instance is an Oracle instance that performs very few database writes.

These restrictions apply when setting the parameter on different Oracle Real Application Clusters (Oracle RAC) instances:

1. There must be at least one running instance with INSTANCE_MODE set to READ-WRITE at any given time. If the only instance with INSTANCE_MODE set to READ-WRITE goes down, all other instances will be brought down by Oracle automatically.
2. An instance with INSTANCE_MODE set to READ-ONLY cannot be the first instance to open a database or any pluggable database (PDB) among all instances in an Oracle RAC cluster.
3. Oracle does not support co-existence of an instance with INSTANCE_MODE set to READ-ONLY and an instance with INSTANCE_MODE set to READ-MOSTLY in the same Oracle RAC cluster.

2.173 INSTANCE_NAME

In an Oracle Real Application Clusters environment, multiple instances can be associated with a single database service. Clients can override Oracle's connection load balancing by specifying a particular instance by which to connect to the database. INSTANCE_NAME specifies the unique name of this instance.

Property	Description
Parameter type	String
Syntax	INSTANCE_NAME = *instance_id*
Default value	The instance's SID **Note:** The SID identifies the instance's shared memory on a host, but may not uniquely distinguish this instance from other instances.
Modifiable	No
Modifiable in a PDB	No

Property	Description
Range of values	Alphanumeric ASCII characters and the underscore (_) character, up to a maximum of 255 characters
Basic	No

In a single-instance database system, the instance name is usually the same as the database name.

> **See Also:**
>
> *Oracle Real Application Clusters Administration and Deployment Guide* and *Oracle Database Net Services Administrator's Guide* for more information

2.174 INSTANCE_NUMBER

`INSTANCE_NUMBER` specifies a unique number that maps the instance to one free list group for each database object created with storage parameter `FREELIST GROUPS`.

Property	Description
Parameter type	Integer
Default value	`0` (zero)
Modifiable	No
Modifiable in a PDB	No
Range of values	1 to maximum number of instances specified when the database was created
Basic	Yes
Oracle RAC	You must set this parameter for every instance, and all instances must have different values.

`INSTANCE_NUMBER` is an Oracle RAC parameter that can be specified in parallel mode or exclusive mode.

The `INSTANCE` parameter of the `ALTER TABLE ... ALLOCATE EXTENT` statement assigns an extent to a particular free list group. If you set `INSTANCE_NUMBER` to the value specified for the `INSTANCE` parameter, the instance uses that extent for inserts and for updates that expand rows.

The practical maximum value of this parameter is the maximum number of instances specified in the `CREATE DATABASE` statement. The absolute maximum is operating system-dependent.

> **See Also:**
>
> *Oracle Real Application Clusters Administration and Deployment Guide* for more information

2.175 INSTANCE_TYPE

`INSTANCE_TYPE` specifies whether the instance is a database instance, an Oracle Automatic Storage Management (Oracle ASM) instance, or an Oracle ASM Proxy instance.

Property	Description
Parameter type	String
Syntax	`INSTANCE_TYPE = { RDBMS | ASM | ASMPROXY }`
Default value	`RDBMS`
Modifiable	No
Modifiable in a PDB	No
Basic	No
Oracle RAC	Multiple instances must have the same value.

Values

- `RDBMS`

  The instance is a database instance.

- `ASM`

  The instance is an Oracle ASM instance.

- `ASMPROXY`

  The instance is an Oracle ASM proxy instance.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for information about managing Oracle Flex ASM

2.176 IORM_LIMIT_POLICY

`IORM_LIMIT_POLICY` specifies the policy for computing the Exadata I/O Resource Management (IORM) share and limit values for pluggable databases.

Property	Description
Parameter type	String

Property	Description
Syntax	IORM_LIMIT_POLICY = { RM_PLAN | CPU_COUNT_RATIO }
Default value	RM_PLAN
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Basic	No
Oracle RAC	Multiple instances should use the same value.

Values:

- RM_PLAN
  - If a CDB resource plan is not specified by the user, that is, the CDB resource plan is set to DEFAULT_CDB_PLAN, then this setting gives equal IORM shares to all PDBs and specifies no utilization limits. If the CPU_MIN_COUNT initialization parameter is set, the IORM share values are determined by using the RAC-wide PDB value of CPU_MIN_COUNT. Otherwise, the IORM share values for each PDB are determined using the RAC-wide PDB value of CPU_COUNT.
  - If a user-defined CDB resource plan has been specified by setting the RESOURCE_MANAGER_PLAN initialization parameter, then the IORM share and utilization limit values for the PDBs are obtained from that resource plan.
- CPU_COUNT_RATIO

  If the CPU_MIN_COUNT initialization parameter is set, the IORM share values are determined by using the RAC-wide PDB value of CPU_MIN_COUNT. Otherwise, the IORM share values for each PDB are determined using the RAC-wide PDB value of CPU_COUNT. In either case, IORM utilization limit values for each PDB are computed as a ratio of the RAC-wide PDB CPU_COUNT to the RAC-wide CDB CPU_COUNT.

The IORM utilization limit applies only to flash devices. It is not applicable for hard disks or XRMEM devices. The utilization limit is used for managing flash IOPS and throughput, and is not used to manage PDB flash cache space usage.

Note:

This parameter allows a third setting, CPU_COUNT_BASED. However, this setting is not supported.

Note:

This parameter is available starting with Oracle Database 23ai.

2.177 JAVA_JIT_ENABLED

JAVA_JIT_ENABLED enables or disables the Just-in-Time (JIT) compiler for the Oracle Java Virtual Machine (OracleJVM) environment.

Property	Description
Parameter type	Boolean
Default value	Operating system-dependent
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	true | false
Basic	No

For platforms that support the JIT compiler, the default value of this parameter is true; otherwise the default value is false. Attempting to set this parameter to true on unsupported platforms will result in an error.

> **See Also:**
>
> *Oracle Database Java Developer's Guide* for more information about setting this parameter

2.178 JAVA_MAX_SESSIONSPACE_SIZE

JAVA_MAX_SESSIONSPACE_SIZE specifies (in bytes) the maximum amount of session space made available to a Java program executing in the server.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	No
Modifiable in a PDB	No
Range of values	0 to 2 GB - 1
Basic	No

Java session space is the memory that holds Java state from one database call to another. When a user's session-duration Java state attempts to exceed the amount specified by JAVA_MAX_SESSIONSPACE_SIZE, the Java virtual machine terminates the session with an out-of-memory failure.

> **See Also:**
>
> - *Oracle Database Java Developer's Guide* for more information about this parameter
> - "JAVA_SOFT_SESSIONSPACE_LIMIT"

2.179 JAVA_POOL_SIZE

`JAVA_POOL_SIZE` specifies (in bytes) the size of the Java pool, from which the Java memory manager allocates most Java state during run-time execution. This memory includes the shared in-memory representation of Java method and class definitions, as well as the Java objects that are migrated to the Java session space at end-of-call.

Property	Description
Parameter type	Big integer
Syntax	`JAVA_POOL_SIZE = integer [K | M | G]`
Default value	If `SGA_TARGET` is set: If the parameter is not specified, then the default is `0` (internally determined by the Oracle Database). If the parameter is specified, then the user-specified value indicates a minimum value for the memory pool. If `SGA_TARGET` is not set: `24` MB, rounded up to the nearest granule size
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	Minimum: `0` (values greater than zero are rounded up to the nearest granule size) Maximum: operating system-dependent
Basic	No

> **See Also:**
>
> *Oracle Database Java Developer's Guide* for more information about this parameter

2.180 JAVA_SOFT_SESSIONSPACE_LIMIT

`JAVA_SOFT_SESSIONSPACE_LIMIT` specifies (in bytes) a **soft limit** on Java memory usage in a session, as a means to warn you if a user's session-duration Java state is using too much memory.

Property	Description
Parameter type	Integer

Property	Description
Default value	0
Modifiable	No
Modifiable in a PDB	No
Range of values	0 to 2 GB - 1
Basic	No

Java session space is the memory that holds Java state from one database call to another. When a user's session-duration Java state exceeds the size specified by JAVA_SOFT_SESSIONSPACE_LIMIT, Oracle generates a warning that goes into the trace files.

See Also:

- *Oracle Database Java Developer's Guide* for more information on this parameter
- "JAVA_MAX_SESSIONSPACE_SIZE"

2.181 JOB_QUEUE_PROCESSES

JOB_QUEUE_PROCESSES specifies the maximum number of job workers per CDB or PDB that can be created for the execution of DBMS_JOB jobs and Oracle Scheduler (DBMS_SCHEDULER) jobs.

Property	Description
Parameter type	Integer
Default value	Derived. The lesser value of: • CPU_COUNT * 20 • SESSIONS / 4 If the result of the above derivation is less than twice the number of open containers in the CDB, then the value of this parameter is adjusted to equal twice the number of open containers in the CDB. Containers include CDB$ROOT, PDB$SEED, PDBs, application roots, application seeds, and application PDBs. You can obtain the number of open containers in a CDB with the following query: `SELECT COUNT(*) FROM V$CONTAINERS WHERE open_mode != 'MOUNTED';`
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	0 to 4000
Basic	No
Oracle RAC	Multiple instances can have different values.

DBMS_JOB and Oracle Scheduler share the same job coordinator and job workers, and they are both controlled by the JOB_QUEUE_PROCESSES parameter. The actual number of job workers created for Oracle Scheduler jobs is auto-tuned by the Scheduler depending on several factors, including available resources, Resource Manager settings, and currently running jobs. However, the combined total number of job workers running DBMS_JOB jobs and Oracle Scheduler jobs in a CDB or PDB can never exceed the value of JOB_QUEUE_PROCESSES for that CDB or PDB.

The default value for JOB_QUEUE_PROCESSES provides a compromise between quality of service for applications and reasonable use of system resources. However, it is possible that the default value does not suit every environment. In such cases, you can use the following guidelines to fine tune this parameter:

- In a CDB root:
  Set JOB_QUEUE_PROCESSES to the maximum number of job workers that can be used simultaneously in the entire CDB. Oracle recommends that you set the value of this parameter to at least twice the number of open containers in the CDB, otherwise, there might be severe starvation between PDBs trying to run multiple jobs. If JOB_QUEUE_PROCESSES is set to 0 in a CDB root, then DBMS_JOB and Oracle Scheduler jobs cannot run in the CDB root or in any PDB, regardless of the JOB_QUEUE_PROCESSES setting at the PDB level.
- In a PDB:
  Set JOB_QUEUE_PROCESSES to the maximum number of job workers that can be used simultaneously in the PDB. The actual number depends on the resources assigned by Resource Manager and the demand in other containers. When multiple PDBs request jobs, Oracle Scheduler attempts to give all PDBs a fair share of the processes. Oracle recommends that you set the value of this parameter to at least 2 in a PDB. However, if you do not want to run DBMS_JOB and Oracle Scheduler jobs in a PDB, then set JOB_QUEUE_PROCESSES to 0 in the PDB.

Materialized views and AutoTask use Oracle Scheduler for automatic refreshes. Setting JOB_QUEUE_PROCESS to 0 will disable these features and any other features that use Oracle Scheduler or DBMS_JOB.

> **Note:**
>
> DBMS_JOB is deprecated in Oracle Database 12*c* Release 2 (12.2.0.1) and may be removed in a future release. Oracle recommends that you use DBMS_SCHEDULER instead.

See Also:

- *Oracle Database PL/SQL Packages and Types Reference* for more information on the `DBMS_SCHEDULER` package
- *Oracle Database Data Warehousing Guide* for more information on managing materialized views
- *Oracle Database Advanced Queuing User's Guide* for more information about job queue processes
- *Oracle Database Administrator's Guide* for more information about the maximum number of scheduler job processes

2.182 JSON_BEHAVIOR

`JSON_BEHAVIOR` specifies the default `ON ERROR` behavior for certain SQL functions that operate on JSON data.

Property	Description
Parameter type	String
Syntax	`JSON_BEHAVIOR = { ON_ERROR:ERROR | ON_ERROR:NULL }`
Default value	None
Modifiable	`ALTER SESSION`
Modifiable in a PDB	No
Basic	No

This parameter is set at the session level and allows you to ensure that JSON queries in a session are valid. This parameter is effective only for SQL functions for which `NULL ON ERROR` is the default behavior: `JSON_QUERY`, `JSON_TABLE` (without the `EXISTS` clause), and `JSON_VALUE`.

Values:

- `ON_ERROR:ERROR` - `ERROR ON ERROR` behavior is the session default for the affected SQL functions.
- `ON_ERROR:NULL` - `NULL ON ERROR` behavior is the session default for the affected SQL functions. This setting is equivalent to having no setting for this parameter.

Example:

The following `JSON_VALUE` query will fail, because the supplied JSON data contains more than one value for property `a`. Because `NULL ON ERROR` is the default behavior for the `JSON_VALUE` function, by default, this query returns null:

```
SQL> SELECT JSON_VALUE('[{a:1},{a:2}]', '$.a');

JSON_VALUE('[{A:1},{A:2}]','$.A')
---------------------------------
```

If you set the JSON_BEHAVIOR parameter to ON_ERROR:ERROR for the session, then the query returns an error:

```
SQL> ALTER SESSION SET JSON_BEHAVIOR = 'ON_ERROR:ERROR';

Session altered.

SQL> SHO PARAMETER JSON_BEHAVIOR

NAME                                 TYPE        VALUE
------------------------------------ -----------
------------------------------
json_behavior                        string      ON_ERROR:ERROR

SQL> SELECT JSON_VALUE('[{a:1},{a:2}]', '$.a');
SELECT JSON_VALUE('[{a:1},{a:2}]', '$.a')
                                           *
ERROR at line 1:
ORA-40470: JSON query '$.a' evaluated to multiple values.
```

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.183 JSON_EXPRESSION_CHECK

Use JSON_EXPRESSION_CHECK to enable or disable JSON query statement checking.

Property	Description
Parameter type	String
Syntax	JSON_EXPRESSION_CHECK = { ON | OFF }
Default value	OFF
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Different instances can use different values.

Set this parameter to ON to enable JSON query statement checking; set it to OFF to disable JSON query statement checking.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

> **See Also:**
>
> *JSON-Relational Duality Developer's Guide* for more information about `JSON_EXPRESSION_CHECK`

2.184 LARGE_POOL_SIZE

`LARGE_POOL_SIZE` specifies (in bytes) the size of the large pool allocation heap.

Property	Description
Parameter type	Big integer
Syntax	`LARGE_POOL_SIZE = integer [K | M | G]`
Default value	If `SGA_TARGET` is set, but a value is not specified for `LARGE_POOL_SIZE`, then the default is `0` (internally determined by the Oracle database). If `LARGE_POOL_SIZE` is specified, then the user-specified value indicates a minimum value for the memory pool. If `SGA_TARGET` is not set, then the default is `0`.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	Minimum: the granule size Maximum: operating system-dependent
Basic	No

The large pool allocation heap is used in shared server systems for session memory, by parallel execution for message buffers, and by backup processes for disk I/O buffers. Parallel execution allocates buffers out of the large pool only when `SGA_TARGET` is set.

You can specify the value of this parameter using a number, optionally followed by K or M to specify kilobytes or megabytes, respectively. If you do not specify K or M, then the number is taken as bytes.

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information on setting this parameter

2.185 LDAP_DIRECTORY_ACCESS

`LDAP_DIRECTORY_ACCESS` specifies whether Oracle refers to Oracle Internet Directory for user authentication information.

> **Note:**
>
> Enterprise User Security (EUS) is deprecated with Oracle Database 23ai.
>
> Oracle recommends that you migrate to using Centrally Managed Users (CMU). This feature enables you to directly connect with Microsoft Active Directory without an intervening directory service for enterprise user authentication and authorization to the database. If your Oracle Database is in the cloud, you can also choose to move to one of the newer integrations with a cloud identity provider.

Property	Description
Parameter type	String
Syntax	`LDAP_DIRECTORY_ACCESS = { NONE | PASSWORD | SSL }`
Default value	`NONE`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

If directory access is turned on, then this parameter also specifies how users are authenticated.

Values

- `NONE`

  Oracle does not refer to Oracle Internet Directory for Enterprise User Security information.

- `PASSWORD`

  Oracle tries to connect to the enterprise directory service using the database password stored in the database wallet. If that fails, then the Oracle Internet Directory connection fails and the database will not be able to retrieve enterprise roles and schema mappings upon enterprise user login.

- `SSL`

  Oracle tries to connect to Oracle Internet Directory using SSL.

> **See Also:**
>
> *Oracle Database Enterprise User Security Administrator's Guide* for more information on Enterprise User Security

Using LDAP_DIRECTORY_ACCESS with PDBs

PDBs can use password or SSL authentication with Oracle Internet Directory for EUS, or Microsoft Active Directory for CMU, when the parameter value is set accordingly.

The `LDAP_DIRECTORY_ACCESS` initialization parameter is PDB-specific and can be set as follows:

- When you use the `ALTER SYSTEM` command to set the value of `LDAP_DIRECTORY_ACCESS` while connected to the CDB root:
  - If you specify the `CONTAINER=ALL` clause, then the setting applies to the CDB root and all PDBs.
  - If you omit the `CONTAINER=ALL` clause, or specify the `CONTAINER=CURRENT` clause, then the setting applies only to the CDB root.
- When you use the `ALTER SYSTEM` command to set the value of `LDAP_DIRECTORY_ACCESS` while connected to a PDB, the setting applies only to that PDB.
- When you set the value of `LDAP_DIRECTORY_ACCESS` in an initialization parameter file, the setting applies only to the CDB root; it does not apply to the PDBs.

For a CDB, if the wallet location is not specified in `sqlnet.ora`, then the default database wallet path is:

`ORACLE_BASE/admin/`*db-unique-name/pdb-GUID*`/wallet` (if `ORACLE_BASE` is set)

or:

`ORACLE_HOME/admin/`*db-unique-name/pdb-GUID*`/wallet` (if `ORACLE_BASE` is not set)

The exception is for the root database, which has a default wallet path of:

`ORACLE_BASE/admin/`*db-unique-name*`/wallet` (if `ORACLE_BASE` is set)

or:

`ORACLE_HOME/admin/`*db-unique-name*`/wallet` (if `ORACLE_BASE` is not set)

All PDBs in a CDB have the same database unique name. By placing wallets in the default location, each PDB can have its own identity.

Note that because there is only one `sqlnet.ora` file for a CDB, the wallet location in `sqlnet.ora` is only used by the CDB root container. Because each PDB must have its own wallet, a PDB wallet will be specified by the *pdb-GUID* under the wallet location in `sqlnet.ora`.

For the root container of a CDB, the wallet location is:

WALLET_LOCATION_specified_in_sqlnet.ora

For each PDB of the CDB, the wallet location is:

WALLET_LOCATION_specified_in_sqlnet.ora/*pdb-GUID*/

> **Note:**
>
> Oracle databases are registered with Oracle Internet Directory using Database Configuration Assistant (DBCA). For registration with Oracle Internet Directory to work, all the PDBs for a CDB must be registered using DBCA.

Using LDAP_DIRECTORY_ACCESS with Non-CDBs

For non-CDBs, if the wallet location is not specified in `sqlnet.ora`, then the default database wallet path is:

`ORACLE_BASE/admin/`*db-unique-name*`/wallet` (if `ORACLE_BASE` is set)

or:

`ORACLE_HOME/admin/`*db-unique-name*`/wallet` (if `ORACLE_BASE` is not set)

> **See Also:**
>
> *Oracle Database Enterprise User Security Administrator's Guide* for an example of setting the value of this parameter to `SSL` in the server parameter file using `ALTER SYSTEM`

2.186 LDAP_DIRECTORY_SYSAUTH

`LDAP_DIRECTORY_SYSAUTH` allows or disallows directory-based authorization for users granted administrative privileges, such as `SYSDBA`, `SYSOPER`, `SYSBACKUP`, `SYSDG`, and `SYSKM`.

Property	Description
Parameter type	String
Syntax	`LDAP_DIRECTORY_SYSAUTH = { yes | no }`
Default value	`no`
Modifiable	No
Modifiable in a PDB	Yes
Basic	Yes

When `LDAP_DIRECTORY_SYSAUTH` is set to `yes`, directory users are allowed to connect to the database as `SYSDBA`, `SYSOPER`, `SYSBACKUP`, `SYSDG`, or `SYSKM`, if they have mapped database global users that are granted corresponding administrative privileges such as `SYSDBA`, `SYSOPER`, `SYSBACKUP`, `SYSDG`, and `SYSKM`.

When LDAP_DIRECTORY_SYSAUTH is set to no, directory users are not allowed to connect to the database as SYSDBA, SYSOPER, SYSBACKUP, SYSDG, or SYSKM, even if they have mapped database global users that are granted corresponding administrative privileges such as SYSDBA, SYSOPER, SYSBACKUP, SYSDG, and SYSKM.

When modifying this parameter in a PDB, use the ALTER SYSTEM command with SCOPE=SPFILE.

2.187 LICENSE_MAX_SESSIONS

LICENSE_MAX_SESSIONS specifies the maximum number of concurrent user sessions allowed.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	0 to number of session licenses
Basic	No
Oracle RAC	Multiple instances can have different values, but the total for all instances mounting a database should be less than or equal to the total number of sessions licensed for that database.

Note:

Oracle no longer offers licensing by the number of concurrent sessions. Therefore the LICENSE_MAX_SESSIONS and LICENSE_SESSIONS_WARNING initialization parameters have been deprecated.

When the limit specified by LICENSE_MAX_SESSIONS is reached, only users with the RESTRICTED SESSION privilege can connect to the database. Users who are not able to connect receive a warning message indicating that the system has reached maximum capacity.

A zero value indicates that concurrent usage (session) licensing is not enforced. If you set this parameter to a nonzero number, you might also want to set LICENSE_SESSIONS_WARNING (see "LICENSE_SESSIONS_WARNING").

Do not enable both concurrent usage licensing and user licensing. Set either LICENSE_MAX_SESSIONS or LICENSE_MAX_USERS to zero.

See Also:

Oracle Database Administrator's Guide for more information about this parameter

2.188 LICENSE_MAX_USERS

`LICENSE_MAX_USERS` specifies the maximum number of users you can create in the database.

Property	Description
Parameter type	Integer
Default value	`0`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	0 to number of user licenses
Basic	No
Oracle RAC	Oracle recommends that multiple instances have the same value.

When you reach the limit specified by `LICENSE_MAX_USERS`, you cannot create more users. You can, however, increase the limit.

> **Note:**
>
> Oracle no longer offers licensing by the number of concurrent sessions. Therefore the `LICENSE_MAX_SESSIONS` and `LICENSE_SESSIONS_WARNING` initialization parameters have been deprecated.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about this parameter

2.189 LICENSE_SESSIONS_WARNING

`LICENSE_SESSIONS_WARNING` specifies a warning limit on the number of concurrent user sessions.

Property	Description
Parameter type	Integer
Default value	`0`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	0 to value of `LICENSE_MAX_SESSIONS` parameter
Basic	No

Property	Description
Oracle RAC	Multiple instances can have different values.

> **Note:**
>
> Oracle no longer offers licensing by the number of concurrent sessions. Therefore the LICENSE_MAX_SESSIONS and LICENSE_SESSIONS_WARNING initialization parameters have been deprecated.

When this limit specified by LICENSE_SESSIONS_WARNING is reached, additional users can connect, but Oracle writes a message in the alert log for each new connection. Users with RESTRICTED SESSION privilege who connect after the limit is reached receive a warning message stating that the system is nearing its maximum capacity.

If this parameter is set to zero, no warning is given as you approach the concurrent usage (session) limit. If you set this parameter to a nonzero number, you should also set LICENSE_MAX_SESSIONS (see "LICENSE_MAX_SESSIONS").

> **See Also:**
>
> - *Oracle Database Administrator's Guide* for more information on setting this parameter

2.190 LISTENER_NETWORKS

LISTENER_NETWORKS specifies one or more sets of local, forward, and remote listeners for cross-registration. All listeners within the same *network_name* will cross-register.

Property	Description
Parameter type	String
Syntax	LISTENER_NETWORKS = '((NAME=*network_name*) (LOCAL_LISTENER=["]*listener_address*[,...]["]) (FORWARD_LISTENER=["]*listener_address*[,...]["]) [(REMOTE_LISTENER=["]*listener_address*[,...]["])])' [,...]
Default value	There is no default value.
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No

If a *network_name* is specified multiple times, then the resulting listener set is the union of each specification. This can be used to specify sets that require more than 255 characters, which is the per element limit.

The *listener_address* specifies a string that is an address, address list, or an alias that resolves to an address or address list of Oracle Net listeners. If an alias, the address or address list is specified in the TNSNAMES.ORA file or another address repository as configured for your system.

If a comma is used to specify a *listener_address* list, then the set of addresses must be surrounded by double quotes.

See Also:

- "LOCAL_LISTENER"
- "FORWARD_LISTENER"
- "REMOTE_LISTENER"
- *Oracle Database Net Services Administrator's Guide* for more information on setting this parameter

2.191 LOB_SIGNATURE_ENABLE

`LOB_SIGNATURE_ENABLE` is used to enable or disable the LOB locator signature feature.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No
Oracle RAC	Multiple instances must have the same value.

You can secure your LOBs by enabling the LOB locator signature feature. A LOB locator is a pointer to the location of a large object (LOB) value. If the `LOB_SIGNATURE_ENABLED` initialization parameter is set to `true`, then when you create a LOB, Oracle Database automatically assigns a signature to the LOB locator. When Oracle Database receives a request from a client, it uses the signature to determine if any tampering with the LOB locator has occurred.

When this parameter is set to `true`, you also have the option of further securing your LOBs by encrypting your LOB locator signature keys.

> **See Also:**
>
> *Oracle Database Security Guide* for more information on LOB locator signatures and encrypting LOB locator signature keys

2.192 LOCAL_LISTENER

`LOCAL_LISTENER` specifies a network name that resolves to an address or address list of Oracle Net local listeners (that is, listeners that run on the same system as this instance). The address or address list is specified in the `TNSNAMES.ORA` file or other address repository as configured for your system.

Property	Description
Parameter type	String
Syntax	`LOCAL_LISTENER = network_name`
Default value	`(ADDRESS = (PROTOCOL=TCP)(HOST=hostname)(PORT=1521))` where *hostname* is the network name of the local host.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

> **See Also:**
>
> - *Oracle Database Concepts* for more information about listener processes and dispatcher processes
> - *Oracle Database Net Services Administrator's Guide* and your operating system-specific Oracle documentation for more information about specifying network addresses for the protocols on your system

2.193 LOCK_NAME_SPACE

`LOCK_NAME_SPACE` specifies the namespace that the distributed lock manager (DLM) uses to generate lock names.

Property	Description
Parameter type	String
Syntax	`LOCK_NAME_SPACE = namespace`
Default value	There is no default value.
Modifiable	No
Modifiable in a PDB	No
Range of values	Up to 8 alphanumeric characters. No special characters allowed.

Property	Description
Basic	No

> **Note:**
>
> The `LOCK_NAME_SPACE` parameter is deprecated. It is retained for backward compatibility only.

Consider setting this parameter if a standby or clone database has the same database name on the same cluster as the primary database.

If the standby database resides on the same file system as the primary database, then set `LOCK_NAME_SPACE` in the standby parameter file to a distinct value such as the following:

```
LOCK_NAME_SPACE = standby
```

2.194 LOCK_SGA

`LOCK_SGA` locks the entire SGA into physical memory.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No

It is usually advisable to lock the SGA into real (physical) memory, especially if the use of virtual memory would include storing some of the SGA using disk space. This parameter is ignored on platforms that do not support it.

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about using this parameter

2.195 LOG_ARCHIVE_CONFIG

`LOG_ARCHIVE_CONFIG` enables or disables the sending of redo logs to remote destinations and the receipt of remote redo logs, and specifies the unique database names (`DB_UNIQUE_NAME`) for each database in the Data Guard configuration.

Property	Description
Parameter type	String

Syntax	LOG_ARCHIVE_CONFIG =
	{
	[SEND | NOSEND]
	[RECEIVE | NORECEIVE]
	[DG_CONFIG=(*remote_db_unique_name1* [, ...
	remote_db_unique_name30) | NODG_CONFIG]
	}

Default value	NULL
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Basic	No

Values

- SEND

  Enables the sending of redo logs to remote destinations

- NOSEND

  Disables the sending of redo logs to remote destinations

- RECEIVE

  Enables the receipt of remotely archived redo logs

- NORECEIVE

  Disables the receipt of remotely archived redo logs

- DG_CONFIG

  Specifies a list of up to 30 unique database names (defined with the DB_UNIQUE_NAME initialization parameter) for all of the databases in the Data Guard configuration.

- NODG_CONFIG

  Eliminates the list of service provider names previously specified with the DG_CONFIG option.

When this parameter has not been set, its default value is NULL. However, the NULL value is treated as if the parameter has been set to 'SEND, RECEIVE, NODG_CONFIG'.

2.196 LOG_ARCHIVE_DEST

Use LOG_ARCHIVE_DEST to specify the destination to which redo log files will be archived.

Property	Description
Parameter type	String
Syntax	LOG_ARCHIVE_DEST = *filespec*
Default value	Null

Property	Description
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	Any valid path or device name, except raw partitions
Basic	No
Oracle RAC	Multiple instances can have different values.

> **Note:**
>
> For Enterprise Edition users, this parameter has been deprecated in favor of the LOG_ARCHIVE_DEST_*n* parameters. If Oracle Enterprise Edition is not installed or it is installed, but you have not specified any LOG_ARCHIVE_DEST_*n* parameters, this parameter is valid.

LOG_ARCHIVE_DEST is applicable only if you are running the database in ARCHIVELOG mode or are recovering a database from archived redo logs. LOG_ARCHIVE_DEST is incompatible with the LOG_ARCHIVE_DEST_*n* parameters, and must be defined as the null string ("") or (' ') when any LOG_ARCHIVE_DEST_*n* parameter has a value other than a null string. Use a text string to specify the default location and root of the disk file or tape device when archiving redo log files. (Archiving to tape is not supported on all operating systems.) The value cannot be a raw partition.

If LOG_ARCHIVE_DEST is not explicitly defined and all the LOG_ARCHIVE_DEST_*n* parameters have null string values, LOG_ARCHIVE_DEST is set to an operating system-specific default value on instance startup.

To override the destination that this parameter specifies, either specify a different destination for manual archiving or use the SQL*Plus statement ARCHIVE LOG START *filespec* for automatic archiving, where *filespec* is the new archive destination. To permanently change the destination, use the statement ALTER SYSTEM SET LOG_ARCHIVE_DEST = *filespec*, where *filespec* is the new archive destination.

Neither LOG_ARCHIVE_DEST nor LOG_ARCHIVE_FORMAT have to be complete file or directory specifiers themselves; they only need to form a valid file path after the variables are substituted into LOG_ARCHIVE_FORMAT and the two parameters are concatenated together.

See Also:

- *Oracle Database Backup and Recovery User's Guide*
- "LOG_ARCHIVE_DUPLEX_DEST", "LOG_ARCHIVE_MIN_SUCCEED_DEST", and "V$ARCHIVE_DEST" for more information on setting this parameter
- Your Oracle operating system-specific documentation for the default value and for an example of how to specify the destination path or file name using `LOG_ARCHIVE_DEST`

2.197 LOG_ARCHIVE_DEST_*n*

The `LOG_ARCHIVE_DEST_n` initialization parameter defines up to 31 (where `n` = 1, 2, 3, ... 31) destinations, each of which *must* specify either the `LOCATION` or the `SERVICE` attribute to specify where to archive the redo data.

Property	Description
Parameter type	String

Syntax	`LOG_ARCHIVE_DEST_[1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31] =`
	`{ null_string |`
	`{ LOCATION=path_name | SERVICE=service_name }`
	`[ MANDATORY ]`
	`[ REOPEN[=seconds] ]`
	`[ DELAY[=minutes] ]`
	`[ ENCRYPTION=ENABLED|DISABLED ]`
	`[ GROUP=group ]`
	`[ NOREGISTER ]`
	`[ PRIORITY=priority ]`
	`[ TEMPLATE=template ]`
	`[ ALTERNATE=destination ]`
	`[ MAX_FAILURE=count ]`
	`[ SYNC | ASYNC ]`
	`[ AFFIRM | NOAFFIRM ]`
	`[ NET_TIMEOUT=seconds ]`
	`[ VALID_FOR=(redo_log_type,database_role) ]`
	`[ DB_UNIQUE_NAME ]`
	`[ COMPRESSION={ENABLE|DISABLE|ZLIB|LZO} ]`
	`}`

Default value	There is no default value.
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	No
Basic	Yes

All other attributes except the `LOCATION` or `SERVICE` attributes are optional. Note that whether you are specifying the `LOCATION` attribute or the `SERVICE` attribute, it must be the first attribute supplied in the list of attributes.

If you choose not to enter any attributes, then you can specify a NULL string by entering the following:

```
LOG_ARCHIVE_DEST_n=' ';
```

You set the attributes for the LOG_ARCHIVE_DEST_*n* initialization parameter to control different aspects of how redo transport services transfer redo data from a production or primary database destination to another (standby) database destination. You can query the V$ARCHIVE_DEST view to see the current attribute settings for each destination (n).

> **Note:**
>
> Some of the attributes for this parameter are deprecated, but are being retained for backward compatibility. See "Deprecated Attributes for LOG_ARCHIVE_DEST_n".

For every LOG_ARCHIVE_DEST_n initialization parameter that you define, you must specify a corresponding LOG_ARCHIVE_DEST_STATE_n parameter. The LOG_ARCHIVE_DEST_STATE_n (where n is an integer from 1 to 31) initialization parameter specifies whether the corresponding destination is currently enabled or disabled.

> **See Also:**
>
> "LOG_ARCHIVE_DEST_STATE_*n*"

Destinations LOG_ARCHIVE_DEST_11 through LOG_ARCHIVE_DEST_31 do not support the SYNC, ARCH, LOCATION, MANDATORY, or ALTERNATE attributes, and cannot be specified as the target of the ALTERNATE attribute.

LOG_ARCHIVE_DEST_11 through LOG_ARCHIVE_DEST_31 can only be used when the COMPATIBLE initialization parameter is set to 11.2.0 or higher.

Values

> **See Also:**
>
> *Oracle Data Guard Concepts and Administration* for detailed descriptions of all the values listed in this section

- AFFIRM and NOAFFIRM

  Control whether a redo transport destination acknowledges received redo data before or after writing it to the standby redo log. The default is NOAFFIRM.

- ALTERNATE=LOG_ARCHIVE_DEST_*n*

Specifies an alternate archiving destination to be used when the original destination fails. There is no default value; if an alternate destination is not specified, then archiving does not automatically change to another destination if the original destination fails.

- ASYNC

  The redo data generated by a transaction need not have been received at a destination which has this attribute before that transaction can commit. This is the default behavior if neither SYNC nor ASYNC is specified.

- COMPRESSION

  Indicates whether network compression is enabled or disabled, or disabled, or whether the ZLIB or LZO algorithm is used. The possible values include:

  – DISABLE: Compression is disabled.
  – ENABLE: Compression is enabled. The ZLIB compression algorithm is used.
  – ZLIB: ZLIB compression is used.
  – LZO: LZO compression is used.

  The Advanced Compression option is required in order to use the COMPRESSION attribute.

- DB_UNIQUE_NAME=*name*

  Specifies a unique name for the database at this destination. You must specify a name; there is no default value.

- DELAY[=*minutes*]

  Specifies a minimum time lag between when redo data is archived on a standby site retrieving redo from a primary and when the archived redo log file is applied to the standby database or any standbys cascading from it. If you specify the DELAY attribute without a time interval, the default is 30 minutes.

- ENCRYPTION=DISABLE|ENABLE

  Controls whether encryption of the redo stream sent to Zero Data Loss Recovery Appliance (Recovery Appliance) is enabled or disabled. The default value for the attribute is DISABLE.

  This attribute cannot be used with the COMPRESSION, LOCATION, or SYNC attributes.

  To use the ENCRYPTION attribute, you must set the COMPATIBLE initialization parameter to 11.2.0.4 or higher on the protected database.

  > **See Also:**
  >
  > *Zero Data Loss Recovery Appliance Administrator's Guide* for introductory information about Recovery Appliance

- GROUP=*group*

  The GROUP attribute is used to specify membership in a specific collection of log archive destinations. Groups are numbered 1 through 8. The default group (GROUP=0) is special in that it cannot be assigned. The default group is populated with all destinations that are not explicitly assigned to a group. All groups other than the default group must consist of a set of remote destinations. No group (other than the default group) can contain local destinations.

- LOCATION=*local_disk_directory* or USE_DB_RECOVERY_FILE_DEST

  Specifies either a local file system destination or the directory, file system, or Automatic Storage Management disk group that will serve as the fast recovery area. You must specify this attribute for at least one destination. You can specify either a local disk directory or fast recovery area with the LOCATION attribute. You *must* include either the LOCATION or the SERVICE attribute for each destination to specify where to archive the redo data.

- MANDATORY

  Specifies that the transmission of redo data to the destination must succeed before the local online redo log file can be made available for reuse. If the MANDATORY attribute is not specified, then the destination is optional.

- MAX_FAILURE

  Controls the consecutive number of times redo transport services attempt to reestablish communication and transmit redo data to a failed destination before the primary database gives up on the destination. See the MAX_FAILURE description in *Oracle Data Guard Concepts and Administration* for usage notes about how this attribute is handled differently in Oracle Database 12*c* Release 2 (12.2.0.1) and in Oracle Database 12*c* Release 1 (12.1.0.2).

- NET_TIMEOUT=*seconds*

  Specifies the number of seconds the log writer process on the primary system waits for status from the SYNC (NSS*n*) process before terminating the network connection. The default is 30 seconds.

- NOREGISTER

  Indicates that the location of the archived redo log file is not to be recorded at the corresponding destination.

- PRIORITY=*priority*

  The PRIORITY attribute is used to specify preference within a group of log archive destinations. Priorities are numbered 1 through 8. A lower value represents a higher priority. The lowest priority (PRIORITY=8) is special in the sense that if that priority is active then all destinations at that priority will be made active. If any higher priority destination returns to service then that destination will be made active and all low priority destinations will be made inactive because they will be receiving redo from one of the other redo destinations, either through cascading or a Far Sync.

- REOPEN[=*seconds*]

  Specifies the minimum number of seconds before the archiver processes (ARC*n*) or the log writer process (LGWR) should try again to access a previously failed destination. The default is 300 seconds.

- SERVICE=*net_service_name*

  Specifies a valid Oracle Net service name (SERVICE=*net_service_name*) that identifies the remote Oracle database instance to which redo data will be sent. Each destination *must* specify either the LOCATION or the SERVICE attribute. There is no default net service name.

- SYNC

The redo data generated by a transaction must have been received by every enabled destination which has this attribute before that transaction can commit.

- `TEMPLATE=`*filename_template*`_%t_%s_%r`

  Specifies a path name and a file name template for archived redo log files created at a redo transport destination that contain redo data from the database where this attribute is specified. This attribute overrides the value of the `LOG_ARCHIVE_FORMAT` initialization parameter at a redo transport destination. This attribute does not have a default value.

- `VALID_FOR=(redo_log_type, database_role)`

  Identifies when redo transport services can transmit redo data to destinations based on the following factors:

  - `redo_log_type`—whether online redo log files, standby redo log files, or both are *currently* being archived on the database at this destination
  - `database_role`—whether the database is *currently* running in the primary or the standby role

Deprecated Attributes for LOG_ARCHIVE_DEST_n

The following attributes are deprecated for the `LOG_ARCHIVE_DEST_`*n* parameter. They are retained for backward compatibility only.

Table 2-3 Deprecated Attributes on the LOG_ARCHIVE_DEST_n Initialization Parameter

Deprecated Attribute	Alternative
`ARCH`	Specify `SYNC` or `ASYNC`. `ASYNC` is the default if neither attribute is specified.
`LGWR`	Specify `SYNC` or `ASYNC`. `ASYNC` is the default if neither attribute is specified.
`OPTIONAL`	Destinations are optional by default.
`VERIFY`	None. This attribute is only used with the deprecated `ARCH` attribute.

In addition, note the following changes to the `ASYNC` and `SYNC` attributes:

- The `BLOCKS` keyword on the `ASYNC` attribute is no longer needed.

  It is no longer necessary to set this keyword because Data Guard dynamically adjusts the block count up or down to an appropriate number of blocks, as necessary.

- The `PARALLEL` and `NOPARALLEL` keywords on the `SYNC` attribute are no longer needed.

2.198 LOG_ARCHIVE_DEST_STATE_*n*

The `LOG_ARCHIVE_DEST_STATE_`*n* parameters (where *n* = 1, 2, 3, ... 31) specify the availability state of the corresponding destination.

Property	Description
Parameter type	String

Property	Description
Syntax	`LOG_ARCHIVE_DEST_STATE_[1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 | 27 | 28 | 29 | 30 | 31] = { enable | defer | alternate | reset }`
Default value	`enable`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	No
Basic	Yes

The parameter suffix (1 through 31) specifies one of the corresponding `LOG_ARCHIVE_DEST_`*n* destination parameters.

Values

- `enable`

  Specifies that a valid log archive destination can be used for a subsequent archiving operation (automatic or manual). This is the default.

- `defer`

  Specifies that valid destination information and attributes are preserved, but the destination is excluded from archiving operations until reenabled.

- `alternate`

  Specifies that a log archive destination is not enabled but will become enabled if communications to another destination fail.

- `reset`

  Functions the same as `defer`, but clears any error messages for the destination if it had previously failed.

The `LOG_ARCHIVE_DEST_STATE_`*n* parameters have no effect on the `ENABLE` state for the `LOG_ARCHIVE_DEST` or `LOG_ARCHIVE_DUPLEX_DEST` parameters.

The `V$ARCHIVE_DEST` dynamic performance view shows values in use for the current session. The `DEST_ID` column of that view corresponds to the archive destination suffix *n*.

See Also:

- *Oracle Data Guard Concepts and Administration* for more information about this parameter
- "V$ARCHIVE_DEST"

2.199 LOG_ARCHIVE_DUPLEX_DEST

`LOG_ARCHIVE_DUPLEX_DEST` is similar to the initialization parameter `LOG_ARCHIVE_DEST`. This parameter specifies a second archive destination: the **duplex** archive destination. This duplex archive destination can be either a must-succeed or a best-effort archive destination, depending on how many archive destinations must succeed (as specified in the `LOG_ARCHIVE_MIN_SUCCEED_DEST` parameter).

Property	Description
Parameter type	String
Syntax	`LOG_ARCHIVE_DUPLEX_DEST = filespec`
Default value	There is no default value.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	Either a null string or any valid path or device name, except raw partitions
Basic	No

Note:

If you are using Oracle Enterprise Edition, this parameter is deprecated in favor of the `LOG_ARCHIVE_DEST_n` parameters. If Oracle Enterprise Edition is not installed or it is installed but you have not specified any `LOG_ARCHIVE_DEST_n` parameters, this parameter is valid.

The default setting of a null string ("") or (' ') indicates that a duplex archive destination does not exist.

See Also:

- "LOG_ARCHIVE_DEST_*n*"
- "LOG_ARCHIVE_MIN_SUCCEED_DEST"
- "V$ARCHIVE_DEST"
- *Oracle Database Administrator's Guide* for an example of using this parameter to specify an optional secondary archive destination

2.200 LOG_ARCHIVE_FORMAT

Use `LOG_ARCHIVE_FORMAT` to specify the default filename format when archiving redo log files.

Property	Description
Parameter type	String

Property	Description
Syntax	LOG_ARCHIVE_FORMAT = *filename*
Default value	Operating system-dependent
Modifiable	No
Modifiable in a PDB	No
Range of values	Any string that resolves to a valid filename
Basic	No
Oracle RAC	Multiple instances can have different values, but identical values are recommended.

LOG_ARCHIVE_FORMAT is applicable only if you are using the redo log in ARCHIVELOG mode. Use a text string and variables to specify the default filename format when archiving redo log files. The string generated from this format is appended to the string specified in the LOG_ARCHIVE_DEST parameter.

The following variables can be used in the format:

%s log sequence number

%S log sequence number, zero filled

%t thread number

%T thread number, zero filled

%a activation ID

%d database ID

%r resetlogs ID that ensures unique names are constructed for the archived log files across multiple incarnations of the database

Using uppercase letters for the variables (for example, %S) causes the value to be fixed length and padded to the left with zeros. An example of specifying the archive redo log filename format follows:

```
LOG_ARCHIVE_FORMAT = 'log%t_%s_%r.arc'
```

Archive log file names must contain each of the elements %s (sequence), %t (thread), and %r (resetlogs ID) to ensure that all archive log file names are unique. If the LOG_ARCHIVE_FORMAT initialization parameter is set in the parameter file, then make sure the parameter value contains the %s, %t, and %r elements. Otherwise, the following error is displayed at the time of instance startup:

```
ORA-19905: log_archive_format must contain %s, %t and %r
```

Neither LOG_ARCHIVE_DEST nor LOG_ARCHIVE_FORMAT have to be complete file or directory specifiers themselves; they only need to form a valid file path after the variables are substituted into LOG_ARCHIVE_FORMAT and the two parameters are concatenated together.

LOG_ARCHIVE_FORMAT is ignored in these cases:

- For archived log files that go to the fast recovery area

- When LOG_ARCHIVE_DEST[_n] points to the root of an Oracle ASM disk group (for example, +DATA). The directory of a disk group (for example, +DATA/logs) must be specified for the parameter to be honored.

In these cases where LOG_ARCHIVE_FORMAT is ignored, an Oracle ASM file name is used. See *Oracle Automatic Storage Management Administrator's Guide* for more information on Oracle ASM file names.

See Also:

- *Oracle Database Backup and Recovery User's Guide*, *Oracle Data Guard Concepts and Administration*, and *Oracle Real Application Clusters Administration and Deployment Guide* for more information about this parameter
- Your operating system- specific Oracle documentation for the default value and range of values for LOG_ARCHIVE_FORMAT

2.201 LOG_ARCHIVE_MAX_PROCESSES

LOG_ARCHIVE_MAX_PROCESSES specifies the maximum number of ARC*n* processes that can be created.

Property	Description
Parameter type	Integer
Default value	4
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	1 to 30
Basic	No

See Also:

- "Background Processes" for more information about ARC*n* processes
- *Oracle Database Administrator's Guide* for more information about LOG_ARCHIVE_MAX_PROCESSES

2.202 LOG_ARCHIVE_MIN_SUCCEED_DEST

LOG_ARCHIVE_MIN_SUCCEED_DEST defines the minimum number of destinations that must succeed in order for the online logfile to be available for reuse.

Property	Description
Parameter type	Integer
Default value	1
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	1 to 10 if you are using LOG_ARCHIVE_DEST_*n* 1 or 2 if you are using LOG_ARCHIVE_DEST and LOG_ARCHIVE_DUPLEX_DEST
Basic	No

If you are using the LOG_ARCHIVE_DEST_*n* parameters and automatic archiving is enabled, then the value of this parameter cannot exceed the number of enabled, valid destinations specified as MANDATORY plus the number of enabled, valid destinations that are configured with the OPTIONAL and LOCATION attributes.

If you are using LOG_ARCHIVE_DEST and LOG_ARCHIVE_DUPLEX_DEST and automatic archiving is enabled, a value of 1 specifies that the destination specified in LOG_ARCHIVE_DEST must succeed. A value of 2 specifies that the destinations specified in both parameters must succeed.

If the value of this parameter is less than the number of enabled, valid MANDATORY destinations, this parameter is ignored in favor of the MANDATORY destination count. If the value is more than the number of enabled, valid MANDATORY destinations, then some of the enabled, valid destinations configured with the OPTIONAL and LOCATION attributes are treated as MANDATORY.

You can switch dynamically from using the older parameters to the LOG_ARCHIVE_DEST_*n* parameter using ALTER SYSTEM, as follows:

1. Set LOG_ARCHIVE_MIN_SUCCEED_DEST to 1.
2. Set the value of LOG_ARCHIVE_DEST and LOG_ARCHIVE_DUPLEX_DEST to the null string.
3. Set the desired number of destinations for the LOG_ARCHIVE_DEST_*n* parameters.
4. Reset LOG_ARCHIVE_MIN_SUCCEED_DEST to the desired value.

See Also:

- *Oracle Database Administrator's Guide* for more information on setting this parameter
- "LOG_ARCHIVE_DEST_*n*", "LOG_ARCHIVE_DUPLEX_DEST", and "V$ARCHIVE_DEST" for information on related parameters

2.203 LOG_ARCHIVE_TRACE

LOG_ARCHIVE_TRACE enables and controls the generation of comprehensive trace information for log archiving and redo transport activity.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	0, 1, 2, 4, 8, 16, 32, 64, 128, 256, 512, 1024, 2048, 4096, 8192, 16384, 32768
Basic	No
Oracle RAC	Multiple instances can have different values.

The additional tracing that is output when setting LOG_ARCHIVE_TRACE to a non-zero value can appear in trace files for an archive process, RFS process, LGWR process, SYNC process, ASYNC process, foreground process, MRP process, recovery process, log apply process, startup process, shutdown process, and other processes that use redo transport services.

Table 2-4 describes the valid LOG_ARCHIVE_TRACE values.

Table 2-4 LOG_ARCHIVE_TRACE Values

Value	Description	More Information
0	Disables archivelog tracing (this is the default)	
1	High-level tracing	High-level tracing provides a small amount of tracing from most redo transport processes. When a value is specified that is not high-level (not 1), the high-level tracing for that value will be output to the trace file even if the high-level tracing has not been specifically requested. For example, if you set LOG_ARCHIVE_TRACE to 128, you will get all the trace messages pertaining to the FAL engine, *including* the high-level tracing from the FAL engine.
2	Tracks Data Guard interfaces	This tracing level is for the various Data Guard configuration parameters, the various Data Guard related SQL commands, the various Data Guard table accesses, and some Data Guard internal interfaces.

Table 2-4 (Cont.) LOG_ARCHIVE_TRACE Values

Value	Description	More Information
4	Tracks common redo transport services	This tracing level is for a number of common services provided by redo transport to various internal users (such as the RFS process, the LGWR process, and the ASYNC process). These include locking primitives, use of common VOS (Virtual Operating System) interfaces, task scheduling, process monitoring, control file access, and other miscellaneous common services.
8	Tracks database protection mode	
16	Tracks disk and network I/O requests	
32	Tracks redo transport destinations	
64	Tracks redo transport archive engine	
128	Tracks redo transport FAL (fetch archive log) engine	
256	Tracks Physical, Logical, and Availability Machine clients of RFS process	
512	Tracks redo transport of LGWR, SYNC, and ASYNC processes	
1024	Tracks redo transport RFS process	
2048	Tracks redo transport gap resolution	
4096	Tracks real-time apply	
8192	Tracks recovery process	
16384	Tracks redo transport buffer management	
32768	Tracks LogMiner dictionary	

You can combine tracing levels by adding together the values of the desired tracing levels. For example, a setting of 3 will generate level 1 and level 2 trace output. You can set different values for the primary and standby database.

When this parameter is set to the default value of 0, Oracle will still generate appropriate alert and trace entries in response to error conditions. If you change the value of this parameter dynamically in an `ALTER SYSTEM` statement, the change takes effect immediately.

Many of the trace messages from redo transport processes include a routine name at the beginning of the trace message. The first part of the routine name specifies the module for that routine. Table 2-5 shows the tracing value used for each redo transport module. Note that the tracing value for transport modules can change from release to release.

Table 2-5 Tracing Values Used for Redo Transport Modules

Module Name	Purpose	Tracing Value
krsa	Locking primitives	4
krsb	Buffer management	16384
krsc	Crash recovery	64
krsd	Destination	32
krse	Archive engine	64
krsf	FAL engine	128
krsg	Gap resolution	2048
krsh	Helper	4
krsi	Input/output	16
krsj	Protection mode	8
krsk	Control file access	4
krsl	Log writer	512
krsm	MRP process	8192
krsn	Configuration	2
krso	Process monitor	4
krsp	Physical standby and Availability Machine RFS client	256
krsq	SQL commands	2
krsr	RFS process	1024
krst	Tables	2
krsu	Network I/O	16
krsv	VOS front end	4
krsw	ASYNC process	512
krsx	Internal interfaces	2

See Also:

Oracle Database Administrator's Guide

2.204 LOG_BUFFER

`LOG_BUFFER` specifies the amount of memory (in bytes) that Oracle uses when buffering redo entries to a redo log file.

Property	Description
Parameter type	Big integer
Default value	2 MB to 32 MB, depending on the SGA size and CPU count

Property	Description
Modifiable	No
Modifiable in a PDB	No
Range of values	2 MB to operating system-dependent
Basic	No

Redo log entries contain a record of the changes that have been made to the database block buffers. The LGWR process writes redo log entries from the log buffer to a redo log file.

The log buffer size depends on the number of redo strands in the system. One redo strand is allocated for every 16 CPUs and has a default size of 2 MB. Oracle allocates a minimum of 2 redo strands per instance. When the log buffer size is not specified, any remaining memory in the redo granules is given to the log buffer.

See Also:

- Your operating system-specific Oracle documentation for the default value and range of values
- *Oracle Database Performance Tuning Guide* for information on resizing the redo log buffer using this parameter

2.205 LOG_CHECKPOINT_INTERVAL

`LOG_CHECKPOINT_INTERVAL` specifies the frequency of checkpoints in terms of the number of redo log file blocks that can exist between an incremental checkpoint and the last block written to the redo log. This number refers to physical operating system blocks, not database blocks.

Property	Description
Parameter type	Integer
Default value	`0`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	`0` to $2^{31} - 1$
Basic	No
Oracle RAC	Multiple instances can have different values.

Regardless of this value, a checkpoint always occurs when switching from one online redo log file to another. Therefore, if the value exceeds the actual redo log file size, checkpoints occur only when switching logs. Checkpoint frequency is one of the factors that influence the time required for the database to recover from an unexpected failure.

Note:

- Specifying a value of `0` (zero) for `LOG_CHECKPOINT_INTERVAL` has the same effect as setting the parameter to infinity and causes the parameter to be ignored. Only nonzero values of this parameter are considered meaningful.
- Recovery I/O can also be limited by setting the `LOG_CHECKPOINT_TIMEOUT` parameter or by the size specified for the smallest redo log. For information on which mechanism is controlling checkpointing behavior, query the `V$INSTANCE_RECOVERY` view.

See Also:

- "LOG_CHECKPOINT_TIMEOUT"
- "V$INSTANCE_RECOVERY"
- *Oracle Database Performance Tuning Guide* for information on disabling or removing this parameter when the `FAST_START_MTTR_TARGET` parameter is set

2.206 LOG_CHECKPOINT_TIMEOUT

`LOG_CHECKPOINT_TIMEOUT` specifies (in seconds) the amount of time that has passed since the incremental checkpoint at the position where the last write to the redo log (sometimes called the **tail of the log**) occurred. This parameter also signifies that no buffer will remain dirty (in the cache) for more than *integer* seconds.

Property	Description
Parameter type	Integer
Default value	`1800`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	`0` to 2^{31} - 1
Basic	No
Oracle RAC	Multiple instances can have different values.

Specifying a value of `0` for the timeout disables time-based checkpoints. Hence, setting the value to `0` is not recommended unless `FAST_START_MTTR_TARGET` is set.

Note:

- A checkpoint scheduled to occur because of this parameter is delayed until the completion of the previous checkpoint if the previous checkpoint has not yet completed.
- Recovery I/O can also be limited by setting the `LOG_CHECKPOINT_INTERVAL` parameter or by the size specified for the smallest redo log. For information on which mechanism is controlling checkpointing behavior, query the `V$INSTANCE_RECOVERY` view.

See Also:

- "LOG_CHECKPOINT_TIMEOUT"
- "V$INSTANCE_RECOVERY"
- *Oracle Database Performance Tuning Guide* for information on disabling or removing this parameter when the `FAST_START_MTTR_TARGET` parameter is set

2.207 LOG_CHECKPOINTS_TO_ALERT

`LOG_CHECKPOINTS_TO_ALERT` lets you log your checkpoints to the alert log. Doing so is useful for determining whether checkpoints are occurring at the desired frequency.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No

2.208 LOG_FILE_NAME_CONVERT

`LOG_FILE_NAME_CONVERT` converts the filename of a new log file on the primary database to the filename of a log file on the standby database.

Property	Description
Parameter type	String

Property	Description

Syntax	`LOG_FILE_NAME_CONVERT = 'string1' , 'string2' , 'string3' , 'string4' , ...`
	Where:
	• *string1* is the pattern of the primary database filename
	• *string2* is the pattern of the standby database filename
	• *string3* is the pattern of the primary database filename
	• *string4* is the pattern of the standby database filename
	You can enclose each string in single or double quotation marks.
	You can specify as many pairs of primary and standby replacement strings as required.
	Example:
	`LOG_FILE_NAME_CONVERT = '/dbs/t1/','/dbs/t1/s','dbs/t2/','dbs/t2/s'`

Default value	There is no default value.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No

If you add a log file to the primary database, you must add a corresponding file to the standby database.

Set the value of this parameter to one or more pairs of strings. The first string is the pattern found in the log file names on the primary database. The second string is the pattern found in the log file names on the standby database.

When the standby database is updated, this parameter converts the log file name on the primary database to the log file name on the standby database. The file must exist on the standby database and must be writable or the recovery process will halt with an error.

If you specify an odd number of strings (the last string has no corresponding replacement string), an error is signalled during startup. If the filename being converted matches more than one pattern in the pattern/replace string list, the first matched pattern takes effect. There is no limit on the number of pairs that you can specify in this parameter (other than the hard limit of the maximum length of multivalue parameters).

You should also use `LOG_FILE_NAME_CONVERT` to rename the logfiles in the clone control file when setting up the clone database during tablespace point-in-time recovery.

Note:

The `LOG_FILE_NAME_CONVERT` parameter applies only to online logs (not to archived logs).

See Also:

Oracle Data Guard Concepts and Administration

2.209 LONG_MODULE_ACTION

LONG_MODULE_ACTION enables the use of longer lengths for modules and actions.

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	true | false
Basic	No
Oracle RAC	The same value must be used on all instances.

Module length was 48 bytes and action length was 32 bytes in Oracle Database releases prior to Oracle Database 12*c* Release 2 (12.2.0.1).

Starting with Oracle Database 12*c* Release 2 (12.2.0.1):

- If LONG_MODULE_ACTION is set to TRUE (the default value), then the length of modules and actions will be 64 bytes each.
- If LONG_MODULE_ACTION is set to FALSE, then the length of modules will be 48 bytes, and the length of actions will be 32 bytes.

2.210 MANDATORY_USER_PROFILE

MANDATORY_USER_PROFILE specifies the mandatory user profile for a CDB or PDB.

Property	Description
Parameter type	String
Syntax	MANDATORY_USER_PROFILE = *profile_name*
Default value	There is no default value
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Multiple instances must use the same value.

For *profile_name*, specify the name of a mandatory user profile. Mandatory user profiles are common profiles created in the CDB root with the following SQL statement:

```
CREATE MANDATORY PROFILE ... CONTAINER = ALL;
```

You can set the value of MANDATORY_USER_PROFILE in the CDB root or in a PDB.

- When you set this parameter in the CDB root, the specified mandatory user profile applies to the CDB root and all PDBs.

- When you set this parameter in a PDB, the specified mandatory user profile applies only to that PDB and overrides the mandatory user profile for the CDB root, if any.

Only common users with the commonly granted `ALTER SYSTEM` privilege or the commonly granted `SYSDBA` privilege can set the value of `MANDATORY_USER_PROFILE` in the CDB root or in a PDB. This prevents local PDB administrators from circumventing any restrictions that are enforced at the CDB root.

> **See Also:**
>
> See *Oracle Database Security Guide* for more information about mandatory user profiles

2.211 MAX_AUTH_SERVERS

`MAX_AUTH_SERVERS` specifies the maximum number of authentication servers in the authentication pool. This pool authenticates user connections when client applications connect to Database Resident Connection Pooling (DRCP).

Property	Description
Parameter type	Integer
Default value	`25`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes, according to the following guidelines: • When the `ENABLE_PER_PDB_DRCP` initialization parameter is set to `true`, `MAX_AUTH_SERVERS` can be modified only at the PDB level; it cannot be modified for the CDB root. • When the `ENABLE_PER_PDB_DRCP` initialization parameter is set to `false`, `MAX_AUTH_SERVERS` can be modified only for the CDB root; it cannot be modified at the PDB level.
Range of values	Minimum: `MIN_AUTH_SERVERS` or `1`, whichever is the greater value Maximum: operating system-dependent
Basic	No
Oracle RAC	Different instances can use different values.

The value of this parameter must be greater than or equal to the value of the `MIN_AUTH_SERVERS` initialization parameter, which specifies the minimum number of authentication servers in the authentication pool. The exception is when `MIN_AUTH_SERVERS = 0`. In this case, the value of `MAX_AUTH_SERVERS` must be greater than or equal to `1`.

> **See Also:**
>
> - *Oracle Database Administrator's Guide* for more information about setting this parameter
> - "ENABLE_PER_PDB_DRCP"
> - "MIN_AUTH_SERVERS"

2.212 MAX_COLUMNS

Use `MAX_COLUMNS` to enable or disable Wide Tables for the database.

Property	Description
Parameter type	String
Syntax	`MAX_COLUMNS = { STANDARD | EXTENDED }`
Default value	`STANDARD`
Modifiable	No
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Multiple instances must use the same value.

Values:

- To enable Wide Tables, set this parameter to `EXTENDED`. With this setting, the maximum number of columns allowed in a database table or view is 4096.

  The `COMPATIBLE` initialization parameter must be set to `23.0.0.0` or higher in order to set `MAX_COLUMNS = EXTENDED`.

- To disable Wide Tables, set this parameter to `STANDARD`. With this setting, the maximum number of columns allowed in a database table or view is 1000. This matches the behavior in releases prior to Oracle Database 23ai.

You can change the value of `MAX_COLUMNS` from `STANDARD` to `EXTENDED` at any time. However, you can change the value of `MAX_COLUMNS` from `EXTENDED` to `STANDARD` only when all tables and views in the database contain 1000 or fewer columns.

> **Note:**
>
> The increased column limit of 4096 is supported by Oracle Database 23ai clients, such as SQL*Plus, OCI, JDBC-OCI, unmanaged ODP.NET, and open source drivers. Older client versions (pre-Oracle Database 23ai) do not support the increased column limit and cannot access more than 1000 columns in a table or view.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.213 MAX_DATAPUMP_JOBS_PER_PDB

`MAX_DATAPUMP_JOBS_PER_PDB` determines the maximum number of concurrent Oracle Data Pump jobs per PDB.

Property	Description
Parameter type	String
Syntax	`MAX_DATAPUMP_JOBS_PER_PDB = { AUTO | integer }`
Default value	`AUTO`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`0` to `250` or `AUTO`
Basic	No
Oracle RAC	The same value must be used on all instances.

When this parameter has a value of `AUTO`, Oracle Data Pump will derive its actual value to be 50% of the `SESSIONS` initialization parameter.

A value that is too large could cause Oracle Data Pump to consume too many system resources, while a value that is too small could prevent users from performing their Oracle Data Pump tasks.

The main resource Oracle Data Pump uses is shared pool in the System Global Area (SGA) for the database. Parallel jobs increase the number of sessions and, depending on the job, the number of PX servers used.

> **See Also:**
>
> - *Oracle Database Utilities* for more information about using Oracle Data Pump with CDBs
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_DATAPUMP` PL/SQL package

2.214 MAX_DATAPUMP_PARALLEL_PER_JOB

`MAX_DATAPUMP_PARALLEL_PER_JOB` specifies the maximum number of parallel processes allowed per Oracle Data Pump job.

Property	Description
Parameter type	String
Syntax	`MAX_DATAPUMP_PARALLEL_PER_JOB = { integer | AUTO }`
Default value	`AUTO`
Range of values	`1` to `1024`, or `AUTO`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Different instances can use different values.

When this parameter has a value of `AUTO`, Oracle Data Pump derives its value to be 50 percent of the value of the `SESSIONS` initialization parameter.

2.215 MAX_DISPATCHERS

`MAX_DISPATCHERS` specifies the maximum number of dispatcher processes allowed to be running simultaneously.

Property	Description
Parameter type	Integer
Default value	There is no default value.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	If `MAX_DISPATCHERS` is specified, then it should be greater than or equal to the number of dispatchers specified by the `DISPATCHERS` parameter and less than the number of processes specified by the `PROCESSES` parameter.
Basic	No

This parameter can be overridden by the `DISPATCHERS` parameter and is maintained for backward compatibility with older releases.

See Also:

- *Oracle Database Administrator's Guide* for more information about this parameter
- Your operating system-specific Oracle documentation for the default value and range of values

2.216 MAX_DUMP_FILE_SIZE

`MAX_DUMP_FILE_SIZE` specifies the maximum size of trace files (excluding the alert log).

Property	Description
Parameter type	String
Syntax	`MAX_DUMP_FILE_SIZE = { integer [K | M | G] | UNLIMITED }`
Default value	Oracle Database Free: `32M` All other Oracle Database offerings: • `1G` for foregrounds (5 segments of 200M each) • `10G` for others (5 segments of 1G each)
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	0 to unlimited, or `UNLIMITED`
Basic	No

You can change this limit if you are concerned that trace files may use too much space.

- A numeric value for `MAX_DUMP_FILE_SIZE` specifies the maximum size in operating system blocks.
- A numeric value followed by a `K` or `M` or `G` suffix specifies the file size in kilobytes, megabytes, or gigabytes.
- The special value string `UNLIMITED` means that there is no upper limit on trace file size. Thus, dump files can be as large as the operating system permits.

When the trace file is limited in size, it may be automatically split into multiple files, called segments, if needed. This process is call trace file segmentation. The segments will have the same file name as the active trace file, but with an extra segment number appended.

The trace file can be split into a maximum of 5 segments, and the size of each segment will typically be 1/5th of the trace file limit.

When the combined size of all the trace file segments exceeds the specified limit, the oldest segment is deleted, and a new, empty segment is created. Thus, the trace file always contains the most recent trace information. The first segment is never deleted, because it may contain relevant information about the initial state of the process.

Note that trace file segmentation will not occur when this parameter is set to a value less than 25 MB.

See Also:

Oracle Database Administrator's Guide and *Oracle Database SQL Tuning Guide* for more information on setting this parameter

2.217 MAX_IDLE_BLOCKER_TIME

MAX_IDLE_BLOCKER_TIME specifies the maximum number of minutes that a blocking session can be idle. After that point, the session is automatically terminated.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	0 to the maximum integer. The value of 0 indicates that there is no limit.
Basic	No
Oracle RAC	Different instances can use different values.

A session is considered to be a blocking session when it is holding resources required by other sessions. For example:

- The session is holding a lock required by another session.
- The session is a parallel operation and its consumer group, PDB, or database has either reached its maximum parallel server limit or has queued parallel operations.
- The session's PDB or database instance is about to reach its SESSIONS or PROCESSES limit.

This parameter differs from the MAX_IDLE_TIME parameter in that MAX_IDLE_TIME applies to all sessions (blocking and non-blocking), whereas MAX_IDLE_BLOCKING_TIME applies only to blocking sessions. Therefore, in order for MAX_IDLE_BLOCKING_TIME to be effective, its limit must be less than the MAX_IDLE_TIME limit.

Note:

This parameter does not have an effect on parallel query processes, nor on SYS user sessions.

See Also:

"MAX_IDLE_TIME"

2.218 MAX_IDLE_TIME

`MAX_IDLE_TIME` specifies the maximum number of minutes that a session can be idle. After that point, the session is automatically terminated.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	0 to the maximum integer. The value of 0 indicates that there is no limit.
Basic	No
Oracle RAC	Different instances can use different values.

> **See Also:**
>
> "MAX_IDLE_BLOCKER_TIME" to learn how to set a lower idle time limit for sessions that are holding resources required by other sessions

2.219 MAX_IOPS

`MAX_IOPS` enables you to set the maximum number of I/Os that can be issued per second on a per pluggable database (PDB) basis. This parameter is used to throttle PDB I/Os.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`0` to the maximum `Integer` value. A very low value (for example, under 100 I/Os per second) is not recommended.
Basic	No
Oracle RAC	Different values can be set on different instances.

DBWR I/Os, control file I/Os, password file I/Os and other critical I/Os are exempted from the rate limit set by this parameter, but their I/Os are accounted for while throttling. Because of these exemptions, the PDB's actual I/O rate may sometimes exceed the limit.

This feature is enabled for multitenant container database (CDB) only. The feature is not supported on Oracle Exadata.

This parameter can be set from inside a PDB. If the parameter is set in CDB$ROOT, all the PDBs in that CDB will inherit the parameter value from CDB$ROOT. This parameter cannot be set in a non-CDB environment.

The default value of `0` means that no limits are set on the maximum number of I/Os that can be issued per second in a PDB.

If Oracle processes need to wait because of this IO rate limit, the wait event is resmgr: I/O rate limit.

> **See Also:**
>
> - "MAX_MBPS"
> - "resmgr: I/O rate limit"

Examples

This example shows how to use SQL statements to set a maximum of 3000 I/Os per second on a PDB named CDB1_PDB1:

```
alter session set container = cdb1_pdb1;
alter system set max_iops = 3000;
```

2.220 MAX_MBPS

`MAX_MBPS` enables you to set the maximum number of megabytes (MB) of I/Os issued per second on a per pluggable database (PDB) basis. This parameter is used to throttle PDB I/Os.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`0` to the maximum `Integer` value. A very low value (for example, under 25 MB per second) is not recommended.
Basic	No
Oracle RAC	Different values can be set on different instances.

DBWR I/Os, control file I/Os, password file I/Os and other critical I/Os are exempted from the throughput limit set by this parameter, but their I/Os are accounted for while throttling. Because of these exemptions, the PDB's actual I/O rate may sometimes exceed the limit.

This feature is enabled for multitenant container database (CDB) only. The feature is not supported on Oracle Exadata.

This parameter can be set from inside a PDB. If the parameter is set in CDB$ROOT, all the PDBs in that CDB will inherit the parameter value from CDB$ROOT. This parameter cannot be set in a non-CDB environment.

The default value of `0` means that no limits are set on the maximum number of megabytes (MB) of I/Os that can be issued per second in a PDB.

If Oracle processes need to wait because of this IO rate limit, the wait event is resmgr: I/O rate limit.

> **See Also:**
>
> - "MAX_IOPS"
> - "resmgr: I/O rate limit"

Examples

This example shows how to use SQL statements to set a maximum of 200 megabytes per second on a PDB named CDB1_PDB1:

```
alter session set container = cdb1_pdb1;
alter system set max_mbps = 200;
```

2.221 MAX_PDBS

`MAX_PDBS` allows you to limit the number of pluggable databases (PDBs) that can be created in a CDB or an application container.

Property	Description
Parameter type	Integer
Default value	Depends on the Oracle Database edition Possible values: `5`, `254`, or `4098`
Modifiable	`ALTER SYSTEM ... SID='*'`
Modifiable in a PDB	No. However, this parameter can be modified in the application root of an application container.
Range of values	Minimum: `0` Maximum: The default value for the Oracle Database edition (`5`, `254`, or `4098`)
Basic	No
Oracle RAC	The same value must be used on all instances.

This parameter can only be set while connected to the CDB root or an application root.

This parameter applies to PDBs, application containers, and application PDBs. An application PDB is a PDB that resides in an application container.

This parameter does not apply to the PDB seed (`PDB$SEED`), application seeds, or application root clones.

> **Note:**
>
> The maximum number of PDBs that you are allowed to create in a CDB depends on the licensing policy for your Oracle Database edition. To learn more, refer to the Oracle Multitenant information in the "Consolidation" table in *Oracle Database Licensing Information User Manual*.

2.222 MAX_SAGA_DURATION

`MAX_SAGA_DURATION` specifies the maximum duration for a saga (in seconds).

If a saga exists for longer than the amount of time specified by this parameter, it is considered incomplete and is eligible for termination.

Property	Description
Parameter type	Integer
Default value	`86400` seconds (equivalent to 24 hours)
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	1 to 2^{31} - 1
Basic	No
Oracle RAC	Multiple instances must have the same value.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.223 MAX_SHARED_SERVERS

`MAX_SHARED_SERVERS` specifies the maximum number of shared server processes allowed to be running simultaneously. Setting this parameter enables you to reserve process slots for other processes, such as dedicated servers.

Property	Description
Parameter type	Integer
Default value	There is no default value.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	If `MAX_SHARED_SERVERS` is specified, then it should be greater than or equal to `SHARED_SERVERS` and less than `PROCESSES`.
Basic	No

When you want to reduce the range of shared servers, you can reduce MAX_SHARED_SERVERS before reducing SHARED_SERVERS. If MAX_SHARED_SERVERS is lower than SHARED_SERVERS, then the number of shared servers will not vary but will remain at the constant level specified by SHARED_SERVERS. If MAX_SHARED_SERVERS is not specified, then a shared server process may be spawned as long as the number of free process slots is greater than 1 / 8 the maximum number of processes, or 2 if PROCESSES is less than 24.

See Also:

- "SHARED_SERVERS"
- "PROCESSES"
- *Oracle Database Administrator's Guide* for more information on setting this parameter
- *Oracle Database Concepts* for information on processes
- Your operating system-specific Oracle documentation for the default value and range of values

2.224 MAX_STRING_SIZE

MAX_STRING_SIZE controls the maximum size of VARCHAR2, NVARCHAR2, and RAW data types in SQL.

Property	Description
Parameter type	String
Syntax	MAX_STRING_SIZE = { STANDARD | EXTENDED }
Default value	STANDARD
Modifiable	ALTER SYSTEM ... SID='*'[1]
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Multiple instances must use the same value.

1 Use ALTER SYSTEM only when the database is in UPGRADE mode, and run the utl32k.sql script afterward, as explained in this section.

STANDARD means that the length limits for Oracle Database releases prior to Oracle Database 12*c* apply (for example, 4000 bytes for VARCHAR2 and NVARCHAR2, and 2000 bytes for RAW).

EXTENDED means that the 32767 byte limit introduced in Oracle Database 12*c* applies.

The COMPATIBLE initialization parameter must be set to 12.0.0.0 or higher to set MAX_STRING_SIZE = EXTENDED.

You can change the value of MAX_STRING_SIZE from STANDARD to EXTENDED. However, you cannot change the value of MAX_STRING_SIZE from EXTENDED to STANDARD.

By setting MAX_STRING_SIZE = EXTENDED, users are taking an explicit action that could introduce application incompatibility in their database. Applications that do not want to use the expanded data types can be rewritten for compatibility with either setting; for example, these applications could use explicit CASTs to fix the length of VARCHAR2 expressions during CREATE TABLE AS SELECT.

Altering MAX_STRING_SIZE will update database objects and possibly invalidate them, as follows:

- Tables with virtual columns will be updated with new data type metadata for virtual columns of VARCHAR2(4000), 4000-byte NVARCHAR2, or RAW(2000) type.
  - Functional indexes will become unusable if a change to their associated virtual columns causes the index key to exceed index key length limits. Attempts to rebuild such indexes will fail with ORA-01450: maximum key length exceeded.
- Views will be invalidated if they contain VARCHAR2(4000), 4000-byte NVARCHAR2, or RAW(2000) typed expression columns.
- Materialized views will be updated with new metadata VARCHAR2(4000), 4000-byte NVARCHAR2, and RAW(2000) typed expression columns

Increasing the Maximum Size of VARCHAR2, NVARCHAR2, and RAW Columns in a CDB

To increase the maximum size of VARCHAR2, NVARCHAR2, and RAW columns in a CDB and in all the PDBs in the CDB:

1. Connect to the CDB AS SYSDBA.
2. In the root, change the setting of MAX_STRING_SIZE to EXTENDED:

```
ALTER SESSION SET CONTAINER=CDB$ROOT;
ALTER SYSTEM SET max_string_size=extended SCOPE=SPFILE;
```

> **Note:**
>
> The root continues to use STANDARD semantics even after MAX_STRING_SIZE is set to EXTENDED. The reason for setting MAX_STRING_SIZE to EXTENDED in the root is so all the PDBs in the CDB can inherit the EXTENDED setting from the root.

3. Shut down the CDB.
4. Restart the CDB in UPGRADE mode.

```
startup upgrade;
```

5. Use the catcon.pl script to run the rdbms/admin/utl32k.sql script in the root and in all the PDBs in the CDB to increase the maximum size of the VARCHAR2, NVARCHAR2, and RAW columns. The --force_pdb_mode ‘UPGRADE’ option is used

to ensure that all PDBs, including application root clones, are opened in migrate mode. Enter the SYS password when prompted:

```
$ cd $ORACLE_HOME/rdbms/admin
$ mkdir /scratch/mydir/utl32k_cdb_pdbs_output
$ $ORACLE_HOME/perl/bin/perl $ORACLE_HOME/rdbms/admin/catcon.pl -u SYS --
force_pdb_mode 'UPGRADE' -d $ORACLE_HOME/rdbms/admin -l '/scratch/mydir/
utl32k_cdb_pdbs_output' -b
utl32k_cdb_pdbs_output utl32k.sql
catcon: ALL catcon-related output will be written to [/scratch/mydir/
utl32k_cdb_pdbs_output/utl32k_cdb_pdbs_output_catcon_23172.lst]
catcon: See [/scratch/mydir/utl32k_cdb_pdbs_output/
utl32k_cdb_pdbs_output*.log] files for output generated by scripts
catcon: See [/scratch/mydir/utl32k_cdb_pdbs_output/
utl32k_cdb_pdbs_output_*.lst] files for spool files, if any
Enter Password:
catcon.pl: completed successfully
$
```

> **Note:**
>
> The `utl32k.sql` script increases the maximum size of the `VARCHAR2`, `NVARCHAR2`, and `RAW` columns for the views where this is required. The script does not increase the maximum size of the `VARCHAR2`, `NVARCHAR2`, and `RAW` columns in some views because of the way the SQL for those views is written.

6. Connect to the CDB AS SYSDBA and shut down the database.
7. Restart the CDB in NORMAL mode.

```
startup;
```

8. Use the `catcon.pl` script to run the `rdbms/admin/utlrp.sql` script to recompile invalid objects in the root and in all the PDBs in the CDB. The --force_pdb_mode ‘READ WRITE’ option is used to ensure that all the PDBs (including application root clones) are opened in read write mode. Enter the SYS password when prompted:

```
$ cd $ORACLE_HOME/rdbms/admin
$ mkdir /scratch/mydir/utlrp_cdb_pdbs_output
$ $ORACLE_HOME/perl/bin/perl $ORACLE_HOME/rdbms/admin/catcon.pl -u SYS --
force_pdb_mode 'READ WRITE' -d $ORACLE_HOME/rdbms/admin -l '/scratch/
mydir/utlrp_cdb_pdbs_output' -b utlrp_cdb_pdbs_output utlrp.sql
catcon: ALL catcon-related output will be written to [/scratch/mydir/
utlrp_cdb_pdbs_output/utlrp_cdb_pdbs_output_catcon_24271.lst]
catcon: See [/scratch/mydir/utlrp_cdb_pdbs_output/
utlrp_cdb_pdbs_output*.log] files for output generated by scripts
catcon: See [/scratch/mydir/utlrp_cdb_pdbs_output/
utlrp_cdb_pdbs_output_*.lst] files for spool files, if any
Enter Password:
catcon.pl: completed successfully
$
```

> **See Also:**
>
> *Oracle Multitenant Administrator's Guide* for information about using the `catcon.pl` script to run Oracle-supplied scripts in a CDB and PDBs.

Increasing the Maximum Size of VARCHAR2, NVARCHAR2, and RAW Columns in a PDB

To increase the maximum size of `VARCHAR2`, `NVARCHAR2`, and `RAW` columns in a PDB:

1. Shut down the PDB.
2. Reopen the PDB in migrate mode.

> **Note:**
>
> The following SQL statement can be used to reopen a PDB in migrate mode when the current container is the PDB:
>
> `ALTER PLUGGABLE DATABASE` *pdb-name* `OPEN UPGRADE;`

3. Change the setting of `MAX_STRING_SIZE` in the PDB to `EXTENDED`.
4. Run the `rdbms/admin/utl32k.sql` script in the PDB. You must be connected `AS SYSDBA` to run the `utl32k.sql` script.
5. Reopen the PDB in `NORMAL` mode.

> **Note:**
>
> The `utl32k.sql` script increases the maximum size of the `VARCHAR2`, `NVARCHAR2`, and `RAW` columns for the views where this is required. The script does not increase the maximum size of the `VARCHAR2`, `NVARCHAR2`, and `RAW` columns in some views because of the way the SQL for those views is written.

6. Run the `rdbms/admin/utlrp.sql` script in the PDB to recompile invalid objects. You must be connected `AS SYSDBA` to run the script.

> **See Also:**
>
> *Oracle Multitenant Administrator's Guide* for more information about modifying the open mode of PDBs.

Increasing the Maximum Size of VARCHAR2, NVARCHAR2, and RAW Columns in an Oracle RAC Database

To increase the maximum size of `VARCHAR2`, `NVARCHAR2`, and `RAW` columns in an Oracle RAC database:

1. Shut down all of the Oracle RAC database instances, except one.
2. Restart the Oracle RAC database instance in `UPGRADE` mode.
3. Change the setting of `MAX_STRING_SIZE` to `EXTENDED`.
4. Run the `rdbms/admin/utl32k.sql` script in the Oracle RAC database instance. You must be connected `AS SYSDBA` to run the script.
5. Restart all Oracle RAC database instances in `NORMAL` mode.

> **Note:**
>
> The `utl32k.sql` script increases the maximum size of the `VARCHAR2`, `NVARCHAR2`, and `RAW` columns for the views where this is required. The script does not increase the maximum size of the `VARCHAR2`, `NVARCHAR2`, and `RAW` columns in some views because of the way the SQL for those views is written.

6. Run the `rdbms/admin/utlrp.sql` script to recompile invalid objects. You must be connected `AS SYSDBA` to run the script.

Increasing the Maximum Size of VARCHAR2, NVARCHAR2, and RAW Columns in an Oracle Data Guard Logical Standby Database

To increase the maximum size of `VARCHAR2`, `NVARCHAR2`, and `RAW` columns in an Oracle Data Guard logical standby database:

1. Shut down the Oracle Data Guard primary database and logical standby database.
2. Restart the primary database and logical standby database in `UPGRADE` mode.
3. Change the setting of `MAX_STRING_SIZE` to `EXTENDED` on the primary database and logical standby database.
4. Run the `rdbms/admin/utl32k.sql` script on both the primary database and the logical standby database. You must be connected `AS SYSDBA` to run the script.
5. Restart the primary database and logical standby database in `NORMAL` mode.

> **Note:**
>
> The `utl32k.sql` script increases the maximum size of the `VARCHAR2`, `NVARCHAR2`, and `RAW` columns for the views where this is required. The script does not increase the maximum size of the `VARCHAR2`, `NVARCHAR2`, and `RAW` columns in some views because of the way the SQL for those views is written.

6. Run the `rdbms/admin/utlrp.sql` script on the primary database and logical standby database to recompile invalid objects. You must be connected `AS SYSDBA` to run the script.
7. Restart SQL Apply.

> **See Also:**
>
> *Oracle Database Globalization Support Guide* for more information about the `MAX_STRING_SIZE` parameter

2.225 MEMOPTIMIZE_POOL_SIZE

`MEMOPTIMIZE_POOL_SIZE` sets the size of the memoptimize pool, a memory area in the system global area (SGA) used by the Memoptimized Rowstore.

Property	Description
Parameter type	Big integer
Syntax	`MEMOPTIMIZE_POOL_SIZE = integer [K | M | G]`
Default value	0
Modifiable	No
Modifiable in a PDB	No
Range of values	0 to no maximum
Basic	No
Oracle RAC	Different values can be used on different instances.

The Memoptimized Rowstore improves the data query performance of applications, such as Internet of Things (IoT), that frequently query tables based on primary key values.

The Memoptimized Rowstore provides the capability of fast lookup of data for the tables that are mainly queried based on primary key columns.

This parameter specifies an integer value to indicate the amount of SGA to use for allocating the following structures for the memoptimize pool:

- The size of the buffer cache region: This is the total number of blocks for all `MEMOPTIMIZE FOR READ` tables.
- The size of the hash index segmented data structure pointing to the special blocks of `MEMOPTIMIZE FOR READ` tables.

Calculate the buffer cache requirement for the table being considered for `MEMOPTIMIZE FOR READ`, and include an additional 25% memory requirement for the hash index segmented data structure.

These structures are allocated from SGA at instance startup.

The value specified for this parameter counts toward `SGA_TARGET`. For example, if you set `SGA_TARGET` to 10 GB and you set `MEMOPTIMIZE_POOL_SIZE` to 2 GB, then 20% of the `SGA_TARGET` setting is allocated to the memoptimize pool.

Unlike other SGA components such as the buffer cache and shared pool, the memoptimize pool size is not controlled by automatic memory management. The database does not automatically shrink the memoptimize pool when the buffer cache or shared pool requires more memory, or increase the memoptimize pool when it runs out of space. You can only increase the size of the memoptimize pool by manually adjusting the `MEMOPTIMIZE_POOL_SIZE` initialization parameter.

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about the Memoptimized Rowstore and the memoptimize pool.

2.226 MEMOPTIMIZE_WRITE_AREA_SIZE

`MEMOPTIMIZE_WRITE_AREA_SIZE` specifies the size of the ingest buffer in the large pool of the SGA. The ingest buffer is where Memoptimized Rowstore fast ingest inserts are buffered.

Property	Description
Parameter type	Big integer
Syntax	`MEMOPTIMIZE_WRITE_AREA_SIZE = integer [K | M | G]`
Default value	`0`
Modifiable	`ALTER SYSTEM ... SID='*'`
Modifiable in a PDB	No
Range of values	`0` to operating system-dependent
Basic	No
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.227 MEMOPTIMIZE_WRITES

`MEMOPTIMIZE_WRITES` allows you to instruct the database to always use fast ingest when inserting data into tables enabled for Memoptimized Rowstore fast ingest.

Property	Description
Parameter type	String
Syntax	`MEMOPTIMIZE_WRITES = { HINT | ON }`
Default value	`HINT`
Modifiable	`ALTER SESSION`

Property	Description
Modifiable in a PDB	No
Basic	No

The fast ingest feature of Memoptimized Rowstore was introduced in Oracle Database 19c. At that time, the only way to direct the database to use fast ingest was to specify the `MEMOPTIMIZE_WRITE` hint in the `INSERT` statement.

Starting with Oracle Database 23ai, you can also direct the database to use fast ingest by setting the `MEMOPTIMIZE_WRITES` initialization parameter as follows:

- `ON` - When inserting data into tables enabled for fast ingest, the fast ingest feature is always used, regardless of whether the `MEMOPTIMIZE_WRITE` hint is specified in the `INSERT` statement.
- `HINT` - When inserting data into tables enabled for fast ingest, the fast ingest feature is used only when the `MEMOPTIMIZE_WRITE` hint is specified in the `INSERT` statement.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.228 MEMORY_MAX_SIZE

`MEMORY_MAX_SIZE` specifies the maximum value to which a DBA can set the `MEMORY_SIZE` initialization parameter.

Property	Description
Parameter type	Big integer
Syntax	`MEMORY_MAX_SIZE = integer [K | M | G]`
Default value	The value of the `MEMORY_SIZE` initialization parameter
Modifiable	No
Modifiable in a PDB	No
Range of values	`MEMORY_SIZE` to the physical memory size available to the Oracle database
Basic	No
Oracle RAC	Different instances can use different values.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

> **See Also:**
>
> "MEMORY_SIZE" for more information about how the settings of MEMORY_MAX_SIZE and MEMORY_SIZE affect each other

2.229 MEMORY_MAX_TARGET

MEMORY_MAX_TARGET specifies the maximum value to which a DBA can set the MEMORY_TARGET initialization parameter.

Property	Description
Parameter type	Big integer
Syntax	MEMORY_MAX_TARGET = *integer* [K | M | G]
Default value	0
Modifiable	No
Modifiable in a PDB	No
Range of values	0 to the physical memory size available to the Oracle Database
Basic	No

See the description of MEMORY_TARGET for more information about how the settings of MEMORY_MAX_TARGET and MEMORY_TARGET affect each other.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about managing memory

2.230 MEMORY_SIZE

MEMORY_SIZE specifies the size of instance-wide usable memory.

Property	Description
Parameter type	Big integer
Syntax	MEMORY_SIZE = *integer* [K | M | G]
Default value	0
Modifiable	You can use ALTER SYSTEM to increase or decrease the value of this parameter. However, the value of this parameter must always be greater than or equal to its value at instance startup.
Modifiable in a PDB	No
Range of values	1536 MB to MEMORY_MAX_SIZE
Basic	No

Property	Description
Oracle RAC	Different instances can use different values.

In a text-based initialization parameter file, if you omit `MEMORY_MAX_SIZE` and include a value for `MEMORY_SIZE`, then the database automatically sets `MEMORY_MAX_SIZE` to the value of `MEMORY_SIZE`. If you omit the line for `MEMORY_SIZE` and include a value for `MEMORY_MAX_SIZE`, the `MEMORY_SIZE` parameter defaults to `0`. After instance startup, you can dynamically change `MEMORY_SIZE` to a nonzero value, provided that it does not exceed the value of `MEMORY_MAX_SIZE`.

Based on the value of `MEMORY_SIZE`, the values for the SGA and PGA parameters `SGA_TARGET` and `PGA_AGGREGATE_LIMIT` will be calculated internally for the instance. The sizing will also depend on the large page settings.

When `MEMORY_SIZE` is set to a nonzero value, the CDB-level values for the following SGA and PGA parameters will be ignored by the database: `SGA_MAX_SIZE`, `PGA_AGGREGATE_LIMIT`, and `SGA_TARGET`. If you assign a value to any of these parameters at the time of instance startup, the database will not report an error, but the parameter value will be ignored. If you dynamically modify any of these parameters, an error will be reported.

When `MEMORY_SIZE` is set to a nonzero value, the `MEMORY_MAX_TARGET` and `MEMORY_TARGET` parameters should be set to `0`. If you attempt to set either of these parameters to a nonzero value, the request will be ignored, and a warning will be written to the alert log at startup.

Note:

This parameter is available starting with Oracle Database 23ai.

See Also:

"MEMORY_MAX_SIZE"

2.231 MEMORY_TARGET

`MEMORY_TARGET` specifies the Oracle system-wide usable memory.

The database tunes memory to the `MEMORY_TARGET` value, reducing or enlarging the SGA and PGA as needed.

Property	Description
Parameter type	Big integer
Syntax	`MEMORY_TARGET = integer [K | M | G]`
Default value	`0` (SGA autotuning is disabled for `DEFERRED` mode autotuning requests, but allowed for `IMMEDIATE` mode autotuning requests)

Property	Description
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	152 MB to MEMORY_MAX_TARGET
Basic	No

MEMORY_TARGET should be set higher than or equal to the sum of the current sizes of the SGA and PGA.

In a text-based initialization parameter file, if you omit MEMORY_MAX_TARGET and include a value for MEMORY_TARGET, then the database automatically sets MEMORY_MAX_TARGET to the value of MEMORY_TARGET. If you omit the line for MEMORY_TARGET and include a value for MEMORY_MAX_TARGET, the MEMORY_TARGET parameter defaults to zero. After startup, you can then dynamically change MEMORY_TARGET to a nonzero value, provided that it does not exceed the value of MEMORY_MAX_TARGET.

Total memory usage can grow beyond the value of MEMORY_TARGET. For example, memory is allocated to PL/SQL tables and varrays regardless of the value of MEMORY_TARGET as long as memory is available at the operating system level.

In the **Default value** field, IMMEDIATE mode autotuning requests are necessary to avoid ORA-04031 errors. The DEFERRED and IMMEDIATE modes are reflected in the OPER_MODE column of the V$MEMORY_RESIZE_OPS view.

Note:

The default value of SGA_MAX_SIZE depends on the values of MEMORY_TARGET and MEMORY_MAX_TARGET.

See Also:

- *Oracle Database Administrator's Guide* for more information about managing memory
- *Oracle Multitenant Administrator's Guide* for information about the initialization parameters that control the memory usage of PDBs

2.232 MIN_AUTH_SERVERS

MIN_AUTH_SERVERS specifies the minimum number of authentication servers in the authentication pool. This pool authenticates user connections when client applications connect to Database Resident Connection Pooling (DRCP).

Property	Description
Parameter type	Integer

Property	Description
Default value	If the ENABLE_PER_PDB_DRCP initialization parameter is set to true, then the default value for MIN_AUTH_SERVERS is 0 in each PDB. If the ENABLE_PER_PDB_DRCP initialization parameter is set to false, then the default value for MIN_AUTH_SERVERS is 1 in the CDB root.
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes, according to the following guidelines: • When the ENABLE_PER_PDB_DRCP initialization parameter is set to true, MIN_AUTH_SERVERS can be modified only at the PDB level; it cannot be modified for the CDB root. • When the ENABLE_PER_PDB_DRCP initialization parameter is set to false, MIN_AUTH_SERVERS can be modified only for the CDB root; it cannot be modified at the PDB level.
Range of values	Minimum: 0 Maximum: MAX_AUTH_SERVERS or PROCESSES, whichever is the lesser value
Basic	No
Oracle RAC	Different instances can use different values.

The value of this parameter must be less than or equal to the values of both the MAX_AUTH_SERVERS initialization parameter and the PROCESSES initialization parameter. The MAX_AUTH_SERVERS parameter specifies the maximum number of authentication servers in the authentication pool. The PROCESSES parameter specifies the maximum number of operating system user processes that can simultaneously connect to Oracle.

See Also:

- *Oracle Database Administrator's Guide* for more information about setting this parameter
- "ENABLE_PER_PDB_DRCP"
- "MAX_AUTH_SERVERS"
- "PROCESSES"

2.233 MLE_PROG_LANGUAGES

Use MLE_PROG_LANGUAGES to enable or disable Oracle Database Multilingual Engine (MLE) completely, or selectively enable certain languages.

Property	Description
Parameter type	String
Syntax	MLE_PROG_LANGUAGES = { ALL | JAVASCRIPT | OFF }
Default value	ALL
Modifiable	ALTER SESSION, ALTER SYSTEM

Property	Description
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Multiple instances must have the same value.

Values:

- `ALL` - Enable MLE completely.
- `JAVASCRIPT` - Enable MLE for JavaScript only. Note that MLE currently supports JavaScript as its sole language. Therefore, the `JAVASCRIPT` setting has the same effect as the `ALL` setting.
- `OFF` - Disable MLE completely.

  If MLE is disabled completely at the CDB level, it cannot be enabled at the PDB or session level. Similarly, if MLE is disabled completely at the PDB level, it cannot be enabled at the session level.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

> **See Also:**
>
> *Oracle Database Multilingual Engine JavaScript Developer's Guide* for more information about this parameter

2.234 MULTISHARD_QUERY_DATA_CONSISTENCY

`MULTISHARD_QUERY_DATA_CONSISTENCY` enables you to specify a data consistency setting for multi-shard queries.

Property	Description
Parameter type	String
Syntax	`MULTISHARD_QUERY_DATA_CONSISTENCY = { STRONG | SHARD_LOCAL | DELAYED_STANDBY_ALLOWED }`
Default value	`STRONG`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	The value of this parameter can be different on different Oracle RAC instances.

You can use MULTISHARD_QUERY_DATA_CONSISTENCY to avoid the cost of SCN synchronization when executing multi-shard queries across shards, which can be globally distributed.

MULTISHARD_QUERY_DATA_CONSISTENCY can be set at the system level or the session level.

The values that can be set for MULTISHARD_QUERY_DATA_CONSISTENCY are:

- STRONG: With this setting, SCN synchronization is performed across all shards, and data is consistent across all shards. This setting provides global consistent read capability. This is the default value.
- SHARD_LOCAL: With this setting, SCN synchronization is not performed across all shards. Data is consistent within each shard. This setting provides the most current data.
- DELAYED_STANDBY_ALLOWED: With this setting, SCN synchronization is not performed across all shards. Data is consistent within each shard. This setting allows data to be fetched from Data Guard standby databases when possible (for example, depending on load balancing), and may return stale data from standby databases.

> **See Also:**
>
> *Oracle Globally Distributed Database Guide* for more information about specifying consistency levels in a multi-shard query

2.235 NLS_CALENDAR

NLS_CALENDAR specifies which calendar system Oracle uses.

Property	Description
Parameter type	String
Syntax	NLS_CALENDAR = "*calendar_system*"
Default value	None, implies GREGORIAN
Modifiable	ALTER SESSION
Modifiable in a PDB	Yes
Range of values	Any valid calendar format name
Basic	No

NLS_CALENDAR can have one of the following values:

- Arabic Hijrah
- English Hijrah
- Ethiopian
- Gregorian
- Japanese Imperial

- Persian
- ROC Official (Republic of China)
- Thai Buddha

For example, suppose NLS_CALENDAR is set to "Japanese Imperial", the date format is "E YY-MM-DD". ("E" is the date format element for the abbreviated era name.) If the date is May 15, 1997, then the SYSDATE is displayed as follows:

```
SELECT SYSDATE FROM DUAL;
SYSDATE
--------
H 09-05-15
```

> **Note:**
>
> The value of the initialization parameter NLS_CALENDER is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. If the initialization parameter is not specified, the initial session value becomes GREGORIAN. This initial value is overridden by a client-side value if the client is OCI-based and the NLS_LANG client setting (environment variable) is defined.

> **See Also:**
>
> *Oracle Database Globalization Support Guide* for a listing of available calendar systems

2.236 NLS_COMP

NLS_COMP specifies the collation behavior of the database session.

Property	Description
Parameter type	String
Syntax	NLS_COMP = { BINARY | LINGUISTIC | ANSI }
Default value	BINARY
Modifiable	ALTER SESSION
Modifiable in a PDB	Yes
Basic	No

Values

- BINARY

  Normally, comparisons in the WHERE clause and in PL/SQL blocks is binary unless you specify the NLSSORT function.

- LINGUISTIC

Comparisons for all SQL operations in the `WHERE` clause and in PL/SQL blocks should use the linguistic sort specified in the `NLS_SORT` parameter. To improve the performance, you can also define a linguistic index on the column for which you want linguistic comparisons.

- `ANSI`

  A setting of `ANSI` is for backward compatibility; in general, you should set `NLS_COMP` to `LINGUISTIC`

> **Note:**
>
> Unless you explicitly set the value for `NLS_COMP` in your initialization parameter file, a default value of NULL is shown in the following views: `V$PARAMETER`, `V$SYSTEM_PARAMETER`, `V$PARAMETER2`, `V$SYSTEM_PARAMETER2`, and `NLS_INSTANCE_PARAMETERS`. However, the actual default value, and behavior, is `BINARY`. Note that you cannot change the default to NULL, because NULL is not among the valid values.

Examples

See *Oracle Database Globalization Support Guide* for examples of using this parameter.

> **Note:**
>
> The value of this initialization parameter `NLS_COMP` is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the `NLS_LANG` client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

2.237 NLS_CURRENCY

`NLS_CURRENCY` specifies the string to use as the local currency symbol for the L number format element. The default value of this parameter is determined by `NLS_TERRITORY`.

Property	Description
Parameter type	String
Syntax	`NLS_CURRENCY = currency_symbol`
Default value	Derived from `NLS_TERRITORY`
Modifiable	`ALTER SESSION`
Modifiable in a PDB	Yes
Range of values	Any valid character string, with a maximum of 10 bytes (not including null)

Property	Description
Basic	No

> **Note:**
>
> The value of this initialization parameter `NLS_CURRENCY` is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the `NLS_LANG` client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

> **See Also:**
>
> - *Oracle Database Globalization Support Guide* for more information about this parameter
> - *Oracle Database SQL Language Reference* for information on number format elements

2.238 NLS_DATE_FORMAT

`NLS_DATE_FORMAT` specifies the default date format to use with the `TO_CHAR` and `TO_DATE` functions. The default value of this parameter is determined by `NLS_TERRITORY`.

Property	Description
Parameter type	String
Syntax	`NLS_DATE_FORMAT = "format"`
Default value	Derived from `NLS_TERRITORY`
Modifiable	`ALTER SESSION`
Modifiable in a PDB	Yes
Range of values	Any valid date format mask but not exceeding a fixed length
Basic	No

The value of this parameter can be any valid date format mask, and the value must be surrounded by double quotation marks. For example:

```
NLS_DATE_FORMAT = "MM/DD/YYYY"
```

> **Note:**
>
> The value of this initialization parameter `NLS_DATE_FORMAT` is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the `NLS_LANG` client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

> **See Also:**
>
> *Oracle Database Globalization Support Guide* for more information about this parameter

2.239 NLS_DATE_LANGUAGE

`NLS_DATE_LANGUAGE` specifies the language to use for the spelling of day and month names and date abbreviations (a.m., p.m., AD, BC) returned by the `TO_DATE` and `TO_CHAR` functions.

Property	Description
Parameter type	String
Syntax	`NLS_DATE_LANGUAGE = language`
Default value	Derived from `NLS_LANGUAGE`
Modifiable	`ALTER SESSION`
Modifiable in a PDB	Yes
Range of values	Any valid `NLS_LANGUAGE` value
Basic	No

> **Note:**
>
> The value of this initialization parameter `NLS_DATE_LANGUAGE` is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the `NLS_LANG` client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also:

- *Oracle Database Globalization Support Guide* for more information about this parameter
- *Oracle Database SQL Language Reference* for information on the `TO_DATE` function.
- *Oracle Database SQL Language Reference* for information on the `TO_CHAR` function.

2.240 NLS_DUAL_CURRENCY

`NLS_DUAL_CURRENCY` specifies the dual currency symbol (such as "Euro") for the territory. The default is the dual currency symbol defined in the territory of your current language environment.

Property	Description
Parameter type	String
Syntax	`NLS_DUAL_CURRENCY = currency_symbol`
Default value	Derived from `NLS_TERRITORY`
Modifiable	`ALTER SESSION`
Modifiable in a PDB	Yes
Range of values	Any valid format name up to 10 characters
Basic	No

Note:

The value of this initialization parameter `NLS_DUAL_CURRENCY` is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the `NLS_LANG` client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also:

Oracle Database Globalization Support Guide for more information about this parameter

2.241 NLS_ISO_CURRENCY

NLS_ISO_CURRENCY determines the string to use as the international currency symbol corresponding to the C number format element in a call to the TO_CHAR function.

Property	Description
Parameter type	String
Syntax	NLS_ISO_CURRENCY = *territory*
Default value	Derived from NLS_TERRITORY
Modifiable	ALTER SESSION
Modifiable in a PDB	Yes
Range of values	Any valid NLS_TERRITORY value
Basic	No

Local currency symbols can be ambiguous. For example, a dollar sign ($) can refer to U.S. dollars or Australian dollars. ISO Specification 4217 defines unique "international" currency symbols for the currencies of specific territories or countries. The value of the NLS_ISO_CURRENCY parameter is the Oracle name of the territory whose ISO currency symbol is returned in place of the C number format element. For example, if NLS_ISO_CURRENCY is set to AMERICA, the string 'USD' is returned by TO_CHAR where the C element is specified in the format.

Note:

The value of this initialization parameter NLS_ISO_CURRENCY is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the NLS_LANG client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also:

- *Oracle Database Globalization Support Guide* for more information about this parameter
- *Oracle Database SQL Language Reference* for information on number format elements

2.242 NLS_LANGUAGE

NLS_LANGUAGE specifies the default language of the database.

Property	Description
Parameter type	String
Syntax	`NLS_LANGUAGE = language`
Default value	Operating system-dependent, derived from the `NLS_LANG` environment variable
Modifiable	`ALTER SESSION`
Modifiable in a PDB	Yes
Range of values	Any valid language name
Basic	Yes

This language specified by `NLS_LANGUAGE` is used for messages, day and month names, symbols for AD, BC, a.m., and p.m., and the default sorting mechanism. This parameter also determines the default values of the parameters `NLS_DATE_LANGUAGE` and `NLS_SORT`.

> **Note:**
>
> The value of this initialization parameter `NLS_LANGUAGE` is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the `NLS_LANG` client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

Examples

See these examples of using the `NLS_LANGUAGE` parameter:

- For an example of setting `NLS_LANGUAGE` to Italian, see *Oracle Database Globalization Support Guide*.
- For an example of overriding default values for `NLS_LANGUAGE` and `NLS_TERRITORY` during a session, see *Oracle Database Globalization Support Guide*.

> **See Also:**
>
> - *Oracle Database Globalization Support Guide* for more information about this parameter.
> - *Oracle Database Globalization Support Guide* for a complete list of languages that can be specified using this parameter
> - *Oracle Database Globalization Support Guide* for information on overriding the default values for this parameter
> - Your operating system-specific Oracle documentation and the release notes for your country

2.243 NLS_LENGTH_SEMANTICS

NLS_LENGTH_SEMANTICS is used to specify length semantics.

Property	Description
Parameter type	String
Syntax	NLS_LENGTH_SEMANTICS = *string* Example: NLS_LENGTH_SEMANTICS = 'CHAR'
Default value	BYTE
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	BYTE | CHAR
Basic	No

The session-level value of NLS_LENGTH_SEMANTICS specifies the default length semantics to use for VARCHAR2 and CHAR table columns, user-defined object attributes, and PL/SQL variables in database objects created in the session. This default may be overridden by the explicit length semantics qualifiers BYTE and CHAR in column, attribute, and variable definitions.

The instance-level value of NLS_LENGTH_SEMANTICS provides a default for the session-level value if NLS_LENGTH_SEMANTICS is not set explicitly by the database client through the NLS_LENGTH_SEMANTICS client environment variable (does not apply to JDBC Thin clients), or the ALTER SESSION SET NLS_LENGTH_SEMANTICS statement.

NCHAR, NVARCHAR2, CLOB, and NCLOB columns are always character-based.

Sessions logged in as SYS do not use the NLS_LENGTH_SEMANTICS parameter. They use BYTE length semantics for all created objects unless overridden by the explicit BYTE and CHAR qualifiers in object definitions (SQL DDL statements).

Note:

Oracle strongly recommends that you do NOT set the NLS_LENGTH_SEMANTICS parameter to CHAR in the instance or server parameter file. This may cause many existing installation scripts to unexpectedly create columns with character length semantics, resulting in run-time errors, including buffer overflows.

See Also:

Oracle Database Globalization Support Guide for more information about this parameter

2.244 NLS_NCHAR_CONV_EXCP

NLS_NCHAR_CONV_EXCP determines whether an error is reported when there is data loss during an implicit or explicit character type conversion between NCHAR/NVARCHAR2 and CHAR/VARCHAR2.

Property	Description
Parameter type	String
Syntax	NLS_NCHAR_CONV_EXCP = { TRUE | FALSE }
Default value	FALSE
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No

The default value results in no error being reported.

> **See Also:**
>
> *Oracle Database Globalization Support Guide* for more information about this parameter

2.245 NLS_NUMERIC_CHARACTERS

NLS_NUMERIC_CHARACTERS specifies the characters to use as the group separator and decimal character.

Property	Description
Parameter type	String
Syntax	NLS_NUMERIC_CHARACTERS = "*decimal_character group_separator*"
Default value	Derived from NLS_TERRITORY
Modifiable	ALTER SESSION
Modifiable in a PDB	Yes
Basic	No

NLS_NUMERIC_CHARACTERS overrides those characters defined implicitly by NLS_TERRITORY. The group separator separates integer groups (that is, thousands, millions, billions, and so on). The decimal separates the integer portion of a number from the decimal portion.

You can specify any character as the decimal or group separator. The two characters specified must be single-byte and must be different from each other. The characters cannot be any numeric character or any of the following characters: plus (+), minus sign (-), less than sign (<), greater than sign (>). Either character can be a space.

For example, if you want to specify a comma as the decimal character and a space as the group separator, you would set this parameter as follows:

```
NLS_NUMERIC_CHARACTERS = ", "
```

> **Note:**
>
> The value of this initialization parameter NLS_NUMERIC_CHARACTERS is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the NLS_LANG client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

> **See Also:**
>
> *Oracle Database Globalization Support Guide* for more information about this parameter

2.246 NLS_SORT

NLS_SORT specifies the collating sequence for character value comparison in various SQL operators and clauses.

Property	Description
Parameter type	String
Syntax	NLS_SORT = { BINARY | *linguistic_definition* }
Default value	Derived from NLS_LANGUAGE
Modifiable	ALTER SESSION
Modifiable in a PDB	Yes
Range of values	BINARY or any valid linguistic definition name
Basic	No

For example, NLS_SORT specifies the collating sequence for character value comparison in these SQL operators and clauses: ORDER BY, GROUP BY, comparison conditions (=, <>, <=, >=), IN, BETWEEN, LIKE, MIN/MAX, GREATEST/LEAST, and INSTR.

- If the value is BINARY, then comparison is based directly on byte values in the binary encoding of the character values being compared. The ordering depends on the character set of the compared values, which is either the database character set (for VARCHAR2, CHAR, LONG, and CLOB) or the national character set (for NVARCHAR2, NCHAR, and NCLOB).
- If the value is a named linguistic sort, then comparison is defined by this sort. A linguistic sort uses various rules to achieve ordering expected by speakers of one

or more natural languages. This is usually the same ordering that is used in dictionaries and telephone directories in those languages.

The exact operators and query clauses that obey the NLS_SORT parameter depend on the value of the NLS_COMP parameter. If an operator or clause does not obey the NLS_SORT value, as determined by NLS_COMP, the collation used is BINARY.

The BINARY comparison is faster and uses less resources than any linguistic comparison but for text in a natural language, it does not provide ordering expected by users.

The value of NLS_SORT affects execution plans of queries. Because a standard index cannot be used as a source of values sorted in a linguistic order, an explicit sort operation must usually be performed instead of an index range scan. A functional index on the NLSSORT function may be defined to provide values sorted in a linguistic order and reintroduce the index range scan to the execution plan.

Note:

The value of the initialization parameter NLS_SORT is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overriden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the NLS_LANG client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

See Also:

- *Oracle Database Globalization Support Guide* for more information about this parameter and a current listing of values you can specify

2.247 NLS_TERRITORY

NLS_TERRITORY specifies the name of the territory whose conventions are to be followed for day and week numbering.

Property	Description
Parameter type	String
Syntax	NLS_TERRITORY = *territory*
Default value	Operating system-dependent
Modifiable	ALTER SESSION
Modifiable in a PDB	Yes
Range of values	Any valid territory name
Basic	Yes

This parameter also establishes the default date format, the default decimal character and group separator, and the default ISO and local currency symbols.

For information on these settings, see "NLS_DATE_FORMAT", "NLS_NUMERIC_CHARACTERS", "NLS_CURRENCY", and "NLS_ISO_CURRENCY".

> **Note:**
>
> The value of this initialization parameter NLS_TERRITORY is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the NLS_LANG client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

Examples

For an example of overriding the default value for the NLS_TERRITORY parameter, see *Oracle Database Globalization Support Guide*.

> **See Also:**
>
> - *Oracle Database Globalization Support Guide* for a complete list of territories
> - Your operating system-specific Oracle documentation for the territory-dependent default values for these parameters

2.248 NLS_TIMESTAMP_FORMAT

NLS_TIMESTAMP_FORMAT defines the default timestamp format to use with the TO_CHAR and TO_TIMESTAMP functions.

Property	Description
Parameter type	String
Syntax	NLS_TIMESTAMP_FORMAT = "*format*"
Default value	Derived from NLS_TERRITORY
Modifiable	ALTER SESSION
Modifiable in a PDB	Yes
Range of values	Any valid datetime format mask
Basic	No

The value must be surrounded by quotation marks as follows:

```
NLS_TIMESTAMP_FORMAT = 'YYYY-MM-DD HH:MI:SS.FF'
```

You can specify the value of NLS_TIMESTAMP_FORMAT by setting it in the initialization parameter file. You can specify its value for a client as a client environment variable.

You can also alter the value of NLS_TIMESTAMP_FORMAT by changing its value in the initialization parameter and then restarting the instance. To alter the value during a session use the ALTER SESSION SET statement.

> **Note:**
>
> The value of this initialization parameter NLS_TIMESTAMP_FORMAT is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the NLS_LANG client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

> **See Also:**
>
> *Oracle Database Globalization Support Guide* for more information about this parameter

2.249 NLS_TIMESTAMP_TZ_FORMAT

NLS_TIMESTAMP_TZ_FORMAT defines the default timestamp with time zone format to use with the TO_CHAR and TO_TIMESTAMP_TZ functions.

Property	Description
Parameter type	String
Syntax	NLS_TIMESTAMP_TZ_FORMAT = "*format*"
Default value	Derived from NLS_TERRITORY
Modifiable	ALTER SESSION
Modifiable in a PDB	Yes
Range of values	Any valid datetime format mask
Basic	No

The value must be surrounded by quotation marks as follows:

```
NLS_TIMESTAMP_TZ_FORMAT = 'YYYY-MM-DD HH:MI:SS.FF TZH:TZM'
```

You can specify the value of NLS_TIMESTAMP_TZ_FORMAT by setting it in the initialization parameter file. You can specify its value for a client as a client environment variable.

You can also alter the value of NLS_TIMESTAMP_TZ_FORMAT by changing its value in the initialization parameter and then restarting the instance. To alter the value during a session use the ALTER SESSION SET statement.

> **Note:**
>
> The value of this initialization parameter `NLS_TIMESTAMP_TZ_FORMAT` is used to initialize the session value of this parameter, which is the actual value referenced by the SQL query processing. This initial value is overridden by a client-side value if the client uses the Oracle JDBC driver or if the client is OCI-based and the `NLS_LANG` client setting (environment variable) is defined. The initialization parameter value is, therefore, usually ignored.

> **See Also:**
>
> *Oracle Database Globalization Support Guide* for more information about this parameter

2.250 NONCDB_COMPATIBLE

`NONCDB_COMPATIBLE` enables you to get behavior similar to a non-CDB when issuing SQL commands inside a PDB in a CDB.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No

Set this parameter if you are using a single PDB in your CDB configuration and you have legacy code that causes `ORA-65040` when you run it in the PDB.

Values

- `TRUE`

  Indicates the behavior for SQL statements will be like a non-CDB although the statements are issued in a PDB in a CDB.

- `FALSE`

  Indicates the behavior will for SQL statements will be like a CDB. This is the default value of the parameter.

There are some statements (such as `ALTER DB BACKUP CONTROLFILE`) which can be issued in a non-CDB, but in a CDB they must be issued in the root (because they affect the whole CDB) and would result in an error if issued in a PDB.

Some `ALTER DATABASE` or `ALTER SYSTEM` statements are not permitted inside a PDB, and they will fail if `NONCDB_COMPATIBLE=FALSE` is set in `init.ora`. However, these statements will succeed if `NONCDB_COMPATIBLE=TRUE` is set.

See Also:

- *Oracle Multitenant Administrator's Guide* for an introduction to PDBs and CDBs
- *Oracle Multitenant Administrator's Guide* for information about the initialization parameters that control the memory usage of PDBs
- *Oracle Multitenant Administrator's Guide* for information about the ALTER SYSTEM statements that can be run in a PDB.

2.251 OBJECT_CACHE_MAX_SIZE_PERCENT

The **object cache** is a memory block on the client that allows applications to store entire objects and to navigate among them without round trips to the server. `OBJECT_CACHE_MAX_SIZE_PERCENT` specifies the percentage of the optimal cache size that the session object cache can grow past the optimal size.

Property	Description
Parameter type	Integer
Default value	`10`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM ... DEFERRED`
Modifiable in a PDB	Yes
Range of values	0 to operating system-dependent maximum
Basic	No

The maximum size is equal to the optimal size plus the product of this percentage and the optimal size. When the cache size exceeds this maximum size, the system will attempt to shrink the cache to the optimal size.

See Also:

- "OBJECT_CACHE_OPTIMAL_SIZE" for a description of the object cache
- *Pro*C/C++ Developer's Guide* and *Oracle Call Interface Developer's Guide* for information on precompiler use of the object cache

2.252 OBJECT_CACHE_OPTIMAL_SIZE

`OBJECT_CACHE_OPTIMAL_SIZE` specifies (in bytes) the size to which the session object cache is reduced when the size of the cache exceeds the maximum size.

Property	Description
Parameter type	Integer
Default value	`51200000` (50M)
Modifiable	`ALTER SESSION`, `ALTER SYSTEM ... DEFERRED`
Modifiable in a PDB	Yes
Range of values	10 KB to operating system-dependent maximum
Basic	No

The **object cache** is a memory block on the client that allows applications to store entire objects and to navigate among them without round trips to the server. On the server, it is used to cache frequently used objects requested as a result of client requests to help in performance.

> **See Also:**
>
> *Pro*C/C++ Developer's Guide* and *Oracle Call Interface Developer's Guide* for information on precompiler use of the object cache

2.253 OFS_THREADS

`OFS_THREADS` sets the maximum number of Oracle file system (OFS) threads that can be started to service Oracle file system requests.

Property	Description
Parameter type	Integer
Default value	`4`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	`2` to `128`
Basic	No
Oracle RAC	The same value should be specified on all instances.

> **Note:**
>
> This initialization parameter is supported only on the Linux operating system.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about the Oracle Database NFS server feature

2.254 OLAP_PAGE_POOL_SIZE

`OLAP_PAGE_POOL_SIZE` specifies (in bytes) the size of the OLAP page pool.

Property	Description
Parameter type	Big integer
Syntax	`OLAP_PAGE_POOL_SIZE = integer [K | M | G]`
Default value	`0`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM ... DEFERRED`
Modifiable in a PDB	Yes
Range of values	0, 2097152 (2 MB) to 2^{31} - 1
Basic	No

> **Caution:**
>
> Oracle strongly recommends that you leave this parameter set to its default value of `0`. This instructs the database to autonomously adjust the OLAP page pool size to serve the requirements of the analytic workspaces. Setting this parameter to a value other than `0` can lead to errors in OLAP processing or wasted memory.

> **See Also:**
>
> *Oracle OLAP User's Guide* for more information about the OLAP option for Oracle Database

2.255 ONE_STEP_PLUGIN_FOR_PDB_WITH_TDE

If a pluggable database (PDB) has Transparent Data Encryption-encrypted (TDE-encrypted) tables or tablespaces, you can enable `ONE_STEP_PLUGIN_FOR_PDB_WITH_TDE` on the target CDB to simplify the move of TDE keys in a single step PDB move operation.

`ONE_STEP_PLUGIN_FOR_PDB_WITH_TDE` eliminates the need of having to manually provide a keystore password when you import the TDE keys into the PDB after it has moved to the target CDB.

Property	Description
Parameter type	Boolean
Default value	FALSE
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	true | false
Basic	No
Oracle RAC	A different value can be set for this parameter on different Oracle RAC instances.

The default for ONE_STEP_PLUGIN_FOR_PDB_WITH_TDE is FALSE.

When ONE_STEP_PLUGIN_FOR_PDB_WITH_TDE is set to TRUE on the target CDB, the plug in of the PDB does not require a keystore password.

> **Note:**
>
> The ONE_STEP_PLUGIN_FOR_PDB_WITH_TDE parameter is deprecated in Oracle Database 23ai.
>
> ONE_STEP_PLUGIN_FOR_PDB_WITH_TDE enables you to clone remotely or to relocate encrypted PDBs without providing the Transparent Data Encryption (TDE) keystore password. However, EXTERNAL STORE provides the same functionality, and is universally applicable to all ADMINISTER KEY MANAGEMENT statements that do not change the TDE configuration. Instead of using ONE_STEP_PLUGIN_FOR_PDB_WITH_TDE, Oracle recommends that you use the IDENTIFIED BY EXTERNAL STORE clause for the ADMINISTER KEY MANAGEMENT statement.

2.256 OPEN_CURSORS

OPEN_CURSORS specifies the maximum number of open cursors (handles to private SQL areas) a session can have at once. You can use this parameter to prevent a session from opening an excessive number of cursors.

Property	Description
Parameter type	Integer
Default value	50
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	0 to 65535
Basic	Yes

It is important to set the value of OPEN_CURSORS high enough to prevent your application from running out of open cursors. The number will vary from one

application to another. Assuming that a session does not open the number of cursors specified by OPEN_CURSORS, there is no added overhead to setting this value higher than actually needed.

See Also:

- *Oracle Database Performance Tuning Guide* for more information on setting this parameter
- Your operating system-specific Oracle documentation for the range of values

2.257 OPEN_LINKS

OPEN_LINKS specifies the maximum number of concurrent open connections to remote databases in one session. These connections include database links, as well as external procedures and cartridges, each of which uses a separate process.

Property	Description
Parameter type	Integer
Default value	4
Modifiable	No
Modifiable in a PDB	Yes
Range of values	0 to 32768
Basic	No

Oracle counts one open link for the following:

- For each user that references a public or private database link
- For each external procedure or cartridge connection when it is executed for the first time

Both types of connections close when the session ends. You can also close a database link connection explicitly by issuing an ALTER SESSION CLOSE DATABASE LINK statement.

You should set this parameter to allow for the external procedure and cartridge connections expected during the session plus the number of databases referred to in typical distributed transactions (that is, a single SQL statement that references multiple databases), so that all the databases can be open to execute the statement. For example, if queries alternately access databases A, B, and C, and OPEN_LINKS is set to 2, time will be lost waiting while one connection is broken and another made. Increase the value if many different databases are accessed over time.

This parameter refers only to connections used for distributed transactions. Direct connections to a remote database specified as an application connects are not counted.

If you set OPEN_LINKS to 0, then no distributed transactions are allowed.

In a multitenant container database (CDB), the OPEN_LINKS parameter can be set at both the root and at the PDB level using either an initialization parameter file (PFILE) or server parameter file (SPFILE). You need to restart the instance or reopen the PDB for a new OPEN_LINKS value to become effective.

> **See Also:**
>
> "OPEN_LINKS_PER_INSTANCE" for information on setting open connections globally for a database instance

2.258 OPEN_LINKS_PER_INSTANCE

`OPEN_LINKS_PER_INSTANCE` specifies the maximum number of migratable open connections globally for each database instance.

Property	Description
Parameter type	Integer
Default value	`4`
Modifiable	No
Modifiable in a PDB	No
Range of values	0 to 2^{31} - 1
Basic	No
Oracle RAC	Multiple instances can have different values.

XA transactions use migratable open connections so that the connections are cached after a transaction is committed. Another transaction can use the connection, provided the user who created the connection is the same as the user who owns the transaction.

`OPEN_LINKS_PER_INSTANCE` is different from `OPEN_LINKS`, which indicates the number of connections from a session. The `OPEN_LINKS` parameter is not applicable to XA applications.

> **See Also:**
>
> - "OPEN_LINKS"
> - *Oracle Database Development Guide* for more information about using this parameter in Oracle XA applications

2.259 OPTIMIZER_ADAPTIVE_PLANS

`OPTIMIZER_ADAPTIVE_PLANS` controls adaptive plans. Adaptive plans are execution plans built with alternative choices that are decided at run time based on statistics collected as the query executes.

Property	Description
Parameter type	Boolean
Default value	`true`

Property	Description
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	true | false
Basic	No
Oracle RAC	The same value must be set on all instances

Setting this parameter to `false` disables the following adaptive features:

- Nested loop join/hash join selection
- Star transformation bitmap pruning
- Adaptive parallel distribution method

> **See Also:**
>
> *Oracle Database SQL Tuning Guide* for information about adaptive plans

2.260 OPTIMIZER_ADAPTIVE_REPORTING_ONLY

`OPTIMIZER_ADAPTIVE_REPORTING_ONLY` controls reporting-only mode for adaptive optimizations.

Property	Description
Parameter type	Boolean
Default value	FALSE
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	TRUE | FALSE
Basic	No

When `OPTIMIZER_ADAPTIVE_REPORTING_ONLY` is set to `FALSE`, reporting-only mode is off, and the adaptive optimizations are enabled as usual.

When `OPTIMIZER_ADAPTIVE_REPORTING_ONLY` is set to `TRUE`, adaptive optimizations run in reporting-only mode. With this setting, the information required for an adaptive optimization is gathered, but no action is taken to change the plan. For instance, an adaptive plan will always choose the default (optimizer-chosen) plan, but information is collected on what plan to adapt to in non-reporting mode. This information can be viewed in the adaptive plan report.

This parameter affects only adaptive optimizations that are enabled.

> **See Also:**
>
> - *Oracle Database SQL Tuning Guide* for more information about adaptive plans and automatic reoptimization
> - *Oracle Database SQL Tuning Guide* for information on controlling adaptive optimization

2.261 OPTIMIZER_ADAPTIVE_STATISTICS

`OPTIMIZER_ADAPTIVE_STATISTICS` controls adaptive statistics. Some query shapes are too complex to rely on base table statistics alone, so the optimizer augments these statistics with adaptive statistics.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No
Oracle RAC	The same value must be set on all instances

Setting this parameter to `false` disables the following adaptive features:

- SQL plan directives
- Statistics feedback for joins
- Adaptive dynamic sampling for parallel execution

> **Note:**
>
> Setting `OPTIMIZER_ADAPTIVE_STATISTICS` to `false` preserves the statistics feedback functionality that was introduced in Oracle Database 11*g*.
>
> `OPTIMIZER_ADAPTIVE_STATISTICS` does not control the creation of SQL plan directives. SQL plan directives will be created even if this parameter is `false`, but they will not be used to refine SQL execution plans with dynamic sampling.

> **See Also:**
>
> *Oracle Database SQL Tuning Guide* for information about adaptive plans

2.262 OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES

`OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES` enables or disables the automatic recognition of repeatable SQL statements, as well as the generation of SQL plan baselines for such statements.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No

> **See Also:**
>
> *Oracle Database SQL Tuning Guide* for more information about the optimizer

2.263 OPTIMIZER_CAPTURE_SQL_QUARANTINE

`OPTIMIZER_CAPTURE_SQL_QUARANTINE` enables or disables the automatic creation of SQL Quarantine configurations.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No
Oracle RAC	Different instances can use different values.

Values:

- `true`

  Enables the automatic creation of SQL Quarantine configurations. If the Resource Manager terminates a SQL statement because the statement has exceeded resource limits, then the database automatically creates a SQL Quarantine configuration for the execution plan used by the terminated SQL statement. Note that the *plan* for a terminated SQL statement is quarantined, not the statement itself.

- `false`

  Disables the automatic creation of SQL Quarantine configurations.

See Also:

- "DBA_SQL_QUARANTINE"
- "OPTIMIZER_USE_SQL_QUARANTINE"
- *Oracle Database SQL Tuning Guide* for more information about SQL Quarantine

2.264 OPTIMIZER_CROSS_SHARD_RESILIENCY

`OPTIMIZER_CROSS_SHARD_RESILIENCY` enables resilient execution of cross shard queries.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No
Oracle RAC	The same value must be used on all instances.

When this parameter is set to `true` and a cross-shard query fails on one or more shards, the query execution continues on the Oracle Data Guard standbys of the failed shards. This parameter is not set to `true` by default, because there may be performance overhead for the resilient query execution.

2.265 OPTIMIZER_DYNAMIC_SAMPLING

`OPTIMIZER_DYNAMIC_SAMPLING` controls both when the database gathers dynamic statistics, and the size of the sample that the optimizer uses to gather the statistics.

Property	Description
Parameter type	Integer
Default value	If `OPTIMIZER_FEATURES_ENABLE` is set to `10.0.0` or higher, then `2` If `OPTIMIZER_FEATURES_ENABLE` is set to `9.2.0`, then `1` If `OPTIMIZER_FEATURES_ENABLE` is set to `9.0.1` or lower, then `0`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`0` to `11`
Basic	No

> **Note:**
>
> Dynamic statistics were called dynamic sampling in releases earlier than Oracle Database 12*c* Release 1 (12.1).

If the value of `OPTIMIZER_DYNAMIC_SAMPLING` is set to `11`, the `OPTIMIZER_FEATURES_ENABLE` setting has no effect on the `OPTIMIZER_DYNAMIC_SAMPLING` setting.

> **See Also:**
>
> *Oracle Database SQL Tuning Guide* for detailed information about the values (0 – 11) that can be set for the `OPTIMIZER_DYNAMIC_SAMPLING` parameter.

2.266 OPTIMIZER_FEATURES_ENABLE

`OPTIMIZER_FEATURES_ENABLE` acts as an umbrella parameter for enabling a series of optimizer features based on an Oracle release number.

Property	Description
Parameter type	String
Syntax	`OPTIMIZER_FEATURES_ENABLE = { 8.0.0 | 8.0.3 | 8.0.4 | 8.0.5 | 8.0.6 | 8.0.7 | 8.1.0 | 8.1.3 | 8.1.4 | 8.1.5 | 8.1.6 | 8.1.7 | 9.0.0 | 9.0.1 | 9.2.0 | 9.2.0.8 | 10.1.0 | 10.1.0.3 | 10.1.0.4 | 10.1.0.5 | 10.2.0.1 | 10.2.0.2 | 10.2.0.3 | 10.2.0.4 | 10.2.0.5 | 11.1.0.6 | 11.1.0.7 | 11.2.0.1 | 11.2.0.2 | 11.2.0.3 | 11.2.0.4 | 12.1.0.1 | 12.1.0.2 | 12.2.0.1 | 18.1.0 | 19.1.0 | 21.1.0 | 23.1.0 }`
Default value	`23.1.0`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

For example, if you upgrade your database from release 19c to release 23ai, but you want to keep the release 19c optimizer behavior, you can do so by setting this parameter to `19.1.0`. At a later time, you can try the enhancements introduced in releases up to and including release 23ai by setting the parameter to `23.1.0`.

> **Note:**
>
> When setting this parameter to a value representing Oracle Database 18c or later, you must specify three numeric values separated by periods, such as `21.1.0` or `23.1.0`.

Table 2-6 describes some of the optimizer features that are enabled when you set the `OPTIMIZER_FEATURES_ENABLE` parameter to `12.1.0.2` or a later release.

Table 2-6 Optimizer Features for Oracle Database 12c and Later Releases

Features	12.1.0.2	12.2.0.1	18c	19c	21c	23ai
Adaptive Query Optimization	X	X	X	X	X	X
Online statistics gathering for bulk loads	X	X	X	X	X	X
Session level statistics for Global Temporary Tables	X	X	X	X	X	X
Multi-table left outer joins	X	X	X	X	X	X
Lateral views	X	X	X	X	X	X
Batch table access by rowid	X	X	X	X	X	X
Null accepting semi joins	X	X	X	X	X	X
Scalar subquery unnesting	X	X	X	X	X	X
Conversion of joins that produce unnecessary duplicates to semi-joins	X	X	X	X	X	X
Parallel Union and Parallel Union All operations	X	X	X	X	X	X
Enhance Auto DOP	X	X	X	X	X	X
Approximate count distinct	X	X	X	X	X	X
Support for Oracle Database In-Memory	X	X	X	X	X	X
Group-by and aggregation elimination	X	X	X	X	X	X
Query rewrite for approximate query processing		X	X	X	X	X
Statistics advisor		X	X	X	X	X
Support for sharded databases		X	X	X	X	X
Expression tracking		X	X	X	X	X
Space-saving algorithm for partition synopses		X	X	X	X	X
Oracle In-Memory Database statistics		X	X	X	X	X
Support for sharding		X	X	X	X	X
Cost-based OR expansion		X	X	X	X	X
Sub-query elimination		X	X	X	X	X
Multi-column key join elimination		X	X	X	X	X
SQL Quarantine				X	X	X
Gathering and use of real-time statistics				X	X	X
Use of automatic indexes				X	X	X
Exists-to-any rewrite of subqueries					X	X
`WITH` clause filter predicate pushdown					X	X
Number of distinct value (NDV) modeling for real time statistics					X	X
Pushing down group-by into union-all branches						X

Table 2-6 (Cont.) Optimizer Features for Oracle Database 12c and Later Releases

Features	12.1.0.2	12.2.0.1	18c	19c	21c	23ai
Subsumption of views or subqueries						X

> **See Also:**
>
> *Oracle Database SQL Tuning Guide* for more information about the optimizer

2.267 OPTIMIZER_IGNORE_HINTS

`OPTIMIZER_IGNORE_HINTS` enables embedded hints to be ignored.

Property	Description
Parameter type	Boolean
Default value	`FALSE`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No
Oracle RAC	Different values can be set on different instances.

When this parameter is set to `TRUE`, the optimizer ignores embedded hints.

The default value is `FALSE`. When this parameter's value is `FALSE`, the optimizer does not ignore embedded hints.

2.268 OPTIMIZER_IGNORE_PARALLEL_HINTS

`OPTIMIZER_IGNORE_PARALLEL_HINTS` enables embedded parallel hints to be ignored.

Property	Description
Parameter type	Boolean
Default value	`FALSE`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No
Oracle RAC	Different values can be set on different instances.

When this parameter is set to `TRUE`, the optimizer ignores embedded parallel hints.

The default value is FALSE. When this parameter's value is FALSE, the optimizer does not ignore parallel embedded hints.

2.269 OPTIMIZER_INDEX_CACHING

OPTIMIZER_INDEX_CACHING lets you adjust the behavior of cost-based optimization to favor nested loops joins and IN-list iterators.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	0 to 100
Basic	No

The cost of executing an index using an IN-list iterator or of executing a nested loops join when an index is used to access the inner table depends on the caching of that index in the buffer cache. The amount of caching depends on factors that the optimizer cannot predict, such as the load on the system and the block access patterns of different users.

You can modify the optimizer's assumptions about index caching for nested loops joins and IN-list iterators by setting this parameter to a value between 0 and 100 to indicate the percentage of the index blocks the optimizer should assume are in the cache. Setting this parameter to a higher value makes nested loops joins and IN-list iterators look less expensive to the optimizer. As a result, it will be more likely to pick nested loops joins over hash or sort-merge joins and to pick indexes using IN-list iterators over other indexes or full table scans. The default for this parameter is 0, which results in default optimizer behavior.

> **See Also:**
>
> *Oracle Database SQL Language Reference* for additional information about this initialization parameter

2.270 OPTIMIZER_INDEX_COST_ADJ

OPTIMIZER_INDEX_COST_ADJ lets you tune optimizer behavior for access path selection to be more or less index friendly—that is, to make the optimizer more or less prone to selecting an index access path over a full table scan.

Property	Description
Parameter type	Integer
Default value	100
Modifiable	ALTER SESSION, ALTER SYSTEM

Property	Description
Modifiable in a PDB	Yes
Range of values	1 to 10000
Basic	No

The default for this parameter is 100 percent, at which the optimizer evaluates index access paths at the regular cost. Any other value makes the optimizer evaluate the access path at that percentage of the regular cost. For example, a setting of 50 makes the index access path look half as expensive as normal.

> **Note:**
>
> The adjustment does not apply to user-defined cost functions for domain indexes.

> **See Also:**
>
> *Oracle Database SQL Language Reference* for additional information about this initialization parameter

2.271 OPTIMIZER_INMEMORY_AWARE

`OPTIMIZER_INMEMORY_AWARE` enables or disables all of the optimizer cost model enhancements for in-memory.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No
Oracle RAC	All instances should use the same value

Setting the parameter to `false` causes the optimizer to ignore the in-memory property of tables during the optimization of SQL statements. This behavior can also be achieved by setting the `OPTIMIZER_FEATURES_ENABLE` initialization parameter to values lower than 12.1.0.2.

See Also:

- "OPTIMIZER_FEATURES_ENABLE"
- *Oracle Database Concepts* and *Oracle Database SQL Tuning Guide* for more information about the optimizer

2.272 OPTIMIZER_MODE

`OPTIMIZER_MODE` establishes the default behavior for choosing an optimization approach for the instance.

Property	Description
Parameter type	String
Syntax	`OPTIMIZER_MODE = { FIRST_ROWS_[1 | 10 | 100 | 1000] | FIRST_ROWS | ALL_ROWS }`
Default value	`ALL_ROWS`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

Values

- `FIRST_ROWS_`*n*

  The optimizer uses a cost-based approach and optimizes with a goal of best response time to return the first *n* rows (where *n* = 1, 10, 100, 1000).

- `FIRST_ROWS`

  The optimizer uses a mix of costs and heuristics to find a best plan for fast delivery of the first few rows.

  `FIRST_ROWS` is available for backward compatibility and plan stability; use `FIRST_ROWS_`*n* instead.

- `ALL_ROWS`

  The optimizer uses a cost-based approach for all SQL statements in the session and optimizes with a goal of best throughput (minimum resource use to complete the entire statement).

See Also:

- *Oracle Database SQL Tuning Guide* for more information on setting this parameter
- *Oracle Database Concepts* and *Oracle Database SQL Tuning Guide* for more information about the optimizer

2.273 OPTIMIZER_REAL_TIME_STATISTICS

`OPTIMIZER_REAL_TIME_STATISTICS` controls whether the database automatically gathers real-time statistics during conventional DML operations.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No
Oracle RAC	Different values can be set on different instances.

When this parameter is set to `true`, the database automatically gathers real-time statistics during conventional DML operations. The default setting is `false`, which means real-time statistics are disabled.

2.274 OPTIMIZER_SESSION_TYPE

`OPTIMIZER_SESSION_TYPE` controls how the database performs automatic indexing for SQL statements in the session.

Property	Description
Parameter type	String
Syntax	`OPTIMIZER_SESSION_TYPE = { NORMAL	CRITICAL	ADHOC }`
Default value	`NORMAL`
Modifiable	`ALTER SESSION`
Modifiable in a PDB	No
Basic	No

Values:

- `NORMAL`

  Automatic indexing is performed normally for SQL statements in the session. The automatic indexing process identifies auto index candidates, creates auto indexes, and verifies them against SQL statements.

- `CRITICAL`

  Automatic indexing is performed for SQL statements in the session, with a higher priority given to long-running statements. The automatic indexing process identifies auto index candidates and creates auto indexes. However, auto indexes are verified against SQL statements in descending order of elapsed execution time for each statement.

- `ADHOC`

  Automatic indexing is suspended for SQL statements in the session. The automatic indexing process does not identify auto index candidates, create auto indexes, or verify auto indexes against SQL statements. This setting is useful when running ad hoc queries or testing new functionality.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about how automatic indexing works

2.275 OPTIMIZER_USE_INVISIBLE_INDEXES

`OPTIMIZER_USE_INVISIBLE_INDEXES` enables or disables the use of invisible indexes.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No

Values

- `true`

  Invisible indexes are treated as visible (normal) indexes.

- `false`

  Invisible indexes will not be considered by the optimizer but will still be maintained by DML operations.

2.276 OPTIMIZER_USE_PENDING_STATISTICS

`OPTIMIZER_USE_PENDING_STATISTICS` specifies whether the optimizer uses pending statistics when compiling SQL statements.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No

See Also:

Oracle Database SQL Tuning Guide for more information on setting this parameter

2.277 OPTIMIZER_USE_SQL_PLAN_BASELINES

`OPTIMIZER_USE_SQL_PLAN_BASELINES` enables or disables the use of SQL plan baselines stored in SQL Management Base.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No

When enabled, the optimizer looks for a SQL plan baseline for the SQL statement being compiled. If one is found in SQL Management Base, then the optimizer will cost each of the baseline plans and pick one with the lowest cost.

See Also:

- *Oracle Database SQL Tuning Guide* for information on enabling automatic initial plan capture
- *Oracle Database SQL Tuning Guide* for information about configuring the capture and use of SQL plan baselines

2.278 OPTIMIZER_USE_SQL_QUARANTINE

`OPTIMIZER_USE_SQL_QUARANTINE` determines whether the optimizer considers SQL Quarantine configurations when choosing an execution plan for a SQL statement.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No
Oracle RAC	Different instances can use different values.

Values:

- `true`

  The optimizer considers SQL Quarantine configurations when choosing an execution plan for a SQL statement. The statement will be terminated if it would otherwise use a quarantined execution plan.

- `false`

  The optimizer ignores SQL Quarantine configurations when choosing an execution plan for a SQL statement. It may use any execution plan, regardless of its quarantine status.

See Also:

- "DBA_SQL_QUARANTINE"
- "OPTIMIZER_CAPTURE_SQL_QUARANTINE"
- *Oracle Database SQL Tuning Guide* for more information about SQL Quarantine

2.279 OS_AUTHENT_PREFIX

`OS_AUTHENT_PREFIX` specifies a prefix that Oracle Database uses to authenticate users attempting to connect to the server.

Property	Description
Parameter type	String
Syntax	`OS_AUTHENT_PREFIX = authentication_prefix`
Default value	`OPS$`
Modifiable	No

Property	Description
Modifiable in a PDB	No
Basic	No

Oracle Database concatenates the value of this parameter to the beginning of the user's operating system account name. When a connection request is attempted, Oracle Database compares the prefixed username with Oracle user names in the database.

The default value of this parameter is `OPS$` for backward compatibility with previous versions. However, you might prefer to set the prefix value to "" (a null string), thereby eliminating the addition of any prefix to operating system account names.

Note:

The text of the `OS_AUTHENT_PREFIX` parameter is case sensitive on some operating systems.

See Also:

- *Oracle Database Security Guide* for more information on setting this parameter
- Your operating system-specific Oracle documentation for the default value

2.280 OS_ROLES

`OS_ROLES` determines whether Oracle or the operating system identifies and manages the roles of each username.

Note:

Enterprise User Security (EUS) is deprecated with Oracle Database 23ai.

Oracle recommends that you migrate to using Centrally Managed Users (CMU). This feature enables you to directly connect with Microsoft Active Directory without an intervening directory service for enterprise user authentication and authorization to the database. If your Oracle Database is in the cloud, you can also choose to move to one of the newer integrations with a cloud identity provider.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	No
Modifiable in a PDB	No

Property	Description
Range of values	`true | false`
Basic	No

Values

- `TRUE`

  The operating system completely manages the role grants for all database usernames. When a user attempts to create a session, the username's security domain is initialized using the roles identified by the operating system.

  Revocation by Oracle of roles granted by the operating system is ignored, as are any roles previously granted by Oracle.

- `FALSE`

  Oracle identifies and manages the roles.

> **See Also:**
>
> - *Oracle Database Administrator's Guide* and *Oracle Database Enterprise User Security Administrator's Guide* for more information on roles and on setting this parameter
> - "REMOTE_OS_ROLES"

2.281 OUTBOUND_DBLINK_PROTOCOLS

`OUTBOUND_DBLINK_PROTOCOLS` specifies the network protocols allowed for communicating for outbound database links in the database.

Property	Description
Parameter type	String
Syntax	`OUTBOUND_DBLINK_PROTOCOLS = { ALL | NONE | [ TCP | [, ] | TCPS | [, ] | IPC ] }`
Default value	`ALL`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No
Oracle RAC	The same value must be used on all instances.

Specify a value of `ALL` to allow all network protocols, and a value of `NONE` to disallow all network communication protocols for database link communication. Specify a single value or a list of comma separated network communication protocols to allow only certain network protocols for outbound database link communication.

2.282 PARALLEL_ADAPTIVE_MULTI_USER

`PARALLEL_ADAPTIVE_MULTI_USER`, when set to `true`, enables an adaptive algorithm designed to improve performance in multiuser environments that use parallel execution.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No

The algorithm automatically reduces the requested degree of parallelism based on the system load at query startup time. The effective degree of parallelism is based on the default degree of parallelism, or the degree from the table or hints, divided by a reduction factor.

The algorithm assumes that the system has been tuned for optimal performance in a single-user environment.

Tables and hints use the default degree of parallelism.

Note:

The `PARALLEL_ADAPTIVE_MULTI_USER` initialization parameter is deprecated in Oracle Database 12*c* Release 2 (12.2.0.1) and may be removed in a future release. Oracle recommends that you use the parallel statement queuing feature instead.

See Also:

- *Oracle Database SQL Language Reference* for more information about optimizer hints
- *Oracle Database VLDB and Partitioning Guide* for more information about parallel statement queuing

2.283 PARALLEL_DEGREE_LIMIT

`PARALLEL_DEGREE_LIMIT` limits the degree of parallelism used by the optimizer to ensure that parallel server processes do not flood the system.

Property	Description
Parameter type	String

Property	Description
Syntax	PARALLEL_DEGREE_LIMIT = { CPU | AUTO | IO | *integer* }
Default value	CPU
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No

With automatic degree of parallelism, Oracle automatically decides whether a statement should execute in parallel and what degree of parallelism the statement should use. The optimizer automatically determines the degree of parallelism for a statement based on the resource requirements of the statement. However, PARALLEL_DEGREE_LIMIT enforces the limit for the degree of parallelism used by the optimizer.

Values

- CPU

  The maximum degree of parallelism is limited by the number of CPUs in the system. The formula used to calculate the limit is PARALLEL_THREADS_PER_CPU * CPU_COUNT * the number of instances available (by default, all the opened instances on the cluster but can be constrained using PARALLEL_INSTANCE_GROUP or service specification). This is the default.

- AUTO

  This value is equivalent to the CPU value.

- IO

  The maximum degree of parallelism the optimizer can use is limited by the I/O capacity of the system. The value is calculated by dividing the total system throughput by the maximum I/O bandwidth per process. You must run the DBMS_RESOURCE_MANAGER.CALIBRATE_IO procedure on the system to use the IO setting. This procedure will calculate the total system throughput and the maximum I/O bandwidth per process.

- *integer*

  A numeric value for this parameter specifies the maximum degree of parallelism the optimizer can choose for a SQL statement when automatic degree of parallelism is active. Automatic degree of parallelism is only enabled if PARALLEL_DEGREE_POLICY is set to ADAPTIVE, AUTO, or LIMITED.

See Also:

- *Oracle Database VLDB and Partitioning Guide* for information about automatic degree of parallelism
- *Oracle Database PL/SQL Packages and Types Reference* for information on the DBMS_RESOURCE_MANAGER.CALIBRATE_IO procedure

2.284 PARALLEL_DEGREE_POLICY

PARALLEL_DEGREE_POLICY specifies whether automatic degree of parallelism, statement queuing, and in-memory parallel execution will be enabled.

Property	Description
Parameter type	String
Syntax	PARALLEL_DEGREE_POLICY = { MANUAL | LIMITED | AUTO | ADAPTIVE }
Default value	MANUAL
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No

Values

> **Note:**
>
> Automatic degree of parallelism will be enabled regardless of the value of PARALLEL_DEGREE_POLICY if a PARALLEL hint is used at the SQL statement level.

- MANUAL

  Disables automatic degree of parallelism, statement queuing, and in-memory parallel execution. This reverts the behavior of parallel execution to what it was prior to Oracle Database 11*g* Release 2 (11.2). This is the default.

- LIMITED

  Enables automatic degree of parallelism for some statements but statement queuing and in-memory Parallel Execution are disabled. Automatic degree of parallelism is only applied to those statements that access tables or indexes decorated explicitly with the DEFAULT degree of parallelism using the PARALLEL clause. Statements that do not access any tables or indexes decorated with the DEFAULT degree of parallelism will retain the MANUAL behavior.

- AUTO

  Enables automatic degree of parallelism, statement queuing, and in-memory parallel execution.

- ADAPTIVE

  This value enables automatic degree of parallelism, statement queuing and in-memory parallel execution, similar to the AUTO value. In addition, performance feedback is enabled. Performance feedback helps to improve the degree of parallelism automatically chosen for repeated SQL statements. After the initial execution of a statement, the degree of parallelism chosen by the optimizer is compared to the degree of parallelism computed based on the actual execution performance. If they vary significantly, then the statement is marked for re-parse and the initial execution performance statistics (for

example, CPU-time) are provided as feedback for subsequent executions. The optimizer uses the initial execution performance statistics to better determine a degree of parallelism for subsequent executions.

See Also:

- *Oracle Database SQL Language Reference* for information about `PARALLEL` hints
- *Oracle Database VLDB and Partitioning Guide* for information about automatic degree of parallelism

2.285 PARALLEL_EXECUTION_MESSAGE_SIZE

`PARALLEL_EXECUTION_MESSAGE_SIZE` specifies the size of messages used for parallel execution (formerly referred to as parallel query, PDML, Parallel Recovery, replication).

Property	Description
Parameter type	Integer
Default value	Operating system-dependent
Modifiable	No
Modifiable in a PDB	No
Range of values	Minimum: 2148 Maximum: 65536, but some operating systems may have a smaller value
Basic	No
Oracle RAC	Multiple instances must have the same value.

On most platforms, the default value is as follows:

- `16384` bytes if `COMPATIBLE` is set to `11.2.0` or higher
- `2148` bytes if `COMPATIBLE` is less than `11.2.0`

The default value is adequate for most applications. Larger values require a larger shared pool. Larger values result in better performance at the cost of higher memory use. For this reason, replication gets no benefit from increasing the size.

See Also:

Oracle Database VLDB and Partitioning Guide to learn how this parameter affects memory consumption for parallel operations, including parallel execution

2.286 PARALLEL_FORCE_LOCAL

PARALLEL_FORCE_LOCAL controls parallel execution in an Oracle RAC environment.

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	true | false
Basic	No

By default, the parallel server processes selected to execute a SQL statement can operate on any or all Oracle RAC nodes in the cluster. By setting PARALLEL_FORCE_LOCAL to true, the parallel server processes are restricted so that they can only operate on the same Oracle RAC node where the query coordinator resides (the node on which the SQL statement was executed).

> **See Also:**
>
> *Oracle Database VLDB and Partitioning Guide* for more information about this parameter

2.287 PARALLEL_INSTANCE_GROUP

Used in conjunction with services or with the INSTANCE_GROUPS parameter, PARALLEL_INSTANCE_GROUP lets you restrict parallel query operations to a limited number of instances.

Property	Description
Parameter type	String
Syntax	PARALLEL_INSTANCE_GROUP = *service_name* | *group_name*
Default value	There is no default value; parallel execution is enabled across all currently active instances.
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	Any service name or any group name specified in the INSTANCE_GROUPS parameter of any active instance
Basic	No
Oracle RAC	Multiple instances can have different values.

PARALLEL_INSTANCE_GROUP is an Oracle RAC parameter that you can specify in parallel mode only. Note that the INSTANCE_GROUPS parameter has been deprecated.

This parameter identifies the parallel instance group Oracle will use for spawning parallel execution processes. If used in conjunction with services, then parallel operations will spawn parallel execution processes only on instances defined in the service. If used in conjunction with INSTANCE_GROUPS, then parallel operations will spawn parallel execution processes only on instances that specify a matching group in their INSTANCE_GROUPS parameter.

If the value assigned to PARALLEL_INSTANCE_GROUP is the name of a service or group that does not exist, then the operation runs serially. No parallelism is used.

2.288 PARALLEL_MAX_SERVERS

PARALLEL_MAX_SERVERS specifies the maximum number of parallel execution processes and parallel recovery processes for an instance. As demand increases, Oracle Database increases the number of processes from the number created at instance startup up to this value.

Property	Description
Parameter type	Integer
Default value	PARALLEL_THREADS_PER_CPU * CPU_COUNT * *concurrent_parallel_users* * 5
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	0 to 32767
Basic	No
Oracle RAC	Multiple instances can have different values.

> **Note:**
>
> This parameter applies to parallel execution in exclusive mode as well as in a Real Application Clusters environment.

The number of concurrent parallel users running at default degree of parallelism on an instance depends on the memory initialization parameter settings for the instance. For example, if the MEMORY_TARGET or SGA_TARGET initialization parameter is set, then the number of concurrent_parallel_users = 4. If neither MEMORY_TARGET or SGA_TARGET is set, then PGA_AGGREGATE_TARGET is examined. If a value is set for PGA_AGGREGATE_TARGET, then concurrent_parallel_users = 2. If a value is not set for PGA_AGGREGATE_TARGET, then concurrent_parallel_users = 1.

The database system always reserves a certain number of reserved processes. Therefore, the following two values are taken into account when setting the PARALLEL_MAX_SERVERS initialization parameter:

- The default value of PARALLEL_MAX_SERVERS determined using the calculation in the table above
- The value of the PROCESSES initialization parameter minus the number of reserved processes

The lower of the two values is used as the default value of PARALLEL_MAX_SERVERS, and if you attempt to explicitly set PARALLEL_MAX_SERVERS to a value that is higher than either of the values, then the setting is adjusted to the lower of the two values.

When the PARALLEL_MAX_SERVERS parameter is set to a value lower than the value in the table above, the lower default value enables the database to start service processes and allows user processes to connect to the database.

The default value for PARALLEL_MAX_SERVERS for a PDB is determined using the calculation in the table above with the PDB's CPU_COUNT value.

Note:

If you set this parameter too low, then some queries may not have a parallel execution process available to them during query processing. If you set it too high, then memory resource shortages may occur during peak periods, which can degrade performance.

See Also:

Oracle Database SQL Tuning Guide for more information about parallel execution

2.289 PARALLEL_MIN_DEGREE

PARALLEL_MIN_DEGREE controls the minimum degree of parallelism computed by automatic degree of parallelism.

Property	Description
Parameter type	String
Syntax	PARALLEL_MIN_DEGREE = [n | CPU]
Default value	1
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	A different value can be set on different instances.

The value of PARALLEL_MIN_DEGREE is either a number that corresponds to the lower bound on the degree of parallelism computed by automatic degree of parallelism, or the string value CPU, which is computed by the function CPU_COUNT * PARALLEL_THREADS_PER_CPU.

The default value of PARALLEL_MIN_DEGREE is 1.

Note:

PARALLEL_MIN_DEGREE has no impact in either of these cases:

- When the value of PARALLEL_MIN_DEGREE is greater than the value of CPU_COUNT
- When the object is Oracle-owned, such as a dictionary table or view created on a dictionary table

See Also:

- "PARALLEL_DEGREE_LIMIT"
- *Oracle Database VLDB and Partitioning Guide* for information about how the optimizer automatically determines the degree of parallelism for a statement

2.290 PARALLEL_MIN_PERCENT

PARALLEL_MIN_PERCENT lets you specify the minimum percentage of the requested number of parallel execution processes required for parallel execution.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SESSION
Modifiable in a PDB	No
Range of values	0 to 100
Basic	No
Oracle RAC	Multiple instances can have different values.

This parameter controls the behavior for parallel operations when parallel statement queuing is not enabled (when PARALLEL_DEGREE_POLICY is set to manual or limited). It ensures that an operation always gets a minimum percentage of parallel execution servers or errors out. Setting this parameter ensures that parallel operations will not execute unless adequate resources are available. The default value of 0 means that no minimum percentage of processes has been set.

Consider the following settings:

```
PARALLEL_MIN_PERCENT = 50
PARALLEL_MIN_SERVERS = 5
PARALLEL_MAX_SERVERS = 10
```

If 8 of the 10 parallel execution processes are busy, only 2 processes are available. If you then request a query with a degree of parallelism of 8, the minimum 50% will not be met.

You can use this parameter with `PARALLEL_ADAPTIVE_MULTI_USER`. In a multi-user environment, an individual user or application can set `PARALLEL_MIN_PERCENT` to a minimum value until sufficient resources are available on the system and an acceptable degree of parallelism is returned.

See Also:

- *Oracle Database SQL Tuning Guide* for more information about parallel execution
- "PARALLEL_DEGREE_POLICY", "PARALLEL_MAX_SERVERS", "PARALLEL_MIN_SERVERS", and "PARALLEL_ADAPTIVE_MULTI_USER"

2.291 PARALLEL_MIN_SERVERS

`PARALLEL_MIN_SERVERS` is the number of parallel execution processes Oracle creates when the instance is started. These processes will be kept active to service parallel statements.

Property	Description
Parameter type	Integer
Default value	`CPU_COUNT * PARALLEL_THREADS_PER_CPU * 2`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	Default value to the value of `PARALLEL_MAX_SERVERS`
Basic	No
Oracle RAC	Multiple instances can have different values.

Note:

This parameter applies to parallel execution in exclusive mode as well as in an Oracle Real Application Clusters environment.

Note:

When the `PROCESSES` initialization parameter is set to a value that is lower than the documented default value for the `PARALLEL_MIN_SERVERS` parameter in the table above, the database sets the default value of `PARALLEL_MIN_SERVERS` to a value that is lower than the documented default value. The lower default value enables the database to start service processes and allows user processes to connect to the database.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about parallel execution servers

2.292 PARALLEL_MIN_TIME_THRESHOLD

`PARALLEL_MIN_TIME_THRESHOLD` specifies the minimum execution time a statement should have before the statement is considered for automatic degree of parallelism.

Property	Description
Parameter type	String
Syntax	`PARALLEL_MIN_TIME_THRESHOLD = { AUTO | integer }`
Default value	`AUTO`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

By default, this parameter is set to 10 seconds. Automatic degree of parallelism is only enabled if `PARALLEL_DEGREE_POLICY` is set to `ADAPTIVE`, `AUTO`, or `LIMITED`.

If all tables referenced by a SQL statement use In-Memory Column Store (IM column store), then `PARALLEL_MIN_TIME_THRESHOLD` defaults to 1.

> **See Also:**
>
> *Oracle Database VLDB and Partitioning Guide* for information about automatic degree of parallelism

2.293 PARALLEL_SERVERS_TARGET

`PARALLEL_SERVERS_TARGET` specifies the number of parallel server processes allowed to run parallel statements before statement queuing will be used.

Property	Description
Parameter type	Integer
Default value	For a CDB: Equal to the `PARALLEL_MAX_SERVERS` value for the CDB. For a PDB or non-CDB: `PARALLEL_THREADS_PER_CPU` * `CPU_COUNT` * *`concurrent_parallel_users`* * 2
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes

Property	Description
Range of values	0 to PARALLEL_MAX_SERVERS
Basic	No

When the parameter PARALLEL_DEGREE_POLICY is set to ADAPTIVE or AUTO, Oracle will queue SQL statements that require parallel execution, if the necessary parallel server processes are not available. In a single instance database, statement queuing will begin once the number of parallel server processes active on the system is equal to or greater than PARALLEL_SERVERS_TARGET. In an Oracle RAC database, a statement running on one instance can allocate parallel server processes on another instance when necessary. For example, if a statement running on one instance requires parallel execution, but the number of parallel server processes active on that instance is equal to or greater than the value of PARALLEL_SERVERS_TARGET for that instance, then the statement can allocate parallel server processes on a different instance. Therefore, statement queuing in an Oracle RAC database will begin only when every instance has reached its PARALLEL_SERVER_TARGET threshold.

Note:

Consumer groups that have been marked with the PARALLEL_STMT_CRITICAL directive set to BYPASS_QUEUE are allowed to bypass the parallel statement queue, and therefore may drive the total number of active parallel server processes beyond PARALLEL_SERVERS_TARGET. Parallel statements issued with PARALLEL_DEGREE_POLICY not set to ADAPTIVE and AUTO can also drive the total number of active parallel server processes beyond PARALLEL_SERVERS_TARGET.

By default, PARALLEL_SERVERS_TARGET is set lower than the maximum number of parallel server processes allowed on the system (PARALLEL_MAX_SERVERS) to ensure each parallel statement will get all of the parallel server resources required and to prevent overloading the system with parallel server processes.

The number of concurrent parallel users running at default degree of parallelism on an instance depends on the memory initialization parameter settings for the instance. For example, if the MEMORY_TARGET or SGA_TARGET initialization parameter is set, then the number of concurrent_parallel_users = 4. If neither MEMORY_TARGET or SGA_TARGET is set, then PGA_AGGREGATE_TARGET is examined. If a value is set for PGA_AGGREGATE_TARGET, then concurrent_parallel_users = 2. If a value is not set for PGA_AGGREGATE_TARGET, then concurrent_parallel_users = 1.

Note that all serial (non-parallel) statements will execute immediately even if statement queuing has been activated.

By default, all PDB queries are subjected to queuing at the PDB level first by the PDB's PARALLEL_SERVERS_TARGET value, and then at the CDB level by the CDB's PARALLEL_SERVERS_TARGET value. This default behavior prevents any SQL statement inside a PDB from getting downgraded if parallel servers are exhausted in the CDB.

Parallel statement queuing is enabled by default at the CDB level because the CDB has a default value for PARALLEL_SERVERS_TARGET. You can disable parallel statement queuing at the CDB level by using ALTER SYSTEM to set PARALLEL_SERVERS_TARGET to 0 for the CDB.

The default value for PARALLEL_SERVERS_TARGET for a PDB is determined using the calculation in the table above with the PDB's CPU_COUNT value.

Note:

A PDB can set a lower limit for parallel execution servers than the limit specified in the CDB resource plan. When the PARALLEL_SERVERS_TARGET initialization parameter is set in a PDB, and parallel execution server limit is specified for a PDB in the CDB resource plan, then the lower of the two limits is enforced. For example, assume that the PARALLEL_SERVERS_TARGET initialization parameter is set to 100 in the CDB root. Also assume that hrpdb has its PARALLEL_SERVERS_TARGET initialization parameter set to 50 and the CDB plan has a directive for hrpdb with parallel_server_limit set to 70%. In this case, the limit for parallel execution servers for hrpdb is 50, because 50 is lower than the CDB resource plan limit of 70 for hrpdb.

See Also:

- "PARALLEL_DEGREE_POLICY"
- "PARALLEL_MAX_SERVERS"
- "MEMORY_TARGET"
- "SGA_TARGET"
- "PGA_AGGREGATE_TARGET"
- *Oracle Database VLDB and Partitioning Guide* for more information about this parameter

2.294 PARALLEL_THREADS_PER_CPU

PARALLEL_THREADS_PER_CPU describes the number of parallel execution processes or threads that a CPU can handle during parallel execution.

Property	Description
Parameter type	Integer
Default value	1
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	Any nonzero number
Basic	No

> **Note:**
>
> This parameter applies to parallel execution in exclusive mode as well as in an Oracle Real Application Clusters environment.

This parameter is used in determining the default values of other parallel execution related parameters, for example, `PARALLEL_MAX_SERVERS`. It is also used in determining the default degree of parallelism for SQL statements, and determining the upper bound for the degree of parallelism in automatic degree of parallelism. The default value is adequate in most cases.

> **See Also:**
>
> - *Oracle Database SQL Tuning Guide* for more information about parallel execution
> - *Oracle Database VLDB and Partitioning Guide* for information about how the optimizer automatically determines the degree of parallelism for a statement

2.295 PDB_FILE_NAME_CONVERT

`PDB_FILE_NAME_CONVERT` maps names of existing files to new file names when processing a `CREATE PLUGGABLE DATABASE` statement, as well as when processing the `ENABLE PLUGGABLE DATABASE` clause of the `CREATE DATABASE` statement, if the *`file_name_convert_clause`* is not specified and Oracle Managed Files is not enabled.

Property	Description
Parameter type	String

Syntax	`PDB_FILE_NAME_CONVERT = '`*`string1`*`' , '`*`string2`*`' , '`*`string3`*`' , '`*`string4`*`' , ...`
	Where:
	• *`string1`* is the pattern of the existing filename
	• *`string2`* is the pattern of the new filename
	• *`string3`* is the pattern of the existing filename
	• *`string4`* is the pattern of the new filename
	You can enclose each string in single or double quotation marks.
	You can specify as many pairs of existing and new replacement strings as required.
	Example:
	`PDB_FILE_NAME_CONVERT = '/dbs/t1/','/dbs/t1/s','dbs/t2/','dbs/t2/s'`

Default value	There is no default value
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

Property	Description
Oracle RAC	You must set this parameter for every instance, and multiple instances must have the same value.

File name patterns specified in this initialization parameter cannot match files or directories managed by Oracle Managed Files.

> **See Also:**
>
> *Oracle Multitenant Administrator's Guide* for more information about this parameter

2.296 PDB_LOCKDOWN

`PDB_LOCKDOWN` determines the PDB lockdown profile that applies to a PDB.

Property	Description
Parameter type	String
Syntax	`PDB_LOCKDOWN = pdb-lockdown-profile-name`
Default value	`NULL`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	All instances should have the same value

A PDB lockdown profile is a mechanism to restrict operations (such as setting values of certain parameters and using certain options) that can be performed by users connected to a given PDB. You can also restrict execution of any packages that allow network access, for example, `UTL_SMTP`.

You create lockdown profiles using the SQL `CREATE LOCKDOWN PROFILE` statement. Then you can set a profile using the SQL `ALTER SESSION` or `ALTER SYSTEM` statement. See the Examples section.

This parameter can be set using the `ALTER SYSTEM` statement with scope set to `MEMORY`, `SPFILE`, or `BOTH`.

The lockdown profile for PDBs can be specified by a common user with common `ALTER SYSTEM` or common `SYSDBA` privilege.

If a PDB lockdown profile is dropped, any PDB to which the dropped profile was assigned (by means of storing the dropped profile name in the `PDB_LOCKDOWN` parameter) will continue to have its `PDB_LOCKDOWN` parameter set to the dropped lockdown profile name. However, the PDB will not have any restrictions imposed by the dropped lockdown profile.

Lockdown profiles can now be created in an application root and are referred to as application lockdown profiles.

A CDB common user with common SYSDBA or common ALTER SYSTEM privilege can only set PDB_LOCKDOWN to a CDB lockdown profile. Similarly, an application common user with application common SYSDBA or application common ALTER SYSTEM privilege can only set PDB_LOCKDOWN to an application lockdown profile.

An application common user cannot overwrite PDB_LOCKDOWN if PDB_LOCKDOWN is already set to a CDB lockdown profile in an application root or application PDB.

If the PDB_LOCKDOWN parameter in a PDB is set to the name of a lockdown profile different from that in its ancestor (for a CDB, the CDB root or, for application PDBs, the application root), the following will govern the interaction between restrictions imposed by these profiles:

- If the PDB_LOCKDOWN parameter in a PDB (including an application PDB) is set to a CDB lockdown profile, lockdown profiles specified by the PDB_LOCKDOWN parameter in CDB root (and for application PDBs, the application root) are ignored.
- If the PDB_LOCKDOWN parameter in an application PDB is set to an application lockdown profile while the PDB_LOCKDOWN parameter in the application root or CDB root is set to a CDB lockdown profile, in addition to the rules stipulated in the application lockdown profile, the DISABLE rules from the CDB lockdown profile set in its nearest ancestor (that is, an application root or CDB root) are inherited.
- If there are conflicts between rules comprising the CDB lockdown profile and the application lockdown profile, the rules in the CDB lockdown profile will take precedence (for example, the OPTION_VALUE clause of a CDB lockdown profile will take precedence over the OPTION_VALUE clause of an application lockdown profile).

Examples

This example shows how the SYS user can connect to the database AS SYSDBA and use the CREATE LOCKDOWN PROFILE statement in the root of a CDB to define a new lockdown profile. After defining the new lockdown profile, the SYS user can assign the new lockdown profile to a PDB using the PDB_LOCKDOWN parameter:

```
SQL> ALTER SESSION SET CONTAINER=CDB$ROOT;

Session altered.

SQL> CREATE LOCKDOWN PROFILE MYPROFILE;

Lockdown Profile created.

SQL> ALTER SESSION SET CONTAINER=CDB1_PDB1;

Session altered.

SQL> ALTER SYSTEM SET PDB_LOCKDOWN=MYPROFILE;

System altered.

SQL> SHOW PARAMETER PDB_LOCKDOWN

NAME           TYPE        VALUE
-------------- ----------- ---------
```

```
pdb_lockdown    string      MYPROFILE
SQL>
```

See Also:

- "DBA_LOCKDOWN_PROFILES"
- *Oracle Multitenant Administrator's Guide* for an introduction to PDB lockdown profiles
- *Oracle Database SQL Language Reference* for more information about the `CREATE LOCKDOWN PROFILE` statement

2.297 PDB_OS_CREDENTIAL

`PDB_OS_CREDENTIAL` determines the identity of the operating system user (OS user) employed when interacting with the operating system from a PDB.

Property	Description
Parameter type	String
Syntax	`PDB_OS_CREDENTIAL = credential`
Default value	None
Modifiable	No
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	The same value should be used for all instances

Note:

The Oracle OS user will continue to be used when interacting with the operating system from the root.

The Oracle OS user is usually a highly privileged user, and using the same user for operating system interactions for every PDB is not recommended. Also, using the same OS user for operating system interactions from different PDBs may compromise data belonging to a given PDB.

In contrast, using an OS user described by a credential whose name is specified as a value of the `PDB_OS_CREDENTIAL` parameter helps ensure that operating system interactions are performed as a less powerful user and provides the ability to protect data belonging to one PDB from being accessed by users connected to another PDB. A credential is an object that is created using the `CREATE_CREDENTIAL` procedure for the `DBMS_CREDENTIAL` package.

The operating system interactions that are done as the OS user name specified in the credential include:

- External jobs that do not already have an operating system credential specified
- External table pre-processors
- PL/SQL library executions

This parameter can be specified for all the PDBs in a CDB but the CDB-wide value can be overridden for a specific PDB and can be modified *only* by a common administrative user with the `EXECUTE` privilege for the `DBMS_CREDENTIAL` PL/SQL package and the `ALTER SYSTEM` system privilege.

If a value is not set for this parameter for a given PDB, the Oracle OS User will continue to be used when interacting with the operating system from that PDB.

See Also:

- *Oracle Database Security Guide* for an example of setting an OS user for a PDB using this parameter
- *Oracle Multitenant Administrator's Guide* for conceptual information about CDBs and PDBs
- *Oracle Multitenant Administrator's Guide* for information about managing CDBs and PDBs
- *Oracle Database PL/SQL Packages and Types Reference* for information about creating a credential using the `DBMS_CREDENTIAL.CREATE_CREDENTIAL` procedure

2.298 PERMIT_92_WRAP_FORMAT

`PERMIT_92_WRAP_FORMAT` allows Oracle Database release 9.2 wrapped versions of PL/SQL source text to be used in Oracle Database releases 10.2 and later when this parameter is set to `true`.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true	false`
Basic	No
Oracle RAC	Multiple instances should use the same value

Oracle recommends that wrapped files be created using the PL/SQL Wrapper utility from Oracle Database release 10 or later.

> **See Also:**
>
> *Oracle Database PL/SQL Language Reference* for more information about PL/SQL source text wrapping

2.299 PGA_AGGREGATE_LIMIT

`PGA_AGGREGATE_LIMIT` specifies a limit on the aggregate PGA memory consumed by the instance.

Property	Description
Parameter type	Big integer
Syntax	`PGA_AGGREGATE_LIMIT = integer [K | M | G]`
Default value	If `MEMORY_TARGET` is set, then `PGA_AGGREGATE_LIMIT` defaults to the `MEMORY_MAX_TARGET` value. If `MEMORY_TARGET` is not set, then `PGA_AGGREGATE_LIMIT` defaults to 200% of `PGA_AGGREGATE_TARGET`. If `MEMORY_TARGET` is not set, and `PGA_AGGREGATE_TARGET` is explicitly set to 0, then the value of `PGA_AGGREGATE_LIMIT` is set to 90% of the physical memory size minus the total SGA size. In all cases, the default `PGA_AGGREGATE_LIMIT` is at least 2GB and at least 3MB times the `PROCESSES` parameter (and at least 5MB times the `PROCESSES` parameter for an Oracle RAC instance). For a PDB, the default value is the same as the CDB's default value.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	Do not attempt to set `PGA_AGGREGATE_LIMIT` below its default value, even in a parameter file (pfile), or instance startup will fail. However, `PGA_AGGREGATE_LIMIT` can be set to 0 either in a parameter file or dynamically after startup. If a value of 0 is specified, it means there is no limit to the aggregate PGA memory consumed by the instance.
Basic	No

Actions Taken When PGA_AGGREGATE_LIMIT is Exceeded

Parallel queries will be treated as a unit. First, the sessions that are using the most untunable memory will have their calls terminated. Then, if the total PGA memory usage is still over the limit, the sessions that are using the most untunable memory will be terminated.

SYS processes and background processes other than job queue processes will not be subjected to any of the actions described in this section. Instead, if they are using the most untunable memory, they will periodically write a brief summary of their PGA usage to a trace file.

Note:

This parameter is optional for pluggable databases (PDBs). When this parameter is set for a PDB, it specifies the maximum PGA size for the PDB.

To be able to use Resource Manager in a CDB to control the amount of memory each PDB can use:

- The `NONCDB_COMPATIBLE` initialization parameter must be set to `FALSE` at the CDB level (in the root of the CDB).
- The `MEMORY_TARGET` initialization parameter must not be set at the CDB level.
- You must set the `PGA_AGGREGATE_LIMIT` initialization parameter in a PDB to a value that meets these requirements:
  - Less than or equal to the `PGA_AGGREGATE_LIMIT` value set at the CDB level
  - Greater than or equal to twice the value of `PGA_AGGREGATE_TARGET` set in the PDB

  When you set `PGA_AGGREGATE_LIMIT` in a PDB to a value that does not meet these requirements, you receive an error. If these requirements are violated after the PDB's parameter is set (for example, if the `PGA_AGGREGATE_LIMIT` value is changed at the CDB level, Oracle will adjust the PDB's value to meet these requirements.

See Also:

- "MEMORY_TARGET"
- "PGA_AGGREGATE_TARGET"
- *Oracle Multitenant Administrator's Guide* for more information about the initialization parameters that control the memory usage of PDBs
- *Oracle Database Performance Tuning Guide* for more information about this parameter

2.300 PGA_AGGREGATE_TARGET

`PGA_AGGREGATE_TARGET` specifies the target aggregate PGA memory available to all server processes attached to the instance.

Property	Description
Parameter type	Big integer
Syntax	`PGA_AGGREGATE_TARGET = integer [K | M | G]`
Default value	`10` MB or 20% of the size of the SGA, whichever is greater For a PDB, the default value is the same as the CDB's default value.
Modifiable	`ALTER SYSTEM`

Property	Description
Modifiable in a PDB	Yes
Range of values	Minimum: 10 MB Maximum: 4096 GB - 1
Basic	Yes

To set a hard limit for aggregate PGA memory, use the `PGA_AGGREGATE_LIMIT` parameter.

Setting `PGA_AGGREGATE_TARGET` to a nonzero value has the effect of automatically setting the `WORKAREA_SIZE_POLICY` parameter to `AUTO`. With this setting, SQL working areas used by memory-intensive SQL operators (such as sort, group-by, hash-join, bitmap merge, and bitmap create) will be automatically sized. A nonzero value for this parameter is the default since, unless you specify otherwise, Oracle sets it to 20% of the SGA or 10 MB, whichever is greater.

Setting `PGA_AGGREGATE_TARGET` to 0 automatically sets the `WORKAREA_SIZE_POLICY` parameter to `MANUAL`. With this setting, SQL working areas are sized using the `*_AREA_SIZE` parameters.

Oracle attempts to keep the amount of private memory below the target specified by this parameter by adapting the size of the working areas to private memory. When increasing the value of this parameter, you indirectly increase the memory allotted to working areas. Consequently, more memory-intensive operations are able to run fully in memory and fewer will work their way over to disk.

If Automatic Memory Management is enabled (`MEMORY_TARGET` is set to a positive value) and `PGA_AGGREGATE_TARGET` is also set to a positive value, the `PGA_AGGREGATE_TARGET` value acts as the minimum value for the size of the instance PGA.

Note:

This parameter is optional for pluggable databases (PDBs). When this parameter is set for a PDB, it specifies the target aggregate PGA size for the PDB.

To be able to use Resource Manager in a CDB to control the amount of memory each PDB can use:

- The `NONCDB_COMPATIBLE` initialization parameter must be set to `FALSE` at the CDB level (in the root of the CDB).
- The `MEMORY_TARGET` initialization parameter must not be set at the CDB level.
- You must set the `PGA_AGGREGATE_TARGET` initialization parameter in a PDB to a value that meets these requirements:
  - Less than or equal to the `PGA_AGGREGATE_TARGET` value set at the CDB level
  - Less than or equal to 50% of the `PGA_AGGREGATE_LIMIT` initialization parameter value set at the CDB level
  - Less than or equal to 50% of the `PGA_AGGREGATE_LIMIT` value set in the PDB

  When you set `PGA_AGGREGATE_TARGET` in a PDB to a value that does not meet these requirements, you receive an error. If these requirements are violated after the PDB's parameter is set (for example, if the `PGA_AGGREGATE_TARGET` value is changed at the CDB level), Oracle will adjust the PDB's value to meet these requirements.

See Also:

- "WORKAREA_SIZE_POLICY"
- *Oracle Database Performance Tuning Guide* for more information about configuring memory
- "PGA_AGGREGATE_LIMIT"

2.301 PKCS11_LIBRARY_LOCATION

`PKCS11_LIBRARY_LOCATION` specifies the PKCS#11 library location for Transparent Data Encryption (TDE).

Property	Description
Parameter type	String
Syntax	`PKCS11_LIBRARY_LOCATION = '`*`library_location`*`'`
Default value	None
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes

Property	Description
Basic	No
Oracle RAC	The same value must be used on all instances.

For *library_location*, specify the full operating system path to the PKCS#11 library. For example:

```
ALTER SYSTEM SET PKCS11_LIBRARY_LOCATION =
    '/opt/oracle/extapi/64/pkcs11/okv/21.8/liborapkcs.so';
```

> **See Also:**
>
> "V$PKCS11_PATH"

2.302 PLSCOPE_SETTINGS

PLSCOPE_SETTINGS controls the compile time collection, cross-reference, and storage of PL/SQL source code identifier data.

Property	Description
Parameter type	String
Syntax	PLSCOPE_SETTINGS = 'value_clause [, value_clause]' **value_clause::=** { IDENTIFIERS | STATEMENTS } : { ALL | NONE | PUBLIC (for IDENTIFIERS only) | SQL (for IDENTIFIERS only) | PLSQL (for IDENTIFIERS only) }
Default value	'IDENTIFIERS:NONE'
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No

Values

- IDENTIFIERS:ALL

  Enables the collection of all source code identifier data.

- IDENTIFIERS:NONE

  Disables the collection of all source code identifier data.

- IDENTIFIERS: PUBLIC

  Enables the collection of all PUBLIC user identifier data (except for DEFINITION)

- IDENTIFIERS:SQL

  Enables the collection of all SQL identifier data.

- `IDENTIFIERS:PLSQL`

  Enables the collection of all PLSQL identifier data.

- `STATEMENTS:ALL`

  Enables the collection of all SQL statements used in PL/SQL.

- `STATEMENTS:NONE`

  Disables the collection of all statements.

`PLSCOPE_SETTINGS` can be set on a session, system, or per-library unit (`ALTER COMPILE`) basis. The current setting of `PLSCOPE_SETTINGS` for any library unit can be attained by querying the `*_PLSQL_OBJECT_SETTINGS` views. Any identifier data collected by setting this parameter can be accessed using the `*_IDENTIFIERS` views.

When a `STATEMENTS` setting is not specified, and `IDENTIFIERS` is specified but set to a value other than `NONE`, `STATEMENTS` defaults to a setting of `ALL`, which is equal to:

```
IDENTIFIERS: [ALL|PLSQL|PLSQL|PUBLIC]
```

Examples

The following parameter setting causes PL/SQL and SQL identifiers and statements to be collected:

```
PLSCOPE_SETTINGS = 'IDENTIFIERS:ALL, STATEMENTS:ALL'
```

The following parameter setting causes only SQL identifiers and statements to be collected:

```
PLSCOPE_SETTINGS = 'IDENTIFIERS:SQL, STATEMENTS:ALL'
```

The following parameter setting causes only PL/SQL identifiers to be collected:

```
PLSCOPE_SETTINGS = 'IDENTIFIERS:PLSQL, STATEMENTS:NONE'
```

The following parameter setting causes no identifier data to be collected, and drops any existing identifier data:

```
PLSCOPE_SETTINGS = 'IDENTIFIERS: NONE'
```

See Also:

- "ALL_PLSQL_OBJECT_SETTINGS," "DBA_PLSQL_OBJECT_SETTINGS," and "USER_PLSQL_OBJECT_SETTINGS"
- "ALL_IDENTIFIERS,""DBA_IDENTIFIERS," and "USER_IDENTIFIERS"
- *Oracle Database PL/SQL Language Reference* for more information about this parameter

2.303 PLSQL_CCFLAGS

PLSQL_CCFLAGS provides a mechanism that allows PL/SQL programmers to control conditional compilation of each PL/SQL library unit independently.

Property	Description
Parameter type	String
Syntax	PLSQL_CCFLAGS = '<*v1*>:<*c1*>,<*v2*>:<*c2*>,...,<*vn*>:<*cn*>'
Default value	Empty string
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	Any string literal that satisfies the internal syntax
Basic	No
Examples	ALTER SESSION SET PLSQL_CCFLAGS = 'DeBug:TruE'; ALTER SESSION SET PLSQL_CCFLAGS = 'debug:TRUE';

Values

- <*vi*> has the form of an unquoted PL/SQL identifier. It is unrestricted and can be a reserved word or a keyword. The text is insensitive to case. Each one is known as a flag or flag name. Each <*vi*> can occur more than once in the string, each occurrence can have a different flag value, and the flag values can be of different kinds.
- <*ci*> is one of the following: a PL/SQL boolean literal, a PLS_INTEGER literal, or the literal NULL. The text is insensitive to case. Each one is known as a flag value and corresponds to a flag name.

You can define any allowable value for PLSQL_CCFLAGS. However, Oracle recommends that this parameter be used for controlling the conditional compilation of debugging or tracing code. It is recommended that the following identifiers not be used as flag name values:

- Names of Oracle parameters (for example, NLS_LENGTH_SEMANTICS)
- Identifiers with any of the following prefixes: PLS_, PLSQL_, PLSCC_, ORA_, ORACLE_, DBMS_, SYS_

> **See Also:**
>
> *Oracle Database PL/SQL Language Reference* for more information about this parameter

2.304 PLSQL_CODE_TYPE

PLSQL_CODE_TYPE specifies the compilation mode for PL/SQL library units.

Property	Description
Parameter type	String
Syntax	`PLSQL_CODE_TYPE = { INTERPRETED | NATIVE }`
Default value	`INTERPRETED`
Modifiable	`ALTER SESSION, ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

Values

- `INTERPRETED`

  PL/SQL library units will be compiled to PL/SQL bytecode format. Such modules are executed by the PL/SQL interpreter engine.

- `NATIVE`

  PL/SQL library units (with the possible exception of top-level anonymous PL/SQL blocks) will be compiled to native (machine) code. Such modules will be executed natively without incurring any interpreter overhead.

When the value of this parameter is changed, it has no effect on PL/SQL library units that have already been compiled. The value of this parameter is stored persistently with each library unit.

If a PL/SQL library unit is compiled native, all subsequent automatic recompilations of that library unit will use native compilation.

> **See Also:**
>
> *Oracle Database PL/SQL Language Reference* for more information about this parameter

2.305 PLSQL_DEBUG

`PLSQL_DEBUG` specifies whether or not PL/SQL library units will be compiled for debugging.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION, ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true | false`
Basic	No

> **Note:**
>
> The PLSQL_DEBUG parameter is deprecated. It is retained for backward compatibility only.

Values

- true

  PL/SQL library units will be compiled for debugging

- false

  PL/SQL library units will be compiled for normal execution

When PLSQL_DEBUG is set to true, PL/SQL library units are always compiled INTERPRETED in order to be debuggable.

When the value of this parameter is changed, it has no effect on PL/SQL library units that have already been compiled. The value of this parameter is stored persistently with each library unit.

2.306 PLSQL_IMPLICIT_CONVERSION_BOOL

PLSQL_IMPLICIT_CONVERSION_BOOL allows or disallows implicit conversions in PL/SQL between numeric data types and the BOOLEAN data type, and between character data types and the BOOLEAN data type.

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	true | false
Basic	No
Oracle RAC	Multiple instances must have the same value.

When this parameter is set to true, PL/SQL supports the following implicit data type conversions:

- Numeric data type to BOOLEAN data type
  - Non-zero numeric values are implicitly converted to the BOOLEAN value TRUE
  - The numeric value of 0 is implicitly converted to the BOOLEAN value FALSE
- Character data type to BOOLEAN data type
  - Character values such as 'true', 't', 'yes', 'y', '1', and 'on' (case-insensitive) are implicitly converted to the BOOLEAN value TRUE
  - Character values such as 'false', 'f', 'no', 'n', '0', and 'off' (case-insensitive) are implicitly converted to the BOOLEAN value FALSE

- `BOOLEAN` data type to numeric data type
  - The `BOOLEAN` value `TRUE` is implicitly converted to the numeric value `1`
  - The `BOOLEAN` value `FALSE` is implicitly converted to the numeric value `0`
- `BOOLEAN` data type to character data type
  - The `BOOLEAN` value `TRUE` is implicitly converted to the character value `'TRUE'`
  - The `BOOLEAN` value `FALSE` is implicitly converted to the character value `'FALSE'`

When this parameter is set to `false`, PL/SQL does not support such implicit conversions.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.307 PLSQL_OPTIMIZE_LEVEL

`PLSQL_OPTIMIZE_LEVEL` specifies the optimization level that will be used to compile PL/SQL library units. The higher the setting of this parameter, the more effort the compiler makes to optimize PL/SQL library units.

Property	Description
Parameter type	Integer
Default value	2
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	0 to 3
Basic	No

Values

- `0`

  Maintains the evaluation order and hence the pattern of side effects, exceptions, and package initializations of Oracle9*i* and earlier releases. Also removes the new semantic identity of `BINARY_INTEGER` and `PLS_INTEGER` and restores the earlier rules for the evaluation of integer expressions. Although code will run somewhat faster than it did in Oracle9*i*, use of level 0 will forfeit most of the performance gains of PL/SQL in Oracle Database 10*g*.

- `1`

  Applies a wide range of optimizations to PL/SQL programs including the elimination of unnecessary computations and exceptions, but generally does not move source code out of its original source order.

- `2`

  Applies a wide range of modern optimization techniques beyond those of level 1 including changes which may move source code relatively far from its original location.

- 3

  Applies a wide range of optimization techniques beyond those of level 2, automatically including techniques not specifically requested.

Generally, setting this parameter to `2` pays off in better execution performance. If, however, the compiler runs slowly on a particular source module or if optimization does not make sense for some reason (for example, during rapid turnaround development), then setting this parameter to `1` will result in almost as good a compilation with less use of compile-time resources.

The value of this parameter is stored persistently with the library unit.

> **See Also:**
>
> - *Oracle Database PL/SQL Language Reference* for more information about this parameter
> - *Oracle Database Development Guide* for an example of using this parameter

2.308 PLSQL_V2_COMPATIBILITY

`PLSQL_V2_COMPATIBILITY` is used to specify whether nonstandard behavior that PL/SQL Version 2 allows will be allowed in PL/SQL Version 8.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No

> **Note:**
>
> The `PLSQL_V2_COMPATIBILITY` parameter is deprecated. It is retained for backward compatibility only.

PL/SQL Version 2 allows some nonstandard behavior that Version 8 disallows. If you want to retain that behavior for backward compatibility, set `PLSQL_V2_COMPATIBILITY` to `true`. If you set it to `false`, then PL/SQL Version 8 behavior is enforced and Version 2 behavior is not allowed.

> **See Also:**
>
> *Oracle Database PL/SQL Language Reference* for a description of the differences between PL/SQL Version 2 and Version 8, and for more information on setting this parameter

2.309 PLSQL_WARNINGS

`PLSQL_WARNINGS` enables or disables the reporting of warning messages by the PL/SQL compiler, and specifies which warning messages to show as errors.

Property	Description
Parameter type	String
Syntax	`PLSQL_WARNINGS = 'value_clause' [, 'value_clause' ] ...`

Syntax	**`value_clause::=`**
	`{ ENABLE | DISABLE | ERROR }:`
	`{ ALL`
	`| SEVERE`
	`| INFORMATIONAL`
	`| PERFORMANCE`
	`| { integer`
	`| (integer [, integer ] ...)`
	`}`
	`}`

Default value	`'DISABLE:ALL'`
Modifiable	`ALTER SESSION, ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

Examples	`PLSQL_WARNINGS = 'ENABLE:SEVERE', 'DISABLE:INFORMATIONAL';`
	`PLSQL_WARNINGS = 'DISABLE:ALL';`
	`PLSQL_WARNINGS = 'DISABLE:5000', 'ENABLE:5001', 'ERROR:5002';`
	`PLSQL_WARNINGS = 'ENABLE:(5000,5001,5002)', 'DISABLE:(6000,6001)';`

`value_clause`

Multiple value clauses may be specified, enclosed in quotes and separated by commas. Each value clause is composed of a qualifier, a colon (`:`), and a modifier.

Qualifier values:

- `ENABLE`

  Enable a specific warning or a set of warnings

- `DISABLE`

  Disable a specific warning or a set of warnings

- `ERROR`

  Treat a specific warning or a set of warnings as errors

Modifier values:

- `ALL`

  Apply the qualifier to all warning messages

- `SEVERE`

  Apply the qualifier to only those warning messages in the `SEVERE` category

- `INFORMATIONAL`

  Apply the qualifier to only those warning messages in the `INFORMATIONAL` category

- `PERFORMANCE`

  Apply the qualifier to only those warning messages in the `PERFORMANCE` category

> **See Also:**
>
> *Oracle Database PL/SQL Language Reference* for more information about this parameter

2.310 PMEM_FILESTORE

`PMEM_FILESTORE` specifies the Persistent Memory Filestores (PMEM Filestores) that the database automatically mounts during instance startup.

Property	Description
Parameter type	String
Syntax	`PMEM_FILESTORE = ( 'mount_point', 'backing_file' [, 'mount_point', 'backing_file' ]... )`
Default value	None
Modifiable	No
Modifiable in a PDB	No
Basic	No

You can specify one or more PMEM Filestores to be mounted during instance startup.

Specify the following pair of values for each PMEM Filestore:

- *mount_point*: The operating system directory path for the mount point of the PMEM Filestore
- *backing_file*: The operating system file path for the backing file of the PMEM Filestore

For example:

```
PMEM_FILESTORE=('/var/db/db_1', '/var/db_storage/db1.f')
```

```
PMEM_FILESTORE=('/var/db/db_1', '/var/db_storage/db1.f', '/var/db/db_2',
'/var/db_storage/db2.f')
```

2.311 PRE_PAGE_SGA

PRE_PAGE_SGA determines whether Oracle accesses the entire SGA at instance startup.

Operating system page table entries are then prebuilt for each page of the SGA.

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	No
Modifiable in a PDB	No
Range of values	true | false
Basic	No

When this parameter is set to true, the database server touches the entire SGA after the instance startup. These accesses are done by a background process and are initiated after the instance startup. The accesses cause the OS to allocate memory to the SGA and populate the page tables, making the SGA memory resident and increasing database performance.

Note:

This setting does not prevent your operating system from paging or swapping the SGA after it is initially read into memory.

Note:

The PRE_PAGE_SGA parameter is deprecated in Oracle Database 23ai because it is obsolete. Setting this parameter typically provides little or no potential performance benefits, and can create problems.

The Oracle Database design for SGA packaging has evolved over time, so that process start-up effects on the SGA are initiated after instance startup, and there is little to no benefit in changing the value for PRE_PAGE_SGA. The only use case for this parameter is on Oracle Exadata systems, which should have PRE_PAGE_SGA set to TRUE.

2.312 PRIORITY_TXNS_HIGH_WAIT_TARGET

`PRIORITY_TXNS_HIGH_WAIT_TARGET` specifies the maximum number of seconds that a `HIGH` priority transaction will wait for a row lock before the Priority Transactions feature rolls back a lower priority transaction holding the lock.

Property	Description
Parameter type	Integer
Default value	`2147483647`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`1` to `2147483647`
Basic	No
Oracle RAC	Different instances can use different values.

The Priority Transactions feature automatically rolls back low-priority transactions that are blocking higher priority transactions from obtaining row locks.

This parameter is one of four initialization parameters that enable you to configure Priority Transactions. The other parameters are:

- `TXN_PRIORITY` - Specifies a priority (`HIGH`, `MEDIUM`, or `LOW`) for all transactions in a user session
- `PRIORITY_TXNS_MEDIUM_WAIT_TARGET` - Specifies the maximum number of seconds that a `MEDIUM` priority transaction will wait for a row lock
- `PRIORITY_TXNS_MODE` - Specifies whether to enable Priority Transactions or test Priority Transactions by running in tracking mode

Note:

This parameter is available starting with Oracle Database 23ai.

See Also:

- "TXN_PRIORITY"
- "PRIORITY_TXNS_MEDIUM_WAIT_TARGET"
- "PRIORITY_TXNS_MODE"
- *Oracle Database Administrator's Guide* for more information about Priority Transactions

2.313 PRIORITY_TXNS_MEDIUM_WAIT_TARGET

`PRIORITY_TXNS_MEDIUM_WAIT_TARGET` specifies the maximum number of seconds that a `MEDIUM` priority transaction will wait for a row lock before the Priority Transactions feature rolls back a lower priority transaction holding the lock.

Property	Description
Parameter type	Integer
Default value	`2147483647`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`1` to `2147483647`
Basic	No
Oracle RAC	Different instances can use different values.

The Priority Transactions feature automatically rolls back low-priority transactions that are blocking higher priority transactions from obtaining row locks.

This parameter is one of four initialization parameters that enable you to configure Priority Transactions. The other parameters are:

- `TXN_PRIORITY` - Specifies a priority (`HIGH`, `MEDIUM`, or `LOW`) for all transactions in a user session
- `PRIORITY_TXNS_HIGH_WAIT_TARGET` - Specifies the maximum number of seconds that a `HIGH` priority transaction will wait for a row lock
- `PRIORITY_TXNS_MODE` - Specifies whether to enable Priority Transactions or test Priority Transactions by running in tracking mode

Note:

This parameter is available starting with Oracle Database 23ai.

See Also:

- "TXN_PRIORITY"
- "PRIORITY_TXNS_HIGH_WAIT_TARGET"
- "PRIORITY_TXNS_MODE"
- *Oracle Database Administrator's Guide* for more information about Priority Transactions

2.314 PRIORITY_TXNS_MODE

PRIORITY_TXNS_MODE specifies the mode for Priority Transactions.

Property	Description
Parameter type	String
Syntax	PRIORITY_TXNS_MODE = { ROLLBACK | TRACK }
Default value	ROLLBACK
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Multiple instances must have the same value.

Values:

- ROLLBACK - This setting enables Priority Transactions. The database will automatically roll back low-priority transactions that are blocking higher priority transactions from obtaining row locks.

  Before enabling Priority Transactions, ensure that the following initialization parameters are configured properly:

  - PRIORITY_TXNS_HIGH_WAIT_TARGET - Specifies the maximum number of seconds that a HIGH priority transaction will wait for a row lock
  - PRIORITY_TXNS_MEDIUM_WAIT_TARGET - Specifies the maximum number of seconds that a MEDIUM priority transaction will wait for a row lock
  - TXN_PRIORITY - Specifies a priority (HIGH, MEDIUM, or LOW) for all transactions in a user session

  When running in ROLLBACK mode, you can track the performance of Priority Transactions by monitoring the following statistics:

  - txns rollback priority_txns_high_wait_target
  - txns rollback priority_txns_medium_wait_target

- TRACK - This setting allows you to track the potential behavior of Priority Transactions. You can use this mode to tune the Priority Transactions initialization parameters before enabling ROLLBACK mode.

  The database determines when HIGH and MEDIUM priority transactions would be rolled back, given the current values of the Priority Transactions initialization parameters. However, instead of actually rolling back the transactions, the database only increments the following statistics:

  - txns track mode priority_txns_high_wait_target
  - txns track mode priority_txns_medium_wait_target

  You can also monitor the following wait events to determine the amount of time transactions are waiting for row locks:

  - enq: TX - row lock (HIGH priority)

- `enq: TX - row lock (MEDIUM priority)`
- `enq: TX - row lock (LOW priority)`

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "PRIORITY_TXNS_HIGH_WAIT_TARGET"
> - "PRIORITY_TXNS_MEDIUM_WAIT_TARGET"
> - "TXN_PRIORITY"
> - *Oracle Database Administrator's Guide* for more information about Priority Transactions

2.315 PRIVATE_TEMP_TABLE_PREFIX

`PRIVATE_TEMP_TABLE_PREFIX` specifies the prefix that the database uses for private temporary tables.

Property	Description
Parameter type	String
Syntax	`PRIVATE_TEMP_TABLE_PREFIX = string`
Default value	`ORA$PTT_`
Modifiable	`ALTER SYSTEM ... DEFERRED`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	The same value must be specified on each instance.

The default value used for the `PRIVATE_TEMP_TABLE_PREFIX` parameter is `ORA$PTT_`.

If you choose to specify a different prefix value, it must begin with the string `ORA$` and must be unique across the database. Use the following SQL query to determine if the prefix value is unique (in the query, replace `prefix-value` with your actual prefix value):

```
select count(*) from obj$ where name like '<prefix-value>%';
```

If the above query returns 0, then the prefix you specified is an appropriate value to set.

> **Note:**
>
> After setting the prefix, regular table, view, and object names cannot use the same prefix.

> **See Also:**
>
> - "DBA_PRIVATE_TEMP_TABLES"
> - "USER_PRIVATE_TEMP_TABLES"
> - *Oracle Database Administrator's Guide* for an introduction to private temporary tables

2.316 PROCESSES

`PROCESSES` specifies the maximum number of operating system user processes that can simultaneously connect to Oracle.

Property	Description
Parameter type	Integer
Default value	The value is derived, and it typically depends on the number of cores reported in the alert log.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	6 to operating system dependent
Basic	Yes
Oracle RAC	Multiple instances can have different values.

The value for this parameter should allow for all background processes such as locks, job queue processes, and parallel execution processes.

The default values of the `SESSIONS` and `TRANSACTIONS` parameters are derived from this parameter. Therefore, if you change the value of `PROCESSES`, you should evaluate whether to adjust the values of those derived parameters.

> **See Also:**
>
> - Your operating system-specific Oracle documentation for the range of values
> - *Oracle Database Concepts* for an introduction to Oracle database instance processes

2.317 PROCESSOR_GROUP_NAME

PROCESSOR_GROUP_NAME specifies the name of the processor group that this instance should run in.

Property	Description
Parameter type	String
Syntax	PROCESSOR_GROUP_NAME = *string*
Default value	There is no default value
Modifiable	No
Modifiable in a PDB	No
Basic	No
Oracle RAC	For Oracle RAC databases, it is recommended that the operating system processor groups for each database instance are all named the same, so that the same PROCESSOR_GROUP_NAME value can be used. However, you can choose to use different names. In this case, you would set the PROCESSOR_GROUP_NAME explicitly for each database instance.

This initialization parameter is supported on the Linux and Solaris operating systems.

PROCESSOR_GROUP_NAME instructs the database instance to run itself within the specified operating system processor group. All Oracle processes will be bound to the CPUs in this group and will only run on these CPUs.

Notes:

- Oracle recommends that this parameter be set only for databases on which the USE_DEDICATED_BROKER initialization parameter is also set to TRUE.
- For NUMA systems, all SGA and PGA memory allocated by the database instance will be allocated from NUMA nodes within the group.
- Starting with Oracle Database Appliance (ODA) release 19.9, you can use PROCESSOR_GROUP_NAME to specify the set of CPU cores on which the database on ODA will run. For more information, refer to *Oracle Database Appliance X8-2 Deployment and User's Guide*.

See Also:

"USE_DEDICATED_BROKER"

2.318 QUERY_REWRITE_ENABLED

Use QUERY_REWRITE_ENABLED to enable or disable query rewriting globally for the database.

Property	Description
Parameter type	String
Syntax	`QUERY_REWRITE_ENABLED = { false | true | force }`
Default value	If `OPTIMIZER_FEATURES_ENABLE` is set to `10.0.0` or higher, then `true` If `OPTIMIZER_FEATURES_ENABLE` is set to `9.2.0` or lower, then `false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Multiple instances can have different values.

Values

- `false`

  Oracle does not use rewrite.

- `true`

  Oracle costs the query with rewrite and without rewrite and chooses the method with the lower cost.

- `force`

  Oracle always uses rewrite and does not evaluate the cost before doing so. Use `force` when you know that the query will always benefit from rewrite and when reduction in compile time is important.

To take advantage of query rewrite for a particular materialized view, you must enable query rewrite for that materialized view, and you must enable cost-based optimization.

See Also:

- *Oracle Database Data Warehousing Guide* for information on query rewrite of materialized views
- *Oracle Database SQL Tuning Guide* and "OPTIMIZER_MODE" for information on cost-based optimization

2.319 QUERY_REWRITE_INTEGRITY

`QUERY_REWRITE_INTEGRITY` determines the degree to which Oracle must enforce query rewriting. At the safest level, Oracle does not use query rewrite transformations that rely on unenforced relationships.

Property	Description
Parameter type	String

Property	Description
Syntax	`QUERY_REWRITE_INTEGRITY = { enforced | trusted | stale_tolerated }`
Default value	`enforced`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Multiple instances can have different values.

`QUERY_REWRITE_INTEGRITY` is relevant for materialized views as well as for foreign key constraints in `NOVALIDATE` state.

Values

- `enforced`

  Oracle enforces and guarantees consistency and integrity.

- `trusted`

  Oracle allows rewrites using relationships that have been declared, but that are not enforced by Oracle.

- `stale_tolerated`

  Oracle allows rewrites using unenforced relationships. Materialized views are eligible for rewrite even if they are known to be inconsistent with the underlying detail data. You must set the `QUERY_REWRITE_INTEGRITY` initialization parameter to `stale_tolerated` before querying an external table in the In-Memory Column Store (IM column store).

If a foreign key constraint is in `NOVALIDATE` state, join elimination is not done when `QUERY_REWRITE_INTEGRITY=enforced`. This means that queries with joins over a foreign key constraint that is in `RELY NOVALIDATE` state can potentially take longer to parse and execute as the optimizer does not trust the `RELY`.

See Also:

- "INMEMORY_CLAUSE_DEFAULT"
- *Oracle Database Data Warehousing Guide* for more information about query rewrite for materialized views
- *Oracle Database Data Warehousing Guide* for more information about the `QUERY_REWRITE_INTEGRITY` parameter

2.320 RDBMS_SERVER_DN

`RDBMS_SERVER_DN` specifies the Distinguished Name (DN) of the Oracle server. It is used for retrieving Enterprise Roles from an enterprise directory service.

> **Note:**
>
> Enterprise User Security (EUS) is deprecated with Oracle Database 23ai.
>
> Oracle recommends that you migrate to using Centrally Managed Users (CMU). This feature enables you to directly connect with Microsoft Active Directory without an intervening directory service for enterprise user authentication and authorization to the database. If your Oracle Database is in the cloud, you can also choose to move to one of the newer integrations with a cloud identity provider.

Property	Description
Parameter type	X.500 Distinguished Name
Default value	There is no default value.
Modifiable	No
Modifiable in a PDB	No
Range of values	All X.500 Distinguished Name format values
Basic	No

> **Note:**
>
> The `RDBMS_SERVER_DN` parameter is deprecated in Oracle Database 12*c* Release 1 (12.1.0.2). It is replaced by the `LDAP_DIRECTORY_ACCESS` initialization parameter.

If you do not want to use a directory for enterprise user and privilege management, but prefer to use SSL authentication alone, do not set this parameter.

> **See Also:**
>
> - *Oracle Database Enterprise User Security Administrator's Guide* for more information on enterprise roles and the enterprise directory service
> - "LDAP_DIRECTORY_ACCESS"

2.321 READ_ONLY

READ_ONLY enables or disables read-only mode for a user session.

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SESSION
Modifiable in a PDB	No
Range of values	true | false
Basic	No
Oracle RAC	Different instances can use different values.

The READ_ONLY parameter allows you to prohibit write operations in a user session, without having to put an entire CDB or container into read-only mode. You can set this parameter in a session created by any type of user, such as a CDB common user, an application common user, or a local user. This parameter is effective in any type of container, such as the CDB root, a PDB, an application root, or an application PDB, when the container is open in read/write mode.

- To enable read-only mode for the current session, set the READ_ONLY parameter to true. You cannot set this parameter to true when there are active transactions in the session.
- To disable read-only mode for the current session, set the READ_ONLY parameter to false.

The READ_ONLY parameter value for a user session does not affect the value of the OPEN_MODE column for the session's container, as displayed in views such as V$CONTAINER_TOPOLOGY, V$CONTAINERS, V$DATABASE, and V$PDBS.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.322 READ_ONLY_OPEN_DELAYED

READ_ONLY_OPEN_DELAYED determines when datafiles in read-only tablespaces are accessed.

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Modifiable in a PDB	No
Range of values	true | false
Basic	No

Values

- `true`

  The datafiles are accessed for the first time only when an attempt is made to read data stored within them.

- `false`

  The datafiles are accessed at database open time.

You can use this parameter to speed up some operations (primarily opening the database) for very large databases when substantial portions of the database are stored in read-only tablespaces. Consider setting this parameter to `true` for such databases, especially if portions of the read-only data are stored on slow-access devices or hierarchical storage.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for information on the consequences of delaying access of datafiles in read-only tablespaces

2.323 RECOVERY_PARALLELISM

`RECOVERY_PARALLELISM` specifies the number of processes to participate in instance or crash recovery.

Property	Description
Parameter type	Integer
Default value	System-determined parallel recovery
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	System-determined, but cannot exceed `PARALLEL_MAX_SERVERS` initialization parameter setting
Basic	No

To force serial crash and instance recovery, set the `RECOVERY_PARALLELISM` parameter to 0 or 1. 0 or 1 disable parallel instance and crash recovery on a system that has multiple CPUs. An alert log displays the degree of parallelism that was chosen when the database instance/recovery starts.

> **See Also:**
>
> - *Oracle Real Application Clusters Administration and Deployment Guide* for information on setting this parameter in an Oracle RAC environment

2.324 RECYCLEBIN

RECYCLEBIN is used to control whether the Flashback Drop capability is turned on or off.

Property	Description
Parameter type	String
Syntax	RECYCLEBIN = { on | off }
Default value	on
Modifiable	ALTER SESSION, ALTER SYSTEM ... DEFERRED
Modifiable in a PDB	Yes
Basic	No

If the parameter is set to off, then dropped tables do not go into the recycle bin. If this parameter is set to on, then dropped tables go into the recycle bin and can be recovered.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about using Flashback Drop and managing the recycle bin

2.325 REDO_TRANSPORT_USER

REDO_TRANSPORT_USER specifies the name of the user whose password verifier is used when a remote login password file is used for redo transport authentication. This user must have the SYSOPER privilege and must have the same password in the database that initiates the redo transport session and in the database that is the target of the redo transport session.

Property	Description
Parameter type	String
Syntax	REDO_TRANSPORT_USER = *user_name*
Default value	There is no default value.
Range of values	Any character string that matches the name of a user who has been granted the SYSOPER privilege
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Basic	No
Oracle RAC	Every instance should use the same value

The value of this parameter is case sensitive and must exactly match the value of the USERNAME column of a row in the V$PWFILE_USERS view. The value of the SYSOPER column of the row must also be TRUE.

If this parameter is not specified, then the password verifier of the SYS user will be used when a remote login password file is used for redo transport authentication.

> **See Also:**
>
> *Oracle Data Guard Concepts and Administration* for more information about this parameter

2.326 REMOTE_DEPENDENCIES_MODE

REMOTE_DEPENDENCIES_MODE specifies how Oracle should handle dependencies upon remote PL/SQL stored procedures.

Property	Description
Parameter type	String
Syntax	REMOTE_DEPENDENCIES_MODE = { TIMESTAMP | SIGNATURE }
Default value	TIMESTAMP
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No

Values

- TIMESTAMP

  The client running the procedure compares the timestamp recorded on the server-side procedure with the current timestamp of the local procedure and executes the procedure only if the timestamps match.

- SIGNATURE

  Oracle allows the procedure to execute as long as the signatures are considered safe. This setting allows client PL/SQL applications to be run without recompilation.

> **See Also:**
>
> *Oracle Database Development Guide* for suggestions for managing dependencies

2.327 REMOTE_LISTENER

REMOTE_LISTENER specifies a network name that resolves to an address or address list of Oracle Net remote listeners (that is, listeners that are not running on the same system as this instance). The address or address list is specified in the TNSNAMES.ORA file or other address repository as configured for your system.

Property	Description
Parameter type	String
Syntax	`REMOTE_LISTENER = network_name`
Default value	There is no default value.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	Yes

See Also:

- *Oracle Database Concepts* for more information about listener processes and dispatcher processes
- *Oracle Database Net Services Administrator's Guide* and your operating system-specific Oracle documentation for more information about specifying network addresses for the protocols on your system
- *Oracle Clusterware Administration and Deployment Guide* for information about SCAN addresses

2.328 REMOTE_LOGIN_PASSWORDFILE

`REMOTE_LOGIN_PASSWORDFILE` specifies whether Oracle checks for a password file.

Property	Description
Parameter type	String
Syntax	`REMOTE_LOGIN_PASSWORDFILE = { shared | exclusive | none }`
Default value	`exclusive`
Modifiable	No
Modifiable in a PDB	No
Basic	Yes
Oracle RAC	Multiple instances must have the same value.

Values

- `shared`

  One or more databases can use the password file. The password file can contain `SYS` and non-`SYS` users.

  When `REMOTE_LOGIN_PASSWORDFILE` is set to `shared`:

  – The `SYS` password cannot be changed. If you try, the password change operation fails with "ORA-28046: Password change for SYS disallowed."

  - The password of any user who has SYS* admin privileges (SYSDBA, SYSOPER, SYSASM, SYSBACKUP, SYSDG, SYSKM) cannot be changed. If you try, the password change operation fails with "ORA-01999: password file cannot be updated in SHARED mode."
  - Grants of SYS* admin privileges (SYSDBA, SYSOPER, SYSASM, SYSBACKUP, SYSDG, SYSKM) to individual users are not allowed. For example, grant sysdba to scott fails with "ORA-01999: password file cannot be updated in SHARED mode." Similarly, revoke of SYS* admin privileges fails.
  - If the password file does not exist, then the behavior is the same as setting REMOTE_LOGIN_PASSWORDFILE to none.

- exclusive

  The password file can be used by only one database. The password file can contain SYS and non-SYS users.

  When REMOTE_LOGIN_PASSWORDFILE is set to exclusive, if the password file does not exist, then the behavior is the same as setting REMOTE_LOGIN_PASSWORDFILE to none.

- none

  Oracle ignores any password file. Therefore, privileged users must be authenticated by the operating system.

> **Note:**
>
> If you change REMOTE_LOGIN_PASSWORDFILE to exclusive or shared from none, then ensure that the password file is synchronized with the dictionary passwords.

2.329 REMOTE_OS_ROLES

REMOTE_OS_ROLES specifies whether operating system roles are allowed for remote clients.

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Modifiable in a PDB	No
Range of values	true | false
Basic	No

The default value, false, causes Oracle to identify and manage roles for remote clients.

See Also:

- *Oracle Database Security Guide* for more information on setting this parameter
- "OS_ROLES"

2.330 REMOTE_RECOVERY_FILE_DEST

`REMOTE_RECOVERY_FILE_DEST` specifies a directory from which to read archive log files during a pluggable database (PDB) refresh operation if the source is not available.

Property	Description
Parameter type	String
Syntax	`REMOTE_RECOVERY_FILE_DEST = string`
Default value	None
Modifiable	`ALTER SYSTEM ... SID='*'`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	The directory location where archive redo logs are accessible can be different on different instances, so this parameter can be set to different values on different instances.

For a PDB refresh copy to be in sync with its source, redo is accessed from the source PDB over a database link. Sometimes the source PDB or the CDB to which the source PDB belongs is not accessible when the refresh copy needs to be updated. In those cases, if this parameter is set, an attempt will be made to read archive log files from the directory specified by this parameter.

2.331 REPLICATION_DEPENDENCY_TRACKING

`REPLICATION_DEPENDENCY_TRACKING` enables or disables dependency tracking for read/write operations to the database.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true	false`
Basic	No

Dependency tracking is essential for propagating changes in a replicated environment in parallel.

Values

- `TRUE`

  Enables dependency tracking.

- `FALSE`

  Allows read/write operations to the database to run faster, but does not produce dependency information for Oracle to perform parallel propagation.

> **Note:**
>
> Do not specify this value unless you are sure that your application will not perform any read/write operations to the replicated tables.

2.332 RESOURCE_LIMIT

`RESOURCE_LIMIT` determines whether resource limits are enforced in database profiles.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true | false`
Basic	No

Values

- `TRUE`

  Enables the enforcement of resource limits

- `FALSE`

  Disables the enforcement of resource limits

> **See Also:**
>
> *Oracle Database Administrator's Guide* and *Oracle Database SQL Language Reference* for more information on setting resource limits for profiles

2.333 RESOURCE_MANAGE_GOLDENGATE

RESOURCE_MANAGE_GOLDENGATE determines whether Oracle GoldenGate apply processes in the database are resource managed.

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	true | false
Basic	No
Oracle RAC	All instances should use the same value.

To enable Resource Manager, set the RESOURCE_MANAGER_PLAN parameter.

By default, Oracle GoldenGate apply processes in the database are not resource managed. Given that replication to a PDB requires a separate Oracle GoldenGate apply process, it is possible that the apply processes for one PDB could end up consuming most of the CPU on the machine, even if there is a CPU resource management plan in place to limit CPU usage per PDB.

You can set the following values for the RESOURCE_MANAGE_GOLDENGATE parameter:

- TRUE: With this setting, Oracle GoldenGate apply processes in the database are resource managed based on the resources allocated to the GoldenGate apply user.
- FALSE: With this setting, Oracle GoldenGate apply processes are not resource managed.

2.334 RESOURCE_MANAGER_CPU_ALLOCATION

RESOURCE_MANAGER_CPU_ALLOCATION specifies the number of CPUs that the Resource Manager should use. The Resource Manager controls how a system's CPUs are utilized by its database's sessions.

Property	Description
Parameter type	Integer
Default value	The number of logical CPUs reported by the operating system.
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	0 to operating system-specific
Basic	No

> **Note:**
>
> The `RESOURCE_MANAGER_CPU_ALLOCATION` parameter is deprecated. It is retained for backward compatibility only. Use the `CPU_COUNT` parameter instead.

The Resource Manager schedules database sessions on the CPUs according to a resource plan that has been configured and enabled by the DBA. Normally, the Resource Manager schedules enough database sessions to keep all CPUs utilized. However, in some scenarios, a DBA may only want to schedule enough database sessions to keep a subset of the CPUs utilized.

> **See Also:**
>
> "CPU_COUNT"

2.335 RESOURCE_MANAGER_CPU_SCOPE

`RESOURCE_MANAGER_CPU_SCOPE` controls the scope of CPU resource management.

In previous releases, Oracle offered one method of CPU resource management, which operated within a database instance. Starting with Oracle Database 23ai, Oracle offers an alternative method for CPU resource management, which operates across all database instances on the server. This parameter allows you to choose between the two methods.

Property	Description
Parameter type	String
Syntax	`RESOURCE_MANAGER_CPU_SCOPE = { SERVER_WIDE | INSTANCE_ONLY }`
Default value	`INSTANCE_ONLY`
Modifiable	No
Modifiable in a PDB	No
Basic	No
Oracle RAC	The same value must be used on all instances.

Values:

- `SERVER_WIDE` - Enables server-level inter-instance CPU resource management

  Introduced in Oracle Database 23ai, this method can be used when multiple database instances share a Linux server. It enables CPU resource management across all database instances on the server. With this method, Oracle automatically configures Linux control groups (cgroups) with the desired CPU sharing and CPU utilization limits, and then places database sessions into the appropriate cgroups.

In order to use this method, the following system and database requirements must be met:

- This method requires the Linux operating system. It is supported on Oracle Autonomous Database, Oracle Database Exadata Cloud@Customer, Oracle Database Exadata Cloud Service, and on-premises Oracle Exadata systems. This method is not supported on non-Exadata Linux systems.
- The server operating system must be Unbreakable Enterprise Kernel (UEK) version 5 or later.

You can configure this method as follows:

- Oracle Autonomous Database: All system and database requirements are installed and configured by default. `RESOURCE_MANAGER_CPU_SCOPE` is set to `SERVER_WIDE` by default.
- Oracle Database Exadata Cloud@Customer: All system and database requirements are installed and configured by default. `RESOURCE_MANAGER_CPU_SCOPE` is set to `INSTANCE_ONLY` by default. You must set it to `SERVER_WIDE` if you want to use this method.
- Oracle Database Exadata Cloud Service and on-premises Oracle Exadata systems: The Exadata image meets all system and database requirements. `RESOURCE_MANAGER_CPU_SCOPE` is set to `INSTANCE_ONLY` by default. You must set it to `SERVER_WIDE` if you want to use this method.

When you specify the `SERVER_WIDE` setting, the value of the `PROCESSOR_GROUP_NAME` initialization parameter is ignored.

- `INSTANCE_ONLY` - Enables CPU resource management only within the database instance.

  This is the method of CPU resource management used in releases prior to Oracle Database 23ai. It is supported on all Oracle Databases.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about setting this parameter

2.336 RESOURCE_MANAGER_PLAN

`RESOURCE_MANAGER_PLAN` specifies the resource plan to use for a database (CDB or non-CDB).

Property	Description
Parameter type	String

Property	Description
Syntax	`RESOURCE_MANAGER_PLAN = resource_plan_name`
Default value	There is no default value.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	Any valid character string
Basic	No

In a CDB

In the root for a CDB, `RESOURCE_MANAGER_PLAN` specifies the CDB resource plan. A CDB resource plan allocates resources among PDBs.

A CDB resource plan is created using `DBMS_RESOURCE_MANAGER.CREATE_CDB_PLAN` and `CREATE_CDB_PLAN_DIRECTIVE`.

See Also:

- *Oracle Database Administrator's Guide* for more information about using `DBMS_RESOURCE_MANAGER.CREATE_CDB_PLAN` and `DBMS_RESOURCE_MANAGER.CREATE_CDB_PLAN_DIRECTIVE`
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `CREATE_CDB_PLAN` procedure and `CREATE_CDB_PLAN_DIRECTIVE` procedure for the `DBMS_RESOURCE_MANAGER` package

A session must be `root` to change the value of `RESOURCE_MANAGER_PLAN` for a CDB using the `ALTER SYSTEM` statement. For example, to enable and disable a CDB resource plan:

```
SQL> ALTER SYSTEM SET RESOURCE_MANAGER_PLAN = CDB_resource_plan_name;
SQL> ALTER SYSTEM SET RESOURCE_MANAGER_PLAN = '';
```

In a PDB, `RESOURCE_MANAGER_PLAN` specifies the PDB resource plan to use for the PDB.

A session must be in the PDB to enable or disable a PDB resource plan for that PDB. For example, to enable and disable a PDB resource plan:

```
SQL> ALTER SYSTEM SET RESOURCE_MANAGER_PLAN = PDB_resource_plan_name;
SQL> ALTER SYSTEM SET RESOURCE_MANAGER_PLAN = '';
```

In a PDB, the PDB resource plan has some restrictions compared to the resource plan of a non-CDB. The following restrictions apply to PDB resource plans:

- A PDB resource plan cannot have subplans.
- A PDB resource plan can have a maximum of eight consumer groups.
- A PDB resource plan cannot have a multiple-level scheduling policy.

To enforce certain PDB resource plan policies, policies regarding resource allocation among PDBs should exist in the CDB resource plan. Without a CDB resource plan, certain PDB resource plan policies will not be enforced. If a PDB resource plan contains CPU or parallel statement queuing directives and a CDB resource plan is not specified, then Resource Manager will automatically enable the `DEFAULT_CDB_PLAN` plan. To prevent this behavior, set the `RESOURCE_MANAGER_PLAN` parameter at the root level to `ORA$INTERNAL_CDB_PLAN`.

> **Note:**
>
> See *Oracle Database Administrator's Guide* for information on CPU, I/O bandwidth, and parallel execution servers requirements in CDB resource plans, and for a description of the results in the PDB resource plans when those requirements are not met.

In a Non-CDB

`RESOURCE_MANAGER_PLAN` specifies the top-level resource plan to use for an instance in a non-CDB. The resource manager will load this top-level resource plan along with all its descendants (subplans, directives, and consumer groups). If you do not specify this parameter, the resource manager is off by default.

You can change the setting of this parameter using the `ALTER SYSTEM` statement to turn on the resource manager (if it was previously off) or to turn off the resource manager or change the current resource plan (if it was previously on). If you specify a resource plan that does not exist in the data dictionary, Oracle returns an error message.

> **See Also:**
>
> - *Oracle Database Administrator's Guide* for information on using Oracle Resource Manager
> - *Oracle Database PL/SQL Packages and Types Reference* for information on the `DBMS_RESOURCE_MANAGER` package
> - *Oracle Database PL/SQL Packages and Types Reference* for information on the `DBMS_RESOURCE_MANAGER_PRIVS` package
> - "DBA_RSRC_PLANS", "DBA_RSRC_PLAN_DIRECTIVES", and the various `V$RSRC_*` dynamic performance views in Dynamic Performance Views for information on existing resource plans

2.337 RESULT_CACHE_AUTO_BLOCKLIST

Use `RESULT_CACHE_AUTO_BLOCKLIST` to enable or disable adaptive result cache object exclusion.

Property	Description
Parameter type	String
Syntax	`RESULT_CACHE_AUTO_BLOCKLIST = { OFF | ON }`

Property	Description
Default value	ON
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Different instances can use different values.

When this parameter is set to ON, adaptive result cache object exclusion is enabled.

When this parameter is set to OFF, adaptive result cache object exclusion is disabled.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.338 RESULT_CACHE_EXECUTION_THRESHOLD

RESULT_CACHE_EXECUTION_THRESHOLD specifies the maximum number of times a PL/SQL function can be executed before its result is stored in the result cache.

Property	Description
Parameter type	Integer
Default value	2
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	0 to operating system-dependent
Basic	No
Oracle RAC	Multiple instances can have different values.

2.339 RESULT_CACHE_INTEGRITY

RESULT_CACHE_INTEGRITY specifies whether the database enforces result cache integrity.

Property	Description
Parameter type	String
Syntax	RESULT_CACHE_INTEGRITY = { ENFORCED | TRUSTED }
Default value	Oracle Autonomous Database: ENFORCED All other Oracle databases: TRUSTED
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes

Property	Description
Basic	No
Oracle RAC	Different instances can have different values.

Values:

- `ENFORCED`

  Regardless of the setting of the `RESULT_CACHE_MODE` initialization parameter or any specified hints, only deterministic constructs will be eligible for result caching. For example, queries using PL/SQL functions that are not explicitly declared as deterministic will not be cached. This setting enforces result cache integrity.

- `TRUSTED`

  The database honors the setting of the `RESULT_CACHE_MODE` initialization parameter and any specified hints, and will consider queries using possibly nondeterministic constructs as candidates for result caching. For example, queries using PL/SQL functions that are not explicitly declared as deterministic may be cached. Results that are certain to be nondeterministic (for example, `SYSDATE` or constructs involving `SYSDATE`) will not be cached. This setting does not enforce result cache integrity, which matches the behavior in releases prior to Oracle Database 23ai.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

> **See Also:**
>
> "RESULT_CACHE_MODE"

2.340 RESULT_CACHE_MAX_RESULT

`RESULT_CACHE_MAX_RESULT` specifies the percentage of `RESULT_CACHE_MAX_SIZE` that any single result can use.

Property	Description
Parameter type	Integer
Default value	`5` percent
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`0` to `100`
Basic	No
Oracle RAC	Multiple instances can have different values.

2.341 RESULT_CACHE_MAX_SIZE

RESULT_CACHE_MAX_SIZE specifies the maximum amount of SGA memory (in bytes) that can be used by the result cache.

Property	Description
Parameter type	Big integer
Syntax	RESULT_CACHE_MAX_SIZE = *integer* [K | M | G]
Default value	Derived from the values of SHARED_POOL_SIZE, SGA_TARGET, and MEMORY_TARGET
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	0 to operating system-dependent
Basic	No
Oracle RAC	You must either set this parameter to 0 on all instances to disable the result cache, or use a nonzero value on all instances. Disabling the result cache on some instances may lead to incorrect results.

Values of this parameter greater than 0 are rounded up to the next multiple of 32 KB. If the value of this parameter is 0, then the feature is disabled.

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for information about tuning the result cache

2.342 RESULT_CACHE_MAX_TEMP_RESULT

RESULT_CACHE_MAX_TEMP_RESULT specifies the percentage of RESULT_CACHE_MAX_TEMP_SIZE that any single cached query result can consume.

Property	Description
Parameter type	Integer
Default value	5 percent
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	0 to 100
Basic	No
Oracle RAC	Multiple instances can have different values.

2.343 RESULT_CACHE_MAX_TEMP_SIZE

RESULT_CACHE_MAX_TEMP_SIZE specifies the maximum amount of temporary tablespace (in bytes) that can be consumed by the result cache.

Property	Description
Parameter type	Big integer
Syntax	RESULT_CACHE_MAX_TEMP_SIZE = *integer* [K | M | G]
Default value	RESULT_CACHE_SIZE * 10
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	0 to operating system-dependent
Basic	No
Oracle RAC	You must either set this parameter to 0 on all instances to disable the result cache, or use a nonzero value on all instances. Disabling the result cache on some instances may lead to incorrect results.

If you attempt to set this parameter to a value that is less than 5% of the size of the SGA, then this parameter will be set to 5% of the size of the SGA. If you attempt to set this parameter to a value that is more than 10% of the current total unused space available for temporary tablespaces in the SYS schema, then this parameter will be set to 10% of the current total unused space available for temporary tablespaces in the SYS schema.

If the value of this parameter is 0, then the result cache is disabled for the PDB.

See Also:

Oracle Database Performance Tuning Guide for information about tuning the result cache

2.344 RESULT_CACHE_MODE

RESULT_CACHE_MODE specifies which queries are eligible to store result sets in the result cache. Only query execution plans with the result cache operator will attempt to read from or write to the result cache.

Property	Description
Parameter type	String
Syntax	RESULT_CACHE_MODE = { MANUAL | MANUAL_TEMP | FORCE | FORCE_TEMP }
Default value	Oracle Autonomous Database: FORCE All other Oracle databases: MANUAL
Modifiable	ALTER SESSION, ALTER SYSTEM

Property	Description
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Different instances can have different values.

Values

- `MANUAL`

  Query results can only be stored in the result cache by using a query hint or table annotation.

- `MANUAL_TEMP`

  Query results can only be stored in the result cache by using a query hint or table annotation. All hinted queries are allowed to leverage temporary segments on disk unless explicitly prohibited by using the `/*+ RESULT_CACHE (TEMP=FALSE) */` hint.

- `FORCE`

  All query results are stored in the result cache. If a query result is not in the cache, then the database executes the query and stores the result in the cache. Subsequent executions of the same SQL statement that include the `/*+ RESULT_CACHE */` hint will retrieve data from the cache. Sessions will use these results, if possible. To exclude query results from the cache, use the `/*+ NO_RESULT_CACHE */` hint.

- `FORCE_TEMP`

  All query results are stored in the result cache. All queries are allowed to leverage temporary segments on disk unless explicitly prohibited by a hint.

Caution:

If this parameter is set to `FORCE` or `FORCE_TEMP`, then Oracle recommends setting the `RESULT_CACHE_INTEGRITY` parameter to `ENFORCED`, which ensures that only deterministic constructs are eligible for result caching. This prevents the caching of nondeterministic constructs, which can potentially cause material changes to results. See "RESULT_CACHE_INTEGRITY" for more information.

See Also:

- *Oracle Database SQL Tuning Guide* for more information on how the result cache handles PL/SQL functions before changing the value of this initialization parameter
- *Oracle Database SQL Language Reference* for more information about the `NO_RESULT_CACHE` hint

2.345 RESULT_CACHE_REMOTE_EXPIRATION

RESULT_CACHE_REMOTE_EXPIRATION specifies the number of minutes that a result using a remote object is allowed to remain valid.

Property	Description
Parameter type	Integer
Default value	0
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	0 to operating system-dependent
Basic	No

Setting this parameter to 0 implies that results using remote objects should not be cached. Setting this parameter to a nonzero value can produce stale answers (for example, if the remote table used by a result is modified at the remote database).

See Also:

Oracle Database Performance Tuning Guide for information about tuning the result cache

2.346 RESUMABLE_TIMEOUT

RESUMABLE_TIMEOUT enables or disables resumable statements and specifies resumable timeout at the system level.

Property	Description
Parameter type	Integer
Default value	0 (seconds)
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Range of values	0 to 2^{31} - 1 (in seconds)
Basic	No
Oracle RAC	Multiple instances can have different values.

See Also:

Oracle Database Administrator's Guide for more information about enabling resumable space allocation, what conditions are correctable, and what statements can be made resumable

2.347 ROLLBACK_SEGMENTS

ROLLBACK_SEGMENTS allocates one or more rollback segments by name to this instance.

Property	Description
Parameter type	String
Syntax	ROLLBACK_SEGMENTS = (segment_name [, segment_name] ...)
Default value	If you do not specify this parameter, the instance uses public rollback segments by default, unless the UNDO_MANAGEMENT initialization parameter is set to AUTO. In that case, the ROLLBACK_SEGMENTS parameter is ignored and automatic undo management is used.
Modifiable	No
Modifiable in a PDB	Yes
Range of values	Any rollback segment names listed in DBA_ROLLBACK_SEGS except SYSTEM
Basic	No
Oracle RAC	Multiple instances must have different values.

If you set this parameter, the instance acquires all of the rollback segments named in this parameter, even if the number of rollback segments exceeds the minimum number required by the instance (calculated as TRANSACTIONS / TRANSACTIONS_PER_ROLLBACK_SEGMENT).

You cannot change the value of this parameter dynamically, but you can change its value and then restart the instance. Although this parameter usually specifies private rollback segments, it can also specify public rollback segments if they are not already in use.

To find the name, segment ID number, and status of each rollback segment in the database, query the data dictionary view DBA_ROLLBACK_SEGS.

When UNDO_MANAGEMENT is set to AUTO, ROLLBACK_SEGMENTS is ignored.

See Also:

- *Oracle Real Application Clusters Administration and Deployment Guide* for information on setting this parameter in an Oracle RAC environment
- "DBA_ROLLBACK_SEGS"

2.348 SAGA_HIST_RETENTION

SAGA_HIST_RETENTION specifies the length of time (in minutes) that completed sagas are retained in the DBA_HIST_SAGAS and USER_HIST_SAGAS views.

Property	Description
Parameter type	Integer
Default value	43200 minutes (equivalent to 30 days)
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	1 - 2147483647 minutes
Basic	No
Oracle RAC	Multiple instances must have the same value.

Note:

This parameter is available starting with Oracle Database 23ai.

See Also:

- "ALL_HIST_SAGAS"
- "DBA_HIST_SAGAS"
- "USER_HIST_SAGAS"

2.349 SEC_MAX_FAILED_LOGIN_ATTEMPTS

SEC_MAX_FAILED_LOGIN_ATTEMPTS specifies the number of authentication attempts that can be made by a client on a connection to the server process.

Property	Description
Parameter type	Integer
Default value	3
Modifiable	No
Modifiable in a PDB	No
Range of values	An integer greater than or equal to 1.
Basic	No

These login attempts can be for multiple user accounts in the same connection. After the specified number of failure attempts, the connection will be automatically dropped by the server process, and the server process is terminated.

> **See Also:**
>
> *Oracle Database Security Guide* for more information about this parameter

2.350 SEC_PROTOCOL_ERROR_FURTHER_ACTION

`SEC_PROTOCOL_ERROR_FURTHER_ACTION` specifies the further execution of a server process when receiving bad packets from a possibly malicious client.

Property	Description
Parameter type	String
Syntax	`SEC_PROTOCOL_ERROR_FURTHER_ACTION = { CONTINUE	(DELAY,`*integer*`)	(DROP,`*integer*`) }`
Default value	`(DROP,3)`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No

Values

- `CONTINUE`

  The server process continues execution. The database server may be subject to a Denial of Service (DoS) if bad packets continue to be sent by a malicious client.

- `(DELAY,`*integer*`)`

  The client experiences a delay of *integer* seconds before the server process accepts the next request from the same client connection. Malicious clients are prevented from excessive consumption of server resources while legitimate clients experience a degradation in performance but can continue to function.

- `(DROP,`*integer*`)`

  The server forcefully terminates the client connection after *integer* cumulative bad packets. The server protects itself at the expense of the client (for example, a client transaction may be lost). The client may reconnect and attempt the same operation.

> **See Also:**
>
> *Oracle Database Security Guide* for examples of using this parameter

2.351 SEC_PROTOCOL_ERROR_TRACE_ACTION

SEC_PROTOCOL_ERROR_TRACE_ACTION specifies the kind of logging the database server does when bad packets are received from a possibly malicious client, apart from the client receiving the error.

Property	Description
Parameter type	String
Syntax	SEC_PROTOCOL_ERROR_TRACE_ACTION = { NONE | TRACE | LOG | ALERT }
Default value	TRACE
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Basic	No

Values

- NONE

  The database server does not record it in any of the trace files.

- TRACE

  A short entry is made in the alert log file and a detailed incident file is generated. The server trace file also will have an entry about the protocol error and incident file.

- LOG

  The server trace file will have an entry about the protocol violation.

- ALERT

  A short entry is made in the alert log file and in the server trace file about the protocol violation.

2.352 SEC_RETURN_SERVER_RELEASE_BANNER

SEC_RETURN_SERVER_RELEASE_BANNER specifies whether the server returns complete database software information to unauthenticated clients.

Property	Description
Parameter type	Boolean
Default value	false
Modifiable	No
Modifiable in a PDB	No
Range of values	true | false
Basic	No

Values

- `true`

  Returns complete database version information to the client.

- `false`

  Returns a generic version string to the client.

> **See Also:**
>
> *Oracle Call Interface Developer's Guide* and *Oracle Database Security Guide* for more information on controlling the display of the database version banner.

2.353 SERIAL_REUSE

`SERIAL_REUSE` specifies which types of cursors make use of the serial-reusable memory feature. This feature allocates private cursor memory in the SGA so that it can be reused (serially, not concurrently) by sessions executing the same cursor.

Property	Description
Parameter type	String
Syntax	`SERIAL_REUSE = { disable | all | select | dml | plsql | force }`
Default value	`disable`
Modifiable	No
Modifiable in a PDB	No
Basic	No

> **Note:**
>
> The `SERIAL_REUSE` parameter is deprecated. It is retained for backward compatibility only.

Values

- `disable`

  Disables the option for all SQL statement types. This value overrides any other values included in the list.

- `all`

  Enables the option for both DML and `SELECT` statements. Equivalent to setting `select`, `dml`, and `plsql`.

- `select`

Enables the option for `SELECT` statements.

- `dml`

  Enables the option for DML statements.

- `plsql`

  Currently has no effect (although PL/SQL packages do support the serial-reuse memory option using PL/SQL pragmas).

> **Note:**
>
> If `CURSOR_SPACE_FOR_TIME` is set to `true`, then the value of `SERIAL_REUSE` is ignored and treated as if it were set to `disable`.

> **See Also:**
>
> "CURSOR_SPACE_FOR_TIME"

2.354 SERVICE_NAMES

`SERVICE_NAMES` specifies one or more names by which clients can connect to the instance.

Property	Description
Parameter type	String
Syntax	`SERVICE_NAMES =` *`db_service_name`* `[,` *`db_service_name`* `[ ... ] ]`
Default value	`DB_UNIQUE_NAME.DB_DOMAIN` if defined
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	Any ASCII string or comma-separated list of string names
Basic	No
Oracle RAC	Do not set the `SERVICE_NAMES` parameter for Oracle RAC environments. Instead, define services using Oracle Enterprise Manager and manage those services using Server Control (SRVCTL) utility.

The instance registers its service names with the listener. When a client requests a service, the listener determines which instances offer the requested service and routes the client to the appropriate instance.

You can specify multiple service names to distinguish among different uses of the same database. For example:

```
SERVICE_NAMES = sales.example.com, widgetsales.example.com
```

You can also use service names to identify a single service that is available from two different databases through the use of replication.

If you do not qualify the names in this parameter with a domain, Oracle qualifies them with the value of the DB_DOMAIN parameter. If DB_DOMAIN is not specified, then no domain will be applied to the non-qualified SERVICE_NAMES values.

When you specify additional service names with this parameter, the default service name is not overridden. The default service name plus the additional service names specified with this parameter are the service names that clients can use to connect to the database.

Note:

The SERVICE_NAMES initialization parameter is deprecated in Oracle Database 19c and may be desupported in a future release.

Use of the SERVICE_NAMES parameter is no longer actively supported. It must not be used for high availability (HA) deployments and it is not supported for HA operations. This restriction includes FAN, load balancing, FAILOVER_TYPE, FAILOVER_RESTORE, SESSION_STATE_CONSISTENCY, and any other uses.

To manage your services, Oracle recommends that you instead use the SRVCTL command-line utility, the GDSCTL command-line utility, or the DBMS_SERVICE PL/SQL package.

See Also:

- *Oracle Database Net Services Administrator's Guide* for more information on this parameter and its settings
- *Oracle Real Application Clusters Administration and Deployment Guide* for information about services administration in an Oracle RAC environment
- "DB_DOMAIN"

2.355 SESSION_CACHED_CURSORS

SESSION_CACHED_CURSORS specifies the number of session cursors to cache.

Property	Description
Parameter type	Integer
Default value	50
Modifiable	ALTER SESSION, ALTER SYSTEM ... DEFERRED
Modifiable in a PDB	Yes
Range of values	0 to operating system-dependent
Basic	No
Oracle RAC	Multiple instances can have different values.

Repeated parse calls of the same SQL (including recursive SQL) or PL/SQL statement cause the session cursor for that statement to be moved into the session cursor cache. Oracle uses a least recently used algorithm to remove entries in the session cursor cache to make room for new entries when needed.

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for information about enabling the session cursor cache

2.356 SESSION_EXIT_ON_PACKAGE_STATE_ERROR

Use `SESSION_EXIT_ON_PACKAGE_STATE_ERROR` to force a hard session exit when a session's state has been invalidated.

Exiting sessions after state invalidation avoids errors that can occur when applications mishandle an invalid state.

Property	Description
Parameter type	Boolean
Default value	`FALSE`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`TRUE	FALSE`
Basic	No
Oracle RAC	Different instances can use different values.

Set `SESSION_EXIT_ON_PACKAGE_STATE_ERROR` to `TRUE` to force a hard session exit under the following circumstances:

- When a stateful PL/SQL package undergoes modification, the sessions that have an active instantiation of the package receive an `ORA-4068` error when they attempt to run it. When `SESSION_EXIT_ON_PACKAGE_STATE_ERROR` is set to `TRUE`, the session immediately exits instead of raising `ORA-04068`. This can be advantageous because many applications are better equipped to handle a session being discarded, and failing to catch errors related to session state, such as `ORA-04068`, can lead to silent data corruption.
- When an Oracle Database Multilingual Engine (MLE) module or environment is modified via DDL, sessions that have an active instantiation of the object receive an `ORA-4106` or `ORA-4107` error. Setting `SESSION_EXIT_ON_PACKAGE_STATE_ERROR` to `TRUE` forces sessions to be disconnected if the session state is invalidated. Because many applications capture session disconnect, this option can help simplify the recovery from the invalidation of an existing session state.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.357 SESSION_MAX_OPEN_FILES

SESSION_MAX_OPEN_FILES specifies the maximum number of BFILEs that can be opened in any session. Once this number is reached, subsequent attempts to open more files in the session by using DBMS_LOB.FILEOPEN() or OCILobFileOpen() will fail. The maximum value for this parameter depends on the equivalent parameter defined for the underlying operating system.

Property	Description
Parameter type	Integer
Default value	10
Modifiable	No
Modifiable in a PDB	No
Range of values	1 to either 50 or the value of MAX_OPEN_FILES defined at the operating system level, whichever is less
Basic	No

See Also:

- *Oracle Database SecureFiles and Large Objects Developer's Guide* for information on LOBs in general
- *Oracle Database SecureFiles and Large Objects Developer's Guide* for information on BFILEs
- *Oracle Database PL/SQL Packages and Types Reference* for information on the DBMS_LOB.FILEOPEN() procedure
- *Oracle Call Interface Developer's Guide* for information on the OCILobFileOpen() procedure

2.358 SESSIONS

SESSIONS specifies the maximum number of sessions that can be created in the system.

Property	Description
Parameter type	Integer
Default value	Derived: (1.5 * PROCESSES) + 22
Modifiable	ALTER SYSTEM can be used in a PDB only to change the value of the SESSIONS parameter for that PDB. ALTER SYSTEM *cannot* be used to change the value of the SESSIONS parameter in a non-CDB or in a CDB$ROOT.
Modifiable in a PDB	Yes

Property	Description
Range of values	1 to 2^{16} (which is 1 to 65536)
Basic	Yes

Because every login requires a session, this parameter effectively determines the maximum number of concurrent users in the system. You should always set this parameter explicitly to a value equivalent to your estimate of the maximum number of concurrent users, plus the number of background processes, plus approximately 10% for recursive sessions.

Oracle uses the default value of this parameter as its minimum. Values between 1 and the default do not trigger errors, but Oracle ignores them and uses the default instead.

The default values of the `ENQUEUE_RESOURCES` and `TRANSACTIONS` parameters are derived from `SESSIONS`. Therefore, if you increase the value of `SESSIONS`, you should consider whether to adjust the values of `ENQUEUE_RESOURCES` and `TRANSACTIONS` as well. (Note that `ENQUEUE_RESOURCES` is obsolete as of Oracle Database 10g release 2 (10.2).)

In a shared server environment, the value of `PROCESSES` can be quite small. Therefore, Oracle recommends that you adjust the value of `SESSIONS` to approximately 1.1 * total number of *connections*.

For a CDB, the root container's `SESSIONS` parameter specifies the total number of sessions for the database.

The `SESSIONS` parameter for a PDB specifies the total number of sessions that can be used by that PDB. Its value defaults to the root container's `SESSIONS` value. If the PDB tries to use more sessions than configured by its `SESSIONS` parameter, an `ORA-00018` error message is generated. For PDBs, the SESSIONS parameter does not count recursive sessions and hence does not require the 10% adjustment.

The `SESSIONS` parameter for a PDB can only be modified by the PDB. It cannot be set higher than the CDB's `SESSIONS` value.

See Also:

- *Oracle Database Concepts* for more information on memory structures
- *Oracle Database Concepts* for more information on processes
- *Oracle Multitenant Administrator's Guide* for more information about CDBs and PDBs

2.359 SGA_MAX_SIZE

`SGA_MAX_SIZE` specifies the maximum size of the SGA for the lifetime of the instance.

Property	Description
Parameter type	Big integer
Syntax	`SGA_MAX_SIZE = integer [K | M | G]`

Property	Description
Default value	Initial size of SGA at startup, dependent on the sizes of different pools in the SGA, such as buffer cache, shared pool, large pool, and so on.
Modifiable	No
Modifiable in a PDB	No
Range of values	0 to operating system-dependent

On 64-bit platforms and non-Windows 32-bit platforms, when either `MEMORY_TARGET` or `MEMORY_MAX_TARGET` is specified, the default value of `SGA_MAX_SIZE` is set to the larger of the two parameters. This causes more address space to be reserved for expansion of the SGA.

On Windows 32-bit platforms, the default value of `SGA_MAX_SIZE` is the largest of the following values:

- 60% of `MEMORY_TARGET`, if specified
- 60% of `MEMORY_MAX_TARGET`, if specified
- 25% of the total available virtual address space

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this parameter

2.360 SGA_MIN_SIZE

`SGA_MIN_SIZE` indicates a possible minimum value for SGA usage of a pluggable database (PDB).

Property	Description
Parameter type	Big integer
Syntax	`SGA_MIN_SIZE = integer [K | M | G]`
Default value	`0`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	0 to 50% of `SGA_TARGET`
Basic	No
Oracle RAC	The same value must be used for all instances.

Setting this parameter at the CDB level has no effect.

Note:

To be able to use Resource Manager in a CDB to control the amount of memory each PDB can use:

- The NONCDB_COMPATIBLE initialization parameter must be set to FALSE at the CDB level (in the root of the CDB).
- The MEMORY_TARGET initialization parameter must not be set at the CDB level.
- A value for SGA_TARGET must be set at the CDB level.

  If SGA_TARGET is not set at the CDB level, then setting SGA_MIN_SIZE in a PDB has no effect. You will not receive an error message, and the PDB's SGA_MIN_SIZE value will not be enforced.
- You must set the SGA_MIN_SIZE value to a value that meets these requirements:
  - In a PDB, to a value that is less than or equal to 50% of the value of SGA_TARGET in the PDB
  - In a PDB, to a value that is less than or equal to 50% of the value of SGA_TARGET at the CDB level
  - In a PDB, to a value that is less than the value of SGA_MAX_SIZE at the CDB level
  - Across all the open PDBs in a CDB, the sum of SGA_MIN_SIZE values must be less than or equal to 50% of the managed SGA total at the CDB level. Managed SGA is DB_CACHE_SIZE plus SHARED_POOL_SIZE.

  When you set SGA_MIN_SIZE in a PDB to a value that does not meet these requirements, you receive an error.

See Also:

Oracle Multitenant Administrator's Guide for more information about the initialization parameters that control the memory usage of PDBs

2.361 SGA_TARGET

SGA_TARGET specifies the total size of all SGA components.

Property	Description
Parameter type	Big integer
Syntax	SGA_TARGET = *integer* [K | M | G]
Default value	0 (SGA autotuning is disabled for DEFERRED mode autotuning requests, but allowed for IMMEDIATE mode autotuning requests)
Modifiable	ALTER SYSTEM
Modifiable in a PDB	Yes

Property	Description
Range of values	64 MB to SGA_MAX_SIZE Note that if MEMORY_MAX_TARGET > 0, then the value of SGA_TARGET also cannot exceed the value of MEMORY_MAX_TARGET.
Basic	Yes

If SGA_TARGET is specified, then the following memory pools are automatically sized:

- Buffer cache (DB_CACHE_SIZE)
- Shared pool (SHARED_POOL_SIZE)
- Large pool (LARGE_POOL_SIZE)
- Java pool (JAVA_POOL_SIZE)
- Streams pool (STREAMS_POOL_SIZE)
- Data transfer cache (DATA_TRANSFER_CACHE_SIZE)

If these automatically tuned memory pools are set to nonzero values, then those values are used as minimum levels by Automatic Shared Memory Management. You would set minimum values if an application component needs a minimum amount of memory to function properly.

The following pools are manually sized components and are not affected by Automatic Shared Memory Management:

- Log buffer
- Other buffer caches, such as KEEP, RECYCLE, and other block sizes
- Fixed SGA and other internal allocations

The memory allocated to these pools is deducted from the total available for SGA_TARGET when Automatic Shared Memory Management computes the values of the automatically tuned memory pools.

In the **Default value** field, IMMEDIATE mode autotuning requests are necessary to avoid ORA-04031 errors. The DEFERRED and IMMEDIATE modes are reflected in the OPER_MODE column of the V$MEMORY_RESIZE_OPS view.

If Automatic Memory Management is enabled (MEMORY_TARGET is set to a positive value) and SGA_TARGET is also set to a positive value, the SGA_TARGET value acts as the minimum value for the size of the SGA.

Note:

This parameter is optional for pluggable databases (PDBs). When this parameter is set for a PDB, it specifies the maximum SGA that the PDB can use at any time. When this parameter is not set at the PDB level, the PDB has no limit for the amount of SGA it can use, other than the CDB's SGA size.

To be able to use Resource Manager in a CDB to control the amount of memory each PDB can use:

- The `NONCDB_COMPATIBLE` initialization parameter must be set to `FALSE` at the CDB level (in the root of the CDB).
- The `MEMORY_TARGET` initialization parameter must not be set at the CDB level.
- You must set the `SGA_TARGET` initialization parameter at the CDB level.
- You must set `SGA_TARGET` in a PDB.

  If you set a PDB's `SGA_TARGET` value and `SGA_TARGET` is not set at the CDB level, you will not receive an error message and the PDB's `SGA_TARGET` value will not be enforced.
- When setting `SGA_TARGET` in a PDB, the following requirements must be met:
  - The value of `SGA_TARGET` in the PDB must be less than or equal to the `SGA_TARGET` value at the CDB level.
  - The value of `SGA_TARGET` in the PDB must be less than or equal to the `SGA_MAX_SIZE` value at the CDB level.
  - The value of `SGA_TARGET` in the PDB must be twice the PDB's `DB_CACHE_SIZE` value, if the PDB's `DB_CACHE_SIZE` value is set.
  - The value of `SGA_TARGET` in the PDB must be twice the PDB's `SHARED_POOL_SIZE` value, if the PDB's `SHARED_POOL_SIZE` value is set.
  - The value of `SGA_TARGET` in the PDB must be twice the PDB's `SGA_MIN_SIZE` value, if the PDB's `SGA_MIN_SIZE` value is set.

  When you set `SGA_TARGET` in a PDB to a value that does not meet these requirements, you receive an error.

See Also:

- "DB_CACHE_SIZE"
- "SHARED_POOL_SIZE"
- "LARGE_POOL_SIZE"
- "JAVA_POOL_SIZE"
- "STREAMS_POOL_SIZE"
- "V$MEMORY_RESIZE_OPS"
- "MEMORY_TARGET"
- "PGA_AGGREGATE_TARGET"
- *Oracle Multitenant Administrator's Guide* for more information about the initialization parameters that control the memory usage of PDBs
- *Oracle Database Administrator's Guide* for information on automatic memory management
- *Oracle Database Administrator's Guide* for information on managing the SGA manually

2.362 SHADOW_CORE_DUMP

`SHADOW_CORE_DUMP` specifies whether Oracle includes the SGA in the core file for foreground (client) processes.

Property	Description
Parameter type	String
Syntax	`SHADOW_CORE_DUMP = { partial | full | none }`
Default value	`partial`. On Windows, the default value is `none`.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

Values

- `partial`

  Oracle does not include the SGA in the core dump.

- `full`

  Oracle includes the SGA in the core dump.

- `none`

  No core files will be generated for foreground processes.

> **See Also:**
>
> "BACKGROUND_CORE_DUMP"

2.363 SHARD_ENABLE_RAFT_FOLLOWER_READ

Use `SHARD_ENABLE_RAFT_FOLLOWER_READ` to enable or disable reads from follower replication units in a shard.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.364 SHARD_RAFT_LOGFILE_SIZE

`SHARD_RAFT_LOGFILE_SIZE` specifies (in bytes) the size of Raft log files.

Property	Description
Parameter type	Big integer
Syntax	`SHARD_RAFT_LOGFILE_SIZE = integer [K	M	G]`
Default value	`1G`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`0` to operating system-dependent
Basic	No
Oracle RAC	Different instances can use different values.

Each replication unit (RU) has 3 Raft log files. Therefore, the log capacity of an RU is 3 times the value of this parameter.

When you modify the value of this parameter in the current instance, the change takes effect the first time a Raft log file is subsequently overwritten.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.365 SHARED_MEMORY_ADDRESS

`SHARED_MEMORY_ADDRESS` and `HI_SHARED_MEMORY_ADDRESS` specify the starting address at run time of the system global area (SGA). This parameter is ignored on the many platforms that specify the SGA's starting address at linktime.

Property	Description
Parameter type	Integer
Default value	`0`
Modifiable	No
Modifiable in a PDB	No
Basic	No

Use this parameter to specify the entire address on 32-bit platforms and to specify the low-order 32 bits of a 64-bit address on 64-bit platforms. Use `HI_SHARED_MEMORY_ADDRESS` to specify the high-order 32 bits of a 64-bit address on 64-bit platforms. If both parameters are 0 or unspecified, the SGA address defaults to a platform-specific location.

> **See Also:**
>
> "HI_SHARED_MEMORY_ADDRESS"

2.366 SHARED_POOL_RESERVED_SIZE

`SHARED_POOL_RESERVED_SIZE` specifies (in bytes) the shared pool space that is reserved for large contiguous requests for shared pool memory.

Property	Description
Parameter type	Big integer
Syntax	`SHARED_POOL_RESERVED_SIZE = integer [K | M | G]`
Default value	5% of the value of `SHARED_POOL_SIZE`
Modifiable	No
Modifiable in a PDB	No
Range of values	Minimum: `5000` Maximum: half of the value of `SHARED_POOL_SIZE`
Basic	No

You can use this parameter to avoid performance degradation in the shared pool in situations where pool fragmentation forces Oracle to search for and free chunks of unused pool to satisfy the current request.

See Also:

- "SHARED_POOL_SIZE"
- *Oracle Database Performance Tuning Guide* for information on sizing the shared pool

2.367 SHARED_POOL_SIZE

`SHARED_POOL_SIZE` specifies (in bytes) the size of the shared pool.

Property	Description
Parameter type	Big integer
Syntax	`SHARED_POOL_SIZE = integer [K | M | G]`
Default value	If `SGA_TARGET` is set: If the parameter is not specified, then the default is `0` (internally determined by the Oracle Database). If the parameter is specified, then the user-specified value indicates a minimum value for the memory pool. If `SGA_TARGET` is not set (32-bit platforms): `64` MB, rounded up to the nearest granule size. If `SGA_TARGET` is not set (64-bit platforms): `128` MB, rounded up to the nearest granule size. For considerations when dealing with database instances using Oracle ASM, see "SHARED_POOL_SIZE and Automatic Storage Management".
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	Minimum: the granule size Maximum: operating system-dependent
Basic	No

The shared pool contains shared cursors, stored procedures, control structures, and other structures. If `SGA_TARGET` is not set, then Oracle also allocates parallel execution message buffers from the shared pool. Larger values improve performance in multiuser systems. Smaller values use less memory.

You can monitor utilization of the shared pool by querying the view `V$SGASTAT`.

Note:

This parameter is optional for pluggable databases (PDBs). When this parameter is set for a PDB, it indicates a possible minimum value for the PDB usage of the memory pool.

To be able to use Resource Manager in a CDB to control the amount of memory each PDB can use:

- The `NONCDB_COMPATIBLE` initialization parameter must be set to `FALSE` at the CDB level (in the root of the CDB).
- The `MEMORY_TARGET` initialization parameter must not be set at the CDB level.
- If the `SGA_TARGET` initialization parameter is set at the CDB level, then the following requirement must be met:
  - The value of `SHARED_POOL_SIZE` set in a PDB must be less than or equal to 50% of the `SGA_TARGET` value at the CDB level.
- If the `SGA_TARGET` initialization parameter is set at the PDB level, then the following requirement must be met:
  - The value of `SHARED_POOL_SIZE` set in a PDB must be less than or equal to 50% of the `SGA_TARGET` value at the PDB level.
- If the `SGA_TARGET` initialization parameter is not set, but the `SHARED_POOL_SIZE` initialization parameter is set at the CDB level, then the following requirement must be met:
  - The value of `SHARED_POOL_SIZE` set in a PDB must be less than or equal to 50% of the `SHARED_POOL_SIZE` value at the CDB level.

When you set `SHARED_POOL_SIZE` in a PDB to a value that does not meet these requirements, you receive an error.

See Also:

- "V$SGASTAT"
- *Oracle Multitenant Administrator's Guide* for more information about the initialization parameters that control the memory usage of PDBs
- *Oracle Database Performance Tuning Guide* for more information on setting this parameter

SHARED_POOL_SIZE and Automatic Storage Management

On a database instance using Oracle Automatic Storage Management (Oracle ASM), additional memory is required to store extent maps. As a general guideline, you can aggregate the values from the following queries to obtain current database storage size that is either already on Oracle ASM or will be stored in Oracle ASM. Then determine the redundancy type that is used (or will be used), and calculate the value for `SHARED_POOL_SIZE`, using the aggregated value as input.

```
SELECT SUM(BYTES)/(1024*1024*1024) FROM V$DATAFILE;
SELECT SUM(BYTES)/(1024*1024*1024) FROM V$LOGFILE a, V$LOG b
WHERE a.group#=b.group#;
SELECT SUM(BYTES)/(1024*1024*1024) FROM V$TEMPFILE WHERE
status='ONLINE';
```

Additionally, keep the following guidelines in mind:

- For disk groups using external redundancy:

  (Every 100G of space needs 1M of extra shared pool) + 2M
- For disk groups using normal redundancy:

  (Every 50G of space needs 1M of extra shared pool) + 4M
- For disk groups using high redundancy:

  (Every 33G of space needs 1M of extra shared pool) + 6M

2.368 SHARED_SERVER_SESSIONS

`SHARED_SERVER_SESSIONS` specifies the total number of shared server sessions to allow.

Property	Description
Parameter type	Integer
Default value	There is no default value.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	If `SHARED_SERVER_SESSIONS` is specified, then it should be less than `SESSIONS`. If `SHARED_SERVER_SESSIONS` is not specified, then a shared server session may be created as long as there is a free session slot.
Basic	No

Setting this parameter enables you to reserve user sessions for dedicated servers.

> **See Also:**
>
> *Oracle Database Concepts* for more information on sessions

2.369 SHARED_SERVERS

`SHARED_SERVERS` specifies the number of server processes that you want to create when an instance is started. If system load decreases, then this minimum number of servers is maintained. Therefore, you should take care not to set `SHARED_SERVERS` too high at system startup.

Property	Description
Parameter type	Integer

Property	Description
Default value	`0`, meaning that shared server is not on. If you are using shared server architecture or if the `DISPATCHERS` parameter is set such that the total number of dispatchers is more than 0, then the default value is `1`.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	The value of this parameter should be less than `MAX_SHARED_SERVERS`. If it is greater than or equal to `MAX_SHARED_SERVERS`, then the number of servers will not be self-tuned but will remain constant, as specified by `SHARED_SERVERS`.
Basic	Yes

Starting with Oracle Database 12*c* Release 1 (12.1.0.2), the `SHARED_SERVERS` parameter can be set on PDBs. However, unlike most other parameters that can be set on a PDB, this parameter can only be used within a PDB to enable or disable use of shared servers for that PDB. Therefore, in a PDB, the DBA can either set `SHARED_SERVERS` to 0 to disable use of shared servers for that PDB or use `ALTER SYSTEM RESET SHARED_SERVERS` to re-enable shared servers for the PDB. The configuration of shared servers for the CDB can only be done in the root.

See Also:

- "DISPATCHERS"
- "MAX_SHARED_SERVERS"
- *Oracle Database Administrator's Guide* for more information on setting this parameter

2.370 SHRD_DUPL_TABLE_REFRESH_RATE

`SHRD_DUPL_TABLE_REFRESH_RATE` displays the duplicated table refresh rate (in seconds).

Property	Description
Parameter type	Integer
Default value	`60`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	20 to 2^{31} - 1
Basic	No
Oracle RAC	All instances should use the same instance.

You can change the value of this parameter to change the duplicated table refresh rate.

A duplicated table is a table that has the same contents on all shards in a sharded database. Duplicated tables are implemented using materialized views that are refreshed at a certain rate.

See Also:

- *Oracle Globally Distributed Database Guide* for an introduction to sharding
- *Oracle Globally Distributed Database Guide* for more information about duplicated tables

2.371 SKIP_UNUSABLE_INDEXES

`SKIP_UNUSABLE_INDEXES` enables or disables the use and reporting of tables with unusable indexes or index partitions.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No

If a SQL statement uses a hint that forces the usage of an unusable index, then this hint takes precedence over initialization parameter settings, including `SKIP_UNUSABLE_INDEXES`. If the optimizer chooses an unusable index, then an `ORA-01502` error will result. (See *Oracle Database Administrator's Guide* for more information about using hints.)

Values

- `true`

  Disables error reporting of indexes and index partitions marked UNUSABLE. This setting allows all operations (inserts, deletes, updates, and selects) on tables with unusable indexes or index partitions.

  Note:

  If an index is used to enforce a UNIQUE constraint on a table, then allowing insert and update operations on the table might violate the constraint. Therefore, this setting does not disable error reporting for unusable indexes that are unique.

- `false`

Enables error reporting of indexes marked UNUSABLE. This setting does not allow inserts, deletes, and updates on tables with unusable indexes or index partitions.

> **See Also:**
>
> *Oracle Database SQL Language Reference* for more information about hints

2.372 SMTP_OUT_SERVER

`SMTP_OUT_SERVER` specifies the SMTP host and port to which `UTL_MAIL` delivers outbound E-mail.

Property	Description
Parameter type	String
Syntax	`SMTP_OUT_SERVER = server_clause [, server_clause ] ...`
Syntax	**`server_clause::=`** *`host_name`*`[:`*`port`*`]`
Default value	There is no default value.
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

Multiple servers may be specified, separated by commas.

If the first server in the list is unavailable, then `UTL_MAIL` tries the second server, and so on.

If `SMTP_OUT_SERVER` is not specified, then the SMTP server name defaults to the value of `DB_DOMAIN`, the port number defaults to `25`, and the SMTP domain defaults to the suffix of `DB_DOMAIN`.

> **See Also:**
>
> *Oracle Database PL/SQL Packages and Types Reference* for information on the `UTL_MAIL` package

2.373 SORT_AREA_RETAINED_SIZE

`SORT_AREA_RETAINED_SIZE` specifies (in bytes) the maximum amount of the user global area (UGA) memory retained after a sort run completes. The retained size controls the size of the read buffer, which Oracle uses to maintain a portion of the sort in memory. This memory is released back to the UGA, not to the operating system, after the last row is fetched from the sort space.

Property	Description
Parameter type	Integer
Default value	Derived from SORT_AREA_SIZE
Modifiable	ALTER SESSION, ALTER SYSTEM ... DEFERRED
Modifiable in a PDB	Yes
Range of values	From the value equivalent of two database blocks to the value of SORT_AREA_SIZE
Basic	No

Note:

Oracle does not recommend using the SORT_AREA_RETAINED_SIZE parameter unless the instance is configured with the shared server option. Oracle recommends that you enable automatic sizing of SQL working areas by setting PGA_AGGREGATE_TARGET instead. SORT_AREA_RETAINED_SIZE is retained for backward compatibility.

Oracle may allocate multiple sort spaces of this size for each query. Usually, only one or two sorts occur simultaneously, even for complex queries. In some cases, however, additional concurrent sorts are required, and each sort keeps its own memory area. If the shared server is used, allocation is to the SGA until the value in SORT_AREA_RETAINED_SIZE is reached. The difference between SORT_AREA_RETAINED_SIZE and SORT_AREA_SIZE is allocated to the PGA.

Note:

The default value as reflected in the V$PARAMETER dynamic performance view is 0. However, if you do not explicitly set this parameter, Oracle actually uses the value of the SORT_AREA_SIZE parameter.

See Also:

- "SORT_AREA_SIZE"
- *Oracle Database Performance Tuning Guide* for information on setting the values of this parameter and the SORT_AREA_SIZE parameter to tune sort operations using shared servers

2.374 SORT_AREA_SIZE

SORT_AREA_SIZE specifies (in bytes) the maximum amount of memory Oracle will use for a sort.

Property	Description
Parameter type	Integer
Default value	65536
Modifiable	ALTER SESSION, ALTER SYSTEM ... DEFERRED
Modifiable in a PDB	Yes
Range of values	Minimum: the value equivalent of six database blocks Maximum: operating system-dependent
Basic	No

Note:

Oracle does not recommend using the SORT_AREA_SIZE parameter unless the instance is configured with the shared server option. Oracle recommends that you enable automatic sizing of SQL working areas by setting PGA_AGGREGATE_TARGET instead. SORT_AREA_SIZE is retained for backward compatibility.

After the sort is complete, but before the rows are returned, Oracle releases all of the memory allocated for the sort, except the amount specified by the SORT_AREA_RETAINED_SIZE parameter. After the last row is returned, Oracle releases the remainder of the memory.

Increasing SORT_AREA_SIZE size improves the efficiency of large sorts.

Each sort in a query can consume memory up to the amount specified by SORT_AREA_SIZE, and there can be multiple sorts in a query. Also, if a query is executed in parallel, each PX server can consume memory up to the amount specified by SORT_AREA_SIZE for each sort it does.

SORT_AREA_SIZE is also used for inserts and updates to bitmap indexes. Setting this value appropriately results in a bitmap segment being updated only once for each DML operation, even if more than one row in that segment changes.

Larger values of SORT_AREA_SIZE permit more sorts to be performed in memory. If more space is required to complete the sort than will fit into the memory provided, then temporary segments on disk are used to hold the intermediate sort runs.

The default is adequate for most OLTP operations. You might want to adjust this parameter for decision support systems, batch jobs, or large CREATE INDEX operations.

See Also:

- *Oracle Database Concepts* for information on sort areas
- Your operating system-specific Oracle documentation for the default value on your system
- "SORT_AREA_RETAINED_SIZE"

2.375 SPATIAL_VECTOR_ACCELERATION

`SPATIAL_VECTOR_ACCELERATION` enables or disables the spatial vector acceleration.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No
Oracle RAC	Multiple instances should use the same value

The setting of `true` for this parameter improves spatial vector query performance.

> **See Also:**
>
> *Oracle Spatial Developer's Guide* for more information about this parameter

2.376 SPFILE

The value of this parameter is the name of the current server parameter file (`SPFILE`) in use.

Property	Description
Parameter type	String
Syntax	`SPFILE = spfile_name`
Default value	*`ORACLE_BASE_CONFIG`*`/dbs/spfile.ora`
Modifiable	No
Modifiable in a PDB	No
Range of values	Any valid `SPFILE`
Basic	No
Oracle RAC	Multiple instances must have the same value.

This parameter can be defined in a client side PFILE to indicate the name of the server parameter file to use.

When the default server parameter file is used by the server, the value of `SPFILE` is internally set by the server.

The `SPFILE` resides in the *`ORACLE_BASE_CONFIG`*`/dbs` directory; however, users can place it anywhere on their system as long as it is specified in an initialization parameter file.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about creating the server parameter file

2.377 SQL_ERROR_MITIGATION

Use `SQL_ERROR_MITIGATION` to enable or disable automatic error mitigation for SQL statements.

Property	Description
Parameter type	String
Syntax	`SQL_ERROR_MITIGATION = { ON | OFF }`
Default value	`ON`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Different instances can use different values.

Set this parameter to `ON` to enable automatic error mitigation for SQL statements; set it to `OFF` to disable automatic error mitigation for SQL statements.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.378 SQL_HISTORY_ENABLED

Use `SQL_HISTORY_ENABLED` to enable or disable SQL history monitoring.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true` | `false`
Basic	No
Oracle RAC	Different instances can use different values.

To enable SQL history monitoring, set this parameter to `true`. This feature monitors user-issued SQL statements in each user session on a best effort, depending on memory capacity. DDL, DML, and query statements are monitored; SQL statements

issued in the background and recursive SQL statements are excluded. The monitored information is exposed by the `V$SQL_HISTORY` dynamic performance view.

To disable SQL history monitoring, set this parameter to `false`.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

> **See Also:**
>
> "V$SQL_HISTORY"

2.379 SQL_TRACE

`SQL_TRACE` enables or disables the SQL trace facility.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No

Setting this parameter to `true` provides information on tuning that you can use to improve performance.

> **Note:**
>
> Using this initialization parameter to enable the SQL trace facility for the entire instance can have a severe performance impact. Enable the facility for specific sessions using the `ALTER SESSION` statement. If you must enable the facility on an entire production environment, then you can minimize performance impact by:
>
> - Maintaining at least 25% idle CPU capacity
> - Maintaining adequate disk space for the `USER_DUMP_DEST` location
> - Striping disk space over sufficient disks

> **Note:**
>
> The SQL_TRACE parameter is deprecated. Oracle recommends that you use the DBMS_MONITOR and DBMS_SESSION packages instead. SQL_TRACE is retained for backward compatibility only.

> **See Also:**
>
> - "USER_DUMP_DEST"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_MONITOR package
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SESSION package
> - *Oracle Database Performance Tuning Guide* for more information about performance diagnostic tools

2.380 SQL_TRANSPILER

SQL_TRANSPILER enables or disables the SQL Transpiler.

Property	Description
Parameter type	String
Syntax	SQL_TRANSPILER = { ON | OFF }
Default value	OFF
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Different instances can use different values.

When this parameter is set to ON, the SQL Transpiler feature is enabled and PL/SQL functions are automatically transpiled into SQL expressions whenever possible, without user intervention. When this parameter is set to OFF, the SQL Transpiler feature is disabled.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.381 SQL92_SECURITY

SQL92_SECURITY specifies whether users must have been granted the SELECT privilege on a table to execute an UPDATE or DELETE statement that references table column values in a WHERE or SET clause.

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	No
Modifiable in a PDB	Yes
Range of values	true | false
Basic	No

The SQL standard specifies that security administrators should be able to require that users have SELECT privilege on a table when executing an UPDATE or DELETE statement that references table column values in a WHERE or SET clause.

Values

- true

  The user must have SELECT privilege on a column to reference it in the WHERE clause of a DELETE or UPDATE statement, on the right hand side of an assignment in the SET clause of an UPDATE statement.

- false

  A user with DELETE privilege on the target table of a DELETE statement may reference any column of that target table in the WHERE clause. A user with UPDATE privilege on the target table of an UPDATE statement may reference any column of that target in the WHERE clause or on the right hand side of any assignment in the SET clause of the UPDATE statement.

2.382 SQLTUNE_CATEGORY

SQLTUNE_CATEGORY specifies the category name for use by sessions to qualify the lookup of SQL profiles during SQL compilation.

Property	Description
Parameter type	String
Syntax	SQLTUNE_CATEGORY = *category_name*
Default value	DEFAULT
Modifiable	ALTER SESSION, ALTER SYSTEM
Modifiable in a PDB	Yes
Basic	No

> **See Also:**
>
> *Oracle Database PL/SQL Packages and Types Reference* for information on the `DBMS_SQLTUNE` package

2.383 STANDBY_DB_PRESERVE_STATES

`STANDBY_DB_PRESERVE_STATES` controls whether user sessions, buffers, and other internal states of the instance are retained when a readable physical standby database is converted to a primary database. This parameter is meaningful on a physical standby database that is open in real-time query mode.

Property	Description
Parameter type	String
Syntax	`STANDBY_DB_PRESERVE_STATES = { NONE | SESSION | BUFFER | ALL }`
Default value	`NONE`
Modifiable	No
Modifiable in a PDB	No
Basic	No
Oracle RAC	The same value must be used on all instances.

Values

- `NONE`

  Nothing is retained. All sessions are disconnected and all buffers are flushed. This is the default value.

- `SESSION`

  User sessions are retained. When the database is reopened as the primary, the retained sessions resume their operations as if nothing had happened. If the database (or an individual PDB) is not opened in the primary role, the sessions will be terminated.

- `BUFFER`

  All current buffers are retained. Media recovery buffers are converted to current buffers and retained, if possible. When the database is reopened as the primary, the retained buffers are available for use, which may enable queries to run faster during the first few minutes of operation. If the database (or an individual PDB) is not opened in the primary role, the buffers will be flushed.

- `ALL`

  This value is equivalent to setting both the `SESSION` and `BUFFER` values.

> **Note:**
>
> Sessions that have long running queries or are using database links will not be retained regardless of the setting of this parameter.

> **See Also:**
>
> - *Oracle Data Guard Concepts and Administration* for more information about real-time query mode
> - *Oracle Data Guard Concepts and Administration* for more information about preserving user sessions and buffers when a standby database is converted to a primary database

2.384 STANDBY_FILE_MANAGEMENT

`STANDBY_FILE_MANAGEMENT` enables or disables automatic standby file management.

Property	Description
Parameter type	String
Syntax	`STANDBY_FILE_MANAGEMENT = { MANUAL | AUTO }`
Default value	`MANUAL`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No

When automatic standby file management is enabled, operating system file additions and deletions on the primary database are replicated on the standby database. `STANDBY_FILE_MANAGEMENT` is only applicable to physical standby databases.

Values

- `MANUAL`

  Disables automatic standby file management

- `AUTO`

  Enables automatic standby file management

Setting `STANDBY_FILE_MANAGEMENT` to `AUTO` causes Oracle to automatically create files on the standby database and, in some cases, overwrite existing files. Care must be taken when setting `STANDBY_FILE_MANAGEMENT` and `DB_FILE_NAME_CONVERT` so that existing standby files will not be accidentally overwritten.

If the standby database is on the same system as the primary database, then ensure that the primary and standby systems do not point to the same files.

> **See Also:**
>
> *Oracle Data Guard Concepts and Administration* for more information about setting this parameter

2.385 STANDBY_PDB_SOURCE_FILE_DBLINK

`STANDBY_PDB_SOURCE_FILE_DBLINK` specifies the name of a database link that will be used to try to copy the datafiles from a source PDB to which the database link points.

Property	Description
Parameter type	String
Syntax	`STANDBY_PDB_SOURCE_FILE_DBLINK = database-link`
Default value	NULL
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No
Oracle RAC	Different values can be set on different instances.

In Oracle Database releases prior to Oracle Database 18c, if a PDB was created by cloning a PDB from the same CDB (a local clone), on a standby the datafiles were automatically copied from the source PDB. However, when the PDB was created as a remote clone, the user was responsible for copying datafiles to the Oracle Managed Files (OMF) location on the standby.

To address that deficiency, the `STANDBY_PDB_SOURCE_FILE_DBLINK` parameter specifies the name of a database link that will be used to try to copy the datafiles from a source PDB to which the database link points. The file copy is done only if the database link points to the source PDB and the source PDB is open in read only mode. Otherwise, the user is still responsible for copying datafiles to the OMF location on the standby.

This parameter can also be used to try to copy files in cases where the source PDB's files are not present on the standby. For example, the source PDB could have been created with standbys=NONE. In this case, the `STANDBY_PDB_SOURCE_FILE_DBLINK` parameter can enable the standby to copy files from the primary if there is a database link set up to the primary.

> **See Also:**
>
> "STANDBY_PDB_SOURCE_FILE_DIRECTORY"

2.386 STANDBY_PDB_SOURCE_FILE_DIRECTORY

`STANDBY_PDB_SOURCE_FILE_DIRECTORY` specifies a directory location on the standby where source datafiles for instantiating the standby PDB may be found.

Property	Description
Parameter type	String
Syntax	`STANDBY_PDB_SOURCE_FILE_DIRECTORY = datafiles-directory`
Default value	NULL
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Basic	No
Oracle RAC	Different values can be set on different instances.

In Oracle Database releases prior to Oracle Database 18c, if a PDB was plugged into a CDB, on a standby, the datafiles were expected to be in PDB's Oracle Managed Files (OMF) directory location. If they were not found there, the user had to copy the datafiles to the OMF location and then restart redo apply on the standby.

To address that deficiency, the `STANDBY_PDB_SOURCE_FILE_DIRECTORY` specifies a directory location on the standby where source datafiles for instantiating the PDB may be found. If the datafiles are not found there, an attempt will be made to locate them in the OMF location on the standby.

This parameter can also be used to try to copy files in cases where the source PDB's files are not present on the standby. For example, the source PDB could have been created with standbys=NONE. In this case, the `STANDBY_PDB_SOURCE_FILE_DIRECTORY` parameter can enable the standby to copy files from a location if they are made available.

See Also:

"STANDBY_PDB_SOURCE_FILE_DBLINK"

2.387 STAR_TRANSFORMATION_ENABLED

`STAR_TRANSFORMATION_ENABLED` determines whether a cost-based query transformation will be applied to star queries.

Property	Description
Parameter type	String
Syntax	`STAR_TRANSFORMATION_ENABLED = { FALSE | TRUE | TEMP_DISABLE }`
Default value	`FALSE`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes

Property	Description
Basic	Yes

Values

- `FALSE`

  The transformation will not be applied.

- `TRUE`

  The optimizer will consider performing a cost-based query transformation on the star query.

- `TEMP_DISABLE`

  The optimizer will consider performing a cost-based query transformation on the star query but will not use temporary tables in the star transformation.

See Also:

- *Oracle Database SQL Tuning Guide* for information on enabling star queries

2.388 STATISTICS_LEVEL

`STATISTICS_LEVEL` specifies the level of collection for database and operating system statistics. The Oracle Database collects these statistics for a variety of purposes, including making self-management decisions.

Property	Description
Parameter type	String
Syntax	`STATISTICS_LEVEL = { ALL | TYPICAL | BASIC }`
Default value	`TYPICAL`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

The default setting of `TYPICAL` ensures collection of all major statistics required for database self-management functionality and provides best overall performance. The default value should be adequate for most environments.

When the `STATISTICS_LEVEL` parameter is set to `ALL`, additional statistics are added to the set of statistics collected with the `TYPICAL` setting. The additional statistics are timed operating system statistics and plan execution statistics.

Setting the `STATISTICS_LEVEL` parameter to `BASIC` disables the collection of many of the important statistics required by Oracle Database features and functionality, including:

- All server-generated alerts
- Automatic Database Diagnostic Monitor (ADDM)
- Automatic optimizer statistics collection
- Automatic SGA Memory Management
- Automatic Workload Repository (AWR) Snapshots
- Buffer cache advisory
- Database time distribution statistics (`V$SESS_TIME_MODEL` and `V$SYS_TIME_MODEL`)
- End to End Application Tracing (`V$CLIENT_STATS`)
- Monitoring of statistics
- MTTR advisory
- Object Activity Tracking System (OATS)
- Object level statistics
- PGA Target advisory
- Segment level statistics
- Service level statistics
- Shared pool sizing advisory
- Timed statistics

> **Note:**
>
> Oracle strongly recommends that you do not disable these important features and functionality.

When the `STATISTICS_LEVEL` parameter is modified by `ALTER SYSTEM`, all advisories or statistics are dynamically turned on or off, depending on the new value of `STATISTICS_LEVEL`. When modified by `ALTER SESSION`, the following advisories or statistics are turned on or off in the local session only. Their systemwide state is not changed:

- Timed statistics
- Timed operating system statistics
- Plan execution statistics

The `V$STATISTICS_LEVEL` view displays information about the status of the statistics or advisories controlled by the `STATISTICS_LEVEL` parameter. See "V$STATISTICS_LEVEL".

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this parameter

2.389 STREAMS_POOL_SIZE

The STREAMS_POOL_SIZE value helps determine the size of the Streams pool.

Property	Description
Parameter type	Big integer
Syntax	STREAMS_POOL_SIZE = *integer* [K | M | G]
Default value	0
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	Minimum: 0 (values greater than zero are rounded up to the nearest granule size) Maximum: operating system-dependent
Basic	No

Oracle's Automatic Shared Memory Management feature manages the size of the Streams pool when the SGA_TARGET initialization parameter is set to a nonzero value. If the STREAMS_POOL_SIZE initialization parameter also is set to a nonzero value, then Automatic Shared Memory Management uses this value as a minimum for the Streams pool.

If SGA_TARGET is set to a nonzero value and STREAMS_POOL_SIZE is not specified or is set to a null value, Automatic Shared Memory Management uses 0 (zero) bytes as a minimum for the Streams pool.

If the STREAMS_POOL_SIZE initialization parameter is set to a nonzero value, and the SGA_TARGET parameter is set to 0 (zero), then the Streams pool size is the value specified by the STREAMS_POOL_SIZE parameter, in bytes.

If both the STREAMS_POOL_SIZE and the SGA_TARGET initialization parameters are set to 0 (zero), then, by default, on the first request for Streams pool memory in a database, an amount of memory equal to 10% of the shared pool is transferred from the buffer cache to the Streams pool. Products and features that use the Streams pool include Oracle GoldenGate, XStream, Oracle Advanced Queuing, and Oracle Data Pump.

The Streams pool is a shared resource, and the amount of memory a process can use from the Streams pool is determined by the application. The capture or apply parameter MAX_SGA_SIZE can be controlled for Oracle GoldenGate or XStream. For Oracle Advanced Queuing, use the procedures in the dbms_aqadm package to control the amount of Streams Pool needed.

See Also:

- *Oracle Database XStream Guide* for information on configuring the Streams pool for an XStream Out configuration
- *Oracle Database XStream Guide* for information on configuring the Streams pool for an XStream In configuration
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `dbms_aqadm` package

2.390 SYSDATE_AT_DBTIMEZONE

`SYSDATE_AT_DBTIMEZONE` enables special handling for the date and time value returned in calls to `SYSDATE` and `SYSTIMESTAMP`.

Depending on the value of `SYSDATE_AT_DBTIMEZONE`, you see either the date and time based on the default Autonomous Database time zone, Coordinated Universal Time (UTC), or based on the time zone that you set in your database.

Note:

This parameter is valid only for Oracle Autonomous Database Serverless. On other types of Oracle databases, the value of this parameter is ignored.

See Also:

Using Oracle Autonomous Database Serverless for more information about this parameter

2.391 TABLESPACE_ENCRYPTION

`TABLESPACE_ENCRYPTION` specifies the tablespace encryption policy for a database.

Property	Description
Parameter type	String
Syntax	`TABLESPACE_ENCRYPTION = { AUTO_ENABLE | MANUAL_ENABLE | DECRYPT_ONLY }`
Default value	Cloud databases: `AUTO_ENABLE` On-premises databases: `MANUAL_ENABLE`
Modifiable	No
Modifiable in a PDB	No
Basic	No

Property	Description
Oracle RAC	The same value should be specified for all instances.

The TABLESPACE_ENCRYPTION parameter is an alternative to the deprecated ENCRYPT_NEW_TABLESPACES parameter. Similar to ENCRYPT_NEW_TABLESPACES, this parameter allows you to specify whether to encrypt newly created user tablespaces. However, the TABLESPACE_ENCRYPTION parameter offers an additional benefit in Data Guard environments. In previous releases, tablespaces in Data Guard environments were required to use the same encryption policy on the primary and standby databases. For example, if all tablespaces were encrypted on the primary database, then all tablespaces were required to be encrypted on the standby database. The TABLESPACE_ENCRYPTION parameter eliminates this requirement and allows you to use different tablespace encryption policies on primary and standby databases. See *Oracle Database Advanced Security Guide* for more information.

If the behavior specified by the ENCRYPT_NEW_TABLESPACES setting conflicts with the behavior specified by the TABLESPACE_ENCRYPTION setting, then the TABLESPACE_ENCRYPTION behavior takes precedence.

Values:

- AUTO_ENABLE

  Use this setting if you would like to encrypt all tablespaces in the database.

  All newly created tablespaces will be encrypted. In the CREATE TABLESPACE statement, if you specify the DECRYPT clause, it will be ignored and the tablespace will be encrypted. If you specify the ENCRYPTION USING *algorithm* ENCRYPT clause, the specified algorithm will be used to encrypt the tablespace. If you specify the ENCRYPTION ENCRYPT clause and do not specify an algorithm, the tablespace will be encrypted with the algorithm specified by the TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM parameter.

  If an existing tablespace is unencrypted, the database writes a warning to the alert log. See *Oracle Database Advanced Security Guide* for information about encrypting existing tablespaces.

  If you attempt to decrypt an existing encrypted tablespace, an error will occur.

  This is the default setting for Cloud databases. Moreover, because all tablespaces must be encrypted in the Cloud, setting this parameter to MANUAL_ENABLE or DECRYPT_ONLY for a Cloud database will be ignored and the Cloud database will behave as if the setting is AUTO_ENABLE.

- MANUAL_ENABLE

  Use this setting if you would like to manually control which tablespaces are encrypted.

  To encrypt a tablespace, specify the ENCRYPTION ... ENCRYPT clause in the CREATE TABLESPACE statement. If you specify the ENCRYPTION USING *algorithm* ENCRYPT clause, the specified algorithm will be used to encrypt the tablespace. If you specify the ENCRYPTION ENCRYPT clause and do not specify an algorithm, the tablespace will be encrypted with the algorithm specified by the TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM parameter.

This is the default setting for on-premises databases. This setting is ignored for Cloud databases.

- `DECRYPT_ONLY`

  Use this setting if you do not want any encrypted tablespaces in the database.

  All newly created tablespaces must be unencrypted. If you specify the `ENCRYPT` clause in the `CREATE TABLESPACE` statement, an error will occur.

  If an existing tablespace is encrypted, the database writes a warning to the alert log. See *Oracle Database Advanced Security Guide* for information about decrypting existing tablespaces.

  If you attempt to encrypt an existing unencrypted tablespace, an error will occur.

  This setting is valid only for on-premises databases. This setting is ignored for Cloud databases.

> **See Also:**
>
> "ENCRYPT_NEW_TABLESPACES"

2.392 TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM

`TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM` specifies the default algorithm the database uses when encrypting a tablespace.

Property	Description
Parameter type	String
Syntax	`TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM = { AES128 | AES192 | AES256 | ARIA128 | ARIA192 | ARIA256 | 3DES168 }` **Note:** `3DES168` must be enclosed in single quotation marks when specified in the `ALTER SYSTEM` command.
Default value	`AES256`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	The same value should be specified for all instances.

The value of this initialization parameter determines the algorithm the database uses if an encryption algorithm is not specified when creating an encrypted tablespace or when encrypting an existing tablespace. For example, the value of this parameter takes effect when:

- You create a tablespace with the `CREATE TABLESPACE` statement and you specify the `ENCRYPTION … ENCRYPT` clause, but you do not specify the `USING` keyword and an algorithm.
- You create a tablespace with the `CREATE TABLESPACE` statement and you do not specify the `ENCRYPTION … ENCRYPT` clause. However, the value of the `ENCRYPT_NEW_TABLESPACES` initialization parameter instructs the database to encrypt the tablespace.

- You encrypt an existing tablespace with the `ALTER TABLESPACE` statement, either by specifying the `ENCRYPTION OFFLINE ENCRYPT` clause or the `ENCRYPTION ONLINE … ENCRYPT` clause, and you do not specify the `USING` keyword and an algorithm.

> **Note:**
>
> GOST 28147-89 has been deprecated by the Russian government, and SEED has been deprecated by the South Korean government. If you need South Korean government-approved TDE cryptography, then use ARIA instead. If you are using GOST 28147-89, then you must decrypt and encrypt with another supported TDE algorithm. The decryption algorithms for GOST 28147-89 and SEED are included in Oracle Database 23ai, but are deprecated, and the GOST encryption algorithm is desupported with Oracle Database 23ai. If you are using GOST or SEED for TDE encryption, then Oracle recommends that you decrypt and encrypt with another algorithm before upgrading to Oracle Database 23ai. However, with the exception of the HP Itanium platform, the GOST and SEED decryption libraries are available with Oracle Database 23ai, so you can also decrypt after upgrading.

> **See Also:**
>
> - "ENCRYPT_NEW_TABLESPACES"
> - *Oracle Database SQL Language Reference* for more information about the `CREATE TABLESPACE` statement
> - *Oracle Database SQL Language Reference* for more information about the `ALTER TABLESPACE` statement

2.393 TAPE_ASYNCH_IO

`TAPE_ASYNCH_IO` controls whether I/O to sequential devices (for example, backup or restore of Oracle data to or from tape) is asynchronous—that is, whether parallel server processes can overlap I/O requests with CPU processing during table scans.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No

If your platform supports asynchronous I/O to sequential devices, Oracle recommends that you leave this parameter set to its default. However, if the asynchronous I/O implementation is not stable, you can set `TAPE_ASYNCH_IO` to `false` to disable

asynchronous I/O. If your platform does not support asynchronous I/O to sequential devices, this parameter has no effect.

> **See Also:**
>
> *Oracle Database VLDB and Partitioning Guide* for more information about this parameter

2.394 TDE_CONFIGURATION

Use `TDE_CONFIGURATION` to set the type of keystore that is used for Transparent Data Encryption (TDE) by the root container; united PDBs inherit the value from the root container, isolated PDBs can be set individually.

Before Oracle Database 18c, each PDB stored its separate encryption keys in the CDB's keystore (united mode). Starting with Oracle Database 18c Cloud environments, a PDB can optionally store its encryption keys in a separate keystore (isolated mode), thus allowing protection by a separate keystore password. Starting with Oracle Database 19c, version 19.14, isolated mode is available for all Oracle database deployments, including on-premises databases, legacy deployments, and engineered systems.

The `WALLET_ROOT` initialization parameter must be set in order for `TDE_CONFIGURATION` to take effect.

Property	Description
Parameter type	String
Syntax	`TDE_CONFIGURATION = "{ KEYSTORE_CONFIGURATION = value [; CONTAINER = pdb-name] }"`

Syntax	**value ::=**
	`{`
	`FILE |`
	`OKV |`
	`HSM |`
	`FILE|OKV |`
	`FILE|HSM |`
	`OKV|FILE |`
	`HSM|FILE`
	`}`
	Notes:
	• The `KEYSTORE_CONFIGURATION` value is case-insensitive. For example, you can specify `FILE` or `file`.
	• `FILE|OKV`, `FILE|HSM`, `OKV|FILE`, and `HSM|FILE` are values. The vertical bars they contain are not separators in the syntax shown above.

Default value	None
Modifiable	`ALTER SYSTEM`[1]
Modifiable in a PDB	Yes
Basic	No

Property	Description
Oracle RAC	The same value must be specified on all instances using the `ALTER SYSTEM SET TDE_CONFIGURATION="KEYSTORE_CONFIGURATION=value" SCOPE=BOTH SID='*';` statement.

[1] In some cases, when this parameter is set using `ALTER SYSTEM SCOPE=SPFILE`, the `SHOW PARAMETER TDE_CONFIGURATION` statement does not show the correct value. However, the value set for `TDE_CONFIGURATION` can be derived from information shown in the `V$ENCRYPTION_WALLET` view.

The following attributes can be specified:

- `KEYSTORE_CONFIGURATION` attribute. This attribute is required. The value specified with this attribute configures the keystore type for the specified PDB. The following values can be specified for this attribute:
  - `FILE`: This value configures a wallet keystore.
  - `OKV`: This value configures the database to use Oracle Key Vault (OKV) for TDE key management.

    This value is also used to disable an auto-login OKV configuration and cause any existing `cwallet.sso` files, containing the credentials to the OKV server as the `OKV_PASSWORD` client secret, to be ignored.
  - `HSM`: This value configures a hardware security module (HSM).

    Oracle does not support the use of HSMs for TDE key management. For more information, see My Oracle Support note 2310066.1 "Oracle TDE Support With 3rd Party HSM Vendors" at the following URL: https://support.oracle.com/rs?type=doc&id=2310066.1
  - `FILE|OKV`: This value configures a reverse migration from OKV to a wallet keystore.
  - `FILE|HSM`: This value configures a reverse migration from a HSM to a wallet keystore.
  - `OKV|FILE`: This value configures a migration from a wallet to OKV.

    This value is also used in an auto-login OKV configuration, because in this configuration a `cwallet.sso` file, containing the `OKV_PASSWORD` client secret, must be used by the Oracle server to obtain the credentials to log in to the OKV server.
  - `HSM|FILE`: This value configures a migration from a wallet to a HSM.

    Oracle does not support the use of HSMs for TDE key management. For more information, see My Oracle Support note 2310066.1 "Oracle TDE Support With 3rd Party HSM Vendors" at the following URL: https://support.oracle.com/rs?type=doc&id=2310066.1

  Some of the `KEYSTORE_CONFIGURATION` attribute values consist of a single word, for example, the `FILE`, `OKV`, and `HSM` values. The other `KEYSTORE_CONFIGURATION` attribute values consist of two words separated by the "|" character that is a required part of the value's syntax, for example, the `FILE|OKV`, `FILE|HSM`, `OKV|FILE`, and `HSM|FILE` values.

- `CONTAINER` attribute: This optional attribute can be used only when setting the parameter in the `CDB$ROOT` of a CDB. The `CONTAINER` attribute can be specified only when the `CDB$ROOT` is in `MOUNTED` state. With this attribute, you must specify the name of the PDB for which you are setting the parameter. When you specify the `CONTAINER` attribute, you must use a semicolon ";" as the separation character between the `KEYSTORE_CONFIGURATION` and `CONTAINER` attributes.

Examples

The following statement configures a wallet keystore for the open PDB from which the statement is issued:

```
ALTER SYSTEM SET TDE_CONFIGURATION="KEYSTORE_CONFIGURATION=FILE" SCOPE=BOTH SID='*';
```

The following statement configures an OKV keystore for the PDB in `MOUNTED` state from which the statement is issued:

```
ALTER SYSTEM SET TDE_CONFIGURATION="KEYSTORE_CONFIGURATION=OKV" SCOPE=SPFILE SID='*';
```

The following statement configures an isolated standby PDB for an auto-open Oracle Key Vault setup; standby PDBs are `MOUNTED`, so the command must be executed in the standby root CDB:

```
ALTER SYSTEM SET TDE_CONFIGURATION="KEYSTORE_CONFIGURATION=OKV|FILE;
CONTAINER=FINANCIALS" SCOPE=both SID='*';
```

See Also:

- WALLET_ROOT
- V$ENCRYPTION_WALLET
- *Oracle Database Advanced Security Guide* for information about managing keystores and encryption keys in united mode
- *Oracle Database Advanced Security Guide* for information about managing keystores and encryption keys in isolated mode

2.395 TDE_KEY_CACHE

Use `TDE_KEY_CACHE` to enable or disable sharing of Transparent Data Encryption (TDE) master encryption keys across Oracle processes.

Note:

This parameter is available only for databases in Oracle Cloud Infrastructure (OCI) that use the OCI Key Management Service (KMS) for TDE key management.

Property	Description
Parameter type	Boolean

Property	Description
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No
Oracle RAC	The same value must be used on all instances.

Values:

- `true`

  Enables sharing of TDE master encryption keys across Oracle processes

- `false`

  Disables sharing of TDE master encryption keys across Oracle processes

> **See Also:**
>
> - *Oracle Database Advanced Security Guide* for more information about setting the TDE master encryption key in a hardware keystore in united mode
> - *Oracle Database Advanced Security Guide* for more information about setting the TDE master encryption key in a hardware keystore in isolated mode

2.396 TEMP_UNDO_ENABLED

`TEMP_UNDO_ENABLED` determines whether transactions within a particular session can have a temporary undo log.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true	false`
Basic	No
Oracle RAC	Each session of each instance can have its own value or not set any value at all

The default choice for database transactions has been to have a single undo log per transaction. This parameter, at the session level / system level scope, lets a

transaction split its undo log into temporary undo log (for changes on temporary objects) and permanent undo log (for changes on persistent objects).

By splitting the undo stream of a transaction into two streams (temporary and permanent), a database can provide separate storage and retention model for these. This results in overall reduction in the size of undo log and redo log in the database

If database applications make use of temporary objects (using global temporary tables or temporary table transformations), it is advisable to set this parameter's value to `true`.

When `TEMP_UNDO_ENABLED` is set to `true` and the COMPATIBLE initialization parameter is set to `12.0.0`, this feature is enabled. The temporary undo feature is enabled for the session in which it is set. Setting it across the system will affect all existing and upcoming sessions. If the value is set in the `init.ora` file, all upcoming sessions will inherit this value unless overwritten by an explicit ALTER SESSION or ALTER SYSTEM statement. All undo for operations on temporary objects is deemed temporary.

If `TEMP_UNDO_ENABLED` is not set to `true`, existing applications that make use of temporary objects run as is without any change.

Once the value of the parameter is set, it cannot be changed for the lifetime of the session. If the session has temporary objects using temporary undo, the parameter cannot be disabled for the session. Similarly, if the session already has temporary objects using regular undo, setting this parameter will have no effect.

This parameter is only applicable for the primary database. For a standby database, this parameter is ignored because temporary undo is enabled by default on the standby database.

> **See Also:**
>
> *Oracle Database Administrator's Guide* for information on managing temporary undo

2.397 THREAD

`THREAD` has been superseded by the `INSTANCE_NAME` and `INSTANCE_NUMBER` parameters, and will be made obsolete in a future release of the Oracle Database.

Property	Description
Parameter type	Integer
Default value	`0`
Modifiable	No
Modifiable in a PDB	No
Range of values	0 to the maximum number of enabled threads
Basic	No
Oracle RAC	If specified, multiple instances must have different values.

> **See Also:**
>
> "INSTANCE_NAME" and "INSTANCE_NUMBER"

2.398 THREADED_EXECUTION

`THREADED_EXECUTION` specifies whether to enable the multithreaded Oracle model.

Property	Description
Parameter type	Boolean
Default value	On UNIX and Linux: `false` On Windows: `true`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No
Oracle RAC	If specified, all instances must use the same value

THREADED_EXECUTION on UNIX and Linux

Oracle Database 12*c* introduced the `THREADED_EXECUTION` initialization parameter for databases running on UNIX and Linux systems. On such databases, the default value for `THREADED_EXECUTION` is `false`. Setting this parameter to `true` enables the multithreaded Oracle model, which allows Oracle processes on UNIX and Linux to run as operating system threads in separate address spaces.

By default, some background processes on UNIX and Linux always use threaded execution; the remaining Oracle processes run as operating system processes. Thus, an "Oracle process" is not always equivalent to an "operating system process."

> **Note:**
>
> When `THREADED_EXECUTION` is set to `true` on databases running on UNIX and Linux systems, which enables the multithreaded Oracle model, operating system authentication is not supported. Attempts to connect to the database using operating system authentication (for example, `CONNECT / AS SYSDBA` or `CONNECT /`) when this initialization parameter is set to `true` receive an `ORA-01031 "insufficient privileges"` error.
>
> The solution to this error is to always use the password when connecting to the database.
>
> Also, when this initialization parameter is set to `true` on databases running on UNIX and Linux systems, the `DEDICATED_THROUGH_BROKER_listener-name=ON` parameter should be added to the listener.ora file, where *`listener-name`* is the name of the Oracle Net listener and the `LOCAL_LISTENER` initialization parameter should be set to a TNS name entry corresponding to your instance service. This enables the server to spawn threads when connections to the database are requested through the listener.

THREADED_EXECUTION on Windows

Starting with Oracle Database 21c, the `THREADED_EXECUTION` initialization parameter is supported for databases running on Microsoft Windows. On such databases, this parameter must remain set to its default value of `true`; setting this parameter to `false` on databases running on Windows is not supported. The introduction of this parameter does not change the threading model for Oracle database on Windows. As in previous releases, an Oracle Database server instance on Windows is a service with a single multi-threaded operating system process. However, starting with Oracle Database 21c, you will observe changes to the `V$PROCESS` view, the dedicated connection broker, and the naming of trace files. For details about these changes, refer to *Oracle Database Administrator's Reference for Microsoft Windows*.

> **Note:**
>
> Unlike on UNIX and Linux systems, when `THREADED_EXECUTION` is set to `true` on Windows, operating system authentication is supported.

See Also:

- *Oracle Database Concepts* for more information about multithreaded Oracle
- Table F-1 for more information about background processes that run as threads instead of as operating system processes when multithreaded Oracle is enabled
- *Oracle Database Net Services Reference* for more information about the `DEDICATED_THROUGH_BROKER_`*listener-name* parameter in the listener.ora file
- *Oracle Database Net Services Administrator's Guide* for an overview of Oracle Net listener

2.399 TIME_AT_DBTIMEZONE

`TIME_AT_DBTIMEZONE` specifies whether time-dependent database operations use the time zone of the database host system or the time zone of the PDB.

Some examples of time-dependent database operations are running the SQL functions `SYSDATE` and `SYSTIMESTAMP`, querying table columns of type `DATE` or `TIMESTAMP`, using Oracle Job scheduler, performing materialized view refresh, and using Oracle Flashback Technology.

Property	Description
Parameter type	String
Syntax	`TIME_AT_DBTIMEZONE = { OFF | USER_SQL | DATABASE }`
Default value	`OFF`
Modifiable	No
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Multiple instances must use the same value.

Values:

- `OFF` - For all time-dependent operations, the database uses the time zone of the database host system that was in effect when the database was started. This is the behavior in releases prior to Oracle Database 23ai.
- `USER_SQL` - The SQL functions `SYSDATE` and `SYSTIMESTAMP` return the date and time based on the `DBTIMEZONE` setting for the PDB. For all other time-dependent operations, the database uses the time zone of the database host system that was in effect when the database was started.
- `DATABASE` - For all time-dependent operations, the database uses the time zone specified by the `DBTIMEZONE` setting for the PDB.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

> **See Also:**
>
> - *Oracle Database SQL Language Reference* for information about the `SYSDATE` function
> - *Oracle Database SQL Language Reference* for information about the `SYSTIMESTAMP` function

2.400 TIMED_OS_STATISTICS

`TIMED_OS_STATISTICS` specifies (in seconds) the interval at which Oracle collects operating system statistics when a request is made from the client to the server or when a request completes.

Property	Description
Parameter type	Integer
Default value	If `STATISTICS_LEVEL` is set to `ALL`, then `60` If `STATISTICS_LEVEL` is set to `BASIC` or `TYPICAL`, then `0`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	Unlimited
Basic	No

On dedicated servers, Oracle collects operating system statistics at user logon and after each subsequent client invocation through the OCI into the Oracle server as a remote procedure call message.

On shared servers, Oracle collects statistics when client calls to Oracle are processed.

A value of zero specifies that operating system statistics are not gathered. To collect statistics, set a value meaningful for your application and site needs.

> **Note:**
>
> Gathering operating system statistics is very expensive. Oracle recommends that you set this parameter in an `ALTER SYSTEM` statement rather than in the initialization parameter file, and that you reset the value to zero as soon as the needed statistics have been gathered.

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this parameter

2.401 TIMED_STATISTICS

`TIMED_STATISTICS` specifies whether statistics related to time are collected.

Property	Description
Parameter type	Boolean
Default value	If `STATISTICS_LEVEL` is set to `TYPICAL` or `ALL`, then `true` If `STATISTICS_LEVEL` is set to `BASIC`, then `false`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true | false`
Basic	No

Values

- `true`

  The statistics are collected and stored in trace files or displayed in the `V$SESSTATS` and `V$SYSSTATS` dynamic performance views.

- `false`

  The value of all time-related statistics is set to zero. This setting lets Oracle avoid the overhead of requesting the time from the operating system.

Starting with release 11.1.0.7.0, the value of the `TIMED_STATISTICS` parameter cannot be set to `false` if the value of `STATISTICS_LEVEL` is set to `TYPICAL` or `ALL`.

On some systems with very fast timer access, Oracle might enable timing even if this parameter is set to `false`. On these systems, setting the parameter to `true` can sometimes produce more accurate statistics for long-running operations.

> **See Also:**
>
> - *Oracle Database SQL Tuning Guide* for more information on setting this parameter
> - Statistics Descriptions indicates which statistics depend on the setting of this parameter.

2.402 TIMEZONE_VERSION_UPGRADE_ONLINE

`TIMEZONE_VERSION_UPGRADE_ONLINE` enables you to keep the database running in normal mode while upgrading time zone data using the `DBMS_DST` package.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`true | false`
Basic	No
Oracle RAC	Multiple instances must have the same value.

In releases prior to Oracle Database 21c, you were required to put the database in `UPGRADE` mode in order to initiate a time zone data upgrade using the `DBMS_DST` package. Starting with Oracle Database 21c, you can perform such an upgrade while the database is in normal mode by setting the value of `TIMEZONE_VERSION_UPGRADE_ONLINE` to `true`.

> **Note:**
>
> Setting the value of this parameter is only one step in a series of steps for upgrading your time zone data. Refer to *Oracle Database Globalization Support Guide* for the complete set of steps before you set this parameter value.

2.403 TRACE_ENABLED

`TRACE_ENABLED` controls tracing of the execution history, or code path, of Oracle. Oracle Support Services uses this information for debugging.

Property	Description
Parameter type	Boolean
Default value	`true`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No
Oracle RAC	The default value is `TRUE`. Oracle recommends that multiple instances have the same value.

When `TRACE_ENABLED` is set to `true`, Oracle records information in specific files when errors occur.

Oracle records this information for all instances, even if only one instance terminates. This allows Oracle to retain diagnostics for an entire cluster.

Although the overhead incurred from this processing is not excessive, you can improve performance by setting `TRACE_ENABLED` to `false`. You might do this, for example, to meet high-end benchmark requirements. However, if you leave this parameter set to `false`, you may lose valuable diagnostic information. Therefore, always set `TRACE_ENABLED` to `true` to trace system problems and to reduce diagnostic efforts when unexplained instance failures occur.

2.404 TRACEFILE_IDENTIFIER

`TRACEFILE_IDENTIFIER` specifies a custom identifier that becomes part of the Oracle Trace file name. Such a custom identifier is used to identify a trace file simply from its name and without having to open it or view its contents.

Property	Description
Parameter type	String
Syntax	`TRACEFILE_IDENTIFIER = "`*`traceid`*`"`
Default value	There is no default value.
Modifiable	`ALTER SESSION`
Modifiable in a PDB	No
Range of values	Any characters that can occur as part of a file name on the customer platform
Basic	No

Each time this parameter is dynamically modified, the next trace dump will be written to a trace file which has the new parameter value embedded in its name. Trace file continuity information is automatically added to both the old and new trace files to indicate that these trace files belong to the same process.

This parameter can only be used to change the name of the foreground process' trace file; the background processes continue to have their trace files named in the regular format. For foreground processes, the `TRACEID` column of the `V$PROCESS` view contains the current value of the `TRACEFILE_IDENTIFIER` parameter. When this parameter value is set, the trace file name has the following format:

`sid``_ora_`*`pid`*`_`*`traceid`*`.trc`

In this example, *`sid`* is the Oracle instance ID, *`pid`* is the process ID, and *`traceid`* is the value of the `TRACEFILE_IDENTIFIER` parameter.

See Also:

- *Oracle Database SQL Tuning Guide* for more information about this parameter
- This parameter is not supported on all operating systems. See your operating system-specific Oracle documentation for more information.

2.405 TRANSACTION_RECOVERY

`TRANSACTION_RECOVERY` specifies whether transaction recovery is enabled or disabled for a PDB.

Transaction recovery refers to the series of steps that the database performs in the event of a crash (either an instance crash or a transaction crash) to roll back uncommitted transactions.

Property	Description
Parameter type	String
Syntax	`TRANSACTION_RECOVERY = { ENABLED | DISABLED }`
Default value	`ENABLED`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Multiple instances must use the same value.

Values:

- `ENABLED` - Transaction recovery is enabled for a PDB.
- `DISABLED` - Transaction recovery is disabled for a PDB.

During normal operation, the value of this parameter is set to `ENABLED` by the database and this setting should not be modified by a DBA. However, there are two circumstances under which it is permissible for a DBA to modify the value of this parameter:

- A quarantined transaction is a transaction that is isolated and for which transaction recovery will not be attempted while the quarantine on it remains. It requires intervention by the DBA to first resolve the issue that caused the transaction to be quarantined, and then to drop the transaction quarantine so that transaction recovery is attempted again. If transaction recovery becomes disabled on a PDB due to an excessive number of quarantined transactions (a process known as "transaction quarantine escalation"), then the database automatically sets the value of this parameter to `DISABLED`. When this happens, the DBA should take corrective action for the quarantined transactions, then restart transaction recovery for the PDB by setting the value of this parameter to `ENABLED`. Refer to *Oracle Database Administrator's Guide* to learn about this entire process before you set this parameter.
- While working to resolve an issue, Oracle Support may instruct a DBA to temporarily disable transaction recovery by setting this parameter to `DISABLED`. After the issue has been resolved, this parameter should ultimately be set back to `ENABLED` so that normal database operation can resume.

> **Caution:**
>
> You should never set this parameter to `DISABLED` unless specifically directed to do so by Oracle Support. Setting this parameter to `DISABLED` could lead to severe problems

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

2.406 TRANSACTIONS

`TRANSACTIONS` specifies how many rollback segments to online when `UNDO_MANAGEMENT = MANUAL`.

Property	Description
Parameter type	Integer
Default value	Derived: (1.1 * `SESSIONS`)
Modifiable	No
Modifiable in a PDB	No
Range of values	4 to 2^{31} - 1
Basic	No
Oracle RAC	Multiple instances can have different values.

The maximum number of concurrent transactions is now restricted by undo tablespace size (`UNDO_MANAGEMENT = AUTO`) or the number of online rollback segments (`UNDO_MANAGEMENT = MANUAL`).

2.407 TRANSACTIONS_PER_ROLLBACK_SEGMENT

`TRANSACTIONS_PER_ROLLBACK_SEGMENT` specifies the number of concurrent transactions you expect each rollback segment to have to handle.

Property	Description
Parameter type	Integer
Default value	`5`
Modifiable	No
Modifiable in a PDB	No
Range of values	1 to operating system-dependent
Basic	No
Oracle RAC	Multiple instances can have different values.

The minimum number of rollback segments acquired at startup is `TRANSACTIONS` divided by the value for this parameter. For example, if `TRANSACTIONS` is 101 and this parameter is 10, then the minimum number of rollback segments acquired would be the ratio 101/10, rounded up to 11.

You can acquire more rollback segments by naming them in the parameter `ROLLBACK_SEGMENTS`.

> **See Also:**
>
> Your operating system-specific Oracle documentation for the range of values for this parameter.

2.408 TRUE_CACHE

Use `TRUE_CACHE` to specify that an instance is a True Cache.

Property	Description
Parameter type	Boolean
Default value	`false`
Modifiable	No
Modifiable in a PDB	No
Range of values	`true | false`
Basic	No

Set this parameter to `true` on a True Cache. Otherwise, leave this parameter set to `false`.

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

> **See Also:**
>
> *Oracle True Cache User's Guide* for more information about this parameter

2.409 TXN_PRIORITY

`TXN_PRIORITY` specifies the priority for all user transactions in a session.

Property	Description
Parameter type	String
Syntax	`TXN_PRIORITY = { HIGH | MEDIUM | LOW }`
Default value	`HIGH`
Modifiable	`ALTER SESSION`
Modifiable in a PDB	No
Basic	No

The Priority Transactions feature automatically rolls back low-priority transactions that are blocking higher priority transactions from obtaining row locks.

You can use the TXN_PRIORITY parameter to assign a priority (HIGH, MEDIUM, or LOW) to all transactions in a particular user session. Priority Transactions then operates as follows for the three priorities:

- HIGH - Priority Transactions never rolls back a HIGH priority transaction in order to release a row lock for another transaction. This is the default.
- MEDIUM - Priority Transactions will roll back a MEDIUM priority transaction if it is holding a row lock required by a HIGH priority transaction, and the HIGH priority transaction has been waiting for the row lock longer than the time specified by the PRIORITY_TXNS_HIGH_WAIT_TARGET parameter.
- LOW - Priority Transactions will roll back a LOW priority transaction if it is holding a row lock required by a HIGH or MEDIUM priority transaction, and the HIGH or MEDIUM priority transaction has been waiting for the row lock longer than the time specified by the PRIORITY_TXNS_HIGH_WAIT_TARGET or PRIORITY_TXNS_MEDIUM_WAIT_TARGET parameter, respectively.

  If a LOW priority transaction is blocked waiting for a row lock, Priority Transactions will not roll back the transaction holding the row lock, regardless of its priority.

You can view the priority and maximum wait time for a transaction by querying the TXN_PRIORITY and PRIORITY_TXNS_WAIT_TARGET columns in the V$TRANSACTION view.

Note:

This parameter is available starting with Oracle Database 23ai.

See Also:

- "PRIORITY_TXNS_HIGH_WAIT_TARGET"
- "PRIORITY_TXNS_MEDIUM_WAIT_TARGET"
- "PRIORITY_TXNS_MODE"
- "V$TRANSACTION"
- *Oracle Database Administrator's Guide* for more information about Priority Transactions

2.410 UNDO_MANAGEMENT

UNDO_MANAGEMENT specifies which undo space management mode the system should use.

Property	Description
Parameter type	String

Property	Description
Syntax	`UNDO_MANAGEMENT = { MANUAL | AUTO }`
Default value	`AUTO`
Modifiable	No
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	Multiple instances must have the same value.

When `UNDO_MANAGEMENT` is set to `AUTO`, the instance starts in automatic undo management mode. In manual undo management mode, undo space is allocated externally as rollback segments.

Note:

In a CDB, the `UNDO_MANAGEMENT` initialization parameter must be set to `AUTO`, and an undo tablespace is required to be created to manage the undo data.

See Also:

- *Oracle Database Administrator's Guide* for more information about this parameter
- *Oracle Database Administrator's Guide* for more information about managing undo data

2.411 UNDO_RETENTION

`UNDO_RETENTION` specifies (in seconds) the low threshold value of undo retention.

Property	Description
Parameter type	Integer
Default value	`900`
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	`0` to 2^{31} - 1
Basic	No
Oracle RAC	Oracle recommends that multiple instances have the same value.

For both `AUTOEXTEND` undo tablespaces and fixed-size undo tablespaces, the system retains undo for at least the time specified in this parameter, and automatically tunes the undo retention period to satisfy the undo requirements of the queries.

Automatic tuning of undo retention is not supported for LOBs. The RETENTION value for LOB columns is set to the value of the UNDO_RETENTION parameter.

The UNDO_RETENTION parameter is honored only if the current undo tablespace has enough space. If an active transaction requires undo space and the undo tablespace does not have available space, then the system starts reusing unexpired undo space. This action can potentially cause some queries to fail with a "snapshot too old" message.

The amount of time for which undo is retained for the Oracle Database for the current undo tablespace can be obtained by querying the TUNED_UNDORETENTION column of the V$UNDOSTAT dynamic performance view.

Recommendations for Modifying UNDO_RETENTION

Oracle generally recommends that you leave UNDO_RETENTION set to its default value. Modifying this parameter is recommended only in the following situations:

- You may want to increase the value of UNDO_RETENTION when using flashback features, such as Oracle Flashback Query, which require undo to be retained for longer than the longest running query in the system.
- In Oracle Active Data Guard environments, you may want to increase the value of UNDO_RETENTION on the primary instance in order to accommodate undo retention requirements on the standby instances. This allows the primary instance to retain undo for a longer period of time to serve queries on the standby instances. For more information, see *Oracle Database Administrator's Guide* and *Oracle Data Guard Concepts and Administration*.

Modifying UNDO_RETENTION in a CDB

You can set the value of UNDO_RETENTION in the CDB root (CDB$ROOT) and in individual PDBs. The CDB root and PDBs can have the same value or different values. Note that you can modify this parameter in a PDB only if the PDB is in local undo mode; you cannot modify this parameter if the PDB is in shared undo mode.

Starting with Oracle Database release 19c, version 19.9, the value of UNDO_RETENTION is not inherited in a CDB. Therefore, if you change the value for UNDO_RETENTION in the CDB root, the PDBs do not inherit the new value. If you want to change the value for UNDO_RETENTION at the PDB level, you must explicitly do so. For example, if your CDB contains two PDBs (PDB1 and PDB2), you can set UNDO_RETENTION to 2000 in the CDB root and both PDBs as follows:

```
ALTER SESSION SET CONTAINER = CDB$ROOT;
ALTER SYSTEM SET UNDO_RETENTION=2000 SCOPE=BOTH;

ALTER SESSION SET CONTAINER = PDB1;
ALTER SYSTEM SET UNDO_RETENTION=2000 SCOPE=BOTH;

ALTER SESSION SET CONTAINER = PDB2;
ALTER SYSTEM SET UNDO_RETENTION=2000 SCOPE=BOTH;
```

See Also:

- *Oracle Database SQL Language Reference* for information about creating undo tablespaces
- *Oracle Database Administrator's Guide* for information about managing undo data

2.412 UNDO_TABLESPACE

`UNDO_TABLESPACE` specifies the undo tablespace to be used when an instance starts. If this parameter is specified when the instance is in manual undo management mode, then an error will occur and startup will fail.

Property	Description
Parameter type	String
Syntax	`UNDO_TABLESPACE = undoname`
Default value	The first available undo tablespace in the database.
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	Yes
Range of values	Legal name of an existing undo tablespace
Basic	Yes
Oracle RAC	Each instance must have a unique value for this parameter, when it is set.

If the `UNDO_TABLESPACE` parameter is omitted, the first available undo tablespace in the database is chosen. If no undo tablespace is available, the instance will start without an undo tablespace. In such cases, user transactions will be executed using the `SYSTEM` rollback segment. You should avoid running in this mode under normal circumstances.

You can replace an undo tablespace with another undo tablespace while the instance is running.

Note:

When you update this parameter on the primary database in an Oracle Data Guard configuration, you must also update it on all the physical standby databases in the configuration. This ensures that the standby databases can find the undo tablespace when they become the primary database.

See Also:

Oracle Database SQL Language Reference for information about creating undo tablespaces

2.413 UNIFIED_AUDIT_COMMON_SYSTEMLOG

`UNIFIED_AUDIT_COMMON_SYSTEMLOG` specifies whether key fields of unified audit records generated due to common audit policies will be written to the SYSLOG utility.

> **Note:**
>
> This initialization parameter is supported only on UNIX platforms.

Property	Description
Parameter type	String

Syntax	`UNIFIED_AUDIT_COMMON_SYSTEMLOG = '`*`facility_clause.priority_clause`*`'`
	`facility_clause``::=`
	`{ USER | LOCAL[ 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 ] }`
	`priority_clause``::=`
	`{ NOTICE | INFO | DEBUG | WARNING | ERR | CRIT | ALERT | EMERG }`

Default value	None
Modifiable	No
Modifiable in a PDB	No
Basic	No
Oracle RAC	The same value must be used on all instances.

When this parameter is set, key fields of unified audit records generated due to common audit policies are written to SYSLOG. These fields uniquely identify the detailed unified audit records in the `UNIFIED_AUDIT_TRAIL` view. Only a subset of unified audit record fields are written to ensure that the audit record entries do not exceed the maximum allowed size for a SYSLOG entry (typically 1024 bytes).

Do not set this parameter if you do not want key fields of unified audit records generated due to common audit policies written to SYSLOG.

This parameter differs from the `UNIFIED_AUDIT_SYSTEMLOG` parameter in that it is set at the CDB level and enables all unified audit records from common unified audit policies to be consolidated into a single destination, whereas `UNIFIED_AUDIT_SYSTEMLOG` is set at the PDB level and enables the logging of unified audit records on a per-PDB basis.

See Also:

- "UNIFIED_AUDIT_SYSTEMLOG"
- "UNIFIED_AUDIT_TRAIL"
- *Oracle Database Security Guide* for a table that maps the names given to the unified audit records fields that are written to SYSLOG to the corresponding column names in the `UNIFIED_AUDIT_TRAIL` view

2.414 UNIFIED_AUDIT_SYSTEMLOG

`UNIFIED_AUDIT_SYSTEMLOG` specifies whether key fields of unified audit records will be written to the SYSLOG utility (on UNIX platforms) or to the Windows Event Viewer (on Windows). In a CDB, this parameter is a per-PDB static initialization parameter.

Property	Description
Parameter type	String for UNIX platforms, Boolean for Windows

Syntax	**On UNIX:**
	`UNIFIED_AUDIT_SYSTEMLOG = '`*`facility_clause.priority_clause`*`'`
	`facility_clause``::=`
	`{ USER | LOCAL[ 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 ] }`
	`priority_clause``::=`
	`{ NOTICE | INFO | DEBUG | WARNING | ERR | CRIT | ALERT | EMERG }`
	On Windows:
	`UNIFIED_AUDIT_SYSTEMLOG = { FALSE | TRUE }`

Default value	No default on UNIX platforms `FALSE` on Windows
Modifiable	No
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	The same value must be used on all instances.

When this parameter is set on UNIX, key fields of unified audit records are written to SYSLOG. When this parameter is set on Windows, key fields of unified audit records are written to the Windows Event Viewer.

Do not set this parameter (or set it to `FALSE` on Windows) if you do not want key fields of unified audit records written to SYSLOG or the Windows Event Viewer.

When `UNIFIED_AUDIT_SYSTEMLOG` is enabled, the key fields of the unified audit records that are written to SYSLOG or Windows Event Viewer uniquely identify the detailed unified audit records in the `UNIFIED_AUDIT_TRAIL` view. Only a subset of the unified audit record fields are written to ensure that the audit record entries do not exceed the maximum allowed size for a SYSLOG entry (typically 1024 bytes).

This parameter differs from the `UNIFIED_AUDIT_COMMON_SYSTEMLOG` parameter in that it is set at the PDB level and enables the logging of unified audit records on a per-PDB basis,

whereas UNIFIED_AUDIT_COMMON_SYSTEMLOG is set at the CDB level and enables all unified audit records from common unified audit policies to be consolidated into a single destination.

See Also:

- "UNIFIED_AUDIT_COMMON_SYSTEMLOG"
- "UNIFIED_AUDIT_TRAIL"
- *Oracle Database Security Guide* for a table that maps the names given to the unified audit records fields that are written to SYSLOG and the Windows Event Viewer to the corresponding column names in the UNIFIED_AUDIT_TRAIL view

2.415 UNIFORM_LOG_TIMESTAMP_FORMAT

UNIFORM_LOG_TIMESTAMP_FORMAT specifies that a uniform timestamp format be used in Oracle Database trace (.trc) files and log files (such as the alert log).

Property	Description
Parameter type	Boolean
Default value	true
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Range of values	true | false
Basic	No
Oracle RAC	Multiple instances should use the same value.

When the value of UNIFORM_LOG_TIMESTAMP_FORMAT is TRUE, the format used for timestamps in trace files is standardized on universal time with millisecond precision. For example:

```
2012-09-26 00:16:47.154
```

When the value of UNIFORM_LOG_TIMESTAMP_FORMAT is FALSE, trace files include a mix of timestamps using different precisions, with some timestamps showing local time and other timestamps showing universal time.

2.416 USE_DEDICATED_BROKER

USE_DEDICATED_BROKER determines how dedicated servers are spawned.

> **Note:**
>
> Starting with Oracle Database 23ai, the type for this parameter is changed from Boolean to String, the NONE and CDB values are introduced, and the default value is changed from FALSE to NONE. However, there is no change to the functionality of this parameter, because the NONE value is equivalent to FALSE, and the CDB value is equivalent to TRUE.

Property	Description
Parameter type	String
Syntax	USE_DEDICATED_BROKER = { NONE | FALSE | CDB | TRUE }
Default value	NONE unless multithreaded Oracle is enabled[1]
Modifiable	ALTER SYSTEM
Modifiable in a PDB	No
Basic	No
Oracle RAC	If specified, all instances must use the same value

[1] Multithreaded Oracle is enabled by setting the THREADED_EXECUTION initialization parameter to TRUE.

When this parameter is set to NONE or FALSE, the listener spawns a dedicated server directly.

When this parameter is set to CDB or TRUE, the listener hands the connection to a dedicated connection broker that spawns the dedicated server. Unlike the listener, the dedicated connection broker is a database process, and hence it can implement policies leveraging database information before the spawn.

To enable the dedicated connection broker using the USE_DEDICATED_BROKER initialization parameter, you must:

1. Set the USE_DEDICATED_BROKER initialization parameter to TRUE.
2. Set the DEDICATED_THROUGH_BROKER_*listener-name* parameter to on in the listener.ora file.

Performing these two steps configures the Connection Broker Process (N*nnn*).

> **Note:**
>
> When multithreaded Oracle is enabled, the dedicated connection broker process is also enabled and used.

Configuration of the brokers is controlled by the CONNECTION_BROKERS initialization parameter.

> **See Also:**
>
> - "CONNECTION_BROKERS" for more information about configuring brokers
> - Table F-1 for more information about the Connection Broker Process (N*nnn*)
> - "THREADED_EXECUTION" for more information about enabling multithreaded Oracle
> - *Oracle Database Net Services Reference* for more information about the `DEDICATED_THROUGH_BROKER_`*listener-name* parameter in the listener.ora file

2.417 USE_LARGE_PAGES

`USE_LARGE_PAGES` is used to manage the database's use of large pages for SGA memory.

> **Note:**
>
> This parameter is applicable only on the Linux operating system. However, setting this parameter to `FALSE` can cause performance degradation on any platform.

Property	Description
Parameter type	String
Syntax	`USE_LARGE_PAGES = { TRUE | FALSE | AUTO | ONLY | AUTO_ONLY }`
Default value	`ONLY` for Exadata Database Service in the cloud and Base Database Service in the cloud `AUTO_ONLY` for on-premises Exadata systems running Oracle Database 19c or later `TRUE` for all other systems
Modifiable	No
Modifiable in a PDB	No
Basic	No
Oracle RAC	Multiple instances can use different values

This parameter does not affect process-private memory allocations.

Values

These values can be specified for `USE_LARGE_PAGES`:

- `TRUE`

Specifies that the instance can use large pages if large pages are configured on the system.

In Oracle Database 11*g* Release 2 (11.2.0.2), if there are not enough large pages configured on the system, then regular sized pages will be used to allocate SGA memory. This can cause the free large pages to go unused, and the operating system can allocate a huge amount of memory to create page tables to map SGA into physical pages for the Oracle processes. This may lead to `ORA-04030` errors and severe performance degradation on an instance.

In Oracle Database 11*g* Release 2 (11.2.0.3) and later releases, Oracle allocates as much of the SGA as it can in large pages, and if it runs out, it will allocate the rest of the SGA using regular sized pages. This can cause the instance to create additional shared memory segments for the SGA, but the total SGA size will be unchanged. In this supported mixed page mode allocation, the database will exhaust the available large pages before switching to regular sized pages.

- `FALSE`

  Specifies that the instance will not use large pages. This setting is not recommended because it can cause severe performance degradation for the instance. Although the `USE_LARGE_PAGES` initialization parameter applies only to Linux systems, setting this parameter to `FALSE` can cause performance degradation on any platform.

- `AUTO`

  Specifies that, during startup, the instance will calculate and request the number of large pages it requires. If the operating system cannot fulfill this request, then the instance will start with a combination of large and regular pages.

- `ONLY`

  Specifies that the instance will fail to start if large pages cannot be used for the entire SGA memory. Oracle recommends this setting for consistent performance. This setting is the default setting for Exadata Database Service in the cloud and Base Database Service in the cloud.

- `AUTO_ONLY`

  Specifies that, during startup, the instance will calculate and request the number of large pages it requires. If the operating system can fulfill this request, then the instance will start successfully. If the operating system cannot fulfill this request, then the instance will fail to start. This ensures that no instances will run with under-provisioned large pages. This setting is available starting with Oracle Database 19c and it is the default setting for on-premises Exadata systems.

> **Note:**
>
> `USE_LARGE_PAGES` is set to `FALSE` automatically in an Oracle ASM instance when `MEMORY_TARGET` is enabled. In this case, the `FALSE` setting does not cause performance degradation.

2.418 USER_DUMP_DEST

`USER_DUMP_DEST` specifies the pathname for a directory where the server will write debugging trace files on behalf of a user process.

Property	Description
Parameter type	String
Syntax	`USER_DUMP_DEST = { pathname | directory }`
Default value	Operating system-dependent
Modifiable	`ALTER SYSTEM`
Modifiable in a PDB	No
Range of values	Any valid local path, directory, or disk
Basic	No

Note:

The `USER_DUMP_DEST` initialization parameter is deprecated.

For example, this directory might be set as follows:

- On MS-DOS: `C:\ORACLE\UTRC`
- On UNIX: `/oracle/utrc`
- On VMS: `DISK$UR3:[ORACLE.UTRC]`

Note:

This parameter is ignored by the diagnosability infrastructure introduced in Oracle Database 11g Release 1 (11.1), which places trace and core files in a location controlled by the `DIAGNOSTIC_DEST` initialization parameter.

See Also:

- *Oracle Database SQL Tuning Guide* for more information about the use of trace files
- Your operating system-specific Oracle documentation for the range of values

2.419 WALLET_ROOT

`WALLET_ROOT` specifies the path to the root of a directory tree containing a subdirectory for each pluggable database (PDB).

Property	Description
Parameter type	String

Property	Description
Syntax	`WALLET_ROOT = wallet-root-directory-path`
Default value	There is no default value.
Modifiable	No
Modifiable in a PDB	No
Basic	No
Oracle RAC	Multiple instances must have the same value.

The name of the various wallet files is always the same, regardless of the component they are associated with. The wallets for each component are stored under each PDB GUID directory within the `WALLET_ROOT` directory structure in a directory whose name is based on the component name. For example, for the TDE component, the subdirectory name is `tde`.

The `TDE_CONFIGURATION` initialization parameter cannot be set unless the `WALLET_ROOT` parameter is also set.

For example, the contents of the directory at the location specified by the `WALLET_ROOT` initialization parameter could look as follows, where *wallet-root* is the directory specified by the `WALLET_ROOT` parameter:

```
wallet-root/eus/ewallet.p12
wallet-root/tde/ewallet.p12
wallet-root/tde/ewallet_2016120918333644.p12
wallet-root/tde_seps/cwallet.sso
wallet-root/tls/ewallet.p12
wallet-root/xdb_wallet/ewallet.p12
wallet-root/3FD1C95B48205D0FE053C5A0E40AEF8C/tde/ewallet.p12
wallet-root/3FD1C95B48205D0FE053C5A0E40AEF8C/tde/ewallet_2016110918331622.p12
wallet-root/3FD1C95B48205D0FE053C5A0E40AEF8C/tde/ewallet_2016110918332363.p12
wallet-root/3FD1C95B48205D0FE053C5A0E40AEF8C/tde_seps/cwallet.sso
wallet-root/3FD1C95B48205D0FE053C5A0E40AEF8C/tls/cwallet.sso
wallet-root/3FD1C95B48205D0FE053C5A0E40AEF8C/tls/ewallet.p12
```

When the `WALLET_ROOT` parameter is set, you can omit the path from some `ADMINISTER KEY MANAGEMENT` commands.

The `WALLET_ROOT` value can include references to environment variables. The following example shows how to use `WALLET_ROOT` when multiple TDE-enabled databases are installed into the same `ORACLE_HOME`:

```
WALLET_ROOT=/etc/ORACLE/KEYSTORES/$ORACLE_SID
```

The `ORACLE_SID` environment variable (or the `DB_UNIQUE_NAME` environment variable for Oracle RAC) makes sure that each database that is installed into the same `ORACLE_HOME` has its own set of wallets and TDE keys. This sets the root of the wallet directory hierarchy to the directory specified by `wallet-root-directory-path`.

Note:

The normalized length of the `wallet-root-directory-name` that is specified with the `WALLET_ROOT` parameter cannot exceed 255 characters, otherwise one of the following sets of error messages is displayed:

```
ORA-46693: The WALLET_ROOT location is missing or invalid.
ORA-32021: parameter value longer than 255 characters
ORA-01078: failure in processing system parameters
```

```
ORA-46693: The WALLET_ROOT location is missing or invalid.
ORA-07204: sltln: name translation failed due to lack of
output buffer space.
ORA-01078: failure in processing system parameters
```

The normalized length includes the length of expanded environment variables specified with the `WALLET_ROOT` parameter. The values of the environment variables of the user who starts the instance are used in the normalization of the `WALLET_ROOT` parameter.

The `SHOW PARAMETER WALLET_ROOT` command always displays the normalized value (with all the environment variables expanded).

For non-ASM file systems, the PDB GUID-extended paths for the TDE component are created automatically under the directory specified by the `WALLET_ROOT` parameter when any Transparent Data Encryption (TDE) wallet is created for a PDB.

Enabling Automatic Creation of Directories Under WALLET_ROOT

By using the specific configuration of `WALLET_ROOT` described in each of the following sub-sections, Oracle Database can be configured to automatically create the necessary *pdb-guid* and *component name* directories under the `WALLET_ROOT` directory path. Other settings of `WALLET_ROOT` are allowed, but would not result in the automatic creation of the necessary sub-directories by the ASM OMF layer.

Required setting to enable auto-directory creation for a database not using Oracle ASM

For a database not using Oracle ASM filesystems, the `WALLET_ROOT` parameter needs to be set as follows:

```
WALLET_ROOT=wallet-root-directory-path
```

This sets the root of the wallet directory hierarchy to the directory specified by `wallet-root-directory-path`. For example:

```
/etc/ORACLE/KEYSTORES/FINANCE
```

When this is done, Oracle Database automatically creates the directory for the TDE wallet of a CDB$ROOT at the following location:

```
/etc/ORACLE/KEYSTORES/FINANCE/tde
```

The directories, that Oracle Database automatically creates for holding the TDE wallets of isolated PDBs, will include the *pdb-guid*. For example:

```
/etc/ORACLE/KEYSTORES/FINANCE/3FD1C95B48205D0FE053C5A0E40AEF8C/tde
```

Required setting to enable auto-directory creation for a database using Oracle ASM with Oracle Managed Files

For a database using ASM with OMF, the `WALLET_ROOT` parameter needs to begin with a plus sign followed by a disk group name and the value of the `DB_UNIQUE_NAME` initialization parameter. In the example below, `DATA` is the name of a disk group and `FINRAC` is the value of the `DB_UNIQUE_NAME` initialization parameter:

```
WALLET_ROOT=+DATA/FINRAC
```

When this is done, Oracle Database automatically creates the necessary directory within the ASM filesystem at the following location when the `ADMINISTER KEY MANAGEMENT CREATE KEYSTORE` command is run:

```
+DATA/FINRAC/tde
```

For isolated PDBs, the directories that Oracle Database automatically creates for holding the TDE wallets of PDBs will include the *pdb-guid*. For example:

```
+DATA/FINRAC/3FD1C95B48205D0FE053C5A0E40AEF8C/tde
```

Required setting to enable auto-directory creation for RAC-enabled databases

For a RAC-enabled database, only shared TDE wallets are supported (as opposed to individual TDE-wallets per RAC instance). `WALLET_ROOT` can either point to an ASM disk group, or a directory in ACFS. If the `WALLET_ROOT` parameter points to `+diskgroup/dbname`, then the `/tde` sub-directory is automatically created when issuing an `ADMINISTER KEY MANAGEMENT CREATE KEYSTORE` command. For example, when`WALLET_ROOT` is set to `+DATA/FINANCE`, the directory `+DATA/FINANCE/tde` is automatically created. This guarantees that when multiple databases are installed, their TDE-wallets are kept separate.

> **See Also:**
>
> "TDE_CONFIGURATION"

2.420 WORKAREA_SIZE_POLICY

`WORKAREA_SIZE_POLICY` specifies the policy for sizing work areas. This parameter controls the mode in which working areas are tuned.

Property	Description
Parameter type	String
Syntax	`WORKAREA_SIZE_POLICY = { AUTO | MANUAL }`
Default value	`AUTO`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes

Property	Description
Basic	No

Values

You can specify the following values for `WORKAREA_SIZE_POLICY`:

- `AUTO`

  When `AUTO` is specified, work areas used by memory-intensive operators are sized automatically, based on the PGA memory used by the system, the target PGA memory set in `PGA_AGGREGATE_TARGET`, and the requirement of each individual operator.

- `MANUAL`

  When `MANUAL` is specified, the sizing of work areas is manual and based on the values of the `*_AREA_SIZE` parameter corresponding to the operation (for example, a sort uses `SORT_AREA_SIZE`). Specifying `MANUAL` may result in sub-optimal performance and poor PGA memory utilization.

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for additional information on setting this parameter

2.421 XML_DB_EVENTS

`XML_DB_EVENTS` enables or disables XML DB events.

Property	Description
Parameter type	String
Syntax	`XML_DB_EVENTS = { enable | disable }`
Default value	`enable`
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No

Changing this parameter through an `ALTER SESSION` statement affects only the current session. Only users with the `XDBADMIN` role are allowed to change this parameter in a session.

Changing this parameter through an `ALTER SYSTEM` statement will make a systemwide change of this parameter; however, the change is only registered by new sessions started after the change. Currently running sessions need to be restarted to pick up the new change. Users must have the `ALTER SYSTEM` privilege to make a systemwide change.

> **See Also:**
>
> *Oracle XML DB Developer's Guide* for more information about this parameter

2.422 XML_PARAMS

`XML_PARAMS` lets you adjust the behavior for `XMLType` data.

Property	Description
Parameter type	String
Syntax	`XML_PARAMS = "parameter=value [, parameter=value ] ..."`
Default value	None
Modifiable	`ALTER SESSION`, `ALTER SYSTEM`
Modifiable in a PDB	Yes
Basic	No
Oracle RAC	If specified, Oracle recommends that multiple instances have the same value.

You can specify one of the following for *parameter*=*value*:

- `xml_default_storage_tbx=true`

  Sets the default `XMLType` storage to Transportable Binary XML (TBX) when no storage type is explicitly specified. Starting with Oracle Database 23ai, this is the default and recommended storage type for all `XMLType` data, even if this parameter is not set. Note that Transportable Binary XML must be stored as Securefiles LOBs.

- `xml_default_storage_tbx=false`

  Sets the default `XMLType` storage to Not-Transportable Binary XML (CSX) when no storage type is explicitly specified. This setting can be used as a workaround for applications that still rely on the CSX storage type. Not-Transportable Binary XML can be stored as Basicfiles LOBs or Securefiles LOBs.

Example:

```
ALTER SYSTEM SET XML_PARAMS = "xml_default_storage_tbx=true”;
```

> **Note:**
>
> This parameter is available starting with Oracle Database 23ai.

Part II
Static Data Dictionary Views

This part describes data dictionary tables and views. These tables and views are called **static**, because they change only when a change is made to the data dictionary (for example, when a new table is created or when a user is granted new privileges).
This part contains the following chapters:

- Static Data Dictionary Views: ALL_ALL_TABLES to ALL_OUTLINES
- Static Data Dictionary Views: ALL_PART_COL_STATISTICS to DATABASE_PROPERTIES
- Static Data Dictionary Views: DBA_2PC_NEIGHBORS to DBA_HIST_JAVA_POOL_ADVICE
- Static Data Dictionary Views: DBA_HIST_LATCH to DBA_STORED_SETTINGS
- Static Data Dictionary Views: DBA_STREAMS_ADD_COLUMN to USER_ZONEMAPS

> **Note:**
>
> Oracle also maintains views that monitor ongoing database activity. These **dynamic performance views** are described in Dynamic Performance Views .

> **Note:**
>
> A multitenant container database is the only supported architecture in Oracle Database 21c and later releases. While the documentation is being revised, legacy terminology may persist. In most cases, "database" and "non-CDB" refer to a CDB or PDB, depending on context. In some contexts, such as upgrades, "non-CDB" refers to a non-CDB from a previous release.

3

Static Data Dictionary Views: ALL_ALL_TABLES to ALL_OUTLINES

This chapter describes the first set (in alphabetical order) of static data dictionary views.

The remaining static data dictionary views appear in alphabetical order in Static Data Dictionary Views: ALL_PART_COL_STATISTICS to DATABASE_PROPERTIES through Static Data Dictionary Views: DBA_STREAMS_ADD_COLUMN to USER_ZONEMAPS.

This chapter contains the following topics:

- About Static Data Dictionary Views
- AWR_PDB_* Views
- AWR_ROOT_* Views
- CDB_* Views
- DBA_HIST_* Views
- Oracle Database Real Application Security Views
- Oracle Database Vault Views
- Oracle Label Security Views
- Oracle Workspace Manager Views
- Recovery Catalog Views
- Static Data Dictionary View Descriptions

3.1 About Static Data Dictionary Views

Data dictionary tables are not directly accessible, but you can access information in them through data dictionary views. To list the data dictionary views available to you, query the view `DICTIONARY`.
Many data dictionary tables have three corresponding views:

- An `ALL_` view displays all the information accessible to the current user, including information from the current user's schema as well as information from objects in other schemas, if the current user has access to those objects by way of grants of privileges or roles.
- A `DBA_` view displays all relevant information in the entire database. `DBA_` views are intended only for administrators. They can be queried only by users with the `SYSDBA` system privilege or `SELECT ANY DICTIONARY` privilege, or `SELECT_CATALOG_ROLE` role, or by users with direct privileges granted to them. The `SELECT ANY DICTIONARY` privilege is assigned to the `DBA` role when the system is initially installed.
- A `USER_` view displays all the information from the schema of the current user. No special privileges are required to query these views.

The columns of the `ALL_`, `DBA_`, and `USER_` views corresponding to a single data dictionary table are usually nearly identical. Therefore, these views are described in full only once in this chapter, at their first occurrence alphabetically, and are listed without full descriptions at their other occurrences.

> **See Also:**
>
> "Static Data Dictionary View Descriptions" introduces the alphabetical listing of view descriptions that are documented in this manual

3.2 AWR_PDB_* Views

The AWR_PDB views show the local Automatic Workload Repository (AWR) data present on a CDB root or a PDB from where the AWR_PDB views are accessed.

The AWR_PDB views on a CDB root show the AWR data stored on the CDB root.

The AWR_PDB views on a PDB show the AWR data stored on that PDB.

> **See Also:**
>
> - "AWR_ROOT_* Views"
> - *Oracle Database Performance Tuning Guide* for an introduction to AWR
> - *Oracle Database Performance Tuning Guide* for more information about AWR_PDB views and related views for accessing AWR in a multitenant environment

3.3 AWR_ROOT_* Views

The AWR_ROOT views show the AWR data stored only on a CDB root. In general, the AWR_ROOT views are equivalent to the DBA_HIST views.

When the AWR_ROOT views are accessed from a CDB root, they show the AWR data specific to the CDB root.

When the AWR_ROOT views are accessed from a PDB, they show the AWR data specific to that PDB.

> **See Also:**
>
> - "AWR_PDB_* Views"
> - *Oracle Database Performance Tuning Guide* for an introduction to AWR
> - *Oracle Database Performance Tuning Guide* for more information about AWR_ROOT views and related views for accessing AWR in a multitenant environment

3.4 CDB_* Views

For every DBA_* view, a CDB_* view is defined. In the root of a multitenant container database (CDB), CDB_* views can be used to obtain information about tables, tablespaces, users, privileges, parameters, and so on contained in the root and in pluggable databases (PDBs).
The CDB_* views can be queried only by users with the `SYSDBA` system privilege or `SELECT ANY DICTIONARY` privilege, or `SELECT_CATALOG_ROLE` role, or by users with direct privileges granted to them.

CDB_* views are container data objects. When a user connected to the root queries a CDB_* view, the query results will depend on the `CONTAINER_DATA` attribute for users for the view. The `CONTAINER_DATA` clause of the SQL `ALTER USER` statement is used to set and modify users' `CONTAINER_DATA` attribute.

The CDB_* views are owned by `SYS`, regardless of who owns the underlying DBA_* view.

By default, a user connected to the root will only see data pertaining to the root.

> **See Also:**
>
> - *Oracle Database Security Guide* for more information about container data objects
> - *Oracle Database SQL Language Reference* for more information about the `CONTAINER_DATA` clause for the SQL `ALTER USER` statement

CDB_* views include these hidden columns:

- `CON$NAME`: This column includes the name of the container whose data a given CDB_* row represents
- `CDB$NAME`: This column displays the name of the CDB whose data a given CDB_* row represents

In a PDB, the CDB_* views only show objects visible through a corresponding DBA_* view.

In addition to all the columns found in a given DBA_* view, the corresponding CDB_* view also contains the `CON_ID` column, which identifies a container whose data a given CDB_* row represents. In a non-CDB, the value of a `CON_ID` column will be `0`.

CDB views can return data from different containers in a CDB when queried from the root container. These objects will implicitly convert data to the character set of the root container (AL32UTF8) and then return the result to the user. Some character sets may have character expansion (more bytes needed to represent a character) when converted to AL32UTF8, so there may be data truncation if the view column width is not able to accommodate data from a given PDB.

Data is returned by these views from all open PDBs at the time the query is issued, except for PDBs that are open in RESTRICTED mode. In an Oracle RAC environment, data returned by these views may vary according to the instance to which a session is connected.

3.5 DBA_HIST_* Views

The DBA_HIST views show the local Automatic Workload Repository (AWR) data present on a CDB root or a PDB.

If a DBA_HIST view is queried from a CDB root, the view shows all the AWR data stored on the CDB root.

If a DBA_HIST view is queried from a PDB, the view shows the subset of the CDB root AWR data that is specific to that PDB. Also, the view shows the PDB level snapshots at that PDB, if they exist.

See Also:

- *Oracle Database Performance Tuning Guide* for an introduction to AWR
- *Oracle Database Performance Tuning Guide* for an introduction to Oracle Database views for accessing AWR data stored on the CDB root and individual PDBs in a multitenant environment

3.6 Oracle Database Real Application Security Views

This manual describes these Oracle Database Real Application Security auditing views:

- DBA_XS_AUDIT_POLICY_OPTIONS
- DBA_XS_AUDIT_TRAIL
- DBA_XS_ENB_AUDIT_POLICIES

Descriptions of the other Oracle Database Real Application Security views are provided in *Oracle Database Real Application Security Administrator's and Developer's Guide*.

Note:

Oracle Database Real Application Security views include `_XS_` in the view name.

3.7 Oracle Database Vault Views

Descriptions of Oracle Database Vault views are not provided in this manual.

See *Oracle Database Vault Administrator's Guide* for descriptions of Oracle Database Vault views.

> **Note:**
>
> Oracle Database Vault views include `_DV_` in the view name.

3.8 Oracle Label Security Views

Descriptions of Oracle Label Security views are not provided in this manual.

See *Oracle Label Security Administrator's Guide* for descriptions of Oracle Label Security views.

> **Note:**
>
> Oracle Label Security views include `_SA_` in the view name.

3.9 Oracle Workspace Manager Views

A number of data dictionary views are relevant only if you are using Oracle Workspace Manager:

- `ALL_MP_GRAPH_WORKSPACES` and `USER_MP_GRAPH_WORKSPACES`
- `ALL_MP_PARENT_WORKSPACES` and `USER_MP_PARENT_WORKSPACES`
- `ALL_REMOVED_WORKSPACES` and `USER_REMOVED_WORKSPACES`
- `ALL_VERSION_HVIEW`
- `ALL_WM_CONS_COLUMNS` and `USER_WM_CONS_COLUMNS`
- `ALL_WM_CONSTRAINTS` and `USER_WM_CONSTRAINTS`
- `ALL_WM_IND_COLUMNS` and `USER_WM_IND_COLUMNS`
- `ALL_WM_IND_EXPRESSIONS` and `USER_WM_IND_EXPRESSIONS`
- `ALL_WM_LOCKED_TABLES` and `USER_WM_LOCKED_TABLES`
- `ALL_WM_MODIFIED_TABLES` and `USER_WM_MODIFIED_TABLES`
- `ALL_WM_RIC_INFO` and `USER_WM_RIC_INFO`
- `ALL_WM_TAB_TRIGGERS` and `USER_WM_TAB_TRIGGERS`
- `ALL_WM_VERSIONED_TABLES` and `USER_WM_VERSIONED_TABLES`

- ALL_WM_VT_ERRORS, DBA_WM_VT_ERRORS, and USER_WM_VT_ERRORS
- ALL_WORKSPACE_PRIVS and USER_WORKSPACE_PRIVS
- ALL_WORKSPACE_SAVEPOINTS and USER_WORKSPACE_SAVEPOINTS
- ALL_WORKSPACES, DBA_WORKSPACES, and USER_WORKSPACES
- DBA_WM_SYS_PRIVS
- DBA_WORKSPACE_SESSIONS
- ROLE_WM_PRIVS
- USER_WM_PRIVS
- WM_COMPRESS_BATCH_SIZES
- WM_COMPRESSIBLE_TABLES
- WM_EVENTS_INFO
- WM_INSTALLATION

See Also:

Oracle Database Workspace Manager Developer's Guide for information about these views

3.10 Recovery Catalog Views

The following data dictionary views are only available after you create an optional recovery catalog (which contains schemas containing information about backups) for use with Recovery Manager:

```
RC_ARCHIVED_LOG
RC_BACKUP_ARCHIVELOG_DETAILS
RC_BACKUP_ARCHIVELOG_SUMMARY
RC_BACKUP_CONTROLFILE
RC_BACKUP_CONTROLFILE_DETAILS
RC_BACKUP_CONTROLFILE_SUMMARY
RC_BACKUP_COPY_DETAILS
RC_BACKUP_COPY_SUMMARY
RC_BACKUP_CORRUPTION
RC_BACKUP_DATAFILE
RC_BACKUP_DATAFILE_DETAILS
RC_BACKUP_DATAFILE_SUMMARY
RC_BACKUP_FILES
RC_BACKUP_PIECE
RC_BACKUP_PIECE_DETAILS
RC_BACKUP_REDOLOG
RC_BACKUP_SET
RC_BACKUP_SET_DETAILS
```

```
RC_BACKUP_SET_SUMMARY
RC_BACKUP_SPFILE
RC_BACKUP_SPFILE_DETAILS
RC_BACKUP_SPFILE_SUMMARY
RC_CHECKPOINT
RC_CONTROLFILE_COPY
RC_COPY_CORRUPTION
RC_DATABASE
RC_DATABASE_BLOCK_CORRUPTION
RC_DATABASE_INCARNATION
RC_DATAFILE
RC_DATAFILE_COPY
RC_LOG_HISTORY
RC_OFFLINE_RANGE
RC_PROXY_ARCHIVEDLOG
RC_PROXY_ARCHIVELOG_DETAILS
RC_PROXY_ARCHIVELOG_SUMMARY
RC_PROXY_CONTROLFILE
RC_PROXY_COPY_DETAILS
RC_PROXY_COPY_SUMMARY
RC_PROXY_DATAFILE
RC_REDO_LOG
RC_REDO_THREAD
RC_RESTORE_POINT
RC_RESYNC
RC_RMAN_BACKUP_JOB_DETAILS
RC_RMAN_BACKUP_SUBJOB_DETAILS
RC_RMAN_BACKUP_TYPE
RC_RMAN_CONFIGURATION
RC_RMAN_OUTPUT
RC_RMAN_STATUS
RC_SITE
RC_STORED_SCRIPT
RC_STORED_SCRIPT_LINE
RC_TABLESPACE
RC_TEMPFILE
RC_UNUSABLE_BACKUPFILE_DETAILS
```

See Also:

Oracle Database Backup and Recovery Reference for information about these views

3.11 Static Data Dictionary View Descriptions

The remainder of this chapter describes the static data dictionary views in alphabetical order.

3.12 ALL_ALL_TABLES

ALL_ALL_TABLES describes the object tables and relational tables accessible to the current user.

Related Views

- DBA_ALL_TABLES describes all object tables and relational tables in the database.
- USER_ALL_TABLES describes the object tables and relational tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace containing the table; NULL for partitioned, temporary, and index-organized tables
CLUSTER_NAME	VARCHAR2(128)		Name of the cluster, if any, to which the table belongs
IOT_NAME	VARCHAR2(128)		Name of the index-organized table, if any, to which the overflow or mapping table entry belongs. If the IOT_TYPE column is not NULL, then this column contains the base table name.
STATUS	VARCHAR2(8)		If a previous DROP TABLE operation failed, indicates whether the table is unusable (UNUSABLE) or valid (VALID)
PCT_FREE	NUMBER		Minimum percentage of free space in a block; NULL for partitioned tables
PCT_USED	NUMBER		Minimum percentage of used space in a block; NULL for partitioned tables
INI_TRANS	NUMBER		Initial number of transactions; NULL for partitioned tables
MAX_TRANS	NUMBER		Maximum number of transactions; NULL for partitioned tables
INITIAL_EXTENT	NUMBER		Size of the initial extent (in bytes); NULL for partitioned tables
NEXT_EXTENT	NUMBER		Size of secondary extents (in bytes); NULL for partitioned tables
MIN_EXTENTS	NUMBER		Minimum number of extents allowed in the segment; NULL for partitioned tables
MAX_EXTENTS	NUMBER		Maximum number of extents allowed in the segment; NULL for partitioned tables

Column	Datatype	NULL	Description
PCT_INCREASE	NUMBER		Percentage increase in extent size; NULL for partitioned tables
FREELISTS	NUMBER		Number of process freelists allocated to the segment; NULL for partitioned tables
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to the segment
LOGGING	VARCHAR2(3)		Indicates whether or not changes to the table are logged: • YES • NO
BACKED_UP	VARCHAR2(1)		Indicates whether the table has been backed up since the last modification (Y) or not (N)
NUM_ROWS	NUMBER		Number of rows in the table
BLOCKS	NUMBER		Number of used blocks in the table
EMPTY_BLOCKS	NUMBER		Number of empty (never used) blocks in the table
AVG_SPACE	NUMBER		Average available free space in the table
CHAIN_CNT	NUMBER		Number of rows in the table that are chained from one data block to another or that have migrated to a new block, requiring a link to preserve the old rowid. This column is updated only after you analyze the table.
AVG_ROW_LEN	NUMBER		Average row length, including row overhead
AVG_SPACE_FREELIST_BLOCKS	NUMBER		Average freespace of all blocks on a freelist
NUM_FREELIST_BLOCKS	NUMBER		Number of blocks on the freelist
DEGREE	VARCHAR2(10)		Number of threads per instance for scanning the table, or DEFAULT
INSTANCES	VARCHAR2(10)		Number of instances across which the table is to be scanned, or DEFAULT
CACHE	VARCHAR2(5)		Indicates whether the table is to be cached in the buffer cache (Y) or not (N)
TABLE_LOCK	VARCHAR2(8)		Indicates whether table locking is enabled (ENABLED) or disabled (DISABLED)
SAMPLE_SIZE	NUMBER		Sample size used in analyzing the table
LAST_ANALYZED	DATE		Date on which the table was most recently analyzed
PARTITIONED	VARCHAR2(3)		Indicates whether the table is partitioned (YES) or not (NO)
IOT_TYPE	VARCHAR2(12)		If the table is an index-organized table, then IOT_TYPE is IOT, IOT_OVERFLOW, or IOT_MAPPING. If the table is not an index-organized table, then IOT_TYPE is NULL.
OBJECT_ID_TYPE	VARCHAR2(16)		Indicates whether the object ID (OID) is USER-DEFINED or SYSTEM GENERATED
TABLE_TYPE_OWNER	VARCHAR2(128)		If an object table, owner of the type from which the table is created

Column	Datatype	NULL	Description
TABLE_TYPE	VARCHAR2(128)		If an object table, type of the table
TEMPORARY	VARCHAR2(1)		Indicates whether the table is temporary (Y) or not (N)
SECONDARY	VARCHAR2(1)		Indicates whether the table is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge to contain the contents of a domain index (Y) or not (N)
NESTED	VARCHAR2(3)		Indicates whether the table is a nested table (YES) or not (NO)
BUFFER_POOL	VARCHAR2(7)		Buffer pool to be used for table blocks: • DEFAULT • KEEP • RECYCLE • NULL
FLASH_CACHE	VARCHAR2(7)		Database Smart Flash Cache hint to be used for table blocks: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2(7)		Cell flash cache hint to be used for table blocks: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
ROW_MOVEMENT	VARCHAR2(8)		If a partitioned table, indicates whether row movement is enabled (ENABLED) or disabled (DISABLED)
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics are gathered or incrementally maintained, otherwise it will be NO
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
DURATION	VARCHAR2(15)		Indicates the duration of a temporary table: SYS$SESSION - Rows are preserved for the duration of the session SYS$TRANSACTION - Rows are deleted after COMMIT Null - Permanent table
SKIP_CORRUPT	VARCHAR2(8)		Indicates whether Oracle Database ignores blocks marked corrupt during table and index scans (ENABLED) or raises an error (DISABLED). To enable this feature, run the DBMS_REPAIR.skip_corrupt_blocks procedure.
MONITORING	VARCHAR2(3)		Indicates whether the table has the MONITORING attribute set (YES) or not (NO)
CLUSTER_OWNER	VARCHAR2(128)		Owner of the cluster, if any, to which the table belongs

Column	Datatype	NULL	Description
DEPENDENCIES	VARCHAR2(8)		Indicates whether row-level dependency tracking is enabled (ENABLED) or disabled (DISABLED)
COMPRESSION	VARCHAR2(8)		Indicates whether table compression is enabled (ENABLED) or not (DISABLED); NULL for partitioned tables
COMPRESS_FOR	VARCHAR2(30)		Default compression for what kind of operations: • BASIC • ADVANCED • QUERY LOW • QUERY HIGH • ARCHIVE LOW • ARCHIVE HIGH • NULL The QUERY LOW, QUERY HIGH, ARCHIVE LOW, and ARCHIVE HIGH values are associated with Hybrid Columnar Compression, a feature of the Enterprise Edition of Oracle Database that is dependent on the underlying storage system. See *Oracle Database Concepts* for more information.
DROPPED	VARCHAR2(3)		Indicates whether the table has been dropped and is in the recycle bin (YES) or not (NO); NULL for partitioned tables This view does not return the names of tables that have been dropped.
SEGMENT_CREATED	VARCHAR2(3)		Indicates whether the table segment has been created (YES) or not (NO)
INMEMORY	VARCHAR2(8)		Indicates whether the In-Memory Column Store (IM column store) is enabled (ENABLED) or disabled (DISABLED) for this table
INMEMORY_PRIORITY	VARCHAR2(8)		Indicates the priority at which this table is populated into the In-Memory Column Store (IM column store). Possible values: • LOW • MEDIUM • HIGH • CRITICAL • NONE • NULL This column has a value based on where the segments lie for a table. For example, if the table is partitioned and is enabled for the IM column store, the value is NULL for ALL_TABLES but non-NULL for ALL_TAB_PARTITIONS.
INMEMORY_DISTRIBUTE	VARCHAR2(15)		Indicates how the table will be distributed in the IM column stores in an Oracle Real Application Clusters (Oracle RAC) environment: • AUTO • BY ROWID RANGE • BY PARTITION • BY SUBPARTITION

Column	Datatype	NULL	Description
INMEMORY_COMPRESSION	VARCHAR2(17)		Compression level for the in-memory store: • NO MEMCOMPRESS • FOR DML • FOR QUERY [LOW | HIGH] • FOR CAPACITY [LOW | HIGH] • AUTO • NULL This column has a value based on where the segments lie for a table. For example, if the table is partitioned and is enabled for the IM column store, the value is NULL for ALL_TABLES but non-NULL for ALL_TAB_PARTITIONS.
INMEMORY_DUPLICATE	VARCHAR2(13)		Indicates the duplicate setting for the In-Memory Column Store (IM column store) in an Oracle RAC environment: • NO DUPLICATE • DUPLICATE • DUPLICATE ALL
EXTERNAL	VARCHAR2(3)		Indicates whether the table is an external table (YES) or not (NO)
HYBRID	VARCHAR2(3)		Indicates whether the table is a hybrid partitioned table (YES) or not (NO). A hybrid partitioned table can contain a mixture of partitions stored in segments and partitions stored externally.
CELLMEMORY[1]	VARCHAR2(24)		The value for columnar compression in the storage cell flash cache. Possible values: • ENABLED: Oracle Exadata Storage will decide automatically whether to cache in columnar form • DISABLED: Oracle Exadata Storage is prevented from caching in columnar form • NO CACHECOMPRESS: Oracle Exadata Storage will cache in HCC format (no recompression) • FOR QUERY: Oracle Exadata Storage will recompress and cache in INMEMORY query high format • FOR CAPACITY: Oracle Exadata Storage will recompress and cache in INMEMORY capacity low format

Column	Datatype	NULL	Description
INMEMORY_SERVICE	VARCHAR2(12)		Indicates how the IM column store is populated on various instances. The possible values are: • DEFAULT: Data is populated on all instances specified with the PARALLEL_INSTANCE_GROUP initialization parameter. If that parameter is not set, then the data is populated on all instances. This is the default. • NONE: Data is not populated on any instance. • ALL: Data is populated on all instances, regardless of the value of the PARALLEL_INSTANCE_GROUP initialization parameter. • USER_DEFINED: Data is populated only on the instances on which the user-specified service is active. The service name corresponding to this is stored in the INMEMORY_SERVICE_NAME column.
INMEMORY_SERVICE_NAME	VARCHAR2(1000)		Indicates the service name for the service on which the IM column store should be populated. This column has a value only when the corresponding INMEMORY_SERVICE is USER_DEFINED. In all other cases, this column is null.
MEMOPTIMIZE_READ	VARCHAR2(8)		Indicates whether the table is enabled for Fast Key Based Access (ENABLED) or not (DISABLED)
MEMOPTIMIZE_WRITE	VARCHAR2(8)		For internal use only
HAS_SENSITIVE_COLUMN	VARCHAR2(3)		Indicates whether the table has one or more sensitive columns (YES) or not (NO)
LOGICAL_REPLICATION	VARCHAR2(8)		Indicates whether the table is enabled for logical replication (ENABLED) or not (DISABLED). This setting is ignored if database-wide column data supplemental logging is enabled.
STAGING	VARCHAR2(3)		Indicates whether the table is a staging table (YES) or not (NO)
HAS_RESERVABLE_COLUMN	VARCHAR2(3)		Indicates whether the table has one or more reservable columns (YES) or not (NO)

1 This column is intended for use with Oracle Exadata.

See Also:

- "DBA_ALL_TABLES"
- "USER_ALL_TABLES"
- "PARALLEL_INSTANCE_GROUP"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_REPAIR.SKIP_CORRUPT_BLOCKS` procedure
- *Oracle Database In-Memory Guide* for an introduction to the IM column store
- *Oracle Database In-Memory Guide* for more information about the IM column store

3.13 ALL_ANALYTIC_VIEW_ATTR_CLASS

`ALL_ANALYTIC_VIEW_ATTR_CLASS` describes the attribute classifications of the analytic views accessible to the current user.

Related Views

- `DBA_ANALYTIC_VIEW_ATTR_CLASS` describes the attribute classifications of all analytic views in the database.
- `USER_ANALYTIC_VIEW_ATTR_CLASS` describes the attribute classifications of the analytic views owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
HIER_ALIAS	VARCHAR2(128)		Alias of the hierarchy specified by an attribute dimension in the analytic view
ATTRIBUTE_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute within the analytic view
CLASSIFICATION	VARCHAR2(128)		Name of analytic view attribute classification
VALUE	CLOB		Value of attribute classification
LANGUAGE	VARCHAR2(64)		Language of attribute classification
ORDER_NUM	NUMBER	NOT NULL	Order number of the attribute classification
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

> **See Also:**
>
> - "DBA_ANALYTIC_VIEW_ATTR_CLASS"
> - "USER_ANALYTIC_VIEW_ATTR_CLASS"

3.14 ALL_ANALYTIC_VIEW_ATTR_CLS

ALL_ANALYTIC_VIEW_ATTR_CLS is identical to ALL_ANALYTIC_VIEW_ATTR_CLASS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_ATTR_CLASS"

3.15 ALL_ANALYTIC_VIEW_ATTR_CLS_AE

ALL_ANALYTIC_VIEW_ATTR_CLS_AE describes the attribute classifications of the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_ATTR_CLS_AE describes the attribute classifications of all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEW_ATTR_CLS_AE describes the attribute classifications of the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
HIER_ALIAS	VARCHAR2(128)		Alias of the hierarchy specified by an attribute dimension in the analytic view
ATTRIBUTE_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute within the analytic view
CLASSIFICATION	VARCHAR2(128)		Name of analytic view attribute classification
VALUE	CLOB		Value of attribute classification
LANGUAGE	VARCHAR2(64)		Language of attribute classification
ORDER_NUM	NUMBER	NOT NULL	Order number of the attribute classification

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

See Also:

- "DBA_ANALYTIC_VIEW_ATTR_CLS_AE"
- "USER_ANALYTIC_VIEW_ATTR_CLS_AE"

3.16 ALL_ANALYTIC_VIEW_BAS_MEAS

ALL_ANALYTIC_VIEW_BAS_MEAS is identical to ALL_ANALYTIC_VIEW_BASE_MEAS.

See Also:

"ALL_ANALYTIC_VIEW_BASE_MEAS"

3.17 ALL_ANALYTIC_VIEW_BAS_MEAS_AE

ALL_ANALYTIC_VIEW_BAS_MEAS_AE describes the base measures in the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_BAS_MEAS_AE describes the base measures in all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEW_BAS_MEAS_AE describes the base measures in the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
MEASURE_NAME	VARCHAR2(128)		Name of the analytic view base measure

Column	Datatype	NULL	Description
TABLE_ALIAS	VARCHAR2(128)		Alias of the table or view in the USING clause to which the column belongs
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Column name in the table or view on which this measure is defined
MEAS_EXPRESSION	CLOB		Text of the expression for the measure
AGGR_FUNCTION	VARCHAR2(128)		Aggregation operator specified for this measure or NULL if not specified
AGGR_GROUP_NAME	VARCHAR2(128)		Aggregation function group name specified for this measure or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order number of the base measure in the list of measures in the analytic view
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

See Also:

- "DBA_ANALYTIC_VIEW_BAS_MEAS_AE"
- "USER_ANALYTIC_VIEW_BAS_MEAS_AE"

3.18 ALL_ANALYTIC_VIEW_BASE_MEAS

ALL_ANALYTIC_VIEW_BASE_MEAS describes the base measures in the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_BASE_MEAS describes the base measures in all analytic views in the database.
- USER_ANALYTIC_VIEW_BASE_MEAS describes the base measures in the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
MEASURE_NAME	VARCHAR2(128)		Name of the analytic view base measure
TABLE_ALIAS	VARCHAR2(128)		Alias of the table or view in the USING clause to which the column belongs

Column	Datatype	NULL	Description
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Column name in the table or view on which this measure is defined
MEAS_EXPRESSION	CLOB		Text of the expression for the measure
AGGR_FUNCTION	VARCHAR2(128)		Aggregation operator specified for this measure or NULL if not specified
AGGR_GROUP_NAME	VARCHAR2(128)		Aggregation function group name specified for this measure or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order number of the base measure in the list of measures in the analytic view
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ANALYTIC_VIEW_BASE_MEAS"
- "USER_ANALYTIC_VIEW_BASE_MEAS"

3.19 ALL_ANALYTIC_VIEW_CALC_MEAS

ALL_ANALYTIC_VIEW_CALC_MEAS describes the calculated measures in the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_CALC_MEAS describes the calculated measures in all analytic views in the database.
- USER_ANALYTIC_VIEW_CALC_MEAS describes the calculated measures in the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
MEASURE_NAME	VARCHAR2(128)		Name of the analytic view calculated measure
MEAS_EXPRESSION	CLOB		Text of the expression for the measure
ORDER_NUM	NUMBER	NOT NULL	Order number of the calculated measure in the list of the measures in the analytic view

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ANALYTIC_VIEW_CALC_MEAS"
- "USER_ANALYTIC_VIEW_CALC_MEAS"

3.20 ALL_ANALYTIC_VIEW_CLASS

ALL_ANALYTIC_VIEW_CLASS describes the classifications of the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_CLASS describes the classifications of all analytic views in the database.
- USER_ANALYTIC_VIEW_CLASS describes the classifications of the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
CLASSIFICATION	VARCHAR2(128)		Classification associated with the analytic view
VALUE	CLOB		Value of the classification or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the analytic view
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

> **See Also:**
>
> - "DBA_ANALYTIC_VIEW_CLASS"
> - "USER_ANALYTIC_VIEW_CLASS"

3.21 ALL_ANALYTIC_VIEW_CLASS_AE

ALL_ANALYTIC_VIEW_CLASS_AE describes the classifications of the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_CLASS_AE describes the classifications of all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEW_CLASS_AE describes the classifications of the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
CLASSIFICATION	VARCHAR2(128)		Classification associated with the analytic view
VALUE	CLOB		Value of the classification or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the analytic view
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

> **See Also:**
>
> - "DBA_ANALYTIC_VIEW_CLASS_AE"
> - "USER_ANALYTIC_VIEW_CLASS_AE"

3.22 ALL_ANALYTIC_VIEW_CLC_MEAS

`ALL_ANALYTIC_VIEW_CLC_MEAS` is identical to `ALL_ANALYTIC_VIEW_CALC_MEAS`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_CALC_MEAS"

3.23 ALL_ANALYTIC_VIEW_CLC_MEAS_AE

`ALL_ANALYTIC_VIEW_CLC_MEAS_AE` describes the calculated measures in the analytic views (across all editions) accessible to the current user.

Related Views

- `DBA_ANALYTIC_VIEW_CLC_MEAS_AE` describes the calculated measures in all analytic views (across all editions) in the database.
- `USER_ANALYTIC_VIEW_CLC_MEAS_AE` describes the calculated measures in the analytic views (across all editions) owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
MEASURE_NAME	VARCHAR2(128)		Name of the analytic view calculated measure
MEAS_EXPRESSION	CLOB		Text of the expression for the measure
ORDER_NUM	NUMBER	NOT NULL	Order number of the calculated measure in the list of the measures in the analytic view
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

> **See Also:**
>
> - "DBA_ANALYTIC_VIEW_CLC_MEAS_AE"
> - "USER_ANALYTIC_VIEW_CLC_MEAS_AE"

3.24 ALL_ANALYTIC_VIEW_COLUMNS

ALL_ANALYTIC_VIEW_COLUMNS describes the columns of the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_COLUMNS describes the columns of all analytic views in the database.
- USER_ANALYTIC_VIEW_COLUMNS describes the columns of the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_NAME	VARCHAR2(128)		Alias of the analytic view dimension in the analytic view; for a measure the value is MEASURES
HIER_NAME	VARCHAR2(128)		Alias of the analytic view hierarchy within DIMENSION_NAME in the analytic view; for a measure the value is MEASURES
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
ROLE	VARCHAR2(4)	NOT NULL	The role the attribute plays in the analytic view: • KEY • AKEY • HIER • PROP • MEAS
DATA_TYPE	VARCHAR2(106)	NOT NULL	Datatype of the column
DATA_LENGTH	NUMBER	NOT NULL	Length of the column (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for the NUMBER datatype; binary precision for the FLOAT datatype, NULL for all other datatypes
DATA_SCALE	NUMBER		Number of digits to the right of the decimal point in a number
NULLABLE	CHAR(1)	NOT NULL	Indicates whether a column allows NULL values; the value is N if there is a NOT NULL constraint on the column or if the column is part of a PRIMARY KEY
CHARACTER_SET_NAME	VARCHAR2(44)		Name of the character set: • CHAR_CS • NCHAR_CS
CHAR_COL_DECL_LENGTH	NUMBER		Declaration length of the character type column

Column	Datatype	NULL	Description
CHAR_USED	VARCHAR2(1)		Indicates that the column uses BYTE length semantics (B) or CHAR length semantics (C), or whether the datatype is not any of the following (NULL): • CHAR • VARCHAR2 • NCHAR • NVARCHAR2
ORDER_NUM	NUMBER	NOT NULL	Order of the column, with the hierarchy columns first followed by measure columns. The columns for a hierarchy are grouped together, listed in their order in the HIERARCHIES clause of the analytic view definition. Within a hierarchy, attributes are listed first in order of their definition in the ATTRIBUTES clause of the attribute dimension definition followed by hierarchical attributes in the DIMENSION BY clause of the analytic view.
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ANALYTIC_VIEW_COLUMNS"
- "USER_ANALYTIC_VIEW_COLUMNS"

3.25 ALL_ANALYTIC_VIEW_COLUMNS_AE

ALL_ANALYTIC_VIEW_COLUMNS_AE describes the columns of the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_COLUMNS_AE describes the columns of all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEW_COLUMNS_AE describes the columns of the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view

Column	Datatype	NULL	Description
DIMENSION_NAME	VARCHAR2(128)		Alias of the analytic view dimension in the analytic view; for a measure the value is MEASURES
HIER_NAME	VARCHAR2(128)		Alias of the analytic view hierarchy within DIMENSION_NAME in the analytic view; for a measure the value is MEASURES
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
ROLE	VARCHAR2(4)	NOT NULL	The role the attribute plays in the analytic view: • KEY • AKEY • HIER • PROP • MEAS
DATA_TYPE	VARCHAR2(106)	NOT NULL	Datatype of the column
DATA_LENGTH	NUMBER	NOT NULL	Length of the column (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for the NUMBER datatype; binary precision for the FLOAT datatype, NULL for all other datatypes
DATA_SCALE	NUMBER		Number of digits to the right of the decimal point in a number
NULLABLE	CHAR(1)	NOT NULL	Indicates whether a column allows NULL values; the value is N if there is a NOT NULL constraint on the column or if the column is part of a PRIMARY KEY
CHARACTER_SET_NAME	VARCHAR2(44)		Name of the character set: • CHAR_CS • NCHAR_CS
CHAR_COL_DECL_LENGTH	NUMBER		Declaration length of the character type column
CHAR_USED	VARCHAR2(1)		Indicates that the column uses BYTE length semantics (B) or CHAR length semantics (C), or whether the datatype is not any of the following (NULL): • CHAR • VARCHAR2 • NCHAR • NVARCHAR2
ORDER_NUM	NUMBER	NOT NULL	Order of the column, with the hierarchy columns first followed by measure columns. The columns for a hierarchy are grouped together, listed in their order in the HIERARCHIES clause of the analytic view definition. Within a hierarchy, attributes are listed first in order of their definition in the ATTRIBUTES clause of the attribute dimension definition followed by hierarchical attributes in the DIMENSION BY clause of the analytic view.

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

See Also:

- "DBA_ANALYTIC_VIEW_COLUMNS_AE"
- "USER_ANALYTIC_VIEW_COLUMNS_AE"

3.26 ALL_ANALYTIC_VIEW_DIM_ATRS

ALL_ANALYTIC_VIEW_DIM_ATRS is identical to ALL_ANALYTIC_VIEW_DIM_ATTRS.

See Also:

"ALL_ANALYTIC_VIEW_DIM_ATTRS"

3.27 ALL_ANALYTIC_VIEW_DIM_ATRS_AE

ALL_ANALYTIC_VIEW_DIM_ATRS_AE describes the attributes of the attribute dimensions in the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_DIM_ATRS_AE describes the attributes of the attribute dimensions in all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEW_DIM_ATRS_AE describes the attributes of the attribute dimensions in the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
ATTRIBUTE_NAME	VARCHAR2(128)	NOT NULL	The name of the attribute within the analytic view

Column	Datatype	NULL	Description
TABLE_ALIAS	VARCHAR2(128)		Alias of the source table for the attribute
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
ORDER_NUM	NUMBER	NOT NULL	Order of the attribute as defined in the metadata
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

See Also:

- "DBA_ANALYTIC_VIEW_DIM_ATRS_AE"
- "USER_ANALYTIC_VIEW_DIM_ATRS_AE"

3.28 ALL_ANALYTIC_VIEW_DIM_ATTRS

ALL_ANALYTIC_VIEW_DIM_ATTRS describes the attributes of the attribute dimensions in the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_DIM_ATTRS describes the attributes of the attribute dimensions in all analytic views in the database.
- USER_ANALYTIC_VIEW_DIM_ATTRS describes the attributes of the attribute dimensions in the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
ATTRIBUTE_NAME	VARCHAR2(128)	NOT NULL	The name of the attribute within the analytic view
TABLE_ALIAS	VARCHAR2(128)		Alias of the source table for the attribute
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
ORDER_NUM	NUMBER	NOT NULL	Order of the attribute as defined in the metadata

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ANALYTIC_VIEW_DIM_ATTRS"
- "USER_ANALYTIC_VIEW_DIM_ATTRS"

3.29 ALL_ANALYTIC_VIEW_DIM_CLASS

ALL_ANALYTIC_VIEW_DIM_CLASS describes the classifications of the attribute dimensions in the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_DIM_CLASS describes the classifications of the attribute dimensions in all analytic views in the database.
- USER_ANALYTIC_VIEW_DIM_CLASS describes the classifications of the attribute dimensions in the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
CLASSIFICATION	VARCHAR2(128)		Classification associated with the attribute dimension
VALUE	CLOB		Value of the classification or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the attribute dimension
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

> **See Also:**
>
> - "DBA_ANALYTIC_VIEW_DIM_CLASS"
> - "USER_ANALYTIC_VIEW_DIM_CLASS"

3.30 ALL_ANALYTIC_VIEW_DIM_CLS

ALL_ANALYTIC_VIEW_DIM_CLS is identical to ALL_ANALYTIC_VIEW_DIM_CLASS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_DIM_CLASS"

3.31 ALL_ANALYTIC_VIEW_DIM_CLS_AE

ALL_ANALYTIC_VIEW_DIM_CLS_AE describes the classifications of the attribute dimensions in the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_DIM_CLS_AE describes the classifications of the attribute dimensions in all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEW_DIM_CLS_AE describes the classifications of the attribute dimensions in the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
CLASSIFICATION	VARCHAR2(128)		Classification associated with the attribute dimension
VALUE	CLOB		Value of the classification or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the attribute dimension

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

See Also:

- "DBA_ANALYTIC_VIEW_DIM_CLS_AE"
- "USER_ANALYTIC_VIEW_DIM_CLS_AE"

3.32 ALL_ANALYTIC_VIEW_DIMENSIONS

ALL_ANALYTIC_VIEW_DIMENSIONS describes the attribute dimensions in the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_DIMENSIONS describes the attribute dimensions in all analytic views in the database.
- USER_ANALYTIC_VIEW_DIMENSIONS describes the attribute dimensions in the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_OWNER	VARCHAR2(128)	NOT NULL	Owner of the schema containing the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
DIMENSION_TYPE	VARCHAR2(8)		Type of the attribute dimension: • TIME • STANDARD
ALL_MEMBER_NAME	CLOB		An expression for the name of the ALL member for the attribute dimension
ALL_MEMBER_CAPTION	CLOB		An expression for the caption for the ALL member of the attribute dimension, or NULL if not specified
ALL_MEMBER_DESCRIPTION	CLOB		An expression for the description for the ALL member of the attribute dimension, or NULL if not specified

Column	Datatype	NULL	Description
REFERENCES_DISTINCT	VARCHAR2(1)		Indicates whether the reference between the fact table key and the attribute dimension attribute specifies the DISTINCT keyword. Possible values are: • Y: The reference specifies the DISTINCT keyword. • N: The reference does not specify the DISTINCT keyword.
ORDER_NUM	NUMBER	NOT NULL	Order number of the attribute dimension in the analytic view
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ANALYTIC_VIEW_DIMENSIONS"
- "USER_ANALYTIC_VIEW_DIMENSIONS"

3.33 ALL_ANALYTIC_VIEW_DIMS

ALL_ANALYTIC_VIEW_DIMS is identical to ALL_ANALYTIC_VIEW_DIMENSIONS.

See Also:

"ALL_ANALYTIC_VIEW_DIMENSIONS"

3.34 ALL_ANALYTIC_VIEW_DIMS_AE

ALL_ANALYTIC_VIEW_DIMS_AE describes the attribute dimensions in the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_DIMS_AE describes the attribute dimensions in all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEW_DIMS_AE describes the attribute dimensions in the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_OWNER	VARCHAR2(128)	NOT NULL	Owner of the schema containing the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
DIMENSION_TYPE	VARCHAR2(8)		Type of the attribute dimension: • TIME • STANDARD
ALL_MEMBER_NAME	CLOB		An expression for the name of the ALL member for the attribute dimension
ALL_MEMBER_CAPTION	CLOB		An expression for the caption for the ALL member of the attribute dimension, or NULL if not specified
ALL_MEMBER_DESCRIPTION	CLOB		An expression for the description for the ALL member of the attribute dimension, or NULL if not specified
REFERENCES_DISTINCT	VARCHAR2(1)		Indicates whether the reference between the fact table key and the attribute dimension attribute specifies the DISTINCT keyword. Possible values are: • Y: The reference specifies the DISTINCT keyword. • N: The reference does not specify the DISTINCT keyword.
ORDER_NUM	NUMBER	NOT NULL	Order number of the attribute dimension in the analytic view
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

See Also:

- "DBA_ANALYTIC_VIEW_DIMS_AE"
- "USER_ANALYTIC_VIEW_DIMS_AE"

3.35 ALL_ANALYTIC_VIEW_FACT_COLS

ALL_ANALYTIC_VIEW_FACT_COLS describes the fact columns of the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_FACT_COLS describes the fact columns of all analytic views in the database.
- USER_ANALYTIC_VIEW_FACT_COLS describes the fact columns of the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
TABLE_ALIAS	VARCHAR2(128)		Alias of the fact table in the analytic view
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
COLUMN_ALIAS	VARCHAR2(128)	NOT NULL	Alias of the column. Use this value as the identifier for the fact column in a query.
ORDER_NUM	NUMBER	NOT NULL	Order of the column in the fact table
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ANALYTIC_VIEW_FACT_COLS"
- "USER_ANALYTIC_VIEW_FACT_COLS"

3.36 ALL_ANALYTIC_VIEW_FCT_COLS

ALL_ANALYTIC_VIEW_FCT_COLS is identical to ALL_ANALYTIC_VIEW_FACT_COLS.

See Also:

"ALL_ANALYTIC_VIEW_FACT_COLS"

3.37 ALL_ANALYTIC_VIEW_FCT_COLS_AE

ALL_ANALYTIC_VIEW_FCT_COLS_AE describes the fact columns of the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_FCT_COLS_AE describes the fact columns of all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEW_FCT_COLS_AE describes the fact columns of the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
TABLE_ALIAS	VARCHAR2(128)		Alias of the fact table in the analytic view
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
COLUMN_ALIAS	VARCHAR2(128)	NOT NULL	Alias of the column. Use this value as the identifier for the fact column in a query.
ORDER_NUM	NUMBER	NOT NULL	Order of the column in the fact table
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

See Also:

- "DBA_ANALYTIC_VIEW_FCT_COLS_AE"
- "USER_ANALYTIC_VIEW_FCT_COLS_AE"

3.38 ALL_ANALYTIC_VIEW_HIER_CLASS

ALL_ANALYTIC_VIEW_HIER_CLASS describes the classifications of the hierarchies in the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_HIER_CLASS describes the classifications of the hierarchies in all analytic views in the database.

- USER_ANALYTIC_VIEW_HIER_CLASS describes the classifications of the hierarchies in the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
HIER_ALIAS	VARCHAR2(128)		Alias of the hierarchy in the attribute dimension in the analytic view
CLASSIFICATION	VARCHAR2(128)		Classification associated with the hierarchy
VALUE	CLOB		Value of the classification, or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification, or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the hierarchy
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ANALYTIC_VIEW_HIER_CLASS"
- "USER_ANALYTIC_VIEW_HIER_CLASS"

3.39 ALL_ANALYTIC_VIEW_HIER_CLS

ALL_ANALYTIC_VIEW_HIER_CLS is identical to ALL_ANALYTIC_VIEW_HIER_CLASS.

See Also:

"ALL_ANALYTIC_VIEW_HIER_CLASS"

3.40 ALL_ANALYTIC_VIEW_HIER_CLS_AE

ALL_ANALYTIC_VIEW_HIER_CLS_AE describes the classifications of the hierarchies in the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_HIER_CLS_AE describes the classifications of the hierarchies in all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEW_HIER_CLS_AE describes the classifications of the hierarchies in the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
HIER_ALIAS	VARCHAR2(128)		Alias of the hierarchy in the attribute dimension in the analytic view
CLASSIFICATION	VARCHAR2(128)		Classification associated with the hierarchy
VALUE	CLOB		Value of the classification, or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification, or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the hierarchy
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

See Also:

- "DBA_ANALYTIC_VIEW_HIER_CLS_AE"
- "USER_ANALYTIC_VIEW_HIER_CLS_AE"

3.41 ALL_ANALYTIC_VIEW_HIERS

ALL_ANALYTIC_VIEW_HIERS describes the hierarchies in the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_HIERS describes the hierarchies in all analytic views in the database.
- USER_ANALYTIC_VIEW_HIERS describes the hierarchies in the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view hierarchy
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
HIER_OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
HIER_ALIAS	VARCHAR2(128)		Alias specified for the hierarchy
IS_DEFAULT	VARCHAR2(1)		Indicates whether this is the default hierarchy for the analytic view dimension in the analytic view (Y) or not (N)
ORDER_NUM	NUMBER	NOT NULL	Order of the hierarchy in the list of hierarchies in the analytic view
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ANALYTIC_VIEW_HIERS"
- "USER_ANALYTIC_VIEW_HIERS"

3.42 ALL_ANALYTIC_VIEW_HIERS_AE

ALL_ANALYTIC_VIEW_HIERS_AE describes the hierarchies in the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_HIERS_AE describes the hierarchies in all analytic views (across all editions) in the database.

- USER_ANALYTIC_VIEW_HIERS_AE describes the hierarchies in the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view hierarchy
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
HIER_OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
HIER_ALIAS	VARCHAR2(128)		Alias specified for the hierarchy
IS_DEFAULT	VARCHAR2(1)		Indicates whether this is the default hierarchy for the analytic view dimension in the analytic view (Y) or not (N)
ORDER_NUM	NUMBER	NOT NULL	Order of the hierarchy in the list of hierarchies in the analytic view
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

See Also:

- "DBA_ANALYTIC_VIEW_HIERS_AE"
- "USER_ANALYTIC_VIEW_HIERS_AE"

3.43 ALL_ANALYTIC_VIEW_KEYS

ALL_ANALYTIC_VIEW_KEYS describes the key columns of the attribute dimensions in the analytic views accessible to the current user.

The keys reference attributes of the attribute dimensions of the analytic view.

Related Views

- DBA_ANALYTIC_VIEW_KEYS describes the key columns of the attribute dimensions in all analytic views in the database.
- USER_ANALYTIC_VIEW_KEYS describes the key columns of the attribute dimensions in the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of analytic view

Column	Datatype	NULL	Description
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
AV_KEY_TABLE_ALIAS	VARCHAR2(128)		Table alias of the key column
AV_KEY_COLUMN	VARCHAR2(128)	NOT NULL	Name of the column for the key
REF_DIMENSION_ATTR	VARCHAR2(128)		Name of the referenced attribute dimension attribute
ORDER_NUM	NUMBER	NOT NULL	Order number of the key in the list of keys in the analytic view
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ANALYTIC_VIEW_KEYS"
- "USER_ANALYTIC_VIEW_KEYS"

3.44 ALL_ANALYTIC_VIEW_KEYS_AE

ALL_ANALYTIC_VIEW_KEYS_AE describes the key columns of the attribute dimensions in the analytic views (across all editions) accessible to the current user.

The keys reference attributes of the attribute dimensions of the analytic view.

Related Views

- DBA_ANALYTIC_VIEW_KEYS_AE describes the key columns of the attribute dimensions in all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEW_KEYS_AE describes the key columns of the attribute dimensions in the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
AV_KEY_TABLE_ALIAS	VARCHAR2(128)		Table alias of the key column
AV_KEY_COLUMN	VARCHAR2(128)	NOT NULL	Name of the column for the key

Column	Datatype	NULL	Description
REF_DIMENSION_ATTR	VARCHAR2(128)		Name of the referenced attribute dimension attribute
ORDER_NUM	NUMBER	NOT NULL	Order number of the key in the list of keys in the analytic view
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

See Also:

- "DBA_ANALYTIC_VIEW_KEYS_AE"
- "USER_ANALYTIC_VIEW_KEYS_AE"

3.45 ALL_ANALYTIC_VIEW_LEVEL_CLASS

ALL_ANALYTIC_VIEW_LEVEL_CLASS describes the level classifications of the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_LEVEL_CLASS describes the level classifications of all analytic views in the database.
- USER_ANALYTIC_VIEW_LEVEL_CLASS describes the level classifications of the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the analytic view dimension in the analytic view
HIER_ALIAS	VARCHAR2(128)		Alias of the hierarchy in the analytic view
LEVEL_NAME	VARCHAR2(128)	NOT NULL	Name of the level in the analytic view
CLASSIFICATION	VARCHAR2(128)		Classification associated with the level
VALUE	CLOB		Value of the classification, or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification, or NULL if not specified

Column	Datatype	NULL	Description
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the level
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ANALYTIC_VIEW_LEVEL_CLASS"
- "USER_ANALYTIC_VIEW_LEVEL_CLASS"

3.46 ALL_ANALYTIC_VIEW_LEVELS

ALL_ANALYTIC_VIEW_LEVELS describes the levels in the hierarchies in the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_LEVELS describes the levels in the hierarchies in all analytic views in the database.
- USER_ANALYTIC_VIEW_LEVELS describes the levels in the hierarchies in the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the analytic view
HIER_ALIAS	VARCHAR2(128)		Alias of the hierarchy in the attribute dimension in the analytic view
LEVEL_NAME	VARCHAR2(128)	NOT NULL	Name of the level within the attribute dimension in the analytic view
ORDER_NUM	NUMBER	NOT NULL	Order number of the level in the list of levels in the analytic view hierarchy
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

> **See Also:**
>
> - "DBA_ANALYTIC_VIEW_LEVELS"
> - "USER_ANALYTIC_VIEW_LEVELS"

3.47 ALL_ANALYTIC_VIEW_LEVELS_AE

`ALL_ANALYTIC_VIEW_LEVELS_AE` describes the levels in the hierarchies in the analytic views (across all editions) accessible to the current user.

Related Views

- `DBA_ANALYTIC_VIEW_LEVELS_AE` describes the levels in the hierarchies in all analytic views (across all editions) in the database.
- `USER_ANALYTIC_VIEW_LEVELS_AE` describes the levels in the hierarchies in the analytic views (across all editions) owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
`OWNER`	`VARCHAR2(128)`	`NOT NULL`	Owner of the analytic view
`ANALYTIC_VIEW_NAME`	`VARCHAR2(128)`	`NOT NULL`	Name of the analytic view
`DIMENSION_ALIAS`	`VARCHAR2(128)`		Alias of the attribute dimension in the analytic view
`HIER_ALIAS`	`VARCHAR2(128)`		Alias of the hierarchy in the attribute dimension in the analytic view
`LEVEL_NAME`	`VARCHAR2(128)`	`NOT NULL`	Name of the level within the attribute dimension in the analytic view
`ORDER_NUM`	`NUMBER`	`NOT NULL`	Order number of the level in the list of levels in the analytic view hierarchy
`ORIGIN_CON_ID`	`NUMBER`		The ID of the container where the data originates. Possible values include: • `0`: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
`EDITION_NAME`	`VARCHAR2(128)`		Name of the application edition where the analytic view is defined

> **See Also:**
>
> - "DBA_ANALYTIC_VIEW_LEVELS_AE"
> - "USER_ANALYTIC_VIEW_LEVELS_AE"

3.48 ALL_ANALYTIC_VIEW_LVL_CLS

ALL_ANALYTIC_VIEW_LVL_CLS is identical to ALL_ANALYTIC_VIEW_LEVEL_CLASS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_LEVEL_CLASS"

3.49 ALL_ANALYTIC_VIEW_LVL_CLS_AE

ALL_ANALYTIC_VIEW_LVL_CLS_AE describes the level classifications of the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_LVL_CLS_AE describes the level classifications of all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEW_LVL_CLS_AE describes the level classifications of the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of analytic view
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the analytic view dimension in the analytic view
HIER_ALIAS	VARCHAR2(128)		Alias of the hierarchy in the analytic view
LEVEL_NAME	VARCHAR2(128)	NOT NULL	Name of the level in the analytic view
CLASSIFICATION	VARCHAR2(128)		Classification associated with the level
VALUE	CLOB		Value of the classification, or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification, or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the level
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

> **See Also:**
>
> - "DBA_ANALYTIC_VIEW_LVL_CLS_AE"
> - "USER_ANALYTIC_VIEW_LVL_CLS_AE"

3.50 ALL_ANALYTIC_VIEW_LVLGRPS

ALL_ANALYTIC_VIEW_LVLGRPS describes the analytic view measure and level groups of the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_LVLGRPS describes the analytic view measure and level groups of all analytic views in the database.
- USER_ANALYTIC_VIEW_LVLGRPS describes the analytic view measure and level groups of the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)		Name of the analytic view
CACHE_TYPE	VARCHAR2(128)		Type of the materialized view; one of the following: • DYNAMIC • MATERIALIZED (the default value)
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the group
HIER_ALIAS	VARCHAR2(128)		Alias of the hierarchy associated with the attribute dimension in the group
LEVEL_NAME	VARCHAR2(128)		Name of the level in the hierarchy in the group
MEASURE_NAME	VARCHAR2(128)		Names of the measures in the group
MAT_TABLE_OWNER	VARCHAR2(128)		If the schema for an aggregation table is specified for the analytic view, then the schema owner; otherwise NULL
MAT_TABLE_NAME	VARCHAR2(128)		If an aggregation table is specified for an analytic view, then the name of the materialized table; otherwise NULL
AV_LVLGRP_ORDER	NUMBER		Order of the groups in the analytic view
LEVEL_MEAS_ORDER	NUMBER		Order of the levels and measures in the group
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

> **See Also:**
>
> - "DBA_ANALYTIC_VIEW_LVLGRPS"
> - "USER_ANALYTIC_VIEW_LVLGRPS"

3.51 ALL_ANALYTIC_VIEW_LVLGRPS_AE

ALL_ANALYTIC_VIEW_LVLGRPS_AE describes the analytic view measure and level groups of the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_LVLGRPS_AE describes the analytic view measure and level groups of all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEW_LVLGRPS_AE describes the analytic view measure and level groups of the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)		Name of the analytic view
CACHE_TYPE	VARCHAR2(128)		Type of the materialized view; one of the following: • DYNAMIC • MATERIALIZED (the default value)
DIMENSION_ALIAS	VARCHAR2(128)		Alias of the attribute dimension in the group
HIER_ALIAS	VARCHAR2(128)		Alias of the hierarchy associated with the attribute dimension in the group
LEVEL_NAME	VARCHAR2(128)		Name of the level in the hierarchy in the group
MEASURE_NAME	VARCHAR2(128)		Names of the measures in the group
MAT_TABLE_OWNER	VARCHAR2(128)		If the schema for an aggregation table is specified for the analytic view, then the schema owner; otherwise NULL
MAT_TABLE_NAME	VARCHAR2(128)		If an aggregation table is specified for an analytic view, then the name of the materialized table; otherwise NULL
AV_LVLGRP_ORDER	NUMBER		Order of the groups in the analytic view
LEVEL_MEAS_ORDER	NUMBER		Order of the levels and measures in the group
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

See Also:

- "DBA_ANALYTIC_VIEW_LVLGRPS_AE"
- "USER_ANALYTIC_VIEW_LVLGRPS_AE"

3.52 ALL_ANALYTIC_VIEW_MEAS_CLASS

ALL_ANALYTIC_VIEW_MEAS_CLASS describes the classifications of the measures of the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_MEAS_CLASS describes the classifications of the measures of all analytic views in the database.
- USER_ANALYTIC_VIEW_MEAS_CLASS describes the classifications of the measures of the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
MEASURE_NAME	VARCHAR2(128)		Name of the measure associated with the classification
CLASSIFICATION	VARCHAR2(128)		Classification associated with the measure of the analytic view
VALUE	CLOB		Value of the classification, or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification, or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the measure
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ANALYTIC_VIEW_MEAS_CLASS"
- "USER_ANALYTIC_VIEW_MEAS_CLASS"

3.53 ALL_ANALYTIC_VIEW_MEAS_CLS

ALL_ANALYTIC_VIEW_MEAS_CLS is identical to ALL_ANALYTIC_VIEW_MEAS_CLASS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_MEAS_CLASS"

3.54 ALL_ANALYTIC_VIEW_MEAS_CLS_AE

ALL_ANALYTIC_VIEW_MEAS_CLS_AE describes the classifications of the measures of the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEW_MEAS_CLS_AE describes the classifications of the measures of all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEW_MEAS_CLS_AE describes the classifications of the measures of the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
MEASURE_NAME	VARCHAR2(128)		Name of the measure associated with the classification
CLASSIFICATION	VARCHAR2(128)		Classification associated with the measure of the analytic view
VALUE	CLOB		Value of the classification, or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification, or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the measure
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

See Also:

- "DBA_ANALYTIC_VIEW_MEAS_CLS_AE"
- "USER_ANALYTIC_VIEW_MEAS_CLS_AE"

3.55 ALL_ANALYTIC_VIEWS

ALL_ANALYTIC_VIEWS describes the analytic views accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEWS describes all analytic views in the database.
- USER_ANALYTIC_VIEWS describes the analytic views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the fact table or view on which the analytic view is defined
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the fact table or view on which the analytic view is defined
TABLE_ALIAS	VARCHAR2(128)		Alias of the fact table or view on which the analytic view is defined; the default is TABLE_NAME
IS_REMOTE	VARCHAR2(1)		Indicates whether the source is a remote table. The values are: • Y - Remote table • N - Local table
DEFAULT_AGGR	VARCHAR2(128)		Default aggregation of the analytic view
DEFAULT_AGGR_GROUP_NAME	VARCHAR2(128)	NOT NULL	Always DEFAULT_AGGREGATION$ at present
DEFAULT_MEASURE	VARCHAR2(128)		Name of the default measure of the analytic view
COMPILE_STATE	VARCHAR2(7)		Compile status of the analytic view: • VALID • INVALID
DYN_ALL_CACHE	VARCHAR2(1)		The value of this column is always N
QUERY_TRANSFORM_ENABLED	VARCHAR2(1)		Indicates whether query transformation is enabled for the analytic view (Y) or not (N)
QUERY_TRANSFORM_RELY	VARCHAR2(1)		Indicates whether the RELY option is specified for the query transformation (Y) or not (N)

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

> **See Also:**
>
> - "DBA_ANALYTIC_VIEWS"
> - "USER_ANALYTIC_VIEWS"

3.56 ALL_ANALYTIC_VIEWS_AE

ALL_ANALYTIC_VIEWS_AE describes the analytic views (across all editions) accessible to the current user.

Related Views

- DBA_ANALYTIC_VIEWS_AE describes all analytic views (across all editions) in the database.
- USER_ANALYTIC_VIEWS_AE describes the analytic views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic view
ANALYTIC_VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the analytic view
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the fact table or view on which the analytic view is defined
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the fact table or view on which the analytic view is defined
TABLE_ALIAS	VARCHAR2(128)		Alias of the fact table or view on which the analytic view is defined; the default is TABLE_NAME
IS_REMOTE	VARCHAR2(1)		Indicates whether the source is a remote table. The values are: • Y - Remote table • N - Local table
DEFAULT_AGGR	VARCHAR2(128)		Default aggregation of the analytic view
DEFAULT_AGGR_GROUP_NAME	VARCHAR2(128)	NOT NULL	Always DEFAULT_AGGREGATION$ at present
DEFAULT_MEASURE	VARCHAR2(128)		Name of the default measure of the analytic view

Column	Datatype	NULL	Description
COMPILE_STATE	VARCHAR2(7)		Compile status of the analytic view: • VALID • INVALID
DYN_ALL_CACHE	VARCHAR2(1)		The value of this column is always N
QUERY_TRANSFORM_ENABLED	VARCHAR2(1)		Indicates whether query transformation is enabled for the analytic view (Y) or not (N)
QUERY_TRANSFORM_RELY	VARCHAR2(1)		Indicates whether the RELY option is specified for the query transformation (Y) or not (N)
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the analytic view is defined

See Also:

- "DBA_ANALYTIC_VIEWS_AE"
- "USER_ANALYTIC_VIEWS_AE"

3.57 ALL_ANNOTATION_VALUES

ALL_ANNOTATION_VALUES displays the values for schema annotations accessible to the current user.

Related Views

- DBA_ANNOTATION_VALUES displays the values for all schema annotations in the database.
- USER_ANNOTATION_VALUES displays the values for schema annotations owned by the current user. This view does not display the ANNOTATION_OWNER column.

Column	Datatype	NULL	Description
ANNOTATION_OWNER	VARCHAR2(128)	NOT NULL	Annotation owner
ANNOTATION_NAME	VARCHAR2(1024)	NOT NULL	Annotation name
ANNOTATION_VALUE	VARCHAR2(4000)		Annotation value

Note:

This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_ANNOTATION_VALUES"
> - "USER_ANNOTATION_VALUES"

3.58 ALL_ANNOTATIONS

ALL_ANNOTATIONS displays schema annotations accessible to the current user.

Related Views

- DBA_ANNOTATIONS displays all schema annotations in the database.
- USER_ANNOTATIONS displays schema annotations owned by the current user. This view does not display the ANNOTATION_OWNER column.

Column	Datatype	NULL	Description
ANNOTATION_OWNER	VARCHAR2(128)	NOT NULL	Annotation owner
ANNOTATION_NAME	VARCHAR2(1024)	NOT NULL	Annotation name

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_ANNOTATIONS"
> - "USER_ANNOTATIONS"

3.59 ALL_ANNOTATIONS_USAGE

ALL_ANNOTATIONS_USAGE provides usage information about schema annotations accessible to the current user.

Related Views

- DBA_ANNOTATIONS_USAGE provides usage information about all schema annotations in the database.
- USER_ANNOTATIONS_USAGE provides usage information about schema annotations owned by the current user. This view does not display the ANNOTATION_OWNER column.

Column	Datatype	NULL	Description
OBJECT_NAME	VARCHAR2(128)		Object name
OBJECT_TYPE	VARCHAR2(9)		Object type
COLUMN_NAME	VARCHAR2(128)		If the annotation is specified for a table column, view column, or domain column, the name of the column; otherwise NULL
DOMAIN_NAME	VARCHAR2(128)		If the annotation is carried over from a domain or a domain column, the name of the domain; otherwise NULL Note that domains carry over their annotations to objects that reference them.
DOMAIN_OWNER	VARCHAR2(128)		If the annotation is carried over from a domain or domain column, the owner of the domain; otherwise NULL Note that domains carry over their annotations to objects that reference them.
ANNOTATION_OWNER	VARCHAR2(128)		Annotation owner
ANNOTATION_NAME	VARCHAR2(1024)		Annotation name
ANNOTATION_VALUE	VARCHAR2(4000)		Optional annotation value A NULL value is possible when the annotation does not require a value, that is, when the annotation is defined solely by its name.

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_ANNOTATIONS_USAGE"
- "USER_ANNOTATIONS_USAGE"

3.60 ALL_APPLY

ALL_APPLY displays information about the apply processes that dequeue messages from queues accessible to the current user.

Related View

DBA_APPLY displays information about all apply processes in the database.

Column	Datatype	NULL	Description
APPLY_NAME	VARCHAR2(128)	NOT NULL	Name of the apply process

Column	Datatype	NULL	Description
QUEUE_NAME	VARCHAR2(128)	NOT NULL	Name of the queue from which the apply process dequeues
QUEUE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the queue from which the apply process dequeues
APPLY_CAPTURED	VARCHAR2(3)		Indicates whether the apply process applies captured messages (YES) or user-enqueued messages (NO)
RULE_SET_NAME	VARCHAR2(128)		Name of the positive rule set used by the apply process for filtering
RULE_SET_OWNER	VARCHAR2(128)		Owner of the positive rule set used by the apply process for filtering
APPLY_USER	VARCHAR2(128)		User who is applying messages
APPLY_DATABASE_LINK	VARCHAR2(128)		Database link to which changes are applied. If NULL, then changes are applied to the local database.
APPLY_TAG	RAW(2000)		Tag associated with redo log records that are generated when changes are made by the apply process
DDL_HANDLER	VARCHAR2(98)		Name of the user-specified data definition language (DDL) handler, which handles DDL logical change records (LCRs)
PRECOMMIT_HANDLER	VARCHAR2(98)		Name of the user-specified pre-commit handler
MESSAGE_HANDLER	VARCHAR2(98)		Name of the user-specified procedure that handles dequeued messages other than logical change records (LCRs)
STATUS	VARCHAR2(8)		Status of the apply process: • DISABLED • ENABLED • ABORTED
MAX_APPLIED_MESSAGE_NUMBER	NUMBER		System change number (SCN) corresponding to the apply process high watermark for the last time the apply process was stopped using the DBMS_APPLY_ADM.STOP_APPLY procedure with the force parameter set to false. The apply process high watermark is the SCN beyond which no messages have been applied.
NEGATIVE_RULE_SET_NAME	VARCHAR2(128)		Name of the negative rule set used by the apply process for filtering
NEGATIVE_RULE_SET_OWNER	VARCHAR2(128)		Owner of the negative rule set used by the apply process for filtering
STATUS_CHANGE_TIME	DATE		Time that the STATUS of the apply process was changed
ERROR_NUMBER	NUMBER		Error number if the apply process was terminated
ERROR_MESSAGE	VARCHAR2(4000)		Error message if the apply process was terminated
MESSAGE_DELIVERY_MODE	VARCHAR2(10)		Reserved for internal use

Column	Datatype	NULL	Description
PURPOSE	VARCHAR2(19)		Purpose of the apply process: • GoldenGate Apply - An Oracle GoldenGate Inbound server configured by Oracle GoldenGate integrated replicat • XStream Out - An XStream outbound server in an XStream Out configuration • XStream In - An XStream inbound server in an XStream In configuration • AUDIT VAULT - An apply process in an audit vault configuration • CHANGE DATA CAPTURE - An apply process in a change data capture configuration
LCRID_VERSION	NUMBER		LCR ID format currently being used

See Also:

- "DBA_APPLY"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLY_ADM.STOP_APPLY procedure
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_XSTREAM_ADM.ENABLE_GG_XSTREAM_FOR_STREAMS procedure

3.61 ALL_APPLY_CHANGE_HANDLERS

ALL_APPLY_CHANGE_HANDLERS displays information about the change handlers on the tables accessible to the current user.

Related View

DBA_APPLY_CHANGE_HANDLERS displays information about the change handlers on all tables in the database.

Column	Datatype	NULL	Description
CHANGE_TABLE_OWNER	VARCHAR2(128)		Owner of the change table
CHANGE_TABLE_NAME	VARCHAR2(128)		Name of the change table
SOURCE_TABLE_OWNER	VARCHAR2(128)		Owner of the source table
SOURCE_TABLE_NAME	VARCHAR2(128)		Name of the source table
HANDLER_NAME	VARCHAR2(128)		Name of the statement-based change handler
CAPTURE_VALUES	VARCHAR2(3)		Indicates whether to capture the old (OLD), new (NEW), or both (*) values
APPLY_NAME	VARCHAR2(128)		Name of the apply process

Column	Datatype	NULL	Description
OPERATION_NAME	VARCHAR2(10)		Name of the DML operation to which the DML handler is set: • DEFAULT • INSERT • UPDATE • DELETE • LOB_UPDATE
CREATION_TIME	TIMESTAMP(6)		Change handler creation time
MODIFICATION_TIME	TIMESTAMP(6)		Change handler modification time

> **See Also:**
>
> "DBA_APPLY_CHANGE_HANDLERS"

3.62 ALL_APPLY_CONFLICT_COLUMNS

ALL_APPLY_CONFLICT_COLUMNS displays information about the conflict handlers on the tables accessible to the current user.

Related View

DBA_APPLY_CONFLICT_COLUMNS displays information about the conflict handlers on all tables in the database.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)		Owner of the object on which the update conflict handler is defined
OBJECT_NAME	VARCHAR2(128)		Name of the object on which the update conflict handler is defined
METHOD_NAME	VARCHAR2(92)		Name of the update conflict handler used to resolve conflicts
RESOLUTION_COLUMN	VARCHAR2(4000)		Name of the column used to resolve conflicts
COLUMN_NAME	VARCHAR2(128)		Name of a column in the column list for the update conflict handler
APPLY_DATABASE_LINK	VARCHAR2(128)		Database link to which changes are applied. If null, then changes are applied to the local database.

> **See Also:**
>
> "DBA_APPLY_CONFLICT_COLUMNS"

3.63 ALL_APPLY_DML_CONF_HANDLERS

ALL_APPLY_DML_CONF_HANDLERS provides details about DML conflict handlers on objects visible to the current user.

Related View

DBA_APPLY_DML_CONF_HANDLERS provides details about DML conflict handlers.

Column	Datatype	NULL	Description
APPLY_NAME	VARCHAR2(128)		Name of the apply process
OBJECT_OWNER	VARCHAR2(128)		Owner of the target object
OBJECT_NAME	VARCHAR2(128)		Name of the target object
SOURCE_OBJECT_OWNER	VARCHAR2(128)		Source database owner of the object
SOURCE_OBJECT_NAME	VARCHAR2(128)		Source database name of the object
COMMAND_TYPE	VARCHAR2(6)		Type of the DML operation: INSERT, UPDATE, or DELETE
CONFLICT_TYPE	VARCHAR2(11)		Type of conflict: • ROW EXISTS • ROW MISSING
METHOD_NAME	VARCHAR2(9)		Method used for resolving the error, depending on the conflict type: • OVERWRITE • RECORD • IGNORE • MAXIMUM • MINIMUM • DELTA
CONFLICT_HANDLER_NAME	VARCHAR2(128)		Name of the conflict handler
RESOLUTION_COLUMN	VARCHAR2(128)		Name of the column used to resolve the conflict for MAXIMUM, MINIMUM, and DELTA
SET_BY	VARCHAR2(10)		Entity that set up the handler: • USER • GOLDENGATE

See Also:

"DBA_APPLY_DML_CONF_HANDLERS"

3.64 ALL_APPLY_DML_HANDLERS

ALL_APPLY_DML_HANDLERS displays information about the DML handlers on the tables accessible to the current user.

Related View

DBA_APPLY_DML_HANDLERS displays information about the DML handlers on all tables in the database.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the object on which the DML handler is specified
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object on which the DML handler is specified
OPERATION_NAME	VARCHAR2(13)		Name of the DML operation for which the DML handler is used: • DEFAULT • INSERT • UPDATE • DELETE • LOB_UPDATE • ASSEMBLE_LOBS
USER_PROCEDURE	VARCHAR2(98)		Name of the user-specified DML handler, which handles row logical change records that contain the DML operation in the OPERATION_NAME column on the object
ERROR_HANDLER	VARCHAR2(1)		Indicates whether the DML handler handles only the relevant row logical change records that result in apply errors (Y) or all relevant row logical change records (N)
APPLY_DATABASE_LINK	VARCHAR2(128)		Database link to which changes are applied. If null, then changes are applied to the local database.
APPLY_NAME	VARCHAR2(128)		Name of the apply process for the given object
ASSEMBLE_LOBS	VARCHAR2(1)		Indicates whether LOB assembly is used for LOB columns in logical change records (LCRs) processed by the handler (Y) or not (N) LOB assembly combines multiple LCRs for a LOB column resulting from a single row change into one row LCR before passing the LCR to the handler.
SET_BY	VARCHAR2(10)		Entity that set up the handler. Possible values include: • GOLDENGATE • USER

> **See Also:**
>
> - "DBA_APPLY_DML_HANDLERS"
> - *Oracle Database XStream Guide* for more information about DML handlers in an Oracle XStream environment

3.65 ALL_APPLY_ENQUEUE

ALL_APPLY_ENQUEUE displays information about the apply enqueue actions for the rules where the destination queue exists and is accessible to the current user.

Related View

DBA_APPLY_ENQUEUE displays information about the apply enqueue actions for all rules in the database.

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2(128)	NOT NULL	Name of the rule
DESTINATION_QUEUE_NAME	VARCHAR2(4000)		Name of the queue where events satisfying the rule will be enqueued

> **See Also:**
>
> "DBA_APPLY_ENQUEUE"

3.66 ALL_APPLY_ERROR

ALL_APPLY_ERROR displays information about the error transactions generated by the apply processes that dequeue messages from queues accessible to the current user.

Related Views

- DBA_APPLY_ERROR displays information about the error transactions generated by all apply processes in the database.
- USER_APPLY_ERROR displays information about the error transactions generated by apply processes visible to the current user. This view does not display the SOURCE_ROOT_NAME column.

Column	Datatype	NULL	Description
APPLY_NAME	VARCHAR2(128)		Name of the apply process at the local database which processed the transaction
QUEUE_NAME	VARCHAR2(128)		Name of the queue at the local database from which the transaction was dequeued

Column	Datatype	NULL	Description
QUEUE_OWNER	VARCHAR2(128)		Owner of the queue at the local database from which the transaction was dequeued
LOCAL_TRANSACTION_ID	VARCHAR2(22)		Local transaction ID for the error transaction
SOURCE_DATABASE	VARCHAR2(128)		Database where the transaction originated
SOURCE_TRANSACTION_ID	VARCHAR2(128)		Original transaction ID at the source database
SOURCE_COMMIT_SCN	NUMBER		Original commit system change number (SCN) for the transaction at the source database
MESSAGE_NUMBER	NUMBER		Identifier for the message in the transaction that raised an error
ERROR_NUMBER	NUMBER		Error number of the error raised by the transaction
ERROR_MESSAGE	VARCHAR2(4000)		Error message of the error raised by the transaction
RECIPIENT_ID	NUMBER		User ID of the original user that applied the transaction
RECIPIENT_NAME	VARCHAR2(128)		Name of the original user that applied the transaction
MESSAGE_COUNT	NUMBER		Total number of messages inside the error transaction
ERROR_CREATION_TIME	DATE		Time that the error was created
SOURCE_COMMIT_POSITION	RAW(64)		Original commit position for the transaction
ERROR_TYPE	VARCHAR2(11)		NULL if the apply process can access all of the LCRs in the error transaction. EAGER ERROR if the apply process cannot access all of the LCRs in the error transaction. This error type typically means that the apply process was applying LCRs in a large transaction. When the ERROR_TYPE is EAGER ERROR, manage the error transaction using the instructions in *Oracle Database XStream Guide*. RECORD LCR indicates that a single LCR has been recorded as requested by user-specified error handling configuration RECORD TXN NO LCRS indicates that the identified transaction encountered an error and only the transaction ID is recorded as requested by user-specified error handling configuration RECORD TXN WITH LCRS indicates that the identified transaction encountered and error. The entire transaction is recorded as requested by user-specified error handling configuration. UNHANDLED ERRORS NO LCR indicates that the identified transaction encountered an error and there was no error handling specified for this handler. No LCRs are recorded for this transaction. DISCARDED is used to mark recorded and discarded LCRs.
SOURCE_ROOT_NAME	VARCHAR2(128)		The global name of the source root database
ERROR_POSITION	RAW(64)		LCR position at which the error occurred

See Also:

- "DBA_APPLY_ERROR"
- "USER_APPLY_ERROR"
- *Oracle Database XStream Guide* for information on how to display detailed information about apply errors

3.67 ALL_APPLY_ERROR_MESSAGES

`ALL_APPLY_ERROR_MESSAGES` displays information about the individual messages in an error transaction generated by the apply processes that dequeue messages from queues accessible to the current user.

For XStream inbound servers, each message in an error transaction is a logical change record (LCR).

Note:

- Messages that were spilled from memory to hard disk do not appear in this view.
- This view does not contain information related to XStream outbound servers.

Related View

`DBA_APPLY_ERROR_MESSAGES` displays information about the individual messages in all of the error transactions generated by all apply processes in the database.

Column	Datatype	NULL	Description
MESSAGE_ID	RAW(16)		Unique identifier of the message stored in the error queue
LOCAL_TRANSACTION_ID	VARCHAR2(22)		Local transaction ID for the error transaction
TRANSACTION_MESSAGE_NUMBER	NUMBER		Message number of the message that raised the error. The message number is a sequence number for the messages in the transaction, starting with 1.
ERROR_NUMBER	NUMBER		Error number of the error raised by the transaction. The error number is populated only for the LCR that raised the error. This field is NULL for the other LCRs in the transaction.
ERROR_MESSAGE	VARCHAR2(4000)		Error message of the error raised by the transaction. The error message is populated only for the LCR that raised the error. This field is NULL for the other LCRs in the transaction.
SOURCE_OBJECT_OWNER	VARCHAR2(128)		Owner of the object at the source database
SOURCE_OBJECT_NAME	VARCHAR2(128)		Name of the object at the source database

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)		Owner of the target table
OBJECT_NAME	VARCHAR2(128)		Object name of the target table
PRIMARY_KEY	VARCHAR2(4000)		Primary key of the table row that caused the source transaction to fail at the target
POSITION	RAW(64)		The LCR position
OPERATION	VARCHAR2(100)		The DML or DDL operation represented in the LCR
CONFLICT_TYPE	VARCHAR2(18)		Conflict type. Possible values: • INSERT ROW EXISTS: DML operation is INSERT and a row already exists with the specified key value. • UPDATE ROW EXISTS: DML operation is UPDATE. A row with the specified key exists but has conflicting values for some columns. • UPDATE ROW MISSING: DML operation is UPDATE and no row with the specified key value exists. • DELETE ROW EXISTS: DML operation is DELETE. A row with the specified key exists but has conflicting values for some columns • DELETE ROW MISSING: DML operation is DELETE and no row with the specified key value exists.
APPLIED_STATE	VARCHAR2(22)		Conflict applied state. Possible values: • WON: Incoming LCR was applied in its entirety • PARTIAL: Incoming LCR was applied for one or more conflict groups • LOST: Incoming LCR was not applied • SITE PRIORITY, WON: Site priority resolution was in effect and incoming LCR was applied in its entirety • SITE PRIORITY, PARTIAL: Site priority resolution was in effect and incoming LCR was applied for one or more conflict groups • SITE PRIORITY, LOST: Site priority resolution was in effect and incoming LCR was not applied
SEQ#	NUMBER		Trail file number (Oracle GoldenGate)
RBA	NUMBER		Position with Trail file (Oracle GoldenGate)
CONFLICT_INFO	VARCHAR2(4000)		Identifies the conflict group information
SOURCE_PACKAGE_NAME	VARCHAR2(128)		Package name of the source for procedural replication
PACKAGE_NAME	VARCHAR2(128)		Package name of the destination for procedural replication
MESSAGE	CLOB		The content of the LCR. Content includes column name and value for old and/or new values in DML LCRs. For DDL LCRs, the content is the text of the DDL SQL.

See Also:

- "DBA_APPLY_ERROR_MESSAGES"
- *Oracle Database XStream Guide* for information on managing eager errors encountered by an inbound server

3.68 ALL_APPLY_EXECUTE

ALL_APPLY_EXECUTE displays information about the apply execute actions for the rules visible to the current user.

Related View

DBA_APPLY_EXECUTE displays information about the apply execute actions for all rules in the database.

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2(128)	NOT NULL	Name of the rule
EXECUTE_EVENT	VARCHAR2(2)		Indicates whether the event satisfying the rule is executed

See Also:

"DBA_APPLY_EXECUTE"

3.69 ALL_APPLY_HANDLE_COLLISIONS

ALL_APPLY_HANDLE_COLLISIONS provides details about apply handlers for collisions on objects visible to the user at the table level.

Related View

DBA_APPLY_HANDLE_COLLISIONS provides details about apply handlers for collisions at the table level.

Column	Datatype	NULL	Description
APPLY_NAME	VARCHAR2(128)	NOT NULL	Name of the apply process
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the target object
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the target object
SOURCE_OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Source database owner of the object
SOURCE_OBJECT_NAME	VARCHAR2(128)	NOT NULL	Source database name of the object
ENABLED	VARCHAR2(1)	NOT NULL	State of the collision handlers: Y for enabled, N for disabled

Column	Datatype	NULL	Description
SET_BY	VARCHAR2(10)		Entity that set up the handler: • USER • GOLDENGATE

> **See Also:**
>
> "DBA_APPLY_HANDLE_COLLISIONS"

3.70 ALL_APPLY_INSTANTIATED_GLOBAL

ALL_APPLY_INSTANTIATED_GLOBAL displays information for the current user about databases for which an instantiation SCN has been set.

Related View

DBA_APPLY_INSTANTIATED_GLOBAL displays information about databases for which an instantiation SCN has been set.

Column	Datatype	NULL	Description
SOURCE_DATABASE	VARCHAR2(128)	NOT NULL	Name of the database that was instantiated
INSTANTIATION_SCN	NUMBER		Instantiation SCN for the database. Only changes committed after this SCN are applied by an apply process.
APPLY_DATABASE_LINK	VARCHAR2(128)		Database link to which changes are applied. If null, then changes are applied to the local database.
SOURCE_ROOT_NAME	VARCHAR2(128)		The global name of the source root database

> **See Also:**
>
> "DBA_APPLY_INSTANTIATED_GLOBAL"

3.71 ALL_APPLY_INSTANTIATED_OBJECTS

ALL_APPLY_INSTANTIATED_OBJECTS displays information about objects accessible to the current user for which an instantiation SCN has been set.

Related View

DBA_APPLY_INSTANTIATED_OBJECTS displays information about objects for which an instantiation SCN has been set.

Column	Datatype	NULL	Description
SOURCE_DATABASE	VARCHAR2(128)	NOT NULL	Name of the database where the object originated
SOURCE_OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the object at the source database
SOURCE_OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object at the source database
SOURCE_OBJECT_TYPE	VARCHAR2(11)		Type of the object at the source database
INSTANTIATION_SCN	NUMBER		Instantiation SCN for the object. Only changes committed after this SCN are applied by an apply process.
IGNORE_SCN	NUMBER		SCN below which the instantiation SCN cannot be set. This value corresponds to the SCN value at the source database at the time when the object was prepared for instantiation.
APPLY_DATABASE_LINK	VARCHAR2(128)		Database link to which changes are applied. If null, then changes are applied to the local database.
SOURCE_ROOT_NAME	VARCHAR2(128)		The global name of the source root database

See Also:

"DBA_APPLY_INSTANTIATED_OBJECTS"

3.72 ALL_APPLY_INSTANTIATED_SCHEMAS

ALL_APPLY_INSTANTIATED_SCHEMAS displays information about schemas accessible to the current user for which an instantiation SCN has been set.

Related View

DBA_APPLY_INSTANTIATED_SCHEMAS displays information about schemas for which an instantiation SCN has been set.

Column	Datatype	NULL	Description
SOURCE_DATABASE	VARCHAR2(128)	NOT NULL	Name of the database where the schema originated
SOURCE_SCHEMA	VARCHAR2(128)		Name of the schema at the source database
INSTANTIATION_SCN	NUMBER		Instantiation SCN for the schema. Only changes committed after this SCN are applied by an apply process.
APPLY_DATABASE_LINK	VARCHAR2(128)		Database link to which changes are applied. If null, then changes are applied to the local database.
SOURCE_ROOT_NAME	VARCHAR2(128)		The global name of the source root database

> **See Also:**
>
> "DBA_APPLY_INSTANTIATED_SCHEMAS"

3.73 ALL_APPLY_KEY_COLUMNS

ALL_APPLY_KEY_COLUMNS displays information about the substitute key columns for the tables accessible to the current user. Substitute key columns are set using the DBMS_APPLY_ADM.SET_KEY_COLUMNS procedure.

Related View

DBA_APPLY_KEY_COLUMNS displays information about the substitute key columns for all tables in the database.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the object on which substitute key columns are set
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object on which substitute key columns are set
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Column name of a column specified as a substitute key column
APPLY_DATABASE_LINK	VARCHAR2(128)		Database link to which changes are applied. If null, then changes are applied to the local database.

> **See Also:**
>
> - "DBA_APPLY_KEY_COLUMNS"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLY_ADM.SET_KEY_COLUMNS procedure

3.74 ALL_APPLY_PARAMETERS

ALL_APPLY_PARAMETERS displays information about the parameters for the apply processes that dequeue events from queues accessible to the current user.

Related View

DBA_APPLY_PARAMETERS displays information about the parameters for all apply processes in the database.

Column	Datatype	NULL	Description
APPLY_NAME	VARCHAR2(128)	NOT NULL	Name of the apply process
PARAMETER	VARCHAR2(128)	NOT NULL	Name of the parameter

Column	Datatype	NULL	Description
VALUE	VARCHAR2(4000)		Parameter value
SET_BY_USER	VARCHAR2(3)		Indicates whether the parameter value was set by the user (YES) or was not set by the user (NO). If NO for a parameter, then the parameter is set to its default value. If YES for a parameter, then the parameter may or may not be set to its default value.

See Also:

"DBA_APPLY_PARAMETERS"

3.75 ALL_APPLY_PROGRESS

ALL_APPLY_PROGRESS displays information about the progress made by the apply processes that dequeue events from queues accessible to the current user. This view only contains information about captured events. It does not contain information about user-enqueued events.

Related View

DBA_APPLY_PROGRESS displays information about the progress made by all apply processes in the database.

Column	Datatype	NULL	Description
APPLY_NAME	VARCHAR2(128)	NOT NULL	Name of the apply process
SOURCE_DATABASE	VARCHAR2(128)	NOT NULL	Global name of the source database of the changes that are applied by the apply process
APPLIED_MESSAGE_NUMBER	NUMBER	NOT NULL	Message number up to which all transactions have definitely been applied. This value is the low watermark for the apply process. That is, messages with a commit message number less than or equal to this message number have definitely been applied, but some messages with a higher commit message number may also have been applied.
OLDEST_MESSAGE_NUMBER	NUMBER	NOT NULL	Earliest message number of the transactions currently being dequeued and applied
APPLY_TIME	DATE		Time at which the message with the message number displayed in the APPLIED_MESSAGE_NUMBER column was applied
APPLIED_MESSAGE_CREATE_TIME	DATE		Time at which the message with the message number displayed in the APPLIED_MESSAGE_NUMBER column was created at its source database
OLDEST_TRANSACTION_ID	VARCHAR2(128)		Oldest transaction ID of interest. (useful for detecting long-running or large transactions)

Column	Datatype	NULL	Description
SPILL_MESSAGE_NUMBER	NUMBER		Spill low watermark. Any message with a lower SCN has either been applied or spilled to disk (it will be dequeued from the Streams queue and capture will not need to resend any logical change records (LCRs) with a lower SCN). Spilled messages may not have been applied yet.
SOURCE_ROOT_NAME	VARCHAR2(128)		The global name of the source root database

> **See Also:**
>
> "DBA_APPLY_PROGRESS"

3.76 ALL_APPLY_REPERROR_HANDLERS

ALL_APPLY_REPERROR_HANDLERS provides details about apply reperror handlers on objects visible to the user.

Related View

DBA_APPLY_REPERROR_HANDLERS provides details about apply reperror handlers.

Column	Datatype	NULL	Description
APPLY_NAME	VARCHAR2(128)	NOT NULL	Name of the apply process
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object
SOURCE_OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Source database owner of the source object
SOURCE_OBJECT_NAME	VARCHAR2(128)	NOT NULL	Source database name of the object
ERROR_NUMBER	NUMBER	NOT NULL	Error number for the handler
METHOD	VARCHAR2(18)		Error handling method: • ABEND • RECORD • IGNORE • RETRY • RETRY_TRANSACTION • RECORD_TRANSACTION
MAX_RETRIES	NUMBER		Maximum number of times to retry for the method RETRY and RETRY_TRANSACTION
DELAY_CSECS	NUMBER		Number of centiseconds to wait between retries for RETRY and RETRY_TRANSACTION
SET_BY	VARCHAR2(10)		Entity that set up the handler: • USER • GOLDENGATE

> **See Also:**
>
> "DBA_APPLY_REPERROR_HANDLERS"

3.77 ALL_APPLY_TABLE_COLUMNS

ALL_APPLY_TABLE_COLUMNS displays, for the tables accessible to the current user, information about the nonkey table columns for which apply process conflict detection has been stopped for update and delete operations.

Conflict detection for nonkey columns can be stopped using the DBMS_APPLY_ADM.COMPARE_OLD_VALUES procedure.

Related View

DBA_APPLY_TABLE_COLUMNS displays, for all tables in the database, information about the nonkey table columns for which apply process conflict detection has been stopped for update and delete operations.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)		Owner of the table
OBJECT_NAME	VARCHAR2(128)		Name of the table
COLUMN_NAME	VARCHAR2(4000)		Name of the column
COMPARE_OLD_ON_DELETE	VARCHAR2(3)		Indicates whether to Compare the old value of the column on deletes (YES) or not (NO)
COMPARE_OLD_ON_UPDATE	VARCHAR2(3)		Indicates whether to Compare the old value of the column on updates (YES) or not (NO)
APPLY_DATABASE_LINK	VARCHAR2(128)		For remote tables, name of the database link pointing to the remote database

> **See Also:**
>
> - "DBA_APPLY_TABLE_COLUMNS"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLY_ADM.COMPARE_OLD_VALUES procedure

3.78 ALL_ARGUMENTS

ALL_ARGUMENTS lists the arguments of the functions and procedures that are accessible to the current user.

> **Note:**
>
> The following changes have been made to this view:
>
> - Starting with Oracle Database 12c release 1 (12.1.0.2), this view omits procedures with no arguments. Prior to Oracle Database 12c release 1 (12.1.0.2), a procedure with no arguments was presented as a single row in this view.
> - Starting with Oracle Database 18c, this view displays only one row for an argument that is a composite type. Prior to Oracle Database 18c, this view displayed multiple rows for composite types.
>
> To obtain information about composite type arguments, use the value of the TYPE_NAME column in this view to query the ALL_PLSQL_TYPES, ALL_PLSQL_TYPE_ATTRS, and ALL_PLSQL_COLL_TYPES views, which fully describe composite types.
>
> See *Oracle Database Upgrade Guide* for more information about these changes.

Related Views

- DBA_ARGUMENTS lists the arguments of the functions and procedures that are available in the database.
- USER_ARGUMENTS lists the arguments of the functions and procedures that are owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2(128)		Name of the procedure or function
PACKAGE_NAME	VARCHAR2(128)		Name of the package
OBJECT_ID	NUMBER	NOT NULL	Object number of the object
OVERLOAD	VARCHAR2(40)		Indicates the *n*th overloading ordered by its appearance in the source; otherwise, it is NULL.
SUBPROGRAM_ID	NUMBER		Unique subprogram identifier
ARGUMENT_NAME	VARCHAR2(128)		Name of the argument A null argument name is used to denote a function return.
POSITION	NUMBER	NOT NULL	This column holds the position of this item in the argument list, or 0 for a function return value.

Column	Datatype	NULL	Description
SEQUENCE	NUMBER	NOT NULL	Defines the sequential order of the argument. Argument sequence starts from 1. Return type comes first, and each argument will follow.
DATA_LEVEL	NUMBER	NOT NULL	Nesting depth of the argument for composite types **Note:** Starting with Oracle Database 18c, the value of this columns is always 0, because this view displays only one row for each argument. This view no longer displays multiple rows for composite type arguments.
DATA_TYPE	VARCHAR2(30)		Datatype of the argument
DEFAULTED	VARCHAR2(1)		Specifies whether or not the argument is defaulted
DEFAULT_VALUE	LONG		Reserved for future use
DEFAULT_LENGTH	NUMBER		Reserved for future use
IN_OUT	VARCHAR2(9)		Direction of the argument: • IN • OUT • IN/OUT
DATA_LENGTH	NUMBER		Length of the column (in bytes)
DATA_PRECISION	NUMBER		Length in decimal digits (NUMBER) or binary digits (FLOAT)
DATA_SCALE	NUMBER		Digits to the right of the decimal point in a number
RADIX	NUMBER		Argument radix for a number
CHARACTER_SET_NAME	VARCHAR2(44)		Character set name for the argument
TYPE_OWNER	VARCHAR2(128)		Owner of the type of the argument
TYPE_NAME	VARCHAR2(128)		Name of the type of the argument. If the type is a package local type (that is, it is declared in a package specification), then this column displays the name of the package.
TYPE_SUBNAME	VARCHAR2(128)		Relevant only for package local types. Displays the name of the type declared in the package identified in the TYPE_NAME column.
TYPE_LINK	VARCHAR2(128)		Relevant only for package local types when the package identified in the TYPE_NAME column is a remote package. This column displays the database link used to refer to the remote package.
TYPE_OBJECT_TYPE	VARCHAR2(7)		Displays the type of the type described by the TYPE_OWNER, TYPE_NAME, and TYPE_SUBNAME columns. Possible values are: • TABLE • VIEW • PACKAGE • TYPE
PLS_TYPE	VARCHAR2(128)		For numeric arguments, the name of the PL/SQL type of the argument. Null otherwise.
CHAR_LENGTH	NUMBER		Character limit for string datatypes
CHAR_USED	VARCHAR2(1)		Indicates whether the byte limit (B) or char limit (C) is official for the string

Column	Datatype	NULL	Description
ORIGIN_CON_ID	VARCHAR2(256)		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)

Note:

To list the procedure names in a package, use the ALL_PROCEDURES view.

See Also:

- "DBA_ARGUMENTS"
- "USER_ARGUMENTS"
- "ALL_PLSQL_TYPES"
- "ALL_PLSQL_TYPE_ATTRS"
- "ALL_PLSQL_COLL_TYPES"
- "ALL_PROCEDURES" for information about the functions and procedures that are accessible to the current user

3.79 ALL_ASSEMBLIES

ALL_ASSEMBLIES provides information about assemblies accessible to the current user.

Related Views

- DBA_ASSEMBLIES provides information about all assemblies in the database.
- USER_ASSEMBLIES provides information about all assemblies owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the assembly
ASSEMBLY_NAME	VARCHAR2(128)	NOT NULL	Name of the assembly
FILE_SPEC	VARCHAR2(4000)		Operating system file specification of the assembly
SECURITY_LEVEL	VARCHAR2(10)		The maximum security level of the assembly
IDENTITY	VARCHAR2(4000)		The identity of the assembly
STATUS	VARCHAR2(7)		Status of the assembly

See Also:

- "DBA_ASSEMBLIES"
- "USER_ASSEMBLIES"

3.80 ALL_ASSOCIATIONS

`ALL_ASSOCIATIONS` describes user-defined statistics associated with objects accessible to the current user.

Related Views

- `DBA_ASSOCIATIONS` describes all user-defined statistics in the database.
- `USER_ASSOCIATIONS` describes user-defined statistics associated with objects owned by the current user.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the object for which the association is being defined
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object for which the association is being defined
COLUMN_NAME	VARCHAR2(128)		Column name in the object for which the association is being defined
OBJECT_TYPE	VARCHAR2(9)		Kind of object with which statistics are being associated: column, type, package or function, indextype, or domain index.
STATSTYPE_SCHEMA	VARCHAR2(128)		Owner of the statistics type
STATSTYPE_NAME	VARCHAR2(128)		Name of statistics type that contains the cost, selectivity or statistics functions
DEF_SELECTIVITY	NUMBER		Default selectivity of the object, if any
DEF_CPU_COST	NUMBER		Default CPU cost of the object, if any
DEF_IO_COST	NUMBER		Default I/O cost of the object, if any
DEF_NET_COST	NUMBER		Default networking cost of the object, if any
INTERFACE_VERSION	NUMBER		Identifies the version number of the `ODCIStats` interface. Value is `1` for statistics type implementing Oracle8*i* 8.1; `0` for types implementing Oracle9*i* 9.0.0.
MAINTENANCE_TYPE	VARCHAR2(14)		Specifies whether the object is system-managed or user-managed

See Also:

- "DBA_ASSOCIATIONS"
- "USER_ASSOCIATIONS"

3.81 ALL_ATTRIBUTE_DIM_ATTR_CLASS

ALL_ATTRIBUTE_DIM_ATTR_CLASS describes the attribute classifications of the attribute dimensions accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_ATTR_CLASS describes the attribute classifications of all attribute dimensions in the database.
- USER_ATTRIBUTE_DIM_ATTR_CLASS describes the attribute classifications of the attribute dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
ATTRIBUTE_NAME	VARCHAR2(128)		Name of the attribute
CLASSIFICATION	VARCHAR2(128)		Classification associated with the attribute
VALUE	CLOB		Value of the classification, or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification, or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the attribute
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ATTRIBUTE_DIM_ATTR_CLASS"
- "USER_ATTRIBUTE_DIM_ATTR_CLASS"

3.82 ALL_ATTRIBUTE_DIM_ATTR_CLS

ALL_ATTRIBUTE_DIM_ATTR_CLS is identical to ALL_ATTRIBUTE_DIM_ATTR_CLASS.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ATTR_CLASS"

3.83 ALL_ATTRIBUTE_DIM_ATTR_CLS_AE

ALL_ATTRIBUTE_DIM_ATTR_CLS_AE describes the attribute classifications of the attribute dimensions (across all editions) accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_ATTR_CLS_AE describes the attribute classifications of all attribute dimensions (across all editions) in the database.
- USER_ATTRIBUTE_DIM_ATTR_CLS_AE describes the attribute classifications of the attribute dimensions (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
ATTRIBUTE_NAME	VARCHAR2(128)		Name of the attribute
CLASSIFICATION	VARCHAR2(128)		Classification associated with the attribute
VALUE	CLOB		Value of the classification, or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification, or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the attribute
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the attribute dimension is defined

See Also:

- "DBA_ATTRIBUTE_DIM_ATTR_CLS_AE"
- "USER_ATTRIBUTE_DIM_ATTR_CLS_AE"

3.84 ALL_ATTRIBUTE_DIM_ATTRS

`ALL_ATTRIBUTE_DIM_ATTRS` describes the attributes of the attribute dimensions accessible to the current user.

Related Views

- `DBA_ATTRIBUTE_DIM_ATTRS` describes the attributes of all attribute dimensions in the database.
- `USER_ATTRIBUTE_DIM_ATTRS` describes the attributes of the attribute dimensions owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
`OWNER`	`VARCHAR2(128)`	`NOT NULL`	Owner of the attribute dimension
`DIMENSION_NAME`	`VARCHAR2(128)`	`NOT NULL`	Name of the attribute dimension
`ATTRIBUTE_NAME`	`VARCHAR2(128)`		Name of the attribute dimension attribute
`TABLE_ALIAS`	`VARCHAR2(128)`		Alias of the table or view in the `USING` clause to which the column belongs
`COLUMN_NAME`	`VARCHAR2(128)`	`NOT NULL`	Name of the column in the table or view on which the attribute is defined
`ORDER_NUM`	`NUMBER`	`NOT NULL`	Order of the attribute in the list of attribute dimension attributes
`ORIGIN_CON_ID`	`NUMBER`		The ID of the container where the data originates. Possible values include: • `0`: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ATTRIBUTE_DIM_ATTRS"
- "USER_ATTRIBUTE_DIM_ATTRS"

3.85 ALL_ATTRIBUTE_DIM_ATTRS_AE

ALL_ATTRIBUTE_DIM_ATTRS_AE describes the attributes of the attribute dimensions (across all editions) accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_ATTRS_AE describes the attributes of all attribute dimensions (across all editions) in the database.
- USER_ATTRIBUTE_DIM_ATTRS_AE describes the attributes of the attribute dimensions (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
ATTRIBUTE_NAME	VARCHAR2(128)		Name of the attribute dimension attribute
TABLE_ALIAS	VARCHAR2(128)		Alias of the table or view in the USING clause to which the column belongs
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column in the table or view on which the attribute is defined
ORDER_NUM	NUMBER	NOT NULL	Order of the attribute in the list of attribute dimension attributes
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the attribute dimension is defined

See Also:

- "DBA_ATTRIBUTE_DIM_ATTRS_AE"
- "USER_ATTRIBUTE_DIM_ATTRS_AE"

3.86 ALL_ATTRIBUTE_DIM_CLASS

ALL_ATTRIBUTE_DIM_CLASS describes the classifications of the attribute dimensions accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_CLASS describes the classifications of all attribute dimensions in the database.
- USER_ATTRIBUTE_DIM_CLASS describes the classifications of the attribute dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
CLASSIFICATION	VARCHAR2(128)		Classification associated with the attribute dimension
VALUE	CLOB		Value of the classification, or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification, or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the attribute dimension
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ATTRIBUTE_DIM_CLASS"
- " USER_ATTRIBUTE_DIM_CLASS"

3.87 ALL_ATTRIBUTE_DIM_CLASS_AE

ALL_ATTRIBUTE_DIM_CLASS_AE describes the classifications of the attribute dimensions (across all editions) accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_CLASS_AE describes the classifications of all attribute dimensions (across all editions) in the database.

- USER_ATTRIBUTE_DIM_CLASS_AE describes the classifications of the attribute dimensions (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
CLASSIFICATION	VARCHAR2(128)		Classification associated with the attribute dimension
VALUE	CLOB		Value of the classification, or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification, or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the attribute dimension
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the attribute dimension is defined

See Also:

- "DBA_ATTRIBUTE_DIM_CLASS_AE"
- "USER_ATTRIBUTE_DIM_CLASS_AE"

3.88 ALL_ATTRIBUTE_DIM_JN_PTHS

ALL_ATTRIBUTE_DIM_JN_PTHS is identical to ALL_ATTRIBUTE_DIM_JOIN_PATHS.

See Also:

"ALL_ATTRIBUTE_DIM_JOIN_PATHS"

3.89 ALL_ATTRIBUTE_DIM_JN_PTHS_AE

ALL_ATTRIBUTE_DIM_JN_PTHS_AE describes the join paths for the attribute dimensions (across all editions) accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_JN_PTHS_AE describes the join paths for all attribute dimensions (across all editions) in the database.
- USER_ATTRIBUTE_DIM_JN_PTHS_AE describes the join paths for the attribute dimensions (across all editions) owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
JOIN_PATH_NAME	VARCHAR2(128)	NOT NULL	Name of the join path
ON_CONDITION	VARCHAR2(4000)		Join condition specified in the ON clause
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the attribute dimension
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the attribute dimension is defined

See Also:

- "DBA_ATTRIBUTE_DIM_JN_PTHS_AE"
- "USER_ATTRIBUTE_DIM_JN_PTHS_AE"

3.90 ALL_ATTRIBUTE_DIM_JOIN_PATHS

ALL_ATTRIBUTE_DIM_JOIN_PATHS describes the join paths for the attribute dimensions accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_JOIN_PATHS describes the join paths for all attribute dimensions in the database.

- USER_ATTRIBUTE_DIM_JOIN_PATHS describes the join paths for the attribute dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
JOIN_PATH_NAME	VARCHAR2(128)	NOT NULL	Name of the join path
ON_CONDITION	VARCHAR2(4000)		Join condition specified in the ON clause
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the attribute dimension
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ATTRIBUTE_DIM_JOIN_PATHS"
- "USER_ATTRIBUTE_DIM_JOIN_PATHS"

3.91 ALL_ATTRIBUTE_DIM_KEYS

ALL_ATTRIBUTE_DIM_KEYS describes the keys of the attribute dimensions accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_KEYS describes the keys of all attribute dimensions in the database.
- USER_ATTRIBUTE_DIM_KEYS describes the keys of the attribute dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
LEVEL_NAME	VARCHAR2(128)		Name of the level of the key
IS_ALTERNATE	VARCHAR2(1)		Indicates whether the attribute dimension key is an alternate key (Y) or not (N)
ATTRIBUTE_NAME	VARCHAR2(128)		Name of the key attribute
ATTR_ORDER_NUM	NUMBER	NOT NULL	Order of the attribute in the list of attributes comprising the key

Column	Datatype	NULL	Description
KEY_ORDER_NUM	NUMBER	NOT NULL	Order of the key in the list of keys (if alternate keys are specified)
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ATTRIBUTE_DIM_KEYS"
- "USER_ATTRIBUTE_DIM_KEYS"

3.92 ALL_ATTRIBUTE_DIM_KEYS_AE

ALL_ATTRIBUTE_DIM_KEYS_AE describes the keys of the attribute dimensions (across all editions) accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_KEYS_AE describes the keys of all attribute dimensions (across all editions) in the database.
- USER_ATTRIBUTE_DIM_KEYS_AE describes the keys of the attribute dimensions (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
LEVEL_NAME	VARCHAR2(128)		Name of the level of the key
IS_ALTERNATE	VARCHAR2(1)		Indicates whether the attribute dimension key is an alternate key (Y) or not (N)
ATTRIBUTE_NAME	VARCHAR2(128)		Name of the key attribute
ATTR_ORDER_NUM	NUMBER	NOT NULL	Order of the attribute in the list of attributes comprising the key
KEY_ORDER_NUM	NUMBER	NOT NULL	Order of the key in the list of keys (if alternate keys are specified)

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the attribute dimension is defined

See Also:

- "DBA_ATTRIBUTE_DIM_KEYS_AE"
- "USER_ATTRIBUTE_DIM_KEYS_AE"

3.93 ALL_ATTRIBUTE_DIM_LEVEL_ATTRS

ALL_ATTRIBUTE_DIM_LEVEL_ATTRS describes the attributes of the levels of the attribute dimensions accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_LEVEL_ATTRS describes the attributes of the levels of all attribute dimensions in the database.
- USER_ATTRIBUTE_DIM_LEVEL_ATTRS describes the attributes of the levels of the attribute dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)		Name of the attribute dimension
LEVEL_NAME	VARCHAR2(128)		Name of the attribute dimension level
ATTRIBUTE_NAME	VARCHAR2(128)		Name of the attribute determined by the level
ROLE	VARCHAR2(4)		Role of the attribute determined by the level
IS_MINIMAL_DTM	VARCHAR2(1)		Indicates whether the attribute is minimally determined (Y) or not (N)
ORDER_NUM	NUMBER		Order of the attribute in the list of attributes determined by the level
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

> **See Also:**
>
> - "DBA_ATTRIBUTE_DIM_LEVEL_ATTRS"
> - "USER_ATTRIBUTE_DIM_LEVEL_ATTRS"

3.94 ALL_ATTRIBUTE_DIM_LEVELS

ALL_ATTRIBUTE_DIM_LEVELS describes the levels of the attribute dimensions accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_LEVELS describes the levels of all attribute dimensions in the database.
- USER_ATTRIBUTE_DIM_LEVELS describes the levels of the attribute dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
LEVEL_NAME	VARCHAR2(128)		Name of the attribute dimension level
SKIP_WHEN_NULL	VARCHAR2(1)		Indicates whether to skip the level when the key is NULL; the value can be Y or N.
LEVEL_TYPE	VARCHAR2(10)		Type of attribute dimension level
MEMBER_NAME_EXPR	CLOB	NOT NULL	Expression representing the level member name
MEMBER_CAPTION_EXPR	CLOB		Expression representing the level member caption, or NULL if not specified
MEMBER_DESCRIPTION_EXPR	CLOB		Expression representing the level member description, or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the level in the list of attribute dimension levels
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

> **See Also:**
>
> - "DBA_ATTRIBUTE_DIM_LEVELS"
> - "USER_ATTRIBUTE_DIM_LEVELS"

3.95 ALL_ATTRIBUTE_DIM_LEVELS_AE

ALL_ATTRIBUTE_DIM_LEVELS_AE describes the levels of the attribute dimensions (across all editions) accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_LEVELS_AE describes the levels of all attribute dimensions (across all editions) in the database.
- USER_ATTRIBUTE_DIM_LEVELS_AE describes the levels of the attribute dimensions (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
LEVEL_NAME	VARCHAR2(128)		Name of the attribute dimension level
SKIP_WHEN_NULL	VARCHAR2(1)		Indicates whether to skip the level when the key is NULL; the value can be Y or N.
LEVEL_TYPE	VARCHAR2(10)		Type of attribute dimension level
MEMBER_NAME_EXPR	CLOB	NOT NULL	Expression representing the level member name
MEMBER_CAPTION_EXPR	CLOB		Expression representing the level member caption, or NULL if not specified
MEMBER_DESCRIPTION_EXPR	CLOB		Expression representing the level member description, or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the level in the list of attribute dimension levels
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the attribute dimension is defined

See Also:

- "DBA_ATTRIBUTE_DIM_LEVELS_AE"
- "USER_ATTRIBUTE_DIM_LEVELS_AE"

3.96 ALL_ATTRIBUTE_DIM_LVL_ATRS

ALL_ATTRIBUTE_DIM_LVL_ATRS is identical to ALL_ATTRIBUTE_DIM_LEVEL_ATTRS.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_LEVEL_ATTRS"

3.97 ALL_ATTRIBUTE_DIM_LVL_ATRS_AE

ALL_ATTRIBUTE_DIM_LVL_ATRS_AE describes the attributes of the levels of the attribute dimensions (across all editions) accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_LVL_ATRS_AE describes the attributes of the levels of all attribute dimensions (across all editions) in the database.
- USER_ATTRIBUTE_DIM_LVL_ATRS_AE describes the attributes of the levels of the attribute dimensions (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)		Name of the attribute dimension
LEVEL_NAME	VARCHAR2(128)		Name of the attribute dimension level
ATTRIBUTE_NAME	VARCHAR2(128)		Name of the attribute determined by the level
ROLE	VARCHAR2(4)		Role of the attribute determined by the level
IS_MINIMAL_DTM	VARCHAR2(1)		Indicates whether the attribute is minimally determined (Y) or not (N)
ORDER_NUM	NUMBER		Order of the attribute in the list of attributes determined by the level
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the attribute dimension is defined

> **See Also:**
>
> - "DBA_ATTRIBUTE_DIM_LVL_ATRS_AE"
> - "USER_ATTRIBUTE_DIM_LVL_ATRS_AE"

3.98 ALL_ATTRIBUTE_DIM_LVL_CLASS

ALL_ATTRIBUTE_DIM_LVL_CLASS describes the level classifications of the attribute dimensions accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_LVL_CLASS describes the level classifications of all attribute dimensions in the database.
- USER_ATTRIBUTE_DIM_LVL_CLASS describes the level classifications of the attribute dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
LEVEL_NAME	VARCHAR2(128)		Name of the level
CLASSIFICATION	VARCHAR2(128)		Classification associated with the level
VALUE	CLOB		Value of the classification, or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification, or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the level
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ATTRIBUTE_DIM_LVL_CLASS"
- "USER_ATTRIBUTE_DIM_LVL_CLASS"

3.99 ALL_ATTRIBUTE_DIM_LVL_CLS

ALL_ATTRIBUTE_DIM_LVL_CLS is identical to ALL_ATTRIBUTE_DIM_LVL_CLASS.

See Also:

"ALL_ATTRIBUTE_DIM_LVL_CLASS"

3.100 ALL_ATTRIBUTE_DIM_LVL_CLS_AE

ALL_ATTRIBUTE_DIM_LVL_CLS_AE describes the level classifications of the attribute dimensions (across all editions) accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_LVL_CLS_AE describes the level classifications of all attribute dimensions (across all editions) in the database.
- USER_ATTRIBUTE_DIM_LVL_CLS_AE describes the level classifications of the attribute dimensions (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
LEVEL_NAME	VARCHAR2(128)		Name of the level
CLASSIFICATION	VARCHAR2(128)		Classification associated with the level
VALUE	CLOB		Value of the classification, or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification, or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the level
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the attribute dimension is defined

See Also:

- "DBA_ATTRIBUTE_DIM_LVL_CLS_AE"
- "USER_ATTRIBUTE_DIM_LVL_CLS_AE"

3.101 ALL_ATTRIBUTE_DIM_ORD_ATRS

ALL_ATTRIBUTE_DIM_ORD_ATRS is identical to ALL_ATTRIBUTE_DIM_ORDER_ATTRS.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ORDER_ATTRS"

3.102 ALL_ATTRIBUTE_DIM_ORD_ATRS_AE

ALL_ATTRIBUTE_DIM_ORD_ATRS_AE describes the order attributes of the attribute dimensions (across all editions) accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_ORD_ATRS_AE describes the order attributes of all attribute dimensions (across all editions) in the database.
- USER_ATTRIBUTE_DIM_ORD_ATRS_AE describes the order attributes of the attribute dimensions (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
LEVEL_NAME	VARCHAR2(128)		Name of the level to order or the name of the level that has the ORDER BY clause
AGG_FUNC	VARCHAR2(3)		Aggregation function of the ORDER BY clause: • MIN • MAX
ATTRIBUTE_NAME	VARCHAR2(128)		Name of the order attribute
ORDER_NUM	NUMBER	NOT NULL	Order number of the attribute in the list of order attributes
CRITERIA	VARCHAR2(4)		Criteria of the ordering, either ascending or descending: • ASC • DESC
NULLS_POSITION	VARCHAR2(5)		Position of ORDER BY values in the orderings: • FIRST • LAST
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the attribute dimension is defined

> **See Also:**
>
> - "DBA_ATTRIBUTE_DIM_ORD_ATRS_AE"
> - "USER_ATTRIBUTE_DIM_ORD_ATRS_AE"

3.103 ALL_ATTRIBUTE_DIM_ORDER_ATTRS

`ALL_ATTRIBUTE_DIM_ORDER_ATTRS` describes the order attributes of the attribute dimensions accessible to the current user.

Related Views

- `DBA_ATTRIBUTE_DIM_ORDER_ATTRS` describes the order attributes of all attribute dimensions in the database.
- `USER_ATTRIBUTE_DIM_ORDER_ATTRS` describes the order attributes of the attribute dimensions owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
`OWNER`	`VARCHAR2(128)`	`NOT NULL`	Owner of the attribute dimension
`DIMENSION_NAME`	`VARCHAR2(128)`	`NOT NULL`	Name of the attribute dimension
`LEVEL_NAME`	`VARCHAR2(128)`		Name of the level to order or the name of the level that has the `ORDER BY` clause
`AGG_FUNC`	`VARCHAR2(3)`		Aggregation function of the `ORDER BY` clause: • `MIN` • `MAX`
`ATTRIBUTE_NAME`	`VARCHAR2(128)`		Name of the order attribute
`ORDER_NUM`	`NUMBER`	`NOT NULL`	Order number of the attribute in the list of order attributes
`CRITERIA`	`VARCHAR2(4)`		Criteria of the ordering, either ascending or descending: • `ASC` • `DESC`
`NULLS_POSITION`	`VARCHAR2(5)`		Position of `ORDER BY` values in the orderings: • `FIRST` • `LAST`
`ORIGIN_CON_ID`	`NUMBER`		The ID of the container where the data originates. Possible values include: • `0`: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ATTRIBUTE_DIM_ORDER_ATTRS"
- "USER_ATTRIBUTE_DIM_ORDER_ATTRS"

3.104 ALL_ATTRIBUTE_DIM_TABLES

ALL_ATTRIBUTE_DIM_TABLES describes the tables used by the attribute dimensions accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_TABLES describes the tables used by all attribute dimensions in the database.
- USER_ATTRIBUTE_DIM_TABLES describes the tables used by the attribute dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of table used by the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table or view used by the attribute dimension
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table or view used by the attribute dimension
TABLE_ALIAS	VARCHAR2(128)		Alias specified for the table or view; if not specified, the name of the table or view
IS_REMOTE	VARCHAR2(1)		Indicates whether the source is a remote table. The values are: • Y for a remote table • N for a local table
ORDER_NUM	NUMBER	NOT NULL	Order of the table in the list of tables in the USING clause
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ATTRIBUTE_DIM_TABLES"
- "USER_ATTRIBUTE_DIM_TABLES"

3.105 ALL_ATTRIBUTE_DIM_TABLES_AE

ALL_ATTRIBUTE_DIM_TABLES_AE describes the tables used by the attribute dimensions (across all editions) accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIM_TABLES_AE describes the tables used by all attribute dimensions (across all editions) in the database.
- USER_ATTRIBUTE_DIM_TABLES_AE describes the tables used by the attribute dimensions (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of table used by the attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table or view used by the attribute dimension
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table or view used by the attribute dimension
TABLE_ALIAS	VARCHAR2(128)		Alias specified for the table or view; if not specified, the name of the table or view
IS_REMOTE	VARCHAR2(1)		Indicates whether the source is a remote table. The values are: • Y for a remote table • N for a local table
ORDER_NUM	NUMBER	NOT NULL	Order of the table in the list of tables in the USING clause
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the attribute dimension is defined

See Also:

- "DBA_ATTRIBUTE_DIM_TABLES_AE"
- "USER_ATTRIBUTE_DIM_TABLES_AE"

3.106 ALL_ATTRIBUTE_DIMENSIONS

ALL_ATTRIBUTE_DIMENSIONS describes the attribute dimensions accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIMENSIONS describes all attribute dimensions in the database.
- USER_ATTRIBUTE_DIMENSIONS describes the attribute dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
DIMENSION_TYPE	VARCHAR2(8)		Type of the attribute dimension: • TIME • STANDARD
CACHE_STAR	VARCHAR2(12)	NOT NULL	Type of the cache for the dimension star table: • NONE indicates that no cache is being used • DYNAMIC • MATERIALIZED (the default value when a cache is used)
MAT_TABLE_OWNER	VARCHAR2(128)		The owner of the materialized table
MAT_TABLE_NAME	VARCHAR2(128)		The name of the materialized table
ALL_MEMBER_NAME	CLOB	NOT NULL	An expression for the name of the ALL member for the attribute dimension
ALL_MEMBER_CAPTION	CLOB		An expression for the caption for the ALL member of the attribute dimension, or NULL if not specified
ALL_MEMBER_DESCRIPTION	CLOB		An expression for the description for the ALL member of the attribute dimension
COMPILE_STATE	VARCHAR2(7)		Compile status of the attribute dimension: • VALID • INVALID
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_ATTRIBUTE_DIMENSIONS"
- "USER_ATTRIBUTE_DIMENSIONS"

3.107 ALL_ATTRIBUTE_DIMENSIONS_AE

ALL_ATTRIBUTE_DIMENSIONS_AE describes the attribute dimensions (across all editions) accessible to the current user.

Related Views

- DBA_ATTRIBUTE_DIMENSIONS_AE describes all attribute dimensions (across all editions) in the database.
- USER_ATTRIBUTE_DIMENSIONS_AE describes the attribute dimensions (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of attribute dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension
DIMENSION_TYPE	VARCHAR2(8)		Type of the attribute dimension: • TIME • STANDARD
CACHE_STAR	VARCHAR2(12)	NOT NULL	Type of the cache for the dimension star table: • NONE indicates that no cache is being used • DYNAMIC • MATERIALIZED (the default value when a cache is used)
MAT_TABLE_OWNER	VARCHAR2(128)		The owner of the materialized table
MAT_TABLE_NAME	VARCHAR2(128)		The name of the materialized table
ALL_MEMBER_NAME	CLOB)	NOT NULL	An expression for the name of the ALL member for the attribute dimension
ALL_MEMBER_CAPTION	CLOB		An expression for the caption for the ALL member of the attribute dimension, or NULL if not specified
ALL_MEMBER_DESCRIPTION	CLOB		An expression for the description for the ALL member of the attribute dimension
COMPILE_STATE	VARCHAR2(7)		Compile status of the attribute dimension: • VALID • INVALID
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the attribute dimension is defined

See Also:

- "DBA_ATTRIBUTE_DIMENSIONS_AE"
- "USER_ATTRIBUTE_DIMENSIONS_AE"

3.108 ALL_ATTRIBUTE_TRANSFORMATIONS

ALL_ATTRIBUTE_TRANSFORMATIONS describes the transformation functions for the transformations accessible to the current user.

Related Views

- DBA_ATTRIBUTE_TRANSFORMATIONS describes the transformation functions for all transformations in the database.
- USER_ATTRIBUTE_TRANSFORMATIONS describes the transformation functions for the transformations owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
TRANSFORMATION_ID	NUMBER	NOT NULL	Unique identifier for the transformation
OWNER	VARCHAR2(128)	NOT NULL	Owning user of the transformation
NAME	VARCHAR2(128)	NOT NULL	Transformation name
FROM_TYPE	VARCHAR2(257)		Source type name
TO_TYPE	VARCHAR2(385)		Target type name
ATTRIBUTE	NUMBER	NOT NULL	Target type attribute number
ATTRIBUTE_TRANSFORMATION	VARCHAR2(4000)		Transformation function for the attribute

See Also:

- "DBA_ATTRIBUTE_TRANSFORMATIONS"
- "USER_ATTRIBUTE_TRANSFORMATIONS"

3.109 ALL_AUDIT_POLICIES

ALL_AUDIT_POLICIES describes the fine-grained auditing policies on the tables and views accessible to the current user.

> **Note:**
>
> This view is populated only in an Oracle Database where unified auditing is not enabled. When unified auditing is enabled in Oracle Database, the audit records are populated in the new audit trail and can be viewed from UNIFIED_AUDIT_TRAIL.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

Related Views

- DBA_AUDIT_POLICIES describes all fine-grained auditing policies in the database.
- USER_AUDIT_POLICIES describes the fine-grained auditing policies on the tables and views owned by the current user. This view does not display the OBJECT_SCHEMA column.

Column	Datatype	NULL	Description
OBJECT_SCHEMA	VARCHAR2(128)		Name of the schema that includes the table or view
OBJECT_NAME	VARCHAR2(128)		Name of the table or view
POLICY_OWNER	VARCHAR2(128)		Owner of the policy
POLICY_NAME	VARCHAR2(128)		Name of the policy
POLICY_TEXT	VARCHAR2(4000)		Audit condition
POLICY_COLUMN	VARCHAR2(128)		Relevant column
PF_SCHEMA	VARCHAR2(128)		Owner of the audit handler function
PF_PACKAGE	VARCHAR2(128)		Name of the package containing the audit handler function
PF_FUNCTION	VARCHAR2(128)		Name of the audit handler function
ENABLED	VARCHAR2(3)		Indicates whether the policy is enabled (YES) or disabled (NO)
SEL	VARCHAR2(3)		Indicates whether the policy is applied to queries on the object (YES) or not (NO)
INS	VARCHAR2(3)		Indicates whether the policy is applied to INSERT statements on the object (YES) or not (NO)
UPD	VARCHAR2(3)		Indicates whether the policy is applied to UPDATE statements on the object (YES) or not (NO)

Column	Datatype	NULL	Description
DEL	VARCHAR2(3)		Indicates whether the policy is applied to DELETE statements on the object (YES) or not (NO)
AUDIT_TRAIL	VARCHAR2(12)		Indicates the audit trail to which the audit records generated by this audit policy will be written: • DB - Audit records are written to DBA_FGA_AUDIT_TRAIL (fine-grained audit trail) • DB+EXTENDED - Audit records are written to DBA_FGA_AUDIT_TRAIL (fine-grained audit trail) and the SQL_TEXT and SQL_BIND columns are populated for this policy • XML - Audit records are written to V$XML_AUDIT_TRAIL (XML audit files) • XML+EXTENDED - Audit records are written to V$XML_AUDIT_TRAIL (XML audit files) and the SQL_TEXT and SQL_BIND columns are populated for this policy
POLICY_COLUMN_OPTIONS	VARCHAR2(11)		Indicates whether all columns in the AUDIT_COLUMN parameter (ALL_COLUMNS) or any of the columns in the AUDIT_COLUMN parameter (ANY_COLUMNS) are considered for triggering fine-grained auditing
COMMON	VARCHAR2(3)		Indicates whether the policy applies across multiple containers (YES) or not (NO)
INHERITED	VARCHAR2(3)		Indicates whether the policy was inherited from another container (YES) or not (NO)

See Also:

- "DBA_AUDIT_POLICIES"
- "USER_AUDIT_POLICIES"

3.110 ALL_AUDIT_POLICY_COLUMNS

ALL_AUDIT_POLICY_COLUMNS describes the fine-grained auditing policy columns on the tables and views accessible to the current user.

> **Note:**
>
> This view is populated only in an Oracle Database where unified auditing is not enabled. When unified auditing is enabled in Oracle Database, the audit records are populated in the new audit trail and can be viewed from UNIFIED_AUDIT_TRAIL.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

Related Views

- DBA_AUDIT_POLICY_COLUMNS describes all fine-grained auditing policy columns in the database.
- USER_AUDIT_POLICY_COLUMNS describes the fine-grained auditing policy columns on the tables and views owned by the current user.

Column	Datatype	NULL	Description
OBJECT_SCHEMA	VARCHAR2(128)		Owner of the table or view
OBJECT_NAME	VARCHAR2(128)		Name of the table or view
POLICY_NAME	VARCHAR2(128)		Name of the policy
POLICY_COLUMN	VARCHAR2(128)		Relevant column of the policy

> **See Also:**
>
> - "DBA_AUDIT_POLICY_COLUMNS"
> - "USER_AUDIT_POLICY_COLUMNS"

3.111 ALL_AW_PS

ALL_AW_PS describes the page spaces in the analytic workspaces accessible to the current user.

Related Views

- DBA_AW_PS describes the page spaces in all analytic workspaces in the database.

- USER_AW_PS describes the page spaces in the analytic workspaces owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic workspace
AW_NUMBER	NUMBER	NOT NULL	Number of the analytic workspace
AW_NAME	VARCHAR2(128)		Name of the analytic workspace
PSNUMBER	NUMBER(10)		Number of the page space
GENERATIONS	NUMBER		Number of active generations in the page space
MAXPAGES	NUMBER		Maximum pages allocated in the page space

See Also:

- "DBA_AW_PS"
- "USER_AW_PS"
- *Oracle OLAP User's Guide* for more information about the OLAP option for Oracle Database

3.112 ALL_AWS

ALL_AWS describes the analytic workspaces accessible to the current user.

Related Views

- DBA_AWS describes all analytic workspaces in the database.
- USER_AWS describes the analytic workspaces owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the analytic workspace
AW_NUMBER	NUMBER	NOT NULL	Number of the analytic workspace
AW_NAME	VARCHAR2(128)		Name of the analytic workspace
AW_VERSION	VARCHAR2(4)		Format version of the analytic workspace: • 9.1 • 10.1 • 10.2 • 11.1
PAGESPACES	NUMBER		Number of pagespaces in the analytic workspace
GENERATIONS	NUMBER		Number of active generations in the analytic workspace
FROZEN	VARCHAR2(6)		Freeze state of the analytic workspace: • Frozen • NoThaw

See Also:

- "DBA_AWS"
- "USER_AWS"
- *Oracle OLAP User's Guide* for more information about the OLAP option for Oracle Database

3.113 ALL_BASE_TABLE_MVIEWS

`ALL_BASE_TABLE_MVIEWS` describes the materialized views using materialized view logs accessible to the current user. A materialized view log can be created for a master, base table, or master materialized view. Query this view at the master site or the master materialized view site to show one row for each materialized view using a materialized view log.

Related Views

- `DBA_BASE_TABLE_MVIEWS` describes all materialized views using materialized view logs in the database.
- `USER_BASE_TABLE_MVIEWS` describes the materialized views using materialized view logs owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Schema in which the master table or the master materialized view was created
MASTER	VARCHAR2(128)	NOT NULL	Name of the master table or the master materialized view
MVIEW_LAST_REFRESH_TIME	DATE	NOT NULL	Date when the materialized view based on the master was last refreshed
MVIEW_ID	NUMBER(38)		Unique identifier of the materialized view that is based on the master

See Also:

- "DBA_BASE_TABLE_MVIEWS"
- "USER_BASE_TABLE_MVIEWS"

3.114 ALL_BLOCKCHAIN_ROW_VERSION_COLS

ALL_BLOCKCHAIN_ROW_VERSION_COLS displays information about row versioned columns in the blockchain tables accessible to the current user.

Related Views

- DBA_BLOCKCHAIN_ROW_VERSION_COLS displays information about row versioned columns in all blockchain tables in the database.
- USER_BLOCKCHAIN_ROW_VERSION_COLS displays information about row versioned columns in the blockchain tables owned by the current user.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Schema containing the blockchain table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the blockchain table
ROW_VERSION_NAME	VARCHAR2(128)	NOT NULL	Name of the row version
USER_CHAIN	VARCHAR2(3)		Indicates whether row versioning with user chains is enabled for the blockchain table (YES) or not (NO)
KEYCOL1_NAME	VARCHAR2(128)	NOT NULL	Name of version key column 1
KEYCOL2_NAME	VARCHAR2(128)		Name of version key column 2 Null if only one version key column is specified for the row version
KEYCOL3_NAME	VARCHAR2(128)		Name of version key column 3 Null if only one or two version key columns are specified for the row version

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_BLOCKCHAIN_ROW_VERSION_COLS"
- "USER_BLOCKCHAIN_ROW_VERSION_COLS"

3.115 ALL_BLOCKCHAIN_ROW_VERSION_HISTORY

ALL_BLOCKCHAIN_ROW_VERSION_HISTORY provides a history of row versions in the blockchain tables accessible to the current user.

This view is populated for a blockchain table with a row version only when rows are purged from that blockchain table. For each different value of the PDB_GUID and KEYCOL*n*_VALUE columns, information about only the youngest purged row is kept in the view.

Related Views

- `DBA_BLOCKCHAIN_ROW_VERSION_HISTORY` provides a history of row versions in all blockchain tables in the database.
- `USER_BLOCKCHAIN_ROW_VERSION_HISTORY` provides a history of row versions in the blockchain tables owned by the current user. This view does not display the `SCHEMA_NAME` column.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Schema containing the blockchain table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the blockchain table
ROW_VERSION_NAME	VARCHAR2(128)	NOT NULL	Name of the row version
PDB_GUID	RAW(16)		Global unique identifier of the pluggable database that inserted the row before any GoldenGate processes might have replicated the row to another database
KEYCOL1_VALUE	VARCHAR2(400)		Value associated with version key column 1
KEYCOL2_VALUE	VARCHAR2(400)		Value associated with version key column 2 Null if only one version key column is specified for the row version
KEYCOL3_VALUE	VARCHAR2(400)		Value associated with version key column 3 Null if only one or two version key columns are specified for the row version
VERSION_NUMBER	NUMBER		Row version number
USER_CHAIN_HASH	RAW(2000)		User chain cryptographic hash
ROW_CREATE_TIME	TIMESTAMP(6) WITH TIME ZONE		Date and time at which the row version was created
INST_ID	NUMBER		Identifier of any instance using a distributed or XA transaction to append to the row version history
TRAN_ID	VARCHAR2(22)		Identifier of any distributed transaction branch that is appending to the row version history

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_BLOCKCHAIN_ROW_VERSION_HISTORY"
- "USER_BLOCKCHAIN_ROW_VERSION_HISTORY"

3.116 ALL_BLOCKCHAIN_TABLE_CHAINS

ALL_BLOCKCHAIN_TABLE_CHAINS displays system chain information for the blockchain tables accessible to the current user.

Related Views

- DBA_BLOCKCHAIN_TABLE_CHAINS displays system chain information for all blockchain tables in the database.
- USER_BLOCKCHAIN_TABLE_CHAINS displays system chain information for the blockchain tables owned by the current user. This view does not display the SCHEMA_NAME column.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Name of the schema containing the blockchain table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Blockchain table name
PDB_GUID	RAW(16)		Global unique identifier of the pluggable database that can insert rows into the chain
INSTANCE_ID	NUMBER	NOT NULL	Identifier of the instance on the PDB that can insert rows into the chain
CHAIN_ID	NUMBER	NOT NULL	Chain ID number By default, chains are numbered from 0 to 31.
EPOCH_NUMBER	NUMBER		Epoch number for this section of the chain
HASH_DATA_FMT_VER	NUMBER		Hash data format version for this section of the chain
MIN_SEQ_NUMBER	NUMBER		Smallest sequence number in this section of the chain
MAX_SEQ_NUMBER	NUMBER		Largest sequence number in this section of the chain
LAST_CREATE_TIME	TIMESTAMP(6) WITH TIME ZONE		Time at which the last row was added to this section of the chain
TRAN_ID	VARCHAR2(22)		Identifier of any distributed transaction that is appending a row to the chain
DELETED_SEQ_NUM	NUMBER		Largest sequence number for rows in the chain that have been deleted
DELETED_ROW_HASH	RAW(2000)		Cryptographic hash that was stored in the row of the chain with sequence number DELETED_SEQ_NUM
LAST_ROW_HASH	RAW(2000)		Cryptographic hash stored in the last row in this section of the chain with sequence number MAX_SEQ_NUMBER

Note:

This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_BLOCKCHAIN_TABLE_CHAINS"
> - "USER_BLOCKCHAIN_TABLE_CHAINS"

3.117 ALL_BLOCKCHAIN_TABLE_EPOCHS

`ALL_BLOCKCHAIN_TABLE_EPOCHS` displays epoch information for the blockchain tables accessible to the current user.

Related Views

- `DBA_BLOCKCHAIN_TABLE_EPOCHS` displays epoch information for all blockchain tables in the database.
- `USER_BLOCKCHAIN_TABLE_EPOCHS` displays epoch information for the blockchain tables owned by the current user. This view does not display the `SCHEMA_NAME` column.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Name of the schema containing the blockchain table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Blockchain table name
EPOCH_NUMBER	NUMBER		Epoch number
EPOCH_NAME	VARCHAR2(11)		Epoch name describes the reason for the epoch and is one of the following values: • CREATE • IMPORT • ADD COLUMN • DROP COLUMN
PDB_GUID	RAW(16)		Global unique identifier of the pluggable database where the blockchain table epoch was created
HASH_ALGORITHM	VARCHAR2(8)		Algorithm used for computing the cryptographic hash on each row produced in the epoch The value of this column is always `SHA2_512`.
HASH_DATA_FORMAT_VERSION	NUMBER		Hash data format version for the epoch
START_TIME	TIMESTAMP(6) WITH TIME ZONE		Time at which the epoch was created

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_BLOCKCHAIN_TABLE_EPOCHS"
> - "USER_BLOCKCHAIN_TABLE_EPOCHS"

3.118 ALL_BLOCKCHAIN_TABLE_HASH_COL_ORDER

`ALL_BLOCKCHAIN_TABLE_HASH_COL_ORDER` displays information about columns used to compute the cryptographic hash in the blockchain tables accessible to the current user.

Related Views

- `DBA_BLOCKCHAIN_TABLE_HASH_COL_ORDER` displays information about columns used to compute the cryptographic hash in all blockchain tables in the database.
- `USER_BLOCKCHAIN_TABLE_HASH_COL_ORDER` displays information about columns used to compute the cryptographic hash in the blockchain tables owned by the current user. This view does not display the `SCHEMA_NAME` column.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Name of the schema containing the blockchain table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Blockchain table name
EPOCH_NUMBER	NUMBER		Epoch number
COLUMN_NAME	VARCHAR2(128)		Name of the user column or hidden column
COLUMN_POSITION	NUMBER		Order in which the column is hashed
INTERNAL_COLUMN_ID	NUMBER		Internal column ID
COLUMN_DATA_TYPE	VARCHAR2(106)		Data type of the user column or hidden column

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_BLOCKCHAIN_TABLE_HASH_COL_ORDER"
> - "USER_BLOCKCHAIN_TABLE_HASH_COL_ORDER"

3.119 ALL_BLOCKCHAIN_TABLES

ALL_BLOCKCHAIN_TABLES describes the blockchain tables accessible to the current user.

Related Views

- DBA_BLOCKCHAIN_TABLES describes all blockchain tables in the database.
- USER_BLOCKCHAIN_TABLES describes the blockchain tables owned by the current user. This view does not display the SCHEMA_NAME column.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	The schema containing the blockchain table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the blockchain table
ROW_RETENTION	NUMBER		Row retention period for the blockchain table, that is, the minimum number of days a row must be retained and cannot be deleted after it is inserted into the table If the value of this column is NULL, then rows can never be deleted from the table.
ROW_RETENTION_LOCKED	VARCHAR2(3)		Indicates whether the row retention period for the blockchain table is locked. Possible values: • YES: The row retention period is locked. You cannot change the row retention period • NO: The row retention period is not locked. You can change the row retention period to a value higher than the current value with the SQL statement ALTER TABLE … NO DELETE UNTIL *n* DAYS AFTER INSERT
TABLE_INACTIVITY_RETENTION	NUMBER		Number of days for which the blockchain table must be inactive before it can be dropped, that is, the number of days that must pass after the most recent row insertion before the table can be dropped A table with no rows can be dropped at any time, regardless of this column value.
HASH_ALGORITHM	VARCHAR2(8)		Algorithm used for computing the cryptographic hash for each table row
TABLE_VERSION	VARCHAR2(7)		Blockchain table version. Possible values: • V1 • V2
CURRENT_EPOCH	NUMBER		Current epoch number for the blockchain table
MAX_SYSTEM_CHAINS	NUMBER		Number of system chains in each database instance that can link rows with a cryptographic hash
DELETE_TIME	TIMESTAMP(6) WITH TIME ZONE		Youngest threshold used to delete rows in the blockchain table

See Also:

- "DBA_BLOCKCHAIN_TABLES"
- "USER_BLOCKCHAIN_TABLES"

3.120 ALL_CAPTURE

ALL_CAPTURE displays information about the capture processes that enqueue the captured changes into queues accessible to the current user.

Related View

DBA_CAPTURE displays information about all capture processes in the database.

Column	Datatype	NULL	Description
CAPTURE_NAME	VARCHAR2(128)		Name of the capture process
QUEUE_NAME	VARCHAR2(128)		Name of the queue used for staging captured changes
QUEUE_OWNER	VARCHAR2(128)		Owner of the queue used for staging captured changes
RULE_SET_NAME	VARCHAR2(128)		Name of the positive rule set used by the capture process for filtering
RULE_SET_OWNER	VARCHAR2(128)		Owner of the positive rule set
CAPTURE_USER	VARCHAR2(128)		Current user who is enqueuing captured messages
START_SCN	NUMBER		System change number (SCN) from which the capture process will start to capture changes. START_SCN is only modified as the result of an ALTER_CAPTURE statement or if the FIRST_SCN moves beyond the existing START_SCN.
STATUS	VARCHAR2(8)		Status of the capture process: • DISABLED • ENABLED • ABORTED
CAPTURED_SCN	NUMBER		System change number (SCN) of the last redo log record scanned
APPLIED_SCN	NUMBER		System change number (SCN) of the most recent message dequeued by the relevant apply processes. All changes below this SCN have been dequeued by all apply processes that apply changes captured by this capture process.
USE_DATABASE_LINK	VARCHAR2(3)		Indicates whether the source database name is used as the database link to connect to the source database from the downstream database (YES) or not (NO). If the capture process was created at the source database, then this column will be NULL.

Column	Datatype	NULL	Description
FIRST_SCN	NUMBER		System change number (SCN) from which the capture process can be restarted. FIRST_SCN indicates the lowest SCN to which the capture can be repositioned.
SOURCE_DATABASE	VARCHAR2(128)		Global name of the source database
SOURCE_DBID	NUMBER		Database ID of the source database
SOURCE_RESETLOGS_SCN	NUMBER		Resetlogs system change number (SCN) of the source database
SOURCE_RESETLOGS_TIME	NUMBER		Resetlogs time of the source database
LOGMINER_ID	NUMBER		Session ID of the Oracle LogMiner session associated with the capture process
NEGATIVE_RULE_SET_NAME	VARCHAR2(128)		Name of the negative rule set used by the capture process for filtering
NEGATIVE_RULE_SET_OWNER	VARCHAR2(128)		Owner of the negative rule set used by the capture process for filtering
MAX_CHECKPOINT_SCN	NUMBER		System change number (SCN) at which the last checkpoint was taken by the capture process
REQUIRED_CHECKPOINT_SCN	NUMBER		Lowest checkpoint SCN for which the capture process requires redo information. **Note:** This SCN value does not necessarily correspond with a checkpoint SCN value.
LOGFILE_ASSIGNMENT	VARCHAR2(8)		Logfile assignment type for the capture process: • IMPLICIT • EXPLICIT
STATUS_CHANGE_TIME	DATE		Time that the STATUS of the capture process was changed
ERROR_NUMBER	NUMBER		Error number if the capture process was terminated
ERROR_MESSAGE	VARCHAR2(4000)		Error message if the capture process was terminated
VERSION	VARCHAR2(64)		Version number of the capture process
CAPTURE_TYPE	VARCHAR2(10)		Type of the capture process: • DOWNSTREAM • LOCAL
LAST_ENQUEUED_SCN	NUMBER		Last enqueued system change number (SCN)
CHECKPOINT_RETENTION_TIME	NUMBER		Checkpoint retention time **Note:** When the checkpoint retention time for a capture process is set to INFINITE, then the value displayed in this column is 4294967295.
START_TIME	TIMESTAMP(6)		Time from which the capture process will start to capture changes. START_TIME is related to START_SCN and can only be modified by an ALTER_CAPTURE statement. You can modify either START_SCN or START_TIME, but not both at the same time.

Column	Datatype	NULL	Description
PURPOSE	VARCHAR2(19)		Purpose of the capture process: • GoldenGate Capture - A capture process configured using Oracle GoldenGate Extract in integrated capture mode • XStream Out - A capture process in an XStream Out configuration • AUDIT VAULT - A capture process in an audit vault configuration
SOURCE_ROOT_NAME	VARCHAR2(128)		The global name of the source root database
CLIENT_NAME	VARCHAR2(4000)		Client name of the capture process. This is the outbound name for XStream Out, and the extract name for GoldenGate.
CLIENT_STATUS	VARCHAR2(8)		Status of the client process: • DISABLED - For XStream Out if the outbound server is not running; for GoldenGate if the capture process is not running • DETACHED - For XStream Out if the outbound server is running, but the XStream client application is not attached to it; For GoldenGate if the capture process is running, but the extract process is not attached to it • ATTACHED - For XStream out if the outbound server is running and the XStream client application is attached to it; For GoldenGate if the capture process is running and the extract process is attached to it • ABORTED - For XStream out if the outbound server became disabled because it encountered an error; for GoldenGate if the capture process became disabled because it encountered an error
OLDEST_SCN	NUMBER		Oldest SCN of the transactions currently being processed
FILTERED_SCN	NUMBER		SCN of the low watermark transaction processed
USE_SHARED_CAPTURE	VARCHAR2(3)		Reserved for future use
SHARED_CAPTURE_NAME	VARCHAR2(128)		Reserved for future use
CONVERSION_STATE	VARCHAR2(34)		Reserved for future use
CONVERSION_SCN	NUMBER		Reserved for future use
ALT_LOGMNR_SID	NUMBER		Reserved for future use

See Also:

- "DBA_CAPTURE"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_XSTREAM_ADM.ENABLE_GG_XSTREAM_FOR_STREAMS procedure

3.121 ALL_CAPTURE_EXTRA_ATTRIBUTES

ALL_CAPTURE_EXTRA_ATTRIBUTES displays information about the extra attributes for the capture processes accessible to the current user.

Related View

DBA_CAPTURE_EXTRA_ATTRIBUTES displays information about the extra attributes for all capture processes in the database.

Column	Datatype	NULL	Description
CAPTURE_NAME	VARCHAR2(128)	NOT NULL	Name of the capture process
ATTRIBUTE_NAME	VARCHAR2(128)	NOT NULL	Name of the extra attribute
INCLUDE	VARCHAR2(3)		Indicates whether the extra attribute is included (YES) or not (NO)
ROW_ATTRIBUTE	VARCHAR2(3)		Indicates whether the extra attribute is a row LCR attribute (YES) or not (NO)
DDL_ATTRIBUTE	VARCHAR2(3)		Indicates whether the extra attribute is a DDL LCR attribute (YES) or not (NO)

See Also:

"DBA_CAPTURE_EXTRA_ATTRIBUTES"

3.122 ALL_CAPTURE_PARAMETERS

ALL_CAPTURE_PARAMETERS displays information about the parameters for the capture processes that enqueue the captured changes into queues accessible to the current user.

Related View

DBA_CAPTURE_PARAMETERS displays information about the parameters for all capture processes in the database.

Column	Datatype	NULL	Description
CAPTURE_NAME	VARCHAR2(128)	NOT NULL	Name of the capture process
PARAMETER	VARCHAR2(128)	NOT NULL	Name of the parameter
VALUE	VARCHAR2(4000)		Parameter value
SET_BY_USER	VARCHAR2(3)		Indicates whether the parameter value was set by the user (YES) or was not set by the user (NO). If NO, then the parameter is set to its default value. If YES, then the parameter may or may not be set to its default value.
SOURCE_DATABASE	VARCHAR2(128)		Global name of the container for which the capture parameter is defined

> **See Also:**
>
> "DBA_CAPTURE_PARAMETERS"

3.123 ALL_CAPTURE_PREPARED_DATABASE

ALL_CAPTURE_PREPARED_DATABASE displays information about when the local database was prepared for instantiation. If the local database was not prepared for instantiation, then this view contains no rows.

Related View

DBA_CAPTURE_PREPARED_DATABASE displays information about when the local database was prepared for instantiation.

Column	Datatype	NULL	Description
TIMESTAMP	DATE		Date and time at which the local database was ready to be instantiated
SUPPLEMENTAL_LOG_DATA_PK	VARCHAR2(8)		Status of database-level PRIMARY KEY COLUMNS supplemental logging: • IMPLICIT • EXPLICIT • NO
SUPPLEMENTAL_LOG_DATA_UI	VARCHAR2(8)		Status of database-level UNIQUE INDEX COLUMNS supplemental logging: • IMPLICIT • EXPLICIT • NO
SUPPLEMENTAL_LOG_DATA_FK	VARCHAR2(8)		Status of database-level FOREIGN KEY COLUMNS supplemental logging: • IMPLICIT • EXPLICIT • NO
SUPPLEMENTAL_LOG_DATA_ALL	VARCHAR2(8)		Status of database-level ALL COLUMNS supplemental logging: • IMPLICIT • EXPLICIT • NO

> **See Also:**
>
> "DBA_CAPTURE_PREPARED_DATABASE"

3.124 ALL_CAPTURE_PREPARED_SCHEMAS

ALL_CAPTURE_PREPARED_SCHEMAS displays information about the schemas prepared for instantiation that are accessible to the current user at the local database.

Related View

DBA_CAPTURE_PREPARED_SCHEMAS displays information about all schemas prepared for instantiation at the local database.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Name of the schema that is ready to be instantiated
TIMESTAMP	DATE		Date and time at which the schema was ready to be instantiated
SUPPLEMENTAL_LOG_DATA_PK	VARCHAR2(8)		Status of schema-level PRIMARY KEY COLUMNS supplemental logging: • IMPLICIT • EXPLICIT • NO
SUPPLEMENTAL_LOG_DATA_UI	VARCHAR2(8)		Status of schema-level UNIQUE INDEX COLUMNS supplemental logging: • IMPLICIT • EXPLICIT • NO
SUPPLEMENTAL_LOG_DATA_FK	VARCHAR2(8)		Status of schema-level FOREIGN KEY COLUMNS supplemental logging: • IMPLICIT • EXPLICIT • NO
SUPPLEMENTAL_LOG_DATA_ALL	VARCHAR2(8)		Status of schema-level ALL COLUMNS supplemental logging: • IMPLICIT • EXPLICIT • NO

See Also:

"DBA_CAPTURE_PREPARED_SCHEMAS"

3.125 ALL_CAPTURE_PREPARED_TABLES

ALL_CAPTURE_PREPARED_TABLES displays information about the tables prepared for instantiation that are accessible to the current user at the local database.

Related View

DBA_CAPTURE_PREPARED_TABLES displays information about all tables prepared for instantiation at the local database.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table that is ready to be instantiated
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table that is ready to be instantiated
SCN	NUMBER	NOT NULL	Smallest system change number (SCN) for which the table can be instantiated
TIMESTAMP	DATE		Date and time at which the table was ready to be instantiated
SUPPLEMENTAL_LOG_DATA_PK	VARCHAR2(8)		Status of table-level PRIMARY KEY COLUMNS supplemental logging: • IMPLICIT • EXPLICIT • NO
SUPPLEMENTAL_LOG_DATA_UI	VARCHAR2(8)		Status of table-level UNIQUE INDEX COLUMNS supplemental logging: • IMPLICIT • EXPLICIT • NO
SUPPLEMENTAL_LOG_DATA_FK	VARCHAR2(8)		Status of table-level FOREIGN KEY COLUMNS supplemental logging: • IMPLICIT • EXPLICIT • NO
SUPPLEMENTAL_LOG_DATA_ALL	VARCHAR2(8)		Status of table-level ALL COLUMNS supplemental logging: • IMPLICIT • EXPLICIT • NO

See Also:

"DBA_CAPTURE_PREPARED_TABLES"

3.126 ALL_CATALOG

ALL_CATALOG displays the tables, clusters, views, synonyms, and sequences accessible to the current user.

Related Views

- DBA_CATALOG displays all tables, clusters, views, synonyms, and sequences in the entire database.
- USER_CATALOG displays the tables, clusters, views, synonyms, and sequences in the current user's schema. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the TABLE, CLUSTER, VIEW, SYNONYM, SEQUENCE, or UNDEFINED
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the TABLE, CLUSTER, VIEW, SYNONYM, SEQUENCE, or UNDEFINED
TABLE_TYPE	VARCHAR2(11)		Type of the TABLE, CLUSTER, VIEW, SYNONYM, SEQUENCE, or UNDEFINED

See Also:

- "DBA_CATALOG"
- "USER_CATALOG"

3.127 ALL_CERTIFICATES

ALL_CERTIFICATES displays the certificates accessible to the current user which are used for signature verification for blockchain tables.

Related Views

- DBA_CERTIFICATES displays all certificates in the database which are used for signature verification for blockchain tables.
- USER_CERTIFICATES displays the certificates added by the current user which are used for signature verification for blockchain tables. This view does not display the USER_NAME column.

Column	Datatype	NULL	Description
CERTIFICATE_ID	RAW(16)	NOT NULL	ID for the certificate
USER_NAME	VARCHAR2(128)	NOT NULL	User who added the certificate
DISTINGUISHED_NAME	VARCHAR2(2000)		Uniquely identifies the entity that owns the certificate
CERTIFICATE	BLOB		Contents of the certificate

> **See Also:**
>
> - "DBA_CERTIFICATES"
> - "USER_CERTIFICATES"

3.128 ALL_CLUSTER_HASH_EXPRESSIONS

ALL_CLUSTER_HASH_EXPRESSIONS displays hash functions for all hash clusters accessible to the current user.

Related Views

- DBA_CLUSTER_HASH_EXPRESSIONS displays hash functions for all hash clusters in the database.
- USER_CLUSTER_HASH_EXPRESSIONS displays hash functions for all hash clusters owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cluster
CLUSTER_NAME	VARCHAR2(128)	NOT NULL	Name of the cluster
HASH_EXPRESSION	LONG		Text of the hash function of the hash cluster

> **See Also:**
>
> - "DBA_CLUSTER_HASH_EXPRESSIONS"
> - "USER_CLUSTER_HASH_EXPRESSIONS"

3.129 ALL_CLUSTERING_DIMENSIONS

ALL_CLUSTERING_DIMENSIONS describes dimension tables associated with tables with an attribute clustering clause that the user owns or has system privileges for.

Related Views

- DBA_CLUSTERING_DIMENSIONS describes dimension tables associated with all tables with an attribute clustering clause in the database.
- USER_CLUSTERING_DIMENSIONS describes dimension tables associated with tables with an attribute clustering clause owned by the user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute clustering table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute clustering table

Column	Datatype	NULL	Description
DIMENSION_OWNER	VARCHAR2(128)	NOT NULL	Owner of the dimension table
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the dimension table

See Also:

- "DBA_CLUSTERING_DIMENSIONS"
- "USER_CLUSTERING_DIMENSIONS"
- The ALTER TABLE section in *Oracle Database SQL Language Reference* for information about using the CLUSTERING clause to create an attribute clustering table
- The CREATE TABLE section in *Oracle Database SQL Language Reference* for information about using the CLUSTERING clause to create an attribute clustering table
- *Oracle Database Data Warehousing Guide* for information about dimension tables
- *Oracle Database Data Warehousing Guide* for information about attribute clustering with zone maps

3.130 ALL_CLUSTERING_JOINS

ALL_CLUSTERING_JOINS describes joins to the dimension tables associated with tables with an attribute clustering clause the user owns or has system privileges for.

Related Views

- DBA_CLUSTERING_JOINS describes joins to the dimension tables associated with all tables with an attribute clustering clause in the database.
- USER_CLUSTERING_JOINS describes joins to the dimension tables associated with tables with an attribute clustering clause owned by the user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute clustering table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute clustering table
TAB1_OWNER	VARCHAR2(128)	NOT NULL	Table 1 owner of the join
TAB1_NAME	VARCHAR2(128)	NOT NULL	Table 1 name of the join
TAB1_COLUMN	VARCHAR2(128)	NOT NULL	Table 1 column name of the join
TAB2_OWNER	VARCHAR2(128)	NOT NULL	Table 2 owner of the join
TAB2_NAME	VARCHAR2(128)	NOT NULL	Table 2 name of the join
TAB2_COLUMN	VARCHAR2(128)	NOT NULL	Table 2 column name of the join

See Also:

- "DBA_CLUSTERING_JOINS"
- "USER_CLUSTERING_JOINS"
- The `ALTER TABLE` section in *Oracle Database SQL Language Reference* for information about using the `CLUSTERING` clause to create an attribute clustering table
- The `CREATE TABLE` section in *Oracle Database SQL Language Reference* for information about using the `CLUSTERING` clause to create an attribute clustering table
- *Oracle Database Data Warehousing Guide* for information about dimension tables
- *Oracle Database Data Warehousing Guide* for information about attribute clustering with zone maps

3.131 ALL_CLUSTERING_KEYS

`ALL_CLUSTERING_KEYS` describes clustering keys for tables with an attribute clustering clause accessible to the user.

Related Views

- `DBA_CLUSTERING_KEYS` describes clustering keys for all tables with an attribute clustering clause.
- `USER_CLUSTERING_KEYS` describes clustering keys for tables with an attribute clustering clause owned by the user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table on which the clustering clause is defined
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table on which the clustering clause is defined
DETAIL_OWNER	VARCHAR2(128)	NOT NULL	Owner of the detailed table contributing to the clustering keys
DETAIL_NAME	VARCHAR2(128)	NOT NULL	Name of the detailed table contributing to the clustering keys
DETAIL_COLUMN	VARCHAR2(128)	NOT NULL	Name of the detail column
POSITION	NUMBER	NOT NULL	Position of the column in the clustering clause
GROUPID	NUMBER	NOT NULL	Group ID of the column in the clustering clause

See Also:

- "DBA_CLUSTERING_KEYS"
- "USER_CLUSTERING_KEYS"
- The `ALTER TABLE` section in *Oracle Database SQL Language Reference* for information about using the `CLUSTERING` clause to create an attribute clustering table
- The `CREATE TABLE` section in *Oracle Database SQL Language Reference* for information about using the `CLUSTERING` clause to create an attribute clustering table
- *Oracle Database Data Warehousing Guide* for information about dimension tables
- *Oracle Database Data Warehousing Guide* for information about attribute clustering with zone maps

3.132 ALL_CLUSTERING_TABLES

`ALL_CLUSTERING_TABLES` describes tables with an attribute clustering clause that are accessible to the user.

Related Views

- `DBA_CLUSTERING_TABLES` describes all the tables with an attribute clustering clause.
- `USER_CLUSTERING_TABLES` describes the tables with an attribute clustering clause owned by the user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
CLUSTERING_TYPE	VARCHAR2(11)		Clustering type: • INTERLEAVED • LINEAR
ON_LOAD	VARCHAR2(3)		Indicates whether Oracle will cluster data on load (YES) or not (NO)
ON_DATAMOVEMENT	VARCHAR2(3)		Indicates whether Oracle will cluster data on data movement, for example, partition move (YES), or not (NO)

Column	Datatype	NULL	Description
VALID	VARCHAR2(3)		Indicates if clustering is valid (YES) or not (NO). For clustering with dimension tables, it is required that the joins of the fact table to the dimensions is via primary key or unique key on the dimension table. Therefore, dimension join keys must have a valid primary key or unique key constraint. If the primary key or unique key constraint is not valid, then clustering will not occur. If there are no joins in the CLUSTERING clause, then the value of this column is YES.
WITH_ZONEMAP	VARCHAR2(3)		Indicates if a zonemap was created with clustering (YES) or not (NO).
LAST_LOAD_CLST	TIMESTAMP(6)		Last time the clustering occurred on load
LAST_DATAMOVE_CLST	TIMESTAMP(6)		Last time the clustering occurred on data movement, for example, partition move

See Also:

- "DBA_CLUSTERING_TABLES"
- "USER_CLUSTERING_TABLES"
- The ALTER TABLE section in *Oracle Database SQL Language Reference* for information about using the CLUSTERING clause to create an attribute clustering table
- The CREATE TABLE section in *Oracle Database SQL Language Reference* for information about using the CLUSTERING clause to create an attribute clustering table
- *Oracle Database Data Warehousing Guide* for information about dimension tables
- *Oracle Database Data Warehousing Guide* for information about attribute clustering with zone maps

3.133 ALL_CLUSTERS

ALL_CLUSTERS describes all clusters accessible to the current user.

Related Views

- DBA_CLUSTERS describes all clusters in the database.
- USER_CLUSTERS describes all clusters owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cluster

Column	Datatype	NULL	Description
CLUSTER_NAME	VARCHAR2(128)	NOT NULL	Name of the cluster
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of the tablespace containing the cluster
PCT_FREE	NUMBER		Minimum percentage of free space in a block
PCT_USED	NUMBER		Minimum percentage of used space in a block
KEY_SIZE	NUMBER		Estimated size of cluster key plus associated rows
INI_TRANS	NUMBER	NOT NULL	Initial number of transactions
MAX_TRANS	NUMBER	NOT NULL	Maximum number of transactions
INITIAL_EXTENT	NUMBER		Size of the initial extent in bytes
NEXT_EXTENT	NUMBER		Size of secondary extents in bytes
MIN_EXTENTS	NUMBER	NOT NULL	Minimum number of extents allowed in the segment
MAX_EXTENTS	NUMBER	NOT NULL	Maximum number of extents allowed in the segment
PCT_INCREASE	NUMBER		Percentage increase in extent size
FREELISTS	NUMBER		Number of process freelists allocated to this segment
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to this segment
AVG_BLOCKS_PER_KEY	NUMBER		Number of blocks in the table divided by number of cluster keys
CLUSTER_TYPE	VARCHAR2(5)		Type of the cluster: • INDEX - B*-Tree index • HASH - Hash
FUNCTION	VARCHAR2(15)		If the cluster is a hash cluster, the hash function
HASHKEYS	NUMBER		If the cluster is a hash cluster, the number of hash keys (hash buckets)
DEGREE	VARCHAR2(10)		Number of threads per instance for scanning the cluster, or DEFAULT
INSTANCES	VARCHAR2(10)		Number of instances across which the cluster is to be scanned , or DEFAULT
CACHE	VARCHAR2(5)		Indicates whether the cluster is to be cached in the buffer cache (Y) or not (N)
BUFFER_POOL	VARCHAR2(7)		Buffer pool to be used for cluster blocks: • DEFAULT • KEEP • RECYCLE • NULL
FLASH_CACHE	VARCHAR2(7)		Database Smart Flash Cache hint to be used for cluster blocks: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.

Column	Datatype	NULL	Description
CELL_FLASH_CACHE	VARCHAR2(7)		Cell flash cache hint to be used for cluster blocks: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
SINGLE_TABLE	VARCHAR2(5)		Indicates whether this is a single-table cluster (Y) or not (N)
DEPENDENCIES	VARCHAR2(8)		Indicates whether row-level dependency tracking is enabled (ENABLED) or disabled (DISABLED)

See Also:

- "DBA_CLUSTERS"
- "USER_CLUSTERS"

3.134 ALL_CODE_ROLE_PRIVS

ALL_CODE_ROLE_PRIVS describes all the roles that are associated with program units owned or accessible by the current user.

Related Views

- DBA_CODE_ROLE_PRIVS describes all the roles that are associated with program units in the database.
- USER_CODE_ROLE_PRIVS describes all the roles that are associated with program units owned by current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Username of the owner of the object
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object
OBJECT_TYPE	VARCHAR2(9)		Type of the object
ROLE	VARCHAR2(128)	NOT NULL	The role associated with the object

See Also:

- "DBA_CODE_ROLE_PRIVS"
- "USER_CODE_ROLE_PRIVS"
- *Oracle Database Security Guide* for more information about granting and revoking roles to and from program units

3.135 ALL_COL_COMMENTS

ALL_COL_COMMENTS displays comments on the columns of the tables and views accessible to the current user.

Related Views

- DBA_COL_COMMENTS displays comments on the columns of all tables and views in the database.
- USER_COL_COMMENTS displays comments on the columns of the tables and views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the object
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
COMMENTS	VARCHAR2(4000)		Comment on the column
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs • *n*: This value is used for rows containing data that originate in the container with the ID *n* (*n*=1 if the data originates in root)

See Also:

- "DBA_COL_COMMENTS"
- "USER_COL_COMMENTS"

3.136 ALL_COL_PENDING_STATS

ALL_COL_PENDING_STATS describes the pending statistics of the columns accessible to the current user.

Related Views

- DBA_COL_PENDING_STATS describes the pending statistics of all columns in the database.
- USER_COL_PENDING_STATS describes the pending statistics of the columns owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table

Column	Datatype	NULL	Description
PARTITION_NAME	VARCHAR2(128)		Name of the partition
SUBPARTITION_NAME	VARCHAR2(128)		Name of the subpartition
COLUMN_NAME	VARCHAR2(128)		Name of the column
NUM_DISTINCT	NUMBER		Number of distinct values in the column
LOW_VALUE	RAW(32)		Low value in the column
HIGH_VALUE	RAW(32)		High value in the column
DENSITY	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT.
NUM_NULLS	NUMBER		Number of NULLs in the column
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
SAMPLE_SIZE	NUMBER		Sample size used in analyzing the column
LAST_ANALYZED	DATE		Most recent date on which the column was analyzed

See Also:

- "DBA_COL_PENDING_STATS"
- "USER_COL_PENDING_STATS"

3.137 ALL_COL_PRIVS

ALL_COL_PRIVS describes the following types of grants:

- Column object grants for which the current user is the object owner, grantor, or grantee
- Column object grants for which an enabled role or PUBLIC is the grantee

Related Views

- DBA_COL_PRIVS describes all column object grants in the database.
- USER_COL_PRIVS describes the column object grants for which the current user is the object owner, grantor, or grantee.

Column	Datatype	NULL	Description
GRANTOR	VARCHAR2(128)		Name of the user who performed the grant
GRANTEE	VARCHAR2(128)		Name of the user or role to whom access was granted
TABLE_SCHEMA	VARCHAR2(128)		Schema of the object

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2(128)		Name of the object
COLUMN_NAME	VARCHAR2(128)		Name of the column
PRIVILEGE	VARCHAR2(40)		Privilege on the column: • INSERT • REFERENCES • UPDATE
GRANTABLE	VARCHAR2(3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the privilege grant was inherited from another container (YES) or not (NO)

See Also:

- "DBA_COL_PRIVS"
- "USER_COL_PRIVS"

3.138 ALL_COL_PRIVS_MADE

ALL_COL_PRIVS_MADE describes the column object grants for which the current user is the object owner or grantor.

Related View

USER_COL_PRIVS_MADE describes the column object grants for which the current user is the object owner. This view does not display the OWNER column.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)		Name of the user or role to whom access was granted
OWNER	VARCHAR2(128)		Owner of the object
TABLE_NAME	VARCHAR2(128)		Name of the object
COLUMN_NAME	VARCHAR2(128)		Name of the column
GRANTOR	VARCHAR2(128)		Name of the user who performed the grant
PRIVILEGE	VARCHAR2(40)		Privilege on the column: • INSERT • REFERENCES • UPDATE

Column	Datatype	NULL	Description
GRANTABLE	VARCHAR2(3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the privilege grant was inherited from another container (YES) or not (NO)

> **See Also:**
>
> "USER_COL_PRIVS_MADE"

3.139 ALL_COL_PRIVS_RECD

ALL_COL_PRIVS_RECD describes the following types of grants:

- Column object grants for which the current user is the grantee
- Column object grants for which an enabled role or PUBLIC is the grantee

Related View

USER_COL_PRIVS_RECD describes the column object grants for which the current user is the grantee. This view does not display the GRANTEE column.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)		Name of the user or role to whom access was granted
OWNER	VARCHAR2(128)		Owner of the object
TABLE_NAME	VARCHAR2(128)		Name of the object
COLUMN_NAME	VARCHAR2(128)		Name of the column
GRANTOR	VARCHAR2(128)		Name of the user who performed the grant
PRIVILEGE	VARCHAR2(40)		Privilege on the column: • INSERT • REFERENCES • UPDATE
GRANTABLE	VARCHAR2(3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)

Column	Datatype	NULL	Description
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the privilege grant was inherited from another container (YES) or not (NO)

See Also:

"USER_COL_PRIVS_RECD"

3.140 ALL_COLL_TYPES

ALL_COLL_TYPES describes all named collection types (varrays and nested tables) accessible to the current user.

Related Views

- DBA_COLL_TYPES describes all named collection types in the database.
- USER_COLL_TYPES describes all named collection types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the collection
TYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the collection
COLL_TYPE	VARCHAR2(128)	NOT NULL	Description of the collection, such as VARYING ARRAY, [nested] TABLE
UPPER_BOUND	NUMBER		For varrays only, maximum size
ELEM_TYPE_MOD	VARCHAR2(7)		Type modifier of the element
ELEM_TYPE_OWNER	VARCHAR2(128)		Owner of the type upon which the collection is based. This value is useful primarily for a user-defined type.
ELEM_TYPE_NAME	VARCHAR2(128)		Name of the data type or user-defined type upon which the collection is based
LENGTH	NUMBER		Length of CHAR elements or maximum length of VARCHAR or VARCHAR2 elements
PRECISION	NUMBER		Decimal precision of NUMBER or DECIMAL elements; binary precision of FLOAT elements
SCALE	NUMBER		Scale of NUMBER or DECIMAL elements
CHARACTER_SET_NAME	VARCHAR2(44)		Name of the character set (CHAR_CS | NCHAR_CS)
ELEM_STORAGE	VARCHAR2(7)		Obsolete column

Column	Datatype	NULL	Description
NULLS_STORED	VARCHAR2(3)		Obsolete column
CHAR_USED	VARCHAR2(1)		Indicates whether the attribute uses BYTE length semantics (B) or CHAR length semantics (C). For NCHAR and NVARCHAR2 attribute types, this value is always C.

See Also:

- "DBA_COLL_TYPES"
- "USER_COLL_TYPES"

3.141 ALL_CONS_COLUMNS

ALL_CONS_COLUMNS describes columns that are accessible to the current user and that are specified in constraints.

Related Views

- DBA_CONS_COLUMNS describes all columns in the database that are specified in constraints.
- USER_CONS_COLUMNS describes columns that are owned by the current user and that are specified in constraints.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the constraint definition
CONSTRAINT_NAME	VARCHAR2(128)	NOT NULL	Name of the constraint definition If the constraint is inherited from a data use case domain specified for the column, a system-generated constraint name is displayed, not the constraint name specified in the data use case domain.
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table with the constraint definition
COLUMN_NAME	VARCHAR2(4000)		Name of the column or attribute of the object type column specified in the constraint definition **Note:** If you create a constraint on a user-defined REF column, the system creates the constraint on the attributes that make up the REF column. Therefore, the column names displayed in this view are the attribute names, with the REF column name as a prefix, in the following form: "REF_name"."attribute"
POSITION	NUMBER		Original position of the column or attribute in the definition of the object

Column	Datatype	NULL	Description
DOMAIN_OWNER	VARCHAR2(128)		If the constraint is inherited from a data use case domain specified for the column, the owner of the data use case domain
DOMAIN_NAME	VARCHAR2(128)		If the constraint is inherited from a data use case domain specified for the column, the name of the data use case domain

See Also:

- "DBA_CONS_COLUMNS"
- "USER_CONS_COLUMNS"

3.142 ALL_CONS_OBJ_COLUMNS

ALL_CONS_OBJ_COLUMNS displays information about the types that object columns (or attributes) or collection elements have been constrained to, in the tables accessible to the current user.

Related Views

- DBA_CONS_OBJ_COLUMNS displays information about the types that object columns (or attributes) or collection elements have been constrained to, in all tables in the database.
- USER_CONS_OBJ_COLUMNS displays information about the types that object columns (or attributes) or collection elements have been constrained to, in the tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table containing the object column or attribute
COLUMN_NAME	VARCHAR2(4000)		Fully qualified name of the object column or attribute
CONS_TYPE_OWNER	VARCHAR2(128)		Owner of the type that the column (or element) is constrained to
CONS_TYPE_NAME	VARCHAR2(128)		Name of the type that the column (or element) is constrained to
CONS_TYPE_ONLY	VARCHAR2(15)		Indicates whether the column (or element) is constrained to ONLY type (Y) or not (N)

> **See Also:**
>
> - "DBA_CONS_OBJ_COLUMNS"
> - "USER_CONS_OBJ_COLUMNS"

3.143 ALL_CONSTRAINTS

ALL_CONSTRAINTS describes constraint definitions on tables accessible to the current user.

Related Views

- DBA_CONSTRAINTS describes all constraint definitions in the database.
- USER_CONSTRAINTS describes constraint definitions on tables in the current user's schema.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the constraint definition
CONSTRAINT_NAME	VARCHAR2(128)		Name of the constraint definition If the constraint is defined in a data use case domain, this column displays a system-generated constraint name. The constraint name specified in the data use case domain is displayed in DOMAIN_CONSTRAINT_NAME.
CONSTRAINT_TYPE	VARCHAR2(1)		Type of the constraint definition: • C - Check constraint on a table • P - Primary key • U - Unique key • R - Referential integrity • V - With check option, on a view • O - With read only, on a view • H - Hash expression • F - Constraint that involves a REF column • S - Supplemental logging
TABLE_NAME	VARCHAR2(128)		Name associated with the table (or view) with the constraint definition
SEARCH_CONDITION	LONG		Text of search condition for a check constraint. This column returns the correct value only when the row originates from the current container.
SEARCH_CONDITION_VC	VARCHAR2(4000)		Text of search condition for a check constraint. This column may truncate the search condition.
R_OWNER	VARCHAR2(128)		Owner of the table referred to in a referential constraint
R_CONSTRAINT_NAME	VARCHAR2(128)		Name of the unique constraint definition for the referenced table
DOMAIN_OWNER	VARCHAR2(128)		If the constraint is inherited from a data use case domain, the owner of the data use case domain

Column	Datatype	NULL	Description
DOMAIN_NAME	VARCHAR2(128)		If the constraint is inherited from a data use case domain, the name of the data use case domain
DOMAIN_CONSTRAINT_NAME	VARCHAR2(128)		If the constraint is inherited from a data use case domain, the name of the constraint definition, as specified in the data use case domain
DELETE_RULE	VARCHAR2(9)		Delete rule for a referential constraint: • CASCADE • SET NULL • NO ACTION
STATUS	VARCHAR2(8)		Enforcement status of the constraint: • ENABLED • DISABLED
DEFERRABLE	VARCHAR2(14)		Indicates whether the constraint is deferrable (DEFERRABLE) or not (NOT DEFERRABLE)
DEFERRED	VARCHAR2(9)		Indicates whether the constraint was initially deferred (DEFERRED) or not (IMMEDIATE)
VALIDATED	VARCHAR2(13)		When STATUS = ENABLED, possible values are: • VALIDATED - All data obeys the constraint (that is, the existing data in the table was validated when the constraint was enabled, as well as any subsequent data entered into the table) • NOT VALIDATED - All data may not obey the constraint (that is, the existing data in the table was not validated when the constraint was enabled, but subsequent data entered into the table was validated) When STATUS = DISABLED, possible values are: • VALIDATED - All data obeys the constraint, but the unique index on the constraint has been dropped. This setting is useful in data warehousing environments, but has some restrictions. Refer to *Oracle Database Data Warehousing Guide* for more information on this setting. • NOT VALIDATED - All data may not obey the constraint
GENERATED	VARCHAR2(14)		Indicates whether the name of the constraint is user-generated (USER NAME) or system-generated (GENERATED NAME) If the constraint is defined in a data use case domain, the value of this column is always GENERATED NAME and applies to the system-generated name for the constraint (CONSTRAINT_NAME), not the user-specified name for the constraint (DOMAIN_CONSTRAINT_NAME).

Column	Datatype	NULL	Description
BAD	VARCHAR2(3)		Indicates whether this constraint specifies a century in an ambiguous manner (BAD) or not (NULL). To avoid errors resulting from this ambiguity, rewrite the constraint using the TO_DATE function with a four-digit year. **See Also:** the TO_DATE function in *Oracle Database SQL Language Reference* and *Oracle Database Development Guide*
RELY	VARCHAR2(4)		When VALIDATED = NOT VALIDATED, this column indicates whether the constraint is to be taken into account for query rewrite (RELY) or not (NULL). When VALIDATED = VALIDATED, this column is not meaningful. **See Also:** *constraints* in *Oracle Database SQL Language Reference*
PRECHECK	VARCHAR2(10)		Indicates whether the constraint is a precheckable JSON constraint (PRECHECK) or not (NOPRECHECK)
LAST_CHANGE	DATE		When the constraint was last enabled or disabled
INDEX_OWNER	VARCHAR2(128)		Name of the user owning the index
INDEX_NAME	VARCHAR2(128)		Name of the index (only shown for unique and primary-key constraints)
INVALID	VARCHAR2(7)		Indicates whether the constraint is invalid (INVALID) or not (NULL)
VIEW_RELATED	VARCHAR2(14)		Indicates whether the constraint depends on a view (DEPEND ON VIEW) or not (NULL)
ORIGIN_CON_ID	VARCHAR2(256)		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)

See Also:

- "DBA_CONSTRAINTS"
- "USER_CONSTRAINTS"

3.144 ALL_CONTEXT

ALL_CONTEXT describes all context namespaces in the current session for which attributes and values have been specified using the DBMS_SESSION.SET_CONTEXT procedure. This view does not display the TYPE and ORIGIN_CON_ID columns.

Related View

DBA_CONTEXT describes all context namespaces defined in the database, regardless whether any attributes have been specified for them using the DBMS_SESSION.SET_CONTEXT procedure.

Column	Datatype	NULL	Description
NAMESPACE	VARCHAR2(128)	NOT NULL	Name of the context namespace
SCHEMA	VARCHAR2(128)	NOT NULL	Schema name of the designated package that can set attributes using this namespace
PACKAGE	VARCHAR2(128)	NOT NULL	Package name of the designated package that can set attributes using this namespace

See Also:

- "DBA_CONTEXT"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SESSION.SET_CONTEXT procedure

3.145 ALL_CREDENTIALS

ALL_CREDENTIALS lists all credentials visible to the user.

Related Views

- DBA_CREDENTIALS lists all credentials in the database.
- USER_CREDENTIALS lists credentials owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the credential
CREDENTIAL_NAME	VARCHAR2(128)	NOT NULL	Name of the credential
USERNAME	VARCHAR2(128)		Name of the user that will be used to log in to the remote database or the remote or local operating system
WINDOWS_DOMAIN	VARCHAR2(30)		For a Windows target, the Windows domain to use when logging in
COMMENTS	VARCHAR2(4000)		Comments on the credential

Column	Datatype	NULL	Description
ENABLED	VARCHAR2(5)		Indicates whether this credential is enabled (TRUE) or not (FALSE)

Note:

DBMS_CREDENTIAL lists credentials that can be used to run external procedures, or by DBMS_SCHEDULER for remote or external jobs, or for storing or retrieving files from the operating system.

If a credential is disabled, then any of the actions above that attempts to use the credential will fail.

See Also:

- "DBA_CREDENTIALS"
- "USER_CREDENTIALS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_CREDENTIAL package
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SCHEDULER package

3.146 ALL_CUBE_ATTR_VISIBILITY

ALL_CUBE_ATTR_VISIBILITY describes the OLAP attributes visible for the dimensions, hierarchies, and levels accessible to the current user.

Related Views

- DBA_CUBE_ATTR_VISIBILITY describes all OLAP attributes visible for the dimensions, hierarchies, and levels in the database.
- USER_CUBE_ATTR_VISIBILITY describes the OLAP attributes visible for the dimensions, hierarchies, and levels owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the cube dimension
DIMENSION_NAME	VARCHAR2(128)		Name of a cube dimension (such as TIME)
ATTRIBUTE_NAME	VARCHAR2(128)		Name of an attribute of the dimension (such as LONG_DESCRIPTION or END_DATE)
HIERARCHY_NAME	VARCHAR2(128)		Name of a hierarchy for the dimension (such as CALENDAR)

Column	Datatype	NULL	Description
LEVEL_NAME	VARCHAR2(128)		Name of the dimension level (such as MONTH)
FROM_TYPE	VARCHAR2(10)		Identifies the dimension type that the current row derives the attribute visibility from. Possible values: • DIMENSION - Derives the attribute visibility from itself. • HIERARCHY - Derives the attribute visibility from the VisibleAttributes explicitly set on the associated DIMENSION or itself. • DIM_LEVEL - Derives the attribute visibility from the VisibleAttributes explicitly set on the associated DIMENSION or itself. • HIER_LEVEL - Derives the attribute visibility from the VisibleAttributes explicitly set on the associated DIMENSION, HIERARCHY, DIM_LEVEL, or itself.
TO_TYPE	VARCHAR2(10)		Identifies the dimension type for the current row. Possible values: • DIMENSION - When the TO_TYPE is DIMENSION, then only the DIMENSION_NAME is populated. • HIERARCHY - When the TO_TYPE is HIERARCHY, then only the DIMENSION_NAME and HIERARCHY_NAME are populated. • DIM_LEVEL - When the TO_TYPE is DIM_LEVEL, then only the DIMENSION_NAME and LEVEL_NAME are populated. • HIER_LEVEL - When the TO_TYPE is HIER_LEVEL, then only the HIERARCHY_NAME and LEVEL_NAME are populated.

See Also:

- "DBA_CUBE_ATTR_VISIBILITY"
- "USER_CUBE_ATTR_VISIBILITY"

3.147 ALL_CUBE_ATTRIBUTES

ALL_CUBE_ATTRIBUTES describes the attributes for the OLAP cube dimensions accessible to the current user.

Related Views

- DBA_CUBE_ATTRIBUTES describes the attributes for all OLAP cube dimensions in the database.
- USER_CUBE_ATTRIBUTES describes the attributes for the OLAP cube dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cube dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of a cube dimension (such as TIME)
ATTRIBUTE_NAME	VARCHAR2(128)	NOT NULL	Name of an attribute of the dimension (such as LONG_DESCRIPTION or END_DATE)
ATTRIBUTE_ID	NUMBER	NOT NULL	ID of the attribute of the dimension
TARGET_DIMENSION_NAME	VARCHAR2(128)		Name of the target dimension of the attribute
ATTRIBUTE_ROLE	VARCHAR2(17)		Special role this attribute plays; NULL if none: • SHORT_DESCRIPTION • LONG_DESCRIPTION • DESCRIPTION • TIME_SPAN • END_DATE
DESCRIPTION	NVARCHAR2(300)		Description of the attribute in the session language
ATTRIBUTE_GROUP_NAME	VARCHAR2(200)		Name of the attribute group
DATA_TYPE	VARCHAR2(106)		Data type of the attribute, (such as VARCHAR2 or FLOAT)
DATA_LENGTH	NUMBER	NOT NULL	Length of a text data type
DATA_PRECISION	NUMBER		Precision of a numeric data type
DATA_SCALE	NUMBER		Scale of a numeric data type
CREATE_INDEX	VARCHAR2(3)		Create index flag of the OLAP attribute. Possible values: • YES: The attribute is represented in the AW as a relation. Setting CreateIndex="True" in the metadata guarantees that it will be represented in the AW as a relation. • NO: The attribute is not represented in the AW as a relation. Setting CreateIndex="False" in the metadata does not guarantee that it will be represented in the AW a a variable; the system will make that determination.
IS_MULTI_LINGUAL	VARCHAR2(3)		Shows the setting for the IsMultiLingual flag of the OLAP Atttribute. Possible values: • YES: The attribute is set as multilingual. Setting IsMultiLingual to True in the metadata means that the attribute can have a value per language instead of a single value. • NO: The attribute is not set as multilingual. Setting IsMultiLingual to False in the metadata means that the attribute has only one value, independent of language.

> **See Also:**
>
> - "DBA_CUBE_ATTRIBUTES"
> - "USER_CUBE_ATTRIBUTES"

3.148 ALL_CUBE_BUILD_PROCESSES

ALL_CUBE_BUILD_PROCESSES describes the OLAP build processes and maintenance scripts accessible to the current user.

Related Views

- DBA_CUBE_BUILD_PROCESSES describes all OLAP build processes and maintenance scripts in the database.
- USER_CUBE_BUILD_PROCESSES describes the OLAP build processes and maintenance scripts owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the build process
BUILD_PROCESS_NAME	VARCHAR2(128)	NOT NULL	Name of the build process
BUILD_PROCESS_ID	NUMBER	NOT NULL	ID of the build process
BUILD_PROCESS	CLOB		Syntax of the build process
DESCRIPTION	NVARCHAR2(300)		Description of the build process in the session language

> **See Also:**
>
> - "DBA_CUBE_BUILD_PROCESSES"
> - "USER_CUBE_BUILD_PROCESSES"

3.149 ALL_CUBE_CALCULATED_MEMBERS

ALL_CUBE_CALCULATED_MEMBERS describes the calculated members for the OLAP cube dimensions accessible to the current user.

Related Views

- DBA_CUBE_CALCULATED_MEMBERS describes the calculated members for all OLAP cube dimensions in the database.
- USER_CUBE_CALCULATED_MEMBERS describes the calculated members for the OLAP cube dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cube dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of a cube dimension
MEMBER_NAME	VARCHAR2(128)	NOT NULL	Name of a calculated member in the cube dimension
IS_CUSTOM_AGGREGATE	VARCHAR2(3)		Indicates whether the calculated member is a custom aggregate (YES) or not (NO)
STORAGE_TYPE	VARCHAR2(10)		Storage type of the calculated member: • DYNAMIC - Value of the member is calculated for a query • PRECOMPUTE - Value of the member is calculated and stored during data maintenance
EXPRESSION	CLOB		Expression used to generate the value of the calculated member

See Also:

- "DBA_CUBE_CALCULATED_MEMBERS"
- "USER_CUBE_CALCULATED_MEMBERS"

3.150 ALL_CUBE_DIM_LEVELS

ALL_CUBE_DIM_LEVELS describes the OLAP dimension levels accessible to the current user.

Related Views

- DBA_CUBE_DIM_LEVELS describes all OLAP dimension levels in the database.
- USER_CUBE_DIM_LEVELS describes the OLAP dimension levels owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of a dimension, such as CUSTOMER
LEVEL_NAME	VARCHAR2(128)	NOT NULL	Name of a level in the dimension, such as WAREHOUSE
LEVEL_ID	NUMBER	NOT NULL	ID of the dimension level
DESCRIPTION	NVARCHAR2(300)		Description of the dimension level in the session language

> **See Also:**
>
> - "DBA_CUBE_DIM_LEVELS"
> - "USER_CUBE_DIM_LEVELS"

3.151 ALL_CUBE_DIM_MODELS

ALL_CUBE_DIM_MODELS describes the models for the OLAP dimensions accessible to the current user.

Related Views

- DBA_CUBE_DIM_MODELS describes the models for all OLAP dimensions in the database.
- USER_CUBE_DIM_MODELS describes the models for the OLAP dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cube dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of a cube dimension
MODEL_NAME	VARCHAR2(128)	NOT NULL	Name of a model for the cube dimension
MODEL_ID	NUMBER	NOT NULL	ID of the model
DESCRIPTION	NVARCHAR2(300)		Description of the model in the session language

> **See Also:**
>
> - "DBA_CUBE_DIM_MODELS"
> - "USER_CUBE_DIM_MODELS"

3.152 ALL_CUBE_DIM_VIEW_COLUMNS

ALL_CUBE_DIM_VIEW_COLUMNS describes the columns of the relational views of the OLAP cube dimensions accessible to the current user.

Related Views

- DBA_CUBE_DIM_VIEW_COLUMNS describes the columns of the relational views of all OLAP cube dimensions in the database.
- USER_CUBE_DIM_VIEW_COLUMNS describes the columns of the relational views of the OLAP cube dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the cube dimension
DIMENSION_NAME	VARCHAR2(128)		Name of a cube dimension, such as PRODUCT
VIEW_NAME	VARCHAR2(128)		Name of a view of the dimension, such as PRODUCT_VIEW
COLUMN_NAME	VARCHAR2(128)		Name of a column in the view, such as LONG_DESCRIPTION or WAREHOUSE_ID
COLUMN_TYPE	VARCHAR2(11)		Type of the column: • KEY - A key of the dimension view (that is, the dimension value itself) • LEVEL_NAME - Name of the level (if any) corresponding to a row in the view • DIM_ORDER - A column by which the results may be ordered (if present) • MEMBER_TYPE • ATTRIBUTE - An attribute owned by the dimension
OBJECT_NAME	VARCHAR2(128)		Name of the level or attribute represented in the column, such as LONG_DESCRIPTION or WAREHOUSE_ID

See Also:

- "DBA_CUBE_DIM_VIEW_COLUMNS"
- "USER_CUBE_DIM_VIEW_COLUMNS"

3.153 ALL_CUBE_DIM_VIEWS

ALL_CUBE_DIM_VIEWS describes the relational views of the OLAP dimensions accessible to the current user.

Related Views

- DBA_CUBE_DIM_VIEWS describes the relational views of all OLAP dimensions in the database.
- USER_CUBE_DIM_VIEWS describes the relational views of the OLAP dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cube dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of a cube dimension, such as PRODUCT
VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of a view of the cube dimension, such as PRODUCT_VIEW

See Also:

- "DBA_CUBE_DIM_VIEWS"
- "USER_CUBE_DIM_VIEWS"

3.154 ALL_CUBE_DIMENSIONALITY

ALL_CUBE_DIMENSIONALITY describes the dimension order for the OLAP cubes accessible to the current user.

Related Views

- DBA_CUBE_DIMENSIONALITY describes the dimension order for all OLAP cubes in the database.
- USER_CUBE_DIMENSIONALITY describes the dimension order for the OLAP cubes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cube
CUBE_NAME	VARCHAR2(128)	NOT NULL	Name of a cube, such as UNITS_CUBE
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of a dimension of the cube, such as PRODUCT
DIMENSIONALITY_NAME	VARCHAR2(200)		The name of a dimensionality of the cube. For example, a cube dimensioned by the PRODUCT dimension can have a product dimension named PRODUCT_DIM.
DIMENSIONALITY_ID	NUMBER	NOT NULL	ID of the cube dimensionality
ORDER_NUM	NUMBER	NOT NULL	Order number of the dimension in the cube
IS_SPARSE	NUMBER		Indicates whether the dimension is sparse in the cube (1) or not sparse (0)
ET_ATTR_PREFIX	VARCHAR2(200)		Specifies the prefix that will be added to the column names in the Materialized Views to ensure uniqueness. If the user does not specify an ET_ATTR_PREFIX for any dimensions in a cube, then they default in the pattern D1_, D2_, and so on.

See Also:

- "DBA_CUBE_DIMENSIONALITY"
- "USER_CUBE_DIMENSIONALITY"

3.155 ALL_CUBE_DIMENSIONS

ALL_CUBE_DIMENSIONS describes the OLAP cube dimensions accessible to the current user.

Related Views

- DBA_CUBE_DIMENSIONS describes all OLAP cube dimensions in the database.
- USER_CUBE_DIMENSIONS describes the OLAP cube dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cube dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of a cube dimension, such as TIME
DIMENSION_ID	NUMBER	NOT NULL	ID of the cube dimension
DIMENSION_TYPE	VARCHAR2(17)		Type of the OLAP cube dimension: • STANDARD • TIME
AW_NAME	VARCHAR2(128)		Name of the analytic workspace that contains the cube dimension, such as GLOBAL
DEFAULT_HIERARCHY_NAME	VARCHAR2(128)		Name of the default hierarchy for the cube dimension, such as FISCAL
DESCRIPTION	NVARCHAR2(300)		Description of the cube dimension in the session language
HIERARCHY_CONSISTENCY_RULE	VARCHAR2(200)		Hierarchy consistency rule of the OLAP cube dimension. Possible values: • CONSISTENT • STAR_CONSISTENT • SOLVE_CONSISTENT
ADD_UNIQUE_KEY_PREFIX	VARCHAR2(3)		Add_Unique_Key_Prefix flag of the OLAP cube dimension. Possible values: • YES: This is the value if AddUniqueKeyPrefix="True" was set in the metadata. This tells the system to add the level name prefix to the dimension members. This should be done when a dimension member can have the same value across different levels, for example, New York (state) and New York (city). • NO: This is the value if AddUniqueKeyPrefix="True" was not set in the metadata.
CUSTOM_ORDER	CLOB		The textual representation of the sort orderby clause used to load dimension members into the AW

> **See Also:**
>
> - "DBA_CUBE_DIMENSIONS"
> - "USER_CUBE_DIMENSIONS"

3.156 ALL_CUBE_HIER_LEVELS

ALL_CUBE_HIER_LEVELS describes the hierarchy levels for the OLAP cube dimensions accessible to the current user.

Related Views

- DBA_CUBE_HIER_LEVELS describes the hierarchy levels for all OLAP cube dimensions in the database.
- USER_CUBE_HIER_LEVELS describes the hierarchy levels for the OLAP cube dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cube dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of a cube dimension, such as TIME
HIERARCHY_NAME	VARCHAR2(128)	NOT NULL	Name of a hierarchy for the dimension, such as CALENDAR
LEVEL_NAME	VARCHAR2(128)	NOT NULL	Name of the dimension level, such as MONTH
HIERARCHY_LEVEL_ID	NUMBER	NOT NULL	ID of the hierarchy level
ORDER_NUM	NUMBER	NOT NULL	Order number of the level within the hierarchy; 0 is the top level
DESCRIPTION	NVARCHAR2(300)		Description of the level in the session language

> **See Also:**
>
> - "DBA_CUBE_HIER_LEVELS"
> - "USER_CUBE_HIER_LEVELS"

3.157 ALL_CUBE_HIER_VIEW_COLUMNS

ALL_CUBE_HIER_VIEW_COLUMNS describes the columns of the relational hierarchy views of the OLAP cube dimensions accessible to the current user.

Related Views

- DBA_CUBE_HIER_VIEW_COLUMNS describes the columns of the relational hierarchy views of all OLAP cube dimensions in the database.

- USER_CUBE_HIER_VIEW_COLUMNS describes the columns of the relational hierarchy views of the OLAP cube dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the cube dimension
DIMENSION_NAME	VARCHAR2(128)		Name of a cube dimension, such as TIME
HIERARCHY_NAME	VARCHAR2(128)		Name of a hierarchy for the cube dimension, such as CALENDAR
VIEW_NAME	VARCHAR2(128)		Name of a view of the hierarchy, such as TIME_CALENDAR_VIEW
COLUMN_NAME	VARCHAR2(128)		Name of a column in the view, such as CALENDAR_QUARTER or PARENT
COLUMN_TYPE	VARCHAR2(11)		Type of the column: • KEY - A key of the hierarchy view (that is, the hierarchy value itself) • PARENT - Dimension value of the parent of the current row in the view (or NULL if no parent) • LEVEL_NAME - Name of the level (if any) corresponding to a row in the view • DEPTH - Depth in the hierarchy tree of the current row in the view • HIER_ORDER - A column by which the results may be ordered (if present) • MEMBER_TYPE • ATTRIBUTE - An attribute owned by the hierarchy • LEVEL - One of the level columns comprising the hierarchy
OBJECT_NAME	VARCHAR2(128)		Name of a level or attribute for the dimension

See Also:

- "DBA_CUBE_HIER_VIEW_COLUMNS"
- "USER_CUBE_HIER_VIEW_COLUMNS"

3.158 ALL_CUBE_HIER_VIEWS

ALL_CUBE_HIER_VIEWS describes the hierarchies for the OLAP cube dimensions accessible to the current user.

Related Views

- DBA_CUBE_HIER_VIEWS describes the hierarchies for all OLAP cube dimensions in the database.
- USER_CUBE_HIER_VIEWS describes the hierarchies for the OLAP cube dimensions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cube dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of a cube dimension, such as TIME
HIERARCHY_NAME	VARCHAR2(128)	NOT NULL	Name of a hierarchy for the cube dimension, such as CALENDAR
VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of a view of the hierarchy, such as TIME_CALENDAR_VIEW

See Also:

- "DBA_CUBE_HIER_VIEWS"
- "USER_CUBE_HIER_VIEWS"

3.159 ALL_CUBE_HIERARCHIES

ALL_CUBE_HIERARCHIES describes the OLAP dimension hierarchies accessible to the current user.

Related Views

- DBA_CUBE_HIERARCHIES describes all OLAP dimension hierarchies in the database.
- USER_CUBE_HIERARCHIES describes the OLAP dimension hierarchies owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of a dimension, such as TIME
HIERARCHY_NAME	VARCHAR2(128)	NOT NULL	Name of a hierarchy for the dimension, such as CALENDAR
HIERARCHY_ID	NUMBER	NOT NULL	ID of the hierarchy
HIERARCHY_TYPE	VARCHAR2(5)		Type of the hierarchy: • LEVEL • VALUE
DESCRIPTION	NVARCHAR2(300)		Description of the hierarchy in the session language
IS_RAGGED	NUMBER		Indicates whether ragged hierarchies are permitted in subsequent builds. User dimensions that are enabled for materialized views and Time dimensions are set to 0. Builds then check the data for ragged hierarchies and fail if one is detected. When User dimensions are set to 1, the builds do not check for ragged hierarchies.

Column	Datatype	NULL	Description
IS_SKIP_LEVEL	NUMBER		Indicates whether skip-level hierarchies are permitted in subsequent builds. User dimensions that are enabled for materialized views and Time dimensions are set to 0. Builds then check the data for skip-level hierarchies and fail if one is detected. When User dimensions are set to 1, the builds do not check for skip-level hierarchies.
REFRESH_MVIEW_NAME	VARCHAR2(200)		Name of the Refresh Materialized View associated with the hierarchy
CUSTOM_ORDER	CLOB		The textual representation of the sort orderby clause used to load dimension members of the hierarchy into the AW

See Also:

- "DBA_CUBE_HIERARCHIES"
- "USER_CUBE_HIERARCHIES"

3.160 ALL_CUBE_MEASURES

ALL_CUBE_MEASURES describes the measures for the OLAP cubes accessible to the current user.

Related Views

- DBA_CUBE_MEASURES describes the measures for all OLAP cubes in the database.
- USER_CUBE_MEASURES describes the measures for the OLAP cubes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cube
CUBE_NAME	VARCHAR2(128)	NOT NULL	Name of a cube, such as UNITS_CUBE
MEASURE_NAME	VARCHAR2(128)	NOT NULL	Name of a measure in the cube, such as SALES
MEASURE_ID	NUMBER	NOT NULL	ID of a measure
OVERRIDE_SOLVE_SPEC	CLOB		Syntax text for the measure's consistent solve specification that overrides that of its cube
MEASURE_TYPE	VARCHAR2(7)		Type of the OLAP measure: • BASE - Base measures store the data • DERIVED - Derived measures calculate the data from base measures; also called calculated measures
EXPRESSION	CLOB		Expression that provides the values of the measure

Column	Datatype	NULL	Description
DESCRIPTION	NVARCHAR2(300)		Description of the measure in the session language
DATA_TYPE	VARCHAR2(106)		Data type of the measure, such as NUMBER
DATA_LENGTH	NUMBER	NOT NULL	Length of a character data type
DATA_PRECISION	NUMBER		Precision of a numeric data type
DATA_SCALE	NUMBER		Scale of a numeric data type
LOOP_VAR_OVERRIDE	VARCHAR2(200)		The value that overrides the $LOOP_VAR property of the OLAP derived measure
LOOP_DENSE_OVERRIDE	VARCHAR2(200)		The value that overrides the $LOOP_DENSE property of the OLAP derived measure
LOOP_TYPE	VARCHAR2(200)		The $LOOP_TYPE property of the OLAP derived measure. Possible values: • INNER • OUTER • DENSE

See Also:

- "DBA_CUBE_MEASURES"
- "USER_CUBE_MEASURES"

3.161 ALL_CUBE_NAMED_BUILD_SPECS

ALL_CUBE_NAMED_BUILD_SPECS describes the OLAP cube named build specifications in the database that are accessible by the user.

Related Views

- DBA_CUBE_NAMED_BUILD_SPECS describes the OLAP cube named build specifications in the database.
- USER_CUBE_NAMED_BUILD_SPECS describes the OLAP cube named build specifications in the database that are owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the OLAP named build specification
CUBE_NAME	VARCHAR2(128)	NOT NULL	Name of the OLAP cube
NAMED_BUILD_SPEC	CLOB		Name of the OLAP cube named build specification

> **See Also:**
>
> - "DBA_CUBE_NAMED_BUILD_SPECS"
> - "USER_CUBE_NAMED_BUILD_SPECS"

3.162 ALL_CUBE_SUB_PARTITION_LEVELS

ALL_CUBE_SUB_PARTITION_LEVELS describes the OLAP secondary partition levels in the database that are accessible by the user.

Related Views

- DBA_CUBE_SUB_PARTITION_LEVELS describes the OLAP secondary partition levels in the database.
- USER_CUBE_SUB_PARTITION_LEVELS describes the OLAP secondary partition levels in the database that are owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the OLAP secondary partition level
CUBE_NAME	VARCHAR2(128)		Name of the OLAP cube
SUB_PARTITION_LEVEL_NAME	VARCHAR2(200)		Name of the secondary partition level of the OLAP cube
PRECOMPUTE_PERCENT	NUMBER		Precompute percent of the secondary partition level of the OLAP cube
PARTITION_DIMENSION_NAME	VARCHAR2(128)		Name of the cube dimension for which there is a secondary partition level on the OLAP cube
PARTITION_HIERARCHY_NAME	VARCHAR2(128)		Name of the hierarchy for which there is a secondary partition level on the OLAP cube
PARTITION_LEVEL_NAME	VARCHAR2(128)		Name of the hierarchy level for which there is a secondary partition level on the OLAP cube
SUB_PARTITION_LEVEL_ORDER	NUMBER		Order number of the secondary partition level on the OLAP cube

> **See Also:**
>
> - "DBA_CUBE_SUB_PARTITION_LEVELS"
> - "USER_CUBE_SUB_PARTITION_LEVELS"

3.163 ALL_CUBE_VIEW_COLUMNS

ALL_CUBE_VIEW_COLUMNS describes the columns of the relational views of the OLAP cubes accessible to the current user.

Related Views

- DBA_CUBE_VIEW_COLUMNS describes the columns of relational views of all OLAP cubes in the database.
- USER_CUBE_VIEW_COLUMNS describes the columns of relational views of OLAP cubes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the cube
CUBE_NAME	VARCHAR2(128)		Name of a cube, such as UNITS_CUBE
VIEW_NAME	VARCHAR2(128)		Name of a view of the cube, such as PRODUCT_VIEW
COLUMN_NAME	VARCHAR2(128)		Name of a column in the view, such as DIM_KEY or LEVEL_NAME
COLUMN_TYPE	VARCHAR2(7)		Type of the column: • MEASURE • KEY
OBJECT_NAME	VARCHAR2(128)		Name of the measure or dimension represented in the column

See Also:

- "DBA_CUBE_VIEW_COLUMNS"
- "USER_CUBE_VIEW_COLUMNS"

3.164 ALL_CUBE_VIEWS

ALL_CUBE_VIEWS describes the relational views of the OLAP cubes accessible to the current user.

Related Views

- DBA_CUBE_VIEWS describes the relational views of all OLAP cubes in the database.
- USER_CUBE_VIEWS describes the relational views of the OLAP cubes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cube
CUBE_NAME	VARCHAR2(128)	NOT NULL	Name of a cube, such as UNITS_CUBE

Column	Datatype	NULL	Description
VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of a view of the cube, such as UNITS_CUBE_VIEW

See Also:

- "DBA_CUBE_VIEWS"
- "USER_CUBE_VIEWS"

3.165 ALL_CUBES

ALL_CUBES describes the OLAP cubes accessible to the current user.

Related Views

- DBA_CUBES describes all OLAP cubes in the database.
- USER_CUBES describes the OLAP cubes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the cube
CUBE_NAME	VARCHAR2(128)	NOT NULL	Name of a cube, such as UNITS_CUBE
CUBE_ID	NUMBER	NOT NULL	ID of a cube
AW_NAME	VARCHAR2(128)		Name of the analytic workspace that contains the cube, such as GLOBAL
CONSISTENT_SOLVE_SPEC	CLOB		Default aggregation rules for the cube
DESCRIPTION	NVARCHAR2(300)		Description of the cube in the session language
SPARSE_TYPE	VARCHAR2(200)		Text value indicating the type of sparsity for the OLAP cube
PRECOMPUTE_CONDITION	CLOB		Condition syntax representing the precompute condition of the OLAP cube
PRECOMPUTE_PERCENT	NUMBER		Percentage of aggregate data values that are calculated and stored during data maintenance. If the cube is partitioned, then this percentage is for the bottom partitions.
PRECOMPUTE_PERCENT_TOP	NUMBER		Percentage of aggregate data values in the top partition that are calculated and stored during data maintenance
PARTITION_DIMENSION_NAME	VARCHAR2(128)		Name of the dimension used to partition the cube, such as TIME
PARTITION_HIERARCHY_NAME	VARCHAR2(128)		Name of the dimension hierarchy used to partition the cube, such as CALENDAR
PARTITION_LEVEL_NAME	VARCHAR2(128)		Name of the level used to partition the cube, such as QUARTER

Column	Datatype	NULL	Description
REFRESH_MVIEW_NAME	VARCHAR2(200)		Name of the refresh materialized view for the OLAP cube
REWRITE_MVIEW_NAME	VARCHAR2(200)		Name of the rewrite materialized view for the OLAP cube
DEFAULT_BUILD_SPEC	CLOB		The default build specification for the OLAP cube
MEASURE_STORAGE	VARCHAR2(200)		The measure storage for the OLAP cube. Possible values: • INDEPENDENT • SHARED
SQL_CUBE_STORAGE_TYPE	CLOB		The SQL cube storage type for the OLAP cube. This value represents a SQL data type.
CUBE_STORAGE_TYPE	VARCHAR2(200)		The cube storage type for the OLAP cube. This value represents a DML data type.

See Also:

- "DBA_CUBES"
- "USER_CUBES"

3.166 ALL_DB_LINKS

ALL_DB_LINKS describes the database links accessible to the current user.

Related Views

- DBA_DB_LINKS describes all database links in the database.
- USER_DB_LINKS describes the database links owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the database link
DB_LINK	VARCHAR2(128)	NOT NULL	Name of the database link
USERNAME	VARCHAR2(128)		Name of the user to be used when connecting to a remote database
CREDENTIAL_NAME	VARCHAR2(128)		Name of the credential to be used when connecting to a remote database
CREDENTIAL_OWNER	VARCHAR2(128)		Owner of the credential to be used when connecting to a remote database
HOST	VARCHAR2(2000)		Oracle Net connect string
CREATED	DATE	NOT NULL	Creation time of the database link
HIDDEN	VARCHAR2(3)		For internal use only

Column	Datatype	NULL	Description
SHARD_INTERNAL	VARCHAR2(3)		Indicates whether the database link is used to support operations across sharded databases. Possible values: • YES: The database link is used and managed for to support sharded databases • NO: The database link is not used and managed to support sharded databases Users should not alter or delete database links that are used and managed to support sharded databases.
VALID	VARCHAR2(3)		Indicates whether the database link is valid and usable. Possible values: • YES: The database link is valid and usable. • NO: The database link is invalid and unusable.
INTRA_CDB	VARCHAR2(3)		For internal use only

See Also:

- "DBA_DB_LINKS"
- "USER_DB_LINKS"
- "DBA_DB_LINK_SOURCES"
- "DBA_EXTERNAL_SCN_ACTIVITY"

3.167 ALL_DEF_AUDIT_OPTS

ALL_DEF_AUDIT_OPTS contains default object-auditing options that will be applied when objects are created.

The output for each column takes one of the following forms:

- -/-: no default auditing
- S/-: auditing whenever successful
- -/S: auditing whenever not successful

Note:

This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

Column	Datatype	NULL	Description
ALT	VARCHAR2(3)		Auditing ALTER WHENEVER SUCCESSFUL / UNSUCCESSFUL
AUD	VARCHAR2(3)		Auditing AUDIT WHENEVER SUCCESSFUL / UNSUCCESSFUL
COM	VARCHAR2(3)		Auditing COMMENT WHENEVER SUCCESSFUL / UNSUCCESSFUL
DEL	VARCHAR2(3)		Auditing DELETE WHENEVER SUCCESSFUL / UNSUCCESSFUL
GRA	VARCHAR2(3)		Auditing GRANT WHENEVER SUCCESSFUL / UNSUCCESSFUL
IND	VARCHAR2(3)		Auditing INDEX WHENEVER SUCCESSFUL / UNSUCCESSFUL
INS	VARCHAR2(3)		Auditing INSERT WHENEVER SUCCESSFUL / UNSUCCESSFUL
LOC	VARCHAR2(3)		Auditing LOCK WHENEVER SUCCESSFUL / UNSUCCESSFUL
REN	VARCHAR2(3)		Auditing RENAME WHENEVER SUCCESSFUL / UNSUCCESSFUL
SEL	VARCHAR2(3)		Auditing SELECT WHENEVER SUCCESSFUL / UNSUCCESSFUL
UPD	VARCHAR2(3)		Auditing UPDATE WHENEVER SUCCESSFUL / UNSUCCESSFUL
EXE	VARCHAR2(3)		Auditing EXECUTE WHENEVER SUCCESSFUL / UNSUCCESSFUL
FBK	VARCHAR2(3)		Auditing FLASHBACK WHENEVER SUCCESSFUL / UNSUCCESSFUL
REA	VARCHAR2(3)		Auditing READ WHENEVER SUCCESSFUL / UNSUCCESSFUL

3.168 ALL_DEPENDENCIES

ALL_DEPENDENCIES describes dependencies between procedures, packages, functions, package bodies, and triggers accessible to the current user, including dependencies on views created without any database links. This view does not display the SCHEMAID column.

Related Views

- DBA_DEPENDENCIES describes all dependencies between objects in the database. This view does not display the SCHEMAID column.
- USER_DEPENDENCIES describes dependencies between objects in the current user's schema. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
NAME	VARCHAR2(128)	NOT NULL	Name of the object

Column	Datatype	NULL	Description
TYPE	VARCHAR2(18)		Type of the object
REFERENCED_OWNER	VARCHAR2(128)		Owner of the referenced object (remote owner if remote object)
REFERENCED_NAME	VARCHAR2(128)		Name of the referenced object
REFERENCED_TYPE	VARCHAR2(18)		Type of the referenced object
REFERENCED_LINK_NAME	VARCHAR2(128)		Name of the link to the parent object (if remote)
DEPENDENCY_TYPE	VARCHAR2(4)		Indicates whether the dependency is a REF dependency (REF) or not (HARD)

See Also:

- "DBA_DEPENDENCIES"
- "USER_DEPENDENCIES"

3.169 ALL_DEQUEUE_QUEUES

ALL_DEQUEUE_QUEUES describes all queues on which the current user has dequeue privileges. If the user has any Advanced Queuing system privileges, such as DEQUEUE ANY QUEUE or MANAGE ANY QUEUE, then this view describes all queues in the database.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the queue
NAME	VARCHAR2(128)	NOT NULL	Name of the queue
QUEUE_TABLE	VARCHAR2(128)	NOT NULL	Name of the table in which the queue data resides
QID	NUMBER	NOT NULL	Object number of the queue
QUEUE_TYPE	VARCHAR2(20)		Type of the queue. Possible values: • EXCEPTION_QUEUE • NORMAL_QUEUE
MAX_RETRIES	NUMBER		Maximum number of retries allowed when dequeuing from the queue
RETRY_DELAY	NUMBER		Time interval between retries
ENQUEUE_ENABLED	VARCHAR2(7)		Indicates whether the queue is enabled for enqueue (YES) or not (NO)
DEQUEUE_ENABLED	VARCHAR2(7)		Indicates whether the queue is enabled for dequeue (YES) or not (NO)
RETENTION	VARCHAR2(40)		Time interval that processed messages are retained in the queue, or FOREVER
USER_COMMENT	VARCHAR2(50)		User-specified comment
NETWORK_NAME	VARCHAR2(512)		Network name of the queue service
SHARDED	VARCHAR2(5)		TRUE if the queue is sharded, FALSE otherwise

Column	Datatype	NULL	Description
QUEUE_CATEGORY	VARCHAR2(25)		Queue category. Possible values: • Classic Queue • Sharded Queue • Transactional Event Queue
RECIPIENTS	VARCHAR2(8)		SINGLE or MULTIPLE recipients

3.170 ALL_DIM_ATTRIBUTES

ALL_DIM_ATTRIBUTES describes the relationship between a dimension level and a functionally dependent column. The level columns and the dependent column must be in the same table.

Related Views

- DBA_DIM_ATTRIBUTES describes all such dimension relationships in the database.
- USER_DIM_ATTRIBUTES describes all such dimension attributes in the current user's schema.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the dimension
ATTRIBUTE_NAME	VARCHAR2(128)		Name of the attribute
LEVEL_NAME	VARCHAR2(128)		Name of the hierarchy level
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Dependent column name
INFERRED	CHAR(1)		Indicates whether the attribute is inferred from a JOIN KEY specification (Y) or not (N)

See Also:

- "DBA_DIM_ATTRIBUTES"
- "USER_DIM_ATTRIBUTES"

3.171 ALL_DIM_CHILD_OF

ALL_DIM_CHILD_OF describes hierarchical relationships of 1 to *n* between the pairs of levels in the dimensions accessible to the current user.

Related Views

- DBA_DIM_CHILD_OF describes all such hierarchical relationships in the database.
- USER_DIM_CHILD_OF describes all such hierarchical attributes in the current user's schema.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the dimension
HIERARCHY_NAME	VARCHAR2(128)		Hierarchy name
POSITION	NUMBER	NOT NULL	Hierarchical position within this hierarchy, position 1 being the most detailed
CHILD_LEVEL_NAME	VARCHAR2(128)		Child side of 1:n relationship
JOIN_KEY_ID	VARCHAR2(40)		If non-null, then the child joins to the parent
PARENT_LEVEL_NAME	VARCHAR2(128)		Parent side of 1:n relationship in relation to the CHILD_LEVEL_NAME

See Also:

- "DBA_DIM_CHILD_OF"
- "USER_DIM_CHILD_OF"

3.172 ALL_DIM_HIERARCHIES

ALL_DIM_HIERARCHIES describes all dimension hierarchies accessible to the current user.

Related Views

- DBA_DIM_HIERARCHIES describes all such hierarchies in the database.
- USER_DIM_HIERARCHIES describes all such hierarchies owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the dimension
HIERARCHY_NAME	VARCHAR2(128)		Hierarchy name

See Also:

- "DBA_DIM_HIERARCHIES"
- "USER_DIM_HIERARCHIES"

3.173 ALL_DIM_JOIN_KEY

ALL_DIM_JOIN_KEY describes the joins between two dimension tables that are accessible to the current user. The join is always specified between a parent dimension level column and a child column.

Related Views

- DBA_DIM_JOIN_KEY describes all such joins in the database.
- USER_DIM_JOIN_KEY describes all such joins owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the dimension
DIM_KEY_ID	NUMBER	NOT NULL	Join key ID (unique within a dimension)
LEVEL_NAME	VARCHAR2(128)		Name of the hierarchy level
KEY_POSITION	NUMBER	NOT NULL	Ordinal position of the key column within the level
HIERARCHY_NAME	VARCHAR2(128)		Name of the hierarchy
CHILD_JOIN_OWNER	VARCHAR2(128)	NOT NULL	Owner of the join column table
CHILD_JOIN_TABLE	VARCHAR2(128)	NOT NULL	Name of the join column table
CHILD_JOIN_COLUMN	VARCHAR2(128)	NOT NULL	Name of the join column
CHILD_LEVEL_NAME	VARCHAR2(128)		Name of the child hierarchy level of the join key

See Also:

- "DBA_DIM_JOIN_KEY"
- "USER_DIM_JOIN_KEY"

3.174 ALL_DIM_LEVEL_KEY

ALL_DIM_LEVEL_KEY describes a column of a dimension level accessible to the current user. The position of a column within a level is specified by KEY_POSITION.

Related Views

- DBA_DIM_LEVEL_KEY describes all columns of dimension levels in the database.
- USER_DIM_LEVEL_KEY describes all columns of dimension levels owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the dimension

Column	Datatype	NULL	Description
LEVEL_NAME	VARCHAR2(128)		Name of the hierarchy level
KEY_POSITION	NUMBER	NOT NULL	Ordinal position of the key column within the level
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the key column

See Also:

- "DBA_DIM_LEVEL_KEY"
- "USER_DIM_LEVEL_KEY"

3.175 ALL_DIM_LEVELS

ALL_DIM_LEVELS describes the dimension levels accessible to the current user. All columns of a dimension level must come from the same relation.

Related Views

- DBA_DIM_LEVELS describes all dimension levels in the database.
- USER_DIM_LEVELS describes the levels of all dimensions owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the dimension
LEVEL_NAME	VARCHAR2(128)		Unique within a dimension
NUM_COLUMNS	NUMBER		Number of columns in the level definition
DETAILOBJ_OWNER	VARCHAR2(128)	NOT NULL	Owner of the detail object that the keys of this level come from
DETAILOBJ_NAME	VARCHAR2(128)	NOT NULL	Name of the table that the keys of this level come from
SKIP_WHEN_NULL	VARCHAR2(1)		Indicates whether the level is declared with the SKIP WHEN NULL clause (Y) or not (N)

See Also:

- "DBA_DIM_LEVELS"
- "USER_DIM_LEVELS"

3.176 ALL_DIMENSIONS

ALL_DIMENSIONS describes the dimension objects accessible to the current user.

Related Views

- DBA_DIMENSIONS describes all dimensions in the database.
- USER_DIMENSIONS describes the dimensions in the current user's schema.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the dimension
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the dimension
INVALID	VARCHAR2(1)		Indicates whether the dimension is invalid (Y) or valid (N)
COMPILE_STATE	VARCHAR2(13)		Compile status of the dimension: • INVALID • NEEDS_COMPILE • ERROR
REVISION	NUMBER		Dimension revision level

> **See Also:**
>
> - "DBA_DIMENSIONS"
> - "USER_DIMENSIONS"

3.177 ALL_DIRECTORIES

ALL_DIRECTORIES describes all directories accessible to the current user.

Related View

DBA_DIRECTORIES describes all directories in the database.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the directory (always SYS)
DIRECTORY_NAME	VARCHAR2(128)	NOT NULL	Name of the directory
DIRECTORY_PATH	VARCHAR2(4000)		Operating system pathname for the directory
ORIGIN_CON_ID	VARCHAR2(256)		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)

> **See Also:**
>
> "DBA_DIRECTORIES"

3.178 ALL_DOMAIN_COLS

ALL_DOMAIN_COLS describes columns of the data use case domains accessible to the current user.

This view displays use case domain column attributes. Use case domain columns with alternative data types are displayed for each possible data type.

Related Views

- DBA_DOMAIN_COLS describes columns of all data use case domains in the database.
- USER_DOMAIN_COLS describes columns of the data use case domains owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the use case domain
DOMAIN_NAME	VARCHAR2(128)	NOT NULL	Name of the use case domain
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
COLUMN_ID	NUMBER	NOT NULL	Column number in the use case domain
DATA_TYPE_ID	NUMBER	NOT NULL	Indicates whether this row represents the primary (1) or secondary (2) data type specification for the column
DATA_TYPE	VARCHAR2(106)		Data type of the column
DATA_LENGTH	NUMBER		Length of the column (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for NUMBER data type; binary precision for FLOAT data type; null for all other data types
DATA_SCALE	NUMBER		Digits to the right of the decimal point in a number; null for all other data types
NULLABLE	VARCHAR2(1)		Indicates whether a column allows NULLs. The value is N if there is a NOT NULL constraint on the column.
DATA_DEFAULT	CLOB		Default value for the column
DEFAULT_LENGTH	NUMBER		Length of the default value for the column (in bytes)
DEFAULT_ON_NULL	VARCHAR2(3)		Indicates whether the column has DEFAULT ON NULL for INSERT semantics (YES) or not (NO)
DEFAULT_ON_NULL_UPD	VARCHAR2(3)		Indicates whether the column has DEFAULT ON NULL for UPDATE semantics (YES) or not (NO)
CHARACTER_SET_NAME	VARCHAR2(44)		For character type columns, the name of the character set for the column: • CHAR_CS • NCHAR_CS

Column	Datatype	NULL	Description
CHAR_COL_DECL_LENGTH	NUMBER		For character type columns, the declared length of the column (in bytes)
COLLATION	VARCHAR2(100)		For character type columns, the collation for the column If a collation was not specified, the value of this column is null.
EXACT	BOOLEAN		Indicates whether the column data type specification is strict (TRUE) or not (FALSE)
CHAR_LENGTH	NUMBER		For character type columns, the length of the column (in characters)
DISCRIMINANT	BOOLEAN		Indicates whether the column is a discriminant column in a flexible domain (TRUE) or not (FALSE)

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_DOMAIN_COLS"
- "USER_DOMAIN_COLS"

3.179 ALL_DOMAIN_CONSTRAINTS

ALL_DOMAIN_CONSTRAINTS describes constraint definitions in the data use case domains accessible to the current user.

Related Views

- DBA_DOMAIN_CONSTRAINTS describes constraint definitions in all data use case domains in the database.
- USER_DOMAIN_CONSTRAINTS describes constraint definitions in the data use case domains owned by the current user.

Column	Datatype	NULL	Description
NAME	VARCHAR2(128)	NOT NULL	Name of the constraint definition
DOMAIN_OWNER	VARCHAR2(128)	NOT NULL	Owner of the use case domain in which the constraint is defined
DOMAIN_NAME	VARCHAR2(128)	NOT NULL	Name of the use case domain in which the constraint is defined

Column	Datatype	NULL	Description
CONSTRAINT_TYPE	VARCHAR2(1)		Type of the constraint definition The value of this column is always C, which means the constraint is either a check constraint or a NOT NULL constraint.
SEARCH_CONDITION	CLOB		Text of the search condition for a check constraint
STATUS	VARCHAR2(8)		Enforcement status of the constraint: • ENABLED • DISABLED
DEFERRABLE	VARCHAR2(14)		Indicates whether the constraint is deferrable (DEFERRABLE) or not (NOT DEFERRABLE)
DEFERRED	VARCHAR2(9)		Indicates whether the constraint was initially deferred (DEFERRED) or not (IMMEDIATE)
VALIDATED	VARCHAR2(13)		When STATUS = ENABLED, possible values are: • VALIDATED - All data obeys the constraint (that is, the existing data in the table was validated when the constraint was enabled, as well as any subsequent data entered into the table) • NOT VALIDATED - All data may not obey the constraint (that is, the existing data in the table was not validated when the constraint was enabled, but subsequent data entered into the table was validated) When STATUS = DISABLED, possible values are: • VALIDATED - All data obeys the constraint, but the unique index on the constraint has been dropped. This setting is useful in data warehousing environments, but has some restrictions. Refer to *Oracle Database Data Warehousing Guide* for more information on this setting. • NOT VALIDATED - All data may not obey the constraint
GENERATED	VARCHAR2(14)		Indicates whether the name of the constraint is user-generated (USER NAME) or system-generated (GENERATED NAME)
BAD	VARCHAR2(3)		Indicates whether the constraint specifies a century in an ambiguous manner (BAD) or not (null). To avoid errors resulting from this ambiguity, rewrite the constraint using the TO_DATE function with a four-digit year. **See Also:** the TO_DATE function in *Oracle Database SQL Language Reference* and *Oracle Database Development Guide*

Column	Datatype	NULL	Description
RELY	VARCHAR2(4)		When VALIDATED = NOT VALIDATED, this column indicates whether the constraint is to be taken into account for query rewrite (RELY) or not (null). When VALIDATED = VALIDATED, this column is not meaningful. **See Also:** *constraints* in *Oracle Database SQL Language Reference*
INVALID	VARCHAR2(7)		Indicates whether the constraint is invalid (INVALID) or not (null)
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_DOMAIN_CONSTRAINTS"
> - "USER_DOMAIN_CONSTRAINTS"

3.180 ALL_DOMAINS

ALL_DOMAINS describes the data use case domains accessible to the current user.

Related Views

- DBA_DOMAINS describes all data use case domains in the database.
- USER_DOMAINS describes the data use case domains owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the use case domain
NAME	VARCHAR2(128)	NOT NULL	Name of the use case domain
COLS	NUMBER	NOT NULL	Number of columns in the use case domain

Column	Datatype	NULL	Description
DISCRIMINANTCOLS	NUMBER		For flexible domains, the number of discriminant columns in the use case domain. Otherwise, 0.
BUILTIN	BOOLEAN		Indicates whether the use case domain is built-in (TRUE) or not (FALSE)
DATA_DISPLAY	CLOB		Text of the DISPLAY expression for the use case domain
DISPLAY_LENGTH	NUMBER		Length of the DISPLAY expression for the use case domain (in bytes) Null if a DISPLAY expression was not specified.
DATA_ORDER	CLOB		Text of the ORDER expression for the use case domain
ORDER_LENGTH	NUMBER		Length of the ORDER expression for the use case domain (in bytes) Null if an ORDER expression was not specified.
SELECTOR	CLOB		For flexible domains, the text of the domain selector expression. Otherwise, null.
SELECTOR_LENGTH	NUMBER		For flexible domains, the length of the domain selector expression (in bytes). Otherwise, null.
TYPE	VARCHAR2(10)		Use case domain type: • ENUMERATED • FLEXIBLE

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_DOMAINS"
- "USER_DOMAINS"

3.181 ALL_EDITION_COMMENTS

ALL_EDITION_COMMENTS describes the comments on the editions accessible to the current user.

Related View

DBA_EDITION_COMMENTS describes the comments on all editions in the database.

Column	Datatype	NULL	Description
EDITION_NAME	VARCHAR2(128)	NOT NULL	Name of the edition

Column	Datatype	NULL	Description
COMMENTS	VARCHAR2(4000)		Edition comments

> **See Also:**
>
> "DBA_EDITION_COMMENTS"

3.182 ALL_EDITIONING_VIEW_COLS

ALL_EDITIONING_VIEW_COLS describes the relationship between the columns of the editioning views accessible to the current user and the table columns to which they map.

Related Views

- DBA_EDITIONING_VIEW_COLS describes the relationship between the columns of all editioning views in the database and the table columns to which they map.
- USER_EDITIONING_VIEW_COLS describes the relationship between the columns of the editioning views owned by the current user and the table columns to which they map. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of an editioning view
VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of an editioning view
VIEW_COLUMN_ID	NUMBER	NOT NULL	Column number within the editioning view
VIEW_COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column in the editioning view
TABLE_COLUMN_ID	NUMBER	NOT NULL	Column number of a table column to which this editioning view column maps
TABLE_COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of a table column to which this editioning view column maps

> **See Also:**
>
> - "DBA_EDITIONING_VIEW_COLS"
> - "USER_EDITIONING_VIEW_COLS"

3.183 ALL_EDITIONING_VIEW_COLS_AE

ALL_EDITIONING_VIEW_COLS_AE describes the relationship between the columns of the editioning views (across all editions) accessible to the current user and the table columns to which they map.

Related Views

- DBA_EDITIONING_VIEW_COLS_AE describes the relationship between the columns of all editioning views (across all editions) in the database and the table columns to which they map.
- USER_EDITIONING_VIEW_COLS_AE describes the relationship between the columns of the editioning views (across all editions) owned by the current user and the table columns to which they map. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of an editioning view
VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of an editioning view
VIEW_COLUMN_ID	NUMBER	NOT NULL	Column number within the editioning view
VIEW_COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column in the editioning view
TABLE_COLUMN_ID	NUMBER	NOT NULL	Column number of a table column to which this editioning view column maps
TABLE_COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of a table column to which this editioning view column maps
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the editioning view is defined

See Also:

- "DBA_EDITIONING_VIEW_COLS_AE"
- "USER_EDITIONING_VIEW_COLS_AE"

3.184 ALL_EDITIONING_VIEWS

ALL_EDITIONING_VIEWS describes the editioning views accessible to the current user.

Related Views

- DBA_EDITIONING_VIEWS describes all editioning views in the database.
- USER_EDITIONING_VIEWS describes the editioning views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of an editioning view

Column	Datatype	NULL	Description
VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of an editioning view
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of an editioning view's base table

See Also:

- "DBA_EDITIONING_VIEWS"
- "USER_EDITIONING_VIEWS"

3.185 ALL_EDITIONING_VIEWS_AE

ALL_EDITIONING_VIEWS_AE describes the editioning views (across all editions) accessible to the current user.

Related Views

- DBA_EDITIONING_VIEWS_AE describes all editioning views (across all editions) in the database.
- USER_EDITIONING_VIEWS_AE describes the editioning views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of an editioning view
VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of an editioning view
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of an editioning view's base table
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the editioning view is defined

See Also:

- "DBA_EDITIONING_VIEWS_AE"
- "USER_EDITIONING_VIEWS_AE"

3.186 ALL_EDITIONS

ALL_EDITIONS describes the editions accessible to the current user.

Related View

DBA_EDITIONS describes all editions in the database.

Column	Datatype	NULL	Description
EDITION_NAME	VARCHAR2(128)	NOT NULL	Name of the edition
PARENT_EDITION_NAME	VARCHAR2(128)		Name of the parent edition for this edition
USABLE	VARCHAR2(3)		Indicates whether the edition is usable (YES) or unusable (NO)

See Also:

- "DBA_EDITIONS"
- *Oracle Database Development Guide* for more information about editions

3.187 ALL_ENCRYPTED_COLUMNS

ALL_ENCRYPTED_COLUMNS displays encryption algorithm information for the encrypted columns in the tables accessible to the current user.

Related Views

- DBA_ENCRYPTED_COLUMNS displays encryption algorithm information for all encrypted columns in the database.
- USER_ENCRYPTED_COLUMNS displays encryption algorithm information for the encrypted columns in the tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
ENCRYPTION_ALG	VARCHAR2(29)		Encryption algorithm used to protect secrecy of data in this column: • 3 Key Triple DES 168 bits key • AES 128 bits key • AES 192 bits key • AES 256 bits key
SALT	VARCHAR2(3)		Indicates whether the column is encrypted with SALT (YES) or not (NO)
INTEGRITY_ALG	VARCHAR2(12)		Integrity algorithm used for the column: • SHA-1 • NOMAC

> **See Also:**
>
> - "DBA_ENCRYPTED_COLUMNS"
> - "USER_ENCRYPTED_COLUMNS"

3.188 ALL_ERROR_TRANSLATIONS

ALL_ERROR_TRANSLATIONS describes all error translations accessible to the user.

Related Views

- DBA_ERROR_TRANSLATIONS describes all error translations in the database.
- USER_ERROR_TRANSLATIONS describes all error translations owned by the user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the SQL translation profile
PROFILE_NAME	VARCHAR2(128)	NOT NULL	Name of the SQL translation profile
ERROR_CODE	NUMBER	NOT NULL	The Oracle error code
TRANSLATED_CODE	NUMBER		The translated error code
TRANSLATED_SQLSTATE	VARCHAR2(5)		The translated SQLSTATE
ENABLED	VARCHAR2(5)		TRUE if the translation is enabled, FALSE otherwise.
REGISTRATION_TIME	TIMESTAMP(6)		Time the translation was registered
COMMENTS	VARCHAR2(4000)		Comment on the translation

> **See Also:**
>
> - "DBA_ERROR_TRANSLATIONS"
> - "USER_ERROR_TRANSLATIONS"

3.189 ALL_ERRORS

ALL_ERRORS describes the current errors on the stored objects accessible to the current user.

Related Views

- DBA_ERRORS describes the current errors on all stored objects in the database.
- USER_ERRORS describes the current errors on the stored objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
NAME	VARCHAR2(128)	NOT NULL	Name of the object
TYPE	VARCHAR2(12)		Type of the object: • VIEW • PROCEDURE • FUNCTION • PACKAGE • PACKAGE BODY • TRIGGER • TYPE • TYPE BODY • LIBRARY • JAVA SOURCE • JAVA CLASS • DIMENSION
SEQUENCE	NUMBER	NOT NULL	Sequence number (for ordering purposes)
LINE	NUMBER	NOT NULL	Line number at which the error occurred
POSITION	NUMBER	NOT NULL	Position in the line at which the error occurred
TEXT	VARCHAR2(4000)	NOT NULL	Text of the error
ATTRIBUTE	VARCHAR2(9)		Indicates whether the error is an error (ERROR) or a warning (WARNING)
MESSAGE_NUMBER	NUMBER		Numeric error number (without any prefix)

See Also:

- "DBA_ERRORS"
  "USER_ERRORS"

3.190 ALL_ERRORS_AE

ALL_ERRORS_AE describes the current errors on the stored objects (across all editions) accessible to the current user.

Related Views

- DBA_ERRORS_AE describes the current errors on all stored objects (across all editions) in the database.
- USER_ERRORS_AE describes the current errors on the stored objects (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
NAME	VARCHAR2(128)	NOT NULL	Name of the object

Column	Datatype	NULL	Description
TYPE	VARCHAR2(12)		Type of the object: • TYPE • TYPE BODY • VIEW • PROCEDURE • FUNCTION • PACKAGE • PACKAGE BODY • TRIGGER • JAVA SOURCE • JAVA CLASS
SEQUENCE	NUMBER	NOT NULL	Sequence number (for ordering purposes)
LINE	NUMBER	NOT NULL	Line number at which this error occurred
POSITION	NUMBER	NOT NULL	Position in the line at which this error occurred
TEXT	VARCHAR2(4000)	NOT NULL	Text of the error
ATTRIBUTE	VARCHAR2(9)		Indicates whether the error is an error (ERROR) or a warning (WARNING)
MESSAGE_NUMBER	NUMBER		Numeric error number (without any prefix)
EDITION_NAME	VARCHAR2(128)		Name of the edition in which the object is actual

See Also:

- "DBA_ERRORS_AE"
- "USER_ERRORS_AE"

3.191 ALL_EVALUATION_CONTEXT_TABLES

ALL_EVALUATION_CONTEXT_TABLES describes the tables in the rule evaluation contexts accessible to the current user.

Related Views

- DBA_EVALUATION_CONTEXT_TABLES describes the tables in all rule evaluation contexts in the database.
- USER_EVALUATION_CONTEXT_TABLES describes the tables in the rule evaluation contexts owned by the current user. This view does not display the EVALUATION_CONTEXT_OWNER column.

Column	Datatype	NULL	Description
EVALUATION_CONTEXT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the evaluation context
EVALUATION_CONTEXT_NAME	VARCHAR2(128)	NOT NULL	Name of the evaluation context

Column	Datatype	NULL	Description
TABLE_ALIAS	VARCHAR2(128)		Alias for a table in the evaluation context
TABLE_NAME	VARCHAR2(4000)		Name of the table referred to by the table alias

See Also:

- "DBA_EVALUATION_CONTEXT_TABLES"
- "USER_EVALUATION_CONTEXT_TABLES"

3.192 ALL_EVALUATION_CONTEXT_VARS

ALL_EVALUATION_CONTEXT_VARS describes the variables in the rule evaluation contexts accessible to the current user.

Related Views

- DBA_EVALUATION_CONTEXT_VARS describes the variables in all rule evaluation contexts in the database.
- USER_EVALUATION_CONTEXT_VARS describes the variables in the rule evaluation contexts owned by the current user. This view does not display the EVALUATION_CONTEXT_OWNER column.

Column	Datatype	NULL	Description
EVALUATION_CONTEXT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the evaluation context
EVALUATION_CONTEXT_NAME	VARCHAR2(128)	NOT NULL	Name of the evaluation context
VARIABLE_NAME	VARCHAR2(128)		Name of a variable in the evaluation context
VARIABLE_TYPE	VARCHAR2(4000)		Datatype of the variable
VARIABLE_VALUE_FUNCTION	VARCHAR2(4000)		Function used to retrieve the value of the variable; NULL for variables that are not implicit
VARIABLE_METHOD_FUNCTION	VARCHAR2(228)		Function used to retrieve the result of method invocation on the variable. Such a function can speed up evaluation, if there are many simple rules that invoke the method on the variable.

See Also:

- "DBA_EVALUATION_CONTEXT_VARS"
- "USER_EVALUATION_CONTEXT_VARS"

3.193 ALL_EVALUATION_CONTEXTS

ALL_EVALUATION_CONTEXTS describes the rule evaluation contexts accessible to the current user.

Related Views

- DBA_EVALUATION_CONTEXTS describes all rule evaluation contexts in the database.
- USER_EVALUATION_CONTEXTS describes the rule evaluation contexts owned by the current user. This view does not display the EVALUATION_CONTEXT_OWNER column.

Column	Datatype	NULL	Description
EVALUATION_CONTEXT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the evaluation context
EVALUATION_CONTEXT_NAME	VARCHAR2(128)	NOT NULL	Name of the evaluation context
EVALUATION_FUNCTION	VARCHAR2(4000)		Evaluation function associated with the evaluation context, if any
EVALUATION_CONTEXT_COMMENT	VARCHAR2(4000)		Comment specified with the evaluation context, if any

> **See Also:**
>
> - "DBA_EVALUATION_CONTEXTS"
> - "USER_EVALUATION_CONTEXTS"

3.194 ALL_EXPRESSION_STATISTICS

ALL_EXPRESSION_STATISTICS provides expression usage tracking statistics for tables that are accessible to the current user.

Related Views

- DBA_EXPRESSION_STATISTICS provides expression usage tracking statistics for all the tables in the database.
- USER_EXPRESSION_STATISTICS provides expression usage tracking statistics for tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table contained in the expression
EXPRESSION_ID	NUMBER		Expression ID of the current expression

Column	Datatype	NULL	Description
SNAPSHOT	VARCHAR2(10)		Type of snapshot for the expression: • LATEST: Latest snapshot • CUMULATIVE: Cumulative snapshot • WINDOW: Window snapshot
EVALUATION_COUNT	NUMBER		Number of times the expression has been evaluated
FIXED_COST	NUMBER	NOT NULL	Optimizer fixed cost of evaluating the expression
DYNAMIC_COST	NUMBER		Optimizer dynamic cost of evaluating the expression
EXPRESSION_TEXT	VARCHAR2(4000)	NOT NULL	Text of the expression
CREATED	DATE	NOT NULL	Time this expression is first evaluated
LAST_MODIFIED	DATE		Time this expression is last evaluated

See Also:

- "DBA_EXPRESSION_STATISTICS"
- "USER_EXPRESSION_STATISTICS"
- "V$EXP_STATS"

3.195 ALL_EXTERNAL_LOCATIONS

ALL_EXTERNAL_LOCATIONS describes the locations (data sources) of the external tables accessible to the current user.

Related Views

- DBA_EXTERNAL_LOCATIONS describes the locations (data sources) of all external tables in the database.
- USER_EXTERNAL_LOCATIONS describes the locations (data sources) of the external tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the external table location
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the corresponding external table
LOCATION	VARCHAR2(4000)		External table location clause
DIRECTORY_OWNER	CHAR(3)		Owner of the directory containing the external table location
DIRECTORY_NAME	VARCHAR2(128)		Name of the directory containing the external table location

> **See Also:**
>
> - "DBA_EXTERNAL_LOCATIONS"
> - "USER_EXTERNAL_LOCATIONS"

3.196 ALL_EXTERNAL_TABLES

ALL_EXTERNAL_TABLES describes the external tables accessible to the current user.

Related Views

- DBA_EXTERNAL_TABLES describes all external tables in the database.
- USER_EXTERNAL_TABLES describes the external tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the external table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the external table
TYPE_OWNER	CHAR(3)		Owner of the implementation type for the external table access driver
TYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the implementation type for the external table access driver
DEFAULT_DIRECTORY_OWNER	CHAR(3)		Owner of the default directory for the external table
DEFAULT_DIRECTORY_NAME	VARCHAR2(128)	NOT NULL	Name of the default directory for the external table
REJECT_LIMIT	VARCHAR2(40)		Reject limit for the external table, or UNLIMITED
ACCESS_TYPE	VARCHAR2(7)		Type of access parameters for the external table: • BLOB • CLOB
ACCESS_PARAMETERS	CLOB		Access parameters for the external table
PROPERTY	VARCHAR2(10)		Property of the external table: • REFERENCED - Referenced columns • ALL - All columns
INMEMORY	VARCHAR2(8)		Indicates whether the In-Memory Column Store (IM column store) is enabled (ENABLED) or disabled (DISABLED) for this table

Column	Datatype	NULL	Description
INMEMORY_COMPRESSION	VARCHAR2(17)		Indicates the compression level for the IM column store: • NO MEMCOMPRESS • FOR DML • FOR CAPACITY [HIGH | LOW] • FOR QUERY [HIGH | LOW] • NULL This column has a value based on where the segments lie for a table. For example, if the table is partitioned and is enabled for the IM column store, the value is NULL for ALL_EXTERNAL_TABLES but non-NULL for ALL_XTERNAL_TAB_PARTITIONS.

See Also:

- "DBA_EXTERNAL_TABLES"
- "USER_EXTERNAL_TABLES"

3.197 ALL_GG_AUTO_CDR_COLUMN_GROUPS

ALL_GG_AUTO_CDR_COLUMN_GROUPS provides details about Oracle GoldenGate automatic conflict detection and resolution (CDR) column groups owned by the current user.

Related View

DBA_GG_AUTO_CDR_COLUMN_GROUPS provides details about all of the Oracle GoldenGate automatic CDR column groups in the database.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Table name
COLUMN_GROUP_NAME	VARCHAR2(128)	NOT NULL	Column group name
RESOLUTION_COLUMN	VARCHAR2(128)	NOT NULL	Timestamp resolution column

See Also:

"DBA_GG_AUTO_CDR_COLUMN_GROUPS"

3.198 ALL_GG_AUTO_CDR_COLUMNS

ALL_GG_AUTO_CDR_COLUMNS provides details about Oracle GoldenGate automatic conflict detection and resolution (CDR) columns owned by the current user.

Related View

DBA_GG_AUTO_CDR_COLUMNS provides details about all of the Oracle GoldenGate automatic CDR columns in the database.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Table name
COLUMN_GROUP_NAME	VARCHAR2(128)		Column group name
COLUMN_NAME	VARCHAR2(128)		Column name
RESOLUTION_COLUMN	VARCHAR2(128)		Timestamp resolution column

See Also:

"DBA_GG_AUTO_CDR_COLUMNS"

3.199 ALL_GG_AUTO_CDR_TABLES

ALL_GG_AUTO_CDR_TABLES provides details about tables configured for Oracle GoldenGate automatic conflict detection and resolution (CDR) that are owned by the current user.

Related View

DBA_GG_AUTO_CDR_TABLES provides details about all the tables configured for Oracle GoldenGate automatic conflict detection and resolution (CDR).

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Table name
RESOLUTION_GRANULARITY	VARCHAR2(6)		Resolution granularity: • ROW • COLUMN
FETCHCOLS	VARCHAR2(3)		Extract fetchcols configuration: • Yes: Extract will fetch non-scalar data • No: Extract will not fetch non-scalar data
RECORD_CONFLICTS	VARCHAR2(3)		Monitoring of conflicts: • Yes: Conflict info is recorded • No: Conflict info is not recorded

Column	Datatype	NULL	Description
USE_CUSTOM_HANDLERS	VARCHAR2(4)		Use of customized or automatic conflict handlers: • All: If using custom handlers • None: If using automatic handlers
ROW_RESOLUTION_METHOD	VARCHAR2(18)		Indicates which row-level conflict resolution method to use when the old value of the logical change record (LCR) timestamp column is different from the timestamp column value in the table. Possible values: • EARLIEST TIMESTAMP: The conflict will be resolved in favor of the LCR when the new value of the LCR timestamp column is *less than* the timestamp column value in the table • LATEST TIMESTAMP: The conflict will be resolved in favor of the LCR when the new value of the LCR timestamp column is *greater than* the timestamp column value in the table
DELETE_ALWAYS_WINS	VARCHAR2(3)		When a conflict occurs between a delete operation and another operation, a YES value indicates that the delete operation succeeds and the other operation is discarded, and a NO value indicates that there is no special preference for the delete operation
IGNORE_SITE_PRIORITY	VARCHAR2(3)		When a conflict occurs between a target table change and a source table change, and SITE PRIORITY has been specified, this value indicates whether SITE PRIORITY should be ignored (YES) or not (NO)
TOMBSTONE_TABLE	VARCHAR2(128)		Tombstone table name (if table has delete tombstoning enabled)
ROW_RESOLUTION_COLUMN	VARCHAR2(128)	NOT NULL	Name of row-level timestamp column
KEY_VERSION_COLUMN	VARCHAR2(8)		Indicates whether the table contains a hidden column named KEYVER$$, which contains a version timestamp Possible values: • KEYVER$$ - The table contains a KEYVER$$ column • NONE - The table does not contain a KEYVER$$ column
EXISTING_DATA_TIMESTAMP	TIMESTAMP(6)		Timestamp to give existing rows when a new timestamp column is added

See Also:

"DBA_GG_AUTO_CDR_TABLES"

3.200 ALL_GG_INBOUND_PROGRESS

ALL_GG_INBOUND_PROGRESS displays information about the progress made by the GoldenGate inbound servers accessible to the current user.

Related View

DBA_GG_INBOUND_PROGRESS displays information about the progress made by all GoldenGate inbound servers in the database.

Column	Datatype	NULL	Description
SERVER_NAME	VARCHAR2(128)	NOT NULL	Name of the inbound server
PROCESSED_LOW_POSITION	VARCHAR2(4000)		Position of the processed low transaction
APPLIED_LOW_POSITION	VARCHAR2(4000)		All messages with commit position less than this value have been applied. This column should be used to view the progress of the GoldenGate apply. This column will hold an Oracle SCN numeric value in text format for an Oracle source database. For a non-Oracle source database, this column will hold the apply low position in GoldenGate CSN text format for that specific source database.
APPLIED_HIGH_POSITION	VARCHAR2(4000)		Highest commit position of a transaction that has been applied
SPILL_POSITION	VARCHAR2(4000)		Position of the spill low watermark of the transactions currently being applied
OLDEST_POSITION	VARCHAR2(4000)		Earliest position of the transactions currently being applied
APPLIED_LOW_SCN	NUMBER	NOT NULL	All SCN below or equal to this number have been successfully applied. This column is not applicable for GoldenGate replication since the source database may be non-Oracle.
APPLIED_TIME	DATE		Time at which the APPLIED_MESSAGE_NUMBER message was applied
APPLIED_MESSAGE_CREATE_TIME	DATE		Time at which the APPLIED_MESSAGE_NUMBER message was created
SOURCE_DATABASE	VARCHAR2(128)		Database where the transaction originated
SOURCE_ROOT_NAME	VARCHAR2(128)		The global name of the source root database where all transactions originated
LOGBSN	VARCHAR2(4000)		Log BSN value from the GoldenGate trail file

See Also:

"DBA_GG_INBOUND_PROGRESS"

3.201 ALL_GOLDENGATE_INBOUND

ALL_GOLDENGATE_INBOUND displays information about the GoldenGate inbound servers accessible to the current user.

Related View

DBA_GOLDENGATE_INBOUND displays information about all GoldenGate inbound servers in the database.

Column	Datatype	NULL	Description
REPLICAT_NAME	VARCHAR2(4000)		The name of the replicat group created from GGSCI using GoldenGate
SERVER_NAME	VARCHAR2(128)	NOT NULL	Name of the inbound server
APPLY_USER	VARCHAR2(128)		Name of the user who can connect to the inbound server and apply messages
USER_COMMENT	VARCHAR2(4000)		User comment
CREATE_DATE	TIMESTAMP(6)		Date when inbound server was created
STATUS	VARCHAR2(8)		Status of the inbound server: • DISABLED - The inbound server is not running. • DETACHED - The inbound server is running, but the GoldenGate client application is not attached to it. • ATTACHED - The inbound server is running, and the GoldenGate client application is attached to it. • ABORTED - The inbound server became disabled because it encountered an error.

See Also:

"DBA_GOLDENGATE_INBOUND"

3.202 ALL_GOLDENGATE_PRIVILEGES

ALL_GOLDENGATE_PRIVILEGES displays details about Oracle GoldenGate privileges for the user. Oracle GoldenGate privileges are granted using the DBMS_GOLDENGATE_AUTH package.

Related Views

- DBA_GOLDENGATE_PRIVILEGES displays details about Oracle GoldenGate privileges for all users who have been granted Oracle GoldenGate privileges.
- USER_GOLDENGATE_PRIVILEGES displays details about Oracle GoldenGate privileges. This view does not display the USERNAME column.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user that is granted the privilege
PRIVILEGE_TYPE	VARCHAR2(7)		Type of privilege granted: • APPLY • CAPTURE • *: Both APPLY and CAPTURE
GRANT_SELECT_PRIVILEGES	VARCHAR2(3)		Shows whether the set of privileges granted to the administrator make the administrator a full privilege administrator or a minimum privilege administrator: • YES: The administrator has the SELECT_CATALOG_ROLE role and other privileges, is considered a full privilege administrator, and can manage any Oracle GoldenGate configuration. • NO: The administrator is considered a minimum privilege administrator, and can only manage Oracle GoldenGate configurations where the apply_user or capture_user (based on the PRIVILEGE_TYPE column) matches the username.
CREATE_TIME	TIMESTAMP(6)		Time at which the privilege was granted
LAST_MODIFIED	TIMESTAMP(6)		Time at which the privilege was last modified

See Also:

- "DBA_GOLDENGATE_PRIVILEGES"
- "USER_GOLDENGATE_PRIVILEGES"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_GOLDENGATE_AUTH package

3.203 ALL_GOLDENGATE_RULES

ALL_GOLDENGATE_RULES displays information about the GoldenGate rules accessible to the current user.

Related View

DBA_GOLDENGATE_RULES displays information about all GoldenGate server rules in the database.

Column	Datatype	NULL	Description
COMPONENT_NAME	VARCHAR2(128)		Name of the GoldenGate process
COMPONENT_TYPE	VARCHAR2(12)		Type of the GoldenGate process: • CAPTURE • APPLY

Column	Datatype	NULL	Description
COMPONENT_RULE_TYPE	VARCHAR2(9)		For global, schema or table rules, the GoldenGate type of the rule: • TABLE • SCHEMA • GLOBAL
RULE_SET_OWNER	VARCHAR2(128)		Owner of the rule set
RULE_SET_NAME	VARCHAR2(128)		Name of the rule set
RULE_SET_TYPE	CHAR(8)		Type of the rule set: • POSITIVE • NEGATIVE
RULE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2(128)	NOT NULL	Name of the rule
RULE_TYPE	VARCHAR2(9)		For global, schema or table rules, the type of the rule: • DML • DDL
RULE_CONDITION	CLOB		Current rule condition
SCHEMA_NAME	VARCHAR2(128)		For table and schema rules, the schema name
OBJECT_NAME	VARCHAR2(128)		For table rules, the table name
INCLUDE_TAGGED_LCR	VARCHAR2(3)		For global, schema or table rules, indicates whether to include tagged LCRs (YES) or not (NO)
SUBSETTING_OPERATION	VARCHAR2(6)		For subset rules, the type of operation: • INSERT • UPDATE • DELETE
DML_CONDITION	VARCHAR2(4000)		For subset rules, the row subsetting condition
SOURCE_DATABASE	VARCHAR2(128)		For global, schema or table rules, the name of the database where the LCRs originated
ORIGINAL_RULE_CONDITION	VARCHAR2(4000)		For rules created by GoldenGate administrative APIs, the original rule condition when the rule was created
SAME_RULE_CONDITION	VARCHAR2(3)		For rules created by GoldenGate administrative APIs, indicates whether the current rule condition is the same as the original rule condition (YES) or not (NO)
SOURCE_ROOT_NAME	VARCHAR2(128)		The global name of the source root database where the transactions originated
SOURCE_CONTAINER_NAME	VARCHAR2(128)		The container name of the database where the transactions originated

See Also:

"DBA_GOLDENGATE_RULES"

3.204 ALL_HEAT_MAP_SEG_HISTOGRAM

ALL_HEAT_MAP_SEG_HISTOGRAM displays segment access information for all segments visible to the user.

Related Views

- DBA_HEAT_MAP_SEG_HISTOGRAM displays segment access information for all segments.
- USER_HEAT_MAP_SEG_HISTOGRAM displays segment access information for segments owned by the user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Table owner
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object
SUBOBJECT_NAME	VARCHAR2(128)		Name of the sub-object
TRACK_TIME	DATE		System time when the segment access was tracked
SEGMENT_WRITE	VARCHAR2(3)		Indicates whether the segment has write access (YES or NO)
FULL_SCAN	VARCHAR2(3)		Indicates whether the segment has full table scan (YES or NO)
LOOKUP_SCAN	VARCHAR2(3)		Indicates whether the segment has lookup scan (YES or NO)

See Also:

- "DBA_HEAT_MAP_SEG_HISTOGRAM"
- "USER_HEAT_MAP_SEG_HISTOGRAM"

3.205 ALL_HEAT_MAP_SEGMENT

ALL_HEAT_MAP_SEGMENT displays the latest segment access time for all segments visible to the user. The timestamps in the view are coarse with a granularity of a day reflecting the flush times of the heat map.

Related Views

- DBA_HEAT_MAP_SEGMENT displays the latest segment access time for all segments.
- USER_HEAT_MAP_SEGMENT displays the latest segment access time for all segments owned by the user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Table owner

Column	Datatype	NULL	Description
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object
SUBOBJECT_NAME	VARCHAR2(128)		Name of the sub-object
SEGMENT_WRITE_TIME	DATE		Latest timestamp on which the segment has write access
SEGMENT_READ_TIME	DATE		Latest timestamp on which the segment has read access
FULL_SCAN	DATE		Latest timestamp on which the segment has full table scan
LOOKUP_SCAN	DATE		Latest timestamp on which the segment has index scan

See Also:

- "DBA_HEAT_MAP_SEGMENT"
- "USER_HEAT_MAP_SEGMENT"

3.206 ALL_HIER_CLASS

ALL_HIER_CLASS describes the classifications of the hierarchies accessible to the current user.

Related Views

- DBA_HIER_CLASS describes the classifications of all hierarchies in the database.
- USER_HIER_CLASS describes the classifications of the hierarchies owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
CLASSIFICATION	VARCHAR2(128)		Classification associated with the hierarchy
VALUE	CLOB		Value of the classification or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the hierarchy
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

> **See Also:**
>
> - "DBA_HIER_CLASS"
> - "USER_HIER_CLASS"

3.207 ALL_HIER_CLASS_AE

ALL_HIER_CLASS_AE describes the classifications of the hierarchies (across all editions) accessible to the current user.

Related Views

- DBA_HIER_CLASS_AE describes the classifications of all hierarchies (across all editions) in the database.
- USER_HIER_CLASS_AE describes the classifications of the hierarchies (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
CLASSIFICATION	VARCHAR2(128)		Classification associated with the hierarchy
VALUE	CLOB		Value of the classification or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the hierarchy
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the hierarchy is defined

> **See Also:**
>
> - "DBA_HIER_CLASS_AE"
> - "USER_HIER_CLASS_AE"

3.208 ALL_HIER_COLUMNS

ALL_HIER_COLUMNS describes the columns of the hierarchies accessible to the current user.

Related Views

- DBA_HIER_COLUMNS describes the columns of all hierarchies in the database.
- USER_HIER_COLUMNS describes the columns of the hierarchies owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
ROLE	VARCHAR2(4)		The role the attribute plays in the hierarchy: • KEY • AKEY • HIER • PROP
DATA_TYPE	VARCHAR2(106)		Datatype of the column
DATA_LENGTH	NUMBER	NOT NULL	Length of the column (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for the NUMBER datatype; binary precision for the FLOAT datatype, NULL for all other datatypes
DATA_SCALE	NUMBER		Number of digits to the right of the decimal point in a number
NULLABLE	CHAR(1)		Indicates whether a column allows NULL values; the value is N if there is a NOT NULL constraint on the column or if the column is part of a PRIMARY KEY
CHARACTER_SET_NAME	VARCHAR2(44)		Name of the character set: • CHAR_CS • NCHAR_CS
CHAR_COL_DECL_LENGTH	NUMBER		Declaration length of the character type column
CHAR_USED	VARCHAR2(1)		Indicates that the column uses BYTE length semantics (B) or CHAR length semantics (C), or whether the datatype is not any of the following (NULL): • CHAR • VARCHAR2 • NCHAR • NVARCHAR2
ORDER_NUM	NUMBER	NOT NULL	Order of the column, with attributes first in the order specified in the definition of the hierarchy followed by hierarchical attributes

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_HIER_COLUMNS"
- "USER_HIER_COLUMNS"

3.209 ALL_HIER_COLUMNS_AE

ALL_HIER_COLUMNS_AE describes the columns of the hierarchies (across all editions) accessible to the current user.

Related Views

- DBA_HIER_COLUMNS_AE describes the columns of all hierarchies (across all editions) in the database.
- USER_HIER_COLUMNS_AE describes the columns of the hierarchies (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
ROLE	VARCHAR2(4)		The role the attribute plays in the hierarchy: • KEY • AKEY • HIER • PROP
DATA_TYPE	VARCHAR2(106)		Datatype of the column
DATA_LENGTH	NUMBER	NOT NULL	Length of the column (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for the NUMBER datatype; binary precision for the FLOAT datatype, NULL for all other datatypes
DATA_SCALE	NUMBER		Number of digits to the right of the decimal point in a number

Column	Datatype	NULL	Description
NULLABLE	CHAR(1)		Indicates whether a column allows NULL values; the value is N if there is a NOT NULL constraint on the column or if the column is part of a PRIMARY KEY
CHARACTER_SET_NAME	VARCHAR2(44)		Name of the character set: • CHAR_CS • NCHAR_CS
CHAR_COL_DECL_LENGTH	NUMBER		Declaration length of the character type column
CHAR_USED	VARCHAR2(1)		Indicates that the column uses BYTE length semantics (B) or CHAR length semantics (C), or whether the datatype is not any of the following (NULL): • CHAR • VARCHAR2 • NCHAR • NVARCHAR2
ORDER_NUM	NUMBER	NOT NULL	Order of the column, with attributes first in the order specified in the definition of the hierarchy followed by hierarchical attributes
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the hierarchy is defined

See Also:

- "DBA_HIER_COLUMNS_AE"
- "USER_HIER_COLUMNS_AE"

3.210 ALL_HIER_HIER_ATTR_CLASS

ALL_HIER_HIER_ATTR_CLASS describes the classifications of the hierarchical attributes of the hierarchies accessible to the current user.

Related Views

- DBA_HIER_HIER_ATTR_CLASS describes the classifications of the hierarchical attributes of all hierarchies in the database.
- USER_HIER_HIER_ATTR_CLASS describes the classifications of the hierarchical attributes of the hierarchies owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
HIER_ATTR_NAME	VARCHAR2(128)		Name of the hierarchical attribute
CLASSIFICATION	VARCHAR2(128)		Classification associated with the hierarchical attribute
VALUE	CLOB		Value associated with the classification or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the hierarchical attribute
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_HIER_HIER_ATTR_CLASS"
- "USER_HIER_HIER_ATTR_CLASS"

3.211 ALL_HIER_HIER_ATTR_CLASS_AE

ALL_HIER_HIER_ATTR_CLASS_AE describes the classifications of the hierarchical attributes of the hierarchies (across all editions) accessible to the current user.

Related Views

- DBA_HIER_HIER_ATTR_CLASS_AE describes the classifications of the hierarchical attributes of all hierarchies (across all editions) in the database.
- USER_HIER_HIER_ATTR_CLASS_AE describes the classifications of the hierarchical attributes of the hierarchies (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
HIER_ATTR_NAME	VARCHAR2(128)		Name of the hierarchical attribute
CLASSIFICATION	VARCHAR2(128)		Classification associated with the hierarchical attribute

Column	Datatype	NULL	Description
VALUE	CLOB		Value associated with the classification or NULL if not specified
LANGUAGE	VARCHAR2(64)		NLS_LANGUAGE value associated with the classification or NULL if not specified
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of classifications associated with the hierarchical attribute
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the hierarchy is defined

See Also:

- "DBA_HIER_HIER_ATTR_CLASS_AE"
- "USER_HIER_HIER_ATTR_CLASS_AE"

3.212 ALL_HIER_HIER_ATTRIBUTES

ALL_HIER_HIER_ATTRIBUTES describes the hierarchical attributes of the hierarchies accessible to the current user.

Related Views

- DBA_HIER_HIER_ATTRIBUTES describes the hierarchical attributes of all hierarchies in the database.
- USER_HIER_HIER_ATTRIBUTES describes the hierarchical attributes of the hierarchies owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
HIER_ATTR_NAME	VARCHAR2(128)		Name of the hierarchical attribute
EXPRESSION	CLOB		The expression defining the hierarchical attribute value
ORDER_NUM	NUMBER	NOT NULL	Order of the hierarchical attribute in the list of hierarchical attributes

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_HIER_HIER_ATTRIBUTES"
- "USER_HIER_HIER_ATTRIBUTES"

3.213 ALL_HIER_HIER_ATTRIBUTES_AE

ALL_HIER_HIER_ATTRIBUTES_AE describes the hierarchical attributes of the hierarchies (across all editions) accessible to the current user.

Related Views

- DBA_HIER_HIER_ATTRIBUTES_AE describes the hierarchical attributes of all hierarchies (across all editions) in the database.
- USER_HIER_HIER_ATTRIBUTES_AE describes the hierarchical attributes of the hierarchies (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
HIER_ATTR_NAME	VARCHAR2(128)		Name of the hierarchical attribute
EXPRESSION	CLOB		The expression defining the hierarchical attribute value
ORDER_NUM	NUMBER	NOT NULL	Order of the hierarchical attribute in the list of hierarchical attributes
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the hierarchy is defined

> **See Also:**
>
> - "DBA_HIER_HIER_ATTRIBUTES_AE"
> - "USER_HIER_HIER_ATTRIBUTES_AE"

3.214 ALL_HIER_JOIN_PATHS

`ALL_HIER_JOIN_PATHS` describes the join paths for the hierarchies accessible to the current user.

Related Views

- `DBA_HIER_JOIN_PATHS` describes the join paths for all hierarchies in the database.
- `USER_HIER_JOIN_PATHS` describes the join paths for the hierarchies owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
`OWNER`	`VARCHAR2(128)`	`NOT NULL`	Owner of the hierarchy
`HIER_NAME`	`VARCHAR2(128)`	`NOT NULL`	Name of the hierarchy
`JOIN_PATH_NAME`	`VARCHAR2(128)`	`NOT NULL`	Name of the join path
`ORDER_NUM`	`NUMBER`	`NOT NULL`	Order of the classification in the list of join paths associated with the hierarchy
`ORIGIN_CON_ID`	`NUMBER`		The ID of the container where the data originates. Possible values include: • `0`: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

> **See Also:**
>
> - "DBA_HIER_JOIN_PATHS"
> - "USER_HIER_JOIN_PATHS"

3.215 ALL_HIER_JOIN_PATHS_AE

`ALL_HIER_JOIN_PATHS_AE` describes the join paths for the hierarchies (across all editions) accessible to the current user.

Related Views

- `DBA_HIER_JOIN_PATHS_AE` describes the join paths for all hierarchies (across all editions) in the database.

- USER_HIER_JOIN_PATHS_AE describes the join paths for the hierarchies (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
JOIN_PATH_NAME	VARCHAR2(128)	NOT NULL	Name of the join path
ORDER_NUM	NUMBER	NOT NULL	Order of the classification in the list of join paths associated with the hierarchy
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the hierarchy is defined

See Also:

- "DBA_HIER_JOIN_PATHS_AE"
- "USER_HIER_JOIN_PATHS_AE"

3.216 ALL_HIER_LEVEL_ID_ATTRS

ALL_HIER_LEVEL_ID_ATTRS describes the attributes that uniquely identify members of the levels of the hierarchies accessible to the current user.

Related Views

- DBA_HIER_LEVEL_ID_ATTRS describes the attributes that uniquely identify members of the levels of all hierarchies in the database.
- USER_HIER_LEVEL_ID_ATTRS describes the attributes that uniquely identify members of the levels of the hierarchies owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
LEVEL_NAME	VARCHAR2(128)	NOT NULL	Name of hierarchy level
ATTRIBUTE_NAME	VARCHAR2(128)	NOT NULL	Name of the unique identifier attribute
ORDER_NUM	NUMBER	NOT NULL	Order of the level in the list of unique identifier attributes for the level

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_HIER_LEVEL_ID_ATTRS"
- "USER_HIER_LEVEL_ID_ATTRS"

3.217 ALL_HIER_LEVEL_ID_ATTRS_AE

ALL_HIER_LEVEL_ID_ATTRS_AE describes the attributes that uniquely identify members of the levels of the hierarchies (across all editions) accessible to the current user.

Related Views

- DBA_HIER_LEVEL_ID_ATTRS_AE describes the attributes that uniquely identify members of the levels of all hierarchies (across all editions) in the database.
- USER_HIER_LEVEL_ID_ATTRS_AE describes the attributes that uniquely identify members of the levels of the hierarchies (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
LEVEL_NAME	VARCHAR2(128)	NOT NULL	Name of hierarchy level
ATTRIBUTE_NAME	VARCHAR2(128)	NOT NULL	Name of the unique identifier attribute
ORDER_NUM	NUMBER	NOT NULL	Order of the level in the list of unique identifier attributes for the level
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the hierarchy is defined

> **See Also:**
>
> - "DBA_HIER_LEVEL_ID_ATTRS_AE"
> - "USER_HIER_LEVEL_ID_ATTRS_AE"

3.218 ALL_HIER_LEVELS

ALL_HIER_LEVELS describes the levels of the hierarchies accessible to the current user.

Related Views

- DBA_HIER_LEVELS describes the levels of all hierarchies in the database.
- USER_HIER_LEVELS describes the levels of the hierarchies owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
LEVEL_NAME	VARCHAR2(128)	NOT NULL	Name of hierarchy level
ORDER_NUM	NUMBER	NOT NULL	Order of the level in the list of hierarchy levels
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

> **See Also:**
>
> - "DBA_HIER_LEVELS"
> - "USER_HIER_LEVELS"

3.219 ALL_HIER_LEVELS_AE

ALL_HIER_LEVELS_AE describes the levels of the hierarchies (across all editions) accessible to the current user.

Related Views

- DBA_HIER_LEVELS_AE describes the levels of all hierarchies (across all editions) in the database.
- USER_HIER_LEVELS_AE describes the levels of the hierarchies (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
LEVEL_NAME	VARCHAR2(128)	NOT NULL	Name of hierarchy level
ORDER_NUM	NUMBER	NOT NULL	Order of the level in the list of hierarchy levels
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the hierarchy is defined

See Also:

- "DBA_HIER_LEVELS_AE"
- "USER_HIER_LEVELS_AE"

3.220 ALL_HIERARCHIES

ALL_HIERARCHIES describes the hierarchies accessible to the current user.

Related Views

- DBA_HIERARCHIES describes all hierarchies in the database.
- USER_HIERARCHIES describes the hierarchies owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
DIMENSION_OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension used by the hierarchy
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension used by the hierarchy
PARENT_ATTR	VARCHAR2		The value of this column is always NULL
COMPILE_STATE	VARCHAR2(7)		Compile status of the hierarchy: • VALID • INVALID

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).

See Also:

- "DBA_HIERARCHIES"
- "USER_HIERARCHIES"

3.221 ALL_HIERARCHIES_AE

ALL_HIERARCHIES_AE describes the hierarchies (across all editions) accessible to the current user.

Related Views

- DBA_HIERARCHIES_AE describes all hierarchies (across all editions) in the database.
- USER_HIERARCHIES_AE describes the hierarchies (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the hierarchy
HIER_NAME	VARCHAR2(128)	NOT NULL	Name of the hierarchy
DIMENSION_OWNER	VARCHAR2(128)	NOT NULL	Owner of the attribute dimension used by the hierarchy
DIMENSION_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute dimension used by the hierarchy
PARENT_ATTR	VARCHAR2		The value of this column is always NULL
COMPILE_STATE	VARCHAR2(7)		Compile status of the hierarchy: • VALID • INVALID
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root).
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the hierarchy is defined

> **See Also:**
>
> - "DBA_HIERARCHIES_AE"
> - "USER_HIERARCHIES_AE"

3.222 ALL_HIST_SAGAS

ALL_HIST_SAGAS provides a history of the completed sagas accessible to the current user.

This view displays sagas that were either initiated in the current PDB or joined by participants in the current PDB.

Completed sagas are retained in this view for the length of time specified by the SAGA_HIST_RETENTION initialization parameter. The default is 30 days.

Related Views

- DBA_HIST_SAGAS provides a history of all completed sagas in the database.
- USER_HIST_SAGAS provides a history of the completed sagas owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
ID	RAW(16)	NOT NULL	Saga ID
INITIATOR	VARCHAR2(128)		Name of the saga initiator
IS_INITIATOR	VARCHAR2(3)		Indicates whether this participant is the saga initiator (YES) or not (NO)
COORDINATOR	VARCHAR2(128)		Name of the saga coordinator
COORDINATOR_TYPE	VARCHAR2(50)		Type of the saga coordinator: • Internal • External
OWNER	VARCHAR2(128)	NOT NULL	Owner of the saga participant
PARTICIPANT	VARCHAR2(128)	NOT NULL	Name of the saga participant
STATUS	VARCHAR2(15)		Saga status: • Auto Committed • Auto Rolledback • Committed • Finalization • Rejected • Rolledback
VERSION	NUMBER	NOT NULL	Saga version
DURATION	NUMBER		Time limit for the saga (in seconds)
START_TIME	TIMESTAMP(6) WITH TIME ZONE		Saga start time
FINALIZATION_TIME	TIMESTAMP(6) WITH TIME ZONE		Time at which the saga finalization was initiated

Column	Datatype	NULL	Description
COMPLETION_TIME	TIMESTAMP(6) WITH TIME ZONE		Time at which the saga was marked as completed, that is, all saga participants responded to the finalization request

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_HIST_SAGAS"
> - "USER_HIST_SAGAS"
> - "SAGA_HIST_RETENTION"

3.223 ALL_HISTOGRAMS

ALL_HISTOGRAMS is a synonym for ALL_TAB_HISTOGRAMS.

> **See Also:**
>
> "ALL_TAB_HISTOGRAMS"

3.224 ALL_HIVE_COLUMNS

ALL_HIVE_COLUMNS describes all Hive columns accessible to the current user in a Hive metastore.

Related Views

- DBA_HIVE_COLUMNS describes all Hive columns in a Hive metastore.
- USER_HIVE_COLUMNS describes all Hive columns owned by the current user in a Hive metastore.

Column	Datatype	NULL	Description
CLUSTER_ID	VARCHAR2(4000)		Identifier for the Hadoop cluster
DATABASE_NAME	VARCHAR2(4000)		Hive database where the owning Hive table resides
TABLE_NAME	VARCHAR2(4000)		Hive table name that the column belongs to
COLUMN_NAME	VARCHAR2(4000)		Hive column name

Column	Datatype	NULL	Description
HIVE_COLUMN_TYPE	VARCHAR2(4000)		Data type of the Hive column
ORACLE_COLUMN_TYPE	VARCHAR2(4000)		Equivalent Oracle data type of the Hive column
LOCATION	VARCHAR2(4000)		Physical location of the Hive table
OWNER	VARCHAR2(4000)		Owner of the Hive table
CREATION_TIME	DATE		Time that the Hive column was created
HIVE_URI	VARCHAR2(4000)		The connection string (URI and port number) for the metastore database

See Also:

- "DBA_HIVE_COLUMNS"
- "USER_HIVE_COLUMNS"

3.225 ALL_HIVE_DATABASES

ALL_HIVE_DATABASES describes all the Hive schemas accessible to the current user in a Hadoop cluster.

Related Views

- DBA_HIVE_DATABASES describes all the Hive schemas in a Hadoop cluster.
- USER_HIVE_DATABASES describes all the Hive schemas owned by the current user in a Hadoop cluster.

Column	Datatype	NULL	Description
CLUSTER_ID	VARCHAR2(4000)		Hadoop cluster name
DATABASE_NAME	VARCHAR2(4000)		Name of the Hive database
DESCRIPTION	VARCHAR2(4000)		Description of the Hive database
DB_LOCATION	VARCHAR2(4000)		Physical location of the Hive database
HIVE_URI	VARCHAR2(4000)		The connection string (URI and port number) for the metastore database

See Also:

- "DBA_HIVE_DATABASES"
- "USER_HIVE_DATABASES"

3.226 ALL_HIVE_PART_KEY_COLUMNS

ALL_HIVE_PART_KEY_COLUMNS provides information about all Hive table partition columns accessible to the current user in the database.

Related Views

- DBA_HIVE_PART_KEY_COLUMNS provides information about all Hive table partition columns in the database.
- USER_HIVE_PART_KEY_COLUMNS provides information about all Hive table partition columns owned by the current user in the database.

Column	Datatype	NULL	Description
CLUSTER_ID	VARCHAR2(4000)		Hadoop cluster name
DATABASE_NAME	VARCHAR2(4000)		Hive database where the Hive table resides
TABLE_NAME	VARCHAR2(4000)		Hive table name
OWNER	VARCHAR2(4000)		Owner of the Hive table
COLUMN_NAME	VARCHAR2(4000)		Partition column name
COLUMN_TYPE	VARCHAR2(4000)		Partition column type
COLUMN_POSITION	NUMBER		Partition column position in the Hive partition specification
ORACLE_COLUMN_TYPE	VARCHAR2(4000)		Equivalent Oracle data type of the Hive column

See Also:

- "DBA_HIVE_PART_KEY_COLUMNS"
- "USER_HIVE_PART_KEY_COLUMNS"

3.227 ALL_HIVE_TAB_PARTITIONS

ALL_HIVE_TAB_PARTITIONS provides information about all Hive table partitions accessible to the current user in the database.

Related Views

- DBA_HIVE_TAB_PARTITIONS provides information about all Hive table partitions in the database.
- USER_HIVE_TAB_PARTITIONS provides information about all Hive table partitions owned by the current user in the database.

Column	Datatype	NULL	Description
CLUSTER_ID	VARCHAR2(4000)		Hadoop cluster name
DATABASE_NAME	VARCHAR2(4000)		Hive database where the Hive table resides

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2(4000)		Hive table name
LOCATION	VARCHAR2(4000)		Physical location of the Hive partition
OWNER	VARCHAR2(4000)		Owner of the Hive table
PARTITION_SPECS	VARCHAR2(4000)		The current Hive partition specification
PART_SIZE	NUMBER		Partition size in bytes
CREATION_TIME	DATE		Time that the partition was created

See Also:

- "DBA_HIVE_TAB_PARTITIONS"
- "USER_HIVE_TAB_PARTITIONS"

3.228 ALL_HIVE_TABLES

ALL_HIVE_TABLES provides information about all the Hive tables accessible to the current user in the Hive metastore.

Related Views

- DBA_HIVE_TABLES provides information about all Hive tables in the Hive metastore.
- USER_HIVE_TABLES provides information about all Hive tables owned by the current user in the Hive metastore.

Column	Datatype	NULL	Description
CLUSTER_ID	VARCHAR2(4000)		Hadoop cluster name
DATABASE_NAME	VARCHAR2(4000)		Hive database where the Hive table resides
TABLE_NAME	VARCHAR2(4000)		Hive table name
LOCATION	VARCHAR2(4000)		Physical location of the Hive table
NO_OF_COLS	NUMBER		Number of columns in the Hive table
CREATION_TIME	DATE		Creation time of the Hive table
LAST_ACCESSED_TIME	DATE		Time that the Hive table was last accessed
OWNER	VARCHAR2(4000)		Owner of the Hive table
TABLE_TYPE	VARCHAR2(4000)		Type of the Hive table
PARTITIONED	VARCHAR2(4000)		Is this Hive table partitioned?
NO_OF_PART_KEYS	NUMBER		Number of partition keys in the Hive table
INPUT_FORMAT	VARCHAR2(4000)		Hive table input format
OUTPUT_FORMAT	VARCHAR2(4000)		Hive table output format
SERIALIZATION	VARCHAR2(4000)		Hive table serialization
COMPRESSED	NUMBER		Is this Hive table compressed?

Column	Datatype	NULL	Description
HIVE_URI	VARCHAR2(4000)		The connection string (URI and port number) for the metastore database

See Also:

- "DBA_HIVE_TABLES"
- "USER_HIVE_TABLES"

3.229 ALL_IDENTIFIERS

ALL_IDENTIFIERS displays information about the identifiers in the stored objects accessible to the current user.

Related Views

- DBA_IDENTIFIERS displays information about the identifiers in all stored objects in the database.
- USER_IDENTIFIERS displays information about the identifiers in the stored objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the identifier
NAME	VARCHAR2(128)		Name of the identifier
SIGNATURE	VARCHAR2(32)		Signature of the identifier
TYPE	VARCHAR2(18)		Type of the identifier. For SQL identifiers, the types include: • TABLE • VIEW • SEQUENCE • ALIAS • COLUMN • MATERIALIZED VIEW • OPERATOR For PL/SQL identifiers, the types include: • FUNCTION • PROCEDURE • PACKAGE
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object where the identifier action occurred
OBJECT_TYPE	VARCHAR2(13)		Type of the object where the identifier action occurred

Column	Datatype	NULL	Description
USAGE	VARCHAR2(11)		Type of the identifier usage: • DECLARATION • DEFINITION • CALL • REFERENCE • ASSIGNMENT
USAGE_ID	NUMBER		Unique key for the identifier usage within the object
LINE	NUMBER		Line number of the identifier action
COL	NUMBER		Column number of the identifier action
USAGE_CONTEXT_ID	NUMBER		Context USAGE_ID of the identifier usage
CHARACTER_SET	VARCHAR2(10)		Contains the value of the character set clause when it is used in a variable identifier declaration. These are the possible values when the character set is derived from another variable identifier: • CHAR_CS • NCHAR_CS • IDENTIFIER
ATTRIBUTE	VARCHAR2(7)		Column contains the attribute value when %attribute is used in a variable declaration. Possible values: • ROWTYPE • TYPE • CHARSET
CHAR_USED	VARCHAR2(4)		Contains the type of the length constraint when it is used in a string length constraint declaration. Possible values: • CHAR • BYTE
LENGTH	NUMBER		Contains the numeric length constraint value for a string length constraint declaration
PRECISION	NUMBER		Contains the numeric precision when it is used in a variable declaration
PRECISION2	NUMBER		Contains the numeric second precision value (for instance, interval types) used in a variable declaration
SCALE	NUMBER		Contains the numeric scale value used in a variable declaration.
LOWER_RANGE	NUMBER		Contains the numeric lower range value used by a variable declaration with a range constraint
UPPER_RANGE	NUMBER		Contains the numeric upper range value used by a variable declaration with a range constraint
NULL_CONSTRAINT	VARCHAR2(8)		This column is set when a NULL constraint is used by a variable declaration. Possible values: • NULL • NOT NULL
SQL_BUILTIN	VARCHAR2(3)		Is set to YES when an identifier is a SQL builtin used in a SQL statement issued from PL/SQL. Otherwise, this column is set to NO.

Column	Datatype	NULL	Description
IMPLICIT	VARCHAR2(3)		Indicates whether the identifier is an implicit identifier that does not appear in the source (YES) or not (NO)
DECLARED_OWNER	VARCHAR2(128)	NOT NULL	Owner of the object in which this identifier was declared
DECLARED_OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object in which this identifier was declared
DECLARED_OBJECT_TYPE	VARCHAR2(12)		Type of the object in which this identifier was declared
ORIGIN_CON_ID	VARCHAR2(256)		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)

See Also:

- "DBA_IDENTIFIERS"
- "USER_IDENTIFIERS"

3.230 ALL_IMMUTABLE_ROW_VERSION_COLS

ALL_IMMUTABLE_ROW_VERSION_COLS displays information about row versioned columns in the immutable tables accessible to the current user.

Related Views

- DBA_IMMUTABLE_ROW_VERSION_COLS displays information about row versioned columns in all immutable tables in the database.
- USER_IMMUTABLE_ROW_VERSION_COLS displays information about row versioned columns in the immutable tables owned by the current user.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Schema containing the immutable table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the immutable table
ROW_VERSION_NAME	VARCHAR2(128)	NOT NULL	Name of the row version
KEYCOL1_NAME	VARCHAR2(128)	NOT NULL	Name of version key column 1
KEYCOL2_NAME	VARCHAR2(128)		Name of version key column 2 Null if only one version key column is specified for the row version

Column	Datatype	NULL	Description
KEYCOL3_NAME	VARCHAR2(128)		Name of version key column 3 Null if only one or two version key columns are specified for the row version

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_IMMUTABLE_ROW_VERSION_COLS"
- "USER_IMMUTABLE_ROW_VERSION_COLS"

3.231 ALL_IMMUTABLE_ROW_VERSION_HISTORY

ALL_IMMUTABLE_ROW_VERSION_HISTORY provides a history of row versions in the immutable tables accessible to the current user.

This view is populated for an immutable table with a row version only when rows are purged from that immutable table. For each different value of the PDB_GUID and KEYCOL*n*_VALUE columns, information about only the youngest purged row is kept in the view.

Related Views

- DBA_IMMUTABLE_ROW_VERSION_HISTORY provides a history of row versions in all immutable tables in the database.
- USER_IMMUTABLE_ROW_VERSION_HISTORY provides a history of row versions in the immutable tables owned by the current user. This view does not display the SCHEMA_NAME column.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Schema containing the immutable table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the immutable table
ROW_VERSION_NAME	VARCHAR2(128)	NOT NULL	Name of the row version
PDB_GUID	RAW(16)		Global unique identifier of the pluggable database that inserted the row before any GoldenGate processes might have replicated the row to another database
KEYCOL1_VALUE	VARCHAR2(400)		Value of version key column 1
KEYCOL2_VALUE	VARCHAR2(400)		Value of version key column 2 Null if only one version key column is specified for the row version

Column	Datatype	NULL	Description
KEYCOL3_VALUE	VARCHAR2(400)		Value of version key column 3 Null if only one or two version key columns are specified for the row version
VERSION_NUMBER	NUMBER		Row version number
ROW_CREATE_TIME	TIMESTAMP(6) WITH TIME ZONE		Date and time at which the row version was created
INST_ID	NUMBER		Identifier of any instance using a distributed or XA transaction to append to the row version history
TRAN_ID	VARCHAR2(22)		Identifier of any distributed transaction branch that is appending to the row version history

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_IMMUTABLE_ROW_VERSION_HISTORY"
- "USER_IMMUTABLE_ROW_VERSION_HISTORY"

3.232 ALL_IMMUTABLE_TABLE_COLUMNS

ALL_IMMUTABLE_TABLE_COLUMNS displays information about columns valid in each epoch in the immutable tables accessible to the current user.

Related Views

- DBA_IMMUTABLE_TABLE_COLUMNS displays information about columns valid in each epoch in all immutable tables in the database.
- USER_IMMUTABLE_TABLE_COLUMNS displays information about columns valid in each epoch in the immutable tables owned by the current user. This view does not display the SCHEMA_NAME column.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Name of the schema containing the immutable table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Immutable table name
EPOCH_NUMBER	NUMBER		Epoch number
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
INTERNAL_COLUMN_ID	NUMBER	NOT NULL	Internal identifier of the column
COLUMN_DATA_TYPE	VARCHAR2(106)		Data type of the column

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_IMMUTABLE_TABLE_COLUMNS"
> - "USER_IMMUTABLE_TABLE_COLUMNS"

3.233 ALL_IMMUTABLE_TABLE_EPOCHS

`ALL_IMMUTABLE_TABLE_EPOCHS` displays epoch information for the immutable tables accessible to the current user.

Related Views

- `DBA_IMMUTABLE_TABLE_EPOCHS` displays epoch information for all immutable tables in the database.
- `USER_IMMUTABLE_TABLE_EPOCHS` displays epoch information for the immutable tables owned by the current user. This view does not display the `SCHEMA_NAME` column.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Name of the schema containing the immutable table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Immutable table name
EPOCH_NUMBER	NUMBER		Epoch number
EPOCH_NAME	VARCHAR2(11)		Epoch name describes the reason for the epoch and is one of the following values: • CREATE • IMPORT • ADD COLUMN • DROP COLUMN
PDB_GUID	RAW(16)		Global unique identifier of the pluggable database where the immutable table epoch was created
START_TIME	TIMESTAMP(6) WITH TIME ZONE		Time at which the epoch was created

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_IMMUTABLE_TABLE_EPOCHS"
> - "USER_IMMUTABLE_TABLE_EPOCHS"

3.234 ALL_IMMUTABLE_TABLES

ALL_IMMUTABLE_TABLES describes the immutable tables accessible to the current user.

Related Views

- DBA_IMMUTABLE_TABLES describes all immutable tables in the database.
- USER_IMMUTABLE_TABLES describes the immutable tables owned by the current user. This view does not display the SCHEMA_NAME column.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	The schema containing the immutable table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the immutable table
ROW_RETENTION	NUMBER		Row retention period for the immutable table, that is, the minimum number of days a row must be retained and cannot be deleted after it is inserted into the table If the value of this column is NULL, then rows can never be deleted from the table.
ROW_RETENTION_LOCKED	VARCHAR2(3)		Indicates whether the row retention period for the immutable table is locked. Possible values: • YES: The row retention period is locked. You cannot change the row retention period • NO: The row retention period is not locked. You can change the row retention period to a value higher than the current value with the SQL statement ALTER TABLE … NO DELETE UNTIL *n* DAYS AFTER INSERT
TABLE_INACTIVITY_RETENTION	NUMBER		Number of days for which the immutable table must be inactive before it can be dropped, that is, the number of days that must pass after the most recent row insertion before the table can be dropped A table with no rows can be dropped at any time, regardless of this column value.
TABLE_VERSION	VARCHAR2(7)		Immutable table version. Possible values: • V1 • V2
CURRENT_EPOCH	NUMBER		Current epoch number for the immutable table
DELETE_TIME	TIMESTAMP(6) WITH TIME ZONE		Youngest threshold used to delete rows in the immutable table

> **See Also:**
>
> - "DBA_IMMUTABLE_TABLES"
> - "USER_IMMUTABLE_TABLES"

3.235 ALL_INCOMPLETE_SAGAS

ALL_INCOMPLETE_SAGAS describes the incomplete sagas accessible to the current user.

This view displays sagas that were either initiated in the current PDB or joined by participants in the current PDB.

Related Views

- DBA_INCOMPLETE_SAGAS describes all incomplete sagas in the database.
- USER_INCOMPLETE_SAGAS describes the incomplete sagas owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
ID	RAW(16)	NOT NULL	Saga ID
INITIATOR	VARCHAR2(128)		Name of the saga initiator
IS_INITIATOR	VARCHAR2(3)		Indicates whether this participant is the saga initiator (YES) or not (NO)
COORDINATOR	VARCHAR2(128)		Name of the saga coordinator
COORDINATOR_TYPE	VARCHAR2(50)		Type of the saga coordinator: • Internal • External
OWNER	VARCHAR2(128)	NOT NULL	Owner of the saga participant
PARTICIPANT	VARCHAR2(128)	NOT NULL	Name of the saga participant
STATUS	VARCHAR2(15)		Saga status: • Commit Failed • Rollback Failed • Timeout
VERSION	NUMBER	NOT NULL	Saga version
DURATION	NUMBER		Time limit for the saga (in seconds)
START_TIME	TIMESTAMP(6) WITH TIME ZONE		Saga start time

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_INCOMPLETE_SAGAS"
> - "USER_INCOMPLETE_SAGAS"

3.236 ALL_IND_COLUMNS

ALL_IND_COLUMNS describes the columns of indexes on all tables accessible to the current user.

Related Views

- DBA_IND_COLUMNS describes the columns of indexes on all tables in the database.
- USER_IND_COLUMNS describes the columns of indexes owned by the current user and columns of indexes on tables owned by the current user. This view does not display the INDEX_OWNER or TABLE_OWNER columns.

> **Note:**
>
> For join indexes, the TABLE_NAME and TABLE_OWNER columns in this view may not match the TABLE_NAME and TABLE_OWNER columns you find in the *_INDEXES (and other similar) data dictionary views.

Column	Datatype	NULL	Description
INDEX_OWNER	VARCHAR2(128)	NOT NULL	Owner of the index
INDEX_NAME	VARCHAR2(128)	NOT NULL	Name of the index
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table or cluster
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table or cluster
COLUMN_NAME	VARCHAR2(4000)		Column name or attribute of the object type column **Note:** If you create an index on a user-defined REF column, the system creates the index on the attributes that make up the REF column. Therefore, the column names displayed in this view are the attribute names, with the REF column name as a prefix, in the following form: "REF_name"."attribute"
COLUMN_POSITION	NUMBER	NOT NULL	Position of the column or attribute within the index
COLUMN_LENGTH	NUMBER	NOT NULL	Indexed length of the column
CHAR_LENGTH	NUMBER		Maximum codepoint length of the column
DESCEND	VARCHAR2(4)		Indicates whether the column is sorted in descending order (DESC) or ascending order (ASC)

Column	Datatype	NULL	Description
COLLATED_COLUMN_ID	NUMBER		Internal sequence number of the column for which this column provides linguistic ordering

See Also:

- "DBA_IND_COLUMNS"
- "USER_IND_COLUMNS"

3.237 ALL_IND_EXPRESSIONS

ALL_IND_EXPRESSIONS describes the expressions of function-based indexes on tables accessible to the current user.

Related Views

- DBA_IND_EXPRESSIONS describes the expressions of all function-based indexes in the database.
- USER_IND_EXPRESSIONS describes the expressions of function-based indexes on tables owned by the current user. This view does not display the INDEX_OWNER or TABLE_OWNER columns.

Column	Datatype	NULL	Description
INDEX_OWNER	VARCHAR2(128)	NOT NULL	Owner of the index
INDEX_NAME	VARCHAR2(128)	NOT NULL	Name of the index
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table or cluster
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table or cluster
COLUMN_EXPRESSION	LONG		Function-based index expression defining the column
COLUMN_POSITION	NUMBER	NOT NULL	Position of the column or attribute within the index

See Also:

- "DBA_IND_EXPRESSIONS"
- "USER_IND_EXPRESSIONS"

3.238 ALL_IND_PARTITIONS

ALL_IND_PARTITIONS displays, for each index partition accessible to the current user, the partition-level partitioning information, the storage parameters for the partition, and various partition statistics generated by the DBMS_STATS package.

Related Views

- DBA_IND_PARTITIONS describes all index partitions in the database.
- USER_IND_PARTITIONS describes the index partitions owned by the current user. This view does not display the INDEX_OWNER column.

Column	Datatype	NULL	Description
INDEX_OWNER	VARCHAR2(128)		Owner of the index
INDEX_NAME	VARCHAR2(128)		Name of the index
COMPOSITE	VARCHAR2(3)		Indicates whether the partition belongs to a local index on a composite-partitioned table (YES) or not (NO)
PARTITION_NAME	VARCHAR2(128)		Name of the partition
SUBPARTITION_COUNT	NUMBER		If a local index on a composite-partitioned table, the number of subpartitions in the partition
HIGH_VALUE	LONG		Partition bound value expression
HIGH_VALUE_LENGTH	NUMBER		Length of the partition bound value expression
PARTITION_POSITION	NUMBER		Position of the partition within the index
STATUS	VARCHAR2(8)		Indicates whether the index partition is usable (USABLE) or not (UNUSABLE)
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace containing the partition
PCT_FREE	NUMBER		Minimum percentage of free space in a block
INI_TRANS	NUMBER		Initial number of transactions
MAX_TRANS	NUMBER		Maximum number of transactions
INITIAL_EXTENT	NUMBER		Size of the initial extent in bytes
NEXT_EXTENT	NUMBER		Size of secondary extents in bytes
MIN_EXTENT	NUMBER		Minimum number of extents allowed in the segment
MAX_EXTENT	NUMBER		Maximum number of extents allowed in the segment
MAX_SIZE	NUMBER		Maximum number of blocks allowed in the segment
PCT_INCREASE	NUMBER		Percentage increase in extent size
FREELISTS	NUMBER		Number of process freelists allocated in this segment
FREELIST_GROUPS	NUMBER		Number of process freelist groups allocated in this segment

Column	Datatype	NULL	Description
LOGGING	VARCHAR2(7)		Indicates whether or not changes to the index are logged: • NONE - Not specified **See Also:** the *_IND_SUBPARTITIONS view • YES • NO
COMPRESSION	VARCHAR2(13)		Type of compression being used for the partition: • ENABLED - Prefix compression • ADVANCED HIGH - Advanced high compression • ADVANCED LOW - Advanced low compression • DISABLED - No compression is present
BLEVEL	NUMBER		B*-Tree level (depth of the index from its root block to its leaf blocks). A depth of 0 indicates that the root block and leaf block are the same.
LEAF_BLOCKS	NUMBER		Number of leaf blocks in the index partition
DISTINCT_KEYS	NUMBER		Number of distinct keys in the index partition
AVG_LEAF_BLOCKS_PER_KEY	NUMBER		Average number of leaf blocks in which each distinct value in the index appears, rounded to the nearest integer. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is always 1.
AVG_DATA_BLOCKS_PER_KEY	NUMBER		Average number of data blocks in the table that are pointed to by a distinct value in the index rounded to the nearest integer. This statistic is the average number of data blocks that contain rows that contain a given value for the indexed columns.
CLUSTERING_FACTOR	NUMBER		Indicates the amount of order of the rows in the table based on the values of the index. • If the value is near the number of blocks, then the table is very well ordered. In this case, the index entries in a single leaf block tend to point to rows in the same data blocks. • If the value is near the number of rows, then the table is very randomly ordered. In this case, it is unlikely that index entries in the same leaf block point to rows in the same data blocks.
NUM_ROWS	NUMBER		Number of rows returned
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this partition
LAST_ANALYZED	DATE		Date on which this partition was most recently analyzed
BUFFER_POOL	VARCHAR2(7)		Actual buffer pool for the partition: • DEFAULT • KEEP • RECYCLE • NULL

Column	Datatype	NULL	Description
FLASH_CACHE	VARCHAR2(7)		Database Smart Flash Cache hint to be used for partition blocks: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2(7)		Cell flash cache hint to be used for partition blocks: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
PCT_DIRECT_ACCESS	NUMBER		If a secondary index on index-organized table, the percentage of rows with VALID guess
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics have been gathered or NO if statistics have been aggregated from subpartitions or have not been gathered
DOMIDX_OPSTATUS	VARCHAR2(6)		Status of the operation on a domain index: • NULL - Index is not a domain index • VALID - Operation performed without errors • FAILED - Operation failed with an error
PARAMETERS	VARCHAR2(1000)		For a domain index, the parameter string
INTERVAL	VARCHAR2(3)		Indicates whether the partition is in the interval section of an interval partitioned table (YES) or whether the partition is in the range section (NO)
SEGMENT_CREATED	VARCHAR2(3)		Indicates whether the index partition segment has been created (YES) or not (NO); N/A indicates that this index is subpartitioned and no segment exists at the partition level
ORPHANED_ENTRIES	VARCHAR2(3)		Indicates whether a global index partition contains stale entries because of deferred index maintenance during DROP/TRUNCATE PARTITION, or MODIFY PARTITION INDEXING OFF operations. Possible values: • YES - the index partition contains orphaned entries • NO - the index partition does not contain orphaned entries
HIGH_VALUE_CLOB	CLOB		High value (boundary) information for the index partition, in CLOB format
HIGH_VALUE_JSON	JSON		High value (boundary) information for the index partition, in JSON format

See Also:

- "DBA_IND_PARTITIONS"
- "USER_IND_PARTITIONS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

3.239 ALL_IND_PENDING_STATS

ALL_IND_PENDING_STATS describes the pending statistics for tables, partitions, and subpartitions accessible to the current user collected using the DBMS_STATS package.

Related Views

- DBA_IND_PENDING_STATS describes pending statistics for all tables, partitions, and subpartitions in the database.
- USER_IND_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Name of the index owner
INDEX_NAME	VARCHAR2(128)		Index name
TABLE_OWNER	VARCHAR2(128)		Table owner name
TABLE_NAME	VARCHAR2(128)		Name of the table
PARTITION_NAME	VARCHAR2(128)		Name of the partition
SUBPARTITION_NAME	VARCHAR2(128)		Name of the subpartition
BLEVEL	NUMBER		Number of levels in the index
LEAF_BLOCKS	NUMBER		Number of leaf blocks in the index
DISTINCT_KEYS	NUMBER		Number of distinct keys in the index
AVG_LEAF_BLOCKS_PER_KEY	NUMBER		Average number of leaf blocks per key
AVG_DATA_BLOCKS_PER_KEY	NUMBER		Average number of data blocks per key
CLUSTERING_FACTOR	NUMBER		Clustering factor
NUM_ROWS	NUMBER		Number of rows in the index
SAMPLE_SIZE	NUMBER		Sample size
LAST_ANALYZED	DATE		Time of the last analysis

See Also:

- "DBA_IND_PENDING_STATS"
- "USER_IND_PENDING_STATS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

3.240 ALL_IND_STATISTICS

ALL_IND_STATISTICS displays optimizer statistics for the indexes on the tables accessible to the current user collected using the DBMS_STATS package.

Related Views

- DBA_IND_STATISTICS displays optimizer statistics for all indexes in the database.
- USER_IND_STATISTICS displays optimizer statistics for the indexes on the tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the index
INDEX_NAME	VARCHAR2(128)		Name of the index
TABLE_OWNER	VARCHAR2(128)		Owner of the indexed object
TABLE_NAME	VARCHAR2(128)		Name of the indexed object
PARTITION_NAME	VARCHAR2(128)		Name of the partition
PARTITION_POSITION	NUMBER		Position of the partition within the index
SUBPARTITION_NAME	VARCHAR2(128)		Name of the subpartition
SUBPARTITION_POSITION	NUMBER		Position of the subpartition within the partition
OBJECT_TYPE	VARCHAR2(12)		Type of the object: • INDEX • PARTITION • SUBPARTITION
BLEVEL	NUMBER		B-Tree level
LEAF_BLOCKS	NUMBER		Number of leaf blocks in the index
DISTINCT_KEYS	NUMBER		Number of distinct keys in the index
AVG_LEAF_BLOCKS_PER_KEY	NUMBER		Average number of leaf blocks per key
AVG_DATA_BLOCKS_PER_KEY	NUMBER		Average number of data blocks per key

Column	Datatype	NULL	Description
CLUSTERING_FACTOR	NUMBER		Indicates the amount of order of the rows in the table based on the values of the index. • If the value is near the number of blocks, then the table is very well ordered. In this case, the index entries in a single leaf block tend to point to rows in the same data blocks. • If the value is near the number of rows, then the table is very randomly ordered. In this case, it is unlikely that index entries in the same leaf block point to rows in the same data blocks.
NUM_ROWS	NUMBER		Number of rows in the index
AVG_CACHED_BLOCKS	NUMBER		Average number of blocks in the buffer cache
AVG_CACHE_HIT_RATIO	NUMBER		Average cache hit ratio for the object
SAMPLE_SIZE	NUMBER		Sample size used in analyzing the index
LAST_ANALYZED	DATE		Date of the most recent time the index was analyzed
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics are gathered or incrementally maintained, otherwise it will be NO
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
STATTYPE_LOCKED	VARCHAR2(5)		Type of statistics lock
STALE_STATS	VARCHAR2(3)		Whether statistics for the object are stale or not
SCOPE	VARCHAR2(7)		The value is SHARED for statistics gathered on any table other than global temporary tables. For a global tempoary table, the possible values are: • SESSION - Indicates that the statistics are session-specific • SHARED - Indicates that the statistics are shared across all sessions See *Oracle Database PL/SQL Packages and Types Reference* for information about using the GLOBAL_TEMP_TABLE_STATS preference of the DBMS_STATS package to control whether to gather session or shared statistics for global temporary tables.

See Also:

- "DBA_IND_STATISTICS"
- "USER_IND_STATISTICS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

3.241 ALL_IND_SUBPARTITIONS

ALL_IND_SUBPARTITIONS displays, for each index subpartition accessible to the current user, the subpartition-level partitioning information, the storage parameters for the subpartition, and various subpartition statistics generated by the DBMS_STATS package.

Related Views

- DBA_IND_SUBPARTITIONS describes all index subpartitions in the database.
- USER_IND_SUBPARTITIONS describes the index subpartitions owned by the current user. This view does not display the INDEX_OWNER column.

Column	Datatype	NULL	Description
INDEX_OWNER	VARCHAR2(128)	NOT NULL	Owner of the index
INDEX_NAME	VARCHAR2(128)	NOT NULL	Name of the index
PARTITION_NAME	VARCHAR2(128)		Name of the partition
SUBPARTITION_NAME	VARCHAR2(128)		Name of the subpartition
HIGH_VALUE	LONG		Subpartition bound value expression
HIGH_VALUE_LENGTH	NUMBER	NOT NULL	Length of the subpartition bound value expression
PARTITION_POSITION	NUMBER		Position of the partition within the index
SUBPARTITION_POSITION	NUMBER		Position of a subpartition within a partition
STATUS	VARCHAR2(8)		Indicates whether the index partition is usable (USABLE) or not (UNUSABLE)
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of the tablespace containing the partition
PCT_FREE	NUMBER	NOT NULL	Minimum percentage of free space in a block
INI_TRANS	NUMBER	NOT NULL	Initial number of transactions
MAX_TRANS	NUMBER	NOT NULL	Maximum number of transactions
INITIAL_EXTENT	NUMBER		Size of the initial extent in bytes
NEXT_EXTENT	NUMBER		Size of secondary extents in bytes
MIN_EXTENT	NUMBER		Minimum number of extents allowed in the segment
MAX_EXTENT	NUMBER		Maximum number of extents allowed in the segment
MAX_SIZE	NUMBER		Maximum number of blocks allowed in the segment
PCT_INCREASE	NUMBER	NOT NULL	Percentage increase in extent size
FREELISTS	NUMBER		Number of process freelists allocated in this segment
FREELIST_GROUPS	NUMBER		Number of process freelist groups allocated in this segment
LOGGING	VARCHAR2(3)		Indicates whether or not changes to the index are logged: • YES • NO

Column	Datatype	NULL	Description
COMPRESSION	VARCHAR2(13)		Type of compression being used for the subpartition: • ENABLED - Prefix compression • ADVANCED HIGH - Advanced high compression • ADVANCED LOW - Advanced low compression • DISABLED - No compression is present
BLEVEL	NUMBER		B-Tree level (depth of the index from its root block to its leaf blocks). A depth of 0 indicates that the root block and leaf block are the same.
LEAF_BLOCKS	NUMBER		Number of leaf blocks in the index
DISTINCT_KEYS	NUMBER		Number of distinct keys in the index partition
AVG_LEAF_BLOCKS_PER_KEY	NUMBER		Average number of leaf blocks in which each distinct value in the index appears, rounded to the nearest integer. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is always 1.
AVG_DATA_BLOCKS_PER_KEY	NUMBER		Average number of data blocks in the table that are pointed to by a distinct value in the index rounded to the nearest integer. This statistic is the average number of data blocks that contain rows that contain a given value for the indexed columns.
CLUSTERING_FACTOR	NUMBER		Indicates the amount of order of the rows in the table based on the values of the index. • If the value is near the number of blocks, then the table is very well ordered. In this case, the index entries in a single leaf block tend to point to rows in the same data blocks. • If the value is near the number of rows, then the table is very randomly ordered. In this case, it is unlikely that index entries in the same leaf block point to rows in the same data blocks.
NUM_ROWS	NUMBER		Number of rows in this index subpartition
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this subpartition
LAST_ANALYZED	DATE		Date on which this partition was most recently analyzed
BUFFER_POOL	VARCHAR2(7)		Buffer pool for the subpartition: • DEFAULT • KEEP • RECYCLE • NULL
FLASH_CACHE	VARCHAR2(7)		Database Smart Flash Cache hint to be used for subpartition blocks: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.

Column	Datatype	NULL	Description
CELL_FLASH_CACHE	VARCHAR2(7)		Cell flash cache hint to be used for subpartition blocks: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics have been gathered or NO if statistics have not been gathered
INTERVAL	VARCHAR2(3)		Indicates whether the partition is in the interval section of an interval partitioned table (YES) or whether the partition is in the range section (NO)
SEGMENT_CREATED	VARCHAR2(3)		Indicates whether the index subpartition segment has been created (YES) or not (NO); N/A indicates that this index is not subpartitioned
DOMIDX_OPSTATUS	VARCHAR2(6)		Status of the operation on the domain index: • NULL - Index is not a domain index • VALID - Operation performed without errors • FAILED - Operation failed with an error
PARAMETERS	VARCHAR2(1000)		For a domain index, the parameter string
HIGH_VALUE_CLOB	CLOB		High value (boundary) information for the index subpartition, in CLOB format
HIGH_VALUE_JSON	JSON		High value (boundary) information for the index subpartition, in JSON format

See Also:

- "DBA_IND_SUBPARTITIONS"
- "USER_IND_SUBPARTITIONS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

3.242 ALL_INDEXES

ALL_INDEXES describes the indexes on the tables accessible to the current user.

To gather statistics for this view and the related views DBA_INDEXES and USER_INDEXES, use the DBMS_STATS package.

Related Views

- DBA_INDEXES describes all indexes in the database.

- USER_INDEXES describes the indexes owned by the current user. This view does not display the OWNER column.

> **Note:**
>
> Column names followed by an asterisk are populated only if you collect statistics on the index using the DBMS_STATS package.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the index
INDEX_NAME	VARCHAR2(128)	NOT NULL	Name of the index
INDEX_TYPE	VARCHAR2(27)		Type of the index: • LOB • NORMAL • NORMAL/REV • BITMAP • FUNCTION-BASED NORMAL • FUNCTION-BASED NORMAL/REV • FUNCTION-BASED BITMAP • FUNCTION-BASED DOMAIN • CLUSTER • IOT - TOP • DOMAIN
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the indexed object
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the indexed object
TABLE_TYPE	CHAR(11)		Type of the indexed object: • NEXT OBJECT • INDEX • TABLE • CLUSTER • VIEW • SYNONYM • SEQUENCE
UNIQUENESS	VARCHAR2(9)		Indicates whether the index is unique (UNIQUE) or nonunique (NONUNIQUE)
COMPRESSION	VARCHAR2(13)		Type of compression being used for the index: • ENABLED - Prefix compression • ADVANCED HIGH - Advanced high compression • ADVANCED LOW - Advanced low compression • DISABLED - No compression is present
PREFIX_LENGTH	NUMBER		Number of columns in the prefix of the compression key
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace containing the index
INI_TRANS	NUMBER		Initial number of transactions
MAX_TRANS	NUMBER		Maximum number of transactions
INITIAL_EXTENT	NUMBER		Size of the initial extent

Column	Datatype	NULL	Description
NEXT_EXTENT	NUMBER		Size of secondary extents
MIN_EXTENTS	NUMBER		Minimum number of extents allowed in the segment
MAX_EXTENTS	NUMBER		Maximum number of extents allowed in the segment
PCT_INCREASE	NUMBER		Percentage increase in extent size
PCT_THRESHOLD	NUMBER		Threshold percentage of block space allowed per index entry
INCLUDE_COLUMN	NUMBER		Column ID of the last column to be included in index-organized table primary key (non-overflow) index. This column maps to the COLUMN_ID column of the *_TAB_COLUMNS view.
FREELISTS	NUMBER		Number of process freelists allocated to this segment
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to this segment
PCT_FREE	NUMBER		Minimum percentage of free space in a block
LOGGING	VARCHAR2(3)		Indicates whether or not changes to the index are logged: • YES • NO
BLEVEL*	NUMBER		B*-Tree level (depth of the index from its root block to its leaf blocks). A depth of 0 indicates that the root block and leaf block are the same.
LEAF_BLOCKS*	NUMBER		Number of leaf blocks in the index
DISTINCT_KEYS*	NUMBER		Number of distinct indexed values. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is the same as the number of rows in the table (*_TABLES.NUM_ROWS)
AVG_LEAF_BLOCKS_PER_KEY*	NUMBER		Average number of leaf blocks in which each distinct value in the index appears, rounded to the nearest integer. For indexes that enforce UNIQUE and PRIMARY KEY constraints, this value is always 1.
AVG_DATA_BLOCKS_PER_KEY*	NUMBER		Average number of data blocks in the table that are pointed to by a distinct value in the index rounded to the nearest integer. This statistic is the average number of data blocks that contain rows that contain a given value for the indexed columns.

Column	Datatype	NULL	Description
CLUSTERING_FACTOR*	NUMBER		Indicates the amount of order of the rows in the table based on the values of the index. • If the value is near the number of blocks, then the table is very well ordered. In this case, the index entries in a single leaf block tend to point to rows in the same data blocks. • If the value is near the number of rows, then the table is very randomly ordered. In this case, it is unlikely that index entries in the same leaf block point to rows in the same data blocks. For bitmap indexes, this column is not applicable.
STATUS	VARCHAR2(8)		Indicates whether a nonpartitioned index is VALID or UNUSABLE
NUM_ROWS	NUMBER		Number of rows in the index. For bitmap indexes, this column is the number of distinct keys, so its value is the same as the DISTINCT_KEYS column.
SAMPLE_SIZE	NUMBER		Size of the sample used to analyze the index
LAST_ANALYZED	DATE		Date on which this index was most recently analyzed
DEGREE	VARCHAR2(40)		Number of threads per instance for scanning the index, or DEFAULT
INSTANCES	VARCHAR2(40)		Number of instances across which the indexes to be scanned, or DEFAULT
PARTITIONED	VARCHAR2(3)		Indicates whether the index is partitioned (YES) or not (NO)
TEMPORARY	VARCHAR2(1)		Indicates whether the index is on a temporary table (Y) or not (N)
GENERATED	VARCHAR2(1)		Indicates whether the name of the index is system-generated (Y) or not (N)
SECONDARY	VARCHAR2(1)		Indicates whether the index is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y) or not (N)
BUFFER_POOL	VARCHAR2(7)		Buffer pool to be used for index blocks: • DEFAULT • KEEP • RECYCLE • NULL
FLASH_CACHE	VARCHAR2(7)		Database Smart Flash Cache hint to be used for index blocks: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.

Column	Datatype	NULL	Description
CELL_FLASH_CACHE	VARCHAR2(7)		Cell flash cache hint to be used for index blocks: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
DURATION	VARCHAR2(15)		Indicates the duration of a temporary table: • SYS$SESSION - Rows are preserved for the duration of the session • SYS$TRANSACTION - Rows are deleted after COMMIT NULL - Permanent table
PCT_DIRECT_ACCESS	NUMBER		For a secondary index on an index-organized table, the percentage of rows with VALID guess
ITYP_OWNER	VARCHAR2(128)		For a domain index, the owner of the indextype
ITYP_NAME	VARCHAR2(128)		For a domain index, the name of the indextype
PARAMETERS	VARCHAR2(1000)		For a domain index, the parameter string
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics are gathered or incrementally maintained, otherwise it will be NO
DOMIDX_STATUS	VARCHAR2(12)		Status of a domain index: • NULL - Index is not a domain index • VALID - Index is a valid domain index • IDXTYP_INVLD - Indextype of the domain index is invalid
DOMIDX_OPSTATUS	VARCHAR2(6)		Status of the operation on a domain index: • NULL - Index is not a domain index • VALID - Operation performed without errors • FAILED - Operation failed with an error
FUNCIDX_STATUS	VARCHAR2(8)		Status of a function-based index: • NULL - Index is not a function-based index • ENABLED - Function-based index is enabled • DISABLED - Function-based index is disabled
JOIN_INDEX	VARCHAR2(3)		Indicates whether the index is a join index (YES) or not (NO)
IOT_REDUNDANT_PKEY_ELIM	VARCHAR2(3)		Indicates whether redundant primary key columns are eliminated from secondary indexes on index-organized tables (YES) or not (NO)
DROPPED	VARCHAR2(3)		Indicates whether the index has been dropped and is in the recycle bin (YES) or not (NO); NULL for partitioned tables This view does not return the names of indexes that have been dropped.
VISIBILITY	VARCHAR2(9)		Indicates whether the index is VISIBLE or INVISIBLE to the optimizer

Column	Datatype	NULL	Description
DOMIDX_MANAGEMENT	VARCHAR2(14)		If this is a domain index, indicates whether the domain index is system-managed (SYSTEM_MANAGED) or user-managed (USER_MANAGED)
SEGMENT_CREATED	VARCHAR2(3)		Indicates whether the index segment has been created (YES) or not (NO)
ORPHANED_ENTRIES	VARCHAR2(3)		Indicates whether a global index contains stale entries because of deferred index maintenance during DROP/TRUNCATE PARTITION, or MODIFY PARTITION INDEXING OFF operations. Possible values: • YES - The index contains orphaned entries • NO - The index does not contain orphaned entries
INDEXING	VARCHAR2(7)		Indicates whether a global index is decoupled from the underlying table. Possible values: • PARTIAL - The index is partial, that is, it will follow the table's indexing property. • FULL - The index will include all partitions of the table.
AUTO	VARCHAR2(3)		Indicates whether the index is an auto index (YES) or not (NO)
CONSTRAINT_INDEX	VARCHAR2(3)		Indicates whether the index was created as part of a constraint (YES) or not (NO)

See Also:

- "DBA_INDEXES"
- "USER_INDEXES"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

3.243 ALL_INDEXTYPE_ARRAYTYPES

ALL_INDEXTYPE_ARRAYTYPES displays information about the array types specified by the indextypes accessible to the current user.

Related Views

- DBA_INDEXTYPE_ARRAYTYPES displays information about the array types specified by all indextypes in the database.
- USER_INDEXTYPE_ARRAYTYPES displays information about the array types specified by the indextypes owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the indextype
INDEXTYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the indextype
BASE_TYPE_SCHEMA	VARCHAR2(128)		Name of the base type schema
BASE_TYPE_NAME	VARCHAR2(128)		Name of the base type name
BASE_TYPE	VARCHAR2(30)		Datatype of the base type
ARRAY_TYPE_SCHEMA	VARCHAR2(128)	NOT NULL	Name of the array type schema
ARRAY_TYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the array type name

See Also:

- "DBA_INDEXTYPE_ARRAYTYPES"
- "USER_INDEXTYPE_ARRAYTYPES"

3.244 ALL_INDEXTYPE_COMMENTS

ALL_INDEXTYPE_COMMENTS displays comments for the user-defined indextypes accessible to the current user.

Related Views

- DBA_INDEXTYPE_COMMENTS displays comments for all user-defined indextypes in the database.
- USER_INDEXTYPE_COMMENTS displays comments for the user-defined indextypes owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the user-defined indextype
INDEXTYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the user-defined indextype
COMMENTS	VARCHAR2(4000)		Comment for the user-defined indextype

See Also:

- "DBA_INDEXTYPE_COMMENTS"
- "USER_INDEXTYPE_COMMENTS"

3.245 ALL_INDEXTYPE_OPERATORS

ALL_INDEXTYPE_OPERATORS lists all operators supported by indextypes accessible to the current user.

Related Views

- DBA_INDEXTYPE_OPERATORS lists all operators supported by indextypes in the database.
- USER_INDEXTYPE_OPERATORS lists all operators supported by indextypes owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the indextype
INDEXTYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the indextype
OPERATOR_SCHEMA	VARCHAR2(128)	NOT NULL	Name of the operator schema
OPERATOR_NAME	VARCHAR2(128)	NOT NULL	Name of the operator for which the indextype is defined
BINDING#	NUMBER	NOT NULL	Binding number associated with the operator

See Also:

- "DBA_INDEXTYPE_OPERATORS"
- "USER_INDEXTYPE_OPERATORS"

3.246 ALL_INDEXTYPES

ALL_INDEXTYPES displays information about the indextypes accessible to the current user.

Related Views

- DBA_INDEXTYPES displays information about all indextypes in the database.
- USER_INDEXTYPES displays information about the indextypes owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the indextype
INDEXTYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the indextype
IMPLEMENTATION_SCHEMA	VARCHAR2(128)	NOT NULL	Name of the schema for the indextype implementation (that is, containing the indextype operators)
IMPLEMENTATION_NAME	VARCHAR2(128)	NOT NULL	Name of the indextype implementation type
INTERFACE_VERSION	NUMBER		Version of the indextype interface
IMPLEMENTATION_VERSION	NUMBER	NOT NULL	Version of the indextype implementation

Column	Datatype	NULL	Description
NUMBER_OF_OPERATORS	NUMBER		Number of operators associated with the indextype
PARTITIONING	VARCHAR2(10)		Kinds of local partitioning supported by the indextype: • NONE - Indextype does not support local domain indexes • RANGE - Indextype can support range partitioned local user managed domain indexes • LOCAL - Indextype can support local system managed domain indexes (range, list, hash, or interval)
ARRAY_DML	VARCHAR2(3)		Indicates whether the indextype supports array DML (YES) or not (NO)
MAINTENANCE_TYPE	VARCHAR2(14)		Indicates whether the indextype is system-managed (SYSTEM_MANAGED) or user-managed (USER_MANAGED)

See Also:

- "DBA_INDEXTYPES"
- "USER_INDEXTYPES"

3.247 ALL_INTERNAL_TRIGGERS

ALL_INTERNAL_TRIGGERS describes internal triggers on tables accessible to the current user. Internal triggers are internal pieces of code executed when a particular flag is set for a table. This view does not display the OWNER_NAME column.

Related Views

- DBA_INTERNAL_TRIGGERS describes internal triggers on all tables in the database.
- USER_INTERNAL_TRIGGERS describes all internal triggers on tables owned by the current user. This view does not display the OWNER_NAME column.

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2(128)		Name of the table on which the trigger is defined
INTERNAL_TRIGGER_TYPE	VARCHAR2(19)		Indicates the type of internal trigger on the table

See Also:

- "DBA_INTERNAL_TRIGGERS"
- "USER_INTERNAL_TRIGGERS"

3.248 ALL_JAVA_ARGUMENTS

ALL_JAVA_ARGUMENTS displays argument information about the stored Java classes accessible to the current user.

Related Views

- DBA_JAVA_ARGUMENTS displays argument information about all stored Java classes in the database.
- USER_JAVA_ARGUMENTS displays argument information about the stored Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Java class
NAME	VARCHAR2(4000)		Name of the Java class
METHOD_INDEX	NUMBER		Index of the hosting method of the argument
METHOD_NAME	VARCHAR2(4000)		Name of the hosting method of the argument
ARGUMENT_POSITION	NUMBER		Position of the argument, starting from 0
ARRAY_DEPTH	NUMBER		Array depth of the type of the argument
BASE_TYPE	VARCHAR2(7)		Base type of the type of the argument: • int • long • float • double • boolean • byte • char • short • class
ARGUMENT_CLASS	VARCHAR2(4000)		Actual class name of the argument if the base type is class

See Also:

- "DBA_JAVA_ARGUMENTS"
- "USER_JAVA_ARGUMENTS"

3.249 ALL_JAVA_CLASSES

ALL_JAVA_CLASSES displays class level information about the stored Java classes accessible to the current user.

Related Views

- DBA_JAVA_CLASSES displays class level information about all stored Java classes in the database.
- USER_JAVA_CLASSES displays class level information about the stored Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Java class
NAME	VARCHAR2(4000)		Name of the Java class
MAJOR	NUMBER		Major version number of the Java class, as defined in the JVM specification
MINOR	NUMBER		Minor version number of the Java class, as defined in the JVM specification
KIND	VARCHAR2(50)		Indicates whether the stored object is a Java class (CLASS) or a Java interface (INTERFACE)
ACCESSIBILITY	VARCHAR2(9)		Accessibility of the Java class
IS_INNER	VARCHAR2(3)		Indicates whether this Java class is an inner class (YES) or not (NO)
IS_ABSTRACT	VARCHAR2(3)		Indicates whether this Java class is an abstract class (YES) or not (NO)
IS_FINAL	VARCHAR2(3)		Indicates whether this Java class is a final class (YES) or not (NO)
IS_STATIC	VARCHAR2(3)		Indicates whether this is a static inner class (YES) or not (NO)
IS_STRICTFP	VARCHAR2(3)		Indicates whether the class is declared strict floating point for portability (YES) or not (NO)
IS_SYNTHETIC	VARCHAR2(3)		Indicates whether this is an inner class generated by the compiler (YES) or not (NO)
IS_DEBUG	VARCHAR2(3)		Indicates whether this Java class contains debug information (YES) or not (NO)
SOURCE	VARCHAR2(4000)		Source designation of the Java class
SUPER	VARCHAR2(4000)		Super class of this Java class
OUTER	VARCHAR2(4000)		Outer class of this Java class if this Java class is an inner class

> **See Also:**
>
> - "DBA_JAVA_CLASSES"
> - "USER_JAVA_CLASSES"

3.250 ALL_JAVA_COMPILER_OPTIONS

ALL_JAVA_COMPILER_OPTIONS displays information about the native compiler options accessible to the current user.

Related Views

- DBA_JAVA_COMPILER_OPTIONS displays information about all native compiler options in the database.
- USER_JAVA_COMPILER_OPTIONS displays information about the native compiler options owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the native compiler option
OPTION_NAME	VARCHAR2(64)		Name of the native compiler option
VALUE	VARCHAR2(4000)		Value of the native compiler option

> **See Also:**
>
> - "DBA_JAVA_COMPILER_OPTIONS"
> - "USER_JAVA_COMPILER_OPTIONS"

3.251 ALL_JAVA_DERIVATIONS

ALL_JAVA_DERIVATIONS displays mapping information about Java source objects and their derived Java class objects and Java resource objects for the Java classes accessible to the current user.

Related Views

- DBA_JAVA_DERIVATIONS displays mapping information about Java source objects and their derived Java class objects and Java resource objects for all Java classes in the database.
- USER_JAVA_DERIVATIONS displays mapping information about Java source objects and their derived Java class objects and Java resource objects for the Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Java source object
SOURCE_NAME	VARCHAR2(4000)		Name of the Java source object
CLASS_INDEX	NUMBER		Index of the derived Java class object
CLASS_NAME	VARCHAR2(4000)		Name of the derived Java class object

See Also:

- "DBA_JAVA_DERIVATIONS"
- "USER_JAVA_DERIVATIONS"

3.252 ALL_JAVA_FIELDS

ALL_JAVA_FIELDS displays field information about the stored Java classes accessible to the current user.

Related Views

- DBA_JAVA_FIELDS displays field information about all stored Java classes in the database.
- USER_JAVA_FIELDS displays field information about the stored Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Java class
NAME	VARCHAR2(4000)		Name of the Java class
FIELD_INDEX	NUMBER		Index of the field
FIELD_NAME	VARCHAR2(4000)		Name of the field identified by the FIELD_INDEX column
ACCESSIBILITY	VARCHAR2(9)		Accessibility of the field: • PUBLIC • PRIVATE • PROTECTED
IS_STATIC	VARCHAR2(3)		Indicates whether the field is a static field (YES) or not (NO)
IS_FINAL	VARCHAR2(3)		Indicates whether the field is a final field (YES) or not (NO)
IS_VOLATILE	VARCHAR2(3)		Indicates whether the field is volatile (YES) or not (NO)
IS_TRANSIENT	VARCHAR2(3)		Indicates whether the field is transient (YES) or not (NO)
IS_SYNTHETIC	VARCHAR2(3)		Indicates whether the field is generated by the compiler (YES) or not (NO)

Column	Datatype	NULL	Description
IS_ENUM	VARCHAR2(3)		Indicates whether the field is a member of an enum (YES) or not (NO)
ARRAY_DEPTH	NUMBER		Array depth of the type of the field
BASE_TYPE	VARCHAR2(7)		Base type of the type of the field: • int • long • float • double • boolean • byte • char • short • class
FIELD_CLASS	VARCHAR2(4000)		Actual class name of the base object if the base type is class

See Also:

- "DBA_JAVA_FIELDS"
- "USER_JAVA_FIELDS"

3.253 ALL_JAVA_IMPLEMENTS

ALL_JAVA_IMPLEMENTS describes interfaces implemented by the stored Java classes accessible to the current user.

Related Views

- DBA_JAVA_IMPLEMENTS describes interfaces implemented by all stored Java classes in the database.
- USER_JAVA_IMPLEMENTS describes interfaces implemented by the stored Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Java class
NAME	VARCHAR2(4000)		Name of the Java class
INTERFACE_INDEX	NUMBER		Index of the interfaces implemented by the Java class
INTERFACE_NAME	VARCHAR2(4000)		Name of the interface identified by the INTERFACE_INDEX column

> **See Also:**
>
> - "DBA_JAVA_IMPLEMENTS"
> - "USER_JAVA_IMPLEMENTS"

3.254 ALL_JAVA_INNERS

ALL_JAVA_INNERS displays information about inner classes referred to by the stored Java classes accessible to the current user.

Related Views

- DBA_JAVA_INNERS displays information about inner classes referred to by all stored Java classes in the database.
- USER_JAVA_INNERS displays information about inner classes referred to by the stored Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Java class
NAME	VARCHAR2(4000)		Name of the Java class
INNER_INDEX	NUMBER		Index of the referred inner class
SIMPLE_NAME	VARCHAR2(4000)		Simple name of the referred inner class
FULL_NAME	VARCHAR2(4000)		Full name of the referred inner class
ACCESSIBILITY	VARCHAR2(9)		Accessibility of the referred inner class: • PUBLIC • PRIVATE • PROTECTED
IS_STATIC	VARCHAR2(3)		Indicates whether the referred inner class is declared static in the source file (YES) or not (NO)
IS_FINAL	VARCHAR2(3)		Indicates whether the referred inner class is declared final in the source file (YES) or not (NO)
IS_ABSTRACT	VARCHAR2(3)		Indicates whether the referred inner class is declared abstract in the source file (YES) or not (NO)
IS_INTERFACE	VARCHAR2(3)		Indicates whether the referred inner class is declared interface in the source file (YES) or not (NO)
IS_STRICTFP	VARCHAR2(3)		Indicates whether the inner class is declared strictfp (YES) or not (NO)
IS_SYNTHETIC	VARCHAR2(3)		Indicates whether the inner class is generated by the compiler (YES) or not (NO)
IS_ENUM	VARCHAR2(3)		Indicates whether the inner class is an enum (YES) or not (NO)
IS_ANNOTATION	VARCHAR2(3)		Indicates whether the inner class is an annotation (YES) or not (NO)

Column	Datatype	NULL	Description
KIND	VARCHAR2(50)		Type (class, interface, enum or annotation) of the inner class
ALL_QUALIFIERS	VARCHAR2(101)		Concatenation of accessibility, type and other attributes of the inner class

See Also:

- "DBA_JAVA_INNERS"
- "USER_JAVA_INNERS"

3.255 ALL_JAVA_LAYOUTS

ALL_JAVA_LAYOUTS displays class layout information about the stored Java classes accessible to the current user.

Related Views

- DBA_JAVA_LAYOUTS displays class layout information about all stored Java classes in the database.
- USER_JAVA_LAYOUTS displays class layout information about the stored Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Java class
NAME	VARCHAR2(4000)		Name of the Java class
INTERFACES	NUMBER		Number of interfaces that this Java class implements
INNER_CLASSES	NUMBER		Number of inner classes that this Java class contains
FIELDS	NUMBER		Number of locally declared fields that this Java class contains
STATIC_FIELDS	NUMBER		Number of locally declared static fields that this Java class contains
METHODS	NUMBER		Number of locally declared methods that this Java class contains
STATIC_METHODS	NUMBER		Number of locally declared static methods that this Java class contains
NATIVE_METHODS	NUMBER		Number of locally declared native methods that this Java class contains

> **See Also:**
>
> - "DBA_JAVA_LAYOUTS"
> - "USER_JAVA_LAYOUTS"

3.256 ALL_JAVA_METHODS

ALL_JAVA_METHODS displays method information about the stored Java classes accessible to the current user.

Related Views

- DBA_JAVA_METHODS displays method information about all stored Java classes in the database.
- USER_JAVA_METHODS displays method information about the stored Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Java class
NAME	VARCHAR2(4000)		Name of the Java class
METHOD_INDEX	NUMBER		Index of the method
METHOD_NAME	VARCHAR2(4000)		Name of the method identified by the METHOD_INDEX column
ACCESSIBILITY	VARCHAR2(9)		Accessibility of the method: • PUBLIC • PRIVATE • PROTECTED
IS_STATIC	VARCHAR2(3)		Indicates whether the method is a static method (YES) or not (NO)
IS_FINAL	VARCHAR2(3)		Indicates whether the method is a final method (YES) or not (NO)
IS_SYNCHRONIZED	VARCHAR2(3)		Indicates whether the method is a synchronized method (YES) or not (NO)
HAS_VARARGS	VARCHAR2(3)		Indicates whether the method has a variable number of arguments (YES) or not (NO)
IS_NATIVE	VARCHAR2(3)		Indicates whether the method is a native method (YES) or not (NO)
IS_ABSTRACT	VARCHAR2(3)		Indicates whether the method is an abstract method (YES) or not (NO)
IS_STRICTFP	VARCHAR2(3)		Indicates whether the method is a strict method (YES) or not (NO)
IS_SYNTHETIC	VARCHAR2(3)		Indicates whether the method is generated by the compiler (YES) or not (NO)
ARGUMENTS	NUMBER		Number of arguments of the method
THROWS	NUMBER		Number of exceptions thrown by the method

Column	Datatype	NULL	Description
ARRAY_DEPTH	NUMBER		Array depth of the return type of the method
BASE_TYPE	VARCHAR2(7)		Base type of the return type of the method: • int • long • float • double • boolean • byte • char • short • class • void
RETURN_CLASS	VARCHAR2(4000)		Actual class name of the return value if the base type is class
IS_COMPILED	VARCHAR2(3)		Indicates whether the Java method has been natively compiled by the JIT compiler (YES) or not (NO)

See Also:

- "DBA_JAVA_METHODS"
- "USER_JAVA_METHODS"

3.257 ALL_JAVA_NCOMPS

ALL_JAVA_NCOMPS displays ncomp-related information about the Java classes accessible to the current user.

Related Views

- DBA_JAVA_NCOMPS displays ncomp-related information about all Java classes in the database.
- USER_JAVA_NCOMPS displays ncomp-related information about the Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Java class object
NAME	VARCHAR2(4000)		Name of the Java class object
SOURCE	VARCHAR2(4000)		ncomp source shown in this row
INITIALIZER	VARCHAR2(4000)		ncomp initializer shown in this row
LIBRARYFILE	VARCHAR2(4000)		ncomp library file shown in this row
LIBRARY	VARCHAR2(4000)		ncomp library shown in this row

See Also:

- "DBA_JAVA_NCOMPS"
- "USER_JAVA_NCOMPS"

3.258 ALL_JAVA_RESOLVERS

ALL_JAVA_RESOLVERS displays information about resolvers of the Java classes accessible to the current user.

Related Views

- DBA_JAVA_RESOLVERS displays information about resolvers of all Java classes in the database.
- USER_JAVA_RESOLVERS displays information about resolvers of the Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Java class object
NAME	VARCHAR2(4000)		Name of the Java class object
TERM_INDEX	NUMBER		Index of the resolver term in this row
PATTERN	VARCHAR2(4000)		Resolver pattern of the resolver term identified by the TERM_INDEX column
SCHEMA	VARCHAR2(64)		Resolver schema of the resolver term identified by the TERM_INDEX column

See Also:

- "DBA_JAVA_RESOLVERS"
- "USER_JAVA_RESOLVERS"

3.259 ALL_JAVA_THROWS

ALL_JAVA_THROWS displays information about exceptions thrown from methods of the Java classes accessible to the current user.

Related Views

- DBA_JAVA_THROWS displays information about exceptions thrown from methods of all Java classes in the database.
- USER_JAVA_THROWS displays information about exceptions thrown from methods of the Java classes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Java class
NAME	VARCHAR2(4000)		Name of the Java class
METHOD_INDEX	NUMBER		Index of the throwing method of the exception
METHOD_NAME	VARCHAR2(4000)		Name of the throwing method of the exception
EXCEPTION_INDEX	NUMBER		Index of the exception
EXCEPTION_CLASS	VARCHAR2(4000)		Class of the exception

See Also:

- "DBA_JAVA_THROWS"
- "USER_JAVA_THROWS"

3.260 ALL_JOBS

ALL_JOBS is a synonym for USER_JOBS.

See Also:

"USER_JOBS"

3.261 ALL_JOIN_IND_COLUMNS

ALL_JOIN_IND_COLUMNS describes the join conditions of bitmap join indexes accessible to the current user. Bitmap join indexes are indexes built on a child table with an index key containing columns from associated parent tables, where all of the tables are connected through join conditions. There is one row for each join condition.

Related Views

- DBA_JOIN_IND_COLUMNS describes all join conditions in the database.
- USER_JOIN_IND_COLUMNS describes the join conditions owned by the current user. This view does not display the INDEX_OWNER column.

Column	Datatype	NULL	Description
INDEX_OWNER	VARCHAR2(128)	NOT NULL	Owner of the bitmap join index
INDEX_NAME	VARCHAR2(128)	NOT NULL	Name of the bitmap join index
INNER_TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the fact table
INNER_TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the fact table
INNER_TABLE_COLUMN	VARCHAR2(128)	NOT NULL	Name of the fact table join column

Column	Datatype	NULL	Description
OUTER_TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the dimension table
OUTER_TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the dimension table
OUTER_TABLE_COLUMN	VARCHAR2(128)	NOT NULL	Name of the dimension table join column

See Also:

- "DBA_JOIN_IND_COLUMNS"
- "USER_JOIN_IND_COLUMNS"

3.262 ALL_JSON_COLLECTION_TABLES

ALL_JSON_COLLECTION_TABLES describes JSON collection tables accessible to the current user.

Related Views

- DBA_JSON_COLLECTION_TABLES describes all JSON collection tables in the database.
- USER_JSON_COLLECTION_TABLES describes JSON collection tables owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Name of the JSON collection table owner
COLLECTION_NAME	VARCHAR2(128)	NOT NULL	Name of the JSON collection table
WITH_ETAG	VARCHAR2(3)		Indicates whether the JSON collection table was created with the ETAG option (YES) or not (NO)

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_JSON_COLLECTION_TABLES"
- "USER_JSON_COLLECTION_TABLES"

3.263 ALL_JSON_COLLECTIONS

ALL_JSON_COLLECTIONS describes JSON collections accessible to the current user.

Related Views

- DBA_JSON_COLLECTIONS describes all JSON collections in the database.
- USER_JSON_COLLECTIONS describes JSON collections owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Name of the JSON collection owner
COLLECTION_NAME	VARCHAR2(128)		Name of the JSON collection
COLLECTION_TYPE	VARCHAR2(12)		Type of the JSON collection: • TABLE • VIEW • DUALITY VIEW

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_JSON_COLLECTIONS"
> - "USER_JSON_COLLECTIONS"

3.264 ALL_JSON_COLUMNS

ALL_JSON_COLUMNS provides information on the JavaScript Object Notation (JSON) columns accessible to the current user.

This view displays information on table and view columns that are guaranteed to return JSON data. These include:

- Columns of data type JSON
- Columns on which a check constraint containing the IS JSON condition is defined, where the IS JSON condition is always enforced. Such check constraints can contain only the IS JSON condition, or they can contain the IS JSON condition as part of a logical AND condition.

  For example, the following check constraints ensure that the IS JSON condition is always enforced and will therefore cause mycol to appear in the ALL_JSON_COLUMNS view:

```
mycol IS JSON
mycol IS JSON AND LENGTH(mycol) > 100
```

However, the following check constraint does not ensure that the `IS JSON` condition is enforced, because it is part of a logical `OR` condition, and will therefore cause `mycol` to be omitted from the `ALL_JSON_COLUMNS` view:

```
mycol IS JSON OR LENGTH(mycol) > 100
```

- View columns that are defined as the return value of a SQL function that returns JSON data. Such functions include:
  - `TREAT ( expr AS JSON )`
  - `JSON_ARRAY`, `JSON_ARRAYAGG`, `JSON_MERGEPATCH`, `JSON_OBJECT`, `JSON_OBJECTAGG`, `JSON_QUERY`, `JSON_SERIALIZE`, and `JSON_TRANSFORM`

  For example, in the following definition for view `v1`, column `mycol` is defined as the return value of the `JSON_OBJECT` function, which will therefore cause `mycol` to appear in the `ALL_JSON_COLUMNS` view:

```
CREATE TABLE t1 (text varchar2(100));
CREATE VIEW v1 AS SELECT JSON_OBJECT(text) AS mycol FROM t1;
```

Related Views

- `DBA_JSON_COLUMNS` provides information on all JSON columns.
- `USER_JSON_COLUMNS` provides information on the JSON columns for which the user is the owner. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
`OWNER`	`VARCHAR2(128)`		Owner of the table with the JSON column
`TABLE_NAME`	`VARCHAR2(128)`		Name of the table with the JSON column
`OBJECT_TYPE`	`VARCHAR2(5)`		Object type: • `TABLE` • `VIEW`
`COLUMN_NAME`	`VARCHAR2(128)`		Name of the JSON column
`FORMAT`	`VARCHAR2(9)`		Format of the JSON data
`DATA_TYPE`	`VARCHAR2(13)`		Data type of the JSON column

See Also:

- "DBA_JSON_COLUMNS"
- "USER_JSON_COLUMNS"
- *Oracle Database JSON Developer's Guide* for more information about using JSON with Oracle Database

3.265 ALL_JSON_DATAGUIDE_FIELDS

ALL_JSON_DATAGUIDE_FIELDS extracts the path and type information from the data guides accessible to the current user, which are the data guides returned to the user by the ALL_JSON_DATAGUIDE view.

Related Views

- DBA_JSON_DATAGUIDE_FIELDS extracts the path and type information from all the data guides in the database, which are the data guides returned by the DBA_JSON_DATAGUIDE view.
- USER_JSON_DATAGUIDE_FIELDS extracts the path and type information from all the data guides in the current user's schema, which are the data guides returned to the user by the USER_JSON_DATAGUIDE view. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table containing the JSON column
TABLE_NAME	VARCHAR2(128)		Name of the table containing the JSON column
COLUMN_NAME	VARCHAR2(128)		Name of the JSON column that has data guide enabled
PATH	VARCHAR2(4000)		Path to the JSON field in the data guide
TYPE	VARCHAR2(40)		Type of the JSON field in the data guide
LENGTH	NUMBER		Maximum length of the JSON field value, in bytes

See Also:

- "DBA_JSON_DATAGUIDE_FIELDS"
- "USER_JSON_DATAGUIDE_FIELDS"

3.266 ALL_JSON_DATAGUIDES

ALL_JSON_DATAGUIDES provides information on the JavaScript Object Notation (JSON) columns accessible to the current user that have data guide enabled.

Related Views

- DBA_JSON_DATAGUIDES provides information on all JavaScript Object Notation (JSON) columns in the database that have data guide enabled.
- USER_JSON_DATAGUIDES provides information on the JavaScript Object Notation (JSON) columns owned by the current user that have data guide enabled. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table containing the JSON column

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table containing the JSON column
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the JSON column that has data guide enabled
DATAGUIDE	CLOB		The data guide of the JSON column in flat format

See Also:

- "DBA_JSON_DATAGUIDES"
- "USER_JSON_DATAGUIDES"

3.267 ALL_JSON_DOMAIN_SCHEMA_COLUMNS

ALL_JSON_DOMAIN_SCHEMA_COLUMNS describes JSON schema constraints on columns of data use case domains accessible to the current user.

Related Views

- DBA_JSON_DOMAIN_SCHEMA_COLUMNS describes JSON schema constraints on columns of all data use case domains in the database.
- USER_JSON_DOMAIN_SCHEMA_COLUMNS describes JSON schema constraints on columns of data use case domains owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the data use case domain containing the column on which the JSON schema constraint is defined
DOMAIN_NAME	VARCHAR2(128)	NOT NULL	Name of the data use case domain containing the column on which the JSON schema constraint is defined
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the data use case domain column on which the JSON schema constraint is defined
CONSTRAINT_NAME	VARCHAR2(128)	NOT NULL	Name of the JSON schema constraint
JSON_SCHEMA	JSON		JSON schema constraint definition
CAST_MODE	BOOLEAN		Indicates whether the JSON schema validator is operating in cast mode (TRUE) or not (FALSE)

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_JSON_DOMAIN_SCHEMA_COLUMNS"
- "USER_JSON_DOMAIN_SCHEMA_COLUMNS"

3.268 ALL_JSON_DUALITY_VIEW_LINKS

`ALL_JSON_DUALITY_VIEW_LINKS` describes the links associated with the JSON-relational duality views accessible to the current user.

Related Views

- `DBA_JSON_DUALITY_VIEW_LINKS` describes the links associated with all JSON-relational duality views in the database.
- `USER_JSON_DUALITY_VIEW_LINKS` describes the links associated with the JSON-relational duality views owned by the current user. This view does not display the `VIEW_OWNER` column.

Column	Datatype	NULL	Description
`VIEW_OWNER`	`VARCHAR2(128)`		Owner of the duality view
`VIEW_NAME`	`VARCHAR2(128)`		Name of the duality view
`PARENT_TABLE_OWNER`	`VARCHAR2(128)`		Owner of the parent table in the link
`PARENT_TABLE_NAME`	`VARCHAR2(128)`		Name of the parent table in the link
`CHILD_TABLE_OWNER`	`VARCHAR2(128)`		Owner of the child table in the link
`CHILD_TABLE_NAME`	`VARCHAR2(128)`		Name of the child table in the link
`FROM_COLUMN`	`VARCHAR2(128)`		Name of the column on the `FROM` side of the link
`TO_COLUMN`	`VARCHAR2(128)`		Name of the column on the `TO` side of the link
`JOIN_TYPE`	`VARCHAR2(16)`		Join type for the link: • `NESTED` - Primary key to foreign key • `OUTER` - Foreign key to primary key • `INNER` - This value is currently not used
`KEY_NAME`	`VARCHAR2(128)`		Name of the JSON key associated with the link

Note:

This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_JSON_DUALITY_VIEW_LINKS"
> - "USER_JSON_DUALITY_VIEW_LINKS"

3.269 ALL_JSON_DUALITY_VIEW_TAB_COLS

ALL_JSON_DUALITY_VIEW_TAB_COLS describes the table columns associated with the JSON-relational duality views accessible to the current user.

Related Views

- DBA_JSON_DUALITY_VIEW_TAB_COLS describes the table columns associated with all JSON-relational duality views in the database.
- USER_JSON_DUALITY_VIEW_TAB_COLS describes the table columns associated with the JSON-relational duality views owned by the current user. This view does not display the VIEW_OWNER column.

Column	Datatype	NULL	Description
VIEW_OWNER	VARCHAR2(128)		Owner of the duality view
VIEW_NAME	VARCHAR2(128)		Name of the duality view
TABLE_OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table
ROOT_TABLE	BOOLEAN		Indicates whether the table is the root (topmost) table (TRUE) or not (FALSE)
TABLE_NUMBER	NUMBER		Number value that identifies this table in the duality view
COLUMN_NAME	VARCHAR2(128)		Name of the column
DATA_TYPE	VARCHAR2(128)		Data type of the column
LENGTH	NUMBER		For character data types, the maximum length of the column (in characters)
JSON_KEY_NAME	NVARCHAR2(128)		JSON key name corresponding to the column
ALLOW_INSERT	BOOLEAN		Indicates whether rows can be inserted into the table using the duality view (TRUE) or not (FALSE)
ALLOW_UPDATE	BOOLEAN		Indicates whether the column can be updated using the duality view (TRUE) or not (FALSE)
ALLOW_DELETE	BOOLEAN		Indicates whether rows can be deleted from the table using the duality view (TRUE) or not (FALSE)
READ_ONLY	BOOLEAN		Indicates whether changes to the column are prohibited (TRUE) or not (FALSE)
IS_FLEX_COL	BOOLEAN		Indicates whether the column is a flex column (TRUE) or not (FALSE)
IS_GENERATED	BOOLEAN		Indicates whether the value associated with JSON_KEY_NAME is a generated (TRUE) or not (FALSE)

Column	Datatype	NULL	Description
IS_HIDDEN	BOOLEAN		Indicates whether JSON_KEY_NAME is hidden in the document (TRUE) or not (FALSE)
PRIMARY_KEY_POS	NUMBER		If the column is part of a primary key, its position in the primary key specification; otherwise, null
ETAG_POS	NUMBER		If the column is part of an ETAG, its position in the ETAG specification; otherwise, null
ORDER_BY_POS	NUMBER		If the column is part of the ORDER BY clause of the JSON_ARRAYAGG function, then its position in the ORDER BY clause; otherwise, null

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_JSON_DUALITY_VIEW_TAB_COLS"
- "USER_JSON_DUALITY_VIEW_TAB_COLS"

3.270 ALL_JSON_DUALITY_VIEW_TABS

ALL_JSON_DUALITY_VIEW_TABS describes the tables associated with the JSON-relational duality views accessible to the current user.

Related Views

- DBA_JSON_DUALITY_VIEW_TABS describes the tables associated with all JSON-relational duality views in the database.
- USER_JSON_DUALITY_VIEW_TABS describes the tables associated with the JSON-relational duality views owned by the current user. This view does not display the VIEW_OWNER column.

Column	Datatype	NULL	Description
VIEW_OWNER	VARCHAR2(128)		Owner of the duality view
VIEW_NAME	VARCHAR2(128)		Name of the duality view
TABLE_OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table
WHERE_CLAUSE	NVARCHAR2(128)		SQL expression in the WHERE clause of the duality view query that accesses the table If the query does not contain a WHERE clause, then null.

Column	Datatype	NULL	Description
ALLOW_INSERT	BOOLEAN		Indicates whether rows can be inserted into the table using the duality view (TRUE) or not (FALSE)
ALLOW_UPDATE	BOOLEAN		Indicates whether the column can be updated using the duality view (TRUE) or not (FALSE)
ALLOW_DELETE	BOOLEAN		Indicates whether rows can be deleted from the table using the duality view (TRUE) or not (FALSE)
READ_ONLY	BOOLEAN		Indicates whether the table is read-only in the duality view, that is, no rows can be modified, inserted, or deleted (TRUE) or not (FALSE)
HAS_FLEX_COL	BOOLEAN		Indicates whether the table contains a flex column (TRUE) or not (FALSE)
ROOT_TABLE	BOOLEAN		Indicates whether the table is the root (topmost) table (TRUE) or not (FALSE)
TABLE_NUMBER	NUMBER		Number value that identifies this table in the duality view
PARENT_TABLE_NUMBER	NUMBER		Number value that points to the parent table in the hierarchy
RELATIONSHIP	VARCHAR2(10)		Relationship between the table (that is, the child table) and the parent table: • NESTED - The child table is nested as a JSON array under the parent table • REFERENCED - The child table is the target of an outer join • SINGLETON - The child table is the target of an inner join

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_JSON_DUALITY_VIEW_TABS"
- "USER_JSON_DUALITY_VIEW_TABS"

3.271 ALL_JSON_DUALITY_VIEWS

ALL_JSON_DUALITY_VIEWS describes the JSON-relational duality views accessible to the current user.

Related Views

- DBA_JSON_DUALITY_VIEWS describes all JSON-relational duality views in the database.
- USER_JSON_DUALITY_VIEWS describes the JSON-relational duality views owned by the current user. This view does not display the VIEW_OWNER column.

Column	Datatype	NULL	Description
VIEW_OWNER	VARCHAR2(128)		Owner of the duality view
VIEW_NAME	VARCHAR2(128)		Name of the duality view
JSON_COLUMN_NAME	CHAR(4)		Name of the column containing the JSON data
ROOT_TABLE_NAME	VARCHAR2(128)		Name of the root table
ROOT_TABLE_OWNER	VARCHAR2(128)		Owner of the root table
ALLOW_INSERT	BOOLEAN		Indicates whether inserts of top level objects or sub-objects into the duality view are allowed (TRUE) or not (FALSE)
ALLOW_UPDATE	BOOLEAN		Indicates whether updates to top level objects or sub-objects in the duality view are allowed (TRUE) or not (FALSE)
ALLOW_DELETE	BOOLEAN		Indicates whether deletes of top level objects or sub-objects from the duality view are allowed (TRUE) or not (FALSE)
READ_ONLY	BOOLEAN		Indicates whether the duality view is read-only, that is, no objects or sub-objects can be modified, inserted, or deleted (TRUE) or not (FALSE)
JSON_SCHEMA	JSON		JSON schema description of the JSON data
STATUS	VARCHAR2(7)		Status of the duality view (VALID or INVALID)

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_JSON_DUALITY_VIEWS"
- "USER_JSON_DUALITY_VIEWS"

3.272 ALL_JSON_INDEXES

ALL_JSON_INDEXES describes indexes on JSON data that are accessible to the current user.

Related Views

- DBA_JSON_INDEXES describes all indexes on JSON data in the database.

- USER_JSON_INDEXES describes indexes on JSON data that are owned by the current user. This view does not display the INDEX_OWNER column.

Column	Datatype	NULL	Description
INDEX_OWNER	VARCHAR2(128)	NOT NULL	Owner of the index
INDEX_NAME	VARCHAR2(128)	NOT NULL	Name of the index
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table on which the index is defined
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table on which the index is defined
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the JSON column on which the index is defined
COLUMN_DATATYPE	VARCHAR2(13)		Data type of the JSON column on which the index is defined
SEARCH_INDEX	BOOLEAN		Indicates whether the index is a search index (TRUE) or not (FALSE)
FUNCTIONAL_INDEX	BOOLEAN		Indicates whether the index is a function-based index (TRUE) or not (FALSE)
COMPOSITE_INDEX	BOOLEAN		Indicates whether the index is a composite index (TRUE) or not (FALSE)
BITMAP_INDEX	BOOLEAN		Indicates whether the index is a bitmap index (TRUE) or not (FALSE)
MULTIVALUE_INDEX	BOOLEAN		Indicates whether the index is a multivalue index (TRUE) or not (FALSE)
INDEX_EXPRESSION	VARCHAR2(4000)		SQL text of the index expression

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_JSON_INDEXES"
- "USER_JSON_INDEXES"

3.273 ALL_JSON_SCHEMA_COLUMNS

ALL_JSON_SCHEMA_COLUMNS describes JSON schema constraints on columns in tables accessible to the current user.

Related Views

- DBA_JSON_SCHEMA_COLUMNS describes JSON schema constraints on columns in all tables in the database.
- USER_JSON_SCHEMA_COLUMNS describes JSON schema constraints on columns in tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table containing the column on which the JSON schema constraint is defined
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table containing the column on which the JSON schema constraint is defined
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column on which the JSON schema constraint is defined
CONSTRAINT_NAME	VARCHAR2(128)	NOT NULL	Name of the JSON schema constraint
JSON_SCHEMA	JSON		JSON schema constraint definition
CAST_MODE	BOOLEAN		Indicates whether the JSON schema validator is operating in cast mode (TRUE) or not (FALSE)

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_JSON_SCHEMA_COLUMNS"
- "USER_JSON_SCHEMA_COLUMNS"

3.274 ALL_LIBRARIES

ALL_LIBRARIES describes the libraries accessible to the current user.

Related Views

- DBA_LIBRARIES describes all libraries in the database.
- USER_LIBRARIES describes the libraries owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the library
LIBRARY_NAME	VARCHAR2(128)	NOT NULL	Library name
FILE_SPEC	VARCHAR2(2000)		Operating system file specification associated with the library
DYNAMIC	VARCHAR2(1)		Indicates whether the library is dynamically loadable (Y) or not (N)
STATUS	VARCHAR2(7)		Status of the library: • N/A • VALID • INVALID

Column	Datatype	NULL	Description
AGENT	VARCHAR2(128)		Agent of the library
LEAF_FILENAME	VARCHAR2(2000)		Leaf filename of the library
ORIGIN_CON_ID	VARCHAR2(256)		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)

See Also:

- "DBA_LIBRARIES"
- "USER_LIBRARIES"

3.275 ALL_LOB_PARTITIONS

ALL_LOB_PARTITIONS displays the LOB partitions in the tables accessible to the current user.

Related Views

- DBA_LOB_PARTITIONS displays all LOB partitions in the database.
- USER_LOB_PARTITIONS displays the LOB partitions owned by the current user. This view does not display the TABLE_OWNER column.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table
COLUMN_NAME	VARCHAR2(4000)		Name of the LOB column
LOB_NAME	VARCHAR2(128)		Name of the partitioned LOB item
PARTITION_NAME	VARCHAR2(128)		Name of the table partition
LOB_PARTITION_NAME	VARCHAR2(128)		Name of the LOB data partition
LOB_INDPART_NAME	VARCHAR2(128)		Name of the corresponding LOB index partition
PARTITION_POSITION	NUMBER		Position of the LOB data partition within the LOB item
COMPOSITE	VARCHAR2(3)		Indicates whether the partition is composite (YES) or not (NO)
CHUNK	NUMBER		Value of the CHUNK attribute of the LOB data partition
PCTVERSION	NUMBER		Value of the PCTVERSION attribute of the LOB data partition

Column	Datatype	NULL	Description
CACHE	VARCHAR2(10)		Indicates whether and how the LOB data is to be cached in the buffer cache: • YES - LOB data is placed in the buffer cache • NO - LOB data either is not brought into the buffer cache or is brought into the buffer cache and placed at the least recently used end of the LRU list • CACHEREADS - LOB data is brought into the buffer cache only during read operations but not during write operations
IN_ROW	VARCHAR2(3)		Indicates whether the STORAGE IN ROW attribute is enabled for the LOB data partition (YES) or not (NO)
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace containing the LOB data partition
INITIAL_EXTENT	VARCHAR2(40)		Size (in bytes) of the initial extent of the LOB data partition, or DEFAULT
NEXT_EXTENT	VARCHAR2(40)		Size (in bytes) of secondary extents of the LOB data partition, or DEFAULT
MIN_EXTENTS	VARCHAR2(40)		Minimum number of extents allowed in the segment of the LOB data partition, or DEFAULT
MAX_EXTENTS	VARCHAR2(40)		Maximum number of extents allowed in the segment of the LOB data partition, or DEFAULT
MAX_SIZE	VARCHAR2(40)		Maximum number of blocks allowed in the segment of the LOB data partition, or DEFAULT
RETENTION	VARCHAR2(7)		Retention option. Possible values for a SecureFiles segment: • NONE • AUTO • MIN • MAX • DEFAULT • INVALID Possible values for a BasicFiles segment: • YES • NO
MINRETENTION	VARCHAR2(40)		Minimum retention duration for a SecureFiles segment, or DEFAULT
PCT_INCREASE	VARCHAR2(40)		Percentage increase in extent size for the LOB data partition, or DEFAULT
FREELISTS	VARCHAR2(40)		Number of process freelists allocated in the segment of the LOB data partition, or DEFAULT
FREELIST_GROUPS	VARCHAR2(40)		Number of freelist groups allocated in the segment of the LOB data partition, or DEFAULT

Column	Datatype	NULL	Description
LOGGING	VARCHAR2(7)		Indicates whether or not changes to the LOB are logged: • NONE - Not specified **See Also:** the *_LOB_SUBPARTITIONS view • YES • NO
BUFFER_POOL	VARCHAR2(7)		Buffer pool for the LOB partition blocks: • DEFAULT • KEEP • RECYCLE • NULL
FLASH_CACHE	VARCHAR2(7)		Database Smart Flash Cache hint to be used for partition blocks: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2(7)		Cell flash cache hint to be used for partition blocks: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
ENCRYPT	VARCHAR2(4)		Indicates whether or not the LOB is encrypted. Possible values for SecureFiles: • YES • NO Possible value for BasicFiles: • NONE - Not applicable
COMPRESSION	VARCHAR2(6)		Level of compression used for this LOB. Possible values for SecureFiles: • LOW • MEDIUM • HIGH • NO - Compression is off Possible value for BasicFiles: • NONE - Not applicable
DEDUPLICATION	VARCHAR2(15)		Kind of deduplication used for this LOB. Possible values for SecureFiles: • LOB - Deduplicate • NO - Keep duplicates Possible value for BasicFiles: • NONE - Not applicable
SECUREFILE	VARCHAR2(3)		Indicates whether the LOB is SecureFiles (YES) or not (NO)

Column	Datatype	NULL	Description
SEGMENT_CREATED	VARCHAR2(3)		Indicates whether the LOB partition segment has been created (YES) or not (NO); N/A indicates that this LOB is subpartitioned and no segment exists at the partition level
MAX_INLINE	NUMBER		Size of inline LOB storage (in bytes) • For inline LOBs (IN_ROW = YES), this column displays the size of inline LOB storage (in bytes). • For out-of-inline LOBs (IN_ROW = NO), the value of this column is 0. • For LOBs in subpartitioned tables, the value of this column is null. Instead, refer to the MAX_INLINE column in the *_LOB_SUBPARTITIONS views.

See Also:

- "DBA_LOB_PARTITIONS"
- "USER_LOB_PARTITIONS"

3.276 ALL_LOB_SUBPARTITIONS

ALL_LOB_SUBPARTITIONS displays partition-level attributes of the LOB data subpartitions accessible to the current user.

Related Views

- DBA_LOB_SUBPARTITIONS displays partition-level attributes of all LOB data subpartitions in the database.
- USER_LOB_SUBPARTITIONS displays the LOB subpartitions owned by the current user. This view does not display the TABLE_OWNER column.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
COLUMN_NAME	VARCHAR2(4000)		Name of the LOB column
LOB_NAME	VARCHAR2(128)	NOT NULL	Name of the partitioned LOB item
LOB_PARTITION_NAME	VARCHAR2(128)		Name of the LOB data partition to which this LOB data subpartition belongs
SUBPARTITION_NAME	VARCHAR2(128)		Name of the table subpartition to which this LOB subpartition corresponds
LOB_SUBPARTITION_NAME	VARCHAR2(128)		Name of the LOB subpartition
LOB_INDSUBPART_NAME	VARCHAR2(128)		Name of the corresponding LOB index subpartition

Column	Datatype	NULL	Description
SUBPARTITION_POSITION	NUMBER		Position of the LOB data partition within the LOB item
CHUNK	NUMBER		Value of the CHUNK attribute of the LOB data partition
PCTVERSION	NUMBER	NOT NULL	Value of the PCTVERSION attribute of the LOB data partition
CACHE	VARCHAR2(10)		Indicates whether and how the LOB data is to be cached in the buffer cache: • YES - LOB data is placed in the buffer cache • NO - LOB data either is not brought into the buffer cache or is brought into the buffer cache and placed at the least recently used end of the LRU list • CACHEREADS - LOB data is brought into the buffer cache only during read operations but not during write operations
IN_ROW	VARCHAR2(3)		Indicates whether the STORAGE IN ROW attribute of the LOB data partition is enabled (YES) or not (NO)
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of the tablespace containing the LOB data partition
INITIAL_EXTENT	VARCHAR2(40)		Size in bytes of the initial extent for the LOB data partition
NEXT_EXTENT	VARCHAR2(40)		Size in bytes of secondary extents for the LOB data partition
MIN_EXTENTS	VARCHAR2(40)	NOT NULL	Minimum number of extents allowed in the segment of the LOB data partition
MAX_EXTENTS	VARCHAR2(40)	NOT NULL	Maximum number of extents allowed in the segment of the LOB data partition
MAX_SIZE	VARCHAR2(40)		Maximum number of blocks allowed in the segment of the LOB data partition
RETENTION	VARCHAR2(7)		Retention option. Possible values for a SecureFiles segment: • NONE • AUTO • MIN • MAX • DEFAULT • INVALID Possible values for a BasicFiles segment: • YES • NO
MINRETENTION	VARCHAR2(40)		Minimum retention duration for a SecureFiles segment
PCT_INCREASE	VARCHAR2(40)		Percentage increase in extent size for the LOB data partition
FREELISTS	VARCHAR2(40)		Number of process freelists allocated in the segment of the LOB data partition

Column	Datatype	NULL	Description
FREELIST_GROUPS	VARCHAR2(40)		Number of freelist groups allocated in the segment of the LOB data partition
LOGGING	VARCHAR2(3)		Indicates whether or not changes to the LOB are logged: • YES • NO
BUFFER_POOL	VARCHAR2(7)		Buffer pool to be used for the LOB data partition blocks: • DEFAULT • KEEP • RECYCLE • NULL
FLASH_CACHE	VARCHAR2(7)		Database Smart Flash Cache hint to be used for subpartition blocks: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2(7)		Cell flash cache hint to be used for subpartition blocks: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
ENCRYPT	VARCHAR2(4)		Indicates whether or not the LOB is encrypted. Possible values for SecureFiles: • YES • NO Possible value for BasicFiles: • NONE - Not applicable
COMPRESSION	VARCHAR2(6)		Level of compression used for this LOB. Possible values for SecureFiles: • LOW • MEDIUM • HIGH • NO - Compression is off Possible value for BasicFiles: • NONE - Not applicable
DEDUPLICATION	VARCHAR2(15)		Kind of deduplication used for this LOB. Possible values for SecureFiles: • LOB - Deduplicate • NO - Keep duplicates Possible value for BasicFiles: • NONE - Not applicable
SECUREFILE	VARCHAR2(3)		Indicates whether the LOB is SecureFiles (YES) or not (NO)

Column	Datatype	NULL	Description
SEGMENT_CREATED	VARCHAR2(3)		Indicates whether the LOB subpartition segment has been created (YES) or not (NO); N/A indicates that this LOB is not subpartitioned
MAX_INLINE	NUMBER	NOT NULL	Size of inline LOB storage (in bytes) • For inline LOBs (IN_ROW = YES), this column displays the size of inline LOB storage (in bytes). • For out-of-inline LOBs (IN_ROW = NO), the value of this column is 0.

See Also:

- "DBA_LOB_SUBPARTITIONS"
- "USER_LOB_SUBPARTITIONS"

3.277 ALL_LOB_TEMPLATES

ALL_LOB_TEMPLATES describes the LOB subpartition templates accessible to the current user.

Related Views

- DBA_LOB_TEMPLATES describes all LOB subpartition templates in the database.
- USER_LOB_TEMPLATES describes the LOB subpartition templates owned by the current user. This view does not display the USER_NAME column.

Column	Datatype	NULL	Description
USER_NAME	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
LOB_COL_NAME	VARCHAR2(4000)		Name of the LOB column
SUBPARTITION_NAME	VARCHAR2(132)	NOT NULL	Name of the subpartition
LOB_SEGMENT_NAME	VARCHAR2(132)	NOT NULL	Name of the LOB segment
TABLESPACE_NAME	VARCHAR2(30)		Tablespace name of the subpartition

See Also:

- "DBA_LOB_TEMPLATES"
- "USER_LOB_TEMPLATES"

3.278 ALL_LOBS

ALL_LOBS displays the large objects (LOBs) contained in tables accessible to the current user. LOBs include binary large objects (BLOBs) and character large objects (CLOBs). Binary files (BFILEs) are stored outside the database, so they are not displayed by this view or the related views.

Related Views

- DBA_LOBS describes all LOBs in the database.
- USER_LOBS describes the LOBs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the object containing the LOB
TABLE_NAME	VARCHAR2(128)		Name of the object containing the LOB
COLUMN_NAME	VARCHAR2(4000)		Name of the LOB column or attribute
SEGMENT_NAME	VARCHAR2(128)		Name of the LOB segment
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace containing the LOB segment
INDEX_NAME	VARCHAR2(128)		Name of the LOB index
CHUNK	NUMBER		Size (in bytes) of the LOB chunk as a unit of allocation or manipulation
PCTVERSION	NUMBER		Maximum percentage of the LOB space used for versioning
RETENTION	NUMBER		Maximum time duration for versioning of the LOB space
FREEPOOLS	NUMBER		Number of freepools for this LOB segment
CACHE	VARCHAR2(10)		Indicates whether and how the LOB data is to be cached in the buffer cache: • YES - LOB data is placed in the buffer cache • NO - LOB data either is not brought into the buffer cache or is brought into the buffer cache and placed at the least recently used end of the LRU list • CACHEREADS - LOB data is brought into the buffer cache only during read operations but not during write operations
LOGGING	VARCHAR2(7)		Indicates whether or not changes to the LOB are logged: • NONE - Not specified **See Also:** the *_LOB_SUBPARTITIONS view • YES • NO

Column	Datatype	NULL	Description
ENCRYPT	VARCHAR2(4)		Indicates whether or not the LOB is encrypted. Possible values for SecureFiles: • YES • NO Possible value for BasicFiles: • NONE - Not applicable
COMPRESSION	VARCHAR2(6)		Level of compression used for this LOB. Possible values for SecureFiles: • LOW • MEDIUM • HIGH • NO - Compression is off Possible value for BasicFiles: • NONE - Not applicable
DEDUPLICATION	VARCHAR2(15)		Kind of deduplication used for this LOB. Possible values for SecureFiles: • LOB - Deduplicate • NO - Keep duplicates Possible value for BasicFiles: • NONE - Not applicable
IN_ROW	VARCHAR2(3)		Indicates whether some LOBs are stored inline with the base row (YES) or not (NO). For partitioned objects, refer to the *_LOB_PARTITIONS and *_PART_LOBS views.
FORMAT	VARCHAR2(15)		Indicates whether the LOB storage format depends on the endianness of the platform: • NOT APPLICABLE • ENDIAN SPECIFIC • ENDIAN NEUTRAL
PARTITIONED	VARCHAR2(3)		Indicates whether the LOB column is in a partitioned table (YES) or not (NO)
SECUREFILE	VARCHAR2(3)		Indicates whether the LOB is SecureFiles (YES) or not (NO)
SEGMENT_CREATED	VARCHAR2(3)		Indicates whether the LOB segment has been created (YES) or not (NO)
RETENTION_TYPE	VARCHAR2(7)		Type of retention used for this LOB. Possible values for SecureFiles: • NONE • AUTO • MIN • MAX • DEFAULT • INVALID Possible values for BasicFiles: • YES • NO

Column	Datatype	NULL	Description
RETENTION_VALUE	NUMBER		Minimum retention time (in seconds). This column is only meaningful for SecureFiles with RETENTION_TYPE set to MIN.
VALUE_BASED	VARCHAR2(3)		Indicates whether the LOB is value based (YES) or not (NO)
MAX_INLINE	NUMBER		Size of inline LOB storage (in bytes) • For inline LOBs in nonpartitioned tables (IN_ROW = YES and PARTITIONED = NO), this column displays the size of inline LOB storage (in bytes). • For out-of-inline LOBs in nonpartitioned tables (IN_ROW = NO and PARTITIONED = NO), the value of this column is 0. • For LOBs in partitioned tables (PARTITIONED = YES), the value of this column is null. Instead, refer to the MAX_INLINE column in the *_PART_LOBS, *_LOB_PARTITIONS, and *_LOB_SUBPARTITIONS views.

See Also:

- "DBA_LOBS"
- "USER_LOBS"

3.279 ALL_LOG_GROUP_COLUMNS

ALL_LOG_GROUP_COLUMNS describes columns that are accessible to the current user and that are specified in log groups.

Related Views

- DBA_LOG_GROUP_COLUMNS describes all columns in the database that are specified in log groups.
- USER_LOG_GROUP_COLUMNS describes columns that are owned by the current user and that are specified in log groups.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the log group definition
LOG_GROUP_NAME	VARCHAR2(128)	NOT NULL	Name of the log group definition
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table in which the log group is defined
COLUMN_NAME	VARCHAR2(4000)		Name of the column or attribute of the object type column specified in the log group definition
POSITION	NUMBER		Original position of the column or attribute in the definition of the object

Column	Datatype	NULL	Description
LOGGING_PROPERTY	VARCHAR2(6)		Indicates whether the column or attribute would be supplementally logged (LOG) or not (NO LOG)

See Also:

- "DBA_LOG_GROUP_COLUMNS"
- "USER_LOG_GROUP_COLUMNS"

3.280 ALL_LOG_GROUPS

ALL_LOG_GROUPS describes the log group definitions on the tables accessible to the current user.

Related Views

- DBA_LOG_GROUPS describes the log group definitions on all tables in the database.
- USER_LOG_GROUPS describes the log group definitions on the tables owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the log group definition
LOG_GROUP_NAME	VARCHAR2(128)	NOT NULL	Name of the log group definition
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table on which the log group is defined
LOG_GROUP_TYPE	VARCHAR2(28)		Type of the log group: • PRIMARY KEY LOGGING • UNIQUE KEY LOGGING • FOREIGN KEY LOGGING • ALL COLUMN LOGGING • USER LOG GROUP
ALWAYS	VARCHAR2(11)		Y indicates the log group is logged any time a row is updated; N indicates the log group is logged any time a member column is updated
GENERATED	VARCHAR2(14)		Indicates whether the name of the supplemental log group was system generated (GENERATED NAME) or not (USER NAME)

See Also:

- "DBA_LOG_GROUPS"
- "USER_LOG_GROUPS"

3.281 ALL_MEASURE_FOLDER_CONTENTS

ALL_MEASURE_FOLDER_CONTENTS describes the contents of the OLAP measure folders accessible to the current user.

Related Views

- DBA_MEASURE_FOLDER_CONTENTS describes the contents of all OLAP measure folders in the database.
- USER_MEASURE_FOLDER_CONTENTS describes the contents of the OLAP measure folders owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the measure folder
MEASURE_FOLDER_NAME	VARCHAR2(128)	NOT NULL	Name of a measure folder
CUBE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the cube
CUBE_NAME	VARCHAR2(128)	NOT NULL	Name of a cube included in the measure folder
MEASURE_NAME	VARCHAR2(128)	NOT NULL	Name of a measure in the cube
ORDER_NUM	NUMBER	NOT NULL	Order number of the measure in the folder

See Also:

- "DBA_MEASURE_FOLDER_CONTENTS"
- "USER_MEASURE_FOLDER_CONTENTS"

3.282 ALL_MEASURE_FOLDER_SUBFOLDERS

ALL_MEASURE_FOLDER_SUBFOLDERS describes the OLAP measure folders contained within the OLAP measure folders accessible to the user.

Related Views

- DBA_MEASURE_FOLDER_SUBFOLDERS describes the OLAP measure folders contained within the database OLAP measure folders.
- USER_MEASURE_FOLDER_SUBFOLDERS describes the OLAP measure folders contained within the OLAP measure folders owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the OLAP measure folder that contains a subfolder
MEASURE_FOLDER_NAME	VARCHAR2(128)	NOT NULL	Name of the OLAP measure folder that contains a subfolder

Column	Datatype	NULL	Description
MEASURE_SUBFOLDER_OWNER	VARCHAR2(128)	NOT NULL	Owner of the OLAP measure folder subfolder
MEASURE_SUBFOLDER_NAME	VARCHAR2(128)	NOT NULL	Name of the owning OLAP measure folder subfolder

See Also:

- "DBA_MEASURE_FOLDER_SUBFOLDERS"
- "USER_MEASURE_FOLDER_SUBFOLDERS"

3.283 ALL_MEASURE_FOLDERS

ALL_MEASURE_FOLDERS describes the OLAP measure folders accessible to the current user.

Related Views

- DBA_MEASURE_FOLDERS describes all OLAP measure folders in the database.
- USER_MEASURE_FOLDERS describes the OLAP measure folders owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the measure folder
MEASURE_FOLDER_NAME	VARCHAR2(128)	NOT NULL	Name of a measure folder
MEASURE_FOLDER_ID	NUMBER	NOT NULL	ID of a measure folder
DESCRIPTION	NVARCHAR2(300)		Description of the measure folder in the session language

See Also:

- "DBA_MEASURE_FOLDERS"
- "USER_MEASURE_FOLDERS"

3.284 ALL_METADATA_PROPERTIES

ALL_METADATA_PROPERTIES describes OLAP metadata properties in the database that are accessible to the current user.

Related Views

- DBA_METADATA_PROPERTIES describes OLAP metadata properties in the database.

- USER_METADATA_PROPERTIES describes OLAP metadata properties in the current user's schema. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the OLAP metadata property
OWNING_OBJECT_ID	NUMBER		Dictionary ID of the OLAP metadata property owner
OWNING_TYPE	VARCHAR2(23)		Owning type of the OLAP metadata property
PROPERTY_ID	NUMBER		Dictionary Id of the OLAP metadata property
PROPERTY_KEY	VARCHAR2(128)		Key of the OLAP metadata property
PROPERTY_VALUE	CLOB		Value of the OLAP metadata property
PROPERTY_ORDER	NUMBER		Order number of the OLAP metadata property

See Also:

- "DBA_METADATA_PROPERTIES"
- "USER_METADATA_PROPERTIES"

3.285 ALL_METHOD_PARAMS

ALL_METHOD_PARAMS describes the method parameters of the object types accessible to the current user.

Related Views

- DBA_METHOD_PARAMS describes the method parameters of all object types in the database.
- USER_METHOD_PARAMS describes the method parameters of the object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the type
TYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the type
METHOD_NAME	VARCHAR2(128)	NOT NULL	Name of the method
METHOD_NO	NUMBER	NOT NULL	For an overloaded method, a number distinguishing this method from others of the same. Do not confuse this number with the object ID.
PARAM_NAME	VARCHAR2(128)	NOT NULL	Name of the parameter
PARAM_NO	NUMBER	NOT NULL	Parameter number (position)
PARAM_MODE	VARCHAR2(6)		Mode of the parameter (IN, OUT, IN OUT)
PARAM_TYPE_MOD	VARCHAR2(7)		Whether this parameter is a REF to another object
PARAM_TYPE_OWNER	VARCHAR2(128)		Owner of the type of the parameter
PARAM_TYPE_NAME	VARCHAR2(128)		Name of the type of the parameter

Column	Datatype	NULL	Description
CHARACTER_SET_NAME	VARCHAR2(44)		Whether the character set or the method is fixed-length character set (CHAR_CS) or fixed-length national character set (NCHAR_CS), or a particular character set specified by the user

See Also:

- "DBA_METHOD_PARAMS"
- "USER_METHOD_PARAMS"

3.286 ALL_METHOD_RESULTS

ALL_METHOD_RESULTS describes the method results of the object types accessible to the current user.

Related Views

- DBA_METHOD_RESULTS describes the method results of all object types in the database.
- USER_METHOD_RESULTS describes the method results of the object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the type
TYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the type
METHOD_NAME	VARCHAR2(128)	NOT NULL	Name of the method
METHOD_NO	NUMBER	NOT NULL	For an overloaded method, a number distinguishing this method from others of the same. Do not confuse this number with the object ID.
RESULT_TYPE_MOD	VARCHAR2(7)		Whether this result is a REF to another object
RESULT_TYPE_OWNER	VARCHAR2(128)		Owner of the type of the result
RESULT_TYPE_NAME	VARCHAR2(128)		Name of the type of the result
CHARACTER_SET_NAME	VARCHAR2(44)		Whether the character set or the method is fixed-length character set (CHAR_CS) or fixed-length national character set (NCHAR_CS), or a particular character set specified by the user

See Also:

- "DBA_METHOD_RESULTS"
- "USER_METHOD_RESULTS"

3.287 ALL_MINING_ALGORITHMS

ALL_MINING_ALGORITHMS describes the settings for a current user.

Column	Datatype	NULL	Description
ALGORITHM_NAME	VARCHAR2(128)		Algorithm used by the model.
MINING_FUNCTION	VARCHAR2(30)		Function of the machine learning model. The machine learning function is specified when the model is built: • CLASSIFICATION • REGRESSION • CLUSTERING • FEATURE_EXTRACTION • ASSOCIATION_RULES • ATTRIBUTE_IMPORTANCE • ANOMALY DETECTION
ALGORITHM_TYPE	VARCHAR2(20)		Algorithm type of the model
ALGORITHM_METADATA	CLOB		Metadata of the algorithm
DESCRIPTION	VARCHAR2(4000)		Description of the algorithm

3.288 ALL_MINING_MODEL_ATTRIBUTES

ALL_MINING_MODEL_ATTRIBUTES describes the attributes of the machine learning models accessible to the current user.

Only the attributes in the model signature are included in this view. The attributes in the model signature correspond to the columns in the training data that were used to build the model.

Machine learning models are schema objects created by Oracle Machine Learning for SQL.

Related Views

- DBA_MINING_MODEL_ATTRIBUTES describes the attributes of all machine learning models in the database.
- USER_MINING_MODEL_ATTRIBUTES describes the attributes of the machine learning models owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the machine learning model

Column	Datatype	NULL	Description
MODEL_NAME	VARCHAR2(128)	NOT NULL	Name of the machine learning model
ATTRIBUTE_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute The target attribute name for ONNX models (mining model with ALGORITHM set to ONNX) is always ORA$ONNXTARGET.
ATTRIBUTE_TYPE	VARCHAR2(11)	–	Logical type of the attribute. The type is identified during the model build or apply process: • NUMERICAL: Numeric data • CATEGORICAL: Character data • TEXT: Unstructured text data • PARTITION: The input signature column is used for the partitioning key • MIXED: The input signature column takes on more than one attribute type. This is due to user-defined embedded transformations that allow an input column to be transformed into multiple independent mining attributes, including mining attributes of different types. • VECTOR: Attribute of type vectors (typically, target attribute of embedding models).
DATA_TYPE	VARCHAR2(106)	–	Data type of the attribute
DATA_LENGTH	NUMBER	–	Length of the data type
DATA_PRECISION	NUMBER	–	Precision of a fixed point number. Precision, which is the total number of significant decimal digits, is represented as *p* in the data type NUMBER(p,s).
DATA_SCALE	NUMBER	–	Scale of a fixed point number. Scale, which is the number of digits from the decimal to the least significant digit, is represented as *s* in the data type NUMBER(p,s).
USAGE_TYPE	VARCHAR2(8)	–	Indicates whether the attribute was used to construct the model (ACTIVE) or not (INACTIVE). Some attributes may be eliminated by transformations or algorithmic processing. The *_MINING_MODEL_ATTRIBUTES view only lists the attributes used by the model, therefore the value of this column is always ACTIVE.
TARGET	VARCHAR2(3)	–	Indicates whether the attribute is the target of a predictive model (YES) or not (NO). The target describes the result that is produced when the model is applied.

Column	Datatype	NULL	Description
ATTRIBUTE_SPEC	VARCHAR2(4000)	–	One or more keywords that identify special treatment for the attribute during model build. Values are: • FORCE_IN: (GLM only) When feature selection is enabled, forces the inclusion of the attribute in the model build. Feature selection is disabled by default. If the model is not using GLM with feature selection enabled, this value is ignored. • NOPREP: When ADP is on, prevents automatic transformation of the attribute. If ADP is OFF, this value is ignored. • TEXT: Causes the attribute to be treated as unstructured text data. The TEXT value supports three subsettings: POLICY_NAME, MAX_FEATURES, TOKEN_TYPE, and MIN_DOCUMENTS. Subsettings are specified as name:value pairs within parentheses. For example: (POLICY_NAME:mypolicy)(MAX_FEATURES:2000)(TOKEN_TYPE:THEME). See *Oracle Machine Learning for SQL API Guide* for details. • NULL: The ATTRIBUTE_SPEC for this attribute is NULL. ATTRIBUTE_SPEC is a parameter to the PL/SQL procedure DBMS_DATA_MINING_TRANSFORM.SET_TRANSFORM. See *Oracle Database PL/SQL Packages and Types Reference* for details.
VECTOR_INFO	VECTOR(<dimension>, <element_type>)	–	Indicates the number of vectors with their data type in an ONNX model. For example, VECTOR(768,float32).

3.289 ALL_MINING_MODEL_PARTITIONS

ALL_MINING_MODEL_PARTITIONS describes all the model partitions accessible to the user.

Related Views

- DBA_MINING_MODEL_PARTITIONS describes all the model partitions accessible to the system.
- USER_MINING_MODEL_PARTITIONS describes the user's own model partitions. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Name of the model owner
MODEL_NAME	VARCHAR2(128)	NOT NULL	Name of the model
PARTITION_NAME	VARCHAR2(128)	–	Name of the model partition

Column	Datatype	NULL	Description
POSITION	NUMBER	–	Column position number for partitioning column. Column position represents the position of the column in a multi-column partitioning key, or 1 for a unary column partitioning key.
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column used for partitioning
COLUMN_VALUE	VARCHAR2(4000)	–	Value of the column for this partition

3.290 ALL_MINING_MODEL_SETTINGS

ALL_MINING_MODEL_SETTINGS describes the settings of the machine learning models accessible to the current user.

Machine learning models are schema objects created by Oracle Machine Learning for SQL.

Related Views

- DBA_MINING_MODEL_SETTINGS describes the settings of all machine learning models in the database.
- USER_MINING_MODEL_SETTINGS describes the settings of the machine learning models owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the machine learning model
MODEL_NAME	VARCHAR2(128)	NOT NULL	Name of the machine learning model
SETTING_NAME	VARCHAR2(30)	NOT NULL	Name of the setting
SETTING_VALUE	VARCHAR2(4000)	–	Value of the setting
SETTING_TYPE	VARCHAR2(7)	–	Indicates whether the default value (DEFAULT) or a user-specified value (INPUT) is used by the model

See Also:

Oracle Database PL/SQL Packages and Types Reference for descriptions of model settings

3.291 ALL_MINING_MODEL_VIEWS

ALL_MINING_MODEL_VIEWS provides a description of all the model views accessible to the user.

Related Views

- DBA_MINING_MODEL_VIEWS provides a description of all the model views in the database.

- USER_MINING_MODEL_VIEWS provides a description of the user's own model views. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the model view
MODEL_NAME	VARCHAR2(128)	NOT NULL	Name of the model to which model views belongs
VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the model view
VIEW_TYPE	VARCHAR2(128)	–	Type of the model view

> **See Also:**
>
> "ALL_MINING_MODEL_VIEWS" in *Oracle Machine Learning for SQL User's Guide*

3.292 ALL_MINING_MODEL_XFORMS

ALL_MINING_MODEL_XFORMS describes the user-specified transformations embedded in all models accessible to the user.

Related Views

- DBA_MINING_MODEL_XFORMS describes the user-specified transformations embedded in all models accessible in the system.
- USER_MINING_MODEL_XFORMS describes the user-specified transformations embedded with the user's own models. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Name of the model owner
MODEL_NAME	VARCHAR2(128)	NOT NULL	Name of the model
ATTRIBUTE_NAME	VARCHAR2(128)		Name of the attribute used in the transformation
ATTRIBUTE_SUBNAME	VARCHAR2(4000)		Subname of the attribute used in the transformation
ATTRIBUTE_SPEC	VARCHAR2(4000)		Attribute specification provided to model training
EXPRESSION	CLOB		Transformation expression provided to model training
REVERSE	VARCHAR2(3)		Indicates whether the specified transformation is a reverse transformation (YES) or a forward expression (NO)

3.293 ALL_MINING_MODELS

ALL_MINING_MODELS describes the machine learning models accessible to the current user.

Mining models are schema objects created by Oracle Machine Learning for SQL.

Related Views

- DBA_MINING_MODELS describes all machine learning models in the database.
- USER_MINING_MODELS describes the machine learning models owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the machine learning model
MODEL_NAME	VARCHAR2(128)	NOT NULL	Name of the machine learning model
MINING_FUNCTION	VARCHAR2(30)		Function of the mining model. The function identifies the class of problems that can be solved by this model. The machine learning function is specified when the model is built: • CLASSIFICATION • REGRESSION • CLUSTERING • EMBEDDING • FEATURE_EXTRACTION • ASSOCIATION_RULES • ATTRIBUTE_IMPORTANCE • TIME_SERIES
ALGORITHM	VARCHAR2(30)		Algorithm used by the model. Each machine learning function has a default algorithm. The default can be overridden with a model setting (see *_MINING_MODEL_SETTINGS): • APRIORI_ASSOCIATION_RULES • CUR_DECOMPOSITION • DECISION_TREE • EXPECTATION_MAXIMIZATION • EXPLICIT_SEMANTIC_ANALYS • EXPONENTIAL_SMOOTHING • EXTENSIBLE_LANG • GENERALIZED_LINEAR_MODEL • KMEANS • MINIMUM_DESCRIPTION_LENGTH • MSET_SPRT • NAIVE_BAYES • NEURAL_NETWORK • NONNEGATIVE_MATRIX_FACTOR • O_CLUSTER • ONNX • RANDOM_FOREST • SUPPORT_VECTOR_MACHINE • SINGULAR_VALUE_DECOMP • XGBOOST
ALGORITHM_TYPE	VARCHAR2(10)		R type algorithm. This column is used in R algorithm registration.
CREATION_DATE	DATE	NOT NULL	Date that the model was created
BUILD_DURATION	NUMBER		Time (in seconds) of the model build process
MODEL_SIZE	NUMBER		Size of the model (in megabytes)

Column	Datatype	NULL	Description
PARTITIONED	VARCHAR2(3)		Indicates whether the model is partitioned or not. Possible values: • YES: The model is partitioned. • NO: The model is not partitioned
BUILD_SOURCE	CLOB		Input data source (provided by the user at build time) on which to build the model This column is populated for models created in Oracle Database 23ai or later. For older version models that were imported into Oracle Database 23ai or later, the value of this column is null.
COMMENTS	VARCHAR2(4000)		Comment applied to the model with a SQL COMMENT statement

3.294 ALL_MLE_ENV_IMPORTS

ALL_MLE_ENV_IMPORTS describes import name to module mappings in the Oracle Database Multilingual Engine (MLE) environments accessible to the current user.

Related Views

- DBA_MLE_ENV_IMPORTS describes import name to module mappings in all MLE environments in the database.
- USER_MLE_ENV_IMPORTS describes import name to module mappings in the MLE environments owned by the current user. This view does not display the ENV_OWNER column.

Column	Datatype	NULL	Description
ENV_OWNER	VARCHAR2(128)	NOT NULL	Owner of the MLE environment
ENV_NAME	VARCHAR2(128)	NOT NULL	Name of the MLE environment
ENV_ID	NUMBER	NOT NULL	Object number of the MLE environment
IMPORT_NAME	VARCHAR2(2048)	NOT NULL	Import name, as specified in the MLE environment's IMPORTS clause It is possible for a single MLE environment to have multiple import names. The import name is a case-sensitive identifier.
MODULE_OWNER	VARCHAR2(128)		Owner of the MLE module
MODULE_NAME	VARCHAR2(128)	NOT NULL	Name of the MLE module

Note:

This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_MLE_ENV_IMPORTS"
> - "USER_MLE_ENV_IMPORTS"

3.295 ALL_MLE_ENVS

ALL_MLE_ENVS describes the Oracle Database Multilingual Engine (MLE) environments accessible to the current user.

Related Views

- DBA_MLE_ENVS describes all MLE environments in the database.
- USER_MLE_ENVS describes the MLE environments owned by the current user. This view does not display the ENV_OWNER column.

Column	Datatype	NULL	Description
ENV_OWNER	VARCHAR2(128)	NOT NULL	Owner of the MLE environment
ENV_NAME	VARCHAR2(128)	NOT NULL	Name of the MLE environment
ENV_ID	NUMBER	NOT NULL	Object number of the MLE environment
LANGUAGE_OPTIONS	VARCHAR2(4000)		MLE environment language options

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_MLE_ENVS"
> - "USER_MLE_ENVS"

3.296 ALL_MLE_MODULES

ALL_MLE_MODULES describes the Oracle Database Multilingual Engine (MLE) modules accessible to the current user.

Related Views

- DBA_MLE_MODULES describes all MLE modules in the database.

- USER_MLE_MODULES describes the MLE modules owned by the current user. This view does not display the MODULE_OWNER column.

Column	Datatype	NULL	Description
MODULE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the MLE module
MODULE_NAME	VARCHAR2(128)	NOT NULL	Name of the MLE module
MODULE_ID	NUMBER	NOT NULL	Object number of the MLE module
MODULE	BLOB	NOT NULL	Contents of the MLE module
LANGUAGE_OWNER	VARCHAR2(128)		Owner of the MLE language of the MLE module
LANGUAGE_NAME	VARCHAR2(128)	NOT NULL	Name of the MLE language of the MLE module
VERSION	VARCHAR2(256)		Version of the MLE module
METADATA	CLOB		Metadata of the MLE module
TYPE	VARCHAR2(7)		Type of the MLE module: • TEXT • UNKNOWN

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_MLE_MODULES"
- "USER_MLE_MODULES"

3.297 ALL_MLE_PROCEDURES

ALL_MLE_PROCEDURES describes the Oracle Database Multilingual Engine (MLE) functions and procedures accessible to the current user.

Related Views

- DBA_MLE_PROCEDURES describes all MLE functions and procedures in the database.
- USER_MLE_PROCEDURES describes the MLE functions and procedures owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the top-level object • For a function or procedure defined in a package or type, this column displays the owner of the package or type. • For a standalone function or procedure, this column displays the owner of the function or procedure.
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the top-level object • For a function or procedure defined in a package or type, this column displays the name of the package or type. • For a standalone function or procedure, this column displays the name of the function or procedure.
PROCEDURE_NAME	VARCHAR2(128)		Name of the function or procedure • For a function or procedure defined in a package or type, this column displays the name of the function or procedure. • For a standalone function or procedure, the value of this column is null.
OBJECT_ID	NUMBER	NOT NULL	Object number of the object displayed in OBJECT_NAME This value corresponds to the OBJECT_ID column in the ALL_OBJECTS and ALL_PROCEDURES views.
SUBPROGRAM_ID	NUMBER	NOT NULL	Unique subprogram identifier
SIGNATURE	CLOB		Signature of the function or procedure (in the target language)
MODULE_OWNER	VARCHAR2(128)		Owner of the top-level MLE module
MODULE_NAME	VARCHAR2(128)		Name of the top-level MLE module
ENV_OWNER	VARCHAR2(128)		Owner of the MLE environment
ENV_NAME	VARCHAR2(128)		Name of the MLE environment
LANG_OWNER	VARCHAR2(128)		MLE language owner
LANG_NAME	VARCHAR2(128)		MLE language name
SRC	CLOB		Text of the source code for the function or procedure

Note:

This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_MLE_PROCEDURES"
> - "USER_MLE_PROCEDURES"

3.298 ALL_MVIEW_AGGREGATES

ALL_MVIEW_AGGREGATES describes the grouping functions (aggregate operations) that appear in the SELECT list of materialized aggregate views accessible to the current user.

Related Views

- DBA_MVIEW_AGGREGATES describes all such grouping functions defined for all materialized views in the database.
- USER_MVIEW_AGGREGATES describes all such grouping functions defined for all materialized views owned by the current user.

> **Note:**
>
> All three views exclude materialized views that reference remote tables or that include references to a nonstatic value such as SYSDATE or USER. These views also exclude materialized views that were created as "snapshots" before Oracle8*i* and that were never altered to enable query rewrite.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
POSITION_IN_SELECT	NUMBER	NOT NULL	Ordinal position of this aggregation within the SELECT list. For the position of nonaggregate elements of the select list, see "ALL_MVIEW_KEYS".
CONTAINER_COLUMN	VARCHAR2(128)	NOT NULL	Name of this column in the container table
AGG_FUNCTION	VARCHAR2(8)		Aggregation function
DISTINCTFLAG	VARCHAR2(1)		Indicates whether this aggregation is distinct (Y) or not (N)
MEASURE	LONG		SQL text of the measure, excluding the aggregation function. Equal to * for COUNT(*).

> **See Also:**
>
> - "DBA_MVIEW_AGGREGATES"
> - "USER_MVIEW_AGGREGATES"

3.299 ALL_MVIEW_ANALYSIS

ALL_MVIEW_ANALYSIS describes the materialized views accessible to the current user. It provides additional information for analysis by applications. Minimal information is displayed for materialized views that do not support query rewrite (such as materialized views with remote master tables or nondeterministic functions).

Related Views

- DBA_MVIEW_ANALYSIS describes all such materialized views in the database.
- USER_MVIEW_ANALYSIS describes all such materialized views owned by the current user.

> **Note:**
>
> All of the information in these views is also displayed in ALL_MVIEWS and its related views. Oracle recommends that you refer to ALL_MVIEWS for this information instead of these views.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
MVIEW_TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the container table (see next column)
CONTAINER_NAME	VARCHAR2(128)		Name of the internal container in which the materialized view data is held. Normally this is the same as MVIEW_NAME. For materialized views created before Oracle8*i*, Oracle Database attaches the 6-byte prefix SNAP$_. If MVIEW_NAME has more than 19 bytes, then Oracle Database truncates the name to 19 bytes and adds a 4-byte sequence number as a suffix to produce a nonambiguous CONTAINER_NAME.
LAST_REFRESH_SCN	NUMBER		System change number (SCN) of the last refresh operation
LAST_REFRESH_DATE	DATE		SYSDATE of the last refresh
REFRESH_METHOD	VARCHAR2(8)		Default refresh method: • FORCE • FAST • COMPLETE • NEVER
SUMMARY	VARCHAR2(1)		Indicates whether this materialized view includes a GROUP BY clause or aggregation (Y) or not (N)
FULLREFRESHTIM	NUMBER		Approximate refresh time, in seconds, for full refresh
INCREFRESHTIM	NUMBER		Approximate refresh time, in seconds, for fast refresh

Column	Datatype	NULL	Description
CONTAINS_VIEWS	VARCHAR2(1)		Indicates whether this materialized view contains a view in its definition (Y) or not (N)
UNUSABLE	VARCHAR2(1)		Indicates whether this materialized view is UNUSABLE (inconsistent data) (Y) or not (N). A materialized view can be UNUSABLE if a system failure occurs during a full refresh.
RESTRICTED_SYNTAX	VARCHAR2(1)		Indicates whether this materialized view had a restriction in its defining query that limits the use of query rewrite (Y) or not (N). More complete information is provided by the REWRITE_CAPABILITY column of the *_MVIEWS view.
INC_REFRESHABLE	VARCHAR2(1)		Indicates whether this materialized view can be fast refreshed (Y) or not (N)
KNOWN_STALE	VARCHAR2(1)		Indicates whether the data contained in the materialized view is known to be inconsistent with the master table data because that has been updated since the last successful refresh (Y) or not (N)
INVALID	VARCHAR2(1)		Indicates whether this materialized view is in an invalid state (inconsistent metadata) (Y) or not (N)
REWRITE_ENABLED	VARCHAR2(1)		Indicates whether this materialized view is currently enabled for query rewrite (Y) or not (N)
QUERY_LEN	NUMBER		Length (in bytes) of the query field
QUERY	LONG		SELECT expression of the materialized view definition
REVISION	NUMBER	NOT NULL	Reserved for internal use

See Also:

- "DBA_MVIEW_ANALYSIS"
- "USER_MVIEW_ANALYSIS"

3.300 ALL_MVIEW_COMMENTS

ALL_MVIEW_COMMENTS displays comments on the materialized views accessible to the current user.

Related Views

- DBA_MVIEW_COMMENTS displays comments on the materialized views in the database.
- USER_MVIEW_COMMENTS displays comments on the materialized views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
COMMENTS	VARCHAR2(4000)		Comment on the materialized view

See Also:

- "DBA_MVIEW_COMMENTS"
- "USER_MVIEW_COMMENTS"

3.301 ALL_MVIEW_DETAIL_LOGICAL_PARTITION

ALL_MVIEW_DETAIL_LOGICAL_PARTITION displays freshness information, with respect to logical partition change tracking (LPCT) detail partitions, for the materialized views accessible to the current user.

Related Views

- DBA_MVIEW_DETAIL_LOGICAL_PARTITION displays freshness information, with respect to LPCT detail partitions, for all materialized views in the database.
- USER_MVIEW_DETAIL_LOGICAL_PARTITION displays freshness information, with respect to LPCT detail partitions, for the materialized views owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
DETAILOBJ_OWNER	VARCHAR2(128)	NOT NULL	Owner of the detail object
DETAILOBJ_NAME	VARCHAR2(128)	NOT NULL	Name of the detail object
DETAIL_LOGICAL_PARTITION_NAME	VARCHAR2(128)		Name of the detail object logical partition
DETAIL_LOGICAL_PARTITION_NUMBER	NUMBER	NOT NULL	Unique identifier of the detail object logical partition
FRESHNESS	VARCHAR2(7)		Freshness state of the detail object logical partition. Possible values: • FRESH • STALE • UNKNOWN
LAST_REFRESH_TIME	DATE		Date and time at which the materialized view was last refreshed
DETAIL_LOGICAL_PARTITION_HIBOUND	LONG		High bound value for the detail object logical partition

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_MVIEW_DETAIL_LOGICAL_PARTITION"
> - "USER_MVIEW_DETAIL_LOGICAL_PARTITION"

3.302 ALL_MVIEW_DETAIL_PARTITION

`ALL_MVIEW_DETAIL_PARTITION` displays freshness information, with respect to partition change tracking (PCT) detail partitions, for the materialized views accessible to the current user.

Related Views

- `DBA_MVIEW_DETAIL_PARTITION` displays freshness information, with respect to PCT detail partitions, for all materialized views in the database.
- `USER_MVIEW_DETAIL_PARTITION` displays freshness information, with respect to PCT detail partitions, for the materialized views owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
DETAILOBJ_OWNER	VARCHAR2(128)	NOT NULL	Owner of the detail object
DETAILOBJ_NAME	VARCHAR2(128)	NOT NULL	Name of the detail object
DETAIL_PARTITION_NAME	VARCHAR2(128)		Name of the detail object partition
DETAIL_PARTITION_POSITION	NUMBER		Position of the detail object partition
FRESHNESS	VARCHAR2(7)		Freshness state of the detail object logical partition. Possible values: • FRESH • STALE • UNKNOWN
LAST_REFRESH_TIME	DATE		Date and time at which the materialized view was last refreshed

> **See Also:**
>
> - "DBA_MVIEW_DETAIL_PARTITION"
> - "USER_MVIEW_DETAIL_PARTITION"

3.303 ALL_MVIEW_DETAIL_RELATIONS

ALL_MVIEW_DETAIL_RELATIONS describes the named detail relations that are either specified in the FROM list of the subquery that defines a materialized view accessible to the current user, or that are indirectly referenced through views in that FROM list. Inline views in the materialized view definition are not represented in this view or the related views.

Related Views

- DBA_MVIEW_DETAIL_RELATIONS describes all such detail relations defined for all materialized views in the database.
- USER_MVIEW_DETAIL_RELATIONS describes such detail relations defined for all materialized views owned by the current user.

> **Note:**
>
> All three views exclude materialized views that reference remote tables or that includes references to a nonstatic value such as SYSDATE or USER. These views also exclude materialized views that were created as *snapshots* before Oracle8*i* and that were never altered to enable query rewrite.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
DETAILOBJ_OWNER	VARCHAR2(128)	NOT NULL	Detail object owner
DETAILOBJ_NAME	VARCHAR2(128)	NOT NULL	Detail object name (that is, the name of a table or view)
DETAILOBJ_TYPE	VARCHAR2(9)		Detail object type: • TABLE • VIEW • SNAPSHOT • CONTAINER • UNDEFINED
DETAILOBJ_ALIAS	VARCHAR2(128)		Implicit or explicit alias for detail relation
DETAILOBJ_PCT	VARCHAR2(1)		Indicates whether the detail object PCT is supported (Y) or not (N)
NUM_FRESH_PCT_PARTITIONS	NUMBER		Number of fresh PCT partitions
NUM_STALE_PCT_PARTITIONS	NUMBER		Number of stale PCT partitions

> **See Also:**
>
> - "DBA_MVIEW_DETAIL_RELATIONS"
> - "USER_MVIEW_DETAIL_RELATIONS"

3.304 ALL_MVIEW_DETAIL_SUBPARTITION

ALL_MVIEW_DETAIL_SUBPARTITION displays freshness information, with respect to partition change tracking (PCT) detail subpartitions, for the materialized views accessible to the current user.

Related Views

- DBA_MVIEW_DETAIL_SUBPARTITION displays freshness information, with respect to PCT detail subpartitions, for all materialized views in the database.
- USER_MVIEW_DETAIL_SUBPARTITION displays freshness information, with respect to PCT detail subpartitions, for the materialized views owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
DETAILOBJ_OWNER	VARCHAR2(128)	NOT NULL	Owner of the detail object
DETAILOBJ_NAME	VARCHAR2(128)	NOT NULL	Name of the detail object
DETAIL_PARTITION_NAME	VARCHAR2(128)		Name of the detail object partition
DETAIL_SUBPARTITION_NAME	VARCHAR2(128)		Name of the detail object subpartition
DETAIL_SUBPARTITION_POSITION	NUMBER		Position of the detail object subpartition
FRESHNESS	CHAR(5)		Freshness state of the detail object subpartition (FRESH or STALE)

> **See Also:**
>
> - "DBA_MVIEW_DETAIL_SUBPARTITION"
> - "USER_MVIEW_DETAIL_SUBPARTITION"

3.305 ALL_MVIEW_JOINS

ALL_MVIEW_JOINS describes joins between two columns in the WHERE clause of the subquery that defines a materialized view accessible to the current user.

Related Views

- DBA_MVIEW_JOINS describes all such joins for all materialized views in the database.

- USER_MVIEW_JOINS describes such joins for all materialized views owned by the current user.

> **Note:**
>
> All three views exclude materialized views that reference remote tables or that includes references to a nonstatic value such as SYSDATE or USER. These views also exclude materialized views that were created as "snapshots" before Oracle8*i* and that were never altered to enable query rewrite.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2(128)	NOT NULL	Materialized view name
DETAILOBJ1_OWNER	VARCHAR2(128)	NOT NULL	Owner of the first object in the join[1]
DETAILOBJ1_RELATION	VARCHAR2(128)	NOT NULL	Name of the first object in the join[1]
DETAILOBJ1_COLUMN	VARCHAR2(128)	NOT NULL	Join column of the first object in the join[1]
OPERATOR	CHAR(1)		Join operator[1]
OPERATOR_TYPE	VARCHAR2(1)		Indicates whether the join is an inner join (I) or the DETAILOBJ1 table is the left side of an outer join (L)[1]
DETAILOBJ2_OWNER	VARCHAR2(128)	NOT NULL	Owner of the second object in the join[1]
DETAILOBJ2_RELATION	VARCHAR2(128)	NOT NULL	Name of the second object in the join[1]
DETAILOBJ2_COLUMN	VARCHAR2(128)	NOT NULL	Join column of the second object in the join[1]

1 These rows relate only to materialized join views and materialized aggregate views. They describe the two detail objects of a materialized view join.

> **See Also:**
>
> - "DBA_MVIEW_JOINS"
> - "USER_MVIEW_JOINS"

3.306 ALL_MVIEW_KEYS

ALL_MVIEW_KEYS describes the columns or expressions in the SELECT list upon which materialized views accessible to the current user are based.

Related Views

- DBA_MVIEW_KEYS describes such columns and expressions for all materialized views in the database.
- USER_MVIEW_KEYS describes such columns and expressions for all materialized views owned by the current user.

> **Note:**
>
> All three views exclude materialized views that reference remote tables or that includes references to a nonstatic value such as SYSDATE or USER. These views also exclude materialized views that were created as *snapshots* before Oracle8*i* and that were never altered to enable query rewrite.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2(128)	NOT NULL	Materialized view name
POSITION_IN_SELECT	NUMBER	NOT NULL	Ordinal position of this key within the SELECT list
CONTAINER_COLUMN	VARCHAR2(128)	NOT NULL	Name of the column in the container table
DETAILOBJ_OWNER	VARCHAR2(128)	NOT NULL	Detail object owner
DETAILOBJ_NAME	VARCHAR2(128)	NOT NULL	Detail object name (for example, the name of a table or view)
DETAILOBJ_ALIAS	VARCHAR2(128)		Implicit or explicit alias for detail relation
DETAILOBJ_TYPE	VARCHAR2(5)		Detail object type: • TABLE • VIEW
DETAILOBJ_COLUMN	VARCHAR2(128)	NOT NULL	Name of the detail relation column

> **See Also:**
>
> - "DBA_MVIEW_KEYS"
> - "USER_MVIEW_KEYS"

3.307 ALL_MVIEW_LOGS

ALL_MVIEW_LOGS describes all materialized view logs accessible to the current user.

Related Views

- DBA_MVIEW_LOGS describes all materialized view logs in the database.
- USER_MVIEW_LOGS describes all materialized view logs owned by the current user.

Column	Datatype	NULL	Description
LOG_OWNER	VARCHAR2(128)		Owner of the materialized view log
MASTER	VARCHAR2(128)		Name of the master table or master materialized view whose changes are logged
LOG_TABLE	VARCHAR2(128)		Name of the table where the changes to the master table or master materialized view are logged

Column	Datatype	NULL	Description
LOG_TRIGGER	VARCHAR2(128)		Obsolete with Oracle8*i* and later. Set to NULL. Formerly, this parameter was an after-row trigger on the master which inserted rows into the log.
ROWIDS	VARCHAR2(3)		Indicates whether rowid information is recorded (YES) or not (NO)
PRIMARY_KEY	VARCHAR2(3)		Indicates whether primary key information is recorded (YES) or not (NO)
OBJECT_ID	VARCHAR2(3)		Indicates whether object identifier information in an object table is recorded (YES) or not (NO)
FILTER_COLUMNS	VARCHAR2(3)		Indicates whether filter column information is recorded (YES) or not (NO)
SEQUENCE	VARCHAR2(3)		Indicates whether the sequence value, which provides additional ordering information, is recorded (YES) or not (NO)
INCLUDE_NEW_VALUES	VARCHAR2(3)		Indicates whether both old and new values are recorded (YES) or old values are recorded but new values are not recorded (NO)
PURGE_ASYNCHRONOUS	VARCHAR2(3)		Indicates whether the materialized view log is purged asynchronously (YES) or not (NO)
PURGE_DEFERRED	VARCHAR2(3)		Indicates whether the materialized view log is purged in a deferred manner (YES) or not (NO)
PURGE_START	DATE		For deferred purge, the purge start date
PURGE_INTERVAL	VARCHAR2(200)		For deferred purge, the purge interval
LAST_PURGE_DATE	DATE		Date of the last purge
LAST_PURGE_STATUS	NUMBER		Status of the last purge (error code or 0 for success)
NUM_ROWS_PURGED	NUMBER		Number of rows purged in the last purge
COMMIT_SCN_BASED	VARCHAR2(3)		Indicates whether the materialized view log is commit SCN-based (YES) or not (NO)
STAGING_LOG	VARCHAR2(3)		Indicates whether the materialized view log is a staging log for synchronous refresh (YES) or not (NO)
AUTO	VARCHAR2(6)		Indicates whether the materialized view log is an automatic materialized view log. Possible values: • YES - It is an automatic materialized view log • NO - It is a user-created materialized view log • HYBRID - It is a hybrid materialized view log. It was initially a user-created materialized view log and was subsequently altered automatically to include one or more additional columns to support an automatic materialized view.

See Also:

- "DBA_MVIEW_LOGS"
- "USER_MVIEW_LOGS"

3.308 ALL_MVIEW_REFRESH_TIMES

ALL_MVIEW_REFRESH_TIMES describes refresh times of the materialized views accessible to the current user.

Related Views

- DBA_MVIEW_REFRESH_TIMES describes refresh times of all materialized views in the database.
- USER_MVIEW_REFRESH_TIMES describes refresh times of the materialized views owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
MASTER_OWNER	VARCHAR2(128)		Owner of the master table
MASTER	VARCHAR2(128)		Name of the master table
LAST_REFRESH	DATE		SYSDATE from the master site at the time of the last refresh

See Also:

- "DBA_MVIEW_REFRESH_TIMES"
- "USER_MVIEW_REFRESH_TIMES"

3.309 ALL_MVIEWS

ALL_MVIEWS describes all materialized views accessible to the current user.

Related Views

- DBA_MVIEWS describes all materialized views in the database.
- USER_MVIEWS describes all materialized views owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Schema in which the materialized view was created

Column	Datatype	NULL	Description
MVIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
CONTAINER_NAME	VARCHAR2(128)	NOT NULL	Name of the container in which the materialized view's data is held. Normally this is the same as MVIEW_NAME. For materialized views created before Oracle8*i*, Oracle Database attaches the 6-byte prefix SNAP$_. If MVIEW_NAME has more than 19 bytes, then Oracle Database truncates the name to 19 bytes and may add a 4-byte sequence number as a suffix to produce a nonambiguous CONTAINER_NAME.
QUERY	LONG		Query that defines the materialized view
QUERY_LEN	NUMBER(38)		Length (in bytes) of the defining query
UPDATABLE	VARCHAR2(1)		Indicates whether the materialized view is updatable (Y) or not (N)
UPDATE_LOG	VARCHAR2(128)		For updatable materialized views, the filename of the update log
MASTER_ROLLBACK_SEG	VARCHAR2(128)		Rollback segment for the master site or the master materialized view site
MASTER_LINK	VARCHAR2(128)		Database link for the master site or the master materialized view site
REWRITE_ENABLED	VARCHAR2(1)		Indicates whether rewrite is enabled (Y) or not (N)
REWRITE_CAPABILITY	VARCHAR2(9)		Indicates whether the materialized view is eligible for rewrite, and if so, what rules must be followed: • NONE - Materialized view cannot be used for rewrite, because rewrite is disallowed or prevented • TEXTMATCH - Defining query of the materialized view contained restrictions on the use of query rewrite • GENERAL - Defining query of the materialized view contained no restrictions on the use of query rewrite, so Oracle Database can apply any rewrite rule that is supported
REFRESH_MODE	VARCHAR2(6)		Refresh mode of the materialized view: • DEMAND - Oracle Database refreshes this materialized view whenever an appropriate refresh procedure is called • COMMIT - Oracle Database refreshes this materialized view when a transaction on one of the materialized view's masters commits • NEVER - Oracle Database never refreshes this materialized view

Column	Datatype	NULL	Description
REFRESH_METHOD	VARCHAR2(8)		Default method used to refresh the materialized view (can be overridden through the API): • COMPLETE - Materialized view is completely refreshed from the masters • FORCE - Oracle Database performs a fast refresh if possible, otherwise a complete refresh • FAST - Oracle Database performs an incremental refresh applying changes that correspond to changes in the masters since the last refresh • NEVER - User specified that Oracle Database should not refresh this materialized view
BUILD_MODE	VARCHAR2(9)		Indicates how the materialized view was populated during creation: • IMMEDIATE - Populated from the masters during creation • DEFERRED - Not populated during creation. Must be explicitly populated later by the user. • PREBUILT - Populated with an existing table during creation. The relationship of the contents of this prebuilt table to the materialized view's masters is unknown to Oracle Database.
FAST_REFRESHABLE	VARCHAR2(18)		Indicates whether the materialized view is eligible for incremental (fast) refresh. Oracle Database calculates this value statically, based on the materialized view definition query: • NO - Materialized view is not fast refreshable, and hence is complex • DML - Fast refresh is supported only for DML operations • DIRLOAD_DML - Fast refresh is supported for both direct loads and DML operations • DIRLOAD_LIMITEDDML - Fast refresh is supported for direct loads and a subset of DML operations
LAST_REFRESH_TYPE	VARCHAR2(8)		Method used for the most recent refresh: • COMPLETE - Most recent refresh was complete • FAST - Most recent refresh was fast (incremental) • NA - Materialized view has not yet been refreshed (for example, if it was created DEFERRED)
LAST_REFRESH_DATE	DATE		Date on which the materialized view was most recently refreshed (blank if not yet populated)
LAST_REFRESH_END_TIME	DATE		End time of the most recent refresh on the materialized view (blank if not yet populated)

Column	Datatype	NULL	Description
STALENESS	VARCHAR2(19)		Relationship between the contents of the materialized view and the contents of the materialized view's masters: • FRESH - Materialized view is a read-consistent view of the current state of its masters • IMPORT - Materialized view is imported from another database (the value of the UNKNOWN_IMPORT column is Y). Therefore, it is unknown whether the materialized view is in a read-consistent view of its masters from any point in time. The STALENESS of this view will turn to FRESH on a complete refresh. • NEEDS_COMPILE - Some object upon which the materialized view depends has changed. An ALTER MATERIALIZED VIEW...COMPILE statement is required to validate this materialized view and compute the staleness of the contents. • STALE - Materialized view is out of date because one or more of its masters has changed. If the materialized view was FRESH before it became STALE, then it is a read-consistent view of a former state of its masters. • UNDEFINED - Materialized view has remote masters. The concept of staleness is not defined for such materialized views. • UNKNOWN - Oracle Database does not know whether the materialized view is in a read-consistent view of its masters from any point in time (this is the case for materialized views created on prebuilt tables) • UNUSABLE - Materialized view is not a read-consistent view of its masters from any point in time
AFTER_FAST_REFRESH	VARCHAR2(19)		Specifies the staleness value that will occur if a fast refresh is applied to this materialized view. Its values are the same as for the STALENESS column, plus the value NA, which is used when fast refresh is not applicable to this materialized view.
UNKNOWN_PREBUILT	VARCHAR2(1)		Indicates whether the materialized view is prebuilt (Y) or not (N)
UNKNOWN_PLSQL_FUNC	VARCHAR2(1)		Indicates whether the materialized view contains PL/SQL functions (Y) or not (N)
UNKNOWN_EXTERNAL_TABLE	VARCHAR2(1)		Indicates whether the materialized view contains external tables (Y) or not (N)
UNKNOWN_CONSIDER_FRESH	VARCHAR2(1)		Indicates whether the materialized view is considered fresh (Y) or not (N)
UNKNOWN_IMPORT	VARCHAR2(1)		Indicates whether the materialized view is imported (Y) or not (N)
UNKNOWN_TRUSTED_FD	VARCHAR2(1)		Indicates whether the materialized view uses trusted constraints for refresh (Y) or not (N)

Column	Datatype	NULL	Description
COMPILE_STATE	VARCHAR2(19)		Validity of the materialized view with respect to the objects upon which it depends: • VALID - Materialized view has been validated without error, and no object upon which it depends has changed since the last validation • NEEDS_COMPILE - Some object upon which the materialized view depends has changed. An ALTER MATERIALIZED VIEW...COMPILE statement is required to validate this materialized view. • ERROR - Materialized view has been validated with one or more errors
USE_NO_INDEX	VARCHAR2(1)		Indicates whether the materialized view was created using the USING NO INDEX clause (Y) or the materialized view was created with the default index (N). The USING NO INDEX clause suppresses the creation of the default index.
STALE_SINCE	DATE		Time from when the materialized view became stale
NUM_PCT_TABLES	NUMBER		Number of PCT detail tables
NUM_FRESH_PCT_REGIONS	NUMBER		Number of fresh PCT partition regions
NUM_STALE_PCT_REGIONS	NUMBER		Number of stale PCT partition regions
SEGMENT_CREATED	VARCHAR2(3)		Indicates whether the materialized view was created using the SEGMENT CREATION DEFERRED clause. The value is YES if the segment for the materialized view is created and NO if it is not.
EVALUATION_EDITION	VARCHAR2(128)		Name of the edition in which editioned objects referenced in an expression column are resolved
UNUSABLE_BEFORE	VARCHAR2(128)		Name of the oldest edition in which the stored results of the materialized view's subquery may be used for query rewrite. In editions before the specified edition, the stored results of the materialized view's data are considered unusable. This value is NULL if no such edition is specified.
UNUSABLE_BEGINNING	VARCHAR2(128)		Name of the oldest edition in which the stored results of the materialized view's subquery may *not* be used for query rewrite. The data is unusable for query rewrite in the specified edition and in any descendants of this edition. This value is NULL if no such edition is specified.
DEFAULT_COLLATION	VARCHAR2(100)		Default collation for the materialized view
ON_QUERY_COMPUTATION	VARCHAR2(1)		Indicates whether the materialized view is a real-time materialized view (Y) or not (N)
AUTO	VARCHAR2(3)		Indicates whether the materialized view is an automatic materialized view (YES) or not (NO)
CONCURRENT_REFRESH_ENABLED	VARCHAR2(1)		Indicates whether concurrent refresh is enabled for the materialized view (Y) or not (N)

> **See Also:**
>
> - "DBA_MVIEWS"
> - "USER_MVIEWS"
> - *Oracle Database Data Warehousing Guide* for more information on materialized views to support data warehousing

3.310 ALL_NESTED_TABLE_COLS

ALL_NESTED_TABLE_COLS describes the columns of the nested tables accessible to the current user. To gather statistics for this view, use the DBMS_STATS package.

Related Views

- DBA_NESTED_TABLE_COLS describes the columns of all nested tables in the database.
- USER_NESTED_TABLE_COLS describes the columns of the nested tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the nested table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the nested table
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Column name
DATA_TYPE	VARCHAR2(128)		Data type of the column
DATA_TYPE_MOD	VARCHAR2(3)		Data type modifier of the column
DATA_TYPE_OWNER	VARCHAR2(128)		Owner of the data type of the column
DATA_LENGTH	NUMBER	NOT NULL	Length of the column (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for NUMBER data type; binary precision for FLOAT data type; NULL for all other data types
DATA_SCALE	NUMBER		Digits to the right of the decimal point in a number
NULLABLE	VARCHAR2(1)		Indicates whether a column allows NULLs. The value is N if there is a NOT NULL constraint on the column or if the column is part of a PRIMARY KEY.
COLUMN_ID	NUMBER		Sequence number of the column as created
DEFAULT_LENGTH	NUMBER		Length of the default value for the column
DATA_DEFAULT	LONG		Default value for the column
DATA_DEFAULT_VC	VARCHAR2(4000)		Default value for the column This column may truncate the default value.
NUM_DISTINCT	NUMBER		Number of distinct values in the column. This column remains for backward compatibility with Oracle7. This information is now in the {TAB|PART}_COL_STATISTICS views.

Column	Datatype	NULL	Description
LOW_VALUE	RAW(1000)		Low value in the column. This column remains for backward compatibility with Oracle7. This information is now in the {TAB|PART}_COL_STATISTICS views.
HIGH_VALUE	RAW(1000)		High value in the column. This column remains for backward compatibility with Oracle7. This information is now in the {TAB|PART}_COL_STATISTICS views.
DENSITY	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT. This column remains for backward compatibility with Oracle7. This information is now in the {TAB|PART}_COL_STATISTICS views.
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in the histogram for the column **Note:** The number of buckets in a histogram is specified in the SIZE parameter of the SQL ANALYZE statement. However, Oracle Database does not create a histogram with more buckets than the number of rows in the sample. Also, if the sample contains any values that are very repetitious, Oracle Database creates the specified number of buckets, but the value indicated by this column may be smaller because of an internal compression algorithm.
LAST_ANALYZED	DATE		Date on which this column was most recently analyzed
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this column
CHARACTER_SET_NAME	VARCHAR2(44)		Name of the character set: • CHAR_CS • NCHAR_CS
CHAR_COL_DECL_LENGTH	NUMBER		Declaration length of the character type column
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics are gathered or incrementally maintained, otherwise it will be NO
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
CHAR_LENGTH	NUMBER		Displays the length of the column in characters. This value only applies to the following data types: • CHAR • VARCHAR2 • NCHAR • NVARCHAR2

Column	Datatype	NULL	Description
CHAR_USED	VARCHAR2(1)		Indicates that the column uses BYTE length semantics (B) or CHAR length semantics (C), or whether the data type is not any of the following (NULL): • CHAR • VARCHAR2 • NCHAR • NVARCHAR2
V80_FMT_IMAGE	VARCHAR2(3)		Indicates whether the column data is in release 8.0 image format (YES) or not (NO)
DATA_UPGRADED	VARCHAR2(3)		Indicates whether the column data has been upgraded to the latest type version format (YES) or not (NO)
HIDDEN_COLUMN	VARCHAR2(3)		Indicates whether the column is a hidden column (YES) or not (NO)
VIRTUAL_COLUMN	VARCHAR2(3)		Indicates whether the column is a virtual column (YES) or not (NO)
SEGMENT_COLUMN_ID	NUMBER		Sequence number of the column in the segment
INTERNAL_COLUMN_ID	NUMBER	NOT NULL	Internal sequence number of the column
HISTOGRAM	VARCHAR2(15)		Indicates existence/type of histogram: • NONE • FREQUENCY • HEIGHT BALANCED
QUALIFIED_COL_NAME	VARCHAR2(4000)		Qualified column name

See Also:

- "DBA_NESTED_TABLE_COLS"
- "USER_NESTED_TABLE_COLS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

3.311 ALL_NESTED_TABLES

ALL_NESTED_TABLES describes the nested tables in tables accessible to the current user.

Related Views

- DBA_NESTED_TABLES describes all nested tables in the database.
- USER_NESTED_TABLES describes nested tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the nested table
TABLE_NAME	VARCHAR2(128)		Name of the nested table
TABLE_TYPE_OWNER	VARCHAR2(128)		Owner of the type of which the nested table was created
TABLE_TYPE_NAME	VARCHAR2(128)		Name of the type of the nested table
PARENT_TABLE_NAME	VARCHAR2(128)		Name of the parent table containing the nested table
PARENT_TABLE_COLUMN	VARCHAR2(4000)		Column name of the parent table that corresponds to the nested table
STORAGE_SPEC	VARCHAR2(30)		Indicates whether storage for the nested table is USER_SPECIFIED or DEFAULT
RETURN_TYPE	VARCHAR2(20)		Return type of the varray column (LOCATOR) or (VALUE)
ELEMENT_SUBSTITUTABLE	VARCHAR2(25)		Indicates whether the nested table element is substitutable (Y) or not (N)

See Also:

- "DBA_NESTED_TABLES"
- "USER_NESTED_TABLES"

3.312 ALL_OBJ_COLATTRS

ALL_OBJ_COLATTRS describes object columns and attributes contained in the tables accessible to the current user.

Related Views

- DBA_OBJ_COLATTRS describes object columns and attributes contained in all tables in the database.
- USER_OBJ_COLATTRS describes object columns and attributes contained in the tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table containing the object column or attribute
COLUMN_NAME	VARCHAR2(4000)		Fully qualified name of the object column or attribute
SUBSTITUTABLE	VARCHAR2(15)		Indicates whether the column is substitutable (Y) or not (N)

> **See Also:**
>
> - "DBA_OBJ_COLATTRS"
> - "USER_OBJ_COLATTRS"

3.313 ALL_OBJECT_TABLES

ALL_OBJECT_TABLES describes the object tables accessible to the current user.

Related Views

- DBA_OBJECT_TABLES describes all object tables in the database.
- USER_OBJECT_TABLES describes the object tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace containing the table; NULL for partitioned, temporary, and index-organized tables
CLUSTER_NAME	VARCHAR2(128)		Name of the cluster, if any, to which the table belongs
IOT_NAME	VARCHAR2(128)		Name of the index-organized table, if any, to which the overflow or mapping table entry belongs. If the IOT_TYPE column is not NULL, then this column contains the base table name.
STATUS	VARCHAR2(8)		If a previous DROP TABLE operation failed, indicates whether the table is unusable (UNUSABLE) or valid (VALID)
PCT_FREE	NUMBER		Minimum percentage of free space in a block; NULL for partitioned tables
PCT_USED	NUMBER		Minimum percentage of used space in a block; NULL for partitioned tables
INI_TRANS	NUMBER		Initial number of transactions; NULL for partitioned tables
MAX_TRANS	NUMBER		Maximum number of transactions; NULL for partitioned tables
INITIAL_EXTENT	NUMBER		Size of the initial extent (in bytes); NULL for partitioned tables
NEXT_EXTENT	NUMBER		Size of secondary extents (in bytes); NULL for partitioned tables
MIN_EXTENTS	NUMBER		Minimum number of extents allowed in the segment; NULL for partitioned tables
MAX_EXTENTS	NUMBER		Maximum number of extents allowed in the segment; NULL for partitioned tables

Column	Datatype	NULL	Description
PCT_INCREASE	NUMBER		Percentage increase in extent size; NULL for partitioned tables
FREELISTS	NUMBER		Number of process freelists allocated to the segment; NULL for partitioned tables
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to the segment; NULL for partitioned tables
LOGGING	VARCHAR2(3)		Indicates whether or not changes to the table are logged: • YES • NO
BACKED_UP	VARCHAR2(1)		Indicates whether the table has been backed up since the last modification (Y) or not (N)
NUM_ROWS	NUMBER		Number of rows in the table
BLOCKS	NUMBER		Number of used blocks in the table
EMPTY_BLOCKS	NUMBER		Number of empty (never used) blocks in the table
AVG_SPACE	NUMBER		Average available free space in the table
CHAIN_CNT	NUMBER		Number of chained rows in the table
AVG_ROW_LEN	NUMBER		Average row length, including row overhead
AVG_SPACE_FREELIST_BLOCKS	NUMBER		Average free space of all blocks on a freelist
NUM_FREELIST_BLOCKS	NUMBER		Number of blocks on the freelist
DEGREE	VARCHAR2(10)		Number of parallel execution processes per instance for scanning the table, or DEFAULT
INSTANCES	VARCHAR2(10)		Number of instances across which the table is to be scanned, or DEFAULT
CACHE	VARCHAR2(5)		Indicates whether the table is to be cached in the buffer cache (Y) or not (N)
TABLE_LOCK	VARCHAR2(8)		Indicates whether table locking is enabled (ENABLED) or disabled (DISABLED)
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this table
LAST_ANALYZED	DATE		Date on which this table was most recently analyzed
PARTITIONED	VARCHAR2(3)		Indicates whether the table is partitioned (YES) or not (NO)
IOT_TYPE	VARCHAR2(12)		If the table is an index-organized table, then IOT_TYPE is IOT, IOT_OVERFLOW, or IOT_MAPPING. If the table is not an index-organized table, then IOT_TYPE is NULL.
OBJECT_ID_TYPE	VARCHAR2(16)		Indicates whether the object ID (OID) is USER-DEFINED or SYSTEM GENERATED
TABLE_TYPE_OWNER	VARCHAR2(128)		Owner of the type of the table
TABLE_TYPE	VARCHAR2(128)		Type of the table
TEMPORARY	VARCHAR2(1)		Indicates whether this is a temporary table (Y) or not (N)

Column	Datatype	NULL	Description
SECONDARY	VARCHAR2(1)		Indicates whether the object table is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y) or not (N)
NESTED	VARCHAR2(3)		Indicates whether the table is a nested table (YES) or not (NO)
BUFFER_POOL	VARCHAR2(7)		Buffer pool to be used for table blocks: • DEFAULT • KEEP • RECYCLE • NULL
FLASH_CACHE	VARCHAR2(7)		Database Smart Flash Cache hint to be used for table blocks: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2(7)		Cell flash cache hint to be used for table blocks: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
ROW_MOVEMENT	VARCHAR2(8)		Indicates whether partitioned row movement is enabled (ENABLED) or disabled (DISABLED)
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics are gathered or incrementally maintained, otherwise it will be NO
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
DURATION	VARCHAR2(15)		Indicates the duration of a temporary table: • SYS$SESSION - Rows are preserved for the duration of the session • SYS$TRANSACTION - Rows are deleted after COMMIT Null - Permanent table
SKIP_CORRUPT	VARCHAR2(8)		Indicates whether Oracle Database ignores blocks marked corrupt during table and index scans (ENABLED) or raises an error (DISABLED). To enable this feature, run the DBMS_REPAIR.SKIP_CORRUPT_BLOCKS procedure.
MONITORING	VARCHAR2(3)		Indicates whether the table has the MONITORING attribute set (YES) or not (NO)
CLUSTER_OWNER	VARCHAR2(128)		Owner of the cluster, if any, to which the table belongs
DEPENDENCIES	VARCHAR2(8)		Indicates whether row-level dependency tracking is enabled (ENABLED) or disabled (DISABLED)
COMPRESSION	VARCHAR2(8)		Indicates whether table compression is enabled (ENABLED) or not (DISABLED); NULL for partitioned tables

Column	Datatype	NULL	Description
COMPRESS_FOR	VARCHAR2(30)		Default compression for what kind of operations: • BASIC • ADVANCED • QUERY LOW • QUERY HIGH • ARCHIVE LOW • ARCHIVE HIGH • NULL The QUERY LOW, QUERY HIGH, ARCHIVE LOW, and ARCHIVE HIGH values are associated with Hybrid Columnar Compression, a feature of the Enterprise Edition of Oracle Database. See *Oracle Database Concepts* for more information.
DROPPED	VARCHAR2(3)		Indicates whether the table has been dropped and is in the recycle bin (YES) or not (NO); NULL for partitioned tables This view does not return the names of tables that have been dropped.
SEGMENT_CREATED	VARCHAR2(3)		Indicates whether the table segment has been created (YES) or not (NO)
INMEMORY	VARCHAR2(8)		Indicates whether the In-Memory Column Store (IM column store) is enabled (ENABLED) or disabled (DISABLED) for this segment
INMEMORY_PRIORITY	VARCHAR2(8)		Indicates the priority for In-Memory Column Store (IM column store) population. Possible values: • LOW • MEDIUM • HIGH • CRITICAL • NONE • NULL This column has a value based on where the segments lie for a table. For example, if the table is partitioned and is enabled for the IM column store, the value is NULL for ALL_TABLES but non-NULL for ALL_TAB_PARTITIONS.
INMEMORY_DISTRIBUTE	VARCHAR2(15)		Indicates how the IM column store is distributed in an Oracle Real Application Clusters (Oracle RAC) environment: • AUTO • BY ROWID RANGE • BY PARTITION • BY SUBPARTITION

Column	Datatype	NULL	Description
INMEMORY_COMPRESSION	VARCHAR2(17)		Indicates the compression level for the IM column store: • NO MEMCOMPRESS • FOR DML • FOR QUERY [LOW | HIGH] • FOR CAPACITY [LOW | HIGH] • AUTO • NULL This column has a value based on where the segments lie for a table. For example, if the table is partitioned and is enabled for the IM column store, the value is NULL for ALL_TABLES but non-NULL for ALL_TAB_PARTITIONS.
INMEMORY_DUPLICATE	VARCHAR2(13)		Indicates the duplicate setting for the IM column store in an Oracle RAC environment: • NO DUPLICATE • DUPLICATE • DUPLICATE ALL
EXTERNAL	VARCHAR2(3)		Indicates whether the table is an external table (YES) or not (NO).
CELLMEMORY[1]	VARCHAR2(24)		The value for columnar compression in the storage cell flash cache. Possible values: • ENABLED: Oracle Exadata Storage will decide automatically whether to cache in columnar form • DISABLED: Oracle Exadata Storage is prevented from caching in columnar form • NO CACHECOMPRESS: Oracle Exadata Storage will cache in HCC format (no recompression) • FOR QUERY: Oracle Exadata Storage will recompress and cache in INMEMORY query high format • FOR CAPACITY: Oracle Exadata Storage will recompress and cache in INMEMORY capacity low format
HYBRID	VARCHAR2(3)		Indicates whether the table is a hybrid partitioned table (YES) or not (NO). A hybrid partitioned table can contain a mixture of partitions stored in segments and partitions stored externally.

Column	Datatype	NULL	Description
INMEMORY_SERVICE	VARCHAR2(12)		Indicates how the IM column store is populated on various instances. The possible values are: • DEFAULT: Data is populated on all instances specified with the PARALLEL_INSTANCE_GROUP initialization parameter. If that parameter is not set, then the data is populated on all instances. This is the default. • NONE: Data is not populated on any instance. • ALL: Data is populated on all instances, regardless of the value of the PARALLEL_INSTANCE_GROUP initialization parameter. • USER_DEFINED: Data is populated only on the instances on which the user-specified service is active. The service name corresponding to this is stored in the INMEMORY_SERVICE_NAME column.
INMEMORY_SERVICE_NAME	VARCHAR2(1000)		Indicates the service name for the service on which the IM column store should be populated. This column has a value only when the corresponding INMEMORY_SERVICE is USER_DEFINED. In all other cases, this column is null.
MEMOPTIMIZE_READ	VARCHAR2(8)		Indicates whether the table is enabled for Fast Key Based Access (ENABLED) or not (DISABLED)
MEMOPTIMIZE_WRITE	VARCHAR2(8)		For internal use only
HAS_SENSITIVE_COLUMN	VARCHAR2(3)		Indicates whether the table has one or more sensitive columns (YES) or not (NO)
LOGICAL_REPLICATION	VARCHAR2(8)		Indicates whether the table is enabled for logical replication (ENABLED) or not (DISABLED). This setting is ignored if database-wide column data supplemental logging is enabled.
STAGING	VARCHAR2(3)		Indicates whether the table is a staging table (YES) or not (NO)
HAS_RESERVABLE_COLUMN	VARCHAR2(3)		Indicates whether the table has one or more reservable columns (YES) or not (NO)

1 This column is intended for use with Oracle Exadata.

See Also:

- "DBA_OBJECT_TABLES"
- "USER_OBJECT_TABLES"
- "PARALLEL_INSTANCE_GROUP"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_REPAIR.SKIP_CORRUPT_BLOCKS procedure

3.314 ALL_OBJECTS

ALL_OBJECTS describes all objects accessible to the current user.

Related Views

- DBA_OBJECTS describes all objects in the database.
- USER_OBJECTS describes all objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object
SUBOBJECT_NAME	VARCHAR2(128)		Name of the subobject (for example, partition)
OBJECT_ID	NUMBER	NOT NULL	Dictionary object number of the object
DATA_OBJECT_ID	NUMBER		Dictionary object number of the segment that contains the object. **Note:** OBJECT_ID and DATA_OBJECT_ID display data dictionary metadata. Do not confuse these numbers with the unique 16-byte object identifier (*object ID*) that Oracle Database assigns to row objects in object tables in the system.
OBJECT_TYPE	VARCHAR2(23)		Type of the object (such as TABLE, INDEX)
CREATED	DATE	NOT NULL	Timestamp for the creation of the object
LAST_DDL_TIME	DATE	NOT NULL	Timestamp for the last modification of the object and dependent objects resulting from a DDL statement (including grants and revokes)
TIMESTAMP	VARCHAR2(19)		Timestamp for the specification of the object (character data)
STATUS	VARCHAR2(7)		Status of the object: • VALID • INVALID • N/A
TEMPORARY	VARCHAR2(1)		Indicates whether the object is temporary (the current session can see only data that it placed in this object itself) (Y) or not (N)
GENERATED	VARCHAR2(1)		Indicates whether the name of this object was system-generated (Y) or not (N)
SECONDARY	VARCHAR2(1)		Indicates whether this is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y) or not (N)
NAMESPACE	NUMBER	NOT NULL	Namespace for the object
EDITION_NAME	VARCHAR2(128)		Name of the edition in which the object is actual

Column	Datatype	NULL	Description
SHARING	VARCHAR2(18)		Values: • DATA LINK - If the object is data-linked or a data link to an object in the root • METADATA LINK - If the object is metadata-linked or a metadata link to an object in the root • EXTENDED DATA LINK - If the object is extended-data-linked or an extended data link to an object in the root • NONE - If none of the above applies
EDITIONABLE	VARCHAR2(1)		Values: • Y - For objects marked EDITIONABLE • N - For objects marked NONEDITIONABLE • NULL - For objects whose type is not editionable in the database
ORACLE_MAINTAINED	VARCHAR2(1)		Denotes whether the object was created, and is maintained, by Oracle-supplied scripts (such as catalog.sql or catproc.sql). An object for which this column has the value Y must not be changed in any way except by running an Oracle-supplied script.
APPLICATION	VARCHAR2(1)		Indicates whether the object is an Application common object (Y) or not (N)
DEFAULT_COLLATION	VARCHAR2(100)		Default collation for the object
DUPLICATED	VARCHAR2(1)		Indicates whether this object is duplicated on this shard (Y) or not (N)
SHARDED	VARCHAR2(1)		Indicates whether this object is sharded (Y) or not (N)
IMPORTED_OBJECT	VARCHAR2(1)		Indicates whether this object is imported (Y) or not (N)
SYNCHRONOUS_DUPLICATED	VARCHAR2(1)		Indicates whether this object is a synchronous duplicated table (Y) or not (N)
CREATED_APPID	NUMBER		ID of the Application that created the object
CREATED_VSNID	NUMBER		ID of the Application Version that created the object
MODIFIED_APPID	NUMBER		ID of the Application that last modified the object
MODIFIED_VSNID	NUMBER		ID of the Application Version that last modified the object

See Also:

- "DBA_OBJECTS"
- "USER_OBJECTS"

3.315 ALL_OBJECTS_AE

ALL_OBJECTS_AE describes the objects (across all editions) accessible to the current user. Dropped objects appear in this view with OBJECT_TYPE = NON-EXISTENT.

Related Views

- DBA_OBJECTS_AE describes all objects (across all editions) in the database.
- USER_OBJECTS_AE describes the objects (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object
SUBOBJECT_NAME	VARCHAR2(128)		Name of the subobject (for example, partition)
OBJECT_ID	NUMBER	NOT NULL	Dictionary object number of the object
DATA_OBJECT_ID	NUMBER		Dictionary object number of the segment which contains the object
OBJECT_TYPE	VARCHAR2(23)		Type of the object
CREATED	DATE	NOT NULL	Timestamp for the creation of the object
LAST_DDL_TIME	DATE	NOT NULL	Timestamp for the last modification of the object and dependent objects resulting from a DDL statement (including grants and revokes)
TIMESTAMP	VARCHAR2(19)		Timestamp for the specification of the object (character data)
STATUS	VARCHAR2(7)		Status of the object: • VALID • INVALID • N/A
TEMPORARY	VARCHAR2(1)		Indicates whether the object is temporary (the current session can see only data that it placed in this object itself) (Y) or not (N)
GENERATED	VARCHAR2(1)		Indicates whether the name of this object was system-generated (Y) or not (N)
SECONDARY	VARCHAR2(1)		Indicates whether this is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y) or not (N)
NAMESPACE	NUMBER	NOT NULL	Namespace for the object
EDITION_NAME	VARCHAR2(128)		Name of the edition in which the object is actual

Column	Datatype	NULL	Description
SHARING	VARCHAR2(18)		Values: • DATA LINK - If the object is data-linked or a data link to an object in the root • METADATA LINK - If the object is metadata-linked or a metadata link to an object in the root • EXTENDED DATA LINK - If the object is extended-data-linked or an extended data link to an object in the root • NONE - If none of the above applies
EDITIONABLE	VARCHAR2(1)		Values: • Y - For objects marked EDITIONABLE • N - For objects marked NONEDITIONABLE • NULL - For objects whose type is not editionable in the database
ORACLE_MAINTAINED	VARCHAR2(1)		Denotes whether the object was created, and is maintained, by Oracle-supplied scripts (such as catalog.sql or catproc.sql). An object for which this column has the value Y must not be changed in any way except by running an Oracle-supplied script.
APPLICATION	VARCHAR2(1)		Indicates whether the object is an Application common object (Y) or not (N)
DEFAULT_COLLATION	VARCHAR2(100)		Default collation for the object
DUPLICATED	VARCHAR2(1)		Indicates whether this object is duplicated on this shard (Y) or not (N)
SHARDED	VARCHAR2(1)		Indicates whether this object is sharded (Y) or not (N)
IMPORTED_OBJECT	VARCHAR2(1)		Indicates whether this object is imported (Y) or not (N)
SYNCHRONOUS_DUPLICATED	VARCHAR2(1)		Indicates whether this object is a synchronous duplicated table (Y) or not (N)
CREATED_APPID	NUMBER		ID of the Application that created the object
CREATED_VSNID	NUMBER		ID of the Application Version that created the object
MODIFIED_APPID	NUMBER		ID of the Application that last modified the object
MODIFIED_VSNID	NUMBER		ID of the Application Version that last modified the object

See Also:

- "DBA_OBJECTS_AE"
- "USER_OBJECTS_AE"

3.316 ALL_OPANCILLARY

ALL_OPANCILLARY describes operators whose bindings are ancillary to other (primary) operators.

Related Views

- DBA_OPANCILLARY describes such information about all operators in the database.
- USER_OPANCILLARY describes such information about operators owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the ancillary operator
OPERATOR_NAME	VARCHAR2(128)	NOT NULL	Name of the ancillary operator
BINDING#	NUMBER	NOT NULL	Binding number of the ancillary operator
PRIMOP_OWNER	VARCHAR2(128)	NOT NULL	Owner of the primary operator
PRIMOP_NAME	VARCHAR2(128)	NOT NULL	Name of the primary operator
PRIMOP_BIND#	NUMBER	NOT NULL	Binding number of the primary operator

See Also:

- "DBA_OPANCILLARY"
- "USER_OPANCILLARY"

3.317 ALL_OPARGUMENTS

ALL_OPARGUMENTS describes arguments for each operator binding accessible to the current user.

Related Views

- DBA_OPARGUMENTS describes arguments of all operator bindings in the database.
- USER_OPARGUMENTS describes arguments of all operator bindings owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the operator argument
OPERATOR_NAME	VARCHAR2(128)	NOT NULL	Name of the operator argument
BINDING#	NUMBER	NOT NULL	Binding number of the operator argument
POSITION	NUMBER	NOT NULL	Position of the operator argument (1, 2, 3, ...)
ARGUMENT_TYPE	VARCHAR2(61)		Datatype of the operator argument

> **See Also:**
>
> - "DBA_OPARGUMENTS"
> - "USER_OPARGUMENTS"

3.318 ALL_OPBINDINGS

ALL_OPBINDINGS describes the binding functions and methods on the operators accessible to the current user.

Related Views

- DBA_OPBINDINGS describes the binding functions and methods on all operators in the database.
- USER_OPBINDINGS describes the binding functions and methods on the operators owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the operator
OPERATOR_NAME	VARCHAR2(128)	NOT NULL	Name of the operator
BINDING#	NUMBER	NOT NULL	Binding number of the operator
FUNCTION_NAME	VARCHAR2(92)		Name of the binding function or method as specified by the user
RETURN_SCHEMA	VARCHAR2(128)		Name of the schema of the return type if the return type of the binding is an object type
RETURN_TYPE	VARCHAR2(128)		Name of the return type
IMPLEMENTATION_TYPE_SCHEMA	VARCHAR2(128)		If the operator was created WITH INDEX CONTEXT or SCAN CONTEXT, then this column displays the schema of the implementation type used by the functional implementation of the operator as a scan context (null if the operator was created without this syntax). **See Also:** the CREATE OPERATOR statement in *Oracle Database SQL Language Reference*
IMPLEMENTATION_TYPE	VARCHAR2(128)		If the operator was created WITH INDEX CONTEXT or SCAN CONTEXT, then this column displays the name of the implementation type used by the functional implementation of the operator as a scan context (null if the operator was created without this syntax). **See Also:** the CREATE OPERATOR statement in *Oracle Database SQL Language Reference*

Column	Datatype	NULL	Description
PROPERTY	VARCHAR2(43)		Property of the operator binding: • WITH INDEX CONTEXT • COMPUTE ANCILLARY DATA • ANCILLARY TO • WITH COLUMN CONTEXT • WITH INDEX, COLUMN CONTEXT • COMPUTE ANCILLARY DATA, WITH COLUMN CONTEXT

See Also:

- "DBA_OPBINDINGS"
- "USER_OPBINDINGS"

3.319 ALL_OPERATOR_COMMENTS

ALL_OPERATOR_COMMENTS displays comments for the user-defined operators accessible to the current user.

Related Views

- DBA_OPERATOR_COMMENTS displays comments for all user-defined operators in the database.
- USER_OPERATOR_COMMENTS displays comments for the user-defined operators owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the user-defined operator
OPERATOR_NAME	VARCHAR2(128)	NOT NULL	Name of the user-defined operator
COMMENTS	VARCHAR2(4000)		Comment for the user-defined operator

See Also:

- "DBA_OPERATOR_COMMENTS"
- "USER_OPERATOR_COMMENTS"

3.320 ALL_OPERATORS

ALL_OPERATORS describes the operators accessible to the current user.

Related Views

- DBA_OPERATORS describes all operators in the database.
- USER_OPERATORS describes the operators owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the operator
OPERATOR_NAME	VARCHAR2(128)	NOT NULL	Name of the operator
NUMBER_OF_BINDS	NUMBER	NOT NULL	Number of bindings associated with the operator

See Also:

- "DBA_OPERATORS"
- "USER_OPERATORS"

3.321 ALL_OUTLINE_HINTS

ALL_OUTLINE_HINTS is a synonym for USER_OUTLINE_HINTS.

See Also:

"USER_OUTLINE_HINTS"

3.322 ALL_OUTLINES

ALL_OUTLINES is a synonym for USER_OUTLINES.

See Also:

"USER_OUTLINES"

4

Static Data Dictionary Views: ALL_PART_COL_STATISTICS to DATABASE_PROPERTIES

This chapter contains the static data dictionary views ALL_PART_COL_STATISTICS through DATABASE_PROPERTIES.

4.1 ALL_PART_COL_STATISTICS

ALL_PART_COL_STATISTICS displays column statistics and histogram information for the table partitions accessible to the current user.

Related Views

- DBA_PART_COL_STATISTICS displays column statistics and histogram information for all table partitions in the database.
- USER_PART_COL_STATISTICS displays column statistics and histogram information for the table partitions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the partitioned table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
PARTITION_NAME	VARCHAR2(128)		Name of the table partition
COLUMN_NAME	VARCHAR2(4000)		Name of the column
NUM_DISTINCT	NUMBER		Number of distinct values in the column
LOW_VALUE	RAW(1000)		Low value in the column
HIGH_VALUE	RAW(1000)		High value in the column
DENSITY	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT.
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in histogram for the column
SAMPLE_SIZE	NUMBER		Sample size used in analyzing the column
LAST_ANALYZED	DATE		Date on which the column was most recently analyzed
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics have been gathered or NO if statistics have been aggregated from subpartitions or have not been gathered

Column	Datatype	NULL	Description
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
NOTES	VARCHAR2(81)		Additional properties of the statistics, if any. Possible values: • INCREMENTAL: The column has synopses. • ADAPTIVE_SAMPLING: The column has synopses, and the synopses are in the adaptive sampling format introduced in Oracle Database 11*g* Release 1 (11.1). • HYPERLOGLOG: The column has synopses, and the synopses are in the HyperLogLog format introduced in Oracle Database 12*c* Release 2 (12.2.0.1). • HISTOGRAM_ONLY: Table statistics were gathered using the GATHER AUTO option and histograms were gathered without re-gathering other table and column statistics. • HIST_FOR_INCREM_STATS: A histogram used to support incremental statistics has been created and it is not used for optimization. • STATS_ON_LOAD: Online statistics were gathered during direct path load. This column can be used to determine whether synopses in the adaptive sampling format have been phased out entirely and purged properly.
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
HISTOGRAM	VARCHAR2(15)		Indicates existence/type of histogram: • NONE • FREQUENCY • HEIGHT BALANCED • HYBRID • TOP-FREQUENCY

See Also:

- "DBA_PART_COL_STATISTICS"
- "USER_PART_COL_STATISTICS"

4.2 ALL_PART_HISTOGRAMS

ALL_PART_HISTOGRAMS displays the histogram data (endpoints per histogram) for the histograms on the table partitions accessible to the current user.

Related Views

- DBA_PART_HISTOGRAMS displays the histogram data for the histograms on all table partitions in the database.

- USER_PART_HISTOGRAMS displays the histogram data for the histograms on the table partitions owned by the current user. This view does not display the OWNER column.

> **Note:**
>
> These views are populated only if you collect statistics on the index using the DBMS_STATS package.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table
PARTITION_NAME	VARCHAR2(128)		Name of the table partition
COLUMN_NAME	VARCHAR2(4000)		Name of the column
BUCKET_NUMBER	NUMBER		Bucket number of the histogram
ENDPOINT_VALUE	NUMBER		Normalized endpoint values for the bucket
ENDPOINT_ACTUAL_VALUE	VARCHAR2(4000)		Actual (not normalized) string value of the endpoint for the bucket
ENDPOINT_ACTUAL_VALUE_RAW	RAW(1000)		Endpoint actual value in raw format
ENDPOINT_REPEAT_COUNT	NUMBER		Frequency of the endpoint (applies only to hybrid histograms, and is set to 0 for other histogram types)

> **See Also:**
>
> - "DBA_PART_HISTOGRAMS"
> - "USER_PART_HISTOGRAMS"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

4.3 ALL_PART_INDEXES

ALL_PART_INDEXES displays the object-level partitioning information for the partitioned indexes accessible to the current user.

Related Views

- DBA_PART_INDEXES displays the object-level partitioning information for all partitioned indexes in the database.
- USER_PART_INDEXES displays the object-level partitioning information for the partitioned indexes owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the partitioned index
INDEX_NAME	VARCHAR2(128)	NOT NULL	Name of the partitioned index
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the partitioned table
PARTITIONING_TYPE	VARCHAR2(9)		Type of the partitioning method: • NONE - Not specified **See Also:** the *_INDEXES view • RANGE • HASH • SYSTEM • LIST • REFERENCE
SUBPARTITIONING_TYPE	VARCHAR2(9)		Type of the composite partitioning method: • NONE - Not specified **See Also:** the *_INDEXES view • RANGE • HASH • SYSTEM • LIST • REFERENCE
PARTITION_COUNT	NUMBER	NOT NULL	Number of partitions in the index
DEF_SUBPARTITION_COUNT	NUMBER		For a composite-partitioned index, the default number of subpartitions, if specified
PARTITIONING_KEY_COUNT	NUMBER	NOT NULL	Number of columns in the partitioning key
SUBPARTITIONING_KEY_COUNT	NUMBER		For a composite-partitioned index, the number of columns in the subpartitioning key
LOCALITY	VARCHAR2(6)		Indicates whether the partitioned index is local (LOCAL) or global (GLOBAL)
ALIGNMENT	VARCHAR2(12)		Indicates whether the partitioned index is prefixed (PREFIXED) or non-prefixed (NON_PREFIXED)
DEF_TABLESPACE_NAME	VARCHAR2(30)		For a local index, the default tablespace to be used when adding or splitting a table partition
DEF_PCT_FREE	NUMBER	NOT NULL	For a local index, the default PCTFREE value to be used when adding a table partition
DEF_INI_TRANS	NUMBER	NOT NULL	For a local index, the default INITRANS value to be used when adding a table partition
DEF_MAX_TRANS	NUMBER	NOT NULL	For a local index, the default MAXTRANS value to be used when adding a table partition
DEF_INITIAL_EXTENT	VARCHAR2(40)		For a local index, the default INITIAL value (in Oracle blocks) to be used when adding a table partition, or DEFAULT if no INITIAL value was specified
DEF_NEXT_EXTENT	VARCHAR2(40)		For a local index, the default NEXT value (in Oracle blocks) to be used when adding a table partition, or DEFAULT if no NEXT value was specified
DEF_MIN_EXTENTS	VARCHAR2(40)		For a local index, the default MINEXTENTS value to be used when adding a table partition, or DEFAULT if no MINEXTENTS value was specified

Column	Datatype	NULL	Description
DEF_MAX_EXTENTS	VARCHAR2(40)		For a local index, the default MAXEXTENTS value to be used when adding a table partition, or DEFAULT if no MAXEXTENTS value was specified
DEF_MAX_SIZE	VARCHAR2(40)		For a local index, the default MAXSIZE value to be used when adding a table partition, or DEFAULT if no MAXSIZE value was specified
DEF_PCT_INCREASE	VARCHAR2(40)		For a local index, the default PCTINCREASE value to be used when adding a table partition, or DEFAULT if no PCTINCREASE value was specified
DEF_FREELISTS	NUMBER	NOT NULL	For a local index, the default FREELISTS value to be used when adding a table partition
DEF_FREELIST_GROUPS	NUMBER	NOT NULL	For a local index, the default FREELIST GROUPS value to be used when adding a table partition
DEF_LOGGING	VARCHAR2(7)		For a local index, the default LOGGING attribute to be used when adding a table partition: • NONE - Not specified **See Also:** the *_INDEXES view • YES • NO
DEF_BUFFER_POOL	VARCHAR2(7)		For a local index, the default buffer pool to be used when adding a table partition: • DEFAULT • KEEP • RECYCLE • NULL
DEF_FLASH_CACHE	VARCHAR2(7)		For a local index, the default Database Smart Flash Cache hint to be used when adding a table partition: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.
DEF_CELL_FLASH_CACHE	VARCHAR2(7)		For a local index, the default cell flash cache hint to be used when adding a table partition: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
DEF_PARAMETERS	VARCHAR2(1000)		Default parameter string for domain indexes
INTERVAL	VARCHAR2(1000)		String of the interval value
AUTOLIST	VARCHAR2(3)		Indicates whether a local index is partitioned by auto list partitioning (YES) or not (NO)
INTERVAL_SUBPARTITION	VARCHAR2(1000)		String of the subpartition interval value
AUTOLIST_SUBPARTITION	VARCHAR2(3)		Indicates whether a local index is subpartitioned by auto list partitioning (YES) or not (NO)

> **See Also:**
>
> - "DBA_PART_INDEXES"
> - "USER_PART_INDEXES"

4.4 ALL_PART_KEY_COLUMNS

ALL_PART_KEY_COLUMNS describes the partitioning key columns for the partitioned objects accessible to the current user.

Related Views

- DBA_PART_KEY_COLUMNS describes the partitioning key columns for all partitioned objects in the database.
- USER_PART_KEY_COLUMNS describes the partitioning key columns for the partitioned objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the partitioned table or index
NAME	VARCHAR2(128)		Name of the partitioned table or index
OBJECT_TYPE	CHAR(5)		Object type: • TABLE • INDEX
COLUMN_NAME	VARCHAR2(4000)		Name of the column
COLUMN_POSITION	NUMBER		Position of the column within the partitioning key
COLLATED_COLUMN_ID	NUMBER		Internal sequence number of the column for which this column provides linguistic ordering

> **See Also:**
>
> - "DBA_PART_KEY_COLUMNS"
> - "USER_PART_KEY_COLUMNS"

4.5 ALL_PART_LOBS

ALL_PART_LOBS displays table-level information about the partitioned LOBs accessible to the current user, including default attributes for LOB data partitions.

Related Views

- DBA_PART_LOBS displays table-level information about all partitioned LOBs in the database.

- USER_PART_LOBS displays table-level information about the partitioned LOBs owned by the current user. This view does not display the TABLE_OWNER column.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the partitioned table containing the LOBs
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the partitioned table containing the LOBs
COLUMN_NAME	VARCHAR2(4000)		Name of the LOB column
LOB_NAME	VARCHAR2(128)	NOT NULL	Name of the partitioned LOB
LOB_INDEX_NAME	VARCHAR2(128)	NOT NULL	Name of the partitioned LOB index
DEF_CHUNK	NUMBER	NOT NULL	Default value of CHUNK for a LOB data partition to be used when adding a partition
DEF_PCTVERSION	NUMBER	NOT NULL	Default value of PCTVERSION for a LOB data partition to be used when adding a partition
DEF_CACHE	VARCHAR2(10)		Indicates whether and how the LOB data is cached by default in the buffer cache: • YES - LOB data is placed in the buffer cache • NO - LOB data either is not brought into the buffer cache or is brought into the buffer cache and placed at the least recently used end of the LRU list • CACHEREADS - LOB data is brought into the buffer cache only during read operations but not during write operations
DEF_IN_ROW	VARCHAR2(3)		Indicates whether LOB data < 4000 bytes is stored by default inline (in the row) (YES) or not (NO); that is, whether or not ENABLE STORAGE IN ROW was specified when the LOB column was created or last altered
DEF_TABLESPACE_NAME	VARCHAR2(30)		Default tablespace for a LOB data partition to be used when adding a partition
DEF_INITIAL_EXTENT	VARCHAR2(40)		Default value of INITIAL for a LOB data partition to be used when adding a partition, or DEFAULT if no INITIAL value was specified
DEF_NEXT_EXTENT	VARCHAR2(40)		Default value of NEXT for a LOB data partition to be used when adding a partition, or DEFAULT if no NEXT value was specified
DEF_MIN_EXTENTS	VARCHAR2(40)		Default value of MINEXTENTS for a LOB data partition to be used when adding a partition, or DEFAULT if no MINEXTENTS value was specified
DEF_MAX_EXTENTS	VARCHAR2(40)		Default value of MAXEXTENTS for a LOB data partition to be used when adding a partition, or DEFAULT if no MAXEXTENTS value was specified
DEF_MAX_SIZE	VARCHAR2(40)		Default value of MAXSIZE for a LOB data partition to be used when adding a partition, or DEFAULT if no MAXSIZE value was specified

Column	Datatype	NULL	Description
DEF_RETENTION	VARCHAR2(7)		Default value of RETENTION for a LOB data partition to be used when adding a partition. Possible values for SecureFiles: • NONE • AUTO • MIN • MAX • DEFAULT • INVALID Possible values for BasicFiles: • YES • NO
DEF_MINRET	VARCHAR2(40)		Default value of RETENTION MIN for a LOB data partition to be used when adding a partition, or DEFAULT if no RETENTION MIN value was specified
DEF_PCT_INCREASE	VARCHAR2(40)		Default value of PCTINCREASE for a LOB data partition to be used when adding a partition, or DEFAULT if no PCTINCREASE value was specified
DEF_FREELISTS	VARCHAR2(40)		Default value of FREELISTS for a LOB data partition to be used when adding a partition, or DEFAULT if no FREELISTS value was specified
DEF_FREELIST_GROUPS	VARCHAR2(40)		Default value of FREELIST GROUPS for a LOB data partition to be used when adding a partition, or DEFAULT if no FREELIST GROUPS value was specified
DEF_LOGGING	VARCHAR2(7)		Default LOGGING attribute for a LOB data partition to be used when adding a partition: • NONE - Not specified **See Also:** the *_LOBS and *_LOB_PARTITIONS views • YES • NO
DEF_BUFFER_POOL	VARCHAR2(7)		Default buffer pool for a LOB data partition to be used when adding a partition: • DEFAULT • KEEP • RECYCLE • NULL
DEF_FLASH_CACHE	VARCHAR2(7)		Default Database Smart Flash Cache hint to be used when adding a partition: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.

Column	Datatype	NULL	Description
DEF_CELL_FLASH_CACHE	VARCHAR2(7)		Default cell flash cache hint to be used when adding a partition: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
DEF_ENCRYPT	VARCHAR2(4)		Default value of ENCRYPT for a LOB data partition to be used when adding a partition. Possible values for SecureFiles: • YES • NO Possible value for BasicFiles: • NONE - Not applicable
DEF_COMPRESS	VARCHAR2(6)		Default value of COMPRESS for a LOB data partition to be used when adding a partition. Possible values for SecureFiles: • LOW • MEDIUM • HIGH • NO - Compression is off Possible value for BasicFiles: • NONE - Not applicable
DEF_DEDUPLICATE	VARCHAR2(15)		Default value of DEDUPLICATE for a LOB data partition to be used when adding a partition. Possible values for SecureFiles: • LOB - Deduplicate • NO - Keep duplicates Possible values for BasicFiles: • NONE - Not applicable
DEF_SECUREFILE	VARCHAR2(3)		Indicates whether the LOB is SecureFiles (YES) or not (NO)
DEF_MAX_INLINE	NUMBER		Default inline LOB size (in bytes)

See Also:

- "DBA_PART_LOBS"
- "USER_PART_LOBS"

4.6 ALL_PART_TABLES

ALL_PART_TABLES displays the object-level partitioning information for the partitioned tables accessible to the current user.

Related Views

- DBA_PART_TABLES displays the object-level partitioning information for all partitioned tables in the database.
- USER_PART_TABLES displays the object-level partitioning information for the partitioned tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the partitioned table
TABLE_NAME	VARCHAR2(128)		Name of the partitioned table
PARTITIONING_TYPE	VARCHAR2(9)		Type of the partitioning method: • UNKNOWN - Not specified **See Also:** the *_TABLES view • RANGE • HASH • SYSTEM • LIST • REFERENCE
SUBPARTITIONING_TYPE	VARCHAR2(9)		Type of the composite partitioning method: • NONE - Not subpartitioned **See Also:** the *_TABLES view • RANGE • HASH • SYSTEM • LIST • REFERENCE
PARTITION_COUNT	NUMBER		Number of partitions in the table. For interval partitioned tables, the value of this column is always 1048575.
DEF_SUBPARTITION_COUNT	NUMBER		For a composite-partitioned table, the default number of subpartitions, if specified
PARTITIONING_KEY_COUNT	NUMBER		Number of columns in the partitioning key
SUBPARTITIONING_KEY_COUNT	NUMBER		For a composite-partitioned table, the number of columns in the subpartitioning key
STATUS	VARCHAR2(8)		If a previous DROP TABLE operation failed, indicates whether the table is unusable (UNUSABLE) or valid (VALID)
DEF_TABLESPACE_NAME	VARCHAR2(30)		Default tablespace to be used when adding a partition
DEF_PCT_FREE	NUMBER		Default value of PCTFREE to be used when adding a partition

Column	Datatype	NULL	Description
DEF_PCT_USED	NUMBER		Default value of PCTUSED to be used when adding a partition
DEF_INI_TRANS	NUMBER		Default value of INITRANS to be used when adding a partition
DEF_MAX_TRANS	NUMBER		Default value of MAXTRANS to be used when adding a partition
DEF_INITIAL_EXTENT	VARCHAR2(40)		Default value of INITIAL (in Oracle blocks) to be used when adding a partition, or DEFAULT if no INITIAL value was specified
DEF_NEXT_EXTENT	VARCHAR2(40)		Default value of NEXT (in Oracle blocks) to be used when adding a partition, or DEFAULT if no NEXT value was specified
DEF_MIN_EXTENTS	VARCHAR2(40)		Default value of MINEXTENTS to be used when adding a partition, or DEFAULT if no MINEXTENTS value was specified
DEF_MAX_EXTENTS	VARCHAR2(40)		Default value of MAXEXTENTS to be used when adding a partition, or DEFAULT if no MAXEXTENTS value was specified
DEF_MAX_SIZE	VARCHAR2(40)		Default value of MAXSIZE to be used when adding a partition, or DEFAULT if no MAXSIZE value was specified
DEF_PCT_INCREASE	VARCHAR2(40)		Default value of PCTINCREASE to be used when adding a partition, or DEFAULT if no PCTINCREASE value was specified
DEF_FREELISTS	NUMBER		Default value of FREELISTS to be used when adding a partition
DEF_FREELIST_GROUPS	NUMBER		Default value of FREELIST GROUPS to be used when adding a partition
DEF_LOGGING	VARCHAR2(7)		Default LOGGING attribute to be used when adding a partition: • NONE - Not specified **See Also:** the *_TABLES view • YES • NO
DEF_COMPRESSION	VARCHAR2(8)		Default compression to be used when adding a partition: • NONE - Not specified **See Also:** the *_TABLES view • ENABLED • DISABLED

Column	Datatype	NULL	Description
DEF_COMPRESS_FOR	VARCHAR2(30)		Default compression for what kind of operations to be used when adding a partition: • BASIC • ADVANCED • QUERY LOW[1] • QUERY HIGH[1] • ARCHIVE LOW[1] • ARCHIVE HIGH[1] • UNKNOWN • NULL
DEF_BUFFER_POOL	VARCHAR2(7)		Default buffer pool to be used when adding a partition: • DEFAULT • KEEP • RECYCLE • NULL
DEF_FLASH_CACHE	VARCHAR2(7)		Default Database Smart Flash Cache hint to be used when adding a partition: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.
DEF_CELL_FLASH_CACHE	VARCHAR2(7)		Default cell flash cache hint to be used when adding a partition: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
REF_PTN_CONSTRAINT_NAME	VARCHAR2(128)		Name of the partitioning referential constraint for reference-partitioned tables
INTERVAL	VARCHAR2(1000)		String of the interval value
AUTOLIST	VARCHAR2(3)		Indicates whether a table is partitioned by auto list partitioning (YES) or not (NO)
INTERVAL_SUBPARTITION	VARCHAR2(1000)		String of the subpartition interval value
AUTOLIST_SUBPARTITION	VARCHAR2(3)		Indicates whether auto list partitioning is being used (YES) or not (NO) for this subpartition
IS_NESTED	VARCHAR2(3)		Indicates whether the partitioned table is a nested table (YES) or not (NO) **See Also:** the *_NESTED_TABLES view for the parent table name/column
DEF_SEGMENT_CREATION	VARCHAR2(4)		Specifies whether the default for segment creation was specified on the table level: • NO - deferred was specified • YES - immediate was specified • NONE - a default for segment creation was not specified

Column	Datatype	NULL	Description
DEF_INDEXING	VARCHAR2(3)		Indicates the indexing property specified for the table. Possible values: • ON - INDEXING on was specified explicitly, or no indexing property was specified • OFF - INDEXING off was specified.
DEF_INMEMORY	VARCHAR2(8)		Indicates whether the In-Memory Column Store (IM column store) is by default enabled (ENABLED), disabled (DISABLED), or not specified (NONE) for partitions in this table
DEF_INMEMORY_PRIORITY	VARCHAR2(8)		Indicates the default priority for In-Memory Column Store (IM column store) population. Possible values: • LOW • MEDIUM • HIGH • CRITICAL • NONE • NULL
DEF_INMEMORY_DISTRIBUTE	VARCHAR2(15)		Indicates how the IM column store is distributed by default for partitions of the table in an Oracle Real Application Clusters (Oracle RAC) environment: • AUTO • BY ROWID RANGE • BY PARTITION • BY SUBPARTITION
DEF_INMEMORY_COMPRESSION	VARCHAR2(17)		Default compression level for the IM column store: • NO MEMCOMPRESS • FOR DML • FOR QUERY [LOW | HIGH] • FOR CAPACITY [LOW | HIGH] • AUTO • NULL
DEF_INMEMORY_DUPLICATE	VARCHAR2(13)		Indicates the default duplicate setting for the IM column store in an Oracle RAC environment: • NO DUPLICATE • DUPLICATE • DUPLICATE ALL
DEF_READ_ONLY	VARCHAR2(3)		Indicates the default setting for new partitions: • YES: The default setting for new partitions is read-only. • NO: The default setting for new partitions is read/write.
DEF_CELLMEMORY[2]	VARCHAR2(24)		Shows the default value for the CELLMEMORY attribute that new partitions in the parent table will inherit unless the behavior is overridden explicitly

Column	Datatype	NULL	Description
DEF_INMEMORY_SERVICE	VARCHAR2(12)		Indicates how the IM column store is populated on various instances by default for partitions of the table. The possible values are: • DEFAULT: Data is populated on all instances specified with the PARALLEL_INSTANCE_GROUP initialization parameter. If that parameter is not set, then the data is populated on all instances. This is the default. • NONE: Data is not populated on any instance. • ALL: Data is populated on all instances, regardless of the value of the PARALLEL_INSTANCE_GROUP initialization parameter. • USER_DEFINED: Data is populated only on the instances on which the user-specified service is active. The service name corresponding to this is stored in the DEF_INMEMORY_SERVICE_NAME column.
DEF_INMEMORY_SERVICE_NAME	VARCHAR2(1000)		Specifies the service name for the service on which the IM column store should be populated by default for partitions of the table. This column has a value only when the corresponding DEF_INMEMORY_SERVICE is USER_DEFINED. In all other cases, this column is null.
AUTO	VARCHAR2(3)		Indicates whether the table was automatically partitioned (YES) or not (NO)

1 Hybrid Columnar Compression is a feature of the Enterprise Edition of Oracle Database that is dependent on the underlying storage system. See *Oracle Database Concepts* for more information.
2 This column is intended for use with Oracle Exadata

See Also:

- "DBA_PART_TABLES"
- "USER_PART_TABLES"
- "PARALLEL_INSTANCE_GROUP"

4.7 ALL_PARTIAL_DROP_TABS

ALL_PARTIAL_DROP_TABS describes tables accessible to the current user that have partially completed DROP COLUMN operations. Such operations might have been interrupted by the user or by a system crash.

Related Views

- DBA_PARTIAL_DROP_TABS describes all tables in the database that have partially completed DROP COLUMN operations.

- USER_PARTIAL_DROP_TABS describes tables in the schema of the current user that have partially completed DROP COLUMN operations. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table

See Also:

- "DBA_PARTIAL_DROP_TABS"
- "USER_PARTIAL_DROP_TABS"

4.8 ALL_PENDING_CONV_TABLES

ALL_PENDING_CONV_TABLES describes the pending conversion tables (tables which are not upgraded to the latest type version) accessible to the current user.

Related Views

- DBA_PENDING_CONV_TABLES describes all pending conversion tables in the database.
- USER_PENDING_CONV_TABLES describes the pending conversion tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table

See Also:

- "DBA_PENDING_CONV_TABLES"
- "USER_PENDING_CONV_TABLES"

4.9 ALL_PG_EDGE_RELATIONSHIPS

ALL_PG_EDGE_RELATIONSHIPS describes edge relationships in the property graphs accessible to the current user.

This view displays one row for each key column used for an edge relationship. For example, an edge table defined as follows will result in two rows in this view:

```
EDGE TABLES(et1 SOURCE KEY(cx, cy) REFERENCES vt1(fk1, fk2) ... )
```

Related Views

- DBA_PG_EDGE_RELATIONSHIPS describes edge relationships in all property graphs in the database.
- USER_PG_EDGE_RELATIONSHIPS describes edge relationships in the property graphs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the property graph
GRAPH_NAME	VARCHAR2(128)	NOT NULL	Name of the property graph
EDGE_TAB_NAME	VARCHAR2(128)	NOT NULL	Name of the edge table
VERTEX_TAB_NAME	VARCHAR2(128)	NOT NULL	Name of the vertex table
EDGE_END	VARCHAR2(11)		Indicates whether the vertex table is a source vertex table (SOURCE) or a destination vertex table (DESTINATION)
EDGE_COL_NAME	VARCHAR2(128)	NOT NULL	Name of the foreign column in the edge table
VERTEX_COL_NAME	VARCHAR2(128)	NOT NULL	Name of the referenced column in the vertex table

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_PG_EDGE_RELATIONSHIPS"
- "USER_PG_EDGE_RELATIONSHIPS"

4.10 ALL_PG_ELEMENT_LABELS

ALL_PG_ELEMENT_LABELS describes labels for the element tables in the property graphs accessible to the current user.

Related Views

- DBA_PG_ELEMENT_LABELS describes labels for the element tables in all property graphs in the database.
- USER_PG_ELEMENT_LABELS describes labels for the element tables in the property graphs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the property graph
GRAPH_NAME	VARCHAR2(128)	NOT NULL	Name of the property graph

Column	Datatype	NULL	Description
ELEMENT_NAME	VARCHAR2(128)	NOT NULL	Name of the element table
LABEL_NAME	VARCHAR2(128)	NOT NULL	Name of the label

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_PG_ELEMENT_LABELS"
> - "USER_PG_ELEMENT_LABELS"

4.11 ALL_PG_ELEMENTS

ALL_PG_ELEMENTS describes element tables in the property graphs accessible to the current user.

Related Views

- DBA_PG_ELEMENTS describes element tables in all property graphs in the database.
- USER_PG_ELEMENTS describes element tables in the property graphs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the property graph
GRAPH_NAME	VARCHAR2(128)	NOT NULL	Name of the property graph
ELEMENT_NAME	VARCHAR2(128)	NOT NULL	Name of the element table
ELEMENT_KIND	VARCHAR2(6)		Kind of element table (VERTEX or EDGE)
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Schema in which the object storing the elements was created
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object storing the elements

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_PG_ELEMENTS"
> - "USER_PG_ELEMENTS"

4.12 ALL_PG_KEYS

ALL_PG_KEYS describes key columns in the property graphs accessible to the current user.

Related Views

- DBA_PG_KEYS describes key columns in all property graphs in the database.
- USER_PG_KEYS describes key columns in the property graphs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the property graph
GRAPH_NAME	VARCHAR2(128)	NOT NULL	Name of the property graph
ELEMENT_NAME	VARCHAR2(128)	NOT NULL	Name of the element table
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column used to define the key

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_PG_KEYS"
> - "USER_PG_KEYS"

4.13 ALL_PG_LABEL_PROPERTIES

ALL_PG_LABEL_PROPERTIES describes properties in the property graphs accessible to the current user.

Related Views

- DBA_PG_LABEL_PROPERTIES describes properties in all property graphs in the database.

- USER_PG_LABEL_PROPERTIES describes properties in the property graphs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the property graph
GRAPH_NAME	VARCHAR2(128)	NOT NULL	Name of the property graph
LABEL_NAME	VARCHAR2(128)	NOT NULL	Name of the label
PROPERTY_NAME	VARCHAR2(128)	NOT NULL	Name of the property
DATA_TYPE	VARCHAR2(106)		Data type of the property
DATA_LENGTH	NUMBER	NOT NULL	Length of the data type (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for NUMBER data type; binary precision for FLOAT data type; null for all other data types
DATA_SCALE	NUMBER		Digits to the right of the decimal point in a number; null for all other data types
DATA_CHAR_LENGTH	NUMBER		Maximum length of the property (in characters)
CHARACTER_SET_NAME	VARCHAR2(44)		Name of the character set: • CHAR_CS • NCHAR_CS
COLLATION	VARCHAR2(100)		Collation for the column. Only applies to columns with character data types.
PROPERTY_ORDER	NUMBER	NOT NULL	Declaration order of the property in the label

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_PG_LABEL_PROPERTIES"
- "USER_PG_LABEL_PROPERTIES"

4.14 ALL_PG_LABELS

ALL_PG_LABELS describes labels in the property graphs accessible to the current user.

Related Views

- DBA_PG_LABELS describes labels in all property graphs in the database.
- USER_PG_LABELS describes labels in the property graphs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the property graph
GRAPH_NAME	VARCHAR2(128)	NOT NULL	Name of the property graph
LABEL_NAME	VARCHAR2(128)	NOT NULL	Name of the label

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_PG_LABELS"
> - "USER_PG_LABELS"

4.15 ALL_PG_PROP_DEFINITIONS

ALL_PG_PROP_DEFINITIONS describes columns and expressions exposed as properties in the property graphs accessible to the current user.

Related Views

- DBA_PG_PROP_DEFINITIONS describes columns and expressions exposed as properties in all property graphs in the database.
- USER_PG_PROP_DEFINITIONS describes columns and expressions exposed as properties in the property graphs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the property graph
GRAPH_NAME	VARCHAR2(128)	NOT NULL	Name of the property graph
ELEMENT_NAME	VARCHAR2(128)	NOT NULL	Name of the element table
PROPERTY_NAME	VARCHAR2(128)	NOT NULL	Name of the property
COLUMN_NAME	VARCHAR2(128)		Column exposed by the property
COLUMN_EXPR	LONG		Expression exposed by the property

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_PG_PROP_DEFINITIONS"
> - "USER_PG_PROP_DEFINITIONS"

4.16 ALL_PLSQL_COLL_TYPES

ALL_PLSQL_COLL_TYPES describes named PL/SQL collection types accessible to the user.

Related Views

- DBA_PLSQL_COLL_TYPES describes all named PL/SQL collection types in the database. This view does not display the CHAR_USED column.
- USER_PLSQL_COLL_TYPES describes the user's own named PL/SQL collection types. This view does not display the OWNER or CHAR_USED columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the type
TYPE_NAME	VARCHAR2(128)		Name of the type
PACKAGE_NAME	VARCHAR2(128)		Name of the package containing the collection
COLL_TYPE	VARCHAR2(128)		Collection type
UPPER_BOUND	NUMBER		The upper bound of a varray or length constraint of an index by VARCHAR2 table
ELEM_TYPE_OWNER	VARCHAR2(128)		Owner of the type of the element
ELEM_TYPE_NAME	VARCHAR2(136)		Name of the type of the element
ELEM_TYPE_PACKAGE	VARCHAR2(128)		Name of the package containing the element
LENGTH	NUMBER		Length of the CHAR element or maximum length of the VARCHAR or VARCHAR2 element
PRECISION	NUMBER		Decimal precision of the NUMBER or DECIMAL element or binary precision of the FLOAT element
SCALE	NUMBER		Scale of the NUMBER or DECIMAL element
CHARACTER_SET_NAME	VARCHAR2(44)		Character set name of the element
ELEM_STORAGE	VARCHAR2(7)		Storage optimization specification for VARRAY of numeric elements
NULLS_STORED	VARCHAR2(3)		Indicates whether null information is stored with each VARRAY element (YES) or not (NO)
CHAR_USED	VARCHAR2(1)		C if the width was specified in characters, B if in bytes
INDEX_BY	VARCHAR2(14)		Index by BINARY_INTEGER or VARCHAR2
ELEM_TYPE_MOD	VARCHAR2(7)		Type modifier of the element

> **See Also:**
>
> - "DBA_PLSQL_COLL_TYPES"
> - "USER_PLSQL_COLL_TYPES"

4.17 ALL_PLSQL_OBJECT_SETTINGS

ALL_PLSQL_OBJECT_SETTINGS displays information about the compiler settings for the stored objects accessible to the current user.

Related Views

- DBA_PLSQL_OBJECT_SETTINGS displays information about the compiler settings for all stored objects in the database.
- USER_PLSQL_OBJECT_SETTINGS displays information about the compiler settings for the stored objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
NAME	VARCHAR2(128)	NOT NULL	Name of the object
TYPE	VARCHAR2(12)		Type of the object: • PROCEDURE • FUNCTION • PACKAGE • PACKAGE BODY • TRIGGER • TYPE • TYPE BODY
PLSQL_OPTIMIZE_LEVEL	NUMBER		Optimization level that was used to compile the object
PLSQL_CODE_TYPE	VARCHAR2(4000)		Compilation mode for the object
PLSQL_DEBUG	VARCHAR2(4000)		Indicates whether the object was compiled with debug information or not
PLSQL_WARNINGS	VARCHAR2(4000)		Compiler warning settings that were used to compile the object
NLS_LENGTH_SEMANTICS	VARCHAR2(4000)		NLS length semantics that were used to compile the object
PLSQL_CCFLAGS	VARCHAR2(4000)		Conditional compilation flag settings that were used to compile the object
PLSCOPE_SETTINGS	VARCHAR2(4000)		Settings for using PL/Scope

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)
PLSQL_IMPLICIT_CONVERSION_BOOL	VARCHAR2(4000)		Indicates whether the object is to be compiled with implicit conversion for the BOOLEAN data type or not

See Also:

- "DBA_PLSQL_OBJECT_SETTINGS"
- "USER_PLSQL_OBJECT_SETTINGS"

4.18 ALL_PLSQL_TYPE_ATTRS

ALL_PLSQL_TYPE_ATTRS describes the attributes of PL/SQL types accessible to the user.

Related Views

- DBA_PLSQL_TYPE_ATTRS describes the attributes of all PL/SQL types in the database.
- USER_PLSQL_TYPE_ATTRS describes the attributes of the user's own PL/SQL types. This view does not display the OWNER or CHAR_USED columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the type
TYPE_NAME	VARCHAR2(136)		Name of the type
PACKAGE_NAME	VARCHAR2(128)		Name of the package containing the type
ATTR_NAME	VARCHAR2(128)		Name of the attribute
ATTR_TYPE_MOD	VARCHAR2(7)		Type modifier of the attribute
ATTR_TYPE_OWNER	VARCHAR2(128)		Owner of the type of the attribute
ATTR_TYPE_NAME	VARCHAR2(136)		Name of the type of the attribute
ATTR_TYPE_PACKAGE	VARCHAR2(128)		Name of the package containing the attribute type
LENGTH	NUMBER		Length of the CHAR attribute or maximum length of the VARCHAR or VARCHAR2 attribute
PRECISION	NUMBER		Decimal precision of the NUMBER or DECIMAL attribute or binary precision of the FLOAT attribute
SCALE	NUMBER		Scale of the NUMBER or DECIMAL attribute
CHARACTER_SET_NAME	VARCHAR2(44)		Character set name of the attribute

Column	Datatype	NULL	Description
ATTR_NO	NUMBER		Syntactical order number or position of the attribute as specified in the type specification or CREATE TYPE statement (not to be used as ID number)
CHAR_USED	VARCHAR2(1)		C if the width was specified in characters, B if in bytes

See Also:

- "DBA_PLSQL_TYPE_ATTRS"
- "USER_PLSQL_TYPE_ATTRS"

4.19 ALL_PLSQL_TYPES

ALL_PLSQL_TYPES describes the PL/SQL types accessible to the user.

Related Views

- DBA_PLSQL_TYPES describes all the PL/SQL types in the database.
- USER_PLSQL_TYPES describes the user's own PL/SQL types. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the type
TYPE_NAME	VARCHAR2(136)		Name of the type
PACKAGE_NAME	VARCHAR2(128)	NOT NULL	Name of the package containing the type
TYPE_OID	RAW(16)	NOT NULL	Object identifier (OID) of the type
TYPECODE	VARCHAR2(58)		Typecode of the type
ATTRIBUTES	NUMBER		Number of attributes in the type
CONTAINS_PLSQL	VARCHAR2(3)		Indicates whether the type contains PL/SQL-specific data types (YES) or not (NO)

See Also:

- "DBA_PLSQL_TYPES"
- "USER_PLSQL_TYPES"

4.20 ALL_POLICIES

ALL_POLICIES describes all Oracle Virtual Private Database (VPD) security policies for objects accessible to the current user. A security policy is a list of security requirements and rules that regulate row level access to those database objects.

Related Views

- DBA_POLICIES describes all Oracle Virtual Private Database (VPD) security policies in the database.
- USER_POLICIES describes all Oracle Virtual Private Database (VPD) security policies associated with objects owned by the current user. This view does not display the OBJECT_OWNER column.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)		Owner of the synonym, table, or view
OBJECT_NAME	VARCHAR2(128)		Name of the synonym, table, or view
POLICY_GROUP	VARCHAR2(128)		Name of the policy group
POLICY_NAME	VARCHAR2(128)		Name of the policy
PF_OWNER	VARCHAR2(128)		Owner of the policy function
PACKAGE	VARCHAR2(128)		Name of the package containing the policy function
FUNCTION	VARCHAR2(128)		Name of the policy function
SEL	VARCHAR2(3)		Indicates whether the policy is applied to queries on the object (YES) or not (NO)
INS	VARCHAR2(3)		Indicates whether the policy is applied to INSERT statements on the object (YES) or not (NO)
UPD	VARCHAR2(3)		Indicates whether the policy is applied to UPDATE statements on the object (YES) or not (NO)
DEL	VARCHAR2(3)		Indicates whether the policy is applied to DELETE statements on the object (YES) or not (NO)
IDX	VARCHAR2(3)		Indicates whether the policy is enforced for index maintenance on the object (YES) or not (NO)
CHK_OPTION	VARCHAR2(3)		Indicates whether the check option is enforced for the policy (YES) or not (NO)
ENABLE	VARCHAR2(3)		Indicates whether the policy is enabled (YES) or disabled (NO)
STATIC_POLICY	VARCHAR2(3)		Indicates whether the policy is static (YES) or not (NO). This column is obsolete because information about static policies is shown in the POLICY_TYPE column.
POLICY_TYPE	VARCHAR2(24)		Policy type: • STATIC • SHARED_STATIC • CONTEXT_SENSITIVE • SHARED_CONTEXT_SENSITIVE • DYNAMIC

Column	Datatype	NULL	Description
LONG_PREDICATE	VARCHAR2(3)		Indicates whether the policy function can return a maximum of 32 KB of predicate (YES) or not (NO). If NO, the default maximum predicate size is 4000 bytes.
COMMON	VARCHAR2(3)		Indicates whether the policy is applied and enforced in all application PDBs (YES) or only in the local PDB (NO)
INHERITED	VARCHAR2(3)		Indicates whether the policy is inherited from the root (YES) or not (NO)

See Also:

- "DBA_POLICIES"
- "USER_POLICIES"
- *Oracle Database Security Guide* for more information about security policies
- The DBMS_RLS package in *Oracle Database PL/SQL Packages and Types Reference* for information on administering security policies

4.21 ALL_POLICY_ATTRIBUTES

ALL_POLICY_ATTRIBUTES lists the attribute associations {Namespaces, Attributes} of context-sensitive and shared context-sensitive Oracle Virtual Private Database (VPD) policies for objects accessible to the current user.

Related Views

- DBA_POLICY_ATTRIBUTES lists the attribute associations {Namespaces, Attributes} of all context-sensitive and shared context-sensitive Oracle Virtual Private Database (VPD) policies in the database.
- USER_POLICY_ATTRIBUTES lists the attribute associations {Namespaces, Attributes} of all context-sensitive and shared-context sensitive Oracle Virtual Private Database (VPD) policies for synonyms, tables, or views owned by the user.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)		Owner of the synonym, table, or view
OBJECT_NAME	VARCHAR2(128)		Name of the synonym, table, or view
POLICY_GROUP	VARCHAR2(128)		Name of the policy group
POLICY_NAME	VARCHAR2(128)		Name of the policy
NAMESPACE	VARCHAR2(128)		Name of the local application context
ATTRIBUTE	VARCHAR2(128)		Name of the attribute

Column	Datatype	NULL	Description
COMMON	VARCHAR2(3)		Indicates whether the policy attribute is applied and enforced in all application PDBs (YES) or only in the local PDB (NO)
INHERITED	VARCHAR2(3)		Indicates whether the policy attribute is inherited from the root (YES) or not (NO)

See Also:

- "DBA_POLICY_ATTRIBUTES"
- "USER_POLICY_ATTRIBUTES"

4.22 ALL_POLICY_CONTEXTS

ALL_POLICY_CONTEXTS describes the driving contexts defined for the synonyms, tables, and views accessible to the current user.

Related Views

- DBA_POLICY_CONTEXTS describes all driving contexts in the database.
- USER_POLICY_CONTEXTS describes the driving contexts defined for the synonyms, tables, and views owned by the current user. This view does not display the OBJECT_OWNER column.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the synonym, table, or view
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the synonym, table, or view
NAMESPACE	VARCHAR2(128)	NOT NULL	Namespace of the driving context
ATTRIBUTE	VARCHAR2(128)	NOT NULL	Attribute of the driving context
COMMON	VARCHAR2(3)		Indicates whether the policy context is applied and enforced in all application PDBs (YES) or only in the local PDB (NO)
INHERITED	VARCHAR2(3)		Indicates whether the policy context is inherited from the root (YES) or not (NO)

See Also:

- "DBA_POLICY_CONTEXTS"
- "USER_POLICY_CONTEXTS"

4.23 ALL_POLICY_GROUPS

ALL_POLICY_GROUPS describes the policy groups defined for the synonyms, tables, and views accessible to the current user.

Related Views

- DBA_POLICY_GROUPS describes all policy groups in the database.
- USER_POLICY_GROUPS describes the policy groups defined for the synonyms, tables, and views owned by the current user. This view does not display the OBJECT_OWNER column.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)		Owner of the synonym, table, or view
OBJECT_NAME	VARCHAR2(128)		Name of the synonym, table, or view
POLICY_GROUP	VARCHAR2(128)		Name of the policy group
COMMON	VARCHAR2(3)		Indicates whether the policy group is applied and enforced in all application PDBs (YES) or only in the local PDB (NO)
INHERITED	VARCHAR2(3)		Indicates whether the policy group is inherited from the root (YES) or not (NO)

See Also:

- "DBA_POLICY_GROUPS"
- "USER_POLICY_GROUPS"

4.24 ALL_PROCEDURES

ALL_PROCEDURES lists all functions and procedures that are accessible to the current user, along with associated properties. For example, ALL_PROCEDURES indicates whether or not a function is pipelined, parallel enabled or an aggregate function. If a function is pipelined or an aggregate function, the associated implementation type (if any) is also identified.

Related Views

- DBA_PROCEDURES lists all functions and procedures available in the database, along with associated properties.
- USER_PROCEDURES lists all functions and procedures owned by the current user, along with associated properties. It does not contain the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the procedure

Column	Datatype	NULL	Description
OBJECT_NAME	VARCHAR2(128)		Name of the object: top-level function, procedure, or package name
PROCEDURE_NAME	VARCHAR2(128)		Name of the procedure
OBJECT_ID	NUMBER		Object number of the object
SUBPROGRAM_ID	NUMBER		Unique subprogram identifier
OVERLOAD	VARCHAR2(40)		Overload unique identifier
OBJECT_TYPE	VARCHAR2(13)		The typename of the object
AGGREGATE	VARCHAR2(3)		Indicates whether the procedure is an aggregate function (YES) or not (NO)
PIPELINED	VARCHAR2(3)		Indicates whether the procedure is a pipelined table function (YES) or not (NO)
IMPLTYPEOWNER	VARCHAR2(128)		Owner of the implementation type, if any
IMPLTYPENAME	VARCHAR2(128)		Name of the implementation type, if any
PARALLEL	VARCHAR2(3)		Indicates whether the procedure or function is parallel-enabled (YES) or not (NO)
INTERFACE	VARCHAR2(3)		YES, if the procedure/function is a table function implemented using the ODCI interface; otherwise NO
DETERMINISTIC	VARCHAR2(3)		YES, if the procedure/function is declared to be deterministic; otherwise NO
AUTHID	VARCHAR2(12)		Indicates whether the procedure/function is declared to execute as DEFINER or CURRENT_USER (invoker)
RESULT_CACHE	VARCHAR2(3)		Indicates whether the function is result–cached (YES) or not (NO)
ORIGIN_CON_ID	VARCHAR2(256)		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)
POLYMORPHIC	VARCHAR2(5)		The type of polymorphic table function: • ROW • TABLE • LEAF • NULL
SQL_MACRO	VARCHAR2(6)		Indicates whether the procedure is a SQL macro. Possible values: • SCALAR: The procedure is a SQL macro for a scalar expression • TABLE: The procedure is a SQL macro for a table expression • NULL: The procedure is not a SQL macro
BLOCKCHAIN	VARCHAR2(3)		For internal use only
BLOCKCHAIN_MANDATORY_VOTES	VARCHAR2(4000)		For internal use only

> **See Also:**
>
> - "DBA_PROCEDURES"
> - "USER_PROCEDURES"
> - "ALL_ARGUMENTS" for information about the arguments of the functions and procedures that are accessible to the current user

4.25 ALL_PROPAGATION

ALL_PROPAGATION displays information about the propagations that have a source queue accessible to the current user.

Related View

DBA_PROPAGATION displays information about all propagations in the database.

Column	Datatype	NULL	Description
PROPAGATION_NAME	VARCHAR2(128)	NOT NULL	Name of the propagation
SOURCE_QUEUE_OWNER	VARCHAR2(128)		Owner of the source queue of the propagation
SOURCE_QUEUE_NAME	VARCHAR2(128)		Name of the source queue of the propagation
DESTINATION_QUEUE_OWNER	VARCHAR2(128)		Owner of the destination queue of the propagation
DESTINATION_QUEUE_NAME	VARCHAR2(128)		Name of the destination queue of the propagation
DESTINATION_DBLINK	VARCHAR2(128)		Database link to propagate events from the source queue to the destination queue
RULE_SET_OWNER	VARCHAR2(128)		Owner of the propagation positive rule set
RULE_SET_NAME	VARCHAR2(128)		Name of the propagation positive rule set
NEGATIVE_RULE_SET_OWNER	VARCHAR2(128)		Owner of the propagation negative rule set
NEGATIVE_RULE_SET_NAME	VARCHAR2(128)		Name of the propagation negative rule set
QUEUE_TO_QUEUE	VARCHAR2(5)		Indicates whether the propagation is a queue-to-queue propagation (TRUE) or not (FALSE). A queue-to-queue propagation always has its own exclusive propagation job to propagate messages from the source queue to the destination queue.
STATUS	VARCHAR2(8)		Status of the propagation: • DISABLED • ENABLED • ABORTED
ERROR_MESSAGE	VARCHAR2(4000)		Error message last encountered by propagation
ERROR_DATE	DATE		Time that propagation last encountered an error
ORIGINAL_PROPAGATION_NAME	VARCHAR2(128)		Original propagation from which the propagation is cloned
ORIGINAL_SOURCE_QUEUE_OWNER	VARCHAR2(128)		Source queue owner of the original propagation

Column	Datatype	NULL	Description
ORIGINAL_SOURCE_QUEUE_NAME	VARCHAR2(128)		Source queue name of the original propagation
ACKED_SCN	NUMBER		Acknowledged SCN of the subscribers of captured messages in the destination queue for the propagation
AUTO_MERGE_THRESHOLD	NUMBER		Merge threshold value for merging the propagation back to the original source queue

See Also:

"DBA_PROPAGATION"

4.26 ALL_PROPERTY_GRAPHS

ALL_PROPERTY_GRAPHS describes the property graphs accessible to the current user.

Related Views

- DBA_PROPERTY_GRAPHS describes all property graphs in the database.
- USER_PROPERTY_GRAPHS describes the property graphs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the property graph
GRAPH_NAME	VARCHAR2(128)	NOT NULL	Name of the property graph
GRAPH_MODE	VARCHAR2(8)		Mode of the property graph (ENFORCED or TRUSTED)
ALLOWS_MIXED_TYPES	VARCHAR2(3)		Indicates whether mixed property types are allowed in the property graph (YES) or not (NO)
INMEMORY	VARCHAR2(3)		Indicates whether the property graph is enabled for the In-Memory Column Store (YES) or not (NO)

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_PROPERTY_GRAPHS"
- "USER_PROPERTY_GRAPHS"

4.27 ALL_QUEUE_EVENT_STREAMS

ALL_QUEUE_EVENT_STREAMS describes the Transactional Event Queue (TxEventQ) event streams accessible to the current user.

Related Views

- DBA_QUEUE_EVENT_STREAMS describes all TxEventQ event streams in the database.
- USER_QUEUE_EVENT_STREAMS describes the TxEventQ event streams owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the queue
NAME	VARCHAR2(128)	NOT NULL	Name of the queue
QUEUE_ID	NUMBER	NOT NULL	Queue ID
BASE_QUEUE_ID	NUMBER		If the queue is an exception queue, then this column displays the base queue ID
EVENT_STREAM_ID	NUMBER	NOT NULL	Event stream ID
DELAY_EVENT_STREAM_ID	NUMBER		Delay event stream ID
ENQUEUE_INSTANCE	NUMBER	NOT NULL	Event stream enqueue instance ID
EVENT_STREAM_TYPE	VARCHAR2(10)		Type of event stream. Possible values: • VOLATILE • PERSISTENT

See Also:

- "DBA_QUEUE_EVENT_STREAMS"
- "USER_QUEUE_EVENT_STREAMS"
- *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Transactional Event Queues and Advanced Queuing

4.28 ALL_QUEUE_SCHEDULES

ALL_QUEUE_SCHEDULES describes the propagation schedules whose source queues are accessible to the current user.

Related Views

- DBA_QUEUE_SCHEDULES describes all propagation schedules in the database.
- USER_QUEUE_SCHEDULES describes the propagation schedules whose source queues are owned by the current user. This view does not display the SCHEMA column.

Column	Datatype	NULL	Description
SCHEMA	VARCHAR2(128)		Source queue owner
QNAME	VARCHAR2(128)		Source queue name
DESTINATION	VARCHAR2(395)		Destination name, currently limited to be a DBLINK name
START_DATE	TIMESTAMP(6) WITH TIME ZONE		Date at which to start propagation
START_TIME	VARCHAR2(8)		Time of day at which to start propagation (in HH:MI:SS format)
PROPAGATION_WINDOW	NUMBER		Duration for the propagation window (in seconds)
NEXT_TIME	VARCHAR2(4000)		Function to compute the start of the next propagation window
LATENCY	NUMBER		Maximum wait time to propagate a message during the propagation window
SCHEDULE_DISABLED	VARCHAR2(1)		Indicates whether the schedule is disabled (Y) or enabled (N). If disabled, then the schedule will not be executed.
PROCESS_NAME	VARCHAR2(4)		Name of the process executing the schedule; NULL if not currently executing
SESSION_ID	VARCHAR2(82)		Session ID and session serial number of the job executing this schedule (SID, SERIAL#); NULL if not currently executing
INSTANCE	NUMBER		Cluster database instance number executing the schedule
LAST_RUN_DATE	TIMESTAMP(6) WITH TIME ZONE		Date of the last successful execution
LAST_RUN_TIME	VARCHAR2(8)		Time of day of the last successful execution (in HH:MI:SS format)
CURRENT_START_DATE	TIMESTAMP(6) WITH TIME ZONE		Date at which the current window of this schedule was started
CURRENT_START_TIME	VARCHAR2(8)		Time of day at which the current window of this schedule was started (in HH:MI:SS format)
NEXT_RUN_DATE	TIMESTAMP(6) WITH TIME ZONE		Date at which the next window of this schedule will be started
NEXT_RUN_TIME	VARCHAR2(8)		Time of day at which the next window of this schedule will be started (in HH:MI:SS format)
TOTAL_TIME	NUMBER		Total time spent by the system in executing this schedule (in seconds)
TOTAL_NUMBER	NUMBER		Total number of messages propagated in this schedule
TOTAL_BYTES	NUMBER		Total number of bytes propagated in this schedule
MAX_NUMBER	NUMBER		Maximum number of messages propagated in a propagation window
MAX_BYTES	NUMBER		Maximum number of bytes propagated in a propagation window
AVG_NUMBER	NUMBER		Average number of messages propagated in a propagation window

Column	Datatype	NULL	Description
AVG_SIZE	NUMBER		Average size of a propagated message (in bytes)
AVG_TIME	NUMBER		Average time to propagate a message (in seconds)
FAILURES	NUMBER		Number of consecutive times schedule execution has failed, if any. After 16 consecutive failures, a propagation job becomes disabled automatically.
LAST_ERROR_DATE	DATE		Date of the last unsuccessful execution
LAST_ERROR_TIME	VARCHAR2(8)		Time of day of the last unsuccessful execution (in HH:MI:SS format)
LAST_ERROR_MSG	VARCHAR2(4000)		Error number and error message text of the last unsuccessful execution
MESSAGE_DELIVERY_MODE	VARCHAR2(10)		Message delivery mode: • PERSISTENT • BUFFERED
ELAPSED_DEQUEUE_TIME	NUMBER		Elapsed dequeue time (in hundredths of a second)
ELAPSED_PICKLE_TIME	NUMBER		Elapsed pickle time (time taken to linearize a logical change record (LCR) into a stream of bytes that can be sent over the network) (in hundredths of a second)
JOB_NAME	VARCHAR2(128)		Name of the Scheduler job

See Also:

- "DBA_QUEUE_SCHEDULES"
- "USER_QUEUE_SCHEDULES"

4.29 ALL_QUEUE_SUBSCRIBERS

ALL_QUEUE_SUBSCRIBERS displays the list of subscribers that the current user has privilege to dequeue from.

Related Views

- DBA_QUEUE_SUBSCRIBERS displays the list of subscribers on all queues in the database.
- USER_QUEUE_SUBSCRIBERS displays the list of subscribers on queues that are under the current user's schema. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the queue
QUEUE_NAME	VARCHAR2(128)	NOT NULL	Name of the queue
QUEUE_TABLE	VARCHAR2(128)	NOT NULL	Name of the queue table on which the queue is defined

Column	Datatype	NULL	Description
CONSUMER_NAME	VARCHAR2(512)		Name of the subscriber
ADDRESS	VARCHAR2(1024)		Address of the subscriber
PROTOCOL	NUMBER		Protocol of the subscriber
TRANSFORMATION	VARCHAR2(61)		Transformation for the subscriber
RULE	CLOB		Rule condition for the subscriber
DELIVERY_MODE	VARCHAR2(22)		Message delivery mode for the subscriber: • PERSISTENT • BUFFERED • PERSISTENT_OR_BUFFERED
IF_NONDURABLE_SUBSCRIBER	VARCHAR2(3)		Indicates whether the subscriber is a non-durable subscriber (YES) or not (NO)
QUEUE_TO_QUEUE	VARCHAR2(5)		Indicates whether the subscriber is a queue-to-queue subscriber (TRUE) or not (FALSE)
SUBSCRIBER_ID	NUMBER		ID of the subscriber
POS_BITMAP	NUMBER		Position of the subscriber in the bitmap

See Also:

- "DBA_QUEUE_SUBSCRIBERS"
- "USER_QUEUE_SUBSCRIBERS"

4.30 ALL_QUEUE_TABLES

ALL_QUEUE_TABLES describes the queues in the queue tables accessible to the current user.

Related Views

- DBA_QUEUE_TABLES describes the queues in all queue tables in the database.
- USER_QUEUE_TABLES describes the queues in the queue tables created in the current user's schema. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the queue table
QUEUE_TABLE	VARCHAR2(128)		Name of the queue table
TYPE	VARCHAR2(9)		Type of user data: • RAW - Raw type • OBJECT - User-defined object type • VARIANT - Variant type (for internal use only)
OBJECT_TYPE	VARCHAR2(257)		Object type of the payload when TYPE is OBJECT
SORT_ORDER	VARCHAR2(22)		User-specified sort order
RECIPIENTS	VARCHAR2(8)		SINGLE or MULTIPLE recipients

Column	Datatype	NULL	Description
MESSAGE_GROUPING	VARCHAR2(13)		NONE or TRANSACTIONAL
REPLICATION_MODE	VARCHAR2(22)		Indicates whether the queue tables are enabled for replication through Oracle GoldenGate. If the queue tables are replicated, these values appear in the column: • REPLICATED_SOURCE: This value is displayed for a source queue table. • REPLICATED_DESTINATION: This value is displayed for a destination queue table. If replication is not enabled on the queue tables, then this column is empty.
COMPATIBLE	VARCHAR2(6)		Lowest release level which the queue table is compatible with (for example, 8.0.3)
PRIMARY_INSTANCE	NUMBER		Indicates the instance number of the instance which is the primary owner of the queue table. A value of 0 indicates that there is no primary owner.
SECONDARY_INSTANCE	NUMBER		Indicates the instance number of the instance which is the secondary owner of the queue table. This instance becomes the owner of the queue table if the primary owner goes down. A value of 0 indicates that there is no secondary owner.
OWNER_INSTANCE	NUMBER		Instance number of the instance which currently owns the queue table
USER_COMMENT	VARCHAR2(50)		Comment supplied by the user
SECURE	VARCHAR2(3)		Indicates whether the queue table is secure (YES) or not (NO)

See Also:

- "DBA_QUEUE_TABLES"
- "USER_QUEUE_TABLES"
- *Oracle Database Advanced Queuing User's Guide* for more information Advanced Queuing

4.31 ALL_QUEUES

ALL_QUEUES describes all queues on which the current user has enqueue or dequeue privileges. If the user has any Advanced Queuing system privileges, like MANAGE ANY QUEUE, ENQUEUE ANY QUEUE or DEQUEUE ANY QUEUE, then this view describes all queues in the database.

Related Views

- DBA_QUEUES describes all queues in the database.

- USER_QUEUES describes the operational characteristics of every queue owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the queue
NAME	VARCHAR2(128)	NOT NULL	Name of the queue
QUEUE_TABLE	VARCHAR2(128)	NOT NULL	Name of the table the queue data resides in
QID	NUMBER	NOT NULL	Object number of the queue
QUEUE_TYPE	VARCHAR2(20)		Type of the queue. Possible values: • EXCEPTION_QUEUE • NON_PERSISTENT_QUEUE • NORMAL_QUEUE
MAX_RETRIES	NUMBER		Maximum number of retries allowed when dequeuing from the queue
RETRY_DELAY	NUMBER		Time interval between retries
ENQUEUE_ENABLED	VARCHAR2(7)		Indicates whether the queue is enabled for enqueue (YES) or not (NO)
DEQUEUE_ENABLED	VARCHAR2(7)		Indicates whether the queue is enabled for dequeue (YES) or not (NO)
RETENTION	VARCHAR2(40)		Time interval (in seconds) processed messages are retained in the queue, or FOREVER
USER_COMMENT	VARCHAR2(50)		User specified comment
NETWORK_NAME	VARCHAR2(512)		Network name
SHARDED	VARCHAR2(5)		TRUE if queue is sharded, FALSE otherwise
QUEUE_CATEGORY	VARCHAR2(25)		Queue category. Possible values: • Classic Queue • Sharded Queue • Transactional Event Queue
RECIPIENTS	VARCHAR2(8)		SINGLE or MULTIPLE recipients

See Also:

- "DBA_QUEUES"
- "USER_QUEUES"
- *Oracle Database Advanced Queuing User's Guide* for more information Advanced Queuing

4.32 ALL_REFRESH

ALL_REFRESH describes all the refresh groups accessible to the current user.

Related Views

- DBA_REFRESH describes all refresh groups in the database.

- USER_REFRESH describes all refresh groups owned by the current user.

Column	Datatype	NULL	Description
ROWNER	VARCHAR2(128)	NOT NULL	Owner of the refresh group
RNAME	VARCHAR2(128)	NOT NULL	Name of the refresh group
REFGROUP	NUMBER		Internal identifier of the refresh group
IMPLICIT_DESTROY	VARCHAR2(1)		Indicates whether the refresh group is destroyed when its last item is subtracted (Y) or not (N)
PUSH_DEFERRED_RPC	VARCHAR2(1)		Indicates whether changes are pushed from the snapshot to the master before refresh (Y) or not (N)
REFRESH_AFTER _ERRORS	VARCHAR2(1)		Indicates whether to proceed with refresh despite errors when pushing deferred RPCs (Y) or not (N)
ROLLBACK_SEG	VARCHAR2(128)		Name of the rollback segment to use while refreshing
JOB	NUMBER		Identifier of the job used to refresh the group automatically
NEXT_DATE	DATE		Date that this job will next be refreshed automatically, if not broken
INTERVAL	VARCHAR2(200)		A date function used to compute the next NEXT_DATE
BROKEN	VARCHAR2(1)		Indicates whether the job is broken and will never be run (Y) or not (N)
PURGE_OPTION	NUMBER(38)		Method for purging the transaction queue after each push (1 indicates quick purge option; 2 indicates precise purge option)
PARALLELISM	NUMBER(38)		Level of parallelism for transaction propagation
HEAP_SIZE	NUMBER(38)		Size of the heap
JOB_NAME	VARCHAR2(128)		The name of the job used to automatically refresh the group

See Also:

- "DBA_REFRESH"
- "USER_REFRESH"

4.33 ALL_REFRESH_CHILDREN

ALL_REFRESH_CHILDREN describes all the objects in refresh groups that are accessible to the current user.

Related Views

- DBA_REFRESH_CHILDREN describes the objects in all refresh groups in the database.
- USER_REFRESH_CHILDREN describes the objects in all refresh groups owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object in the refresh group
NAME	VARCHAR2(128)	NOT NULL	Name of the object in the refresh group
TYPE	VARCHAR2(128)		Type of the object in the refresh group
ROWNER	VARCHAR2(128)	NOT NULL	Owner of the refresh group
RNAME	VARCHAR2(128)	NOT NULL	Name of the refresh group
REFGROUP	NUMBER		Internal identifier of the refresh group
IMPLICIT_DESTROY	VARCHAR2(1)		Indicates whether the refresh group is destroyed when its last item is subtracted (Y) or not (N)
PUSH_DEFERRED_RPC	VARCHAR2(1)		Indicates whether changes are pushed from the snapshot to the master before refresh (Y) or not (N)
REFRESH_AFTER _ERRORS	VARCHAR2(1)		Indicates whether to proceed with refresh despite errors when pushing deferred RPCs (Y) or not (N)
ROLLBACK_SEG	VARCHAR2(128)		Name of the rollback segment to use while refreshing
JOB	NUMBER		Identifier of the job used to refresh the group automatically
NEXT_DATE	DATE		Date that this job will next be refreshed automatically, if not broken
INTERVAL	VARCHAR2(200)		A date function used to compute the next NEXT_DATE
BROKEN	VARCHAR2(1)		Indicates whether the job is broken and will never be run (Y) or not (N)
PURGE_OPTION	NUMBER(38)		Method for purging the transaction queue after each push. 1 indicates quick purge option; 2 indicates precise purge option
PARALLELISM	NUMBER(38)		Level of parallelism for transaction propagation
HEAP_SIZE	NUMBER(38)		Size of the heap
JOB_NAME	VARCHAR2(128)		The name of the job used to automatically refresh the group

See Also:

- "DBA_REFRESH_CHILDREN"
- "USER_REFRESH_CHILDREN"

4.34 ALL_REFRESH_DEPENDENCIES

ALL_REFRESH_DEPENDENCIES displays the names of the dependent detail or container tables of all the materialized views in the current schema.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2(128)	NOT NULL	Table name, unique within this schema
PARENT_OBJECT_TYPE	CHAR(17)		MATERIALIZED VIEW
OLDEST_REFRESH_SCN	NUMBER		Minimum SCN of any summary or materialized view that has TABLE_NAME as a detail table
OLDEST_REFRESH_DATE	DATE		SYSDATE when last refreshed

4.35 ALL_REFS

ALL_REFS describes the REF columns and REF attributes in object type columns accessible to the current user.

Related Views

- DBA_REFS describes all REF columns and REF attributes in the database.
- USER_REFS describes the REF columns and REF attributes in object type columns owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
COLUMN_NAME	VARCHAR2(4000)		Name of the REF column or attribute. If it is not a top-level attribute, the value of COLUMN_NAME should be a path name starting with the column name.
WITH_ROWID	VARCHAR2(3)		Indicates whether the REF value is stored with ROWID (YES) or not (NO)
IS_SCOPED	VARCHAR2(3)		Indicates whether the REF column is scoped (YES) or not (NO)
SCOPE_TABLE_OWNER	VARCHAR2(128)		Owner of the scope table, if it exists and is accessible by the user
SCOPE_TABLE_NAME	VARCHAR2(128)		Name of the scope table, if it exists and is accessible by the user
OBJECT_ID_TYPE	VARCHAR2(33)		Indicates whether the object ID (OID) is USER-DEFINED or SYSTEM GENERATED

See Also:

- "DBA_REFS"
- "USER_REFS"

4.36 ALL_REGISTERED_MVIEWS

ALL_REGISTERED_MVIEWS describes all registered materialized views (registered at a master site or a master materialized view site) accessible to the current user.

A materialized view created with the BUILD DEFERRED option of the CREATE MATERIALIZED VIEW statement is only registered with ALL_REGISTERED_MVIEWS if that materialized view has been completely refreshed at least once.

Related Views

- DBA_REGISTERED_MVIEWS describes all registered materialized views in the database.
- USER_REGISTERED_MVIEWS describes all registered materialized views owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
MVIEW_SITE	VARCHAR2(128)	NOT NULL	Global name of the materialized view site
CAN_USE_LOG	VARCHAR2(3)		Indicates whether the materialized view can use a materialized view log (YES) or the materialized view is too complex to use a log (NO)
UPDATABLE	VARCHAR2(3)		Indicates whether the materialized view is updatable (YES) or not and the materialized view is read only (NO)
REFRESH_METHOD	VARCHAR2(11)		Indicates whether the materialized view uses primary key (PRIMARY KEY), rowids (ROWID), or object identifiers (OBJECT ID) for fast refresh
MVIEW_ID	NUMBER(38)		Identifier for the materialized view used by the masters for fast refresh
VERSION	VARCHAR2(26)		Oracle version of the materialized view **Note:** Oracle Database materialized views show ORACLE 8 MATERIALIZED VIEW.
QUERY_TXT	LONG		Query that defines the materialized view

See Also:

- "DBA_REGISTERED_MVIEWS"
- "USER_REGISTERED_MVIEWS"

4.37 ALL_REGISTRY_BANNERS

ALL_REGISTRY_BANNERS displays the valid components loaded into the database.

Column	Datatype	NULL	Description
BANNER	VARCHAR2(80)		Component display banner
BANNER_FULL	VARCHAR2(80)		Component display banner with full version

4.38 ALL_REPL_DBNAME_MAPPING

ALL_REPL_DBNAME_MAPPING provides details about the database name mapping in replication for the current user.

Related View

DBA_REPL_DBNAME_MAPPING provides details about the database name mapping in replication.

Column	Datatype	NULL	Description
SOURCE_ROOT_NAME	VARCHAR2(128)		The fully qualified global name of the root in a multitenant container database (CDB) where the changes originated
SOURCE_DATABASE_NAME	VARCHAR2(128)		The fully qualified global name of the pluggable database (PDB) where the changes originated
SOURCE_CONTAINER_NAME	VARCHAR2(128)		The container name of the database where the changes originated

> **See Also:**
>
> "DBA_REPL_DBNAME_MAPPING"

4.39 ALL_REPLICATION_PROCESS_EVENTS

ALL_REPLICATION_PROCESS_EVENTS provides information about the replication processes events accessible to the current user.

Related View

DBA_REPLICATION_PROCESS_EVENTS provides information about the replication processes events in the database.

Column	Datatype	NULL	Description
STREAMS_TYPE	VARCHAR2(10)		Streams type: • XStream • GoldenGate

Column	Datatype	NULL	Description
PROCESS_TYPE	VARCHAR2(27)		Process type: • Capture • Capture server • Apply Coordinator • Apply Server • Apply Network Receiver • Apply Reader • Apply Hash server
STREAMS_NAME	VARCHAR2(128)	NOT NULL	Streams name
EVENT_NAME	VARCHAR2(128)		Event name: • START • STOP • ABORT • CREATE • DROP • PARAMETER CHANGE • HANDLER CREATE • HANDLER REMOVE • ALTER
DESCRIPTION	VARCHAR2(2000)		Event description
EVENT_TIME	TIMESTAMP(6)		Time when the event occurred
ERROR_NUMBER	NUMBER		Error number (valid when event is Error)
ERROR_MESSAGE	VARCHAR2(2000)		Error Message (valid when event is an error)

See Also:

"DBA_REPLICATION_PROCESS_EVENTS"

4.40 ALL_REWRITE_EQUIVALENCES

ALL_REWRITE_EQUIVALENCES describes the rewrite equivalences accessible to the current user.

Related Views

- DBA_REWRITE_EQUIVALENCES describes all rewrite equivalences in the database.
- USER_REWRITE_EQUIVALENCES describes the rewrite equivalences owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the rewrite equivalence
NAME	VARCHAR2(128)	NOT NULL	Name of the rewrite equivalence
SOURCE_STMT	CLOB		Source statement of the rewrite equivalence
DESTINATION_STMT	CLOB		Destination of the rewrite equivalence

Column	Datatype	NULL	Description
REWRITE_MODE	VARCHAR2(10)		Rewrite mode of the rewrite equivalence: • DISABLED • TEXT_MATCH • GENERAL • RECURSIVE

See Also:

- "DBA_REWRITE_EQUIVALENCES"
- "USER_REWRITE_EQUIVALENCES"

4.41 ALL_RULE_SET_RULES

ALL_RULE_SET_RULES describes the rules in the rule sets accessible to the current user.

Related Views

- DBA_RULE_SET_RULES describes the rules in all rule sets in the database.
- USER_RULE_SET_RULES describes the rules in the rule sets owned by the current user. This view does not display the RULE_SET_OWNER column.

Column	Datatype	NULL	Description
RULE_SET_OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule set
RULE_SET_NAME	VARCHAR2(128)	NOT NULL	Name of the rule set
RULE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2(128)	NOT NULL	Name of the rule
RULE_SET_RULE_ENABLED	VARCHAR2(8)		Indicates whether the rule is enabled in the rule set (ENABLED) or not (DISABLED)
RULE_SET_RULE_EVAL_CTX_OWNER	VARCHAR2(128)		Owner of the evaluation context specified when the rule was added to the rule set, if any
RULE_SET_RULE_EVAL_CTX_NAME	VARCHAR2(128)		Name of the evaluation context specified when the rule was added to the rule set, if any
RULE_SET_RULE_COMMENT	VARCHAR2(4000)		Comment specified when the rule was added to the rule set, if any

See Also:

- "DBA_RULE_SET_RULES"
- "USER_RULE_SET_RULES"

4.42 ALL_RULE_SETS

ALL_RULE_SETS describes the rule sets accessible to the current user.

Related Views

- DBA_RULE_SETS describes all rule sets in the database.
- USER_RULE_SETS describes the rule sets owned by the current user. This view does not display the RULE_SET_OWNER column.

Column	Datatype	NULL	Description
RULE_SET_OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule set
RULE_SET_NAME	VARCHAR2(128)	NOT NULL	Name of the rule set
RULE_SET_EVAL_CONTEXT_OWNER	VARCHAR2(128)		Owner of the evaluation context associated with the rule set, if any
RULE_SET_EVAL_CONTEXT_NAME	VARCHAR2(128)		Name of the evaluation context associated with the rule set, if any
RULE_SET_COMMENT	VARCHAR2(4000)		Comment specified with the rule set, if any

See Also:

- "DBA_RULE_SETS"
- "USER_RULE_SETS"

4.43 ALL_RULES

ALL_RULES describes the rules accessible to the current user.

Related Views

- DBA_RULES describes all rules in the database.
- USER_RULES describes the rules owned by the current user. This view does not display the RULE_OWNER column.

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2(128)	NOT NULL	Name of the rule
RULE_CONDITION	CLOB		Expressions and operators that constitute the rule condition
RULE_EVALUATION_CONTEXT_OWNER	VARCHAR2(128)		Owner of the evaluation context associated with the rule, if any
RULE_EVALUATION_CONTEXT_NAME	VARCHAR2(128)		Name of the evaluation context associated with the rule, if any

Column	Datatype	NULL	Description
RULE_ACTION_CONTEXT	RE$NV_LIST		Action context associated with the rule, if any
RULE_COMMENT	VARCHAR2(4000)		Comment specified with the rule, if any

See Also:

- "DBA_RULES"
- "USER_RULES"

4.44 ALL_SAGA_BROKERS

ALL_SAGA_BROKERS displays the saga brokers accessible to the current user.

Related Views

- DBA_SAGA_BROKERS displays all saga brokers in the database.
- USER_SAGA_BROKERS displays the saga brokers owned by the current user.

Column	Datatype	NULL	Description
ID	RAW(16)	NOT NULL	ID of the saga broker
NAME	VARCHAR2(128)	NOT NULL	Name of the saga broker
OWNER	VARCHAR2(128)	NOT NULL	Owner of the saga broker
BROKER_TOPIC	VARCHAR2(128)		Name of the queue used by the broker
REMOTE	VARCHAR2(50)		Indicates whether the saga broker is remote (TRUE) or not (FALSE)
VERSION	NUMBER	NOT NULL	Saga broker version
QUEUE_PARTITIONS	NUMBER	NOT NULL	Controls the degree of parallelism of the broker • For Classic Queue based brokers, the number of queues created • For TxEvent Queue based brokers, the number of internal partitions
QUEUE_TYPE	VARCHAR2(13)		Saga topic type: • Classic Queue • TxEvent Queue

Note:

This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_SAGA_BROKERS"
> - "USER_SAGA_BROKERS"

4.45 ALL_SAGA_DETAILS

ALL_SAGA_DETAILS displays details for sagas accessible to the current user.

Related Views

- DBA_SAGA_DETAILS displays details for all sagas in the database.
- USER_SAGA_DETAILS displays details for sagas owned by the current user.

Column	Datatype	NULL	Description
ID	RAW(16)	NOT NULL	Saga ID
PARTICIPANT	VARCHAR2(128)	NOT NULL	Name of the saga participant
SOURCE	VARCHAR2(128)		Name of the saga participant responsible for the event
TARGET	VARCHAR2(128)		Name of the saga participant that is the target for the event
MESSAGE	VARCHAR2(2048)		Short description of the event
TYPE	NUMBER		Type of event
QUEUE_TYPE	NUMBER	NOT NULL	Type of saga queue
CREATED_TIME	TIMESTAMP(6) WITH TIME ZONE		Time at which the event was processed
MESSAGE_ID	RAW(16)		Internal identifier of the message
CORRELATION	VARCHAR2(128)		Correlation identifier

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_SAGA_DETAILS"
> - "USER_SAGA_DETAILS"

4.46 ALL_SAGA_ERRORS

ALL_SAGA_ERRORS describes errors generated by the sagas accessible to the current user.

This view displays sagas that were either initiated in the current PDB or joined by participants in the current PDB.

Related Views

- DBA_INCOMPLETE_SAGAS describes errors generated by all sagas in the database.
- USER_SAGA_ERRORS describes errors generated by the sagas owned by the current user.

Column	Datatype	NULL	Description
SAGA_ID	RAW(16)		Saga ID
PARTICIPANT	VARCHAR2(128)		Name of the saga participant
SQL_ERROR	VARCHAR2(200)		SQL error
SQL_CODE	VARCHAR2(7)		SQL error code
ERROR_TIME	VARCHAR2(19)		Time at which the error occurred

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_SAGA_ERRORS"
> - "USER_SAGA_ERRORS"

4.47 ALL_SAGA_FINALIZATION

ALL_SAGA_FINALIZATION displays information about pending finalization actions for sagas accessible to the current user.

This view displays one row for each unique reservable table updated as part of a participant transaction for sagas that were either initiated in the current PDB or joined by participants in the current PDB.

Related Views

- DBA_SAGA_FINALIZATION displays information about pending finalization actions for all sagas in the database.

- `USER_SAGA_FINALIZATION` displays information about pending finalization actions for sagas owned by the current user.

Column	Datatype	NULL	Description
`SAGA_ID`	`RAW(16)`	`NOT NULL`	Saga ID
`PARTICIPANT`	`VARCHAR2(128)`		Name of the saga participant
`TXN_ID`	`VARCHAR2(32)`		ID of the reservable column transaction in the saga
`RESERVABLE_SCHEMA`	`VARCHAR2(128)`	`NOT NULL`	Schema of the reservable column table involved in the transaction
`RESERVABLE_TABLE`	`VARCHAR2(128)`	`NOT NULL`	Name of the reservable column table involved in the transaction
`RESERVABLE_JOURNAL`	`VARCHAR2(55)`		Name of the reservable journal table involved in the transaction
`STATUS`	`VARCHAR2(15)`		Status of the transaction: • `Initiated` - Participant transactions committed; saga not finalized • `Committed` - Saga branch committed • `Rolledback` - Saga branch rolled back • `Commit Failed` - Saga branch commit failed • `Rollback Failed` - Saga branch rollback failed

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_SAGA_FINALIZATION"
- "USER_SAGA_FINALIZATION"

4.48 ALL_SAGA_PARTICIPANT_SET

`ALL_SAGA_PARTICIPANT_SET` displays information about saga participants for sagas accessible to the current user.

Related Views

- `DBA_INCOMPLETE_SAGAS` displays information about saga participants for all sagas in the database.
- `USER_SAGA_PARTICIPANT_SET` displays information about saga participants for sagas owned by the current user.

Column	Datatype	NULL	Description
ID	RAW(16)	NOT NULL	Saga ID
COORDINATOR	VARCHAR2(128)	NOT NULL	Name of the saga coordinator
PARTICIPANT	VARCHAR2(128)	NOT NULL	Name of the saga participant
STATUS	VARCHAR2(57)		Saga status: • Joined • Committed • Rolledback • Commit Failed • Rollback Failed • Rejected • Auto Committed • Auto Rolledback
JOIN_TIME	TIMESTAMP(6) WITH TIME ZONE		Join time of the saga participant
COMPLETION_TIME	TIMESTAMP(6) WITH TIME ZONE		Completion time of the saga participant

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_SAGA_PARTICIPANT_SET"
- "USER_SAGA_PARTICIPANT_SET"

4.49 ALL_SAGA_PARTICIPANTS

ALL_SAGA_PARTICIPANTS describes the saga participants accessible to the current user.

This view displays sagas that were either initiated in the current PDB or joined by participants or coordinators in the current PDB.

Related Views

- DBA_SAGA_PARTICIPANTS describes all saga participants in the database.
- USER_SAGA_PARTICIPANTS describes the saga participants owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
ID	RAW(16)	NOT NULL	ID of the saga participant

Column	Datatype	NULL	Description
NAME	VARCHAR2(128)	NOT NULL	Name of the saga participant
OWNER	VARCHAR2(128)	NOT NULL	Owner of the saga participant
BROKER_NAME	VARCHAR2(128)	NOT NULL	Name of the saga broker
TYPE	VARCHAR2(50)		Participant type: • Coordinator • Participant
COORDINATOR	VARCHAR2(128)		Name of the saga coordinator
INCOMING_TOPIC	VARCHAR2(128)	NOT NULL	Saga incoming topic
OUTGOING_TOPIC	VARCHAR2(128)	NOT NULL	Saga outgoing topic
QUEUE_PARTITIONS	NUMBER	NOT NULL	Number of saga topic partitions
QUEUE_TYPE	VARCHAR2(13)		Saga topic type: • Classic Queue • TxEvent Queue
LISTENER_COUNT	VARCHAR2(40)		Possible values: • AQ - The saga coordinator processes messages using the Advanced Queuing (AQ) notification mechanism. • AUTO - The saga coordinator processes messages using job queue processes that dequeue from the coordinator queue. This mechanism spawns a monitoring job that automatically adds and removes dequeuer jobs depending on the queue depth. • If this column displays a number value, then the value represents the number of fixed jobs that are created to process messages for the saga coordinator.
VERSION	NUMBER	NOT NULL	Saga participant version

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_SAGA_PARTICIPANTS"
- "USER_SAGA_PARTICIPANTS"

4.50 ALL_SAGA_PENDING

ALL_SAGA_PENDING describes the pending sagas accessible to the current user.

This view displays sagas that were initiated in the current PDB.

Related Views

- DBA_SAGA_PENDING describes all pending sagas in the database.
- USER_SAGA_PENDING describes the pending sagas owned by the current user.

Column	Datatype	NULL	Description
SAGA_ID	RAW(16)	NOT NULL	Saga ID
PARTICIPANT	VARCHAR2(128)		Name of the saga participant
TXN_ID	VARCHAR2(16)		ID of the reservable column transaction in the saga
SCHEMA	VARCHAR2(128)	NOT NULL	Schema of the reservable column table involved in the transaction
RESERVABLE_TABLE	VARCHAR2(128)	NOT NULL	Name of the reservable column table involved in the transaction
RESERVABLE_JOURNAL_STATUS	VARCHAR2(12)		Status of the transaction in the reservable journal table
STATEMENT_TYPE	VARCHAR2(16)		SQL statement type (for example, UPDATE or MERGE)
OPERATION_TYPE	VARCHAR2(16)	NOT NULL	Type of saga operation (for example, commit, rollback, or timeout)
PRIMARYKEY_INFO	CLOB	NOT NULL	Primary key and its value in the row whose reservable column value was updated in this transaction
RESERVABLE_COL_INFO	CLOB	NOT NULL	Reservable column value update information in this transaction

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_SAGA_PENDING"
- "USER_SAGA_PENDING"

4.51 ALL_SAGAS

ALL_SAGAS describes the active sagas accessible to the current user.

This view displays sagas that were either initiated in the current PDB or joined by participants in the current PDB.

Related Views

- DBA_SAGAS describes all active sagas in the database.
- USER_SAGAS describes the active sagas owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
ID	RAW(16)	NOT NULL	Saga ID
INITIATOR	VARCHAR2(128)		Name of the saga initiator
IS_INITIATOR	VARCHAR2(3)		Indicates whether this participant is the saga initiator (YES) or not (NO)
COORDINATOR	VARCHAR2(128)		Name of the saga coordinator
COORDINATOR_TYPE	VARCHAR2(50)		Type of the saga coordinator: • Internal • External
OWNER	VARCHAR2(128)	NOT NULL	Owner of the saga participant
PARTICIPANT	VARCHAR2(128)	NOT NULL	Name of the saga participant
STATUS	VARCHAR2(14)		Saga status: • New • Joining • Initiated • Joined
VERSION	NUMBER	NOT NULL	Saga version
DURATION	NUMBER		Time limit for the saga (in seconds)
START_TIME	TIMESTAMP(6) WITH TIME ZONE		Saga start time

Note:

This view displays active sagas. Completed sagas are displayed in the ALL_HIST_SAGAS view.

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_SAGAS"
- "USER_SAGAS"

4.52 ALL_SCHEDULER_CHAIN_RULES

ALL_SCHEDULER_CHAIN_RULES displays information about the rules for the chains accessible to the current user (that is, those chains that the user has ALTER or EXECUTE privileges for).

Related Views

- DBA_SCHEDULER_CHAIN_RULES displays information about the rules for all chains in the database.
- USER_SCHEDULER_CHAIN_RULES displays information about the rules for the chains owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Scheduler chain that the rule is in
CHAIN_NAME	VARCHAR2(128)	NOT NULL	Name of the Scheduler chain that the rule is in
RULE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2(128)		Name of the rule
CONDITION	VARCHAR2(4000)		Boolean condition triggering the rule
ACTION	VARCHAR2(4000)		Action to be performed when the rule is triggered
COMMENTS	VARCHAR2(4000)		User-specified comments about the rule

See Also:

- "DBA_SCHEDULER_CHAIN_RULES"
- "USER_SCHEDULER_CHAIN_RULES"

4.53 ALL_SCHEDULER_CHAIN_STEPS

ALL_SCHEDULER_CHAIN_STEPS displays information about the defined steps of the chains accessible to the current user (that is, those chains that the user has ALTER or EXECUTE privileges for).

Related Views

- DBA_SCHEDULER_CHAIN_STEPS displays information about the defined steps of all chains in the database.
- USER_SCHEDULER_CHAIN_STEPS displays information about the defined steps of the chains owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Scheduler chain the step is in
CHAIN_NAME	VARCHAR2(128)	NOT NULL	Name of the Scheduler chain the step is in

Column	Datatype	NULL	Description
STEP_NAME	VARCHAR2(128)	NOT NULL	Name of the chain step
PROGRAM_OWNER	VARCHAR2(392)		Owner of the program that runs during the step
PROGRAM_NAME	VARCHAR2(392)		Name of the program that runs during the step
EVENT_SCHEDULE_OWNER	VARCHAR2(392)		Owner of the event schedule that this step waits for
EVENT_SCHEDULE_NAME	VARCHAR2(392)		Name of the event schedule that this step waits for
EVENT_QUEUE_OWNER	VARCHAR2(128)		Owner of the source queue into which the event will be raised
EVENT_QUEUE_NAME	VARCHAR2(128)		Name of the source queue into which the event will be raised
EVENT_QUEUE_AGENT	VARCHAR2(523)		Name of the AQ agent used by the user on the event source queue (for a secure queue)
EVENT_CONDITION	VARCHAR2(4000)		Boolean expression used as the subscription rule for an event on the source queue
CREDENTIAL_OWNER	VARCHAR2(128)		Owner of the credential to be used for an external step job
CREDENTIAL_NAME	VARCHAR2(128)		Name of the credential to be used for an external step job
DESTINATION	VARCHAR2(261)		Destination host on which a remote step job will run
SKIP	VARCHAR2(5)		Indicates whether the step should be skipped (TRUE) or not (FALSE)
PAUSE	VARCHAR2(5)		Indicates whether the step should be paused after running (TRUE) or not (FALSE)
PAUSE_BEFORE	VARCHAR2(5)		Indicates whether the step should be paused before running (TRUE) or not (FALSE)
RESTART_ON_RECOVERY	VARCHAR2(5)		Indicates whether the step should be restarted on database recovery (TRUE) or not (FALSE)
RESTART_ON_FAILURE	VARCHAR2(5)		Indicates whether the step should be restarted on application failure (TRUE) or not (FALSE)
STEP_TYPE	VARCHAR2(21)		Type of the step: • EVENT_SCHEDULE • INLINE_EVENT • SUBCHAIN • PROGRAM
TIMEOUT	INTERVAL DAY(3) TO SECOND(0)		Timeout for waiting on an event schedule

See Also:

- "DBA_SCHEDULER_CHAIN_STEPS"
- "USER_SCHEDULER_CHAIN_STEPS"

4.54 ALL_SCHEDULER_CHAINS

ALL_SCHEDULER_CHAINS displays information about the chains accessible to the current user (that is, those chains that the user has ALTER or EXECUTE privileges for).

Related Views

- DBA_SCHEDULER_CHAINS displays information about all chains in the database.
- USER_SCHEDULER_CHAINS displays information about the chains owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Scheduler chain
CHAIN_NAME	VARCHAR2(128)	NOT NULL	Name of the Scheduler chain
RULE_SET_OWNER	VARCHAR2(128)		Owner of the rule set describing the dependencies
RULE_SET_NAME	VARCHAR2(128)		Name of the rule set describing the dependencies
NUMBER_OF_RULES	NUMBER		Number of rules in the chain
NUMBER_OF_STEPS	NUMBER		Number of defined steps in the chain
ENABLED	VARCHAR2(5)		Indicates whether the chain is enabled (TRUE) or disabled (FALSE)
EVALUATION_INTERVAL	INTERVAL DAY(3) TO SECOND(0)		Periodic interval at which to reevaluate rules for the chain
USER_RULE_SET	VARCHAR2(5)		Indicates whether the chain uses a user-specified rule set (TRUE) or not (FALSE)
COMMENTS	VARCHAR2(4000)		Comments on the chain

See Also:

- "DBA_SCHEDULER_CHAINS"
- "USER_SCHEDULER_CHAINS"

4.55 ALL_SCHEDULER_CREDENTIALS

ALL_SCHEDULER_CREDENTIALS displays information about the credentials accessible to the current user (that is, those credentials that the user has ALTER or EXECUTE privileges for).

Note:

This view is deprecated in favor of the ALL_CREDENTIALS view. Oracle recommends that you use ALL_CREDENTIALS instead. ALL_SCHEDULER_CREDENTIALS is retained for backward compatibility only.

Related Views

- DBA_SCHEDULER_CREDENTIALS displays information about all credentials in the database.
- USER_SCHEDULER_CREDENTIALS displays information about the credentials owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Scheduler credential
CREDENTIAL_NAME	VARCHAR2(128)	NOT NULL	Name of the Scheduler credential
USERNAME	VARCHAR2(128)		Name of the user that will be used to log in to the remote database or operating system
DATABASE_ROLE	VARCHAR2(9)		For a database target, the database role to use when logging in: • SYSDBA • SYSOPER
WINDOWS_DOMAIN	VARCHAR2(30)		For a Windows target, the Windows domain to use when logging in
COMMENTS	VARCHAR2(4000)		Comments on the credential

See Also:

- "ALL_CREDENTIALS"
- "DBA_SCHEDULER_CREDENTIALS"
- "USER_SCHEDULER_CREDENTIALS"

4.56 ALL_SCHEDULER_DB_DESTS

ALL_SCHEDULER_DB_DESTS displays information about the destination objects accessible to the current user pointing to remote databases.

Related Views

- DBA_SCHEDULER_DB_DESTS displays information about all destination objects in the database pointing to remote databases.
- USER_SCHEDULER_DB_DESTS displays information about the destination objects owned by the current user pointing to remote databases. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of this destination object
DESTINATION_NAME	VARCHAR2(128)	NOT NULL	Name of this destination object
CONNECT_INFO	VARCHAR2(4000)		Connect string to connect to the remote database
AGENT	VARCHAR2(128)		Name of the agent through which the connection to the remote database is being made

Column	Datatype	NULL	Description
ENABLED	VARCHAR2(5)		Indicates whether this destination object is enabled (TRUE) or disabled (FALSE)
REFS_ENABLED	VARCHAR2(5)		Indicates whether all referenced objects are enabled (TRUE) or disabled (FALSE)
COMMENTS	VARCHAR2(4000)		Optional comment

See Also:

- "DBA_SCHEDULER_DB_DESTS"
- "USER_SCHEDULER_DB_DESTS"

4.57 ALL_SCHEDULER_DESTS

ALL_SCHEDULER_DESTS displays information about the destination objects for jobs accessible to the current user.

Related Views

- DBA_SCHEDULER_DESTS displays information about all destination objects for jobs in the database.
- USER_SCHEDULER_DESTS displays information about the destination objects for jobs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of this destination object
DESTINATION_NAME	VARCHAR2(128)	NOT NULL	Name of this destination object
DESTINATION_TYPE	VARCHAR2(8)		Type of this destination object: • EXTERNAL • DATABASE
ENABLED	VARCHAR2(5)		Indicates whether this destination object is enabled (TRUE) or disabled (FALSE)
COMMENTS	VARCHAR2(4000)		Optional comment

See Also:

- "DBA_SCHEDULER_DESTS"
- "USER_SCHEDULER_DESTS"

4.58 ALL_SCHEDULER_EXTERNAL_DESTS

ALL_SCHEDULER_EXTERNAL_DESTS displays information about the destination objects accessible to the current user pointing to remote agents.

Related View

DBA_SCHEDULER_EXTERNAL_DESTS displays information about all destination objects in the database pointing to remote agents.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of this destination object
DESTINATION_NAME	VARCHAR2(128)	NOT NULL	Name of this destination object
HOSTNAME	VARCHAR2(256)		Name or IP address of the host on which the agent is located
PORT	NUMBER		Port that the agent is listening on
IP_ADDRESS	VARCHAR2(64)		IP address of the host on which the agent is located
ENABLED	VARCHAR2(5)		Indicates whether this destination object is enabled (TRUE) or disabled (FALSE)
COMMENTS	VARCHAR2(4000)		Optional comment

> **See Also:**
>
> "DBA_SCHEDULER_EXTERNAL_DESTS"

4.59 ALL_SCHEDULER_FILE_WATCHERS

ALL_SCHEDULER_FILE_WATCHERS displays information about the Scheduler file watch requests accessible to the current user.

Related Views

- DBA_SCHEDULER_FILE_WATCHERS displays information about all Scheduler file watch requests in the database.
- USER_SCHEDULER_FILE_WATCHERS displays information about the Scheduler file watch requests owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the file watch request
FILE_WATCHER_NAME	VARCHAR2(128)	NOT NULL	Name of the file watch request
ENABLED	VARCHAR2(5)		Indicates whether this file watch request is enabled (TRUE) or disabled (FALSE)
DESTINATION_OWNER	VARCHAR2(261)		Owner of the named destination object

Column	Datatype	NULL	Description
DESTINATION	VARCHAR2(261)		Name of the destination object
DIRECTORY_PATH	VARCHAR2(4000)	NOT NULL	Name of the directory path where the file will arrive
FILE_NAME	VARCHAR2(512)	NOT NULL	Name or pattern specifying the files that need to be monitored
CREDENTIAL_OWNER	VARCHAR2(128)		Owner of the credential that should be used to authorize the file watch
CREDENTIAL_NAME	VARCHAR2(128)		Name of the credential that should be used to authorize the file watch
MIN_FILE_SIZE	NUMBER	NOT NULL	Minimum size of the file being monitored
STEADY_STATE_DURATION	INTERVAL DAY(3) TO SECOND(0)		Time to wait before concluding that the file has stopped growing
LAST_MODIFIED_TIME	TIMESTAMP(6) WITH TIME ZONE		Time at which this file watcher was last modified
COMMENTS	VARCHAR2(4000)		Comments on the file watch request

See Also:

- "DBA_SCHEDULER_FILE_WATCHERS"
- "USER_SCHEDULER_FILE_WATCHERS"

4.60 ALL_SCHEDULER_GLOBAL_ATTRIBUTE

ALL_SCHEDULER_GLOBAL_ATTRIBUTE displays the values of all scheduler attributes (for example, DEFAULT_TIMEZONE and CURRENT_OPEN_WINDOW).

Related View

DBA_SCHEDULER_GLOBAL_ATTRIBUTE displays the values of all scheduler attributes in the database.

Column	Datatype	NULL	Description
ATTRIBUTE_NAME	VARCHAR2(128)	NOT NULL	Name of the Scheduler attribute
VALUE	VARCHAR2(128)		Value of the Scheduler attribute

See Also:

"DBA_SCHEDULER_GLOBAL_ATTRIBUTE"

4.61 ALL_SCHEDULER_GROUP_MEMBERS

ALL_SCHEDULER_GROUP_MEMBERS displays information about the members of the Scheduler object groups accessible to the current user.

Related Views

- DBA_SCHEDULER_GROUP_MEMBERS displays information about the members of all Scheduler object groups in the database.
- USER_SCHEDULER_GROUP_MEMBERS displays information about the members of the Scheduler object groups owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the group
GROUP_NAME	VARCHAR2(128)	NOT NULL	Name of the group
MEMBER_NAME	VARCHAR2(523)		Name of the member of this group

See Also:

- "DBA_SCHEDULER_GROUP_MEMBERS"
- "USER_SCHEDULER_GROUP_MEMBERS"

4.62 ALL_SCHEDULER_GROUPS

ALL_SCHEDULER_GROUPS displays information about the Scheduler object groups accessible to the current user.

Related Views

- DBA_SCHEDULER_GROUPS displays information about all Scheduler object groups in the database.
- USER_SCHEDULER_GROUPS displays information about the Scheduler object groups owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the group
GROUP_NAME	VARCHAR2(128)	NOT NULL	Name of the group
GROUP_TYPE	VARCHAR2(13)		Type of object contained in the group: • WINDOW • JOB • DB_DEST • EXTERNAL_DEST

Column	Datatype	NULL	Description
ENABLED	VARCHAR2(5)		Indicates whether the group is enabled (TRUE) or disabled (FALSE)
NUMBER_OF_MEMBERS	NUMBER		Number of members in this group
COMMENTS	VARCHAR2(4000)		An optional comment about this group

See Also:

- "DBA_SCHEDULER_GROUPS"
- "USER_SCHEDULER_GROUPS"

4.63 ALL_SCHEDULER_INCOMPAT_MEMBER

ALL_SCHEDULER_INCOMPAT_MEMBER displays all Scheduler incompatibility resource objects members accessible to the current user.

Related Views

- DBA_SCHEDULER_INCOMPAT_MEMBER displays all Scheduler incompatibility resource objects members in the database.
- USER_SCHEDULER_INCOMPAT_MEMBER displays all Scheduler incompatibility resource objects members owned by the current user.

Column	Datatype	NULL	Description
INCOMPATIBILITY_OWNER	VARCHAR2(128)	NOT NULL	Owner of the incompatibility resource object containing this member
INCOMPATIBILITY_NAME	VARCHAR2(128)	NOT NULL	Name of the incompatibility resource object containing this member
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the incompatibility resource member
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the incompatibility resource member

See Also:

- "DBA_SCHEDULER_INCOMPAT_MEMBER"
- "USER_SCHEDULER_INCOMPAT_MEMBER"

4.64 ALL_SCHEDULER_INCOMPATS

ALL_SCHEDULER_INCOMPATS displays all Scheduler incompatibility resource objects accessible to the current user.

Related Views

- DBA_SCHEDULER_INCOMPATS displays all Scheduler incompatibility resource objects in the database.
- USER_SCHEDULER_INCOMPATS displays all Scheduler incompatibility resource objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the incompatibility resource object
INCOMPATIBILITY_NAME	VARCHAR2(128)	NOT NULL	Name of the incompatibility resource object
CONSTRAINT_LEVEL	VARCHAR2(13)		JOB_LEVEL or PROGRAM_LEVEL The default value JOB_LEVEL indicates that only a single job that is based on the program (or programs) mentioned in the object_name argument of the DBMS_SCHEDULER.CREATE_INCOMPATIBILITY procedure can run at one time. The value PROGRAM_LEVEL indicates that the programs are incompatible, but the jobs based on the same program are not incompatible.
ENABLED	VARCHAR2(5)		Indicates whether the incompatibility is enabled (TRUE) or not (FALSE)
JOBS_RUNNING_COUNT	NUMBER		Current number of running jobs using the incompatibility resource object
COMMENTS	VARCHAR2(256)		Comments for the resource incompatibility object

See Also:

- "DBA_SCHEDULER_INCOMPATS"
- "USER_SCHEDULER_INCOMPATS"

4.65 ALL_SCHEDULER_JOB_ARGS

ALL_SCHEDULER_JOB_ARGS displays information about the arguments of the Scheduler jobs accessible to the current user.

Related Views

- DBA_SCHEDULER_JOB_ARGS displays information about the arguments of all Scheduler jobs in the database.

- USER_SCHEDULER_JOB_ARGS displays information about the arguments of the Scheduler jobs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the job to which the argument belongs
JOB_NAME	VARCHAR2(128)		Name of the job to which the argument belongs
ARGUMENT_NAME	VARCHAR2(128)		Optional name of the argument
ARGUMENT_POSITION	NUMBER		Position of the argument in the argument list
ARGUMENT_TYPE	VARCHAR2(257)		Data type of the argument
VALUE	VARCHAR2(4000)		Value of the argument (in string format) if the argument is a string
ANYDATA_VALUE	ANYDATA		Value of the argument (in AnyData format)
OUT_ARGUMENT	VARCHAR2(5)		Reserved for future use

See Also:

- "DBA_SCHEDULER_JOB_ARGS"
- "USER_SCHEDULER_JOB_ARGS"

4.66 ALL_SCHEDULER_JOB_CLASSES

ALL_SCHEDULER_JOB_CLASSES displays information about the Scheduler job classes accessible to the current user.

Related View

DBA_SCHEDULER_JOB_CLASSES displays information about all Scheduler job classes in the database.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Scheduler job class
JOB_CLASS_NAME	VARCHAR2(128)	NOT NULL	Name of the Scheduler job class
RESOURCE_CONSUMER_GROUP	VARCHAR2(128)		Resource consumer group associated with the class
SERVICE	VARCHAR2(64)		Name of the service the class is associated with
LOGGING_LEVEL	VARCHAR2(11)		Amount of logging that will be done pertaining to the class: • OFF • RUNS • FAILED RUNS • FULL
LOG_HISTORY	NUMBER		History (in days) to maintain in the job log for the class
COMMENTS	VARCHAR2(4000)		Comments on the class

> **See Also:**
>
> "DBA_SCHEDULER_JOB_CLASSES"

4.67 ALL_SCHEDULER_JOB_DESTS

ALL_SCHEDULER_JOB_DESTS displays information about the state of the jobs accessible to the current user at each of their destinations.

Related Views

- DBA_SCHEDULER_JOB_DESTS displays information about the state of all jobs in the database at each of their destinations.
- USER_SCHEDULER_JOB_DESTS displays information about the state of the jobs owned by the current user at each of their destinations. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the Scheduler job
JOB_NAME	VARCHAR2(128)		Name of the Scheduler job
JOB_SUBNAME	VARCHAR2(128)		Subname of the Scheduler job
CREDENTIAL_OWNER	VARCHAR2(128)		Owner of the credential used for the remote destination
CREDENTIAL_NAME	VARCHAR2(128)		Name of the credential used for the remote destination
DESTINATION_OWNER	VARCHAR2(261)		Owner of the destination object that points to the destination
DESTINATION	VARCHAR2(261)		Name of the destination object or the name of the destination itself
JOB_DEST_ID	NUMBER		Numerical ID assigned to the job at this destination
ENABLED	VARCHAR2(5)		Indicates whether the parent job is enabled (TRUE) or disabled (FALSE)
REFS_ENABLED	VARCHAR2(5)		Indicates whether this destination and its agent are enabled (TRUE) or disabled (FALSE)
STATE	VARCHAR2(15)		State of this job at this destination: • DISABLED • RUNNING • CHAIN_STALLED • SCHEDULED • RETRY SCHEDULED • READY TO RUN • COMPLETED • BROKEN • FAILED • SUCCEEDED • REMOTE • STOPPED

Column	Datatype	NULL	Description
NEXT_START_DATE	TIMESTAMP(6) WITH TIME ZONE		Next start time of this job at this destination
RUN_COUNT	NUMBER		Number of times this job has run at this destination
RETRY_COUNT	NUMBER		Number of times this job has been retried at this destination
FAILURE_COUNT	NUMBER		Number of times this job has failed at this destination
LAST_START_DATE	TIMESTAMP(6) WITH TIME ZONE		Last time this job started at this destination
LAST_END_DATE	TIMESTAMP(6) WITH TIME ZONE		Last time this job ended at this destination

See Also:

- "DBA_SCHEDULER_JOB_DESTS"
- "USER_SCHEDULER_JOB_DESTS"

4.68 ALL_SCHEDULER_JOB_LOG

ALL_SCHEDULER_JOB_LOG displays log information for the Scheduler jobs accessible to the current user.

Related Views

- DBA_SCHEDULER_JOB_LOG displays log information for all Scheduler jobs in the database.
- USER_SCHEDULER_JOB_LOG displays log information for the Scheduler jobs owned by the current user.

Column	Datatype	NULL	Description
LOG_ID	NUMBER	NOT NULL	Unique identifier that identifies a row
LOG_DATE	TIMESTAMP(6) WITH TIME ZONE		Date of the log entry
OWNER	VARCHAR2(128)		Owner of the Scheduler job
JOB_NAME	VARCHAR2(261)		Name of the Scheduler job
JOB_SUBNAME	VARCHAR2(261)		Subname of the Scheduler job (for a chain step job)
JOB_CLASS	VARCHAR2(128)		Class that the job belonged to at the time of entry
OPERATION	VARCHAR2(30)		Operation corresponding to the log entry

Column	Datatype	NULL	Description
STATUS	VARCHAR2(30)		Status of the operation, if applicable. Possible values for this column are dependent on the value in the OPERATION column. In most cases, STATUS will be NULL. Only for job run operations will it have a value. STATUS will be NULL when OPERATION is one of the following: • CREATE - Job was created • UPDATE - One or more job attributes have been modified • ENABLE - Job has been enabled • DISABLE - Job has been disabled • COMPLETED - For repeating jobs only, job has reached its end date or maximum number of runs • BROKEN - Job has reached its maximum number of failures STATUS can be SUCCEEDED (job run completed successfully), FAILED (job run failed), or STOPPED (job run was stopped) when OPERATION is one of the following: • RUN - Regular job run • RETRY_RUN - Job is being retried because the previous run resulted in an error and RESTARTABLE is set to TRUE • RECOVERY_RUN - Job is being rerun because the database went down, or the job worker process crashed and RESTARTABLE is set to TRUE
USER_NAME	VARCHAR2(128)		Name of the user who performed the operation, if applicable
CLIENT_ID	VARCHAR2(64)		Client identifier of the user who performed the operation, if applicable
GLOBAL_UID	VARCHAR2(32)		Global user identifier of the user who performed the operation, if applicable
CREDENTIAL_OWNER	VARCHAR2(261)		Owner of the credential used for this remote job run
CREDENTIAL_NAME	VARCHAR2(261)		Name of the credential used for this remote job run
DESTINATION_OWNER	VARCHAR2(261)		Owner of the destination object used in this remote job run; NULL if no object used
DESTINATION	VARCHAR2(261)		Destination for a remote job operation
ADDITIONAL_INFO	CLOB		Additional information on the entry, if applicable

See Also:

- "DBA_SCHEDULER_JOB_LOG"
- "USER_SCHEDULER_JOB_LOG"

4.69 ALL_SCHEDULER_JOB_RUN_DETAILS

ALL_SCHEDULER_JOB_RUN_DETAILS displays log run details for the Scheduler jobs accessible to the current user.

Related Views

- DBA_SCHEDULER_JOB_RUN_DETAILS displays log run details for all Scheduler jobs in the database.
- USER_SCHEDULER_JOB_RUN_DETAILS displays log run details for the Scheduler jobs owned by the current user.

Column	Datatype	NULL	Description
LOG_ID	NUMBER	NOT NULL	Unique identifier of the log entry (foreign key of the *_SCHEDULER_JOB_LOG views)
LOG_DATE	TIMESTAMP(6) WITH TIME ZONE		Date of the log entry
OWNER	VARCHAR2(128)		Owner of the Scheduler job
JOB_NAME	VARCHAR2(261)		Name of the Scheduler job
JOB_SUBNAME	VARCHAR2(261)		Subname of the Scheduler job (for a chain step job)
STATUS	VARCHAR2(30)		Status of the job run
ERROR#	NUMBER		Error number in the case of an error
REQ_START_DATE	TIMESTAMP(6) WITH TIME ZONE		Requested start date of the job run
ACTUAL_START_DATE	TIMESTAMP(6) WITH TIME ZONE		Actual date on which the job was run
RUN_DURATION	INTERVAL DAY(3) TO SECOND(0)		Duration of the job run
INSTANCE_ID	NUMBER		Identifier of the instance on which the job was run
SESSION_ID	VARCHAR2(128)		Session identifier of the job run
SLAVE_PID	VARCHAR2(30)		Process identifier of the worker on which the job was run
CPU_USED	INTERVAL DAY(3) TO SECOND(2)		Amount of CPU used for the job run
CREDENTIAL_OWNER	VARCHAR2(261)		Owner of the credential used for this remote job run
CREDENTIAL_NAME	VARCHAR2(261)		Name of the credential used for this remote job run
DESTINATION_OWNER	VARCHAR2(261)		Owner of the destination object used in this remote job run; NULL if no object used

Column	Datatype	NULL	Description
DESTINATION	VARCHAR2(261)		Destination for a remote job operation
ADDITIONAL_INFO	VARCHAR2(4000)		Additional information on the job run, if applicable
ERRORS	VARCHAR2(4000)		Error messages generated by this job run
OUTPUT	VARCHAR2(4000)		Output messages generated by this job run
BINARY_ERRORS	BLOB		Error messages generated by this job run in a binary format
BINARY_OUTPUT	BLOB		Binary output messages generated by this job run

See Also:

- "DBA_SCHEDULER_JOB_RUN_DETAILS"
- "USER_SCHEDULER_JOB_RUN_DETAILS"

4.70 ALL_SCHEDULER_JOBS

ALL_SCHEDULER_JOBS displays information about the Scheduler jobs accessible to the current user.

Related Views

- DBA_SCHEDULER_JOBS displays information about all Scheduler jobs in the database.
- USER_SCHEDULER_JOBS displays information about the Scheduler jobs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the Scheduler job
JOB_NAME	VARCHAR2(128)		Name of the Scheduler job
JOB_SUBNAME	VARCHAR2(128)		Subname of the Scheduler job (for a job running a chain step)
JOB_STYLE	VARCHAR2(17)		Job style: • REGULAR • LIGHTWEIGHT • IN_MEMORY_RUNTIME • IN_MEMORY_FULL
JOB_CREATOR	VARCHAR2(128)		Original creator of the job
CLIENT_ID	VARCHAR2(65)		Client identifier of the user creating the job
GLOBAL_UID	VARCHAR2(33)		Global user identifier of the user creating the job
PROGRAM_OWNER	VARCHAR2(4000)		Owner of the program associated with the job
PROGRAM_NAME	VARCHAR2(4000)		Name of the program associated with the job

Column	Datatype	NULL	Description
JOB_TYPE	VARCHAR2(16)		Inline job action type: • PLSQL_BLOCK • STORED_PROCEDURE • EXECUTABLE • CHAIN • SQL_SCRIPT • BACKUP_SCRIPT • EXTERNAL_SCRIPT
JOB_ACTION	VARCHAR2(4000)		Inline job action
NUMBER_OF_ARGUMENTS	NUMBER		Inline number of job arguments
SCHEDULE_OWNER	VARCHAR2(4000)		Owner of the schedule that the job uses (can be a window or a window group)
SCHEDULE_NAME	VARCHAR2(4000)		Name of the schedule that the job uses (can be a window or a window group)
SCHEDULE_TYPE	VARCHAR2(12)		Type of the schedule that the job uses: • IMMEDIATE - Start date and repeat interval are NULL • ONCE - Repeat interval is NULL • PLSQL - PL/SQL expression used as schedule • CALENDAR - Oracle calendaring expression used as schedule • EVENT - Event schedule • NAMED - Named schedule • WINDOW - Window used as schedule • WINDOW_GROUP - Window group used as schedule
START_DATE	TIMESTAMP(6) WITH TIME ZONE		Original scheduled start date of the job (for an inline schedule)
REPEAT_INTERVAL	VARCHAR2(4000)		Inline schedule PL/SQL expression or calendar string
EVENT_QUEUE_OWNER	VARCHAR2(128)		Owner of the source queue into which the event will be raised
EVENT_QUEUE_NAME	VARCHAR2(128)		Name of the source queue into which the event will be raised
EVENT_QUEUE_AGENT	VARCHAR2(523)		Name of the AQ agent used by the user on the event source queue (if it is a secure queue)
EVENT_CONDITION	VARCHAR2(4000)		Boolean expression used as the subscription rule for the event on the source queue
EVENT_RULE	VARCHAR2(261)		Name of the rule used by the coordinator to trigger the event-based job
FILE_WATCHER_OWNER	VARCHAR2(261)		Owner of the file watcher on which this job is based
FILE_WATCHER_NAME	VARCHAR2(261)		Name of the file watcher on which this job is based
END_DATE	TIMESTAMP(6) WITH TIME ZONE		Date after which the job will no longer run (for an inline schedule)
JOB_CLASS	VARCHAR2(128)		Name of the job class associated with the job

Column	Datatype	NULL	Description
ENABLED	VARCHAR2(5)		Indicates whether the job is enabled (TRUE) or disabled (FALSE)
AUTO_DROP	VARCHAR2(5)		Indicates whether the job will be dropped when it has completed (TRUE) or not (FALSE)
RESTART_ON_RECOVERY	VARCHAR2(5)		Indicates whether the step should be restarted on database recovery (TRUE) or not (FALSE)
RESTART_ON_FAILURE	VARCHAR2(5)		Indicates whether the step should be restarted on application failure (TRUE) or not (FALSE)
STATE	VARCHAR2(20)		Current state of the job: • BLOCKED • BROKEN • CHAIN_STALLED • COMPLETED • DISABLED • FAILED • READY TO RUN • REMOTE • RESOURCE_UNAVAILABLE • RETRY SCHEDULED • RUNNING • SCHEDULED • SOME FAILED • STOPPED • SUCCEEDED
JOB_PRIORITY	NUMBER		Priority of the job relative to other jobs in the same class
RUN_COUNT	NUMBER		Number of times the job has run
UPTIME_RUN_COUNT	NUMBER		Number of runs since the database last restarted. For in-memory jobs, this column is populated, but the RUN_COUNT column is not populated. For all other jobs, this column is NULL.
MAX_RUNS	NUMBER		Maximum number of times the job is scheduled to run
FAILURE_COUNT	NUMBER		Number of times the job has failed to run
UPTIME_FAILURE_COUNT	NUMBER		Number of failures since the database last restarted. For in-memory jobs, this column is populated, but the FAILURE_COUNT column is not populated. For all other jobs, this column is NULL.
MAX_FAILURES	NUMBER		Number of times the job will be allowed to fail before being marked broken
RETRY_COUNT	NUMBER		Number of times the job has retried, if it is retrying
LAST_START_DATE	TIMESTAMP(6) WITH TIME ZONE		Last date on which the job started running
LAST_RUN_DURATION	INTERVAL DAY(9) TO SECOND(6)		Amount of time the job took to complete during the last run
NEXT_RUN_DATE	TIMESTAMP(6) WITH TIME ZONE		Next date on which the job is scheduled to run

Column	Datatype	NULL	Description
SCHEDULE_LIMIT	INTERVAL DAY(3) TO SECOND(0)		Time after which a job which has not run yet will be rescheduled
MAX_RUN_DURATION	INTERVAL DAY(3) TO SECOND(0)		Maximum amount of time for which the job will be allowed to run
LOGGING_LEVEL	VARCHAR2(11)		Amount of logging that will be done pertaining to the job: • OFF • RUNS • FAILED RUNS • FULL
STORE_OUTPUT	VARCHAR2(5)		Indicates whether all job output messages for the job are stored in the OUTPUT column of the *_JOB_RUN_DETAILS views for job runs that are logged. Possible values: • TRUE: All job output messages for the job are stored in the OUTPUT column of the *_JOB_RUN_DETAILS views for job runs that are logged. This is the default for new jobs. A new job is a job created using Oracle Database 12*c* software. • FALSE: Job output messages for the job are not stored in the OUTPUT column of the *_JOB_RUN_DETAILS views. This is the default for existing jobs. An existing job is a job created using pre-Oracle Database 12*c* software.
STOP_ON_WINDOW_CLOSE	VARCHAR2(5)		Indicates whether the job will stop if a window associated with the job closes (TRUE) or not (FALSE)
INSTANCE_STICKINESS	VARCHAR2(5)		Indicates whether the job is sticky (TRUE) or not (FALSE)
RAISE_EVENTS	VARCHAR2(4000)		List of job events to raise for the job: • JOB_STARTED • JOB_SUCCEEDED • JOB_FAILED • JOB_BROKEN • JOB_COMPLETED • JOB_STOPPED • JOB_SCH_LIM_REACHED • JOB_DISABLED • JOB_CHAIN_STALLED • JOB_OVER_MAX_DUR
SYSTEM	VARCHAR2(5)		Indicates whether the job is a system job (TRUE) or not (FALSE)
JOB_WEIGHT	NUMBER		Weight of the job
NLS_ENV	VARCHAR2(4000)		NLS environment of the job
SOURCE	VARCHAR2(128)		Source global database identifier
NUMBER_OF_DESTINATIONS	NUMBER		Number of destinations associated with this job

Column	Datatype	NULL	Description
DESTINATION_OWNER	VARCHAR2(261)		Owner of the destination object (if used), else NULL
DESTINATION	VARCHAR2(261)		Destination that this job will run on
CREDENTIAL_OWNER	VARCHAR2(128)		Owner of the credential to be used for an external job
CREDENTIAL_NAME	VARCHAR2(128)		Name of the credential to be used for an external job
INSTANCE_ID	NUMBER		Instance on which the user requests the job to run
DEFERRED_DROP	VARCHAR2(5)		Indicates whether the job will be dropped when completed due to user request (TRUE) or not (FALSE)
ALLOW_RUNS_IN_RESTRICTED_MODE	VARCHAR2(5)		Indicates whether the job is allowed to run in restricted session mode (TRUE) or not (FALSE)
COMMENTS	VARCHAR2(4000)		Comments on the job
FLAGS	NUMBER		This column is for internal use
RESTARTABLE	VARCHAR2(5)		Indicates whether the job can be restarted (TRUE) or not (FALSE)
HAS_CONSTRAINTS	VARCHAR2(5)		Indicates whether the job (not including the program of the job) is part of a resource constraint or incompatibility (TRUE) or not (FALSE)
CONNECT_CREDENTIAL_OWNER	VARCHAR2(128)		Owner of connect credential
CONNECT_CREDENTIAL_NAME	VARCHAR2(128)		Name of connect credential
FAIL_ON_SCRIPT_ERROR	VARCHAR2(5)		Indicates whether this job fails on script error (TRUE) or not (FALSE)

See Also:

- "DBA_SCHEDULER_JOBS"
- "USER_SCHEDULER_JOBS"

4.71 ALL_SCHEDULER_NOTIFICATIONS

ALL_SCHEDULER_NOTIFICATIONS displays information about the E-mail notifications for the jobs accessible to the current user.

Related Views

- DBA_SCHEDULER_NOTIFICATIONS displays information about the E-mail notifications for all jobs in the database.
- USER_SCHEDULER_NOTIFICATIONS displays information about the E-mail notifications for the jobs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
NOTIFICATION_OWNER	VARCHAR2(128)	NOT NULL	Owner of this notification
OWNER	VARCHAR2(128)	NOT NULL	Owner of the job this notification is for
JOB_NAME	VARCHAR2(128)	NOT NULL	Name of the job this notification is for
JOB_SUBNAME	VARCHAR2(128)		Subname of the job this notification is for
RECIPIENT	VARCHAR2(4000)	NOT NULL	E-mail address to send this E-mail notification to
SENDER	VARCHAR2(4000)		E-mail address to send this E-mail notification from
SUBJECT	VARCHAR2(4000)		Subject of the notification E-mail
BODY	VARCHAR2(4000)		Body of the notification E-mail
FILTER_CONDITION	VARCHAR2(4000)		Filter specifying which job events to send notifications for
EVENT	VARCHAR2(19)		Job event to send notifications for: • JOB_STARTED • JOB_SUCCEEDED • JOB_FAILED • JOB_BROKEN • JOB_COMPLETED • JOB_STOPPED • JOB_SCH_LIM_REACHED • JOB_DISABLED • JOB_CHAIN_STALLED • JOB_OVER_MAX_DUR
EVENT_FLAG	NUMBER	NOT NULL	Event number of the job event to send notifications for

See Also:

- "DBA_SCHEDULER_NOTIFICATIONS"
- "USER_SCHEDULER_NOTIFICATIONS"

4.72 ALL_SCHEDULER_PROGRAM_ARGS

ALL_SCHEDULER_PROGRAM_ARGS displays information about the arguments of the Scheduler programs accessible to the current user.

Related Views

- DBA_SCHEDULER_PROGRAM_ARGS displays information about the arguments of all Scheduler programs in the database.
- USER_SCHEDULER_PROGRAM_ARGS displays information about the arguments of the Scheduler programs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the program to which the argument belongs
PROGRAM_NAME	VARCHAR2(128)	NOT NULL	Name of the program to which the argument belongs
ARGUMENT_NAME	VARCHAR2(128)		Optional name of the argument
ARGUMENT_POSITION	NUMBER	NOT NULL	Position of the argument in the argument list
ARGUMENT_TYPE	VARCHAR2(257)		Data type of the argument
METADATA_ATTRIBUTE	VARCHAR2(19)		Metadata attribute: • JOB_NAME • JOB_OWNER • JOB_START • WINDOW_START • WINDOW_END • JOB_SUBNAME • EVENT_MESSAGE • JOB_SCHEDULED_START
DEFAULT_VALUE	VARCHAR2(4000)		Default value taken by the argument (in string format) if the argument is a string
DEFAULT_ANYDATA_VALUE	ANYDATA		Default value taken by the argument (in AnyData format)
OUT_ARGUMENT	VARCHAR2(5)		Reserved for future use

See Also:

- "DBA_SCHEDULER_PROGRAM_ARGS"
- "USER_SCHEDULER_PROGRAM_ARGS"

4.73 ALL_SCHEDULER_PROGRAMS

ALL_SCHEDULER_PROGRAMS displays information about the Scheduler programs accessible to the current user.

Related Views

- DBA_SCHEDULER_PROGRAMS displays information about all Scheduler programs in the database.
- USER_SCHEDULER_PROGRAMS displays information about the Scheduler programs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Scheduler program
PROGRAM_NAME	VARCHAR2(128)	NOT NULL	Name of the Scheduler program

Column	Datatype	NULL	Description
PROGRAM_TYPE	VARCHAR2(16)		Type of the program action: • PLSQL_BLOCK • STORED_PROCEDURE • EXECUTABLE
PROGRAM_ACTION	VARCHAR2(4000)		String specifying the program action
NUMBER_OF_ARGUMENTS	NUMBER		Number of arguments accepted by the program
ENABLED	VARCHAR2(5)		Indicates whether the program is enabled (TRUE) or disabled (FALSE)
DETACHED	VARCHAR2(5)		This column is for internal use
SCHEDULE_LIMIT	INTERVAL DAY(3) TO SECOND(0)		Maximum delay in running the program after the scheduled start
PRIORITY	NUMBER		Priority of the program
WEIGHT	NUMBER		Weight of the program
MAX_RUNS	NUMBER		Maximum number of runs of any job based on this program
MAX_FAILURES	NUMBER		Maximum number of failures of any job based on this program
MAX_RUN_DURATION	INTERVAL DAY(3) TO SECOND(0)		Maximum amount of time this program can run
HAS_CONSTRAINTS	VARCHAR2(5)		Indicates whether the job (not including the program of the job) is part of a resource constraint or incompatibility (TRUE) or not (FALSE)
NLS_ENV	VARCHAR2(4000)		NLS environment in which the program was created
COMMENTS	VARCHAR2(4000)		Comments on the program

See Also:

- "DBA_SCHEDULER_PROGRAMS"
- "USER_SCHEDULER_PROGRAMS"

4.74 ALL_SCHEDULER_REMOTE_DATABASES

ALL_SCHEDULER_REMOTE_DATABASES displays information about the remote databases accessible to the current user that have been registered as sources and destinations for remote database jobs.

Related View

DBA_SCHEDULER_REMOTE_DATABASES displays information about all remote databases that have been registered as sources and destinations for remote database jobs.

Column	Datatype	NULL	Description
DATABASE_NAME	VARCHAR2(512)	NOT NULL	Global name of the remote database
REGISTERED_AS	VARCHAR2(11)		Indicates whether the database is registered as a source (SOURCE) or as a destination (DESTINATION)
DATABASE_LINK	VARCHAR2(512)	NOT NULL	Name of a valid database link to the remote database

> **See Also:**
>
> "DBA_SCHEDULER_REMOTE_DATABASES"

4.75 ALL_SCHEDULER_REMOTE_JOBSTATE

ALL_SCHEDULER_REMOTE_JOBSTATE displays information about the state of the jobs accessible to the current user at remote databases.

Related Views

- DBA_SCHEDULER_REMOTE_JOBSTATE displays information about the state of all jobs at remote databases.
- USER_SCHEDULER_REMOTE_JOBSTATE displays information about the state of the jobs owned by the current user at remote databases. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Scheduler job
JOB_NAME	VARCHAR2(128)	NOT NULL	Name of the Scheduler job
DESTINATION	VARCHAR2(512)	NOT NULL	Name of the job destination
STATE	VARCHAR2(15)		State of the job at the destination: • DISABLED • RETRY SCHEDULED • SCHEDULED • RUNNING • COMPLETED • BROKEN • FAILED • SUCCEEDED • STOPPED
NEXT_START_DATE	TIMESTAMP(6) WITH TIME ZONE		Next start date of the job at the destination
RUN_COUNT	NUMBER		Run count of the job at the destination
FAILURE_COUNT	NUMBER		Failure count of the job at the destination
RETRY_COUNT	NUMBER		Retry count of the job at the destination
LAST_START_DATE	TIMESTAMP(6) WITH TIME ZONE		Last start date of the job at the destination

Column	Datatype	NULL	Description
LAST_END_DATE	TIMESTAMP(6) WITH TIME ZONE		Last end date of the job at the destination

See Also:

- "DBA_SCHEDULER_REMOTE_JOBSTATE"
- "USER_SCHEDULER_REMOTE_JOBSTATE"

4.76 ALL_SCHEDULER_RESOURCES

ALL_SCHEDULER_RESOURCES displays all scheduler resource objects in the database that are accessible to the current user.

Related Views

- DBA_SCHEDULER_RESOURCES displays all scheduler resource objects in the database.
- USER_SCHEDULER_RESOURCES displays all scheduler resource objects in the database from the schema of the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the resource object
RESOURCE_NAME	VARCHAR2(128)	NOT NULL	Name of the resource object
STATUS	VARCHAR2(19)		Resource status for resource object.
RESOURCE_UNITS	NUMBER		Maximum number of available units for the resource object
UNITS_USED	NUMBER		Current number of resource units in use for the resource object
JOBS_RUNNING_COUNT	NUMBER		Current number of running jobs using the resource object
COMMENTS	VARCHAR2(256)		Comments for the resource object

See Also:

- "DBA_SCHEDULER_RESOURCES"
- "USER_SCHEDULER_RESOURCES"

4.77 ALL_SCHEDULER_RSC_CONSTRAINTS

ALL_SCHEDULER_RSC_CONSTRAINTS lists all Oracle Scheduler resource constraint members accessible to the current user.

Related Views

- DBA_SCHEDULER_RSC_CONSTRAINTS lists all Oracle Scheduler resource constraint members in the database.
- USER_SCHEDULER_RSC_CONSTRAINTS lists all Oracle Scheduler resource constraint members owned by the current user.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the resource object the member is in
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the resource object the member is in
RESOURCE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the resource constraint resource member
RESOURCE_NAME	VARCHAR2(128)	NOT NULL	Name of the resource constraint resource member
UNITS_USED	NUMBER		Number of units used of the resource by this constraint resource member

See Also:

- "DBA_SCHEDULER_RSC_CONSTRAINTS"
- "USER_SCHEDULER_RSC_CONSTRAINTS"

4.78 ALL_SCHEDULER_RUNNING_CHAINS

ALL_SCHEDULER_RUNNING_CHAINS displays information about the chain steps of the running chains accessible to the current user (that is, those chains that the user has ALTER privileges for). In the case of nested chains, this view also enables you to traverse the hierarchy of the chain with a SQL statement that contains a CONNECT BY clause linking up the JOB_SUBNAME and STEP_JOB_SUBNAME columns.

Related Views

- DBA_SCHEDULER_RUNNING_CHAINS displays information about the chain steps of all running chains in the database.
- USER_SCHEDULER_RUNNING_CHAINS displays information about the chain steps of the running chains owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the job which is running the chain
JOB_NAME	VARCHAR2(128)	NOT NULL	Name of the job which is running the chain

Column	Datatype	NULL	Description
JOB_SUBNAME	VARCHAR2(128)		Subname of the job which is running the chain (for a nested chain), else NULL
CHAIN_OWNER	VARCHAR2(128)	NOT NULL	Owner of the chain being run
CHAIN_NAME	VARCHAR2(128)	NOT NULL	Name of the chain being run
STEP_NAME	VARCHAR2(128)	NOT NULL	Name of the step of the running chain
STATE	VARCHAR2(15)		State of the running chain step: • NOT_STARTED • RUNNING • SUCCEEDED • STOPPED • FAILED • SCHEDULED • RETRY SCHEDULED • PAUSED • STALLED
ERROR_CODE	NUMBER		Error code with which the step completed (if it has completed)
COMPLETED	VARCHAR2(5)		Indicates whether the running chain step has completed (TRUE) or not (FALSE)
START_DATE	TIMESTAMP(6) WITH TIME ZONE		Date when the running chain step started (if it has started)
END_DATE	TIMESTAMP(6) WITH TIME ZONE		Date when the running chain step stopped (if it has stopped)
DURATION	INTERVAL DAY(9) TO SECOND(6)		Amount of time it took the chain step to complete (if it has completed)
SKIP	VARCHAR2(5)		Indicates whether the chain step should be skipped (TRUE) or not (FALSE)
PAUSE	VARCHAR2(5)		Indicates whether the chain step should be paused after running (TRUE) or not (FALSE)
PAUSE_BEFORE	VARCHAR2(5)		Indicates whether the chain step should be paused before running (TRUE) or not (FALSE)
RESTART_ON_RECOVERY	VARCHAR2(5)		Indicates whether the chain step will be restarted on database recovery (TRUE) or not (FALSE)
RESTART_ON_FAILURE	VARCHAR2(5)		Indicates whether the chain step will be restarted on application failure (TRUE) or not (FALSE)
STEP_JOB_SUBNAME	VARCHAR2(128)		Subname of the job running the step
STEP_JOB_LOG_ID	NUMBER		Log ID of the job running the step

See Also:

- "DBA_SCHEDULER_RUNNING_CHAINS"
- "USER_SCHEDULER_RUNNING_CHAINS"

4.79 ALL_SCHEDULER_RUNNING_JOBS

ALL_SCHEDULER_RUNNING_JOBS displays information about the running Scheduler jobs accessible to the current user.

Related Views

- DBA_SCHEDULER_RUNNING_JOBS displays information about all running Scheduler jobs in the database.
- USER_SCHEDULER_RUNNING_JOBS displays information about the running Scheduler jobs owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the running Scheduler job
JOB_NAME	VARCHAR2(128)		Name of the running Scheduler job
JOB_SUBNAME	VARCHAR2(128)		Subname of the running Scheduler job (for a job running a chain step)
JOB_STYLE	VARCHAR2(17)		Job style: • REGULAR • LIGHTWEIGHT • IN_MEMORY_RUNTIME • IN_MEMORY_FULL
DETACHED	VARCHAR2(5)		Indicates whether the detached attribute is set for the job (TRUE) or not (FALSE). If the detached attribute is set, then the job will remain running even after the job action has completed.
SESSION_ID	NUMBER		Identifier of the session running the Scheduler job
SLAVE_PROCESS_ID	NUMBER		Process number of the worker process running the Scheduler job
SLAVE_OS_PROCESS_ID	VARCHAR2(12)		Process number of the operating system worker process running the scheduler job
RUNNING_INSTANCE	NUMBER		Database instance number of the worker process running the Scheduler job
RESOURCE_CONSUMER_GROUP	VARCHAR2(32)		Resource consumer group of the session in which the Scheduler job is running
ELAPSED_TIME	INTERVAL DAY(3) TO SECOND(2)		Elapsed time since the Scheduler job was started
CPU_USED	INTERVAL DAY(3) TO SECOND(2)		CPU time consumed by the running Scheduler job, if available
DESTINATION_OWNER	VARCHAR2(261)		Owner of the destination object (if used), else NULL
DESTINATION	VARCHAR2(261)		Destination that this job is running on
CREDENTIAL_OWNER	VARCHAR2(128)		Owner of the login credential used for this running job, if any
CREDENTIAL_NAME	VARCHAR2(128)		Name of the login credential used for this running job, if any

Column	Datatype	NULL	Description
LOG_ID	NUMBER		Log ID used for this running job. This column maps to the LOG_ID column of the *_SCHEDULER_JOB_LOG and *_SCHEDULER_JOB_RUN_DETAILS views.

See Also:

- "DBA_SCHEDULER_RUNNING_JOBS"
- "USER_SCHEDULER_RUNNING_JOBS"

4.80 ALL_SCHEDULER_SCHEDULES

ALL_SCHEDULER_SCHEDULES displays information about the Scheduler schedules accessible to the current user.

Related Views

- DBA_SCHEDULER_SCHEDULES displays information about all Scheduler schedules in the database.
- USER_SCHEDULER_SCHEDULES displays information about the Scheduler schedules owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the schedule
SCHEDULE_NAME	VARCHAR2(128)	NOT NULL	Name of the schedule
SCHEDULE_TYPE	VARCHAR2(12)		Type of the schedule: • ONCE - Repeat interval is NULL • CALENDAR - Oracle calendaring expression used as schedule • EVENT - Event schedule
START_DATE	TIMESTAMP(6) WITH TIME ZONE		Start date for the repeat interval
REPEAT_INTERVAL	VARCHAR2(4000)		Calendar syntax expression for the schedule
EVENT_QUEUE_OWNER	VARCHAR2(128)		Owner of the source queue into which the event will be raised
EVENT_QUEUE_NAME	VARCHAR2(128)		Name of the source queue into which the event will be raised
EVENT_QUEUE_AGENT	VARCHAR2(523)		Name of the AQ agent used by the user on the event source queue (if it is a secure queue)
EVENT_CONDITION	VARCHAR2(4000)		Boolean expression used as the subscription rule for the event on the source queue
FILE_WATCHER_OWNER	VARCHAR2(261)		Owner of the file watcher on which this schedule is based

Column	Datatype	NULL	Description
FILE_WATCHER_NAME	VARCHAR2(261)		Name of the file watcher on which this schedule is based
END_DATE	TIMESTAMP(6) WITH TIME ZONE		Cutoff date after which the schedule will not specify any dates
COMMENTS	VARCHAR2(4000)		Comments on the schedule

See Also:

- "DBA_SCHEDULER_SCHEDULES"
- "USER_SCHEDULER_SCHEDULES"

4.81 ALL_SCHEDULER_WINDOW_DETAILS

ALL_SCHEDULER_WINDOW_DETAILS displays log details for the Scheduler windows accessible to the current user.

Related View

DBA_SCHEDULER_WINDOW_DETAILS displays log details for all Scheduler windows in the database.

Column	Datatype	NULL	Description
LOG_ID	NUMBER		Unique identifier of the log entry (foreign key of the *_SCHEDULER_WINDOW_LOG views)
LOG_DATE	TIMESTAMP(6) WITH TIME ZONE		Date of the log entry
OWNER	VARCHAR2(128)		Owner of the Scheduler window
WINDOW_NAME	VARCHAR2(261)		Name of the Scheduler window
REQ_START_DATE	TIMESTAMP(6) WITH TIME ZONE		Requested start date for the Scheduler window
ACTUAL_START_DATE	TIMESTAMP(6) WITH TIME ZONE		Actual start date of the Scheduler window
WINDOW_DURATION	INTERVAL DAY(3) TO SECOND(0)		Requested duration of the Scheduler window
ACTUAL_DURATION	INTERVAL DAY(3) TO SECOND(0)		Actual duration for which the Scheduler window lasted
INSTANCE_ID	NUMBER		Identifier of the instance on which the window was run
ADDITIONAL_INFO	VARCHAR2(4000)		Additional information on the entry, if applicable

> **See Also:**
>
> "DBA_SCHEDULER_WINDOW_DETAILS"

4.82 ALL_SCHEDULER_WINDOW_GROUPS

ALL_SCHEDULER_WINDOW_GROUPS displays information about the Scheduler window groups accessible to the current user.

Related View

DBA_SCHEDULER_WINDOW_GROUPS displays information about all Scheduler window groups in the database.

Column	Datatype	NULL	Description
WINDOW_GROUP_NAME	VARCHAR2(128)	NOT NULL	Name of the window group
ENABLED	VARCHAR2(5)		Indicates whether the window group is enabled (TRUE) or disabled (FALSE)
NUMBER_OF_WINDOWS	NUMBER		Number of members in the window group
NEXT_START_DATE	VARCHAR2(64)		If a window group is disabled, then this column will be NULL. Otherwise, it will be set to the earliest NEXT_START_DATE from the enabled windows in the group.
COMMENTS	VARCHAR2(4000)		Optional comment about the window group

> **See Also:**
>
> "DBA_SCHEDULER_WINDOW_GROUPS"

4.83 ALL_SCHEDULER_WINDOW_LOG

ALL_SCHEDULER_WINDOW_LOG displays log information for the Scheduler windows accessible to the current user.

Related View

DBA_SCHEDULER_WINDOW_LOG displays log information for all Scheduler windows in the database.

Column	Datatype	NULL	Description
LOG_ID	NUMBER	NOT NULL	Unique identifier of the log entry
LOG_DATE	TIMESTAMP(6) WITH TIME ZONE		Date of the log entry
OWNER	VARCHAR2(128)		Owner of the Scheduler window
WINDOW_NAME	VARCHAR2(261)		Name of the Scheduler window

Column	Datatype	NULL	Description
OPERATION	VARCHAR2(30)		Operation corresponding to the log entry
STATUS	VARCHAR2(30)		Status of the operation, if applicable
USER_NAME	VARCHAR2(128)		Name of the user who performed the operation, if applicable
CLIENT_ID	VARCHAR2(64)		Client identifier of the user who performed the operation, if applicable
GLOBAL_UID	VARCHAR2(32)		Global user identifier of the user who performed the operation, if applicable
ADDITIONAL_INFO	CLOB		Additional information on the entry, if applicable

See Also:

"DBA_SCHEDULER_WINDOW_LOG"

4.84 ALL_SCHEDULER_WINDOWS

ALL_SCHEDULER_WINDOWS displays information about the Scheduler windows accessible to the current user.

Related View

DBA_SCHEDULER_WINDOWS displays information about all Scheduler windows in the database.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Scheduler window
WINDOW_NAME	VARCHAR2(128)	NOT NULL	Name of the Scheduler window
RESOURCE_PLAN	VARCHAR2(128)		Resource plan associated with the window
SCHEDULE_OWNER	VARCHAR2(4000)		Owner of the schedule of the window
SCHEDULE_NAME	VARCHAR2(4000)		Name of the schedule of the window
SCHEDULE_TYPE	VARCHAR2(8)		Type of the schedule of the window: • ONCE - Repeat interval is NULL • NAMED - Named schedule • CALENDAR - Oracle calendaring expression used as schedule
START_DATE	TIMESTAMP(6) WITH TIME ZONE		Start date of the window (for an inline schedule)
REPEAT_INTERVAL	VARCHAR2(4000)		Calendar string for the window (for an inline schedule)
END_DATE	TIMESTAMP(6) WITH TIME ZONE		Date after which the window will no longer open (for an inline schedule)
DURATION	INTERVAL DAY(3) TO SECOND(0)		Duration of the window

Column	Datatype	NULL	Description
WINDOW_PRIORITY	VARCHAR2(4)		Priority of the job relative to other windows: • HIGH • LOW
NEXT_START_DATE	TIMESTAMP(6) WITH TIME ZONE		Next date on which the window is scheduled to start
LAST_START_DATE	TIMESTAMP(6) WITH TIME ZONE		Last date on which the window opened
ENABLED	VARCHAR2(5)		Indicates whether the window is enabled (TRUE) or disabled (FALSE)
ACTIVE	VARCHAR2(5)		Indicates whether the window is open (TRUE) or not (FALSE)
MANUAL_OPEN_TIME	TIMESTAMP(6) WITH TIME ZONE		Open time of the window if it was manually opened, else NULL
MANUAL_DURATION	INTERVAL DAY(3) TO SECOND(0)		Duration of the window if it was manually opened, else NULL
COMMENTS	VARCHAR2(4000)		Comments on the window

See Also:

"DBA_SCHEDULER_WINDOWS"

4.85 ALL_SCHEDULER_WINGROUP_MEMBERS

ALL_SCHEDULER_WINGROUP_MEMBERS displays the members of the Scheduler window groups accessible to the current user.

Related View

DBA_SCHEDULER_WINGROUP_MEMBERS displays the members of all Scheduler window groups in the database.

Column	Datatype	NULL	Description
WINDOW_GROUP_NAME	VARCHAR2(128)	NOT NULL	Name of the window group
WINDOW_NAME	VARCHAR2(128)	NOT NULL	Name of the window member of the window group

See Also:

"DBA_SCHEDULER_WINGROUP_MEMBERS"

4.86 ALL_SEC_RELEVANT_COLS

ALL_SEC_RELEVANT_COLS describes the security relevant columns of the security policies for the tables and views accessible to the current user.

Related Views

- DBA_SEC_RELEVANT_COLS describes the security relevant columns of all security policies in the database.
- USER_SEC_RELEVANT_COLS describes the security relevant columns of the security policies for the tables and views owned by the current user. This view does not display the OBJECT_OWNER column.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)		Owner of the table or view
OBJECT_NAME	VARCHAR2(128)		Name of the table or view
POLICY_GROUP	VARCHAR2(128)		Name of the policy group
POLICY_NAME	VARCHAR2(128)		Name of the policy
SEC_REL_COLUMN	VARCHAR2(128)		Name of the security relevant column
COLUMN_OPTION	VARCHAR2(8)		Option of the security relevant column: • NONE • ALL_ROWS
COMMON	VARCHAR2(3)		Indicates whether the policy security relevant column is applied and enforced in all application PDBs (YES) or only in the local PDB (NO)
INHERITED	VARCHAR2(3)		Indicates whether the policy security relevant column is inherited from the root (YES) or not (NO)

See Also:

- "DBA_SEC_RELEVANT_COLS"
- "USER_SEC_RELEVANT_COLS"

4.87 ALL_SECONDARY_OBJECTS

ALL_SECONDARY_OBJECTS provides information about secondary objects associated with domain indexes accessible to the user.

This view is only relevant for domain indexes. And currently, the secondary objects can only be tables.

Related Views

- DBA_SECONDARY_OBJECTS provides information about all secondary objects that are associated with domain indexes in the database.

- USER_SECONDARY_OBJECTS provides information about secondary objects associated with domain indexes owned by the current user.

Column	Datatype	NULL	Description
INDEX_OWNER	VARCHAR2(128)	NOT NULL	Owner of the domain index
INDEX_NAME	VARCHAR2(128)	NOT NULL	Name of the domain index
SECONDARY_OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the secondary object created by the domain index
SECONDARY_OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the secondary object created by the domain index
SECONDARY_OBJDATA_TYPE	VARCHAR2(20)		Type of the secondary object created by the domain index

See Also:

- "DBA_SECONDARY_OBJECTS"
- "USER_SECONDARY_OBJECTS"

4.88 ALL_SEQUENCES

ALL_SEQUENCES describes all sequences accessible to the current user.

Related Views

- DBA_SEQUENCES describes all sequences in the database.
- USER_SEQUENCES describes all sequences owned by the current user. This view does not display the SEQUENCE_OWNER column.

Column	Datatype	NULL	Description
SEQUENCE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the sequence
SEQUENCE_NAME	VARCHAR2(128)	NOT NULL	Sequence name
MIN_VALUE	NUMBER		Minimum value of the sequence
MAX_VALUE	NUMBER		Maximum value of the sequence
INCREMENT_BY	NUMBER	NOT NULL	Value by which sequence is incremented
CYCLE_FLAG	VARCHAR2(1)		Indicates whether the sequence wraps around on reaching the limit (Y) or not (N)
ORDER_FLAG	VARCHAR2(1)		Indicates whether sequence numbers are generated in order (Y) or not (N)
CACHE_SIZE	NUMBER	NOT NULL	Number of sequence numbers to cache

Column	Datatype	NULL	Description
LAST_NUMBER	NUMBER	NOT NULL	Last sequence number written to disk. If a sequence uses caching, the number written to disk is the last number placed in the sequence cache. This number is likely to be greater than the last sequence number that was used. For session sequences, the value in this column should be ignored.
SCALE_FLAG	VARCHAR2(1)		Indicates whether this is a scalable sequence (Y) or not (N)
EXTEND_FLAG	VARCHAR2(1)		Indicates whether this scalable sequence's generated values extend beyond MAX_VALUE or MIN_VALUE (Y) or not (N)
SHARDED_FLAG	VARCHAR2(1)		Indicates whether this is a sharded sequence (Y) or not (N)
SESSION_FLAG	VARCHAR2(1)		Indicates whether sequence values are session private (Y) or not (N)
KEEP_VALUE	VARCHAR2(1)		Indicates whether sequence values are kept during replay after a failure (Y) or not (N)

See Also:

- "DBA_SEQUENCES"
- "USER_SEQUENCES"

4.89 ALL_SERVICES

ALL_SERVICES displays all services in the database. The view excludes rows marked for deletion.

Related View

DBA_SERVICES displays all services in the database. The view excludes rows marked for deletion.

Column	Datatype	NULL	Description
SERVICE_ID	NUMBER		Unique ID for the service
NAME	VARCHAR2(64)		Name describing the workload
NAME_HASH	NUMBER		Hash of the short name for the service
NETWORK_NAME	VARCHAR2(512)		Network name used to connect to the service
CREATION_DATE	DATE		Date the service was created
CREATION_DATE_HASH	NUMBER		Hash of the creation date
FAILOVER_METHOD	VARCHAR2(64)		TAF only for compatibility - BASIC or NONE

Column	Datatype	NULL	Description
FAILOVER_TYPE	VARCHAR2(64)		For Application Continuity for Java, TRANSACTION. For TAF, SESSION or SELECT.
FAILOVER_RETRIES	NUMBER(10)		For Application Continuity and TAF, when reconnecting after a failure, number of attempts to re-connect per incident
FAILOVER_DELAY	NUMBER(10)		For Application Continuity and TAF, when reconnecting after a failure, delay between each connection retry (in seconds)
MIN_CARDINALITY	NUMBER		Reserved for internal use
MAX_CARDINALITY	NUMBER		Reserved for internal use
GOAL	VARCHAR2(12)		Runtime Load Balancing Goal being used to create run-time load balancing and connection load balancing advice: • NONE • SERVICE_TIME - Connections are balanced by response time • THROUGHPUT - Connections are balanced by throughput
DTP	VARCHAR2(1)		DTP (distributed transaction processing) enforces all sessions for a service at one instance. This is a requirement for XA before 11*g*, and is a requirement if resuming and suspending the same XA branch.
ENABLED	VARCHAR2(3)		Reserved for internal use
AQ_HA_NOTIFICATIONS	VARCHAR2(3)		To enable FAN for OCI connections, set AQ HA Notifications to True. For Oracle Database 12*c*, FAN uses ONS (Oracle Notification Service)
CLB_GOAL	VARCHAR2(5)		Connection load balancing goal. When using run-time load balancing, GOAL=SERVICE_TIME or THROUGHPUT, set to SHORT. For a session count per service only, use LONG.
EDITION	VARCHAR2(128)		A non-NULL value specifies the initial session edition for subsequent database connections that use the service and do not specify an edition. A NULL value has no effect.
COMMIT_OUTCOME	VARCHAR2(3)		For Transaction Guard and Database Native Transaction Guard, indicates whether the database service associated with the user session has the COMMIT_OUTCOME service attribute enabled (YES) or not (NO). This attribute applies on a per session basis and is set at connect time. When the value of this column is YES, the commit status is managed for all supported transaction types and the outcome of a COMMIT transaction is preserved after the COMMIT has executed. Refer to the COMMIT_OUTCOME_FASTPATH column to view the preferred method for preserving the commit outcome. **See Also:** *Oracle Database Development Guide* for information about preserving the commit outcome

Column	Datatype	NULL	Description
RETENTION_TIMEOUT	NUMBER		For Transaction Guard and Database Native Transaction Guard, when COMMIT_OUTCOME = YES, this value indicates the amount of time (in seconds) that the commit outcome is retained in the database.
REPLAY_INITIATION_TIMEOUT	NUMBER		For Application Continuity, indicates a time period (in seconds) after which the request will not be replayed. The time period starts at the first request submission. The default value is 300 seconds, which is 5 minutes.
SESSION_STATE_CONSISTENCY	VARCHAR2(128)		Describes how non-transactional is changed during a request. This parameter is considered only if failover_type is set to TRANSACTION for Application Continuity. Examples of session state are NLS settings, optimizer preferences, event settings, PL/SQL global variables, temporary tables, advanced queues, LOBs and result cache. If non-transactional values change after the request starts, the default value of DYNAMIC should be set. Almost all applications should use DYNAMIC mode. If you are unsure, use DYNAMIC mode.
GLOBAL_SERVICE	VARCHAR2(3)		Indicates whether the service is global. A global service is managed by Global Data Services (GDS) and can be provided by multiple databases that contain replicated data. Possible values: • YES: Indicates the service is global • NO: Indicates the service is not global This attribute is set when using GDS. It cannot be set by a user.
PDB	VARCHAR2(128)		Name of a PDB associated with a given service. Will contain NULL for a non-CDB or if the service is not associated with a PDB (that is, connecting to a CDB using this service will cause a user to connect to the root.) When managing services for a PDB, use SRVCTL for Oracle RAC and Oracle RAC One Node databases, or connect to that PDB if it is a single instance (not RAC). The PDB attribute shows which PDB has the service. It cannot be set or modified explicitly.
SQL_TRANSLATION_PROFILE	VARCHAR2(261)		A non-NULL value specifies the initial SQL translation profile for subsequent database connections that use the service and do not specify a SQL translation profile. A NULL value has no effect.
MAX_LAG_TIME	VARCHAR2(128)		The maximum replication lag (in seconds) that is acceptable for a data replica to be used for providing the database service. Can only be specified for global services using the Global Data Services (GDS) interfaces. It is not supported to change this value at local databases.

Column	Datatype	NULL	Description
GSM_FLAGS	NUMBER		Flags specific to Global Data Services (GDS). Can only be specified for global services using the GDS interfaces. It is not supported to change these values at local databases.
PQ_SVC	VARCHAR2(64)		Name of the associated parallel query rim service
STOP_OPTION	VARCHAR2(13)		Stop option for sessions of this service for planned maintenance
FAILOVER_RESTORE	VARCHAR2(6)		Indicates whether sessions recover their commonly used session state (like NLS, schema) when they are failed over with TAF
DRAIN_TIMEOUT	NUMBER		Number of seconds to wait for sessions to be drained
TABLE_FAMILY_ID	NUMBER		Sharded table family ID associated with the service
PLACEMENT_POLICY	NUMBER		Placement policy for the service. Possible values: • 0: PDB-NONE • 1: PDB-SINGLETON • 2: PDB-UNIFORM **Note:** Values other than 0 are applicable only in the ATP-Dedicated Cloud in an Oracle RAC environment.
RESET_STATE	VARCHAR2(6)		Reset state for the service. Possible values: • LEVEL1 • NONE
PLACEMENT_TEMPLATE	VARCHAR2(64)		Reserved for future use

Column	Datatype	NULL	Description
COMMIT_OUTCOME_FASTPATH	VARCHAR2(3)		For Transaction Guard and Database Native Transaction Guard, when COMMIT_OUTCOME = YES, the value of this column indicates the preferred method for preserving the commit outcome. Possible values: • YES - Database Native Transaction Guard is used. Each transaction is assigned a unique transaction identifier (DB XID) in the database. The DB XID and status of the corresponding transaction are maintained persistently in a transaction table. Note that if COMMIT_OUTCOME = YES, then the value of COMMIT_OUTCOME_FASTPATH defaults to YES. • NO - Transaction Guard is used. A logical transaction ID (LTXID) is set for each user session at login and at each successful commit. LTXIDs are used only when the commit is not in the same round-trip to the database as the start of the transaction. Moreover, some transaction types, such as commit on success transactions, DDL transactions, and PL/SQL transactions, will continue to use LTXIDs in the same round-trip. When Transaction Guard is used, the outcome of a COMMIT transaction is known. If there is an outage, the application can use DBMS_APP_CONT.GET_LTXID_OUTCOME to return a reliable status for the last in-flight work. **See Also:** *Oracle Real Application Clusters Administration and Deployment Guide* for information about logical transaction IDs
TRUE_CACHE_SERVICE	VARCHAR2(64)		True Cache service associated with this database service
VCSPARE1	VARCHAR2(1024)		Reserved for internal use
NSPARE1	NUMBER		Reserved for internal use

See Also:

- "DBA_SERVICES"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APP_CONT.GET_LTXID_OUTCOME procedure

4.90 ALL_SOURCE

ALL_SOURCE describes the text source of the stored objects accessible to the current user.

Related Views

- DBA_SOURCE describes the text source of all stored objects in the database.

- USER_SOURCE describes the text source of the stored objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
NAME	VARCHAR2(128)	NOT NULL	Name of the object
TYPE	VARCHAR2(12)		Type of object: FUNCTION, JAVA SOURCE, PACKAGE, PACKAGE BODY, PROCEDURE, TRIGGER, TYPE, TYPE BODY
LINE	NUMBER	NOT NULL	Line number of this line of source
TEXT	VARCHAR2(4000)		Text source of the stored object
ORIGIN_CON_ID	VARCHAR2(256)		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)

See Also:

- "DBA_SOURCE"
- "USER_SOURCE"

4.91 ALL_SOURCE_AE

ALL_SOURCE_AE describes the text source of the stored objects (across all editions) accessible to the current user.

Related Views

- DBA_SOURCE_AE describes the text source of all stored objects (across all editions) in the database.
- USER_SOURCE_AE describes the text source of the stored objects (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the object
NAME	VARCHAR2(128)		Name of the object

Column	Datatype	NULL	Description
TYPE	VARCHAR2(12)		Type of the object: • TYPE • TYPE BODY • PROCEDURE • FUNCTION • PACKAGE • PACKAGE BODY • LIBRARY • JAVA SOURCE
LINE	NUMBER		Line number of this line of source
TEXT	VARCHAR2(4000)		Source text
EDITION_NAME	VARCHAR2(128)		Name of the Edition
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)

See Also:

- "DBA_SOURCE_AE"
- "USER_SOURCE_AE"

4.92 ALL_SQL_TRANSLATION_PROFILES

ALL_SQL_TRANSLATION_PROFILES describes all SQL translation profiles accessible to the user.

Related Views

- DBA_SQL_TRANSLATION_PROFILES describes all SQL translation profiles in the database.
- USER_SQL_TRANSLATION_PROFILES describes all SQL translation profiles owned by the user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the SQL translation profile
PROFILE_NAME	VARCHAR2(128)	NOT NULL	Name of the SQL translation profile
TRANSLATOR	VARCHAR2(261)		The translator package
FOREIGN_SQL_SYNTAX	VARCHAR2(5)		Indicates whether the SQL syntax is foreign. Possible values: • TRUE • FALSE

Column	Datatype	NULL	Description
TRANSLATE_NEW_SQL	VARCHAR2(5)		Indicates whether to translate new SQL statements and errors using the translator. Possible values: • TRUE • FALSE
RAISE_TRANSLATION_ERROR	VARCHAR2(5)		Indicates whether to raise translation error. Possible values: • TRUE • FALSE
LOG_TRANSLATION_ERROR	VARCHAR2(5)		Indicates whether to log translation error. Possible values: • TRUE • FALSE
TRACE_TRANSLATION	VARCHAR2(5)		Indicates whether to trace translation. Possible values: • TRUE • FALSE
LOG_ERRORS	VARCHAR2(5)		Indicates whether there are log errors (TRUE) or not (FALSE)

See Also:

- "DBA_SQL_TRANSLATION_PROFILES"
- "USER_SQL_TRANSLATION_PROFILES"

4.93 ALL_SQL_TRANSLATIONS

ALL_SQL_TRANSLATIONS describes all SQL translations accessible to the user.

Related Views

- DBA_SQL_TRANSLATIONS describes all SQL translations in the database.
- USER_SQL_TRANSLATIONS describes all SQL translations owned by the user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the SQL translation profile
PROFILE_NAME	VARCHAR2(128)	NOT NULL	Name of the SQL translation profile
SQL_TEXT	CLOB	NOT NULL	The SQL statement
TRANSLATED_TEXT	CLOB		The translated SQL statement
SQL_ID	VARCHAR2(13)	NOT NULL	SQL identifier of the SQL statement
HASH_VALUE	NUMBER	NOT NULL	Hash value of the SQL statement

Column	Datatype	NULL	Description
ENABLED	VARCHAR2(5)		Displays whether the translation is enabled. Possible values: • TRUE • FALSE
REGISTRATION_TIME	TIMESTAMP(6)		Time the translation was registered
CLIENT_INFO	VARCHAR2(64)		Client information when the SQL was parsed and the translation was registered
MODULE	VARCHAR2(64)		Module when the SQL was parsed and the translation was registered
ACTION	VARCHAR2(64)		Action when the SQL was parsed and the translation was registered
PARSING_USER_ID	NUMBER		Current user ID when the SQL was parsed and the translation was registered
PARSING_SCHEMA_ID	NUMBER		Current schema ID when the SQL was parsed and the translation was registered
COMMENTS	VARCHAR2(4000)		Comment on the translation
ERROR_CODE	NUMBER		Last error code when the SQL was run
ERROR_SOURCE	VARCHAR2(9)		Source of the last error
TRANSLATION_METHOD	VARCHAR2(10)		Method used to translate the SQL during the last error
DICTIONARY_SQL_ID	VARCHAR2(13)		SQL identifier of the SQL text in the translation dictionary used to translate the SQL during the last error

See Also:

- "DBA_SQL_TRANSLATIONS"
- "USER_SQL_TRANSLATIONS"

4.94 ALL_SQLJ_TYPE_ATTRS

ALL_SQLJ_TYPE_ATTRS describes the attributes of the SQLJ object types accessible to the current user.

Related Views

- DBA_SQLJ_TYPE_ATTRS describes the attributes of all SQLJ object types in the database.
- USER_SQLJ_TYPE_ATTRS describes the attributes of the object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the type
TYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the type

Column	Datatype	NULL	Description
ATTR_NAME	VARCHAR2(128)	NOT NULL	Name of the attribute
EXTERNAL_ATTR_NAME	VARCHAR2(4000)		External name of the attribute
ATTR_TYPE_MOD	VARCHAR2(7)		Type modifier of the attribute: • REF • POINTER
ATTR_TYPE_OWNER	VARCHAR2(128)		Owner of the type of the attribute
ATTR_TYPE_NAME	VARCHAR2(128)		Name of the type of the attribute
LENGTH	NUMBER		Length of the CHAR attribute, or maximum length of the VARCHAR or VARCHAR2 attribute.
PRECISION	NUMBER		Decimal precision of the NUMBER or DECIMAL attribute, or binary precision of the FLOAT attribute.
SCALE	NUMBER		Scale of the NUMBER or DECIMAL attribute
CHARACTER_SET _NAME	VARCHAR2(44)		Character set name of the attribute (CHAR_CS or NCHAR_CS)
ATTR_NO	NUMBER	NOT NULL	Syntactical order number or position of the attribute as specified in the type specification or CREATE TYPE statement (not to be used as an ID number)
INHERITED	VARCHAR2(3)		Indicates whether the attribute is inherited from a supertype (YES) or not (NO)

See Also:

- "DBA_SQLJ_TYPE_ATTRS"
- "USER_SQLJ_TYPE_ATTRS"

4.95 ALL_SQLJ_TYPE_METHODS

ALL_SQLJ_TYPE_METHODS describes the methods of the SQLJ object types accessible to the current user.

Related Views

- DBA_SQLJ_TYPE_METHODS describes the methods of all SQLJ object types in the database.
- USER_SQLJ_TYPE_METHODS describes the methods of the SQLJ object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the type
TYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the type
METHOD_NAME	VARCHAR2(128)	NOT NULL	Name of the method

Column	Datatype	NULL	Description
EXTERNAL_VAR_NAME	VARCHAR2(4000)		Name of the external variable
METHOD_NO	NUMBER	NOT NULL	Method number that distinguishes overloaded methods (not to be used as an ID number)
METHOD_TYPE	VARCHAR2(6)		Type of the method: • MAP • ORDER • PUBLIC
PARAMETERS	NUMBER	NOT NULL	Number of parameters to the method
RESULTS	NUMBER	NOT NULL	Number of results returned by the method
FINAL	VARCHAR2(3)		Indicates whether the method is final (YES) or not (NO)
INSTANTIABLE	VARCHAR2(3)		Indicates whether the method is instantiable (YES) or not (NO)
OVERRIDING	VARCHAR2(3)		Indicates whether the method is overriding a supertype method (YES) or not (NO)
INHERITED	VARCHAR2(3)		Indicates whether the method is inherited from a supertype (YES) or not (NO)

See Also:

- "DBA_SQLJ_TYPE_METHODS"
- "USER_SQLJ_TYPE_METHODS"

4.96 ALL_SQLJ_TYPES

ALL_SQLJ_TYPES describes the SQLJ object types accessible to the current user.

Related Views

- DBA_SQLJ_TYPES describes all SQLJ object types in the database.
- USER_SQLJ_TYPES describes the SQLJ object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the type
TYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the type
TYPE_OID	RAW(16)	NOT NULL	Object identifier (OID) of the type
EXTERNAL_NAME	VARCHAR2(4000)		External class name of the type

Column	Datatype	NULL	Description
USING	VARCHAR2(21)		Representation of the type: • SQLData • CustomDatum • Serializable • Serializable Internal • ORAData
TYPECODE	VARCHAR2(128)		Typecode of the type
ATTRIBUTES	NUMBER		Number of attributes (if any) in the type
METHODS	NUMBER		Number of methods (if any) in the type
PREDEFINED	VARCHAR2(3)		Indicates whether the type is a predefined type (YES) or not (NO)
INCOMPLETE	VARCHAR2(3)		Indicates whether the type is an incomplete type (YES) or not (NO)
FINAL	VARCHAR2(3)		Indicates whether the type is a final type (YES) or not (NO)
INSTANTIABLE	VARCHAR2(3)		Indicates whether the type is an instantiable type (YES) or not (NO)
SUPERTYPE_OWNER	VARCHAR2(128)		Owner of the supertype (NULL if type is not a subtype)
SUPERTYPE_NAME	VARCHAR2(128)		Name of the supertype (NULL if type is not a subtype)
LOCAL_ATTRIBUTES	NUMBER		Number of local (not inherited) attributes (if any) in the subtype
LOCAL_METHODS	NUMBER		Number of local (not inherited) methods (if any) in the subtype

See Also:

- "DBA_SQLJ_TYPES"
- "USER_SQLJ_TYPES"

4.97 ALL_SQLSET

ALL_SQLSET displays information about all SQL tuning sets accessible to the current user.

Related Views

- DBA_SQLSET displays information about all SQL tuning sets in the database.
- USER_SQLSET displays information about the SQL tuning sets owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
NAME	VARCHAR2(128)	NOT NULL	Name of the SQL tuning set
ID	NUMBER	NOT NULL	SQL tuning set identifier
CON_DBID	NUMBER	NOT NULL	The database ID of the PDB
OWNER	VARCHAR2(128)		Owner of the SQL tuning set
DESCRIPTION	VARCHAR2(256)		Description of the SQL tuning set
CREATED	DATE		Date the SQL tuning set was created
LAST_MODIFIED	DATE		Date the SQL tuning set was last modified
STATEMENT_COUNT	NUMBER		Number of statements in the SQL tuning set

See Also:

- "DBA_SQLSET"
- "USER_SQLSET"

4.98 ALL_SQLSET_BINDS

ALL_SQLSET_BINDS displays the bind values associated with all SQL tuning sets accessible to the current user.

Related Views

- DBA_SQLSET_BINDS displays the bind values associated with all SQL tuning sets in the database.
- USER_SQLSET_BINDS displays the bind values associated with the SQL tuning sets owned by the current user. This view does not display the SQLSET_OWNER column.

Column	Datatype	NULL	Description
SQLSET_NAME	VARCHAR2(128)		Name of the SQL tuning set for the statement
SQLSET_OWNER	VARCHAR2(128)		User name of the SQL tuning set owner
SQLSET_ID	NUMBER		ID of the SQL tuning set for the statement
CON_DBID	NUMBER		The database ID of the PDB
SQL_ID	VARCHAR2(13)		SQL identifier of the parent cursor in the library cache
FORCE_MATCHING_SIGNATURE	NUMBER		The signature used when the CURSOR_SHARING parameter is set to FORCE
PLAN_HASH_VALUE	NUMBER		Numerical representation of the SQL plan for the cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line-by-line).
POSITION	NUMBER		Bind position

Column	Datatype	NULL	Description
VALUE	ANYDATA		Bind value. This column is NULL for PL/SQL bind types.
CAPTURED	CHAR(1)		Binds captured
SQL_SEQ	NUMBER		SQL sequence

> **See Also:**
>
> - "DBA_SQLSET_BINDS"
> - "USER_SQLSET_BINDS"

4.99 ALL_SQLSET_PLANS

ALL_SQLSET_PLANS describes captured plans for statements in the SQL tuning sets accessible to the current user.

Related Views

- DBA_SQLSET_PLANS describes captured plans in the SQL tuning sets in the database.
- USER_SQLSET_PLANS describes captured plans for statements in the SQL tuning sets owned by the current user. This view does not display the SQLSET_OWNER column.

Column	Datatype	NULL	Description
SQLSET_NAME	VARCHAR2(128)	NOT NULL	Name of SQL tuning set for the statement
SQLSET_OWNER	VARCHAR2(128)		User name of SQL tuning set owner
SQLSET_ID	NUMBER	NOT NULL	ID of SQL tuning set for the statement
CON_DBID	NUMBER	NOT NULL	The database ID of the PDB
SQL_ID	VARCHAR2(13)	NOT NULL	SQL identifier of the parent cursor in the library cache
FORCE_MATCHING_SIGNATURE	NUMBER	NOT NULL	The signature used when the CURSOR_SHARING parameter is set to FORCE
PLAN_HASH_VALUE	NUMBER	NOT NULL	Numerical representation of the SQL plan for the cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line-by-line).
SQL_SEQ	NUMBER	NOT NULL	SQL sequence
STATEMENT_ID	VARCHAR2(128)		Statement ID
PLAN_ID	NUMBER		Plan ID
TIMESTAMP	DATE		Date and time timestamp
REMARKS	VARCHAR2(4000)		Remarks

Column	Datatype	NULL	Description
OPERATION	VARCHAR2(128)		Name of the internal operation performed in this step (for example, TABLE ACCESS)
OPTIONS	VARCHAR2(255)		A variation on the operation described in the OPERATION column (for example, FULL)
OBJECT_NODE	VARCHAR2(128)		Name of the database link used to reference the object (a table name or view name). For local queries that use parallel execution, this column describes the order in which output from operations is consumed.
OBJECT_OWNER	VARCHAR2(128)		Name of the user who owns the schema containing the table or index
OBJECT_NAME	VARCHAR2(128)		Name of the table or index
OBJECT_ALIAS	VARCHAR2(261)		Alias for the object
OBJECT_INSTANCE	NUMBER(38)		Instance number for the object
OBJECT_TYPE	VARCHAR2(128)		Type of the object
OPTIMIZER	VARCHAR2(255)		Current mode of the optimizer for the first row in the plan (statement line), for example, CHOOSE. When the operation is a database access (for example, TABLE ACCESS), this column indicates whether or not the object is analyzed.
SEARCH_COLUMNS	NUMBER		Number of index columns with start and stop keys (that is, the number of columns with matching predicates)
ID	NUMBER(38)	NOT NULL	A number assigned to each step in the execution plan
PARENT_ID	NUMBER(38)		ID of the next execution step that operates on the output of the current step
DEPTH	NUMBER(38)		Depth (or level) of the operation in the tree. It is not necessary to issue a CONNECT BY statement to get the level information, which is generally used to indent the rows from the PLAN_TABLE table. The root operation (statement) is level 0.
POSITION	NUMBER(38)		Order of processing for all operations that have the same PARENT_ID.
COST	NUMBER(38)		Cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
CARDINALITY	NUMBER(38)		Estimate, made by the cost-based optimizer, of the number of rows produced by the operation
BYTES	NUMBER(38)		Estimate, made by the cost-based optimizer, of the number of bytes produced by the operation
OTHER_TAG	VARCHAR2(255)		Describes the contents of the OTHER column. For information about values, see *Oracle Database SQL Tuning Guide*.
PARTITION_START	VARCHAR2(255)		Start partition of a range of accessed partitions
PARTITION_STOP	VARCHAR2(255)		Stop partition of a range of accessed partitions

Column	Datatype	NULL	Description
PARTITION_ID	NUMBER(38)		Step that computes the pair of values of the PARTITION_START and PARTITION_STOP columns
OTHER	LONG		Other information specific to the execution step that users may find useful. For information about values, see *Oracle Database SQL Tuning Guide*.
DISTRIBUTION	VARCHAR2(128)		Stores the method used to distribute rows from producer query servers to consumer query servers
CPU_COST	NUMBER(38)		CPU cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
IO_COST	NUMBER(38)		I/O cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
TEMP_SPACE	NUMBER(38)		Temporary space usage of the operation (sort or hash join) as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
ACCESS_PREDICATES	VARCHAR2(4000)		Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.
FILTER_PREDICATES	VARCHAR2(4000)		Predicates used to filter rows before producing them
PROJECTION	VARCHAR2(4000)		Expressions produced by the operation
TIME	NUMBER(38)		Elapsed time (in seconds) of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
QBLOCK_NAME	VARCHAR2(128)		Name of the query block
OTHER_XML	CLOB		Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML since multiple pieces of information can be stored there. This includes: • Name of the schema against which the query was parsed • Release number of the Oracle Database that produced the explain plan • Hash value associated with the execution plan • Name (if any) of the outline or the SQL profile used to build the execution plan • Indication of whether or not dynamic statistics were used to produce the plan • The outline data, a set of optimizer hints that can be used to regenerate the same plan For further information about values, see *Oracle Database SQL Tuning Guide*.
EXECUTIONS	NUMBER		Number of times the plan has been executed

Column	Datatype	NULL	Description
STARTS	NUMBER		Number of times this operation has been started, accumulated over the past executions
OUTPUT_ROWS	NUMBER		Number of rows produced by the row source, accumulated over the past executions
CR_BUFFER_GETS	NUMBER		Number of buffers received in consistent mode, accumulated over the past executions. Buffers are usually retrieved in consistent mode for queries.
CU_BUFFER_GETS	NUMBER		Number of buffers retrieved in current mode, accumulated over the past executions. Buffers are retrieved in current mode for statements such as INSERT, UPDATE, and DELETE.
DISK_READS	NUMBER		Number of physical disk reads performed by the operation, accumulated over the past executions
DISK_WRITES	NUMBER		Number of physical disk writes performed by the operation, accumulated over the past executions
ELAPSED_TIME	NUMBER		Elapsed time (in microseconds) corresponding to this operation, accumulated over the past executions
LAST_STARTS	NUMBER		Number of times this operation has been started, during the last execution
LAST_OUTPUT_ROWS	NUMBER		Number of rows produced by the row source, during the last execution
LAST_CR_BUFFER_GETS	NUMBER		Number of buffers retrieved in consistent mode, during the last execution. Buffers are usually retrieved in consistent mode for queries.
LAST_CU_BUFFER_GETS	NUMBER		Number of buffers retrieved in current mode, during the last execution. Buffers are retrieved in current mode for statements such as INSERT, UPDATE, and DELETE.
LAST_DISK_READS	NUMBER		Number of physical disk reads performed by the operation, during the last execution
LAST_DISK_WRITES	NUMBER		Number of physical disk writes performed by the operation, during the last execution
LAST_ELAPSED_TIME	NUMBER		Elapsed time (in microseconds) corresponding to this operation, during the last execution
POLICY	VARCHAR2(10)		Sizing policy for this work area: • MANUAL • AUTO
ESTIMATED_OPTIMAL_SIZE	NUMBER		Estimated size (in KB) required by this work area to execute the operation completely in memory (optimal execution). This is either derived from optimizer statistics or from previous executions.
ESTIMATED_ONEPASS_SIZE	NUMBER		Estimated size (in KB) required by this work area to execute the operation in a single pass. This is either derived from optimizer statistics or from previous executions.
LAST_MEMORY_USED	NUMBER		Memory size (in KB) used by this work area during the last execution of the cursor

Column	Datatype	NULL	Description
LAST_EXECUTION	VARCHAR2(10)		Indicates whether this work area ran using OPTIMAL, ONE PASS, or under ONE PASS memory requirement (MULTI-PASS), during the last execution of the cursor
LAST_DEGREE	NUMBER		Degree of parallelism used, during the last execution of the cursor
TOTAL_EXECUTIONS	NUMBER		Number of times this work area was active
OPTIMAL_EXECUTIONS	NUMBER		Number of times this work area ran in optimal mode
ONEPASS_EXECUTIONS	NUMBER		Number of times this work area ran in one pass mode
MULTIPASSES_EXECUTIONS	NUMBER		Number of times this work area ran below the one pass memory requirement
ACTIVE_TIME	NUMBER		Average time this work area is active (in hundredths of a second)
MAX_TEMPSEG_SIZE	NUMBER		Maximum temporary segment size (in bytes) created by an instantiation of this work area. This column is null if this work area has never spilled to disk.
LAST_TEMPSEG_SIZE	NUMBER		Temporary segment size (in bytes) created in the last instantiation of this work area. This column is null if the last instantiation of this work area did not spill to disk.

See Also:

- "DBA_SQLSET_PLANS"
- "USER_SQLSET_PLANS"

4.100 ALL_SQLSET_REFERENCES

ALL_SQLSET_REFERENCES describes whether or not the SQL tuning sets accessible to the current user are active.

Related Views

- DBA_SQLSET_REFERENCES describes whether or not all SQL tuning sets in the database are active. A SQL tuning set cannot be dropped if it is referenced.
- USER_SQLSET_REFERENCES describes whether or not the SQL tuning sets owned by the current user are active.

Column	Datatype	NULL	Description
SQLSET_NAME	VARCHAR2(128)	NOT NULL	Name of the SQL tuning set
SQLSET_OWNER	VARCHAR2(128)		User name of SQL tuning set owner

Column	Datatype	NULL	Description
SQLSET_ID	NUMBER	NOT NULL	Identifier of the SQL tuning set
ID	NUMBER	NOT NULL	Reference identifier
OWNER	VARCHAR2(128)		User who registered to use the SQL tuning set
DESCRIPTION	VARCHAR2(256)		Description of the usage of the SQL tuning set
CREATED	DATE		Date the reference was created

See Also:

- "DBA_SQLSET_REFERENCES"
- "USER_SQLSET_REFERENCES"

4.101 ALL_SQLSET_STATEMENTS

ALL_SQLSET_STATEMENTS displays information about the SQL statements, along with their statistics, that form all SQL tuning sets accessible to the current user.

Related Views

- DBA_SQLSET_STATEMENTS displays information about the SQL statements, along with their statistics, that form all SQL tuning sets in the database.
- USER_SQLSET_STATEMENTS displays information about the SQL statements, along with their statistics, that form the SQL tuning sets owned by the current user. This view does not display the SQLSET_OWNER column.

Column	Datatype	NULL	Description
SQLSET_NAME	VARCHAR2(128)	NOT NULL	Name of the SQL tuning set for the statement
SQLSET_OWNER	VARCHAR2(128)		User name of the SQL tuning set owner
SQLSET_ID	NUMBER	NOT NULL	ID of the SQL tuning set for the statement
CON_DBID	NUMBER	NOT NULL	The database ID of the PDB
SQL_ID	VARCHAR2(13)	NOT NULL	SQL identifier of the parent cursor in the library cache
FORCE_MATCHING_SIGNATURE	NUMBER	NOT NULL	The signature used when the CURSOR_SHARING parameter is set to FORCE
SQL_TEXT	CLOB		Full text for the SQL statement exposed as a CLOB column.
PARSING_SCHEMA_NAME	VARCHAR2(128)		Name of the user in whose schema the statement was parsed
PLAN_HASH_VALUE	NUMBER	NOT NULL	Hash value for the plan corresponding to statistics in this record
BIND_DATA	RAW(2000)		Bind data
BINDS_CAPTURED	CHAR(1)		Binds captured

Column	Datatype	NULL	Description
MODULE	VARCHAR2(64)		Contains the name of the module that was executing when the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_MODULE
ACTION	VARCHAR2(64)		Contains the name of the action that was executing when the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_ACTION
ELAPSED_TIME	NUMBER		Elapsed time (in microseconds) used by this cursor for parsing, executing, and fetching
CPU_TIME	NUMBER		CPU time (in microseconds) used by this cursor for parsing, executing, and fetching
BUFFER_GETS	NUMBER		Number of buffer gets for this child cursor
DISK_READS	NUMBER		Number of disk reads for this child cursor
DIRECT_WRITES	NUMBER		Number of direct writes for this child cursor
ROWS_PROCESSED	NUMBER		Total number of rows that the parsed SQL statement returns
FETCHES	NUMBER		Number of fetches associated with the SQL statement
EXECUTIONS	NUMBER		Number of executions that took place on this object since it was brought into the library cache
END_OF_FETCH_COUNT	NUMBER		Number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic in not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed. By definition, the value of the END_OF_FETCH_COUNT column should be less than, or equal to, the value of the EXECUTIONS column.
OPTIMIZER_COST	NUMBER		Cost of this query, given by the optimizer
OPTIMIZER_ENV	RAW(2000)		Optimizer environment
PRIORITY	NUMBER		User-defined priority
COMMAND_TYPE	NUMBER		Oracle command type definition
FIRST_LOAD_TIME	VARCHAR2(19)		Timestamp of the parent creation time
STAT_PERIOD	NUMBER		Time (in seconds) during which the statistics of the SQL statement were collected
ACTIVE_STAT_PERIOD	NUMBER		Effective time (in seconds) during which the SQL statement was active
OTHER	CLOB		Client data, specified by the user, for this statement
PLAN_TIMESTAMP	DATE		Timestamp for the plan corresponding to the statistics in this record
SQL_SEQ	NUMBER	NOT NULL	SQL sequence
LAST_EXEC_START_TIME	VARCHAR2(19)		For SQLs captured from the cursor cache, this is the time when the most recent execution of this SQL started

See Also:

- "DBA_SQLSET_STATEMENTS"
- "USER_SQLSET_STATEMENTS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_APPLICATION_INFO.SET_MODULE` procedure
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_APPLICATION_INFO.SET_ACTION` procedure

4.102 ALL_STAT_EXTENSIONS

`ALL_STAT_EXTENSIONS` displays information about the optimizer statistics extensions accessible to the current user.

Related Views

- `DBA_STAT_EXTENSIONS` displays information about all optimizer statistics extensions in the database.
- `USER_STAT_EXTENSIONS` displays information about the optimizer statistics extensions owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
`OWNER`	`VARCHAR2(128)`	`NOT NULL`	Owner of the extension
`TABLE_NAME`	`VARCHAR2(128)`	`NOT NULL`	Name of the table to which the extension belongs
`EXTENSION_NAME`	`VARCHAR2(128)`	`NOT NULL`	Name of the statistics extension
`EXTENSION`	`CLOB`		Extension (the expression or column group)
`CREATOR`	`VARCHAR2(6)`		Creator of the extension: • `USER` • `SYSTEM`
`DROPPABLE`	`VARCHAR2(3)`		Indicates whether the extension is droppable using `DBMS_STATS.DROP_EXTENDED_STATS` (`YES`) or not (`NO`)

See Also:

- "DBA_STAT_EXTENSIONS"
- "USER_STAT_EXTENSIONS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_STATS.DROP_EXTENDED_STATS` procedure

4.103 ALL_STATEMENTS

ALL_STATEMENTS describes all SQL statements in stored PL/SQL objects accessible to the user.

Related Views

- DBA_STATEMENTS describes SQL statements in stored PL/SQL objects accessible to SYS.
- USER_STATEMENTS describes SQL statements in stored PL/SQL objects accessible to the user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the statement
SIGNATURE	VARCHAR2(32)		Signature of the statement. Every statement type has a unique PL/Scope signature that identifies that instance of th statement.
TYPE	VARCHAR2(17)		Type of the statement. Statement types correspond to statements that can be used in PL/SQL to execute or otherwise interact with SQL: • SELECT • UPDATE • INSERT • DELETE • MERGE • CLOSE • FETCH • OPEN • SAVEPOINT • COMMIT • SET_TRANSACTION • ROLLBACK • LOCK_TABLE • EXECUTE_IMMEDIATE
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object where the statement usage occurred
OBJECT_TYPE	VARCHAR2(12)		Type of the object where the statement usage occurred
USAGE_ID	NUMBER		Unique key for a statement usage within the object
LINE	NUMBER		Line number of the statement usage
COL	NUMBER		Column number of the statement usage
USAGE_CONTEXT_ID	NUMBER		Context USAGE_ID of an statement usage
SQL_ID	VARCHAR2(13)		SQL ID of the SQL statement. The value of this column is null for statements that do not have a SQL ID.

Column	Datatype	NULL	Description
HAS_HINT	VARCHAR2(3)		YES if the SQL statement contains a hint, NO otherwise. If a hint appears inside of a subquery, then HAS_HINT will be YES for the containing statement or statements of the subquery as well as for the subquery itself.
HAS_INTO_BULK	VARCHAR2(3)		Indicates whether the statement contains a BULK_COLLECT clause (YES) or not (NO)
HAS_INTO_RETURNING	VARCHAR2(3)		Indicates whether the statement contains a RETURNING_INTO clause (YES) or not (NO)
HAS_INTO_RECORD	VARCHAR2(3)		Indicates whether the statement returns results into a PL/SQL record (YES) or not (NO)
HAS_CURRENT_OF	VARCHAR2(3)		Indicates whether the statement contains a HAS_CURRENT_OF clause (YES) or not (NO)
HAS_FOR_UPDATE	VARCHAR2(3)		Indicates whether the statement contains a HAS_FOR_UPDATE clause (YES) or not (NO)
HAS_IN_BINDS	VARCHAR2(3)		Indicates whether the statement contains an IN_BINDS clause (YES) or not (NO)
TEXT	VARCHAR2(4000)		The normalized form of the statement, when the statement has a normalized form. These are typically the same statements that have a SQL ID. The column value is null when the statement does not have a normalized form.
FULL_TEXT	CLOB		Clob text of the SQL statement
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)

See Also:

- "DBA_STATEMENTS"
- "USER_STATEMENTS"

4.104 ALL_STORED_SETTINGS

ALL_STORED_SETTINGS provides information about the persistent parameter settings for stored PL/SQL units for which the current user has execute privileges.

Related Views

- DBA_STORED_SETTINGS lists information about the persistent parameter settings for stored PL/SQL units for which the current user has execute privileges. It also returns parameter

information for all objects in the database and is accessible only to users with the SELECT_CATALOG_ROLE privilege.

- USER_STORED_SETTINGS lists information about the persistent parameter settings for stored PL/SQL units, but only shows information about PL/SQL units owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Name of the database user owning the stored PL/SQL unit
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the PL/SQL unit
OBJECT_ID	NUMBER	NOT NULL	Object number of the PL/SQL unit
OBJECT_TYPE	VARCHAR2(12)		The type of PL/SQL unit: PROCEDURE, FUNCTION, PACKAGE, PACKAGE BODY, TRIGGER, TYPE, or TYPE BODY
PARAM_NAME	VARCHAR2(128)	NOT NULL	The name of the parameter stored persistently with the PL/SQL unit
PARAM_VALUE	VARCHAR2(4000)		The TO_CHAR() representation of the value of the persistently stored parameter. The width of this column is operating system dependent; however, it is never less than 255.
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)

Note:

This view is deprecated in favor of the ALL_PLSQL_OBJECT_SETTINGS view. Oracle recommends that you use ALL_PLSQL_OBJECT_SETTINGS instead. ALL_STORED_SETTINGS is retained for backward compatibility only.

See Also:

"ALL_PLSQL_OBJECT_SETTINGS"

4.105 ALL_STREAMS_GLOBAL_RULES

ALL_STREAMS_GLOBAL_RULES displays information about rules.

ALL_STREAMS_GLOBAL_RULES displays information about the following types of rules:

- Global rules created for the capture processes that enqueue the captured changes into queues accessible to the current user

- Global rules created for the propagations that have a source queue accessible to the current user
- Global rules created for the apply processes that dequeue events from queues accessible to the current user

This view does not contain information about rules created using the DBMS_RULE_ADM package.

Related View

DBA_STREAMS_GLOBAL_RULES displays information about the global rules created for all capture processes, propagations, and apply processes in the database.

Column	Datatype	NULL	Description
STREAMS_NAME	VARCHAR2(128)		Name of the Replication process or propagation
STREAMS_TYPE	VARCHAR2(11)		Type of the Replication process or propagation: • CAPTURE • PROPAGATION • APPLY
RULE_TYPE	VARCHAR2(9)		Type of the rule: • DML • DDL
INCLUDE_TAGGED_LCR	VARCHAR2(3)		Indicates whether a redo entry or logical change record (LCR) with a non-NULL tag is considered for capture, propagation, or apply (YES) or not (NO)
SOURCE_DATABASE	VARCHAR2(128)		Source database in the rule condition. The rule evaluates to true for a redo entry or logical change record (LCR) only if the redo entry or LCR contains this source database.
RULE_NAME	VARCHAR2(128)	NOT NULL	Name of the rule
RULE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule
RULE_CONDITION	VARCHAR2(4000)		First 4000 bytes of the system-generated rule condition evaluated by the rules engine

See Also:

- "DBA_STREAMS_GLOBAL_RULES"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_RULE_ADM package

4.106 ALL_STREAMS_MESSAGE_CONSUMERS

ALL_STREAMS_MESSAGE_CONSUMERS displays information about the Replication messaging clients accessible to the current user.

Related View

DBA_STREAMS_MESSAGE_CONSUMERS displays information about all Replication messaging clients in the database.

Column	Datatype	NULL	Description
STREAMS_NAME	VARCHAR2(128)	NOT NULL	Name of the messaging client
QUEUE_NAME	VARCHAR2(128)	NOT NULL	Name of the queue
QUEUE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the queue
RULE_SET_NAME	VARCHAR2(128)		Name of the positive rule set
RULE_SET_OWNER	VARCHAR2(128)		Owner of the positive rule set
NEGATIVE_RULE_SET_NAME	VARCHAR2(128)		Name of the negative rule set
NEGATIVE_RULE_SET_OWNER	VARCHAR2(128)		Owner of the negative rule set
NOTIFICATION_TYPE	VARCHAR2(9)		Type of the notification action: • PROCEDURE • MAIL • HTTP
NOTIFICATION_ACTION	VARCHAR2(256)		Notification action
NOTIFICATION_CONTEXT	ANYDATA		Context for the notification action

> **See Also:**
>
> "DBA_STREAMS_MESSAGE_CONSUMERS"

4.107 ALL_STREAMS_NEWLY_SUPPORTED

ALL_STREAMS_NEWLY_SUPPORTED displays information about the tables accessible to the current user that are newly supported by capture processes.

Related View

DBA_STREAMS_NEWLY_SUPPORTED displays information about all tables in the database that are newly supported by capture processes.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table

Column	Datatype	NULL	Description
REASON	VARCHAR2(39)		Reason why the table was not supported in a previous release: • IOT • column with user-defined type • unsupported column exists • object table • AQ queue table • temporary table • sub object • external table • materialized view • FILE column exists • materialized view log • materialized view container table • streams unsupported object • domain index
COMPATIBLE	CHAR(4)		Minimum database compatibility for capture processes to support the database object

See Also:

"DBA_STREAMS_NEWLY_SUPPORTED"

4.108 ALL_STREAMS_SCHEMA_RULES

ALL_STREAMS_SCHEMA_RULES displays information about several types of schema rules.

ALL_STREAMS_SCHEMA_RULES displays information about these types of schema rules:

- Schema rules created for the capture processes that enqueue the captured changes into queues accessible to the current user
- Schema rules created for the propagations that have a source queue accessible to the current user
- Schema rules created for the apply processes that dequeue events from queues accessible to the current user

This view does not contain information about rules created using the DBMS_RULE_ADM package.

Related View

DBA_STREAMS_SCHEMA_RULES displays information about the schema rules created for all capture processes, propagations, and apply processes in the database.

Column	Datatype	NULL	Description
STREAMS_NAME	VARCHAR2(128)		Name of the Replication process or propagation

Column	Datatype	NULL	Description
STREAMS_TYPE	VARCHAR2(11)		Type of the Replication process or propagation: • CAPTURE • PROPAGATION • APPLY
SCHEMA_NAME	VARCHAR2(128)		Schema name in the rule condition. The rule evaluates to true for a redo entry or logical change record (LCR) only if the redo entry or LCR contains this schema name.
RULE_TYPE	VARCHAR2(7)		Type of the rule: • DML • DDL
INCLUDE_TAGGED_LCR	VARCHAR2(3)		Indicates whether a redo entry or logical change record (LCR) with a non-NULL tag is considered for capture, propagation, or apply (YES) or not (NO)
SOURCE_DATABASE	VARCHAR2(128)		Source database in the rule condition. The rule evaluates to true for a redo entry or logical change record (LCR) only if the redo entry or LCR contains this source database.
RULE_NAME	VARCHAR2(128)	NOT NULL	Name of the rule
RULE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule
RULE_CONDITION	VARCHAR2(4000)		First 4000 bytes of the system-generated rule condition evaluated by the rules engine

See Also:

- "DBA_STREAMS_SCHEMA_RULES"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_RULE_ADM package

4.109 ALL_STREAMS_TABLE_RULES

ALL_STREAMS_TABLE_RULES displays information about several types of rules.

ALL_STREAMS_TABLE_RULES displays information about these types of table and subset rules:

- Table rules created for the capture processes that enqueue the captured changes into queues accessible to the current user
- Table rules created for the propagations that have a source queue accessible to the current user
- Table rules created for the apply processes that dequeue events from queues accessible to the current user
- Subset rules created for the apply processes that have a source queue accessible to the current user

This view does not contain information about rules created using the DBMS_RULE_ADM package.

Related View

DBA_STREAMS_TABLE_RULES displays information about the table rules created for all capture processes, propagations, and apply processes in the database.

Column	Datatype	NULL	Description
STREAMS_NAME	VARCHAR2(128)		Name of the Replication process or propagation
STREAMS_TYPE	VARCHAR2(12)		Type of the Replication process or propagation: • CAPTURE • PROPAGATION • APPLY • DEQUEUE
TABLE_OWNER	VARCHAR2(128)		Table owner in the rule condition. The rule evaluates to true for a redo entry or logical change record (LCR) only if the redo entry or LCR contains this table owner.
TABLE_NAME	VARCHAR2(128)		Table name in the rule condition. The rule evaluates to true for a redo entry or logical change record (LCR) only if the redo entry or LCR contains this table name.
RULE_TYPE	VARCHAR2(7)		Type of the rule: • DML • DDL
DML_CONDITION	VARCHAR2(4000)		Row subsetting condition, if the rule is a subset rule
SUBSETTING_OPERATION	VARCHAR2(6)		DML operation for row subsetting in the rule condition, if the rule is a subset rule: • INSERT • UPDATE • DELETE The rule evaluates to true for a logical change record (LCR) only if the LCR contains this command type after internal transformation.
INCLUDE_TAGGED_LCR	VARCHAR2(3)		Indicates whether a redo entry or logical change record (LCR) with a non-NULL tag is considered for capture, propagation, or apply (YES) or not (NO)
SOURCE_DATABASE	VARCHAR2(128)		Source database in the rule condition. The rule evaluates to true for a redo entry or logical change record (LCR) only if the redo entry or LCR contains this source database.
RULE_NAME	VARCHAR2(128)	NOT NULL	Name of the rule
RULE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule
RULE_CONDITION	VARCHAR2(4000)		First 4000 bytes of the system-generated rule condition evaluated by the rules engine

> **See Also:**
>
> - "DBA_STREAMS_TABLE_RULES"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_RULE_ADM package

4.110 ALL_STREAMS_TRANSFORM_FUNCTION

ALL_STREAMS_TRANSFORM_FUNCTION displays information about the rule-based transformation functions accessible to the current user.

Related View

DBA_STREAMS_TRANSFORM_FUNCTION displays information about all rule-based transformation functions in the database.

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule associated with the transformation function
RULE_NAME	VARCHAR2(128)	NOT NULL	Name of the rule associated with the transformation function
VALUE_TYPE	VARCHAR2(4000)		Type of the transformation function name. This type must be VARCHAR2 for a rule-based transformation to work properly.
TRANSFORM_FUNCTION_NAME	VARCHAR2(4000)		Name of the transformation function (NULL if VALUE_TYPE is not VARCHAR2)
CUSTOM_TYPE	VARCHAR2(11)		Type of the transformation function: • ONE TO ONE - One-to-one transformations • ONE TO MANY - One-to-many transformations

> **See Also:**
>
> "DBA_STREAMS_TRANSFORM_FUNCTION"

4.111 ALL_SUBPART_COL_STATISTICS

ALL_SUBPART_COL_STATISTICS describes column statistics and histogram information for subpartitions of partitioned objects accessible to the current user.

Related Views

- DBA_SUBPART_COL_STATISTICS provides this information for all subpartitions in the database.

- USER_SUBPART_COL_STATISTICS provides this information for subpartitions of all partitioned objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
SUBPARTITION_NAME	VARCHAR2(128)		Table subpartition name
COLUMN_NAME	VARCHAR2(4000)		Column name
NUM_DISTINCT	NUMBER		Number of distinct values in the column
LOW_VALUE	RAW(1000)		Low value in the column
HIGH_VALUE	RAW(1000)		High value in the column
DENSITY	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT.
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in histogram for the column
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this column
LAST_ANALYZED	DATE		Date on which this column was most recently analyzed
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics have been gathered or NO if statistics have not been gathered
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
NOTES	VARCHAR2(41)		Describes some additional properties of the statistics. For example, if the value is INCREMENTAL, the global statistics are derived from synopses, that is, the global statistics are incrementally maintained.
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
HISTOGRAM	VARCHAR2(15)		Indicates existence/type of histogram: • NONE • FREQUENCY • HEIGHT BALANCED • HYBRID • TOP-FREQUENCY

See Also:

- "DBA_SUBPART_COL_STATISTICS"
- "USER_SUBPART_COL_STATISTICS"

4.112 ALL_SUBPART_HISTOGRAMS

ALL_SUBPART_HISTOGRAMS displays the actual histogram data (end-points per histogram) for histograms on table subpartitions accessible to the current user.

Related Views

- DBA_SUBPART_HISTOGRAMS displays this information for all subpartitions in the database.
- USER_SUBPART_HISTOGRAMS displays this information for subpartitions of all partitioned objects owned by the current user. This view does not display the OWNER column.

> **Note:**
>
> These views are populated only if you collect statistics on the index using the DBMS_STATS package.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table
SUBPARTITION_NAME	VARCHAR2(128)		Table subpartition name
COLUMN_NAME	VARCHAR2(4000)		Column name
BUCKET_NUMBER	NUMBER		Bucket number
ENDPOINT_VALUE	NUMBER		Normalized endpoint values for this bucket
ENDPOINT_ACTUAL_VALUE	VARCHAR2(4000)		Actual (not normalized) string value of the endpoint for this bucket
ENDPOINT_ACTUAL_VALUE_RAW	RAW(1000)		Endpoint actual value in raw format
ENDPOINT_REPEAT_COUNT	NUMBER		Frequency of the endpoint (applies only to hybrid histograms, and is set to 0 for other histogram types)

> **See Also:**
>
> - "DBA_SUBPART_HISTOGRAMS"
> - "USER_SUBPART_HISTOGRAMS"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

4.113 ALL_SUBPART_KEY_COLUMNS

ALL_SUBPART_KEY_COLUMNS displays subpartitioning key columns for composite-partitioned tables (and local indexes on composite-partitioned tables) accessible to the current user.

Related Views

- DBA_SUBPART_KEY_COLUMNS displays this information for all subpartitions in the database.
- USER_SUBPART_KEY_COLUMNS displays this information for subpartitions of all partitioned objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the partitioned table or index
NAME	VARCHAR2(128)		Name of the partitioned table or index
OBJECT_TYPE	CHAR(5)		Object type: • TABLE • INDEX
COLUMN_NAME	VARCHAR2(4000)		Column name
COLUMN_POSITION	NUMBER		Position of the column within the subpartitioning key
COLLATED_COLUMN_ID	NUMBER		Internal sequence number of the column for which this column provides linguistic ordering

> **See Also:**
>
> - "DBA_SUBPART_KEY_COLUMNS"
> - "USER_SUBPART_KEY_COLUMNS"

4.114 ALL_SUBPARTITION_TEMPLATES

ALL_SUBPARTITION_TEMPLATES describes the subpartition templates accessible to the current user.

Related Views

- DBA_SUBPARTITION_TEMPLATES describes all subpartition templates in the database.
- USER_SUBPARTITION_TEMPLATES describes the subpartition templates owned by the current user. This view does not display the USER_NAME column.

Column	Datatype	NULL	Description
USER_NAME	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
SUBPARTITION_NAME	VARCHAR2(132)	NOT NULL	Name of the subpartition

Column	Datatype	NULL	Description
SUBPARTITION_POSITION	NUMBER		Position of the subpartition
TABLESPACE_NAME	VARCHAR2(30)		Tablespace name of the subpartition
HIGH_BOUND	LONG		Literal list values of the subpartition
COMPRESSION	VARCHAR2(4)		Compression values of COMPRESSION or NOCOMPRESSION can be specified in a subpartition template. The value in this column indicates whether the subpartition template specifies that for each new added composite partition, its subpartition data will be stored in compressed format (YES) or not (NO). If compression is not specified in the subpartition template, then the default is that data stored in newly-added subpartitions will not be stored in compressed format (NO).
INDEXING	VARCHAR2(4)		Indexing values of INDEXING ON or INDEXING OFF can be specified in a subpartition template. The value in this column indicates whether the subpartition template specifies that for each new added composite partition, its subpartition data will be considered for a partial index (ON) or not (OFF). If indexing is not specified in the subpartition template, then the default is that data stored in newly-added subpartitions will considered for a partial index (ON).
READ_ONLY	VARCHAR2(4)		Values of READ ONLY or READ WRITE can be specified in a subpartition template. The value in this column indicates whether the subpartition template specifies that for each new added composite partition, its subpartition data will be read only (YES) or not (NO). If the read clause is not specified in the subpartition template, then the default is that data stored in newly-added subpartitions will be read/write (NO).

See Also:

- "DBA_SUBPARTITION_TEMPLATES"
- "USER_SUBPARTITION_TEMPLATES"

4.115 ALL_SUMDELTA

ALL_SUMDELTA lists direct path load entries accessible to the current user.

Column	Datatype	NULL	Description
TABLEOBJ#	NUMBER	NOT NULL	Object number of the table

Column	Datatype	NULL	Description
PARTITIONOBJ#	NUMBER	NOT NULL	Object number of table partitions (if the table is partitioned)
DMLOPERATION	VARCHAR2(1)		Type of DML operation applied to the table
SCN	NUMBER	NOT NULL	SCN when the bulk DML occurred
TIMESTAMP	DATE	NOT NULL	Timestamp of the log entry
LOWROWID	ROWID	NOT NULL	Start ROWID in the loaded rowid range
HIGHROWID	ROWID	NOT NULL	End ROWID in the loaded rowid range
SEQUENCE	NUMBER		Sequence number of the direct load
XID	NUMBER		Transaction ID

4.116 ALL_SYNC_CAPTURE

ALL_SYNC_CAPTURE displays information about the synchronous capture processes that store the captured changes in queues accessible to the current user.

Related View

DBA_SYNC_CAPTURE displays information about all synchronous capture processes in the database.

Column	Datatype	NULL	Description
CAPTURE_NAME	VARCHAR2(128)	NOT NULL	Name of the capture process
QUEUE_NAME	VARCHAR2(128)	NOT NULL	Name of the queue used for holding captured changes
QUEUE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the queue used for holding captured changes
RULE_SET_NAME	VARCHAR2(128)		Rule set used by the capture process
RULE_SET_OWNER	VARCHAR2(128)		Owner of the rule set
CAPTURE_USER	VARCHAR2(128)		Current user who is enqueuing captured messages

See Also:

"DBA_SYNC_CAPTURE"

4.117 ALL_SYNC_CAPTURE_PREPARED_TABS

ALL_SYNC_CAPTURE_PREPARED_TABS displays information about the tables accessible to the current user that are prepared for synchronous capture instantiation.

Related View

DBA_SYNC_CAPTURE_PREPARED_TABS displays information about all tables in the database that are prepared for synchronous capture instantiation.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table prepared for synchronous capture instantiation
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table prepared for synchronous capture instantiation
SCN	NUMBER	NOT NULL	SCN from which changes can be captured
TIMESTAMP	DATE		Time at which the table was ready to be instantiated

See Also:

"DBA_SYNC_CAPTURE_PREPARED_TABS"

4.118 ALL_SYNC_CAPTURE_TABLES

ALL_SYNC_CAPTURE_TABLES displays information about the tables accessible to the current user that are captured by synchronous captures.

Related View

DBA_SYNC_CAPTURE_TABLES displays information about all tables in the database that are captured by synchronous captures.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)		Owner of the synchronous capture table
TABLE_NAME	VARCHAR2(128)		Name of the synchronous capture table
ENABLED	VARCHAR2(3)		Indicates whether synchronous capture is enabled for the table (YES) or not (NO)

See Also:

"DBA_SYNC_CAPTURE_TABLES"

4.119 ALL_SYNONYMS

ALL_SYNONYMS describes the synonyms accessible to the current user.

The following criteria determine the list of synonyms that ALL_SYNONYMS shows:

- All private synonyms owned by the logged-in user, even if the base object pointed to is not accessible.
- All public synonyms, even if the base object pointed to is not accessible.

- All private synonyms owned by a different user, where the ultimate base object pointed to by that synonym or by any chain of nested synonyms, is know to be accessible because of a grant to the logged-in user, or a grant to a role in effect for this session.
- If the current session has any of the following privileges, then all synonyms that point directly to local objects are shown because it is assumed that the session can access those objects:
  - LOCK ANY TABLE
  - READ ANY TABLE
  - SELECT ANY TABLE
  - INSERT ANY TABLE
  - UPDATE ANY TABLE
  - DELETE ANY TABLE

  Synonyms that point to remote objects are excluded because the system privileges just listed do not automatically convey access to those remote objects. Also, if the synonyms point to objects other than tables and views (such as sequences, PL/SQL procedures, and so on) then this rule may show synonyms that ultimately resolve to objects that this session cannot access.
- All private synonyms owned by a different user, where the synonym is via a database link, are excluded.

Related Views

- DBA_SYNONYMS describes all synonyms in the database.
- USER_SYNONYMS describes the synonyms owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the synonym
SYNONYM_NAME	VARCHAR2(128)		Name of the synonym
TABLE_OWNER	VARCHAR2(128)		Owner of the object referenced by the synonym, or creator of the referring synonym if the target is a public synonym (that is, the object referred to by TABLE_NAME). Although the column is called TABLE_OWNER, the object owned is not necessarily a table. It can be any general object such as a view, sequence, stored procedure, synonym, and so on.
TABLE_NAME	VARCHAR2(128)		Name of the object referenced by the synonym. Although the column is called TABLE_NAME, the object does not necessarily have to be a table. It can be any general object such as a view, sequence, stored procedure, synonym, and so on.
DB_LINK	VARCHAR2(128)		Name of the database link referenced, if any

Column	Datatype	NULL	Description
ORIGIN_CON_ID	VARCHAR2(256)		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)

See Also:

- "DBA_SYNONYMS"
- "USER_SYNONYMS"

4.120 ALL_TAB_COL_STAT_MODELS

ALL_TAB_COL_STAT_MODELS describes real-time statistics models for all tables accessible to the current user.

Real-time statistics models use machine learning algorithms to predict the number of distinct values (NDV) for table columns.

Related Views

- DBA_TAB_COL_STAT_MODELS describes real-time statistics models for all tables in the database.
- USER_TAB_COL_STAT_MODELS describes real-time statistics models for all tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the table column to which the model applies
STATS_TYPE	VARCHAR2(7)		Statistics type The value of this column is always NDV.
MODEL_NAME	VARCHAR2(200)	NOT NULL	Name of the model
STATUS	VARCHAR2(8)		Status of the model (ENABLED or DISABLED)
CREATED	TIMESTAMP(6) WITH TIME ZONE		Time at which the model was created
LAST_USED	TIMESTAMP(6) WITH TIME ZONE		Time at which the model was most recently used

> **See Also:**
>
> - "DBA_TAB_COL_STAT_MODELS"
> - "USER_TAB_COL_STAT_MODELS"

4.121 ALL_TAB_COL_STATISTICS

ALL_TAB_COL_STATISTICS displays column statistics and histogram information extracted from ALL_TAB_COLUMNS.

Related Views

- DBA_TAB_COL_STATISTICS displays such information extracted from "DBA_TAB_COLUMNS".
- USER_TAB_COL_STATISTICS displays such information extracted from "USER_TAB_COLUMNS". This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table
COLUMN_NAME	VARCHAR2(128)		Column name
NUM_DISTINCT	NUMBER		Number of distinct values in the column
LOW_VALUE	RAW(1000)		Low value in the column
HIGH_VALUE	RAW(1000)		High value in the column
DENSITY	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT.
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in histogram for the column
LAST_ANALYZED	DATE		Date on which this column was most recently analyzed
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this column
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics are gathered or incrementally maintained, otherwise it will be NO
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)

Column	Datatype	NULL	Description
NOTES	VARCHAR2(99)		Describes some additional properties of the statistics. For example: • A value of INCREMENTAL indicates that the global statistics are derived from synopses, that is, the global statistics are incrementally maintained. • A value of STATS_ON_CONVENTIONAL_LOAD indicates that the statistics are obtained by online statistics gathering for conventional DML.
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
HISTOGRAM	VARCHAR2(15)		Indicates existence/type of histogram: • NONE • FREQUENCY • HEIGHT BALANCED • HYBRID • TOP-FREQUENCY
SCOPE	VARCHAR2(7)		The value is SHARED for statistics gathered on any table other than global temporary tables. For a global tempoary table, the possible values are: • SESSION - Indicates that the statistics are session-specific • SHARED - Indicates that the statistics are shared across all sessions See *Oracle Database PL/SQL Packages and Types Reference* for information about using the GLOBAL_TEMP_TABLE_STATS preference of the DBMS_STATS package to control whether to gather session or shared statistics for global temporary tables.

See Also:

- "DBA_TAB_COL_STATISTICS"
- "USER_TAB_COL_STATISTICS"
- "ALL_TAB_COLUMNS"

4.122 ALL_TAB_COLS

ALL_TAB_COLS describes the columns of the tables, views, and clusters accessible to the current user.

To gather statistics for this view, use the DBMS_STATS package.

This view differs from ALL_TAB_COLUMNS in that system-generated hidden columns are not filtered out.

Related Views

- DBA_TAB_COLS describes the columns of all tables, views, and clusters in the database.
- USER_TAB_COLS describes the columns of the tables, views, and clusters owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table, view, or cluster
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table, view, or cluster
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Column name
DATA_TYPE	VARCHAR2(128)		Data type of the column
DATA_TYPE_MOD	VARCHAR2(3)		Data type modifier of the column
DATA_TYPE_OWNER	VARCHAR2(128)		Owner of the data type of the column
DATA_LENGTH	NUMBER	NOT NULL	Length of the column (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for NUMBER datatype; binary precision for FLOAT datatype; NULL for all other datatypes
DATA_SCALE	NUMBER		Digits to the right of the decimal point in a number
NULLABLE	VARCHAR2(1)		Indicates whether a column allows NULLs. The value is N if there is a NOT NULL constraint on the column or if the column is part of a PRIMARY KEY.
COLUMN_ID	NUMBER		Sequence number of the column as created
DEFAULT_LENGTH	NUMBER		Length of the default value for the column
DATA_DEFAULT	LONG		Default value for the column
DATA_DEFAULT_VC	VARCHAR2(4000)		Default value for the column This column may truncate the default value.
NUM_DISTINCT	NUMBER		Number of distinct values in the column. This column remains for backward compatibility with Oracle7. This information is now in the {TAB|PART}_COL_STATISTICS views.
LOW_VALUE	RAW(1000)		Low value in the column. This column remains for backward compatibility with Oracle7. This information is now in the {TAB|PART}_COL_STATISTICS views.
HIGH_VALUE	RAW(1000)		High value in the column. This column remains for backward compatibility with Oracle7. This information is now in the {TAB|PART}_COL_STATISTICS views.

Column	Datatype	NULL	Description
DENSITY	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT. This column remains for backward compatibility with Oracle7. This information is now in the {TAB|PART}_COL_STATISTICS views.
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in the histogram for the column **Note:** The number of buckets in a histogram is specified in the SIZE parameter of the ANALYZE SQL statement. However, Oracle Database does not create a histogram with more buckets than the number of rows in the sample. Also, if the sample contains any values that are very repetitious, Oracle Database creates the specified number of buckets, but the value indicated by this column may be smaller because of an internal compression algorithm.
LAST_ANALYZED	DATE		Date on which this column was most recently analyzed
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this column
CHARACTER_SET_NAME	VARCHAR2(44)		Name of the character set: • CHAR_CS • NCHAR_CS
CHAR_COL_DECL_LENGTH	NUMBER		Declaration length of the character type column
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics are gathered or incrementally maintained, otherwise it will be NO
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
CHAR_LENGTH	NUMBER		Displays the length of the column in characters. This value only applies to the following datatypes: • CHAR • VARCHAR2 • NCHAR • NVARCHAR2
CHAR_USED	VARCHAR2(1)		Indicates that the column uses BYTE length semantics (B) or CHAR length semantics (C), or whether the datatype is not any of the following (NULL): • CHAR • VARCHAR2 • NCHAR • NVARCHAR2

Column	Datatype	NULL	Description
V80_FMT_IMAGE	VARCHAR2(3)		Indicates whether the column data is in release 8.0 image format (YES) or not (NO)
DATA_UPGRADED	VARCHAR2(3)		Indicates whether the column data has been upgraded to the latest type version format (YES) or not (NO)
HIDDEN_COLUMN	VARCHAR2(3)		Indicates whether the column is a hidden column (YES) or not (NO)
VIRTUAL_COLUMN	VARCHAR2(3)		Indicates whether the column is a virtual column (YES) or not (NO)
SEGMENT_COLUMN_ID	NUMBER		Sequence number of the column in the segment
INTERNAL_COLUMN_ID	NUMBER	NOT NULL	Internal sequence number of the column
HISTOGRAM	VARCHAR2(15)		Indicates existence/type of histogram: • NONE • FREQUENCY • TOP-FREQUENCY • HEIGHT BALANCED • HYBRID
QUALIFIED_COL_NAME	VARCHAR2(4000)		Qualified column name
USER_GENERATED	VARCHAR2(3)		Indicates whether the column is a user-generated column (YES) or a system-generated column (NO). Invisible columns are hidden columns that are also user- generated columns.
DEFAULT_ON_NULL	VARCHAR2(3)		Indicates whether the column has DEFAULT ON NULL for INSERT semantics (YES) or not (NO)
DEFAULT_ON_NULL_UPD	VARCHAR2(3)		Indicates whether the column has DEFAULT ON NULL for UPDATE semantics (YES) or not (NO)
RESERVABLE_COLUMN	VARCHAR2(3)		Indicates whether the column is a reservable column (YES) or not (NO)
IDENTITY_COLUMN	VARCHAR2(3)		Indicates whether the column is an identity column (YES) or not (NO)
EVALUATION_EDITION	VARCHAR2(128)		Name of the edition in which editioned objects referenced in an expression column are resolved
UNUSABLE_BEFORE	VARCHAR2(128)		Name of the oldest edition in which the column is usable
UNUSABLE_BEGINNING	VARCHAR2(128)		Name of the oldest edition in which the column becomes perpetually unusable
COLLATION	VARCHAR2(100)		Collation for the column. Only applies to columns with character data types.
COLLATED_COLUMN_ID	NUMBER		Internal sequence number of a column, for which this virtual column generates a collation key.
DOMAIN_OWNER	VARCHAR2(128)		If a data use case domain is specified for the column, the owner of the data use case domain
DOMAIN_NAME	VARCHAR2(128)		If a data use case domain is specified for the column, the name of the data use case domain
DOMAIN_COLUMN_NAME	VARCHAR2(128)		If a data use case domain is specified for the column, the name of the data use case domain column

Column	Datatype	NULL	Description
DOMAIN_ASSOCIATION_ID	NUMBER		If a data use case domain is specified for the column, the domain association ID
VECTOR_INFO	VARCHAR2(56)		Indicates the number of vectors and their data type in an ONNX model Format: VECTOR(*dimension*,*element_type*) Example: VECTOR(768,float32)

> **See Also:**
>
> - "DBA_TAB_COLS"
> - "USER_TAB_COLS"
> - "ALL_TAB_COLUMNS"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

4.123 ALL_TAB_COLUMNS

ALL_TAB_COLUMNS describes the columns of the tables, views, and clusters accessible to the current user.

To gather statistics for this view, use the DBMS_STATS package.

This view filters out system-generated hidden columns. The ALL_TAB_COLS view does not filter out system-generated hidden columns.

Related Views

- DBA_TAB_COLUMNS describes the columns of all tables, views, and clusters in the database.
- USER_TAB_COLUMNS describes the columns of the tables, views, and clusters owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table, view, or cluster
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table, view, or cluster
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Column name
DATA_TYPE	VARCHAR2(128)		Data type of the column
DATA_TYPE_MOD	VARCHAR2(3)		Data type modifier of the column
DATA_TYPE_OWNER	VARCHAR2(128)		Owner of the data type of the column
DATA_LENGTH	NUMBER	NOT NULL	Length of the column (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for NUMBER data type; binary precision for FLOAT data type; NULL for all other data types

Column	Datatype	NULL	Description
DATA_SCALE	NUMBER		Digits to the right of the decimal point in a number
NULLABLE	VARCHAR2(1)		Indicates whether a column allows NULLs. The value is N if there is a NOT NULL constraint on the column or if the column is part of a PRIMARY KEY. The constraint should be in an ENABLE VALIDATE state.
COLUMN_ID	NUMBER		Sequence number of the column as created
DEFAULT_LENGTH	NUMBER		Length of the default value for the column
DATA_DEFAULT	LONG		Default value for the column
DATA_DEFAULT_VC	VARCHAR2(4000)		Default value for the column This column may truncate the default value.
NUM_DISTINCT	NUMBER		Number of distinct values in the column. This column remains for backward compatibility with Oracle7. This information is now in the {TAB|PART}_COL_STATISTICS views.
LOW_VALUE	RAW(1000)		Low value in the column. This column remains for backward compatibility with Oracle7. This information is now in the {TAB|PART}_COL_STATISTICS views.
HIGH_VALUE	RAW(1000)		High value in the column. This column remains for backward compatibility with Oracle7. This information is now in the {TAB|PART}_COL_STATISTICS views.
DENSITY	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT. This column remains for backward compatibility with Oracle7. This information is now in the {TAB|PART}_COL_STATISTICS views.
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in the histogram for the column **Note:** The number of buckets in a histogram is specified in the SIZE parameter of the ANALYZE SQL statement. However, Oracle Database does not create a histogram with more buckets than the number of rows in the sample. Also, if the sample contains any values that are very repetitious, Oracle Database creates the specified number of buckets, but the value indicated by this column may be smaller because of an internal compression algorithm.
LAST_ANALYZED	DATE		Date on which this column was most recently analyzed
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this column

Column	Datatype	NULL	Description
CHARACTER_SET_NAME	VARCHAR2(44)		Name of the character set: • CHAR_CS • NCHAR_CS
CHAR_COL_DECL_LENGTH	NUMBER		Declaration length of the character type column
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics are gathered or incrementally maintained, otherwise it will be NO
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
CHAR_LENGTH	NUMBER		Displays the length of the column in characters. This value only applies to the following datatypes: • CHAR • VARCHAR2 • NCHAR • NVARCHAR2
CHAR_USED	VARCHAR2(1)		Indicates that the column uses BYTE length semantics (B) or CHAR length semantics (C), or whether the datatype is not any of the following (NULL): • CHAR • VARCHAR2 • NCHAR • NVARCHAR2
V80_FMT_IMAGE	VARCHAR2(3)		Indicates whether the column data is in release 8.0 image format (YES) or not (NO)
DATA_UPGRADED	VARCHAR2(3)		Indicates whether the column data has been upgraded to the latest type version format (YES) or not (NO)
HISTOGRAM	VARCHAR2(15)		Indicates existence/type of histogram: • NONE • FREQUENCY • TOP-FREQUENCY • HEIGHT BALANCED • HYBRID
DEFAULT_ON_NULL	VARCHAR2(3)		Indicates whether the column has DEFAULT ON NULL for INSERT semantics (YES) or not (NO)
DEFAULT_ON_NULL_UPD	VARCHAR2(3)		Indicates whether the column has DEFAULT ON NULL for UPDATE semantics (YES) or not (NO)
RESERVABLE_COLUMN	VARCHAR2(3)		Indicates whether the column is a reservable column (YES) or not (NO)
IDENTITY_COLUMN	VARCHAR2(3)		Indicates whether the column is an identity column (YES) or not (NO)
EVALUATION_EDITION	VARCHAR2(128)		Name of the edition in which editioned objects referenced in an expression column are resolved
UNUSABLE_BEFORE	VARCHAR2(128)		Name of the oldest edition in which the column is usable

Column	Datatype	NULL	Description
UNUSABLE_BEGINNING	VARCHAR2(128)		Name of the oldest edition in which the column becomes perpetually unusable
COLLATION	VARCHAR2(100)		Collation for the column. Only applies to columns with character data types.
DOMAIN_OWNER	VARCHAR2(128)		If a data use case domain is specified for the column, the owner of the data use case domain
DOMAIN_NAME	VARCHAR2(128)		If a data use case domain is specified for the column, the name of the data use case domain
DOMAIN_COLUMN_NAME	VARCHAR2(128)		If a data use case domain is specified for the column, the name of the data use case domain column
DOMAIN_ASSOCIATION_ID	NUMBER		If a data use case domain is specified for the column, the domain association ID
VECTOR_INFO	VARCHAR2(56)		Indicates the number of vectors and their data type in an ONNX model Format: VECTOR(*dimension*,*element_type*) Example: VECTOR(768,float32)

See Also:

- "DBA_TAB_COLUMNS"
- "USER_TAB_COLUMNS"
- "ALL_TAB_COLS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

4.124 ALL_TAB_COMMENTS

ALL_TAB_COMMENTS displays comments on the tables and views accessible to the current user.

Related Views

- DBA_TAB_COMMENTS displays comments on all tables and views in the database.
- USER_TAB_COMMENTS displays comments on the tables and views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the object
TABLE_TYPE	VARCHAR2(11)		Type of the object
COMMENTS	VARCHAR2(4000)		Comment on the object

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs • *n*: This value is used for rows containing data that originate in the container with the ID *n* (*n*=1 if the data originates in root)

See Also:

- "DBA_TAB_COMMENTS"
- "USER_TAB_COMMENTS"

4.125 ALL_TAB_HISTGRM_PENDING_STATS

ALL_TAB_HISTGRM_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions accessible to the current user.

Related Views

- DBA_TAB_HISTGRM_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions in the database.
- USER_TAB_HISTGRM_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table
PARTITION_NAME	VARCHAR2(128)		Name of the partition
SUBPARTITION_NAME	VARCHAR2(128)		Name of the subpartition
COLUMN_NAME	VARCHAR2(128)		Name of the column
ENDPOINT_NUMBER	NUMBER		Endpoint number
ENDPOINT_VALUE	NUMBER		Normalized endpoint value
ENDPOINT_ACTUAL_VALUE	VARCHAR2(4000)		Actual endpoint value
ENDPOINT_ACTUAL_VALUE_RAW	RAW(1000)		Endpoint actual value in raw format
ENDPOINT_REPEAT_COUNT	NUMBER		Frequency of the endpoint (applies only to hybrid histograms, and is set to 0 for other histogram types)

> **See Also:**
>
> - "DBA_TAB_HISTGRM_PENDING_STATS"
> - "USER_TAB_HISTGRM_PENDING_STATS"

4.126 ALL_TAB_HISTOGRAMS

ALL_TAB_HISTOGRAMS describes histograms on tables and views accessible to the current user.

The ALL_TAB_HISTOGRAMS view may contain a one-bucket histogram, which in fact signifies "No histogram" to the Oracle Database software. Therefore, it should not be queried to indicate the presence or absence of a histogram on a particular column. Instead, query the value of column HISTOGRAM in the ALL_TAB_COL_STATISTICS view.

Related Views

- DBA_TAB_HISTOGRAMS describes histograms on all tables and views in the database.
- USER_TAB_HISTOGRAMS describes histograms on all tables and views owned by the current user. This view does not display the OWNER column.

> **Note:**
>
> These views are populated only if you collect statistics on the table using the DBMS_STATS package. For more information, see *Oracle Database PL/SQL Packages and Types Reference*.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table
COLUMN_NAME	VARCHAR2(4000)		Column name or attribute of the object type column
ENDPOINT_NUMBER	NUMBER		Histogram bucket number
ENDPOINT_VALUE	NUMBER		Normalized endpoint value for this bucket
ENDPOINT_ACTUAL_VALUE	VARCHAR2(4000)		Actual (not normalized) string value of the endpoint for this bucket
ENDPOINT_ACTUAL_VALUE_RAW	RAW(1000)		Endpoint actual value in raw format
ENDPOINT_REPEAT_COUNT	NUMBER		Frequency of the endpoint (applies only to hybrid histograms, and is set to 0 for other histogram types)

Column	Datatype	NULL	Description
SCOPE	VARCHAR2(7)		The value is SHARED for statistics gathered on any table other than global temporary tables. For a global tempoary table, the possible values are: • SESSION - Indicates that the statistics are session-specific • SHARED - Indicates that the statistics are shared across all sessions See *Oracle Database PL/SQL Packages and Types Reference* for information about using the GLOBAL_TEMP_TABLE_STATS preference of the DBMS_STATS package to control whether to gather session or shared statistics for global temporary tables.

See Also:

- "DBA_TAB_HISTOGRAMS"
- "USER_TAB_HISTOGRAMS"
- "ALL_TAB_COL_STATISTICS"

4.127 ALL_TAB_IDENTITY_COLS

ALL_TAB_IDENTITY_COLS describes all table identity columns.

Related Views

- DBA_TAB_IDENTITY_COLS describes all table identity columns.
- USER_TAB_IDENTITY_COLS describes all table identity columns. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the identity column
GENERATION_TYPE	VARCHAR2(10)		Generation type of the identity column. Possible values are ALWAYS or BY DEFAULT.
SEQUENCE_NAME	VARCHAR2(128)	NOT NULL	Name of the sequence associated with the identity column
IDENTITY_OPTIONS	VARCHAR2(298)		Options for the identity column sequence generator

See Also:

- "DBA_TAB_IDENTITY_COLS"
- "USER_TAB_IDENTITY_COLS"

See Also:

- The ALTER TABLE statement in *Oracle Database SQL Language Reference* for more information about creating an identity column
- The CREATE TABLE statements in *Oracle Database SQL Language Reference* for more information about creating an identity column

4.128 ALL_TAB_MODIFICATIONS

`ALL_TAB_MODIFICATIONS` describes tables accessible to the current user that have been modified since the last time statistics were gathered on the tables.

Related Views

- `DBA_TAB_MODIFICATIONS` describes such information for all tables in the database.
- `USER_TAB_MODIFICATIONS` describes such information for tables owned by the current user. This view does not display the `TABLE_OWNER` column.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)		Owner of the modified table
TABLE_NAME	VARCHAR2(128)		Name of the modified table
PARTITION_NAME	VARCHAR2(128)		Name of the modified partition
SUBPARTITION_NAME	VARCHAR2(128)		Name of the modified subpartition
INSERTS	NUMBER		Approximate number of inserts since the last time statistics were gathered
UPDATES	NUMBER		Approximate number of updates since the last time statistics were gathered
DELETES	NUMBER		Approximate number of deletes since the last time statistics were gathered
TIMESTAMP	DATE		Indicates the last time the table was modified
TRUNCATED	VARCHAR2(3)		Indicates whether the table has been truncated since the last analyze (YES) or not (NO)
DROP_SEGMENTS	NUMBER		Number of partition and subpartition segments dropped since the last analyze

> **See Also:**
>
> - "DBA_TAB_MODIFICATIONS"
> - "USER_TAB_MODIFICATIONS"

4.129 ALL_TAB_PARTITIONS

ALL_TAB_PARTITIONS displays partition-level partitioning information, partition storage parameters, and partition statistics generated by the DBMS_STATS package for the partitions accessible to the current user.

Related Views

- DBA_TAB_PARTITIONS displays such information for all partitions in the database.
- USER_TAB_PARTITIONS displays such information for the partitions of all partitioned objects owned by the current user. This view does not display the TABLE_OWNER column.

> **Note:**
>
> Columns marked with an asterisk (*) are populated only if you collect statistics on the table with the DBMS_STATS package.

> **Note:**
>
> The following is true for the columns below that include double asterisks (**) in the column description:
>
> The column can display information about segment-level attributes (for simple partitioned tables) or metadata (for composite partitioned tables). In a simple partitioned table, the partition physically contains the data (the segment) in the database. In a composite partitioned table, the partition is metadata and the data itself is stored in the subpartitions.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table
COMPOSITE	VARCHAR2(3)		Indicates whether the table is composite-partitioned (YES) or not (NO)
PARTITION_NAME	VARCHAR2(128)		Name of the partition
SUBPARTITION_COUNT	NUMBER		If this is a composite partitioned table, the number of subpartitions in the partition

Column	Datatype	NULL	Description
HIGH_VALUE	LONG		Partition bound value expression
HIGH_VALUE_LENGTH	NUMBER		Length of the partition bound value expression
PARTITION_POSITION	NUMBER		Position of the partition within the table
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace containing the partition**
PCT_FREE	NUMBER		Minimum percentage of free space in a block**
PCT_USED	NUMBER		Minimum percentage of used space in a block**
INI_TRANS	NUMBER		Initial number of transactions**
MAX_TRANS	NUMBER		Maximum number of transactions**
INITIAL_EXTENT	NUMBER		Size of the initial extent in bytes (for a range partition); size of the initial extent in blocks (for a composite partition)**
NEXT_EXTENT	NUMBER		Size of secondary extents in bytes (for a range partition); size of secondary extents in blocks (for a composite partition)**
MIN_EXTENT	NUMBER		Minimum number of extents allowed in the segment**
MAX_EXTENT	NUMBER		Maximum number of extents allowed in the segment**
MAX_SIZE	NUMBER		Maximum number of blocks allowed in the segment**
PCT_INCREASE	NUMBER		Percentage increase in extent size**
FREELISTS	NUMBER		Number of process freelists allocated in this segment**
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated in this segment**
LOGGING	VARCHAR2(7)		Indicates whether or not changes to the table are logged:** • NONE - Not specified **See Also:** the *_TAB_SUBPARTITIONS view • YES • NO
COMPRESSION	VARCHAR2(8)		Indicates the actual compression property for a partition of a simple partitioned table, or the default (if specified) for subpartitions for composite partitioned tables, otherwise NONE.** • NONE - The partition is composite, and a default setting is not specified for compression. **See Also:** the *_TAB_SUBPARTITIONS view • ENABLED - The setting for compression is enabled. • DISABLED - The setting for compression is disabled.

Column	Datatype	NULL	Description
COMPRESS_FOR	VARCHAR2(30)		Default compression for what kind of operations:** • BASIC • ADVANCED • QUERY LOW • QUERY HIGH • ARCHIVE LOW • ARCHIVE HIGH • NULL The QUERY_LOW, QUERY_HIGH, ARCHIVE_LOW, and ARCHIVE_HIGH values are associated with Hybrid Columnar Compression, a feature of the Enterprise Edition of Oracle Database that is dependent on the underlying storage system. See *Oracle Database Concepts* for more information.
NUM_ROWS*	NUMBER		Number of rows in the partition
BLOCKS*	NUMBER		Number of used data blocks in the partition
EMPTY_BLOCKS	NUMBER		Number of empty (never used) data blocks in the partition. This column is populated only if you collect statistics on the table using the DBMS_STATS package.
AVG_SPACE*	NUMBER		Average amount of free space, in bytes, in a data block allocated to the partition
CHAIN_CNT*	NUMBER		Number of rows in the partition that are chained from one data block to another, or which have migrated to a new block, requiring a link to preserve the old ROWID
AVG_ROW_LEN*	NUMBER		Average length of a row in the partition (in bytes)
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this partition
LAST_ANALYZED	DATE		Date on which this partition was most recently analyzed
BUFFER_POOL	VARCHAR2(7)		Buffer pool to be used for the partition blocks:** • DEFAULT • KEEP • RECYCLE • NULL
FLASH_CACHE	VARCHAR2(7)		Database Smart Flash Cache hint to be used for partition blocks:** • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2(7)		Cell flash cache hint to be used for partition blocks:** • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information

Column	Datatype	NULL	Description
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics have been gathered or NO if statistics have been aggregated from subpartitions or have not been gathered
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
IS_NESTED	VARCHAR2(3)		Indicates whether this is a nested table partition (YES) or not (NO) **See Also:** the *_NESTED_TABLES view for the parent table name/column
PARENT_TABLE_PARTITION	VARCHAR2(128)		Parent table's corresponding partition **See Also:** the *_NESTED_TABLES view for the parent table name/column
INTERVAL	VARCHAR2(3)		Indicates whether the partition is in the interval section of an interval partitioned table (YES) or whether the partition is in the range section (NO)
SEGMENT_CREATED	VARCHAR2(4)		Indicates the actual segment creation property for a partition of a simple partitioned table, or the default (if specified) for subpartitions for composite partitioned tables, otherwise NONE.** For a simple partitioned table, this column indicates whether a segment was created (YES) or not (NO). For composite partitioned tables, this column indicates whether or not a default segment creation property was explicitly specified. Possible values: • NONE - No default segment creation property was specified at the partition level. This value appears only for composite partitions, and is treated as an unspecified value. • YES - Immediate segment creation was explicitly specified at the partition level and will be used as the default for all of its subpartitions. • NO - Deferred segment creation was explicitly specified at the partition level and will be used as the default for all of its subpartitions.

Column	Datatype	NULL	Description
INDEXING	VARCHAR2(4)		Indicates the actual indexing property for a partition of a simple partitioned table, or the default (if specified) for subpartitions for composite partitioned tables, otherwise NONE.** Possible values: • NONE - The partition is composite, and a default setting is not specified for indexing. This value appears only for composite partitions, and is treated as an unspecified value. When a user adds a subpartition to a table, since the defaults for the partition are unspecified, the ALL_PART_TABLES.DEF_INDEXING value is used for the newly created subpartition. • ON - INDEXING is on. • OFF - INDEXING is off.
READ_ONLY	VARCHAR2(4)		Indicates the default setting for the partition: • YES: The default setting for the partition is read-only. • NO: The default setting for the partition is read/write. • NONE: No default setting is specified for the partition.
INMEMORY	VARCHAR2(8)		Indicates whether the In-Memory Column Store (IM column store) is enabled (ENABLED) or disabled (DISABLED) for this partition
INMEMORY_PRIORITY	VARCHAR2(8)		Indicates the priority for In-Memory Column Store (IM column store) population. Possible values: • LOW • MEDIUM • HIGH • CRITICAL • NONE • NULL
INMEMORY_DISTRIBUTE	VARCHAR2(15)		Indicates how the IM column store is distributed in an Oracle Real Application Clusters (Oracle RAC) environment: • AUTO • BY ROWID RANGE • BY PARTITION • BY SUBPARTITION

Column	Datatype	NULL	Description
INMEMORY_COMPRESSION	VARCHAR2(17)		Indicates the compression level for the IM column store: • NO MEMCOMPRESS • FOR DML • FOR QUERY [LOW | HIGH] • FOR CAPACITY [LOW | HIGH] • AUTO • NULL This column has a value based on where the segments lie for a table. For example, if the table is partitioned and is enabled for the IM column store, the value is NULL for ALL_TABLES but non-NULL for ALL_TAB_PARTITIONS.
INMEMORY_DUPLICATE	VARCHAR2(13)		Indicates the duplicate setting for the IM column store in an Oracle RAC environment: • NO DUPLICATE • DUPLICATE • DUPLICATE ALL
CELLMEMORY	VARCHAR2(24)		The value for columnar compression in the storage cell flash cache. Possible values: • ENABLED: Oracle Exadata Storage will decide automatically whether to cache in columnar form • DISABLED: Oracle Exadata Storage is prevented from caching in columnar form • NO CACHECOMPRESS: Oracle Exadata Storage will cache in HCC format (no recompression) • FOR QUERY: Oracle Exadata Storage will recompress and cache in INMEMORY query high format • FOR CAPACITY: Oracle Exadata Storage will recompress and cache in INMEMORY capacity low format This column is intended for use with Oracle Exadata.
INMEMORY_SERVICE	VARCHAR2(12)		Indicates how the IM column store is populated on various instances. The possible values are: • DEFAULT: Data is populated on all instances specified with the PARALLEL_INSTANCE_GROUP initialization parameter. If that parameter is not set, then the data is populated on all instances. This is the default. • NONE: Data is not populated on any instance. • ALL: Data is populated on all instances, regardless of the value of the PARALLEL_INSTANCE_GROUP initialization parameter. • USER_DEFINED: Data is populated only on the instances on which the user-specified service is active. The service name corresponding to this is stored in the INMEMORY_SERVICE_NAME column.

Column	Datatype	NULL	Description
INMEMORY_SERVICE_NAME	VARCHAR2(100)		Indicates the service name for the service on which the IM column store should be populated. This column has a value only when the corresponding INMEMORY_SERVICE is USER_DEFINED. In all other cases, this column is null.
MEMOPTIMIZE_READ	VARCHAR2(8)		Indicates whether the table is enabled for Fast Key Based Access (ENABLED) or not (DISABLED)
MEMOPTIMIZE_WRITE	VARCHAR2(8)		For internal use only
HIGH_VALUE_CLOB	CLOB		High value (boundary) information for the partition, in CLOB format
HIGH_VALUE_JSON	JSON		High value (boundary) information for the partition, in JSON format

See Also:

- "DBA_TAB_PARTITIONS"
- "USER_TAB_PARTITIONS"
- "PARALLEL_INSTANCE_GROUP"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

4.130 ALL_TAB_PENDING_STATS

ALL_TAB_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions accessible to the current user.

Related Views

- DBA_TAB_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions in the database.
- USER_TAB_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table
PARTITION_NAME	VARCHAR2(128)		Name of the partition
SUBPARTITION_NAME	VARCHAR2(128)		Name of the subpartition
NUM_ROWS	NUMBER		Number of rows
BLOCKS	NUMBER		Number of blocks

Column	Datatype	NULL	Description
AVG_ROW_LEN	NUMBER		Average row length
IM_IMCU_COUNT	NUMBER		Number of In-Memory Compression Units (IMCUs) in the table.
IM_BLOCK_COUNT	NUMBER		Number of In-Memory blocks in the table.
SCAN_RATE	NUMBER		Scan rate for the table in megabytes per second. This statistic is only relevant or meaningful for external tables.
SAMPLE_SIZE	NUMBER		Sample size
LAST_ANALYZED	DATE		Time of last analyze operation

See Also:

- "DBA_TAB_PENDING_STATS"
- "USER_TAB_PENDING_STATS"

4.131 ALL_TAB_PRIVS

ALL_TAB_PRIVS describes grants.

ALL_TAB_PRIVS describes the following types of grants:

- Object grants for which the current user is the object owner, grantor, or grantee
- Object grants for which an enabled role or PUBLIC is the grantee

Related Views

- DBA_TAB_PRIVS describes all object grants in the database.
- USER_TAB_PRIVS describes the object grants for which the current user is the object owner, grantor, or grantee.

Column	Datatype	NULL	Description
GRANTOR	VARCHAR2(128)		Name of the user who performed the grant
GRANTEE	VARCHAR2(128)		Name of the user or role to whom access was granted
TABLE_SCHEMA	VARCHAR2(128)		Schema of the object
TABLE_NAME	VARCHAR2(128)		Name of the object
PRIVILEGE	VARCHAR2(40)		Privilege on the object
GRANTABLE	VARCHAR2(3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)
HIERARCHY	VARCHAR2(3)		Indicates whether the privilege was granted with the HIERARCHY OPTION (YES) or not (NO)

Column	Datatype	NULL	Description
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
TYPE	VARCHAR2(24)		Type of the object
INHERITED	VARCHAR2(3)		Indicates whether the privilege grant was inherited from another container (YES) or not (NO)

See Also:

- "DBA_TAB_PRIVS"
- "USER_TAB_PRIVS"

4.132 ALL_TAB_PRIVS_MADE

ALL_TAB_PRIVS_MADE describes the object grants for which the current user is the object owner or grantor.

Related View

USER_TAB_PRIVS_MADE describes the object grants for which the current user is the object owner. This view does not display the OWNER column.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)		Name of the user or role to whom access was granted
OWNER	VARCHAR2(128)		Owner of the object
TABLE_NAME	VARCHAR2(128)		Name of the object
GRANTOR	VARCHAR2(128)		Name of the user who performed the grant
PRIVILEGE	VARCHAR2(40)		Privilege on the object
GRANTABLE	VARCHAR2(3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)
HIERARCHY	VARCHAR2(3)		Indicates whether the privilege was granted with the HIERARCHY OPTION (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
TYPE	VARCHAR2(24)		Type of the object

Column	Datatype	NULL	Description
INHERITED	VARCHAR2(3)		Indicates whether the privilege grant was inherited from another container (YES) or not (NO)

> **See Also:**
>
> "USER_TAB_PRIVS_MADE"

4.133 ALL_TAB_PRIVS_RECD

ALL_TAB_PRIVS_RECD describes object grants.

ALL_TAB_PRIVS_RECD describes the following types of grants:

- Object grants for which the current user is the grantee
- Object grants for which an enabled role or PUBLIC is the grantee

Related View

USER_TAB_PRIVS_RECD describes the object grants for which the current user is the grantee. This view does not display the GRANTEE column.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)		Name of the user or role to whom access was granted
OWNER	VARCHAR2(128)		Owner of the object
TABLE_NAME	VARCHAR2(128)		Name of the object
GRANTOR	VARCHAR2(128)		Name of the user who performed the grant
PRIVILEGE	VARCHAR2(40)		Privilege on the object
GRANTABLE	VARCHAR2(3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)
HIERARCHY	VARCHAR2(3)		Indicates whether the privilege was granted with the HIERARCHY OPTION (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
TYPE	VARCHAR2(24)		Type of the object
INHERITED	VARCHAR2(3)		Indicates whether the privilege grant was inherited from another container (YES) or not (NO)

> **See Also:**
>
> "USER_TAB_PRIVS_RECD"

4.134 ALL_TAB_STAT_PREFS

ALL_TAB_STAT_PREFS displays information about statistics preferences for the tables accessible to the current user.

Related Views

- DBA_TAB_STAT_PREFS displays information about statistics preferences for all tables in the database.
- USER_TAB_STAT_PREFS displays information about statistics preferences for the tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
PREFERENCE_NAME	VARCHAR2(30)		Name of the preference
PREFERENCE_VALUE	VARCHAR2(4000)		Value of the preference

> **See Also:**
>
> - "DBA_TAB_STAT_PREFS"
> - "USER_TAB_STAT_PREFS"

4.135 ALL_TAB_STATISTICS

ALL_TAB_STATISTICS displays optimizer statistics for the tables accessible to the current user.

Related Views

- DBA_TAB_STATISTICS displays optimizer statistics for all tables in the database.
- USER_TAB_STATISTICS displays optimizer statistics for the tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the object
TABLE_NAME	VARCHAR2(128)		Name of the table
PARTITION_NAME	VARCHAR2(128)		Name of the partition

Column	Datatype	NULL	Description
PARTITION_POSITION	NUMBER		Position of the partition within the table
SUBPARTITION_NAME	VARCHAR2(128)		Name of the subpartition
SUBPARTITION_POSITION	NUMBER		Position of the subpartition within the partition
OBJECT_TYPE	VARCHAR2(12)		Type of the object: • TABLE • PARTITION • SUBPARTITION
NUM_ROWS	NUMBER		Number of rows in the object
BLOCKS	NUMBER		Number of used blocks in the object
EMPTY_BLOCKS	NUMBER		Number of empty blocks in the object
AVG_SPACE	NUMBER		Average available free space in the object
CHAIN_CNT	NUMBER		Number of chained rows in the object
AVG_ROW_LEN	NUMBER		Average row length, including row overhead
AVG_SPACE_FREELIST_BLOCKS	NUMBER		Average freespace of all blocks on a freelist
NUM_FREELIST_BLOCKS	NUMBER		Number of blocks on the freelist
AVG_CACHED_BLOCKS	NUMBER		Average number of blocks in the buffer cache
AVG_CACHE_HIT_RATIO	NUMBER		Average cache hit ratio for the object
IM_IMCU_COUNT	NUMBER		Number of In-Memory Compression Units (IMCUs) in the table
IM_BLOCK_COUNT	NUMBER		Number of In-Memory blocks in the table
IM_STAT_UPDATE_TIME	TIMESTAMP(9)		The timestamp of the most recent update to the In-Memory statistics
SCAN_RATE	NUMBER		Scan rate for the object in megabytes per second. This statistic is only relevant or meaningful for external tables.
SAMPLE_SIZE	NUMBER		Sample size used in analyzing the table
LAST_ANALYZED	DATE		Date of the most recent time the table was analyzed
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics are gathered or incrementally maintained, otherwise it will be NO
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
STATTYPE_LOCKED	VARCHAR2(5)		Type of statistics lock: • DATA • CACHE • ALL
STALE_STATS	VARCHAR2(7)		Indicates whether statistics for the object are stale (YES) or not (NO)
NOTES	VARCHAR2(25)		Describes some additional properties of the statistics. For example, a value of STATS_ON_CONVENTIONAL_LOAD indicates that the statistics are obtained by online statistics gathering for conventional DML.

Column	Datatype	NULL	Description
SCOPE	VARCHAR2(7)		The value is SHARED for statistics gathered on any table other than global temporary tables. For a global temporary table, the possible values are: • SESSION - Indicates that the statistics are session-specific • SHARED - Indicates that the statistics are shared across all sessions See *Oracle Database PL/SQL Packages and Types Reference* for information about using the GLOBAL_TEMP_TABLE_STATS preference of the DBMS_STATS package to control whether to gather session or shared statistics for global temporary tables.

See Also:

- "DBA_TAB_STATISTICS"
- "USER_TAB_STATISTICS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

4.136 ALL_TAB_STATS_HISTORY

ALL_TAB_STATS_HISTORY provides a history of table statistics modifications for all tables accessible to the current user.

Related Views

- DBA_TAB_STATS_HISTORY provides a history of table statistics modifications for all tables in the database.
- USER_TAB_STATS_HISTORY provides a history of table statistics modifications for all tables owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the object
TABLE_NAME	VARCHAR2(128)		Name of the table
PARTITION_NAME	VARCHAR2(128)		Name of the partition
SUBPARTITION_NAME	VARCHAR2(128)		Name of the subpartition
STATS_UPDATE_TIME	TIMESTAMP(6) WITH TIME ZONE		Time at which the statistics were updated

See Also:

- "DBA_TAB_STATS_HISTORY"
- "USER_TAB_STATS_HISTORY"

4.137 ALL_TAB_SUBPARTITIONS

ALL_TAB_SUBPARTITIONS displays, for each table subpartition accessible to the current user, the subpartition name, name of the table and partition to which it belongs, its storage attributes, and statistics generated by the DBMS_STATS package.

Related Views

- DBA_TAB_SUBPARTITIONS displays such information for all subpartitions in the database.
- USER_TAB_SUBPARTITIONS displays such information for subpartitions of all partitioned objects owned by the current user. This view does not display the TABLE_OWNER column.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
PARTITION_NAME	VARCHAR2(128)		Name of the partition
SUBPARTITION_NAME	VARCHAR2(128)		Name of the subpartition
HIGH_VALUE	LONG		Subpartition bound value expression
HIGH_VALUE_LENGTH	NUMBER	NOT NULL	Length of the subpartition bound value expression
PARTITION_POSITION	NUMBER		Position of the partition within the table
SUBPARTITION_POSITION	NUMBER		Position of the subpartition within the partition
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of the tablespace containing the subpartition
PCT_FREE	NUMBER	NOT NULL	Minimum percentage of free space in a block
PCT_USED	NUMBER		Minimum percentage of used space in a block
INI_TRANS	NUMBER	NOT NULL	Initial number of transactions
MAX_TRANS	NUMBER	NOT NULL	Maximum number of transactions
INITIAL_EXTENT	NUMBER		Size of the initial extent in bytes (for a range partition); size of the initial extent in blocks (for a composite partition)
NEXT_EXTENT	NUMBER		Size of secondary extents in bytes (for a range partition); size of secondary extents in blocks (for a composite partition)
MIN_EXTENT	NUMBER		Minimum number of extents allowed in the segment
MAX_EXTENT	NUMBER		Maximum number of extents allowed in the segment
MAX_SIZE	NUMBER		Maximum number of blocks allowed in the segment

Column	Datatype	NULL	Description
PCT_INCREASE	NUMBER		Percentage increase in extent size
FREELISTS	NUMBER		Number of freelist groups allocated in this segment
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated in this segment
LOGGING	VARCHAR2(3)		Indicates whether or not changes to the table are logged: • YES • NO
COMPRESSION	VARCHAR2(8)		Indicates whether this subpartition is compressed (ENABLED) or not (DISABLED)
COMPRESS_FOR	VARCHAR2(30)		Default compression for what kind of operations: • BASIC • ADVANCED • QUERY LOW • QUERY HIGH • ARCHIVE LOW • ARCHIVE HIGH • NULL The QUERY_LOW, QUERY_HIGH, ARCHIVE_LOW, and ARCHIVE_HIGH values are associated with Hybrid Columnar Compression, a feature of the Enterprise Edition of Oracle Database that is dependent on the underlying storage system. See *Oracle Database Concepts* for more information.
NUM_ROWS	NUMBER		Number of rows in the subpartition
BLOCKS	NUMBER		Number of blocks in the subpartition
EMPTY_BLOCKS	NUMBER		Number of empty blocks in the subpartition
AVG_SPACE	NUMBER		Average space in the subpartition
CHAIN_CNT	NUMBER		Chain count
AVG_ROW_LEN	NUMBER		Average row length
SAMPLE_SIZE	NUMBER		Sample size
LAST_ANALYZED	DATE		Date on which this table was most recently analyzed
BUFFER_POOL	VARCHAR2(7)		Buffer pool for this subpartition: • DEFAULT • KEEP • RECYCLE • NULL
FLASH_CACHE	VARCHAR2(7)		Database Smart Flash Cache hint to be used for subpartition blocks: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.

Column	Datatype	NULL	Description
CELL_FLASH_CACHE	VARCHAR2(7)		Cell flash cache hint to be used for subpartition blocks: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics have been gathered or NO if statistics have not been gathered
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
INTERVAL	VARCHAR2(3)		Indicates whether the partition is in the interval section of an interval partitioned table (YES) or whether the partition is in the range section (NO)
SEGMENT_CREATED	VARCHAR2(3)		Indicates whether the table subpartition segment has been created (YES) or not (NO); N/A indicates that this table is not subpartitioned
INDEXING	VARCHAR2(3)		Indicates the indexing property. Possible values: • ON - Indexing is on for this subpartition • OFF - Indexing is off for this subpartition
READ_ONLY	VARCHAR2(3)		Indicates whether a subpartition is read-only or read/write: • YES: The default setting for the subpartition is read-only. • NO: The default setting for the subpartition is read/write.
INMEMORY	VARCHAR2(8)		Indicates whether the In-Memory Column Store (IM column store) is enabled (ENABLED) or disabled (DISABLED) for this subpartition
INMEMORY_PRIORITY	VARCHAR2(8)		Indicates the priority for In-Memory Column Store (IM column store) population. Possible values: • LOW • MEDIUM • HIGH • CRITICAL • NONE • NULL
INMEMORY_DISTRIBUTE	VARCHAR2(15)		Indicates how the IM column store is distributed in an Oracle Real Application Clusters (Oracle RAC) environment: • AUTO • BY ROWID RANGE • DBY PARTITION • BY SUBPARTITION

Column	Datatype	NULL	Description
INMEMORY_COMPRESSION	VARCHAR2(17)		Indicates the compression level for the IM column store: • NO MEMCOMPRESS • FOR DML • FOR QUERY [LOW | HIGH] • FOR CAPACITY [LOW | HIGH] • AUTO • NULL This column has a value based on where the segments lie for a table. For example, if the table is partitioned and is enabled for IM column store, the value is NULL for ALL_TABLES but non-NULL for ALL_TAB_SUBPARTITIONS.
INMEMORY_DUPLICATE			Indicates the duplicate setting for the IM column store in an Oracle RAC environment: • DUPLICATE • NO DUPLICATE • DUPLICATE ALL
INMEMORY_SERVICE	VARCHAR2(12)		Indicates how the IM column store is populated on various instances. The possible values are: • DEFAULT: Data is populated on all instances specified with the PARALLEL_INSTANCE_GROUP initialization parameter. If that parameter is not set, then the data is populated on all instances. This is the default. • NONE: Data is not populated on any instance. • ALL: Data is populated on all instances, regardless of the value of the PARALLEL_INSTANCE_GROUP initialization parameter. • USER_DEFINED: Data is populated only on the instances on which the user-specified service is active. The service name corresponding to this is stored in the INMEMORY_SERVICE_NAME column.
INMEMORY_SERVICE_NAME	VARCHAR2(1000)		Indicates the service name for the service on which the IM column store should be populated. This column has a value only when the corresponding INMEMORY_SERVICE is USER_DEFINED. In all other cases, this column is null.

Column	Datatype	NULL	Description
CELLMEMORY	VARCHAR2(24)		The value for columnar compression in the storage cell flash cache. Possible values: • ENABLED: Oracle Exadata Storage will decide automatically whether to cache in columnar form • DISABLED: Oracle Exadata Storage is prevented from caching in columnar form • NO CACHECOMPRESS: Oracle Exadata Storage will cache in HCC format (no recompression) • FOR QUERY: Oracle Exadata Storage will recompress and cache in INMEMORY query high format • FOR CAPACITY: Oracle Exadata Storage will recompress and cache in INMEMORY capacity low format This column is intended for use with Oracle Exadata.
MEMOPTIMIZE_READ	VARCHAR2(8)		Indicates whether the table is enabled for Fast Key Based Access (ENABLED) or not (DISABLED)
MEMOPTIMIZE_WRITE	VARCHAR2(8)		For internal use only
HIGH_VALUE_CLOB	CLOB		High value (boundary) information for the subpartition, in CLOB format
HIGH_VALUE_JSON	JSON		High value (boundary) information for the subpartition, in JSON format

See Also:

- "DBA_TAB_SUBPARTITIONS"
- "USER_TAB_SUBPARTITIONS"
- "PARALLEL_INSTANCE_GROUP"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

4.138 ALL_TABLE_ACCESS_STATS

ALL_TABLE_ACCESS_STATS displays the scan count for tables and partitions accessible to the current user.

The scan data collection begins at instance startup.

Related Views

- DBA_TABLE_ACCESS_STATS displays the scan count for all tables and partitions in the database.
- USER_TABLE_ACCESS_STATS displays the scan count for tables and partitions owned by the current user. This view does not display the TABLE_OWNER column.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
PARTITION_NAME	VARCHAR2(128)		Name of the partition For non-partitioned tables, the value of this column is null.
INSTANCE_ID	NUMBER		ID of the instance in which the table or partition was scanned
READ_COUNT	NUMBER		Aggregated scan count since instance startup
LAST_ACCESSED_TIME	TIMESTAMP(0)		Date and time of the most recent scan

Note:

The ALL_TABLE_ACCESS_STATS and DBA_TABLE_ACCESS_STATS views do not display data for Oracle-maintained schemas. You can view data for an Oracle-maintained schema by connecting to the schema and querying the USER_TABLE_ACCESS_STATS view.

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_TABLE_ACCESS_STATS"
- "USER_TABLE_ACCESS_STATS"

4.139 ALL_TABLE_VIRTUAL_COLUMNS

ALL_TABLE_VIRTUAL_COLUMNS describes virtual columns in tables accessible to the current user.

Related Views

- DBA_TABLE_VIRTUAL_COLUMNS describes virtual columns in all tables in the database.
- USER_TABLE_VIRTUAL_COLUMNS describes virtual columns in tables owned by the current user.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
VIRTUAL_COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the virtual column
VIRTUAL_COLUMN_EXPRESSION	VARCHAR2(4000)		Expression of the virtual column
COLUMN_ID	NUMBER	NOT NULL	Sequence number of the column as created
SEGMENT_COLUMN_ID	NUMBER	NOT NULL	Sequence number of the column in the segment
INTERNAL_COLUMN_ID	NUMBER	NOT NULL	Internal sequence number of the column

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_TABLE_VIRTUAL_COLUMNS"
- "USER_TABLE_VIRTUAL_COLUMNS"

4.140 ALL_TABLES

ALL_TABLES describes the relational tables accessible to the current user. To gather statistics for this view, use the DBMS_STATS package.

Related Views

- DBA_TABLES describes all relational tables in the database.
- USER_TABLES describes the relational tables owned by the current user. This view does not display the OWNER column.

Note:

Columns marked with an asterisk (*) are populated only if you collect statistics on the table with the DBMS_STATS package.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace containing the table; NULL for partitioned, temporary, and index-organized tables
CLUSTER_NAME	VARCHAR2(128)		Name of the cluster, if any, to which the table belongs
IOT_NAME	VARCHAR2(128)		Name of the index-organized table, if any, to which the overflow or mapping table entry belongs. If the IOT_TYPE column is not NULL, then this column contains the base table name.
STATUS	VARCHAR2(8)		If a previous DROP TABLE operation failed, indicates whether the table is unusable (UNUSABLE) or valid (VALID)
PCT_FREE	NUMBER		Minimum percentage of free space in a block; NULL for partitioned tables
PCT_USED	NUMBER		Minimum percentage of used space in a block; NULL for partitioned tables
INI_TRANS	NUMBER		Initial number of transactions; NULL for partitioned tables
MAX_TRANS	NUMBER		Maximum number of transactions; NULL for partitioned tables
INITIAL_EXTENT	NUMBER		Size of the initial extent (in bytes); NULL for partitioned tables
NEXT_EXTENT	NUMBER		Size of secondary extents (in bytes); NULL for partitioned tables
MIN_EXTENTS	NUMBER		Minimum number of extents allowed in the segment; NULL for partitioned tables
MAX_EXTENTS	NUMBER		Maximum number of extents allowed in the segment; NULL for partitioned tables
PCT_INCREASE	NUMBER		Percentage increase in extent size; NULL for partitioned tables
FREELISTS	NUMBER		Number of process freelists allocated to the segment; NULL for partitioned tables
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to the segment; NULL for partitioned tables
LOGGING	VARCHAR2(3)		Indicates whether or not changes to the table are logged; NULL for partitioned tables: • YES • NO
BACKED_UP	VARCHAR2(1)		Indicates whether the table has been backed up since the last modification (Y) or not (N)
NUM_ROWS*	NUMBER		Number of rows in the table
BLOCKS*	NUMBER		Number of used data blocks in the table
EMPTY_BLOCKS	NUMBER		Number of empty (never used) data blocks in the table. This column is populated only if you collect statistics on the table using the DBMS_STATS package.
AVG_SPACE*	NUMBER		Average amount of free space, in bytes, in a data block allocated to the table

Column	Datatype	NULL	Description
CHAIN_CNT*	NUMBER		Number of rows in the table that are chained from one data block to another, or which have migrated to a new block, requiring a link to preserve the old ROWID
AVG_ROW_LEN*	NUMBER		Average length of a row in the table (in bytes)
AVG_SPACE_FREELIST_BLOCKS	NUMBER		Average freespace of all blocks on a freelist
NUM_FREELIST_BLOCKS	NUMBER		Number of blocks on the freelist
DEGREE	VARCHAR2(10)		Number of threads per instance for scanning the table, or DEFAULT
INSTANCES	VARCHAR2(10)		Number of instances across which the table is to be scanned, or DEFAULT
CACHE	VARCHAR2(5)		Indicates whether the table is to be cached in the buffer cache (Y) or not (N)
TABLE_LOCK	VARCHAR2(8)		Indicates whether table locking is enabled (ENABLED) or disabled (DISABLED)
SAMPLE_SIZE	NUMBER		Sample size used in analyzing the table
LAST_ANALYZED	DATE		Date on which the table was most recently analyzed
PARTITIONED	VARCHAR2(3)		Indicates whether the table is partitioned (YES) or not (NO)
IOT_TYPE	VARCHAR2(12)		If the table is an index-organized table, then IOT_TYPE is IOT, IOT_OVERFLOW, or IOT_MAPPING. If the table is not an index-organized table, then IOT_TYPE is NULL.
TEMPORARY	VARCHAR2(1)		Indicates whether the table is temporary (Y) or not (N)
SECONDARY	VARCHAR2(1)		Indicates whether the table is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y) or not (N)
NESTED	VARCHAR2(3)		Indicates whether the table is a nested table (YES) or not (NO)
BUFFER_POOL	VARCHAR2(7)		Buffer pool for the table; NULL for partitioned tables: • DEFAULT • KEEP • RECYCLE • NULL
FLASH_CACHE	VARCHAR2(7)		Database Smart Flash Cache hint to be used for table blocks: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.

Column	Datatype	NULL	Description
CELL_FLASH_CACHE	VARCHAR2(7)		Cell flash cache hint to be used for table blocks: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
ROW_MOVEMENT	VARCHAR2(8)		Indicates whether partitioned row movement is enabled (ENABLED) or disabled (DISABLED)
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics are gathered or incrementally maintained, otherwise it will be NO
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
DURATION	VARCHAR2(15)		Indicates the duration of a temporary table: • SYS$SESSION - Rows are preserved for the duration of the session • SYS$TRANSACTION - Rows are deleted after COMMIT Null - Permanent table
SKIP_CORRUPT	VARCHAR2(8)		Indicates whether Oracle Database ignores blocks marked corrupt during table and index scans (ENABLED) or raises an error (DISABLED). To enable this feature, run the DBMS_REPAIR.SKIP_CORRUPT_BLOCKS procedure.
MONITORING	VARCHAR2(3)		This column is obsolete
CLUSTER_OWNER	VARCHAR2(128)		Owner of the cluster, if any, to which the table belongs
DEPENDENCIES	VARCHAR2(8)		Indicates whether row-level dependency tracking is enabled (ENABLED) or disabled (DISABLED)
COMPRESSION	VARCHAR2(8)		Indicates whether table compression is enabled (ENABLED) or not (DISABLED); NULL for partitioned tables

Column	Datatype	NULL	Description
COMPRESS_FOR	VARCHAR2(30)		Default compression for what kind of operations: • BASIC • ADVANCED • QUERY LOW • QUERY HIGH • ARCHIVE LOW • ARCHIVE HIGH • QUERY LOW ROW LEVEL LOCKING • QUERY HIGH ROW LEVEL LOCKING • ARCHIVE LOW ROW LEVEL LOCKING • ARCHIVE HIGH ROW LEVEL LOCKING • NO ROW LEVEL LOCKING • NULL The QUERY LOW, QUERY HIGH, ARCHIVE LOW, ARCHIVE HIGH, QUERY LOW ROW LEVEL LOCKING, QUERY HIGH ROW LEVEL LOCKING, ARCHIVE LOW ROW LEVEL LOCKING, ARCHIVE HIGH ROW LEVEL LOCKING, and NO ROW LEVEL LOCKING values are associated with Hybrid Columnar Compression, a feature of the Enterprise Edition of Oracle Database that is dependent on the underlying storage system. See *Oracle Database Concepts* for more information.
DROPPED	VARCHAR2(3)		Indicates whether the table has been dropped and is in the recycle bin (YES) or not (NO); NULL for partitioned tables This view does not return the names of tables that have been dropped.
READ_ONLY	VARCHAR2(3)		Indicates whether the table segment is READ-ONLY or not. Possible values: • YES - The table segment is READ-ONLY • NO - The table segment is not READ-ONLY • N/A - Not applicable. This value appears in a partitioned table, where there is no segment that relates to the logical table object.
SEGMENT_CREATED	VARCHAR2(3)		Indicates whether the table segment is created. Possible values: • YES - The table segment is created. • NO - The table segment is not created. • N/A - Not applicable. This value appears in a partitioned table, where there is no segment that relates to the logical table object.
RESULT_CACHE	VARCHAR2(7)		Result cache mode annotation for the table: • DEFAULT - Table has not been annotated • FORCE • MANUAL
CLUSTERING	VARCHAR2(3)		Indicates whether the table has the attribute clustering clause (YES) or not (NO)
ACTIVITY_TRACKING	VARCHAR2(23)		Indicates whether Heat Map tracking is enabled on the table

Column	Datatype	NULL	Description
DML_TIMESTAMP	VARCHAR2(25)		Modification time, creation time, or both for Automatic Data Optimization
HAS_IDENTITY	VARCHAR2(3)		Indicates whether the table has an identity column (YES) or not (NO)
CONTAINER_DATA	VARCHAR2(3)		Indicates whether the table contains container-specific data. Possible values: • YES if the table was created with the CONTAINER_DATA clause • NO otherwise
INMEMORY	VARCHAR2(8)		Indicates whether the In-Memory Column Store (IM column store) is enabled (ENABLED) or disabled (DISABLED) for the table
INMEMORY_PRIORITY	VARCHAR2(8)		Indicates the priority for In-Memory Column Store (IM column store) population. Possible values: • LOW • MEDIUM • HIGH • CRITICAL • NONE • NULL
INMEMORY_DISTRIBUTE	VARCHAR2(15)		Indicates how the IM column store is distributed in an Oracle Real Application Clusters (Oracle RAC) environment: • AUTO • BY ROWID RANGE • DUPLICATE • NONE • NULL
INMEMORY_COMPRESSION	VARCHAR2(17)		Indicates the compression level for the IM column store: • NO MEMCOMPRESS • FOR DML • FOR QUERY [LOW | HIGH] • FOR CAPACITY [LOW | HIGH] • AUTO • NULL This column has a value based on where the segments lie for a table. For example, if the table is partitioned and is enabled for the IM column store, the value is NULL for ALL_TABLES but non-NULL for ALL_TAB_PARTITIONS.
INMEMORY_DUPLICATE	VARCHAR2(13)		Indicates the duplicate setting for the IM column store in an Oracle RAC environment: • NO DUPLICATE • DUPLICATE • DUPLICATE ALL
DEFAULT_COLLATION	VARCHAR2(100)		Default collation for the table
DUPLICATED	VARCHAR2(1)		Indicates whether the table is duplicated on this shard (Y) or not (N)

Column	Datatype	NULL	Description
SYNCHRONOUS_DUPLICATED	VARCHAR2(1)		Indicates whether the table is a synchronous duplicated table (Y) or not (N)
SHARDED	VARCHAR2(1)		Indicates whether the table is sharded (Y) or not (N)
EXTERNALLY_SHARDED	VARCHAR2(1)		Indicates whether the table is externally sharded (Y) or not (N)
EXTERNALLY_DUPLICATED	VARCHAR2(1)		Indicates whether the table is externally duplicated (Y) or not (N)
EXTERNAL	VARCHAR2(3)		Indicates whether the table is an external table (YES) or not (NO)
HYBRID	VARCHAR2(3)		Indicates whether the table is a hybrid partitioned table (YES) or not (NO). A hybrid partitioned table can contain a mixture of partitions stored in segments and partitions stored externally.
CELLMEMORY	VARCHAR2(24)		The value for columnar compression in the storage cell flash cache. Possible values: • ENABLED: Oracle Exadata Storage will decide automatically whether to cache in columnar form • DISABLED: Oracle Exadata Storage is prevented from caching in columnar form • NO CACHECOMPRESS: Oracle Exadata Storage will cache in HCC format (no recompression) • FOR QUERY: Oracle Exadata Storage will recompress and cache in INMEMORY query high format • FOR CAPACITY: Oracle Exadata Storage will recompress and cache in INMEMORY capacity low format This column is intended for use with Oracle Exadata.
CONTAINERS_DEFAULT	VARCHAR2(3)		Indicates whether the table is enabled for CONTAINERS() by default (YES) or not (NO)
CONTAINER_MAP	VARCHAR2(3)		Indicates whether the table is enabled for use with the container_map database property (YES) or not (NO)
EXTENDED_DATA_LINK	VARCHAR2(3)		Indicates whether the table is enabled for fetching an extended data link from the root (YES) or not (NO)
EXTENDED_DATA_LINK_MAP	VARCHAR2(3)		For internal use only

Column	Datatype	NULL	Description
INMEMORY_SERVICE	VARCHAR2(12)		Indicates how the IM column store is populated on various instances. The possible values are: • DEFAULT: Data is populated on all instances specified with the PARALLEL_INSTANCE_GROUP initialization parameter. If that parameter is not set, then the data is populated on all instances. This is the default. • NONE: Data is not populated on any instance. • ALL: Data is populated on all instances, regardless of the value of the PARALLEL_INSTANCE_GROUP initialization parameter. • USER_DEFINED: Data is populated only on the instances on which the user-specified service is active. The service name corresponding to this is stored in the INMEMORY_SERVICE_NAME column.
INMEMORY_SERVICE_NAME	VARCHAR2(1000)		Indicates the service name for the service on which the IM column store should be populated. This column has a value only when the corresponding INMEMORY_SERVICE is USER_DEFINED. In all other cases, this column is null.
CONTAINER_MAP_OBJECT	VARCHAR2(3)		Indicates whether the table is used as the value of the container_map database property (YES) or not (NO)
MEMOPTIMIZE_READ	VARCHAR2(8)		Indicates whether the table is enabled for Fast Key Based Access (ENABLED) or not (DISABLED)
MEMOPTIMIZE_WRITE	VARCHAR2(8)		For internal use only
HAS_SENSITIVE_COLUMN	VARCHAR2(3)		Indicates whether the table has one or more sensitive columns (YES) or not (NO)
ADMIT_NULL	VARCHAR2(3)		Indicates whether the table admits null CON_ID data (YES) or not (NO)
DATA_LINK_DML_ENABLED	VARCHAR2(3)		Indicates whether DML is permitted on the Data Link table (YES) or not (NO)
LOGICAL_REPLICATION	VARCHAR2(8)		Indicates whether the table is enabled for logical replication (ENABLED) or not (DISABLED). This setting is ignored if database-wide column data supplemental logging is enabled.
STAGING	VARCHAR2(3)		Indicates whether the table is a staging table (YES) or not (NO)
HAS_RESERVABLE_COLUMN	VARCHAR2(3)		Indicates whether the table has one or more reservable columns (YES) or not (NO)

Examples

This SQL query returns the names of the tables in the EXAMPLES tablespace:

```
SELECT table_name FROM all_tables
WHERE tablespace_name = 'EXAMPLE' ORDER BY table_name;
```

This SQL query returns the name of the tablespace that contains the HR schema:

```
SELECT DISTINCT tablespace_name FROM all_tables WHERE owner='HR';
```

See Also:

- "DBA_TABLES"
- "USER_TABLES"
- "PARALLEL_INSTANCE_GROUP"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_STATS` package

4.141 ALL_TRANSFORMATIONS

`ALL_TRANSFORMATIONS` displays information about all transformations accessible to the current user.

These transformations can be specified with Advanced Queuing operations such as enqueue, dequeue, and subscribe to automatically integrate transformations in AQ messaging.

Related Views

- `DBA_TRANSFORMATIONS` displays information about all transformations in the database.
- `USER_TRANSFORMATIONS` displays information about transformations owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
TRANSFORMATION_ID	NUMBER	NOT NULL	Unique identifier for the transformation
OWNER	VARCHAR2(128)	NOT NULL	Owning user of the transformation
NAME	VARCHAR2(128)	NOT NULL	Transformation name
FROM_TYPE	VARCHAR2(128)		Source type name
TO_TYPE	VARCHAR2(256)		Target type name

See Also:

- "DBA_TRANSFORMATIONS"
- "USER_TRANSFORMATIONS"

4.142 ALL_TRIGGER_COLS

ALL_TRIGGER_COLS describes the use of columns in the triggers accessible to the current user and in triggers on tables accessible to the current user.

If the user has the CREATE ANY TRIGGER privilege, then this view describes the use of columns in all triggers in the database.

Related Views

- DBA_TRIGGER_COLS describes the use of columns in all triggers in the database.
- USER_TRIGGER_COLS describes the use of columns in the triggers owned by the current user and in triggers on tables owned by the current user.

Column	Datatype	NULL	Description
TRIGGER_OWNER	VARCHAR2(128)		Owner of the trigger
TRIGGER_NAME	VARCHAR2(128)		Name of the trigger
TABLE_OWNER	VARCHAR2(128)		Owner of the table on which the trigger is defined
TABLE_NAME	VARCHAR2(128)		Table on which the trigger is defined
COLUMN_NAME	VARCHAR2(4000)		Name of the column used in the trigger
COLUMN_LIST	VARCHAR2(3)		Indicates whether the column is specified in the UPDATE clause (YES) or not (NO)
COLUMN_USAGE	VARCHAR2(17)		How the column is used in the trigger: • NEW IN • OLD IN • NEW IN OLD IN • NEW OUT • NEW IN OUT • NEW OUT OLD IN • NEW IN OUT OLD IN • PARENT IN

See Also:

- "DBA_TRIGGER_COLS"
- "USER_TRIGGER_COLS"

4.143 ALL_TRIGGER_ORDERING

ALL_TRIGGER_ORDERING describes the triggers accessible to the current user that have FOLLOWS or PRECEDES ordering.

Related Views

- DBA_TRIGGER_ORDERING describes all triggers in the database that have FOLLOWS or PRECEDES ordering.

- USER_TRIGGER_ORDERING describes the triggers owned by the current user that have FOLLOWS or PRECEDES ordering. This view does not display the TRIGGER_OWNER column.

Column	Datatype	NULL	Description
TRIGGER_OWNER	VARCHAR2(128)	NOT NULL	Owner of the trigger
TRIGGER_NAME	VARCHAR2(128)	NOT NULL	Name of the trigger
REFERENCED_TRIGGER_OWNER	VARCHAR2(128)		Owner of the referenced trigger
REFERENCED_TRIGGER_NAME	VARCHAR2(128)		Name of the referenced trigger
ORDERING_TYPE	VARCHAR2(8)		Type of the ordering between the trigger and the referenced trigger: • FOLLOWS • PRECEDES

See Also:

- "DBA_TRIGGER_ORDERING"
- "USER_TRIGGER_ORDERING"

4.144 ALL_TRIGGERS

ALL_TRIGGERS describes the triggers on tables accessible to the current user.

If the user has the CREATE ANY TRIGGER privilege, then this view describes all triggers in the database.

Related Views

- DBA_TRIGGERS describes all triggers in the database.
- USER_TRIGGERS describes the triggers owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the trigger
TRIGGER_NAME	VARCHAR2(128)		Name of the trigger
TRIGGER_TYPE	VARCHAR2(16)		When the trigger fires: • BEFORE STATEMENT • BEFORE EACH ROW • AFTER STATEMENT • AFTER EACH ROW • INSTEAD OF • COMPOUND

Column	Datatype	NULL	Description
TRIGGERING_EVENT	VARCHAR2(246)		DML, DDL, or database event that fires the trigger **See Also:** *Oracle Database PL/SQL Language Reference* for additional information about triggers and triggering events.
TABLE_OWNER	VARCHAR2(128)		Owner of the table on which the trigger is defined
BASE_OBJECT_TYPE	VARCHAR2(18)		Base object on which the trigger is defined: • TABLE • VIEW • SCHEMA • DATABASE
TABLE_NAME	VARCHAR2(128)		If the base object type of the trigger is SCHEMA or DATABASE, then this column is NULL; if the base object type of the trigger is TABLE or VIEW, then this column indicates the table or view name on which the trigger is defined
COLUMN_NAME	VARCHAR2(4000)		Name of the nested table column (if a nested table trigger), else NULL
REFERENCING_NAMES	VARCHAR2(422)		Names used for referencing OLD and NEW column values from within the trigger
WHEN_CLAUSE	VARCHAR2(4000)		Must evaluate to TRUE for TRIGGER_BODY to execute
STATUS	VARCHAR2(8)		Indicates whether the trigger is enabled (ENABLED) or disabled (DISABLED); a disabled trigger will not fire
DESCRIPTION	VARCHAR2(4000)		Trigger description; useful for re-creating a trigger creation statement
ACTION_TYPE	VARCHAR2(11)		Action type of the trigger body: • CALL • PL/SQL
TRIGGER_BODY	LONG		Statements executed by the trigger when it fires
CROSSEDITION	VARCHAR2(7)		Type of crossedition trigger: • FORWARD • REVERSE • NO
BEFORE_STATEMENT	VARCHAR2(3)		Indicates whether the trigger has a BEFORE STATEMENT section (YES) or not (NO)
BEFORE_ROW	VARCHAR2(3)		Indicates whether the trigger has a BEFORE EACH ROW section (YES) or not (NO)
AFTER_ROW	VARCHAR2(3)		Indicates whether the trigger has an AFTER EACH ROW section (YES) or not (NO)
AFTER_STATEMENT	VARCHAR2(3)		Indicates whether the trigger has an AFTER STATEMENT section (YES) or not (NO)
INSTEAD_OF_ROW	VARCHAR2(3)		Indicates whether the trigger has an INSTEAD OF section (YES) or not (NO)
FIRE_ONCE	VARCHAR2(3)		Indicates whether the trigger will fire only for user processes making changes (YES) or whether the trigger will also fire for Replication Apply or SQL Apply processes (NO)

Column	Datatype	NULL	Description
APPLY_SERVER_ONLY	VARCHAR2(3)		Indicates whether the trigger will only fire for a Replication Apply or SQL Apply process (YES) or not (NO). If set to YES, then the setting of FIRE_ONCE does not matter. **See Also:** the DBMS_DDL.SET_TRIGGER_FIRING_PROPERTY procedure

See Also:

- "DBA_TRIGGERS"
- "USER_TRIGGERS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_DDL.SET_TRIGGER_FIRING_PROPERTY procedure

4.145 ALL_TRIGGERS_AE

ALL_TRIGGERS_AE describes the triggers on tables (across all editions) accessible to the current user.

If the user has the CREATE ANY TRIGGER privilege, then this view describes all triggers (across all editions) in the database.

Related Views

- DBA_TRIGGERS_AE describes all triggers (across all editions) in the database.
- USER_TRIGGERS_AE describes the triggers (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the trigger
TRIGGER_NAME	VARCHAR2(128)		Name of the trigger
TRIGGER_TYPE	VARCHAR2(16)		When the trigger fires: • BEFORE STATEMENT • BEFORE EACH ROW • AFTER STATEMENT • AFTER EACH ROW • INSTEAD OF • COMPOUND
TRIGGERING_EVENT	VARCHAR2(246)		DML, DDL, or database event that fires the trigger **See Also:** *Oracle Database PL/SQL Language Reference* for additional information about triggers and triggering events.
TABLE_OWNER	VARCHAR2(128)		Owner of the table on which the trigger is defined

Column	Datatype	NULL	Description
BASE_OBJECT_TYPE	VARCHAR2(18)		Base object on which the trigger is defined: • TABLE • VIEW • SCHEMA • DATABASE
TABLE_NAME	VARCHAR2(128)		If the base object type of the trigger is SCHEMA or DATABASE, then this column is NULL; if the base object type of the trigger is TABLE or VIEW, then this column indicates the table or view name on which the trigger is defined
COLUMN_NAME	VARCHAR2(4000)		Name of the nested table column (if a nested table trigger), else NULL
REFERENCING_NAMES	VARCHAR2(422)		Names used for referencing OLD and NEW column values from within the trigger
WHEN_CLAUSE	VARCHAR2(4000)		Must evaluate to TRUE for TRIGGER_BODY to execute
STATUS	VARCHAR2(8)		Indicates whether the trigger is enabled (ENABLED) or disabled (DISABLED); a disabled trigger will not fire
DESCRIPTION	VARCHAR2(4000)		Trigger description; useful for re-creating a trigger creation statement
ACTION_TYPE	VARCHAR2(11)		Action type of the trigger body: • CALL • PL/SQL
TRIGGER_BODY	LONG		Statements executed by the trigger when it fires
CROSSEDITION	VARCHAR2(7)		Type of crossedition trigger: • FORWARD • REVERSE • NO
BEFORE_STATEMENT	VARCHAR2(3)		Indicates whether the trigger has a BEFORE STATEMENT section (YES) or not (NO)
BEFORE_ROW	VARCHAR2(3)		Indicates whether the trigger has a BEFORE EACH ROW section (YES) or not (NO)
AFTER_ROW	VARCHAR2(3)		Indicates whether the trigger has an AFTER EACH ROW section (YES) or not (NO)
AFTER_STATEMENT	VARCHAR2(3)		Indicates whether the trigger has an AFTER STATEMENT section (YES) or not (NO)
INSTEAD_OF_ROW	VARCHAR2(3)		Indicates whether the trigger has an INSTEAD OF section (YES) or not (NO)
FIRE_ONCE	VARCHAR2(3)		Indicates whether the trigger will fire only for user processes making changes (YES) or whether the trigger will also fire for Replication Apply or SQL Apply processes (NO)

Column	Datatype	NULL	Description
APPLY_SERVER_ONLY	VARCHAR2(3)		Indicates whether the trigger will only fire for a Replication Apply or SQL Apply process (YES) or not (NO). If set to YES, then the setting of FIRE_ONCE does not matter. **See Also:** the DBMS_DDL.SET_TRIGGER_FIRING_PROPERTY procedure
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the trigger is defined

See Also:

- "DBA_TRIGGERS_AE"
- "USER_TRIGGERS_AE"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_DDL.SET_TRIGGER_FIRING_PROPERTY procedure

4.146 ALL_TSTZ_TAB_COLS

ALL_TSTZ_TAB_COLS displays information about the columns of the tables accessible to the current user, which have columns defined on TIMESTAMP WITH TIME ZONE data types or object types containing attributes of TIMESTAMP WITH TIME ZONE data types.

Related Views

- DBA_TSTZ_TAB_COLS displays information about the columns of all tables in the database, which have columns defined on TIMESTAMP WITH TIME ZONE data types or object types containing attributes of TIMESTAMP WITH TIME ZONE data types. This view does not display the COLUMN_NAME, NESTED, and VIRTUAL_COLUMN columns.
- USER_TSTZ_TAB_COLS displays information about the columns of the tables owned by the current user, which have columns defined on TIMESTAMP WITH TIME ZONE data types or object types containing attributes of TIMESTAMP WITH TIME ZONE data types. This view does not display the OWNER, COLUMN_NAME, NESTED, and VIRTUAL_COLUMN columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Column name
QUALIFIED_COL_NAME	VARCHAR2(4000)		Qualified column name
NESTED	NUMBER		Indicates whether the column is a nested table (1) or not (0)
VIRTUAL_COLUMN	NUMBER		Indicates whether the column is a virtual column (1) or not (0)

Column	Datatype	NULL	Description
SCALAR_COLUMN	NUMBER		Indicates whether the column is a scalar column (1) or not (0)
UNUSED_COLUMN	NUMBER		Indicates whether the column is an unused column (1) or not (0)

See Also:

- "DBA_TSTZ_TAB_COLS"
- "USER_TSTZ_TAB_COLS"

4.147 ALL_TSTZ_TABLES

ALL_TSTZ_TABLES displays information about the tables accessible to the current user, which have columns defined on TIMESTAMP WITH TIME ZONE data types or object types containing attributes of TIMESTAMP WITH TIME ZONE data types.

Related Views

- DBA_TSTZ_TABLES displays information about all tables in the database, which have columns defined on TIMESTAMP WITH TIME ZONE data types or object types containing attributes of TIMESTAMP WITH TIME ZONE data types.
- USER_TSTZ_TABLES displays information about the tables owned by the current user, which have columns defined on TIMESTAMP WITH TIME ZONE data types or object types containing attributes of TIMESTAMP WITH TIME ZONE data types. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
UPGRADE_IN_PROGRESS	VARCHAR2(3)		Indicates whether a table upgrade is in progress (YES) or not (NO)
READ_ONLY	VARCHAR2(3)		Indicates whether the table upgrade is in READ ONLY mode (YES) or not (NO)

See Also:

- "DBA_TSTZ_TABLES"
- "USER_TSTZ_TABLES"

4.148 ALL_TXEVENTQ_MIGRATION_STATUS

ALL_TXEVENTQ_MIGRATION_STATUS provides information about migrations from AQ classic queues to Transactional Event Queues (TxEventQs) accessible to the current user.

Related Views

- DBA_TXEVENTQ_MIGRATION_STATUS provides information about all migrations from AQ classic queues to Transactional Event Queues (TxEventQs). This view also displays the SUFFIX column.
- USER_TXEVENTQ_MIGRATION_STATUS provides information about migrations from AQ classic queues to Transactional Event Queues (TxEventQs) owned by the current user. This view does not display the SOURCE_SCHEMA_NAME and SUFFIX columns.

Column	Datatype	NULL	Description
SOURCE_SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Source schema name
SOURCE_QUEUE_NAME	VARCHAR2(128)	NOT NULL	Source AQ classic queue name
SOURCE_QUEUE_TABLE	VARCHAR2(128)		Source AQ classic queue table name
TARGET_SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Target schema name
TARGET_QUEUE_NAME	VARCHAR2(128)	NOT NULL	Target TxEventQ name
EVENT_STATUS	NUMBER		Migration record/event type: • 0 - This row displays data about unsupported features captured via a migration API • 1 - This row displays specific migration API details that the user executed • 2 - This row displays data about unsupported features captured as warnings
EVENT	VARCHAR2(128)		Migration event. Possible values include: • Retry Delay • Message Grouping • Listen • Next Message
EVENT_TIMESTAMP	TIMESTAMP (6) WITH TIME ZONE		Date and time at which the migration event occurred
EVENT_ERROR_COMMENTS	VARCHAR2(1024)		Migration event error comments, if any

Note:

This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_TXEVENTQ_MIGRATION_STATUS"
> - "USER_TXEVENTQ_MIGRATION_STATUS"

4.149 ALL_TYPE_ATTRS

ALL_TYPE_ATTRS describes the attributes of the object types accessible to the current user.

Related Views

- DBA_TYPE_ATTRS describes the attributes of all object types in the database. This view does not include the CHAR_USED column.
- USER_TYPE_ATTRS describes the attributes of the object types owned by the current user. This view does not display the OWNER or CHAR_USED column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the type
TYPE_NAME	VARCHAR2(128)		Name of the type
ATTR_NAME	VARCHAR2(128)		Name of the attribute
ATTR_TYPE_MOD	VARCHAR2(7)		Type modifier of the attribute: • REF • POINTER
ATTR_TYPE_OWNER	VARCHAR2(128)		Owner of the type of the attribute
ATTR_TYPE_NAME	VARCHAR2(128)		Name of the type of the attribute
LENGTH	NUMBER		Length of the CHAR attribute, or maximum length of the VARCHAR or VARCHAR2 attribute.
PRECISION	NUMBER		Decimal precision of the NUMBER or DECIMAL attribute, or binary precision of the FLOAT attribute.
SCALE	NUMBER		Scale of the NUMBER or DECIMAL attribute
CHARACTER_SET _NAME	VARCHAR2(44)		Character set name of the attribute (CHAR_CS or NCHAR_CS)
ATTR_NO	NUMBER		Syntactical order number or position of the attribute as specified in the type specification or CREATE TYPE statement (not to be used as an ID number)
INHERITED	VARCHAR2(3)		Indicates whether the attribute is inherited from a supertype (YES) or not (NO)
CHAR_USED	VARCHAR2(1)		Indicates whether the attribute uses BYTE length semantics (B) or CHAR length semantics (C). For NCHAR and NVARCHAR2 attribute types, this value is always C.

> **See Also:**
>
> - "DBA_TYPE_ATTRS"
> - "USER_TYPE_ATTRS"

4.150 ALL_TYPE_METHODS

ALL_TYPE_METHODS describes the methods of the object types accessible to the current user.

Related Views

- DBA_TYPE_METHODS describes the methods of all object types in the database.
- USER_TYPE_METHODS describes the methods of the object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the type
TYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the type
METHOD_NAME	VARCHAR2(128)	NOT NULL	Name of the method
METHOD_NO	NUMBER	NOT NULL	Method number for distinguishing overloaded methods (not to be used as ID number)
METHOD_TYPE	VARCHAR2(6)		Type of the method: • MAP • ORDER • PUBLIC
PARAMETERS	NUMBER	NOT NULL	Number of parameters to the method
RESULTS	NUMBER	NOT NULL	Number of results returned by the method
FINAL	VARCHAR2(3)		Indicates whether the method is final (YES) or not (NO)
INSTANTIABLE	VARCHAR2(3)		Indicates whether the method is instantiable (YES) or not (NO)
OVERRIDING	VARCHAR2(3)		Indicates whether the method is overriding a supertype method (YES) or not (NO)
INHERITED	VARCHAR2(3)		Indicates whether the method is inherited from a supertype (YES) or not (NO)

> **See Also:**
>
> - "DBA_TYPE_METHODS"
> - "USER_TYPE_METHODS"

4.151 ALL_TYPE_VERSIONS

ALL_TYPE_VERSIONS describes the versions of the object types accessible to the current user.

Related Views

- DBA_TYPE_VERSIONS describes the versions of all object types in the database.
- USER_TYPE_VERSIONS describes the versions of the object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the type
TYPE_NAME	VARCHAR2(128)	NOT NULL	Name of the type
VERSION#	NUMBER	NOT NULL	Internal version number of the type
TYPECODE	VARCHAR2(128)		Typecode of the type
STATUS	VARCHAR2(7)		Status of the type: • N/A • VALID • INVALID
LINE	NUMBER	NOT NULL	Line number of the type's spec
TEXT	VARCHAR2(4000)		Text of the type's spec
HASHCODE	RAW(17)		Hashcode of the type

See Also:

- "DBA_TYPE_VERSIONS"
- "USER_TYPE_VERSIONS"

4.152 ALL_TYPES

ALL_TYPES describes the object types accessible to the current user.

Related Views

- DBA_TYPES describes all object types in the database.
- USER_TYPES describes the object types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the type
TYPE_NAME	VARCHAR2(128)		Name of the type
TYPE_OID	RAW(16)		Object identifier (OID) of the type

Column	Datatype	NULL	Description
TYPECODE	VARCHAR2(128)		Typecode of the type
ATTRIBUTES	NUMBER		Number of attributes (if any) in the type
METHODS	NUMBER		Number of methods (if any) in the type
PREDEFINED	VARCHAR2(3)		Indicates whether the type is a predefined type (YES) or not (NO)
INCOMPLETE	VARCHAR2(3)		Indicates whether the type is an incomplete type (YES) or not (NO)
FINAL	VARCHAR2(3)		Indicates whether the type is a final type (YES) or not (NO)
INSTANTIABLE	VARCHAR2(3)		Indicates whether the type is an instantiable type (YES) or not (NO)
PERSISTABLE	VARCHAR2(3)		Indicates whether the type is a persistable type (YES) or not (NO)
SUPERTYPE_OWNER	VARCHAR2(128)		Owner of the supertype (NULL if type is not a subtype)
SUPERTYPE_NAME	VARCHAR2(128)		Name of the supertype (NULL if type is not a subtype)
LOCAL_ATTRIBUTES	NUMBER		Number of local (not inherited) attributes (if any) in the subtype
LOCAL_METHODS	NUMBER		Number of local (not inherited) methods (if any) in the subtype
TYPEID	RAW(16)		Type ID value of the type

See Also:

- "DBA_TYPES"
- "USER_TYPES"

4.153 ALL_UNIFIED_AUDIT_ACTIONS

ALL_UNIFIED_AUDIT_ACTIONS describes unified audit trail actions.

The actions described in this view are valid for audit trail records from the UNIFIED_AUDIT_TRAIL view. Such records are generated only when unified auditing is enabled.

See Also:

- *Oracle Database Security Guide* for more information about unified auditing.
- *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

Column	Datatype	NULL	Description
TYPE	NUMBER	NOT NULL	Numeric component type for system wide actions
COMPONENT	VARCHAR2(64)	NOT NULL	Name of component for system wide actions
ACTION	NUMBER	NOT NULL	Numeric auditable action code for system wide actions **Note:** The action code values have changed from Oracle Database release 12.2 to the current release. If your applications have queries that include the ACTION column, and if these queries were written in release 12.2, then be aware that the output may be different if you are running these queries in the current release.
NAME	VARCHAR2(64)	NOT NULL	Name of auditable action

See Also:

"UNIFIED_AUDIT_TRAIL"

4.154 ALL_UNUSED_COL_TABS

ALL_UNUSED_COL_TABS describes the tables accessible to the current user that contain unused columns.

Related Views

- DBA_UNUSED_COL_TABS describes all tables in the database that contain unused columns.
- USER_UNUSED_COL_TABS describes the tables owned by the current user that contain unused columns. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
COUNT	NUMBER		Number of unused columns

See Also:

- "DBA_UNUSED_COL_TABS"
- "USER_UNUSED_COL_TABS"

4.155 ALL_UPDATABLE_COLUMNS

ALL_UPDATABLE_COLUMNS describes all columns in a join view that are updatable by the current user, subject to appropriate privileges.

Related Views

- DBA_UPDATABLE_COLUMNS describes all columns in a join view that are updatable by the database administrator, subject to appropriate privileges.
- USER_UPDATABLE_COLUMNS describes all columns owned by the current user that are in a join view and are updatable by the current user, subject to appropriate privileges.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Column name
UPDATABLE	VARCHAR2(3)		Indicates whether the column is updatable (YES) or not (NO)
INSERTABLE	VARCHAR2(3)		Indicates whether the column is insertable (YES) or not (NO)
DELETABLE	VARCHAR2(3)		Indicates whether the column is deletable (YES) or not (NO)

See Also:

- "DBA_UPDATABLE_COLUMNS"
- "USER_UPDATABLE_COLUMNS"
- *Oracle Database Concepts* for information on updatable join views

4.156 ALL_USERS

ALL_USERS lists all users of the database visible to the current user.

This view does not describe the users (see the related views).

Related Views

- DBA_USERS describes all users of the database, and contains more columns than ALL_USERS.
- USER_USERS describes the current user, and contains more columns than ALL_USERS.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user
USER_ID	NUMBER	NOT NULL	ID number of the user

Column	Datatype	NULL	Description
CREATED	DATE	NOT NULL	User creation date
COMMON	VARCHAR2(3)		Indicates whether a given user is common. Possible values: • YES if a user is common • NO if a user is local (not common)
ORACLE_MAINTAINED	VARCHAR2(1)		Denotes whether the user was created, and is maintained, by Oracle-supplied scripts (such as catalog.sql or catproc.sql). A user for which this column has the value Y must not be changed in any way except by running an Oracle-supplied script.
INHERITED	VARCHAR2(3)		Indicates whether the user definition was inherited from another container (YES) or not (NO)
DEFAULT_COLLATION	VARCHAR2(100)		Default collation for the user's schema
IMPLICIT	VARCHAR2(3)		Indicates whether this user is a common user created by an implicit application (YES) or not (NO)
ALL_SHARD	VARCHAR2(3)		In a sharded database, the value in this column indicates whether the user was created with shard DDL enabled. The possible values are: • YES: The user was created with shard DDL enabled. The user exists on all shards and the shard catalog. • NO: The user was created without shard DDL enabled. The user exists only in the database in which the user was created. In a non-sharded database, the value in this column is always NO.
EXTERNAL_SHARD	VARCHAR2(3)		In a federated sharded database, the value in this column indicates whether the user is an external shard user (YES) or not (NO). In other types of databases, the value in this column is always NO.
DICTIONARY_PROTECTED[1]	VARCHAR2(3)		Indicates whether the user's schema is dictionary protected (YES) or not (NO) **See Also:** *Oracle Database Security Guide* for more information about dictionary-protected schemas

1

See Also:

- "DBA_USERS"
- "USER_USERS"
- *Oracle Globally Distributed Database Guide* for more information about sharded database management

4.157 ALL_USTATS

ALL_USTATS describes the user-defined statistics collected on the tables and indexes accessible to the current user.

Related Views

- DBA_USTATS describes the user-defined statistics collected on all tables and indexes in the database.
- USER_USTATS describes the user-defined statistics collected on the tables and indexes owned by the current user.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)		Owner of the table or index for which the statistics have been collected
OBJECT_NAME	VARCHAR2(128)		Name of the table or index for which the statistics have been collected
PARTITION_NAME	VARCHAR2(128)		Partition name of a table; NULL if the table is either nonpartitioned or the entry corresponds to the aggregate statistics for the table
OBJECT_TYPE	VARCHAR2(6)		Type of the object for which statistics have been collected: • INDEX • COLUMN
ASSOCIATION	VARCHAR2(8)		Statistics type association: • DIRECT Direct association with the object for which the statistics have been collected • IMPLICIT - Association for which the statistics have been collected is with the column type or index type, and the object is an instance of that column type or index type
COLUMN_NAME	VARCHAR2(128)		Column name, if OBJECT_TYPE is COLUMN, for which statistics have been collected
STATSTYPE_SCHEMA	VARCHAR2(128)		Schema of the statistics type which was used to collect the statistics
STATSTYPE_NAME	VARCHAR2(128)		Name of the statistics type which was used to collect statistics
STATISTICS	RAW(2000)		User-collected statistics for the object

See Also:

- "DBA_USTATS"
- "USER_USTATS"

4.158 ALL_VARRAYS

ALL_VARRAYS describes the varrays accessible to the current user.

Related Views

- DBA_VARRAYS describes all varrays in the database.
- USER_VARRAYS describes the varrays owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table containing the varray
PARENT_TABLE_NAME	VARCHAR2(128)		Name of the containing table
PARENT_TABLE_COLUMN	VARCHAR2(4000)		Name of the varray column or attribute
TYPE_OWNER	VARCHAR2(128)		Owner of the varray type
TYPE_NAME	VARCHAR2(128)		Name of the varray type
LOB_NAME	VARCHAR2(128)		Name of the LOB if the varray is stored in a LOB
STORAGE_SPEC	VARCHAR2(30)		Indicates whether the storage was defaulted (DEFAULT) or user-specified (USER_SPECIFIED)
RETURN_TYPE	VARCHAR2(20)		Return type of the column: • LOCATOR • VALUE
ELEMENT_SUBSTITUTABLE	VARCHAR2(25)		Indicates whether the varray element is substitutable (Y) or not (N)

See Also:

- "DBA_VARRAYS"
- "USER_VARRAYS"

4.159 ALL_VIEWS

ALL_VIEWS describes the views accessible to the current user.

Related Views

- DBA_VIEWS describes all views in the database.
- USER_VIEWS describes the views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the view
VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the view

Column	Datatype	NULL	Description
TEXT_LENGTH	NUMBER		Length of the view text
TEXT	LONG		View text. This column returns the correct value only when the row originates from the current container. The BEQUEATH clause will not appear as part of the TEXT column in this view.
TEXT_VC	VARCHAR2(4000)		View text. This column may truncate the view text. The BEQUEATH clause will not appear as part of the TEXT_VC column in this view.
TYPE_TEXT_LENGTH	NUMBER		Length of the type clause of the typed view
TYPE_TEXT	VARCHAR2(4000)		Type clause of the typed view
OID_TEXT_LENGTH	NUMBER		Length of the WITH OID clause of the typed view
OID_TEXT	VARCHAR2(4000)		WITH OID clause of the typed view
VIEW_TYPE_OWNER	VARCHAR2(128)		Owner of the type of the view if the view is a typed view
VIEW_TYPE	VARCHAR2(128)		Type of the view if the view is a typed view
SUPERVIEW_NAME	VARCHAR2(128)		Name of the superview
EDITIONING_VIEW	VARCHAR2(1)		Reserved for future use
READ_ONLY	VARCHAR2(1)		Indicates whether the view is read-only (Y) or not (N)
CONTAINER_DATA	VARCHAR2(1)		Indicates whether the view contains container-specific data. Possible values: • Y if the view was created with the CONTAINER_DATA clause • N otherwise
BEQUEATH	VARCHAR2(12)		Possible values: • CURRENT_USER: When the view is a BEQUEATH CURRENT_USER view • DEFINER: When the view is a BEQUEATH DEFINER view For more information about the syntax and semantics of the BEQUEATH clause in the SQL CREATE VIEW statement, see *Oracle Database SQL Language Reference*.
ORIGIN_CON_ID	VARCHAR2(256)		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)
DEFAULT_COLLATION	VARCHAR2(100)		Default collation for the view
CONTAINERS_DEFAULT	VARCHAR2(3)		Indicates whether the view is enabled for CONTAINERS() by default (YES) or not (NO)
CONTAINER_MAP	VARCHAR2(3)		Indicates whether the view is enabled for use with the container_map database property (YES) or not (NO)

Column	Datatype	NULL	Description
EXTENDED_DATA_LINK	VARCHAR2(3)		Indicates whether the view is enabled for fetching an extended data link from the root (YES) or not (NO)
EXTENDED_DATA_LINK_MAP	VARCHAR2(3)		For internal use only
HAS_SENSITIVE_COLUMN	VARCHAR2(3)		Indicates whether the view has one or more sensitive columns (YES) or not (NO)
ADMIT_NULL	VARCHAR2(3)		Indicates whether the view admits null CON_ID data (YES) or not (NO)
PDB_LOCAL_ONLY	VARCHAR2(3)		For internal use only
DUALITY_VIEW	VARCHAR2(3)		Indicates whether the view is a JSON-relational duality view (YES) or not (NO)

See Also:

- "DBA_VIEWS"
- "USER_VIEWS"

4.160 ALL_VIEWS_AE

ALL_VIEWS_AE describes the views (across all editions) accessible to the current user.

Related Views

- DBA_VIEWS_AE describes all views (across all editions) in the database.
- USER_VIEWS_AE describes the views (across all editions) owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the view
VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the view
TEXT_LENGTH	NUMBER		Length of the view text
TEXT	LONG		View text. The BEQUEATH clause will not appear as part of the TEXT column in this view.
TEXT_VC	VARCHAR2(4000)		View text. This column may truncate the view text. The BEQUEATH clause will not appear as part of the TEXT_VC column in this view.
TYPE_TEXT_LENGTH	NUMBER		Length of the type clause of the typed view
TYPE_TEXT	VARCHAR2(4000)		Type clause of the typed view
OID_TEXT_LENGTH	NUMBER		Length of the WITH OID clause of the typed view
OID_TEXT	VARCHAR2(4000)		WITH OID clause of the typed view
VIEW_TYPE_OWNER	VARCHAR2(128)		Owner of the type of the view if the view is an typed view

Column	Datatype	NULL	Description
VIEW_TYPE	VARCHAR2(128)		Type of the view if the view is a typed view
SUPERVIEW_NAME	VARCHAR2(128)		Name of the superview, if the view is a subview
EDITIONING_VIEW	VARCHAR2(1)		Indicates whether the view is an editioning view (Y) or not (N)
READ_ONLY	VARCHAR2(1)		Indicates whether the view is read-only (Y) or not (N)
EDITION_NAME	VARCHAR2(128)		Name of the application edition where the object is defined
CONTAINER_DATA	VARCHAR2(1)		Indicates whether the view contains container-specific data. Possible values: • Y if the view was created with the CONTAINER_DATA clause • N otherwise
BEQUEATH	VARCHAR2(12)		Possible values: • CURRENT_USER: When the view is a BEQUEATH CURRENT_USER view • DEFINER: When the view is a BEQUEATH DEFINER view For more information about the syntax and semantics of the BEQUEATH clause in the SQL CREATE VIEW statement, see *Oracle Database SQL Language Reference*.
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)
DEFAULT_COLLATION	VARCHAR2(100)		Default collation for the view
CONTAINERS_DEFAULT	VARCHAR2(3)		Indicates whether the view is enabled for CONTAINERS() by default (YES) or not (NO)
CONTAINER_MAP	VARCHAR2(3)		Indicates whether the view is enabled for use with the container_map database property (YES) or not (NO)
EXTENDED_DATA_LINK	VARCHAR2(3)		Indicates whether the view is enabled for fetching an extended data link from the root (YES) or not (NO)
EXTENDED_DATA_LINK_MAP	VARCHAR2(3)		For internal use only
HAS_SENSITIVE_COLUMN	VARCHAR2(3)		Indicates whether the view has one or more sensitive columns (YES) or not (NO)
ADMIT_NULL	VARCHAR2(3)		Indicates whether the view admits null CON_ID data (YES) or not (NO)
PDB_LOCAL_ONLY	VARCHAR2(3)		For internal use only
DUALITY_VIEW	VARCHAR2(3)		Indicates whether the view is a JSON-relational duality view (YES) or not (NO)

> **See Also:**
>
> - "DBA_VIEWS_AE"
> - "USER_VIEWS_AE"

4.161 ALL_WARNING_SETTINGS

ALL_WARNING_SETTINGS displays information about the warning parameter settings for the objects accessible to the current user.

Related Views

- DBA_WARNING_SETTINGS displays information about the warning parameter settings for all objects in the database.
- USER_WARNING_SETTINGS displays information about the warning parameter settings for the objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object
OBJECT_ID	NUMBER	NOT NULL	Object number of the object
OBJECT_TYPE	VARCHAR2(12)		Type of the object: • PROCEDURE • FUNCTION • PACKAGE • PACKAGE BODY • TRIGGER • TYPE • TYPE BODY
WARNING	VARCHAR2(40)		Warning number or category: • INFORMATIONAL • PERFORMANCE • SEVERE • ALL
SETTING	VARCHAR2(7)		Value of the warning setting: • DISABLE • ENABLE • ERROR

> **See Also:**
>
> - "DBA_WARNING_SETTINGS"
> - "USER_WARNING_SETTINGS"

4.162 ALL_XML_INDEXES

ALL_XML_INDEXES describes the XML indexes accessible to the current user.

Related Views

- DBA_XML_INDEXES describes all XML indexes in the database.
- USER_XML_INDEXES describes the XML indexes owned by the current user. This view does not display the INDEX_OWNER column.

Column	Datatype	NULL	Description
INDEX_OWNER	VARCHAR2(128)	NOT NULL	Owner of the XML index
INDEX_NAME	VARCHAR2(128)	NOT NULL	Name of the XML index
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the indexed object
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the indexed object
TYPE	VARCHAR2(10)		Type of the indexed column: • REPOSITORY • BINARY • CLOB in OR • CLOB
INDEX_TYPE	VARCHAR2(27)		Type of the index: • STRUCTURED • STRUCTURED and UNSTRUCTURED • UNSTRUCTURED
PATH_TABLE_NAME	VARCHAR2(128)		Name of the path table
PARAMETERS	XMLTYPE		Indexed paths and Scheduler job information
ASYNC	VARCHAR2(9)		Asynchronous index type: • ON-COMMIT • MANUAL • EVERY • ALWAYS
STALE	VARCHAR2(5)		Indicates whether the index type is stale (TRUE) or not (FALSE)
PEND_TABLE_NAME	VARCHAR2(128)		Name of the pending table
EX_OR_INCLUDE	VARCHAR2(8)		Path subsetting: • INCLUDE • EXCLUDE • FULLY IX

See Also:

- "DBA_XML_INDEXES"
- "USER_XML_INDEXES"

4.163 ALL_XML_NESTED_TABLES

ALL_XML_NESTED_TABLES describes all the tables and their corresponding nested tables accessible to the current user.

Related Views

- DBA_XML_NESTED_TABLES describes all the tables and their corresponding nested tables in the database.
- USER_XML_NESTED_TABLES describes all the tables and their corresponding nested tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table
NESTED_TABLE_NAME	VARCHAR2(128)		Name of the nested table
PARENT_COLUMN_NAME	VARCHAR2(4000)		Name of the parent XML column

See Also:

- "DBA_XML_NESTED_TABLES"
- "USER_XML_NESTED_TABLES"

4.164 ALL_XML_OUT_OF_LINE_TABLES

ALL_XML_OUT_OF_LINE_TABLES descibes all the out of line tables connected to a given root table for the same schema accessible to the current user.

Related Views

- DBA_XML_OUT_OF_LINE_TABLES describes all the out of line tables connected to a given root table for the same schema in the database.
- USER_XML_OUT_OF_LINE_TABLES describes all the out of line tables connected to a given root table for the same schema owned by the current user. This view does not display the TABLE_OWNER column.

Column	Datatype	NULL	Description
SCHEMA_URL	VARCHAR2(700)		The URL of the schema within which the out of line table is defined Refer to the **See Also** note below for links to more information about the schemaurl attribute for an XML schema.
SCHEMA_OWNER	VARCHAR2(128)		Owner of the schema
TABLE_NAME	VARCHAR2(128)		Name of the out of line table

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)		Owner of the out of line table

See Also:

- "DBA_XML_OUT_OF_LINE_TABLES"
- "USER_XML_OUT_OF_LINE_TABLES"
- *Oracle XML DB Developer's Guide* for information about registering an XML schema with Oracle XML DB
- *Oracle XML DB Developer's Guide* for information about restrictions for an XML schema URL

4.165 ALL_XML_SCHEMA_ATTRIBUTES

ALL_XML_SCHEMA_ATTRIBUTES describes all the attributes and their properties accessible to the current user.

Related Views

- DBA_XML_SCHEMA_ATTRIBUTES describes all the attributes and their properties accessible to the current user in the database.
- USER_XML_SCHEMA_ATTRIBUTES describes all the attributes and their properties owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		The user who owns the attribute
SCHEMA_URL	VARCHAR2(700)		The URL of the schema within which the attribute is defined Refer to the **See Also** note below for links to more information about the schemaurl attribute for an XML schema.
TARGET_NAMESPACE	VARCHAR2(2000)		The namespace of the attribute
ATTRIBUTE_NAME	VARCHAR2(2000)		Name of the attribute
IS_REF	NUMBER		Indicates whether an attribute was defined using a reference in the XML schema (1) or not (0)
TYPE_NAME	VARCHAR2(2000)		Name of the type of the attribute
GLOBAL	RAW(1)		Indicates whether the attribute is global (1) or not (0)
ATTRIBUTE	XMLTYPE		Actual XMLType for the attribute
ELEMENT_ID	RAW(20)		Element ID of the element to which the attribute belongs
SQL_TYPE	VARCHAR2(128)		XDB annotation for sqlType
SQL_NAME	VARCHAR2(128)		XDB annotation value for sqlName

See Also:

- "DBA_XML_SCHEMA_ATTRIBUTES"
- "USER_XML_SCHEMA_ATTRIBUTES"
- *Oracle XML DB Developer's Guide* for information about registering an XML schema with Oracle XML DB
- *Oracle XML DB Developer's Guide* for information about restrictions for an XML schema URL

4.166 ALL_XML_SCHEMA_COMPLEX_TYPES

`ALL_XML_SCHEMA_COMPLEX_TYPES` describes all complex types accessible to the current user.

Related Views

- `DBA_XML_SCHEMA_COMPLEX_TYPES` describes all complex types in the database.
- `USER_XML_SCHEMA_COMPLEX_TYPES` describes all complex types owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		The user who owns the type
SCHEMA_URL	VARCHAR2(700)		The URL of the schema within which the type is defined Refer to the **See Also** note below for links to more information about the `schemaurl` attribute for an XML schema.
TARGET_NAMESPACE	VARCHAR2(2000)		The namespace of the type
COMPLEX_TYPE_NAME	VARCHAR2(256)		Name of the complex type
COMPLEX_TYPE	XMLTYPE(XMLSchema "http://xmlns.oracle.com/xdb/XDBSchema.xsd" Element "complexType")		The actual XMLType of the type
BASE_NAME	VARCHAR2(256)		Name of the base type to which the complex type refers
BASE_SCHEMA_URL	VARCHAR2(700)		The URL of the schema within which the complex type is defined
BASE_TARGET_NAMESPACE	VARCHAR2(2000)		The namespace of the type
MAINTAIN_DOM	RAW(1)		XDB annotation for maintainDOM
SQL_TYPE	VARCHAR2(128)		XDB annotation for sqlType
SQL_SCHEMA	VARCHAR2(128)		XDB annotation for sqlSchema

See Also:

- "DBA_XML_SCHEMA_COMPLEX_TYPES"
- "USER_XML_SCHEMA_COMPLEX_TYPES"
- *Oracle XML DB Developer's Guide* for information about registering an XML schema with Oracle XML DB
- *Oracle XML DB Developer's Guide* for information about restrictions for an XML schema URL

4.167 ALL_XML_SCHEMA_ELEMENTS

`ALL_XML_SCHEMA_ELEMENTS` describes all the elements and their properties accessible to the current user.

Related Views

- `DBA_XML_SCHEMA_ELEMENTS` describes all the elements and their properties.
- `USER_XML_SCHEMA_ELEMENTS` describes all the elements and their properties owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		The user who owns the element
SCHEMA_URL	VARCHAR2(700)		The URL of the schema within which the element is defined Refer to the **See Also** note below for links to more information about the `schemaurl` attribute for an XML schema.
TARGET_NAMESPACE	VARCHAR2(2000)		The namespace of the element
ELEMENT_NAME	VARCHAR2(2000)		Name of the element
IS_REF	NUMBER		Indicates whether an attribute was defined using a reference in the XML schema (`1`) or not (`0`)
TYPE_NAME	VARCHAR2(2000)		Name of the type of the element
GLOBAL	RAW(1)		Indicates whether the attribute is global (`1`) or not (`0`)
ELEMENT	XMLTYPE		The actual XML fragment of the element
SQL_INLINE	RAW(1)		XDB annotation for sqlInline
SQL_TYPE	VARCHAR2(128)		XDB annotation value for sqlType
SQL_SCHEMA	VARCHAR2(128)		XDB annotation value for sqlSchema
DEFAULT_TABLE	VARCHAR2(128)		XDB annotation value for default table
SQL_NAME	VARCHAR2(128)		XDB annotation value for sqlName
SQL_COL_TYPE	VARCHAR2(128)		XDB annotation value for sqlColType
MAINTAIN_DOM	RAW(1)		XDB annotation for maintainDOM
MAINTAIN_ORDER	RAW(1)		XDB annotation for maintainOrder

Column	Datatype	NULL	Description
ELEMENT_ID	RAW(20)		Unique identifier for the element
PARENT_ELEMENT_ID	RAW(20)		Identies the parent of the element

See Also:

- "DBA_XML_SCHEMA_ELEMENTS"
- "USER_XML_SCHEMA_ELEMENTS"
- *Oracle XML DB Developer's Guide* for information about registering an XML schema with Oracle XML DB
- *Oracle XML DB Developer's Guide* for information about restrictions for an XML schema URL

4.168 ALL_XML_SCHEMA_NAMESPACES

ALL_XML_SCHEMA_NAMESPACES describes all the available namespaces accessible to the current user.

Related Views

- DBA_XML_SCHEMA_NAMESPACES describes all the available namespaces.
- USER_XML_SCHEMA_NAMESPACES describes all the available namespaces owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		User who owns the namespace
TARGET_NAMESPACE	VARCHAR2(2000)		The target namespace
SCHEMA_URL	VARCHAR2(700)		The URL of the schema Refer to the **See Also** note below for links to more information about the schemaurl attribute for an XML schema.

See Also:

- "DBA_XML_SCHEMA_NAMESPACES"
- "USER_XML_SCHEMA_NAMESPACES"
- *Oracle XML DB Developer's Guide* for information about registering an XML schema with Oracle XML DB
- *Oracle XML DB Developer's Guide* for information about restrictions for an XML schema URL

4.169 ALL_XML_SCHEMA_SIMPLE_TYPES

ALL_XML_SCHEMA_SIMPLE_TYPES describes all simple types accessible to the current user.

Related Views

- DBA_XML_SCHEMA_SIMPLE_TYPES describes all simple types.
- USER_XML_SCHEMA_SIMPLE_TYPES describes all simple types owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		The user who owns the type
SCHEMA_URL	VARCHAR2(700)		The URL of the schema within which the type is defined Refer to the **See Also** note below for links to more information about the schemaurl attribute for an XML schema.
TARGET_NAMESPACE	VARCHAR2(2000)		The namespace of the type
SIMPLE_TYPE_NAME	VARCHAR2(256)		Name of the simple type
SIMPLE_TYPE	XMLTYPE(XMLSchema "http://xmlns.oracle.com/xdb/XDBSchema.xsd" Element "simpleType")		The actual XMLType of the type

See Also:

- "DBA_XML_SCHEMA_SIMPLE_TYPES"
- "USER_XML_SCHEMA_SIMPLE_TYPES"
- *Oracle XML DB Developer's Guide* for information about registering an XML schema with Oracle XML DB
- *Oracle XML DB Developer's Guide* for information about restrictions for an XML schema URL

4.170 ALL_XML_SCHEMA_SUBSTGRP_HEAD

ALL_XML_SCHEMA_SUBSTGRP_HEAD describes the heads of substitution groups accessible to the current user.

Related Views

- DBA_XML_SCHEMA_SUBSTGRP_HEAD describes the heads of substitution groups.
- USER_XML_SCHEMA_SUBSTGRP_HEAD describes the heads of substitution groups owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		The user who owns the element
SCHEMA_URL	VARCHAR2(700)		The URL of the schema within which the element is defined Refer to the **See Also** note below for links to more information about the `schemaurl` attribute for an XML schema.
TARGET_NAMESPACE	VARCHAR2(2000)		The namespace of the element
ELEMENT_NAME	VARCHAR2(256)		Name of the element
ELEMENT	XMLTYPE(XMLSchema "http://xmlns.oracle.com/xdb/XDBSchema.xsd" Element "element")		The actual XML fragment of the element

See Also:

- "DBA_XML_SCHEMA_SUBSTGRP_HEAD"
- "USER_XML_SCHEMA_SUBSTGRP_HEAD"
- *Oracle XML DB Developer's Guide* for information about registering an XML schema with Oracle XML DB
- *Oracle XML DB Developer's Guide* for information about restrictions for an XML schema URL

4.171 ALL_XML_SCHEMA_SUBSTGRP_MBRS

`ALL_XML_SCHEMA_SUBSTGRP_MBRS` describes all members of substitution groups accessible to the current user.

Related Views

- `DBA_XML_SCHEMA_SUBSTGRP_MBRS` describes all members of substitution groups.
- `USER_XML_SCHEMA_SUBSTGRP_MBRS` describes all members of substitution groups owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		The user who owns the element
SCHEMA_URL	VARCHAR2(700)		The URL of the schema within which the element is defined Refer to the **See Also** note below for links to more information about the `schemaurl` attribute for an XML schema.
TARGET_NAMESPACE	VARCHAR2(2000)		The namespace of the element

Column	Datatype	NULL	Description
ELEMENT_NAME	VARCHAR2(256)		Name of the element
ELEMENT	XMLTYPE(XMLSchema "http://xmlns.oracle.com/xdb/XDBSchema.xsd" Element "element")		The actual XML fragment of the element
HEAD_OWNER	VARCHAR2(128)		The user who owns the head element for the current element
HEAD_SCHEMA_URL	VARCHAR2(700)		The URL of the schema within which the head element exists
HEAD_TARGET_NAMESPACE	VARCHAR2(2000)		The namespace of the head element
HEAD_ELEMENT_NAME	VARCHAR2(256)		Name of the head element
HEAD_ELEMENT	XMLTYPE(XMLSchema "http://xmlns.oracle.com/xdb/XDBSchema.xsd" Element "element")		The actual XMLType of the head element

See Also:

- "DBA_XML_SCHEMA_SUBSTGRP_MBRS"
- "USER_XML_SCHEMA_SUBSTGRP_MBRS"
- *Oracle XML DB Developer's Guide* for information about registering an XML schema with Oracle XML DB
- *Oracle XML DB Developer's Guide* for information about restrictions for an XML schema URL

4.172 ALL_XML_SCHEMAS

ALL_XML_SCHEMAS describes the registered XML schemas accessible to the current user.

Related Views

- DBA_XML_SCHEMAS describes all registered XML schemas in the database.
- USER_XML_SCHEMAS describes the registered XML schemas owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the XML schema

Column	Datatype	NULL	Description
SCHEMA_URL	VARCHAR2(700)		Schema URL of the XML schema Refer to the **See Also** note below for links to more information about the `schemaurl` attribute for an XML schema.
LOCAL	VARCHAR2(3)		Indicates whether the XML schema is local (`YES`) or global (`NO`)
SCHEMA	XMLTYPE		XML schema document
INT_OBJNAME	VARCHAR2(4000)		Internal database object name for the schema
QUAL_SCHEMA_URL	VARCHAR2(865)		Fully qualified schema URL
HIER_TYPE	VARCHAR2(11)		Type of hierarchy for which the schema is enabled: • `NONE` • `RESMETADATA` • `CONTENTS`
BINARY	VARCHAR2(3)		Indicates whether the XML Schema is registered for binary encoding usage (`YES`) or not (`NO`)
SCHEMA_ID	RAW(16)		Opaque schema identifier (16 bytes)
HIDDEN	VARCHAR2(3)		Indicates whether the XML Schema has been deleted in hidden mode (`YES`) or not (`NO`)

See Also:

- "DBA_XML_SCHEMAS"
- "USER_XML_SCHEMAS"
- *Oracle XML DB Developer's Guide* for information about registering an XML schema with Oracle XML DB
- *Oracle XML DB Developer's Guide* for information about restrictions for an XML schema URL

4.173 ALL_XML_TAB_COLS

`ALL_XML_TAB_COLS` describes the columns of the XML tables accessible to the current user.

Related Views

- `DBA_XML_TAB_COLS` describes the columns of all XML tables in the database.
- `USER_XML_TAB_COLS` describes the columns of the XML tables owned by the current user. This view does not display the `OWNER` column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the XML table
TABLE_NAME	VARCHAR2(128)		Name of the XML table

Column	Datatype	NULL	Description
COLUMN_NAME	VARCHAR2(4000)		Name of the XML table column
XMLSCHEMA	VARCHAR2(700)		Name of the XML Schema that is used for the table definition
SCHEMA_OWNER	VARCHAR2(128)		Owner of the XML Schema that is used for the table definition
ELEMENT_NAME	VARCHAR2(2000)		Name of the XML SChema element that is used for the table
STORAGE_TYPE	VARCHAR2(20)		Storage option for the XMLType data: • BINARY • CLOB • OBJECT-RELATIONAL • TRANSPORTABLE BINARY **Note:** The CLOB storage option for XMLType data is deprecated in Oracle Database 12*c* Release 1 (12.1). Oracle recommends instead using the TRANSPORTABLE BINARY storage option.
ANYSCHEMA	VARCHAR2(3)		If storage is BINARY, indicates whether the column allows ANYSCHEMA (YES) or not (NO), else NULL
NONSCHEMA	VARCHAR2(3)		If storage is BINARY, indicates whether the column allows NONSCHEMA (YES) or not (NO), else NULL
TOKENSETS	VARCHAR2(4000)		This column is for internal use only.

See Also:

- "DBA_XML_TAB_COLS"
- "USER_XML_TAB_COLS"

4.174 ALL_XML_TABLES

ALL_XML_TABLES describes the XML tables accessible to the current user.

Related Views

- DBA_XML_TABLES describes all XML tables in the database.
- USER_XML_TABLES describes the XML tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the XML table
TABLE_NAME	VARCHAR2(128)		Name of the XML table
XMLSCHEMA	VARCHAR2(700)		Name of the XML Schema that is used for the table definition

Column	Datatype	NULL	Description
SCHEMA_OWNER	VARCHAR2(128)		Owner of the XML Schema that is used for the table definition
ELEMENT_NAME	VARCHAR2(2000)		Name of the XML SChema element that is used for the table
STORAGE_TYPE	VARCHAR2(20)		Storage option for the XMLType data: • BINARY • CLOB • OBJECT-RELATIONAL • TRANSPORTABLE BINARY **Note:** The CLOB storage option for XMLType data is deprecated in Oracle Database 12*c* Release 1 (12.1). Oracle recommends instead using the TRANSPORTABLE BINARY storage option.
ANYSCHEMA	VARCHAR2(3)		If storage is BINARY, indicates whether the column allows ANYSCHEMA (YES) or not (NO), else NULL
NONSCHEMA	VARCHAR2(3)		If storage is BINARY, indicates whether the column allows NONSCHEMA (YES) or not (NO), else NULL
TOKENSETS	VARCHAR2(4000)		This column is for internal use only.

See Also:

- "DBA_XML_TABLES"
- "USER_XML_TABLES"

4.175 ALL_XML_VIEW_COLS

ALL_XML_VIEW_COLS describes the columns of the XML views accessible to the current user.

Related Views

- DBA_XML_VIEW_COLS describes the columns of all XML views in the database.
- USER_XML_VIEW_COLS describes the columns of the XML views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the XML view
VIEW_NAME	VARCHAR2(128)		Name of the XML view
COLUMN_NAME	VARCHAR2(4000)		Name of the XML view column
XMLSCHEMA	VARCHAR2(700)		Name of the XML Schema that is used for the view definition
SCHEMA_OWNER	VARCHAR2(128)		Owner of the XML Schema that is used for the view definition

Column	Datatype	NULL	Description
ELEMENT_NAME	VARCHAR2(2000)		Name of the XML SChema element that is used for the view

See Also:

- "DBA_XML_VIEW_COLS"
- "USER_XML_VIEW_COLS"

4.176 ALL_XML_VIEWS

ALL_XML_VIEWS describes the XML views accessible to the current user.

Related Views

- DBA_XML_VIEWS describes all XML views the database.
- USER_XML_VIEWS describes the XML views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the XML view
VIEW_NAME	VARCHAR2(128)		Name of the XML view
XMLSCHEMA	VARCHAR2(700)		Name of the XML Schema that is used for the view definition
SCHEMA_OWNER	VARCHAR2(128)		Owner of the XML Schema that is used for the view definition
ELEMENT_NAME	VARCHAR2(2000)		Name of the XML SChema element that is used for the view

See Also:

- "DBA_XML_VIEWS"
- "USER_XML_VIEWS"

4.177 ALL_XSTREAM_ADMINISTRATOR

ALL_XSTREAM_ADMINISTRATOR displays information about the current users's granted privileges to be an XStream administrator by procedures in the DBMS_XSTREAM_AUTH package.

Related View

DBA_XSTREAM_ADMINISTRATOR displays information about the users who have been granted privileges to be XStream administrators by procedures in the DBMS_XSTREAM_AUTH package.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user who has been granted privileges to be an XStream administrator
PRIVILEGE_TYPE	VARCHAR2(7)		Type of privilege granted: • APPLY • CAPTURE • * - Both APPLY and CAPTURE
GRANT_SELECT_PRIVILEGES	VARCHAR2(3)		Shows whether set of privileges granted to the user (grantee) includes the SELECT_CATALOG_ROLE role, which enables the user to manage other XStream servers that belong to other XStream users. Possible values: • YES: The administrator has the SELECT_CATALOG_ROLE role and other privileges, is considered a full privilege administrator, and can manage other users' XStream configuration • NO: The administrator is considered a minimum privilege administrator, and can only manage XStream configurations where the apply_user or capture_user (based on the PRIVILEGE_TYPE column) matches the username.
CREATE_TIME	TIMESTAMP(6)		Time at which the privilege was granted
LAST_MODIFIED	TIMESTAMP(6)		Time at which the privilege was last modified

See Also:

- "DBA_XSTREAM_ADMINISTRATOR"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_XSTREAM_AUTH package

4.178 ALL_XSTREAM_INBOUND

ALL_XSTREAM_INBOUND displays information about the XStream inbound servers accessible to the current user.

Related View

DBA_XSTREAM_INBOUND displays information about all XStream inbound servers in the database.

Column	Datatype	NULL	Description
SERVER_NAME	VARCHAR2(128)	NOT NULL	Name of the inbound server
QUEUE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the queue associated with the inbound server
QUEUE_NAME	VARCHAR2(128)	NOT NULL	Name of the queue associated with the inbound server
APPLY_USER	VARCHAR2(128)		Name of the user who can connect to the inbound server and apply messages
USER_COMMENT	VARCHAR2(4000)		User comment
CREATE_DATE	TIMESTAMP(6)		Date when the inbound server was created
STATUS	VARCHAR2(8)		Status of the inbound server: • DISABLED - The inbound server is not running. • DETACHED - The inbound server is running, but the XStream client application is not attached to it. • ATTACHED - The inbound server is running, and the XStream client application is attached to it. • ABORTED - The inbound server became disabled because it encountered an error.
COMMITTED_DATA_ONLY	VARCHAR2(3)		YES - means the inbound server can receive only LCRs in committed transactions from the XStream client application. A committed transaction is an assembled, noninterleaving transaction with no rollbacks.

See Also:

"DBA_XSTREAM_INBOUND"

4.179 ALL_XSTREAM_INBOUND_PROGRESS

ALL_XSTREAM_INBOUND_PROGRESS displays information about the progress made by the XStream inbound servers accessible to the current user.

Related View

DBA_XSTREAM_INBOUND_PROGRESS displays information about the progress made by all XStream inbound servers in the database.

Column	Datatype	NULL	Description
SERVER_NAME	VARCHAR2(128)	NOT NULL	Name of the inbound server
PROCESSED_LOW_POSITION	RAW(64)		Position of the processed low transaction
APPLIED_LOW_POSITION	RAW(64)		All messages with a commit position less than this value have been applied
APPLIED_HIGH_POSITION	RAW(64)		Highest commit position of a transaction that has been applied
SPILL_POSITION	RAW(64)		Position of the spill low watermark of the transactions currently being applied
OLDEST_POSITION	RAW(64)		Earliest position of the transactions currently being applied
OLDEST_MESSAGE_NUMBER	NUMBER	NOT NULL	Earliest message number of the transactions currently being applied
APPLIED_MESSAGE_NUMBER	NUMBER	NOT NULL	Message number up to which all transactions have definitely been applied. This value is the low watermark for the inbound server. That is, messages with a commit message number less than or equal to this message number have definitely been applied, but some messages with a higher commit message number may also have been applied.
APPLIED_TIME	DATE		Time at which the message with the message number displayed in the APPLIED_MESSAGE_NUMBER column was applied
APPLIED_MESSAGE_CREATE_TIME	DATE		Time at which the message with the message number displayed in the APPLIED_MESSAGE_NUMBER column was created at its source database
SPILL_MESSAGE_NUMBER	NUMBER		Spill low watermark. Any message with a lower SCN has either been applied or spilled to disk. The XStream client application does not need to send logical change records (LCRs) with a lower SCN than the spill low watermark. Spilled messages may not have been applied yet.
SOURCE_DATABASE	VARCHAR2(128)	NOT NULL	Database where the transaction originated
SOURCE_ROOT_NAME	VARCHAR2(128)		The global name of the source root database

> **See Also:**
>
> "DBA_XSTREAM_INBOUND_PROGRESS"

4.180 ALL_XSTREAM_OUT_SUPPORT_MODE

`ALL_XSTREAM_OUT_SUPPORT_MODE` displays information about the level of XStream capture process support for the tables accessible to the current user in the database.

Related View

`DBA_XSTREAM_OUT_SUPPORT_MODE` displays information about the level of XStream capture process support for the tables in the database.

Column	Datatype	NULL	Description
`OWNER`	`VARCHAR2(128)`		Table owner
`OBJECT_NAME`	`VARCHAR2(128)`		Table name
`SUPPORT_MODE`	`VARCHAR2(6)`		Capture process support level for the table: • `FULL` - A capture process can capture changes made to all of the columns in the table. • `ID KEY` - A capture process can capture changes made to the key columns and any other columns in the table that are supported by the capture process, except for LOB, `LONG`, `LONG RAW`, and `XMLType` columns. • `NONE` - A capture process cannot capture changes made to any columns in the table.
`EXPLANATION`	`VARCHAR2(4000)`		Reason the table does not have `FULL` capture process support This column is populated only when both of the following conditions are met: • The value of the `COMPATIBLE` initialization parameter is `20.0` or higher • The value of the `SUPPORT_MODE` column is `ID KEY` or `NONE`

> **See Also:**
>
> "DBA_XSTREAM_OUT_SUPPORT_MODE"

4.181 ALL_XSTREAM_OUTBOUND

ALL_XSTREAM_OUTBOUND displays information about the XStream outbound servers accessible to the current user.

Related View

DBA_XSTREAM_OUTBOUND displays information about all XStream outbound servers in the database.

Column	Datatype	NULL	Description
SERVER_NAME	VARCHAR2(128)	NOT NULL	Name of the outbound server
CONNECT_USER	VARCHAR2(128)		Name of the user who can connect to the outbound server and process the outbound LCRs
CAPTURE_NAME	VARCHAR2(128)		Name of the Replication capture process
SOURCE_DATABASE	VARCHAR2(128)		Database where the transaction originated
CAPTURE_USER	VARCHAR2(128)		Current user who is enqueuing captured messages
QUEUE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the queue associated with the outbound server
QUEUE_NAME	VARCHAR2(128)	NOT NULL	Name of the queue associated with the outbound server
USER_COMMENT	VARCHAR2(4000)		User comment
CREATE_DATE	TIMESTAMP(6)		Date when the outbound server was created
STATUS	VARCHAR2(8)		Status of the outbound server: • DISABLED - The outbound server is not running. • DETACHED - The outbound server is running, but the XStream client application is not attached to it. • ATTACHED - The outbound server is running, and the XStream client application is attached to it. • ABORTED - The outbound server became disabled because it encountered an error.
COMMITTED_DATA_ONLY	VARCHAR2(3)		YES if the outbound server can send only LCRs in committed transactions to the XStream client application. A committed transaction is an assembled, noninterleaving transaction with no rollbacks. NO if the outbound server can send LCRs in transactions that have not yet committed to the XStream client application. This mode is for internal Oracle use only.
START_SCN	NUMBER		The SCN from which the outbound server's capture process started capturing changes when it was last started
START_TIME	TIMESTAMP(6)		The time from which the outbound server's capture process started capturing changes when it was last started

Column	Datatype	NULL	Description
SOURCE_ROOT_NAME	VARCHAR2(128)		The global name of the source root database
LCRID_VERSION	NUMBER		LCR ID format currently being used

> **See Also:**
>
> "DBA_XSTREAM_OUTBOUND"

4.182 ALL_XSTREAM_OUTBOUND_PROGRESS

ALL_XSTREAM_OUTBOUND_PROGRESS displays information about the progress made by the XStream outbound servers accessible to the current user.

Related View

DBA_XSTREAM_OUTBOUND_PROGRESS displays information about the progress made by all XStream outbound servers in the database.

Column	Datatype	NULL	Description
SERVER_NAME	VARCHAR2(128)	NOT NULL	Name of the outbound server
SOURCE_DATABASE	VARCHAR2(128)		Global name of the database where the transaction originated. For a PDB, this is the global name of the PDB.
PROCESSED_LOW_POSITION	RAW(64)		Position of the low-watermark transaction processed by the outbound server
PROCESSED_LOW_TIME	DATE		Time when the processed low position was last updated by the outbound server
OLDEST_POSITION	RAW(64)		The position of the earliest LCR that is required by the XStream client application
SOURCE_ROOT_NAME	VARCHAR2(128)		The global name of the source root database
PROCESSED_LOW_SCN	NUMBER	NOT NULL	SCN of the processed low transaction
OLDEST_SCN	NUMBER	NOT NULL	Oldest SCN of the transactions currently being captured

> **See Also:**
>
> "DBA_XSTREAM_OUTBOUND_PROGRESS"

4.183 ALL_XSTREAM_RULES

ALL_XSTREAM_RULES displays information about the XStream rules accessible to the current user.

Related View

DBA_XSTREAM_RULES displays information about all XStream server rules in the database.

Column	Datatype	NULL	Description
STREAMS_NAME	VARCHAR2(128)		Name of the XStream process
STREAMS_TYPE	VARCHAR2(12)		Type of the XStream process: • CAPTURE • APPLY
STREAMS_RULE_TYPE	VARCHAR2(9)		The XStream type of the rule: • TABLE • SCHEMA • GLOBAL
RULE_SET_OWNER	VARCHAR2(128)		Owner of the rule set
RULE_SET_NAME	VARCHAR2(128)		Name of the rule set
RULE_SET_TYPE	CHAR(8)		Type of the rule set: • POSITIVE • NEGATIVE
RULE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule
RULE_NAME	VARCHAR2(128)	NOT NULL	Name of the rule
RULE_TYPE	VARCHAR2(9)		The type of the rule: • DML • DDL
RULE_CONDITION	CLOB		Current rule condition
SCHEMA_NAME	VARCHAR2(128)		For table and schema rules, the schema name
OBJECT_NAME	VARCHAR2(128)		For table rules, the table name
INCLUDE_TAGGED_LCR	VARCHAR2(3)		Indicates whether to include tagged LCRs (YES) or not (NO)
SUBSETTING_OPERATION	VARCHAR2(6)		For subset rules, the type of operation: • INSERT • UPDATE • DELETE
DML_CONDITION	VARCHAR2(4000)		For subset rules, the row subsetting condition
SOURCE_DATABASE	VARCHAR2(128)		The global name of the database where the LCRs originated. In a PDB, this is the global name of the PDB.
ORIGINAL_RULE_CONDITION	VARCHAR2(4000)		For rules created by the XStream administrative APIs, the original rule condition when the rule was created

Column	Datatype	NULL	Description
SAME_RULE_CONDITION	VARCHAR2(3)		For rules created by the XStream administrative APIs, indicates whether the current rule condition is the same as the original rule condition (YES) or not (NO)
SOURCE_ROOT_NAME	VARCHAR2(128)		The global name of the source root database
SOURCE_CONTAINER_NAME	VARCHAR2(128)		The container name of the database where the transactions originated

> **See Also:**
>
> "DBA_XSTREAM_RULES"

4.184 ALL_XSTREAM_TRANSFORMATIONS

ALL_XSTREAM_TRANSFORMATIONS displays information about all XStream transformations accessible to the current user, in order of execution.

Related View

DBA_XSTREAM_TRANSFORMATIONS displays information about all XStream transformations available on a system, in order of execution.

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2(128)		Owner of the rule which has an associated transformation
RULE_NAME	VARCHAR2(128)		Name of the rule which has an associated transformation
TRANSFORM_TYPE	VARCHAR2(26)		Type of the transformation: • DECLARATIVE TRANSFORMATION • SUBSET RULE • CUSTOM TRANSFORMATION
FROM_SCHEMA_NAME	VARCHAR2(128)		Schema to be renamed
TO_SCHEMA_NAME	VARCHAR2(128)		New schema name
FROM_TABLE_NAME	VARCHAR2(128)		Table to be renamed
TO_TABLE_NAME	VARCHAR2(128)		New table name
SCHEMA_NAME	VARCHAR2(128)		Schema of the column to be modified
TABLE_NAME	VARCHAR2(128)		Table of the column to be modified
FROM_COLUMN_NAME	VARCHAR2(4000)		Column to be renamed
TO_COLUMN_NAME	VARCHAR2(4000)		New column name
COLUMN_NAME	VARCHAR2(4000)		Column to add or delete
COLUMN_VALUE	ANYDATA		Value of the column to add
COLUMN_TYPE	VARCHAR2(4000)		Type of the new column
COLUMN_FUNCTION	VARCHAR2(128)		Name of the default function used to add a column

Column	Datatype	NULL	Description
VALUE_TYPE	VARCHAR2(3)		Indicates whether to modify the old (OLD), new (NEW), or both (*) values of the LCR
USER_FUNCTION_NAME	VARCHAR2(4000)		Name of the user-defined transformation function to run
SUBSETTING_OPERATION	VARCHAR2(6)		DML operation for row subsetting: • INSERT • UPDATE • DELETE
DML_CONDITION	VARCHAR2(4000)		Row subsetting condition
DECLARATIVE_TYPE	VARCHAR2(13)		Type of declarative transform to run: • KEEP COLUMNS • DELETE COLUMN • RENAME COLUMN • ADD COLUMN • RENAME TABLE • RENAME SCHEMA
PRECEDENCE	NUMBER		Execution order relative to other declarative transformations on the same STEP_NUMBER
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

See Also:

"DBA_XSTREAM_TRANSFORMATIONS"

4.185 ALL_XTERNAL_LOC_PARTITIONS

ALL_XTERNAL_LOC_PARTITIONS describes partition-level locations accessible to the current user.

If an external table is partitioned, then the existing ALL_EXTERNAL_LOCATIONS, DBA_EXTERNAL_LOCATIONS, and USER_EXTERNAL_LOCATIONS views will have no rows for that table. Instead, locations will be indicated in the ALL_XTERNAL_LOC_PARTITIONS, DBA_XTERNAL_LOC_PARTITIONS, USER_XTERNAL_LOC_PARTITIONS, ALL_XTERNAL_LOC_SUBPARTITIONS, DBA_XTERNAL_LOC_SUBPARTITIONS, and USER_XTERNAL_LOC_SUBPARTITIONS views.

Related Views

- DBA_XTERNAL_LOC_PARTITIONS describes partition-level locations in the database.
- USER_XTERNAL_LOC_PARTITIONS describes partition-level locations owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the partitioned external table

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2(128)		Name of the partitioned external table
PARTITION_NAME	VARCHAR2(128)		Name of the partition
LOCATION	VARCHAR2(4000)		External table location clause for the partition
DIRECTORY_OWNER	CHAR(3)		Owner of the directory containing the external table partition location
DIRECTORY_NAME	VARCHAR2(128)		Name of the directory containing the external table partition location

See Also:

- "DBA_XTERNAL_LOC_PARTITIONS"
- "USER_XTERNAL_LOC_PARTITIONS"

4.186 ALL_XTERNAL_LOC_SUBPARTITIONS

ALL_XTERNAL_LOC_SUBPARTITIONS describes subpartition-level locations accessible to the current user.

If an external table is partitioned, then the existing ALL_EXTERNAL_LOCATIONS, DBA_EXTERNAL_LOCATIONS, and USER_EXTERNAL_LOCATIONS views will have no rows for that table. Instead, locations will be indicated in the ALL_XTERNAL_LOC_PARTITIONS, DBA_XTERNAL_LOC_PARTITIONS, USER_XTERNAL_LOC_PARTITIONS, ALL_XTERNAL_LOC_SUBPARTITIONS, DBA_XTERNAL_LOC_SUBPARTITIONS, and USER_XTERNAL_LOC_SUBPARTITIONS views.

Related Views

- DBA_XTERNAL_LOC_SUBPARTITIONS describes subpartition-level locations in the database.
- USER_XTERNAL_LOC_SUBPARTITIONS describes subpartition-level locations owned by the current user. This view does not display the TABLE_OWNER column.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the partitioned external table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the partitioned external table
PARTITION_NAME	VARCHAR2(128)		Name of the partition
SUBPARTITION_NAME	VARCHAR2(128)		Name of the subpartition
LOCATION	VARCHAR2(4000)		External table location clause for the subpartition
DIRECTORY_OWNER	CHAR(3)		Owner of the directory containing the external table subpartition location
DIRECTORY_NAME	VARCHAR2(128)		Name of the directory containing the external table subpartition location

See Also:

- "DBA_XTERNAL_LOC_SUBPARTITIONS"
- "USER_XTERNAL_LOC_SUBPARTITIONS"

4.187 ALL_XTERNAL_PART_TABLES

ALL_XTERNAL_PART_TABLES describes object-level information for partitioned external tables accessible to the current user.

Related Views

- DBA_XTERNAL_PART_TABLES describes object-level information for partitioned external tables in the database
- USER_XTERNAL_PART_TABLES describes object-level information for partitioned external tables owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the partitioned external table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the partitioned external table
TYPE_OWNER	CHAR(3)		Owner of the implementation type for the external table access driver
TYPE_NAME	VARCHAR2(128)		Name of the implementation type for the external table access driver
DEFAULT_DIRECTORY_OWNER	CHAR(3)		Owner of the default directory for the external table
DEFAULT_DIRECTORY_NAME	VARCHAR2(128)		Name of the default directory for the external table
REJECT_LIMIT	VARCHAR2(40)		Reject limit for the external table, or UNLIMITED
ACCESS_TYPE	VARCHAR2(7)		Type of access parameters for the external table (BLOB, CLOB)
ACCESS_PARAMETERS	CLOB		Access parameters for the external table
PROPERTY	VARCHAR2(10)		Property of the external table (REFERENCED, ALL)
INMEMORY[1]	VARCHAR2(8)		Indicates whether the In-Memory Column Store (IM column store) is by default enabled (ENABLED), disabled (DISABLED), or not specified (NONE) for partitions in the external table
INMEMORY_COMPRESSION[1]	VARCHAR2(17)		Indicates the default compression level for the IM column store: • NO MEMCOMPRESS • FOR DML • FOR QUERY [LOW | HIGH] • FOR CAPACITY [LOW | HIGH] • NULL

1 This column is available starting with Oracle Database 21c. It appears in the USER_XTERNAL_PART_TABLES view and is omitted from the ALL_XTERNAL_PART_TABLES and DBA_XTERNAL_PART_TABLES views.

> **See Also:**
>
> - "DBA_XTERNAL_PART_TABLES"
> - "USER_XTERNAL_PART_TABLES"

4.188 ALL_XTERNAL_TAB_PARTITIONS

ALL_XTERNAL_TAB_PARTITIONS describes partition-level information for partitioned external tables accessible to the current user.

Related Views

- DBA_XTERNAL_TAB_PARTITIONS describes partition-level information for partitioned external tables in the databae
- USER_XTERNAL_TAB_PARTITIONS describes partition-level information for partitioned external tables owned by the current user. This view does not display the TABLE_OWNER column.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)		Owner of the partitioned external table
TABLE_NAME	VARCHAR2(128)		Name of the partitioned external table
PARTITION_NAME	VARCHAR2(128)		Name of the partition
DEFAULT_DIRECTORY_OWNER	CHAR(3)		Owner of the default directory for the external table partition
DEFAULT_DIRECTORY_NAME	VARCHAR2(128)		Name of the default directory for the external table partition
ACCESS_TYPE	VARCHAR2(7)		Type of access parameters for the partition (BLOB, CLOB)
ACCESS_PARAMETERS	CLOB		Access parameters for the external table partition
PROPERTY	VARCHAR2(10)		Property of the external table partition: • REFERENCED - Referenced columns • ALL - All columns
INMEMORY	VARCHAR2(8)		Indicates whether the In-Memory Column Store (IM column store) is enabled (ENABLED) or disabled (DISABLED) for the external table partition
INMEMORY_COMPRESSION	VARCHAR2(17)		Indicates the compression level for the IM column store: • NO MEMCOMPRESS • FOR DML • FOR QUERY [LOW | HIGH] • FOR CAPACITY [LOW | HIGH] • NULL

> **See Also:**
>
> - "DBA_XTERNAL_TAB_PARTITIONS"
> - "USER_XTERNAL_TAB_PARTITIONS"

4.189 ALL_XTERNAL_TAB_SUBPARTITIONS

ALL_XTERNAL_TAB_SUBPARTITIONS describes subpartition-level information for partitioned external tables accessible to the current user.

Related Views

- DBA_XTERNAL_TAB_SUBPARTITIONS describes subpartition-level information for partitioned external tables in the database.
- USER_XTERNAL_TAB_SUBPARTITIONS describes subpartition-level information for partitioned external tables owned by the current user. This view does not display the TABLE_OWNER column.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the partitioned external table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the partitioned external table
PARTITION_NAME	VARCHAR2(128)		Name of the partition
SUBPARTITION_NAME	VARCHAR2(128)		Name of the subpartition
DEFAULT_DIRECTORY_OWNER	CHAR(3)		Owner of the default directory for the external table partition
DEFAULT_DIRECTORY_NAME	VARCHAR2(128)		Name of the default directory for the external table partition
ACCESS_TYPE	VARCHAR2(7)		Type of access parameters for the partition (BLOB, CLOB)
ACCESS_PARAMETERS	CLOB		Access parameters for the external table partition

> **See Also:**
>
> - "DBA_XTERNAL_TAB_SUBPARTITIONS"
> - "USER_XTERNAL_TAB_SUBPARTITIONS"

4.190 ALL_ZONEMAP_MEASURES

ALL_ZONEMAP_MEASURES describes the measures for all zone maps accessible to the user.

Related Views

- DBA_ZONEMAP_MEASURES describes the measures for all the zone maps in the database.
- USER_ZONEMAP_MEASURES describes the measures for all the zone maps owned by the user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the zone map
ZONEMAP_NAME	VARCHAR2(128)	NOT NULL	Name of the zone map
MEASURE	LONG		Column whose MIN/MAX value is computed
POSITION_IN_SELECT	NUMBER	NOT NULL	Original position of the mesaure aggregate on the SELECT list of zone map defining query
AGG_FUNCTION	VARCHAR2(13)		Name of aggregate in zone map table
AGG_COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column whose MIN/MAX per zone maintained

Note:

This view is intended for use with Oracle Exadata release 12.1.2.1.1 or later.

See Also:

- "DBA_ZONEMAP_MEASURES"
- "USER_ZONEMAP_MEASURES"
- *Oracle Database Data Warehousing Guide* for more information about zone maps

4.191 ALL_ZONEMAPS

ALL_ZONEMAPS describes all the zone maps accessible to the user.

Related Views

- DBA_ZONEMAPS describes all the zone maps in the database.
- USER_ZONEMAPS describes all the zone maps owned by the user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the zone map
ZONEMAP_NAME	VARCHAR2(128)		Name of the zone map
FACT_OWNER	VARCHAR2(128)		Owner of the fact table of the zone map
FACT_TABLE	VARCHAR2(128)		Name of the fact table on which the zone map is defined
SCALE	NUMBER		Scale factor of the zone map
HIERARCHICAL	VARCHAR2(12)		Indicates whether the zone map is hierarchical (YES) or not (NO)
WITH_CLUSTERING	VARCHAR2(15)		Indicates whether the zone map is created with the CLUSTERING clause (YES) or not (NO)
AUTOMATIC	VARCHAR2(9)		Indicates whether the zone map is automatic (YES) or not (NO)
QUERY	LONG		Zone map defining query
QUERY_LEN	NUMBER(38)		Length of defining query in bytes
PRUNING	VARCHAR2(8)		Indicates whether the zone map is enabled for pruning (ENABLED) or not (DISABLED)
REFRESH_MODE	VARCHAR2(17)		Refresh mode for the zone map: • COMMIT • DEMAND • DATAMOVEMENT • LOAD • LOAD DATAMOVEMENT
REFRESH_METHOD	VARCHAR2(14)		Refresh method for the zone map • COMPLETE • FORCE • FAST
LAST_REFRESH_METHOD	VARCHAR2(19)		The last refresh method used for the zone map: • NA • COMPLETE • FAST • ERROR-UNKNOWN
LAST_REFRESH_TIME	TIMESTAMP(9)		Time of the last refresh
INVALID	VARCHAR2(7)		Indicates whether the zone map is invalid due to some DDL (YES) or not (NO)
STALE	VARCHAR2(7)		Indicates whether the zone map is stale because of DML operations and cannot be used for pruning (YES) or not (NO), or whether this cannot be determined (UNKNOWN)
PARTLY_STALE	VARCHAR2(12)		Indicates whether the zone map is partly stale (YES) or not (NO), or whether this cannot be determined (UNKNOWN). A partly stale zone map contains both fresh and stale zones.
INCOMPLETE	VARCHAR2(12)		Indicates whether the zone map has missing zones (YES) or not (NO), or whether this cannot be determined (UNKNOWN). Missing zones result when data is added to the base table and a subsequent refresh of the zone map is not performed.

Column	Datatype	NULL	Description
UNUSABLE	VARCHAR2(8)		Indicates whether the zone map has been marked unusable by the owner (YES) or not (NO)
COMPILE_STATE	VARCHAR2(19)		Current compile state of the zone map: • VALID • AUTHORIZATION_ERROR • COMPILATION_ERROR • NEEDS_COMPILE • ERROR_UNKNOWN Similar to ALL_MVIEWS.COMPILE_STATE.

Note:

This view is intended for use with Oracle Exadata release 12.1.2.1.1 or later.

See Also:

- "DBA_ZONEMAPS"
- "USER_ZONEMAPS"
- *Oracle Database Data Warehousing Guide* for more information about zone maps

4.192 AUDIT_ACTIONS

AUDIT_ACTIONS describes audit trail action type codes. This table can be used to map action type numbers to action type names.

Note:

The mapping explained in this view is valid for audit trail records from the following views only, and such audit records are generated only when unified auditing is not enabled:

- DBA_AUDIT_TRAIL
- DBA_COMMON_AUDIT_TRAIL
- DBA_FGA_AUDIT_TRAIL
- USER_AUDIT_TRAIL
- V$XML_AUDIT_TRAIL

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

Column	Datatype	NULL	Description
ACTION	NUMBER	NOT NULL	Numeric audit trail action type code.
NAME	VARCHAR2(28)	NOT NULL	Name of the type of audit trail action

4.193 AUDIT_UNIFIED_CONTEXTS

AUDIT_UNIFIED_CONTEXTS describes the application context's attributes, which are configured to be captured in the audit trail.

> **Note:**
>
> This view is populated only in an Oracle Database where unified auditing is enabled.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

Column	Datatype	NULL	Description
NAMESPACE	VARCHAR2(128)		Application context namespace
ATTRIBUTE	VARCHAR2(128)		Application context attribute
USER_NAME	VARCHAR2(128)		Username of database user for whom the application context's attribute is confiured to be captured in the audit trail

4.194 AUDIT_UNIFIED_ENABLED_POLICIES

`AUDIT_UNIFIED_ENABLED_POLICIES` describes all the audit policies that are enabled in the database.

> **Note:**
>
> This view is populated only in an Oracle Database where unified auditing is enabled.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

Column	Datatype	NULL	Description
`POLICY_NAME`	`VARCHAR2(128)`		Name of the audit policy
`ENABLED_OPTION`	`VARCHAR2(15)`		Enabled option of the audit policy. Possible values: • `BY USER`: For policies that are enabled on users • `EXCEPT USER`: For policies that are enabled on users • `BY GRANTED ROLE`: For policies that are enabled on roles • `INVALID`: For policies that are not enabled on either users or roles
`ENTITY_NAME`	`VARCHAR2(128)`		Database entity (user name or role name) on which the audit policy is enabled. When an audit policy is enabled on all database users, `ALL USERS` is displayed in this column.
`ENTITY_TYPE`	`VARCHAR2(7)`		Database entity type. Possible values: • `USER`: Indicates that the policy is enabled on a user or users. • `ROLE`: Indicates that the policy is enabled on a role or roles.
`SUCCESS`	`VARCHAR2(3)`		Indicates whether the audit policy is enabled for auditing successful events (`YES`) or not (`NO`)
`FAILURE`	`VARCHAR2(3)`		Indicates whether the audit policy is enabled for auditing unsuccessful events (`YES`) or not (`NO`)

4.195 AUDIT_UNIFIED_POLICIES

`AUDIT_UNIFIED_POLICIES` describes all audit policies created in the database.

> **Note:**
>
> This view is populated only in an Oracle Database where unified auditing is enabled.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

Column	Datatype	NULL	Description
POLICY_NAME	VARCHAR2(128)		Name of the audit policy
AUDIT_CONDITION	VARCHAR2(4000)		Condition associated with the audit policy
CONDITION_EVAL_OPT	VARCHAR2(9)		Evaluation option associated with the audit policy's condition. The possible values are `STATEMENT`, `SESSION`, `INSTANCE`, and `NONE`.
AUDIT_OPTION	VARCHAR2(128)		Auditing option defined in the audit policy
AUDIT_OPTION_TYPE	VARCHAR2(18)		Type of the auditing option. Possible values: • COLUMN ACTION • DATAPUMP ACTION • DIRECT LOAD ACTION • DV ACTION • INVALID • OBJECT ACTION • OLS_ACTION • ROLE PRIVILEGE • STANDARD ACTION • SYSTEM ACTION • SYSTEM PRIVILEGE • XS ACTION
OBJECT_SCHEMA	VARCHAR2(128)		Owner of the object, for an object-specific auditing option
OBJECT_NAME	VARCHAR2(128)		Name of the object, for an object-specific auditing option
OBJECT_TYPE	VARCHAR2(23)		Type of the object, for an object-specific auditing option

Column	Datatype	NULL	Description
COMMON	VARCHAR2(3)		Indicates whether the audit policy is a common audit policy or local audit policy. The value is NULL for a non-CDB. For local audit policies, the value of the COMMON column is always NO. For a CDB common policy: • If you query AUDIT_UNIFIED_POLICIES from the CDB root container, the value of the COMMON column will be YES and the value of the INHERITED column will be NO. • If you query AUDIT_UNIFIED_POLICIES from any other container besides the CDB root container, the value of the COMMON column and the INHERITED column will be YES. For an application container common policy: • If you query AUDIT_UNIFIED_POLICIES from the application root container, the value of the COMMON column will be YES and the value of the INHERITED column will be NO. • If you query AUDIT_UNIFIED_POLICIES from any other container besides the application root container, the value of the COMMON column and the INHERITED column will be YES.
INHERITED	VARCHAR2(3)		Indicates whether the audit policy was inherited from another container (YES) or not (NO). This value is NULL for non-CDBs.
AUDIT_ONLY_TOPLEVEL	VARCHAR2(3)		Indicates whether the audit policy is defined to audit only top level SQL statements (YES) or both top level SQL statements and recursive SQL statements (NO)
ORACLE_SUPPLIED	VARCHAR2(3)		Indicates whether the audit policy is an Oracle-supplied policy (YES) or not (NO) Oracle-supplied policies are also called predefined policies.
COLUMN_NAME	VARCHAR2(128)		If AUDIT_OPTION_TYPE = COLUMN ACTION, then this column displays the name of the table column on which the audit policy was created. In this case, the OBJECT_SCHEMA, OBJECT_NAME, and OBJECT_TYPE columns apply to the table containing the audited column. Otherwise, the value of this column is null.

4.196 AUDIT_UNIFIED_POLICY_COMMENTS

AUDIT_UNIFIED_POLICY_COMMENTS shows the description of each unified audit policy, if a description was entered for the unified audit policy using the COMMENT SQL statement.

> **Note:**
>
> This view is populated only in an Oracle Database where unified auditing is enabled.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

Column	Datatype	NULL	Description
POLICY_NAME	VARCHAR2(128)	NOT NULL	Name of the unified audit policy
COMMENTS	VARCHAR2(4000)		Description of the unified audit policy, if one was entered using the COMMENT SQL statement

4.197 AUDITABLE_SYSTEM_ACTIONS

AUDITABLE_SYSTEM_ACTIONS maps the auditable system action numbers to the action names. These actions are configurable for audit when unified auditing is enabled.

The actions include:

- All standard RDBMS actions (from the V$SQLCOMMAND view) except the following, which are not configurable for auditing:
  - ALTER EDITION
  - ALTER REWRITE EQUIVALENCE
  - ALTER SUMMARY
  - ALTER TRACING
  - CREATE BITMAPFILE
  - CREATE CONTROL FILE
  - CREATE DATABASE
  - CREATE SUMMARY
  - DECLARE REWRITE EQUIVALENCE
  - DROP BITMAPFILE
  - DROP DATABASE
  - DROP REWRITE EQUIVALENCE

  - DROP SUMMARY
  - FLASHBACK DATABASE
  - MERGE
  - SAVEPOINT
  - SET CONSTRAINTS
  - UNDROP OBJECT
  - UPDATE INDEXES
  - UPDATE JOIN INDEX
  - VALIDATE INDEX
- Other actions:
  - ALL
  - LOGON
  - LOGOFF

> **Note:**
>
> This view is populated only in an Oracle Database where unified auditing is enabled.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

Column	Datatype	NULL	Description
TYPE	NUMBER		Numeric component type for system wide actions
COMPONENT	VARCHAR2(64)		Name of component for system wide actions
ACTION	NUMBER		Numeric auditable action code for system wide actions
NAME	VARCHAR2(64)		Name of auditable action

Some auditable actions in `AUDITABLE_SYSTEM_ACTIONS` have different names than their equivalent commands in `V$SQLCOMMAND`, as shown in the following table:

AUDITABLE_SYSTEM_ACTIONS Action Name	V$SQLCOMMAND Command Name
GRANT	GRANT OBJECT
REVOKE	REVOKE OBJECT
AUDIT	AUDIT OBJECT
NOAUDIT	NOAUDIT OBJECT
EXECUTE	PL/SQL EXECUTE
EXPLAIN PLAN	EXPLAIN

AUDITABLE_SYSTEM_ACTIONS Action Name	V$SQLCOMMAND Command Name
CALL	CALL METHOD
PURGE DBA_RECYCLEBIN	PURGE DBA RECYCLEBIN

> **See Also:**
>
> "V$SQLCOMMAND"

4.198 CAT

`CAT` is a synonym for `USER_CATALOG`.

> **See Also:**
>
> "USER_CATALOG"

4.199 CATALOG

`CATALOG` is included for compatibility. Oracle recommends that you not use this view.

4.200 CHAINED_ROWS

`CHAINED_ROWS` stores the output for the `ANALYZE` statement with the `LIST CHAINED ROWS` clause.

You must run the `utlchain.sql` or `utlchn1.sql` script to create this table.

Column	Description
`OWNER_NAME`	Table owner
`TABLE_NAME`	Table name
`CLUSTER_NAME`	Cluster the table is in, if any
`PARTITION_NAME`	The name of the partition
`SUBPARTITION_NAME`	The name of the subpartition
`HEAD_ROWID`	ROWID the chained row is accessed by
`ANALYZE_TIMESTAMP`	Date/time that the `ANALYZE` statement was issued

4.201 CLIENT_RESULT_CACHE_STATS$

CLIENT_RESULT_CACHE_STATS$ displays various client result cache settings and usage statistics.

Statistics are stored as name, value pairs. For each client cache ID, there will be multiple rows for each statistic.

Column	Datatype	NULL	Description
CACHE_ID	NUMBER	NOT NULL	Unique ID per client cache
STAT_ID	NUMBER	NOT NULL	Statistic ID
NAME	VARCHAR2(128)		Name of the statistic (see Table 4-1)
VALUE	NUMBER		Value of the statistic

Table 4-1 CLIENT_RESULT_CACHE_STATS$ Statistics

Statistic Name	Description
Block Size	Size (in bytes) of each memory block in the result cache.
Block Count Max	Maximum number of blocks that can be allocated in the result cache based on the cache size configuration parameters on server and on client.
Block Count Current	Current number of blocks allocated by the client result cache.
Hash Bucket Count	Size of the hash table used for query matching.
Create Count Success	Number of cached result sets that did not get invalidated before caching all the rows of the result set.
Create Count Failure	Number of cached result sets that did not fetch all the rows in the result set.
Find Count	Number of cache hits.
Invalidation Count	Number of cached result sets that got invalidated due to database changes that could have affected the result set.
Delete Count Invalid	Number of cached result rests not invalidated whose memory was reclaimed by result cache.
Delete Count Valid	Number of invalidated cached result rests whose memory was reclaimed by result cache.

4.202 CLU

CLU is a synonym for USER_CLUSTERS.

> **See Also:**
>
> "USER_CLUSTERS"

4.203 COL

`COL` is included for compatibility. Oracle recommends that you not use this view.

4.204 COLS

`COLS` is a synonym for `USER_TAB_COLUMNS`.

> **See Also:**
>
> "USER_TAB_COLUMNS"

4.205 DATABASE_EXPORT_OBJECTS

`DATABASE_EXPORT_OBJECTS` lists simple path names for some of the object types belonging to a full Data Pump export, which is invoked using the `FULL=Y` parameter on the `expdp` command.

Users of the Data Pump Export and Import utilities can query this view to determine valid values for the `EXCLUDE` and `INCLUDE` parameters.

Column	Datatype	NULL	Description
OBJECT_PATH	VARCHAR2(200)	NOT NULL	Simple path name for the object type
COMMENTS	VARCHAR2(2000)		Comment on the object type
NAMED	CHAR(1)		Do objects of this type have names? If yes (`Y`), then the name can be specified in the optional name_clause on the `EXCLUDE` and `INCLUDE` parameters.

> **See Also:**
>
> - "SCHEMA_EXPORT_OBJECTS"
> - "TABLE_EXPORT_OBJECTS"
> - *Oracle Database Utilities* for more information on performing a full Data Pump export using the `expdp` command

4.206 DATABASE_PROPERTIES

`DATABASE_PROPERTIES` lists permanent database properties.

Column	Datatype	NULL	Description
PROPERTY_NAME	VARCHAR2(128)	NOT NULL	Property name
PROPERTY_VALUE	VARCHAR2(4000)		Property value
DESCRIPTION	VARCHAR2(4000)		Property description

Note:

The CDB_PROPERTIES view provides access to data visible to PDBs through the DATABASE_PROPERTIES view.

5

Static Data Dictionary Views: DBA_2PC_NEIGHBORS to DBA_HIST_JAVA_POOL_ADVICE

This chapter contains the static data dictionary views DBA_2PC_NEIGHBORS through DBA_HIST_JAVA_POOL_ADVICE.

5.1 DBA_2PC_NEIGHBORS

DBA_2PC_NEIGHBORS describes incoming and outgoing connections for pending transactions.

Column	Datatype	NULL	Description
LOCAL_TRAN_ID	VARCHAR2(22)		Local identifier of a transaction
IN_OUT	VARCHAR2(3)		IN for incoming connections, OUT for outgoing
DATABASE	VARCHAR2(128)		IN for client database name, OUT for outgoing database link
DBUSER_OWNER	VARCHAR2(128)		IN for name of local user, OUT for owner of database link
INTERFACE	VARCHAR2(1)		C for request commit, otherwise N for prepare or request read only commit
DBID	VARCHAR2(16)		Database ID at the other end of the connection
SESS#	NUMBER(38)		Session number of the connection at this database
BRANCH	VARCHAR2(128)		Transaction branch ID of the connection at this database

5.2 DBA_2PC_PENDING

DBA_2PC_PENDING describes distributed transactions awaiting recovery.

Column	Datatype	NULL	Description
LOCAL_TRAN_ID	VARCHAR2(22)	NOT NULL	String of form: n.n.n; n is a number
GLOBAL_TRAN_ID	VARCHAR2(169)		Globally unique transaction ID
STATE	VARCHAR2(16)	NOT NULL	Collecting, prepared, committed, forced commit, or forced rollback
MIXED	VARCHAR2(3)		YES indicates part of the transaction committed and part rolled back
ADVICE	VARCHAR2(1)		C for commit, R for rollback, else NULL
TRAN_COMMENT	VARCHAR2(255)		Text for commit work comment text

Column	Datatype	NULL	Description
FAIL_TIME	DATE	NOT NULL	Value of SYSDATE when the row was inserted (transaction or system recovery)
FORCE_TIME	DATE		Time of manual force decision (null if not forced locally)
RETRY_TIME	DATE	NOT NULL	Time automatic recovery (RECO) last tried to recover the transaction
OS_USER	VARCHAR2(64)		Operating system-specific name for the end-user
OS_TERMINAL	VARCHAR2(255)		Operating system-specific name for the end-user terminal
HOST	VARCHAR2(128)		Name of the host system for the end-user
DB_USER	VARCHAR2(128)		Oracle user name of the end-user at the topmost database
COMMIT#	VARCHAR2(16)		Global commit number for committed transactions

5.3 DBA_ACCHK_EVENTS

DBA_ACCHK_EVENTS displays information about events that occurred during an Application Continuity Protection Check (ACCHK) workload run.

Each row in this view represents one trace record for an event. You can use this view in conjunction with the DBA_ACCHK_STATISTICS view. Join the SESSION_ID and SERIAL# columns in this view with the SESSION_ID and SERIAL# columns in DBA_ACCHK_STATISTICS to view Application Continuity protection statistics for a particular session.

The ACCHK_READ role allows users with no administrative privileges to query this view.

Column	Datatype	NULL	Description
INST_ID	NUMBER		Identifier for the instance in which the trace record was generated
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
TIMESTAMP	TIMESTAMP(3) WITH TIME ZONE		Time at which the event occurred
SESSION_ID	NUMBER		ID of the session that generated the trace record
SERIAL#	NUMBER		Serial number of the session that generated the trace record
SERVICE_NAME	VARCHAR2(64)		Service name of the session that generated the trace record

Column	Datatype	NULL	Description
PROGRAM	VARCHAR2(84)		Name of the operating system program that generated the trace record
MODULE	VARCHAR2(64)		Name of the module that generated the trace record
ACTION	VARCHAR2(64)		Name of the action that generated the trace record
SQL_ID	VARCHAR2(13)		SQL identifier of the SQL statement that generated the trace record
CALL_NAME	VARCHAR2(20)		Name of the user call that generated the trace record
EVENT_TYPE	VARCHAR2(16)		Event type. Possible values: • DISABLED - The event caused capture or replay to be disabled. Refer to the ERROR_CODE column for more information. • NEVER ENABLED - Neither Application Continuity nor Transparent Application Continuity was enabled for the session when the event occurred. • NOT ENABLING - The event describes why the database could not reenable protection after protection was disabled. Refer to the ERROR_CODE column for more information. • REPLAY FAILED - The event describes why the session did not fail over. This event only occurs if Application Continuity could not fail over. Refer to the ERROR_CODE column for more information.
ERROR_CODE	NUMBER		If an error occurred, this column displays the error code: ORA-*number*. Otherwise, the value of this column is 0.

> **See Also:**
>
> "DBA_ACCHK_STATISTICS"

5.4 DBA_ACCHK_EVENTS_SUMMARY

DBA_ACCHK_EVENTS_SUMMARY displays summary information about events that occurred during an Application Continuity Protection Check (ACCHK) workload run.

This view describes the number of times a particular type of event occurred in a session. You can use this view in conjunction with the DBA_ACCHK_STATISTICS_SUMMARY view. Join the INST_ID and CON_ID columns in this view with the INST_ID and CON_ID columns in DBA_ACCHK_STATISTICS_SUMMARY to view Application Continuity protection statistics for a particular instance.

The ACCHK_READ role allows users with no administrative privileges to query this view.

Column	Datatype	NULL	Description
INST_ID	NUMBER		Identifier for the instance
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
SERVICE_NAME	VARCHAR2(64)		Service name of the session
FAILOVER_TYPE	VARCHAR2(16)		Indicates the FAILOVER_TYPE service setting for the session. Possible values: • AUTO - Transparent Application Continuity (TAC) was enabled for the session • TRANSACTION - Application Continuity (AC) was enabled for the session • NONE - Failover was disabled for the session
FAILOVER_RESTORE	VARCHAR2(16)		Indicates the FAILOVER_RESTORE service setting for the session. Possible values: • AUTO - Transparent Application Continuity • LEVEL1 - Application Continuity • NONE - Session state was not restored at failover
RESET_STATE	VARCHAR2(16)		Indicates the RESET_STATE service setting for the session. Possible values: • LEVEL1 - The session state was cleaned at the end of a request • NONE - The session state was not cleaned at the end of a request
PROGRAM	VARCHAR2(84)		Name of the operating system program that generated the trace record
MODULE	VARCHAR2(64)		Name of the module that generated the trace record
ACTION	VARCHAR2(64)		Name of the action that generated the trace record
SQL_ID	VARCHAR2(13)		SQL identifier of the SQL statement that generated the trace record
CALL_NAME	VARCHAR2(20)		Name of the user call that generated the trace record

Column	Datatype	NULL	Description
EVENT_TYPE	VARCHAR2(16)		Event type. Possible values: • DISABLED - The event caused capture or replay to be disabled. Refer to the ERROR_CODE column for more information. • NEVER ENABLED - Neither Application Continuity nor Transparent Application Continuity was enabled for the session when the event occurred. • NOT ENABLING - The event describes why the database could not reenable protection after protection was disabled. Refer to the ERROR_CODE column for more information. • REPLAY FAILED - The event describes why the session did not fail over. This event only occurs if Application Continuity could not fail over. Refer to the ERROR_CODE column for more information.
ERROR_CODE	NUMBER		If an error occurred, this column displays the error code: ORA-*number*. Otherwise, the value of this column is 0.
FREQUENCY	NUMBER		Number of times the event occurred during the workload run

5.5 DBA_ACCHK_STATISTICS

DBA_ACCHK_STATISTICS displays Application Continuity protection statistics for each session that executed during an Application Continuity Protection Check (ACCHK) workload run.

ACCHK should be used on a running workload. Sessions that are terminated are not included in this view.

The ACCHK_READ role allows users with no administrative privileges to query this view.

Column	Datatype	NULL	Description
INST_ID	NUMBER		Identifier for the instance for the session
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
TIMESTAMP	TIMESTAMP(3) WITH TIME ZONE		Time at which the session was terminated and the statistics were reported
SESSION_ID	NUMBER		ID of the session
SERIAL#	NUMBER		Serial number of the session

Column	Datatype	NULL	Description
STAT_TYPE	VARCHAR2(32)		Type of statistic The value of this column is always SESSION_STATISTICS.
SERVICE_NAME	VARCHAR2(64)		Service name of the session
FAILOVER_TYPE	VARCHAR2(16)		Indicates the FAILOVER_TYPE service setting for the session. Possible values: • AUTO - Transparent Application Continuity (TAC) was enabled for the session • TRANSACTION - Application Continuity (AC) was enabled for the session • NONE - Failover was disabled for the session
FAILOVER_RESTORE	VARCHAR2(16)		Indicates the FAILOVER_RESTORE service setting for the session. Possible values: • AUTO - Transparent Application Continuity • LEVEL1 - Application Continuity • NONE - Session state was not restored at failover
RESET_STATE	VARCHAR2(16)		Indicates the RESET_STATE service setting for the session. Possible values: • LEVEL1 - The session state was cleaned at the end of a request • NONE - The session state was not cleaned at the end of a request
PROGRAM	VARCHAR2(84)		Name of the operating system program
BEGIN_REQUESTS	NUMBER		Number of begin requests received for the session
END_REQUESTS	NUMBER		Number of end requests received for the session
USER_CALLS_IN_REQUESTS	NUMBER		Number of user calls received from the application within requests (between begin request and end request)
PROTECTED_CALLS_IN_REQUESTS	NUMBER		Number of user calls protected by Application Continuity (between begin request and end request)
TIME_IN_REQUESTS	NUMBER		Time in microseconds spent in user calls within requests (between begin request and end request)
TIME_PROTECTED_IN_REQUESTS	NUMBER		Time in microseconds for user calls protected by Application Continuity within requests (between begin request and end request)

5.6 DBA_ACCHK_STATISTICS_SUMMARY

DBA_ACCHK_STATISTICS_SUMMARY displays a summary of Application Continuity protection statistics for each session that executed during an Application Continuity Protection Check (ACCHK) workload run.

ACCHK should be used on a running workload. Sessions that are terminated are not included in this view.

The ACCHK_READ role allows users with no administrative privileges to query this view.

Column	Datatype	NULL	Description
INST_ID	NUMBER		Identifier for the instance for the session
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
SERVICE_NAME	VARCHAR2(64)		Service name of the session
FAILOVER_TYPE	VARCHAR2(16)		Indicates the FAILOVER_TYPE service setting for the session. Possible values: • AUTO - Transparent Application Continuity (TAC) was enabled for the session • TRANSACTION - Application Continuity (AC) was enabled for the session • NONE - Failover was disabled for the session
FAILOVER_RESTORE	VARCHAR2(16)		Indicates the FAILOVER_RESTORE service setting for the session. Possible values: • AUTO - Transparent Application Continuity • LEVEL1 - Application Continuity • NONE - Session state is not restored at failover
RESET_STATE	VARCHAR2(16)		Indicates the RESET_STATE service setting for the session. Possible values: • LEVEL1 - The session state was cleaned at the end of a request • NONE - The session state was not cleaned at the end of a request
TOTAL_REQUESTS	NUMBER		Number of requests received for this session
PROTECTED_CALLS_PERCENT	NUMBER		Percentage of user calls within requests protected by Application Continuity for failover
PROTECTED_TIME_PERCENT	NUMBER		Percentage of time spent within requests protected by Application Continuity for failover
AVG_USER_CALLS_IN_REQUESTS	NUMBER		Average number of user calls received from the application within requests (between begin request and end request)
AVG_PROTECTED_CALLS_IN_REQUESTS	NUMBER		Average number of user calls protected by Application Continuity within requests (between begin request and end request)
AVG_TIME_IN_REQUESTS	NUMBER		Average time in microseconds spent in user calls within requests (between begin request and end request)
AVG_TIME_PROTECTED_IN_REQUESTS	NUMBER		Average time in microseconds for user calls protected by Application Continuity within requests (between begin request and end request)

5.7 DBA_ACL_NAME_MAP

DBA_ACL_NAME_MAP maps new names of the access control lists for PL/SQL network utility packages from old XDB names.

Column	Datatype	NULL	Description
XDB_NAME	VARCHAR2(4000)	NOT NULL	The old XDB name of the access control list
ACL	VARCHAR2(128)		The new name of the access control list
ACL_OWNER	VARCHAR2(128)		The owner of the access control list

5.8 DBA_ACTIVITY_CONFIG

DBA_ACTIVITY_CONFIG describes the configuration parameters that control the Object Activity Tracking System (OATS).

Column	Datatype	NULL	Description
CON_DBNAME	VARCHAR2(128)	NOT NULL	Name of the container to which the data pertains
PARAMETER_NAME	VARCHAR2(128)	NOT NULL	Name of the configuration parameter
PARAMETER_VALUE	VARCHAR2(4000)		Value of the configuration parameter
LAST_UPDATED_TIME	TIMESTAMP(3)		If the value of the configuration parameter was last updated by a user, then this column displays the time at which the parameter was updated. Otherwise, this column is null.
LAST_UPDATED_USER	VARCHAR2(128)		If the value of the configuration parameter was last updated by a user, then this column displays the name of the user who performed the update. Otherwise, this column is null.

5.9 DBA_ACTIVITY_MVIEW

DBA_ACTIVITY_MVIEW describes materialized view activity snapshots that were recently taken by the Object Activity Tracking System (OATS).

Each row in this view represents one recently completed activity snapshot and describes the materialized view activity that occurred during the snapshot interval.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Activity snapshot identifier
CON_DBNAME	VARCHAR2(128)	NOT NULL	Name of the container to which the data pertains
INSTANCE_NUMBER	NUMBER	NOT NULL	Identifier for the instance in which the activity snapshot was taken
BEGIN_TIME	TIMESTAMP(3)	NOT NULL	Begin time for the activity snapshot interval
END_TIME	TIMESTAMP(3)	NOT NULL	End time for the activity snapshot interval
MVIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view for which the activity snapshot was taken

Column	Datatype	NULL	Description
MVIEW_OWNER	VARCHAR2(128)	NOT NULL	Owner of materialized view for which the activity snapshot was taken
USER_CLASS	VARCHAR2(7)		Indicates whether the activity was performed by the RDBMS (SYS) or by a user (NON-SYS)
COMPILES	NUMBER		Number of times the materialized view was compiled This number includes: • Explicit compiles performed with the SQL statement ALTER MATERIALIZED VIEW ... COMPILE • Automatic compiles that occurred because the structure of an underlying base table changed
REWRITES_TEXTMATCH	NUMBER		Number of query rewrites that used the text match rewrite method
REWRITES_GENERAL	NUMBER		Number of query rewrites that used general rewrite methods
REWRITES_PARTIAL	NUMBER		Number of query rewrites that occurred when the view was partially stale This number includes: • UNION ALL operations involving rewritten queries that had one branch with the materialized view and the other branch with its underlying base tables (partial rewrites) • Single query block rewrites of the materialized view that involved a join back to its underlying base table
REWRITES_DELTA	NUMBER		Number of query rewrites that used stale data in the materialized view plus the delta information stored in the materialized view logs
REWRITES_PCT	NUMBER		Number of partition change tracking (PCT) rewrites
REWRITES_HINTED	NUMBER		Number of query rewrites that occurred because the materialized view was eligible for query rewrite and the SELECT statement contained the REWRITE hint with the name of the materialized view specified in the hint
NOREWRITES_HINTED	NUMBER		Reserved for future use
NOREWRITES_STALE	NUMBER		Number of query executions that did not use query rewrite because the materialized view was eligible for query rewrite, but stale
REFRESHES_ON_DEMAND	NUMBER		Number of ON DEMAND refreshes This type of refresh is performed on materialized views that use the ON DEMAND refresh mode, which instructs the database to refresh the materialized view only when a manual refresh is launched by one of the three DBMS_MVIEW refresh procedures.

Column	Datatype	NULL	Description
REFRESHES_ON_COMMIT	NUMBER		Number of ON COMMIT refreshes This type of refresh is performed on materialized views that use the ON COMMIT refresh mode, which instructs the database to refresh the materialized view whenever the database commits a transaction that operates on a master table of the materialized view.
REFRESHES_ON_STATEMENT	NUMBER		Number of ON STATEMENT refreshes This type of refresh is performed on materialized views that use the ON STATEMENT refresh mode, which instructs the database to perform an automatic refresh of the materialized view every time a DML operation is performed on any of the view's base tables.
REFRESHES_SCHEDULED	NUMBER		Number of scheduled refreshes
REFRESHES_AUTOMATIC	NUMBER		Number of automatic refreshes
REFRESHES_FAST	NUMBER		Number of incremental refreshes
REFRESHES_COMPLETE	NUMBER		Number of full refreshes
REFRESHES_PCT	NUMBER		Number of partition change tracking (PCT) refreshes

Note:

The counts in this view are approximate in order to keep system overhead low. Also, there are database activities, such as statistics collection, query compilation, and query optimization, that may cause the counts to be different than expected or to vary slightly across successive queries.

See Also:

"V$ACTIVITY_MVIEW" to view in-progress materialized view activity snapshots

5.10 DBA_ACTIVITY_SNAPSHOT_META

DBA_ACTIVITY_SNAPSHOT_META displays information about activity snapshots taken by the Object Activity Tracking System (OATS).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Activity snapshot identifier
CON_DBNAME	VARCHAR2(128)	NOT NULL	Name of the container to which the data pertains
INSTANCE_NUMBER	NUMBER	NOT NULL	Identifier for the instance in which the activity snapshot was taken

Column	Datatype	NULL	Description
BEGIN_TIME	TIMESTAMP(3)	NOT NULL	Begin time for the activity snapshot interval
END_TIME	TIMESTAMP(3)	NOT NULL	End time for the activity snapshot interval
FLUSH_ELAPSED_TIME	INTERVAL DAY(2) TO SECOND(3)		Amount of time spent creating the activity snapshot
FLUSH_IS_MANUAL	VARCHAR2(3)		Indicates whether the activity snapshot was created manually (YES) or not (NO)

5.11 DBA_ACTIVITY_TABLE

DBA_ACTIVITY_TABLE describes table activity snapshots that were recently taken by the Object Activity Tracking System (OATS).

Each row in this view represents one recently completed activity snapshot and describes the table activity that occurred during the snapshot interval.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Activity snapshot identifier
CON_DBNAME	VARCHAR2(128)	NOT NULL	Name of the container to which the data pertains
INSTANCE_NUMBER	NUMBER	NOT NULL	Identifier for the instance in which the activity snapshot was taken
BEGIN_TIME	TIMESTAMP(3)	NOT NULL	Begin time for the activity snapshot interval
END_TIME	TIMESTAMP(3)	NOT NULL	End time for the activity snapshot interval
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table for which the activity snapshot was taken
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table for which the activity snapshot was taken
USER_CLASS	VARCHAR2(7)		Reserved for future use
SCANS	NUMBER		Number of table scans
LOADS	NUMBER		Number of table loads
LOAD_ROWS	NUMBER		Number of rows that were loaded into the table
INSERT_ROWS	NUMBER		Number of rows that were inserted into the table
DELETE_ROWS	NUMBER		Number of rows that were deleted from the table
UPDATE_ROWS	NUMBER		Number of table rows that were updated
TRUNCATES	NUMBER		Number of table truncations
TRUNCATED_ROWS	NUMBER		Number of table rows that were deleted due to table truncations
PARTITION_TRUNCATES	NUMBER		Number of table partition or subpartition truncations
PARTITION_TRUNCATED_ROWS	NUMBER		Number of table rows that were deleted due to table partition or subpartition truncations
PARTITION_CREATES	NUMBER		Number of table partitions or subpartitions that were created
PARTITION_DROPS	NUMBER		Number of table partition or subpartition drops

Column	Datatype	NULL	Description
PARTITION_DROPS_ROWS	NUMBER		Number of table rows that were dropped due to table partition or subpartition drops
PARTITION_MOVES	NUMBER		Number of table partition or subpartition moves
PARTITION_MOVES_ROWS	NUMBER		Number of table rows that were moved due to table partition or subpartition moves
PARTITION_SPLITS	NUMBER		Number of table partition or subpartition splits
PARTITION_SPLITS_ROWS	NUMBER		Number of table rows that were split due to table partition or subpartition splits
PARTITION_MERGES	NUMBER		Number of table partition or subpartition merges
PARTITION_MERGES_ROWS	NUMBER		Number of table rows that were merged due to table partition or subpartition merges
PARTITION_COALESCES	NUMBER		Number of table partition or subpartition coalesces
PARTITION_COALESCE_ROWS	NUMBER		Number of table rows that were redistributed due to table partition or subpartition coalesces
PARTITION_EXCHANGES	NUMBER		Number of table partition or subpartition exchanges
PARTITION_EXCHANGES_ROWS	NUMBER		Number of table rows that were exchanged due to table partition or subpartition exchanges

Note:

The counts in this view are approximate in order to keep system overhead low. Also, there are database activities, such as statistics collection, query compilation, and query optimization, that may cause the counts to be different than expected or to vary slightly across successive queries.

Note:

This view does not contain information related to temporary tables or external tables.

See Also:

"V$ACTIVITY_TABLE" to view in-progress table activity snapshots

5.12 DBA_ADDM_FDG_BREAKDOWN

DBA_ADDM_FDG_BREAKDOWN describes the contribution for each finding from the different instances.

There is one row for each finding and for each instance participating in the analysis. Rows are omitted if the impact from that instance is not sufficient to register a finding in a local ADDM analysis.

Related View

USER_ADDM_FDG_BREAKDOWN describes the contribution for each finding from the different instances owned by the current user.

Column	Datatype	NULL	Description
TASK_ID	NUMBER	NOT NULL	Identifies the task to which this finding belongs (see DBA_ADVISOR_TASKS)
FINDING_ID	NUMBER	NOT NULL	Identifies the finding (see DBA_ADVISOR_FINDINGS)
INSTANCE_NUMBER	NUMBER	NOT NULL	The number of the instance contributing to the finding
DATABASE_TIME	NUMBER		The database time, in microseconds, accumulated by this instance during the analysis period
ACTIVE_SESSIONS	NUMBER		The average number of active sessions of the finding in this instance
PERC_ACTIVE_SESSIONS	NUMBER		The percentage of contribution from this instance compared to the total impact of the finding

See Also:

"USER_ADDM_FDG_BREAKDOWN"

5.13 DBA_ADDM_FINDINGS

DBA_ADDM_FINDINGS displays the ADDM findings discovered by all advisors in the database.

Each row for ADDM tasks in the related DBA_ADVISOR_FINDINGS view has a corresponding row in this view.

Related View

USER_ADDM_FINDINGS displays the ADDM findings discovered by the advisors owned by the current user. Each row for ADDM tasks in the related USER_ADVISOR_FINDINGS view has a corresponding row in this view. The USER_ADDM_FINDINGS view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task

Column	Datatype	NULL	Description
TASK_ID	NUMBER	NOT NULL	Identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task
EXECUTION_NAME	VARCHAR2(128)		The name of the task execution with which this entry (row) is associated
FINDING_ID	NUMBER	NOT NULL	Identifier of the finding
FINDING_NAME	VARCHAR2(4000)		Name of the finding
TYPE	VARCHAR2(11)		Type of the finding: PROBLEM SYMPTOM ERROR INFORMATION
TYPE_ID	NUMBER	NOT NULL	Numeric ID for the value in column TYPE
PARENT	NUMBER	NOT NULL	Identifier of the parent finding
OBJECT_ID	NUMBER		Identifier of the associated object, if any
IMPACT_TYPE	VARCHAR2(4000)		Impact of the finding on the system
IMPACT	NUMBER		Impact value
MESSAGE	VARCHAR2(4000)		Message describing the finding
MORE_INFO	VARCHAR2(4000)		Additional info associated with the finding
FILTERED	VARCHAR2(1)		A value of Y means that the row in the view was filtered out by a directive (or a combination of directives). A value of N means that the row was not filtered.
FLAGS	NUMBER		For internal use only by advisor framework clients
DATABASE_TIME	NUMBER		The database time, in microseconds, accumulated by this finding
ACTIVE_SESSIONS	NUMBER		The average number of active sessions for the finding
PERC_ACTIVE_SESS	NUMBER		The percentage of active sessions for this finding out of the total active sessions for the task
IS_AGGREGATE	CHAR(1)		A value of Y means that this finding is created for global/continental ADDM as an aggregate of local ADDM findings. Otherwise, the value is N.
METER_LEVEL	VARCHAR2(6)		Reserved for future use
QUERY_IS_APPROX	CHAR(1)		Indicates whether the ASH SQL associated with the finding is an approximate query (Y) or an exact query (N). To get the associated query, use the TASK_NAME and FINDING_ID columns from this view and call the PL/SQL function DBMS_ADDM.GET_ASH_QUERY(task_name, finding_id).

> **See Also:**
>
> - "USER_ADDM_FINDINGS"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_ADDM.GET_ASH_QUERY` procedure

5.14 DBA_ADDM_INSTANCES

`DBA_ADDM_INSTANCES` displays instance-level information for ADDM tasks that finished executing.

For each instance that was supposed to be analyzed (whether it was or not) there is one row describing information about it.

Related View

`USER_ADDM_INSTANCES` displays instance-level information for ADDM tasks that finished executing in all instances owned by the current user.

Column	Datatype	NULL	Description
TASK_ID	NUMBER	NOT NULL	The ID of the main ADDM task
INSTANCE_NUMBER	NUMBER	NOT NULL	The number of the instance
INSTANCE_NAME	VARCHAR2(16)		The name of the instance
HOST_NAME	VARCHAR2(64)		The name of the system on which the instance was running
STATUS	VARCHAR2(10)		How information from this instance was used by the ADDM task. A value of ANALYZED means that the instance participated fully in the analysis. For the following remaining values, the instance was not used during task execution, for the stated reason: BOUNCED - the instance was shut down or started during the analysis period NO_SNAPS - there were either begin or end snapshots missing for the instance NO_STATS - there were key statistics missing for the instance NOT_FOUND - no mention of this instance could be found in AWR during the analysis period
DATABASE_TIME	NUMBER		The database time, in microseconds, accumulated by this instance during the analysis period
ACTIVE_SESSIONS	NUMBER		The average number of active sessions for the instance during the analysis period
PERC_ACTIVE_SESS	NUMBER		The percentage of active sessions for this instance, out of the total active sessions for the task
METER_LEVEL	VARCHAR2(6)		Reserved for future use

Column	Datatype	NULL	Description
LOCAL_TASK_ID	NUMBER		The ID of a local ADDM task that contained an analysis of the instance for the same analysis period as that of the main task. If the main task is a local ADDM, then this value is the same as the TASK_ID value.

> **See Also:**
>
> "USER_ADDM_INSTANCES"

5.15 DBA_ADDM_PENDING_AUTOTASKS

DBA_ADDM_PENDING_AUTOTASKS displays information about all automatic ADDM tasks in the database that are currently being executed.

This view is accessible at both the CDB and PDB level and contains information about the ADDM tasks that were executed at each level. Oracle Autonomous Database and Oracle Cloud users can see information about the tasks that were executed in their PDB, obtain more diagnostic information on failed tasks, and manually re-execute those tasks. Once a task is executed successfully, its entry is removed from this view. Failed tasks automatically age out and are removed when the corresponding AWR snapshots age out.

Column	Datatype	NULL	Description
DBID	NUMBER		Database ID for the ADDM task
INSTANCE_NUMBER	NUMBER		Instance number for the ADDM task
END_SNAP_ID	NUMBER		End snapshot for the ADDM task
STATUS	VARCHAR2(20)		Status of the task execution
REGISTERED_TIME	TIMESTAMP(6)		Time at which the ADDM task was first registered for automatic execution
ERROR_MESSAGE	VARCHAR2(200)		If the execution of the ADDM task failed, the error message
CREATION_ATTEMPTS	NUMBER		The number of attempts to automatically start the ADDM task.
LAST_CREATION_ATTEMPT	TIMESTAMP(6)		The time of the last attempt to automatically start the ADDM task.
EXECUTION_ATTEMPTS	NUMBER		Number of times the ADDM task has attempted to be run
LAST_EXECUTION_ATTEMPT	TIMESTAMP(6)		Time of the most recent attempt to execute the ADDM task

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

5.16 DBA_ADDM_SCHEDULED_AUTOTASKS

DBA_ADDM_SCHEDULED_AUTOTASKS displays information about all automatic ADDM tasks in the database that are currently scheduled to be executed by the Manageability Monitor Process (MMON).

This view is accessible at both the CDB and PDB level and contains information about the ADDM tasks that are scheduled to be executed at each level. Oracle Autonomous Database and Oracle Cloud users can see information about the tasks that are scheduled for their PDB. Once a task starts executing, its entry is removed from this view.

Column	Datatype	NULL	Description
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the ADDM task
DBID	NUMBER	NOT NULL	Database ID for the ADDM task
END_SNAP_ID	NUMBER	NOT NULL	End snapshot for the ADDM task
TASK_TYPE	VARCHAR2(14)		Type of ADDM task: • INSTANCE LEVEL • SYSTEM LEVEL
SCHEDULED_SINCE_UTC	TIMESTAMP(6) WITH TIME ZONE		Time at which the ADDM task was scheduled to be executed, in UTC (Coordinated Universal Time) time zone

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

5.17 DBA_ADDM_SYSTEM_DIRECTIVES

DBA_ADDM_SYSTEM_DIRECTIVES displays information about global instances for ADDM system directives.

Column	Datatype	NULL	Description
INSTANCE_ID	NUMBER	NOT NULL	Unique ID for the directive instance. The directive management engine automatically generates ID numbers.
INSTANCE_NAME	VARCHAR2(128)	NOT NULL	User-assigned name for the directive instance.
DIRECTIVE_NAME	VARCHAR2(128)	NOT NULL	Any value that further classifies this directive within a domain. The domain and the name form a unique key for the directive.

Column	Datatype	NULL	Description
DESCRIPTION	VARCHAR2(4000)		Description of the ADDM system directive, shown in the language used by the current session

5.18 DBA_ADDM_TASK_DIRECTIVES

DBA_ADDM_TASK_DIRECTIVES displays information about all ADDM task directives in the database.

Related View

USER_ADDM_TASK_DIRECTIVES displays information about ADDM task directives owned by the current user.

Column	Datatype	NULL	Description
TASK_ID	NUMBER		An ADDM advisor task identifier to which the directive instance is associated
TASK_NAME	VARCHAR2(128)		An ADDM advisor task to which the directive instance is associated
USERNAME	VARCHAR2(128)	NOT NULL	Database user who owns the ADDM task instance
SEQ_ID	NUMBER	NOT NULL	Unique ID for the directive instance. The directive management engine automatically generates ID numbers.
INSTANCE_NAME	VARCHAR2(128)	NOT NULL	A user-assigned name for the ADDM task directive instance
DIRECTIVE_NAME	VARCHAR2(128)	NOT NULL	Any value that further classifies this directive within a domain. The domain and the name form a unique key for the directive.
DESCRIPTION	VARCHAR2(4000)		Description of the ADDM task directive, shown in the language used by the current session

See Also:

"USER_ADDM_TASK_DIRECTIVES"

5.19 DBA_ADDM_TASKS

DBA_ADDM_TASKS displays information about all ADDM tasks in the database.

The view contains one row for each row in the related DBA_ADVISOR_TASKS view that has ADVISOR_NAME=ADDM and STATUS=COMPLETED.

Related View

USER_ADDM_TASKS displays information about the ADDM tasks owned by the current user. The view contains one row for each row in the related USER_ADVISOR_TASKS view

that has ADVISOR_NAME=ADDM and STATUS=COMPLETED. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task
DESCRIPTION	VARCHAR2(256)		User-supplied description of the task
ADVISOR_NAME	VARCHAR2(128)		Advisor associated with the task
CREATED	DATE	NOT NULL	Creation date of the task
LAST_MODIFIED	DATE	NOT NULL	Date on which the task was last modified
PARENT_TASK_ID	NUMBER		Identifier of the parent task (if the task was created because of the recommendation of another task)
PARENT_RXEC_ID	NUMBER		Identifier of the recommendation within the parent task that resulted in the creation of the task
LAST_EXECUTION	VARCHAR2(128)		Name of the current or last task execution
EXECUTION_TYPE	VARCHAR2(128)		Type of the last execution. This information is optional for single-execution tasks.
EXECUTION_TYPE#	NUMBER		Reserved for internal use
EXECUTION_DESCRIPTION	VARCHAR2(256)		Optional description of the last execution
EXECUTION_START	DATE		Execution start date and time of the task
EXECUTION_END	DATE		Execution end date and time of the task
STATUS	VARCHAR2(11)		Current operational status of the task: • INITIAL - Initial state of the task; no recommendations are present • EXECUTING - Task is currently running • INTERRUPTED - Task analysis was interrupted by the user. Recommendation data, if present, can be viewed and reported at this time. • COMPLETED - Task successfully completed the analysis operation. Recommendation data can be viewed and reported. • ERROR - An error occurred during the analysis operation. Recommendations, if present, can be viewed and reported at this time.
STATUS_MESSAGE	VARCHAR2(4000)		Informational message provided by the advisor, regarding the status
PCT_COMPLETION_TIME	NUMBER		Percent completion, in terms of time, of the task when it is executing
PROGRESS_METRIC	NUMBER		Metric that measures the progress of the task in terms of quality. Each advisor may have its own metric.
METRIC_UNITS	VARCHAR2(64)		Unit of the metric used to measure progress
ACTIVITY_COUNTER	NUMBER		Counter that is updated frequently by the advisor, denoting that useful work is being performed
RECOMMENDATION_COUNT	NUMBER		Number of recommendations produced
ERROR_MESSAGE	VARCHAR2(4000)		Informational message or an error message indicating the current operation or condition

Column	Datatype	NULL	Description
SOURCE	VARCHAR2(128)		Optional name that identifies the creator of the task
HOW_CREATED	VARCHAR2(30)		Optional task or template on which the object was based
READ_ONLY	VARCHAR2(5)		Indicates whether the task is read-only (TRUE) or not (FALSE)
SYSTEM_TASK	VARCHAR2(5)		Indicates whether the task is a system task (TRUE) or not (FALSE). The automatic SQL tuning task, SYS_AUTO_SQL_TUNING_TASK, is one example of a system task.
ADVISOR_ID	NUMBER	NOT NULL	Unique identifier for the advisor
STATUS#	NUMBER		Reserved for internal use
DBID	NUMBER		The database ID that the task was using
DBNAME	VARCHAR2(9)		The name of the database that the task was analyzing
DBVERSION	VARCHAR2(17)		The version of the database that the task was analyzing
ANALYSIS_VERSION	VARCHAR2(17)		The version of the database that executed the task
BEGIN_SNAP_ID	NUMBER		The snapshot ID that starts the analysis period
BEGIN_TIME	TIMESTAMP(3)		The SYSDATE at the time the BEGIN_SNAP_ID was taken
END_SNAP_ID	NUMBER		The snapshot ID that ends the analysis period
END_TIME	TIMESTAMP(3)		The SYSDATE at the time the END_SNAP_ID was taken
REQUESTED_ANALYSIS	VARCHAR2(8)		The type of ADDM analysis that was requested before task execution, as follows: DATABASE - global ADDM INSTANCE - local ADDM PARTIAL - continental ADDM
ACTUAL_ANALYSIS	VARCHAR2(8)		The type of ADDM analysis that was actually performed when the task was executed (either DATABASE, INSTANCE, or PARTIAL)
DATABASE_TIME	NUMBER		The total database time accumulated in the analysis period (and analyzed instances) in microseconds
ACTIVE_SESSIONS	NUMBER		The average active sessions during the analysis period (and analyzed sessions)
METER_LEVEL	VARCHAR2(6)		Reserved for future use
FDG_COUNT	NUMBER		The number of findings for the ADDM task, which will appear in the list of findings in a default ADDM report
DB_TYPE_DETECTED[1]	VARCHAR2(10)		Indicates the open mode of the database that the task was analyzing, as detected by ADDM. Possible values: • READ-ONLY • READ-WRITE

Column	Datatype	NULL	Description
DB_TYPE_ANALYZED[1]	VARCHAR2(10)		Indicates the assumed open mode of the database that the task was analyzing. If the value of this column is different from the value of the DB_TYPE_DETECTED column, then ADDM ignored the detected open mode of the database and analyzed the task as if it occurred on a database with the assumed open mode. Possible values: • READ-ONLY • READ-WRITE
CDB_TYPE_DETECTED[1]	VARCHAR2(25)		Indicates the type of database that the task was analyzing, as detected by ADDM. Possible values: • NON-CDB - A non-CDB • CDB ROOT - The root container in a CDB • PDB - A pluggable database (PDB) in a CDB • AUTONOMOUS DATA WAREHOUSE - A PDB that hosts an Oracle Autonomous Data Warehouse Cloud service • AUTONOMOUS OLTP - A PDB that hosts an Oracle Autonomous Transaction Processing service
CDB_TYPE_ANALYZED[1]	VARCHAR2(25)		Indicates the assumed type of database that the task was analyzing. If the value of this column is different from the value of the CDB_TYPE_DETECTED column, then ADDM ignored the detected type of database and analyzed the task as if it occurred on the assumed type of database. Possible values: • NON-CDB - A non-CDB • CDB ROOT - The root container in a CDB • PDB - A pluggable database (PDB) in a CDB • AUTONOMOUS DATA WAREHOUSE - A PDB that hosts an Oracle Autonomous Data Warehouse Cloud service • AUTONOMOUS OLTP - A PDB that hosts an Oracle Autonomous Transaction Processing service

1 This column is available starting with Oracle Database release 19c, version 19.1. If the task was analyzing a database at a release earlier than Oracle Database 19c, and that database was subsequently upgraded to Oracle Database 19c, then the value of this column is NULL.

See Also:

"USER_ADDM_TASKS"

5.20 DBA_ADVISOR_ACTIONS

DBA_ADVISOR_ACTIONS displays information about the actions associated with all recommendations in the database.

Each action is specified by the COMMAND and ATTR1 through ATTR6 columns. Each command defines how the attribute columns will be used.

Related View

USER_ADVISOR_ACTIONS displays information about the actions associated with the recommendations owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task
EXECUTION_NAME	VARCHAR2(128)		The name of the task execution with which this entry (row) is associated
REC_ID	NUMBER	NOT NULL	Recommendation associated with the action
ACTION_ID	NUMBER	NOT NULL	Unique identifier for the action
OBJECT_ID	NUMBER		Object associated with the action
COMMAND	VARCHAR2(64)		Command to be executed **See Also:** DBA_ADVISOR_COMMANDS for a list of commands
COMMAND_ID	NUMBER	NOT NULL	ID of the command to be executed **See Also:** DBA_ADVISOR_COMMANDS for a list of commands
FLAGS	NUMBER		Advisor-specific flags
ATTR1	VARCHAR2(4000)		Parameters defining the command
ATTR2	VARCHAR2(4000)		Parameters defining the command
ATTR3	VARCHAR2(4000)		Parameters defining the command
ATTR4	VARCHAR2(4000)		Parameters defining the command
ATTR5	CLOB		Parameters defining the command; to be used if the text is significantly large (for example, a SQL statement defining a materialized view)
ATTR6	CLOB		Parameters defining the command; to be used if the text is significantly large (for example, a SQL statement defining a materialized view)
NUM_ATTR1	NUMBER		General numeric attribute
NUM_ATTR2	NUMBER		General numeric attribute
NUM_ATTR3	NUMBER		General numeric attribute
NUM_ATTR4	NUMBER		General numeric attribute
NUM_ATTR5	NUMBER		General numeric attribute
MESSAGE	VARCHAR2(4000)		Message associated with the action

Column	Datatype	NULL	Description
FILTERED	VARCHAR2(1)		A value of Y means that the row in the view was filtered out by a directive (or a combination of directives). A value of N means that the row was not filtered.
RESULT_STATUS	VARCHAR2(25)		Result status. Possible values: • AUTOMATION PENDING • TIMED OUT • MISSING INFORMATION • COMPLETED WITH NO RESULTS • COMPLETED AND IMPLEMENTED • ENCOUNTERED ERROR • NOT AUTOMATED
RESULT_LAST_MODIFIED	TIMESTAMP(3)		Time at which result status was last modified
RESULT_MESSAGE	VARCHAR2(4000)		Result message text

See Also:

"USER_ADVISOR_ACTIONS"

5.21 DBA_ADVISOR_COMMANDS

DBA_ADVISOR_COMMANDS displays information about the commands used by all advisors in the database for specifying recommendation actions.

In addition to the set of commands in the COMMAND column of V$SESSION, the following additional commands are defined:

- RUN ADVISOR
- CHECK EXECUTION PLAN
- ALTER PARAMETER
- ENABLE TRACE

Column	Datatype	NULL	Description
COMMAND_ID	NUMBER		Identifier of the command
COMMAND_NAME	VARCHAR2(64)		Name of the command

5.22 DBA_ADVISOR_DEF_PARAMETERS

DBA_ADVISOR_DEF_PARAMETERS displays all default task parameters and their current values in the database.

When a task or object is created, the parameters and their values are copied into the private parameter table.

Column	Datatype	NULL	Description
ADVISOR_NAME	VARCHAR2(128)	NOT NULL	Name of the advisor that supports the parameter
PARAMETER_NAME	VARCHAR2(128)	NOT NULL	Name of the parameter
PARAMETER_VALUE	VARCHAR2(4000)	NOT NULL	Value of the parameter. Numeric parameter values are converted to a string equivalent. Possible keywords as values: • ALL • UNLIMITED • UNUSED
PARAMETER_TYPE	VARCHAR2(10)		Datatype of the parameter: • NUMBER - Numeric value • STRING - String value. If the string contains special characters, then it will be enclosed in single quotes. • STRINGLIST - Comma-separated list of string elements. If a string element contains a comma or other special characters, then the element will be enclosed in single quotes. • TABLE - Single table reference. A reference will contain a schema name, followed by an optional table name. If the table name is omitted or is the character %, then the table name is interpreted as a wildcard. SQL quoted identifiers are supported. • TABLELIST - List of one or more comma-separated table references. A reference will contain schema name, followed by an optional table name. If the table name is omitted or is the character %, then the table name is interpreted as a wildcard. SQL quoted identifiers are supported.
IS_DEFAULT	VARCHAR2(1)		Indicates whether the parameter value is set to the advisor's default value (Y) or not (N)
IS_OUTPUT	VARCHAR2(1)		Indicates whether the task execution process sets the parameter value (Y) or not (N)
IS_MODIFIABLE_ANYTIME	VARCHAR2(1)		Indicates whether the parameter value can be modified when the task is not in its initial state (Y) or not (N)
IS_SYSTEM_TASK_ONLY	VARCHAR2(1)		Indicates whether the task is a system task (Y) or not (N)
DESCRIPTION	VARCHAR2(4000)		Optional description of the parameter
EXECUTION_TYPE	VARCHAR2(128)		Type of the last execution. This information is optional for single-execution tasks.

5.23 DBA_ADVISOR_DEFINITIONS

DBA_ADVISOR_DEFINITIONS displays the properties of all advisors in the database.

The view contains one row for each task, representing the current state of the task as well as execution-specific data such as progress monitoring and completion status.

Column	Datatype	NULL	Description
ADVISOR_ID	NUMBER	NOT NULL	Unique identifier for the advisor
ADVISOR_NAME	VARCHAR2(128)	NOT NULL	Name of the advisor
PROPERTY	NUMBER	NOT NULL	Properties: • Bit 0: - Indicates whether the advisor runs in COMPREHENSIVE mode (1) or not (0) • Bit 1: - Indicates whether the advisor runs in LIMITED mode (1) or not (0) • Bit 2: - Indicates whether the advisor is resumable (1) or not (0) • Bit 3: - Indicates whether the advisor accepts user directives (1) or not (0)

5.24 DBA_ADVISOR_DIR_DEFINITIONS

DBA_ADVISOR_DIR_DEFINITIONS provides a definition of the base directive.

Column	Datatype	NULL	Description
ID	NUMBER	NOT NULL	Unique id for directive. The directive management engine automatically generates ID numbers. The identifier is unique among all directives regardless of the domain name and directive name.
ADVISOR_ID	NUMBER	NOT NULL	Identifier number of the owner advisor.
ADVISOR_NAME	VARCHAR2(128)	NOT NULL	The name of the advisor to which this directive belongs.
DIRECTIVE_NAME	VARCHAR2(128)	NOT NULL	Any value that further classifies this directive within a domain. The domain and the name form a unique key for the directive.
DOMAIN_NAME	VARCHAR2(128)	NOT NULL	Domain or namespace name.
DESCRIPTION	VARCHAR2(256)	NOT NULL	An optional description that documents the purpose of the directive.

Column	Datatype	NULL	Description
TYPE	NUMBER	NOT NULL	Further describes the use of the directive. Possible values are: 1. **Filter** - An Xpath filter 2. **Single Value** - Evaluation returns a single string value 3. **Multiple Values** - Evaluation returns one to many string values 4. **Conditional** - Evaluation returns a single value based on an input key, similar to a CASE or SWITCH statement
TYPE_NAME	VARCHAR2(15)		A decoded version of the TYPE column.
TASK_STATUS	VARCHAR2(9)		The status of the directive instances when a task is not in its initial state. Possible values are: • IMMUTABLE • MUTABLE
INSTANCES	VARCHAR2(8)		Indicates whether a directive will permit multiple instances. Possible values are: • SINGLE • MULTIPLE
METADATA	CLOB	NOT NULL	A DTD that is used to process the directive.

5.25 DBA_ADVISOR_DIR_INSTANCES

DBA_ADVISOR_DIR_INSTANCES provides information about all global instances for a directive.

Column	Datatype	NULL	Description
DIRECTIVE_ID	NUMBER	NOT NULL	Unique id for directive. The directive management engine automatically generates ID numbers.
INSTANCE_ID	NUMBER	NOT NULL	Unique id for the directive instance. The directive management engine automatically generates ID numbers.
INSTANCE_NAME	VARCHAR2(128)	NOT NULL	A user-assigned name for the directive instance.
DATA	CLOB	NOT NULL	An XML document that gives meaningful default values for all parts of the directive.

5.26 DBA_ADVISOR_DIR_TASK_INST

DBA_ADVISOR_DIR_TASK_INST provides information about all task directive instances.

Related View

USER_ADVISOR_DIR_TASK_INST provides information about all task directive instances owned by the current user.

Column	Datatype	NULL	Description
DIRECTIVE_ID	NUMBER	NOT NULL	Unique id for directive. The directive management engine automatically generates ID numbers.
SEQ_ID	NUMBER	NOT NULL	Unique id for the directive instance. The directive management engine automatically generates ID numbers.
INSTANCE_NAME	VARCHAR2(128)	NOT NULL	A user-assigned name for the directive instance.
USERNAME	VARCHAR2(128)	NOT NULL	Database user who owns the task instance.
TASK_ID	NUMBER		An advisor task identifier to which the directive instance is associated
TASK_NAME	VARCHAR2(128)		An advisor task to which the directive instance is associated.
DATA	CLOB	NOT NULL	An XML document that gives meaningful default values for all parts of the directive.

See Also:

"USER_ADVISOR_DIR_TASK_INST"

5.27 DBA_ADVISOR_EXEC_PARAMETERS

DBA_ADVISOR_EXEC_PARAMETERS displays the parameter values used for past executions of tasks.

It is more useful for advisors supporting multiple executions, such as SQL Performance Analyzer, where a parameter can have different values for different executions.

Related View

USER_ADVISOR_EXEC_PARAMETERS displays the parameter values used for past executions of tasks owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task
EXECUTION_NAME	VARCHAR2(128)	NOT NULL	Name of the task execution with which this entry (row) is associated
EXECUTION_TYPE	VARCHAR2(128)		Type of the last execution. This information is optional for single-execution tasks.
PARAMETER_NAME	VARCHAR2(128)	NOT NULL	Name of the parameter
PARAMETER_VALUE	VARCHAR2(4000)		Value of the parameter. Numeric parameter values are converted to a string equivalent.
PARAMETER_TYPE	VARCHAR2(10)		Datatype of the parameter (see DBA_ADVISOR_PARAMETERS)

Column	Datatype	NULL	Description
IS_DEFAULT	VARCHAR2(1)		Indicates whether the parameter value is set to the advisor's default value (Y) or not (N)
IS_OUTPUT	VARCHAR2(1)		Indicates whether the task execution process sets the parameter value (Y) or not (N)
IS_MODIFIABLE_ANYTIME	VARCHAR2(1)		Indicates whether the parameter value can be modified when the task is not in its initial state (Y) or not (N)
DESCRIPTION	VARCHAR2(4000)		Optional description of the parameter
PARAMETER_FLAGS	NUMBER	NOT NULL	Reserved for internal use
PARAMETER_TYPE#	NUMBER	NOT NULL	Reserved for internal use

See Also:

"USER_ADVISOR_EXEC_PARAMETERS"

5.28 DBA_ADVISOR_EXECUTION_TYPES

DBA_ADVISOR_EXECUTION_TYPES displays possible execution action for a given advisor.

Only advisors that support multiple executions of their tasks have entries in this view.

Column	Datatype	NULL	Description
ADVISOR_NAME	VARCHAR2(128)	NOT NULL	Name of the advisor
EXECUTION_TYPE	VARCHAR2(128)	NOT NULL	Execution type supported by the advisor
EXECUTION_DESCRIPTION	VARCHAR2(4000)		Optional description of the execution type

5.29 DBA_ADVISOR_EXECUTIONS

DBA_ADVISOR_EXECUTIONS displays metadata information for task executions.

For example, the SQL Performance Analyzer creates a minimum of three executions to perform a change impact analysis on a SQL workload. The first one collects performance data for the version of the workload before the change, the second one collects data for the version of the workload after the change, and the third one performs impact analysis. All of these executions belong to the same task and are grouped into this view. Similarly, the automatic SQL tuning task, SYS_AUTO_SQL_TUNING_TASK, creates a new execution for each tuning run.

Related View

USER_ADVISOR_EXECUTIONS displays metadata information for task executions owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task
EXECUTION_NAME	VARCHAR2(128)	NOT NULL	Name of the task execution with which this entry (row) is associated
EXECUTION_ID	NUMBER	NOT NULL	Execution ID
DESCRIPTION	VARCHAR2(256)		User-supplied description of the task
EXECUTION_TYPE	VARCHAR2(128)		Type of the last execution (optional for single-execution tasks)
EXECUTION_TYPE#	NUMBER		Reserved for internal use
EXECUTION_START	DATE		Execution start date and time
EXECUTION_LAST_MODIFIED	DATE	NOT NULL	Last modified date and time for the execution
EXECUTION_END	DATE		Execution end date and time
ADVISOR_NAME	VARCHAR2(128)		Advisor associated with the task
REQUESTED_DOP	NUMBER		The degree of parallelism (DOP) value requested by the user (through the TEST_EXECUTE_DOP parameter). It can be any value greater or equal to zero.
ACTUAL_DOP	NUMBER		The actual degree of parallelism (DOP) with which the execution finished. If the requested DOP is greater than than what is available on the system, the ACTUAL_DOP value can be lower than the REQUESTED_DOP value.
CONCURRENT_EXECUTION	VARCHAR2(3)		Indicates whether concurrency was used for this execution (YES) or not (NO)
ADVISOR_ID	NUMBER	NOT NULL	Unique identifier for the advisor
STATUS	VARCHAR2(11)		Current operational status of the task: • EXECUTING • COMPLETED • INTERRUPTED • CANCELLED • FATAL ERROR
STATUS#	NUMBER	NOT NULL	Reserved for internal use
STATUS_MESSAGE	VARCHAR2(4000)		Informational message provided by the advisor regarding the status
ERROR_MESSAGE	VARCHAR2(4000)		Informational message or an error message indicating the current operation or condition

See Also:

"USER_ADVISOR_EXECUTIONS"

5.30 DBA_ADVISOR_FDG_BREAKDOWN

DBA_ADVISOR_FDG_BREAKDOWN describes the contribution from the different instances to the findings for each ADDM task.

This view is populated only with ADDM tasks that are analyzing multiple instances (that is, the ACTUAL_ANALYSIS column in the task's row in DBA_ADDM_TASKS is set to DATABASE or PARTIAL).

Related View

USER_ADVISOR_FDG_BREAKDOWN describes the contribution from the different instances to the findings for each ADDM task owned by the current user.

Column	Datatype	NULL	Description
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task (see DBA_ADVISOR_TASKS and DBA_ADDM_TASKS)
FINDING_ID	NUMBER	NOT NULL	Identifier of the finding to which this breakdown applies (see DBA_ADVISOR_FINDINGS and DBA_ADDM_FINDINGS)
INSTANCE_NUMBER	NUMBER	NOT NULL	The number of the instance for the breakdown
IMPACT	NUMBER		The database time (in microseconds) of the finding in the instance
PERC_IMPACT	NUMBER		Percentage of the contribution of the instance to the overall finding's impact
EXECUTION_NAME	VARCHAR2(128)		The name of the task execution with which this entry (row) is associated

See Also:

"USER_ADVISOR_FDG_BREAKDOWN"

5.31 DBA_ADVISOR_FINDING_NAMES

DBA_ADVISOR_FINDING_NAMES provides a list of all finding names registered with the Advisor Framework.

Column	Datatype	NULL	Description
ID	NUMBER		ID of the finding name
ADVISOR_NAME	VARCHAR2(128)	NOT NULL	Advisor name
FINDING_NAME	VARCHAR2(4000)		Finding name

5.32 DBA_ADVISOR_FINDINGS

DBA_ADVISOR_FINDINGS displays the findings discovered by all advisors in the database.

Related View

USER_ADVISOR_FINDINGS displays the findings discovered by the advisors owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task
EXECUTION_NAME	VARCHAR2(128)		The name of the task execution with which this entry (row) is associated
FINDING_ID	NUMBER	NOT NULL	Identifier of the finding
FINDING_NAME	VARCHAR2(4000)		Name of the finding
TYPE	VARCHAR2(11)		Type of the finding: • PROBLEM • SYMPTOM • ERROR • INFORMATION
TYPE_ID	NUMBER	NOT NULL	Numeric ID for the value in column TYPE
PARENT	NUMBER	NOT NULL	Identifier of the parent finding
OBJECT_ID	NUMBER		Identifier of the associated object, if any
IMPACT_TYPE	VARCHAR2(4000)		Impact of the finding on the system
IMPACT	NUMBER		Impact value
MESSAGE	VARCHAR2(4000)		Message describing the finding
MORE_INFO	VARCHAR2(4000)		Additional info associated with the finding
FILTERED	VARCHAR2(1)		A value of Y means that the row in the view was filtered out by a directive (or a combination of directives). A value of N means that the row was not filtered.
FLAGS	NUMBER		For internal use only by advisor framework clients

See Also:

"USER_ADVISOR_FINDINGS"

5.33 DBA_ADVISOR_JOURNAL

DBA_ADVISOR_JOURNAL displays the journal entries for all tasks in the database.

Related View

USER_ADVISOR_JOURNAL displays the journal entries for the tasks owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Identifier of the task or workload object
TASK_NAME	VARCHAR2(128)		Name of the task or workload object
EXECUTION_NAME	VARCHAR2(128)		The name of the task execution with which this entry (row) is associated
JOURNAL_ENTRY_SEQ	NUMBER	NOT NULL	Sequence number of the journal entry (unique for each task). This sequence number is used to order the data.
JOURNAL_ENTRY_TYPE	VARCHAR2(12)		Type of the task: • FATAL • ERROR • WARNING • INFORMATION • INFORMATION[2 | 3 | 4 | 5 | 6]
JOURNAL_ENTRY	VARCHAR2(4000)		Entry in the journal

See Also:

"USER_ADVISOR_JOURNAL"

5.34 DBA_ADVISOR_LOG

DBA_ADVISOR_LOG displays information about the current state of all tasks in the database, as well as execution-specific data such as progress monitoring and completion status.

The view contains one row for each task.

Related View

USER_ADVISOR_LOG displays information about the current state of the tasks owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Identifier of the task

Column	Datatype	NULL	Description
TASK_NAME	VARCHAR2(128)		Name of the task
EXECUTION_START	DATE		Execution start date and time of the task
EXECUTION_END	DATE		Execution end date and time of the task
STATUS	VARCHAR2(11)		Current operational status of the task: • INITIAL - Initial state of the task; no recommendations are present • EXECUTING - Task is currently running • COMPLETED - Task successfully completed the analysis operation. Recommendation data can be viewed and reported. • INTERRUPTED - Task analysis was interrupted by the user. Recommendation data, if present, can be viewed and reported at this time. • CANCELLED • FATAL ERROR - An irrecoverable error occurred during the analysis operation. All recommendation data is unusable.
STATUS_MESSAGE	VARCHAR2(4000)		Informational message provided by the advisor regarding the status
PCT_COMPLETION_TIME	NUMBER		Percent completion, in terms of time, of the task when it is executing
PROGRESS_METRIC	NUMBER		Metric that measures the progress of the task in terms of quality. Each advisor could have its own metric.
METRIC_UNITS	VARCHAR2(64)		Unit of the metric used to measure progress
ACTIVITY_COUNTER	NUMBER		Counter that is updated frequently by the advisor, denoting that useful work is being performed
RECOMMENDATION_COUNT	NUMBER		Number of recommendations produced
ERROR_MESSAGE	VARCHAR2(4000)		Informational message or an error message indicating the current operation or condition

See Also:

"USER_ADVISOR_LOG"

5.35 DBA_ADVISOR_OBJECT_TYPES

DBA_ADVISOR_OBJECT_TYPES displays information about the object types used by all advisors in the database.

In addition to the regular database object types (such as TABLE and INDEX), the following types are defined:

- SYSTEM
- I/O

- SGA
- PGA
- SHARED POOL
- BUFFER CACHE
- LIBRARY CACHE
- PROCESS
- SESSION
- ENQUEUE
- LATCH
- ROLLBACK SEGMENT
- FILE
- PARAMETER
- CURSOR
- SQL
- SQL WORKLOAD

Column	Datatype	NULL	Description
OBJECT_TYPE_ID	NUMBER		Type identifier
OBJECT_TYPE	VARCHAR2(64)		Type name

5.36 DBA_ADVISOR_OBJECTS

DBA_ADVISOR_OBJECTS displays information about the objects currently referenced by all advisors in the database.

Each row in the view pertains to an object instantiation.

Related View

USER_ADVISOR_OBJECTS displays information about the objects currently referenced by the advisors owned by the current user. This view does not display the OWNER ATTR21, and ATTR22 columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the object
OBJECT_ID	NUMBER	NOT NULL	Identifier of the object
TYPE	VARCHAR2(64)		Name of the type
TYPE_ID	NUMBER	NOT NULL	Type identifier number
TASK_ID	NUMBER	NOT NULL	Task referencing the object
TASK_NAME	VARCHAR2(128)		Name of the task
EXECUTION_NAME	VARCHAR2(128)		The name of the task execution with which this entry (row) is associated

Column	Datatype	NULL	Description
ATTR1	VARCHAR2(4000)		Attributes and identifier of the object
ATTR2	VARCHAR2(4000)		Attributes and identifier of the object
ATTR3	VARCHAR2(4000)		Attributes and identifier of the object
ATTR4	CLOB		Attributes and identifiers that cannot be expressed in the ATTR1, ATTR2, and ATTR3 columns
ATTR5	VARCHAR2(4000)		Attributes and identifier of the object
ATTR6	RAW(2000)		Attributes and identifier of the object
ATTR7	NUMBER		Attributes and identifier of the object
ATTR8	NUMBER		Attributes and identifier of the object
ATTR9	NUMBER		Attributes and identifier of the object
ATTR10	NUMBER		Attributes and identifier of the object
ATTR11	NUMBER		Attributes and identifier of the object
ATTR16	VARCHAR2(4000)		Attributes and identifier of the object
ATTR17	VARCHAR2(4000)		Attributes and identifier of the object
ATTR18	VARCHAR2(4000)		Attributes and identifier of the object
ATTR21	DATE		Attributes and identifier of the object
ATTR22	DATE		Attributes and identifier of the object
OTHER	CLOB		Other attributes and identifiers of the object
ADV_SQL_ID	VARCHAR2(13)		If the object type is SQL, then this column contains the SQL identifier of the SQL statement. Otherwise, the value of this column is null.

Note:

The definition of the ATTRn columns depends on the advisors that are using the object. For example, the SQL object type defines the attribute columns as follows:

- ATTR1 contains the SQL ID
- ATTR2 contains the SQL address (in the cursor cache)
- ATTR4 contains the SQL text

See Also:

"USER_ADVISOR_OBJECTS"

5.37 DBA_ADVISOR_PARAMETERS

DBA_ADVISOR_PARAMETERS displays all task parameters and their current values in the database.

This data is accessible by all tasks.

Related View

USER_ADVISOR_PARAMETERS displays the task parameters and their current values for the tasks owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task or workload object
TASK_ID	NUMBER	NOT NULL	Unique identifier number of the task or workload object
TASK_NAME	VARCHAR2(128)		Name of the task or workload object
PARAMETER_NAME	VARCHAR2(128)	NOT NULL	Name of the parameter
PARAMETER_VALUE	VARCHAR2(4000)	NOT NULL	Value of the parameter. Numeric parameter values are converted to a string equivalent. Possible keywords as values: • ALL • UNLIMITED • UNUSED
PARAMETER_TYPE	VARCHAR2(10)		Datatype of the parameter: • NUMBER - Numeric value • STRING - String value. If the string contains special characters, then it will be enclosed in single quotes. • STRINGLIST - Comma-separated list of string elements. If a string element contains a comma or other special characters, then the element will be enclosed in single quotes. • TABLE - Single table reference. A reference will contain a schema name, followed by an optional table name. If the table name is omitted or is the character %, then the table name is interpreted as a wildcard. SQL quoted identifiers are supported. • TABLELIST - List of one or more comma-separated table references. A reference will contain schema name, followed by an optional table name. If the table name is omitted or is the character %, then the table name is interpreted as a wildcard. SQL quoted identifiers are supported.
IS_DEFAULT	VARCHAR2(1)		Indicates whether the parameter value is set to the advisor's default value (Y) or not (N)

Column	Datatype	NULL	Description
IS_OUTPUT	VARCHAR2(1)		Indicates whether the task execution process sets the parameter value (Y) or not (N)
IS_MODIFIABLE_ANYTIME	VARCHAR2(1)		Indicates whether the parameter value can be modified when the task is not in its initial state (Y) or not (N)
DESCRIPTION	VARCHAR2(4000)		Optional description of the parameter
EXECUTION_TYPE	VARCHAR2(128)		For advisors supporting multiple executions, the type of execution this parameter pertains to

See Also:

"USER_ADVISOR_PARAMETERS"

5.38 DBA_ADVISOR_RATIONALE

DBA_ADVISOR_RATIONALE displays information about the rationales for all recommendations in the database.

Related View

USER_ADVISOR_RATIONALE displays information about the rationales for the recommendations owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task
EXECUTION_NAME	VARCHAR2(128)		The name of the task execution with which this entry (row) is associated
REC_ID	NUMBER		Recommendation associated with the rationale
RATIONALE_ID	NUMBER	NOT NULL	Unique identifier for the rationale
IMPACT_TYPE	VARCHAR2(4000)		Impact on the system due to the problem described in the rationale. The impact can be described in terms of time, cost, or % degradation.
IMPACT	NUMBER		Calculated impact value
MESSAGE	VARCHAR2(4000)		Message containing an overview of the rationale
OBJECT_ID	NUMBER		Identifier of an object specified in the DBA_ADVISOR_OBJECTS view

Column	Datatype	NULL	Description
TYPE	VARCHAR2(30)		Type of the rationale; defines what data exists in the attribute columns and how to interpret it: • TEXT - Text sentence for descriptive messages. The ATTR1 column contains the text. • CHART - Chart containing data to be displayed. The ATTR1 column contains the data.
ATTR1	VARCHAR2(4000)		Parameters defining the rationale
ATTR2	VARCHAR2(4000)		Parameters defining the rationale
ATTR3	VARCHAR2(4000)		Parameters defining the rationale
ATTR4	VARCHAR2(4000)		Parameters defining the rationale
ATTR5	CLOB		Parameters defining the rationale

See Also:

"USER_ADVISOR_RATIONALE"

5.39 DBA_ADVISOR_RECOMMENDATIONS

DBA_ADVISOR_RECOMMENDATIONS displays the results of an analysis of all recommendations in the database.

A recommendation can have multiple actions associated with it. Actions are described in the DBA_ADVISOR_ACTIONS view. A recommendation also points to a set of rationales that present a justification/reasoning for that recommendation. These rationales are in the DBA_ADVISOR_RATIONALE view.

Related View

USER_ADVISOR_RECOMMENDATIONS displays the results of an analysis of the recommendations owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
REC_ID	NUMBER	NOT NULL	Unique identifier of the recommendation
TASK_ID	NUMBER	NOT NULL	Task that owns the recommendation
TASK_NAME	VARCHAR2(128)		Name of the task
EXECUTION_NAME	VARCHAR2(128)		The name of the task execution with which this entry (row) is associated
FINDING_ID	NUMBER		Unique identifier of the finding
TYPE	VARCHAR2(30)		Type of the recommendation
RANK	NUMBER		Ranking, in terms of importance, within the set of recommendations generated for the task

Column	Datatype	NULL	Description
PARENT_REC_IDS	VARCHAR2(4000)		Comma-separated list of the recommendation IDs of the parent recommendations. If this column is nonzero, then the recommendation depends on the parents, and cannot be accepted if the parents are not accepted.
BENEFIT_TYPE	VARCHAR2(4000)		Describes the benefit obtained by carrying out the recommendation If there is a set of parents for the recommendation, then the benefit is the cumulative benefit (the improvement in system performance when this and all prior parent recommendations are accepted). If there are no parents, then this is the improvement when the recommendation is accepted, independent of other recommendations.
BENEFIT	NUMBER		Calculated benefit value This column displays an estimate of the savings in total activity (or load) on the system if all actions of the recommendation are implemented. Recommendations are not additive, that is, the benefit from one recommendation may overlap with the benefit from another. For example, Oracle might recommend increasing the shared pool size, or reducing hard parses (by not using literals), and both recommendations might reduce the same part of the workload related to parsing. The benefit is given in both pure active sessions and as a percent of the average active sessions of the analysis time period. Therefore, if the benefit is 20% of active sessions, Oracle estimates that if you apply the actions on the same workload, the average active sessions on the server will be reduced by 20%. The DBA_ADDM_TASKS view displays the average active sessions for an ADDM task.
ANNOTATION_STATUS	VARCHAR2(11)		When a task is complete, the recommendations are marked ACCEPT. The status can be changed later using the MARK_RECOMMENDATION procedure: • ACCEPT - Current recommendation is ready to implement. This recommendation can also be used as advice for future analysis operations. • REJECT - Current recommendation is not acceptable to the user, and therefore will be excluded from any implementation scripts. This recommendation can also be used as advice for future analysis operations. • IGNORE - Though not rejected, the current recommendation will be ignored when generating scripts and will never be used as advice to future analysis operations.
FLAGS	NUMBER		Advisor-specific flags

Column	Datatype	NULL	Description
FILTERED	VARCHAR2(1)		A value of Y means that the row in the view was filtered out by a directive (or a combination of directives). A value of N means that the row was not filtered.
REC_TYPE_ID	NUMBER		Recommendation type ID

See Also:

- "USER_ADVISOR_RECOMMENDATIONS"
- "DBA_ADDM_TASKS"

5.40 DBA_ADVISOR_SQLA_REC_SUM

DBA_ADVISOR_SQLA_REC_SUM displays recommendation rollup information for all workload objects in the database after an Access Advisor analysis operation.

Related View

USER_ADVISOR_SQLA_REC_SUM displays recommendation rollup information for the workload objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER		Unique identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task
REC_ID	NUMBER		Identifier of the recommendation
TOTAL_STMTS	NUMBER		Total number of statements processed during analysis
TOTAL_PRECOST	NUMBER		Total cost of executing the statements in which the recommended object will be used, before the recommendations
TOTAL_POSTCOST	NUMBER		Total cost of executing the statements in which the recommended object will be utilized, after the recommendations have been implemented

See Also:

"USER_ADVISOR_SQLA_REC_SUM"

5.41 DBA_ADVISOR_SQLA_TABLES

DBA_ADVISOR_SQLA_TABLES displays cross references between the workload statements and the tables referenced in the statement.

Related View

USER_ADVISOR_SQLA_TABLES displays cross references between the workload statements and the tables referenced in the statement for the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the workload object
TASK_ID	NUMBER		Unique identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task
SQL_ID	VARCHAR2(13)		SQL identifier of the parent cursor in the library cache
STMT_ID	NUMBER		Statement ID
TABLE_OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Table name

> **See Also:**
>
> "USER_ADVISOR_SQLA_TABLES"

5.42 DBA_ADVISOR_SQLA_WK_MAP

DBA_ADVISOR_SQLA_WK_MAP displays the workload references for all tasks in the database.

Workload references are necessary to allow the SQL Access Advisor to find required workload data.

Related View

USER_ADVISOR_SQLA_WK_MAP displays the workload references for the tasks owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER		Unique identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task
WORKLOAD_ID	NUMBER		Unique identifier of the workload object
WORKLOAD_NAME	VARCHAR2(128)		Name of the workload

Column	Datatype	NULL	Description
IS_STS	NUMBER		Type of workload source: • 0 - SQL workload object • 1 - SQL Tuning Set

> **See Also:**
>
> "USER_ADVISOR_SQLA_WK_MAP"

5.43 DBA_ADVISOR_SQLA_WK_STMTS

DBA_ADVISOR_SQLA_WK_STMTS displays information about all workload objects in the database after an Access Advisor analysis operation.

Related View

USER_ADVISOR_SQLA_WK_STMTS displays information about the workload objects owned by the current user after an Access Advisor analysis operation. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_NAME	VARCHAR2(128)		Name of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task
SQLSET_ID	NUMBER		ID of the SQL tuning set for the statement
SQLSET_NAME	VARCHAR2(128)		Name of the SQL tuning set for the statement
WORKLOAD_NAME	VARCHAR2(128)		Name of the workload
SQL_ID	VARCHAR(13)	NOT NULL	Generated identifier of the statement
SQL_SEQ	NUMBER	NOT NULL	SQL sequence
PLAN_HASH_VALUE	NUMBER	NOT NULL	Numerical representation of the SQL plan for the cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line-by-line).
PARSING_SCHEMA_NAME	VARCHAR2(128)		Schema name that was used to originally build this child cursor
USERNAME	VARCHAR2(128)		Name of the user executing the statement
MODULE	VARCHAR2(64)		Name of the module issuing the statement
ACTION	VARCHAR2(64)		Module action for the statement
CPU_TIME	NUMBER		Total CPU count (in seconds) of the executing statement
BUFFER_GETS	NUMBER		Total number of buffer gets for the statement
DISK_READS	NUMBER		Total disk-read I/O count for the statement

Column	Datatype	NULL	Description
ELAPSED_TIME	NUMBER		Total elapsed time (in seconds) of the executing statement
ROWS_PROCESSED	NUMBER		Total number of rows processed by the statement
EXECUTIONS	NUMBER		Total number of times the statement was executed
FIRST_LOAD_TIME	DATE		Load time of parent cursor
LAST_EXECUTION_DATE	DATE		Date on which the statement was last executed
PRIORITY	NUMBER		Business importance of the statement: • 1 - High • 2 - Medium • 3 - Low
COMMAND_TYPE	NUMBER		Type of the command
STAT_PERIOD	NUMBER		Unused
ACTIVE_STAT_PERIOD	NUMBER		Effective period of time (in seconds) during which the SQL statement was active
SQL_TEXT	CLOB		Text of the SQL statement
PRECOST	NUMBER		Cost of executing the statement in the workload prior to the recommendations
POSTCOST	NUMBER		Cost of executing the statement in the workload after the recommendations
IMPORTANCE	NUMBER		Advisor-calculated importance value
REC_ID	NUMBER		Associated recommendation identifier
VALIDATED	NUMBER		Indicates whether the statement is valid for analysis: • 0 - Statement will not be analyzed by the EXECUTE_TASK procedure. Typically, the statement references one or more tables that do not have valid statistics. To correct this problem, ensure that the tables have valid statistics and execute the RESET_SQLWKLD procedure on the current workload. • 1- Statement is eligible for analysis by the EXECUTE_TASK procedure

See Also:

"USER_ADVISOR_SQLA_WK_STMTS"

5.44 DBA_ADVISOR_SQLPLANS

DBA_ADVISOR_SQLPLANS displays the different SQL execution plans generated as part of an advisor analysis.

Related View

USER_ADVISOR_SQLPLANS displays the different SQL execution plans owned by the current user generated as part of an advisor analysis.

Column	Datatype	NULL	Description
TASK_NAME	VARCHAR2(128)		Advisor task name in which the SQL plan was generated (see DBA_ADVISOR_TASKS)
TASK_ID	NUMBER(38)	NOT NULL	Advisor task ID in which the SQL plan was generated (see DBA_ADVISOR_TASKS)
EXECUTION_NAME	VARCHAR2(128)	NOT NULL	Advisor task execution in which the SQL plan was generated (see DBA_ADVISOR_EXECUTIONS)
SQL_ID	VARCHAR2(13)	NOT NULL	Identifier for the relevant SQL statement
OBJECT_ID	NUMBER(38)	NOT NULL	Advisor object ID identifying the relevant SQL statement (see DBA_ADVISOR_OBJECTS)
ATTRIBUTE	VARCHAR2(34)		Text string identifying the type of the execution plan. The following values are used by the SQL Tuning Advisor: • Original - Original plan of the query • Original with adjusted cost - Same as Original but with adjusted cost • Using SQL profile - Plan with SQL profile applied • Using new indices - Plan with indexes applied
STATEMENT_ID	VARCHAR2(30)		Optional statement identifier specified in the EXPLAIN PLAN statement
PLAN_HASH_VALUE	NUMBER	NOT NULL	Numerical representation of the execution plan
PLAN_ID	NUMBER	NOT NULL	Plan identifier
TIMESTAMP	DATE		Date and time when the EXPLAIN PLAN statement was issued
REMARKS	VARCHAR2(4000)		Place for comments that can be added to the steps of the execution plan
OPERATION	VARCHAR2(30)		Name of the operation performed at this step
OPTIONS	VARCHAR2(255)		Options used for the operation performed at this step
OBJECT_NODE	VARCHAR2(128)		Name of the database link used to reference the object
OBJECT_OWNER	VARCHAR2(128)		Owner of the object
OBJECT_NAME	VARCHAR2(128)		Name of the object
OBJECT_ALIAS	VARCHAR2(261)		Object alias
OBJECT_INSTANCE	NUMBER(38)		Numbered position of the object name in the original SQL statement

Column	Datatype	NULL	Description
OBJECT_TYPE	VARCHAR2(30)		Descriptive modifier that further describes the type of object
OPTIMIZER	VARCHAR2(255)		Current mode of the optimizer
SEARCH_COLUMNS	NUMBER		Number of index columns with start and stop keys (that is, the number of columns with matching predicates)
ID	NUMBER(38)	NOT NULL	Identification number for this step in the execution plan
PARENT_ID	NUMBER(38)		ID of the next step that operates on the results of this step
DEPTH	NUMBER(38)		Depth
POSITION	NUMBER(38)		Order of processing for steps with the same parent ID
COST	NUMBER(38)		Cost of the current operation estimated by the cost-based optimizer (CBO)
CARDINALITY	NUMBER(38)		Number of rows returned by the current operation (estimated by the CBO)
BYTES	NUMBER(38)		Number of bytes returned by the current operation
OTHER_TAG	VARCHAR2(255)		Describes the function of the SQL text in the OTHER column. Values for OTHER_TAG are: • SERIAL - SQL is the text of a locally-executed, serial query plan. Currently, SQL is not loaded in OTHER for this case. • SERIAL_FROM_REMOTE - SQL text shown in the OTHER column will be executed at a remote site • PARALLEL_COMBINED_WITH_PARENT - Parent of this operation is a DFO that performs both operations in the parallel execution plan • PARALLEL_COMBINED_WITH_CHILD - Child of this operation is a DFO that performs both operations in the parallel execution plan. • PARALLEL_TO_SERIAL - SQL text shown in the OTHER column is the top-level of the parallel plan. • PARALLEL_TO_PARALLEL - SQL text shown in the OTHER column is executed and output in parallel • PARALLEL_FROM_SERIAL - Operation consumes data from a serial operation and outputs it in parallel
PARTITION_START	VARCHAR2(255)		Start partition of a range of accessed partitions
PARTITION_STOP	VARCHAR2(255)		Stop partition of a range of accessed partitions
PARTITION_ID	NUMBER(38)		Step that has computed the pair of values of the PARTITION_START and PARTITION_STOP columns
OTHER	LONG		Information about parallel execution servers and parallel queries
DISTRIBUTION	VARCHAR2(30)		Distribution method

Column	Datatype	NULL	Description
CPU_COST	NUMBER(38)		User-defined CPU cost
IO_COST	NUMBER(38)		User-defined I/O cost
TEMP_SPACE	NUMBER(38)		Temporary space usage of the operation (sort or hash-join) as estimated by the CBO
ACCESS_PREDICATES	VARCHAR2(4000)		Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.
FILTER_PREDICATES	VARCHAR2(4000)		Predicates used to filter rows before producing them
PROJECTION	VARCHAR2(4000)		Expressions produced by the operation
TIME	NUMBER(38)		Elapsed time (in seconds) of the operation as estimated by the CBO
QBLOCK_NAME	VARCHAR2(128)		Name of the query block
OTHER_XML	CLOB		Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML because it allows multiple pieces of information to be stored, including the following: • Name of the schema against which the query was parsed • Release number of the Oracle Database that produced the explain plan • Hash value associated with the execution plan • Name (if any) of the outline or the SQL profile used to build the execution plan • Indication of whether or not dynamic statistics were used to produce the plan • The outline data, a set of optimizer hints that can be used to regenerate the same plan

See Also:

"USER_ADVISOR_SQLPLANS"

5.45 DBA_ADVISOR_SQLSTATS

DBA_ADVISOR_SQLSTATS displays execution statistics for the test-execution of different SQL plans during the advisor analysis.

Related View

USER_ADVISOR_SQLSTATS displays execution statistics owned by the current user for the test-execution of different SQL plans during the advisor analysis.

Column	Datatype	NULL	Description
TASK_NAME	VARCHAR2(128)		Advisor task name in which the SQL statement was executed (see DBA_ADVISOR_TASKS)
TASK_ID	NUMBER(38)	NOT NULL	Advisor task ID in which the SQL statement was executed (see DBA_ADVISOR_TASKS)
EXECUTION_NAME	VARCHAR2(128)	NOT NULL	Advisor task execution in which the SQL statement was executed (see DBA_ADVISOR_EXECUTIONS)
EXECUTION_TYPE	VARCHAR2(128)		Type of the advisor task execution in which the SQL statement was executed (see DBA_ADVISOR_EXECUTIONS)
OBJECT_ID	NUMBER(38)	NOT NULL	Advisor object ID identifying the relevant SQL statement (see DBA_ADVISOR_OBJECTS)
PLAN_ID	NUMBER	NOT NULL	Plan ID number generated to uniquely identify a plan for a particular SQL statement (foreign key to DBA_ADVISOR_SQLPLANS)
SQL_ID	VARCHAR2(13)	NOT NULL	Identifier for the SQL statement executed
PLAN_HASH_VALUE	NUMBER	NOT NULL	Hash value of the SQL execution plan
ATTR1	NUMBER		For internal use only
CON_DBID	NUMBER		The database ID of the pluggable database (PDB)
PARSE_TIME	NUMBER		Parse time (in microseconds) measured for the SQL
ELAPSED_TIME	NUMBER		Elapsed time (in microseconds) to execute the SQL and fetch all of its rows, after parsing
CPU_TIME	NUMBER		CPU time (in microseconds) to execute the SQL and fetch all of its rows, after parsing
USER_IO_TIME	NUMBER		I/O time (in microseconds) to execute the SQL and fetch all of its rows, after parsing
BUFFER_GETS	NUMBER		Number of buffer gets measured for executing the SQL and fetching all of its rows
DISK_READS	NUMBER		Number of disk reads measured for executing the SQL and fetching all of its rows
DIRECT_WRITES	NUMBER		Number of direct writes measured for executing the SQL and fetching all of its rows
PHYSICAL_READ_REQUESTS	NUMBER		Number of physical read I/O requests issued by the monitored SQL
PHYSICAL_WRITE_REQUESTS	NUMBER		Number of physical write I/O requests issued by the monitored SQL
PHYSICAL_READ_BYTES	NUMBER		Number of bytes read from disks by the monitored SQL
PHYSICAL_WRITE_BYTES	NUMBER		Number of bytes written to disks by the monitored SQL
ROWS_PROCESSED	NUMBER		Number of rows returned by the SQL execution
FETCHES	NUMBER		Number of fetches for the SQL execution
EXECUTIONS	NUMBER		Execution count for the SQL. This column will always have a value of 1 or 0.

Column	Datatype	NULL	Description
END_OF_FETCH_COUNT	NUMBER		Indicates whether the SQL was executed to end-of-fetch (1) or not (0)
OPTIMIZER_COST	NUMBER		Optimizer cost for the execution plan
OTHER	CLOB		For internal use only
TESTEXEC_TOTAL_EXECS	NUMBER		Total number of executions during test execute
IO_INTERCONNECT_BYTES	NUMBER		Number of I/O bytes exchanged between Oracle Database and the storage system
TESTEXEC_FIRST_EXEC_IGNORED	VARCHAR2(1)		Indicates whether the first execution in test execute is ignored (Y) or not (N)
CON_DBID	NUMBER		The database ID of the PDB
ATTR2	NUMBER		For internal use only
ATTR3	NUMBER		For internal use only
CACHED_GETS	NUMBER		The total of the db block gets from cache statistic and the consistent gets from cache statistic
DIRECT_GETS	NUMBER		The total of the db block gets direct statistic and the consistent gets direct statistic
EXECUTIONS_ORIGINAL	NUMBER		Number of original executions from the SQL tuning set, independent of trial executions
OBJECT_FLAGS	NUMBER		Value of the flags from the execution of the SQL, such as timeout or error

See Also:

- "USER_ADVISOR_SQLSTATS"
- "Statistics Descriptions" for more information about statistics

5.46 DBA_ADVISOR_SQLW_JOURNAL

DBA_ADVISOR_SQLW_JOURNAL displays the journal entries for all workload objects in the database.

Related View

USER_ADVISOR_SQLW_JOURNAL displays the journal entries for the workload objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the workload
WORKLOAD_ID	NUMBER	NOT NULL	Identifier number of the workload object
WORKLOAD_NAME	VARCHAR2(128)		Name of the workload object
JOURNAL_ENTRY_SEQ	NUMBER	NOT NULL	Sequence number of the journal entry (unique for each workload). The sequence number is used to order the data.

Column	Datatype	NULL	Description
JOURNAL_ENTRY_TYPE	VARCHAR2(12)		Type of the task: • FATAL • ERROR • WARNING • INFORMATION • INFORMATION[2 | 3 | 4 | 5 | 6]
JOURNAL_ENTRY	VARCHAR2(4000)		Entry in the journal

> **See Also:**
>
> "USER_ADVISOR_SQLW_JOURNAL"

5.47 DBA_ADVISOR_SQLW_PARAMETERS

DBA_ADVISOR_SQLW_PARAMETERS displays all workload parameters and their current values in the database.

Related View

USER_ADVISOR_SQLW_PARAMETERS displays the workload parameters and their current values owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task or workload object
WORKLOAD_ID	NUMBER	NOT NULL	Unique identifier number of the workload object
WORKLOAD_NAME	VARCHAR2(128)		Name of the workload object
PARAMETER_NAME	VARCHAR2(128)	NOT NULL	Name of the parameter
PARAMETER_VALUE	VARCHAR2(4000)	NOT NULL	Value of the parameter. Numeric parameter values are converted to a string equivalent. Possible keywords as values: • ALL • UNLIMITED • UNUSED

Column	Datatype	NULL	Description
PARAMETER_TYPE	VARCHAR2(10)		Datatype of the parameter: • NUMBER - Numeric value • STRING - String value. If the string contains special characters, then it will be enclosed in single quotes. • STRINGLIST - Comma-separated list of string elements. If a string element contains a comma or other special characters, then the element will be enclosed in single quotes. • TABLE - Single table reference. A reference contains a schema name, followed by an optional table name. If the table name is omitted or is the character %, then the table name is interpreted as a wildcard. SQL quoted identifiers are supported. • TABLELIST - List of one or more comma-separated table references. A reference contains a schema name, followed by an optional table name. If the table name is omitted or is the character %, then the table name is interpreted as a wildcard. SQL quoted identifiers are supported.
DESCRIPTION	VARCHAR2(4000)		Parameter description

See Also:

"USER_ADVISOR_SQLW_PARAMETERS"

5.48 DBA_ADVISOR_SQLW_STMTS

DBA_ADVISOR_SQLW_STMTS displays rows that correspond to all statements in the workload.

All columns are guaranteed to be non-null.

Related View

USER_ADVISOR_SQLW_STMTS displays rows that correspond to the statements in the workload owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the workload object
WORKLOAD_ID	NUMBER	NOT NULL	Unique identifier number of the workload object
WORKLOAD_NAME	VARCHAR2(128)		Name of the workload
SQL_ID	NUMBER	NOT NULL	Generated identifier of the statement

Column	Datatype	NULL	Description
HASH_VALUE	NUMBER		Hash value for the parent statement in the cache
USERNAME	VARCHAR2(128)		Name of the user executing the statement
MODULE	VARCHAR2(64)		Name of the module issuing the statement
ACTION	VARCHAR2(64)		Module action for the statement
CPU_TIME	NUMBER		Total CPU count (in seconds) of the executing statement
BUFFER_GETS	NUMBER		Total number of buffer gets for the statement
DISK_READS	NUMBER		Total disk-read I/O count for the statement
ELAPSED_TIME	NUMBER		Total elapsed time (in seconds) of the executing statement
ROWS_PROCESSED	NUMBER		Total number of rows processed by the statement
EXECUTIONS	NUMBER		Total number of times the statement was executed
OPTIMIZER_COST	NUMBER		Cost of executing the statement in the workload prior to the recommendations
LAST_EXECUTION_DATE	DATE		Date on which the statement was last executed
PRIORITY	NUMBER		Priority of the statement: • 1 - High • 2 - Medium • 3 - Low
COMMAND_TYPE	NUMBER		Type of the command
STAT_PERIOD	NUMBER		Unused
SQL_TEXT	CLOB		Text of the SQL statement
VALID	NUMBER		Indicates whether the statement is valid for analysis: • 0 - Statement will not be analyzed by the EXECUTE_TASK procedure. Typically, the statement references one or more tables that do not have valid statistics. To correct this problem, ensure that the tables have valid statistics and execute the RESET_SQLWKLD procedure on the current workload. • 1 - Statement is eligible for analysis by the EXECUTE_TASK procedure.

See Also:

"USER_ADVISOR_SQLW_STMTS"

5.49 DBA_ADVISOR_SQLW_SUM

DBA_ADVISOR_SQLW_SUM displays an aggregated picture of all SQLWkld workload objects in the database.

Related View

USER_ADVISOR_SQLW_SUM displays an aggregated picture of the SQLWkld workload objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the workload object
WORKLOAD_ID	NUMBER	NOT NULL	Unique identifier number of the workload object
WORKLOAD_NAME	VARCHAR2(128)		Unique name of the workload
DESCRIPTION	VARCHAR2(256)		User-specified description of the workload
CREATE_DATE	DATE	NOT NULL	Date on which the workload object was created
MODIFY_DATE	DATE	NOT NULL	Date of last update to the current workload
NUM_SELECT_STMT	NUMBER		Number of SELECT statements in the workload
NUM_UPDATE_STMT	NUMBER		Number of UPDATE statements in the workload
NUM_DELETE_STMT	NUMBER		Number of DELETE statements in the workload
NUM_INSERT_STMT	NUMBER		Number of INSERT statements in the workload
NUM_MERGE_STMT	NUMBER		Number of MERGE statements in the workload
SOURCE	VARCHAR2(128)		Optional name that identifies the creator of the object
HOW_CREATED	VARCHAR2(30)		Optional object or template on which the object was based
DATA_SOURCE	VARCHAR2(2000)		Workload data source
READ_ONLY	VARCHAR2(5)		Indicates whether or not the workload can be modified or deleted (TRUE) or not (FALSE)

See Also:

"USER_ADVISOR_SQLW_SUM"

5.50 DBA_ADVISOR_SQLW_TABLES

DBA_ADVISOR_SQLW_TABLES displays cross references between the workload statements and the tables referenced in the statement.

Related View

USER_ADVISOR_SQLW_TABLES displays cross references between the workload statements and the tables referenced in the statement. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the workload object
WORKLOAD_ID	NUMBER		Unique identifier number of the workload object
WORKLOAD_NAME	VARCHAR2(128)		Name of the workload
SQL_ID	NUMBER		Identifier of the statement
TABLE_OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table

See Also:

"USER_ADVISOR_SQLW_TABLES"

5.51 DBA_ADVISOR_SQLW_TEMPLATES

DBA_ADVISOR_SQLW_TEMPLATES displays an aggregated picture of all SQLWkld template objects in the database.

Related View

USER_ADVISOR_SQLW_TEMPLATES displays an aggregated picture of the SQLWkld template objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the workload object
WORKLOAD_ID	NUMBER	NOT NULL	Unique identifier number of the workload object
WORKLOAD_NAME	VARCHAR2(128)		Unique name of the workload
DESCRIPTION	VARCHAR2(256)		User-specified description of the workload
CREATE_DATE	DATE	NOT NULL	Date on which the workload object was created
MODIFY_DATE	DATE	NOT NULL	Date of last update to the current workload
SOURCE	VARCHAR2(128)		Optional object or template on which the object was based
READ_ONLY	VARCHAR2(5)		Indicates whether the workload template can be modified or deleted (TRUE) or not (FALSE)

See Also:

"USER_ADVISOR_SQLW_TEMPLATES"

5.52 DBA_ADVISOR_TASKS

DBA_ADVISOR_TASKS displays information about all tasks in the database.

The view contains one row for each task. Each task has a name that is unique to the owner. Task names are just informational and no uniqueness is enforced within any other namespace.

Related View

USER_ADVISOR_TASKS displays information about the tasks owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task
DESCRIPTION	VARCHAR2(256)		User-supplied description of the task
ADVISOR_NAME	VARCHAR2(128)		Advisor associated with the task
CREATED	DATE	NOT NULL	Creation date of the task
LAST_MODIFIED	DATE	NOT NULL	Date on which the task was last modified
PARENT_TASK_ID	NUMBER		Identifier of the parent task (if the task was created because of the recommendation of another task)
PARENT_RXEC_ID	NUMBER		Identifier of the recommendation within the parent task that resulted in the creation of the task
LAST_EXECUTION	VARCHAR2(128)		Name of the current or last task execution
EXECUTION_TYPE	VARCHAR2(128)		Type of the last execution. This information is optional for single-execution tasks.
EXECUTION_TYPE#	NUMBER		Reserved for internal use
EXECUTION_DESCRIPTION	VARCHAR2(256)		Optional description of the last execution
EXECUTION_START	DATE		Execution start date and time of the task
EXECUTION_END	DATE		Execution end date and time of the task
STATUS	VARCHAR2(11)		Current operational status of the task: • INITIAL - Initial state of the task; no recommendations are present • EXECUTING - Task is currently running • INTERRUPTED - Task analysis was interrupted by the user. Recommendation data, if present, can be viewed and reported at this time. • COMPLETED - Task successfully completed the analysis operation. Recommendation data can be viewed and reported. • ERROR - An error occurred during the analysis operation. Recommendations, if present, can be viewed and reported at this time.
STATUS_MESSAGE	VARCHAR2(4000)		Informational message provided by the advisor regarding the status

Column	Datatype	NULL	Description
PCT_COMPLETION_TIME	NUMBER		Percent completion, in terms of time, of the task when it is executing
PROGRESS_METRIC	NUMBER		Metric that measures the progress of the task in terms of quality. Each advisor may have its own metric.
METRIC_UNITS	VARCHAR2(64)		Unit of the metric used to measure progress
ACTIVITY_COUNTER	NUMBER		Counter that is updated frequently by the advisor, denoting that useful work is being performed
RECOMMENDATION_COUNT	NUMBER		Number of recommendations produced
ERROR_MESSAGE	VARCHAR2(4000)		Informational message or an error message indicating the current operation or condition
SOURCE	VARCHAR2(128)		Optional name that identifies the creator of the task
HOW_CREATED	VARCHAR2(30)		Optional task or template on which the object was based
READ_ONLY	VARCHAR2(5)		Indicates whether the task is read-only (TRUE) or not (FALSE)
SYSTEM_TASK	VARCHAR2(5)		Indicates whether the task is a system task (TRUE) or not (FALSE). The automatic SQL tuning task, SYS_AUTO_SQL_TUNING_TASK, is one example of a system task.
ADVISOR_ID	NUMBER	NOT NULL	Unique identifier for the advisor
STATUS#	NUMBER		Reserved for internal use

See Also:

"USER_ADVISOR_TASKS"

5.53 DBA_ADVISOR_TEMPLATES

DBA_ADVISOR_TEMPLATES displays information about all templates in the database.

Related View

USER_ADVISOR_TEMPLATES displays information about the templates owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task
DESCRIPTION	VARCHAR2(256)		User-supplied description of the task
ADVISOR_NAME	VARCHAR2(128)		Advisor associated with the task

Column	Datatype	NULL	Description
CREATED	DATE	NOT NULL	Creation date of the task
LAST_MODIFIED	DATE	NOT NULL	Date on which the task was last modified
SOURCE	VARCHAR2(128)		Optional task or template on which the template was based
READ_ONLY	VARCHAR2(5)		Indicates whether the task can be modified or deleted (TRUE) or not (FALSE)

See Also:

"USER_ADVISOR_TEMPLATES"

5.54 DBA_ADVISOR_USAGE

DBA_ADVISOR_USAGE displays the usage information for each type of advisor in the database.

Column	Datatype	NULL	Description
ADVISOR_ID	NUMBER	NOT NULL	Type of the advisor
ADVISOR_NAME	VARCHAR2(128)	NOT NULL	Name of the advisor
LAST_EXEC_TIME	DATE	NOT NULL	Date of the last execution
NUM_EXECS	NUMBER	NOT NULL	Cumulative number of executions
NUM_DB_REPORTS	NUMBER	NOT NULL	Cumulative number of reports
FIRST_REPORT_TIME	DATE		Time of the first report
LAST_REPORT_TIME	DATE		Time of the last report

5.55 DBA_AIM_PERF_FEATURES

DBA_AIM_PERF_FEATURES describes table columns on which Automatic In-Memory (AIM) performance features are enabled.

Column	Datatype	NULL	Description
OWNER_NAME	VARCHAR2(128)	NOT NULL	Table owner
TABLE_NAME	VARCHAR2(128)	NOT NULL	Table name
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column on which AIM performance features are enabled
OPTIMIZED_ARITHMETIC	CHAR(1)		Indicates whether the column is optimized for arithmetic operations (Y) or not (N)
BLOOMFILTER_OPTIMIZATION	CHAR(1)		Indicates whether queries on the column use cached hash values to probe the bloom filter during hash joins (Y) or not (N)

Column	Datatype	NULL	Description
VECTOR_OPTIMIZATION	CHAR(1)		Indicates whether data is stored in the column using vector optimization (Y) or not (N)
JOIN_GROUP	CHAR(1)		Indicates whether the column is part of a join group that was created by AIM (Y) or not (N)
CREATION_DATE	DATE		Date and time at which the AIM performance features were implemented

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

5.56 DBA_ALERT_HISTORY

DBA_ALERT_HISTORY describes a time-limited history of alerts which are no longer outstanding.

Column	Datatype	NULL	Description
SEQUENCE_ID	NUMBER	NOT NULL	Alert sequence number
REASON_ID	NUMBER		ID of the alert reason
OWNER	VARCHAR2(128)		Owner of the object on which the alert was issued
OBJECT_NAME	VARCHAR2(513)		Name of the object
SUBOBJECT_NAME	VARCHAR2(128)		Name of the subobject (for example: partition)
OBJECT_TYPE	VARCHAR2(64)		Type of the object (for example: table, tablespace)
REASON	VARCHAR2(4000)		Reason for the alert
TIME_SUGGESTED	TIMESTAMP(6) WITH TIME ZONE		Time when the alert was last updated
CREATION_TIME	TIMESTAMP(6) WITH TIME ZONE		Time when the alert was first created
SUGGESTED_ACTION	VARCHAR2(4000)		Advice of the recommended action
ADVISOR_NAME	VARCHAR2(128)		Name of the advisor to be invoked for more information
METRIC_VALUE	NUMBER		Value of the related metrics
MESSAGE_TYPE	VARCHAR2(12)		Message type: • Notification • Warning
MESSAGE_GROUP	VARCHAR2(64)		Name of the message group to which the alert belongs
MESSAGE_LEVEL	NUMBER		Severity message level (1 to 32)
HOSTING_CLIENT_ID	VARCHAR2(64)		ID of the client or security group to which the alert relates
MODULE_ID	VARCHAR2(64)		ID of the module that originated the alert
PROCESS_ID	VARCHAR2(128)		Process ID

Column	Datatype	NULL	Description
HOST_ID	VARCHAR2(256)		DNS host name of the originating host
HOST_NW_ADDR	VARCHAR2(256)		IP or other network address of the originating host
INSTANCE_NAME	VARCHAR2(16)		Originating instance name
INSTANCE_NUMBER	NUMBER		Originating instance number
USER_ID	VARCHAR2(128)		User ID
EXECUTION_CONTEXT_ID	VARCHAR2(128)		Execution Context ID
ERROR_INSTANCE_ID	VARCHAR2(142)		ID of an error instance plus a sequence number
RESOLUTION	VARCHAR2(7)		Resolution: • Cleared • N/A
PDB_NAME	VARCHAR2(128)		PDB name
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.57 DBA_ALERT_HISTORY_DETAIL

DBA_ALERT_HISTORY_DETAIL describes a time-limited history of cleared and outstanding alerts.

Column	Datatype	NULL	Description
SEQUENCE_ID	NUMBER	NOT NULL	Alert sequence number
REASON_ID	NUMBER		ID of the alert reason
OWNER	VARCHAR2(128)		Owner of the object on which alert is issued
OBJECT_NAME	VARCHAR2(513)		Name of the object
SUBOBJECT_NAME	VARCHAR2(128)		Name of the subobject (for example: partition)
OBJECT_TYPE	VARCHAR2(64)		Type of the object (for example: table, tablespace)
REASON	VARCHAR2(4000)		Reason for the alert
TIME_SUGGESTED	TIMESTAMP(6) WITH TIME ZONE		Time when the alert was last updated
CREATION_TIME	TIMESTAMP(6) WITH TIME ZONE		Time when the alert was first created
SUGGESTED_ACTION	VARCHAR2(4000)		Advice of the recommended action
ADVISOR_NAME	VARCHAR2(128)		Name of the advisor to be invoked for more information
METRIC_VALUE	NUMBER		Value of the related metrics

Column	Datatype	NULL	Description
MESSAGE_TYPE	VARCHAR2(12)		Message type: • Notification • Warning
MESSAGE_GROUP	VARCHAR2(64)		Name of the message group to which the alert belongs
MESSAGE_LEVEL	NUMBER		Severity level (1 to 32)
HOSTING_CLIENT_ID	VARCHAR2(64)		ID of the client or security group to which the alert relates
MODULE_ID	VARCHAR2(64)		ID of the module that originated the alert
PROCESS_ID	VARCHAR2(128)		Process id
HOST_ID	VARCHAR2(256)		DNS host name of the originating host
HOST_NW_ADDR	VARCHAR2(256)		IP or other network address of originating host
INSTANCE_NAME	VARCHAR2(16)		Originating instance name
INSTANCE_NUMBER	NUMBER		Originating instance number
USER_ID	VARCHAR2(128)		User ID
EXECUTION_CONTEXT_ID	VARCHAR2(128)		Execution Context ID
ERROR_INSTANCE_ID	VARCHAR2(142)		ID of an error instance plus a sequence number
RESOLUTION	VARCHAR2(11)		Resolution: • Cleared • Outstanding • N/A
STATE_TRANSITION_NUMBER	NUMBER	NOT NULL	Sequence number of the state transition for the alert
PDB_NAME	VARCHAR2(128)		PDB name
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.58 DBA_ALL_TABLES

DBA_ALL_TABLES describes all object tables and relational tables in the database. Its columns are the same as those in ALL_ALL_TABLES.

See Also:

"ALL_ALL_TABLES"

5.59 DBA_ANALYTIC_VIEW_ATTR_CLASS

DBA_ANALYTIC_VIEW_ATTR_CLASS describes the attribute classifications of all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_ATTR_CLASS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_ATTR_CLASS"

5.60 DBA_ANALYTIC_VIEW_ATTR_CLS

DBA_ANALYTIC_VIEW_ATTR_CLS is identical to DBA_ANALYTIC_VIEW_ATTR_CLASS.

> **See Also:**
>
> "DBA_ANALYTIC_VIEW_ATTR_CLASS"

5.61 DBA_ANALYTIC_VIEW_ATTR_CLS_AE

DBA_ANALYTIC_VIEW_ATTR_CLS_AE describes the attribute classifications of all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_ATTR_CLS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_ATTR_CLS_AE"

5.62 DBA_ANALYTIC_VIEW_BAS_MEAS

DBA_ANALYTIC_VIEW_BAS_MEAS is identical to DBA_ANALYTIC_VIEW_BASE_MEAS.

> **See Also:**
>
> "DBA_ANALYTIC_VIEW_BASE_MEAS"

5.63 DBA_ANALYTIC_VIEW_BAS_MEAS_AE

DBA_ANALYTIC_VIEW_BAS_MEAS_AE describes the base measures in all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_BAS_MEAS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_BAS_MEAS_AE"

5.64 DBA_ANALYTIC_VIEW_BASE_MEAS

DBA_ANALYTIC_VIEW_BASE_MEAS describes the base measures in all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_BASE_MEAS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_BASE_MEAS"

5.65 DBA_ANALYTIC_VIEW_CALC_MEAS

DBA_ANALYTIC_VIEW_CALC_MEAS describes the calculated measures in all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_CALC_MEAS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_CALC_MEAS"

5.66 DBA_ANALYTIC_VIEW_CLASS

DBA_ANALYTIC_VIEW_CLASS describes the classifications of all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_CLASS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_CLASS"

5.67 DBA_ANALYTIC_VIEW_CLASS_AE

DBA_ANALYTIC_VIEW_CLASS_AE describes the classifications of all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_CLASS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_CLASS_AE"

5.68 DBA_ANALYTIC_VIEW_CLC_MEAS

DBA_ANALYTIC_VIEW_CLC_MEAS is identical to DBA_ANALYTIC_VIEW_CALC_MEAS.

> **See Also:**
>
> "DBA_ANALYTIC_VIEW_CALC_MEAS"

5.69 DBA_ANALYTIC_VIEW_CLC_MEAS_AE

DBA_ANALYTIC_VIEW_CLC_MEAS_AE describes the calculated measures in all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_CLC_MEAS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_CLC_MEAS_AE"

5.70 DBA_ANALYTIC_VIEW_COLUMNS

DBA_ANALYTIC_VIEW_COLUMNS describes the columns of all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_COLUMNS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_COLUMNS"

5.71 DBA_ANALYTIC_VIEW_COLUMNS_AE

DBA_ANALYTIC_VIEW_COLUMNS_AE describes the columns of all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_COLUMNS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_COLUMNS_AE"

5.72 DBA_ANALYTIC_VIEW_DIM_ATRS

DBA_ANALYTIC_VIEW_DIM_ATRS is identical to DBA_ANALYTIC_VIEW_DIM_ATTRS.

> **See Also:**
>
> "DBA_ANALYTIC_VIEW_DIM_ATTRS"

5.73 DBA_ANALYTIC_VIEW_DIM_ATRS_AE

DBA_ANALYTIC_VIEW_DIM_ATRS_AE describes the attributes of the attribute dimensions in all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_DIM_ATRS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_DIM_ATRS_AE"

5.74 DBA_ANALYTIC_VIEW_DIM_ATTRS

DBA_ANALYTIC_VIEW_DIM_ATTRS describes the attributes of all attribute dimensions in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_DIM_ATTRS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_DIM_ATTRS"

5.75 DBA_ANALYTIC_VIEW_DIM_CLASS

DBA_ANALYTIC_VIEW_DIM_CLASS describes the classifications of the attribute dimensions in all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_DIM_CLASS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_DIM_CLASS"

5.76 DBA_ANALYTIC_VIEW_DIM_CLS

DBA_ANALYTIC_VIEW_DIM_CLS is identical to DBA_ANALYTIC_VIEW_DIM_CLASS.

> **See Also:**
>
> "DBA_ANALYTIC_VIEW_DIM_CLASS"

5.77 DBA_ANALYTIC_VIEW_DIM_CLS_AE

DBA_ANALYTIC_VIEW_DIM_CLS_AE describes the classifications of the attribute dimensions in all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_DIM_CLS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_DIM_CLS_AE"

5.78 DBA_ANALYTIC_VIEW_DIMENSIONS

DBA_ANALYTIC_VIEW_DIMENSIONS describes the attribute dimensions in all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_DIMENSIONS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_DIMENSIONS"

5.79 DBA_ANALYTIC_VIEW_DIMS

DBA_ANALYTIC_VIEW_DIMS is identical to DBA_ANALYTIC_VIEW_DIMENSIONS.

> **See Also:**
>
> "DBA_ANALYTIC_VIEW_DIMENSIONS"

5.80 DBA_ANALYTIC_VIEW_DIMS_AE

DBA_ANALYTIC_VIEW_DIMS_AE describes the attribute dimensions in all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_DIMS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_DIMS_AE"

5.81 DBA_ANALYTIC_VIEW_FACT_COLS

DBA_ANALYTIC_VIEW_FACT_COLS describes the fact columns of all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_FACT_COLS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_FACT_COLS"

5.82 DBA_ANALYTIC_VIEW_FCT_COLS

DBA_ANALYTIC_VIEW_FCT_COLS is identical to DBA_ANALYTIC_VIEW_FACT_COLS.

> **See Also:**
>
> "DBA_ANALYTIC_VIEW_FACT_COLS"

5.83 DBA_ANALYTIC_VIEW_FCT_COLS_AE

DBA_ANALYTIC_VIEW_FCT_COLS_AE describes the fact columns of all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_FCT_COLS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_FCT_COLS_AE"

5.84 DBA_ANALYTIC_VIEW_HIER_CLASS

DBA_ANALYTIC_VIEW_HIER_CLASS describes the classifications of the hierarchies in all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_HIER_CLASS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_HIER_CLASS"

5.85 DBA_ANALYTIC_VIEW_HIER_CLS

DBA_ANALYTIC_VIEW_HIER_CLS is identical to DBA_ANALYTIC_VIEW_HIER_CLASS.

> **See Also:**
>
> "DBA_ANALYTIC_VIEW_HIER_CLASS"

5.86 DBA_ANALYTIC_VIEW_HIER_CLS_AE

DBA_ANALYTIC_VIEW_HIER_CLS_AE describes the classifications of the hierarchies in all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_HIER_CLS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_HIER_CLS_AE"

5.87 DBA_ANALYTIC_VIEW_HIERS

DBA_ANALYTIC_VIEW_HIERS describes the hierarchies in all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_HIERS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_HIERS"

5.88 DBA_ANALYTIC_VIEW_HIERS_AE

DBA_ANALYTIC_VIEW_HIERS_AE describes the hierarchies in all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_HIERS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_HIERS_AE"

5.89 DBA_ANALYTIC_VIEW_KEYS

DBA_ANALYTIC_VIEW_KEYS describes the key columns of the attribute dimensions in all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_KEYS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_KEYS"

5.90 DBA_ANALYTIC_VIEW_KEYS_AE

DBA_ANALYTIC_VIEW_KEYS_AE describes the key columns of the attribute dimensions in all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_KEYS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_KEYS_AE"

5.91 DBA_ANALYTIC_VIEW_LEVEL_CLASS

DBA_ANALYTIC_VIEW_LEVEL_CLASS describes the level classifications of all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_LEVEL_CLASS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_LEVEL_CLASS"

5.92 DBA_ANALYTIC_VIEW_LEVELS

DBA_ANALYTIC_VIEW_LEVELS describes the levels in the hierarchies in all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_LEVELS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_LEVELS"

5.93 DBA_ANALYTIC_VIEW_LEVELS_AE

DBA_ANALYTIC_VIEW_LEVELS_AE describes the levels in the hierarchies in all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_LEVELS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_LEVELS_AE"

5.94 DBA_ANALYTIC_VIEW_LVL_CLS

DBA_ANALYTIC_VIEW_LVL_CLS is identical to DBA_ANALYTIC_VIEW_LEVEL_CLASS.

> **See Also:**
>
> "DBA_ANALYTIC_VIEW_LEVEL_CLASS"

5.95 DBA_ANALYTIC_VIEW_LVL_CLS_AE

DBA_ANALYTIC_VIEW_LVL_CLS_AE describes the level classifications of all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_LVL_CLS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_LVL_CLS_AE"

5.96 DBA_ANALYTIC_VIEW_LVLGRPS

DBA_ANALYTIC_VIEW_LVLGRPS describes the analytic view measure and level groups of all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_LVLGRPS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_LVLGRPS"

5.97 DBA_ANALYTIC_VIEW_LVLGRPS_AE

DBA_ANALYTIC_VIEW_LVLGRPS_AE describes the analytic view measure and level groups of all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_LVLGRPS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_LVLGRPS_AE"

5.98 DBA_ANALYTIC_VIEW_MEAS_CLASS

DBA_ANALYTIC_VIEW_MEAS_CLASS describes the classifications of the measures of all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_MEAS_CLASS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_MEAS_CLASS"

5.99 DBA_ANALYTIC_VIEW_MEAS_CLS

DBA_ANALYTIC_VIEW_MEAS_CLS is identical to DBA_ANALYTIC_VIEW_MEAS_CLASS.

> **See Also:**
>
> "DBA_ANALYTIC_VIEW_MEAS_CLASS"

5.100 DBA_ANALYTIC_VIEW_MEAS_CLS_AE

DBA_ANALYTIC_VIEW_MEAS_CLS_AE describes the classifications of the measures of all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEW_MEAS_CLS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_MEAS_CLS_AE"

5.101 DBA_ANALYTIC_VIEWS

DBA_ANALYTIC_VIEWS describes all analytic views in the database. Its columns are the same as those in ALL_ANALYTIC_VIEWS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEWS"

5.102 DBA_ANALYTIC_VIEWS_AE

DBA_ANALYTIC_VIEWS_AE describes all analytic views (across all editions) in the database. Its columns are the same as those in ALL_ANALYTIC_VIEWS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEWS_AE"

5.103 DBA_ANNOTATION_VALUES

`DBA_ANNOTATION_VALUES` displays the values for all schema annotations in the database. Its columns are the same as those in `ALL_ANNOTATION_VALUES`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_ANNOTATION_VALUES"

5.104 DBA_ANNOTATIONS

`DBA_ANNOTATIONS` displays all schema annotations in the database. Its columns are the same as those in `ALL_ANNOTATIONS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_ANNOTATIONS"

5.105 DBA_ANNOTATIONS_USAGE

`DBA_ANNOTATIONS_USAGE` provides usage information about all schema annotations in the database. Its columns are the same as those in `ALL_ANNOTATIONS_USAGE`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_ANNOTATIONS_USAGE"

5.106 DBA_APP_ERRORS

DBA_APP_ERRORS displays errors raised when an application PDB synchronizes with an application in the application root.

This view displays errors raised during the last synchronization for each application.

Column	Datatype	NULL	Description
APP_NAME	VARCHAR2(128)		Name of the application whose statement was captured
APP_STATEMENT	CLOB		Application statement
ERRORNUM	NUMBER		Error number for the statement
ERRORMSG	VARCHAR2(4000)		Error message for the statement
SYNC_TIME	DATE	NOT NULL	Sync time for the statement
SYSTEM_IGNORABLE	VARCHAR2(1)		Indicates whether the error is a system-ignorable error (Y) or not (N)
USER_IGNORABLE	VARCHAR2(1)		Indicates whether the error is a user-ignorable error (Y) or not (N)

5.107 DBA_APP_ERRORS_HISTORY

DBA_APP_ERRORS_HISTORY displays the history of errors raised when an application PDB synchronizes with an application in the application root.

This view displays errors raised during the last 10 synchronizations for each application.

Column	Datatype	NULL	Description
APP_NAME	VARCHAR2(128)		Name of the application whose statement was captured
APP_STATEMENT	CLOB		Application statement
ERRORNUM	NUMBER		Error number for the statement
ERRORMSG	VARCHAR2(4000)		Error message for the statement
SYNC_TIME	TIMESTAMP(6)	NOT NULL	Sync time for the statement
SYSTEM_IGNORABLE	VARCHAR2(1)		Indicates whether the error is a system-ignorable error (Y) or not (N)
USER_IGNORABLE	VARCHAR2(1)		Indicates whether the error is a user-ignorable error (Y) or not (N)

5.108 DBA_APP_PATCHES

DBA_APP_PATCHES describes all the application patches in the Application Container.

Column	Datatype	NULL	Description
APP_NAME	VARCHAR2(128)		Name of the application
PATCH_NUMBER	NUMBER		Patch number
PATCH_MIN_VERSION	VARCHAR2(30)		Minimum application version for the patch
PATCH_STATUS	VARCHAR2(10)		Status of the patch
PATCH_COMMENT	VARCHAR2(4000)		Comment associated with the patch
PATCH_CHECKSUM	NUMBER		Checksum for the patch

5.109 DBA_APP_PDB_STATUS

DBA_APP_PDB_STATUS provides information about applications in all the application PDBs in the current application container. It provides this information when queried in the application root.

The view should be queried in the application root.

This view can be used to show which version of an application has been synced to which application PDBs.

Column	Datatype	NULL	Description
CON_UID	NUMBER		Unique ID of the PDB
APP_NAME	VARCHAR2(128)		Name of the application
APP_ID	NUMBER		Id of the application
APP_VERSION	VARCHAR2(30)		Version of the application
APP_STATUS	VARCHAR2(12)		Status of the application

5.110 DBA_APP_STATEMENTS

DBA_APP_STATEMENTS describes all statements from all the applications in the Application Container.

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n*=1 if the row originates in root)
STATEMENT_ID	NUMBER		Statement ID

Column	Datatype	NULL	Description
CAPTURE_TIME	DATE	NOT NULL	Time of capture of the application statement
APP_STATEMENT	CLOB		Application statement
APP_NAME	VARCHAR2(128)		Name of the application whose statement was captured
APP_STATUS	VARCHAR2(12)		Status of the application when the statement was captured
PATCH_NUMBER	NUMBER		Patch number of patch installation when the statement was captured
VERSION_NUMBER	NUMBER		Version number when the statement was captured
SESSION_ID	NUMBER		Unique session ID when the statement was captured
OPCODE	NUMBER	NOT NULL	Operation code indicating the statement type

5.111 DBA_APP_VERSIONS

DBA_APP_VERSIONS displays information about all application versions installed in an application container.

Column	Datatype	NULL	Description
APP_NAME	VARCHAR2(128)		Name of the application
APP_VERSION	VARCHAR2(30)		Version of the application
APP_VERSION_COMMENT	VARCHAR2(4000)		Comment associated with the application version
APP_VERSION_CHECKSUM	NUMBER		Checksum for the application version
APP_ROOT_CLONE_NAME	VARCHAR2(64)		Name of the application root clone that corresponds to the application
APP_VERSION_BEGIN_TIME	DATE		Begin time of the most recent sync of the application
APP_VERSION_END_TIME	DATE		End time of the most recent sync of the application
APP_VERSION_NUMBER	NUMBER		Version number of the application version

> **See Also:**
>
> *Oracle Multitenant Administrator's Guide* for more information about application containers

5.112 DBA_APPLICATION_ROLES

DBA_APPLICATION_ROLES describes all the roles that have authorization policy functions defined.

Related View

USER_APPLICATION_ROLES describes all the roles for the current user that have authorization policy functions defined.

Column	Datatype	NULL	Description
ROLE	VARCHAR2(128)	NOT NULL	Name of the application role
SCHEMA	VARCHAR2(128)	NOT NULL	Schema of the authorized package
PACKAGE	VARCHAR2(128)	NOT NULL	Name of the authorized package

> **See Also:**
>
> "USER_APPLICATION_ROLES"

5.113 DBA_APPLICATIONS

DBA_APPLICATIONS provides information about the applications in the current application container.

Column	Datatype	NULL	Description
APP_NAME	VARCHAR2(128)		Name of the application
APP_ID	NUMBER		ID of the application
APP_VERSION	VARCHAR2(30)		Version of the application
APP_STATUS	VARCHAR2(12)		Status of the application
APP_IMPLICIT	VARCHAR2(1)		Indicates whether the application is implicit (Y) or not (N)
APP_CAPTURE_SERVICE	VARCHAR2(64)		Service name used for the capture
APP_CAPTURE_MODULE	VARCHAR2(64)		Module name used for the capture

5.114 DBA_APPLY

DBA_APPLY displays information about all apply processes in the database. Its columns are the same as those in ALL_APPLY.

> **See Also:**
>
> "ALL_APPLY"

5.115 DBA_APPLY_CHANGE_HANDLERS

DBA_APPLY_CHANGE_HANDLERS displays information about the change handlers on all tables in the database. Its columns are the same as those in ALL_APPLY_CHANGE_HANDLERS.

> **See Also:**
>
> "ALL_APPLY_CHANGE_HANDLERS"

5.116 DBA_APPLY_CONFLICT_COLUMNS

DBA_APPLY_CONFLICT_COLUMNS displays information about the conflict handlers on all tables in the database. Its columns are the same as those in ALL_APPLY_CONFLICT_COLUMNS.

> **See Also:**
>
> "ALL_APPLY_CONFLICT_COLUMNS"

5.117 DBA_APPLY_DML_CONF_HANDLERS

DBA_APPLY_DML_CONF_HANDLERS provides details about DML conflict handlers. Its columns are the same as those in ALL_APPLY_DML_CONF_HANDLERS.

> **See Also:**
>
> "ALL_APPLY_DML_CONF_HANDLERS"

5.118 DBA_APPLY_DML_HANDLERS

DBA_APPLY_DML_HANDLERS displays information about the DML handlers on all tables in the database. Its columns are the same as those in ALL_APPLY_DML_HANDLERS.

> **See Also:**
>
> "ALL_APPLY_DML_HANDLERS"

5.119 DBA_APPLY_ENQUEUE

DBA_APPLY_ENQUEUE displays information about the apply enqueue actions for all rules in the database. Its columns are the same as those in ALL_APPLY_ENQUEUE.

> **See Also:**
>
> "ALL_APPLY_ENQUEUE"

5.120 DBA_APPLY_ERROR

DBA_APPLY_ERROR displays information about the error transactions generated by all apply processes in the database. Its columns are the same as those in ALL_APPLY_ERROR.

> **See Also:**
>
> "ALL_APPLY_ERROR"

5.121 DBA_APPLY_ERROR_MESSAGES

DBA_APPLY_ERROR_MESSAGES displays information about the individual messages in all of the error transactions generated by all apply processes in the database. Its columns are the same as those in ALL_APPLY_ERROR_MESSAGES.

For XStream inbound servers, each message in an error transaction is an LCR.

> **Note:**
>
> - Messages that were spilled from memory to hard disk do not appear in this view.
> - This view does not contain information related to XStream outbound servers.

> **See Also:**
>
> "ALL_APPLY_ERROR_MESSAGES"

5.122 DBA_APPLY_EXECUTE

DBA_APPLY_EXECUTE displays information about the apply execute actions for all rules in the database. Its columns are the same as those in ALL_APPLY_EXECUTE.

> **See Also:**
>
> "ALL_APPLY_EXECUTE"

5.123 DBA_APPLY_HANDLE_COLLISIONS

DBA_APPLY_HANDLE_COLLISIONS provides details about apply handlers for collisions at the table level. Its columns are the same as those in ALL_APPLY_HANDLE_COLLISIONS.

> **See Also:**
>
> "ALL_APPLY_HANDLE_COLLISIONS"

5.124 DBA_APPLY_INSTANTIATED_GLOBAL

DBA_APPLY_INSTANTIATED_GLOBAL displays information about databases for which an instantiation SCN has been set. Its columns are the same as those in ALL_APPLY_INSTANTIATED_GLOBAL.

> **See Also:**
>
> "ALL_APPLY_INSTANTIATED_GLOBAL"

5.125 DBA_APPLY_INSTANTIATED_OBJECTS

DBA_APPLY_INSTANTIATED_OBJECTS displays information about objects for which an instantiation SCN has been set. Its columns are the same as those in ALL_APPLY_INSTANTIATED_OBJECTS.

> **See Also:**
>
> "ALL_APPLY_INSTANTIATED_OBJECTS"

5.126 DBA_APPLY_INSTANTIATED_SCHEMAS

DBA_APPLY_INSTANTIATED_SCHEMAS displays information about schemas for which an instantiation SCN has been set. Its columns are the same as those in ALL_APPLY_INSTANTIATED_SCHEMAS.

> **See Also:**
>
> "ALL_APPLY_INSTANTIATED_SCHEMAS"

5.127 DBA_APPLY_KEY_COLUMNS

DBA_APPLY_KEY_COLUMNS displays information about the substitute key columns for all tables in the database. Its columns are the same as those in ALL_APPLY_KEY_COLUMNS.

> **See Also:**
>
> "ALL_APPLY_KEY_COLUMNS"

5.128 DBA_APPLY_OBJECT_DEPENDENCIES

DBA_APPLY_OBJECT_DEPENDENCIES displays information about the object dependencies for all apply processes in the database.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object
PARENT_OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Parent of the object owner
PARENT_OBJECT_NAME	VARCHAR2(128)	NOT NULL	Parent of the named object

5.129 DBA_APPLY_PARAMETERS

DBA_APPLY_PARAMETERS displays information about the parameters for all apply processes in the database. Its columns are the same as those in ALL_APPLY_PARAMETERS.

> **See Also:**
>
> "ALL_APPLY_PARAMETERS"

5.130 DBA_APPLY_PROGRESS

DBA_APPLY_PROGRESS displays information about the progress made by all apply processes in the database. Its columns are the same as those in ALL_APPLY_PROGRESS.

> **See Also:**
>
> "ALL_APPLY_PROGRESS"

5.131 DBA_APPLY_REPERROR_HANDLERS

DBA_APPLY_REPERROR_HANDLERS provides details about apply reperror handlers. Its columns are the same as those in ALL_APPLY_REPERROR_HANDLERS.

> **See Also:**
>
> "ALL_APPLY_REPERROR_HANDLERS"

5.132 DBA_APPLY_SPILL_TXN

DBA_APPLY_SPILL_TXN displays information about the transactions spilled from memory to hard disk by all apply processes in the database.

Column	Datatype	NULL	Description
APPLY_NAME	VARCHAR2(128)	NOT NULL	Name of the apply process that spilled one or more transactions
XIDUSN	NUMBER	NOT NULL	Transaction ID undo segment number
XIDSLT	NUMBER	NOT NULL	Transaction ID slot number
XIDSQN	NUMBER	NOT NULL	Transaction ID sequence number
PDB_ID	NUMBER		PDB ID number
FIRST_SCN	NUMBER	NOT NULL	SCN of the first message in the transaction
MESSAGE_COUNT	NUMBER		Number of messages spilled for the transaction
FIRST_MESSAGE_CREATE_TIME	DATE		Source creation time of the first message in the transaction
SPILL_CREATION_TIME	DATE		Time the first message was spilled
FIRST_POSITION	RAW(64)		Position of the first message in this transaction. This column is populated only for an XStream inbound server.
TRANSACTION_ID	VARCHAR2(128)		Transaction ID of the spilled transaction

5.133 DBA_APPLY_TABLE_COLUMNS

DBA_APPLY_TABLE_COLUMNS displays, for all tables in the database, information about the nonkey table columns for which apply process conflict detection has been stopped for update and delete operations. Its columns are the same as those in ALL_APPLY_TABLE_COLUMNS.

> **See Also:**
>
> "ALL_APPLY_TABLE_COLUMNS"

5.134 DBA_APPLY_VALUE_DEPENDENCIES

DBA_APPLY_VALUE_DEPENDENCIES displays information about the value dependencies for all apply processes in the database.

Column	Datatype	NULL	Description
DEPENDENCY_NAME	VARCHAR2(128)	NOT NULL	Name of the dependency
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
COLUMN_POSITION	NUMBER		Position of the column

5.135 DBA_AQ_AGENT_PRIVS

DBA_AQ_AGENT_PRIVS displays information about the registered AQ agents that are mapped to all users in the database.

Related View

USER_AQ_AGENT_PRIVS displays information about the registered AQ agents that are mapped to the current user. This view does not display the DB_USERNAME column.

Column	Datatype	NULL	Description
AGENT_NAME	VARCHAR2(128)	NOT NULL	Name of the AQ agent
DB_USERNAME	VARCHAR2(128)		Name of the database user that the agent maps to
HTTP_ENABLED	VARCHAR2(4)		Indicates whether the agent is allowed to access AQ through HTTP (YES) or not (NO)
SMTP_ENABLED	VARCHAR2(4)		Indicates whether the agent is allowed to access AQ through SMTP (YES) or not (NO)

> **See Also:**
>
> "USER_AQ_AGENT_PRIVS"

5.136 DBA_AQ_AGENTS

DBA_AQ_AGENTS displays information about all registered AQ agents in the database.

Column	Datatype	NULL	Description
AGENT_NAME	VARCHAR2(128)	NOT NULL	Name of the AQ agent
HTTP_ENABLED	VARCHAR2(4)		Indicates whether the agent is allowed to access AQ through HTTP (YES) or not (NO)
SMTP_ENABLED	VARCHAR2(4)		Indicates whether the agent is allowed to access AQ through SMTP (YES) or not (NO)

5.137 DBA_ARGUMENTS

DBA_ARGUMENTS lists the arguments of the functions and procedures that are available in the database. Its columns are the same as those in ALL_ARGUMENTS.

> **See Also:**
>
> - "ALL_ARGUMENTS"
> - "DBA_PROCEDURES" for information about the functions and procedures that are available in the database

5.138 DBA_ASSEMBLIES

DBA_ASSEMBLIES provides information about all assemblies in the database. Its columns are the same as those in ALL_ASSEMBLIES.

> **See Also:**
>
> "ALL_ASSEMBLIES"

5.139 DBA_ASSOCIATIONS

`DBA_ASSOCIATIONS` describes all user-defined statistics in the database. Its columns are the same as those in `ALL_ASSOCIATIONS`.

> **See Also:**
>
> "ALL_ASSOCIATIONS"

5.140 DBA_ATTRIBUTE_DIM_ATTR_CLASS

`DBA_ATTRIBUTE_DIM_ATTR_CLASS` describes the attribute classifications of all attribute dimensions in the database. Its columns are the same as those in `ALL_ATTRIBUTE_DIM_ATTR_CLASS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ATTR_CLASS"

5.141 DBA_ATTRIBUTE_DIM_ATTR_CLS

`DBA_ATTRIBUTE_DIM_ATTR_CLS` is identical to `DBA_ATTRIBUTE_DIM_ATTR_CLASS`.

> **See Also:**
>
> "DBA_ATTRIBUTE_DIM_ATTR_CLASS"

5.142 DBA_ATTRIBUTE_DIM_ATTR_CLS_AE

`DBA_ATTRIBUTE_DIM_ATTR_CLS_AE` describes the attribute classifications of all attribute dimensions (across all editions) in the database. Its columns are the same as those in `ALL_ATTRIBUTE_DIM_ATTR_CLS_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ATTR_CLS_AE"

5.143 DBA_ATTRIBUTE_DIM_ATTRS

DBA_ATTRIBUTE_DIM_ATTRS describes the attributes of all attribute dimensions in the database. Its columns are the same as those in ALL_ATTRIBUTE_DIM_ATTRS.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ATTRS"

5.144 DBA_ATTRIBUTE_DIM_ATTRS_AE

DBA_ATTRIBUTE_DIM_ATTRS_AE describes the attributes of all attribute dimensions (across all editions) in the database. Its columns are the same as those in ALL_ATTRIBUTE_DIM_ATTRS_AE.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ATTRS_AE"

5.145 DBA_ATTRIBUTE_DIM_CLASS

DBA_ATTRIBUTE_DIM_CLASS describes the classifications of all attribute dimensions in the database. Its columns are the same as those in ALL_ATTRIBUTE_DIM_CLASS.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_CLASS"

5.146 DBA_ATTRIBUTE_DIM_CLASS_AE

DBA_ATTRIBUTE_DIM_CLASS_AE describes the classifications of all attribute dimensions (across all editions) in the database. Its columns are the same as those in ALL_ATTRIBUTE_DIM_CLASS_AE.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_CLASS_AE"

5.147 DBA_ATTRIBUTE_DIM_JN_PTHS

DBA_ATTRIBUTE_DIM_JN_PTHS is identical to DBA_ATTRIBUTE_DIM_JOIN_PATHS.

> **See Also:**
>
> "DBA_ATTRIBUTE_DIM_JOIN_PATHS"

5.148 DBA_ATTRIBUTE_DIM_JN_PTHS_AE

DBA_ATTRIBUTE_DIM_JN_PTHS_AE describes the join paths for all attribute dimensions (across all editions) in the database. Its columns are the same as those in ALL_ATTRIBUTE_DIM_JN_PTHS_AE.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_JN_PTHS_AE"

5.149 DBA_ATTRIBUTE_DIM_JOIN_PATHS

DBA_ATTRIBUTE_DIM_JOIN_PATHS describes the join paths for all attribute dimensions in the database. Its columns are the same as those in ALL_ATTRIBUTE_DIM_JOIN_PATHS.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_JOIN_PATHS"

5.150 DBA_ATTRIBUTE_DIM_KEYS

DBA_ATTRIBUTE_DIM_KEYS describes the keys of all attribute dimensions in the database. Its columns are the same as those in ALL_ATTRIBUTE_DIM_KEYS.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_KEYS"

5.151 DBA_ATTRIBUTE_DIM_KEYS_AE

`DBA_ATTRIBUTE_DIM_KEYS_AE` describes the keys of all attribute dimensions (across all editions) in the database. Its columns are the same as those in `ALL_ATTRIBUTE_DIM_KEYS_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_KEYS_AE"

5.152 DBA_ATTRIBUTE_DIM_LEVEL_ATTRS

`DBA_ATTRIBUTE_DIM_LEVEL_ATTRS` describes the attributes of the levels of all attribute dimensions in the database. Its columns are the same as those in `ALL_ATTRIBUTE_DIM_LEVEL_ATTRS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_LEVEL_ATTRS"

5.153 DBA_ATTRIBUTE_DIM_LEVELS

`DBA_ATTRIBUTE_DIM_LEVELS` describes the levels of all attribute dimensions in the database. Its columns are the same as those in `ALL_ATTRIBUTE_DIM_LEVELS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_LEVELS"

5.154 DBA_ATTRIBUTE_DIM_LEVELS_AE

`DBA_ATTRIBUTE_DIM_LEVELS_AE` describes the levels of all attribute dimensions (across all editions) in the database. Its columns are the same as those in `ALL_ATTRIBUTE_DIM_LEVELS_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_LEVELS_AE"

5.155 DBA_ATTRIBUTE_DIM_LVL_ATRS

DBA_ATTRIBUTE_DIM_LVL_ATRS is identical to DBA_ATTRIBUTE_DIM_LEVEL_ATTRS.

> **See Also:**
>
> "DBA_ATTRIBUTE_DIM_LEVEL_ATTRS"

5.156 DBA_ATTRIBUTE_DIM_LVL_ATRS_AE

DBA_ATTRIBUTE_DIM_LVL_ATRS_AE describes the attributes of the levels of all attribute dimensions (across all editions) in the database. Its columns are the same as those in ALL_ATTRIBUTE_DIM_LVL_ATRS_AE.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_LVL_ATRS_AE"

5.157 DBA_ATTRIBUTE_DIM_LVL_CLASS

DBA_ATTRIBUTE_DIM_LVL_CLASS describes the level classifications of all attribute dimensions in the database. Its columns are the same as those in ALL_ATTRIBUTE_DIM_LVL_CLASS.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_LVL_CLASS"

5.158 DBA_ATTRIBUTE_DIM_LVL_CLS

DBA_ATTRIBUTE_DIM_LVL_CLS is identical to DBA_ATTRIBUTE_DIM_LVL_CLASS.

> **See Also:**
>
> "DBA_ATTRIBUTE_DIM_LVL_CLASS"

5.159 DBA_ATTRIBUTE_DIM_LVL_CLS_AE

`DBA_ATTRIBUTE_DIM_LVL_CLS_AE` describes the level classifications of all attribute dimensions (across all editions) in the database. Its columns are the same as those in `ALL_ATTRIBUTE_DIM_LVL_CLS_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_LVL_CLS_AE"

5.160 DBA_ATTRIBUTE_DIM_ORD_ATRS

`DBA_ATTRIBUTE_DIM_ORD_ATRS` is identical to `DBA_ATTRIBUTE_DIM_ORDER_ATTRS`.

> **See Also:**
>
> "DBA_ATTRIBUTE_DIM_ORDER_ATTRS"

5.161 DBA_ATTRIBUTE_DIM_ORD_ATRS_AE

`DBA_ATTRIBUTE_DIM_ORD_ATRS_AE` describes the order attributes of all attribute dimensions (across all editions) in the database. Its columns are the same as those in `ALL_ATTRIBUTE_DIM_ORD_ATRS_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ORD_ATRS_AE"

5.162 DBA_ATTRIBUTE_DIM_ORDER_ATTRS

`DBA_ATTRIBUTE_DIM_ORDER_ATTRS` describes the order attributes of all attribute dimensions in the database. Its columns are the same as those in `ALL_ATTRIBUTE_DIM_ORDER_ATTRS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ORDER_ATTRS"

5.163 DBA_ATTRIBUTE_DIM_TABLES

`DBA_ATTRIBUTE_DIM_TABLES` describes the tables used by all attribute dimensions in the database. Its columns are the same as those in `ALL_ATTRIBUTE_DIM_TABLES`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_TABLES"

5.164 DBA_ATTRIBUTE_DIM_TABLES_AE

`DBA_ATTRIBUTE_DIM_TABLES_AE` describes the tables used by all attribute dimensions (across all editions) in the database. Its columns are the same as those in `ALL_ATTRIBUTE_DIM_TABLES_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_TABLES_AE"

5.165 DBA_ATTRIBUTE_DIMENSIONS

`DBA_ATTRIBUTE_DIMENSIONS` describes all attribute dimensions in the database. Its columns are the same as those in `ALL_ATTRIBUTE_DIMENSIONS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIMENSIONS"

5.166 DBA_ATTRIBUTE_DIMENSIONS_AE

`DBA_ATTRIBUTE_DIMENSIONS_AE` describes all attribute dimensions (across all editions) in the database. Its columns are the same as those in `ALL_ATTRIBUTE_DIMENSIONS_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIMENSIONS_AE"

5.167 DBA_ATTRIBUTE_TRANSFORMATIONS

DBA_ATTRIBUTE_TRANSFORMATIONS describes the transformation functions for all transformations in the database. Its columns are the same as those in ALL_ATTRIBUTE_TRANSFORMATIONS.

> **See Also:**
>
> "ALL_ATTRIBUTE_TRANSFORMATIONS"

5.168 DBA_AUDIT_EXISTS

DBA_AUDIT_EXISTS displays audit trail entries produced by AUDIT EXISTS and AUDIT NOT EXISTS.

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

Column	Datatype	NULL	Description
OS_USERNAME	VARCHAR2(255)		Operating system login username of the user whose actions were audited
USERNAME	VARCHAR2(128)		Name (not ID number) of the user whose actions were audited
USERHOST	VARCHAR2(128)		Client host machine name
TERMINAL	VARCHAR2(255)		Identifier of the user's terminal
TIMESTAMP	DATE		Date and time of the creation of the audit trail entry (date and time of user login for entries created by AUDIT SESSION) in the local database session time zone
OWNER	VARCHAR2(128)		Intended creator of the non-existent object
OBJ_NAME	VARCHAR2(128)		Name of the object affected by the action
ACTION_NAME	VARCHAR2(28)		Name of the action type corresponding to the numeric code in the ACTION column in DBA_AUDIT_TRAIL
NEW_OWNER	VARCHAR2(128)		Owner of the object named in the NEW_NAME column
NEW_NAME	VARCHAR2(128)		New name of an object after a RENAME or the name of the underlying object

Column	Datatype	NULL	Description
OBJ_PRIVILEGE	VARCHAR2(32)		Object privileges granted or revoked by a GRANT or REVOKE statement. The value of this column is a 32-character string of Y and dash (-) characters. Each character corresponds to a numbered privilege in the following list. The left-most character corresponds to privilege 0, the next character corresponds to privilege 1, and so on. The right-most character corresponds to privilege 31. 0 - ALTER 1 - AUDIT 2 - COMMENT 3 - DELETE 4 - GRANT 5 - INDEX 6 - INSERT 7 - LOCK 8 - CREATE 9 - SELECT 10 - UPDATE 11 - REFERENCES 12 - EXECUTE 13 - VIEW 14 - DROP 15 - ANALYZE 16 - CREATE 17 - READ 18 - WRITE 19 - KEEP SEQUENCE 20 - ENQUEUE 21 - DEQUEUE 22 - UNDER 23 - ON COMMIT 24 - REWRITE 25 - UPSERT 26 - DEBUG 27 - FLASHBACK 28 - MERGE 29 - USE 30 - FLASHBACK ARCHIVE 31 - DIRECTORY EXECUTE A Y indicates that the privilege was granted or revoked by the statement. A dash indicates that the privilege was not affected by the statement. For example, the following value indicates that the MERGE privilege was granted or revoked by the statement: ----------------------------Y---
SYS_PRIVILEGE	VARCHAR2(40)		System privileges granted or revoked by a GRANT or REVOKE statement

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)		Name of the grantee specified in a GRANT or REVOKE statement
SESSIONID	NUMBER	NOT NULL	Numeric ID for each Oracle session
ENTRYID	NUMBER	NOT NULL	Numeric ID for each audit trail entry in the session
STATEMENTID	NUMBER	NOT NULL	Numeric ID for each statement run
RETURNCODE	NUMBER	NOT NULL	Oracle error code generated by the action. Some useful values: • 0 - Action succeeded • 2004 - Security violation
CLIENT_ID	VARCHAR2(128)		Client identifier in each Oracle session
ECONTEXT_ID	VARCHAR2(64)		Application execution context identifier
SESSION_CPU	NUMBER		Amount of CPU time used by each Oracle session
EXTENDED_TIMESTAMP	TIMESTAMP(6) WITH TIME ZONE		Timestamp of the creation of the audit trail entry (timestamp of user login for entries created by AUDIT SESSION) in UTC (Coordinated Universal Time) time zone
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism
GLOBAL_UID	VARCHAR2(32)		Global user identifier for the user, if the user has logged in as an enterprise user
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OS_PROCESS	VARCHAR2(16)		Operating System process identifier of the Oracle process
TRANSACTIONID	RAW(8)		Transaction identifier of the transaction in which the object is accessed or modified
SCN	NUMBER		System change number (SCN) of the query
SQL_BIND	NVARCHAR2(2000)		Bind variable data of the query
SQL_TEXT	NVARCHAR2(2000)		SQL text of the query
OBJ_EDITION_NAME	VARCHAR2(128)		Name of the edition containing the audited object

Note:

The SQL_BIND and SQL_TEXT columns are only populated if the AUDIT_TRAIL initialization parameter is set to db, extended.

See Also:

"AUDIT_TRAIL"

5.169 DBA_AUDIT_MGMT_CLEAN_EVENTS

DBA_AUDIT_MGMT_CLEAN_EVENTS displays information about the history of audit trail cleanup or purge events.

Periodically, you should delete the contents of this view so that it will not grow too large.

> **Note:**
>
> This view is intended for use with traditional auditing (pre-Oracle Database 12c auditing) only, not for unified auditing.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

Column	Datatype	NULL	Description
AUDIT_TRAIL	VARCHAR2(28)		Audit trail that was cleaned at the time of the event: • STANDARD AUDIT TRAIL • FGA AUDIT TRAIL • STANDARD AND FGA AUDIT TRAIL • OS AUDIT TRAIL • XML AUDIT TRAIL • OS AND XML AUDIT TRAIL • ALL AUDIT TRAILS
RAC_INSTANCE	NUMBER	NOT NULL	Instance number indicating the Oracle RAC instance that was cleaned up at the time of the event; 0 implies not applicable
CLEANUP_TIME	TIMESTAMP(6) WITH TIME ZONE		Timestamp when the cleanup event completed
DELETE_COUNT	NUMBER		Number of audit records or audit files that were deleted at the time of the event
WAS_FORCED	VARCHAR2(3)		Indicates whether a forced cleanup occurred (YES) or not (NO); forced cleanup bypasses the last archive timestamp set

> **Note:**
>
> In a read-only database, including an Oracle Active Data Guard physical standby database, this view is not populated. Instead, a summary of cleanup events is written to the respective database instance's alert log file.

5.170 DBA_AUDIT_MGMT_CLEANUP_JOBS

DBA_AUDIT_MGMT_CLEANUP_JOBS displays information about the configured audit trail purge jobs.

> **Note:**
>
> This view is populated in any Oracle Database where auditing is enabled, regardless of whether pre-Oracle Database 12*c* auditing or unified auditing is enabled for the database.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

Column	Datatype	NULL	Description
JOB_NAME	VARCHAR2(100)	NOT NULL	Name of the audit trail purge job
JOB_STATUS	VARCHAR2(8)		Current status of the audit trail purge job (ENABLED) or (DISABLED)
AUDIT_TRAIL	VARCHAR2(28)		Audit trail for which the audit trail purge job is configured: • STANDARD AUDIT TRAIL • FGA AUDIT TRAIL • STANDARD AND FGA AUDIT TRAIL • OS AUDIT TRAIL • XML AUDIT TRAIL • OS AND XML AUDIT TRAIL • ALL AUDIT TRAILS • UNIFIED AUDIT TRAIL
JOB_FREQUENCY	VARCHAR2(100)		Frequency at which the audit trail purge job runs
USE_LAST_ARCHIVE_TIMESTAMP	VARCHAR2(3)		Indicates whether the audit trail purge job invocation uses the last archive timestamp. The last archive timestamp is shown in the LAST_ARCHIVE_TS column of the DBA_AUDIT_MGMT_LAST_ARCH_TS view. Possible values: • YES - Indicates that the audit trail purge job invocation uses the last archive timestamp • NO - Indicates that the audit trail purge job invocation does not use the last archive timestamp

Column	Datatype	NULL	Description
JOB_CONTAINER	VARCHAR2(7)		In a CDB, indicates whether audit trail purge job will be performed only in the current container or in all the containers. Possible values: • CURRENT - Indicates that audit trail purge job will be performed only in the current container • ALL - Indicates that audit trail purge job will be performed in all the containers In a non-CDB, the value in this column is always CURRENT.

> **See Also:**
>
> "DBA_AUDIT_MGMT_LAST_ARCH_TS"

5.171 DBA_AUDIT_MGMT_CONFIG_PARAMS

DBA_AUDIT_MGMT_CONFIG_PARAMS displays information about the currently configured audit trail properties that are used by the DBMS_AUDIT_MGMT PL/SQL package.

> **Note:**
>
> This view is populated in any Oracle Database where auditing is enabled, regardless of whether pre-Oracle Database 12*c* auditing or unified auditing is enabled for the database.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

Column	Datatype	NULL	Description
PARAMETER_NAME	VARCHAR2(1024)	NOT NULL	Name of the property
PARAMETER_VALUE	VARCHAR2(4000)		Value of the property
AUDIT_TRAIL	VARCHAR2(28)		Audit trails for which the property is configured: • STANDARD AUDIT TRAIL • FGA AUDIT TRAIL • STANDARD AND FGA AUDIT TRAIL • OS AUDIT TRAIL • XML AUDIT TRAIL • OS AND XML AUDIT TRAIL • ALL AUDIT TRAILS • UNIFIED AUDIT TRAIL

> **Note:**
>
> In a read-only database, including an Oracle Active Data Guard physical standby database, this view is not populated when the `DBMS_AUDIT_MGMT.SET_AUDIT_TRAIL` PL/SQL procedure is invoked. If the procedure was used when the database was in read-only mode, use `DBMS_AUDIT_MGMT.GET_AUDIT_TRAIL` to check the value of the property.

> **See Also:**
>
> *Oracle Database PL/SQL Packages and Types Reference* for more information about the parameters specified with the `DBMS_AUDIT_MGMT.SET_AUDIT_TRAIL_PROPERTY` procedure

5.172 DBA_AUDIT_MGMT_LAST_ARCH_TS

`DBA_AUDIT_MGMT_LAST_ARCH_TS` displays information about the last archive timestamps set for audit trail cleanup or purges.

> **Note:**
>
> This view is populated in any Oracle Database where auditing is enabled, regardless of whether pre-Oracle Database 12*c* auditing or unified auditing is enabled for the database.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

Column	Datatype	NULL	Description
`AUDIT_TRAIL`	`VARCHAR2(20)`		Audit trail for which the last archive timestamp applies: • `STANDARD AUDIT TRAIL` • `FGA AUDIT TRAIL` • `OS AUDIT TRAIL` • `XML AUDIT TRAIL` • `UNIFIED AUDIT TRAIL`
`RAC_INSTANCE`	`NUMBER`	`NOT NULL`	Oracle RAC instance number for which the last archive timestamp applies; `0` implies not applicable
`LAST_ARCHIVE_TS`	`TIMESTAMP(6) WITH TIME ZONE`		Timestamp of the last audit record or audit file that has been archived
`DATABASE_ID`	`NUMBER`	`NOT NULL`	Database ID of the audit records to clean up

Column	Datatype	NULL	Description
CONTAINER_GUID	VARCHAR2(33)	NOT NULL	GUID of the container of the audit records to clean up
DB_UNIQUE_NAME	VARCHAR2(257)	NOT NULL	Unique database name of the audited database, which is defined by the DB_UNIQUE_NAME initialization parameter. This value is useful for differentiating between the primary and standby databases in an Oracle Data Guard configuration.

Note:

In a read-only database, including an Oracle Active Data Guard physical standby database, this view is not populated when DBMS_AUDIT_MGMT.SET_LAST_ARCHIVE_TIMESTAMP is invoked. In such a case, use DBMS_AUDIT_MGMT.GET_LAST_ARCHIVE_TIMESTAMP to check for the timestamp, if it was configured for the database instance.

See Also:

Oracle Database PL/SQL Packages and Types Reference for more information about DBMS_AUDIT_MGMT subprograms

5.173 DBA_AUDIT_OBJECT

DBA_AUDIT_OBJECT displays audit trail records for all objects in the database.

Note:

This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

Related View

USER_AUDIT_OBJECT displays audit trail records for the objects accessible to the current user.

Column	Datatype	NULL	Description
OS_USERNAME	VARCHAR2(255)		Operating system login username of the user whose actions were audited
USERNAME	VARCHAR2(128)		Name (not ID number) of the user whose actions were audited

Column	Datatype	NULL	Description
USERHOST	VARCHAR2(128)		Client host machine name
TERMINAL	VARCHAR2(255)		Identifier of the user's terminal
TIMESTAMP	DATE		Date and time of the creation of the audit trail entry (date and time of user login for entries created by AUDIT SESSION) in the local database session time zone
OWNER	VARCHAR2(128)		Creator of the object affected by the action
OBJ_NAME	VARCHAR2(128)		Name of the object affected by the action
ACTION_NAME	VARCHAR2(28)		Name of the action type corresponding to the numeric code in the ACTION column in DBA_AUDIT_TRAIL
NEW_OWNER	VARCHAR2(128)		Owner of the object named in the NEW_NAME column
NEW_NAME	VARCHAR2(128)		New name of an object after a RENAME or the name of the underlying object
SES_ACTIONS	VARCHAR2(19)		Session summary (a string of 16 characters, one for each action type in the order ALTER, AUDIT, COMMENT, DELETE, GRANT, INDEX, INSERT, LOCK, RENAME, SELECT, UPDATE, REFERENCES, and EXECUTE). Positions 14, 15, and 16 are reserved for future use. The characters are: • - - None • S - Success • F - Failure • B - Both
COMMENT_TEXT	VARCHAR2(4000)		Text comment on the audit trail
SESSIONID	NUMBER	NOT NULL	Numeric ID for each Oracle session
ENTRYID	NUMBER	NOT NULL	Numeric ID for each audit trail entry in the session
STATEMENTID	NUMBER	NOT NULL	Numeric ID for each statement run
RETURNCODE	NUMBER	NOT NULL	Oracle error code generated by the action. Some useful values: • 0 - Action succeeded • 2004 - Security violation
PRIV_USED	VARCHAR2(40)		System privilege used to execute the action
CLIENT_ID	VARCHAR2(128)		Client identifier in each Oracle session
ECONTEXT_ID	VARCHAR2(64)		Application execution context identifier
SESSION_CPU	NUMBER		Amount of CPU time used by each Oracle session
EXTENDED_TIMESTAMP	TIMESTAMP(6) WITH TIME ZONE		Timestamp of the creation of the audit trail entry (timestamp of user login for entries created by AUDIT SESSION) in UTC (Coordinated Universal Time) time zone
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism
GLOBAL_UID	VARCHAR2(32)		Global user identifier for the user, if the user has logged in as an enterprise user

Column	Datatype	NULL	Description
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OS_PROCESS	VARCHAR2(16)		Operating System process identifier of the Oracle process
TRANSACTIONID	RAW(8)		Transaction identifier of the transaction in which the object is accessed or modified
SCN	NUMBER		System change number (SCN) of the query
SQL_BIND	NVARCHAR2(2000)		Bind variable data of the query
SQL_TEXT	NVARCHAR2(2000)		SQL text of the query
OBJ_EDITION_NAME	VARCHAR2(128)		Name of the edition containing the audited object

Note:

The SQL_BIND and SQL_TEXT columns are only populated if the AUDIT_TRAIL initialization parameter is set to db, extended.

See Also:

- "AUDIT_TRAIL"
- "USER_AUDIT_OBJECT"

5.174 DBA_AUDIT_POLICIES

DBA_AUDIT_POLICIES describes all fine-grained auditing policies in the database. Its columns are the same as those in ALL_AUDIT_POLICIES.

Note:

This view is populated only in an Oracle Database where unified auditing is not enabled. When unified auditing is enabled in Oracle Database, the audit records are populated in the new audit trail and can be viewed from UNIFIED_AUDIT_TRAIL.

- See *Oracle Database Security Guide* for more information about unified auditing.
- See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

> **See Also:**
>
> "ALL_AUDIT_POLICIES"

5.175 DBA_AUDIT_POLICY_COLUMNS

DBA_AUDIT_POLICY_COLUMNS describes all fine-grained auditing policy columns in the database. Its columns are the same as those in ALL_AUDIT_POLICY_COLUMNS.

> **Note:**
>
> This view is populated only in an Oracle Database where unified auditing is not enabled. When unified auditing is enabled in Oracle Database, the audit records are populated in the new audit trail and can be viewed from UNIFIED_AUDIT_TRAIL.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

> **See Also:**
>
> "ALL_AUDIT_POLICY_COLUMNS"

5.176 DBA_AUDIT_SESSION

DBA_AUDIT_SESSION displays all audit trail records concerning CONNECT and DISCONNECT.

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

Related View

USER_AUDIT_SESSION displays the audit trail records concerning connections and disconnections of the current user.

Column	Datatype	NULL	Description
OS_USERNAME	VARCHAR2(255)		Operating system login username of the user whose actions were audited
USERNAME	VARCHAR2(128)		Name (not ID number) of the user whose actions were audited
USERHOST	VARCHAR2(128)		Client host machine name
TERMINAL	VARCHAR2(255)		Identifier of the user's terminal
TIMESTAMP	DATE		Date and time of the creation of the audit trail entry (date and time of user login for entries created by AUDIT SESSION) in the local database session time zone
ACTION_NAME	VARCHAR2(28)		Name of the action type corresponding to the numeric code in the ACTION column in DBA_AUDIT_TRAIL
LOGOFF_TIME	DATE		Date and time of user log off
LOGOFF_LREAD	NUMBER		Logical reads for the session
LOGOFF_PREAD	NUMBER		Physical reads for the session
LOGOFF_LWRITE	NUMBER		Logical writes for the session
LOGOFF_DLOCK	VARCHAR2(40)		Deadlocks detected during the session
SESSIONID	NUMBER	NOT NULL	Numeric ID for each Oracle session
RETURNCODE	NUMBER	NOT NULL	Oracle error code generated by the action. Some useful values: • 0 - Action succeeded • 2004 - Security violation
CLIENT_ID	VARCHAR2(128)		Client identifier in each Oracle session
SESSION_CPU	NUMBER		Amount of CPU time used by each Oracle session (in centiseconds)
EXTENDED_TIMESTAMP	TIMESTAMP(6) WITH TIME ZONE		Timestamp of the creation of the audit trail entry (timestamp of user login for entries created by AUDIT SESSION) in UTC (Coordinated Universal Time) time zone
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism
GLOBAL_UID	VARCHAR2(32)		Global user identifier for the user, if the user has logged in as an enterprise user
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OS_PROCESS	VARCHAR2(16)		Operating System process identifier of the Oracle process

See Also:

"USER_AUDIT_SESSION"

5.177 DBA_AUDIT_STATEMENT

DBA_AUDIT_STATEMENT displays audit trail records for all GRANT, REVOKE, AUDIT, NOAUDIT, and ALTER SYSTEM statements in the database.

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

Related View

USER_AUDIT_STATEMENT displays audit trail records for the GRANT, REVOKE, AUDIT, NOAUDIT, and ALTER SYSTEM statements issued by the current user.

Column	Datatype	NULL	Description
OS_USERNAME	VARCHAR2(255)		Operating system login username of the user whose actions were audited
USERNAME	VARCHAR2(128)		Name (not ID number) of the user whose actions were audited
USERHOST	VARCHAR2(128)		Client host machine name
TERMINAL	VARCHAR2(255)		Identifier of the user's terminal
TIMESTAMP	DATE		Date and time of the creation of the audit trail entry (date and time of user login for entries created by AUDIT SESSION) in the local database session time zone
OWNER	VARCHAR2(128)		Creator of the object affected by the action
OBJ_NAME	VARCHAR2(128)		Name of the object affected by the action
ACTION_NAME	VARCHAR2(28)		Name of the action type corresponding to the numeric code in the ACTION column in DBA_AUDIT_TRAIL
NEW_NAME	VARCHAR2(128)		New name of an object after a RENAME or the name of the underlying object

Column	Datatype	NULL	Description
OBJ_PRIVILEGE	VARCHAR2(32)		Object privileges granted or revoked by a GRANT or REVOKE statement. The value of this column is a 32-character string of Y and dash (-) characters. Each character corresponds to a numbered privilege in the following list. The left-most character corresponds to privilege 0, the next character corresponds to privilege 1, and so on. The right-most character corresponds to privilege 31. 0 - ALTER 1 - AUDIT 2 - COMMENT 3 - DELETE 4 - GRANT 5 - INDEX 6 - INSERT 7 - LOCK 8 - CREATE 9 - SELECT 10 - UPDATE 11 - REFERENCES 12 - EXECUTE 13 - VIEW 14 - DROP 15 - ANALYZE 16 - CREATE 17 - READ 18 - WRITE 19 - KEEP SEQUENCE 20 - ENQUEUE 21 - DEQUEUE 22 - UNDER 23 - ON COMMIT 24 - REWRITE 25 - UPSERT 26 - DEBUG 27 - FLASHBACK 28 - MERGE 29 - USE 30 - FLASHBACK ARCHIVE 31 - DIRECTORY EXECUTE A Y indicates that the privilege was granted or revoked by the statement. A dash indicates that the privilege was not affected by the statement. For example, the following value indicates that the MERGE privilege was granted or revoked by the statement: ----------------------------Y---
SYS_PRIVILEGE	VARCHAR2(40)		System privileges granted or revoked by a GRANT or REVOKE statement

Column	Datatype	NULL	Description
ADMIN_OPTION	VARCHAR2(1)		Signifies the role or system privilege was granted with the ADMIN option
GRANTEE	VARCHAR2(128)		Name of the grantee specified in a GRANT or REVOKE statement
AUDIT_OPTION	VARCHAR2(40)		Auditing option set with the AUDIT statement
SES_ACTIONS	VARCHAR2(19)		Session summary (a string of 16 characters, one for each action type in the order ALTER, AUDIT, COMMENT, DELETE, GRANT, INDEX, INSERT, LOCK, RENAME, SELECT, UPDATE, REFERENCES, and EXECUTE). Positions 14, 15, and 16 are reserved for future use. The characters are: • - - None • S - Success • F - Failure • B - Both
COMMENT_TEXT	VARCHAR2(4000)		Text comment on the audit trail, inserted by the application
SESSIONID	NUMBER	NOT NULL	Numeric ID for each Oracle session
ENTRYID	NUMBER	NOT NULL	Numeric ID for each audit trail entry in the session
STATEMENTID	NUMBER	NOT NULL	Numeric ID for each statement run
RETURNCODE	NUMBER	NOT NULL	Oracle error code generated by the action. Some useful values: • 0 - Action succeeded • 2004 - Security violation
PRIV_USED	VARCHAR2(40)		System privilege used to execute the action
CLIENT_ID	VARCHAR2(128)		Client identifier in each Oracle session
ECONTEXT_ID	VARCHAR2(64)		Application execution context identifier
SESSION_CPU	NUMBER		Amount of CPU time used by each Oracle session
EXTENDED_TIMESTAMP	TIMESTAMP(6) WITH TIME ZONE		Timestamp of the creation of the audit trail entry (timestamp of user login for entries created by AUDIT SESSION) in UTC (Coordinated Universal Time) time zone
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism
GLOBAL_UID	VARCHAR2(32)		Global user identifier for the user, if the user has logged in as an enterprise user
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OS_PROCESS	VARCHAR2(16)		Operating System process identifier of the Oracle process
TRANSACTIONID	RAW(8)		Transaction identifier of the transaction in which the object is accessed or modified
SCN	NUMBER		System change number (SCN) of the query
SQL_BIND	NVARCHAR2(2000)		Bind variable data of the query
SQL_TEXT	NVARCHAR2(2000)		SQL text of the query
OBJ_EDITION_NAME	VARCHAR2(128)		Name of the edition containing the audited object

> **Note:**
>
> The SQL_BIND and SQL_TEXT columns are only populated if the AUDIT_TRAIL initialization parameter is set to db, extended.

> **See Also:**
>
> - "AUDIT_TRAIL"
> - "USER_AUDIT_STATEMENT"

5.178 DBA_AUDIT_TRAIL

DBA_AUDIT_TRAIL displays all standard audit trail entries.

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

Related View

USER_AUDIT_TRAIL displays the standard audit trail entries related to the current user.

Column	Datatype	NULL	Description
OS_USERNAME	VARCHAR2(255)		Operating system login username of the user whose actions were audited
USERNAME	VARCHAR2(128)		Name (not ID number) of the user whose actions were audited
USERHOST	VARCHAR2(128)		Client host machine name
TERMINAL	VARCHAR2(255)		Identifier of the user's terminal
TIMESTAMP	DATE		Date and time of the creation of the audit trail entry (date and time of user login for entries created by AUDIT SESSION) in the local database session time zone
OWNER	VARCHAR2(128)		Creator of the object affected by the action
OBJ_NAME	VARCHAR2(128)		Name of the object affected by the action
ACTION	NUMBER	NOT NULL	Numeric action type code. The corresponding name of the action type is in the ACTION_NAME column.

Column	Datatype	NULL	Description
ACTION_NAME	VARCHAR2(28)		Name of the action type corresponding to the numeric code in the ACTION column
NEW_OWNER	VARCHAR2(128)		Owner of the object named in the NEW_NAME column
NEW_NAME	VARCHAR2(128)		New name of the object after a RENAME or the name of the underlying object

Column	Datatype	NULL	Description
OBJ_PRIVILEGE	VARCHAR2(32)		Object privileges granted or revoked by a GRANT or REVOKE statement. The value of this column is a 32-character string of Y and dash (-) characters. Each character corresponds to a numbered privilege in the following list. The left-most character corresponds to privilege 0, the next character corresponds to privilege 1, and so on. The right-most character corresponds to privilege 31. 0 - ALTER 1 - AUDIT 2 - COMMENT 3 - DELETE 4 - GRANT 5 - INDEX 6 - INSERT 7 - LOCK 8 - CREATE 9 - SELECT 10 - UPDATE 11 - REFERENCES 12 - EXECUTE 13 - VIEW 14 - DROP 15 - ANALYZE 16 - CREATE 17 - READ 18 - WRITE 19 - KEEP SEQUENCE 20 - ENQUEUE 21 - DEQUEUE 22 - UNDER 23 - ON COMMIT 24 - REWRITE 25 - UPSERT 26 - DEBUG 27 - FLASHBACK 28 - MERGE 29 - USE 30 - FLASHBACK ARCHIVE 31 - DIRECTORY EXECUTE A Y indicates that the privilege was granted or revoked by the statement. A dash indicates that the privilege was not affected by the statement. For example, the following value indicates that the MERGE privilege was granted or revoked by the statement: ----------------------------Y---
SYS_PRIVILEGE	VARCHAR2(40)		System privileges granted or revoked by a GRANT or REVOKE statement

Column	Datatype	NULL	Description
ADMIN_OPTION	VARCHAR2(1)		Indicates whether the role or system privilege was granted with the ADMIN option
GRANTEE	VARCHAR2(128)		Name of the grantee specified in a GRANT or REVOKE statement
AUDIT_OPTION	VARCHAR2(40)		Auditing option set with the AUDIT statement
SES_ACTIONS	VARCHAR2(19)		Session summary (a string of 16 characters, one for each action type in the order ALTER, AUDIT, COMMENT, DELETE, GRANT, INDEX, INSERT, LOCK, RENAME, SELECT, UPDATE, REFERENCES, and EXECUTE). Positions 14, 15, and 16 are reserved for future use. The characters are: • - - None • S - Success • F - Failure • B - Both
LOGOFF_TIME	DATE		Date and time of user log off
LOGOFF_LREAD	NUMBER		Logical reads for the session
LOGOFF_PREAD	NUMBER		Physical reads for the session
LOGOFF_LWRITE	NUMBER		Logical writes for the session
LOGOFF_DLOCK	VARCHAR2(40)		Deadlocks detected during the session
COMMENT_TEXT	VARCHAR2(4000)		Text comment on the audit trail entry, providing more information about the statement audited Also indicates how the user or remote call was authenticated. The method can be one of the following: • DATABASE - Authentication was done by password • NETWORK - Authentication was done by Oracle Net Services or strong authentication • PROXY - Client was authenticated by another user; the name of the proxy user follows the method type When an object is accessed remotely over a database link, the COMMENT_TEXT column also captures the information about the database link. For example: `DBLINK_INFO: (SOURCE_GLOBAL_NAME=view02.regress.rdbms.dev.us.example.com, DBLINK_NAME=VIEW05_LINK.REGRESS.RDBMS.DEV.US.EXAMPLE.COM, SOURCE_AUDIT_SESSIONID=250805)`
SESSIONID	NUMBER	NOT NULL	Numeric ID for each Oracle session. Each user session gets a unique session ID.
ENTRYID	NUMBER	NOT NULL	Numeric ID for each audit trail entry in the session. The entry ID is an index of a session's audit entries that starts at 1 and increases to the number of entries that are written.

Column	Datatype	NULL	Description
STATEMENTID	NUMBER	NOT NULL	*n*th statement in the user session. The first SQL statement gets a value of 1 and the value is incremented for each subsequent SQL statement. Note that one SQL statement can create more than one audit trail entry (for example, when more than one object is audited from the same SQL statement), and in this case the statement ID remains the same for that statement and the entry ID increases for each audit trail entry created by the statement.
RETURNCODE	NUMBER	NOT NULL	Oracle error code generated by the action. Some useful values: • 0 - Action succeeded • 2004 - Security violation
PRIV_USED	VARCHAR2(40)		System privilege used to execute the action
CLIENT_ID	VARCHAR2(128)		Client identifier in each Oracle session
ECONTEXT_ID	VARCHAR2(64)		Application execution context identifier
SESSION_CPU	NUMBER		Amount of CPU time used by each Oracle session (in centiseconds)
EXTENDED_TIMESTAMP	TIMESTAMP(6) WITH TIME ZONE		Timestamp of the creation of the audit trail entry (timestamp of user login for entries created by AUDIT SESSION) in UTC (Coordinated Universal Time) time zone
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism
GLOBAL_UID	VARCHAR2(32)		Global user identifier for the user, if the user has logged in as an enterprise user
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OS_PROCESS	VARCHAR2(16)		Operating System process identifier of the Oracle process
TRANSACTIONID	RAW(8)		Transaction identifier of the transaction in which the object is accessed or modified
SCN	NUMBER		System change number (SCN) of the creation of the audit trail entry
SQL_BIND	NVARCHAR2(2000)		Bind variable data of the query
SQL_TEXT	NVARCHAR2(2000)		SQL text of the query
OBJ_EDITION_NAME	VARCHAR2(128)		Name of the edition containing the audited object
DBID	NUMBER		Database identifier of the audited database
RLS_INFO	CLOB		Stores virtual private database (VPD) policy names and predicates separated by delimiter. To format the output into individual rows, use the DBMS_AUDIT_UTIL.DECODE_RLS_INFO_ATRAIL_STD function.
CURRENT_USER	VARCHAR2(128)		Effective user for the statement execution

> **Note:**
>
> The SQL_BIND and SQL_TEXT columns are only populated if the AUDIT_TRAIL initialization parameter is set to db, extended.

> **See Also:**
>
> - "AUDIT_TRAIL"
> - "USER_AUDIT_TRAIL"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_AUDIT_UTIL.DECODE_RLS_INFO_ATRAIL_XML function.

5.179 DBA_AUTO_CLUSTERING_CONFIG

DBA_AUTO_CLUSTERING_CONFIG displays the current configuration parameter settings for automatic clustering.

Column	Datatype	NULL	Description
PARAMETER_NAME	VARCHAR2(128)	NOT NULL	Name of the configuration parameter
PARAMETER_VALUE	VARCHAR2(4000)		Value of the configuration parameter
LAST_UPDATED	TIMESTAMP(6) WITH TIME ZONE		Date and time at which the parameter value was last updated
UPDATED_BY	VARCHAR2(128)		User who last updated the parameter value
DESCRIPTION	VARCHAR2(73)		Brief description of the parameter

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

5.180 DBA_AUTO_CLUSTERING_RECOMMENDATIONS

DBA_AUTO_CLUSTERING_RECOMMENDATIONS displays recommendations associated with automatic clustering.

Column	Datatype	NULL	Description
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
RECOMMENDATION_ID	RAW(16)	NOT NULL	Unique ID representing the recommendation

Column	Datatype	NULL	Description
SQLSET_OWNER	VARCHAR2(128)		Owner of the SQL tuning set that is used for the recommendation
SQLSET_NAME	VARCHAR2(128)		Name of the SQL tuning set that is used for the recommendation
CLUSTERING_METHOD	VARCHAR2(8)		Recommended clustering method for the table. Possible values: • SINGLE - Single table clustering (clustering is based on columns from a single table) • JOIN - Join clustering (clustering is based on columns from two or more tables that are joined together) A null value means there is no recommended clustering method for the table.
CLUSTERING_DDL	VARCHAR2(4000)		DDL that was, or would be, used to apply the clustering recommendation to the table A null value means there is no clustering recommendation for the table.
ZONEMAP_DDL	VARCHAR2(4000)		DDL that was, or would be, used to apply the zone map recommendation to the table A null value means there is no zone map recommendation for the table.
APPLY_MODE	VARCHAR2(16)		Mode for the application of the recommendation. Possible values: • FULL - Data clustered using online redefinition • INCREMENTAL - Data clustered incrementally
APPLY_START_TIMESTAMP	TIMESTAMP(6) WITH TIME ZONE		Date and time at which the application of the recommendation started A null value means the recommendation was not applied.
APPLY_END_TIMESTAMP	TIMESTAMP(6) WITH TIME ZONE		Date and time at which the application of the recommendation finished A null value means either the recommendation was not applied or the application of the recommendation is not finished.
STATUS	VARCHAR2(16)	NOT NULL	Verification or application status. Possible values: • ACCEPTED • FAILED • IMPLEMENTED • REJECTED • UNVERIFIED

Note:

This view is available starting with Oracle Database 23ai.

5.181 DBA_AUTO_INDEX_CONFIG

DBA_AUTO_INDEX_CONFIG displays the current configuration parameter settings for automatic indexing.

You can set automatic indexing configuration parameters by using the DBMS_AUTO_INDEX.CONFIGURE procedure.

Column	Datatype	NULL	Description
PARAMETER_NAME	VARCHAR2(128)	NOT NULL	Name of the configuration parameter
PARAMETER_VALUE	VARCHAR2(4000)		Value of the configuration parameter
LAST_MODIFIED	TIMESTAMP(6)		Time at which the parameter value was last modified
MODIFIED_BY	VARCHAR2(128)		User who last modified the parameter value

See Also:

Oracle Database PL/SQL Packages and Types Reference for more information about the DBMS_AUTO_INDEX.CONFIGURE procedure

5.182 DBA_AUTO_MV_ANALYSIS_ACTIONS

DBA_AUTO_MV_ANALYSIS_ACTIONS displays information about analysis and tuning activities associated with automatic materialized views.

Each action is specified by the COMMAND and attribute (ATTR1 through ATTR6) columns. Each command defines how the attribute columns will be used.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task The value of this column is always SYS_AUTO_MV_TASK.
EXECUTION_NAME	VARCHAR2(128)		The name of the task execution with which this entry (row) is associated
REC_ID	NUMBER	NOT NULL	Recommendation associated with the action
ACTION_ID	NUMBER	NOT NULL	Unique identifier for the action
OBJECT_ID	NUMBER		Object associated with the action
COMMAND	VARCHAR2(64)		Command to be executed **See Also:** DBA_ADVISOR_COMMANDS for a list of commands

Column	Datatype	NULL	Description
COMMAND_ID	NUMBER	NOT NULL	ID of the command to be executed **See Also:** DBA_ADVISOR_COMMANDS for a list of commands
FLAGS	NUMBER		Advisor-specific flags
ATTR1	VARCHAR2(4000)		Parameters defining the command
ATTR2	VARCHAR2(4000)		Parameters defining the command
ATTR3	VARCHAR2(4000)		Parameters defining the command
ATTR4	VARCHAR2(4000)		Parameters defining the command
ATTR5	CLOB		Parameters defining the command; to be used if the text is significantly large (for example, a SQL statement defining a materialized view)
ATTR6	CLOB		Parameters defining the command; to be used if the text is significantly large (for example, a SQL statement defining a materialized view)
NUM_ATTR1	NUMBER		General numeric attribute
NUM_ATTR2	NUMBER		General numeric attribute
NUM_ATTR3	NUMBER		General numeric attribute
NUM_ATTR4	NUMBER		General numeric attribute
NUM_ATTR5	NUMBER		General numeric attribute
MESSAGE	VARCHAR2(4000)		Message associated with the action
FILTERED	VARCHAR2(1)		A value of Y means that the row in the view was filtered out by a directive (or a combination of directives). A value of N means that the row was not filtered.
RESULT_STATUS	VARCHAR2(25)		Result status. Possible values: • AUTOMATION PENDING • TIMED OUT • MISSING INFORMATION • COMPLETED WITH NO RESULTS • COMPLETED AND IMPLEMENTED • ENCOUNTERED ERROR • NOT AUTOMATED
RESULT_LAST_MODIFIED	TIMESTAMP(3)		Time at which result status was last modified
RESULT_MESSAGE	VARCHAR2(4000)		Result message text

5.183 DBA_AUTO_MV_ANALYSIS_EXECUTIONS

DBA_AUTO_MV_ANALYSIS_EXECUTIONS displays information about analysis and tuning executions associated with automatic materialized views.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task

Column	Datatype	NULL	Description
TASK_NAME	VARCHAR2(128)		Name of the task The value of this column is always SYS_AUTO_MV_TASK.
EXECUTION_NAME	VARCHAR2(128)	NOT NULL	Name of the task execution with which this entry (row) is associated
EXECUTION_ID	NUMBER	NOT NULL	Execution ID
DESCRIPTION	VARCHAR2(256)		User-supplied description of the task
EXECUTION_TYPE	VARCHAR2(128)		Type of the last execution (optional for single-execution tasks)
EXECUTION_TYPE#	NUMBER		Reserved for internal use
EXECUTION_START	DATE		Execution start date and time
EXECUTION_LAST_MODIFIED	DATE	NOT NULL	Last modified date and time for the execution
EXECUTION_END	DATE		Execution end date and time
REQUESTED_DOP	NUMBER		The degree of parallelism (DOP) value requested by the user (through the TEST_EXECUTE_DOP parameter). It can be any value greater or equal to zero.
ACTUAL_DOP	NUMBER		The actual degree of parallelism (DOP) with which the execution finished. If the requested DOP is greater than than what is available on the system, the ACTUAL_DOP value can be lower than the REQUESTED_DOP value.
CONCURRENT_EXECUTION	VARCHAR2(3)		Indicates whether concurrency was used for this execution (YES) or not (NO)
ADVISOR_NAME	VARCHAR2(128)		Advisor associated with the task
ADVISOR_ID	NUMBER	NOT NULL	Unique identifier for the advisor
STATUS	VARCHAR2(11)		Current operational status of the task: • EXECUTING • COMPLETED • INTERRUPTED • CANCELLED • FATAL ERROR
STATUS#	NUMBER	NOT NULL	Reserved for internal use
STATUS_MESSAGE	VARCHAR2(4000)		Informational message provided by the advisor regarding the status
ERROR_MESSAGE	VARCHAR2(4000)		Informational message or an error message indicating the current operation or condition

5.184 DBA_AUTO_MV_ANALYSIS_RECOMMENDATIONS

DBA_AUTO_MV_ANALYSIS_RECOMMENDATIONS displays recommendations associated with automatic materialized views.

Column	Datatype	NULL	Description
TASK_NAME	VARCHAR2(128)		Name of the task The value of this column is always SYS_AUTO_MV_TASK.
EXECUTION_NAME	VARCHAR2(128)	NOT NULL	The name of the task execution with which this entry (row) is associated
RECOMMENDATIONS	CLOB		Recommendation for the task

5.185 DBA_AUTO_MV_ANALYSIS_REPORT

DBA_AUTO_MV_ANALYSIS_REPORT reports on analyses and recommendations associated with automatic materialized views.

Column	Datatype	NULL	Description
TASK_NAME	VARCHAR2(128)		Name of the task The value of this column is always SYS_AUTO_MV_TASK.
EXECUTION_NAME	VARCHAR2(128)		The name of the task execution with which this entry (row) is associated
SEQUENCE	NUMBER	NOT NULL	Sequence number of the journal entry (unique for each task). This sequence number is used to order the data.
MESSAGE	VARCHAR2(4000)		Entry in the journal

5.186 DBA_AUTO_MV_ANALYSIS_TASK

DBA_AUTO_MV_ANALYSIS_TASK display analysis information associated with automatic materialized views.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_ID	NUMBER	NOT NULL	Unique identifier of the task
TASK_NAME	VARCHAR2(128)		Name of the task The value of this column is always SYS_AUTO_MV_TASK.
DESCRIPTION	VARCHAR2(256)		User-supplied description of the task
ADVISOR_NAME	VARCHAR2(128)		Advisor associated with the task
CREATED	DATE	NOT NULL	Creation date of the task
LAST_MODIFIED	DATE	NOT NULL	Date on which the task was last modified

Column	Datatype	NULL	Description
PARENT_TASK_ID	NUMBER		Identifier of the parent task (if the task was created because of the recommendation of another task)
PARENT_RXEC_ID	NUMBER		Identifier of the recommendation within the parent task that resulted in the creation of the task
LAST_EXECUTION	VARCHAR2(128)		Name of the current or last task execution
EXECUTION_TYPE	VARCHAR2(128)		Type of the last execution. This information is optional for single-execution tasks.
EXECUTION_TYPE#	NUMBER		Reserved for internal use
EXECUTION_DESCRIPTION	VARCHAR2(256)		Optional description of the last execution
EXECUTION_START	DATE		Execution start date and time of the task
EXECUTION_END	DATE		Execution end date and time of the task
STATUS	VARCHAR2(11)		Current operational status of the task: • INITIAL - Initial state of the task; no recommendations are present • EXECUTING - Task is currently running • INTERRUPTED - Task analysis was interrupted by the user. Recommendation data, if present, can be viewed and reported at this time. • COMPLETED - Task successfully completed the analysis operation. Recommendation data can be viewed and reported. • ERROR - An error occurred during the analysis operation. Recommendations, if present, can be viewed and reported at this time.
STATUS_MESSAGE	VARCHAR2(4000)		Informational message provided by the advisor regarding the status
PCT_COMPLETION_TIME	NUMBER		Percent completion, in terms of time, of the task when it is executing
PROGRESS_METRIC	NUMBER		Metric that measures the progress of the task in terms of quality. Each advisor may have its own metric.
METRIC_UNITS	VARCHAR2(64)		Unit of the metric used to measure progress
ACTIVITY_COUNTER	NUMBER		Counter that is updated frequently by the advisor, denoting that useful work is being performed
RECOMMENDATION_COUNT	NUMBER		Number of recommendations produced
ERROR_MESSAGE	VARCHAR2(4000)		Informational message or an error message indicating the current operation or condition
SOURCE	VARCHAR2(128)		Optional name that identifies the creator of the task
HOW_CREATED	VARCHAR2(30)		Optional task or template on which the object was based
READ_ONLY	VARCHAR2(5)		Indicates whether the task is read-only (TRUE) or not (FALSE)
SYSTEM_TASK	VARCHAR2(5)		Indicates whether the task is a system task (TRUE) or not (FALSE)
ADVISOR_ID	NUMBER	NOT NULL	Unique identifier for the advisor
STATUS#	NUMBER		Reserved for internal use

5.187 DBA_AUTO_MV_CONFIG

DBA_AUTO_MV_CONFIG displays configuration parameters associated with automatic materialized views and automatic zone maps.

The configuration parameters displayed in this view can be updated with CONFIGURE procedure of the DBMS_AUTO_MV package.

Column	Datatype	NULL	Description
PARAMETER_NAME	VARCHAR2(128)	NOT NULL	Name of the configuration parameter
PARAMETER_VALUE	VARCHAR2(4000)		Value of the configuration parameter
LAST_UPDATED	TIMESTAMP(6)		Date and time of the last parameter value update
UPDATED_BY	VARCHAR2(128)		User who last updated the parameter value
DESCRIPTION	VARCHAR2(72)		Description of the configuration parameter

See Also:

Oracle Database PL/SQL Packages and Types Reference for more information about the DBMS_AUTO_MV.CONFIGURE procedure

5.188 DBA_AUTO_MV_MAINT_REPORT

DBA_AUTO_MV_MAINT_REPORT displays maintenance operation details associated with automatic materialized view refresh.

Column	Datatype	NULL	Description
SWAT_MM_START_TIME	DATE		Date and time of the maintenance invocation
MESSAGE	VARCHAR2(4000)		Message associated with the materialized view maintenance action

5.189 DBA_AUTO_MV_REFRESH_HISTORY

DBA_AUTO_MV_REFRESH_HISTORY describes automatic materialized view refreshes.

Column	Datatype	NULL	Description
MVIEW_OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MVIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
SWAT_MM_START_TIME	DATE		Date and time of the maintenance invocation
REFRESH_START_TIME	DATE		Date and time the refresh started
REFRESH_END_TIME	DATE		Date and time the refresh ended
ELAPSED_REFRESH_TIME	NUMBER		Duration of the refresh (in seconds)

Column	Datatype	NULL	Description
STATUS	NUMBER		Status of the refresh. Possible values: • 0 - The refresh is in-progress • 1 - The refresh completed successfully • 2 - An error occurred during the refresh. Refer to the value of the ERROR column for more information. • 3 - The refresh was terminated
ERROR	NUMBER		If an error occurred during the refresh, this column displays the error number, which corresponds to error code ORA-*number*. Otherwise, the value of this column is 0.

5.190 DBA_AUTO_MV_VERIFICATION_REPORT

DBA_AUTO_MV_VERIFICATION_REPORT displays information about verifications associated with automatic materialized views.

Column	Datatype	NULL	Description
TASK_NAME	VARCHAR2(128)		Name of the task
EXECUTION_NAME	VARCHAR2(128)		The name of the task execution with which this entry (row) is associated
MESSAGE	VARCHAR2(4000)		Message associated with the inference

5.191 DBA_AUTO_MV_VERIFICATION_STATUS

DBA_AUTO_MV_VERIFICATION_STATUS displays the status of verifications associated with automatic materialized views.

Column	Datatype	NULL	Description
TASK_NAME	VARCHAR2(128)		Name of the task
EXECUTION_NAME	VARCHAR2(128)	NOT NULL	The name of the task execution with which this entry (row) is associated
STS_NAME_FOR_SRS	VARCHAR2(256)		Name of the SQL tuning set used for simple random sampling
STS_OWNER_NAME_FOR_SRS	CHAR(3)		Owner of the SQL tuning set used for simple random sampling
SPA_TASK_NAME_FOR_SRS	VARCHAR2(256)		Name of the SQL Performance Analyzer task used for simple random sampling
SPA_OWNER_NAME_FOR_SRS	CHAR(3)		Owner of the SQL Performance Analyzer task used for simple random sampling
STS_NAME_FOR_VERIFICATION	VARCHAR2(256)		Name of the SQL tuning set used for verification on sampled queries
STS_OWNER_NAME_FOR_VERIFICATION	CHAR(3)		Owner of the SQL tuning set used for verification on sampled queries

Column	Datatype	NULL	Description
SPA_TASK_NAME_FOR_VERIFICATION	VARCHAR2(256)		Name of the SQL Performance Analyzer task used for for verification on sampled queries
SPA_OWNER_NAME_FOR_VERIFICATION	CHAR(3)		Owner of the SQL Performance Analyzer task used for for verification on sampled queries
START_TIME	TIMESTAMP(6)		Date and time the verification started
END_TIME	TIMESTAMP(6)		Date and time the verification ended
STATUS	VARCHAR2(128)		Verification status

5.192 DBA_AUTO_SEGADV_CTL

DBA_AUTO_SEGADV_CTL exposes the control information used by the segment advisor.

This information gives the DBA an idea of what is happening in the auto advisor.

Column	Datatype	NULL	Description
AUTO_TASKID	NUMBER		Unique task ID generated by the auto advisor
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace containing the segment
SEGMENT_OWNER	VARCHAR2(128)		Owner of the segment
SEGMENT_NAME	VARCHAR2(128)		Name of the segment
SEGMENT_TYPE	VARCHAR2(18)		The type of segment (TABLE, INDEX, and so on)
PARTITION_NAME	VARCHAR2(128)		Name of the subsegment (if partitioned)
STATUS	VARCHAR2(40)		Status of the analysis: • NEW - the segment/tablespace has not been analyzed • BEING-PROCESSED - the segment/tablespace is being processed • COMPLETE - the segment/tablespace has been analyzed • ERROR - problem with the segment/tablespace
REASON	VARCHAR2(40)		Reason why this segment was chosen
REASON_VALUE	NUMBER		A value associated with the reason
CREATION_TIME	TIMESTAMP(6)		Time when this entry was created
PROCESSED_TASKID	NUMBER		Auto advisor task that was used to process the segment/tablespace
END_TIME	TIMESTAMP(6)		Time at which the advisor task was completed

5.193 DBA_AUTO_SEGADV_SUMMARY

DBA_AUTO_SEGADV_SUMMARY provides a summary of the auto advisor task runs.

Column	Datatype	NULL	Description
AUTO_TASKID	NUMBER	NOT NULL	Unique auto task ID

Column	Datatype	NULL	Description
SNAPID	NUMBER		Maximum AWR snapid used to process the segments
SEGMENTS_SELECTED	NUMBER		Number of segments chosen for analysis
SEGMENTS_PROCESSED	NUMBER		Number of segments actually processed
TABLESPACE_SELECTED	NUMBER		Number of tablespaces chosen for analysis
TABLESPACE_PROCESSED	NUMBER		Number of tablespaces actually processed
RECOMMENDATIONS_COUNT	NUMBER		Number of recommendations generated
START_TIME	TIMESTAMP(6)		Time at which the auto task was started
END_TIME	TIMESTAMP(6)		Time at which the auto task ended

5.194 DBA_AUTO_STAT_EXECUTIONS

DBA_AUTO_STAT_EXECUTIONS displays information about automatic optimizer statistics collection tasks, which are executed by the automated maintenance tasks infrastructure (known as AutoTask).

Column	Datatype	NULL	Description
OPID	NUMBER		Unique identifier for the execution of the task
ORIGIN	VARCHAR2(19)		Origin of the execution of the task. Possible values: • AUTO_TASK: A standard automatic optimizer statistics collection task, which is executed automatically in an Oracle Scheduler window, known as maintenance window • HIGH_FREQ_AUTO_TASK: A high-frequency automatic optimizer statistics collection task, which is executed at frequent intervals and complements the standard automatic optimizer statistics collection tasks
STATUS	VARCHAR2(49)		Status of the execution of the task. Possible values: • IN PROGRESS: The operation is currently running • COMPLETED: The operation has completed successfully • FAILED: The operation has failed • TIMED OUT: The operation timed out because the time allocated for the maintenance window was not sufficient for the operation to complete
START_TIME	TIMESTAMP(6) WITH TIME ZONE		Start time for the execution of the task
END_TIME	TIMESTAMP(6) WITH TIME ZONE		End time for the execution of the task
COMPLETED	NUMBER		Number of objects for which statistics collection was completed during the execution of the task

Column	Datatype	NULL	Description
FAILED	NUMBER		Number of objects for which statistics collection failed during the execution of the task
TIMED_OUT	NUMBER		Number of objects for which statistics collection timed out during the execution of the task
IN_PROGRESS	NUMBER		Number of objects for which statistics collection is in progress during the execution of the task

5.195 DBA_AUTO_ZONEMAP_CONFIG

DBA_AUTO_ZONEMAP_CONFIG describes the current settings for automatic zone map configuration parameters.

Column	Datatype	NULL	Description
PARAMETER_NAME	VARCHAR2(128)	NOT NULL	Parameter name
PARAMETER_VALUE	VARCHAR2(4000)		Parameter value
LAST_UPDATED	TIMESTAMP(6)		Time at which the parameter value was last updated
UPDATED_BY	VARCHAR2(128)		User who last updated the parameter value
DESCRIPTION	VARCHAR2(71)		Brief description of the parameter

5.196 DBA_AUTOTASK_CLIENT

DBA_AUTOTASK_CLIENT displays statistical data for each automated maintenance task over 7-day and 30-day periods.

Column	Datatype	NULL	Description
CLIENT_NAME	VARCHAR2(64)		Name of the client
STATUS	VARCHAR2(8)		Job status: • ENABLED • DISABLED
CONSUMER_GROUP	VARCHAR2(128)		Consumer group used for normal priority jobs for this client
CLIENT_TAG	VARCHAR2(2)		Tag used to identify jobs for this client
PRIORITY_OVERRIDE	VARCHAR2(7)		User-specified priority at which the task executes: • URGENT • HIGH • MEDIUM • LOW
ATTRIBUTES	VARCHAR2(4000)		Attributes of the client
WINDOW_GROUP	VARCHAR2(64)		Window group used to schedule jobs
SERVICE_NAME	VARCHAR2(64)		Name of the service on which jobs will execute for the client
RESOURCE_PERCENTAGE	NUMBER		Percentage of maintenance resources for high priority maintenance tasks for this client

Column	Datatype	NULL	Description
USE_RESOURCE_ESTIMATES	VARCHAR2(5)		Indicates whether resource estimates are used for this client (TRUE) or not (FALSE)
MEAN_JOB_DURATION	INTERVAL DAY(9) TO SECOND(9)		Average elapsed time for a job for this client (in seconds)
MEAN_JOB_CPU	INTERVAL DAY(9) TO SECOND(9)		Average CPU time for a job submitted by this client (in seconds)
MEAN_JOB_ATTEMPTS	NUMBER		Average number of attempts it takes to complete a task
MEAN_INCOMING_TASKS_7_DAYS	NUMBER		Average number of incoming tasks at the Maintenance Window Start over the last 7 days
MEAN_INCOMING_TASKS_30_DAYS	NUMBER		Average number of incoming tasks at the Maintenance Window Start over the last 30 days
TOTAL_CPU_LAST_7_DAYS	INTERVAL DAY(9) TO SECOND(9)		Cumulative CPU time used by the jobs for this client over the last 7 days (in seconds)
TOTAL_CPU_LAST_30_DAYS	INTERVAL DAY(9) TO SECOND(9)		Cumulative CPU time used by the jobs for this client over the last 30 days (in seconds)
MAX_DURATION_LAST_7_DAYS	INTERVAL DAY(3) TO SECOND(0)		Maximum elapsed time for a job over the last 7 days (in seconds)
MAX_DURATION_LAST_30_DAYS	INTERVAL DAY(3) TO SECOND(0)		Maximum elapsed time for a job over the last 30 days (in seconds)
WINDOW_DURATION_LAST_7_DAYS	INTERVAL DAY(9) TO SECOND(9)		Total time during which the client was active during the last 7 days
WINDOW_DURATION_LAST_30_DAYS	INTERVAL DAY(9) TO SECOND(9)		Total time during which the client was active during the last 30 days
LAST_CHANGE	TIMESTAMP(6) WITH TIME ZONE		Timestamp of last configuration change for the client
AUTOTASK_STATUS	VARCHAR2(8)		Status of the automated maintenance task subsystem: • ENABLED • DISABLED • ALLOWED

5.197 DBA_AUTOTASK_CLIENT_HISTORY

DBA_AUTOTASK_CLIENT_HISTORY displays per-window history of job execution counts for each automated maintenance task.

This information is viewable in the Job History page of Enterprise Manager.

Column	Datatype	NULL	Description
CLIENT_NAME	VARCHAR2(64)		Name of the client
WINDOW_NAME	VARCHAR2(261)		Name of the maintenance window
WINDOW_START_TIME	TIMESTAMP(6) WITH TIME ZONE		Maintenance window start time
WINDOW_DURATION	INTERVAL DAY(9) TO SECOND(6)		Window duration (NULL for currently open window)

Column	Datatype	NULL	Description
JOBS_CREATED	NUMBER		Number of jobs created on behalf of the client in this window
JOBS_STARTED	NUMBER		Number of jobs started on behalf of the client during the maintenance window
JOBS_COMPLETED	NUMBER		Number of jobs successfully completed on behalf of the client during the maintenance window
WINDOW_END_TIME	TIMESTAMP(6) WITH TIME ZONE		Window end time

5.198 DBA_AUTOTASK_CLIENT_JOB

DBA_AUTOTASK_CLIENT_JOB displays information about currently running Scheduler jobs created for automated maintenance tasks.

DBA_AUTOTASK_CLIENT_JOB provides information about some objects targeted by those jobs, as well as some additional statistics from previous instantiations of the same task. Some of this additional data is taken from generic Scheduler views.

Column	Datatype	NULL	Description
CLIENT_NAME	VARCHAR2(64)		Name of the client
JOB_NAME	VARCHAR2(65)		Name of the job
JOB_SCHEDULER_STATUS	VARCHAR2(15)		Job status: • DISABLED • RETRY SCHEDULED • SCHEDULED • RUNNING • COMPLETED • BROKEN • FAILED • REMOTE • SUCCEEDED • CHAIN_STALLED
TASK_NAME	VARCHAR2(64)		Name of the task being performed
TASK_TARGET_TYPE	VARCHAR2(64)		Type of the target being processed
TASK_TARGET_NAME	VARCHAR2(513)	NOT NULL	Name of the target
TASK_PRIORITY	VARCHAR2(7)		Priority of the task: • URGENT • HIGH • MEDIUM • LOW
TASK_OPERATION	VARCHAR2(64)		Operation performed on the object

5.199 DBA_AUTOTASK_JOB_HISTORY

DBA_AUTOTASK_JOB_HISTORY displays the history of automated maintenance task job runs. Jobs are added to this view after they finish executing.

Column	Datatype	NULL	Description
CLIENT_NAME	VARCHAR2(64)		Name of the automated maintenance client
WINDOW_NAME	VARCHAR2(261)		Name of the maintenance window
WINDOW_START_TIME	TIMESTAMP(6) WITH TIME ZONE		Start time of the maintenance window
WINDOW_DURATION	INTERVAL DAY(9) TO SECOND(6)		Duration of the maintenance window
JOB_NAME	VARCHAR2(261)		Name of the maintenance job
JOB_STATUS	VARCHAR2(30)		Status of the maintenance job
JOB_START_TIME	TIMESTAMP(6) WITH TIME ZONE		Start time of the maintenance job
JOB_DURATION	INTERVAL DAY(3) TO SECOND(0)		Duration of the maintenance job
JOB_ERROR	NUMBER		Error code for the job (if any)
JOB_INFO	VARCHAR2(4000)		Additional information about the job

5.200 DBA_AUTOTASK_OPERATION

DBA_AUTOTASK_OPERATION displays all automated maintenance task operations for each client.

Column	Datatype	NULL	Description
CLIENT_NAME	VARCHAR2(64)		Name of the client
OPERATION_NAME	VARCHAR2(64)		Name of the operation
OPERATION_TAG	VARCHAR2(3)		Tag for the operation
PRIORITY_OVERRIDE	VARCHAR2(7)		User-specified priority at which the task executes: • URGENT • HIGH • MEDIUM • LOW
ATTRIBUTES	VARCHAR2(4000)		Attributes of the operation
USE_RESOURCE_ESTIMATES	VARCHAR2(5)		Indicates whether resource usage estimates are used for the operation (TRUE) or not (FALSE)
STATUS	VARCHAR2(8)		Job status: • ENABLED • DISABLED
LAST_CHANGE	TIMESTAMP(6) WITH TIME ZONE		Timestamp of the last change

5.201 DBA_AUTOTASK_SCHEDULE

DBA_AUTOTASK_SCHEDULE displays the schedule of maintenance windows for the next 32 days for each client.

Column	Datatype	NULL	Description
WINDOW_NAME	VARCHAR2(128)		Name of the maintenance window
START_TIME	TIMESTAMP(6) WITH TIME ZONE		Projected start time of the window
DURATION	INTERVAL DAY(3) TO SECOND(0)		Currently defined duration of the window (NULL for the currently open window)

5.202 DBA_AUTOTASK_SCHEDULE_CONTROL

DBA_AUTOTASK_SCHEDULE_CONTROL displays the status of automated tasks.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Identifier of the database used by the task
TASK_ID	NUMBER	NOT NULL	Identifier of the task
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the task
TASK_NAME	VARCHAR2(64)		Name of the task
STATUS	VARCHAR2(10)		Status of the task Possible values: • FAILED • RUNNING • SCHEDULED • SKIPPED • SUCCEEDED • TERMINATED
ELAPSED_TIME	NUMBER		Elapsed time of the last execution (in seconds)
LAST_SCHEDULE_TIME	TIMESTAMP(3) WITH TIME ZONE		Last time the task was scheduled to execute
LAST_EXEC_INSTNUM	NUMBER		Oracle RAC instance number for the database instance used for the last execution of the task

5.203 DBA_AUTOTASK_SETTINGS

DBA_AUTOTASK_SETTINGS displays the settings for automated tasks.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Identifier of the database used by the task
TASK_ID	NUMBER	NOT NULL	Identifier of the task
TASK_NAME	VARCHAR2(64)		Name of the task
INTERVAL	NUMBER		The time interval between task invocations (in seconds)
MAX_RUN_TIME	NUMBER		Maximum run time allowed for the task before it is stopped (in seconds)
ENABLED	VARCHAR2(5)		Indicates whether the task is enabled (TRUE) or not (FALSE)

5.204 DBA_AUTOTASK_STATUS

DBA_AUTOTASK_STATUS displays status information for automated maintenance.

Column	Datatype	NULL	Description
STATUS	VARCHAR2(8)		Shows the status of automated maintenance. Possible values are: • ENABLED • DISABLED • ALLOWED • INVALID
LAST_CHANGE	TIMESTAMP(6) WITH TIME ZONE		Timestamp of last status change

5.205 DBA_AUTOTASK_TASK

DBA_AUTOTASK_TASK displays information about current and past automated maintenance tasks.

Column	Datatype	NULL	Description
CLIENT_NAME	VARCHAR2(64)		Name of the client
TASK_NAME	VARCHAR2(64)		Name of the task being performed
TASK_TARGET_TYPE	VARCHAR2(64)		Target type of the task
TASK_TARGET_NAME	VARCHAR2(513)	NOT NULL	Name of the target
OPERATION_NAME	VARCHAR2(64)		Operation performed on the object
ATTRIBUTES	VARCHAR2(4000)		Attributes of the task
TASK_PRIORITY	NUMBER		Task priority, relative to other tasks for this Client
PRIORITY_OVERRIDE	NUMBER		Task priority as overridden by the user
STATUS	VARCHAR2(8)		Status of the task: • DISABLED • DEFERRED • ENABLED
DEFERRED_WINDOW_NAME	VARCHAR2(65)		Appropriate window for this task
CURRENT_JOB_NAME	VARCHAR2(65)		Name of the currently scheduled job, if any
JOB_SCHEDULER_STATUS	VARCHAR2(15)		Job status: • DISABLED • RETRY SCHEDULED • SCHEDULED • RUNNING • COMPLETED • BROKEN • FAILED • REMOTE • SUCCEEDED • CHAIN_STALLED

Column	Datatype	NULL	Description
ESTIMATE_TYPE	VARCHAR2(7)		Type of resource estimates applied: • DERIVED • FORCED • LOCKED
ESTIMATED_WEIGHT	NUMBER		Task weight indicator
ESTIMATED_DURATION	NUMBER		Estimated elapsed time for the job (in seconds)
ESTIMATED_CPU_TIME	NUMBER		Estimated CPU time for the job (in seconds)
ESTIMATED_TEMP	NUMBER		Estimated temporary space usage for the job (in KB)
ESTIMATED_DOP	NUMBER		Estimated degree of parallelism for the job
ESTIMATED_IO_RATE	NUMBER		Estimated I/O utilization for the job (in KB per second)
ESTIMATED_UNDO_RATE	NUMBER		Estimated UNDO generation rate for the job (in KB per second)
RETRY_COUNT	NUMBER		Number of attempts to perform this task since the last successful attempt
LAST_GOOD_DATE	TIMESTAMP(6) WITH TIME ZONE		Timestamp of the last successful attempt to perform this task
LAST_GOOD_PRIORITY	NUMBER		Job priority of the last successful attempt to perform this task
LAST_GOOD_DURATION	NUMBER		Elapsed time (in seconds) of the last successful attempt to perform this task
LAST_GOOD_CPU_TIME	NUMBER		CPU time for the job (in seconds) of the last successful attempt to perform this task
LAST_GOOD_TEMP	NUMBER		Temporary space usage for the job (in KB) of the last successful attempt to perform this task
LAST_GOOD_DOP	NUMBER		Peak degree of parallelism for the job during the last successful attempt to perform this task
LAST_GOOD_IO_RATE	NUMBER		I/O utilization rate for the job (in KB per second) of the last successful attempt to perform this task
LAST_GOOD_UNDO_RATE	NUMBER		NDO generation rate (in KB per second) of the last successful attempt to perform this task
LAST_GOOD_CPU_WAIT	NUMBER		Resource Manager wait time (in seconds) of the last successful attempt to perform this task
LAST_GOOD_IO_WAIT	NUMBER		Resource Manager wait time (in seconds) of the last successful attempt to perform this task
LAST_GOOD_UNDO_WAIT	NUMBER		Resource Manager wait time (in seconds) of the last successful attempt to perform this task
LAST_GOOD_TEMP_WAIT	NUMBER		Resource Manager wait time (in seconds) of the last successful attempt to perform this task
LAST_GOOD_CONCURRENCY	NUMBER		Concurrency wait time (in seconds) of the last successful attempt to perform this task
LAST_GOOD_CONTENTION	NUMBER		Contention wait time (in seconds) of the last successful attempt to perform this task
NEXT_TRY_DATE	TIMESTAMP(6) WITH TIME ZONE		Next projected start time for the deferred maintenance window

Column	Datatype	NULL	Description
LAST_TRY_DATE	TIMESTAMP(6) WITH TIME ZONE		Time at which the task was last attempted
LAST_TRY_PRIORITY	NUMBER		Task priority at the time of the last attempt
LAST_TRY_RESULT	VARCHAR2(36)		Result code of the last execution of the task: • SUCCEEDED • FAILED • STOPPED BY USER ACTION • STOPPED AT END OF MAINTENANCE WINDOW • STOPPED AT INSTANCE SHUTDOWN • STOPPED
LAST_TRY_DURATION	NUMBER		Elapsed time of the last run (in seconds)
LAST_TRY_CPU_TIME	NUMBER		CPU time during the last run (in seconds)
LAST_TRY_TEMP	NUMBER		Temporary space usage for the job (in KB) for the last run
LAST_TRY_DOP	NUMBER		Peak degree of parallelism for the job during the last run
LAST_TRY_IO_RATE	NUMBER		I/O rate during the last run (in seconds)
LAST_TRY_UNDO_RATE	NUMBER		UNDO generation rate during the last run (in seconds)
LAST_TRY_CPU_WAIT	NUMBER		Time spent waiting for CPU during the last run (in seconds)
LAST_TRY_IO_WAIT	NUMBER		Time spent waiting for I/O during the last run (in seconds)
LAST_TRY_UNDO_WAIT	NUMBER		Time spent waiting for UNDO during the last run (in seconds)
LAST_TRY_TEMP_WAIT	NUMBER		Time spent waiting for temporary space during the last run (in seconds)
LAST_TRY_CONCURRENCY	NUMBER		Concurrency wait time during the last run (in seconds)
LAST_TRY_CONTENTION	NUMBER		Contention wait time during the last run (in seconds)
MEAN_GOOD_DURATION	NUMBER		Average elapsed time for successful executions of this task (in seconds)
MEAN_GOOD_CPU_TIME	NUMBER		Average CPU time for successful executions of this task (in seconds)
MEAN_GOOD_TEMP	NUMBER		Average temporary space usage for successful executions of this task (in KB)
MEAN_GOOD_DOP	NUMBER		Average peak degree of parallelism for successful executions of this task
MEAN_GOOD_IO	NUMBER		Average I/O utilization for successful executions of this task (in KB per second)
MEAN_GOOD_UNDO	NUMBER		Average UNDO generation rate for this task (in KB per second)
MEAN_GOOD_CPU_WAIT	NUMBER		Average time waiting for CPU for successful executions of this task (in seconds)
MEAN_GOOD_IO_WAIT	NUMBER		Average time waiting for I/O for successful executions of this task (in seconds)

Column	Datatype	NULL	Description
MEAN_GOOD_UNDO_WAIT	NUMBER		Average time waiting for UNDO for successful executions of this task (in seconds)
MEAN_GOOD_TEMP_WAIT	NUMBER		Average time waiting for temporary space for successful executions of this task (in seconds)
MEAN_GOOD_CONCURRENCY	NUMBER		Average concurrency wait time for successful executions of this task (in seconds)
MEAN_GOOD_CONTENTION	NUMBER		Average contention wait time for successful executions of this task (in seconds)
INFO_FIELD_1	VARCHAR2(4000)		Client-interpreted information
INFO_FIELD_2	CLOB		Client-interpreted information
INFO_FIELD_3	NUMBER		Client-interpreted information
INFO_FIELD_4	NUMBER		Client-interpreted information

5.206 DBA_AUTOTASK_WINDOW_CLIENTS

DBA_AUTOTASK_WINDOW_CLIENTS displays the windows that belong to MAINTENANCE_WINDOW_GROUP, along with the Enabled or Disabled status for the window for each maintenance task.

DBA_AUTOTASK_WINDOW_CLIENTS is primarily used by Enterprise Manager.

Column	Datatype	NULL	Description
WINDOW_NAME	VARCHAR2(128)	NOT NULL	Name of the maintenance window
WINDOW_NEXT_TIME	TIMESTAMP(6) WITH TIME ZONE		Next scheduled window open time unless the window is disabled
WINDOW_ACTIVE	VARCHAR2(5)		Indicates whether the window is currently active (open) (TRUE) or not (FALSE)
AUTOTASK_STATUS	VARCHAR2(8)		Status of the automated maintenance task subsystem: • ENABLED • DISABLED
OPTIMIZER_STATS	VARCHAR2(8)		Status of optimizer statistics gathering: • ENABLED • DISABLED
SEGMENT_ADVISOR	VARCHAR2(8)		Status of Segment Advisor: • ENABLED • DISABLED
SQL_TUNE_ADVISOR	VARCHAR2(8)		Status of SQL Tuning Advisor: • ENABLED • DISABLED

5.207 DBA_AUTOTASK_WINDOW_HISTORY

DBA_AUTOTASK_WINDOW_HISTORY displays historical information for automated maintenance task windows.

Column	Datatype	NULL	Description
WINDOW_NAME	VARCHAR2(261)		Name of the maintenance window
WINDOW_START_TIME	TIMESTAMP(6) WITH TIME ZONE		Window start time
WINDOW_END_TIME	TIMESTAMP(6) WITH TIME ZONE		Window end time

5.208 DBA_AW_PS

DBA_AW_PS describes the page spaces in all analytic workspaces in the database. Its columns are the same as those in ALL_AW_PS.

> **See Also:**
>
> "ALL_AW_PS"

5.209 DBA_AWS

DBA_AWS describes all analytic workspaces in the database. Its columns are the same as those in ALL_AWS.

> **See Also:**
>
> "ALL_AWS"

5.210 DBA_BASE_TABLE_MVIEWS

DBA_BASE_TABLE_MVIEWS describes all materialized views using materialized view logs in the database. Its columns are the same as those in ALL_BASE_TABLE_MVIEWS.

> **See Also:**
>
> "ALL_BASE_TABLE_MVIEWS"

5.211 DBA_BLOCKCHAIN_ROW_VERSION_COLS

DBA_BLOCKCHAIN_ROW_VERSION_COLS displays information about row versioned columns in all blockchain tables in the database. Its columns are the same as those in ALL_BLOCKCHAIN_ROW_VERSION_COLS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_BLOCKCHAIN_ROW_VERSION_COLS"

5.212 DBA_BLOCKCHAIN_ROW_VERSION_HISTORY

DBA_BLOCKCHAIN_ROW_VERSION_HISTORY provides a history of row versions in all blockchain tables in the database. Its columns are the same as those in ALL_BLOCKCHAIN_ROW_VERSION_HISTORY.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_BLOCKCHAIN_ROW_VERSION_HISTORY"

5.213 DBA_BLOCKCHAIN_TABLE_CHAINS

DBA_BLOCKCHAIN_TABLE_CHAINS displays system chain information for all blockchain tables in the database. Its columns are the same as those in ALL_BLOCKCHAIN_TABLE_CHAINS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_BLOCKCHAIN_TABLE_CHAINS"

5.214 DBA_BLOCKCHAIN_TABLE_EPOCHS

`DBA_BLOCKCHAIN_TABLE_EPOCHS` displays epoch information for all blockchain tables in the database. Its columns are the same as those in `ALL_BLOCKCHAIN_TABLE_EPOCHS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_BLOCKCHAIN_TABLE_EPOCHS"

5.215 DBA_BLOCKCHAIN_TABLE_HASH_COL_ORDER

`DBA_BLOCKCHAIN_TABLE_HASH_COL_ORDER` displays information about columns used to compute the cryptographic hash in all blockchain tables in the database. Its columns are the same as those in `ALL_BLOCKCHAIN_TABLE_HASH_COL_ORDER`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_BLOCKCHAIN_TABLE_HASH_COL_ORDER"

5.216 DBA_BLOCKCHAIN_TABLES

DBA_BLOCKCHAIN_TABLES describes all blockchain tables in the database. Its columns are the same as those in ALL_BLOCKCHAIN_TABLES.

> **See Also:**
>
> "ALL_BLOCKCHAIN_TABLES"

5.217 DBA_BLOCKER_RESOLVER_PARAMETERS

DBA_BLOCKER_RESOLVER_PARAMETERS shows the available user-tunable Blocker Resolver parameters and their values.

Column	Datatype	NULL	Description
NAME	VARCHAR2(40)	NOT NULL	String representation of the parameter name
CURRENT_VALUE	VARCHAR2(20)		String representation of the current parameter value
CURRENT_TIME	DATE		Time at which the current value was set
PREVIOUS_VALUE	VARCHAR2(20)		String representation of the previous parameter value
PREVIOUS_TIME	DATE		Time at which the previous value was set

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

5.218 DBA_BLOCKERS

DBA_BLOCKERS displays a session if it is not waiting for a locked object but is holding a lock on an object for which another session is waiting.

In an Oracle RAC environment, this only applies if the blocker is on the same instance.

Column	Datatype	NULL	Description
HOLDING_SESSION	NUMBER		Session holding a lock

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.219 DBA_CAPTURE

DBA_CAPTURE displays information about all capture processes in the database. Its columns are the same as those in ALL_CAPTURE.

> **See Also:**
>
> "ALL_CAPTURE"

5.220 DBA_CAPTURE_EXTRA_ATTRIBUTES

DBA_CAPTURE_EXTRA_ATTRIBUTES displays information about the extra attributes for all capture processes in the database. Its columns are the same as those in ALL_CAPTURE_EXTRA_ATTRIBUTES.

> **See Also:**
>
> "ALL_CAPTURE_EXTRA_ATTRIBUTES"

5.221 DBA_CAPTURE_PARAMETERS

DBA_CAPTURE_PARAMETERS displays information about the parameters for all capture processes in the database. Its columns are the same as those in ALL_CAPTURE_PARAMETERS.

> **See Also:**
>
> "ALL_CAPTURE_PARAMETERS"

5.222 DBA_CAPTURE_PREPARED_DATABASE

DBA_CAPTURE_PREPARED_DATABASE displays information about when the local database was prepared for instantiation. Its columns are the same as those in ALL_CAPTURE_PREPARED_DATABASE.

> **See Also:**
>
> "ALL_CAPTURE_PREPARED_DATABASE"

5.223 DBA_CAPTURE_PREPARED_SCHEMAS

DBA_CAPTURE_PREPARED_SCHEMAS displays information about all schemas prepared for instantiation at the local database. Its columns are the same as those in ALL_CAPTURE_PREPARED_SCHEMAS.

> **See Also:**
>
> "ALL_CAPTURE_PREPARED_SCHEMAS"

5.224 DBA_CAPTURE_PREPARED_TABLES

DBA_CAPTURE_PREPARED_TABLES displays information about all tables prepared for instantiation at the local database. Its columns are the same as those in ALL_CAPTURE_PREPARED_TABLES.

> **See Also:**
>
> "ALL_CAPTURE_PREPARED_TABLES"

5.225 DBA_CATALOG

DBA_CATALOG lists all tables, views, clusters, synonyms, and sequences in the database. Its columns are the same as those in ALL_CATALOG.

> **See Also:**
>
> "ALL_CATALOG"

5.226 DBA_CDB_RSRC_PLAN_DIRECTIVES

DBA_CDB_RSRC_PLAN_DIRECTIVES provides information about all the CDB resource plan directives.

> **Note:**
>
> ORA$DEFAULT_PDB_DIRECTIVE is the default directive for PDBs. For more information about ORA$DEFAULT_PDB_DIRECTIVE, see *Oracle Multitenant Administrator's Guide*.

Column	Datatype	NULL	Description
PLAN	VARCHAR2(128)		Name of the CDB resource plan to which this directive belongs
PLUGGABLE_DATABASE	VARCHAR2(128)		Name of the PDB referred to. NULL for profile directives
PROFILE	VARCHAR2(128)		For internal use only
DIRECTIVE_TYPE	VARCHAR2(30)		For internal use only
SHARES	NUMBER		Resource allocation, expressed in shares
UTILIZATION_LIMIT	NUMBER		Maximum resource utilization allowed, expressed in percentage
PARALLEL_SERVER_LIMIT	NUMBER		Maximum percentage of the parallel target used before queueing subsequent parallel queries
MEMORY_MIN	NUMBER		The percentage of Exadata Smart Flash Cache and Exadata PMEM cache that is guaranteed to the PDB This percentage is based on the total amount of space allocated to the CDB for Exadata Smart Flash Cache and Exadata PMEM cache. See *Oracle Exadata System Software User's Guide* for more information.
MEMORY_LIMIT	NUMBER		The maximum percentage of Exadata Smart Flash Cache and Exadata PMEM cache that the PDB can use This percentage is based on the total amount of space allocated to the CDB for Exadata Smart Flash Cache and Exadata PMEM cache. See *Oracle Exadata System Software User's Guide* for more information.
COMMENTS	VARCHAR2(2000)		Text comment on the resource plan directive
STATUS	VARCHAR2(128)		PENDING if it is part of the pending area, NULL otherwise
MANDATORY	VARCHAR2(3)		Whether the resource plan directive is mandatory. Mandatory plans cannot be deleted.

> **Note:**
>
> Oracle recommends that you do not use the `parallel_server_limit` directive in a CDB resource plan.

5.227 DBA_CDB_RSRC_PLANS

`DBA_CDB_RSRC_PLANS` provides information about all the CDB resource plans.

Column	Datatype	NULL	Description
`PLAN_ID`	`NUMBER`	`NOT NULL`	CDB resource plan ID
`PLAN`	`VARCHAR2(128)`		CDB resource plan name
`COMMENTS`	`VARCHAR2(2000)`		Text comment on the CDB resource plan
`STATUS`	`VARCHAR2(128)`		`PENDING` if it is part of the pending area, `NULL` otherwise
`MANDATORY`	`VARCHAR2(3)`		Whether the resource plan is mandatory. Mandatory plans cannot be deleted.

5.228 DBA_CERTIFICATES

`DBA_CERTIFICATES` displays all certificates in the database which are used for signature verification for blockchain tables. Its columns are the same as those in `ALL_CERTIFICATES`.

> **See Also:**
>
> "ALL_CERTIFICATES"

5.229 DBA_CHANGE_NOTIFICATION_REGS

`DBA_CHANGE_NOTIFICATION_REGS` describes all change notification registrations in the database.

Related View

`USER_CHANGE_NOTIFICATION_REGS` describes the change notification registrations owned by the current user. This view does not display the `USERNAME` column.

Column	Datatype	NULL	Description
`USERNAME`	`VARCHAR2(31)`		For invoker's rights units, the user creating the registration For definer's rights units, the owner of the registration

Column	Datatype	NULL	Description
REGID	NUMBER		Internal registration ID
REGFLAGS	NUMBER		Registration flags
CALLBACK	VARCHAR2(256)		Notification callback
OPERATIONS_FILTER	NUMBER		Operations filter (if specified)
CHANGELAG	NUMBER		Transaction lag between notifications (if specified)
TIMEOUT	NUMBER		Registration timeout (if specified)
TABLE_NAME	VARCHAR2(63)		Name of the registered table

> **See Also:**
>
> "USER_CHANGE_NOTIFICATION_REGS"

5.230 DBA_CHECKED_ROLES

DBA_CHECKED_ROLES lists the roles (without role grant paths) that are used for the role analysis policies reported by the DBMS__CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed role records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a role analysis policy
SEQUENCE	NUMBER	NOT NULL	The sequence number of the role analysis run during which the role was reported
OS_USER	VARCHAR2(128)		Operating system login username
USERHOST	VARCHAR2(128)		Client host machine name
MODULE	VARCHAR2(64)		Module name
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user whose role was reported
CHECKED_ROLE	VARCHAR2(128)		Checked role
RUN_NAME	VARCHAR2(128)		The name of the run during which the role was reported

> **See Also:**
>
> "DBA_CHECKED_ROLES_PATH"

5.231 DBA_CHECKED_ROLES_PATH

DBA_CHECKED_ROLES_PATH lists the roles that are used for the role analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed role records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a role analysis policy
SEQUENCE	NUMBER	NOT NULL	The sequence number of the role analysis run during which the role was reported
OS_USER	VARCHAR2(128)		Operating system login username
USERHOST	VARCHAR2(128)		Client host machine name
MODULE	VARCHAR2(64)		Module name
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user whose role was reported
CHECKED_ROLE	VARCHAR2(128)		Checked role
PATH	GRANT_PATH		Role grant paths
RUN_NAME	VARCHAR2(128)		The name of the run during which the role was reported

See Also:

"DBA_CHECKED_ROLES"

5.232 DBA_CLU_COLUMNS

DBA_CLU_COLUMNS maps all table columns to related cluster columns.

Related View

USER_CLU_COLUMNS maps all table columns owned by the current user to related cluster columns. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cluster
CLUSTER_NAME	VARCHAR2(128)	NOT NULL	Name of the cluster
CLU_COLUMN_NAME	VARCHAR2(128)	NOT NULL	Key column in the cluster
TABLE_NAME	VARCHAR2(128)	NOT NULL	Clustered table name
TAB_COLUMN_NAME	VARCHAR2(4000)		Key column or attribute of the object type column

> **See Also:**
>
> "USER_CLU_COLUMNS"

5.233 DBA_CLUSTER_HASH_EXPRESSIONS

`DBA_CLUSTER_HASH_EXPRESSIONS` lists hash functions for all hash clusters in the database. Its columns are the same as those in `ALL_CLUSTER_HASH_EXPRESSIONS`.

> **See Also:**
>
> "ALL_CLUSTER_HASH_EXPRESSIONS"

5.234 DBA_CLUSTERING_DIMENSIONS

`DBA_CLUSTERING_DIMENSIONS` describes dimension tables associated with all tables with an attribute clustering clause in the database. Its columns are the same as those in `ALL_CLUSTERING_DIMENSIONS`.

> **See Also:**
>
> - "ALL_CLUSTERING_DIMENSIONS"
> - *Oracle Database Data Warehousing Guide* for information about attribute clustering with zone maps

5.235 DBA_CLUSTERING_JOINS

`DBA_CLUSTERING_JOINS` describes joins to the dimension tables associated with all tables with an attribute clustering clause in the database. Its columns are the same as those in `ALL_CLUSTERING_JOINS`.

> **See Also:**
>
> - "ALL_CLUSTERING_JOINS"
> - *Oracle Database Data Warehousing Guide* for information about attribute clustering with zone maps

5.236 DBA_CLUSTERING_KEYS

`DBA_CLUSTERING_KEYS` describes clustering keys for all tables with an attribute clustering clause. Its columns are the same as those in `ALL_CLUSTERING_KEYS`.

> **See Also:**
>
> - "ALL_CLUSTERING_KEYS"
> - *Oracle Database Data Warehousing Guide* for information about attribute clustering with zone maps

5.237 DBA_CLUSTERING_TABLES

`DBA_CLUSTERING_TABLES` describes all the tables with an attribute clustering clause. Its columns are the same as those in `ALL_CLUSTERING_TABLES`.

> **See Also:**
>
> - "ALL_CLUSTERING_TABLES"
> - *Oracle Database Data Warehousing Guide* for information about attribute clustering with zone maps

5.238 DBA_CLUSTERS

`DBA_CLUSTERS` describes all clusters in the database. Its columns are the same as those in `ALL_CLUSTERS`.

> **Note:**
>
> "ALL_CLUSTERS"

5.239 DBA_CODE_ROLE_PRIVS

DBA_CODE_ROLE_PRIVS describes all the roles that are associated with program units in the database. Its columns are the same as those in ALL_CODE_ROLE_PRIVS.

> **See Also:**
>
> "ALL_CODE_ROLE_PRIVS"

5.240 DBA_COL_COMMENTS

DBA_COL_COMMENTS displays comments on the columns of all tables and views in the database. Its columns are the same as those in ALL_COL_COMMENTS.

> **See Also:**
>
> "ALL_COL_COMMENTS"

5.241 DBA_COL_PENDING_STATS

DBA_COL_PENDING_STATS describes the pending statistics of all columns in the database. Its columns are the same as those in ALL_COL_PENDING_STATS.

> **See Also:**
>
> "ALL_COL_PENDING_STATS"

5.242 DBA_COL_PRIVS

DBA_COL_PRIVS describes all column object grants in the database.

Related View

USER_COL_PRIVS describes the column object grants for which the current user is the object owner, grantor, or grantee.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)		Name of the user or role to whom access was granted
OWNER	VARCHAR2(128)		Owner of the object
TABLE_NAME	VARCHAR2(128)		Name of the object

Column	Datatype	NULL	Description
COLUMN_NAME	VARCHAR2(128)		Name of the column
GRANTOR	VARCHAR2(128)		Name of the user who performed the grant
PRIVILEGE	VARCHAR2(40)		Privilege on the column
GRANTABLE	VARCHAR2(3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the privilege grant was inherited from another container (YES) or not (NO)

See Also:

"USER_COL_PRIVS"

5.243 DBA_COLL_TYPES

DBA_COLL_TYPES describes all named collection types (arrays, nested tables, object tables, and so on) in the database. Its columns are the same as those in ALL_COLL_TYPES.

Note:

"ALL_COLL_TYPES"

5.244 DBA_COMMON_AUDIT_TRAIL

DBA_COMMON_AUDIT_TRAIL displays all standard and fine-grained audit trail entries, mandatory and SYS audit records written in XML format.

Note:

This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

Column	Datatype	NULL	Description
AUDIT_TYPE	VARCHAR2(22)		Audit trail type: • Standard Audit • Standard XML Audit • Fine Grained Audit • Fine Grained XML Audit • SYS XML Audit • Mandatory XML Audit
SESSION_ID	NUMBER		Numeric ID for the Oracle session
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism
STATEMENTID	NUMBER		Numeric ID for the statement run; a statement may cause multiple audit records
ENTRYID	NUMBER		Numeric ID for the audit trail entry in the session
EXTENDED_TIMESTAMP	TIMESTAMP(6) WITH TIME ZONE		Timestamp of the audited operation (timestamp of user login for entries created by AUDIT SESSION) in the session's time zone
GLOBAL_UID	VARCHAR2(32)		Global user identifier for the user, if the user has logged in as an enterprise user
DB_USER	VARCHAR2(128)		Database user name of the user whose actions were audited
CLIENT_ID	VARCHAR2(128)		Client identifier in the Oracle session
ECONTEXT_ID	VARCHAR2(64)		Application execution context identifier
EXT_NAME	VARCHAR2(4000)		User external name
OS_USER	VARCHAR2(255)		Operating system login user name of the user whose actions were audited
USERHOST	VARCHAR2(128)		Client host machine name
OS_PROCESS	VARCHAR2(16)		Operating system process identifier of the Oracle process
TERMINAL	VARCHAR2(255)		Identifier of the user's terminal
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OBJECT_SCHEMA	VARCHAR2(128)		Owner of the audited object
OBJECT_NAME	VARCHAR2(128)		Name of the object affected by the action
POLICY_NAME	VARCHAR2(128)		Name of the Fine-Grained Auditing Policy
NEW_OWNER	VARCHAR2(128)		Owner of the object named in the NEW_NAME column
NEW_NAME	VARCHAR2(128)		New name of the object after a RENAME or the name of the underlying object
ACTION	NUMBER		Numeric action type code. The corresponding name of the action type is in the STATEMENT_TYPE column.
STATEMENT_TYPE	VARCHAR2(28)		Name of the action type corresponding to the numeric code in the ACTION column
AUDIT_OPTION	VARCHAR2(40)		Auditing option set with the AUDIT statement

Column	Datatype	NULL	Description
TRANSACTIONID	RAW(8)		Transaction identifier of the transaction in which the object was accessed or modified
RETURNCODE	NUMBER		Oracle error code generated by the action (0 if the action succeeded)
SCN	NUMBER		System change number (SCN) of the query
COMMENT_TEXT	VARCHAR2(4000)		Text comment on the audit trail entry, providing more information about the statement audited Also indicates how the user was authenticated: • DATABASE - Authentication was done by password • NETWORK - Authentication was done by Oracle Net Services or the Advanced Networking Option • PROXY - Client was authenticated by another user. The name of the proxy user follows the method type.
SQL_BIND	NVARCHAR2(2000)		Bind variable data of the query
SQL_TEXT	NVARCHAR2(2000)		SQL text of the query

Column	Datatype	NULL	Description
OBJ_PRIVILEGE	VARCHAR2(32)		Object privileges granted or revoked by a GRANT or REVOKE statement. The value of this column is a 32-character string of Y and dash (-) characters. Each character corresponds to a numbered privilege in the following list. The left-most character corresponds to privilege 0, the next character corresponds to privilege 1, and so on. The right-most character corresponds to privilege 31. 0 - ALTER 1 - AUDIT 2 - COMMENT 3 - DELETE 4 - GRANT 5 - INDEX 6 - INSERT 7 - LOCK 8 - CREATE 9 - SELECT 10 - UPDATE 11 - REFERENCES 12 - EXECUTE 13 - VIEW 14 - DROP 15 - ANALYZE 16 - CREATE 17 - READ 18 - WRITE 19 - KEEP SEQUENCE 20 - ENQUEUE 21 - DEQUEUE 22 - UNDER 23 - ON COMMIT 24 - REWRITE 25 - UPSERT 26 - DEBUG 27 - FLASHBACK 28 - MERGE 29 - USE 30 - FLASHBACK ARCHIVE 31 - DIRECTORY EXECUTE A Y indicates that the privilege was granted or revoked by the statement. A dash indicates that the privilege was not affected by the statement. For example, the following value indicates that the MERGE privilege was granted or revoked by the statement: ----------------------------Y---
SYS_PRIVILEGE	VARCHAR2(40)		System privileges granted or revoked by a GRANT or REVOKE statement

Column	Datatype	NULL	Description
ADMIN_OPTION	VARCHAR2(1)		Indicates whether the role or system privilege was granted with the ADMIN option
OS_PRIVILEGE	VARCHAR2(7)		Operating privilege (SYSDBA or SYSOPER), if any, used in the session. If no privilege is used, it will be NONE.
GRANTEE	VARCHAR2(128)		Name of the grantee specified in a GRANT or REVOKE statement
PRIV_USED	VARCHAR2(40)		System privilege used to execute the action
SES_ACTIONS	VARCHAR2(19)		Session summary (a string of 16 characters, one for each action type in the order ALTER, AUDIT, COMMENT, DELETE, GRANT, INDEX, INSERT, LOCK, RENAME, SELECT, UPDATE, REFERENCES, and EXECUTE). Positions 14, 15, and 16 are reserved for future use. The characters are: • - - None • S - Success • F - Failure • B - Both
LOGOFF_TIME	DATE		Timestamp of user log off
LOGOFF_LREAD	NUMBER		Number of logical reads in the session
LOGOFF_PREAD	NUMBER		Number of physical reads in the session
LOGOFF_LWRITE	NUMBER		Number of logical writes for the session
LOGOFF_DLOCK	VARCHAR2(40)		Number of deadlocks detected during the session
SESSION_CPU	NUMBER		Amount of CPU time used by the Oracle session
OBJ_EDITION_NAME	VARCHAR2(128)		Name of the edition containing the audited object
DBID	NUMBER		Database identifier of the audited database
RLS_INFO	CLOB		Stores virtual private database (VPD) policy names and predicates separated by delmiter
COMMON_USER	VARCHAR2(128)		Effective user for the statement execution

Note:

The SQL_BIND and SQL_TEXT columns are only populated if the AUDIT_TRAIL initialization parameter is set to db, extended or xml, extended or if the AUDIT_SYS_OPERATIONS initialization parameter is set to TRUE.

See Also:

- "AUDIT_SYS_OPERATIONS"
- "AUDIT_TRAIL"

5.245 DBA_COMPARISON

DBA_COMPARISON displays information about all comparison objects in the database.

Related View

USER_COMPARISON displays information about the comparison objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the comparison
COMPARISON_NAME	VARCHAR2(128)	NOT NULL	Name of the comparison
COMPARISON_MODE	VARCHAR2(5)		Mode of the comparison: • TABLE
SCHEMA_NAME	VARCHAR2(128)		Schema name of the local object
OBJECT_NAME	VARCHAR2(128)		Name of the local object
OBJECT_TYPE	VARCHAR2(17)		Type of the local object: • TABLE • VIEW • SYNONYM • MATERIALIZED VIEW
REMOTE_SCHEMA_NAME	VARCHAR2(128)		Schema name of the remote object
REMOTE_OBJECT_NAME	VARCHAR2(128)		Name of the remote object
REMOTE_OBJECT_TYPE	VARCHAR2(17)		Type of the remote object: • TABLE • VIEW • SYNONYM • MATERIALIZED VIEW
DBLINK_NAME	VARCHAR2(128)		Database link name to the remote database
SCAN_MODE	VARCHAR2(9)		Scan mode of the comparison: FULL • FULL • RANDOM • CYCLIC • CUSTOM
SCAN_PERCENT	NUMBER		Scan percent of the comparison; applicable to random and cyclic modes
CYCLIC_INDEX_VALUE	VARCHAR2(4000)		Last index column value used in a cyclic scan
NULL_VALUE	VARCHAR2(4000)		Value to use for NULL columns
LOCAL_CONVERGE_TAG	RAW(2000)		Local Replication tag used while performing converge DMLs
REMOTE_CONVERGE_TAG	RAW(2000)		Remote Replication tag used while performing converge DMLs
MAX_NUM_BUCKETS	NUMBER		Suggested maximum number of buckets in a scan
MIN_ROWS_IN_BUCKET	NUMBER		Suggested minimum number of rows in a bucket
LAST_UPDATE_TIME	TIMESTAMP(6)		Time that this row was last updated

> **See Also:**
>
> "USER_COMPARISON"

5.246 DBA_COMPARISON_COLUMNS

DBA_COMPARISON_COLUMNS displays information about the columns for all comparison objects in the database.

Related View

USER_COMPARISON_COLUMNS displays information about the columns for the comparison objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the comparison
COMPARISON_NAME	VARCHAR2(128)	NOT NULL	Name of the comparison
COLUMN_POSITION	NUMBER	NOT NULL	Position of the column
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column
INDEX_COLUMN	VARCHAR2(1)		Indicates whether the column is an index column (Y) or not (N)

> **See Also:**
>
> "USER_COMPARISON_COLUMNS"

5.247 DBA_COMPARISON_ROW_DIF

DBA_COMPARISON_ROW_DIF displays information about the differing rows in all comparison scans in the database.

Related View

USER_COMPARISON_ROW_DIF displays information about the differing rows in the comparison scans owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the comparison
COMPARISON_NAME	VARCHAR2(128)	NOT NULL	Name of the comparison
SCAN_ID	NUMBER	NOT NULL	Scan ID for the comparison scan
LOCAL_ROWID	ROWID		Local rowid of the differing row
REMOTE_ROWID	ROWID		Remote rowid of the differing row
INDEX_VALUE	VARCHAR2(4000)		Index column value of the differing row

Column	Datatype	NULL	Description
STATUS	VARCHAR2(3)		Status of the differing row: • SUC • DIF
LAST_UPDATE_TIME	TIMESTAMP(6)		Time that this row was last updated

> **See Also:**
>
> "USER_COMPARISON_ROW_DIF"

5.248 DBA_COMPARISON_SCAN

DBA_COMPARISON_SCAN displays information about all comparison scans in the database.

Related View

USER_COMPARISON_SCAN displays information about the comparison scans owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the comparison scan
COMPARISON_NAME	VARCHAR2(128)	NOT NULL	Name of the comparison scan
SCAN_ID	NUMBER	NOT NULL	Scan ID
PARENT_SCAN_ID	NUMBER		Scan ID of the immediate parent scan
ROOT_SCAN_ID	NUMBER		Scan ID of the root (top-most) parent
STATUS	VARCHAR2(16)		Status of the scan: • SUC • BUCKET DIF • FINAL BUCKET DIF • ROW DIF
CURRENT_DIF_COUNT	NUMBER		Current cumulative (including children) diff count of the scan
INITIAL_DIF_COUNT	NUMBER		Initial cumulative (including children) diff count of the scan
COUNT_ROWS	NUMBER		Number of rows in the scan
SCAN_NULLS	VARCHAR2(1)		Indicates whether NULLs are part of this scan (Y) or not (N)
LAST_UPDATE_TIME	TIMESTAMP(6)		Time that this row was last updated

> **See Also:**
>
> "USER_COMPARISON_SCAN"

5.249 DBA_COMPARISON_SCAN_VALUES

DBA_COMPARISON_SCAN_VALUES displays information about the values for all comparison scans in the database.

Related View

USER_COMPARISON_SCAN_VALUES displays information about the values for the comparison scans owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the comparison scan
COMPARISON_SCAN	VARCHAR2(128)	NOT NULL	Name of the comparison scan
SCAN_ID	NUMBER	NOT NULL	Scan ID
COLUMN_POSITION	NUMBER	NOT NULL	Column position, as in DBA_COMPARISON_COLUMNS
MIN_VALUE	VARCHAR2(4000)		Minimum value of the scan
MAX_VALUE	VARCHAR2(4000)		Maximum value of the scan
LAST_UPDATE_TIME	TIMESTAMP(6)		Time that this row was last updated

> **See Also:**
>
> "USER_COMPARISON_SCAN_VALUES"

5.250 DBA_CONNECT_ROLE_GRANTEES

DBA_CONNECT_ROLE_GRANTEES displays information about users who are granted the CONNECT privilege.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)		User or schema to which the CONNECT role is granted
PATH_OF_CONNECT_ROLE_GRANT	VARCHAR2(4000)		The path of role inheritance through which the grantee is granted the CONNECT role
ADMIN_OPT	VARCHAR2(3)		Whether or not the grantee was granted the ADMIN option for the CONNECT role

5.251 DBA_CONNECTION_TESTS

DBA_CONNECTION_TESTS provides information about connection tests in use for CDBs and PDBs.

This view shows SQL and non-SQL connection tests.

Column	Datatype	NULL	Description
PREDEFINED	VARCHAR2(1)		Indicates whether the test is predefined or custom. Possible values: • Y: The test is predefined. • N: The test is added by the user. Predefined tests can be disabled, but not deleted.
CONNECTION_TEST_TYPE	VARCHAR2(15)		Indicates the test type. Possible values include: • SQL_TEST: Application servers and applications use SQL tests to check the validity of a connection. Use this value for SQL based connection tests, for example (SELECT 1 FROM DUAL;) • PING_TEST: Used when you are using tests that use the ping function to test the connection, including the OCIPing, isValid, isUsable, connection.status, and PING_DATABASE connection tests. • ENDREQUEST_TEST: Used when request boundaries are received at the RDBMS. Oracle Connection Pools and all application servers using JDK9 send request boundaries to the RDBMS starting in Oracle Database 12*c* Release 2 (12.2.0.1). The test type values are the CONNECTION_TEST_TYPE parameter values that can be specified for the ENABLE_CONNECTION_TEST and DISABLE_CONNECTION_TEST procedures for the DBMS_APP_CONT_ADMIN PL/SQL package.
SQL_CONNECTION_TEST	VARCHAR2(64)		SQL test. This column is null for non-SQL tests.
SERVICE_NAME	VARCHAR2(128)		Optional service name qualifier
ENABLED	VARCHAR2(1)		Indicates whether the SQL test is enabled. Possible values: • Y: The test is enabled. • N: The test is not enabled.

See Also:

Oracle Database PL/SQL Packages and Types Reference for additional information about the ENABLE_CONNECTION_TEST procedure for the DBMS_APP_CONT_ADMIN PL/SQL package

5.252 DBA_CONS_COLUMNS

DBA_CONS_COLUMNS describes all columns in the database that are specified in constraints. Its columns are the same as those in ALL_CONS_COLUMNS.

> **See Also:**
>
> "ALL_CONS_COLUMNS"

5.253 DBA_CONS_OBJ_COLUMNS

DBA_CONS_OBJ_COLUMNS displays information about the types that object columns (or attributes) or collection elements have been constrained to, in all tables in the database. Its columns are the same as those in ALL_CONS_OBJ_COLUMNS.

> **See Also:**
>
> "ALL_CONS_OBJ_COLUMNS"

5.254 DBA_CONSTRAINTS

DBA_CONSTRAINTS describes all constraint definitions on all tables in the database. Its columns are the same as those in ALL_CONSTRAINTS.

> **See Also:**
>
> "ALL_CONSTRAINTS"

5.255 DBA_CONTAINER_DATA

DBA_CONTAINER_DATA displays default (user-level) and object-specific CONTAINER_DATA attributes for container data objects.

Objects created with the CONTAINER_DATA clause include CONTAINER_DATA attributes.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the user whose attribute is described by this row
DEFAULT_ATTR	CHAR2(1)		An indicator of whether the attribute is a default attribute

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Name of the object owner if the attribute is object-specific
OBJECT_NAME	VARCHAR2(128)		Name of the object if the attribute is object-specific
ALL_CONTAINERS	VARCHAR2(1)		An indicator of whether this attribute applies to all containers
CONTAINER_NAME	VARCHAR2(128)		Name of a container included in this attribute if it does not apply to all containers

See Also:

For more information about container data objects:

- "CDB_* Views"
- "ALL_TABLES"
- "ALL_VIEWS"
- "ALL_VIEWS_AE"
- "V$ Views"
- "GV$ Views"
- *Oracle Multitenant Administrator's Guide*
- *Oracle Database Security Guide*

5.256 DBA_CONTEXT

DBA_CONTEXT provides all context namespace information in the database.

Related View

ALL_CONTEXT describes all context namespaces in the current session for which attributes and values have been specified using the DBMS_SESSION.SET_CONTEXT procedure. This view does not describe the TYPE and ORIGIN_CON_ID columns.

Column	Datatype	NULL	Description
NAMESPACE	VARCHAR2(128)	NOT NULL	Name of the context namespace
SCHEMA	VARCHAR2(128)	NOT NULL	Schema name of the designated package that can set attributes using this namespace
PACKAGE	VARCHAR2(128)	NOT NULL	Package name of the designated package that can set attributes using this namespace
TYPE	VARCHAR2(22)		Type of the context create

Column	Datatype	NULL	Description
ORIGIN_CON_ID	NUMBER		The ID of the container where the data originates. Possible values include: • 0: This value is used for rows in non-CDBs. This value is not used for CDBs. • *n*: This value is used for rows containing data that originate in the container with container ID *n* (*n* = 1 if the row originates in root)

> **See Also:**
>
> "ALL_CONTEXT"

5.257 DBA_CPOOL_INFO

DBA_CPOOL_INFO displays configuration information about all Database Resident Connection Pools in the database.

Column	Datatype	NULL	Description
CONNECTION_POOL	VARCHAR2(128)		Name of the connection pool
STATUS	VARCHAR2(16)		Status of the pool: • ACTIVE • INACTIVE
MINSIZE	NUMBER		Minimum number of pooled servers that are always running in the pool
MAXSIZE	NUMBER		Maximum number of pooled servers in the pool
INCRSIZE	NUMBER		Number of pooled servers by which the pool is incremented if servers are unavailable when a client application request is received
SESSION_CACHED_CURSORS	NUMBER		Number of session cursors to cache in each pooled server
INACTIVITY_TIMEOUT	NUMBER		Maximum time (in seconds) that the pooled server can stay idle in the pool. After this time, the server is terminated.
MAX_THINK_TIME	NUMBER		Maximum time of inactivity (in seconds) for a client after obtaining a pooled server from the pool. After obtaining a pooled server from the pool, if the client application does not issue a database call for the time specified by this column, then the pooled server is freed and the client connection is terminated.
MAX_USE_SESSION	NUMBER		Number of times a pooled server can be taken and released to the pool
MAX_LIFETIME_SESSION	NUMBER		Time (in seconds) for a pooled server to live in the pool

Column	Datatype	NULL	Description
NUM_CBROK	NUMBER		Number of connection brokers spawned per instance
MAXCONN_CBROK	NUMBER		Maximum number of connections per connection broker
MAX_TXN_THINK_TIME	NUMBER		Maximum time of inactivity (in seconds) for a client after it obtains a pooled server from the pool and starts a transaction. If the client application does not issue a database call for the time specified by MAX_TXN_THINK_TIME while in a transaction, the pooled server is freed, the transaction is rolled back, and the client connection is terminated. The default value is 0, which means MAX_THINK_TIME applies for all connections, irrespective of transactions being open or not in those connections. Care should be taken while setting the two parameters MAX_THINK_TIME and MAX_TXN_THINK_TIME to higher values, as it would mean the servers are not released to the pool for a longer time, even if clients are not responding for any reason, thereby making other users wait unnecessarily.
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- *Oracle Database Administrator's Guide* for more information about the configuration parameters for Database Resident Connection Pooling
- *Oracle Database PL/SQL Packages and Types Reference* for more information on the DBMS_CONNECTION_POOL package

5.258 DBA_CPU_USAGE_STATISTICS

DBA_CPU_USAGE_STATISTICS displays database CPU usage statistics.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
VERSION	VARCHAR2(17)	NOT NULL	Database version
TIMESTAMP	DATE	NOT NULL	Time at which the CPU usage changed

Column	Datatype	NULL	Description
CPU_COUNT	NUMBER		CPU count of the database
CPU_CORE_COUNT	NUMBER		CPU core count of the database
CPU_SOCKET_COUNT	NUMBER		CPU socket count of the database

5.259 DBA_CQ_NOTIFICATION_QUERIES

DBA_CQ_NOTIFICATION_QUERIES describes the registered queries for all CQ notifications in the database.

Related View

USER_CQ_NOTIFICATION_QUERIES describes the registered queries for the CQ notifications owned by the current user. This view does not display the USERNAME column.

Column	Datatype	NULL	Description
QUERYID	NUMBER		ID of the query
QUERYTEXT	CLOB		Text of the query
REGID	NUMBER		Registration ID that the query is registered with
USERNAME	VARCHAR2(31)		Name of the user who registered the query

> **See Also:**
>
> "USER_CQ_NOTIFICATION_QUERIES"

5.260 DBA_CREDENTIALS

DBA_CREDENTIALS lists all credentials in the database. Its columns are the same as those in ALL_CREDENTIALS.

> **See Also:**
>
> "ALL_CREDENTIALS"

5.261 DBA_CUBE_ATTR_VISIBILITY

DBA_CUBE_ATTR_VISIBILITY describes all OLAP attributes visible for the dimensions, hierarchies, and levels in the database. Its columns are the same as those in ALL_CUBE_ATTR_VISIBILITY.

> **See Also:**
>
> "ALL_CUBE_ATTR_VISIBILITY"

5.262 DBA_CUBE_ATTRIBUTES

DBA_CUBE_ATTRIBUTES describes the attributes for all OLAP cube dimensions in the database. Its columns are the same as those in ALL_CUBE_ATTRIBUTES.

> **See Also:**
>
> "ALL_CUBE_ATTRIBUTES"

5.263 DBA_CUBE_BUILD_PROCESSES

DBA_CUBE_BUILD_PROCESSES describes all OLAP build processes and maintenance scripts in the database. Its columns are the same as those in ALL_CUBE_BUILD_PROCESSES.

> **See Also:**
>
> "ALL_CUBE_BUILD_PROCESSES"

5.264 DBA_CUBE_CALCULATED_MEMBERS

DBA_CUBE_CALCULATED_MEMBERS describes the calculated members for all OLAP cube dimensions in the database. Its columns are the same as those in ALL_CUBE_CALCULATED_MEMBERS.

> **See Also:**
>
> "ALL_CUBE_CALCULATED_MEMBERS"

5.265 DBA_CUBE_DIM_LEVELS

DBA_CUBE_DIM_LEVELS describes all OLAP dimension levels in the database. Its columns are the same as those in ALL_CUBE_DIM_LEVELS.

> **See Also:**
>
> "ALL_CUBE_DIM_LEVELS"

5.266 DBA_CUBE_DIM_MODELS

DBA_CUBE_DIM_MODELS describes the models for all OLAP dimensions in the database. Its columns are the same as those in ALL_CUBE_DIM_MODELS.

> **See Also:**
>
> "ALL_CUBE_DIM_MODELS"

5.267 DBA_CUBE_DIM_VIEW_COLUMNS

DBA_CUBE_DIM_VIEW_COLUMNS describes the columns of the relational views of all OLAP cube dimensions in the database. Its columns are the same as those in ALL_CUBE_DIM_VIEW_COLUMNS.

> **See Also:**
>
> "ALL_CUBE_DIM_VIEW_COLUMNS"

5.268 DBA_CUBE_DIM_VIEWS

DBA_CUBE_DIM_VIEWS describes the relational views of all OLAP dimensions in the database. Its columns are the same as those in ALL_CUBE_DIM_VIEWS.

> **See Also:**
>
> "ALL_CUBE_DIM_VIEWS"

5.269 DBA_CUBE_DIMENSIONALITY

`DBA_CUBE_DIMENSIONALITY` describes the dimension order for all OLAP cubes in the database. Its columns are the same as those in `ALL_CUBE_DIMENSIONALITY`.

> **See Also:**
>
> "ALL_CUBE_DIMENSIONALITY"

5.270 DBA_CUBE_DIMENSIONS

`DBA_CUBE_DIMENSIONS` describes all OLAP cube dimensions in the database. Its columns are the same as those in `ALL_CUBE_DIMENSIONS`.

> **See Also:**
>
> "ALL_CUBE_DIMENSIONS"

5.271 DBA_CUBE_HIER_LEVELS

`DBA_CUBE_HIER_LEVELS` describes the hierarchy levels for all OLAP cube dimensions in the database. Its columns are the same as those in `ALL_CUBE_HIER_LEVELS`.

> **See Also:**
>
> "ALL_CUBE_HIER_LEVELS"

5.272 DBA_CUBE_HIER_VIEW_COLUMNS

`DBA_CUBE_HIER_VIEW_COLUMNS` describes the columns of the relational hierarchy views of all OLAP cube dimensions in the database. Its columns are the same as those in `ALL_CUBE_HIER_VIEW_COLUMNS`.

> **See Also:**
>
> "ALL_CUBE_HIER_VIEW_COLUMNS"

5.273 DBA_CUBE_HIER_VIEWS

DBA_CUBE_HIER_VIEWS describes the hierarchies for all OLAP cube dimensions in the database. Its columns are the same as those in ALL_CUBE_HIER_VIEWS.

> **See Also:**
>
> "ALL_CUBE_HIER_VIEWS"

5.274 DBA_CUBE_HIERARCHIES

DBA_CUBE_HIERARCHIES describes all OLAP dimension hierarchies in the database. Its columns are the same as those in ALL_CUBE_HIERARCHIES.

> **See Also:**
>
> "ALL_CUBE_HIERARCHIES"

5.275 DBA_CUBE_MEASURES

DBA_CUBE_MEASURES describes the measures for all OLAP cubes in the database. Its columns are the same as those in ALL_CUBE_MEASURES.

> **See Also:**
>
> "ALL_CUBE_MEASURES"

5.276 DBA_CUBE_NAMED_BUILD_SPECS

DBA_CUBE_NAMED_BUILD_SPECS describes the OLAP cube named build specifications in the database. Its columns are the same as those in ALL_CUBE_NAMED_BUILD_SPECS.

> **See Also:**
>
> "ALL_CUBE_NAMED_BUILD_SPECS"

5.277 DBA_CUBE_SUB_PARTITION_LEVELS

DBA_CUBE_SUB_PARTITION_LEVELS describes the OLAP secondary partition levels in the database. Its columns are the same as those in ALL_CUBE_SUB_PARTITION_LEVELS.

> **See Also:**
>
> "ALL_CUBE_SUB_PARTITION_LEVELS"

5.278 DBA_CUBE_VIEW_COLUMNS

DBA_CUBE_VIEW_COLUMNS describes the columns of relational views of all OLAP cubes in the database. Its columns are the same as those in ALL_CUBE_VIEW_COLUMNS.

> **See Also:**
>
> "ALL_CUBE_VIEW_COLUMNS"

5.279 DBA_CUBE_VIEWS

DBA_CUBE_VIEWS describes the relational views of all OLAP cubes in the database. Its columns are the same as those in ALL_CUBE_VIEWS.

> **See Also:**
>
> "ALL_CUBE_VIEWS"

5.280 DBA_CUBES

DBA_CUBES describes all OLAP cubes in the database. Its columns are the same as those in ALL_CUBES.

> **See Also:**
>
> "ALL_CUBES"

5.281 DBA_DATA_FILES

DBA_DATA_FILES describes database files.

> **Note:**
>
> When you query the DBA_DATA_FILES data dictionary view, Oracle must have access to all tablespaces and their data files if the requested information is not already available in the dictionary. If the tablespaces are encrypted, then you must open the Oracle wallet (keystore) before you can query DBA_DATA_FILES. You can use the ADMINISTER KEY MANAGEMENT SET KEYSTORE OPEN statement to open the keystore.

Column	Datatype	NULL	Description
FILE_NAME	VARCHAR2(513)		Name of the database file
FILE_ID	NUMBER		Absolute file number of the database file
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace to which the file belongs
BYTES	NUMBER		Size of the file in bytes
BLOCKS	NUMBER		Size of the file in Oracle blocks
STATUS	VARCHAR2(9)		File status: AVAILABLE or INVALID (INVALID means that the file number is not in use, for example, a file in a tablespace that was dropped)
RELATIVE_FNO	NUMBER		Relative file number
AUTOEXTENSIBLE	VARCHAR2(3)		Autoextensible indicator
MAXBYTES	NUMBER		Maximum file size in bytes
MAXBLOCKS	NUMBER		Maximum file size in blocks
INCREMENT_BY	NUMBER		Number of Oracle blocks used as autoextension increment
USER_BYTES	NUMBER		The size of the file available for user data. The actual size of the file minus the USER_BYTES value is used to store file related metadata.
USER_BLOCKS	NUMBER		Number of blocks which can be used by the data
ONLINE_STATUS	VARCHAR2(7)		Online status of the file: • SYSOFF • SYSTEM • OFFLINE • ONLINE • RECOVER

Column	Datatype	NULL	Description
LOST_WRITE_PROTECT	VARCHAR2(7)		Lost write protection status of the file. Possible values: • ENABLED: Indicates that lost write data is being collected • OFF: Indicates that lost write data is not being collected • SUSPEND: Indicates that lost write data is not currently being collected, but it can be enabled at a later date. The lost write data collected when the file was ENABLED remains in the lost write database, but it is not being checked or updated. If lost write protection is enabled for a single data file, it does not have to be enabled for another data file in the same tablespace. If lost write protection is enabled for a tablespace, it is enabled for all data files for that tablespace, including data files added later. You can check the lost write protection status for a tablespace by querying the LOST_WRITE_PROTECT column in the DBA_TABLESPACES view.

See Also:

- *Oracle Database Advanced Security Guide* for information on opening a software keystore
- *Oracle Database Advanced Security Guide* for information on opening a hardware keystore
- "DBA_TABLESPACES"

5.282 DBA_DATAPUMP_JOBS

DBA_DATAPUMP_JOBS identifies all active Data Pump jobs in the database, regardless of their state, on an instance (or on all instances for Real Application Clusters). It also show all Data Pump control job tables not currently associated with an active job.

Related View

USER_DATAPUMP_JOBS displays the Data Pump jobs owned by the current user. This view does not display the OWNER_NAME column.

Column	Datatype	NULL	Description
OWNER_NAME	VARCHAR2(128)		User that initiated the job
JOB_NAME	VARCHAR2(128)		User-supplied name for the job (or the default name generated by the server)
OPERATION	VARCHAR2(128)		Type of job

Column	Datatype	NULL	Description
JOB_MODE	VARCHAR2(128)		Mode of job
STATE	VARCHAR2(128)		Current job state
DEGREE	NUMBER		Number of worker processes performing the operation
ATTACHED_SESSIONS	NUMBER		Number of sessions attached to the job
DATAPUMP_SESSIONS	NUMBER		Number of Data Pump sessions participating in the job

See Also:

"USER_DATAPUMP_JOBS"

5.283 DBA_DATAPUMP_SESSIONS

DBA_DATAPUMP_SESSIONS identifies the user sessions that are attached to a Data Pump job. The information in this view is useful for determining why a stopped Data Pump operation has not gone away.

Column	Datatype	NULL	Description
OWNER_NAME	VARCHAR2(128)		User that initiated the job
JOB_NAME	VARCHAR2(128)		User-supplied name for the job (or the default name generated by the server)
INSTANCE_ID	NUMBER		Instance ID
SADDR	RAW(4 | 8)		Address of the session attached to the job. Can be used with V$SESSION view.
SESSION_TYPE	VARCHAR2(14)		Data Pump session type: • DBMS_DATAPUMP - Data Pump interface process (one for each active instantiation of DBMS_DATAPUMP.OPEN and DBMS_DATAPUMP.ATTACH per job.) • MASTER - Data Pump control job process (one per job) • WORKER - worker process (1 to *n* per job, depending on degree of parallelism) • EXTERNAL TABLE - external table data access process (1 to *n*, depending on degree of parallelism, for jobs that use external tables as the data access method for some tables) • OTHER

> **See Also:**
>
> *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_DATAPUMP` package

5.284 DBA_DB_LINK_SOURCES

`DBA_DB_LINK_SOURCES` identifies all unique source databases that opened database links to the local database.

By default, only a DBA has access to this view. However, a DBA can grant access to this view to others.

This view is based on a persistent table that resides in the same system tablespace that is used by Database Auditing.

In a multitenant container database (CDB) environment, for every DBA_ view, there is a corresponding CDB_ view that contains data for all the pluggable databases (PDBs) in the CDB. A query on the `CDB_DB_LINK_SOURCES` view done in the `CDB$ROOT` container will show sources of all the database links recorded in all PDBs. A query on the corresponding `DBA_DB_LINK_SOURCES` view done in a PDB show information corresponding to that PDB only (that is, where that specific PDB was the target of an inbound database link).

Note that the CDB_ views would only show data from PDBs that are open at the time the query is issued. Therefore, when you are diagnosing sources of database links, Oracle recommends that you keep open any or all PDBs that might contain useful information for the diagnosis.

Column	Datatype	NULL	Description
SOURCE_ID	NUMBER	NOT NULL	Unique ID that identifies an incoming database link
DB_NAME	VARCHAR2(256)	NOT NULL	Global name of the source database
DBID	NUMBER	NOT NULL	Database identifier of the source database. Maps to the `DBID` of the source database in `V$DATABASE`.
DB_UNIQUE_NAME	VARCHAR2(256)		Unique database name of the source database. Maps to the `DB_UNIQUE_NAME` of the source database in `V$DATABASE`. Null for source databases that do not provide this information.
HOST_NAME	VARCHAR2(256)		Resolved host name. Null if not available.
IP_ADDRESS	VARCHAR2(128)		IP address of source machine. Null if not available.
PROTOCOL	VARCHAR2(64)		One of supported protocols such as `ipc`, `sdp`, `tcp`, or `tcps`. Null if not available.
USERNAME	VARCHAR2(128)	NOT NULL	Oracle username of the user who logged into the local database. Maps to the `USERNAME` column in `V$SESSION`.
USER#	NUMBER	NOT NULL	Oracle user id of the user who logged into the local database. Maps to the `USER#` column in `V$SESSION`.

Column	Datatype	NULL	Description
FIRST_LOGON_TIME	TIMESTAMP(6)	NOT NULL	The timestamp of the first connection on this database link in UTC
LAST_LOGON_TIME	TIMESTAMP(6)		The timestamp of the last connection on this database link in UTC
LOGON_COUNT	NUMBER		Number of times connection has been established through this database link

See Also:

- "V$DATABASE"
- "V$SESSION"
- "DBA_EXTERNAL_SCN_ACTIVITY"
- "DBA_DB_LINKS"

5.285 DBA_DB_LINKS

DBA_DB_LINKS describes all database links in the database. Its columns are the same as those in ALL_DB_LINKS.

See Also:

- "ALL_DB_LINKS"
- "DBA_DB_LINK_SOURCES"
- "DBA_EXTERNAL_SCN_ACTIVITY"

5.286 DBA_DBFS_HS

DBA_DBFS_HS shows all Database File System (DBFS) hierarchical stores.

Related View

USER_DBFS_HS shows all Database File System hierarchical stores owned by the current user. This view does not display the STOREOWNER column.

Column	Datatype	NULL	Description
STORENAME	VARCHAR2(256)		Name of store
STOREOWNER	VARCHAR2(64)		Owner of store

> **See Also:**
>
> "USER_DBFS_HS"

5.287 DBA_DBFS_HS_COMMANDS

DBA_DBFS_HS_COMMANDS shows all the registered store commands for all Database File System (DBFS) hierarchical stores.

Related View

USER_DBFS_HS_COMMANDS shows all the registered store commands for all DBFS hierarchical stores owned by current user. This view does not display the STOREOWNER column.

Column	Datatype	NULL	Description
STORENAME	VARCHAR2(256)		Name of store
STOREOWNER	VARCHAR2(64)		Owner of store
STORECOMMAND	VARCHAR2(512)		Store command
STOREFLAGS	NUMBER		Valid values are: • 1 - Indicates that the command is sent to the device before put • 2 - Indicates that the command is sent to the device before get

> **See Also:**
>
> "USER_DBFS_HS_COMMANDS"

5.288 DBA_DBFS_HS_FIXED_PROPERTIES

DBA_DBFS_HS_FIXED_PROPERTIES shows non-modifiable properties of all Database File System (DBFS) hierarchical stores.

Related View

USER_DBFS_HS_FIXED_PROPERTIES shows non-modifiable properties of all DBFS hierarchical stores owned by current user. This view does not display the STORE_OWNER column.

Column	Datatype	NULL	Description
STORE_NAME	VARCHAR2(128)	NOT NULL	Name of store
STORE_OWNER	VARCHAR2(128)	NOT NULL	Owner of store
PROP_NAME	VARCHAR2(256)	NOT NULL	Property name

Column	Datatype	NULL	Description
PROP_VALUE	VARCHAR2(256)	NOT NULL	Property value

> **See Also:**
>
> "USER_DBFS_HS_FIXED_PROPERTIES"

5.289 DBA_DBFS_HS_PROPERTIES

DBA_DBFS_HS_PROPERTIES shows modifiable properties of all Database File System (DBFS) hierarchical stores.

Related View

USER_DBFS_HS_PROPERTIES shows modifiable properties of all DBFS hierarchical stores owned by current user. This view does not display the STOREOWNER column.

Column	Datatype	NULL	Description
STORENAME	VARCHAR2(256)		Name of store
STOREOWNER	VARCHAR2(64)		Owner of store
PROPERTYNAME	VARCHAR2(256)		Property name
PROPERTYVALUE	VARCHAR2(256)		Property value

> **See Also:**
>
> "USER_DBFS_HS_PROPERTIES"

5.290 DBA_DDL_LOCKS

DBA_DDL_LOCKS lists all DDL locks held in the database and all outstanding requests for a DDL lock.

Column	Datatype	NULL	Description
SESSION_ID	NUMBER		Session identifier
OWNER	VARCHAR2(128)		Owner of the lock
NAME	VARCHAR2(1000)		Name of the lock

Column	Datatype	NULL	Description
TYPE	VARCHAR2(40)		Lock type: • Cursor • Table/Procedure/Type • Body • Trigger • Index • Cluster • Java Source • Java Resource • Java Data
MODE_HELD	VARCHAR2(9)		Lock mode: • None • Null • Share • Exclusive
MODE_REQUESTED	VARCHAR2(9)		Lock request type: • None • Null • Share • Exclusive

See Also:

Oracle Database Concepts for more information about DDL locks

5.291 DBA_DDL_REGS

DBA_DDL_REGS displays all DDL notification registrations in the database.

Related View

USER_DDL_REGS displays DDL notification registrations that apply to tables owned by the current user. This view does not display the USERNAME column.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)	NOT NULL	Registration owner
REG_ID	NUMBER	NOT NULL	Internal registration ID
TYPE	VARCHAR2(8)		Registration type. Possible values: • TABLE • SCHEMA • DATABASE
NAME	VARCHAR2(257)		Name of the registered table, schema, or database
CLIENT_ID	VARCHAR2(64)		User-specified client ID

Column	Datatype	NULL	Description
INCLUDE_TRUNCATE	VARCHAR2(3)		Indicates whether notifications are generated for TRUNCATE operations (YES) or not (NO)
INCLUDE_PMOP	VARCHAR2(3)		Indicates whether notifications are generated for partition maintenance operations (YES) or not (NO)

Note:

This view is available starting with Oracle Database 23ai.

See Also:

"USER_DDL_REGS"

5.292 DBA_DEPENDENCIES

DBA_DEPENDENCIES describes all dependencies in the database between procedures, packages, functions, package bodies, and triggers, including dependencies on views created without any database links. Its columns are the same as those in ALL_DEPENDENCIES.

See Also:

"ALL_DEPENDENCIES"

5.293 DBA_DIGEST_VERIFIERS

DBA_DIGEST_VERIFIERS enables the database administrator to check which users have Digest verifiers stored on disk and the type of hashing algorithm used for the verifiers.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the user
HAS_DIGEST_VERIFIERS	VARCHAR2(3)		YES if a Digest verifier exists, NO otherwise
DIGEST_TYPE	CHAR(3)		The type of hashing algorithm used for the Digest verifier. For instance, MD5 for users with MD5 Digest verifiers. If no Digest verifier exists, this column is NULL.

5.294 DBA_DIM_ATTRIBUTES

`DBA_DIM_ATTRIBUTES` describes the relationships between dimension levels and functionally dependent columns in the database. The level columns and the dependent column must be in the same table. This view's columns are the same as those in `ALL_DIM_ATTRIBUTES`.

> **See Also:**
>
> "ALL_DIM_ATTRIBUTES"

5.295 DBA_DIM_CHILD_OF

`DBA_DIM_CHILD_OF` describes a hierarchical relationship of 1 to *n* between all the pairs of levels in the dimensions in the database. Its columns are the same as those in `ALL_DIM_CHILD_OF`.

> **See Also:**
>
> "ALL_DIM_CHILD_OF"

5.296 DBA_DIM_HIERARCHIES

`DBA_DIM_HIERARCHIES` describes all the dimension hierarchies in the database. Its columns are the same as those in `ALL_DIM_HIERARCHIES`.

> **See Also:**
>
> "ALL_DIM_HIERARCHIES"

5.297 DBA_DIM_JOIN_KEY

`DBA_DIM_JOIN_KEY` describes all joins in the database between two dimension tables. The join is always specified between a parent dimension level column and a child column. This view's columns are the same as those in `ALL_DIM_JOIN_KEY`.

> **See Also:**
>
> "ALL_DIM_JOIN_KEY"

5.298 DBA_DIM_LEVEL_KEY

DBA_DIM_LEVEL_KEY describes the columns of all dimension levels in the database. This view's columns are the same as those in ALL_DIM_LEVEL_KEY.

> **See Also:**
>
> "ALL_DIM_LEVEL_KEY"

5.299 DBA_DIM_LEVELS

DBA_DIM_LEVELS describes all dimension levels in the database. All columns of a dimension level must come from the same relation. This view's columns are the same as those in ALL_DIM_LEVELS.

> **See Also:**
>
> "ALL_DIM_LEVELS"

5.300 DBA_DIMENSIONS

DBA_DIMENSIONS represents dimension objects. Its columns are the same as those in ALL_DIMENSIONS.

> **See Also:**
>
> "ALL_DIMENSIONS"

5.301 DBA_DIRECTORIES

DBA_DIRECTORIES describes all directory objects in the database. Its columns are the same as those in ALL_DIRECTORIES.

> **See Also:**
>
> "ALL_DIRECTORIES"

5.302 DBA_DISCOVERY_SOURCE

DBA_DISCOVERY_SOURCE describes sensitive data discovery import information.

Column	Datatype	NULL	Description
SOURCE_NAME	VARCHAR2(128)		The name of the discovery source. In the case of Application Data Model (ADM), this is the ADM instance name.
SOURCE_TYPE	VARCHAR2(6)		The type of the source: • ADM: import from ADM • CUSTOM: custom import • DB: discovered within the database
CTIME	TIMESTAMP(6)		The last time sensitive data was imported from this source

> **See Also:**
>
> *Oracle Database Security Guide* for more information about transparent sensitive data protection

5.303 DBA_DML_LOCKS

DBA_DML_LOCKS lists all DML locks held in the database and all outstanding requests for a DML lock.

Column	Datatype	NULL	Description
SESSION_ID	NUMBER		Session holding or acquiring the lock
OWNER	VARCHAR2(128)	NOT NULL	Owner of the lock
NAME	VARCHAR2(128)	NOT NULL	Name of the lock
MODE_HELD	VARCHAR2(13)		The type of lock held. The values are: • ROWS_S (SS): row share lock • ROW-X (SX): row exclusive lock • SHARE (S): share lock • S/ROW-X (SSX): exclusive lock • NONE: lock requested but not yet obtained
MODE_REQUESTED	VARCHAR2(13)		Lock request type. The values are: • ROWS_S (SS): row share lock • ROW-X (SX): row exclusive lock • SHARE (S): share lock • S/ROW-X (SSX): exclusive lock • NONE: Lock identifier obtained; lock not held or requested
LAST_CONVERT	NUMBER		Time since current mode was granted
BLOCKING_OTHERS	VARCHAR2(40)		Blocking others

> **See Also:**
>
> *Oracle Database Concepts* for more information about lock modes for table locks

5.304 DBA_DMT_FREE_SPACE

`DBA_DMT_FREE_SPACE` describes the free extents in all dictionary managed tablespaces in the database.

Column	Datatype	NULL	Description
TABLESPACE_ID	NUMBER	NOT NULL	Identifier number of the tablespace containing the extent
FILE_ID	NUMBER	NOT NULL	File identifier number of the file containing the extent
BLOCK_ID	NUMBER	NOT NULL	Starting block number of the extent
BLOCKS	NUMBER	NOT NULL	Size of the extent (in Oracle blocks)

5.305 DBA_DMT_USED_EXTENTS

`DBA_DMT_USED_EXTENTS` describes the extents comprising the segments in all dictionary managed tablespaces in the database.

Column	Datatype	NULL	Description
SEGMENT_FILEID	NUMBER	NOT NULL	File number of the segment header of the extent
SEGMENT_BLOCK	NUMBER	NOT NULL	Block number of the segment header of the extent
TABLESPACE_ID	NUMBER	NOT NULL	Identifier number of the tablespace containing the extent
EXTENT_ID	NUMBER	NOT NULL	Extent number in the segment
FILEID	NUMBER	NOT NULL	File identifier number of the file containing the extent
BLOCK	NUMBER	NOT NULL	Starting block number of the extent
LENGTH	NUMBER	NOT NULL	Number of blocks in the extent

5.306 DBA_DOMAIN_COLS

`DBA_DOMAIN_COLS` describes columns of all data use case domains in the database. Its columns are the same as those in `ALL_DOMAIN_COLS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_DOMAIN_COLS"

5.307 DBA_DOMAIN_CONSTRAINTS

`DBA_DOMAIN_CONSTRAINTS` describes constraint definitions on all data use case domains in the database. Its columns are the same as those in `ALL_DOMAIN_CONSTRAINTS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_DOMAIN_CONSTRAINTS"

5.308 DBA_DOMAINS

`DBA_DOMAINS` describes all data use case domains in the database. Its columns are the same as those in `ALL_DOMAINS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_DOMAINS"

5.309 DBA_EDITION_COMMENTS

DBA_EDITION_COMMENTS describes the comments on all editions in the database. Its columns are the same as those in ALL_EDITION_COMMENTS.

> **See Also:**
>
> "ALL_EDITION_COMMENTS"

5.310 DBA_EDITIONED_TYPES

DBA_EDITIONED_TYPES lists all types that are editioned by default for every user in the database.

Related View

USER_EDITIONED_TYPES lists the types that are editioned by default for the current user. This view does not display the SCHEMA column.

Column	Datatype	NULL	Description
SCHEMA	VARCHAR2(128)	NOT NULL	Schema in which the object types is editionable
OBJECT_TYPE	VARCHAR2(23)		Object type that is editionable

> **See Also:**
>
> "USER_EDITIONED_TYPES"

5.311 DBA_EDITIONING_VIEW_COLS

DBA_EDITIONING_VIEW_COLS describes the relationship between the columns of all editioning views in the database and the table columns to which they map. Its columns are the same as those in ALL_EDITIONING_VIEW_COLS.

> **See Also:**
>
> "ALL_EDITIONING_VIEW_COLS"

5.312 DBA_EDITIONING_VIEW_COLS_AE

DBA_EDITIONING_VIEW_COLS_AE describes the relationship between the columns of all editioning views (across all editions) in the database and the table columns to which they map. Its columns are the same as those in ALL_EDITIONING_VIEW_COLS_AE.

> **See Also:**
>
> "ALL_EDITIONING_VIEW_COLS_AE"

5.313 DBA_EDITIONING_VIEWS

DBA_EDITIONING_VIEWS describes all editioning views in the database. Its columns are the same as those in ALL_EDITIONING_VIEWS.

> **See Also:**
>
> "ALL_EDITIONING_VIEWS"

5.314 DBA_EDITIONING_VIEWS_AE

DBA_EDITIONING_VIEWS_AE describes all editioning views (across all editions) in the database. Its columns are the same as those in ALL_EDITIONING_VIEWS_AE.

> **See Also:**
>
> "ALL_EDITIONING_VIEWS_AE"

5.315 DBA_EDITIONS

DBA_EDITIONS describes all editions in the database. Its columns are the same as those in ALL_EDITIONS.

> **See Also:**
>
> - "ALL_EDITIONS"
> - *Oracle Database Development Guide* for more information about editions

5.316 DBA_ENABLED_AGGREGATIONS

DBA_ENABLED_AGGREGATIONS displays information about enabled on-demand statistic aggregation.

Column	Datatype	NULL	Description
AGGREGATION_TYPE	VARCHAR2(21)		Type of the aggregation: • CLIENT_ID • SERVICE • SERVICE_MODULE • SERVICE_MODULE_ACTION
PRIMARY_ID	VARCHAR2(64)		Primary qualifier (specific client identifier or service name)
QUALIFIER_ID1	VARCHAR2(48)		Secondary qualifier (specific module name)
QUALIFIER_ID2	VARCHAR2(32)		Additional qualifier (specific action name)

5.317 DBA_ENABLED_TRACES

DBA_ENABLED_TRACES displays information about enabled SQL traces.

Column	Datatype	NULL	Description
TRACE_TYPE	VARCHAR2(21)		Type of the trace: • CLIENT_ID • SERVICE • SERVICE_MODULE • SERVICE_MODULE_ACTION • DATABASE
PRIMARY_ID	VARCHAR2(64)		Primary qualifier (specific client identifier or service name)
QUALIFIER_ID1	VARCHAR2(64)		Secondary qualifier (specific module name)
QUALIFIER_ID2	VARCHAR2(64)		Additional qualifier (specific action name)
WAITS	VARCHAR2(5)		Indicates whether waits are traced (TRUE) or not (FALSE)
BINDS	VARCHAR2(5)		Indicates whether binds are traced (TRUE) or not (FALSE)
PLAN_STATS	VARCHAR2(10)		Indicates whether cursor execution statistics are traced. Possible values include: • ALL_EXEC: Execution statistics are dumped at each cursor execution • NEVER: Execution statistics are never dumped • FIRST_EXEC: Execution statistics are dumped during the first execution of the cursor. This is the default behavior.
INSTANCE_NAME	VARCHAR2(16)		Instance name for tracing restricted to named instances

> **See Also:**
>
> *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_MONITOR` package

5.318 DBA_ENCRYPTED_COLUMNS

`DBA_ENCRYPTED_COLUMNS` maintains encryption algorithm information for all encrypted columns in the database. Its columns are the same as those in `ALL_ENCRYPTED_COLUMNS`.

> **See Also:**
>
> "ALL_ENCRYPTED_COLUMNS"

5.319 DBA_EPG_DAD_AUTHORIZATION

`DBA_EPG_DAD_AUTHORIZATION` describes the DADs that are authorized to use different user's privileges.

Related View

`USER_EPG_DAD_AUTHORIZATION` describes the DADs that are authorized to use the user's privileges. This view does not display the `USERNAME` column.

Column	Datatype	NULL	Description
`DAD_NAME`	`VARCHAR2(64)`	NOT NULL	Name of DAD
`USERNAME`	`VARCHAR2(128)`	NOT NULL	Name of the user whose privileges the DAD is authorized to use

> **See Also:**
>
> "USER_EPG_DAD_AUTHORIZATION"

5.320 DBA_ERROR_TRANSLATIONS

DBA_ERROR_TRANSLATIONS describes all error translations in the database. Its columns are the same as those in ALL_ERROR_TRANSLATIONS.

> **See Also:**
>
> "ALL_ERROR_TRANSLATIONS"

5.321 DBA_ERRORS

DBA_ERRORS describes the current errors on all stored objects in the database. Its columns are the same as those in ALL_ERRORS.

> **See Also:**
>
> "ALL_ERRORS"

5.322 DBA_ERRORS_AE

DBA_ERRORS_AE describes the current errors on all stored objects (across all editions) in the database. Its columns are the same as those in ALL_ERRORS_AE.

> **See Also:**
>
> "ALL_ERRORS_AE"

5.323 DBA_EVALUATION_CONTEXT_TABLES

DBA_EVALUATION_CONTEXT_TABLES describes the tables in all rule evaluation contexts in the database. Its columns are the same as those in ALL_EVALUATION_CONTEXT_TABLES.

> **See Also:**
>
> "ALL_EVALUATION_CONTEXT_TABLES"

5.324 DBA_EVALUATION_CONTEXT_VARS

DBA_EVALUATION_CONTEXT_VARS describes the variables in all rule evaluation contexts in the database. Its columns are the same as those in ALL_EVALUATION_CONTEXT_VARS.

> **See Also:**
>
> "ALL_EVALUATION_CONTEXT_VARS"

5.325 DBA_EVALUATION_CONTEXTS

DBA_EVALUATION_CONTEXTS describes all rule evaluation contexts in the database. Its columns are the same as those in ALL_EVALUATION_CONTEXTS.

> **See Also:**
>
> "ALL_EVALUATION_CONTEXTS"

5.326 DBA_EXP_FILES

DBA_EXP_FILES describes export files.

Column	Datatype	NULL	Description
EXP_VERSION	NUMBER(3)	NOT NULL	Version number of the export session
EXP_TYPE	VARCHAR2(11)		Type of export file: complete, cumulative, or incremental
FILE_NAME	VARCHAR2(100)	NOT NULL	Name of the export file
USER_NAME	VARCHAR2(128)	NOT NULL	Name of user who executed export
TIMESTAMP	DATE	NOT NULL	Timestamp of the export session

5.327 DBA_EXP_OBJECTS

DBA_EXP_OBJECTS describes objects that have been incrementally exported.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of exported object
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of exported object
OBJECT_TYPE	VARCHAR2(13)		Type of exported object
CUMULATIVE	DATE		Timestamp of last cumulative export
INCREMENTAL	DATE	NOT NULL	Timestamp of last incremental export

Column	Datatype	NULL	Description
EXPORT_VERSION	NUMBER(3)	NOT NULL	The ID of the export session

5.328 DBA_EXP_VERSION

DBA_EXP_VERSION displays the version number of the last export session.

Column	Datatype	NULL	Description
EXP_VERSION	NUMBER(3)	NOT NULL	Version number of the last export session

5.329 DBA_EXPRESSION_STATISTICS

DBA_EXPRESSION_STATISTICS provides expression usage tracking statistics for all the tables in the database. Its columns are the same as those in ALL_EXPRESSION_STATISTICS.

> **See Also:**
>
> "ALL_EXPRESSION_STATISTICS"

5.330 DBA_EXTENTS

DBA_EXTENTS describes the extents comprising the segments in all tablespaces in the database.

Note that if a data file (or entire tablespace) is offline in a locally managed tablespace, you will not see any extent information. If an object has extents in an online file of the tablespace, you will see extent information about the offline data file. However, if the object is entirely in the offline file, a query of this view will not return any records.

Related View

USER_EXTENTS describes the extents comprising the segments owned by the current user's objects. This view does not display the OWNER, FILE_ID, BLOCK_ID, or RELATIVE_FNO columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the segment associated with the extent
SEGMENT_NAME	VARCHAR2(128)		Name of the segment associated with the extent
PARTITION_NAME	VARCHAR2(128)		Object Partition Name (Set to NULL for nonpartitioned objects)
SEGMENT_TYPE	VARCHAR2(18)		Type of the segment: INDEX PARTITION, TABLE PARTITION
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace containing the extent
EXTENT_ID	NUMBER		Extent number in the segment

Column	Datatype	NULL	Description
FILE_ID	NUMBER		Absolute file number of the data file containing the extent
BLOCK_ID	NUMBER		Starting block number of the extent
BYTES	NUMBER		Size of the extent in bytes
BLOCKS	NUMBER		Size of the extent in Oracle blocks
RELATIVE_FNO	NUMBER		Relative file number of the first extent block

> **See Also:**
>
> "USER_EXTENTS"

5.331 DBA_EXTERNAL_LOCATIONS

DBA_EXTERNAL_LOCATIONS describes the locations (data sources) of all external tables in the database. Its columns are the same as those in ALL_EXTERNAL_LOCATIONS.

> **See Also:**
>
> "ALL_EXTERNAL_LOCATIONS"

5.332 DBA_EXTERNAL_SCN_ACTIVITY

DBA_EXTERNAL_SCN_ACTIVITY works in conjunction with the DBA_DB_LINK_SOURCES and DBA_DB_LINKS views to determine the source of high SCN activities.

If the SCN is increased by an inbound database link, then you can join the DBA_EXTERNAL_SCN_ACTIVITY view with the DBA_DB_LINK_SOURCES view on the INBOUND_DB_LINK_SOURCE_ID column to get details of the remote database where the SCN increase originated.

If the SCN is increased by an outbound database link, then the INBOUND_DB_LINK_SOURCE_ID column will be NULL, but the OUTBOUND_DB_LINK_NAME and OUTBOUND_DB_LINK_OWNER columns can be joined with the DB_LINK and OWNER columns respectively in the DBA_DB_LINKS view to determine the remote database that caused the SCN increase.

If neither of the above cases are true (the INBOUND_DB_LINK_SOURCE_ID, OUTBOUND_DB_LINK_NAME, and OUTBOUND_DB_LINK_OWNER are all NULL), then the SCN increase resulted from a client connection and not as a result of a database link to or from another database. You can join the SESSION_ID and SESSION_SERIAL# columns with the SID and SERIAL# columns in V$SESSION to get the client session details.

In a multitenant container database (CDB) environment, for every DBA_ view, there is a corresponding CDB_ view that contains data for all the pluggable databases (PDBs) in the CDB.

As the SCN is a property of the CDB (and not a PDB), a DBA interested in understanding large SCN jumps will likely find the CDB_EXTERNAL_SCN_ACTIVITY view more useful for diagnosing SCN jumps on a CDB. Querying the CDB_EXTERNAL_SCN_ACTIVITY view from CDB$ROOT ensures that external SCN jumps occurring on all PDBs are looked at and noticed. On the other hand, a query on the corresponding DBA_EXTERNAL_SCN_ACTIVITY view, or a query on the CDB_EXTERNAL_SCN_ACTIVITY view done from a PDB would only show data for that PDB (that is, details regarding any external activity that occurred on that specific PDB that resulted in large SCN jumps).

Note that the CDB_ views would only show data from PDBs that are open at the time the query is issued. Therefore, when you are diagnosing sources of external SCN activities, Oracle recommends that you keep open any or all PDBs that might contain useful information for the diagnosis.

Column	Datatype	NULL	Description
OPERATION_TIMESTAMP	TIMESTAMP(6)	NOT NULL	Timestamp when SCN was received in UTC
SESSION_ID	NUMBER	NOT NULL	Session identifier of the local session that created this entry. Maps to V$SESSION.SID and to V$ACTIVE_SESSION_HISTORY.SESSION_ID.
SESSION_SERIAL#	NUMBER	NOT NULL	Session serial number of the local session that created this entry. Maps to V$SESSION.SERIAL# and to V$ACTIVE_SESSION_HISTORY.SESSION_SERIAL#.
AUDIT_SESSIONID	NUMBER		Session identifier that can be joined with DBA_AUDIT_TRAIL.SESSIONID or UNIFIED_AUDIT_TRAIL.SESSIONID (depending on which kind of auditing is enabled). Null if auditing is not enabled.
USERNAME	VARCHAR2(128)	NOT NULL	Oracle username of the user who logged into the local database. Maps to V$SESSION.USERNAME.
INBOUND_DB_LINK_SOURCE_ID	NUMBER		If the SCN was bumped by an inbound database link, then this is the inbound database link identified by the DBA_DB_LINK_SOURCES.SOURCE_ID database link. If the SCN was not increased by an inbound database link, then this value is null.
OUTBOUND_DB_LINK_NAME	VARCHAR2(128)		If the SCN was bumped by an outbound database link, then this is the outbound database link identified by the DBA_DB_LINKS.DB_LINK database link. Using this column and the OUTBOUND_DB_LINK_OWNER column, you can determine the source of the SCN increase for outbound links. If the SCN was not increased by an outbound database link, then this value is null.

Column	Datatype	NULL	Description
OUTBOUND_DB_LINK_OWNER	VARCHAR2(128)		If the SCN was bumped by an outbound database link, then this is the owner of the outbound database link identified by DBA_DB_LINKS.OWNER. Using this column and the OUTBOUND_DB_LINK_NAME column, you can determine the source of the SCN increase for outbound links. If the SCN was not increased by an outbound database link, then this value is null.
RESULT	VARCHAR2(64)	NOT NULL	The following SCN activities are captured: • REJECTED_HIGH_SCN - SCN rejection due to unreasonable value • REJECTED_HIGH_DELTA - SCN rejection due to unreasonable rate of growth • ACCEPTED - SCN accepted with warning Regular SCN activities which do not result in errors or warnings are not captured . SCN errors and warnings also appear in alert.log.
EXTERNAL_SCN	NUMBER	NOT NULL	The external SCN received from an inbound database link, an outbound database link, or a client
SCN_ADJUSTMENT	NUMBER	NOT NULL	For ACCEPTED SCNs in the RESULT column, how much the local SCN was increased. For REJECTED SCNs in the RESULT column, the attempted SCN increase.

See Also:

- "V$SESSION"
- "V$ACTIVE_SESSION_HISTORY"
- "DBA_AUDIT_TRAIL"
- "UNIFIED_AUDIT_TRAIL"
- "DBA_DB_LINKS"
- "DBA_DB_LINK_SOURCES"

5.333 DBA_EXTERNAL_TABLES

DBA_EXTERNAL_TABLES describes all external tables in the database. Its columns are the same as those in ALL_EXTERNAL_TABLES.

> **See Also:**
>
> "ALL_EXTERNAL_TABLES"

5.334 DBA_FEATURE_USAGE_STATISTICS

DBA_FEATURE_USAGE_STATISTICS displays information about database feature usage statistics.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database identifier of the database being tracked
NAME	VARCHAR2(64)	NOT NULL	Name of the feature
VERSION	VARCHAR2(17)	NOT NULL	Database version in which the feature was tracked
DETECTED_USAGES	NUMBER	NOT NULL	Number of times the system has detected usage for the feature
TOTAL_SAMPLES	NUMBER	NOT NULL	Number of times the system has woken up and checked for feature usage
CURRENTLY_USED	VARCHAR2(5)		Indicates whether usage was detected the last time the system checked (TRUE) or not (FALSE)
FIRST_USAGE_DATE	DATE		First sample time the system detected usage of the feature
LAST_USAGE_DATE	DATE		Last sample time the system detected usage of the feature
AUX_COUNT	NUMBER		This column stores feature-specific usage data in number format.
FEATURE_INFO	CLOB		This column stores feature-specific usage data in character format.
LAST_SAMPLE_DATE	DATE		The last time the system checked for usage
LAST_SAMPLE_PERIOD	NUMBER		Amount of time (in seconds) between the last two usage sample times
SAMPLE_INTERVAL	NUMBER		Sample interval
DESCRIPTION	VARCHAR2(128)		Description of the feature and usage detection logic
LAST_FEAT_SAMPLE_DATE	DATE		The last time the system checked for usage of the feature

> **Note:**
>
> Use the following SQL query to list the database features and their descriptions in alphabetical order:
>
> ```
> SELECT name, description FROM dba_feature_usage_statistics
> ORDER BY name;
> ```

5.335 DBA_FGA_AUDIT_TRAIL

DBA_FGA_AUDIT_TRAIL displays all audit records for fine-grained auditing.

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

Column	Datatype	NULL	Description
SESSION_ID	NUMBER	NOT NULL	Session id of the query
TIMESTAMP	DATE		Date and time of the query in the local database session time zone
DB_USER	VARCHAR2(128)		Database username who executed the query
OS_USER	VARCHAR2(255)		Operating system username who executed the query
USERHOST	VARCHAR2(128)		Client host machine name
CLIENT_ID	VARCHAR2(128)		Client identifier in each Oracle session
ECONTEXT_ID	VARCHAR2(64)		Application execution context identifier
EXT_NAME	VARCHAR2(4000)		External name
OBJECT_SCHEMA	VARCHAR2(128)		Owner of the table or view
OBJECT_NAME	VARCHAR2(128)		Name of the table or view
POLICY_NAME	VARCHAR2(128)		Name of the Fine-Grained Auditing Policy
SCN	NUMBER		System change number (SCN) of the query
SQL_TEXT	NVARCHAR2(2000)		SQL text of the query
SQL_BIND	NVARCHAR2(2000)		Bind variable data of the query
COMMENT$TEXT	VARCHAR2(4000)		Comments
STATEMENT_TYPE	VARCHAR2(7)		Statement type of the query: • SELECT • INSERT • UPDATE • DELETE

Column	Datatype	NULL	Description
EXTENDED_TIMESTAMP	TIMESTAMP(6) WITH TIME ZONE		Timestamp of the query in UTC (Coordinated Universal Time) time zone
PROXY_SESSIONID	NUMBER		Proxy session serial number, if an enterprise user has logged in through the proxy mechanism
GLOBAL_UID	VARCHAR2(32)		Global user identifier for the user, if the user has logged in as an enterprise user
INSTANCE_NUMBER	NUMBER		Instance number as specified by the INSTANCE_NUMBER initialization parameter
OS_PROCESS	VARCHAR2(16)		Operating System process identifier of the Oracle process
TRANSACTIONID	RAW(8)		Transaction identifier of the transaction in which the object is accessed or modified
STATEMENTID	NUMBER		Numeric ID for each statement run (a statement may cause many actions)
ENTRYID	NUMBER		Numeric ID for each audit trail entry in the session
OBJ_EDITION_NAME	VARCHAR2(128)		Name of the edition containing the audited object
DBID	NUMBER		Database identifier of the audited database
RLS_INFO	CLOB		Stores virtual private database (VPD) policy names and predicates separated by delimiter. To format the output into individual rows, use the DBMS_AUDIT_UTIL.DECODE_RLS_INFO_ATRAIL_FGA function.
CURRENT_USER	VARCHAR2(128)		Effective user for the statement execution

Note:

The SQL_BIND and SQL_TEXT columns are populated only if the policy has been created with the AUDIT_TRAIL parameter set to db, extended.

See Also:

Oracle Database PL/SQL Packages and Types Reference for more information about the DBMS_AUDIT_UTIL.DECODE_RLS_INFO_ATRAIL_FGA function.

5.336 DBA_FLASHBACK_ARCHIVE

DBA_FLASHBACK_ARCHIVE describes all flashback archives available in the database.

Related View

USER_FLASHBACK_ARCHIVE describes the flashback archives available to the current user.

Column	Datatype	NULL	Description
OWNER_NAME	VARCHAR2(255)		Name of the creator of the flashback archive
FLASHBACK_ARCHIVE_NAME	VARCHAR2(255)	NOT NULL	Name of the flashback archive
FLASHBACK_ARCHIVE#	NUMBER	NOT NULL	Number of the flashback archive
RETENTION_IN_DAYS	NUMBER	NOT NULL	Maximum duration (in days) for which data is retained in the flashback archive
CREATE_TIME	TIMESTAMP(9)		Time at which the flashback archive was created
LAST_PURGE_TIME	TIMESTAMP(9)		Time at which the data in the flashback archive was last purged by the system
STATUS	VARCHAR2(7)		Indicates whether the flashback archive is a default flashback archive for the system (DEFAULT) or not (NULL)

See Also:

"USER_FLASHBACK_ARCHIVE"

5.337 DBA_FLASHBACK_ARCHIVE_TABLES

DBA_FLASHBACK_ARCHIVE_TABLES displays information about all tables in the database that are enabled for Flashback Archive.

Related View

USER_FLASHBACK_ARCHIVE_TABLES displays information about the tables owned by the current user that are enabled for Flashback Archive.

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table enabled for Flashback Archive
OWNER_NAME	VARCHAR2(128)	NOT NULL	Owner name of the table enabled for Flashback Archive
FLASHBACK_ARCHIVE_NAME	VARCHAR2(255)	NOT NULL	Name of the flashback archive
ARCHIVE_TABLE_NAME	VARCHAR2(53)		Name of the archive table containing the historical data for the user table
STATUS	VARCHAR2(13)		Status of whether flashback archive is enabled or being disabled on the table

See Also:

"USER_FLASHBACK_ARCHIVE_TABLES"

5.338 DBA_FLASHBACK_ARCHIVE_TS

DBA_FLASHBACK_ARCHIVE_TS describes all tablespaces in the flashback archives available in the database.

Column	Datatype	NULL	Description
FLASHBACK_ARCHIVE_NAME	VARCHAR2(255)	NOT NULL	Name of the flashback archive
FLASHBACK_ARCHIVE#	NUMBER	NOT NULL	Number of the flashback archive
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of a tablespace in the flashback archive
QUOTA_IN_MB	VARCHAR2(40)		Maximum space (in MB) that can be used for Flashback Archive from the tablespace; NULL indicates no Quota restriction

5.339 DBA_FLASHBACK_TXN_REPORT

DBA_FLASHBACK_TXN_REPORT displays information about all compensating transactions that have been committed in the database.

Each row in this view is associated with one compensating transaction.

Related View

USER_FLASHBACK_TXN_REPORT displays information about the compensating transactions owned by the current user that have been committed in the database. This view does not display the USERNAME column.

Column	Datatype	NULL	Description
COMPENSATING_XID	RAW(8)	NOT NULL	Transaction responsible for backout
COMPENSATING_TXN_NAME	VARCHAR2(256)		Name of the compensating transaction
COMMIT_TIME	DATE		Timestamp when the compensating transaction committed
XID_REPORT	CLOB		An XML report describing the details of the transactions backed out by the compensating transaction
USERNAME	VARCHAR2(128)	NOT NULL	User who is executing the compensating transaction

See Also:

"USER_FLASHBACK_TXN_REPORT"

5.340 DBA_FLASHBACK_TXN_STATE

DBA_FLASHBACK_TXN_STATE displays information about the compensating status of all transactions in the database.

For each compensating transaction, there could be multiple rows, where each row provides the dependency relation between the transactions that have been compensated by the compensating transaction.

Related View

USER_FLASHBACK_TXN_STATE displays information about the compensating status of the transactions owned by the current user. This view does not display the USERNAME column.

Column	Datatype	NULL	Description
COMPENSATING_XID	RAW(8)		Transaction ID of the compensating transaction
XID	RAW(8)		A transaction that has been compensated by the compensating transaction
DEPENDENT_XID	RAW(8)		A dependent transaction of XID **Note:** In the case of BACKOUT_MODE = CASCADE, there must be another row with XID = DEPENDENT_XID of this column.
BACKOUT_MODE	VARCHAR2(16)		Mode in which XID was backed out: • NOCASCADE • NOCASCADE_FORCE • NONCONFLICT_ONLY • CASCADE
USERNAME	VARCHAR2(128)	NOT NULL	User who is performing the compensating transaction

See Also:

"USER_FLASHBACK_TXN_STATE"

5.341 DBA_FREE_SPACE

DBA_FREE_SPACE describes the free extents in all tablespaces in the database.

If a data file (or entire tablespace) is offline in a locally managed tablespace, you will not see any extent information. If an object has extents in an online file of the tablespace, you will see extent information about the offline data file. However, if the object is entirely in the offline file, a query of this view will not return any records.

If a data file does not have any free space, you will not see a row for the data file in this view.

Related View

`USER_FREE_SPACE` describes the free extents in the tablespaces accessible to the current user.

Column	Datatype	NULL	Description
`TABLESPACE_NAME`	`VARCHAR2(30)`		Name of the tablespace containing the extent
`FILE_ID`	`NUMBER`		Absolute file number of the data file containing the extent
`BLOCK_ID`	`NUMBER`		Starting block number of the extent
`BYTES`	`NUMBER`		Size of the extent (in bytes)
`BLOCKS`	`NUMBER`		Size of the extent (in Oracle blocks)
`RELATIVE_FNO`	`NUMBER`		Relative file number of the file containing the extent

See Also:

"USER_FREE_SPACE"

5.342 DBA_FREE_SPACE_COALESCED

`DBA_FREE_SPACE_COALESCED` describes statistics on coalesced space in all tablespaces in the database.

Column	Datatype	NULL	Description
`TABLESPACE_NAME`	`VARCHAR2(30)`		Name of the tablespace
`TOTAL_EXTENTS`	`NUMBER`		Total number of free extents in the tablespace
`EXTENTS_COALESCED`	`NUMBER`		Total number of coalesced free extents in the tablespace
`PERCENT_EXTENTS_COALESCED`	`NUMBER`		Percentage of coalesced free extents in the tablespace
`TOTAL_BYTES`	`NUMBER`		Total number of free bytes in the tablespace
`BYTES_COALESCED`	`NUMBER`		Total number of coalesced free bytes in the tablespace
`TOTAL_BLOCKS`	`NUMBER`		Total number of free Oracle blocks in the tablespace
`BLOCKS_COALESCED`	`NUMBER`		Total number of coalesced free Oracle blocks in the tablespace
`PERCENT_BLOCKS_COALESCED`	`NUMBER`		Percentage of coalesced free Oracle blocks in the tablespace

5.343 DBA_GG_AUTO_CDR_COLUMN_GROUPS

`DBA_GG_AUTO_CDR_COLUMN_GROUPS` provides details about all of the Oracle GoldenGate automatic conflict detection and resolution (CDR) column groups in the database.

Its columns are the same as those in `ALL_GG_AUTO_CDR_COLUMN_GROUPS`.

> **See Also:**
>
> "ALL_GG_AUTO_CDR_COLUMN_GROUPS"

5.344 DBA_GG_AUTO_CDR_COLUMNS

`DBA_GG_AUTO_CDR_COLUMNS` provides details about all of the Oracle GoldenGate automatic conflict detection and resolution (CDR) columns in the database.

Its columns are the same as those in `ALL_GG_AUTO_CDR_COLUMNS`.

> **See Also:**
>
> "ALL_GG_AUTO_CDR_COLUMNS"

5.345 DBA_GG_AUTO_CDR_TABLES

`DBA_GG_AUTO_CDR_TABLES` provides details about all the tables configured for Oracle GoldenGate automatic conflict detection and resolution (CDR).

Its columns are the same as those in `ALL_GG_AUTO_CDR_TABLES`.

> **See Also:**
>
> "ALL_GG_AUTO_CDR_TABLES"

5.346 DBA_GG_INBOUND_PROGRESS

DBA_GG_INBOUND_PROGRESS displays information about the progress made by all GoldenGate inbound servers in the database. Its columns are the same as those in ALL_GG_INBOUND_PROGRESS.

> **See Also:**
>
> "ALL_GG_INBOUND_PROGRESS"

5.347 DBA_GG_PROC_OBJECT_EXCLUSION

DBA_GG_PROC_OBJECT_EXCLUSION provides details about all tables that should be filtered when operating on given objects.

Column	Datatype	NULL	Description
PACKAGE_OWNER	VARCHAR2(384)		Procedure package owner
PACKAGE_NAME	VARCHAR2(384)		Procedure package name
OBJECT_OWNER	VARCHAR2(384)		Object owner to filter for the given procedure
OBJECT_NAME	VARCHAR2(384)		Object name to filter for the given procedure

5.348 DBA_GG_PROCEDURE_ANNOTATION

DBA_GG_PROCEDURE_ANNOTATION annotates the position of Owner and Object arguments in procedure calls.

Column	Datatype	NULL	Description
PACKAGE_OWNER	VARCHAR2(384)	NOT NULL	Procedure package owner
PACKAGE_NAME	VARCHAR2(384)	NOT NULL	Procedure package name
PROCEDURE_NAME	VARCHAR2(384)	NOT NULL	Procedure name
OBJECT_OWNER_ARGPOS	NUMBER	NOT NULL	Object owner name position in argument list, -1 if not present
OBJECT_ARGPOS	NUMBER	NOT NULL	Object name position in argument list, -1 if not present
MIN_DB_VERSION	VARCHAR2(100)		Minimum database version for the procedure
MAX_DB_VERSION	VARCHAR2(100)		Maximum database version for the procedure
MIN_REDO_COMPAT_LEVEL	VARCHAR2(100)		Minimum redo compatibility for the procedure
MAX_REDO_COMPAT_LEVEL	VARCHAR2(100)		Maximum redo compatibility for the procedure
FLAGS	NUMBER		Additional information about procedure arguments

5.349 DBA_GG_SUPPORTED_PACKAGES

DBA_GG_SUPPORTED_PACKAGES provides details about supported procedure packages for Oracle GoldenGate replication.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(384)	NOT NULL	Procedure package owner
NAME	VARCHAR2(384)	NOT NULL	Procedure package name
FEATURE	VARCHAR2(384)	NOT NULL	DBMS feature that the procedure package belongs to
MIN_DB_VERSION	VARCHAR2(100)		Minimum database version for the supported package
MAX_DB_VERSION	VARCHAR2(100)		Maximum database version for the supported package
MIN_REDO_COMPAT_LEVEL	VARCHAR2(100)		Minimum redo compatibility for the supported package
MAX_REDO_COMPAT_LEVEL	VARCHAR2(100)		Maximum redo compatibility for the supported package
SUPPORTED_LEVEL	VARCHAR2(100)		Supported level of the package

5.350 DBA_GG_SUPPORTED_PROCEDURES

DBA_GG_SUPPORTED_PROCEDURES provides details about all procedures that are supported for Oracle GoldenGate replication.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Procedure package owner
PACKAGE_NAME	VARCHAR2(128)		Procedure package name
PROCEDURE_NAME	VARCHAR2(128)		Procedure name
MIN_DB_VERSION	VARCHAR2(100)		Minimum database version for the procedure
MAX_DB_VERSION	VARCHAR2(100)		Maximum database version for the procedure
MIN_REDO_COMPAT_LEVEL	VARCHAR2(100)		Minimum redo compatibility for the procedure
MAX_REDO_COMPAT_LEVEL	VARCHAR2(100)		Maximum redo compatibility for the procedure
SUPPORTED_MODE	VARCHAR2(100)		Supported mode for the procedure: ALWAYS or DBMS_ROLLING
EXCLUSION_RULE_EXISTS	VARCHAR2(3)		Specifies whether an exclusion rule exists for the procedure (YES) or not (NO). **See Also:** "DBA_GG_PROC_OBJECT_EXCLUSION"

5.351 DBA_GLOBAL_CONTEXT

DBA_GLOBAL_CONTEXT displays the definition (name, schema, and package) of all global contexts created in the database.

This view is a subset of DBA_CONTEXT, which describes all contexts, including global contexts.

Column	Datatype	NULL	Description
NAMESPACE	VARCHAR2(128)	NOT NULL	Name of the context namespace
SCHEMA	VARCHAR2(128)	NOT NULL	Schema of the package that administers the globally accessible context
PACKAGE	VARCHAR2(128)	NOT NULL	Package that administers the globally accessible context

See Also:

- "DBA_CONTEXT"
- *Oracle Database Security Guide* for more information about using global application contexts
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SESSION.SET_CONTEXT procedure

5.352 DBA_GOLDENGATE_INBOUND

DBA_GOLDENGATE_INBOUND displays information about all GoldenGate inbound servers in the database. Its columns are the same as those in ALL_GOLDENGATE_INBOUND.

See Also:

"ALL_GOLDENGATE_INBOUND"

5.353 DBA_GOLDENGATE_NOT_UNIQUE

DBA_GOLDENGATE_NOT_UNIQUE displays all tables that have no primary and no non-null unique indexes.

Most of the tables displayed by this view are supported because their columns contain enough information to be maintained by Oracle GoldenGate. Some tables, however, cannot be supported because their columns do not contain the necessary information. Unsupported tables usually contain a column defined using an unsupported data type.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Schema name of the non-unique table

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2(128)		Table name of the non-unique table
BAD_COLUMN	VARCHAR2(1)		Indicates that the table has a column not useful in the where clause. Possible values: • Y - Table column is defined using an unbounded data type, such as LONG or BLOB. If two rows in the table match except in their LOB columns, then the table cannot be maintained properly. Log apply services will attempt to maintain these tables, but you must ensure the application does not allow uniqueness only in the unbounded columns. • N - Enough column information is present to maintain the table in Oracle GoldenGate but the log transport services and log apply services would run more efficiently if you added a primary key. You should consider adding a disabled RELY constraint to these tables.

5.354 DBA_GOLDENGATE_PRIVILEGES

DBA_GOLDENGATE_PRIVILEGES displays details about Oracle GoldenGate privileges. Its columns are the same as those in ALL_GOLDENGATE_PRIVILEGES.

> **See Also:**
>
> "ALL_GOLDENGATE_PRIVILEGES"

5.355 DBA_GOLDENGATE_RULES

DBA_GOLDENGATE_RULES displays information about all GoldenGate server rules in the database. Its columns are the same as those in ALL_GOLDENGATE_RULES.

> **See Also:**
>
> "ALL_GOLDENGATE_RULES"

5.356 DBA_GOLDENGATE_SUPPORT_MODE

DBA_GOLDENGATE_SUPPORT_MODE displays information about the level of Oracle GoldenGate capture process support for the tables in the database.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Table owner
OBJECT_NAME	VARCHAR2(128)		Table name
SUPPORT_MODE	VARCHAR2(6)		Capture process support level for the table: • FULL - A capture process can capture changes made to all of the columns in the table • ID KEY - A capture process can capture changes made to the key columns and any other columns in the table supported by the capture process, except for LOB, LONG, LONG RAW, and XMLType columns. • INTERNAL - A capture process cannot capture changes made to any columns in the table because the table is secondary to a user-created table and is updated implicitly when changes are made to the user-created table. Such tables include mapping tables for index-organized tables, storage tables for nested tables, materialized view logs, secondary objects associated with domain indexes, and temporary tables. • PLSQL - A capture process can capture changes made to the table as long as Procedural Supplemental Logging is enabled on the source database. Such tables include hierarchy-enabled tables, AQ queue tables, and tables containing columns of type MDSYS.SDO_TOPO_GEOMETRY, MDSYS.SDO_GEORASTER, or MDSYS.SDO_RDF_TRIPLE_S. • NONE - A capture process cannot capture changes made to any columns in the table because the table is not supported for replication.
EXPLANATION	VARCHAR2(4000)		Reason the table does not have FULL capture process support This column is populated only when both of the following conditions are met: • The value of the COMPATIBLE initialization parameter is 20.0 or higher • The value of the SUPPORT_MODE column is ID KEY, INTERNAL, PLSQL, or NONE

5.357 DBA_HANG_MANAGER_PARAMETERS

DBA_HANG_MANAGER_PARAMETERS shows the available user-tunable Blocker Resolver parameters and their values.

> **Note:**
>
> This view is deprecated. Oracle recommends that you instead use the DBA_BLOCKER_RESOLVER_PARAMETERS view.

> **See Also:**
>
> "DBA_BLOCKER_RESOLVER_PARAMETERS"

5.358 DBA_HEAT_MAP_SEG_HISTOGRAM

DBA_HEAT_MAP_SEG_HISTOGRAM displays segment access information for all segments. Its columns are the same as those in ALL_HEAT_MAP_SEG_HISTOGRAM.

> **See Also:**
>
> "ALL_HEAT_MAP_SEG_HISTOGRAM"

5.359 DBA_HEAT_MAP_SEGMENT

DBA_HEAT_MAP_SEGMENT displays the latest segment access time for all segments. Its columns are the same as those in ALL_HEAT_MAP_SEGMENT.

> **See Also:**
>
> "ALL_HEAT_MAP_SEGMENT"

5.360 DBA_HEATMAP_TOP_OBJECTS

DBA_HEATMAP_TOP_OBJECTS displays heat map information for the top 10000 objects by default.

If the database contains fewer than 10000 objects, then fewer than 10000 objects are returned by the view.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Object owner
OBJECT_NAME	VARCHAR2(128)		Object name
OBJECT_TYPE	VARCHAR2(18)		Object type
TABLESPACE_NAME	VARCHAR2(30)		Tablespace name
SEGMENT_COUNT	NUMBER		Segments in the tablespace
OBJECT_SIZE	NUMBER		Size of the object in MB
MIN_WRITETIME	DATE		Oldest modification time for a set of blocks
MAX_WRITETIME	DATE		Latest modification time for a set of blocks
AVG_WRITETIME	DATE		Average of the modification times for a set of blocks
MIN_READTIME	DATE		Oldest read time for a set of blocks
MAX_READTIME	DATE		Latest read time for a set of blocks
AVG_READTIME	DATE		Average of the read times for a set of blocks
MIN_FTSTIME	DATE		Minimum full table scan time of the object
MAX_FTSTIME	DATE		Maximum full table scan time of the object
AVG_FTSTIME	DATE		Average full table scan time of the object
MIN_LOOKUPTIME	DATE		Minimum lookup time of the object
MAX_LOOKUPTIME	DATE		Maximum lookup time of the object
AVG_LOOKUPTIME	DATE		Average lookup time of the object

5.361 DBA_HEATMAP_TOP_TABLESPACES

DBA_HEATMAP_TOP_TABLESPACES displays heat map information for the top 100 tablespaces.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2(128)		Tablespace name
SEGMENT_COUNT	NUMBER		Segments in the tablespace
ALLOCATED_BYTES	NUMBER		Total bytes allocated to the objects in the tablespace
MIN_WRITETIME	DATE		Minimum write time of objects tracked
MAX_WRITETIME	DATE		Maximum write time of objects tracked
AVG_WRITETIME	DATE		Average write time of objects tracked
MIN_READTIME	DATE		Minimum read time of objects tracked
MAX_READTIME	DATE		Maximum read time of objects tracked
AVG_READTIME	DATE		Average read time of objects tracked
MIN_FTSTIME	DATE		Minimum full table scan time of objects tracked
MAX_FTSTIME	DATE		Maximum full table scan time of objects tracked
AVG_FTSTIME	DATE		Average full table scan time of objects tracked
MIN_LOOKUPTIME	DATE		Minimum lookup time of objects tracked
MAX_LOOKUPTIME	DATE		Maximum lookup time of objects tracked

Column	Datatype	NULL	Description
AVG_LOOKUPTIME	DATE		Average lookup time of objects tracked

5.362 DBA_HIER_CLASS

DBA_HIER_CLASS describes the classifications of all hierarchies in the database. Its columns are the same as those in ALL_HIER_CLASS.

> **See Also:**
>
> "ALL_HIER_CLASS"

5.363 DBA_HIER_CLASS_AE

DBA_HIER_CLASS_AE describes the classifications of all hierarchies (across all editions) in the database. Its columns are the same as those in ALL_HIER_CLASS_AE.

> **See Also:**
>
> "ALL_HIER_CLASS_AE"

5.364 DBA_HIER_COLUMNS

DBA_HIER_COLUMNS describes the columns of all hierarchies in the database. Its columns are the same as those in ALL_HIER_COLUMNS.

> **See Also:**
>
> "ALL_HIER_COLUMNS"

5.365 DBA_HIER_COLUMNS_AE

DBA_HIER_COLUMNS_AE describes the columns of all hierarchies (across all editions) in the database. Its columns are the same as those in ALL_HIER_COLUMNS_AE.

> **See Also:**
>
> "ALL_HIER_COLUMNS_AE"

5.366 DBA_HIER_HIER_ATTR_CLASS

`DBA_HIER_HIER_ATTR_CLASS` describes the classifications of the hierarchical attributes of all hierarchies in the database. Its columns are the same as those in `ALL_HIER_HIER_ATTR_CLASS`.

> **See Also:**
>
> "ALL_HIER_HIER_ATTR_CLASS"

5.367 DBA_HIER_HIER_ATTR_CLASS_AE

`DBA_HIER_HIER_ATTR_CLASS_AE` describes the classifications of the hierarchical attributes of all hierarchies (across all editions) in the database. Its columns are the same as those in `ALL_HIER_HIER_ATTR_CLASS_AE`.

> **See Also:**
>
> "ALL_HIER_HIER_ATTR_CLASS_AE"

5.368 DBA_HIER_HIER_ATTRIBUTES

`DBA_HIER_HIER_ATTRIBUTES` describes the hierarchical attributes of all hierarchies in the database. Its columns are the same as those in `ALL_HIER_HIER_ATTRIBUTES`.

> **See Also:**
>
> "ALL_HIER_HIER_ATTRIBUTES"

5.369 DBA_HIER_HIER_ATTRIBUTES_AE

`DBA_HIER_HIER_ATTRIBUTES_AE` describes the hierarchical attributes of all hierarchies (across all editions) in the database. Its columns are the same as those in `ALL_HIER_HIER_ATTRIBUTES_AE`.

> **See Also:**
>
> "ALL_HIER_HIER_ATTRIBUTES_AE"

5.370 DBA_HIER_JOIN_PATHS

DBA_HIER_JOIN_PATHS describes the join paths for all hierarchies in the database. Its columns are the same as those in ALL_HIER_JOIN_PATHS.

> **See Also:**
>
> "ALL_HIER_JOIN_PATHS"

5.371 DBA_HIER_JOIN_PATHS_AE

DBA_HIER_JOIN_PATHS_AE describes the join paths for all hierarchies (across all editions) in the database. Its columns are the same as those in ALL_HIER_JOIN_PATHS_AE.

> **See Also:**
>
> "ALL_HIER_JOIN_PATHS_AE"

5.372 DBA_HIER_LEVEL_ID_ATTRS

DBA_HIER_LEVEL_ID_ATTRS describes the attributes that uniquely identify members of the levels of all hierarchies in the database. Its columns are the same as those in ALL_HIER_LEVEL_ID_ATTRS.

> **See Also:**
>
> "ALL_HIER_LEVEL_ID_ATTRS"

5.373 DBA_HIER_LEVEL_ID_ATTRS_AE

DBA_HIER_LEVEL_ID_ATTRS_AE describes the attributes that uniquely identify members of the levels of all hierarchies (across all editions) in the database. Its columns are the same as those in ALL_HIER_LEVEL_ID_ATTRS_AE.

> **See Also:**
>
> "ALL_HIER_LEVEL_ID_ATTRS_AE"

5.374 DBA_HIER_LEVELS

DBA_HIER_LEVELS describes the levels of all hierarchies in the database. Its columns are the same as those in ALL_HIER_LEVELS.

> **See Also:**
>
> "ALL_HIER_LEVELS"

5.375 DBA_HIER_LEVELS_AE

DBA_HIER_LEVELS_AE describes the levels of all hierarchies (across all editions) in the database. Its columns are the same as those in ALL_HIER_LEVELS_AE.

> **See Also:**
>
> "ALL_HIER_LEVELS_AE"

5.376 DBA_HIERARCHIES

DBA_HIERARCHIES describes all hierarchies in the database. Its columns are the same as those in ALL_HIERARCHIES.

> **See Also:**
>
> "ALL_HIERARCHIES"

5.377 DBA_HIERARCHIES_AE

DBA_HIERARCHIES_AE describes all hierarchies (across all editions) in the database. Its columns are the same as those in ALL_HIERARCHIES_AE.

> **See Also:**
>
> "ALL_HIERARCHIES_AE"

5.378 DBA_HIGH_WATER_MARK_STATISTICS

DBA_HIGH_WATER_MARK_STATISTICS displays information about database high-watermark statistics.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Identifier of the database for which the high-watermark statistics are tracked
NAME	VARCHAR2(64)	NOT NULL	Name of the high-watermark statistic (see Table 5-1)
VERSION	VARCHAR2(17)	NOT NULL	Database version in which the high watermarks were tracked
HIGHWATER	NUMBER		Highest value of the statistic seen at sampling time
LAST_VALUE	NUMBER		Value of the statistic at the last sample time
DESCRIPTION	VARCHAR2(128)		Description of the high-watermark statistics (see Table 5-1)

Table 5-1 DBA_HIGH_WATER_MARK_STATISTICS Statistics

Name	Description
ACTIVE_SESSIONS	Maximum Number of Active Sessions seen in the system
CPU_COUNT	Maximum Number of CPUs
DATAFILES	Maximum Number of Datafiles
DB_SIZE	Maximum Size of the Database (Bytes)
EXADATA_DISKS	Number of physical disks
INSTANCES	Oracle Database instances
PART_INDEXES	Maximum Number of Partitions belonging to an User Index
PART_TABLES	Maximum Number of Partitions belonging to an User Table
QUERY_LENGTH	Maximum Query Length
SEGMENT_SIZE	Size of Largest Segment (Bytes)
SESSIONS	Maximum Number of Concurrent Sessions seen in the database
SQL_NCHAR_COLUMNS	Maximum Number of SQL NCHAR Columns
TABLESPACES	Maximum Number of Tablespaces
USER_INDEXES	Number of User Indexes
USER_MV	Maximum Number of Materialized Views (User)
USER_TABLES	Number of User Tables

5.379 DBA_HIST_ACTIVE_SESS_HISTORY

DBA_HIST_ACTIVE_SESS_HISTORY displays the history of the contents of the in-memory active session history of recent system activity.

DBA_HIST_ACTIVE_SESS_HISTORY contains snapshots of V$ACTIVE_SESSION_HISTORY. See "V$ACTIVE_SESSION_HISTORY" for further interpretation details for many of these columns (except SNAP_ID, DBID, and INSTANCE_NUMBER).

> **Note:**
>
> If you want to perform a join with the snapshots view, use the DBA_HIST_ASH_SNAPSHOT view instead of the DBA_HIST_SNAPSHOT view.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SAMPLE_ID	NUMBER	NOT NULL	ID of the sample
SAMPLE_TIME	TIMESTAMP(3)	NOT NULL	Time of the sample
SAMPLE_TIME_UTC	TIMESTAMP(3)		SAMPLE_TIME in UTC
USECS_PER_ROW	NUMBER		Time in microseconds since the last active session history sample
SESSION_ID	NUMBER	NOT NULL	Session identifier
SESSION_SERIAL#	NUMBER		Session serial number (used to uniquely identify a session's objects)
SESSION_TYPE	VARCHAR2(10)		Session type: • FOREGROUND • BACKGROUND
FLAGS	NUMBER		Reserved for future use
USER_ID	NUMBER		Oracle user identifier
SQL_ID	VARCHAR2(13)		SQL identifier of the SQL statement that is currently being executed
IS_SQLID_CURRENT	VARCHAR2(1)		Indicates whether the SQL identifier in the SQL_ID column is being executed (Y) or not (N)
SQL_CHILD_NUMBER	NUMBER		Child number of the SQL statement that is currently being executed
SQL_OPCODE	NUMBER		Indicates what phase of operation the SQL statement is in
SQL_OPNAME	VARCHAR2(64)		SQL command name
FORCE_MATCHING_SIGNATURE	NUMBER		Signature used when the CURSOR_SHARING parameter is set to FORCE
TOP_LEVEL_SQL_ID	VARCHAR2(13)		SQL identifier of the top level SQL statement

Column	Datatype	NULL	Description
TOP_LEVEL_SQL_OPCODE	NUMBER		Indicates what phase of operation the top level SQL statement was in
SQL_PLAN_HASH_VALUE	NUMBER		Numerical representation of the SQL plan for the cursor
SQL_FULL_PLAN_HASH_VALUE	NUMBER		Numerical representation of the complete SQL plan for the cursor being executed by this session
SQL_ADAPTIVE_PLAN_RESOLVED	NUMBER		Indicates whether the SQL plan of the sampled database session is a resolved adaptive plan or not
SQL_PLAN_LINE_ID	NUMBER		SQL plan line ID
SQL_PLAN_OPERATION	VARCHAR2(64)		Plan operation name
SQL_PLAN_OPTIONS	VARCHAR2(64)		Plan operation options
SQL_EXEC_ID	NUMBER		SQL execution identifier
SQL_EXEC_START	DATE		Time when the execution of the SQL started
PLSQL_ENTRY_OBJECT_ID	NUMBER		Object ID of the top-most PL/SQL subprogram on the stack (or NULL if there is no PL/SQL subprogram on the stack)
PLSQL_ENTRY_SUBPROGRAM_ID	NUMBER		Subprogram ID of the top-most PL/SQL subprogram on the stack (or NULL if there is no PL/SQL subprogram on the stack)
PLSQL_OBJECT_ID	NUMBER		Object ID of the currently executing PL/SQL subprogram (or NULL if executing SQL)
PLSQL_SUBPROGRAM_ID	NUMBER		Subprogram ID of the currently executing PL/SQL object (or NULL if executing SQL)
QC_INSTANCE_ID	NUMBER		Query coordinator instance ID
QC_SESSION_ID	NUMBER		Query coordinator session ID
QC_SESSION_SERIAL#	NUMBER		Query coordinator session serial number
PX_FLAGS	NUMBER		Reserved for internal use
EVENT	VARCHAR2(64)		If SESSION_STATE = WAITING, then the event for which the session was waiting at the time of sampling. If SESSION_STATE = ON CPU, then this column will be NULL.
EVENT_ID	NUMBER		Identifier of the resource or event for which the session is waiting or for which the session last waited
SEQ#	NUMBER		Sequence number that uniquely identifies the wait (incremented for each wait)
P1TEXT	VARCHAR2(64)		Text of first additional parameter
P1	NUMBER		First additional parameter
P2TEXT	VARCHAR2(64)		Text of second additional parameter
P2	NUMBER		Second additional parameter
P3TEXT	VARCHAR2(64)		Text of third additional parameter
P3	NUMBER		Third additional parameter

Column	Datatype	NULL	Description
WAIT_CLASS	VARCHAR2(64)		Wait class name of the event for which the session was waiting at the time of sampling. Interpretation is similar to that of the EVENT column. Maps to V$SESSION.WAIT_CLASS.
WAIT_CLASS_ID	NUMBER		Wait class identifier of the event for which the session was waiting at the time of sampling. Interpretation is similar to that of the EVENT column. Maps to V$SESSION.WAIT_CLASS_ID.
WAIT_TIME	NUMBER		Total wait time (in microseconds) for the event for which the session last waited (0 if currently waiting)
SESSION_STATE	VARCHAR2(7)		Session state: • WAITING • ON CPU
TIME_WAITED	NUMBER		Time that the current session actually spent waiting for the event (in microseconds). This column is set for waits that were in progress at the time the sample was taken.
BLOCKING_SESSION_STATUS	VARCHAR2(11)		Status of the blocking session: • VALID • NO HOLDER • GLOBAL • NOT IN WAIT • UNKNOWN
BLOCKING_SESSION	NUMBER		Session identifier of the blocking session. Populated only when the session was waiting for enqueues or a "buffer busy" wait. Maps to V$SESSION.BLOCKING_SESSION.
BLOCKING_SESSION_SERIAL#	NUMBER		Serial number of the blocking session
BLOCKING_INST_ID	NUMBER		Instance number of the blocker shown in BLOCKING_SESSION
BLOCKING_HANGCHAIN_INFO	VARCHAR2(1)		Indicates whether the information about BLOCKING_SESSION comes from the hang chain (Y) or not (N)
CURRENT_OBJ#	NUMBER		Object ID of the object that the session is currently referencing. This information is only available if the session was waiting for Application, Cluster, Concurrency, and User I/O wait events. Maps to V$SESSION.ROW_WAIT_OBJ#.
CURRENT_FILE#	NUMBER		File number of the file containing the block that the session is currently referencing. This information is only available if the session was waiting for Cluster, Concurrency, and User I/O wait events. Maps to V$SESSION.ROW_WAIT_FILE#.
CURRENT_BLOCK#	NUMBER		ID of the block that the session is currently referencing
CURRENT_ROW#	NUMBER		Row identifier that the session is referencing
TOP_LEVEL_CALL#	NUMBER		Oracle top level call number

Column	Datatype	NULL	Description
TOP_LEVEL_CALL_NAME	VARCHAR2(64)		Oracle top level call name
CONSUMER_GROUP_ID	NUMBER		Consumer group ID
XID	RAW(8)		Transaction ID that the session was working on at the time of sampling. V$SESSION does not contain this information.
REMOTE_INSTANCE#	NUMBER		Remote instance identifier that will serve the block that this session is waiting for. This information is only available if the session was waiting for cluster events.
TIME_MODEL	NUMBER		Time model information
IN_CONNECTION_MGMT	VARCHAR2(1)		Indicates whether the session was doing connection management at the time of sampling (Y) or not (N)
IN_PARSE	VARCHAR2(1)		Indicates whether the session was parsing at the time of sampling (Y) or not (N)
IN_HARD_PARSE	VARCHAR2(1)		Indicates whether the session was hard parsing at the time of sampling (Y) or not (N)
IN_SQL_EXECUTION	VARCHAR2(1)		Indicates whether the session was executing SQL statements at the time of sampling (Y) or not (N)
IN_PLSQL_EXECUTION	VARCHAR2(1)		Indicates whether the session was executing PL/SQL at the time of sampling (Y) or not (N)
IN_PLSQL_RPC	VARCHAR2(1)		Indicates whether the session was executing inbound PL/SQL RPC calls at the time of sampling (Y) or not (N)
IN_PLSQL_COMPILATION	VARCHAR2(1)		Indicates whether the session was compiling PL/SQL at the time of sampling (Y) or not (N)
IN_JAVA_EXECUTION	VARCHAR2(1)		Indicates whether the session was executing Java at the time of sampling (Y) or not (N)
IN_BIND	VARCHAR2(1)		Indicates whether the session was doing bind operations at the time of sampling (Y) or not (N)
IN_CURSOR_CLOSE	VARCHAR2(1)		Indicates whether the session was closing a cursor at the time of sampling (Y) or not (N)
IN_SEQUENCE_LOAD	VARCHAR2(1)		Indicates whether the session is loading in sequence (in sequence load code) (Y) or not (N)
IN_INMEMORY_QUERY	VARCHAR2(1)		Indicates whether the session was querying the In-Memory Column Store (IM column store) at the time of sampling (Y) or not (N)
IN_INMEMORY_POPULATE	VARCHAR2(1)		Indicates whether the session was populating the IM column store at the time of sampling (Y) or not (N)
IN_INMEMORY_PREPOPULATE	VARCHAR2(1)		Indicates whether the session was prepopulating the IM column store at the time of sampling (Y) or not (N)
IN_INMEMORY_REPOPULATE	VARCHAR2(1)		Indicates whether the session was repopulating the IM column store at the time of sampling (Y) or not (N)

Column	Datatype	NULL	Description
IN_INMEMORY_TREPOPULATE	VARCHAR2(1)		Indicates whether the session was trickle repopulating the IM column store at the time of sampling (Y) or not (N)
IN_TABLESPACE_ENCRYPTION	VARCHAR2(1)		Indicates whether encryption or decryption of a tablespace occurred at the time of sampling (Y) or not (N)
CAPTURE_OVERHEAD	VARCHAR2(1)		Indicates whether the session is executing capture code (Y) or not (N)
REPLAY_OVERHEAD	VARCHAR2(1)		Indicates whether the session is executing replay code (Y) or not (N)
IS_CAPTURED	VARCHAR2(1)		Indicates whether the session is being captured (Y) or not (N)
IS_REPLAYED	VARCHAR2(1)		Indicates whether the session is being replayed (Y) or not (N)
IS_REPLAY_SYNC_TOKEN_HOLDER	VARCHAR2(1)		Indicates whether the session is holding a synchronization token (Y) or not (N) during workload replay
SPID	VARCHAR2(24)		Operating system process identifier
STID	VARCHAR2(24)		Operating system thread identifier
SERVICE_HASH	NUMBER		Hash that identifies the Service
PROGRAM	VARCHAR2(84)		Name of the operating system program
MODULE	VARCHAR2(64)		Name of the currently executing module as set by the DBMS_APPLICATION_INFO.SET_MODULE procedure
ACTION	VARCHAR2(64)		Name of the currently executing action as set by the DBMS_APPLICATION_INFO.SET_ACTION procedure
CLIENT_ID	VARCHAR2(64)		Client identifier of the session
CLIENT_INFO	VARCHAR2(64)		Client information for the session
MACHINE	VARCHAR2(64)		Client's operating system machine name
PORT	NUMBER		Client port number
ECID	VARCHAR2(64)		Execution context identifier (sent by Application Server)
DBREPLAY_FILE_ID	NUMBER		If the session is being captured or replayed, then DBREPLAY_FILE_ID is the file ID for the workload capture or workload replay; otherwise it is NULL.
DBREPLAY_CALL_COUNTER	NUMBER		If the session is being captured or replayed, then DBREPLAY_CALL_COUNTER is the call counter of the user call that is being captured or replayed; otherwise it is NULL.
TM_DELTA_TIME	NUMBER		Time interval (in microseconds) over which TM_DELTA_CPU_TIME and TM_DELTA_DB_TIME are accumulated
TM_DELTA_CPU_TIME	NUMBER		Amount of time this session spent on CPU over the last TM_DELTA_TIME microseconds
TM_DELTA_DB_TIME	NUMBER		Amount of time spent by this session in database calls over the last TM_DELTA_TIME microseconds

Column	Datatype	NULL	Description
DELTA_TIME	NUMBER		Time interval (microseconds) since the last time this session was sampled or created, over which the next five statistics are accumulated
DELTA_READ_IO_REQUESTS	NUMBER		Number of read I/O requests made by this session over the last DELTA_TIME microseconds
DELTA_WRITE_IO_REQUESTS	NUMBER		Number of write I/O requests made by this session over the last DELTA_TIME microseconds
DELTA_READ_IO_BYTES	NUMBER		Number of I/O bytes read by this session over the last DELTA_TIME microseconds
DELTA_WRITE_IO_BYTES	NUMBER		Number of I/O bytes written by this session over the last DELTA_TIME microseconds
DELTA_INTERCONNECT_IO_BYTES	NUMBER		Number of I/O bytes sent over the I/O interconnect over the last DELTA_TIME microseconds
PGA_ALLOCATED	NUMBER		Amount of PGA memory (in bytes) consumed by this session at the time this sample was taken
TEMP_SPACE_ALLOCATED	NUMBER		Amount of TEMP memory (in bytes) consumed by this session at the time this sample was taken
DBOP_NAME	VARCHAR2(64)		Database operation name. If the type is SQL, the DBOP_NAME will be NULL.
DBOP_EXEC_ID	NUMBER		Database operation execution identifier for the current execution. If the type is SQL, the DBOP_EXEC_ID will be NULL.
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "DBA_HIST_ASH_SNAPSHOT"
- "DBA_HIST_SNAPSHOT"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLICATION_INFO package

5.380 DBA_HIST_APPLY_SUMMARY

DBA_HIST_APPLY_SUMMARY displays historical statistics information about each apply process for Oracle GoldenGate, and Oracle XStream. This view is intended for use with Automatic Workload Repository (AWR).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
APPLY_NAME	VARCHAR2(128)	NOT NULL	Name of the apply process
STARTUP_TIME	DATE	NOT NULL	The time that the apply process was last started
READER_TOTAL_MESSAGES_DEQUEUED	NUMBER		Total number of messages dequeued since the apply process was last started
READER_LAG	NUMBER		For captured messages, the delay (in seconds) between the creation of the last message and it being received by the apply process. For user enqueued messages, the delay between the message being enqueued in the local database and being received by the apply process.
COORD_TOTAL_RECEIVED	NUMBER		Total number of transactions received by the coordinator process since the apply process was last started
COORD_TOTAL_APPLIED	NUMBER		Total number of transactions applied by the apply process since the apply process was last started
COORD_TOTAL_ROLLBACKS	NUMBER		Number of transactions which were rolled back due to unexpected contention
COORD_TOTAL_WAIT_DEPS	NUMBER		Number of times since the apply process was last started that an apply server waited to apply a logical change record (LCR) in a transaction until another apply server applied a transaction because of a dependency between the transactions
COORD_TOTAL_WAIT_CMTS	NUMBER		Number of times since the apply process was last started that an apply server waited to commit a transaction until another apply server committed a transaction to serialize commits
COORD_LWM_LAG	NUMBER		For captured messages, the delay (in seconds) between the creation of the message corresponding to the low watermark and it being applied by the apply process. For user enqueued messages, the delay between the message being enqueued in the local database and being applied by the apply process.
SERVER_TOTAL_MESSAGES_APPLIED	NUMBER		Total number of messages applied by all the apply servers since the apply process was last started
SERVER_ELAPSED_DEQUEUE_TIME	NUMBER		Time elapsed (in hundredths of a second) dequeuing messages by all the apply servers since the apply process was last started

Column	Datatype	NULL	Description
SERVER_ELAPSED_APPLY_TIME	NUMBER		Time elapsed (in hundredths of a second) applying messages by all the apply servers since the apply process was last started
CON_DBID	NUMBER		The database ID of the PDB
REPLICAT_NAME	VARCHAR2(128)		The name of the replicat group created from GGSCI using GoldenGate
UNASSIGNED_COMPLETE_TXN	NUMBER		Total number of complete transactions that the coordinator has not assigned to any apply servers
TOTAL_LCRS_RETRIED	NUMBER		Total number of LCRs retried by this server
TOTAL_TRANSACTIONS_RETRIED	NUMBER		Total transactions retried by this server
TOTAL_ERRORS	NUMBER		Number of transactions applied by the apply process that resulted in an apply error since the apply process was last started
SESSION_MODULE	VARCHAR2(64)	NOT NULL	Session module. Valid values: • XStream • GoldenGate
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.381 DBA_HIST_ASH_SNAPSHOT

DBA_HIST_ASH_SNAPSHOT provides the list of snapshots that contains Active Session History (ASH) data.

This view differs from DBA_HIST_SNAPSHOT in that it provides snapshots which had errors flushing some Automatic Workload Repository (AWR) tables, but for which ASH data may be successfully flushed (DBA_HIST_SNAPSHOT filters out snapshots which had errors flushing AWR tables).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
STARTUP_TIME	TIMESTAMP(3)	NOT NULL	Startup time of the instance
BEGIN_INTERVAL_TIME	TIMESTAMP(3)	NOT NULL	Time at the beginning of the snapshot interval
END_INTERVAL_TIME	TIMESTAMP(3)	NOT NULL	Time at the end of the snapshot interval; the actual time the snapshot was taken
FLUSH_ELAPSED	INTERVAL DAY(5) TO SECOND(1)		Amount of time to perform the snapshot

Column	Datatype	NULL	Description
SNAP_LEVEL	NUMBER		Snapshot level
STATUS	NUMBER		Indicates if the snapshot was successfully flushed without any errors. Possible values: • 0 - No errors • 1 - Errors on some AWR tables
ERROR_COUNT	NUMBER		Number of errors occurring in the tables for the particular snapshot
BL_MOVED	NUMBER		Reserved for internal use
SNAP_FLAG	NUMBER		Condition under which the snapshot was inserted. Possible values are: • 1 - Manual snapshot created using a PL/SQL package • 2 - Imported snapshot • 4 - Snapshot taken while Diagnostic Pack or Tuning Pack was not enabled
SNAP_TIMEZONE	INTERVAL DAY(0) TO SECOND(0)		Snapshot time zone expressed as offset from UTC (Coordinated Universal Time) time zone
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"DBA_HIST_SNAPSHOT"

5.382 DBA_HIST_BASELINE

DBA_HIST_BASELINE displays information on baselines taken in the system.

For each baseline, this view displays the complete time range and whether the baseline is the default baseline.

Column	Datatype	NULL	Description
DBID	NUMBER		Database ID
BASELINE_ID	NUMBER		Internal ID for the baseline
BASELINE_NAME	VARCHAR2(64)		User-specified name for the baseline

Column	Datatype	NULL	Description
BASELINE_TYPE	VARCHAR2(13)		The baseline type, as follows: STATIC - baselines that are created manually by the user MOVING WINDOW - baselines that have dynamic start and end snapshot IDs GENERATED - baselines that are automatically generated by the system, using a template
START_SNAP_ID	NUMBER		Start snapshot ID for the baseline
START_SNAP_TIME	TIMESTAMP(3)		Time associated with the start snapshot ID
END_SNAP_ID	NUMBER		End snapshot ID for the baseline
END_SNAP_TIME	TIMESTAMP(3)		Time associated with the end snapshot ID
MOVING_WINDOW_SIZE	NUMBER		If BASELINE_TYPE is MOVING WINDOW, this field is the size of the moving window in number of days. If NULL, then the window size is the value of the AWR retention setting.
CREATION_TIME	DATE		Time the baseline was created
EXPIRATION	NUMBER		How long to keep the baseline, in number of days. A NULL value means that the baseline will be kept forever.
TEMPLATE_NAME	VARCHAR2(64)		Name of the template that created this baseline, if any.
LAST_TIME_COMPUTED	DATE		Last time that statistics were computed on the baseline.
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.383 DBA_HIST_BASELINE_DETAILS

DBA_HIST_BASELINE_DETAILS displays details about the baseline.

Column	Datatype	NULL	Description
DBID	NUMBER		Database ID
INSTANCE_NUMBER	NUMBER		Instance ID for the baseline data
BASELINE_ID	NUMBER		Internal ID for the baseline
BASELINE_NAME	VARCHAR2(64)		User-specified name for the baseline

Column	Datatype	NULL	Description
BASELINE_TYPE	VARCHAR2(13)		The baseline type, as follows: STATIC - baselines that are created manually by the user MOVING WINDOW - baselines that have dynamic start and end snapshot IDs GENERATED - baselines that are automatically generated by the system, using a template
START_SNAP_ID	NUMBER		Start snapshot ID for the baseline
START_SNAP_TIME	TIMESTAMP(3)		Start snapshot time for the baseline
END_SNAP_ID	NUMBER		End snapshot ID for the baseline
END_SNAP_TIME	TIMESTAMP(3)		End snapshot time for the baseline
SHUTDOWN	VARCHAR2(3)		Whether or not there is a database startup or shutdown in this interval (YES, NO, or NULL).
ERROR_COUNT	NUMBER		Number of errors in the snapshots in the baseline snapshot range
PCT_TOTAL_TIME	NUMBER		Amount of time captured in snapshots, divided by the total possible time for this baseline
LAST_TIME_COMPUTED	DATE		Last time that statistics were computed on the baseline
MOVING_WINDOW_SIZE	NUMBER		If BASELINE_TYPE is MOVING WINDOW, this field is the size of the moving window in number of days. If NULL, then the window size is the value of the AWR retention setting.
CREATION_TIME	DATE		Time the baseline was created
EXPIRATION	NUMBER		How long to keep the baseline, in number of days. A value of NULL indicates that the baseline will be kept forever.
TEMPLATE_NAME	VARCHAR2(64)		Name of the template that created this baseline, if any.
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.384 DBA_HIST_BASELINE_METADATA

DBA_HIST_BASELINE_METADATA displays metadata information for the baseline.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
BASELINE_ID	NUMBER	NOT NULL	Internal ID for the baseline

Column	Datatype	NULL	Description
BASELINE_NAME	VARCHAR2(64)		User-specified name for the baseline
BASELINE_TYPE	VARCHAR2(13)		The baseline type, as follows: STATIC - baselines that are created manually by the user MOVING WINDOW - baselines that have dynamic start and end snapshot IDs GENERATED - baselines that are automatically generated by the system, using a template
START_SNAP_ID	NUMBER		Start snapshot ID for the baseline
END_SNAP_ID	NUMBER		End snapshot ID for the baseline
MOVING_WINDOW_SIZE	NUMBER		If BASELINE_TYPE is MOVING WINDOW, this field is the size of the moving window in number of days. If NULL, then the window size is the value of the AWR retention setting.
CREATION_TIME	DATE		Time the baseline was created
EXPIRATION	NUMBER		How long to keep the baseline, in number of days. If the value is NULL, the baseline will be kept forever.
TEMPLATE_NAME	VARCHAR2(64)		Name of the template that created this baseline, if any
LAST_TIME_COMPUTED	DATE		Last time that statistics were computed on the baseline
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.385 DBA_HIST_BASELINE_TEMPLATE

DBA_HIST_BASELINE_TEMPLATE displays the templates used by the system for baseline generation.

The system uses this information to determine which baselines should be automatically created or removed.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
TEMPLATE_ID	NUMBER	NOT NULL	Internal ID for the template
TEMPLATE_NAME	VARCHAR2(128)	NOT NULL	Name of the template

Column	Datatype	NULL	Description
TEMPLATE_TYPE	VARCHAR2(9)	NOT NULL	Type of the template, as follows: SINGLE - one time period REPEATING - maintain a time period
BASELINE_NAME_PREFIX	VARCHAR2(128)	NOT NULL	Name to use for the baselines that are created: For a template type of SINGLE, the BASELINE_NAME_PREFIX is the name that will be used. For a template type of REPEATING, the BASELINE_NAME will be the prefix to the name.
START_TIME	DATE	NOT NULL	For a template type of SINGLE, this is the start time for future baselines For a template type of REPEATING, this is the effective start time that baselines should start being generated.
END_TIME	DATE	NOT NULL	For a template type of SINGLE, this is the end time for future baselines. For a template type of REPEATING, this is the effective end time that baselines should stop being generated.
DAY_OF_WEEK	VARCHAR2(9)		For a template type of REPEATING, this indicates the day of the week to create the baseline: SUNDAY, MONDAY, TUESDAY, WEDNESDAY, THURSDAY, FRIDAY, SATURDAY, ALL.
HOUR_IN_DAY	NUMBER		For a template type of REPEATING, a value from 0 - 23 to indicate the hour of the day to create the baseline for.
DURATION	NUMBER		For a template type of REPEATING, the length of time for the baseline to be created.
EXPIRATION	NUMBER		How long to keep the baseline, in number of days
REPEAT_INTERVAL	VARCHAR2(128)		String that represents the time repeating information in the format used by the DBMS_SCHEDULER package
LAST_GENERATED	DATE		Last time a baseline was generated for this template
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_SCHEDULER` package

5.386 DBA_HIST_BG_EVENT_SUMMARY

`DBA_HIST_BG_EVENT_SUMMARY` displays the historical summary background event activity.

This view contains snapshots from `V$SESSION_EVENT`.

Column	Datatype	NULL	Description
`SNAP_ID`	`NUMBER`	`NOT NULL`	Unique snapshot ID
`DBID`	`NUMBER`	`NOT NULL`	Database ID for the snapshot
`INSTANCE_NUMBER`	`NUMBER`	`NOT NULL`	Instance number for the snapshot
`EVENT_ID`	`NUMBER`	`NOT NULL`	Identifier of the wait event
`EVENT_NAME`	`VARCHAR2(64)`	`NOT NULL`	Name of the wait event
`WAIT_CLASS_ID`	`NUMBER`		Identifier of the class of the wait event
`WAIT_CLASS`	`VARCHAR2(64)`		Name of the class of the wait event
`TOTAL_WAITS`	`NUMBER`		Total number of waits for the event
`TOTAL_TIMEOUTS`	`NUMBER`		Total number of timeouts for the event
`TIME_WAITED_MICRO`	`NUMBER`		Total amount of time waited for the event (in microseconds)
`CON_DBID`	`NUMBER`		The database ID of the PDB for the sampled session
`CON_ID`	`NUMBER`		The ID of the container that `CON_DBID` identifies. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$SESSION_EVENT"

5.387 DBA_HIST_BUFFER_POOL_STAT

DBA_HIST_BUFFER_POOL_STAT displays historical statistics about all buffer pools available for the instance.

This view contains snapshots of V$BUFFER_POOL_STATISTICS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
ID	NUMBER	NOT NULL	Buffer pool identifier number
NAME	VARCHAR2(20)		Name of the buffer pool
BLOCK_SIZE	NUMBER		Block Size
SET_MSIZE	NUMBER		Buffer pool maximum set size
CNUM_REPL	NUMBER		Number of buffers on the replacement list
CNUM_WRITE	NUMBER		Number of buffers on the write list
CNUM_SET	NUMBER		Number of buffers in the set
BUF_GOT	NUMBER		Number of buffers gotten by the set
SUM_WRITE	NUMBER		Number of buffers written by the set
SUM_SCAN	NUMBER		Number of buffers scanned in the set
FREE_BUFFER_WAIT	NUMBER		Free buffer wait statistic
WRITE_COMPLETE_WAIT	NUMBER		Write complete wait statistic
BUFFER_BUSY_WAIT	NUMBER		Buffer busy wait statistic
FREE_BUFFER_INSPECTED	NUMBER		Free buffer inspected statistic
DIRTY_BUFFERS_INSPECTED	NUMBER		Dirty buffers inspected statistic
DB_BLOCK_CHANGE	NUMBER		Database blocks changed statistic
DB_BLOCK_GETS	NUMBER		Database blocks gotten statistic
CONSISTENT_GETS	NUMBER		Consistent gets statistic
PHYSICAL_READS	NUMBER		Physical reads statistic
PHYSICAL_WRITES	NUMBER		Physical writes statistic
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$BUFFER_POOL_STATISTICS"

5.388 DBA_HIST_BUFFERED_QUEUES

DBA_HIST_BUFFERED_QUEUES displays historical information about all buffered queues available for the instance.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
QUEUE_SCHEMA	VARCHAR2(128)	NOT NULL	Owner of the queue
QUEUE_NAME	VARCHAR2(128)	NOT NULL	Name of the queue
STARTUP_TIME	DATE	NOT NULL	Startup time of the instance
QUEUE_ID	NUMBER	NOT NULL	ID of the queue
NUM_MSGS	NUMBER		Total number of outstanding messages currently enqueued in the buffered queue for the subscriber (includes the count of the messages overflowed to disk)
SPILL_MSGS	NUMBER		Current number of overflow messages spilled to disk from the buffered queue
CNUM_MSGS	NUMBER		Cumulative total number of messages enqueued into the buffered queue since the buffered queue was created.
CSPILL_MSGS	NUMBER		Cumulative total number of overflow messages spilled to disk from the buffered queue since the buffered queue was created
EXPIRED_MSGS	NUMBER		Number of expired messages
OLDEST_MSGID	RAW(16)		Message ID of the oldest message
OLDEST_MSG_ENQTM	TIMESTAMP(3)		Enqueue time of the oldest message
QUEUE_STATE	VARCHAR2(25)		Indicates whether the queue is in recovery mode (QUEUE IS IN RECOVERY MODE) or not (NORMAL)
ELAPSED_ENQUEUE_TIME	NUMBER		Total time spent in enqueue (in hundredths of a second)
ELAPSED_DEQUEUE_TIME	NUMBER		Total time spent in dequeue (in hundredths of a second)
ELAPSED_TRANSFORMATION_TIME	NUMBER		Total time for evaluating transformations (in hundredths of a second)
ELAPSED_RULE_EVALUATION_TIME	NUMBER		Total time for rule evaluations (in hundredths of a second)
ENQUEUE_CPU_TIME	NUMBER		Total CPU time for enqueue (in hundredths of a second)

Column	Datatype	NULL	Description
DEQUEUE_CPU_TIME	NUMBER		Total CPU time for dequeue (in hundredths of a second)
LAST_ENQUEUE_TIME	TIMESTAMP(3)		Last message enqueue time
LAST_DEQUEUE_TIME	TIMESTAMP(3)		Last message dequeue time
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.389 DBA_HIST_BUFFERED_SUBSCRIBERS

DBA_HIST_BUFFERED_SUBSCRIBERS displays historical information about the subscribers for all buffered queues in the instance.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
QUEUE_SCHEMA	VARCHAR2(128)	NOT NULL	Owner of the queue
QUEUE_NAME	VARCHAR2(128)	NOT NULL	Name of the queue
SUBSCRIBER_ID	NUMBER	NOT NULL	Internal subscriber number (for identification)
SUBSCRIBER_NAME	VARCHAR2(128)		Name of the subscriber
SUBSCRIBER_ADDRESS	VARCHAR2(1024)		Address of the subscribing agent
SUBSCRIBER_TYPE	VARCHAR2(128)		Type of subscriber: • PROXY - Proxy subscriber • SUBSCRIBOR
STARTUP_TIME	DATE	NOT NULL	Startup time of the instance
LAST_BROWSED_SEQ	NUMBER		Sequence number of the most recently browsed message for the subscriber (comparable to the number of messages in the V$STREAMS_APPLY_READER view)
LAST_BROWSED_NUM	NUMBER		Internal Message number for the most recently browsed message for the subscriber
LAST_DEQUEUED_SEQ	NUMBER		Sequence number of the most recently dequeued message for the subscriber (comparable to the number of messages in the V$STREAMS_APPLY_COORDINATOR view)
LAST_DEQUEUED_NUM	NUMBER		Internal Message number for the most recently dequeued message for the subscriber

Column	Datatype	NULL	Description
CURRENT_ENQ_SEQ	NUMBER		Current sequence number of the most recently enqueued message for the subscriber
NUM_MSGS	NUMBER		Total number of outstanding messages currently enqueued in the buffered queue for the subscriber (includes the count of the messages overflowed to disk)
CNUM_MSGS	NUMBER		Cumulative total number of messages enqueued for the subscriber since the creation of the buffered queue
TOTAL_DEQUEUED_MSG	NUMBER		Total number of messages dequeued by the subscriber
TOTAL_SPILLED_MSG	NUMBER		Total number of spilled messages for the subscriber
EXPIRED_MSGS	NUMBER		Number of expired messages
MESSAGE_LAG	NUMBER		Message lag of the subscriber
ELAPSED_DEQUEUE_TIME	NUMBER		Total time spent in dequeue (in hundredths of a second)
DEQUEUE_CPU_TIME	NUMBER		Total CPU time for dequeue (in hundredths of a second)
LAST_DEQUEUE_TIME	TIMESTAMP(3)		Last message dequeue time
OLDEST_MSGID	RAW(16)		Message ID of the oldest message
OLDEST_MSG_ENQTM	TIMESTAMP(3)		Enqueue time of the oldest message
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.390 DBA_HIST_CAPTURE

DBA_HIST_CAPTURE displays historical statistics information about each capture process for Oracle GoldenGate, and XStream capture operations.

This view is intended for use with Automatic Workload Repository (AWR).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
CAPTURE_NAME	VARCHAR2(128)	NOT NULL	Name of the capture process

Column	Datatype	NULL	Description
STARTUP_TIME	DATE	NOT NULL	Time that the capture process was last started
LAG	NUMBER		Delay (in seconds) between the creation and capture of the most recently captured message
TOTAL_MESSAGES_CAPTURED	NUMBER		Total changes captured since the capture process was last started
TOTAL_MESSAGES_ENQUEUED	NUMBER		Total number of messages enqueued since the capture process was last started
ELAPSED_RULE_TIME	NUMBER		Elapsed time (in hundredths of a second) evaluating rules since the capture process was last started
ELAPSED_ENQUEUE_TIME	NUMBER		Elapsed time (in hundredths of a second) enqueuing messages since the capture process was last started
ELAPSED_REDO_WAIT_TIME	NUMBER		Elapsed time (in hundredths of a second) spent by the capture process in the WAITING FOR REDO state since the capture process was last started.
ELAPSED_PAUSE_TIME	NUMBER		Elapsed pause time (in hundredths of a second) spent by the capture process since the capture process was last restarted
CON_DBID	NUMBER		The database ID of the PDB
EXTRACT_NAME	VARCHAR2(128)		Name of the extract process, if applicable
BYTES_REDO_MINED	NUMBER		The total amount of redo data mined (in bytes) since the capture process last started
BYTES_SENT	NUMBER		Total number of bytes sent by the capture process to the extract process since the last time the extract process attached to the capture process
SESSION_MODULE	VARCHAR2(64)	NOT NULL	Session module. Valid values: • XStream • GoldenGate
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.391 DBA_HIST_CHANNEL_WAITS

DBA_HIST_CHANNEL_WAITS display the amount of messages broadcast on KSR and KSXR channels as well as the total time taken for the broadcast to complete.

KSR channels are local to an instance, that is, only processes within an instance subscribed to the channel can receive the message. KSXR channels allow messages to be broadcast across instances. The messages broadcast and the total time to broadcast are cumulative from the start of the instance. Channels with high overall average wait times could indicate

potential problems with a subscriber on that channel which can lead to poor scaled performance.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
CHANNEL	VARCHAR2(64)		The name of the KSR or KSXR channel
MESSAGES_PUBLISHED	NUMBER		The cumulative count of messages published on the channel (from instance startup)
WAIT_COUNT	NUMBER		The total number of times a publisher has waited for a broadcast to complete. This metric is only pertinent for asynchronous broadcasts where the broadcast can be dispatched and publisher can wait for completion at a later point of time. A high wait count along with increased wait time can indicate a potential performance bottleneck.
WAIT_TIME_USEC	NUMBER		The cumulative amount of time in microseconds that publishers have waited for message broadcast to complete. Average time for broadcast on a channel can be computed by dividing WAIT_TIME_USEC by WAIT_COUNT. A high average time can indicate a potential performance bottleneck.
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.392 DBA_HIST_CLUSTER_INTERCON

DBA_HIST_CLUSTER_INTERCON displays information about the devices used by the instance to access the interconnect (that is, communicate with other instances).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
NAME	VARCHAR2(256)	NOT NULL	Operating system name of the device
IP_ADDRESS	VARCHAR2(64)	NOT NULL	IP address of the device

Column	Datatype	NULL	Description
IS_PUBLIC	VARCHAR2(3)		Indicates whether the device is a public interface (YES) or a private interface (NO) Public interfaces can be listened to by outside applications, which may be a security problem. Oracle recommends using private interfaces for interconnect.
SOURCE	VARCHAR2(31)		Describes the type of device
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.393 DBA_HIST_COLORED_SQL

DBA_HIST_COLORED_SQL displays the SQL IDs that have been marked for AWR SQL capture.

If a SQL statement is colored using the DBMS_WORKLOAD_REPOSITORY.ADD_COLORED_SQL procedure, then AWR will always capture the SQL statistics for the colored SQL ID. A SQL statement can be removed from coloring using the DBMS_WORKLOAD_REPOSITORY.REMOVE_COLORED_SQL procedure.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
SQL_ID	VARCHAR2(13)	NOT NULL	SQL ID of colored SQL statement
CREATE_TIME	DATE	NOT NULL	Time the SQL ID was colored
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database PL/SQL Packages and Types Reference for more information about the DBMS_WORKLOAD_REPOSITORY package.

5.394 DBA_HIST_COMP_IOSTAT

DBA_HIST_COMP_IOSTAT displays information about I/O statistics aggregated on the component level.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
COMPONENT	VARCHAR2(64)	NOT NULL	Component name
FILE_TYPE	VARCHAR2(64)	NOT NULL	File type
IO_TYPE	CHAR(5)	NOT NULL	The type of I/O performed
OPERATION	CHAR(5)	NOT NULL	Operation name
BYTES	NUMBER	NOT NULL	Number of bytes
IO_COUNT	NUMBER	NOT NULL	Number of I/Os that were performed
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.395 DBA_HIST_CON_SYS_TIME_MODEL

DBA_HIST_CON_SYS_TIME_MODEL displays historical system time model statistics, including OLAP timed stastistics. This view contains snapshots of V$SYS_TIME_MODEL.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
STAT_ID	NUMBER		Statistic ID
STAT_NAME	VARCHAR2(64)		Statistic name
VALUE	NUMBER		Statistic value
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • When queried from a non-CDB, the statistics for that instance are returned, and the CON_ID value is 0. • When queried from the root of a CDB, the statistics in every container are returned, and the CON_ID value indicates the container to which the statistics belong. • When queried from a PDB, statistics from that PDB are returned, and the CON_ID value is the container ID for that PDB.

See Also:

- "V$CON_SYSMETRIC"
- "DBA_HIST_SYS_TIME_MODEL"
- "V$SYS_TIME_MODEL"

5.396 DBA_HIST_CON_SYSMETRIC_HIST

DBA_HIST_CON_SYSMETRIC_HIST externalizes all available history of the system metric values for the entire set of data kept in the database. This view contains snapshots of V$CON_SYSMETRIC_HISTORY.

Note:

This view is not populated and is reserved for future use.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
BEGIN_TIME	DATE		Begin time of the interval
END_TIME	DATE		End time of the interval
INTSIZE	NUMBER		Interval size (in hundredths of a second)
GROUP_ID	NUMBER		Group ID
METRIC_ID	NUMBER		Metric ID
METRIC_NAME	VARCHAR2(64)		Metric name
VALUE	NUMBER		Metric value
METRIC_UNIT	VARCHAR2(64)		Unit of measurement

Column	Datatype	NULL	Description
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • When queried from a non-CDB, the statistics for that instance are returned, and the CON_ID value is 0. • When queried from the root of a CDB, the statistics in every container are returned, and the CON_ID value indicates the container to which the statistics belong. • When queried from a PDB, statistics from that PDB are returned, and the CON_ID value is the container ID for that PDB.

See Also:

- "V$CON_SYSMETRIC_HISTORY"
- "DBA_HIST_SYSMETRIC_HISTORY"

5.397 DBA_HIST_CON_SYSMETRIC_SUMM

DBA_HIST_CON_SYSMETRIC_SUMM displays a history of statistical summary of all metric values in the system metrics long duration (60–second) group. This view contains snapshots of V$CON_SYSMETRIC_SUMMARY.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
BEGIN_TIME	DATE		Begin time of the interval
END_TIME	DATE		End time of the interval
INTSIZE	NUMBER		Interval size (in hundredths of a second)
GROUP_ID	NUMBER		Group ID
METRIC_ID	NUMBER		Metric ID
METRIC_NAME	VARCHAR2(64)		Metric name
METRIC_UNIT	VARCHAR2(64)		Unit of measurement
NUM_INTERVAL	NUMBER		Number of intervals observed
MINVAL	NUMBER		Minimum value observed
MAXVAL	NUMBER		Maximum value observed
AVERAGE	NUMBER		Average over the period
STANDARD_DEVIATION	NUMBER		One standard deviation

Column	Datatype	NULL	Description
SUM_SQUARES	NUMBER		Sum of the squared deviations from the mean
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • When queried from a non-CDB, the statistics for that instance are returned, and the CON_ID value is 0. • When queried from the root of a CDB, the statistics in every container are returned, and the CON_ID value indicates the container to which the statistics belong. • When queried from a PDB, statistics from that PDB are returned, and the CON_ID value is the container ID for that PDB.

Note:

- "V$CON_SYSMETRIC_SUMMARY"
- "DBA_HIST_SYSMETRIC_SUMMARY"

5.398 DBA_HIST_CON_SYSSTAT

DBA_HIST_CON_SYSSTAT displays historical system statistics information, including OLAP kernel statistics. This view contains snapshots of V$CON_SYSSTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
STAT_ID	NUMBER	NOT NULL	Statistic identifier
STAT_NAME	VARCHAR2(64)	NOT NULL	Statistic name
VALUE	NUMBER		Statistic value
CON_DBID	NUMBER	NOT NULL	The database ID for the PDB of the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER	NOT NULL	The ID of the container that CON_DBID identifies. Possible values include: • When queried from a non-CDB, the statistics for that instance are returned, and the CON_ID value is 0. • When queried from the root of a CDB, the statistics in every container are returned, and the CON_ID value indicates the container to which the statistics belong. • When queried from a PDB, statistics from that PDB are returned, and the CON_ID value is the container ID for that PDB.

See Also:

- "V$CON_SYSSTAT"
- "DBA_HIST_SYSSTAT"

5.399 DBA_HIST_CON_SYSTEM_EVENT

DBA_HIST_CON_SYSTEM_EVENT displays historical information on total waits for an event in a container. This view contains snapshots of V$CON_SYSTEM_EVENT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
EVENT_ID	NUMBER	NOT NULL	Identifier of the wait event
EVENT_NAME	VARCHAR2(64)	NOT NULL	Name of the wait event
WAIT_CLASS_ID	NUMBER		Identifier of the Class of the Wait Event
WAIT_CLASS	VARCHAR2(64)		Name of the Class of the Wait Event
TOTAL_WAITS	NUMBER		Total number of waits for the event
TOTAL_TIMEOUTS	NUMBER		Total number of timeouts for the event
TIME_WAITED_MICRO	NUMBER		Total amount of time waited for the event (in microseconds)
TOTAL_WAITS_FG	NUMBER		Total number of waits for the event, from foreground sessions
TOTAL_TIMEOUTS_FG	NUMBER		Total number of timeouts for the event, from foreground sessions
TIME_WAITED_MICRO_FG	NUMBER		Amount of time waited for the event (in microseconds), from foreground sessions
CON_DBID	NUMBER	NOT NULL	The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$CON_SYSTEM_EVENT"

5.400 DBA_HIST_CR_BLOCK_SERVER

DBA_HIST_CR_BLOCK_SERVER displays historical statistics on the Global Cache Service processes (LMS) used in cache fusion.

This view contains snapshots of V$CR_BLOCK_SERVER.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
CR_REQUESTS	NUMBER		Number of CR blocks served due to remote CR block requests
CURRENT_REQUESTS	NUMBER		Number of current blocks served due to remote CR block requests CR_REQUESTS + CURRENT_REQUESTS = global cache CR blocks served (from V$SYSSTAT).
DATA_REQUESTS	NUMBER		Number of current or CR requests for data blocks
UNDO_REQUESTS	NUMBER		Number of CR requests for undo blocks
TX_REQUESTS	NUMBER		Number of CR requests for undo segment header blocks DATA_REQUESTS + UNDO_REQUESTS + TX_REQUESTS = total number of requests handled by the LMS processes
CURRENT_RESULTS	NUMBER		Number of requests for which no changes were rolled out of the block returned to the requesting instance
PRIVATE_RESULTS	NUMBER		Number of requests for which changes were rolled out of the block returned to the requesting instance, and only the requesting transaction can use the resulting CR block

Column	Datatype	NULL	Description
ZERO_RESULTS	NUMBER		Number of requests for which changes were rolled out of the block returned to the requesting instance. Only zero-XID transactions can use the block.
DISK_READ_RESULTS	NUMBER		Number of requests for which the requesting instance had to read the requested block from disk
FAIL_RESULTS	NUMBER		Number of requests that failed; the requesting transaction must reissue the request
FAIRNESS_DOWN_CONVERTS	NUMBER		Number of times an instance receiving a request has down-converted an X lock on a block because it was not modifying the block
FLUSHES	NUMBER		Number of times the log has been flushed by an LMS process
FLUSHES	NUMBER		Number of times the log has been flushed by an LMS process
BUILDS	NUMBER		Number of requests for which the server had to fabricate a CR block
LIGHT_WORKS	NUMBER		Number of times the light-work rule was evoked. This rule prevents the LMS processes from going to disk while responding to CR requests for data, undo, or undo segment header blocks. This rule can prevent the LMS process from completing its response to the CR request.
ERRORS	NUMBER		Number of times an error was signalled by an LMS process
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$CR_BLOCK_SERVER"

5.401 DBA_HIST_CURRENT_BLOCK_SERVER

DBA_HIST_CURRENT_BLOCK_SERVER displays historical statistics on the Global Cache Service processes (LMS) used in cache fusion.

This view contains snapshots of V$CURRENT_BLOCK_SERVER.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
PIN0	NUMBER		Pins taking less than 100 microseconds
PIN1	NUMBER		Pins taking 100 microseconds to 1 millisecond
PIN10	NUMBER		Pins taking 1 to 10 milliseconds
PIN100	NUMBER		Pins taking 10 to 100 milliseconds
PIN1000	NUMBER		Pins taking 100 to 1000 milliseconds
PIN10000	NUMBER		Pins taking 1000 to 10000 milliseconds
PINOVER	NUMBER		Pins taking more than 10000 milliseconds
FLUSH0	NUMBER		Flushes taking less than 100 microseconds
FLUSH1	NUMBER		Flushes taking 100 microseconds to 1 millisecond
FLUSH10	NUMBER		Flushes taking 1 to 10 milliseconds
FLUSH100	NUMBER		Flushes taking 10 to 100 milliseconds
FLUSH1000	NUMBER		Flushes taking 100 to 1000 milliseconds
FLUSH10000	NUMBER		Flushes taking 1000 to 10000 milliseconds
FLUSHOVER	NUMBER		Flushes taking more than 10000 milliseconds
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$CURRENT_BLOCK_SERVER"

5.402 DBA_HIST_DATABASE_INSTANCE

DBA_HIST_DATABASE_INSTANCE displays the databases and instances in the Workload Repository.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number

Column	Datatype	NULL	Description
STARTUP_TIME	TIMESTAMP(3)	NOT NULL	Startup time of the instance
PARALLEL	VARCHAR2(3)	NOT NULL	Indicates whether the instance is running in an Oracle Real Application Clusters (Oracle RAC) environment (YES) or not (NO)
VERSION	VARCHAR2(17)	NOT NULL	Database version
DB_NAME	VARCHAR2(9)		Name of the database
INSTANCE_NAME	VARCHAR2(16)		Name of the instance
HOST_NAME	VARCHAR2(64)		Name of the host
LAST_ASH_SAMPLE_ID	NUMBER	NOT NULL	Last sample ID for the active session history
PLATFORM_NAME	VARCHAR2(101)		Platform on which the instance is running
CDB	VARCHAR2(3)		Possible values are: • YES if the database is a CDB • NO if the database is not a CDB
EDITION	VARCHAR2(7)		The edition of the database. Possible values include: • CORE EE: CORE Enterprise Edition • EE: Enterprise Edition • PO: Personal Edition • FREE: Free
DB_UNIQUE_NAME	VARCHAR2(30)		Unique database name
DATABASE_ROLE	VARCHAR2(16)		Current role of the database: • SNAPSHOT STANDBY • LOGICAL STANDBY • PHYSICAL STANDBY • PRIMARY • FAR SYNC
CDB_ROOT_DBID	NUMBER		The database ID of the CDB root for the sampled session
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
STARTUP_TIME_TZ	TIMESTAMP(3) WITH TIME ZONE		Startup time of the instance

See Also:

"DB_UNIQUE_NAME"

5.403 DBA_HIST_DATAFILE

DBA_HIST_DATAFILE displays a history of the data file information from the control file.

This view contains snapshots of V$DATAFILE.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
FILE#	NUMBER	NOT NULL	File identification number
CREATION_CHANGE#	NUMBER	NOT NULL	Change number at which the data file was created
FILENAME	VARCHAR2(513)	NOT NULL	Name of the data file
TS#	NUMBER	NOT NULL	Tablespace number
TSNAME	VARCHAR2(30)		Name of the tablespace
BLOCK_SIZE	NUMBER		Block size of the data file
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$DATAFILE"

5.404 DBA_HIST_DB_CACHE_ADVICE

DBA_HIST_DB_CACHE_ADVICE displays historical predictions of the number of physical reads for the cache size corresponding to each row.

This view contains snapshots of V$DB_CACHE_ADVICE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
BPID	NUMBER	NOT NULL	Buffer Pool identifier (ranges from 1 to 8)
BUFFERS_FOR_ESTIMATE	NUMBER	NOT NULL	Cache size for prediction (in terms of buffers)
NAME	VARCHAR2(20)		Buffer pool name

Column	Datatype	NULL	Description
BLOCK_SIZE	NUMBER		Block size in bytes for buffers in the pool (the standard block size, the power of 2 nonstandard block sizes, 2048, 4096, 8192, 16384, or 32768)
ADVICE_STATUS	VARCHAR2(3)		Status of the advisory: • ON - Currently running • OFF - Disabled (the estimates are historical and calculated when last enabled)
SIZE_FOR_ESTIMATE	NUMBER		Cache size for prediction (in megabytes)
SIZE_FACTOR	NUMBER		Size factor with respect to the current cache size
PHYSICAL_READS	NUMBER		Physical reads for the cache size
BASE_PHYSICAL_READS	NUMBER		Base physical reads for the cache size
ACTUAL_PHYSICAL_READS	NUMBER		Actual physical reads for the cache size
ESTD_PHYSICAL_READ_TIME	NUMBER		Estimated physical read time for the cache size
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$DB_CACHE_ADVICE"

5.405 DBA_HIST_DISPATCHER

DBA_HIST_DISPATCHER displays historical information for each dispatcher process present at the time of the snapshot.

This view contains snapshots of information from V$DISPATCHER and V$QUEUE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
NAME	VARCHAR2(4)	NOT NULL	Name of the dispatcher process
SERIAL#	NUMBER		Serial number of the dispatcher process

Column	Datatype	NULL	Description
IDLE	NUMBER		Total idle time for the dispatcher (in hundredths of a second)
BUSY	NUMBER		Total busy time for the dispatcher (in hundredths of a second)
WAIT	NUMBER		Total time that all items in the dispatcher queue have waited (in hundredths of a second). Divide by TOTALQ for average wait per item.
TOTALQ	NUMBER		Total number of items that have ever been in the dispatcher queue
SAMPLED_TOTAL_CONN	NUMBER		Cumulative sum of total number of connections to the dispatcher over all samples. To determine the average number of connections to the dispatcher between two snapshots, divide the difference in SAMPLED_TOTAL_CONN by the difference in NUM_SAMPLES (obtained from DBA_HIST_SHARED_SERVER_SUMMARY).
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$DISPATCHER"
- "V$QUEUE"

5.406 DBA_HIST_DLM_MISC

DBA_HIST_DLM_MISC displays miscellaneous Oracle Real Application Clusters (Oracle RAC) statistics.

This view contains snapshots of V$DLM_MISC.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER		Database ID for the snapshot
INSTANCE_NUMBER	NUMBER		Instance number for the snapshot
STATISTIC#	NUMBER		Statistic number

Column	Datatype	NULL	Description
NAME	VARCHAR2(38)		Statistic name
VALUE	NUMBER		Statistic value
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.407 DBA_HIST_DYN_REMASTER_STATS

DBA_HIST_DYN_REMASTER_STATS displays historical statistical information about the dynamic remastering process.

All times are given in hundredths of a second, except where otherwise noted, and total values reflect what has been collected since instance startup. This view contains snapshots of V$DYNAMIC_REMASTER_STATS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
REMASTER_TYPE	VARCHAR2(11)	NOT NULL	Remaster process type. Possible values: • AFFINITY: This value is used for the row containing statistics that pertain to dynamic remastering activity on object affinity. • READ-MOSTLY: This value is used for the row containing statistics that pertain to dynamic remastering activity on read-mostly objects.
PERSISTENT_OBJECTS	NUMBER		Current number of objects that are marked persistent read-mostly in the cluster
REMASTER_OPS	NUMBER		Total number of dynamic remastering operations
REMASTER_TIME	NUMBER		Total dynamic remastering time
REMASTERED_OBJECTS	NUMBER		Total number of objects dynamically remastered due to affinity
QUIESCE_TIME	NUMBER		Total quiesce step time
FREEZE_TIME	NUMBER		Total freeze step time
CLEANUP_TIME	NUMBER		Total cleanup step time
REPLAY_TIME	NUMBER		Total replay step time
FIXWRITE_TIME	NUMBER		Total fixwrite step time
SYNC_TIME	NUMBER		Total synchronization step time

Column	Datatype	NULL	Description
REMASTERED_BUFFERS	NUMBER		Total sum of the sizes (number of buffers) of all dynamically remastered objects The size of a buffer is specified by the DB_BLOCK_SIZE initialization parameter. The default is 8192 bytes.
AVG_BUFFER_AGE	NUMBER		Average time (in seconds) that buffers spent in the request queue, waiting to be processed
FILTERED_OBJECTS	NUMBER		Number of requests that were filtered (not processed)
FILTERED_BUFFERS	NUMBER		Total sum of the sizes (number of buffers) of all requests that were filtered The size of a buffer is specified by the DB_BLOCK_SIZE initialization parameter. The default is 8192 bytes.
RESOURCES_CLEANED	NUMBER		Total number of resources cleaned in the cleanup steps
REPLAYED_LOCKS_SENT	NUMBER		Total number of locks replayed to other instances in the replay steps
REPLAYED_LOCKS_RECEIVED	NUMBER		Total number of locks received from other instances in the replay steps
CURRENT_OBJECTS	NUMBER		Current number of objects remastered on this instance due to affinity or the current number of objects that are marked read-mostly in the cluster
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$DYNAMIC_REMASTER_STATS"

5.408 DBA_HIST_ENQUEUE_STAT

DBA_HIST_ENQUEUE_STAT displays historical statistics on the number of enqueue (lock) requests for each type of lock.

This view contains snapshots of V$ENQUEUE_STATISTICS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
EQ_TYPE	VARCHAR2(2)	NOT NULL	Type of enqueue requested
REQ_REASON	VARCHAR2(64)	NOT NULL	Reason for the enqueue request
TOTAL_REQ#	NUMBER		Total number of enqueue requests or enqueue conversions for this type of enqueue
TOTAL_WAIT#	NUMBER		Total number of times an enqueue request or conversion resulted in a wait
SUCC_REQ#	NUMBER		Number of times an enqueue request or conversion was granted
FAILED_REQ#	NUMBER		Number of times an enqueue request or conversion failed
CUM_WAIT_TIME	NUMBER		Total amount of time (in milliseconds) spent waiting for the enqueue or enqueue conversion
EVENT#	NUMBER		Event number
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$ENQUEUE_STATISTICS"

5.409 DBA_HIST_EVENT_HISTOGRAM

DBA_HIST_EVENT_HISTOGRAM displays event histogram historical statistics information.

This view contains snapshots of V$EVENT_HISTOGRAM.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
EVENT_ID	NUMBER	NOT NULL	Identifier of the wait event

Column	Datatype	NULL	Description
EVENT_NAME	VARCHAR2(64)	NOT NULL	Name of the wait event
WAIT_CLASS_ID	NUMBER		Identifier of the class of the wait event
WAIT_CLASS	VARCHAR2(64)		Name of the class of the wait event
WAIT_TIME_MILLI	NUMBER	NOT NULL	Wait time (in milliseconds)
WAIT_COUNT	NUMBER		Wait count
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$EVENT_HISTOGRAM"

5.410 DBA_HIST_EVENT_NAME

DBA_HIST_EVENT_NAME displays information about wait events.

This view contains a snapshot of V$EVENT_NAME.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
EVENT_ID	NUMBER	NOT NULL	Identifier of the wait event
EVENT_NAME	VARCHAR2(64)	NOT NULL	Name of the wait event
PARAMETER1	VARCHAR2(64)		Description of the first parameter for the wait event
PARAMETER2	VARCHAR2(64)		Description of the second parameter for the wait event
PARAMETER3	VARCHAR2(64)		Description of the third parameter for the wait event
WAIT_CLASS_ID	NUMBER		Identifier of the class of the wait event
WAIT_CLASS	VARCHAR2(64)		Name of the class of the wait event
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$EVENT_NAME"

5.411 DBA_HIST_FILEMETRIC_HISTORY

DBA_HIST_FILEMETRIC_HISTORY displays the history of file metrics collected in the Workload Repository.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
FILEID	NUMBER	NOT NULL	File number
CREATIONTIME	NUMBER	NOT NULL	File creation time
BEGIN_TIME	DATE	NOT NULL	Begin time of the interval
END_TIME	DATE	NOT NULL	End time of the interval
INTSIZE	NUMBER	NOT NULL	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	NOT NULL	ID of the group to which the file belongs
AVGREADTIME	NUMBER	NOT NULL	Average file read time
AVGWRITETIME	NUMBER	NOT NULL	Average file write time
PHYSICALREAD	NUMBER	NOT NULL	Number of physical reads
PHYSICALWRITE	NUMBER	NOT NULL	Number of physical writes
PHYBLKREAD	NUMBER	NOT NULL	Number of physical block reads
PHYBLKWRITE	NUMBER	NOT NULL	Number of physical block writes
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.412 DBA_HIST_FILESTATXS

DBA_HIST_FILESTATXS displays information about file read/write statistics.

This view contains snapshots of V$FILESTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
FILE#	NUMBER	NOT NULL	File identification number
CREATION_CHANGE#	NUMBER	NOT NULL	Change number at which the data file was created
FILENAME	VARCHAR2(513)	NOT NULL	Name of the data file
TS#	NUMBER	NOT NULL	Tablespace number
TSNAME	VARCHAR2(30)		Name of the tablespace
BLOCK_SIZE	NUMBER		Block size of the data file
PHYRDS	NUMBER		Number of physical reads done
PHYWRTS	NUMBER		Number of times DBWR is required to write
SINGLEBLKRDS	NUMBER		Number of single block reads
READTIM	NUMBER		Time (in hundredths of a second) spent doing reads if the TIMED_STATISTICS parameter is true; 0 if TIMED_STATISTICS is false
WRITETIM	NUMBER		Time (in hundredths of a second) spent doing writes if the TIMED_STATISTICS parameter is true; 0 if TIMED_STATISTICS is false
SINGLEBLKRDTIM	NUMBER		Cumulative single block read time (in hundredths of a second)
PHYBLKRD	NUMBER		Number of physical blocks read
PHYBLKWRT	NUMBER		Number of blocks written to disk, which may be the same as PHYWRTS if all writes are single blocks
WAIT_COUNT	NUMBER		Shows the number of waits at the file level for contended buffers. This value includes the individual wait events that are included in the buffer busy waits wait event. **See Also:** "buffer busy waits"

Column	Datatype	NULL	Description
TIME	NUMBER		Time spent waiting for the wait events in the WAIT_COUNT column
OPTIMIZED_PHYBLKRD	NUMBER		Number of physical reads from Database Smart Flash Cache blocks
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$FILESTAT"

5.413 DBA_HIST_IC_CLIENT_STATS

DBA_HIST_IC_CLIENT_STATS displays information about the usage of an interconnect device by the instance.

The information is divided into several areas of the Oracle Database, each identified by the NAME value.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
NAME	VARCHAR2(9)	NOT NULL	Identifies the area of the Oracle Database: • ipq - Parallel query communications • dlm - Database lock management • cache - Global cache communications All other values are internal to Oracle and are not expected to have high usage.
BYTES_SENT	NUMBER		Number of bytes sent by the instance since instance startup for the software area identified by NAME. This information is aggregated across all devices used by the instance.
BYTES_RECEIVED	NUMBER		Number of bytes received by the instance since instance startup for the software area identified by NAME. This information is aggregated across all devices used by the instance.

Column	Datatype	NULL	Description
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.414 DBA_HIST_IC_DEVICE_STATS

DBA_HIST_IC_DEVICE_STATS displays operating system information about the usage of interconnect devices by the machine.

This usage contains Oracle usage but is not limited to it. The quality of the information depends on the operating system.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
IF_NAME	VARCHAR2(256)	NOT NULL	Name of the device (same as NAME in DBA_HIST_CLUSTER_INTERCON)
IP_ADDR	VARCHAR2(64)	NOT NULL	IP address of the device (same as IP_ADDRESS in DBA_HIST_CLUSTER_INTERCON)
NET_MASK	VARCHAR2(16)		Network mask
FLAGS	VARCHAR2(32)		Flags
MTU	NUMBER		Maximum transmission unit
BYTES_RECEIVED	NUMBER		Number of bytes received since operating system start time
PACKETS_RECEIVED	NUMBER		Number of packets received since operating system start time
RECEIVE_ERRORS	NUMBER		Number of receive errors since operating system start time
RECEIVE_DROPPED	NUMBER		Number of receive messages that were dropped
RECEIVE_BUF_OR	NUMBER		Number of receive buffer overruns experienced
RECEIVE_FRAME_ERR	NUMBER		Number of receive errors due to frame error
BYTES_SENT	NUMBER		Number of bytes sent since operating system start time
PACKETS_SENT	NUMBER		Number of packets sent since operating system start time
SEND_ERRORS	NUMBER		Number of send errors since operating system start time

Column	Datatype	NULL	Description
SENDS_DROPPED	NUMBER		Number of send messages that were dropped
SEND_BUF_OR	NUMBER		Number of send buffer overruns experienced
SEND_CARRIER_LOST	NUMBER		Number of send errors due to carrier lost
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.415 DBA_HIST_IM_SEG_STAT

DBA_HIST_IM_SEG_STAT displays information about historical in-memory segment statistics.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
TS#	NUMBER	NOT NULL	Tablespace number
OBJ#	NUMBER	NOT NULL	Dictionary object number
DATAOBJ#	NUMBER	NOT NULL	Data object number
MEMBYTES	NUMBER		Size of in-memory version of the segment in bytes
SCANS	NUMBER		Count of segment statistics
SCANS_DELTA	NUMBER		Delta values for in-memory scans
DB_BLOCK_CHANGES	NUMBER		The total number of changes that were part of an update or delete operation that were made to segment blocks
DB_BLOCK_CHANGES_DELTA	NUMBER		Delta value for database block changes
POPULATE_CUS	NUMBER		Count of compression units (CUs) populated per segment
POPULATE_CUS_DELTA	NUMBER		Delta value for compression unit (CU) populate operations
REPOPULATE_CUS	NUMBER		Count of CUs repopulated per segment
REPOPULATE_CUS_DELTA	NUMBER		Delta value for compression unit (CU) repopulate operations
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.416 DBA_HIST_IM_SEG_STAT_OBJ

DBA_HIST_IM_SEG_STAT_OBJ displays information about object metadata for historical in-memory segments.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database id for the snapshot
TS#	NUMBER	NOT NULL	Tablespace number
OBJ#	NUMBER	NOT NULL	Dictionary object number
DATAOBJ#	NUMBER	NOT NULL	Data object number
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2(128)		Name of the object
SUBOBJECT_NAME	VARCHAR2(128)		Name of the subobject
OBJECT_TYPE	VARCHAR2(128)		Type of the object
TABLESPACE_NAME	VARCHAR2(128)		Tablespace name for the object
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.417 DBA_HIST_INST_CACHE_TRANSFER

DBA_HIST_INST_CACHE_TRANSFER displays the historical statistics on the cache blocks transferred among instances.

This view contains snapshots of V$INSTANCE_CACHE_TRANSFER.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
INSTANCE	NUMBER	NOT NULL	Instance from which the blocks are transferred
CLASS	VARCHAR2(18)	NOT NULL	Class of the cache block
CR_BLOCK	NUMBER		CR block transfers not affected by remote processing delays
CR_BUSY	NUMBER		Current block transfers affected by remote contention
CR_CONGESTED	NUMBER		CR block transfers affected by remote system load
CURRENT_BLOCK	NUMBER		Current block transfers not affected by remote processing delays
CURRENT_BUSY	NUMBER		Current block transfers affected by remote contention
CURRENT_CONGESTED	NUMBER		Current block transfers affected by remote system load
LOST	NUMBER		The number of blocks that were sent by a particular instance but that never arrived in this instance
CR_2HOP	NUMBER		The count of CR blocks which were received by this instance from a particular instance after a 2-way round-trip
CR_3HOP	NUMBER		The count of CR blocks which were received by this instance from a particular instance after a 3-way round-trip
CR_RDMA	NUMBER		The count of CR Blocks which were directly read from a remote instance via RDMA
CURRENT_2HOP	NUMBER		The count of current blocks which were received by this instance from a particular instance after a 2-way round-trip
CURRENT_3HOP	NUMBER		The count of current blocks which were received by this instance from a particular instance after a 3-way round-trip
CURRENT_RDMA	NUMBER		The count of current blocks which were directly read from a remote instance via RDMA
CR_BLOCK_TIME	NUMBER		Total time waited for CR blocks from a particular instance (includes the other times)
CR_BUSY_TIME	NUMBER		The time waited for CR blocks which were received by this instance from a particular instance and which were delayed by a log flushed on the sending instance
CR_CONGESTED_TIME	NUMBER		The time waited for CR blocks which were received by this instance from a particular instance and which were delayed because LMS was busy
CURRENT_BLOCK_TIME	NUMBER		Total time waited for CR blocks from a particular instance (includes the other times)

Column	Datatype	NULL	Description
CURRENT_BUSY_TIME	NUMBER		The time waited for current blocks which were received by this instance from a particular instance and which were delayed by a log flushed on the sending instance
CURRENT_CONGESTED_TIME	NUMBER		The time waited for current blocks which were received by this instance from a particular instance and which were delayed because LMS was busy
LOST_TIME	NUMBER		The time waited for blocks that were sent by a particular instance but that never arrived in this instance
CR_2HOP_TIME	NUMBER		The time waited for CR blocks which were received by this instance from a particular instance after a 2-way round-trip
CR_3HOP_TIME	NUMBER		The time waited for CR blocks which were received by this instance from a particular instance after a 3-way round-trip
CR_RDMA_TIME	NUMBER		Total time waited to directly read CR blocks from a remote instance via RDMA (in centiseconds)
CURRENT_2HOP_TIME	NUMBER		The time waited for current blocks which were received by this instance from a particular instance after a 2-way round-trip
CURRENT_3HOP_TIME	NUMBER		The time waited for current blocks which were received by this instance from a particular instance after a 3-way round-trip
CURRENT_RDMA_TIME	NUMBER		Total time waited to directly read current blocks from a remote instance via RDMA (in centiseconds)
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$INSTANCE_CACHE_TRANSFER"

5.418 DBA_HIST_INSTANCE_RECOVERY

DBA_HIST_INSTANCE_RECOVERY displays the historical monitoring of the mechanisms available to the user to limit recovery I/O.

This view contains snapshots of V$INSTANCE_RECOVERY.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
RECOVERY_ESTIMATED_IOS	NUMBER		Number of dirty buffers in the buffer cache.
ACTUAL_REDO_BLKS	NUMBER		Current actual number of redo blocks required for recovery
TARGET_REDO_BLKS	NUMBER		Current target number of redo blocks that must be processed for recovery. This value is the minimum value of the following 3 columns, and identifies which of the 3 user-defined limits determines checkpointing.
LOG_FILE_SIZE_REDO_BLKS	NUMBER		Maximum number of redo blocks required to guarantee that a log switch does not occur before the checkpoint completes
LOG_CHKPT_TIMEOUT_REDO_BLKS	NUMBER		Number of redo blocks that need to be processed during recovery to satisfy the LOG_CHECKPOINT_TIMEOUT parameter. The value displayed is not meaningful unless LOG_CHECKPOINT_TIMEOUT has been set.
LOG_CHKPT_INTERVAL_REDO_BLKS	NUMBER		Number of redo blocks that need to be processed during recovery to satisfy the LOG_CHECKPOINT_INTERVAL parameter. The value displayed is not meaningful unless LOG_CHECKPOINT_INTERVAL has been set.
FAST_START_IO_TARGET_REDO_BLKS	NUMBER		This column is obsolete and maintained for backward compatibility. The value of this column is always null.
TARGET_MTTR	NUMBER		Effective MTTR (mean time to recover) target value in seconds. The TARGET_MTTR value is calculated based on the value of the FAST_START_MTTR_TARGET parameter (the TARGET_MTTR value is used internally), and is usually an approximation of the parameter's value. However, if the FAST_START_MTTR_TARGET parameter value is very small (for example, one second), or very large (for example, 3600 seconds), then the calculation will produce a target value dictated by system limitations. In such cases, the TARGET_MTTR value will be the shortest calculated time, or the longest calculated time that recovery is expected to take. If FAST_START_MTTR_TARGET is not specified, then the value of this field is the current estimated MTTR.

Column	Datatype	NULL	Description
ESTIMATED_MTTR	NUMBER		Current estimated mean time to recover (MTTR) based on the number of dirty buffers and log blocks (0 if FAST_START_MTTR_TARGET is not specified). This value tells you how long you can expect recovery to take based on the work the system is doing right now.
CKPT_BLOCK_WRITES	NUMBER		Number of blocks written by checkpoint writes
OPTIMAL_LOGFILE_SIZE	NUMBER		Redo log file size (in megabytes) that is considered optimal based on the current setting of FAST_START_MTTR_TARGET. It is recommended that all online redo logs be configured to be at least this value.
ESTD_CLUSTER_AVAILABLE_TIME	NUMBER		Estimated time (in seconds) that the cluster would become partially available should the instance fail. This column is only meaningful in an Oracle Real Application Clusters (Oracle RAC) environment. In a non-Oracle RAC environment, the value of this column is null.
WRITES_MTTR	NUMBER		Number of writes driven by the FAST_START_MTTR_TARGET parameter
WRITES_LOGFILE_SIZE	NUMBER		Number of writes driven by the smallest redo log file size
WRITES_LOG_CHECKPOINT_SETTINGS	NUMBER		Number of writes driven by the LOG_CHECKPOINT_INTERVAL parameter or the LOG_CHECKPOINT_TIMEOUT parameter
WRITES_OTHER_SETTINGS	NUMBER		Number of writes driven by other reasons (such as the deprecated FAST_START_IO_TARGET parameter)
WRITES_AUTOTUNE	NUMBER		Number of writes due to auto-tune checkpointing
WRITES_FULL_THREAD_CKPT	NUMBER		Number of writes due to full thread checkpoints
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$INSTANCE_RECOVERY"

5.419 DBA_HIST_INTERCONNECT_PINGS

DBA_HIST_INTERCONNECT_PINGS displays information about measured latency of interconnect messages (round-trip) from instance to instance.

In Oracle Database 11*g* and later releases, the PING process assesses the latencies associated with communications for each pair of instances.

Every few seconds, the process in one instance (INSTANCE_NUMBER value) sends two messages to each instance (TARGET_INSTANCE value). One message has a size of 500 bytes and the other has a size of 8 KB. The message is received by the PING process on the target instance and is immediately acknowledged. The time for the round-trip is measured and collected.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
TARGET_INSTANCE	NUMBER	NOT NULL	Target instance number
CNT_500B	NUMBER		Number of pings of size 500 bytes from INSTANCE_NUMBER to TARGET_INSTANCE since the startup of the source instance (INSTANCE_NUMBER)
WAIT_500B	NUMBER		Sum of round-trip times for messages of size 500 bytes from INSTANCE_NUMBER to TARGET_INSTANCE since the startup of the source instance (INSTANCE_NUMBER). Dividing by CNT_500B gives the average latency.
WAITSQ_500B	NUMBER		Sum of squares (divided by 1000) of round-trip times for messages of size 500 bytes from INSTANCE_NUMBER to TARGET_INSTANCE since the startup of the source instance (INSTANCE_NUMBER). When used with CNT_500B and WAIT_500B, the standard deviation of the latency can be calculated.
CNT_8K	NUMBER		Number of pings of size 8 KB from INSTANCE_NUMBER to TARGET_INSTANCE since the startup of the source instance (INSTANCE_NUMBER)
WAIT_8K	NUMBER		Sum of round-trip times for messages of size 8 KB from INSTANCE_NUMBER to TARGET_INSTANCE since the startup of the source instance (INSTANCE_NUMBER). Dividing by CNT_8K gives the average latency.
WAITSQ_8K	NUMBER		Sum of squares (divided by 1000) of round-trip times for messages of size 8 KB from INSTANCE_NUMBER to TARGET_INSTANCE since the startup of the source instance (INSTANCE_NUMBER). When used with CNT_8K and WAIT_8K, the standard deviation of the latency can be calculated.
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

5.420 DBA_HIST_IOSTAT_DETAIL

DBA_HIST_IOSTAT_DETAIL displays I/O statistics aggregated by combination of file type and function (component).

This view contains snapshots of V$IOSTAT_FILE and V$IOSTAT_FUNCTION.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
FUNCTION_ID	NUMBER	NOT NULL	Function ID
FUNCTION_NAME	VARCHAR2(30)	NOT NULL	Function name
FILETYPE_ID	NUMBER	NOT NULL	Type of file (for example, log file, data file, and so on)
FILETYPE_NAME	VARCHAR2(30)	NOT NULL	Name of the file, in the case of a data file or temp file. For all other files, a corresponding string to be displayed (for example, ARCHIVELOG).
SMALL_READ_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes written
SMALL_READ_REQS	NUMBER	NOT NULL	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	NOT NULL	Number of single block write requests
LARGE_READ_REQS	NUMBER	NOT NULL	Number of multiblock read requests
LARGE_WRITE_REQS	NUMBER	NOT NULL	Number of multiblock write requests
NUMBER_OF_WAITS	NUMBER	NOT NULL	Number of I/O waits by functionality
WAIT_TIME	NUMBER	NOT NULL	Total wait time (in milliseconds)
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$IOSTAT_FILE"
- "V$IOSTAT_FUNCTION"

5.421 DBA_HIST_IOSTAT_FILETYPE

DBA_HIST_IOSTAT_FILETYPE displays historical I/O statistics by file type.

This view contains snapshots of V$IOSTAT_FILE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
FILETYPE_ID	NUMBER	NOT NULL	Type of file (for example, log file, data file, and so on)
FILETYPE_NAME	VARCHAR2(30)	NOT NULL	Name of the file, in the case of a data file or temp file. For all other files, a corresponding string to be displayed (for example, ARCHIVELOG).
SMALL_READ_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes written
SMALL_READ_REQS	NUMBER	NOT NULL	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	NOT NULL	Number of single block write requests
SMALL_SYNC_READ_REQS	NUMBER	NOT NULL	Number of synchronous single block read requests
LARGE_READ_REQS	NUMBER	NOT NULL	Number of multiblock read requests
LARGE_WRITE_REQS	NUMBER	NOT NULL	Number of multiblock write requests
SMALL_READ_SERVICETIME	NUMBER	NOT NULL	Total service time (in milliseconds) for single block read requests

Column	Datatype	NULL	Description
SMALL_WRITE_SERVICETIME	NUMBER	NOT NULL	Total service time (in milliseconds) for single block write requests
SMALL_SYNC_READ_LATENCY	NUMBER	NOT NULL	Latency for single block synchronous reads (in milliseconds)
LARGE_READ_SERVICETIME	NUMBER	NOT NULL	Total service time (in milliseconds) for multiblock read requests
LARGE_WRITE_SERVICETIME	NUMBER	NOT NULL	Total service time (in milliseconds) for multiblock write requests
RETRIES_ON_ERROR	NUMBER	NOT NULL	Number of read retries on error
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$IOSTAT_FILE"

5.422 DBA_HIST_IOSTAT_FILETYPE_NAME

DBA_HIST_IOSTAT_FILETYPE_NAME displays historical I/O statistics for file type names.

This view contains snapshots of V$IOSTAT_FILE.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID for the snapshot
FILETYPE_ID	NUMBER	NOT NULL	Type of file (for example, log file, data file, and so on)
FILETYPE_NAME	VARCHAR2(30)	NOT NULL	Name of the file, in the case of a data file or temp file. For all other files, a corresponding string to be displayed (for example, ARCHIVELOG).
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$IOSTAT_FILE"

5.423 DBA_HIST_IOSTAT_FUNCTION

DBA_HIST_IOSTAT_FUNCTION displays historical I/O statistics by function.

This view contains snapshots of V$IOSTAT_FUNCTION.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
FUNCTION_ID	NUMBER	NOT NULL	Function ID
FUNCTION_NAME	VARCHAR2(128)	NOT NULL	Function name
SMALL_READ_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes written
SMALL_READ_REQS	NUMBER	NOT NULL	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	NOT NULL	Number of single block write requests
LARGE_READ_REQS	NUMBER	NOT NULL	Number of multiblock read requests
LARGE_WRITE_REQS	NUMBER	NOT NULL	Number of multiblock write requests
NUMBER_OF_WAITS	NUMBER	NOT NULL	Number of I/O waits by functionality
WAIT_TIME	NUMBER	NOT NULL	Total wait time (in milliseconds)
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$IOSTAT_FUNCTION"

5.424 DBA_HIST_IOSTAT_FUNCTION_NAME

DBA_HIST_IOSTAT_FUNCTION_NAME displays historical I/O statistics by function names.

This view contains snapshots of V$IOSTAT_FUNCTION.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID for the snapshot
FUNCTION_ID	NUMBER	NOT NULL	Function ID
FUNCTION_NAME	VARCHAR2(128)	NOT NULL	Function name
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$IOSTAT_FUNCTION"

5.425 DBA_HIST_JAVA_POOL_ADVICE

DBA_HIST_JAVA_POOL_ADVICE displays historical information about estimated parse time in the Java pool for different pool sizes.

This view contains snapshots of V$JAVA_POOL_ADVICE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
JAVA_POOL_SIZE_FOR_ESTIMATE	NUMBER	NOT NULL	Java pool size for the estimate (in megabytes)
JAVA_POOL_SIZE_FACTOR	NUMBER		Size factor with respect to the current Java pool size
ESTD_LC_SIZE	NUMBER		Estimated memory in use by the library cache (in megabytes)
ESTD_LC_MEMORY_OBJECTS	NUMBER		Estimated number of library cache memory objects in the Java pool of the specified size
ESTD_LC_TIME_SAVED	NUMBER		Estimated elapsed parse time saved (in seconds), owing to library cache memory objects being found in a Java pool of the specified size. This is the time that would have been spent in reloading the required objects in the Java pool had they been aged out due to insufficient amount of available free memory.
ESTD_LC_TIME_SAVED_FACTOR	NUMBER		Estimated parse time saved factor with respect to the current Java pool size
ESTD_LC_LOAD_TIME	NUMBER		Estimated elapsed time (in seconds) for parsing in a Java pool of the specified size.
ESTD_LC_LOAD_TIME_FACTOR	NUMBER		Estimated load time factor with respect to the current Java pool size
ESTD_LC_MEMORY_OBJECT_HITS	NUMBER		Estimated number of times a library cache memory object was found in a Java pool of the specified size
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$JAVA_POOL_ADVICE"

6

Static Data Dictionary Views: DBA_HIST_LATCH to DBA_STORED_SETTINGS

This chapter contains the static data dictionary views DBA_HIST_LATCH through DBA_STORED_SETTINGS.

6.1 DBA_HIST_LATCH

DBA_HIST_LATCH displays historical aggregate latch statistics for both parent and child latches, grouped by latch name.

This view contains snapshots of V$LATCH.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
LATCH_HASH	NUMBER	NOT NULL	Latch hash
LATCH_NAME	VARCHAR2(64)	NOT NULL	Latch name
LEVEL#	NUMBER		Latch level
GETS	NUMBER		Number of times the latch was requested in willing-to-wait mode
MISSES	NUMBER		Number of times the latch was requested in willing-to-wait mode and the requester had to wait
SLEEPS	NUMBER		Number of times a willing-to-wait latch request resulted in a session sleeping while waiting for the latch
IMMEDIATE_GETS	NUMBER		Number of times a latch was requested in no-wait mode
IMMEDIATE_MISSES	NUMBER		Number of times a no-wait latch request did not succeed (that is, missed)
SPIN_GETS	NUMBER		Number of willing-to-wait latch requests which missed the first try but succeeded while spinning
SLEEP[1 | 2 | 3 | 4]	NUMBER		These columns have been deprecated and are present only for compatibility with previous releases of Oracle. No data is accumulated for these columns; they will always have a value of zero.
WAIT_TIME	NUMBER		Elapsed time spent waiting for the latch (in microseconds)

Column	Datatype	NULL	Description
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$LATCH"

6.2 DBA_HIST_LATCH_CHILDREN

DBA_HIST_LATCH_CHILDREN displays historical statistics about child latches.

This view includes all columns of DBA_HIST_LATCH plus the CHILD# column. Note that child latches have the same parent if their LATCH# columns match each other. This view contains snapshots of V$LATCH_CHILDREN.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
LATCH_HASH	NUMBER	NOT NULL	Latch hash
LATCH_NAME	VARCHAR2(64)	NOT NULL	Latch name
CHILD#	NUMBER	NOT NULL	Child latch number (unique only to each parent latch)
GETS	NUMBER		Number of times the latch was requested in willing-to-wait mode
MISSES	NUMBER		Number of times the latch was requested in willing-to-wait mode and the requester had to wait
SLEEPS	NUMBER		Number of times a willing-to-wait latch request resulted in a session sleeping while waiting for the latch
IMMEDIATE_GETS	NUMBER		Number of times a latch was requested in no-wait mode
IMMEDIATE_MISSES	NUMBER		Number of times a no-wait latch request did not succeed (that is, missed)

Column	Datatype	NULL	Description
SPIN_GETS	NUMBER		Number of willing-to-wait latch requests which missed the first try but succeeded while spinning
SLEEP[1 | 2 | 3 | 4]	NUMBER		These columns have been deprecated and are present only for compatibility with previous releases of Oracle. No data is accumulated for these columns; they will always have a value of zero.
WAIT_TIME	NUMBER		Elapsed time spent waiting for the latch (in microseconds)
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "DBA_HIST_LATCH"
- "V$LATCH"

6.3 DBA_HIST_LATCH_MISSES_SUMMARY

DBA_HIST_LATCH_MISSES_SUMMARY displays historical summary statistics about missed attempts to acquire a latch.

This view contains snapshots of V$LATCH_MISSES.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
PARENT_NAME	VARCHAR2(50)	NOT NULL	Latch name of a parent latch
WHERE_IN_CODE	VARCHAR2(64)	NOT NULL	Location that attempted to acquire the latch
NWFAIL_COUNT	NUMBER		Number of times that no-wait acquisition of the latch failed
SLEEP_COUNT	NUMBER		Number of times that acquisition attempts caused sleeps
WTR_SLP_COUNT	NUMBER		Number of times a waiter slept

Column	Datatype	NULL	Description
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$LATCH_MISSES"

6.4 DBA_HIST_LATCH_NAME

DBA_HIST_LATCH_NAME displays information about decoded latch names for the latches shown in DBA_HIST_LATCH.

This view contains a snapshot of V$LATCHNAME.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
LATCH_HASH	NUMBER	NOT NULL	Latch hash
LATCH_NAME	VARCHAR2(64)	NOT NULL	Latch name
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> - "DBA_HIST_LATCH"
> - "V$LATCHNAME"

6.5 DBA_HIST_LATCH_PARENT

DBA_HIST_LATCH_PARENT displays historical statistics about parent latches.

This view contains snapshots of V$LATCH_PARENT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
LATCH_HASH	NUMBER	NOT NULL	Latch hash
LATCH_NAME	VARCHAR2(64)	NOT NULL	Latch name
LEVEL#	NUMBER	NOT NULL	Latch level
GETS	NUMBER		Number of times the latch was requested in willing-to-wait mode
MISSES	NUMBER		Number of times the latch was requested in willing-to-wait mode and the requester had to wait
SLEEPS	NUMBER		Number of times a willing-to-wait latch request resulted in a session sleeping while waiting for the latch
IMMEDIATE_GETS	NUMBER		Number of times a latch was requested in no-wait mode
IMMEDIATE_MISSES	NUMBER		Number of times a no-wait latch request did not succeed (that is, missed)
SPIN_GETS	NUMBER		Number of willing-to-wait latch requests which missed the first try but succeeded while spinning
SLEEP[1 | 2 | 3 | 4]	NUMBER		These columns have been deprecated and are present only for compatibility with previous releases of Oracle. No data is accumulated for these columns; they will always have a value of zero.
WAIT_TIME	NUMBER		Elapsed time spent waiting for the latch (in microseconds)
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$LATCH_PARENT"

6.6 DBA_HIST_LIBRARYCACHE

DBA_HIST_LIBRARYCACHE displays historical statistics about library cache performance and activity.

This view contains snapshots of V$LIBRARYCACHE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
NAMESPACE	VARCHAR2(15)	NOT NULL	Library cache namespace
GETS	NUMBER		Number of times a lock was requested for objects of the namespace
GETHITS	NUMBER		Number of times an object's handle was found in memory
PINS	NUMBER		Number of times a PIN was requested for objects of the namespace
PINHITS	NUMBER		Number of times all of the metadata pieces of the library object were found in memory
RELOADS	NUMBER		Any PIN of an object that is not the first PIN performed since the object handle was created, and which requires loading the object from disk
INVALIDATIONS	NUMBER		Total number of times objects in the namespace were marked invalid because a dependent object was modified
DLM_LOCK_REQUESTS	NUMBER		Number of GET requests lock instance locks
DLM_PIN_REQUESTS	NUMBER		Number of PIN requests lock instance locks
DLM_PIN_RELEASES	NUMBER		Number of release requests PIN instance locks
DLM_INVALIDATION_REQUESTS	NUMBER		Number of GET requests for invalidation instance locks
DLM_INVALIDATIONS	NUMBER		Number of invalidation pings received from other instances
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$LIBRARYCACHE"

6.7 DBA_HIST_LOG

DBA_HIST_LOG displays historical log file information from the control file. This view contains snapshots of V$LOG.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
GROUP#	NUMBER	NOT NULL	Log group number
THREAD#	NUMBER	NOT NULL	Log thread number
SEQUENCE#	NUMBER	NOT NULL	Log sequence number
BYTES	NUMBER		Size of the log (in bytes)
MEMBERS	NUMBER		Number of members in the log group
ARCHIVED	VARCHAR2(3)		Archive status (YES) or NO)

Column	Datatype	NULL	Description
STATUS	VARCHAR2(16)		Log status: • UNUSED - Online redo log has never been written to. This is the state of a redo log that was just added, or just after a RESETLOGS, when it is not the current redo log. • CURRENT - Current redo log. This implies that the redo log is active. The redo log could be open or closed. • ACTIVE - Log is active but is not the current log. It is needed for crash recovery. It may be in use for block recovery. It may or may not be archived. • CLEARING - Log is being re-created as an empty log after an ALTER DATABASE CLEAR LOGFILE statement. After the log is cleared, the status changes to UNUSED. • CLEARING_CURRENT - Current log is being cleared of a closed thread. The log can stay in this status if there is some failure in the switch such as an I/O error writing the new log header. • INACTIVE - Log is no longer needed for instance recovery. It may be in use for media recovery. It may or may not be archived. • INVALIDATED - Archived the current redo log without a log switch.
FIRST_CHANGE#	NUMBER		Lowest system change number (SCN) in the log
FIRST_TIME	DATE		Time of the first SCN in the log
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$LOG"

6.8 DBA_HIST_MEM_DYNAMIC_COMP

DBA_HIST_MEM_DYNAMIC_COMP displays historical memory component sizes.

This view contains snapshots of V$MEMORY_DYNAMIC_COMPONENTS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
COMPONENT	VARCHAR2(64)	NOT NULL	Component name
CURRENT_SIZE	NUMBER		Current size of the component
MIN_SIZE	NUMBER		Minimum size of the component since instance startup
MAX_SIZE	NUMBER		Maximum size of the component since instance startup
USER_SPECIFIED_SIZE	NUMBER		Value of the user parameter for the component
OPER_COUNT	NUMBER		Number of operations since instance startup
LAST_OPER_TYPE	VARCHAR2(13)		Last completed operation for the component: • STATIC • INITIALIZING • DISABLED • GROW • SHRINK • SHRINK_CANCEL
LAST_OPER_MODE	VARCHAR2(9)		Mode of the last completed operation: • MANUAL • DEFERRED • IMMEDIATE
LAST_OPER_TIME	DATE		Start time of the last completed operation
GRANULE_SIZE	NUMBER		Granularity of the GROW or SHRINK operation
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$MEMORY_DYNAMIC_COMPONENTS"

6.9 DBA_HIST_MEMORY_RESIZE_OPS

DBA_HIST_MEMORY_RESIZE_OPS displays memory resize operations history.

This view contains snapshots of V$MEMORY_RESIZE_OPS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
COMPONENT	VARCHAR2(64)	NOT NULL	Component name
OPER_TYPE	VARCHAR2(13)	NOT NULL	Operation type: • STATIC • INITIALIZING • DISABLED • GROW • SHRINK • SHRINK_CANCEL
START_TIME	DATE	NOT NULL	Start time of the operation
END_TIME	DATE	NOT NULL	End time of the operation
TARGET_SIZE	NUMBER	NOT NULL	Requested value of the parameter after the resize
OPER_MODE	VARCHAR2(9)		Operation mode: • MANUAL • DEFERRED • IMMEDIATE
PARAMETER	VARCHAR2(80)		Name of the parameter for the resize operation
INITIAL_SIZE	NUMBER		Parameter value at the start of the operation
FINAL_SIZE	NUMBER		Real value of the parameter after the resize
STATUS	VARCHAR2(9)		Completion status of the operation: • INACTIVE • PENDING • COMPLETE • CANCELLED • ERROR
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$MEMORY_RESIZE_OPS"

6.10 DBA_HIST_MEMORY_TARGET_ADVICE

DBA_HIST_MEMORY_TARGET_ADVICE displays memory target advice history.

This view contains snapshots of V$MEMORY_TARGET_ADVICE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
MEMORY_SIZE	NUMBER	NOT NULL	If the MEMORY_SIZE_FACTOR column has a value of 1, then this column shows the current size of memory, as set by the MEMORY_TARGET initialization parameter. If the value of the MEMORY_SIZE_FACTOR column is less than or greater than 1, then this column shows a proposed memory size.
MEMORY_SIZE_FACTOR	NUMBER		A multiplier for the current memory size. Possible values are 0.25, 0.5, 0.75, 1, 1.5, 1.75 and 2. This multiplier times the current memory size equals the value of the MEMORY_SIZE column.
ESTD_DB_TIME	NUMBER		For current memory size (MEMORY_SIZE_FACTOR = 1), the amount of database time required to complete the current workload. For a proposed memory size, the estimated amount of database time that would be required if the MEMORY_TARGET parameter were changed to the proposed size.
ESTD_DB_TIME_FACTOR	NUMBER		For a proposed memory size, ratio of estimated database time to current database time
VERSION	NUMBER		Version number of this recommendation
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$MEMORY_TARGET_ADVICE"

6.11 DBA_HIST_METRIC_NAME

DBA_HIST_METRIC_NAME describes attributes of the set of RDBMS metrics.

This view contains a snapshot of V$METRICNAME.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
GROUP_ID	NUMBER	NOT NULL	Metric Group ID
GROUP_NAME	VARCHAR2(64)		Metric group name
METRIC_ID	NUMBER	NOT NULL	Metric ID
METRIC_NAME	VARCHAR2(64)	NOT NULL	Metric name
METRIC_UNIT	VARCHAR2(64)	NOT NULL	Unit of measurement
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$METRICNAME"

6.12 DBA_HIST_MTTR_TARGET_ADVICE

DBA_HIST_MTTR_TARGET_ADVICE displays historical predictions of the number of physical I/O requests for the MTTR corresponding to each row.

The data also includes a physical I/O factor, which is the ratio of the number of estimated I/O requests to the number of I/O requests actually performed by the current MTTR setting during the measurement interval. This view contains snapshots of V$MTTR_TARGET_ADVICE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
MTTR_TARGET_FOR_ESTIMATE	NUMBER		MTTR setting being simulated (equal to the current MTTR setting if this is the first row of the view)
ADVICE_STATUS	VARCHAR2(5)		Current status of MTTR simulation: • ON SET • READY SET • OFF
DIRTY_LIMIT	NUMBER		Dirty buffer limit derived from the MTTR being simulated
ESTD_CACHE_WRITES	NUMBER		Estimated number of cache physical writes under the MTTR
ESTD_CACHE_WRITE_FACTOR	NUMBER		Estimated cache physical write ratio under the MTTR. It is the ratio of the estimated number of cache writes to the number of cache writes under the current MTTR setting.
ESTD_TOTAL_WRITES	NUMBER		Estimated total number of physical writes under the MTTR
ESTD_TOTAL_WRITE_FACTOR	NUMBER		Estimated total physical write ratio under the MTTR. It is the ratio of the estimated total number of physical writes to the total number of physical writes under the current MTTR setting.
ESTD_TOTAL_IOS	NUMBER		Estimated total number of I/O requests under the MTTR
ESTD_TOTAL_IO_FACTOR	NUMBER		Estimated total I/O ratio under the MTTR. It is the ratio of the estimated total number of I/O requests to the total number of I/O requests under the current MTTR setting.
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$MTTR_TARGET_ADVICE"

6.13 DBA_HIST_MUTEX_SLEEP

DBA_HIST_MUTEX_SLEEP displays mutex sleep summary historical statistics information.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database identifier for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
MUTEX_TYPE	VARCHAR2(32)	NOT NULL	Mutex type
LOCATION	VARCHAR2(40)	NOT NULL	The code location where the waiter slept for the mutex
SLEEPS	NUMBER		Number of sleeps for this MUTEX_TYPE and LOCATION
WAIT_TIME	NUMBER		Wait time in microseconds
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.14 DBA_HIST_OPTIMIZER_ENV

DBA_HIST_OPTIMIZER_ENV displays the optimizer environments that have been captured in the Workload Repository.

This view is used with the DBA_HIST_SQLSTAT view.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
OPTIMIZER_ENV_HASH_VALUE	NUMBER	NOT NULL	Hash value for the optimizer environment
OPTIMIZER_ENV	RAW(2000)		Optimizer environment
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "DBA_HIST_SQLSTAT"

6.15 DBA_HIST_OPTIMIZER_ENV_DETAILS

DBA_HIST_OPTIMIZER_ENV_DETAILS displays parameter values for the optimizer environments that have been captured in the Workload Repository.

This view is used with the DBA_HIST_SQLSTAT view.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
OPTIMIZER_ENV_HASH_VALUE	NUMBER	NOT NULL	Hash value for the optimizer environment
NAME	VARCHAR2(50)		Parameter name
VALUE	VARCHAR2(25)		Parameter value
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

6.16 DBA_HIST_OSSTAT

DBA_HIST_OSSTAT displays historical operating system statistics.

This view contains snapshots of V$OSSTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
STAT_ID	NUMBER	NOT NULL	Statistic ID
STAT_NAME	VARCHAR2(64)	NOT NULL	Statistic name
VALUE	NUMBER		Statistic value
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$OSSTAT"

6.17 DBA_HIST_OSSTAT_NAME

DBA_HIST_OSSTAT_NAME displays the names of the operating system statistics.

This view is used with DBA_HIST_OSSTAT.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
STAT_ID	NUMBER	NOT NULL	Statistic ID
STAT_NAME	VARCHAR2(64)	NOT NULL	Statistic name
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "DBA_HIST_OSSTAT"

6.18 DBA_HIST_PARAMETER

DBA_HIST_PARAMETER displays historical information about the initialization parameters that were in effect for the instance.

This view contains snapshots of V$SYSTEM_PARAMETER.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
PARAMETER_HASH	NUMBER	NOT NULL	Parameter hash
PARAMETER_NAME	VARCHAR2(64)	NOT NULL	Name of the parameter
VALUE	VARCHAR2(512)		Parameter value for the session (if modified within the session); otherwise, the instance-wide parameter value
ISDEFAULT	VARCHAR2(9)		Indicates whether the parameter is set to the default value (TRUE) or the parameter value was specified in the parameter file (FALSE)
ISMODIFIED	VARCHAR2(10)		Indicates whether the parameter has been modified after instance startup: • MODIFIED - Parameter has been modified with ALTER SESSION • SYSTEM_MOD - Parameter has been modified with ALTER SYSTEM (which causes all the currently logged in sessions' values to be modified) • FALSE - Parameter has not been modified after instance startup
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$SYSTEM_PARAMETER"

6.19 DBA_HIST_PARAMETER_NAME

DBA_HIST_PARAMETER_NAME displays information about the parameter names captured in the workload repository.

This view is used with the DBA_HIST_PARAMETER view.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
PARAMETER_HASH	NUMBER	NOT NULL	Parameter hash
PARAMETER_NAME	VARCHAR2(64)	NOT NULL	Name of the parameter
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "DBA_HIST_PARAMETER"

6.20 DBA_HIST_PDB_IN_SNAP

DBA_HIST_PDB_IN_SNAP captures a list of open pluggable databases (PDBs) at the time of the Automatic Workload Repository (AWR) snapshot. This view can be used with other DBA_HIST_ views to construct the number of opened PDBs at the time of the snapshot.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	AWR snapshot ID
DBID	NUMBER	NOT NULL	Database ID of the database that took this snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number of the instance that took this snapshot
CON_DBID	NUMBER		DBID of an open PDB at the time of the snapshot
FLAG	NUMBER		Flag field in capture properties of the PDB. Not used at this time.
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
OPEN_TIME_TZ	TIMESTAMP(3) WITH TIME ZONE		Time the PDB was last opened

6.21 DBA_HIST_PDB_INSTANCE

DBA_HIST_PDB_INSTANCE displays the pluggable databases (PDBs) and instances in the Workload Repository.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number
STARTUP_TIME	TIMESTAMP(3)	NOT NULL	Startup time of the instance
CON_DBID	NUMBER	NOT NULL	The database ID of the PDB for the sampled session
OPEN_TIME	TIMESTAMP(3)	NOT NULL	Time the PDB was last opened
OPEN_MODE	VARCHAR2(16)		Open mode of the database
PDB_NAME	VARCHAR2(128)		PDB name

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
SNAP_ID	NUMBER		The unique snapshot identifier of the snapshot that flushed the corresponding row
STARTUP_TIME_TZ	TIMESTAMP(3) WITH TIME ZONE		Startup time of the instance
OPEN_TIME_TZ	TIMESTAMP(3) WITH TIME ZONE		Time the PDB was last opened

6.22 DBA_HIST_PERSISTENT_QMN_CACHE

DBA_HIST_PERSISTENT_QMN_CACHE displays the historical summary background queue table activity.

This view contains snapshots from V$PERSISTENT_QMN_CACHE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
QUEUE_TABLE_ID	NUMBER	NOT NULL	Queue table object ID
TYPE	VARCHAR2(32)		Type of the queue table's queue monitor cache
STATUS	NUMBER		Status of the queue table's queue monitor cache
NEXT_SERVICE_TIME	TIMESTAMP(3)		Time when the queue table should be serviced by QMON servers
WINDOW_END_TIME	TIMESTAMP(3)		Time manager activity period for non-owner queue table operations
TOTAL_RUNS	NUMBER		Total number of times this queue table is served
TOTAL_LATENCY	NUMBER		Cumulative latency in serving the queue table (in hundredths of a second)
TOTAL_ELAPSED_TIME	NUMBER		Total time spent in processing this queue table (in seconds)
TOTAL_CPU_TIME	NUMBER		Cumulative CPU time for serving the queue table (in hundredths of a second)
TMGR_ROWS_PROCESSED	NUMBER		Number of time manager entries processed
TMGR_ELAPSED_TIME	NUMBER		Cumulative time for time management activities (in hundredths of a second)
TMGR_CPU_TIME	NUMBER		Cumulative CPU time for time management activities (in hundredths of a second)

Column	Datatype	NULL	Description
LAST_TMGR_PROCESSING_TIME	TIMESTAMP(3)		Last timer manager processing time
DEQLOG_ROWS_PROCESSED	NUMBER		Number of dequeue log entries processed
DEQLOG_PROCESSING_ELAPSED_TIME	NUMBER		Total time for processing dequeue log entries (in hundredths of a second)
DEQLOG_PROCESSING_CPU_TIME	NUMBER		Total CPU time for processing dequeue log entries (in hundredths of a second)
LAST_DEQLOG_PROCESSING_TIME	TIMESTAMP(3)		Last dequeue log processing time
DEQUEUE_INDEX_BLOCKS_FREED	NUMBER		Number of dequeue index blocks freed
HISTORY_INDEX_BLOCKS_FREED	NUMBER		Number of history index blocks freed
TIME_INDEX_BLOCKS_FREED	NUMBER		Number of time manager index blocks freed
INDEX_CLEANUP_COUNT	NUMBER		Number of times index block cleanup was attempted
INDEX_CLEANUP_ELAPSED_TIME	NUMBER		Total time for index block cleanup (in hundredths of a second)
INDEX_CLEANUP_CPU_TIME	NUMBER		Total CPU time for index block cleanup (in hundredths of a second)
LAST_INDEX_CLEANUP_TIME	TIMESTAMP(3)		Last index block cleanup time
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$PERSISTENT_QMN_CACHE"

6.23 DBA_HIST_PERSISTENT_QUEUES

DBA_HIST_PERSISTENT_QUEUES displays Oracle Database AQ persistent queues historical statistics information.

This view contains snapshots of V$PERSISTENT_QUEUES.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
QUEUE_SCHEMA	VARCHAR2(128)	NOT NULL	Owner of the queue
QUEUE_NAME	VARCHAR2(128)	NOT NULL	Name of the queue
QUEUE_ID	NUMBER	NOT NULL	Identifier for the queue
FIRST_ACTIVITY_TIME	TIMESTAMP(6)		First queue activity time since database startup
ENQUEUED_MSGS	NUMBER		Number of messages enqueued
DEQUEUED_MSGS	NUMBER		Number of messages dequeued **Note:** This column will not be incremented until all the subscribers of the message have dequeued the message and its retention time has elapsed.
BROWSED_MSGS	NUMBER		Number of messages that have been browsed
ELAPSED_ENQUEUE_TIME	NUMBER		Total time (in hundredths of a second) spent doing enqueue
ELAPSED_DEQUEUE_TIME	NUMBER		Total time (in hundredths of a second) spent doing dequeue
ENQUEUE_CPU_TIME	NUMBER		Total CPU time for enqueue (in hundredths of a second)
DEQUEUE_CPU_TIME	NUMBER		Total CPU time for dequeue (in hundredths of a second)
AVG_MSG_AGE	NUMBER		Average age of messages in the queue
DEQUEUED_MSG_LATENCY	NUMBER		Last dequeued message latency (in seconds)
ELAPSED_TRANSFORMATION_TIME	NUMBER		Total time (in hundredths of a second) spent doing transformation
ELAPSED_RULE_EVALUATION_TIME	NUMBER		Total time (in hundredths of a second) spent doing rule evaluation
ENQUEUED_EXPIRY_MSGS	NUMBER		Number of messages enqueued with expiry
ENQUEUED_DELAY_MSGS	NUMBER		Number of messages enqueued with delay
MSGS_MADE_EXPIRED	NUMBER		Number of messages expired by time manager
MSGS_MADE_READY	NUMBER		Number of messages made ready by time manager
LAST_ENQUEUE_TIME	TIMESTAMP(6)		Last message enqueue time
LAST_DEQUEUE_TIME	TIMESTAMP(6)		Last message dequeue time
LAST_TM_EXPIRY_TIME	TIMESTAMP(6)		Last time message was expired by time manager
LAST_TM_READY_TIME	TIMESTAMP(6)		Last time message was made ready by time manager
ENQUEUE_TRANSACTIONS	NUMBER		Number of enqueue transactions
DEQUEUE_TRANSACTIONS	NUMBER		Number of dequeue transactions
EXECUTION_COUNT	NUMBER		Number of executions of the dequeue cursor
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$PERSISTENT_QUEUES"

6.24 DBA_HIST_PERSISTENT_SUBS

DBA_HIST_PERSISTENT_SUBS displays Oracle Database AQ persistent queue subscribers historical statistics information.

This view contains snapshots of V$PERSISTENT_SUBSCRIBERS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
QUEUE_SCHEMA	VARCHAR2(128)	NOT NULL	Owner of the queue
QUEUE_NAME	VARCHAR2(128)	NOT NULL	Name of the queue
SUBSCRIBER_ID	NUMBER	NOT NULL	Internal subscriber number
SUBSCRIBER_NAME	VARCHAR2(128)		Name of the subscriber
SUBSCRIBER_ADDRESS	VARCHAR2(1024)		Address of the subscribing agent
SUBSCRIBER_TYPE	VARCHAR2(128)		Type of the subscriber: • PROXY - Propagation subscriber • SUBSCRIBER - Normal subscriber • RECIPIENT - Recipient
FIRST_ACTIVITY_TIME	TIMESTAMP(6)		First subscriber activity time since database startup
ENQUEUED_MSGS	NUMBER		Number of messages enqueued since FIRST_ACTIVITY_TIME
DEQUEUED_MSGS	NUMBER		Number of messages dequeued since FIRST_ACTIVITY_TIME
AVG_MSG_AGE	NUMBER		Average age of messages in the queue
BROWSED_MSGS	NUMBER		Number of messages that have been browsed
EXPIRED_MSGS	NUMBER		Number of messages expired since FIRST_ACTIVITY_TIME

Column	Datatype	NULL	Description
DEQUEUED_MSG_LATENCY	NUMBER		Last dequeued message latency (in seconds)
LAST_ENQUEUE_TIME	TIMESTAMP(6)		Timestamp of the last enqueued message
LAST_DEQUEUE_TIME	TIMESTAMP(6)		Timestamp of the last dequeued message
ELAPSED_DEQUEUE_TIME	NUMBER		Total time spent in dequeue (in hundredths of a second)
DEQUEUE_CPU_TIME	NUMBER		Total CPU time for dequeue (in hundredths of a second)
DEQUEUE_TRANSACTIONS	NUMBER		Number of dequeue transactions
EXECUTION_COUNT	NUMBER		Number of executions of the dequeue index cursor
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$PERSISTENT_SUBSCRIBERS"

6.25 DBA_HIST_PGA_TARGET_ADVICE

DBA_HIST_PGA_TARGET_ADVICE displays historical predictions of how the cache hit percentage and over allocation count statistics displayed by the V$PGASTAT performance view would be impacted if the value of the PGA_AGGREGATE_TARGET parameter is changed.

This view contains snapshots of V$PGA_TARGET_ADVICE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
PGA_TARGET_FOR_ESTIMATE	NUMBER	NOT NULL	Value of PGA_AGGREGATE_TARGET for the prediction (in bytes)
PGA_TARGET_FACTOR	NUMBER		PGA_TARGET_FOR_ESTIMATE / the current value of the PGA_AGGREGATE_TARGET parameter

Column	Datatype	NULL	Description
ADVICE_STATUS	VARCHAR2(3)		Indicates whether the advice is enabled (ON) or disabled (OFF) depending on the value of the STATISTICS_LEVEL parameter
BYTES_PROCESSED	NUMBER		Total bytes processed by all the work areas considered by this advice (in bytes)
ESTD_TIME	NUMBER		Time (in seconds) required to process the bytes
ESTD_EXTRA_BYTES_RW	NUMBER		Estimated number of extra bytes which would be read or written if PGA_AGGREGATE_TARGET was set to the value of the PGA_TARGET_FOR_ESTIMATE column. This number is derived from the estimated number and size of work areas which would run in one-pass (or multi-pass) for that value of PGA_AGGREGATE_TARGET.
ESTD_PGA_CACHE_HIT_PERCENTAGE	NUMBER		Estimated value of the cache hit percentage statistic when PGA_AGGREGATE_TARGET equals PGA_TARGET_FOR_ESTIMATE. This column is derived from the above two columns and is equal to BYTES_PROCESSED / (BYTES_PROCESSED + ESTD_EXTRA_BYTES_RW)
ESTD_OVERALLOC_COUNT	NUMBER		Estimated number of PGA memory over-allocations if the value of PGA_AGGREGATE_TARGET is set to PGA_TARGET_FOR_ESTIMATE. A nonzero value means that PGA_TARGET_FOR_ESTIMATE is not large enough to run the work area workload. Hence, PGA_AGGREGATE_TARGET should not be set to PGA_TARGET_FOR_ESTIMATE since Oracle will not be able to honor that target.
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$PGASTAT"
- "V$PGA_TARGET_ADVICE"
- "PGA_AGGREGATE_TARGET"

6.26 DBA_HIST_PGASTAT

DBA_HIST_PGASTAT displays historical PGA memory usage statistics as well as statistics about the automatic PGA memory manager when it is enabled.

This view contains snapshots of V$PGASTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Database instance number
NAME	VARCHAR2(64)	NOT NULL	Name of the statistic: • aggregate PGA auto target • aggregate PGA target parameter • bytes processed • cache hit percentage • extra bytes read/written • global memory bound • max processes count • maximum PGA allocated • maximum PGA used for auto workareas • maximum PGA used for manual workareas • over allocation count • PGA memory freed back to OS • process count • recompute count (total) • total freeable PGA memory • total PGA allocated • total PGA inuse • total PGA used for auto workareas • total PGA used for manual workareas **See Also:** V$PGASTAT for descriptions of the statistics
VALUE	NUMBER		Statistic value
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$PGASTAT"

6.27 DBA_HIST_PLAN_OPERATION_NAME

DBA_HIST_PLAN_OPERATION_NAME displays historical information about SQL plan operation names.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database identifier
OPERATION_ID	NUMBER	NOT NULL	Plan operation identifier
OPERATION_NAME	VARCHAR2(64)		Plan operation name. This value also appears in the SQL_PLAN_OPERATION column of the DBA_HIST_ACTIVE_SESS_HISTORY view.
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.28 DBA_HIST_PLAN_OPTION_NAME

DBA_HIST_PLAN_OPTION_NAME displays historical information about SQL plan option names.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database identifier
OPTION_ID	NUMBER	NOT NULL	Plan option identifier
OPTION_NAME	VARCHAR2(64)		Plan option name. This value also appears in the SQL_PLAN_OPTIONS column of the DBA_HIST_ACTIVE_SESS_HISTORY view.
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.29 DBA_HIST_PROCESS_MEM_SUMMARY

DBA_HIST_PROCESS_MEM_SUMMARY displays historical information about dynamic PGA memory usage by named component categories for each process.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
CATEGORY	VARCHAR2(15)	NOT NULL	Category name. Categories include "SQL", "PL/SQL", "OLAP" and "JAVA". Special categories are "Freeable" and "Other". Freeable memory has been allocated to the process by the operating system, but has not been allocated to a category. "Other" memory has been allocated to a category, but not to one of the named categories
IS_INSTANCE_WIDE	NUMBER		This column shows whether the process memory detail is for only this container or for the whole instance. If the value is 1, the detail is for the whole instance. Any other value is the container ID for the container to which the detail pertains, as seen in the CON_ID column.
NUM_PROCESSES	NUMBER		Number of processes
NON_ZERO_ALLOCS	NUMBER		Number of processes with nonzero allocations
USED_TOTAL	NUMBER		Bytes of PGA memory used by the process for the category
ALLOCATED_TOTAL	NUMBER		Total number of bytes of PGA memory allocated by the process for the category.
ALLOCATED_AVG	NUMBER		Average number of bytes of PGA memory allocated by the process for the category
ALLOCATED_STDDEV	NUMBER		Standard deviation of the number of bytes of PGA memory allocated by the process for the category
ALLOCATED_MAX	NUMBER		Maximum bytes of PGA memory ever allocated by the process for the category
MAX_ALLOCATED_MAX	NUMBER		Maximum bytes of PGA memory that can be allocated by the process for the category
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.30 DBA_HIST_PROCESS_WAITTIME

DBA_HIST_PROCESS_WAITTIME displays CPU and wait time by process types.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
PROCESS_TYPE	VARCHAR2(5)	NOT NULL	Process type
DESCRIPTION	VARCHAR2(64)	NOT NULL	Process description
WAIT_CLASS_TYPE	VARCHAR2(64)	NOT NULL	Type of wait class
VALUE	NUMBER		Wait time or CPU used time in milliseconds
CON_DBID	NUMBER		The database ID of the PDB for the process
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.31 DBA_HIST_RECOVERY_PROGRESS

DBA_HIST_RECOVERY_PROGRESS displays database recovery progress information for an instance.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
START_TIME	DATE	NOT NULL	Start time of the recovery operation

Column	Datatype	NULL	Description
TYPE	VARCHAR2(64)	NOT NULL	Type of recovery operation being performed: • CRASH RECOVERY • INSTANCE RECOVERY • MEDIA RECOVERY
ITEM	VARCHAR2(32)	NOT NULL	Item being measured. When TYPE is CRASH RECOVERY or INSTANCE RECOVERY, the possible values are: • Log Files • Redo Blocks When TYPE is MEDIA RECOVERY, the possible values are: • Active Apply Rate • Average Apply Rate • Maximum Apply Rate • Redo Applied • Log Files • Last Applied Redo • Active Time • Elapsed Time • Apply Time per Log • Checkpoint Time per Log • Standby Apply Lag • Recovery ID
UNITS	VARCHAR2(32)		The units of measurement for each item
SOFAR	NUMBER		Amount of work done so far
TOTAL	NUMBER		Total amount of work expected
TIMESTAMP	DATE		Timestamp of the last redo record applied
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root. • *n*: Where *n* is the applicable container ID for the rows containing data

6.32 DBA_HIST_REPLICATION_TBL_STATS

DBA_HIST_REPLICATION_TBL_STATS displays replication table statistics for Oracle GoldenGate and XStream sessions. This view is intended for use with Automatic Workload Repository (AWR).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
APPLY_NAME	VARCHAR2(128)	NOT NULL	Name of the apply process
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
SESSION_MODULE	VARCHAR2(64)	NOT NULL	Session module. Valid values: • XStream • GoldenGate
TOTAL_INSERTS	NUMBER		Number of insert operations on this table processed by this apply server
TOTAL_UPDATES	NUMBER		Number of update operations on this table processed by this apply server
TOTAL_DELETES	NUMBER		Number of delete operations on this table processed by this apply server
CDR_SUCCESSFUL	NUMBER		Number of successfully resolved conflicts
CDR_FAILED	NUMBER		Number of conflicts that could not be resolved due to an error during resolution
REPERR_CNT	NUMBER		The total number of errors for the replication operation
HANDLE_COLLISIONS	NUMBER		Number of collisions on this table handled by this apply server
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.33 DBA_HIST_REPLICATION_TXN_STATS

DBA_HIST_REPLICATION_TXN_STATS displays replication transaction statistics for Oracle GoldenGate and XStream sessions.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Object name
SESSION_TYPE	VARCHAR2(64)	NOT NULL	Type of session

Column	Datatype	NULL	Description
SESSION_MODULE	VARCHAR2(64)	NOT NULL	Session module. Valid values: • XStream • GoldenGate
SOURCE_DATABASE	VARCHAR2(128)		Database where the transaction originated
SOURCE_TXN_ID	VARCHAR2(128)	NOT NULL	Original transaction ID at the source database
FIRST_LCR_TIME	DATE		Time of the first LCR (message in an error transaction)
TOTAL_LCRS_COUNT	NUMBER		Total number of LCRs for this replication transaction
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.34 DBA_HIST_REPORTS

DBA_HIST_REPORTS displays information about XML reports captured into Automatic Workload Repository (AWR).

The reports themselves belong to components such as SQL Monitor, DBOP, and Real-Time ADDM.

Each XML report contains details about some activity of a component. For example, a SQL Monitor report contains a detailed report about a particular execution of a SQL statement, or a Real-Time ADDM report contains system performance data analyzed by Real-Time ADDM.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		ID of the first Automatic Workload Repository (AWR) snapshot that will be taken after this report is generated
DBID	NUMBER		Database ID of the current database for the report
INSTANCE_NUMBER	NUMBER		Instance number (for an Oracle RAC system)
REPORT_ID	NUMBER		ID of the captured report
COMPONENT_ID	NUMBER		ID of the component (for example, SQL Monitor) whose report is captured
SESSION_ID	NUMBER		ID of the session corresponding to the captured report (currently used only for SQL Monitor reports)

Column	Datatype	NULL	Description
SESSION_SERIAL#	NUMBER		Session serial number corresponding to the captured report (currently used only for SQL Monitor reports)
PERIOD_START_TIME	DATE		Time when the activity period started
PERIOD_END_TIME	DATE		Time when the activity period ended
GENERATION_TIME	DATE		Time when this report was generated
COMPONENT_NAME	VARCHAR2(128)		Name of the component whose report this is
REPORT_NAME	VARCHAR2(128)		Name of this report
REPORT_PARAMETERS	VARCHAR2(1024)		Parameters associated with this report
KEY1	VARCHAR2(128)		Key1 associated with the captured report
KEY2	VARCHAR2(128)		Key2 associated with the captured report
KEY3	VARCHAR2(128)		Key3 associated with the captured report
KEY4	VARCHAR2(256)		Key4 associated with the captured report
GENERATION_COST_SECONDS	NUMBER		Time taken to generate this report (in seconds)
REPORT_SUMMARY	VARCHAR2(4000)		Summary of this report
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "DBA_HIST_REPORTS_DETAILS"

6.35 DBA_HIST_REPORTS_CONTROL

DBA_HIST_REPORTS_CONTROL contains control information about the report capture mechanism that automatically captures XML reports to Automatic Workload Repository (AWR).

Reports are captured automatically for components like SQL Monitor and Real-Time Automatic Database Diagnostic Monitor (Real-Time ADDM).

Column	Datatype	NULL	Description
DBID	NUMBER		Database ID of the current database for the report

Column	Datatype	NULL	Description
EXECUTION_MODE	VARCHAR2(12)		Mode of execution of automatic report capture. Possible values: • REGULAR: Regular per-minute report capture subject to DBTIME budget • FULL_CAPTURE: Report capture will be run per minute without the DBTIME budget constraints and is provided to capture a more comprehensive set of reports **NOTE**: The FULL_CAPTURE mode can be started and ended respectively by executing the START_REPORT_CAPTURE and FINISH_REPORT_CAPTURE APIs in the DBMS_AUTO_REPORT package. At all other times, the execution mode should be REGULAR.

> **See Also:**
>
> *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_AUTO_REPORT package

6.36 DBA_HIST_REPORTS_DETAILS

DBA_HIST_REPORTS_DETAILS displays details about each report captured in Automatic Workload Repository (AWR).

Metadata for each report appears in the DBA_HIST_REPORTS view while the actual report is available in the DBA_HIST_REPORTS_DETAILS view.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		ID of the first AWR snapshot that will be taken after this report is generated
DBID	NUMBER		Database ID of the current database for the report
INSTANCE_NUMBER	NUMBER		Instance number (for an Oracle RAC system)
REPORT_ID	NUMBER		ID of the captured report
SESSION_ID	NUMBER		ID of the session corresponding to the captured report (currently used only for SQL Monitor reports)
SESSION_SERIAL#	NUMBER		Session serial number relevant to this report (currently used only for SQL Monitor reports)
GENERATION_TIME	DATE		Time when this report was generated
REPORT_COMPRESSED	BLOB		Actual XML report in compressed form
REPORT	CLOB		Full uncompressed report
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "DBA_HIST_REPORTS"

6.37 DBA_HIST_REPORTS_TIMEBANDS

DBA_HIST_REPORTS_TIMEBANDS contains bands of time with a new row created every day corresponding to a band of time.

Each band of time represents a period of time, and has a row for every report captured automatically into Automatic Workload Repository (AWR) during that time. If the activity period of a report spans across two bands of time (for example. the activity started before midnight and ended after midnight), then the view contains two rows for that report, with one row for each band of time. The view is partitioned to provide fast access to all reports captured in a given time frame.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		The AWR snapshot id corresponding to the report
DBID	NUMBER		Database ID of the current database for the report
INSTANCE_NUMBER	NUMBER		Instance number (for an Oracle RAC system)
CON_DBID	NUMBER		CDB ID of the captured report
COMPONENT_ID	NUMBER		ID of the component (for example, SQL Monitor) whose report is captured
COMPONENT_NAME	VARCHAR2(128)		Name of the component whose report is captured
BAND_START_TIME	DATE		Starting time of the time band
BAND_LENGTH	NUMBER		Length of time band in days (currently unused)
REPORT_ID	NUMBER		ID of the captured report
REPORT_GENERATION_TIME	DATE		Time when the report was generated
PERIOD_START_TIME	DATE		Time when the activity period started
PERIOD_END_TIME	DATE		Time when the activity period ended
KEY1	VARCHAR2(128)		Key1 associated with the captured report
KEY2	VARCHAR2(128)		Key2 associated with the captured report
KEY3	VARCHAR2(128)		Key3 associated with the captured report

Column	Datatype	NULL	Description
KEY4	VARCHAR2(256)		Key4 associated with the captured report
SESSION_ID	NUMBER		ID of the session corresponding to the captured report (currently used only for SQL Monitor reports)
SESSION_SERIAL#	NUMBER		Session serial number corresponding to the captured report (currently used only for SQL Monitor reports)
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.38 DBA_HIST_RESOURCE_LIMIT

DBA_HIST_RESOURCE_LIMIT displays historical information about global resource use for some of the system resource.

This view contains snapshots of V$RESOURCE_LIMIT.

If time is of interest, join this view with DBA_HIST_SNAPSHOT.END_INTERVAL_TIME.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
RESOURCE_NAME	VARCHAR2(30)	NOT NULL	Name of the resource
CURRENT_UTILIZATION	NUMBER		Number of (resources, locks, or processes) currently being used
MAX_UTILIZATION	NUMBER		Maximum consumption of the resource since the last instance start up
INITIAL_ALLOCATION	VARCHAR2(10)		Initial allocation. This will be equal to the value specified for the resource in the initialization parameter file (UNLIMITED for infinite allocation).
LIMIT_VALUE	VARCHAR2(10)		Unlimited for resources and locks. This can be greater than the initial allocation value (UNLIMITED for infinite limit).
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.39 DBA_HIST_ROWCACHE_SUMMARY

DBA_HIST_ROWCACHE_SUMMARY displays historical summary statistics for data dictionary activity.

This view contains snapshots of V$ROWCACHE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
PARAMETER	VARCHAR2(32)	NOT NULL	Name of the initialization parameter that determines the number of entries in the data dictionary cache
TOTAL_USAGE	NUMBER		Sum of the total number of entries in the cache
USAGE	NUMBER		Number of cache entries that contain valid data
GETS	NUMBER		Total number of requests for information on the data object
GETMISSES	NUMBER		Number of data requests resulting in cache misses
SCANS	NUMBER		Number of scan requests
SCANMISSES	NUMBER		Number of times a scan failed to find the data in the cache
SCANCOMPLETES	NUMBER		For a list of subordinate entries, the number of times the list was scanned completely
MODIFICATIONS	NUMBER		Number of inserts, updates, and deletions
FLUSHES	NUMBER		Number of times flushed to disk
DLM_REQUESTS	NUMBER		Number of DLM requests
DLM_CONFLICTS	NUMBER		Number of DLM conflicts
DLM_RELEASES	NUMBER		Number of DLM releases
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$ROWCACHE"

6.40 DBA_HIST_RSRC_CONSUMER_GROUP

DBA_HIST_RSRC_CONSUMER_GROUP displays historical information about Resource Manager consumer groups.

This view contains snapshots of V$RSRC_CONS_GROUP_HISTORY.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SEQUENCE#	NUMBER	NOT NULL	A sequential counter that uniquely describes the DBA_HIST_RSRC_PLAN entry to which these consumer group statistics apply. When the instance is restarted, this value is reset to zero.
CONSUMER_GROUP_ID	NUMBER	NOT NULL	Consumer group object ID (a unique number, consistent across database shutdowns and startups)
CONSUMER_GROUP_NAME	VARCHAR2(128)	NOT NULL	Name of the consumer group
REQUESTS	NUMBER	NOT NULL	Cumulative number of requests that were executed in the consumer group
CPU_WAIT_TIME	NUMBER	NOT NULL	Cumulative amount of time that sessions waited for CPU because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on.
CPU_WAITS	NUMBER	NOT NULL	Cumulative number of times all sessions in the consumer group had to wait for CPU because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on.
CONSUMED_CPU_TIME	NUMBER	NOT NULL	Cumulative amount of CPU time consumed by all sessions in the consumer group (in milliseconds)

Column	Datatype	NULL	Description
YIELDS	NUMBER	NOT NULL	Cumulative number of times that sessions in the consumer group had to yield CPU to other sessions because of quantum expiration
ACTIVE_SESS_LIMIT_HIT	NUMBER	NOT NULL	Number of times that sessions in the consumer group were queued because the consumer group reached its active session limit
UNDO_LIMIT_HIT	NUMBER	NOT NULL	Number of times that queries in the consumer group were cancelled because the consumer group reached its UNDO_POOL limit
SWITCHES_IN_CPU_TIME	NUMBER	NOT NULL	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_TIME limit
SWITCHES_OUT_CPU_TIME	NUMBER	NOT NULL	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_TIME limit
SWITCHES_IN_IO_MEGABYTES	NUMBER	NOT NULL	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_MEGABYTES limit
SWITCHES_OUT_IO_MEGABYTES	NUMBER	NOT NULL	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_MEGABYTES limit
SWITCHES_IN_IO_REQUESTS	NUMBER	NOT NULL	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_REQS limit
SWITCHES_OUT_IO_REQUESTS	NUMBER	NOT NULL	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_REQS limit
SWITCHES_IN_IO_LOGICAL	NUMBER		Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_LOGICAL limit
SWITCHES_OUT_IO_LOGICAL	NUMBER		Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_LOGICAL limit
SWITCHES_IN_ELAPSED_TIME	NUMBER		Number of switches into the consumer group because of the Resource Manager plan's SWITCH_ELAPSED_TIME limit
SWITCHES_OUT_ELAPSED_TIME	NUMBER		Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_ELAPSED_TIME limit
PGA_LIMIT_SESSIONS_KILLED	NUMBER		The number of sessions that were terminated because their PGA allocation exceeded the PGA limit specified in the Resource Plan’s SESSION_PGA_LIMIT directive
SQL_CANCELED	NUMBER	NOT NULL	Number of times that SQL queries running in the consumer group were terminated because they exceeded the Resource Manager plan's SWITCH_TIME limit and CANCEL_SQL was specified as the Resource Manager plan's SWITCH_GROUP

Column	Datatype	NULL	Description
ACTIVE_SESS_KILLED	NUMBER	NOT NULL	Number of times that sessions running in the consumer group were terminated because they exceeded the Resource Manager plan's SWITCH_TIME limit and KILL_SESSION was specified as the Resource Manager plan's SWITCH_GROUP
IDLE_SESS_KILLED	NUMBER	NOT NULL	Number of times that sessions in the consumer group were terminated because they were idle for too long (reached MAX_IDLE_TIME)
IDLE_BLKR_SESS_KILLED	NUMBER	NOT NULL	Number of times that sessions in the consumer group were terminated because they were idle too long (reached MAX_IDLE_BLOCKER_TIME) and were blocking other sessions
QUEUED_TIME	NUMBER	NOT NULL	Total amount of time that sessions in the consumer group have spent in the QUEUED state because of the active session limit (in milliseconds)
QUEUE_TIME_OUTS	NUMBER	NOT NULL	Number of times that requests from sessions in the consumer group timed out because they were queued for too long (reached QUEUEING_P1)
IO_SERVICE_TIME	NUMBER	NOT NULL	Cumulative I/O wait time (in milliseconds)
IO_SERVICE_WAITS	NUMBER	NOT NULL	Total number of wait requests
SMALL_READ_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	NOT NULL	Number of multiblock megabytes written
SMALL_READ_REQUESTS	NUMBER	NOT NULL	Number of single block read requests
SMALL_WRITE_REQUESTS	NUMBER	NOT NULL	Number of single block write requests
LARGE_READ_REQUESTS	NUMBER	NOT NULL	Number of multiblock read requests
LARGE_WRITE_REQUESTS	NUMBER	NOT NULL	Number of multiblock write requests
PQS_QUEUED	NUMBER		Number of times that sessions in the consumer group were queued when trying to run parallel statements
PQ_QUEUED_TIME	NUMBER		Total amount of time that sessions in the consumer group were queued when trying to run parallel statements (in milliseconds)
PQ_QUEUE_TIME_OUTS	NUMBER		Number of times that parallel statements from sessions in the consumer group timed out because their queue time exceeded the Resource Manager plan's PARALLEL_QUEUE_TIMEOUT limit
PQS_COMPLETED	NUMBER		Total number of completed parallel statements in the consumer group
PQ_SERVERS_USED	NUMBER		Total number of parallel servers used by completed parallel statements in the consumer group
PQ_ACTIVE_TIME	NUMBER		Cumulative sum of the parallel active times for all completed parallel statements in the consumer group (in milliseconds)

Column	Datatype	NULL	Description
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$RSRC_CONS_GROUP_HISTORY"

6.41 DBA_HIST_RSRC_METRIC

DBA_HIST_RSRC_METRIC displays information about historical Resource Manager metrics for the past hour.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
BEGIN_TIME	TIMESTAMP(3)	NOT NULL	Begin time of the interval
END_TIME	TIMESTAMP(3)	NOT NULL	End time of the interval
INTSIZE_CSEC	NUMBER	NOT NULL	Interval size (in hundredths of a second)
SEQUENCE#	NUMBER	NOT NULL	A sequential counter that uniquely describes the V$RSRC_PLAN_HISTORY entry to which these consumer group statistics apply. When the instance is restarted, this value is reset to zero.
CONSUMER_GROUP_ID	NUMBER	NOT NULL	Consumer group object ID (a unique number, consistent across database shutdowns and startups)
CPU_CONSUMED_TIME	NUMBER	NOT NULL	Cumulative amount of CPU time consumed by all sessions in the consumer group, in milliseconds
CPU_WAIT_TIME	NUMBER	NOT NULL	Cumulative amount of time that sessions waited for CPU because of resource management, in milliseconds. This does not include waits due to latch or enqueue contention, I/O waits, and so on. When CPU resources are not being actively managed, this value is set to zero.
AVG_RUNNING_SESSIONS	NUMBER		Average number of sessions in the consumer group that are currently running

Column	Datatype	NULL	Description
AVG_WAITING_SESSIONS	NUMBER		Average number of sessions in the consumer group that are waiting for CPU due to resource management. When CPU resources are not being actively managed, this value is set to zero.
RUNNING_SESSION_LIMIT	NUMBER		Maximum number of sessions in the consumer group that can run simultaneously. The value of this column is NUM_CPUS multiplied by the consumer group's MAX_UTILIZATION_LIMIT directive in the current Resource Manager plan.
AVG_CPU_UTILIZATION	NUMBER		Average percentage of CPU consumed by the consumer group, with respect to the total number of CPUs in the system
IO_REQUESTS	NUMBER	NOT NULL	I/O requests
IO_MEGABYTES	NUMBER	NOT NULL	I/O megabytes
IOPS	NUMBER		I/O operations per second during the previous minute for this PDB
IOMBPS	NUMBER		I/O megabytes per second during the previous minute for this PDB
AVG_ACTIVE_PARALLEL_STMTS	NUMBER		The average number of parallel statements that were running during the 1-minute metric window
AVG_QUEUED_PARALLEL_STMTS	NUMBER		The average number of parallel statements that were queued during the 1-minute metric window
AVG_ACTIVE_PARALLEL_SERVERS	NUMBER		The average number of parallel servers that were actively running as part of a parallel statement during the 1-minute metric window
AVG_QUEUED_PARALLEL_SERVERS	NUMBER		The average number of parallel servers that were requested by queued parallel statements during the 1-minute metric window
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.42 DBA_HIST_RSRC_PDB_METRIC

DBA_HIST_RSRC_PDB_METRIC displays information about historical Resource Manager metrics for the past hour by PDB.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot

Column	Datatype	NULL	Description
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
BEGIN_TIME	TIMESTAMP(3)	NOT NULL	Begin time of the interval
END_TIME	TIMESTAMP(3)	NOT NULL	End time of the interval
INTSIZE_CSEC	NUMBER	NOT NULL	Interval size (in hundredths of a second)
SEQUENCE#	NUMBER	NOT NULL	A sequential counter that uniquely describes the V$RSRC_PLAN_HISTORY entry to which these PDB statistics apply. When the instance is restarted, this value is reset to zero.
CPU_CONSUMED_TIME	NUMBER	NOT NULL	Cumulative amount of CPU time consumed by all sessions in the PDB, in milliseconds
CPU_WAIT_TIME	NUMBER	NOT NULL	Cumulative amount of time that sessions waited for CPU because of resource management, in milliseconds. This does not include waits due to latch or enqueue contention, I/O waits, and so on. When CPU resources are not being actively managed, this value is set to zero.
AVG_RUNNING_SESSIONS	NUMBER		Average number of sessions in the PDB that are currently running
AVG_WAITING_SESSIONS	NUMBER		Average number of sessions in the PDB that are waiting for CPU due to resource management. When CPU resources are not being actively managed, this value is set to zero.
AVG_CPU_UTILIZATION	NUMBER		Average percentage of CPU consumed by the PDB, with respect to the total number of CPUs in the system
IOPS	NUMBER		I/O operations per second during the previous minute for this PDB
IOMBPS	NUMBER		I/O megabytes per second during the previous minute for this PDB
IOPS_THROTTLE_EXEMPT	NUMBER		Indicates how much of the I/O per second in the current PDB was exempted from throttling. For example, if the value in the IOPS column is 20 I/Os and the value in the IOPS_THROTTLE_EXEMPT column is 5 I/Os, then 5 I/Os of the 20 I/Os in that second were exempted from throttling. I/O throttling is defined by the MAX_IOPS database initialization parameter.
IOMBPS_THROTTLE_EXEMPT	NUMBER		Indicates how many megabytes of I/O executed per second in the current PDB were exempted from throttling. For example, if the value in the IOMBPS column is 200 megabytes and the value in the IOMBPS_THROTTLE_EXEMPT column is 50 megabytes, then 50 megabytes of the 200 megabytes were exempt from throttling. I/O megabytes per second throttling is defined by the MAX_MBPS database initialization parameter.
AVG_IO_THROTTLE	NUMBER		Average throttle time per I/O operation in milliseconds during the previous minute for this PDB

Column	Datatype	NULL	Description
AVG_ACTIVE_PARALLEL_STMTS	NUMBER		The average number of parallel statements that were running during the 1-minute metric window
AVG_QUEUED_PARALLEL_STMTS	NUMBER		The average number of parallel statements that were queued during the 1-minute metric window
AVG_ACTIVE_PARALLEL_SERVERS	NUMBER		The average number of parallel servers that were actively running as part of a parallel statement during the 1-minute metric window
AVG_QUEUED_PARALLEL_SERVERS	NUMBER		The average number of parallel servers that were requested by queued parallel statements during the 1-minute metric window
SGA_BYTES	NUMBER	NOT NULL	The current SGA usage for this PDB in bytes
BUFFER_CACHE_BYTES	NUMBER	NOT NULL	The current usage of the buffer cache by this PDB in bytes
SHARED_POOL_BYTES	NUMBER	NOT NULL	The current usage of the shared pool by this PDB in bytes
PGA_BYTES	NUMBER	NOT NULL	The current PGA usage for this PDB in bytes
PLAN_ID	NUMBER	NOT NULL	Resource Manager plan identifier
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
MAX_AVG_RUNNING_SESSIONS	NUMBER	NOT NULL	Maximum value of AVG_RUNNING_SESSIONS during the last hour

Note:

- "MAX_IOPS"
- "MAX_MBPS"

6.43 DBA_HIST_RSRC_PLAN

DBA_HIST_RSRC_PLAN displays historical information about resource plans.

This view contains snapshots of V$RSRC_PLAN_HISTORY.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SEQUENCE#	NUMBER	NOT NULL	A sequential counter that uniquely describes a row. When the instance is restarted, this value is reset to zero.
START_TIME	DATE	NOT NULL	Time that the resource plan was enabled
END_TIME	DATE		Time that the resource plan was disabled; NULL if the row contains the current resource plan information
PLAN_ID	NUMBER	NOT NULL	Resource plan ID; NULL if the Resource Manager was disabled
PLAN_NAME	VARCHAR2(128)	NOT NULL	Resource plan name; NULL if the Resource Manager was disabled
CPU_MANAGED	VARCHAR2(4)	NOT NULL	Indicates whether the resource plan has parameters that specify a policy for how the Resource Manager should schedule sessions to manage CPU usage (ON) or whether Resource Manager is not managing CPU usage (OFF)
PARALLEL_EXECUTION_MANAGED	VARCHAR2(4)		State of parallel statement queuing: • OFF - Parallel statement queuing is disabled • STARTUP - Parallel statement queuing is enabled. This is a temporary state that can occur when an Oracle RAC database is undergoing configuration changes • FIFO - Parallel statement queuing is enabled. All parallel statements are managed in a single Oracle RAC FIFO queue • FULL - Parallel statement queuing is enabled. All parallel statements are managed in per-consumer group queues according to the current resource plan. This state is used when a resource plan that contains resource allocation directives (MGMT_P*) is enabled.
INSTANCE_CAGING	VARCHAR2(4)		Indicates whether instance caging is enabled (ON) or disabled (OFF). Instance caging is enabled if the CPU_COUNT initialization parameter is explicitly modified to a value other than 0 and Resource Manager is enabled.
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$RSRC_PLAN_HISTORY"

6.44 DBA_HIST_RULE_SET

DBA_HIST_RULE_SET displays historical information about rule set statistics.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
OWNER	VARCHAR2(128)	NOT NULL	Owner of the rule set
NAME	VARCHAR2(128)	NOT NULL	Name of the rule set
STARTUP_TIME	DATE	NOT NULL	Startup time of the instance
CPU_TIME	NUMBER		Total CPU time (in hundredths of a second) spent in evaluation of the rule set
ELAPSED_TIME	NUMBER		Total elapsed time (in hundredths of a second) spent in evaluation of the rule set
EVALUATIONS	NUMBER		Number of evaluations on the rule set
SQL_FREE_EVALUATIONS	NUMBER		Number of evaluations on the rule set which did not internally issue SQL to evaluate rules
SQL_EXECUTIONS	NUMBER		Total number of SQL statements executed during evaluation of the rule set
RELOADS	NUMBER		Number of times the rule set object was reloaded in shared memory
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.45 DBA_HIST_SAGAS

DBA_HIST_SAGAS provides a history of all completed sagas in the database. Its columns are the same as those in ALL_HIST_SAGAS.

This view displays sagas that were either initiated in the current PDB or joined by participants in the current PDB.

Completed sagas are retained in this view for the length of time specified by the SAGA_HIST_RETENTION initialization parameter. The default is 30 days.

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "ALL_HIST_SAGAS"
- "SAGA_HIST_RETENTION"

6.46 DBA_HIST_SEG_STAT

DBA_HIST_SEG_STAT displays historical information about segment-level statistics.

This view captures the top segments based on a set of criteria and captures information from V$SEGSTAT. The total value is the value of the statistics since instance startup. The delta value is the value of the statistics from the BEGIN_INTERVAL_TIME to the END_INTERVAL_TIME in the DBA_HIST_SNAPSHOT view.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
TS#	NUMBER	NOT NULL	Tablespace number
OBJ#	NUMBER	NOT NULL	Dictionary object number
DATAOBJ#	NUMBER	NOT NULL	Data object number
LOGICAL_READS_TOTAL	NUMBER		Cumulative value for logical reads
LOGICAL_READS_DELTA	NUMBER		Delta value for logical reads
BUFFER_BUSY_WAITS_TOTAL	NUMBER		Cumulative value for buffer busy waits
BUFFER_BUSY_WAITS_DELTA	NUMBER		Delta value for buffer busy waits
DB_BLOCK_CHANGES_TOTAL	NUMBER		Cumulative value for db block changes (in blocks)
DB_BLOCK_CHANGES_DELTA	NUMBER		Delta value for db block changes (in blocks)
PHYSICAL_READS_TOTAL	NUMBER		Cumulative value for physical reads (in blocks)
PHYSICAL_READS_DELTA	NUMBER		Delta value for physical reads (in blocks)
PHYSICAL_WRITES_TOTAL	NUMBER		Cumulative value for physical writes (in blocks)
PHYSICAL_WRITES_DELTA	NUMBER		Delta value for physical writes (in blocks)
PHYSICAL_READS_DIRECT_TOTAL	NUMBER		Cumulative value for physical reads direct (in blocks)

Column	Datatype	NULL	Description
PHYSICAL_READS_DIRECT_DELTA	NUMBER		Delta value for physical reads direct (in blocks)
PHYSICAL_WRITES_DIRECT_TOTAL	NUMBER		Cumulative value for physical writes direct (in blocks)
PHYSICAL_WRITES_DIRECT_DELTA	NUMBER		Delta value for physical writes direct (in blocks)
ITL_WAITS_TOTAL	NUMBER		Cumulative value for ITL waits
ITL_WAITS_DELTA	NUMBER		Delta value for ITL waits
ROW_LOCK_WAITS_TOTAL	NUMBER		Cumulative value for row lock waits
ROW_LOCK_WAITS_DELTA	NUMBER		Delta value for row lock waits
GC_CR_BLOCKS_SERVED_TOTAL	NUMBER		Cumulative value for global cache CR blocks served
GC_CR_BLOCKS_SERVED_DELTA	NUMBER		Delta value for global cache CR blocks served
GC_CU_BLOCKS_SERVED_TOTAL	NUMBER		Cumulative value for global cache current blocks served
GC_CU_BLOCKS_SERVED_DELTA	NUMBER		Delta value for global cache current blocks served
GC_BUFFER_BUSY_TOTAL	NUMBER		Cumulative value for global cache buffer busy
GC_BUFFER_BUSY_DELTA	NUMBER		Delta value for global cache buffer busy
GC_CR_BLOCKS_RECEIVED_TOTAL	NUMBER		Cumulative value for global cache CR blocks received
GC_CR_BLOCKS_RECEIVED_DELTA	NUMBER		Delta value for global cache CR blocks received
GC_CU_BLOCKS_RECEIVED_TOTAL	NUMBER		Cumulative value for global cache current blocks received
GC_CU_BLOCKS_RECEIVED_DELTA	NUMBER		Delta value for global cache current blocks received
SPACE_USED_TOTAL	NUMBER		Number of bytes used by user data
SPACE_USED_DELTA	NUMBER		Delta value for space used by user data (in bytes). A negative value indicates the number of bytes deleted in the segment.
SPACE_ALLOCATED_TOTAL	NUMBER		The number of bytes that are allocated
SPACE_ALLOCATED_DELTA	NUMBER		Delta value for the space allocated (in bytes). A negative value indicates the number of bytes deallocated to the tablespace.
TABLE_SCANS_TOTAL	NUMBER		Cumulative value for table scans
TABLE_SCANS_DELTA	NUMBER		Delta value for table scans
CHAIN_ROW_EXCESS_TOTAL	NUMBER		Cumulative value of number of chained row pieces that can be eliminated by table reorganization
CHAIN_ROW_EXCESS_DELTA	NUMBER		Delta value of number of chained row pieces that can be eliminated by table reorganization
PHYSICAL_READ_REQUESTS_TOTAL	NUMBER		Cumulative value of number of physical read I/O requests issued for the monitored segment
PHYSICAL_READ_REQUESTS_DELTA	NUMBER		Delta value of number of physical read I/O requests issued for the monitored segment

Column	Datatype	NULL	Description
PHYSICAL_WRITE_REQUESTS_TOTAL	NUMBER		Cumulative value of number of physical write I/O requests issued for the monitored segment
PHYSICAL_WRITE_REQUESTS_DELTA	NUMBER		Delta value of number of physical write I/O requests issued for the monitored segment
OPTIMIZED_PHYSICAL_READS_TOTAL	NUMBER		Cumulative value of number of physical reads from Database Smart Flash Cache for the monitored segment
OPTIMIZED_PHYSICAL_READS_DELTA	NUMBER		Delta value of number of physical reads from Database Smart Flash Cache for the monitored segment
IM_SCANS_TOTAL	NUMBER		Count of segment statistics
IM_SCANS_DELTA	NUMBER		Delta values for in-memory scans
POPULATE_CUS_TOTAL	NUMBER		Count of compression units (CUs) populated per segment
POPULATE_CUS_DELTA	NUMBER		Delta value for compression unit (CU) populate operations
REPOPULATE_CUS_TOTAL	NUMBER		Count of CUs repopulated per segment
REPOPULATE_CUS_DELTA	NUMBER		Delta value for compression unit (CU) repopulate operations
IM_DB_BLOCK_CHANGES_TOTAL	NUMBER		The total number of changes that were part of an update or delete operation that were made to segment blocks
IM_DB_BLOCK_CHANGES_DELTA	NUMBER		Delta value for database block changes
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SEGSTAT"
- "DBA_HIST_SNAPSHOT"

6.47 DBA_HIST_SEG_STAT_OBJ

DBA_HIST_SEG_STAT_OBJ displays all the names of the segments captured in the workload repository.

This view is used with the DBA_HIST_SEG_STAT view.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
TS#	NUMBER	NOT NULL	Tablespace number
OBJ#	NUMBER	NOT NULL	Dictionary object number
DATAOBJ#	NUMBER	NOT NULL	Data object number
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object
SUBOBJECT_NAME	VARCHAR2(128)		Name of the subobject (for example: partition)
OBJECT_TYPE	VARCHAR2(18)		Type of the object for example: table, tablespace)
TABLESPACE_NAME	VARCHAR2(30)		Tablespace Name for the object
PARTITION_TYPE	VARCHAR2(8)		Partition Type, if relevant
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"DBA_HIST_SEG_STAT"

6.48 DBA_HIST_SERVICE_NAME

DBA_HIST_SERVICE_NAME displays the names of the Services tracked by the Workload Repository.

This view contains information for V$SERVICES.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID for the snapshot
SERVICE_NAME_HASH	NUMBER	NOT NULL	Hash of the service name

Column	Datatype	NULL	Description
SERVICE_NAME	VARCHAR2(64)	NOT NULL	Name of the service
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$SERVICES"

6.49 DBA_HIST_SERVICE_STAT

DBA_HIST_SERVICE_STAT displays the history of important service statistics tracked by the Workload Repository.

The call rate statistics in this view can be used for making run-time routing decisions, for tracking service levels, and for per-instance diagnostics per call rate.

The elapsed timing for each call provides a relative value across instances for how well a node is processing SQL calls issued under a service name. When aggregation is enabled for the service name, this view provides historical data on the timing and work done for calls issued for the whole service. This view contains information from V$SERVICE_STATS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SERVICE_NAME_HASH	NUMBER	NOT NULL	Hash of the service name
SERVICE_NAME	VARCHAR2(64)	NOT NULL	Name of the service
STAT_ID	NUMBER	NOT NULL	Statistic identifier
STAT_NAME	VARCHAR2(64)	NOT NULL	Statistic name
VALUE	NUMBER		Value of the statistic
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$SERVICE_STATS"

6.50 DBA_HIST_SERVICE_WAIT_CLASS

DBA_HIST_SERVICE_WAIT_CLASS displays the history of wait class information for services as tracked by the Workload Repository.

This view contains information from V$SERVICE_WAIT_CLASS.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SERVICE_NAME_HASH	NUMBER	NOT NULL	Hash of the service name
SERVICE_NAME	VARCHAR2(64)	NOT NULL	Name of the service
WAIT_CLASS_ID	NUMBER	NOT NULL	Identifier for the class of the wait event
WAIT_CLASS	VARCHAR2(64)		Name for the class of the wait event
TOTAL_WAITS	NUMBER		Total number of waits for this event
TIME_WAITED	NUMBER		Total amount of time waited for this event (in hundredths of a second)
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$SERVICE_WAIT_CLASS"

6.51 DBA_HIST_SESS_SGA_STATS

DBA_HIST_SESS_SGA_STATS shows usage statistics for high utilization Oracle GoldenGate and XStream sessions.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Object name
SESSION_TYPE	VARCHAR2(64)	NOT NULL	Type of session
SESSION_MODULE	VARCHAR2(64)	NOT NULL	Session module. Valid values: • XStream • GoldenGate
SGA_USED	NUMBER		The total amount of shared memory (in bytes) currently used by the session out of the amount allocated (SGA_ALLOCATED)
SGA_ALLOCATED	NUMBER		The total amount of shared memory (in bytes) allocated from the pool for the session
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.52 DBA_HIST_SESS_TIME_STATS

DBA_HIST_SESS_TIME_STATS displays information about CPU and I/O time for interesting Oracle GoldenGate and XStream sessions.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SESSION_TYPE	VARCHAR2(64)	NOT NULL	Type of session

Column	Datatype	NULL	Description
MIN_LOGON_TIME	DATE		Minimum logon time
SUM_CPU_TIME	NUMBER		Total CPU time
SUM_SYS_IO_WAIT	NUMBER		Total system I/O wait time
SUM_USER_IO_WAIT	NUMBER		Total user I/O wait time
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
SESSION_MODULE	VARCHAR2(64)	NOT NULL	Session module. Valid values: • XStream • GoldenGate
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.53 DBA_HIST_SESSMETRIC_HISTORY

DBA_HIST_SESSMETRIC_HISTORY displays the history of several important session metrics.

> **Note:**
>
> This view is populated only if a session metric exceeds a server metric threshold that was configured using the DBMS_SERVER_ALERT package.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
BEGIN_TIME	DATE	NOT NULL	Begin time of the interval
END_TIME	DATE	NOT NULL	End time of the interval
SESSID	NUMBER	NOT NULL	Session ID
SERIAL#	NUMBER	NOT NULL	Session serial number
INTSIZE	NUMBER	NOT NULL	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	NOT NULL	Group ID
METRIC_ID	NUMBER	NOT NULL	Metric ID
METRIC_NAME	VARCHAR2(64)	NOT NULL	Metric name
VALUE	NUMBER	NOT NULL	Metric Value

Column	Datatype	NULL	Description
METRIC_UNIT	VARCHAR2(64)	NOT NULL	Unit of measurement
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> The DBMS_SERVER_ALERT package in *Oracle Database PL/SQL Packages and Types Reference*

6.54 DBA_HIST_SGA

DBA_HIST_SGA displays historical summary information about the system global area (SGA).

This view contains snapshots of V$SGA.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
NAME	VARCHAR2(64)	NOT NULL	SGA component group
VALUE	NUMBER	NOT NULL	Memory size (in bytes)
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$SGA"

6.55 DBA_HIST_SGA_TARGET_ADVICE

DBA_HIST_SGA_TARGET_ADVICE provides historical information about the SGA_TARGET initialization parameter.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SGA_SIZE	NUMBER	NOT NULL	Size of the SGA
SGA_SIZE_FACTOR	NUMBER	NOT NULL	Ratio between the SGA_SIZE and the current size of the SGA
ESTD_DB_TIME	NUMBER	NOT NULL	Estimated DB_TIME for this SGA_SIZE
ESTD_PHYSICAL_READS	NUMBER		Estimated number of physical reads
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "SGA_TARGET"

6.56 DBA_HIST_SGASTAT

DBA_HIST_SGASTAT displays detailed historical information on the system global area (SGA).

This view contains snapshots of V$SGASTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot

Column	Datatype	NULL	Description
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
NAME	VARCHAR2(64)		SGA component group
POOL	VARCHAR2(30)		Designates the pool in which the memory in NAME resides: • in-memory pool - Memory is allocated from the In-Memory pool • java pool - Memory is allocated from the Java pool • large pool - Memory is allocated from the large pool • numa pool - Memory is allocated from the NUMA pool • shared pool - Memory is allocated from the shared pool • streams pool - Memory is allocated from the Streams pool
BYTES	NUMBER		Memory size (in bytes)
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$SGASTAT"

6.57 DBA_HIST_SHARED_POOL_ADVICE

DBA_HIST_SHARED_POOL_ADVICE displays historical information about estimated parse time in the shared pool for different pool sizes.

This view contains snapshots of V$SHARED_POOL_ADVICE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SHARED_POOL_SIZE_FOR_ESTIMATE	NUMBER	NOT NULL	Shared pool size for the estimate (in megabytes)

Column	Datatype	NULL	Description
SHARED_POOL_SIZE_FACTOR	NUMBER		Size factor with respect to the current shared pool size
ESTD_LC_SIZE	NUMBER		Estimated memory in use by the library cache (in megabytes)
ESTD_LC_MEMORY_OBJECTS	NUMBER		Estimated number of library cache memory objects in the shared pool of the specified size
ESTD_LC_TIME_SAVED	NUMBER		Estimated elapsed parse time saved (in seconds), owing to library cache memory objects being found in a shared pool of the specified size. This is the time that would have been spent in reloading the required objects in the shared pool had they been aged out due to insufficient amount of available free memory.
ESTD_LC_TIME_SAVED_FACTOR	NUMBER		Estimated parse time saved factor with respect to the current shared pool size
ESTD_LC_LOAD_TIME	NUMBER		Estimated elapsed time (in seconds) for parsing in a shared pool of the specified size.
ESTD_LC_LOAD_TIME_FACTOR	NUMBER		Estimated load time factor with respect to the current shared pool size
ESTD_LC_MEMORY_OBJECT_HITS	NUMBER		Estimated number of times a library cache memory object was found in a shared pool of the specified size
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$SHARED_POOL_ADVICE"

6.58 DBA_HIST_SHARED_SERVER_SUMMARY

DBA_HIST_SHARED_SERVER_SUMMARY displays historical information for shared servers.

This includes information about shared server activity, the servers, common queues, and dispatcher queues. This view obtains information from V$SHARED_SERVER, V$DISPATCHER, V$CIRCUIT, and V$QUEUE, and is aggregated over all servers, dispatchers, queues, and circuits.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
NUM_SAMPLES	NUMBER		Total number of samples
SAMPLE_TIME	NUMBER		Last sample timestamp
SAMPLED_TOTAL_CONN	NUMBER		Cumulative sum of total number of connections over all samples. To determine the average number of connections between two snapshots, divide the difference in SAMPLED_TOTAL_CONN by the difference in NUM_SAMPLES.
SAMPLED_ACTIVE_CONN	NUMBER		Cumulative sum of active number of connections over all samples. To determine the average number of active connections between two snapshots, divide the difference in SAMPLED_ACTIVE_CONN by the difference in NUM_SAMPLES.
SAMPLED_TOTAL_SRV	NUMBER		Cumulative sum of total number of servers over all samples. To determine the average number of servers between two snapshots, divide the difference in SAMPLED_TOTAL_SRV by the difference in NUM_SAMPLES.
SAMPLED_ACTIVE_SRV	NUMBER		Cumulative sum of active number of servers over all samples. To determine the average number of active servers between two snapshots, divide the difference in SAMPLED_ACTIVE_SRV by the difference in NUM_SAMPLES.
SAMPLED_TOTAL_DISP	NUMBER		Cumulative sum of total number of dispatchers over all samples. To determine the average number of dispatchers between two snapshots, divide the difference in SAMPLED_TOTAL_DISP by the difference in NUM_SAMPLES.
SAMPLED_ACTIVE_DISP	NUMBER		Cumulative sum of active number of dispatchers over all samples. To determine the average number of active dispatchers between two snapshots, divide the difference in SAMPLED_ACTIVE_DISP by the difference in NUM_SAMPLES.
SRV_BUSY	NUMBER		Total shared server busy time (in hundredths of a second)
SRV_IDLE	NUMBER		Total shared server idle time (in hundredths of a second)
SRV_IN_NET	NUMBER		Total shared server incoming network wait time (in hundredths of a second). This includes waits for receives and resets. This time is also included in SRV_BUSY.
SRV_OUT_NET	NUMBER		Total shared server outgoing network wait time (in hundredths of a second). This includes waits for sends and outbound connection requests. This time is also included in SRV_BUSY.
SRV_MESSAGES	NUMBER		Number of messages processed

Column	Datatype	NULL	Description
SRV_BYTES	NUMBER		Total number of bytes in all messages
CQ_WAIT	NUMBER		Total time that all items in the common queue have waited (in hundredths of a second)
CQ_TOTALQ	NUMBER		Total number of items that have ever been in the common queue
DQ_TOTALQ	NUMBER		Total number of items that have ever been in a dispatcher queue
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SHARED_SERVER"
- "V$DISPATCHER"
- "V$CIRCUIT"
- "V$QUEUE"

6.59 DBA_HIST_SNAP_ERROR

DBA_HIST_SNAP_ERROR displays information about the snapshot error information in the Workload Repository.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table in which the error occurred
ERROR_NUMBER	NUMBER	NOT NULL	Error number for the error encountered
STEP_ID	NUMBER		For internal use only

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.60 DBA_HIST_SNAPSHOT

DBA_HIST_SNAPSHOT displays information about the snapshots in the Workload Repository.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
STARTUP_TIME	TIMESTAMP(3)	NOT NULL	Startup time of the instance
BEGIN_INTERVAL_TIME	TIMESTAMP(3)	NOT NULL	Time at the beginning of the snapshot interval
END_INTERVAL_TIME	TIMESTAMP(3)	NOT NULL	Time at the end of the snapshot interval; the actual time the snapshot was taken
FLUSH_ELAPSED	INTERVAL DAY(5) TO SECOND(1)		Amount of time to perform the snapshot
SNAP_LEVEL	NUMBER		Snapshot level
ERROR_COUNT	NUMBER		Number of errors occurring in the tables for the particular snapshot
SNAP_FLAG	NUMBER		Condition under which the snapshot was inserted. Possible values are: 0 - Snapshot was taken automatically by the Manageability Monitor Process (MMON process) 1 - Manual snapshot created using a PL/SQL package 2 - Imported snapshot 4 - Snapshot taken while Diagnostic Pack or Tuning Pack was not enabled
SNAP_TIMEZONE	INTERVAL DAY(0) TO SECOND(0)		Snapshot time zone expressed as offset from UTC (Coordinated Universal Time) time zone
BEGIN_INTERVAL_TIME_TZ	TIMESTAMP(3) WITH TIME ZONE		Time at the beginning of the snapshot interval, with timezone
END_INTERVAL_TIME_TZ	TIMESTAMP(3) WITH TIME ZONE		Time at the end of the snapshot interval; the actual time the snapshot was taken, with timezone

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> Table F-1 for more information about the MMON process

6.61 DBA_HIST_SQL_BIND_METADATA

DBA_HIST_SQL_BIND_METADATA displays historical information on metadata for bind variables used by SQL cursors.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID for the snapshot
SQL_ID	VARCHAR2(13)	NOT NULL	SQL identifier of the parent cursor in the library cache
NAME	VARCHAR2(128)		Name of the bind variable
POSITION	NUMBER	NOT NULL	Position of the bind variable in the SQL statement
DUP_POSITION	NUMBER		If the binding is performed by name and the bind variable is duplicated, then this column gives the position of the primary bind variable
DATATYPE	NUMBER		Internal identifier for the bind data type. Beginning in Oracle Database 12*c*, a number representing a PL/SQL data type can appear in this column.
DATATYPE_STRING	VARCHAR2(15)		Textual representation of the bind data type. Beginning in Oracle Database 12*c*, a text representation of a PL/SQL-only data type can appear in this column. If the actual data type is a PL/SQL sub type, the name of the data type, not the sub type will be displayed.
CHARACTER_SID	NUMBER		National character set identifier
PRECISION	NUMBER		Precision (for numeric binds)
SCALE	NUMBER		Scale (for numeric binds)
MAX_LENGTH	NUMBER		Maximum bind length
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.62 DBA_HIST_SQL_PLAN

DBA_HIST_SQL_PLAN displays the execution plan information for each child cursor in the workload repository.

This view captures information from V$SQL_PLAN and is used with the DBA_HIST_SQLSTAT view.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
SQL_ID	VARCHAR2(13)	NOT NULL	SQL identifier of the parent cursor in the library cache
PLAN_HASH_VALUE	NUMBER	NOT NULL	Numerical representation of the SQL plan for the cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line).
ID	NUMBER	NOT NULL	A number assigned to each step in the execution plan
OPERATION	VARCHAR2(30)		Name of the internal operation performed in this step (for example, TABLE ACCESS)
OPTIONS	VARCHAR2(30)		A variation on the operation described in the OPERATION column (for example, FULL)
OBJECT_NODE	VARCHAR2(128)		Name of the database link used to reference the object (a table name or view name). For local queries that use parallel execution, this column describes the order in which output from operations is consumed.
OBJECT#	NUMBER		Object number of the table or the index
OBJECT_OWNER	VARCHAR2(128)		Name of the user who owns the schema containing the table or index
OBJECT_NAME	VARCHAR2(128)		Name of the table or index
OBJECT_ALIAS	VARCHAR2(261)		Alias for the object
OBJECT_TYPE	VARCHAR2(20)		Type of the object
OPTIMIZER	VARCHAR2(20)		Current mode of the optimizer for the first row in the plan (statement line), for example, ALL_ROWS. When the operation is a database access (for example, TABLE ACCESS), this column indicates whether or not the object is analyzed.

Column	Datatype	NULL	Description
PARENT_ID	NUMBER		ID of the next execution step that operates on the output of the current step
DEPTH	NUMBER		Depth (or level) of the operation in the tree. It is not necessary to issue a CONNECT BY statement to get the level information, which is generally used to indent the rows from the PLAN_TABLE table. The root operation (statement) is level 0.
POSITION	NUMBER		Order of processing for all operations that have the same PARENT_ID
SEARCH_COLUMNS	NUMBER		Number of index columns with start and stop keys (that is, the number of columns with matching predicates)
COST	NUMBER		Cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
CARDINALITY	NUMBER		Estimate, by the cost-based optimizer, of the number of rows produced by the operation
BYTES	NUMBER		Estimate, by the cost-based optimizer, of the number of bytes produced by the operation
OTHER_TAG	VARCHAR2(35)		Describes the contents of the OTHER column. See EXPLAIN PLAN for values.
PARTITION_START	VARCHAR2(64)		Start partition of a range of accessed partitions
PARTITION_STOP	VARCHAR2(64)		Stop partition of a range of accessed partitions
PARTITION_ID	NUMBER		Step that computes the pair of values of the PARTITION_START and PARTITION_STOP columns
OTHER	VARCHAR2(4000)		Other information specific to the execution step that users may find useful. See EXPLAIN PLAN for values.
DISTRIBUTION	VARCHAR2(20)		Stores the method used to distribute rows from producer query servers to consumer query servers
CPU_COST	NUMBER		CPU cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
IO_COST	NUMBER		I/O cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
TEMP_SPACE	NUMBER		Temporary space usage of the operation (sort or hash-join) as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
ACCESS_PREDICATES	VARCHAR2(4000)		Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.
FILTER_PREDICATES	VARCHAR2(4000)		Predicates used to filter rows before producing them

Column	Datatype	NULL	Description
PROJECTION	VARCHAR2(4000)		Expressions produced by the operation
TIME	NUMBER		Elapsed time (in seconds) of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
QBLOCK_NAME	VARCHAR2(128)		Name of the query block
REMARKS	VARCHAR2(4000)		Remarks
TIMESTAMP	DATE		Timestamp for when the plan was produced
OTHER_XML	CLOB		Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML because it allows multiple pieces of information to be stored, including the following: • Name of the schema against which the query was parsed • Release number of the Oracle Database that produced the explain plan • Hash value associated with the execution plan • Name (if any) of the outline or the SQL profile used to build the execution plan • Indication of whether or not dynamic statistics were used to produce the plan • The outline data, a set of optimizer hints that can be used to regenerate the same plan
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SQL_PLAN"
- "DBA_HIST_SQLSTAT"

6.63 DBA_HIST_SQL_SUMMARY

DBA_HIST_SQL_SUMMARY displays historical SQL summary information.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
TOTAL_SQL	NUMBER	NOT NULL	Total number of SQLs
TOTAL_SQL_MEM	NUMBER	NOT NULL	Total sharable memory in bytes for SQLs
SINGLE_USE_SQL	NUMBER	NOT NULL	Total number of single execution SQLs
SINGLE_USE_SQL_MEM	NUMBER	NOT NULL	Total sharable memory in bytes for single execution SQLs
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.64 DBA_HIST_SQL_WORKAREA_HSTGRM

DBA_HIST_SQL_WORKAREA_HSTGRM displays the historical cumulative work area execution statistics (cumulated since instance startup) for different work area groups.

This view contains snapshots of V$SQL_WORKAREA_HISTOGRAM.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
LOW_OPTIMAL_SIZE	NUMBER	NOT NULL	Lower bound for the optimal memory requirement of work areas included in the row (in bytes)
HIGH_OPTIMAL_SIZE	NUMBER	NOT NULL	Upper bound for the optimal memory requirement of work areas included in the row (in bytes)
OPTIMAL_EXECUTIONS	NUMBER		Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which have been executed in optimal mode since instance startup
ONEPASS_EXECUTIONS	NUMBER		Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which have been executed in one-pass mode since instance startup

Column	Datatype	NULL	Description
MULTIPASSES_EXECUTIONS	NUMBER		Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which have been executed in multi-pass mode since instance startup
TOTAL_EXECUTIONS	NUMBER		Sum of OPTIMAL_EXECUTIONS, ONEPASS_EXECUTIONS, and MULTIPASSES_EXECUTIONS
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$SQL_WORKAREA_HISTOGRAM"

6.65 DBA_HIST_SQLBIND

DBA_HIST_SQLBIND displays historical information on bind variables used by SQL cursors.

This view contains snapshots of V$SQL_BIND_CAPTURE.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SQL_ID	VARCHAR2(13)	NOT NULL	SQL identifier of the parent cursor in the library cache
NAME	VARCHAR2(128)		Name of the bind variable
POSITION	NUMBER	NOT NULL	Position of the bind variable in the SQL statement
DUP_POSITION	NUMBER		If the binding is performed by name and the bind variable is duplicated, then this column gives the position of the primary bind variable.
DATATYPE	NUMBER		Internal identifier for the bind data type. Beginning in Oracle Database 12*c*, a number representing a PL/SQL data type can appear in this column.

Column	Datatype	NULL	Description
DATATYPE_STRING	VARCHAR2(15)		Textual representation of the bind data type. Beginning in Oracle Database 12*c*, a text representation of a PL/SQL-only data type can appear in this column. If the actual data type is a PL/SQL sub type, the name of the data type, not the sub type will be displayed.
CHARACTER_SID	NUMBER		National character set identifier
PRECISION	NUMBER		Precision (for numeric binds)
SCALE	NUMBER		Scale (for numeric binds)
MAX_LENGTH	NUMBER		Maximum bind length
WAS_CAPTURED	VARCHAR2(3)		Indicates whether the bind value was captured (YES) or not (NO)
LAST_CAPTURED	DATE		Date when the bind value was captured. Bind values are captured when SQL statements are executed. To limit the overhead, binds are captured at most every 15 minutes for a given cursor.
VALUE_STRING	VARCHAR2(4000)		Value of the bind represented as a string
VALUE_ANYDATA	ANYDATA		Value of the bind represented using the self-descriptive Sys.AnyData data type. This representation is useful to programmatically decode the value of the bind variable. This column is NULL if a PL/SQL-only data type appears in the DATATYPE column.
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$SQL_BIND_CAPTURE"

6.66 DBA_HIST_SQLCOMMAND_NAME

DBA_HIST_SQLCOMMAND_NAME displays the mapping between SQL opcodes and names.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID

Column	Datatype	NULL	Description
COMMAND_TYPE	NUMBER	NOT NULL	SQL command number
COMMAND_NAME	VARCHAR2(64)		SQL command name
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.67 DBA_HIST_SQLSTAT

DBA_HIST_SQLSTAT displays historical information about SQL statistics.

This view captures the top SQL statements based on a set of criteria and captures the statistics information from V$SQL. The total value is the value of the statistics since instance startup. The delta value is the value of the statistics from the BEGIN_INTERVAL_TIME to the END_INTERVAL_TIME in the DBA_HIST_SNAPSHOT view.

This view is used with the DBA_HIST_OPTIMIZER_ENV, DBA_HIST_SQLTEXT, and DBA_HIST_SQL_PLAN views to provide a complete picture of historical SQL statistics.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SQL_ID	VARCHAR2(13)	NOT NULL	SQL identifier of the parent cursor in the library cache
PLAN_HASH_VALUE	NUMBER	NOT NULL	Numerical representation of the SQL plan for the cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line).
OPTIMIZER_COST	NUMBER		Cost of the query given by the optimizer
OPTIMIZER_MODE	VARCHAR2(10)		Mode under which the SQL statement is executed
OPTIMIZER_ENV_HASH_VALUE	NUMBER		Hash Value for the optimizer environment
SHARABLE_MEM	NUMBER		Amount of shared memory used by the child cursor (in bytes)
LOADED_VERSIONS	NUMBER		Indicates whether the context heap is loaded (1) or not (0)
VERSION_COUNT	NUMBER		Number of children associated with the cursor

Column	Datatype	NULL	Description
MODULE	VARCHAR2(64)		Contains the name of the module that was executing at the time that the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_MODULE
ACTION	VARCHAR2(64)		Contains the name of the action that was executing at the time that the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_ACTION
SQL_PROFILE	VARCHAR2(64)		Name of the applied SQL Profile
FORCE_MATCHING_SIGNATURE	NUMBER		The signature used when the CURSOR_SHARING parameter is set to FORCE
PARSING_SCHEMA_ID	NUMBER		Schema ID that was used to originally build the child cursor
PARSING_SCHEMA_NAME	VARCHAR2(128)		Schema name that was used to originally build the child cursor
PARSING_USER_ID	NUMBER		User ID that was used to originally build the child cursor
FETCHES_TOTAL	NUMBER		Cumulative number of fetches associated with the SQL statement
FETCHES_DELTA	NUMBER		Delta number of fetches associated with the SQL statement
END_OF_FETCH_COUNT_TOTAL	NUMBER		Cumulative number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic is not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed. By definition, the value of the END_OF_FETCH_COUNT column should be less or equal to the value of the EXECUTIONS column.
END_OF_FETCH_COUNT_DELTA	NUMBER		Delta number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic is not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed.
SORTS_TOTAL	NUMBER		Cumulative number of sorts that were done for this child cursor
SORTS_DELTA	NUMBER		Delta number of sorts that were done for this child cursor
EXECUTIONS_TOTAL	NUMBER		Cumulative number of executions that took place on this object since it was brought into the library cache
EXECUTIONS_DELTA	NUMBER		Delta number of executions that took place on this object since it was brought into the library cache
PX_SERVERS_EXECS_TOTAL	NUMBER		Cumulative number of PX server executions
PX_SERVERS_EXECS_DELTA	NUMBER		Delta number of PX server executions

Column	Datatype	NULL	Description
LOADS_TOTAL	NUMBER		Cumulative number of times the object was either loaded or reloaded
LOADS_DELTA	NUMBER		Delta number of times the object was either loaded or reloaded
INVALIDATIONS_TOTAL	NUMBER		Cumulative number of times this child cursor has been invalidated
INVALIDATIONS_DELTA	NUMBER		Delta number of times this child cursor has been invalidated
PARSE_CALLS_TOTAL	NUMBER		Cumulative number of parse calls for this child cursor
PARSE_CALLS_DELTA	NUMBER		Delta number of parse calls for this child cursor
DISK_READS_TOTAL	NUMBER		Cumulative number of disk reads for this child cursor
DISK_READS_DELTA	NUMBER		Delta number of disk reads for this child cursor
BUFFER_GETS_TOTAL	NUMBER		Cumulative number of buffer gets for this child cursor
BUFFER_GETS_DELTA	NUMBER		Delta number of buffer gets for this child cursor
ROWS_PROCESSED_TOTAL	NUMBER		Cumulative number of rows the parsed SQL statement returns
ROWS_PROCESSED_DELTA	NUMBER		Delta number of rows the parsed SQL statement returns
CPU_TIME_TOTAL	NUMBER		Cumulative value of CPU time (in microseconds) used by this cursor for parsing/executing/fetching
CPU_TIME_DELTA	NUMBER		Delta value of CPU time (in microseconds) used by this cursor for parsing/executing/fetching
ELAPSED_TIME_TOTAL	NUMBER		Cumulative value of elapsed time (in microseconds) used by this cursor for parsing/ executing/fetching. If the cursor uses parallel execution, then ELAPSED_TIME_TOTAL is the cumulative time for the query coordinator, plus all parallel query worker processes.
ELAPSED_TIME_DELTA	NUMBER		Delta value of elapsed time (in microseconds) used by this cursor for parsing/executing/fetching
IOWAIT_TOTAL	NUMBER		Cumulative value of user I/O wait time (in microseconds)
IOWAIT_DELTA	NUMBER		Delta value of user I/O wait time (in microseconds)
CLWAIT_TOTAL	NUMBER		Cumulative value of cluster wait time (in microseconds)
CLWAIT_DELTA	NUMBER		Delta value of cluster wait time (in microseconds)
APWAIT_TOTAL	NUMBER		Cumulative value of application wait time (in microseconds)
APWAIT_DELTA	NUMBER		Delta value of application wait time (in microseconds)
CCWAIT_TOTAL	NUMBER		Cumulative value of concurrency wait time (in microseconds)
CCWAIT_DELTA	NUMBER		Delta value of concurrency wait time (in microseconds)

Column	Datatype	NULL	Description
DIRECT_WRITES_TOTAL	NUMBER		Cumulative value of direct writes
DIRECT_WRITES_DELTA	NUMBER		Delta value of direct writes
PLSEXEC_TIME_TOTAL	NUMBER		Cumulative value of PL/SQL Execution Time (in microseconds)
PLSEXEC_TIME_DELTA	NUMBER		Delta value of PL/SQL Execution Time (in microseconds)
JAVEXEC_TIME_TOTAL	NUMBER		Cumulative value of Java Execution Time (in microseconds)
JAVEXEC_TIME_DELTA	NUMBER		Delta value of Java Execution Time (in microseconds)
IO_OFFLOAD_ELIG_BYTES_TOTAL	NUMBER		Cumulative value of number of I/O bytes which can be filtered by the Exadata storage system **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_OFFLOAD_ELIG_BYTES_DELTA	NUMBER		Delta value of number of I/O bytes which can be filtered by the Exadata storage system **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_INTERCONNECT_BYTES_TOTAL	NUMBER		Cumulative value of number of I/O bytes exchanged between Oracle Database and the storage system
IO_INTERCONNECT_BYTES_DELTA	NUMBER		Delta value of number of I/O bytes exchanged between Oracle Database and the storage system
PHYSICAL_READ_REQUESTS_TOTAL	NUMBER		Cumulative value of number of physical read I/O requests issued by the monitored SQL
PHYSICAL_READ_REQUESTS_DELTA	NUMBER		Delta value of number of physical read I/O requests issued by the monitored SQL
PHYSICAL_READ_BYTES_TOTAL	NUMBER		Cumulative value of number of bytes read from disks by the monitored SQL
PHYSICAL_READ_BYTES_DELTA	NUMBER		Delta value of number of bytes read from disks by the monitored SQL
PHYSICAL_WRITE_REQUESTS_TOTAL	NUMBER		Cumulative value of number of physical write I/O requests issued by the monitored SQL
PHYSICAL_WRITE_REQUESTS_DELTA	NUMBER		Delta value of number of physical write I/O requests issued by the monitored SQL
PHYSICAL_WRITE_BYTES_TOTAL	NUMBER		Cumulative value of number of bytes written to disks by the monitored SQL
PHYSICAL_WRITE_BYTES_DELTA	NUMBER		Delta value of number of bytes written to disks by the monitored SQL
OPTIMIZED_PHYSICAL_READS_TOTAL	NUMBER		Cumulative value of number of physical reads from the Database Smart Flash Cache or the Exadata Smart Flash Cache by the monitored SQL
OPTIMIZED_PHYSICAL_READS_DELTA	NUMBER		Delta value of number of physical reads from the Database Smart Flash Cache or the Exadata Smart Flash Cache by the monitored SQL

Column	Datatype	NULL	Description
CELL_UNCOMPRESSED_BYTES_TOTAL	NUMBER		Cumulative value of number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells **See Also:** Oracle Exadata Storage Server Software documentation for more information
CELL_UNCOMPRESSED_BYTES_DELTA	NUMBER		Delta value of number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_OFFLOAD_RETURN_BYTES_TOTAL	NUMBER		Cumulative value of number of bytes that are returned by the Exadata cell for smart scan only (that is, not including bytes for other database I/O) **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_OFFLOAD_RETURN_BYTES_DELTA	NUMBER		Delta value of number of bytes that are returned by the Exadata cell for smart scan only (that is, not including bytes for other database I/O) **See Also:** Oracle Exadata Storage Server Software documentation for more information
BIND_DATA	RAW(2000)		Bind data
FLAG	NUMBER		Reserved for internal use
OBSOLETE_COUNT	NUMBER		Number of times that a parent cursor became obsolete
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "DBA_HIST_SNAPSHOT"
- "DBA_HIST_OPTIMIZER_ENV"
- "DBA_HIST_SQLTEXT"
- "DBA_HIST_SQL_PLAN"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLICATION_INFO package

6.68 DBA_HIST_SQLTEXT

DBA_HIST_SQLTEXT displays the text of SQL statements belonging to shared SQL cursors captured in the Workload Repository.

This view captures information from V$SQL and is used with the DBA_HIST_SQLSTAT view.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
SQL_ID	VARCHAR2(13)	NOT NULL	SQL identifier of the parent cursor in the library cache
SQL_TEXT	CLOB		Full text for the SQL statement exposed as a CLOB column
COMMAND_TYPE	NUMBER		Oracle command type definition
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SQL"
- "DBA_HIST_SQLSTAT"

6.69 DBA_HIST_STAT_NAME

DBA_HIST_STAT_NAME displays decoded statistic names for the statistics captured in the Workload Repository.

This includes OLAP statisitics and OLAP timed events. This view captures information from V$STATNAME and is used with DBA_HIST_SYSSTAT and DBA_HIST_SYS_TIME_MODEL.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
STAT_ID	NUMBER	NOT NULL	Statistic identifier
STAT_NAME	VARCHAR2(64)	NOT NULL	Statistic name

Column	Datatype	NULL	Description
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$STATNAME"
- "DBA_HIST_SYSSTAT"
- "DBA_HIST_SYS_TIME_MODEL"

6.70 DBA_HIST_STREAMS_APPLY_SUM

DBA_HIST_STREAMS_APPLY_SUM displays information about each apply process and its activities.

This view contains a snapshot of V$STREAMS_APPLY_COORDINATOR, V$STREAMS_APPLY_READER, and V$STREAMS_APPLY_SERVER. This view is intended for use with Automatic Workload Repository (AWR).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
APPLY_NAME	VARCHAR2(128)	NOT NULL	Name of the apply process
STARTUP_TIME	DATE	NOT NULL	Time that the apply process was last started
READER_TOTAL_MESSAGES_DEQUEUED	NUMBER		Total number of messages dequeued since the apply process was last started
READER_LAG	NUMBER		For captured messages, the delay (in seconds) between the creation of the last message and it being received by the apply process. For user enqueued messages, the delay between the message being enqueued in the local database and being received by the apply process.
COORD_TOTAL_RECEIVED	NUMBER		Total number of transactions received by the coordinator process since the apply process was last started

Column	Datatype	NULL	Description
COORD_TOTAL_APPLIED	NUMBER		Total number of transactions applied by the apply process since the apply process was last started
COORD_TOTAL_ROLLBACKS	NUMBER		Number of transactions which were rolled back due to unexpected contention
COORD_TOTAL_WAIT_DEPS	NUMBER		Number of times since the apply process was last started that an apply server waited to apply a logical change record (LCR) in a transaction until another apply server applied a transaction because of a dependency between the transactions
COORD_TOTAL_WAIT_CMTS	NUMBER		Number of times since the apply process was last started that an apply server waited to commit a transaction until another apply server committed a transaction to serialize commits
COORD_LWM_LAG	NUMBER		For captured messages, the delay (in seconds) between the creation of the message corresponding to the low watermark and it being applied by the apply process. For user enqueued messages, the delay between the message being enqueued in the local database and being applied by the apply process.
SERVER_TOTAL_MESSAGES_APPLIED	NUMBER		Total number of messages applied by all the apply servers since the apply process was last started
SERVER_ELAPSED_DEQUEUE_TIME	NUMBER		Time elapsed (in hundredths of a second) dequeuing messages by all the apply servers since the apply process was last started
SERVER_ELAPSED_APPLY_TIME	NUMBER		Time elapsed (in hundredths of a second) applying messages by all the apply servers since the apply process was last started
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$STREAMS_APPLY_COORDINATOR"
- "V$STREAMS_APPLY_READER"
- "V$STREAMS_APPLY_SERVER"

6.71 DBA_HIST_STREAMS_CAPTURE

DBA_HIST_STREAMS_CAPTURE displays information about each capture process.

This view is intended for use with Automatic Workload Repository (AWR).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
CAPTURE_NAME	VARCHAR2(128)	NOT NULL	Name of the capture process
STARTUP_TIME	DATE	NOT NULL	Time that the capture process was last started
LAG	NUMBER		Delay (in seconds) between the creation and capture of the most recently captured message
TOTAL_MESSAGES_CAPTURED	NUMBER		Total changes captured since the capture process was last started
TOTAL_MESSAGES_ENQUEUED	NUMBER		Total number of messages enqueued since the capture process was last started
ELAPSED_RULE_TIME	NUMBER		Elapsed time (in hundredths of a second) evaluating rules since the capture process was last started
ELAPSED_ENQUEUE_TIME	NUMBER		Elapsed time (in hundredths of a second) enqueuing messages since the capture process was last started
ELAPSED_REDO_WAIT_TIME	NUMBER		Elapsed time (in hundredths of a second) spent by the capture process in the WAITING FOR REDO state
ELAPSED_PAUSE_TIME	NUMBER		Elapsed pause time
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.72 DBA_HIST_STREAMS_POOL_ADVICE

DBA_HIST_STREAMS_POOL_ADVICE displays historical information about the estimated count of spilled or unspilled messages and the associated time spent in the spill or unspill activity for different Streams pool sizes.

This view is intended for use with Automatic Workload Repository (AWR).

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID of the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number of the snapshot
SIZE_FOR_ESTIMATE	NUMBER	NOT NULL	Pool size for the estimate (in megabytes)
SIZE_FACTOR	NUMBER		Size factor with respect to the current pool size
ESTD_SPILL_COUNT	NUMBER		Estimated count of messages spilled from the Streams pool
ESTD_SPILL_TIME	NUMBER		Estimated elapsed time (in seconds) to spill
ESTD_UNSPILL_COUNT	NUMBER		Estimated count of unspills (read back from disk)
ESTD_UNSPILL_TIME	NUMBER		Estimated elapsed time (in seconds) to unspill
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.73 DBA_HIST_SYS_TIME_MODEL

DBA_HIST_SYS_TIME_MODEL displays historical system time model statistics, including OLAP timed stastistics.

This view contains snapshots of V$SYS_TIME_MODEL.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
STAT_ID	NUMBER	NOT NULL	Statistic ID
STAT_NAME	VARCHAR2(64)	NOT NULL	Statistic name
VALUE	NUMBER		Statistic value
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SYS_TIME_MODEL"
- "DBA_HIST_CON_SYS_TIME_MODEL"
- "V$CON_SYSMETRIC"

6.74 DBA_HIST_SYSMETRIC_HISTORY

DBA_HIST_SYSMETRIC_HISTORY externalizes all available history of the system metric values for the entire set of data kept in the database.

This view contains snapshots of V$SYSMETRIC_HISTORY.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
BEGIN_TIME	DATE	NOT NULL	Begin time of the interval
END_TIME	DATE	NOT NULL	End time of the interval
INTSIZE	NUMBER	NOT NULL	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	NOT NULL	Group ID
METRIC_ID	NUMBER	NOT NULL	Metric ID
METRIC_NAME	VARCHAR2(64)	NOT NULL	Metric name
VALUE	NUMBER	NOT NULL	Metric Value
METRIC_UNIT	VARCHAR2(64)	NOT NULL	Unit of measurement
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SYSMETRIC_HISTORY"
- "DBA_HIST_CON_SYSMETRIC_HIST"
- "V$CON_SYSMETRIC_HISTORY"

6.75 DBA_HIST_SYSMETRIC_SUMMARY

DBA_HIST_SYSMETRIC_SUMMARY displays a history of statistical summary of all metric values in the System Metrics Long Duration group.

This view contains snapshots of V$SYSMETRIC_SUMMARY.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
BEGIN_TIME	DATE	NOT NULL	Begin time of the interval
END_TIME	DATE	NOT NULL	End time of the interval
INTSIZE	NUMBER	NOT NULL	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	NOT NULL	Group ID
METRIC_ID	NUMBER	NOT NULL	Metric ID
METRIC_NAME	VARCHAR2(64)	NOT NULL	Metric name
METRIC_UNIT	VARCHAR2(64)	NOT NULL	Unit of measurement
NUM_INTERVAL	NUMBER	NOT NULL	Number of intervals observed
MINVAL	NUMBER	NOT NULL	Minimum value observed
MAXVAL	NUMBER	NOT NULL	Maximum value observed
AVERAGE	NUMBER	NOT NULL	Average over the period
STANDARD_DEVIATION	NUMBER	NOT NULL	One standard deviation
SUM_SQUARES	NUMBER		Sum of the squared deviations from the mean

Column	Datatype	NULL	Description
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SYSMETRIC_SUMMARY"
- "DBA_HIST_CON_SYSMETRIC_SUMM"
- "V$CON_SYSMETRIC_SUMMARY"

6.76 DBA_HIST_SYSSTAT

DBA_HIST_SYSSTAT displays historical system statistics information, including OLAP kernel statistics.

This view contains snapshots of V$SYSSTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
STAT_ID	NUMBER	NOT NULL	Statistic identifier
STAT_NAME	VARCHAR2(64)	NOT NULL	Statistic name
VALUE	NUMBER		Statistic value
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$SYSSTAT"

6.77 DBA_HIST_SYSTEM_EVENT

DBA_HIST_SYSTEM_EVENT displays historical information on total waits for an event.

This view contains snapshots of V$SYSTEM_EVENT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
EVENT_ID	NUMBER	NOT NULL	Identifier of the wait event
EVENT_NAME	VARCHAR2(64)	NOT NULL	Name of the wait event
WAIT_CLASS_ID	NUMBER		Identifier of the Class of the Wait Event
WAIT_CLASS	VARCHAR2(64)		Name of the Class of the Wait Event
TOTAL_WAITS	NUMBER		Total number of waits for the event
TOTAL_TIMEOUTS	NUMBER		Total number of timeouts for the event
TIME_WAITED_MICRO	NUMBER		Total amount of time waited for the event (in microseconds)
TOTAL_WAITS_FG	NUMBER		Total number of waits for the event, from foreground sessions
TOTAL_TIMEOUTS_FG	NUMBER		Total number of timeouts for the event, from foreground sessions
TIME_WAITED_MICRO_FG	NUMBER		Amount of time waited for the event (in microseconds), from foreground sessions
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$SYSTEM_EVENT"

6.78 DBA_HIST_TABLESPACE

DBA_HIST_TABLESPACE displays tablespace information contained in the Workload Repository.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
TS#	NUMBER	NOT NULL	Tablespace number
TSNAME	VARCHAR2(30)	NOT NULL	Tablespace name
CONTENTS	VARCHAR2(30)		Tablespace contents: • UNDO • PERMANENT • TEMPORARY
SEGMENT_SPACE_MANAGEMENT	VARCHAR2(30)		Indicates whether the free and used space in the tablespace is managed using free lists (MANUAL) or bitmaps (AUTO)
EXTENT_MANAGEMENT	VARCHAR2(30)		Indicates whether the extents in the tablespace are dictionary managed (DICTIONARY) or locally managed (LOCAL)
BLOCK_SIZE	NUMBER		Block size of the tablespace
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.79 DBA_HIST_TABLESPACE_STAT

DBA_HIST_TABLESPACE_STAT displays tablespace information from the control file.

This view contains snapshots of V$TABLESPACE and DBA_TABLESPACES.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
TS#	NUMBER	NOT NULL	Tablespace number
TSNAME	VARCHAR2(30)		Tablespace name
CONTENTS	VARCHAR2(9)		Tablespace contents: • PERMANENT • TEMPORARY

Column	Datatype	NULL	Description
STATUS	VARCHAR2(9)		Tablespace status: • ONLINE • OFFLINE • READ ONLY
SEGMENT_SPACE_MANAGEMENT	VARCHAR2(6)		Indicates whether the free and used segment space in the tablespace is managed using free lists (MANUAL) or bitmaps (AUTO)
EXTENT_MANAGEMENT	VARCHAR2(10)		Indicates whether the extents in the tablespace are dictionary managed (DICTIONARY) or locally managed (LOCAL)
IS_BACKUP	VARCHAR2(5)		Indicates whether the tablespace is part of a backup
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$TABLESPACE"
- "DBA_TABLESPACES"

6.80 DBA_HIST_TBSPC_SPACE_USAGE

DBA_HIST_TBSPC_SPACE_USAGE displays historical tablespace usage statistics.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER		Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
TABLESPACE_ID	NUMBER		Tablespace ID
TABLESPACE_SIZE	NUMBER		Tablespace size (in database blocks)
TABLESPACE_MAXSIZE	NUMBER		Maximum size of the tablespace (in database blocks)
TABLESPACE_USEDSIZE	NUMBER		Used size of the tablespace (in database blocks)
RTIME	VARCHAR2(25)		Runtime

Column	Datatype	NULL	Description
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.81 DBA_HIST_TEMPFILE

DBA_HIST_TEMPFILE displays a history of the temp file information from the control file. This view contains snapshots of V$TEMPFILE.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
FILE#	NUMBER	NOT NULL	File identification number
CREATION_CHANGE#	NUMBER	NOT NULL	Change number at which the temp file was created
FILENAME	VARCHAR2(513)	NOT NULL	Name of the temp file
TS#	NUMBER	NOT NULL	Tablespace number
TSNAME	VARCHAR2(30)		Name of the tablespace
BLOCK_SIZE	NUMBER		Block size of the temp file
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$TEMPFILE"

6.82 DBA_HIST_TEMPSTATXS

DBA_HIST_TEMPSTATXS displays information about temporary file read/write statistics.

This view contains snapshots of V$TEMPSTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
FILE#	NUMBER	NOT NULL	File identification number
CREATION_CHANGE#	NUMBER	NOT NULL	Change number at which the temp file was created
FILENAME	VARCHAR2(513)	NOT NULL	Name of the temp file
TS#	NUMBER	NOT NULL	Tablespace number
TSNAME	VARCHAR2(30)		Name of the tablespace
BLOCK_SIZE	NUMBER		Block size of the temp file
PHYRDS	NUMBER		Number of physical reads done
PHYWRTS	NUMBER		Number of times DBWR is required to write
SINGLEBLKRDS	NUMBER		Number of single block reads
READTIM	NUMBER		Time (in hundredths of a second) spent doing reads if the TIMED_STATISTICS parameter is true; 0 if false
WRITETIM	NUMBER		Time (in hundredths of a second) spent doing writes if the TIMED_STATISTICS parameter is true; 0 if false
SINGLEBLKRDTIM	NUMBER		Cumulative single block read time (in hundredths of a second)
PHYBLKRD	NUMBER		Number of physical blocks read
PHYBLKWRT	NUMBER		Number of blocks written to disk, which may be the same as PHYWRTS if all writes are single blocks
WAIT_COUNT	NUMBER		Shows the number of waits at the file level for contended buffers. This value includes the individual wait events that are included in the buffer busy waits wait event. **See Also:** "buffer busy waits"
TIME	NUMBER		Time spent waiting for the wait events in the WAIT_COUNT column
CON_DBID	NUMBER		The database ID of the PDB for the sampled session

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$TEMPSTAT"

6.83 DBA_HIST_THREAD

DBA_HIST_THREAD displays historical thread information from the control file.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
THREAD#	NUMBER	NOT NULL	Thread number
THREAD_INSTANCE_NUMBER	NUMBER		Instance number of the thread
STATUS	VARCHAR2(6)		Thread status (OPEN) or (CLOSED)
OPEN_TIME	DATE		Last time the thread was opened
CURRENT_GROUP#	NUMBER		Current log group
SEQUENCE#	NUMBER		Sequence number of the current log
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.84 DBA_HIST_TOPLEVELCALL_NAME

DBA_HIST_TOPLEVELCALL_NAME displays the mapping between Oracle top level calls and names.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
TOP_LEVEL_CALL#	NUMBER	NOT NULL	Oracle top level call number
TOP_LEVEL_CALL_NAME	VARCHAR2(64)		Oracle top level call name
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.85 DBA_HIST_UNDOSTAT

DBA_HIST_UNDOSTAT displays the history of histograms of statistical data to show how well the system is working.

The available statistics include undo space consumption, transaction concurrency, and length of queries executed in the instance. This view contains snapshots of V$UNDOSTAT.

Column	Datatype	NULL	Description
BEGIN_TIME	DATE	NOT NULL	Identifies the beginning of the time interval
END_TIME	DATE	NOT NULL	Identifies the end of the time interval
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
UNDOTSN	NUMBER	NOT NULL	Represents the last active undo tablespace in the duration of time. The tablespace ID of the active undo tablespace is returned in this column. If more than one undo tablespace was active in that period, the active undo tablespace that was active at the end of the period is reported.
UNDOBLKS	NUMBER		Represents the total number of undo blocks consumed. You can use this column to obtain the consumption rate of undo blocks, and thereby estimate the size of the undo tablespace needed to handle the workload on your system.
TXNCOUNT	NUMBER		Identifies the total number of transactions executed within the period

Column	Datatype	NULL	Description
MAXQUERYLEN	NUMBER		Identifies the length of the longest query (in number of seconds) executed in the instance during the period. You can use this statistic to estimate the proper setting of the UNDO_RETENTION initialization parameter. The length of a query is measured from the cursor open time to the last fetch/execute time of the cursor. Only the length of those cursors that have been fetched/executed during the period are reflected in the view.
MAXQUERYSQLID	VARCHAR2(13)		SQL identifier of the longest running SQL statement in the period
MAXCONCURRENCY	NUMBER		Identifies the highest number of transactions executed concurrently within the period
UNXPSTEALCNT	NUMBER		Number of attempts to obtain undo space by stealing unexpired extents from other transactions
UNXPBLKRELCNT	NUMBER		Number of unexpired blocks removed from certain undo segments so they can be used by other transactions
UNXPBLKREUCNT	NUMBER		Number of unexpired undo blocks reused by transactions
EXPSTEALCNT	NUMBER		Number of attempts to steal expired undo blocks from other undo segments
EXPBLKRELCNT	NUMBER		Number of expired undo blocks stolen from other undo segments
EXPBLKREUCNT	NUMBER		Number of expired undo blocks reused within the same undo segments
SSOLDERRCNT	NUMBER		Identifies the number of times the error ORA-01555 occurred. You can use this statistic to decide whether the UNDO_RETENTION initialization parameter is set properly given the size of the undo tablespace. Increasing the value of UNDO_RETENTION can reduce the occurrence of this error.
NOSPACEERRCNT	NUMBER		Identifies the number of times space was requested in the undo tablespace and there was no free space available. That is, all of the space in the undo tablespace was in use by active transactions. The corrective action is to add more space to the undo tablespace.
ACTIVEBLKS	NUMBER		Total number of blocks in the active extents of the undo tablespace for the instance at the sampled time in the period
UNEXPIREDBLKS	NUMBER		Total number of blocks in the unexpired extents of the undo tablespace for the instance at the sampled time in the period
EXPIREDBLKS	NUMBER		Total number of blocks in the expired extents of the undo tablespace for the instance at the sampled time in the period

Column	Datatype	NULL	Description
TUNED_UNDORETENTION	NUMBER		System tuned value indicating the period for which undo is being retained The value of this column is not meaningful on an Oracle Active Data Guard standby database instance, because the system does not tune this value on such instances.
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$UNDOSTAT"

6.86 DBA_HIST_WAITCLASSMET_HISTORY

DBA_HIST_WAITCLASSMET_HISTORY displays the history of the wait event class metric data kept by the Workload Repository.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID of the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number of the snapshot
WAIT_CLASS_ID	NUMBER	NOT NULL	Identifier of the class of the wait event
WAIT_CLASS	VARCHAR2(64)		Name of the class of the wait event
BEGIN_TIME	DATE	NOT NULL	Begin time of the interval
END_TIME	DATE	NOT NULL	End time of the interval
INTSIZE	NUMBER	NOT NULL	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	NOT NULL	Metric group ID
AVERAGE_WAITER_COUNT	NUMBER	NOT NULL	Average waiter count
DBTIME_IN_WAIT	NUMBER	NOT NULL	Percent of database time spent in the wait
TIME_WAITED	NUMBER	NOT NULL	Time waited during the interval (in microseconds)
WAIT_COUNT	NUMBER	NOT NULL	Number of times waited
TIME_WAITED_FG	NUMBER		Time waited (in hundredths of a second), from foreground sessions

Column	Datatype	NULL	Description
WAIT_COUNT_FG	NUMBER		Number of times waited, from foreground sessions
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.87 DBA_HIST_WAITSTAT

DBA_HIST_WAITSTAT displays historical block contention statistics. This view contains snapshots of V$WAITSTAT.

Column	Datatype	NULL	Description
SNAP_ID	NUMBER	NOT NULL	Unique snapshot ID
DBID	NUMBER	NOT NULL	Database ID for the snapshot
INSTANCE_NUMBER	NUMBER	NOT NULL	Instance number for the snapshot
CLASS	VARCHAR2(18)	NOT NULL	Class of the block
WAIT_COUNT	NUMBER		Number of waits by the OPERATION for this CLASS of block
TIME	NUMBER		Sum of all wait times for all the waits by the OPERATION for this CLASS of block
CON_DBID	NUMBER		The database ID of the PDB for the sampled session
CON_ID	NUMBER		The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$WAITSTAT"

6.88 DBA_HIST_WR_CONTROL

DBA_HIST_WR_CONTROL displays the control information for the Workload Repository.

Column	Datatype	NULL	Description
DBID	NUMBER	NOT NULL	Database ID
SNAP_INTERVAL	INTERVAL DAY(5) TO SECOND(1)	NOT NULL	Snapshot interval; how often to automatically take snapshots
RETENTION	INTERVAL DAY(5) TO SECOND(1)	NOT NULL	Retention setting for the snapshots; amount of time to keep the snapshots
TOPNSQL	VARCHAR2(10)		The number of Top SQL flushed for each SQL criteria (elapsed time, CPU time, parse calls, sharable memory, version count)
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
SRC_DBID	NUMBER		Database ID of the non-CDB, CDB, or PDB where the AWR snapshot data was collected
SRC_DBNAME	VARCHAR2(128)		Database name of the non-CDB, CDB, or PDB where the AWR snapshot data was collected
TABLESPACE_NAME	VARCHAR2(128)		Name of the tablespace in which AWR snapshot data resides

6.89 DBA_HIST_WR_SETTINGS

DBA_HIST_WR_SETTINGS displays the settings and metadata for the Workload Repository.

Column	Datatype	NULL	Description
LOCAL_AWRDBID	NUMBER	NOT NULL	Database ID of the local database
VIEW_LOCATION	VARCHAR2(8)		Data source of the DBA_HIST dictionary views. Possible values include: • AWR_PDB: Views display AWR data stored in the PDB. • AWR_ROOT: Views display AWR data stored in the root.

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.90 DBA_HISTOGRAMS

DBA_HISTOGRAMS is a synonym for DBA_TAB_HISTOGRAMS.

> **See Also:**
>
> "DBA_TAB_HISTOGRAMS"

6.91 DBA_HIVE_COLUMNS

DBA_HIVE_COLUMNS describes all Hive columns in a Hive metastore. Its columns are the same as those in ALL_HIVE_COLUMNS.

> **See Also:**
>
> "ALL_HIVE_COLUMNS"

6.92 DBA_HIVE_DATABASES

DBA_HIVE_DATABASES describes all the Hive schemas in a Hadoop cluster. Its columns are the same as those in ALL_HIVE_DATABASES.

> **See Also:**
>
> "ALL_HIVE_DATABASES"

6.93 DBA_HIVE_PART_KEY_COLUMNS

DBA_HIVE_PART_KEY_COLUMNS provides information about all Hive table partition columns in the database. Its columns are the same as those in ALL_HIVE_PART_KEY_COLUMNS.

> **See Also:**
>
> "ALL_HIVE_PART_KEY_COLUMNS"

6.94 DBA_HIVE_TAB_PARTITIONS

DBA_HIVE_TAB_PARTITIONS provides information about all Hive table partitions in the database. Its columns are the same as those in ALL_HIVE_TAB_PARTITIONS.

> **See Also:**
>
> "ALL_HIVE_TAB_PARTITIONS"

6.95 DBA_HIVE_TABLES

DBA_HIVE_TABLES provides information about all the Hive tables in the Hive metastore. Its columns are the same as those in ALL_HIVE_TABLES.

> **See Also:**
>
> "ALL_HIVE_TABLES"

6.96 DBA_HOST_ACES

DBA_HOST_ACES describes access control entries defined in host access control lists.

Related View

USER_HOST_ACES describes the status of access control entries for the current user to access network hosts through PL/SQL network utility packages. This view does not display the ACE_ORDER, START_DATE, END_DATE, GRANT_TYPE, INVERTED_PRINCIPAL, PRINCIPAL, or PRINCIPAL_TYPE columns.

Column	Datatype	NULL	Description
HOST	VARCHAR2(1000)	NOT NULL	Network host

Column	Datatype	NULL	Description
LOWER_PORT	NUMBER(5)		Lower bound of the port range
UPPER_PORT	NUMBER(5)		Upper bound of the port range
ACE_ORDER	NUMBER	NOT NULL	Order number of the access control entry
START_DATE	TIMESTAMP(6)		Start date of the access control entry
END_DATE	TIMESTAMP(6)		End date of the access control entry
GRANT_TYPE	VARCHAR2(5)		Indicates whether the access control entry grants or denies the privilege
INVERTED_PRINCIPAL	VARCHAR2(3)		Indicates whether the principal is inverted or not
PRINCIPAL	VARCHAR2(128)		Principal the privilege is applied to
PRINCIPAL_TYPE	VARCHAR2(16)		Type of the principal
PRIVILEGE	VARCHAR2(128)		Privilege

See Also:

"USER_HOST_ACES"

6.97 DBA_HOST_ACLS

DBA_HOST_ACLS describes access control lists assigned to restrict access to network hosts through PL/SQL network utility packages.

Column	Datatype	NULL	Description
HOST	VARCHAR2(1000)	NOT NULL	Network host
LOWER_PORT	NUMBER(5)		Lower bound of the port range
UPPER_PORT	NUMBER(5)		Upper bound of the port range
ACL	VARCHAR2(4000)		The name of the access control list
ACLID	RAW(8)		The object ID of the access control list
ACL_OWNER	VARCHAR2(128)		The owner of the access control list

6.98 DBA_IDENTIFIERS

DBA_IDENTIFIERS displays information about the identifiers in all stored objects in the database. Its columns are the same as those in ALL_IDENTIFIERS.

See Also:

"ALL_IDENTIFIERS"

6.99 DBA_ILMDATAMOVEMENTPOLICIES

DBA_ILMDATAMOVEMENTPOLICIES contains information specific to data movement-related attributes of an Automatic Data Optimization policy in a database.

Related View

USER_ILMDATAMOVEMENTPOLICIES contains information specific to data movement-related attributes of an Automatic Data Optimization policy for a user.

> **Note:**
>
> Automatic Data Optimization is supported in Oracle Database 12*c* Release 2 multitenant environments.

Column	Datatype	NULL	Description
POLICY_NAME	VARCHAR2(128)	NOT NULL	The Automatic Data Optimization policy name is autogenerated
ACTION_TYPE	VARCHAR2(11)		Type of data movement action performed by the Automatic Data Optimization policy: • ANNOTATE • COMPRESSION • EVICT • STORAGE
SCOPE	VARCHAR2(7)		Identifies the scope of the Automatic Data Optimization policy: • ROW • GROUP • SEGMENT
COMPRESSION_LEVEL	VARCHAR2(30)		Compression level to move selected rows or the entire segment to, for a compression Automatic Data Optimization policy
TIER_TABLESPACE	VARCHAR2(128)		Tablespace to move the object to, for a storage Automatic Data Optimization policy
TIER_STATUS	VARCHAR2(9)		This column is only valid for storage tiering policies, and indicates whether the storage tiering policy was specified with a READ ONLY clause. This column takes READ ONLY as a potential value. In all other cases, it is blank. In other words, this column indicates whether the tablespace the object is being moved to will be made READ ONLY after the movement.
CONDITION_TYPE	VARCHAR2(22)		Column on which the condition for the policy is based. Possible values: • LAST ACCESS TIME • LAST MODIFICATION TIME • CREATION TIME • USER DEFINED • LOW ACCESS

Column	Datatype	NULL	Description
CONDITION_DAYS	NUMBER		Number of days in the condition for the policy
CUSTOM_FUNCTION	VARCHAR2(128)		Optional function that evaluates the precondition on the policy
POLICY_SUBTYPE	VARCHAR2(10)		Storage tier on which the policy is specified
ACTION_CLAUSE	CLOB		Text of the action executed by the policy
TIER_TO	VARCHAR2(10)		Storage tier where the data is placed after the policy is executed

See Also:

"USER_ILMDATAMOVEMENTPOLICIES"

6.100 DBA_ILMEVALUATIONDETAILS

DBA_ILMEVALUATIONDETAILS displays details on evaluation of Automatic Data Optimization policies considered for Automatic Data Optimization tasks.

It also shows the job name that executes the policy, in case the policy was selected for execution. If the policy was not selected for execution, this view provides a reason.

Related View

USER_ILMEVALUATIONDETAILS displays details on evaluation of Automatic Data Optimization policies considered for Automatic Data Optimization tasks for a user. It also shows the job name that executes the policy, in case the policy was selected for execution. If the policy was not selected for execution, this view provides a reason.

Note:

Automatic Data Optimization is supported in Oracle Database 12*c* Release 2 multitenant environments.

Column	Datatype	NULL	Description
TASK_ID	NUMBER		Number that uniquely identifies a specific Automatic Data Optimization task
POLICY_NAME	VARCHAR2(128)	NOT NULL	Name of the Automatic Data Optimization policy
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the object associated with the Automatic Data Optimization policy
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object associated with the Automatic Data Optimization policy
SUBOBJECT_NAME	VARCHAR2(128)		Name of the subobject associated with the Automatic Data Optimization policy

Column	Datatype	NULL	Description
OBJECT_TYPE	VARCHAR2(18)		Object type. Valid values include TABLE, TABLE PARTITION, and TABLE SUBPARTITION.
SELECTED_FOR_EXECUTION	VARCHAR2(42)		Indicates whether the policy has been selected for execution on the object. If not, the reason for not being selected is listed. Possible values: • POLICY DISABLED • SELECTED FOR EXECUTION • POLICY OVERRULED • INHERITED POLICY OVERRULED • PRECONDITION NOT SATISFIED • JOB ALREADY EXISTS • NO OPERATION SINCE LAST ILM ACTION • TABLE HAS MATERIALIZED VIEW • TARGET COMPRESSION NOT HIGHER THAN CURRENT • STATISTICS NOT AVAILABLE The value SELECTED FOR EXECUTION means a job was created for this policy on the object. The other values state the reason why the policy on the object was selected for execution.
JOB_NAME	VARCHAR2(128)		Name of the job in the case where the policy is selected for execution on this object
COMMENTS	VARCHAR2(4000)		Reserved for future use

See Also:

"USER_ILMEVALUATIONDETAILS"

6.101 DBA_ILMOBJECTS

DBA_ILMOBJECTS displays all the Automatic Data Optimization policies and objects in the database.

Many objects inherit policies via their parent objects or because they were created in a particular tablespace. This view provides a mapping between the policies and objects and indicates whether a policy is inherited by an object or is directly specified on it.

Related View

USER_ILMOBJECTS displays all the Automatic Data Optimization policies and objects for a user.

Note:

Automatic Data Optimization is supported in Oracle Database 12*c* Release 2 multitenant environments.

Column	Datatype	NULL	Description
POLICY_NAME	VARCHAR2(128)	NOT NULL	Policy name is auto-generated
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the object associated with the Automatic Data Optimization policy
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object associated with the Automatic Data Optimization policy
SUBOBJECT_NAME	VARCHAR2(128)		Name of the subobject associated with the Automatic Data Optimization policy
OBJECT_TYPE	VARCHAR2(18)		Object type. Valid values include: • INDEX • INDEX PARTITION • LOB • LOB PARTITION • TABLE • TABLE PARTITION • TABLE SUBPARTITION Direct policies on Index, Index Partition, LOB, and LOB Partition are not supported in Oracle Database 12*c*.
INHERITED_FROM	VARCHAR2(20)		Indicates if the policy is inherited by the object or subobject, or directly specified on the object or subobject. If the policy is inherited, the level from which the policy is inherited (TABLE, TABLE PARTITION, TABLESPACE) is identified.
TBS_INHERITED_FROM	VARCHAR2(30)		The tablespace name, if the policy is inherited from a tablespace
ENABLED	VARCHAR2(7)		Indicates if the Automatic Data Optimization policy is enabled for the object (YES or NO)
DELETED	VARCHAR2(7)		Possible values: • YES - Indicates that the policy is deleted for any objects that may be added in the future, but is active for those objects that are currently associated with that policy • NO - Indicates that the policy is active

See Also:

"USER_ILMOBJECTS"

6.102 DBA_ILMPARAMETERS

DBA_ILMPARAMETERS can be queried to provide information on the Automatic Data Optimization parameters in the database and their values.

> **Note:**
>
> Automatic Data Optimization is supported in Oracle Database 12*c* Release 2 multitenant environments.

Column	Datatype	NULL	Description
NAME	VARCHAR2(128)		Name of the Automatic Data Optimization environment parameter. The value is one of the constants defined in the DBMS_ILM_ADMIN package.
VALUE	NUMBER		Value of the parameter

> **See Also:**
>
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the API interface for implementing Automatic Data Optimization strategies
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_ILM_ADMIN package

6.103 DBA_ILMPOLICIES

DBA_ILMPOLICIES displays details about Automatic Data Optimization policies in the database.

The view contains common details relevant to all types of Automatic Data Optimization policies, not just details relevant to the data movement-related Automatic Data Optimization policies.

Related View

USER_ILMPOLICIES displays details about Automatic Data Optimization policies owned by the user.

> **Note:**
>
> Automatic Data Optimization is supported in Oracle Database 12*c* Release 2 multitenant environments.

Column	Datatype	NULL	Description
POLICY_NAME	VARCHAR2(128)		The name of the Automatic Data Optimization policy is auto-generated
POLICY_TYPE	VARCHAR2(13)		Type of the policy. Valid values include DATAMOVEMENT.
TABLESPACE	VARCHAR2(30)		Tablespace name, in the case of a tablespace-level policy
ENABLED	VARCHAR2(6)		Indicates whether the policy is enabled or not
DELETED	VARCHAR2(7)		Possible values: • YES - Indicates that the policy associated has been deleted (but shall remain active for this object) • NO - Indicates that the policy is active

Note:

Automatic Data Optimization policies cannot be set on tables with object types or materialized views.

See Also:

"USER_ILMPOLICIES"

6.104 DBA_ILMRESULTS

DBA_ILMRESULTS displays information on data movement-related Automatic Data Optimization jobs in the database.

Related View

USER_ILMRESULTS displays information on data movement-related Automatic Data Optimization jobs for tasks created by the user.

Note:

Automatic Data Optimization is supported in Oracle Database 12*c* Release 2 multitenant environments.

Column	Datatype	NULL	Description
TASK_ID	NUMBER		Number that uniquely identifies a specific Automatic Data Optimization task
JOB_NAME	VARCHAR2(128)		Name of the Automatic Data Optimization job

Column	Datatype	NULL	Description
JOB_STATE	VARCHAR2(35)		State of the job. Possible values: • JOB CREATED • COMPLETED SUCCESSFULLY • FAILED • STOPPED • JOB CREATION FAILED • DEPENDENT OBJECTS BEING REBUILT • FAILED TO REBUILD DEPENDENT OBJECTS
START_TIME	TIMESTAMP(6)		Start time of the Automatic Data Optimization job
COMPLETION_TIME	TIMESTAMP(6)		Completion time of the Automatic Data Optimization job
COMMENTS	VARCHAR2(4000)		Additional information in cases where the Automatic Data Optimization job execution fails
STATISTICS	CLOB		Job specific statistics, such as space saved via compression. This column is in the form of comma separated name / value pairs, with each pair representing a particular statistic name and value.

> **See Also:**
>
> "USER_ILMRESULTS"

6.105 DBA_ILMTASKS

DBA_ILMTASKS displays information on Automatic Data Optimization execution.

Related View

USER_ILMTASKS displays information on Automatic Data Optimization tasks created by a user.

> **Note:**
>
> Automatic Data Optimization is supported in Oracle Database 12*c* Release 2 multitenant environments.

Column	Datatype	NULL	Description
TASK_ID	NUMBER		Number that uniquely identifies a specific Automatic Data Optimization task
TASK_OWNER	VARCHAR2(128)	NOT NULL	User who initiates the task

Column	Datatype	NULL	Description
STATE	VARCHAR2(9)		Possible values: • INACTIVE: Indicates that the task was created for previewing • ACTIVE: Indicates that jobs have been created for the qualifying policies in the task • COMPLETE: Indicates that the task has completed
CREATION_TIME	TIMESTAMP(6)		The time that the task was created
START_TIME	TIMESTAMP(6)		Start time of a specific task
COMPLETION_TIME	TIMESTAMP(6)		Completion time of a specific task

See Also:

"USER_ILMTASKS"

6.106 DBA_IM_EXPRESSIONS

DBA_IM_EXPRESSIONS provides information about the list of expressions (SYS_IME virtual columns) that are currently enabled for in-memory storage.

Typically, you can query this view after invoking the DBMS_INMEMORY_ADMIN.IME_CAPTURE_EXPRESSIONS PL/SQL procedure to see the list of hot expressions added to different tables across the database.

Based on this view, you can:

- Populate expressions on a particular table immediately
- Drop certain expressions that are marked for in-memory but not desired by users

Related View

USER_IM_EXPRESSIONS provides information about the list of expressions (SYS_IME virtual columns) that are currently enabled for in-memory storage in schemas owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(129)		Table owner
TABLE_NAME	VARCHAR2(129)		Table name
OBJECT_NUMBER	NUMBER		Object number of the table
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Column name of the expression added to the table (with SYS_IME prefix)
SQL_EXPRESSION	LONG		SQL representation of the expression

> **See Also:**
>
> "USER_IM_EXPRESSIONS"

6.107 DBA_IMMUTABLE_ROW_VERSION_COLS

`DBA_IMMUTABLE_ROW_VERSION_COLS` displays information about row versioned columns in all immutable tables in the database. Its columns are the same as those in `ALL_IMMUTABLE_ROW_VERSION_COLS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_IMMUTABLE_ROW_VERSION_COLS"

6.108 DBA_IMMUTABLE_ROW_VERSION_HISTORY

`DBA_IMMUTABLE_ROW_VERSION_HISTORY` provides a history of row versions in all immutable tables in the database. Its columns are the same as those in `ALL_IMMUTABLE_ROW_VERSION_HISTORY`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_IMMUTABLE_ROW_VERSION_HISTORY"

6.109 DBA_IMMUTABLE_TABLE_COLUMNS

`DBA_IMMUTABLE_TABLE_COLUMNS` displays information about columns valid in each epoch in all immutable tables in the database. Its columns are the same as those in `ALL_IMMUTABLE_TABLE_COLUMNS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_IMMUTABLE_TABLE_COLUMNS"

6.110 DBA_IMMUTABLE_TABLE_EPOCHS

`DBA_IMMUTABLE_TABLE_EPOCHS` displays epoch information for all immutable tables in the database. Its columns are the same as those in `ALL_IMMUTABLE_TABLE_EPOCHS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_IMMUTABLE_TABLE_EPOCHS"

6.111 DBA_IMMUTABLE_TABLES

`DBA_IMMUTABLE_TABLES` describes all immutable tables in the database. Its columns are the same as those in `ALL_IMMUTABLE_TABLES`.

> **See Also:**
>
> "ALL_IMMUTABLE_TABLES"

6.112 DBA_INCOMPLETE_SAGAS

DBA_INCOMPLETE_SAGAS describes all incomplete sagas in the database. Its columns are the same as those in ALL_INCOMPLETE_SAGAS.

This view displays sagas that were either initiated in the current PDB or joined by participants in the current PDB.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_INCOMPLETE_SAGAS"

6.113 DBA_IND_COLUMNS

DBA_IND_COLUMNS describes the columns of all the indexes on all tables and clusters in the database. Its columns are the same as those in ALL_IND_COLUMNS.

> **See Also:**
>
> "ALL_IND_COLUMNS"

6.114 DBA_IND_EXPRESSIONS

DBA_IND_EXPRESSIONS lists expressions of function-based indexes on all tables and clusters in the database. Its columns are the same as those in ALL_IND_EXPRESSIONS.

> **See Also:**
>
> "ALL_IND_EXPRESSIONS"

6.115 DBA_IND_PARTITIONS

DBA_IND_PARTITIONS displays, for each index partition in the database, the partition-level partitioning information, the storage parameters for the partition, and various

partition statistics generated by the DBMS_STATS package. Its columns are the same as those in ALL_IND_PARTITIONS.

> **See Also:**
>
> "ALL_IND_PARTITIONS"

6.116 DBA_IND_PENDING_STATS

DBA_IND_PENDING_STATS describes pending statistics for all tables, partitions, and subpartitions in the database collected using the DBMS_STATS package. Its columns are the same as those in ALL_IND_PENDING_STATS.

> **See Also:**
>
> "ALL_IND_PENDING_STATS"

6.117 DBA_IND_STATISTICS

DBA_IND_STATISTICS displays optimizer statistics for all indexes in the database collected using the DBMS_STATS package. Its columns are the same as those in ALL_IND_STATISTICS.

> **See Also:**
>
> "ALL_IND_STATISTICS"

6.118 DBA_IND_SUBPARTITIONS

DBA_IND_SUBPARTITIONS displays, for each index subpartition in the database, the subpartition-level partitioning information, the storage parameters for the subpartition, and various subpartition statistics generated by the DBMS_STATS package. Its columns are the same as those in ALL_IND_SUBPARTITIONS.

> **See Also:**
>
> "ALL_IND_SUBPARTITIONS"

6.119 DBA_INDEX_USAGE

DBA_INDEX_USAGE displays cumulative statistics for each index.

Column	Datatype	NULL	Description
OBJECT_ID	NUMBER	NOT NULL	Object ID for the index
NAME	VARCHAR2(128)	NOT NULL	Index name
OWNER	VARCHAR2(128)	NOT NULL	Index owner
TOTAL_ACCESS_COUNT	NUMBER		Total number of times the index has been accessed
TOTAL_EXEC_COUNT	NUMBER		Total executions the index has participated in
TOTAL_ROWS_RETURNED	NUMBER		Total rows returned by the index.
			Index usage is categorized into buckets of different ranges. Each bucket has a range of values for access count and rows returned. An entry is placed into a bucket if the rows returned or access counts falls within the range of that bucket.
BUCKET_0_ACCESS_COUNT	NUMBER		The index has not been accessed
BUCKET_1_ACCESS_COUNT	NUMBER		The index has been accessed once
BUCKET_2_10_ACCESS_COUNT	NUMBER		The index has been accessed between 2 and 10 times
BUCKET_2_10_ROWS_RETURNED	NUMBER		The index has returned between 2 and 10 rows
BUCKET_11_100_ACCESS_COUNT	NUMBER		The index has been accessed between 11 and 100 times
BUCKET_11_100_ROWS_RETURNED	NUMBER		The index has returned between 11 and 100 rows
BUCKET_101_1000_ACCESS_COUNT	NUMBER		The index has been accessed between 101 and 1000 times
BUCKET_101_1000_ROWS_RETURNED	NUMBER		The index has returned between 101 and 1000 rows
BUCKET_1000_PLUS_ACCESS_COUNT	NUMBER		The index has been accessed more than 1000 times
BUCKET_1000_PLUS_ROWS_RETURNED	NUMBER		The index has returned more than 1000 rows
LAST_USED	DATE		Time that the index was last used

See Also:

"V$INDEX_USAGE_INFO"

6.120 DBA_INDEXES

DBA_INDEXES describes all indexes in the database. To gather statistics for this view, use the DBMS_STATS package. This view supports parallel partitioned index scans. Its columns are the same as those in ALL_INDEXES.

> **See Also:**
>
> "ALL_INDEXES"

6.121 DBA_INDEXTYPE_ARRAYTYPES

DBA_INDEXTYPE_ARRAYTYPES displays information about the array types specified by all indextypes in the database. Its columns are the same as those in ALL_INDEXTYPE_ARRAYTYPES.

> **See Also:**
>
> "ALL_INDEXTYPE_ARRAYTYPES"

6.122 DBA_INDEXTYPE_COMMENTS

DBA_INDEXTYPE_COMMENTS displays comments for all user-defined indextypes in the database. Its columns are the same as those in ALL_INDEXTYPE_COMMENTS.

> **See Also:**
>
> "ALL_INDEXTYPE_COMMENTS"

6.123 DBA_INDEXTYPE_OPERATORS

DBA_INDEXTYPE_OPERATORS lists all the operators supported by indextypes in the database. Its columns are the same as those in ALL_INDEXTYPE_OPERATORS.

> **See Also:**
>
> "ALL_INDEXTYPE_OPERATORS"

6.124 DBA_INDEXTYPES

DBA_INDEXTYPES describes all indextypes in the database. Its columns are the same as those in ALL_INDEXTYPES.

> **See Also:**
>
> "ALL_INDEXTYPES"

6.125 DBA_INMEMORY_ADVISOR_RECOMMENDATION

DBA_INMEMORY_ADVISOR_RECOMMENDATION displays In-Memory Advisor recommendations.

In-Memory Advisor simulates various Oracle Database In-Memory sizes and estimates the database time for a reference workload for each size. The results are displayed in this view.

Column	Datatype	NULL	Description
TASK_ID	NUMBER		In-Memory Advisor task ID
INMEMORY_SIZE	NUMBER		Simulated In-Memory size (in bytes)
ESTIMATED_DB_TIME_LOW	NUMBER		Low end of the predicted database time range (in seconds)
ESTIMATED_DB_TIME_HIGH	NUMBER		High end of the predicted database time range (in seconds)
ESTIMATED_DB_TIME_ANALYTICS_LOW	NUMBER		Low end of the predicted database analytical time range (in seconds)
ESTIMATED_DB_TIME_ANALYTICS_HIGH	NUMBER		High end of the predicted database analytical time range (in seconds)
RECOMMENDED_OBJ_LIST	CLOB		List of recommended objects for the simulated In-Memory size (INMEMORY_SIZE)

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

6.126 DBA_INMEMORY_AIMTASKDETAILS

DBA_INMEMORY_AIMTASKDETAILS displays details for an Automatic In-Memory management task.

Column	Datatype	NULL	Description
TASK_ID	NUMBER		Number that uniquely identifies a specific automatic IM column store management task
OBJECT_OWNER	VARCHAR2(128)		Owner of the object subject to automatic IM column store management task action
OBJECT_NAME	VARCHAR2(128)		Name of the object subject to automatic IM column store management task action
SUBOBJECT_NAME	VARCHAR2(128)		Name of the subobject subject to automatic IM column store management task action
ACTION	VARCHAR2(16)		Action taken on the object
STATE	VARCHAR2(10)		Status of the action on the object

See Also:

Oracle Database In-Memory Guide for more information about configuring the Automatic In-Memory feature

6.127 DBA_INMEMORY_AIMTASKS

DBA_INMEMORY_AIMTASKS displays information about Automatic In-Memory management tasks.

Column	Datatype	NULL	Description
TASK_ID	NUMBER		Number that uniquely identifies a specific automatic IM column store management task
CREATION_TIME	TIMESTAMP(6)		Creation time of the task
STATE	VARCHAR2(7)		State of the task

See Also:

Oracle Database In-Memory Guide for more information about configuring the Automatic In-Memory feature

6.128 DBA_INTERNAL_TRIGGERS

DBA_INTERNAL_TRIGGERS describes internal triggers on all tables in the database. Its columns are the same as those in ALL_INTERNAL_TRIGGERS.

> **See Also:**
>
> "ALL_INTERNAL_TRIGGERS"

6.129 DBA_INVALID_OBJECTS

DBA_INVALID_OBJECTS describes all invalid objects in the database. You can use this view to identify invalid objects before and after a database upgrade.

This view eliminates old versions of object types. It only includes the object type it if is the latest version.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the object
OBJECT_NAME	VARCHAR2(128)		Name of the object
SUBOBJECT_NAME	VARCHAR2(128)		Name of the subobject (for example, partition)
OBJECT_ID	NUMBER		Dictionary object number of the object.
DATA_OBJECT_ID	NUMBER		Dictionary object number of the segment that contains the object. **Note:** OBJECT_ID and DATA_OBJECT_ID display data dictionary metadata. Do not confuse these numbers with the unique 16-byte object identifier (*object ID*) that Oracle Database assigns to row objects in object tables in the system.
OBJECT_TYPE	VARCHAR2(23)		Type of the object (such as TABLE, INDEX). The current version of the type is shown only if it is invalid. In other words, if prior versions of the type are invalid but the most recent version of the type is valid, it will not be in this list.
CREATED	DATE		Timestamp for the creation of the object
LAST_DDL_TIME	DATE		Timestamp for the last modification of the object and dependent objects resulting from a DDL statement (including grants and revokes)
TIMESTAMP	VARCHAR2(19)		Timestamp for the specification of the object (character data)
STATUS	VARCHAR2(7)		Status of the object: • VALID • INVALID • N/A

Column	Datatype	NULL	Description
TEMPORARY	VARCHAR2(1)		Indicates whether the object is temporary (the current session can see only data that it placed in this object itself) (Y) or not (N)
GENERATED	VARCHAR2(1)		Indicates whether the name of this object was system-generated (Y) or not (N)
SECONDARY	VARCHAR2(1)		Indicates whether this is a secondary object created by the ODCIIndexCreate method of the Oracle Data Cartridge (Y) or not (N)
NAMESPACE	NUMBER		Namespace for the object
EDITION_NAME	VARCHAR2(128)		Name of the edition in which the object is actual
SHARING	VARCHAR2(18)		Values: • DATA LINK - If the object is data-linked or a data link to an object in the root • METADATA LINK - If the object is metadata-linked or a metadata link to an object in the root • EXTENDED DATA LINK - If the object is extended-data-linked or an extended data link to an object in the root • NONE - If none of the above applies
EDITIONABLE	VARCHAR2(1)		Values: • Y - For objects marked EDITIONABLE • N - For objects marked NONEDITIONABLE • NULL - For objects whose type is not editionable in the database
ORACLE_MAINTAINED	VARCHAR2(1)		Denotes whether the object was created, and is maintained, by Oracle-supplied scripts (such as catalog.sql or catproc.sql). An object for which this column has the value Y must not be changed in any way except by running an Oracle-supplied script.
APPLICATION	VARCHAR2(1)		Indicates whether the object is an Application common object (Y) or not (N)
DEFAULT_COLLATION	VARCHAR2(100)		Default collation for the object
DUPLICATED	VARCHAR2(1)		Indicates whether this object is duplicated on this shard (Y) or not (N)
SHARDED	VARCHAR2(1)		Indicates whether this object is sharded (Y) or not (N)
IMPORTED_OBJECT	VARCHAR2(1)		Indicates whether this object is imported (Y) or not (N)
SYNCHRONOUS_DUPLICATED	VARCHAR2(1)		Indicates whether this object is a synchronous duplicated table (Y) or not (N)
CREATED_APPID	NUMBER		ID of the Application that created the object
CREATED_VSNID	NUMBER		ID of the Application Version that created the object
MODIFIED_APPID	NUMBER		ID of the Application that last modified the object
MODIFIED_VSNID	NUMBER		ID of the Application Version that last modified the object

6.130 DBA_JAVA_ARGUMENTS

DBA_JAVA_ARGUMENTS displays argument information about all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_ARGUMENTS.

> **See Also:**
>
> "ALL_JAVA_ARGUMENTS"

6.131 DBA_JAVA_CLASSES

DBA_JAVA_CLASSES displays class level information about all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_CLASSES.

> **See Also:**
>
> "ALL_JAVA_CLASSES"

6.132 DBA_JAVA_COMPILER_OPTIONS

DBA_JAVA_COMPILER_OPTIONS displays information about all native compiler options in the database. Its columns are the same as those in ALL_JAVA_COMPILER_OPTIONS.

> **See Also:**
>
> "ALL_JAVA_COMPILER_OPTIONS"

6.133 DBA_JAVA_DERIVATIONS

DBA_JAVA_DERIVATIONS displays mapping information about Java source objects and their derived Java class objects and Java resource objects for all Java classes in the database. Its columns are the same as those in ALL_JAVA_DERIVATIONS.

> **See Also:**
>
> "ALL_JAVA_DERIVATIONS"

6.134 DBA_JAVA_FIELDS

DBA_JAVA_FIELDS displays field information about all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_FIELDS.

> **See Also:**
>
> "ALL_JAVA_FIELDS"

6.135 DBA_JAVA_IMPLEMENTS

DBA_JAVA_IMPLEMENTS describes interfaces implemented by all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_IMPLEMENTS.

> **See Also:**
>
> "ALL_JAVA_IMPLEMENTS"

6.136 DBA_JAVA_INNERS

DBA_JAVA_INNERS displays information about inner classes referred to by all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_INNERS.

> **See Also:**
>
> "ALL_JAVA_INNERS"

6.137 DBA_JAVA_LAYOUTS

DBA_JAVA_LAYOUTS displays class layout information about all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_LAYOUTS.

> **See Also:**
>
> "ALL_JAVA_LAYOUTS"

6.138 DBA_JAVA_METHODS

DBA_JAVA_METHODS displays method information about all stored Java classes in the database. Its columns are the same as those in ALL_JAVA_METHODS.

> **See Also:**
>
> "ALL_JAVA_METHODS"

6.139 DBA_JAVA_NCOMPS

DBA_JAVA_NCOMPS displays ncomp-related information about all Java classes in the database. Its columns are the same as those in ALL_JAVA_NCOMPS.

> **See Also:**
>
> "ALL_JAVA_NCOMPS"

6.140 DBA_JAVA_POLICY

DBA_JAVA_POLICY describes Java security permissions for all users in the database.

Related View

USER_JAVA_POLICY describes Java security permissions for the current user.

Column	Datatype	NULL	Description
KIND	VARCHAR2(8)		Indicates whether the permission is a positive (GRANT) or a limitation (RESTRICT)
GRANTEE	VARCHAR2(128)	NOT NULL	Name of the user, schema, or role to which the permission object is assigned
TYPE_SCHEMA	VARCHAR2(128)	NOT NULL	Schema in which the permission object is loaded
TYPE_NAME	VARCHAR2(4000)		Permission class type, which is designated by a string containing the full class name, such as, java.io.FilePermission
NAME	VARCHAR2(4000)		Target attribute (name) of the permission object. This name is used when defining the permission.
ACTION	VARCHAR2(4000)		Action attribute for this permission. Many permissions expect a null value if no action is appropriate for the permission.
ENABLED	VARCHAR2(8)		Indicates whether the permission is enabled (ENABLED) or disabled (DISABLED)

Column	Datatype	NULL	Description
SEQ	NUMBER		Sequence number used to identify this row. This number should be supplied when disabling, enabling, or deleting the permission.

> **See Also:**
>
> "USER_JAVA_POLICY"

6.141 DBA_JAVA_RESOLVERS

DBA_JAVA_RESOLVERS displays information about resolvers of all Java classes in the database. Its columns are the same as those in ALL_JAVA_RESOLVERS.

> **See Also:**
>
> "ALL_JAVA_RESOLVERS"

6.142 DBA_JAVA_THROWS

DBA_JAVA_THROWS displays information about exceptions thrown from methods of all Java classes in the database. Its columns are the same as those in ALL_JAVA_THROWSa.

> **See Also:**
>
> "ALL_JAVA_THROWS"

6.143 DBA_JOBS

DBA_JOBS describes all jobs in the database.

Related View

USER_JOBS describes the jobs owned by the current user.

Column	Datatype	NULL	Description
JOB	NUMBER	NOT NULL	Identifier of job. Neither import/export nor repeated executions change this value.
LOG_USER	VARCHAR2(128)	NOT NULL	Login user when the job was submitted
PRIV_USER	VARCHAR2(128)	NOT NULL	User whose default privileges apply to this job

Column	Datatype	NULL	Description
SCHEMA_USER	VARCHAR2(128)	NOT NULL	Default schema used to parse the job For example, if the SCHEMA_USER is SCOTT and you submit the procedure HIRE_EMP as a job, the Oracle Database looks for SCOTT.HIRE_EMP
LAST_DATE	DATE		Date on which this job last successfully executed
LAST_SEC	VARCHAR2(8)		Same as LAST_DATE. This is when the last successful execution started.
THIS_DATE	DATE		Date that this job started executing (usually null if not executing)
THIS_SEC	VARCHAR2(8)		Same as THIS_DATE. This is when the last successful execution started.
NEXT_DATE	DATE	NOT NULL	Date that this job will next be executed
NEXT_SEC	VARCHAR2(8)		Same as NEXT_DATE. The job becomes due for execution at this time.
TOTAL_TIME	NUMBER		Total wall clock time spent by the system on this job (in seconds) when it last executed
BROKEN	VARCHAR2(1)		Y: no attempt is made to run this job N: an attempt is made to run this job
INTERVAL	VARCHAR2(200)	NOT NULL	A date function, evaluated at the start of execution, becomes next NEXT_DATE
FAILURES	NUMBER		Number of times the job has started and failed since its last success
WHAT	VARCHAR2(4000)		Body of the anonymous PL/SQL block that the job executes
NLS_ENV	VARCHAR2(4000)		Session parameters describing the NLS environment of the job
MISC_ENV	RAW(32)		Other session parameters of the session that created the job. The job is run using these parameters.
INSTANCE	NUMBER		ID of the instance that can execute or is executing the job. The default is 0.

See Also:

"USER_JOBS"

6.144 DBA_JOBS_RUNNING

DBA_JOBS_RUNNING lists all jobs that are currently running in the instance.

Column	Datatype	NULL	Description
SID	NUMBER		Identifier of process that is executing the job. See "V$LOCK".

Column	Datatype	NULL	Description
JOB	NUMBER		Identifier of job. This job is currently executing.
FAILURES	NUMBER		Number of times this job started and failed since its last success.
LAST_DATE	DATE		Date that this job last successfully executed.
LAST_SEC	VARCHAR2(8)		Same as LAST_DATE. This is when the last successful execution started.
THIS_DATE	DATE		Date that this job started executing.
THIS_SEC	VARCHAR2(8)		Same as THIS_DATE. This is when the last successful execution started.
INSTANCE	NUMBER		Indicates which instance can execute or is executing the job; the default is 0.

6.145 DBA_JOIN_IND_COLUMNS

DBA_JOIN_IND_COLUMNS describes all join conditions in the database. Its columns are the same as those in ALL_JOIN_IND_COLUMNS.

> **See Also:**
>
> "ALL_JOIN_IND_COLUMNS"

6.146 DBA_JOINGROUPS

DBA_JOINGROUPS describes join groups in the database. A join group is a user-created object that consists of two or more columns that can be meaningfully joined. The maximum number of columns that can be included in a join group is 255.

In certain queries, join groups enable the database to eliminate the performance overhead of decompressing and hashing column values. Join groups require an In-Memory column store (IM column store).

Related View

USER_JOINGROUPS describes join groups belonging to the user. This view does not display the JOINGROUP_OWNER column.

Column	Datatype	NULL	Description
JOINGROUP_OWNER	VARCHAR2(128)	NOT NULL	Join group owner. This is the user that created the join group.
JOINGROUP_NAME	VARCHAR2(128)	NOT NULL	This is the user specified name of the join group. The join group name is specified when the join group is created as part of the CREATE INMEMORY JOIN GROUP statement.
TABLE_OWNER	VARCHAR2(128)	NOT NULL	Table owner
TABLE_NAME	VARCHAR2(128)	NOT NULL	Table name

Column	Datatype	NULL	Description
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Column name
FLAGS	VARCHAR2(6)		Possible values: • MASTER: Indicates which column in the join group is mastering the global dictionary. A join group is a group of columns sharing a global dictionary; the global dictionary is associated with one column and the other columns share the same dictionary. The column with which the global dictionary is associated is called the mastering column. • NULL: Indicates that the column is not mastering the global dictionary.
GD_ADDRESS	RAW(8)		The memory address of the global dictionary. Ideally, all the columns in one join group should have the same global dictionary address (that is, they share the same global structure). This might not always be the case (for example, a column might be added to a join group after it was populated into memory - in which case its GD_ADDRESS field will be NULL). In such cases, you should force re-populate the tables that are part of the join group and check the views after the repopulates complete.
AUTO_CREATED	VARCHAR2(3)		Indicates whether the join group was created by Automatic In-Memory (AIM) (YES) or whether the join group was user-created (NO)
CREATION_DATE	DATE	NOT NULL	Date and time at which the join group was created

See Also:

- "USER_JOINGROUPS"
- *Oracle Database In-Memory Guide* for an introduction to join groups
- *Oracle Database SQL Language Reference* for information about creating a join group using the CREATE INMEMORY JOIN GROUP statement

6.147 DBA_JSON_COLLECTION_TABLES

DBA_JSON_COLLECTION_TABLES describes all JSON collection tables in the database. Its columns are the same as those in ALL_JSON_COLLECTION_TABLES.

Note:

This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_COLLECTION_TABLES"

6.148 DBA_JSON_COLLECTIONS

DBA_JSON_COLLECTIONS describes all JSON collections in the database. Its columns are the same as those in ALL_JSON_COLLECTIONS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_COLLECTIONS"

6.149 DBA_JSON_COLUMNS

DBA_JSON_COLUMNS provides information on all JavaScript Object Notation (JSON) columns in the database. Its columns are the same as those in ALL_JSON_COLUMNS.

> **See Also:**
>
> - "ALL_JSON_COLUMNS"
> - *Oracle Database JSON Developer's Guide* for more information about using JSON with Oracle Database

6.150 DBA_JSON_DATAGUIDE_FIELDS

DBA_JSON_DATAGUIDE_FIELDS extracts the path and type information from all the data guides in the database, which are the data guides returned by the DBA_JSON_DATAGUIDE view. Its columns are the same as those in ALL_JSON_DATAGUIDE_FIELDS.

> **See Also:**
>
> "ALL_JSON_DATAGUIDE_FIELDS"

6.151 DBA_JSON_DATAGUIDES

DBA_JSON_DATAGUIDES provides information on all JavaScript Object Notation (JSON) columns in the database that have data guide enabled. Its columns are the same as those in ALL_JSON_DATAGUIDES.

> **See Also:**
>
> "ALL_JSON_DATAGUIDES"

6.152 DBA_JSON_DOMAIN_SCHEMA_COLUMNS

DBA_JSON_DOMAIN_SCHEMA_COLUMNS describes JSON schema constraints on columns of all data use case domains in the database. Its columns are the same as those in ALL_JSON_DOMAIN_SCHEMA_COLUMNS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_DOMAIN_SCHEMA_COLUMNS"

6.153 DBA_JSON_DUALITY_VIEW_LINKS

DBA_JSON_DUALITY_VIEW_LINKS describes the links associated with all JSON-relational duality views in the database. Its columns are the same as those in ALL_JSON_DUALITY_VIEW_LINKS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_DUALITY_VIEW_LINKS"

6.154 DBA_JSON_DUALITY_VIEW_TAB_COLS

DBA_JSON_DUALITY_VIEW_TAB_COLS describes the table columns associated with all JSON-relational duality views in the database. Its columns are the same as those in ALL_JSON_DUALITY_VIEW_TAB_COLS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_DUALITY_VIEW_TAB_COLS"

6.155 DBA_JSON_DUALITY_VIEW_TABS

DBA_JSON_DUALITY_VIEW_TABS describes the tables associated with all JSON-relational duality views in the database. Its columns are the same as those in ALL_JSON_DUALITY_VIEW_TABS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_DUALITY_VIEW_TABS"

6.156 DBA_JSON_DUALITY_VIEWS

DBA_JSON_DUALITY_VIEWS describes all JSON-relational duality views in the database. Its columns are the same as those in ALL_JSON_DUALITY_VIEWS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_DUALITY_VIEWS"

6.157 DBA_JSON_INDEXES

`DBA_JSON_INDEXES` describes all indexes on JSON data in the database. Its columns are the same as those in `ALL_JSON_INDEXES`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_INDEXES"

6.158 DBA_JSON_SCHEMA_COLUMNS

`DBA_JSON_SCHEMA_COLUMNS` describes JSON schema constraints on columns in all tables in the database. Its columns are the same as those in `ALL_JSON_SCHEMA_COLUMNS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_SCHEMA_COLUMNS"

6.159 DBA_KAFKA_APPLICATIONS

`DBA_KAFKA_APPLICATIONS` describes all Oracle SQL Access to Kafka (OSAK) applications in the database.

Related View

USER_KAFKA_APPLICATIONS describes OSAK applications owned by the current user. This view does not display the OWNER or CLUSTER_ID columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the application
CLUSTER_ID	VARCHAR2(40)	NOT NULL	ID of the OSAK cluster associated with the application
CLUSTER_NAME	VARCHAR2(30)	NOT NULL	Name of the OSAK cluster associated with the application
APPLICATION_NAME	VARCHAR2(30)	NOT NULL	Application name (also used as the Kafka group name)
TOPIC_NAME	VARCHAR2(249)	NOT NULL	Name of the Kafka topic associated with the application
FORMAT	VARCHAR2(4000)		Format of the Kafka topic value data: • AVRO • DSV • JSON
KEY_FORMAT	VARCHAR2(4000)		Format of the Kafka topic key data: • AVRO • DSV • JSON
NUM_VIEWS	NUMBER(38)	NOT NULL	Number of OSAK views for the application
NUM_PARTITIONS	NUMBER(38)	NOT NULL	Number of Kafka partitions associated with the OSAK views for the application
NUM_VIEWS_REQUESTED	NUMBER(38)	NOT NULL	Number of OSAK views requested for the application
APPLICATION_TYPE	VARCHAR2(30)	NOT NULL	Type of application: • LOAD • SEEKABLE • STREAMING
OPTIONS	BLOB	NOT NULL	User-supplied options (excluding AVRO-related schemas)
AVRO_SCHEMA	BLOB		User-supplied AVRO schema for the Kafka topic value data
KEY_AVRO_SCHEMA	BLOB		Reserved for future use

Note:

This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "USER_KAFKA_APPLICATIONS"
> - "DBMS_KAFKA_APPLICATIONS"

6.160 DBA_KAFKA_CLUSTERS

DBA_KAFKA_CLUSTERS describes the Oracle SQL Access to Kafka (OSAK) clusters for which any database user has READ access.

Related View

USER_KAFKA_CLUSTERS describes the OSAK clusters that are owned by the current user or for which the current user has READ access. This view does not display the OWNER or GRANTEE columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cluster The value of this column is always SYS.
CLUSTER_ID	VARCHAR2(40)	NOT NULL	System-generated unique cluster ID
STATE	NUMBER(38)	NOT NULL	Current state of the cluster: • 0 - CONNECTED • 1 - MAINTENANCE • 2 - BROKEN • 3 - DEREGISTERED
CLUSTER_NAME	VARCHAR2(30)	NOT NULL	User-supplied name of the cluster
BOOTSTRAP_SERVERS	VARCHAR2(4000)	NOT NULL	Comma-separated list of bootstrap servers for the cluster Each bootstrap server is represented in the following form: *hostname*:*port*
KAFKA_PROVIDER	VARCHAR2(128)	NOT NULL	Provider of the Kafka cluster software: • APACHE - Apache Kafka • OSS - Oracle Cloud Infrastructure Streaming Service
CONNECTION_TS	TIMESTAMP(6)		If GRANTEE is currently connected to the cluster, the date and time at which the connection was started; otherwise NULL
CLUSTER_DESCRIPTION	VARCHAR2(4000)		Optional user-supplied description of the Oracle SQL access to the cluster
GRANTEE	VARCHAR2(128)		User who is granted access to the cluster

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "USER_KAFKA_CLUSTERS"
> - "DBMS_KAFKA_CLUSTERS" for information about viewing all registered OSAK clusters in the database

6.161 DBA_KAFKA_LOAD_METRICS

DBA_KAFKA_LOAD_METRICS displays metrics for DBMS_KAFKA.EXECUTE_LOAD_APP operations on all tables in the database.

Related View

USER_KAFKA_LOAD_METRICS displays metrics for DBMS_KAFKA.EXECUTE_LOAD_APP operations on tables owned by the current user. This view does not display the OWNER or CLUSTER_ID columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table into which the Kafka data was loaded (TARGET_TABLE)
CLUSTER_ID	VARCHAR2(40)	NOT NULL	ID of the OSAK cluster associated with the EXECUTE_LOAD_APP operation
CLUSTER_NAME	VARCHAR2(30)	NOT NULL	Name of the OSAK cluster associated with the OSAK cluster ID
APPLICATION_NAME	VARCHAR2(30)		Application name (also used as the Kafka group name)
TARGET_TABLE	VARCHAR2(128)	NOT NULL	Name of the table into which the Kafka data was loaded
TARGET_TABLE_SCHEMA	VARCHAR2(128)	NOT NULL	Schema of the table into which the Kafka data was loaded
INSERTED_ROWS	NUMBER(38)		Total number of rows inserted into the table by the load operation
KAFKA_RECORDS	NUMBER(38)		Total number of Kafka records fetched for the load operation
STARTED_TIME	TIMESTAMP(6) WITH TIME ZONE		Date and time at which the Kafka data started being loaded into the table
FINISHED_TIME	TIMESTAMP(6) WITH TIME ZONE		Date and time at which the Kafka data finished being loaded into the table

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

See Also:

- "USER_KAFKA_LOAD_METRICS"
- "DBMS_KAFKA_LOAD_METRICS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_KAFKA.EXECUTE_LOAD_APP` procedure

6.162 DBA_KAFKA_OPS

`DBA_KAFKA_OPS` describes operations for all Oracle SQL Access to Kafka (OSAK) views in the database.

Related View

`USER_KAFKA_OPS` describes operations for OSAK views owned by the current user. This view does not display the `OWNER` or `CLUSTER_ID` columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the OSAK view
OP_KEY	VARCHAR2(30)	NOT NULL	Unique operation key (replacement for the location file)
OP_TYPE	VARCHAR2(30)	NOT NULL	Generic operation type
OP	VARCHAR2(30)	NOT NULL	Specific type of operation within `OP_TYPE`
CLUSTER_ID	VARCHAR2(40)	NOT NULL	ID of the OSAK cluster associated with the operation
CLUSTER_NAME	VARCHAR2(30)	NOT NULL	Name of the OSAK cluster associated with the operation
APPLICATION_NAME	VARCHAR2(30)		Name of the OSAK application associated with the operation (also used as the Kafka group name)
TOPIC_NAME	VARCHAR2(249)		Name of the Kafka topic associated with the operation
PARTITION_ID	NUMBER(38)		Partition ID of the Kafka topic associated with the operation
OFFSET	NUMBER(38)		Next offset from which an SEQ operation will start reading
RELATIVE_OFFSET	NUMBER(38)		Number of offsets, including the watermark, from which an SEQ operation will start reading
WATERMARK	VARCHAR2(5)		Basis for the start read offset for an SEQ operation (`WMH` or `WML`)
START_OFFSET_EPOCH_TIME	NUMBER(38)		Timestamp (in milliseconds) that determines the next offset from which the operation will start reading This value is used by the `DBMS_KAFKA.INIT_OFFSET_TS` and `DBMS_KAFKA.SEEK_OFFSET_TS` procedures.

Column	Datatype	NULL	Description
END_OFFSET_EPOCH_TIME	NUMBER(38)		Timestamp (in milliseconds) that determines the end offset at which the operation will stop reading This value is used by the DBMS_KAFKA.SEEK_OFFSET_TS procedure.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "USER_KAFKA_OPS"
> - "DBMS_KAFKA_OPS"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_KAFKA.INIT_OFFSET_TS and DBMS_KAFKA.SEEK_OFFSET_TS procedures

6.163 DBA_KAFKA_OPS_RESULTS

DBA_KAFKA_OPS_RESULTS displays the results of operations for all Oracle SQL Access to Kafka (OSAK) views in the database.

Related View

USER_KAFKA_OPS_RESULTS displays the results of operations for Oracle SQL Access to Kafka (OSAK) views owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of OSAK view
OP_KEY	VARCHAR2(30)		Unique operation key (replacement for the location file)
ROWS_READ	NUMBER(38)		Number of Kafka records read and returned by the operation
LAST_OFFSET	NUMBER(38)		Kafka offset of the last record read by the operation

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "USER_KAFKA_OPS_RESULTS"
> - "DBMS_KAFKA_OPS_RESULTS"

6.164 DBA_KAFKA_PARTITIONS

DBA_KAFKA_PARTITIONS describes partitions for Kafka topics associated with all Oracle SQL Access to Kafka (OSAK) views in the database.

Related View

USER_KAFKA_PARTITIONS describes partitions for Kafka topics associated with OSAK views owned by the current user. This view does not display the OWNER or CLUSTER_ID columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the OSAK view
CLUSTER_ID	VARCHAR2(40)	NOT NULL	ID of the OSAK cluster associated with the topic/partition
CLUSTER_NAME	VARCHAR2(30)	NOT NULL	User-supplied name of the associated Kafka server/cluster
APPLICATION_NAME	VARCHAR2(30)	NOT NULL	Application name (also used as the Kafka group name)
TOPIC_NAME	VARCHAR2(249)	NOT NULL	Kafka topic name associated with the topic/partition
PARTITION_ID	NUMBER(38)	NOT NULL	Partition ID of the Kafka topic
VIEW_ID	NUMBER(38)	NOT NULL	ID of the OSAK view associated with the topic/partition
VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the OSAK view associated with the topic/partition
TEMP_TABLE_NAME	VARCHAR2(128)		Name of the OSAK global temporary table associated with the topic/partition The value of this column is null if the application type is LOAD, that is, if the application was created using the DBMS_KAFKA.CREATE_LOAD_APP procedure. The application type is displayed in the APPLICATION_TYPE column of the DBA_KAFKA_APPLICATIONS view.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "USER_KAFKA_PARTITIONS"
> - "DBMS_KAFKA_PARTITIONS"

6.165 DBA_KGLLOCK

DBA_KGLLOCK lists all the locks and pins held on KGL objects (objects in the Kernel Generic Library cache).

Column	Datatype	NULL	Description
kgllkuse	RAW(4)		Address of the user session that holds the lock or pin
kgllkhdl	RAW(4)		Address of the handle for the KGL object
kgllkmod	NUMBER		Current mode of the lock or pin
kgllkreq	NUMBER		Mode in which the lock or pin was requested
kgllktype	VARCHAR2(4)		Whether this is a lock or a pin

6.166 DBA_LIBRARIES

DBA_LIBRARIES describes all libraries in the database. Its columns are the same as those in ALL_LIBRARIES.

> **See Also:**
>
> "ALL_LIBRARIES"

6.167 DBA_LMT_FREE_SPACE

DBA_LMT_FREE_SPACE describes the free extents in all locally managed tablespaces in the database.

Column	Datatype	NULL	Description
TABLESPACE_ID	NUMBER		Identifier number of the tablespace containing the extent
FILE_ID	NUMBER		File identifier number of the file containing the extent
BLOCK_ID	NUMBER		Starting block number of the extent
BLOCKS	NUMBER		Size of the extent (in Oracle blocks)

6.168 DBA_LMT_USED_EXTENTS

DBA_LMT_USED_EXTENTS describes the extents comprising the segments in all locally managed tablespaces in the database.

Column	Datatype	NULL	Description
SEGMENT_FILEID	NUMBER		File number of the segment header of the extent
SEGMENT_BLOCK	NUMBER		Block number of the segment header of the extent
TABLESPACE_ID	NUMBER		Identifier number of the tablespace containing the extent
EXTENT_ID	NUMBER		Extent number in the segment
FILEID	NUMBER		File identifier number of the file containing the extent
BLOCK	NUMBER		Starting block number of the extent
LENGTH	NUMBER		Number of blocks in the extent

6.169 DBA_LOB_PARTITIONS

DBA_LOB_PARTITIONS displays all LOB partitions in the database. Its columns are the same as those in ALL_LOB_PARTITIONS.

> **See Also:**
>
> "ALL_LOB_PARTITIONS"

6.170 DBA_LOB_SUBPARTITIONS

DBA_LOB_SUBPARTITIONS displays partition-level attributes of all LOB data subpartitions in the database. Its columns are the same as those in ALL_LOB_SUBPARTITIONS.

> **See Also:**
>
> "ALL_LOB_SUBPARTITIONS"

6.171 DBA_LOB_TEMPLATES

DBA_LOB_TEMPLATES describes all LOB subpartition templates in the database. Its columns are the same as those in ALL_LOB_TEMPLATES.

> **See Also:**
>
> "ALL_LOB_TEMPLATES"

6.172 DBA_LOBS

DBA_LOBS displays the BLOBs and CLOBs contained in all tables in the database. BFILEs are stored outside the database, so they are not described by this view. This view's columns are the same as those in ALL_LOBS.

> **See Also:**
>
> "ALL_LOBS"

6.173 DBA_LOCK

DBA_LOCK lists all locks or latches held in the database, and all outstanding requests for a lock or latch.

Column	Datatype	NULL	Description
SESSION_ID	NUMBER		Session holding or acquiring the lock
LOCK_TYPE	VARCHAR2(26)		Lock type **See Also:** For a listing of lock types, see Oracle Enqueue Names
MODE_HELD	VARCHAR2(40)		Lock mode
MODE_REQUESTED	VARCHAR2(40)		Lock mode requested
LOCK_ID1	VARCHAR2(40)		Type-specific lock identifier, part 1
LOCK_ID2	VARCHAR2(40)		Type-specific lock identifier, part 2
LAST_CONVERT	NUMBER		The last convert
BLOCKING_OTHERS	VARCHAR2(40)		Whether the lock is currently blocking others

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.174 DBA_LOCK_INTERNAL

DBA_LOCK_INTERNAL displays a row for each lock or latch that is being held, and one row for each outstanding request for a lock or latch.

Column	Datatype	NULL	Description
SESSION_ID	NUMBER		Session holding or acquiring the lock
LOCK_TYPE	VARCHAR2(56)		Lock type **See Also:** For a listing of lock types, see Oracle Enqueue Names
MODE HELD	VARCHAR2(40)		Lock mode
MODE REQUESTED	VARCHAR2(40)		Lock mode requested
LOCK_ID1	VARCHAR2(1130)		Type-specific lock identifier, part 1
LOCK_ID2	VARCHAR2(40)		Type-specific lock identifier, part 2
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.175 DBA_LOCKDOWN_PROFILES

DBA_LOCKDOWN_PROFILES provides information about lockdown profiles.

The PRIVATE_DBAAS, PUBLIC_DBAAS, and SAAS lockdown profiles are empty placeholder profiles for the lockdown profiles of their corresponding deployment type. You can modify and add restrictions to these profiles based on their deployment purpose. For example, if you have a Software as a Service (SAAS) application, you can modify the SAAS lockdown profile and use it. You can also delete and re-create these profiles.

Column	Datatype	NULL	Description
PROFILE_NAME	VARCHAR2(128)	NOT NULL	Name of the lockdown profile

Column	Datatype	NULL	Description
RULE_TYPE	VARCHAR2(128)		Rule type. A lockdown profile is used to restrict operations that can be performed by users connected to a given PDB. It provides the ability to add or remove different types of rules like STATEMENT, FEATURES or OPTIONS which will be restricted in the PDB.
RULE	VARCHAR2(128)		Rule to be enabled or disabled
CLAUSE	VARCHAR2(128)		Clause of the statement
CLAUSE_OPTION	VARCHAR2(128)		Option of the clause
OPTION_VALUE	VARCHAR2(4000)		Value of the option
MIN_VALUE	VARCHAR2(4000)		Minimum value allowed for the option
MAX_VALUE	VARCHAR2(4000)		Maximum value allowed for the option
LIST	VARCHAR2(4000)		List of allowed values for the option
STATUS	VARCHAR2(7)		Status of the lockdown profile: • ENABLE • DISABLE • EMPTY
USERS	VARCHAR2(6)		User type. Possible values: • COMMON • LOCAL • ALL
EXCEPT_USERS	CLOB		For internal use only

See Also:

- "PDB_LOCKDOWN"
- *Oracle Multitenant Administrator's Guide* for an introduction to PDB lockdown profiles
- *Oracle Database SQL Language Reference* for more information about creating lockdown profiles
- *Oracle Database SQL Language Reference* for more information about dropping lockdown profiles
- *Oracle Database SQL Language Reference* for more information about altering lockdown profiles

6.176 DBA_LOCKS

DBA_LOCKS is a synonym for DBA_LOCK.

> **See Also:**
>
> "DBA_LOCK"

6.177 DBA_LOG_GROUP_COLUMNS

DBA_LOG_GROUP_COLUMNS describes all columns in the database that are specified in log groups. Its columns are the same as those in ALL_LOG_GROUP_COLUMNS.

> **See Also:**
>
> "ALL_LOG_GROUP_COLUMNS"

6.178 DBA_LOG_GROUPS

DBA_LOG_GROUPS describes log group definitions on all tables in the database. Its columns are the same as those in ALL_LOG_GROUPS.

> **See Also:**
>
> "ALL_LOG_GROUPS"

6.179 DBA_LOGMNR_DICTIONARY_BUILDLOG

DBA_LOGMNR_DICTIONARY_BUILDLOG describes all successful LogMiner dictionary builds available for GoldenGate REGISTER EXTRACT.

When this view is queried from a PDB, it returns only LogMiner dictionary builds performed in that PDB.

Column	Datatype	NULL	Description
NAME	VARCHAR2(384)		User-supplied name of the LogMiner dictionary build
DATE_OF_BUILD	VARCHAR2(20)		Date and time at which the LogMiner dictionary build was performed
START_SCN	NUMBER		Begin SCN of the LogMiner dictionary build operation

Column	Datatype	NULL	Description
END_SCN	NUMBER		End SCN of the LogMiner dictionary build operation
BUILD_TYPE	VARCHAR2(20)		Internal string that identifies how the LogMiner dictionary build was initiated
BUILD_OP	NUMBER		Internal number that identifies how the LogMiner dictionary build was initiated
CONTAINER_ID	NUMBER		ID of the container in which the LogMiner dictionary build was performed (the CDB root or a PDB)
CONTAINER_UID	NUMBER		Unique number that identifies the container in which the LogMiner dictionary build was performed (the CDB root or a PDB)
CONTAINER_NAME	VARCHAR2(384)		Name of the container in which the LogMiner dictionary build was performed (the CDB root or a PDB)
RESETLOGS_CHANGE#	NUMBER		SCN that identifies the redo branch of the LogMiner dictionary build

6.180 DBA_LOGMNR_LOG

DBA_LOGMNR_LOG displays all archived logs registered with active LogMiner persistent sessions in the database.

A persistent LogMiner session is created either by starting Data Guard SQL Apply on a logical standby database for the first time or by creating Replication capture.

Column	Datatype	NULL	Description
LOGMNR_SESSION_ID	NUMBER	NOT NULL	Unique identifier of the persistent session
NAME	VARCHAR2(513)		Name of the archived log
DBID	NUMBER	NOT NULL	Database identifier that produced the archived log
RESETLOGS_SCN	NUMBER	NOT NULL	SCN at which resetlogs operation was performed at the source database generating the archived log
RESETLOGS_TIME	NUMBER	NOT NULL	Timestamp at which resetlogs operation was performed at the source database generating the archived log
MODIFIED_TIME	DATE		Time at which the archived log was registered with LogMiner
THREAD#	NUMBER	NOT NULL	Redo thread at the source database that generated the archived log
SEQUENCE#	NUMBER	NOT NULL	Logfile sequence number
FIRST_SCN	NUMBER	NOT NULL	Lowest SCN of the redo record contained in the logfile
NEXT_SCN	NUMBER		Highest possible SCN of the redo record contained in the logfile
FIRST_TIME	DATE		Time of the first redo record contained in the logfile

Column	Datatype	NULL	Description
NEXT_TIME	DATE		Time of the last redo record contained in the logfile
DICTIONARY_BEGIN	VARCHAR2(3)		Indicates whether the archived log contains the beginning of a LogMiner dictionary (YES) or not (NO)
DICTIONARY_END	VARCHAR2(3)		Indicates whether the archived log contains the end of a LogMiner dictionary (YES) or not (NO)
KEEP	VARCHAR2(3)		Indicates whether the logfile is still required for this LogMiner session (YES) or not (NO)
SUSPECT	VARCHAR2(3)		Indicates whether the archived log content was deemed to be corrupt or the archived log is partially filled (YES) or not (NO)

6.181 DBA_LOGMNR_PURGED_LOG

DBA_LOGMNR_PURGED_LOG displays archived redo log files that have been applied to the logical standby database and can be deleted because they are no longer needed.

Files in this view are refreshed as a result of executing the DBMS_LOGSTDBY.PURGE_SESSION PL/SQL procedure for Oracle Data Guard SQL Apply:

Column	Datatype	NULL	Description
FILE_NAME	VARCHAR2(513)		Fully qualified names of the archived redo log files that are no longer needed by SQL Apply and can be deleted from the operating system

> **See Also:**
>
> *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_LOGSTDBY.PURGE_SESSION procedure

6.182 DBA_LOGMNR_SESSION

DBA_LOGMNR_SESSION displays all active LogMiner persistent sessions in the database.

A persistent LogMiner session is created either by starting Data Guard SQL Apply on a logical standby database for the first time or by creating Replication capture.

Column	Datatype	NULL	Description
ID	NUMBER	NOT NULL	Unique session identifier
NAME	VARCHAR2(128)	NOT NULL	Unique session name
SOURCE_DATABASE	VARCHAR2(128)		Global name of the source database whose archived logs are to be mined in this persistent LogMiner session

Column	Datatype	NULL	Description
SOURCE_DBID	NUMBER		Database ID of the source database
SOURCE_RESETLOGS_SCN	NUMBER		Resetlogs SCN associated with the incarnation of the source database whose archived logs are mined
SOURCE_RESETLOGS_TIME	NUMBER		Resetlogs time associated with the incarnation of the source database whose archived logs are mined
FIRST_SCN	NUMBER		Only modifications that occurred on or after this SCN can be mined using this persistent session
END_SCN	NUMBER		No modifications that occurred on or after this SCN can be mined using this persistent session
BRANCH_SCN	NUMBER		SCN at which a branch will be taken in terms of the incarnation corresponding to the source database. This implies a point-in-time recovery was performed at the source database at this SCN.
WAIT_FOR_LOG	VARCHAR2(3)		Indicates whether the persistent session waits for RFS to register new archived logs or to fill gaps (YES) or not (NO)
HOT_MINE	VARCHAR2(3)		Indicates whether real-time mining is on (YES) or not (NO)
SAFE_PURGE_SCN	NUMBER		Persistent session can safely be purged up to this SCN
CHECKPOINT_SCN	NUMBER		SCN at which the latest checkpoint is taken by the persistent LogMiner session
PURGE_SCN	NUMBER		The session has been purged up to this SCN

6.183 DBA_LOGSTDBY_EVENTS

DBA_LOGSTDBY_EVENTS displays information about the activity of the logical standby database system.

It can be used to determine the cause of failures that occur when applying redo data to logical standby databases. This view is for logical standby databases only.

Column	Datatype	NULL	Description
EVENT_TIME	DATE		Time when the event was logged
EVENT_TIMESTAMP	TIMESTAMP(6)	NOT NULL	Timestamp when the event was logged
START_SCN	NUMBER		The SCN at which the associated transaction started at the primary database. This SCN refers to the system change number at the primary database.
CURRENT_SCN	NUMBER		SCN associated with the change at the primary database. If a failure occurred, then examine this column to determine which archived log file contains the source of the failure (for example, an unsupported record).

Column	Datatype	NULL	Description
COMMIT_SCN	NUMBER		SCN value on which the change was committed at the primary database
XIDUSN	NUMBER		Transaction ID undo segment number at the primary database of the associated transaction
XIDSLT	NUMBER		Transaction ID slot number at the primary database of the associated transaction
XIDSQN	NUMBER		Transaction ID sequence number at the primary database of the associated transaction
EVENT	CLOB		Statement that was being processed when the failure occurred
STATUS_CODE	NUMBER		Status (or Oracle error code) belonging to the STATUS message
STATUS	VARCHAR2(2000)		Description of the current activity of the process or the reason why the apply operation stopped
SRC_CON_NAME	VARCHAR2(30)		Identifies the PDB name at the primary database where the transaction was executed
SRC_CON_ID	NUMBER		Contains the PDB ID (the PDB_ID column from the DBA_PDBS view) of the primary database where the associated change was generated.

> **Note:**
>
> In a CDB, this view shows data only when queried in the root.

6.184 DBA_LOGSTDBY_HISTORY

DBA_LOGSTDBY_HISTORY displays the history of switchovers and failovers in a Data Guard configuration.

It does this by showing the complete sequence of redo log streams processed or created on the local system, across all role transitions. (After a role transition, a new log stream is started and the log stream sequence number is incremented by the new primary database.). This view is for logical standby databases only.

Column	Datatype	NULL	Description
STREAM_SEQUENCE#	NUMBER		Lists the sequence numbers for all log streams created or applied on the local system. **Note**: A value of 0 indicates an unknown sequence order; this is reserved for future log streams.

Column	Datatype	NULL	Description
STATUS	VARCHAR2(16)		Description of the log stream processing: • Past - The log stream has already been processed • Immediate Past - This is the most recently processed log stream; its status is transitioning from Current to Past • Current - The log stream is currently being processed • Immediate Future - This is the next log stream to be processed; its status is transitioning from Future to Current • Future - The log stream will be processed
SOURCE	VARCHAR2(5)		Describes how the log stream was started: • RFS - The RFS process created the log stream • User - A user registered the initial log file for the log stream • Synch - A user issued the ALTER DATABASE START LOGICAL STANDBY APPLY NEW PRIMARY DDL statement • Redo - The log stream information was recorded in the redo log
DBID	NUMBER		Database identifier of the primary database that created the log stream
FIRST_CHANGE#	NUMBER		Lowest system change number (SCN) in the current log file
LAST_CHANGE#	NUMBER		Highest system change number (SCN) in the current log file
FIRST_TIME	DATE		Time of the first SCN entry (FIRST_CHANGE#) in the current log file
LAST_TIME	DATE		Time of the last SCN entry (LAST_CHANGE#) in the current log file
DGNAME	VARCHAR2(255)		Unique database name (DB_UNIQUE_NAME) of the primary database that produced the log stream. See V$DATAGUARD_CONFIG to display all database DB_UNIQUE_NAME values defined in the Data Guard configuration.
MERGE_CHANGE#	NUMBER		SCN that should be used to flashback a failed primary (that created the log stream) or to flashback a bystander logical standby database following a failover, in the context of the associated redo log stream. It is the SCN up to which redo for the associated log stream can be merged safely in all databases using local copies of archived logs received from the primary database. In order to apply changes beyond this following a failover, you will need to fetch and mine the redo logs from the failover target.

Column	Datatype	NULL	Description
PROCESSED_CHANGE#	NUMBER		Strict upper bound on the SCN up to which SQL Apply has applied redo records before it switched to a new log stream (either because it was activated and became the primary database, or in the case of a bystander logical standby database where it switched to a new log stream to accommodate a new primary database).

> **Note:**
>
> In a CDB, this view shows data only when queried in the root.

6.185 DBA_LOGSTDBY_LOG

DBA_LOGSTDBY_LOG displays information about the logs registered for a logical standby database.

This view is for logical standby databases only.

Column	Datatype	NULL	Description
THREAD#	NUMBER	NOT NULL	Thread ID of the archive log. The THREAD number is 1 for a single instance. For Real Application Clusters, this column will contain different numbers.
RESETLOGS_CHANGE#	NUMBER	NOT NULL	Start SCN of the branch
RESETLOGS_ID	NUMBER	NOT NULL	Resetlogs identifier (a numeric form of the timestamp of the branch)
SEQUENCE#	NUMBER	NOT NULL	Sequence number of the archive log file
FIRST_CHANGE#	NUMBER	NOT NULL	System change number (SCN) of the current archive log
NEXT_CHANGE#	NUMBER		SCN of the next archive log
FIRST_TIME	DATE		Date of the current archive log
NEXT_TIME	DATE		Date of the next archive log
FILE_NAME	VARCHAR2(513)		Name of the archive log
TIMESTAMP	DATE		Time when the archive log was registered
DICT_BEGIN	VARCHAR2(3)		Indicates whether the beginning of the dictionary build is in this archive log (YES) or not (NO)
DICT_END	VARCHAR2(3)		Indicates whether the end of the dictionary build is in this archive log (YES) or not (NO)

Column	Datatype	NULL	Description
APPLIED	VARCHAR2(8)		Indicates primarily whether a given foreign archived log has been applied fully by SQL Apply: • YES - SQL Apply has fully applied the foreign archived log and no longer needs it • CURRENT - SQL Apply is currently applying changes contained in the foreign archived log • NO - SQL Apply has not started applying any changes contained in the foreign archived log • FETCHING - SQL Apply encountered a corruption while reading redo records from this foreign archived log, and is currently using the automatic gap resolution to refetch a new copy of the log from the primary database • CORRUPT - SQL Apply encountered a corruption while reading redo records from this foreign archived log, and refetching a new copy of the archived log did not resolve the problem. SQL Apply will not refetch a new copy of this archived log automatically, and will require user intervention to manually register a new copy of the foreign archived log.
BLOCKS	NUMBER		Number of blocks in the log
BLOCK_SIZE	NUMBER		Size of each block in the log

Note:

The SCN values in this view correlate to the SCN values shown in the DBA_LOGSTDBY_PROGRESS view.

Note:

In a CDB, this view shows data only when queried in the root.

6.186 DBA_LOGSTDBY_NOT_UNIQUE

DBA_LOGSTDBY_NOT_UNIQUE displays all tables that have no primary and no non-null unique indexes.

Most of the tables displayed by this view are supported because their columns contain enough information to be maintained in a logical standby database. Some tables, however, cannot be supported because their columns do not contain the necessary information. Unsupported tables usually contain a column defined using an unsupported data type.

In a CDB, the data displayed pertains to the container in which the view is queried.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Schema name of the non-unique table
TABLE_NAME	VARCHAR2(128)		Table name of the non-unique table
BAD_COLUMN	VARCHAR2(1)		• Y - Table column is defined using an unbounded data type, such as LONG or BLOB. If two rows in the table match except in their LOB columns, then the table cannot be maintained properly. Log apply services will attempt to maintain these tables, but you must ensure the application does not allow uniqueness only in the unbounded columns. • N - Enough column information is present to maintain the table in the logical standby database but the log transport services and log apply services would run more efficiently if you added a primary key. You should consider adding a disabled RELY constraint to these tables.

6.187 DBA_LOGSTDBY_PARAMETERS

DBA_LOGSTDBY_PARAMETERS displays the list of parameters used by SQL apply for logical standby databases.

This view is for logical standby databases only.

Column	Datatype	NULL	Description
NAME	VARCHAR2(64)		Name of the parameter: • MAX_SGA - System global area (SGA) allocated for the log apply services cache (in megabytes) • MAX_SERVERS - Number of processes used by SQL Apply services • PREPARE_SERVERS - Controls the number of parallel execution servers used to prepare changes • APPLY_SERVERS - Controls the number of parallel execution servers used to apply changes • MAX_EVENTS_RECORDED - Number of events stored in the DBA_LOGSTDBY_EVENTS view • RECORD_SKIP_ERRORS - Indicates records that are skipped • RECORD_SKIP_DDL - Indicates skipped DDL statements • RECORD_APPLIED_DDL - Indicates applied DDL statements • RECORD_UNSUPPORTED_OPERATIONS - Shows whether SQL Apply will capture information about transactions that did unsupported operations at the primary database in the DBA_LOGSTDBY_EVENTS view • EVENT_LOG_DEST - Indicates where SQL Apply records the occurrence of an interesting event • LOG_AUTO_DELETE - Shows whether SQL Apply will automatically delete remote archived logs received from the primary database, once the contents of the logs are applied at the logical standby database. • LOG_AUTO_DEL_RETENTION_TARGET - How many minutes a remote archived log received from the primary database will be retained at the logical standby database, once the contents of the log are applied by SQL Apply. • PRESERVE_COMMIT_ORDER - Shows whether transactions are committed at the logical standby database in the same order that they were committed at the primary database
VALUE	VARCHAR2(2000)		Value of the parameter
UNIT	VARCHAR2(64)		Unit of the value, if applicable
SETTING	VARCHAR2(64)		Possible values are as follows: • SYSTEM - Parameter value was not explicitly set by the user. However, the user can change it with an appropriate call to the APPLY_SET procedure. • USER - Parameter value was explicitly set by the user

Column	Datatype	NULL	Description
DYNAMIC	VARCHAR2(64)		YES if the parameter can be set dynamically (that is, without having to stop SQL Apply) NO if setting the parameter requires that SQL Apply be stopped

> **Note:**
>
> In a CDB, this view shows data when queried in the root.

6.188 DBA_LOGSTDBY_PLSQL_MAP

DBA_LOGSTDBY_PLSQL_MAP shows the mapping between a supported user invokable (/ external) PL/SQL procedure to the corresponding replicated internal PL/SQL procedure.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner name of the procedure
PKG_NAME	VARCHAR2(128)		Package name of the user invokable procedure
PROC_NAME	VARCHAR2(128)		Procedure name of the user invokable procedure
INTERNAL_PKG_NAME	VARCHAR2(128)		Package name of the internal procedure
INTERNAL_PROC_NAME	VARCHAR2(128)		Procedure name of the internal procedure

> **Note:**
>
> In a CDB, this view shows data when queried in the root or a PDB.

6.189 DBA_LOGSTDBY_PLSQL_SUPPORT

DBA_LOGSTDBY_PLSQL_SUPPORT shows the PL/SQL packages that are only supported during rolling operations.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner name of the package
PKG_NAME	VARCHAR2(128)		Package name of the user invokable procedure

Column	Datatype	NULL	Description
SUPPORT_LEVEL	VARCHAR2(12)		Logical standby PL/SQL support level for the package: • ALWAYS - PL/SQL replication is always supported for this package, whether it is called inside or outside of DBMS_ROLLING • DBMS_ROLLING: PL/SQL replication is supported only when the procedure is called inside DBMS_ROLLING

Note:

In a CDB, this view shows data when queried in the root or a PDB.

See Also:

Oracle Database PL/SQL Packages and Types Reference for more information about the DBMS_ROLLING package

6.190 DBA_LOGSTDBY_PROGRESS

DBA_LOGSTDBY_PROGRESS is deprecated. The information that was provided in this view is now provided in the V$LOGSTDBY_PROGRESS view.

See Also:

"V$LOGSTDBY_PROGRESS"

6.191 DBA_LOGSTDBY_SKIP

DBA_LOGSTDBY_SKIP displays the skip rules that are used by SQL Apply.

This view is for logical standby databases only.

Column	Datatype	NULL	Description
ERROR	VARCHAR2(1)		Indicates how the skip rule was created: • Y - For rules from DBMS_LOGSTDBY.SKIP_ERROR • N - For rules from DBMS_LOGSTDBY.SKIP
STATEMENT_OPT	VARCHAR2(128)		Specifies the type of statement that should be skipped
OWNER	VARCHAR2(128)		Name of the schema under which the skip option should be used

Column	Datatype	NULL	Description
NAME	VARCHAR2(261)		Name of the object that is being skipped
USE_LIKE	VARCHAR2(1)		Indicates whether the statement should use a SQL wildcard search when matching names (Y) or not (N)
ESC	VARCHAR2(1)		Escape character used when performing wildcard matches
PROC	VARCHAR2(392)		Name of a stored procedure that will be executed when processing the skip option

See Also:

- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_LOGSTDBY.SKIP_ERROR procedure
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_LOGSTDBY.SKIP procedure

6.192 DBA_LOGSTDBY_SKIP_TRANSACTION

DBA_LOGSTDBY_SKIP_TRANSACTION displays the skip settings chosen. This view is for logical standby databases only.

Column	Datatype	NULL	Description
XIDUSN	NUMBER		Transaction ID undo segment number
XIDSLT	NUMBER		Transaction ID slot number
XIDSQN	NUMBER		Transaction ID sequence number
CON_NAME	VARCHAR2(384)		Container name

6.193 DBA_LOGSTDBY_SUPPORT_MODE

DBA_LOGSTDBY_SUPPORT_MODE displays information about whether tables in the database are supported for logical standby.

The query results for this view depend on whether the database is currently undergoing a manual rolling upgrade performed using transient logical standby databases. If the database *is* undergoing such an upgrade, then this view displays information about whether tables in the database are supported for transient logical standby. If the database *is not* undergoing such an upgrade, then this view displays information about whether tables in the database are supported for logical standby.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Table owner
TABLE_NAME	VARCHAR2(128)		Table name

Column	Datatype	NULL	Description
SUPPORT_MODE	VARCHAR2(11)		If the database is currently undergoing a manual rolling upgrade performed using transient logical standby databases, then this column indicates whether the table is supported for transient logical standby. Otherwise, this column indicates whether the table is supported for logical standby. Possible values: • SUPPORTED - The table is fully supported • INTERNAL - The table is not supported because it contains data that should not be replicated. Such tables include mapping tables for index-organized tables, storage tables for nested tables, materialized view logs, secondary objects associated with domain indexes, and temporary tables. • UNSUPPORTED - The table is not supported because it contains a data type that is not supported or uses a feature that is not supported
EXPLANATION	VARCHAR2(4000)		Reason the table is not fully supported for transient logical standby This column is populated only when all of the following conditions are met: • The database is currently undergoing a manual rolling upgrade using transient logical standby databases • The value of the COMPATIBLE initialization parameter is 20.0 or higher • The value of the SUPPORT_MODE column is INTERNAL or UNSUPPORTED

6.194 DBA_LOGSTDBY_UNSUPPORTED

DBA_LOGSTDBY_UNSUPPORTED displays the schemas, tables, and columns in those tables that contain data types that are unsupported by logical standby.

The query results for this view depend on whether the database is currently undergoing a manual rolling upgrade performed using transient logical standby databases. If the database *is* undergoing such an upgrade, then this view displays information about tables in the database that are unsupported for transient logical standby. If the database *is not* undergoing such an upgrade, then this view displays information about tables in the database are unsupported for logical standby.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the unsupported table
TABLE_NAME	VARCHAR2(128)		Name of the unsupported table
COLUMN_NAME	VARCHAR2(128)		Name of the unsupported column

Column	Datatype	NULL	Description
ATTRIBUTES	VARCHAR2(4000)		If the database is currently undergoing a manual rolling upgrade performed using transient logical standby databases and the value of the COMPATIBLE initialization parameter is 20.0 or higher, then this column displays the reason the table is unsupported by SQL Apply.
DATA_TYPE	VARCHAR2(106)		Data type of the unsupported column

Note:

When the value of the COMPATIBLE initialization parameter is 20.0 or higher, this view displays all columns in unsupported tables. Otherwise, this view displays only the unsupported columns in unsupported tables.

Note:

A rolling upgrade performed using the DBMS_ROLLING PL/SQL package supports more object types than a manual rolling upgrade performed using transient logical standby databases.

See Also:

- "DBA_ROLLING_UNSUPPORTED" for more information about determining unsupported data types for a rolling upgrade using the DBMS_ROLLING package
- *Oracle Data Guard Concepts and Administration* for more information about rolling operations
- *Oracle Data Guard Concepts and Administration* for more information about unsupported tables for rolling upgrade operations
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_ROLLING package

6.195 DBA_LOGSTDBY_UNSUPPORTED_TABLE

DBA_LOGSTDBY_UNSUPPORTED_TABLE displays the data tables that are unsupported by logical standby.

The query results for this view depend on whether the database is currently undergoing a manual rolling upgrade performed using transient logical standby databases. If the database *is* undergoing such an upgrade, then this view displays information about tables in the database that are unsupported for transient logical

standby. If the database *is not* undergoing such an upgrade, then this view displays information about tables in the database are unsupported for logical standby.

The data displayed pertains to the container in which the view is queried.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the unsupported table
TABLE_NAME	VARCHAR2(128)		Name of the unsupported table
EXPLANATION	VARCHAR2(4000)		If the database is currently undergoing a manual rolling upgrade performed using transient logical standby databases, then this column displays the reason the table is unsupported for transient logical standby. Otherwise, this column displays the reason the table is unsupported for logical standby. This column is populated only when the value of the COMPATIBLE initialization parameter is 20.0 or higher.

6.196 DBA_MEASURE_FOLDER_CONTENTS

DBA_MEASURE_FOLDER_CONTENTS describes the contents of all OLAP measure folders in the database. Its columns are the same as those in ALL_MEASURE_FOLDER_CONTENTS.

> **See Also:**
>
> "ALL_MEASURE_FOLDER_CONTENTS"

6.197 DBA_MEASURE_FOLDER_SUBFOLDERS

DBA_MEASURE_FOLDER_SUBFOLDERS describes the OLAP measure folders contained within the database OLAP measure folders. Its columns are the same as those in ALL_MEASURE_FOLDER_SUBFOLDERS.

> **See Also:**
>
> "ALL_MEASURE_FOLDER_SUBFOLDERS"

6.198 DBA_MEASURE_FOLDERS

DBA_MEASURE_FOLDERS describes all OLAP measure folders in the database. Its columns are the same as those in ALL_MEASURE_FOLDERS.

> **See Also:**
>
> "ALL_MEASURE_FOLDERS"

6.199 DBA_METADATA_PROPERTIES

DBA_METADATA_PROPERTIES describes OLAP metadata properties in the database. Its columns are the same as those in ALL_METADATA_PROPERTIES.

> **See Also:**
>
> "ALL_METADATA_PROPERTIES"

6.200 DBA_METHOD_PARAMS

DBA_METHOD_PARAMS describes the method parameters of all object types in the database. Its columns are the same as those in ALL_METHOD_PARAMS.

> **See Also:**
>
> "ALL_METHOD_PARAMS"

6.201 DBA_METHOD_RESULTS

DBA_METHOD_RESULTS describes the method results of all object types in the database. Its columns are the same as those in ALL_METHOD_RESULTS.

> **See Also:**
>
> "ALL_METHOD_RESULTS"

6.202 DBA_MINING_MODEL_ATTRIBUTES

DBA_MINING_MODEL_ATTRIBUTES describes all machine learning model attributes in the database. Its columns are the same as those in ALL_MINING_MODEL_ATTRIBUTES.

> **See Also:**
>
> "ALL_MINING_MODEL_ATTRIBUTES"

6.203 DBA_MINING_MODEL_PARTITIONS

DBA_MINING_MODEL_PARTITIONS describes all the model partitions accessible to the system. Its columns are the same as those in ALL_MINING_MODEL_PARTITIONS.

> **See Also:**
>
> "ALL_MINING_MODEL_PARTITIONS"

6.204 DBA_MINING_MODEL_SETTINGS

DBA_MINING_MODEL_SETTINGS describes all machine learning model settings in the database. Its columns are the same as those in ALL_MINING_MODEL_SETTINGS.

> **See Also:**
>
> "ALL_MINING_MODEL_SETTINGS"

6.205 DBA_MINING_MODEL_TABLES

DBA_MINING_MODEL_TABLES describes the tables that contain metadata about the machine learning models in the database.

Machine learning models are schema objects created by Oracle Machine Learning for SQL (OML4SQL).

Model tables reside in the schema of the machine learning model owner. The metadata stored in the tables is controlled by OML4SQL APIs. The tables are read-only. They should not be modified by users.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the machine learning model
MODEL_NAME	VARCHAR2(128)	NOT NULL	Name of the machine learning model

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
TABLE_TYPE	VARCHAR2(21)		The type of metadata stored in the table

6.206 DBA_MINING_MODEL_VIEWS

DBA_MINING_MODEL_VIEWS describes all model views in the database. Its columns are the same as those in ALL_MINING_MODEL_VIEWS.

> **See Also:**
>
> "ALL_MINING_MODEL_VIEWS"

6.207 DBA_MINING_MODEL_XFORMS

DBA_MINING_MODEL_XFORMS describes the user-specified transformations embedded in all models accessible in the system. Its columns are the same as those in ALL_MINING_MODEL_XFORMS.

> **See Also:**
>
> "ALL_MINING_MODEL_XFORMS"

6.208 DBA_MINING_MODELS

DBA_MINING_MODELS describes all machine learning models in the database. Its columns are the same as those in ALL_MINING_MODELS.

> **See Also:**
>
> "ALL_MINING_MODELS"

6.209 DBA_MLE_ENV_IMPORTS

`DBA_MLE_ENV_IMPORTS` describes import name to module mappings in all Oracle Database Multilingual Engine (MLE) environments in the database. Its columns are the same as those in `ALL_MLE_ENV_IMPORTS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_MLE_ENV_IMPORTS"

6.210 DBA_MLE_ENVS

`DBA_MLE_ENVS` describes all Oracle Database Multilingual Engine (MLE) environments in the database. Its columns are the same as those in `ALL_MLE_ENVS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_MLE_ENVS"

6.211 DBA_MLE_MODULES

`DBA_MLE_MODULES` describes all Oracle Database Multilingual Engine (MLE) modules in the database. Its columns are the same as those in `ALL_MLE_MODULES`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_MLE_MODULES"

6.212 DBA_MLE_PROCEDURES

`DBA_MLE_PROCEDURES` describes all Oracle Database Multilingual Engine (MLE) functions and procedures in the database. Its columns are the same as those in `ALL_MLE_PROCEDURES`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_MLE_PROCEDURES"

6.213 DBA_MVIEW_AGGREGATES

`DBA_MVIEW_AGGREGATES` describes the grouping functions (aggregated measures) that appear in the `SELECT` list of all aggregated materialized view in the database. Its columns are the same as those in `ALL_MVIEW_AGGREGATES`.

> **See Also:**
>
> "ALL_MVIEW_AGGREGATES"

6.214 DBA_MVIEW_ANALYSIS

DBA_MVIEW_ANALYSIS describes all materialized views in the database that potentially support query rewrite and that provide additional information for analysis by applications. Its columns are the same as those in ALL_MVIEW_ANALYSIS.

> **Note:**
>
> This view excludes materialized views that reference remote tables or that include references to non-static values such as SYSDATE or USER. This view also excludes materialized views that were created as snapshots before Oracle8*i* and that were never altered to enable query rewrite.

> **See Also:**
>
> "ALL_MVIEW_ANALYSIS"

6.215 DBA_MVIEW_COMMENTS

DBA_MVIEW_COMMENTS displays comments on all materialized views in the database. Its columns are the same as those in ALL_MVIEW_COMMENTS.

> **See Also:**
>
> "ALL_MVIEW_COMMENTS"

6.216 DBA_MVIEW_DETAIL_LOGICAL_PARTITION

DBA_MVIEW_DETAIL_LOGICAL_PARTITION displays freshness information, with respect to logical partition change tracking (LPCT) detail partitions, for all materialized views in the database. Its columns are the same as those in ALL_MVIEW_DETAIL_LOGICAL_PARTITION.

> **See Also:**
>
> "ALL_MVIEW_DETAIL_LOGICAL_PARTITION"

6.217 DBA_MVIEW_DETAIL_PARTITION

DBA_MVIEW_DETAIL_PARTITION displays freshness information, with respect to partition change tracking (PCT) detail partitions, for all materialized views in the database. Its columns are the same as those in ALL_MVIEW_DETAIL_PARTITION.

> **See Also:**
>
> "ALL_MVIEW_DETAIL_PARTITION".

6.218 DBA_MVIEW_DETAIL_RELATIONS

DBA_MVIEW_DETAIL_RELATIONS represents the named detail relations that are either in the FROM list of a materialized view, or that are indirectly referenced through views in the FROM list. Its columns are the same as those in ALL_MVIEW_DETAIL_RELATIONS.

> **See Also:**
>
> "ALL_MVIEW_DETAIL_RELATIONS"

6.219 DBA_MVIEW_DETAIL_SUBPARTITION

DBA_MVIEW_DETAIL_SUBPARTITION displays freshness information, with respect to partition change tracking (PCT) detail subpartitions, for all materialized views in the database. Its columns are the same as those in ALL_MVIEW_DETAIL_SUBPARTITION.

> **See Also:**
>
> "ALL_MVIEW_DETAIL_SUBPARTITION"

6.220 DBA_MVIEW_JOINS

DBA_MVIEW_JOINS describes a join between two columns in the WHERE clause of a subquery that defines a materialized view. Its columns are the same as those in ALL_MVIEW_JOINS.

> **See Also:**
>
> "ALL_MVIEW_JOINS"

6.221 DBA_MVIEW_KEYS

DBA_MVIEW_KEYS describes the columns or expressions in the SELECT list upon which materialized views in the database are based. Its columns are the same as those in ALL_MVIEW_KEYS.

> **See Also:**
>
> "ALL_MVIEW_KEYS"

6.222 DBA_MVIEW_LOG_FILTER_COLS

DBA_MVIEW_LOG_FILTER_COLS displays all columns (excluding primary key columns) being logged in the materialized view logs.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the master table being logged
NAME	VARCHAR2(128)		Name of the master table being logged
COLUMN_NAME	VARCHAR2(128)		Column being logged

6.223 DBA_MVIEW_LOGS

DBA_MVIEW_LOGS describes all materialized view logs in the database. Its columns are the same as those in ALL_MVIEW_LOGS.

> **See Also:**
>
> "ALL_MVIEW_LOGS"

6.224 DBA_MVIEW_REFRESH_TIMES

DBA_MVIEW_REFRESH_TIMES describes refresh times of all materialized views in the database. Its columns are the same as those in ALL_MVIEW_REFRESH_TIMES.

> **See Also:**
>
> "ALL_MVIEW_REFRESH_TIMES"

6.225 DBA_MVIEWS

DBA_MVIEWS describes all materialized views in the database. Its columns are the same as those in ALL_MVIEWS.

> **See Also:**
>
> "ALL_MVIEWS"

6.226 DBA_MVREF_CHANGE_STATS

DBA_MVREF_CHANGE_STATS displays the change data load information on the base tables associated with a refresh run for all the materialized views for the database.

Related View

USER_MVREF_CHANGE_STATS displays the change data load information on the master tables associated with a refresh run for all the materialized views in the database that are accessible to the current user.

Column	Datatype	NULL	Description
TBL_OWNER	VARCHAR2(128)	NOT NULL	Owner of the master table for the materialized view
TBL_NAME	VARCHAR2(128)	NOT NULL	Name of the master table for the materialized view
MV_OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MV_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
REFRESH_ID	NUMBER	NOT NULL	The refresh ID of the refresh run
NUM_ROWS_INS	NUMBER		The number of inserts in the materialized view log of the table (applicable only if the table has a materialized view log)
NUM_ROWS_UPD	NUMBER		The number of updates in the materialized view log of the table (applicable only if the table has a materialized view log)
NUM_ROWS_DEL	NUMBER		The number of deletes in the materialized view log of the table (applicable only if the table has a materialized view log)
NUM_ROWS_DL_INS	NUMBER		The number of direct load inserts on the table
PMOPS_OCCURRED	CHAR(1)		Indicates whether a partition-maintenance operation (PMOP) occurred. Possible values: • Y • N • NULL: Indicates an unknown value
PMOP_DETAILS	VARCHAR2(4000)		Details of the PMOPs in the following format: • TRUNCATE (low_bound, high_bound) • EXECHANGE (low_bound, high_bound)

Column	Datatype	NULL	Description
NUM_ROWS	NUMBER		The number of rows in the table at the start of the refresh operation

> **See Also:**
>
> "USER_MVREF_CHANGE_STATS"

6.227 DBA_MVREF_RUN_STATS

DBA_MVREF_RUN_STATS has information about each refresh run for all the materialized views for the database, with each run being identified by the REFRESH_ID. The information includes timing statistics related to the run and the parameters specified in that run.

Related View

USER_MVREF_RUN_STATS has information about each refresh run for the materialized views accessible for the current database user, with each run being identified by the REFRESH_ID. The information includes timing statistics related to the run and the parameters specified in that run. This view does not display the RUN_OWNER column.

Column	Datatype	NULL	Description
RUN_OWNER	VARCHAR2(128)	NOT NULL	Owner of the refresh operation (the user who launched the operation)
REFRESH_ID	NUMBER	NOT NULL	The refresh ID of the refresh run
NUM_MVS	NUMBER	NOT NULL	The number of materialized views being refreshed in the run
MVIEWS	VARCHAR2(4000)		Shows the list of comma separated parameters specified in the API for the materialized view refresh operation
BASE_TABLES	VARCHAR2(4000)		For internal use only
METHOD	VARCHAR2(4000)		The METHOD parameter specified by the API
ROLLBACK_SEG	VARCHAR2(4000)		The ROLLBACK_SEG parameter specified by the API
PUSH_DEFERRED_RPC	CHAR(1)		The PUSH_DEFERRED_RPC parameter specified by the API
REFRESH_AFTER_ERRORS	CHAR(1)		The REFRESH_AFTER_ERRORS parameter specified by the API
PURGE_OPTION	NUMBER		The PURGE_OPTION parameter specified by the API
PARALLELISM	NUMBER		The PARALLELISM parameter specified by the API
HEAP_SIZE	NUMBER		The HEAP_SIZE parameter specified by the API
ATOMIC_REFRESH	CHAR(1)		The ATOMIC_REFRESH parameter specified by the API
NESTED	CHAR(1)		The NESTED parameter specified by the API
OUT_OF_PLACE	CHAR(1)		The OUT_OF_PLACE parameter specified by the API

Column	Datatype	NULL	Description
NUMBER_OF_FAILURES	NUMBER		The number of failures that occurred in processing the API
START_TIME	TIMESTAMP(6)		Start time of the refresh run
END_TIME	TIMESTAMP(6)		End time of the refresh run
ELAPSED TIME	NUMBER		The length of time for the refresh run, in seconds
LOG_SETUP_TIME	NUMBER		Log setup time (in seconds) for the materialized view for a non-atomic refresh; NULL for an atomic refresh
LOG_PURGE_TIME	NUMBER		Log purge time (in seconds) for the materialized view in the case of atomic refresh; NULL in the case of non-atomic refresh
COMPLETE_STATS_AVAILABLE	CHAR(1)		Indicates whether all the complete refresh statistics are available for this run: • Y: All the statistics are available • N: All the statistics are not available

See Also:

"USER_MVREF_RUN_STATS"

6.228 DBA_MVREF_STATS

DBA_MVREF_STATS shows the REFRESH_ID associated with each refresh run of each materialized view for the database. It also provides some basic timing statistics related to that materialized view's refresh in that run.

Related View

USER_MVREF_STATS shows the REFRESH_ID associated with each refresh run of each materialized view for the database that is accessible to the current user. It also provides some basic timing statistics related to that materialized view's refresh in that run. This view does not display the MV_OWNER column.

Column	Datatype	NULL	Description
MV_OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MV_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
REFRESH_ID	NUMBER	NOT NULL	The refresh ID of the refresh run
REFRESH_METHOD	VARCHAR2(30)		The refresh method used to refresh the materialized view: • FAST • PCT • COMPLETE • OUT OF PLACE FAST • OUT OF PLACE PCT • OUT OF PLACE COMPLETE

Column	Datatype	NULL	Description
REFRESH_OPTIMIZATIONS	VARCHAR2(4000)		The refresh optimization, for example, a null refresh, or a primary key/foreign key that is applied during refresh of the materialize view
ADDITIONAL_EXECUTIONS	VARCHAR2(4000)		The additional executions, for example, an index rebuild, or log operations involved during refresh of the materialized view
START_TIME	TIMESTAMP(6)		Start time of the refresh run
END_TIME	TIMESTAMP(6)		End time of the refresh run
ELAPSED_TIME	NUMBER		The length of time for the refresh run, in seconds
LOG_SETUP_TIME	NUMBER		Log setup time (in seconds) for the materialized view for a non-atomic refresh; NULL for an atomic refresh
LOG_PURGE_TIME	NUMBER		Log purge time (in seconds) for the materialized view in the case of atomic refresh; NULL in the case of non-atomic refresh
INITIAL_NUM_ROWS	NUMBER		Initial number of rows in the materialized view (at the start of the refresh)
FINAL_NUM_ROWS	NUMBER		Final number of rows in the materialized view (at the end of the refresh)

See Also:

"USER_MVREF_STATS"

6.229 DBA_MVREF_STATS_PARAMS

DBA_MVREF_STATS_PARAMS displays the refresh statistics properties associated with each materialized view. These properties can be modified with the DBMS_MVIEW_STATS.SET_MVREF_STATS_PARAMS procedure.

Related View

USER_MVREF_STATS_PARAMS displays the refresh statistics properties associated with each materialized view accessible to the current user. These properties can be modified with the DBMS_MVIEW_STATS.SET_MVREF_STATS_PARAMS procedure.

Column	Datatype	NULL	Description
MV_OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MV_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
COLLECTION_LEVEL	VARCHAR2(8)		The collection level for the materialized view
RETENTION_PERIOD	NUMBER		The retention period for the materialize view

> **See Also:**
>
> "USER_MVREF_STATS_PARAMS"

6.230 DBA_MVREF_STATS_SYS_DEFAULTS

DBA_MVREF_STATS_SYS_DEFAULTS displays the system-wide defaults for the refresh history statistics properties for materialized views. These values can be altered with the SET_SYSTEM_DEFAULTS procedure by a database administrator.

This view contains exactly two rows corresponding to the collection-level and retention-period properties; their initial values are TYPICAL and 31 respectively.

Related View

USER_MVREF_STATS_SYS_DEFAULTS displays the system-wide defaults for the refresh history statistics properties for materialized views accessible to the current user. These values can be altered with the SET_SYSTEM_DEFAULTS procedure by a database administrator.

Column	Datatype	NULL	Description
PARAMETER_NAME	CHAR(16)		Value of the parameter_name parameter: • COLLECTION_LEVEL • RETENTION_PERIOD
VALUE	VARCHAR2(40)		The system-wide default value for the parameter

> **See Also:**
>
> "USER_MVREF_STATS_SYS_DEFAULTS"

6.231 DBA_MVREF_STMT_STATS

DBA_MVREF_STMT_STATS shows information associated with each refresh statement of a materialized view in a refresh run.

Related View

USER_MVREF_STMT_STATS shows information associated with each refresh statement of a materialized view accessible to the current user in a refresh run.

Column	Datatype	NULL	Description
MV_OWNER	VARCHAR2(128)	NOT NULL	Owner of the materialized view
MV_NAME	VARCHAR2(128)	NOT NULL	Name of the materialized view
REFRESH_ID	NUMBER	NOT NULL	The refresh ID of the refresh run

Column	Datatype	NULL	Description
STEP	NUMBER	NOT NULL	A number indicating the step in the refresh process in which the statement is executed for the materialized view. Steps are numbered consecutively starting at 1.
SQLID	VARCHAR2(14)	NOT NULL	The SQL ID of the statement
STMT	CLOB	NOT NULL	The text of the SQL statement
EXECUTION_TIME	NUMBER	NOT NULL	The time it took to execute the statement (in seconds)
EXECUTION_PLAN	XMLTYPE STORAGE NOT TRANSPORTABLE BINARY		For internal use only

See Also:

"USER_MVREF_STMT_STATS"

6.232 DBA_NESTED_TABLE_COLS

DBA_NESTED_TABLE_COLS describes the columns of all nested tables in the database. Its columns are the same as those in ALL_NESTED_TABLE_COLS.

To gather statistics for this view, use the DBMS_STATS package.

See Also:

"ALL_NESTED_TABLE_COLS"

6.233 DBA_NESTED_TABLES

DBA_NESTED_TABLES describes all nested tables contained in all tables in the database. Its columns are the same as those in ALL_NESTED_TABLES.

See Also:

"ALL_NESTED_TABLES"

6.234 DBA_NETWORK_ACL_PRIVILEGES

DBA_NETWORK_ACL_PRIVILEGES describes the network privileges defined in all access control lists that are currently assigned to network hosts.

> **Note:**
>
> This DBA_NETWORK_ACL_PRIVILEGES view is deprecated in Oracle Database 12*c* Release 1 (12.1). Oracle recommends that you use the DBA_HOST_ACES view, instead.

Column	Datatype	NULL	Description
ACL	VARCHAR2(4000)		Path of the access control list
ACLID	RAW(8)	NOT NULL	Object ID of the access control list
PRINCIPAL	VARCHAR2(128)		Principal (database user or role) whom the privilege is granted to or denied from
PRIVILEGE	VARCHAR2(128)		Network privilege
IS_GRANT	VARCHAR2(5)		Indicates whether the privilege is granted (true) or denied (false)
INVERT	VARCHAR2(5)		Indicates whether the access control entry contains invert principal (true) or not (false)
START_DATE	TIMESTAMP(6)		Start date of the access control entry
END_DATE	TIMESTAMP(6)		End date of the access control entry
ACL_OWNER	VARCHAR2(128)		Owner of the access control list

> **See Also:**
>
> "DBA_HOST_ACES"

6.235 DBA_NETWORK_ACLS

DBA_NETWORK_ACLS describes the access control list assignments to network hosts.

> **Note:**
>
> This DBA_NETWORK_ACLS view is deprecated in Oracle Database 12*c* Release 1 (12.1). Oracle recommends that you use the DBA_HOST_ACLS view, instead.

Column	Datatype	NULL	Description
HOST	VARCHAR2(1000)	NOT NULL	Network host

Column	Datatype	NULL	Description
LOWER_PORT	NUMBER(5)		Lower bound of the port range
UPPER_PORT	NUMBER(5)		Upper bound of the port range
ACL	VARCHAR2(4000)		Path of the access control list
ACLID	RAW(8)		Object ID of the access control list
ACL_OWNER	VARCHAR2(128)		Owner of the access control list

> **See Also:**
>
> "DBA_HOST_ACLS"

6.236 DBA_OBJ_AUDIT_OPTS

DBA_OBJ_AUDIT_OPTS describes auditing options on all objects.

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

Related View

USER_OBJ_AUDIT_OPTS describes auditing options on all objects owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the object
OBJECT_NAME	VARCHAR2(128)		Name of the object
OBJECT_TYPE	VARCHAR2(23)		Type of the object
ALT	VARCHAR2(3)		Auditing ALTER WHENEVER SUCCESSFUL / UNSUCCESSFUL
AUD	VARCHAR2(3)		Auditing AUDIT WHENEVER SUCCESSFUL / UNSUCCESSFUL
COM	VARCHAR2(3)		Auditing COMMENT WHENEVER SUCCESSFUL / UNSUCCESSFUL
DEL	VARCHAR2(3)		Auditing DELETE WHENEVER SUCCESSFUL / UNSUCCESSFUL
GRA	VARCHAR2(3)		Auditing GRANT WHENEVER SUCCESSFUL / UNSUCCESSFUL

Column	Datatype	NULL	Description
IND	VARCHAR2(3)		Auditing INDEX WHENEVER SUCCESSFUL / UNSUCCESSFUL
INS	VARCHAR2(3)		Auditing INSERT WHENEVER SUCCESSFUL / UNSUCCESSFUL
LOC	VARCHAR2(3)		Auditing LOCK WHENEVER SUCCESSFUL / UNSUCCESSFUL
REN	VARCHAR2(3)		Auditing RENAME WHENEVER SUCCESSFUL / UNSUCCESSFUL
SEL	VARCHAR2(3)		Auditing SELECT WHENEVER SUCCESSFUL / UNSUCCESSFUL
UPD	VARCHAR2(3)		Auditing UPDATE WHENEVER SUCCESSFUL / UNSUCCESSFUL
EXE	VARCHAR2(3)		Auditing EXECUTE WHENEVER SUCCESSFUL / UNSUCCESSFUL
CRE	VARCHAR2(3)		Auditing CREATE WHENEVER SUCCESSFUL / UNSUCCESSFUL
REA	VARCHAR2(3)		Auditing READ WHENEVER SUCCESSFUL / UNSUCCESSFUL
WRI	VARCHAR2(3)		Auditing WRITE WHENEVER SUCCESSFUL / UNSUCCESSFUL
FBK	VARCHAR2(3)		Auditing FLASHBACK WHENEVER SUCCESSFUL / UNSUCCESSFUL

See Also:

- "USER_OBJ_AUDIT_OPTS"
- *Oracle Database SQL Language Reference* for more information about the SQL AUDIT statement for unified auditing
- *Oracle Database SQL Language Reference* for more information about the SQL AUDIT statement for traditional auditing
- *Oracle Database Security Guide* to learn how to find information about audited activities

6.237 DBA_OBJ_COLATTRS

DBA_OBJ_COLATTRS describes object columns and attributes contained in all tables in the database. Its columns are the same as those in ALL_OBJ_COLATTRS.

See Also:

"ALL_OBJ_COLATTRS"

6.238 DBA_OBJECT_SIZE

DBA_OBJECT_SIZE lists the sizes, in bytes, of various PL/SQL objects.

Related View

- USER_OBJECT_SIZE lists the size of PL/SQL objects owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
NAME	VARCHAR2(128)	NOT NULL	Name of the object
TYPE	VARCHAR2(18)		Type of the object: TYPE, TYPE BODY, TABLE, VIEW, SYNONYM, SEQUENCE, PROCEDURE, FUNCTION, PACKAGE, PACKAGE BODY, JAVA SOURCE, JAVA CLASS or JAVA RESOURCE
SOURCE_SIZE	NUMBER		Size of the source in bytes. Must be in memory during compilation, or dynamic recompilation.
PARSED_SIZE	NUMBER		Size of the parsed form of the object, in bytes. Must be in memory when an object is being compiled that references this object.
CODE_SIZE	NUMBER		Code size, in bytes. Must be in memory when this object is executing.
ERROR_SIZE	NUMBER		Size of error messages, in bytes. In memory during the compilation of the object when there are compilation errors.

See Also:

"USER_OBJECT_SIZE"

6.239 DBA_OBJECT_TABLES

DBA_OBJECT_TABLES describes all object tables in the database. Its columns are the same as those in ALL_OBJECT_TABLES.

See Also:

"ALL_OBJECT_TABLES"

6.240 DBA_OBJECT_USAGE

DBA_OBJECT_USAGE displays statistics about index usage gathered from the database for all the indexes in the database.

You can use this view to monitor index usage. All indexes that have been used at least once can be monitored and displayed in this view.

Related View

- USER_OBJECT_USAGE displays statistics about index usage gathered from the database for the indexes owned by the current user.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Index owner
INDEX_NAME	VARCHAR2(128)	NOT NULL	Index name in sys.obj$.name
TABLE_NAME	VARCHAR2(128)	NOT NULL	Table name in sys.obj$.name
MONITORING	VARCHAR2(3)		Indicates whether the monitoring feature is turned on. Possible values: • YES • NO
USED	VARCHAR2(3)		Indicates whether the index has been accessed. Possible values: • YES • NO
START_MONITORING	VARCHAR2(19)		Start monitoring time in sys.object_stats.start_monitoring
END_MONITORING	VARCHAR2(19)		End monitoring time in sys.object_stats.end_monitoring

See Also:

"USER_OBJECT_USAGE"

6.241 DBA_OBJECTS

DBA_OBJECTS describes all objects in the database. Its columns are the same as those in ALL_OBJECTS.

See Also:

"ALL_OBJECTS"

6.242 DBA_OBJECTS_AE

DBA_OBJECTS_AE describes all objects (across all editions) in the database. Its columns are the same as those in ALL_OBJECTS_AE.

> **See Also:**
>
> "ALL_OBJECTS_AE"

6.243 DBA_OGG_AUTO_CAPTURED_TABLES

DBA_OGG_AUTO_CAPTURED_TABLES describes all tables in the database that are enabled for Oracle GoldenGate automatic capture.

Related View

USER_OGG_AUTO_CAPTURED_TABLES describes the tables owned by the current user that are enabled for Oracle GoldenGate automatic capture. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table
NAME	VARCHAR2(128)	NOT NULL	Name of the table
ALLOW_NOVALIDATE_PK	VARCHAR2(3)		Indicates whether a primary key constraint in NOVALIDATE mode can be used as a unique identifier for the table (YES) or not (NO)

> **See Also:**
>
> "USER_OGG_AUTO_CAPTURED_TABLES"

6.244 DBA_OPANCILLARY

DBA_OPANCILLARY provides ancillary information for all operator bindings in the database. Its columns are the same as those in ALL_OPANCILLARY.

> **See Also:**
>
> "ALL_OPANCILLARY"

6.245 DBA_OPARGUMENTS

DBA_OPARGUMENTS provides argument information for all operator bindings in the database. Its columns are the same as those in ALL_OPARGUMENTS.

> **See Also:**
>
> "ALL_OPARGUMENTS"

6.246 DBA_OPBINDINGS

DBA_OPBINDINGS describes the binding functions and methods on all operators in the database. Its columns are the same as those in ALL_OPBINDINGS.

> **See Also:**
>
> "ALL_OPBINDINGS"

6.247 DBA_OPERATOR_COMMENTS

DBA_OPERATOR_COMMENTS displays comments for all user-defined operators in the database. Its columns are the same as those in ALL_OPERATOR_COMMENTS.

> **See Also:**
>
> "ALL_OPERATOR_COMMENTS"

6.248 DBA_OPERATORS

DBA_OPERATORS describes all operators in the database. Its columns are the same as those in ALL_OPERATORS.

> **See Also:**
>
> "ALL_OPERATORS"

6.249 DBA_OPTSTAT_OPERATION_TASKS

DBA_OPTSTAT_OPERATION_TASKS displays the history of tasks that are performed as part of statistics operations (recorded in DBA_OPTSTAT_OPERATIONS). Each task represents a target object to be processed in the corresponding parent operation.

Column	Datatype	NULL	Description
OPID	NUMBER		Internal identifier for the statistics operation that the task belongs to
TARGET	VARCHAR2(100)		Name of the object that this task operates on
TARGET_OBJN	NUMBER		Object number of the target object
TARGET_TYPE	VARCHAR2(40)		Type of the target object. Possible values are: • TABLE • TABLE (GLOBAL STATS ONLY): Task is created to gather only global statistics of a partitioned table • TABLE (COORDINATOR JOB): Coordinator task for a partitioned table when concurrency is on • TABLE PARTITION • TABLE SUBPARTITION • INDEX • INDEX PARTITION • INDEX SUBPARTITION
TARGET_SIZE	NUMBER		Target size (in number of blocks) when the task started
START_TIME	TIMESTAMP(6) WITH TIME ZONE		Task start time
END_TIME	TIMESTAMP(6) WITH TIME ZONE		Task end time
STATUS	VARCHAR2(49)		Current task status. Possible values are: • PENDING: Task is queued for processing • IN PROGRESS: Task is currently running • COMPLETED: Task has completed successfully • FAILED: Task has failed • SKIPPED: Task has been skipped, as it does not exist any more, or its stats are not stale (applies only to only automatic statistics gathering) • TIMED OUT: Maintenance window was not enough to complete this task (applies only to automatic statistics gathering)
JOB_NAME	VARCHAR2(50)		Name of the scheduler job that executes this task (for example, when concurrency is on)
ESTIMATED_COST	NUMBER		Estimated cost of the task (measured as elapsed time in seconds). This column is populated only when concurrency is on.
BATCHING_COEFF	NUMBER		For internal use only
ACTIONS	NUMBER		For internal use only

Column	Datatype	NULL	Description
PRIORITY	NUMBER		Rank of the task among all target objects for the parent operation
FLAGS	NUMBER		For internal use only
NOTES	VARCHAR2(4000)		Notes about the underlying task, such as the failure message for tasks with status FAILED.

> **See Also:**
>
> "DBA_OPTSTAT_OPERATIONS"

6.250 DBA_OPTSTAT_OPERATIONS

DBA_OPTSTAT_OPERATIONS contains a history of statistics operations performed at the schema and database level using the DBMS_STATS package.

Column	Datatype	NULL	Description
ID	NUMBER		Internal ID of the statistics operation
OPERATION	VARCHAR2(64)		Operation name
TARGET	VARCHAR2(64)		Target on which the operation was performed
START_TIME	TIMESTAMP(6) WITH TIME ZONE		Time at which the operation started
END_TIME	TIMESTAMP(6) WITH TIME ZONE		Time at which the operation ended
STATUS	VARCHAR2(49)		Current operation status. Possible values are: • IN PROGRESS: Operation is currently running • COMPLETED: Operation has completed successfully • FAILED: Operation has failed • TIMED OUT: Maintenance window was not enough to complete this operation (applies only to automatic statistics gathering)
JOB_NAME	VARCHAR2(32)		Name of the scheduler job that executes this operation (for example, a user scheduled statistics gathering job)
SESSION_ID	NUMBER		ID of the session in which this operation is invoked
NOTES	VARCHAR2(4000)		Notes about the operation, such as a failure message for operations with status FAILED

See Also:

- "DBA_OPTSTAT_OPERATION_TASKS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_REPAIR.ADMIN_TABLES procedure
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_REPAIR.DUMP_ORPHAN_KEYS procedure

6.251 DBA_ORPHAN_KEY_TABLE

DBA_ORPHAN_KEY_TABLE reports key values from indexes where the underlying base table has block corruptions.

To create the view, run the DBMS_REPAIR.ADMIN_TABLES procedure. To populate the orphan key table for an index, run the DBMS_REPAIR.DUMP_ORPHAN_KEYS procedure on the index. For each key in the index that points to a corrupt data block, Oracle inserts a row into the orphan key table.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Schema name of the index
INDEX_NAME	VARCHAR2(128)	NOT NULL	Name of the index
IPART_NAME	VARCHAR2(128)	NULL	Name of the index partition or subpartition
INDEX_ID	NUMBER	NOT NULL	Dictionary object ID of the index
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the base table of the index
PART_NAME	VARCHAR2(128)	NULL	Name of the base table partition or subpartition
TABLE_ID	NUMBER	NOT NULL	Dictionary object ID of the base table
KEYROWID	ROWID	NOT NULL	Physical rowid of the corrupt data row
KEY	ROWID	NOT NULL	Key values for the index entry
DUMP_TIMESTAMP	DATE	NOT NULL	Timestamp when the entry was made into the orphan key table

6.252 DBA_OUTLINE_HINTS

DBA_OUTLINE_HINTS describes the set of hints stored in all outlines in the database.

Related View

USER_OUTLINE_HINTS describes the set of hints stored in the outlines owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
NAME	VARCHAR2(128)		Name of the outline

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Name of the user who created the outline
NODE	NUMBER		ID of the query or subquery to which the hint applies. The top-level query is labeled 1. Subqueries are assigned sequentially numbered labels, starting with 2.
STAGE	NUMBER		Outline hints can be applied at three different stages during the compilation process. This column indicates the stage at which this hint was applied.
JOIN_POS	NUMBER		Position of the table in the join order. The value is 0 for all hints except access method hints, which identify a table to which the hint and the join position apply.
HINT	CLOB		Text of the hint

> **See Also:**
>
> "USER_OUTLINE_HINTS"

6.253 DBA_OUTLINES

DBA_OUTLINES describes all stored outlines in the database.

Related View

USER_OUTLINES describes the stored outlines owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
NAME	VARCHAR2(128)		User-specified or generated name of the stored outline. The name must be of a form that can be expressed in SQL.
OWNER	VARCHAR2(128)		Name of the user who created the outline
CATEGORY	VARCHAR2(128)		User-defined name of the category to which the outline belongs
USED	VARCHAR2(6)		Indicates whether the outline has ever been used (USED) or not (UNUSED)
TIMESTAMP	DATE		Timestamp of outline creation
VERSION	VARCHAR2(64)		Oracle version that created the outline

Column	Datatype	NULL	Description
SQL_TEXT	LONG		SQL text of the query, including any hints that were a part of the original statement. If bind variables are included, the variable names are stored as SQL text, not the values that are assigned to the variables. **Note:** This field may contain sensitive information about your database or application. Therefore, use discretion when granting SELECT or VIEW object privileges on these views.
SIGNATURE	RAW(16)		Signature uniquely identifying the outline SQL text
COMPATIBLE	VARCHAR2(12)		Indicates whether the outline hints were compatible across a migration (COMPATIBLE) or not (INCOMPATIBLE)
ENABLED	VARCHAR2(8)		Indicates whether the outline is enabled (ENABLED) or disabled (DISABLED)
FORMAT	VARCHAR2(6)		Hint format: • NORMAL • LOCAL
MIGRATED	VARCHAR2(12)		Indicates whether the outline has been migrated to a SQL plan baseline (MIGRATED) or not (NOT-MIGRATED)

See Also:

"USER_OUTLINES"

6.254 DBA_OUTSTANDING_ALERTS

DBA_OUTSTANDING_ALERTS describes alerts which the server considers to be outstanding.

Column	Datatype	NULL	Description
SEQUENCE_ID	NUMBER		Alert sequence number
REASON_ID	NUMBER	NOT NULL	ID of the alert reason
OWNER	VARCHAR2(128)		Owner of the object on which the alert was issued
OBJECT_NAME	VARCHAR2(513)		Name of the object
SUBOBJECT_NAME	VARCHAR2(128)		Name of the subobject (for example: partition)
OBJECT_TYPE	VARCHAR2(64)		Object type (for example: table, tablespace)
REASON	VARCHAR2(4000)		Reason for the alert
TIME_SUGGESTED	TIMESTAMP(6) WITH TIME ZONE		Time when the alert was last updated
CREATION_TIME	TIMESTAMP(6) WITH TIME ZONE		Time when the alert was first created
SUGGESTED_ACTION	VARCHAR2(4000)		Advice of the recommended action

Column	Datatype	NULL	Description
ADVISOR_NAME	VARCHAR2(128)		Name of the advisor to be invoked for more information
METRIC_VALUE	NUMBER		Value of the related metrics
MESSAGE_TYPE	VARCHAR2(12)		Message type: • Notification • Warning
MESSAGE_GROUP	VARCHAR2(64)		Name of the message group to which the alert belongs
MESSAGE_LEVEL	NUMBER		Message severity level (1 to 32)
HOSTING_CLIENT_ID	VARCHAR2(64)		ID of the client or security group to which the alert relates
MODULE_ID	VARCHAR2(64)		ID of the module that originated the alert
PROCESS_ID	VARCHAR2(128)		Process ID
HOST_ID	VARCHAR2(256)		DNS host name of the originating host
HOST_NW_ADDR	VARCHAR2(256)		IP or other network address of the originating host
INSTANCE_NAME	VARCHAR2(16)		Originating instance name
INSTANCE_NUMBER	NUMBER		Originating instance number
USER_ID	VARCHAR2(128)		User ID
EXECUTION_CONTEXT_ID	VARCHAR2(128)		Execution Context ID
ERROR_INSTANCE_ID	VARCHAR2(142)		ID of an error instance plus a sequence number
STATE_TRANSITION_NUMBER	NUMBER		Sequence number of the state transition for the alert
PDB_NAME	VARCHAR2(128)		PDB name
CON_ID	NUMBER	NOT NULL	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

6.255 DBA_PARALLEL_EXECUTE_CHUNKS

DBA_PARALLEL_EXECUTE_CHUNKS displays the chunks for all tasks in the database.

Related View

USER_PARALLEL_EXECUTE_CHUNKS displays the chunks for tasks created by the current user. This view does not display the TASK_OWNER column.

Column	Datatype	NULL	Description
CHUNK_ID	NUMBER	NOT NULL	Unique ID for the chunk
TASK_OWNER	VARCHAR2(128)	NOT NULL	Owner of the task

Column	Datatype	NULL	Description
TASK_NAME	VARCHAR2(128)	NOT NULL	Name of the task
STATUS	VARCHAR2(20)		Status of the chunk: • UNASSIGNED • ASSIGNED • PROCESSED • PROCESSED_WITH_ERROR
START_ROWID	ROWID		Rowid for the first row in the chunk
END_ROWID	ROWID		Rowid for the last row in the chunk
START_ID	NUMBER		Number column value of the first row in the chunk
END_ID	NUMBER		Number column value of the last row in the chunk
JOB_NAME	VARCHAR2(128)		Name of the job which processed this chunk
START_TS	TIMESTAMP(6)		Processing start time for the chunk
END_TS	TIMESTAMP(6)		Processing end time for the chunk
ERROR_CODE	NUMBER		Error code returned during the execution of the chunk if the STATUS column is PROCESSED_WITH_ERROR
ERROR_MESSAGE	VARCHAR2(4000)		Error message returned during the execution of the chunk if the STATUS column is PROCESSED_WITH_ERROR

See Also:

"USER_PARALLEL_EXECUTE_CHUNKS"

6.256 DBA_PARALLEL_EXECUTE_TASKS

DBA_PARALLEL_EXECUTE_TASKS displays all tasks in the database.

Related View

USER_PARALLEL_EXECUTE_TASKS displays the tasks created by the current user. This view does not display the TASK_OWNER column.

Column	Datatype	NULL	Description
TASK_OWNER	VARCHAR2(128)	NOT NULL	Owner of the task
TASK_NAME	VARCHAR2(128)	NOT NULL	Name of the task
CHUNK_TYPE	VARCHAR2(12)		Type of parallel update: • UNDELARED • ROWID_RANGE • NUMBER_RANGE

Column	Datatype	NULL	Description
STATUS	VARCHAR2(19)		Status of the task: • CREATED • CHUNKING • CHUNKING_FAILED • CHUNKED • PROCESSING • FINISHED • FINISHED_WITH_ERROR • CRASHED
TABLE_OWNER	VARCHAR2(128)		Owner of the table to be chunked
TABLE_NAME	VARCHAR2(128)		Name of the table to be chunked
NUMBER_COLUMN	VARCHAR2(128)		Name of the column holding IDs (only applicable to NUMBER_RANGE chunking type)
TASK_COMMENT	VARCHAR2(4000)		Comment field
JOB_PREFIX	VARCHAR2(128)		Prefix of the job name executing this task
SQL_STMT	CLOB		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK
LANGUAGE_FLAG	NUMBER		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK
EDITION	VARCHAR2(130)		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK
APPLY_CROSSEDITION_TRIGGER	VARCHAR2(130)		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK
FIRE_APPLY_TRIGGER	VARCHAR2(10)		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK
PARALLEL_LEVEL	NUMBER		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK
JOB_CLASS	VARCHAR2(128)		Argument used in the previous DBMS_PARALLEL_EXECUTE.RUN_TASK

See Also:

- "USER_PARALLEL_EXECUTE_TASKS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PARALLEL_EXECUTE.RUN_TASK procedure

6.257 DBA_PART_COL_STATISTICS

`DBA_PART_COL_STATISTICS` displays column statistics and histogram information for all table partitions in the database. Its columns are the same as those in `ALL_PART_COL_STATISTICS`.

> **See Also:**
>
> "ALL_PART_COL_STATISTICS"

6.258 DBA_PART_HISTOGRAMS

`DBA_PART_HISTOGRAMS` displays the histogram data (endpoints per histogram) for the histograms on all table partitions in the database. Its columns are the same as those in `ALL_PART_HISTOGRAMS`.

> **See Also:**
>
> "ALL_PART_HISTOGRAMS"

6.259 DBA_PART_INDEXES

`DBA_PART_INDEXES` displays the object-level partitioning information for all partitioned indexes in the database. Its columns are the same as those in `ALL_PART_INDEXES`.

> **See Also:**
>
> "ALL_PART_INDEXES"

6.260 DBA_PART_KEY_COLUMNS

`DBA_PART_KEY_COLUMNS` describes the partitioning key columns for all partitioned objects in the database. Its columns are the same as those in `ALL_PART_KEY_COLUMNS`.

> **See Also:**
>
> "ALL_PART_KEY_COLUMNS"

6.261 DBA_PART_LOBS

DBA_PART_LOBS displays table-level information for all partitioned LOBs in the database, including default attributes for LOB data partitions. Its columns are the same as those in ALL_PART_LOBS.

> **See Also:**
>
> "ALL_PART_LOBS"

6.262 DBA_PART_TABLES

DBA_PART_TABLES displays the object-level partitioning information for all partitioned tables in the database. Its columns are the same as those in ALL_PART_TABLES.

> **See Also:**
>
> "ALL_PART_TABLES"

6.263 DBA_PARTIAL_DROP_TABS

DBA_PARTIAL_DROP_TABS describes all tables in the database that have partially completed DROP COLUMN operations. Its columns are the same as those in ALL_PARTIAL_DROP_TABS.

> **See Also:**
>
> "ALL_PARTIAL_DROP_TABS"

6.264 DBA_PDB_HISTORY

DBA_PDB_HISTORY describes the lineage of the PDB to which it belongs.

Column	Datatype	NULL	Description
PDB_NAME	VARCHAR2(128)	NOT NULL	Name of this PDB in one of its incarnations
PDB_ID	NUMBER	NOT NULL	Container ID of this PDB in one of its incarnations.
PDB_DBID	NUMBER	NOT NULL	Database ID of this PDB in one of its incarnations
PDB_GUID	RAW(16)	NOT NULL	Globally unique ID of this PDB in one of its incarnations

Column	Datatype	NULL	Description
OP_SCNBAS	NUMBER	NOT NULL	SCN base when an operation was performed on one of the incarnations of this PDB
OP_SCNWRP	NUMBER	NOT NULL	SCN wrap when an operation was performed on one of incarnations of this PDB
OP_TIMESTAMP	DATE	NOT NULL	Timestamp of an operation performed on one of the incarnations of this PDB
OPERATION	VARCHAR2(16)	NOT NULL	Operation that was performed on one of the incarnations of this PDB
DB_VERSION	NUMBER	NOT NULL	Database version
CLONED_FROM_PDB_NAME	VARCHAR2(128)		Name of a PDB from which one of the incarnations of this PDB was cloned
CLONED_FROM_PDB_DBID	NUMBER		Database ID of a PDB from which one of the incarnations of this PDB was cloned
CLONED_FROM_PDB_GUID	RAW(16)		Globally unique ID of a PDB from which one of the incarnations of this PDB was cloned
DB_NAME	VARCHAR2(128)		Name of a CDB in which one of the incarnations of this PDB was created
DB_UNIQUE_NAME	VARCHAR2(128)		Unique name of a CDB in which one of the incarnations of this PDB was created
DB_DBID	NUMBER		Database ID of a CDB in which one of the incarnations of this PDB was created
CLONETAG	VARCHAR2(128)		Clone tag name for the PDB if the PDB was cloned using the snapshot copy mechanism
DB_VERSION_STRING	VARCHAR2(204)		Database version string

6.265 DBA_PDB_SAVED_STATES

DBA_PDB_SAVED_STATES shows information about the current saved PDB states in the CDB.

This view is a data link, so the data is also available within the PDB.

Column	Datatype	NULL	Description
CON_ID	NUMBER	NOT NULL	The ID of the PDB
CON_NAME	VARCHAR2(128)	NOT NULL	Name of the PDB
INSTANCE_NAME	VARCHAR2(128)	NOT NULL	Name of the instance for which the state is saved
CON_UID	NUMBER	NOT NULL	Unique ID assigned to the PDB at creation time
GUID	RAW(16)		Globally unique immutable ID assigned to the PDB at creation time
STATE	VARCHAR2(14)		Open state of the PDB
RESTRICTED	VARCHAR2(3)		Restricted mode of the PDB

> **See Also:**
>
> *Oracle Database SQL Language Reference* for more information about preserving a PDB's open mode across an instance restart

6.266 DBA_PDB_SNAPSHOTFILE

DBA_PDB_SNAPSHOTFILE displays the files associated with snapshots taken of pluggable databases (PDBs).

You can use this view in conjunction with the DBA_PDB_SNAPSHOT view. Join the SNAPSHOT_SCN column in this view with the SNAPSHOT_SCN column in DBA_PDB_SNAPSHOT to determine the files associated with a particular PDB snapshot. A PDB snapshot consists of an archive log file, one or more data files, and one or more XML files. A row is added to this view for each file associated with a PDB snapshot.

Column	Datatype	NULL	Description
CON_ID	NUMBER	NOT NULL	The ID of the PDB
SNAPSHOT_SCN	NUMBER	NOT NULL	SCN at which the snapshot was taken
SNAPSHOT_FILENAME	VARCHAR2(513)	NOT NULL	Snapshot file name
SNAPSHOT_FILETYPE	VARCHAR2(8)	NOT NULL	Snapshot file type. Possible values: • ARCH: Archive log file • DATA: Data file • XML: XML file

> **See Also:**
>
> "DBA_PDB_SNAPSHOTS"

6.267 DBA_PDB_SNAPSHOTS

DBA_PDB_SNAPSHOTS describes the snapshots taken of pluggable databases (PDBs).

Rows are added to this view when a snapshot of a PDB is taken by using the ALTER PLUGGABLE DATABASE SNAPSHOT SQL statement.

Column	Datatype	NULL	Description
CON_ID	NUMBER	NOT NULL	The ID of the PDB
CON_UID	NUMBER	NOT NULL	Unique ID assigned to the PDB at creation time
CON_NAME	VARCHAR2(128)	NOT NULL	Name of the PDB
SNAPSHOT_NAME	VARCHAR2(128)	NOT NULL	Snapshot name of the PDB
SNAPSHOT_SCN	NUMBER	NOT NULL	SCN at which the snapshot was taken
PREVIOUS_SNAPSHOT_SCN	NUMBER	NOT NULL	SCN at which the previous snapshot for the PDB was taken

Column	Datatype	NULL	Description
SNAPSHOT_TIME	NUMBER	NOT NULL	Timestamp at which the snapshot was taken
PREVIOUS_SNAPSHOT_TIME	NUMBER	NOT NULL	Timestamp of the previous snapshot for this PDB
FULL_SNAPSHOT_PATH	VARCHAR2(4000)	NOT NULL	Full path for the snapshot

Note:

This view does not display snapshot copy PDBs, which are created by using the `CREATE PLUGGABLE DATABASE ... SNAPSHOT COPY` SQL statement.

See Also:

"DBA_PDB_SNAPSHOTFILE" for information about the files associated with a particular PDB snapshot

6.268 DBA_PDBS

`DBA_PDBS` describes PDBs belonging to a given CDB.

When queried from a CDB root, this view describes all PDBs that belong to the CDB. When queried from an application root, it describes all PDBs that belong to the application container. When queried from a regular PDB or from an application PDB, it describes the regular PDB or the application PDB.

Column	Datatype	NULL	Description
PDB_ID	NUMBER	NOT NULL	Container ID of the PDB
PDB_NAME	VARCHAR2(128)	NOT NULL	Name of the PDB
DBID	NUMBER	NOT NULL	PDB identifier calculated when the PDB is created and stored in all file headers associated with the PDB
CON_UID	NUMBER	NOT NULL	Unique identifier associated with the container
GUID	RAW(16)		Globally unique immutable ID assigned to the PDB at creation time

Column	Datatype	NULL	Description
STATUS	VARCHAR2(10)		State of the PDB. Possible values: • NEW - The PDB has never been opened since it was created. It must be opened in READ WRITE mode for Oracle to perform processing needed to complete the integration of the PDB into the CDB and mark it NORMAL. An error will be thrown if an attempt is made to open the PDB read only. • NORMAL - The PDB is ready to be used. • UNPLUGGED - The PDB has been unplugged. The only operation that can be performed on it is DROP PLUGGABLE DATABASE. • RELOCATING: The PDB is in the process of being relocated to a different CDB. • RELOCATED: The PDB has been relocated to a different CDB. • REFRESHING: The PDB is a refresh PDB. • UNDEFINED: The PDB is in an undefined state. • UNUSABLE - The PDB is being created or an unrecoverable error was encountered during its creation. The PDB cannot be opened while its state is set to UNUSABLE. If the PDB remains in this state because of an error encountered during its creation, it can only be dropped. The alert log can be checked to determine if there was an error during PDB creation.
CREATION_SCN	NUMBER		Creation SCN
VSN	NUMBER		The version number of the PDB
LOGGING	VARCHAR2(9)		Shows the current logging mode for the PDB. Possible values: • LOGGING • NOLOGGING
FORCE_LOGGING	VARCHAR2(3)		Specifies whether force logging is turned on for the PDB. Possible values: • NO • YES
FORCE_NOLOGGING	VARCHAR2(3)		Specifies whether force nologging is turned on for the PDB. Possible values: • NO • YES
APPLICATION_ROOT	VARCHAR2(3)		Indicates whether the PDB is an application root.
APPLICATION_PDB	VARCHAR2(3)		Indicates whether a PDB is an application PDB
APPLICATION_SEED	VARCHAR2(3)		Indicates whether a PDB is an application seed (an application seed is also an application PDB)

Column	Datatype	NULL	Description
APPLICATION_ROOT_CON_ID	NUMBER		If this PDB is an application PDB, the container ID of an application root to which this application PDB belongs. If this PDB is an application root clone, the container ID of an application root to which this application root clone belongs. Otherwise, NULL.
IS_PROXY_PDB	VARCHAR2(3)		Indicates whether this PDB is a proxy PDB
CON_ID	NUMBER	NOT NULL	The ID of the container that CON_DBID identifies. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
UPGRADE_PRIORITY	NUMBER		The upgrade priority of the PDB.
APPLICATION_CLONE	VARCHAR2(3)		Indicates whether this PDB is an application root clone (YES) or not (NO)
FOREIGN_CDB_DBID	NUMBER		The foreign CDB's DBID
UNPLUG_SCN	NUMBER		SCN at which the PDB was unplugged
FOREIGN_PDB_ID	NUMBER		The foreign PDB ID
CREATION_TIME	DATE	NOT NULL	PDB creation timestamp
REFRESH_MODE	VARCHAR2(6)		PDB refresh mode. Possible values: • MANUAL • AUTO
REFRESH_INTERVAL	NUMBER		PDB refresh interval. This is applicable only when REFRESH_MODE is AUTO.
TEMPLATE	VARCHAR2(3)		For internal use only
LAST_REFRESH_SCN	NUMBER		System change number (SCN) of the last refresh operation
TENANT_ID	VARCHAR2(255)		Pluggable database tenant key
SNAPSHOT_MODE	VARCHAR2(6)		Pluggable database snapshot mode
SNAPSHOT_INTERVAL	NUMBER		Pluggable database snapshot interval, in minutes
CREDENTIAL_NAME	VARCHAR2(262)		Credential object name associated with the PDB
LAST_REFRESH_TIME	DATE		Time of the last refresh operation
CLOUD_IDENTITY	VARCHAR2(4000)		Cloud identifier for the PDB
SOURCE_PDB_NAME	VARCHAR2(128)		Name of the source PDB
SOURCE_DB_LINK	VARCHAR2(128)		Name of the source database link

Column	Datatype	NULL	Description
PRIORITY	NUMBER		The priority of the PDB when performing an OPEN or SAVE STATE operation on multiple PDBs with a single ALTER PLUGGABLE DATABASE or ALTER DATABASE statement If a priority is not assigned to the PDB, then the value of this column is null. An operation is performed first on the PDB with the lowest PRIORITY number, then on the PDB with the second lowest PRIORITY number, and so on. The operation is then performed on PDBs with no assigned priority, if any, in no particular order.

6.269 DBA_PENDING_CONV_TABLES

DBA_PENDING_CONV_TABLES describes all pending conversion tables in the database. Its columns are the same as those in ALL_PENDING_CONV_TABLES.

> **See Also:**
>
> "ALL_PENDING_CONV_TABLES"

6.270 DBA_PENDING_TRANSACTIONS

DBA_PENDING_TRANSACTIONS describes unresolved transactions (either due to failure or if the coordinator has not sent a commit/rollback).

Column	Datatype	NULL	Description
FORMATID	NUMBER		The format identifier of the transaction identifier
GLOBALID	RAW(64)		The global part (gtrid) of the transaction identifier
BRANCHID	RAW(64)		The branch qualifier (bqual) of the transaction identifier

6.271 DBA_PG_EDGE_RELATIONSHIPS

DBA_PG_EDGE_RELATIONSHIPS describes edge relationships in all property graphs in the database. Its columns are the same as those in ALL_PG_EDGE_RELATIONSHIPS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_EDGE_RELATIONSHIPS"

6.272 DBA_PG_ELEMENT_LABELS

`DBA_PG_ELEMENT_LABELS` describes labels for the element tables in all property graphs in the database. Its columns are the same as those in `ALL_PG_ELEMENT_LABELS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_ELEMENT_LABELS"

6.273 DBA_PG_ELEMENTS

`DBA_PG_ELEMENTS` describes element tables in all property graphs in the database. Its columns are the same as those in `ALL_PG_ELEMENTS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_ELEMENTS"

6.274 DBA_PG_KEYS

DBA_PG_KEYS describes key columns in all property graphs in the database. Its columns are the same as those in ALL_PG_KEYS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_KEYS"

6.275 DBA_PG_LABEL_PROPERTIES

DBA_PG_LABEL_PROPERTIES describes properties in all property graphs in the database. Its columns are the same as those in ALL_PG_LABEL_PROPERTIES.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_LABEL_PROPERTIES"

6.276 DBA_PG_LABELS

DBA_PG_LABELS describes labels in all property graphs in the database. Its columns are the same as those in ALL_PG_LABELS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_LABELS"

6.277 DBA_PG_PROP_DEFINITIONS

`DBA_PG_PROP_DEFINITIONS` describes columns and expressions exposed as properties in all property graphs in the database. Its columns are the same as those in `ALL_PG_PROP_DEFINITIONS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_PROP_DEFINITIONS"

6.278 DBA_PLSQL_COLL_TYPES

`DBA_PLSQL_COLL_TYPES` describes all named PL/SQL collection types in the database. Its columns (except for `CHAR_USED`) are the same as those in `ALL_PLSQL_COLL_TYPES`.

> **See Also:**
>
> "ALL_PLSQL_COLL_TYPES"

6.279 DBA_PLSQL_OBJECT_SETTINGS

`DBA_PLSQL_OBJECT_SETTINGS` displays information about the compiler settings for all stored objects in the database. Its columns are the same as those in `ALL_PLSQL_OBJECT_SETTINGS`.

> **See Also:**
>
> "ALL_PLSQL_OBJECT_SETTINGS"

6.280 DBA_PLSQL_TYPE_ATTRS

DBA_PLSQL_TYPE_ATTRS describes the attributes of all PL/SQL types in the database. Its columns are the same as those in ALL_PLSQL_TYPE_ATTRS.

> **See Also:**
>
> "ALL_PLSQL_TYPE_ATTRS"

6.281 DBA_PLSQL_TYPES

DBA_PLSQL_TYPES describes all PL/SQL types in the database. Its columns are the same as those in ALL_PLSQL_TYPES.

> **See Also:**
>
> "ALL_PLSQL_TYPES"

6.282 DBA_POLICIES

DBA_POLICIES describes all Oracle Virtual Private Database (VPD) security policies in the database. Its columns are the same as those in ALL_POLICIES.

A security policy is a list of security requirements and rules that regulate row level access to database objects.

> **See Also:**
>
> "ALL_POLICIES"

6.283 DBA_POLICY_ATTRIBUTES

DBA_POLICY_ATTRIBUTES lists the attribute associations {Namespaces, Attributes} of all context-sensitive and shared context-sensitive Oracle Virtual Private Database (VPD) policies in the database. Its columns are the same as those in ALL_POLICY_ATTRIBUTES.

> **See Also:**
>
> "ALL_POLICY_ATTRIBUTES"

6.284 DBA_POLICY_CONTEXTS

DBA_POLICY_CONTEXTS describes all driving contexts in the database. Its columns are the same as those in ALL_POLICY_CONTEXTS.

> **See Also:**
>
> "ALL_POLICY_CONTEXTS"

6.285 DBA_POLICY_GROUPS

DBA_POLICY_GROUPS describes all policy groups in the database. Its columns are the same as those in ALL_POLICY_GROUPS.

> **See Also:**
>
> "ALL_POLICY_GROUPS"

6.286 DBA_PRIV_AUDIT_OPTS

DBA_PRIV_AUDIT_OPTS describes current system privileges being audited across the system and by user.

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

Column	Datatype	NULL	Description
USER_NAME	VARCHAR2(128)		User name if by user auditing; ANY CLIENT if access by a proxy on behalf of a client is being audited; NULL for systemwide auditing
PROXY_NAME	VARCHAR2(128)		Name of the proxy user which is performing an operation for the client; NULL if the client is performing the operation directly
PRIVILEGE	VARCHAR2(40)	NOT NULL	Name of the system privilege being audited
SUCCESS	VARCHAR2(10)		Mode for WHENEVER SUCCESSFUL system auditing
FAILURE	VARCHAR2(10)		Mode for WHENEVER NOT SUCCESSFUL system auditing

6.287 DBA_PRIV_CAPTURES

DBA_PRIV_CAPTURES lists the privilege analysis policies in the database.

Column	Datatype	NULL	Description
NAME	VARCHAR2(128)	NOT NULL	Name of the privilege analysis policy
DESCRIPTION	VARCHAR2(1024)		Description of the privilege analysis
TYPE	VARCHAR2(16)		Type of the privilege analysis policy. Possible values: • G_DATABASE: Database wide privilege analysis • G_ROLE: Role privilege analysis • G_CONTEXT: Context privilege analysis • G_ROLE_AND_CONTEXT: Role and context privilege analysis
ENABLED	VARCHAR2(1)		Enabling status of the privilege analysis
ROLES	ROLE_ID_LIST		List of roles whose privileges to analyze if the privilege analysis type is G_ROLE or G_ROLE_AND_CONTEXT
CONTEXT	VARCHAR2(4000)		Context condition if the privilege analysis type is G_CONTEXT or G_ROLE_AND_CONTEXT
RUN_NAME	VARCHAR2(128)		Displays run name information for each run

See Also:

Oracle Database Security Guide for more information about privilege analysis

6.288 DBA_PRIVATE_TEMP_TABLES

DBA_PRIVATE_TEMP_TABLES describes all of the private temporary tables in the database.

Related View

USER_PRIVATE_TEMP_TABLES describes the private temporary tables in the current session. This view does not display the INST_ID column.

Column	Datatype	NULL	Description
SID	NUMBER		Session ID of the session that created the private temporary table
SERIAL#	NUMBER		Session serial number of the session that created the private temporary table
INST_ID	NUMBER		Instance ID of the session that created the private temporary table

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner name of the private temporary table
TABLE_NAME	VARCHAR2(128)		Private temporary table name
TABLESPACE_NAME	VARCHAR2(128)		Private temporary table's tablespace name
DURATION	VARCHAR2(128)		Private temporary table's duration (for example, SESSION or TRANSACTION)
NUM_ROWS	NUMBER		Number of rows in the private temporary table when analyzed
BLOCKS	NUMBER		Number of blocks used by private temporary table
AVG_ROW_LEN	NUMBER		Average row length
LAST_ANALYZED	DATE		Timestamp of last analyze
TXN_ID	RAW(8)		Transaction ID of the transaction duration private temporary table
SAVE_POINT_NUM	NUMBER		Save point number of the transaction duration private temporary table

See Also:

- "USER_PRIVATE_TEMP_TABLES"
- "PRIVATE_TEMP_TABLE_PREFIX"
- *Oracle Database Administrator's Guide* for an introduction to private temporary tables

6.289 DBA_PROCEDURES

DBA_PROCEDURES lists all functions and procedures that are available in the database, along with their associated properties. Its columns are the same as those in ALL_PROCEDURES.

See Also:

- "ALL_PROCEDURES"
- "DBA_ARGUMENTS" for information about the arguments of all of the functions and procedures that are available in the database

6.290 DBA_PROFILES

DBA_PROFILES displays all profiles and their limits.

Column	Datatype	NULL	Description
PROFILE	VARCHAR2(128)	NOT NULL	Profile name

Column	Datatype	NULL	Description
RESOURCE_NAME	VARCHAR2(32)	NOT NULL	Resource name
RESOURCE_TYPE	VARCHAR2(8)		Indicates whether the resource profile is a KERNEL or a PASSWORD parameter
LIMIT	VARCHAR2(128)		Limit placed on this resource for the profile
COMMON	VARCHAR2(3)		Indicates whether the profile is common. Possible values: • YES if a profile is common • NO if a profile is local (not common)
INHERITED	VARCHAR2(3)		Indicates whether the profile definition was inherited from another container (YES) or not (NO)
IMPLICIT	VARCHAR2(3)		Indicates whether the profile was created by an implicit application (YES) or not (NO)
ORACLE_MAINTAINED	VARCHAR2(3)		Indicates whether the profile was created by Oracle-supplied scripts (YES) or not (NO) Note that a profile created by Oracle-supplied scripts is local to all PDBs and can be changed inside a PDB to accommodate individual application requirements.
MANDATORY	VARCHAR2(3)		Indicates whether the profile is a mandatory user profile (YES) or not (NO) **See Also:** The MANDATORY_USER_PROFILE initialization parameter

6.291 DBA_PROPERTY_GRAPHS

DBA_PROPERTY_GRAPHS describes all property graphs in the database. Its columns are the same as those in ALL_PROPERTY_GRAPHS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PROPERTY_GRAPHS"

6.292 DBA_PROPAGATION

DBA_PROPAGATION displays information about all propagations in the database. Its columns are the same as those in ALL_PROPAGATION.

> **See Also:**
>
> "ALL_PROPAGATION"

6.293 DBA_PROXIES

DBA_PROXIES displays Information about all proxy connections in the database.

Related View

USER_PROXIES displays information about connections the current user is allowed to proxy. This view does not display the PROXY or PROXY_AUTHORITY columns.

Column	Datatype	NULL	Description
PROXY	VARCHAR2(128)		Name of the proxy user
CLIENT	VARCHAR2(128)	NOT NULL	Name of the client user who the proxy user can act on behalf of
AUTHENTICATION	VARCHAR2(3)		Indicates whether the proxy is required to supply the client's authentication credentials (YES) or not (NO)
AUTHORIZATION_CONSTRAINT	VARCHAR2(35)		Indicates the proxy's authority to exercise roles on the client's behalf: • NO CLIENT ROLES MAY BE ACTIVATED • PROXY MAY ACTIVATE ROLE • PROXY MAY ACTIVATE ALL CLIENT ROLES • PROXY MAY NOT ACTIVATE ROLE
ROLE	VARCHAR2(128)		Name of the role referenced in AUTHORIZATION_CONSTRAINT
PROXY_AUTHORITY	VARCHAR2(9)		Value is either: • DIRECTORY if EUS proxy is enabled for that database user • DATABASE if this row describes a local proxy permission

> **See Also:**
>
> "USER_PROXIES"

6.294 DBA_QUARANTINED_TRANSACTIONS

DBA_QUARANTINED_TRANSACTIONS lists all quarantined transactions in the current container.

Column	Datatype	NULL	Description
USN	NUMBER	NOT NULL	Undo segment number of the quarantined transaction
SLT	NUMBER	NOT NULL	Slot number of the quarantined transaction
SQN	NUMBER	NOT NULL	Sequence number of the quarantined transaction
REASON	VARCHAR2(256)		Reason the transaction failed to recover
TRACE_FILE_NAME	VARCHAR2(4096)		Name of the trace file containing the reason for the transaction's recovery failure, along with diagnostic information about the failure
UNDO_TSN	NUMBER		Undo tablespace number for the quarantined transaction
UNDO_RECORD_OBJN	NUMBER		Dictionary object number of the object (OBJN)
UNDO_RECORD_OBJD	NUMBER		Dictionary object number of the segment that contains the object (OBJD)
DATA_BLOCK_TSN	NUMBER		Tablespace ID for the object
PREV_UNDO_BLOCK_DBA	NUMBER		Previous undo block address, which was used for rollback
UBA_RDBA	NUMBER		Relative data block address of the current undo block being applied for rollback
UBA_SQN	NUMBER		Undo block sequence number of the current undo block being applied for rollback
UBA_RECORD_NUMBER	NUMBER		Undo record number of the current undo block being applied for rollback
TXN_START_SCN	NUMBER		Start SCN of the quarantined transaction
INCIDENT_TIME	VARCHAR2(64)		Time at which the incident occurred

Note:

This view is available starting with Oracle Database 23ai.

See Also:

"V$FAST_START_TRANSACTIONS"

6.295 DBA_QUEUE_EVENT_STREAMS

DBA_QUEUE_EVENT_STREAMS describes all Transactional Event Queue (TxEventQ) event streams in the database. Its columns are the same as those in ALL_QUEUE_EVENT_STREAMS.

> **See Also:**
>
> "ALL_QUEUE_EVENT_STREAMS"

6.296 DBA_QUEUE_SCHEDULES

DBA_QUEUE_SCHEDULES describes all propagation schedules in the database. Its columns are the same as those in ALL_QUEUE_SCHEDULES.

> **See Also:**
>
> "ALL_QUEUE_SCHEDULES"

6.297 DBA_QUEUE_SUBSCRIBERS

DBA_QUEUE_SUBSCRIBERS displays all subscribers on all queues in the database. Its columns are the same as those in ALL_QUEUE_SUBSCRIBERS.

> **See Also:**
>
> "ALL_QUEUE_SUBSCRIBERS"

6.298 DBA_QUEUE_TABLES

DBA_QUEUE_TABLES contains information about the owner instance for a queue table.

A queue table can contain multiple queues. In this case, each queue in a queue table has the same owner instance as the queue table. Its columns are the same as those in ALL_QUEUE_TABLES.

> **See Also:**
>
> "ALL_QUEUE_TABLES"

6.299 DBA_QUEUES

DBA_QUEUES describes the operational characteristics of every queue in a database. Its columns are the same as those in ALL_QUEUES.

> **See Also:**
>
> - "ALL_QUEUES"
> - *Oracle Database Advanced Queuing User's Guide* for more information about Advanced Queuing

6.300 DBA_RAT_CAPTURE_SCHEMA_INFO

DBA_RAT_CAPTURE_SCHEMA_INFO displays the login schema and current schema that were in effect when SQL statements were recorded in a workload capture.

This view is useful when you perform a workload replay in extended PL/SQL mode. This type of replay may include SQL statements that perform table operations such as SELECT, UPDATE, and DELETE. If the current schema was different from the login schema at the time of the workload capture, then those table operations may have been performed with the privileges of the current user, not the login user. During workload replay, all operations are performed with the privileges of the login user. Therefore, errors can occur during replay if the login user does not have the necessary privileges to perform the table operations.

To resolve this issue, you can use this view in conjunction with the DBA_WORKLOAD_CAPTURE_SQLTEXT view. Join the CAPTURE_ID column in this view with the CAPTURE_ID column in DBA_WORKLOAD_CAPTURE_SQLTEXT to determine the login schema and current schema that were in effect when each SQL statement in DBA_WORKLOAD_CAPTURE_SQLTEXT was captured. Examine the SQL_TEXT column in DBA_WORKLOAD_CAPTURE_SQLTEXT to determine whether the SQL statement involved any table operations, and whether those table operations were performed with the privileges of the current user or the login user. You can then grant to the login user the necessary privileges for performing those table operations before performing a workload replay.

Column	Datatype	NULL	Description
CAPTURE_ID	NUMBER(38)		Internal key for the workload capture
SQL_ID	VARCHAR2(13)		SQL identifier for the parent cursor in the library cache
LOGIN_SCHEMA	VARCHAR2(128)		The schema of the user who logged on to the session in which the SQL statement was recorded in the workload capture. This value does not change during a session.

Column	Datatype	NULL	Description
CURRENT_SCHEMA	VARCHAR2(128)		The currently active default schema for the session when the SQL statement was recorded in the workload capture. This value may change during a session through use of an ALTER SESSION SET CURRENT_SCHEMA statement. It may also change during a session to reflect the owner of any active definer's rights object.

> **See Also:**
>
> "DBA_WORKLOAD_CAPTURE_SQLTEXT"

6.301 DBA_RCHILD

DBA_RCHILD displays all the children in any refresh group.

Column	Datatype	NULL	Description
REFGROUP	NUMBER		Internal identifier of the refresh group
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object in the refresh group
NAME	VARCHAR2(128)	NOT NULL	Name of the object in the refresh group
TYPE#	VARCHAR2(128)		Type of the object in the refresh group

6.302 DBA_RECOVERABLE_SCRIPT

DBA_RECOVERABLE_SCRIPT provides details about recoverable operations.

Column	Datatype	NULL	Description
SCRIPT_ID	RAW(16)		Unique ID of the operation
CREATION_TIME	DATE		Time the operation was invoked
INVOKING_PACKAGE_OWNER	VARCHAR2(128)		Invoking package owner of the operation
INVOKING_PACKAGE	VARCHAR2(128)		Invoking package of the operation
INVOKING_PROCEDURE	VARCHAR2(128)		Invoking procedure of the operation
INVOKING_USER	VARCHAR2(128)		Script owner
STATUS	VARCHAR2(12)		State of the recoverable script: GENERATING, NOT EXECUTED, EXECUTING, EXECUTED, or ERROR
TOTAL_BLOCKS	NUMBER		Total number of blocks for the recoverable script to be executed
DONE_BLOCK_NUM	NUMBER		Last block executed, thus far
SCRIPT_COMMENT	VARCHAR2(4000)		Comment for the recoverable script

6.303 DBA_RECOVERABLE_SCRIPT_BLOCKS

DBA_RECOVERABLE_SCRIPT_BLOCKS provides details about recoverable script blocks.

Column	Datatype	NULL	Description
SCRIPT_ID	RAW(16)		Global unique ID of the recoverable script to which this block belongs
BLOCK_NUM	NUMBER		The *n*th block in the recoverable script to be executed
FORWARD_BLOCK	CLOB		Forward block to be executed
FORWARD_BLOCK_DBLINK	VARCHAR2(128)		Database where the forward block is executed
UNDO_BLOCK	CLOB		Block to roll back the forward operation
UNDO_BLOCK_DBLINK	VARCHAR2(128)		Database where the undo block is executed
STATUS	VARCHAR2(12)		Status of the block execution: GENERATING, NOT EXECUTED, EXECUTING, EXECUTED, or ERROR
BLOCK_COMMENT	VARCHAR2(4000)		Comment for the block

6.304 DBA_RECOVERABLE_SCRIPT_ERRORS

DBA_RECOVERABLE_SCRIPT_ERRORS provides details about errors that occurred during script execution.

Column	Datatype	NULL	Description
SCRIPT_ID	RAW(16)		Global unique ID of the recoverable script
BLOCK_NUM	NUMBER		The *n*th block that failed
ERROR_NUMBER	NUMBER		Number of the error encountered while executing the block
ERROR_MESSAGE	VARCHAR2(4000)		Error message encountered while executing the block
ERROR_CREATION_TIME	DATE		Time that the error was created

6.305 DBA_RECOVERABLE_SCRIPT_HIST

DBA_RECOVERABLE_SCRIPT_HIST displays details about executed or purged recoverable operations.

Column	Datatype	NULL	Description
SCRIPT_ID	RAW(16)		Unique id of the operation
CREATION_TIME	DATE		Time the operation was invoked
INVOKING_PACKAGE_OWNER	VARCHAR2(128)		Invoking package owner of the operation
INVOKING_PACKAGE	VARCHAR2(128)		Invoking package of the operation
INVOKING_PROCEDURE	VARCHAR2(128)		Invoking procedure of the operation

Column	Datatype	NULL	Description
INVOKING_USER	VARCHAR2(128)		Script owner
STATUS	VARCHAR2(8)		state of the recoverable script: EXECUTED, PURGED
TOTAL_BLOCKS	NUMBER		total number of blocks for the recoverable script to be executed
DONE_BLOCK_NUM	NUMBER		last block so far executed
SCRIPT_COMMENT	VARCHAR2(4000)		comment for the recoverable script

6.306 DBA_RECOVERABLE_SCRIPT_PARAMS

DBA_RECOVERABLE_SCRIPT_PARAMS provides details about recoverable operation parameters.

Column	Datatype	NULL	Description
SCRIPT_ID	RAW(16)		Unique ID of the operation
PARAMETER	VARCHAR2(128)		Name of the parameter
PARAM_INDEX	NUMBER		Index for multi-valued parameter
VALUE	VARCHAR2(4000)		Value of the parameter

6.307 DBA_RECYCLEBIN

DBA_RECYCLEBIN displays information about all recycle bins in the database.

Related View

USER_RECYCLEBIN displays information about the recycle bin owned by the current user. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Name of the original owner of the object
OBJECT_NAME	VARCHAR2(128)	NOT NULL	New name of the object
ORIGINAL_NAME	VARCHAR2(128)		Original name of the object
OPERATION	VARCHAR2(9)		Operation carried out on the object: • DROP - Object was dropped • TRUNCATE - Object was truncated **Note:** The Oracle Database currently only supports recovering dropped objects from the recycle bin. The truncated objects cannot be recovered.

Column	Datatype	NULL	Description
TYPE	VARCHAR2(25)		Type of the object: • TABLE • NORMAL INDEX • BITMAP INDEX • NESTED TABLE • LOB • LOB INDEX • DOMAIN INDEX • IOT TOP INDEX • IOT OVERFLOW SEGMENT • IOT MAPPING TABLE • TRIGGER • Table Partition • Table Composite Partition • Index Partition • Index Composite Partition • LOB Partition • LOB Composite Partition
TS_NAME	VARCHAR2(30)		Name of the tablespace to which the object belongs
CREATETIME	VARCHAR2(19)		Timestamp for the creation of the object
DROPTIME	VARCHAR2(19)		Timestamp for the dropping of the object
DROPSCN	NUMBER		System change number (SCN) of the transaction which moved the object to the recycle bin
PARTITION_NAME	VARCHAR2(128)		Name of the partition which was dropped
CAN_UNDROP	VARCHAR2(3)		Indicates whether the object can be undropped (YES) or not (NO)
CAN_PURGE	VARCHAR2(3)		Indicates whether the object can be purged (YES) or not (NO)
RELATED	NUMBER	NOT NULL	Object number of the parent object
BASE_OBJECT	NUMBER	NOT NULL	Object number of the base object
PURGE_OBJECT	NUMBER	NOT NULL	Object number for the object which gets purged
SPACE	NUMBER		Number of blocks used by the object

See Also:

"USER_RECYCLEBIN"

6.308 DBA_REDEFINITION_ERRORS

DBA_REDEFINITION_ERRORS is an online redefinition view. It displays the dependent objects for which errors were raised while attempting to create similar objects on the interim table of the redefinition.

Column	Datatype	NULL	Description
OBJECT_TYPE	VARCHAR2(12)		Type of the redefinition object: • TABLE • INDEX • CONSTRAINT • TRIGGER • NESTED TABLE • PARTITION • MV LOG
OBJECT_OWNER	VARCHAR2(4000)		Owner of the redefinition object
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the redefinition object
BASE_TABLE_OWNER	VARCHAR2(128)		Owner of the base table of the redefinition object
BASE_TABLE_NAME	VARCHAR2(128)		Name of the base table of the redefinition object
DDL_TXT	CLOB		DDL used to create the corresponding interim redefinition object
EDITION_NAME	VARCHAR2(128)		Reserved for future use
ERR_NO	NUMBER(38)		Oracle error number corresponding to this error
ERR_TXT	VARCHAR2(1000)		Oracle error text corresponding to this error

See Also:

Oracle Database Administrator's Guide for more information about online redefinition

6.309 DBA_REDEFINITION_OBJECTS

DBA_REDEFINITION_OBJECTS is an online redefinition view. It displays the objects involved in the current redefinitions.

Column	Datatype	NULL	Description
OBJECT_TYPE	VARCHAR2(12)		Type of the redefinition object: • TABLE • INDEX • CONSTRAINT • TRIGGER • NESTED TABLE • PARTITION • MV LOG
OBJECT_OWNER	VARCHAR2(4000)		Owner of the redefinition object
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the redefinition object
BASE_TABLE_OWNER	VARCHAR2(128)		Owner of the base table of the redefinition object
BASE_TABLE_NAME	VARCHAR2(128)		Name of the base table of the redefinition object
INTERIM_OBJECT_OWNER	VARCHAR2(4000)		Owner of the corresponding interim redefinition object

Column	Datatype	NULL	Description
INTERIM_OBJECT_NAME	VARCHAR2(128)		Name of the corresponding interim redefinition object
EDITION_NAME	VARCHAR2(128)		Reserved for future use

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about online redefinition

6.310 DBA_REDEFINITION_STATUS

DBA_REDEFINITION_STATUS is an online redefinition view. It provides information about the online redefinition status.

Column	Datatype	NULL	Description
REDEFINITION_ID	NUMBER(38)	NOT NULL	ID for the redefinition object
BASE_TABLE_OWNER	VARCHAR2(128)		Owner of the base table of the redefinition object
BASE_TABLE_NAME	VARCHAR2(128)		Name of the base table of the redefinition object
BASE_OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the base object of the redefinition object
BASE_OBJECT_TYPE	VARCHAR2(9)		Type of the base object of the redefinition object
INTERIM_OBJECT_OWNER	VARCHAR2(128)		Owner of the interim object of the redefinition object
INTERIM_OBJECT_NAME	VARCHAR2(128)		Name of the interim object of the redefinition object
OPERATION	VARCHAR2(128)	NOT NULL	The current redefinition operation: • START_REDEF_TABLE • SYNC_INTERIM_TABLE • COPY_TABLE_DEPENDENTS • FINISH_REDEF_TABLE
STATUS	VARCHAR2(128)	NOT NULL	Status of the previous redefinition operation: • FAILURE • SUCCESS
RESTARTABLE	VARCHAR2(1)	NOT NULL	Indicates whether the previous operation can be restarted
ERR_TXT	VARCHAR2(1000)		The error message raised from the previous operation
ACTION	VARCHAR2(400)		The suggested action
REFRESH_DEP_MVIEWS	VARCHAR2(1)		Indicates whether the online redefinition will also refresh dependent materialized views when syncing the interim table (Y) or not (N)

> **See Also:**
>
> *Oracle Database Administrator's Guide* for more information about online redefinition

6.311 DBA_REFRESH

`DBA_REFRESH` describes all refresh groups in the database. Its columns are the same as those in `ALL_REFRESH`.

> **See Also:**
>
> "ALL_REFRESH"

6.312 DBA_REFRESH_CHILDREN

`DBA_REFRESH_CHILDREN` lists all of the objects in all refresh groups in the database. Its columns are the same as those in `ALL_REFRESH_CHILDREN`.

> **See Also:**
>
> "ALL_REFRESH_CHILDREN"

6.313 DBA_REFS

`DBA_REFS` describes the `REF` columns and `REF` attributes in object type columns of all the objects in the database. Its columns are the same as those in `ALL_REFS`.

> **See Also:**
>
> "ALL_REFS"

6.314 DBA_REGISTERED_ARCHIVED_LOG

`DBA_REGISTERED_ARCHIVED_LOG` displays information about all registered archived logfiles in the database.

Column	Datatype	NULL	Description
`CONSUMER_NAME`	`VARCHAR2(128)`	`NOT NULL`	Consumer name of the archived logs

Column	Datatype	NULL	Description
SOURCE_DATABASE	VARCHAR2(128)		Name of the database which generated the redo logs
THREAD#	NUMBER	NOT NULL	Thread number of the archived redo log. The thread number is 1 for a single instance. For Real Application Clusters, this column will contain different numbers.
SEQUENCE#	NUMBER	NOT NULL	Sequence number of the archived redo log file
FIRST_SCN	NUMBER	NOT NULL	System change number (SCN) of the current archived redo log
NEXT_SCN	NUMBER		System change number (SCN) of the next archived redo log
FIRST_TIME	DATE		Date and time of the current archived redo log
NEXT_TIME	DATE		Date and time of the next archived redo log
NAME	VARCHAR2(513)		Name of the archived redo log
MODIFIED_TIME	DATE		Time when the archived redo log was registered
DICTIONARY_BEGIN	VARCHAR2(3)		Indicates whether the beginning of the dictionary build is in the archived redo log (YES) or not (NO)
DICTIONARY_END	VARCHAR2(3)		Indicates whether the end of the dictionary build is in the archived redo log (YES) or not (NO)
PURGEABLE	VARCHAR2(3)		Indicates whether the redo log can be permanently removed (YES) or not (NO)
RESET_LOGS_CHANGE#	NUMBER	NOT NULL	Resetlogs change number of the database when the log was written
RESET_TIMESTAMP	NUMBER	NOT NULL	Resetlogs time of the database when the log was written

6.315 DBA_REGISTERED_MVIEWS

DBA_REGISTERED_MVIEWS describes all registered materialized views (registered at a master site or a master materialized view site) in the database. Its columns are the same as those in ALL_REGISTERED_MVIEWS.

> **See Also:**
>
> "ALL_REGISTERED_MVIEWS"

6.316 DBA_REGISTRY

DBA_REGISTRY displays information about all components in the database that are loaded into the component registry.

The component registry tracks components that can be separately loaded into the Oracle Database. When a SQL script loads the PL/SQL packages and other database objects for a component into the database, the script records the component name,

status, and version. If scripts are used to upgrade/downgrade the dictionary elements for the component, then those scripts also record status and version information.

Related View

USER_REGISTRY displays information about the components owned by the current user that are loaded into the component registry.

Column	Datatype	NULL	Description
COMP_ID	VARCHAR2(30)	NOT NULL	Component identifier
COMP_NAME	VARCHAR2(255)		Component name
VERSION	VARCHAR2(30)		Component version loaded
VERSION_FULL	VARCHAR2(30)		Component full version
STATUS	VARCHAR2(11)		Component status: • INVALID • VALID • LOADING • LOADED • UPGRADING • UPGRADED • DOWNGRADING • DOWNGRADED • REMOVING • REMOVED
MODIFIED	VARCHAR2(20)		Time when the component was last modified
NAMESPACE	VARCHAR2(30)	NOT NULL	Component namespace
CONTROL	VARCHAR2(128)	NOT NULL	User that created the component entry
SCHEMA	VARCHAR2(128)	NOT NULL	User that contains the objects for the component
PROCEDURE	VARCHAR2(61)		Validation procedure
STARTUP	VARCHAR2(8)		Indicates whether the component requires a startup after the upgrade (REQUIRED) or not
PARENT_ID	VARCHAR2(30)		Parent component identifier
OTHER_SCHEMAS	VARCHAR2(4000)		A list of ancillary schema names associated with the component

See Also:

"USER_REGISTRY"

6.317 DBA_REGISTRY_BACKPORTS

DBA_REGISTRY_BACKPORTS displays backported bug fixes that were applied to the database. This view displays only bug fixes that changed the data dictionary of the database.

Column	Datatype	NULL	Description
BUGNO	NUMBER	NOT NULL	Bug number
VERSION_FULL	VARCHAR2(30)	NOT NULL	Component full version
COMP_ID	VARCHAR2(30)	NOT NULL	Component identifier
NAMESPACE	VARCHAR2(30)	NOT NULL	Component namespace
BACKPORT_TYPE	VARCHAR2(30)	NOT NULL	Type of backported bug fix The value of this columns is always DICTIONARY, which indicates that the bug fix changed the data dictionary of the database.
BACKPORT_TIME	TIMESTAMP(6)	NOT NULL	Date and time at which the backported bug fix was applied

6.318 DBA_REGISTRY_HIERARCHY

DBA_REGISTRY_HIERARCHY displays information about the components loaded into the database, grouped by owner and organized in the component hierarchy.

Column	Datatype	NULL	Description
NAMESPACE	VARCHAR2(30)	NOT NULL	Component namespace
COMP_ID	VARCHAR2(4000)		Component identifier
VERSION	VARCHAR2(30)		Component version loaded
VERSION_FULL	VARCHAR2(30)		Component full version
STATUS	VARCHAR2(11)		Component status: • INVALID • VALID • LOADING • LOADED • UPGRADING • UPGRADED • DOWNGRADING • DOWNGRADED • REMOVING • REMOVED
MODIFIED	VARCHAR2(20)		Time when the component was last modified

6.319 DBA_REGISTRY_HISTORY

DBA_REGISTRY_HISTORY provides information about upgrades, downgrades, and critical patch updates that have been performed on the database.

Column	Datatype	NULL	Description
ACTION_TIME	TIMESTAMP(6)		The time the upgrade, downgrade, or patch action was completed

Column	Datatype	NULL	Description
ACTION	VARCHAR2(30)		The specific action (for example, UPGRADE or DOWNGRADE)
NAMESPACE	VARCHAR2(30)		The namespace of the components affected (for example, SERVER)
VERSION	VARCHAR2(30)		The version number of the server (for example, 10.2.0.1.0)
ID	NUMBER		Bundle ID
COMMENTS	VARCHAR2(255)		Additional comments about the action taken
BUNDLE_SERIES	VARCHAR2(30)		If a bundle patch, the series (for example, PSU or DBBP)

6.320 DBA_REGISTRY_LOG

DBA_REGISTRY_LOG displays operating information about components loaded into the database.

Column	Datatype	NULL	Description
OPTIME	VARCHAR2(20)		Operation time
NAMESPACE	VARCHAR2(30)		Component namespace
COMP_ID	VARCHAR2(30)		Component identifier
OPERATION	VARCHAR2(11)		Operation name
MESSAGE	VARCHAR2(1000)		Message

6.321 DBA_REGISTRY_SCHEMAS

DBA_REGISTRY_SCHEMAS lists the primary and ancillary schemas included in the component registry. The ancillary schemas that are listed in this view are the same schemas that would be included in the OTHER_SCHEMAS column of the DBA_REGISTRY view.

Column	Datatype	NULL	Description
NAMESPACE	VARCHAR2(30)		Component namespace
COMP_ID	VARCHAR2(30)		Component identifier
SCHEMA	VARCHAR2(128)		User that contains the objects for the component

See Also:

- "DBA_REGISTRY"
- "USER_REGISTRY"

6.322 DBA_REGISTRY_SQLPATCH

DBA_REGISTRY_SQLPATCH contains information about the SQL patches that have been installed in the database.

A SQL patch is a patch that contains SQL scripts which need to be run after OPatch completes. DBA_REGISTRY_SQLPATCH is updated by the datapatch utility. Each row contains information about an installation attempt (apply or roll back) for a given patch.

Column	Datatype	NULL	Description
INSTALL_ID	NUMBER	NOT NULL	Unique numeric identifier for this datapatch session. All patches installed in the same invocation of datapatch will have the same value for INSTALL_ID.
PATCH_ID	NUMBER	NOT NULL	ID associated with the patch
PATCH_UID	NUMBER	NOT NULL	UPI (Universal Patch ID) associated with the patch
PATCH_TYPE	VARCHAR2(10)	NOT NULL	Type of the patch. Possible values: • INTERIM: Interim patch • RU: Release Update • RUI: Release Update Increment • RUR: Release Update Revision • CU: Cumulative Update
ACTION	VARCHAR2(15)	NOT NULL	APPLY or ROLLBACK
STATUS	VARCHAR2(25)	NOT NULL	Possible values: • SUCCESS: Patch application has completed with no errors • WITH ERRORS: Patch application finished with errors
ACTION_TIME	TIMESTAMP(6)	NOT NULL	Timestamp when the install was performed
DESCRIPTION	VARCHAR2(100)		Description of this patch from OPatch metadata
LOGFILE	VARCHAR2(500)	NOT NULL	Location of the logfile for this apply or rollback attempt
RU_LOGFILE	VARCHAR2(500)		Logfile location for RU specific commands
FLAGS	VARCHAR2(10)		One or more of the following: • J: Patch is a JVM patch • M: Patch installation was merged with another patch • N: Patch requires normal mode • R: Patch installation has been retried • U: Patch requires upgrade mode
PATCH_DESCRIPTOR	XMLTYPE		Contents of the XML descriptor for the patch
PATCH_DIRECTORY	BLOB		Contents of the patch directory under ORACLE_HOME/sqlpatch
SOURCE_VERSION	VARCHAR2(15)		5 digit version (for example, 18.3.2.0.0) for the version on which the patch was applied
SOURCE_BUILD_DESCRIPTION	VARCHAR2(80)		Build description (for example, Release_Update or Release_Update_Revision) for the version on which the patch was applied

Column	Datatype	NULL	Description
SOURCE_BUILD_TIMESTAMP	TIMESTAMP(6)		Build timestamp for the version on which the patch was applied
TARGET_VERSION	VARCHAR2(15)		5 digit version (for example, 18.4.0.0.0) for the version to be installed
TARGET_BUILD_DESCRIPTION	VARCHAR2(80)		Build description (for example, Release_Update or Release_Update_Revision) for the version to be installed
TARGET_BUILD_TIMESTAMP	TIMESTAMP(6)		Build timestamp for the version to be installed

See Also:

- *Oracle OPatch User's Guide for Windows and UNIX* for more information about OPatch and related patching utilities
- My Oracle Support note 1585822.1 "Datapatch: Database 12c Post Patch SQL Automation" at the following URL for more information about datapatch:

  https://support.oracle.com/rs?type=doc&id=1585822.1

6.323 DBA_REPAIR_TABLE

DBA_REPAIR_TABLE describes any corruptions found by the DBMS_REPAIR.CHECK_OBJECT procedure.

This information is used by the DBMS_REPAIR.FIX_CORRUPT_BLOCKS procedure on execution. To create this view, first run the DBMS_REPAIR.ADMIN_TABLES procedure. To populate the resulting repair table for an object, run the DBMS_REPAIR.CHECK_OBJECT procedure on the object.

Note:

The table created by the DBMS_REPAIR.ADMIN_TABLES procedure is called REPAIR TABLE by default. If you specify a different name, this view will have the name you specify, preceded by "DBA_REPAIR_".

Column	Datatype	NULL	Description
OBJECT_ID	NUMBER	NOT NULL	Dictionary object number of the object with the corruption
TABLESPACE_ID	NUMBER	NOT NULL	Tablespace number of the corrupt object
RELATIVE_FILE_ID	NUMBER)	NOT NULL	Relative file number of the corrupt object
BLOCK_ID	NUMBER	NOT NULL	Block number of the corruption
CORRUPT_TYPE	NUMBER	NOT NULL	Type of corruption encountered
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Schema of the corrupt object

Column	Datatype	NULL	Description
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the corrupt object
BASEOBJECT_NAME	VARCHAR2(128)	NULL	If the object is an index, the name of its base table
PARTITION_NAME	VARCHAR2(128)	NULL	Partition or subpartition name, if applicable
CORRUPT_DESCRIPTION	VARCHAR2(2000)	NULL	Description of corruption
REPAIR_DESCRIPTION	VARCHAR2(200)	NULL	Description of repair action
MARKED_CORRUPT	VARCHAR2(10)	NOT NULL	Whether the block is marked corrupt (TRUE | FALSE)
CHECK_TIMESTAMP	DATE	NOT NULL	Date and time when this row was inserted into the repair table
FIX_TIMESTAMP	DATE	NULL	Date and time when the block was modified by the FIX_CORRUPT_BLOCKS procedure, if applicable
REFORMAT_TIMESTAMP	DATE	NULL	Reserved for future use

See Also:

Oracle Database PL/SQL Packages and Types Reference for more information about the DBMS_REPAIR package

6.324 DBA_REPL_DBNAME_MAPPING

DBA_REPL_DBNAME_MAPPING provides details about the database name mapping in replication. Its columns are the same as those in ALL_REPL_DBNAME_MAPPING.

See Also:

"ALL_REPL_DBNAME_MAPPING"

6.325 DBA_REPLICATION_PROCESS_EVENTS

DBA_REPLICATION_PROCESS_EVENTS provides information about the replication processes events in the database. Its columns are the same as those in ALL_REPLICATION_PROCESS_EVENTS.

See Also:

"ALL_REPLICATION_PROCESS_EVENTS"

6.326 DBA_RESOURCE_INCARNATIONS

DBA_RESOURCE_INCARNATIONS lists all resource incarnations that are running or eligible for HA status notification.

Column	Datatype	NULL	Description
RESOURCE_TYPE	VARCHAR2(30)	NOT NULL	Type of resource
RESOURCE_NAME	VARCHAR2(256)		Name of resource
DB_UNIQUE_NAME	VARCHAR2(30)	NOT NULL	Database unique name
DB_DOMAIN	VARCHAR2(128)	NOT NULL	Database domain
INSTANCE_NAME	VARCHAR2(30)	NOT NULL	Name of instance at which resource is located
HOST_NAME	VARCHAR2(512)		Name of host at which resource is located
STARTUP_TIME	TIMESTAMP(9) WITH TIME ZONE		Resource startup date and time

6.327 DBA_RESUMABLE

DBA_RESUMABLE displays all resumable statements executed in the system.

Related View

USER_RESUMABLE displays the resumable statements executed by the current user. This view does not display the USER_ID column.

Column	Datatype	NULL	Description
USER_ID	NUMBER		User ID Number of the Resumable Statement Owner
SESSION_ID	NUMBER		Session Identifier of the Resumable Statement
INSTANCE_ID	NUMBER		Instance Number of the Resumable Statement
COORD_INSTANCE_ID	NUMBER		Instance Number on which the Parallel Coordinator is Running
COORD_SESSION_ID	NUMBER		Session Identifier of the Parallel Coordinator
STATUS	VARCHAR2(9)		Status of the resumable statement: • RUNNING • SUSPENDED • TIMEOUT • ERROR • ABORTED
TIMEOUT	NUMBER		Timeout of the resumable statement
START_TIME	VARCHAR2(20)		Start time of the resumable statement
SUSPEND_TIME	VARCHAR2(20)		Last time the resumable statement was suspended (initialized to NULL)
RESUME_TIME	VARCHAR2(20)		Last time the suspended resumable statement was resumed (initialized to NULL)
NAME	VARCHAR2(4000)		Name given in the resumable clause of the resumable statement

Column	Datatype	NULL	Description
SQL_TEXT	VARCHAR2(1000)		Resumable statement, selected from the V$SQL view
ERROR_NUMBER	NUMBER		Error code of the last correctable error. When STATUS is set to RUNNING, its value will be 0.
ERROR_PARAMETER1	VARCHAR2(80)		First parameter for the error message (NULL if no error)
ERROR_PARAMETER2	VARCHAR2(80)		Second parameter for the error message (NULL if no error)
ERROR_PARAMETER3	VARCHAR2(80)		Third parameter for the error message (NULL if no error)
ERROR_PARAMETER4	VARCHAR2(80)		Forth parameter for the error message (NULL if no error)
ERROR_PARAMETER5	VARCHAR2(80)		Fifth parameter for the error message (NULL if no error)
ERROR_MSG	VARCHAR2(4000)		Error message corresponding to ERROR_NUMBER. It will be NULL when ERROR_NUMBER is 0.

See Also:

"USER_RESUMABLE"

6.328 DBA_REWRITE_EQUIVALENCES

DBA_REWRITE_EQUIVALENCES describes all rewrite equivalences in the database. Its columns are the same as those in ALL_REWRITE_EQUIVALENCES.

See Also:

"ALL_REWRITE_EQUIVALENCES"

6.329 DBA_RGROUP

DBA_RGROUP displays all refresh groups.

Column	Datatype	NULL	Description
REFGROUP	NUMBER		Internal identifier of the refresh group
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object in the refresh group
NAME	VARCHAR2(128)	NOT NULL	Name of the object in the refresh group
IMPLICIT_DESTROY	VARCHAR2(1)		Indicates whether the refresh group is destroyed when its last item is removed (Y) or not (N)

Column	Datatype	NULL	Description
PUSH_DEFERRED_RPC	VARCHAR2(1)		Indicates whether changes are pushed from the snapshot to the master before refresh (Y) or not (N)
REFRESH_AFTER_ERRORS	VARCHAR2(1)		Indicates whether to proceed with refresh despite errors when pushing deferred RPCs (Y) or not (N)
ROLLBACK_SEG	VARCHAR2(128)		Name of the rollback segment to use while refreshing
JOB	NUMBER	NOT NULL	Identifier of the job used to refresh the group automatically
PURGE_OPTION	NUMBER(38)		Method for purging the transaction queue after each push. 1 indicates quick purge option; 2 indicates precise purge option
PARALLELISM	NUMBER(38)		Level of parallelism for transaction propagation
HEAP_SIZE	NUMBER(38)		Size of the heap
JOB_NAME	VARCHAR2(128)		The name of the job used to automatically refresh the group

6.330 DBA_ROLE_PRIVS

DBA_ROLE_PRIVS describes the roles granted to all users and roles in the database.

Related View

USER_ROLE_PRIVS describes the roles granted to the current user.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)		Name of the user or role receiving the grant
GRANTED_ROLE	VARCHAR2(128)		Granted role name
ADMIN_OPTION	VARCHAR2(3)		Indicates whether the grant was with the ADMIN OPTION (YES) or not (NO)
DELEGATE_OPTION	VARCHAR2(3)		Indicates whether the grant was with the DELEGATE OPTION (YES) or not (NO)
DEFAULT_ROLE	VARCHAR2(3)		Indicates whether the role is designated as a DEFAULT ROLE for the user (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the role was granted commonly (CONTAINER=ALL was used) • NO if the role was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the role grant was inherited from another container (YES) or not (NO)

> **See Also:**
>
> "USER_ROLE_PRIVS"

6.331 DBA_ROLES

DBA_ROLES describes all roles in the database.

Column	Datatype	NULL	Description
ROLE	VARCHAR2(128)	NOT NULL	Name of the role
ROLE_ID	NUMBER	NOT NULL	ID number of the role
PASSWORD_REQUIRED	VARCHAR2(8)		This column is deprecated in favor of the AUTHENTICATION_TYPE column
AUTHENTICATION_TYPE	VARCHAR2(11)		Indicates the authentication mechanism for the role: • NONE - CREATE ROLE *role1*; • EXTERNAL - CREATE ROLE *role2* IDENTIFIED EXTERNALLY; • GLOBAL - CREATE ROLE *role3* IDENTIFIED GLOBALLY; • APPLICATION - CREATE ROLE *role4* IDENTIFIED USING *schema.package*; • PASSWORD - CREATE ROLE *role5* IDENTIFIED BY *role5*;
COMMON	VARCHAR2(3)		Indicates whether a given role is common. Possible values: • YES if the role is common • NO if the role is local (not common)
ORACLE_MAINTAINED	VARCHAR2(1)		Denotes whether the role was created, and is maintained, by Oracle-supplied scripts (such as catalog.sql or catproc.sql). A role for which this column has the value Y must not be changed in any way except by running an Oracle-supplied script.
INHERITED	VARCHAR2(3)		Indicates whether the role was inherited from another container (YES) or not (NO)
IMPLICIT	VARCHAR2(3)		Indicates whether the role is a common role created by an implicit application (YES) or not (NO)
EXTERNAL_NAME	VARCHAR2(4000)		For a global role, the external name refers to the DN of a group from a directory service that is mapped to the global role. This is not applicable to a local role.

6.332 DBA_ROLLBACK_SEGS

DBA_ROLLBACK_SEGS describes rollback segments.

Column	Datatype	NULL	Description
SEGMENT_NAME	VARCHAR2(30)	NOT NULL	Name of the rollback segment
OWNER	VARCHAR2(6)		Owner of the rollback segment: • PUBLIC • SYS
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of the tablespace containing the rollback segment
SEGMENT_ID	NUMBER	NOT NULL	ID number of the rollback segment
FILE_ID	NUMBER	NOT NULL	Absolute file number of the data file containing the segment header
BLOCK_ID	NUMBER	NOT NULL	ID number of the block containing the segment header
INITIAL_EXTENT	NUMBER		Initial extent size in bytes
NEXT_EXTENT	NUMBER		Secondary extent size in bytes
MIN_EXTENTS	NUMBER	NOT NULL	Minimum number of extents
MAX_EXTENTS	NUMBER	NOT NULL	Maximum number of extent
PCT_INCREASE	NUMBER		Percent increase for extent size
STATUS	VARCHAR2(16)		Rollback segment status: • OFFLINE • ONLINE • NEEDS RECOVERY • PARTLY AVAILABLE • UNDEFINED
INSTANCE_NUM	VARCHAR2(40)		Rollback segment owning Oracle Real Application Clusters instance number
RELATIVE_FNO	NUMBER	NOT NULL	Relative file number of the segment header

6.333 DBA_ROLLING_DATABASES

DBA_ROLLING_DATABASES lists all the databases eligible for configuration with rolling operations.

Column	Datatype	NULL	Description
RDBID	NUMBER		Rolling operation database identifier
DBID	NUMBER		Oracle database identifier
DBUN	VARCHAR2(128)		Database unique name
ROLE	VARCHAR2(8)		Database role
OPEN_MODE	VARCHAR2(15)		Open mode information
PARTICIPANT	VARCHAR2(3)		Indicates whether the database is participating in the rolling operation (YES) or not (NO)
VERSION	VARCHAR2(128)		RDBMS version number
ENGINE_STATUS	VARCHAR2(14)		Running status of the MRP-recovery or LSP-apply process
RAC	VARCHAR2(3)		Indicates whether the database is an Oracle Real Application Clusters (Oracle RAC) database

Column	Datatype	NULL	Description
UPDATE_PROGRESS	VARCHAR2(11)		Upgrade status of the system catalog
PROD_RSCN	VARCHAR(40)		Resetlogs SCN at which redo is currently being produced
PROD_RID	VARCHAR(40)		Resetlogs ID at which redo is currently being produced
PROD_SCN	VARCHAR(40)		Last SCN at which redo was produced
REDO_SOURCE	VARCHAR2(128)		Database unique name of the producer of redo being consumed
CONS_RSCN	VARCHAR(40)		Resetlogs SCN at which redo is currently being consumed
CONS_RID	VARCHAR(40)		Resetlogs ID at which redo is currently being consumed
CONS_SCN	VARCHAR(40)		Last SCN at which redo was consumed
UPDATE_TIME	TIMESTAMP(6)		Time of the last record update

See Also:

Oracle Data Guard Concepts and Administration for more information about rolling operations.

6.334 DBA_ROLLING_EVENTS

DBA_ROLLING_EVENTS lists all the events reported from the DBMS_ROLLING PL/SQL package.

Column	Datatype	NULL	Description
EVENTID	NUMBER		Event identifier which identifies event order
EVENT_TIME	TIMESTAMP(6)		Time associated with the event
TYPE	VARCHAR2(7)		Type of event: INFO, NOTICE, WARNING, or ERROR
MESSAGE	VARCHAR2(256)		Text describing the event details
STATUS	NUMBER		Status code associated with an event
INSTID	NUMBER		Instruction ID associated with an event
REVISION	NUMBER		Plan revision number associated with an event

See Also:

- *Oracle Data Guard Concepts and Administration* for more information about rolling operations.
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_ROLLING package

6.335 DBA_ROLLING_PARAMETERS

DBA_ROLLING_PARAMETERS lists the available parameters of the DBMS_ROLLING PL/SQL package.

Column	Datatype	NULL	Description
SCOPE	VARCHAR2(128)		Database unique name associated with a parameter
TYPE	VARCHAR2(7)		Type of parameter
NAME	VARCHAR2(32)		Name of the parameter
DESCRIPTION	VARCHAR2(256)		Description of the parameter
CURVAL	VARCHAR2(256)		Current value of the parameter
LSTVAL	VARCHAR2(256)		Prior value of the parameter
DEFVAL	VARCHAR2(256)		Default value of the parameter
MINVAL	NUMBER		Minimum value of the parameter
MAXVAL	NUMBER		Maximum value of the parameter

See Also:

- *Oracle Data Guard Concepts and Administration* for more information about rolling operations.
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_ROLLING package

6.336 DBA_ROLLING_PLAN

DBA_ROLLING_PLAN displays the instructions which constitute the active upgrade plan.

Each row in DBA_ROLLING_PLAN identifies a specific instruction scheduled to execute at a specific database. Instructions are created as a result of successful calls to the DBMS_ROLLING.BUILD_PLAN procedure.

During execution, groups of instructions are scheduled in batches to execute at remote databases. Groups of instructions are guaranteed to complete in BATCHID order.

Column	Datatype	NULL	Description
REVISION	NUMBER		Plan revision number associated with an instruction
BATCHID	NUMBER		Identifier for a batch of instructions which are requested together
INSTID	NUMBER		Identifier for a single instruction
SOURCE	VARCHAR2(128)		Database unique name where an instruction executes

Column	Datatype	NULL	Description
TARGET	VARCHAR2(128)		The site where a given instruction will execute
PHASE	VARCHAR2(14)		rolling operation phase in which an instruction executes
STATUS	VARCHAR2(7)		Scheduling status of the instruction
PROGRESS	VARCHAR2(10)		Execution progress of the instruction
DESCRIPTION	VARCHAR2(256)		Description of the instruction
EXEC_STATUS	NUMBER		Status code returned from instruction execution
EXEC_INFO	VARCHAR2(256)		Supplemental information obtained during instruction execution
EXEC_TIME	TIMESTAMP(6)		Time of instruction execution
FINISH_TIME	TIMESTAMP(6)		Time of instruction completion

See Also:

- *Oracle Data Guard Concepts and Administration* for more information about rolling operations.
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_ROLLING package

6.337 DBA_ROLLING_STATISTICS

DBA_ROLLING_STATISTICS provides a list of rolling operation statistics.

Column	Datatype	NULL	Description
NAME	VARCHAR2(256)		Name of the statistic. Possible values: • DBMS_ROLLING execution time • logical to primary switchover finish time • primary services offline for • primary to logical switchover start time • rolling upgrade finish time • rolling upgrade start time • time for former primary to fully recover upgrade redo • time for former primary to start upgrade redo recovery • total time former primary in physical role • transient logical creation finish time • transient logical creation start time • transient logical protection finish time • transient logical protection start time • user upgrade time

Column	Datatype	NULL	Description
VALUE	VARCHAR2(256)		Value of the statistic
UPDATE_TIME	TIMESTAMP(6)		Time of last update

> **See Also:**
>
> *Oracle Data Guard Concepts and Administration* for more information about rolling operations.

6.338 DBA_ROLLING_STATUS

DBA_ROLLING_STATUS displays the overall status of the rolling operation.

Column	Datatype	NULL	Description
REVISION	NUMBER		Revision number of the current upgrade plan
STATUS	VARCHAR2(12)		Readiness of the facility to begin or resume the rolling operation
PHASE	VARCHAR2(14)		Current phase of the plan
NEXT_INSTRUCTION	NUMBER		Instruction ID of the next pending instruction
REMAINING_INSTRUCTIONS	NUMBER		Number of remaining instructions to execute in the plan
COORDINATOR_INSTANCE	NUMBER		Instance number from which the rolling operation is being coordinated
COORDINATOR_PID	NUMBER		Process PID in which the rolling operation is being coordinated
ORIGINAL_PRIMARY	VARCHAR2(128)		Database unique name of the original primary
FUTURE_PRIMARY	VARCHAR2(128)		Database unique name of the future primary
TOTAL_DATABASES	NUMBER		Number of total databases eligible to participate in the rolling operation
PARTICIPATING_DATABASES	NUMBER		Number of databases configured to participate in the rolling operation
INIT_TIME	TIMESTAMP(6)		Time of the last call to DBMS_ROLLING.INIT_PLAN
BUILD_TIME	TIMESTAMP(6)		Time of the last call to DBMS_ROLLING.BUILD
START_TIME	TIMESTAMP(6)		Time of the last call to DBMS_ROLLING.START_UPGRADE
SWITCH_TIME	TIMESTAMP(6)		Time of the last call to DBMS_ROLLING.SWITCHOVER
FINISH_TIME	TIMESTAMP(6)		Time of the last call to DBMS_ROLLING.FINISH

> **See Also:**
>
> - *Oracle Data Guard Concepts and Administration* for more information about rolling operations.
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_ROLLING package

6.339 DBA_ROLLING_SUPPORT_MODE

DBA_ROLLING_SUPPORT_MODE displays information about whether tables in the database are supported for rolling upgrades performed using the DBMS_ROLLING package.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Table owner
TABLE_NAME	VARCHAR2(128)		Table name
SUPPORT_MODE	VARCHAR2(11)		Indicates whether the table is supported Possible values: • SUPPORTED - The table is fully supported • INTERNAL - The table is not supported because it contains data that should not be replicated. Such tables include mapping tables for index-organized tables, storage tables for nested tables, materialized view logs, secondary objects associated with domain indexes, and temporary tables. • UNSUPPORTED - The table is not supported because it contains a data type that is not supported or uses a feature that is not supported
EXPLANATION	VARCHAR2(4000)		Reason why the table is not fully supported This column is populated only when both of the following conditions are met: • The value of the COMPATIBLE initialization parameter is 20.0 or higher • The value of the SUPPORT_MODE column is INTERNAL or UNSUPPORTED

6.340 DBA_ROLLING_UNSUPPORTED

DBA_ROLLING_UNSUPPORTED displays the schemas, tables, and columns in those tables that contain unsupported data types for a rolling upgrade operation for a logical standby database using the DBMS_ROLLING PL/SQL package.

Use this view before you perform a rolling upgrade using DBMS_ROLLING to determine what is unsupported.

The data pertains to the container in which the view is queried.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Schema name of the unsupported column
TABLE_NAME	VARCHAR2(128)		Name of the table that the unsupported column belongs to
COLUMN_NAME	VARCHAR2(128)		Name of the unsupported column
ATTRIBUTES	VARCHAR2(4000)		When the value of the COMPATIBLE initialization parameter is 20.0 or higher, this column displays the reason the table is unsupported. Otherwise, this column displays the reason the table is unsupported only if the reason is not a data type issue.
DATA_TYPE	VARCHAR2(106)		Data type of the unsupported column

Note:

When the value of the COMPATIBLE initialization parameter is 20.0 or higher, this view displays all columns in unsupported tables. Otherwise, this view displays only the unsupported columns in unsupported tables.

Note:

A rolling upgrade using DBMS_ROLLING supports more object types than a manual rolling upgrade using transient logical standby databases

See Also:

- "DBA_LOGSTDBY_UNSUPPORTED" for more information about determining unsupported data types for a manual rolling upgrade operation using transient logical standby databases
- *Oracle Data Guard Concepts and Administration* for more information about rolling operations
- *Oracle Data Guard Concepts and Administration* for more information about unsupported tables for rolling upgrade operations
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_ROLLING package

6.341 DBA_RSRC_CATEGORIES

DBA_RSRC_CATEGORIES displays all resource consumer group categories.

Column	Datatype	NULL	Description
NAME	VARCHAR2(128)		Name of the consumer group category
COMMENTS	VARCHAR2(2000)		Text comment on the consumer group category
STATUS	VARCHAR2(128)		Indicates whether the consumer group category is part of the pending area (PENDING) or not (NULL)
MANDATORY	VARCHAR2(3)		Indicates whether the consumer group category is mandatory (YES) or not (NO)

6.342 DBA_RSRC_CONSUMER_GROUP_PRIVS

DBA_RSRC_CONSUMER_GROUP_PRIVS displays information about all resource consumer groups and the users and roles assigned to them.

The grant referred to in this view and the related view is the grant of the SWITCH_CONSUMER_GROUP object privilege, which is granted using the DBMS_RESOURCE_MANAGER_PRIVS package. This privilege is not granted through the GRANT SQL statement.

Related View

USER_RSRC_CONSUMER_GROUP_PRIVS displays information about the resource consumer groups to which the current user is assigned. This view does not display the GRANTEE column.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)	NOT NULL	User or role receiving the grant
GRANTED_GROUP	VARCHAR2(128)		Granted consumer group name
GRANT_OPTION	VARCHAR2(3)		Indicates whether the grant was with the GRANT option (YES) or not (NO)
INITIAL_GROUP	VARCHAR2(3)		Indicates whether the consumer group is designated as the default for this user or role (YES) or not (NO)

See Also:

- "USER_RSRC_CONSUMER_GROUP_PRIVS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_RESOURCE_MANAGER_PRIVS package

6.343 DBA_RSRC_CONSUMER_GROUPS

DBA_RSRC_CONSUMER_GROUPS displays information about all resource consumer groups in the database.

Column	Datatype	NULL	Description
CONSUMER_GROUP_ID	NUMBER	NOT NULL	ID of the consumer group
CONSUMER_GROUP	VARCHAR2(128)		Name of the consumer group
CPU_METHOD	VARCHAR2(128)		CPU resource allocation method for the consumer group
MGMT_METHOD	VARCHAR2(128)		Resource allocation method for the consumer group
INTERNAL_USE	VARCHAR2(3)		Indicates whether the consumer group is for internal use only (YES) or not (NO)
COMMENTS	VARCHAR2(2000)		Text comment on the consumer group
CATEGORY	VARCHAR2(128)		Category of the consumer group
STATUS	VARCHAR2(128)		Indicates whether the consumer group is part of the pending area (PENDING) or not (NULL)
MANDATORY	VARCHAR2(3)		Indicates whether the consumer group is mandatory (YES) or not (NO)

6.344 DBA_RSRC_GROUP_MAPPINGS

DBA_RSRC_GROUP_MAPPINGS displays the mapping between session attributes and consumer groups in the database.

Column	Datatype	NULL	Description
ATTRIBUTE	VARCHAR2(128)		Session attribute to match
VALUE	VARCHAR2(128)		Attribute value
CONSUMER_GROUP	VARCHAR2(128)		Target consumer group name
STATUS	VARCHAR2(128)		Indicates whether the consumer group is part of the pending area (PENDING) or not (NULL)

6.345 DBA_RSRC_IO_CALIBRATE

DBA_RSRC_IO_CALIBRATE displays I/O calibration results for the latest calibration run.

Column	Datatype	NULL	Description
START_TIME	TIMESTAMP(6)		Start time of the most recent I/O calibration
END_TIME	TIMESTAMP(6)		End time of the most recent I/O calibration
MAX_IOPS	NUMBER		Maximum number of data block read requests that can be sustained per second
MAX_MBPS	NUMBER		Maximum megabytes per second of maximum-sized read requests that can be sustained
MAX_PMBPS	NUMBER		Maximum megabytes per second of large I/O requests that can be sustained by a single process
LATENCY	NUMBER		Latency for data block read requests
NUM_PHYSICAL_DISKS	NUMBER		Number of physical disks in the storage subsystem (as specified by the user)

Column	Datatype	NULL	Description
ADDITIONAL_INFO	VARCHAR2(1024)		Additional information about the most recent calibration run

6.346 DBA_RSRC_MANAGER_SYSTEM_PRIVS

DBA_RSRC_MANAGER_SYSTEM_PRIVS displays information about all the users and roles that have been granted the ADMINISTER_RESOURCE_MANAGER system privilege, which is granted using the DBMS_RESOURCE_MANAGER_PRIVS package.

This privilege is not granted through the GRANT SQL statement.

Related View

USER_RSRC_MANAGER_SYSTEM_PRIVS displays information about the users who are granted system privileges for the DBMS_RESOURCE_MANAGER package. This view does not display the GRANTEE column.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)	NOT NULL	User or role receiving the grant
PRIVILEGE	VARCHAR2(40)	NOT NULL	Name of the system privilege
ADMIN_OPTION	VARCHAR2(3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)

See Also:

- "USER_RSRC_MANAGER_SYSTEM_PRIVS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_RESOURCE_MANAGER package

6.347 DBA_RSRC_MAPPING_PRIORITY

DBA_RSRC_MAPPING_PRIORITY displays information about all consumer group mapping attribute priorities.

Column	Datatype	NULL	Description
ATTRIBUTE	VARCHAR2(128)		Session attribute
PRIORITY	NUMBER		Priority (1 is the highest)
STATUS	VARCHAR2(128)		Indicates whether the consumer group is part of the pending area (PENDING) or not (NULL)

6.348 DBA_RSRC_PLAN_DIRECTIVES

DBA_RSRC_PLAN_DIRECTIVES displays information about all resource plan directives in the database.

Column	Datatype	NULL	Description
PLAN	VARCHAR2(128)		Name of the plan to which the directive belongs
GROUP_OR_SUBPLAN	VARCHAR2(128)		Name of the consumer group or subplan referred to
TYPE	VARCHAR2(14)		Indicates whether GROUP_OR_SUBPLAN refers to a consumer group (CONSUMER_GROUP) or a plan (PLAN)
CPU_P1	NUMBER		This column is deprecated. Use the MGMT_P1 column instead.
CPU_P2	NUMBER		This column is deprecated. Use the MGMT_P2 column instead.
CPU_P3	NUMBER		This column is deprecated. Use the MGMT_P3 column instead.
CPU_P4	NUMBER		This column is deprecated. Use the MGMT_P4 column instead.
CPU_P5	NUMBER		This column is deprecated. Use the MGMT_P5 column instead.
CPU_P6	NUMBER		This column is deprecated. Use the MGMT_P6 column instead.
CPU_P7	NUMBER		This column is deprecated. Use the MGMT_P7 column instead.
CPU_P8	NUMBER		This column is deprecated. Use the MGMT_P8 column instead.
MGMT_P1	NUMBER		Resource allocation at level 1. For share-based plans, indicates the number of shares.
MGMT_P2	NUMBER		Resource allocation at level 2.
MGMT_P3	NUMBER		Resource allocation at level 3.
MGMT_P4	NUMBER		Resource allocation at level 4.
MGMT_P5	NUMBER		Resource allocation at level 5.
MGMT_P6	NUMBER		Resource allocation at level 6.
MGMT_P7	NUMBER		Resource allocation at level 7.
MGMT_P8	NUMBER		Resource allocation at level 8.
ACTIVE_SESS_POOL_P1	NUMBER		Maximum number of calls this consumer group can run concurrently
QUEUEING_P1	NUMBER		Timeout in seconds for waits in the Active Session Limit queue
PARALLEL_TARGET_PERCENTAGE	NUMBER		This column is deprecated. Use the PARALLEL_SERVER_LIMIT column instead.
PARALLEL_DEGREE_LIMIT_P1	NUMBER		Sessions in this consumer group are limited to this maximum degree of parallelism for all parallel operations

Column	Datatype	NULL	Description
SWITCH_GROUP	VARCHAR2(128)		Group to switch to once the switch time is reached
SWITCH_FOR_CALL	VARCHAR2(5)		Indicates whether to switch back to the initial consumer group once the top call has completed (TRUE) or not (FALSE)
SWITCH_TIME	NUMBER		Amount of run time (in seconds) within a group before the session is automatically switched. As with other switch directives, if SWITCH_FOR_CALL is TRUE, the run time is accumulated from the start of a call. Otherwise, the run time is accumulated for the length of the session.
SWITCH_IO_MEGABYTES	NUMBER		The maximum megabytes of I/O within a group that will trigger the action specified by SWITCH_GROUP. As with other switch directives, if SWITCH_FOR_CALL is TRUE, the maximum megabytes of I/O is accumulated from the start of a call. Otherwise, the maximum megabytes of I/O is accumulated for the length of the session.
SWITCH_IO_REQS	NUMBER		The maximum I/O requests within a group that will trigger the action specified by SWITCH_GROUP. As with other switch directives, if SWITCH_FOR_CALL is TRUE, the maximum I/O requests is accumulated from the start of a call. Otherwise, the maximum I/O requests is accumulated for the length of the session.
SWITCH_ESTIMATE	VARCHAR2(5)		Indicates whether estimated execution time should be used for switch criteria (TRUE) or not (FALSE)
MAX_EST_EXEC_TIME	NUMBER		Maximum estimated execution time
UNDO_POOL	NUMBER		Undo pool size for the consumer group
MAX_IDLE_TIME	NUMBER		Maximum idle time for the session
MAX_IDLE_BLOCKER_TIME	NUMBER		Maximum idle time for the session when blocking other sessions
MAX_UTILIZATION_LIMIT	NUMBER		This column is deprecated. Use UTILIZATION_LIMIT instead.
PARALLEL_QUEUE_TIMEOUT	NUMBER		Time (in seconds) that a query can remain in the parallel statement queue for the consumer group before it is removed from the queue. The PQ_TIMEOUT_ACTION directive in a Resource Manager plan can be used in conjunction with the PARALLEL_QUEUE_TIMEOUT directive to either cancel or run the removed query. If the PQ_TIMEOUT_ACTION directive is not specified, the default behavior is to cancel the query with ORA-07454.
SWITCH_TIME_IN_CALL	NUMBER		This column is deprecated. Specify the time in the SWITCH_TIME directive and set SWITCH_FOR_CALL to TRUE.

Column	Datatype	NULL	Description
SWITCH_IO_LOGICAL	NUMBER		The number of logical I/Os that will trigger the action specified by SWITCH_GROUP. As with other switch directives, if SWITCH_FOR_CALL is TRUE, the number of logical I/Os is accumulated from the start of a call. Otherwise, the number of logical IOs is accumulated for the length of the session.
SWITCH_ELAPSED_TIME	NUMBER		The elapsed time that will trigger the action specified by SWITCH_GROUP. As with other switch directives, if SWITCH_FOR_CALL is TRUE, the elapsed time is accumulated from the start of a call. Otherwise, the elapsed time is accumulated for the length of the session.
PARALLEL_SERVER_LIMIT	NUMBER		Maximum percentage of the parallel target used before queuing subsequent parallel queries
UTILIZATION_LIMIT	NUMBER		Maximum resource utilization allowed, expressed in percentage
PARALLEL_STMT_CRITICAL	VARCHAR2(12)		Indicates whether parallel statements from this consumer group are eligible for queuing in the parallel statement queue: • BYPASS QUEUE - Parallel statements in this consumer group are critical and should never be queued. • QUEUE - All parallel statements in this consumer group, irrespective of the PARALLEL_DEGREE_POLICY initialization parameter value, are eligible for being queued. • FALSE - Certain parallel statements are eligible for queuing, depending on the PARALLEL_DEGREE_POLICY initialization parameter value. This is the default.
SESSION_PGA_LIMIT	NUMBER		The maximum amount of untunable PGA in MB that sessions in this consumer group can allocate before being terminated
PQ_TIMEOUT_ACTION	VARCHAR2(6)		Indicates the action to be taken on a parallel query in the parallel queue when its queue time exceeds the limit set by the Resource Manager plan's PARALLEL_QUEUE_TIMEOUT directive: • CANCEL - The statement terminates with error ORA-07454 • RUN - The statement runs immediately, and may get downgraded if parallel servers are unavailable
COMMENTS	VARCHAR2(2000)		Text comment on the plan directive

Column	Datatype	NULL	Description
STATUS	VARCHAR2(128)		Indicates whether the plan directive is part of the pending area (PENDING) or not (NULL). **Note:** PDB resource plans must be single-level, they cannot contain subplans, and they must have 8 or fewer consumer groups. If a resource plan is imported into a PDB and it violates any of these PDB requirements, then the import will automatically convert the resource plan to a compliant version. The original, unmodified resource plan will be stored with a STATUS of LEGACY.
MANDATORY	VARCHAR2(3)		Indicates whether the plan directive is mandatory (YES) or not (NO). Mandatory plans cannot be deleted.

See Also:

- "PARALLEL_DEGREE_POLICY"
- *Oracle Database Administrator's Guide* for information on resource plans in general
- *Oracle Database PL/SQL Packages and Types Reference* for information about specifying Resource Manager directive values using the DBMS_RESOURCE_MANAGER.CREATE_PLAN_DIRECTIVE procedure

6.349 DBA_RSRC_PLANS

DBA_RSRC_PLANS displays information about all resource plans in the database.

For a list of currently active plans, see "V$RSRC_PLAN".

Column	Datatype	NULL	Description
PLAN_ID	NUMBER	NOT NULL	ID number of the resource plan
PLAN	VARCHAR2(128)		Name of the resource plan
NUM_PLAN_DIRECTIVES	NUMBER		Number of plan directives for the plan
CPU_METHOD	VARCHAR2(128)		CPU resource allocation method for the plan
MGMT_METHOD	VARCHAR2(128)		Resource allocation method for the plan
ACTIVE_SESS_POOL_MTH	VARCHAR2(128)		Active session pool resource allocation method for the plan
PARALLEL_DEGREE_LIMIT_MTH	VARCHAR2(128)		Parallel degree limit resource allocation method for the plan
QUEUING_MTH	VARCHAR2(128)		Queuing resource allocation method for the plan
SUB_PLAN	VARCHAR2(3)		Indicates whether the plan is a subplan (YES) or not (NO)
COMMENTS	VARCHAR2(2000)		Text comment on the plan

Column	Datatype	NULL	Description
STATUS	VARCHAR2(128)		Indicates whether the plan is part of the pending area (PENDING) or not (NULL)
MANDATORY	VARCHAR2(3)		Indicates whether the plan is mandatory (YES) or not (NO). Mandatory plans cannot be deleted.

See Also:

- *Oracle Database Administrator's Guide* for information on resource plans in general
- *Oracle Database PL/SQL Packages and Types Reference* for more information on creating resource plans with the DBMS_RESOURCE_MANAGER package

6.350 DBA_RULE_SET_RULES

DBA_RULE_SET_RULES describes the rules in all rule sets in the database. Its columns are the same as those in ALL_RULE_SET_RULES.

See Also:

"ALL_RULE_SET_RULES"

6.351 DBA_RULE_SETS

DBA_RULE_SETS describes all rule sets in the database. Its columns are the same as those in ALL_RULE_SETS.

See Also:

"ALL_RULE_SETS"

6.352 DBA_RULES

DBA_RULES describes all rules in the database. Its columns are the same as those in ALL_RULES.

See Also:

"ALL_RULES"

6.353 DBA_SAGA_BROKERS

DBA_SAGA_BROKERS displays all saga brokers in the database.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_BROKERS"

6.354 DBA_SAGA_DETAILS

DBA_SAGA_DETAILS displays details for all sagas in the database. Its columns are the same as those in ALL_SAGA_DETAILS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_DETAILS"

6.355 DBA_SAGA_ERRORS

DBA_SAGA_ERRORS describes errors generated by all sagas in the database. Its columns are the same as those in ALL_SAGA_ERRORS.

This view displays sagas that were either initiated in the current PDB or joined by participants in the current PDB.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_ERRORS"

6.356 DBA_SAGA_FINALIZATION

`DBA_SAGA_FINALIZATION` displays information about pending finalization actions for all sagas in the database. Its columns are the same as those in `ALL_SAGA_FINALIZATION`.

This view displays one row for each unique reservable table updated as part of a participant transaction for sagas that were either initiated in the current PDB or joined by participants in the current PDB.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_FINALIZATION"

6.357 DBA_SAGA_PARTICIPANT_SET

`DBA_SAGA_PARTICIPANT_SET` displays information about saga participants for all sagas in the database. Its columns are the same as those in `ALL_SAGA_PARTICIPANT_SET`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_PARTICIPANT_SET"

6.358 DBA_SAGA_PARTICIPANTS

`DBA_SAGA_PARTICIPANTS` describes all saga participants in the database. Its columns are the same as those in `ALL_SAGA_PARTICIPANTS`.

This view displays sagas that were either initiated in the current PDB or joined by participants or coordinators in the current PDB.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_PARTICIPANTS"

6.359 DBA_SAGA_PENDING

`DBA_SAGA_PENDING` describes all pending sagas in the database. Its columns are the same as those in `ALL_SAGA_PENDING`.

This view displays sagas that were initiated in the current PDB.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_PENDING"

6.360 DBA_SAGAS

`DBA_SAGAS` describes all active sagas in the database. Its columns are the same as those in `ALL_SAGAS`.

This view displays sagas that were either initiated in the current PDB or joined by participants in the current PDB.

> **Note:**
>
> This view displays active sagas. Completed sagas are displayed in the DBA_HIST_SAGAS view.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGAS"

6.361 DBA_SCHEDULER_CHAIN_RULES

`DBA_SCHEDULER_CHAIN_RULES` displays information about the rules for all chains in the database. Its columns are the same as those in `ALL_SCHEDULER_CHAIN_RULES`.

> **See Also:**
>
> "ALL_SCHEDULER_CHAIN_RULES"

6.362 DBA_SCHEDULER_CHAIN_STEPS

`DBA_SCHEDULER_CHAIN_STEPS` displays information about the defined steps of all chains in the database. Its columns are the same as those in `ALL_SCHEDULER_CHAIN_STEPS`.

> **See Also:**
>
> "ALL_SCHEDULER_CHAIN_STEPS"

6.363 DBA_SCHEDULER_CHAINS

DBA_SCHEDULER_CHAINS displays information about all chains in the database. Its columns are the same as those in ALL_SCHEDULER_CHAINS.

> **See Also:**
>
> "ALL_SCHEDULER_CHAINS"

6.364 DBA_SCHEDULER_CREDENTIALS

DBA_SCHEDULER_CREDENTIALS displays information about all credentials in the database. Its columns are the same as those in ALL_SCHEDULER_CREDENTIALS.

> **Note:**
>
> This view is deprecated in favor of the DBA_CREDENTIALS view. Oracle recommends that you use DBA_CREDENTIALS instead. DBA_SCHEDULER_CREDENTIALS is retained for backward compatibility only.

> **See Also:**
>
> - "DBA_CREDENTIALS"
> - "ALL_SCHEDULER_CREDENTIALS"

6.365 DBA_SCHEDULER_DB_DESTS

DBA_SCHEDULER_DB_DESTS displays information about all destination objects in the database pointing to remote databases. Its columns are the same as those in ALL_SCHEDULER_DB_DESTS.

> **See Also:**
>
> "ALL_SCHEDULER_DB_DESTS"

6.366 DBA_SCHEDULER_DESTS

DBA_SCHEDULER_DESTS displays information about all destination objects for jobs in the database. Its columns are the same as those in ALL_SCHEDULER_DESTS.

> **See Also:**
>
> "ALL_SCHEDULER_DESTS"

6.367 DBA_SCHEDULER_EXTERNAL_DESTS

DBA_SCHEDULER_EXTERNAL_DESTS displays information about all destination objects in the database pointing to remote agents. Its columns are the same as those in ALL_SCHEDULER_EXTERNAL_DESTS.

> **See Also:**
>
> "ALL_SCHEDULER_EXTERNAL_DESTS"

6.368 DBA_SCHEDULER_FILE_WATCHERS

DBA_SCHEDULER_FILE_WATCHERS displays information about all scheduler file watch requests in the database. Its columns are the same as those in ALL_SCHEDULER_FILE_WATCHERS.

> **See Also:**
>
> "ALL_SCHEDULER_FILE_WATCHERS"

6.369 DBA_SCHEDULER_GLOBAL_ATTRIBUTE

DBA_SCHEDULER_GLOBAL_ATTRIBUTE displays the values of all scheduler attributes in the database (for example, DEFAULT_TIMEZONE and CURRENT_OPEN_WINDOW). Its columns are the same as those in ALL_SCHEDULER_GLOBAL_ATTRIBUTE.

> **See Also:**
>
> "ALL_SCHEDULER_GLOBAL_ATTRIBUTE"

6.370 DBA_SCHEDULER_GROUP_MEMBERS

DBA_SCHEDULER_GROUP_MEMBERS displays information about the members of all Scheduler object groups in the database. Its columns are the same as those in ALL_SCHEDULER_GROUP_MEMBERS.

> **See Also:**
>
> "ALL_SCHEDULER_GROUP_MEMBERS"

6.371 DBA_SCHEDULER_GROUPS

DBA_SCHEDULER_GROUPS displays information about all Scheduler object groups in the database. Its columns are the same as those in ALL_SCHEDULER_GROUPS.

> **See Also:**
>
> "ALL_SCHEDULER_GROUPS"

6.372 DBA_SCHEDULER_IN_MEMORY_TRACE

DBA_SCHEDULER_IN_MEMORY_TRACE displays scheduler in-memory trace information generated by all user processes in the database.

Column	Datatype	NULL	Description
USER#	NUMBER		Oracle identifier of the user generating scheduler trace
USERNAME	VARCHAR2(128)		Name of the user generating scheduler trace
PROCESSNAME	VARCHAR2(5)		Name of the process generating scheduler trace
SPID	VARCHAR2(24)		Operating system identifier of the process generating scheduler trace
PADDR	RAW(8)		Address of the process state object generating scheduler trace
TRACE_ST	CLOB		Scheduler trace generated by the process

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

6.373 DBA_SCHEDULER_INCOMPAT_MEMBER

DBA_SCHEDULER_INCOMPAT_MEMBER displays all Scheduler incompatibility resource objects members in the database. Its columns are the same as those in ALL_SCHEDULER_INCOMPAT_MEMBER.

> **See Also:**
>
> "ALL_SCHEDULER_INCOMPAT_MEMBER"

6.374 DBA_SCHEDULER_INCOMPATS

DBA_SCHEDULER_INCOMPATS displays all Scheduler incompatibility resource objects in the database. Its columns are the same as those in ALL_SCHEDULER_INCOMPATS.

> **See Also:**
>
> "ALL_SCHEDULER_INCOMPATS"

6.375 DBA_SCHEDULER_JOB_ARGS

DBA_SCHEDULER_JOB_ARGS displays information about the arguments of all Scheduler jobs in the database. Its columns are the same as those in ALL_SCHEDULER_JOB_ARGS.

> **See Also:**
>
> "ALL_SCHEDULER_JOB_ARGS"

6.376 DBA_SCHEDULER_JOB_CLASSES

DBA_SCHEDULER_JOB_CLASSES displays information about all Scheduler job classes in the database. Its columns are the same as those in ALL_SCHEDULER_JOB_CLASSES.

> **See Also:**
>
> "ALL_SCHEDULER_JOB_CLASSES"

6.377 DBA_SCHEDULER_JOB_DESTS

DBA_SCHEDULER_JOB_DESTS displays information about the state of all jobs in the database at each of their destinations. Its columns are the same as those in ALL_SCHEDULER_JOB_DESTS.

> **See Also:**
>
> "ALL_SCHEDULER_JOB_DESTS"

6.378 DBA_SCHEDULER_JOB_LOG

DBA_SCHEDULER_JOB_LOG displays log information for all Scheduler jobs in the database. Its columns are the same as those in ALL_SCHEDULER_JOB_LOG.

> **See Also:**
>
> "ALL_SCHEDULER_JOB_LOG"

6.379 DBA_SCHEDULER_JOB_ROLES

DBA_SCHEDULER_JOB_ROLES displays information about all Scheduler jobs in the database by database role.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the Scheduler job
JOB_NAME	VARCHAR2(128)	NOT NULL	Name of the Scheduler job
JOB_SUBNAME	VARCHAR2(128)		Subname of the Scheduler job (for a job running a chain step)
JOB_CREATOR	VARCHAR2(128)		Creator of the Scheduler job
DATABASE_ROLE	VARCHAR2(16)		Name of the database role
PROGRAM_OWNER	VARCHAR2(4000)		Owner of the program associated with the job
PROGRAM_NAME	VARCHAR2(4000)		Name of the program associated with the job
JOB_TYPE	VARCHAR2(16)		Inline job action type: • PLSQL_BLOCK • STORED_PROCEDURE • EXECUTABLE • CHAIN
JOB_ACTION	VARCHAR2(4000)		Inline job action
JOB_CLASS	VARCHAR2(128)		Name of the job class associated with the job
SCHEDULE_OWNER	VARCHAR2(4000)		Owner of the schedule that the job uses (can be a window or a window group)

Column	Datatype	NULL	Description
SCHEDULE_NAME	VARCHAR2(4000)		Name of the schedule that the job uses (can be a window or a window group)
SCHEDULE_TYPE	VARCHAR2(12)		Type of the schedule that the job uses: • IMMEDIATE - Start date and repeat interval are NULL • ONCE - Repeat interval is NULL • PLSQL - PL/SQL expression used as schedule • CALENDAR - Oracle calendaring expression used as schedule • EVENT - Event schedule • NAMED - Named schedule • WINDOW - Window used as schedule • WINDOW_GROUP - Window group used as schedule
START_DATE	TIMESTAMP(6) WITH TIME ZONE		Original scheduled start date of the job (for an inline schedule)
REPEAT_INTERVAL	VARCHAR2(4000)		Inline schedule PL/SQL expression or calendar string
END_DATE	TIMESTAMP(6) WITH TIME ZONE		Date after which the job will no longer run (for an inline schedule)
LAST_START_DATE	TIMESTAMP(6) WITH TIME ZONE		Last date on which the job ran
ENABLED	VARCHAR2(5)		Indicates whether the job is enabled (TRUE) or disabled (FALSE)
STATE	VARCHAR2(15)		Current state of the job: • DISABLED • RETRY SCHEDULED • SCHEDULED • RUNNING • COMPLETED • BROKEN • FAILED • REMOTE • SUCCEEDED • CHAIN_STALLED
COMMENTS	VARCHAR2(4000)		Comments on the job

6.380 DBA_SCHEDULER_JOB_RUN_DETAILS

DBA_SCHEDULER_JOB_RUN_DETAILS displays log run details for all Scheduler jobs in the database. Its columns are the same as those in ALL_SCHEDULER_JOB_RUN_DETAILS.

> **See Also:**
>
> "ALL_SCHEDULER_JOB_RUN_DETAILS"

6.381 DBA_SCHEDULER_JOBS

DBA_SCHEDULER_JOBS displays information about all Scheduler jobs in the database. Its columns are the same as those in ALL_SCHEDULER_JOBS.

> **See Also:**
>
> "ALL_SCHEDULER_JOBS"

6.382 DBA_SCHEDULER_NOTIFICATIONS

DBA_SCHEDULER_NOTIFICATIONS displays information about the E-mail notifications for all jobs in the database. Its columns are the same as those in ALL_SCHEDULER_NOTIFICATIONS.

> **See Also:**
>
> "ALL_SCHEDULER_NOTIFICATIONS"

6.383 DBA_SCHEDULER_PROGRAM_ARGS

DBA_SCHEDULER_PROGRAM_ARGS displays information about the arguments of all Scheduler programs in the database. Its columns are the same as those in ALL_SCHEDULER_PROGRAM_ARGS.

> **See Also:**
>
> "ALL_SCHEDULER_PROGRAM_ARGS"

6.384 DBA_SCHEDULER_PROGRAMS

DBA_SCHEDULER_PROGRAMS displays information about all Scheduler programs in the database. Its columns are the same as those in ALL_SCHEDULER_PROGRAMS.

> **See Also:**
>
> "ALL_SCHEDULER_PROGRAMS"

6.385 DBA_SCHEDULER_REMOTE_DATABASES

DBA_SCHEDULER_REMOTE_DATABASES displays information about all remote databases that have been registered as sources and destinations for remote database jobs. Its columns are the same as those in ALL_SCHEDULER_REMOTE_DATABASES.

> **See Also:**
>
> "ALL_SCHEDULER_REMOTE_DATABASES"

6.386 DBA_SCHEDULER_REMOTE_JOBSTATE

DBA_SCHEDULER_REMOTE_JOBSTATE displays information about the state of all jobs at remote databases. Its columns are the same as those in ALL_SCHEDULER_REMOTE_JOBSTATE.

> **See Also:**
>
> "ALL_SCHEDULER_REMOTE_JOBSTATE"

6.387 DBA_SCHEDULER_RESOURCES

DBA_SCHEDULER_RESOURCES displays all scheduler resource objects in the database. Its columns are the same as those in ALL_SCHEDULER_RESOURCES.

> **See Also:**
>
> "ALL_SCHEDULER_RESOURCES"

6.388 DBA_SCHEDULER_RSC_CONSTRAINTS

DBA_SCHEDULER_RSC_CONSTRAINTS lists all Oracle Scheduler resource constraint members in the database. Its columns are the same as those in ALL_SCHEDULER_RSC_CONSTRAINTS.

> **See Also:**
>
> "ALL_SCHEDULER_RSC_CONSTRAINTS"

6.389 DBA_SCHEDULER_RUNNING_CHAINS

DBA_SCHEDULER_RUNNING_CHAINS displays information about the chain steps of all running chains in the database. Its columns are the same as those in ALL_SCHEDULER_RUNNING_CHAINS.

> **See Also:**
>
> "ALL_SCHEDULER_RUNNING_CHAINS"

6.390 DBA_SCHEDULER_RUNNING_JOBS

DBA_SCHEDULER_RUNNING_JOBS displays information about all running Scheduler jobs in the database. Its columns are the same as those in ALL_SCHEDULER_RUNNING_JOBS.

> **See Also:**
>
> "ALL_SCHEDULER_RUNNING_JOBS"

6.391 DBA_SCHEDULER_SCHEDULES

DBA_SCHEDULER_SCHEDULES displays information about all Scheduler schedules in the database. Its columns are the same as those in ALL_SCHEDULER_SCHEDULES.

> **See Also:**
>
> "ALL_SCHEDULER_SCHEDULES"

6.392 DBA_SCHEDULER_WINDOW_DETAILS

DBA_SCHEDULER_WINDOW_DETAILS displays log details for all Scheduler windows in the database. Its columns are the same as those in ALL_SCHEDULER_WINDOW_DETAILS.

> **See Also:**
>
> "ALL_SCHEDULER_WINDOW_DETAILS"

6.393 DBA_SCHEDULER_WINDOW_GROUPS

DBA_SCHEDULER_WINDOW_GROUPS displays information about all Scheduler window groups in the database. Its columns are the same as those in ALL_SCHEDULER_WINDOW_GROUPS.

> **See Also:**
>
> "ALL_SCHEDULER_WINDOW_GROUPS"

6.394 DBA_SCHEDULER_WINDOW_LOG

DBA_SCHEDULER_WINDOW_LOG displays log information for all Scheduler windows in the database. Its columns are the same as those in ALL_SCHEDULER_WINDOW_LOG.

> **See Also:**
>
> "ALL_SCHEDULER_WINDOW_LOG"

6.395 DBA_SCHEDULER_WINDOWS

DBA_SCHEDULER_WINDOWS displays information about all Scheduler windows in the database. Its columns are the same as those in ALL_SCHEDULER_WINDOWS.

> **See Also:**
>
> "ALL_SCHEDULER_WINDOWS"

6.396 DBA_SCHEDULER_WINGROUP_MEMBERS

DBA_SCHEDULER_WINGROUP_MEMBERS displays the members of all Scheduler window groups in the database. Its columns are the same as those in ALL_SCHEDULER_WINGROUP_MEMBERS.

> **See Also:**
>
> "ALL_SCHEDULER_WINGROUP_MEMBERS"

6.397 DBA_SCHEMA_PRIVS

DBA_SCHEMA_PRIVS describes schema privileges granted to users and roles.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)		Grantee name, user, or role receiving the grant
PRIVILEGE	VARCHAR2(40)		Schema privilege
SCHEMA	VARCHAR2(128)		Schema on which the privilege was granted
ADMIN_OPTION	VARCHAR2(3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the grant was inherited from another container (YES) or not (NO)

Note:

This view is available starting with Oracle Database 23ai.

See Also:

"USER_SCHEMA_PRIVS"

6.398 DBA_SEC_RELEVANT_COLS

DBA_SEC_RELEVANT_COLS describes the security relevant columns of all security policies in the database. Its columns are the same as those in ALL_SEC_RELEVANT_COLS.

See Also:

"ALL_SEC_RELEVANT_COLS"

6.399 DBA_SECONDARY_OBJECTS

DBA_SECONDARY_OBJECTS provides information about all secondary objects that are associated with domain indexes in the database.

This view is only relevant in the context of domain indexes. Its columns are the same as those in "ALL_SECONDARY_OBJECTS".

6.400 DBA_SEGMENTS

DBA_SEGMENTS describes the storage allocated for all segments in the database.

Related View

USER_SEGMENTS describes the storage allocated for the segments owned by the current user's objects. This view does not display the OWNER, HEADER_FILE, HEADER_BLOCK, or RELATIVE_FNO columns.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Username of the segment owner
SEGMENT_NAME	VARCHAR2(128)		Name, if any, of the segment
PARTITION_NAME	VARCHAR2(128)		Object Partition Name (Set to NULL for nonpartitioned objects)
SEGMENT_TYPE	VARCHAR2(18)		Type of segment: • NESTED TABLE • TABLE • TABLE PARTITION • CLUSTER • LOBINDEX • INDEX • INDEX PARTITION • LOBSEGMENT • TABLE SUBPARTITION • INDEX SUBPARTITION • LOB PARTITION • LOB SUBPARTITION • ROLLBACK • TYPE2 UNDO • DEFERRED ROLLBACK • TEMPORARY • CACHE • SPACE HEADER • UNDEFINED
SEGMENT_SUBTYPE	VARCHAR2(10)		Subtype of LOB segment: SECUREFILE, ASSM, MSSM, and NULL
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace containing the segment
HEADER_FILE	NUMBER		Absolute file number of the data file containing the segment header
HEADER_BLOCK	NUMBER		ID of the block containing the segment header

Column	Datatype	NULL	Description
BYTES	NUMBER		Size, in bytes, of the segment
BLOCKS	NUMBER		Size, in Oracle blocks, of the segment
EXTENTS	NUMBER		Number of extents allocated to the segment
INITIAL_EXTENT	NUMBER		Size in bytes requested for the initial extent of the segment at create time. (Oracle rounds the extent size to multiples of 5 blocks if the requested size is greater than 5 blocks.)
NEXT_EXTENT	NUMBER		Size in bytes of the next extent to be allocated to the segment
MIN_EXTENTS	NUMBER		Minimum number of extents allowed in the segment
MAX_EXTENTS	NUMBER		Maximum number of extents allowed in the segment
MAX_SIZE	NUMBER		Maximum number of blocks allowed in the segment
RETENTION	VARCHAR2(7)		Retention option for SECUREFILE segment
MINRETENTION	NUMBER		Minimum retention duration for SECUREFILE segment
PCT_INCREASE	NUMBER		Percent by which to increase the size of the next extent to be allocated
FREELISTS	NUMBER		Number of process freelists allocated to this segment
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to this segment
RELATIVE_FNO	NUMBER		Relative file number of the segment header
BUFFER_POOL	VARCHAR2(7)		Buffer pool to be used for segment blocks: • DEFAULT • KEEP • RECYCLE
FLASH_CACHE	VARCHAR2(7)		Database Smart Flash Cache hint to be used for segment blocks: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2(7)		Cell flash cache hint to be used for segment blocks: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
INMEMORY	VARCHAR2(8)		Indicates whether the In-Memory Column Store (IM column store) is enabled (ENABLED) or disabled (DISABLED) for this segment

Column	Datatype	NULL	Description
INMEMORY_PRIORITY	VARCHAR2(8)		Indicates the priority for In-Memory Column Store (IM column store) population: • LOW • MEDIUM • HIGH • CRITICAL • NONE • NULL
INMEMORY_DISTRIBUTE	VARCHAR2(15)		Indicates how the IM column store is distributed in an Oracle Real Application Clusters (Oracle RAC) environment: • AUTO • BY ROWID RANGE • BY PARTITION • BY SUBPARTITION
INMEMORY_DUPLICATE	VARCHAR2(13)		Indicates the duplicate setting for the IM column store in an Oracle RAC environment: • NO DUPLICATE • DUPLICATE • DUPLICATE ALL
INMEMORY_COMPRESSION	VARCHAR2(17)		Indicates the compression level for the IM column store: • NO MEMCOMPRESS • FOR DML • FOR QUERY [LOW | HIGH] • FOR CAPACITY [LOW | HIGH] • AUTO • NULL
CELLMEMORY[11]	VARCHAR2(24)		The value for columnar compression in the storage cell flash cache. Possible values: • ENABLED: Oracle Exadata Storage will decide automatically whether to cache in columnar form • DISABLED: Oracle Exadata Storage is prevented from caching in columnar form • NO CACHECOMPRESS: Oracle Exadata Storage will cache in HCC format (no recompression) • FOR QUERY: Oracle Exadata Storage will recompress and cache in INMEMORY query high format • FOR CAPACITY: Oracle Exadata Storage will recompress and cache in INMEMORY capacity low format

1 This column is intended for use with Oracle Exadata

See Also:

"USER_SEGMENTS"

6.401 DBA_SEGMENTS_OLD

DBA_SEGMENTS_OLD lists information about storage allocated for all database segments.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Username of the segment owner
SEGMENT_NAME	VARCHAR2(128)		Name, if any, of the segment
PARTITION_NAME	VARCHAR2(128)		Name of the partition
SEGMENT_TYPE	VARCHAR2(18)		Type of segment: INDEX PARTITION, TABLE PARTITION, TABLE, CLUSTER, INDEX, ROLLBACK, DEFERRED ROLLBACK, TEMPORARY, CACHE, LOBSEGMENT and LOBINDEX
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace containing the segment
HEADER_FILE	NUMBER		ID of the file containing the segment header
HEADER_BLOCK	NUMBER		ID of the block containing the segment header
BYTES	NUMBER		Size, in bytes, of the segment
BLOCKS	NUMBER		Size, in Oracle blocks, of the segment
EXTENTS	NUMBER		Number of extents allocated to the segment
INITIAL_EXTENT	NUMBER		Size in bytes requested for the initial extent of the segment at create time. (Oracle rounds the extent size to multiples of 5 blocks if the requested size is greater than 5 blocks.)
NEXT_EXTENT	NUMBER		Size in bytes of the next extent to be allocated to the segment
MIN_EXTENTS	NUMBER		Minimum number of extents allowed in the segment
MAX_EXTENTS	NUMBER		Maximum number of extents allowed in the segment
PCT_INCREASE	NUMBER		Percent by which to increase the size of the next extent to be allocated
FREELISTS	NUMBER		Number of process freelists allocated to the segment
FREELIST_GROUPS	NUMBER		Number of freelist groups allocated to this segment
RELATIVE_FNO	NUMBER		Relative file number of the segment header
BUFFER_POOL	VARCHAR2(7)		Buffer pool for the object

6.402 DBA_SENSITIVE_COLUMN_TYPES

DBA_SENSITIVE_COLUMN_TYPES describes sensitive column types in the database.

Column	Datatype	NULL	Description
NAME	VARCHAR2(128)		The name of the sensitive column type
USER_COMMENT	VARCHAR2(4000)		User comment on the sensitive column type

Column	Datatype	NULL	Description
SOURCE_NAME	VARCHAR2(128)		The name of the discovery source for the sensitive column type
SOURCE_TYPE	VARCHAR2(3)		The type of the discovery source: • ADM: import from ADM • DB: added within the database

> **See Also:**
>
> *Oracle Database Security Guide* for more information about transparent sensitive data protection

6.403 DBA_SENSITIVE_DATA

DBA_SENSITIVE_DATA describes the sensitive columns in the database.

Column	Datatype	NULL	Description
SENSITIVE#	NUMBER	NOT NULL	Dictionary ID for the sensitive data
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	The schema containing the sensitive data
TABLE_NAME	VARCHAR2(128)	NOT NULL	The table containing the sensitive data
COLUMN_NAME	VARCHAR2(128)	NOT NULL	The name of the column identified as sensitive
SENSITIVE_TYPE	VARCHAR2(128)		The sensitive column type of the data
SOURCE_NAME	VARCHAR2(128)		The name of the discovery source for the sensitive data
USER_COMMENT	VARCHAR2(4000)		User comment on the sensitive data
TS	TIMESTAMP(6)		The time when the data was identified as sensitive in the database

> **See Also:**
>
> *Oracle Database Security Guide* for more information about transparent sensitive data protection

6.404 DBA_SEQUENCES

DBA_SEQUENCES describes all sequences in the database. Its columns are the same as those in ALL_SEQUENCES.

> **See Also:**
>
> "ALL_SEQUENCES"

6.405 DBA_SERVER_REGISTRY

DBA_SERVER_REGISTRY displays information about all server components in the database that are loaded into the component registry.

Column	Datatype	NULL	Description
COMP_ID	VARCHAR2(30)	NOT NULL	Component identifier
COMP_NAME	VARCHAR2(255)		Component name
VERSION	VARCHAR2(30)		Component version loaded
VERSION_FULL	VARCHAR2(30)		Component full version
STATUS	VARCHAR2(11)		Component status: • INVALID • VALID • LOADING • LOADED • UPGRADING • UPGRADED • DOWNGRADING • DOWNGRADED • REMOVING • REMOVED
MODIFIED	VARCHAR2(20)		Time when the component was last modified
CONTROL	VARCHAR2(128)	NOT NULL	User that created the component entry
SCHEMA	VARCHAR2(128)	NOT NULL	User that contains the objects for the component
PROCEDURE	VARCHAR2(61)		Validation procedure
STARTUP	VARCHAR2(8)		Indicates whether the component requires a startup after the upgrade (REQUIRED) or not
PARENT_ID	VARCHAR2(30)		Parent component identifier
OTHER_SCHEMAS	VARCHAR2(4000)		A list of ancillary schema names associated with the component

6.406 DBA_SERVICES

DBA_SERVICES displays all services in the database. The view excludes rows marked for deletion. Its columns are the same as those in ALL_SERVICES.

> **See Also:**
>
> "ALL_SERVICES"

6.407 DBA_SOURCE

DBA_SOURCE describes the text source of all stored objects in the database. Its columns are the same as those in ALL_SOURCE.

> **See Also:**
>
> "ALL_SOURCE"

6.408 DBA_SOURCE_AE

DBA_SOURCE_AE describes the text source of all stored objects (across all editions) in the database. Its columns are the same as those in ALL_SOURCE_AE.

> **See Also:**
>
> "ALL_SOURCE_AE"

6.409 DBA_SQL_ERROR_MITIGATIONS

DBA_SQL_ERROR_MITIGATIONS describes automatic error mitigations for SQL statements.

Column	Datatype	NULL	Description
SQL_ID	VARCHAR2(13)		Identifier for the relevant SQL statement
SIGNATURE	NUMBER		Unique SQL identifier generated from normalized SQL text
FORCE_MATCHING	VARCHAR2(3)		Indicates whether the signature is force matching (YES) or exact matching (NO)
SQL_TEXT	CLOB		SQL text
INCIDENT_ID	NUMBER		ID for the incident associated with the error mitigation

Column	Datatype	NULL	Description
PROBLEM_KEY	VARCHAR2(64)		Description of the problem
PROBLEM_TYPE	VARCHAR2(17)		Problem type: • COMPILATION ERROR • EXECUTION ERROR
CREATED	TIMESTAMP(6) WITH TIME ZONE		Date and time at which the first automatic error mitigation was created on this SQL
START_TIME	TIMESTAMP(6) WITH TIME ZONE		Start date and time of automatic error mitigation
END_TIME	TIMESTAMP(6) WITH TIME ZONE		End date and time of automatic error mitigation
NOTES	CLOB		Mitigation notes
MITIGATION_TYPE	VARCHAR2(14)		Mitigation type: • ALTERNATE PLAN • SQL PATCH
MITIGATION_NAME	VARCHAR2(128)		Mitigation name
MITIGATION_DETAILS	CLOB		Mitigation details
STATUS	CHAR(7)		Mitigation status: • SUCCESS • FAILURE
LAST_VERIFIED	TIMESTAMP(6) WITH TIME ZONE		Date and time at which the auto patch was last verified

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

6.410 DBA_SQL_FIREWALL_ALLOW_LISTS

DBA_SQL_FIREWALL_ALLOW_LISTS displays information about SQL Firewall allow-lists.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the target user
GENERATED_ON	TIMESTAMP(6) WITH TIME ZONE	NOT NULL	Date and time of allow-list generation
STATUS	VARCHAR2(8)		Allow-list status (ENABLED or DISABLED)
STATUS_UPDATED_ON	TIMESTAMP(6) WITH TIME ZONE	NOT NULL	Date and time of the most recent allow-list status change
TOP_LEVEL_ONLY	VARCHAR2(14)		Indicates whether the allow-list should be enforced on only top-level SQL commands, that is, SQL commands issued directly from the user (Y) or on all SQL commands, including top-level SQL commands and SQL commands from PL/SQL units (N)

Column	Datatype	NULL	Description
ENFORCE	VARCHAR2(15)		Option of the allow-list enforcement: • ENFORCE_CONTEXT - Allowed contexts will be checked and enforced during database connection • ENFORCE_SQL - Allowed SQLs will be checked and enforced for every SQL statement execution • ENFORCE_ALL - Both allowed contexts and allowed SQLs will be checked and enforced
BLOCK	VARCHAR2(14)		If the allow-list is enabled, indicates whether the allow-list is enabled in blocking mode (Y) or non-blocking mode (N)

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

6.411 DBA_SQL_FIREWALL_ALLOWED_IP_ADDR

DBA_SQL_FIREWALL_ALLOWED_IP_ADDR lists the IP addresses that SQL Firewall target users are allowed to use to connect to the database.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the target user
IP_ADDRESS	VARCHAR2(128)	NOT NULL	Allowed client IP address

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

6.412 DBA_SQL_FIREWALL_ALLOWED_OS_PROG

DBA_SQL_FIREWALL_ALLOWED_OS_PROG lists the OS programs that SQL Firewall target users are allowed to use to connect to the database.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the target user
OS_PROGRAM	VARCHAR2(128)	NOT NULL	Allowed OS program name

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

6.413 DBA_SQL_FIREWALL_ALLOWED_OS_USER

DBA_SQL_FIREWALL_ALLOWED_OS_USER lists the OS user names that SQL Firewall target users are allowed to use to connect to the database.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the target user
OS_USER	VARCHAR2(128)	NOT NULL	Allowed OS user name

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

6.414 DBA_SQL_FIREWALL_ALLOWED_SQL

DBA_SQL_FIREWALL_ALLOWED_SQL displays information about allowed SQL for SQL Firewall allow-lists.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the target user
ALLOWED_SQL_ID	NUMBER	NOT NULL	Unique ID of allowed SQL entry for the target user
SQL_SIGNATURE	VARCHAR2(64)	NOT NULL	Allowed SQL signature
SQL_TEXT	VARCHAR2(4000)		SQL text (up to 1000 characters) To view the full SQL text, query the SQL_TEXT column of the DBA_SQL_FIREWALL_SQL_LOGS view.
ACCESSED_OBJECTS	VARCHAR2(4000)		List of accessed objects (up to 1000 characters) To view the full list of accessed objects, query the ACCESSED_OBJECTS column of the DBA_SQL_FIREWALL_SQL_LOGS view.
CURRENT_USER	VARCHAR2(128)		Name of the user who invoked the SQL command
TOP_LEVEL	VARCHAR2(9)		Indicates whether the allowed SQL entry is a top-level SQL command, that is, a SQL command issued directly from the user (Y) or a SQL command from a PL/SQL unit (N)

Column	Datatype	NULL	Description
VERSION	NUMBER	NOT NULL	Version number for the allow-list when the allowed SQL was added You can use this value to determine whether specific allowed SQLs were added to the allow-list in the same batch.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "DBA_SQL_FIREWALL_SQL_LOGS"

6.415 DBA_SQL_FIREWALL_CAPTURE_LOGS

DBA_SQL_FIREWALL_CAPTURE_LOGS displays SQL Firewall capture logs.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the target user
SESSION_ID	NUMBER	NOT NULL	SQL Firewall session ID
COMMAND_TYPE	VARCHAR2(64)		Type of SQL command
SQL_SIGNATURE	VARCHAR2(64)		SQL signature
SQL_TEXT	VARCHAR2(4000)		SQL text (up to 1000 characters) To view the full SQL text, query the SQL_TEXT column of the DBA_SQL_FIREWALL_SQL_LOGS view.
ACCESSED_OBJECTS	VARCHAR2(4000)		List of accessed objects (up to 1000 characters) To view the full list of accessed objects, query the ACCESSED_OBJECTS column of the DBA_SQL_FIREWALL_SQL_LOGS view.
CURRENT_USER	VARCHAR2(128)		Name of the user who invoked the SQL command
TOP_LEVEL	VARCHAR2(9)		Indicates whether the SQL command is a top-level SQL command, that is, a SQL command issued directly from the user (Y) or a SQL command from a PL/SQL unit (N)
CLIENT_PROGRAM	VARCHAR2(84)		Name of the client program
OS_USER	VARCHAR2(128)		Name of the OS user of the client process
IP_ADDRESS	VARCHAR2(48)		Client IP address

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "DBA_SQL_FIREWALL_SQL_LOGS"

6.416 DBA_SQL_FIREWALL_CAPTURES

`DBA_SQL_FIREWALL_CAPTURES` displays information about SQL Firewall captures.

Column	Datatype	NULL	Description
`USERNAME`	`VARCHAR2(128)`		Name of the target user
`TOP_LEVEL_ONLY`	`VARCHAR2(14)`		Indicates whether SQL Firewall should capture only top-level SQL commands, that is, SQL commands issued directly from the user (`Y`) or all SQL commands, including top-level SQL commands and SQL commands from PL/SQL units (`N`)
`STATUS`	`VARCHAR2(8)`		Capture status (`ENABLED` or `DISABLED`)
`LAST_STARTED_ON`	`TIMESTAMP(6) WITH TIME ZONE`		Date and time at which the capture was last started
`LAST_STOPPED_ON`	`TIMESTAMP(6) WITH TIME ZONE`		Date and time at which the capture was last stopped

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

6.417 DBA_SQL_FIREWALL_SESSION_LOGS

`DBA_SQL_FIREWALL_SESSION_LOGS` displays SQL Firewall session logs.

Column	Datatype	NULL	Description
`SESSION_ID`	`NUMBER`	`NOT NULL`	SQL Firewall session ID
`USERNAME`	`VARCHAR2(128)`		Name of the target user
`LOGIN_TIME`	`TIMESTAMP(6) WITH TIME ZONE`		Date and time at which the target user logged in to the database
`IP_ADDRESS`	`VARCHAR2(48)`		Client IP address

Column	Datatype	NULL	Description
CLIENT_PROGRAM	VARCHAR2(84)		Name of the client program
OS_USER	VARCHAR2(128)		Name of the OS user of the client process

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

6.418 DBA_SQL_FIREWALL_SQL_LOGS

DBA_SQL_FIREWALL_SQL_LOGS displays information about SQL logs for SQL Firewall.

Column	Datatype	NULL	Description
COMMAND_TYPE	VARCHAR2(64)		Type of SQL command
SQL_SIGNATURE	VARCHAR2(64)		SQL signature
SQL_TEXT	CLOB		SQL text
ACCESSED_OBJECTS	CLOB		List of accessed objects
CHARSET	VARCHAR2(64)		Character set of the SQL text

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

6.419 DBA_SQL_FIREWALL_STATUS

DBA_SQL_FIREWALL_STATUS displays the status of SQL Firewall.

Column	Datatype	NULL	Description
STATUS	VARCHAR2(8)		SQL Firewall status (ENABLED or DISABLED)
STATUS_UPDATED_ON	TIMESTAMP(6) WITH TIME ZONE	NOT NULL	Date and time of the most recent SQL Firewall status change
EXCLUDE_JOBS	VARCHAR2(12)		Indicates whether the SQL Firewall will capture or enforce allow-lists for database connections and SQL executions of Oracle scheduler job sessions (Y) or not (N)

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

6.420 DBA_SQL_FIREWALL_VIOLATIONS

DBA_SQL_FIREWALL_VIOLATIONS lists SQL Firewall violations.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the target user
COMMAND_TYPE	VARCHAR2(64)		Type of SQL command
SQL_SIGNATURE	VARCHAR2(64)		SQL signature
SQL_TEXT	VARCHAR2(4000)		SQL text (up to 1000 characters) To view the full SQL text, query the SQL_TEXT column of the DBA_SQL_FIREWALL_SQL_LOGS view.
ACCESSED_OBJECTS	VARCHAR2(4000)		List of accessed objects (up to 1000 characters) To view the full list of accessed objects, query the ACCESSED_OBJECTS column of the DBA_SQL_FIREWALL_SQL_LOGS view.
CURRENT_USER	VARCHAR2(128)		Name of the user who invoked the SQL command
TOP_LEVEL	VARCHAR2(9)		Indicates whether the SQL command is a top-level SQL command, that is, a SQL command issued directly from the user (Y) or a SQL command from a PL/SQL unit (N)
IP_ADDRESS	VARCHAR2(48)		Client IP address
CLIENT_PROGRAM	VARCHAR2(84)		Name of the client program
OS_USER	VARCHAR2(128)		Name of the OS user of the client process
CAUSE	VARCHAR2(17)		Cause of the violation: • Context violation • SQL violation
FIREWALL_ACTION	VARCHAR2(7)		Indicates whether the SQL Firewall action was Allowed or Blocked
OCCURRED_AT	TIMESTAMP(6) WITH TIME ZONE		Date and time of the violation

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "DBA_SQL_FIREWALL_SQL_LOGS"

6.421 DBA_SQL_MANAGEMENT_CONFIG

DBA_SQL_MANAGEMENT_CONFIG displays the configuration parameters of the SQL management base.

You must have the DBA role in order to change the configuration parameter values.

Column	Datatype	NULL	Description
PARAMETER_NAME	VARCHAR2(128)	NOT NULL	Name of the configuration parameter: • SPACE_BUDGET_PERCENT • PLAN_RETENTION_WEEKS • AUTO_CAPTURE_SQL_TEXT • AUTO_CAPTURE_PARSING_SCHEMA_NAME • AUTO_CAPTURE_MODULE • AUTO_CAPTURE_ACTION
PARAMETER_VALUE	VARCHAR2(4000)	NOT NULL	Value of the configuration parameter
LAST_MODIFIED	TIMESTAMP(6)		Time the parameter value was last updated
MODIFIED_BY	VARCHAR2(128)		User who last updated the parameter value

6.422 DBA_SQL_QUARANTINE

DBA_SQL_QUARANTINE displays information about SQL Quarantine configurations.

Each row in this view represents a quarantine configuration for a SQL plan.

Column	Datatype	NULL	Description
SIGNATURE	NUMBER	NOT NULL	Unique SQL identifier generated from normalized SQL text
NAME	VARCHAR2(128)	NOT NULL	Unique plan identifier in string form as a search key
SQL_TEXT	CLOB	NOT NULL	Un-normalized SQL text
PLAN_HASH_VALUE	NUMBER		Unique plan identifier in numeric form as a search key
CPU_TIME	VARCHAR2(4000)		CPU time threshold (in seconds)
IO_MEGABYTES	VARCHAR2(4000)		I/O threshold (in megabytes)
IO_REQUESTS	VARCHAR2(4000)		Physical I/O threshold (number of physical I/O requests)
ELAPSED_TIME	VARCHAR2(4000)		Elapsed time threshold (in seconds)
IO_LOGICAL	VARCHAR2(4000)		Logical I/O threshold (number of logical I/O requests)
CREATOR	VARCHAR2(128)		User who created the quarantine configuration

Column	Datatype	NULL	Description
ORIGIN	VARCHAR2(16)		Method by which the quarantine configuration was created. The only possible value is RESOURCE-MANAGER, which indicates that the quarantine configuration was created by the Resource Manager.
DESCRIPTION	VARCHAR2(500)		Text description
CREATED	TIMESTAMP(6)	NOT NULL	Time at which the quarantine configuration was created
LAST_EXECUTED	TIMESTAMP(6)		Time at which the quarantine configuration was last used
ENABLED	VARCHAR2(3)		Indicates whether the quarantine configuration is enabled (YES) or disabled (NO)
AUTOPURGE	VARCHAR2(3)		Indicates whether the quarantine configuration is auto-purged (YES) or not (NO)

See Also:

Oracle Database SQL Tuning Guide for more information about quarantined SQL plans

6.423 DBA_SQL_PATCHES

DBA_SQL_PATCHES displays the set of SQL patches.

Column	Datatype	NULL	Description
NAME	VARCHAR2(128)	NOT NULL	Name of the SQL patch
CATEGORY	VARCHAR2(128)	NOT NULL	Category of the SQL patch
SIGNATURE	NUMBER	NOT NULL	Unique identifier generated from normalized SQL text
SQL_TEXT	CLOB	NOT NULL	Un-normalized SQL text
CREATED	TIMESTAMP(6)	NOT NULL	Timestamp when the SQL patch was created
LAST_MODIFIED	TIMESTAMP(6)		Timestamp when the SQL patch was last modified
DESCRIPTION	VARCHAR2(500)		Text description provided for the SQL patch
ORIGIN	VARCHAR2(22)		Origin of the patch: • AUTO-FOREGROUND-REPAIR • PATCH • UNKNOWN
STATUS	VARCHAR2(8)		Status of the SQL patch: • ENABLED • DISABLED
FORCE_MATCHING	VARCHAR2(3)		Indicates whether the signature is force matching (YES) or exact matching (NO)

Column	Datatype	NULL	Description
TASK_ID	NUMBER		Advisor task ID that generated the SQL patch
TASK_EXEC_NAME	VARCHAR2(128)		Advisor execution name for the SQL patch
TASK_OBJ_ID	NUMBER		Advisor object ID for the SQL patch
TASK_FND_ID	NUMBER		Advisor finding ID for the SQL patch
TASK_REC_ID	NUMBER		Advisor recommendation ID for the SQL patch

6.424 DBA_SQL_PLAN_BASELINES

DBA_SQL_PLAN_BASELINES displays information about the SQL plan baselines currently created for specific SQL statements.

Column	Datatype	NULL	Description
SIGNATURE	NUMBER	NOT NULL	Unique SQL identifier generated from normalized SQL text
SQL_HANDLE	VARCHAR2(30)	NOT NULL	Unique SQL identifier in string form as a search key
SQL_TEXT	CLOB	NOT NULL	Un-normalized SQL text
PLAN_NAME	VARCHAR2(128)	NOT NULL	Unique plan identifier in string form as a search key
CREATOR	VARCHAR2(128)		User who created the plan baseline
ORIGIN	VARCHAR2(29)		How the plan baseline was created: • ADDM-SQLTUNE • AUTO-CAPTURE • AUTO-SQLTUNE • EVOLVE-AUTO-INDEX-LOAD • EVOLVE-CREATE-FROM-ADAPTIVE • EVOLVE-LOAD-FROM-AWR • EVOLVE-LOAD-FROM-CURSOR-CACHE • EVOLVE-LOAD-FROM-STS • FOREGROUND-CAPTURE • MANUAL-LOAD • MANUAL-LOAD-FROM-AWR • MANUAL-LOAD-FROM-CURSOR-CACHE • MANUAL-LOAD-FROM-STS • MANUAL-SQLTUNE • STORED-OUTLINE
PARSING_SCHEMA_NAME	VARCHAR2(128)		Name of the parsing schema
DESCRIPTION	VARCHAR2(500)		Text description provided for the plan baseline
VERSION	VARCHAR2(64)		Database version at the time of plan baseline creation
CREATED	TIMESTAMP(6)	NOT NULL	Timestamp when the plan baseline was created
LAST_MODIFIED	TIMESTAMP(6)		Timestamp when the plan baseline was last modified

Column	Datatype	NULL	Description
LAST_EXECUTED	TIMESTAMP(6)		Timestamp when the plan baseline was last executed **Note:** For performance reasons, this column is not updated immediately after each execution of the plan baseline. Therefore, the plan baseline may have been executed more recently than the value of this column indicates.
LAST_VERIFIED	TIMESTAMP(6)		Timestamp when the plan baseline was last verified
ENABLED	VARCHAR2(3)		Indicates whether the plan baseline is enabled (YES) or disabled (NO)
ACCEPTED	VARCHAR2(3)		Indicates whether the plan baseline is accepted (YES) or not (NO)
FIXED	VARCHAR2(3)		Indicates whether the plan baseline is fixed (YES) or not (NO)
REPRODUCED	VARCHAR2(3)		Indicates whether the optimizer was able to reproduce the plan (YES) or not (NO). The value of this column is set to YES when a plan is initially added to the plan baseline.
AUTOPURGE	VARCHAR2(3)		Indicates whether the plan baseline is auto-purged (YES) or not (NO)
ADAPTIVE	VARCHAR2(3)		Indicates whether a plan that is automatically captured by SQL plan management is marked adaptive or not. When a new adaptive plan is found for a SQL statement that has an existing SQL plan baseline, that new plan will be added to the SQL plan baseline as an unaccepted plan, and the ADAPTIVE column will be marked YES. When this new plan is verified (either manually or via the auto evolve task), the plan will be test executed and the final plan determined at execution will become an accepted plan if its performance is better than the existing plan baseline. At this point, the value of the ADAPTIVE column is set to NO since the plan is no longer adaptive, but resolved.
OPTIMIZER_COST	NUMBER		Optimizer cost at the time the plan baseline was created
MODULE	VARCHAR2(64)		Application module name
ACTION	VARCHAR2(64)		Application action
EXECUTIONS[1]	NUMBER		Number of executions at the time the plan baseline was created
ELAPSED_TIME[1]	NUMBER		Total elapsed time (in microseconds) at the time the plan baseline was created
CPU_TIME[1]	NUMBER		Total CPU time (in microseconds) at the time the plan baseline was created
BUFFER_GETS[1]	NUMBER		Total buffer gets at the time the plan baseline was created

Column	Datatype	NULL	Description
DISK_READS[1]	NUMBER		Total disk reads at the time the plan baseline was created
DIRECT_WRITES[1]	NUMBER		Total direct writes at the time the plan baseline was created
ROWS_PROCESSED[1]	NUMBER		Total rows processed at the time the plan baseline was created
FETCHES[1]	NUMBER		Total number of fetches at the time the plan baseline was created
END_OF_FETCH_COUNT[1]	NUMBER		Total number of full fetches at the time the plan baseline was created
FOREGROUND_LAST_VERIFIED	TIMESTAMP(6)		Timestamp when the SQL plan baseline was verified by real-time SQL plan management
NOTES	CLOB		Internal SQL plan baseline verification information

1 If the value of the ORIGIN column is equal to AUTO-CAPTURE, then data for this column is not populated.

See Also:

- *Oracle Database SQL Tuning Guide* for more information about SQL plan baselines
- The DBMS_SQLTUNE package in *Oracle Database PL/SQL Packages and Types Reference*

6.425 DBA_SQL_PLAN_DIR_OBJECTS

DBA_SQL_PLAN_DIR_OBJECTS displays the objects created in the SQL plan directive.

Column	Datatype	NULL	Description
DIRECTIVE_ID	NUMBER		The identifier of the SQL plan directive
OWNER	VARCHAR2(128)		The username of the owner of the object in the SQL plan directive
OBJECT_NAME	VARCHAR2(128)		The name of the object in the SQL plan directive
SUBOBJECT_NAME	VARCHAR2(128)		The name of the subobject (for example, column) in the SQL plan directive
OBJECT_TYPE	VARCHAR2(6)		The type of the subobject in the SQL plan directive
NUM_ROWS	NUMBER		The number of rows in the object when the directive is created
NOTES	XMLTYPE		Other notes about the object

See Also:

- "DBA_SQL_PLAN_DIRECTIVES"
- *Oracle Database SQL Tuning Guide* for more information about SQL plan directives

6.426 DBA_SQL_PLAN_DIRECTIVES

DBA_SQL_PLAN_DIRECTIVES displays information about the SQL plan directives in the system.

Column	Datatype	NULL	Description
DIRECTIVE_ID	NUMBER	NOT NULL	The identifier of the SQL plan directive
TYPE	VARCHAR2(16)		The type of the SQL plan directive: • DYNAMIC SAMPLING: SQL plan directive • DYNAMIC SAMPLING RESULT: Dynamic sampling query results. This value appears only in Oracle Database 12*c* Release 2 (12.2.0.1) and later releases. • UNKNOWN: Unknown
ENABLED	VARCHAR2(3)		Indicates whether the SQL plan directive is enabled. Possible values: • YES: The SQL plan directive is enabled. • NO: The SQL plan directive is not enabled.
STATE	VARCHAR2(10)		The state of the SQL plan directive. Possible values include: • SUPERSEDED: This value indicates that the corresponding column or groups have an extension or histogram, or that another SQL plan directive exists that can be used for the directive. • USABLE: This value indicates that the SQL plan directive is usable for the optimizer.
AUTO_DROP	VARCHAR2(3)		If YES, the SQL plan directive gets dropped when unused beyond SPD_RETENTION_WEEKS
REASON	VARCHAR2(36)		The reason for creating the SQL plan directive
CREATED	TIMESTAMP(6)		The creation timestamp of the SQL plan directive
LAST_MODIFIED	TIMESTAMP(6)		The timestamp of most recent modification of the SQL plan directive
LAST_USED	TIMESTAMP(9)		The timestamp of most recent usage of the SQL plan directive
NOTES	XMLTYPE		Extra information about the SQL plan directive

See Also:

- "DBA_SQL_PLAN_DIR_OBJECTS"
- *Oracle Database SQL Tuning Guide* for more information about SQL plan directives

6.427 DBA_SQL_PROFILES

DBA_SQL_PROFILES displays information about SQL profiles currently created for specific SQL statements.

Column	Datatype	NULL	Description
NAME	VARCHAR2(128)	NOT NULL	Name of the SQL profile
CATEGORY	VARCHAR2(128)	NOT NULL	Category of the SQL profile
SIGNATURE	NUMBER	NOT NULL	Unique identifier generated from normalized SQL text
SQL_TEXT	CLOB	NOT NULL	Un-normalized SQL text
CREATED	TIMESTAMP(6)	NOT NULL	Timestamp when the SQL profile was created
LAST_MODIFIED	TIMESTAMP(6)		Timestamp when the SQL profile was last modified
DESCRIPTION	VARCHAR2(500)		Text description provided for the SQL profile
TYPE	VARCHAR2(7)		Type of the SQL profile (how it was created): • MANUAL • AUTO
STATUS	VARCHAR2(8)		Status of the SQL profile: • ENABLED • DISABLED • VOID
FORCE_MATCHING	VARCHAR2(3)		If YES, this causes SQL Profiles to target all SQL statements which have the same text after normalizing all literal values to bind variables. If a combination of literal values and bind variables is used in the same SQL text, then no transformation occurs. This is analogous to the matching algorithm use by the FORCE option of the CURSOR_SHARING parameter. If NO, literals are not transformed. This is analogous to the matching algorithm used by the EXACT option of the CURSOR_SHARING parameter.
TASK_ID	NUMBER		Advisor task ID that generated the SQL profile
TASK_EXEC_NAME	VARCHAR2(128)		Advisor execution name for the SQL profile
TASK_OBJ_ID	NUMBER		Advisor object ID for the SQL profile
TASK_FND_ID	NUMBER		Advisor finding ID for the SQL profile
TASK_REC_ID	NUMBER		Advisor recommendation ID for the SQL profile
TASK_CON_DBID	NUMBER		Database ID for the PDB tuning task generating the SQL profile

> **See Also:**
>
> The `DBMS_SQLTUNE` package in *Oracle Database PL/SQL Packages and Types Reference*

6.428 DBA_SQL_TRANSLATION_PROFILES

`DBA_SQL_TRANSLATION_PROFILES` describes all SQL translation profiles in the database. Its columns are the same as those in `ALL_SQL_TRANSLATION_PROFILES`.

> **See Also:**
>
> "ALL_SQL_TRANSLATION_PROFILES"

6.429 DBA_SQL_TRANSLATIONS

`DBA_SQL_TRANSLATIONS` describes all SQL translations in the database. Its columns are the same as those in `ALL_SQL_TRANSLATIONS`.

> **See Also:**
>
> "ALL_SQL_TRANSLATIONS"

6.430 DBA_SQLJ_TYPE_ATTRS

`DBA_SQLJ_TYPE_ATTRS` describes the attributes of all SQLJ object types in the database. Its columns are the same as those in `ALL_SQLJ_TYPE_ATTRS`.

> **See Also:**
>
> "ALL_SQLJ_TYPE_ATTRS"

6.431 DBA_SQLJ_TYPE_METHODS

DBA_SQLJ_TYPE_METHODS describes the methods of all SQLJ object types in the database. Its columns are the same as those in ALL_SQLJ_TYPE_METHODS.

> **See Also:**
>
> "ALL_SQLJ_TYPE_METHODS"

6.432 DBA_SQLJ_TYPES

DBA_SQLJ_TYPES describes all SQLJ object types in the database. Its columns are the same as those in ALL_SQLJ_TYPES.

> **See Also:**
>
> "ALL_SQLJ_TYPES"

6.433 DBA_SQLSET

DBA_SQLSET displays information about all SQL tuning sets in the database. Its columns are the same as those in ALL_SQLSET.

> **See Also:**
>
> "ALL_SQLSET"

6.434 DBA_SQLSET_BINDS

DBA_SQLSET_BINDS displays the bind values associated with all SQL tuning sets in the database. Its columns are the same as those in ALL_SQLSET_BINDS.

> **See Also:**
>
> "ALL_SQLSET_BINDS"

6.435 DBA_SQLSET_PLANS

DBA_SQLSET_PLANS describes captured plans in the SQL tuning sets in the database. Its columns are the same as those in ALL_SQLSET_PLANS.

> **See Also:**
>
> "ALL_SQLSET_PLANS"

6.436 DBA_SQLSET_REFERENCES

DBA_SQLSET_REFERENCES describes whether or not all SQL tuning sets in the database are active. A SQL tuning set cannot be dropped if it is referenced. Its columns are the same as those in ALL_SQLSET_REFERENCES.

> **See Also:**
>
> "ALL_SQLSET_REFERENCES"

6.437 DBA_SQLSET_STATEMENTS

DBA_SQLSET_STATEMENTS displays information about the SQL statements, along with their statistics, that form all SQL tuning sets in the database. Its columns, except for PARSING_SCHEMA_ID, are the same as those in ALL_SQLSET_STATEMENTS.

Column	Datatype	NULL	Description
SQLSET_NAME	VARCHAR2(128)	NOT NULL	Name of the SQL tuning set for the statement
SQLSET_OWNER	VARCHAR2(128)		User name of the SQL tuning set owner
SQLSET_ID	NUMBER	NOT NULL	ID of the SQL tuning set for the statement
CON_DBID	NUMBER	NOT NULL	The database ID of the PDB
SQL_ID	VARCHAR2(13)	NOT NULL	SQL identifier of the parent cursor in the library cache
FORCE_MATCHING_SIGNATURE	NUMBER	NOT NULL	The signature used when the CURSOR_SHARING parameter is set to FORCE
SQL_TEXT	CLOB		Full text for the SQL statement exposed as a CLOB column.
PARSING_SCHEMA_NAME	VARCHAR2(128)		Name of the user in whose schema the statement was parsed
PARSING_SCHEMA_ID	NUMBER		ID of the schema in which the statement was parsed
PLAN_HASH_VALUE	NUMBER	NOT NULL	Hash value for the plan corresponding to statistics in this record

Column	Datatype	NULL	Description
BIND_DATA	RAW(2000)		Bind data
BINDS_CAPTURED	CHAR(1)		Binds captured
MODULE	VARCHAR2(64)		Contains the name of the module that was executing at the time that the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_MODULE
ACTION	VARCHAR2(64)		Contains the name of the action that was executing at the time that the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_ACTION
ELAPSED_TIME	NUMBER		Elapsed time (in microseconds) used by this cursor for parsing, executing, and fetching
CPU_TIME	NUMBER		CPU time (in microseconds) used by this cursor for parsing, executing, and fetching
BUFFER_GETS	NUMBER		Number of buffer gets for this child cursor
DISK_READS	NUMBER		Number of disk reads for this child cursor
DIRECT_WRITES	NUMBER		Number of direct writes for this child cursor
ROWS_PROCESSED	NUMBER		Total number of rows that the parsed SQL statement returns
FETCHES	NUMBER		Number of fetches associated with the SQL statement
EXECUTIONS	NUMBER		Number of executions that took place on this object since it was brought into the library cache
END_OF_FETCH_COUNT	NUMBER		Number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic in not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed. By definition, the value of the END_OF_FETCH_COUNT column should be less than, or equal to, the value of the EXECUTIONS column.
OPTIMIZER_COST	NUMBER		Cost of this query, given by the optimizer
OPTIMIZER_ENV	RAW(2000)		Optimizer environment
PRIORITY	NUMBER		User-defined priority
COMMAND_TYPE	NUMBER		Oracle command type definition
FIRST_LOAD_TIME	VARCHAR2(19)		Timestamp of the parent creation time
STAT_PERIOD	NUMBER		Period of time (in seconds) during which the statistics of the SQL statement were collected
ACTIVE_STAT_PERIOD	NUMBER		Effective period of time (in seconds) during which the SQL statement was active
OTHER	CLOB		Client data, specified by the user, for this statement
PLAN_TIMESTAMP	DATE		Timestamp for the plan corresponding to the statistics in this record
SQL_SEQ	NUMBER	NOT NULL	SQL sequence

Column	Datatype	NULL	Description
LAST_EXEC_START_TIME	VARCHAR2(19)		For SQLs captured from the cursor cache, this is the time when the most recent execution of this SQL started

See Also:

- "ALL_SQLSET_STATEMENTS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLICATION_INFO.SET_MODULE procedure
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLICATION_INFO.SET_ACTION procedure

6.438 DBA_SQLTUNE_BINDS

DBA_SQLTUNE_BINDS displays the bind values associated with all tuned SQL statements in the database.

Related View

USER_SQLTUNE_BINDS displays the bind values associated with the tuned SQL statements owned by the current user.

Column	Datatype	NULL	Description
TASK_ID	NUMBER(38)	NOT NULL	Tuning task identifier
OBJECT_ID	NUMBER(38)	NOT NULL	Advisor framework object identifier
POSITION	NUMBER(38)	NOT NULL	Bind position
VALUE	ANYDATA		Bind value. This column is NULL for PL/SQL bind types.

See Also:

"USER_SQLTUNE_BINDS"

6.439 DBA_SQLTUNE_PLANS

DBA_SQLTUNE_PLANS displays information about the execution plans generated for all SQL statements in the database during a SQL tuning session.

Related View

USER_SQLTUNE_PLANS displays information about the execution plans generated for the SQL statements owned by the current user during a SQL tuning session.

Column	Datatype	NULL	Description
TASK_ID	NUMBER(38)	NOT NULL	Advisor task ID
EXECUTION_NAME	VARCHAR2(128)	NOT NULL	Advisor task execution
OBJECT_ID	NUMBER(38)	NOT NULL	Advisor object ID
ATTRIBUTE	VARCHAR2(34)		Text string identifying the type of the execution plan: • `Original` - Original plan of the query • `Original with adjusted cost` - Same as `Original` but with adjusted cost • `Using SQL profile` - Plan with SQL profile applied • `Using new indices` - Plan with indexes applied
STATEMENT_ID	VARCHAR2(30)		Optional statement identifier specified in the `EXPLAIN PLAN` statement
PLAN_HASH_VALUE	NUMBER	NOT NULL	Numerical representation of the execution plan
PLAN_ID	NUMBER		Plan identifier
TIMESTAMP	DATE		Date and time when the `EXPLAIN PLAN` statement was issued
REMARKS	VARCHAR2(4000)		Place for comments that can be added to the steps of the execution plan
OPERATION	VARCHAR2(30)		Name of the operation performed at this step
OPTIONS	VARCHAR2(255)		Options used for the operation performed at this step
OBJECT_NODE	VARCHAR2(128)		Name of the database link used to reference the object
OBJECT_OWNER	VARCHAR2(128)		Owner of the object
OBJECT_NAME	VARCHAR2(128)		Name of the object
OBJECT_ALIAS	VARCHAR2(261)		Object alias
OBJECT_INSTANCE	NUMBER(38)		Numbered position of the object name in the original SQL statement
OBJECT_TYPE	VARCHAR2(30)		Descriptive modifier that further describes the type of object
OPTIMIZER	VARCHAR2(255)		Current mode of the optimizer
SEARCH_COLUMNS	NUMBER		Number of index columns with start and stop keys (that is, the number of columns with matching predicates)
ID	NUMBER(38)	NOT NULL	Identification number for this step in the execution plan
PARENT_ID	NUMBER(38)		ID of the next step that operates on the results of this step
DEPTH	NUMBER(38)		Depth
POSITION	NUMBER(38)		Order of processing for steps with the same parent ID
COST	NUMBER(38)		Cost of the current operation estimated by the cost-based optimizer (CBO)

Column	Datatype	NULL	Description
CARDINALITY	NUMBER(38)		Number of rows returned by the current operation (estimated by the CBO)
BYTES	NUMBER(38)		Number of bytes returned by the current operation
OTHER_TAG	VARCHAR2(255)		Describes the function of the SQL text in the OTHER column. Values for OTHER_TAG are: • SERIAL - SQL is the text of a locally-executed, serial query plan. Currently, SQL is not loaded in OTHER for this case. • SERIAL_FROM_REMOTE - SQL text shown in the OTHER column will be executed at a remote site • PARALLEL_COMBINED_WITH_PARENT - Parent of this operation is a DFO that performs both operations in the parallel execution plan • PARALLEL_COMBINED_WITH_CHILD - Child of this operation is a DFO that performs both operations in the parallel execution plan. • PARALLEL_TO_SERIAL - SQL text shown in the OTHER column is the top-level of the parallel plan. • PARALLEL_TO_PARALLEL - SQL text shown in the OTHER column is executed and output in parallel • PARALLEL_FROM_SERIAL - Operation consumes data from a serial operation and outputs it in parallel
PARTITION_START	VARCHAR2(255)		Start partition of a range of accessed partitions
PARTITION_STOP	VARCHAR2(255)		Stop partition of a range of accessed partitions
PARTITION_ID	NUMBER(38)		Step that has computed the pair of values of the PARTITION_START and PARTITION_STOP columns
OTHER	LONG		Information about parallel execution servers and parallel queries
DISTRIBUTION	VARCHAR2(30)		Distribution method
CPU_COST	NUMBER(38)		User-defined CPU cost
IO_COST	NUMBER(38)		User-defined I/O cost
TEMP_SPACE	NUMBER(38)		Temporary space usage of the operation (sort or hash-join) as estimated by the CBO
ACCESS_PREDICATES	VARCHAR2(4000)		Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.
FILTER_PREDICATES	VARCHAR2(4000)		Predicates used to filter rows before producing them
PROJECTION	VARCHAR2(4000)		Expressions produced by the operation
TIME	NUMBER(38)		Elapsed time (in seconds) of the operation as estimated by the CBO
QBLOCK_NAME	VARCHAR2(128)		Name of the query block

Column	Datatype	NULL	Description
OTHER_XML	CLOB		Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML because it allows multiple pieces of information to be stored, including the following: • Name of the schema against which the query was parsed • Release number of the Oracle Database that produced the explain plan • Hash value associated with the execution plan • Name (if any) of the outline or the SQL profile used to build the execution plan • Indication of whether or not dynamic statistics were used to produce the plan • The outline data, a set of optimizer hints that can be used to regenerate the same plan

See Also:

"USER_SQLTUNE_PLANS"

6.440 DBA_SQLTUNE_RATIONALE_PLAN

DBA_SQLTUNE_RATIONALE_PLAN displays the association between rationales and operations in the execution plan of all SQL statements in the database.

Related View

USER_SQLTUNE_RATIONALE_PLAN displays the association between rationales and operations in the execution plan of the SQL statements owned by the current user.

Column	Datatype	NULL	Description
TASK_ID	NUMBER(38)	NOT NULL	Tuning task identifier
EXECUTION_NAME	VARCHAR2(128)	NOT NULL	The name of the task execution with which this entry (row) is associated
RATIONALE_ID	NUMBER(38)	NOT NULL	Rationale identifier
OBJECT_ID	NUMBER(38)	NOT NULL	Advisor framework object identifier
OPERATION_ID	NUMBER(38)	NOT NULL	Operation identifier
PLAN_ATTRIBUTE	VARCHAR2(34)		Type of the execution plan: • Original - Original plan of the query • Original with adjusted cost - Same as Original but with adjusted cost • Using SQL profile - Plan with SQL profile applied • Using new indices - Plan with indexes applied

> **See Also:**
>
> "USER_SQLTUNE_RATIONALE_PLAN"

6.441 DBA_SQLTUNE_STATISTICS

`DBA_SQLTUNE_STATISTICS` displays statistics associated with all SQL statements in the database.

Related View

`USER_SQLTUNE_STATISTICS` displays statistics associated with the SQL statements owned by the current user.

Column	Datatype	NULL	Description
TASK_ID	NUMBER(38)	NOT NULL	Tuning task identifier
OBJECT_ID	NUMBER(38)	NOT NULL	Advisor framework object identifier
PARSING_SCHEMA_ID	NUMBER		Schema under which the SQL is parsed
MODULE	VARCHAR2(64)		Last application module recorded for the SQL
ACTION	VARCHAR2(64)		Last application action recorded for the SQL
ELAPSED_TIME	NUMBER		Elapsed time for the SQL statement
CPU_TIME	NUMBER		CPU time for the SQL
BUFFER_GETS	NUMBER		Number of buffer gets
DISK_READS	NUMBER		Number of disk reads
DIRECT_WRITES	NUMBER		Number of disk writes
ROWS_PROCESSED	NUMBER		Number of rows processed by the SQL
FETCHES	NUMBER		Number of fetches
EXECUTIONS	NUMBER		Number of executions
END_OF_FETCH_COUNT	NUMBER		End of fetch count
OPTIMIZER_COST	NUMBER		Optimizer cost for the SQL
OPTIMIZER_ENV	RAW(2000)		Optimizer environment
COMMAND_TYPE	NUMBER		Command type

> **See Also:**
>
> "USER_SQLTUNE_STATISTICS"

6.442 DBA_SR_GRP_STATUS

DBA_SR_GRP_STATUS provides information on the current refresh operations for the current synchronous refresh groups in the database. It has the same columns as the DBA_SR_GRP_STATUS_ALL view.

Refresh operations are controlled using the DBMS_SYNC_REFRESH package.

Related View

USER_SR_GRP_STATUS provides information on the current refresh operations for the current synchronous refresh groups in the database which are owned by the current user. Its columns are the same as those in DBA_SR_GRP_STATUS.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the refresh operation, which is the user who launched the operation
GROUP_ID	NUMBER	NOT NULL	Group ID of the synchronous refresh group
OPERATION	VARCHAR2(7)		The phase of the refresh operation performed: • PREPARE • EXECUTE
STATUS	VARCHAR2(10)		The status of the refresh operation: • RUNNING • NOT PROCESSED • COMPLETE • ERROR-SOFT • ERROR-HARD • ABORT • PARTIAL
NUM_TBLS	NUMBER	NOT NULL	The number of tables in the synchronous refresh group
NUM_MVS	NUMBER	NOT NULL	The number of materialized views in the synchronous refresh group
BASE_TBLS_REFR_STATUS	VARCHAR2(13)		Indicates the refresh status of base tables in the synchronous refresh group. The possible values are: • NOT PROCESSED • COMPLETE • ABORT
NUM_MVS_COMPLETED	NUMBER		The number of materialized views which have completed refresh in the synchronous refresh group
NUM_MVS_ABORTED	NUMBER		The number of materialized views which have terminated refresh in the synchronous refresh group
ERROR_NUMBER	NUMBER		Error number of the run (if any)
ERROR_MESSAGE	VARCHAR2(4000)		Error message of the run (if any)
PREPARE_START_TIME	DATE		Time that the PREPARE_REFRESH phase of the run started

Column	Datatype	NULL	Description
PREPARE_END_TIME	DATE		Time that the PREPARE_REFRESH phase of the run ended
EXECUTE_START_TIME	DATE		Time that the EXECUTE_REFRESH phase of the run started
EXECUTE_END_TIME	DATE		Time that the EXECUTE_REFRESH phase of the run ended

See Also:

- "USER_SR_GRP_STATUS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SYNC_REFRESH package

6.443 DBA_SR_GRP_STATUS_ALL

DBA_SR_GRP_STATUS_ALL provides information on the refresh operations on the synchronous refresh groups in the database.

A refresh operation is also called a run, and it has two phases: PREPARE_REFRESH and EXECUTE_REFRESH. These phases are controlled using the DBMS_SYNC_REFRESH package.

Each row in this view provides information on a run of a group, identified by its GROUP_ID. The view contains information on the status of the objects of both current and past runs of both current and defunct synchronous refresh groups. Therefore, this view can be used to examine the history of synchronous refresh operations.

The current run of a group is the most recent run of a group; a current group is a currently valid group, which is capable of being refreshed. A group becomes defunct when it is unregistered for any reason, either explicitly by the user or implicitly as a side-effect when the user registers materialized views related to the materialized views in the group.

To view the status of refresh operations for the most recent runs of only the current groups, use the DBA_SR_GRP_STATUS view.

Related View

USER_SR_GRP_STATUS_ALL provides information on the refresh operations on the synchronous refresh groups in the database which are owned by the current user. Its columns are the same as those in DBA_SR_GRP_STATUS_ALL.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the refresh operation, which is the user who launched the operation
GROUP_ID	NUMBER	NOT NULL	Group ID of the synchronous refresh group

Column	Datatype	NULL	Description
OPERATION	VARCHAR2(7)		The phase of the refresh operation performed: • PREPARE • EXECUTE
STATUS	VARCHAR2(10)		The status of the refresh operation: • RUNNING • NOT PROCESSED • COMPLETE • ERROR-SOFT • ERROR-HARD • ABORT • PARTIAL
CURRENT_RUN	VARCHAR2(1)		Indicates whether the record is for the most recent refresh-operation on the group: • Y - Yes • N - No
CURRENT_GROUP	VARCHAR2(1)		Indicates whether the record is for a current group: • Y - Yes • N - No
NUM_TBLS	NUMBER	NOT NULL	The number of tables in the synchronous refresh group
NUM_MVS	NUMBER	NOT NULL	The number of materialized views in the synchronous refresh group
BASE_TBLS_REFR_STATUS	VARCHAR2(13)		Indicates the refresh status of base tables in the synchronous refresh group. The possible values are: • NOT PROCESSED • COMPLETE • ABORT
NUM_MVS_COMPLETED	NUMBER		The number of materialized views which have completed refresh in the synchronous refresh group
NUM_MVS_ABORTED	NUMBER		The number of materialized views which have terminated refresh in the synchronous refresh group
ERROR_NUMBER	NUMBER		Error number of the run (if any)
ERROR_MESSAGE	VARCHAR2(4000)		Error message of the run (if any)
PREPARE_START_TIME	DATE		Time that the PREPARE_REFRESH phase of the run started
PREPARE_END_TIME	DATE		Time that the PREPARE_REFRESH phase of the run ended
EXECUTE_START_TIME	DATE		Time that the EXECUTE_REFRESH phase of the run started
EXECUTE_END_TIME	DATE		Time that the EXECUTE_REFRESH phase of the run ended

> **See Also:**
>
> - "USER_SR_GRP_STATUS_ALL"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SYNC_REFRESH package

6.444 DBA_SR_OBJ

DBA_SR_OBJ provides information on the objects registered for synchronous refresh for current groups.

Related View

USER_SR_OBJ provides information on the objects registered for synchronous refresh for current groups for the current user. Its columns are the same as those in DBA_SR_OBJ.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the synchronous refresh object
NAME	VARCHAR2(128)	NOT NULL	Name of the synchronous refresh object
TYPE	VARCHAR2(5)		Type of synchronous refresh object: • MVIEW • TABLE
GROUP_ID	NUMBER	NOT NULL	Group ID of the synchronous refresh group to which this object belongs
STAGING_LOG_NAME	VARCHAR2(128)		Name of the staging log for tables. This column has a value of NULL for materialized views.

> **See Also:**
>
> "USER_SR_OBJ"

6.445 DBA_SR_OBJ_ALL

DBA_SR_OBJ_ALL provides information on the objects registered for synchronous refresh for current and defunct groups.

To see information on the objects registered for synchronous refresh for only the current groups, use the DBA_SR_OBJ view.

Related View

USER_SR_OBJ_ALL provides information on the objects registered for synchronous refresh for current and defunct groups for the current user. Its columns are the same as those in DBA_SR_OBJ_ALL.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the synchronous refresh object
NAME	VARCHAR2(128)	NOT NULL	Name of the synchronous refresh object
TYPE	VARCHAR2(5)		Type of synchronous refresh object: • MVIEW • TABLE
GROUP_ID	NUMBER	NOT NULL	Group ID of the synchronous refresh group to which this object belongs
CURRENT_GROUP	VARCHAR2(1)		Indicates whether the record is for a current group: • Y - Yes • N - No
STAGING_LOG_NAME	VARCHAR2(128)		Name of the staging log for tables. This column has a value of NULL for materialized views.

See Also:

"USER_SR_OBJ_ALL"

6.446 DBA_SR_OBJ_STATUS

DBA_SR_OBJ_STATUS provides information on the status of objects registered for synchronous refresh for the current refresh operations for the current synchronous refresh groups in the database.

To see information on the status of objects registered for synchronous refresh, use the DBA_SR_OBJ_STATUS_ALL view.

Related View

USER_SR_OBJ_STATUS provides information on the status of objects registered for synchronous refresh for the current refresh operations for the current synchronous refresh groups in the database which are owned by the current user. Its columns are the same as those in DBA_SR_OBJ_STATUS.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the synchronous refresh object
NAME	VARCHAR2(128)	NOT NULL	Name of the synchronous refresh object
TYPE	VARCHAR2(5)		Type of synchronous refresh object: • MVIEW • TABLE
GROUP_ID	NUMBER	NOT NULL	Group ID of the synchronous refresh group to which this object belongs
STATUS	VARCHAR2(13)		Status of the synchronous refresh object: • NOT PROCESSED • COMPLETE • ABORT

Column	Datatype	NULL	Description
ERROR_NUMBER	NUMBER		Error number of the run (if any)
ERROR_MESSAGE	VARCHAR2(4000)		Error message of the run (if any)
LAST_MODIFIED_TIME	DATE		Last modification time of the synchronous refresh object

> **See Also:**
>
> "USER_SR_OBJ_STATUS"

6.447 DBA_SR_OBJ_STATUS_ALL

DBA_SR_OBJ_STATUS_ALL provides information on the status of objects registered for synchronous refresh.

The view contains information on the status of the objects of both the current and past runs of both current and defunct groups. Therefore, this view can be used to examine the history of synchronous refresh operations. The current run of a group is the most recent run of a group; a current group is a currently valid group, which is capable of being refreshed. A group becomes defunct when it is unregistered for any reason, either explicitly by the user or implicitly as a side-effect when the user registers materialized views related to the materialized views in the group.

To see information on the status of refresh operations for the most recent runs of only the current groups, use the DBA_SR_OBJ_STATUS view.

Related View

USER_SR_OBJ_STATUS_ALL provides information on the status of objects registered for synchronous refresh in the database which are owned by the current user. Its columns are the same as those in DBA_SR_OBJ_STATUS_ALL.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the synchronous refresh object
NAME	VARCHAR2(128)	NOT NULL	Name of the synchronous refresh object
TYPE	VARCHAR2(5)		Type of synchronous refresh object: • MVIEW • TABLE
GROUP_ID	NUMBER	NOT NULL	Group ID of the synchronous refresh group to which this object belongs
STATUS	VARCHAR2(13)		Status of the synchronous refresh object: • NOT PROCESSED • COMPLETE • ABORT

Column	Datatype	NULL	Description
CURRENT_RUN	VARCHAR2(1)		Indicates whether the record is for the most recent refresh operation on the group: • Y - Yes • N - No
CURRENT_GROUP	VARCHAR2(1)		Indicates whether the record is for a current group: • Y - Yes • N - No
ERROR_NUMBER	NUMBER		Error number of the run (if any)
ERROR_MESSAGE	VARCHAR2(4000)		Error message of the run (if any)
LAST_MODIFIED_TIME	DATE		Last modification time of the synchronous refresh object

See Also:

"USER_SR_OBJ_STATUS_ALL"

6.448 DBA_SR_PARTN_OPS

DBA_SR_PARTN_OPS provides information on the partition operations registered on the base tables of the materialized views registered for synchronous refresh.

These rows last only as long as the registrations are active; that is, they disappear after EXECUTE_REFRESH or ABORT_REFRESH of the base table by the DBMS_SYNC_REFRESH package.

Related View

USER_SR_PARTN_OPS provides information on the partition operations registered on the base tables of the materialized views registered for synchronous refresh belonging to the current user. Its columns are the same as those in DBA_SR_PARTN_OPS.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the base table registered for synchronous refresh
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
PARTITION_OP	VARCHAR2(128)	NOT NULL	Type of partition operation: • DROP • EXCHANGE • TRUNCATE
PARTITION_NAME	VARCHAR2(128)	NOT NULL	Name of the partition to be changed
OUTSIDE_TABLE_SCHEMA	VARCHAR2(128)		Schema in which the outside table (for EXCHANGE PARTITION) was created
OUTSIDE_TABLE_NAME	VARCHAR2(128)		Name of the outside table (for EXCHANGE PARTITION)

> **See Also:**
>
> - "USER_SR_PARTN_OPS"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SYNC_REFRESH package

6.449 DBA_SR_STLOG_EXCEPTIONS

DBA_SR_STLOG_EXCEPTIONS provides information on the exceptions in the staging logs for the tables processed by DBMS_SYNC_REFRESH.PREPARE_STAGING_LOG.

Related View

USER_SR_STLOG_EXCEPTIONS provides information on the exceptions in the staging logs for the tables belonging to the current user processed by DBMS_SYNC_REFRESH.PREPARE_STAGING_LOG. Its columns are the same as those in DBA_SR_STLOG_EXCEPTIONS.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the base table registered for synchronous refresh
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the base table registered for synchronous refresh
STAGING_LOG_NAME	VARCHAR2(128)	NOT NULL	Name of the staging log for tables. This column has a value of NULL for materialized views.
BAD_ROWID	ROWID	NOT NULL	Row ID of the staging log row causing the exception for the synchronous refresh
ERROR_NUMBER	NUMBER		Error number of the exception for the synchronous refresh
ERROR_MESSAGE	VARCHAR2(4000)		Error message associated with the ERROR_NUMBER for the synchronous refresh

> **See Also:**
>
> - "USER_SR_STLOG_EXCEPTIONS"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SYNC_REFRESH package

6.450 DBA_SR_STLOG_STATS

DBA_SR_STLOG_STATS provides information on the statistics in the staging logs for the tables processed by DBMS_SYNC_REFRESH.PREPARE_STAGING_LOG.

These three statistics columns in the staging log are filled in PREPARE_STAGING_LOG:

- The number of inserts (NUM_INSERTS)
- The number of deletes (NUM_DELETES)
- The number of updates (NUM_UPDATES)

After the data in the staging logs of a synchronous refresh group have been processed by PREPARE_REFRESH and EXECUTE_REFRESH, the statistics columns for the tables in the group are cleared and appear as NULL.

Related View

USER_SR_STLOG_STATS provides information on the statistics in the staging logs for the tables belonging to the current user processed by DBMS_SYNC_REFRESH.PREPARE_STAGING_LOG.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the base table registered for synchronous refresh
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table
STAGING_LOG_NAME	VARCHAR2(128)	NOT NULL	Name of the staging log for tables. NULL for materialized views
NUM_INSERTS	NUMBER	NOT NULL	The number of inserts in the staging log
NUM_DELETES	NUMBER	NOT NULL	The number of deletes in the staging log
NUM_UPDATES	NUMBER	NOT NULL	The number of updates in the staging log
PSL_MODE	VARCHAR2(33)		The mode specified by the user in running DBMS_SYNC_REFRESH.PREPARE_STAGING_LOG. Possible values: • DELETE_TRUSTED • DELETE_TRUSTED and UPDATE_TRUSTED • ENFORCED • INSERT_TRUSTED • INSERT_TRUSTED and DELETE_TRUSTED • TRUSTED • UPDATE_TRUSTED • UPDATE_TRUSTED and INSERT_TRUSTED

See Also:

- "USER_SR_STLOG_STATS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SYNC_REFRESH package

6.451 DBA_SSCR_CAPTURE

DBA_SSCR_CAPTURE displays session state capture statistics.

Column	Datatype	NULL	Description
DB_NAME	VARCHAR2(4000)		Database name of captured session

Column	Datatype	NULL	Description
INST_NAME	VARCHAR2(4000)		Instance name of captured session
INST_ID	NUMBER		Instance ID of captured session
SESSION_ID	NUMBER		Session ID of captured session
SESSION_SERIAL#	NUMBER		Session serial number of captured session
USER_NAME	VARCHAR2(128)	NOT NULL	User name of captured session
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Schema name of captured session
SEQUENCE#	NUMBER		Sequence number of captured session
CAPTURE_MODE	VARCHAR2(7)		Mode of capture operation
CAPTURE_SCOPE	VARCHAR2(7)		Scope of capture operation
CAPTURE_FORMAT	VARCHAR2(9)		Format of capture files
CAPTURE_DIR	VARCHAR2(128)		Directory object of capture files
CAPTURE_LOCATOR	RAW(64)		Locator of primary capture file
CAPTURE_TIME	TIMESTAMP(6)		Timestamp of capture operation

6.452 DBA_SSCR_RESTORE

DBA_SSCR_RESTORE displays session state restore statistics.

Column	Datatype	NULL	Description
DB_NAME	VARCHAR2(4000)		Database name of restored session
INST_NAME	VARCHAR2(4000)		Instance name of restored session
INST_ID	NUMBER		Instance ID of restored session
SESSION_ID	NUMBER		Session ID of restored session
SESSION_SERIAL#	NUMBER		Session serial number of restored session
USER_NAME	VARCHAR2(128)	NOT NULL	User name of restored session
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Schema name of restored session
SEQUENCE#	NUMBER		Sequence number of restore operation
RESTORE_MODE	VARCHAR2(7)		Mode of restore operation
RESTORE_SCOPE	VARCHAR2(7)		Scope of restore operation
RESTORE_FORMAT	VARCHAR2(9)		Format of restore files
RESTORE_DIR	VARCHAR2(128)		Directory object of restore files
RESTORE_LOCATOR	RAW(64)		Locator of primary restore file
RESTORE_TIME	TIMESTAMP(6)		Timestamp of restore operation

6.453 DBA_STAT_EXTENSIONS

`DBA_STAT_EXTENSIONS` displays information about all optimizer statistics extensions in the database.

> **See Also:**
>
> "ALL_STAT_EXTENSIONS"

6.454 DBA_STATEMENTS

`DBA_STATEMENTS` Statements in stored objects accessible to sys. Its columns are the same as those in `ALL_STATEMENTS`.

> **See Also:**
>
> "ALL_STATEMENTS"

6.455 DBA_STMT_AUDIT_OPTS

`DBA_STMT_AUDIT_OPTS` describes current system auditing options across the system and by user.

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

Column	Datatype	NULL	Description
USER_NAME	VARCHAR2(128)		User name if by user auditing; `ANY CLIENT` if access by a proxy on behalf of a client is being audited; NULL for system-wide auditing
PROXY_NAME	VARCHAR2(128)		Name of the proxy user which is performing an operation for the client; NULL if the client is performing the operation directly
AUDIT_OPTION	VARCHAR2(40)	NOT NULL	Name of the system auditing option
SUCCESS	VARCHAR2(10)		Mode for `WHENEVER SUCCESSFUL` system auditing
FAILURE	VARCHAR2(10)		Mode for `WHENEVER NOT SUCCESSFUL` system auditing

6.456 DBA_STORED_SETTINGS

`DBA_STORED_SETTINGS` lists information about the persistent parameter settings for stored PL/SQL units for which the current user has execute privileges.

It also returns parameter information for all objects in the database and is accessible only to users with the `SELECT_CATALOG_ROLE` privilege. Its columns are the same as those in `ALL_STORED_SETTINGS`.

> **See Also:**
>
> "ALL_STORED_SETTINGS"

7

Static Data Dictionary Views: DBA_STREAMS_ADD_COLUMN to USER_ZONEMAPS

This chapter contains the static data dictionary views DBA_STREAMS_ADD_COLUMN through USER_ZONEMAPS.

7.1 DBA_STREAMS_ADD_COLUMN

DBA_STREAMS_ADD_COLUMN displays information about declarative rule-based transformations that add a column to a row logical change record (LCR).

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2(128)		Owner of the rule
RULE_NAME	VARCHAR2(128)		Name of the rule
SCHEMA_NAME	VARCHAR2(128)		Schema of the column to be added
TABLE_NAME	VARCHAR2(128)		Table of the column to be added
COLUMN_NAME	VARCHAR2(4000)		Name of the column to be added
COLUMN_VALUE	ANYDATA		Value of the column to be added
COLUMN_TYPE	VARCHAR2(4000)		Type of the column to be added
COLUMN_FUNCTION	VARCHAR2(128)		Name of the default function used to add a column
VALUE_TYPE	VARCHAR2(3)		Indicates whether to modify the old (OLD), new (NEW), or both (*) values of the LCR
PRECEDENCE	NUMBER		3 (the execution order relative to other transformations on the same STEP_NUMBER; the smaller number will be executed first)
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

7.2 DBA_STREAMS_DELETE_COLUMN

DBA_STREAMS_DELETE_COLUMN displays information about declarative rule-based transformations that delete a column from a row logical change record (LCR).

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2(128)		Owner of the rule
RULE_NAME	VARCHAR2(128)		Name of the rule
SCHEMA_NAME	VARCHAR2(128)		Schema of the column to be deleted
TABLE_NAME	VARCHAR2(128)		Table of the column to be deleted

Column	Datatype	NULL	Description
COLUMN_NAME	VARCHAR2(4000)		Name of the column to delete
VALUE_TYPE	VARCHAR2(3)		Indicates whether to modify the old (OLD), new (NEW), or both (*) values of the LCR
PRECEDENCE	NUMBER		1 (the execution order relative to other transformations on the same STEP_NUMBER; the smaller number will be executed first)
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

7.3 DBA_STREAMS_GLOBAL_RULES

DBA_STREAMS_GLOBAL_RULES displays information about the global rules created for all capture processes, propagations, and apply processes in the database. Its columns are the same as those in ALL_STREAMS_GLOBAL_RULES.

See Also:

"ALL_STREAMS_GLOBAL_RULES"

7.4 DBA_STREAMS_KEEP_COLUMNS

DBA_STREAMS_KEEP_COLUMNS displays information about declarative rule-based transformations that keep a list of columns in a row logical change record (LCR).

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2(128)		Owner of the rule which has an associated transformation
RULE_NAME	VARCHAR2(128)		Name of the rule which has an associated transformation
SCHEMA_NAME	VARCHAR2(128)		Schema of the column to be kept
TABLE_NAME	VARCHAR2(128)		Table of the column to be kept
COLUMN_NAME	VARCHAR2(4000)		Column to keep
VALUE_TYPE	VARCHAR2(3)		Indicates whether to keep the old (OLD), new (NEW), or both (*) value of the LCR
PRECEDENCE	NUMBER		0 (the execution order relative to other transformations on the same STEP_NUMBER; the smaller number will be executed first)
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

7.5 DBA_STREAMS_MESSAGE_CONSUMERS

DBA_STREAMS_MESSAGE_CONSUMERS displays information about all Streams messaging clients in the database. Its columns are the same as those in ALL_STREAMS_MESSAGE_CONSUMERS.

> **See Also:**
>
> "ALL_STREAMS_MESSAGE_CONSUMERS"

7.6 DBA_STREAMS_NEWLY_SUPPORTED

DBA_STREAMS_NEWLY_SUPPORTED displays information about all tables in the database that are newly supported by capture processes. Its columns are the same as those in ALL_STREAMS_NEWLY_SUPPORTED.

> **See Also:**
>
> "ALL_STREAMS_NEWLY_SUPPORTED"

7.7 DBA_STREAMS_RENAME_COLUMN

DBA_STREAMS_RENAME_COLUMN displays information about declarative rule-based transformations that rename a column in a row logical change record (LCR).

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2(128)		Owner of the rule
RULE_NAME	VARCHAR2(128)		Name of the rule
SCHEMA_NAME	VARCHAR2(128)		Schema of the column to be renamed
TABLE_NAME	VARCHAR2(128)		Table of the column to be renamed
FROM_COLUMN_NAME	VARCHAR2(4000)		Column to rename
TO_COLUMN_NAME	VARCHAR2(4000)		New column name
VALUE_TYPE	VARCHAR2(3)		Indicates whether to modify the old (OLD), new (NEW), or both (*) values of the LCR
PRECEDENCE	NUMBER		2 (the execution order relative to other transformations on the same STEP_NUMBER; the smaller number will be executed first)
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

7.8 DBA_STREAMS_RENAME_SCHEMA

DBA_STREAMS_RENAME_SCHEMA displays information about declarative rule-based transformations that rename a schema in a row logical change record (LCR).

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2(128)		Owner of the rule
RULE_NAME	VARCHAR2(128)		Name of the rule
FROM_SCHEMA_NAME	VARCHAR2(128)		Schema to be renamed
TO_SCHEMA_NAME	VARCHAR2(128)		New schema name
PRECEDENCE	NUMBER		5 (the execution order relative to other transformations on the same STEP_NUMBER; the smaller number will be executed first)
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

7.9 DBA_STREAMS_RENAME_TABLE

DBA_STREAMS_RENAME_TABLE displays information about declarative rule-based transformations that rename a table in a row logical change record (LCR).

Column	Datatype	NULL	Description
RULE_OWNER	VARCHAR2(128)		Owner of the rule
RULE_NAME	VARCHAR2(128)		Name of the rule
FROM_SCHEMA_NAME	VARCHAR2(128)		Schema to be renamed
TO_SCHEMA_NAME	VARCHAR2(128)		New schema name
FROM_TABLE_NAME	VARCHAR2(128)		Table to be renamed
TO_TABLE_NAME	VARCHAR2(128)		New table name
PRECEDENCE	NUMBER		4 (the execution order relative to other transformations on the same STEP_NUMBER; the smaller number will be executed first)
STEP_NUMBER	NUMBER		Order in which this transformation should be executed

7.10 DBA_STREAMS_SCHEMA_RULES

DBA_STREAMS_SCHEMA_RULES displays information about the schema rules created for all capture processes, propagations, and apply processes in the database. Its columns are the same as those in ALL_STREAMS_SCHEMA_RULES.

See Also:

"ALL_STREAMS_SCHEMA_RULES"

7.11 DBA_STREAMS_TABLE_RULES

DBA_STREAMS_TABLE_RULES displays information about the table rules created for all capture processes, propagations, and apply processes in the database. Its columns are the same as those in ALL_STREAMS_TABLE_RULES.

> **See Also:**
>
> "ALL_STREAMS_TABLE_RULES"

7.12 DBA_STREAMS_TP_COMPONENT

DBA_STREAMS_TP_COMPONENT displays information about each Replication component at each database.

Column	Datatype	NULL	Description
COMPONENT_ID	NUMBER	NOT NULL	ID of the Replication component
COMPONENT_NAME	VARCHAR2(4000)		Name of the Replication component
COMPONENT_DB	VARCHAR2(128)		Database where the Replication component resides
COMPONENT_TYPE	VARCHAR2(20)		Type of the Replication component: • CAPTURE • PROPAGATION SENDER • PROPAGATION RECEIVER • APPLY • QUEUE
COMPONENT_CHANGED_TIME	DATE		Time that the Replication component was last changed

7.13 DBA_STREAMS_TP_COMPONENT_LINK

DBA_STREAMS_TP_COMPONENT_LINK displays information about how messages flow between Replication components.

Column	Datatype	NULL	Description
SOURCE_COMPONENT_ID	NUMBER	NOT NULL	ID of the source Replication component
SOURCE_COMPONENT_NAME	VARCHAR2(4000)		Name of the source Replication component
SOURCE_COMPONENT_DB	VARCHAR2(128)		Database where the source Replication component resides

Column	Datatype	NULL	Description
SOURCE_COMPONENT_TYPE	VARCHAR2(20)		Type of the source Replication component: • CAPTURE • PROPAGATION SENDER • PROPAGATION RECEIVER • APPLY • QUEUE
DESTINATION_COMPONENT_ID	NUMBER	NOT NULL	ID of the destination Replication component
DESTINATION_COMPONENT_NAME	VARCHAR2(4000)		Name of the destination Replication component
DESTINATION_COMPONENT_DB	VARCHAR2(128)		Database where the destination Replication component resides
DESTINATION_COMPONENT_TYPE	VARCHAR2(20)		Type of the destination Replication component: • CAPTURE • PROPAGATION SENDER • PROPAGATION RECEIVER • APPLY • QUEUE
PATH_ID	NUMBER	NOT NULL	ID of the stream path
POSITION	NUMBER		Position of the link within the stream path

7.14 DBA_STREAMS_TP_COMPONENT_STAT

DBA_STREAMS_TP_COMPONENT_STAT displays temporary performance statistics and session statistics about each Replication component.

Column	Datatype	NULL	Description
COMPONENT_ID	NUMBER	NOT NULL	ID of the Replication component
COMPONENT_NAME	VARCHAR2(4000)		Name of the Replication component
COMPONENT_DB	VARCHAR2(128)		Database where the Replication component resides
COMPONENT_TYPE	VARCHAR2(20)		Type of the Replication component: • CAPTURE • PROPAGATION SENDER • PROPAGATION RECEIVER • APPLY • QUEUE
SUB_COMPONENT_TYPE	VARCHAR2(27)		Type of the Replication subcomponent: • LOGMINER READER • LOGMINER PREPARER • LOGMINER BUILDER • CAPTURE SESSION • PROPAGATION SENDER+RECEIVER • APPLY READER • APPLY COORDINATOR • APPLY SERVER

Column	Datatype	NULL	Description
SESSION_ID	NUMBER		ID of the Replication session for the Replication component
SESSION_SERIAL#	NUMBER		Serial number of the Replication session for the Replication component
STATISTIC_TIME	DATE		Time that the statistic was taken
STATISTIC_NAME	VARCHAR2(64)		Name of the statistic
STATISTIC_VALUE	VARCHAR2(4000)		Value of the statistic
STATISTIC_UNIT	VARCHAR2(64)		Unit of the statistic
ADVISOR_RUN_ID	NUMBER		Logical number (1-based) of the Advisor run
ADVISOR_RUN_TIME	DATE		Time that the Advisor was run

7.15 DBA_STREAMS_TP_DATABASE

DBA_STREAMS_TP_DATABASE displays information about each database that contains Replication components.

Column	Datatype	NULL	Description
GLOBAL_NAME	VARCHAR2(128)	NOT NULL	Global name of the database
LAST_QUERIED	DATE	NOT NULL	Time that the database was last queried
VERSION	VARCHAR2(128)		Database version of the database
COMPATIBILITY	VARCHAR2(128)		Compatible setting of the database
MANAGEMENT_PACK_ACCESS	VARCHAR2(128)		Management pack access of the database

7.16 DBA_STREAMS_TP_PATH_BOTTLENECK

DBA_STREAMS_TP_PATH_BOTTLENECK displays temporary information about Replication components that might be slowing down the flow of messages in a stream path.

Column	Datatype	NULL	Description
PATH_ID	NUMBER		ID of the stream path
COMPONENT_ID	NUMBER		ID of the bottleneck component
COMPONENT_NAME	VARCHAR2(4000)		Name of the bottleneck component
COMPONENT_DB	VARCHAR2(128)		Database where the bottleneck component resides
COMPONENT_TYPE	VARCHAR2(20)		Type of the bottleneck component: • CAPTURE • PROPAGATION SENDER • PROPAGATION RECEIVER • APPLY • QUEUE
TOP_SESSION_ID	NUMBER		ID of the top session for the bottleneck component

Column	Datatype	NULL	Description
TOP_SESSION_SERIAL#	NUMBER		Serial number of the top session for the bottleneck component
ACTION_NAME	VARCHAR2(64)		Action name for the bottleneck process
BOTTLENECK_IDENTIFIED	VARCHAR2(30)		Indicates whether the bottleneck was identified (YES) or not (NO)
ADVISOR_RUN_ID	NUMBER		Logical number (1-based) of the Advisor run
ADVISOR_RUN_TIME	DATE		Time that the Advisor was run
ADVISOR_RUN_REASON	VARCHAR2(4000)		Reason for the bottleneck analysis result.: • NULL - Bottleneck is identified • PRE-11.1 DATABASE EXISTS - A pre-release 11.1 database exists in the stream path • DIAGNOSTIC PACK REQUIRED - A database in the stream path does not have the diagnostic package installed • NO BOTTLENECK IDENTIFIED

7.17 DBA_STREAMS_TP_PATH_STAT

DBA_STREAMS_TP_PATH_STAT displays temporary performance statistics about each stream path that exists in the Replication topology.

Column	Datatype	NULL	Description
PATH_ID	NUMBER		ID of the stream path
STATISTIC_TIME	DATE		Time that the statistic was taken
STATISTIC_NAME	VARCHAR2(64)		Name of the statistic
STATISTIC_VALUE	NUMBER		Value of the statistic
STATISTIC_UNIT	VARCHAR2(64)		Unit of the statistic
ADVISOR_RUN_ID	NUMBER		Logical number (1-based) of the Advisor run
ADVISOR_RUN_TIME	DATE		Time that the Advisor was run

7.18 DBA_STREAMS_TRANSFORM_FUNCTION

DBA_STREAMS_TRANSFORM_FUNCTION displays information about all rule-based transformation functions in the database. Its columns are the same as those in ALL_STREAMS_TRANSFORM_FUNCTION.

See Also:

"ALL_STREAMS_TRANSFORM_FUNCTION"

7.19 DBA_SUBPART_COL_STATISTICS

DBA_SUBPART_COL_STATISTICS provides column statistics and histogram information for all subpartitions in the database. Its columns are the same as those in ALL_SUBPART_COL_STATISTICS.

> **See Also:**
>
> "ALL_SUBPART_COL_STATISTICS"

7.20 DBA_SUBPART_HISTOGRAMS

DBA_SUBPART_HISTOGRAMS lists actual histogram data (end-points per histogram) for histograms on all table subpartitions in the database. Its columns are the same as those in ALL_SUBPART_HISTOGRAMS.

> **See Also:**
>
> "ALL_SUBPART_HISTOGRAMS"

7.21 DBA_SUBPART_KEY_COLUMNS

DBA_SUBPART_KEY_COLUMNS lists subpartitioning key columns for all composite-partitioned tables (and local indexes on composite-partitioned tables) in the database. Its columns are the same as those in ALL_SUBPART_KEY_COLUMNS.

> **See Also:**
>
> "ALL_SUBPART_KEY_COLUMNS"

7.22 DBA_SUBPARTITION_TEMPLATES

DBA_SUBPARTITION_TEMPLATES describes all subpartition templates in the database. Its columns are the same as those in ALL_SUBPARTITION_TEMPLATES.

> **See Also:**
>
> "ALL_SUBPARTITION_TEMPLATES"

7.23 DBA_SUBSCR_REGISTRATIONS

DBA_SUBSCR_REGISTRATIONS displays information about all subscription registrations in the database.

Related View

USER_SUBSCR_REGISTRATIONS displays information about the subscription registrations owned by the current user.

Column	Datatype	NULL	Description
REG_ID	NUMBER		Registration ID
SUBSCRIPTION_NAME	VARCHAR2(128)	NOT NULL	Name of the subscription registration. The subscription name is of the form *schema.queue* if the registration is for a single consumer queue or *schema.queue:consumer_name* if the registration is for a multiconsumer queue.
LOCATION_NAME	VARCHAR2(256)	NOT NULL	Location endpoint of the registration
USER#	NUMBER	NOT NULL	Internally generated user ID
USER_CONTEXT	RAW(128)		Context the user provided during registration of PL/SQL registrations or an internally generated context for OCI registrations
CONTEXT_SIZE	NUMBER		Size of the context
NAMESPACE	VARCHAR2(9)		Namespace of the subscription registration: • ANONYMOUS • AQ • DBCHANGE
PRESENTATION	VARCHAR2(7)		Presentation format of notifications: • DEFAULT - Binary • XML
VERSION	VARCHAR2(8)		Database version: • 8.1.6 • 10.2 • 11.1
STATUS	VARCHAR2(8)		Status of the registration: • DB REG - Database registration • LDAP REG - LDAP registration
ANY_CONTEXT	ANYDATA		AnyData user context
CONTEXT_TYPE	NUMBER		Type of the user context
QOSFLAGS	VARCHAR2(64)		Quality of service of the registration: • RELIABLE - Reliable notifications persist across instance and database restarts • PAYLOAD - Payload delivery is required. It is only supported for client notification and only for RAW queues. • PURGE_ON_NTFN - Registration is to be purged automatically when the first notification is delivered to this registration location

Column	Datatype	NULL	Description
PAYLOAD_CALLBACK	VARCHAR2(4000)		Any callback registered to serialize the notification payload
TIMEOUT	TIMESTAMP(6)		Registration timeout
REG_TIME	TIMESTAMP(6) WITH TIME ZONE		Time of the registration
NTFN_GROUPING_CLASS	VARCHAR2(4)		Notification grouping class
NTFN_GROUPING_VALUE	NUMBER		Notification grouping value
NTFN_GROUPING_TYPE	VARCHAR2(7)		Notification grouping type: • SUMMARY • LAST
NTFN_GROUPING_START_TIME	TIMESTAMP(6) WITH TIME ZONE		Notification grouping start time
NTFN_GROUPING_REPEAT_COUNT	VARCHAR2(40)		Notification grouping repeat count, or FOREVER

> **See Also:**
>
> "USER_SUBSCR_REGISTRATIONS"

7.24 DBA_SUPPLEMENTAL_LOGGING

DBA_SUPPLEMENTAL_LOGGING provides information about supplemental logging for a pluggable database (PDB) in a multitenant container database (CDB).

Column	Datatype	NULL	Description
MINIMAL	VARCHAR2(3)		Identifies whether minimal supplemental logging is on (YES or NO)
PRIMARY_KEY	VARCHAR2(3)		Identifies whether primary key supplemental logging is on (YES or NO)
UNIQUE_INDEX	VARCHAR2(3)		Identifies whether unique column supplemental logging is on (YES or NO)
FOREIGN_KEY	VARCHAR2(3)		Identifies whether foreign key supplemental logging is on (YES or NO)
ALL_COLUMN	VARCHAR2(3)		Identifies whether all column supplemental logging is on (YES or NO)
PROCEDURAL	VARCHAR2(3)		Identifies whether supplemental logging for procedural replication is on (YES or NO)
SUBSET_REP	VARCHAR2(3)		Indicates whether subset database replication is on (YES or NO)

> **See Also:**
>
> - *Oracle Database Utilities* for more information about supplemental logging
> - "V$DATABASE" for information about supplemental logging in a CDB

7.25 DBA_SYNC_CAPTURE

`DBA_SYNC_CAPTURE` displays information about all synchronous capture processes in the database. Its columns are the same as those in `ALL_SYNC_CAPTURE`.

> **See Also:**
>
> "ALL_SYNC_CAPTURE"

7.26 DBA_SYNC_CAPTURE_PREPARED_TABS

`DBA_SYNC_CAPTURE_PREPARED_TABS` displays information about all tables in the database that are prepared for synchronous capture instantiation. Its columns are the same as those in `ALL_SYNC_CAPTURE_PREPARED_TABS`.

> **See Also:**
>
> "ALL_SYNC_CAPTURE_PREPARED_TABS"

7.27 DBA_SYNC_CAPTURE_TABLES

`DBA_SYNC_CAPTURE_TABLES` displays information about all tables in the database that are captured by synchronous captures. Its columns are the same as those in `ALL_SYNC_CAPTURE_TABLES`.

> **See Also:**
>
> "ALL_SYNC_CAPTURE_TABLES"

7.28 DBA_SYNONYMS

DBA_SYNONYMS describes all synonyms in the database. Its columns are the same as those in ALL_SYNONYMS.

> **See Also:**
>
> "ALL_SYNONYMS"

7.29 DBA_SYS_PRIVS

DBA_SYS_PRIVS describes system privileges granted to users and roles.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)		Grantee name, user, or role receiving the grant
PRIVILEGE	VARCHAR2(40)		System privilege
ADMIN_OPTION	VARCHAR2(3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the grant was inherited from another container (YES) or not (NO)

> **See Also:**
>
> "USER_SYS_PRIVS"

7.30 DBA_SYS_PRIVS_ALL

DBA_SYS_PRIVS_ALL describes system privileges and schema privileges granted to users and roles.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)		Grantee name, user, or role receiving the grant
PRIVILEGE	VARCHAR2(40)		Privilege

Column	Datatype	NULL	Description
SCHEMA	VARCHAR2(128)		Schema on which the privilege was granted For system privileges, the value of this column is null.
ADMIN_OPTION	VARCHAR2(3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the grant was inherited from another container (YES) or not (NO)

Note:

This view is available starting with Oracle Database 23ai.

See Also:

"USER_SYS_PRIVS_ALL"

7.31 DBA_TAB_COL_STAT_MODELS

DBA_TAB_COL_STAT_MODELS describes real-time statistics models for all tables in the database. Its columns are the same as those in ALL_TAB_COL_STAT_MODELS.

Real-time statistics models use machine learning algorithms to predict the number of distinct values (NDV) for table columns.

See Also:

"ALL_TAB_COL_STAT_MODELS"

7.32 DBA_TAB_COL_STATISTICS

DBA_TAB_COL_STATISTICS contains column statistics and histogram information extracted from DBA_TAB_COLUMNS. Its columns are the same as those in ALL_TAB_COL_STATISTICS.

> **See Also:**
>
> - "DBA_TAB_COLUMNS"
> - "ALL_TAB_COL_STATISTICS"

7.33 DBA_TAB_COLS

DBA_TAB_COLS describes the columns of all tables, views, and clusters in the database.

Its columns (except for SENSITIVE_COLUMN) are the same as those in ALL_TAB_COLS.

To gather statistics for this view, use the DBMS_STATS package.

This view differs from DBA_TAB_COLUMNS in that system-generated hidden columns are not filtered out.

Columns marked with an asterisk (*) in the table below remain for backward compatibility with Oracle7. This information is now in the [TAB|PART]_COL_STATISTICS views.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table, view, or cluster
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table, view, or cluster
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Column name
DATA_TYPE	VARCHAR2(128)		Data type of the column
DATA_TYPE_MOD	VARCHAR2(3)		Data type modifier of the column
DATA_TYPE_OWNER	VARCHAR2(128)		Owner of the data type of the column
DATA_LENGTH	NUMBER	NOT NULL	Length of the column (in bytes)
DATA_PRECISION	NUMBER		Decimal precision for NUMBER data type; binary precision for FLOAT data type; NULL for all other data types
DATA_SCALE	NUMBER		Digits to the right of the decimal point in a number
NULLABLE	VARCHAR2(1)		Indicates whether a column allows NULLs. The value is N if there is a NOT NULL constraint on the column or if the column is part of a PRIMARY KEY.
COLUMN_ID	NUMBER		Sequence number of the column as created
DEFAULT_LENGTH	NUMBER		Length of the default value for the column
DATA_DEFAULT	LONG		Default value for the column
DATA_DEFAULT_VC	VARCHAR2(4000)		Default value for the column This column may truncate the default value.

Column	Datatype	NULL	Description
NUM_DISTINCT*	NUMBER		Number of distinct values in the column
LOW_VALUE*	RAW(1000)		Low value in the column
HIGH_VALUE*	RAW(1000)		High value in the column
DENSITY*	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT.
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in the histogram for the column **Note:** The number of buckets in a histogram is specified in the SIZE parameter of the ANALYZE SQL statement. However, Oracle Database does not create a histogram with more buckets than the number of rows in the sample. Also, if the sample contains any values that are very repetitious, Oracle Database creates the specified number of buckets, but the value indicated by this column may be smaller because of an internal compression algorithm.
LAST_ANALYZED	DATE		Date on which this column was most recently analyzed
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this column
CHARACTER_SET_NAME	VARCHAR2(44)		Name of the character set: • CHAR_CS • NCHAR_CS
CHAR_COL_DECL_LENGTH	NUMBER		Declaration length of the character type column
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics are gathered or incrementally maintained, otherwise it will be NO
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
CHAR_LENGTH	NUMBER		Displays the length of the column in characters. This value only applies to the following data types: • CHAR • VARCHAR2 • NCHAR • NVARCHAR2
CHAR_USED	VARCHAR2(1)		Indicates that the column uses BYTE length semantics (B) or CHAR length semantics (C), or whether the data type is not any of the following (NULL): • CHAR • VARCHAR2 • NCHAR • NVARCHAR2

Column	Datatype	NULL	Description
V80_FMT_IMAGE	VARCHAR2(3)		Indicates whether the column data is in release 8.0 image format (YES) or not (NO)
DATA_UPGRADED	VARCHAR2(3)		Indicates whether the column data has been upgraded to the latest type version format (YES) or not (NO)
HIDDEN_COLUMN	VARCHAR2(3)		Indicates whether the column is a hidden column (YES) or not (NO)
VIRTUAL_COLUMN	VARCHAR2(3)		Indicates whether the column is a virtual column (YES) or not (NO)
SEGMENT_COLUMN_ID	NUMBER		Sequence number of the column in the segment
INTERNAL_COLUMN_ID	NUMBER	NOT NULL	Internal sequence number of the column
HISTOGRAM	VARCHAR2(15)		Indicates existence/type of histogram: • NONE • FREQUENCY • TOP-FREQUENCY • HEIGHT BALANCED • HYBRID
QUALIFIED_COL_NAME	VARCHAR2(4000)		Qualified column name
USER_GENERATED	VARCHAR2(3)		Indicates whether the column is a user-generated column (YES) or a system-generated column (NO)
DEFAULT_ON_NULL	VARCHAR2(3)		Indicates whether the column has DEFAULT ON NULL for INSERT semantics (YES) or not (NO)
DEFAULT_ON_NULL_UPD	VARCHAR2(3)		Indicates whether the column has DEFAULT ON NULL for UPDATE semantics (YES) or not (NO)
RESERVABLE_COLUMN	VARCHAR2(3)		Indicates whether the column is a reservable column (YES) or not (NO)
IDENTITY_COLUMN	VARCHAR2(3)		Indicates whether this is an identity column (YES) or not (NO)
SENSITIVE_COLUMN	VARCHAR2(3)		Indicates whether this is a sensitive column (YES) or not (NO)
EVALUATION_EDITION	VARCHAR2(128)		Name of the edition in which editioned objects referenced in an expression column are resolved
UNUSABLE_BEFORE	VARCHAR2(128)		Name of the oldest edition in which the index may be used as part of a query plan
UNUSABLE_BEGINNING	VARCHAR2(128)		Name of the edition for which the index may not be used as part of a query plan in this edition or any of its descendants
COLLATION	VARCHAR2(100)		Collation for the column. Only applies to columns with character data types.
COLLATED_COLUMN_ID	NUMBER		Internal sequence number of a column, for which this virtual column generates a collation key
DOMAIN_OWNER	VARCHAR2(128)		If a data use case domain is specified for the column, the owner of the data use case domain
DOMAIN_NAME	VARCHAR2(128)		If a data use case domain is specified for the column, the name of the data use case domain

Column	Datatype	NULL	Description
DOMAIN_COLUMN_NAME	VARCHAR2(128)		If a data use case domain is specified for the column, the name of the data use case domain column
DOMAIN_ASSOCIATION_ID	NUMBER		If a data use case domain is specified for the column, the domain association ID
VECTOR_INFO	VARCHAR2(56)		Indicates the number of vectors and their data type in an ONNX model Format: VECTOR(*dimension*,*element_type*) Example: VECTOR(768,float32)

See Also:

- "ALL_TAB_COLS"
- "DBA_TAB_COLUMNS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

7.34 DBA_TAB_COLUMNS

DBA_TAB_COLUMNS describes the columns of all tables, views, and clusters in the database.

Its columns (except for SENSITIVE_COLUMN) are the same as those in ALL_TAB_COLUMNS.

To gather statistics for this view, use the DBMS_STATS package.

This view filters out system-generated hidden columns. The DBA_TAB_COLS view does not filter out system-generated hidden columns.

Columns marked with an asterisk (*) in the table below remain for backward compatibility with Oracle7. This information is now in the [TAB|PART]_COL_STATISTICS views.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table, view, or cluster
TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the table, view, or cluster
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Column name
DATA_TYPE	VARCHAR2(128)		Data type of the column
DATA_TYPE_MOD	VARCHAR2(3)		Data type modifier of the column
DATA_TYPE_OWNER	VARCHAR2(128)		Owner of the data type of the column
DATA_LENGTH	NUMBER	NOT NULL	Length of the column (in bytes)

Column	Datatype	NULL	Description
DATA_PRECISION	NUMBER		Decimal precision for NUMBER data type; binary precision for FLOAT data type; NULL for all other data types
DATA_SCALE	NUMBER		Digits to the right of the decimal point in a number
NULLABLE	VARCHAR2(1)		Indicates whether a column allows NULLs. The value is N if there is a NOT NULL constraint on the column or if the column is part of a PRIMARY KEY. The constraint should be in an ENABLE VALIDATE state.
COLUMN_ID	NUMBER		Sequence number of the column as created
DEFAULT_LENGTH	NUMBER		Length of the default value for the column
DATA_DEFAULT	LONG		Default value for the column
DATA_DEFAULT_VC	VARCHAR2(4000)		Default value for the column This column may truncate the default value.
NUM_DISTINCT*	NUMBER		Number of distinct values in the column
LOW_VALUE*	RAW(1000)		Low value in the column
HIGH_VALUE*	RAW(1000)		High value in the column
DENSITY*	NUMBER		If a histogram is available on COLUMN_NAME, then this column displays the selectivity of a value that spans fewer than 2 endpoints in the histogram. It does not represent the selectivity of values that span 2 or more endpoints. If a histogram is not available on COLUMN_NAME, then the value of this column is 1/NUM_DISTINCT.
NUM_NULLS	NUMBER		Number of NULLs in the column
NUM_BUCKETS	NUMBER		Number of buckets in the histogram for the column **Note:** The number of buckets in a histogram is specified in the SIZE parameter of the ANALYZE SQL statement. However, Oracle Database does not create a histogram with more buckets than the number of rows in the sample. Also, if the sample contains any values that are very repetitious, Oracle Database creates the specified number of buckets, but the value indicated by this column may be smaller because of an internal compression algorithm.
LAST_ANALYZED	DATE		Date on which this column was most recently analyzed
SAMPLE_SIZE	NUMBER		Sample size used in analyzing this column
CHARACTER_SET_NAME	VARCHAR2(44)		Name of the character set: • CHAR_CS • NCHAR_CS
CHAR_COL_DECL_LENGTH	NUMBER		Declaration length of the character type column
GLOBAL_STATS	VARCHAR2(3)		GLOBAL_STATS will be YES if statistics are gathered or incrementally maintained, otherwise it will be NO
USER_STATS	VARCHAR2(3)		Indicates whether statistics were entered directly by the user (YES) or not (NO)

Column	Datatype	NULL	Description
AVG_COL_LEN	NUMBER		Average length of the column (in bytes)
CHAR_LENGTH	NUMBER		Displays the length of the column in characters. This value only applies to the following data types: • CHAR • VARCHAR2 • NCHAR • NVARCHAR2
CHAR_USED	VARCHAR2(1)		Indicates that the column uses BYTE length semantics (B) or CHAR length semantics (C), or whether the data type is not any of the following (NULL): • CHAR • VARCHAR2 • NCHAR • NVARCHAR2
V80_FMT_IMAGE	VARCHAR2(3)		Indicates whether the column data is in release 8.0 image format (YES) or not (NO)
DATA_UPGRADED	VARCHAR2(3)		Indicates whether the column data has been upgraded to the latest type version format (YES) or not (NO)
HISTOGRAM	VARCHAR2(15)		Indicates existence/type of histogram: • NONE • FREQUENCY • TOP-FREQUENCY • HEIGHT BALANCED • HYBRID
DEFAULT_ON_NULL	VARCHAR2(3)		Indicates whether the column has DEFAULT ON NULL for INSERT semantics (YES) or not (NO)
DEFAULT_ON_NULL_UPD	VARCHAR2(3)		Indicates whether the column has DEFAULT ON NULL for UPDATE semantics (YES) or not (NO)
RESERVABLE_COLUMN	VARCHAR2(3)		Indicates whether the column is a reservable column (YES) or not (NO)
IDENTITY_COLUMN	VARCHAR2(3)		Indicates whether this is an identity column (YES) or not (NO)
SENSITIVE_COLUMN	VARCHAR2(3)		Indicates whether this is a sensitive column (YES) or not (NO)
EVALUATION_EDITION	VARCHAR2(128)		Name of the edition in which editioned objects referenced in an expression column are resolved
UNUSABLE_BEFORE	VARCHAR2(128)		Name of the oldest edition in which the index may be used as part of a query plan
UNUSABLE_BEGINNING	VARCHAR2(128)		Name of the edition for which the index may not be used as part of a query plan in this edition or any of its descendants
COLLATION	VARCHAR2(100)		Collation for the column. Only applies to columns with character data types.
DOMAIN_OWNER	VARCHAR2(128)		If a data use case domain is specified for the column, the owner of the data use case domain

Column	Datatype	NULL	Description
DOMAIN_NAME	VARCHAR2(128)		If a data use case domain is specified for the column, the name of the data use case domain
DOMAIN_COLUMN_NAME	VARCHAR2(128)		If a data use case domain is specified for the column, the name of the data use case domain column
DOMAIN_ASSOCIATION_ID	NUMBER		If a data use case domain is specified for the column, the domain association ID
VECTOR_INFO	VARCHAR2(56)		Indicates the number of vectors and their data type in an ONNX model Format: VECTOR(*dimension*,*element_type*) Example: VECTOR(768,float32)

See Also:

- "ALL_TAB_COLUMNS"
- "DBA_TAB_COLS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

7.35 DBA_TAB_COMMENTS

DBA_TAB_COMMENTS displays comments on all tables and views in the database. Its columns are the same as those in ALL_TAB_COMMENTS.

See Also:

"ALL_TAB_COMMENTS"

7.36 DBA_TAB_HISTGRM_PENDING_STATS

DBA_TAB_HISTGRM_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions in the database. Its columns are the same as those in ALL_TAB_HISTGRM_PENDING_STATS.

See Also:

"ALL_TAB_HISTGRM_PENDING_STATS"

7.37 DBA_TAB_HISTOGRAMS

DBA_TAB_HISTOGRAMS describes histograms on columns of all tables in the database. Its columns are the same as those in ALL_TAB_HISTOGRAMS.

> **See Also:**
>
> "ALL_TAB_HISTOGRAMS"

7.38 DBA_TAB_IDENTITY_COLS

DBA_TAB_IDENTITY_COLS describes all table identity columns. Its columns are the same as those in ALL_TAB_IDENTITY_COLS.

> **See Also:**
>
> "ALL_TAB_IDENTITY_COLS"

7.39 DBA_TAB_MODIFICATIONS

DBA_TAB_MODIFICATIONS describes modifications to all tables in the database that have been modified since the last time statistics were gathered on the tables. Its columns are the same as those in ALL_TAB_MODIFICATIONS.

> **See Also:**
>
> "ALL_TAB_MODIFICATIONS"

7.40 DBA_TAB_PARTITIONS

DBA_TAB_PARTITIONS displays partition-level partitioning information, partition storage parameters, and partition statistics generated by the DBMS_STATS package for all partitions in the database.

Its columns are the same as those in "ALL_TAB_PARTITIONS".

7.41 DBA_TAB_PENDING_STATS

DBA_TAB_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions in the database. Its columns are the same as those in ALL_TAB_PENDING_STATS.

> **See Also:**
>
> "ALL_TAB_PENDING_STATS"

7.42 DBA_TAB_PRIVS

DBA_TAB_PRIVS describes all object grants in the database.

Related View

USER_TAB_PRIVS describes the object grants for which the current user is the object owner, grantor, or grantee.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)		Name of the user or role to whom access was granted
OWNER	VARCHAR2(128)		Owner of the object
TABLE_NAME	VARCHAR2(128)		Name of the object. The object can be any object, including tables, packages, indexes, sequences, and so on.
GRANTOR	VARCHAR2(128)		Name of the user who performed the grant
PRIVILEGE	VARCHAR2(40)		Privilege on the object
GRANTABLE	VARCHAR2(3)		Indicates whether the privilege was granted with the GRANT OPTION (YES) or not (NO)
HIERARCHY	VARCHAR2(3)		Indicates whether the privilege was granted with the HIERARCHY OPTION (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
TYPE	VARCHAR2(24)		Type of the object
INHERITED	VARCHAR2(3)		Indicates whether the grant was inherited from another container (YES) or not (NO)

> **See Also:**
>
> "USER_TAB_PRIVS"

7.43 DBA_TAB_STATISTICS

`DBA_TAB_STATISTICS` displays optimizer statistics for all tables in the database. Its columns are the same as those in `ALL_TAB_STATISTICS`.

> **See Also:**
>
> "ALL_TAB_STATISTICS"

7.44 DBA_TAB_STAT_PREFS

`DBA_TAB_STAT_PREFS` displays information about statistics preferences for all tables in the database. Its columns are the same as those in `ALL_TAB_STAT_PREFS`.

> **See Also:**
>
> "ALL_TAB_STAT_PREFS".

7.45 DBA_TAB_STATS_HISTORY

`DBA_TAB_STATS_HISTORY` provides a history of table statistics modifications for all tables in the database. Its columns are the same as those in `ALL_TAB_STATS_HISTORY`.

> **See Also:**
>
> "ALL_TAB_STATS_HISTORY"

7.46 DBA_TAB_SUBPARTITIONS

`DBA_TAB_SUBPARTITIONS` displays, for each table subpartition, the subpartition name, name of the table and partition to which it belongs, its storage attributes, and statistics generated by the `DBMS_STATS` package.

Its columns are the same as those in "ALL_TAB_SUBPARTITIONS".

7.47 DBA_TABLE_ACCESS_STATS

DBA_TABLE_ACCESS_STATS displays the scan count for all tables and partitions in the database. Its columns are the same as those in ALL_TABLE_ACCESS_STATS.

> **Note:**
>
> The ALL_TABLE_ACCESS_STATS and DBA_TABLE_ACCESS_STATS views do not display data for Oracle-maintained schemas. You can view data for an Oracle-maintained schema by connecting to the schema and querying the USER_TABLE_ACCESS_STATS view.

> **See Also:**
>
> - "ALL_TABLE_ACCESS_STATS"
> - "USER_TABLE_ACCESS_STATS"

7.48 DBA_TABLE_VIRTUAL_COLUMNS

DBA_TABLE_VIRTUAL_COLUMNS describes virtual columns in all tables in the database. Its columns are the same as those in ALL_TABLE_VIRTUAL_COLUMNS.

> **See Also:**
>
> "ALL_TABLE_VIRTUAL_COLUMNS"

7.49 DBA_TABLES

DBA_TABLES describes all relational tables in the database. Its columns are the same as those in ALL_TABLES.

To gather statistics for this view, use the DBMS_STATS package.

> **See Also:**
>
> "ALL_TABLES"

7.50 DBA_TABLESPACE_GROUPS

DBA_TABLESPACE_GROUPS describes all tablespace groups in the database.

Column	Datatype	NULL	Description
GROUP_NAME	VARCHAR2(30)	NOT NULL	Name of the tablespace group
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of the tablespace

7.51 DBA_TABLESPACE_THRESHOLDS

DBA_TABLESPACE_THRESHOLDS describes space utilization threshold settings for all tablespaces in the database.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2(30)		Tablespace name
CONTENTS	VARCHAR2(9)		Tablespace contents: • UNDO • PERMANENT • TEMPORARY
EXTENT_MANAGEMENT	VARCHAR2(10)		Indicates whether the extents in the tablespace are dictionary managed (DICTIONARY) or locally managed (LOCAL)
THRESHOLD_TYPE	VARCHAR2(8)		Indicates whether the threshold value is derived from a DEFAULT threshold or an EXPLICIT threshold
METRICS_NAME	VARCHAR2(64)		Name of the metric for which the threshold is set
WARNING_OPERATOR	VARCHAR2(12)		Relational operator for warning thresholds: • GT • EQ • LT • LE • GE • CONTAINS • NE • DO_NOT_CHECK
WARNING_VALUE	VARCHAR2(256)		Warning threshold value
CRITICAL_OPERATOR	VARCHAR2(12)		Relational operator for critical thresholds: • GT • EQ • LT • LE • GE • CONTAINS • NE • DO_NOT_CHECK
CRITICAL_VALUE	VARCHAR2(256)		Critical threshold value

7.52 DBA_TABLESPACE_USAGE_METRICS

DBA_TABLESPACE_USAGE_METRICS describes tablespace usage metrics for all types of tablespaces, including permanent, temporary, and undo tablespaces.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2(30)		Tablespace name
USED_SPACE	NUMBER		Total space consumed by all objects created in the tablespace, expressed as number of data blocks For undo tablespaces, the value of this column includes space consumed by both expired and unexpired undo segments.
ALLOCATION_SIZE	NUMBER		For smallfile tablespaces, the combined current size of all datafiles, expressed as number of data blocks For bigfile tablespaces, the current size of the single datafile
TABLESPACE_SIZE	NUMBER		The maximum size of the tablespace, expressed as number of data blocks • If the tablespace contains any datafiles with autoextend enabled, then this column displays the maximum size to which the tablespace can grow. Underlying storage free space, such as Oracle ASM or file system storage, is also taken into account when computing this value. For example: – If a tablespace has a current size of 5 GB, the combined maximum size of its datafiles is 32 GB, and its underlying storage has 20 GB of free space, then this column will have a value of approximately 25 GB. – If a tablespace has a current size of 10 GB, the combined maximum size its datafiles is 20 GB, and its underlying storage has 25 GB of free space, then this column will have a value of approximately 20 GB. • If the tablespace contains only datafiles with autoextend disabled, then this column displays the combined size of all datafiles in the tablespace.
USED_PERCENT	NUMBER		Percentage of used space, as a function of the maximum possible tablespace size
BLOCK_SIZE	NUMBER		Tablespace block size (in bytes)

7.53 DBA_TABLESPACES

DBA_TABLESPACES describes all tablespaces in the database.

Related View

USER_TABLESPACES describes the tablespaces accessible to the current user. This view does not display the PLUGGED_IN column.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of the tablespace
BLOCK_SIZE	NUMBER	NOT NULL	Tablespace block size (in bytes)
INITIAL_EXTENT	NUMBER		Default initial extent size (in bytes)
NEXT_EXTENT	NUMBER		Default incremental extent size (in bytes)
MIN_EXTENTS	NUMBER	NOT NULL	Default minimum number of extents
MAX_EXTENTS	NUMBER		Default maximum number of extents
MAX_SIZE	NUMBER		Default maximum size of segments (in Oracle blocks)
PCT_INCREASE	NUMBER		Default percent increase for extent size
MIN_EXTLEN	NUMBER		Minimum extent size for this tablespace (in bytes)
STATUS	VARCHAR2(9)		Tablespace status: • ONLINE • OFFLINE • READ ONLY
CONTENTS	VARCHAR2(9)		Tablespace contents: • UNDO • LOST WRITE PROTECTION • PERMANENT • TEMPORARY
LOGGING	VARCHAR2(9)		Default logging attribute: • LOGGING • NOLOGGING
FORCE_LOGGING	VARCHAR2(3)		Indicates whether the tablespace is under force logging mode (YES) or not (NO)
EXTENT_MANAGEMENT	VARCHAR2(10)		Indicates whether the extents in the tablespace are dictionary managed (DICTIONARY) or locally managed (LOCAL)
ALLOCATION_TYPE	VARCHAR2(9)		Type of extent allocation in effect for the tablespace: • SYSTEM • UNIFORM • USER
PLUGGED_IN	VARCHAR2(3)		Indicates whether the tablespace is plugged in (YES) or not (NO)
SEGMENT_SPACE_MANAGEMENT	VARCHAR2(6)		Indicates whether the free and used segment space in the tablespace is managed using free lists (MANUAL) or bitmaps (AUTO)

Column	Datatype	NULL	Description
DEF_TAB_COMPRESSION	VARCHAR2(8)		Indicates whether default table compression is enabled (ENABLED) or not (DISABLED) **Note:** Enabling default table compression indicates that all tables in the tablespace will be created with table compression enabled unless otherwise specified.
RETENTION	VARCHAR2(11)		Undo tablespace retention: • GUARANTEE - Tablespace is an undo tablespace with RETENTION specified as GUARANTEE A RETENTION value of GUARANTEE indicates that unexpired undo in all undo segments in the undo tablespace should be retained even if it means that forward going operations that need to generate undo in those segments fail. • NOGUARANTEE - Tablespace is an undo tablespace with RETENTION specified as NOGUARANTEE • NOT APPLY - Tablespace is not an undo tablespace
BIGFILE	VARCHAR2(3)		Indicates whether the tablespace is a bigfile tablespace (YES) or a smallfile tablespace (NO)
PREDICATE_EVALUATION	VARCHAR2(7)		Indicates whether predicates are evaluated by host (HOST) or by storage (STORAGE)
ENCRYPTED	VARCHAR2(3)		Indicates whether the tablespace is encrypted (YES) or not (NO)
COMPRESS_FOR	VARCHAR2(30)		Default compression for what kind of operations: • BASIC • ADVANCED • QUERY LOW • QUERY HIGH • ARCHIVE LOW • ARCHIVE HIGH • NULL The QUERY LOW, QUERY HIGH, ARCHIVE LOW, and ARCHIVE HIGH values are associated with Hybrid Columnar Compression, a feature of the Enterprise Edition of Oracle Database that is dependent on the underlying storage system. See *Oracle Database Concepts* for more information.
DEF_INMEMORY	VARCHAR2(8)		Indicates whether the In-Memory Column Store (IM column store) is by default enabled (ENABLED) or disabled (DISABLED) for tables in this tablespace

Column	Datatype	NULL	Description
DEF_INMEMORY_PRIORITY	VARCHAR2(8)		Indicates the default priority for In-Memory Column Store (IM column store) population for this tablespace. Possible values: • LOW • MEDIUM • HIGH • CRITICAL • NONE • NULL
DEF_INMEMORY_DISTRIBUTE	VARCHAR2(15)		Indicates how the IM column store is distributed by default for this tablespace in an Oracle Real Application Clusters (Oracle RACE) environment: • AUTO • BY ROWID RANGE • BY PARTITION • BY SUBPARTITION
DEF_INMEMORY_COMPRESSION	VARCHAR2(17)		Indicates the default compression level for the IM column store for this tablespace: • NO MEMCOMPRESS • FOR DML • FOR QUERY [LOW | HIGH] • FOR CAPACITY [LOW | HIGH] • NULL
DEF_INMEMORY_DUPLICATE	VARCHAR2(13)		Indicates the duplicate setting for the IM column store in an Oracle RAC environment: • NO DUPLICATE • DUPLICATE • DUPLICATE ALL
SHARED	VARCHAR2(12)		Tablespace type: • SHARED: For shared tablespace • LOCAL_ON_LEAF: For local temporary tablespace for leaf (read-only) instances • LOCAL_ON_ALL: For local temporary tablespace for all instance types
DEF_INDEX_COMPRESSION	VARCHAR2(8)		Indicates whether default index compression is enabled (ENABLED) or not (DISABLED) **Note:** Enabling default index compression indicates that all indexes in the tablespace will be created with index compression enabled unless otherwise specified.
INDEX_COMPRESS_FOR	VARCHAR2(13)		Valid values are: • ADVANCED LOW • ADVANCED HIGH • NULL No other values are allowed.
DEF_CELLMEMORY	VARCHAR2(14)		This specifies the default value for the CELLMEMORY attribute that tables created in the tablespace will inherit unless the behavior is overridden explicitly This column is intended for use with Oracle Exadata.

Column	Datatype	NULL	Description
DEF_INMEMORY_SERVICE	VARCHAR2(12)		Indicates how the IM column store is populated on various instances by default for this tablespace. The possible values are: • DEFAULT: Data is populated on all instances specified with the PARALLEL_INSTANCE_GROUP initialization parameter. If that parameter is not set, then the data is populated on all instances. This is the default. • NONE: Data is not populated on any instance. • ALL: Data is populated on all instances, regardless of the value of the PARALLEL_INSTANCE_GROUP initialization parameter. • USER_DEFINED: Data is populated only on the instances on which the user-specified service is active. The service name corresponding to this is stored in the DEF_INMEMORY_SERVICE_NAME column.
DEF_INMEMORY_SERVICE_NAME	VARCHAR2(1000)		Indicates the service name for the service on which the IM column store should be populated by default for this tablespace. This column has a value only when the corresponding DEF_INMEMORY_SERVICE is USER_DEFINED. In all other cases, this column is null.
LOST_WRITE_PROTECT	VARCHAR2(7)		The lost write protection setting for the tablespace. Possible values: • ENABLED: Indicates that lost write data is being collected • OFF: Indicates that lost write data is not being collected • SUSPEND: Indicates that lost write data is not currently being collected, but it can be enabled at a later date. The lost write data collected when the file was ENABLED remains in the lost write database, but it is not being checked or updated. If lost write protection is enabled for a tablespace, it is enabled for all data files for that tablespace, including data files added later. If lost write protection is enabled for a single data file, it does not have to be enabled for another data file in the same tablespace. You can check the lost write protection status for a data file by querying the LOST_WRITE_PROTECT column in the DBA_DATA_FILES view.
CHUNK_TABLESPACE	VARCHAR2(1)		Indicates whether this is a chunk tablespace (Y) or not (N)

See Also:

- "USER_TABLESPACES"
- "PARALLEL_INSTANCE_GROUP"
- "DBA_DATA_FILES"

7.54 DBA_TEMP_FILES

DBA_TEMP_FILES describes all temporary files (tempfiles) in the database.

Column	Datatype	NULL	Description
FILE_NAME	VARCHAR2(513)		Name of the database temp file
FILE_ID	NUMBER		File identifier number of the database temp file
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of the tablespace to which the file belongs
BYTES	NUMBER		Size of the file (in bytes)
BLOCKS	NUMBER		Size of the file (in Oracle blocks)
STATUS	VARCHAR2(7)		File status: • OFFLINE • ONLINE • UNKNOWN
RELATIVE_FNO	NUMBER		Tablespace-relative file number
AUTOEXTENSIBLE	VARCHAR2(3)		Indicates whether the file is autoextensible (YES) or not (NO)
MAXBYTES	NUMBER		maximum size of the file (in bytes)
MAXBLOCKS	NUMBER		Maximum size of the file (in Oracle blocks)
INCREMENT_BY	NUMBER		Default increment for autoextension (in Oracle blocks)
USER_BYTES	NUMBER		Size of the useful portion of the file (in bytes)
USER_BLOCKS	NUMBER		Size of the useful portion of the file (in Oracle blocks)
SHARED	VARCHAR2(12)		Type of tablespace this file belongs to: • SHARED: For shared tablespace • LOCAL_FOR_RIM: Local temporary tablespace for RIM (read-only) instances • LOCAL_FOR_ALL: Local temporary tablespace for all instance types
INST_ID	NUMBER		Instance ID of the instance to which the temp file belongs. This column has a NULL value for temp files that belong to shared tablespaces.

7.55 DBA_TEMP_FREE_SPACE

DBA_TEMP_FREE_SPACE displays temporary space usage information at tablespace level.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of the tablespace
TABLESPACE_SIZE	NUMBER		Total size of the tablespace, in bytes
ALLOCATED_SPACE	NUMBER		Total allocated space, in bytes, including space that is currently allocated and used and space that is currently allocated and available for reuse
FREE_SPACE	NUMBER		Total free space available, in bytes, including space that is currently allocated and available for reuse and space that is currently unallocated
SHARED	VARCHAR2(12)		Type of tablespace this file belongs to: • SHARED: For shared tablespace • LOCAL_FOR_RIM: Local temporary tablespace for RIM (read-only) instances • LOCAL_FOR_ALL: Local temporary tablespace for all instance types
INST_ID	NUMBER		Instance ID of the instance to which the tempfile belongs

7.56 DBA_THRESHOLDS

DBA_THRESHOLDS describes all thresholds.

Column	Datatype	NULL	Description
METRICS_NAME	VARCHAR2(64)		Metrics name
WARNING_OPERATOR	VARCHAR2(12)		Relational operator for warning thresholds: • GT • EQ • LT • LE • GE • CONTAINS • NE • DO NOT CHECK • DO_NOT_CHECK
WARNING_VALUE	VARCHAR2(256)		Warning threshold value
CRITICAL_OPERATOR	VARCHAR2(12)		Relational operator for critical thresholds: • GT • EQ • LT • LE • GE • CONTAINS • NE • DO NOT CHECK • DO_NOT_CHECK
CRITICAL_VALUE	VARCHAR2(256)		Critical threshold value
OBSERVATION_PERIOD	NUMBER		Observation period length (in minutes)

Column	Datatype	NULL	Description
CONSECUTIVE_OCCURRENCES	NUMBER		Number of occurrences before an alert is issued
INSTANCE_NAME	VARCHAR2(16)		Instance name; NULL for database-wide alerts
OBJECT_TYPE	VARCHAR2(64)		Object type: • SYSTEM • SERVICE • EVENT_CLASS • TABLESPACE • FILE
OBJECT_NAME	VARCHAR2(513)		Name of the object for which the threshold is set
STATUS	VARCHAR2(7)		Indicates whether the threshold is applicable on a valid object (VALID) or not (INVALID) Thresholds for non-tablespace metrics can only be set in ROOT and apply to a CDB as a whole. Any pre-existing non-tablespace thresholds that may exist in a PDB have a status of INVALID in the DBA_THRESHOLDS view. You can remove these threshold settings using the DBMS_SERVER_ALERT.SET_THRESHOLD API. See *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SERVER_ALERT.SET_THRESHOLD API.

7.57 DBA_TRANSFORMATIONS

DBA_TRANSFORMATIONS displays information about all transformations in the database. These transformations can be specified with Advanced Queuing operations such as enqueue, dequeue, and subscribe to automatically integrate transformations in AQ messaging. Its columns are the same as those in ALL_TRANSFORMATIONS.

> **See Also:**
>
> "ALL_TRANSFORMATIONS"

7.58 DBA_TRIGGER_COLS

DBA_TRIGGER_COLS describes the use of columns in all triggers in the database. Its columns are the same as those in ALL_TRIGGER_COLS.

> **See Also:**
>
> "ALL_TRIGGER_COLS"

7.59 DBA_TRIGGER_ORDERING

DBA_TRIGGER_ORDERING describes all triggers in the database that have FOLLOWS or PRECEDES ordering. Its columns are the same as those in ALL_TRIGGER_ORDERING.

> **See Also:**
>
> "ALL_TRIGGER_ORDERING"

7.60 DBA_TRIGGERS

DBA_TRIGGERS describes all triggers in the database. Its columns are the same as those in ALL_TRIGGERS.

> **See Also:**
>
> "ALL_TRIGGERS"

7.61 DBA_TRIGGERS_AE

DBA_TRIGGERS_AE describes all triggers (across all editions) in the database. Its columns are the same as those in ALL_TRIGGERS_AE.

> **See Also:**
>
> "ALL_TRIGGERS_AE"

7.62 DBA_TS_QUOTAS

DBA_TS_QUOTAS describes tablespace quotas for all users.

Related View

USER_TS_QUOTAS describes tablespace quotas for the current user. This view does not display the USERNAME column.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Tablespace name
USERNAME	VARCHAR2(128)	NOT NULL	User with resource rights on the tablespace
BYTES	NUMBER		Number of bytes charged to the user
MAX_BYTES	NUMBER		User's quota in bytes, or -1 if no limit

Column	Datatype	NULL	Description
BLOCKS	NUMBER		Number of Oracle blocks charged to the user
MAX_BLOCKS	NUMBER		User's quota in Oracle blocks, or -1 if no limit
DROPPED	VARCHAR2(3)		Whether the tablespace has been dropped

> **See Also:**
>
> "USER_TS_QUOTAS"

7.63 DBA_TSDP_IMPORT_ERRORS

DBA_TSDP_IMPORT_ERRORS shows information about the errors encountered during import of the Transparent Sensitive Data Protection discovery result.

This error information corresponds to the last import of the discovery result done using the DBMS_TSDP_MANAGE.IMPORT_DISCOVERY_RESULT API.

Column	Datatype	NULL	Description
ERROR_CODE	NUMBER	NOT NULL	The ORA error code of the error encountered
SCHEMA_NAME	VARCHAR2(128)		The schema corresponding to the error
TABLE_NAME	VARCHAR2(128)		The table corresponding to the error
COLUMN_NAME	VARCHAR2(128)		The column corresponding to the error
SENSITIVE_TYPE	VARCHAR2(128)		The sensitive type corresponding to the error

> **See Also:**
>
> - *Oracle Database Security Guide* for more information about using Transparent Sensitive Data Protection
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_TSDP_MANAGE.IMPORT_DISCOVERY_RESULT procedure

7.64 DBA_TSDP_POLICY_CONDITION

DBA_TSDP_POLICY_CONDITION describes the Transparent Sensitive Data Protection policy and condition mapping. It also lists the property-value pairs for the condition.

Column	Datatype	NULL	Description
POLICY_NAME	VARCHAR2(128)		The name of the Transparent Sensitive Data Protection policy

Column	Datatype	NULL	Description
SUB_POLICY	NUMBER	NOT NULL	The sub policy of the Transparent Sensitive Data Protection policy
PROPERTY	VARCHAR2(11)		The condition property. Possible values: • DATATYPE • LENGTH • SCHEMA_NAME • TABLE_NAME
VALUE	VARCHAR2(128)		The value of the condition property

See Also:

Oracle Database Security Guide for more information about using Transparent Sensitive Data Protection

7.65 DBA_TSDP_POLICY_FEATURE

DBA_TSDP_POLICY_FEATURE shows the Transparent Sensitive Data Protection policy security feature mapping for all the TSDP policies in the database.

At this time, only Oracle Data Redaction is supported.

Column	Datatype	NULL	Description
POLICY_NAME	VARCHAR2(128)		The name of the Transparent Sensitive Data Protection policy
SECURITY_FEATURE	VARCHAR2(12)		The Oracle security feature with which the Transparent Sensitive Data Protection policy is associated

See Also:

Oracle Database Security Guide for more information about using Transparent Sensitive Data Protection

7.66 DBA_TSDP_POLICY_PARAMETER

DBA_TSDP_POLICY_PARAMETER shows the parameter-value pairs for the condition of the Transparent Sensitive Data Protection policy.

Column	Datatype	NULL	Description
POLICY_NAME	VARCHAR2(128)		The name of the Transparent Sensitive Data Protection policy

Column	Datatype	NULL	Description
SUB_POLICY	NUMBER	NOT NULL	The sub policy of the Transparent Sensitive Data Protection policy
PARAMETER	VARCHAR2(128)		The parameter for the Transparent Sensitive Data Protection sub policy
VALUE	VARCHAR2(4000)		The value of the parameter
DEFAULT_OPTION	VARCHAR2(5)		Indicates whether this is the default option for the policy: • TRUE: This is the default option for the policy • FALSE: This is not the default option for the policy

See Also:

Oracle Database Security Guide for more information about using Transparent Sensitive Data Protection

7.67 DBA_TSDP_POLICY_PROTECTION

DBA_TSDP_POLICY_PROTECTION shows the list of columns that have been protected through Transparent Sensitive Data Protection.

Column	Datatype	NULL	Description
SCHEMA_NAME	VARCHAR2(128)	NOT NULL	The schema containing the sensitive data
TABLE_NAME	VARCHAR2(128)	NOT NULL	The table containing the sensitive column
COLUMN_NAME	VARCHAR2(128)	NOT NULL	The name of the sensitive column
TSDP_POLICY	VARCHAR2(128)		The TSDP policy name based on which the column protection was enabled
SECURITY_FEATURE	VARCHAR2(12)		The security feature enabled on the sensitive column
SECURITY_FEATURE_POLICY	VARCHAR2(128)	NOT NULL	Name of the underlying Oracle security feature policy
SUBPOLICY#	NUMBER	NOT NULL	The subpolicy of the Transparent Sensitive Data Protection policy based on which protection has been enabled

See Also:

Oracle Database Security Guide for more information about using Transparent Sensitive Data Protection

7.68 DBA_TSDP_POLICY_TYPE

DBA_TSDP_POLICY_TYPE shows the Transparent Sensitive Data Protection policy to sensitive column type mapping.

Column	Datatype	NULL	Description
POLICY_NAME	VARCHAR2(128)		The Transparent Sensitive Data Protection policy name
SENSITIVE_TYPE	VARCHAR2(128)		The sensitive column type name

> **See Also:**
>
> *Oracle Database Security Guide* for more information about using Transparent Sensitive Data Protection

7.69 DBA_TSM_DESTINATION

DBA_TSM_DESTINATION lists transparent session migration (TSM) destination session statistics.

Column	Datatype	NULL	Description
SOURCE_DATABASE_NAME	VARCHAR2(4000)		Database name of source session
DESTINATION_DATABASE_NAME	VARCHAR2(4000)		Database name of destination session
DESTINATION_INSTANCE_NAME	VARCHAR2(4000)		Instance name of destination session
DESTINATION_INSTANCE_ID	VARCHAR2(4000)		Instance ID of destination session
DESTINATION_INST_START_TIME	TIMESTAMP(6) WITH TIME ZONE		Instance start time of destination session
SEQUENCE#	NUMBER		Migration sequence number
DESTINATION_SID	NUMBER		Session ID of destination session
DESTINATION_SERIAL#	NUMBER		Session serial number of destination session
DESTINATION_START_TIME	TIMESTAMP(6) WITH TIME ZONE		Start time for migration on destination session
DESTINATION_END_TIME	TIMESTAMP(6) WITH TIME ZONE		End time for migration on destination session
DESTINATION_USER_NAME	VARCHAR2(128)	NOT NULL	User associated with the destination session
DESTINATION_SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Schema associated with the destination session
DESTINATION_STATE	VARCHAR2(24)		Migration state of destination session

7.70 DBA_TSM_SOURCE

DBA_TSM_SOURCE lists transparent session migration (TSM) source session statistics.

Column	Datatype	NULL	Description
SOURCE_DATABASE_NAME	VARCHAR2(4000)		Database name of source session
SOURCE_INSTANCE_NAME	VARCHAR2(4000)		Instance name of source session
SOURCE_INSTANCE_ID	VARCHAR2(4000)		Instance ID of source session
SOURCE_INSTANCE_START_TIME	TIMESTAMP(6) WITH TIME ZONE		Instance start time of source session
SEQUENCE#	NUMBER		Migration sequence number
SOURCE_SID	NUMBER		Session ID of source session
SOURCE_SERIAL#	NUMBER		Source serial number of source session
SOURCE_STATE	VARCHAR2(24)		Migration state of source session
CONNECT_STRING	VARCHAR2(4000)		Connect string specified for migration
SOURCE_START_TIME	TIMESTAMP(6) WITH TIME ZONE		Start time for migration on source session
COST	NUMBER		Estimate of migration cost
FAILURE_REASON	VARCHAR2(34)		Reason for migration failure, if any
SOURCE_END_TIME	TIMESTAMP(6) WITH TIME ZONE		End time for migration on source session
ROUNDTRIPS	NUMBER		Number of client/server round trips during migration
SOURCE_USER_NAME	VARCHAR2(128)	NOT NULL	User associated with the source session
SOURCE_SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Schema associated with the source session
DESTINATION_DATABASE_NAME	VARCHAR2(4000)		Database name of the destination session

7.71 DBA_TSTZ_TAB_COLS

DBA_TSTZ_TAB_COLS displays information about the columns of all tables in the database, which have columns defined on TIMESTAMP WITH TIME ZONE data types or object types containing attributes of TIMESTAMP WITH TIME ZONE data types.

Its columns (except for COLUMN_NAME, NESTED, VIRTUAL_COLUMN, SCALAR_COLUMN, and UNUSED_COLUMN) are the same as those in ALL_TSTZ_TAB_COLS.

See Also:

"ALL_TSTZ_TAB_COLS"

7.72 DBA_TSTZ_TABLES

DBA_TSTZ_TABLES displays information about all tables in the database, which have columns defined on TIMESTAMP WITH TIME ZONE data types or object types containing attributes of TIMESTAMP WITH TIME ZONE data types.

Its columns are the same as those in ALL_TSTZ_TABLES.

> **See Also:**
>
> "ALL_TSTZ_TABLES"

7.73 DBA_TUNE_MVIEW

DBA_TUNE_MVIEW displays the result of executing the DBMS_ADVISOR.TUNE_MVIEW procedure.

Related View

USER_TUNE_MVIEW displays the result of executing the DBMS_ADVISOR.TUNE_MVIEW procedure. This view does not display the OWNER column.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the task
TASK_NAME	VARCHAR2(128)		Name of the task
ACTION_ID	NUMBER	NOT NULL	Identifier of the action
SCRIPT_TYPE	VARCHAR2(14)		Type of the script: • IMPLEMENTATION • UNDO
STATEMENT	CLOB		Action statement

> **See Also:**
>
> - "USER_TUNE_MVIEW"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_ADVISOR.TUNE_MVIEW procedure

7.74 DBA_TXEVENTQ_MIGRATION_STATUS

DBA_TXEVENTQ_MIGRATION_STATUS provides information about all migrations from AQ classic queues to Transactional Event Queues (TxEventQs).

Its columns (except for SUFFIX) are the same as those in ALL_TXEVENTQ_MIGRATION_STATUS.

Column	Datatype	NULL	Description
SOURCE_SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Source schema name
SOURCE_QUEUE_NAME	VARCHAR2(128)	NOT NULL	Source AQ classic queue name
SOURCE_QUEUE_TABLE	VARCHAR2(128)		Source AQ classic queue table name
TARGET_SCHEMA_NAME	VARCHAR2(128)	NOT NULL	Target schema name
TARGET_QUEUE_NAME	VARCHAR2(128)	NOT NULL	Target TxEventQ name
EVENT_STATUS	NUMBER		Migration event status
EVENT	VARCHAR2(128)		Migration event
EVENT_TIMESTAMP	TIMESTAMP (6) WITH TIME ZONE		Date and time at which the migration event occurred
EVENT_ERROR_COMMENTS	VARCHAR2(1024)		Migration event error comments, if any
SUFFIX	VARCHAR2(2)		Temporary TxEventQ name suffix, if any This suffix is supplied by the user to avoid name conflicts during the migration.

Note:

This view is available starting with Oracle Database 23ai.

See Also:

"ALL_TXEVENTQ_MIGRATION_STATUS"

7.75 DBA_TYPE_ATTRS

DBA_TYPE_ATTRS describes the attributes of all object types in the database. Its columns (except for CHAR_USED) are the same as those in ALL_TYPE_ATTRS.

See Also:

"ALL_TYPE_ATTRS"

7.76 DBA_TYPE_METHODS

DBA_TYPE_METHODS describes the methods of all object types in the database. Its columns are the same as those in ALL_TYPE_METHODS.

> **See Also:**
>
> "ALL_TYPE_METHODS"

7.77 DBA_TYPE_VERSIONS

DBA_TYPE_VERSIONS describes the versions of all object types in the database. Its columns are the same as those in ALL_TYPE_VERSIONS.

> **See Also:**
>
> "ALL_TYPE_VERSIONS"

7.78 DBA_TYPES

DBA_TYPES describes all object types in the database. Its columns are the same as those in ALL_TYPES.

> **See Also:**
>
> "ALL_TYPES"

7.79 DBA_UMF_LINK

DBA_UMF_LINK displays information about the registered database links in the Remote Management Framework (RMF).

This view returns no rows if you are querying on an RMF source node. It returns all the registered database links in the topology if you are querying on a target node.

Column	Datatype	NULL	Description
TOPOLOGY_NAME	VARCHAR2(128)	NOT NULL	Topology name for the link
FROM_NODE_ID	NUMBER	NOT NULL	Node ID of the local node
TO_NODE_ID	NUMBER	NOT NULL	Node ID of the remote node
LINK_NAME	VARCHAR2(128)	NOT NULL	Fully qualified database link name

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for information about configuring the Remote Management Framework (RMF) architecture

7.80 DBA_UMF_REGISTRATION

`DBA_UMF_REGISTRATION` displays information about the registered nodes in the Remote Management Framework (RMF).

This view returns no rows if you are querying on an RMF source node. It returns all the registered nodes in the topology if you are querying on a target node.

Column	Datatype	NULL	Description
`TOPOLOGY_NAME`	`VARCHAR2(128)`	`NOT NULL`	Topology name for the node
`NODE_NAME`	`VARCHAR2(128)`	`NOT NULL`	Unique node name in the topology
`NODE_ID`	`NUMBER`	`NOT NULL`	Unique node ID in the topology
`NODE_TYPE`	`NUMBER`	`NOT NULL`	Node type. Possible value: • `0`: RDBMS node
`AS_SOURCE`	`VARCHAR2(5)`		Indicates whether the node is a source node. Possible values: • `TRUE`: The node is a source node, and it can provide remote services • `FALSE`: The node is not a source node, and it cannot provide remote services
`AS_CANDIDATE_TARGET`	`VARCHAR2(5)`		Node is a candidate target. Possible values: • `TRUE`: Node can be promoted to target role • `FALSE`: Node cannot be promoted to target role
`STATE`	`VARCHAR2(20)`		Current state of the node. Possible values: • `OK`: Node is registered • `REGISTRATION_PENDING`: Node registration has started, but has not been completed • `SYNC_FAILED`: Unable to synchronize the topology with the node

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for information about configuring the Remote Management Framework (RMF) architecture

7.81 DBA_UMF_SERVICE

DBA_UMF_SERVICE displays information about the registered services in the Remote Management Framework (RMF).

This view returns no rows if you are querying on an RMF source node. It returns all the registered services in the topology if you are querying on a target node

Column	Datatype	NULL	Description
TOPOLOGY_NAME	VARCHAR2(128)	NOT NULL	Topology name for the service
NODE_ID	NUMBER	NOT NULL	Node ID of the node providing the service
SERVICE_ID	VARCHAR2(7)		Service Identifier. Possible values: • 1: Automatic Workload Repository • 2: SQL Tuning

See Also:

Oracle Database Performance Tuning Guide for information about configuring the Remote Management Framework (RMF) architecture

7.82 DBA_UMF_TOPOLOGY

DBA_UMF_TOPOLOGY displays information about the registered topologies in the Remote Management Framework (RMF).

This view returns no rows if you are querying on an RMF source node. It returns one row per registered topology if you are querying on a target node.

Column	Datatype	NULL	Description
TOPOLOGY_NAME	VARCHAR2(128)	NOT NULL	Unique topology name
TARGET_ID	NUMBER		Node ID of the target node
TOPOLOGY_VERSION	NUMBER	NOT NULL	Topology version number
TOPOLOGY_STATE	VARCHAR2(8)		Possible values: • ACTIVE: Topology can be used for RMF operations • INACTIVE: Topology cannot be used for RMF operations

See Also:

Oracle Database Performance Tuning Guide for information about configuring the Remote Management Framework (RMF) architecture

7.83 DBA_UNDO_EXTENTS

DBA_UNDO_EXTENTS describes the extents comprising the segments in all undo tablespaces in the database.

> **Note:**
>
> The status of the undo space distribution reported by DBA_UNDO_EXTENTS is correct for the undo tablespace that is active on the instance on which DBA_UNDO_EXTENTS is queried. However, due to the use of in-memory information that is different on each instance, there can be a discrepancy in the status of the undo space distribution of undo tablespaces active on other instances when queried from one instance. This does not affect undo functionality and is only a reporting discrepancy for other instances' undo tablespace space distribution status. As a best practice, query the space distribution for an undo tablespace from the instance on which it is active.

Column	Datatype	NULL	Description
OWNER	CHAR(3)		Owner of the undo tablespace
SEGMENT_NAME	VARCHAR2(128)	NOT NULL	Name of the undo segment
TABLESPACE_NAME	VARCHAR2(128)	NOT NULL	Name of the undo tablespace
EXTENT_ID	NUMBER		ID of the extent
FILE_ID	NUMBER	NOT NULL	Absolute file number of the data file containing the extent
BLOCK_ID	NUMBER		Start block number of the extent
BYTES	NUMBER		Size of the extent (in bytes)
BLOCKS	NUMBER		Size of the extent (in blocks)
RELATIVE_FNO	NUMBER		Relative number of the file containing the segment header
COMMIT_JTIME	NUMBER		Commit time of the undo in the extent expressed as Julian time. This column is deprecated, but retained for backward compatibility reasons.
COMMIT_WTIME	VARCHAR2(20)		Commit time of the undo in the extent expressed as Wallclock time.This column is deprecated, but retained for backward compatibility reasons.
STATUS	VARCHAR2(9)		Transaction Status of the undo in the extent: • ACTIVE • EXPIRED • UNEXPIRED

7.84 DBA_UNUSED_COL_TABS

DBA_UNUSED_COL_TABS describes all tables in the database containing unused columns. Its columns are the same as those in ALL_UNUSED_COL_TABS.

> **See Also:**
>
> "ALL_UNUSED_COL_TABS"

7.85 DBA_UNUSED_GRANTS

DBA_UNUSED_GRANTS shows all the grants that are not used during the privilege capture.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)		Name of the privilege analysis policy
RUN_NAME	VARCHAR2(128)		Name of the run of the privilege analysis policy
GRANTEE	VARCHAR2(128)		Name of the user who is granted with the privilege or role
ROLENAME	VARCHAR2(128)		Name of the role that is granted to the grantee
SYS_PRIV	VARCHAR2(40)		Name of the system privilege that is granted to the grantee
SCH_PRIV	VARCHAR2(40)		Name of the schema privilege that is granted to the grantee
OBJ_PRIV	VARCHAR2(40)		Name of the object privilege that is granted to the grantee
USER_PRIV	VARCHAR2(25)		Name of the user privilege that is granted to the grantee
OBJECT_OWNER	VARCHAR2(128)		Name of the owner of the object for which the object privilege is granted
OBJECT_NAME	VARCHAR2(128)		Name of the object for which the object privilege is granted
OBJECT_TYPE	VARCHAR2(23)		Type of the object for which the object privilege is granted
COLUMN_NAME	VARCHAR2(128)		Name of the column in the table for which the object privilege is granted
OPTION$	NUMBER		Whether the grant option of the privilege is granted

> **See Also:**
>
> *Oracle Database Security Guide* for more information about privilege analysis

7.86 DBA_UNUSED_OBJPRIVS

DBA_UNUSED_OBJPRIVS lists the object privileges (without privilege grant paths) that are not used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of the privilege analysis policy
USERNAME	VARCHAR2(128)		Name of the user whose privileges are reported
ROLENAME	VARCHAR2(128)		Name of the role whose unused privileges are reported (for ROLE type privilege analysis or ROLE AND CONTEXT privilege analysis)
OBJ_PRIV	VARCHAR2(40)		Unused object privilege
OBJECT_OWNER	VARCHAR2(128)		Object owner
OBJECT_NAME	VARCHAR2(128)		Name of the object that USERNAME has OBJ_PRIV on
OBJECT_TYPE	VARCHAR2(23)		Type of the object USERNAME has OBJ_PRIV on
COLUMN_NAME	VARCHAR2(128)		Name of the column that USERNAME has OBJ_PRIV on
GRANT_OPTION	NUMBER		Indicates whether the privilege is granted with the GRANT option: • 0 - Indicates that the privilege is granted without the GRANT option • 1 - Indicates that the privilege is granted with the GRANT option
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- "DBA_UNUSED_OBJPRIVS_PATH" for privilege grant path information for unused object privileges
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.87 DBA_UNUSED_OBJPRIVS_PATH

DBA_UNUSED_OBJPRIVS_PATH lists the object privileges that are not used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of the privilege analysis policy
USERNAME	VARCHAR2(128)		Name of the user whose privileges are reported
ROLENAME	VARCHAR2(128)		Name of the role whose unused privileges are reported (for ROLE type privilege analysis or ROLE AND CONTEXT privilege analysis)
OBJ_PRIV	VARCHAR2(40)		Unused object privilege
OBJECT_OWNER	VARCHAR2(128)		Object owner
OBJECT_NAME	VARCHAR2(128)		Name of the object that USERNAME has OBJ_PRIV on
OBJECT_TYPE	VARCHAR2(23)		Type of the object that USERNAME has OBJ_PRIV on
COLUMN_NAME	VARCHAR2(128)		Name of the column that USERNAME has OBJ_PRIV on
GRANT_OPTION	NUMBER		Indicates whether the privilege is granted with the GRANT option: • 0 - Indicates that the privilege is granted without the GRANT option • 1 - Indicates that the privilege is granted with the GRANT option
PATH	GRANT_PATH		Object privilege grant paths
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- "DBA_USED_OBJPRIVS_PATH"
- "DBA_UNUSED_OBJPRIVS"
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.88 DBA_UNUSED_PRIVS

DBA_UNUSED_PRIVS lists the privileges that are not used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of the privilege analysis policy
USERNAME	VARCHAR2(128)		Name of the user whose unused privileges are reported
ROLENAME	VARCHAR2(128)		Name of the role whose unused privileges are reported (for ROLE type privilege analysis or ROLE AND CONTEXT privilege analysis)
SYS_PRIV	VARCHAR2(40)		Unused system privilege
SCH_PRIV	VARCHAR2(40)		Unused schema privilege
OBJ_PRIV	VARCHAR2(40)		Unused object privilege
USER_PRIV	VARCHAR2(25)		Unused user privilege
OBJECT_OWNER	VARCHAR2(128)		Object owner
OBJECT_NAME	VARCHAR2(128)		Name of the object that USERNAME has OBJ_PRIV or USER_PRIV on
OBJECT_TYPE	VARCHAR2(23)		Type of the object that OBJ_PRIV has accessed or USER if USER_PRIV was used
COLUMN_NAME	VARCHAR2(128)		Name of the column that OBJ_PRIV has access on
OPTION$	NUMBER		Indicates whether the privilege is granted with the GRANT option or the ADMIN option: • 0 - Indicates that the privilege is granted without the GRANT option or ADMIN option • 1 - Indicates that the privilege is granted with the GRANT option or ADMIN option
PATH	GRANT_PATH		Privilege grant paths
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- "DBA_USED_PRIVS"
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.89 DBA_UNUSED_SCHEMA_PRIVS

DBA_UNUSED_SCHEMA_PRIVS lists the schema privileges (without privilege grant paths) that are not used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy
USERNAME	VARCHAR2(128)		Name of the user whose privileges are reported
ROLENAME	VARCHAR2(128)		Name of the role whose unused privileges are reported (for ROLE type privilege analysis or ROLE AND CONTEXT privilege analysis)
SCH_PRIV	VARCHAR2(40)		Unused schema privilege
SCHEMA	VARCHAR2(128)		Schema on which the privilege was granted
ADMIN_OPTION	NUMBER		Indicates whether the privilege was granted with the ADMIN option: • 0 - Indicates that the privilege was granted without the ADMIN option • 1 - Indicates that the privilege was granted with the ADMIN option
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_UNUSED_SCHEMA_PRIVS_PATH" for privilege grant path information for unused schema privileges
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.90 DBA_UNUSED_SCHEMA_PRIVS_PATH

DBA_UNUSED_SCHEMA_PRIVS_PATH lists the schema privileges that are not used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy
USERNAME	VARCHAR2(128)		Name of the user whose privileges are reported
ROLENAME	VARCHAR2(128)		Name of the role whose unused privileges are reported (for ROLE type privilege analysis or ROLE AND CONTEXT privilege analysis)
SCH_PRIV	VARCHAR2(40)		Unused schema privilege
SCHEMA	VARCHAR2(128)		Schema on which the privilege was granted
ADMIN_OPTION	NUMBER		Indicates whether the privilege is granted with the ADMIN option: • 0 - Indicates that the privilege is granted without the ADMIN option • 1 - Indicates that the privilege is granted with the ADMIN option
PATH	GRANT_PATH		Schema privilege grant paths
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_USED_SCHEMA_PRIVS_PATH"
- "DBA_UNUSED_SCHEMA_PRIVS"
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.91 DBA_UNUSED_SYSPRIVS

DBA_UNUSED_SYSPRIVS lists the system privileges (without privilege grant paths) that are not used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy
USERNAME	VARCHAR2(128)		Name of the user whose privileges are reported
ROLENAME	VARCHAR2(128)		Name of the role whose unused privileges are reported (for ROLE type privilege analysis or ROLE AND CONTEXT privilege analysis)
SYS_PRIV	VARCHAR2(40)		Unused system privilege
ADMIN_OPTION	NUMBER		Indicates whether the privilege is granted with the ADMIN option: • 0 - Indicates that the privilege is granted without the ADMIN option • 1 - Indicates that the privilege is granted with the ADMIN option
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- "DBA_UNUSED_SYSPRIVS_PATH" for privilege grant path information for unused system privileges
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.92 DBA_UNUSED_SYSPRIVS_PATH

DBA_UNUSED_SYSPRIVS_PATH lists the system privileges that are not used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the user whose privileges are reported
ROLENAME	VARCHAR2(128)		Name of the role whose unused privileges are reported (for ROLE type privilege analysis or ROLE AND CONTEXT privilege analysis)
SYS_PRIV	VARCHAR2(40)		Unused system privilege
ADMIN_OPTION	NUMBER		Indicates whether the privilege is granted with the ADMIN option: • 0 - Indicates that the privilege is granted without the ADMIN option • 1 - Indicates that the privilege is granted with the ADMIN option
PATH	GRANT_PATH		System privilege grant paths
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- "DBA_USED_SYSPRIVS_PATH"
- "DBA_UNUSED_SYSPRIVS"
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.93 DBA_UNUSED_USERPRIVS

DBA_UNUSED_USERPRIVS lists the user privileges (without privilege grant paths) that are not used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy
USERNAME	VARCHAR2(128)		Name of the user whose privileges are reported
ROLENAME	VARCHAR2(128)		Name of the role whose unused privileges are reported (for ROLE type privilege analysis or ROLE AND CONTEXT privilege analysis)
USER_PRIV	VARCHAR2(25)		Unused user privilege

Column	Datatype	NULL	Description
ONUSER	VARCHAR2(128)		The user whose user privileges the grantee can exercise
GRANT_OPTION	NUMBER		Indicates whether the privilege is granted with the GRANT option: • 0 - Indicates that the privilege is granted without the GRANT option • 1 - Indicates that the privilege is granted with the GRANT option
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.94 DBA_UNUSED_USERPRIVS_PATH

DBA_UNUSED_USERPRIVS_PATH lists the user privileges that are not used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy
USERNAME	VARCHAR2(128)		Name of the user whose privileges are reported
ROLENAME	VARCHAR2(128)		Name of the role whose unused privileges are reported (for ROLE type privilege analysis or ROLE AND CONTEXT privilege analysis)
USER_PRIV	VARCHAR2(25)		Unused user privilege
ONUSER	VARCHAR2(128)		The user whose user privileges the grantee can exercise
GRANT_OPTION	NUMBER		Indicates whether the privilege is granted with the GRANT option: • 0 - Indicates that the privilege is granted without the GRANT option • 1 - Indicates that the privilege is granted with the GRANT option
PATH	GRANT_PATH		User privilege grant paths
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

> **See Also:**
>
> - *Oracle Database Security Guide* for more information about privilege analysis
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT` procedure

7.95 DBA_UPDATABLE_COLUMNS

`DBA_UPDATABLE_COLUMNS` describes all columns in a join view that can be updated by the database administrator, subject to appropriate privileges. Its columns are the same as those in `ALL_UPDATABLE_COLUMNS`.

> **See Also:**
>
> - "ALL_UPDATABLE_COLUMNS"
> - *Oracle Database Concepts* for information on updatable join views

7.96 DBA_USED_OBJPRIVS

`DBA_USED_OBJPRIVS` lists the object privileges (without privilege grant paths) that are used for the privilege analysis policies reported by the `DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT` procedure.

This view provides access to analyzed privilege records in `SYS` tables.

You must have the `CAPTURE_ADMIN` role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of the privilege analysis policy
SEQUENCE	NUMBER	NOT NULL	The sequence number of the privilege analysis run during which the privilege was reported
OS_USER	VARCHAR2(128)		Operating system login username
USERHOST	VARCHAR2(128)		Client host machine name
MODULE	VARCHAR2(64)		Module name
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user whose privilege was reported
USED_ROLE	VARCHAR2(128)		Used role
OBJ_PRIV	VARCHAR2(40)		Used object privilege
OBJECT_OWNER	VARCHAR2(128)		Object owner
OBJECT_NAME	VARCHAR2(128)		Name of the object that `OBJ_PRIV` was used to access

Column	Datatype	NULL	Description
OBJECT_TYPE	VARCHAR2(23)		Type of the object that OBJ_PRIV was used to access
COLUMN_NAME	VARCHAR2(128)		Name of the column that OBJ_PRIV was used to access
GRANT_OPTION	NUMBER		Indicates whether the GRANT option was used: • 0 - Indicates that the GRANT option was not used • 1 - Indicates that the GRANT option was used
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- "DBA_USED_OBJPRIVS_PATH" for privilege grant path information for used object privileges
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.97 DBA_USED_OBJPRIVS_PATH

DBA_USED_OBJPRIVS_PATH lists the object privileges that are used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of the privilege analysis policy
SEQUENCE	NUMBER	NOT NULL	The sequence number of the privilege analysis run during which the privilege was reported
OS_USER	VARCHAR2(128)		Operating system login username
USERHOST	VARCHAR2(128)		Client host machine name
MODULE	VARCHAR2(64)		Module name
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user whose privilege was reported
USED_ROLE	VARCHAR2(128)		Used role
OBJ_PRIV	VARCHAR2(40)		Used object privilege
OBJECT_OWNER	VARCHAR2(128)		Object owner
OBJECT_NAME	VARCHAR2(128)		Name of the object that OBJ_PRIV is used to access
OBJECT_TYPE	VARCHAR2(23)		Type of the object that OBJ_PRIV is used to access

Column	Datatype	NULL	Description
COLUMN_NAME	VARCHAR2(128)		Name of the column that OBJ_PRIV is used to access
GRANT_OPTION	NUMBER		Indicates whether the GRANT option was used: • 0 - Indicates that the GRANT option was not used • 1 - Indicates that the GRANT option was used
PATH	GRANT_PATH		Object privilege grant paths
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- "DBA_UNUSED_OBJPRIVS_PATH"
- "DBA_USED_OBJPRIVS"
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.98 DBA_USED_PRIVS

DBA_USED_PRIVS lists the privileges that are used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy
SEQUENCE	NUMBER	NOT NULL	The sequence number of the privilege analysis run during which the privilege was reported
OS_USER	VARCHAR2(128)		Operating system login username
USERHOST	VARCHAR2(128)		Client host machine name
MODULE	VARCHAR2(64)		Module name
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user whose privilege was reported
USED_ROLE	VARCHAR2(128)		Used role
SYS_PRIV	VARCHAR2(40)		Used system privilege
SCH_PRIV	VARCHAR2(40)		Used schema privilege
OBJ_PRIV	VARCHAR2(40)		Used object privilege
USER_PRIV	VARCHAR2(25)		Used user privilege

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)		Object owner
OBJECT_NAME	VARCHAR2(128)		Name of the object or user that OBJ_PRIV or USER_PRIV is used to access
OBJECT_TYPE	VARCHAR2(23)		Type of the object or user that OBJ_PRIV or USER_PRIV is used to access
COLUMN_NAME	VARCHAR2(128)		Name of the column that OBJ_PRIV is used to access
OPTION$	NUMBER		Indicates whether the GRANT option or the ADMIN option was used: • 0 - Indicates that the GRANT option or ADMIN option was not used • 1 - Indicates that the GRANT option or ADMIN option was used
PATH	GRANT_PATH		Used privilege grant paths
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- "DBA_UNUSED_PRIVS"
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.99 DBA_USED_PUBPRIVS

DBA_USED_PUBPRIVS lists the privileges that are used from the PUBLIC role for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy
SEQUENCE	NUMBER	NOT NULL	The sequence number of the privilege analysis run during which the privilege was reported
OS_USER	VARCHAR2(128)		Operating system login username
USERHOST	VARCHAR2(128)		Client host machine name
MODULE	VARCHAR2(64)		Module name
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user who used the privilege from the PUBLIC role
SYS_PRIV	VARCHAR2(40)		Used system privilege

Column	Datatype	NULL	Description
SCH_PRIV	VARCHAR2(40)		Used schema privilege
OBJ_PRIV	VARCHAR2(40)		Used object privilege
OBJECT_OWNER	VARCHAR2(128)		Object owner
OBJECT_NAME	VARCHAR2(128)		Name of the object that OBJ_PRIV is used to access
OBJECT_TYPE	VARCHAR2(23)		Type of the object that OBJ_PRIV is used to access
OPTION$	NUMBER		Indicates whether the GRANT option or the ADMIN option was used: • 0 - Indicates that the GRANT option or ADMIN option was not used • 1 - Indicates that the GRANT option or ADMIN option was used
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.100 DBA_USED_SCHEMA_PRIVS

DBA_USED_SCHEMA_PRIVS lists the schema privileges (without privilege grant paths) that are used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy
SEQUENCE	NUMBER	NOT NULL	The sequence number of the privilege analysis run during which the privilege was used
OS_USER	VARCHAR2(128)		Operating system login username
USERHOST	VARCHAR2(128)		Client host machine name
MODULE	VARCHAR2(64)		Module name
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user whose privilege was reported
USED_ROLE	VARCHAR2(128)		Used role
SCH_PRIV	VARCHAR2(40)		Used schema privilege

Column	Datatype	NULL	Description
SCHEMA	VARCHAR2(128)		Schema on which the privilege was granted
ADMIN_OPTION	NUMBER		Indicates whether the ADMIN option was used: • 0 - Indicates that the ADMIN option was not used • 1 - Indicates that the ADMIN option was used
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_USED_SCHEMA_PRIVS_PATH" for privilege grant path information for used schema privileges
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.101 DBA_USED_SCHEMA_PRIVS_PATH

DBA_USED_SCHEMA_PRIVS_PATH lists the schema privileges that are used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy
SEQUENCE	NUMBER	NOT NULL	The sequence number of the privilege analysis run during which the privilege was reported
OS_USER	VARCHAR2(128)		Operating system login username
USERHOST	VARCHAR2(128)		Client host machine name
MODULE	VARCHAR2(64)		Module name
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user whose privilege was reported
USED_ROLE	VARCHAR2(128)		Used role
SCH_PRIV	VARCHAR2(40)		Used schema privilege
SCHEMA	VARCHAR2(128)		Schema on which the privilege was granted

Column	Datatype	NULL	Description
ADMIN_OPTION	NUMBER		Indicates whether the ADMIN option was used: • 0 - Indicates that the ADMIN option was not used • 1 - Indicates that the ADMIN option was used
PATH	GRANT_PATH		Schema privilege grant paths
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_UNUSED_SCHEMA_PRIVS_PATH"
- "DBA_USED_SCHEMA_PRIVS"
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.102 DBA_USED_SYSPRIVS

DBA_USED_SYSPRIVS lists the system privileges (without privilege grant paths) that are used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy
SEQUENCE	NUMBER	NOT NULL	The sequence number of the privilege analysis run during which the privilege was used
OS_USER	VARCHAR2(128)		Operating system login username
USERHOST	VARCHAR2(128)		Client host machine name
MODULE	VARCHAR2(64)		Module name
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user whose privilege was reported
USED_ROLE	VARCHAR2(128)		Used role

Column	Datatype	NULL	Description
SYS_PRIV	VARCHAR2(40)		Used system privilege
ADMIN_OPTION	NUMBER		Indicates whether the ADMIN option was used: • 0 - Indicates that the ADMIN option was not used • 1 - Indicates that the ADMIN option was used
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- "DBA_USED_SYSPRIVS_PATH" for privilege grant path information for used system privileges
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure

7.103 DBA_USED_SYSPRIVS_PATH

DBA_USED_SYSPRIVS_PATH lists the system privileges that are used for the privilege analysis policies reported by the DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT procedure.

This view provides access to analyzed privilege records in SYS tables.

You must have the CAPTURE_ADMIN role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy
SEQUENCE	NUMBER	NOT NULL	The sequence number of the privilege analysis run during which the privilege was reported
OS_USER	VARCHAR2(128)		Operating system login username
USERHOST	VARCHAR2(128)		Client host machine name
MODULE	VARCHAR2(64)		Module name
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user whose privilege was reported
USED_ROLE	VARCHAR2(128)		Used role
SYS_PRIV	VARCHAR2(40)		Used system privilege
ADMIN_OPTION	NUMBER		Indicates whether the ADMIN option was used: • 0 - Indicates that the ADMIN option was not used • 1 - Indicates that the ADMIN option was used
PATH	GRANT_PATH		System privilege grant paths
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- "DBA_UNUSED_SYSPRIVS_PATH"
- "DBA_USED_SYSPRIVS"
- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT` procedure

7.104 DBA_USED_USERPRIVS

`DBA_USED_USERPRIVS` lists the user privileges (without privilege grant paths) that are used for the privilege analysis policies reported by the `DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT` procedure.

This view provides access to analyzed privilege records in `SYS` tables.

You must have the `CAPTURE_ADMIN` role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy
SEQUENCE	NUMBER	NOT NULL	The sequence number of the privilege analysis run during which the privilege was reported
OS_USER	VARCHAR2(128)		Operating system login username
USERHOST	VARCHAR2(128)		Client host machine name
MODULE	VARCHAR2(64)		Module name
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user whose privilege was reported
USED_ROLE	VARCHAR2(128)		Used role
USER_PRIV	VARCHAR2(25)		Used user privilege
ONUSER	VARCHAR2(128)		The user whose user privileges the grantee can exercise
GRANT_OPTION	NUMBER		Indicates whether the privilege is granted with the `GRANT` option: • `0` - Indicates that the privilege is granted without the `GRANT` option • `1` - Indicates that the privilege is granted with the `GRANT` option
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT` procedure

7.105 DBA_USED_USERPRIVS_PATH

`DBA_USED_USERPRIVS_PATH` lists the user privileges that are used for the privilege analysis policies reported by the `DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT` procedure.

This view provides access to analyzed privilege records in `SYS` tables.

You must have the `CAPTURE_ADMIN` role to access this view.

Column	Datatype	NULL	Description
CAPTURE	VARCHAR2(128)	NOT NULL	Name of a privilege analysis policy
SEQUENCE	NUMBER	NOT NULL	The sequence number of the privilege analysis run during which the privilege was reported
OS_USER	VARCHAR2(128)		Operating system login username
USERHOST	VARCHAR2(128)		Client host machine name
MODULE	VARCHAR2(64)		Module name
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user whose privilege was reported
USED_ROLE	VARCHAR2(128)		Used role
USER_PRIV	VARCHAR2(25)		Used user privilege
ONUSER	VARCHAR2(128)		The user whose user privileges the grantee can exercise
GRANT_OPTION	NUMBER		Indicates whether the privilege is granted with the `GRANT` option: • `0` - Indicates that the privilege is granted without the `GRANT` option • `1` - Indicates that the privilege is granted with the `GRANT` option
PATH	GRANT_PATH		User privilege grant paths
RUN_NAME	VARCHAR2(128)		The name of the run during which the privilege was reported

See Also:

- *Oracle Database Security Guide* for more information about privilege analysis
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_PRIVILEGE_CAPTURE.GENERATE_RESULT` procedure

7.106 DBA_USERS

DBA_USERS describes all users of the database.

Related View

USER_USERS describes the current user. This view does not display the PASSWORD, PROFILE, PASSWORD_VERSIONS, EDITIONS_ENABLED, AUTHENTICATION_TYPE, and LAST_LOGIN columns.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user
USER_ID	NUMBER	NOT NULL	ID number of the user
PASSWORD	VARCHAR2(4000)		This column is deprecated in favor of the AUTHENTICATION_TYPE column

Column	Datatype	NULL	Description
ACCOUNT_STATUS	VARCHAR2(32)	NOT NULL	Account status: • OPEN The account is open. • EXPIRED The password for the account is expired, either because the PASSWORD_LIFE_TIME limit was reached or because the password was expired by the ALTER USER ... PASSWORD EXPIRE command. The user can log in with the expired password, then change the password. • EXPIRED(GRACE) The password for the account is expired because the PASSWORD_LIFE_TIME limit was reached, but the password change grace period (PASSWORD_GRACE_TIME) has not yet elapsed. The user can log in with the expired password, but will receive an ORA-28002 warning as a reminder that the password must soon be changed. If the PASSWORD_GRACE_TIME elapses, the user can log in with the expired password, then change the password. • LOCKED The account is locked, either by the ALTER USER ... ACCOUNT LOCK command, or because the number of consecutive failed login attempts exceeded the FAILED_LOGIN_ATTEMPTS limit and the value of PASSWORD_LOCK_TIME is UNLIMITED. The account can be unlocked by the ALTER USER ... ACCOUNT UNLOCK command. • LOCKED(TIMED) The account is locked because the number of consecutive failed login attempts exceeded the FAILED_LOGIN_ATTEMPTS limit and the PASSWORD_LOCK_TIME has not yet elapsed. The account can be unlocked either by the ALTER USER ... ACCOUNT UNLOCK command or by waiting until the PASSWORD_LOCK_TIME has elapsed. • EXPIRED & LOCKED The password for the account is expired, as described for the EXPIRED account status, and the account is locked as described for the LOCKED account status. The account can first be unlocked as described for the LOCKED account status, then the password can be changed as described for the EXPIRED account status. • EXPIRED(GRACE) & LOCKED The password for the account is expired, as described for the EXPIRED(GRACE) account status, and the account is locked as described for the LOCKED account status. The

Column	Datatype	NULL	Description
			account can first be unlocked as described for the `LOCKED` account status, then the password can be changed as described for the `EXPIRED(GRACE)` account status. • `EXPIRED & LOCKED(TIMED)` The password for the account is expired, as described for the `EXPIRED` account status, and the account is locked as described for the `LOCKED(TIMED)` account status. The account can first be unlocked as described for the `LOCKED(TIMED)` account status, then the password can be changed as described for the `EXPIRED` account status. • `EXPIRED(GRACE) & LOCKED(TIMED)` The password for the account is expired, as described for the `EXPIRED(GRACE)` account status, and the account is locked as described for the `LOCKED(TIMED)` account status. The account can first be unlocked as described for the `LOCKED(TIMED)` account status, then the password can be changed as described for the `EXPIRED(GRACE)` account status. • `OPEN & IN ROLLOVER` The account is in the password rollover period. The user can log in with either the earlier password or the new password. However, at the time the user logs in, the server recalculates whether the account is still in its password rollover period. If the password rollover period has elapsed, then the login will succeed only if the new password was specified, and the account status will change to `OPEN`. • `EXPIRED & IN ROLLOVER` The account is in the password rollover period and the password is expired as described for the `EXPIRED` account status. The user can log in with either the earlier password or the new password. However, at the time the user logs in, the server recalculates whether the account is still in its password rollover period. If the password rollover period has elapsed, then the login will succeed only if the new password was specified, and the account status will change to `EXPIRED`. After logging in, the user will be prompted to change the password. • `LOCKED & IN ROLLOVER` The account is in the password rollover period and is also locked as described for the `LOCKED` account status. The account can be unlocked as described for the `LOCKED` account status, after which the user can log in as described for the `OPEN & IN ROLLOVER` account status.

Column	Datatype	NULL	Description
			• EXPIRED & LOCKED & IN ROLLOVER The account is in the password rollover period, its password is expired as described for the EXPIRED account status, and the account is locked as described for the LOCKED account status. The account can be unlocked as described for the LOCKED account status, after which the user can log in as described for the EXPIRED & IN ROLLOVER account status. • LOCKED(TIMED) & IN ROLLOVER The account is in the password rollover period and is also locked as described for the LOCKED(TIMED) account status. The account can be unlocked as described for the LOCKED(TIMED) account status, after which the user can log in with either the earlier password or the new password. However, at the time the user logs in, the server recalculates whether the account is still in its password rollover period. If the password rollover period has elapsed, then the login will succeed only if the new password was specified. • EXPIRED & LOCKED(TIMED) & IN ROL The account is in the password rollover period, its password is expired as described for the EXPIRED account status, and the account is locked as described for the LOCKED(TIMED) account status. The account can be unlocked as described for the LOCKED(TIMED) account status, after which the user can log in as described for the EXPIRED & IN ROLLOVER account status.
LOCK_DATE	DATE		Date the account was locked if account status was LOCKED
EXPIRY_DATE	DATE		Date of expiration of the account
DEFAULT_TABLESPACE	VARCHAR2(30)	NOT NULL	Default tablespace for data
TEMPORARY_TABLESPACE	VARCHAR2(30)	NOT NULL	Name of the default tablespace for temporary tables or the name of a tablespace group
LOCAL_TEMP_TABLESPACE	VARCHAR2(30)		Default local temporary tablespace for the user
CREATED	DATE	NOT NULL	User creation date
PROFILE	VARCHAR2(128)	NOT NULL	User resource profile name
INITIAL_RSRC_CONSUMER_GROUP	VARCHAR2(128)		Initial resource consumer group for the user
EXTERNAL_NAME	VARCHAR2(4000)		User external name. For centrally managed users, if the database user mapping is an exclusive mapping, then this will be the directory service DN for the user. If this database user is a shared schema, it will be the DN of a group.

Column	Datatype	NULL	Description
PASSWORD_VERSIONS	VARCHAR2(12)		Shows the list of versions of the password hashes (also known as "verifiers") existing for the account. The values for this column can include: • 11G: If a SHA-1 hash exists • 12C: If a de-optimized PBKDF2-based hash exists • HTTP: If an MD5 hash (for HTTP Digest authentication) exists For more information about the 12C verifier, see *Oracle Database Concepts*. Note that any combination of these verifiers can exist for any given account.
EDITIONS_ENABLED	VARCHAR2(1)		Indicates whether editions have been enabled for the corresponding user (Y) or not (N)
AUTHENTICATION_TYPE	VARCHAR2(8)		Indicates the authentication mechanism for the user: • NONE - The user has not been configured for an authentication method • EXTERNAL - CREATE USER *user1* IDENTIFIED EXTERNALLY; • GLOBAL - CREATE USER *user2* IDENTIFIED GLOBALLY; • PASSWORD - CREATE USER *user3* IDENTIFIED BY *password*;
PROXY_ONLY_CONNECT	VARCHAR2(1)		Indicates whether a user can connect directly (N) or whether the account can only be proxied (Y) by users who have proxy privileges for this account (that is, by users who have been granted the "connect through" privilege for this account). **Note:** Setting PROXY_ONLY_CONNECT for users is deprecated in this release, and may be desupported in a future release. Oracle recommends that you instead use schema-only accounts. For more information about schema-only accounts, see *Oracle Database Security Guide*.
COMMON	VARCHAR2(3)		Indicates whether a given user is common. Possible values • YES if a user is common • NO if a user is local (not common)
LAST_LOGIN	TIMESTAMP(9) WITH TIME ZONE		The time of the last user login This column is not populated when a user connects to the database with administrative privileges, that is, AS { SYSASM | SYSBACKUP | SYSDBA | SYSDG | SYSOPER | SYSRAC | SYSKM }.
ORACLE_MAINTAINED	VARCHAR2(1)		Denotes whether the user was created, and is maintained, by Oracle-supplied scripts (such as catalog.sql or catproc.sql). A user for which this column has the value Y must not be changed in any way except by running an Oracle-supplied script.

Column	Datatype	NULL	Description
INHERITED	VARCHAR2(3)		Indicates whether the user definition was inherited from another container (YES) or not (NO)
DEFAULT_COLLATION	VARCHAR2(100)		Default collation for the user's schema
IMPLICIT	VARCHAR2(3)		Indicates whether this user is a common user created by an implicit application (YES) or not (NO)
ALL_SHARD	VARCHAR2(3)		In a sharded database, the value in this column indicates whether the user was created with shard DDL enabled. The possible values are: • YES: The user was created with shard DDL enabled. The user exists on all shards and the shard catalog. • NO: The user was created without shard DDL enabled. The user exists only in the database in which the user was created. In a non-sharded database, the value in this column is always NO.
EXTERNAL_SHARD	VARCHAR2(3)		In a federated sharded database, the value in this column indicates whether the user is an external shard user (YES) or not (NO). In other types of databases, the value in this column is always NO.
PASSWORD_CHANGE_DATE	DATE		Date on which the user's password was last set This column is populated only when the value of the AUTHENTICATION_TYPE column is PASSWORD. Otherwise, this column is null.
MANDATORY_PROFILE_VIOLATION	VARCHAR2(3)		If the value in this column is YES, then the user account password violates the mandatory profile password complexity requirements and must be changed before the grace period expires. Otherwise, the value in this column is NO.
PROTECTED	VARCHAR2(3)		Indicates whether the user is a protected user (YES) or not (NO) A protected user can be managed only by another protected user or a common user.
READ_ONLY	VARCHAR2(3)		Indicates whether write privileges for the user are disabled (YES) or enabled (NO)
DICTIONARY_PROTECTED	VARCHAR2(3)		Indicates whether the user's schema is dictionary protected (YES) or not (NO) **See Also:** *Oracle Database Security Guide* for more information about dictionary-protected schemas

> **See Also:**
>
> - "USER_USERS"
> - *Oracle Globally Distributed Database Guide* for more information about sharded database management

7.107 DBA_USERS_WITH_DEFPWD

`DBA_USERS_WITH_DEFPWD` displays all users in the database that are still using their default passwords.

Column	Datatype	NULL	Description
`USERNAME`	`VARCHAR2(128)`	`NOT NULL`	Name of the user
`PRODUCT`	`VARCHAR2(4000)`		Name of the product the user belongs to

> **Note:**
>
> In a CDB, when `DBA_USERS_WITH_DEFPWD` is queried from a PDB, information about local users who are using their default passwords is displayed. To display information about common users, query `DBA_USERS_WITH_DEFPWD` from the root.

> **See Also:**
>
> *Oracle Multitenant Administrator's Guide* for an introduction to local and common users in a CDB

7.108 DBA_USTATS

`DBA_USTATS` describes the user-defined statistics collected on all tables and indexes in the database. Its columns are the same as those in `ALL_USTATS`.

> **See Also:**
>
> "ALL_USTATS"

7.109 DBA_VARRAYS

DBA_VARRAYS describes all varrays in the database. Its columns are the same as those in ALL_VARRAYS.

> **See Also:**
>
> "ALL_VARRAYS"

7.110 DBA_VIEWS

DBA_VIEWS describes all views in the database. Its columns are the same as those in ALL_VIEWS.

> **See Also:**
>
> "ALL_VIEWS"

7.111 DBA_VIEWS_AE

DBA_VIEWS_AE describes all views (across all editions) in the database. Its columns are the same as those in ALL_VIEWS_AE.

> **See Also:**
>
> "ALL_VIEWS_AE"

7.112 DBA_WAITERS

DBA_WAITERS shows all the sessions that are waiting for a lock. In an Oracle RAC environment, this only applies if the waiter is on the same instance.

Column	Datatype	NULL	Description
WAITING_SESSION	NUMBER		The waiting session
WAITING_CON_ID	NUMBER		The container ID (CON_ID) of the waiting session
HOLDING_SESSION	NUMBER		The holding session
HOLDING_CON_ID	NUMBER		The container ID (CON_ID) of the holding session.
LOCK_TYPE	VARCHAR2(26)		The lock type
MODE_HELD	VARCHAR2(40)		The mode held

Column	Datatype	NULL	Description
MODE_REQUESTED	VARCHAR2(40)		The mode requested
LOCK_ID1	NUMBER		Lock ID 1
LOCK_ID2	NUMBER		Lock ID 2

7.113 DBA_WALLET_ACES

DBA_WALLET_ACES describes access control entries defined in wallet access control lists.

Related View

USER_WALLET_ACES describes the status of access control entries for the current user to access wallets through PL/SQL network utility packages. This view does not display the ACE_ORDER, START_DATE, END_DATE, GRANT_TYPE, INVERTED_PRINCIPAL, PRINCIPAL, or PRINCIPAL_TYPE columns.

Column	Datatype	NULL	Description
WALLET_PATH	VARCHAR2(1000)	NOT NULL	Wallet path
ACE_ORDER	NUMBER	NOT NULL	Order number of the access control entry
START_DATE	TIMESTAMP(6)		Start date of the access control entry
END_DATE	TIMESTAMP(6)		End date of the access control entry
GRANT_TYPE	VARCHAR2(5)		Indicates whether the access control entry grants or denies the privilege
INVERTED_PRINCIPAL	VARCHAR2(3)		Indicates whether the principal is inverted or not
PRINCIPAL	VARCHAR2(128)		Principal the privilege is applied to
PRINCIPAL_TYPE	VARCHAR2(16)		Type of the principal
PRIVILEGE	VARCHAR2(128)		Privilege

See Also:

"USER_WALLET_ACES"

7.114 DBA_WALLET_ACLS

DBA_WALLET_ACLS displays the access control lists assigned to restrict access to wallets through PL/SQL network utility packages.

Column	Datatype	NULL	Description
WALLET_PATH	VARCHAR2(1000)	NOT NULL	Wallet path
ACL	VARCHAR2(4000)		Path of the access control list
ACLID	RAW(8)		Object ID of the access control list

Column	Datatype	NULL	Description
ACL_OWNER	VARCHAR2(128)		Owner of the access control list

7.115 DBA_WARNING_SETTINGS

DBA_WARNING_SETTINGS displays information about the warning parameter settings for all objects in the database. Its columns are the same as those in ALL_WARNING_SETTINGS.

> **See Also:**
>
> "ALL_WARNING_SETTINGS"

7.116 DBA_WI_CAPTURE_FILES

Each row in DBA_WI_CAPTURE_FILES represents a capture file that belongs to the workload analyzed in the current Workload Intelligence job.

Column	Datatype	NULL	Description
JOB_ID	NUMBER	NOT NULL	The identifier of the job in the workload to which the given capture file belongs
FILE_ID	NUMBER	NOT NULL	The identifier of the current capture file
FILE_PATH	VARCHAR2(4000)	NOT NULL	The path of the current capture file

7.117 DBA_WI_JOBS

Each row in DBA_WI_JOBS describes a Workload Intelligence job, that is, a task that applies the algorithms of Workload Intelligence on a given capture directory.

Column	Datatype	NULL	Description
JOB_ID	NUMBER	NOT NULL	The job identifier
JOB_NAME	VARCHAR2(128)	NOT NULL	A name that uniquely identifies the given job
CAPTURE_DIRECTORY	VARCHAR2(4000)	NOT NULL	Path to the capture directory on which the given job has been applied
MODEL_ORDER	NUMBER		The order of the markov model that describes the workload associated with the current job. If NULL, the corresponding order has not been calculated yet.
THRESHOLD	NUMBER		A number in the range [0, 1] that represents the threshold that the user has given as an input parameter to the current job of Workload Intelligence for the identification of significant patterns. If NULL, the process of pattern identification has not been initiated yet.

7.118 DBA_WI_OBJECTS

Each row in DBA_WI_OBJECTS represents a database object (table) that is accessed by the given template in the given Workload Intelligence job.

Column	Datatype	NULL	Description
JOB_ID	NUMBER	NOT NULL	The identifier of the job in the workload of which the given object has been accessed
TEMPLATE_ID	NUMBER	NOT NULL	The identifier of the template in the given job by which the current object has been accessed
OBJECT_ID	NUMBER	NOT NULL	The identifier of the current object
ACCESS_TYPE	VARCHAR2(2)	NOT NULL	Possible values: • R - Indicates that the current object has been accessed for reading by the given template • W - Indicates that the current object has been accessed for writing by the given template • RW - Indicates that the current object has been accessed for both reading and writing by the given template

7.119 DBA_WI_PATTERN_ITEMS

Each row in DBA_WI_PATTERN_ITEMS represents a template that participates in a significant pattern that has been found by the given Workload Intelligence job.

Column	Datatype	NULL	Description
JOB_ID	NUMBER	NOT NULL	The identifier of the job in the workload of which the current pattern has been found
PATTERN_ID	NUMBER	NOT NULL	The identifier of the pattern to which the current item (template) belongs
SEQUENCE_NUMBER	NUMBER	NOT NULL	Number that indicates the position of the current item in the given pattern
TEMPLATE_ID	NUMBER	NOT NULL	The identifier of the template that participates in the given position of the current pattern
IS_FIRST_IN_LOOP	CHAR(1)	NOT NULL	A flag that indicates whether or not the current item marks the beginning of a loop in the given pattern. The possible values are Y and N.
IS_LAST_IN_LOOP	CHAR(1)	NOT NULL	A flag that indicates whether or not the current item marks the end of a loop in the given pattern. The possible values are Y and N.

7.120 DBA_WI_PATTERNS

Each row in DBA_WI_PATTERNS represents a pattern that has been identified by Workload Intelligence as significant in the workload associated with the given job. Such a pattern consists of one or more templates.

These templates that comprise the given pattern are described in the related view DBA_WI_PATTERN_ITEMS.

Column	Datatype	NULL	Description
JOB_ID	NUMBER	NOT NULL	The identifier of the job in the workload of which the current pattern has been found
PATTERN_ID	NUMBER	NOT NULL	The identifier of the current pattern
LENGTH	NUMBER	NOT NULL	The length of the pattern, that is, the number of items (templates) it consists of
NUMBER_OF_EXECUTIONS	NUMBER	NOT NULL	The number of times the current pattern has been executed in the given workload
DB_TIME	NUMBER	NOT NULL	The total time consumed in the database server by all the executions of the current pattern in the given workload

See Also:

"DBA_WI_PATTERN_ITEMS"

7.121 DBA_WI_STATEMENTS

Each row in DBA_WI_STATEMENTS describes a statement (SQL or PL/SQL) that is part of the template with identifier TEMPLATE_ID, which has been found in the workload that is related to the Workload Intelligence job whose identifier is equal to JOB_ID.

A template may consist of multiple statements, for example, if it represents a transaction. In this case, there is one row in this view for every one of these statements. These statements are ordered, based on the order defined by the corresponding transaction. Column SEQUENCE_NUMBER is used to describe this order.

Column	Datatype	NULL	Description
JOB_ID	NUMBER	NOT NULL	The identifier of the job in the workload of which the given statement has been found
TEMPLATE_ID	NUMBER	NOT NULL	The identifier of the template in the given job to which the current statement belongs
SEQUENCE_NUMBER	NUMBER	NOT NULL	A number that indicates the order of the current statement in the given template

Column	Datatype	NULL	Description
SQL_TEXT	CLOB	NOT NULL	The SQL text associated with the current statement. Note that although multiple SQL statements can be classified to the same template, only one row is stored that represents them all. This row corresponds to the first instance of the given template that is found during parsing of the workload.

7.122 DBA_WI_TEMPLATE_EXECUTIONS

Each row in DBA_WI_TEMPLATE_EXECUTIONS represents an execution of a template in a capture that belongs to the workload that is associated with the current Workload Intelligence job.

Column	Datatype	NULL	Description
JOB_ID	NUMBER	NOT NULL	The identifier of the job in the workload of which the current execution of the given template belongs
CAPTURE_FILE_ID	NUMBER	NOT NULL	The identifier of the capture file in which the current execution of the given template was found
SEQUENCE_NUMBER	NUMBER	NOT NULL	A number that indicates the order of the current execution in the given capture file
TEMPLATE_ID	NUMBER	NOT NULL	The identifier of the template that was executed in the execution represented by the current row
DB_TIME	NUMBER	NOT NULL	The time that the current execution consumed on the database server

7.123 DBA_WI_TEMPLATES

Each row in DBA_WI_TEMPLATES describes a template that has been found in the workload that is related to the Workload Intelligence job whose identifier is equal to JOB_ID.

A template can represent either a simple query, or an entire transaction. Two queries in the given workload belong to the same template, if they exhibit trivial differences, for example, if they contain different literal values, different bind variable names, different comments, or different white spaces.

Column	Datatype	NULL	Description
JOB_ID	NUMBER	NOT NULL	The identifier of the job in the workload of which the given template has been found
TEMPLATE_ID	NUMBER	NOT NULL	The identifier of a template in a given job
IS_TRANSACTION	CHAR(1)	NOT NULL	Flag that indicates whether the given template represents a transaction: • Y - indicates that the given template represents a transaction • N - indicates that the given template does not represent a transaction

7.124 DBA_WORKLOAD_ACTIVE_USER_MAP

DBA_WORKLOAD_ACTIVE_USER_MAP contains the mappings that are going to be valid for the next replay or are valid for the current replay.

Column	Datatype	NULL	Description
SCHEDULE_CAP_ID	NUMBER		The ID of a capture in the schedule
CAPTURE_USER	VARCHAR2(4000)	NOT NULL	The user name during the time of the workload capture
REPLAY_USER	VARCHAR2(4000)		The user name to which captured user should be remapped during replay

7.125 DBA_WORKLOAD_CAPTURE_SQLTEXT

DBA_WORKLOAD_CAPTURE_SQLTEXT displays all the SQL statements that have been recorded in a workload capture. For those SQL statements whose length exceeds 1000 characters, the full statements can be loaded to the DBA_WORKLOAD_LONG_SQLTEXT view using the DBMS_WORKLOAD_REPLAY.LOAD_LONG_SQLTEXT procedure.

Column	Datatype	NULL	Description
CAPTURE_ID	NUMBER(38)	NOT NULL	Internal key for the workload capture
SQL_ID	VARCHAR2(13)	NOT NULL	SQL identifier of the parent cursor in the library cache
SQL_TYPE	VARCHAR2(64)		Type of the SQL statement, which can include values such as INSERT, SELECT, and CREATE INDEX
SQL_TEXT	VARCHAR2(1000)		First thousand characters of the SQL text for the current cursor
SQL_LENGTH	NUMBER(38)		The length of the SQL statement
SQL_TEXT_COMPLETE	CHAR(1)		Indicates whether the SQL_TEXT column includes the full text of the SQL statement. Possible values: • Y: The column SQL_TEXT includes the full text of the SQL statement • N: The column SQL_TEXT contains only the first thousand characters of the SQL text

See Also:

- "DBA_WORKLOAD_LONG_SQLTEXT"
- "DBA_RAT_CAPTURE_SCHEMA_INFO"
- *Oracle Database PL/SQL Packages and Types Reference* for information about the DBMS_WORKLOAD_REPLAY package

7.126 DBA_WORKLOAD_CAPTURES

DBA_WORKLOAD_CAPTURES displays all the workload captures that have been performed in the current database.

It also lists captures on which DBMS_WORKLOAD_CAPTURE.GET_CAPTURE_INFO() or DBMS_WORKLOAD_REPLAY.GET_REPLAY_INFO() have been called. Each row contains information about one workload capture.

Column	Datatype	NULL	Description
ID	NUMBER	NOT NULL	Internal key for the workload capture
NAME	VARCHAR2(128)	NOT NULL	Name for the workload capture
DBID	NUMBER	NOT NULL	ID of the database in which the workload was captured
DBNAME	VARCHAR2(128)	NOT NULL	Name of the database in which the workload was captured
DBVERSION	VARCHAR2(17)	NOT NULL	Version of the database in which the workload was captured
PARALLEL	VARCHAR2(3)		Indicates whether the database in which the workload was captured is an Oracle RAC database (YES) or a single instance database (NO)
DIRECTORY	VARCHAR2(128)	NOT NULL	Name of the directory object for workload capture
STATUS	VARCHAR2(40)	NOT NULL	Current status of the workload capture: • IN PROGRESS - Workload capture is in progress • COMPLETED - Workload capture has completed successfully • FAILED - Workload capture was terminated due to errors encountered
START_TIME	DATE	NOT NULL	Datetime when the capture began
END_TIME	DATE		Datetime when the capture completed or failed; NULL if the capture is still in progress
DURATION_SECS	NUMBER		Duration of the workload capture (in seconds)
START_SCN	NUMBER	NOT NULL	Start SCN value for this capture
END_SCN	NUMBER		End SCN value for this capture; NULL if the capture is still in progress
DEFAULT_ACTION	VARCHAR2(30)	NOT NULL	Mode in which to apply workload capture filters: • INCLUDE - All the capture filters are treated as EXCLUSION filters, determining the workload that will not be captured. • EXCLUDE - All the capture filters are treated as INCLUSION FILTERS, determining the workload that will be captured.
FILTERS_USED	NUMBER		Number of filters that were used for this capture
CAPTURE_SIZE	NUMBER		Total size of workload capture
DBTIME	NUMBER		Total amount of database time (in microseconds) that has been recorded in this workload capture

Column	Datatype	NULL	Description
DBTIME_TOTAL	NUMBER		Total amount of database time (in microseconds) across the entire database during the workload capture, including the part of the workload that was not captured.
USER_CALLS	NUMBER		Total number of user calls that have been recorded in this workload capture
USER_CALLS_TOTAL	NUMBER		Total number of user calls across the entire database during the workload capture, including the part of the workload that was not captured.
USER_CALLS_UNREPLAYABLE	NUMBER		Total number of user calls that will not be replayed in a subsequent replay of this workload capture
PLSQL_SUBCALL_SIZE	NUMBER		Total size of workload capture for SQL executed from PL/SQL
PLSQL_CALLS	NUMBER		Total number of PL/SQL calls recorded in the workload capture
PLSQL_SUBCALLS	NUMBER		Total number of calls recorded in the workload capture for SQL executed from PL/SQL
PLSQL_DBTIME	NUMBER		Total amount of database time (in microseconds) from PL/SQL calls that have been recorded in the workload capture
TRANSACTIONS	NUMBER		Total number of transactions that have been recorded in this workload capture
TRANSACTIONS_TOTAL	NUMBER		Total number of transactions across the entire database during the workload capture, including the part of the workload that was not captured.
CONNECTS	NUMBER		Total number of session connects that have been recorded in this workload capture
CONNECTS_TOTAL	NUMBER		Total number of session connects across the entire database during the workload capture, including the part of the workload that was not captured
ERRORS	NUMBER		Total number of errors that have been recorded in this workload capture
AWR_DBID	NUMBER		Database ID of the AWR snapshots that correspond to this workload capture. For captures that were performed in the current database, this value is equal to the current database's DBID. For captures that were performed in other databases, this value will either be NULL or will be populated by `DBMS_WORKLOAD_CAPTURE.IMPORT_AWR()`.
AWR_BEGIN_SNAP	NUMBER		Begin snapshot ID of the AWR snapshots that correspond to this workload capture
AWR_END_SNAP	NUMBER		End snapshot ID of the AWR snapshots that correspond to this workload capture

Column	Datatype	NULL	Description
AWR_EXPORTED	VARCHAR2(12)		Indicates whether the AWR snapshots that correspond to this workload capture have been exported using DBMS_WORKLOAD_CAPTURE.EXPORT_AWR() (YES) or not (NO), or whether AWR snapshots cannot be exported because the capture is still in progress, has run to completion successfully, or was done in a different database from which it was not exported (NOT POSSIBLE)
ERROR_CODE	NUMBER		Error code for this workload capture
ERROR_MESSAGE	VARCHAR2(512)		Error message for this workload capture
DIR_PATH	VARCHAR2(4000)	NOT NULL	Full directory path for the workload capture directory object
DIR_PATH_SHARED	VARCHAR2(10)	NOT NULL	Indicates whether the workload capture directory is shared by all the instances of the recording database (applicable only for Oracle RAC databases)
LAST_PROCESSED_VERSION	VARCHAR2(128)		Database version in which this capture was preprocessed using DBMS_WORKLOAD_REPLAY.PROCESS_CAPTURE() last; NULL if the capture has never been preprocessed
SQLSET_OWNER	VARCHAR2(128)		User name of the SQL tuning set owner
SQLSET_NAME	VARCHAR2(128)		Name of the SQL tuning set for this workload capture
PLSQL_MODE	VARCHAR2(12)		Capture options for PL/SQL calls. Possible values: • TOP_LEVEL: Top-level PL/SQL only • EXTENDED: Both top-level PL/SQL and SQL executed from PL/SQL
ENCRYPTION	VARCHAR2(128)		Indicates the encryption standard used for the given capture: • NULL - Capture files are not encrypted • AES128 – Capture files are encrypted using AES128 • AES192 – Capture files are encrypted using AES192 • AES256 – Capture files are encrypted using AES256
ENCRYPTION_VERIFIER	RAW(512)		Data used internally for creating an encrypted capture
PATCH_NAME	VARCHAR2(128)		Database workload capture and replay patch name This column is populated only for backports to Oracle Database 12c Release 1 (12.1) and earlier releases.
STORAGE_TYPE	NUMBER(38)		Describes where the captured workload is stored

See Also:

- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_WORKLOAD_CAPTURE package
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_WORKLOAD_REPLAY package

7.127 DBA_WORKLOAD_CONNECTION_MAP

DBA_WORKLOAD_CONNECTION_MAP displays the connection mapping information for workload replay. Each row defines one connection mapping for a particular workload replay.

Column	Datatype	NULL	Description
REPLAY_ID	NUMBER	NOT NULL	ID of the replay (corresponds to DBA_WORKLOAD_REPLAYS.ID)
CONN_ID	NUMBER	NOT NULL	Key (ID) of the connection mapping table
SCHEDULE_CAP_ID	NUMBER		Schedule capture ID (corresponds to DBA_WORKLOAD_SCHEDULE_CAPTURES.SCHEDULE_CAP_ID)
CAPTURE_CONN	VARCHAR2(4000)	NOT NULL	Connection string that was used during capture
REPLAY_CONN	VARCHAR2(4000)		Connection string that should be used during replay

7.128 DBA_WORKLOAD_DIV_SUMMARY

DBA_WORKLOAD_DIV_SUMMARY displays a summary of the replay divergence information in the DBA_WORKLOAD_REPLAY_DIVERGENCE view. DBA_WORKLOAD_REPLAY_DIVERGENCE may have duplicate entries, while DBA_WORKLOAD_DIV_SUMMARY keeps only one entry and tracks the number of occurrences of each duplicate entry.
Starting with Oracle Database 12.2.0.1, the replay report is generated from DBA_WORKLOAD_DIV_SUMMARY instead of from DBA_WORKLOAD_REPLAY_DIVERGENCE, which results in faster generation of the replay report.

Column	Datatype	NULL	Description
REPLAY_ID	NUMBER	NOT NULL	ID (key) for the workload replay
DIVERGENCE_TYPE	NUMBER	NOT NULL	Reserved for future use
IS_QUERY_DATA_DIVERGENCE	VARCHAR2(1)		Indicates whether the data divergence is from the number of rows fetched by SELECT queries (Y) or not (N)
IS_DML_DATA_DIVERGENCE	VARCHAR2(1)		Indicates whether the divergence is from the number of rows affected by INSERT, UPDATE, or DELETE SQL statements (Y) or not (N)
IS_ERROR_DIVERGENCE	VARCHAR2(1)		Indicates whether the divergence is from errors seen during capture or replay (Y) or not (N)

Column	Datatype	NULL	Description
IS_THREAD_FAILURE	VARCHAR2(1)		Indicates whether the divergence is from sessions that failed during replay (Y) or not (N)
IS_DATA_MASKED	VARCHAR2(1)		Indicates whether the SQL call contains masked bind data (Y) or not (N). If data masking technology is used at the replay database, the workload capture files need to be masked. Otherwise, SQL statements generated from capture files that contain sensitive bind data will not match the database. When the replay client sends masked bind data to the server, it turns on the IS_DATA_MASKED flag for the current SQL call.
IS_CLIENT_FAILURE	VARCHAR2(1)		Indicates whether the workload replay client failed during replay (Y) or not (N)
STREAM_ID	NUMBER	NOT NULL	Stream ID of the session that reported the divergence
SQL_ID	VARCHAR2(13)		SQL ID of the SQL that reported the divergence
EXPECTED_ERROR#	NUMBER		Error number that was seen during capture (0 if the capture ran successfully)
EXPECTED_ERROR_MESSAGE	VARCHAR2(4000)		Text of the error message whose number appears in the EXPECTED_ERROR# column
OBSERVED_ERROR#	NUMBER		Actual error number seen during replay (0 if the replay ran successfully, 15566 (corresponding to ORA-15566) if the captured call could not be replayed)
OBSERVED_ERROR_MESSAGE	VARCHAR2(4000)		Text of the error message whose number appears in the OBSERVED_ERROR# column
SERVICE	VARCHAR2(64)		Service name of the session that reported the divergence
MODULE	VARCHAR2(64)		Module name of the session that reported the divergence
INSTANCE_NUMBER	NUMBER		The number of the instance that reported the divergence
WRC_ID	NUMBER		The identifier of the workload replay client
OCCURRENCES	NUMBER		Number of times the divergence occurred during replay

Example

The following query prints the top 3 SQL statements that got error divergence during replay. This query shows the captured error number and the actual error number seen during replay.

```
SQL> SELECT * FROM
 (SELECT occurrences, sql_id, expected_error#, observed_error#
  FROM    dba_workload_div_summary
  WHERE   replay_id = 123
   AND    is_error_divergence = 'Y'
  ORDER BY occurrences DESC)
WHERE ROWNUM <= 3;
```

```
OCCURRENCES SQL_ID        EXPECTED_ERROR# OBSERVED_ERROR#
----------- ------------- --------------- ---------------
          8 0xrm2wjdqv17m               0               1
          4 8bzwdnnznspjd            1422               0
          3 6d8rwrac8dsk7               1            1400

SQL>
```

> **See Also:**
>
> "DBA_WORKLOAD_REPLAY_DIVERGENCE"

7.129 DBA_WORKLOAD_FILTERS

DBA_WORKLOAD_FILTERS displays all the workload filters that have been defined in the current database.

In Oracle Database 11*g*, only workload filters of type CAPTURE are supported. Starting with Oracle Database 11*g*R2, filters of type REPLAY are supported.

Column	Datatype	NULL	Description
TYPE	VARCHAR2(30)		Type of the workload filter (CAPTURE or REPLAY)
ID	VARCHAR2(40)		Sequence number of the workload filter
STATUS	VARCHAR2(6)		Status of the workload filter: • NEW - This filter will be used by the next subsequent operation such as the next workload capture. • IN USE - This filter is currently being used by an operation that is in progress such as an active workload capture. • USED - This filter was used in the past by some operation such as a past workload capture.
SET_NAME	VARCHAR2(1000)		Name of the filter set to which the filter belongs
NAME	VARCHAR2(128)		Name of the workload filter
ATTRIBUTE	VARCHAR2(128)		Name of the attribute on which the filter is defined
VALUE	VARCHAR2(4000)		Value of the attribute on which the filter is defined. Wildcards such as % and _ are supported if the attribute is of string type.

7.130 DBA_WORKLOAD_GROUP_ASSIGNMENTS

DBA_WORKLOAD_GROUP_ASSIGNMENTS displays all the workload capture groups and their assigned instances. A workload capture group is a subset of the captured workload. Each group accesses its own set of recorded database objects.

Column	Datatype	NULL	Description
REPLAY_DIR_NUMBER	NUMBER(38)	NOT NULL	The value that is associated with the subdirectory under the replay directory. See REPLAY_DIR_NUMBER in DBA_WORKLOAD_REPLAYS.
GROUP_ID	NUMBER(38)	NOT NULL	The identifier of a workload capture group
INSTANCE_NUMBER	NUMBER(38)	NOT NULL	The instance a given group is assigned to

> **See Also:**
>
> "DBA_WORKLOAD_REPLAYS"

7.131 DBA_WORKLOAD_LONG_SQLTEXT

DBA_WORKLOAD_LONG_SQLTEXT displays the captured SQL statements that are longer than 1000 characters. You can load SQL statements longer than 1000 characters to the DBA_WORKLOAD_LONG_SQLTEXT view using the DBMS_WORKLOAD_REPLAY.LOAD_LONG_SQLTEXT procedure.

Column	Datatype	NULL	Description
CAPTURE_ID	NUMBER(38)	NOT NULL	Internal key for the workload capture
SQL_ID	VARCHAR2(13)	NOT NULL	SQL identifier of the parent cursor in the library cache
SQL_FULLTEXT	CLOB		Full text for the SQL statement exposed as a CLOB column

> **See Also:**
>
> - "DBA_WORKLOAD_CAPTURE_SQLTEXT"
> - *Oracle Database PL/SQL Packages and Types Reference* for information about the DBMS_WORKLOAD_REPLAY package

7.132 DBA_WORKLOAD_REPLAY_CLIENTS

DBA_WORKLOAD_REPLAY_CLIENTS displays all workload replay clients and their assigned instances.

Column	Datatype	NULL	Description
WRC_ID	NUMBER(38)	NOT NULL	The identifier of a workload replay client
SCHEDULE_CAP_ID	NUMBER(38)	NOT NULL	A unique identifier for a workload capture added to a replay schedule. 0 for a non-consolidated replay

Column	Datatype	NULL	Description
INSTANCE_NUMBER	NUMBER(38)	NOT NULL	The instance that the replay client connects to

7.133 DBA_WORKLOAD_REPLAY_DIVERGENCE

DBA_WORKLOAD_REPLAY_DIVERGENCE displays information about data/error divergence for a user call that has been replayed.

DBA_WORKLOAD_DIV_SUMMARY displays a summary of the replay divergence information in the DBA_WORKLOAD_REPLAY_DIVERGENCE view. DBA_WORKLOAD_REPLAY_DIVERGENCE may have duplicate entries, while DBA_WORKLOAD_DIV_SUMMARY keeps only one entry and tracks the number of occurrences of each duplicate entry.

Column	Datatype	NULL	Description
REPLAY_ID	NUMBER	NOT NULL	ID (key) for the workload replay
TIMESTAMP	TIMESTAMP(6) WITH TIME ZONE		Time that the divergence occurred
DIVERGENCE_TYPE	NUMBER	NOT NULL	Reserved for future use
IS_QUERY_DATA_DIVERGENCE	VARCHAR2(1)		Indicates whether the data divergence is from the number of rows fetched by SELECT queries (Y) or not (N)
IS_DML_DATA_DIVERGENCE	VARCHAR2(1)		Indicates whether the divergence is from the number of rows affected by INSERT, UPDATE, or DELETE SQL statements (Y) or not (N)
IS_ERROR_DIVERGENCE	VARCHAR2(1)		Indicates whether the divergence is from errors seen during capture or replay (Y) or not (N)
IS_THREAD_FAILURE	VARCHAR2(1)		Indicates whether the divergence is from sessions that failed during replay (Y) or not (N)
IS_DATA_MASKED	VARCHAR2(1)		Indicates whether the SQL call contains masked bind data (Y) or not (N). If data masking technology is used at the replay database, the workload capture files need to be masked. Otherwise, SQL statements generated from capture files that contain sensitive bind data will not match the database. When the replay client sends masked bind data to the server, it turns on the IS_DATA_MASKED flag for the current SQL call.
IS_CLIENT_FAILURE	VARCHAR2(1)		Indicates whether the workload replay client failed during replay (Y) or not (N)
EXPECTED_ROW_COUNT	NUMBER		Number of rows fetched for SELECT queries or rows affected for INSERT, UPDATE, or DELETE SQL statements during capture
OBSERVED_ROW_COUNT	NUMBER		Actual number of rows fetched for SELECT queries or rows affected for INSERT, UPDATE, or DELETE SQL statements during replay
EXPECTED_ERROR#	NUMBER		Error number that was seen during capture (0 if the capture ran successfully)

Column	Datatype	NULL	Description
EXPECTED_ERROR_MESSAGE	VARCHAR2(4000)		Text of the error message whose number appears in the EXPECTED_ERROR# column
OBSERVED_ERROR#	NUMBER		Actual error number seen during replay (0 if the replay ran successfully, 15566 (corresponding to ORA-15566) if the captured call could not be replayed)
OBSERVED_ERROR_MESSAGE	VARCHAR2(4000)		Text of the error message whose number appears in the OBSERVED_ERROR# column
STREAM_ID	NUMBER	NOT NULL	Stream ID of the session that reported the divergence
CALL_COUNTER	NUMBER	NOT NULL	Call counter of the user call that reported the divergence
CAPTURE_STREAM_ID	NUMBER		Internal ID of the capture file whose replay produced the divergence
SQL_ID	VARCHAR2(13)		SQL ID of the SQL that reported the divergence
SESSION_ID	NUMBER	NOT NULL	Session ID of the session that reported the divergence
SESSION_SERIAL#	NUMBER	NOT NULL	Captured session serial number of the session that reported the divergence
SERVICE	VARCHAR2(64)		Service name of the session that reported the divergence
MODULE	VARCHAR2(64)		Module name of the session that reported the divergence
ACTION	VARCHAR2(64)		Action name of the session that reported the divergence
INSTANCE_NUMBER	NUMBER		The number of the instance that reported the divergence
WRC_ID	NUMBER		The identifier of the workload replay client

See Also:

"DBA_WORKLOAD_DIV_SUMMARY"

7.134 DBA_WORKLOAD_REPLAY_SCHEDULES

DBA_WORKLOAD_REPLAY_SCHEDULES displays the names of replay schedules for the current replay directory.

A replay schedule defines one or multiple workload captures, and the order to start their replays. The current replay directory is set by DBMS_WORKLOAD_REPLAY.SET_REPLAY_DIRECTORY('replay_dir'). Each row in the view contains information about one replay schedule.

Column	Datatype	NULL	Description
SCHEDULE_NAME	VARCHAR2(128)	NOT NULL	The name of a schedule to be replayed. It defines one or multiple workload captures, and the order to start their replays.
DIRECTORY	VARCHAR2(128)	NOT NULL	Directory object name for the replay schedule name
STATUS	VARCHAR2(128)		NEW if the schedule is being created, CURRENT if the schedule is currently being used by a replay, otherwise NULL

See Also:

- "DBA_WORKLOAD_SCHEDULE_CAPTURES" displays the workload captures in a replay schedule.
- "DBA_WORKLOAD_SCHEDULE_ORDERING" displays the order to start captures in a replay schedule.
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_WORKLOAD_REPLAY package

7.135 DBA_WORKLOAD_REPLAYS

DBA_WORKLOAD_REPLAYS displays all the workload replays that have been performed in the current database.

It also lists replays on which DBMS_WORKLOAD_REPLAY.GET_REPLAY_INFO() has been called. Each row contains information about one workload replay.

Column	Datatype	NULL	Description
ID	NUMBER	NOT NULL	Internal key for the workload replay
NAME	VARCHAR2(128)	NOT NULL	Name of the workload replay
DBID	NUMBER	NOT NULL	ID of the database in which the workload was replayed
DBNAME	VARCHAR2(128)	NOT NULL	Name of the database in which the workload was replayed
DBVERSION	VARCHAR2(17)	NOT NULL	Version of the database in which the workload was replayed
PARALLEL	VARCHAR2(3)		Indicates whether the database in which the workload was replayed was an Oracle RAC database (YES) or a single instance database (NO)
DIRECTORY	VARCHAR2(128)	NOT NULL	Name of the directory object for the workload replay
CAPTURE_ID	NUMBER		ID of the capture (DBA_WORKLOAD_CAPTURES.ID) that was replayed. If the replay involves a replay schedule, the CAPTURE_ID will be null.

Column	Datatype	NULL	Description
STATUS	VARCHAR2(40)	NOT NULL	Current status of the workload replay: • PREPARE - Workload prepare has been started and is waiting for clients to join • IN PROGRESS - Workload replay is in progress • COMPLETED - Workload replay has successfully completed • CANCELLED - Workload replay or the workload prepare has been cancelled • FAILED - Workload replay was terminated due to errors encountered. See the COMMENTS column for further information.
PREPARE_TIME	DATE		Datetime at which the workload prepare started
START_TIME	DATE		Datetime when the replay began
END_TIME	DATE		Datetime when the replay completed or cancelled; NULL if the replay is still in progress
DURATION_SECS	NUMBER		Duration of the workload replay (in seconds)
NUM_CLIENTS	NUMBER	NOT NULL	Number of workload replay client processes that were used in this workload replay
NUM_CLIENTS_DONE	NUMBER	NOT NULL	Number of workload replay client processes that have finished replay
FILTER_SET_NAME	VARCHAR2(128)		Name of the filter set used for the replay
DEFAULT_ACTION	VARCHAR2(30)	NOT NULL	Reserved for future use
SYNCHRONIZATION	VARCHAR2(9)		Indicates whether recorded transaction semantics should be maintained (TRUE) or not (FALSE) When synchronization is on, the commit order observed during the original workload capture will be preserved. Every action that is replayed will be executed only after all of its dependent commits have been executed. Dependent commits are commits that were issued before the given action in the original workload capture. **See Also:** DBMS_WORKLOAD_REPLAY.PREPARE_REPLAY() in *Oracle Database PL/SQL Packages and Types Reference* for a detailed explanation of this replay parameter
CONNECT_TIME_SCALE	NUMBER	NOT NULL	Connection time scaling factor for captured streams during replay. The value is interpreted as a percentage.The default value of 100 means 100 percent. **See Also:** DBMS_WORKLOAD_REPLAY.PREPARE_REPLAY() in *Oracle Database PL/SQL Packages and Types Reference* for a detailed explanation of this replay parameter

Column	Datatype	NULL	Description
THINK_TIME_SCALE	NUMBER	NOT NULL	Think time scaling factor for captured streams during replay. It scales the thinking time elapsed between two successive user calls from the same captured stream. The input is interpreted as a percentage. The default value of 100 means 100 percent. **See Also:** DBMS_WORKLOAD_REPLAY.PREPARE_REPLAY() in *Oracle Database PL/SQL Packages and Types Reference* for a detailed explanation of this replay parameter
THINK_TIME_AUTO_CORRECT	VARCHAR2(5)		Indicates whether the think time should be automatically corrected between calls (TRUE) or not (FALSE) A value of TRUE reduces think time if replay goes slower than capture. A value of FALSE results in no action. **See Also:** DBMS_WORKLOAD_REPLAY.PREPARE_REPLAY() in *Oracle Database PL/SQL Packages and Types Reference* for a detailed explanation of this replay parameter
SCALE_UP_MULTIPLIER	NUMBER	NOT NULL	Before the multiple-capture replay, SCALE_UP_MULTIPLIER is used to scale up the query part of a workload capture. The queries from each captured session are replayed concurrently as many times as the value of SCALE_UP_MULTIPLIER.
USER_CALLS	NUMBER		Total number of user calls replayed
DBTIME	NUMBER		Accumulated database time (in microseconds) for the replay
NETWORK_TIME	NUMBER		Accumulated network time for the replay (in microseconds)
THINK_TIME	NUMBER		Accumulated think time (in microseconds) for the replay
PAUSE_TIME	NUMBER		The total time (in seconds) that the replay has been paused (by calling the PAUSE_REPLAY procedure)
PLSQL_CALLS	NUMBER		Total number of replayed top-level PL/SQL calls
PLSQL_SUBCALLS	NUMBER		Total number of replayed calls for SQL executed from PL/SQL
PLSQL_DBTIME	NUMBER		Total amount of database time (in microseconds) from PL/SQL calls
ELAPSED_TIME_DIFF	NUMBER		Reserved for future use

Column	Datatype	NULL	Description
REPLAY_DEADLOCKS	NUMBER		A workload replay uses either the timing information from the capture files or the commit-based synchronization. With commit-based synchronization, the capture-time commit order is preserved during replay, and sessions normally wait on the session that is to do the next commit; such waits are classified as “WCR: replay clock” waits. A replay deadlock occurs if the session that is to do the next commit is itself blocked by a session that is waiting on “WCR: replay clock.” Replay deadlocks are resolved by allowing the blocker to go ahead and commit out of order. Replay deadlocks are not detected as database deadlocks since “WCR: replay clock” is an idle wait, introduced specifically for DB Replay. **See Also**: "WCR: replay clock"
AWR_DBID	NUMBER		Database ID of the AWR snapshots that correspond to this workload replay. For replays that were performed in the current database, this value is equal to the current database's DBID. For replays that were performed in other databases, this value will either be NULL or will be populated by `DBMS_WORKLOAD_REPLAY.IMPORT_AWR()`. **See Also:** DBMS_WORKLOAD_REPLAY.IMPORT_AWR() in *Oracle Database PL/SQL Packages and Types Reference*
AWR_BEGIN_SNAP	NUMBER		Begin snapshot ID of the AWR snapshots that correspond to this workload replay
AWR_END_SNAP	NUMBER		End snapshot ID of the AWR snapshots that correspond to this workload replay
AWR_EXPORTED	VARCHAR2(12)		Indicates whether the AWR snapshots that correspond to this workload replay have been exported using `DBMS_WORKLOAD_REPLAY.EXPORT_AWR()` (`YES`) or not (`NO`), or whether AWR snapshots cannot be exported because the replay is still in progress, has run to completion successfully, or was done in a different database from which it was not exported (`NOT POSSIBLE`) **See Also:** DBMS_WORKLOAD_REPLAY.EXPORT_AWR() in *Oracle Database PL/SQL Packages and Types Reference*
ERROR_CODE	NUMBER		Error code for this workload replay
ERROR_MESSAGE	VARCHAR2(512)		Error message for this workload replay
DIR_PATH	VARCHAR2(4000)	NOT NULL	Full directory path for the replay directory object

Column	Datatype	NULL	Description
REPLAY_DIR_NUMBER	NUMBER		A hash value computed based on the values of other columns in this view, such as the NAME, DBID, DBNAME, PREPARE_TIME, START_TIME, and END_TIME columns. It should be fairly unique for any replay. The value is used to create a subdirectory under the replay directory.
SQLSET_OWNER	VARCHAR2(128)		User name of the SQL tuning set owner
SQLSET_NAME	VARCHAR2(128)		Name of the SQL tuning set for this workload replay
SCHEDULE_NAME	VARCHAR2(128)		The name of a schedule to be replayed. It defines one or multiple workload captures, and the order to start their replays. If SCHEDULE_NAME is NULL, the replay is a regular replay introduced since Oracle Database 11*g*, done with existing APIs from DBMS_WORKLOAD_REPLAY: INITIALIZE_REPLAY, PREPARE_REPLAY, and START_REPLAY. If SCHEDULE_NAME is not NULL, the replay is a new consolidated replay introduced in Oracle Database 12*c*. That is, it is a replay of one or more workload captures done with new APIs at DBMS_WORKLOAD_REPLAY: INITIALIZE_CONSOLIDATED_REPLAY, PREPARE_CONSOLIDATED_REPLAY, and START_CONSOLIDATED_REPLAY. **See Also:** DBMS_WORKLOAD_REPLAY in *Oracle Database PL/SQL Packages and Types Reference*
DIVERGENCE_LOAD_STATUS	VARCHAR2(5)		Indicates whether replay divergence data have been loaded (TRUE) or not (FALSE)
PLSQL_MODE	VARCHAR2(12)		Replay options for PL/SQL calls. Possible values: • TOP_LEVEL: Top-level PL/SQL only • EXTENDED: SQL executed from PL/SQL or top-level PL/SQL if there is no SQL recorded inside the PL/SQL
CONNECT_TIME_AUTO_CORRECT	VARCHAR2(12)		Indicates whether the waiting time for a new session to be connected is automatically reduced when the replay proceeds faster than its capture. The reduced amount is determined by the elapsed-time difference between the replay and the capture of the slowest session. The default value is true. There is no impact when the replay proceeds slower than the capture.

Column	Datatype	NULL	Description
RAC_MODE	VARCHAR2(19)		Replay options in an Oracle RAC environment: • GLOBAL_SYNC: Synchronization is across all instances. This is the default. Database connections from workload replay client (wrc) are done based on connection remapping. • PER_INSTANCE_CLIENT: Synchronization is across all instances. All database connections from one wrc are connected to only one instance. • PER_INSTANCE_SYNC: Synchronization is within one instance. All database connections from one wrc are connected to only one instance.
QUERY_ONLY	VARCHAR2(1)		Indicates whether only the query-only workload from the current workload capture will be replayed, skipping all the DML/DDL that might update the database (Y) or not (N)
PDB_LEVEL	VARCHAR2(1)		Indicates whether the replay is a PDB-level replay (Y) or not (N)
NUM_CLIENTS_ABORTED	NUMBER		Number of workload replay clients terminated during the replay
PATCH_NAME	VARCHAR2(128)		Database workload capture and replay patch name This column is only populated for backports to Oracle Database 12c Release 1 (12.1) and earlier releases.
DURATION_LIMIT	NUMBER(38)		Replay duration limit (in seconds) If the replay duration limit has not been set, then the value of this column is null.
STATUS_DETAILS	VARCHAR2(128)		Provides additional details about the replay status If additional details are not available, then the value of this column is null.

See Also:

Oracle Database PL/SQL Packages and Types Reference for more information about the DBMS_WORKLOAD_REPLAY package

7.136 DBA_WORKLOAD_SCHEDULE_CAPTURES

DBA_WORKLOAD_SCHEDULE_CAPTURES displays the workload captures used by replay schedules.

Each row in the view contains information about one workload capture.

Column	Datatype	NULL	Description
SCHEDULE_NAME	VARCHAR2(128)	NOT NULL	The name of a schedule to be replayed
SCHEDULE_CAP_ID	NUMBER	NOT NULL	Identifies a workload capture added to a replay schedule. It starts with 1. If the same capture is added multiple times to a schedule, there will be multiple rows with different SCHEDULE_CAP_ID columns and identical CAPTURE_ID columns.
CAPTURE_ID	NUMBER	NOT NULL	Points to the capture ID from DBA_WORKLOAD_CAPTURES.
CAPTURE_DIR	VARCHAR2(128)	NOT NULL	Name of the directory object for workload capture
OS_SUBDIR	VARCHAR2(4000)	NOT NULL	Name of the subdirectory under the replay directory for this workload capture
MAX_CONCURRENT_SESSIONS	NUMBER		The maximal number of concurrent sessions that was seen in this workload capture
NUM_CLIENTS_ASSIGNED	NUMBER		Number of clients assigned to this workload capture before replay starts
NUM_CLIENTS	NUMBER		Number of clients that are running for this workload capture during replay
NUM_CLIENTS_DONE	NUMBER		Number of clients that have finished the replay of this workload capture
STOP_REPLAY	VARCHAR2(1)	NOT NULL	Indicates whether the whole replay will stop once the replay of this workload capture is done (Y) or not (N)
TAKE_BEGIN_SNAPSHOT	VARCHAR2(1)	NOT NULL	Indicates whether an AWR snapshot will be taken when the replay of this capture starts (Y) or not (N)
TAKE_END_SNAPSHOT	VARCHAR2(1)	NOT NULL	Indicates whether an AWR snapshot will be taken when the replay of this capture finishes (Y) or not (N)
QUERY_ONLY	VARCHAR2(1)	NOT NULL	Indicates whether only the query-only workload from the current workload capture will be replayed, skipping all the DML/DDL that might update the database (Y) or not (N)
START_DELAY_SECS	NUMBER		Displays the wait time (in seconds) when the replay of a workload capture is ready to start. "Ready to start" means the capture does not wait for any other capture, or all the captures for which it should wait have already been replayed. The default value is 0.
START_TIME	DATE		Start time for the replay of this capture
END_TIME	DATE		Finish time for the replay of this capture
AWR_DBID	NUMBER		AWR database ID of the replay
AWR_BEGIN_SNAP	NUMBER		AWR snapshot ID when the replay starts
AWR_END_SNAP	NUMBER		AWR snapshot ID when the replay finishes
NUM_CLIENTS_ABORTED	NUMBER		Number of workload replay clients terminated during the replay

7.137 DBA_WORKLOAD_SCHEDULE_ORDERING

DBA_WORKLOAD_SCHEDULE_ORDERING displays the start ordering between workload captures in the replay schedule.

Each row in the view defines one start ordering between two workload captures in the same replay schedule.

Column	Datatype	NULL	Description
SCHEDULE_NAME	VARCHAR2(128)	NOT NULL	Name of a schedule to be replayed
SCHEDULE_CAP_ID	NUMBER	NOT NULL	Identifies the workload capture that will wait
WAITFOR_CAP_ID	NUMBER	NOT NULL	Identifies the workload capture for which the workload capture identified by SCHEDULE_CAP_ID needs to wait. The replay of capture SCHEDULE_CAP_ID will not start until capture WAITFOR_CAP_ID finishes its replay. If the view has multiple rows with the same SCHEDULE_CAP_ID but different WAITFOR_CAP_ID, it defines a schedule so that the replay of a capture specified by SCHEDULE_CAP_ID will not start unless all the replays of the waited captures run into completion. If the view has multiple rows with the same WAITFOR_CAP_ID but different SCHEDULE_CAP_ID, it defines a schedule so that the replay of multiple captures will not start unless the replay of the capture specified by WAITFOR_CAP_ID finishes.

7.138 DBA_WORKLOAD_SQL_MAP

DBA_WORKLOAD_SQL_MAP contains the mapping information for skipping or replacing a SQL statement based on its sql_id during workload replay.

Column	Datatype	NULL	Description
REPLAY_ID	NUMBER(38)	NOT NULL	A foreign key to the ID column in the DBA_WORKLOAD_REPLAYs view
SCHEDULE_CAP_ID	NUMBER(38)	NOT NULL	The ID of a capture in the schedule
SQL_ID	VARCHAR2(13)	NOT NULL	SQL identifier of the SQL statement at the time of capture
OPERATION	VARCHAR2(7)		SKIP or REPLACE
SQL_ID_NUMBER	NUMBER		Internal representation of SQL_ID
REPLACEMENT_SQL_TEXT	VARCHAR2(4000)		When the value in the OPERATION column is SKIP, this column is NULL. When the value in the OPERATION column is REPLACE, this column shows the SQL statement to be used.

7.139 DBA_WORKLOAD_TRACKED_COMMITS

DBA_WORKLOAD_TRACKED_COMMITS displays the commits tracked every second during a database replay.

Column	Datatype	NULL	Description
REPLAY_DIR_NUMBER	NUMBER	NOT NULL	The numerical value that is associated with the subdirectory under the replay directory. See REPLAY_DIR_NUMBER in DBA_WORKLOAD_REPLAYS
INSTANCE_NUMBER	NUMBER(38)		The instance where the commit is executed
FILE_ID	NUMBER(38)	NOT NULL	The file ID
CALL_CTR	NUMBER(38)	NOT NULL	The call counter of the commit
COMMIT_SCN	NUMBER(38)		The recorded commit SCN value
PREV_GLOBAL_COMMIT_FILE_ID	NUMBER(38)		The file ID of the latest commit across all sessions
PREV_GLOBAL_COMMIT_SCN	NUMBER(38)		The recorded SCN of the latest commit across all sessions
PREV_LOCAL_COMMIT_CALL_CTR	NUMBER(38)		The call counter of the latest commit in the same session
CAPTURE_COMMIT_TIME	NUMBER(38)		The time in seconds since the capture started
CAPTURE_COMMIT_TIME_DELTA	NUMBER(38)		The elapsed time in seconds since the previous commit across all sessions during capture
REPLAY_COMMIT_TIME	NUMBER(38)		The time in seconds since the replay started
REPLAY_COMMIT_TIME_DELTA	NUMBER(38)		The elapsed time in seconds since the previous commit across all sessions during the replay

See Also:

DBA_WORKLOAD_REPLAYS

7.140 DBA_WORKLOAD_USER_MAP

DBA_WORKLOAD_USER_MAP contains all the mappings ever done until they are removed at some point.

The mappings are stored in a table made public through this view.

To remove old mappings, execute this statement:

```
SQL> delete * from DBA_WORKLOAD_USER_MAP;
```

Column	Datatype	NULL	Description
REPLAY_ID	NUMBER		This is a foreign key to the ID column in the DBA_WORKLOAD_REPLAYS view

Column	Datatype	NULL	Description
SCHEDULE_CAP_ID	NUMBER		The ID of a capture in the schedule
CAPTURE_USER	VARCHAR2(4000)	NOT NULL	The user name during the time of the workload capture
REPLAY_USER	VARCHAR2(4000)		The user name to which the captured user should be remapped during replay. If the REPLAY_USER is null, the CAPTURE_USER is used during replay. In other words, the original user is used.

> **See Also:**
>
> "DBA_WORKLOAD_REPLAYS"

7.141 DBA_XML_INDEXES

DBA_XML_INDEXES describes all XML indexes in the database. Its columns are the same as those in ALL_XML_INDEXES.

> **See Also:**
>
> "ALL_XML_INDEXES"

7.142 DBA_XML_NESTED_TABLES

DBA_XML_NESTED_TABLES describes all the tables and their corresponding nested tables. Its columns are the same as those in ALL_XML_NESTED_TABLES.

> **See Also:**
>
> "ALL_XML_NESTED_TABLES"

7.143 DBA_XML_OUT_OF_LINE_TABLES

DBA_XML_OUT_OF_LINE_TABLES descibes all the out of line tables connected to a given root table for the same schema. Its columns are the same as those in ALL_XML_OUT_OF_LINE_TABLES.

> **See Also:**
>
> "ALL_XML_OUT_OF_LINE_TABLES"

7.144 DBA_XML_SCHEMA_ATTRIBUTES

DBA_XML_SCHEMA_ATTRIBUTES describes all the attributes and their properties. Its columns are the same as those in ALL_XML_SCHEMA_ATTRIBUTES.

> **See Also:**
>
> "ALL_XML_SCHEMA_ATTRIBUTES"

7.145 DBA_XML_SCHEMA_COMPLEX_TYPES

DBA_XML_SCHEMA_COMPLEX_TYPES describes all complex types in the database. Its columns are the same as those in ALL_XML_SCHEMA_COMPLEX_TYPES.

> **See Also:**
>
> "ALL_XML_SCHEMA_COMPLEX_TYPES"

7.146 DBA_XML_SCHEMA_ELEMENTS

DBA_XML_SCHEMA_ELEMENTS describes all the elements and their properties. Its columns are the same as those in ALL_XML_SCHEMA_ELEMENTS.

> **See Also:**
>
> "ALL_XML_SCHEMA_ELEMENTS"

7.147 DBA_XML_SCHEMA_NAMESPACES

DBA_XML_SCHEMA_NAMESPACES describes all the available namespaces. Its columns are the same as those in ALL_XML_SCHEMA_NAMESPACES.

> **See Also:**
>
> "ALL_XML_SCHEMA_NAMESPACES"

7.148 DBA_XML_SCHEMA_SIMPLE_TYPES

DBA_XML_SCHEMA_SIMPLE_TYPES describes all simple types. Its columns are the same as those in ALL_XML_SCHEMA_SIMPLE_TYPES.

> **See Also:**
>
> "ALL_XML_SCHEMA_SIMPLE_TYPES"

7.149 DBA_XML_SCHEMA_SUBSTGRP_HEAD

DBA_XML_SCHEMA_SUBSTGRP_HEAD describes the heads of substitution groups. Its columns are the same as those in ALL_XML_SCHEMA_SUBSTGRP_HEAD.

> **See Also:**
>
> "ALL_XML_SCHEMA_SUBSTGRP_HEAD"

7.150 DBA_XML_SCHEMA_SUBSTGRP_MBRS

DBA_XML_SCHEMA_SUBSTGRP_MBRS describes all members of substitution groups. Its columns are the same as those in ALL_XML_SCHEMA_SUBSTGRP_MBRS.

> **See Also:**
>
> "ALL_XML_SCHEMA_SUBSTGRP_MBRS"

7.151 DBA_XML_SCHEMAS

`DBA_XML_SCHEMAS` describes all registered XML schemas in the database. Its columns are the same as those in `ALL_XML_SCHEMAS`.

> **See Also:**
>
> "ALL_XML_SCHEMAS"

7.152 DBA_XML_TAB_COLS

`DBA_XML_TAB_COLS` describes the columns of all XML tables in the database. Its columns are the same as those in `ALL_XML_TAB_COLS`.

> **See Also:**
>
> "ALL_XML_TAB_COLS"

7.153 DBA_XML_TABLES

`DBA_XML_TABLES` describes all XML tables in the database. Its columns are the same as those in `ALL_XML_TABLES`.

> **See Also:**
>
> "ALL_XML_TABLES"

7.154 DBA_XML_VIEW_COLS

`DBA_XML_VIEW_COLS` describes the columns of all XML views in the database. Its columns are the same as those in `ALL_XML_VIEW_COLS`.

> **See Also:**
>
> "ALL_XML_VIEW_COLS"

7.155 DBA_XML_VIEWS

DBA_XML_VIEWS describes all XML views in the database. Its columns are the same as those in ALL_XML_VIEWS.

> **See Also:**
>
> "ALL_XML_VIEWS"

7.156 DBA_XS_AUDIT_POLICY_OPTIONS

DBA_XS_AUDIT_POLICY_OPTIONS describes auditing options defined under all audit policies specific to Oracle Database Real Application Security.

Column	Datatype	NULL	Description
POLICY_NAME	VARCHAR2(128)		Name of the audit policy
AUDIT_CONDITION	VARCHAR2(4000)		Condition associated with the audit policy
AUDIT_OPTION	VARCHAR2(128)		Auditing option defined in the audit policy
CONDITION_EVAL_OPT	VARCHAR2(9)		Evaluation option associated with the audit policy's condition. The possible values are STATEMENT, SESSION, INSTANCE, NONE.
COMMON	VARCHAR2(3)		Indicates whether the audit policy is a common audit policy (YES) or local (NO). The value is NULL in non-CDBs.

> **See Also:**
>
> *Oracle Database Security Guide* for more information about auditing

7.157 DBA_XS_AUDIT_TRAIL

DBA_XS_AUDIT_TRAIL describes all audit records specific to Oracle Database Real Application Security.

Column	Datatype	NULL	Description
USERID	VARCHAR2(128)		Name of the database user whose actions were audited
ACTION	NUMBER		Numeric audit trail action type code. The corresponding name of the action type is in the ACTION_NAME column.
ACTION_NAME	VARCHAR2(64)		Name of the action type corresponding to the numeric code in the ACTION column

Column	Datatype	NULL	Description
OBJ_OWNER	VARCHAR2(128)		Owner of the object affected by the action
OBJ_NAME	VARCHAR2(128)		Name of the object affected by the action
RETURN_CODE	NUMBER		Oracle error code generated by the action
XS_USER_NAME	VARCHAR2(128)		Name of the Real Application Security user
XS_SESSIONID	RAW(33)		Identifer of the Real Application Security session
XS_INACTIVITY_TIMEOUT	NUMBER		Inactivity timeout of the Real Application Security session
XS_ENTITY_TYPE	VARCHAR2(32)		Type of the Real Application Security entity. Possible values are USER, ROLE, ROLESET, SECURITYCLASS, ACL, DATASECURITY, and NSTEMPLATE.
XS_TARGET_PRINCIPAL_NAME	VARCHAR2(128)		Target principal name in Real Application Security operations. Possible operations are set verifier, set password, add proxy, remove proxy, switch user, assign user, create session, grant roles.
XS_PROXY_USER_NAME	VARCHAR2(128)		Name of the Real Application Security proxy user.
XS_DATASEC_POLICY_NAME	VARCHAR2(128)		Name of the Real Application Security data security policy enabled or disabled
XS_SCHEMA_NAME	VARCHAR2(128)		Name of the schema in enable, disable data security policy and global callback operation
XS_CALLBACK_EVENT_TYPE	VARCHAR2(32)		Real Application Security global callback event type
XS_PACKAGE_NAME	VARCHAR2(128)		Real Application Security callback package name for the global callback
XS_PROCEDURE_NAME	VARCHAR2(128)		Real Application Security callback procedure name for the global callback
XS_ENABLED_ROLE	VARCHAR2(128)		The role that is enabled
XS_COOKIE	VARCHAR2(1024)		Real Application Security session cookie
XS_NS_NAME	VARCHAR2(128)		Name of the Real Application Security session namespace
XS_NS_ATTRIBUTE	VARCHAR2(4000)		Name of the Real Application Security session namespace attribute
XS_NS_ATTRIBUTE_OLD_VAL	VARCHAR2(4000)		The old value of the Real Application Security session namespace attribute
XS_NS_ATTRIBUTE_NEW_VAL	VARCHAR2(4000)		The new value of the Real Application Security session namespace attribute
EVENT_TIMESTAMP	TIMESTAMP(6) WITH TIME ZONE		Timestamp of audit record

See Also:

Oracle Database Security Guide for more information about auditing

7.158 DBA_XS_ENABLED_AUDIT_POLICIES

DBA_XS_ENABLED_AUDIT_POLICIES describes all the audit policies specific to Oracle Database Real Application Security that are enabled to users.

> **Note:**
>
> This view was known as DBA_XS_ENB_AUDIT_POLICIES in Oracle Database 12*c* Release 1. It was renamed to DBA_XS_ENABLED_AUDIT_POLICIES in Oracle Database 12*c* Release 2 (12.2.0.1).

Column	Datatype	NULL	Description
POLICY_NAME	VARCHAR2(128)		Name of the audit policy
ENABLED_OPTION	VARCHAR2(15)		Enabled option of the audit policy. Possible values: • BY USER: For policies that are enabled on users • EXCEPT USERS: For policies that are enabled on users • BY GRANTED ROLE: For policies that are enabled on roles • INVALID: For policies that are enabled on roles
ENTITY_NAME	VARCHAR2(128)		Database entity (user name or role name) on which the audit policy is enabled
ENTITY_TYPE	VARCHAR2(7)		Database entity type. Possible values: • USER: Indicates that the policy is enabled on a user or users. • ROLE: Indicates that the policy is enabled on a role or roles.
SUCCESS	VARCHAR2(3)		Indicates whether the audit policy is enabled for auditing successful events (YES) or not (NO)
FAILURE	VARCHAR2(3)		Indicates whether the audit policy is enabled for auditing unsuccessful events (YES) or not (NO)

> **See Also:**
>
> *Oracle Database Security Guide* for more information about auditing

7.159 DBA_XS_ENB_AUDIT_POLICIES

DBA_XS_ENB_AUDIT_POLICIES is a synonym for the DBA_XS_ENABLED_AUDIT_POLICIES view.

See Also:

- "DBA_XS_ENABLED_AUDIT_POLICIES"
- *Oracle Database Security Guide* for more information about auditing
- *Oracle Database Security Guide* for more information about auditing

7.160 DBA_XSTREAM_ADMINISTRATOR

`DBA_XSTREAM_ADMINISTRATOR` displays information about the users who have been granted privileges to be XStream administrators by procedures in the `DBMS_XSTREAM_AUTH` package. Its columns are the same as those in `ALL_XSTREAM_ADMINISTRATOR`.

See Also:

"ALL_XSTREAM_ADMINISTRATOR"

7.161 DBA_XSTREAM_INBOUND

`DBA_XSTREAM_INBOUND` displays information about all XStream inbound servers in the database. Its columns are the same as those in `ALL_XSTREAM_INBOUND`.

See Also:

"ALL_XSTREAM_INBOUND"

7.162 DBA_XSTREAM_INBOUND_PROGRESS

`DBA_XSTREAM_INBOUND_PROGRESS` displays information about the progress made by all XStream inbound servers in the database. Its columns are the same as those in `ALL_XSTREAM_INBOUND_PROGRESS`.

See Also:

"ALL_XSTREAM_INBOUND_PROGRESS"

7.163 DBA_XSTREAM_OUT_SUPPORT_MODE

DBA_XSTREAM_OUT_SUPPORT_MODE displays information about the level of XStream capture process support for the tables in the database. Its columns are the same as those in ALL_XSTREAM_OUT_SUPPORT_MODE.

> **See Also:**
>
> "ALL_XSTREAM_OUT_SUPPORT_MODE"

7.164 DBA_XSTREAM_OUTBOUND

DBA_XSTREAM_OUTBOUND displays information about all XStream outbound servers in the database. Its columns are the same as those in ALL_XSTREAM_OUTBOUND.

> **See Also:**
>
> "ALL_XSTREAM_OUTBOUND"

7.165 DBA_XSTREAM_OUTBOUND_PROGRESS

DBA_XSTREAM_OUTBOUND_PROGRESS displays information about the progress made by all XStream outbound servers in the database. Its columns are the same as those in ALL_XSTREAM_OUTBOUND_PROGRESS.

> **See Also:**
>
> "ALL_XSTREAM_OUTBOUND_PROGRESS"

7.166 DBA_XSTREAM_RULES

DBA_XSTREAM_RULES displays information about all XStream rules in the database. Its columns are the same as those in ALL_XSTREAM_RULES.

> **See Also:**
>
> "ALL_XSTREAM_RULES"

7.167 DBA_XSTREAM_SPLIT_MERGE

DBA_XSTREAM_SPLIT_MERGE displays information about XStream current automatic split and merge operations.

Column	Datatype	NULL	Description
ORIGINAL_CAPTURE_NAME	VARCHAR2(128)	NOT NULL	Name of the original capture process
CLONED_CAPTURE_NAME	VARCHAR2(128)		Name of the cloned capture process
ORIGINAL_CAPTURE_STATUS	VARCHAR2(8)		Status of the original capture process: • DISABLED • ENABLED • ABORTED
CLONED_CAPTURE_STATUS	VARCHAR2(8)		Status of the cloned capture process: • DISABLED • ENABLED • ABORTED
ORIGINAL_XSTREAM_NAME	VARCHAR2(128)		Name of the original XStream component that receives database changes directly from the original capture process. The component is either a progagation or a local apply process.
CLONED_XSTREAM_NAME	VARCHAR2(128)		Name of the cloned XStream component that receives database changes directly from the cloned capture process. The component is either a progagation or a local apply process.
XSTREAM_TYPE	VARCHAR2(11)		Type of the component in ORIGINAL_XSTREAM_NAME and CLONED_XSTREAM_NAME: • PROPAGATION • APPLY
RECOVERABLE_SCRIPT_ID	RAW(16)		Unique ID of the script to split or merge operation
SCRIPT_STATUS	VARCHAR2(12)		Status of the recoverable script: • GENERATING • NOT EXECUTING • EXECUTING • EXECUTED • ERROR
ACTION_TYPE	VARCHAR2(7)		type of action performed by the script: • SPLIT • MERGE • MONITOR
ACTION_THRESHOLD	VARCHAR2(40)		For SPLIT actions, the threshold set by the split_threshold capture process parameter. For MERGE actions, the threshold set by the merge_threshold capture process parameter.

Column	Datatype	NULL	Description
STATUS	VARCHAR2(16)		Status of the action: • NOTHING TO SPLIT - Not ready to split or does not need to split • ABOUT TO SPLIT • SPLITTING - A split is in progress • SPLIT DONE - A split is done • NOTHING TO MERGE - Not ready to merge • ABOUT TO MERGE • MERGING - A merge is in progress • MERGE DONE - A merge is done • ERROR - An error was returned during a split or merge • NONSPLITTABLE - The original capture is not splittable either because it is disabled, it has more than one publisher to its queue, or it has only one destination for captured messages
STATUS_UPDATE_TIME	TIMESTAMP(6)		Time when status was last updated
CREATION_TIME	TIMESTAMP(6)		Time when the action started
LAG	NUMBER		Time (in seconds) that the cloned capture process lags behind the original capture process
JOB_OWNER	VARCHAR2(128)		Owner of the job that performs the split or merge operation
JOB_NAME	VARCHAR2(128)		Name of the job that performs the split or merge operation
JOB_STATE	VARCHAR2(15)		Current state of the job: • DISABLED • RETRY SCHEDULED • SCHEDULED • RUNNING • COMPLETED • BROKEN • FAILED • REMOTE • SUCCEEDED • CHAIN_STALLED
JOB_NEXT_RUN_DATE	VARCHAR2(64)		Next time the job will run
ERROR_NUMBER	NUMBER		Error number if the capture process was terminated
ERROR_MESSAGE	VARCHAR2(4000)		Error message if the capture process was terminated

7.168 DBA_XSTREAM_SPLIT_MERGE_HIST

DBA_XSTREAM_SPLIT_MERGE_HIST displays information about past XStream automatic split and merge operations.

Column	Datatype	NULL	Description
ORIGINAL_CAPTURE_NAME	VARCHAR2(128)	NOT NULL	Name of the original capture process
CLONED_CAPTURE_NAME	VARCHAR2(128)		Name of the cloned capture process
ORIGINAL_QUEUE_OWNER	VARCHAR2(128)		Owner of the queue used by the original capture process
ORIGINAL_QUEUE_NAME	VARCHAR2(128)		Name of the queue used by the original capture process
CLONED_QUEUE_OWNER	VARCHAR2(128)		Owner of the queue used by the cloned capture process
CLONED_QUEUE_NAME	VARCHAR2(128)		Name of the queue used by the cloned capture process
ORIGINAL_CAPTURE_STATUS	VARCHAR2(8)		Status of the original capture process: • DISABLED • ENABLED • ABORTED
CLONED_CAPTURE_STATUS	VARCHAR2(8)		Status of the cloned capture process: • DISABLED • ENABLED • ABORTED
ORIGINAL_XSTREAM_NAME	VARCHAR2(128)		Name of the original XStream component that receives database changes directly from the original capture process. The component is either a progagation or a local apply process.
CLONED_XSTREAM_NAME	VARCHAR2(128)		Name of the cloned XStream component that receives database changes directly from the cloned capture process. The component is either a progagation or a local apply process.
XSTREAM_TYPE	VARCHAR2(11)		Type of the component in ORIGINAL_XSTREAM_NAME and CLONED_XSTREAM_NAME: • PROPAGATION • APPLY
RECOVERABLE_SCRIPT_ID	RAW(16)		Unique ID of the script to split or merge operation
SCRIPT_STATUS	VARCHAR2(12)		Status of the recoverable script: • GENERATING • NOT EXECUTING • EXECUTING • EXECUTED • ERROR
ACTION_TYPE	VARCHAR2(7)		type of action performed by the script: • SPLIT • MERGE • MONITOR
ACTION_THRESHOLD	VARCHAR2(40)		For SPLIT actions, the threshold set by the split_threshold capture process parameter. For MERGE actions, the threshold set by the merge_threshold capture process parameter.

Column	Datatype	NULL	Description
STATUS	VARCHAR2(16)		Status of the action: • NOTHING TO SPLIT - Not ready to split or does not need to split • ABOUT TO SPLIT • SPLITTING - A split is in progress • SPLIT DONE - A split is done • NOTHING TO MERGE - Not ready to merge • ABOUT TO MERGE • MERGING - A merge is in progress • MERGE DONE - A merge is done • ERROR - An error was returned during a split or merge • NONSPLITTABLE - The original capture is not splittable either because it is disabled, it has more than one publisher to its queue, or it has only one destination for captured messages
STATUS_UPDATE_TIME	TIMESTAMP(6)		Time when status was last updated
CREATION_TIME	TIMESTAMP(6)		Time when the action started
LAG	NUMBER		Time (in seconds) that the cloned capture process lags behind the original capture process
JOB_OWNER	VARCHAR2(128)		Owner of the job that performs the split or merge operation
JOB_NAME	VARCHAR2(128)		Name of the job that performs the split or merge operation
ERROR_NUMBER	NUMBER		Error number if the capture process was terminated
ERROR_MESSAGE	VARCHAR2(4000)		Error message if the capture process was terminated

7.169 DBA_XSTREAM_STMT_HANDLERS

DBA_XSTREAM_STMT_HANDLERS displays information about all XStream statement DML handlers in the database.

Column	Datatype	NULL	Description
HANDLER_NAME	VARCHAR2(128)	NOT NULL	Name of the statement handler
HANDLER_COMMENT	VARCHAR2(4000)		Comment of the statement handler
CREATION_TIME	TIMESTAMP(6)		Timestamp for script creation
MODIFICATION_TIME	TIMESTAMP(6)		Timestamp for script modification

7.170 DBA_XSTREAM_STMTS

DBA_XSTREAM_STMTS displays information about the statements in all XStream statement DML handlers in the database.

Column	Datatype	NULL	Description
HANDLER_NAME	VARCHAR2(128)	NOT NULL	Name of the statement handler
EXECUTION_SEQUENCE	NUMBER	NOT NULL	Execution sequence of the statement
STATEMENT	CLOB		Text of the SQL statement
CREATION_TIME	TIMESTAMP(6)		Timestamp for statement creation
MODIFICATION_TIME	TIMESTAMP(6)		Timestamp for statement modification

7.171 DBA_XSTREAM_TRANSFORMATIONS

DBA_XSTREAM_TRANSFORMATIONS displays information about all XStream transformations available on a system, in order of execution. Its columns are the same as those in ALL_XSTREAM_TRANSFORMATIONS.

See Also:

"ALL_XSTREAM_TRANSFORMATIONS"

7.172 DBA_XTERNAL_LOC_PARTITIONS

DBA_XTERNAL_LOC_PARTITIONS describes partition-level locations in the database. Its columns are the same as those in ALL_XTERNAL_LOC_PARTITIONS.

See Also:

"ALL_XTERNAL_LOC_PARTITIONS"

7.173 DBA_XTERNAL_LOC_SUBPARTITIONS

DBA_XTERNAL_LOC_SUBPARTITIONS describes subpartition-level locations in the database. Its columns are the same as those in ALL_XTERNAL_LOC_SUBPARTITIONS.

See Also:

"ALL_XTERNAL_LOC_SUBPARTITIONS"

7.174 DBA_XTERNAL_PART_TABLES

DBA_XTERNAL_PART_TABLES describes object-level information for partitioned external tables in the database. Its columns are the same as those in ALL_XTERNAL_PART_TABLES.

> **See Also:**
>
> "ALL_XTERNAL_PART_TABLES"

7.175 DBA_XTERNAL_TAB_PARTITIONS

DBA_XTERNAL_TAB_PARTITIONS describes partition-level information for partitioned external tables in the database. Its columns are the same as those in ALL_XTERNAL_TAB_PARTITIONS.

> **See Also:**
>
> "ALL_XTERNAL_TAB_PARTITIONS"

7.176 DBA_XTERNAL_TAB_SUBPARTITIONS

DBA_XTERNAL_TAB_SUBPARTITIONS describes subpartition-level information for partitioned external tables in the database. Its columns are the same as those in ALL_XTERNAL_TAB_SUBPARTITIONS.

> **See Also:**
>
> "ALL_XTERNAL_TAB_SUBPARTITIONS"

7.177 DBA_ZONEMAP_AUTO_ACTIONS

DBA_ZONEMAP_AUTO_ACTIONS provides information about automatic zone map tasks and executions.

Column	Datatype	NULL	Description
TASK_ID	NUMBER	NOT NULL	Zone map task identifier
MSG_ID	NUMBER	NOT NULL	Zone map message identifier
EXEC_NAME	VARCHAR2(128)		Zone map execution name
ACTION_MSG	VARCHAR2(4000)		Execution message text

Column	Datatype	NULL	Description
TIME_STAMP	TIMESTAMP(9)		Execution timestamp

The TASK_ID, MSG_ID, and EXEC_NAME columns in this view correspond to the same columns in the DBA_ZONEMAP_AUTO_FINDINGS view. This allows you to correlate the actions in DBA_ZONEMAP_AUTO_ACTIONS with their corresponding findings in DBA_ZONEMAP_AUTO_FINDINGS.

> **See Also:**
>
> "DBA_ZONEMAP_AUTO_FINDINGS"

7.178 DBA_ZONEMAP_AUTO_FINDINGS

DBA_ZONEMAP_AUTO_FINDINGS provides information about automatic zone map findings.

Column	Datatype	NULL	Description
TASK_ID	NUMBER	NOT NULL	Zone map task identifier
MSG_ID	NUMBER	NOT NULL	Zone map message identifier
EXEC_NAME	VARCHAR2(128)		Zone map execution name
MESSAGE	VARCHAR2(4000)		Execution message text
TIME_STAMP	TIMESTAMP(9)		Finding timestamp
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object for which the finding was observed, typically a table name or a zone map name
FINDING_REASON	VARCHAR2(9)		Finding reason code
FINDING_TYPE	VARCHAR2(9)		Finding type. Possible values: • BLACKLIST: The table is no longer a candidate for automatic zone maps • ERROR: An error occurred • EVICT: The table does not meet automatic zone map creation criteria • OTHER Refer to the MESSAGE column for additional information about the reasoning behind the finding type.

Automatic zone map findings contain information that the database learned when performing automatic zone map executions. The database uses these findings to optimize subsequent automatic zone maps executions, which saves on execution time and resources.

The TASK_ID, MSG_ID, and EXEC_NAME columns in this view correspond to the same columns in the DBA_ZONEMAP_AUTO_ACTIONS view. This allows you to correlate the findings in DBA_ZONEMAP_AUTO_FINDINGS with their corresponding actions in DBA_ZONEMAP_AUTO_ACTIONS.

> **See Also:**
>
> "DBA_ZONEMAP_AUTO_ACTIONS"

7.179 DBA_ZONEMAP_MEASURES

`DBA_ZONEMAP_MEASURES` describes the measures for all the zone maps in the database. Its columns are the same as those in `ALL_ZONEMAP_MEASURES`.

> **Note:**
>
> This view is intended for use with Oracle Exadata release 12.1.2.1.1 or later.

> **See Also:**
>
> - "ALL_ZONEMAP_MEASURES"
> - *Oracle Database Data Warehousing Guide* for more information about zone maps

7.180 DBA_ZONEMAPS

`DBA_ZONEMAPS` describes all the zone maps in the database. Its columns are the same as those in `ALL_ZONEMAPS`.

> **Note:**
>
> This view is intended for use with Oracle Exadata release 12.1.2.1.1 or later.

> **See Also:**
>
> - "ALL_ZONEMAPS"
> - *Oracle Database Data Warehousing Guide* for more information about zone maps

7.181 DBFS_CONTENT

`DBFS_CONTENT` displays all the path items from all available content stores in the system.

Column	Datatype	NULL	Description
STORE	VARCHAR2(256)		Name of store
MOUNT	VARCHAR2(256)		Location at which instance of store is mounted
PATHNAME	VARCHAR2(1024)		Name of path to item
PATHTYPE	VARCHAR2(32)		Type of path item (see DBMS_DBFS_CONTENT Constants - Path Name Types)
FILEDATA	BLOB		BLOB locator that can be used to access data in the path item
STD_ACCESS_TIME	TIMESTAMP(6)		Time of last access of a path name's contents
STD_ACL	VARCHAR2(1024)		Access Control List (in standard ACL syntax)
STD_CHANGE_TIME	TIMESTAMP(6)		Time of last change to the path name
STD_CHILDREN	NUMBER		Number of child directories/folders a directory/ folder path has (this property should be available in providers that support the FEATURE_FOLDERS feature)
STD_CONTENT_TYPE	VARCHAR2(1024)		One or more client-supplied mime-types (in standard RFC syntax) describing the path name which is typically of TYPE_FILE. The content type is not necessarily interpreted by the store.
STD_CREATION_TIME	TIMESTAMP(6)		Time at which the item was created. Once set, this value remains the same for the lifetime of the path name.
STD_DELETED	NUMBER		Set to a nonzero number if the path name has been soft-deleted but not yet purged (see DBMS_DBFS_CONTENT Constants - Store Features)
STD_GUID	NUMBER		Store-specific unique identifier for a path name. Clients must not depend on the GUID being unique across different stores, but a given (store-name, store-specific-path name) has a stable and unique GUID for its lifetime.
STD_MODIFICATION_TIME	TIMESTAMP(6)		Time of last change to the data associated with a path name. Changes to the content of a TYPE_FILE or TYPE_REFERENCE path, the referent of the TYPE_LINK path, and addition or deletion of immediate children in a TYPE_DIRECTORY path, all constitute data changes.
STD_OWNER	VARCHAR2(32)		Client-supplied (or implicit) owner name for the path name
STD_PARENT_GUID	NUMBER		Store-specific unique identifier for the parent of a path name. Clients must not depend on the GUID being unique across different stores, but a given (store-name, store-specific-path name) has a stable and unique GUID for its lifetime. The GUID of the parent of this path name (that is that std_parent_guid(pathname) == std_guid(parent(pathname))).

Column	Datatype	NULL	Description
STD_REFERENT	VARCHAR2(1024)		Content of the symbolic link of a TYPE_LINK path, otherwise NULL. The STD_REFERENT can be an arbitrary string and must not necessarily be interpreted as path name by clients (or such interpretation should be done with great care).
OPT_HASH_TYPE	VARCHAR2(32)		Type of hash provided in the OPT_HASH_VALUE property (see DBMS_CRYPTO for possible options)
OPT_HASH_VALUE	VARCHAR2(128)		Hash value of type OPT_HASH_TYPE describing the content of the path name
OPT_LOCK_COUNT	NUMBER		Number of compatible locks placed on a path name. If different principals are allowed to place compatible (read) locks on a path, the OPT_LOCKER must specify all lockers with repeats so that lock counts can be correctly maintained.
OPT_LOCK_DATA	VARCHAR2(128)		Client-supplied user-data associated with a user-lock, uninterpreted by the store
OPT_LOCKER	VARCHAR2(128)		One or more implicit or client-specified principals that applied a user-lock on a path name
OPT_LOCK_STATUS	NUMBER		One of the (LOCK_READ_ONLY, LOCK_WRITE_ONLY, LOCK_READ_WRITE) values describing the type of lock currently applied on a path name
OPT_VERSION	NUMBER		Sequence number for linear versioning of a path name
OPT_VERSION_PATH	VARCHAR2(1024)		Version path name for hierarchical versioning of a path name
OPT_CONTENT_ID	RAW(128)		A provider-generated store-specific unique contentID in the form of a string for a file element (that may optionally not be associated with a path (see FEATURE_CONTENT_ID and FEATURE_LAZY_PATH in DBMS_DBFS_CONTENT Constants - Store Features)

See Also:

- *Oracle Database PL/SQL Packages and Types Reference* for more information about DBMS_DBFS_CONTENT Constants - Path Name Types and DBMS_DBFS_CONTENT Constants - Store Features
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_CRYPTO package

7.182 DBFS_CONTENT_PROPERTIES

DBFS_CONTENT_PROPERTIES displays all the property/value pairs for all path items in all content stores in the system.

Column	Datatype	NULL	Description
STORE	VARCHAR2(256)		Name of store
MOUNT	VARCHAR2(256)		Location at which instance of store is mounted
PATHNAME	VARCHAR2(1024)		Name of path to item
PROPERTY_NAME	VARCHAR2(32)		Name of the property
PROPERTY_VALUE	VARCHAR2(1024)		Value of the property
PROPERTY_TYPE	NUMBER		PL/SQL typecode for the property value

7.183 DBMS_ALERT_INFO

DBMS_ALERT_INFO describes registered alerts.

Column	Datatype	NULL	Description
NAME	VARCHAR2(30)	NOT NULL	Name of the alert
SID	VARCHAR2(30)	NOT NULL	Session ID of a session waiting for this alert
CHANGED	VARCHAR2(1)		Boolean flag to indicate that an alert has been signaled. Y: alert signaled, N: no alert.
MESSAGE	VARCHAR2(1800)		Optional message passed by signaler

7.184 DBMS_KAFKA_APPLICATIONS

DBMS_KAFKA_APPLICATIONS describes all Oracle SQL Access to Kafka (OSAK) applications in the database.

The role OSAK_ADMIN_ROLE allows users with no administrative privileges to query this table.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the application
CLUSTER_ID	VARCHAR2(40)	NOT NULL	ID of the OSAK cluster associated with the application
APPLICATION_NAME	VARCHAR2(30)	NOT NULL	Application name (also used as the Kafka group name)
TOPIC_NAME	VARCHAR2(249)	NOT NULL	Name of the Kafka topic associated with the application
NUM_VIEWS	NUMBER(38)	NOT NULL	Number of OSAK views for the application
NUM_PARTITIONS	NUMBER(38)	NOT NULL	Number of Kafka partitions associated with the OSAK views for the application
NUM_VIEWS_REQUESTED	NUMBER(38)	NOT NULL	Number of OSAK views requested for the application
APPLICATION_TYPE	VARCHAR2(30)	NOT NULL	Type of application: • LOAD • SEEKABLE • STREAMING
OPTIONS	BLOB	NOT NULL	User-supplied options (excluding AVRO-related schemas)

Column	Datatype	NULL	Description
AVRO_SCHEMA	BLOB		User-supplied AVRO schema for the Kafka topic value data
KEY_AVRO_SCHEMA	BLOB		Reserved for future use
EXT_TABLE_NAME	VARCHAR2(128)		Name of the external table created for the application
EXT_TABLE_SCHEMA	VARCHAR2(128)		Schema of the external table created for the application
PARTITION_TABLE_NAME	VARCHAR2(128)		Name of the PARTITIONS table created for the application
PARTITION_TABLE_SCHEMA	VARCHAR2(128)		Schema of the PARTITIONS table created for the application
PARTITION_VIEW_NAME	VARCHAR2(128)		Name of the PARTITIONS view created for the application
PARTITION_VIEW_SCHEMA	VARCHAR2(128)		Schema of the PARTITIONS view created for the application

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_KAFKA_APPLICATIONS"
- "USER_KAFKA_APPLICATIONS"

7.185 DBMS_KAFKA_CLUSTERS

DBMS_KAFKA_CLUSTERS describes all registered Oracle SQL Access to Kafka (OSAK) clusters in the database.

The role OSAK_ADMIN_ROLE allows users with no administrative privileges to query this table.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the cluster The value of this column is always SYS.
CLUSTER_ID	VARCHAR2(40)	NOT NULL	System-generated unique cluster ID
STATE	NUMBER(38)	NOT NULL	Current state of the cluster: • 0 - CONNECTED • 1 - MAINTENANCE • 2 - BROKEN • 3 - DEREGISTERED

Column	Datatype	NULL	Description
CLUSTER_NAME	VARCHAR2(30)	NOT NULL	User-supplied name of the cluster
BOOTSTRAP_SERVERS	VARCHAR2(4000)	NOT NULL	Comma-separated list of bootstrap servers for the cluster Each bootstrap server is represented in the following form: *hostname*:*port*
CLUSTER_ACCESS_DIRECTORY	VARCHAR2(128)	NOT NULL	Name of the directory object associated with the cluster Users with READ access to this directory object are allowed to access the cluster.
KAFKA_PROVIDER	VARCHAR2(128)	NOT NULL	Provider of the Kafka cluster software: • APACHE - Apache Kafka • OSS - Oracle Cloud Infrastructure Streaming Service
CREDENTIAL_NAME	VARCHAR2(128)		If KAFKA_PROVIDER = OSS, the name of the database credential for the Oracle Cloud Infrastructure Streaming Service connection
CREDENTIAL_SCHEMA	VARCHAR2(128)		If KAFKA_PROVIDER = OSS, the schema of CREDENTIAL_NAME
CLUSTER_CONFIG_DIRECTORY	VARCHAR2(128)		If KAFKA_PROVIDER = APACHE, the directory object that references the operating system directory containing the osakafka.properties file for the cluster
CLUSTER_DESCRIPTION	VARCHAR2(4000)		Optional user-supplied description of the Oracle SQL access to the cluster
CONNECTION_TS	TIMESTAMP(6)		Timestamp of the last known successful connection to the cluster The value of this column is NULL if a disconnect occurred or if there has never been a connection to the cluster.
OPTIONS	BLOB		Optional user-supplied options for the cluster

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_KAFKA_CLUSTERS"
- "USER_KAFKA_CLUSTERS"

7.186 DBMS_KAFKA_LOAD_METRICS

DBMS_KAFKA_LOAD_METRICS displays metrics for DBMS_KAFKA.EXECUTE_LOAD_APP operations on all tables in the database.

The role OSAK_ADMIN_ROLE allows users with no administrative privileges to query this table.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the table into which the Kafka data was loaded (TARGET_TABLE)
CLUSTER_ID	VARCHAR2(40)	NOT NULL	ID of the OSAK cluster associated with the EXECUTE_LOAD_APP operation
APPLICATION_NAME	VARCHAR2(30)		Application name (also used as the Kafka group name)
TARGET_TABLE	VARCHAR2(128)	NOT NULL	Name of the table into which the Kafka data was loaded
TARGET_TABLE_SCHEMA	VARCHAR2(128)	NOT NULL	Schema of the table into which the Kafka data was loaded
INSERTED_ROWS	NUMBER(38)		Total number of rows inserted into the table by the load operation
KAFKA_RECORDS	NUMBER(38)		Total number of Kafka records fetched for the load operation
STARTED_TIME	TIMESTAMP(6) WITH TIME ZONE		Date and time at which the Kafka data started being loaded into the table
FINISHED_TIME	TIMESTAMP(6) WITH TIME ZONE		Date and time at which the Kafka data finished being loaded into the table

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_KAFKA_LOAD_METRICS"
- "USER_KAFKA_LOAD_METRICS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_KAFKA.EXECUTE_LOAD_APP procedure

7.187 DBMS_KAFKA_MESSAGES

DBMS_KAFKA_MESSAGES displays messages logged by all Oracle SQL Access to Kafka (OSAK) applications in the database.

The role OSAK_ADMIN_ROLE allows users with no administrative privileges to query this table.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the application
CLUSTER_ID	VARCHAR2(40)	NOT NULL	ID of the OSAK cluster associated with the application
CLUSTER_NAME	VARCHAR2(30)	NOT NULL	Name of the OSAK cluster associated with the application
APPLICATION_NAME	VARCHAR2(30)		Application name (also used as the Kafka group name)
VIEW_NAME	VARCHAR2(128)		Name of the view associated with the application
VIEW_SCHEMA	VARCHAR2(128)		Schema of the view associated with the application
MESSAGE_TYPE	VARCHAR2(20)		Message type
MESSAGE_TS	TIMESTAMP(6)		Timestamp for when the message was logged
MESSAGE	VARCHAR2(4000)		Message text

Note:

This view is available starting with Oracle Database 23ai.

See Also:

"USER_KAFKA_MESSAGES"

7.188 DBMS_KAFKA_OPS

DBMS_KAFKA_OPS describes operations for all Oracle SQL Access to Kafka (OSAK) views in the database.

The role OSAK_ADMIN_ROLE allows users with no administrative privileges to query this table.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the OSAK view
OP_KEY	VARCHAR2(30)	NOT NULL	Unique operation key (replacement for the location file)
OP_TYPE	VARCHAR2(30)	NOT NULL	Generic operation type

Column	Datatype	NULL	Description
OP	VARCHAR2(30)	NOT NULL	Specific type of operation within OP_TYPE
CLUSTER_ID	VARCHAR2(40)	NOT NULL	ID of the OSAK cluster associated with the operation
APPLICATION_NAME	VARCHAR2(30)		Name of the OSAK application associated with the operation (also used as the Kafka group name)
TOPIC_NAME	VARCHAR2(249)		Name of the Kafka topic associated with the operation
PARTITION_ID	NUMBER(38)		Partition ID of the Kafka topic associated with the operation
OFFSET	NUMBER(38)		Next offset from which an SEQ operation will start reading
RELATIVE_OFFSET	NUMBER(38)		Number of offsets, including the watermark, from which an SEQ operation will start reading
WATERMARK	VARCHAR2(5)		Basis for the start read offset for an SEQ operation (WMH or WML)
START_OFFSET_EPOCH_TIME	NUMBER(38)		Timestamp (in milliseconds) that determines the next offset from which the operation will start reading This value is used by the DBMS_KAFKA.INIT_OFFSET_TS and DBMS_KAFKA.SEEK_OFFSET_TS procedures.
END_OFFSET_EPOCH_TIME	NUMBER(38)		Timestamp (in milliseconds) that determines the end offset at which the operation will stop reading This value is used by the DBMS_KAFKA.SEEK_OFFSET_TS procedure.
OPTIONS	BLOB		Options associated with the operation

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_KAFKA_OPS"
- "USER_KAFKA_OPS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_KAFKA.INIT_OFFSET_TS and DBMS_KAFKA.SEEK_OFFSET_TS procedures

7.189 DBMS_KAFKA_OPS_RESULTS

DBMS_KAFKA_OPS displays the results of operations for all Oracle SQL Access to Kafka (OSAK) views in the database.

The role OSAK_ADMIN_ROLE allows users with no administrative privileges to query this table.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of OSAK view
OP_KEY	VARCHAR2(30)		Unique operation key (replacement for the location file)
ROWS_READ	NUMBER(38)		Number of Kafka records read and returned by the operation
LAST_OFFSET	NUMBER(38)		Kafka offset of the last record read by the operation
OPTIONS	BLOB		Options associated with the operation results

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_KAFKA_OPS_RESULTS"
- "USER_KAFKA_OPS_RESULTS"

7.190 DBMS_KAFKA_PARTITIONS

DBMS_KAFKA_PARTITIONS describes partitions for Kafka topics associated with all Oracle SQL Access to Kafka (OSAK) views in the database.

The role OSAK_ADMIN_ROLE allows users with no administrative privileges to query this table.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	Owner of the OSAK view
CLUSTER_ID	VARCHAR2(40)	NOT NULL	ID of the OSAK cluster associated with the topic/ partition
APPLICATION_NAME	VARCHAR2(30)	NOT NULL	Application name (also used as the Kafka group name)
TOPIC_NAME	VARCHAR2(249)	NOT NULL	Kafka topic name associated with the topic/ partition
PARTITION_ID	NUMBER(38)	NOT NULL	Partition ID of the Kafka topic

Column	Datatype	NULL	Description
VIEW_ID	NUMBER(38)	NOT NULL	ID of the OSAK view associated with the topic/partition
VIEW_NAME	VARCHAR2(128)	NOT NULL	Name of the OSAK view associated with the topic/partition
VIEW_SCHEMA	VARCHAR2(128)	NOT NULL	Schema of the OSAK view associated with the topic/partition
TEMP_TABLE_NAME	VARCHAR2(128)		Name of the OSAK global temporary table associated with the topic/partition The value of this column is null if the application type is LOAD, that is, if the application was created using the DBMS_KAFKA.CREATE_LOAD_APP procedure. The application type is displayed in the APPLICATION_TYPE column of the DBMS_KAFKA_APPLICATIONS view.
TEMP_TABLE_SCHEMA	VARCHAR2(128)		Schema of the OSAK global temporary table associated with the topic/partition The value of this column is null if the application type is LOAD, that is, if the application was created using the DBMS_KAFKA.CREATE_LOAD_APP procedure. The application type is displayed in the APPLICATION_TYPE column of the DBMS_KAFKA_APPLICATIONS view.
OPTIONS	BLOB		Options associated with the partition

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DBA_KAFKA_PARTITIONS"
- "USER_KAFKA_PARTITIONS"

7.191 DBMS_KAFKA_SEC_ALLOWED_PROPERTIES

DBMS_KAFKA_SEC_ALLOWED_PROPERTIES displays valid Oracle SQL Access to Kafka (OSAK) security properties.

DBMS_KAFKA_SEC_ALLOWED_PROPERTIES is a system table that is created and populated during database installation. It displays the properties that are allowed in the osakafka.properties file, which contains security configuration properties as required by the librdkafka library.

Immediately after installation, DBMS_KAFKA_SEC_ALLOWED_PROPERTIES displays the initial Oracle SQL Access to Kafka (OSAK) security properties listed in Table 7-1.

Subsequently, a user with the role `OSAK_ADMIN_ROLE` can view `DBMS_KAFKA_SEC_ALLOWED_PROPERTIES` and add additional properties to this table, as required or suggested by Oracle Support. Only the properties displayed in the `DBMS_KAFKA_SEC_ALLOWED_PROPERTIES` table are read from the `osakafka.properties` file.

Column	Datatype	NULL	Description
PROPERTY_NAME	VARCHAR2(200)	NOT NULL	Name of the security property
DESCRIPTION	VARCHAR2(4000)		Description of the security property

Table 7-1 Initial Oracle SQL Access to Kafka (OSAK) Security Properties

Property Name	Description
debug	Enables `rdkafka` client debug output. The debug information is logged in Oracle trace files. The only allowed value is `all`.
max.partition.fetch.bytes	Maximum number of bytes a Kafka server can return in a poll of a single partition. This is a positive integer value. Oracle Cloud Infrastructure (OCI) Streaming service Kafka recommends limiting the request size to 1 MB per partition.
osak.kgmps.max.message.size	Maximum number of bytes a Kafka client can fetch in a poll of a single partition. This is a positive integer value with a default of 1 MB. This parameter, along with `max.partition.fetch.bytes`, allows for the retrieval of single Kafka records larger the 1 MB.
sasl.kerberos.ccname	File name of the Kerberos credentials (ticket) cache (`KRB5CCNAME`) of the Kafka cluster
sasl.kerberos.config	File name of the Kerberos configuration file (`krb5.conf`) of the Kafka cluster
sasl.kerberos.principal	Kafka client Kerberos principal name
sasl.kerberos.service.name	Primary name of the Kerberos principal, as specified in the Kafka Broker JAAS configuration file For example: The format of a typical Kerberos V5 principal is: *primary*/*instance*@*REALM*. Therefore, if the following is specified in the Kafka Broker JAAS configuration file: `principal="kafka/example.hostname.com@EXAMPLEREALM.COM"` Then the value of `sasl.kerberos.service.name` will be `kafka`.
sasl.mechanism	Simple Authentication and Security Layer (SASL) mechanism to use for authentication. This is an alias for the `sasl.mechanisms` property. The allowed values are `GSSAPI`, `PLAIN`, `SCRAM-SHA-256`, and `SCRAM-SHA-512`. Only one value is allowed. The default value is `GSSAPI`.
sasl.mechanisms	SASL mechanism to use for authentication. The allowed values are `GSSAPI`, `PLAIN`, `SCRAM-SHA-256`, and `SCRAM-SHA-512`. Only one value is allowed. The default value is `GSSAPI`.
sasl.username	User name for SASL authentication
security.protocol	Protocol used to communicate with Kafka brokers. The allowed values are `plaintext`, `ssl`, `sasl_plaintext`, and `sasl_ssl`. Only one value is allowed.
ssl.ca.location	File name of the Certificate Authority (CA) file for verifying the Kafka broker key

Table 7-1 (Cont.) Initial Oracle SQL Access to Kafka (OSAK) Security Properties

Property Name	Description
`ssl.certificate.location`	File name of the Kafka client certificate in Privacy-Enhanced Mail (PEM) format
`ssl.endpoint.identification.algorithm`	Endpoint identification algorithm to validate the Kafka broker host name using a Kafka broker certificate. The allowed values are `https` and `none`. The default value is `none`.
`ssl.key.location`	File name of the Kafka client private key

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> *Oracle Database Utilities* for more information about the `osakafka.properties` file

7.192 DBMS_LOCK_ALLOCATED

`DBMS_LOCK_ALLOCATED` describes user-allocated locks.

Column	Datatype	NULL	Description
`NAME`	`VARCHAR2(128)`	`NOT NULL`	Name of the lock
`LOCKID`	`NUMBER(38)`		Lock identifier number
`EXPIRATION`	`DATE`		Planned lock expiration date (updates whenever the allocation procedure is run)

7.193 DBMS_METADATA_PARSE_ITEMS

`DBMS_METADATA_PARSE_ITEMS` documents the valid parse items.

Column	Datatype	NULL	Description
`OBJECT_TYPE`	`VARCHAR2(128)`	`NOT NULL`	Object type name
`PARSE_ITEM`	`VARCHAR2(124)`		Parse item name
`ALTER_XML`	`VARCHAR2(1)`		`Y`: Can be used when generating `ALTER_XML` document
`FETCH_XML_CLOB`	`VARCHAR2(1)`		`Y`: Can be returned by `FETCH_XML_CLOB`
`CONVERT`	`VARCHAR2(1)`		`Y`: Can be returned by `CONVERT` or `FETCH_DDL`

Column	Datatype	NULL	Description
DESCRIPTION	VARCHAR2(4000)		Description of the parse item

See Also:

- "DBMS_METADATA_TRANSFORM_PARAMS"
- "DBMS_METADATA_TRANSFORMS"

7.194 DBMS_METADATA_TRANSFORM_PARAMS

DBMS_METADATA_TRANSFORM_PARAMS documents the valid transform parameters for each transform.

Column	Datatype	NULL	Description
OBJECT_TYPE	VARCHAR2(128)	NOT NULL	Object type name
TRANSFORM	VARCHAR2(128)	NOT NULL	Transform name
PARAM	VARCHAR2(128)	NOT NULL	Parameter name
DATATYPE	VARCHAR2(11)		BOOLEAN, TEXT, NUMBER or UNSPECIFIED
DEFAULT_VAL	VARCHAR2(2000)		Default value of the transform parameter
CLIENT	VARCHAR2(1)		Indicates whether the transform parameter is available to the Data Pump client (Y) or not (N)
API	VARCHAR2(1)		Indicates whether the transform parameter is available to the Data Pump API (Y) or not (N)
DESCRIPTION	VARCHAR2(4000)		Description of the transform parameter

See Also:

- "DBMS_METADATA_PARSE_ITEMS"
- "DBMS_METADATA_TRANSFORMS"

7.195 DBMS_METADATA_TRANSFORMS

DBMS_METADATA_TRANSFORMS documents the valid Oracle-supplied transforms.

Column	Datatype	NULL	Description
OBJECT_TYPE	VARCHAR2(128)	NOT NULL	Object type name
TRANSFORM	VARCHAR2(128)	NOT NULL	Transform name
INPUT_TYPE	VARCHAR2(24)		Type of input document

Column	Datatype	NULL	Description
OUTPUT_TYPE	VARCHAR2(24)		Type of output document
DESCRIPTION	VARCHAR2(71)		Description of the transform

> **See Also:**
>
> - "DBMS_METADATA_PARSE_ITEMS"
> - "DBMS_METADATA_TRANSFORM_PARAMS"

7.196 DEPTREE

This view, created by `utldtree.sql`, contains information on the object dependency tree.

For user `SYS`, this view displays shared cursors (and only shared cursors) that depend on the object. For all other users, it displays objects other than shared cursors. Other users can access `SYS.DEPTREE` for information on shared cursors.

Column	Datatype	NULL	Description
NESTED_LEVEL	NUMBER		Nesting level in the dependency tree
TYPE	VARCHAR2(23)		Object type
SCHEMA	VARCHAR2(128)		Object schema
NAME	VARCHAR2(1002)		Object name
SEQ#	NUMBER		Sequence number in the dependency tree. Used for ordering queries. **See Also:** "IDEPTREE"

7.197 DICT

`DICT` is a synonym for `DICTIONARY`.

> **See Also:**
>
> "DICTIONARY"

7.198 DICT_COLUMNS

`DICT_COLUMNS` contains descriptions of columns in data dictionary tables and views.

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2(128)		Name of the object that contains the column
COLUMN_NAME	VARCHAR2(128)		Name of the column
COMMENTS	VARCHAR2(4000)		Text comment on the column

7.199 DICTIONARY

DICTIONARY contains descriptions of data dictionary tables and views.

Column	Datatype	NULL	Description
TABLE_NAME	VARCHAR2(128)		Name of the object
COMMENTS	VARCHAR2(4000)		Text comment on the object

7.200 DICTIONARY_CREDENTIALS_ENCRYPT

DICTIONARY_CREDENTIALS_ENCRYPT indicates whether encryption of dictionary credentials is enforced or not. You can encrypt sensitive credential information, such as passwords that are stored in the data dictionary.

Column	Datatype	NULL	Description
ENFORCEMENT	VARCHAR2(8)		Enforcement status for encryption of dictionary credentials. Possible values: • ENABLED: Encryption of dictionary credentials is enforced • DISABLED: Encryption of dictionary credentials is not enforced

See Also:

Oracle Database Security Guide for information about encrypting sensitive credential information in the data dictionary

7.201 DM_USER_MODELS

DM_USER_MODELS displays information about the models in the user's schema.

Column	Datatype	NULL	Description
NAME	VARCHAR2(128)	NOT NULL	Name of the model

Column	Datatype	NULL	Description
FUNCTION_NAME	VARCHAR2(30)		Model function: • association - Association is a descriptive mining function. An association model identifies relationships and the probability of their occurrence within a data set. • attribute_importance - Attribute Importance is a predictive mining function. An attribute importance model identifies the relative importance of an attribute in predicting a given outcome. • classification - Classification is a predictive mining function. A classification model uses historical data to predict new discrete or categorical data. The classification function can also be used for anomaly detection. In this case, the SVM algorithm with a null target is used (One-Class SVM). • clustering - Clustering is a descriptive mining function. A clustering model identifies natural groupings within a data set. • feature_extraction - Feature Extraction is a descriptive mining function. A feature extraction model creates an optimized data set on which to base a model. • regression - Regression is a predictive mining function. A regression model uses historical data to predict new continuous, numeric data.

Column	Datatype	NULL	Description
ALGORITHM_NAME	VARCHAR2(30)		Algorithm used by the model: • algo_name - Setting that specifies the algorithm used by the model. • asso_max_rule_length - Setting that specifies the maximum length of a rule used by an association model. • asso_min_confidence - Setting that specifies the minimum confidence for an association model. • asso_min_support - Setting that specifies the minimum support for an association model. • clas_cost_table_name - Setting that specifies the name of the cost matrix table for a classification model. • clas_priors_table_name - Setting that specifies the name of the prior probability table for NB and ABN models. Decision Tree is the only classification algorithm that does not use priors. For SVM classification models, this setting specifies the name of a table of weights. • clus_num_clusters - Setting that specifies the number of clusters for a clustering model. • feat_num_features - Setting that specifies the number of features for a feature selection model.
CREATION_DATE	DATE	NOT NULL	Date on which the model was created
BUILD_DURATION	NUMBER		Duration of the model build process
TARGET_ATTRIBUTE	VARCHAR2(128)		Attribute designated as the target of a classification model
MODEL_SIZE	NUMBER		Size of the model (in megabytes)

7.202 DOCUMENT_LINKS

DOCUMENT_LINKS provides system information about Oracle XML DB document links in Oracle XML DB Repository documents.

When an XML document that includes XLink or XInclude links is added to the repository, these links can be mapped to document links, which are tracked using view DOCUMENT_LINKS.

Column	Datatype	NULL	Description
SOURCE_ID	RAW(16)		The source resource OID
TARGET_ID	RAW(16)		The target resource OID
TARGET_PATH	VARCHAR2(4000)		This column is always NULL. It is reserved for future use.
LINK_TYPE	VARCHAR2(8)		The document link type: Hard or Weak
LINK_FORM	VARCHAR2(8)		Whether the original link was of form XLink or XInclude

Column	Datatype	NULL	Description
SOURCE_TYPE	VARCHAR2(17)		Whether the link is contained in Resource Content or Resource Metadata

> **Note:**
>
> Oracle XML DB Repository is deprecated in Oracle Database 23ai. Oracle recommends that you replace any functionality used in Oracle XML DB Repository with alternative technologies.

> **See Also:**
>
> *Oracle XML DB Developer's Guide* for information about using this view

7.203 ERROR_SIZE

ERROR_SIZE is accessed to create DBA_OBJECT_SIZE and USER_OBJECT_SIZE.

> **See Also:**
>
> - "DBA_OBJECT_SIZE"
> - "USER_OBJECT_SIZE"

7.204 EXCEPTIONS

EXCEPTIONS contains information on violations of integrity constraints. This table is created by the utlexcpt.sql script.

Column	Datatype	NULL	Description
ROW_ID	ROWID		Row that caused the violation
OWNER	VARCHAR2(128)		Owner of the table
TABLE_NAME	VARCHAR2(128)		Name of the table
CONSTRAINT	VARCHAR2(128)		Integrity constraint that was violated

7.205 FLASHBACK_TRANSACTION_QUERY

FLASHBACK_TRANSACTION_QUERY displays information about all flashback transaction queries in the database.

The database must have at least minimal supplemental logging enabled to avoid unpredictable behavior.

Column	Datatype	NULL	Description
XID	RAW(8)		Transaction identifier
START_SCN	NUMBER		Transaction start system change number (SCN)
START_TIMESTAMP	DATE		Transaction start timestamp
COMMIT_SCN	NUMBER		Transaction commit system change number; NULL for active transactions
COMMIT_TIMESTAMP	DATE		Transaction commit timestamp; NULL for active transactions
LOGON_USER	VARCHAR2(128)		Logon user for the transaction
UNDO_CHANGE#	NUMBER		Undo system change number (1 or higher)
OPERATION	VARCHAR2(32)		Forward-going DML operation performed by the transaction: • D - Delete • I - Insert • U - Update • B • UNKNOWN
TABLE_NAME	VARCHAR2(256)		Name of the table to which the DML applies
TABLE_OWNER	VARCHAR2(386)		Owner of the table to which the DML applies
ROW_ID	VARCHAR2(19)		Rowid of the row that was modified by the DML
UNDO_SQL	VARCHAR2(4000)		SQL to undo the DML indicated by OPERATION

See Also:

Oracle Database Utilities for information on how to enable minimal supplemental logging

7.206 GLOBAL_CONTEXT

GLOBAL_CONTEXT displays the values of global context attributes, which are accessible for the current session, based on the CLIENT_IDENTIFIER value.

GLOBAL_CONTEXT is similar to SESSION_CONTEXT, which lists the values of session (or local) context attributes set under the current session.

Column	Datatype	NULL	Description
NAMESPACE	VARCHAR2(31)		Namespace of the globally accessible context
ATTRIBUTE	VARCHAR2(31)		Attribute of the globally accessible context
VALUE	VARCHAR2(4000)		Value of the attribute of the globally accessible context
USERNAME	VARCHAR2(31)		Username for which globally accessible context value is applicable
CLIENT_IDENTIFIER	VARCHAR2(65)		Client identifier of the globally accessible context

See Also:

- "SESSION_CONTEXT"
- *Oracle Database Security Guide* for more information about using global application contexts

7.207 GLOBAL_NAME

GLOBAL_NAME contains one row that displays the global name of the current database.

Column	Datatype	NULL	Description
GLOBAL_NAME	VARCHAR2(4000)		Global name of the database

7.208 HS_ALL_CAPS

HS_ALL_CAPS contains information about all of the capabilities (that is, features) associated with non-Oracle (FDS) data stores.

Column	Datatype	NULL	Description
CAP_NUMBER	NUMBER		Capability number
CONTEXT	NUMBER		Context in which this capability is applicable
TRANSLATION	VARCHAR2(255)		Valid for functions; contains translation to FDS dialect
ADDITIONAL_INFO	NUMBER		Flag for internal use
FDS_CLASS_NAME	VARCHAR2(30)		Name of the FDS Class
FDS_INST_NAME	VARCHAR2(30)		Name of the FDS instance

7.209 HS_ALL_DD

HS_ALL_DD contains data dictionary information about non-Oracle (FDS) data stores.

Column	Datatype	NULL	Description
DD_TABLE_NAME	VARCHAR2(128)		Data dictionary table name
TRANSLATION_TYPE	CHAR(1)		T = Translation, M = Mimic
TRANSLATION_TEXT	VARCHAR2(4000)		SQL statement containing the mapping
FDS_CLASS_NAME	VARCHAR2(30)		Name of the FDS Class
FDS_INST_NAME	VARCHAR2(30)		Name of the FDS instance
DD_TABLE_DESC	VARCHAR2(255)		Description of the Oracle data dictionary table

7.210 HS_ALL_INITS

HS_ALL_INITS contains initialization parameter information about non-Oracle (FDS) data stores.

Column	Datatype	NULL	Description
INIT_VALUE_NAME	VARCHAR2(64)		Name of the initialization parameter
INIT_VALUE	VARCHAR2(255)		Value of the initialization parameter
INIT_VALUE_TYPE	VARCHAR2(1)		Environment variable (T or F). T means this is an environment variable; F means do not set as an environment variable
FDS_CLASS_NAME	VARCHAR2(30)		Name of the FDS Class
FDS_INST_NAME	VARCHAR2(30)		Name of the FDS instance

7.211 HS_BASE_CAPS

HS_BASE_CAPS contains information about base capability (that is, base features) of the non-Oracle (FDS) data store.

Column	Datatype	NULL	Description
CAP_NUMBER	NUMBER	NOT NULL	Capability number
CAP_DESCRIPTION	VARCHAR2(255)		Description of the capability

7.212 HS_BASE_DD

HS_BASE_DD displays information from the base data dictionary translation table.

Column	Datatype	NULL	Description
DD_TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the Oracle data dictionary table
DD_TABLE_DESC	VARCHAR2(255)		Description of the Oracle data dictionary table
DD_TABLE_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

7.213 HS_CLASS_CAPS

HS_CLASS_CAPS contains information about the class-specific (driver) capabilities belonging to the non-Oracle (FDS) data store.

Column	Datatype	NULL	Description
CAP_NUMBER	NUMBER	NOT NULL	Capability number
CAP_DESCRIPTION	VARCHAR2(255)		Capability description
CONTEXT	NUMBER		Flag indicating the context in which the capability is enabled
TRANSLATION	VARCHAR2(255)		Valid for functions; contains translation to FDS dialect
ADDITIONAL_INFO	NUMBER		Additional flags for internal use
FDS_CLASS_NAME	VARCHAR2(30)	NOT NULL	Name of the FDS Class
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

7.214 HS_CLASS_DD

HS_CLASS_DD displays information from the non-Oracle data store (FDS) class-specific data dictionary translations.

Column	Datatype	NULL	Description
DD_TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the Oracle data dictionary table
DD_TABLE_DESC	VARCHAR2(255)		Description of the Oracle data dictionary table
TRANSLATION_TYPE	CHAR(1)	NOT NULL	T = Translation, M = Mimic
TRANSLATION_TEXT	VARCHAR2(4000)		SQL statement containing the mapping
FDS_CLASS_NAME	VARCHAR2(30)	NOT NULL	Name of the FDS Class
DD_TABLE_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

7.215 HS_CLASS_INIT

HS_CLASS_INIT displays information about the non-Oracle (FDS) class-specific initialization parameters.

Column	Datatype	NULL	Description
INIT_VALUE_NAME	VARCHAR2(64)	NOT NULL	Name of the initialization parameter
INIT_VALUE	VARCHAR2(255)	NOT NULL	Value of the initialization parameter
INIT_VALUE_TYPE	VARCHAR2(1)	NOT NULL	Environment variable (T or F). T means this is an environment variable; F means do not set as an environment variable

Column	Datatype	NULL	Description
FDS_CLASS_NAME	VARCHAR2(30)	NOT NULL	Name of the FDS Class
FDS_CLASS_INIT_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

7.216 HS_FDS_CLASS

HS_FDS_CLASS contains information about legal non-Oracle (FDS) classes.

Column	Datatype	NULL	Description
FDS_CLASS_NAME	VARCHAR2(30)	NOT NULL	Name of the FDS class (for example, ODBC, DB2)
FDS_CLASS _COMMENTS	VARCHAR2(255)		Text description of the non-Oracle class
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

7.217 HS_FDS_INST

HS_FDS_INST contains information about non-Oracle (FDS) instances.

Column	Datatype	NULL	Description
FDS_INST_NAME	VARCHAR2(30)	NOT NULL	Name of the FDS instance
FDS_INST_COMMENTS	VARCHAR2(255)		Text description of the non-Oracle instance
FDS_CLASS_NAME	VARCHAR2(30)	NOT NULL	Name of the FDS class
FDS_INST_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

7.218 HS_INST_CAPS

HS_INST_CAPS contains information about instance-specific capabilities (that is, features).

Column	Datatype	NULL	Description
CAP_NUMBER	NUMBER	NOT NULL	Capability number
CAP_DESCRIPTION	VARCHAR2(255)		Capability description
CONTEXT	NUMBER		Context in which this capability is applicable
TRANSLATION	VARCHAR2(255)		Valid for functions; contains translation to FDS dialect
ADDITIONAL_INFO	NUMBER		Additional flags for internal use
FDS_CLASS_NAME	VARCHAR2(30)	NOT NULL	Name of the FDS class (for example, ODBC, DB2)
FDS_INST_NAME	VARCHAR2(30)	NOT NULL	Name of the FDS instance

Column	Datatype	NULL	Description
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_INST_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

7.219 HS_INST_DD

HS_INST_DD displays information from the non-Oracle (FDS) instance-specific data dictionary translations.

Column	Datatype	NULL	Description
DD_TABLE_NAME	VARCHAR2(128)	NOT NULL	Name of the Oracle data dictionary table
DD_TABLE_DESC	VARCHAR2(255)		Description of the Oracle data dictionary table
TRANSLATION_TYPE	CHAR(1)	NOT NULL	T = Translation, M = Mimic
TRANSLATION_TEXT	VARCHAR2(4000)		SQL statement containing the mapping
FDS_CLASS_NAME	VARCHAR2(30)	NOT NULL	Name of the FDS class (for example, ODBC, DB2)
FDS_INST_NAME	VARCHAR2(30)	NOT NULL	Name of the FDS instance
DD_TABLE_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_INST_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

7.220 HS_INST_INIT

HS_INST_INIT contains information about the non-Oracle (FDS) instance-specific initialization parameters.

Column	Datatype	NULL	Description
INIT_VALUE_NAME	VARCHAR2(64)	NOT NULL	Name of the initialization parameter
INIT_VALUE	VARCHAR2(255)	NOT NULL	Value of the initialization parameter
INIT_VALUE_TYPE	VARCHAR2(1)	NOT NULL	Environment variable (T or F). T means this is an environment variable; F means do not set as an environment variable
FDS_CLASS_NAME	VARCHAR2(30)	NOT NULL	Name of the FDS class (for example: ODBC, DB2)
FDS_INST_NAME	VARCHAR2(30)	NOT NULL	Name of the FDS instance
FDS_INST_INIT_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_CLASS_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)
FDS_INST_ID	NUMBER	NOT NULL	Sequence: a counter that is incremented for every row inserted (used internally)

7.221 IDEPTREE

This view, created by `utldtree.sql`, lists the indented dependency tree. It is a pre-sorted, pretty-print version of `DEPTREE`.

Column	Datatype	NULL	Description
`NESTED_LEVEL`	`NUMBER`		Nesting level in the dependency tree
`TYPE`	`VARCHAR2(23)`		Object type
`OWNER`	`VARCHAR2(28)`		Object schema
`NAME`	`VARCHAR2(1002)`		Object name

7.222 IND

`IND` is a synonym for `USER_INDEXES`.

> **See Also:**
>
> "USER_INDEXES"

7.223 INDEX_HISTOGRAM

`INDEX_HISTOGRAM` contains information from the `ANALYZE INDEX ... VALIDATE STRUCTURE` statement.

> **Note:**
>
> The `ANALYZE INDEX ... VALIDATE STRUCTURE OFFLINE` statement must be used to collect statistics.

Column	Datatype	NULL	Description
`REPEAT_COUNT`	`NUMBER`		Number of times that one or more index keys is repeated in the table
`KEYS_WITH_REPEAT_COUNT`	`NUMBER`		Number of index keys that are repeated that many times

7.224 INDEX_STATS

INDEX_STATS stores information from the last ANALYZE INDEX ... VALIDATE STRUCTURE statement.

> **Note:**
>
> The ANALYZE INDEX ... VALIDATE STRUCTURE OFFLINE statement must be used in order to collect statistics

Column	Datatype	NULL	Description
HEIGHT	NUMBER		Height of the B-Tree
BLOCKS	NUMBER	NOT NULL	Blocks allocated to the segment
NAME	VARCHAR2(128)	NOT NULL	Name of the index
PARTITION_NAME	VARCHAR2(128)		Name of the partition of the index which was analyzed. If the index is not partitioned, NULL is returned.
LF_ROWS	NUMBER		Number of leaf rows (values in the index)
LF_BLKS	NUMBER		Number of leaf blocks in the B-Tree
LF_ROWS_LEN	NUMBER		Sum of the lengths of all the leaf rows
LF_BLK_LEN	NUMBER		Usable space in a leaf block
BR_ROWS	NUMBER		Number of branch rows in the B-Tree
BR_BLKS	NUMBER		Number of branch blocks in the B-Tree
BR_ROWS_LEN	NUMBER		Sum of the lengths of all the branch blocks in the B-Tree
BR_BLK_LEN	NUMBER		Usable space in a branch block
DEL_LF_ROWS	NUMBER		Number of deleted leaf rows in the index
DEL_LF_ROWS_LEN	NUMBER		Total length of all deleted rows in the index
DISTINCT_KEYS	NUMBER		Number of distinct keys in the index (may include rows that have been deleted)
MOST_REPEATED_KEY	NUMBER		How many times the most repeated key is repeated (may include rows that have been deleted)
BTREE_SPACE	NUMBER		Total space currently allocated in the B-Tree
USED_SPACE	NUMBER		Total space that is currently being used in the B-Tree
PCT_USED	NUMBER		Percent of space allocated in the B-Tree that is being used
ROWS_PER_KEY	NUMBER		Average number of rows per distinct key (this figure is calculated without consideration of deleted rows)

Column	Datatype	NULL	Description
BLKS_GETS_PER_ACCESS	NUMBER		Expected number of consistent mode block reads per row, assuming that a randomly chosen row is accessed using the index. Used to calculate the number of consistent reads that will occur during an index scan.
PRE_ROWS	NUMBER		Number of prefix rows (values in the index)
PRE_ROWS_LEN	NUMBER		Sum of lengths of all prefix rows
OPT_CMPR_COUNT	NUMBER		Optimal index compression length
OPT_CMPR_PCTSAVE	NUMBER		Corresponding space savings after an ANALYZE
DEL_LF_CMP_ROWS	NUMBER		Number of deleted rows that are within a compression unit (CU)
PRG_LF_CMP_ROWS	NUMBER		Number of purged rows that are within a CU
LF_CMP_ROWS	NUMBER		Number of rows that are in a CU or prefix compressed
LF_CMP_ROWS_LEN	NUMBER		Sum of lengths of all prefix rows and CUs
LF_UNCMP_ROWS	NUMBER		Number of rows that are neither in a CU nor prefix compressed
LF_UNCMP_ROWS_LEN	NUMBER		Sum of lengths of rows that are neither in a CU nor prefix compressed
LF_SUF_ROWS_LEN	NUMBER		Sum of lengths of suffix rows
LF_CMP_ROWS_UNCMP_LEN	NUMBER		Sum of the uncompressed lengths of rows that are in a CU or prefix compressed
LF_CMP_RECMP_COUNT	NUMBER		Sum of CU recompression counts
LF_CMP_LOCK_VEC_LEN	NUMBER		Sum of CU lock vector lengths
LF_CMP_BLKS	NUMBER		Number of blocks that have a CU or nonzero prefix column count
LF_UNCMP_BLKS	NUMBER		Number of blocks that do not have a CU and have a zero prefix column count
LF_CMP_ADVLO_BLKS	NUMBER		Number of blocks that are enabled for COMPRESS ADVANCED LOW
LF_CMP_ADVHI_BLKS	NUMBER		Number of blocks that are enabled for COMPRESS ADVANCED HIGH

7.225 LOGSTDBY_UNSUPPORTED_TABLES

LOGSTDBY_UNSUPPORTED_TABLES is a synonym for DBA_LOGSTDBY_UNSUPPORTED_TABLE.

See Also:

"DBA_LOGSTDBY_UNSUPPORTED_TABLE"

7.226 MAP_OBJECT

MAP_OBJECT is a global temporary table that displays the hierarchical arrangement of storage containers for objects. Each row in the table represents a level in the hierarchy.

Column	Datatype	NULL	Description
OBJECT_NAME	VARCHAR2(2000)		Name of the object
OBJECT_OWNER	VARCHAR2(2000)		Owner of the object
OBJECT_TYPE	VARCHAR2(2000)		Object type
FILE_MAP_IDX	NUMBER		File index (corresponds to FILE_MAP_IDX in V$MAP_FILE)
DEPTH	NUMBER		Element depth within the I/O stack
ELEM_IDX	NUMBER		Index corresponding to the element
CU_SIZE	NUMBER		Contiguous set of logical blocks of the file (in HKB units) that is resident contiguously on the element
STRIDE	NUMBER		Number of HKB between contiguous units (CU) in the file that are contiguous on this element. Used in RAID5 and striped files.
NUM_CU	NUMBER		Number of contiguous units that are adjacent to each other on this element that are separated by STRIDE HKB in the file. In RAID5, the number of contiguous units also include the parity stripes.
ELEM_OFFSET	NUMBER		Element offset (in HKB units)
FILE_OFFSET	NUMBER		Offset (in HKB units) from the start of the file to the first byte of the contiguous units
DATA_TYPE	VARCHAR2(2000)		Data type (DATA, PARITY, or DATA AND PARITY)
PARITY_POS	NUMBER		Position of the parity. Only for RAID5. This field is needed to distinguish the parity from the data part.
PARITY_PERIOD	NUMBER		Parity period. Only for RAID5.

7.227 NLS_DATABASE_PARAMETERS

NLS_DATABASE_PARAMETERS lists permanent NLS parameters of the database.

Column	Datatype	NULL	Description
PARAMETER	VARCHAR2(128)		Parameter name
VALUE	VARCHAR2(64)		Parameter value

7.228 NLS_INSTANCE_PARAMETERS

NLS_INSTANCE_PARAMETERS lists NLS parameters of the instance.

Column	Datatype	NULL	Description
PARAMETER	VARCHAR2(30)		Parameter name
VALUE	VARCHAR2(64)		Parameter value

7.229 NLS_SESSION_PARAMETERS

NLS_SESSION_PARAMETERS lists NLS parameters of the user session.

Column	Datatype	NULL	Description
PARAMETER	VARCHAR2(30)		Parameter name
VALUE	VARCHAR2(64)		Parameter value

7.230 OBJ

OBJ is a synonym for USER_OBJECTS.

> **See Also:**
>
> "USER_OBJECTS"

7.231 PATH_VIEW

PATH_VIEW contains one row for each unique path to access a resource in Oracle XML DB Repository.

Column	Datatype	NULL	Description
PATH	VARCHAR2(1024)		An (absolute) path to repository resource RES
RES	XMLTYPE(XMLSchema "http://xmlns.oracle.com/xdb/XDBResource.xsd" Element "Resource")		The resource referred to by the PATH column
LINK	XMLTYPE		Link property
RESID	RAW(16)		Resource OID

> **Note:**
>
> Oracle XML DB Repository is deprecated in Oracle Database 23ai. Oracle recommends that you replace any functionality used in Oracle XML DB Repository with alternative technologies.

> **See Also:**
>
> *Oracle XML DB Developer's Guide* for information about using this view

7.232 PDB_ALERTS

`PDB_ALERTS` contains descriptions of reasons for PDB alerts.

Column	Datatype	NULL	Description
`TIME`	`TIMESTAMP(6)`	`NOT NULL`	Time when the violation happened
`NAME`	`VARCHAR2(128)`	`NOT NULL`	A name of a PDB or non-CDB to which this record applies
`CAUSE_NO`	`NUMBER`	`NOT NULL`	Number identifying a specific reason for a PDB alert
`TYPE_NO`	`NUMBER`	`NOT NULL`	Type of the violation
`ERROR`	`NUMBER`		Oracle error, if any, for this violation
`LINE`	`NUMBER`	`NOT NULL`	Line number for the violation message
`MESSAGE`	`VARCHAR2(4000)`	`NOT NULL`	Description of the violation
`STATUS`	`NUMBER`		Status of the violation
`ACTION`	`VARCHAR2(4000)`		Actions to take to resolve the violations

7.233 PDB_PLUG_IN_VIOLATIONS

`PDB_PLUG_IN_VIOLATIONS` displays information about incompatibilities between a PDB and the CDB to which it belongs.

This view is also used to display information generated by executing `DBMS_PDB.CHECK_PLUG_COMPATIBILITY`.

Column	Datatype	NULL	Description
`TIME`	`TIMESTAMP(6)`	`NOT NULL`	Time when a violation described by this row was discovered
`NAME`	`VARCHAR2(128)`	`NOT NULL`	The name of an existing PDB or a PDB intended to be created (if a row was entered as a result of running `DBMS_PDB.CHECK_PLUG_COMPATIBILITY`)
`CAUSE`	`VARCHAR2(64)`	`NOT NULL`	Attribute which was being checked
`TYPE`	`VARCHAR2(9)`	`NOT NULL`	`ERROR` or `WARNING`

Column	Datatype	NULL	Description
ERROR_NUMBER	NUMBER		Oracle error number, if any, encountered during a check
LINE	NUMBER	NOT NULL	Used to differentiate between violations which share a cause
MESSAGE	VARCHAR2(4000)	NOT NULL	Description of a violation
STATUS	VARCHAR2(9)		PENDING, RESOLVED, or IGNORE
ACTION	VARCHAR2(4000)		Description of an action to take to correct the violation
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database PL/SQL Packages and Types Reference for more information about the DBMS_PDB package, which provides an interface for examining and manipulating data about PDBs

7.234 PLAN_TABLE

PLAN_TABLE is automatically created as a global temporary table to hold the output of an EXPLAIN PLAN statement for all users.

PLAN_TABLE is the default sample output table into which the EXPLAIN PLAN statement inserts rows describing execution plans.

While a PLAN_TABLE table is automatically set up for each user, you can use the SQL script utlxplan.sql to manually create a local PLAN_TABLE in your schema.

Column	Datatype	NULL	Description
STATEMENT_ID	VARCHAR2(30)		Value of the optional STATEMENT_ID parameter specified in the EXPLAIN PLAN statement
PLAN_ID	NUMBER		Unique identifier of a plan in the database
TIMESTAMP	DATE		Date and time when the EXPLAIN PLAN statement was generated

Column	Datatype	NULL	Description
REMARKS	VARCHAR2(4000)		Any comment (of up to 4000 bytes) you want to associate with each step of the explained plan. This column is used to indicate whether an outline or SQL Profile was used for the query. If you need to add or change a remark on any row of the PLAN_TABLE, then use the UPDATE statement to modify the rows of the PLAN_TABLE.
OPERATION	VARCHAR2(30)		Name of the internal operation performed in this step. In the first row generated for a statement, the column contains one of the following values: • DELETE STATEMENT • INSERT STATEMENT • SELECT STATEMENT • UPDATE STATEMENT
OPTIONS	VARCHAR2(255)		A variation on the operation described in the OPERATION column
OBJECT_NODE	VARCHAR2(128)		Name of the database link used to reference the object (a table name or view name). For local queries using parallel execution, this column describes the order in which output from operations is consumed.
OBJECT_OWNER	VARCHAR2(128)		Owner of the table or index
OBJECT_NAME	VARCHAR2(128)		Name of the table or index
OBJECT_ALIAS	VARCHAR2(261)		Unique alias of a table or view in a SQL statement. For indexes, it is the object alias of the underlying table.
OBJECT_INSTANCE	NUMBER(38)		Number corresponding to the ordinal position of the object as it appears in the original statement. The numbering proceeds from left to right, outer to inner with respect to the original statement text. View expansion results in unpredictable numbers.
OBJECT_TYPE	VARCHAR2(30)		Modifier that provides descriptive information about the object; for example, NON-UNIQUE for indexes
OPTIMIZER	VARCHAR2(255)		Current mode of the optimizer
SEARCH_COLUMNS	NUMBER		Not currently used
ID	NUMBER(38)		A number assigned to each step in the execution plan
PARENT_ID	NUMBER(38)		ID of the next execution step that operates on the output of the ID step
DEPTH	NUMBER(38)		Depth of the operation in the row source tree that the plan represents. The value can be used for indenting the rows in a plan table report.
POSITION	NUMBER(38)		For the first row of output, this indicates the optimizer's estimated cost of executing the statement. For the other rows, it indicates the position relative to the other children of the same parent.

Column	Datatype	NULL	Description
COST	NUMBER(38)		Cost of the operation as estimated by the optimizer's query approach. Cost is not determined for table access operations. The value of this column does not have any particular unit of measurement; it is merely a weighted value used to compare costs of execution plans. The value of this column is a function of the CPU_COST and IO_COST columns.
CARDINALITY	NUMBER(38)		Estimate by the query optimization approach of the number of rows accessed by the operation
BYTES	NUMBER(38)		Estimate by the query optimization approach of the number of bytes accessed by the operation
OTHER_TAG	VARCHAR2(255)		Describes the contents of the OTHER column: • SERIAL - Serial execution. Currently, SQL is not loaded in the OTHER column for this case. • SERIAL_FROM_REMOTE - Serial execution at a remote site. • PARALLEL_FROM_SERIAL - Serial execution. Output of step is partitioned or broadcast to parallel execution servers. • PARALLEL_TO_SERIAL - Parallel execution. Output of step is returned to serial query coordinator (QC) process. • PARALLEL_TO_PARALLEL - Parallel execution. Output of step is repartitioned to second set of parallel execution servers. • PARALLEL_COMBINED_WITH_PARENT - Parallel execution; Output of step goes to next step in same parallel process. No interprocess communication to parent. • PARALLEL_COMBINED_WITH_CHILD - Parallel execution. Input of step comes from prior step in same parallel process. No interprocess communication from child.
PARTITION_START	VARCHAR2(255)		Start partition of a range of accessed partitions: • *number* - Start partition has been identified by the SQL compiler, and its partition number is given by *number* • KEY - Start partition will be identified at run time from partitioning key values • ROW LOCATION - Start partition (same as the stop partition) will be computed at run time from the location of each record being retrieved. The record location is obtained from a user-specified ROWID or from a global index. • INVALID - Range of accessed partitions is empty

Column	Datatype	NULL	Description
PARTITION_STOP	VARCHAR2(255)		Stop partition of a range of accessed partitions: • *number* - Stop partition has been identified by the SQL compiler, and its partition number is given by *number* • KEY - Stop partition will be identified at run time from partitioning key values • ROW LOCATION - Stop partition (same as the start partition) will be computed at run time from the location of each record being retrieved. The record location is obtained from a user-specified ROWID or from a global index. • INVALID - Range of accessed partitions is empty
PARTITION_ID	NUMBER(38)		Step that has computed the pair of values of the PARTITION_START and PARTITION_STOP columns
OTHER	LONG		Other information that is specific to the execution step that a user might find useful (see the OTHER_TAG column)
OTHER_XML	CLOB		Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML since multiple pieces of information can be stored there. This includes: • Name of the schema against which the query was parsed • Release number of the Oracle Database that produced the explain plan • Hash value associated with the execution plan • Name (if any) of the outline or the SQL profile used to build the execution plan • Indication of whether or not dynamic statistics were used to produce the plan • The outline data, a set of optimizer hints that can be used to regenerate the same plan • Additional data that describes the relationship between rows in the plan table and subplans of adaptive plans.
DISTRIBUTION	VARCHAR2(30)		Method used to distribute rows from producer query servers to consumer query servers
CPU_COST	NUMBER(38)		CPU cost of the operation as estimated by the query optimizer's approach. The value of this column is proportional to the number of machine cycles required for the operation. For statements that use the rule-based approach, this column is NULL.
IO_COST	NUMBER(38)		I/O cost of the operation as estimated by the query optimizer's approach. The value of this column is proportional to the number of data blocks read by the operation. For statements that use the rule-based approach, this column is NULL.

Column	Datatype	NULL	Description
TEMP_SPACE	NUMBER(38)		Temporary space (in bytes) used by the operation as estimated by the query optimizer's approach. For statements that use the rule-based approach, or for operations that do not use any temporary space, this column is NULL.
ACCESS_PREDICATES	VARCHAR2(4000)		Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.
FILTER_PREDICATES	VARCHAR2(4000)		Predicates used to filter rows before producing them
PROJECTION	VARCHAR2(4000)		Expressions produced by the operation
TIME	NUMBER(38)		Elapsed time (in seconds) of the operation as estimated by query optimization. For statements that use the rule-based approach, this column is NULL.
QBLOCK_NAME	VARCHAR2(128)		Name of the query block (either system-generated or defined by the user with the QB_NAME hint)

7.235 PLUGGABLE_SET_CHECK

PLUGGABLE_SET_CHECK contains pluggable set checks.

Column	Datatype	NULL	Description
OBJ1_OWNER	VARCHAR2(128)		Owner of the object
OBJ1_NAME	VARCHAR2(128)		Object 1
OBJ1_SUBNAME	VARCHAR2(128)		SubObject1Name
OBJ1_TYPE	VARCHAR2(18)		Object Type
TS1_NAME	VARCHAR2(30)		Tablespace containing Object 1
OBJ2_NAME	VARCHAR2(128)		Object Name
OBJ2_SUBNAME	VARCHAR2(128)		SubObject2Name
OBJ2_TYPE	VARCHAR2(18)		Object Type
OBJ2_OWNER	VARCHAR2(128)		Object owner of second object
TS2_NAME	VARCHAR2(30)		Tablespace containing Object 1
CONSTRAINT_NAME	VARCHAR2(128)		Name of dependent constraint
REASON	VARCHAR2(86)		Reason for Pluggable check violation
MESG_ID	NUMBER		The message ID

7.236 PRODUCT_COMPONENT_VERSION

PRODUCT_COMPONENT_VERSION contains version and status information for component products.

Column	Datatype	NULL	Description
PRODUCT	VARCHAR2(80)		Product name
VERSION	VARCHAR2(80)		Version number
VERSION_FULL	VARCHAR2(160)		The version number with the new Oracle Database version scheme introduced in Oracle Database 18c. The version number is displayed only for the database component. All other components return a null value for this column.
STATUS	VARCHAR2(80)		Status of release

7.237 PROXY_USERS

PROXY_USERS describes the list of proxy users and the clients on whose behalf they can act.

Column	Datatype	NULL	Description
PROXY	VARCHAR2(128)	NOT NULL	Name of a proxy user
CLIENT	VARCHAR2(128)	NOT NULL	Name of the client user who the proxy user can act as
AUTHENTICATION	VARCHAR2(3)		Indicates whether the proxy is required to supply the client's authentication credentials (YES) or not (NO)
FLAGS	VARCHAR2(35)		Flags associated with the proxy/client pair: • PROXY MAY ACTIVATE ALL CLIENT ROLES • NO CLIENT ROLES MAY BE ACTIVATED • PROXY MAY ACTIVATE ROLE • PROXY MAY ACTIVATE ALL CLIENT ROLES • PROXY MAY NOT ACTIVATE ROLE

7.238 PSTUBTBL

This table contains information on stubs generated by the PSTUB utility so that an Oracle Forms 3.0 client can call stored procedures in Oracle Database.

> **Note:**
>
> The contents of this table are intended only for use by the PSTUB utility.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Schema part of the identifier of a stored procedure
DBNAME	VARCHAR2(128)		Database link part of the identifier of a stored procedure
LUN	VARCHAR2(128)		Library unit name part of the identifier of a stored procedure

Column	Datatype	NULL	Description
LUTYPE	VARCHAR2(3)		Type of the stored procedure
LINENO	NUMBER		Line number of the stub
LINE	VARCHAR2(1800)		Text of the stub

7.239 PUBLIC_DEPENDENCY

PUBLIC_DEPENDENCY lists dependencies to and from objects, by object number.

Column	Datatype	NULL	Description
OBJECT_ID	NUMBER	NOT NULL	Object number
REFERENCED_OBJECT_ID	NUMBER	NOT NULL	Referenced object (the parent object)

7.240 PUBLICSYN

PUBLICSYN contains information on public synonyms.

Column	Datatype	NULL	Description
SNAME	VARCHAR2(128)		Name of the synonym
CREATOR	VARCHAR2(128)		Owner of the synonym
TNAME	VARCHAR2(128)		Table of which this is a synonym
DATABASE	VARCHAR2(128)		Database in which the table resides
TABTYPE	VARCHAR2(10)		Type of table

7.241 QUEUE_PRIVILEGES

QUEUE_PRIVILEGES shows all Advanced Queuing object privileges granted to the session.

Column	Datatype	NULL	Description
GRANTEE	VARCHAR2(128)	NOT NULL	Name of the user or role to whom access was granted
OWNER	VARCHAR2(128)	NOT NULL	Owner of the object
NAME	VARCHAR2(128)	NOT NULL	Name of the object
GRANTOR	VARCHAR2(128)	NOT NULL	Name of the user who performed the grant
ENQUEUE_PRIVILEGE	NUMBER		Permission to ENQUEUE to the queue
DEQUEUE_PRIVILEGE	NUMBER		Permission to DEQUEUE from the queue

7.242 RECYCLEBIN

RECYCLEBIN is a synonym for USER_RECYCLEBIN.

> **See Also:**
>
> "USER_RECYCLEBIN"

7.243 REDACTION_COLUMNS

REDACTION_COLUMNS describes all redacted columns in the database, giving the owner of the table or view within which the column resides, the object name, the column name, the type of redaction function, the parameters to the redaction function (if any), and an optional description of the redaction policy.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the object that is redacted
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object that is redacted
COLUMN_NAME	VARCHAR2(128)	NOT NULL	Name of the column that is redacted
FUNCTION_TYPE	VARCHAR2(27)		Redaction function for this column
FUNCTION_PARAMETERS	VARCHAR2(1000)		Redaction function_parameters for this column
REGEXP_PATTERN	VARCHAR2(512)		Regular expression pattern to search for
REGEXP_REPLACE_STRING	VARCHAR2(4000)		Replacement string (up to 4000 characters in length) with up to 500 back-references to subexpressions in the form \n, (where n is a number from 1 to 9)
REGEXP_POSITION	NUMBER		Integer counting from 1, giving the position where the search should begin
REGEXP_OCCURRENCE	NUMBER		Either 0 (to replace all occurrences of the match), or a positive integer n (to replace the nth occurrence of the match)
REGEXP_MATCH_PARAMETER	VARCHAR2(10)		To change the default matching behavior, possible values are a combination of i, c, n, m, and x. See the documentation of the match_parameter in the REGEXP_REPLACE section of the *Oracle Database SQL Language Reference*.
COLUMN_DESCRIPTION	VARCHAR2(4000)		User-provided description of the redaction function that is performed on the column. For example, for a Social Security Number column, the description might be: "redact SSN to XXX-XX-(last 4 digits)".

> **See Also:**
>
> *Oracle Database Advanced Security Guide* for more information about Oracle Data Redaction

7.244 REDACTION_EXPRESSIONS

REDACTION_EXPRESSIONS shows all the Data Redaction named Policy Expressions in the database.

Column	Datatype	NULL	Description
POLICY_EXPRESSION_NAME	VARCHAR2(256)		Customer-specified name of the named Policy Expression
EXPRESSION	VARCHAR2(4000)		The SQL expression defined for this Data Redaction named Policy Expression
OBJECT_OWNER	VARCHAR2(128)		Owner of the table or view which this named Policy Expression is associated with
OBJECT_NAME	VARCHAR2(128)		Name of the table or view which this named Policy Expression is associated with
COLUMN_NAME	VARCHAR2(128)		Name of the column which this named Policy Expression is associated with
POLICY_EXPRESSION_DESCRIPTION	VARCHAR2(4000)		Description of this named Policy Expression

7.245 REDACTION_POLICIES

REDACTION_POLICIES displays all redaction policies in the database.

Column	Datatype	NULL	Description
OBJECT_OWNER	VARCHAR2(128)	NOT NULL	Owner of the object with the policy
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the object with the policy
POLICY_NAME	VARCHAR2(128)	NOT NULL	Name of the policy
EXPRESSION	VARCHAR2(4000)	NOT NULL	Expression for this policy
ENABLE	VARCHAR2(7)		Indicates whether the policy is enabled (YES) or not (NO)
POLICY_DESCRIPTION	VARCHAR2(4000)		Description of the policy

> **See Also:**
>
> *Oracle Database Advanced Security Guide* for more information about Oracle Data Redaction

7.246 REDACTION_VALUES_FOR_TYPE_FULL

REDACTION_VALUES_FOR_TYPE_FULL shows all of the current values for full redaction.

For example, if a redaction policy is applied to a column of type BINARY_DOUBLE and the redaction type is full redaction, that column will be redacted with the value shown in the BINARY_DOUBLE_VALUE column of this view.

Column	Datatype	NULL	Description
NUMBER_VALUE	NUMBER	NOT NULL	Redaction result for full redaction on NUMBER columns
BINARY_FLOAT_VALUE	BINARY_FLOAT	NOT NULL	Redaction result for full redaction on BINARY_FLOAT columns
BINARY_DOUBLE_VALUE	BINARY_DOUBLE	NOT NULL	Redaction result for full redaction on BINARY_DOUBLE columns
CHAR_VALUE	VARCHAR2(1)		Redaction result for full redaction on CHAR columns
VARCHAR_VALUE	VARCHAR2(1)		Redaction result for full redaction on VARCHAR2 columns
NCHAR_VALUE	NCHAR(1)		Redaction result for full redaction on NCHAR columns
NVARCHAR_VALUE	NVARCHAR2(1)		Redaction result for full redaction on NVARCHAR2 columns
DATE_VALUE	DATE	NOT NULL	Redaction result for full redaction on DATE columns
TIMESTAMP_VALUE	TIMESTAMP(6)	NOT NULL	Redaction result for full redaction on TIMESTAMP columns
TIMESTAMP_WITH_TIME_ZONE_VALUE	TIMESTAMP(6) WITH TIME ZONE	NOT NULL	Redaction result for full redaction on TIMESTAMP WITH TIME ZONE columns
BLOB_VALUE	BLOB		Redaction result for full redaction on BLOB columns
CLOB_VALUE	CLOB		Redaction result for full redaction on CLOB columns
NCLOB_VALUE	NCLOB		Redaction result for full redaction on NCLOB columns

See Also:

Oracle Database Advanced Security Guide for more information about Oracle Data Redaction

7.247 REPORT_COMPONENTS

REPORT_COMPONENTS displays metadata about different database components offering reports in XML, HTML, or Text formats.

Reports are first generated in XML and can then be translated into HTML or Text formats, for supported report types. Each component generates one or more reports containing different types of content. You can request reports using the component's own PL/SQL interface (for example, DBMS_SQLTUNE for SQL Tuning Advisor).

Column	Datatype	NULL	Description
COMPONENT_ID	NUMBER	NOT NULL	ID number of the database component building the report
COMPONENT_NAME	VARCHAR2(128)	NOT NULL	Name of the database component building the report (for example, sqltune for SQL Tuning Advisor)
COMPONENT_DESCRIPTION	VARCHAR2(256)		Component description
REPORT_ID	NUMBER	NOT NULL	ID number of the report type
REPORT_NAME	VARCHAR2(128)	NOT NULL	Name of the report type
REPORT_DESCRIPTION	VARCHAR2(256)		Description of the report type
SCHEMA_FILENAME	VARCHAR2(500)		Filename of the XML schema for the report (optional)
SCHEMA_DATA	XMLTYPE		XML schema for this report (optional)

See Also:

Oracle Database PL/SQL Packages and Types Reference for more information about the DBMS_SQLTUNE package

7.248 REPORT_FILES

REPORT_FILES displays data for all of the XML schema and XSLT files associated with reports for a given component.

Column	Datatype	NULL	Description
FILENAME	VARCHAR2(500)	NOT NULL	Name of the XSLT/XML schema file
DATA	XMLTYPE		XSLT/XML schema data

7.249 REPORT_FORMATS

REPORT_FORMATS displays metadata about the different output formats supported for reports.

Some reports are generated in XML only, in which case no data will appear in this view. When reports support HTML or Text formats (for example, the SQL Performance Analyzer reports), metadata about the format will appear in this view.

Column	Datatype	NULL	Description
COMPONENT_ID	NUMBER	NOT NULL	ID number of the database component building the report
COMPONENT_NAME	VARCHAR2(128)	NOT NULL	Name of the database component building the report (for example, sqltune for SQL Tuning Advisor)
REPORT_ID	NUMBER	NOT NULL	ID number of the report type
REPORT_NAME	VARCHAR2(128)	NOT NULL	Name of the report type
FORMAT_NAME	VARCHAR2(128)	NOT NULL	Name of the report format
DESCRIPTION	VARCHAR2(256)		Description of the report format
TYPE	VARCHAR2(6)		Format type: • XSLT - Reports generated by applying an XSLT style sheet to XML data (for example, HTML reports) • Text - Reports generated by first applying an XSLT style sheet to convert XML data to HTML, and then converting the HTML to formatted Text using the internal report HTML-to-text translation engine. • Custom - Custom formats implemented natively by report clients
XSLT_FILENAME	VARCHAR2(500)		Name of the XSLT used for this format (XSLT and Text format types only)
XSLT_DATA	XMLTYPE		XSLT data (XSLT and Text format types only)
TEXT_LINESIZE	NUMBER		Maximum line size of the formatted text report (Text format types only)

7.250 RESOURCE_COST

RESOURCE_COST lists the cost for each resource.

Column	Datatype	NULL	Description
RESOURCE_NAME	VARCHAR2(32)	NOT NULL	Name of the resource
UNIT_COST	NUMBER	NOT NULL	Cost of the resource

7.251 RESOURCE_MAP

RESOURCE_MAP describes resources. This table can be used to map resource names to resource numbers.

Column	Datatype	NULL	Description
RESOURCE#	NUMBER	NOT NULL	Numeric resource code
TYPE#	NUMBER	NOT NULL	Numeric type code
NAME	VARCHAR2(32)	NOT NULL	Name of the resource

7.252 RESOURCE_VIEW

RESOURCE_VIEW contains one row for each resource in Oracle XML DB Repository.

Column	Datatype	NULL	Description
RES	XMLTYPE(XMLSchema "http://xmlns.oracle.com/xdb/XDBResource.xsd" Element "Resource")		A resource in the repository
ANY_PATH	VARCHAR2(4000)		An (absolute) path to the resource
RESID	RAW(16)		Resource OID, which is a unique handle to the resource

> **Note:**
>
> Oracle XML DB Repository is deprecated in Oracle Database 23ai. Oracle recommends that you replace any functionality used in Oracle XML DB Repository with alternative technologies.

> **See Also:**
>
> *Oracle XML DB Developer's Guide* for information about using this view

7.253 ROLE_ROLE_PRIVS

ROLE_ROLE_PRIVS describes the roles granted to other roles.

Information is provided only about roles to which the user has access.

Column	Datatype	NULL	Description
ROLE	VARCHAR2(128)		Name of the role
GRANTED_ROLE	VARCHAR2(128)		Role that was granted
ADMIN_OPTION	VARCHAR2(3)		Signifies that the role was granted with ADMIN option
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the role was granted commonly (CONTAINER=ALL was used) • NO if the role was granted locally (CONTAINER=ALL was not used)

Column	Datatype	NULL	Description
INHERITED	VARCHAR2(3)		Indicates whether the role grant was inherited from another container (YES) or not (NO)

7.254 ROLE_SCHEMA_PRIVS

ROLE_SCHEMA_PRIVS describes schema privileges granted to roles.

Information is provided only about roles to which the user has access.

Column	Datatype	NULL	Description
ROLE	VARCHAR2(128)		Name of the role
PRIVILEGE	VARCHAR2(40)		Schema privilege granted to the role
SCHEMA	VARCHAR2(128)		Schema on which the privilege was granted
ADMIN_OPTION	VARCHAR2(3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the role grant was inherited from another container (YES) or not (NO)

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

7.255 ROLE_SYS_PRIVS

ROLE_SYS_PRIVS describes system privileges granted to roles.

Information is provided only about roles to which the user has access.

Column	Datatype	NULL	Description
ROLE	VARCHAR2(128)		Name of the role
PRIVILEGE	VARCHAR2(40)		System privilege granted to the role
ADMIN_OPTION	VARCHAR2(3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)

Column	Datatype	NULL	Description
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the role grant was inherited from another container (YES) or not (NO)

7.256 ROLE_SYS_PRIVS_ALL

ROLE_SYS_PRIVS_ALL describes system privileges and schema privileges granted to roles.

Information is provided only about roles to which the user has access.

Column	Datatype	NULL	Description
ROLE	VARCHAR2(128)		Name of the role
PRIVILEGE	VARCHAR2(40)		Privilege granted to the role
SCHEMA	VARCHAR2(128)		Schema on which the privilege was granted For system privileges, the value of this column is null.
ADMIN_OPTION	VARCHAR2(3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the role grant was inherited from another container (YES) or not (NO)

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

7.257 ROLE_TAB_PRIVS

ROLE_TAB_PRIVS describes table privileges granted to roles. Information is provided only about roles to which the user has access.

Column	Datatype	NULL	Description
ROLE	VARCHAR2(128)		Name of the role

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)		Owner of the object
TABLE_NAME	VARCHAR2(128)		Name of the object
COLUMN_NAME	VARCHAR2(128)		Name of the column, if applicable
PRIVILEGE	VARCHAR2(40)		Object privilege granted to the role
GRANTABLE	VARCHAR2(3)		YES if the role was granted with ADMIN OPTION; otherwise NO
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the role grant was inherited from another container (YES) or not (NO)

7.258 SCHEDULER_BATCH_ERRORS

SCHEDULER_BATCH_ERRORS displays the errors caused by each call in the batch after a Scheduler batch call (when the COMMIT_SEMANTICS argument has been set to ABSORB_ERRORS).

Column	Datatype	NULL	Description
ARRAY_INDEX	NUMBER		Index of the job in the batch
OBJECT_TYPE	VARCHAR2(30)		Object type: • JOB • LIGHTWEIGHT JOB • UNKNOWN
OBJECT_NAME	VARCHAR2(100)		Full name of the object (including schema)
ATTR_NAME	VARCHAR2(30)		Name of the attribute being set (if this is a batch set attribute call); NULL otherwise
ERROR_CODE	NUMBER		Top level error code
ERROR_MESSAGE	VARCHAR2(4000)		Complete error stack
ADDITIONAL_INFO	VARCHAR2(4000)		Additional information (currently unused)

7.259 SCHEMA_EXPORT_OBJECTS

SCHEMA_EXPORT_OBJECTS lists simple path names for some of the object types belonging to a Data Pump schema export, which is invoked using the SCHEMAS parameter on the expdp command.

Users of the Data Pump Export and Import utilities can query this view to determine valid values for the EXCLUDE and INCLUDE parameters.

Column	Datatype	NULL	Description
OBJECT_PATH	VARCHAR2(200)	NOT NULL	Simple path name for the object type
COMMENTS	VARCHAR2(2000)		Comment on the object type
NAMED	CHAR(1)		Do objects of this type have names? If yes (Y), then the name can be specified in the optional name_clause on the EXCLUDE and INCLUDE parameters.

See Also:

- "DATABASE_EXPORT_OBJECTS"
- "TABLE_EXPORT_OBJECTS"
- *Oracle Database Utilities* for more information on performing a full Data Pump export using the `expdp` command

7.260 SEQ

`SEQ` is a synonym for `USER_SEQUENCES`.

See Also:

"USER_SEQUENCES"

7.261 SESSION_CONTEXT

`SESSION_CONTEXT` describes the context attributes and their values set for the current session.

Column	Datatype	NULL	Description
NAMESPACE	VARCHAR2(128)		Namespace that the active attribute is in
ATTRIBUTE	VARCHAR2(128)		Name of the active attribute
VALUE	VARCHAR2(4000)		Value of the active attribute

7.262 SESSION_PRIVS

`SESSION_PRIVS` describes the system privileges that are currently available to the user.

Column	Datatype	NULL	Description
PRIVILEGE	VARCHAR2(40)	NOT NULL	Name of the privilege

7.263 SESSION_PRIVS_ALL

SESSION_PRIVS_ALL describes the system privileges and schema privileges that are currently available to the user.

Column	Datatype	NULL	Description
PRIVILEGE	VARCHAR2(40)		Name of the privilege
SCHEMA	VARCHAR2(128)		Schema on which the privilege was granted For system privileges, the value of this column is null.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

7.264 SESSION_SCHEMA_PRIVS

SESSION_SCHEMA_PRIVS describes the schema privileges that are currently available to the user.

Column	Datatype	NULL	Description
PRIVILEGE	VARCHAR2(40)	NOT NULL	Schema privilege
SCHEMA	VARCHAR2(128)	NOT NULL	Schema on which the privilege was granted

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

7.265 SESSION_ROLES

SESSION_ROLES describes the roles that are currently enabled to the user.

Column	Datatype	NULL	Description
ROLE	VARCHAR2(128)	NOT NULL	Name of the role

7.266 SHARD_RAFT_PARAMETERS

SHARD_RAFT_PARAMETERS displays Oracle Globally Distributed Database Raft replication parameters and their values.

This view displays the parameters that are set at the replication unit level on each shard.

Column	Datatype	NULL	Description
ORA_SHARD_ID	NUMBER		Shard identifier
RU_ID	NUMBER		Replication unit (RU) identifier
NAME	VARCHAR2(128)	NOT NULL	Parameter name
VALUE	VARCHAR2(4000)		Parameter value

Note:

This view is available starting with Oracle Database 23ai.

See Also:

Oracle Globally Distributed Database Guide for more information about Raft replication parameters

7.267 SOURCE_SIZE

Oracle accesses this view to create views about object size.

See Also:

"DBA_OBJECT_SIZE" and "USER_OBJECT_SIZE"

7.268 STMT_AUDIT_OPTION_MAP

`STMT_AUDIT_OPTION_MAP` describes auditing option type codes. This table can be used to map auditing option type numbers to type names.

> **Note:**
>
> This view is populated in any Oracle Database where auditing is enabled, regardless of whether pre-Oracle Database 12*c* auditing or unified auditing is enabled for the database.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

> **Note:**
>
> The mapping explained in this view is valid for audit configuration from the `DBA_STMT_AUDIT_OPTS` view only, and such audit configurations can be made when unified auditing is not enabled.

Column	Datatype	NULL	Description
`OPTION#`	`NUMBER`	`NOT NULL`	Numeric auditing option type code
`NAME`	`VARCHAR2(40)`	`NOT NULL`	Name of the type of auditing option
`PROPERTY`	`NUMBER`	`NOT NULL`	Property flag of the auditing option

> **See Also:**
>
> "DBA_STMT_AUDIT_OPTS"

7.269 SYN

`SYN` is a synonym for `USER_SYNONYMS`.

> **See Also:**
>
> "ALL_SYNONYMS"

7.270 SYNONYMS

SYNONYMS is included for compatibility. Oracle recommends that you do not use this view.

7.271 SYS_OBJECTS

SYS_OBJECTS maps object IDs to object types and segment data block addresses.

Column	Datatype	NULL	Description
OBJECT_TYPE	VARCHAR2(18)		Type of the object
OBJECT_TYPE_ID	NUMBER		Type ID of the object
SEGMENT_TYPE_ID	NUMBER		Type of segment: TABLE, CLUSTER, INDEX, ROLLBACK, DEFERRED ROLLBACK, TEMPORARY, CACHE
OBJECT_ID	NUMBER		Object identifier
HEADER_FILE	NUMBER		ID of the file containing the segment header
HEADER_BLOCK	NUMBER		ID of the block containing the segment header
TS_NUMBER	NUMBER		The tablespace number

7.272 SYSCATALOG

SYSCATALOG is included for compatibility.

Oracle recommends that you do not use this view.

7.273 SYSFILES

SYSFILES is included for compatibility.

Oracle recommends that you do not use this view.

7.274 SYSSEGOBJ

SYSSEGOBJ is included for compatibility.

Oracle recommends that you do not use this view.

7.275 SYSTEM_PRIVILEGE_MAP

SYSTEM_PRIVILEGE_MAP describes privilege (auditing option) type codes.

This table can be used to map privilege (auditing option) type numbers to type names.

Column	Datatype	NULL	Description
PRIVILEGE	NUMBER	NOT NULL	Numeric privilege (auditing option) type code

Column	Datatype	NULL	Description
NAME	VARCHAR2(40)	NOT NULL	Name of the type of privilege (auditing option). See *Oracle Database SQL Language Reference* for a list of valid system privileges.
PROPERTY	NUMBER	NOT NULL	Property flag of the privilege (auditing option): • 0 - Indicates a privilege that can be granted with a SQL GRANT statement • 1 - Indicates a privilege that can only be granted using a PL/SQL package

7.276 TAB

TAB is included for compatibility.

Oracle recommends that you do not use this view.

7.277 TABLE_EXPORT_OBJECTS

TABLE_EXPORT_OBJECTS lists simple path names for some of the object types belonging to a Data Pump schema export, which is invoked using the TABLES parameter on the expdp command.

Users of the Data Pump Export and Import utilities can query this view to determine valid values for the EXCLUDE and INCLUDE parameters.

Column	Datatype	NULL	Description
OBJECT_PATH	VARCHAR2(200)	NOT NULL	Simple path name for the object type
COMMENTS	VARCHAR2(2000)		Comment on the object type
NAMED	CHAR(1)		Do objects of this type have names? If yes (Y), then the name can be specified in the optional name_clause on the EXCLUDE and INCLUDE parameters.

See Also:

- "DATABASE_EXPORT_OBJECTS"
- "SCHEMA_EXPORT_OBJECTS"
- *Oracle Database Utilities* for more information on performing a full Data Pump export using the expdp command

7.278 TABLE_PRIVILEGE_MAP

TABLE_PRIVILEGE_MAP describes privilege (auditing option) type codes.

This table can be used to map privilege (auditing option) type numbers to type names.

Column	Datatype	NULL	Description
PRIVILEGE	NUMBER	NOT NULL	Numeric privilege (auditing option) type code
NAME	VARCHAR2(40)	NOT NULL	Name of the type of privilege (auditing option)

7.279 TABQUOTAS

TABQUOTAS is included for compatibility.

Oracle recommends that you do not use this view.

7.280 TABS

TABS is a synonym for USER_TABLES.

> **See Also:**
>
> "USER_TABLES"

7.281 TRUSTED_SERVERS

TRUSTED_SERVERS displays whether a server is trusted or untrusted.

> **Note:**
>
> Enterprise User Security (EUS) is deprecated with Oracle Database 23ai.
>
> Oracle recommends that you migrate to using Centrally Managed Users (CMU). This feature enables you to directly connect with Microsoft Active Directory without an intervening directory service for enterprise user authentication and authorization to the database. If your Oracle Database is in the cloud, you can also choose to move to one of the newer integrations with a cloud identity provider.

Column	Datatype	NULL	Description
TRUST	VARCHAR2(9)		Trustedness of the server listed. Values can be TRUSTED or UNTRUSTED servers which are not listed in the NAME column have opposite trustedness.
NAME	VARCHAR2(128)		Server name. Can be a specific server name or ALL for all servers.

Table 7-2 shows examples of the values returned depending on the status of the servers.

Table 7-2 TRUSTED_SERVERS Values

Condition (If . . .)	TRUSTED column	NAME column
... all servers are trusted	Trusted	ALL
... no servers are trusted	Untrusted	ALL
... all servers except DB1 are trusted	Untrusted	DB1
... all servers except DB1 are untrusted	Trusted	DB1

See Also:

- *Oracle Database PL/SQL Packages and Types Reference*
- *Oracle Database Enterprise User Security Administrator's Guide*

7.282 TS_PITR_CHECK

This view, created by `catpitr.sql`, provides information on any dependencies or restrictions that might prevent tablespace point-in-time recovery from proceeding.

This view applies only to the tablespace point-in-time recovery feature.

Column	Datatype	NULL	Description
OBJ1_OWNER	VARCHAR2(128)		The owner of the object preventing tablespace point-in-time recovery. See the REASON column for details.
OBJ1_NAME	VARCHAR2(128)		The name of the object preventing tablespace point-in-time recovery
OBJ1_SUBNAME	VARCHAR2(128)		Subordinate to OBJ1_NAME
OBJ1_TYPE	VARCHAR2(16)		The object type for the object preventing tablespace point-in-time recovery
TS1_NAME	VARCHAR2(30)		Name of the tablespace containing the object preventing tablespace point-in-time recovery
OBJ2_NAME	VARCHAR2(128)		The name of a second object which may be preventing tablespace point-in-time recovery. If NULL, object 1 is the only object preventing recovery.
OBJ2_SUBNAME	VARCHAR2(128)		Subordinate to OBJ2_NAME
OBJ2_TYPE	VARCHAR2(15)		The object type for the second object (will be NULL if OBJ2_NAME is NULL)
OBJ2_OWNER	VARCHAR2(128)		The owner of the second object (will be NULL if OBJ2_NAME is NULL)
TS2_NAME	VARCHAR2(30)		Name of the tablespace containing second object which may be preventing tablespace point-in-time recovery (-1 indicates not applicable)

Column	Datatype	NULL	Description
CONSTRAINT_NAME	VARCHAR2(128)		Name of the constraint
REASON	VARCHAR2(81)		Reason why tablespace point-in-time recovery cannot proceed

> **See Also:**
>
> *Oracle Database Backup and Recovery User's Guide* for more information about tablespace point-in-time recovery

7.283 TS_PITR_OBJECTS_TO_BE_DROPPED

TS_PITR_OBJECTS_TO_BE_DROPPED lists all objects lost as a result of performing tablespace point-in-time recovery.

This view applies only to the tablespace point-in-time recovery feature.

Column	Datatype	NULL	Description
OWNER	VARCHAR2(128)	NOT NULL	The owner of the object
NAME	VARCHAR2(128)	NOT NULL	The name of the object that will be lost as a result of undergoing tablespace point-in-time recovery
CREATION_TIME	DATE	NOT NULL	Creation timestamp of the object
TABLESPACE_NAME	VARCHAR2(30)		Name of the tablespace containing the object

> **See Also:**
>
> *Oracle Database Backup and Recovery User's Guide* for more information about tablespace point-in-time recovery

7.284 UNI_PLUGGABLE_SET_CHECK

UNI_PLUGGABLE_SET_CHECK contains pluggable check information.

Column	Datatype	NULL	Description
OBJ1_OWNER	VARCHAR2(128)		Owner of object
OBJ1_NAME	VARCHAR2(128)		Object 1
OBJ1_SUBNAME	VARCHAR2(128)		SubObject1Name
OBJ1_TYPE	VARCHAR2(18)		Object Type
TS1_NAME	VARCHAR2(30)		Tablespace containing Object 1
OBJ2_NAME	VARCHAR2(128)		Object Name
OBJ2_SUBNAME	VARCHAR2(128)		SubObject2Name

Column	Datatype	NULL	Description
OBJ2_TYPE	VARCHAR2(18)		Object Type
OBJ2_OWNER	VARCHAR2(128)		Object owner of second object
TS2_NAME	VARCHAR2(30)		Tablespace containing Object 1
CONSTRAINT_NAME	VARCHAR2(128)		Name of dependent constraint
REASON	VARCHAR2(86)		Reason for Pluggable check violation
MESG_ID	NUMBER		The message ID

7.285 UNIFIED_AUDIT_TRAIL

When unified auditing is enabled in Oracle Database, the audit records are populated in this new audit trail.

This view displays audit records in tabular form by retrieving the audit records from the audit trail.

> **Note:**
>
> This view is populated only in an Oracle Database where unified auditing is enabled.
>
> - See *Oracle Database Security Guide* for more information about unified auditing.
> - See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

Column	Datatype	NULL	Description
AUDIT_TYPE	VARCHAR2(64)		Type of auditing: • Database Vault • Datapump • Direct path API • FineGrainedAudit • KACL_AUDIT • Label Security • Protocol • RMAN_AUDIT • SQL Firewall • Standard • XS
SESSIONID	NUMBER		Audit session identifier
PROXY_SESSIONID	NUMBER		Audit session identifier of proxying session
OS_USERNAME	VARCHAR2(128)		Name of the operating system user for the database session
USERHOST	VARCHAR2(128)		Name of the host machine from which the session was spawned

Column	Datatype	NULL	Description
TERMINAL	VARCHAR2(30)		The operating system terminal of the user session
INSTANCE_ID	NUMBER		Instance number as specified in the initialization parameter file, init.ora
DBID	NUMBER		Database identifier of the audited database
AUTHENTICATION_TYPE	VARCHAR2(1024)		Authentication information for the session user **See:** "AUTHENTICATION_TYPE Description"
DBUSERNAME	VARCHAR2(128)		Database user name of the user whose actions were audited
DBPROXY_USERNAME	VARCHAR2(128)		Proxying user name, in the case of proxy authentication
EXTERNAL_USERID	VARCHAR2(1024)		External user name, in the case of network or external authentication
GLOBAL_USERID	VARCHAR2(32)		Global user identifier for the user, for a user logged in as an enterprise user
CLIENT_PROGRAM_NAME	VARCHAR2(84)		Name of the program used for the database session
DBLINK_INFO	VARCHAR2(4000)		Value of `SYS_CONTEXT('USERENV','DBLINK_INFO')`. Valid if the connection was via a database link.
XS_USER_NAME	VARCHAR2(128)		Name of the Real Application Security user
XS_SESSIONID	RAW(33)		Identifer of the Real Application Security session
ENTRY_ID	NUMBER		Numeric ID for each audit trail entry in the session
STATEMENT_ID	NUMBER		Numeric ID for each statement run (a statement may cause many actions)
EVENT_TIMESTAMP	TIMESTAMP(6)		Timestamp of the creation of the audit trail entry in the local time zone
EVENT_TIMESTAMP_UTC	TIMESTAMP(6)		Timestamp of the creation of the audit trail entry in UTC (Coordinated Universal Time)
ACTION_NAME	VARCHAR2(64)		Name of the action executed by the user. The name should be read in conjunction with the `AUDIT_TYPE` to understand the real action.
RETURN_CODE	NUMBER		Oracle error code generated by the action. Zero if the action succeeded
OS_PROCESS	VARCHAR2(16)		Operating system process identifier of the Oracle database process
TRANSACTION_ID	RAW(8)		Transaction identifier of the transaction in which the object is modified
SCN	NUMBER		System change number (SCN) of the creation of the audit trail entry
EXECUTION_ID	VARCHAR2(64)		Execution context identifier for each action
OBJECT_SCHEMA	VARCHAR2(128)		Schema name of object affected by the action
OBJECT_NAME	VARCHAR2(128)		Name of the object affected by the action
SQL_TEXT	CLOB		SQL associated with the event
SQL_BINDS	CLOB		List of bind variables, if any, associated with `SQL_TEXT`

Column	Datatype	NULL	Description
APPLICATION_CONTEXTS	VARCHAR2(4000)		Semicolon-seperated list of Application Context Namespace, Attribute, Value information in (APPCTX_NSPACE,APPCTX_ATTRIBUTE=<value>) format
CLIENT_IDENTIFIER	VARCHAR2(64)		Client identifier in each Oracle session
NEW_SCHEMA	VARCHAR2(128)		The schema of the object named in the NEW_NAME column
NEW_NAME	VARCHAR2(128)		New name of object after RENAME, or name of underlying object (for example, CREATE INDEX owner.obj_name ON new_owner.new_name)
OBJECT_EDITION	VARCHAR2(128)		Name of the edition containing the audited object
SYSTEM_PRIVILEGE_USED	VARCHAR2(1024)		Comma-separated list of system privileges used to execute the action
SYSTEM_PRIVILEGE	VARCHAR2(40)		System privilege granted/revoked by a GRANT/ REVOKE statement
AUDIT_OPTION	VARCHAR2(40)		AUDIT/NOAUDIT SQL command
OBJECT_PRIVILEGES	VARCHAR2(37)		Object privileges granted/revoked by a GRANT/ REVOKE statement
ROLE	VARCHAR2(128)		Roles granted or revoked or set by GRANT/ REVOKE/SET ROLE command
TARGET_USER	VARCHAR2(128)		User on whom the GRANT/REVOKE/AUDIT/ NOAUDIT statement was executed
EXCLUDED_USER	VARCHAR2(128)		User who was excluded when the AUDIT/ NOAUDIT statement was executed
EXCLUDED_SCHEMA	VARCHAR2(128)		Displays the schema of the excluded objects
EXCLUDED_OBJECT	VARCHAR2(128)		Displays object excluded from the action
CURRENT_USER	VARCHAR2(128)		Effective user for the statement execution
ADDITIONAL_INFO	VARCHAR2(4000)		Text comment on the audit trail entry, if any
UNIFIED_AUDIT_POLICIES	VARCHAR2(4000)		Lists the audit policies that caused the current audit record. For example, if `SELECT ON SCOTT.EMP` was configured from policy `SCOTT_EMP_POL`, for the `SELECT` event this column will display `SCOTT_EMP_POL`. If more than one policy was configured, the list of policies that caused the event to be recorded in the audit trail are displayed in a comma-separated list. This column has a NULL value for mandatory audit records. See *Oracle Database Security Guide* for information on activities that are mandatorily audited.
FGA_POLICY_NAME	VARCHAR2(128)		Fine-grained auditing (FGA) policy name that generated this FGA audit record
XS_INACTIVITY_TIMEOUT	NUMBER		Inactivity timeout of the Real Application Security session

Column	Datatype	NULL	Description
XS_ENTITY_TYPE	VARCHAR2(32)		Type of the Real Application Security entity. Possible values are USER, ROLE, ROLESET, SECURITYCLASS, ACL, DATASECURITY, and NSTEMPLATE.
XS_TARGET_PRINCIPAL_NAME	VARCHAR2(128)		Target principal name in Real Application Security operations. Possible operations are set verifier, set password, add proxy, remove proxy, switch user, assign user, create session,and grant roles.
XS_PROXY_USER_NAME	VARCHAR2(128)		Name of the Real Application Security proxy user
XS_DATASEC_POLICY_NAME	VARCHAR2(128)		Name of the Real Application Security data security policy enabled or disabled
XS_SCHEMA_NAME	VARCHAR2(128)		Name of the schema in enable, disable data security policy and global callback operation
XS_CALLBACK_EVENT_TYPE	VARCHAR2(32)		Real Application Security global callback event type
XS_PACKAGE_NAME	VARCHAR2(128)		Real Application Security callback package name for the global callback
XS_PROCEDURE_NAME	VARCHAR2(128)		Real Application Security callback procedure name for the global callback
XS_ENABLED_ROLE	VARCHAR2(128)		The role that is enabled
XS_COOKIE	VARCHAR2(1024)		Real Application Security session cookie
XS_NS_NAME	VARCHAR2(128)		Name of the Real Application Security session namespace
XS_NS_ATTRIBUTE	VARCHAR2(4000)		Name of the Real Application Security session namespace attribute
XS_NS_ATTRIBUTE_OLD_VAL	VARCHAR2(4000)		The old value of the Real Application Security session namespace attribute
XS_NS_ATTRIBUTE_NEW_VAL	VARCHAR2(4000)		The new value of the Real Application Security session namespace
DV_ACTION_CODE	NUMBER		Numeric action type code for Database Vault
DV_ACTION_NAME	VARCHAR2(128)		Name of the action whose numeric code appears in the DV_ACTION_CODE column
DV_EXTENDED_ACTION_CODE	NUMBER		Numeric action type code for Database Vault administration
DV_GRANTEE	VARCHAR2(128)		Name of the user whose Database Vault authorization was modified
DV_RETURN_CODE	NUMBER		Database Vault specific error code
DV_ACTION_OBJECT_NAME	VARCHAR2(128)		The unique name of the Database Vault object that was modified
DV_RULE_SET_NAME	VARCHAR2(128)		The unique name of the rule set that was executing and caused the audit event to trigger
DV_COMMENT	VARCHAR2(4000)		Text comment on the audit trail entry, providing more information about the statement audited
DV_FACTOR_CONTEXT	VARCHAR2(4000)		An XML document that contains all of the factor identifiers for the current session at the point when the audit event was triggered

Column	Datatype	NULL	Description
DV_OBJECT_STATUS	VARCHAR2(1)		Indicates whether a particular Database Vault object is enabled or disabled. For example, if a Database Vault administrator enables or disables a realm, then this event will be audited and the DV_OBJECT_STATUS value will show the status of the realm after the event occurred. Possible values for this column are: • Y - The object is enabled • N - The object is disabled
OLS_POLICY_NAME	VARCHAR2(128)		Name of the Oracle Label Security (OLS) policy for which this audit record is generated
OLS_GRANTEE	VARCHAR2(1024)		Name of the user whose OLS authorization was modified
OLS_MAX_READ_LABEL	VARCHAR2(4000)		Maximum read label assigned to a user
OLS_MAX_WRITE_LABEL	VARCHAR2(4000)		Maximum write label assigned to a user
OLS_MIN_WRITE_LABEL	VARCHAR2(4000)		Minimum write label assigned to a user
OLS_PRIVILEGES_GRANTED	VARCHAR2(128)		OLS privileges assigned to a user or a trusted stored procedure
OLS_PROGRAM_UNIT_NAME	VARCHAR2(128)		Name of the trusted stored procedure whose authorization was modified or was executed
OLS_PRIVILEGES_USED	VARCHAR2(128)		OLS privileges used for an event
OLS_STRING_LABEL	VARCHAR2(4000)		String representation of the OLS label
OLS_LABEL_COMPONENT_TYPE	VARCHAR2(12)		Type of the OLS label component
OLS_LABEL_COMPONENT_NAME	VARCHAR2(30)		Name of the OLS label component
OLS_PARENT_GROUP_NAME	VARCHAR2(30)		Name of the parent of the OLS group
OLS_OLD_VALUE	VARCHAR2(4000)		Old value for OLS ALTER events
OLS_NEW_VALUE	VARCHAR2(4000)		New value for OLS ALTER events
RMAN_SESSION_RECID	NUMBER		RMAN session identifier. Together with RMAN_SESSION_STAMP uniquely identifies an RMAN job (note that this is not same as user session ID; the value is a recid in controlfile that identifies RMAN job)
RMAN_SESSION_STAMP	NUMBER		Timestamp for the session
RMAN_OPERATION	VARCHAR2(20)		The RMAN operation executed by the job. One row will be added for each distinct operation within an RMAN session. For example, a backup job would contain BACKUP in the RMAN_OPERATION column.

Column	Datatype	NULL	Description
RMAN_OBJECT_TYPE	VARCHAR2(20)		Type of objects involved for backup or restore/ recover or change/delete/crosscheck commands. It contains one of the following values. If RMAN command does not satisfy one of them, then preference is given in order, from top to bottom of the list: • DB FULL • RECVR AREA • DB INCR • DATAFILE FULL • DATAFILE INCR • ARCHIVELOG • CONTROLFILE • SPFILE
RMAN_DEVICE_TYPE	VARCHAR2(5)		Device involved in the RMAN job. It may be DISK or SBT_TAPE or * (An * indicates that more than one location is involved). For a backup job, it will be the output device type. For other commands (such as restore or crosscheck), it will be the input device type.
DP_TEXT_PARAMETERS1	VARCHAR2(512)		Parameters during a Data Pump operation that have a text/string value. This may contain the values for: • ACCESS METHOD • DATA OPTIONS • DUMPER DIRECTORY • JOB_TYPE • JOB VERSION • MASTER TABLE • METADATA_JOB_MODE • PARTITION OPTIONS • REMOTE LINK • SCHEMA • TABLE EXISTS For descriptions and more information about the settings that can appear for these Data Pump text parameters, see Table 7-3.

Column	Datatype	NULL	Description
DP_BOOLEAN_PARAMETERS1	VARCHAR2(512)		Parameters during a Data Pump operation that have a boolean value. This may contain the values for: • DATA_ONLY - Boolean value for whether or not the operation processed data only (as opposed to metadata only, or metadata and data combined) • DUMPFILE_PRESENT - Denotes whether a dump file exists. Typically, it indicates whether a network export in which no dumpfile is required. • ENCRYPTED - Boolean value for whether or not encryption was used for the operation • JOB_RESTARTED - Boolean that indicates if the export or import job had to be restarted • MASTER_ONLY - Indicates whether the import job imported only the control job table and then stopped the job so that the contents of the control job table can be examined • METADATA_ONLY - Boolean value for whether or not the operation processed metadata only (as opposed to data only, or metadata and data combined)
DP_WARNINGS1	VARCHAR2(512)		Contains warnings issued during a Data Pump operation If no warnings were issued, this column contains WARNING(S) ISSUED: No warnings issued.
DIRECT_PATH_NUM_COLUMNS_LOADED	NUMBER		Shows the number of columns that were loaded using the SQL*Loader direct path load method
RLS_INFO	CLOB		Stores virtual private database (VPD), Oracle Label Security (OLS), Real Application Security (RAS), and redaction policy names and predicates separated by a delimiter. In the case of redaction policies, the policy expression is displayed in place of the predicate. To format the output into individual rows, use the DBMS_AUDIT_UTIL.DECODE_RLS_INFO_ATRAIL_UNI function.
KSACL_USER_NAME	VARCHAR2(128)		The connecting user name The value in this column is meaningful only when the UNIFIED_AUDIT_TRAIL.RETURN_CODE is 46981, which is the denial-of-service (DoS) error code.
KSACL_SERVICE_NAME	VARCHAR2(512)		The target database service name The value in this column is meaningful only when the UNIFIED_AUDIT_TRAIL.RETURN_CODE is 46981, which is the denial-of-service (DoS) error code.
KSACL_SOURCE_LOCATION	VARCHAR2(48)		The source location of the initiating connection The value in this column is meaningful only when the UNIFIED_AUDIT_TRAIL.RETURN_CODE is 46981, which is the denial-of-service (DoS) error code.

Column	Datatype	NULL	Description
PROTOCOL_SESSION_ID	NUMBER		Oracle XML DB session ID The PROTOCOL_* columns in this view are meaningful when auditing Oracle XML DB protocol (HTTP or FTP) messages. You can use this column to identify audit records from the same Oracle XML DB session.
PROTOCOL_RETURN_CODE	NUMBER		Return code for the Oracle XML DB protocol request This value is logged in the audit records for both the reply message containing the return code and its corresponding request message. For HTTP requests, a return code of 200 (OKAY) or 304 (NOT-MODIFIED) is considered successful, and a return code of 207 means the reply may have multiple components with separate return codes. All other HTTP return codes are considered unsuccessful.
PROTOCOL_ACTION_NAME	VARCHAR2(32)		Indicates the protocol and method for the Oracle XML DB protocol message This value is of the form *protocol-method*. Possible values for *protocol* are HTTP or FTP. Examples: HTTP-GET and FTP-RETR. Note that the HTTP GET and HEAD methods are both logged as HTTP-GET. Unrecognized methods are logged as HTTP-UNKNOWN or FTP-UNKNOWN.
PROTOCOL_USERHOST	VARCHAR2(128)		IP address of the client
PROTOCOL_MESSAGE	VARCHAR2(4000)		Text of the Oracle XML DB protocol message
DB_UNIQUE_NAME	VARCHAR2(257)		Unique database name of the audited database, which is defined by the DB_UNIQUE_NAME initialization parameter. This value is useful for differentiating between the primary and standby databases in an Oracle Data Guard configuration.
OBJECT_TYPE	VARCHAR2(23)		Object type of the object being audited
FW_ACTION_NAME	VARCHAR2(30)		For SQL Firewall audit actions, the name of the action
FW_RETURN_CODE	NUMBER		For SQL Firewall audit actions, return code of the SQL execution
SOURCE	VARCHAR2(8)		Source of the audit record: • FILE - Refers to records from the operating system spillover files in each database instance • DATABASE - Refers to records from the AUDSYS.AUD$UNIFIED table

Column	Datatype	NULL	Description
SCHEMA	VARCHAR2(4000)		Schema name • If a schema privilege was used to execute the action, this column displays the schema and the SYSTEM_PRIVILEGE_USED column displays the privilege granted on the schema. • If a schema privilege was granted or revoked by a GRANT or REVOKE statement, this column displays the schema and the SYSTEM_PRIVILEGE column displays the privilege that was granted to or revoked from the schema. • Otherwise, the value of this column is null.
DP_CLOB_PARAMETERS1	CLOB		Parameters used by Data Pump export or import, in JSON format

Table 7-3 Data Pump Text Parameter Descriptions

Parameter	Description
ACCESS METHOD	The method used to load the data. Settings can be: • AUTOMATIC: Enables Oracle Data Pump to determine the optimal load method • DIRECT_PATH : Uses the direct path API to pass the data to be loaded. • EXTERNAL_TABLE: Loads data using the external tables option. • CONVENTIONAL: Loads the data using SQL INSERT statements
DATA OPTIONS	Indicates how certain types of data were handled during import operations. Settings are in bit-mask format, which are as follows: • 1 (SKIP_CONSTRAINT_ERRORS): Specifies that the import operation proceeded even if non-deferred constraint violations were encountered. • 8 (DISABLE_APPEND_HINT): The import operation did not use the APPEND hint while loading a data object. • 16 (REJECT_ROWS_WITH_REPL_CHAR): Warnings are issued when the replacement character may be used and an option was added to reject data rows where the replacement character was used during a Data Pump import. This situation can occur if different character sets are used for the export/import process
DUMPER DIRECTORY	Not in use
JOB_TYPE	Is either EXPORT or IMPORT
JOB VERSION	Specifies the version of database objects that were imported
MASTER TABLE	Indicates the name of the control job table. By default, it appears as follows for export operations: *schema_name*.SYS_EXPORT_TABLE_*n* For import operations, it appears as follows: *schema_name*.SYS_IMPORT_TABLE_*n* The *n* represents a numeric value of 01. If 01 is in use, the number is incremented with 02, 03, and so on.

Table 7-3 (Cont.) Data Pump Text Parameter Descriptions

Parameter	Description
METADATA_JOB_MODE	Type of export or import operation. For example a table export would be TABLE_EXPORT
PARTITION OPTIONS	Indicates how table partitions were created during an import operation. Settings can be: • NONE: The tables were created as they existed on the system from which the export operation was performed. • DEPARTITION: Each partition or subpartition was promoted to a new individual table. • MERGE: All partitions and subpartitions were merged into one table
REMOTE LINK	Indicates that the export was performed from a (source) database identified by a valid database link. The data from the source database instance was written to a dump file set on the connected database instance.
SCHEMA	Indicates the schema containing the data that was exported or imported
TABLE EXISTS	Indicates the action that was taken on an import operation when the target table already existed. The values are as follows: • REPLACE • TRUNCATE • SKIP • APPEND

AUTHENTICATION_TYPE Description

The AUTHENTICATION_TYPE column of UNIFIED_AUDIT_TRAIL displays authentication information for the session user.

The value of this column is a string with the following syntax:

```
(TYPE=(auth_string));(CLIENT ADDRESS=((PROTOCOL=protocol)
(HOST=client_ip_address)(PORT=client_port_number)));
[(LOGON_INFO=((VERIFIER=%s-%s)(CLIENT_CAPABILITIES=%s));]
```

- (TYPE=(*auth_string*));

  Indicates the type of authentication for the session user.

  Possible values for *auth_string*:

  - DATABASE - Username/password authentication
  - DIRECTORY PASSWORD - Directory-based user authentication
  - NETWORK SERVICE - Authentication was performed by Oracle Net Services or strong authentication
  - OS - Operating system external user authentication
  - PROXY - OCI proxy connection authentication

- (CLIENT ADDRESS=((PROTOCOL=*protocol*)(HOST=*client_ip_address*)
(PORT=*client_port_number*)));

Displays the protocol used by the client, such as `ipc`, `sdp`, `tcp`, or `tcps`, the client IP address, and the client port number.

- `(LOGON_INFO=((VERIFIER=`*`version`*`-`*`rollover_state`*`)(CLIENT_CAPABILITIES=`*`capability_list`*`));`

  This syntax is displayed only if authentication was completed during gradual database password rollover.

  The value of `VERIFIER` comprises the following two values, separated by a hyphen:

  – *`version`* - Indicates the password version (`11G` or `12C`)

  – *`rollover_state`* - Indicates whether the user was authenticated with the `OLD` password or the `NEW` password

  For `CLIENT_CAPABILITIES`, the value of *`capabilitiy_list`* is a comma-separated list of one or more of the following client capabilities: `O5L_NP`, `O7L_MR`, or `O8L_LI`. See *Oracle Database Net Services Reference* for more information about client capabilities.

See Also:

- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_AUDIT_MGMT` package
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_AUDIT_UTIL.DECODE_RLS_INFO_ATRAIL_UNI` function

7.286 USABLE_EDITIONS

`USABLE_EDITIONS` describes the usable editions of the current user.

Column	Datatype	NULL	Description
`EDITION_NAME`	`VARCHAR2(128)`	`NOT NULL`	Name of the edition
`PARENT_EDITION_NAME`	`VARCHAR2(128)`		Name of the parent edition for this edition

See Also:

Oracle Database Development Guide for more information about editions

7.287 USER_ADDM_FDG_BREAKDOWN

`USER_ADDM_FDG_BREAKDOWN` describes the contribution for each finding from the different instances owned by the current user. Its columns are the same as those in `DBA_ADDM_FDG_BREAKDOWN`.

> **See Also:**
>
> "DBA_ADDM_FDG_BREAKDOWN"

7.288 USER_ADDM_FINDINGS

`USER_ADDM_FINDINGS` displays the ADDM findings discovered by the advisors owned by the current user.

Each row for ADDM tasks in the related `USER_ADVISOR_FINDINGS` view has a corresponding row in this view. Its columns (except for `OWNER`) are the same as those in `DBA_ADDM_FINDINGS`.

> **See Also:**
>
> "DBA_ADDM_FINDINGS"

7.289 USER_ADDM_INSTANCES

`USER_ADDM_INSTANCES` provides instance-level information for ADDM tasks that finished executing in all instances owned by the current user. Its columns are the same as those in `DBA_ADDM_INSTANCES`.

> **See Also:**
>
> "DBA_ADDM_INSTANCES"

7.290 USER_ADDM_TASK_DIRECTIVES

`USER_ADDM_TASK_DIRECTIVES` displays information about ADDM task directives owned by the current user. Its columns (except for `USERNAME` and `SEQ_ID`) are the same as those in `DBA_ADDM_TASK_DIRECTIVES`.

> **See Also:**
>
> "DBA_ADDM_TASK_DIRECTIVES"

7.291 USER_ADDM_TASKS

`USER_ADDM_TASKS` displays information about the ADDM tasks owned by the current user.

The view contains one row for each row in the related `USER_ADVISOR_TASKS` view that has `ADVISOR_NAME=ADDM` and `STATUS=COMPLETED`. Its columns (except for `OWNER`) are the same as those in `DBA_ADDM_TASKS`.

> **See Also:**
>
> "DBA_ADDM_TASKS"

7.292 USER_ADVISOR_ACTIONS

`USER_ADVISOR_ACTIONS` displays information about the actions associated with the recommendations owned by the current user. Its columns (except for `OWNER`) are the same as those in `DBA_ADVISOR_ACTIONS`.

> **See Also:**
>
> "DBA_ADVISOR_ACTIONS"

7.293 USER_ADVISOR_DIR_TASK_INST

`USER_ADVISOR_DIR_TASK_INST` displays information about all task directive instances owned by the current user. Its columns (except for `SEQ_ID` and `USERNAME`) are the same as those in `DBA_ADVISOR_DIR_TASK_INST`.

> **See Also:**
>
> "DBA_ADVISOR_DIR_TASK_INST"

7.294 USER_ADVISOR_EXEC_PARAMETERS

`USER_ADVISOR_EXEC_PARAMETERS` displays the parameter values used for past executions of tasks owned by the current user. Its columns (except for `OWNER`) are the same as those in `DBA_ADVISOR_EXEC_PARAMETERS`.

> **See Also:**
>
> "DBA_ADVISOR_EXEC_PARAMETERS"

7.295 USER_ADVISOR_EXECUTIONS

`USER_ADVISOR_EXECUTIONS` displays metadata information for tasks owned by the current user. Its columns (except for `OWNER`) are the same as those in `DBA_ADVISOR_EXECUTIONS`.

> **See Also:**
>
> "DBA_ADVISOR_EXECUTIONS"

7.296 USER_ADVISOR_FDG_BREAKDOWN

`USER_ADVISOR_FDG_BREAKDOWN` describes the contribution from the different instances to the findings for each ADDM task owned by the current user. Its columns are the same as those in `DBA_ADVISOR_FDG_BREAKDOWN`.

> **See Also:**
>
> "DBA_ADVISOR_FDG_BREAKDOWN"

7.297 USER_ADVISOR_FINDINGS

USER_ADVISOR_FINDINGS displays the findings discovered by the advisors owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_FINDINGS.

> **See Also:**
>
> "DBA_ADVISOR_FINDINGS"

7.298 USER_ADVISOR_JOURNAL

USER_ADVISOR_JOURNAL displays the journal entries for the tasks owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_JOURNAL.

> **See Also:**
>
> "DBA_ADVISOR_JOURNAL"

7.299 USER_ADVISOR_LOG

USER_ADVISOR_LOG displays information about the current state of the tasks owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_LOG.

> **See Also:**
>
> "DBA_ADVISOR_LOG"

7.300 USER_ADVISOR_OBJECTS

USER_ADVISOR_OBJECTS displays information about the objects currently referenced by the advisors owned by the current user. Its columns (except for OWNER, ATTR21, and ATTR22) are the same as those in DBA_ADVISOR_OBJECTS.

> **See Also:**
>
> "DBA_ADVISOR_OBJECTS"

7.301 USER_ADVISOR_PARAMETERS

USER_ADVISOR_PARAMETERS displays the task parameters and their current values for the tasks owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_PARAMETERS.

> **See Also:**
>
> "DBA_ADVISOR_PARAMETERS"

7.302 USER_ADVISOR_RATIONALE

USER_ADVISOR_RATIONALE displays information about the rationales for the recommendations owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_RATIONALE.

> **See Also:**
>
> "DBA_ADVISOR_RATIONALE"

7.303 USER_ADVISOR_RECOMMENDATIONS

USER_ADVISOR_RECOMMENDATIONS displays the results of an analysis of the recommendations owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_RECOMMENDATIONS.

> **See Also:**
>
> "DBA_ADVISOR_RECOMMENDATIONS"

7.304 USER_ADVISOR_SQLA_REC_SUM

USER_ADVISOR_SQLA_REC_SUM displays recommendation rollup information for the workload objects owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLA_REC_SUM.

> **See Also:**
>
> "DBA_ADVISOR_SQLA_REC_SUM"

7.305 USER_ADVISOR_SQLA_TABLES

USER_ADVISOR_SQLA_TABLES displays cross references between the workload statements and the tables referenced in the statement for the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLA_TABLES.

> **See Also:**
>
> "DBA_ADVISOR_SQLA_TABLES"

7.306 USER_ADVISOR_SQLA_WK_MAP

USER_ADVISOR_SQLA_WK_MAP displays the workload references for the tasks owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLA_WK_MAP.

> **See Also:**
>
> "DBA_ADVISOR_SQLA_WK_MAP"

7.307 USER_ADVISOR_SQLA_WK_STMTS

USER_ADVISOR_SQLA_WK_STMTS displays information about the workload objects owned by the current user after an Access Advisor analysis operation. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLA_WK_STMTS.

> **See Also:**
>
> "DBA_ADVISOR_SQLA_WK_STMTS"

7.308 USER_ADVISOR_SQLPLANS

USER_ADVISOR_SQLPLANS displays the different SQL execution plans owned by the current user generated as part of an advisor analysis. Its columns are the same as those in DBA_ADVISOR_SQLPLANS.

> **See Also:**
>
> "DBA_ADVISOR_SQLPLANS"

7.309 USER_ADVISOR_SQLSTATS

`USER_ADVISOR_SQLSTATS` displays execution statistics owned by the current user for the test-execution of different SQL plans during the advisor analysis. Its columns are the same as those in `DBA_ADVISOR_SQLSTATS`.

> **See Also:**
>
> "DBA_ADVISOR_SQLSTATS"

7.310 USER_ADVISOR_SQLW_JOURNAL

`USER_ADVISOR_SQLW_JOURNAL` displays the journal entries for the workload objects owned by the current user. Its columns (except for `OWNER`) are the same as those in `DBA_ADVISOR_SQLW_JOURNAL`.

> **See Also:**
>
> "DBA_ADVISOR_SQLW_JOURNAL"

7.311 USER_ADVISOR_SQLW_PARAMETERS

`USER_ADVISOR_SQLW_PARAMETERS` displays the workload parameters and their current values owned by the current user. Its columns (except for `OWNER`) are the same as those in `DBA_ADVISOR_SQLW_PARAMETERS`.

> **See Also:**
>
> "DBA_ADVISOR_SQLW_PARAMETERS"

7.312 USER_ADVISOR_SQLW_STMTS

`USER_ADVISOR_SQLW_STMTS` displays rows that correspond to the statements in the workload owned by the current user. Its columns (except for `OWNER`) are the same as those in `DBA_ADVISOR_SQLW_STMTS`.

> **See Also:**
>
> "DBA_ADVISOR_SQLW_STMTS"

7.313 USER_ADVISOR_SQLW_SUM

USER_ADVISOR_SQLW_SUM displays an aggregated picture of the SQLWkld workload objects owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLW_SUM.

> **See Also:**
>
> "DBA_ADVISOR_SQLW_SUM"

7.314 USER_ADVISOR_SQLW_TABLES

USER_ADVISOR_SQLW_TABLES displays cross references between the workload statements and the tables referenced in the statement. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLW_TABLES.

> **See Also:**
>
> "DBA_ADVISOR_SQLW_TABLES"

7.315 USER_ADVISOR_SQLW_TEMPLATES

USER_ADVISOR_SQLW_TEMPLATES displays an aggregated picture of the SQLWkld template objects owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_SQLW_TEMPLATES.

> **See Also:**
>
> "DBA_ADVISOR_SQLW_TEMPLATES"

7.316 USER_ADVISOR_TASKS

USER_ADVISOR_TASKS displays information about the tasks owned by the current user. Its columns (except for OWNER) are the same as those in DBA_ADVISOR_TASKS.

> **See Also:**
>
> "DBA_ADVISOR_TASKS"

7.317 USER_ADVISOR_TEMPLATES

`USER_ADVISOR_TEMPLATES` displays information about the templates owned by the current user. Its columns (except for `OWNER`) are the same as those in `DBA_ADVISOR_TEMPLATES`.

> **See Also:**
>
> "DBA_ADVISOR_TEMPLATES"

7.318 USER_ALL_TABLES

`USER_ALL_TABLES` describes the object tables and relational tables owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ALL_TABLES`.

> **See Also:**
>
> "ALL_ALL_TABLES"

7.319 USER_ANALYTIC_VIEW_ATTR_CLASS

`USER_ANALYTIC_VIEW_ATTR_CLASS` describes the attribute classifications of the analytic views owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_ATTR_CLASS`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_ATTR_CLASS"

7.320 USER_ANALYTIC_VIEW_ATTR_CLS

`USER_ANALYTIC_VIEW_ATTR_CLS` is identical to `USER_ANALYTIC_VIEW_ATTR_CLASS`.

> **See Also:**
>
> "USER_ANALYTIC_VIEW_ATTR_CLASS"

7.321 USER_ANALYTIC_VIEW_ATTR_CLS_AE

`USER_ANALYTIC_VIEW_ATTR_CLS_AE` describes the attribute classifications of the analytic views (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_ATTR_CLS_AE`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_ATTR_CLS_AE"

7.322 USER_ANALYTIC_VIEW_BAS_MEAS

`USER_ANALYTIC_VIEW_BAS_MEAS` is identical to `USER_ANALYTIC_VIEW_BASE_MEAS`.

> **See Also:**
>
> "USER_ANALYTIC_VIEW_BASE_MEAS"

7.323 USER_ANALYTIC_VIEW_BAS_MEAS_AE

`USER_ANALYTIC_VIEW_BAS_MEAS_AE` describes the base measures in the analytic views (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_BAS_MEAS_AE`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_BAS_MEAS_AE"

7.324 USER_ANALYTIC_VIEW_BASE_MEAS

`USER_ANALYTIC_VIEW_BASE_MEAS` describes the base measures in the analytic views owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_BASE_MEAS`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_BASE_MEAS"

7.325 USER_ANALYTIC_VIEW_CALC_MEAS

USER_ANALYTIC_VIEW_CALC_MEAS describes the calculated measures in the analytic views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ANALYTIC_VIEW_CALC_MEAS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_CALC_MEAS"

7.326 USER_ANALYTIC_VIEW_CLASS

USER_ANALYTIC_VIEW_CLASS describes the classifications of the analytic views owned by the current user. Its columns (except for OWNER) are the same as those in USER_ANALYTIC_VIEW_CLASS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_CLASS"

7.327 USER_ANALYTIC_VIEW_CLASS_AE

USER_ANALYTIC_VIEW_CLASS_AE describes the classifications of the analytic views (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ANALYTIC_VIEW_CLASS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_CLASS_AE"

7.328 USER_ANALYTIC_VIEW_CLC_MEAS

USER_ANALYTIC_VIEW_CLC_MEAS is identical to USER_ANALYTIC_VIEW_CALC_MEAS.

> **See Also:**
>
> "USER_ANALYTIC_VIEW_CALC_MEAS"

7.329 USER_ANALYTIC_VIEW_CLC_MEAS_AE

`USER_ANALYTIC_VIEW_CLC_MEAS_AE` describes the calculated measures in the analytic views (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_CLC_MEAS_AE`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_CLC_MEAS_AE"

7.330 USER_ANALYTIC_VIEW_COLUMNS

`USER_ANALYTIC_VIEW_COLUMNS` describes the columns of the analytic views owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_COLUMNS`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_COLUMNS"

7.331 USER_ANALYTIC_VIEW_COLUMNS_AE

`USER_ANALYTIC_VIEW_COLUMNS_AE` describes the columns of the analytic views (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_COLUMNS_AE`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_COLUMNS_AE"

7.332 USER_ANALYTIC_VIEW_DIM_ATRS

`USER_ANALYTIC_VIEW_DIM_ATRS` is identical to `USER_ANALYTIC_VIEW_DIM_ATTRS`.

> **See Also:**
>
> "USER_ANALYTIC_VIEW_DIM_ATTRS"

7.333 USER_ANALYTIC_VIEW_DIM_ATRS_AE

`USER_ANALYTIC_VIEW_DIM_ATRS_AE` describes the attributes of the attribute dimensions in the analytic views (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_DIM_ATRS_AE`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_DIM_ATRS_AE"

7.334 USER_ANALYTIC_VIEW_DIM_ATTRS

`USER_ANALYTIC_VIEW_DIM_ATTRS` describes the attributes of the attribute dimensions in the analytic views owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_DIM_ATTRS`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_DIM_ATTRS"

7.335 USER_ANALYTIC_VIEW_DIM_CLASS

`USER_ANALYTIC_VIEW_DIM_CLASS` describes the classifications of the attribute dimensions in the analytic views owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_DIM_CLASS`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_DIM_CLASS"

7.336 USER_ANALYTIC_VIEW_DIM_CLS

`USER_ANALYTIC_VIEW_DIM_CLS` is identical to `USER_ANALYTIC_VIEW_DIM_CLASS`.

> **See Also:**
>
> "USER_ANALYTIC_VIEW_DIM_CLASS"

7.337 USER_ANALYTIC_VIEW_DIM_CLS_AE

USER_ANALYTIC_VIEW_DIM_CLS_AE describes the classifications of the attribute dimensions in the analytic views (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ANALYTIC_VIEW_DIM_CLS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_DIM_CLS_AE"

7.338 USER_ANALYTIC_VIEW_DIMENSIONS

USER_ANALYTIC_VIEW_DIMENSIONS describes the attribute dimensions in the analytic views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ANALYTIC_VIEW_DIMENSIONS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_DIMENSIONS"

7.339 USER_ANALYTIC_VIEW_DIMS

USER_ANALYTIC_VIEW_DIMS is identical to USER_ANALYTIC_VIEW_DIMENSIONS.

> **See Also:**
>
> "USER_ANALYTIC_VIEW_DIMENSIONS"

7.340 USER_ANALYTIC_VIEW_DIMS_AE

USER_ANALYTIC_VIEW_DIMS_AE describes the attribute dimensions in the analytic views (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ANALYTIC_VIEW_DIMS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_DIMS_AE"

7.341 USER_ANALYTIC_VIEW_FACT_COLS

`USER_ANALYTIC_VIEW_FACT_COLS` describes the fact columns of the analytic views owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_FACT_COLS`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_FACT_COLS"

7.342 USER_ANALYTIC_VIEW_FCT_COLS

`USER_ANALYTIC_VIEW_FCT_COLS` is identical to `USER_ANALYTIC_VIEW_FACT_COLS`.

> **See Also:**
>
> "USER_ANALYTIC_VIEW_FACT_COLS"

7.343 USER_ANALYTIC_VIEW_FCT_COLS_AE

`USER_ANALYTIC_VIEW_FCT_COLS_AE` describes the fact columns of the analytic views (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_FCT_COLS_AE`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_FCT_COLS_AE"

7.344 USER_ANALYTIC_VIEW_HIER_CLASS

`USER_ANALYTIC_VIEW_HIER_CLASS` describes the classifications of the hierarchies in the analytic views owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_HIER_CLASS`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_HIER_CLASS"

7.345 USER_ANALYTIC_VIEW_HIER_CLS

USER_ANALYTIC_VIEW_HIER_CLS is identical to USER_ANALYTIC_VIEW_HIER_CLASS.

> **See Also:**
>
> "USER_ANALYTIC_VIEW_HIER_CLASS"

7.346 USER_ANALYTIC_VIEW_HIER_CLS_AE

USER_ANALYTIC_VIEW_HIER_CLS_AE describes the classifications of the hierarchies in the analytic views (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ANALYTIC_VIEW_HIER_CLS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_HIER_CLS_AE"

7.347 USER_ANALYTIC_VIEW_HIERS

USER_ANALYTIC_VIEW_HIERS describes the hierarchies in the analytic views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ANALYTIC_VIEW_HIERS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_HIERS"

7.348 USER_ANALYTIC_VIEW_HIERS_AE

USER_ANALYTIC_VIEW_HIERS_AE describes the hierarchies in the analytic views (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ANALYTIC_VIEW_HIERS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_HIERS_AE"

7.349 USER_ANALYTIC_VIEW_KEYS

`USER_ANALYTIC_VIEW_KEYS` describes the key columns of the attribute dimensions in the analytic views owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_KEYS`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_KEYS"

7.350 USER_ANALYTIC_VIEW_KEYS_AE

`USER_ANALYTIC_VIEW_KEYS_AE` describes the key columns of the attribute dimensions in the analytic views (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_KEYS_AE`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_KEYS_AE"

7.351 USER_ANALYTIC_VIEW_LEVEL_CLASS

`USER_ANALYTIC_VIEW_LEVEL_CLASS` describes the level classifications of the analytic views owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_LEVEL_CLASS`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_LEVEL_CLASS"

7.352 USER_ANALYTIC_VIEW_LEVELS

`USER_ANALYTIC_VIEW_LEVELS` describes the levels in the hierarchies in the analytic views owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_LEVELS`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_LEVELS"

7.353 USER_ANALYTIC_VIEW_LEVELS_AE

`USER_ANALYTIC_VIEW_LEVELS_AE` describes the levels in the hierarchies in the analytic views (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_LEVELS_AE`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_LEVELS_AE"

7.354 USER_ANALYTIC_VIEW_LVL_CLS

`USER_ANALYTIC_VIEW_LVL_CLS` is identical to `USER_ANALYTIC_VIEW_LEVEL_CLASS`.

> **See Also:**
>
> "USER_ANALYTIC_VIEW_LEVEL_CLASS"

7.355 USER_ANALYTIC_VIEW_LVL_CLS_AE

`USER_ANALYTIC_VIEW_LVL_CLS_AE` describes the level classifications of the analytic views (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_LVL_CLS_AE`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_LVL_CLS_AE"

7.356 USER_ANALYTIC_VIEW_LVLGRPS

`USER_ANALYTIC_VIEW_LVLGRPS` describes the analytic view measure and level groups of the analytic views owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_LVLGRPS`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_LVLGRPS"

7.357 USER_ANALYTIC_VIEW_LVLGRPS_AE

`USER_ANALYTIC_VIEW_LVLGRPS_AE` describes the analytic view measure and level groups of the analytic views (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_LVLGRPS_AE`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_LVLGRPS_AE"

7.358 USER_ANALYTIC_VIEW_MEAS_CLASS

`USER_ANALYTIC_VIEW_MEAS_CLASS` describes the classifications of the measures of the analytic views owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_MEAS_CLASS`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_MEAS_CLASS"

7.359 USER_ANALYTIC_VIEW_MEAS_CLS

`USER_ANALYTIC_VIEW_MEAS_CLS` is identical to `USER_ANALYTIC_VIEW_MEAS_CLASS`.

> **See Also:**
>
> "USER_ANALYTIC_VIEW_MEAS_CLASS"

7.360 USER_ANALYTIC_VIEW_MEAS_CLS_AE

`USER_ANALYTIC_VIEW_MEAS_CLS_AE` describes the classifications of the measures of the analytic views (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ANALYTIC_VIEW_MEAS_CLS_AE`.

> **See Also:**
>
> "ALL_ANALYTIC_VIEW_MEAS_CLS_AE"

7.361 USER_ANALYTIC_VIEWS

USER_ANALYTIC_VIEWS describes the analytic views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ANALYTIC_VIEWS.

> **See Also:**
>
> "ALL_ANALYTIC_VIEWS"

7.362 USER_ANALYTIC_VIEWS_AE

USER_ANALYTIC_VIEWS_AE describes the analytic views (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ANALYTIC_VIEWS_AE.

> **See Also:**
>
> "ALL_ANALYTIC_VIEWS_AE"

7.363 USER_ANNOTATION_VALUES

USER_ANNOTATION_VALUES displays the values for schema annotations owned by the current user. Its columns (except for ANNOTATION_OWNER) are the same as those in ALL_ANNOTATION_VALUES.

The annotation owner is the same as the owner of the annotated object.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_ANNOTATION_VALUES"

7.364 USER_ANNOTATIONS

USER_ANNOTATIONS displays schema annotations owned by the current user. Its columns (except for ANNOTATION_OWNER) are the same as those in ALL_ANNOTATIONS.

The annotation owner is the same as the owner of the annotated object.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_ANNOTATIONS"

7.365 USER_ANNOTATIONS_USAGE

`USER_ANNOTATIONS_USAGE` provides usage information about schema annotations owned by the current user. Its columns (except for `ANNOTATION_OWNER`) are the same as those in `ALL_ANNOTATIONS_USAGE`.

The annotation owner is the same as the owner of the annotated object.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_ANNOTATIONS_USAGE"

7.366 USER_APPLICATION_ROLES

`USER_APPLICATION_ROLES` describes all the roles for the current user that have authorization policy functions defined.

Its columns are the same as those in `DBA_APPLICATION_ROLES`.

> **See Also:**
>
> "DBA_APPLICATION_ROLES"

7.367 USER_APPLY_ERROR

`USER_APPLY_ERROR` displays information about the error transactions generated by apply processes visible to the current user. Its columns (except for `SOURCE_ROOT_NAME`) are the same as those in `ALL_APPLY_ERROR`.

> **See Also:**
>
> "ALL_APPLY_ERROR"

7.368 USER_AQ_AGENT_PRIVS

`USER_AQ_AGENT_PRIVS` displays information about the registered AQ agents that are mapped to the current user. Its columns (except for `DB_USERNAME`) are the same as those in `DBA_AQ_AGENT_PRIVS`.

> **See Also:**
>
> "DBA_AQ_AGENT_PRIVS"

7.369 USER_ARGUMENTS

`USER_ARGUMENTS` lists the arguments of the functions and procedures that are owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ARGUMENTS`.

> **See Also:**
>
> - "ALL_ARGUMENTS"
> - "USER_PROCEDURES" for information about the functions and procedures that are owned by the current user

7.370 USER_ASSEMBLIES

`USER_ASSEMBLIES` provides information about all assemblies owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ASSEMBLIES`.

> **See Also:**
>
> "ALL_ASSEMBLIES"

7.371 USER_ASSOCIATIONS

`USER_ASSOCIATIONS` describes user-defined statistics associated with objects owned by the current user. Its columns are the same as those in `ALL_ASSOCIATIONS`.

> **See Also:**
>
> "ALL_ASSOCIATIONS"

7.372 USER_ATTRIBUTE_DIM_ATTR_CLASS

`USER_ATTRIBUTE_DIM_ATTR_CLASS` describes the attribute classifications of the attribute dimensions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIM_ATTR_CLASS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ATTR_CLASS"

7.373 USER_ATTRIBUTE_DIM_ATTR_CLS

`USER_ATTRIBUTE_DIM_ATTR_CLS` is identical to `USER_ATTRIBUTE_DIM_ATTR_CLASS`.

> **See Also:**
>
> "USER_ATTRIBUTE_DIM_ATTR_CLASS"

7.374 USER_ATTRIBUTE_DIM_ATTR_CLS_AE

USER_ATTRIBUTE_DIM_ATTR_CLS_AE describes the attribute classifications of the attribute dimensions (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ATTRIBUTE_DIM_ATTR_CLS_AE.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ATTR_CLS_AE"

7.375 USER_ATTRIBUTE_DIM_ATTRS

USER_ATTRIBUTE_DIM_ATTRS describes the attributes of the attribute dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ATTRIBUTE_DIM_ATTRS.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ATTRS"

7.376 USER_ATTRIBUTE_DIM_ATTRS_AE

USER_ATTRIBUTE_DIM_ATTRS_AE describes the attributes of the attribute dimensions (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ATTRIBUTE_DIM_ATTRS_AE.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ATTRS_AE"

7.377 USER_ATTRIBUTE_DIM_CLASS

USER_ATTRIBUTE_DIM_CLASS describes the classifications of the attribute dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ATTRIBUTE_DIM_CLASS.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_CLASS"

7.378 USER_ATTRIBUTE_DIM_CLASS_AE

`USER_ATTRIBUTE_DIM_CLASS_AE` describes the classifications of the attribute dimensions (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIM_CLASS_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_CLASS_AE"

7.379 USER_ATTRIBUTE_DIM_JN_PTHS

`USER_ATTRIBUTE_DIM_JN_PTHS` is identical to `USER_ATTRIBUTE_DIM_JOIN_PATHS`.

> **See Also:**
>
> "USER_ATTRIBUTE_DIM_JOIN_PATHS"

7.380 USER_ATTRIBUTE_DIM_JN_PTHS_AE

`USER_ATTRIBUTE_DIM_JN_PTHS_AE` describes the join paths for the attribute dimensions (across all editions) owned by the current user. Its columns are the same as those in `ALL_ATTRIBUTE_DIM_JN_PTHS_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_JN_PTHS_AE"

7.381 USER_ATTRIBUTE_DIM_JOIN_PATHS

`USER_ATTRIBUTE_DIM_JOIN_PATHS` describes the join paths for the attribute dimensions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIM_JOIN_PATHS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_JOIN_PATHS"

7.382 USER_ATTRIBUTE_DIM_KEYS

`USER_ATTRIBUTE_DIM_KEYS` describes the keys of the attribute dimensions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIM_KEYS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_KEYS"

7.383 USER_ATTRIBUTE_DIM_KEYS_AE

`USER_ATTRIBUTE_DIM_KEYS_AE` describes the keys of the attribute dimensions (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIM_KEYS_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_KEYS_AE"

7.384 USER_ATTRIBUTE_DIM_LEVEL_ATTRS

`USER_ATTRIBUTE_DIM_LEVEL_ATTRS` describes the attributes of the levels of the attribute dimensions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIM_LEVEL_ATTRS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_LEVEL_ATTRS"

7.385 USER_ATTRIBUTE_DIM_LEVELS

`USER_ATTRIBUTE_DIM_LEVELS` describes the levels of the attribute dimensions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIM_LEVELS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_LEVELS"

7.386 USER_ATTRIBUTE_DIM_LEVELS_AE

`USER_ATTRIBUTE_DIM_LEVELS_AE` describes the levels of the attribute dimensions (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIM_LEVELS_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_LEVELS_AE"

7.387 USER_ATTRIBUTE_DIM_LVL_ATRS

`USER_ATTRIBUTE_DIM_LVL_ATRS` is identical to `USER_ATTRIBUTE_DIM_LEVEL_ATTRS`.

> **See Also:**
>
> "USER_ATTRIBUTE_DIM_LEVEL_ATTRS"

7.388 USER_ATTRIBUTE_DIM_LVL_ATRS_AE

`USER_ATTRIBUTE_DIM_LVL_ATRS_AE` describes the attributes of the levels of the attribute dimensions (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIM_LVL_ATRS_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_LVL_ATRS_AE"

7.389 USER_ATTRIBUTE_DIM_LVL_CLASS

`USER_ATTRIBUTE_DIM_LVL_CLASS` describes the level classifications of the attribute dimensions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIM_LVL_CLASS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_LVL_CLASS"

7.390 USER_ATTRIBUTE_DIM_LVL_CLS

USER_ATTRIBUTE_DIM_LVL_CLS is identical to USER_ATTRIBUTE_DIM_LVL_CLASS.

> **See Also:**
>
> "USER_ATTRIBUTE_DIM_LVL_CLASS"

7.391 USER_ATTRIBUTE_DIM_LVL_CLS_AE

USER_ATTRIBUTE_DIM_LVL_CLS_AE describes the level classifications of the attribute dimensions (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ATTRIBUTE_DIM_LVL_CLS_AE.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_LVL_CLS_AE"

7.392 USER_ATTRIBUTE_DIM_ORD_ATRS

USER_ATTRIBUTE_DIM_ORD_ATRS is identical to USER_ATTRIBUTE_DIM_ORDER_ATTRS.

> **See Also:**
>
> "USER_ATTRIBUTE_DIM_ORDER_ATTRS"

7.393 USER_ATTRIBUTE_DIM_ORD_ATRS_AE

USER_ATTRIBUTE_DIM_ORD_ATRS_AE describes the order attributes of the attribute dimensions (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ATTRIBUTE_DIM_ORD_ATRS_AE.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ORD_ATRS_AE"

7.394 USER_ATTRIBUTE_DIM_ORDER_ATTRS

`USER_ATTRIBUTE_DIM_ORDER_ATTRS` describes the order attributes of the attribute dimensions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIM_ORDER_ATTRS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_ORDER_ATTRS"

7.395 USER_ATTRIBUTE_DIM_TABLES

`USER_ATTRIBUTE_DIM_TABLES` describes the tables used by the attribute dimensions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIM_TABLES`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_TABLES"

7.396 USER_ATTRIBUTE_DIM_TABLES_AE

`USER_ATTRIBUTE_DIM_TABLES_AE` describes the tables used by the attribute dimensions (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIM_TABLES_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIM_TABLES_AE"

7.397 USER_ATTRIBUTE_DIMENSIONS

`USER_ATTRIBUTE_DIMENSIONS` describes the attribute dimensions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIMENSIONS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIMENSIONS"

7.398 USER_ATTRIBUTE_DIMENSIONS_AE

`USER_ATTRIBUTE_DIMENSIONS_AE` describes the attribute dimensions (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_DIMENSIONS_AE`.

> **See Also:**
>
> "ALL_ATTRIBUTE_DIMENSIONS_AE"

7.399 USER_ATTRIBUTE_TRANSFORMATIONS

`USER_ATTRIBUTE_TRANSFORMATIONS` describes the transformation functions for the transformations owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_ATTRIBUTE_TRANSFORMATIONS`.

> **See Also:**
>
> "ALL_ATTRIBUTE_TRANSFORMATIONS"

7.400 USER_AUDIT_OBJECT

`USER_AUDIT_OBJECT` displays audit trail records for the objects accessible to the current user. Its columns are the same as those in `DBA_AUDIT_OBJECT`.

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

7.401 USER_AUDIT_POLICIES

`USER_AUDIT_POLICIES` describes the fine-grained auditing policies on the tables and views owned by the current user. Its columns (except for `OBJECT_SCHEMA`) are the same as those in `ALL_AUDIT_POLICIES`.

Note:

This view is populated only in an Oracle Database where unified auditing is not enabled. When unified auditing is enabled in Oracle Database, the audit records are populated in the new audit trail and can be viewed from `UNIFIED_AUDIT_TRAIL`.

- See *Oracle Database Security Guide* for more information about unified auditing.
- See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

See Also:

"ALL_AUDIT_POLICIES"

7.402 USER_AUDIT_POLICY_COLUMNS

`USER_AUDIT_POLICY_COLUMNS` describes the fine-grained auditing policy columns on the tables and views owned by the current user. Its columns are the same as those in `ALL_AUDIT_POLICY_COLUMNS`.

Note:

This view is populated only in an Oracle Database where unified auditing is not enabled. When unified auditing is enabled in Oracle Database, the audit records are populated in the new audit trail and can be viewed from `UNIFIED_AUDIT_TRAIL`.

- See *Oracle Database Security Guide* for more information about unified auditing.
- See *Oracle Database Upgrade Guide* for more information about migrating to unified auditing.

See Also:

"ALL_AUDIT_POLICY_COLUMNS"

7.403 USER_AUDIT_SESSION

`USER_AUDIT_SESSION` displays the audit trail records concerning connections and disconnections of the current user. Its columns are the same as those in `DBA_AUDIT_SESSION`.

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

7.404 USER_AUDIT_STATEMENT

`USER_AUDIT_STATEMENT` displays audit trail entries for the `GRANT`, `REVOKE`, `AUDIT`, `NOAUDIT`, and `ALTER SYSTEM` statements issued by the current user.

Its columns are the same as those in "DBA_AUDIT_STATEMENT".

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

7.405 USER_AUDIT_TRAIL

`USER_AUDIT_TRAIL` displays the standard audit trail entries related to the current user.

Its columns are the same as those in "DBA_AUDIT_TRAIL".

The view displays audit records generated by actions performed by the user and audit records generated by actions performed on the user's schema objects.

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

7.406 USER_AW_PS

USER_AW_PS describes the page spaces in the analytic workspaces owned by the current user. Its columns (except for OWNER) are the same as those in ALL_AW_PS.

> **See Also:**
>
> "ALL_AW_PS"

7.407 USER_AWS

USER_AWS describes the analytic workspaces owned by the current user. Its columns (except for OWNER) are the same as those in ALL_AWS.

> **See Also:**
>
> "ALL_AWS"

7.408 USER_BASE_TABLE_MVIEWS

USER_BASE_TABLE_MVIEWS describes the materialized views using materialized view logs owned by the current user. Its columns are the same as those in ALL_BASE_TABLE_MVIEWS.

> **See Also:**
>
> "ALL_BASE_TABLE_MVIEWS"

7.409 USER_BLOCKCHAIN_ROW_VERSION_COLS

USER_BLOCKCHAIN_ROW_VERSION_COLS displays information about row versioned columns in the blockchain tables owned by the current user. Its columns are the same as those in ALL_BLOCKCHAIN_ROW_VERSION_COLS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_BLOCKCHAIN_ROW_VERSION_COLS"

7.410 USER_BLOCKCHAIN_ROW_VERSION_HISTORY

`USER_BLOCKCHAIN_ROW_VERSION_HISTORY` provides a history of row versions in the blockchain tables owned by the current user. Its columns (except for `SCHEMA_NAME`) are the same as those in `ALL_BLOCKCHAIN_ROW_VERSION_HISTORY`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_BLOCKCHAIN_ROW_VERSION_HISTORY"

7.411 USER_BLOCKCHAIN_TABLE_CHAINS

`USER_BLOCKCHAIN_TABLE_CHAINS` displays system chain information for the blockchain tables owned by the current user. Its columns (except for `SCHEMA_NAME`) are the same as those in `ALL_BLOCKCHAIN_TABLE_CHAINS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_BLOCKCHAIN_TABLE_CHAINS"

7.412 USER_BLOCKCHAIN_TABLE_EPOCHS

USER_BLOCKCHAIN_TABLE_EPOCHS displays epoch information for the blockchain tables owned by the current user. Its columns (except for SCHEMA_NAME) are the same as those in ALL_BLOCKCHAIN_TABLE_EPOCHS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_BLOCKCHAIN_TABLE_EPOCHS"

7.413 USER_BLOCKCHAIN_TABLE_HASH_COL_ORDER

USER_BLOCKCHAIN_TABLE_HASH_COL_ORDER displays information about columns used to compute the cryptographic hash in the blockchain tables owned by the current user. Its columns (except for SCHEMA_NAME) are the same as those in ALL_BLOCKCHAIN_TABLE_HASH_COL_ORDER.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_BLOCKCHAIN_TABLE_HASH_COL_ORDER"

7.414 USER_BLOCKCHAIN_TABLES

USER_BLOCKCHAIN_TABLES describes the blockchain tables owned by the current user. Its columns (except for SCHEMA_NAME) are the same as those in ALL_BLOCKCHAIN_TABLES.

> **See Also:**
>
> "ALL_BLOCKCHAIN_TABLES"

7.415 USER_CATALOG

USER_CATALOG lists tables, views, clusters, synonyms, and sequences owned by the current user. Its columns are the same as those in ALL_CATALOG.

> **See Also:**
>
> "ALL_CATALOG"

7.416 USER_CERTIFICATES

USER_CERTIFICATES displays the certificates added by the current user which are used for signature verification for blockchain tables. Its columns (except USER_NAME) are the same as those in ALL_CERTIFICATES.

> **See Also:**
>
> "ALL_CERTIFICATES"

7.417 USER_CHANGE_NOTIFICATION_REGS

USER_CHANGE_NOTIFICATION_REGS describes the change notification registrations owned by the current user. Its columns (except for USERNAME) are the same as those in DBA_CHANGE_NOTIFICATION_REGS.

> **See Also:**
>
> "DBA_CHANGE_NOTIFICATION_REGS"

7.418 USER_CLU_COLUMNS

USER_CLU_COLUMNS maps columns in the current user's tables to cluster columns. Its columns are the same as those in DBA_CLU_COLUMNS.

> **See Also:**
>
> "DBA_CLU_COLUMNS"

7.419 USER_CLUSTER_HASH_EXPRESSIONS

`USER_CLUSTER_HASH_EXPRESSIONS` lists hash functions for the hash clusters owned by the current user. Its columns are the same as those in `ALL_CLUSTER_HASH_EXPRESSIONS`.

> **See Also:**
>
> "ALL_CLUSTER_HASH_EXPRESSIONS"

7.420 USER_CLUSTERING_DIMENSIONS

`USER_CLUSTERING_DIMENSIONS` describes dimension tables associated with tables with an attribute clustering clause owned by the user. Its columns (except for `OWNER`) are the same as those in `ALL_CLUSTERING_DIMENSIONS`.

> **See Also:**
>
> - "ALL_CLUSTERING_DIMENSIONS"
> - *Oracle Database Data Warehousing Guide* for information about attribute clustering with zone maps

7.421 USER_CLUSTERING_JOINS

`USER_CLUSTERING_JOINS` describes joins to the dimension tables associated with tables with an attribute clustering clause owned by the user. Its columns (except for `OWNER`) are the same as those in `ALL_CLUSTERING_JOINS`.

> **See Also:**
>
> - "ALL_CLUSTERING_JOINS"
> - *Oracle Database Data Warehousing Guide* for information about attribute clustering with zone maps

7.422 USER_CLUSTERING_KEYS

`USER_CLUSTERING_KEYS` describes clustering keys for tables with an attribute clustering clause owned by the user. Its columns are the same as those in `ALL_CLUSTERING_KEYS`.

> **See Also:**
>
> - "ALL_CLUSTERING_KEYS"
> - *Oracle Database Data Warehousing Guide* for information about attribute clustering with zone maps

7.423 USER_CLUSTERING_TABLES

`USER_CLUSTERING_TABLES` describes the tables with an attribute clustering clause owned by the user. Its columns are the same as those in `ALL_CLUSTERING_TABLES`.

> **See Also:**
>
> - "ALL_CLUSTERING_TABLES"
> - *Oracle Database Data Warehousing Guide* for information about attribute clustering with zone maps

7.424 USER_CLUSTERS

`USER_CLUSTERS` describes all the clusters owned by the current user. Its columns are the same as those in `ALL_CLUSTERS`.

> **See Also:**
>
> "ALL_CLUSTERS"

7.425 USER_CODE_ROLE_PRIVS

USER_CODE_ROLE_PRIVS describes all the roles that are associated with program units owned by current user. Its columns (except for OWNER) are the same as those in ALL_CODE_ROLE_PRIVS.

> **See Also:**
>
> "ALL_CODE_ROLE_PRIVS"

7.426 USER_COL_COMMENTS

USER_COL_COMMENTS displays comments on the columns of the tables and views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_COL_COMMENTS.

> **See Also:**
>
> "ALL_COL_COMMENTS"

7.427 USER_COL_PENDING_STATS

USER_COL_PENDING_STATS describes the pending statistics of the columns owned by the current user. Its columns (except for OWNER) are the same as those in ALL_COL_PENDING_STATS.

> **See Also:**
>
> "ALL_COL_PENDING_STATS"

7.428 USER_COL_PRIVS

USER_COL_PRIVS describes the column object grants for which the current user is the object owner, grantor, or grantee. Its columns are the same as those in DBA_COL_PRIVS.

> **See Also:**
>
> "DBA_COL_PRIVS"

7.429 USER_COL_PRIVS_MADE

USER_COL_PRIVS_MADE describes the column object grants for which the current user is the object owner. Its columns (except for OWNER) are the same as those in ALL_COL_PRIVS_MADE.

> **See Also:**
>
> "ALL_COL_PRIVS_MADE"

7.430 USER_COL_PRIVS_RECD

USER_COL_PRIVS_RECD describes the column object grants for which the current user is the grantee. Its columns (except for GRANTEE) are the same as those in ALL_COL_PRIVS_RECD.

> **See Also:**
>
> "ALL_COL_PRIVS_RECD"

7.431 USER_COLL_TYPES

USER_COLL_TYPES describes named collection types (VARRAYs, nested tables, object tables, and so on) in the current user's schema. Its columns are the same as those in ALL_COLL_TYPES.

> **See Also:**
>
> "ALL_COLL_TYPES"

7.432 USER_COMPARISON

USER_COMPARISON displays information about the comparison objects owned by the current user. Its columns (except for OWNER) are the same as those in DBA_COMPARISON.

> **See Also:**
>
> "DBA_COMPARISON"

7.433 USER_COMPARISON_COLUMNS

`USER_COMPARISON_COLUMNS` displays information about the columns for the comparison objects owned by the current user. Its columns (except for `OWNER`) are the same as those in `DBA_COMPARISON_COLUMNS`.

> **See Also:**
>
> "DBA_COMPARISON_COLUMNS"

7.434 USER_COMPARISON_ROW_DIF

`USER_COMPARISON_ROW_DIF` displays information about the differing rows in the comparison scans owned by the current user. Its columns are the same as those in `DBA_COMPARISON_ROW_DIF`.

> **See Also:**
>
> "DBA_COMPARISON_ROW_DIF"

7.435 USER_COMPARISON_SCAN

`USER_COMPARISON_SCAN` displays information about the comparison scans owned by the current user. Its columns (except for `OWNER`) are the same as those in `DBA_COMPARISON_SCAN`.

> **See Also:**
>
> "DBA_COMPARISON_SCAN"

7.436 USER_COMPARISON_SCAN_VALUES

`USER_COMPARISON_SCAN_VALUES` displays information about the values for the comparison scans owned by the current user. Its columns (except for `OWNER`) are the same as those in `DBA_COMPARISON_SCAN_VALUES`.

> **See Also:**
>
> "DBA_COMPARISON_SCAN_VALUES"

7.437 USER_CONS_COLUMNS

USER_CONS_COLUMNS describes columns that are owned by the current user and that are specified in constraint definitions. Its columns are the same as those in ALL_CONS_COLUMNS.

> **See Also:**
>
> "ALL_CONS_COLUMNS"

7.438 USER_CONS_OBJ_COLUMNS

USER_CONS_OBJ_COLUMNS displays information about the types that object columns (or attributes) or collection elements have been constrained to, in the tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CONS_OBJ_COLUMNS.

> **See Also:**
>
> "ALL_CONS_OBJ_COLUMNS"

7.439 USER_CONSTRAINTS

USER_CONSTRAINTS describes all constraint definitions on tables owned by the current user. Its columns are the same as those in ALL_CONSTRAINTS.

> **See Also:**
>
> "ALL_CONSTRAINTS"

7.440 USER_CQ_NOTIFICATION_QUERIES

USER_CQ_NOTIFICATION_QUERIES describes the registered queries for the CQ notifications owned by the current user. Its columns (except for USERNAME) are the same as those in DBA_CQ_NOTIFICATION_QUERIES.

> **See Also:**
>
> "DBA_CQ_NOTIFICATION_QUERIES"

7.441 USER_CREDENTIALS

`USER_CREDENTIALS` displays credentials owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_CREDENTIALS`.

> **See Also:**
>
> "ALL_CREDENTIALS"

7.442 USER_CUBE_ATTR_VISIBILITY

`USER_CUBE_ATTR_VISIBILITY` describes the OLAP attributes visible for the dimensions, hierarchies, and levels owned by the current user Its columns (except for `OWNER`) are the same as those in `ALL_CUBE_ATTR_VISIBILITY`.

> **See Also:**
>
> "ALL_CUBE_ATTR_VISIBILITY"

7.443 USER_CUBE_ATTRIBUTES

`USER_CUBE_ATTRIBUTES` describes the attributes for the OLAP cube dimensions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_CUBE_ATTRIBUTES`.

> **See Also:**
>
> "ALL_CUBE_ATTRIBUTES"

7.444 USER_CUBE_BUILD_PROCESSES

`USER_CUBE_BUILD_PROCESSES` describes the OLAP build processes and maintenance scripts owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_CUBE_BUILD_PROCESSES`.

> **See Also:**
>
> "ALL_CUBE_BUILD_PROCESSES"

7.445 USER_CUBE_CALCULATED_MEMBERS

USER_CUBE_CALCULATED_MEMBERS describes the calculated members for the OLAP cube dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_CALCULATED_MEMBERS.

> **See Also:**
>
> "ALL_CUBE_CALCULATED_MEMBERS"

7.446 USER_CUBE_DIM_LEVELS

USER_CUBE_DIM_LEVELS describes the OLAP dimension levels owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_DIM_LEVELS.

> **See Also:**
>
> "ALL_CUBE_DIM_LEVELS"

7.447 USER_CUBE_DIM_MODELS

USER_CUBE_DIM_MODELS describes the models for the OLAP dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_DIM_MODELS.

> **See Also:**
>
> "ALL_CUBE_DIM_MODELS"

7.448 USER_CUBE_DIM_VIEW_COLUMNS

USER_CUBE_DIM_VIEW_COLUMNS describes the columns of the relational views of the OLAP cube dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_DIM_VIEW_COLUMNS.

> **See Also:**
>
> "ALL_CUBE_DIM_VIEW_COLUMNS"

7.449 USER_CUBE_DIM_VIEWS

USER_CUBE_DIM_VIEWS describes the relational views of the OLAP dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_DIM_VIEWS.

> **See Also:**
>
> "ALL_CUBE_DIM_VIEWS"

7.450 USER_CUBE_DIMENSIONALITY

USER_CUBE_DIMENSIONALITY describes the dimension order for the OLAP cubes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_DIMENSIONALITY.

> **See Also:**
>
> "ALL_CUBE_DIMENSIONALITY"

7.451 USER_CUBE_DIMENSIONS

USER_CUBE_DIMENSIONS describes the OLAP cube dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_DIMENSIONS.

> **See Also:**
>
> "ALL_CUBE_DIMENSIONS"

7.452 USER_CUBE_HIER_LEVELS

USER_CUBE_HIER_LEVELS describes the hierarchy levels for the OLAP cube dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_HIER_LEVELS.

> **See Also:**
>
> "ALL_CUBE_HIER_LEVELS"

7.453 USER_CUBE_HIER_VIEW_COLUMNS

USER_CUBE_HIER_VIEW_COLUMNS describes the columns of the relational hierarchy views of the OLAP cube dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_HIER_VIEW_COLUMNS.

> **See Also:**
>
> "ALL_CUBE_HIER_VIEW_COLUMNS"

7.454 USER_CUBE_HIER_VIEWS

USER_CUBE_HIER_VIEWS describes the hierarchies for the OLAP cube dimensions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_HIER_VIEWS.

> **See Also:**
>
> "ALL_CUBE_HIER_VIEWS"

7.455 USER_CUBE_HIERARCHIES

USER_CUBE_HIERARCHIES describes the OLAP dimension hierarchies owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_HIERARCHIES.

> **See Also:**
>
> "ALL_CUBE_HIERARCHIES"

7.456 USER_CUBE_MEASURES

USER_CUBE_MEASURES describes the measures for the OLAP cubes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_MEASURES.

> **See Also:**
>
> "ALL_CUBE_MEASURES"

7.457 USER_CUBE_NAMED_BUILD_SPECS

USER_CUBE_NAMED_BUILD_SPECS describes the OLAP cube named build specifications in the database that are owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_NAMED_BUILD_SPECS.

> **See Also:**
>
> "ALL_CUBE_NAMED_BUILD_SPECS"

7.458 USER_CUBE_SUB_PARTITION_LEVELS

USER_CUBE_SUB_PARTITION_LEVELS describes the OLAP secondary partition levels in the database that are owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_SUB_PARTITION_LEVELS.

> **See Also:**
>
> "ALL_CUBE_SUB_PARTITION_LEVELS"

7.459 USER_CUBE_VIEW_COLUMNS

USER_CUBE_VIEW_COLUMNS describes the columns of relational views of OLAP cubes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_VIEW_COLUMNS.

> **See Also:**
>
> "ALL_CUBE_VIEW_COLUMNS"

7.460 USER_CUBE_VIEWS

USER_CUBE_VIEWS describes the relational views of the OLAP cubes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_CUBE_VIEWS.

> **See Also:**
>
> "ALL_CUBE_VIEWS"

7.461 USER_CUBES

`USER_CUBES` describes the OLAP cubes owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_CUBES`.

> **See Also:**
>
> "ALL_CUBES"

7.462 USER_DATAPUMP_JOBS

`USER_DATAPUMP_JOBS` displays the Data Pump jobs owned by the current user. Its columns (except for `OWNER_NAME`) are the same as those in `DBA_DATAPUMP_JOBS`.

> **See Also:**
>
> "DBA_DATAPUMP_JOBS"

7.463 USER_DB_LINKS

`USER_DB_LINKS` describes the database links owned by the current user. Its columns are the same as those in `ALL_DB_LINKS` except that it does not have the `OWNER` column.

It also displays an additional column, `PASSWORD`, which is no longer used and for which nothing is returned. The `PASSWORD` column is maintained for backward compatibility only.

> **See Also:**
>
> "ALL_DB_LINKS"

7.464 USER_DBFS_HS

`USER_DBFS_HS` shows all Database File System (DBFS) hierarchical stores owned by the current user. Its columns (except for `STOREOWNER`) are the same as those in `DBA_DBFS_HS`.

> **See Also:**
>
> "DBA_DBFS_HS"

7.465 USER_DBFS_HS_COMMANDS

USER_DBFS_HS_COMMANDS shows all the registered store commands for all Database File system (DBFS) hierarchical stores owned by current user. Its columns (except for STOREOWNER) are the same as those in DBA_DBFS_HS_COMMANDS.

> **See Also:**
>
> "DBA_DBFS_HS_COMMANDS"

7.466 USER_DBFS_HS_FILES

USER_DBFS_HS_FILES displays files in the Database File System (DBFS) hierarchical store owned by the current user and their location on the back-end device.

Column	Datatype	NULL	Description
PATH	VARCHAR2(1024)		Path name of the file
SEQUENCENUMBER	NUMBER		Sequence number of this piece of the file
STARTOFFSET	NUMBER		Begin offset of this piece in the tarball
ENDOFFSET	NUMBER		End offset of this piece in the tarball
TARBALLID	NUMBER		Tarball ID
BACKUPFILENAME	VARCHAR2(256)		File on back end in which this tarball is located
TARSTARTOFFSET	NUMBER		Begin offset of this tarball in the backup file
TARENDOFFSET	NUMBER		End offset of this tarball in the backup file

7.467 USER_DBFS_HS_FIXED_PROPERTIES

USER_DBFS_HS_FIXED_PROPERTIES shows non-modifiable properties of all Databaase File System (DBFS) hierarchical stores owned by current user. Its columns (except for STORE_OWNER) are the same as those in DBA_DBFS_HS_FIXED_PROPERTIES.

> **See Also:**
>
> "DBA_DBFS_HS_FIXED_PROPERTIES"

7.468 USER_DBFS_HS_PROPERTIES

`USER_DBFS_HS_PROPERTIES` shows modifiable properties of all Database File System (DBFS) hierarchical stores owned by current user. Its columns (except for `STOREOWNER`) are the same as those in `DBA_DBFS_HS_PROPERTIES`.

> **See Also:**
>
> "DBA_DBFS_HS_PROPERTIES"

7.469 USER_DDL_REGS

`USER_DDL_REGS` displays DDL notification registrations that apply to tables owned by the current user. Its columns (except for `USERNAME`) are the same as those in `DBA_DDL_REGS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "DBA_DDL_REGS"

7.470 USER_DEPENDENCIES

`USER_DEPENDENCIES` describes dependencies between procedures, packages, functions, package bodies, and triggers owned by the current user, including dependencies on views created without any database links. Its columns are the same as those in `ALL_DEPENDENCIES`.

> **See Also:**
>
> "ALL_DEPENDENCIES"

7.471 USER_DIM_ATTRIBUTES

`USER_DIM_ATTRIBUTES` describes the relationship between dimension levels and functionally dependent columns in the current user's schema.

The level columns and the dependent column must be in the same table. This view's columns are the same as those in `ALL_DIM_ATTRIBUTES`.

> **See Also:**
>
> "ALL_DIM_ATTRIBUTES"

7.472 USER_DIM_CHILD_OF

`USER_DIM_CHILD_OF` describes a hierarchical relationship of 1 to *n* between pairs of levels in dimensions owned by the current user. Its columns are the same as those in `ALL_DIM_CHILD_OF`.

> **See Also:**
>
> "ALL_DIM_CHILD_OF"

7.473 USER_DIM_HIERARCHIES

`USER_DIM_HIERARCHIES` describes the dimension hierarchies owned by the current user. Its columns are the same as those in `ALL_DIM_HIERARCHIES`.

> **See Also:**
>
> "ALL_DIM_HIERARCHIES"

7.474 USER_DIM_JOIN_KEY

`USER_DIM_JOIN_KEY` describes the join between two dimension tables owned by the current user. The join is always specified between a parent dimension level column and a child column. This view's columns are the same as those in `ALL_DIM_JOIN_KEY`.

> **See Also:**
>
> "ALL_DIM_JOIN_KEY"

7.475 USER_DIM_LEVEL_KEY

USER_DIM_LEVEL_KEY describes columns of dimension levels owned by the current user. This view's columns are the same as those in ALL_DIM_LEVEL_KEY.

> **See Also:**
>
> "ALL_DIM_LEVEL_KEY"

7.476 USER_DIM_LEVELS

USER_DIM_LEVELS describes the levels of dimensions owned by the current user. All columns of a dimension level must come from the same relation. This view's columns are the same as those in ALL_DIM_LEVELS.

> **See Also:**
>
> "ALL_DIM_LEVELS"

7.477 USER_DIMENSIONS

USER_DIMENSIONS describes dimension objects in the user's schema. Its columns are the same as those in ALL_DIMENSIONS.

> **See Also:**
>
> "ALL_DIMENSIONS"

7.478 USER_DOMAIN_COLS

USER_DOMAIN_COLS describes columns of the data use case domains owned by the current user. Its columns are the same as those in ALL_DOMAIN_COLS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_DOMAIN_COLS"

7.479 USER_DOMAIN_CONSTRAINTS

`USER_DOMAIN_CONSTRAINTS` describes constraint definitions on the data use case domains owned by the current user. Its columns are the same as those in `ALL_DOMAIN_CONSTRAINTS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_DOMAIN_CONSTRAINTS"

7.480 USER_DOMAINS

`USER_DOMAINS` describes the data use casedomains owned by the current user. Its columns are the same as those in `ALL_DOMAINS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_DOMAINS"

7.481 USER_EDITIONED_TYPES

USER_EDITIONED_TYPES lists the types that are editioned by default for the current user. Its columns (except for SCHEMA) are the same as those in DBA_EDITIONED_TYPES.

> **See Also:**
>
> "DBA_EDITIONED_TYPES"

7.482 USER_EDITIONING_VIEW_COLS

USER_EDITIONING_VIEW_COLS describes the relationship between the columns of the editioning views owned by the current user and the table columns to which they map. Its columns (except for OWNER) are the same as those in ALL_EDITIONING_VIEW_COLS.

> **See Also:**
>
> "ALL_EDITIONING_VIEW_COLS"

7.483 USER_EDITIONING_VIEW_COLS_AE

USER_EDITIONING_VIEW_COLS_AE describes the relationship between the columns of the editioning views (across all editions) owned by the current user and the table columns to which they map. Its columns (except for OWNER) are the same as those in ALL_EDITIONING_VIEW_COLS_AE.

> **See Also:**
>
> "ALL_EDITIONING_VIEW_COLS_AE"

7.484 USER_EDITIONING_VIEWS

USER_EDITIONING_VIEWS describes the editioning views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_EDITIONING_VIEWS.

> **See Also:**
>
> "ALL_EDITIONING_VIEWS"

7.485 USER_EDITIONING_VIEWS_AE

USER_EDITIONING_VIEWS_AE describes the editioning views (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_EDITIONING_VIEWS_AE.

> **See Also:**
>
> "ALL_EDITIONING_VIEWS_AE"

7.486 USER_ENCRYPTED_COLUMNS

USER_ENCRYPTED_COLUMNS maintains encryption algorithm information for all encrypted columns in all tables in the user's schema. Its columns (except for OWNER) are the same as those in ALL_ENCRYPTED_COLUMNS.

> **See Also:**
>
> "ALL_ENCRYPTED_COLUMNS"

7.487 USER_EPG_DAD_AUTHORIZATION

USER_EPG_DAD_AUTHORIZATION describes the DADs that are authorized to use the user's privileges. Its columns (except for USERNAME) are the same as those in DBA_EPG_DAD_AUTHORIZATION.

> **See Also:**
>
> "DBA_EPG_DAD_AUTHORIZATION"

7.488 USER_ERROR_TRANSLATIONS

USER_ERROR_TRANSLATIONS describes all error translations owned by the user. Its columns (except for OWNER) are the same as those in ALL_ERROR_TRANSLATIONS.

> **See Also:**
>
> "ALL_ERROR_TRANSLATIONS"

7.489 USER_ERRORS

USER_ERRORS describes the current errors on the stored objects owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ERRORS.

> **See Also:**
>
> "ALL_ERRORS"

7.490 USER_ERRORS_AE

USER_ERRORS_AE describes the current errors on the stored objects (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_ERRORS_AE.

> **See Also:**
>
> "ALL_ERRORS_AE"

7.491 USER_EVALUATION_CONTEXT_TABLES

USER_EVALUATION_CONTEXT_TABLES describes the tables in the rule evaluation contexts owned by the current user. Its columns (except for EVALUATION_CONTEXT_OWNER) are the same as those in ALL_EVALUATION_CONTEXT_TABLES.

> **See Also:**
>
> "ALL_EVALUATION_CONTEXT_TABLES"

7.492 USER_EVALUATION_CONTEXT_VARS

USER_EVALUATION_CONTEXT_VARS describes the variables in the rule evaluation contexts owned by the current user. Its columns (except for EVALUATION_CONTEXT_OWNER) are the same as those in ALL_EVALUATION_CONTEXT_VARS.

> **See Also:**
>
> "ALL_EVALUATION_CONTEXT_VARS"

7.493 USER_EVALUATION_CONTEXTS

USER_EVALUATION_CONTEXTS describes the rule evaluation contexts owned by the current user. Its columns (except for EVALUATION_CONTEXT_OWNER) are the same as those in ALL_EVALUATION_CONTEXTS.

> **See Also:**
>
> "ALL_EVALUATION_CONTEXTS"

7.494 USER_EXPRESSION_STATISTICS

USER_EXPRESSION_STATISTICS provides expression usage tracking statistics for tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_EXPRESSION_STATISTICS.

> **See Also:**
>
> "ALL_EXPRESSION_STATISTICS"

7.495 USER_EXTENTS

USER_EXTENTS describes the extents comprising the segments owned by the current user's objects. Its columns (except for OWNER, FILE_ID, BLOCK_ID, and RELATIVE_FNO) are the same as those in DBA_EXTENTS.

> **See Also:**
>
> "DBA_EXTENTS"

7.496 USER_EXTERNAL_LOCATIONS

USER_EXTERNAL_LOCATIONS describes the locations (data sources) of the external tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_EXTERNAL_LOCATIONS.

> **See Also:**
>
> "ALL_EXTERNAL_LOCATIONS"

7.497 USER_EXTERNAL_TABLES

USER_EXTERNAL_TABLES describes the external tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_EXTERNAL_TABLES.

> **See Also:**
>
> "ALL_EXTERNAL_TABLES"

7.498 USER_FLASHBACK_ARCHIVE

USER_FLASHBACK_ARCHIVE describes flashback data archives, which consist of multiple tablespaces and historic data from all transactions against tracked tables.

The content of this view depends on the privileges of the user who queries it, as follows:

- If the user has the FLASHBACK ARCHIVE ADMINISTER system privilege, then USER_FLASHBACK_ARCHIVE describes the flashback archives for all users who have been granted the FLASHBACK ARCHIVE object privilege.
- If the user does not have the FLASHBACK ARCHIVE ADMINISTER system privilege, then USER_FLASHBACK_ARCHIVE describes flashback archives for which the current user has been granted the FLASHBACK ARCHIVE object privilege.

The columns of the USER_FLASHBACK_ARCHIVE view are the same as those in DBA_FLASHBACK_ARCHIVE.

> **See Also:**
>
> "DBA_FLASHBACK_ARCHIVE"

7.499 USER_FLASHBACK_ARCHIVE_TABLES

USER_FLASHBACK_ARCHIVE_TABLES displays information about the tables owned by the current user that are enabled for Flashback Archive. Its columns are the same as those in DBA_FLASHBACK_ARCHIVE_TABLES.

> **See Also:**
>
> "DBA_FLASHBACK_ARCHIVE_TABLES"

7.500 USER_FLASHBACK_TXN_REPORT

USER_FLASHBACK_TXN_REPORT displays information about the compensating transactions owned by the current user that have been committed in the database. Its columns (except for USERNAME) are the same as those in DBA_FLASHBACK_TXN_REPORT.

> **See Also:**
>
> "DBA_FLASHBACK_TXN_REPORT"

7.501 USER_FLASHBACK_TXN_STATE

USER_FLASHBACK_TXN_STATE displays information about the compensating status of the transactions owned by the current user. Its columns (except for USERNAME) are the same as those in DBA_FLASHBACK_TXN_STATE.

> **See Also:**
>
> "DBA_FLASHBACK_TXN_STATE"

7.502 USER_FREE_SPACE

USER_FREE_SPACE describes the free extents in the tablespaces accessible to the current user. Its columns are the same as those in DBA_FREE_SPACE.

> **See Also:**
>
> "DBA_FREE_SPACE"

7.503 USER_GOLDENGATE_PRIVILEGES

USER_GOLDENGATE_PRIVILEGES displays details about Oracle GoldenGate privileges. Its columns (except for USERNAME) are the same as those in ALL_GOLDENGATE_PRIVILEGES.

> **See Also:**
>
> "ALL_GOLDENGATE_PRIVILEGES"

7.504 USER_HEAT_MAP_SEG_HISTOGRAM

`USER_HEAT_MAP_SEG_HISTOGRAM` displays segment access information for segments owned by the user. Its columns (except for `OWNER`) are the same as those in `ALL_HEAT_MAP_SEG_HISTOGRAM`.

> **See Also:**
>
> "ALL_HEAT_MAP_SEG_HISTOGRAM"

7.505 USER_HEAT_MAP_SEGMENT

`USER_HEAT_MAP_SEGMENT` displays the latest segment access time for all segments owned by the user. Its columns (except for `OWNER`) are the same as those in `ALL_HEAT_MAP_SEGMENT`.

> **See Also:**
>
> "ALL_HEAT_MAP_SEGMENT"

7.506 USER_HIER_CLASS

`USER_HIER_CLASS` describes the classifications of the hierarchies owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_HIER_CLASS`.

> **See Also:**
>
> "ALL_HIER_CLASS"

7.507 USER_HIER_CLASS_AE

`USER_HIER_CLASS_AE` describes the classifications of the hierarchies (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_HIER_CLASS_AE`.

> **See Also:**
>
> "ALL_HIER_CLASS_AE"

7.508 USER_HIER_COLUMNS

USER_HIER_COLUMNS describes the columns of the hierarchies owned by the current user. Its columns (except for OWNER) are the same as those in ALL_HIER_COLUMNS.

> **See Also:**
>
> "ALL_HIER_COLUMNS"

7.509 USER_HIER_COLUMNS_AE

USER_HIER_COLUMNS_AE describes the columns of the hierarchies (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_HIER_COLUMNS_AE.

> **See Also:**
>
> "ALL_HIER_COLUMNS_AE"

7.510 USER_HIER_HIER_ATTR_CLASS

USER_HIER_HIER_ATTR_CLASS describes the classifications of the hierarchical attributes of the hierarchies owned by the current user. Its columns (except for OWNER) are the same as those in ALL_HIER_HIER_ATTR_CLASS.

> **See Also:**
>
> "ALL_HIER_HIER_ATTR_CLASS"

7.511 USER_HIER_HIER_ATTR_CLASS_AE

USER_HIER_HIER_ATTR_CLASS_AE describes the classifications of the hierarchical attributes of the hierarchies (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_HIER_HIER_ATTR_CLASS_AE.

> **See Also:**
>
> "ALL_HIER_HIER_ATTR_CLASS_AE"

7.512 USER_HIER_HIER_ATTRIBUTES

USER_HIER_HIER_ATTRIBUTES describes the hierarchical attributes of the hierarchies owned by the current user. Its columns (except for OWNER) are the same as those in ALL_HIER_HIER_ATTRIBUTES.

> **See Also:**
>
> "ALL_HIER_HIER_ATTRIBUTES"

7.513 USER_HIER_HIER_ATTRIBUTES_AE

USER_HIER_HIER_ATTRIBUTES_AE describes the hierarchical attributes of the hierarchies (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_HIER_HIER_ATTRIBUTES_AE.

> **See Also:**
>
> "ALL_HIER_HIER_ATTRIBUTES_AE"

7.514 USER_HIER_JOIN_PATHS

USER_HIER_JOIN_PATHS describes the join paths for the hierarchies owned by the current user. Its columns (except for OWNER) are the same as those in ALL_HIER_JOIN_PATHS.

> **See Also:**
>
> "ALL_HIER_JOIN_PATHS"

7.515 USER_HIER_JOIN_PATHS_AE

USER_HIER_JOIN_PATHS_AE describes the join paths for the hierarchies (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_HIER_JOIN_PATHS_AE.

> **See Also:**
>
> "ALL_HIER_JOIN_PATHS_AE"

7.516 USER_HIER_LEVEL_ID_ATTRS

USER_HIER_LEVEL_ID_ATTRS describes the attributes that uniquely identify members of the levels of the hierarchies owned by the current user. Its columns (except for OWNER) are the same as those in ALL_HIER_LEVEL_ID_ATTRS.

> **See Also:**
>
> "ALL_HIER_LEVEL_ID_ATTRS"

7.517 USER_HIER_LEVEL_ID_ATTRS_AE

USER_HIER_LEVEL_ID_ATTRS_AE describes the attributes that uniquely identify members of the levels of the hierarchies (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_HIER_LEVEL_ID_ATTRS_AE.

> **See Also:**
>
> "ALL_HIER_LEVEL_ID_ATTRS_AE"

7.518 USER_HIER_LEVELS

USER_HIER_LEVELS describes the levels of the hierarchies owned by the current user. Its columns (except for OWNER) are the same as those in ALL_HIER_LEVELS.

> **See Also:**
>
> "ALL_HIER_LEVELS"

7.519 USER_HIER_LEVELS_AE

USER_HIER_LEVELS_AE describes the levels of the hierarchies (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_HIER_LEVELS_AE.

> **See Also:**
>
> "ALL_HIER_LEVELS_AE"

7.520 USER_HIERARCHIES

`USER_HIERARCHIES` describes the hierarchies owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_HIERARCHIES`.

> **See Also:**
>
> "ALL_HIERARCHIES"

7.521 USER_HIERARCHIES_AE

`USER_HIERARCHIES_AE` describes the hierarchies (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_HIERARCHIES_AE`.

> **See Also:**
>
> "ALL_HIERARCHIES_AE"

7.522 USER_HIST_SAGAS

`USER_HIST_SAGAS` provides a history of the completed sagas owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_HIST_SAGAS`.

This view displays sagas that were either initiated in the current PDB or joined by participants in the current PDB.

Completed sagas are retained in this view for the length of time specified by the `SAGA_HIST_RETENTION` initialization parameter. The default is 30 days.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "ALL_HIST_SAGAS"
> - "SAGA_HIST_RETENTION"

7.523 USER_HISTOGRAMS

`USER_HISTOGRAMS` is a synonym for `USER_TAB_HISTOGRAMS`.

> **See Also:**
>
> "USER_TAB_HISTOGRAMS"

7.524 USER_HIVE_COLUMNS

`USER_HIVE_COLUMNS` describes all Hive columns owned by the current user in a Hive metastore. Its columns are the same as those in `ALL_HIVE_COLUMNS`.

> **See Also:**
>
> "ALL_HIVE_COLUMNS"

7.525 USER_HIVE_DATABASES

`USER_HIVE_DATABASES` describes all the Hive schemas owned by the current user in a Hadoop cluster. Its columns are the same as those in `ALL_HIVE_DATABASES`.

> **See Also:**
>
> "ALL_HIVE_DATABASES"

7.526 USER_HIVE_PART_KEY_COLUMNS

`USER_HIVE_PART_KEY_COLUMNS` provides information about all Hive table partition columns owned by the current user in the database. Its columns are the same as those in `ALL_HIVE_PART_KEY_COLUMNS`.

> **See Also:**
>
> "ALL_HIVE_PART_KEY_COLUMNS"

7.527 USER_HIVE_TAB_PARTITIONS

USER_HIVE_TAB_PARTITIONS provides information about all Hive table partitions owned by the current user in the database. Its columns are the same as those in ALL_HIVE_TAB_PARTITIONS.

> **See Also:**
>
> "ALL_HIVE_TAB_PARTITIONS"

7.528 USER_HIVE_TABLES

USER_HIVE_TABLES provides information about all the Hive tables owned by the current user in the Hive metastore. Its columns are the same as those in ALL_HIVE_TABLES.

> **See Also:**
>
> "ALL_HIVE_TABLES"

7.529 USER_HOST_ACES

USER_HOST_ACES describes the status of access control entries for the current user to access network hosts through PL/SQL network utility packages.

Its columns (except for ACE_ORDER, START_DATE, END_DATE, GRANT_TYPE, INVERTED_PRINCIPAL, PRINCIPAL, PRINCIPAL_TYPE, and STATUS) are the same as those in DBA_HOST_ACES.

> **See Also:**
>
> "DBA_HOST_ACES"

7.530 USER_IDENTIFIERS

`USER_IDENTIFIERS` displays information about the identifiers in the stored objects owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_IDENTIFIERS`.

> **See Also:**
>
> "ALL_IDENTIFIERS"

7.531 USER_ILMDATAMOVEMENTPOLICIES

`USER_ILMDATAMOVEMENTPOLICIES` contains information specific to data movement-related attributes of an Automatic Data Optimization policy for a user. Its columns are the same as those in `DBA_ILMDATAMOVEMENTPOLICIES`.

> **Note:**
>
> Automatic Data Optimization is supported in Oracle Database 12*c* Release 2 multitenant environments.

> **See Also:**
>
> "DBA_ILMDATAMOVEMENTPOLICIES"

7.532 USER_ILMEVALUATIONDETAILS

`USER_ILMEVALUATIONDETAILS` displays details on evaluation of Automatic Data Optimization policies considered for Automatic Data Optimization tasks for a user.

It also shows the job name that executes the policy, in case the policy was selected for execution. If the policy was not selected for execution, this view provides a reason. Its columns are the same as those in `DBA_ILMEVALUATIONDETAILS`.

> **Note:**
>
> Automatic Data Optimization is supported in Oracle Database 12*c* Release 2 multitenant environments.

> **See Also:**
>
> "DBA_ILMEVALUATIONDETAILS"

7.533 USER_ILMOBJECTS

`USER_ILMOBJECTS` displays all the Automatic Data Optimization policies and objects for a user.

Many objects inherit policies via their parent objects or because they were created in a particular tablespace. This view provides a mapping between the policies and objects and indicates whether a policy is inherited by an object or is directly specified on it. Its columns are the same as those in `DBA_ILMOBJECTS`.

> **Note:**
>
> Automatic Data Optimization is supported in Oracle Database 12*c* Release 2 multitenant environments.

> **See Also:**
>
> "DBA_ILMOBJECTS"

7.534 USER_ILMPOLICIES

`USER_ILMPOLICIES` displays details about Automatic Data Optimization policies owned by the user.

The view contains common details relevant to all types of Automatic Data Optimization policies, not just details relevant to the data movement-related Automatic Data Optimization policies. Its columns are the same as those in `DBA_ILMPOLICIES`.

> **Note:**
>
> Automatic Data Optimization is supported in Oracle Database 12c Release 2 multitenant environments.

> **See Also:**
>
> "DBA_ILMPOLICIES"

7.535 USER_ILMRESULTS

`USER_ILMRESULTS` displays information on data movement-related Automatic Data Optimization jobs for tasks created by the user.

Its columns are the same as those in `DBA_ILMRESULTS`.

> **Note:**
>
> Automatic Data Optimization is supported in Oracle Database 12*c* Release 2 multitenant environments.

> **See Also:**
>
> "DBA_ILMRESULTS"

7.536 USER_ILMTASKS

`USER_ILMTASKS` displays information on Automatic Data Optimization tasks created by a user. Its columns are the same as those in `DBA_ILMTASKS`.

> **Note:**
>
> Automatic Data Optimization is supported in Oracle Database 12*c* Release 2 multitenant environments.

> **See Also:**
>
> "DBA_ILMTASKS"

7.537 USER_IM_EXPRESSIONS

`USER_IM_EXPRESSIONS` provides information about the list of expressions (SYS_IME virtual columns) that are currently enabled for in-memory storage in schemas owned by the current user. Its columns (except for `OWNER`) are the same as those in `DBA_IM_EXPRESSIONS`.

Typically, you can query this view after invoking the `DBMS_INMEMORY_ADMIN.IME_CAPTURE_EXPRESSIONS` PL/SQL procedure to see the list of hot expressions added to tables owned by you across the database.

Based on this view, you can:

- Populate expressions on a particular table immediately
- Drop certain expressions that are marked for in-memory but not desired by you

> **See Also:**
>
> "DBA_IM_EXPRESSIONS"

7.538 USER_IMMUTABLE_ROW_VERSION_COLS

`USER_IMMUTABLE_ROW_VERSION_COLS` displays information about row versioned columns in the immutable tables owned by the current user. Its columns are the same as those in `ALL_IMMUTABLE_ROW_VERSION_COLS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_IMMUTABLE_ROW_VERSION_COLS"

7.539 USER_IMMUTABLE_ROW_VERSION_HISTORY

`USER_IMMUTABLE_ROW_VERSION_HISTORY` provides a history of row versions in the immutable tables owned by the current user. Its columns (except for `SCHEMA_NAME`) are the same as those in `ALL_IMMUTABLE_ROW_VERSION_HISTORY`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_IMMUTABLE_ROW_VERSION_HISTORY"

7.540 USER_IMMUTABLE_TABLE_COLUMNS

`USER_IMMUTABLE_TABLE_COLUMNS` displays information about columns valid in each epoch in the immutable tables owned by the current user. Its columns (except for `SCHEMA_NAME`) are the same as those in `ALL_IMMUTABLE_TABLE_COLUMNS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_IMMUTABLE_TABLE_COLUMNS"

7.541 USER_IMMUTABLE_TABLE_EPOCHS

`USER_IMMUTABLE_TABLE_EPOCHS` displays epoch information for the immutable tables owned by the current user. Its columns (except for `SCHEMA_NAME`) are the same as those in `ALL_IMMUTABLE_TABLE_EPOCHS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_IMMUTABLE_TABLE_EPOCHS"

7.542 USER_IMMUTABLE_TABLES

`USER_IMMUTABLE_TABLES` describes the immutable tables owned by the current user. Its columns (except for `SCHEMA_NAME`) are the same as those in `ALL_IMMUTABLE_TABLES`.

> **See Also:**
>
> "ALL_IMMUTABLE_TABLES"

7.543 USER_INCOMPLETE_SAGAS

`USER_INCOMPLETE_SAGAS` describes the incomplete sagas owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_INCOMPLETE_SAGAS`.

This view displays sagas that were either initiated in the current PDB or joined by participants in the current PDB.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_INCOMPLETE_SAGAS"

7.544 USER_IND_COLUMNS

`USER_IND_COLUMNS` describes the columns of the indexes owned by the current user and columns of indexes on tables owned by the current user.

Its columns (except for `INDEX_OWNER` and `TABLE_OWNER`) are the same as those in "ALL_IND_COLUMNS".

7.545 USER_IND_EXPRESSIONS

`USER_IND_EXPRESSIONS` describes expressions of function-based indexes on tables owned by the current user. Its columns (except for `INDEX_OWNER` and `TABLE_OWNER`) are the same as those in `ALL_IND_EXPRESSIONS`.

> **See Also:**
>
> "ALL_IND_EXPRESSIONS"

7.546 USER_IND_PARTITIONS

`USER_IND_PARTITIONS` displays, for each index partition owned by the current user, the partition-level partitioning information, the storage parameters for the partition, and

various partition statistics generated by the DBMS_STATS package. Its columns are the same as those in ALL_IND_PARTITIONS.

> **See Also:**
>
> "ALL_IND_PARTITIONS"

7.547 USER_IND_PENDING_STATS

USER_IND_PENDING_STATS describes pending statistics for all tables, partitions, and subpartitions owned by the current user and collected using the DBMS_STATS package. Its columns (except for OWNER) are the same as those in ALL_IND_PENDING_STATS.

> **See Also:**
>
> "ALL_IND_PENDING_STATS"

7.548 USER_IND_STATISTICS

USER_IND_STATISTICS displays optimizer statistics for the indexes on the tables owned by the current user and collected using the DBMS_STATS package. Its columns (except for OWNER) are the same as those in ALL_IND_STATISTICS.

> **See Also:**
>
> "ALL_IND_STATISTICS"

7.549 USER_IND_SUBPARTITIONS

USER_IND_SUBPARTITIONS displays, for each index subpartition owned by the current user, the subpartition-level partitioning information, the storage parameters for the subpartition, and various subpartition statistics generated by the DBMS_STATS package.

Its columns are the same as those in "ALL_IND_SUBPARTITIONS".

7.550 USER_INDEXES

`USER_INDEXES` describes indexes owned by the current user. To gather statistics for this view, use the `DBMS_STATS` package. This view supports parallel partitioned index scans. Its columns (except for `OWNER`) are the same as those in `ALL_INDEXES`.

> **See Also:**
>
> "ALL_INDEXES"

7.551 USER_INDEXTYPE_ARRAYTYPES

`USER_INDEXTYPE_ARRAYTYPES` displays information about the array types specified by the indextypes owned by the current user. Its columns are the same as those in `ALL_INDEXTYPE_ARRAYTYPES`.

> **See Also:**
>
> "ALL_INDEXTYPE_ARRAYTYPES"

7.552 USER_INDEXTYPE_COMMENTS

`USER_INDEXTYPE_COMMENTS` displays comments for the user-defined indextypes owned by the current user. Its columns are the same as those in `ALL_INDEXTYPE_COMMENTS`.

> **See Also:**
>
> "ALL_INDEXTYPE_COMMENTS"

7.553 USER_INDEXTYPE_OPERATORS

`USER_INDEXTYPE_OPERATORS` lists all the operators supported by indextypes owned by the current user. Its columns are the same as those in `ALL_INDEXTYPE_OPERATORS`.

> **See Also:**
>
> "ALL_INDEXTYPE_OPERATORS"

7.554 USER_INDEXTYPES

USER_INDEXTYPES describes the indextypes owned by the current user. Its columns are the same as those in ALL_INDEXTYPES.

> **See Also:**
>
> "ALL_INDEXTYPES"

7.555 USER_INTERNAL_TRIGGERS

USER_INTERNAL_TRIGGERS describes the internal triggers on all tables owned by the current user. Its columns are the same as those in ALL_INTERNAL_TRIGGERS.

> **See Also:**
>
> "ALL_INTERNAL_TRIGGERS".

7.556 USER_JAVA_ARGUMENTS

USER_JAVA_ARGUMENTS displays argument information about the stored Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_ARGUMENTS.

> **See Also:**
>
> "ALL_JAVA_ARGUMENTS"

7.557 USER_JAVA_CLASSES

USER_JAVA_CLASSES displays class level information about the stored Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_CLASSES.

> **See Also:**
>
> "ALL_JAVA_CLASSES"

7.558 USER_JAVA_COMPILER_OPTIONS

`USER_JAVA_COMPILER_OPTIONS` displays information about the native compiler options owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_JAVA_COMPILER_OPTIONS`.

> **See Also:**
>
> "ALL_JAVA_COMPILER_OPTIONS"

7.559 USER_JAVA_DERIVATIONS

`USER_JAVA_DERIVATIONS` displays mapping information about Java source objects and their derived Java class objects and Java resource objects for the Java classes owned by the current user.

Its columns (except for `OWNER`) are the same as those in `ALL_JAVA_DERIVATIONS`.

> **See Also:**
>
> "ALL_JAVA_DERIVATIONS"

7.560 USER_JAVA_FIELDS

`USER_JAVA_FIELDS` displays field information about the stored Java classes owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_JAVA_FIELDS`.

> **See Also:**
>
> "ALL_JAVA_FIELDS"

7.561 USER_JAVA_IMPLEMENTS

`USER_JAVA_IMPLEMENTS` describes interfaces implemented by the stored Java classes owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_JAVA_IMPLEMENTS`.

> **See Also:**
>
> "ALL_JAVA_IMPLEMENTS"

7.562 USER_JAVA_INNERS

`USER_JAVA_INNERS` displays information about inner classes referred to by the stored Java classes owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_JAVA_INNERS`.

> **See Also:**
>
> "ALL_JAVA_INNERS"

7.563 USER_JAVA_LAYOUTS

`USER_JAVA_LAYOUTS` displays class layout information about the stored Java classes owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_JAVA_LAYOUTS`.

> **See Also:**
>
> "ALL_JAVA_LAYOUTS"

7.564 USER_JAVA_METHODS

`USER_JAVA_METHODS` displays method information about the stored Java classes owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_JAVA_METHODS`.

> **See Also:**
>
> "ALL_JAVA_METHODS"

7.565 USER_JAVA_NCOMPS

USER_JAVA_NCOMPS displays ncomp-related information about the Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_NCOMPS.

> **See Also:**
>
> "ALL_JAVA_NCOMPS"

7.566 USER_JAVA_POLICY

USER_JAVA_POLICY describes Java security permissions for the current user. Its columns are the same as those in DBA_JAVA_POLICY.

> **See Also:**
>
> "DBA_JAVA_POLICY"

7.567 USER_JAVA_RESOLVERS

USER_JAVA_RESOLVERS displays information about resolvers of the Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_RESOLVERS.

> **See Also:**
>
> "ALL_JAVA_RESOLVERS"

7.568 USER_JAVA_THROWS

USER_JAVA_THROWS displays information about exceptions thrown from methods of the Java classes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JAVA_THROWS.

> **See Also:**
>
> "ALL_JAVA_THROWS"

7.569 USER_JOBS

`USER_JOBS` describes the jobs owned by the current user. Its columns are the same as those in `DBA_JOBS`.

> **See Also:**
>
> "DBA_JOBS"

7.570 USER_JOIN_IND_COLUMNS

`USER_JOIN_IND_COLUMNS` describes all join conditions owned by the current user. Its columns are the same as those in `ALL_JOIN_IND_COLUMNS`.

> **See Also:**
>
> "ALL_JOIN_IND_COLUMNS"

7.571 USER_JOINGROUPS

`USER_JOINGROUPS` describes join groups belonging to the user. A join group is a user-created object that consists of two or more columns that can be meaningfully joined. The maximum number of columns that can be included in a join group is 255. The `USER_JOINGROUPS` columns (except for `JOINGROUP_OWNER`) are the same as those in `DBA_JOINGROUPS`.

In certain queries, join groups enable the database to eliminate the performance overhead of decompressing and hashing column values. Join groups require an In-Memory column store (IM column store).

> **See Also:**
>
> - "DBA_JOINGROUPS"
> - *Oracle Database In-Memory Guide* for an introduction to join groups
> - *Oracle Database SQL Language Reference* for information about creating a join group using the `CREATE INMEMORY JOIN GROUP` statement

7.572 USER_JSON_COLLECTION_TABLES

`USER_JSON_COLLECTION_TABLES` describes JSON collection tables owned by the current user. Its columns are the same as those in `ALL_JSON_COLLECTION_TABLES`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_COLLECTION_TABLES"

7.573 USER_JSON_COLLECTIONS

`USER_JSON_COLLECTIONS` describes JSON collections owned by the current user. Its columns are the same as those in `ALL_JSON_COLLECTIONS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_COLLECTIONS"

7.574 USER_JSON_COLUMNS

`USER_JSON_COLUMNS` provides information on the JavaScript Object Notation (JSON) columns for which the user is the owner. Its columns (except for `OWNER`) are the same as those in `ALL_JSON_COLUMNS`.

> **See Also:**
>
> - "ALL_JSON_COLUMNS"
> - *Oracle Database JSON Developer's Guide* for more information about using JSON with Oracle Database

7.575 USER_JSON_DATAGUIDE_FIELDS

USER_JSON_DATAGUIDE_FIELDS extracts the path and type information from all the data guides in the current user's schema, which are the data guides returned to the user by the USER_JSON_DATAGUIDE view. Its columns (except for OWNER) are the same as those in ALL_JSON_DATAGUIDE_FIELDS.

> **See Also:**
>
> "ALL_JSON_DATAGUIDE_FIELDS"

7.576 USER_JSON_DATAGUIDES

USER_JSON_DATAGUIDES provides information on the JavaScript Object Notation (JSON) columns owned by the current user that have data guide enabled. Its columns (except for OWNER) are the same as those in ALL_JSON_DATAGUIDES.

> **See Also:**
>
> "ALL_JSON_DATAGUIDES"

7.577 USER_JSON_DOMAIN_SCHEMA_COLUMNS

USER_JSON_DOMAIN_SCHEMA_COLUMNS describes JSON schema constraints on columns of data use case domains owned by the current user. Its columns (except for OWNER) are the same as those in ALL_JSON_DOMAIN_SCHEMA_COLUMNS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_DOMAIN_SCHEMA_COLUMNS"

7.578 USER_JSON_DUALITY_VIEW_LINKS

`USER_JSON_DUALITY_VIEW_LINKS` describes the links associated with the JSON-relational duality views owned by the current user. Its columns (except for `VIEW_OWNER`) are the same as those in `ALL_JSON_DUALITY_VIEW_LINKS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_DUALITY_VIEW_LINKS"

7.579 USER_JSON_DUALITY_VIEW_TAB_COLS

`USER_JSON_DUALITY_VIEW_TAB_COLS` describes the table columns associated with the JSON-relational duality views owned by the current user. Its columns (except for `VIEW_OWNER`) are the same as those in `ALL_JSON_DUALITY_VIEW_TAB_COLS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_DUALITY_VIEW_TAB_COLS"

7.580 USER_JSON_DUALITY_VIEW_TABS

`USER_JSON_DUALITY_VIEW_TABS` describes the tables associated with the JSON-relational duality views owned by the current user. Its columns (except for `VIEW_OWNER`) are the same as those in `ALL_JSON_DUALITY_VIEW_TABS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_DUALITY_VIEW_TABS"

7.581 USER_JSON_DUALITY_VIEWS

`USER_JSON_DUALITY_VIEWS` describes the JSON-relational duality views owned by the current user. Its columns (except for `VIEW_OWNER`) are the same as those in `ALL_JSON_DUALITY_VIEWS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_DUALITY_VIEWS"

7.582 USER_JSON_INDEXES

`USER_JSON_INDEXES` describes indexes on JSON data that are owned by the current user. Its columns (except for `INDEX_OWNER`) are the same as those in `ALL_JSON_INDEXES`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_INDEXES"

7.583 USER_JSON_SCHEMA_COLUMNS

`USER_JSON_SCHEMA_COLUMNS` describes JSON schema constraints on columns in tables owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_JSON_SCHEMA_COLUMNS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_JSON_SCHEMA_COLUMNS"

7.584 USER_KAFKA_APPLICATIONS

`USER_KAFKA_APPLICATIONS` describes Oracle SQL Access to Kafka (OSAK) applications owned by the current user. Its columns (except for `OWNER` and `CLUSTER_ID`) are the same as those in `DBA_KAFKA_APPLICATIONS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_KAFKA_APPLICATIONS"
> - "DBMS_KAFKA_APPLICATIONS"

> **See Also:**
>
> "DBA_KAFKA_APPLICATIONS"

7.585 USER_KAFKA_CLUSTERS

`USER_KAFKA_CLUSTERS` describes the Oracle SQL Access to Kafka (OSAK) clusters that are owned by the current user or for which the current user has `READ` access. Its

columns (except for OWNER and GRANTEE) are the same as those in DBA_KAFKA_CLUSTERS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_KAFKA_CLUSTERS"
> - "DBMS_KAFKA_CLUSTERS" for information about viewing all registered OSAK clusters in the database

7.586 USER_KAFKA_LOAD_METRICS

USER_KAFKA_LOAD_METRICS displays metrics for DBMS_KAFKA.EXECUTE_LOAD_APP operations on tables owned by the current user. Its columns (except for OWNER and CLUSTER_ID) are the same as those in DBA_KAFKA_LOAD_METRICS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_KAFKA_LOAD_METRICS"
> - "DBMS_KAFKA_LOAD_METRICS"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_KAFKA.EXECUTE_LOAD_APP procedure

7.587 USER_KAFKA_MESSAGES

USER_KAFKA_MESSAGES displays messages logged by Oracle SQL Access to Kafka (OSAK) applications owned by the current user.

Column	Datatype	NULL	Description
CLUSTER_NAME	VARCHAR2(30)	NOT NULL	Name of the OSAK cluster associated with the application
APPLICATION_NAME	VARCHAR2(30)		Application name (also used as the Kafka group name)

Column	Datatype	NULL	Description
VIEW_NAME	VARCHAR2(128)		Name of the view associated with the application
MESSAGE_TYPE	VARCHAR2(20)		Message type. Possible values: • BADFILE • LOGFILE • NETWORK • ROLLBACK
MESSAGE_TS	TIMESTAMP(6)		Timestamp for when the message was logged
MESSAGE	VARCHAR2(4000)		Message text

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "DBMS_KAFKA_MESSAGES"

7.588 USER_KAFKA_OPS

USER_KAFKA_OPS describes operations for Oracle SQL Access to Kafka (OSAK) views owned by the current user. Its columns (except for OWNER and CLUSTER_ID) are the same as those in DBA_KAFKA_OPS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_KAFKA_OPS"
> - "DBMS_KAFKA_OPS"

7.589 USER_KAFKA_OPS_RESULTS

`USER_KAFKA_OPS_RESULTS` displays the results of operations for Oracle SQL Access to Kafka (OSAK) views owned by the current user. Its columns (except for `OWNER`) are the same as those in `DBA_KAFKA_OPS_RESULTS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_KAFKA_OPS_RESULTS"
> - "DBMS_KAFKA_OPS_RESULTS"

7.590 USER_KAFKA_PARTITIONS

`USER_KAFKA_PARTITIONS` describes partitions for Kafka topics associated with Oracle SQL Access to Kafka (OSAK) views owned by the current user. Its columns (except for `OWNER` and `CLUSTER_ID`) are the same as those in `DBA_KAFKA_PARTITIONS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> - "DBA_KAFKA_PARTITIONS"
> - "DBMS_KAFKA_PARTITIONS"

7.591 USER_LIBRARIES

USER_LIBRARIES describes the libraries owned by the current user. Its columns (except for OWNER) are the same as those in ALL_LIBRARIES.

> **See Also:**
>
> "ALL_LIBRARIES"

7.592 USER_LOB_PARTITIONS

USER_LOB_PARTITIONS displays the LOB partitions contained in the tables owned by the current user. Its columns are the same as those in ALL_LOB_PARTITIONS.

> **See Also:**
>
> "ALL_LOB_PARTITIONS"

7.593 USER_LOB_SUBPARTITIONS

USER_LOB_SUBPARTITIONS displays partition-level attributes of the LOB data subpartitions owned by the current user. Its columns are the same as those in ALL_LOB_SUBPARTITIONS.

DBA_LOB_TEMPLATES describes all LOB subpartition templates in the database.

> **See Also:**
>
> "ALL_LOB_SUBPARTITIONS"

7.594 USER_LOB_TEMPLATES

USER_LOB_TEMPLATES describes the LOB subpartition templates owned by the current user. Its columns (except for USER_NAME) are the same as those in ALL_LOB_TEMPLATES.

> **See Also:**
>
> "ALL_LOB_TEMPLATES"

7.595 USER_LOBS

USER_LOBS displays the user's CLOBs and BLOBs contained in the user's tables. BFILEs are stored outside the database, so they are not described by this view. This view's columns are the same as those in ALL_LOBS.

> **See Also:**
>
> "ALL_LOBS"

7.596 USER_LOG_GROUP_COLUMNS

USER_LOG_GROUP_COLUMNS describes columns that are owned by the current user and that are specified in log groups. Its columns are the same as those in ALL_LOG_GROUP_COLUMNS.

> **See Also:**
>
> "ALL_LOG_GROUP_COLUMNS"

7.597 USER_LOG_GROUPS

USER_LOG_GROUPS describes log group definitions on tables owned by the current user. Its columns are the same as those in ALL_LOG_GROUPS.

> **See Also:**
>
> "ALL_LOG_GROUPS"

7.598 USER_MEASURE_FOLDER_CONTENTS

USER_MEASURE_FOLDER_CONTENTS describes the contents of the OLAP measure folders owned by the current user. Its columns (except for OWNER) are the same as those in ALL_MEASURE_FOLDER_CONTENTS.

> **See Also:**
>
> "ALL_MEASURE_FOLDER_CONTENTS"

7.599 USER_MEASURE_FOLDER_SUBFOLDERS

`USER_MEASURE_FOLDER_SUBFOLDERS` describes the OLAP measure folders contained within the OLAP measure folders owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_MEASURE_FOLDER_SUBFOLDERS`.

> **See Also:**
>
> "ALL_MEASURE_FOLDER_SUBFOLDERS"

7.600 USER_MEASURE_FOLDERS

`USER_MEASURE_FOLDERS` describes the OLAP measure folders owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_MEASURE_FOLDERS`.

> **See Also:**
>
> "ALL_MEASURE_FOLDERS"

7.601 USER_METADATA_PROPERTIES

`USER_METADATA_PROPERTIES` describes OLAP metadata properties in the current user's schema. Its columns (except for `OWNER`) are the same as those in `ALL_METADATA_PROPERTIES`.

> **See Also:**
>
> "ALL_METADATA_PROPERTIES"

7.602 USER_METHOD_PARAMS

`USER_METHOD_PARAMS` describes the method parameters of the object types owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_METHOD_PARAMS`.

> **See Also:**
>
> "ALL_METHOD_PARAMS"

7.603 USER_METHOD_RESULTS

`USER_METHOD_RESULTS` describes the method results of the object types owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_METHOD_RESULTS`.

> **See Also:**
>
> "ALL_METHOD_RESULTS"

7.604 USER_MINING_MODEL_ATTRIBUTES

`USER_MINING_MODEL_ATTRIBUTES` describes the machine learning model attributes owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_MINING_MODEL_ATTRIBUTES`.

> **See Also:**
>
> "ALL_MINING_MODEL_ATTRIBUTES"

7.605 USER_MINING_MODEL_PARTITIONS

`USER_MINING_MODEL_PARTITIONS` describes the user's own model partitions. Its columns (except `OWNER`) are the same as those in `ALL_MINING_MODEL_PARTITIONS`.

> **Note:**
>
> The `USER_MINING_MODEL_PARTITIONS` view is available in Oracle Database 12*c* Release 2 and later.

> **See Also:**
>
> "ALL_MINING_MODEL_PARTITIONS"

7.606 USER_MINING_MODEL_SETTINGS

`USER_MINING_MODEL_SETTINGS` describes the machine learning model settings owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_MINING_MODEL_SETTINGS`.

> **See Also:**
>
> "ALL_MINING_MODEL_SETTINGS"

7.607 USER_MINING_MODEL_VIEWS

`USER_MINING_MODEL_VIEWS` describes the user's own model views. Its columns (except `OWNER`) are the same as those in `ALL_MINING_MODEL_VIEWS`.

> **See Also:**
>
> "ALL_MINING_MODEL_VIEWS"

7.608 USER_MINING_MODEL_XFORMS

`USER_MINING_MODEL_XFORMS` describes the user-specified transformations embedded with the user's own models. Its columns (except `OWNER`) are the same as those in `ALL_MINING_MODEL_XFORMS`.

> **See Also:**
>
> "ALL_MINING_MODEL_XFORMS"

7.609 USER_MINING_MODELS

`USER_MINING_MODELS` describes the machine learning models owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_MINING_MODELS`.

> **See Also:**
>
> "ALL_MINING_MODELS"

7.610 USER_MLE_ENV_IMPORTS

USER_MLE_ENV_IMPORTS describes import name to module mappings in the Oracle Database Multilingual Engine (MLE) environments owned by the current user. Its columns (except for ENV_OWNER) are the same as those in ALL_MLE_ENV_IMPORTS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_MLE_ENV_IMPORTS"

7.611 USER_MLE_ENVS

USER_MLE_ENVS describes the Oracle Database Multilingual Engine (MLE) environments owned by the current user. Its columns (except for ENV_OWNER) are the same as those in ALL_MLE_ENVS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_MLE_ENVS"

7.612 USER_MLE_MODULES

USER_MLE_MODULES describes the Oracle Database Multilingual Engine (MLE) modules owned by the current user. Its columns (except for MODULE_OWNER) are the same as those in ALL_MLE_MODULES.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_MLE_MODULES"

7.613 USER_MLE_PROCEDURES

`USER_MLE_PROCEDURES` describes the Oracle Database Multilingual Engine (MLE) functions and procedures owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_MLE_PROCEDURES`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_MLE_PROCEDURES"

7.614 USER_MVIEW_AGGREGATES

`USER_MVIEW_AGGREGATES` describes the grouping functions (aggregated measures) that appear in the `SELECT` list of aggregated materialized views owned by the current user. Its columns are the same as those in `ALL_MVIEW_AGGREGATES`.

> **See Also:**
>
> "ALL_MVIEW_AGGREGATES"

7.615 USER_MVIEW_ANALYSIS

USER_MVIEW_ANALYSIS describes all materialized views owned by the current user that potentially support query rewrite and that provide additional information for analysis by applications. Its columns are the same as those in ALL_MVIEW_ANALYSIS.

> **Note:**
>
> This view excludes materialized views that reference remote tables or that include references to non-static values such as SYSDATE or USER. This view also excludes materialized views that were created as snapshots before Oracle8*i* and that were never altered to enable query rewrite.

> **See Also:**
>
> "ALL_MVIEW_ANALYSIS"

7.616 USER_MVIEW_COMMENTS

USER_MVIEW_COMMENTS displays comments on the materialized views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_MVIEW_COMMENTS.

> **See Also:**
>
> "ALL_MVIEW_COMMENTS"

7.617 USER_MVIEW_DETAIL_LOGICAL_PARTITION

USER_MVIEW_DETAIL_LOGICAL_PARTITION displays freshness information, with respect to logical partition change tracking (LPCT) detail partitions, for the materialized views owned by the current user. Its columns are the same as those in ALL_MVIEW_DETAIL_LOGICAL_PARTITION.

> **See Also:**
>
> "ALL_MVIEW_DETAIL_LOGICAL_PARTITION"

7.618 USER_MVIEW_DETAIL_PARTITION

`USER_MVIEW_DETAIL_PARTITION` displays freshness information, with respect to partition change tracking (PCT) detail partitions, for the materialized views owned by the current user. Its columns are the same as those in `ALL_MVIEW_DETAIL_PARTITION`.

> **See Also:**
>
> "ALL_MVIEW_DETAIL_PARTITION"

7.619 USER_MVIEW_DETAIL_RELATIONS

`USER_MVIEW_DETAIL_RELATIONS` represents the named detail relations that are either in the `FROM` list of a materialized view, or that are indirectly referenced through views in the `FROM` list. Its columns are the same as those in `ALL_MVIEW_DETAIL_RELATIONS`.

> **See Also:**
>
> "ALL_MVIEW_DETAIL_RELATIONS"

7.620 USER_MVIEW_DETAIL_SUBPARTITION

`USER_MVIEW_DETAIL_SUBPARTITION` displays freshness information, with respect to partition change tracking (PCT) detail subpartitions, for the materialized views owned by the current user. Its columns are the same as those in `ALL_MVIEW_DETAIL_SUBPARTITION`.

> **See Also:**
>
> "ALL_MVIEW_DETAIL_SUBPARTITION"

7.621 USER_MVIEW_JOINS

`USER_MVIEW_JOINS` describes a join between two columns in the WHERE clause of a subquery that defines a materialized view. Its columns are the same as those in `ALL_MVIEW_JOINS`.

> **See Also:**
>
> "ALL_MVIEW_JOINS"

7.622 USER_MVIEW_KEYS

USER_MVIEW_KEYS describes the columns or expressions in the SELECT list upon which materialized views in the current user's schema are based. Its columns are the same as those in ALL_MVIEW_KEYS.

> **See Also:**
>
> "ALL_MVIEW_KEYS"

7.623 USER_MVIEW_LOGS

USER_MVIEW_LOGS describes all materialized view logs owned by the current user. Its columns are the same as those in ALL_MVIEW_LOGS.

> **See Also:**
>
> "ALL_MVIEW_LOGS"

7.624 USER_MVIEW_REFRESH_TIMES

USER_MVIEW_REFRESH_TIMES describes refresh times of the materialized views owned by the current user. Its columns are the same as those in ALL_MVIEW_REFRESH_TIMES.

> **See Also:**
>
> "ALL_MVIEW_REFRESH_TIMES"

7.625 USER_MVIEWS

USER_MVIEWS describes all materialized views owned by the current user. Its columns are the same as those in ALL_MVIEWS.

> **See Also:**
>
> "ALL_MVIEWS"

7.626 USER_MVREF_CHANGE_STATS

USER_MVREF_CHANGE_STATS displays the change data load information on the master tables associated with a refresh run for all the materialized views in the database that are accessible to the current user. Its columns are the same as those in DBA_MVREF_CHANGE_STATS.

> **See Also:**
>
> "DBA_MVREF_CHANGE_STATS"

7.627 USER_MVREF_RUN_STATS

USER_MVREF_RUN_STATS has information about each refresh run for the materialized views accessible for the current database user, with each run being identified by the REFRESH_ID. The information includes timing statistics related to the run and the parameters specified in that run.

Its columns (except for RUN_OWNER) are the same as those in DBA_MVREF_RUN_STATS.

> **See Also:**
>
> "DBA_MVREF_RUN_STATS"

7.628 USER_MVREF_STATS

USER_MVREF_STATS shows the REFRESH_ID associated with each refresh run of each materialized view for the database that is accessible to the current user. It also provides some basic timing statistics related to that materialized view's refresh in that run.

Its columns (except for MV_OWNER) are the same as those in DBA_MVREF_STATS.

> **See Also:**
>
> "DBA_MVREF_STATS"

7.629 USER_MVREF_STATS_PARAMS

USER_MVREF_STATS_PARAMS displays the refresh statistics properties associated with each materialized view accessible to the current user. These properties can be modified with the DBMS_MVIEW_STATS.SET_MVREF_STATS_PARAMS procedure.

Its columns are the same as those in DBA_MVREF_STATS_PARAMS.

> **See Also:**
>
> "DBA_MVREF_STATS_PARAMS"

7.630 USER_MVREF_STATS_SYS_DEFAULTS

USER_MVREF_STATS_SYS_DEFAULTS displays the system-wide defaults for the refresh history statistics properties for materialized views accessible to the current user. These values can be altered with the SET_SYSTEM_DEFAULTS procedure by a database administrator.

Its columns are the same as those in DBA_MVREF_STATS_SYS_DEFAULTS.

This view contains exactly two rows corresponding to the collection-level and retention-period properties; their initial values are TYPICAL and 31 respectively.

> **See Also:**
>
> "DBA_MVREF_STATS_SYS_DEFAULTS"

7.631 USER_MVREF_STMT_STATS

USER_MVREF_STMT_STATS shows information associated with each refresh statement of a materialized view accessible to the current user in a refresh run.

Its columns are the same as those in DBA_MVREF_STMT_STATS.

> **See Also:**
>
> "DBA_MVREF_STMT_STATS"

7.632 USER_NESTED_TABLE_COLS

USER_NESTED_TABLE_COLS describes the columns of the nested tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_NESTED_TABLE_COLS.

To gather statistics for this view, use the DBMS_STATS package.

> **See Also:**
>
> "ALL_NESTED_TABLE_COLS"

7.633 USER_NESTED_TABLES

USER_NESTED_TABLES describes the nested tables in tables owned by the current user. Its columns are the same as those in ALL_NESTED_TABLES.

> **See Also:**
>
> "ALL_NESTED_TABLES"

7.634 USER_NETWORK_ACL_PRIVILEGES

USER_NETWORK_ACL_PRIVILEGES describes the status of the network privileges for the current user to access network hosts.

> **Note:**
>
> This USER_NETWORK_ACL_PRIVILEGES view is deprecated in Oracle Database 12*c* Release 1 (12.1). Oracle recommends that you use the USER_HOST_ACES view, instead.

Column	Datatype	NULL	Description
HOST	VARCHAR2(1000)	NOT NULL	Network host
LOWER_PORT	NUMBER(5)		Lower bound of the port range
UPPER_PORT	NUMBER(5)		Upper bound of the port range
PRIVILEGE	CHAR(128)		Network privilege
STATUS	VARCHAR2(7)		Privilege status: • DENIED • GRANTED

> **See Also:**
>
> "USER_HOST_ACES"

7.635 USER_OBJ_AUDIT_OPTS

`USER_OBJ_AUDIT_OPTS` describes auditing options on all objects owned by the current user. Its columns (except for `OWNER`) are the same as those in `DBA_OBJ_AUDIT_OPTS`.

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

> **See Also:**
>
> "DBA_OBJ_AUDIT_OPTS"

7.636 USER_OBJ_COLATTRS

`USER_OBJ_COLATTRS` describes object columns and attributes contained in the tables owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_OBJ_COLATTRS`.

> **See Also:**
>
> "ALL_OBJ_COLATTRS"

7.637 USER_OBJECT_SIZE

`USER_OBJECT_SIZE` lists the sizes, in bytes, of various PL/SQL objects. Its columns are the same as those in `DBA_OBJECT_SIZE`.

> **See Also:**
>
> "DBA_OBJECT_SIZE"

7.638 USER_OBJECT_TABLES

`USER_OBJECT_TABLES` describes the object tables owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_OBJECT_TABLES`.

> **See Also:**
>
> "ALL_OBJECT_TABLES"

7.639 USER_OBJECT_USAGE

`USER_OBJECT_USAGE` displays statistics about index usage gathered from the database for the indexes owned by the current user.

You can use this view to monitor index usage. All indexes owned by the current user that have been used at least once can be monitored and displayed in this view. Its columns (except for `OWNER`) are the same as those in `DBA_OBJECT_USAGE`.

> **See Also:**
>
> "DBA_OBJECT_USAGE"

7.640 USER_OBJECTS

`USER_OBJECTS` describes all objects owned by the current user. Its columns (except for `OWNER`), are the same as those in `ALL_OBJECTS`.

> **See Also:**
>
> "ALL_OBJECTS"

7.641 USER_OBJECTS_AE

`USER_OBJECTS_AE` describes the objects (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_OBJECTS_AE`.

> **See Also:**
>
> "ALL_OBJECTS_AE"

7.642 USER_OGG_AUTO_CAPTURED_TABLES

`USER_OGG_AUTO_CAPTURED_TABLES` describes the tables owned by the current user that are enabled for Oracle GoldenGate automatic capture. Its columns (except for `OWNER`) are the same as those in `DBA_OGG_AUTO_CAPTURED_TABLES`.

> **See Also:**
>
> "DBA_OGG_AUTO_CAPTURED_TABLES"

7.643 USER_OPANCILLARY

`USER_OPANCILLARY` provides ancillary information for operators owned by the current user. Its columns are the same as those in `ALL_OPANCILLARY`.

> **See Also:**
>
> "ALL_OPANCILLARY"

7.644 USER_OPARGUMENTS

`USER_OPARGUMENTS` provides argument information for operator bindings owned by the current user. Its columns are the same as those in `ALL_OPARGUMENTS`.

> **See Also:**
>
> "ALL_OPARGUMENTS"

7.645 USER_OPBINDINGS

`USER_OPBINDINGS` describes the binding functions and methods on the operators owned by the current user. Its columns are the same as those in `ALL_OPBINDINGS`.

> **See Also:**
>
> "ALL_OPBINDINGS"

7.646 USER_OPERATOR_COMMENTS

USER_OPERATOR_COMMENTS displays comments for the user-defined operators owned by the current user. Its columns are the same as those in ALL_OPERATOR_COMMENTS.

> **See Also:**
>
> "ALL_OPERATOR_COMMENTS"

7.647 USER_OPERATORS

USER_OPERATORS describes all operators owned by the current user. Its columns are the same as those in ALL_OPERATORS.

> **See Also:**
>
> "ALL_OPERATORS"

7.648 USER_OUTLINE_HINTS

USER_OUTLINE_HINTS describes the set of hints stored in the outlines owned by the current user. Its columns (except for OWNER) are the same as those in DBA_OUTLINE_HINTS.

> **See Also:**
>
> "DBA_OUTLINE_HINTS"

7.649 USER_OUTLINES

USER_OUTLINES describes the stored outlines owned by the current user. Its columns (except for OWNER) are the same as those in DBA_OUTLINES.

> **See Also:**
>
> "DBA_OUTLINES"

7.650 USER_PARALLEL_EXECUTE_CHUNKS

`USER_PARALLEL_EXECUTE_CHUNKS` displays the chunks for tasks created by the current user. Its columns (except for `TASK_OWNER`) are the same as those in `DBA_PARALLEL_EXECUTE_CHUNKS`.

> **See Also:**
>
> "DBA_PARALLEL_EXECUTE_CHUNKS"

7.651 USER_PARALLEL_EXECUTE_TASKS

`USER_PARALLEL_EXECUTE_TASKS` displays the tasks created by the current user. Its columns (except for `TASK_OWNER`) are the same as those in `DBA_PARALLEL_EXECUTE_TASKS`.

> **See Also:**
>
> "DBA_PARALLEL_EXECUTE_TASKS"

7.652 USER_PART_COL_STATISTICS

`USER_PART_COL_STATISTICS` displays column statistics and histogram information for the table partitions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_PART_COL_STATISTICS`.

> **See Also:**
>
> "ALL_PART_COL_STATISTICS"

7.653 USER_PART_HISTOGRAMS

`USER_PART_HISTOGRAMS` displays the histogram data (endpoints per histogram) for the histograms on the table partitions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_PART_HISTOGRAMS`.

> **See Also:**
>
> "ALL_PART_HISTOGRAMS"

7.654 USER_PART_INDEXES

USER_PART_INDEXES displays the object-level partitioning information for the partitioned indexes owned by the current user. Its columns (except for OWNER) are the same as those in ALL_PART_INDEXES.

> **See Also:**
>
> "ALL_PART_INDEXES"

7.655 USER_PART_KEY_COLUMNS

USER_PART_KEY_COLUMNS describes the partitioning key columns for the partitioned objects owned by the current user. Its columns (except for OWNER) are the same as those in ALL_PART_KEY_COLUMNS.

> **See Also:**
>
> "ALL_PART_KEY_COLUMNS"

7.656 USER_PART_LOBS

USER_PART_LOBS displays table-level information about the partitioned LOBs owned by the current user, including default attributes for LOB data partitions. Its columns (except for TABLE_OWNER) are the same as those in ALL_PART_LOBS.

> **See Also:**
>
> "ALL_PART_LOBS"

7.657 USER_PART_TABLES

USER_PART_TABLES displays the object-level partitioning information for the partitioned tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_PART_TABLES.

> **See Also:**
>
> "ALL_PART_TABLES"

7.658 USER_PARTIAL_DROP_TABS

USER_PARTIAL_DROP_TABS describes all tables in the schema of the current user that have partially completed DROP COLUMN operations. Its columns are the same as those in ALL_PARTIAL_DROP_TABS.

> **See Also:**
>
> "ALL_PARTIAL_DROP_TABS"

7.659 USER_PASSWORD_LIMITS

USER_PASSWORD_LIMITS describes the password profile parameters that are assigned to the user.

Column	Datatype	NULL	Description
RESOURCE_NAME	VARCHAR2(32)	NOT NULL	Name of the password resource
LIMIT	VARCHAR2(40)		Value of the resource limit

7.660 USER_PENDING_CONV_TABLES

USER_PENDING_CONV_TABLES describes the pending conversion tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_PENDING_CONV_TABLES.

> **See Also:**
>
> "ALL_PENDING_CONV_TABLES"

7.661 USER_PG_EDGE_RELATIONSHIPS

USER_PG_EDGE_RELATIONSHIPS describes edge relationships in the property graphs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_PG_EDGE_RELATIONSHIPS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_EDGE_RELATIONSHIPS"

7.662 USER_PG_ELEMENT_LABELS

`USER_PG_ELEMENT_LABELS` describes labels for the element tables in the property graphs owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_PG_ELEMENT_LABELS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_ELEMENT_LABELS"

7.663 USER_PG_ELEMENTS

`USER_PG_ELEMENTS` describes element tables in the property graphs owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_PG_ELEMENTS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_ELEMENTS"

7.664 USER_PG_KEYS

`USER_PG_KEYS` describes key columns in the property graphs owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_PG_KEYS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_KEYS"

7.665 USER_PG_LABEL_PROPERTIES

`USER_PG_LABEL_PROPERTIES` describes properties in the property graphs owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_PG_LABEL_PROPERTIES`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_LABEL_PROPERTIES"

7.666 USER_PG_LABELS

`USER_PG_LABELS` describes labels in the property graphs owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_PG_LABELS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_LABELS"

7.667 USER_PG_PROP_DEFINITIONS

`USER_PG_PROP_DEFINITIONS` describes columns and expressions exposed as properties in the property graphs owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_PG_PROP_DEFINITIONS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PG_PROP_DEFINITIONS"

7.668 USER_PLSQL_COLL_TYPES

`USER_PLSQL_COLL_TYPES` describes the user's own named PL/SQL collection types. Its columns (except for `OWNER` and `CHAR_USED`) are the same as those in `ALL_PLSQL_COLL_TYPES`.

> **See Also:**
>
> "ALL_PLSQL_COLL_TYPES"

7.669 USER_PLSQL_OBJECT_SETTINGS

`USER_PLSQL_OBJECT_SETTINGS` displays information about the compiler settings for the stored objects owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_PLSQL_OBJECT_SETTINGS`.

> **See Also:**
>
> "ALL_PLSQL_OBJECT_SETTINGS"

7.670 USER_PLSQL_TYPE_ATTRS

`USER_PLSQL_TYPE_ATTRS` describes the attributes of the user's own PL/SQL types. Its columns (except for `OWNER` and `CHAR_USED`) are the same as those in `ALL_PLSQL_TYPE_ATTRS`.

> **See Also:**
>
> "ALL_PLSQL_TYPE_ATTRS"

7.671 USER_PLSQL_TYPES

`USER_PLSQL_TYPES` describes the user's own PL/SQL types. Its columns (except for `OWNER`) are the same as those in `ALL_PLSQL_TYPES`.

> **See Also:**
>
> "ALL_PLSQL_TYPES"

7.672 USER_POLICIES

`USER_POLICIES` describes all Oracle Virtual Private Database (VPD) security policies associated with objects owned by the current user. Its columns (except for `OBJECT_OWNER`) are the same as those in `ALL_POLICIES`.

> **See Also:**
>
> "ALL_POLICIES"

7.673 USER_POLICY_ATTRIBUTES

`USER_POLICY_ATTRIBUTES` lists the attribute associations {Namespaces, Attributes} of all context-sensitive and shared-context sensitive Oracle Virtual Private Database (VPD) policies for synonyms, tables, or views owned by the user.

Its columns are the same as those in `ALL_POLICY_ATTRIBUTES`.

> **See Also:**
>
> "ALL_POLICY_ATTRIBUTES"

7.674 USER_POLICY_CONTEXTS

USER_POLICY_CONTEXTS describes the driving contexts defined for the synonyms, tables, and views owned by the current user. Its columns (except for OBJECT_OWNER) are the same as those in ALL_POLICY_CONTEXTS.

> **See Also:**
>
> "ALL_POLICY_CONTEXTS"

7.675 USER_POLICY_GROUPS

USER_POLICY_GROUPS describes the policy groups defined for the synonyms, tables, and views owned by the current user. Its columns (except for OBJECT_OWNER) are the same as those in ALL_POLICY_GROUPS.

> **See Also:**
>
> "ALL_POLICY_GROUPS"

7.676 USER_PRIVATE_TEMP_TABLES

USER_PRIVATE_TEMP_TABLES describes the private temporary tables in the current session. Its columns (except for INST_ID) are the same as those in DBA_PRIVATE_TEMP_TABLES.

> **See Also:**
>
> "DBA_PRIVATE_TEMP_TABLES"

7.677 USER_PRIVILEGE_MAP

USER_PRIVILEGE_MAP shows privilege (auditing option) type codes for object privileges that can be granted on a user.

This table can be used to map privilege type numbers to type names.

Column	Datatype	NULL	Description
PRIVILEGE	NUMBER	NOT NULL	A numeric privilege (auditing option) type code
NAME	VARCHAR2(40)	NOT NULL	Name of the type of privilege (auditing option)

7.678 USER_PROCEDURES

USER_PROCEDURES lists all functions and procedures that are owned by the current user, along with their associated properties. Its columns (except OWNER) are the same as those in ALL_PROCEDURES.

> **See Also:**
>
> - "ALL_PROCEDURES"
> - "USER_ARGUMENTS" for information about the arguments of the functions and procedures owned by the current user

7.679 USER_PROPERTY_GRAPHS

USER_PROPERTY_GRAPHS describes the property graphs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_PROPERTY_GRAPHS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_PROPERTY_GRAPHS"

7.680 USER_PROXIES

USER_PROXIES displays information about connections the current user is allowed to proxy. Its columns (except for PROXY) are the same as those in DBA_PROXIES.

> **See Also:**
>
> "DBA_PROXIES"

7.681 USER_QUEUE_EVENT_STREAMS

USER_QUEUE_EVENT_STREAMS describes the Transactional Event Queue (TxEventQ) event streams owned by the current user. Its columns are the same as those in ALL_QUEUE_EVENT_STREAMS.

> **See Also:**
>
> "ALL_QUEUE_EVENT_STREAMS"

7.682 USER_QUEUE_SCHEDULES

USER_QUEUE_SCHEDULES describes the propagation schedules whose source queues are owned by the current user. Its columns (except for SCHEMA) are the same as those in ALL_QUEUE_SCHEDULES.

> **See Also:**
>
> "ALL_QUEUE_SCHEDULES"

7.683 USER_QUEUE_SUBSCRIBERS

USER_QUEUE_SUBSCRIBERS displays the list of subscribers on queues that are under the current user's schema. Its columns (except for OWNER) are the same as those in ALL_QUEUE_SUBSCRIBERS.

> **See Also:**
>
> "ALL_QUEUE_SUBSCRIBERS"

7.684 USER_QUEUE_TABLES

USER_QUEUE_TABLES describes the queues in the queue tables created in the current user's schema. Its columns (except for OWNER) are the same as those in ALL_QUEUE_TABLES.

> **See Also:**
>
> "ALL_QUEUE_TABLES"

7.685 USER_QUEUES

USER_QUEUES describes the operational characteristics of every queue in the user's schema. Its columns (except for OWNER) are the same as those in ALL_QUEUES.

> **See Also:**
>
> - "ALL_QUEUES"
> - *Oracle Database Advanced Queuing User's Guide* for more information about these views and Advanced Queuing

7.686 USER_RECYCLEBIN

USER_RECYCLEBIN displays information about the recycle bin owned by the current user. Its columns (except for OWNER) are the same as those in DBA_RECYCLEBIN.

> **See Also:**
>
> "DBA_RECYCLEBIN"

7.687 USER_REFRESH

USER_REFRESH describes all refresh groups owned by the current user. Its columns are the same as those in ALL_REFRESH.

> **See Also:**
>
> "ALL_REFRESH"

7.688 USER_REFRESH_CHILDREN

USER_REFRESH_CHILDREN lists all the objects in refresh groups owned by the current user. Its columns are the same as those in ALL_REFRESH_CHILDREN.

> **See Also:**
>
> "ALL_REFRESH_CHILDREN"

7.689 USER_REFS

USER_REFS describes the REF columns and REF attributes in the object type columns of tables owned by the current user. Its columns are the same as those in ALL_REFS.

> **See Also:**
>
> "ALL_REFS"

7.690 USER_REGISTERED_MVIEWS

USER_REGISTERED_MVIEWS describes all registered materialized views (registered at a master site or a master materialized view site) owned by the current user. Its columns are the same as those in ALL_REGISTERED_MVIEWS.

> **See Also:**
>
> "ALL_REGISTERED_MVIEWS"

7.691 USER_REGISTRY

USER_REGISTRY displays information about the components owned by the current user that are loaded into the component registry. Its columns are the same as those in DBA_REGISTRY.

> **See Also:**
>
> "DBA_REGISTRY"

7.692 USER_RESOURCE_LIMITS

USER_RESOURCE_LIMITS displays the resource limits for the current user.

Column	Datatype	NULL	Description
RESOURCE_NAME	VARCHAR2(32)	NOT NULL	Name of the resource
LIMIT	VARCHAR2(40)		Limit placed on this resource

7.693 USER_RESUMABLE

USER_RESUMABLE displays the resumable statements executed by the current user. Its columns (except for USER_ID) are the same as those in DBA_RESUMABLE.

> **See Also:**
>
> "DBA_RESUMABLE"

7.694 USER_REWRITE_EQUIVALENCES

USER_REWRITE_EQUIVALENCES describes the rewrite equivalences owned by the current user. Its columns are the same as those in ALL_REWRITE_EQUIVALENCES.

> **See Also:**
>
> "ALL_REWRITE_EQUIVALENCES"

7.695 USER_ROLE_PRIVS

USER_ROLE_PRIVS describes the roles granted to the current user.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the user, or PUBLIC
GRANTED_ROLE	VARCHAR2(128)		Name of the role granted to the user
ADMIN_OPTION	VARCHAR2(3)		Indicates whether the grant was with the ADMIN OPTION (YES) or not (NO)
DELEGATE_OPTION	VARCHAR2(3)		Indicates whether the grant was with the DELEGATE OPTION (YES) or not (NO)
DEFAULT_ROLE	VARCHAR2(3)		Indicates whether the role is designated as a DEFAULT ROLE for the user (YES) or not (NO)
OS_GRANTED	VARCHAR2(3)		Indicates whether the role was granted by the operating system (YES) or not (NO); occurs if the OS_ROLES initialization parameter is true
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the role was granted commonly (CONTAINER=ALL was used) • NO if the role was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the grant was inherited from another container (YES) or not (NO)

> **See Also:**
>
> "DBA_ROLE_PRIVS"

7.696 USER_RSRC_CONSUMER_GROUP_PRIVS

`USER_RSRC_CONSUMER_GROUP_PRIVS` displays information about the resource consumer groups to which the current user is assigned. Its columns (except for `GRANTEE`) are the same as those in `DBA_RSRC_CONSUMER_GROUP_PRIVS`.

> **See Also:**
>
> "DBA_RSRC_CONSUMER_GROUP_PRIVS"

7.697 USER_RSRC_MANAGER_SYSTEM_PRIVS

`USER_RSRC_MANAGER_SYSTEM_PRIVS` displays information about the users who are granted system privileges for the `DBMS_RESOURCE_MANAGER` package. Its columns (except for `GRANTEE`) are the same as those in `DBA_RSRC_MANAGER_SYSTEM_PRIVS`.

> **See Also:**
>
> "DBA_RSRC_MANAGER_SYSTEM_PRIVS"

7.698 USER_RULE_SET_RULES

`USER_RULE_SET_RULES` describes the rules in the rule sets owned by the current user. Its columns (except for `RULE_SET_OWNER`) are the same as those in `ALL_RULE_SET_RULES`.

> **See Also:**
>
> "ALL_RULE_SET_RULES"

7.699 USER_RULE_SETS

`USER_RULE_SETS` describes the rule sets owned by the current user. Its columns (except for `RULE_SET_OWNER`) are the same as those in `ALL_RULE_SETS`.

> **See Also:**
>
> "ALL_RULE_SETS"

7.700 USER_RULES

`USER_RULES` describes the rules owned by the current user. Its columns (except for `RULE_OWNER`) are the same as those in `ALL_RULES`.

> **See Also:**
>
> "ALL_RULES"

7.701 USER_SAGA_BROKERS

`USER_SAGA_BROKERS` displays the saga brokers owned by the current user. Its columns are the same as those in `ALL_SAGA_BROKERS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_BROKERS"

7.702 USER_SAGA_DETAILS

USER_SAGA_DETAILS displays details for sagas owned by the current user. Its columns are the same as those in ALL_SAGA_DETAILS.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_DETAILS"

7.703 USER_SAGA_ERRORS

USER_SAGA_ERRORS describes errors generated by the sagas owned by the current user. Its columns are the same as those in ALL_SAGA_ERRORS.

This view displays sagas that were either initiated in the current PDB or joined by participants in the current PDB.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_ERRORS"

7.704 USER_SAGA_FINALIZATION

USER_SAGA_FINALIZATION displays information about pending finalization actions for sagas owned by the current user. Its columns are the same as those in ALL_SAGA_FINALIZATION.

This view displays one row for each unique reservable table updated as part of a participant transaction for sagas that were either initiated in the current PDB or joined by participants in the current PDB.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_FINALIZATION"

7.705 USER_SAGA_PARTICIPANT_SET

`USER_SAGA_PARTICIPANT_SET` displays information about saga participants for sagas owned by the current user. Its columns are the same as those in `ALL_SAGA_PARTICIPANT_SET`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_PARTICIPANT_SET"

7.706 USER_SAGA_PARTICIPANTS

`USER_SAGA_PARTICIPANTS` describes the saga participants owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_SAGA_PARTICIPANTS`.

This view displays sagas that were either initiated in the current PDB or joined by participants or coordinators in the current PDB.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_PARTICIPANTS"

7.707 USER_SAGA_PENDING

`USER_SAGA_PENDING` describes the pending sagas owned by the current user. Its columns are the same as those in `ALL_SAGA_PENDING`.

This view displays sagas that were initiated in the current PDB.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGA_PENDING"

7.708 USER_SAGAS

`USER_SAGAS` describes the active sagas owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_SAGAS`.

This view displays sagas that were either initiated in the current PDB or joined by participants in the current PDB.

> **Note:**
>
> This view displays active sagas. Completed sagas are displayed in the USER_HIST_SAGAS view.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_SAGAS"

7.709 USER_SCHEDULER_CHAIN_RULES

USER_SCHEDULER_CHAIN_RULES displays information about the rules for the chains owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_CHAIN_RULES.

> **See Also:**
>
> "ALL_SCHEDULER_CHAIN_RULES"

7.710 USER_SCHEDULER_CHAIN_STEPS

USER_SCHEDULER_CHAIN_STEPS displays information about the defined steps of the chains owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_CHAIN_STEPS.

> **See Also:**
>
> "ALL_SCHEDULER_CHAIN_STEPS"

7.711 USER_SCHEDULER_CHAINS

USER_SCHEDULER_CHAINS displays information about the chains owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_CHAINS.

> **See Also:**
>
> "ALL_SCHEDULER_CHAINS"

7.712 USER_SCHEDULER_CREDENTIALS

USER_SCHEDULER_CREDENTIALS displays information about the credentials owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_CREDENTIALS.

> **Note:**
>
> This view is deprecated in favor of the USER_CREDENTIALS view. Oracle recommends that you use USER_CREDENTIALS instead. USER_SCHEDULER_CREDENTIALS is retained for backward compatibility only.

> **See Also:**
>
> - "USER_CREDENTIALS"
> - "ALL_SCHEDULER_CREDENTIALS"

7.713 USER_SCHEDULER_DB_DESTS

`USER_SCHEDULER_DB_DESTS` displays information about the destination objects owned by the current user pointing to remote databases. Its columns (except for `OWNER`) are the same as those in `ALL_SCHEDULER_DB_DESTS`.

> **See Also:**
>
> "ALL_SCHEDULER_DB_DESTS"

7.714 USER_SCHEDULER_DESTS

`USER_SCHEDULER_DESTS` displays information about the destination objects for jobs owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_SCHEDULER_DESTS`.

> **See Also:**
>
> "ALL_SCHEDULER_DESTS"

7.715 USER_SCHEDULER_FILE_WATCHERS

`USER_SCHEDULER_FILE_WATCHERS` displays information about the Scheduler file watch requests owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_SCHEDULER_FILE_WATCHERS`.

> **See Also:**
>
> "ALL_SCHEDULER_FILE_WATCHERS"

7.716 USER_SCHEDULER_GROUP_MEMBERS

USER_SCHEDULER_GROUP_MEMBERS displays information about the members of the Scheduler object groups owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_GROUP_MEMBERS.

> **See Also:**
>
> "ALL_SCHEDULER_GROUP_MEMBERS"

7.717 USER_SCHEDULER_GROUPS

USER_SCHEDULER_GROUPS displays information about the Scheduler object groups owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_GROUPS.

> **See Also:**
>
> "ALL_SCHEDULER_GROUPS"

7.718 USER_SCHEDULER_INCOMPAT_MEMBER

USER_SCHEDULER_INCOMPAT_MEMBER displays all Scheduler incompatibility resource objects members owned by the current user. Its columns are the same as those in ALL_SCHEDULER_INCOMPAT_MEMBER.

> **See Also:**
>
> "ALL_SCHEDULER_INCOMPAT_MEMBER"

7.719 USER_SCHEDULER_INCOMPATS

USER_SCHEDULER_INCOMPATS displays all Scheduler incompatibility resource objects owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_INCOMPATS.

> **See Also:**
>
> "ALL_SCHEDULER_INCOMPATS"

7.720 USER_SCHEDULER_JOB_ARGS

USER_SCHEDULER_JOB_ARGS displays information about the arguments of the Scheduler jobs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_JOB_ARGS.

> **See Also:**
>
> "ALL_SCHEDULER_JOB_ARGS"

7.721 USER_SCHEDULER_JOB_DESTS

USER_SCHEDULER_JOB_DESTS displays information about the state of the jobs owned by the current user at each of their destinations. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_JOB_DESTS.

> **See Also:**
>
> "ALL_SCHEDULER_JOB_DESTS"

7.722 USER_SCHEDULER_JOB_LOG

USER_SCHEDULER_JOB_LOG displays log information for the Scheduler jobs owned by the current user. Its columns are the same as those in ALL_SCHEDULER_JOB_LOG.

> **See Also:**
>
> "ALL_SCHEDULER_JOB_LOG"

7.723 USER_SCHEDULER_JOB_RUN_DETAILS

USER_SCHEDULER_JOB_RUN_DETAILS displays log run details for the Scheduler jobs owned by the current user. Its columns are the same as those in ALL_SCHEDULER_JOB_RUN_DETAILS.

> **See Also:**
>
> "ALL_SCHEDULER_JOB_RUN_DETAILS"

7.724 USER_SCHEDULER_JOBS

USER_SCHEDULER_JOBS displays information about the Scheduler jobs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_JOBS.

> **See Also:**
>
> "ALL_SCHEDULER_JOBS"

7.725 USER_SCHEDULER_NOTIFICATIONS

USER_SCHEDULER_NOTIFICATIONS displays information about the E-mail notifications for the jobs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_NOTIFICATIONS.

> **See Also:**
>
> "ALL_SCHEDULER_NOTIFICATIONS"

7.726 USER_SCHEDULER_PROGRAM_ARGS

USER_SCHEDULER_PROGRAM_ARGS displays information about the arguments of the Scheduler programs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_PROGRAM_ARGS.

> **See Also:**
>
> "ALL_SCHEDULER_PROGRAM_ARGS"

7.727 USER_SCHEDULER_PROGRAMS

USER_SCHEDULER_PROGRAMS displays information about the Scheduler programs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_PROGRAMS.

> **See Also:**
>
> "ALL_SCHEDULER_PROGRAMS"

7.728 USER_SCHEDULER_REMOTE_JOBSTATE

USER_SCHEDULER_REMOTE_JOBSTATE displays information about the state of the jobs owned by the current user at remote databases. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_REMOTE_JOBSTATE.

> **See Also:**
>
> "ALL_SCHEDULER_REMOTE_JOBSTATE"

7.729 USER_SCHEDULER_RESOURCES

USER_SCHEDULER_RESOURCES displays all scheduler resource objects in the database from the schema of the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_RESOURCES.

> **See Also:**
>
> "ALL_SCHEDULER_RESOURCES"

7.730 USER_SCHEDULER_RSC_CONSTRAINTS

USER_SCHEDULER_RSC_CONSTRAINTS lists all Oracle Scheduler resource constraint members owned by the current user. Its columns are the same as those in ALL_SCHEDULER_RSC_CONSTRAINTS.

> **See Also:**
>
> "ALL_SCHEDULER_RSC_CONSTRAINTS"

7.731 USER_SCHEDULER_RUNNING_CHAINS

USER_SCHEDULER_RUNNING_CHAINS displays information about the chain steps of the running chains owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_RUNNING_CHAINS.

> **See Also:**
>
> "ALL_SCHEDULER_RUNNING_CHAINS"

7.732 USER_SCHEDULER_RUNNING_JOBS

USER_SCHEDULER_RUNNING_JOBS displays information about the running Scheduler jobs owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_RUNNING_JOBS.

> **See Also:**
>
> "ALL_SCHEDULER_RUNNING_JOBS"

7.733 USER_SCHEDULER_SCHEDULES

USER_SCHEDULER_SCHEDULES displays information about the Scheduler schedules owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SCHEDULER_SCHEDULES.

> **See Also:**
>
> "ALL_SCHEDULER_SCHEDULES"

7.734 USER_SCHEMA_PRIVS

USER_SCHEMA_PRIVS describes schema privileges granted to the current user.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the user, or PUBLIC
PRIVILEGE	VARCHAR2(40)		Schema privilege
SCHEMA	VARCHAR2(128)		Schema on which the privilege was granted
ADMIN_OPTION	VARCHAR2(3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the grant was inherited from another container (YES) or not (NO)

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "DBA_SCHEMA_PRIVS"

7.735 USER_SEC_RELEVANT_COLS

`USER_SEC_RELEVANT_COLS` describes the security relevant columns of the security policies for the tables and views owned by the current user. Its columns (except for `OBJECT_OWNER`) are the same as those in `ALL_SEC_RELEVANT_COLS`.

> **See Also:**
>
> "ALL_SEC_RELEVANT_COLS"

7.736 USER_SECONDARY_OBJECTS

`USER_SECONDARY_OBJECTS` provides information about secondary objects associated with domain indexes owned by the current user. Its columns are the same as those in `ALL_SECONDARY_OBJECTS`.

This view is only relevant in the context of domain indexes.

> **See Also:**
>
> "ALL_SECONDARY_OBJECTS"

7.737 USER_SEGMENTS

`USER_SEGMENTS` describes the storage allocated for the segments owned by the current user's objects. Its columns (except for `OWNER`, `HEADER_FILE`, `HEADER_BLOCK`, and `RELATIVE_FNO`) are the same as those in `DBA_SEGMENTS`.

> **See Also:**
>
> "DBA_SEGMENTS"

7.738 USER_SEQUENCES

USER_SEQUENCES describes all sequences owned by the current user. Its columns are the same as those in ALL_SEQUENCES.

> **See Also:**
>
> "ALL_SEQUENCES"

7.739 USER_SODA_COLLECTIONS

USER_SODA_COLLECTIONS displays information about Simple Oracle Document Access (SODA) collections.

Column	Datatype	NULL	Description
URI_NAME	NVARCHAR2(255)	NOT NULL	Collection name
OBJECT_TYPE	VARCHAR2(10)	NOT NULL	Indicates whether the collection is table-based (TABLE) or view-based (VIEW)
OBJECT_SCHEMA	VARCHAR2(128)	NOT NULL	Name of the schema that includes the table or view on which the collection is based
OBJECT_NAME	VARCHAR2(128)	NOT NULL	Name of the table or view on which the collection is based
CREATED_ON	TIMESTAMP(6)	NOT NULL	Collection creation time
CREATE_MODE	VARCHAR2(10)	NOT NULL	Creation mode. Possible values: • DDL: A new table was created at collection creation time • MAP: The collection was created by mapping a preexisting table or view **Note:** For view-based collections, the value of this column is always MAP. New views are not created for view-based collections. A view-based collection is always created by mapping a preexisting view.
JSON_DESCRIPTOR	VARCHAR2(4000)	NOT NULL	Collection metadata, expressed in JavaScript Object Notation (JSON)

7.740 USER_SOURCE

USER_SOURCE describes the text source of the stored objects owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SOURCE.

> **See Also:**
>
> "ALL_SOURCE"

7.741 USER_SOURCE_AE

USER_SOURCE_AE describes the text source of the stored objects (across all editions) owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SOURCE_AE.

> **See Also:**
>
> "ALL_SOURCE_AE"

7.742 USER_SQL_TRANSLATION_PROFILES

USER_SQL_TRANSLATION_PROFILES describes all SQL translation profiles owned by the user. Its columns (except for OWNER) are the same as those in ALL_SQL_TRANSLATION_PROFILES.

> **See Also:**
>
> "ALL_SQL_TRANSLATION_PROFILES"

7.743 USER_SQL_TRANSLATIONS

USER_SQL_TRANSLATIONS describes all SQL translations owned by the user. Its columns (except for OWNER) are the same as those in ALL_SQL_TRANSLATIONS.

> **See Also:**
>
> "ALL_SQL_TRANSLATIONS"

7.744 USER_SQLJ_TYPE_ATTRS

USER_SQLJ_TYPE_ATTRS describes the attributes of the SQLJ object types owned by the current user. Its columns (except for OWNER) are the same as those in ALL_SQLJ_TYPE_ATTRS.

> **See Also:**
>
> "ALL_SQLJ_TYPE_ATTRS"

7.745 USER_SQLJ_TYPE_METHODS

`USER_SQLJ_TYPE_METHODS` describes the methods of the SQLJ object types owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_SQLJ_TYPE_METHODS`.

> **See Also:**
>
> "ALL_SQLJ_TYPE_METHODS"

7.746 USER_SQLJ_TYPES

`USER_SQLJ_TYPES` describes the SQLJ object types owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_SQLJ_TYPES`.

> **See Also:**
>
> "ALL_SQLJ_TYPES"

7.747 USER_SQLSET

`USER_SQLSET` displays information about the SQL tuning sets owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_SQLSET`.

> **See Also:**
>
> "ALL_SQLSET"

7.748 USER_SQLSET_BINDS

`USER_SQLSET_BINDS` displays the bind values associated with the SQL tuning sets owned by the current user. Its columns (except for `SQLSET_OWNER`) are the same as those in `ALL_SQLSET_BINDS`.

> **See Also:**
>
> "ALL_SQLSET_BINDS"

7.749 USER_SQLSET_PLANS

`USER_SQLSET_PLANS` describes captured plans for statements in the SQL tuning sets owned by the current user. Its columns (except for `SQLSET_OWNER`) are the same as those in `ALL_SQLSET_PLANS`.

> **See Also:**
>
> "ALL_SQLSET_PLANS"

7.750 USER_SQLSET_REFERENCES

`USER_SQLSET_REFERENCES` describes whether or not the SQL tuning sets owned by the current user are active. Its columns (except for `SQLSET_OWNER`) are the same as those in `ALL_SQLSET_REFERENCES`.

> **See Also:**
>
> "ALL_SQLSET_REFERENCES"

7.751 USER_SQLSET_STATEMENTS

`USER_SQLSET_STATEMENTS` displays information about the SQL statements, along with their statistics, that form the SQL tuning sets owned by the current user. Its columns (except for `SQLSET_OWNER`) are the same as those in `ALL_SQLSET_STATEMENTS`.

> **See Also:**
>
> "ALL_SQLSET_STATEMENTS"

7.752 USER_SQLTUNE_BINDS

`USER_SQLTUNE_BINDS` displays the bind values associated with the tuned SQL statements owned by the current user. Its columns are the same as those in `DBA_SQLTUNE_BINDS`.

> **See Also:**
>
> "DBA_SQLTUNE_BINDS"

7.753 USER_SQLTUNE_PLANS

USER_SQLTUNE_PLANS displays information about the execution plans generated for the SQL statements owned by the current user during a SQL tuning session. Its columns are the same as those in DBA_SQLTUNE_PLANS.

> **See Also:**
>
> "DBA_SQLTUNE_PLANS"

7.754 USER_SQLTUNE_RATIONALE_PLAN

USER_SQLTUNE_RATIONALE_PLAN displays the association between rationales and operations in the execution plan of the SQL statements owned by the current user. Its columns are the same as those in DBA_SQLTUNE_RATIONALE_PLAN.

> **See Also:**
>
> "DBA_SQLTUNE_RATIONALE_PLAN"

7.755 USER_SQLTUNE_STATISTICS

USER_SQLTUNE_STATISTICS displays statistics associated with the SQL statements owned by the current user. Its columns are the same as those in DBA_SQLTUNE_STATISTICS.

> **See Also:**
>
> "DBA_SQLTUNE_STATISTICS"

7.756 USER_SR_GRP_STATUS

USER_SR_GRP_STATUS provides information on the current refresh operations for the current synchronous refresh groups in the database which are owned by the current user. Its columns are the same as those in DBA_SR_GRP_STATUS.

> **See Also:**
>
> "DBA_SR_GRP_STATUS"

7.757 USER_SR_GRP_STATUS_ALL

`USER_SR_GRP_STATUS_ALL` provides information on the refresh operations on the synchronous refresh groups in the database which are owned by the current user. Its columns are the same as those in `DBA_SR_GRP_STATUS_ALL`.

> **See Also:**
>
> "DBA_SR_GRP_STATUS_ALL"

7.758 USER_SR_OBJ

`USER_SR_OBJ` provides information on the objects currently registered for synchronous refresh for current groups for the current user. Its columns are the same as those in `DBA_SR_OBJ`.

> **See Also:**
>
> "DBA_SR_OBJ"

7.759 USER_SR_OBJ_ALL

`USER_SR_OBJ_ALL` provides information on the objects registered for synchronous refresh for current and defunct groups for the current user. Its columns are the same as those in `DBA_SR_OBJ_ALL`.

> **See Also:**
>
> "DBA_SR_OBJ_ALL"

7.760 USER_SR_OBJ_STATUS

`USER_SR_OBJ_STATUS` provides information on the status of objects registered for synchronous refresh for the current refresh operations for the current synchronous refresh groups in the database which are owned by the current user. Its columns are the same as those in `DBA_SR_OBJ_STATUS`.

> **See Also:**
>
> "DBA_SR_OBJ_STATUS"

7.761 USER_SR_OBJ_STATUS_ALL

USER_SR_OBJ_STATUS_ALL provides information on the status of objects registered for synchronous refresh in the database which are owned by the current user. Its columns are the same as those in DBA_SR_OBJ_STATUS_ALL.

> **See Also:**
>
> "DBA_SR_OBJ_STATUS_ALL"

7.762 USER_SR_PARTN_OPS

USER_SR_PARTN_OPS provides information on the partition operations registered on the base tables of the materialized views registered for synchronous refresh belonging to the current user. Its columns are the same as those in DBA_SR_PARTN_OPS.

> **See Also:**
>
> "DBA_SR_PARTN_OPS"

7.763 USER_SR_STLOG_EXCEPTIONS

USER_SR_STLOG_EXCEPTIONS provides information on the exceptions in the staging logs for the tables belonging to the current user processed by DBMS_SYNC_REFRESH.PREPARE_STAGING_LOG. Its columns are the same as those in DBA_SR_STLOG_EXCEPTIONS.

> **See Also:**
>
> "DBA_SR_STLOG_EXCEPTIONS"

7.764 USER_SR_STLOG_STATS

USER_SR_STLOG_STATS provides information on the statistics in the staging logs for the tables belonging to the current user processed by DBMS_SYNC_REFRESH.PREPARE_STAGING_LOG. Its columns are the same as those in DBA_SR_STLOG_STATS.

> **See Also:**
>
> "DBA_SR_STLOG_STATS"

7.765 USER_STAT_EXTENSIONS

`USER_STAT_EXTENSIONS` displays information about the optimizer statistics extensions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_STAT_EXTENSIONS`.

> **See Also:**
>
> "ALL_STAT_EXTENSIONS"

7.766 USER_STATEMENTS

`USER_STATEMENTS` SQL statements in stored PL/SQL objects accessible to the user. Its columns (except for `OWNER`) are the same as those in `ALL_STATEMENTS`.

> **See Also:**
>
> "ALL_STATEMENTS"

7.767 USER_STORED_SETTINGS

`USER_STORED_SETTINGS` lists information about the persistent parameter settings for stored PL/SQL units, but only shows information about PL/SQL units owned by the current user.

`USER_STORED_SETTINGS` does not display the `OWNER` column. The rest of its columns are the same as those in `ALL_STORED_SETTINGS`.

> **See Also:**
>
> "ALL_STORED_SETTINGS"

7.768 USER_SUBPART_COL_STATISTICS

`USER_SUBPART_COL_STATISTICS` provides column statistics and histogram information for subpartitions of subpartitioned objects owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_SUBPART_COL_STATISTICS`.

> **See Also:**
>
> "ALL_SUBPART_COL_STATISTICS"

7.769 USER_SUBPART_HISTOGRAMS

`USER_SUBPART_HISTOGRAMS` lists actual histogram data (end-points per histogram) for histograms on table subpartitions owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_SUBPART_HISTOGRAMS`.

> **See Also:**
>
> "ALL_SUBPART_HISTOGRAMS"

7.770 USER_SUBPART_KEY_COLUMNS

`USER_SUBPART_KEY_COLUMNS` lists subpartitioning key columns for composite-partitioned tables (and local indexes on composite-partitioned tables) owned by the current user. Its columns are the same as those in `ALL_SUBPART_KEY_COLUMNS`.

> **See Also:**
>
> "ALL_SUBPART_KEY_COLUMNS"

7.771 USER_SUBPARTITION_TEMPLATES

`USER_SUBPARTITION_TEMPLATES` describes the subpartition templates owned by the current user. Its columns (except for `USER_NAME`) are the same as those in `ALL_SUBPARTITION_TEMPLATES`.

> **See Also:**
>
> "ALL_SUBPARTITION_TEMPLATES"

7.772 USER_SUBSCR_REGISTRATIONS

USER_SUBSCR_REGISTRATIONS displays information about the subscription registrations owned by the current user. Its columns are the same as those in DBA_SUBSCR_REGISTRATIONS.

> **See Also:**
>
> "DBA_SUBSCR_REGISTRATIONS"

7.773 USER_SYNONYMS

USER_SYNONYMS describes the private synonyms (synonyms owned by the current user). Its columns (except for OWNER) are the same as those in ALL_SYNONYMS.

> **See Also:**
>
> "ALL_SYNONYMS"

7.774 USER_SYS_PRIVS

USER_SYS_PRIVS describes system privileges granted to the current user.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the user, or PUBLIC
PRIVILEGE	VARCHAR2(40)		System privilege
ADMIN_OPTION	VARCHAR2(3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the grant was inherited from another container (YES) or not (NO)

> **See Also:**
>
> "DBA_SYS_PRIVS"

7.775 USER_SYS_PRIVS_ALL

USER_SYS_PRIVS_ALL describes system privileges and schema privileges granted to the current user.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)		Name of the user, or PUBLIC
PRIVILEGE	VARCHAR2(40)		Privilege
SCHEMA	VARCHAR2(128)		Schema on which the privilege was granted For system privileges, the value of this column is null.
ADMIN_OPTION	VARCHAR2(3)		Indicates whether the grant was with the ADMIN option (YES) or not (NO)
COMMON	VARCHAR2(3)		Indicates how the grant was made. Possible values: • YES if the privilege was granted commonly (CONTAINER=ALL was used) • NO if the privilege was granted locally (CONTAINER=ALL was not used)
INHERITED	VARCHAR2(3)		Indicates whether the grant was inherited from another container (YES) or not (NO)

Note:

This view is available starting with Oracle Database 23ai.

See Also:

"DBA_SYS_PRIVS_ALL"

7.776 USER_TAB_COL_STAT_MODELS

USER_TAB_COL_STAT_MODELS describes real-time statistics models for all tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TAB_COL_STAT_MODELS.

Real-time statistics models use machine learning algorithms to predict the number of distinct values (NDV) for table columns.

See Also:

"ALL_TAB_COL_STAT_MODELS"

7.777 USER_TAB_COL_STATISTICS

USER_TAB_COL_STATISTICS contains column statistics and histogram information extracted from USER_TAB_COLUMNS.

Its columns (except for OWNER) are the same as those in ALL_TAB_COL_STATISTICS.

See Also:

- "USER_TAB_COLUMNS"
- "ALL_TAB_COL_STATISTICS"

7.778 USER_TAB_COLS

USER_TAB_COLS describes the columns of the tables, views, and clusters owned by the current user.

Its columns (except for OWNER) are the same as those in ALL_TAB_COLS.

To gather statistics for this view, use the DBMS_STATS package.

This view differs from USER_TAB_COLUMNS in that system-generated hidden columns are not filtered out.

See Also:

- "ALL_TAB_COLS"
- "USER_TAB_COLUMNS"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

7.779 USER_TAB_COLUMNS

USER_TAB_COLUMNS describes the columns of the tables, views, and clusters owned by the current user.

Its columns (except for OWNER) are the same as those in ALL_TAB_COLUMNS.

To gather statistics for this view, use the DBMS_STATS package.

This view filters out system-generated hidden columns. The USER_TAB_COLS view does not filter out system-generated hidden columns.

> **See Also:**
>
> - "ALL_TAB_COLUMNS"
> - "USER_TAB_COLS"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

7.780 USER_TAB_COMMENTS

USER_TAB_COMMENTS displays comments on the tables and views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TAB_COMMENTS.

> **See Also:**
>
> "ALL_TAB_COMMENTS"

7.781 USER_TAB_HISTGRM_PENDING_STATS

USER_TAB_HISTGRM_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TAB_HISTGRM_PENDING_STATS.

> **See Also:**
>
> "ALL_TAB_HISTGRM_PENDING_STATS"

7.782 USER_TAB_HISTOGRAMS

USER_TAB_HISTOGRAMS describes histograms on columns of tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TAB_HISTOGRAMS.

> **See Also:**
>
> "ALL_TAB_HISTOGRAMS"

7.783 USER_TAB_IDENTITY_COLS

USER_TAB_IDENTITY_COLS describes all table identity columns. Its columns (except for OWNER) are the same as those in ALL_TAB_IDENTITY_COLS.

> **See Also:**
>
> "ALL_TAB_IDENTITY_COLS"

7.784 USER_TAB_MODIFICATIONS

USER_TAB_MODIFICATIONS describes modifications to all tables owned by the current user that have been modified since the last time statistics were gathered on the tables. Its columns are the same as those in ALL_TAB_MODIFICATIONS.

> **Note:**
>
> For performance reasons, Oracle Database does not populate this view immediately when the actual modifications occur.

> **See Also:**
>
> "ALL_TAB_MODIFICATIONS"

7.785 USER_TAB_PARTITIONS

USER_TAB_PARTITIONS describes partition-level partitioning information, partition storage parameters, and partition statistics generated by the DBMS_STATS package for all partitions owned by the current user.

Its columns are the same as those in ALL_TAB_PARTITIONS.

> **See Also:**
>
> "ALL_TAB_PARTITIONS"

7.786 USER_TAB_PENDING_STATS

USER_TAB_PENDING_STATS describes pending statistics for tables, partitions, and subpartitions owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TAB_PENDING_STATS.

> **See Also:**
>
> "ALL_TAB_PENDING_STATS"

7.787 USER_TAB_PRIVS

USER_TAB_PRIVS describes the object grants for which the current user is the object owner, grantor, or grantee. Its columns are the same as those in DBA_TAB_PRIVS.

> **See Also:**
>
> "DBA_TAB_PRIVS"

7.788 USER_TAB_PRIVS_MADE

USER_TAB_PRIVS_MADE describes the object grants for which the current user is the object owner. Its columns (except for OWNER) are the same as those in ALL_TAB_PRIVS_MADE.

> **See Also:**
>
> "ALL_TAB_PRIVS_MADE"

7.789 USER_TAB_PRIVS_RECD

USER_TAB_PRIVS_RECD describes the object grants for which the current user is the grantee. Its columns (except for GRANTEE) are the same as those in ALL_TAB_PRIVS_RECD.

> **See Also:**
>
> "ALL_TAB_PRIVS_RECD"

7.790 USER_TAB_STAT_PREFS

USER_TAB_STAT_PREFS displays information about statistics preferences for the tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TAB_STAT_PREFS.

> **See Also:**
>
> "ALL_TAB_STAT_PREFS"

7.791 USER_TAB_STATISTICS

USER_TAB_STATISTICS displays optimizer statistics for the tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TAB_STATISTICS.

> **See Also:**
>
> "ALL_TAB_STATISTICS"

7.792 USER_TAB_STATS_HISTORY

USER_TAB_STATS_HISTORY provides a history of table statistics modifications for all tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TAB_STATS_HISTORY.

> **See Also:**
>
> "ALL_TAB_STATS_HISTORY"

7.793 USER_TAB_SUBPARTITIONS

USER_TAB_SUBPARTITIONS describes, for each table subpartition owned by the current user, the subpartition name, name of the table and partition to which it belongs, and its storage attributes. Its columns are the same as those in ALL_TAB_SUBPARTITIONS.

> **See Also:**
>
> "ALL_TAB_SUBPARTITIONS"

7.794 USER_TABLE_ACCESS_STATS

USER_TABLE_ACCESS_STATS displays the scan count for tables and partitions owned by the current user. Its columns (except for TABLE_OWNER) are the same as those in ALL_TABLE_ACCESS_STATS.

> **Note:**
>
> The ALL_TABLE_ACCESS_STATS and DBA_TABLE_ACCESS_STATS views do not display data for Oracle-maintained schemas. You can view data for an Oracle-maintained schema by connecting to the schema and querying the USER_TABLE_ACCESS_STATS view.

> **See Also:**
>
> - "ALL_TABLE_ACCESS_STATS"
> - "DBA_TABLE_ACCESS_STATS"

7.795 USER_TABLE_VIRTUAL_COLUMNS

USER_TABLE_VIRTUAL_COLUMNS describes virtual columns in tables owned by the current user. Its columns are the same as those in ALL_TABLE_VIRTUAL_COLUMNS.

> **See Also:**
>
> "ALL_TABLE_VIRTUAL_COLUMNS"

7.796 USER_TABLES

USER_TABLES describes the relational tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_TABLES.

To gather statistics for this view, use the DBMS_STATS package.

> **See Also:**
>
> "ALL_TABLES"

7.797 USER_TABLESPACES

`USER_TABLESPACES` describes the tablespaces accessible to the current user. Its columns (except for `PLUGGED_IN`) are the same as those in `DBA_TABLESPACES`.

> **See Also:**
>
> "DBA_TABLESPACES"

7.798 USER_TRANSFORMATIONS

`USER_TRANSFORMATIONS` displays information about the transformations owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_TRANSFORMATIONS`.

> **See Also:**
>
> "ALL_TRANSFORMATIONS"

7.799 USER_TRIGGER_COLS

`USER_TRIGGER_COLS` describes the use of columns in the triggers owned by the current user and in triggers on tables owned by the current user. Its columns are the same as those in `ALL_TRIGGER_COLS`.

> **See Also:**
>
> "ALL_TRIGGER_COLS"

7.800 USER_TRIGGER_ORDERING

`USER_TRIGGER_ORDERING` describes the triggers owned by the current user that have `FOLLOWS` or `PRECEDES` ordering. Its columns (except for `TRIGGER_OWNER`) are the same as those in `ALL_TRIGGER_ORDERING`.

> **See Also:**
>
> "ALL_TRIGGER_ORDERING"

7.801 USER_TRIGGERS

`USER_TRIGGERS` describes the triggers owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_TRIGGERS`.

> **See Also:**
>
> "ALL_TRIGGERS"

7.802 USER_TRIGGERS_AE

`USER_TRIGGERS_AE` describes the triggers (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_TRIGGERS_AE`.

> **See Also:**
>
> "ALL_TRIGGERS_AE"

7.803 USER_TS_QUOTAS

`USER_TS_QUOTAS` contains information about tablespace quotas for the current user. Its columns (except for `USERNAME`) the same as those in `DBA_TS_QUOTAS`.

> **See Also:**
>
> "DBA_TS_QUOTAS"

7.804 USER_TSTZ_TAB_COLS

`USER_TSTZ_TAB_COLS` displays information about the columns of the tables owned by the current user, which have columns defined on `TIMESTAMP WITH TIME ZONE` data types or object types containing attributes of `TIMESTAMP WITH TIME ZONE` data types.

Its columns (except for `OWNER`, `COLUMN_NAME`, `NESTED`, `VIRTUAL_COLUMN`, `SCALAR_COLUMN`, and `UNUSED_COLUMN`) are the same as those in `ALL_TSTZ_TAB_COLS`.

> **See Also:**
>
> "ALL_TSTZ_TAB_COLS"

7.805 USER_TSTZ_TABLES

`USER_TSTZ_TABLES` displays information about the tables owned by the current user, which have columns defined on `TIMESTAMP WITH TIME ZONE` data types or object types containing attributes of `TIMESTAMP WITH TIME ZONE` data types.

Its columns (except for `OWNER`) are the same as those in `ALL_TSTZ_TABLES`.

> **See Also:**
>
> "ALL_TSTZ_TABLES"

7.806 USER_TUNE_MVIEW

`USER_TUNE_MVIEW` displays the result of executing the `DBMS_ADVISOR.TUNE_MVIEW` procedure. Its columns (except for `OWNER`) are the same as those in `DBA_TUNE_MVIEW`.

> **See Also:**
>
> "DBA_TUNE_MVIEW"

7.807 USER_TXEVENTQ_MIGRATION_STATUS

`USER_TXEVENTQ_MIGRATION_STATUS` provides information about migrations from AQ classic queues to Transactional Event Queues (TxEventQs) owned by the current user. Its columns (except for `SOURCE_SCHEMA_NAME`) are the same as those in `ALL_TXEVENTQ_MIGRATION_STATUS`.

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

> **See Also:**
>
> "ALL_TXEVENTQ_MIGRATION_STATUS"

7.808 USER_TYPE_ATTRS

`USER_TYPE_ATTRS` describes the attributes of the object types owned by the current user. Its columns (except for `OWNER` and `CHAR_USED`) are the same as those in `ALL_TYPE_ATTRS`.

> **See Also:**
>
> "ALL_TYPE_ATTRS"

7.809 USER_TYPE_METHODS

`USER_TYPE_METHODS` describes the methods of the object types owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_TYPE_METHODS`.

> **See Also:**
>
> "ALL_TYPE_METHODS"

7.810 USER_TYPE_VERSIONS

`USER_TYPE_VERSIONS` describes the versions of the object types owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_TYPE_VERSIONS`.

> **See Also:**
>
> "ALL_TYPE_VERSIONS"

7.811 USER_TYPES

`USER_TYPES` describes the object types owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_TYPES`.

> **See Also:**
>
> "ALL_TYPES"

7.812 USER_UNUSED_COL_TABS

USER_UNUSED_COL_TABS describes the tables owned by the current user that contain unused columns. Its columns (except for OWNER) are the same as those in ALL_UNUSED_COL_TABS.

> **See Also:**
>
> "ALL_UNUSED_COL_TABS"

7.813 USER_UPDATABLE_COLUMNS

USER_UPDATABLE_COLUMNS describes columns in a join view that can be updated by the current user, subject to appropriate privileges. Its columns are the same as those in ALL_UPDATABLE_COLUMNS.

> **See Also:**
>
> - "ALL_UPDATABLE_COLUMNS"
> - *Oracle Database Concepts* for information on updatable join views

7.814 USER_USERS

USER_USERS describes the current user.

Column	Datatype	NULL	Description
USERNAME	VARCHAR2(128)	NOT NULL	Name of the user
USER_ID	NUMBER	NOT NULL	ID number of the user

Column	Datatype	NULL	Description
ACCOUNT_STATUS	VARCHAR2(32)	NOT NULL	Account status: • OPEN The account is open. • EXPIRED The password for the account is expired, either because the PASSWORD_LIFE_TIME limit was reached or because the password was expired by the ALTER USER ... PASSWORD EXPIRE command. The user can log in with the expired password, then change the password. • EXPIRED(GRACE) The password for the account is expired because the PASSWORD_LIFE_TIME limit was reached, but the password change grace period (PASSWORD_GRACE_TIME) has not yet elapsed. The user can log in with the expired password, but will receive an ORA-28002 warning as a reminder that the password must soon be changed. If the PASSWORD_GRACE_TIME elapses, the user can log in with the expired password, then change the password. • LOCKED The account is locked, either by the ALTER USER ... ACCOUNT LOCK command, or because the number of consecutive failed login attempts exceeded the FAILED_LOGIN_ATTEMPTS limit and the value of PASSWORD_LOCK_TIME is UNLIMITED. The account can be unlocked by the ALTER USER ... ACCOUNT UNLOCK command. • LOCKED(TIMED) The account is locked because the number of consecutive failed login attempts exceeded the FAILED_LOGIN_ATTEMPTS limit and the PASSWORD_LOCK_TIME has not yet elapsed. The account can be unlocked either by the ALTER USER ... ACCOUNT UNLOCK command or by waiting until the PASSWORD_LOCK_TIME has elapsed. • EXPIRED & LOCKED The password for the account is expired, as described for the EXPIRED account status, and the account is locked as described for the LOCKED account status. The account can first be unlocked as described for the LOCKED account status, then the password can be changed as described for the EXPIRED account status. • EXPIRED(GRACE) & LOCKED The password for the account is expired, as described for the EXPIRED(GRACE) account status, and the account is locked as described for the LOCKED account status. The account

Column	Datatype	NULL	Description
			can first be unlocked as described for the `LOCKED` account status, then the password can be changed as described for the `EXPIRED(GRACE)` account status. • `EXPIRED & LOCKED(TIMED)` The password for the account is expired, as described for the `EXPIRED` account status, and the account is locked as described for the `LOCKED(TIMED)` account status. The account can first be unlocked as described for the `LOCKED(TIMED)` account status, then the password can be changed as described for the `EXPIRED` account status. • `EXPIRED(GRACE) & LOCKED(TIMED)` The password for the account is expired, as described for the `EXPIRED(GRACE)` account status, and the account is locked as described for the `LOCKED(TIMED)` account status. The account can first be unlocked as described for the `LOCKED(TIMED)` account status, then the password can be changed as described for the `EXPIRED(GRACE)` account status. • `OPEN & IN ROLLOVER` The account is in the password rollover period. The user can log in with either the earlier password or the new password. However, at the time the user logs in, the server recalculates whether the account is still in its password rollover period. If the password rollover period has elapsed, then the login will succeed only if the new password was specified, and the account status will change to `OPEN`. • `EXPIRED & IN ROLLOVER` The account is in the password rollover period and the password is expired as described for the `EXPIRED` account status. The user can log in with either the earlier password or the new password. However, at the time the user logs in, the server recalculates whether the account is still in its password rollover period. If the password rollover period has elapsed, then the login will succeed only if the new password was specified, and the account status will change to `EXPIRED`. After logging in, the user will be prompted to change the password. • `LOCKED & IN ROLLOVER` The account is in the password rollover period and is also locked as described for the `LOCKED` account status. The account can be unlocked as described for the `LOCKED` account status, after which the user can log in as described for the `OPEN & IN ROLLOVER` account status. • `EXPIRED & LOCKED & IN ROLLOVER`

Column	Datatype	NULL	Description
			The account is in the password rollover period, its password is expired as described for the `EXPIRED` account status, and the account is locked as described for the `LOCKED` account status. The account can be unlocked as described for the `LOCKED` account status, after which the user can log in as described for the `EXPIRED & IN ROLLOVER` account status. • `LOCKED(TIMED) & IN ROLLOVER` The account is in the password rollover period and is also locked as described for the `LOCKED(TIMED)` account status. The account can be unlocked as described for the `LOCKED(TIMED)` account status, after which the user can log in with either the earlier password or the new password. However, at the time the user logs in, the server recalculates whether the account is still in its password rollover period. If the password rollover period has elapsed, then the login will succeed only if the new password was specified. • `EXPIRED & LOCKED(TIMED) & IN ROL` The account is in the password rollover period, its password is expired as described for the `EXPIRED` account status, and the account is locked as described for the `LOCKED(TIMED)` account status. The account can be unlocked as described for the `LOCKED(TIMED)` account status, after which the user can log in as described for the `EXPIRED & IN ROLLOVER` account status.
`LOCK_DATE`	`DATE`		Date the account was locked if account status was `LOCKED`
`EXPIRY_DATE`	`DATE`		Date of expiration of the account
`DEFAULT_TABLESPACE`	`VARCHAR2(30)`	`NOT NULL`	Default tablespace for data
`TEMPORARY_TABLESPACE`	`VARCHAR2(30)`	`NOT NULL`	Name of the default tablespace for temporary tables or the name of a tablespace group
`LOCAL_TEMP_TABLESPACE`	`VARCHAR2(30)`		Default local temporary tablespace for the user
`CREATED`	`DATE`	`NOT NULL`	User creation date
`INITIAL_RSRC_CONSUMER_GROUP`	`VARCHAR2(128)`		Initial resource consumer group for the user
`EXTERNAL_NAME`	`VARCHAR2(4000)`		User external name. For centrally managed users, if the database user mapping is an exclusive mapping, then this will be the directory service DN for the user. If this database user is a shared schema, it will be the DN of a group.

Column	Datatype	NULL	Description
PROXY_ONLY_CONNECT	VARCHAR2(1)		Indicates whether a user can connect directly (N) or whether the account can only be proxied (Y) by users who have proxy privileges for this account (that is, by users who have been granted the "connect through" privilege for this account). **Note:** Setting PROXY_ONLY_CONNECT for users is deprecated in this release, and may be desupported in a future release. Oracle recommends that you instead use schema-only accounts. For more information about schema-only accounts, see *Oracle Database Security Guide*.
COMMON	VARCHAR2(3)		Indicates whether a given user is common. Possible values • YES if a user is common • NO if a user is local (not common)
ORACLE_MAINTAINED	VARCHAR2(1)		Denotes whether the user was created, and is maintained, by Oracle-supplied scripts (such as catalog.sql or catproc.sql). A user for which this column has the value Y must not be changed in any way except by running an Oracle-supplied script.
INHERITED	VARCHAR2(3)		Indicates whether the user definition was inherited from another container (YES) or not (NO)
DEFAULT_COLLATION	VARCHAR2(100)		Default collation for the user's schema
IMPLICIT	VARCHAR2(3)		Indicates whether this user is a common user created by an implicit application (YES) or not (NO)
ALL_SHARD	VARCHAR2(3)		In a sharded database, the value in this column indicates whether the user was created with shard DDL enabled. The possible values are: • YES: The user was created with shard DDL enabled. The user exists on all shards and the shard catalog. • NO: The user was created without shard DDL enabled. The user exists only in the database in which the user was created. In a non-sharded database, the value in this column is always NO.
EXTERNAL_SHARD	VARCHAR2(3)		In a federated sharded database, the value in this column indicates whether the user is an external shard user (YES) or not (NO). In other types of databases, the value in this column is always NO.
PASSWORD_CHANGE_DATE	DATE		Date on which the user's password was last set This column is populated only when the value of the AUTHENTICATION_TYPE column is PASSWORD. Otherwise, this column is null.

Column	Datatype	NULL	Description
MANDATORY_PROFILE_VIOLATION	VARCHAR2(3)		If the value in this column is YES, then the user account password violates the mandatory profile password complexity requirements and must be changed before the grace period expires. Otherwise, the value in this column is NO.
PROTECTED	VARCHAR2(3)		Indicates whether the user is a protected user (YES) or not (NO) A protected user can be managed only by another protected user or a common user.
READ_ONLY	VARCHAR2(3)		Indicates whether write privileges for the user are disabled (YES) or enabled (NO)
DICTIONARY_PROTECTED	VARCHAR2(3)		Indicates whether the user's schema is dictionary protected (YES) or not (NO) **See Also:** *Oracle Database Security Guide* for more information about dictionary-protected schemas

See Also:

- "DBA_USERS"
- *Oracle Globally Distributed Database Guide* for more information about sharded database management

7.815 USER_USTATS

USER_USTATS describes the user-defined statistics collected on the tables and indexes owned by the current user. Its columns are the same as those in ALL_USTATS.

See Also:

"ALL_USTATS"

7.816 USER_VARRAYS

USER_VARRAYS describes the varrays owned by the current user. Its columns (except for OWNER) are the same as those in ALL_VARRAYS.

See Also:

"ALL_VARRAYS"

7.817 USER_VIEWS

`USER_VIEWS` describes the views owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_VIEWS`.

> **See Also:**
>
> "ALL_VIEWS"

7.818 USER_VIEWS_AE

`USER_VIEWS_AE` describes the views (across all editions) owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_VIEWS_AE`.

> **See Also:**
>
> "ALL_VIEWS_AE"

7.819 USER_WALLET_ACES

`USER_WALLET_ACES` describes the status of access control entries for the current user to access wallets through PL/SQL network utility packages.

Its columns (except for `ACE_ORDER`, `START_DATE`, `END_DATE`, `GRANT_TYPE`, `INVERTED_PRINCIPAL`, `PRINCIPAL`, `PRINCIPAL_TYPE`, and `STATUS`) are the same as those in `DBA_WALLET_ACES`.

> **See Also:**
>
> "DBA_WALLET_ACES"

7.820 USER_WARNING_SETTINGS

`USER_WARNING_SETTINGS` displays information about the warning parameter settings for the objects owned by the current user. Its columns (except for `OWNER`) are the same as those in `ALL_WARNING_SETTINGS`.

> **See Also:**
>
> "ALL_WARNING_SETTINGS"

7.821 USER_XML_INDEXES

USER_XML_INDEXES describes the XML indexes owned by the current user. Its columns (except for INDEX_OWNER) are the same as those in ALL_XML_INDEXES.

> **See Also:**
>
> "ALL_XML_INDEXES"

7.822 USER_XML_NESTED_TABLES

USER_XML_NESTED_TABLES describes all the tables and their corresponding nested tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_NESTED_TABLES.

> **See Also:**
>
> "ALL_XML_NESTED_TABLES"

7.823 USER_XML_OUT_OF_LINE_TABLES

USER_XML_OUT_OF_LINE_TABLES describes all the out of line tables connected to a given root table for the same schema owned by the current user. Its columns (except for TABLE_OWNER) are the same as those in ALL_XML_OUT_OF_LINE_TABLES.

> **See Also:**
>
> "ALL_XML_OUT_OF_LINE_TABLES"

7.824 USER_XML_SCHEMA_ATTRIBUTES

USER_XML_SCHEMA_ATTRIBUTES describes all the attributes and their properties owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_SCHEMA_ATTRIBUTES.

> **See Also:**
>
> "ALL_XML_SCHEMA_ATTRIBUTES"

7.825 USER_XML_SCHEMA_COMPLEX_TYPES

USER_XML_SCHEMA_COMPLEX_TYPES describes all complex types owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_SCHEMA_COMPLEX_TYPES.

See Also:

"ALL_XML_SCHEMA_COMPLEX_TYPES"

7.826 USER_XML_SCHEMA_ELEMENTS

USER_XML_SCHEMA_ELEMENTS describes all the elements and their properties owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_SCHEMA_ELEMENTS.

See Also:

"ALL_XML_SCHEMA_ELEMENTS"

7.827 USER_XML_SCHEMA_NAMESPACES

USER_XML_SCHEMA_NAMESPACES describes all the available namespaces owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_SCHEMA_NAMESPACES.

See Also:

"ALL_XML_SCHEMA_NAMESPACES"

7.828 USER_XML_SCHEMA_SIMPLE_TYPES

USER_XML_SCHEMA_SIMPLE_TYPES describes all simple types owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_SCHEMA_SIMPLE_TYPES.

See Also:

"ALL_XML_SCHEMA_SIMPLE_TYPES"

7.829 USER_XML_SCHEMA_SUBSTGRP_HEAD

USER_XML_SCHEMA_SUBSTGRP_HEAD describes the heads of substitution groups owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_SCHEMA_SUBSTGRP_HEAD.

> **See Also:**
>
> "ALL_XML_SCHEMA_SUBSTGRP_HEAD"

7.830 USER_XML_SCHEMA_SUBSTGRP_MBRS

USER_XML_SCHEMA_SUBSTGRP_MBRS describes all members of substitution groups owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_SCHEMA_SUBSTGRP_MBRS.

> **See Also:**
>
> "ALL_XML_SCHEMA_SUBSTGRP_MBRS"

7.831 USER_XML_SCHEMAS

USER_XML_SCHEMAS describes the registered XML schemas owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_SCHEMAS.

> **See Also:**
>
> "ALL_XML_SCHEMAS"

7.832 USER_XML_TAB_COLS

USER_XML_TAB_COLS describes the columns of the XML tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_TAB_COLS.

> **See Also:**
>
> "ALL_XML_TAB_COLS"

7.833 USER_XML_TABLES

USER_XML_TABLES describes the XML tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_TABLES.

> **See Also:**
>
> "ALL_XML_TABLES"

7.834 USER_XML_VIEW_COLS

USER_XML_VIEW_COLS describes the columns of the XML views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_VIEW_COLS.

> **See Also:**
>
> "ALL_XML_VIEW_COLS"

7.835 USER_XML_VIEWS

USER_XML_VIEWS describes the XML views owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XML_VIEWS.

> **See Also:**
>
> "ALL_XML_VIEWS"

7.836 USER_XTERNAL_LOC_PARTITIONS

USER_XTERNAL_LOC_PARTITIONS describes partition-level locations owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XTERNAL_LOC_PARTITIONS.

> **See Also:**
>
> "ALL_XTERNAL_LOC_PARTITIONS"

7.837 USER_XTERNAL_LOC_SUBPARTITIONS

USER_XTERNAL_LOC_SUBPARTITIONS describes subpartition-level locations owned by the current user. Its columns (except for TABLE_OWNER) are the same as those in ALL_XTERNAL_LOC_SUBPARTITIONS.

> **See Also:**
>
> "ALL_XTERNAL_LOC_SUBPARTITIONS"

7.838 USER_XTERNAL_PART_TABLES

USER_XTERNAL_PART_TABLES describes object-level information for partitioned external tables owned by the current user. Its columns (except for OWNER) are the same as those in ALL_XTERNAL_PART_TABLES.

> **See Also:**
>
> "ALL_XTERNAL_PART_TABLES"

7.839 USER_XTERNAL_TAB_PARTITIONS

USER_XTERNAL_TAB_PARTITIONS describes partition-level information for partitioned external tables owned by the current user. Its columns (except for TABLE_OWNER) are the same as those in ALL_XTERNAL_TAB_PARTITIONS.

> **See Also:**
>
> "ALL_XTERNAL_TAB_PARTITIONS"

7.840 USER_XTERNAL_TAB_SUBPARTITIONS

USER_XTERNAL_TAB_SUBPARTITIONS describes subpartition-level information for partitioned external tables owned by the current user. Its columns (except for TABLE_OWNER) are the same as those in ALL_XTERNAL_TAB_SUBPARTITIONS.

> **See Also:**
>
> "ALL_XTERNAL_TAB_SUBPARTITIONS"

7.841 USER_ZONEMAP_MEASURES

`USER_ZONEMAP_MEASURES` describes the measures for all the zone maps owned by the user. Its columns are the same as those in `ALL_ZONEMAP_MEASURES`.

> **Note:**
>
> This view is intended for use with Oracle Exadata release 12.1.2.1.1 or later.

> **See Also:**
>
> - "ALL_ZONEMAP_MEASURES"
> - *Oracle Database Data Warehousing Guide* for more information about zone maps

7.842 USER_ZONEMAPS

`USER_ZONEMAPS` describes the zone maps owned by the user. Its columns are the same as those in `ALL_ZONEMAPS`.

> **Note:**
>
> This view is intended for use with Oracle Exadata release 12.1.2.1.1 or later.

> **See Also:**
>
> - "ALL_ZONEMAPS"
> - *Oracle Database Data Warehousing Guide* for more information about zone maps

Part III
Dynamic Performance Views

This part describes the dynamic performance views, which are often referred to as `V$` views.

This part contains the following chapters:

- Dynamic Performance (V$) Views: V$ACCESS to V$HVMASTER_INFO
- Dynamic Performance (V$) Views: V$IM_COLUMN_LEVEL to V$RULE_SET_AGGREGATE_STATS
- Dynamic Performance (V$) Views: V$SCHEDULER_IN_MEMORY_TRACE to V$ZONEMAP_USAGE_STATS

> **Note:**
>
> Oracle also maintains tables and views that change only when a change is made to the data dictionary. These **static** tables and views are described in Static Data Dictionary Views .

> **Note:**
>
> A multitenant container database is the only supported architecture in Oracle Database 21c and later releases. While the documentation is being revised, legacy terminology may persist. In most cases, "database" and "non-CDB" refer to a CDB or PDB, depending on context. In some contexts, such as upgrades, "non-CDB" refers to a non-CDB from a previous release.

8

Dynamic Performance (V$) Views: V$ACCESS to V$HVMASTER_INFO

This chapter describes the first set (in alphabetical order) of dynamic performance views.

The remaining dynamic performance views appear in alphabetical order in Dynamic Performance (V$) Views: V$IM_COLUMN_LEVEL to V$RULE_SET_AGGREGATE_STATS through Dynamic Performance (V$) Views: V$SCHEDULER_IN_MEMORY_TRACE to V$ZONEMAP_USAGE_STATS.

This chapter contains the following topics:

- About Dynamic Performance Views
- Oracle Exadata Database Machine Views
- Dynamic Performance View Descriptions

8.1 About Dynamic Performance Views

Oracle contains a set of underlying views that are maintained by the database server and accessible to the database administrator user `SYS`. These views are called **dynamic performance views** because they are continuously updated while a database is open and in use, and their contents relate primarily to performance.
Although these views appear to be regular database tables, they are not. These views provide data on internal disk structures and memory structures. You can select from these views, but you can never update or alter them.

> **Note:**
>
> - You can query the dynamic performance views to extract information from them. However, only simple queries are supported. If sorts, joins, `GROUP BY` clauses and the like are needed, then you should copy the information from each `V$` view into a table (for example, using a `CREATE TABLE ... AS SELECT` statement), and then query from those tables.
> - Because the information in the `V$` views is dynamic, read consistency is not guaranteed for `SELECT` operations on these views.

The `catalog.sql` script contains definitions of the views and public synonyms for the dynamic performance views. You must run `catalog.sql` to create these views and synonyms. After installation, only user `SYS` or anyone with `SYSDBA` privilege has access to the dynamic performance tables. See *Oracle Database Administrator's Guide* for more information about running `catalog.sql`.

8.1.1 V$ Views

The actual dynamic performance views are identified by the prefix `V_$`. Public synonyms for these views have the prefix `V$`. Database administrators and other users should access only the `V$` objects, not the `V_$` objects.

The dynamic performance views are used by Oracle Enterprise Manager, which is the primary interface for accessing information about system performance. After an instance is started, the `V$` views that read from memory are accessible. Views that read data from disk require that the database be mounted, and some require that the database be open.

V$ views are `CONTAINER_DATA` objects. When a user connected to the root queries a V$ view, the query results will depend on the `CONTAINER_DATA` attribute for users for the view. The `CONTAINER_DATA` clause of the SQL `ALTER USER` statement is used to set and modify users' `CONTAINER_DATA` attribute.

V$ views can return data from different containers in a CDB when queried from the root container. These objects will implicitly convert data to the character set of the root container (AL32UTF8) and then return the result to the user. Some character sets may have character expansion (more bytes needed to represent a character) when converted to AL32UTF8, so there may be data truncation if the view column width is not able to accommodate data from a given PDB.

See Also:

- *Oracle Database Security Guide* for more information about container data objects
- *Oracle Database SQL Language Reference* for more information about the `CONTAINER_DATA` clause for the SQL `ALTER USER` statement

8.1.2 GV$ Views

For almost every `V$` view described in this chapter, Oracle has a corresponding `GV$` (global `V$`) view. In Oracle Real Application Clusters, querying a `GV$` view retrieves the `V$` view information from all qualified instances. In addition to the `V$` information, each `GV$` view contains an extra column named `INST_ID` of data type `NUMBER`. The `INST_ID` column displays the instance number from which the associated `V$` view information was obtained. The `INST_ID` column can be used as a filter to retrieve `V$` information from a subset of available instances. For example, the following query retrieves the information from the `V$LOCK` view on instances 2 and 5:

```
SQL> SELECT * FROM GV$LOCK WHERE INST_ID = 2 OR INST_ID = 5;
```

See Also:

Oracle Real Application Clusters Installation and Configuration Guide for your operating system

GV$ views are CONTAINER_DATA objects. When a user connected to the root queries a GV$ view, the query results will depend on the CONTAINER_DATA attribute for users for the view. The CONTAINER_DATA clause of the SQL ALTER USER statement is used to set and modify users' CONTAINER_DATA attribute.

GV$ views can return data from different containers in a CDB when queried from the root container. These objects will implicitly convert data to the character set of the root container (AL32UTF8) and then return the result to the user. Some character sets may have character expansion (more bytes needed to represent a character) when converted to AL32UTF8, so there may be data truncation if the view column width is not able to accommodate data from a given PDB.

See Also:

- *Oracle Database Security Guide* for more information about container data objects
- *Oracle Database SQL Language Reference* for more information about the CONTAINER_DATA clause for the SQL ALTER USER statement

8.2 Oracle Exadata Database Machine Views

Descriptions of Oracle Exadata Database Machine views are not provided in this manual.

See *Oracle Exadata System Software User's Guide* for descriptions of Oracle Exadata Database Machine views.

Note:

Oracle Exadata Database Machine view names begin with V$CELL.

8.3 Dynamic Performance View Descriptions

The remainder of this chapter describes the dynamic performance views in alphabetical order.

8.4 V$ACCESS

V$ACCESS displays information about locks that are currently imposed on library cache objects.

The locks are imposed to ensure that they are not aged out of the library cache while they are required for SQL execution.

Column	Datatype	Description
SID	NUMBER	Session number that is accessing an object
OWNER	VARCHAR2(64)	Owner of the object

Column	Datatype	Description
OBJECT	VARCHAR2(1000)	Name of the object
TYPE	VARCHAR2(64)	Type identifier for the object
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.5 V$ACTIVE_INSTANCES

V$ACTIVE_INSTANCES displays the mapping between instance names and instance numbers for all instances that have the database currently mounted.

Column	Datatype	Description
INST_NUMBER	NUMBER	Instance number
INST_NAME	VARCHAR2(256)	Instance name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.6 V$ACTIVE_SERVICES

V$ACTIVE_SERVICES displays information about the active services in the database.

Column	Datatype	Description
SERVICE_ID	NUMBER	Service ID
NAME	VARCHAR2(64)	Name of the service
NAME_HASH	NUMBER	Service name hash
NETWORK_NAME	VARCHAR2(512)	Network name
CREATION_DATE	DATE	Creation date
CREATION_DATE_HASH	NUMBER	Creation date hash

Column	Datatype	Description
GOAL	VARCHAR2(12)	Runtime Load Balancing Goal being used to create run-time load balancing and connection load balancing advice: • NONE • SERVICE_TIME - Connections are balanced by response time • THROUGHPUT - Connections are balanced by throughput
DTP	VARCHAR2(1)	Indicates whether or not Distributed Transaction Processing is enabled for this service. When Distributed Transaction Processing is set to Y (YES), it means that the service is offered at exactly one instance at a time for XA affinity. Possible values: • Y - YES • N - NO
BLOCKED	CHAR(2)	Indicates whether a service on the specified instance is blocked from accepting new connections altogether (YES) or not (NO). If a service is blocked, then all connections will be directed to other instances (if any) that are hosting the desired service.
AQ_HA_NOTIFICATION	VARCHAR2(3)	Indicates whether FAN - Fast Application Notification for OCI connections is set (YES) or not (NO)
CLB_GOAL	VARCHAR2(5)	Connection load balancing goal used with statistics that are sent to the listeners to determine how new connections are distributed: • LONG • SHORT
COMMIT_OUTCOME	VARCHAR2(3)	For Transaction Guard and Database Native Transaction Guard, indicates whether the database service associated with the user session has the COMMIT_OUTCOME service attribute enabled (YES) or not (NO). This attribute applies on a per session basis and is set at connect time. When the value of this column is YES, the commit status is managed for all supported transaction types and the outcome of a COMMIT transaction is preserved after the COMMIT has executed. Refer to the COMMIT_OUTCOME_FASTPATH column to view the preferred method for preserving the commit outcome. **See Also:** *Oracle Database Development Guide* for information about preserving the commit outcome
RETENTION_TIME	NUMBER	For Transaction Guard and Database Native Transaction Guard, when COMMIT_OUTCOME = YES, this value indicates the amount of time (in seconds) that the commit outcome is retained in the database.
REPLAY_INITIATION_TIMEOUT	NUMBER	For Application Continuity, this option specifies the difference between the time (in seconds) of original execution of the first operation of a request and the time that the replay is ready to start after a successful reconnect. Application Continuity will not replay after the specified amount of time has passed. This option is intended to avoid the unintentional execution of a transaction when a system is recovered after a long period of time. The default is 5 minutes (300 seconds).

Column	Datatype	Description
SESSION_STATE_CONSISTENCY	VARCHAR2(128)	Describes how non-transactional is changed during a request. This parameter is considered only if `failover_type` is set to `TRANSACTION` for Application Continuity. Examples of session state are NLS settings, optimizer preferences, event settings, PL/SQL global variables, temporary tables, advanced queues, LOBs, and result cache. If non-transactional values change after the request starts, the default value of `DYNAMIC` should be set. Almost all applications should use `DYNAMIC` mode. If you are unsure, use `DYNAMIC` mode.
GLOBAL	VARCHAR2(3)	Indicates whether the service is global. A global service is managed by Global Service Manager (GSM) and can be provided by multiple databases that contain replicated data. Possible values: • `YES`: Indicates the service is global • `NO`: Indicates the service is not global
CON_NAME	VARCHAR2(128)	Container name of the object. The value of this column is `NULL` in non-CDBs.
SQL_TRANSLATION_PROFILE	VARCHAR2(261)	A non-NULL value specifies the initial SQL translation profile for subsequent database connections that use the service and do not specify a SQL translation profile. A NULL value has no effect.
MAX_LAG_TIME	VARCHAR2(128)	The maximum replication lag (in seconds) that is acceptable for a data replica to be used for providing the database service. Can only be specified for global services.
STOP_OPTION	VARCHAR2(128)	Stop option for sessions of this service for planned maintenance
FAILOVER_RESTORE	VARCHAR2(128)	Indicates whether sessions recover their commonly used session state (like NLS, schema) when they are failed over with TAF
DRAIN_TIMEOUT	NUMBER	Number of seconds to wait for sessions to be drained
TABLE_FAMILY_ID	NUMBER	Sharded table family ID associated with the service
PLACEMENT_TEMPLATE	VARCHAR2(64)	Reserved for future use

Column	Datatype	Description
COMMIT_OUTCOME_FASTPATH	VARCHAR2(3)	For Transaction Guard and Database Native Transaction Guard, when COMMIT_OUTCOME = YES, the value of this column indicates the preferred method for preserving the commit outcome. Possible values: • YES - Database Native Transaction Guard is used. Each transaction is assigned a unique transaction identifier (DB XID) in the database. The DB XID and status of the corresponding transaction are maintained persistently in a transaction table. Note that if COMMIT_OUTCOME = YES, then the value of COMMIT_OUTCOME_FASTPATH defaults to YES. • NO - Transaction Guard is used. A logical transaction ID (LTXID) is set for each user session at login and at each successful commit. LTXIDs are used only when the commit is not in the same round-trip to the database as the start of the transaction. Moreover, some transaction types, such as commit on success transactions, DDL transactions, and PL/SQL transactions, will continue to use LTXIDs in the same round-trip. When Transaction Guard is used, the outcome of a COMMIT transaction is known. If there is an outage, the application can use DBMS_APP_CONT.GET_LTXID_OUTCOME to return a reliable status for the last in-flight work. **See Also:** *Oracle Real Application Clusters Administration and Deployment Guide* for information about logical transaction IDs
TRUE_CACHE_SERVICE	VARCHAR2(64)	True Cache service associated with this database service
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.7 V$ACTIVE_SESS_POOL_MTH

V$ACTIVE_SESS_POOL_MTH displays available active session pool resource allocation methods.

Column	Datatype	Description
NAME	VARCHAR2(40)	Name of the active session pool resource allocation method
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.8 V$ACTIVE_SESSION_HISTORY

V$ACTIVE_SESSION_HISTORY displays sampled session activity in the database.

It contains snapshots of active database sessions taken once a second. A database session is considered active if it was on the CPU or was waiting for an event that didn't belong to the Idle wait class. Refer to the V$EVENT_NAME view for more information on wait classes.

This view contains one row for each active session per sample and returns the latest session sample rows first. A majority of the columns describing the session in the active session history are present in the V$SESSION view.

Column	Datatype	Description
SAMPLE_ID	NUMBER	ID of the sample
SAMPLE_TIME	TIMESTAMP(3)	Time at which the sample was taken
SAMPLE_TIME_UTC	TIMESTAMP(3)	Time at which the sample was taken in UTC (Coordinated Universal Time) time zone
USECS_PER_ROW	NUMBER	Time in microseconds since the last sample was taken
IS_AWR_SAMPLE	VARCHAR2(1)	Indicates whether this sample has been flushed or will be flushed to the Automatic Workload Repository (DBA_HIST_ACTIVE_SESS_HISTORY) (Y) or not (N)
SESSION_ID	NUMBER	Session identifier; maps to V$SESSION.SID
SESSION_SERIAL#	NUMBER	Session serial number (used to uniquely identify a session's objects); maps to V$SESSION.SERIAL#
SESSION_TYPE	VARCHAR2(10)	Session type: • FOREGROUND • BACKGROUND
FLAGS	NUMBER	Reserved for future use
USER_ID	NUMBER	Oracle user identifier; maps to V$SESSION.USER#
SQL_ID	VARCHAR2(13)	SQL identifier of the SQL statement that the session was executing at the time of sampling
IS_SQLID_CURRENT	VARCHAR2(1)	Indicates whether the SQL identifier in the SQL_ID column is being executed (Y) or not (N)
SQL_CHILD_NUMBER	NUMBER	Child number of the SQL statement that the session was executing at the time of sampling
SQL_OPCODE	NUMBER	Indicates what phase of operation the SQL statement was in; maps to V$SESSION.COMMAND **See Also:** "V$SESSION" for information on interpreting this column
SQL_OPNAME	VARCHAR2(64)	SQL command name
FORCE_MATCHING_SIGNATURE	NUMBER	Signature used when the CURSOR_SHARING parameter is set to FORCE
TOP_LEVEL_SQL_ID	VARCHAR2(13)	SQL identifier of the top level SQL statement
TOP_LEVEL_SQL_OPCODE	NUMBER	Indicates what phase of operation the top level SQL statement was in
SQL_ADAPTIVE_PLAN_RESOLVED	NUMBER	Indicates whether the SQL plan of the sampled database session is a resolved adaptive plan or not

Column	Datatype	Description
SQL_FULL_PLAN_HASH_VALUE	NUMBER	Numerical representation of the complete SQL plan for the cursor being executed by this session
SQL_PLAN_HASH_VALUE	NUMBER	Numeric representation of the SQL plan for the cursor. This information might not be available for all session samples. V$SESSION does not contain this information.
SQL_PLAN_LINE_ID	NUMBER	SQL plan line ID
SQL_PLAN_OPERATION	VARCHAR2(30)	Plan operation name
SQL_PLAN_OPTIONS	VARCHAR2(30)	Plan operation options
SQL_EXEC_ID	NUMBER	SQL execution identifier
SQL_EXEC_START	DATE	Time when the execution of the SQL started
PLSQL_ENTRY_OBJECT_ID	NUMBER	Object ID of the top-most PL/SQL subprogram on the stack; NULL if there is no PL/SQL subprogram on the stack. Maps to DBA_OBJECTS.OBJECT_ID.
PLSQL_ENTRY_SUBPROGRAM_ID	NUMBER	Subprogram ID of the top-most PL/SQL subprogram on the stack. Maps to DBA_OBJECTS.DATA_OBJECT_ID.
PLSQL_OBJECT_ID	NUMBER	Object ID of the currently executing PL/SQL subprogram. Maps to DBA_OBJECTS.OBJECT_ID.
PLSQL_SUBPROGRAM_ID	NUMBER	Subprogram ID of the currently executing PL/SQL object; NULL if executing SQL. Maps to DBA_OBJECTS.DATA_OBJECT_ID.
QC_INSTANCE_ID	NUMBER	Query coordinator instance ID. This information is only available if the sampled session is a parallel query worker. For all other sessions, the value is 0.
QC_SESSION_ID	NUMBER	Query coordinator session ID. This information is only available if the sampled session is a parallel query worker. For all other sessions, the value is 0.
QC_SESSION_SERIAL#	NUMBER	Query coordinator session serial number. This information is only available if the sampled session is a parallel query worker. For all other sessions, the value is 0.
PX_FLAGS	NUMBER	Reserved for internal use
EVENT	VARCHAR2(64)	If SESSION_STATE = WAITING, then the event for which the session was waiting for at the time of sampling. If SESSION_STATE = ON CPU, then this column is NULL. **See Also:** Oracle Wait Events
EVENT_ID	NUMBER	Identifier of the resource or event for which the session is waiting or for which the session last waited. Interpretation is similar to that of the EVENT column.
EVENT#	NUMBER	Number of the resource or event for which the session is waiting or for which the session last waited. Interpretation is similar to that of the EVENT column.
SEQ#	NUMBER	Sequence number that uniquely identifies the wait (incremented for each wait)
P1TEXT	VARCHAR2(64)	Text of the first additional parameter
P1	NUMBER	First additional parameter
P2TEXT	VARCHAR2(64)	Text of the second additional parameter
P2	NUMBER	Second additional parameter
P3TEXT	VARCHAR2(64)	Text of the third additional parameter

Column	Datatype	Description
P3	NUMBER	Third additional parameter
WAIT_CLASS	VARCHAR2(64)	Wait class name of the event for which the session was waiting at the time of sampling. Interpretation is similar to that of the EVENT column. Maps to V$SESSION.WAIT_CLASS.
WAIT_CLASS_ID	NUMBER	Wait class identifier of the event for which the session was waiting at the time of sampling. Interpretation is similar to that of the EVENT column. Maps to V$SESSION.WAIT_CLASS_ID.
WAIT_TIME	NUMBER	Total wait time for the event for which the session last waited if the session was on the CPU when sampled; 0 if the session was waiting at the time of sampling **Note:** Whether or not WAIT_TIME = 0 is what is useful to find the SESSION_STATE at the time of sampling, rather than the actual value of WAIT_TIME itself. Maps to V$SESSION.WAIT_TIME.
SESSION_STATE	VARCHAR2(7)	Session state: • WAITING • ON CPU
TIME_WAITED	NUMBER	If SESSION_STATE = WAITING, then the time that the session actually spent waiting for that event (in microseconds). This column is set for waits that were in progress at the time the sample was taken. If a wait event lasted for more than a second and was caught waiting in more than one session sample row, then the actual time spent waiting for that wait event will be populated in the last of those session sample rows. At any given time, this information will not be available for the latest session sample.
BLOCKING_SESSION_STATUS	VARCHAR2(11)	Status of the blocking session: • VALID • NO HOLDER • GLOBAL • NOT IN WAIT • UNKNOWN
BLOCKING_SESSION	NUMBER	Session identifier of the blocking session. Populated only if the blocker is on the same instance and the session was waiting for enqueues or a "buffer busy" wait. Maps to V$SESSION.BLOCKING_SESSION.
BLOCKING_SESSION_SERIAL#	NUMBER	Serial number of the blocking session
BLOCKING_INST_ID	NUMBER	Instance number of the blocker shown in BLOCKING_SESSION
BLOCKING_HANGCHAIN_INFO	VARCHAR2(1)	Indicates whether the information about BLOCKING_SESSION comes from the hang chain (Y) or not (N)
CURRENT_OBJ#	NUMBER	Object ID of the object that the session is referencing. This information is only available if the session was waiting for application, cluster, concurrency, and user I/O wait events. Maps to V$SESSION.ROW_WAIT_OBJ#.
CURRENT_FILE#	NUMBER	File number of the file containing the block that the session is referencing. This information is only available if the session was waiting for cluster, concurrency, and user I/O wait events. Maps to V$SESSION.ROW_WAIT_FILE#.

Column	Datatype	Description
CURRENT_BLOCK#	NUMBER	ID of the block that the session is referencing. This information is only available if the session was waiting for cluster, concurrency, and user I/O wait events. Maps to V$SESSION.ROW_WAIT_BLOCK#.
CURRENT_ROW#	NUMBER	Row identifier that the session is referencing. This information is only available if the session was waiting for cluster, concurrency, and user I/O wait events. Maps to V$SESSION.ROW_WAIT_ROW#.
TOP_LEVEL_CALL#	NUMBER	Oracle top level call number
TOP_LEVEL_CALL_NAME	VARCHAR2(64)	Oracle top level call name
CONSUMER_GROUP_ID	NUMBER	Consumer group ID
XID	RAW(8)	Transaction ID that the session was working on at the time of sampling. V$SESSION does not contain this information.
REMOTE_INSTANCE#	NUMBER	Remote instance identifier that will serve the block that this session is waiting for. This information is only available if the session was waiting for cluster events.
TIME_MODEL	NUMBER	Time model information
IN_CONNECTION_MGMT	VARCHAR2(1)	Indicates whether the session was doing connection management at the time of sampling (Y) or not (N)
IN_PARSE	VARCHAR2(1)	Indicates whether the session was parsing at the time of sampling (Y) or not (N)
IN_HARD_PARSE	VARCHAR2(1)	Indicates whether the session was hard parsing at the time of sampling (Y) or not (N)
IN_SQL_EXECUTION	VARCHAR2(1)	Indicates whether the session was executing SQL statements at the time of sampling (Y) or not (N)
IN_PLSQL_EXECUTION	VARCHAR2(1)	Indicates whether the session was executing PL/SQL at the time of sampling (Y) or not (N)
IN_PLSQL_RPC	VARCHAR2(1)	Indicates whether the session was executing inbound PL/SQL RPC calls at the time of sampling (Y) or not (N)
IN_PLSQL_COMPILATION	VARCHAR2(1)	Indicates whether the session was compiling PL/SQL at the time of sampling (Y) or not (N)
IN_JAVA_EXECUTION	VARCHAR2(1)	Indicates whether the session was executing Java at the time of sampling (Y) or not (N)
IN_BIND	VARCHAR2(1)	Indicates whether the session was doing bind operations at the time of sampling (Y) or not (N)
IN_CURSOR_CLOSE	VARCHAR2(1)	Indicates whether the session was closing a cursor at the time of sampling (Y) or not (N)
IN_SEQUENCE_LOAD	VARCHAR2(1)	Indicates whether the session is loading in sequence (in sequence load code) (Y) or not (N)
IN_INMEMORY_QUERY	VARCHAR2(1)	Indicates whether the session was querying the In-Memory Column Store (IM column store) at the time of sampling (Y) or not (N)
IN_INMEMORY_POPULATE	VARCHAR2(1)	Indicates whether the session was populating the IM column store at the time of sampling (Y) or not (N)
IN_INMEMORY_PREPOPULATE	VARCHAR2(1)	Indicates whether the session was prepopulating the IM column store at the time of sampling (Y) or not (N)
IN_INMEMORY_REPOPULATE	VARCHAR2(1)	Indicates whether the session was repopulating the IM column store at the time of sampling (Y) or not (N)

Column	Datatype	Description
IN_INMEMORY_TREPOPULATE	VARCHAR2(1)	Indicates whether the session was trickle repopulating the IM column store at the time of sampling (Y) or not (N)
IN_TABLESPACE_ENCRYPTION	VARCHAR2(1)	Indicates whether encryption or decryption of a tablespace occurred at the time of sampling (Y) or not (N)
CAPTURE_OVERHEAD	VARCHAR2(1)	Indicates whether the session is executing capture code (Y) or not (N)
REPLAY_OVERHEAD	VARCHAR2(1)	Indicates whether the session is executing replay code (Y) or not (N)
IS_CAPTURED	VARCHAR2(1)	Indicates whether the session is being captured (Y) or not (N)
IS_REPLAYED	VARCHAR2(1)	Indicates whether the session is being replayed (Y) or not (N)
IS_REPLAY_SYNC_TOKEN_HOLDER	VARCHAR2(1)	Indicates whether the session is holding a synchronization token (Y) or not (N) during workload replay
SPID	VARCHAR2(24)	Operating system process identifier
STID	VARCHAR2(24)	Operating system thread identifier
SERVICE_HASH	NUMBER	Hash that identifies the Service; maps to V$ACTIVE_SERVICES.NAME_HASH
PROGRAM	VARCHAR2(84)	Name of the operating system program
MODULE	VARCHAR2(64)	Name of the executing module when sampled, as set by the DBMS_APPLICATION_INFO.SET_MODULE procedure
ACTION	VARCHAR2(64)	Name of the executing module when sampled, as set by the DBMS_APPLICATION_INFO.SET_ACTION procedure
CLIENT_ID	VARCHAR2(64)	Client identifier of the session; maps to V$SESSION.CLIENT_IDENTIFIER
CLIENT_INFO	VARCHAR2(64)	Client information for the session; maps to V$SESSION.CLIENT_INFO
MACHINE	VARCHAR2(64)	Client's operating system machine name
PORT	NUMBER	Client port number
ECID	VARCHAR2(64)	Execution context identifier (sent by Application Server)
DBREPLAY_FILE_ID	NUMBER	If the session is being captured or replayed, then DBREPLAY_FILE_ID is the file ID for the workload capture or workload replay; otherwise it is NULL.
DBREPLAY_CALL_COUNTER	NUMBER	If the session is being captured or replayed, then DBREPLAY_CALL_COUNTER is the call counter of the user call that is being captured or replayed; otherwise it is NULL.
TM_DELTA_TIME	NUMBER	Time interval (in microseconds) over which TM_DELTA_CPU_TIME and TM_DELTA_DB_TIME are accumulated
TM_DELTA_CPU_TIME	NUMBER	Amount of time this session spent on CPU over the last TM_DELTA_TIME microseconds
TM_DELTA_DB_TIME	NUMBER	Amount of time spent by this session in database calls over the last TM_DELTA_TIME microseconds
DELTA_TIME	NUMBER	Time interval (in microseconds) since the last time this session was sampled or created, over which the next five statistics are accumulated
DELTA_READ_IO_REQUESTS	NUMBER	Number of read I/O requests made by this session over the last DELTA_TIME microseconds

Column	Datatype	Description
DELTA_WRITE_IO_REQUESTS	NUMBER	Number of write I/O requests made by this session over the last DELTA_TIME microseconds
DELTA_READ_IO_BYTES	NUMBER	Number of I/O bytes read by this session over the last DELTA_TIME microseconds
DELTA_WRITE_IO_BYTES	NUMBER	Number of I/O bytes written by this session over the last DELTA_TIME microseconds
DELTA_INTERCONNECT_IO_BYTES	NUMBER	Number of I/O bytes sent over the I/O interconnect over the last DELTA_TIME microseconds
DELTA_READ_MEM_BYTES	NUMBER	Number of read bytes through the buffer cache
PGA_ALLOCATED	NUMBER	Amount of PGA memory (in bytes) consumed by this session at the time this sample was taken
TEMP_SPACE_ALLOCATED	NUMBER	Amount of TEMP memory (in bytes) consumed by this session at the time this sample was taken
CON_DBID	NUMBER	The database ID of the pluggable database (PDB)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
DBOP_NAME	VARCHAR2(30)	Database operation name. If the type is SQL, the DBOP_NAME will be NULL.
DBOP_EXEC_ID	NUMBER	Database operation execution identifier for the current execution. If the type is SQL, the DBOP_EXEC_ID will be NULL.

See Also:

- "V$SESSION"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLICATION_INFO.SET_MODULE procedure
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLICATION_INFO.SET_ACTION procedure

8.9 V$ACTIVITY_MVIEW

V$ACTIVITY_MVIEW describes the materialized view activity snapshots that are currently being taken by the Object Activity Tracking System (OATS).

Each row in this view represents one in-progress activity snapshot and describes the materialized view activity that has occurred so far during the snapshot interval.

Column	Datatype	Description
MVIEW_NAME	VARCHAR2(128)	Name of the materialized view for which the activity snapshot is being taken
MVIEW_OWNER	VARCHAR2(128)	Owner of the materialized view for which the activity snapshot is being taken
USER_CLASS	VARCHAR2(7)	Indicates whether the activity was performed by the RDBMS (SYS) or by a user (NON-SYS)
COMPILES	NUMBER	Number of times the materialized view was compiled This number includes: • Explicit compiles performed with the SQL statement ALTER MATERIALIZED VIEW ... COMPILE • Automatic compiles that occurred because the structure of an underlying base table changed
REWRITES_TEXTMATCH	NUMBER	Number of query rewrites that used the text match rewrite method
REWRITES_GENERAL	NUMBER	Number of query rewrites that used general rewrite methods
REWRITES_PARTIAL	NUMBER	Number of query rewrites that occurred when the view was partially stale This number includes: • UNION ALL operations involving rewritten queries that had one branch with the materialized view and the other branch with its underlying base tables (partial rewrites) • Single query block rewrites of the materialized view that involved a join back to its underlying base table
REWRITES_DELTA	NUMBER	Number of query rewrites that used stale data in the materialized view plus the delta information stored in the materialized view logs
REWRITES_PCT	NUMBER	Number of partition change tracking (PCT) rewrites
REWRITES_HINTED	NUMBER	Number of query rewrites that occurred because the materialized view was eligible for query rewrite and the SELECT statement contained the REWRITE hint with the name of the materialized view specified in the hint
NOREWRITES_HINTED	NUMBER	Reserved for future use
NOREWRITES_STALE	NUMBER	Number of query executions that did not use query rewrite because the materialized view was eligible for query rewrite, but stale
REFRESHES_ON_DEMAND	NUMBER	Number of ON DEMAND refreshes This type of refresh is performed on materialized views that use the ON DEMAND refresh mode, which instructs the database to refresh the materialized view only when a manual refresh is launched by one of the three DBMS_MVIEW refresh procedures.
REFRESHES_ON_COMMIT	NUMBER	Number of ON COMMIT refreshes This type of refresh is performed on materialized views that use the ON COMMIT refresh mode, which instructs the database to refresh the materialized view whenever the database commits a transaction that operates on a master table of the materialized view.

Column	Datatype	Description
REFRESHES_ON_STATEMENT	NUMBER	Number of ON STATEMENT refreshes This type of refresh is performed on materialized views that use the ON STATEMENT refresh mode, which instructs the database to perform an automatic refresh of the materialized view every time a DML operation is performed on any of the view's base tables.
REFRESHES_SCHEDULED	NUMBER	Number of scheduled refreshes
REFRESHES_AUTOMATIC	NUMBER	Number of automatic refreshes
REFRESHES_FAST	NUMBER	Number of incremental refreshes
REFRESHES_COMPLETE	NUMBER	Number of full refreshes
REFRESHES_PCT	NUMBER	Number of partition change tracking (PCT) refreshes
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

The counts in this view are approximate in order to keep system overhead low. Also, there are database activities, such as statistics collection, query compilation, and query optimization, that may cause the counts to be different than expected or to vary slightly across successive queries.

See Also:

"DBA_ACTIVITY_MVIEW" to view recently completed materialized view activity snapshots

8.10 V$ACTIVITY_TABLE

V$ACTIVITY_TABLE describes the table activity snapshots that are currently being taken by the Object Activity Tracking System (OATS).

Each row in this view represents one in-progress activity snapshot and describes the table activity that has occurred so far during the snapshot interval.

Column	Datatype	Description
TABLE_NAME	VARCHAR2(128)	Name of the table for which the activity snapshot is being taken
TABLE_OWNER	VARCHAR2(128)	Owner of the table for which the activity snapshot is being taken
USER_CLASS	VARCHAR2	Reserved for future use

Column	Datatype	Description
SCANS	NUMBER	Number of table scans
LOADS	NUMBER	Number of table loads
LOAD_ROWS	NUMBER	Number of rows that were loaded into the table
INSERT_ROWS	NUMBER	Number of rows that were inserted into the table
DELETE_ROWS	NUMBER	Number of rows that were deleted from the table
UPDATE_ROWS	NUMBER	Number of table rows that were updated
TRUNCATES	NUMBER	Number of table truncations
TRUNCATED_ROWS	NUMBER	Number of table rows that were deleted due to table truncations
PARTITION_TRUNCATES	NUMBER	Number of table partition or subpartition truncations
PARTITION_TRUNCATED_ROWS	NUMBER	Number of table rows that were deleted due to table partition or subpartition truncations
PARTITION_CREATES	NUMBER	Number of table partitions or subpartitions that were created
PARTITION_DROPS	NUMBER	Number of table partition or subpartition drops
PARTITION_DROPS_ROWS	NUMBER	Number of table rows that were dropped due to table partition or subpartition drops
PARTITION_MOVES	NUMBER	Number of table partition or subpartition moves
PARTITION_MOVES_ROWS	NUMBER	Number of table rows that were moved due to table partition or subpartition moves
PARTITION_SPLITS	NUMBER	Number of table partition or subpartition splits
PARTITION_SPLITS_ROWS	NUMBER	Number of table rows that were split due to table partition or subpartition splits
PARTITION_MERGES	NUMBER	Number of table partition or subpartition merges
PARTITION_MERGES_ROWS	NUMBER	Number of table rows that were merged due to table partition or subpartition merges
PARTITION_COALESCES	NUMBER	Number of table partition or subpartition coalesces
PARTITION_COALESCE_ROWS	NUMBER	Number of table rows that were redistributed due to table partition or subpartition coalesces
PARTITION_EXCHANGES	NUMBER	Number of table partition or subpartition exchanges
PARTITION_EXCHANGES_ROWS	NUMBER	Number of table rows that were exchanged due to table partition or subpartition exchanges
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> The counts in this view are approximate in order to keep system overhead low. Also, there are database activities, such as statistics collection, query compilation, and query optimization, that may cause the counts to be different than expected or to vary slightly across successive queries.

> **Note:**
>
> This view does not contain information related to temporary tables or external tables.

> **See Also:**
>
> "DBA_ACTIVITY_TABLE" to view recently completed table activity snapshots

8.11 V$ADVISOR_PROGRESS

V$ADVISOR_PROGRESS displays information about the progress of advisor execution.

Column	Datatype	Description
SID	NUMBER	Session ID
SERIAL#	NUMBER	Session serial number
USERNAME	VARCHAR2(128)	Oracle user name
OPNAME	VARCHAR2(64)	Operation name
ADVISOR_NAME	VARCHAR2(64)	Advisor name
TASK_ID	NUMBER	Task ID
TARGET_DESC	VARCHAR2(32)	Description of the target of the advisor
SOFAR	NUMBER	Amount of work done so far
TOTALWORK	NUMBER	Total work to be done
UNITS	VARCHAR2(32)	Units that the work is measured in
BENEFIT_SOFAR	NUMBER	Benefit obtained so far
BENEFIT_MAX	NUMBER	Estimate of maximum benefit that could be obtained
FINDINGS	NUMBER	Number of findings so far
RECOMMENDATIONS	NUMBER	Number of recommendations so far
TIME_REMAINING	NUMBER	Estimate of time remaining for the completion of the task (in seconds)
START_TIME	DATE	Start time of the task
LAST_UPDATE_TIME	DATE	Last time progress was posted
ELAPSED_SECONDS	NUMBER	Elapsed time so far

Column	Datatype	Description
ADVISOR_METRIC1	NUMBER	Value of the advisor-specific metric
METRIC1_DESC	VARCHAR2(64)	Description of the advisor-specific metric
EXECUTION_TYPE	VARCHAR2(64)	Type of the last execution. This information is optional for single-execution tasks.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.12 V$ALERT_TYPES

V$ALERT_TYPES displays information about server alert types.

Column	Datatype	Description
REASON_ID	NUMBER	ID of the alert reason
OBJECT_TYPE	VARCHAR2(64)	Object type
TYPE	VARCHAR2(9)	Alert type: • Stateful • Stateless
GROUP_NAME	VARCHAR2(64)	Group name
SCOPE	VARCHAR2(8)	Scope: • Database • Instance
INTERNAL_METRIC_CATEGORY	VARCHAR2(64)	Internal metric category
INTERNAL_METRIC_NAME	VARCHAR2(64)	Internal metric name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.13 V$ALL_ACTIVE_SESSION_HISTORY

V$ALL_ACTIVE_SESSION_HISTORY displays sampled session activity in the database.

> **Note:**
>
> V$ALL_ACTIVE_SESSION_HISTORY allows application developers to view their own session activity. It is similar to the V$ACTIVE_SESSION_HISTORY view, with the following exception:
>
> - When queried by the SYS user or anyone with the SYSDBA privilege, the V$ALL_ACTIVE_SESSION_HISTORY view displays the same data as the V$ACTIVE_SESSION_HISTORY view.
> - When queried by any other user, the V$ALL_ACTIVE_SESSION_HISTORY view displays only data about sessions owned by that user.
>
> See also "V$ACTIVE_SESSION_HISTORY"

Column	Datatype	Description
SAMPLE_ID	NUMBER	ID of the sample
SAMPLE_TIME	TIMESTAMP(3)	Time at which the sample was taken
SAMPLE_TIME_UTC	TIMESTAMP(3)	Time at which the sample was taken in UTC (Coordinated Universal Time) time zone
USECS_PER_ROW	NUMBER	Time in microseconds since the last sample was taken
IS_AWR_SAMPLE	VARCHAR2(1)	Indicates whether this sample has been flushed or will be flushed to the Automatic Workload Repository (DBA_HIST_ACTIVE_SESS_HISTORY) (Y) or not (N)
SESSION_ID	NUMBER	Session identifier; maps to V$SESSION.SID
SESSION_SERIAL#	NUMBER	Session serial number (used to uniquely identify a session's objects); maps to V$SESSION.SERIAL#
SESSION_TYPE	VARCHAR2(10)	Session type: • FOREGROUND • BACKGROUND
FLAGS	NUMBER	Reserved for future use
USER_ID	NUMBER	Oracle user identifier; maps to V$SESSION.USER#
SQL_ID	VARCHAR2(13)	SQL identifier of the SQL statement that the session was executing at the time of sampling
IS_SQLID_CURRENT	VARCHAR2(1)	Indicates whether the SQL identifier in the SQL_ID column is being executed (Y) or not (N)
SQL_CHILD_NUMBER	NUMBER	Child number of the SQL statement that the session was executing at the time of sampling
SQL_OPCODE	NUMBER	Indicates what phase of operation the SQL statement was in; maps to V$SESSION.COMMAND **See Also:** "V$SESSION" for information on interpreting this column

Column	Datatype	Description
SQL_OPNAME	VARCHAR2(64)	SQL command name
FORCE_MATCHING_SIGNATURE	NUMBER	Signature used when the CURSOR_SHARING parameter is set to FORCE
TOP_LEVEL_SQL_ID	VARCHAR2(13)	SQL identifier of the top level SQL statement
TOP_LEVEL_SQL_OPCODE	NUMBER	Indicates what phase of operation the top level SQL statement was in
SQL_ADAPTIVE_PLAN_RESOLVED	NUMBER	Indicates whether the SQL plan of the sampled database session is a resolved adaptive plan or not
SQL_FULL_PLAN_HASH_VALUE	NUMBER	Numerical representation of the complete SQL plan for the cursor being executed by this session
SQL_PLAN_HASH_VALUE	NUMBER	Numeric representation of the SQL plan for the cursor. This information might not be available for all session samples. V$SESSION does not contain this information.
SQL_PLAN_LINE_ID	NUMBER	SQL plan line ID
SQL_PLAN_OPERATION	VARCHAR2(30)	Plan operation name
SQL_PLAN_OPTIONS	VARCHAR2(30)	Plan operation options
SQL_EXEC_ID	NUMBER	SQL execution identifier
SQL_EXEC_START	DATE	Time when the execution of the SQL started
PLSQL_ENTRY_OBJECT_ID	NUMBER	Object ID of the top-most PL/SQL subprogram on the stack; NULL if there is no PL/SQL subprogram on the stack. Maps to DBA_OBJECTS.OBJECT_ID.
PLSQL_ENTRY_SUBPROGRAM_ID	NUMBER	Subprogram ID of the top-most PL/SQL subprogram on the stack. Maps to DBA_OBJECTS.DATA_OBJECT_ID.
PLSQL_OBJECT_ID	NUMBER	Object ID of the currently executing PL/SQL subprogram. Maps to DBA_OBJECTS.OBJECT_ID.
PLSQL_SUBPROGRAM_ID	NUMBER	Subprogram ID of the currently executing PL/SQL object; NULL if executing SQL. Maps to DBA_OBJECTS.DATA_OBJECT_ID.
PLSQL_CURRENT_ENTRY_OBJECT_ID	NUMBER	Object ID of the currently executing PL/SQL subprogram; NULL if executing SQL.
QC_INSTANCE_ID	NUMBER	Query coordinator instance ID. This information is only available if the sampled session is a parallel query worker. For all other sessions, the value is 0.
QC_SESSION_ID	NUMBER	Query coordinator session ID. This information is only available if the sampled session is a parallel query worker. For all other sessions, the value is 0.
QC_SESSION_SERIAL#	NUMBER	Query coordinator session serial number. This information is only available if the sampled session is a parallel query worker. For all other sessions, the value is 0.
PX_FLAGS	NUMBER	Reserved for internal use
EVENT	VARCHAR2(64)	If SESSION_STATE = WAITING, then the event for which the session was waiting for at the time of sampling. If SESSION_STATE = ON CPU, then this column is NULL. **See Also:** Oracle Wait Events
EVENT_ID	NUMBER	Identifier of the resource or event for which the session is waiting or for which the session last waited. Interpretation is similar to that of the EVENT column.

Column	Datatype	Description
EVENT#	NUMBER	Number of the resource or event for which the session is waiting or for which the session last waited. Interpretation is similar to that of the EVENT column.
SEQ#	NUMBER	Sequence number that uniquely identifies the wait (incremented for each wait)
P1TEXT	VARCHAR2(64)	Text of the first additional parameter
P1	NUMBER	First additional parameter
P2TEXT	VARCHAR2(64)	Text of the second additional parameter
P2	NUMBER	Second additional parameter
P3TEXT	VARCHAR2(64)	Text of the third additional parameter
P3	NUMBER	Third additional parameter
WAIT_CLASS	VARCHAR2(64)	Wait class name of the event for which the session was waiting at the time of sampling. Interpretation is similar to that of the EVENT column. Maps to V$SESSION.WAIT_CLASS.
WAIT_CLASS_ID	NUMBER	Wait class identifier of the event for which the session was waiting at the time of sampling. Interpretation is similar to that of the EVENT column. Maps to V$SESSION.WAIT_CLASS_ID.
WAIT_TIME	NUMBER	Total wait time for the event for which the session last waited if the session was on the CPU when sampled; 0 if the session was waiting at the time of sampling **Note:** Whether or not WAIT_TIME = 0 is what is useful to find the SESSION_STATE at the time of sampling, rather than the actual value of WAIT_TIME itself. Maps to V$SESSION.WAIT_TIME.
SESSION_STATE	VARCHAR2(7)	Session state: • WAITING • ON CPU
TIME_WAITED	NUMBER	If SESSION_STATE = WAITING, then the time that the session actually spent waiting for that event (in microseconds). This column is set for waits that were in progress at the time the sample was taken. If a wait event lasted for more than a second and was caught waiting in more than one session sample row, then the actual time spent waiting for that wait event will be populated in the last of those session sample rows. At any given time, this information will not be available for the latest session sample.
BLOCKING_SESSION_STATUS	VARCHAR2(11)	Status of the blocking session: • VALID • NO HOLDER • GLOBAL • NOT IN WAIT • UNKNOWN
BLOCKING_SESSION	NUMBER	Session identifier of the blocking session. Populated only if the blocker is on the same instance and the session was waiting for enqueues or a "buffer busy" wait. Maps to V$SESSION.BLOCKING_SESSION.
BLOCKING_SESSION_SERIAL#	NUMBER	Serial number of the blocking session
BLOCKING_INST_ID	NUMBER	Instance number of the blocker shown in BLOCKING_SESSION

Column	Datatype	Description
BLOCKING_HANGCHAIN_INFO	VARCHAR2(1)	Indicates whether the information about BLOCKING_SESSION comes from the hang chain (Y) or not (N)
CURRENT_OBJ#	NUMBER	Object ID of the object that the session is referencing. This information is only available if the session was waiting for application, cluster, concurrency, and user I/O wait events. Maps to V$SESSION.ROW_WAIT_OBJ#.
CURRENT_FILE#	NUMBER	File number of the file containing the block that the session is referencing. This information is only available if the session was waiting for cluster, concurrency, and user I/O wait events. Maps to V$SESSION.ROW_WAIT_FILE#.
CURRENT_BLOCK#	NUMBER	ID of the block that the session is referencing. This information is only available if the session was waiting for cluster, concurrency, and user I/O wait events. Maps to V$SESSION.ROW_WAIT_BLOCK#.
CURRENT_ROW#	NUMBER	Row identifier that the session is referencing. This information is only available if the session was waiting for cluster, concurrency, and user I/O wait events. Maps to V$SESSION.ROW_WAIT_ROW#.
TOP_LEVEL_CALL#	NUMBER	Oracle top level call number
TOP_LEVEL_CALL_NAME	VARCHAR2(64)	Oracle top level call name
CONSUMER_GROUP_ID	NUMBER	Consumer group ID
XID	RAW(8)	Transaction ID that the session was working on at the time of sampling. V$SESSION does not contain this information.
REMOTE_INSTANCE#	NUMBER	Remote instance identifier that will serve the block that this session is waiting for. This information is only available if the session was waiting for cluster events.
TIME_MODEL	NUMBER	Time model information
IN_CONNECTION_MGMT	VARCHAR2(1)	Indicates whether the session was doing connection management at the time of sampling (Y) or not (N)
IN_PARSE	VARCHAR2(1)	Indicates whether the session was parsing at the time of sampling (Y) or not (N)
IN_HARD_PARSE	VARCHAR2(1)	Indicates whether the session was hard parsing at the time of sampling (Y) or not (N)
IN_SQL_EXECUTION	VARCHAR2(1)	Indicates whether the session was executing SQL statements at the time of sampling (Y) or not (N)
IN_PLSQL_EXECUTION	VARCHAR2(1)	Indicates whether the session was executing PL/SQL at the time of sampling (Y) or not (N)
IN_PLSQL_RPC	VARCHAR2(1)	Indicates whether the session was executing inbound PL/SQL RPC calls at the time of sampling (Y) or not (N)
IN_PLSQL_COMPILATION	VARCHAR2(1)	Indicates whether the session was compiling PL/SQL at the time of sampling (Y) or not (N)
IN_JAVA_EXECUTION	VARCHAR2(1)	Indicates whether the session was executing Java at the time of sampling (Y) or not (N)
IN_BIND	VARCHAR2(1)	Indicates whether the session was doing bind operations at the time of sampling (Y) or not (N)
IN_CURSOR_CLOSE	VARCHAR2(1)	Indicates whether the session was closing a cursor at the time of sampling (Y) or not (N)
IN_SEQUENCE_LOAD	VARCHAR2(1)	Indicates whether the session is loading in sequence (in sequence load code) (Y) or not (N)

Column	Datatype	Description
IN_INMEMORY_QUERY	VARCHAR2(1)	Indicates whether the session was querying the In-Memory Column Store (IM column store) at the time of sampling (Y) or not (N)
IN_INMEMORY_POPULATE	VARCHAR2(1)	Indicates whether the session was populating the IM column store at the time of sampling (Y) or not (N)
IN_INMEMORY_PREPOPULATE	VARCHAR2(1)	Indicates whether the session was prepopulating the IM column store at the time of sampling (Y) or not (N)
IN_INMEMORY_REPOPULATE	VARCHAR2(1)	Indicates whether the session was repopulating the IM column store at the time of sampling (Y) or not (N)
IN_INMEMORY_TREPOPULATE	VARCHAR2(1)	Indicates whether the session was trickle repopulating the IM column store at the time of sampling (Y) or not (N)
IN_TABLESPACE_ENCRYPTION	VARCHAR2(1)	Indicates whether encryption or decryption of a tablespace occurred at the time of sampling (Y) or not (N)
CAPTURE_OVERHEAD	VARCHAR2(1)	Indicates whether the session is executing capture code (Y) or not (N)
REPLAY_OVERHEAD	VARCHAR2(1)	Indicates whether the session is executing replay code (Y) or not (N)
IS_CAPTURED	VARCHAR2(1)	Indicates whether the session is being captured (Y) or not (N)
IS_REPLAYED	VARCHAR2(1)	Indicates whether the session is being replayed (Y) or not (N)
IS_REPLAY_SYNC_TOKEN_HOLDER	VARCHAR2(1)	Indicates whether the session is holding a synchronization token (Y) or not (N) during workload replay
SERVICE_HASH	NUMBER	Hash that identifies the Service; maps to V$ACTIVE_SERVICES.NAME_HASH
PROGRAM	VARCHAR2(84)	Name of the operating system program
MODULE	VARCHAR2(64)	Name of the executing module when sampled, as set by the DBMS_APPLICATION_INFO.SET_MODULE procedure
ACTION	VARCHAR2(64)	Name of the executing module when sampled, as set by the DBMS_APPLICATION_INFO.SET_ACTION procedure
CLIENT_ID	VARCHAR2(64)	Client identifier of the session; maps to V$SESSION.CLIENT_IDENTIFIER
MACHINE	VARCHAR2(64)	Client's operating system machine name
PORT	NUMBER	Client port number
ECID	VARCHAR2(64)	Execution context identifier (sent by Application Server)
DBREPLAY_FILE_ID	NUMBER	If the session is being captured or replayed, then DBREPLAY_FILE_ID is the file ID for the workload capture or workload replay; otherwise it is NULL.
DBREPLAY_CALL_COUNTER	NUMBER	If the session is being captured or replayed, then DBREPLAY_CALL_COUNTER is the call counter of the user call that is being captured or replayed; otherwise it is NULL.
TM_DELTA_TIME	NUMBER	Time interval (in microseconds) over which TM_DELTA_CPU_TIME and TM_DELTA_DB_TIME are accumulated
TM_DELTA_CPU_TIME	NUMBER	Amount of time this session spent on CPU over the last TM_DELTA_TIME microseconds
TM_DELTA_DB_TIME	NUMBER	Amount of time spent by this session in database calls over the last TM_DELTA_TIME microseconds

Column	Datatype	Description
DELTA_TIME	NUMBER	Time interval (in microseconds) since the last time this session was sampled or created, over which the next five statistics are accumulated
DELTA_READ_IO_REQUESTS	NUMBER	Number of read I/O requests made by this session over the last DELTA_TIME microseconds
DELTA_WRITE_IO_REQUESTS	NUMBER	Number of write I/O requests made by this session over the last DELTA_TIME microseconds
DELTA_READ_IO_BYTES	NUMBER	Number of I/O bytes read by this session over the last DELTA_TIME microseconds
DELTA_WRITE_IO_BYTES	NUMBER	Number of I/O bytes written by this session over the last DELTA_TIME microseconds
DELTA_INTERCONNECT_IO_BYTES	NUMBER	Number of I/O bytes sent over the I/O interconnect over the last DELTA_TIME microseconds
DELTA_READ_MEM_BYTES	NUMBER	Number of read bytes through the buffer cache
PGA_ALLOCATED	NUMBER	Amount of PGA memory (in bytes) consumed by this session at the time this sample was taken
TEMP_SPACE_ALLOCATED	NUMBER	Amount of TEMP memory (in bytes) consumed by this session at the time this sample was taken
CON_DBID	NUMBER	The database ID of the pluggable database (PDB)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
DBOP_NAME	VARCHAR2(30)	Database operation name. If the type is SQL, the DBOP_NAME will be NULL.
DBOP_EXEC_ID	NUMBER	Database operation execution identifier for the current execution. If the type is SQL, the DBOP_EXEC_ID will be NULL.

8.14 V$ALL_SQL_BIND_CAPTURE

V$ALL_SQL_BIND_CAPTURE displays information on bind variables used by SQL cursors.

> **Note:**
>
> V$ALL_SQL_BIND_CAPTURE allows application developers to view information about their own bind variables used by SQL cursors. It is similar to the V$SQL_BIND_CAPTURE view, with the following exception:
>
> - When queried by the SYS user or anyone with the SYSDBA privilege, the V$ALL_SQL_BIND_CAPTURE view displays the same data as the V$SQL_BIND_CAPTURE view.
> - When queried by any other user, the V$ALL_SQL_BIND_CAPTURE view displays only data about bind variables used by the SQL cursors owned by that user.
>
> See also "V$SQL_BIND_CAPTURE"

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Address of the parent cursor
HASH_VALUE	NUMBER	Hash value of the parent cursor in the library cache. The hash value is a fixed index for the view and should always be used to speed up access to the view.
SQL_ID	VARCHAR2(13)	SQL identifier of the parent cursor in the library cache
CHILD_ADDRESS	RAW(4 | 8)	Address of the child cursor
CHILD_NUMBER	NUMBER	Child cursor number
NAME	VARCHAR2(128)	Name of the bind variable
POSITION	NUMBER	Position of the bind variable in the SQL statement
DUP_POSITION	NUMBER	If the binding is performed by name and the bind variable is duplicated, then this column gives the position of the primary bind variable.
DATATYPE	NUMBER	Internal identifier for the bind data type. Beginning in Oracle Database 12*c*, a number representing a PL/SQL data type can appear in this column.
DATATYPE_STRING	VARCHAR2(15)	Textual representation of the bind data type. Beginning in Oracle Database 12*c*, a text representation of a PL/SQL-only data type can appear in this column. If the actual data type is a PL/SQL sub type, the name of the data type, not the sub type will be displayed.
CHARACTER_SID	NUMBER	National character set identifier
PRECISION	NUMBER	Precision (for numeric binds)
SCALE	NUMBER	Scale (for numeric binds)
MAX_LENGTH	NUMBER	Maximum bind length
WAS_CAPTURED	VARCHAR2(3)	Indicates whether the bind value was captured (YES) or not (NO)
LAST_CAPTURED	DATE	Date when the bind value was captured. Bind values are captured when SQL statements are executed. To limit the overhead, binds are captured at most every 15 minutes for a given cursor.

Column	Datatype	Description
VALUE_STRING	VARCHAR2(4000)	Value of the bind represented as a string
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

8.15 V$ALL_SQL_MONITOR

V$ALL_SQL_MONITOR displays SQL statements whose execution have been (or are being) monitored by Oracle.

> **Note:**
>
> V$ALL_SQL_MONITOR allows application developers to view information about their own SQL statements. It is similar to the V$SQL_MONITOR view, with the following exception:
>
> - When queried by the SYS user or anyone with the SYSDBA privilege, the V$ALL_SQL_MONITOR view displays the same data as the V$SQL_MONITOR view.
> - When queried by any other user, the V$ALL_SQL_MONITOR view displays data only about SQL statements that were executed in sessions owned by that user.
>
> See also "V$SQL_MONITOR"

Column	Datatype	Description
KEY	NUMBER	Artificial join key to efficiently join V$ALL_SQL_MONITOR with its corresponding plan level monitoring statistics stored in V$ALL_SQL_PLAN_MONITOR
REPORT_ID	NUMBER	Unique ID of the XML report stored in Automatic Workload Repository (AWR) for this monitored entity

Column	Datatype	Description
STATUS	VARCHAR2(19)	SQL execution status: • QUEUED - SQL statement is queued • EXECUTING - SQL statement is still executing • DONE (ERROR) - Execution terminated with an error • DONE (FIRST N ROWS) - Execution terminated by the application before all rows were fetched • DONE (ALL ROWS) - Execution terminated and all rows were fetched • DONE - Execution terminated (parallel execution)
USER#	NUMBER	User ID of the database user who issued the SQL being monitored
USERNAME	VARCHAR2(128)	User name of the database user who issued the SQL being monitored
MODULE	VARCHAR2(64)	Name of the executing module when sampled, as set by the DBMS_APPLICATION_INFO.SET_MODULE procedure
ACTION	VARCHAR2(64)	Name of the executing action when sampled, as set by the DBMS_APPLICATION_INFO.SET_ACTION procedure
SERVICE_NAME	VARCHAR2(64)	Service name of the user session
CLIENT_IDENTIFIER	VARCHAR2(64)	Client identifier from the user session
CLIENT_INFO	VARCHAR2(64)	Client information for the user session
PROGRAM	VARCHAR2(84)	Name of the operating system program that issued the monitored SQL
PLSQL_ENTRY_OBJECT_ID	NUMBER	Object ID of the top-most PL/SQL subprogram on the stack; NULL if there is no PL/SQL subprogram on the stack
PLSQL_ENTRY_SUBPROGRAM_ID	NUMBER	Subprogram ID of the top-most PL/SQL subprogram on the stack; NULL if there is no PL/SQL subprogram on the stack
PLSQL_OBJECT_ID	NUMBER	Object ID of the currently executing PL/SQL subprogram; NULL if executing SQL
PLSQL_OWNER_ID	NUMBER	ID of the owner of the currently executing PL/SQL subprogram; NULL if executing SQL
PLSQL_SUBPROGRAM_ID	NUMBER	Subprogram ID of the currently executing PL/SQL object; NULL if executing SQL
FIRST_REFRESH_TIME	DATE	Time when monitoring of the SQL statement started, generally a few seconds after execution start time
LAST_REFRESH_TIME	DATE	Time when statistics in V$ALL_SQL_MONITOR were last updated for the SQL statement. Statistics are generally refreshed every second when the statement executes.
REFRESH_COUNT	NUMBER	Number of times V$ALL_SQL_MONITOR statistics have been refreshed (generally once every second when the SQL statement executes)
DBOP_EXEC_ID	NUMBER	Database operation execution identifier for the current execution. If the type is SQL, the DBOP_EXEC_ID will be NULL.
DBOP_NAME	VARCHAR2(30)	Database operation name. If the type is SQL, the DBOP_NAME will be NULL.
SID	NUMBER	Session identifier executing (or having executed) the SQL statement being monitored

Column	Datatype	Description
PROCESS_NAME	VARCHAR2(5)	Process name identifier executing (or having executed)the statement; ora if the process is foreground, else the background process name (for example, p001 for PX server p001)
SQL_ID	VARCHAR2(13)	SQL identifier of the statement being monitored
SQL_TEXT	VARCHAR2(2000)	Up to the first 2000 characters of the text of the SQL being monitored
IS_FULL_SQLTEXT	VARCHAR2(1)	Indicates whether the SQL_TEXT column has the entire SQL text (Y) or not (N)
SQL_EXEC_START	DATE	Time when the execution started
SQL_EXEC_ID	NUMBER	Execution identifier. Together, the three columns SQL_ID, SQL_EXEC_START, and SQL_EXEC_ID represent the execution key. The execution key is used to uniquely identify one execution of the SQL statement.
SQL_PLAN_HASH_VALUE	NUMBER	SQL plan hash value
SQL_FULL_PLAN_HASH_VALUE	NUMBER	Numeric representation of the complete SQL plan for this cursor. Comparing one SQL_FULL_PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line). Note that the SQL_FULL_PLAN_HASH_VALUE cannot be compared across databases releases. It is not backward compatible.
EXACT_MATCHING_SIGNATURE	NUMBER	Signature calculated on the normalized SQL text. The normalization includes the removal of white space and the uppercasing of all non-literal strings.
FORCE_MATCHING_SIGNATURE	NUMBER	Same as EXACT_MATCHING_SIGNATURE but literals in the SQL text are replaced by binds
SQL_CHILD_ADDRESS	RAW(8)	Address of the child cursor (can be used with SQL_ID to join with V$SQL)
SESSION_SERIAL#	NUMBER	Session serial number executing the statement being monitored
PX_IS_CROSS_INSTANCE	VARCHAR2(1)	Indicates whether the SQL statement ran parallel across multiple instances (Y) or not (N)
PX_MAXDOP	NUMBER	Maximum degree of parallelism for any plan operation executed on behalf of the monitored SQL
PX_MAXDOP_INSTANCES	NUMBER	Number of database instances touched at the maximum degree of parallelism
PX_SERVERS_REQUESTED	NUMBER	Total number of parallel execution servers requested to execute the monitored SQL
PX_SERVERS_ALLOCATED	NUMBER	Actual number of parallel execution servers allocated to execute the query
PX_SERVER#	NUMBER	Logical parallel execution server process number executing (or having executed) the statement being monitored; NULL if this monitoring entry is not associated with an execution server. This is a logical number within the parallel server set (see SERVER# in V$PX_SESSION).
PX_SERVER_GROUP	NUMBER	Logical parallel execution server group number to which PX_SERVER# belongs (see SERVER_GROUP in V$PX_SESSION); NULL if this monitoring entry is not associated with a parallel execution server. This value is generally 1 unless the SQL statement has one or more parallel sub-queries.

Column	Datatype	Description
PX_SERVER_SET	NUMBER	Number (1 or 2) of the logical set of parallel execution servers to which PX_SERVER# belongs (see SERVER_SET in V$PX_SESSION); NULL if this monitoring entry is not associated with a parallel execution server
PX_QCINST_ID	NUMBER	Instance identifier where the parallel execution coordinator runs; NULL if PX_SERVER# is NULL
PX_QCSID	NUMBER	Session identifier for the parallel execution coordinator; NULL if PX_SERVER# is NULL
ERROR_NUMBER	VARCHAR2(40)	Error number encountered in case a SQL fails to execute successfully (for example, 932 in case of ORA-00932)
ERROR_FACILITY	VARCHAR2(4)	Error facility in case a SQL fails to execute successfully (for example, ORA in case of ORA-00932)
ERROR_MESSAGE	VARCHAR2(256)	Detailed error message displayed corresponding to the error number and error facility when a SQL fails to execute successfully
BINDS_XML	CLOB	Information about bind variables used with the SQL, such as name, position, value, data type, and so on (stored in XML format)
OTHER_XML	CLOB	Additional information about SQL execution stored in XML format
ELAPSED_TIME	NUMBER	Elapsed time (in microseconds); updated as the statement executes
QUEUING_TIME	NUMBER	Duration of time (in microseconds) spent by SQL in the statement queue
CPU_TIME	NUMBER	CPU time (in microseconds); updated as the statement executes
FETCHES	NUMBER	Number of fetches associated with the SQL statement; updated as the statement executes
BUFFER_GETS	NUMBER	Number of buffer get operations; updated as the statement executes
DISK_READS	NUMBER	Number of disk reads; updated as the statement executes
DIRECT_WRITES	NUMBER	Number of direct writes; updated as the statement executes
IO_INTERCONNECT_BYTES	NUMBER	Number of I/O bytes exchanged between Oracle Database and the storage system
PHYSICAL_READ_REQUESTS	NUMBER	Number of physical read I/O requests issued by the monitored SQL
PHYSICAL_READ_BYTES	NUMBER	Number of bytes read from disks by the monitored SQL
PHYSICAL_WRITE_REQUESTS	NUMBER	Number of physical write I/O requests issued by the monitored SQL
PHYSICAL_WRITE_BYTES	NUMBER	Number of bytes written to disks by the monitored SQL
APPLICATION_WAIT_TIME	NUMBER	Application wait time (in microseconds); updated as the statement executes
CONCURRENCY_WAIT_TIME	NUMBER	Concurrency wait time (in microseconds); updated as the statement executes
CLUSTER_WAIT_TIME	NUMBER	Cluster wait time (in microseconds); updated as the statement executes
USER_IO_WAIT_TIME	NUMBER	User I/O Wait Time (in microseconds); updated as the statement executes
PLSQL_EXEC_TIME	NUMBER	PL/SQL execution time (in microseconds); updated as the statement executes

Column	Datatype	Description
JAVA_EXEC_TIME	NUMBER	Java execution time (in microseconds); updated as the statement executes
RM_LAST_ACTION	VARCHAR2(48)	The most recent action that was taken on this SQL operation by Resource Manager. Its value is one of the following: • CANCEL_SQL • KILL_SESSION • LOG_ONLY • SWITCH TO <CG NAME> For the last value, <CG NAME> is the name of the consumer group that the SQL operation was switched to. If the Resource Plan has since been changed then <CG NAME> is the ID of the consumer group.
RM_LAST_ACTION_REASON	VARCHAR2(128)	The reason for the most recent action that was taken on this SQL operation by Resource Manager. Its value is one of the following: • SWITCH_CPU_TIME • SWITCH_IO_REQS • SWITCH_IO_MBS • SWITCH_ELAPSED_TIME • SWITCH_IO_LOGICAL
RM_LAST_ACTION_TIME	DATE	The time of the most recent action that was taken on this SQL operation by Resource Manager
RM_CONSUMER_GROUP	VARCHAR2(128)	The current consumer group for this SQL operation
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
CON_NAME	VARCHAR2(128)	Container name of the object. The value of this column is NULL in non-CDBs.
ECID	VARCHAR2(64)	Execution context identifier (sent by Application Server)
IS_ADAPTIVE_PLAN	VARCHAR2(1)	Indicates whether the statistics are from an adaptive plan (Y) or not (N).
IS_FINAL_PLAN	VARCHAR2(1)	Indicates whether the statistics are from the final plan (Y) or not (N).
IN_DBOP_NAME	VARCHAR2(30)	If the SQL that is monitored was executed by a session that was also monitored by a database operation (DBOP), then this column specifies the name of that DBOP
IN_DBOP_EXEC_ID	NUMBER	If the SQL that is monitored was executed by a session that was also monitored by a database operation (DBOP), then this column specifies the execution ID of that DBO
IO_CELL_UNCOMPRESSED_BYTES	NUMBER	Number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells **See Also:** Oracle Exadata Storage Server Software documentation for more information

Column	Datatype	Description
IO_CELL_OFFLOAD_ELIGIBLE_BYTES	NUMBER	Number of I/O bytes which can be filtered by the Exadata storage system **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_CELL_OFFLOAD_RETURNED_BYTES	NUMBER	Number of filtered bytes returned by Exadata cells (that is, the number of bytes returned after processing has been offloaded on the Exadata cells) **See Also:** Oracle Exadata Storage Server Software documentation for more information
CURRENT_USER#	NUMBER	Unique number identifying the current user
CURRENT_USERNAME	VARCHAR2(128)	Username for the current user
PDB_REPORT_ID	NUMBER	Unique ID of the XML report of a PDB monitored entity that is stored in the CDB's Automatic Workload Repository (AWR) tables

8.16 V$ALL_SQL_PLAN_MONITOR

V$ALL_SQL_PLAN_MONITOR displays plan level monitoring statistics for each SQL statement found in V$ALL_SQL_MONITOR.

> **Note:**
>
> V$ALL_SQL_PLAN_MONITOR allows application developers to view statistics about their own SQL statements. It is similar to the V$SQL_PLAN_MONITOR view, with the following exception:
>
> - When queried by the SYS user or anyone with the SYSDBA privilege, the V$ALL_SQL_PLAN_MONITOR view displays the same data as the V$SQL_PLAN_MONITOR view.
> - When queried by any other user, the V$ALL_SQL_PLAN_MONITOR view displays data only about SQL statements that were executed in sessions owned by that user.
>
> See also "V$SQL_PLAN_MONITOR"

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
KEY	NUMBER	Foreign key to efficiently join V$ALL_SQL_PLAN_MONITOR with V$ALL_SQL_MONITOR (see V$ALL_SQL_MONITOR)

Column	Datatype	Description
STATUS	VARCHAR2(19)	SQL execution status: • EXECUTING - SQL statement is still executing • DONE (ERROR) - Execution terminated with an error • DONE (FIRST N ROWS) - Execution terminated by the application before all rows were fetched • DONE (ALL ROWS) - Execution terminated and all rows were fetched • DONE - Execution terminated (parallel execution)
FIRST_REFRESH_TIME	DATE	Time when monitoring of the SQL statement started
LAST_REFRESH_TIME	DATE	Time when statistics were last updated for the SQL statement
FIRST_CHANGE_TIME	DATE	First time a row was produced by this operation
LAST_CHANGE_TIME	DATE	Last time a row was produced by this operation
REFRESH_COUNT	NUMBER	Number of times statistics have been refreshed
SID	NUMBER	Session identifier executing (or having executed) the SQL statement being monitored
PROCESS_NAME	VARCHAR2(5)	Process name identifier
SQL_ID	VARCHAR2(13)	SQL identifier
SQL_EXEC_START	DATE	Time when the execution started
SQL_EXEC_ID	NUMBER	Execution identifier
SQL_PLAN_HASH_VALUE	NUMBER	SQL plan hash value
SQL_CHILD_ADDRESS	RAW(8)	Address of the child cursor
PLAN_PARENT_ID	NUMBER	ID of the next execution step that operates on the output of the current step
PLAN_LINE_ID	NUMBER	Plan line number for the entry
PLAN_OPERATION	VARCHAR2(30)	Plan operation name (from V$SQL_PLAN)
PLAN_OPTIONS	VARCHAR2(30)	Plan option name (from V$SQL_PLAN)
PLAN_OBJECT_OWNER	VARCHAR2(128)	Name of the user who owns the schema containing the table or index
PLAN_OBJECT_NAME	VARCHAR2(128)	Name of the table or index
PLAN_OBJECT_TYPE	VARCHAR2(20)	Type of the object
PLAN_DEPTH	NUMBER	Depth (or level) of the operation in the tree. It is not necessary to issue a CONNECT BY statement to get the level information, which is generally used to indent the rows from the PLAN_TABLE table. The root operation (statement) is level 0.
PLAN_POSITION	NUMBER	Order of processing for all operations that have the same PARENT_ID
PLAN_COST	NUMBER	Cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
PLAN_CARDINALITY	NUMBER	Estimate, by the cost-based optimizer, of the number of rows produced by the operation
PLAN_BYTES	NUMBER	Estimate, by the cost-based optimizer, of the number of bytes produced by the operation

Column	Datatype	Description
PLAN_TIME	NUMBER	Elapsed time (in seconds) of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
PLAN_PARTITION_START	VARCHAR2(64)	Start partition of a range of accessed partitions
PLAN_PARTITION_STOP	VARCHAR2(64)	Stop partition of a range of accessed partitions
PLAN_CPU_COST	NUMBER	CPU cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
PLAN_IO_COST	NUMBER	I/O cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
PLAN_TEMP_SPACE	NUMBER	Temporary space usage of the operation (sort or hash-join) as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
STARTS	NUMBER	Number of times this operation was executed. For example, an operation is executed multiple times when it is on the right side of a nested-loop join (once for each row of the left input of that nested-loop join).
OUTPUT_ROWS	NUMBER	Number of rows produced by this operation since the execution started. This number is cumulated for all executions of this operation. Divide by the value of the STARTS column to compute the average number of rows per execution of the operation. Note that the value in the STARTS column is equal to or higher than the value in the OUTPUT_ROWS column. The value will usually be equal, but depending on internal optimizations a higher value may be seen.
IO_INTERCONNECT_BYTES	NUMBER	Number of I/O bytes exchanged between Oracle Database and the storage system. Maintained only after Oracle starts to monitor the execution.
PHYSICAL_READ_REQUESTS	NUMBER	Number of physical read I/O requests issued by the monitored SQL. Maintained only after Oracle starts to monitor the execution.
PHYSICAL_READ_BYTES	NUMBER	Number of bytes read from disks by the monitored SQL. Maintained only after Oracle starts to monitor the execution.
PHYSICAL_WRITE_REQUESTS	NUMBER	Number of physical write I/O requests issued by the monitored SQL. Maintained only after Oracle starts to monitor the execution.
PHYSICAL_WRITE_BYTES	NUMBER	Number of bytes written to disks by the monitored SQL. Maintained only after Oracle starts to monitor the execution.
WORKAREA_MEM	NUMBER	Amount of memory (in bytes) used by the operation when the query is executing; NULL if the execution is done. This applies only to operations using a work area, such as sort, hash-join, group-by, and so on.
WORKAREA_MAX_MEM	NUMBER	Maximum value (in bytes) for WORKAREA_MEM; NULL if the operation is not using a work area. When the execution is finished, this value will hold the maximum amount of memory consumed by this operation during the execution of the statement.
WORKAREA_TEMPSEG	NUMBER	Amount of temporary space (in bytes) used by the operation when the query is executing; NULL if the operation has not spilled to disk or if the execution is finished

Column	Datatype	Description
WORKAREA_MAX_TEMPSEG	NUMBER	Maximum value (in bytes) for WORKAREA_TEMPSEG; NULL if this operation never spilled to disk. When the execution is done, this value will hold the maximum amount of temporary space consumed by this operation during the entire execution.
OTHERSTAT_GROUP_ID	NUMBER	Plan line statistic group identifier (see GROUP_ID column in V$SQL_MONITOR_STATNAME)
OTHERSTAT_1_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 1 of that plan line
OTHERSTAT_1_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_1_VALUE	NUMBER	Value of statistic number 1 of that plan line
OTHERSTAT_2_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 2 of that plan line
OTHERSTAT_2_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_2_VALUE	NUMBER	Value of statistic number 2 of that plan line
OTHERSTAT_3_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 3 of that plan line
OTHERSTAT_3_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_3_VALUE	NUMBER	Value of statistic number 3 of that plan line
OTHERSTAT_4_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 4 of that plan line
OTHERSTAT_4_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_4_VALUE	NUMBER	Value of statistic number 4 of that plan line
OTHERSTAT_5_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 5 of that plan line
OTHERSTAT_5_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_5_VALUE	NUMBER	Value of statistic number 5 of that plan line
OTHERSTAT_6_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 6 of that plan line
OTHERSTAT_6_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_6_VALUE	NUMBER	Value of statistic number 6 of that plan line
OTHERSTAT_7_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 7 of that plan line
OTHERSTAT_7_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_7_VALUE	NUMBER	Value of statistic number 7 of that plan line
OTHERSTAT_8_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 8 of that plan line
OTHERSTAT_8_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_8_VALUE	NUMBER	Value of statistic number 8 of that plan line
OTHERSTAT_9_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 9 of that plan line
OTHERSTAT_9_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_9_VALUE	NUMBER	Value of statistic number 9 of that plan line

Column	Datatype	Description
OTHERSTAT_10_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 10 of that plan line
OTHERSTAT_10_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_10_VALUE	NUMBER	Value of statistic number 10 of that plan line
OTHERSTAT_11_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 11 of that plan line
OTHERSTAT_11_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_11_VALUE	NUMBER	Value of statistic number 11 of that plan line
OTHERSTAT_12_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 12 of that plan line
OTHERSTAT_12_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_12_VALUE	NUMBER	Value of statistic number 12 of that plan line
OTHERSTAT_13_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 13 of that plan line
OTHERSTAT_13_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_13_VALUE	NUMBER	Value of statistic number 13 of that plan line
OTHERSTAT_14_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 14 of that plan line
OTHERSTAT_14_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_14_VALUE	NUMBER	Value of statistic number 14 of that plan line
OTHERSTAT_15_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 15 of that plan line
OTHERSTAT_15_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_15_VALUE	NUMBER	Value of statistic number 15 of that plan line
OTHERSTAT_16_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 16 of that plan line
OTHERSTAT_16_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_16_VALUE	NUMBER	Value of statistic number 16 of that plan line
OTHERSTAT_17_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 17 of that plan line
OTHERSTAT_17_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_17_VALUE	NUMBER	Value of statistic number 17 of that plan line
OTHERSTAT_18_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 18 of that plan line
OTHERSTAT_18_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_18_VALUE	NUMBER	Value of statistic number 18 of that plan line
OTHERSTAT_19_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 19 of that plan line
OTHERSTAT_19_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_19_VALUE	NUMBER	Value of statistic number 19 of that plan line
OTHERSTAT_20_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 20 of that plan line
OTHERSTAT_20_TYPE	NUMBER	Reserved for internal use

Column	Datatype	Description
OTHERSTAT_20_VALUE	NUMBER	Value of statistic number 20 of that plan line
OTHERSTAT_21_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 21 of that plan line
OTHERSTAT_21_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_21_VALUE	NUMBER	Value of statistic number 21 of that plan line
OTHERSTAT_22_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 22 of that plan line
OTHERSTAT_22_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_22_VALUE	NUMBER	Value of statistic number 22 of that plan line
OTHERSTAT_23_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 23 of that plan line
OTHERSTAT_23_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_23_VALUE	NUMBER	Value of statistic number 23 of that plan line
OTHERSTAT_24_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 24 of that plan line
OTHERSTAT_24_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_24_VALUE	NUMBER	Value of statistic number 24 of that plan line
OTHERSTAT_25_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 25 of that plan line
OTHERSTAT_25_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_25_VALUE	NUMBER	Value of statistic number 25 of that plan line
OTHERSTAT_26_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 26 of that plan line
OTHERSTAT_26_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_26_VALUE	NUMBER	Value of statistic number 26 of that plan line
OTHERSTAT_27_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 27 of that plan line
OTHERSTAT_27_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_27_VALUE	NUMBER	Value of statistic number 27 of that plan line
OTHERSTAT_28_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 28 of that plan line
OTHERSTAT_28_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_28_VALUE	NUMBER	Value of statistic number 28 of that plan line
OTHERSTAT_29_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 29 of that plan line
OTHERSTAT_29_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_29_VALUE	NUMBER	Value of statistic number 29 of that plan line
OTHERSTAT_30_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 30 of that plan line
OTHERSTAT_30_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_30_VALUE	NUMBER	Value of statistic number 30 of that plan line

Column	Datatype	Description
OTHER_XML	CLOB	Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML because it allows multiple pieces of information to be stored, including the following: • Name of the schema against which the query was parsed • Release number of the Oracle Database that produced the explain plan • Hash value associated with the execution plan • Name (if any) of the outline or the SQL profile used to build the execution plan • Indication of whether or not dynamic statistics were used to produce the plan • The outline data, a set of optimizer hints that can be used to regenerate the same plan
PLAN_OPERATION_INACTIVE	NUMBER	Indicates whether this plan operation was part of the final resolved plan

8.17 V$AQ

V$AQ displays statistics for the queues in the database.

Column	Datatype	Description
QID	NUMBER	Unique queue identifier
WAITING	NUMBER	Number of messages in the queue in the state 'WAITING'
READY	NUMBER	Number of messages in the queue in the state 'READY'
EXPIRED	NUMBER	Number of messages in the queue the state 'EXPIRED'
AVERAGE_MSG_AGE	NUMBER	Average age of the messages in the queue'
TOTAL_WAIT	NUMBER	Total wait time of all 'READY' messages in the queue
AVERAGE_WAIT	NUMBER	Average wait time of 'READY' messages in the queue
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database Advanced Queuing User's Guide for more information about Oracle Database Advanced Queueing

8.18 V$AQ_BACKGROUND_COORDINATOR

V$AQ_BACKGROUND_COORDINATOR lists performance statistics for the Oracle Database Advanced Queueing primary background coordinator process (AQPC).

Column	Datatype	Description
PROCESS_ID	VARCHAR2(24)	Operating system process ID of the primary
PROCESS_NAME	VARCHAR2(48)	Operating system name of the primary
NUM_JOBS	NUMBER	Number of jobs started
JOB_LATENCY	NUMBER	Job start latency
NUM_COORDINATORS	NUMBER	Number of primaries started
CON_ID	NUMBER	The ID of the container to which the data pertains. The CON_ID value in this view is always 0. The rows pertain to the entire CDB or to the non-CDB.

See Also:

Oracle Database Advanced Queuing User's Guide for more information about Oracle Database Advanced Queueing

8.19 V$AQ_BMAP_NONDUR_SUBSCRIBERS

V$AQ_BMAP_NONDUR_SUBSCRIBERS can be used to get the available bit positions. The view is queried to get the free bit position during creation of a non-durable subscriber.

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue ID
USED_POS	RAW(128)	Stream of bits to identify used and available bit positions
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database Advanced Queuing User's Guide for more information about Oracle Database Advanced Queueing

8.20 V$AQ_CROSS_INSTANCE_JOBS

V$AQ_CROSS_INSTANCE_JOBS describes each of the cross process jobs.

Each job serves to forward messages for a shard from a source instance to a destination instance for a set of subscribers of a sharded queue.

> **Note:**
>
> AQ sharded queues are deprecated in Oracle Database 21c. Oracle recommends that you instead use Transactional Event Queues (TxEventQs) for higher throughput and better performance.

Column	Datatype	Description
JOB_ID	NUMBER	Job ID within this coordinator
SCHEMA_NAME	VARCHAR2(128)	Source schema of the job
QUEUE_NAME	VARCHAR2(128)	Source queue name of the cross job
SHARD_ID	NUMBER	Source shard ID
START_SUBSHARD_ID	NUMBER	Start subshard ID of the job
DESTINATION_INSTANCE_ID	NUMBER	Destination instance of the cross job
COORDINATOR_ID	NUMBER	Index of the coordinator serving the job
DEST_SERVER_PROCESS_ID	NUMBER	Process ID of the destination server
JOB_STATE	VARCHAR2(28)	State of the job: • REQUESTED • RUNNING • STOPPED • PAUSED • CRASHED • INACTIVE
FLOW_CONTROL	NUMBER	Indicates whether the job is flow controlled: • 0 - The job is not flow controlled • 1 - The job is flow controlled
MSGS_SENT	NUMBER	Messages sent during the job
BYTES_SENT	NUMBER	Bytes sent during the job
ACK_LATENCY	NUMBER	Latency for receiving ACK for the job

Column	Datatype	Description
JOB_TYPE	VARCHAR2(26)	Cross instance job type. Values: • CROSS_STREAM : This job type is responsible for forwarding a shard from its owner instance to a destination dequeue instance for all subscribers performing dequeue from that shard at the destination dequeue instance. • DEQUEUE_AFFINITY_TO_REMOTE: This job type is responsible for switching a subscriber's dequeue affinity from a shard's owner instance to a remote dequeue instance. • DEQUEUE_AFFINITY_TO_LOCAL: This job type is responsible for switching back a subscriber's dequeue affinity from a remote dequeue instance to a shard's owner instance.
PRIORITY0_CROSS_LWM	NUMBER	Last priority 0 subshard received at DESTINATION_INSTANCE_ID
PRIORITY1_CROSS_LWM	NUMBER	Last priority 1 subshard received at DESTINATION_INSTANCE_ID
PRIORITY2_CROSS_LWM	NUMBER	Last priority 2 subshard received at DESTINATION_INSTANCE_ID
PRIORITY3_CROSS_LWM	NUMBER	Last priority 3 subshard received at DESTINATION_INSTANCE_ID
PRIORITY4_CROSS_LWM	NUMBER	Last priority 4 subshard received at DESTINATION_INSTANCE_ID
PRIORITY5_CROSS_LWM	NUMBER	Last priority 5 subshard received at DESTINATION_INSTANCE_ID
PRIORITY6_CROSS_LWM	NUMBER	Last priority 6 subshard received at DESTINATION_INSTANCE_ID
PRIORITY7_CROSS_LWM	NUMBER	Last priority 7 subshard received at DESTINATION_INSTANCE_ID
PRIORITY8_CROSS_LWM	NUMBER	Last priority 8 subshard received at DESTINATION_INSTANCE_ID
PRIORITY9_CROSS_LWM	NUMBER	Last priority 9 subshard received at DESTINATION_INSTANCE_ID
JOB_START_TIME	TIMESTAMP(3) WITH TIME ZONE	Start time of this job
SUBSCRIBER_ID	NUMBER	Subscriber ID whose affinity is being switched for the DEQUEUE_AFFINITY_TO_REMOTE and DEQUEUE_AFFINITY_TO_LOCAL job types
SUBSCRIBER_NAME	VARCHAR2(512)	Subscriber name whose affinity is being switched for the DEQUEUE_AFFINITY_TO_REMOTE and DEQUEUE_AFFINITY_TO_LOCAL job types. This column is NULL for the CROSS_STREAM job type.
OWNER_INSTANCE_ID	NUMBER	Owner instance of the shard
QUEUE_ID	NUMBER	Queue ID
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database Advanced Queuing User's Guide for more information about Oracle Database Advanced Queueing

8.21 V$AQ_IPC_ACTIVE_MSGS

V$AQ_IPC_ACTIVE_MSGS displays the information related to active IPC messages being processed by AQ background processes.

Column	Datatype	Description
PROCESS_NAME	VARCHAR2(48)	Worker process name
PROCESS_ID	NUMBER	Oracle process ID for this worker
SLAVE_STATE	NUMBER	Worker status: • 3: Picked task • 4: Running • 7: Idle
SLAVEOBJ_STATE	NUMBER	Worker object status: • 0: Invalid • 1: Valid
SEQUENCE_NUMBER	NUMBER	Message sequence number
MSG_CLASS_NAME	VARCHAR2(30)	Message class name
MSG_FLAGS	NUMBER	Message flags: • 1: This message needs ack • 2: Short • 4: Long • 8: Priority • 10: Special ack
MSG_SUBMT_TIME	NUMBER	Time this message was added into the IPC primary's list (in seconds)
MSG_PICKD_TIME	NUMBER	Time this message was picked by worker or primary for processing (in seconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.22 V$AQ_IPC_MSG_STATS

V$AQ_IPC_MSG_STATS displays the statistics of each IPC message class, such as the total number of invocations of a message class, total pending message/processed message count, and last failure related data. Information like total processed message count, average pending time/average processing time gives a real-time outline of AQ IPC background state.

Column	Datatype	Description
MSG_CLASS_NAME	VARCHAR2(30)	Message class name

Column	Datatype	Description
TOTAL_MSG_CALLS	NUMBER	Total number of calls for this message class
TOTAL_ACTIVE_MSGS	NUMBER	Total number of active messages presently processed by workers and primary
TOTAL_PENDING_MSGS	NUMBER	Total number of pending messages in the primary's local context
TOTAL_PROCESSED_MSGS	NUMBER	Total number of processed messages
LAST_RECEIVED_TIME	TIMESTAMP(3) WITH TIME ZONE	Time when the last message of this type was received in the primary's context list
LAST_PROCESS_TIME	TIMESTAMP(3) WITH TIME ZONE	Time when the last message was picked for processing
LAST_DONE_TIME	TIMESTAMP(3) WITH TIME ZONE	Time when the last message was done processing
AVERAGE_PENDING_TIME	NUMBER	Average pending time for this message class (in seconds)
AVERAGE_PROCESSING_TIME	NUMBER	Average processing time for this message class (in seconds)
LAST_FAILURE_TIME	TIMESTAMP(3) WITH TIME ZONE	Time of the last failure for this message class
LAST_ERROR_MSG	VARCHAR2(512)	Last error message for this message class
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.23 V$AQ_IPC_PENDING_MSGS

V$AQ_IPC_PENDING_MSGS displays information about pending messages, present in the local primary context.

Column	Datatype	Description
SEQUENCE_NUMBER	NUMBER	Message sequence number
MSG_CLASS_NAME	VARCHAR2(30)	Message class name
MSG_FLAGS	NUMBER	Message flags: • 1: This message needs ack • 2: Short • 4: Long • 8: Priority • 10: Special ack
MSG_SUBMT_TIME	NUMBER	Time this message was added into the IPC primary's list (in seconds)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.24 V$AQ_JOB_COORDINATOR

V$AQ_JOB_COORDINATOR lists performance statistics per coordinator, for every AQ coordinator controlled by the Oracle Database Advanced Queueing primary coordinator.

Column	Datatype	Description
COORDINATOR_ID	NUMBER	ID of the coordinator
PROCESS_ID	VARCHAR2(24)	Operating system process ID of the coordinator
PROCESS_NAME	VARCHAR2(48)	Operating system process name of the coordinator
JOB_NAME	VARCHAR2(32)	Name of the job handled
JOB_TYPE	NUMBER	Type of job handled
SERVER_COUNT	NUMBER	Number of servers active
MAX_SERVER_COUNT	NUMBER	Maximum server fanout achieved
CON_ID	NUMBER	The ID of the container to which the data pertains. The CON_ID value in this view is always 0. The rows pertain to the entire CDB or to the non-CDB.

See Also:

Oracle Database Advanced Queuing User's Guide for more information about Oracle Database Advanced Queueing

8.25 V$AQ_MESSAGE_CACHE

V$AQ_MESSAGE_CACHE provides performance statistics of the message cache for sharded queues at the subshard level in the instance.

Note:

AQ sharded queues are deprecated in Oracle Database 21c. Oracle recommends that you instead use Transactional Event Queues (TxEventQs) for higher throughput and better performance.

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue ID
SHARD_ID	NUMBER	Shard ID
PRIORITY	NUMBER	Priority of the subshard for dequeue, range 0-9
SUBSHARD_ID	NUMBER	Subshard ID in the shard
PARTITION_ID	NUMBER	Partition id for the particular subshard
MAX_MSGS	NUMBER	Maximum number of messages of subshard
ENQUEUED_MSGS	NUMBER	Number of messages enqueued for the subshard
MSGS_MADE_EXPIRED	NUMBER	Number of messages made expired
CHUNK_SIZE	NUMBER	The size of the memory chunk for storing messages
NUM_CHUNKS	NUMBER	Number of chunks for the subshard
NUM_FREE_CHUNKS	NUMBER	Number of free chunks for the subshard
USED_MEMORY_SIZE	NUMBER	Total estimated size of memory in use (in bytes) for the subshard
STATE	VARCHAR2(13)	Subshard state. Possible values: • CACHED (in memory) • UNCACHED (on disk) • UNCACHED_FREE • CACHED_FREE • UNKNOWN
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database Advanced Queuing User's Guide for more information about Oracle Database Advanced Queueing

8.26 V$AQ_MESSAGE_CACHE_ADVICE

V$AQ_MESSAGE_CACHE_ADVICE shows simulated metrics for a range of potential message cache sizes. This view assists in cache sizing by providing information in the form of metrics as described below.

> **Note:**
>
> AQ sharded queues are deprecated in Oracle Database 21c. Oracle recommends that you instead use Transactional Event Queues (TxEventQs) for higher throughput and better performance.

Column	Datatype	Description
SIZE_FOR_ESTIMATE	NUMBER	Cache size for simulation (in megabytes)
SIZE_FACTOR	NUMBER	Size factor with respect to the current cache size
ESTD_SIZE_TYPE	VARCHAR2(9)	Possible values: • MINIMUM: This cache size is required to have all dequeues in-memory (no uncached). • PREFERRED: This is the smallest message cache size required to eliminate 80% of unevictions that occur with a message cache size of MINIMUM for subscribers who keep up, that is, subscribers whose dequeue rate matches the enqueue rate. • MAXIMUM: This cache size is required to have zero evictions. • NULL: This is the value in all other cases.
ESTD_CACHED_SUBSHARDS	NUMBER	Estimated number of cached subshards for this size
ESTD_UNCACHED_SUBSHARDS	NUMBER	Estimated number of uncached subshards for this size
ESTD_EVICTIONS	NUMBER	Estimated number of subshards evicted for this size
ESTD_EVICTION_RATE	NUMBER	Estimated number of subshards getting evicted per minute
ESTD_FG_UNEVICTIONS	NUMBER	Estimated number of subshards unevicted by foreground processes
ESTD_FG_UNEVICTION_RATE	NUMBER	Estimated number of subshards getting unevicted by foreground processes
ESTD_BG_UNEVICTIONS	NUMBER	Estimated number of subshards unevicted by background processes
ESTD_BG_UNEVICTION_RATE	NUMBER	Estimated number of subshards getting unevicted by background processes
ESTD_BG_PROCESSES	NUMBER	Estimated number of background processes required for this size
TOTAL_ENQUEUE_RATE	NUMBER	Simulated number of messages being enqueued per second
TOTAL_DEQUEUE_RATE	NUMBER	Simulated number of messages being dequeued per second
AVG_SUBSHARD_SIZE	NUMBER	Simulated average number of messages per cached subshard
AVG_SUBSHARD_MEMORY	NUMBER	Simulated average memory per cached subshard (in megabytes)
AVG_EVICTION_TIME	NUMBER	Simulated average time to evict a cached subshard (in milliseconds)
AVG_UNEVICTION_TIME	NUMBER	Simulated average time to unevict a cached subshard (in milliseconds)

Column	Datatype	Description
FLAGS	NUMBER	Reserved for internal use
SIMULATION_TIME	NUMBER	Amount of time that was simulated for (in minutes)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.27 V$AQ_MESSAGE_CACHE_STAT

V$AQ_MESSAGE_CACHE_STAT displays statistics about memory management for sharded queues in the Streams pool within the System Global Area (SGA). Sharded queues use the Streams pool in units of subshards. Thus, columns of this view shows statistics at subshard level. This view shows statistics across all sharded queues.

> **Note:**
>
> AQ sharded queues are deprecated in Oracle Database 21c. Oracle recommends that you instead use Transactional Event Queues (TxEventQs) for higher throughput and better performance.

Column	Datatype	Description
NUM_EVICTED	NUMBER	Number of evicted subshards across all sharded queues
NUM_PREFETCHED	NUMBER	Number of subshards pre-fetched by AQ background process
NUM_UNEVICTION	NUMBER	Number of subshards un-evicted by foreground process (like dequeue process)
NUM_UNCACHED	NUMBER	Number of subshards stored as uncached
NUM_TRACKED	NUMBER	Number of subshards which are actively tracking dequeue rates
NUM_CACHED	NUMBER	Number of subshards stored as cached
MAX_SUBSH_SIZE	NUMBER	Maximum subshard size seen till now, in terms of number of messages per subshard
MIN_SUBSH_SIZE	NUMBER	Minimum subshard size seen till now, in terms of number of messages per subshard
MEAN_SUBSH_SIZE	NUMBER	Mean subshard size seen till now, in terms of number of messages per subshard
AVG_EVICTION_RATE	NUMBER	Average number subshards evicted per second
AVG_LOAD_RATE	NUMBER	Average number of subshards pre-fetched or un-evicted per second
AVG_EVICTION_TIME	NUMBER	Average time taken to evict one subshard (in milliseconds)
AVG_LOAD_TIME	NUMBER	Average time taken to un-evict one subshard (in milliseconds)

Column	Datatype	Description
AVG_MISS_RATIO	NUMBER	Average ratio of number of foreground un-evictions versus background pre-fetch
AVG_THRASH_RATIO	NUMBER	Average ratio of number of subshard pre-fetched by background without dequeue attempt versus total number of subshards prefetched
MANDATORY_AFF_SWITCH_ATTEMPTS	NUMBER	An affinity switch is a change in dequeue instance for a shard-subscriber pair. A mandatory affinity switch is when there are local enqueues in the queue at the instance but no local dequeues present, so the dequeue affinity is switched to another instance for that shard-subscriber pair. This column shows the number of times mandatory affinity switches were attempted across all instances. Populated at the smallest instance id only.
OPTIONAL_AFF_SWITCH_ATTEMPTS	NUMBER	Optional affinity switches are affinity switches that are not mandatory. Optional affinity switches are done for global load balancing across the Oracle Real Application Clusters (Oracle RAC) database. This column shows the number of times optional affinity switches were attempted across all instances. Populated at the smallest instance id only.
MIN_EVICT_PERCENT	NUMBER	Percentage of `streams_pool` memory beyond which sharded queue subshard eviction is triggered
LAST_AVG_CACHED_HORIZON	NUMBER	Last average number of cached subshards seen in sharded queue memory manager horizon
LAST_AVG_MEMORY_HORIZON	NUMBER	Last average memory of cached subshards seen in sharded queue memory manager horizon
LAST_AVG_SUBSHARD_HORIZON	NUMBER	Last average number of subshards seen in sharded queue memory manager horizon
LAST_LEEWAY_SHIFT	NUMBER	Internal leeway for memory threshold
AVG_OPTTIME_DRIFT	NUMBER	Average drift of opt_time for all subshards. A drift is defined as a difference between opt_time as set on a subshard and the actual time at which subshard is first dequeueed after prefetch/ uneviction.
NUM_THRESHOLD_DRIFT	NUMBER	Number of times drift value has gone over threshold time. A typical threshold time can be horizon_time/2.
MAX_OPT_TIME_DRIFT	NUMBER	Maximum drift till now
MIN_OPT_TIME_DRIFT	NUMBER	Minimum drift till now
AVG_OPT_TIME_ERROR	NUMBER	An opt_time error occurs when a cached subshard is unevicted by a foreground process (instead of being prefetched by the aq background). Thus, opt_time error is the difference between the actual opt_time set for a sharded queue subshard and the absolute time at which foreground unevicts the same subshard. This column represents average time of this error.
MAX_OPT_TIME_ERROR	NUMBER	Maximum opt_time error
MIN_OPT_TIME_ERROR	NUMBER	Minimum opt_time error
NUM_FG_RELOADED	NUMBER	Number of subshards reloaded from disk into message cache by foreground processes
NUM_PRERELOADED	NUMBER	Number of subshards reloaded from disk into message cache in advance by background processes
AVG_RELOAD_TIME	NUMBER	Average time to reload a subshard from disk into message cache (in milliseconds)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.28 V$AQ_NONDUR_REGISTRATIONS

V$AQ_NONDUR_REGISTRATIONS provides information about non-durable subscriptions.

Column	Datatype	Description
REG_ID	NUMBER	Registration ID
SUBSCRIPTION	VARCHAR2(128)	Subscription name
LOCATION	VARCHAR2(256)	Location name
USER#	NUMBER	User ID
USER_CONTEXT	RAW(32)	Context the user provided
CONTEXT_SIZE	NUMBER	Size of the context
NAMESPACE	NUMBER	Subscription namespace
VERSION	NUMBER	Database version number
STATE	NUMBER	State of the registration: • ENABLED: The registration is enabled for notification • STOPPING: The registration is in a transient state before it becomes DISABLED • DISABLED: The registration is disabled for notification • DEAD: The registration does not exist any more, and it is marked for deferred cleanup.
QOS	NUMBER	Quality of service
REG_TIME	TIMESTAMP(3) WITH TIME ZONE	Time of registration
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Database Advanced Queueing

8.29 V$AQ_NONDUR_SUBSCRIBER

`V$AQ_NONDUR_SUBSCRIBER` provides information about the non-durable subscriptions on sharded queues.

> **Note:**
>
> AQ sharded queues are deprecated in Oracle Database 21c. Oracle recommends that you instead use Transactional Event Queues (TxEventQs) for higher throughput and better performance.

Column	Datatype	Description
`QUEUE_ID`	`NUMBER`	Queue ID
`SUBSCRIBER_ID`	`NUMBER`	ID of the non-durable subscriber
`SUBSCRIBER_NAME`	`VARCHAR2(128)`	Subscriber name
`RULE_CONDITION`	`VARCHAR2(4000)`	Rule condition of the subscriber
`TRANSFORMATION_OWNER`	`VARCHAR2(128)`	Owner of the transformation (for JMS queues)
`TRANSFORMATION_NAME`	`VARCHAR2(128)`	Name of the transformation (for JMS queues)
`CREATION_TIME`	`TIMESTAMP(1) WITH TIME ZONE`	Non-durable subscriber creation time
`FLAGS`	`NUMBER`	Property of the subscriber: • `0x0001` – Persistent subscriber • `0x0002` – Buffered subscriber • `0x0004` – JMS subscriber • `0x0008` – Rule-based subscriber • `0x0010` – Subscriber has transformation • `0x0020` – Notification-only non-durable subscriber subscriber
`SUBSCRIBER_TYPE`	`NUMBER`	Type of subscriber: • `1` – JMS non-durable subscriber • `2` – Service layer dummy non-durable subscriber • `3` – Notification-only non-durable subscriber
`BITPOS`	`NUMBER`	Position of subscriber in subscriber bitmap

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Database Advanced Queueing

8.30 V$AQ_NONDUR_SUBSCRIBER_LWM

V$AQ_NONDUR_SUBSCRIBER_LWM projects the low watermarks (LWMs) of non-durable subscribers in a sharded queue. The LWM of a non-durable subscriber is a combination of shard, priority and LWM (subshard).

> **Note:**
>
> AQ sharded queues are deprecated in Oracle Database 21c. Oracle recommends that you instead use Transactional Event Queues (TxEventQs) for higher throughput and better performance.

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue ID
SUBSCRIBER_ID	NUMBER	ID of the non-durable subscriber
SHARD_ID	NUMBER	Shard ID
PRIORITY	NUMBER	Priority of the shard
LWM	NUMBER	Lower watermark (in a subshard) of the non-durable subscriber
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Database Advanced Queueing

8.31 V$AQ_NOTIFICATION_CLIENTS

`V$AQ_NOTIFICATION_CLIENTS` displays performance statistics for secure OCI client connections.

Column	Datatype	Description
`CLIENT_ID`	`VARCHAR2(29)`	Internally generated client ID for secure notification clients
`EMON_ID`	`NUMBER`	Emon ID serving the client
`NOTIFICATION_STATE`	`NUMBER`	Notification state: • `ACTIVE` – Sending notification • `WAIT_FOR_ACK` – Waiting for client acknowledgment • `INACTIVE` - Idle connection
`NUM_MESSAGE_SENT`	`NUMBER`	Number of messages sent on the connection
`NUM_BYTES_SENT`	`NUMBER`	Number of bytes sent on the connection
`NUM_MESSAGE_RECEIVED`	`NUMBER`	Number of messages successfully received by the client
`LAST_SEND_TIME`	`TIMESTAMP(3) WITH TIME ZONE`	Time when the last message was sent on the connection
`LAST_RECEIVE_TIME`	`TIMESTAMP(3) WITH TIME ZONE`	Time when the last message was received over the connection
`CONNECT_TIME`	`TIMESTAMP(3) WITH TIME ZONE`	Time at which the client connected
`DISCONNECT_TIME`	`TIMESTAMP(3) WITH TIME ZONE`	Time at which the client disconnected
`LAST_ERROR`	`NUMBER`	The last error that occurred on the client connection
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Database Advanced Queueing

8.32 V$AQ_PARTITION_STATS

V$AQ_PARTITION_STATS displays usage statistics for the queue partition cache and the dequeue log partition cache.

> **Note:**
>
> AQ sharded queues are deprecated in Oracle Database 21c. Oracle recommends that you instead use Transactional Event Queues (TxEventQs) for higher throughput and better performance.

Column	Datatype	Description
INST_ID	NUMBER	Current instance ID
QUEUE_ID	NUMBER	Queue ID
QUEUE_TABLE_ID	NUMBER	Queue table object ID
QUEUE_SCHEMA	VARCHAR2(128)	Queue schema name
QUEUE_NAME	VARCHAR2(128)	Queue name
PT_TUNED_SIZ_QT	NUMBER	Current tuned size of the queue partition cache, expressed in number of partition cache elements
PT_CACHED_PTNS_QT	NUMBER	Current number of cached partitions in the queue partition cache
PT_OVER_CACHED_PTNS_QT	NUMBER	Current number of over-cached partitions in the queue partition cache, that is, the number of cached partitions whose partition cache elements exceed the current tuned size of the queue partition cache
PT_TOTAL_UPTUNE_QT	NUMBER	Total amount of space added to the queue partition cache due to tune-ups, since the cache was initialized, expressed in number of partition cache elements
PT_NO_OF_UPTUNES_QT	NUMBER	Total number of times a tune-up was triggered on the queue partition cache, since the cache was initialized
PT_TOTAL_DOWNTUNE_QT	NUMBER	Total amount of space removed from the queue partition cache due to tune-downs, since the cache was initialized, expressed in number of partition cache elements
PT_NO_OF_DOWNTUNES_QT	NUMBER	Total number of times a tune-down was triggered on the queue partition cache, since the cache was initialized
PT_CACHE_MISS_QT	NUMBER	Total number of cache misses during partition lookups on the queue partition cache
PT_CACHE_HIT_QT	NUMBER	Total number of cache hits during partition lookups on the queue partition cache
PT_TOTAL_CACH_GET_QT	NUMBER	Total number of successful fetches from the queue partition cache
PT_TOTAL_CACH_PUT_QT	NUMBER	Total number of caching operations that occurred on the queue partition cache
PT_UNBOUNDINGS_QT	NUMBER	Total number of times queue partitions were unbounded
PT_TUNED_SIZ_DQ	NUMBER	Current tuned size of the dequeue log partition cache, expressed in number of partition cache elements
PT_CACHED_PTNS_DQ	NUMBER	Current number of cached partitions in the dequeue log partition cache

Column	Datatype	Description
PT_OVER_CACHED_PTNS_DQ	NUMBER	Current number of over-cached partitions in the dequeue log partition cache, that is, the number of cached dequeue log partitions whose partition cache elements exceed the current tuned size of the dequeue log partition cache
PT_TOTAL_UPTUNE_DQ	NUMBER	Total amount of space added to the dequeue log partition cache due to tune-ups, since the cache was initialized, expressed in number of partition cache elements
PT_NO_OF_UPTUNES_DQ	NUMBER	Total number of times a tune-up was triggered on the dequeue log partition cache, since the cache was initialized
PT_TOTAL_DOWNTUNE_DQ	NUMBER	Total amount of space removed from the dequeue log partition cache due to tune-downs, since the cache was initialized, expressed in number of partition cache elements
PT_NO_OF_DOWNTUNES_DQ	NUMBER	Total number of times a tune-down was triggered on the dequeue log partition cache, since the cache was initialized
PT_CACHE_MISS_DQ	NUMBER	Total number of cache misses during partition lookups on the dequeue log partition cache
PT_CACHE_HIT_DQ	NUMBER	Total number of cache hits during partition lookups on the dequeue log partition cache
PT_TOTAL_CACH_GET_DQ	NUMBER	Total number of successful fetches from the dequeue log partition cache
PT_TOTAL_CACH_PUT_DQ	NUMBER	Total number of caching operations that occurred on the dequeue log partition cache
PT_UNBOUNDINGS_DQ	NUMBER	Total number of times dequeue log partitions were unbounded
ADD_PARTITION_FG_QT	NUMBER	Total number of queue partitions created inline during foreground AQ enqueue operations
ADD_PARTITION_BG_QT	NUMBER	Total number of queue partitions created asynchronously by the AQ partitioning background process
ADD_PARTITION_FG_DQLOG	NUMBER	Total number of dequeue log partitions created inline during foreground AQ dequeue operations
ADD_PARTITION_BG_DQLOG	NUMBER	Total number of dequeue log partitions created asynchronously by the AQ partitioning background process
TRUNC_PARTITION_QT	NUMBER	Total number of truncated and recycled queue partitions
TRUNC_PARTITION_DQLOG	NUMBER	Total number of truncated and recycled dequeue log partitions
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.33 V$AQ_REMOTE_DEQUEUE_AFFINITY

V$AQ_REMOTE_DEQUEUE_AFFINITY lists the dequeue affinity instance of the subscribers not dequeuing locally from the shard's owner instance. Cross instance message forwarding is used for these subscribers.

> **Note:**
>
> AQ sharded queues are deprecated in Oracle Database 21c. Oracle recommends that you instead use Transactional Event Queues (TxEventQs) for higher throughput and better performance.

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue ID
SHARD_ID	NUMBER	Shard ID which is being forwarded from SOURCE_INSTANCE to INST_ID for the subscriber
SOURCE_INSTANCE_ID	NUMBER	Owner instance ID from where the shard is being forwarded
SUBSCRIBER_ID	NUMBER	Subscriber ID
QUEUE_SCHEMA	VARCHAR2(128)	Queue schema name
QUEUE_NAME	VARCHAR2(128)	Queue name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.34 V$AQ_SERVER_POOL

V$AQ_SERVER_POOL lists performance statistics for all the servers in the pool.

Column	Datatype	Description
COORDINATOR_ID	NUMBER	ID of the coordinator
COORDINATOR_INSTANCE_ID	NUMBER	Instance of the coordinator
PROCESS_ID	VARCHAR2(24)	Operating system process ID of the server
PROCESS_NAME	VARCHAR2(48)	Operating system process name of the server
JOB_NAME	VARCHAR2(32)	Name of the job handled
POOL_STATE	VARCHAR2(20)	State of the pool: • REMOTE • IDLE • ACTIVE

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. The CON_ID value in this view is always 0. The rows pertain to the entire CDB or to the non-CDB.

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Database Advanced Queueing

8.35 V$AQ_SHARDED_SUBSCRIBER_STAT

V$AQ_SHARDED_SUBSCRIBER_STAT displays basic statistical information about the subscribers of sharded queues. There is one row per queue per shard per subscriber.

> **Note:**
>
> AQ sharded queues are deprecated in Oracle Database 21c. Oracle recommends that you instead use Transactional Event Queues (TxEventQs) for higher throughput and better performance.

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue identifier
SUBSCRIBER_ID	NUMBER	Subscriber identifier
SHARD_ID	NUMBER	Shard identifier
PRIORITY	NUMBER	Priority value of the shard
MSG_SN	NUMBER	Message serial number
DEQUEUE_SUBSHARD	NUMBER	Last known dequeue position in this shard
ENQUEUED_MSGS	NUMBER	Number of enqueued messages
DEQUEUED_MSGS	NUMBER	Number of dequeued messages
ELAPSED_DEQUEUE_TIME	NUMBER	Amount of time spent performing dequeues (in seconds)
CPU_DEQUEUE_TIME	NUMBER	Actual amount of CPU time spent performing dequeues (in seconds)
DEQUEUE_RATE	NUMBER	Number of messages dequeued per second
DEQUEUE_POSITION	RAW(16)	Message ID at the dequeue position of the subscriber in this shard A NULL value indicates that either the shard is empty or no dequeues have been done on this shard.
TIME_SINCE_LAST_DEQUEUE	NUMBER	Time since last dequeue activity (in seconds)
ESTD_TIME_TO_DRAIN	NUMBER	Estimated amount of time to drain the shard (in seconds) with current enqueue and dequeue rates. Null, if the enqueue rate is greater than the dequeue rate.

Column	Datatype	Description
ESTD_TIME_TO_DRAIN_NO_ENQ	NUMBER	Estimated amount of time to drain the shard (in seconds) with no new enqueues
MESSAGE_LATENCY_1	NUMBER	Message latency within the last 5 minutes (in milliseconds). Null if no message is consumed or it is delay dequeue.
MESSAGE_LATENCY_2	NUMBER	Message latency within the last 1 hour (in milliseconds). Null if no message is consumed or it is delay dequeue.
MESSAGE_LATENCY_3	NUMBER	Message latency within the last 5 hours (in milliseconds). Null if no message is consumed or it is delay dequeue.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.36 V$AQ_SUBSCRIBER_LOAD

V$AQ_SUBSCRIBER_LOAD describes the load of all subscribers of sharded queues in terms of latency at every instance in an Oracle RAC environment.

Latency denotes the predicted amount of time (in seconds) required from the current time to drain all the messages for that subscriber at each respective instance. The latency calculation considers past enqueue/dequeue rates and future enqueue/dequeue rates based on history.

> **Note:**
>
> AQ sharded queues are deprecated in Oracle Database 21c. Oracle recommends that you instead use Transactional Event Queues (TxEventQs) for higher throughput and better performance.

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue ID
QUEUE_SCHEMA	VARCHAR2(128)	Queue schema
QUEUE_NAME	VARCHAR2(128)	Queue name
SUBSCRIBER_ID	NUMBER	Subscriber ID
SUBSCRIBER_NAME	VARCHAR2(128)	Subscriber name
LATENCY_STATE	VARCHAR2(8)	Possible values: • FINITE - The subscriber will be able to dequeue all the messages in a finite amount of time • INFINITE - The subscriber's dequeue rate may not catch up to the enqueue rate • UNKNOWN - Latency is not yet known
LATENCY	NUMBER	Latency (in seconds). Valid only when LATENCY_STATE is FINITE.

Column	Datatype	Description
DEQUEUE_REQUESTS	NUMBER	Approximate number of dequeue requests noted recently
ACTIVE_SHARDS	NUMBER	Number of queue shards that have messages for this subscriber
ACTIVE_LISTENER	VARCHAR2(5)	Indicates whether the subscriber is actively listening at this instance for messages (TRUE) or not (FALSE)
DEQUEUE_SESSIONS	NUMBER	Displays the number of active dequeue sessions for this subscriber
FLAGS	NUMBER	For internal use only
MANDATORY_AFF_SWITCHES	NUMBER	An affinity switch is a change in the dequeue instance for a shard-subscriber pair. A mandatory affinity switch is when there are local enqueues in the queue at the instance but no local dequeues present, so the dequeue affinity is switched to another instance for that shard-subscriber pair. This column shows the number of times mandatory affinity switches were needed from this instance to another for this subscriber.
OPTIONAL_AFF_SWITCHES	NUMBER	Optional affinity switches are affinity switches that are not mandatory. Optional affinity switches are done for global load balancing across the Oracle Real Application Clusters (Oracle RAC) database. This column shows the number of times optional affinity switches were needed from this instance to another for this subscriber.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database Advanced Queuing User's Guide for more information about Oracle Database Advanced Queueing

8.37 V$ARCHIVE

V$ARCHIVE displays information about redo log files in need of archiving.

Each row displays information for one thread. This information is also available in V$LOG. Oracle recommends that you use V$LOG.

See Also:

"V$LOG"

Column	Datatype	Description
GROUP#	NUMBER	Log file group number
THREAD#	NUMBER	Log file thread number
SEQUENCE#	NUMBER	Log file sequence number
ISCURRENT	VARCHAR2(3)	This is the current online redo log
CURRENT	VARCHAR2(3)	This column is obsolete and maintained for backward compatibility. The value of this column is always equal to the value in ISCURRENT.
FIRST_CHANGE#	NUMBER	First SCN stored in the current log
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.38 V$ARCHIVE_DEST

V$ARCHIVE_DEST displays, for the current instance, all of the destinations in the Data Guard configuration, including each destination's current value, mode, and status.

Column	Datatype	Description
DEST_ID	NUMBER	Log archive destination parameter identifier (1 to 31)
DEST_NAME	VARCHAR2(256)	Log archive destination parameter name
STATUS	VARCHAR2(9)	Identifies the current status of the destination: • VALID - Initialized and available • INACTIVE - No destination information • DEFERRED - Manually disabled by the user • ERROR - Error during open or copy • DISABLED - Disabled after error • BAD PARAM - Parameter has errors • ALTERNATE - Destination is available as an alternate • FULL - Exceeded quota size for the destination
BINDING	VARCHAR2(9)	Specifies how failure will affect the archival operation: • MANDATORY - Successful archival is required • OPTIONAL - Successful archival is not required (depends on LOG_ARCHIVE_MIN_SUCCEED_DEST)
NAME_SPACE	VARCHAR2(7)	Identifies the scope of parameter setting: • SYSTEM - System definition • SESSION - Session definition

Column	Datatype	Description
TARGET	VARCHAR2(7)	For a primary database, this column specifies whether the archive destination is local or remote to the primary database: • PRIMARY - local • STANDBY - remote For a standby database, this column specifies whether the archive destination is local or remote to the standby database: • LOCAL - local • REMOTE - remote
ARCHIVER	VARCHAR2(10)	Identifies the archiver process relative to the database where the query is issued: • ARC*n* • FOREGROUND • LGWR • RFS
SCHEDULE	VARCHAR2(8)	Indicates whether the archival of this destination is INACTIVE, PENDING, ACTIVE, or LATENT
DESTINATION	VARCHAR2(256)	Specifies the location where the archived redo logs are to be archived
LOG_SEQUENCE	NUMBER	Identifies the sequence number of the last archived redo log to be archived
REOPEN_SECS	NUMBER	Identifies the retry time (in seconds) after error
DELAY_MINS	NUMBER	Identifies the delay interval (in minutes) before the archived redo log is automatically applied to a standby database
NET_TIMEOUT	NUMBER	Number of seconds the log writer process will wait for status from the network server of a network operation issued by the log writer process
PROCESS	VARCHAR2(10)	Identifies the archiver process relative to the primary database, even if the query is issued on the standby database: • ARC*n* • FOREGROUND • LGWR
REGISTER	VARCHAR2(3)	Indicates whether the archived redo log is registered in the remote destination control file (YES) or not (NO). If the archived redo log is registered, it is available to log apply services.
FAIL_DATE	DATE	Date and time of last error
FAIL_SEQUENCE	NUMBER	Sequence number of the archived redo log being archived when the last error occurred
FAIL_BLOCK	NUMBER	Block number of the archived redo log being archived when the last error occurred
FAILURE_COUNT	NUMBER	Current number of contiguous archival operation failures that have occurred for the destination
MAX_FAILURE	NUMBER	Allows you to control the number of times log transport services will attempt to reestablish communication and resume archival operations with a failed destination
ERROR	VARCHAR2(256)	Displays the error text
ALTERNATE	VARCHAR2(256)	Alternate destination, if any
DEPENDENCY	VARCHAR2(256)	Reserved for future use

Column	Datatype	Description
REMOTE_TEMPLATE	VARCHAR2(256)	Specifies the template to be used to derive the location to be recorded
QUOTA_SIZE	NUMBER	Destination quotas, expressed in bytes
QUOTA_USED	NUMBER	Size of all the archived redo logs currently residing on the specified destination
MOUNTID	NUMBER	Instance mount identifier
TRANSMIT_MODE	VARCHAR2(12)	Specifies network transmission mode: • SYNCHRONOUS • PARALLELSYNC • ASYNCHRONOUS
ASYNC_BLOCKS	NUMBER	Number of blocks specified for the ASYNC attribute
AFFIRM	VARCHAR2(3)	Specifies disk I/O mode
TYPE	VARCHAR2(7)	Indicates whether the archived log destination definition is PUBLIC or PRIVATE. Only PUBLIC destinations can be modified at run time using the ALTER SYSTEM SET or ALTER SESSION SET statements. By default, all archived log destinations are PUBLIC.
VALID_NOW	VARCHAR2(16)	Indicates whether the destination is valid right now for archival operations: • YES - Redo log type and database role for this destination are valid for the current database • WRONG VALID_TYPE - Redo log type specified for this destination is not valid for the current database role. For example, WRONG VALID_TYPE would be returned if a destination specified with the VALID_FOR=(STANDBY_LOGFILE,STANDBY_ROLE) attribute is running in the standby database role but does not have standby redo logs implemented. • WRONG VALID_ROLE - Database role specified for this destination is not the role in which the database is currently running. For example, the WRONG VALID_ROLE would be returned when a destination defined with the VALID_FOR=(ONLINE_LOGFILE,STANDBY_ROLE) attribute is running in the primary database role. • INACTIVE - Destination is inactive, probably due to an error
VALID_TYPE	VARCHAR2(15)	Redo log type or types that are valid for the destination: • ONLINE_LOGFILE • STANDBY_LOGFILE • ALL_LOGFILES
VALID_ROLE	VARCHAR2(12)	Database role or roles that are valid for the destination: • PRIMARY_ROLE • STANDBY_ROLE • ALL_ROLES
DB_UNIQUE_NAME	VARCHAR2(30)	Unique database name
VERIFY	VARCHAR2(3)	Indicates whether the value of the VERIFY attribute on the LOG_ARCHIVE_DEST_*n* parameter is verified (YES) or not verified (NO)

Column	Datatype	Description
COMPRESSION	VARCHAR2(7)	Indicates whether network compression is ENABLED or DISABLED, or whether the ZLIB or LZO algorithm is in use. These values correspond to the values accepted by the COMPRESSION attribute for the database initialization parameter LOG_ARCHIVE_DEST_n. The possible values include: • DISABLE: Compression is disabled. • ENABLE: Compression is enabled. The ZLIB compression algorithm is used. • ZLIB: ZLIB compression is used. • LZO: LZO compression is used.
APPLIED_SCN	NUMBER	For a destination that corresponds to a physical or logical standby database, the SCN of the last applied redo. For a destination that corresponds to a snapshot standby database, the SCN of the last redo applied before conversion to a snapshot standby database. This column is only valid for enabled and active standby database destinations on a primary or cascading standby database.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
ENCRYPTION	VARCHAR2(7)	Indicates whether encryption of the redo stream sent to Zero Data Loss Recovery Appliance (Recovery Appliance) is enabled (ENABLED) or not (DISABLED)
ROLE	VARCHAR2(9)	Role of the destination: • DATACACHE • FARSYNC • LOCAL • LOGICAL • PHYSICAL • PRIMARY • SNAPSHOT

See Also:

- *Zero Data Loss Recovery Appliance Administrator's Guide* for introductory information about Recovery Appliance
- "LOG_ARCHIVE_DEST" and "LOG_ARCHIVE_DEST_*n*"
- "LOG_ARCHIVE_DUPLEX_DEST" and "LOG_ARCHIVE_DEST_STATE_*n*"
- "LOG_ARCHIVE_MIN_SUCCEED_DEST"

8.39 V$ARCHIVE_DEST_STATUS

V$ARCHIVE_DEST_STATUS displays run time and configuration information for the archived redo log destinations.

The information in this view does not persist across an instance shutdown.

Column	Datatype	Description
DEST_ID	NUMBER	Identifies the log archive destination parameter (1 to 31)
DEST_NAME	VARCHAR2(256)	Log archive destination parameter name
STATUS	VARCHAR2(9)	Current status of the destination: • VALID - Initialized and available • INACTIVE - No destination information • DEFERRED - Manually disabled by the user • ERROR - Error during open or copy • DISABLED - Disabled after error • BAD PARAM - Parameter has errors • ALTERNATE - Destination is in an alternate state • FULL - Exceeded quota size for the destination
TYPE	VARCHAR2(14)	Type of archival destination database: • LOCAL - Local to primary database • PHYSICAL - Physical standby • CROSS-INSTANCE - An instance of the primary • LOGICAL - Logical standby • SNAPSHOT - Snapshot standby database • DOWNSTREAM - Streams downstream capture database • FAR SYNC - Far Sync Instance
DATABASE_MODE	VARCHAR2(15)	Current mode of the archival destination database: • STARTED - Instance started, not mounted • MOUNTED - Mounted • MOUNTED-STANDBY - Mounted standby • OPEN - Open read/write • OPEN_READ-ONLY - Open read-only

Column	Datatype	Description
RECOVERY_MODE	VARCHAR2(23)	Current apply mode at the archival destination: • IDLE - Managed recovery is not active • MANAGED - Managed recovery is active. This value is used when the standby database is mounted. In this recovery mode, users cannot query data on the standby. • MANAGED WITH QUERY - Managed recovery is active in this recovery mode. In a non-CDB, this value is used when the database is open, and users can query data on the standby. In a CDB, this value is used when one or more PDBs in the CDB are open, and users can query data on the standby. • MANAGED REAL TIME APPLY - In this recovery mode, log apply services recover redo data from standby redo logs at the same time the logs are being written to, as opposed to recovering redo from archived redo logs when a log switch occurs. In this recovery mode, users cannot query data on the standby. • MANAGED REAL TIME APPLY WITH QUERY - In this recovery mode, log apply services recover redo data from standby redo logs at the same time the logs are being written to, as opposed to recovering redo from archived redo logs when a log switch occurs. In a non-CDB, this mode is used when the database is open, and users can query data on the standby. In a CDB, this value is used when one or more PDBs in the CDB are open, and users can query data on the standby. • LOGICAL REAL TIME APPLY - Real time SQL Apply • LOGICAL APPLY - SQL Apply
PROTECTION_MODE	VARCHAR2(20)	Indicates whether the database is protected: • MAXIMUM PROTECTION • MAXIMUM AVAILABILITY • RESYNCHRONIZATION • MAXIMUM PERFORMANCE • UNPROTECTED
DESTINATION	VARCHAR2(256)	Specifies the location where the redo data is to be archived
STANDBY_LOGFILE_COUNT	NUMBER	Indicates the total number of standby redo logs created on the standby database
STANDBY_LOGFILE_ACTIVE	NUMBER	Indicates the total number of standby redo logs on the standby database that are active and contain primary database online redo log information
ARCHIVED_THREAD#	NUMBER	Identifies the thread number of the most recent archived redo log received at the destination
ARCHIVED_SEQ#	NUMBER	Identifies the log sequence number of the most recent archived redo log received at the destination
APPLIED_THREAD#	NUMBER	Identifies the thread number of the most recent applied redo log received at the destination
APPLIED_SEQ#	NUMBER	Identifies the log sequence number of the most recent applied redo log received at the destination
ERROR	VARCHAR2(256)	Displays the error text
SRL	VARCHAR2(3)	Indicates whether standby redo logfiles are used on the standby database (YES) or not (NO)

Column	Datatype	Description
DB_UNIQUE_NAME	VARCHAR2(30)	Specifies the unique database name of the current instance that was defined with the DB_UNIQUE_NAME attribute on the LOG_ARCHIVE_DEST_*n* parameter
SYNCHRONIZATION_STATUS	VARCHAR2(22)	Possible values for this column are as follows: • CHECK CONFIGURATION - Synchronization with this destination is not possible because this database is either not in MAXIMUM PROTECTION or MAXIMUM AVAILABILITY data protection mode, or the LOG_ARCHIVE_DEST_*n* parameter associated with this destination has not been configured with the SYNC and AFFIRM attributes. • CHECK STANDBY REDO LOG - The standby redo log at this destination is configured improperly. • CHECK NETWORK - One or more instances of this database cannot send redo data to this destination. • DESTINATION HAS A GAP - This destination is missing redo data needed for synchronization with this database. • OK - This destination is synchronized with this database. • NOT AVAILABLE - Synchronization status is not available. **See Also:** *Oracle Data Guard Concepts and Administration* for more information about redo transport configuration
SYNCHRONIZED	VARCHAR2(3)	Possible values are: • YES - This destination is synchronized with the primary database. • NO - The destination is not synchronized with the primary database. • UNKNOWN - The synchronization status of this destination cannot be determined.
GAP_STATUS	VARCHAR2(24)	Redo gap status: • NO GAP - Destination does not have a redo gap. • LOG SWITCH GAP - Destination has not yet received all of the redo from the previous log file. • RESOLVABLE GAP - Destination has a redo gap that can be automatically resolved by fetching the missing redo from this database. • UNRESOLVABLE GAP - Destination has a redo gap that cannot be automatically resolved by fetching the missing redo from this database and there are no other destinations from which redo can be fetched. • LOCALLY UNRESOLVABLE GAP - Destination has a redo gap that cannot be automatically resolved by fetching the missing redo from this database. It may be possible to resolve the gap by fetching the missing redo from another destination.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.40 V$ARCHIVE_GAP

V$ARCHIVE_GAP displays information about archive gaps on a standby database. This view can be used to find out the current archive gap that is blocking recovery for the current recovery incarnation.

Column	Datatype	Description
THREAD#	NUMBER	Thread number of the missing archived redo log files. The number is 1 for a single instance. For Oracle Real Application Clusters, this column will contain different numbers.
LOW_SEQUENCE#	NUMBER	Lowest sequence number of the log files received on the standby system
HIGH_SEQUENCE#	NUMBER	Highest sequence number of the log files received on the standby system
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.41 V$ARCHIVE_PROCESSES

V$ARCHIVE_PROCESSES displays the state of the various ARCH processes for the instance.

Column	Datatype	Description
PROCESS	NUMBER	Identifier for the ARCH process for the instance, numbered from 0-9
STATUS	VARCHAR2(10)	Status of the ARCH process, displayed as a keyword. Possible values are: STOPPED, SCHEDULED, STARTING, ACTIVE, STOPPING, and TERMINATED.
LOG_SEQUENCE	NUMBER	This is the online redo log sequence number currently being archived, if STATE="BUSY"
STATE	VARCHAR2(4)	This is the current state of the ARCH process, displayed as a keyword. Possible keywords are IDLE or BUSY.
ROLES	VARCHAR2(36)	The list of roles assigned to the archive process. The roles include: HEART_BEAT, NO_FAL, NO_SRL, CLEAR_LOGS
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.42 V$ARCHIVED_LOG

V$ARCHIVED_LOG displays archived log information from the control file, including archive log names.

An archive log record is inserted after the online redo log is successfully archived or cleared (name column is NULL if the log was cleared). If the log is archived twice, there will be two archived log records with the same THREAD#, SEQUENCE#, and FIRST_CHANGE#, but with a different name. An archive log record is also inserted when an archive log is restored from a backup set or a copy and whenever a copy of a log is made with the RMAN COPY command.

Column	Datatype	Description
RECID	NUMBER	Archived log record ID
STAMP	NUMBER	Archived log record stamp
NAME	VARCHAR2(513)	Archived log file name. If set to NULL, either the log file was cleared before it was archived or an RMAN backup command with the "delete input" option was executed to back up archivelog all (RMAN> backup archivelog all delete input;).
DEST_ID	NUMBER	Original destination from which the archive log was generated. The value is 0 if the destination identifier is not available.
THREAD#	NUMBER	Redo thread number
SEQUENCE#	NUMBER	Redo log sequence number
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the database when the log was written
RESETLOGS_TIME	DATE	Resetlogs time of the database when the log was written
RESETLOGS_ID	NUMBER	Resetlogs identifier associated with the archived redo log
FIRST_CHANGE#	NUMBER	First change number in the archived log
FIRST_TIME	DATE	Timestamp of the first change
NEXT_CHANGE#	NUMBER	First change in the next log
NEXT_TIME	DATE	Timestamp of the next change
BLOCKS	NUMBER	Size of the archived log (in blocks)
BLOCK_SIZE	NUMBER	Redo log block size. This is the logical block size of the archived log, which is the same as the logical block size of the online log from which the archived log was copied. The online log logical block size is a platform-specific value that is not adjustable by the user.
CREATOR	VARCHAR2(7)	Creator of the archivelog: • ARCH - Archiver process • FGRD - Foreground process • RMAN - Recovery Manager • SRMN - RMAN at standby • LGWR - Logwriter process

Column	Datatype	Description
REGISTRAR	VARCHAR2(7)	Registrar of the entry: • RFS - Remote File Server process • ARCH - Archiver process • FGRD - Foreground process • RMAN - Recovery manager • SRMN - RMAN at standby • LGWR - Logwriter process
STANDBY_DEST	VARCHAR2(3)	Indicates whether the entry is an archivelog destination (YES) or not (NO)
ARCHIVED	VARCHAR2(3)	Indicates whether the online redo log was archived (YES) or whether RMAN only inspected the log and created a record for future application of redo logs during recovery (NO).
APPLIED	VARCHAR2(9)	Indicates whether an archived redo log file has been applied to the corresponding physical standby database. The value is always NO for local destinations. This column is meaningful on a physical standby database for rows where REGISTRAR = RFS: • If REGISTRAR = RFS and APPLIED = NO, then the log file has been received but has not yet been applied. • If REGISTRAR = RFS and APPLIED = IN-MEMORY, then the log file has been applied in memory, but the data files have not yet been updated. • If REGISTRAR = RFS and APPLIED = YES, then the log file has been applied and the data files have been updated. This column can be used to identify log files that can be backed up and deleted. When used for this purpose, the value IN-MEMORY should be treated as if it were NO.
DELETED	VARCHAR2(3)	Indicates whether an RMAN DELETE command has physically deleted the archived log file from disk, as well as logically removing it from the control file of the target database and from the recovery catalog (YES) or not (NO)
STATUS	VARCHAR2(1)	Status of the archived log: A - Available D - Deleted U - Unavailable X - Expired
COMPLETION_TIME	DATE	Time when the archiving completed
DICTIONARY_BEGIN	VARCHAR2(3)	Indicates whether the log contains the start of a LogMiner dictionary (YES) or not (NO)
DICTIONARY_END	VARCHAR2(3)	Indicates whether the log contains the end of a LogMiner dictionary (YES) or not (NO)
END_OF_REDO	VARCHAR2(3)	Indicates whether the archived redo log contains the end of all redo information from the primary database (YES) or not (NO)
BACKUP_COUNT	NUMBER	Indicates the number of times this file has been backed up. Values range from 0-15. If the file has been backed up more than 15 times, the value remains 15.

Column	Datatype	Description
ARCHIVAL_THREAD#	NUMBER	Redo thread number of the instance that performed the archival operation. This column differs from the THREAD# column only when a closed thread is archived by another instance.
ACTIVATION#	NUMBER	Number assigned to the database instantiation
IS_RECOVERY_DEST_FILE	VARCHAR2(3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)
COMPRESSED	VARCHAR2(3)	Reserved for internal use
FAL	VARCHAR2(3)	Indicates whether the archive log was generated as the result of a FAL request (YES) or not (NO)
END_OF_REDO_TYPE	VARCHAR2(10)	Possible values are as follows: • SWITCHOVER - Shows archived redo log files that are produced at the end of a switchover • TERMINAL - Shows archived redo log files produced after a failover • RESETLOGS - Shows online redo log files archived on the primary database after an ALTER DATABASE OPEN RESETLOGS statement is issued • ACTIVATION - Shows any log files archived on a physical standby database after an ALTER DATABASE ACTIVATE STANDBY DATABASE statement is issued • "empty string" - Any empty string implies that the log is just a normal archival and was not archived due to any of the other events
BACKED_BY_VSS	VARCHAR2(3)	Whether or not the file has been backed up by Volume Shadow Copy Service (VSS). This column is reserved for internal use.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.43 V$ASM_ACFS_ENCRYPTION_INFO

V$ASM_ACFS_ENCRYPTION_INFO displays encryption information for every mounted Oracle ACFS.

Column	Datatype	Description
FS_NAME	VARCHAR2(1024)	File system mount point (foreign key to V$ASM_FILESYSTEM)
VOL_DEVICE	VARCHAR2(256)	Name of the Oracle ADVM device
SET_STATUS	VARCHAR2(7)	Indicates whether encryption parameters have been set on the file system (YES) or not (NO); otherwise UNKNOWN.
ENABLED_STATUS	VARCHAR2(8)	Indicates whether file system level encryption is enabled (ENABLED) or not (DISABLED); otherwise UNKNOWN.
ALGORITHM	VARCHAR2(7)	Encryption algorithm used. AES is the only supported algorithm.

Column	Datatype	Description
KEY_LENGTH	VARCHAR2(7)	Key length used for the encryption key
LAST_REKEY_TIME	DATE	Time that the volume was last rekeyed
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

See Also:

- *Oracle Automatic Storage Management Administrator's Guide* for more information about Oracle Advanced Cluster File System (Oracle ACFS)
- *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle Advanced Cluster File System (Oracle ACFS) and Oracle ASM Dynamic Volume Manager (Oracle ADVM) information

Note:

To display information about Oracle ACFS file systems or volumes that are located on nodes in an Oracle Flex ASM configuration, you must connect to the Oracle ASM proxy instance instead of the local Oracle ASM instance. For information about Oracle Flex ASM, refer to *Oracle Automatic Storage Management Administrator's Guide*.

8.44 V$ASM_ACFSAUTORESIZE

V$ASM_ACFSAUTORESIZE displays the auto-resize settings for each mounted Oracle ACFS file system.

Column	Datatype	Description
FS_NAME	VARCHAR2(1024)	Full path name of the Oracle ACFS file system mount point
RESIZE_INCREMENT	NUMBER	Auto-resize increment (in megabytes)
RESIZE_MAXIMUM	NUMBER	Auto-resize maximum (in megabytes)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- *Oracle Automatic Storage Management Administrator's Guide* for more information about Oracle Advanced Cluster File System (Oracle ACFS)
- *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle Advanced Cluster File System (Oracle ACFS) and Oracle ASM Dynamic Volume Manager (Oracle ADVM) information

Note:

To display information about Oracle ACFS file systems or volumes that are located on nodes in an Oracle Flex ASM configuration, you must connect to the Oracle ASM proxy instance instead of the local Oracle ASM instance. For information about Oracle Flex ASM, refer to *Oracle Automatic Storage Management Administrator's Guide*.

8.45 V$ASM_ACFSREPL

V$ASM_ACFSREPL displays information for Oracle ACFS file systems that are initialized for replication.

Column	Datatype	Description
FSNAME	VARCHAR2(1024)	File system mount point (foreign key to V$ASM_FILESYSTEM)
VOLDEV	VARCHAR2(256)	Name of the Oracle ADVM device
SITE	VARCHAR2(7)	Replication site role: • PRIMARY - File system is initialized as a primary • STANDBY - File system is initialized as a standby
LAG	VARCHAR2(128)	Amount of time standby is behind primary in hours:minutes:seconds (primary only)

Column	Datatype	Description
STATUS	VARCHAR2(12)	Replication primary or standby status: • ONLINE - Replication is initialized and processing real-time changes • INITIALIZING - Replication is still processing files on the primary that existed before replication started • PAUSED - The primary is not sending logs to the standby or the standby is not applying logged changes
INITSTATUS	VARCHAR2(11)	Replication primary or standby initialization status: • NONE - Replication is ONLINE and not initializing • DIRECTORIES - Directories are being initialized • FILES - Files are being initialized
DIRSSCAN	NUMBER	Number of directories scanned and logged (primary only)
PERCENT	NUMBER	Percentage of files initialized that existed before replication started (primary only)
LASTSYNC	DATE	Time of last apply on the standby site (standby only)
CRSRUN	NUMBER	Number of Cluster Ready Services replication daemons currently running
CRSTOTAL	NUMBER	Number of Cluster Ready Services replication daemons expected to be running
PMNTPT	VARCHAR2(1024)	Replication primary site mount point
SMNTPT	VARCHAR2(1024)	Replication standby site mount point
PSVCNAME	VARCHAR2(1024)	Replication primary site service name
SSVCNAME	VARCHAR2(1024)	Replication standby site service name
PHOST	VARCHAR2(1024)	A replication primary cluster host name
SHOST	VARCHAR2(1024)	A replication standby cluster host name
REMALIAS	VARCHAR2(4096)	Replication remote alias name
TAGS	NUMBER	TRUE (1) if replicating tagged files
COMPRESSION	VARCHAR2(3)	Replication log compression status: • OFF - Replication logs are not being compressed • ON - Replication logs are being compressed
DBGLVL	NUMBER	Replication trace log debug level
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

> **Note:**
>
> This view only contains records for Oracle ASM releases prior to Oracle Database 12*c* Release 2 (12.2.0.1). To display Oracle ACFS replication information for Oracle Database 12*c* Release 2 (12.2.0.1) or higher, use the `acfsutil repl info` command.

> **See Also:**
>
> - *Oracle Automatic Storage Management Administrator's Guide* for more information about Oracle Advanced Cluster File System (Oracle ACFS)
> - *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle Advanced Cluster File System (Oracle ACFS) and Oracle ASM Dynamic Volume Manager (Oracle ADVM) information

> **Note:**
>
> To display information about Oracle ACFS file systems or volumes that are located on nodes in an Oracle Flex ASM configuration, you must connect to the Oracle ASM proxy instance instead of the local Oracle ASM instance. For information about Oracle Flex ASM, refer to *Oracle Automatic Storage Management Administrator's Guide*.

8.46 V$ASM_ACFSREPLTAG

`V$ASM_ACFSREPLTAG` displays replicated tag information for Oracle ACFS file systems that are initialized for replication.

Column	Datatype	Description
`FSNAME`	`VARCHAR2(1024)`	File system mount point (foreign key to `V$ASM_FILESYSTEM`)
`VOLDEV`	`VARCHAR2(256)`	Name of the Oracle ADVM device
`TAG`	`VARCHAR2(32)`	Tag name that is being replicated
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always `0`.

Note:

This view only contains records for Oracle ASM releases prior to Oracle Database 12*c* Release 2 (12.2.0.1). To display Oracle ACFS replication information for Oracle Database 12*c* Release 2 (12.2.0.1) or higher, use the `acfsutil repl info` command.

See Also:

- *Oracle Automatic Storage Management Administrator's Guide* for more information about Oracle Advanced Cluster File System (Oracle ACFS)
- *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle Advanced Cluster File System (Oracle ACFS) and Oracle ASM Dynamic Volume Manager (Oracle ADVM) information

Note:

To display information about Oracle ACFS file systems or volumes that are located on nodes in an Oracle Flex ASM configuration, you must connect to the Oracle ASM proxy instance instead of the local Oracle ASM instance. For information about Oracle Flex ASM, refer to *Oracle Automatic Storage Management Administrator's Guide*.

8.47 V$ASM_ACFSSNAPSHOTS

`V$ASM_ACFSSNAPSHOTS` displays snapshot information for every mounted Oracle ACFS.

Column	Datatype	Description
FS_NAME	VARCHAR2(1024)	File system mount point (foreign key to `V$ASM_FILESYSTEM`)
VOL_DEVICE	VARCHAR2(256)	Name of the Oracle ADVM device
SNAP_NAME	VARCHAR2(1024)	Name of the snapshot
CREATE_TIME	DATE	Time when the snapshot was created
TYPE	VARCHAR2(2)	Snapshot type. Possible types are read-only (RO) or read/write (RW).
PARENT	VARCHAR2(1024)	Parent name used to create the snapshot. If the snapshot was created using the mount point as a base, parent name will be NULL. If the snapshot was created using an existing snapshot as the base, the parent name will be the name of the snapshot passed to the `acfsutil snap create -p` operation.
LINK	VARCHAR2(1024)	If link has been set, the path of the link. If unset, NULL.
ADDITIONAL_STORAGE	NUMBER	Equivalent to "storage added to snapshot" output

Column	Datatype	Description
QUOTA	NUMBER	Value of quota. If unset, NULL.
REPL	VARCHAR2(5)	Indicates whether the snapshot is being used for replication (TRUE) or not (FALSE)
STATE	VARCHAR2(14)	The state of the snapshot: • AVAILABLE - Default • DELETE_WAITING - Maps to "delete waiting for last close" • DELETE_IN_PROGRESS - Maps to "delete in progress"
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

See Also:

- *Oracle Automatic Storage Management Administrator's Guide* for more information about Oracle Advanced Cluster File System (Oracle ACFS)
- *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle Advanced Cluster File System (Oracle ACFS) and Oracle ASM Dynamic Volume Manager (Oracle ADVM) information

Note:

To display information about Oracle ACFS file systems or volumes that are located on nodes in an Oracle Flex ASM configuration, you must connect to the Oracle ASM proxy instance instead of the local Oracle ASM instance. For information about Oracle Flex ASM, refer to *Oracle Automatic Storage Management Administrator's Guide*.

8.48 V$ASM_ACFSTAG

V$ASM_ACFSTAG displays every file or directory that has a tag and its tag name for every mounted Oracle ACFS.

Column	Datatype	Description
TAG_NAME	VARCHAR2(32)	Tag name on file or directory
FS_NAME	VARCHAR2(1024)	File system mount point

Column	Datatype	Description
PATH_NAME	VARCHAR2(4096)	Complete file path name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

See Also:

- *Oracle Automatic Storage Management Administrator's Guide* for more information about Oracle Advanced Cluster File System (Oracle ACFS)
- *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle Advanced Cluster File System (Oracle ACFS) and Oracle ASM Dynamic Volume Manager (Oracle ADVM) information

Note:

To display information about Oracle ACFS file systems or volumes that are located on nodes in an Oracle Flex ASM configuration, you must connect to the Oracle ASM proxy instance instead of the local Oracle ASM instance. For information about Oracle Flex ASM, refer to *Oracle Automatic Storage Management Administrator's Guide*.

8.49 V$ASM_ACFSVOLUMES

V$ASM_ACFSVOLUMES displays information about mounted Oracle ACFS volumes, correlated with V$ASM_FILESYSTEM.

Column	Datatype	Description
FS_NAME	VARCHAR2(1024)	File system mount point (foreign key to V$ASM_FILESYSTEM)
VOL_DEVICE	VARCHAR2(256)	Name of the Oracle ADVM device
VOL_LABEL	VARCHAR2(64)	Volume label (optional name) assigned through mkfs/acfsformat; NULL if no name exists
PRIMARY_VOL	VARCHAR2(5)	Indicates whether the volume is the primary volume for the file system (TRUE) or not (FALSE)
TOTAL_MB	NUMBER	Size of the volume device (in megabytes)
FREE_MB	NUMBER	Available space on the volume device (in megabytes)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

See Also:

- "V$ASM_FILESYSTEM"
- *Oracle Automatic Storage Management Administrator's Guide* for more information about Oracle Advanced Cluster File System (Oracle ACFS)
- *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle Advanced Cluster File System (Oracle ACFS) and Oracle ASM Dynamic Volume Manager (Oracle ADVM) information

Note:

To display information about Oracle ACFS file systems or volumes that are located on nodes in an Oracle Flex ASM configuration, you must connect to the Oracle ASM proxy instance instead of the local Oracle ASM instance. For information about Oracle Flex ASM, refer to *Oracle Automatic Storage Management Administrator's Guide*.

8.50 V$ASM_ALIAS

In an Oracle Automatic Storage Management (Oracle ASM) instance, V$ASM_ALIAS displays one row for every alias present in every disk group mounted by the Oracle ASM instance.

Column	Datatype	Description
NAME	VARCHAR2(70)	Oracle ASM alias or alias directory name
GROUP_NUMBER	NUMBER	Owning disk group number of the alias (foreign key to the V$ASM_DISKGROUP view)
FILE_NUMBER	NUMBER	Oracle ASM file number of the alias (foreign key to the V$ASM_FILE view)
FILE_INCARNATION	NUMBER	Oracle ASM file incarnation number for the alias
ALIAS_INDEX	NUMBER	Alias entry number for the alias

Column	Datatype	Description
ALIAS_INCARNATION	NUMBER	Incarnation number for the parent of the alias
PARENT_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and an alias entry number in the low-order 24 bits (number of the directory containing the alias)
REFERENCE_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and an alias entry number in the low-order 24 bits (number of the directory describing the current entry)
ALIAS_DIRECTORY	VARCHAR2(1)	Indicates whether the alias is to a directory (Y) or to an Oracle ASM file (N)
SYSTEM_CREATED	VARCHAR2(1)	Indicates whether the alias is system created (Y) or user created (N)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.51 V$ASM_ATTRIBUTE

V$ASM_ATTRIBUTE displays one row for each attribute defined. In addition to attributes specified by CREATE DISKGROUP and ALTER DISKGROUP statements, the view may show other attributes that are created automatically.

Note that attributes are only displayed for disk groups where COMPATIBLE.ASM is set to 11.1 or higher.

Column	Datatype	Description
NAME	VARCHAR2(256)	Full name of the attribute
VALUE	VARCHAR2(256)	Value of the attribute
GROUP_NUMBER	NUMBER	Number of the disk group in which this attribute exists (composite primary key)
ATTRIBUTE_INDEX	NUMBER	Number of this attribute in the disk group (composite primary key)
ATTRIBUTE_INCARNATION	NUMBER	Incarnation number for this attribute (composite primary key)
READ_ONLY	VARCHAR2(7)	Indicates whether the attribute is read-only (Y) or not (N)
SYSTEM_CREATED	VARCHAR2(7)	Indicates whether this is a system-created attribute (Y) or not (N)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

Note:

In an Oracle Database instance, this view returns 0 rows when queried from a PDB.

See Also:

- *Oracle Automatic Storage Management Administrator's Guide* for more information about viewing Oracle ASM disk group attributes using this view
- *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.52 V$ASM_AUDIT_CLEANUP_JOBS

In an Oracle Automatic Storage Management (Oracle ASM) instance, V$ASM_AUDIT_CLEANUP_JOBS displays information about the configured audit trail purge jobs.

In a database instance, V$ASM_AUDIT_CLEANUP_JOBS displays no rows.

Column	Datatype	Description
JOB_NAME	VARCHAR2(64)	Name of the audit trail purge job
JOB_STATUS	VARCHAR2(64)	Current status of the audit trail purge job (ENABLED) or (DISABLED)
AUDIT_TRAIL	VARCHAR2(64)	Audit trail for which the audit trail purge job is configured: OS AUDIT TRAIL and UNIFIED AUDIT TRAIL
JOB_FREQUENCY	NUMBER	Frequency at which the audit trail purge job runs
USE_TIMESTAMP	VARCHAR2(64)	Indicates whether the audit trail purge job is configured to use the last archive timestamp (TRUE) or not (FALSE)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.53 V$ASM_AUDIT_CONFIG_PARAMS

In an Oracle Automatic Storage Management (Oracle ASM) instance, V$ASM_AUDIT_CONFIG_PARAMS displays information about the currently configured audit trail properties that are used by the DBMS_AUDIT_MGMT package.

In a database instance, V$ASM_AUDIT_CONFIG_PARAMS displays no rows.

Column	Datatype	Description
PARAMETER_NAME	VARCHAR2(64)	Name of the property
PARAMETER_VALUE	VARCHAR2(64)	Value of the property
AUDIT_TRAIL	VARCHAR2(64)	Audit trails for which the property is configured: OS AUDIT TRAIL and UNIFIED AUDIT TRAIL
PARAMETER_UNIT	VARCHAR2(64)	Provides description of units of audit properties (file size in KB and file age in day(s))
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

> **See Also:**
>
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_AUDIT_MGMT` package
> - *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.54 V$ASM_AUDIT_LAST_ARCH_TS

In an Oracle Automatic Storage Management (Oracle ASM) instance, `V$ASM_AUDIT_LAST_ARCH_TS` displays information about the last archive timestamps set for audit trail cleanup or purges.

In a database instance, `V$ASM_AUDIT_LAST_ARCH_TS` displays no rows.

Column	Datatype	Description
`AUDIT_TRAIL`	`VARCHAR2(64)`	Audit trail for which the last archive timestamp applies: `OS AUDIT TRAIL` and `UNIFIED AUDIT TRAIL`
`LAST_ARCHIVE_TS`	`TIMESTAMP(6) WITH TIME ZONE`	Timestamp of the last audit file that has been archived
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always `0`.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.55 V$ASM_CLIENT

In an Oracle Automatic Storage Management (Oracle ASM) instance, `V$ASM_CLIENT` identifies databases using disk groups managed by the Oracle ASM instance.

In a database instance, `V$ASM_CLIENT` displays information about the Oracle ASM instance if the database has any open Oracle ASM files.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Number of the disk group being used by the database instance (foreign key to the V$ASM_DISKGROUP view). When a client is connected to an Oracle ASM instance, but is not currently using any disk groups, V$ASM_CLIENT.GROUP_NUMBER contains 0. When the Cluster Ready Services Daemon (CRSD) or Cluster Synchronization Services (OCSSD) connects to the Oracle ASM instance, this will represent the number of the disk group used for their OCR and voting files respectively.
INSTANCE_NAME	VARCHAR2(64)	Identifier for the database instance client When CRSD or OCSSD has opened its files in the disk group mounted by the Oracle ASM instance, this will contain the node name where CRSD or OCSSD is running.
DB_NAME	VARCHAR2(8)	Unique database name of the database client instance When CRSD has opened the Oracle Cluster Registry (OCR) file in the disk group mounted by the Oracle ASM instance, DB_NAME will contain _OCR. When OCSSD has opened the voting file in the disk group mounted by the Oracle ASM instance, DB_NAME will contain _CSS.
CLUSTER_NAME	VARCHAR2(31)	Name of the cluster
STATUS	VARCHAR2(12)	Status of the client connection: • CONNECTED - Database instance client has an active connection to the Oracle ASM instance • DISCONNECTED - Database instance client normally ended its connection to the Oracle ASM instance • BROKEN - Connection with the database instance client terminated in a nonstandard way When CRSD or OCSSD has opened its files in the disk group mounted by the Oracle ASM instance, it will report Connected as status.
SOFTWARE_VERSION	VARCHAR2(60)	Software version number of the database or Oracle ASM instance for the selected disk group connection
COMPATIBLE_VERSION	VARCHAR2(60)	Compatibility setting of the database or Oracle ASM instance for the selected disk group connection The value will be – when CRSD or OCSSD has opened its files in the disk group mounted by the Oracle ASM instance.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

Note:

In an Oracle Database instance, this view returns 0 rows when queried from a PDB.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.56 V$ASM_DBCLONE_INFO

`V$ASM_DBCLONE_INFO` shows the relationship between the parent database and point-in-time database clones.

Column	Datatype	Description
`GROUP_NUMBER`	`NUMBER`	Disk group number
`DBCLONE_NAME`	`VARCHAR2(128)`	Name of the point-in-time database clone
`MIRRORCOPY_NAME`	`VARCHAR2(128)`	Name of the mirror copy associated with the database clone
`DBCLONE_STATUS`	`VARCHAR2(128)`	Status of the database clone. Possible values: • `PREPARING` — The process to prepare the database for splitting has started, but the database is not yet ready to be split. • `PREPARED` — The preparation process is complete and the database is ready to be split. • `SPLITTING` — The process to split the database files has started. • `SPLIT COMPLETED` — The database has been split. • `DROPPING` — The process to drop the prepared database clone has started. • `FAILED` — The clone operation has failed. The incomplete clone will be dropped.
`PARENT_DBNAME`	`VARCHAR2(128)`	Name of the parent database
`PARENT_FILEGROUP_NAME`	`VARCHAR2(128)`	Name of the file group associated with the parent database
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for information about point-in-time database clones

8.57 V$ASM_DISK

V$ASM_DISK displays one row for every disk discovered by the Oracle Automatic Storage Management (Oracle ASM) instance, including disks that are not part of any disk group.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Number of the disk group containing the disk (foreign key to the V$ASM_DISKGROUP view)
DISK_NUMBER	NUMBER	Number assigned to the disk within its disk group
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and a disk number in the low-order 24 bits (for efficient access to the view)
INCARNATION	NUMBER	Incarnation number for the disk
MOUNT_STATUS	VARCHAR2(7)	Per-instance status of the disk relative to group mounts: • MISSING - Oracle ASM metadata indicates that the disk is known to be part of the Oracle ASM disk group but no disk in the storage system was found with the indicated name • CLOSED - Disk is present in the storage system but is not being accessed by Oracle ASM • OPENED - Disk is present in the storage system and is being accessed by Oracle ASM. This is the normal state for disks in a database instance which are part of a disk group being actively used by the instance. • CACHED - Disk is present in the storage system and is part of a disk group being accessed by the Oracle ASM instance. This is the normal state for disks in an Oracle ASM instance which are part of a mounted disk group. • IGNORED - Disk is present in the system but is ignored by Oracle ASM because of one of the following: – The disk is detected by the system library but is ignored because an Oracle ASM library discovered the same disk – Oracle ASM has determined that the membership claimed by the disk header is no longer valid • CLOSING - Oracle ASM is in the process of closing this disk

Column	Datatype	Description
HEADER_STATUS	VARCHAR2(12)	Per-instance status of the disk as seen by discovery: • UNKNOWN - Oracle ASM disk header has not been read • CANDIDATE - Disk is not part of a disk group and may be added to a disk group with the ALTER DISKGROUP statement • INCOMPATIBLE - Version number in the disk header is not compatible with the Oracle ASM software version • PROVISIONED - Disk is not part of a disk group and may be added to a disk group with the ALTER DISKGROUP statement. The PROVISIONED header status is different from the CANDIDATE header status in that PROVISIONED implies that an additional platform-specific action has been taken by an administrator to make the disk available for Oracle ASM. • MEMBER - Disk is a member of an existing disk group. No attempt should be made to add the disk to a different disk group. The ALTER DISKGROUP statement will reject such an addition unless overridden with the FORCE option. • FORMER - Disk was once part of a disk group but has been dropped cleanly from the group. It may be added to a new disk group with the ALTER DISKGROUP statement. • CONFLICT - Oracle ASM disk was not mounted due to a conflict • FOREIGN - Disk contains data created by an Oracle product other than Oracle ASM. This includes data files, logfiles, and OCR disks.
MODE_STATUS	VARCHAR2(7)	Global status about which kinds of I/O requests are allowed to the disk: • ONLINE - Disk is online and operating normally. Reads and writes are attempted when the disk is mounted. Reads are attempted as part of disk discovery. • OFFLINE - Disk is offline and access to data is not permitted. Reads and writes are not attempted. An offline disk remains logically part of its disk group. • SYNCING - Disk is offline for reads, but online for writes. Oracle ASM is resyncing stale data on the disk. See V$ASM_OPERATION to view resync progress.
STATE	VARCHAR2(8)	Global state of the disk with respect to the disk group: • UNKNOWN - Oracle ASM disk state is not known (typically the disk is not mounted) • NORMAL - Disk is online and operating normally • ADDING - Disk is being added to a disk group, and is pending validation by all instances that have the disk group mounted • DROPPING - Disk has been manually taken offline and space allocation or data access for the disk halts. Rebalancing will commence to relocate data off the disks to other disks in the disk group. Upon completion of the rebalance, the disk is expelled from the group. • HUNG - Disk drop operation cannot continue because there is insufficient space to relocate the data from the disk being dropped • FORCING - Disk is being removed from the disk group without attempting to offload its data. The data will be recovered from redundant copies, where possible.

Column	Datatype	Description
REDUNDANCY	VARCHAR2(7)	Hardware redundancy of the disk: • UNKNOWN • UNPROT • MIRROR • PARITY **Note:** This column is valid only if an ASMLIB is present that supports returning hardware redundancy information. This column is not related to the redundancy of the disk group of which the disk is a member.
LIBRARY	VARCHAR2(64)	Name of the library that discovered the disk
OS_MB	NUMBER	Size of the disk (in megabytes) as reported by the host operating system
TOTAL_MB	NUMBER	Total capacity of the disk (in megabytes)
FREE_MB	NUMBER	Unused capacity of the disk (in megabytes)
HOT_USED_MB[1]	NUMBER	Number of used megabytes in the hot region
COLD_USED_MB[1]	NUMBER	Number of used megabytes in the cold region
NAME	VARCHAR2(30)	Name of the disk
FAILGROUP	VARCHAR2(30)	Name of the failure group containing the disk
LABEL	VARCHAR2(31)	Disk label portion of the name returned by discovery
PATH	VARCHAR2(256)	Operating system path name portion of the name returned by discovery
UDID	VARCHAR2(64)	Unique Device ID portion of the name returned by discovery
PRODUCT	VARCHAR2(32)	Name of the manufacturer and the name of the product. All disks with the same product id will have the same performance and reliability characteristics.
CREATE_DATE	DATE	Date and time when the disk was added to the disk group
MOUNT_DATE	DATE	Date and time when the disk was mounted by the first instance
REPAIR_TIMER	NUMBER	Seconds remaining until the disk is automatically dropped (0 if not failed)
READS	NUMBER	Total number of I/O read requests for the disk
WRITES	NUMBER	Total number of I/O write requests for the disk
READ_ERRS	NUMBER	Total number of failed I/O read requests for the disk
WRITE_ERRS	NUMBER	Total number of failed I/O write requests for the disk
READ_TIMEOUT	NUMBER	Number of read I/Os that are timed out
WRITE_TIMEOUT	NUMBER	Number of write I/Os that are timed out
READ_TIME	NUMBER	Total I/O time (in seconds) for read requests for the disk if the TIMED_STATISTICS initialization parameter is set to true (0 if set to false)
WRITE_TIME	NUMBER	Total I/O time (in seconds) for write requests for the disk if the TIMED_STATISTICS initialization parameter is set to true (0 if set to false)
BYTES_READ	NUMBER	Total number of bytes read from the disk
BYTES_WRITTEN	NUMBER	Total number of bytes written to the disk

Column	Datatype	Description
PREFERRED_READ	VARCHAR2(1)	Status of the preferred read failure group: • U - Disk group has no preferred read failure group • Y - Disk is a preferred read disk • N - Disk is not a preferred read disk For a disk group with one or more preferred read failure groups, if the disk is in one of the preferred read failure groups, the value of this column is Y; otherwise it is N.
HASH_VALUE	NUMBER	A unique hash value for an Oracle ASM disk, computed using the Oracle ASM disk name (as specified by NAME column in v$asm_disk) and the Oracle ASM disk group name (as specified by NAME column in v$asm_diskgroup).
HOT_READS[1]	NUMBER	This column is not meaningful and its value is always 0
HOT_WRITES[1]	NUMBER	This column is not meaningful and its value is always 0
HOT_BYTES_READ[1]	NUMBER	This column is not meaningful and its value is always 0
HOT_BYTES_WRITTEN[1]	NUMBER	This column is not meaningful and its value is always 0
COLD_READS[1]	NUMBER	Number of reads from the disk
COLD_WRITES[1]	NUMBER	Number of writes to the disk
COLD_BYTES_READ[1]	NUMBER	Number of bytes read from the disk
COLD_BYTES_WRITTEN[1]	NUMBER	Number of bytes written to the disk
VOTING_FILE	VARCHAR2(1)	Indicates whether the disk contains a voting file (Y) or not (N)
SECTOR_SIZE	NUMBER	Physical block size (in bytes)
LOGICAL_SECTOR_SIZE	NUMBER	Shows the logical sector size value of the disk in bytes. This is the smallest possible I/O that can be done by the disk. If the value of the LOGICAL_SECTOR_SIZE column is 512, while the value in the SECTOR_SIZE column is 4096, then the disk supports 512 sector size emulation. This means the disk can be used for both 512 native and 4096 native disk groups.
FAILGROUP_TYPE	VARCHAR2(7)	Type of the failure group: • REGULAR • QUORUM
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.
THIN_PROVISION_CAPABLE	VARCHAR2(1)	Indicates whether the disk supports Storage Thin Provisioning (Y) or not (N)
DATA_INTEGRITY_CAPABLE	VARCHAR2(1)	Indicates whether the disk supports the Data Integrity feature (Y) or not (N)
SITE_NAME	VARCHAR2(30)	The name of the site to which the specific disk belongs
SITE_GUID	VARCHAR2(33)	The GUID for the site to which the specific disk belongs

Column	Datatype	Description
FAILGROUP_LABEL	VARCHAR2(30)	This is the suggested name for the failure group to which the disk belongs, as returned by discovery
SITE_LABEL	VARCHAR2(30)	This is the suggested name for the site to which the disk belongs, as returned by discovery
SITE_STATUS	VARCHAR2(11)	This column is populated only for disks in Oracle ASM extended disk groups. The site status is computed after every Partnership and Status Table (PST) refresh or when the PST is read from disks into memory. The possible states include: • UNKNOWN: This is the state before any checks have been performed. • UNAVAILABLE: This is the state when all the disks in the site are offline. • COMPROMISED: The state when enough disks or PST copies are offline, such that the site can no longer provide data availability. • AVAILABLE: The state when there is enough redundancy within the site to provide data availability in case another site becomes compromised or unavailable.

[1] Intelligent Data Placement is desupported starting with Oracle Database 21c. As a result, the individual values for the HOT_USED_MB and COLD_USED_MB columns are not meaningful. However, the sum of the HOT_USED_MB and COLD_USED_MB values represents the total number of used megabytes on the disk. Also, the HOT_READS, HOT_WRITES, HOT_BYTES_READ, and HOT_BYTES_WRITTEN columns are no longer meaningful and always return 0, and the COLD_READS, COLD_WRITES, COLD_BYTES_READ, and COLD_BYTES_WRITTEN columns return statistics for the entire disk.

Note:

The GROUP_NUMBER and DISK_NUMBER columns will only be valid if the disk is part of a disk group which is currently mounted by the instance. Otherwise, GROUP_NUMBER will be 0, and DISK_NUMBER will be a unique value with respect to the other disks that also have a group number of 0.

Note:

In an Oracle Database instance, this view returns 0 rows when queried from a PDB.

See Also:

Oracle Automatic Storage Management Administrator's Guide for additional information about using views to display Oracle ASM information

8.58 V$ASM_DISK_IOSTAT

V$ASM_DISK_IOSTAT displays information about disk I/O statistics for each Oracle Automatic Storage Management (Oracle ASM) client.

If this view is queried from the database instance, only the rows for that instance are shown.

Column	Datatype	Description
INSTNAME	VARCHAR2(64)	Identifier for the DB/ADVM instance client
DBNAME	VARCHAR2(8)	Unique database name (DB_UNIQUE_NAME)
CLUSTERNAME	VARCHAR2(31)	Name of the cluster
GROUP_NUMBER	NUMBER	Number of the disk group containing the disk
DISK_NUMBER	NUMBER	Number assigned to the disk within its disk group
FAILGROUP	VARCHAR2(30)	Name of the failure group to which the disk belongs
SITE_NAME	VARCHAR2(30)	This is the name of the site to which the disk belongs
READS	NUMBER	Total number of I/O read requests for the disk
WRITES	NUMBER	Total number of I/O write requests for the disk
READ_ERRS	NUMBER	Total number of failed I/O read requests for the disk
WRITE_ERRS	NUMBER	Total number of failed I/O write requests for the disk
READ_TIMEOUT	NUMBER	Number of read I/Os that are timed out
WRITE_TIMEOUT	NUMBER	Number of write I/Os that are timed out
READ_TIME	NUMBER	Total I/O time (in seconds) for read requests for the disk if the TIMED_STATISTICS initialization parameter is set to TRUE (0 if set to FALSE).
WRITE_TIME	NUMBER	Total I/O time (in seconds) for write requests for the disk if the TIMED_STATISTICS initialization parameter is set to TRUE (0 if set to FALSE)
BYTES_READ	NUMBER	Total number of bytes read from the disk
BYTES_WRITTEN	NUMBER	Total number of bytes written from the disk
HOT_READS[1]	NUMBER	This column is not meaningful and its value is always 0
HOT_WRITES[1]	NUMBER	This column is not meaningful and its value is always 0
HOT_BYTES_READ[1]	NUMBER	This column is not meaningful and its value is always 0
HOT_BYTES_WRITTEN[1]	NUMBER	This column is not meaningful and its value is always 0
COLD_READS[1]	NUMBER	Number of reads from the disk
COLD_WRITES[1]	NUMBER	Number of writes to the disk
COLD_BYTES_READ[1]	NUMBER	Number of bytes read from the disk
COLD_BYTES_WRITTEN[1]	NUMBER	Number of bytes written to the disk

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

1 Intelligent Data Placement is desupported starting with Oracle Database 21c. As a result, the HOT_READS, HOT_WRITES, HOT_BYTES_READ, and HOT_BYTES_WRITTEN columns are no longer meaningful and always return 0, and the COLD_READS, COLD_WRITES, COLD_BYTES_READ, and COLD_BYTES_WRITTEN columns return statistics for the entire disk.

Note:

In an Oracle Database instance, this view returns 0 rows when queried from a PDB.

See Also:

Oracle Automatic Storage Management Administrator's Guide for additional information about using views to display Oracle ASM information

8.59 V$ASM_DISK_STAT

V$ASM_DISK_STAT displays performance statistics in the same way that V$ASM_DISK does, but without performing discovery of new disks

This results in a less expensive operation. However, since discovery is not performed, the output of this view does not include any data about disks that are new to the system.

The columns for V$ASM_DISK_STAT are the same as those for V$ASM_DISK.

Note:

In an Oracle Database instance, this view returns 0 rows when queried from a PDB.

See Also:

"V$ASM_DISK"

8.60 V$ASM_DISKGROUP

V$ASM_DISKGROUP displays one row for every Oracle Automatic Storage Management (Oracle ASM) disk group discovered by the Oracle ASM instance on the node.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Cluster-wide number assigned to the disk group (primary key)
NAME	VARCHAR2(30)	Name of the disk group
SECTOR_SIZE	NUMBER	Physical block size (in bytes)
LOGICAL_SECTOR_SIZE	NUMBER	This column represents the logical sector size value of the disk group in bytes. This is the smallest possible I/O that can be done in this disk group. Any I/O smaller than the logical sector size will cause an assert in the code. If the value of the LOGICAL_SECTOR_SIZE column is 512, while the value in the SECTOR_SIZE column is 4096, then the disk group supports 512 sector size emulation. This means that I/O operations can be both 512 or 4096 aligned. For example, this means that you can have redo log files with a file block size of 512 bytes in this disk group that can be both read and written to, as well as create new redo log files with a file block size of 4096 bytes.
BLOCK_SIZE	NUMBER	Oracle ASM metadata block size (in bytes)
ALLOCATION_UNIT_SIZE	NUMBER	Size of the allocation unit (in bytes)
STATE	VARCHAR2(11)	State of the disk group relative to the instance: • BROKEN - Database instance lost connectivity to the Oracle ASM instance that mounted the disk group • CONNECTED - Disk group is in use by the database instance • DISMOUNTED - Disk group was cleanly dismounted by the Oracle ASM instance following a successful mount • MOUNTED - Instance is successfully serving the disk group to its database clients • QUIESCING - CRSCTL utility attempted to dismount a disk group that contains the Oracle Cluster Registry (OCR). The disk group cannot be dismounted until Cluster Ready Services (CRS) exits, because the disk group contains the OCR. • RESTRICTED - A disk group mounted in this mode can only be seen by this Oracle ASM instance for maintenance purposes • UNKNOWN - Oracle ASM instance has never attempted to mount the disk group
TYPE	VARCHAR2(6)	Redundancy type for the disk group: • EXTEND • EXTERN • FLEX • HIGH • NORMAL
TOTAL_MB	NUMBER	Total capacity of the disk group, excluding that of quorum disks (in megabytes)
FREE_MB	NUMBER	Unused capacity of the disk group (in megabytes)

Column	Datatype	Description
HOT_USED_MB[1]	NUMBER	Number of used megabytes in the hot region
COLD_USED_MB[1]	NUMBER	Number of used megabytes in the cold region
REQUIRED_MIRROR_FREE_MB	NUMBER	Amount of space that is required to be available in a given disk group in order to restore redundancy after one or more disk failures. The amount of space displayed in this column takes mirroring effects into account.
USABLE_FILE_MB	NUMBER	Amount of free space that can be safely utilized taking mirroring into account and yet be able to restore redundancy after a disk failure
OFFLINE_DISKS	NUMBER	Number of disks in the disk group that are currently offline
COMPATIBILITY	VARCHAR2(60)	Minimum software version required for an Oracle ASM instance to mount this disk group
DATABASE_COMPATIBILITY	VARCHAR2(60)	Minimum software version required for a database instance to use files in this disk group
VOTING_FILES	VARCHAR2(1)	Indicates whether the disk contains voting files (Y) or not (N)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

[1] Intelligent Data Placement is desupported starting with Oracle Database 21c. As a result, the individual values for the HOT_USED_MB and COLD_USED_MB columns are not meaningful. However, the sum of the HOT_USED_MB and COLD_USED_MB values represents the total number of used megabytes in the disk group.

Note:

The GROUP_NUMBER, TOTAL_MB, and FREE_MB columns are only meaningful if the disk group is mounted by the instance. Otherwise, their values will be 0.

See Also:

Oracle Automatic Storage Management Administrator's Guide for additional information about using views to display Oracle ASM information

8.61 V$ASM_DISKGROUP_STAT

V$ASM_DISKGROUP_STAT displays performance statistics in the same way that V$ASM_DISKGROUP does, but without performing discovery of new disk groups.

This results in a less expensive operation. However, since discovery is not performed, the output of this view does not include any data about disk groups that are new to the system.

The columns for V$ASM_DISKGROUP_STAT are the same as those for V$ASM_DISKGROUP.

> **See Also:**
>
> "V$ASM_DISKGROUP"

8.62 V$ASM_ESTIMATE

V$ASM_ESTIMATE displays an estimate of the work involved in execution plans for Oracle Automatic Storage Management (Oracle ASM) disk group rebalance and resync operations.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Oracle ASM disk group number
STATEMENT_ID	VARCHAR2(30)	Value of the optional STATEMENT_ID parameter specified in the EXPLAIN WORK statement
TIMESTAMP	DATE	Date and time when the EXPLAIN WORK statement was issued
EST_WORK	NUMBER	Estimated number of Allocation Units that have to be moved by the operation
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.63 V$ASM_FILE

In an Oracle Automatic Storage Management (Oracle ASM) instance, V$ASM_FILE displays one row for each file in each disk group mounted by the Oracle ASM instance.

For example, if there are three disk groups and five files in each, fifteen rows are displayed (unless the query is qualified with a WHERE clause).

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Number of the disk group containing the file (composite primary key)
FILE_NUMBER	NUMBER	Number of the file within the disk group (composite primary key)
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and a file number in the low-order 24 bits (for efficient access to the view)
INCARNATION	NUMBER	Incarnation number for the file (composite primary key)
BLOCK_SIZE	NUMBER	Block size of the file (in bytes)
BLOCKS	NUMBER	Number of blocks in the file
BYTES	NUMBER	Number of bytes in the file
SPACE	NUMBER	Number of bytes allocated to the file
TYPE	VARCHAR2(64)	Type of the file. Possible values are as follows: • ARCHIVELOG • AUTOBACKUP • BACKUPSET • CHANGETRACKING • CONTROLFILE • DATAFILE • DATAGUARDCONFIG • DUMPSET • FLASHBACK • ONLINELOG • PARAMETERFILE • TEMPFILE • XTRANSPORT
REDUNDANCY	VARCHAR2(6)	Redundancy of the file: • HIGH • MIRROR • PARITY • UNPROT
STRIPED	VARCHAR2(6)	Indicates how the file is striped: • FINE • COARSE
CREATION_DATE	DATE	Date on which the file was created
MODIFICATION_DATE	DATE	Date of the last open/close for writing, rounded back to the nearest hour

Column	Datatype	Description
REDUNDANCY_LOWERED	VARCHAR2(1)	Indicates whether a file has lower redundancy than what was expected (Y) or not (N). Redundancy is said to have been lowered for a file when one or more data extents in that file are not mirrored at the level specified by the administrator. In case of unprotected files, data extents could be missing altogether. Another possible value for this column is (U), which means that it is unknown. This column is deprecated, and it always displays a value of U.
PERMISSIONS	VARCHAR2(16)	Access permissions of the file, in order of user, group, and other
USER_NUMBER	NUMBER	User number
USER_INCARNATION	NUMBER	Incarnation number of the user
USERGROUP_NUMBER	NUMBER	User group number
USERGROUP_INCARNATION	NUMBER	Incarnation number of the user group
PRIMARY_REGION[1]	VARCHAR2(4)	Region used for allocating primary extents: • HOT • COLD
MIRROR_REGION[1]	VARCHAR2(4)	Region for allocating mirrored extents: • HOT • COLD
HOT_READS[1]	NUMBER	This column is not meaningful and its value is always 0
HOT_WRITES[1]	NUMBER	This column is not meaningful and its value is always 0
HOT_BYTES_READ[1]	NUMBER	This column is not meaningful and its value is always 0
HOT_BYTES_WRITTEN[1]	NUMBER	This column is not meaningful and its value is always 0
COLD_READS[1]	NUMBER	Number of reads from the file
COLD_WRITES[1]	NUMBER	Number of writes to the file
COLD_BYTES_READ[1]	NUMBER	Number of bytes read from the file
COLD_BYTES_WRITTEN[1]	NUMBER	Number of bytes written to the file
FILEGROUP_NUMBER	NUMBER	Shows the number of the associated file group
FILEGROUP_INCARNATION	NUMBER	The incarnation number for the file group the file belongs to in a flex redundancy disk group
REMIRROR	VARCHAR2(1)	This column has the value Y when rebalance is needed for the file after a redundancy change in a flex redundancy disk group, N otherwise. A redundancy change can occur when the file is moved to a file group with a different redundancy, or when the redundancy property of the file group is changed. After rebalance is run for the file, the value changes to N.
PARENT_FILNUM	NUMBER	For internal use only.
PARENT_FILNUMINC	NUMBER	For internal use only.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

1 Intelligent Data Placement is desupported starting with Oracle Database 21c. As a result, the PRIMARY_REGION and MIRROR_REGION columns are no longer meaningful. Also, the HOT_READS, HOT_WRITES, HOT_BYTES_READ, and HOT_BYTES_WRITTEN columns are no longer meaningful and always return 0, and the COLD_READS, COLD_WRITES, COLD_BYTES_READ, and COLD_BYTES_WRITTEN columns return statistics for the entire file.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.64 V$ASM_FILEGROUP

V$ASM_FILEGROUP describes the properties of the Oracle Automatic Storage Management (Oracle ASM) File Groups.

In both Oracle ASM and Oracle Database instances, V$ASM_FILEGROUP displays one row for every File Group present in every Disk Group mounted by the Oracle ASM instance. File Groups are only displayed for Disk Groups where COMPATIBLE.ASM is set to 12.2 or higher.

> **Note:**
>
> There will not be an entry for the default File Group.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Number of the Disk Group in which this File Group exists (composite primary key)
FILEGROUP_NUMBER	NUMBER	Number associated to the File Group within its Disk Group (composite primary key)
INCARNATION	NUMBER	Incarnation number for the File Group (composite primary key)
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a Disk Group number in the high-order 8 bits and a File Group number in the low-order 24 bits (for efficient access to the view)
NAME	VARCHAR2(128)	Name of the File Group

Column	Datatype	Description
CLIENT_TYPE	NUMBER	Type of client that the File Group is associated to: • DATABASE • CLUSTER • VOLUME
CLIENT_NAME	VARCHAR2(128)	Name of the client (database, PDB, CDB, cluster, or volume) that the File Group is associated to
GUID	VARCHAR2(32)	If the CLIENT_TYPE is DATABASE: • In a CDB environment, it is the GUID of the PDB or CDB associated with the file group, the same value as the GUID in V$CONTAINERS. • In a non-CDB environment it is the database identifier (DBID) of the database associated with that file group. If the CLIENT_TYPE is VOLUME or CLUSTER, the GUID column is empty.
QUOTAGROUP_NUMBER	NUMBER	Number of the quota group associated with this File Group (foreign key to the V$ASM_QUOTAGROUP view)
QUOTAGROUP_INCARNATION	NUMBER	Incarnation number for the Quota Group
USED_QUOTA_MB	NUMBER	Used quota of the quota group in GB
USER_NUMBER	NUMBER	User number
USER_INCARNATION	NUMBER	Incarnation number of the user
USERGROUP_NUMBER	NUMBER	User group number
USERGROUP_INCARNATION	NUMBER	Incarnation number of the user group
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$ASM_FILEGROUP_PROPERTY"

8.65 V$ASM_FILEGROUP_FILE

V$ASM_FILEGROUP_FILE lists all the Oracle Automatic Storage Management (Oracle ASM) files associated with each File Group.

In both Oracle ASM and Oracle Database instances, V$ASM_FILEGROUP_FILE will display one row for every file associated with a File Group contained in every Disk Group mounted by the instance.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Number of the Disk Group in which this File Group exists
FILEGROUP_NUMBER	NUMBER	Number associated to the File Group within its Disk Group
FILEGROUP_INCARN	NUMBER	Incarnation number for the File Group
FILE_NUMBER	NUMBER	Number associated to the ASM File (same file number as in V$ASM_FILE)
INCARNATION	NUMBER	Incarnation number for the ASM File
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a Disk Group number in the high-order 8 bits and a File number in the low-order 24 bits (for efficient access to the view)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$ASM_FILE"
- "V$ASM_FILEGROUP"

8.66 V$ASM_FILEGROUP_PROPERTY

V$ASM_FILEGROUP_PROPERTY describes all the properties of every Oracle Automatic Storage Management (Oracle ASM) File Group.

In both Oracle ASM and Oracle Database instances, V$ASM_FILEGROUP_PROPERTY will display one row for every property of every file type of every File Group contained in every Disk Group mounted by the instance.

File Group properties are only displayed for File Groups on Disk Groups where COMPATIBLE.ASM is set to 12.2 or higher.

Note:

There will not be an entry for the default File Group.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Number of the Disk Group in which this File Group exists (composite primary key)

Column	Datatype	Description
FILEGROUP_NUMBER	NUMBER	Number associated to the File Group within its Disk Group (composite primary key)
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a Disk Group number in the high-order 8 bits and a Property Number in the low-order 24 bits (for efficient access to the view)
PROPERTY_INDEX	NUMBER	Number of this property in the Disk Group for the File Group (composite primary key)
INCARNATION	NUMBER	Incarnation number for this property (composite primary key)
FILE_TYPE	VARCHAR2(30)	Type of file the property will be applied to: • ARCHIVELOG • ASMPARAMETERFILE • ASMVDRL • ASMVOL • AUDIT_SPILLFILES • AUTOBACKUP • BACKUPSET • CHANGETRACKING • CONTAINER • CONTROLFILE • DATAFILE • DATAGUARDCONFIG • DUMPSET • FLASHBACK • FLASHFILE • KEY_STORE • OCRBACKUP • OCRFILE • ONLINELOG • PARAMETERFILE • TEMPFILE • VOTINGFILE • XTRANSPORT The value can be NULL for properties with a File Group granularity.
NAME	VARCHAR2(64)	Full name of the property. Possible values: • COMPATIBLE.CLIENT • DBCLONE_STATUS • OWNER • PARENT_FILEGROUP_NUMBER • POWER_LIMIT • PRIORITY • REDUNDANCY • STRIPING • USER_GROUP
VALUE	VARCHAR2(256)	Value of the property See *Oracle Automatic Storage Management Administrator's Guide* for information about file group property values.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$ASM_FILEGROUP"

8.67 V$ASM_FILESYSTEM

V$ASM_FILESYSTEM displays information for every mounted Oracle ACFS.

Column	Datatype	Description
FS_NAME	VARCHAR2(1024)	Mount point (primary key)
AVAILABLE_TIME	DATE	Mount time or the time that the file system became available again; NULL if the file system is not available
BLOCK_SIZE	NUMBER	File system block size (in kilobytes)
STATE	VARCHAR2(13)	File system status:: • NOT AVAILABLE • AVAILABLE • OFFLINE - Either the Oracle ASM instance is down, the disk group has been forced dismounted, or less commonly, a metadata I/O failure occurred or serious metadata corruption was detected. In the case of a metadata I/O failure, the file system is also marked as corrupt. An offline file system can only be unmounted; other attempts at access result in errors.
CORRUPT	VARCHAR2(5)	Indicates whether the file system needs the fixer (fsck, acfschkdsk) to be run (TRUE) or not (FALSE)
NUM_VOL	NUMBER	Number of volumes in the file system
TOTAL_SIZE	NUMBER	Total capacity of the file system (in megabytes)
TOTAL_FREE	NUMBER	Total free space in the file system (in megabytes)
TOTAL_SNAP_SPACE_USAGE	NUMBER	Total space used by snapshots (in megabytes)
REPLSTATE	VARCHAR2(7)	Replication status: • NO REPL - Replication is not initialized • PRIMARY - File system is initialized for replication as a primary • STANDBY - File system is initialized for replication as a standby

Column	Datatype	Description
RESIZE_STATE	VARCHAR2(5)	Possible resize states: • NONE - AutoResize not configured • AUTO - Equivalent to AutoResizeEnabled flag • ERROR - Equivalent to AutoResizeError flag
COMPRESS_STATE	VARCHAR2(7)	Compression status of the file system. Possible values: • DISABLED - Compression is not active • ENABLED - Compression is active • PARTIAL - Compression is disabled, but the file system may contain compressed files
FROZEN_STATE	VARCHAR2(5)	Indicates whether the filesystem is frozen (TRUE) or not (FALSE)
ACFS_COMPATIBILITY	VARCHAR2(60)	Oracle Release streams where Oracle ACFS has shipped
METADATA_BLOCK_SIZE	NUMBER	Metadata block size of the file system. Possible values: • 512 • 4096
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.68 V$ASM_OPERATION

In an Oracle Automatic Storage Management (Oracle ASM) instance, V$ASM_OPERATION displays one row for every active Oracle ASM long running operation executing in the Oracle ASM instance.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Disk group number (primary key). This is the foreign key to the V$ASM_DISKGROUP view.

Column	Datatype	Description
OPERATION	CHAR(5)	Type of the operation: • REBAL - Rebalance pending for this group. The disk group is rebalancing. • REMIRROR - Remirror is pending for this group. • SCRUB - Scrubbing is pending for this group. Starting with Oracle Database 12*c*, new queries should use the PASS column instead of this column.
PASS	VARCHAR2(9)	Type of the operation: • COMPACT - Oracle ASM is moving user data closer together, which improves performance by reducing seek distance • PREPARE - Completing work corresponding to the prepare SQL operation. This phase is enabled only for FLEX or EXTENDED redundancy disk groups and COMPATIBLE.ASM must be set to 12.2 or higher. • REBALANCE - Rebalance pending for this group. The disk group is rebalancing. • REBUILD - Restoring the redundancy of forcing disks. Forcing disks are those disks that have been dropped with the FORCE option. • RESILVER - This value appears in Oracle Exadata environments when WriteBack FlashCache is enabled • RESYNC - Resync operation in progress to bring one or more Oracle ASM disks online • SCRUBBING - The disk group is scrubbing. Starting with Oracle Database 12*c*, new queries should use this column instead of the OPERATION column.
STATE	VARCHAR2(4)	State of the operation: • WAIT - No operations running for the group • EST - An estimate is computed on the amount of work to be done for the rebalance • RUN - Operation running for the group • REAP - Operation is being run down • DONE - Displayed for a pass that is complete • ERRS - Operation halted by errors Estimates are computed in parallel in the background while the work is being executed. Thus, the transition from the EST to the RUN state may be extremely fast.
POWER	NUMBER	Power requested for the operation as specified by the ASM_POWER_LIMIT initialization parameter or command syntax. Or, power requested for the operation as specified by the power option of the scrubbing SQL syntax.
ACTUAL	NUMBER	Power allocated to the operation
SOFAR	NUMBER	Number of Allocation Units that are being moved per minute by the operation. Or, the number of Allocation Units that have been scrubbed so far.
EST_WORK	NUMBER	Estimated number of Allocation Units that have to be moved by the operation. Or, the estimated number of Allocation Units that have to be scrubbed by the scrubbing operation.
EST_RATE	NUMBER	Estimated number of Allocation Units that are being moved per minute by the operation

Column	Datatype	Description
EST_MINUTES	NUMBER	Estimated amount of time (in minutes) that the remainder of the operation is expected to take
ERROR_CODE	VARCHAR2(44)	Oracle external error code; NULL if no error
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.69 V$ASM_QUOTAGROUP

V$ASM_QUOTAGROUP displays one row for every Oracle Automatic Storage Management (Oracle ASM) quota group discovered by the Oracle ASM instance on the node.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Number of the disk group containing the quota group (composite primary key)
QUOTAGROUP_NUMBER	NUMBER	Number of the quota group within the disk group (composite primary key)
INCARNATION	NUMBER	Incarnation of the quota group (composite primary key)
NAME	VARCHAR2(30)	Name of the quota group
USED_QUOTA_MB	NUMBER	Used quota of the quota group in GB
QUOTA_LIMIT_MB	NUMBER	Quota limit (capacity) of the quota group in GB
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.70 V$ASM_TEMPLATE

In an Oracle Automatic Storage Management (Oracle ASM) instance, V$ASM_TEMPLATE displays one row for every template present in every disk group mounted by the Oracle ASM instance.

In a database instance, V$ASM_TEMPLATE displays one row for every template present in every disk group mounted by the Oracle ASM instance with which the database instance communicates.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Owning disk group number (foreign key to the V$ASM_DISKGROUP view)
ENTRY_NUMBER	NUMBER	Template number (primary key)
REDUNDANCY	VARCHAR2(6)	Redundancy of the template: • HIGH • MIRROR • PARITY • UNPROT
STRIPE	VARCHAR2(6)	Indicates how the template is striped: • FINE • COARSE
SYSTEM	VARCHAR2(1)	Indicates whether the template is a system template (Y) or not (N)
NAME	VARCHAR2(30)	Name of the template
PRIMARY_REGION[1]	VARCHAR2(4)	Region used for allocating primary extents: • HOT • COLD
MIRROR_REGION[1]	VARCHAR2(4)	Region for allocating mirrored extents: • HOT • COLD
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

1 Intelligent Data Placement is desupported starting with Oracle Database 21c. As a result, the PRIMARY_REGION and MIRROR_REGION columns are no longer meaningful.

> **Note:**
>
> In an Oracle Database instance, this view returns 0 rows when queried from a PDB.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.71 V$ASM_USER

V$ASM_USER displays the effective operating system user names of connected database instances and of file owners.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Oracle ASM disk group number
USER_NUMBER	NUMBER	Oracle ASM internal unique user number
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and a user number in the low-order 24 bits (for efficient access to the view)
INCARNATION	NUMBER	Incarnation number of the user
CLUSTER_ID	VARCHAR2(128)	Oracle ASM cluster ID. The CLUSTER_ID and OS_NAME pair can be used to uniquely identify a user.
OS_ID	VARCHAR2(128)	Operating system user ID
OS_NAME	VARCHAR2(33)	Operating system user name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

> **Note:**
>
> In an Oracle Database instance, this view returns 0 rows when queried from a PDB.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.72 V$ASM_USERGROUP

V$ASM_USERGROUP displays the creator for each Oracle Automatic Storage Management (Oracle ASM) File Access Control group.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Oracle ASM disk group number
USERGROUP_NUMBER	NUMBER	Number of the user group
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and a user group number in the low-order 24 bits (for efficient access to the view)
INCARNATION	NUMBER	Incarnation number of the user group
OWNER_NUMBER	NUMBER	User group owner identified by a unique number
OWNER_INCARNATION	NUMBER	Incarnation number of the user group owner
NAME	VARCHAR2(64)	User group name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

Note:

In an Oracle Database instance, this view returns 0 rows when queried from a PDB.

See Also:

Oracle Automatic Storage Management Administrator's Guide for additional information about using views to display Oracle ASM information

8.73 V$ASM_USERGROUP_MEMBER

V$ASM_USERGROUP_MEMBER displays the members for each Oracle Automatic Storage Management (Oracle ASM) File Access Control group.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Oracle ASM disk group number
MEMBER_NUMBER	NUMBER	Number of the user group member

Column	Datatype	Description
MEMBER_INCARNATION	NUMBER	Incarnation number of the user group member
USERGROUP_NUMBER	NUMBER	User group number
USERGROUP_INCARNATION	NUMBER	Incarnation number of the user group
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

> **Note:**
>
> In an Oracle Database instance, this view returns 0 rows when queried from a PDB.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.74 V$ASM_VOLUME

In an Oracle Automatic Storage Management (Oracle ASM) instance, V$ASM_VOLUME displays information about each Oracle ADVM volume.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Cluster-wide number assigned to the disk group (composite primary key)
VOLUME_NAME	VARCHAR2(30)	Name of the volume
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and a volume number in the low-order 24 bits (for efficient access to the view)
SIZE_MB	NUMBER	Size of the volume (in megabytes)
VOLUME_NUMBER	NUMBER	Number of the Volume within the disk group (composite primary key)
REDUNDANCY	VARCHAR2(6)	Redundancy type for the volume: • UNPROT • HIGH • MIRROR

Column	Datatype	Description
STRIPE_COLUMNS	NUMBER	Number of columns in a stripe set
STRIPE_WIDTH_K	NUMBER	Stripe width of the volume (in kilobytes)
STATE	VARCHAR2(8)	Indicates whether the volume is enabled (ENABLED), disabled (DISABLED), or remote (REMOTE)
FILE_NUMBER	NUMBER	Volume file number
INCARNATION	NUMBER	Volume file incarnation number
DRL_FILE_NUMBER	NUMBER	Volume Dirty Region Logging (DRL) file used for mirrored volumes
RESIZE_UNIT_MB	NUMBER	Volume allocation unit (in megabytes) that a volume can be created
USAGE	VARCHAR2(30)	Optional usage string for the volume
VOLUME_DEVICE	VARCHAR2(256)	OSD path for the volume device
MOUNTPATH	VARCHAR2(1024)	Optional mount path string for the volume
PRIMARY_REGION[1]	VARCHAR2(4)	Region used for allocating primary extents: • HOT • COLD
MIRROR_REGION[1]	VARCHAR2(4)	Region used for allocating mirrored extents: • HOT • COLD
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

1 Intelligent Data Placement is desupported starting with Oracle Database 21c. As a result, the PRIMARY_REGION and MIRROR_REGION columns are no longer meaningful.

> **See Also:**
>
> *Oracle Automatic Storage Management Administrator's Guide* for additional information about using views to display Oracle ASM information

8.75 V$ASM_VOLUME_STAT

In an Oracle Automatic Storage Management (Oracle ASM) instance, V$ASM_VOLUME_STAT displays information about statistics for each Oracle ADVM volume.

Column	Datatype	Description
GROUP_NUMBER	NUMBER	Cluster-wide number assigned to the disk group (composite primary key)

Column	Datatype	Description
VOLUME_NAME	VARCHAR2(30)	Name of the volume
COMPOUND_INDEX	NUMBER	A 32-bit number consisting of a disk group number in the high-order 8 bits and a volume number in the low-order 24 bits (for efficient access to the view)
VOLUME_NUMBER	NUMBER	Number of the Volume within the disk group (composite primary key)
READS	NUMBER	Total number of read requests for this volume
WRITES	NUMBER	Total number of write requests for this volume
READ_ERRS	NUMBER	Total number of failed read I/O operations for this volume
WRITE_ERRS	NUMBER	Total number of failed write I/O operations for this volume
READ_TIME	NUMBER	Total I/O time (in seconds) for read requests for this volume
WRITE_TIME	NUMBER	Total I/O time (in seconds) for write requests for this volume
BYTES_READ	NUMBER	Total number of bytes read for this volume
BYTES_WRITTEN	NUMBER	Total number of bytes written for this volume
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data For this view, the value is always 0.

See Also:

Oracle Automatic Storage Management Administrator's Guide for additional information about using views to display Oracle ASM information

8.76 V$AUTHPOOL_STATS

V$AUTHPOOL_STATS displays statistics for the authentication pool. This pool authenticates user connections when client applications connect to Database Resident Connection Pooling (DRCP).

Column	Datatype	Description
NUM_SRVS	NUMBER	Total number of servers in the authentication pool
NUM_BUSY	NUMBER	Number of busy servers in the authentication pool
NUM_FREE	NUMBER	Number of free servers in the authentication pool
NUM_WAITERS	NUMBER	Number of connections waiting for a server in the authentication pool to become available

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.77 V$AUTO_IM_FEATURES

V$AUTO_IM_FEATURES describes the In-Memory Column Store performance features that are optimized by Automatic In-Memory (AIM).

Column	Datatype	Description
FEATURE_ID	NUMBER	Unique feature ID
DESCRIPTION	VARCHAR2(64)	Feature description. Possible values: • Autonomous Bloom Filter Optimization • Autonomous Join Groups • Autonomous Optimized Arithmetic • Autonomous Vector Optimization
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

8.78 V$AW_AGGREGATE_OP

V$AW_AGGREGATE_OP displays the aggregation operators available in analytic workspaces. You can use this view in an application to provide a list of choices.

Column	Datatype	Description
NAME	VARCHAR2(14)	Keyword for the aggregation operator
LONGNAME	VARCHAR2(30)	Descriptive name for the operator

Column	Datatype	Description
DEFAULT_WEIGHT	NUMBER	Default weight factor for weighted operators
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.79 V$AW_ALLOCATE_OP

V$AW_ALLOCATE_OP displays the allocation operators available in analytic workspaces. You can use this view in an application to provide a list of choices.

Column	Datatype	Description
NAME	VARCHAR2(14)	Keyword for the allocation operator
LONGNAME	VARCHAR2(30)	Descriptive name for the operator
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.80 V$AW_CALC

V$AW_CALC reports on the effectiveness of various caches used by Oracle OLAP during dynamic aggregation.

Column	Datatype	Description
SESSION_ID	NUMBER	A unique numeric identifier for the session.
AGGREGATE_CACHE_HITS	NUMBER	The number of times a dimension member is found in the aggregate cache (a hit). The number of hits for run-time aggregation can be increased by fetching data across the dense dimension
AGGREGATE_CACHE_MISSES	NUMBER	The number of times a dimension member is not found in the aggregate cache and must be read from disk (a miss).
SESSION_CACHE_HITS	NUMBER	The number of times the data is found in the session cache (a hit).
SESSION_CACHE_MISSES	NUMBER	The number of times the data is not found in the session cache (a miss).
POOL_HITS	NUMBER	The number of times the data is found in a page in the OLAP page pool (a hit).

Column	Datatype	Description
POOL_MISSES	NUMBER	The number of times the data is not found in the OLAP page pool (a miss).
POOL_NEW_PAGES	NUMBER	The number of newly created pages in the OLAP page pool that have not yet been written to the workspace LOB.
POOL_RECLAIMED_PAGES	NUMBER	The number of previously unused pages that have been recycled with new data.
CACHE_WRITES	NUMBER	The number of times the data from the OLAP page pool has been written to the database cache.
POOL_SIZE	NUMBER	The number of kilobytes in the OLAP page pool.
CURR_DML_COMMAND	VARCHAR2(64)	The command currently being executed.
PREV_DML_COMMAND	VARCHAR2(64)	The command most recently completed.
AGGR_FUNC_LOGICAL_NA	NUMBER	The number of times the aggregation engine returns a logical NA because the AGGINDEX option is on and the composite tuple does not exist.
AGGR_FUNC_PRECOMPUTE	NUMBER	The number of times the aggregation engine finds a value in a position that it was called to calculate.
AGGR_FUNC_CALCS	NUMBER	The number of times the aggregation engine calculates a parent value based on the values of its children.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.81 V$AW_LONGOPS

V$AW_LONGOPS displays status information about active SQL cursors initiated in an analytic workspace.

Column	Datatype	Description
SESSION_ID	NUMBER	Identifier for the session in which the fetch is executing. This table can be joined with V$SESSION to obtain the user name.
CURSOR_NAME	VARCHAR2(64)	Name assigned to the cursor
COMMAND	VARCHAR2(17)	Command that is actively fetching data from relational tables: • QUERY • FETCH • IMPORT • EXECUTE • UPDATE • SOLVE • CLEAR • LOAD CUBE • LOAD DIMENSION • DIMENSION COMPILE

Column	Datatype	Description
STATUS	VARCHAR2(9)	Status of the current operation: • EXECUTING - Command has begun executing • FETCHING - Data is being fetched into the analytic workspace • FINISHED - Command has finished executing. This status appears very briefly before the record disappears from the table.
ROWS_PROCESSED	NUMBER	Number of rows already inserted, updated, or deleted
SEQ_NUMBER	NUMBER	Sequence number in the Cube Build log
SQL_ID	VARCHAR2(13)	SQL ID of the statement
TARGET	VARCHAR2(64)	Operated object name
TARGET_DESC	VARCHAR2(64)	A brief description of the operated object
START_TIME	DATE	Time the command started executing
LAST_UPDATE_TIME	DATE	Last updated time
ELAPSED_SECONDS	NUMBER	Number of seconds between START_TIME and LAST_UPDATE_TIME
SOFAR	NUMBER	Number of units so far
TOTALWORK	NUMBER	Total number of units
UNITS	VARCHAR2(6)	Units description: • ROWS • NODES • VALUES
MESSAGE	VARCHAR2(512)	Message for the user
USERNAME	VARCHAR2(32)	User name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.82 V$AW_OLAP

V$AW_OLAP provides a record of active sessions and their use with analytic workspaces.

A row is generated whenever an analytic workspace is created or attached. The first row for a session is created when the first command is issued. It identifies the SYS.EXPRESS workspace, which is attached automatically to each session. Rows related to a particular analytic workspace are deleted when the workspace is detached from the session or the session ends.

Column	Datatype	Description
SESSION_ID	NUMBER	A unique numeric identifier for a session

Column	Datatype	Description
AW_NUMBER	NUMBER	A unique numeric identifier for an analytic workspace. To get the name of the analytic workspace, join this column to the AW_NUMBER column of the USER_AWS view or to the AWSEQ# column of the AW$ table.
ATTACH_MODE	VARCHAR2(10)	READ ONLY or READ WRITE
GENERATION	NUMBER	The generation of an analytic workspace. Each UPDATE creates a new generation. Sessions attaching the same workspace between UPDATE commands share the same generation.
TEMP_SPACE_PAGES	NUMBER	The number of pages stored in temporary segments for the analytic workspace.
TEMP_SPACE_READS	NUMBER	The number of times data has been read from a temporary segment and not from the page pool.
LOB_READS	NUMBER	The number of times data has been read from the table where the analytic workspace is stored (the permanent LOB).
POOL_CHANGED_PAGES	NUMBER	The number of pages in the page pool that have been modified in this analytic workspace.
POOL_UNCHANGED_PAGES	NUMBER	The number of pages in the page pool that have not been modified in this analytic workspace.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.83 V$AW_SESSION_INFO

V$AW_SESSION_INFO provides information about each active session.

A transaction is a single exchange between a client session and Oracle OLAP. Multiple commands can execute within a single transaction.

Column	Datatype	Description
SESSION_ID	NUMBER	A unique numeric identifier for a session
CLIENT_TYPE	VARCHAR2(64)	OLAP
SESSION_STATE	VARCHAR2(64)	TRANSACTING, NOT_TRANSACTING, EXCEPTION_HANDLING, CONSTRUCTING, CONSTRUCTED, DECONSTRUCTING, or DECONSTRUCTED
SESSION_HANDLE	NUMBER	The session identifier
USERID	VARCHAR2(64)	The database user name under which the session opened
TOTAL_TRANSACTION	NUMBER	The total number of transactions executed within the session; this number provides a general indication of the level of activity in the session
TRANSACTION_TIME	NUMBER	The elapsed time in milliseconds of the mostly recently completed transaction

Column	Datatype	Description
TOTAL_TRANSACTION_TIME	NUMBER	The total elapsed time in milliseconds in which transactions were being executed
AVERAGE_TRANSACTION_TIME	NUMBER	The average elapsed time in milliseconds to complete a transaction
TRANSACTION_CPU_TIME	NUMBER	The total CPU time in milliseconds used to complete the most recent transaction
TOTAL_TRANSACTION_CPU_TIME	NUMBER	The total CPU time used to execute all transactions in this session; this total does not include transactions that are currently in progress
AVERAGE_TRANSACTION_CPU_TIME	NUMBER	The average CPU time to complete a transaction; this average does not include transactions that are currently in progress
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.84 V$BACKUP

V$BACKUP displays the backup status of all online data files.

Column	Datatype	Description
FILE#	NUMBER	File identifier
STATUS	VARCHAR2(18)	File status: NOT ACTIVE, ACTIVE (backup in progress), OFFLINE NORMAL, or description of an error. NOT ACTIVE indicates that the file is not currently in backup mode (that is, an ALTER TABLESPACE ... BEGIN BACKUP or ALTER DATABASE BEGIN BACKUP statement has not been issued), whereas ACTIVE indicates that the file is currently in backup mode.
CHANGE#	NUMBER	System change number when backup started
TIME	DATE	Time the backup started
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.85 V$BACKUP_ARCHIVELOG_DETAILS

V$BACKUP_ARCHIVELOG_DETAILS contains information about all restorable archive logs.

It will include all archived logs backed up in a backup set or proxy copies.

Column	Datatype	Description
BTYPE	CHAR(9)	Backup type container, either BACKUPSET or PROXYCOPY
BTYPE_KEY	NUMBER	Unique identifier for the backup type. For BACKUPSET, it is BS_KEY.
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp
ID1	NUMBER	If BACKUPSET, it contains SET_STAMP If PROXYCOPY, it is RECID from the control file
ID2	NUMBER	If BACKUPSET, it contains SET_COUNT If PROXYCOPY, it is STAMP
THREAD#	NUMBER	Thread number
SEQUENCE#	NUMBER	Sequence number
RESETLOGS_CHANGE#	NUMBER	Resetlogs change SCN
RESETLOGS_TIME	DATE	Resetlogs change time
FIRST_CHANGE#	NUMBER	First change SCN
FIRST_TIME	DATE	First change time
NEXT_CHANGE#	NUMBER	Next change SCN
NEXT_TIME	DATE	Next change time
FILESIZE	NUMBER	File size
COMPRESSION_RATIO	NUMBER	The ratio between the total blocks in the archive log and the blocks that RMAN backed up. This is *not* the ratio from the AS COMPRESSED BACKUPSET clause of the BACKUP command.
FILESIZE_DISPLAY	VARCHAR2(4000)	Same value as the FILESIZE column, but converted to a user-displayable format, for example *n*M, *n*G, *n*T, *n*P, and so on
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.86 V$BACKUP_ARCHIVELOG_SUMMARY

V$BACKUP_ARCHIVELOG_SUMMARY provides archive log summary information based on archive logs in the backup set or on proxy copies.

Column	Datatype	Description
NUM_FILES_BACKED	NUMBER	Number of files backed up
NUM_DISTINCT_FILES_BACKED	NUMBER	Number of distinct archive log files backed up
MIN_FIRST_CHANGE#	NUMBER	Lowest SCN range value
MAX_NEXT_CHANGE#	NUMBER	Highest SCN range value
MIN_FIRST_TIME	DATE	Lowest SCN range time
MAX_NEXT_TIME	DATE	Highest SCN range time
INPUT_BYTES	NUMBER	Total input bytes read
OUTPUT_BYTES	NUMBER	Output size of backups
COMPRESSION_RATIO	NUMBER	The ratio between the total blocks in the archive log and the blocks that RMAN backed up. This is *not* the ratio from the AS COMPRESSED BACKUPSET clause of the BACKUP command.
INPUT_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for input bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for output bytes
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.87 V$BACKUP_ASYNC_IO

V$BACKUP_ASYNC_IO displays performance information about ongoing and recently completed RMAN backups and restores.

For each backup, it contains one row for each input data file, one row for the aggregate total performance of all data files, and one row for the output backup piece. This data is not stored persistently, and is not preserved when the instance is re-started.

Column	Datatype	Description
SID	NUMBER	Oracle SID of the session doing the backup or restore
SERIAL	NUMBER	Use count for the SID doing the backup or restore
USE_COUNT	NUMBER	A counter that can be used to identify rows from different backup sets
RMAN_STATUS_RECID	NUMBER	Owning V$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V$RMAN_STATUS record stamp
DEVICE_TYPE	VARCHAR2(17)	Device type where the file is located
TYPE	VARCHAR2(9)	INPUT, OUTPUT, or AGGREGATE
STATUS	VARCHAR2(11)	NOT STARTED, IN PROGRESS, or FINISHED
FILENAME	VARCHAR2(513)	Name of the backup file being read or written

Column	Datatype	Description
SET_COUNT	NUMBER	Set count of the backup set being read or written
SET_STAMP	NUMBER	Set stamp of the backup set being read or written
BUFFER_SIZE	NUMBER	Size of the buffers being used to read/write the file, in bytes
BUFFER_COUNT	NUMBER	Number of buffers being used to read/write the file
TOTAL_BYTES	NUMBER	Total number of bytes that will be read or written for the file, if known. If not known, this column will be null
OPEN_TIME	DATE	Time the file was opened. If TYPE='AGGREGATE', then this is the time that the first file in the aggregate was opened
CLOSE_TIME	DATE	Time the file was closed. If TYPE='AGGREGATE', then this is the time that the last file in the aggregate was closed
ELAPSED_TIME	NUMBER	Time, in hundredths of a second, that the file was open
MAXOPENFILES	NUMBER	Number of concurrently open DISK files. This value is only present in rows where TYPE='AGGREGATE'.
BYTES	NUMBER	Number of bytes read or written so far
EFFECTIVE_BYTES_PER_SECOND	NUMBER	I/O rate that was achieved with this device during this backup
IO_COUNT	NUMBER	Number of I/Os that were performed to this file
READY	NUMBER	Number of asynchronous requests for which a buffer was immediately ready for use
SHORT_WAITS	NUMBER	Number of times that a buffer was not immediately available, but a buffer became available after doing a nonblocking poll for I/O completion
SHORT_WAIT_TIME_TOTAL	NUMBER	Total time, in hundredths of a second, taken by nonblocking polls for I/O completion
SHORT_WAIT_TIME_MAX	NUMBER	Maximum time taken for a nonblocking poll for I/O completion, in hundredths of a second
LONG_WAITS	NUMBER	The number of times that a buffer was not immediately available, and only became available after a blocking wait was issued
LONG_WAIT_TIME_TOTAL	NUMBER	The total time, in hundredths of a second, taken by blocking waits for I/O completion
LONG_WAIT_TIME_MAX	NUMBER	The maximum time taken for a blocking wait for I/O completion, in hundredths of a second
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.88 V$BACKUP_CONTROLFILE_DETAILS

V$BACKUP_CONTROLFILE_DETAILS contains information about restorable control files.

It will include all the control files backed up in the backup set, image copies, and proxy copies.

Column	Datatype	Description
BTYPE	CHAR(9)	Backup type container. Possible values are BACKUPSET, IMAGECOPY, PROXYCOPY.
BTYPE_KEY	NUMBER	Unique identifier for the backup type, either BS_KEY or COPY_KEY.
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp
ID1	NUMBER	If BACKUPSET, it contains SET_STAMP If IMAGECOPY or PROXYCOPY, it is RECID from the control file
ID2	NUMBER	If BACKUPSET, it contains SET_COUNT If IMAGECOPY or PROXYCOPY, it is STAMP
CREATION_TIME	DATE	File creation time
RESETLOGS_CHANGE#	NUMBER	Resetlogs change SCN
RESETLOGS_TIME	DATE	Resetlogs change time
CHECKPOINT_CHANGE#	NUMBER	Checkpoint change SCN
CHECKPOINT_TIME	DATE	Checkpoint change time
FILESIZE	NUMBER	File size, in bytes, for the output of backing up this control file
COMPRESSION_RATIO	NUMBER	The ratio between the total blocks in the datafile and the blocks that RMAN backed up. This is *not* the the ratio from the AS COMPRESSED BACKUPSET clause of the BACKUP command.
FILESIZE_DISPLAY	VARCHAR2(4000)	Same value as the FILESIZE column, but converted to a user-displayable format, for example *n*M, *n*G, *n*T, *n*P, and so on
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.89 V$BACKUP_CONTROLFILE_SUMMARY

V$BACKUP_CONTROLFILE_SUMMARY provides control file summary information, based on either a backup set of files, image copies, or proxy copies.

Column	Datatype	Description
NUM_FILES_BACKED	NUMBER	Number of files backed up for specific criteria
NUM_DISTINCT_FILES_BACKED	NUMBER	Number of distinct files backed up
MIN_CHECKPOINT_CHANGE#	NUMBER	Minimum checkpoint change number of the data file for specified criteria
MAX_CHECKPOINT_CHANGE#	NUMBER	Maximum checkpoint change number of the data file for specified criteria
MIN_CHECKPOINT_TIME	DATE	Minimum checkpoint time of the data file for specified criteria

Column	Datatype	Description
MAX_CHECKPOINT_TIME	DATE	Maximum checkpoint time of the data file for specified criteria
INPUT_BYTES	NUMBER	Total input bytes of files read
OUTPUT_BYTES	NUMBER	Total output bytes written
COMPRESSION_RATIO	NUMBER	The ratio between the total blocks in the datafile and the blocks that RMAN backed up. This is *not* the the ratio from the AS COMPRESSED BACKUPSET clause of the BACKUP command.
INPUT_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for input bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for output bytes
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.90 V$BACKUP_COPY_DETAILS

V$BACKUP_COPY_DETAILS contains information about all available control file and data file copies.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp
COPY_KEY	NUMBER	Unique identifier for this data file or control file copy
FILE#	NUMBER	Absolute data file number
NAME	VARCHAR2(513)	File name of the data file copy. The maximum length of the name is dependent on your operating system.
TAG	VARCHAR2(32)	Data file copy tag
CREATION_CHANGE#	NUMBER	Data file creation change number
CREATION_TIME	DATE	Data file creation timestamp
CHECKPOINT_CHANGE#	NUMBER	Checkpoint change number of the data file when the copy was made
CHECKPOINT_TIME	DATE	Checkpoint timestamp of the data file when the copy was made
MARKED_CORRUPT	NUMBER	Number of blocks marked corrupt by this copy operation. That is, blocks that were not marked corrupted in the source data file, but were detected and marked as corrupted during the copy operation.
OUTPUT_BYTES	NUMBER	Total output bytes written
COMPLETION_TIME	DATE	Time when the copy was completed
CONTROLFILE_TYPE	VARCHAR2(1)	Type of control file. B indicates normal copies. S indicates standby copies.

Column	Datatype	Description
KEEP	VARCHAR2(3)	(YES|NO) Indicates whether or not this backup set has a retention policy that is different than the value for the configure retention policy
KEEP_UNTIL	DATE	If specified, this is the date after which the backup becomes obsolete. If this column is null, then the backup never expires.
KEEP_OPTIONS	VARCHAR2(11)	Lists additional retention options for this backup set. Possible values are: • LOGS - The logs needed to recover this backup set are kept • NOLOGS - The logs needed to recover this backup set are not kept
IS_RECOVERY_DEST_FILE	VARCHAR2(3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)
SPARSE_BACKUP	VARCHAR2(3)	Indicates whether the file is sparse (YES) or not (NO)
OUTPUT_BYTES_DISPLAY	VARCHAR2(4000)	Size of backup set to display
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.91 V$BACKUP_COPY_SUMMARY

V$BACKUP_COPY_SUMMARY provides summary information for the output data file and control file copy.

Column	Datatype	Description
NUM_COPIES	NUMBER	Number of copies created
NUM_DISTINCT_COPIES	NUMBER	Number of distinct copies (that contain data files with different checkpoints)
MIN_CHECKPOINT_CHANGE#	NUMBER	Minimum checkpoint change SCN
MAX_CHECKPOINT_CHANGE#	NUMBER	Maximum checkpoint change SCN
MIN_CHECKPOINT_TIME	DATE	Minimum checkpoint change time
MAX_CHECKPOINT_TIME	DATE	Maximum checkpoint change time
OUTPUT_BYTES	NUMBER	Total number of output bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for output bytes
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.92 V$BACKUP_CORRUPTION

V$BACKUP_CORRUPTION displays information about corrupt block ranges in data file backups from the control file.

Note that corruptions are not tolerated in the control file and archived redo log backups.

Column	Datatype	Description
RECID	NUMBER	Backup corruption record ID
STAMP	NUMBER	Backup corruption record stamp
SET_STAMP	NUMBER	Backup set stamp
SET_COUNT	NUMBER	Backup set count
PIECE#	NUMBER	backup piece that contains this corrupt block
FILE#	NUMBER	Absolute file number of the data file that contains the corrupt blocks
BLOCK#	NUMBER	Block number of the first corrupt block in the range of corrupted blocks
BLOCKS	NUMBER	Number of corrupted blocks found starting with BLOCK#
CORRUPTION_CHANGE#	NUMBER	Change number at which the logical corruption was detected. Set to 0 to indicate media corruption.
MARKED_CORRUPT	VARCHAR2(3)	Indicates whether this corruption was not previously detected by the Oracle Database (YES) or the Oracle Database had already discovered this corrupt block and marked it as corrupt (NO). Note that when a corrupt block is encountered in a backup, and was not already marked corrupt by the Oracle Database, then the backup process does not mark the block as corrupt in the production data file. Thus, this field may be YES for the same block in more than one backup set.
CORRUPTION_TYPE	VARCHAR2(9)	Type of block corruption in the data file: • ALL ZERO - Block header on disk contained only zeros. The block may be valid if it was never filled and if it is in an Oracle7 file. The buffer will be reformatted to the Oracle8 standard for an empty block. • FRACTURED - Block header looks reasonable, but the front and back of the block are different versions. • CHECKSUM - optional check value shows that the block is not self-consistent. It is impossible to determine exactly why the check value fails, but it probably fails because sectors in the middle of the block are from different versions. • CORRUPT - Block is wrongly identified or is not a data block (for example, the data block address is missing) • LOGICAL - Block is logically corrupt • NOLOGGING - Block does not have redo log entries (for example, NOLOGGING operations on primary database can introduce this type of corruption on a physical standby)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.93 V$BACKUP_DATAFILE

V$BACKUP_DATAFILE displays information about control files and data files in backup sets from the control file.

Column	Datatype	Description
RECID	NUMBER	Backup data file record ID
STAMP	NUMBER	Backup data file record stamp
SET_STAMP	NUMBER	Backup set stamp
SET_COUNT	NUMBER	Backup set count
FILE#	NUMBER	Data file number; set to 0 for control file
CREATION_CHANGE#	NUMBER	Creation system change number (SCN) of the data file
CREATION_TIME	DATE	Creation timestamp of the data file
RESETLOGS_CHANGE#	NUMBER	Resetlogs system change number (SCN) of the data file when it was backed up
RESETLOGS_TIME	DATE	Resetlogs timestamp of the data file when it was backed up
INCREMENTAL_LEVEL	NUMBER	Normal full backups have a NULL value, level 0 incremental backups have a value of 0, and level 1 incremental backups have a value of 1
INCREMENTAL_CHANGE#	NUMBER	All blocks changed after the incremental change number is included in this backup; set to 0 for a full backup
CHECKPOINT_CHANGE#	NUMBER	All changes up to the checkpoint change number are included in this backup
CHECKPOINT_TIME	DATE	Timestamp of the checkpoint
ABSOLUTE_FUZZY_CHANGE#	NUMBER	Highest change number in this backup
MARKED_CORRUPT	NUMBER	Number of blocks marked corrupt
MEDIA_CORRUPT	NUMBER	Number of blocks media corrupt
LOGICALLY_CORRUPT	NUMBER	Number of blocks logically corrupt
DATAFILE_BLOCKS	NUMBER	Size of the data file in blocks at backup time. This value is also the number of blocks taken by the data file restarted from this backup.
BLOCKS	NUMBER	Size of the backup data file (in blocks). Unused blocks are not copied to the backup.
BLOCK_SIZE	NUMBER	Block size
OLDEST_OFFLINE_RANGE	NUMBER	RECID of the oldest offline range record in this backup control file. 0 for data file backups.

Column	Datatype	Description
COMPLETION_TIME	DATE	Time completed
CONTROLFILE_TYPE	VARCHAR2(1)	B - Normal copies S - Standby copies
USED_CHANGE_TRACKING	VARCHAR2(3)	Indicates whether change tracking data was used to accelerate this incremental backup (YES) or whether change tracking data was not used (NO)
BLOCKS_READ	NUMBER	Number of blocks that were scanned while taking this backup. If this was an incremental backup, and change tracking was used to optimize the backup, then the value of this column will be smaller than DATAFILE_BLOCKS. Otherwise, the value of this column will be the same as DATAFILE_BLOCKS. Even when change tracking data is used, the value of this column may be larger than BLOCKS, because the data read by change tracking is further refined during the process of creating an incremental backup.
USED_OPTIMIZATION	VARCHAR2(3)	Indicates whether backup optimization was applied (YES) or not (NO)
FOREIGN_DBID	NUMBER	Foreign DBID of the database from which this data file was transported. The value is 0 if the file backed up is not a foreign database file.
PLUGGED_READONLY	VARCHAR2(3)	YES if this is a backup of a transported read-only foreign file; otherwise NO.
PLUGIN_CHANGE#	NUMBER	SCN at which the foreign data file was transported into the database. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_CHANGE#	NUMBER	The SCN of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_TIME	DATE	The time of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
SECTION_SIZE	NUMBER	Specifies the number of blocks in each section of a multisection backup. Value is 0 for whole file backups.
UNDO_OPTIMIZED	VARCHAR2(3)	Indicates whether undo blocks were ignored when creating the backup data file (YES) or not (NO)
BLOCKS_SKIPPED_IN_CELL	NUMBER	Number of blocks that were not backed up because they were skipped by the Exadata cell **See Also:** Oracle Exadata Storage Server Software documentation for more information
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Column	Datatype	Description
BACKED_BY_PDB	VARCHAR2(3)	Recovery Manager (RMAN) allows a PDB to be backed up in two ways. The value in this column indicates how the PDB backup was taken: • YES: The backup was taken when connected to the PDB • NO: The backup was taken when connected to the root container
SPARSE_BACKUP	VARCHAR2(3)	Indicates whether the file is sparse (YES) or not (NO)
GUID	RAW(16)	The GUID of the PDB to which the backup belongs. This is useful after the PDB is dropped to identify which PDB the backup belongs to.

8.94 V$BACKUP_DATAFILE_DETAILS

V$BACKUP_DATAFILE_DETAILS contains information about restorable data files.

It will include all data files backed in the backup set, image copies, and proxy copies.

Column	Datatype	Description
BTYPE	CHAR(9)	Backup type container. Possible values are: BACKUPSET, IMAGECOPY, PROXYCOPY.
BTYPE_KEY	NUMBER	Unique identifier for the backup type. For BACKUPSET, it is BS_KEY.
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session record ID
SESSION_STAMP	NUMBER	Session stamp
ID1	NUMBER	If BACKUPSET, it contains SET_STAMP. If IMAGECOPY or PROXYCOPY, it is RECID from the control file.
ID2	NUMBER	If BACKUPSET, it contains SET_COUNT. If IMAGECOPY or PROXYCOPY, it is STAMP.
FILE#	NUMBER	File number
CREATION_CHANGE#	NUMBER	File creation change SCN
CREATION_TIME	DATE	File creation time
RESETLOGS_CHANGE#	NUMBER	Resetlogs change SCN
RESETLOGS_TIME	DATE	Resetlogs change time
INCREMENTAL_LEVEL	NUMBER	Normal full backups have a NULL value, level 0 incremental backups have a value of 0, and level 1 incremental backups have a value of 1
INCREMENTAL_CHANGE#	NUMBER	Incremental change SCN
CHECKPOINT_CHANGE#	NUMBER	Checkpoint change SCN
CHECKPOINT_TIME	DATE	Checkpoint change time
MARKED_CORRUPT	NUMBER	Number of blocks marked corrupt
FILESIZE	NUMBER	File size, in bytes
COMPRESSION_RATIO	NUMBER	The ratio between the total blocks in the datafile and the blocks that RMAN backed up. This is *not* the the ratio from the AS COMPRESSED BACKUPSET clause of the BACKUP command.

Column	Datatype	Description
SPARSE_BACKUP	VARCHAR2(3)	Indicates whether the file is sparse (YES) or not (NO)
TS#	NUMBER	Tablespace number
TSNAME	VARCHAR2(30)	Tablespace name
FILESIZE_DISPLAY	VARCHAR2(4000)	Same value as the FILESIZE column, but converted to a user-displayable format, for example *n*M, *n*G, *n*T, *n*P, and so on
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.95 V$BACKUP_DATAFILE_SUMMARY

V$BACKUP_DATAFILE_SUMMARY provides summary information for a specific criteria set, based on a backup job, a time range applicable to jobs, or a specific data file).

Column	Datatype	Description
NUM_FILES_BACKED	NUMBER	Number of files backed up for specified criteria
NUM_DISTINCT_FILES_BACKED	NUMBER	Number of distinct files backed up
NUM_DISTINCT_TS_BACKED	NUMBER	Number of distinct tablespaces backed up
MIN_CHECKPOINT_CHANGE#	NUMBER	Minimum checkpoint change number of the data file for specified criteria
MAX_CHECKPOINT_CHANGE#	NUMBER	Maximum checkpoint change number of the data file for specified criteria
MIN_CHECKPOINT_TIME	DATE	Minimum checkpoint time of the data file for specified criteria
MAX_CHECKPOINT_TIME	DATE	Maximum checkpoint time of the data file for specified criteria
INPUT_BYTES	NUMBER	Total input bytes of files read
OUTPUT_BYTES	NUMBER	Total output bytes written
COMPRESSION_RATIO	NUMBER	The ratio between the total blocks in the datafile and the blocks that RMAN backed up. This is *not* the the ratio from the AS COMPRESSED BACKUPSET clause of the BACKUP command.
INPUT_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for input bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for output bytes
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.96 V$BACKUP_DEVICE

V$BACKUP_DEVICE displays information about supported backup devices.

If a device type does not support named devices, then one row with the device type and a null device name is returned for that device type. If a device type supports named devices then one row is returned for each available device of that type. The special device type DISK is not returned by this view because it is always available.

Column	Datatype	Description
DEVICE_TYPE	VARCHAR2(17)	Type of the backup device
DEVICE_NAME	VARCHAR2(513)	Name of the backup device
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.97 V$BACKUP_FILES

V$BACKUP_FILES displays information about all RMAN backups (both image copies and backup sets) and archived logs.

This view simulates the LIST BACKUP and LIST COPY RMAN commands. This view requires that the database be set using the DBMS_RCVMAN.SETDATABASE procedure.

Column	Datatype	Description
PKEY	NUMBER	Primary key for the backup
BACKUP_TYPE	VARCHAR2(32)	Type of the backup: • BACKUP SET • COPY • PROXY COPY
FILE_TYPE	VARCHAR2(32)	Type of the file: • DATAFILE • CONTROLFILE • SPFILE • REDO LOG • ARCHIVED LOG • COPY (for an image copy backup) • PIECE (for a backup piece)
KEEP	VARCHAR2(3)	Indicates whether the backup has a retention policy different from the value for CONFIGURE RETENTION POLICY (YES) or not (NO)
KEEP_UNTIL	DATE	If the KEEP UNTIL TIME clause of the BACKUP command was specified, then this column shows the date after which the backup becomes obsolete. If the column is null and KEEP_OPTIONS is not null, the backup never becomes obsolete.

Column	Datatype	Description
KEEP_OPTIONS	VARCHAR2(13)	KEEP options for the backup: • LOGS - RMAN keeps the logs needed to recover the backup • NOLOGS - RMAN does not keep the logs needed to recover the backup If this column is null, then the backup has no KEEP options and will be made obsolete based on the retention policy.
STATUS	VARCHAR2(16)	Status of the backup: • AVAILABLE • UNAVAILABLE • EXPIRED • OTHER
FNAME	VARCHAR2(1024)	Name of the file
TAG	VARCHAR2(32)	Tag of the piece, copy, or proxy copy
MEDIA	VARCHAR2(80)	Media ID of the piece or proxy copy
RECID	NUMBER	Recid of the record in the control file
STAMP	NUMBER	Stamp of the record in the control file
DEVICE_TYPE	VARCHAR2(255)	Type of media device that stores the backup
BLOCK_SIZE	NUMBER	Block size for the backup (in bytes)
COMPLETION_TIME	DATE	Time when the backup completed
COMPRESSED	VARCHAR2(3)	Indicates whether the backup piece is compressed (YES) or not (NO); valid only if FILE_TYPE is PIECE. Image copies cannot be compressed.
OBSOLETE	VARCHAR2(3)	Indicates whether the backup piece or copy is obsolete (YES) or not (NO); valid only if FILE_TYPE is PIECE or COPY
BYTES	NUMBER	Size of the file (in bytes)
BS_KEY	NUMBER	Primary key of the backup set (valid only if BACKUP_TYPE is BACKUP SET)
BS_COUNT	NUMBER	Count of the backup set from the control file record (valid only if BACKUP_TYPE is BACKUP SET)
BS_STAMP	NUMBER	Stamp of the backup set from the control file record (valid only if BACKUP_TYPE is BACKUP SET)
BS_TYPE	VARCHAR2(32)	Type of the backup set (valid only if BACKUP_TYPE is BACKUP SET): • DATAFILE • ARCHIVED LOG
BS_INCR_TYPE	VARCHAR2(32)	Incremental type of the backup set (valid only if BACKUP_TYPE is BACKUP SET)
BS_PIECES	NUMBER	Number of backup pieces in the backup set (valid only if BACKUP_TYPE is BACKUP SET)
BS_COPIES	NUMBER	Number of copies of the backup set (valid only if FILE_TYPE is PIECE and BACKUP_TYPE is BACKUP SET)
BS_COMPLETION_TIME	DATE	Completion time of the backup set (valid only if BACKUP_TYPE is BACKUP SET)

Column	Datatype	Description
BS_STATUS	VARCHAR2(16)	Status of the backup set (valid only if BACKUP_TYPE is BACKUP SET): • AVAILABLE • UNAVAILABLE • EXPIRED • OTHER - Pieces which are part of the backup set do not have uniform status (that is, some of them are available, some not)
BS_BYTES	NUMBER	Sum of all backup piece sizes in the backup set (valid only if BACKUP_TYPE is BACKUP SET)
BS_COMPRESSED	VARCHAR2(3)	Indicates whether the backup pieces of the backup set are compressed (YES) or not (NO); valid only if BACKUP_TYPE is BACKUP SET
BS_TAG	VARCHAR2(1024)	Tags of the backup set. If pieces have different tags, then all piece tags are concatenated and separated by commas. Valid only if BACKUP_TYPE is BACKUP SET)
BS_DEVICE_TYPE	VARCHAR2(255)	Device type of the backup set. If there is more than one device type, then they are separated by commas. Valid only if BACKUP_TYPE is BACKUP SET
BP_PIECE#	NUMBER	Number of pieces inside the backup set (valid only if FILE_TYPE is PIECE and BACKUP_TYPE is BACKUP SET)
BP_COPY#	NUMBER	Number of copies of the backup set (valid only if FILE_TYPE is PIECE and BACKUP_TYPE is BACKUP SET)
DF_FILE#	NUMBER	Absolute file number of the data file (valid only if FILE_TYPE is DATAFILE)
DF_TABLESPACE	VARCHAR2(30)	Tablespace name of the data file (valid only if FILE_TYPE is DATAFILE)
DF_RESETLOGS_CHANGE#	NUMBER	System change number (SCN) of the most recent RESETLOGS when the control file or data file was created (valid only if FILE_TYPE is DATAFILE)
DF_CREATION_CHANGE#	NUMBER	Creation SCN of the control file or data file (valid only if FILE_TYPE is CONTROLFILE or DATAFILE)
DF_CHECKPOINT_CHANGE#	NUMBER	System change number (SCN) of the most recent control file or data file checkpoint (valid only if FILE_TYPE is CONTROLFILE or DATAFILE)
DF_CKP_MOD_TIME	DATE	Modification time in case of SPFILE, otherwise time when the control file or data file was checkpointed (valid only if FILE_TYPE is SPFILE, CONTROLFILE, or DATAFILE)
RL_THREAD#	NUMBER	Redo log thread number of the archived log (valid only if FILE_TYPE is REDO LOG)
RL_SEQUENCE#	NUMBER	Redo log sequence number of the archived log (valid only if FILE_TYPE is REDO LOG)
RL_RESETLOGS_CHANGE#	NUMBER	System change number (SCN) of the most recent RESETLOGS when the record was created (valid only if FILE_TYPE is REDO LOG)
RL_FIRST_CHANGE#	NUMBER	First SCN of the redo log (valid only if FILE_TYPE is REDO LOG)
RL_FIRST_TIME	DATE	Time when the Oracle Database switched into the redo log (valid only if FILE_TYPE is REDO LOG)
RL_NEXT_CHANGE#	NUMBER	First SCN of the next redo log in the thread (valid only if FILE_TYPE is REDO LOG)

Column	Datatype	Description
RL_NEXT_TIME	DATE	First timestamp of the next redo log in the thread (valid only if FILE_TYPE is REDO LOG)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Backup and Recovery User's Guide* for more information about the DBMS_RCVMAN.SETDATABASE procedure

8.98 V$BACKUP_NONLOGGED

V$BACKUP_NONLOGGED displays information about nonlogged block ranges in data file backups, recorded in the control file.

Column	Datatype	Description
RECID	NUMBER	Nologged backup record ID
STAMP	NUMBER	Nonlogged backup record stamp
SET_STAMP	NUMBER	Backup set stamp
SET_COUNT	NUMBER	Backup set count
PIECE#	NUMBER	Backup piece that contains the range of nonlogged blocks
FILE#	NUMBER	Absolute file number of the data file that contains this range of nonlogged blocks
BLOCK#	NUMBER	Block number of the first nonlogged block in the range of nologged blocks
BLOCKS	NUMBER	Number of nonlogged blocks found starting with BLOCK#
NONLOGGED_CHANGE#	NUMBER	The smallest SCN on which any block in this block range became nonlogged. NULL if unknown.
NONLOGGED_TIME	VARCHAR2	The time that corresponds to NONLOGGED_CHANGE#. NULL if unknown.
RESETLOGS_CHANGE#	VARCHAR2	The resetlogs SCN of the incarnation on which this block range was first marked as nonlogged. NULL if unknown.
RESETLOGS_TIME	VARCHAR2	The resetlogs time of the incarnation on which this block range was first marked as nologged. NULL if unknown.
OBJECT#	VARCHAR2	The object ID this range belongs to. If this field is NULL, the object number is unknown.

Column	Datatype	Description
REASON	CHAR(7)	The reason why this block range appears in this list, for example, primary file offline, could not talk to primary, non-standby recovery, and so on. For Oracle Database 12*c* and later releases, it is always UNKNOWN.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.99 V$BACKUP_PIECE

V$BACKUP_PIECE displays information about backup pieces from the control file. Each backup set consists of one or more backup pieces.

Column	Datatype	Description
RECID	NUMBER	Backup piece record ID
STAMP	NUMBER	Backup piece record stamp
SET_STAMP	NUMBER	Backup set stamp
SET_COUNT	NUMBER	Backup set count
PIECE#	NUMBER	Backup piece number (1-N)
COPY#	NUMBER	Indicates the copy number for backup pieces created with duplex enabled. 1 if the backup piece is not duplexed.
DEVICE_TYPE	VARCHAR2(17)	Type of the device on which the backup piece resides. Set to DISK for backup sets on disk. **See Also:** V$BACKUP_DEVICE
HANDLE	VARCHAR2(513)	Backup piece handle identifies the backup piece on restore
COMMENTS	VARCHAR2(64)	Comment returned by the operating system or storage subsystem. Set to NULL for backup pieces on disk. This value is informational only; not needed for restore.
MEDIA	VARCHAR2(65)	Name of the media on which the backup piece resides. This value is informational only; not needed for restore.
MEDIA_POOL	NUMBER	The media pool in which the copy resides. This is the same value that was entered in the POOL operand of the Recovery Manager BACKUP command.
CONCUR	VARCHAR2(3)	(YES | NO) Indicates whether the piece on a media that can be accessed concurrently
TAG	VARCHAR2(32)	Backup piece tag. The tag is specified at backup set level, but stored at piece level.
STATUS	VARCHAR2(1)	Indicates the status of the piece: A (available), D (deleted), or X (expired)
START_TIME	DATE	Starting time
COMPLETION_TIME	DATE	Completion time

Column	Datatype	Description
ELAPSED_SECONDS	NUMBER	Number of elapsed seconds
DELETED	VARCHAR2(3)	(YES/NO) NO indicates that the file still exists. YES indicates the file no longer exists because it has been deleted.
BYTES	NUMBER	Size of the backup piece (in bytes)
IS_RECOVERY_DEST_FILE	VARCHAR2(3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)
RMAN_STATUS_RECID	NUMBER	Owning V$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V$RMAN_STATUS record stamp
COMPRESSED	VARCHAR2(3)	Indicates whether the backup piece is compressed (YES) or not (NO)
BACKED_BY_VSS	VARCHAR2(3)	Whether or not the file has been backed up by Volume Shadow Copy Service (VSS). This column is reserved for internal use.
ENCRYPTED	VARCHAR2(3)	A value of YES means an encrypted backup, otherwise not an encrypted backup.
BACKED_BY_OSB	VARCHAR2(3)	A value of YES means the backup was done to Oracle Secure Backup. Otherwise, backed up by other third party tape library.
FOR_XTTS	VARCHAR2(3)	Indicates whether this is a cross platform backup piece: • YES: This is a cross platform backup piece. • NO: This is not a cross platform backup piece.
SAME_ENDIAN	VARCHAR2(3)	If the value of FOR_XTTS is YES, then this column indicates whether the backup piece has the same endianess as the current database (YES) or not (NO); otherwise NULL.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
GUID	RAW(16)	The GUID of the PDB to which the backup belongs. This is useful after the PDB is dropped to identify which PDB the backup belongs to.

8.100 V$BACKUP_PIECE_DETAILS

V$BACKUP_PIECE_DETAILS displays information about all available backup pieces.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp
BS_KEY	NUMBER	Backup set identifier
BP_KEY	NUMBER	Backup piece key
RECID	NUMBER	Backup piece record ID

Column	Datatype	Description
STAMP	NUMBER	Backup piece record stamp
SET_STAMP	NUMBER	Backup set stamp
SET_COUNT	NUMBER	Backup set count
PIECE#	NUMBER	Backup piece number (1-N)
COPY#	NUMBER	Indicates the copy number for backup pieces created with duplex enabled. The value is 1 if the backup piece is not duplexed.
DEVICE_TYPE	VARCHAR2(17)	Type of device on which the backup piece resides. Set to DISK for backup sets on disk.
HANDLE	VARCHAR2(513)	Backup piece handle identifies the backup piece on restore
COMMENTS	VARCHAR2(64)	Comments returned by the operating system or storage subsystem. Set to NULL for backup pieces on disk. This value is informational only. It is not needed for restore.
MEDIA	VARCHAR2(65)	Name of the media on which the backup piece resides. This value is informational only. It is not needed for restore.
MEDIA_POOL	NUMBER	The media pool in which the copy resides. This is the same value that was entered in the POOL operand of the Recovery Manager BACKUP command.
CONCUR	VARCHAR2(3)	(YES|NO) indicates whether or not the piece is on a media that can be accessed concurrently
TAG	VARCHAR2(32)	Backup piece tag. The tag is specified at backup set level, but stored at piece level.
STATUS	VARCHAR2(1)	Indicates the status of the piece: A (available), D (deleted), or X (expired)
START_TIME	DATE	Starting time
COMPLETION_TIME	DATE	Completion time
ELAPSED_SECONDS	NUMBER	Number of elapsed seconds
DELETED	VARCHAR2(3)	NO indicates that the file still exists. YES indicates that the file no longer exists because it has been deleted.
BYTES	NUMBER	Size of the backup piece, in bytes
IS_RECOVERY_DEST_FILE	VARCHAR2(3)	Indicates whether or not the file was created in the fast recovery area (YES) or not (NO)
RMAN_STATUS_RECID	NUMBER	Owning V$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V$RMAN_STATUS record stamp
COMPRESSED	VARCHAR2(3)	Indicates whether the backup piece is compressed (YES) or not (NO)
BACKED_BY_VSS	VARCHAR2(3)	Whether or not the file has been backed up by Volume Shadow Copy Service (VSS). This column is reserved for internal use.
ENCRYPTED	VARCHAR2(3)	A value of YES means an encrypted backup, otherwise not an encrypted backup.
BACKED_BY_OSB	VARCHAR2(3)	A value of YES means the backup was done to Oracle Secure Backup. Otherwise, backed up by other third party tape library.
FOR_XTTS	VARCHAR2(3)	Indicates whether this is a cross platform backup piece: • YES: This is a cross platform backup piece. • NO: This is not a cross platform backup piece.

Column	Datatype	Description
SAME_ENDIAN	VARCHAR2(3)	If the value of FOR_XTTS is YES, then this column indicates whether the backup piece has the same endianess as the current database (YES) or not (NO); otherwise NULL.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
PIECES_PER_SET	NUMBER	Number of backup pieces per set
SIZE_BYTES_DISPLAY	VARCHAR2(4000)	Size (in bytes) of the backup piece to display

8.101 V$BACKUP_REDOLOG

V$BACKUP_REDOLOG displays information about archived logs in backup sets from the control file.

Note that online redo logs cannot be backed up directly; they must be archived first to disk and then backed up. An archive log backup set can contain one or more archived logs.

Column	Datatype	Description
RECID	NUMBER	Record ID for this row; it is an integer that identifies this row
STAMP	NUMBER	Timestamp used with RECID to uniquely identify this row
SET_STAMP	NUMBER	One of the foreign keys for the row of the V$BACKUP_SET table that identifies this backup set
SET_COUNT	NUMBER	One of the foreign keys for the row of the V$BACKUP_SET table that identifies this backup set
THREAD#	NUMBER	Thread number for the log
SEQUENCE#	NUMBER	Log sequence number
RESETLOGS_CHANGE#	NUMBER	Change number of the last resetlogs before the log was written
RESETLOGS_TIME	DATE	Change time of the last resetlogs before the log was written. These will be the same for all logs in a backup set.
FIRST_CHANGE#	NUMBER	SCN when the log was switched into. The redo in the log is at this SCN and greater.
FIRST_TIME	DATE	Time allocated when the log was switched into
NEXT_CHANGE#	NUMBER	SCN when the next log in this thread was switched into. The redo in the log is below this SCN.
NEXT_TIME	DATE	Time when the next log in this thread was switched into
BLOCKS	NUMBER	Size of the log in logical blocks including the header block
BLOCK_SIZE	NUMBER	Size of the log blocks in bytes
TERMINAL	VARCHAR2(3)	Indicates whether this record corresponds to a terminal archived redo log, as defined in V$ARCHIVED_LOG (YES) or not (NO)

Column	Datatype	Description
SECTION_SIZE	NUMBER	Number of blocks in each section of a multisection log. The value is 0 for whole file logs.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.102 V$BACKUP_SET

V$BACKUP_SET displays information about backup sets from the control file.

A backup set record is inserted after the backup set is successfully completed.

Column	Datatype	Description
RECID	NUMBER	Backup set record ID
STAMP	NUMBER	Backup set record stamp
SET_STAMP	NUMBER	Backup set stamp. The backup set stamp and count uniquely identify the backup set. Primary key for the V$BACKUP_SET table, and the foreign key for the following tables: V$BACKUP_PIECE, V$BACKUP_DATAFILE, V$BACKUP_REDOLOG, V$BACKUP_CORRUPTION.
SET_COUNT	NUMBER	Backup set count. The backup set count is incremented by one every time a new backup set is started (if the backup set is never completed the number is "lost"). If the control file is re-created then the count is reset to 1. Therefore the count must be used with the stamp to uniquely identify a backup set. Primary key for the V$BACKUP_SET table, and the foreign key for the following tables: V$BACKUP_PIECE, V$BACKUP_DATAFILE, V$BACKUP_REDOLOG, V$BACKUP_CORRUPTION
BACKUP_TYPE	VARCHAR2(1)	Type of files that are in this backup. If the backup contains archived redo logs, the value is L. If this is a data file full backup, the value is D. If this is an incremental backup, the value is I.
CONTROLFILE_INCLUDED	VARCHAR2(3)	Provides information about the control file in the backup set: • YES: The control file included is a primary control file. • SBY: The control file included is a standby control file. • NO: A control file is not included.
INCREMENTAL_LEVEL	NUMBER	Location where this backup set fits into the database's backup strategy. Set to NULL for full datafile, archivelog, controlfile, and spfile backups, set to 0 for incremental level 0 datafile backups, and set to 1 for incremental level 1 datafile backups.
PIECES	NUMBER	Number of distinct backup pieces in the backup set
START_TIME	DATE	Starting time
COMPLETION_TIME	DATE	Time that this backup set completed

Column	Datatype	Description
ELAPSED_SECONDS	NUMBER	The number of elapsed seconds
BLOCK_SIZE	NUMBER	Block size of the backup set
INPUT_FILE_SCAN_ONLY	VARCHAR2(3)	YES indicates no actual backup is performed, but the data files are read. NO indicates a normal backup is performed.
KEEP	VARCHAR2(3)	(YES/NO) Indicates whether or not this backup set has a retention policy that is different than the value for the configure retention policy
KEEP_UNTIL	DATE	If KEEP_UNTIL_TIME is specified, this is the date after which the backup becomes obsolete. If this column is null, then the backup never expires.
KEEP_OPTIONS	VARCHAR2(11)	Lists additional retention options for this backup set. Possible values are: LOGS - The logs need to recover this backup are kept NOLOGS - The logs needed to recover this backup will not be kept BACKUP_LOGS - An archive log backup exists to support this backup set
MULTI_SECTION	VARCHAR2(3)	Indicates whether or not this backup set is a multi-section backup. Valid values are YES and NO. A multi-section backup is a backup in which multiple backup pieces are produced independently in parallel by multiple channels.
FOR_XTTS	VARCHAR2(3)	Indicates whether this is a cross platform backup set: • YES: This is a cross platform backup set. • NO: This is not a cross platform backup set.
SAME_ENDIAN	VARCHAR2(3)	If the value of FOR_XTTS is YES, then this column indicates whether the backup set has the same endianess as the current database (YES) or not (NO); otherwise NULL.
INC_DMPFILE	VARCHAR2(3)	If the value of FOR_XTTS is YES, then this column indicates whether the backup set includes a Data Pump export file of the backed up data files (YES) or not (NO), otherwise NULL.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
GUID	RAW(16)	The GUID of the PDB to which the backup belongs. This is useful after the PDB is dropped to identify which PDB the backup belongs to.

8.103 V$BACKUP_SET_DETAILS

V$BACKUP_SET_DETAILS provides detailed information about the backup set.

This view will contain an extra row for each backup session that invokes BACKUP BACKUPSET (that is, creates new copies for the same backup set or copies backup set information from disk to tape). However, the remaining values of other columns belong to the complete backup set.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Identifies the job, together with SESSION_STAMP.
SESSION_STAMP	NUMBER	Identifies the job, together with SESSION_RECID
BS_KEY	NUMBER	Backup set identifier
RECID	NUMBER	RECID from V$BACKUP_SET record
STAMP	NUMBER	Stamp from V$BACKUP_SET record
SET_STAMP	NUMBER	Backup set stamp
SET_COUNT	NUMBER	Backup count number
BACKUP_TYPE	VARCHAR2(1)	Type of backup (same as in V$BACKUP_SET)
CONTROLFILE_INCLUDED	VARCHAR2(3)	Control file included in backup set (same as in V$BACKUP_SET)
INCREMENTAL_LEVEL	NUMBER	Incremental level (same as in V$BACKUP_SET)
PIECES	NUMBER	Number of pieces (same as in V$BACKUP_SET)
START_TIME	DATE	Start time of the backup set (same as in V$BACKUP_SET)
COMPLETION_TIME	DATE	Completion time of the backup set (same as in V$BACKUP_SET)
ELAPSED_SECONDS	NUMBER	Time taken for backup set creation (same as in V$BACKUP_SET)
BLOCK_SIZE	NUMBER	Block size (same as in V$BACKUP_SET)
KEEP	VARCHAR2(3)	Keep value (same as in V$BACKUP_SET)
KEEP_UNTIL	DATE	Keep Until time (same as in V$BACKUP_SET)
KEEP_OPTIONS	VARCHAR2(11)	Keep options (same as in V$BACKUP_SET)
DEVICE_TYPE	VARCHAR2(17)	Type of device. If the backup set exists on more than one device type, an * is indicated here.
COMPRESSED	VARCHAR2(3)	YES, if backup is compressed
NUM_COPIES	NUMBER	Number of identical copies
OUTPUT_BYTES	NUMBER	Size of the backup set
ORIGINAL_INPUT_BYTES	NUMBER	Amount of data backed up when the backup set was created
COMPRESSION_RATIO	NUMBER	The ratio between the total blocks in the datafile and the blocks that RMAN backed up. This is *not* the the ratio from the AS COMPRESSED BACKUPSET clause of the BACKUP command.
STATUS	CHAR(1)	The status of the backup set. It is always A (all backup pieces available), because this view only reflects available backup sets.
ORIGINAL_INPRATE_BYTES	NUMBER	Number of bytes read per second when backup set was initially created
OUTPUT_RATE_BYTES	NUMBER	Number of bytes written per second when the backup set was initially created
ORIGINAL_INPUT_BYTES_DISPLAY	VARCHAR2(4000)	Input rate to display
OUTPUT_BYTES_DISPLAY	VARCHAR2(4000)	Size of backup set to display
ORIGINAL_INPRATE_BYTES_DISPLAY	VARCHAR2(4000)	Input rate per second for display
OUTPUT_RATE_BYTES_DISPLAY	VARCHAR2(4000)	Output rate per second for display
TIME_TAKEN_DISPLAY	VARCHAR2(4000)	Elapsed time in hh:mm:ss format

Column	Datatype	Description
ENCRYPTED	VARCHAR2(3)	A value of YES means an encrypted backup, otherwise not an encrypted backup.
BACKED_BY_OSB	VARCHAR2(3)	A value of YES means the backup was done to Oracle Secure Backup. Otherwise, backed up by other third party tape library.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$BACKUP_SET"

8.104 V$BACKUP_SET_SUMMARY

V$BACKUP_SET_SUMMARY provides summary information for a backup set.

Column	Datatype	Description
NUM_BACKUPSETS	NUMBER	Total number of backup sets created
OLDEST_BACKUP_TIME	DATE	Oldest backup start time
NEWEST_BACKUP_TIME	DATE	Newest backup start time
OUTPUT_BYTES	NUMBER	Number of output bytes (not including multiple copies)
ORIGINAL_INPUT_BYTES	NUMBER	Number of input bytes when backup sets were created
ORIGINAL_INPRATE_BYTES	NUMBER	Average input rate
OUTPUT_RATE_BYTES	NUMBER	Average output rate
COMPRESSION_RATIO	NUMBER	The ratio between the total blocks in the datafile and the blocks that RMAN backed up. This is *not* the the ratio from the AS COMPRESSED BACKUPSET clause of the BACKUP command.
ORIGINAL_INPUT_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for input bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for output bytes
ORIGINAL_INPRATE_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for input rate
OUTPUT_RATE_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for output rate

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.105 V$BACKUP_SPFILE

V$BACKUP_SPFILE displays information about server parameter files in backup sets from the control file.

Column	Datatype	Description
RECID	NUMBER	Backup SPFILE record ID
STAMP	NUMBER	Backup SPFILE record stamp
SET_STAMP	NUMBER	Backup set stamp (of the set which contains this SPFILE backup)
SET_COUNT	NUMBER	Backup set count (of the set which contains this SPFILE backup)
MODIFICATION_TIME	DATE	Time when the SPFILE was last modified (this also includes creation time)
BYTES	NUMBER	Size of the SPFILE (in bytes)
COMPLETION_TIME	DATE	Time when the backup of the SPFILE completed
DB_UNIQUE_NAME	VARCHAR2(30)	Unique database name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
GUID	RAW(16)	The GUID of the PDB to which the backup belongs. This is useful after the PDB is dropped to identify which PDB the backup belongs to.

8.106 V$BACKUP_SPFILE_DETAILS

V$BACKUP_SPFILE_DETAILS displays information about all restorable SP files backed up in the backup set.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp

Column	Datatype	Description
BS_KEY	NUMBER	Unique backup set identifier
SET_STAMP	NUMBER	Backup set stamp
SET_COUNT	NUMBER	Backup set count
MODIFICATION_TIME	DATE	Time the backup set was modified
FILESIZE	NUMBER	Size, in bytes, of the SPFILE that was backed up
FILESIZE_DISPLAY	VARCHAR2(4000)	Same value as the FILESIZE column, but converted to a user-displayable format, for example *n*M, *n*G, *n*T, *n*P, and so on
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.107 V$BACKUP_SPFILE_SUMMARY

V$BACKUP_SPFILE_SUMMARY provides summary information for input SP file, based on either a backup job or time range applicable to jobs.

Column	Datatype	Description
NUM_FILES_BACKED	NUMBER	Number of files backed up
NUM_DISTINCT_FILES_BACKED	NUMBER	Number of distinct SP files backed up (with modification timestamp)
MIN_MODIFICATION_TIME	DATE	Minimum modification time
MAX_MODIFICATION_TIME	DATE	Maximum modification time
INPUT_BYTES	NUMBER	Total input bytes for all SP files backed up
INPUT_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for all input bytes
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.108 V$BACKUP_SYNC_IO

V$BACKUP_SYNC_IO displays performance information about ongoing and recently completed RMAN backups and restores.

For each backup, it contains one row for each input data file, one row for the aggregate total performance of all data files, and one row for the output backup piece. This data is not stored persistently, and is not preserved when the instance is re-started.

Column	Datatype	Description
SID	NUMBER	The Oracle SID of the session doing the backup or restore
SERIAL	NUMBER	The use count for the SID doing the backup or restore
USE_COUNT	NUMBER	A counter that can be used to identify rows from different backup sets
RMAN_STATUS_RECID	NUMBER	Owning V$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V$RMAN_STATUS record stamp
DEVICE_TYPE	VARCHAR2(17)	The device type where the file is located
TYPE	VARCHAR2(9)	INPUT, OUTPUT, or AGGREGATE
STATUS	VARCHAR2(11)	NOT STARTED, IN PROGRESS, or FINISHED
FILENAME	VARCHAR2(513)	The name of the backup file being read or written
SET_COUNT	NUMBER	The set count of the backup set being read or written
SET_STAMP	NUMBER	The set stamp of the backup set being read or written
BUFFER_SIZE	NUMBER	The size of the buffers being used to read/write this file, in bytes
BUFFER_COUNT	NUMBER	The number of buffers being used to read/write this file
TOTAL_BYTES	NUMBER	The total number of bytes that will be read or written for this file, if known. If not known, this column will be null.
OPEN_TIME	DATE	The time this file was opened. If TYPE='AGGREGATE', then this is the time that the first file in the aggregate was opened.
CLOSE_TIME	DATE	The time this file was closed. If TYPE='AGGREGATE', then this is the time that the last file in the aggregate was closed.
ELAPSED_TIME	NUMBER	The time, in hundredths of a second, that the file was open
MAXOPENFILES	NUMBER	The number of concurrently open DISK files. This value is only present in rows where TYPE='AGGREGATE'.
BYTES	NUMBER	The number of bytes read or written so far
EFFECTIVE_BYTES_PER_SECOND	NUMBER	The I/O rate that was achieved with this device during this backup
IO_COUNT	NUMBER	The number of I/Os that were performed to this file
IO_TIME_TOTAL	NUMBER	The total time, in hundredths of a second, taken to do I/O for this file
IO_TIME_MAX	NUMBER	The maximum time taken for a single I/O request
DISCRETE_BYTES_PER_SECOND	NUMBER	The average transfer rate for this file
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.109 V$BGPROCESS

V$BGPROCESS displays information about the background processes.

Column	Datatype	Description
PADDR	RAW(4 | 8)	Address of the process state object
PSERIAL#	NUMBER	Process state object serial number
NAME	VARCHAR2(5)	Name of this background process
DESCRIPTION	VARCHAR2(64)	Description of the background process
ERROR	NUMBER	Error encountered
TYPE	VARCHAR2(5)	This column has a value of SLAVE for all background worker processes, otherwise it is null.
PRIORITY	VARCHAR2(8)	Lists the current priority with which the process is running. This column has string values based on the operating system. On Linux, the values that can appear in this column are: • TS: Time sharing • RT: Real time priority
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.110 V$BH

V$BH displays the status and number of pings for every buffer in the SGA. This is an Oracle Real Application Clusters view.

Column	Datatype	Description
FILE#	NUMBER	Data file identifier number (to find the file name, query DBA_DATA_FILES or V$DBFILE)
BLOCK#	NUMBER	Block number
CLASS#	NUMBER	Class number

Column	Datatype	Description
STATUS	VARCHAR2(10)	Status of the buffer: • cr - Consistent read • flashcur - A current flash cache buffer • flashfree - A free flash cache buffer • free - Not currently in use • irec - In instance recovery mode • mrec - In media recovery mode • pi - A past image in RAC mode • pmemfree - A free PMEM buffer • pmemcr - pmemcr - A consistent-read/previous version of a PMEM buffer • pmemcur - A current PMEM buffer • read - Being read from disk • scur - Shared current • securefile - A secured file buffer • xcur - Exclusive
XNC	NUMBER	This column is obsolete. Its value is hard-coded to 0.
FORCED_READS	NUMBER	This column is obsolete. Its value is hard-coded to 0.
FORCED_WRITES	NUMBER	This column is obsolete. Its value is hard-coded to 0.
LOCK_ELEMENT_ADDR	RAW(4 | 8)	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
LOCK_ELEMENT_NAME	NUMBER	The address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
LOCK_ELEMENT_CLASS	NUMBER	The address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
DIRTY	VARCHAR2(1)	Y - block modified
TEMP	VARCHAR2(1)	Y - temporary block
PING	VARCHAR2(1)	Y - block pinged
STALE	VARCHAR2(1)	Y - block is stale
DIRECT	VARCHAR2(1)	Y - direct block
NEW	CHAR(1)	Always set to N. This column is obsolete and maintained for backward compatibility.
OBJD	NUMBER	Database object number of the block that the buffer represents
TS#	NUMBER	Tablespace number of block
LOBID	NUMBER	If the buffer belongs to a SecureFiles object, the value in this column is the unique identifier for the SecureFiles object. For other buffer types, the value in this column is meaningless.
CACHEHINT	NUMBER	Numeric representation of the values in the FLASH_CACHE and CELL_FLASH_CACHE columns. See the descriptions and possible values for the FLASH_CACHE and CELL_FLASH_CACHE columns in this view.

Column	Datatype	Description
FLASH_CACHE	VARCHAR2(7)	Database Smart Flash Cache hint to be used for segment blocks: • DEFAULT • KEEP • NONE Solaris and Oracle Linux functionality only.
CELL_FLASH_CACHE	VARCHAR2(7)	Cell flash cache hint to be used for segment blocks: • DEFAULT • KEEP • NONE **See Also:** Oracle Exadata Storage Server Software documentation for more information
XCUR_PIN_HOLDER	NUMBER	ID of the Oracle process that holds the exclusive pin You can join this column with the PID column of the V$PROCESS and V$WAIT_CHAINS views to obtain details about the process.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.111 V$BLOCK_CHANGE_TRACKING

V$BLOCK_CHANGE_TRACKING displays the status of block change tracking for the database.

Column	Datatype	Description
STATUS	VARCHAR2(10)	Status of block change tracking in the database: • DISABLED - Block change tracking is disabled • TRANSITION - Block change tracking is in the process of transitioning between the enabled and disabled states. The TRANSITION state should usually never be observed, because it only exists while enabling or disabling block change tracking. This state might be observed if the instance crashed while enabling or disabling block change tracking, in which case it will be cleaned up automatically the next time that the database is opened. • ENABLED - Block change tracking is enabled
FILENAME	VARCHAR2(513)	Name of the block change tracking file for the database
BYTES	NUMBER	Size of the block change tracking file (in bytes)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Backup and Recovery User's Guide* for information on setting up block change tracking

8.112 V$BLOCKING_QUIESCE

V$BLOCKING_QUIESCE indicates if a session is blocking, or would block, a quiesce operation.

Column	Datatype	Description
SID	NUMBER	Session identifier
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.113 V$BT_SCAN_CACHE

V$BT_SCAN_CACHE shows the parameters and status of the big table cache section.

Column	Datatype	Description
BT_CACHE_ALLOC	NUMBER	Current ratio of the big table cache section to the buffer cache
BT_CACHE_TARGET	NUMBER	Target ratio of the big table cache section to the buffer cache
OBJECT_COUNT	NUMBER	Number of objects tracked by the big table cache section
MEMORY_BUF_ALLOC	NUMBER	Number of memory buffers allocated by the big table cache section to objects
MIN_CACHED_TEMP	NUMBER	Minimum temperature of any object that is allowed to be cached by the big table cache section

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "DB_BIG_TABLE_CACHE_PERCENT_TARGET" for more information about enabling the big table cache

8.114 V$BT_SCAN_OBJ_TEMPS

V$BT_SCAN_OBJ_TEMPS shows the active objects currently tracked by the big table cache.

Column	Datatype	Description
TS#	NUMBER	Tablespace number
DATAOBJ#	NUMBER	Data object number (objd)
SIZE_IN_BLKS	NUMBER	Size of the object being scanned on this instance, in blocks
TEMPERATURE	NUMBER	Temperature of this object
POLICY	VARCHAR2(10)	Caching policy of this object. Possible values: • MEM_ONLY: This object will be fully cached in memory. • MEM_PART: This object will be partially cached in memory and some portion will remain on disk and will not be cached. • DISK: this object will not be cached in memory or flash for the scan at all. • INVALID: The caching policy is not valid.
CACHED_IN_MEM	NUMBER	The number of blocks that are cached/allocated in memory for this object
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "DB_BIG_TABLE_CACHE_PERCENT_TARGET" for more information about enabling the big table cache

8.115 V$BUFFER_POOL

V$BUFFER_POOL displays information about all buffer pools available for the instance.

Column	Datatype	Description
ID	NUMBER	Buffer pool identifier number
NAME	VARCHAR2(20)	Name of the buffer pool: • DEFAULT • KEEP • RECYCLE **Note:** Currently, KEEP and RECYCLE pools only exist for the standard block size. All nonstandard block size pools are DEFAULT.
BLOCK_SIZE	NUMBER	Block size (in bytes) for buffers in this pool. Possible values: the standard block size, the power of 2 nonstandard block sizes, 2048, 4096, 8192, 16384, 32768.
RESIZE_STATE	VARCHAR2(10)	Current state of the resize operation: STATIC - Not being resized ALLOCATING - Memory is being allocated (can be canceled by the user) ACTIVATING - New buffers are being created (user cannot cancel) SHRINKING - Buffers are being deleted (can be canceled by the user)
CURRENT_SIZE	NUMBER	Present size of the sub-cache (in megabytes)
BUFFERS	NUMBER	Current instantaneous number of buffers
TARGET_SIZE	NUMBER	If a resize is in progress (state is not STATIC), records new target size (in megabytes). If the pool is STATIC, the value in this column is the same as the current size of the pool.
TARGET_BUFFERS	NUMBER	If a resize is in progress, records new target size in terms of buffers. Otherwise, the value in this column is the same as the current number of buffers.
PREV_SIZE	NUMBER	Previous buffer pool size. If the buffer pool has never been resized, the previous size is zero.
PREV_BUFFERS	NUMBER	Previous number of buffers in the buffer pool. Value is zero if the buffer pool has never been resized.
LO_BNUM	NUMBER	Obsolete column
HI_BNUM	NUMBER	Obsolete column
LO_SETID	NUMBER	Obsolete column
HI_SETID	NUMBER	Obsolete column
SET_COUNT	NUMBER	Obsolete column

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "DB_BLOCK_SIZE"

8.116 V$BUFFER_POOL_STATISTICS

V$BUFFER_POOL_STATISTICS displays statistics about all buffer pools available for the instance.

Column	Datatype	Description
ID	NUMBER	Buffer pool identifier number
NAME	VARCHAR2(20)	Name of the buffer pool
BLOCK_SIZE	NUMBER	Block size (in bytes) for buffers in this pool. Possible values: the standard block size, the power of 2 nonstandard block sizes, 2048, 4096, 8192, 16384, 32768.
SET_MSIZE	NUMBER	Buffer pool maximum set size
CNUM_REPL	NUMBER	Number of buffers on replacement list
CNUM_WRITE	NUMBER	Number of buffers on write list
CNUM_SET	NUMBER	Number of buffers in set
BUF_GOT	NUMBER	Number of buffers gotten by the set
SUM_WRITE	NUMBER	Number of buffers written by the set
SUM_SCAN	NUMBER	Number of buffers scanned in the set
FREE_BUFFER_WAIT	NUMBER	Free buffer wait statistic
WRITE_COMPLETE_WAIT	NUMBER	Write complete wait statistic
BUFFER_BUSY_WAIT	NUMBER	Buffer busy wait statistic
FREE_BUFFER_INSPECTED	NUMBER	Free buffer inspected statistic
DIRTY_BUFFERS_INSPECTED	NUMBER	Dirty buffers inspected statistic
DB_BLOCK_CHANGE	NUMBER	Database blocks changed statistic
DB_BLOCK_GETS	NUMBER	Database blocks gotten statistic
CONSISTENT_GETS	NUMBER	Consistent gets statistic
PHYSICAL_READS	NUMBER	Physical reads statistic
PHYSICAL_WRITES	NUMBER	Physical writes statistic

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "DB_CACHE_SIZE"

8.117 V$BUFFERED_PUBLISHERS

V$BUFFERED_PUBLISHERS displays information about all buffered publishers in the instance.

There is one row per queue per sender. The values are reset to zero when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
QUEUE_ID	NUMBER	Identifier for the queue
QUEUE_SCHEMA	VARCHAR2(128)	Owner of the queue
QUEUE_NAME	VARCHAR2(128)	Name of the queue
SENDER_NAME	VARCHAR2(128)	Name of the agent enqueuing the message (the Streams name assigned for a capture process)
SENDER_ADDRESS	VARCHAR2(1024)	Queue name and database name of the source (last propagating) queue; database name is not specified if the source queue is in the local database
SENDER_PROTOCOL	NUMBER	Protocol used by the sender's address
NUM_MSGS	NUMBER	Current number of messages that have yet to be dequeued from the buffer queue
CNUM_MSGS	NUMBER	Cumulative total number of messages enqueued into the buffered queue since the database last started
LAST_ENQUEUED_MSG	NUMBER	Most recently enqueued message identifier
UNBROWSED_MSGS	NUMBER	Number of messages that have been enqueued but not browsed
OVERSPILLED_MSGS	NUMBER	Number of messages that have been spilled but not browsed
MEMORY_USAGE	NUMBER	Percentage of the Streams pool that is being used (or 0 if there is no Streams pool)
ELAPSED_ENQUEUE_TIME	NUMBER	Total time spent in enqueue (in hundredths of a second)
ENQUEUE_CPU_TIME	NUMBER	Total CPU time for enqueue (in hundredths of a second)
LAST_ENQUEUE_TIME	TIMESTAMP(3) WITH TIME ZONE	Last message enqueue time

Column	Datatype	Description
PUBLISHER_STATE	VARCHAR2(59)	State of the publisher: • IN FLOW CONTROL: TOO MANY UNBROWSED MESSAGES • IN FLOW CONTROL: OVERSPILLED MESSAGES • IN FLOW CONTROL: INSUFFICIENT MEMORY AND UNBROWSED MESSAGES • PUBLISHING MESSAGES - Normal
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.118 V$BUFFERED_QUEUES

V$BUFFERED_QUEUES displays information about all buffered queues in the instance. There is one row per queue.

Column	Datatype	Description
QUEUE_ID	NUMBER	Identifier for the queue
QUEUE_SCHEMA	VARCHAR2(128)	Owner of the queue
QUEUE_NAME	VARCHAR2(128)	Name of the queue
STARTUP_TIME	DATE	Startup time
NUM_MSGS	NUMBER	Total number of messages currently in the buffered queue
SPILL_MSGS	NUMBER	Current number of overflow messages spilled to disk from the buffered queue
CNUM_MSGS	NUMBER	Cumulative total number of messages enqueued into the buffered queue since the database last started
CSPILL_MSGS	NUMBER	Cumulative total number of overflow messages spilled to disk from the buffered queue since the database last started
EXPIRED_MSGS	NUMBER	Number of expired messages
OLDEST_MSGID	RAW(16)	Message ID of the oldest message
OLDEST_MSG_ENQTM	TIMESTAMP(3)	Enqueue time of the oldest message
QUEUE_STATE	VARCHAR2(25)	Indicates whether the queue is in recovery mode (QUEUE IS IN RECOVERY MODE) or not (NORMAL)
ELAPSED_ENQUEUE_TIME	NUMBER	Total time spent in enqueue (in hundredths of a second)
ELAPSED_DEQUEUE_TIME	NUMBER	Total time spent in dequeue (in hundredths of a second)
ELAPSED_TRANSFORMATION_TIME	NUMBER	Total time for evaluating transformations (in hundredths of a second)
ELAPSED_RULE_EVALUATION_TIME	NUMBER	Total time for rule evaluations (in hundredths of a second)
ENQUEUE_CPU_TIME	NUMBER	Total CPU time for enqueue (in hundredths of a second)

Column	Datatype	Description
DEQUEUE_CPU_TIME	NUMBER	Total CPU time for dequeue (in hundredths of a second)
AVG_MSG_AGE	NUMBER	Average age of messages in the queue
LAST_ENQUEUE_TIME	TIMESTAMP(3) WITH TIME ZONE	Last message enqueue time
LAST_DEQUEUE_TIME	TIMESTAMP(3) WITH TIME ZONE	Last message dequeue time
QUEUE_SIZE	NUMBER	Size of queue, which is the total number of bytes allocated for all messages and metadata
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.119 V$BUFFERED_SUBSCRIBERS

V$BUFFERED_SUBSCRIBERS displays information about the subscribers for all buffered queues in the instance. There is one row per subscriber per queue.

Column	Datatype	Description
QUEUE_ID	NUMBER	Identifier for the queue
QUEUE_SCHEMA	VARCHAR2(128)	Owner of the queue
QUEUE_NAME	VARCHAR2(128)	Name of the queue
SUBSCRIBER_ID	NUMBER	Internal subscriber number (for identification)
SUBSCRIBER_NAME	VARCHAR2(512)	Name of the subscriber
SUBSCRIBER_ADDRESS	VARCHAR2(1024)	Address of the subscribing agent
PROTOCOL	NUMBER	Protocol of the subscribing agent
SUBSCRIBER_TYPE	VARCHAR2(128)	Type of the subscriber: • PROXY - Proxy subscriber • SUBSCRIBER
STARTUP_TIME	DATE	Startup time
LAST_BROWSED_SEQ	NUMBER	Sequence number of the most recently browsed message for the subscriber (comparable to the number of messages in the V$STREAMS_APPLY_READER view)
LAST_BROWSED_NUM	NUMBER	Internal Message number for the most recently browsed message for the subscriber
LAST_DEQUEUED_SEQ	NUMBER	Sequence number of the most recently dequeued message for the subscriber (comparable to the number of messages in the V$STREAMS_APPLY_COORDINATOR view)
LAST_DEQUEUED_NUM	NUMBER	Internal Message number for the most recently dequeued message for the subscriber

Column	Datatype	Description
CURRENT_ENQ_SEQ	NUMBER	Current sequence number of the most recently enqueued message for the subscriber
NUM_MSGS	NUMBER	Total number of outstanding messages currently enqueued in the buffered queue for the subscriber (includes the count of the messages overflowed to disk)
CNUM_MSGS	NUMBER	Cumulative total number of messages enqueued for the subscriber since the database last started
TOTAL_DEQUEUED_MSG	NUMBER	Total number of messages dequeued by the subscriber
TOTAL_SPILLED_MSG	NUMBER	Total number of spilled messages for the subscriber
EXPIRED_MSGS	NUMBER	Number of expired messages
MESSAGE_LAG	NUMBER	Message lag of the subscriber
ELAPSED_DEQUEUE_TIME	NUMBER	Total time spent in dequeue (in hundredths of a second)
DEQUEUE_CPU_TIME	NUMBER	Total CPU time for dequeue (in hundredths of a second)
AVG_MSG_AGE	NUMBER	Average age of messages currently enqueued in the buffered queue for the subscriber
LAST_DEQUEUE_TIME	TIMESTAMP(3) WITH TIME ZONE	Last message dequeue time
OLDEST_MSGID	RAW(16)	Message ID of the oldest message
OLDEST_MSG_ENQTM	TIMESTAMP(3)	Enqueue time of the oldest message
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.120 V$CACHE

V$CACHE displays information from the block header of each block in the SGA of the current instance as related to particular database objects. This is an Oracle Real Application Clusters view.

Column	Datatype	Description
FILE#	NUMBER	Data file identifier number (to find the file name, query DBA_DATA_FILES or V$DBFILE)
BLOCK#	NUMBER	Block number
CLASS#	NUMBER	Class number

Column	Datatype	Description
STATUS	VARCHAR2(10)	Status of the block: • free - Not currently in use • xcur - Exclusive • scur - Shared current • cr - Consistent read • read - Being read from disk • mrec - In media recovery mode • irec - In instance recovery mode
XNC	NUMBER	Number of PCM x to null lock conversions due to contention with another instance. This column is obsolete and maintained for backward compatibility.
FORCED_READS	NUMBER	Number of times the block had to be reread from the cache because another instance has forced it out of this instance's cache by requesting the lock on the block in exclusive mode
FORCED_WRITES	NUMBER	Number of times GCS had to write this block to cache because this instance had used the block and another instance had requested the lock on the block in a conflicting mode
NAME	VARCHAR2(128)	Name of the database object containing the block
PARTITION_NAME	VARCHAR2(128)	Name of the partition (null for nonpartitioned objects)
KIND	VARCHAR2(15)	Type of the database object: • INDEX • TABLE • CLUSTER • VIEW • SYNONYM • SEQUENCE • PROCEDURE • FUNCTION • PACKAGE • NON-EXISTENT • PACKAGE BODY • TRIGGER • TYPE • TYPE BODY • TABLE PARTITION • INDEX PARTITION • LOB • LIBRARY • JAVA SOURCE • JAVA CLASS • JAVA RESOURCE • JAVA DATA • UNDO
OWNER#	NUMBER	Owner number
LOCK_ELEMENT_ADDR	RAW(4 | 8)	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.

Column	Datatype	Description
LOCK_ELEMENT_NAME	NUMBER	Name of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.121 V$CACHE_LOCK

V$CACHE_LOCK is deprecated. The information that was provided in this view is now provided in the V$INSTANCE_CACHE_TRANSFER and V$SEGMENT_STATISTICS views.

Column	Datatype	Description
FILE#	NUMBER	Data file identifier number (to find file name, query DBA_DATA_FILES or V$DBFILE)
BLOCK#	NUMBER	Block number
STATUS	VARCHAR2(10)	Status of the block: • free - Not currently in use • xcur - Exclusive • scur - Shared current • cr - Consistent read • read - Being read from disk • mrec - In media recovery mode • irec - In instance recovery mode
XNC	NUMBER	Number of parallel cache management (PCM) lock conversions due to contention with another instance
FORCED_READS	NUMBER	Number of times the block had to be reread from the cache because another instance has forced it out of this instance's cache by requesting the lock on the block in exclusive mode
FORCED_WRITES	NUMBER	Number of times GCS had to write this block to cache because this instance had used the block and another instance had requested the lock on the block in a conflicting mode
NAME	VARCHAR2(128)	Name of the database object containing the block

Column	Datatype	Description
KIND	VARCHAR2(15)	Type of database object: • 1 - Index • 2 - Table • 3 - Cluster • 4 - View • 5 - Synonym • 6 - Sequence • 7 - Procedure • 8 - Function • 9 - Package • 10 - Nonexistent • 11 - Package body • 12 - Trigger • 13 - Type • 14 - Type body • 19 - Table partition • 20 - Index partition • 21 - LOB • 22 - Library • Null - Unknown
OWNER#	NUMBER	Owner number
LOCK_ELEMENT_ADDR	RAW(4 | 8)	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
LOCK_ELEMENT_NAME	NUMBER	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
INDX	NUMBER	Platform-specific lock manager identifier
CLASS	NUMBER	Platform-specific lock manager identifier
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.122 V$CACHE_TRANSFER

V$CACHE_TRANSFER is identical to the V$CACHE view but only displays blocks that have been pinged at least once.

This view contains information from the block header of each block in the SGA of the current instance as related to particular database objects. This is an Oracle Real Application Clusters view.

Column	Datatype	Description
FILE#	NUMBER	Data file identifier number (to find the file name, query DBA_DATA_FILES or V$DBFILE)
BLOCK#	NUMBER	Block number
CLASS#	NUMBER	Class number
STATUS	VARCHAR2(10)	Status of the block: • free - Not currently in use • xcur - Exclusive • scur - Shared current • cr - Consistent read • read - Being read from disk • mrec - In media recovery mode • irec - In instance recovery mode
XNC	NUMBER	Number of PCM lock conversions due to contention with another instance. This column is obsolete and maintained for backward compatibility.
FORCED_READS	NUMBER	Number of times the block had to be reread from the cache because another instance has forced it out of this instance's cache by requesting the lock on the block in exclusive mode
FORCED_WRITES	NUMBER	Number of times GCS had to write this block to cache because this instance had used the block and another instance had requested the lock on the block in a conflicting mode
NAME	VARCHAR2(128)	Name of the database object containing the block
PARTITION_NAME	VARCHAR2(128)	NULL for nonpartitioned objects
KIND	VARCHAR2(15)	Type of database object **See Also:** Table 9-1
OWNER#	NUMBER	Owner number
LOCK_ELEMENT_ADDR	RAW(4 | 8)	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
LOCK_ELEMENT_NAME	NUMBER	The name of the lock that contains the PCM lock that is covering the buffer
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$CACHE"

8.123 V$CHUNK_METRIC

V$CHUNK_METRIC displays the metric values captured for the most recent 30-second intervals for the workload against each chunk available on the database.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
CHUNK_ID	NUMBER	Chunk number (internal)
CALLSPERSEC	NUMBER	Number of user calls per second to the chunks
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$SERVICE_REGION_METRIC"

8.124 V$CIRCUIT

V$CIRCUIT contains information about virtual circuits, which are user connections to the database through dispatchers and servers.

Column	Datatype	Description
CIRCUIT	RAW(4 | 8)	Circuit address
DISPATCHER	RAW(4 | 8)	Current dispatcher process address
SERVER	RAW(4 | 8)	Current server process address
WAITER	RAW(4 | 8)	Address of the server process that is waiting for the (currently busy) circuit to become available
SADDR	RAW(4 | 8)	Address of the session bound to the circuit
STATUS	VARCHAR2(16)	Status of the circuit: • BREAK - currently interrupted • EOF - about to be removed • OUTBOUND - an outward link to a remote database • NORMAL - normal circuit into the local database

Column	Datatype	Description
QUEUE	VARCHAR2(16)	Queue the circuit is currently on: • COMMON - on the common queue, waiting to be picked up by a server process • DISPATCHER - waiting for the dispatcher • SERVER - currently being serviced • NONE - idle circuit
MESSAGE0	NUMBER	Size in bytes of the messages in the first message buffer
MESSAGE1	NUMBER	Size in bytes of the messages in the second message buffer
MESSAGE2	NUMBER	Size in bytes of the messages in the third message buffer
MESSAGE3	NUMBER	Size in bytes of the messages in the fourth message buffer
MESSAGES	NUMBER	Total number of messages that have gone through this circuit
BYTES	NUMBER	Total number of bytes that have gone through this circuit
BREAKS	NUMBER	Total number of breaks (interruptions) for this circuit
PRESENTATION	VARCHAR2(257)	Presentation protocol used by the client and server
PCIRCUIT	RAW(4 | 8)	Address of the parent circuit
BOUND_TIME	NUMBER	Time that a circuit and shared server have been bound (in centiseconds)
BOUND_REASON	VARCHAR2(32)	Provides a reason (a short explanation) for why a shared server and circuit could not be unbound. This column is empty when a circuit is not bound to a server. When the server starts serving a circuit, BOUND_REASON is empty and remains empty unless the server tries unsuccessfully to unbind the circuit (after it finishes serving the current request). When this column is not empty, it will be cleared once the server and circuit are unbound (that is, once the resources preventing the session migration to another shared server are released).
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.125 V$CLASS_CACHE_TRANSFER

V$CLASS_CACHE_TRANSFER is deprecated. The information that was provided in this view is now provided in the V$INSTANCE_CACHE_TRANSFER and V$SEGMENT_STATISTICS views.

Column	Datatype	Description
CLASS	CHAR(10)	Block class; always data block
X_2_NULL	NUMBER	Number of blocks with Exclusive-to-NULL conversions; always 0
X_2_NULL_FORCED_WRITE	NUMBER	Number of Exclusive-to-NULL forced writes; always 0
X_2_NULL_FORCED_STALE	NUMBER	Number of Exclusive-to-NULL blocks converted to CR; always 0

Column	Datatype	Description
X_2_S	NUMBER	Number of blocks with Exclusive-to-Shared conversions; always 0
X_2_S_FORCED_WRITE	NUMBER	Number of Exclusive-to-Shared forced writes; always 0
S_2_NULL	NUMBER	Number of blocks with Shared-to-NULL conversions; always 0
S_2_NULL_FORCED_STALE	NUMBER	Number of Shared-to-NULL blocks converted to CR; always 0
NULL_2_X	NUMBER	Number of blocks with NULL-to-Exclusive conversions; always 0
S_2_X	NUMBER	Number of blocks with Shared-to-Exclusive conversions; always 0
NULL_2_S	NUMBER	Number of blocks with NULL-to-Shared conversions; always 0
CR_TRANSFER	NUMBER	Number of CR blocks transferred; always 0
CURRENT_TRANSFER	NUMBER	Number of current blocks transferred; always 0
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$INSTANCE_CACHE_TRANSFER"
- "V$SEGMENT_STATISTICS"

8.126 V$CLEANUP_PROCESS

V$CLEANUP_PROCESS provides information on the PMON processes.

Column	Datatype	Description
NAME	VARCHAR2(5)	Name of the cleanup process (PMON, CLMN, CL**)
PADDR	RAW(8)	Process pointer for the cleanup process (can join with V$PROCESS)
SADDR	RAW(8)	Session pointer for the cleanup process (can join with V$SESSION)
STATE	VARCHAR2(4)	Cleanup process state: • IDLE: Not currently performing cleanup • BUSY: Currently performing cleanup
DEAD_IN_CLEANUP	RAW(8)	Pointer to the root of the tree in cleanup (can join with ROOT_ADDR in V$DEAD_CLEANUP)
CLEANUP_TIME	NUMBER	If STATE = BUSY, the time spent in the current cleanup attempt (in seconds). Otherwise, 0.
TIME_SINCE_LAST_CLEANUP	NUMBER	If STATE = IDLE, time since last needed to perform cleanup (in seconds). Otherwise, 0.

Column	Datatype	Description
NUM_CLEANED	NUMBER	Number of trees cleaned up by the cleanup process. Increased by one every time a root tree is attempted.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$DEAD_CLEANUP"

8.127 V$CLIENT_SECRETS

V$CLIENT_SECRETS lists the secrets that are present in the keystore.

Only SYS, SYSKM, and users with the ADMINISTER KEY MANAGEMENT privilege can access this view.

Column	Datatype	Description
CLIENT	VARCHAR2(2000)	Name provided by the client
SECRET_TAG	VARCHAR2(4000)	Associated information with the client
CREATION_TIME	TIMESTAMP(6) WITH TIME ZONE	Time when the secret was created
ACTIVATION_TIME	TIMESTAMP(6) WITH TIME ZONE	Time when the secret was actually put to use
OWNER	VARCHAR2(128)	User who created the secret
OWNER_ID	NUMBER	User ID of the user who created the secret
KEYSTORE_TYPE	VARCHAR2(17)	Type of keystore in which the secret is stored: • OKV - Oracle Key Vault • SOFTWARE KEYSTORE • UNDEFINED - This value is shown if the database has no information about the type of keystore where the master key resides
BACKED_UP	VARCHAR2(9)	Indicates whether the secret has been backed up or not
OWNER_DBNAME	VARCHAR2(128)	Database that created the secret
OWNER_DBID	NUMBER	Database ID where the secret was created
OWNER_INSTANCE_NAME	VARCHAR2(30)	Instance name of the instance where the secret was created
OWNER_INSTANCE_NUMBER	NUMBER	Instance number of the instance where the secret was created

Column	Datatype	Description
OWNER_INSTANCE_SERIAL	NUMBER	Serial number of the instance where the secret was created
OWNER_PDBNAME	VARCHAR2(128)	Pluggable database (PDB) where the secret was created
OWNER_PDBID	NUMBER	PDB ID where the secret was created
OWNER_PDBUID	NUMBER	PDB UID where the secret was created
OWNER_PDBGUID	RAW(16)	PDB GUID where the secret was created
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database Advanced Security Guide for information about keystore management

8.128 V$CLIENT_STATS

V$CLIENT_STATS displays measures for all sessions that are active for the client identifier per instance.

The statistics available in this view are a subset of those available in V$SESSTAT and V$SESS_TIME_MODEL.

Column	Datatype	Description
CLIENT_IDENTIFIER	VARCHAR2(64)	Client identifier
STAT_ID	NUMBER	Statistic identifier
STAT_NAME	VARCHAR2(64)	Derived statistic name from V$STATNAME and V$SESS_TIME_MODEL
VALUE	NUMBER	Cumulative value (in microseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> - "V$SESSTAT"
> - "V$SESS_TIME_MODEL"

8.129 V$CLONEDFILE

V$CLONEDFILE provides CloneDB file information.

Column	Datatype	Description
SNAPSHOTFILENAME	VARCHAR2(513)	Snapshot file name. This file is the snapshot file from the snapshot database. The snapshot file is also sometimes referred to as the srcfile.
CLONEFILENAME	VARCHAR2(513)	CloneDB file name. This file is the cloned file (of the snapshot file) which resides in the current (cloned database). The cloned file is sometimes referred to as the destfile.
SNAPSHOTBLKREAD	NUMBER	Number of blocks reads to the snapshot file
SNAPSHOTREQUEST	NUMBER	Number of read requests to the snapshot file
FILENUMBER	NUMBER	File number of the cloned file
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
BLOCKS_ALLOCATED	NUMBER	Amount of space allocated in blocks in the file system. This is less than or equal to the actual file size.

> **Note:**
>
> When this view is queried in an Oracle Database environment, rows are returned for every opened file, even those without a parent file backing them (in those cases the column is empty/NULL).
>
> In an Oracle ASM environement, rows are returned for files that an Oracle ASM instance has mounted in disk groups only if those files are children (a clonefile) of a parent snapshot file.

8.130 V$CLUSTER_INTERCONNECTS

V$CLUSTER_INTERCONNECTS displays one or more interconnects that are being used for cluster communication.

Column	Datatype	Description
NAME	VARCHAR2(15)	Name of the interconnect (such as eth0)
IP_ADDRESS	VARCHAR2(46)	IP address of the interconnect
IS_PUBLIC	VARCHAR2(3)	If the value is YES, the interface is known to the public. If the value is NO, the interface is known to be private. Note that if the CLUSTER_INTERCONNETS initialization parameter is also specified, then it is expected that the interconnect is private. Oracle expects cluster traffic to be run on private interconnects only. f the value is empty, it is unknown whether the interface is public or private. Oracle recommends that you set the interface for Oracle Real Application Clusters (Oracle RAC) communication in the Oracle Cluster Registry (OCR).
SOURCE	VARCHAR2(31)	Indicates where this interface was picked up from: • Oracle Cluster Registry - Interface was configured in the OCR and Oracle Database found the interface in the OCR • Operating-system dependent software - Oracle Database automatically detects this • CLUSTER_INTERCONNECTS parameter - This initialization parameter was set
PNAME	VARCHAR2(15)	Name of the physical interface of the interconnect This value may differ from the NAME value if the IP address is bound to a device alias. For example, if NAME is eth0:1, then PNAME is eth0.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.131 V$CODE_CLAUSE

V$CODE_CLAUSE contains the supported clause names and parameter names for the Oracle Data Vault ALTER SYSTEM and ALTER SESSION commands.

Column	Datatype	Description
CODE_ID#	NUMBER	The OCT code ID: • 42: For ALTER SESSION • 49: For ALTER SYSTEM
CLAUSE_ID#	NUMBER	Clause ID
CLAUSE_NAME	VARCHAR2(100)	The clause name that is supported by the Oracle Data Vault command rule (for example, SET or ADVICE)
PARAMETER_NAME	VARCHAR2(100)	The parameter name that is supported by the Oracle Data Vault command rule. For example, for ALTER SYSTEM SET EVENTS, EVENTS is the parameter.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.132 V$CON_EVENT_HISTOGRAM_MICRO

V$CON_EVENT_HISTOGRAM_MICRO displays a histogram of the number of waits, the maximum wait, and total wait time on an event basis for a container, in microseconds. The histogram has buckets of time intervals from < 1 us, < 2 us, < 4 us, < 8 us, ... < 2^{31} us, < 2^{32} us, and >= 2^{32} us.

The histogram will not be filled unless the TIMED_STATISTICS initialization parameter is set to true.

Column	Datatype	Description
EVENT#	NUMBER	Event number
EVENT	VARCHAR2(64)	Name of the event
WAIT_TIME_FORMAT	VARCHAR2(30)	A human readable time string which is converted from WAIT_TIME_MICRO. When WAIT_TIME_MICRO < 1 millisecond, WAIT_TIME_FORMAT is shown in microseconds. When WAIT_TIME_MICRO < 1 second, WAIT_TIME_FORMAT is shown in milliseconds. When WAIT_TIME_MICRO < 1 minute, WAIT_TIME_FORMAT is shown in seconds. When WAIT_TIME_MICRO > 1 minute, WAIT_TIME_FORMAT is shown in minutes and seconds.
WAIT_TIME_MICRO	NUMBER	Amount of time the bucket represents (in microseconds). If the duration = num, then this column represents waits of duration < num that are not included in any smaller bucket.
WAIT_COUNT	NUMBER	Number of waits of the duration belonging to the bucket of the histogram
LAST_UPDATE_TIME	VARCHAR2(73)	Indicates the last time the bucket was updated (the ending timestamp of the last wait falling into the bucket's duration)
CON_ID	NUMBER	When queried from a non-CDB, the wait event data in that instance are returned, and the CON_ID value is 0. When queried from the root of a CDB, the wait event data in every container is returned, and the CON_ID value indicates the container to which the wait event data belong. When queried from a PDB, wait event data in that PDB are returned, and the CON_ID value is the container ID for that PDB.

8.133 V$CON_SYS_TIME_MODEL

V$CON_SYS_TIME_MODEL displays the systemwide accumulated times for various operations for the container from which it is queried.

The time reported is the total elapsed or CPU time (in microseconds). Any timed operation will buffer at most 5 seconds of time data. Specifically, this means that if a timed operation (such as SQL execution) takes a long period of time to perform, the data published to this view is at most missing 5 seconds of the time accumulated for the operation.

The time values are 8-byte integers and can therefore hold approximately 580,000 years worth of time before wrapping. Background process time is not included in a statistic value unless the statistic is specifically for background processes.

Column	Datatype	Description
STAT_ID	NUMBER	Statistic identifier for the time statistic
STAT_NAME	VARCHAR2(64)	Name of the statistic (see Table 10-1)
VALUE	NUMBER	Amount of time (in microseconds) that the system has spent in this operation
CON_ID	NUMBER	When queried from a non-CDB, the accumulated times for operations in that instance are returned, and the CON_ID value is 0. When queried from the root of a CDB, accumulated times for operations in every container are returned, and the CON_ID value indicates the container to which the times belong. When queried from a PDB, accumulated times for operations in that PDB are returned, and the CON_ID value is the container ID for that PDB.

8.134 V$CON_SYSMETRIC

V$CON_SYSMETRIC displays the system metric values captured for the most current time interval for the PDB long duration (60-second) system metrics.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	Metric group ID
METRIC_ID	NUMBER	Metric ID
METRIC_NAME	VARCHAR2(64)	Metric name
VALUE	NUMBER	Metric value
METRIC_UNIT	VARCHAR2(64)	Metric unit description

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • When queried from a non-CDB, the statistics for that instance are returned, and the CON_ID value is 0. • When queried from the root of a CDB, the statistics for every container are returned, and the CON_ID value indicates the container to which the statistics belong. • When queried from a PDB, statistics from that PDB are returned, and the CON_ID value is the container ID for that PDB.

See Also:

- "DBA_HIST_CON_SYS_TIME_MODEL"
- "DBA_HIST_SYS_TIME_MODEL"
- "V$SYSMETRIC"

8.135 V$CON_SYSMETRIC_HISTORY

V$CON_SYSMETRIC_HISTORY displays all PDB long duration (60-second with 1 hour history) system metric values available in the database.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	Metric group ID
METRIC_ID	NUMBER	Metric ID
METRIC_NAME	VARCHAR2(64)	Metric name
VALUE	NUMBER	Metric value
METRIC_UNIT	VARCHAR2(64)	Metric unit description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • When queried from a non-CDB, the statistics for that instance are returned, and the CON_ID value is 0. • When queried from the root of a CDB, the statistics for every container are returned, and the CON_ID value indicates the container to which the statistics belong. • When queried from a PDB, statistics from that PDB are returned, and the CON_ID value is the container ID for that PDB.

See Also:

- "DBA_HIST_CON_SYSMETRIC_HIST"
- "DBA_HIST_SYSMETRIC_HISTORY"
- "V$SYSMETRIC_HISTORY"

8.136 V$CON_SYSMETRIC_SUMMARY

`V$CON_SYSMETRIC_SUMMARY` displays a summary of all system metric values for the PDB long-duration system metrics. The average, maximum value, minimum value, and the value of one standard deviation for the last hour are displayed for each metric item.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	Metric group ID
METRIC_ID	NUMBER	Metric ID
METRIC_NAME	VARCHAR2(64)	Metric name
NUM_INTERVAL	NUMBER	Number of intervals observed
MAXVAL	NUMBER	Maximum value observed
MINVAL	NUMBER	Minimum value observed
AVERAGE	NUMBER	Average value over the period
STANDARD_DEVIATION	NUMBER	One standard deviation
METRIC_UNIT	VARCHAR2(64)	Metric unit description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • When queried from a non-CDB, the statistics for that instance are returned, and the CON_ID value is 0. • When queried from the root of a CDB, the statistics for every container are returned, and the CON_ID value indicates the container to which the statistics belong. • When queried from a PDB, statistics from that PDB are returned, and the CON_ID value is the container ID for that PDB.

See Also:

- "V$SYSMETRIC_HISTORY"
- "DBA_HIST_SYSMETRIC_SUMMARY"
- "V$SYSMETRIC_SUMMARY"

8.137 V$CON_SYSSTAT

V$CON_SYSSTAT displays system statistics, including OLAP kernel statistics for the container from which it is queried. To find the name of the statistic associated with each statistic number (STATISTIC#), query the V$STATNAME view.

Column	Datatype	Description
STATISTIC#	NUMBER	Statistic number **Note:** Statistics numbers are not guaranteed to remain constant from one release to another. Therefore, you should rely on the statistics name rather than its number in your applications.
NAME	VARCHAR2(64)	Statistic name. You can get a complete listing of statistic names by querying the V$STATNAME view.
CLASS	NUMBER	A number representing one or more statistics class. The following class numbers are additive: • 1 - User • 2 - Redo • 4 - Enqueue • 8 - Cache • 16 - OS • 32 - Real Application Clusters • 64 - SQL • 128 - Debug • 256 - Instance level
VALUE	NUMBER	Statistic value
STAT_ID	NUMBER	Identifier of the statistic
CON_ID	NUMBER	When queried from a non-CDB, the statistics in that instance are returned, and the CON_ID value is 0. When queried from the root of a CDB, the statistics in every container are returned, and the CON_ID value indicates the container to which the statistics belong. When queried from a PDB, statistics in that PDB are returned, and the CON_ID value is the container ID for that PDB.

See Also:

"V$STATNAME" and " Statistics Descriptions"

8.138 V$CON_SYSTEM_EVENT

V$CON_SYSTEM_EVENT displays information on total waits for an event in a container.

Note that the TIME_WAITED and AVERAGE_WAIT columns will contain a value of zero on those platforms that do not support a fast timing mechanism. If you are running on one of these platforms and you want this column to reflect true wait times, then you must set

TIMED_STATISTICS to TRUE in the parameter file; doing this will have a small negative effect on system performance.

> **See Also:**
>
> "TIMED_STATISTICS"

Column	Datatype	Description
EVENT	VARCHAR2(64)	Name of the wait event; derived statistic name from V$EVENT_NAME **See Also:** " Oracle Wait Events"
TOTAL_WAITS	NUMBER	Total number of waits for the event
TOTAL_TIMEOUTS	NUMBER	Total number of timeouts for the event
TIME_WAITED	NUMBER	Total amount of time waited for the event (in hundredths of a second)
AVERAGE_WAIT	NUMBER	Average amount of time waited for the event (in hundredths of a second)
TIME_WAITED_MICRO	NUMBER	Total amount of time waited for the event (in microseconds)
CPU	NUMBER	Total amount of CPU time consumed while implementing the wait event itself (in microseconds)
TOTAL_WAITS_FG	NUMBER	Total number of waits for the event, from foreground sessions
TOTAL_TIMEOUTS_FG	NUMBER	Total number of timeouts for the event, from foreground sessions
TIME_WAITED_FG	NUMBER	Total amount of time waited for the event, from foreground sessions (in hundredths of a second)
AVERAGE_WAIT_FG	NUMBER	Average amount of time waited for the event, from foreground sessions (in hundredths of a second)
TIME_WAITED_MICRO_FG	NUMBER	Total amount of time waited for the event, from foreground sessions (in microseconds)
CPU_FG	NUMBER	Total amount of CPU time consumed while implementing the wait event itself, from foreground sessions (in microseconds)
EVENT_ID	NUMBER	Identifier of the wait event
WAIT_CLASS_ID	NUMBER	Identifier of the wait class of the wait event
WAIT_CLASS#	NUMBER	Number of the wait class of the wait event
WAIT_CLASS	VARCHAR2(64)	Name of the wait class of the wait event
CON_ID	NUMBER	When queried from a non-CDB, the wait event data in that instance are returned, and the CON_ID value is 0. When queried from the root of a CDB, the wait event data in every container is returned, and the CON_ID value indicates the container to which the wait event data belong. When queried from a PDB, wait event data in that PDB are returned, and the CON_ID value is the container ID for that PDB.

8.139 V$CON_SYSTEM_WAIT_CLASS

V$CON_SYSTEM_WAIT_CLASS displays the time totals for each registered wait class in a container.

Column	Datatype	Description
WAIT_CLASS_ID	NUMBER	Identifier of the wait class
WAIT_CLASS#	NUMBER	Number of the wait class
WAIT_CLASS	VARCHAR2(64)	Name of the wait class
TOTAL_WAITS	NUMBER	Total number of waits from this wait class
TIME_WAITED	NUMBER	Total amount of time spent in waits from this wait class (in hundredths of a second)
TIME_WAITED_MICRO	NUMBER	Total amount of time spent in waits from this wait class (in microseconds)
CPU	NUMBER	Total amount of CPU time consumed while implementing waits from this wait class (in microseconds)
TOTAL_WAITS_FG	NUMBER	Total number of waits from this wait class, from foreground sessions
TIME_WAITED_FG	NUMBER	Total amount of time spent in waits from this wait class, from foreground sessions (in hundredths of a second)
TIME_WAITED_MICRO_FG	NUMBER	Total amount of time spent in waits from this wait class, from foreground sessions (in microseconds)
CPU_FG	NUMBER	Total amount of CPU time consumed while implementing waits from this wait class, from foreground sessions (in microseconds)
CON_ID	NUMBER	When queried from a non-CDB, time totals for each registered wait class in that instance are returned, and the CON_ID value is 0. When queried from the root of a CDB, time totals for each registered wait class in every container is returned, and the CON_ID value indicates the container to which the time total belong. When queried from a PDB, time totals for each registered wait class in that PDB are returned, and the CON_ID value is the container ID for that PDB.

8.140 V$CONFIGURED_INTERCONNECTS

V$CONFIGURED_INTERCONNECTS displays all the interconnects that Oracle is aware of. This view attempts to answer the question of where Oracle found the information about a specific interconnect.

Column	Datatype	Description
NAME	VARCHAR2(15)	Name of the interconnect (such as eth0)
IP_ADDRESS	VARCHAR2(64)	IP address of the interconnect

Column	Datatype	Description
IS_PUBLIC	VARCHAR2(3)	If the value is YES, the interface is known to the public. If the value is NO, the interface is known to be private. Note that if the CLUSTER_INTERCONNECTS initialization parameter is also specified, then it is expected that the interconnect is private. Oracle expects cluster traffic to be run on private interconnects only. If the value is empty, it is unknown whether the interface is public or private. Oracle recommends that you set the interface for Oracle Real Application Clusters (Oracle RAC) communication in the Oracle Cluster Registry (OCR).
SOURCE	VARCHAR2(31)	Indicates where this interface was picked up from: • Oracle Cluster Registry - Interface was configured in the OCR and Oracle Database found the interface in the OCR • Operating-system dependent software - Oracle Database automatically detects this • CLUSTER_INTERCONNECTS parameter - This initialization parameter was set
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.141 V$CONTAINER_TOPOLOGY

V$CONTAINER_TOPOLOGY displays information about the containers associated with the current instance.

Column	Datatype	Description
INSTANCE_NUMBER	NUMBER	Instance number, as specified by the INSTANCE_NUMBER initialization parameter for the database in which the container resides
CON_NAME	VARCHAR2(128)	Container name
OPEN_MODE	VARCHAR2(10)	Open mode for the container: • MIGRATE • MOUNTED • READ ONLY • READ WRITE
CPU_COUNT	NUMBER	CPU count, as specified by the CPU_COUNT initialization parameter for the container

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
RESTRICTED	VARCHAR2(3)	Indicates whether a user connecting to the container is required to have the RESTRICTED SESSION privilege (YES) or not (NO)
IS_HYBRID_READ_ONLY	VARCHAR2(3)	Indicates whether the container is in hybrid read-only mode (YES) or not (NO)

8.142 V$CONTAINERS

V$CONTAINERS displays information about PDBs and the root associated with the current instance.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
DBID	NUMBER	PDB identifier calculated when the PDB is created and stored in all file headers associated with the PDB
CON_UID	NUMBER	Unique identifier associated with the PDB
GUID	RAW(16)	Globally unique identifier (GUID) of this PDB
NAME	VARCHAR2(128)	Name of the PDB
OPEN_MODE	VARCHAR2(10)	Open mode information. Possible values: • MOUNTED • READ WRITE • READ ONLY • MIGRATE
RESTRICTED	VARCHAR2(3)	Indicates whether only users possessing RESTRICTED SESSION privilege can connect to the PDB
OPEN_TIME	TIMESTAMP(3)	Date and time when the database was last opened
CREATE_SCN	NUMBER	System change number (SCN) for the creation of this PDB
TOTAL_SIZE	NUMBER	If a PDB is opened, disk space (in bytes) used by the container, including both data and temp files. If a PDB is closed, will be set to 0.
BLOCK_SIZE	NUMBER	The current block size for the PDB

Column	Datatype	Description
RECOVERY_STATUS	VARCHAR2(26)	Shows the recovery status for the PDB. Possible values: • DISABLED: The PDB is offline. This is similar to all files belonging to this PDB being offline, except that all files to be added to this PDB in the future will also be offline to begin with. • DISABLED AUTOMATIC RECOVER: Same as DISABLED, except that standby Active Data Guard recovery will automatically attempt to spawn PDB recovery isolation for the PDB and transition the PDB into ENABLED. • ENABLED: The PDB is not offline at the PDB level. Individual files in the PDB may be online or offline at the file level.
SNAPSHOT_PARENT_CON_ID	NUMBER	This column shows the container ID of the PDB that this PDB is a snapshot clone of. This column shows a nonzero value only if the PDB is a snapshot clone. For all other cases, it shows a value of 0.
APPLICATION_ROOT	VARCHAR2(3)	Indicates whether the PDB is an application root
APPLICATION_PDB	VARCHAR2(3)	Indicates whether the PDB is an application PDB
APPLICATION_SEED	VARCHAR2(3)	Indicates whether the PDB is an application seed (an application seed is also an application PDB)
APPLICATION_ROOT_CON_ID	NUMBER	If this PDB is an application PDB, the container ID of an application root to which this application PDB belongs. If this PDB is an application root clone, the container ID of an application root to which this application root clone belongs. Otherwise, NULL.
APPLICATION_ROOT_CLONE	VARCHAR2(3)	Indicates whether this PDB is an application root clone (YES) or not (NO)
PROXY_PDB	VARCHAR2(3)	Indicates whether this PDB is a proxy PDB (YES) or not (NO)
LOCAL_UNDO	NUMBER	Shows whether the PDB is in local undo. Possible values: • 1 – PDB is in local undo mode • 0 – PDB is in shared undo mode This column is not relevant for CDB$ROOT.
UNDO_SCN	NUMBER	System change number (SCN) at which the PDB was last converted from shared to local undo, or from local to shared undo. This column is not relevant for CDB$ROOT.
UNDO_TIMESTAMP	DATE	Date and time at which the PDB was last converted from shared to local undo, or from local to shared undo. This column is not relevant for CDB$ROOT.
CREATION_TIME	DATE	Date and time at which the PDB was created.
PDB_COUNT	NUMBER	The number of user-created PDBs belonging to a given application root or CDB$ROOT. For all other containers, its value is 0.
AUDIT_FILES_SIZE	NUMBER	Shows the current disk space usage (in bytes) by Unified Audit files (.bin format) in the container
MAX_SIZE	NUMBER	Shows the maximum amount of disk space (in bytes) that can be used by data and temp files in the container
MAX_DIAGNOSTICS_SIZE	NUMBER	Shows the maximum amount of disk space (in bytes) that can be used by diagnostic traces generated in the container

Column	Datatype	Description
MAX_AUDIT_SIZE	NUMBER	Shows the maximum amount of disk space (in bytes) that can be used by Unified Audit files (.bin format) in the container
LAST_CHANGED_BY	VARCHAR2(11)	Indicates what type of user last changed the PDB. Possible values: • COMMON USER • LOCAL USER
MEMBER_CDB	VARCHAR2(3)	Indicates whether the row corresponds to a Member CDB part of the CDB Fleet (YES) or not (NO). This column is only meaningful in the Lead CDB of a CDB Fleet, which keeps track of other CDBs as containers in the CDB Fleet.
TENANT_ID	VARCHAR2(256)	Pluggable database tenant key
UPGRADE_LEVEL	NUMBER	For internal use only
GUID_BASE64	VARCHAR2(30)	The GUID of the PDB, encoded in base64
CLOUD_IDENTITY	VARCHAR2(4000)	Cloud identifier for the PDB
CLOSE_TIME	TIMESTAMP(3)	Date and time when the database was last closed
BACKUP_STATUS	VARCHAR2(8)	Reserved for future use

8.143 V$CONTEXT

V$CONTEXT displays set attributes in the current session.

Column	Datatype	Description
NAMESPACE	VARCHAR2(31)	Namespace that the attribute is in
ATTRIBUTE	VARCHAR2(31)	Name of the attribute
VALUE	VARCHAR2(4000)	Value of the attribute
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.144 V$CONTROLFILE

V$CONTROLFILE displays the names of the control files.

Column	Datatype	Description
STATUS	VARCHAR2(7)	INVALID if the name cannot be determined (which should not occur); NULL if the name can be determined
NAME	VARCHAR2(513)	Name of the control file
IS_RECOVERY_DEST_FILE	VARCHAR2(3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)

Column	Datatype	Description
BLOCK_SIZE	NUMBER	Control file block size
FILE_SIZE_BLKS	NUMBER	Control file size (in blocks)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.145 V$CONTROLFILE_RECORD_SECTION

V$CONTROLFILE_RECORD_SECTION displays information about the control file record sections.

Column	Datatype	Description
TYPE	VARCHAR2(28)	Identifies the type of record section: • DATABASE • CKPT PROGRESS • REDO THREAD • REDO LOG • DATAFILE • FILENAME • TABLESPACE • TEMPORARY FILENAME • RMAN CONFIGURATION • LOG HISTORY • OFFLINE RANGE • ARCHIVED LOG • BACKUP SET • BACKUP PIECE • BACKUP DATAFILE • BACKUP REDOLOG • DATAFILE COPY • BACKUP CORRUPTION • COPY CORRUPTION • DELETED OBJECT • PROXY COPY • BACKUP SPFILE • DATABASE INCARNATION • FLASHBACK LOG • RECOVERY DESTINATION • INSTANCE SPACE RESERVATION • REMOVABLE RECOVERY FILES • RMAN STATUS • THREAD INSTANCE NAME MAPPING • MTTR • DATAFILE HISTORY • PLUGGED IN DATAFILE
RECORD_SIZE	NUMBER	Record size in bytes
RECORDS_TOTAL	NUMBER	Number of records allocated for the section
RECORDS_USED	NUMBER	Number of records used in the section
FIRST_INDEX	NUMBER	Index (position) of the first record
LAST_INDEX	NUMBER	Index of the last record
LAST_RECID	NUMBER	Record ID of the last record
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.146 V$COPY_CORRUPTION

V$COPY_CORRUPTION displays information about data file copy corruptions from the control file.

Column	Datatype	Description
RECID	NUMBER	Copy corruption record ID
STAMP	NUMBER	Copy corruption record stamp
COPY_RECID	NUMBER	Data file copy record ID
COPY_STAMP	NUMBER	Data file copy record stamp
FILE#	NUMBER	Data file number
BLOCK#	NUMBER	First block of the corrupted range
BLOCKS	NUMBER	Number of contiguous blocks in the corrupted range
CORRUPTION_CHANGE#	NUMBER	Change number at which the logical corruption was detected. Set to 0 to indicate media corruption.
MARKED_CORRUPT	VARCHAR2(3)	(YES | NO) If set to YES the blocks were not marked corrupted in the data file, but were detected and marked as corrupted while making the data file copy
CORRUPTION_TYPE	VARCHAR2(9)	Type of block corruption in the data file: • ALL ZERO - Block header on disk contained only zeros. The block may be valid if it was never filled and if it is in an Oracle7 file. The buffer will be reformatted to the Oracle8 standard for an empty block. • FRACTURED - Block header looks reasonable, but the front and back of the block are different versions. • CHECKSUM - optional check value shows that the block is not self-consistent. It is impossible to determine exactly why the check value fails, but it probably fails because sectors in the middle of the block are from different versions. • CORRUPT - Block is wrongly identified or is not a data block (for example, the data block address is missing) • LOGICAL - Block is logically corrupt • NOLOGGING - Block does not have redo log entries (for example, NOLOGGING operations on primary database can introduce this type of corruption on a physical standby)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.147 V$COPY_NONLOGGED

V$COPY_NONLOGGED displays information about nonlogged block ranges in data file copy blocks, recorded in the control file.

Column	Datatype	Description
INST_ID	NUMBER	Instance ID
RECID	NUMBER	Nonlogged copy record ID
STAMP	NUMBER	Nonlogged copy record stamp
COPY_RECID	NUMBER	Data file copy record ID
COPY_STAMP	NUMBER	Data file copy record stamp
FILE#	NUMBER	Absolute file number of the data file that contains this range of nonlogged blocks
BLOCK#	NUMBER	Block number of the first nonlogged block in the range of nologged blocks
BLOCKS	NUMBER	Number of nonlogged blocks found starting with BLOCK#
NONLOGGED_CHANGE#	NUMBER	The smallest SCN on which any block in this block range became nonlogged. NULL if unknown.
NONLOGGED_TIME	VARCHAR2	The time that corresponds to NONLOGGED_CHANGE#. NULL if unknown.
RESETLOGS_CHANGE#	VARCHAR2	The resetlogs SCN of the incarnation on which this block range was first marked as nonlogged. NULL if unknown.
RESETLOGS_TIME	VARCHAR2	The resetlogs time of the incarnation on which this block range was first marked as nologged. NULL if unknown.
OBJECT#	VARCHAR2	The object ID this range belongs to. If this field is NULL, the object number is unknown.
REASON	CHAR(7)	The reason why this block range appears in this list, for example, primary file offline, could not talk to primary, non-standby recovery, and so on. For Oracle Database 12*c* and later releases, it is always UNKNOWN.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.148 V$CORRUPT_XID_LIST

V$CORRUPT_XID_LIST displays all corrupted XIDs.

Column	Datatype	Description
CORRUPT_XID	VARCHAR2(256)	Name of corrupt XID

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.149 V$CPOOL_CC_INFO

V$CPOOL_CC_INFO displays information about the pool-to-connection class mapping for the Database Resident Connection Pool per instance.

Column	Datatype	Description
POOL_NAME	VARCHAR2(1024)	Name of the Database Resident Connection Pool
CCLASS_NAME	VARCHAR2(1024)	Name of the connection class
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.150 V$CPOOL_CC_STATS

V$CPOOL_CC_STATS displays information about the connection class level statistics for the Database Resident Connection Pool per instance.

Column	Datatype	Description
POOL_NAME	VARCHAR2(1024)	Name of the Database Resident Connection Pool
CCLASS_NAME	VARCHAR2(1024)	Name of the connection class
NUM_REQUESTS	NUMBER	Number of session requests
NUM_HITS	NUMBER	Total number of times a session that matches with the request was found in the pool
NUM_MISSES	NUMBER	Total number of times an exact match to the request was not found in the pool and a new session had to be created
NUM_WAITS	NUMBER	Total number of times session requests had to wait before getting served
WAIT_TIME	NUMBER	Reserved for future use
CLIENT_REQ_TIMEOUTS	NUMBER	Reserved for future use
NUM_AUTHENTICATIONS	NUMBER	Total number of authentications of clients done by the pool

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view returns data only when queried from a CDB root. When queried from a PDB, this view returns 0 rows.

8.151 V$CPOOL_CONN_INFO

V$CPOOL_CONN_INFO displays connection information about each connection to the connection broker.

Column	Datatype	Description
CMON_ADDR	RAW(4 | 8)	Address of the connection broker
SESSION_ADDR	RAW(4 | 8)	Address of the session associated with the connection; NULL if the connection does not have an associated session
CONNECTION_ADDR	RAW(4 | 8)	Address of the connection
POOL_NAME	VARCHAR2(1024)	Name of the Database Resident Connection Pool
USERNAME	VARCHAR2(1024)	Name of the user associated with the connection
PROXY_USER	VARCHAR2(1024)	Name of the proxy user
CCLASS_NAME	VARCHAR2(1024)	Connection class associated with the connection
PURITY	VARCHAR2(1024)	Purity used to create the connection (can be SELF or NEW)
TAG	VARCHAR2(1024)	Tag, if specified, at connection creation time
SERVICE	VARCHAR2(64)	TNS service name for the connection
PROCESS_ID	VARCHAR2(24)	Client process ID of the process which created the connection
PROGRAM	VARCHAR2(84)	Program name of the client process which created the connection
MACHINE	VARCHAR2(64)	Machine name of the client process which created the connection
TERMINAL	VARCHAR2(30)	Terminal identifier of the client process which created the connection
CONNECTION_MODE	VARCHAR2(1024)	Reserved for internal use

Column	Datatype	Description
CONNECTION_STATUS	VARCHAR2(10)	Status of the connection: • NONE • CONNECTING • ACTIVE: A pooled server has been mapped to this connection. • WAITING: The connection is waiting for a pooled server based on the client request. • IDLE: No pooled server has been mapped to this connection and there is no request to map one. • CLOSING
CLIENT_REGID	NUMBER	Query cache registration ID sent by the client
CURSTATUS_TIME	NUMBER	Time in microseconds spent in the current state. See CONNECTION_STATUS above.
IDLE_TIME	NUMBER	Total time in IDLE state for the connection (in microseconds)
ACTIVE_TIME	NUMBER	Total time in ACTIVE state for the connection (in microseconds)
WAIT_TIME	NUMBER	Total time in WAITING state for the connection (in microseconds)
THINK_TIME	NUMBER	Total think time for the connection assigned to the pooled server, but not doing any database activity (in microseconds)
LAST_IDLE_TIME	NUMBER	Time in last IDLE state for this connection (in microseconds)
LAST_ACTIVE_TIME	NUMBER	Time in last ACTIVE state for this connection (in microseconds)
LAST_WAIT_TIME	NUMBER	Time in last WAITING state for this connection (in microseconds)
LAST_THINK_TIME	NUMBER	Time for the connection assigned to the pooled server, but not doing any database activity during the last ACTIVE state (in microseconds)
NUMGETS	NUMBER	Total number of requests at the connection level
NUMHITS	NUMBER	Total number of hits at the connection level
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.152 V$CPOOL_STATS

V$CPOOL_STATS displays information about the Database Resident Connection Pool statistics for an instance.

Column	Datatype	Description
POOL_NAME	VARCHAR2(1024)	Name of the Database Resident Connection Pool
NUM_OPEN_SERVERS	NUMBER	Total number of busy and free servers in the pool (including the authentication servers)
NUM_BUSY_SERVERS	NUMBER	Total number of busy servers in the pool (not including the authentication servers)

Column	Datatype	Description
NUM_AUTH_SERVERS	NUMBER	Number of authentication servers in the pool
NUM_REQUESTS	NUMBER	Number of client requests
NUM_HITS	NUMBER	Total number of times client requests found matching pooled servers in the pool
NUM_MISSES	NUMBER	Total number of times client requests could not find a matching pooled server in the pool
NUM_WAITS	NUMBER	Total number of client requests that had to wait due to non-availability of free pooled servers
WAIT_TIME	NUMBER	Reserved for future use
CLIENT_REQ_TIMEOUTS	NUMBER	Reserved for future use
NUM_AUTHENTICATIONS	NUMBER	Total number of authentications of clients done by the pool
NUM_PURGED	NUMBER	Total number of sessions purged by the pool
HISTORIC_MAX	NUMBER	Maximum size that the pool has ever reached
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view returns data only when queried from a CDB root. When queried from a PDB, this view returns 0 rows.

8.153 V$CR_BLOCK_SERVER

V$CR_BLOCK_SERVER displays statistics on the Global Cache Service processes (LMS) used in cache fusion.

Column	Datatype	Description
CR_REQUESTS	NUMBER	Number of CR blocks served due to remote CR block requests
CURRENT_REQUESTS	NUMBER	Number of current blocks served due to remote CR block requests CR_REQUESTS + CURRENT_REQUESTS = global cache CR clocks served (from V$SYSSTAT).
DATA_REQUESTS	NUMBER	Number of current or CR requests for data blocks
UNDO_REQUESTS	NUMBER	Number of CR requests for undo blocks
TX_REQUESTS	NUMBER	Number of CR requests for undo segment header blocks

Column	Datatype	Description
OTHER_REQUESTS	NUMBER	Number of CR requests for other types of blocks DATA_REQUESTS + UNDO_REQUESTS + TX_REQUESTS + OTHER_REQUESTS = total number of requests handled by the LMS processes
CURRENT_RESULTS	NUMBER	Number of requests for which no changes were rolled out of the block returned to the requesting instance
PRIVATE_RESULTS	NUMBER	Number of requests for which changes were rolled out of the block returned to the requesting instance, and only the requesting transaction can use the resulting CR block
ZERO_RESULTS	NUMBER	Number of requests for which changes were rolled out of the block returned to the requesting instance. Only zero-XID transactions can use the block.
DISK_READ_RESULTS	NUMBER	Number of requests for which the requesting instance had to read the requested block from disk
FAIL_RESULTS	NUMBER	Number of requests that failed; the requesting transaction must reissue the request
STALE	NUMBER	Number of requests for which the disk read of the requested block was stale
FAIRNESS_DOWN_CONVERTS	NUMBER	Number of times an instance receiving a request has down-converted an X lock on a block because it was not modifying the block
FAIRNESS_CLEARS	NUMBER	Number of times the "fairness counter" was cleared. This counter tracks the number of times a block was modified after it was served.
FREE_GC_ELEMENTS	NUMBER	Number of times a request was received from another instance and the X lock had no buffers
FLUSHES	NUMBER	Number of times the log has been flushed by an LMS process
FLUSHES_QUEUED	NUMBER	Number of flushes queued by an LMS process
FLUSH_QUEUE_FULL	NUMBER	Number of times the flush queue was full
FLUSH_MAX_TIME	NUMBER	Maximum time for flush
LIGHT_WORKS	NUMBER	Number of times the light-work rule was evoked. This rule prevents the LMS processes from going to disk while responding to CR requests for data, undo, or undo segment header blocks. This rule can prevent the LMS process from completing its response to the CR request.
ERRORS	NUMBER	Number of times an error was signalled by an LMS process
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view contains internal diagnostic information for use by Oracle Support Services. It is subject to change without notice.

8.154 V$CURRENT_BLOCK_SERVER

`V$CURRENT_BLOCK_SERVER` displays statistics on the Global Cache Service processes (LMS) used in cache fusion.

Column	Datatype	Description
`PIN0`	`NUMBER`	Pins taking less than 100 microseconds
`PIN1`	`NUMBER`	Pins taking 100 microseconds to 1 millisecond
`PIN10`	`NUMBER`	Pins taking 1 to 10 milliseconds
`PIN100`	`NUMBER`	Pins taking 10 to 100 milliseconds
`PIN1000`	`NUMBER`	Pins taking 100 to 1000 milliseconds
`PIN10000`	`NUMBER`	Pins taking 1000 to 10000 milliseconds
`PINOVER`	`NUMBER`	Pins taking more than 10000 milliseconds
`FLUSH0`	`NUMBER`	Flushes taking less than 100 microseconds
`FLUSH1`	`NUMBER`	Flushes taking 100 microseconds to 1 millisecond
`FLUSH10`	`NUMBER`	Flushes taking 1 to 10 milliseconds
`FLUSH100`	`NUMBER`	Flushes taking 10 to 100 milliseconds
`FLUSH1000`	`NUMBER`	Flushes taking 100 to 1000 milliseconds
`FLUSH10000`	`NUMBER`	Flushes taking 1000 to 10000 milliseconds
`FLUSHOVER`	`NUMBER`	Flushes taking more than 10000 milliseconds
`CLEANDC`	`NUMBER`	Reserved for internal use
`RCVDC`	`NUMBER`	Number of lock down-converts to S (shared) caused by instance recovery
`QUEUEDC`	`NUMBER`	Number of queued lock down-converts to NULL
`EVICTDC`	`NUMBER`	Number of lock down-converts to NULL caused by an SGA shrink
`WRITEDC`	`NUMBER`	Number of dirty blocks in read-mostly objects which were written and the X (exclusive) lock down-converted to S (shared) locks
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.155 V$DATABASE

V$DATABASE displays information about the database from the control file.

Column	Datatype	Description
DBID	NUMBER	Database identifier calculated when the database is created and stored in all file headers
NAME	VARCHAR2(9)	Name of the database
CREATED	DATE	Creation date of the database. If the control file was re-created using the CREATE CONTROLFILE statement, then this column displays the date that the control file was re-created.
RESETLOGS_CHANGE#	NUMBER	System change number (SCN) at open resetlogs
RESETLOGS_TIME	DATE	Timestamp of open resetlogs
PRIOR_RESETLOGS_CHANGE#	NUMBER	SCN at prior resetlogs
PRIOR_RESETLOGS_TIME	DATE	Timestamp of prior resetlogs
LOG_MODE	VARCHAR2(12)	Archive log mode: • NOARCHIVELOG • ARCHIVELOG • MANUAL
CHECKPOINT_CHANGE#	NUMBER	Last SCN checkpointed
ARCHIVE_CHANGE#	NUMBER	Database force archiving SCN. Any redo log with a start SCN below this will be forced to archive out.
CONTROLFILE_TYPE	VARCHAR2(7)	Type of control file: • STANDBY - Indicates that the database is in standby mode • CLONE - Indicates a clone database • BACKUP | CREATED - Indicates the database is being recovered using a backup or created control file • CURRENT - database is available for general use
CONTROLFILE_CREATED	DATE	Creation date of the control file
CONTROLFILE_SEQUENCE#	NUMBER	Control file sequence number incremented by control file transactions
CONTROLFILE_CHANGE#	NUMBER	Last SCN in backup control file; null if the control file is not a backup
CONTROLFILE_TIME	DATE	Last timestamp in backup control file; null if the control file is not a backup
OPEN_RESETLOGS	VARCHAR2(11)	(NOT ALLOWED | ALLOWED | REQUIRED) Indicates whether the next database open allows or requires the resetlogs option
VERSION_TIME	DATE	Version time
OPEN_MODE	VARCHAR2(20)	Open mode information: • MOUNTED • READ WRITE • READ ONLY • READ ONLY WITH APPLY - A physical standby database is open in real-time query mode

Column	Datatype	Description
PROTECTION_MODE	VARCHAR2(20)	Protection mode currently in effect for the database: • MAXIMUM PROTECTION - Database is running in maximized protection mode • MAXIMUM AVAILABILITY - Database is running in maximized availability mode • RESYNCHRONIZATION - Database is running in resynchronization mode • MAXIMUM PERFORMANCE - Database is running in maximized performance mode • UNPROTECTED - Database is unprotected (this normally occurs when the primary database is mounted and not open)
PROTECTION_LEVEL	VARCHAR2(20)	Aggregated protection mode currently in effect for the database: • MAXIMUM PROTECTION - Database is running in maximized protection mode • MAXIMUM AVAILABILITY - Database is running in maximized availability mode • RESYNCHRONIZATION - Database is running in resynchronization mode • MAXIMUM PERFORMANCE - Database is running in maximized performance mode • UNPROTECTED - Database is unprotected (this normally occurs when the primary database is mounted and not open) **Note:** This column is an aggregation of the PROTECTION_MODE of all standby archive log destinations.
REMOTE_ARCHIVE	VARCHAR2(8)	Value of the REMOTE_ARCHIVE_ENABLE initialization parameter
ACTIVATION#	NUMBER	Number assigned to the database instantiation
SWITCHOVER#	NUMBER	Number assigned to the database switchover
DATABASE_ROLE	VARCHAR2(16)	Current role of the database: • SNAPSHOT STANDBY • LOGICAL STANDBY • PHYSICAL STANDBY • PRIMARY • FAR SYNC
ARCHIVELOG_CHANGE#	NUMBER	Highest NEXT_CHANGE# (from the V$ARCHIVED_LOG view) for an archive log
ARCHIVELOG_COMPRESSION	VARCHAR2(8)	Status of the archive log compression (ENABLED) or (DISABLED)

Column	Datatype	Description
SWITCHOVER_STATUS	VARCHAR2(20)	Indicates whether switchover is allowed: • NOT ALLOWED - On a primary database, this status indicates that there are no valid and enabled standby databases. On a standby database, this status indicates that a switchover request has not been received from the primary database. • SESSIONS ACTIVE - The database has active sessions. On a physical standby database, the WITH SESSION SHUTDOWN SQL clause must be specified to perform a role transition while in this state. On a logical standby database, a role transition can be performed while in this state, but the role transition will not complete until all current transactions have committed. • SWITCHOVER PENDING - On a physical standby database, this status indicates that a switchover request has been received from the primary database and is being processed. A physical standby database cannot switch to the primary role while in this transient state. • SWITCHOVER LATENT - On a physical standby database, this status indicates that a switchover request was pending, but the original primary database has been switched back to the primary role. • TO PRIMARY - The database is ready to switch to the primary role. • TO STANDBY - The database is ready to switch to either the physical or logical standby role. • TO LOGICAL STANDBY - The database has received a data dictionary from a logical standby database and is ready to switch to the logical standby role. • RECOVERY NEEDED - On a physical standby database, this status indicates that additional redo must be applied before the database can switch to the primary role. • PREPARING SWITCHOVER - On a primary database, this status indicates that a data dictionary is being received from a logical standby database in preparation for switching to the logical standby role. On a logical standby database, this status indicates that the data dictionary has been sent to the primary database and other standby databases. • PREPARING DICTIONARY - On a logical standby database, this status indicates that the data dictionary is being sent to the primary database and other standby databases in preparation for switching to the primary role. • FAILED DESTINATION - On a primary database, this status indicates that one or more standby destinations are in an error state. • RESOLVABLE GAP - On a primary database, this status indicates that one or more standby databases have a redo gap that can be automatically resolved by fetching the missing redo from the primary database or from another standby database. • UNRESOLVABLE GAP - On a primary database, this status indicates that one or more standby databases have a redo gap that cannot be automatically resolved by fetching the missing redo from the primary database or from another standby database.

Column	Datatype	Description
		• LOG SWITCH GAP - On a primary database, this status indicates that one or more standby databases are missing redo due to a recent log switch.
DATAGUARD_BROKER	VARCHAR2(8)	Data Guard broker information: • ENABLED - Database is part of a broker configuration and broker management of the database is enabled • DISABLED - Database is part of a broker configuration and broker management of the database is disabled. This value is displayed if the user disabled broker management of the database or configuration, or if broker management was disabled due to a role change (for example, the old primary was disabled after a failover operation).
GUARD_STATUS	VARCHAR2(7)	Protects data from being changed: • ALL - Indicates all users other than SYS are prevented from making changes to any data in the database. • STANDBY - Indicates all users other than SYS are prevented from making changes to any database object being maintained by logical standby. • NONE - Indicates normal security for all data in the database.
SUPPLEMENTAL_LOG_DATA_MIN	VARCHAR2(8)	Ensures that LogMiner (and any products building on LogMiner technology) will have sufficient information to support chained rows and various storage arrangements such as cluster tables: • NO - None of the database-wide supplemental logging directives are enabled. In a CDB, a value of NO means that minimal supplemental logging is not enabled in all of the PDBs in the CDB. • IMPLICIT - Minimal supplemental logging is enabled because all or a combination of primary key, unique key, and foreign key supplemental logging is enabled • YES - Minimal supplemental logging is enabled through an ALTER DATABASE ADD SUPPLEMENTAL LOG DATA statement. In a CDB, a value of YES means that minimal supplemental logging is enabled in all of the PDBs in the CDB. **See Also:** *Oracle Database SQL Language Reference* for additional information about the ALTER DATABASE ADD SUPPLEMENTAL LOG DATA statement
SUPPLEMENTAL_LOG_DATA_PK	VARCHAR2(3)	For all tables with a primary key, indicates whether all columns of the primary key are placed into the redo log whenever an update is performed (YES) or not (NO). When a value of YES appears in a CDB, it means that primary key supplemental logging is enabled in all of the PDBs in the CDB. When a value of NO appears in a CDB, query the PRIMARY_KEY column in the DBA_SUPPLEMENTAL_LOGGING view for each PDB in the CDB to see whether primary key supplemental logging is enabled in the PDB. **See Also:** *Oracle Database SQL Language Reference* for more information about the ALTER DATABASE ADD SUPPLEMENTAL LOG *supplemental_id_key_clause* statement

Column	Datatype	Description
SUPPLEMENTAL_LOG_DATA_UI	VARCHAR2(3)	For all tables with a unique key, indicates whether all other columns belonging to the unique key are placed into the redo log if any of the unique key columns are modified (YES) or not (NO). When a value of YES appears in a CDB, it means that this value is enabled in all of the PDBs in the CDB. When a value of NO appears in a CDB, query the UNIQUE_INDEX column in the DBA_SUPPLEMENTAL_LOGGING view for each PDB in the CDB to see whether unique column supplemental logging is enabled in the PDB. **See Also:** *Oracle Database SQL Language Reference* for more information about the ALTER DATABASE ADD SUPPLEMENTAL LOG *supplemental_id_key_clause* statement
FORCE_LOGGING	VARCHAR2(39)	Indicates the type of logging mode that is currently in force. The valid values and their meanings are: • NO - This value means that no logging mode has been enabled for the database • YES - This value means that FORCE LOGGING mode has been enabled for the database • STANDBY NOLOGGING FOR LOAD PERFORMANCE - This value is used when this is the current mode for the database • STANDBY NOLOGGING FOR DATA AVAILABILITY - This value is used when this is the current mode for the database
PLATFORM_ID	NUMBER	Platform identification number of the database
PLATFORM_NAME	VARCHAR2(101)	Platform name of the database
RECOVERY_TARGET_INCARNATION#	NUMBER	The incarnation number to which all datafiles would be recovered by the RECOVER DATABASE command
LAST_OPEN_INCARNATION#	NUMBER	Record number of the incarnation in V$DATABASE_INCARNATION that was last opened successfully
CURRENT_SCN	NUMBER	Current SCN; null if the database is not currently open. For a standby database, it is the checkpoint SCN of the mounted physical standby database during media recovery and is always less than the last applied SCN tracked in V$RECOVERY_PROGRESS.
FLASHBACK_ON	VARCHAR2(18)	Possible values are as follows: • YES - Flashback is on • NO - Flashback is off • RESTORE POINT ONLY - Flashback is on but one can only flashback to guaranteed restore points
SUPPLEMENTAL_LOG_DATA_FK	VARCHAR2(3)	For all tables with a foreign key, indicates whether all other columns belonging to the foreign key are placed into the redo log if any foreign key columns are modified (YES) or not (NO). When a value of YES appears in a CDB, it means that foreign key supplemental logging is enabled in all of the PDBs in the CDB. When a value of NO appears in a CDB, query the FOREIGN_KEY column in the DBA_SUPPLEMENTAL_LOGGING view for each PDB in the CDB to see whether foreign key supplemental logging is enabled in the PDB. **See Also:** *Oracle Database SQL Language Reference* for more information about the ALTER DATABASE ADD SUPPLEMENTAL LOG *supplemental_id_key_clause* statement

Column	Datatype	Description
SUPPLEMENTAL_LOG_DATA_ALL	VARCHAR2(3)	For all columns, indicates whether all the fixed-length maximum size columns of that row are placed into the redo log (YES) or not (NO). When a value of YES appears in a CDB, it means that all column supplemental logging is enabled in all of the PDBs in the CDB. When a value of NO appears in a CDB, query the ALL_COLUMN column in the DBA_SUPPLEMENTAL_LOGGING view for each PDB in the CDB to see whether all column supplemental logging is enabled in the PDB. **See Also:** *Oracle Database SQL Language Reference* for more information about the ALTER DATABASE ADD SUPPLEMENTAL LOG *supplemental_id_key_clause* statement
DB_UNIQUE_NAME	VARCHAR2(30)	Unique database name
STANDBY_BECAME_PRIMARY_SCN	NUMBER	SCN at which a physical standby database became a primary database. This SCN is useful for converting a failed primary database into a physical standby database after a forced failover. **See Also:** *Oracle Data Guard Concepts and Administration* for more information about Oracle Data Guard.
FS_FAILOVER_MODE[1]	VARCHAR2(19)	Displays the current fast-start failover mode. Possible values are: • DISABLED - Fast-start failover is disabled. • OBSERVE-ONLY - Fast-start failover is enabled in test drive mode. • ZERO DATA LOSS - Fast-start failover is enabled and a fast-start failover cannot incur any data loss. • POTENTIAL DATA LOSS - Fast-start failover is enabled and a fast-start failover can incur data loss within FastStartFailoverLagLimit seconds. **See Also:** *Oracle Data Guard Broker* for more information about the FastStartFailoverLagLimit configuration property
FS_FAILOVER_STATUS[1]	VARCHAR2(22)	Fast-start failover status: • DISABLED • BYSTANDER • SYNCHRONIZED • UNSYNCHRONIZED • SUSPENDED • STALLED • LOADING DICTIONARY • PRIMARY UNOBSERVED • REINSTATE REQUIRED • REINSTATE FAILED • TARGET OVER LAG LIMIT • TARGET UNDER LAG LIMIT **See Also:** *Oracle Data Guard Broker* for detailed descriptions of these values **Note:** If the value of this column is DISABLED, then the values for the FS_FAILOVER_CURRENT_TARGET, FS_FAILOVER_THRESHOLD, FS_FAILOVER_OBSERVER_PRESENT, and FS_FAILOVER_OBSERVER_HOST columns in this table are not meaningful.

Column	Datatype	Description
FS_FAILOVER_CURRENT_TARGET[1]	VARCHAR2(30)	DB_UNIQUE_NAME of the standby that is the current fail-safe failover observer target standby for the Data Guard configuration
FS_FAILOVER_THRESHOLD[1]	NUMBER	Time (in seconds) that the observer will attempt to reconnect with a disconnected primary before attempting fail-safe failover observer with the target standby
FS_FAILOVER_OBSERVER_PRESENT[1]	VARCHAR2(7)	Indicates whether the master observer is currently connected to the local database (YES) or not (NO) **Note:** This column is consistent throughout an Oracle RAC environment; that is, if the observer is connected to any instance, then all instances will show a value of YES.
FS_FAILOVER_OBSERVER_HOST[1]	VARCHAR2(512)	Machine name that is currently hosting the master observer process, if fast-start failover is enabled. If fast-start failover is not enabled, this column returns a NULL string.
CONTROLFILE_CONVERTED	VARCHAR2(3)	Indicates whether the control file was implicitly converted from its original type during restore (YES) or not (NO) This column will be set to YES when RMAN restores a standby control file from a backup of the control file taken at the primary database or restores a backup control file from a backup taken at the physical standby database. This column will change to NO when the file names are fixed using information in the recovery catalog schema.
PRIMARY_DB_UNIQUE_NAME	VARCHAR2(30)	For any Standby database (Physical, Logical, or Snapshot), this column will contain the DB_UNIQUE_NAME of the Primary database that this Standby last received current redo from. If this standby has not received any current redo since last being started, then this column will be null. For a Primary database that had previously been a Standby, this column will contain the DB_UNIQUE_NAME of the last Primary that this database received current redo from while acting as a Standby. For a Primary database that has never been a Standby, this column will be null.
SUPPLEMENTAL_LOG_DATA_PL	VARCHAR2(3)	Indicates whether additional information is logged in the redo log (YES) or not (NO) during invocation of procedures in Oracle-supplied packages for which procedural replication is supported. When a value of YES appears in a CDB, it means that supplemental logging for procedural replication is enabled in all of the PDBs in the CDB. When a value of NO appears in a CDB, query the PROCEDURAL column in the DBA_SUPPLEMENTAL_LOGGING view for each PDB in the CDB to see whether supplemental logging for procedural replication is supported in the PDB. **See Also:** *Oracle Data Guard Concepts and Administration* for a list of Oracle-supplied packages that are procedurally replicated to a logical standby database
MIN_REQUIRED_CAPTURE_CHANGE#	NUMBER	Minimum REQUIRED_CHECKPOINT_SCN for all local capture processes on the database
CDB	VARCHAR2(3)	Possible values are: • YES if the database is a CDB • NO if the database is not a CDB

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
PENDING_ROLE_CHANGE_TASKS	VARCHAR2(512)	Tasks remaining after an Oracle Data Guard role change. Possible values: • NONE: No pending tasks remain • NOT APPLICABLE: The database is either standby or is not a DG_CONFIG member • BUILD_PENDING: The database was formerly a logical standby and has not yet taken a snapshot of its data dictionary into the redo stream • SRL_ARCHIVE_PENDING: The database was formerly a logical standby and the standby redo logs associated with the earlier failover operation have not yet been archived • ERROR: The database was formerly a logical standby and the snapshot of the dictionary failed • UNKNOWN: The database is not open or the query failed
CON_DBID	NUMBER	The database ID of the PDB
FORCE_FULL_DB_CACHING	VARCHAR2(3)	Indicates the status of the force full database caching feature in the database. Possible values: • YES - The database is in force full database caching mode. • NO - The database is not in force full database caching mode. **See Also**: *Oracle Database SQL Language Reference* for information about the FORCE FULL DATABASE CACHING clause for the ALTER DATABASE statement
SUPPLEMENTAL_LOG_DATA_SR	VARCHAR2(3)	Indicates whether the database is enabled for subset database replication (YES) or not (NO). If the database is enabled for subset database replication, then redo overhead and feature restriction for tables without column data supplemental logging will be reduced.
GOLDENGATE_BLOCKING_MODE	VARCHAR2(8)	Reserved for future use

[1] Oracle Database 23ai introduces the V$FAST_START_FAILOVER_CONFIG view, which contains configuration details about Oracle Data Guard fast-start failover. As a result, the FS_FAILOVER_* columns in the V$DATABASE view are deprecated. Instead, use the corresponding columns in the V$FAST_START_FAILOVER_CONFIG view. See "V$FAST_START_FAILOVER_CONFIG" for more information.

> **See Also:**
>
> "DBA_SUPPLEMENTAL_LOGGING" for more information about supplemental logging in a PDB

8.156 V$DATABASE_BLOCK_CORRUPTION

V$DATABASE_BLOCK_CORRUPTION displays information about database blocks that were corrupted after the last backup.

Column	Datatype	Description
FILE#	NUMBER	Absolute file number of the data file that contains the corrupt blocks
BLOCK#	NUMBER	Block number of the first corrupt block in the range of corrupted blocks
BLOCKS	NUMBER	Number of corrupted blocks found starting with BLOCK#
CORRUPTION_CHANGE#	NUMBER	Change number at which the logical corruption was detected. Set to 0 to indicate media corruption.
CORRUPTION_TYPE	VARCHAR2(9)	Type of block corruption in the data file: • ALL ZERO - Block header on disk contained only zeros. The block may be valid if it was never filled and if it is in an Oracle7 file. The buffer will be reformatted to the Oracle8 standard for an empty block. • FRACTURED - Block header looks reasonable, but the front and back of the block are different versions. • CHECKSUM - optional check value shows that the block is not self-consistent. It is impossible to determine exactly why the check value fails, but it probably fails because sectors in the middle of the block are from different versions. • CORRUPT - Block is wrongly identified or is not a data block (for example, the data block address is missing) • LOGICAL - Block is logically corrupt
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$NONLOGGED_BLOCK" for information about nonlogged blocks

8.157 V$DATABASE_INCARNATION

V$DATABASE_INCARNATION displays information about all database incarnations.

Oracle creates a new incarnation whenever a database is opened with the RESETLOGS option. Records about the current and immediately previous incarnation are also contained in the V$DATABASE view.

Column	Datatype	Description
INCARNATION#	NUMBER	Record ID for the branch record in the control file
RESETLOGS_CHANGE#	NUMBER	Resetlogs system change number (SCN) for the incarnation of the current row
RESETLOGS_TIME	DATE	Resetlogs timestamp for the incarnation of the current row
PRIOR_RESETLOGS_CHANGE#	NUMBER	Resetlogs SCN for the previous incarnation
PRIOR_RESETLOGS_TIME	DATE	Resetlogs timestamp for the previous incarnation
STATUS	VARCHAR2(7)	Incarnation status: • ORPHAN - Orphan incarnation • CURRENT - Current incarnation of the database • PARENT - Parent of the current incarnation
RESETLOGS_ID	NUMBER	Branch ID for the incarnation of the current row (used by user-managed recovery/RMAN restore to get unique names for archived logs across incarnations)
PRIOR_INCARNATION#	NUMBER	Parent incarnation record ID if nonzero
FLASHBACK_DATABASE_ALLOWED	VARCHAR2(26)	Indicate whether or not Flashback Database can be performed into SCNs or timestamps in the incarnation. A value of YES means that you can flashback to some point in that incarnation. A value of NO indicates that you cannot flashback into the incarnation.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$DATABASE"

8.158 V$DATABASE_KEY_INFO

V$DATABASE_KEY_INFO provides the information of the default database key used to encrypt data blocks. Oracle uses the database key to encrypt sensitive information in SYSTEM, UNDO, and TEMP tablespaces when such data has dependency from encrypted tablespaces or encrypted columns

V$DATABASE_KEY_INFO reflects the database key information stored in the control file. Generally it is the same as the system tablespace key recorded in the system tablespace. If the system tablespace is encrypted, it will also appear in V$ENCRYPTED_TABLESPACES. If the system tablespace is not encrypted, this is the only view providing this information.

Column	Datatype	Description
ENCRYPTIONALG	VARCHAR2(7)	Encryption algorithm: • NONE • 3DES168 • AES128 • AES192 • AES256 AES256 is the default encryption algorithm.
ENCRYPTEDKEY	RAW(48)	Encrypted version of the database key
MASTERKEYID	RAW(16)	ID of the master key that was used to encrypt the database key
MASTER_ACTIVATED	VARCHAR2(3)	Indicates whether the master key has been set (YES) or not (NO) for this database or container in the Oracle Key Store. In other words, indicates whether Transparent Data Encryption (TDE) has been activated for this database or container
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$ENCRYPTED_TABLESPACES"

8.159 V$DATAFILE

V$DATAFILE displays datafile information from the control file.

See Also:

"V$DATAFILE_HEADER", which displays information from data file headers

Column	Datatype	Description
FILE#	NUMBER	Absolute file number
CREATION_CHANGE#	NUMBER	Change number at which the data file was created
CREATION_TIME	DATE	Timestamp of the data file creation
TS#	NUMBER	Tablespace number
RFILE#	NUMBER	Tablespace relative data file number

Column	Datatype	Description
STATUS	VARCHAR2(7)	Type of file (system or user) and its status. Values: OFFLINE, ONLINE, SYSTEM, RECOVER, SYSOFF (an offline file from the SYSTEM tablespace)
ENABLED	VARCHAR2(10)	Describes how accessible the file is from SQL: • DISABLED - No SQL access allowed • READ ONLY - No SQL updates allowed • READ WRITE - Full access allowed • UNKNOWN - Unknown whether SQL updates would be allowed or not
CHECKPOINT_CHANGE#	NUMBER	SCN at last checkpoint
CHECKPOINT_TIME	DATE	Timestamp of the checkpoint#
UNRECOVERABLE_CHANGE#	NUMBER	Last unrecoverable change number made to this data file. If the database is in ARCHIVELOG mode, then this column is updated when an unrecoverable operation completes. If the database is not in ARCHIVELOG mode, this column does not get updated.
UNRECOVERABLE_TIME	DATE	Timestamp of the last unrecoverable change. This column is updated only if the database is in ARCHIVELOG mode.
LAST_CHANGE#	NUMBER	Last change number made to this data file (null if the data file is being changed)
LAST_TIME	DATE	Timestamp of the last change
OFFLINE_CHANGE#	NUMBER	Offline change number of the last offline range. This column is updated only when the data file is brought online.
ONLINE_CHANGE#	NUMBER	Online change number of the last offline range
ONLINE_TIME	DATE	Online timestamp of the last offline range
BYTES	NUMBER	Current data file size (in bytes); 0 if inaccessible
BLOCKS	NUMBER	Current data file size (in blocks); 0 if inaccessible
CREATE_BYTES	NUMBER	Size when created (in bytes)
BLOCK_SIZE	NUMBER	Block size of the data file
NAME	VARCHAR2(513)	Name of the data file
PLUGGED_IN	NUMBER	Describes whether the tablespace is plugged in. The value is 1 if the tablespace is plugged in and has not been made read/write, 0 if not.
BLOCK1_OFFSET	NUMBER	Offset from the beginning of the file to where the Oracle generic information begins. The exact length of the file can be computed as follows: BYTES + BLOCK1_OFFSET.
AUX_NAME	VARCHAR2(513)	Auxiliary name that has been set for this file via CONFIGURE AUXNAME
FIRST_NONLOGGED_SCN	NUMBER	First nonlogged SCN (check in standby database)
FIRST_NONLOGGED_TIME	DATE	First nonlogged time (check in standby database)
FOREIGN_DBID	NUMBER	Foreign DBID from which this data file came from. The value is 0 if this file is not a foreign database file.
FOREIGN_CREATION_CHANGE#	NUMBER	Creation SCN of a foreign data file. The value is 0 if this file is not a foreign database file.
FOREIGN_CREATION_TIME	DATE	Creation time of a foreign data file. The value is 0 if this file is not a foreign database file.

Column	Datatype	Description
PLUGGED_READONLY	VARCHAR2(3)	YES if this is a transported read-only foreign file; otherwise NO.
PLUGIN_CHANGE#	NUMBER	SCN at which the foreign data file was transported into the database. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_CHANGE#	NUMBER	The SCN of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_TIME	DATE	The time of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.160 V$DATAFILE_COPY

V$DATAFILE_COPY displays data file copy information from the control file.

Column	Datatype	Description
RECID	NUMBER	Data file copy record ID
STAMP	NUMBER	Data file copy record stamp
NAME	VARCHAR2(513)	File name of the data file copy. The maximum length of the name is operating system dependent.
TAG	VARCHAR2(32)	Data file copy tag
FILE#	NUMBER	Absolute data file number
RFILE#	NUMBER	Tablespace relative data file number
CREATION_CHANGE#	NUMBER	Data file creation change#
CREATION_TIME	DATE	Data file creation timestamp
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the data file when the copy was made
RESETLOGS_TIME	DATE	Resetlogs timestamp of the data file when the copy was made
INCREMENTAL_LEVEL	NUMBER	Normal full backups have a NULL value, level 0 incremental backups have a value of 0, and level 1 incremental backups have a value of 1
CHECKPOINT_CHANGE#	NUMBER	Checkpoint change number of the data file when the copy was made
CHECKPOINT_TIME	DATE	Checkpoint timestamp of the data file when the copy was made
ABSOLUTE_FUZZY_CHANGE#	NUMBER	Highest change seen when the data file was copied
RECOVERY_FUZZY_CHANGE#	NUMBER	Highest change written to the file by media recovery

Column	Datatype	Description
RECOVERY_FUZZY_TIME	DATE	Timestamp of the highest change written to the file by media recovery
ONLINE_FUZZY	VARCHAR2(3)	(YES|NO) If set to YES, this is a copy taken using an operating system utility after a crash or offline immediate (or an invalid copy taken while data file was online and the database open). Recovery will need to apply all redo up to the next crash recovery marker to make the file consistent.
BACKUP_FUZZY	VARCHAR2(3)	(YES|NO) If set to YES, this is a copy taken using the BEGIN BACKUP/END BACKUP technique. Recovery will need to apply all redo up to the end backup marker to make this copy consistent.
MARKED_CORRUPT	NUMBER	Number of blocks marked corrupt by this copy operation. That is, blocks that were not marked corrupted in the source data file, but were detected and marked as corrupted during the copy operation.
MEDIA_CORRUPT	NUMBER	Total number of media corrupt blocks. For example, blocks with checksum errors are marked media corrupt.
LOGICALLY_CORRUPT	NUMBER	Total number of logically corrupt blocks. For example, applying redo for unrecoverable operations will mark affected blocks logically corrupt.
BLOCKS	NUMBER	Size of the data file copy in blocks (also the size of the data file when the copy was made)
BLOCK_SIZE	NUMBER	Block size of the data file
OLDEST_OFFLINE_RANGE	NUMBER	RECID of the oldest offline range record in this control file copy; 0 for data file copies
DELETED	VARCHAR2(3)	(YES|NO) If set to YES the data file copy has been deleted or overwritten
STATUS	VARCHAR2(1)	Identifies the status of this data file copy. Possible values are: A - Available D - Deleted U - Unavailable X - Expired
COMPLETION_TIME	DATE	Time when the copy was completed
CONTROLFILE_TYPE	VARCHAR2(1)	B indicates normal copies S indicates standby copies
KEEP	VARCHAR2(3)	(YES/NO) Indicates whether or not this backup set has a retention policy that is different than the value for the configure retention policy
KEEP_UNTIL	DATE	If KEEP_UNTIL is specified, this is the date after which the backup becomes obsolete. If this column is null, then the backup never expires.
KEEP_OPTIONS	VARCHAR2(11)	Lists additional retention options for this backup set. Possible values are: LOGS - The logs need to recover this backup are kept NOLOGS - The logs needed to recover this backup will not be kept
SCANNED	VARCHAR2(3)	Indicates whether RMAN scanned the file (YES) or not (NO)
IS_RECOVERY_DEST_FILE	VARCHAR2(3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)

Column	Datatype	Description
RMAN_STATUS_RECID	NUMBER	Owning V$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V$RMAN_STATUS record stamp
CONVERTED_FILE	VARCHAR2(3)	(YES/NO) Indicates whether or not the data file copy was created using the RMAN CONVERT command
SAME_ENDIAN	VARCHAR2(3)	If the value of the CONVERTED_FILE column is YES, then this column indicates whether the data file copy has the same endianness as the source data file (YES) or not (NO); otherwise NULL
FOREIGN_DBID	NUMBER	Foreign DBID from which this data file came from. The value is 0 if this file is not a foreign database file.
PLUGGED_READONLY	VARCHAR2(3)	YES if this is a transported read-only foreign file; otherwise NO.
PLUGIN_CHANGE#	NUMBER	SCN at which the foreign data file was transported into the database. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_CHANGE#	NUMBER	The SCN of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_TIME	DATE	The time of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
BACKED_BY_VSS	VARCHAR2(3)	Whether or not the file has been backed up by Volume Shadow Copy Service (VSS). This column is reserved for internal use.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
BACKED_BY_PDB	VARCHAR2(3)	Recovery Manager (RMAN) allows a PDB to be backed up in two ways. The value in this column indicates how the PDB backup was taken: • YES: The backup was taken when connected to the PDB • NO: The backup was taken when connected to the root container
SPARSE_BACKUP	VARCHAR2(3)	Indicates whether the file is sparse (YES) or not (NO)
GUID	RAW(16)	The GUID of the PDB to which the backup belongs. This is useful after the PDB is dropped to identify which PDB the backup belongs to.

8.161 V$DATAFILE_HEADER

V$DATAFILE_HEADER displays data file information from the data file headers.

Column	Datatype	Description
FILE#	NUMBER	Data file number (from control file)
STATUS	VARCHAR2(7)	ONLINE | OFFLINE (from control file)

Column	Datatype	Description
ERROR	VARCHAR2(18)	NULL if the data file header read and validation were successful. If the read failed then the rest of the columns are NULL. If the validation failed then the rest of columns may display invalid data. If there is an error then usually the data file must be restored from a backup before it can be recovered or used.
FORMAT	NUMBER	Indicates the format for the header block. The possible values are 6, 7, 8, 10 or 0. 6 - indicates Oracle Version 6 7 - indicates Oracle Version 7 8 - indicates Oracle Version 8 10 - indicates Oracle Version 10 0 - indicates the format could not be determined (for example, the header could not be read)
RECOVER	VARCHAR2(3)	File needs media recovery (YES | NO)
FUZZY	VARCHAR2(3)	File is fuzzy (YES | NO)
CREATION_CHANGE#	NUMBER	Data file creation change#
CREATION_TIME	DATE	Data file creation timestamp
TABLESPACE_NAME	VARCHAR2(30)	Tablespace name
TS#	NUMBER	Tablespace number
RFILE#	NUMBER	Tablespace relative data file number
RESETLOGS_CHANGE#	NUMBER	Resetlogs change#
RESETLOGS_TIME	DATE	Resetlogs timestamp
CHECKPOINT_CHANGE#	NUMBER	Data file checkpoint change#
CHECKPOINT_TIME	DATE	Data file checkpoint timestamp
CHECKPOINT_COUNT	NUMBER	Data file checkpoint count
BYTES	NUMBER	Current data file size in bytes
BLOCKS	NUMBER	Current data file size in blocks
NAME	VARCHAR2(513)	Data file name
SPACE_HEADER	VARCHAR2(40)	Represents the block address of a space file header block of a locally managed data file
LAST_DEALLOC_CHANGE#	VARCHAR2(16)	Last deallocated SCN
UNDO_OPT_CURRENT_CHANGE#	VARCHAR2(40)	For internal use only
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
IS_SPARSE	VARCHAR2(3)	Indicates whether the file is sparse (YES) or not (NO)

Column	Datatype	Description
ENCRYPTED	VARCHAR2(3)	After file encryption is completed, this column indicates whether the file is encrypted (YES) or not (NO). When file encryption is still in progress, this column has a value of NO.

8.162 V$DATAGUARD_CONFIG

V$DATAGUARD_CONFIG displays the unique database names defined with the DB_UNIQUE_NAME and LOG_ARCHIVE_CONFIG initialization parameters, providing a view of the Oracle Data Guard environment from any database in the configuration.

The first row of the view lists the unique database name of the current database that was specified with the DB_UNIQUE_NAME initialization parameter. Additional rows reflect the unique database names of the other databases in the configuration that were specified with the DG_CONFIG keyword of the LOG_ARCHIVE_CONFIG initialization parameter.

Column	Datatype	Description
DB_UNIQUE_NAME	VARCHAR2(30)	Unique database name
PARENT_DBUN	VARCHAR2(30)	DB_UNIQUE_NAME of the parent database, also known as the database that supplies live redo to the destination. For example, suppose Boston is the DB_UNIQUE_NAME of the primary database, Chicago is the DB_UNIQUE_NAME of the Far Sync Instance, and Seattle is the DB_UNIQUE_NAME of the terminal standby database. Since Boston is the primary database, it has no parent database so the PARENT_DBUN for Boston will be NULL. Since Boston services Chicago, the PARENT_DBUN of Chicago will be Boston. Since Chicago services Seattle, Chicago will be the PARENT_DBUN for Seattle.
DEST_ROLE	VARCHAR2(17)	Type of archival destination database: • LOCAL - Local to primary database • PHYSICAL - Physical standby • FAR SYNC INSTANCE - Far Sync Instance • CROSS-INSTANCE - An instance of the primary • LOGICAL - Logical standby • SNAPSHOT - Snapshot standby database • DOWNSTREAM - Streams downstream capture database
CURRENT_SCN	NUMBER	The SCN up to which the specified database has applied redo
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "DB_UNIQUE_NAME"
- "LOG_ARCHIVE_CONFIG"

8.163 V$DATAGUARD_PROCESS

V$DATAGUARD_PROCESS displays one row for each Oracle Data Guard process that is currently running.

Column	Datatype	Description
NAME	VARCHAR2(5)	Name of the process whose information is being reported. Some of the possible values include: • ARC*n* - Archiver process • DTS - Data transport process • FAL - File/announce process • LGWR - Log Writer Process • MRP0 - Detached recovery server process • NSS*n* - SYNC Redo Transport process • ORA - Foreground process • RFS - Remote file server • RMI - Remote message process • TMON - Redo Transport Process monitor • TT*nn* - Redo Transport Worker Process
PID	VARCHAR2(24)	Operating system process identifier of the process
TYPE	VARCHAR2(3)	Indicates which Oracle subsystem created the process. Possible values: • KSB • KSV • NET • UNK

Column	Datatype	Description
ROLE	VARCHAR2(25)	Role of the process. Possible values: • test • async ORL multi • async ORL single • async SRL multi • async SRL single • log writer • sync • archive redo • archive local • archive gap • RFS async • RFS sync • RFS archive • RFS gap • RFS SMON • data transport • data receive • redo transport monitor • heartbeat redo informer • process kill • post role transition • gap manager • update TMI • RFS ping • FAL GAP • FAL announce • failover • switchover • remote failover • remote switchover • redo transport timer • announce request • managed recovery • recovery • controlfile update • broker monitor • broker worker • broker net worker • broker instance worker • fast-start failover ping • recovery coordinator • recovery logmerger • recovery applier • recovery sender • recovery receiver • redo transport test • temporary • datafile pre-create • redo log management • managed recovery DGPDB BG

Column	Datatype	Description
		• managed recovery DGPDB FG • Compress ORL master • Compress ORL worker • Compress SRL master • Compress SRL worker • UNKNOWN
PROC_TIME	TIMESTAMP(0)	Timestamp of when the process started or registered for inclusion in this fixed view
TASK_TIME	TIMESTAMP(0)	Timestamp of when the first task of the process was requested
TASK_DONE	VARCHAR2(1)	Indicates whether the task performed by the process is done (Y) or not (N)
ACTION	VARCHAR2(12)	Current action of the process. Possible values can include: • ANNOUNCING • APPLYING_LOG • ATTACHED • CLOSING • CONNECTED • ERROR • IDLE • OPENING • PROCESSING • RECEIVING • REGISTERING • STARTING • TERMINATING • UNKNOWN • UNUSED • WAIT_FOR_GAP • WAIT_FOR_LOG • WAIT_FOR_NEW_PRIMARY • WRITING
CLIENT_PID	NUMBER	For RFS and DTS processes, the PID of the process communicating with this process

Column	Datatype	Description
CLIENT_ROLE	VARCHAR2(16)	For RFS and DTS processes, the role of the process communicating with this process. Possible values can include: • none • async ORL multi • async ORL single • async SRL multi • async SRL single • log writer • sync • archive redo • archive gap • data transport • gap manager • failover • switchover • announce request • managed recovery • recovery • UNKNOWN
GROUP#	NUMBER	Group number of the log that the process is operating upon
RESETLOG_ID	NUMBER	Resetlog ID (branch) of the log that the process is operating upon
THREAD#	NUMBER	Thread number that the process is operating upon
SEQUENCE#	NUMBER	Sequence number that the process is operating upon
BLOCK#	NUMBER	Starting block number that the process is operating upon
BLOCK_COUNT	NUMBER	Number of blocks that the process is operating upon
DELAY_MINS	NUMBER	Archived redo log delay interval in minutes
DEST_ID	NUMBER	Destination ID that the process is currently operating upon
DEST_MASK	NUMBER	Mask of all destination IDs that the process will operate upon, where: Bit 0 is LOG_ARCHIVE_DEST1 Bit 1 is LOG_ARCHIVE_DEST2 Bit 2 is LOG_ARCHIVE_DEST3 and so on.
TENANT_KEY	NUMBER	Unique identifier assigned to each customer in the Oracle Cloud If the database is not in the cloud, then the value of this columns is 0. The combination of TENANT_KEY and DBID can be used to uniquely identify a database.
DBID	NUMBER	Database ID of the redo that the process is operating upon
DGID	NUMBER	Data Guard ID that the process must communicate with
INSTANCE	NUMBER	Instance number that the process must communicate with at the specified DGID

Column	Datatype	Description
STOP_STATE	VARCHAR2(7)	Indicates the method by which the process has been requested to stop: • NOW - Requested to stop immediately and exit • SOON - Requested to stop on next log and exit • COMMIT - Requested to write remaining redo and exit • N/A - No request to stop
APPLY	NUMBER	SCN at which the database has applied redo
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> Oracle recommends that you use this view instead of V$MANAGED_STANDBY.

8.164 V$DATAGUARD_STATS

V$DATAGUARD_STATS displays information about Oracle Data Guard metrics when queried on a standby database. No rows are returned when queried on a primary database.

Column	Datatype	Description
SOURCE_DBID	NUMBER	Database ID of the protected source database
SOURCE_DB_UNIQUE_NAME	VARCHAR2(32)	DB unique name of the protected source database

Column	Datatype	Description
NAME	VARCHAR2(32)	Name of the metric: • APPLY FINISH TIME - An estimate of the time needed to apply all received, but unapplied redo from the primary database. If there are one or more redo gaps on the standby database, an estimate of the time needed to apply all received, but unapplied redo up to the end of the last archived redo log before the beginning of the earliest redo gap. • APPLY LAG - Apply lag is a measure of the degree to which the data in a standby database lags behind the data in the primary database, due to delays in propagating and applying redo to the standby database. This value is relevent only to the applying instance. • TRANSPORT LAG - Transport lag is a measure of the degree to which the transport of redo to the standby database lags behind the generation of redo on the primary database. If there are one or more redo gaps on the standby database, the transport lag is calculated as if no redo has been received after the beginning of the earliest redo gap. • ESTIMATED STARTUP TIME - An estimate of the time needed to start and open the database.
VALUE	VARCHAR2(64)	Value of the metric
UNIT	VARCHAR2(30)	Unit of measurement
TIME_COMPUTED	VARCHAR2(30)	Local time at the standby database when the metric was computed
DATUM_TIME	VARCHAR2(30)	Local time at the standby database when the datum used to compute the metric was received The APPLY LAG and TRANSPORT LAG metrics are computed based on data that is periodically received from the primary database. An unchanging value in this column across multiple queries indicates that the standby database is not receiving data from the primary database.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.165 V$DATAGUARD_STATUS

V$DATAGUARD_STATUS displays messages recently written to the alert log or server process trace files that concern physical standby databases or redo transport services for all standby database types.

Column	Datatype	Description
FACILITY	VARCHAR2(24)	Facility that encountered the event: • Crash Recovery • Log Transport Services • Log Apply Services • Role Management Services • Remote File Server • Fetch Archive Log • Data Guard • Network Services
SEVERITY	VARCHAR2(13)	Severity of the event: • Informational - Informational message • Warning - Warning message • Error - Indicates the process has failed • Fatal • Control - An expected change in state such as the start or completion of an archival, log recovery, or switchover operation
DEST_ID	NUMBER	Destination ID number to which the event pertains. If the event does not pertain to a particular destination, then the value is 0.
MESSAGE_NUM	NUMBER	A chronologically increasing number giving each event a unique number
ERROR_CODE	NUMBER	Error ID pertaining to the event
CALLOUT	VARCHAR2(3)	Reserved for future use
TIMESTAMP	DATE	Message date
MESSAGE	VARCHAR2(256)	A text message describing the event
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.166 V$DATAPUMP_SESSIONWAIT_INFO

V$DATAPUMP_SESSIONWAIT_INFO displays information about the current or last wait for each session attached to a Data Pump job.

Column	Datatype	Description
WAITING_SESSION	NUMBER	Session identifier; maps to V$SESSION.SID
SERIAL_NUMBER	NUMBER	Session serial number (used to uniquely identify a session's objects); maps to V$SESSION.SERIAL#
SEQ_NUMBER	NUMBER	A number that uniquely identifies the current or last wait (incremented for each wait)

Column	Datatype	Description
EVENT	VARCHAR2(64)	If the session is currently waiting, then the resource or event for which the session is waiting. If the session is not in a wait, then the resource or event for which the session most recently waited. **See Also:** " Oracle Wait Events"
DP_WAITTIME	NUMBER	If the session is currently waiting, then the value is 0. If the session is not in a wait, then the value is as follows: • > 0 - Value is the duration of the last wait in hundredths of a second • -1 - Duration of the last wait was less than a hundredth of a second • -2 - Parameter TIMED_STATISTICS was set to false
DP_SECONDS_IN_WAIT	NUMBER	If the session is currently waiting, then the value is the amount of time waited for the current wait. If the session is not in a wait, then the value is the amount of time since the start of the last wait.
DP_STATE_IN_WAIT	VARCHAR2(19)	Wait state of the Data Pump session: • WAITING - Session is currently waiting • WAITED UNKNOWN TIME - Duration of the last wait is unknown; this is the value when the parameter TIMED_STATISTICS is set to false • WAITED SHORT TIME - Last wait was less than a hundredth of a second • WAITED KNOWN TIME - Duration of the last wait is specified in the DP_WAITTIME column
DP_P1TEXT	VARCHAR2(64)	Description of the first wait event parameter
DP_P1	NUMBER	First wait event parameter (in decimal)
DP_P2TEXT	VARCHAR2(64)	Description of the second wait event parameter
DP_P2	NUMBER	Second wait event parameter (in decimal)
DP_P3TEXT	VARCHAR2(64)	Description of the third wait event parameter
DP_P3	NUMBER	Third wait event parameter (in decimal)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

This view is available starting with Oracle Database 23ai.

8.167 V$DB_CACHE_ADVICE

V$DB_CACHE_ADVICE contains rows that predict the number of physical reads for the cache size corresponding to each row.

The rows also compute a "physical read factor," which is the ratio of the number of estimated reads to the number of reads actually performed by the real buffer cache during the measurement interval.

> **See Also:**
>
> "DB_CACHE_ADVICE"

Column	Datatype	Description
ID	NUMBER	Buffer pool identifier (ranges from 1 to 8)
NAME	VARCHAR2(20)	Buffer pool name
BLOCK_SIZE	NUMBER	Block size in bytes for buffers in this pool. Possible values: the standard block size, the power of 2 nonstandard block sizes, 2048, 4096, 8192, 16384, 32768.
ADVICE_STATUS	VARCHAR2(3)	Status of the advisory. ON indicates it is currently running; OFF indicates it is disabled (in this case the estimates are historical and calculated when last enabled).
SIZE_FOR_ESTIMATE	NUMBER	Cache size for prediction (in megabytes)
SIZE_FACTOR	NUMBER	Size factor with respect to the current cache size
BUFFERS_FOR_ESTIMATE	NUMBER	Cache size for prediction (in terms of buffers)
ESTD_PHYSICAL_READ_FACTOR	NUMBER	Physical read factor for this cache size, which is the ratio of the number of estimated physical reads to the number of reads in the real cache. If there are no physical reads in the real cache, the value of this column is null.
ESTD_PHYSICAL_READS	NUMBER	Estimated number of physical reads for this cache size
ESTD_PHYSICAL_READ_TIME	NUMBER	Estimated disk read time (in seconds)
ESTD_PCT_OF_DB_TIME_FOR_READS	NUMBER	Estimated disk time as a percentage of the total time
ESTD_CLUSTER_READS	NUMBER	Estimated total number of blocks foreground processes read from the global cache (Oracle Real Application Clusters only)
ESTD_CLUSTER_READ_TIME	NUMBER	Estimated total amount of time, in seconds, foreground processes read from global cache (Oracle Real Application Clusters only)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.168 V$DB_OBJECT_CACHE

V$DB_OBJECT_CACHE displays database objects that are cached in the library cache. Objects include tables, indexes, clusters, synonym definitions, PL/SQL procedures and packages, and triggers.

Column	Datatype	Description
OWNER	VARCHAR2(64)	Owner of the object
NAME	VARCHAR2(1000)	Name of the object
DB_LINK	VARCHAR2(64)	Database link name, if any
NAMESPACE	VARCHAR2(64)	Library cache namespace of the object: TABLE/PROCEDURE, BODY, TRIGGER, INDEX, CLUSTER, OBJECT
TYPE	VARCHAR2(64)	Type of the object: INDEX, TABLE, CLUSTER, VIEW, SET, SYNONYM, SEQUENCE, PROCEDURE, FUNCTION, PACKAGE, PACKAGE BODY, TRIGGER, CLASS, OBJECT, USER, DBLINK
SHARABLE_MEM	NUMBER	Amount of sharable memory in the shared pool consumed by the object
LOADS	NUMBER	Number of times the object has been loaded. This count also increases when an object has been invalidated.
EXECUTIONS	NUMBER	Not used **See Also:** "V$SQLAREA" to see actual execution counts
LOCKS	NUMBER	Number of users currently locking this object
PINS	NUMBER	Number of users currently pinning this object
KEPT	VARCHAR2(3)	(YES | NO) Depends on whether this object has been "kept" (permanently pinned in memory) with the PL/SQL procedure DBMS_SHARED_POOL.KEEP
CHILD_LATCH	NUMBER	Child latch number that is protecting the object. This column is obsolete and maintained for backward compatibility.
INVALIDATIONS	NUMBER	Total number of times objects in the namespace were marked invalid because a dependent object was modified
HASH_VALUE	NUMBER	Hash value of the object
LOCK_MODE	VARCHAR2(9)	Current lock mode of the object
PIN_MODE	VARCHAR2(9)	Current pin mode of the object
STATUS	VARCHAR2(19)	Status of the object
TIMESTAMP	VARCHAR2(19)	Timestamp for the specification of the object
PREVIOUS_TIMESTAMP	VARCHAR2(19)	Previous timestamp for the specification of the object
LOCKED_TOTAL	NUMBER	Total number of times the object has been locked
PINNED_TOTAL	NUMBER	Total number of times the object has been pinned
PROPERTY	VARCHAR2(80)	Property of the object. Possible values include HOT or HOTCOPY when the library cache hot copy feature is used using DBMS_SHARED_POOL.MARKHOT.
FULL_HASH_VALUE	VARCHAR2(32)	Full hash value of the object

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
CON_NAME	VARCHAR2(64)	Container name of the object. The value of this column is NULL in non-CDBs.
ADDR	RAW(8)	Address of the handle for this object
EDITION	VARCHAR2(138)	Edition name

See Also:

- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SHARED_POOL.KEEP procedure
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SHARED_POOL.MARKHOT procedure

8.169 V$DB_PIPES

V$DB_PIPES displays the pipes that are currently represented in the shared pool for this instance.

Column	Datatype	Description
OWNERID	NUMBER	Owner ID of the owner (if this is a private pipe), else NULL
NAME	VARCHAR2(1000)	Name of the pipe (for example, SCOTT.PIPE)
TYPE	VARCHAR2(7)	Type of the pipe: • PUBLIC • PRIVATE
PIPE_SIZE	NUMBER	Amount of memory the pipe uses **Note:** The value of this column may be larger than maxpipesize because of an internal algorithm.
SINGLETON	VARCHAR2(3)	Indicates whether the pipe is a singleton pipe (YES) or not (NO)
SHELFLIFE	NUMBER	The shelf life time (in seconds) for a message in a singleton pipe If the pipe is not a singleton pipe, then the value of this column is 0.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
CON_NAME	VARCHAR2(64)	Container name of the object. The value of this column is NULL in non-CDBs.

8.170 V$DB_TRANSPORTABLE_PLATFORM

V$DB_TRANSPORTABLE_PLATFORM displays all platforms to which the database can be transported using the RMAN CONVERT DATABASE command.

The transportable database feature only supports transports of the same endian platform. Therefore, V$DB_TRANSPORTABLE_PLATFORM displays fewer rows than V$TRANSPORTABLE_PLATFORM.

Column	Datatype	Description
PLATFORM_ID	NUMBER	Platform identification number
PLATFORM_NAME	VARCHAR2(101)	Platform name
ENDIAN_FORMAT	VARCHAR2(14)	Platform endian format: • Big • Little • UNKNOWN FORMAT
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$TRANSPORTABLE_PLATFORM"

8.171 V$DBFILE

V$DBFILE displays all data files making up the database. This view is retained for historical compatibility. Use of V$DATAFILE is recommended instead.

Column	Datatype	Description
FILE#	NUMBER	File identifier
NAME	VARCHAR2(513)	Name of the file
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$DATAFILE"

8.172 V$DBLINK

V$DBLINK describes all database links (links with IN_TRANSACTION = YES) opened by the session issuing the query on V$DBLINK. These database links must be committed or rolled back before being closed.

Column	Datatype	Description
DB_LINK	VARCHAR2(128)	Name of the database link
OWNER_ID	NUMBER	Owner of the database link UID
LOGGED_ON	VARCHAR2(3)	Whether the database link is currently logged on
HETEROGENEOUS	VARCHAR2(3)	Whether the database link is heterogeneous
PROTOCOL	VARCHAR2(6)	Communication protocol for the database link
OPEN_CURSORS	NUMBER	Whether there are open cursors for the database link
IN_TRANSACTION	VARCHAR2(3)	Whether the database link is currently in a transaction
UPDATE_SENT	VARCHAR2(3)	Whether there has been an update on the database link
COMMIT_POINT_STRENGTH	NUMBER	Commit point strength of the transactions on the database link
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.173 V$DEAD_CLEANUP

V$DEAD_CLEANUP shows the terminated processes and sessions present in the instance and their cleanup status.

Column	Datatype	Description
TYPE	VARCHAR2(64)	Indicates whether a row contains a DEAD PROCESS or KILLED SESSION
PADDR	RAW(8)	Process pointer. Can be joined with V$PROCESS. For a KILLED SESSION, this is the owner of the session, which can be NULL.
SADDR	RAW(8)	Session pointer. Can be joined with V$SESSION. For a DEAD PROCESS, this is the user session.
ROOT_ADDR	RAW(8)	Pointer to the root of the tree
CLEANUP_OWNER	VARCHAR2(64)	Indicates which process is responsible for cleanup of this tree: • CLEANUP PROCESS - a cleanup process is responsible • OWNER PROCESS - the root owner is responsible
STATE	VARCHAR2(64)	Cleanup state: • CLEANUP PENDING - Occurs for a DEAD PROCESS or KILLED SESSION that can be cleaned up, but PMON has not yet made an attempt • IN PROGRESS - A cleanup attempt is currently in progress • RESOURCES FREED - Occurs for a DEAD PROCESS or KILLED SESSION where all children have been freed, but the process or session itself is not yet freed • PARTIAL CLEANUP - Occurs if some of the children have been cleaned up
DEAD_TIME	NUMBER	Time since the DEAD PROCESS or KILLED SESSION was marked as such (in seconds)
CLEANUP_ATTEMPTS	NUMBER	Number of times PMON has attempted cleanup
LAST_ATTEMPT	NUMBER	How long ago the last cleanup attempt occurred (in seconds)
CLEANUP_PROCESS	RAW(8)	Process pointer for the cleanup process currently cleaning up this tree (can join with V$CLEANUP_PROCESS). It will be NULL if cleanup is not currently in progress or if the owner is responsible for cleanup.
CLEANUP_TIME	NUMBER	Total amount of time PMON has spent on cleanup of the process/session (in seconds)
NUM_BLOCKED	NUMBER	Number of sessions blocked on cleanup of this session
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$CLEANUP_PROCESS"

8.174 V$DELETED_OBJECT

V$DELETED_OBJECT displays information about deleted archived logs, data file copies and backup pieces from the control file.

The only purpose of this view is to optimize the recovery catalog resync operation. When an archived log, data file copy, or backup piece is deleted, the corresponding record is marked deleted.

Column	Datatype	Description
RECID	NUMBER	Deleted object record ID
STAMP	NUMBER	Deleted object record stamp
TYPE	VARCHAR2(26)	Identifies the type of deleted object: • ARCHIVED LOG • BACKUP PIECE • DATAFILE COPY • PROXY COPY • BACKUP PIECE AVAILABLE • BACKUP PIECE EXPIRED • PROXY COPY AVAILABLE • PROXY COPY EXPIRED • BACKUP PIECE UNAVAILABLE • PROXY COPY UNAVAILABLE • DATAFILE COPY AVAILABLE • DATAFILE COPY EXPIRED • DATAFILE COPY UNAVAILABLE • ARCHIVED LOG AVAILABLE • ARCHIVED LOG EXPIRED • ARCHIVED LOG UNAVAILABLE • BACKUP SET KEEP OPTIONS • BACKUP SET KEEP UNTIL • PROXY COPY KEEP OPTIONS • PROXY COPY KEEP UNTIL • DATAFILE COPY KEEP OPTIONS • DATAFILE COPY KEEP UNTIL • DATAFILE RENAME ON RESTORE
OBJECT_RECID	NUMBER	Record ID of the deleted object
OBJECT_STAMP	NUMBER	Record timestamp of the deleted object
OBJECT_DATA	NUMBER	Displays additional internal information related to this deleted object. For internal Oracle use only.
SET_STAMP	NUMBER	Set stamp of the deleted object
SET_COUNT	NUMBER	Set count of the deleted object

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.175 V$DG_BROKER_CONFIG

V$DG_BROKER_CONFIG provides a summary of an Oracle Data Guard broker configuration.

This is similar to the DGMGRL CLI's SHOW CONFIGURATION command. It provides a view of the entire Oracle Data Guard broker configuration from any database in the configuration.

Column	Datatype	Description
DATABASE	VARCHAR2(512)	Database unique name
CONNECT_IDENTIFIER	VARCHAR2(512)	Net connect identifier used to reach the database
DATAGUARD_ROLE	VARCHAR2(27)	Oracle Data Guard role of the database: • PRIMARY • PHYSICAL STANDBY • LOGICAL STANDBY • SNAPSHOT STANDBY • FAR SYNC INSTANCE • RECOVERY APPLIANCE
REDO_SOURCE	VARCHAR(30)	The database unique name of the redo source
ENABLED	VARCHAR2(5)	TRUE or FALSE to denote whether or not the database is managed by Oracle Data Guard broker
STATUS	NUMBER	An Oracle error number denoting the database's current status
SEVERITY	VARCHAR2(30)	Severity of the Oracle error. Possible values: • FAILURE • SUCCESS • WARNING
STATUS_MESSAGE	VARCHAR2(256)	Error message associated with the Oracle error number in the STATUS column
VERSION	VARCHAR2(30)	Version of the broker configuration
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.176 V$DG_BROKER_ROLE_CHANGE

V$DG_BROKER_ROLE_CHANGE displays information about the last ten role changes across a Data Guard broker configuration.

Column	Datatype	Description
EVENT	VARCHAR2(30)	Type of role change: • Failover • Fast-Start Failover • Immediate Failover • Switchover
STANDBY_TYPE	VARCHAR2(30)	Type of standby database: • Logical • Physical
OLD_PRIMARY	VARCHAR2(30)	Database unique name of the old primary database, that is, the primary database before the role change occurred
NEW_PRIMARY	VARCHAR2(30)	Database unique name of the new primary database, that is, the primary database after the role change occurred
FS_FAILOVER_REASON	VARCHAR2(255)	If the role change was a fast-start failover, then this column displays the reason for the fast-start failover. For example, the primary database became disconnected. Otherwise, the value of this column is null.
BEGIN_TIME	TIMESTAMP(9)	Begin time of the role change • If the role change was a failover, then this column displays the time at which the ALTER DATABASE FAILOVER statement was issued on the target standby. • If the role change was a switchover, then this column displays the time at which the ALTER DATABASE SWITCHOVER statement was issued on the old primary database.
END_TIME	TIMESTAMP(9)	End time of the role change For both failover and switchover role changes, this column displays the time at which the ALTER DATABASE OPEN operation was completed on the first instance of the new primary database.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

This view is available starting with Oracle Database 23ai.

8.177 V$DIAG_ALERT_EXT

V$DIAG_ALERT_EXT shows the contents of the XML-based alert log in the Automatic Diagnostic Repository (ADR) for the current container (PDB).

Column	Datatype	Description
ORIGINATING_TIMESTAMP	TIMESTAMP(9) WITH TIME ZONE	Date and time when the message was generated
NORMALIZED_TIMESTAMP	TIMESTAMP(9) WITH TIME ZONE	Date and time when the message originated, normalized for clock drift to the Oracle Enterprise Manager repository time
ORGANIZATION_ID	VARCHAR2(67)	ID of the organization that wrote the originating component, usually the domain of the organization
COMPONENT_ID	VARCHAR2(67)	ID of the product or component that originated the message
HOST_ID	VARCHAR2(67)	DNS hostname of originating host
HOST_ADDRESS	VARCHAR2(49)	IP of other network address of the originating host for the mesaage
MESSAGE_TYPE	NUMBER	Type of the message, indicating that a different type of response is required. Possible values include: • 1: UNKNOWN - Essentially the NULL type • 2: INCIDENT_ERROR - The program has encountered an error for some internal or unexpected reason, and it must be reported to Oracle Support • 3: ERROR - An error of some kind has occurred • 4: WARNING: An action occurred or a condition was discovered that should be reviewed and may require action • 5: NOTIFICATION: reports a normal action or event. This could be a user action such as "logon completed" • 6: TRACE: Output of a diagnostic trace
MESSAGE_LEVEL	NUMBER	Level the message belongs to. Lower level values imply higher severity for errors. Possible values include: • 1: CRITICAL: critical errors • 2: SEVERE: severe errors • 8: IMPORTANT: important message • 16: NORMAL: normal message
MESSAGE_ID	VARCHAR2(67)	ID of the message
MESSAGE_GROUP	VARCHAR2(67)	Name of the group to which the message belongs
CLIENT_ID	VARCHAR2(67)	ID of the client or security group that the message relates to
MODULE_ID	VARCHAR2(67)	ID of the module that originated the message. This value is unique within a component.
PROCESS_ID	VARCHAR2(35)	ID of the process that originated the message
THREAD_ID	VARCHAR2(67)	ID of the thread of the process that originated the message
USER_ID	VARCHAR2(131)	ID of the user that originated the message
INSTANCE_ID	VARCHAR2(67)	For internal use only
DETAILED_LOCATION	VARCHAR2(163)	Absolute pathname of supplemental detail file on the originating host
UPSTREAM_COMP_ID	VARCHAR2(103)	ID of a component that the originating component is working with on the upstream (client) side

Column	Datatype	Description
DOWNSTREAM_COMP_ID	VARCHAR2(103)	ID of a component that the originating component is working with on the downstream (server) side
EXECUTION_CONTEXT_ID	VARCHAR2(103)	Identifies the thread of execution that the originating component participates in
EXECUTION_CONTEXT_SEQUENCE	NUMBER	Execution sequence of the thread that the originating component participates in
ERROR_INSTANCE_ID	NUMBER	ID of the instance where error occurred
ERROR_INSTANCE_SEQUENCE	NUMBER	Instance sequence where error occurred
MESSAGE_TEXT	VARCHAR2(2051)	Fully formed and localized text of the message
MESSAGE_ARGUMENTS	VARCHAR2(515)	Arguments to be bound with the generic text of the message
SUPPLEMENTAL_ATTRIBUTES	VARCHAR2(515)	Supplemental attributes that are specific to a message. This field contains the impacts for an incident type error message.
SUPPLEMENTAL_DETAILS	VARCHAR2(515)	Supplemental data that is specific to a particular program and error message required to complete the diagnosis. Similar to the extra detail referred to in DETAILED_LOCATION but short enough to simply provide in the message itself
PARTITION	NUMBER	Segment number of physical file
RECORD_ID	NUMBER	Record number for the message (this value is same as the row number)
FILENAME	VARCHAR2(515)	Physical file on disk
LOG_NAME	VARCHAR2(67)	For internal use only
PROBLEM_KEY	VARCHAR2(553)	Describes the key for the current problem that the message is associated with
VERSION	NUMBER	ARB version number for the message
CON_UID	NUMBER	The unique ID of the container to which the data pertains
CONTAINER_ID	NUMBER	The ID of the container to which the data pertains
CONTAINER_NAME	VARCHAR2(33)	The name of the container to which the data pertains
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.178 V$DIAG_APP_TRACE_FILE

V$DIAG_APP_TRACE_FILE contains information about all trace files present in the Automatic Diagnostic Repository (ADR) for the current container (PDB) which contain application trace data (SQL_TRACE or OPTIMIZER_TRACE event data). This view also supports GV$ global views.

Column	Datatype	Description
ADR_HOME	VARCHAR2(444)	Path to the current ADR home
TRACE_FILENAME	VARCHAR2(68)	Displays the name of the process trace file
CHANGE_TIME	TIMESTAMP(3) WITH TIME ZONE	Displays the change time timestamp of the process trace fiile
MODIFY_TIME	TIMESTAMP(3) WITH TIME ZONE	Displays the last modification timestamp of the process trace file
SQL_TRACE	VARCHAR2(1)	Identifies if the process trace file contains SQL_TRACE data. Possible values include: • Y: This value is used when the process trace file contains SQL_TRACE event data • N: This value indicates that the process trace does not contain SQL_TRACE data
OPTIMIZER_TRACE	VARCHAR2(1)	Identifies if the process trace file contains OPTIMIZER_TRACE data. Possible values include: • Y: This value is used when the process trace file contains OPTIMIZER_TRACE event data • N: This value indicates that the process trace does not contain OPTIMIZER_TRACE data
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.179 V$DIAG_INCIDENT

V$DIAG_INCIDENT contains information about all incident metadata records present in the Automatic Diagnostic Repository (ADR) for the current container (PDB).

Column	Datatype	Description
INCIDENT_ID	NUMBER	ID for the current incident
PROBLEM_ID	NUMBER	ID for the problem that the incident is associated with
CREATE_TIME	TIMESTAMP(9) WITH TIME ZONE	Displays the date and time when the incident was created
CLOSE_TIME	TIMESTAMP(9) WITH TIME ZONE	Displays the date and time when the incident was closed

Column	Datatype	Description
STATUS	NUMBER	Describes the current status for the incident. Possible values include: • 1: Incident is inflight • 2: Incident is ready • 3: Incident is tracked • 4: Incident is closed • 5: Incident data is removed • 6: Incident has been purged • 7: Incident is incomplete
FLAGS	NUMBER	For internal use only
FLOOD_CONTROLLED	NUMBER	Describes the flood control status for the current incident. Possible values include: • 0: Incident is not flood-controlled • 1: Incident is fully flood controlled (no dumps)
ERROR_FACILITY	VARCHAR2(12)	Displays the error facility for the current incident
ERROR_NUMBER	NUMBER	Displays the error number for the current incident
ERROR_ARG1	VARCHAR2(66)	Displays error-arguments associated with the given incident
ERROR_ARG2	VARCHAR2(66)	Displays error-arguments associated with the given incident
ERROR_ARG3	VARCHAR2(66)	Displays error-arguments associated with the given incident
ERROR_ARG4	VARCHAR2(66)	Displays error-arguments associated with the given incident
ERROR_ARG5	VARCHAR2(66)	Displays error-arguments associated with the given incident
ERROR_ARG6	VARCHAR2(66)	Displays error-arguments associated with the given incident
ERROR_ARG7	VARCHAR2(66)	Displays error-arguments associated with the given incident
ERROR_ARG8	VARCHAR2(66)	Displays error-arguments associated with the given incident
SIGNALLING_COMPONENT	VARCHAR2(66)	Signalling component for the given incident
SIGNALLING_SUBCOMPONENT	VARCHAR2(66)	Signalling sub-component for the given incident
SUSPECT_COMPONENT	VARCHAR2(66)	Displays the suspect component for the given incident
SUSPECT_SUBCOMPONENT	VARCHAR2(66)	Displays the suspect sub-component for the given incident
ECID	VARCHAR2(66)	Execution context ID for the current incident
IMPACT	NUMBER	Describes the internal representation of the incident impact for the given incident
ERROR_ARG9	VARCHAR2(66)	Displays error-arguments associated with the given incident
ERROR_ARG10	VARCHAR2(66)	Displays error-arguments associated with the given incident
ERROR_ARG11	VARCHAR2(66)	Displays error-arguments associated with the given incident
ERROR_ARG12	VARCHAR2(66)	Displays error-arguments associated with the given incident
CON_UID	NUMBER	Describes the container unique ID to which the data pertains

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.180 V$DIAG_INFO

V$DIAG_INFO describes the state of Automatic Diagnostic Repository (ADR) functionality using NAME=VALUE pairs.

Column	Datatype	Description
INST_ID	NUMBER	Instance ID
NAME	VARCHAR2(64)	Identifies a piece of data that reflects the state of ADR, such as whether it is enabled, where the directories and files are located, and how many ongoing issues (incidents and problems) there are. Possible values include: • Diag Enabled: Indicates whether ADR is enabled or not • ADR Base through Health Monitor: Display different directories (ADR base, ADR home, and then subdirectories within the ADR home) • Default Trace File: Specifies the current default trace file for the current process • Active Problem Count and Active Incident Count: Specify how many problems/incidents there are in this ADR that *either* happened in the last 24 hours *or* have a piece of metadata set indicating that it is a persistent error (like a disk corruption)
VALUE	VARCHAR2(512)	Describes the current state of the piece of data identified in the NAME column
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.181 V$DIAG_OPT_TRACE_RECORDS

V$DIAG_OPT_TRACE_RECORDS contains all optimizer trace event data that is present in the trace files that are part of the current Automatic Diagnostic Repository (ADR). This view also supports GV$ global views.

Column	Datatype	Description
ADR_HOME	VARCHAR2(444)	Path to current ADR home
TRACE_FILENAME	VARCHAR2(68)	Displays the name of the process trace file
RECORD_LEVEL	NUMBER	Displays the level of the trace record
PARENT_LEVEL	NUMBER	Displays the top parent level of the trace record
RECORD_TYPE	NUMBER	Displays the type of the trace record. Possible values include: • 1: Regular trace record • 2: Freeform trace record • 3: Begin Section trace record • 4: Begin Dump trace record • 5: Bucket Dump Begin trace record • 6: Section End trace record • 7: Dump End trace record • 8: Bucket Dump End trace record
TIMESTAMP	TIMESTAMP(3) WITH TIME ZONE	Displays the timestamp when the trace record was produced
PAYLOAD	VARCHAR2(4000)	Describes the trace record payload (contents)
SECTION_ID	NUMBER	Displays the section ID / dump ID of the trace record
SECTION_NAME	VARCHAR2(64)	Displays the section name / dump name of the trace record
COMPONENT_NAME	VARCHAR2(64)	Displays the component name which produced the trace record
OPERATION_NAME	VARCHAR2(64)	Displays the operation name which produced the trace record
FILE_NAME	VARCHAR2(64)	Displays the name of the code file where this trace record is produced
FUNCTION_NAME	VARCHAR2(64)	Displays the function which produced this trace record
LINE_NUMBER	NUMBER	Displays the line number in the code file which produced this trace record
THREAD_ID	VARCHAR2(64)	Displays the operating system thread ID of the process which produced the trace record
SESSION_ID	NUMBER	Displays the user session ID which generated the trace record
SERIAL#	NUMBER	Displays the user session serial number which produced the trace record
SECURITY_LABEL	VARCHAR2(16)	Displays the trace record security label classification. Possible values: • ALGORITHM • CONFIG • DATA • INTERNAL • KEYS • METADATA • NONE • PROGRAM • STATIC • UNKNOWN
CON_UID	NUMBER	Displays the container unique ID where the trace record was produced
CONTAINER_NAME	VARCHAR2(64)	Displays the container name where the trace record was produced

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.182 V$DIAG_PROBLEM

V$DIAG_PROBLEM contains information about all problem metadata records present in the Automatic Diagnostic Repository (ADR) for the current container (PDB).

Column	Datatype	Description
PROBLEM_ID	NUMBER	Displays the ID for the current problem
PROBLEM_KEY	VARCHAR2(552)	Displays the problem key for the current problem
FIRST_INCIDENT	NUMBER	Displays the first incident ID for the current problem
FIRSTINC_TIME	TIMESTAMP(9) WITH TIME ZONE	Displays the timestamp when the first incident occurred for the current problem
LAST_INCIDENT	NUMBER	Displays the last incident ID for the current problem
LASTINC_TIME	TIMESTAMP(9) WITH TIME ZONE	Displays the timestamp when the last incident occurred for the current problem
IMPACT1	NUMBER	Displays the first impact for the current problem
IMPACT2	NUMBER	Displays the second impact for the current problem
IMPACT3	NUMBER	Displays the third impact for the current problem
IMPACT4	NUMBER	Displays the fourth impact for the current problem
SERVICE_REQUEST	VARCHAR2(66)	Displays the service request number for the current problem, if a number has been entered in Support Workbench
BUG_NUMBER	VARCHAR2(66)	Displays the bug number for the current problem, if a number has been entered in Support Workbench
CON_UID	NUMBER	Displays the container unique ID to which the data pertains
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.183 V$DIAG_SESS_OPT_TRACE_RECORDS

V$DIAG_SESS_OPT_TRACE_RECORDS contains all optimizer trace event data that is present in the trace files for the current user session that is part of the current Automatic Diagnostic Repository (ADR).

Column	Datatype	Description
ADR_HOME	VARCHAR2(444)	Path to current ADR home
TRACE_FILENAME	VARCHAR2(68)	Displays the name of the process trace file
RECORD_LEVEL	NUMBER	Displays the level of the trace record
PARENT_LEVEL	NUMBER	Displays the top parent level of the trace record
RECORD_TYPE	NUMBER	Displays the type of the trace record. Possible values include: • 1: Regular trace record • 2: Freeform trace record • 3: Begin Section trace record • 4: Begin Dump trace record • 5: Bucket Dump Begin trace record • 6: Section End trace record • 7: Dump End trace record • 8: Bucket Dump End trace record
TIMESTAMP	TIMESTAMP(3) WITH TIME ZONE	Displays the timestamp when the trace record was produced
PAYLOAD	VARCHAR2(4000)	Displays the trace record payload (contents)
SECTION_ID	NUMBER	Displays the section ID / dump ID of the trace record
SECTION_NAME	VARCHAR2(64)	Displays the section name / dump name of the trace record
COMPONENT_NAME	VARCHAR2(64)	Displays the component name which produced the trace record
OPERATION_NAME	VARCHAR2(64)	Displays the operation name which produced the trace record
FILE_NAME	VARCHAR2(64)	Displays the name of the code file where this trace record is produced
FUNCTION_NAME	VARCHAR2(64)	Displays the function which produced this trace record
LINE_NUMBER	NUMBER	Displays the line number in the code file which produced this trace record
THREAD_ID	VARCHAR2(64)	Displays the operating system thread ID of the process which produced the trace record
SESSION_ID	NUMBER	Displays the user session ID which generated the trace record
SERIAL#	NUMBER	Displays the user session serial number which produced the trace record

Column	Datatype	Description
SECURITY_LABEL	VARCHAR2(16)	Displays the trace record security label classification. Possible values: • ALGORITHM • CONFIG • DATA • INTERNAL • KEYS • METADATA • NONE • PROGRAM • STATIC • UNKNOWN
CON_UID	NUMBER	Displays the container unique ID where the trace record was produced
CONTAINER_NAME	VARCHAR2(64)	Displays the container name where the trace record was produced
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.184 V$DIAG_SESS_SQL_TRACE_RECORDS

V$DIAG_SESS_SQL_TRACE_RECORDS contains all SQL_TRACE data that is present in the trace files for the current user session that is part of the current Automatic Diagnostic Repository (ADR).

Column	Datatype	Description
ADR_HOME	VARCHAR2(444)	Path to current ADR home
TRACE_FILENAME	VARCHAR2(68)	Displays the name of the process trace file
RECORD_LEVEL	NUMBER	Displays the level of the trace record
PARENT_LEVEL	NUMBER	Displays the top parent level of the trace record
RECORD_TYPE	NUMBER	Displays the type of the trace record. Possible values include: • 1: Regular trace record • 2: Freeform trace record • 3: Begin Section trace record • 4: Begin Dump trace record • 5: Bucket Dump Begin trace record • 6: Section End trace record • 7: Dump End trace record • 8: Bucket Dump End trace record
TIMESTAMP	TIMESTAMP(3) WITH TIME ZONE	Displays the timestamp when the trace record was produced

Column	Datatype	Description
PAYLOAD	VARCHAR2(4000)	Displays the trace record payload (contents)
SECTION_ID	NUMBER	Displays the section ID / dump ID of the trace record
SECTION_NAME	VARCHAR2(64)	Displays the section name / dump name of the trace record
COMPONENT_NAME	VARCHAR2(64)	Displays the component name which produced the trace record
OPERATION_NAME	VARCHAR2(64)	Displays the operation name which produced the trace record
FILE_NAME	VARCHAR2(64)	Displays the name of the code file where this trace record is produced
FUNCTION_NAME	VARCHAR2(64)	Displays the function which produced this trace record
LINE_NUMBER	NUMBER	Displays the line number in the code file which produced this trace record
THREAD_ID	VARCHAR2(64)	Displays the operating system thread ID of the process which produced the trace record
SESSION_ID	NUMBER	Displays the user session ID which generated the trace record
SERIAL#	NUMBER	Displays the user session serial number which produced the trace record
SECURITY_LABEL	VARCHAR2(16)	Displays the trace record security label classification. Possible values: • ALGORITHM • CONFIG • DATA • INTERNAL • KEYS • METADATA • NONE • PROGRAM • STATIC • UNKNOWN
CON_UID	NUMBER	Displays the container unique ID where the trace record was produced
CONTAINER_NAME	VARCHAR2(64)	Displays the container name where the trace record was produced
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.185 V$DIAG_SQL_TRACE_RECORDS

V$DIAG_SQL_TRACE_RECORDS contains all SQL_TRACE data that is present in the trace files that are part of the current Automatic Diagnostic Repository (ADR). This view also supports GV$ global views.

Column	Datatype	Description
ADR_HOME	VARCHAR2(444)	Path to current ADR home
TRACE_FILENAME	VARCHAR2(68)	Displays the name of the process trace file
RECORD_LEVEL	NUMBER	Displays the level of the trace record
PARENT_LEVEL	NUMBER	Displays the top parent level of the trace record
RECORD_TYPE	NUMBER	Displays the type of the trace record. Possible values include: • 1: Regular trace record • 2: Freeform trace record • 3: Begin Section trace record • 4: Begin Dump trace record • 5: Bucket Dump Begin trace record • 6: Section End trace record • 7: Dump End trace record • 8: Bucket Dump End trace record
TIMESTAMP	TIMESTAMP(3) WITH TIME ZONE	Displays the timestamp when the trace record was produced
PAYLOAD	VARCHAR2(4000)	Displays the trace record payload (contents)
SECTION_ID	NUMBER	Displays the section ID / dump ID of the trace record
SECTION_NAME	VARCHAR2(64)	Displays the section name / dump name of the trace record
COMPONENT_NAME	VARCHAR2(64)	Displays the component name which produced the trace record
OPERATION_NAME	VARCHAR2(64)	Displays the operation name which produced the trace record
FILE_NAME	VARCHAR2(64)	Displays the name of the code file where this trace record is produced
FUNCTION_NAME	VARCHAR2(64)	Displays the function which produced this trace record
LINE_NUMBER	NUMBER	Displays the line number in the code file which produced this trace record
THREAD_ID	VARCHAR2(64)	Displays the operating system thread ID of the process which produced the trace record
SESSION_ID	NUMBER	Displays the user session ID which generated the trace record
SERIAL#	NUMBER	Displays the user session serial number which produced the trace record
SECURITY_LABEL	VARCHAR2(16)	Displays the trace record security label classification. Possible values: • ALGORITHM • CONFIG • DATA • INTERNAL • KEYS • METADATA • NONE • PROGRAM • STATIC • UNKNOWN
CON_UID	NUMBER	Displays the container unique ID where the trace record was produced
CONTAINER_NAME	VARCHAR2(64)	Displays the container name where the trace record was produced

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.186 V$DIAG_TRACE_FILE

V$DIAG_TRACE_FILE contains information about all trace files present in the Automatic Diagnostic Repository (ADR) for the current container (PDB). This view also supports GV$ global views.

Column	Datatype	Description
ADR_HOME	VARCHAR2(444)	Path to the current ADR home
TRACE_FILENAME	VARCHAR2(68)	Displays the name of the process trace file
CHANGE_TIME	TIMESTAMP(3) WITH TIME ZONE	Displays the change time timestamp of the process trace file
MODIFY_TIME	TIMESTAMP(3) WITH TIME ZONE	Displays the last modification timestamp of the process trace file
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.187 V$DIAG_TRACE_FILE_CONTENTS

V$DIAG_TRACE_FILE_CONTENTS contains trace data that is present in the trace files that are part of the current Automatic Diagnostic Repository (ADR). This view also supports GV$ global views.

Column	Datatype	Description
ADR_HOME	VARCHAR2(444)	Path to the current ADR home
TRACE_FILENAME	VARCHAR2(68)	Displays the name of the process trace file
RECORD_LEVEL	NUMBER	Displays the level of the trace record
PARENT_LEVEL	NUMBER	Displays the top parent level of the trace record

Column	Datatype	Description
RECORD_TYPE	NUMBER	Displays the type of the trace record. Possible values include: • 1: Regular trace record • 2: Freeform trace record • 3: Begin Section trace record • 4: Begin Dump trace record • 5: Bucket Dump Begin trace record • 6: Section End trace record • 7: Dump End trace record • 8: Bucket Dump End trace record
TIMESTAMP	TIMESTAMP(3) WITH TIME ZONE	Displays the timestamp when the trace record was produced
PAYLOAD	VARCHAR2(4000)	Displays the trace record payload (contents)
SECTION_ID	NUMBER	Displays the section ID / dump ID of the trace record
SECTION_NAME	VARCHAR2(64)	Displays the section name / dump name of the trace record
COMPONENT_NAME	VARCHAR2(64)	Displays the component name which produced the trace record
OPERATION_NAME	VARCHAR2(64)	Displays the operation name which produced the trace record
FILE_NAME	VARCHAR2(64)	Displays the name of the code file where this trace record is produced
FUNCTION_NAME	VARCHAR2(64)	Displays the function which produced this trace record
LINE_NUMBER	NUMBER	Displays the line number in the code file which produced this trace record
THREAD_ID	VARCHAR2(64)	Displays the operating system thread ID of the process which produced the trace record
SESSION_ID	NUMBER	Displays the user session ID which generated the trace record
SERIAL#	NUMBER	Displays the user session serial number which produced the trace record
SECURITY_LABEL	VARCHAR2(16)	Displays the trace record security label classification. Possible values: • ALGORITHM • CONFIG • DATA • INTERNAL • KEYS • METADATA • NONE • PROGRAM • STATIC • UNKNOWN
CON_UID	NUMBER	Displays the container unique ID where the trace record was produced
CONTAINER_NAME	VARCHAR2(64)	Displays the container name where the trace record was produced

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.188 V$DISPATCHER

V$DISPATCHER displays information about the dispatcher processes.

Column	Datatype	Description
NAME	VARCHAR2(4)	Name of the dispatcher process
NETWORK	VARCHAR2(1024)	Network address of the dispatcher
PADDR	RAW(4 | 8)	Process address
STATUS	VARCHAR2(16)	Status of the dispatcher: • WAIT - Idle • SEND - Sending a message • RECEIVE - Receiving a message • CONNECT - Establishing a connection • DISCONNECT - Handling a disconnect request • BREAK - Handling a break • TERMINATE - In the process of terminating • ACCEPT - Accepting connections (no further information available) • REFUSE - Rejecting connections (no further information available)
ACCEPT	VARCHAR2(3)	Indicates whether the dispatcher is accepting new connections (YES) or not (NO)
MESSAGES	NUMBER	Number of messages processed by the dispatcher
BYTES	NUMBER	Size (in bytes) of messages processed by the dispatcher
BREAKS	NUMBER	Number of breaks occurring in the connection
OWNED	NUMBER	Number of circuits owned by the dispatcher
CREATED	NUMBER	Number of circuits created by the dispatcher
IDLE	NUMBER	Total idle time for the dispatcher (in hundredths of a second)
BUSY	NUMBER	Total busy time for the dispatcher (in hundredths of a second)
CPU	NUMBER	Total CPU time for the dispatcher (in millionths of a second)
LISTENER	NUMBER	Most recent Oracle error number the dispatcher received from the listener
CONF_INDX	NUMBER	Zero-based index of the DISPATCHERS configuration used by the dispatcher

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.189 V$DISPATCHER_CONFIG

V$DISPATCHER_CONFIG displays information about the dispatcher configurations and their attributes.

Column	Datatype	Description
CONF_INDX	NUMBER	Zero-based index of the DISPATCHERS configuration
NETWORK	VARCHAR2(1024)	Network protocol or listening address of dispatchers (may be truncated)
DISPATCHERS	NUMBER	Number of dispatchers to maintain for the configuration
CONNECTIONS	NUMBER	Maximum number of concurrent connections per dispatcher
SESSIONS	NUMBER	Maximum number of concurrent sessions per dispatcher
MULTIPLEX	VARCHAR2(4)	Indicates whether Session Multiplexing is on: • IN • OUT • BOTH • OFF
LISTENER	VARCHAR2(1200)	Listeners to register dispatchers with (may be truncated)
SERVICE	VARCHAR2(512)	Service names supported (may be truncated)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.190 V$DISPATCHER_RATE

V$DISPATCHER_RATE displays rate statistics for a number of activities performed by the dispatcher processes.

Collected samples have an activity-specific "time-to-live" (TTL_* columns). Statistics are reported over the following two types of time intervals:

- Current statistics (CUR_ columns)

  Current statistics use samples collected over the most recent time-to-live interval.

- Historical statistics (AVG_ and most of the MAX_ columns)

  Historical statistics make use of all samples that are no longer current.

At the time of collection, a sample is current. After the time-to-live has elapsed, the sample becomes historical. Each type of activity has a specific scale (represented by the SCALE_* columns) at which the statistics are reported.

Column	Datatype	Description
NAME	VARCHAR2(4)	Name of the dispatcher process
PADDR	RAW(4 | 8)	Address of the dispatcher process
CUR_LOOP_RATE	NUMBER	Rate at which the dispatcher has been iterating through its dispatching loop, reported over the past TTL_LOOPS, in iterations/SCALE_LOOPS
CUR_EVENT_RATE	NUMBER	Rate at which the dispatcher has been processing dispatcher events, reported over the past TTL_LOOPS, in events/SCALE_LOOPS. Such dispatcher events include network events and shared server requests.
CUR_EVENTS_PER_LOOP	NUMBER	Average number of events the dispatcher has been processing in each iteration through its dispatching loop, reported over the past TTL_LOOPS, in events/iteration
CUR_MSG_RATE	NUMBER	Rate at which the dispatcher has been relaying messages between clients and shared servers, reported over the past TTL_MSG, in messages/SCALE_MSG
CUR_SVR_BUF_RATE	NUMBER	Rate at which the dispatcher has been relaying buffers to shared servers, reported over the past TTL_SVR_BUF, in messages/SCALE_SVR_BUF
CUR_SVR_BYTE_RATE	NUMBER	Rate at which the dispatcher has been relaying data to shared servers, reported over the past TTL_SVR_BUF, in bytes/SCALE_SVR_BUF
CUR_SVR_BYTE_PER_BUF	NUMBER	Average number of data types in each buffer relayed to shared servers, reported over the past TTL_SVR_BUF, in bytes/buffer
CUR_CLT_BUF_RATE	NUMBER	Rate at which the dispatcher has been relaying buffers to clients, reported over the past TTL_CLT_BUF, in buffers/SCALE_CLT_BUF
CUR_CLT_BYTE_RATE	NUMBER	Rate at which the dispatcher has been relaying data to clients, reported over the past TTL_CLT_BUF, in bytes/SCALE_CLT_BUF
CUR_CLT_BYTE_PER_BUF	NUMBER	Average number of data bytes in each buffer relayed to clients, reported over the past TTL_CLT_BUF, in bytes/buffer
CUR_BUF_RATE	NUMBER	Rate at which the dispatcher has been relaying buffers to either clients or shared servers, reported over the past TTL_BUF, in bytes/SCALE_BUF
CUR_BYTE_RATE	NUMBER	Rate at which the dispatcher has been relaying data to either clients or shared servers, reported over the past TTL_BUF, in bytes/SCALE_BUF
CUR_BYTE_PER_BUF	NUMBER	Average number of data bytes in each buffer relayed to either clients or shared servers, reported over the past TTL_BUF, in bytes/buffer
CUR_IN_CONNECT_RATE	NUMBER	Rate at which the dispatcher has been accepting incoming client connections, reported over the past TTL_IN_CONNECT, in connections/SCALE_IN_CONNECT

Column	Datatype	Description
CUR_OUT_CONNECT_RATE	NUMBER	Rate at which the dispatcher has been establishing outbound connections, reported over the past TTL_OUT_CONNECT, in connections/SCALE_OUT_CONNECT
CUR_RECONNECT_RATE	NUMBER	In a connection pooling setup, the rate at which clients have been reconnecting to the dispatcher, reported over the past TTL_RECONNECT, in reconnections/SCALE_RECONNECT
MAX_LOOP_RATE	NUMBER	Maximum rate at which the dispatcher has ever iterated through its dispatching loop, reported in iterations/SCALE_LOOPS, over the dispatcher's lifetime excluding the past TTL_LOOPS
MAX_EVENT_RATE	NUMBER	Maximum rate at which the dispatcher has ever processed dispatcher events, reported in events/SCALE_LOOPS, over the dispatcher's lifetime excluding the past TTL_LOOPS
MAX_EVENTS_PER_LOOP	NUMBER	Maximum number of events the dispatcher has ever processed in one iteration through its dispatching loop, reported in events/ iteration, over the dispatcher's lifetime
MAX_MSG_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed messages between clients and shared servers, reported in messages/ SCALE_MSG, over the dispatcher's lifetime excluding the past TTL_MSG
MAX_SVR_BUF_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed buffers to shared servers, reported in buffers/SCALE_SVR_BUF, over the dispatcher's lifetime excluding the past TTL_SVR_BUF
MAX_SVR_BYTE_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed data to shared servers, reported in bytes/SCALE_SVR_BUF, over the dispatcher's lifetime excluding the past TTL_SVR_BUF
MAX_SVR_BYTE_PER_BUF	NUMBER	Maximum number of data bytes the dispatcher has ever relayed in one buffer to a client, reported in bytes/buffer, over the dispatcher's lifetime
MAX_CLT_BUF_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed buffers to either clients or shared servers, reported in buffers/ SCALE_CLT_BUF, over the dispatcher's life time excluding the past TTL_CLT_BUF
MAX_CLT_BYTE_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed buffers to clients, reported in bytes/SCALE_CLT_BUF, over the dispatcher's lifetime excluding the last TTL_CLT_BUF
MAX_CLT_BYTE_PER_BUF	NUMBER	Maximum number of data bytes the dispatcher has ever relayed in one buffer to a client, reported in bytes/buffer, over the dispatcher's lifetime
MAX_BUF_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed buffers to either clients or shared servers, reported in buffers/SCALE_BUF, over the dispatcher's lifetime, excluding the past TTL_BUF
MAX_BYTE_RATE	NUMBER	Maximum rate at which the dispatcher has ever relayed data to either clients or shared servers, reported in bytes/SCALE_BUF, over the dispatcher's lifetime excluding the past TTL_BUF
MAX_BYTE_PER_BUF	NUMBER	Maximum number of data bytes the dispatcher has ever relayed in one buffer to either a client or a shared server, reported in bytes/ buffer, over the dispatcher's lifetime

Column	Datatype	Description
MAX_IN_CONNECT_RATE	NUMBER	Maximum rate at which the dispatcher has ever accepted incoming client connections, reported in connections/SCALE_IN_CONNECT, over the dispatcher's lifetime excluding the past TTL_IN_CONNECT
MAX_OUT_CONNECT_RATE	NUMBER	Maximum rate at which the dispatcher has ever established outbound connections, reported in connections/SCALE_OUT_CONNECT, over the dispatcher's lifetime excluding the past TTL_OUT_CONNECT
MAX_RECONNECT_RATE	NUMBER	In a connection pooling setup, the maximum rate at which clients have ever reconnected to this dispatcher, reported in reconnections/SCALE_RECONNECT, over the dispatcher's lifetime excluding the past TTL_RECONNECT
AVG_LOOP_RATE	NUMBER	Historical average rate at which the dispatcher has iterated through its dispatching loop, reported in iterations/SCALE_LOOPS, over the dispatcher's lifetime excluding the past TTL_LOOPS
AVG_EVENT_RATE	NUMBER	Historical average rate at which the dispatcher has processed dispatcher events, reported in events/SCALE_LOOPS, over the dispatcher's lifetime excluding the past TTL_LOOPS
AVG_EVENTS_PER_LOOP	NUMBER	Historical average number of events the dispatcher has processed in one iteration through its dispatching loop, reported in events/iteration, over the dispatcher's lifetime excluding the past TTL_LOOPS
AVG_MSG_RATE	NUMBER	Historical average rate at which the dispatcher has relayed messages between clients and shared servers, reported in messages/SCALE_MSG, over the dispatcher's lifetime excluding the past TTL_MSG
AVG_SVR_BUF_RATE	NUMBER	Historical average rate at which the dispatcher has relayed buffers to shared servers, reported in buffers/SCALE_SVR_BUF, over the dispatcher's lifetime excluding the past TTL_SVR_BUF
AVG_SVR_BYTE_RATE	NUMBER	Historical average rate at which the dispatcher has relayed data to shared servers, reported in bytes/SCALE_SVR_BUF, over the dispatcher's lifetime excluding the past TTL_SVR_BUF
AVG_SVR_BYTE_PER_BUF	NUMBER	Historical average number of data bytes per buffer the dispatcher has relayed to shared servers, reported in bytes/buffer, over the dispatcher's lifetime excluding the past TTL_SVR_BUF
AVG_CLT_BUF_RATE	NUMBER	Historical average rate at which the dispatcher has relayed buffers to clients, reported in buffers/SCALE_CLT_BUF, over the dispatcher's lifetime excluding the past TTL_CLT_BUF
AVG_CLT_BYTE_RATE	NUMBER	Historical average rate at which the dispatcher has relayed data to clients, reported in bytes/SCALE_CLT_BUF, over the dispatcher's lifetime excluding the past TTL_CLT_BUF
AVG_CLT_BYTE_PER_BUF	NUMBER	Historical average number of data bytes per buffer the dispatcher has relayed to clients, reported in bytes/buffer, over the dispatcher's lifetime excluding the past TTL_CLT_BUF
AVG_BUF_RATE	NUMBER	Historical average rate at which the dispatcher has relayed buffers to either clients or shared servers, reported in buffers/SCALE_BUF, over the dispatcher's lifetime excluding the past TTL_BUF
AVG_BYTE_RATE	NUMBER	Historical average rate at which the dispatcher has relayed data to either clients or shared servers, reported in bytes/SCALE_BUF, over the dispatcher's lifetime excluding the past TTL_BUF

Column	Datatype	Description
AVG_BYTE_PER_BUF	NUMBER	Historical average number of data bytes per buffer the dispatcher has relayed to either clients or shared servers, reported in bytes/buffer, over the dispatcher's lifetime excluding the past TTL_BUF
AVG_IN_CONNECT_RATE	NUMBER	Historical average rate at which the dispatcher has accepted incoming client connections, reported in connections/SCALE_IN_CONNECT, over the dispatcher's lifetime excluding the past TTL_IN_CONNECT
AVG_OUT_CONNECT_RATE	NUMBER	Historical average rate at which the dispatcher has established outbound connections, reported in connections/SCALE_OUT_CONNECT, over the dispatcher's lifetime excluding the past TTL_OUT_CONNECT
AVG_RECONNECT_RATE	NUMBER	In a connection pooling setup, the historical average rate at which clients have reconnected to this dispatcher, reported in reconnections/SCALE_RECONNECT, over the dispatcher's lifetime excluding the past TTL_RECONNECT
TTL_LOOPS	NUMBER	Time-to-live for "loops" samples, reported in hundredths of a second. Default is 10 minutes.
TTL_MSG	NUMBER	Time-to-live for "messages" samples, reported in hundredths of a second. Default is 10 seconds.
TTL_SVR_BUF	NUMBER	Time-to-live for "buffers to servers" samples, reported in hundredths of a second. Default is 1 second.
TTL_CLT_BUF	NUMBER	Time-to-live for "buffers to clients" samples, reported in hundredths of a second. Default is 1 second.
TTL_BUF	NUMBER	Time-to-live for "buffers to clients/servers" samples, reported in hundredths of a second. Default is 1 second.
TTL_IN_CONNECT	NUMBER	Time-to-live for "inbound connections" samples, reported in hundredths of a second. Default is 10 minutes.
TTL_OUT_CONNECT	NUMBER	Time-to-live for "outbound connections" samples, reported in hundredths of a second. Default is 10 minutes.
TTL_RECONNECT	NUMBER	Time-to-live for "reconnections" samples, reported in hundredths of a second. Default is 10 minutes.
SCALE_LOOPS	NUMBER	Scale for "loops" statistics, reported in hundredths of a second. Default is 1 minute.
SCALE_MSG	NUMBER	Scale for "messages" statistics, reported in hundredths of a second. Default is 1 second.
SCALE_SVR_BUF	NUMBER	Scale for "buffers to servers" statistics, reported in hundredths of a second. Default is 1/10 second.
SCALE_CLT_BUF	NUMBER	Scale for "buffers to clients" statistics, reported in hundredths of a second. Default is 1/10 second.
SCALE_BUF	NUMBER	Scale for "buffers to clients/servers" statistics, reported in hundredths of a second. Default is 1/10 second.
SCALE_IN_CONNECT	NUMBER	Scale for "inbound connections" statistics, reported in hundredths of a second. Default is 1 minute.
SCALE_OUT_CONNECT	NUMBER	Scale for "outbound connections" statistics, reported in hundredths of a second. Default is 1 minute.
SCALE_RECONNECT	NUMBER	Scale for "reconnections" statistics, reported in hundredths of a second. Default is 1 minute.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.191 V$DNFS_CHANNELS

V$DNFS_CHANNELS displays information about the Oracle process connections (channels) open to NFS servers.

Column	Datatype	Description
PNUM	NUMBER	Oracle process number
SVRNAME	VARCHAR2(255)	NFS server name
PATH	VARCHAR2(255)	Network path to the NFS server specified by IP address or by name
LOCAL	VARCHAR2(255)	Local path on the database host specified by IP address or by name
CH_ID	NUMBER	Direct NFS channel identifier
SVR_ID	NUMBER	Direct NFS server identifier
SENDS	NUMBER	Send operations over the channel since the last select
RECVS	NUMBER	Receive operations over the channel since the last select
PINGS	NUMBER	Ping operations over the channel since the last select
SPRECO	NUMBER	Reconnects for the channel on the same port since the last select, given that the reconnect occurred during the first series of reconnect attempts. If the first series of reconnect attempts fails and the reconnect process on that channel times out for 5 minutes, the next reconnect on that channel will not increment either the SPRECO or DPRECO columns, regardless of the port connected to.
DPRECO	NUMBER	Reconnects for the channel on a different port since the last select, given that the reconnect occurred during the first series of reconnect attempts. If the first series of reconnect attempts fails and the reconnect process on that channel times out for 5 minutes, the next reconnect on that channel will not increment either the SPRECO or DPRECO columns, regardless of the port connected to.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Column	Datatype	Description
RDMA	NUMBER	Indicates whether RDMA is enabled for the channel or not. Possible values: • 0: RDMA is not enabled for the channel • 1: RDMA is enabled for the channel
RDMA_CREDITS	NUMBER	The number of RDMA credits supported by the server
CLIENTPORT	NUMBER	The client port to which the channel is bounded
ACTIVE_SPEED	NUMBER	The active speed of the HCA card present (in Gb/second)
PEAK_FMR	NUMBER	The size of fast memory registration (FMR) memory registered by the channel (in bytes)
CURRENT_FMR	NUMBER	The current FMR memory registered (in bytes)
FMRREG_COUNT	NUMBER	The number of FMR memory registration calls for the channel

> **Note:**
>
> RDMA functionality is enabled only for the Exadata environment

8.192 V$DNFS_FILES

V$DNFS_FILES displays information about the Oracle process files open through Direct NFS.

Column	Datatype	Description
FILENAME	VARCHAR2(513)	File name
FILESIZE	NUMBER	File Size
PNUM	NUMBER	Oracle process number which opened the file
SVR_ID	NUMBER	Direct NFS server identifier which identifies the server the file is open on
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.193 V$DNFS_SERVERS

V$DNFS_SERVERS displays information about the Direct NFS servers accessed by Direct NFS.

Column	Datatype	Description
ID	NUMBER	Direct NFS server identifier
SVRNAME	VARCHAR2(255)	NFS server name
DIRNAME	VARCHAR2(1024)	Mounted directory
MNTPORT	NUMBER	NFS mount port
NFSPORT	NUMBER	NFS port
NFSVERSION	VARCHAR2(8)	NFS version
WTMAX	NUMBER	WTMAX exported by the NFS server
RTMAX	NUMBER	RTMAX exported by the NFS server
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
RDMAENABLE	VARCHAR2(16)	Indicates whether the server is RDMA enabled. Possible values: • YES: The server is RDMA enabled. • NO: The server is not RDMA enabled.
RDMAPORT	NUMBER	The port number for RDMA communications on the server. The value is always 20049.
SECURITY	VARCHAR2(32)	NFS RPC authentication method used for the given NFS export

> **Note:**
>
> RDMA functionality is enabled only for the Exadata environment

8.194 V$DNFS_STATS

V$DNFS_STATS displays information about the Oracle process NFS operation statistics issued by Direct NFS.

Column	Datatype	Description
PNUM	NUMBER	Oracle process number that statistics are relevant to
NFS_NULL	NUMBER	Null
NFS_GETATTR	NUMBER	Get attributes
NFS_SETATTR	NUMBER	Set attributes
NFS_LOOKUP	NUMBER	Lookup object
NFS_ACCESS	NUMBER	Access object
NFS_READLINK	NUMBER	Read link
NFS_READ	NUMBER	Read file

Column	Datatype	Description
NFS_WRITE	NUMBER	Write file
NFS_CREATE	NUMBER	Create file
NFS_MKDIR	NUMBER	Make directory
NFS_SYMLINK	NUMBER	Symbolic link
NFS_MKNOD	NUMBER	Make node
NFS_REMOVE	NUMBER	Remove file
NFS_RMDIR	NUMBER	Remove directory
NFS_RENAME	NUMBER	Rename
NFS_LINK	NUMBER	Link
NFS_READDIR	NUMBER	Read directory
NFS_READDIRPLUS	NUMBER	Read directory plus
NFS_FSSTAT	NUMBER	File system status
NFS_FSINFO	NUMBER	File system information
NFS_PATHCONF	NUMBER	Path configuration
NFS_COMMIT	NUMBER	Commit
NFS_MOUNT	NUMBER	Mount
NFS_READBYTES	NUMBER	Number of bytes read from NFS server
NFS_WRITEBYTES	NUMBER	Number of bytes written to NFS server
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.195 V$DYNAMIC_REMASTER_STATS

V$DYNAMIC_REMASTER_STATS displays statistical information about the dynamic remastering process of object affinity and read-mostly. All times are given in hundredths of a second, except where otherwise noted, and total values reflect what has been collected since instance startup.

Column	Datatype	Description
REMASTER_TYPE	VARCHAR2(11)	Remaster process type. Possible values: • AFFINITY: This value is used for the row containing statistics that pertain to dynamic remastering activity on object affinity. • READ-MOSTLY: This value is used for the row containing statistics that pertain to dynamic remastering activity on read-mostly objects.
REMASTER_OPS	NUMBER	Total number of dynamic remastering operations
REMASTER_TIME	NUMBER	Total dynamic remastering time

Column	Datatype	Description
REMASTERED_OBJECTS	NUMBER	Total number of objects dynamically remastered due to affinity
PERSISTENT_OBJECTS	NUMBER	Current number of objects that are marked persistent read-mostly in the cluster
QUIESCE_TIME	NUMBER	Total quiesce step time
FREEZE_TIME	NUMBER	Total freeze step time
CLEANUP_TIME	NUMBER	Total cleanup step time
REPLAY_TIME	NUMBER	Total replay step time
FIXWRITE_TIME	NUMBER	Total fixwrite step time
SYNC_TIME	NUMBER	Total synchronization step time
RESOURCES_CLEANED	NUMBER	Total number of resources cleaned in the cleanup steps
REPLAYED_LOCKS_SENT	NUMBER	Total number of locks replayed to other instances in the replay steps
REPLAYED_LOCKS_RECEIVED	NUMBER	Total number of locks received from other instances in the replay steps
CURRENT_OBJECTS	NUMBER	Current number of objects remastered on this instance due to affinity or the current number of objects that are marked read-mostly in the cluster
REMASTERED_BUFFERS	NUMBER	Total sum of the sizes (number of buffers) of all dynamically remastered objects The size of a buffer is specified by the DB_BLOCK_SIZE initialization parameter. The default is 8192 bytes.
AVG_BUFFER_AGE	NUMBER	Average time (in seconds) that buffers spent in the request queue, waiting to be processed
FILTERED_OBJECTS	NUMBER	Number of requests that were filtered (not processed)
FILTERED_BUFFERS	NUMBER	Total sum of the sizes (number of buffers) of all requests that were filtered The size of a buffer is specified by the DB_BLOCK_SIZE initialization parameter. The default is 8192 bytes.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.196 V$EDITIONABLE_TYPES

V$EDITIONABLE_TYPES lists all the editionable types based on the current compatibility setting. The SELECT privilege on V$EDITIONABLE_TYPES will be granted to PUBLIC.

The database compatibility setting will determine the set of editionable types.

With compatibility set to 11.2 or 12, this set includes FUNCTION, LIBRARY, PACKAGE, PACKAGE BODY, PROCEDURE, SYNONYM, TRIGGER, TYPE, TYPE BODY, and VIEW.

With compatibility set to 12, the set will include these types as well as the SQL TRANSLATION PROFILE.

Column	Datatype	Description
EDITIONABLE_TYPE	VARCHAR2(64)	The name of the type that is editionable
TYPE#	NUMBER	The number of the type that is editionable
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

For more information about edition-based redefinitions, see *Oracle Database Development Guide*.

8.197 V$EMON

V$EMON displays performance statistics per event monitor (EMON) worker for diagnosability of notifications. All processing time and latency is in seconds.

Column	Datatype	Description
EMON#	NUMBER	EMON identifier (0 - 9)
SID	NUMBER	Session identifier
STARTUP_TIME	TIMESTAMP(3) WITH TIME ZONE	Time when this EMON worker was started
SERVER_TYPE	VARCHAR2(8)	Notification quality of the service provided by EMON: • REGULAR • RELIABLE
STATUS	VARCHAR2(6)	EMON status: • IDLE • ACTIVE
STATUS_CHANGE_TIME	TIMESTAMP(3) WITH TIME ZONE	Time at which EMON switched to the current STATUS
NUM_NTFNS	NUMBER	Total number of notifications (including grouping notifications)
NUM_GROUPING_NTFNS	NUMBER	Number of grouping notifications
NUM_NTFNS_ALL_GROUPS	NUMBER	Total number of events in all notification groups
NUM_OCI_NTFNS	NUMBER	Number of OCI notifications
NUM_PLSQL_NTFNS	NUMBER	Number of PL/SQL notifications
NUM_EMAIL_NTFNS	NUMBER	Number of E-mail notifications
NUM_HTTP_NTFNS	NUMBER	Number of HTTP notifications

Column	Datatype	Description
NUM_EVENTS_PROCESSED	NUMBER	Number of events posted by a publisher for which notifications have been delivered
NUM_EVENTS_PENDING	NUMBER	Number of events posted by a publisher for which notifications are not yet delivered
NUM_ANONYMOUS_NTFNS	NUMBER	Number of anonymous notifications
NUM_AQ_NTFNS	NUMBER	Number of AQ notifications
NUM_DBCHANGE_NTFNS	NUMBER	Number of DBChange notifications
TOTAL_ANONYMOUS_NTFN_TIME	NUMBER	Total time to process Anonymous notifications
TOTAL_AQ_NTFN_TIME	NUMBER	Total time to process AQ notifications
TOTAL_DBCHANGE_NTFN_TIME	NUMBER	Total time to process dbchange notifications
TOTAL_PLSQL_NTFN_TIME	NUMBER	Total time to process PL/SQL notifications
TOTAL_OCI_NTFN_TIME	NUMBER	Total time to process OCI notifications
TOTAL_EMAIL_NTFN_TIME	NUMBER	Total time to process E-mail notifications
TOTAL_HTTP_NTFN_TIME	NUMBER	Total time to process HTTP notifications
TOTAL_EMON_LATENCY	NUMBER	Total latency in processing events
REGISTRATIONS_EXPIRED	NUMBER	Number of expired registrations
REGISTRATIONS_PURGED	NUMBER	Number of purged registrations
REGISTRATIONS_INVALID	NUMBER	Number of registrations invalidated due to notification delivery failure
LAST_UPDATE_TIME	TIMESTAMP(3) WITH TIME ZONE	Time when statistics were last updated
CON_ID	NUMBER	The ID of the container to which the data pertains. The CON_ID value in this view is always 0. The rows pertain to the entire CDB or to the non-CDB.

8.198 V$ENABLEDPRIVS

V$ENABLEDPRIVS displays the system privileges that have been granted to the current user directly or through the currently enabled roles.

Column	Datatype	Description
PRIV_NUMBER	NUMBER	Numeric identifier of the system privilege The matching privilege name for each PRIV_NUMBER can be found in the table SYSTEM_PRIVILEGE_MAP.
SCOPE	VARCHAR2(11)	Indicates the scope with which a privilege was granted. Possible values: • COMMON • APPLICATION • LOCAL

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "SYSTEM_PRIVILEGE_MAP"

8.199 V$ENABLEDSCHEMAPRIVS

V$ENABLEDSCHEMAPRIVS displays the schema privileges that have been granted to the current user directly or through the currently enabled roles.

Column	Datatype	Description
PRIV_NUMBER	NUMBER	Numeric identifier of the schema privilege The matching privilege name for each PRIV_NUMBER can be found in the table SYSTEM_PRIVILEGE_MAP.
SCHEMA	NUMBER	Schema on which the privilege was granted
SCOPE	VARCHAR2(11)	Indicates the scope with which the privilege was granted. Possible values: • COMMON • APPLICATION • LOCAL
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

8.200 V$ENCRYPTED_TABLESPACES

V$ENCRYPTED_TABLESPACES displays information about tablespaces that are encrypted.

The information displayed by this view is meaningful only for tablespaces in open containers. This is because the information is derived after the file headers making up a tablespace have been examined during the open operation.

Column	Datatype	Description
TS#	NUMBER	Tablespace number
ENCRYPTIONALG	VARCHAR2(7)	Encryption algorithm: • NONE • 3DES168 • AES128 • AES192 • AES256
ENCRYPTEDTS	VARCHAR2(3)	Indicates whether the tablespace is encrypted (YES) or not (NO)
ENCRYPTEDKEY	RAW(32)	Encrypted version of the tablespace key for the encrypted tablespace
MASTERKEYID	RAW(16)	ID of the master key that was used to encrypt the tablespace key
BLOCKS_ENCRYPTED	NUMBER	Number of tablespace blocks that have been encrypted during the lifetime of this instance
BLOCKS_DECRYPTED	NUMBER	Number of tablespace blocks that have been decrypted during the lifetime of this instance
KEY_VERSION	NUMBER	Every encrypt/decrypt/rekey of a tablespace adds a carnation/version of the tablespace key, and the key version is incremented. A decrypted tablespace could still have a none-zero key version. In certain scenarios, however, the tablespace key version might reset to 0; for example, when a tablespace or a pluggable database (PDB) is plugged into a foreign database, or if the control file is recreated.
STATUS	VARCHAR2(10)	Shows the status of a tablespace. Possible values: • NORMAL: Used when the tablespace is not in one of the other statuses. • REKEYING: Used when a rekey operation is taking place • ENCRYPTING: Used when an encrypt operation is taking place • DECRYPTING: Used when a decrypt operation is taking place • UNKNOWN: Used when the database is mounted but not open (before the datafile is online and the key is known to the database) **Note:** The REKEYING, ENCRYPTING, and DECRYPTING values can also be reported after a datafile, whose encryption state is different from the tablespace definition, is restored. In such cases, the value represents the operation that is required to make all datafiles in the tablespace consistent by using the FINISH clause of the ALTER TABLESPACE ENCRYPTION statement. See *Oracle Database Advanced Security Guide* for information about changing the encryption state of a tablespace.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$DATABASE_KEY_INFO"

8.201 V$ENCRYPTION_KEYS

V$ENCRYPTION_KEYS displays master key description attributes.

Column	Datatype	Description
KEY_ID	VARCHAR2(78)	Master key identifier
HEX_MKID	VARCHAR2(78)	Master key identifier, in hex format
TAG	VARCHAR2(4000)	Associated user-defined Information with the master key
CREATION_TIME	TIMESTAMP(6) WITH TIME ZONE	Time that the master key was created
ACTIVATION_TIME	TIMESTAMP(6) WITH TIME ZONE	Time that the master key was put into use
CREATOR	VARCHAR2(128)	User that created the master key
CREATOR_ID	NUMBER	User ID that created the master key
USER	VARCHAR2(128)	User that activated the master key
USER_ID	NUMBER	User ID that activated the master key
KEY_USE	VARCHAR2(10)	Indicates whether the master key is used for TDE operations in a PDB or not
KEYSTORE_TYPE	VARCHAR2(17)	Type of keystore in which the master key is stored: • OKV - Oracle Key Vault • SOFTWARE KEYSTORE • UNDEFINED - This value is shown if the database has no information about the type of keystore where the master key resides

Column	Datatype	Description
ORIGIN	VARCHAR2(41)	Provides information about the origin of the master key: • LOCAL - The master key was created locally in this database • IMPORTED - The master key was imported from another database • IMPORTED BUT KEY METADATA CREATED LOCALLY - The master key was imported from another database, but the key metadata was created locally due to activation • UNKNOWN BUT KEY METADATA CREATED LOCALLY - It is unknown whether the master key was imported from another database or created locally, but the key metadata was created locally due to activation • UNDEFINED - The status of the master key is unknown
BACKED_UP	VARCHAR2(9)	Indicates whether the key has been backed up or not
CREATOR_DBNAME	VARCHAR2(128)	Database that created the key
CREATOR_DBID	NUMBER	Database ID where the key was created
CREATOR_INSTANCE_NAME	VARCHAR2(30)	Instance name of the instance where the key was created
CREATOR_INSTANCE_NUMBER	NUMBER	Instance number of the instance where the key was created
CREATOR_INSTANCE_SERIAL	NUMBER	Serial number of the instance where the key was created
CREATOR_PDBNAME	VARCHAR2(128)	PDB where the key was created
CREATOR_PDBID	NUMBER	PDB ID where the key was created
CREATOR_PDBUID	NUMBER	PDB UID where the key was created
CREATOR_PDBGUID	RAW(16)	PDB GUID where the key was created
ACTIVATING_DBNAME	VARCHAR2(128)	Database that activated the key
ACTIVATING_DBID	NUMBER	Database ID where the key was activated
ACTIVATING_INSTANCE_NAME	VARCHAR2(30)	Instance name of the instance where the key was activated
ACTIVATING_INSTANCE_NUMBER	NUMBER	Instance number of the instance where the key was activated
ACTIVATING_INSTANCE_SERIAL	NUMBER	Serial number of the instance where the key was activated
ACTIVATING_PDBNAME	VARCHAR2(128)	PDB where the key was activated
ACTIVATING_PDBID	NUMBER	PDB ID where the key was activated
ACTIVATING_PDBUID	NUMBER	PDB UID where the key was activated
ACTIVATING_PDBGUID	RAW(16)	PDB GUID where the key was activated
ALGORITHM	VARCHAR2(9)	Master key encryption algorithm
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Advanced Security Guide* for information about keystore management

8.202 V$ENCRYPTION_WALLET

V$ENCRYPTION_WALLET displays information on the status of the wallet and the wallet location for Transparent Data Encryption. In a multitenant container database (CDB), this view displays information on the wallets for all pluggable database (PDBs) when queried from CDB$ROOT. When queried from a PDB, this view only displays wallet details of that PDB.

Column	Datatype	Description
WRL_TYPE	VARCHAR2(20)	Type of the wallet resource locator (for example, FILE)
WRL_PARAMETER	VARCHAR2(4000)	Parameter of the wallet resource locator (for example, absolute directory location of the wallet or keystore, if WRL_TYPE = FILE)
STATUS	VARCHAR2(30)	Status of the wallet. Possible values: • CLOSED: The wallet is closed • NOT_AVAILABLE: The wallet is not available in the location specified by the WALLET_ROOT initialization parameter • OPEN: The wallet is open • OPEN_NO_MASTER_KEY: The wallet is open, but no master key is set • OPEN_UNKNOWN_MASTER_KEY_STATUS: The wallet is open, but the database could not determine whether the master key is set. This situation can occur when the database is in the mounted state and cannot check if the master key for a hardware keystore is set because the data dictionary is not available. • UNDEFINED: The database could not determine the status of the wallet
WALLET_TYPE	VARCHAR2(20)	Displays the type of keystore being used, FILE or OKV If the keystore was created with the mkstore utility, then the WALLET_TYPE is UNKNOWN. Oracle recommends that you create keystores with the ADMINISTER KEY MANAGEMENT statement.

Column	Datatype	Description
WALLET_ORDER	VARCHAR2(9)	Possible values: • SINGLE - When only a single wallet is configured, this is the value in the column. • PRIMARY - When more than one wallet is configured, this value indicates that the wallet is primary (holds the current master key). • SECONDARY - When more than one wallet is configured, this value indicates that the wallet is secondary (holds old keys). The lookup of master keys happens in the primary keystore first, and then in the secondary keystore, if required. If there is only one type of keystore being used, then SINGLE will appear. If both types are used, then the value in this column shows the order in which each keystore will be looked up.
KEYSTORE_MODE	VARCHAR2(8)	Displays the keystore mode: • NONE: This value is seen when this column is queried from the CDB$ROOT, or when the database is a non-CDB. The keystore mode does not apply in these cases. • UNITED: The PDB is configured to use the wallet of the CDB$ROOT. To open the wallet in this configuration, the password of the wallet of the CDB$ROOT must be used. • ISOLATED: The PDB is configured to use its own wallet. To open the wallet in this configuration, the password of the isolated wallet must be used.
FULLY_BACKED_UP	VARCHAR2(9)	Indicates whether all the keys in the keystore have been backed up
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "TDE_CONFIGURATION"
- "WALLET_ROOT"
- *Oracle Database Advanced Security Guide* for information about creating user-defined master encryption keys
- *Oracle Database Advanced Security Guide* for information about opening hardware keystores

8.203 V$ENQUEUE_LOCK

V$ENQUEUE_LOCK displays all locks owned by enqueue state objects. The columns in this view are identical to the columns in V$LOCK.

> **See Also:**
>
> "V$LOCK"

Column	Datatype	Description
ADDR	RAW(4 | 8)	Address of lock state object
KADDR	RAW(4 | 8)	Address of lock
SID	NUMBER	Identifier for session holding or acquiring the lock
TYPE	VARCHAR2(2)	Type of lock. Lists user and system types that can have locks.
ID1	NUMBER	Lock identifier #1 (depends on type)
ID2	NUMBER	Lock identifier #2 (depends on type)
LMODE	NUMBER	Lock mode in which the session holds the lock: • 0 - none • 1 - null (NULL) • 2 - row-S (SS) • 3 - row-X (SX) • 4 - share (S) • 5 - S/Row-X (SSX) • 6 - exclusive (X)
REQUEST	NUMBER	Lock mode in which the process requests the lock: • 0 - none • 1 - null (NULL) • 2 - row-S (SS) • 3 - row-X (SX) • 4 - share (S) • 5 - S/Row-X (SSX) • 6 - exclusive (X)
CTIME	NUMBER	Time since current mode was granted
BLOCK	NUMBER	The lock is blocking another lock
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.204 V$ENQUEUE_STAT

V$ENQUEUE_STAT displays statistics on the number of enqueue (lock) requests for each type of lock.

Column	Datatype	Description
INST_ID	NUMBER	ID of the instance
EQ_TYPE	VARCHAR2(2)	Type of enqueue requested
TOTAL_REQ#	NUMBER	Total number of enqueue requests or enqueue conversions for this type of enqueue
TOTAL_WAIT#	NUMBER	Total number of times an enqueue request or conversion resulted in a wait
SUCC_REQ#	NUMBER	Number of times an enqueue request or conversion was granted
FAILED_REQ#	NUMBER	Number of times an enqueue request or conversion failed
CUM_WAIT_TIME	NUMBER	Total amount of time (in milliseconds) spent waiting for the enqueue or enqueue conversion
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.205 V$ENQUEUE_STATISTICS

V$ENQUEUE_STATISTICS displays statistics on the number of enqueue (lock) requests for each type of lock.

V$ENQUEUE_STATISTICS encompasses V$ENQUEUE_STAT and gives more detailed information (several rows for same enqueues with different reasons).

Column	Datatype	Description
EQ_NAME	VARCHAR2(64)	Name of the enqueue request
EQ_TYPE	VARCHAR2(2)	Type of enqueue requested
REQ_REASON	VARCHAR2(64)	Reason for the enqueue request
TOTAL_REQ#	NUMBER	Total number of enqueue requests or enqueue conversions for this type of enqueue
TOTAL_WAIT#	NUMBER	Total number of times an enqueue request or conversion resulted in a wait
SUCC_REQ#	NUMBER	Number of times an enqueue request or conversion was granted
FAILED_REQ#	NUMBER	Number of times an enqueue request or conversion failed
CUM_WAIT_TIME	NUMBER	Total amount of time (in milliseconds) spent waiting for the enqueue or enqueue conversion
REQ_DESCRIPTION	VARCHAR2(4000)	Description of the enqueue request

Column	Datatype	Description
EVENT#	NUMBER	Event number
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$ENQUEUE_STAT"

8.206 V$EQ_CACHED_PARTITIONS

V$EQ_CACHED_PARTITIONS describes all cached Transactional Event Queue (TxEventQ) event stream partitions.

Column	Datatype	Description
QUEUE	NUMBER	Queue ID
EVENT_STREAM_ID	NUMBER	Event stream ID
PRIORITY	NUMBER	Priority of the event stream partition
EVENT_STREAM_PARTITION_ID	NUMBER	Event stream partition ID
OPT_STATE	VARCHAR2(19)	Current message cache optimizer state of the event stream partition. Possible values: • EMPTY • READY • EVICTION_PROGRESS • EVICTED • UNEVICTION_PROGRESS • PREFETCH_PROGRESS • NEED_RELOAD • RELOAD_PROGRESS • NA: Error in the message cache optimizer state of the event stream partition
OPT_TIME	TIMESTAMP(3) WITH TIME ZONE	The predicted absolute time when the event stream partition could be accessed in future

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Transactional Event Queues and Advanced Queuing

8.207 V$EQ_CROSS_INSTANCE_JOBS

V$EQ_CROSS_INSTANCE_JOBS describes Transactional Event Queue (TxEventQ) cross-instance jobs.

Each job forwards messages for an event stream from a source instance to a destination instance for a set of subscribers of a TxEventQ.

Column	Datatype	Description
JOB_ID	NUMBER	Job ID within this coordinator
SCHEMA_NAME	VARCHAR2(128)	Source schema of the job
QUEUE_NAME	VARCHAR2(128)	Source queue name of the job
EVENT_STREAM_ID	NUMBER	Source event stream ID
START_EVENT_STREAM_PARTITION_ID	NUMBER	Start event stream partition ID of the job
DESTINATION_INSTANCE_ID	NUMBER	Destination instance of the job
COORDINATOR_ID	NUMBER	Index of the coordinator serving the job
DEST_SERVER_PROCESS_ID	NUMBER	Process ID of the destination server
JOB_STATE	VARCHAR2(28)	State of the job. Possible values: • REQUESTED • RUNNING • STOPPED • PAUSED • CRASHED • INACTIVE
FLOW_CONTROL	NUMBER	Indicates whether the job is flow controlled. Possible values: • 0 - The job is not flow controlled • 1 - The job is flow controlled
MSGS_SENT	NUMBER	Number of messages sent during the job

Column	Datatype	Description
BYTES_SENT	NUMBER	Number of bytes sent during the job
ACK_LATENCY	NUMBER	Latency for receiving ACK for the job
JOB_TYPE	VARCHAR2(26)	Job type. Possible values: • CROSS_STREAM: This job type is responsible for forwarding an event stream from its owner instance to a destination dequeue instance for all subscribers performing dequeue from that event stream at the destination dequeue instance. • DEQUEUE_AFFINITY_TO_REMOTE: This job type is responsible for switching a subscriber's dequeue affinity from an event stream's owner instance to a remote dequeue instance. • DEQUEUE_AFFINITY_TO_LOCAL: This job type is responsible for switching back a subscriber's dequeue affinity from a remote dequeue instance to an event stream's owner instance.
PRIORITY0_CROSS_LWM	NUMBER	ID of last priority 0 event stream partition received at DESTINATION_INSTANCE_ID
PRIORITY1_CROSS_LWM	NUMBER	ID of last priority 1 event stream partition received at DESTINATION_INSTANCE_ID
PRIORITY2_CROSS_LWM	NUMBER	ID of last priority 2 event stream partition received at DESTINATION_INSTANCE_ID
PRIORITY3_CROSS_LWM	NUMBER	ID of last priority 3 event stream partition received at DESTINATION_INSTANCE_ID
PRIORITY4_CROSS_LWM	NUMBER	ID of last priority 4 event stream partition received at DESTINATION_INSTANCE_ID
PRIORITY5_CROSS_LWM	NUMBER	ID of last priority 5 event stream partition received at DESTINATION_INSTANCE_ID
PRIORITY6_CROSS_LWM	NUMBER	ID of last priority 6 event stream partition received at DESTINATION_INSTANCE_ID
PRIORITY7_CROSS_LWM	NUMBER	ID of last priority 7 event stream partition received at DESTINATION_INSTANCE_ID
PRIORITY8_CROSS_LWM	NUMBER	ID of last priority 8 event stream partition received at DESTINATION_INSTANCE_ID
PRIORITY9_CROSS_LWM	NUMBER	ID of last priority 9 event stream partition received at DESTINATION_INSTANCE_ID
JOB_START_TIME	TIMESTAMP(3) WITH TIME ZONE	Start time of this job
SUBSCRIBER_ID	NUMBER	ID of the subscriber whose affinity is being switched for the DEQUEUE_AFFINITY_TO_REMOTE and DEQUEUE_AFFINITY_TO_LOCAL job types
SUBSCRIBER_NAME	VARCHAR2(512)	Name of subscriber whose affinity is being switched for the DEQUEUE_AFFINITY_TO_REMOTE and DEQUEUE_AFFINITY_TO_LOCAL job types. This column is NULL for the CROSS_STREAM job type.
OWNER_INSTANCE_ID	NUMBER	ID of the instance that owns the event stream
QUEUE_ID	NUMBER	Queue ID

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Transactional Event Queues and Advanced Queuing

8.208 V$EQ_INACTIVE_PARTITIONS

V$EQ_INACTIVE_PARTITIONS describes all inactive Transactional Event Queue (TxEventQ) event stream partitions.

Column	Datatype	Description
QUEUE	NUMBER	Queue ID
EVENT_STREAM_ID	NUMBER	Event stream ID
PRIORITY	NUMBER	Priority of the event stream partition
EVENT_STREAM_PARTITION_ID	NUMBER	Event stream partition ID
OPT_STATE	VARCHAR2(19)	Current message cache optimizer state of the event stream partition. Possible values: • EMPTY • CACHED • EVICTION_PROGRESS • EVICTED • UNEVICTION_PROGRESS • PREFETCH_PROGRESS • NA: Error in the message cache optimizer state of the event stream partition
OPT_TIME	TIMESTAMP(3) WITH TIME ZONE	The predicted absolute time when the event stream partition could be accessed in future
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Transactional Event Queues and Advanced Queuing

8.209 V$EQ_MESSAGE_CACHE

`V$EQ_MESSAGE_CACHE` provides performance statistics of the message cache for Transactional Event Queues (TxEventQs) at the event stream partition level in the instance.

Column	Datatype	Description
`QUEUE_ID`	`NUMBER`	Queue ID
`EVENT_STREAM_ID`	`NUMBER`	Event stream ID
`PRIORITY`	`NUMBER`	Priority of the event stream partition for dequeue, range `0` - `9`
`EVENT_STREAM_PARTITION_ID`	`NUMBER`	Event stream partition ID
`PARTITION_ID`	`NUMBER`	Queue partition ID
`MAX_MSGS`	`NUMBER`	Maximum number of messages for the event stream partition
`ENQUEUED_MSGS`	`NUMBER`	Number of messages enqueued for the event stream partition
`MSGS_MADE_EXPIRED`	`NUMBER`	Number of messages made expired
`CHUNK_SIZE`	`NUMBER`	The size of the memory chunk for storing messages
`NUM_CHUNKS`	`NUMBER`	Number of chunks for the event stream partition
`NUM_FREE_CHUNKS`	`NUMBER`	Number of free chunks for the event stream partition
`USED_MEMORY_SIZE`	`NUMBER`	Total estimated size of memory in use (in bytes) for the event stream partition
`STATE`	`VARCHAR2(13)`	Event stream partition state. Possible values: • `CACHED` (in memory) • `UNCACHED` (on disk) • `UNCACHED_FREE` • `CACHED_FREE` • `UNKNOWN`
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Transactional Event Queues and Advanced Queuing

8.210 V$EQ_MESSAGE_CACHE_ADVICE

`V$EQ_MESSAGE_CACHE_ADVICE` shows simulated metrics for a range of potential message cache sizes for Transactional Event Queues (TxEventQs). This view assists in cache sizing by providing information in the form of metrics as described below.

Column	Datatype	Description
SIZE_FOR_ESTIMATE	NUMBER	Cache size for simulation (in megabytes)
SIZE_FACTOR	NUMBER	Size factor with respect to the current cache size
ESTD_SIZE_TYPE	VARCHAR2(9)	Possible values: • MINIMUM: This cache size is required to have all dequeues in-memory (no uncached). • CURRENT: This is the current size of the message cache. • MAXIMUM: This cache size is required to have zero evictions. • NULL: This is the value in all other cases.
ESTD_CACHED_PARTITIONS	NUMBER	Estimated number of cached event stream partitions for this size
ESTD_UNCACHED_PARTITIONS	NUMBER	Estimated number of uncached event stream partitions for this size
ESTD_EVICTIONS	NUMBER	Estimated number of event stream partitions evicted for this size
ESTD_EVICTION_RATE	NUMBER	Estimated number of event stream partitions getting evicted per minute
ESTD_FG_UNEVICTIONS	NUMBER	Estimated number of event stream partitions unevicted by foreground processes
ESTD_FG_UNEVICTION_RATE	NUMBER	Estimated number of event stream partitions getting unevicted by foreground processes
ESTD_BG_UNEVICTIONS	NUMBER	Estimated number of event stream partitions unevicted by background processes
ESTD_BG_UNEVICTION_RATE	NUMBER	Estimated number of event stream partitions getting unevicted by background processes
ESTD_BG_PROCESSES	NUMBER	Estimated number of background processes required for this size
TOTAL_ENQUEUE_RATE	NUMBER	Simulated number of messages being enqueued per second
TOTAL_DEQUEUE_RATE	NUMBER	Simulated number of messages being dequeued per second
AVG_PARTITION_SIZE	NUMBER	Simulated average number of messages per cached event stream partitions
AVG_PARTITION_MEMORY	NUMBER	Simulated average memory per cached event stream partition (in megabytes)
AVG_EVICTION_TIME	NUMBER	Simulated average time to evict a cached event stream partition (in milliseconds)
AVG_UNEVICTION_TIME	NUMBER	Simulated average time to unevict a cached event stream partition (in milliseconds)
FLAGS	NUMBER	Reserved for internal use

Column	Datatype	Description
SIMULATION_TIME	NUMBER	Amount of time that was simulated for (in minutes)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Transactional Event Queues and Advanced Queuing

8.211 V$EQ_MESSAGE_CACHE_STAT

V$EQ_MESSAGE_CACHE_STAT displays statistics about memory management for Transactional Event Queues (TxEventQs) in the Streams pool within the System Global Area (SGA). TxEventQs use the Streams pool in units of event queue partitions. Thus, columns of this view shows statistics at the event queue partition level. This view shows statistics across all TxEventQs.

Column	Datatype	Description
NUM_EVICTED	NUMBER	Number of evicted event queue partitions across all TxEventQs
NUM_PREFETCHED	NUMBER	Number of event queue partitions pre-fetched by an AQ background process
NUM_UNEVICTION	NUMBER	Number of event queue partitions unevicted by a foreground process, such as the dequeue process
NUM_UNCACHED	NUMBER	Number of event queue partitions stored as uncached
NUM_TRACKED	NUMBER	Number of event queue partitions which are actively tracking dequeue rates
NUM_CACHED	NUMBER	Number of event queue partitions stored as cached
MAX_SUBSH_SIZE	NUMBER	Maximum event queue partition size seen till now, in terms of number of messages per event queue partition
MIN_SUBSH_SIZE	NUMBER	Minimum event queue partition size seen till now, in terms of number of messages per event queue partition
MEAN_SUBSH_SIZE	NUMBER	Mean event queue partition size seen till now, in terms of number of messages per event queue partition
AVG_EVICTION_RATE	NUMBER	Average number of event queue partitions evicted per second
AVG_LOAD_RATE	NUMBER	Average number of event queue partitions pre-fetched or unevicted per second
AVG_EVICTION_TIME	NUMBER	Average time taken to evict one event queue partition (in milliseconds)

Column	Datatype	Description
AVG_LOAD_TIME	NUMBER	Average time taken to un-evict one event queue partition (in milliseconds)
AVG_MISS_RATIO	NUMBER	Average ratio of number of foreground un-evictions versus background pre-fetch
AVG_THRASH_RATIO	NUMBER	Average ratio of number of event queue partitions pre-fetched by background without dequeue attempt versus total number of event queue partitions prefetched
MANDATORY_AFF_SWITCH_ATTEMPTS	NUMBER	An affinity switch is a change in dequeue instance for a TxEventQ-subscriber pair. A mandatory affinity switch is when there are local enqueues in the queue at the instance but no local dequeues present, so the dequeue affinity is switched to another instance for that TxEventQ-subscriber pair. This column shows the number of times mandatory affinity switches were attempted across all instances. Populated at the smallest instance ID only.
OPTIONAL_AFF_SWITCH_ATTEMPTS	NUMBER	Optional affinity switches are affinity switches that are not mandatory. Optional affinity switches are done for global load balancing across the Oracle Real Application Clusters (Oracle RAC) database. This column shows the number of times optional affinity switches were attempted across all instances. Populated at the smallest instance ID only.
MIN_EVICT_PERCENT	NUMBER	Percentage of `streams_pool` memory beyond which event queue partition eviction is triggered
LAST_AVG_CACHED_HORIZON	NUMBER	Last average number of cached event queue partitions seen in TxEventQ memory manager horizon
LAST_AVG_MEMORY_HORIZON	NUMBER	Last average memory of cached event queue partitions seen in TxEventQ memory manager horizon
LAST_AVG_SUBSHARD_HORIZON	NUMBER	Last average number of event queue partitions seen in TxEventQ memory manager horizon
LAST_LEEWAY_SHIFT	NUMBER	Internal leeway for memory threshold
AVG_OPTTIME_DRIFT	NUMBER	Average drift of opt_time for all event queue partitions. A drift is defined as a difference between opt_time as set on an event queue partition and the actual time at which an event queue partition is first dequeueed after prefetch/uneviction.
NUM_THRESHOLD_DRIFT	NUMBER	Number of times drift value has gone over threshold time. A typical threshold time can be horizon_time/2.
MAX_OPT_TIME_DRIFT	NUMBER	Maximum drift until now
MIN_OPT_TIME_DRIFT	NUMBER	Minimum drift until now
AVG_OPT_TIME_ERROR	NUMBER	An opt_time error occurs when a cached event queue partition is unevicted by a foreground process (instead of being prefetched by the AQ background). Thus, opt_time error is the difference between the actual opt_time set for an event queue partition and the absolute time at which foreground unevicts the same event queue partition. This column represents the average time of this error.
MAX_OPT_TIME_ERROR	NUMBER	Maximum opt_time error
MIN_OPT_TIME_ERROR	NUMBER	Minimum opt_time error
NUM_FG_RELOADED	NUMBER	Number of event stream partitions reloaded from disk into message cache by foreground processes

Column	Datatype	Description
NUM_PRERELOADED	NUMBER	Number of event stream partitions reloaded from disk into message cache in advance by background processes
AVG_RELOAD_TIME	NUMBER	Average time to reload an event stream partition from disk into message cache (in milliseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database Advanced Queuing User's Guide for more information about Oracle Transactional Event Queues and Advanced Queuing

8.212 V$EQ_NONDUR_SUBSCRIBER

V$EQ_NONDUR_SUBSCRIBER provides information about the non-durable subscriptions on Transactional Event Queues (TxEventQs).

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue ID
SUBSCRIBER_ID	NUMBER	ID of the non-durable subscriber
SUBSCRIBER_NAME	VARCHAR2(128)	Subscriber name
RULE_CONDITION	VARCHAR2(4000)	Rule condition of the subscriber
TRANSFORMATION_OWNER	VARCHAR2(128)	Owner of the transformation (for JMS queues)
TRANSFORMATION_NAME	VARCHAR2(128)	Name of the transformation (for JMS queues)
CREATION_TIME	TIMESTAMP(1) WITH TIME ZONE	Non-durable subscriber creation time
FLAGS	NUMBER	Property of the subscriber. Possible values: • 0x0001 – Persistent subscriber • 0x0002 – Buffered subscriber • 0x0004 – JMS subscriber • 0x0008 – Rule-based subscriber • 0x0010 – Subscriber has transformation • 0x0020 – Notification-only non-durable subscriber subscriber
SUBSCRIBER_TYPE	NUMBER	Type of subscriber. Possible values: • 1 – JMS non-durable subscriber • 2 – Service layer dummy non-durable subscriber • 3 – Notification-only non-durable subscriber

Column	Datatype	Description
BITPOS	NUMBER	Position of subscriber in subscriber bitmap
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Transactional Event Queues and Advanced Queuing

8.213 V$EQ_NONDUR_SUBSCRIBER_LWM

V$EQ_NONDUR_SUBSCRIBER_LWM projects the low watermarks (LWMs) of non-durable subscribers in a Transactional Event Queue (TxEventQ). The LWM of a non-durable subscriber is a combination of event stream, priority, and LWM (event queue partition).

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue ID
SUBSCRIBER_ID	NUMBER	ID of the non-durable subscriber
EVENT_STREAM_ID	NUMBER	Event stream ID
PRIORITY	NUMBER	Priority of the event stream
LWM	NUMBER	Lower watermark (in an event stream partition) of the non-durable subscriber
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Transactional Event Queues and Advanced Queuing

8.214 V$EQ_PARTITION_STATS

V$EQ_PARTITION_STATS displays usage statistics for the Transactional Event Queue (TxEventQ) queue partition cache and the dequeue log partition cache.

Column	Datatype	Description
INST_ID	NUMBER	Current instance ID
QUEUE_ID	NUMBER	Queue ID
QUEUE_TABLE_ID	NUMBER	Queue table object ID
QUEUE_SCHEMA	VARCHAR2(128)	Queue schema name
QUEUE_NAME	VARCHAR2(128)	Queue name
PT_TUNED_SIZ_QT	NUMBER	Current tuned size of the queue partition cache, expressed in number of partition cache elements
PT_CACHED_PTNS_QT	NUMBER	Current number of cached partitions in the queue partition cache
PT_OVER_CACHED_PTNS_QT	NUMBER	Current number of over-cached partitions in the queue partition cache, that is, the number of cached partitions whose partition cache elements exceed the current tuned size of the queue partition cache
PT_TOTAL_UPTUNE_QT	NUMBER	Total amount of space added to the queue partition cache due to tune-ups, since the cache was initialized, expressed in number of partition cache elements
PT_NO_OF_UPTUNES_QT	NUMBER	Total number of times a tune-up was triggered on the queue partition cache, since the cache was initialized
PT_TOTAL_DOWNTUNE_QT	NUMBER	Total amount of space removed from the queue partition cache due to tune-downs, since the cache was initialized, expressed in number of partition cache elements
PT_NO_OF_DOWNTUNES_QT	NUMBER	Total number of times a tune-down was triggered on the queue partition cache, since the cache was initialized
PT_CACHE_MISS_QT	NUMBER	Total number of cache misses during partition lookups on the queue partition cache
PT_CACHE_HIT_QT	NUMBER	Total number of cache hits during partition lookups on the queue partition cache
PT_TOTAL_CACH_GET_QT	NUMBER	Total number of successful fetches from the queue partition cache
PT_TOTAL_CACH_PUT_QT	NUMBER	Total number of caching operations that occurred on the queue partition cache
PT_UNBOUNDINGS_QT	NUMBER	Total number of times queue partitions were unbounded
PT_TUNED_SIZ_DQ	NUMBER	Current tuned size of the dequeue log partition cache, expressed in number of partition cache elements
PT_CACHED_PTNS_DQ	NUMBER	Current number of cached partitions in the dequeue log partition cache
PT_OVER_CACHED_PTNS_DQ	NUMBER	Current number of over-cached partitions in the dequeue log partition cache, that is, the number of cached dequeue log partitions whose partition cache elements exceed the current tuned size of the dequeue log partition cache
PT_TOTAL_UPTUNE_DQ	NUMBER	Total amount of space added to the dequeue log partition cache due to tune-ups, since the cache was initialized, expressed in number of partition cache elements

Column	Datatype	Description
PT_NO_OF_UPTUNES_DQ	NUMBER	Total number of times a tune-up was triggered on the dequeue log partition cache, since the cache was initialized
PT_TOTAL_DOWNTUNE_DQ	NUMBER	Total amount of space removed from the dequeue log partition cache due to tune-downs, since the cache was initialized, expressed in number of partition cache elements
PT_NO_OF_DOWNTUNES_DQ	NUMBER	Total number of times a tune-down was triggered on the dequeue log partition cache, since the cache was initialized
PT_CACHE_MISS_DQ	NUMBER	Total number of cache misses during partition lookups on the dequeue log partition cache
PT_CACHE_HIT_DQ	NUMBER	Total number of cache hits during partition lookups on the dequeue log partition cache
PT_TOTAL_CACH_GET_DQ	NUMBER	Total number of successful fetches from the dequeue log partition cache
PT_TOTAL_CACH_PUT_DQ	NUMBER	Total number of caching operations that occurred on the dequeue log partition cache
PT_UNBOUNDINGS_DQ	NUMBER	Total number of times dequeue log partitions were unbounded
ADD_PARTITION_FG_QT	NUMBER	Total number of queue partitions created inline during foreground AQ enqueue operations
ADD_PARTITION_BG_QT	NUMBER	Total number of queue partitions created asynchronously by the AQ partitioning background process
ADD_PARTITION_FG_DQLOG	NUMBER	Total number of dequeue log partitions created inline during foreground AQ dequeue operations
ADD_PARTITION_BG_DQLOG	NUMBER	Total number of dequeue log partitions created asynchronously by the AQ partitioning background process
TRUNC_PARTITION_QT	NUMBER	Total number of truncated and recycled queue partitions
TRUNC_PARTITION_DQLOG	NUMBER	Total number of truncated and recycled dequeue log partitions
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database Advanced Queuing User's Guide for more information about Oracle Transactional Event Queues and Advanced Queuing

8.215 V$EQ_REMOTE_DEQUEUE_AFFINITY

V$EQ_REMOTE_DEQUEUE_AFFINITY lists the for Transactional Event Queue (TxEventQ) dequeue affinity instance of the subscribers not dequeuing locally from the event streams's owner instance. Cross-instance message forwarding is used for these subscribers.

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue ID
EVENT_STREAM_ID	NUMBER	Event stream ID, which is being forwarded from SOURCE_INSTANCE to INST_ID for the subscriber
SOURCE_INSTANCE_ID	NUMBER	Owner instance ID from which the event stream is being forwarded
SUBSCRIBER_ID	NUMBER	Subscriber ID
QUEUE_SCHEMA	VARCHAR2(128)	Owner of the queue
QUEUE_NAME	VARCHAR2(128)	Queue name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database Advanced Queuing User's Guide for more information about Oracle Transactional Event Queues and Advanced Queuing

8.216 V$EQ_SUBSCRIBER_LOAD

V$EQ_SUBSCRIBER_LOAD describes the load of all subscribers of Transactional Event Queue (TxEventQ) event streams in terms of latency at every instance in an Oracle RAC environment.

Latency denotes the predicted amount of time (in seconds) required from the current time to drain all the messages for that subscriber at each respective instance. The latency calculation considers past enqueue/dequeue rates and future enqueue/dequeue rates based on history.

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue ID
QUEUE_SCHEMA	VARCHAR2(128)	Queue schema
QUEUE_NAME	VARCHAR2(128)	Queue name
SUBSCRIBER_ID	NUMBER	Subscriber ID

Column	Datatype	Description
SUBSCRIBER_NAME	VARCHAR2(128)	Subscriber name
LATENCY_STATE	VARCHAR2(8)	Latency state. Possible values: • FINITE - The subscriber will be able to dequeue all the messages in a finite amount of time • INFINITE - The subscriber's dequeue rate may not catch up to the enqueue rate • UNKNOWN - Latency is not yet known
LATENCY	NUMBER	Latency (in seconds). Valid only when LATENCY_STATE is FINITE.
DEQUEUE_REQUESTS	NUMBER	Approximate number of dequeue requests noted recently
ACTIVE_EVENT_STREAM_ID	NUMBER	Number of event streams that have messages for this subscriber
ACTIVE_LISTENER	VARCHAR2(5)	Indicates whether the subscriber is actively listening at this instance for messages (TRUE) or not (FALSE)
DEQUEUE_SESSIONS	NUMBER	Displays the number of active dequeue sessions for this subscriber
FLAGS	NUMBER	For internal use only
MANDATORY_AFF_SWITCHES	NUMBER	An affinity switch is a change in the dequeue instance for an event stream-subscriber pair. A mandatory affinity switch is when there are local enqueues in the queue at the instance but no local dequeues present, so the dequeue affinity is switched to another instance for that event stream-subscriber pair. This column shows the number of times mandatory affinity switches were needed from this instance to another for this subscriber.
OPTIONAL_AFF_SWITCHES	NUMBER	Optional affinity switches are affinity switches that are not mandatory. Optional affinity switches are done for global load balancing across the Oracle Real Application Clusters (Oracle RAC) database. This column shows the number of times optional affinity switches were needed from this instance to another for this subscriber.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database Advanced Queuing User's Guide for more information about Oracle Transactional Event Queues and Advanced Queuing

8.217 V$EQ_SUBSCRIBER_STAT

V$EQ_SUBSCRIBER_STAT displays basic statistical information about the subscribers of Transactional Event Queue (TxEventQ) event streams. There is one row per queue per event stream per subscriber.

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue identifier
SUBSCRIBER_ID	NUMBER	Subscriber identifier
EVENT_STREAM_ID	NUMBER	Event stream identifier
PRIORITY	NUMBER	Priority value of the event stream
MSG_SN	NUMBER	Message serial number
DEQUEUE_PARTITION_ID	NUMBER	Last known dequeue position in this event stream
ENQUEUED_MSGS	NUMBER	Number of enqueued messages
DEQUEUED_MSGS	NUMBER	Number of dequeued messages
ELAPSED_DEQUEUE_TIME	NUMBER	Amount of time spent performing dequeues (in seconds)
CPU_DEQUEUE_TIME	NUMBER	Actual amount of CPU time spent performing dequeues (in seconds)
DEQUEUE_RATE	NUMBER	Number of messages dequeued per second
DEQUEUE_POSITION	RAW(16)	Message ID at the dequeue position of the subscriber in this event stream A NULL value indicates that either the event stream is empty or no dequeues have been done on this event stream.
TIME_SINCE_LAST_DEQUEUE	NUMBER	Time since last dequeue activity (in seconds)
ESTD_TIME_TO_DRAIN	NUMBER	Estimated amount of time to drain the event stream (in seconds) with current enqueue and dequeue rates. Null, if the enqueue rate is greater than the dequeue rate.
ESTD_TIME_TO_DRAIN_NO_ENQ	NUMBER	Estimated amount of time to drain the event stream (in seconds) with no new enqueues
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database Advanced Queuing User's Guide for more information about Oracle Transactional Event Queues and Advanced Queuing

8.218 V$EQ_UNCACHED_PARTITIONS

V$EQ_UNCACHED_PARTITIONS describes all uncached Transactional Event Queue (TxEventQ) event stream partitions.

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue ID
EVENT_STREAM_ID	NUMBER	Event stream ID
PRIORITY	NUMBER	Priority of the event stream partition
EVENT_STREAM_PARTITION_ID	NUMBER	Event stream partition ID
OPT_STATE	VARCHAR2(19)	Current message cache optimizer state of the event stream partition. Possible values: • EMPTY • READY • EVICTION_PROGRESS • EVICTED • UNEVICTION_PROGRESS • PREFETCH_PROGRESS • NEED_RELOAD • RELOAD_PROGRESS • NA: Error in the message cache optimizer state of the event stream partition
OPT_TIME	TIMESTAMP(3) WITH TIME ZONE	The predicted absolute time when the event stream partition could be accessed in future
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Advanced Queuing User's Guide* for more information about Oracle Transactional Event Queues and Advanced Queuing

8.219 V$EVENT_HISTOGRAM

V$EVENT_HISTOGRAM displays a histogram of the number of waits, the maximum wait, and total wait time on an event basis, in milliseconds. The histogram has buckets of time intervals from < 1 ms, < 2 ms, < 4 ms, < 8 ms, ... < 2^{21} ms, < 2^{22} ms, and >= 2^{22} ms.

The histogram will not be filled unless the TIMED_STATISTICS initialization parameter is set to true.

Column	Datatype	Description
EVENT#	NUMBER	Event number
EVENT	VARCHAR2(64)	Name of the event
WAIT_TIME_MILLI	NUMBER	Amount of time the bucket represents (in milliseconds). If the duration = *num*, then this column represents waits of duration < *num* that are not included in any smaller bucket.
WAIT_COUNT	NUMBER	Number of waits of the duration belonging to the bucket of the histogram
LAST_UPDATE_TIME	VARCHAR2(64)	Indicates the last time the bucket was updated (the ending timestamp of the last wait falling into the bucket's duration)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "TIMED_STATISTICS"

8.220 V$EVENT_HISTOGRAM_MICRO

V$EVENT_HISTOGRAM_MICRO displays a histogram of the number of waits, the maximum wait, and total wait time on an event basis, in microseconds. The histogram has buckets of time intervals from < 1 us, < 2 us, < 4 us, < 8 us, ... < 2^{31} us, < 2^{32} us, and >= 2^{32} us.

The histogram will not be filled unless the TIMED_STATISTICS initialization parameter is set to true.

Column	Datatype	Description
EVENT#	NUMBER	Event number
EVENT	VARCHAR2(64)	Name of the event
WAIT_TIME_FORMAT	VARCHAR2(30)	A human readable time string which is converted from WAIT_TIME_MICRO. When WAIT_TIME_MICRO < 1 millisecond, WAIT_TIME_FORMAT is shown in microseconds. When WAIT_TIME_MICRO < 1 second, WAIT_TIME_FORMAT is shown in milliseconds. When WAIT_TIME_MICRO < 1 minute, WAIT_TIME_FORMAT is shown in seconds. When WAIT_TIME_MICRO > 1 minute, WAIT_TIME_FORMAT is shown in minutes and seconds.
WAIT_TIME_MICRO	NUMBER	Amount of time the bucket represents (in microseconds). If the duration = num, then this column represents waits of duration < num that are not included in any smaller bucket.

Column	Datatype	Description
WAIT_COUNT	NUMBER	Number of waits of the duration belonging to the bucket of the histogram
LAST_UPDATE_TIME	VARCHAR2(64)	Indicates the last time the bucket was updated (the ending timestamp of the last wait falling into the bucket's duration)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.221 V$EVENT_NAME

V$EVENT_NAME displays information about wait events.

Column	Datatype	Description
EVENT#	NUMBER	Number of the wait event
EVENT_ID	NUMBER	Identifier of the wait event
NAME	VARCHAR2(64)	Name of the wait event. Names that appear in this column remain stable across Oracle Database releases, and they can be relied on by customer scripts.
PARAMETER1	VARCHAR2(64)	Description of the first parameter for the wait event
PARAMETER2	VARCHAR2(64)	Description of the second parameter for the wait event
PARAMETER3	VARCHAR2(64)	Description of the third parameter for the wait event
WAIT_CLASS_ID	NUMBER	Identifier of the class of the wait event
WAIT_CLASS#	NUMBER	Number of the class of the wait event
WAIT_CLASS	VARCHAR2(64)	Name of the class of the wait event **See Also:** "Classes of Wait Events" for a description of the different wait event classes
DISPLAY_NAME	VARCHAR2(64)	A clearer and more descriptive name for the wait event that appears in the NAME column. Names that appear in the DISPLAY_NAME column can change across Oracle Database releases, therefore customer scripts should not rely on names that appear in the DISPLAY_NAME column across releases.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.222 V$EVENTMETRIC

V$EVENTMETRIC displays values of wait event metrics for the most recent 60-second interval.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
EVENT#	NUMBER	Number of the event
EVENT_ID	NUMBER	Identifier of the event
NUM_SESS_WAITING	NUMBER	Number of sessions waiting at the end of the interval
TIME_WAITED	NUMBER	Time waited (in hundredths of a second)
WAIT_COUNT	NUMBER	Number of times waited
TIME_WAITED_FG	NUMBER	Time waited (in hundredths of a second), from foreground sessions
WAIT_COUNT_FG	NUMBER	Number of times waited, from foreground sessions
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.223 V$EXADIRECT_ACL

V$EXADIRECT_ACL monitors current ACLs propagated to the database instance.

Column	Datatype	Description
SERVICE_NAME	VARCHAR2(512)	Database service name
SGID	VARCHAR2(39)	Identifier of the VM allowed access to the specified service name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.224 V$EXECUTION

V$EXECUTION displays information on parallel execution.

Column	Datatype	Description
PID	NUMBER	Session ID
DEPTH	NUMBER	The depth
FUNCTION	VARCHAR2(10)	Session serial number
TYPE	VARCHAR2(7)	Name of the OBJECT_NODE in plan table
NVALS	NUMBER	Elapsed time for OBJECT_NODE
VAL1	NUMBER	The value for number 1
VAL2	NUMBER	The value for number 2
SEQH	NUMBER	A sequence
SEQL	NUMBER	A sequence
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.225 V$EXP_STATS

V$EXP_STATS stores the expression tracking statistics of recently executed queries.

Column	Datatype	Description
EXPID	NUMBER	Expression ID of the current expression
OBJNUM	NUMBER	The object number contained in the expression
DYNCOST	NUMBER	Optimizer dynamic cost of evaluating the expression
EVALCNT	NUMBER	Number of times the expression has been evaluated
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "ALL_EXPRESSION_STATISTICS"
- "DBA_EXPRESSION_STATISTICS"
- "ALL_EXPRESSION_STATISTICS"

8.226 V$FALSE_PING

V$FALSE_PING is deprecated. The information that was provided in this view is now provided in the V$INSTANCE_CACHE_TRANSFER and V$SEGMENT_STATISTICS views.

Column	Datatype	Description
FILE#	NUMBER	Data file identifier number (to find the file name, query DBA_DATA_FILES or V$DBFILE)
BLOCK#	NUMBER	Block number
STATUS	VARCHAR2(10)	Status of the block: • free - Not currently in use • xcur - Exclusive • scur - Shared current • cr - Consistent read • read - Being read from disk • mrec - In media recovery mode • irec - In instance recovery mode
XNC	NUMBER	Number of PCM lock conversions from Exclusive mode due to contention with another instance. This column is obsolete and maintained for backward compatibility.
FORCED_READS	NUMBER	Number of times the block had to be reread from the cache because another instance has forced it out of this instance's cache by requesting the lock on the block in exclusive mode
FORCED_WRITES	NUMBER	Number of times GCS had to write this block to cache because this instance had used the block and another instance had requested the lock on the block in a conflicting mode
NAME	VARCHAR2(128)	Name of the database object containing the block
PARTITION_NAME	VARCHAR2(128)	NULL for nonpartitioned objects
KIND	VARCHAR2(15)	Type of database object
OWNER#	NUMBER	Owner number
LOCK_ELEMENT_ADDR	RAW(4 | 8)	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
LOCK_ELEMENT_NAME	NUMBER	Name of the lock that contains the PCM lock that is covering the buffer
CLASS#	NUMBER	Lock element class
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$INSTANCE_CACHE_TRANSFER"
- "V$SEGMENT_STATISTICS"

8.227 V$FAST_START_FAILOVER_CONFIG

V$FAST_START_FAILOVER_CONFIG displays configuration details about Oracle Data Guard fast-start failover.

Column	Datatype	Description
FAST_START_FAILOVER_MODE	VARCHAR2(19)	Displays the current fast-start failover mode. Possible values are: • DISABLED - Fast-start failover is disabled. • OBSERVE-ONLY - Fast-start failover is enabled in test drive mode. • POTENTIAL DATA LOSS - Fast-start failover is enabled and a fast-start failover can incur data loss within FastStartFailoverLagLimit seconds. • ZERO DATA LOSS - Fast-start failover is enabled and a fast-start failover cannot incur any data loss.
STATUS	VARCHAR2(22)	Fast-start failover status: • BYSTANDER • DISABLED • LOADING DICTIONARY • PRIMARY UNOBSERVED • REINSTATE FAILED • REINSTATE REQUIRED • STALLED • SUSPENDED • SYNCHRONIZED • TARGET OVER LAG LIMIT • TARGET UNDER LAG LIMIT • UNSYNCHRONIZED **See Also:** *Oracle Data Guard Broker* for detailed descriptions of these values **Note:** If the value of this column is DISABLED, then the values for the CURRENT_TARGET, THRESHOLD, OBSERVER_PRESENT, and OBSERVER_HOST columns in this table are not meaningful.
CURRENT_TARGET	VARCHAR2(30)	DB_UNIQUE_NAME of the standby that is the current fail-safe failover observer target standby for the Data Guard configuration
THRESHOLD	NUMBER	Time (in seconds) that the observer will attempt to reconnect with a disconnected primary before attempting fail-safe failover observer with the target standby

Column	Datatype	Description
OBSERVER_PRESENT	VARCHAR2(7)	Indicates whether the master observer is currently connected to the local database (YES) or not (NO) **Note:** This column is consistent throughout an Oracle RAC environment; that is, if the observer is connected to any instance, then all instances will show a value of YES.
OBSERVER_HOST	VARCHAR2(512)	Machine name that is currently hosting the master observer process, if fast-start failover is enabled. If fast-start failover is not enabled, this column returns a NULL string.
PING_INTERVAL	NUMBER	ObserverPingInterval value for the fast-start failover configuration This value specifies how frequently the observer must ping the primary database (in milliseconds). **See Also:** *Oracle Data Guard Broker* for more information about the ObserverPingInterval configuration property
PING_RETRY	NUMBER	ObserverPingRetry value for the fast-start failover configuration This value specifies the number of times that the observer retries a failed ping before it initiates a failover to the target standby database. **See Also:** *Oracle Data Guard Broker* for more information about the ObserverPingRetry configuration property
PROTECTION_MODE	VARCHAR2(120)	Protection mode for the fast-start failover configuration: • MAXAVAILABILITY • MAXPERFORMANCE • MAXPROTECTION **See Also:** *Oracle Data Guard Broker* for more information about protection modes
LAG_LIMIT	NUMBER	FastStartFailoverLagLimit value for the fast-start failover configuration This value establishes an acceptable limit (in seconds) that the standby is allowed to fall behind the primary in terms of redo applied. **See Also:** *Oracle Data Guard Broker* for more information about the FastStartFailoverLagLimit configuration property
AUTO_REINSTATE	VARCHAR2(5)	FastStartFailoverAutoReinstate value (TRUE or FALSE) for the fast-start failover configuration This value specifies whether the former primary database is to be automatically reinstated if a fast-start failover was initiated because the primary database was either isolated or had crashed. **See Also:** *Oracle Data Guard Broker* for more information about the FastStartFailoverAutoReinstate configuration property
OBSERVER_RECONNECT	NUMBER	ObserverReconnect value for the fast-start failover configuration This value specifies how often (in seconds) the observer establishes a new connection to the primary database. **See Also:** *Oracle Data Guard Broker* for more information about the ObserverReconnect configuration property

Column	Datatype	Description
OBSERVER_OVERRIDE	VARCHAR2(5)	ObserverOverride value (TRUE or FALSE) for the fast-start failover configuration This value specifies whether an automatic failover is allowed to occur when the observer has lost connectivity to the primary. **See Also:** *Oracle Data Guard Broker* for more information about the ObserverOverride configuration property
SHUTDOWN_PRIMARY	VARCHAR2(5)	FastStartFailoverPmyShutdown value (TRUE or FALSE) for the fast-start failover configuration This value specifies whether the primary database should shut down under certain conditions. **See Also:** *Oracle Data Guard Broker* for more information about the FastStartFailoverPmyShutdown configuration property
LAG_TYPE	VARCHAR2(4000)	FastStartFailoverLagType value (APPLY or TRANSPORT) for the fast-start failover configuration This value specifies the type of lag (apply lag or transport lag) that is used to specify the data loss threshold. **See Also:** *Oracle Data Guard Broker* for more information about the FastStartFailoverLagType configuration property
LAG_GRACE_TIME	NUMBER	FastStartFailoverLagGraceTime value for the fast-start failover configuration This value specifies the maximum amount of time (in seconds) that can pass before the lag limit (FastStartFailoverLagLimit) is reached when the primary database requests permission to move to the lagging state. **See Also:** *Oracle Data Guard Broker* for more information about the FastStartFailoverLagGraceTime configuration property
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

8.228 V$FAST_START_SERVERS

V$FAST_START_SERVERS provides information about all the recovery workers performing parallel transaction recovery.

Column	Datatype	Description
STATE	VARCHAR2(11)	State of the server (IDLE or RECOVERING)

Column	Datatype	Description
UNDOBLOCKSDONE	NUMBER	Number of undo blocks done so far
PID	NUMBER	Process ID
XID	RAW(8)	Transaction ID
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.229 V$FAST_START_TRANSACTIONS

V$FAST_START_TRANSACTIONS displays information about the progress of the transactions that Oracle is recovering.

This view displays only transactions recovered in parallel. Recovery progress for serial transactions is not displayed.

Column	Datatype	Description
USN	NUMBER	Undo segment number of the transaction
SLT	NUMBER	Slot within the rollback segment
SEQ	NUMBER	Incarnation number of the slot
STATE	VARCHAR2(16)	State of the transaction (may be TO BE RECOVERED, RECOVERED, or RECOVERING)
UNDOBLOCKSDONE	NUMBER	Number of undo blocks completed on the transaction
UNDOBLOCKSTOTAL	NUMBER	Total number of undo blocks that need recovery
PID	NUMBER	ID of the current server it has been assigned to
CPUTIME	NUMBER	Time for which recovery has progressed (in seconds)
PARENTUSN	NUMBER	Undo segment number of the parent transaction in PDML
PARENTSLT	NUMBER	Slot of the parent transaction in PDML
PARENTSEQ	NUMBER	Sequence number of the parent transaction in PDML
XID	RAW(8)	Transaction ID
PXID	RAW(8)	Parent transaction ID
RCVSERVERS	NUMBER	Number of servers used in the last recovery
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.230 V$FILE_CACHE_TRANSFER

`V$FILE_CACHE_TRANSFER` is deprecated. The information that was provided in this view is now provided in the `V$INSTANCE_CACHE_TRANSFER` and `V$SEGMENT_STATISTICS` views.

Column	Datatype	Description
FILE_NUMBER	NUMBER	Number of the data file
X_2_NULL	NUMBER	Number of blocks with Exclusive-to-NULL conversions; always 0
X_2_NULL_FORCED_WRITE	NUMBER	Number of Exclusive-to-NULL forced writes; always 0
X_2_NULL_FORCED_STALE	NUMBER	Number of Exclusive-to-NULL blocks converted to CR; always 0
X_2_S	NUMBER	Number of blocks with Exclusive-to-Shared conversions; always 0
X_2_S_FORCED_WRITE	NUMBER	Number of Exclusive-to-Shared forced writes; always 0
S_2_NULL	NUMBER	Number of blocks with Shared-to-NULL conversions; always 0
S_2_NULL_FORCED_STALE	NUMBER	Number of Shared-to-NULL blocks converted to CR; always 0
RBR	NUMBER	Number of reuse blocks cross-instance calls; always 0
RBR_FORCED_WRITE	NUMBER	Number of blocks written due to reuse blocks cross-instance calls; always 0
RBR_FORCED_STALE	NUMBER	Number of blocks marked as flushed due to reuse blocks cross-instance calls; always 0
NULL_2_X	NUMBER	Number of blocks with NULL-to-Exclusive conversions; always 0
S_2_X	NUMBER	Number of blocks with Shared-to-Exclusive conversions; always 0
NULL_2_S	NUMBER	Number of blocks with NULL-to-Shared conversions; always 0
CR_TRANSFERS	NUMBER	Number of CR blocks received; always 0
CUR_TRANSFERS	NUMBER	Number of current blocks received; always 0
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$INSTANCE_CACHE_TRANSFER"
- "V$SEGMENT_STATISTICS"

8.231 V$FILE_HISTOGRAM

V$FILE_HISTOGRAM displays a histogram of all synchronous single block reads on a per-file basis (for data files). The histogram has buckets of time intervals from < 1 ms, < 2 ms, < 4 ms, < 8 ms, ... < 2^{21} ms, < 2^{22} ms, and >= 2^{22} ms.

The histogram will not be filled unless the STATISTICS_LEVEL initialization parameter is set to ALL.

Column	Datatype	Description
FILE#	NUMBER	File number
SINGLEBLKRDTIM_MILLI	NUMBER	Amount of time the bucket represents (in milliseconds). If the duration = *num*, then this column represents waits of duration < *num* that are not included in any smaller bucket.
SINGLEBLKRDS	NUMBER	Number of waits of the duration belonging to the bucket of the histogram
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.232 V$FILEMETRIC

V$FILEMETRIC displays values of file metrics for the most recent 10-minute interval. A history of the last one hour will be kept in the system.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
FILE_ID	NUMBER	File number
CREATION_TIME	NUMBER	Timestamp of the file creation
AVERAGE_READ_TIME	NUMBER	Average file read time (in hundredths of a second)
AVERAGE_WRITE_TIME	NUMBER	Average file write time (in hundredths of a second)
PHYSICAL_READS	NUMBER	Number of physical reads
PHYSICAL_WRITES	NUMBER	Number of physical writes
PHYSICAL_BLOCK_READS	NUMBER	Number of physical block reads
PHYSICAL_BLOCK_WRITES	NUMBER	Number of physical block writes

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.233 V$FILEMETRIC_HISTORY

V$FILEMETRIC_HISTORY displays values of file metrics for all intervals in the last one hour.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
FILE_ID	NUMBER	File number
CREATION_TIME	NUMBER	Timestamp of the file creation
AVERAGE_READ_TIME	NUMBER	Average file read time (in hundredths of a second)
AVERAGE_WRITE_TIME	NUMBER	Average file write time (in hundredths of a second)
PHYSICAL_READS	NUMBER	Number of physical reads
PHYSICAL_WRITES	NUMBER	Number of physical writes
PHYSICAL_BLOCK_READS	NUMBER	Number of physical block reads
PHYSICAL_BLOCK_WRITES	NUMBER	Number of physical block writes
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.234 V$FILESPACE_USAGE

V$FILESPACE_USAGE summarizes space allocation information of each data file and temp file.

Column	Datatype	Description
TABLESPACE_ID	NUMBER	ID of the tablespace to which the file belongs
RFNO	NUMBER	Relative file number of the file
ALLOCATED_SPACE	NUMBER	Total allocated space in the file
FILE_SIZE	NUMBER	Current file size

Column	Datatype	Description
FILE_MAXSIZE	NUMBER	Maximum file size
CHANGESCN_BASE	NUMBER	SCN base of the last change to the file
CHANGESCN_WRAP	NUMBER	SCN wrap of the last change to the file
CHANGESCN8	NUMBER	The 8–byte representation of the SCN at which the last change happened to the file
FLAG	NUMBER	Flags for file attributes
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.235 V$FILESTAT

V$FILESTAT displays the number of physical reads and writes done and the total number of single-block and multiblock I/Os done at file level.

As of Oracle Database 10g Release 2 (10.2), this view also includes reads done by RMAN processes for backup operations.

Column	Datatype	Description
FILE#	NUMBER	Number of the file
PHYRDS	NUMBER	Number of physical reads done
PHYWRTS	NUMBER	Number of times DBWR is required to write
PHYBLKRD	NUMBER	Number of physical blocks read
OPTIMIZED_PHYBLKRD	NUMBER	Number of physical reads from Database Smart Flash Cache blocks
PHYBLKWRT	NUMBER	Number of blocks written to disk, which may be the same as PHYWRTS if all writes are single blocks
SINGLEBLKRDS	NUMBER	Number of single block reads
READTIM	NUMBER	Time (in hundredths of a second) spent doing reads if the TIMED_STATISTICS parameter is true; 0 if false
WRITETIM	NUMBER	Time (in hundredths of a second) spent doing writes if the TIMED_STATISTICS parameter is true; 0 if false
SINGLEBLKRDTIM	NUMBER	Cumulative single block read time (in hundredths of a second)
AVGIOTIM	NUMBER	Average time (in hundredths of a second) spent on I/O, if the TIMED_STATISTICS parameter is true; 0 if false
LSTIOTIM	NUMBER	Time (in hundredths of a second) spent doing the last I/O, if the TIMED_STATISTICS parameter is true; 0 if false
MINIOTIM	NUMBER	Minimum time (in hundredths of a second) spent on a single I/O, if the TIMED_STATISTICS parameter is true; 0 if false

Column	Datatype	Description
MAXIORTM	NUMBER	Maximum time (in hundredths of a second) spent doing a single read, if the TIMED_STATISTICS parameter is true; 0 if false
MAXIOWTM	NUMBER	Maximum time (in hundredths of a second) spent doing a single write, if the TIMED_STATISTICS parameter is true; 0 if false
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.236 V$FIXED_TABLE

V$FIXED_TABLE displays all dynamic performance tables, views, and derived tables in the database.

Some V$ tables (for example, V$ROLLNAME) refer to real tables and are therefore not listed.

Column	Datatype	Description
NAME	VARCHAR2(128)	Name of the object
OBJECT_ID	NUMBER	Identifier of the fixed object
TYPE	VARCHAR2(5)	Object type (TABLE | VIEW)
TABLE_NUM	NUMBER	Number that identifies the dynamic performance table if it is of type TABLE
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.237 V$FIXED_VIEW_DEFINITION

V$FIXED_VIEW_DEFINITION contains the definitions of all the fixed views (views beginning with V$).

Use this table with caution. Oracle tries to keep the behavior of fixed views the same from release to release, but the definitions of the fixed views can change without notice. Use these definitions to optimize your queries by using indexed columns of the dynamic performance tables.

Column	Datatype	Description
VIEW_NAME	VARCHAR2(128)	Name of the fixed view

Column	Datatype	Description
VIEW_DEFINITION	VARCHAR2(4000)	Definition of the fixed view
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.238 V$FLASHBACK_DATABASE_LOG

V$FLASHBACK_DATABASE_LOG displays information about the flashback data. Use this view to help estimate the amount of flashback space required for the current workload.

Column	Datatype	Description
OLDEST_FLASHBACK_SCN	NUMBER	Lowest system change number (SCN) in the flashback data, for any incarnation
OLDEST_FLASHBACK_TIME	DATE	Time of the lowest SCN in the flashback data, for any incarnation
RETENTION_TARGET	NUMBER	Target retention time (in minutes)
FLASHBACK_SIZE	NUMBER	Current size (in bytes) of the flashback data
ESTIMATED_FLASHBACK_SIZE	NUMBER	Estimated size of flashback data needed (in bytes) for the current target retention
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.239 V$FLASHBACK_DATABASE_LOGFILE

V$FLASHBACK_DATABASE_LOGFILE displays information about the flashback log files.

Column	Datatype	Description
NAME	VARCHAR2(513)	Name of the log file
LOG#	NUMBER	Log file number
THREAD#	NUMBER	Log file thread number
SEQUENCE#	NUMBER	Log file sequence number
BYTES	NUMBER	Log file size (in bytes)
FIRST_CHANGE#	NUMBER	Lowest system change number (SCN) in the log file
FIRST_TIME	DATE	Time of the first SCN in the log file

Column	Datatype	Description
TYPE	VARCHAR2(9)	Log type: • NORMAL • RESERVED • FREE • TO DELETE
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.240 V$FLASHBACK_DATABASE_STAT

V$FLASHBACK_DATABASE_STAT displays statistics for monitoring the I/O overhead of logging flashback data. This view also displays the estimated flashback space needed based on previous workloads.

Column	Datatype	Description
BEGIN_TIME	DATE	Beginning of the time interval
END_TIME	DATE	End of the time interval
FLASHBACK_DATA	NUMBER	Number of bytes of flashback data written during the interval
DB_DATA	NUMBER	Number of bytes of database data read and written during the interval
REDO_DATA	NUMBER	Number of bytes of redo data written during the interval
ESTIMATED_FLASHBACK_SIZE	NUMBER	Value of ESTIMATED_FLASHBACK_SIZE in V$FLASHBACK_DATABASE_LOG at the end of the time interval
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.241 V$FLASHBACK_LOG_DEST

V$FLASHBACK_LOG_DEST displays information about the disk quota and current disk usage for the flashback database log storage area.

Column	Datatype	Description
NAME	VARCHAR2(513)	Location of the flashback database log storage area This value is specified by the DB_FLASHBACK_LOG_DEST initialization parameter.
SPACE_LIMIT	NUMBER	Maximum amount of disk space (in bytes) that the database can use for the flashback database log storage area This is the value specified by the DB_FLASHBACK_LOG_DEST_SIZE initialization parameter.
SPACE_USED	NUMBER	Amount of disk space (in bytes) currently used by flashback database log files in the flashback database log storage area
NUMBER_OF_FILES	NUMBER	Number of files currently in the flashback database log storage area
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

This view is available starting with Oracle Database 23ai.

See Also:

- "DB_FLASHBACK_LOG_DEST"
- "DB_FLASHBACK_LOG_DEST_SIZE"

8.242 V$FLASHBACK_TXN_GRAPH

V$FLASHBACK_TXN_GRAPH displays a tabular representation of the transaction dependency graph. For each dependency edge, there could be multiple rows, one for each conflicting operation.

This view is relevant AFTER a compensating transaction has been started through the DBMS_FLASHBACK.TRANSACTION_BACKOUT() set of functions, and is no longer relevant once the compensating transaction is either committed or rolled back. It also provides a tabular representation of the undo SQL that is not available through the CLOB XML construct in the DBA_FLASHBACK_TXN_REPORT view.

Column	Datatype	Description
COMPENSATING_XID	RAW(8)	Transaction ID of the compensating transaction

Column	Datatype	Description
COMPENSATING_TXN_NAME	VARCHAR2(255)	Name of the compensating transaction
XID	RAW(8)	Transaction ID of a relevant transaction found in memory
TXN_NAME	VARCHAR2(255)	Name of the transaction with XID as the transaction ID; NULL if none
PARENT_XID	RAW(8)	Parent transaction ID (for a PDML transaction)
INTERESTING	NUMBER	If the transaction is in the transaction dependency graph
ORIGINAL	NUMBER	If the transaction is part of the input set provided
BACKOUT_SEQ	NUMBER	Order in which the transaction has been backed out
NUM_PREDS	NUMBER	Number of predecessors of the transaction specified by XID in the transaction graph
NUM_SUCCS	NUMBER	Number of successors of the transaction specified by XID in the transaction graph
DEP_XID	RAW(8)	One dependent transaction ID of the transaction specified by XID. This is a particular child of XID.
DEP_TXN_NAME	VARCHAR2(255)	Transaction name, if any, for the transaction specified by DEP_XID
TXN_CONF_SQL_ID	NUMBER	SQL ID of undo SQL executed in the context of XID which conflicts with the dependent transaction
DEP_TXN_CONF_SQL_ID	NUMBER	SQL ID of undo SQL executed in the context of DEP_XID which conflicts with XID
CONFLICT_TYPE	VARCHAR2(32)	The type of conflict that the conflict resolution method is used to resolve: delete, uniqueness, or update
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "DBA_FLASHBACK_TXN_REPORT"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_FLASHBACK.TRANSACTION_BACKOUT procedures

8.243 V$FLASHBACK_TXN_MODS

V$FLASHBACK_TXN_MODS displays the individual modifications of all the transactions in memory.

This view is relevant AFTER a compensating transaction has been started through the DBMS_FLASHBACK.TRANSACTION_BACKOUT() set of functions, and is no longer relevant once the compensating transaction is either committed or rolled back. It also provides a tabular

representation of the undo SQL that is not available through the CLOB XML construct in the DBA_FLASHBACK_TXN_REPORT view.

Column	Datatype	Description
COMPENSATING_XID	RAW(8)	Transaction ID of the compensating transaction
COMPENSATING_TXN_NAME	VARCHAR2(255)	Name of the compensating transaction
XID	RAW(8)	Transaction ID of a relevant transaction found in memory
TXN_NAME	VARCHAR2(255)	Name of the transaction with XID as the transaction ID; NULL if none
PARENT_XID	RAW(8)	Parent transaction ID (for a PDML transaction)
INTERESTING	NUMBER	If the transaction is in the transaction dependency graph
ORIGINAL	NUMBER	If the transaction is part of the input set provided
BACKOUT_SEQ	NUMBER	Order in which the transaction has been backed out
UNDO_SQL	VARCHAR2(4000)	Undo SQL for the modification
UNDO_SQL_SQN	NUMBER	Order in which the given SQL has been executed to back out this transaction
UNDO_SQL_SUB_SQN	NUMBER	If the undo SQL is greater than 4000 bytes, then a sequence number, starting from 1, of a 4000-byte division of the undo SQL
BACKOUT_SQL_ID	NUMBER	SQL ID of the undo SQL (used only for this compensating transaction)
OPERATION	VARCHAR2(128)	Operation (such as insert/update/delete) performed by the forward-going operation
BACKEDOUT	NUMBER	Indicates whether the transaction has been backed out as of now
CONFLICT_MOD	NUMBER	If the concerned modification is causing a conflict
MODS_PER_LCR	NUMBER	Sometimes an LCR could cause multiple modifications (for example, an update of an IOT could actually be a delete followed by an insert)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "DBA_FLASHBACK_TXN_REPORT"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_FLASHBACK.TRANSACTION_BACKOUT procedures

8.244 V$FLASHFILESTAT

V$FLASHFILESTAT displays statistics about Database Smart Flash Cache.

By taking snapshots of SINGLEBLKRDS and SINGLEBLKRDTIM_MICRO, you can easily calculate the average latency of all the flash files in a given time period

Column	Datatype	Description
FLASHFILE#	NUMBER	The file number of the flash file
NAME	VARCHAR2(513)	Name and path of the flash file
BYTES	NUMBER	Size of the flash file, in bytes
ENABLED	NUMBER	Indicates whether this flash file is enabled or not
SINGLEBLKRDS	NUMBER	Number of reads to the flash file
SINGLEBLKRDTIM_MICRO	NUMBER	Cumulative latency of reading blocks from this particular flash file/ device, in microseconds
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database Administrator's Guide for more information about configuring Database Smart Flash Cache

8.245 V$FOREIGN_ARCHIVED_LOG

V$FOREIGN_ARCHIVED_LOG can be queried on a logical standby database to find out the list of foreign archived logs received by a database.

No rows are returned for this view on a physical standby database.

Column	Datatype	Description
RECID	NUMBER	Archived log record ID
STAMP	NUMBER	Archived log record stamp
NAME	VARCHAR2(513)	Archived log file name. If set to NULL, either the log file was cleared before it was archived or an RMAN BACKUP command with the delete input option was executed to back up archivelog all (RMAN> backup archivelog all delete input;).
DEST_ID	NUMBER	Original destination from which the archive log was generated. The value is 0 if the destination identifier is not available

Column	Datatype	Description
THREAD#	NUMBER	Redo thread number
SEQUENCE#	NUMBER	Redo log sequence number
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the database when the log was written
RESETLOGS_TIME	DATE	Resetlogs time of the database when the log was written
RESETLOGS_ID	NUMBER	Resetlogs identifier associated with the archived redo log
FIRST_CHANGE#	NUMBER	First change number in the archived log
FIRST_TIME	DATE	Timestamp of the first change
NEXT_CHANGE#	NUMBER	First change in the next log
NEXT_TIME	DATE	Timestamp of the next change
BLOCKS	NUMBER	Size of the archived log (in blocks)
BLOCK_SIZE	NUMBER	Redo log block size. This is the logical block size of the archived log, which is the same as the logical block size of the online log from which the archived log was copied. The online log logical block size is a platform-specific value that is not adjustable by the user.
CREATOR	VARCHAR2(7)	Creator of the archive log: ARCH - Archiver process FGRD - Foreground process RMAN - Recovery Manager SRMN - RMAN at standby LGWR - Logwriter process
REGISTRAR	VARCHAR2(7)	Registrar of the entry: RFS - Remote File Server process ARCH - Archiver process FGRD - Foreground process RMAN - Recovery Manager SRMN - RMAN at standby LGWR - Logwriter process
ARCHIVED	VARCHAR2(3)	Indicates whether the online redo log was archived (YES) or whether RMAN only inspected the log and created a record for future application of redo logs during recovery (NO).
APPLIED	VARCHAR2(3)	Indicates whether the archivelog has been applied to its corresponding standby database (YES) or not (NO). The value is always NO for local destinations. This column is meaningful at the standby site for the ARCHIVED_LOG entries with REGISTRAR='RFS' (which means this log is shipped from the primary to the standby database). If REGISTRAR='RFS' and APPLIED is NO, then the log has arrived at the standby but has not yet been applied. If REGISTRAR='RFS' and APPLIED is YES, the log has arrived and been applied at the standby database. You can use this field to identify archivelogs that can be backed up and removed from disk.

Column	Datatype	Description
DELETED	VARCHAR2(3)	Indicates whether an RMAN DELETE command has physically deleted the archived log file from disk, as well as logically removing it from the control file of the target database and from the recovery catalog (YES) or not (NO)
STATUS	VARCHAR2(1)	Status of the archived log: A - Available D - Deleted U - Unavailable X - Expired
COMPLETION_TIME	DATE	Time when the archiving completed
DICTIONARY_BEGIN	VARCHAR2(3)	Indicates whether the log contains the start of a LogMiner dictionary (YES) or not (NO)
DICTIONARY_END	VARCHAR2(3)	Indicates whether the log contains the end of a LogMiner dictionary (YES) or not (NO)
END_OF_REDO	VARCHAR2(3)	Indicates whether the archived redo log contains the end of all redo information from the primary database () or not ()
ARCHIVAL_THREAD#	NUMBER	Redo thread number of the instance that performed the archival operation. This column differs from the THREAD# column only when a closed thread is archived by another instance.
IS_RECOVERY_DEST_FILE	VARCHAR2(3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)
COMPRESSED	VARCHAR2(3)	Reserved for internal use
FAL	VARCHAR2(3)	Indicates whether the archive log was generated as the result of a FAL request (YES) or not (NO)
END_OF_REDO_TYPE	VARCHAR2(10)	Possible values are as follows: SWITCHOVER - Shows archived redo log files that are produced at the end of a switchover TERMINAL - Shows archived redo log files produced after a failover RESETLOGS - Shows online redo log files archived on the primary database after an ALTER DATABASE OPEN RESETLOGS statement is issued ACTIVATION - Shows any log files archived on a physical standby database after an ALTER DATABASE ACTIVATE STANDBY DATABASE statement is issued "empty string" - Any empty string implies that the log is just a normal archival and was not archived due to any of the other events
SOURCE_DBID	NUMBER	Database ID of the source database that generated this archived log
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.246 V$FS_FAILOVER_OBSERVERS

V$FS_FAILOVER_OBSERVERS provides information about fast-start failover observers.

If you are querying on the primary database, this view returns three rows, each describing one observer. However, only a row having an non-empty value in column NAME corresponds to a started observer. If you are querying on a non-primary database, the behavior of this view is not defined.

Column	Datatype	Description
NAME	VARCHAR2(513)	The fast-start failover observer name
REGISTERED	VARCHAR2(4)	Indicates if this observer is registered (YES) or not (NO). Note that the observer is registered *only* if HOST is not NULL.
HOST	VARCHAR2(513)	The name of the host where this observer is running
ISMASTER	VARCHAR2(4)	Indicates if this observer is the master observer (YES) or not (NO)
TIME_SELECTED	TIMESTAMP(9)	Shows when this observer became master observer, if ISMASTER is YES; otherwise the following constant appears: 1990-01-01 00:00:00.00
PINGING_PRIMARY	VARCHAR2(4)	Possible values: • YES: Observer is currently connected to the primary database • NO: Observer is not connected to the primary database **Note**: This field is consistent throughout an Oracle Real Application Clusters (Oracle RAC) environment; that is, if the observer is connected to any instance of the primary database in the Oracle RAC environment, all instances will show a value of YES.
PINGING_TARGET	VARCHAR2(4)	Possible values: • YES: Observer is currently connected to the target standby database • NO: Observer is not connected to the target standby database **Note**: This field is consistent throughout an Oracle Real Application Clusters (Oracle RAC) environment; that is, if the observer is connected to any instance of the target standby database in the Oracle RAC environment, all instances will show a value of YES.
LAST_PING_PRIMARY	NUMBER	Amount of time (in seconds) since the observer last pinged the primary database
LAST_PING_TARGET	NUMBER	Amount of time (in seconds) since the observer last pinged the target standby database
LOG_FILE	VARCHAR2(513)	Full path to the observer log file
STATE_FILE	VARCHAR2(513)	Full path to the observer runtime data file
CURRENT_TIME	TIMESTAMP(9)	Date and time at which this view was queried

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.247 V$FS_FAILOVER_STATS

V$FS_FAILOVER_STATS displays statistics about fast-start failovers occurring on the system.

Column	Datatype	Description
LAST_FAILOVER_TIME	VARCHAR2(20)	Timestamp of the last fast-start failover
LAST_FAILOVER_REASON	VARCHAR2(255)	Reason for the last fast-start failover
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

This view is deprecated in Oracle Database 23ai. Oracle recommends that you instead use the V$DG_BROKER_ROLE_CHANGE view. V$FS_FAILOVER_STATS displays one row with limited information about the most recent fast-start failover. The data is available in the primary database only, and is not persisted across database restarts. V$DG_BROKER_ROLE_CHANGE contains detailed information about the ten most recent role changes, including switchover, failover, and reinstate, across the Data Guard broker configuration, and provides richer information than V$FS_FAILOVER_STATS. See "V$DG_BROKER_ROLE_CHANGE" for more information.

8.248 V$FS_OBSERVER_HISTOGRAM

V$FS_OBSERVER_HISTOGRAM displays statistics that are based on the frequency of successful pings between the observer and primary database for different time intervals. The wait event in this histogram is the observer's wait until pings to the primary succeed.

The histogram displays only when there were ping failures between the observer and the primary database.

No rows are shown in this view for unregistered observers.

These statistics can be used to select an appropriate value for the `FastStartFailoverThreshold` configuration property for your environment.

Column	Datatype	Description
`OBSERVER_NAME`	`VARCHAR2(513)`	The Fast-Start Failover observer name
`OBSERVER_HOST`	`VARCHAR2(513)`	The name of the host where this observer is running
`WAIT_TIME`	`NUMBER`	The time interval between a pair of successful observer pings (ping-pairs) to this instance. Note that the values in this column are the upper bound of the inter-ping interval samples represented by a given histogram bucket. If `WAIT_TIME` = *number*, then this column represents inter-ping intervals <= *number* that are not included in any smaller bucket. The value in this column is the time (in seconds) that a ping failure lasted.
`WAIT_COUNT`	`NUMBER`	The number of ping-pairs with an inter-ping interval that corresponds with this histogram bucket. If all pings have been successful so far, this column has a value of 0.
`LAST_UPDATE_TIME`	`VARCHAR2(20)`	The last time this row was updated
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Data Guard Broker for more information about the `FastStartFailoverThreshold` configuration property

Example

Assume that the following shows the status of observer's pings to the primary:

```
Ping time   Ping result
---------  -----------
1:00:00    SUCCESS
1:00:03    FAIL
1:00:06    FAIL
1:00:09    SUCCESS   => Wait time of 6 seconds
1:00:12    SUCCESS
1:00:15    FAIL
1:00:18    FAIL
1:00:21    SUCCESS   => Wait time of 6 seconds
1:00:24    SUCCESS
1:00:27    FAIL
1:00:30    SUCCESS   => Wait time of 3 seconds
```

These ping results will result in the histogram view below:

```
WAIT_TIME   WAIT_COUNT   LAST_UPDATE_TIME
  3         1            1:00:30

  6         2            1:00:21

  9         0

 12         0

...
```

In this case, the `FastStartFailoverThreshold` value should be set to larger than 6 because communication between the observer and the primary sometimes fails for 6 seconds.

8.249 V$GC_ELEMENT

`V$GC_ELEMENT` displays one entry for each global cache resource that is used by the buffer cache. The name of the global cache resource that corresponds to a lock element is {'BL', indx, class}. This is an Oracle Real Application Clusters view.

Column	Datatype	Description
GC_ELEMENT_ADDR	RAW(4 | 8)	Address of the lock element that contains the PCM lock that is covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
INDX	NUMBER	Platform specific lock manager identifier
CLASS	NUMBER	Platform specific lock manager identifier
GC_ELEMENT_NAME	NUMBER	Name of the lock that contains the PCM lock that is covering the buffer
MODE_HELD	NUMBER	Platform dependent value for lock mode held; often: 3 = share; 5 = exclusive
BLOCK_COUNT	NUMBER	Number of blocks covered by PCM lock
RELEASING	NUMBER	Nonzero if PCM lock is being downgraded
ACQUIRING	NUMBER	Nonzero if PCM lock is being upgraded
WRITING	NUMBER	If the GC_ELEMENT is being written, the write status
RECOVERING	NUMBER	If the GC_ELEMENT is being recovered, the recovery status
LOCAL	NUMBER	Zero if the GC_ELEMENT is local, one if it is global
FLAGS	NUMBER	Process level flags for the lock element
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.250 V$GC_ELEMENTS_WITH_COLLISIONS

`V$GC_ELEMENTS_WITH_COLLISIONS` is deprecated. The information that was provided in this view is now provided in the `V$INSTANCE_CACHE_TRANSFER` and `V$SEGMENT_STATISTICS` views.

Column	Datatype	Description
GC_ELEMENT_ADDR	RAW(4 | 8)	Address of the lock element that contains the PCM lock covering the buffer. If more than one buffer has the same address, then these buffers are covered by the same PCM lock.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$INSTANCE_CACHE_TRANSFER"
- "V$SEGMENT_STATISTICS"

8.251 V$GCR_ACTIONS

V$GCR_ACTIONS displays information about the current status of the actions defined to the GCR component that runs under the LMHB background process to detect and mitigate potential issues in the cluster instances.

Column	Datatype	Description
ACTION_ID	NUMBER	Action identification number as used internally to refer to the metric
ACTION_NAME	VARCHAR2(40)	Name of the action
ENVIRONMENT	NUMBER	Environment that the action should run in: • 0: Nowhere (do not run) • 1: Oracle ASM instance only • 2: Oracle Database instance only • 3: Oracle ASM and Oracle Database instance • 4: Standby instance • 5: Oracle ASM and Standby instance • 6: Oracle Database and Standby instance • 7: Oracle Database, Oracle ASM, and Standby instance • 15: All instance types
FLAGS	NUMBER	Various flags describing the action. Used only by Oracle for diagnosis.
ACTIVE	VARCHAR2(9)	Whether the action is active or not: • ACTIVE: Action is active. • INACTIVE: Action is disabled.
STATUS_CHANGE_TIME	TIMESTAMP(6)	Time of last action change of status

Column	Datatype	Description
LAST_RAN_ITERATION	NUMBER	Iteration of the last time the action ran
LAST_RAN_TIME	TIMESTAMP(6)	Time of last run
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.252 V$GCR_LOG

V$GCR_LOG provides information on the last 30 significant events that have occurred in GCR in the recent past.

Column	Datatype	Description
INST_ID	NUMBER	Instance identier
ITERATION	NUMBER	GCR internal iteration count
TIME	TIMESTAMP(6)	Timestamp of record
TYPE	VARCHAR2(14)	Type of record: • METRIC • METRIC ENABLE • METRIC DISABLE • GLOBAL METRIC • ACTION RAN • RESET RAN
DESCRIPTION	VARCHAR2(40)	Description of function
RESULT	VARCHAR2(7)	Result: • OK • FAIL
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data.

8.253 V$GCR_METRICS

V$GCR_METRICS displays information about the current status of the metrics defined to the GCR component that runs under the LMHB background process to detect and mitigate potential issues in the cluster instances.

Column	Datatype	Description
METRIC_ID	NUMBER	Metric identification number as used internally to refer to the metric
METRIC_NAME	VARCHAR2(40)	Name of the metric
ENVIRONMENT	NUMBER	Environment that the metric should run in: • 0: Nowhere (do not run) • 1: Oracle ASM instance only • 2: Oracle Database instance only • 3: Oracle ASM and Oracle Database instance • 4: Standby instance • 5: Oracle ASM and Standby instance • 6: Oracle Database and Standby instance • 7: Oracle Database, Oracle ASM, and Standby instance • 15: All instance types
FREQUENCY	NUMBER	How often the metric runs, in seconds
SCOPE	NUMBER	The scope of sharing of the metric: • 0: The metric does not have associated data • 1: Global - shared with all other instances in the cluster • 2: Local - used only locally (not shared) • 4: Node Global - shared with other instances in the cluster on the same node only • 8: DB Only - Shared with other instances of the same database only
DATA_TYPE	VARCHAR2(7)	The type of the data associated with this metric: • 0: None • 1: Boolean • 2: Numeric • 3: Process
STATUS	VARCHAR2(9)	Indicates the status of the metric: • ACTIVE: Indicates that the metric is active. • INACTIVE: Indicates that the metric is turned off.
STATUS_CHANGE_TIME	TIMESTAMP(6)	Time of last metric change of status
LAST_RAN_ITERATION	NUMBER	Iteration of the last time the metric ran
LAST_RAN_TIME	TIMESTAMP(6)	Time of last run
LAST_PASS_ITERATION	NUMBER	Iteration of last time the metric passed
LAST_PASS_TIME	TIMESTAMP(6)	Time of last metric pass
TOTAL_PASSES	NUMBER	Total number of times the metric passed since start of LMHB
LAST_FAIL_ITERATION	NUMBER	Iteration of last time the metric failed
LAST_FAIL_TIME	TIMESTAMP(6)	Time of last metric failure
TOTAL_FAILS	NUMBER	Total number of times the metric has failed since start of LMHB

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.254 V$GCR_STATUS

V$GCR_STATUS provides information on the current GCR status, what metrics ran and their result. It records the last 100 events.

Column	Datatype	Description
INST_ID	NUMBER	Instance identifier
ITERATION	NUMBER	GCR internal iteration count
TIME	TIMESTAMP(6)	Timestamp of record
TYPE	VARCHAR2(14)	Type of record: • METRIC • GLOBAL METRIC • ACTION RAN • RESET RAN
DESCRIPTION	VARCHAR2(40)	Description of function
RESULT	VARCHAR2(7)	Result: • OK • FAIL
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data.

8.255 V$GCSHVMASTER_INFO

V$GCSHVMASTER_INFO describes the current and previous master instances and the number of re-masterings of Global Cache Service resources except those belonging to files mapped to a particular master.

Column	Datatype	Description
HV_ID	NUMBER	PCM hash value ID
CURRENT_MASTER	NUMBER	Master instance of this PCM hash value ID

Column	Datatype	Description
PREVIOUS_MASTER	NUMBER	Previous master instance of this PCM hash value ID
REMASTER_CNT	NUMBER	Number of times this has been remastered
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.256 V$GCSPFMASTER_INFO

V$GCSPFMASTER_INFO describes the current and previous master instances and the number of re-masterings of Global Cache Service resources belonging to files mapped to instances.

Column	Datatype	Description
FILE_ID	NUMBER	File number
DATA_OBJECT_ID	NUMBER	Data object ID
GC_MASTERING_POLICY	VARCHAR2(11)	Data object type. The possible values are Affinity or Read mostly.
CURRENT_MASTER	NUMBER	Master instance of this file
PREVIOUS_MASTER	NUMBER	Previous master instance of this file
REMASTER_CNT	NUMBER	Number of times this has been remastered
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.257 V$GES_BLOCKING_ENQUEUE

V$GES_BLOCKING_ENQUEUE describes all locks currently known to lock manager that are being blocked or blocking others.

The output of this view is a subset of the output from V$GES_ENQUEUE. This is an Oracle Real Application Clusters view.

> **See Also:**
>
> "V$GES_ENQUEUE" for a description of all locks known to the lock manager

Column	Datatype	Description
HANDLE	RAW(4 | 8)	Lock pointer
GRANT_LEVEL	VARCHAR2(9)	Granted level of the lock
REQUEST_LEVEL	VARCHAR2(9)	Requested level of the lock
RESOURCE_NAME1	VARCHAR2(30)	Resource name for the lock
RESOURCE_NAME2	VARCHAR2(30)	Resource name for the lock
PID	NUMBER	Process identifier which holds the lock
TRANSACTION_ID0	NUMBER	Lower 4 bytes of the transaction identifier where the lock belongs to
TRANSACTION_ID1	NUMBER	Upper 4 bytes of the transaction identifier where the lock belongs to
GROUP_ID	NUMBER	Group identifier for the lock
OPEN_OPT_DEADLOCK	NUMBER	1 if DEADLOCK open option is set, otherwise 0
OPEN_OPT_PERSISTENT	NUMBER	1 if PERSISTENT open option is set, otherwise 0
OPEN_OPT_PROCESS_OWNED	NUMBER	1 if PROCESS_OWNED open option is set, otherwise 0
OPEN_OPT_NO_XID	NUMBER	1 if NO_XID open option is set, otherwise 0
CONVERT_OPT_GETVALUE	NUMBER	1 if GETVALUE convert option is set, otherwise 0
CONVERT_OPT_PUTVALUE	NUMBER	1 if PUTVALUE convert option is set, otherwise 0
CONVERT_OPT_NOVALUE	NUMBER	1 if NOVALUE convert option is set, otherwise 0
CONVERT_OPT_DUBVALUE	NUMBER	1 if DUBVALUE convert option is set, otherwise 0
CONVERT_OPT_NOQUEUE	NUMBER	1 if NOQUEUE convert option is set, otherwise 0
CONVERT_OPT_EXPRESS	NUMBER	1 if EXPRESS convert option is set, otherwise 0
CONVERT_OPT_NODEADLOCKWAIT	NUMBER	1 if NODEADLOCKWAIT convert option is set, otherwise 0
CONVERT_OPT_NODEADLOCKBLOCK	NUMBER	1 if NODEADLOCKBLOCK convert option is set, otherwise 0
WHICH_QUEUE	NUMBER	Which queue the lock is currently located. 0 for NULL queue; 1 for GRANTED queue; 2 for CONVERT queue.
STATE	VARCHAR2(64)	State of lock as owner sees it
AST_EVENT0	NUMBER	Last AST event
OWNER_NODE	NUMBER	Node identifier
BLOCKED	NUMBER	1 if this lock request is blocked by others, otherwise 0
BLOCKER	NUMBER	1 if this lock is blocking others, otherwise 0
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.258 V$GES_CONVERT_LOCAL

V$GES_CONVERT_LOCAL displays statistics for local GES enqueue operations. This view records average convert times, count information, and timed statistics for global enqueue requests.

Column	Datatype	Description
INST_ID	NUMBER	ID of the instance
CONVERT_TYPE	VARCHAR2(16)	Conversion type: • NULL -> SS - NULL mode to subshared mode • NULL -> SX - NULL mode to shared exclusive mode • NULL -> S - NULL mode to shared mode • NULL -> SSX - NULL mode to subshared exclusive mode • NULL -> X - NULL mode to exclusive mode • SS -> SX - Subshared mode to shared exclusive mode • SS -> S - Subshared mode to shared mode • SS -> SSX - Subshared mode to subshared exclusive mode • SS -> X - Subshared mode to exclusive mode • SX -> S - Shared exclusive mode to shared mode • SX -> SSX - Shared exclusive mode to subshared exclusive mode • SX -> X - Shared exclusive mode to exclusive mode • S -> SX - Shared mode to shared exclusive mode • S -> SSX - Shared mode to subshared exclusive mode • S -> X - Shared mode to exclusive mode • SSX -> X - Sub-shared exclusive mode to exclusive mode
AVERAGE_CONVERT_TIME	NUMBER	Average conversion time for each type of lock operation (in hundredths of a second)
CONVERT_COUNT	NUMBER	Number of operations
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.259 V$GES_CONVERT_REMOTE

V$GES_CONVERT_REMOTE displays values for remote GES enqueue conversions. This view records average convert times, count information, and timed statistics for global enqueue requests.

Column	Datatype	Description
INST_ID	NUMBER	ID of the instance

Column	Datatype	Description
CONVERT_TYPE	VARCHAR2(16)	Conversion type: • NULL -> SS - NULL mode to subshared mode • NULL -> SX - NULL mode to shared exclusive mode • NULL -> S - NULL mode to shared mode • NULL -> SSX - NULL mode to subshared exclusive mode • NULL -> X - NULL mode to exclusive mode • SS -> SX - Subshared mode to shared exclusive mode • SS -> S - Subshared mode to shared mode • SS -> SSX - Subshared mode to subshared exclusive mode • SS -> X - Subshared mode to exclusive mode • SX -> S - Shared exclusive mode to shared mode • SX -> SSX - Shared exclusive mode to subshared exclusive mode • SX -> X - Shared exclusive mode to exclusive mode • S -> SX - Shared mode to shared exclusive mode • S -> SSX - Shared mode to subshared exclusive mode • S -> X - Shared mode to exclusive mode • SSX -> X - Sub-shared exclusive mode to exclusive mode
AVERAGE_CONVERT_TIME	NUMBER	Average conversion time for each type of lock operation (in hundredths of a second)
CONVERT_COUNT	NUMBER	Number of operations
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.260 V$GES_ENQUEUE

V$GES_ENQUEUE describes all locks currently known to lock manager. This is an Oracle Real Application Clusters view.

> **See Also:**
>
> "V$GES_BLOCKING_ENQUEUE" for a description of all such locks that are currently blocking or being blocked

Column	Datatype	Description
HANDLE	RAW(4 | 8)	Lock pointer
GRANT_LEVEL	VARCHAR2(9)	Granted level of the lock
REQUEST_LEVEL	VARCHAR2(9)	Requested level of the lock
RESOURCE_NAME1	VARCHAR2(30)	Resource name for the lock

Column	Datatype	Description
RESOURCE_NAME2	VARCHAR2(30)	Resource name for the lock
PID	NUMBER	Process identifier which holds the lock
TRANSACTION_ID0	NUMBER	Lower 4 bytes of the transaction identifier to which the lock belongs
TRANSACTION_ID1	NUMBER	Upper 4 bytes of the transaction identifier to which the lock belongs
GROUP_ID	NUMBER	Group identifier for the lock
OPEN_OPT_DEADLOCK	NUMBER	1 if DEADLOCK open option is set, otherwise 0
OPEN_OPT_PERSISTENT	NUMBER	1 if PERSISTENT open option is set, otherwise 0
OPEN_OPT_PROCESS_OWNED	NUMBER	1 if PROCESS_OWNED open option is set, otherwise 0
OPEN_OPT_NO_XID	NUMBER	1 if NO_XID open option is set, otherwise 0
CONVERT_OPT_GETVALUE	NUMBER	1 if GETVALUE convert option is set, otherwise 0
CONVERT_OPT_PUTVALUE	NUMBER	1 if PUTVALUE convert option is set, otherwise 0
CONVERT_OPT_NOVALUE	NUMBER	1 if NOVALUE convert option is set, otherwise 0
CONVERT_OPT_DUBVALUE	NUMBER	1 if DUBVALUE convert option is set, otherwise 0
CONVERT_OPT_NOQUEUE	NUMBER	1 if NOQUEUE convert option is set, otherwise 0
CONVERT_OPT_EXPRESS	NUMBER	1 if EXPRESS convert option is set, otherwise 0
CONVERT_OPT_NODEADLOCKWAIT	NUMBER	1 if NODEADLOCKWAIT convert option is set, otherwise 0
CONVERT_OPT_NODEADLOCKBLOCK	NUMBER	1 if NODEADLOCKBLOCK convert option is set, otherwise 0
WHICH_QUEUE	NUMBER	Which queue the lock is currently located. 0 for NULL queue; 1 for GRANTED queue; 2 for CONVERT queue.
STATE	VARCHAR2(64)	State of the lock as the owner sees it
AST_EVENT0	NUMBER	Last AST event
OWNER_NODE	NUMBER	Node identifier
BLOCKED	NUMBER	1 if this lock request is blocked by others, otherwise 0
BLOCKER	NUMBER	1 if this lock is blocking others, otherwise 0
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.261 V$GES_LATCH

V$GES_LATCH is deprecated.

> **See Also:**
>
> "V$LATCH" for statistics about GES latch performance

8.262 V$GES_RESOURCE

V$GES_RESOURCE is an Oracle Real Application Clusters view. It displays information of all resources currently known to the lock manager.

Column	Datatype	Description
RESP	RAW(4 | 8)	Resource pointer
RESOURCE_NAME	VARCHAR2(30)	Resource name in hexadecimal for the lock
ON_CONVERT_Q	NUMBER	1 if on convert queue, 0 otherwise
ON_GRANT_Q	NUMBER	1 if on granted queue, 0 otherwise
PERSISTENT_RES	NUMBER	1 if it is a persistent resource, 0 otherwise
MASTER_NODE	NUMBER	Primary node ID
NEXT_CVT_LEVEL	VARCHAR2(9)	Next lock level to convert on global convert queue
VALUE_BLK_STATE	VARCHAR2(32)	State of the value block
VALUE_BLK	VARCHAR2(64)	First 64 bytes of the value block
CACHE_LEVEL	NUMBER	Level at which the resource is cached (0, 1, or 2; 255 if not on cache)
PDBSCOPE	NUMBER	Indicates whether an enqueue is PDB-scoped (1) or not (0)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.263 V$GES_STATISTICS

V$GES_STATISTICS displays miscellaneous GES statistics.

Column	Datatype	Description
STATISTIC#	NUMBER	Statistic number
NAME	VARCHAR2(38)	Name of the statistic

Column	Datatype	Description
VALUE	NUMBER	Value associated with the statistic
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.264 V$GG_APPLY_COORDINATOR

V$GG_APPLY_COORDINATOR displays information about each GoldenGate apply process coordinator.

The coordinator for an apply process gets transactions from the apply process reader and passes them to apply servers. An apply process coordinator is a subcomponent of an apply process used by Oracle GoldenGate Integrated Replicat.

Column	Datatype	Description
SID	NUMBER	Session ID of the coordinator's session
SERIAL#	NUMBER	Serial number of the coordinator's session
STATE	VARCHAR2(21)	State of the coordinator: • INITIALIZING - Starting up • IDLE - Performing no work • APPLYING - Passing transactions to apply servers • SHUTTING DOWN CLEANLY - Stopping without an error • ABORTING - Stopping because of an apply error
APPLY#	NUMBER	Apply process number. An apply process coordinator is an Oracle background process, prefixed by ap.
APPLY_NAME	VARCHAR2(128)	Name of the apply process
TOTAL_APPLIED	NUMBER	Total number of transactions applied by the apply process since the apply process was last started
TOTAL_WAIT_DEPS	NUMBER	Number of times since the apply process was last started that an apply server waited to apply a logical change record (LCR) in a transaction until another apply server applied a transaction because of a dependency between the transactions
TOTAL_WAIT_COMMITS	NUMBER	Number of times since the apply process was last started that an apply server waited to commit a transaction until another apply server committed a transaction to serialize commits
TOTAL_ADMIN	NUMBER	Number of administrative jobs issued since the apply process was last started
TOTAL_ASSIGNED	NUMBER	Number of transactions assigned to apply servers since the apply process was last started
TOTAL_RECEIVED	NUMBER	Total number of transactions received by the coordinator process since the apply process was last started

Column	Datatype	Description
TOTAL_IGNORED	NUMBER	Number of transactions which were received by the coordinator but were ignored because they had been previously applied
TOTAL_ROLLBACKS	NUMBER	Number of transactions which were rolled back due to unexpected contention
TOTAL_ERRORS	NUMBER	Number of transactions applied by the apply process that resulted in an apply error since the apply process was last started
UNASSIGNED_COMPLETE_TXNS	NUMBER	Total number of complete transactions that the coordinator has not assigned to any apply servers
LWM_TIME	DATE	Time when the message with the lowest message number was recorded. The creation time of the message with the lowest message number was also recorded at this time.
LWM_MESSAGE_NUMBER	NUMBER	Number of the message corresponding to the low watermark. That is, messages with a commit message number less than or equal to this message number have definitely been applied, but some messages with a higher commit message number also may have been applied.
LWM_MESSAGE_CREATE_TIME	DATE	For captured messages, creation time at the source database of the message corresponding to the low watermark. For user-enqueued messages, time when the message corresponding to the low watermark was enqueued into the queue at the local database.
HWM_TIME	DATE	Time when the message with the highest message number was recorded. The creation time of the message with the highest message number was also recorded at this time.
HWM_MESSAGE_NUMBER	NUMBER	Number of the message corresponding to the high watermark. That is, no messages with a commit message number greater than this message number have been applied.
HWM_MESSAGE_CREATE_TIME	DATE	For captured messages, creation time at the source database of the message corresponding to the high watermark. For user-enqueued messages, time when the message corresponding to the high watermark was enqueued into the queue at the local database.
STARTUP_TIME	DATE	Time when the apply process was last started
ELAPSED_SCHEDULE_TIME	NUMBER	Time elapsed (in hundredths of a second) scheduling messages since the apply process was last started
ELAPSED_IDLE_TIME	NUMBER	Elapsed idle time
LWM_POSITION	RAW(64)	Position of the low-watermark LCR
HWM_POSITION	RAW(64)	Position of the high-watermark LCR
PROCESSED_MESSAGE_NUMBER	NUMBER	Message number currently processed by the apply coordinator
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
ACTIVE_SERVER_COUNT	NUMBER	Active server count

> **Note:**
>
> The ELAPSED_SCHEDULE_TIME column is only populated if the TIMED_STATISTICS initialization parameter is set to true, or if the STATISTICS_LEVEL initialization parameter is set to TYPICAL or ALL.

> **See Also:**
>
> - "TIMED_STATISTICS"
> - "STATISTICS_LEVEL"

8.265 V$GG_APPLY_READER

V$GG_APPLY_READER displays information about each GoldenGate apply reader.

The apply reader is a process which reads (dequeues) messages from the queue, computes message dependencies, and builds transactions. It passes the transactions on to the coordinator in commit order for assignment to the apply servers. An apply reader is a subcomponent of an apply process used by Oracle GoldenGate Integrated Replicat.

Column	Datatype	Description
SID	NUMBER	Session ID of the reader's session
SERIAL#	NUMBER	Serial number of the reader's session
APPLY#	NUMBER	Apply process number. An apply process is an Oracle background process, prefixed by ap.
APPLY_NAME	VARCHAR2(128)	Name of the apply process
STATE	VARCHAR2(36)	Shows the state of the apply reader and the hash server. The possible values include: • INITIALIZING - Starting up • IDLE - Performing no work • DEQUEUE MESSAGES - Dequeuing messages from the queue • SCHEDULE MESSAGES - Computing dependencies between messages and assembling messages into transactions • SPILLING - Spilling unapplied messages from memory to hard disk • PAUSED - WAITING FOR DDL TO COMPLETE - Waiting for a data definition language (DDL) logical change record (LCR) to be applied The state of the apply reader is displayed first, followed by the state of the hash server. A semicolon separates the apply reader state from the hash server state.
TOTAL_MESSAGES_DEQUEUED	NUMBER	Total number of messages dequeued since the apply process was last started
TOTAL_MESSAGES_SPILLED	NUMBER	Number of messages spilled by the reader since the apply process was last started

Column	Datatype	Description
DEQUEUE_TIME	DATE	Time when the last message was received
DEQUEUED_MESSAGE_CREATE_TIME	DATE	For captured messages, creation time at the source database of the last message received. For user-enqueued messages, time when the message was enqueued into the queue at the local database.
SGA_USED	NUMBER	Amount (in bytes) of SGA memory used by the apply process since it was last started
ELAPSED_DEQUEUE_TIME	NUMBER	Time elapsed (in hundredths of a second) dequeuing messages since the apply process was last started
ELAPSED_SCHEDULE_TIME	NUMBER	Time elapsed (in hundredths of a second) scheduling messages since the apply process was last started. Scheduling includes computing dependencies between messages and assembling messages into transactions.
ELAPSED_SPILL_TIME	NUMBER	Elapsed time (in hundredths of a second) spent spilling messages since the apply process was last started
SPILL_LWM_SCN	NUMBER	Spill low-watermark SCN
PROXY_SID	NUMBER	When the apply process uses combined capture and apply, the session ID of the propagation receiver that is responsible for direct communication between capture and apply. If the apply process does not use combined capture and apply, then this column is `0`.
PROXY_SERIAL	NUMBER	When the apply process uses combined capture and apply, the serial number of the propagation receiver that is responsible for direct communication between capture and apply. If the apply process does not use combined capture and apply, then this column is `0`.
PROXY_SPID	VARCHAR2(12)	When the apply process uses combined capture and apply, the process identification number of the propagation receiver that is responsible for direct communication between capture and apply. If the apply process does not use combined capture and apply, then this column is `0`.
BYTES_RECEIVED	NUMBER	When the apply process uses combined capture and apply, the number of bytes received by the apply process from the capture process since the apply process last started. If the apply process does not use combined capture and apply, then this column is not populated.
DEQUEUED_POSITION	RAW(64)	Dequeued position. This column is populated only for an apply process that is functioning as a GoldenGate inbound server.
SPILL_LWM_POSITION	RAW(64)	Spill low-watermark position. This column is populated only for an apply process that is functioning as a GoldenGate inbound server.
OLDEST_TRANSACTION_ID	VARCHAR2(128)	Oldest transaction ID
TOTAL_LCRS_WITH_DEP	NUMBER	Total number of LCRs with row-level dependencies since the apply process last started
TOTAL_LCRS_WITH_WMDEP	NUMBER	Total number of LCRs with watermark dependencies since the apply process last started. A watermark dependency occurs when an apply process must wait until the apply process's low watermark reaches a particular threshold.
TOTAL_IN_MEMORY_LCRS	NUMBER	Total number of LCRs currently in memory
SGA_ALLOCATED	NUMBER	The total amount of shared memory (in bytes) allocated from the GoldenGate pool for the apply process since the apply process last started

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> The ELAPSED_SCHEDULE_TIME column is only populated if the TIMED_STATISTICS initialization parameter is set to true, or if the STATISTICS_LEVEL initialization parameter is set to TYPICAL or ALL.

> **See Also:**
>
> - "TIMED_STATISTICS"
> - "STATISTICS_LEVEL"

8.266 V$GG_APPLY_RECEIVER

V$GG_APPLY_RECEIVER displays information about the message receiver of the Replicat process.

The values are reset to zero when the database (or instance in an Oracle Real Application Clusters (Oracle RAC) environment) restarts and when the Replicat process is stopped.

Column	Datatype	Description
SID	NUMBER	Session ID of the apply receiver
SERIAL#	NUMBER	Serial number of the apply receiver
APPLY_NAME	VARCHAR2(128)	Name of the apply process
STARTUP_TIME	DATE	Startup time of the apply process
SOURCE_DATABASE_NAME	VARCHAR2(128)	Name of the source database
ACKNOWLEDGEMENT	NUMBER	acknowledgment of the messages received by the receiver
LAST_RECEIVED_MSG	NUMBER	Last received message
TOTAL_MESSAGES_RECEIVED	NUMBER	Total number of messages received
TOTAL_AVAILABLE_MESSAGES	NUMBER	Number of available messages

Column	Datatype	Description
STATE	VARCHAR2(46)	State of the apply receiver: • Initializing • Sending unapplied txns • Waiting for message from client • Receiving LCRs • Evaluating rules • Enqueueing LCRS • Waiting for memory • Waiting for apply to read • Waiting for message from Replicat • Waiting for Replicat flush request to complete • Waiting for Replicat commit to complete
LAST_RECEIVED_MSG_POSITION	VARCHAR2(64)	Last received message position
ACKNOWLEDGEMENT_POSITION	VARCHAR2(64)	acknowledgment position of the messages received by the receiver. Corresponds to ACKNOWLEDGEMENT, except the value is in position rather than SCN.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
OS_PROCESS_ID	VARCHAR2(12)	The OS process ID of the apply receiver process
CURRENT_POSITION	VARCHAR2(81)	The trail position of the current record processed by the apply receiver
TOTAL_TRANSACTIONS	NUMBER	The total number of transactions processed by the apply receiver
TOTAL_COMMITS	NUMBER	The total number of commits executed by the apply receiver
TOTAL_ERRORS	NUMBER	The total number of errors encountered by the apply receiver

8.267 V$GG_APPLY_SERVER

V$GG_APPLY_SERVER displays information about each GoldenGate apply server and its activities.

An apply server receives messages from the apply coordinator for an apply process. For each message received, an apply server either applies the message or sends the message to the appropriate apply handler. An apply server is a subcomponent of an apply process used by Oracle GoldenGate Integrated Replicat.

Column	Datatype	Description
SID	NUMBER	Session ID of the apply server's session
SERIAL#	NUMBER	Serial number of the apply server's session
APPLY#	NUMBER	Apply process number. An apply process is an Oracle background process, prefixed by ap.

Column	Datatype	Description
APPLY_NAME	VARCHAR2(128)	Name of the apply process
SERVER_ID	NUMBER	Parallel execution server number of the apply server
STATE	VARCHAR2(20)	State of the apply server: • INITIALIZING - Starting up • IDLE - Performing no work • RECORD LOW-WATERMARK - Performing an administrative job that maintains information about the apply progress, which is used in the ALL_APPLY_PROGRESS and DBA_APPLY_PROGRESS data dictionary views • ADD PARTITION - Performing an administrative job that adds a partition that is used for recording information about in-progress transactions • DROP PARTITION - Performing an administrative job that purges rows that were used to record information about in-progress transactions • EXECUTE TRANSACTION - Applying a transaction • WAIT COMMIT - Waiting to commit a transaction until all other transactions with a lower commit SCN are applied. This state is possible only if the COMMIT_SERIALIZATION apply process parameter is set to a value other than DEPENDENT_TRANSACTIONS and the PARALLELISM apply process parameter is set to a value greater than 1. • WAIT DEPENDENCY - Waiting to apply a logical change record (LCR) in a transaction until another transaction, on which it has a dependency, is applied. This state is possible only if the PARALLELISM apply process parameter is set to a value greater than 1. • ROLLBACK TRANSACTION - Rolling back a transaction • TRANSACTION CLEANUP - Cleaning up an applied transaction, which includes removing LCRs from the apply process's queue • WAIT FOR CLIENT - Waiting for an XStream client application to request more LCRs • WAIT FOR NEXT CHUNK - Waiting for the next set of LCRs for a large transaction
XIDUSN	NUMBER	Transaction ID undo segment number of the transaction currently being applied
XIDSLT	NUMBER	Transaction ID slot number of the transaction currently being applied
XIDSQN	NUMBER	Transaction ID sequence number of the transaction currently being applied
COMMITSCN	NUMBER	Commit system change number (SCN) of the transaction currently being applied
DEP_XIDUSN	NUMBER	Transaction ID undo segment number of a transaction on which the transaction being applied by this apply server depends
DEP_XIDSLT	NUMBER	Transaction ID slot number of a transaction on which the transaction being applied by this apply server depends
DEP_XIDSQN	NUMBER	Transaction ID sequence number of a transaction on which the transaction being applied by this apply server depends

Column	Datatype	Description
DEP_COMMITSCN	NUMBER	Commit system change number (SCN) of the transaction on which this apply server depends
MESSAGE_SEQUENCE	NUMBER	Number of the current message being applied by the apply server. This value is reset to 1 at the beginning of each transaction.
TOTAL_ASSIGNED	NUMBER	Total number of transactions assigned to the apply server since the apply process was last started
TOTAL_ADMIN	NUMBER	Total number of administrative jobs done by the apply server since the apply process was last started. See the STATE information in this view for the types of administrative jobs.
TOTAL_ROLLBACKS	NUMBER	Number of transactions assigned to this server which were rolled back
TOTAL_MESSAGES_APPLIED	NUMBER	Total number of messages applied by this apply server since the apply process was last started
APPLY_TIME	DATE	Time the last message was applied
ELAPSED_APPLY_TIME	NUMBER	Time elapsed (in hundredths of a second) applying messages since the apply process was last started
COMMIT_POSITION	RAW(64)	Commit position of the transaction. This column is populated only for an apply process that is functioning as a GoldenGate Integrated Replicat.
DEP_COMMIT_POSITION	RAW(64)	Commit position of the transaction the worker depends on. This column is populated only for an apply process that is functioning as a GoldenGate inbound server.
LAST_APPLY_POSITION	RAW(64)	For inbound servers, the position of the last message applied; for outbound servers, the position of the last message sent to the XStream client application. This column is populated only for an apply process that is functioning as a GoldenGate outbound server or inbound server.
TRANSACTION_ID	VARCHAR2(128)	Transaction ID that the worker is applying. This column is populated only for an apply process that is functioning as a GoldenGate inbound server.
DEP_TRANSACTION_ID	VARCHAR2(128)	Transaction ID of the transaction the worker depends on. This column is populated only for an apply process that is functioning as a GoldenGate inbound server.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
TOTAL_LCRS_RETRIED	NUMBER	Total number of LCRs retried by this server
LCR_RETRY_ITERATION	NUMBER	Retry iteration for this transaction by this server
TOTAL_TXNS_RETRIED	NUMBER	Total transactions retried by this server
TXN_RETRY_ITERATION	NUMBER	Retry iteration for this transaction by this server
TOTAL_TXNS_RECORDED	NUMBER	Total transactions recorded in error queue by this server

Note:

The ELAPSED_SCHEDULE_TIME column is only populated if the TIMED_STATISTICS initialization parameter is set to true, or if the STATISTICS_LEVEL initialization parameter is set to TYPICAL or ALL.

See Also:

- "TIMED_STATISTICS"
- "STATISTICS_LEVEL"

8.268 V$GLOBAL_BLOCKED_LOCKS

V$GLOBAL_BLOCKED_LOCKS displays global blocked locks.

Column	Datatype	Description
ADDR	RAW(4 | 8)	Address of lock state object
KADDR	RAW(4 | 8)	Address of lock
SID	NUMBER	Identifier of session holding the lock (number)
TYPE	VARCHAR2(2)	Resource type (char)
ID1	NUMBER	Resource identifier #1 (number)
ID2	NUMBER	Resource identifier #2 (number)
LMODE	NUMBER	Lock mode held (number)
REQUEST	NUMBER	Lock mode requested (number)
CTIME	NUMBER	Time since current mode was granted
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.269 V$GLOBAL_TRANSACTION

V$GLOBAL_TRANSACTION displays information on the currently active global transactions.

Column	Datatype	Description
FORMATID	NUMBER	Format identifier of the global transaction
GLOBALID	RAW(64)	Global transaction identifier of the global transaction
BRANCHID	RAW(64)	Branch qualifier of the global transaction

Column	Datatype	Description
BRANCHES	NUMBER	Total number of branches in the global transaction
REFCOUNT	NUMBER	Number of siblings for the global transaction (must be the same as branches)
PREPARECOUNT	NUMBER	Number of branches of the global transaction that have prepared
STATE	VARCHAR2(38)	State of the branch of the global transaction: • ACTIVE • COLLECTING • FINALIZED • FAILED • RECOVERING • UNASSOCIATED • FORGOTTEN • READY FOR RECOVERY • NO-READONLY FAILED • SIBLING INFO WRITTEN • [ORACLE COORDINATED]ACTIVE • [ORACLE COORDINATED]COLLECTING • [ORACLE COORDINATED]FINALIZED • [ORACLE COORDINATED]FAILED • [ORACLE COORDINATED]RECOVERING • [ORACLE COORDINATED]UNASSOCIATED • [ORACLE COORDINATED]FORGOTTEN • [ORACLE COORDINATED]READY FOR RECOVERY • [ORACLE COORDINATED]NO-READONLY FAILED • [MULTINODE]ACTIVE • [MULTINODE]COLLECTING • [MULTINODE]FINALIZED • [MULTINODE]FAILED • [MULTINODE]RECOVERING • [MULTINODE]UNASSOCIATED • [MULTINODE]FORGOTTEN • [MULTINODE]READY FOR RECOVERY • [MULTINODE]NO-READONLY FAILED • [MULTINODE]SIBLING INFO WRITTEN • COMBINATION
FLAGS	NUMBER	The numeric representation of the state
COUPLING	VARCHAR2(15)	Indicates whether the branches are free (FREE), loosely coupled (LOOSELY COUPLED), or tightly coupled (TIGHTLY COUPLED)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.270 V$GOLDENGATE_CAPABILITIES

V$GOLDENGATE_CAPABILITIES displays information about the usage of various Oracle GoldenGate features, as well as database features used by Oracle GoldenGate.

Column	Datatype	Description
NAME	VARCHAR2(22)	Feature name. Possible values: • AUTOCDR • DBENCRYPTION • DDLTRIGGEROPTIMIZATION • DELETECASCADEHINT • GGSESSION • PROCREPLICATION • SUPPLEMENTALLOG • TRANSIENTDUPLICATE • TRIGGERSUPPRESSION
COUNT	NUMBER	Number of times the feature has been used since instance startup
LAST_USED	DATE	Date on which the feature was last used
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.271 V$GOLDENGATE_CAPTURE

V$GOLDENGATE_CAPTURE displays information about each capture process that sends LCRs to an Oracle GoldenGate outbound server.

Column	Datatype	Description
SID	NUMBER	Session identifier of the capture process
SERIAL#	NUMBER	Session serial number of the capture process session
CAPTURE#	NUMBER	Capture process number. A capture process is an Oracle background process prefixed by cp
CAPTURE_NAME	VARCHAR2(128)	Name of the capture process
LOGMINER_ID	NUMBER	Session ID of the Oracle LogMiner session associated with the capture process
STARTUP_TIME	DATE	Time when the capture process was last started

Column	Datatype	Description
STATE	VARCHAR2(589)	State of the capture process and state of the network. The two states are separated by a semicolon. The possible values are: • INITIALIZING - Starting up. • WAITING FOR DICTIONARY REDO - Waiting for redo log files containing the dictionary build related to the first SCN to be added to the capture process session. A capture process cannot begin to scan the redo log files until all of the log files containing the dictionary build have been added. • DICTIONARY INITIALIZATION - Processing a dictionary build. • MINING (PROCESSED SCN = *scn_value*) - Mining a dictionary build at the SCN *scn_value*. • LOADING (step *X* of *Y*) - Processing information from a dictionary build and currently at step *X* in a process that involves *Y* steps, where *X* and *Y* are numbers. • CAPTURING CHANGES - Scanning the redo log for changes that satisfy the capture process rule sets. • WAITING FOR REDO - Waiting for new redo log files to be added to the capture process session. The capture process has finished processing all of the redo log files added to its session. This state is possible if there is no activity at a source database. For a downstream capture process, this state is possible if the capture process is waiting for new log files to be added to its session. • EVALUATING RULE - Evaluating a change against a capture process rule set. • CREATING LCR - Converting a change into an LCR. • ENQUEUING MESSAGE - Enqueuing an LCR that satisfies the capture process rule sets into the capture process queue. • PAUSED FOR FLOW CONTROL - Unable to enqueue LCRs either because of low memory or because propagations and outbound servers are consuming messages slower than the capture process is creating them. This state indicates flow control that is used to reduce spilling of captured LCRs when propagation or apply has fallen behind or is unavailable. • WAITING FOR THE BUFFERED QUEUE TO SHRINK - Waiting for the buffered queue to change to a smaller size. The buffered queue shrinks when there is a memory limitation or when an administrator reduces its size. • WAITING FOR *n* SUBSCRIBER(S) INITIALIZING - Waiting for outbound servers that receive LCRs from the capture process to start, where *n* is the number of apply processes. • WAITING FOR TRANSACTION - Waiting for LogMiner to provide more transactions. • WAITING FOR INACTIVE DEQUEUERS - Waiting for the capture process's queue subscribers to start. The capture process stops enqueuing LCRs if there are no active subscribers to the queue. • SUSPENDED FOR AUTO SPLIT/MERGE - Waiting for a merge operation to complete. • SHUTTING DOWN - Stopping. • ABORTING - Terminating.
TOTAL_PREFILTER_DISCARDED	NUMBER	Total number of prefiltered messages discarded

Column	Datatype	Description
TOTAL_PREFILTER_KEPT	NUMBER	Total number of prefiltered messages kept
TOTAL_PREFILTER_EVALUATIONS	NUMBER	Total number of prefilter evaluations
TOTAL_MESSAGES_CAPTURED	NUMBER	Total number of redo entries passed by LogMiner to the capture process for detailed rule evaluation since the capture process last started. A capture process converts a redo entry into a message and performs detailed rule evaluation on the message when capture process prefiltering cannot discard the change.
CAPTURE_TIME	DATE	Time when the most recent message was captured
CAPTURE_MESSAGE_NUMBER	NUMBER	Number of the most recently captured message
CAPTURE_MESSAGE_CREATE_TIME	DATE	Creation time of the most recently captured message
TOTAL_MESSAGES_CREATED	NUMBER	Count associated with ELAPSED_LCR_TIME to calculate rate
TOTAL_FULL_EVALUATIONS	NUMBER	Count associated with ELAPSED_RULE_TIME to calculate rate
TOTAL_MESSAGES_ENQUEUED	NUMBER	Total number of messages enqueued since the capture process was last started
ENQUEUE_TIME	DATE	Time when the last message was enqueued
ENQUEUE_MESSAGE_NUMBER	NUMBER	Number of the last enqueued message
ENQUEUE_MESSAGE_CREATE_TIME	DATE	Creation time of the last enqueued message
AVAILABLE_MESSAGE_NUMBER	NUMBER	For local capture, the last redo SCN flushed to the log files. For downstream capture, the last SCN added to LogMiner through the archived redo log files.
AVAILABLE_MESSAGE_CREATE_TIME	DATE	For local capture, the time the SCN was written to the log file. For downstream capture, the time the most recent archived redo log file (containing the most recent SCN) was added to LogMiner.
ELAPSED_CAPTURE_TIME	NUMBER	Elapsed time (in hundredths of a second) scanning for changes in the redo log since the capture process was last started
ELAPSED_RULE_TIME	NUMBER	Elapsed time (in hundredths of a second) evaluating rules since the capture process was last started
ELAPSED_ENQUEUE_TIME	NUMBER	Elapsed time (in hundredths of a second) enqueuing messages since the capture process was last started
ELAPSED_LCR_TIME	NUMBER	Elapsed time (in hundredths of a second) creating LCRs since the capture process was last started
ELAPSED_REDO_WAIT_TIME	NUMBER	Elapsed time (in hundredths of a second) spent by the capture process in the WAITING FOR REDO state
ELAPSED_PAUSE_TIME	NUMBER	Elapsed flow control pause time (in hundredths of a second)
STATE_CHANGED_TIME	DATE	Time at which the state of the capture process changed
SGA_USED	NUMBER	The total amount of shared memory used (in bytes) by the capture process
SGA_ALLOCATED	NUMBER	The total amount of shared memory (in bytes) allocated from the Streams pool for the capture process
BYTES_OF_REDO_MINED	VARCHAR2(64)	The total amount of redo data mined (in bytes) since the capture process last started
SESSION_RESTART_SCN	VARCHAR2(64)	The SCN from which the capture process started mining redo data when it was last started

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
SPID	VARCHAR2(12)	Operating system process identifier of the capture process
EXTRACT_NAME	VARCHAR2(128)	Name of the extract process
SERVER_SID	NUMBER	Session ID of the capture server
SERVER_SERIAL#	NUMBER	Session serial number of the capture server
SERVER_SPID	VARCHAR2(12)	Operating system process identifier of the capture server
TOTAL_MESSAGES_SENT	NUMBER	Total number of LCRs sent by the capture process to the GoldenGate extract process since the last time the extract attached to the capture
SEND_TIME	DATE	Time the last LCR was sent by the capture process to the extract process
LAST_SENT_MESSAGE_NUMBER	NUMBER	Message number of the last LCR sent by the capture process to the extract process
LAST_SENT_MESSAGE_CREATE_TIME	DATE	Creation time at the source database of the last LCR sent by the capture process to the extract process
ELAPSED_SEND_TIME	NUMBER	Time elapsed (in hundredths of a second) sending LCRs to the extract process since the last time the extract process attached to the capture process
BYTES_SENT	NUMBER	Total number of bytes sent by the capture process to the extract process since the last time the extract process attached to the capture process

8.272 V$GOLDENGATE_MESSAGE_TRACKING

V$GOLDENGATE_MESSAGE_TRACKING displays information about LCRs tracked through the stream that are processed by Oracle GoldenGate components.

You can track an LCR through a stream using one of the following methods:

- Set the message_tracking_frequency apply process parameter to 1 or another relatively low value via the Oracle GoldenGate DBOPTIONS INTEGRATEDPARAMS parameter.
- Use the DBMS_XSTREAM_ADM.SET_MESSAGE_TRACKING procedure to specify a tracking label that becomes part of each LCR generated by the current session.

  When the actions parameter in the DBMS_XSTREAM_ADM.SET_MESSAGE_TRACKING procedure is set to DBMS_XSTREAM_ADM.ACTION_MEMORY, information about the LCRs is tracked in memory, and this view is populated with information about the LCRs. Currently, DBMS_XSTREAM_ADM.ACTION_MEMORY is the only valid setting for the actions parameter in the procedure.

Column	Datatype	Description
TRACKING_LABEL	VARCHAR2(128)	User-specified tracking label
TAG	RAW(128)	First 128 bytes of the tag of the LCR
COMPONENT_NAME	VARCHAR2(128)	Name of the component that processed the LCR
COMPONENT_TYPE	VARCHAR2(128)	Type of the component that processed the LCR
ACTION	VARCHAR2(50)	Action performed on the LCR
ACTION_DETAILS	VARCHAR2(312)	Details of the action
TIMESTAMP	TIMESTAMP(9) WITH TIME ZONE	Time when the action was performed
MESSAGE_CREATION_TIME	DATE	Time when the message was created
MESSAGE_NUMBER	NUMBER	SCN of the message
TRACKING_ID	RAW(16)	Globally unique OID of the LCR
SOURCE_DATABASE_NAME	VARCHAR2(128)	Name of the source database
OBJECT_OWNER	VARCHAR2(128)	Owner of the object
OBJECT_NAME	VARCHAR2(128)	Name of the object
XID	VARCHAR2(128)	Transaction ID
COMMAND_TYPE	VARCHAR2(128)	Command type of the LCR
MESSAGE_POSITION	RAW(64)	Position of the message
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Database PL/SQL Packages and Types Reference for more information about the DBMS_XSTREAM_ADM.SET_MESSAGE_TRACKING procedure

8.273 V$GOLDENGATE_PROCEDURE_STATS

V$GOLDENGATE_PROCEDURE_STATS displays procedural replication statistics processed by each Oracle GoldenGate apply server.

Column	Datatype	Description
APPLY_NAME	VARCHAR2(128)	Name of the apply process
SERVER_ID	NUMBER	Parallel apply server worker ID
PROCEDURE_OWNER	VARCHAR2(128)	Owner of the replicated procedure
PACKAGE_NAME	VARCHAR2(128)	Replicated procedure package

Column	Datatype	Description
PROCEDURE_NAME	VARCHAR2(128)	Replicated procedure name
LAST_UPDATE	DATE	Time of the last update of the statistics
TOTAL_EXECUTIONS	NUMBER	Number of executions of the procedure by this apply server
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.274 V$GOLDENGATE_TABLE_STATS

V$GOLDENGATE_TABLE_STATS displays table statistics for all the tables used by each Oracle GoldenGate apply server.

Column	Datatype	Description
APPLY_NAME	VARCHAR2(128)	Name of the apply process
SERVER_ID	NUMBER	Parallel apply server worker ID
SOURCE_TABLE_OWNER	VARCHAR2(128)	Source owner of the captured or replicated table
SOURCE_TABLE_NAME	VARCHAR2(128)	Source name of the captured or replicated table
DESTINATION_TABLE_OWNER	VARCHAR2(128)	Target owner of the captured or replicated table
DESTINATION_TABLE_NAME	VARCHAR2(30)	Target name of the captured or replicated table
LAST_UPDATE	DATE	Time of the last update of the statistics
TOTAL_INSERTS	NUMBER	Number of insert operations on this table processed by this apply server
TOTAL_UPDATES	NUMBER	Number of update operations on this table processed by this apply server
TOTAL_DELETES	NUMBER	Number of delete operations on this table processed by this apply server
INSERT_COLLISIONS	NUMBER	Number of insert collisions on this table encountered by this apply server
UPDATE_COLLISIONS	NUMBER	Number of update collisions on this table encountered by this apply server
DELETE_COLLISIONS	NUMBER	Number of delete collisions on this table encountered by this apply server
REPERROR_RECORDS	NUMBER	Number of change records that resulted in an error that were recorded on this table by this apply server
REPERROR_IGNORES	NUMBER	Number of change records that resulted in an error that were ignored on this table by this apply server
WAIT_DEPENDENCIES	NUMBER	Number of waits for this table due to dependency

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
CDR_INSERT_ROW_EXISTS	NUMBER	Number of conflicts where an insert gets an ORA-00001 error
CDR_UPDATE_ROW_EXISTS	NUMBER	Number of conflicts where an update gets an ORA-26786 error
CDR_UPDATE_ROW_MISSING	NUMBER	Number of conflicts where an update gets an ORA-26787 error
CDR_DELETE_ROW_EXISTS	NUMBER	Number of conflicts where a delete gets an ORA-26786 error
CDR_DELETE_ROW_MISSING	NUMBER	Number of conflicts where a delete gets an ORA-26787 error
CDR_SUCCESSFUL_RESOLUTIONS	NUMBER	Number of successfully resolved conflicts
CDR_FAILED_RESOLUTIONS	NUMBER	Number of conflicts that could not be resolved due to an error during resolution
LOB_OPERATIONS	NUMBER	The number of LOB updates (LOB writes, LOB trims, and LOB erases) applied by the inbound server.

8.275 V$GOLDENGATE_TRANSACTION

V$GOLDENGATE_TRANSACTION displays information about transactions that are being processed by Oracle GoldenGate capture processes, outbound servers, and inbound servers.

This view can identify long running transactions and display how many LCRs are being processed in each transaction. This view only contains information about captured LCRs. It does not contain information about user-enqueued LCRs or user messages.

This view only shows information about LCRs that are being processed because they satisfied the rule sets for the component at the time of the query. For capture processes, this view only shows information about changes in transactions that the capture process has converted into LCRs. It does not show information about all the active transactions present in the redo log.

For outbound servers, this view only shows information about LCRs that the outbound server has dequeued. It does not show information about LCRs in the outbound server's queue. For outbound servers, information about a transaction remains in the view until the transaction is sent to the Oracle GoldenGate client application.

For inbound servers, information about a transaction remains in the view until the transaction commits or until the entire transaction is rolled back.

Column	Datatype	Description
COMPONENT_NAME	VARCHAR2(138)	Name of the component

Column	Datatype	Description
COMPONENT_TYPE	VARCHAR2(20)	Type of component • CAPTURE - Capture process • APPLY - Apply reader subcomponent in an outbound server or inbound server • PROPAGATION_SENDER - Propagation sender that sends LCRs from a capture process to an outbound server
XIDUSN	NUMBER	Transaction ID undo segment number of the transaction
XIDSLT	NUMBER	Transaction ID slot number of the transaction
XIDSQN	NUMBER	Transaction ID sequence number of the transaction
BATCH_XIDUSN	NUMBER	Transaction ID undo segment number of the batch parent transaction. When using BATCHSQL mode in Oracle GoldenGate Integrated Replicat the BATCH_XID columns identify the parent transaction of the batch the current transaction belongs to. The parent transaction is the first transaction of each batch. This column is populated only if COMPONENT_TYPE is APPLY and BATCHSQL mode is enabled.
BATCH_XIDSLT	NUMBER	Transaction ID slot number of the batch parent transaction. When using BATCHSQL mode in Oracle GoldenGate Integrated Replicat the BATCH_XID columns identify the parent transaction of the batch the current transaction belongs to. The parent transaction is the first transaction of each batch. This column is populated only if COMPONENT_TYPE is APPLY and BATCHSQL mode is enabled.
BATCH_XIDSQN	NUMBER	Transaction ID sequence number of the batch parent transaction. When using BATCHSQL mode in Oracle GoldenGate Integrated Replicat the BATCH_XID columns identify the parent transaction of the batch the current transaction belongs to. The parent transaction is the first transaction of each batch. This column is populated only if COMPONENT_TYPE is APPLY and BATCHSQL mode is enabled.
CUMULATIVE_MESSAGE_COUNT	NUMBER	Number of LCRs processed in the transaction. If a component is restarted while the transaction is being processed, then this column shows the number of LCRs processed in the transaction since the component was started.
TOTAL_MESSAGE_COUNT	NUMBER	Total number of LCRs processed in the transaction by an outbound server or inbound server. This column does not pertain to capture processes.
FIRST_MESSAGE_TIME	DATE	Time stamp of the first LCR processed in the transaction. If a capture process is restarted while the transaction is being processed, then this column shows the time stamp of the first LCR processed after the capture process was started.
FIRST_MESSAGE_NUMBER	NUMBER	SCN of the first message in the transaction. If a capture process is restarted while the transaction is being processed, then this column shows the SCN of the first message processed after the capture process was started.
LAST_MESSAGE_TIME	DATE	Time stamp of the last LCR processed in the transaction
LAST_MESSAGE_NUMBER	NUMBER	SCN of the most recent message encountered for the transaction

Column	Datatype	Description
FIRST_MESSAGE_POSITION	RAW(64)	Position of the first message seen by an XStream inbound server This column is populated only for an apply process that is functioning as an Oracle GoldenGate inbound server.
LAST_MESSAGE_POSITION	RAW(64)	Position of the last message seen by an Oracle GoldenGate inbound server This column is populated only for an apply process that is functioning as an Oracle GoldenGate inbound server.
TRANSACTION_ID	VARCHAR2(128)	Transaction ID for an Oracle GoldenGate inbound server This column is populated only for an apply process that is functioning as an Oracle GoldenGate inbound server.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.276 V$HANG_INFO

V$HANG_INFO displays information about hangs found on the cluster.

A hang can be an open wait chain or closed wait chain (cycle or deadlock). A wait chain is a series of sessions that are blocking one another. Each row represents a hang and describes how severe the hang is. This view also includes the victim or final blocker of the hang.

Column	Datatype	Description
HANG_ID	NUMBER	A number identifying the hang
HANG_CHAIN_SESSIONS	NUMBER	Indicates how many sessions are in the main wait chain of the hang
TOTAL_HUNG_SESSIONS	NUMBER	Indicates how many total sessions are affected by the hang, including the main wait chain and any wait chains branching off of the main wait chain
HANG_TYPE	VARCHAR2(18)	Is set to Hang if this is an open wait chain or Deadlock if this is a cycle or closed wait chain

Column	Datatype	Description
HANG_STATUS	VARCHAR2(20)	Status of the hang. Possible values: • Invalid - The hang is about to be removed because its hung status has become in doubt • Pending Resolution - The hang or deadlock has been marked for resolution and will be resolved shortly • Reconfiguration - A reconfiguration occurred and the hang or deadlock must be re-detected and verified before any action can be taken toward resolution • Requires Verification - The hang is about to be verified to confirm if its sessions are still hung • Resolved - The hang or deadlock was resolved by terminating the final blocker (or root) or, if necessary, by terminating the instance • Self-Resolved - The hang was detected but resolved on its own without Blocker Resolver intervention • Unresolvable - The hang was determined to be a special case that is not resolvable • Valid - The hang or deadlock was detected but not yet verified • Verified Hung - The hang has been verified and a decision will be made soon on whether the hang will be resolved or ignored • Victim Selected - A victim has been selected. If the hang is marked for resolution, the victim will be terminated.
HANG_CREATE_TIME	VARCHAR2(20)	Date and time that the hang was detected
HANG_RESOLVE_TIME	VARCHAR2(20)	Time that the hang may be automatically resolved
IGNORED_HANG	VARCHAR2(1)	Y - Hang was ignored and will not be automatically resolved at this time N - The hang has not yet been verified
RESOLUTION_ATTEMPTED	VARCHAR2(1)	Y - An attempt was made to resolve the hang N - No attempt was made to resolve the hang
GLOBAL_HANG	VARCHAR2(1)	Y - The hang spans multiple nodes in the cluster N - All of the sessions in the hang reside on a single instance
ESCALATED_HANG	VARCHAR2(1)	Y - An attempt was made to resolve the hang but was unsuccessful, and the hang is becoming more severe. Another resolution attempt will be made. N - The first resolution attempt was successful and it was not necessary to escalate the hang to a higher resolution level.
RESOLUTION_STATUS	VARCHAR2(45)	Contains the reason why the hang was resolved or ignored
VICTIM_INSTANCE	NUMBER	Instance number of the instance on which the victim or final blocker session resides
VICTIM_SESSION_ID	NUMBER	Victim or final blocker's Oracle session ID
VICTIM_SERIAL#	NUMBER	Victim or final blocker's Oracle session serial number
VICTIM_OSPID	VARCHAR2(24)	Victim or final blocker's operating system process ID
FATAL_BACKGROUND	VARCHAR2(1)	Y - Victim or final blocker is a critical background process N - Victim or final blocker is not a critical background process
PNAME	VARCHAR2(5)	Name of the victim or final blocker process

Column	Datatype	Description
VICTIM_PDB_ID	NUMBER	Victim or final blocker's container ID or PDB ID
WAIT_EVENT_TEXT	VARCHAR2(64)	Resource or event for which the victim or final blocker is waiting; set to `not in a wait` if the session is not waiting on a resource
VICTIM_QOS_PC_RANK	VARCHAR2(12)	Oracle Database Quality of Service (QoS) Management Performance Class rank of the victim or final blocker of the hang.
VICTIM_QOS_PC_ITT	NUMBER	Oracle Database QoS Management Performance Class In-Trouble Threshold of the victim or final blocker of the hang
VICTIM_QOS_PC_RTT	NUMBER	Oracle Database QoS Management Performance Class Root Termination allowed Threshold of the victim or final blocker of the hang
VICTIM_QOS_PC_KEY	NUMBER	Oracle Database QoS Management Performance Class Key of the victim or final blocker of the hang
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$HANG_SESSION_INFO"
- "V$HANG_STATISTICS"
- "DBA_BLOCKER_RESOLVER_PARAMETERS"

8.277 V$HANG_SESSION_INFO

`V$HANG_SESSION_INFO` displays information about sessions involved in hangs described by `V$HANG_INFO`.

Each row with the same `HANG_ID` describes a session that is in the hang wait chain described by the row with the same `HANG_ID` in `V$HANG_INFO`. This session is blocked by the victim or final blocker of that hang.

Column	Datatype	Description
HANG_ID	NUMBER	A number identifying the hang including this session. This column can be used to join `V$HANG_INFO` with `V$HANG_SESSION_INFO`.
INSTANCE	NUMBER	Instance number of the instance on which this session resides
SID	NUMBER	Oracle session ID of this session
SERIAL#	NUMBER	Oracle session serial number of this session
OSPID	VARCHAR2(24)	Operating system process ID of this session

Column	Datatype	Description
FATAL_BACKGROUND	VARCHAR2(1)	Y - Session is a critical background process N - Session is not a critical background process
ROOT	VARCHAR2(1)	Y - This session is the victim or final blocker of the hang N - This session is not the victim or final blocker of the hang
PNAME	VARCHAR2(5)	Name of the victim or final blocker process
PDB_ID	NUMBER	Oracle session's container ID or PDB ID
WAIT_EVENT_TEXT	VARCHAR2(64)	Resource or event for which this session is waiting; set to `not in a wait` if the session is not waiting on a resource
WAIT_TIME	NUMBER	Time spent in wait for this session (in seconds). If the value of `WAIT_EVENT_TEXT` is `not in a wait`, then this column returns the number of seconds since the last wait.
QOS_PC_RANK	VARCHAR2(12)	Session's Oracle Database Quality of Service (QoS) Management Performance Class rank
QOS_PC_ITT	NUMBER	Session's Oracle Database Quality of Service (QoS) Management Performance Class In-Trouble Threshold
QOS_PC_RTT	NUMBER	Session's Oracle Database Quality of Service (QoS) Management Performance Class Root Termination allowed Threshold
QOS_PC_KEY	NUMBER	Session's Oracle Database Quality of Service (QoS) Management Performance Class Key
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$HANG_INFO"
- "V$HANG_STATISTICS"
- "DBA_BLOCKER_RESOLVER_PARAMETERS"

8.278 V$HANG_STATISTICS

`V$HANG_STATISTICS` displays statistics about hangs found on the cluster.

Column	Datatype	Description
STATISTIC#	NUMBER	Statistic number
NAME	VARCHAR2(45)	Name of the statistic
VALUE	NUMBER	Value associated with the statistic

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$HANG_INFO"
- "V$HANG_SESSION_INFO"
- "DBA_BLOCKER_RESOLVER_PARAMETERS"

8.279 V$HEAT_MAP_SEGMENT

V$HEAT_MAP_SEGMENT displays real-time segment access information.

Column	Datatype	Description
OBJECT_NAME	VARCHAR2(128)	Name of the object
SUBOBJECT_NAME	VARCHAR2(128)	Name of the subobject
OBJ#	NUMBER	Object number
DATAOBJ#	NUMBER	Data object number
TS#	NUMBER	ID of the tablespace containing the segment whose heat map is tracked
TRACK_TIME	DATE	Timestamp of current activity tracking
SEGMENT_WRITE	VARCHAR2(3)	Indicates whether the segment has write access: (YES or NO)
SEGMENT_READ	VARCHAR2(3)	Indicates whether the segment has read access: (YES or NO)
FULL_SCAN	VARCHAR2(3)	Indicates whether the segment has full table scan: (YES or NO)
LOOKUP_SCAN	VARCHAR2(3)	Indicates whether the segment has lookup scan: (YES or NO)
N_SEGMENT_WRITE	NUMBER	Number of segment writes
N_FULL_SCAN	NUMBER	Number of table scans
N_LOOKUP_SCAN	NUMBER	Number of lookup scans

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "ALL_HEAT_MAP_SEGMENT"

8.280 V$HM_CHECK

V$HM_CHECK displays information about all the checks registered with Health Monitor. Each check is uniquely identified by a name or an ID.

Column	Datatype	Description
ID	NUMBER	Health check ID
NAME	VARCHAR2(64)	Health check name
NAME_NLS	VARCHAR2(1024)	Internationalized names of the health checks
CLSID	NUMBER	Class ID to which this check belongs
CLS_NAME	VARCHAR2(15)	Class name of the check: • GENERIC • PERSISTENT_DATA
FLAGS	NUMBER	Reserved for internal use
INTERNAL_CHECK	VARCHAR2(1)	Internal check
OFFLINE_CAPABLE	VARCHAR2(1)	Ability to run when database is not open yet (Y or N)
DESCRIPTION	VARCHAR2(1024)	Description of what the check does
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.281 V$HM_CHECK_PARAM

V$HM_CHECK_PARAM displays information about the input parameters of all Health Monitor checks.

Column	Datatype	Description
ID	NUMBER	Parameter ID
NAME	VARCHAR2(64)	Parameter name
CHECK_ID	NUMBER	ID of the check to which this parameter belongs
TYPE	VARCHAR2(20)	Data type of the input parameter: • DBKH_PARAM_UB4 • DBKH_PARAM_UB8 • DBKH_PARAM_TEXT • DBKH_PARAM_DATE • DBKH_PARAM_UB4_LIST • DBKH_PARAM_UB8_LIST • DBKH_PARAM_TEXT_LIST • DBKH_PARAM_DATE_LIST
DEFAULT_VALUE	VARCHAR2(64)	Default value for this parameter
FLAGS	NUMBER	Reserved for internal use
DESCRIPTION	VARCHAR2(1024)	Description of the parameter
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.282 V$HM_FINDING

V$HM_FINDING displays information about all the findings of various Health Monitor runs.

Column	Datatype	Description
FINDING_ID	NUMBER	Unique ID to represent the finding
RUN_ID	NUMBER	ID of the run that created this finding
NAME	VARCHAR2(32)	Name of the finding
PARENT_ID	NUMBER	Parent finding ID for this finding
CHILD_COUNT	NUMBER	Number of active (open) child findings, if this finding is a parent finding type
CLASS_NAME	VARCHAR2(32)	Name of the class to which this finding belongs
TIME_DETECTED	TIMESTAMP(6)	Time this finding was detected
MODIFIED	TIMESTAMP(6)	Time that this finding was last modified
PRIORITY	VARCHAR2(8)	Priority of the finding: • LOW, • HIGH • CRITICAL

Column	Datatype	Description
STATUS	VARCHAR2(12)	Status of the finding: • OPEN • CLOSED
TYPE	VARCHAR2(13)	Type of the finding: • INFORMATIONAL • FAILURE
DESCRIPTION	VARCHAR2(1024)	Description of the finding
DAMAGE_DESCRIPTION	VARCHAR2(1024)	Possible damage description of the finding
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.283 V$HM_INFO

V$HM_INFO displays information about Health Monitor runs, findings, and recommendations.

The information for a run/finding/recommendation is organized as a name, value pair.

If the type of information is RUN, then the data represents the input parameters for that run. If the type of information is FINDING or RECOMMENDATION, then the data represents the information about that particular finding/recommendation.

Column	Datatype	Description
ID	NUMBER	Unique identifier of the information
TYPE	VARCHAR2(14)	Type of the information: • RUN • RUN-RESUME • FINDING • RECOMMENDATION
NAME	VARCHAR2(32)	Information parameter name
VALUE	VARCHAR2(513)	Information parameter value
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.284 V$HM_RECOMMENDATION

V$HM_RECOMMENDATION displays information about all the recommendations made to various Health Monitor findings.

Column	Datatype	Description
RECOMMENDATION_ID	NUMBER	Unique ID to represent the recommendation
FDG_ID	NUMBER	Unique ID to represent either the finding ID or the finding set ID for which the recommendation was made
RUN_ID	NUMBER	ID of the run that may have generated the recommendation If the ID is 0, then the recommendations were generated by RMAN.
NAME	VARCHAR2(32)	Name of the recommendation
TYPE	VARCHAR2(7)	Type of the recommendation: • MANUAL • REPAIR
RANK	NUMBER	Rank of the recommendation
TIME_DETECTED	TIMESTAMP(6)	Time that the recommendation was made
EXECUTED	TIMESTAMP(6)	Time that the recommendation (repair) was implemented
STATUS	VARCHAR2(7)	Status of the recommendation (repair) execution: • NOT RUN • RUNNING • SUCCESS • FAILED
DESCRIPTION	VARCHAR2(1024)	Description of the recommendation
REPAIR_SCRIPT	VARCHAR2(512)	Location of the repair script file
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.285 V$HM_RUN

V$HM_RUN displays information about all Health Monitor checks and their status.

Column	Datatype	Description
RUN_ID	NUMBER	Unique ID to represent the run
NAME	VARCHAR2(32)	Unique name used to identify the run
CHECK_NAME	VARCHAR2(32)	Name of the check

Column	Datatype	Description
RUN_MODE	VARCHAR2(8)	Mode of the run: • MANUAL • REACTIVE • AUTO
TIMEOUT	NUMBER	Number of seconds allowed for this run to complete before it is terminated
START_TIME	TIMESTAMP(6)	Start time of the run
LAST_RESUME_TIME	TIMESTAMP(6)	Last resumed time for the run
END_TIME	TIMESTAMP(6)	End time of the run
MODIFIED_TIME	TIMESTAMP(6)	Last modified time of the run record
STATUS	VARCHAR2(11)	Status of the run: • INITIAL • EXECUTING • INTERRUPTED • TIMEDOUT • CANCELLED • COMPLETED • ERROR
SRC_INCIDENT	NUMBER	Source incident ID that activated this run
NUM_INCIDENT	NUMBER	Number of incidents created by this run
ERROR_NUMBER	NUMBER	Error number if the run failed to complete because of an error
PROBLEM_ID	NUMBER	Problem ID of the source incident ID that may have activated this Run
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.286 V$HS_AGENT

V$HS_AGENT displays the set of HS agents currently running on a given host. There is one row per agent process.

Column	Datatype	Description
AGENT_ID	NUMBER	Oracle Net session identifier used for connections to the agent (the identifier used in the LISTENER.ORA file)
MACHINE	VARCHAR2(64)	Operating system machine name
PROCESS	VARCHAR2(9)	Operating system process identifier of the agent
PROGRAM	VARCHAR2(48)	Program name of the agent
OSUSER	VARCHAR2(128)	Operating system user

Column	Datatype	Description
STARTTIME	DATE	Starting time
AGENT_TYPE	NUMBER	Type of the agent
FDS_CLASS_ID	NUMBER	ID of the Foreign Data Store class
FDS_INST_ID	NUMBER	Instance name of the Foreign Data Store
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.287 V$HS_PARAMETER

V$HS_PARAMETER describes the initialization parameters in use by the server and agent.

Column	Datatype	Description
HS_SESSION_ID	NUMBER	Unique HS session identifier (maps to the HS_SESSION_ID column of V$HS_SESSION)
PARAMETER	VARCHAR2(128)	Name of the parameter
VALUE	VARCHAR2(64)	Value of the parameter
SOURCE	VARCHAR2(1)	Indicates whether the parameter was defined in the agent (A) or server (S)
ENV	VARCHAR2(1)	Indicates whether the parameter was set as an environment variable in the agent (T) or elsewhere (F)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.288 V$HS_SESSION

V$HS_SESSION describes the current HS session.

Column	Datatype	Description
HS_SESSION_ID	NUMBER	Unique HS session identifier
AGENT_ID	NUMBER	Oracle Net session identifier used for connections to the agent (maps to the AGENT_ID column of V$HS_AGENT)
SID	NUMBER	User session identifier (maps to the SID column of V$SESSION)

Column	Datatype	Description
DB_LINK	VARCHAR2(128)	Server database link name used to access the agent; blank if no database link is used (for example, when using external procedures)
DB_LINK_OWNER	NUMBER	Owner of the database link in DB_LINK
STARTTIME	DATE	Time the connection was initiated
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

8.289 V$HVMASTER_INFO

V$HVMASTER_INFO describes the current and previous master instances and the number of re-masterings of Global Enqueue Service resources.

Column	Datatype	Description
HV_ID	NUMBER	Hash value ID
CURRENT_MASTER	NUMBER	Master instance of this hash value ID
PREVIOUS_MASTER	NUMBER	Previous master instance of this hash value ID
REMASTER_CNT	NUMBER	Number of times this has been remastered
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9

Dynamic Performance (V$) Views: V$IM_COLUMN_LEVEL to V$RULE_SET_AGGREGATE_STATS

This chapter contains the dynamic performance views `V$IM_COLUMN_LEVEL` to `V$RULE_SET_AGGREGATE_STATS`.

9.1 V$IM_COLUMN_LEVEL

`V$IM_COLUMN_LEVEL` presents the selective column compression levels that are defined using the `inmemory_memcompress` clause of the `inmemory_column_clause` of the `CREATE TABLE` statement.

This view returns no rows for a table which has no associated selective column compression levels.

Column	Datatype	Description
`INST_ID`	`NUMBER`	Instance ID
`OWNER`	`VARCHAR2(31)`	Username of the table owner
`OBJ_NUM`	`NUMBER`	Table object number
`TABLE_NAME`	`VARCHAR2(31)`	Table name
`SEGMENT_COLUMN_ID`	`NUMBER`	Segment column number
`COLUMN_NAME`	`VARCHAR2(31)`	Column name
`INMEMORY_COMPRESSION`	`VARCHAR2(26)`	Column compression level. Possible values: • `DEFAULT`: This value appears for physical columns of a table that do not have a selective column clause. It also appears when a virtual column has been explicitly enabled for in-memory storage using `ALTER TABLE` *table-name* `INMEMORY(VC)`. • `UNSPECIFIED`: This value appears for virtual columns of a table that do not have a selective column clause. If the `INMEMORY_VIRTUAL_COLUMNS` initialization parameter is set to `MANUAL`, a virtual column with a `DEFAULT INMEMORY_COMPRESSION` clause will be materialized while a virtual column with an `UNSPECIFIED` value will not be.
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> The SYS_IME hidden virtual columns automatically added by the In-Memory Expression (IME) infrastructure will not be shown in this view.

> **See Also:**
>
> - "INMEMORY_CLAUSE_DEFAULT"
> - "V$IM_SEGMENTS"
> - "V$IM_USER_SEGMENTS"
> - *Oracle Database In-Memory Guide* for an introduction to the IM column store
> - *Oracle Database SQL Language Reference* for more information about the `inmemory_column_clause` of the SQL `CREATE TABLE` statement

9.2 V$IM_SEGMENTS

`V$IM_SEGMENTS` presents information about all the in-memory segments in the database.

Only segments that have an in-memory representation are displayed. If a segment is marked for the In-Memory Column Store (IM column store) but is not populated, no corresponding row for that segment is displayed in this view.

Column	Datatype	Description
OWNER	VARCHAR2(128)	User name of the segment owner
SEGMENT_NAME	VARCHAR2(128)	Name of the segment, if any
PARTITION_NAME	VARCHAR2(128)	Object partition name (set to NULL for non-partitioned objects)
SEGMENT_TYPE	VARCHAR2(18)	Type of segment: • TABLE • TABLE PARTITION • TABLE SUBPARTION
TABLESPACE_NAME	VARCHAR2(30)	Name of the tablespace containing the segment
INMEMORY_SIZE	NUMBER	Size of the in-memory version of the segment, in bytes
BYTES	NUMBER	Number of on-disk data bytes for the segment that could be represented in memory (no space metadata blocks)
BYTES_NOT_POPULATED	NUMBER	Size of the portion of the on-disk segment that is not populated in memory, in bytes.
POPULATE_STATUS	VARCHAR2(13)	Status of segment population: • STARTED: A populate task for the segment has started • COMPLETED: There are no populate tasks pending for the segment • OUT OF MEMORY: A populate task for the segment failed due to lack of space in the IM column store

Column	Datatype	Description
INMEMORY_PRIORITY	VARCHAR2(8)	Indicates the priority for IM column store population: • LOW • MEDIUM • HIGH • CRITICAL • NONE
INMEMORY_DISTRIBUTE	VARCHAR2(15)	Indicates how the IM column store is distributed in an Oracle Real Application Clusters (Oracle RAC) environment: • AUTO • BY ROWID RANGE • BY PARTITION • BY SUBPARTITION
INMEMORY_DUPLICATE	VARCHAR2(13)	Indicates the duplicate setting for the IM column store in an Oracle RAC environment: • NO DUPLICATE • DUPLICATE • DUPLICATE ALL
INMEMORY_COMPRESSION	VARCHAR2(17)	Compression level for the IM column store: • NO MEMCOMPRESS • FOR DML • FOR QUERY [LOW | HIGH] • FOR CAPACITY [LOW | HIGH] • AUTO
INMEMORY_SERVICE	VARCHAR2(12)	Specifies how the IM-enabled table is populated on various instances: • DEFAULT: Pre-Oracle Database 12c Release 2 (12.2.0.1) behavior • NONE: Do not populate on any instance • ALL: Populate on all instances • USER_DEFINED: Populate only on the instances on which the user-specified service is active. The service name corresponding to this is stored in the INMEMORY_SERVICE_NAME column.
INMEMORY_SERVICE_NAME	VARCHAR2(129)	Specifies the service name on which the IM-enabled table should be populated. This column has a value only when the corresponding INMEMORY_SERVICE column has a value of USER_DEFINED.
IS_EXTERNAL	VARCHAR2(5)	Indicates whether the IM segment is for an external table. Possible values: • TRUE: The IM segment is for an external table. • FALSE: The IM segment is not for an external table.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "INMEMORY_CLAUSE_DEFAULT"
- "V$IM_COLUMN_LEVEL"
- "V$IM_USER_SEGMENTS"
- *Oracle Database In-Memory Guide* for an introduction to the IM column store

9.3 V$IM_USER_SEGMENTS

V$IM_USER_SEGMENTS presents information about the in-memory segments for the current user in the database.

Only segments that have an in-memory representation are displayed. If a segment is marked for the In-Memory Column Store (IM column store) but is not populated, no corresponding row for that segment is displayed in this view.

Column	Datatype	Description
SEGMENT_NAME	VARCHAR2(128)	Name of the segment, if any
PARTITION_NAME	VARCHAR2(128)	Object partition name (set to NULL for non-partitioned objects)
SEGMENT_TYPE	VARCHAR2(18)	Type of segment: • TABLE • TABLE PARTITION • TABLE SUBPARTION
TABLESPACE_NAME	VARCHAR2(30)	Name of the tablespace containing the segment
INMEMORY_SIZE	NUMBER	Size of the in-memory version of the segment, in bytes
BYTES	NUMBER	Total size of the on-disk segment, in bytes
BYTES_NOT_POPULATED	NUMBER	Size of the portion of the on-disk segment that is not populated in memory, in bytes
POPULATE_STATUS	VARCHAR2(13)	Status of segment population: • STARTED: A populate task for the segment has started • COMPLETED: There are no populate tasks pending for the segment • OUT OF MEMORY: A populate task for the segment failed due to lack of space in the IM column store
INMEMORY_PRIORITY	VARCHAR2(8)	Indicates the priority for IM column store population: • LOW • MEDIUM • HIGH • CRITICAL • NONE

Column	Datatype	Description
INMEMORY_DISTRIBUTE	VARCHAR2(15)	Indicates how the IM column store is distributed in an Oracle Real Application Clusters (Oracle RAC) environment: • AUTO • BY ROWID RANGE • BY PARTITION • BY SUBPARTITION
INMEMORY_DUPLICATE	VARCHAR2(13)	Indicates the duplicate setting for the IM column store in an Oracle RAC environment: • NO DUPLICATE • DUPLICATE • DUPLICATE ALL
INMEMORY_COMPRESSION	VARCHAR2(17)	Compression level for the IM column store: • NO MEMCOMPRESS • FOR DML • FOR QUERY [LOW | HIGH] • FOR CAPACITY [LOW | HIGH] • AUTO
INMEMORY_SERVICE	VARCHAR2(12)	Specifies how the IM-enabled table is populated on various instances: • DEFAULT: Pre-Oracle Database 12c Release 2 (12.2.0.1) behavior • NONE: Do not populate on any instance • ALL: Populate on all instances • USER_DEFINED: Populate only on the instances on which the user-specified service is active. The service name corresponding to this is stored in the INMEMORY_SERVICE_NAME column.
INMEMORY_SERVICE_NAME	VARCHAR2(129)	Specifies the service name on which the IM-enabled table should be populated. This column has a value only when the corresponding INMEMORY_SERVICE column has a value of USER_DEFINED.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "INMEMORY_CLAUSE_DEFAULT"
- "V$IM_COLUMN_LEVEL"
- "V$IM_SEGMENTS"
- *Oracle Database In-Memory Guide* for an introduction to the IM column store

9.4 V$INDEX_USAGE_INFO

V$INDEX_USAGE_INFO keeps track of index usage since the last flush. A flush occurs every 15 minutes. After each flush, ACTIVE_ELEM_COUNT is reset to 0 and LAST_FLUSH_TIME is updated to the current time.

Column	Datatype	Description
INDEX_STATS_ENABLED	NUMBER	Indicates whether the index usage statistics are enabled. Possible values: • 0: Index statistics are disabled • 1: Index statistics are enabled
INDEX_STATS_COLLECTION_TYPE	NUMBER	Indicates the type of collection used for the index usage statistics. Possible values: • 0: Indicates the ALL collection type. With this type of collection, the statistics are collected for each execution that has index access. Selecting this statistics collection type may have some impact on performance. • 1: Indicates the SAMPLED collection type. With this type of collection, the statistics are collected based on sampling (only a few of the executions are considered when collecting the statistics). This is the default statistics collection type. Index statistics collected with the SAMPLED collection type are less accurate than index statistics collected with the ALL collection type.
ACTIVE_ELEM_COUNT	NUMBER	The number of active indexes since the last flush
ALLOC_ELEM_COUNT	NUMBER	The number of index entries allocated
MAX_ELEM_COUNT	NUMBER	The maximum number of active indexes that can be tracked
FLUSH_COUNT	NUMBER	Number of successful flushes since the database started
TOTAL_FLUSH_DURATION	NUMBER	Cumulative elapsed time taken to complete the index usage statistics flush since the database start
LAST_FLUSH_TIME	TIMESTAMP(3)	The time of the last flush
STATUS_MSG	VARCHAR2(256)	Status messages, if any. Flush errors are reported here.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This row is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"DBA_INDEX_USAGE"

9.5 V$INDEXED_FIXED_COLUMN

V$INDEXED_FIXED_COLUMN displays the columns in dynamic performance tables that are indexed (X$ tables).

The X$ tables can change without notice. Use this view only to write queries against fixed views (V$ views) more efficiently.

Column	Datatype	Description
TABLE_NAME	VARCHAR2(128)	Name of the dynamic performance table that is indexed
INDEX_NUMBER	NUMBER	Number that distinguishes to which index a column belongs
COLUMN_NAME	VARCHAR2(128)	Name of the column that is being indexed
COLUMN_POSITION	NUMBER	Position of the column in the index key (this is mostly relevant for multicolumn indexes)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.6 V$INMEMORY_AREA

V$INMEMORY_AREA contains information on the space allocation inside the In-Memory Area.

The In-Memory Area is sub-divided into three pools:

- 1MB POOL - stores the actual column formatted data populated into memory
- 64K POOL - stores metadata about the objects that are populated into the In-Memory Column Store (IM column store)
- IM POOL METADATA - contains information about In-Memory Compression Unit (IMCU) to data block mappings

The amount of available memory in each pool is visible in the V$INMEMORY_AREA view. The relative size of the three pools is determined by internal heuristics. The majority of the In-Memory Area memory is allocated to the 1MB POOL

Column	Datatype	Description
POOL	VARCHAR2(26)	Name of the pools in the In-Memory Area
ALLOC_BYTES	NUMBER	Total amount of memory allocated to this pool
USED_BYTES	NUMBER	Amount of memory currently used in this pool
POPULATE_STATUS	VARCHAR2(26)	Shows the status of the IM column store, for example, whether it is currently being populated or if it is done

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "INMEMORY_CLAUSE_DEFAULT"
- "V$IM_COLUMN_LEVEL"
- "V$IM_SEGMENTS"
- "V$IM_USER_SEGMENTS"
- *Oracle Database In-Memory Guide* for an introduction to the IM column store

9.7 V$INMEMORY_FASTSTART_AREA

V$INMEMORY_FASTSTART_AREA provides information about the In-Memory FastStart (IM FastStart) area.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
TABLESPACE_NAME	VARCHAR2(128)	IM FastStart tablespace name. When IM FastStart is not enabled, the value of TABLESPACE_NAME is INVALID_TABLESPACE and the value of STATUS is DISABLE.

Column	Datatype	Description
STATUS	VARCHAR2(10)	IM FastStart status. Possible values include: • ENABLE: An IM FastStart tablespace has been specified and the content of the IM column is being periodically checkpointed to disk. • ENABLING: An IM FastStart tablespace has been specified and the database is creating the IM FastStart area. • DISABLE: An IM FastStart tablespace has not been specified. This is the default. • MIGRATING: A user has requested the IM FastStart area be migrated from one tablespace to another. • DISABLING: A user has requested IM FastStart to be disabled.
ALLOCATED_SIZE	NUMBER	The allocated size of an IM FastStart tablespace in bytes
USED_SIZE	NUMBER	The currently used size of an IM FastStart area (in bytes) within the tablespace.
LAST_CHECKPOINT_TIME	TIMESTAMP(6)	The time when the last IMCU was checkpointed to the IM FastStart area
LAST_POPULATE_TIME	TIMESTAMP(6)	The time of the last population from the IM FastStart area
NUM_DEFERRED_WRITES	NUMBER	The number of pending deferred writes to the IM FastStart area

9.8 V$INMEMORY_SIZE_ADVICE

V$INMEMORY_SIZE_ADVICE estimates usage and performance statistics for different simulated sizes of the In-Memory Column Store (IM Column Store).

Column	Datatype	Description
IM_POOL_SIZE_FOR_ESTIMATE	NUMBER	Simulated size of the IM Column Store (in megabytes)
SIZE_FACTOR	NUMBER	Size factor with respect to the current IM Column Store size
ESTD_IM_USED_SIZE	NUMBER	Estimated amount of space the IM Column Store would use for this simulation (in megabytes)
ESTD_IM_SCAN_TIME	NUMBER	Estimated in-memory scan time for this simulation (in seconds)
ESTD_TOTAL_DB_TIME	NUMBER	Estimated total database time for this simulation (in seconds) This value estimates the cumulative time spent by the database on processing user requests. It includes the wait time and CPU time of all non-idle user sessions.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

9.9 V$INSTANCE

V$INSTANCE displays the state of the current instance.

Column	Datatype	Description
INSTANCE_NUMBER	NUMBER	Instance number used for instance registration (corresponds to the INSTANCE_NUMBER initialization parameter) **See Also:** "INSTANCE_NUMBER"
INSTANCE_NAME	VARCHAR2(16)	Name of the instance
HOST_NAME	VARCHAR2(64)	Name of the host machine
VERSION	VARCHAR2(17)	Database version
VERSION_LEGACY	VARCHAR2(17)	The legacy database version used before Oracle Database 18c. This column displays the same value as the VERSION column
VERSION_FULL	VARCHAR2(17)	The version string with the new Oracle Database version scheme introduced in Oracle Database 18c.
STARTUP_TIME	DATE	Time when the instance was started
STATUS	VARCHAR2(12)	Status of the instance: • STARTED - After STARTUP NOMOUNT • MOUNTED - After STARTUP MOUNT or ALTER DATABASE CLOSE • OPEN - After STARTUP or ALTER DATABASE OPEN • OPEN MIGRATE - After ALTER DATABASE OPEN { UPGRADE | DOWNGRADE }
PARALLEL	VARCHAR2(3)	Indicates whether the instance is mounted in cluster database mode (YES) or not (NO)
THREAD#	NUMBER	Redo thread opened by the instance
ARCHIVER	VARCHAR2(7)	Automatic archiving status: • STOPPED • STARTED • FAILED - Archiver failed to archive a log last time but will try again within 5 minutes
LOG_SWITCH_WAIT	VARCHAR2(15)	Event that log switching is waiting for: • ARCHIVE LOG • CLEAR LOG • CHECKPOINT • NULL - ALTER SYSTEM SWITCH LOGFILE is hung but there is room in the current online redo log
LOGINS	VARCHAR2(10)	Indicates whether the instance is in unrestricted mode, allowing logins by all users (ALLOWED, or in restricted mode, allowing logins by database administrators only (RESTRICTED)
SHUTDOWN_PENDING	VARCHAR2(3)	Indicates whether a shutdown is pending (YES) or not (NO)

Column	Datatype	Description
DATABASE_STATUS	VARCHAR2(17)	Status of the database: • ACTIVE • SUSPENDED • INSTANCE RECOVERY
INSTANCE_ROLE	VARCHAR2(18)	Indicates whether the instance is an active instance (PRIMARY_INSTANCE) or an inactive secondary instance (SECONDARY_INSTANCE), or UNKNOWN if the instance has been started but not mounted
ACTIVE_STATE	VARCHAR2(9)	Quiesce state of the instance: • NORMAL - Database is in a normal state. • QUIESCING - ALTER SYSTEM QUIESCE RESTRICTED has been issued: no new user transactions, queries, or PL/SQL statements are processed in this instance. User transactions, queries, or PL/SQL statements issued before the ALTER SYSTEM QUIESCE RESTRICTED statement are unaffected. DBA transactions, queries, or PL/SQL statements are also unaffected. • QUIESCED - ALTER SYSTEM QUIESCE RESTRICTED has been issued: no user transactions, queries, or PL/SQL statements are processed. DBA transactions, queries, or PL/SQL statements are unaffected. User transactions, queries, or PL/SQL statements issued after the ALTER SYSTEM QUIESCE RESTRICTED statement are not processed. A single ALTER SYSTEM QUIESCE RESTRICTED statement quiesces all instances in an Oracle RAC environment. After this statement has been issued, some instances may enter into a quiesced state before other instances; the system is quiesced when all instances enter the quiesced state.
BLOCKED	VARCHAR2(3)	Indicates whether all services are blocked (YES) or not (NO)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
INSTANCE_MODE	VARCHAR2(11)	Shows the instance mode of the current instance. Possible values: • REGULAR: A regular Oracle RAC instance. This value is also always used for any non-Oracle RAC instance. • READ MOSTLY: An Oracle RAC instance that performs very few database writes • READ ONLY: A read-only Oracle RAC instance
EDITION	VARCHAR2(7)	The edition of the database. Possible values include: • CORE EE: CORE Enterprise Edition • EE: Enterprise Edition • PO: Personal Edition • FREE: Free

Column	Datatype	Description
FAMILY	VARCHAR2(80)	For internal use only.
DATABASE_TYPE	VARCHAR2(15)	Database type: • RAC: If the database is a regular Oracle RAC database which may have multiple instances. • RACONENODE: If the database is Oracle RAC, but allows only one instance to run at any time - the RAC One Node mode. • SINGLE: If the database is running as a single instance. • UNKNOWN: If the database's type can't be determined. This might happen when the database is registered as a DB resource with CRS but the CRS service has failed to return valid database type information. Typically, this indicates that either the CRS service is down or it is in a faulty state.

9.10 V$INSTANCE_CACHE_TRANSFER

V$INSTANCE_CACHE_TRANSFER displays statistics for the cache blocks transferred among instances.

Oracle keeps multiple versions of data buffered in the buffer cache. The current buffer (or block), CURRENT_BLOCK, is the most up-to-date copy, containing all recent modifications. A consistent read buffer (or block), CR_BLOCK, contains the version of the data at a particular time prior to the current buffer. It is read-consistent (that is, all the data shown in that buffer are consistent for the start time of a query).

Therefore, for the same data block there can be multiple copies in the buffer cache: one current copy, and one or more consistent read copies with data consistent as of different snapshot times.

Column	Datatype	Description
INSTANCE	NUMBER	Instance from which the blocks are transferred
CLASS	VARCHAR2(18)	Class of the cache block
LOST	NUMBER	The number of blocks that were sent by a particular instance but that never arrived in this instance
LOST_TIME	NUMBER	The time waited for blocks that were sent by a particular instance but that never arrived in this instance
CR_BLOCK	NUMBER	CR Block transfers not affected by remote processing delays
CR_BLOCK_TIME	NUMBER	Total time waited for CR blocks from a particular instance (includes the other times)
CR_2HOP	NUMBER	The count of CR blocks which were received by this instance from a particular instance after a 2-way round-trip
CR_2HOP_TIME	NUMBER	The time waited for CR blocks which were received by this instance from a particular instance after a 2-way round-trip
CR_3HOP	NUMBER	The count of CR blocks which were received by this instance from a particular instance after a 3-way round-trip
CR_3HOP_TIME	NUMBER	The time waited for CR blocks which were received by this instance from a particular instance after a 3-way round-trip
CR_RDMA	NUMBER	The count of CR Blocks which were directly read from a remote instance via RDMA

Column	Datatype	Description
CR_RDMA_TIME	NUMBER	Total time waited to directly read CR blocks from a remote instance via RDMA (in centiseconds)
CR_BUSY	NUMBER	CR Block transfers affected by remote contention
CR_BUSY_TIME	NUMBER	The time waited for CR blocks which were received by this instance from a particular instance and which were delayed by a log flushed on the sending instance
CR_CONGESTED	NUMBER	CR Block transfers affected by remote system load
CR_CONGESTED_TIME	NUMBER	The time waited for CR blocks which were received by this instance from a particular instance and which were delayed because LMS was busy
CURRENT_BLOCK	NUMBER	Current block transfers not affected by remote processing delays
CURRENT_BLOCK_TIME	NUMBER	Total time waited for current blocks from a particular instance (includes the other times
CURRENT_2HOP	NUMBER	The count of current blocks which were received by this instance from a particular instance after a 2-way round-trip
CURRENT_2HOP_TIME	NUMBER	The time waited for current blocks which were received by this instance from a particular instance after a 2-way round-trip
CURRENT_3HOP	NUMBER	The count of current blocks which were received by this instance from a particular instance after a 3-way round-trip
CURRENT_3HOP_TIME	NUMBER	The time waited for current blocks which were received by this instance from a particular instance after a 3-way round-trip
CURRENT_RDMA	NUMBER	The count of current blocks which were directly read from a remote instance via RDMA
CURRENT_RDMA_TIME	NUMBER	Total time waited to directly read current blocks from a remote instance via RDMA (in centiseconds)
CURRENT_BUSY	NUMBER	Current block transfers affected by remote contention
CURRENT_BUSY_TIME	NUMBER	The time waited for current blocks which were received by this instance from a particular instance and which were delayed by a log flushed on the sending instance
CURRENT_CONGESTED	NUMBER	Current block transfers affected by remote system load
CURRENT_CONGESTED_TIME	NUMBER	The time waited for current blocks which were received by this instance from a particular instance and which were delayed because LMS was busy
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.11 V$INSTANCE_PING

V$INSTANCE_PING provides information about measured latency of the interconnect for all instances in an Oracle Real Application Clusters (Oracle RAC) environment.

In an Oracle RAC environment, every few seconds the PING process of each instance checks the response of the interconnect to all instances of the same database.

It sends two messages. One message is 500 bytes in size (referred to in the column descriptions as 500B), and the other is 8 kilobytes in size (referred to in column descriptions as 8K).

For each message sent to each instance, the amount of time it took to get a response back is measured (in microseconds). The view records the latest measurements as well as cumulative data since instance startup.

Column	Datatype	Description
INSTANCE	NUMBER	The instance communicated with. In the V$ view for each instance, there is one row for that instance, and in the GV$ view for each instance, there is also one row for that instance, so there are n^2 rows for n instances.
CURRENT_500B	NUMBER	The latest response time for the 500B message (in microseconds)
AVERAGE_500B	NUMBER	The average response time for the 500B messages since instance startup (in microseconds). Note that AVERAGE_500B should be the same as WAIT_TIME_500B/COUNT_500B.
MAX_500B	NUMBER	The maximal response time for the 500B messages since instance startup (in microseconds)
COUNT_500B	NUMBER	The number of measurements for the 500B messages since instance startup
WAIT_TIME_500B	NUMBER	The sum of all response times for the 500B messages since instance startup (in microseconds)
WAIT_TIME_SQUARED_500B	NUMBER	The sum of the response time squared for 500B messages since instance startup. The unit is in microseconds squared and divided by 1000.
CURRENT_8K	NUMBER	The latest response time for the 8K message (in microseconds)
AVERAGE_8K	NUMBER	The average response time for the 8K messages since instance startup (in microseconds). Note that AVERAGE_8K should be the same as WAIT_TIME_8K/COUNT_8K.
MAX_8K	NUMBER	The maximal response time for the 8K messages since instance startup (in microseconds)
COUNT_8K	NUMBER	The number of measurements for the 8K messages since instance startup
WAIT_TIME_8K	NUMBER	The sum of all response times for the 8K messages since instance startup (in microseconds)
WAIT_TIME_SQUARED_8K	NUMBER	The sum of the response time squared for 8K messages since instance startup. The unit is in microseconds squared and divided by 16.
CON_ID	NUMBER	The ID of the container to which the data pertains. For this view, the possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs.

9.12 V$INSTANCE_RECOVERY

V$INSTANCE_RECOVERY monitors the mechanisms available to users to limit recovery I/O. Those mechanisms are:

- Set the LOG_CHECKPOINT_TIMEOUT initialization parameter
- Set the LOG_CHECKPOINT_INTERVAL initialization parameter
- Set the FAST_START_MTTR_TARGET initialization parameter
- Set the size of the smallest redo log

Column	Datatype	Description
RECOVERY_ESTIMATED_IOS	NUMBER	Number of dirty buffers in the buffer cache.
ACTUAL_REDO_BLKS	NUMBER	Current actual number of redo blocks required for recovery
TARGET_REDO_BLKS	NUMBER	Current target number of redo blocks that must be processed for recovery. This value is the minimum value of the following 3 columns, and identifies which of the 3 user-defined limits determines checkpointing.
LOG_FILE_SIZE_REDO_BLKS	NUMBER	Maximum number of redo blocks required to guarantee that a log switch does not occur before the checkpoint completes.
LOG_CHKPT_TIMEOUT_REDO_BLKS	NUMBER	Number of redo blocks that need to be processed during recovery to satisfy the LOG_CHECKPOINT_TIMEOUT parameter. The value displayed is not meaningful unless that parameter has been set.
LOG_CHKPT_INTERVAL_REDO_BLKS	NUMBER	Number of redo blocks that need to be processed during recovery to satisfy the LOG_CHECKPOINT_INTERVAL parameter. The value displayed is not meaningful unless that parameter has been set.
FAST_START_IO_TARGET_REDO_BLKS	NUMBER	This column is obsolete and maintained for backward compatibility. The value of this column is always null.
TARGET_MTTR	NUMBER	Effective MTTR (mean time to recover) target value in seconds. The TARGET_MTTR value is calculated based on the value of the FAST_START_MTTR_TARGET parameter (the TARGET_MTTR value is used internally), and is usually an approximation of the parameter's value. However, if the FAST_START_MTTR_TARGET parameter value is very small (for example, one second), or very large (for example, 3600 seconds), the calculation will produce a target value dictated by system limitations. In such cases, the TARGET_MTTR value will be the shortest calculated time, or the longest calculated time that recovery is expected to take.
ESTIMATED_MTTR	NUMBER	Current estimated mean time to recover (MTTR) based on the number of dirty buffers and log blocks. Basically, this value tells you how long you could expect recovery to take based on the work your system is doing right now.
CKPT_BLOCK_WRITES	NUMBER	Number of blocks written by checkpoint writes
OPTIMAL_LOGFILE_SIZE	NUMBER	Redo log file size (in megabytes) that is considered optimal based on the current setting of FAST_START_MTTR_TARGET. It is recommended that the user configure all online redo logs to be at least this value. Note that redo log files must be at least 4 megabytes in size; otherwise an error is generated.

Column	Datatype	Description
ESTD_CLUSTER_AVAILABLE_TIME	NUMBER	Estimated time (in seconds) that the cluster would become partially available should this instance fail. This column is only meaningful in an Oracle Real Application Clusters (Oracle RAC) environment. In a non-Oracle RAC environment, the value of this column is null.
WRITES_MTTR	NUMBER	Number of writes driven by the FAST_START_MTTR_TARGET initialization parameter
WRITES_LOGFILE_SIZE	NUMBER	Number of writes driven by the smallest redo log file size
WRITES_LOG_CHECKPOINT_SETTINGS	NUMBER	Number of writes driven by the LOG_CHECKPOINT_INTERVAL or LOG_CHECKPOINT_TIMEOUT initialization parameter
WRITES_OTHER_SETTINGS	NUMBER	Number of writes driven by other reasons (such as the deprecated FAST_START_IO_TARGET initialization parameter)
WRITES_AUTOTUNE	NUMBER	Number of writes due to auto-tune checkpointing
WRITES_FULL_THREAD_CKPT	NUMBER	Number of writes due to full thread checkpoints
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.13 V$IO_CALIBRATION_STATUS

V$IO_CALIBRATION_STATUS displays the status of I/O calibration in the instance.

Column	Datatype	Description
STATUS	VARCHAR2(13)	Calibration status: • IN PROGRESS - Calibration in Progress (Results from a previous calibration run are displayed, if available) • READY Results are ready and available from an earlier run • NOT AVAILABLE Calibration results are not available
CALIBRATION_TIME	TIMESTAMP(3)	End time of the last calibration run
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.14 V$IO_OUTLIER

V$IO_OUTLIER contains entries corresponding to I/Os that have taken a long time (more than 500 ms) to complete. Use this view to see if there any occasional delays in serving disk I/O requests by the storage subsystem.

Column	Datatype	Description
FUNCTION_NAME	VARCHAR2(18)	I/O function name of the delayed I/O
IO_SIZE	NUMBER	Size of the I/O in bytes
WAIT_EVENT	VARCHAR2(64)	Wait event name that was used to track the I/O
FILE_NAME	VARCHAR2(513)	Name of the file to which the I/O was targeted
IO_LATENCY	NUMBER	Time taken to complete the I/O (in milliseconds)
DISK1_NAME	VARCHAR2(255)	For Oracle ASM, the name of the first disk to which the I/O was issued
DISK1_LATENCY	NUMBER	Latency seen on the first disk (in milliseconds)
DISK2_NAME	VARCHAR2(255)	For Oracle ASM, the name of the second disk to which the I/O was issued
DISK2_LATENCY	NUMBER	Latency seen on the second disk (in milliseconds)
DISK3_NAME	VARCHAR2(255)	For Oracle ASM, the name of the third disk to which the I/O was issued
DISK3_LATENCY	NUMBER	Latency seen on the third disk (in milliseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$KERNEL_IO_OUTLIER"
- "V$LGWRIO_OUTLIER"

9.15 V$IOFUNCMETRIC

V$IOFUNCMETRIC displays I/O statistics information by database function for the most recent time interval period.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval

Column	Datatype	Description
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
FUNCTION_ID	NUMBER	Function ID
FUNCTION_NAME	VARCHAR2(18)	Function name
SMALL_READ_MBPS	NUMBER	Single block megabytes read per second
SMALL_WRITE_MBPS	NUMBER	Single block megabytes written per second
LARGE_READ_MBPS	NUMBER	Multiblock megabytes read per second
LARGE_WRITE_MBPS	NUMBER	Multiblock megabytes written per second
SMALL_READ_IOPS	NUMBER	Single block read requests per second
SMALL_WRITE_IOPS	NUMBER	Single block write requests per second
LARGE_READ_IOPS	NUMBER	Multiblock read requests per second
LARGE_WRITE_IOPS	NUMBER	Multiblock write requests per second
AVG_WAIT_TIME	NUMBER	Average wait time (in milliseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.16 V$IOFUNCMETRIC_HISTORY

V$IOFUNCMETRIC_HISTORY displays a recent history of the I/O statistics information by database function for the most recent time interval period.

The columns for V$IOFUNCMETRIC_HISTORY are the same as those for V$IOFUNCMETRIC.

> **See Also:**
>
> "V$IOFUNCMETRIC"

9.17 V$IOS_CLIENT

V$IOS_CLIENT provides more information about IO Server clients.

Column	Datatype	Description
CLIENT_ID	NUMBER	The unique ID for this client instance
CLUSTER_ID	VARCHAR2(33)	The GUID of the cluster where the client instance is running

Column	Datatype	Description
CLUSTER_NAME	VARCHAR2(16)	When the query is executed on an Oracle IOServer (IOS) instance, this column shows the name of the cluster where the client (database) instance is running. When the query is executed on a database instance, this column shows the name of the cluster where the IOS instance that the database is connected to is running.
NODE	NUMBER	Number of the node within the cluster where the client instance is running
INSTANCE_NAME	VARCHAR2(64)	Instance name of the database client instance
DB_NAME	VARCHAR2(64)	Database name of the database client instance
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> In an Oracle Database instance, this view returns 0 rows when queried from a PDB.

9.18 V$IOSTAT_CONSUMER_GROUP

V$IOSTAT_CONSUMER_GROUP displays disk I/O statistics for consumer groups.

If the resource manager is enabled, then I/O statistics for all consumer groups that are part of the currently enabled resource plan are captured.

Column	Datatype	Description
CONSUMER_GROUP_ID	NUMBER	Consumer group ID
SMALL_READ_MEGABYTES	NUMBER	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	Number of multiblock megabytes written
SMALL_READ_REQS	NUMBER	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	Number of single block write requests
LARGE_READ_REQS	NUMBER	Number of multiblock read requests
LARGE_WRITE_REQS	NUMBER	Number of multiblock write requests
NUMBER_OF_WAITS	NUMBER	Number of I/O waits by consumer group
WAIT_TIME	NUMBER	Total wait time (in milliseconds)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.19 V$IOSTAT_FILE

V$IOSTAT_FILE displays information about disk I/O statistics of database files (including data files, temp files, and other types of database files).

I/O statistics for Data files and Temp files are provided for each file. All other file types (for example, control files, log files, archive logs, and so on) have their statistics consolidated into one entry in the view.

Column	Datatype	Description
FILE_NO	NUMBER	File identification number
FILETYPE_ID	NUMBER	Type of file (for example, log file, data file, and so on)
FILETYPE_NAME	VARCHAR2(28)	Name of the file, in the case of a data file or temp file. For all other files, a corresponding string to be displayed (for example, ARCHIVELOG).
SMALL_READ_MEGABYTES	NUMBER	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	Number of multiblock megabytes written
SMALL_READ_REQS	NUMBER	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	Number of single block write requests
SMALL_SYNC_READ_REQS	NUMBER	Number of synchronous single block read requests
LARGE_READ_REQS	NUMBER	Number of multiblock read requests
LARGE_WRITE_REQS	NUMBER	Number of multiblock write requests
SMALL_READ_SERVICETIME	NUMBER	Total service time (in milliseconds) for single block read requests
SMALL_WRITE_SERVICETIME	NUMBER	Total service time (in milliseconds) for single block write requests
SMALL_SYNC_READ_LATENCY	NUMBER	Latency for single block synchronous reads (in milliseconds)
LARGE_READ_SERVICETIME	NUMBER	Total service time (in milliseconds) for multiblock read requests
LARGE_WRITE_SERVICETIME	NUMBER	Total service time (in milliseconds) for multiblock write requests
ASYNCH_IO	VARCHAR2(9)	Indicates whether asynchronous I/O is available for the file (ASYNC_ON) or not (ASYNC_OFF)

Column	Datatype	Description
ACCESS_METHOD	VARCHAR2(11)	I/O library used to access the file. Possible values include: • OS_LIB - Operating system calls are used to access the file • ODM_LIB - Oracle Disk Manager library is used to access the file • ASM_MANAGED - The file is managed and accessed though ASM • DNFS_LIB - The file is accessed through Direct NFS library
RETRIES_ON_ERROR	NUMBER	Number of read retries on error
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.20 V$IOSTAT_FUNCTION

V$IOSTAT_FUNCTION displays disk I/O statistics for database functions (such as the LGWR and DBWR).

Column	Datatype	Description
FUNCTION_ID	NUMBER	Function ID
FUNCTION_NAME	VARCHAR2(18)	Function name: • RMAN • DBWR • LGWR • ARCH • XDB • Streams AQ • Data Pump • Recovery • Buffer Cache Reads • Direct Reads • Direct Writes • Smart Scan • Archive Manager • Others
SMALL_READ_MEGABYTES	NUMBER	Number of megabytes read via single block read requests
SMALL_WRITE_MEGABYTES	NUMBER	Number of megabytes written via single block write requests
LARGE_READ_MEGABYTES	NUMBER	Number of megabytes read via multiblock read requests
LARGE_WRITE_MEGABYTES	NUMBER	Number of megabytes written via multiblock write requests
SMALL_READ_REQS	NUMBER	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	Number of single block write requests
LARGE_READ_REQS	NUMBER	Number of multiblock read requests

Column	Datatype	Description
LARGE_WRITE_REQS	NUMBER	Number of multiblock write requests
NUMBER_OF_WAITS	NUMBER	Number of synchronous I/O waits by functionality
WAIT_TIME	NUMBER	Total synchronous I/O wait time (in milliseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.21 V$IOSTAT_FUNCTION_DETAIL

V$IOSTAT_FUNCTION_DETAIL displays disk I/O statistics for database functions (such as the LGWR and DBWR), broken down by file type.

Column	Datatype	Description
FUNCTION_ID	NUMBER	Function ID
FUNCTION_NAME	VARCHAR2(18)	Function name: • RMAN • DBWR • LGWR • ARCH • XDB • Streams AQ • Data Pump • Recovery • Buffer Cache Reads • Direct Reads • Direct Writes • Smart Scan • Archive Manager • Others
FILETYPE_ID	NUMBER	File type ID

Column	Datatype	Description
FILETYPE_NAME	VARCHAR2(28)	File type name: • Control File • Data File • Log File • Archive Log • Temp File • Data File Backup • Data File Incremental Backup • Archive Log Backup • Data File Copy • Flashback Log • Data Pump Dump File • Other
SMALL_READ_MEGABYTES	NUMBER	Number of megabytes read via single block read requests
SMALL_WRITE_MEGABYTES	NUMBER	Number of megabytes written via single block write requests
LARGE_READ_MEGABYTES	NUMBER	Number of megabytes read via multiblock read requests
LARGE_WRITE_MEGABYTES	NUMBER	Number of megabytes written via multiblock write requests
SMALL_READ_REQS	NUMBER	Number of single block read requests
SMALL_WRITE_REQS	NUMBER	Number of single block write requests
LARGE_READ_REQS	NUMBER	Number of multiblock read requests
LARGE_WRITE_REQS	NUMBER	Number of multiblock write requests
NUMBER_OF_WAITS	NUMBER	Number of synchronous I/O waits by functionality
WAIT_TIME	NUMBER	Total synchronous I/O wait time (in milliseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.22 V$IOSTAT_NETWORK

V$IOSTAT_NETWORK displays information about network I/O statistics that were caused by accessing files on a remote database instance.

Column	Datatype	Description
CLIENT	VARCHAR2(32)	Database client name initiating the network I/O (for example, RMAN or PL/SQL)
READS#	NUMBER	Number of read operations issued
WRITES#	NUMBER	Number of write operations issued
KBYTES_READ	NUMBER	Total number of kilobytes read
KBYTES_WRITTEN	NUMBER	Total number of kilobytes written

Column	Datatype	Description
READ_LATENCY	NUMBER	Total read wait time (in milliseconds)
WRITE_LATENCY	NUMBER	Total write wait time (in milliseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.23 V$IP_ACL

V$IP_ACL provides information about access control to database services from network hosts.

Column	Datatype	Description
SERVICE_NAME	VARCHAR2(512)	The database service name
HOST	VARCHAR2(64)	The host being granted access to the SERVICE_NAME. The host can be a hostname, dotted-decimal IPv4 or heximal IPv6 address. Wildcard "*" for IPv4 and Classless Inter-Domain Routing (CIDR) format is allowed.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs • 1: This value is used for rows containing data that pertain only to the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.24 V$JAVA_LIBRARY_CACHE_MEMORY

V$JAVA_LIBRARY_CACHE_MEMORY displays information about memory allocated to library cache memory objects in different namespaces for Java objects.

A memory object is an internal grouping of memory for efficient management. A library cache object may consist of one or more memory objects.

Column	Datatype	Description
LC_NAMESPACE	VARCHAR2(15)	Library cache namespace
LC_INUSE_MEMORY_OBJECTS	NUMBER	Number of library cache memory objects currently in use in the Java pool
LC_INUSE_MEMORY_SIZE	NUMBER	Total size of library cache in-use memory objects (in megabytes)
LC_FREEABLE_MEMORY_OBJECTS	NUMBER	Number of freeable library cache memory objects in the Java pool

Column	Datatype	Description
LC_FREEABLE_MEMORY_SIZE	NUMBER	Size of library cache freeable memory objects (in megabytes)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.25 V$JAVA_POOL_ADVICE

V$JAVA_POOL_ADVICE displays information about estimated parse time in the Java pool for different pool sizes.

The sizes range from 10% of the current Java pool size or the amount of pinned Java library cache memory (whichever is higher) to 200% of the current Java pool size, in equal intervals. The value of the interval depends on the current size of the Java pool.

Parse time saved refers to the amount of time saved by keeping library cache memory objects in the Java pool, as opposed to having to reload these objects.

Column	Datatype	Description
JAVA_POOL_SIZE_FOR_ESTIMATE	NUMBER	Java pool size for the estimate (in megabytes)
JAVA_POOL_SIZE_FACTOR	NUMBER	Size factor with respect to the current Java pool size
ESTD_LC_SIZE	NUMBER	Estimated memory in use by the library cache (in megabytes)
ESTD_LC_MEMORY_OBJECTS	NUMBER	Estimated number of library cache memory objects in the Java pool of the specified size
ESTD_LC_TIME_SAVED	NUMBER	Estimated elapsed parse time saved (in seconds), owing to library cache memory objects being found in a Java pool of the specified size. This is the time that would have been spent in reloading the required objects in the Java pool had they been aged out due to insufficient amount of available free memory.
ESTD_LC_TIME_SAVED_FACTOR	NUMBER	Estimated parse time saved factor with respect to the current Java pool size
ESTD_LC_LOAD_TIME	NUMBER	Estimated elapsed time (in seconds) for parsing in a Java pool of the specified size
ESTD_LC_LOAD_TIME_FACTOR	NUMBER	Estimated load time factor with respect to the current Java pool size
ESTD_LC_MEMORY_OBJECT_HITS	NUMBER	Estimated number of times a library cache memory object was found in a Java pool of the specified size

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.26 V$KERNEL_IO_OUTLIER

V$KERNEL_IO_OUTLIER contains entries corresponding to I/Os that have taken a long time (more than 500 ms) to complete.

Use this view to see the individual kernel components of I/Os for which there are any occasional delays in serving disk I/O requests by the storage subsystem.

> **Note:**
>
> Although this view exists on all platforms in Oracle Database 12*c*, it is only populated on the Solaris platform.

Column	Datatype	Description
TIMESTAMP	NUMBER	Number of seconds elapsed since 00:00 UTC, January 1, 1970
IO_SIZE	NUMBER	Size of the I/O, in KB.
IO_OFFSET	NUMBER	Offset into the device of the I/O
DEVICE_NAME	VARCHAR2(513)	Name of the device to which the I/O was targeted
PROCESS_NAME	VARCHAR2(64)	Name of the process that issued the I/O
TOTAL_LATENCY	NUMBER	Total time the I/O spent in the kernel (in milliseconds)
SETUP_LATENCY	NUMBER	Time spent during initial I/O setup before sending to SCSI target device driver (in milliseconds)
QUEUE_TO_HBA_LATENCY	NUMBER	Time spent in the SCSI target device driver before being sent to the Host Bus Adaptor (in milliseconds)
TRANSFER_LATENCY	NUMBER	Time spent in the Host Bus Adaptor and physically transferring the I/O to the storage device (in milliseconds)
CLEANUP_LATENCY	NUMBER	Time spent freeing resources used by the completed I/O (in milliseconds)
PID	NUMBER	Process ID that issued the I/O

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$IO_OUTLIER"
- "V$LGWRIO_OUTLIER"

9.27 V$KEY_VECTOR

V$KEY_VECTOR provides debugging information related to the data structures used by in-memory aggregation for current and recent queries using key vectors.

Column	Datatype	Description
SESSION_ID	NUMBER	Session ID
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
TRANSLATE_ID	NUMBER	Translation vector ID
SQL_ID	VARCHAR2(13)	SQL ID that uses the translation vector
SQL_EXEC_START	DATE	Time when the execution of the SQL started
SQL_EXEC_ID	NUMBER	SQL execution identifier
PROCESS	VARCHAR2(64)	Operating system client process ID

Column	Datatype	Description
STATE	VARCHAR2(9)	State of the in-memory aggregation operation: • BYPASS Refers to key vectors that are currently in use by queries that have undergone the vector transform. • BYPASSED This is a historical entry for key vectors whose queries have already finished. • FINISHED This is a historical entry for key vectors whose queries have already finished. • RUNNING Refers to key vectors that are currently in use by queries that have undergone the vector transform. One query will probably have multiple key vectors if it has gone through the vector transform. Also, if the query is operating in parallel, there may be multiple entries per PX server. The PROCESS column can be joined to V$SESSION to differentiate these cases.
TYPE	VARCHAR2(9)	Type of translation vector created: • DOUBLEIND • PAGED • SIMPLE • INDIRECT • HASH • OFFSET
WIDTH	NUMBER	Width (number of bits) of DOUBLEIND, SIMPLE, INDIRECT, or OFFSETvector translation array: • 1 • 4 • 8 • 16 • 32
KEY_DATA_TYPE	VARCHAR2(13)	The internal join column key data type of either DOUBLEIND, SIMPLE, INDIRECT, or OFFSET translation vectors: • BINARY • BINARY_FLOAT • NUMBER • PACKED_BINARY • PACKED_DATE • PACKED_NUMBER Also, a value of NULL is displayed for HASH translation vectors with non-numeric data types and for HASH translation vectors with more than one join key column.
JOIN_COLUMN_COUNT	NUMBER	Number of join columns. PAGED and HASHED are the only types which can have greater than one join column.
JOIN_KEY_COUNT	NUMBER	Number of join key values used to build translation vector
DUP_JOIN_KEY_COUNT	NUMBER	Indicates the number of key values in the key vector that have more than one parent value

Column	Datatype	Description
MIN_JOIN_KEY	NUMBER	Min join key value in translation vector
MAX_JOIN_KEY	NUMBER	Max join key value in translation vector
GROUP_KEY_COUNT	NUMBER	Max dense grouping key value. This value is computed while the data that creates the translation vector is processed.
FILTERED	NUMBER	Number of rows filtered by translation vector
PROBED	NUMBER	Number of rows that probed the translation vector in key vector use row source
ACTIVE	NUMBER	Number of active translation vectors used as filters across all workers
DISABLED	NUMBER	Number of translation vector filters across all workers that were disabled
MEMORY_ALLOCATED	NUMBER	Amount of memory allocated for the key vector
JOIN_STRUCTURE_SIZE	NUMBER	Amount of memory used out of the allocated space
FACT_OWNER	VARCHAR2(128)	The owner of the fact table. Null when the fact table is null.
FACT_NAME	VARCHAR2(128)	The table that contains measure data. May be null if more than one fact table is used in the query.
DIMENSION_OWNER	VARCHAR2(128)	When a single table is used to construct the key vector, the table owner will appear in this column. If multiple tables are joined to serve as the dimension (more of a snowflake than a star schema shape, for one example), then this column will be null.
DIMENSION_NAME	VARCHAR2(128)	The table that contains attribute data and is joined to the fact table. May be null if two or more tables are used (for example, snowflake style dimension tables).
CREATION_DURATION	NUMBER	Records the total time in seconds that it took to create the key vector
PAYLOAD_COLUMN_COUNT	NUMBER	The number of columns being carried from the dimension table to the fact table scan for processing without joinback
OFFLOADED	VARCHAR2(10)	Indicates whether and how the key vector has been sent to an Exadata cell. Possible values: • NO: The key vector has not been sent to an Exadata cell. • YES: The key vector was fully sent to an Exadata cell. • COMPRESSED: The key vector was fully sent to an Exadata cell and was compressed. • EFILTER: The key vector could not be sent to an Exadata cell due to the size of another constraint. Instead, a bloom filter-like data structure was sent to aid filtration.
COMPRESSED_SIZE	NUMBER	If the value of OFFLOADED is COMPRESSED, then this column displays the compressed size of metadata transmitted to the Exadata cell (in bytes)
EFILTER_SIZE	NUMBER	If the value of OFFLOADED is EFILTER, then this column displays the size of the data structure sent to the Exadata cell (in bytes)

> **See Also:**
>
> *Oracle Database SQL Tuning Guide* for more information about in-memory aggregation

9.28 V$LATCH

V$LATCH displays aggregate latch statistics for both parent and child latches, grouped by latch name.

Individual parent and child latch statistics are broken down in the views V$LATCH_PARENT and V$LATCH_CHILDREN.

Column	Datatype	Description
ADDR	RAW(4 | 8)	Address of the latch object
LATCH#	NUMBER	Latch number
LEVEL#	NUMBER	Latch level
NAME	VARCHAR2(64)	Latch name
HASH	NUMBER	Latch hash
GETS	NUMBER	Number of times the latch was requested in willing-to-wait mode
MISSES	NUMBER	Number of times the latch was requested in willing-to-wait mode and the requester had to wait
SLEEPS	NUMBER	Number of times a willing-to-wait latch request resulted in a session sleeping while waiting for the latch
IMMEDIATE_GETS	NUMBER	Number of times a latch was requested in no-wait mode
IMMEDIATE_MISSES	NUMBER	Number of times a no-wait latch request did not succeed (that is, missed)
WAITERS_WOKEN	NUMBER	This column has been deprecated and is present only for compatibility with previous releases of Oracle. No data is accumulated for this column; it will always have a value of zero.
WAITS_HOLDING_LATCH	NUMBER	This column has been deprecated and is present only for compatibility with previous releases of Oracle. No data is accumulated for this column; it will always have a value of zero.
SPIN_GETS	NUMBER	Willing-to-wait latch requests which missed the first try but succeeded while spinning
SLEEP[1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11]	NUMBER	These columns have been deprecated and are present only for compatibility with previous releases of Oracle. No data is accumulated for these columns; they will always have a value of zero. As a substitute for these columns you can query the appropriate rows of the V$EVENT_HISTOGRAM view where the EVENT column has a value of latch free or latch:%.
WAIT_TIME	NUMBER	Elapsed time spent waiting for the latch (in microseconds)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$LATCH_CHILDREN"
- "V$LATCH_PARENT"

9.29 V$LATCH_CHILDREN

V$LATCH_CHILDREN displays statistics about child latches.

This view includes all columns of V$LATCH plus the CHILD# column. Note that child latches have the same parent if their LATCH# columns match each other.

Column	Datatype	Description
ADDR	RAW(4 | 8)	Address of the latch object
LATCH#	NUMBER	Latch number of the parent latch
CHILD#	NUMBER	Child latch number (unique only to each parent latch)
LEVEL#	NUMBER	Latch level
NAME	VARCHAR2(64)	Latch name
HASH	NUMBER	Latch hash
GETS	NUMBER	Number of times the latch was requested in willing-to-wait mode
MISSES	NUMBER	Number of times the latch was requested in willing-to-wait mode and the requester had to wait
SLEEPS	NUMBER	Number of times a willing-to-wait latch request resulted in a session sleeping while waiting for the latch
IMMEDIATE_GETS	NUMBER	Number of times a latch was requested in no-wait mode
IMMEDIATE_MISSES	NUMBER	Number of times a no-wait latch request did not succeed (that is, missed)
WAITERS_WOKEN	NUMBER	This column has been deprecated and is present only for compatibility with previous releases of Oracle. No data is accumulated for this column; it will always have a value of zero.
WAITS_HOLDING_LATCH	NUMBER	This column has been deprecated and is present only for compatibility with previous releases of Oracle. No data is accumulated for this column; it will always have a value of zero.

Column	Datatype	Description
SPIN_GETS	NUMBER	Willing-to-wait latch requests which missed the first try but succeeded while spinning
SLEEP[1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11]	NUMBER	These columns have been deprecated and are present only for compatibility with previous releases of Oracle. No data is accumulated for these columns; they will always have a value of zero. As a substitute for these columns you can query the appropriate rows of the V$EVENT_HISTOGRAM view where the EVENT column has a value of latch free or latch:%.
WAIT_TIME	NUMBER	Elapsed time spent waiting for the latch (in microseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$LATCH"

9.30 V$LATCH_MISSES

V$LATCH_MISSES displays statistics about missed attempts to acquire a latch.

Column	Datatype	Description
PARENT_NAME	VARCHAR2(64)	Latch name of a parent latch
WHERE	VARCHAR2(80)	This column is obsolete and maintained for backward compatibility. The value of this column is always equal to the value in LOCATION.
NWFAIL_COUNT	NUMBER	Number of times that no-wait acquisition of the latch failed
SLEEP_COUNT	NUMBER	Number of times that acquisition attempts caused sleeps
WTR_SLP_COUNT	NUMBER	Number of times a waiter slept
LONGHOLD_COUNT	NUMBER	Number of times someone held a latch for the entire duration of someone else's sleep
LOCATION	VARCHAR2(80)	Location that attempted to acquire the latch
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.31 V$LATCH_PARENT

V$LATCH_PARENT displays statistics about parent latches.

\ The columns for V$LATCH_PARENT are the same as those for V$LATCH.

> **See Also:**
>
> "V$LATCH"

9.32 V$LATCHHOLDER

V$LATCHHOLDER displays information about the current latch holders.

Column	Datatype	Description
PID	NUMBER	Identifier of the process holding the latch
SID	NUMBER	Identifier of the session that owns the latch
LADDR	RAW(4 | 8)	Latch address
NAME	VARCHAR2(64)	Name of the latch being held
GETS	NUMBER	Number of times that the latch was obtained in either wait mode or no-wait mode
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.33 V$LATCHNAME

V$LATCHNAME displays information about decoded latch names for the latches shown in V$LATCH.

The rows of V$LATCHNAME have a one-to-one correspondence to the rows of V$LATCH.

Column	Datatype	Description
LATCH#	NUMBER	Latch number
NAME	VARCHAR2(64)	Latch name
DISPLAY_NAME	VARCHAR2(64)	A clearer and more descriptive name for the latch that appears in the NAME column. Names that appear in the DISPLAY_NAME column can change across Oracle Database releases, therefore customer scripts should not rely on names that appear in the DISPLAY_NAME column across releases.

Column	Datatype	Description
HASH	NUMBER	Latch hash
TYPE	VARCHAR2(4)	Type of the latch (SGA, PDB, or OSP):
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$LATCH"

9.34 V$LCR_CACHE

V$LCR_CACHE displays information about entries in the logical change record (LCR) cache.

Column	Datatype	Description
LCR_TYPE	CHAR(12)	Indicates whether the LCR is INTERNAL or EXTERNAL
COMPONENT_NAME	VARCHAR2(128)	Component name
COMPONENT_TYPE	VARCHAR2(40)	Component type. Possible values: • APPLY COORDINATOR • APPLY READER • APPLY SERVER • CAPTURE COORDINATOR • CAPTURE READER • CAPTURE SERVER
NUM_COLUMNS	NUMBER	Number of columns in the LCR
FREE_COUNT	NUMBER	Number of available LCRs
REQUEST_COUNT	NUMBER	Total request count
CACHE_HITS	NUMBER	Cache hit count
ALT_CACHE_HITS	NUMBER	Hit count from an alternate LCR cache entry
PURGED_COUNT	NUMBER	Cache purge count
SID	NUMBER	Session ID of the component process
SERIAL#	NUMBER	Session serial number of the component process

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.35 V$LGWRIO_OUTLIER

V$LGWRIO_OUTLIER contains entries corresponding to Log Writer (LGWR) process I/Os that have taken a long time (more than 500 ms) to complete. Use this view to see if there any occasional delays in serving disk I/O requests by the storage subsystem.

Column	Datatype	Description
FUNCTION_NAME	VARCHAR2(18)	I/O function name of the delayed I/O
IO_SIZE	NUMBER	Size of the I/O in bytes
WAIT_EVENT	VARCHAR2(64)	Wait event name that was used to track the I/O
FILE_NAME	VARCHAR2(513)	Name of the file to which the I/O was targeted
IO_LATENCY	NUMBER	Time taken to complete the I/O (in milliseconds)
DISK1_NAME	VARCHAR2(255)	For Oracle ASM, the name of the first disk to which the I/O was issued
DISK1_LATENCY	NUMBER	Latency seen on the first disk (in milliseconds)
DISK2_NAME	VARCHAR2(255)	For Oracle ASM, the name of the second disk to which the I/O was issued
DISK2_LATENCY	NUMBER	Latency seen on the second disk (in milliseconds)
DISK3_NAME	VARCHAR2(255)	For Oracle ASM, the name of the third disk to which the I/O was issued
DISK3_LATENCY	NUMBER	Latency seen on the third disk (in milliseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$IO_OUTLIER"
- "V$KERNEL_IO_OUTLIER"

9.36 V$LIBCACHE_LOCKS

V$LIBCACHE_LOCKS displays information about the library cache locks and pins. Locks and pins are distinguished based on the value of the TYPE column.

Column	Datatype	Description
TYPE	VARCHAR2(4)	LOCK or PIN
ADDR	RAW(4 | 8)	Address of the lock/pin
HOLDING_USER_SESSION	RAW(4 | 8)	User session holding this lock/pin
HOLDING_SESSION	RAW(4 | 8)	Session holding this lock/pin
OBJECT_HANDLE	RAW(4 | 8)	Handle address for which the lock/pin is acquired
LOCK_HELD	RAW(4 | 8)	If the type is LOCK, then LOCK_HELD represents the pin that is pinning the object. If the type is PIN, then LOCK_HELD represents the lock that is locking the object.
REFCOUNT	NUMBER	Reference count for this lock/pin
MODE_HELD	NUMBER	Lock/pin mode held: • 0 - No lock/pin held • 1 - Null mode • 2 - Share mode • 3 - Exclusive mode
MODE_REQUESTED	NUMBER	Lock/pin mode requested: • 0 - No lock/pin requested • 1 - Null mode • 2 - Share mode • 3 - Exclusive mode
SAVEPOINT_NUMBER	NUMBER	Kernel transaction savepoint number at the time the lock/pin was acquired
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.37 V$LIBRARY_CACHE_MEMORY

V$LIBRARY_CACHE_MEMORY displays information about memory allocated to library cache memory objects in different namespaces.

A memory object is an internal grouping of memory for efficient management. A library cache object may consist of one or more memory objects.

Column	Datatype	Description
LC_NAMESPACE	VARCHAR2(15)	Library cache namespace

Column	Datatype	Description
LC_INUSE_MEMORY_OBJECTS	NUMBER	Number of library cache memory objects currently in use in the shared pool
LC_INUSE_MEMORY_SIZE	NUMBER	Total size of library cache in-use memory objects (in megabytes)
LC_FREEABLE_MEMORY_OBJECTS	NUMBER	Number of freeable library cache memory objects in the shared pool
LC_FREEABLE_MEMORY_SIZE	NUMBER	Size of library cache freeable memory objects (in megabytes)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.38 V$LIBRARYCACHE

V$LIBRARYCACHE contains statistics about library cache performance and activity.

Column	Datatype	Description
NAMESPACE	VARCHAR2(64)	Library cache namespace
GETS	NUMBER	Number of times a lock was requested for objects of this namespace
GETHITS	NUMBER	Number of times an object's handle was found in memory
GETHITRATIO	NUMBER	Ratio of GETHITS to GETS
PINS	NUMBER	Number of times a PIN was requested for objects of this namespace
PINHITS	NUMBER	Number of times all of the metadata pieces of the library object were found in memory
PINHITRATIO	NUMBER	Ratio of PINHITS to PINS
RELOADS	NUMBER	Any PIN of an object that is not the first PIN performed since the object handle was created, and which requires loading the object from disk
INVALIDATIONS	NUMBER	Total number of times objects in this namespace were marked invalid because a dependent object was modified
DLM_LOCK_REQUESTS	NUMBER	Number of GET requests lock instance locks
DLM_PIN_REQUESTS	NUMBER	Number of PIN requests lock instance locks
DLM_PIN_RELEASES	NUMBER	Number of release requests PIN instance locks
DLM_INVALIDATION_REQUESTS	NUMBER	Number of GET requests for invalidation instance locks
DLM_INVALIDATIONS	NUMBER	Number of invalidation pings received from other instances

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.39 V$LICENSE

V$LICENSE displays information about license limits.

Column	Datatype	Description
SESSIONS_MAX	NUMBER	Maximum number of concurrent user sessions allowed for the instance
SESSIONS_WARNING	NUMBER	Warning limit for concurrent user sessions for the instance
SESSIONS_CURRENT	NUMBER	Current number of concurrent user sessions
SESSIONS_HIGHWATER	NUMBER	Highest number of concurrent user sessions since the instance started
USERS_MAX	NUMBER	Maximum number of named users allowed for the database
CPU_COUNT_CURRENT	NUMBER	Current number of logical CPUs or processors on the system
CPU_CORE_COUNT_CURRENT	NUMBER	Current number of CPU cores on the system (includes subcores of multicore CPUs, as well as single-core CPUs)
CPU_SOCKET_COUNT_CURRENT	NUMBER	Current number of CPU sockets on the system (represents an absolute count of CPU chips on the system, regardless of multithreading or multicore architectures)
CPU_COUNT_HIGHWATER	NUMBER	Highest number of logical CPUs or processors on the system since the instance started
CPU_CORE_COUNT_HIGHWATER	NUMBER	Highest number of CPU cores on the system since the instance started (includes subcores of multicore CPUs, as well as single-core CPUs)
CPU_SOCKET_COUNT_HIGHWATER	NUMBER	Highest number of CPU sockets on the system since the instance started (represents an absolute count of CPU chips on the system, regardless of multithreading or multicore architectures)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> The availability of the CPU core count and CPU socket count statistics is subject to the operating system platform on which the Oracle Database is running. If a statistic is unavailable, the view will return NULL for the statistic value.

9.40 V$LOADISTAT

`V$LOADISTAT` contains errors that occurred when updating indexes on a table during a load using the Direct Path API.

Column	Datatype	Description
`OWNER`	`VARCHAR2(31)`	Schema name
`TABNAME`	`VARCHAR2(31)`	Table name
`INDEXNAME`	`VARCHAR2(31)`	Index name
`SUBNAME`	`VARCHAR2(31)`	Index sub name
`MESSAGE_NUM`	`NUMBER`	Error message number
`MESSAGE`	`VARCHAR2(4000)`	Error message
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.41 V$LOADPSTAT

`V$LOADPSTAT` contains statistics about the number of rows loaded into a partition, or subpartition, during a load using the Direct Path API.

Column	Datatype	Description
`OWNER`	`VARCHAR2(31)`	Schema name
`TABNAME`	`VARCHAR2(31)`	Table name
`PARTNAME`	`VARCHAR2(31)`	Partition name
`LOADED`	`NUMBER`	Number of rows loaded
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.42 V$LOCK

V$LOCK lists the locks currently held by the Oracle Database and outstanding requests for a lock or latch.

Column	Datatype	Description
ADDR	RAW(4 | 8)	Address of lock state object
KADDR	RAW(4 | 8)	Address of lock
SID	NUMBER	Identifier for session holding or acquiring the lock
TYPE	VARCHAR2(2)	Type of user or system lock The locks on the user types are obtained by user applications. Any process that is blocking others is likely to be holding one of these locks. The user type locks are: TM - DML enqueue TX - Transaction enqueue UL - User supplied The system type locks are listed in Table 9-1. Be aware that not all types of locks are documented. To find a complete list of locks for the current release, query the V$LOCK_TYPE data dictionary view, described on "V$LOCK_TYPE".
ID1	NUMBER	Lock identifier #1 (depends on type)
ID2	NUMBER	Lock identifier #2 (depends on type)
LMODE	NUMBER	Lock mode in which the session holds the lock: • 0 - none • 1 - null (NULL) • 2 - row-S (SS) • 3 - row-X (SX) • 4 - share (S) • 5 - S/Row-X (SSX) • 6 - exclusive (X)
REQUEST	NUMBER	Lock mode in which the process requests the lock: • 0 - none • 1 - null (NULL) • 2 - row-S (SS) • 3 - row-X (SX) • 4 - share (S) • 5 - S/Row-X (SSX) • 6 - exclusive (X)
CTIME	NUMBER	Time since current mode was granted
BLOCK	NUMBER	Indicates whether the lock in question is blocking other processes. The possible values are: • 0 - The lock is not blocking any other processes • 1 - The lock is blocking other processes • 2 - The lock is not blocking any blocked processes on the local node, but it may or may not be blocking processes on remote nodes. This value is used only in Oracle Real Application Clusters (Oracle RAC) configurations (not in single instance configurations).

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Table 9-1 Values for the TYPE Column: System Types

System Type	Description	System Type	Description
AE	Edition enqueue	MR	Media recovery
AT	Lock held for the ALTER TABLE statement	NA..NZ	Library cache pin instance (A..Z = namespace)
BL	Buffer hash table instance	PF	Password File
CF	Control file schema global enqueue	PI, PS	Parallel operation
CI	Cross-instance function invocation instance	PR	Process startup
CU	Cursor bind	QA..QZ	Row cache instance (A..Z = cache)
DF	datafile instance	RT	Redo thread global enqueue
DL	Direct loader parallel index create	SC	System change number instance
DM	Mount/startup db primary/secondary instance	SM	SMON
DR	Distributed recovery process	SN	Sequence number instance
DX	Distributed transaction entry	SQ	Sequence number enqueue
FS	File set	SS	Sort segment
HW	Space management operations on a specific segment	ST	Space transaction enqueue
IN	Instance number	SV	Sequence number value
IR	Instance recovery serialization global enqueue	TA	Generic enqueue
IS	Instance state	TS	Temporary segment enqueue (ID2=0)
IV	Library cache invalidation instance	TS	New block allocation enqueue (ID2=1)
JQ	Job queue	TT	Temporary table enqueue
KK	Thread kick	UN	User name
LA .. LP	Library cache lock instance lock (A..P = namespace)	US	Undo segment DDL
MM	Mount definition global enqueue	WL	Being-written redo log instance

9.43 V$LOCK_ACTIVITY

`V$LOCK_ACTIVITY` is deprecated. The information that was provided in this view is now provided in the `V$INSTANCE_CACHE_TRANSFER` and `V$SEGMENT_STATISTICS` views.

Column	Datatype	Description
`FROM_VAL`	`CHAR(4)`	Global Cache Resource initial state; always `NULL`
`TO_VAL`	`CHAR(1)`	Global Cache Resource initial state; always `S`
`ACTION_VAL`	`CHAR(21)`	Description of the conversion; always `Lock buffers for read`
`COUNTER`	`NUMBER`	Number of times the lock operation executed
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$INSTANCE_CACHE_TRANSFER"
- "V$SEGMENT_STATISTICS"

9.44 V$LOCK_TYPE

`V$LOCK_TYPE` describes the type of locks available.

Column	Datatype	Description
`TYPE`	`VARCHAR2(64)`	A two-letter internal resource identifier
`NAME`	`VARCHAR2(64)`	Resource type name. This is a short (less than 32 characters) enqueue type name.
`ID1_TAG`	`VARCHAR2(64)`	Description of the enqueue type.
`ID2_TAG`	`VARCHAR2(64)`	Further description of the enqueue type.
`IS_USER`	`VARCHAR2(3)`	User enqueue. These are enqueues that are acquired as a direct result of a SQL statement. Applications may get deadlocks on these enqueues. Such deadlocks are considered application errors.

Column	Datatype	Description
IS_RECYCLE	VARCHAR2(3)	Indicates whether the enqueue requires caching of the associated resource in the DLM's resource cache. Possible values: • NO: Means the enqueue requires caching of the associated resource in the DLM's resource cache • YES: Means the enqueue does not require caching of the associated resource in the DLM's resource cache
DESCRIPTION	VARCHAR2(4000)	Explanation of how or for what purpose the enqueue is used.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.45 V$LOCKDOWN_RULES

V$LOCKDOWN_RULES displays information about lockdown profile rules that are applicable in the pluggable database (PDB) where this view is queried.

Column	Datatype	Description
RULE_TYPE	VARCHAR2(128)	Type of the rule: • STATEMENT • FEATURE • OPTION
RULE	VARCHAR2(128)	Rule to be enabled or disabled
CLAUSE	VARCHAR2(128)	Clause of the statement
CLAUSE_OPTION	VARCHAR2(128)	Option of the clause
STATUS	VARCHAR2(7)	Status of the lockdown profile: • ENABLE • DISABLE • EMPTY
USERS	VARCHAR2(6)	Type of users affected by the rule: • ALL • LOCAL • COMMON
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs • 1: This value is used for rows containing data that pertain to only the root. • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Security Guide* for more information about PDB lockdown profiles

9.46 V$LOCKED_OBJECT

V$LOCKED_OBJECT lists all locks acquired by every transaction on the system. It shows which sessions are holding DML locks (that is, TM-type enqueues) on what objects and in what mode.

Column	Datatype	Description
XIDUSN	NUMBER	Undo segment number
XIDSLOT	NUMBER	Slot number
XIDSQN	NUMBER	Sequence number
OBJECT_ID	NUMBER	Object ID being locked
SESSION_ID	NUMBER	Session ID
ORACLE_USERNAME	VARCHAR2(128)	Oracle user name
OS_USER_NAME	VARCHAR2(128)	Operating system user name
PROCESS	VARCHAR2(24)	Operating system process ID
LOCKED_MODE	NUMBER	Lock mode. The numeric values for this column map to these text values for the lock modes for table locks: • 0 - NONE: lock requested but not yet obtained • 1 - NULL • 2 - ROWS_S (SS): Row Share Lock • 3 - ROW_X (SX): Row Exclusive Table Lock • 4 - SHARE (S): Share Table Lock • 5 - S/ROW-X (SSX): Share Row Exclusive Table Lock • 6 - Exclusive (X): Exclusive Table Lock **See Also:** *Oracle Database Concepts* for more information about lock modes for table locks
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.47 V$LOG

V$LOG displays log file information from the control file.

Column	Datatype	Description
GROUP#	NUMBER	Log group number
THREAD#	NUMBER	Log thread number
SEQUENCE#	NUMBER	Log sequence number
BYTES	NUMBER	Size of the log (in bytes)
BLOCKSIZE	NUMBER	Block size of the logfile (512 or 4096)
MEMBERS	NUMBER	Number of members in the log group
ARCHIVED	VARCHAR2(3)	Archive status (YES) or (NO)
STATUS	VARCHAR2(16)	Log status: • UNUSED - Online redo log has never been written to. This is the state of a redo log that was just added, or just after a RESETLOGS, when it is not the current redo log. • CURRENT - Current redo log. This implies that the redo log is active. The redo log could be open or closed. • ACTIVE - Log is active but is not the current log. It is needed for crash recovery. It may be in use for block recovery. It may or may not be archived. • CLEARING - Log is being re-created as an empty log after an ALTER DATABASE CLEAR LOGFILE statement. After the log is cleared, the status changes to UNUSED. • CLEARING_CURRENT - Current log is being cleared of a closed thread. The log can stay in this status if there is some failure in the switch such as an I/O error writing the new log header. • INACTIVE - Log is no longer needed for instance recovery. It may be in use for media recovery. It may or may not be archived.
FIRST_CHANGE#	NUMBER	Lowest system change number (SCN) in the log
FIRST_TIME	DATE	Time of the first SCN in the log
NEXT_CHANGE#	NUMBER	Highest change number (SCN) in the log When STATUS=CURRENT, NEXT_CHANGE# is set to the highest possible SCN, 9295429630892703743.
NEXT_TIME	DATE	Time of the highest SCN in the log. When STATUS=CURRENT, NEXT_TIME is set to NULL.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.48 V$LOG_HISTORY

V$LOG_HISTORY displays log history information from the control file.

Column	Datatype	Description
RECID	NUMBER	Control file record ID

Column	Datatype	Description
STAMP	NUMBER	Control file record stamp
THREAD#	NUMBER	Thread number of the archived log
SEQUENCE#	NUMBER	Sequence number of the archived log
FIRST_CHANGE#	NUMBER	Lowest system change number (SCN) in the log
FIRST_TIME	DATE	Time of the first entry (lowest SCN) in the log
NEXT_CHANGE#	NUMBER	Highest SCN in the log
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the database when the log was written
RESETLOGS_TIME	DATE	Resetlogs time of the database when the log was written
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.49 V$LOGFILE

V$LOGFILE contains information about redo log files.

Column	Datatype	Description
GROUP#	NUMBER	Redo log group identifier number
STATUS	VARCHAR2(7)	Status of the log member: • INVALID - File is inaccessible • STALE - File's contents are incomplete • DELETED - File is no longer used • null - File is in use
TYPE	VARCHAR2(7)	Type of the logfile: • ONLINE • STANDBY
MEMBER	VARCHAR2(513)	Redo log member name
IS_RECOVERY_DEST_FILE	VARCHAR2(3)	Indicates whether the file was created in the fast recovery area (YES) or not (NO)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.50 V$LOGHIST

V$LOGHIST contains log history information from the control file. This view is retained for historical compatibility. Oracle recommends that you use V$LOG_HISTORY instead.

> **See Also:**
>
> "V$LOG_HISTORY"

Column	Datatype	Description
THREAD#	NUMBER	Log thread number
SEQUENCE#	NUMBER	Log sequence number
FIRST_CHANGE#	NUMBER	Lowest SCN in the log
FIRST_TIME	DATE	Time of first SCN in the log
SWITCH_CHANGE#	NUMBER	SCN at which the log switch occurred; one more than highest SCN in the log
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.51 V$LOGMNR_CONTENTS

V$LOGMNR_CONTENTS contains log history information. To query this view, you must have the LOGMINING privilege.

When a SELECT statement is executed against the V$LOGMNR_CONTENTS view, the archive redo log files are read sequentially. Translated records from the redo log files are returned as rows in the V$LOGMNR_CONTENTS view. This continues until either the filter criteria specified at startup (EndTime or endScn) are met or the end of the archive log file is reached.

When this view is queried from a PDB, it returns only redo generated by that PDB.

Column	Datatype	Description
SCN	NUMBER	System change number (SCN) when the database change was made
START_SCN	NUMBER	System change number (SCN) when the transaction that contains this change started; only meaningful if the COMMITTED_DATA_ONLY option was chosen in a DBMS_LOGMNR.START_LOGMNR() invocation, NULL otherwise. This column may also be NULL if the query is run over a time/SCN range that does not contain the start of the transaction.

Column	Datatype	Description
COMMIT_SCN	NUMBER	System change number (SCN) when the transaction committed; only meaningful if the COMMITTED_DATA_ONLY option was chosen in a DBMS_LOGMNR.START_LOGMNR() invocation
TIMESTAMP	DATE	Timestamp when the database change was made
START_TIMESTAMP	DATE	Timestamp when the transaction that contains this change started; only meaningful if the COMMITTED_DATA_ONLY option was chosen in a DBMS_LOGMNR.START_LOGMNR() invocation, NULL otherwise. This column may also be NULL if the query is run over a time/SCN range that does not contain the start of the transaction.
COMMIT_TIMESTAMP	DATE	Timestamp when the transaction committed; only meaningful if the COMMITTED_DATA_ONLY option was chosen in a DBMS_LOGMNR.START_LOGMNR() invocation
XIDUSN	NUMBER	Transaction ID undo segment number of the transaction that generated the change
XIDSLT	NUMBER	Transaction ID slot number of the transaction that generated the change
XIDSQN	NUMBER	Transaction ID sequence number of the transaction that generated the change
XID	RAW(8)	Raw representation of the transaction identifier
PXIDUSN	NUMBER	Parent transaction ID undo segment number of a parallel transaction
PXIDSLT	NUMBER	Parent transaction ID slot number of a parallel transaction
PXIDSQN	NUMBER	Parent transaction ID sequence number of a parallel transaction
PXID	RAW(8)	Raw representation of the parent transaction identifier
TX_NAME	VARCHAR2(256)	Name of the transaction that made the change; only meaningful if the transaction is a named transaction

Column	Datatype	Description
OPERATION	VARCHAR2(32)	User level SQL operation that made the change: • INTERNAL - Change was caused by internal operations initiated by the database • INSERT - Change was caused by an insert statement • DELETE - Change was caused by a delete statement • UPDATE - Change was caused by an update statement • DDL - Change was caused by a DDL statement • START - Change was caused by the start of a transaction • COMMIT - Change was caused by the commit of a transaction • SEL_LOB_LOCATOR - Operation was a SELECT statement that returned a LOB locator • LOB_WRITE - Change was caused by an invocation of DBMS_LOB.WRITE • LOB_TRIM - Change was caused by an invocation of DBMS_LOB.TRIM • SELECT_FOR_UPDATE - Operation was a SELECT FOR UPDATE statement • LOB_ERASE - Change was caused by an invocation of DBMS_LOB.ERASE • MISSING_SCN - LogMiner encountered a gap in the redo records. This is most likely because not all redo logs were registered with LogMiner. • ROLLBACK - Change was caused by a full rollback of a transaction • XML DOC BEGIN - Beginning of a change to an XMLType column or table • XML DOC WRITE - Data for an XML document • XML DOC END - End of the Data for an XML document • UNSUPPORTED - Change was caused by operations not currently supported by LogMiner (for example, changes made to nested tables) The OPERATION and OPERATION_CODE columns in this view are available for top-level user operations, for example, DML and DDL. Values that are not documented for these columns are internal to LogMiner or the RDBMS and do not reflect user operations.

Column	Datatype	Description
OPERATION_CODE	NUMBER	Number of the operation code: • 0 - INTERNAL • 1 - INSERT • 2 - DELETE • 3 - UPDATE • 5 - DDL • 6 - START • 7 - COMMIT • 9 - SELECT_LOB_LOCATOR • 10 - LOB_WRITE • 11 - LOB_TRIM • 25 - SELECT_FOR_UPDATE • 29 - LOB_ERASE • 34 - MISSING_SCN • 36 - ROLLBACK • 68 - XML DOC BEGIN • 70 = XML DOC WRITE • 71 = XML DOC END • 255 - UNSUPPORTED
ROLLBACK	NUMBER	1 = if the redo record was generated because of a partial or a full rollback of the associated transaction 0 = otherwise
SEG_OWNER	VARCHAR2(386)	Owner of the modified data segment
SEG_NAME	VARCHAR2(256)	Name of the modified data segment
TABLE_NAME	VARCHAR2(386)	Name of the modified table (in case the redo pertains to a table modification)
SEG_TYPE	NUMBER	Type of the modified data segment: • 0 - UNKNOWN • 1 - INDEX • 2 - TABLE • 19 - TABLE PARTITION • 20 - INDEX PARTITION • 34 - TABLE SUBPARTITION • All other values - UNSUPPORTED
SEG_TYPE_NAME	VARCHAR2(32)	Segment type name: • UNKNOWN • INDEX • TABLE • TABLE PARTITION • INDEX PARTITION • TABLE SUBPARTITION • UNSUPPORTED
TABLE_SPACE	VARCHAR2(92)	Name of the tablespace containing the modified data segment. This column is not populated for rows where the value of the OPERATION column is DDL. This is because DDL may operate on more than one tablespace.
ROW_ID	VARCHAR2(18)	Row ID of the row modified by the change (only meaningful if the change pertains to a DML). This will be NULL if the redo record is not associated with a DML.

Column	Datatype	Description
USERNAME	VARCHAR2(384)	Name of the user who executed the transaction
OS_USERNAME	VARCHAR2(4000)	Name of the operating system user
MACHINE_NAME	VARCHAR2(4000)	Machine from which the user connected to the database
AUDIT_SESSIONID	NUMBER	Audit session ID associated with the user session making the change
SESSION#	NUMBER	Session number of the session that made the change
SERIAL#	NUMBER	Serial number of the session that made the change
SESSION_INFO	VARCHAR2(4000)	Information about the database session that executed the transaction. Contains process information, machine name from which the user logged in, and so on. A possible SESSION_INFO column may contain the following: • login_username = HR • client_info = • OS_username = jkundu • Machine_name = nirvan • OS_terminal = pts/31 • OS_program_name = sqlplus@nirvan (TNS V1-V3)
THREAD#	NUMBER	Number of the thread that made the change to the database
SEQUENCE#	NUMBER	Sequence number of the SQL statement within the transaction. If you are mining without the COMMITED_DATA_ONLY option set, then this value is 1.
RBASQN	NUMBER	Sequence# associated with the Redo Block Address (RBA) of the redo record associated with the change
RBABLK	NUMBER	RBA block number within the log file
RBABYTE	NUMBER	RBA byte offset within the block
UBAFIL	NUMBER	Undo Block Address (UBA) file number identifying the file containing the undo block
UBABLK	NUMBER	UBA block number for the undo block
UBAREC	NUMBER	UBA record index within the undo block
UBASQN	NUMBER	UBA undo block sequence number
ABS_FILE#	NUMBER	Data block absolute file number of the block changed by the transaction
REL_FILE#	NUMBER	Data block relative file number. The file number is relative to the tablespace of the object.
DATA_BLK#	NUMBER	Data block number within the file
DATA_OBJ#	NUMBER	Data block object number identifying the object
DATA_OBJV#	NUMBER	Version number of the table being modified
DATA_OBJD#	NUMBER	Data block data object number identifying the object within the tablespace
SQL_REDO	VARCHAR2(4000)	Reconstructed SQL statement that is equivalent to the original SQL statement that made the change. Refer to *Oracle Database Utilities* before executing SQL_REDO to your database. LogMiner does not generate SQL redo for temporary tables. In such a case, this column will contain the string "/* No SQL_REDO for temporary tables */".

Column	Datatype	Description
SQL_UNDO	VARCHAR2(4000)	Reconstructed SQL statement that can be used to undo the effect of the original statement that made the change. DDL statements have no corresponding SQL_UNDO. Refer to *Oracle Database Utilities* before executing SQL_UNDO to your database. LogMiner does not generate SQL undo for temporary tables. In such a case, this column will contain the string "/* No SQL_UNDO for temporary tables */".
RS_ID	VARCHAR2(32)	Record set ID. The tuple (RS_ID, SSN) together uniquely identifies a logical row change. This will usually mean one row from V$LOGMNR_CONTENTS, but could be more than one row if a single SQL statement for either the Redo or Undo would be too large to fit within the respective columns SQL_UNDO or SQL_REDO. RS_ID uniquely identifies the redo record that generated the row.
SSN	NUMBER	SQL sequence number. Used in conjunction with RS_ID, this uniquely identifies a logical row change, shown as one or more rows from the V$LOGMNR_CONTENTS view.
CSF	NUMBER	Continuation SQL flag. Possible values are: • 0 - Indicates SQL_REDO and SQL_UNDO is contained within the same row • 1 - Indicates that either SQL_REDO or SQL_UNDO is greater than 4000 bytes in size and is continued in the next row returned by the view
INFO	VARCHAR2(64)	Informational message about the row. For instance, the string "USER DDL" indicates that the DDL statement returned in the SQL_REDO column was the top-level DDL executed by the user and the string "INTERNAL DDL" indicates that the DDL statement returned in the SQL_REDO column was executed internally by the RDBMS.
STATUS	NUMBER	A value of 0 indicates that the reconstructed SQL statements as shown in the SQL_REDO and SQL_UNDO columns are valid executable SQL statements. Otherwise, the reconstructed SQL statements are not executable. This may be because no data dictionary was provided to LogMiner for the analysis, or that the data dictionary provided did not have the definition of the object being mined. A value of 5 indicates that this row is part of a change to an XMLType column or table and the XML document must be assembled before being applied.
REDO_VALUE	NUMBER	Used as input to the DBMS_LOGMNR.MINE_VALUE() and DBMS_LOGMNR.COLUMN_PRESENT() functions
UNDO_VALUE	NUMBER	Used as input to the DBMS_LOGMNR.MINE_VALUE() and DBMS_LOGMNR.COLUMN_PRESENT() functions
SAFE_RESUME_SCN	NUMBER	Reserved for future use
CSCN	NUMBER	This column is deprecated in favor of the COMMIT_SCN column
OBJECT_ID	RAW(16)	Object identifier for DMLs to XMLType tables. For changes to non-typed tables, this column is NULL.
EDITION_NAME	VARCHAR2(384)	Identifies the edition in which a DDL statement was executed
CLIENT_ID	VARCHAR2(64)	Client identifier in the session that performed the operation, if available.

Column	Datatype	Description
SRC_CON_NAME	VARCHAR2(384)	Contains the pluggable database (PDB) name. This information will only be available when mining with a current LogMiner dictionary.
SRC_CON_ID	NUMBER	Contains the PDB ID (the PDB_ID column from the DBA_PDBS view). This information will be available only with a current LogMiner dictionary.
SRC_CON_UID	NUMBER	Contains the PDB UID (the CON_UID column from the DBA_PDBS view). This information will be available with or without a current LogMiner dictionary.
SRC_CON_DBID	NUMBER	Contains the PDB identifier (the DBID column from the DBA_PDBS view). This information will only be available when mining with a current LogMiner dictionary.
SRC_CON_GUID	RAW(16)	Contains the GUID associated with the PDB (the GUID column from the DBA_PDBS view). This information will only be available when mining with a current LogMiner dictionary.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root

See Also:

- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_LOGMNR package
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_LOB package

9.52 V$LOGMNR_DICTIONARY

V$LOGMNR_DICTIONARY contains log history information.

Column	Datatype	Description
DB_NAME	VARCHAR2(9)	Name of the database
DB_ID	NUMBER	Database ID
DB_CREATED	DATE	Creation date of the source database (corresponds to the CREATED column in the V$DATABASE view)
TIMESTAMP	DATE	Date when the dictionary was created
RESET_SCN	NUMBER	Reset log SCN when the dictionary was created
RESET_SCN_TIME	DATE	Timestamp of the reset log SCN when the dictionary was created
DB_VERSION_TIME	DATE	Version time for the source database (corresponds to the VERSION_TIME column in the V$DATABASE view)
DB_CHARACTER_SET	VARCHAR2(30)	Character set of the source database

Column	Datatype	Description
DB_VERSION	VARCHAR2(64)	This column is deprecated.
DB_STATUS	VARCHAR2(64)	This column is deprecated.
DICTIONARY_SCN	NUMBER	Database checkpoint SCN at which the dictionary was created
ENABLED_THREAD_MAP	RAW(16)	This column is deprecated.
DB_TXN_SCN	NUMBER	SCN at which the dictionary was created
FILENAME	VARCHAR2(512)	Dictionary file name
INFO	VARCHAR2(32)	Informational/Status message BAD_DATE indicates that the SCN of the dictionary file does not match the SCN range of the log files
STATUS	NUMBER	A NULL indicates a valid dictionary file for the list of log files. A non-NULL value indicates further information is contained in the INFO column as a text string.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.53 V$LOGMNR_DICTIONARY_LOAD

V$LOGMNR_DICTIONARY_LOAD displays information about LogMiner dictionaries for all active LogMiner sessions on the system.

Each query of this view will return one row for each attached LogMiner session. This view will not show valid information for LogMiner adhoc query clients.

Column	Datatype	Description
SESSION_ID	NUMBER	LogMiner session ID
LOGMNR_UID	NUMBER	LogMiner dictionary UID
ACTION#	NUMBER	Reserved for internal use
OPCODE	NUMBER	Reserved for internal use
COMMAND	VARCHAR2(161)	Current command being executed
CURRENT_STATE	VARCHAR2(32)	Summary information if LOADED=ACTIVE
COMPLETED_ACTIONS	NUMBER	The steps completed so far
TOTAL_ACTIONS	NUMBER	Total steps to complete
LOADED	VARCHAR2(7)	Status of the dictionary load: • YES - dictionary has been loaded • NO - dictionary has not been loaded • ACTIVE - dictionary is in the process of being loaded
PERCENT_DONE	NUMBER	Percentage of the dictionary that has been loaded

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.54 V$LOGMNR_LATCH

V$LOGMNR_LATCH can be joined with the V$LATCH and the V$LATCH_CHILDREN views to obtain statistics about different latches used by active LogMiner persistent sessions.

A persistent LogMiner session is created either by starting Data Guard SQL Apply on a logical standby database for the first time or by creating a Replication capture.

Column	Datatype	Description
SESSION_ID	NUMBER	Unique identifier of the LogMiner persistent session
NAME	VARCHAR2(32)	Name of the Latch: • LogMiner internal state - Identifies the latch that protects communications between the LogMiner READER, PREPARER, and BUILDER processes • LogMiner memory allocation - Identifies the latch that protects all memory allocation and deallocation inside LogMiner • LogMiner transaction list - Identifies the latch that protects interaction between the LogMiner layer and its clients during Data Guard SQL Apply on a logical standby database
CHILD_ADDR	RAW(4 | 8)	Address of the child latch object. This column matches the corresponding ADDR column in the V$LATCH_CHLDREN view
STATE	VARCHAR2(6)	State of the Latch: • UNINIT - The latch structure is uninitialized; that is, it is not currently assigned to any LogMiner persistent session • READY - The latch structure is being used by a persistent LogMiner session
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$LATCH"
- "V$LATCH_CHILDREN"

9.55 V$LOGMNR_LOGS

V$LOGMNR_LOGS contains log information.

Column	Datatype	Description
LOG_ID	NUMBER	This column is deprecated.
FILENAME	VARCHAR2(512)	Name of the log file
LOW_TIME	DATE	Oldest date of any records in the file
HIGH_TIME	DATE	Most recent date of any records in the file
DB_ID	NUMBER	Database ID
DB_NAME	VARCHAR2(8)	Name of the database
RESET_SCN	NUMBER	Resetlogs SCN of the database incarnation that generated the log file
RESET_SCN_TIME	DATE	Resetlogs timestamp of the database incarnation that generated the log file
COMPATIBLE	VARCHAR2(17)	The setting of the database COMPATIBLE initialization parameter at the time the log file was generated
THREAD_ID	NUMBER	Thread number
THREAD_SQN	NUMBER	Thread sequence number
LOW_SCN	NUMBER	SCN allocated when log switched into
NEXT_SCN	NUMBER	SCN after this log. Low SCN of the next log.
DICTIONARY_BEGIN	VARCHAR2(3)	Indicates whether dictionary dumped to redo logs starts in this redo log (YES) or not (NO)
DICTIONARY_END	VARCHAR2(3)	Indicates whether dictionary dumped to redo logs ends in this redo log (YES) or not (NO)
TYPE	VARCHAR2(7)	Redo log file type: • ARCHIVED • ONLINE
BLOCKSIZE	NUMBER	Database block size
FILESIZE	NUMBER	Size of the redo file (in bytes)
INFO	VARCHAR2(32)	Informational message. A value of MISSING_LOGFILE will be assigned to a row entry where a needed log file is missing from the list of log files.
STATUS	NUMBER	Status of the redo log file: • 0 - Will be read • 1 - First to be read • 2 - Not needed • 4 - Missing log file

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.56 V$LOGMNR_PARAMETERS

V$LOGMNR_PARAMETERS contains log information.

Column	Datatype	Description
START_DATE	DATE	Date to start the search
REQUIRED_START_DATE	DATE	Required date to start the search if DDL tracking is enabled
END_DATE	DATE	Date to end the search
START_SCN	NUMBER	System change number to start the search
REQUIRED_START_SCN	NUMBER	Required system change number to start the search if DDL tracking is enabled
END_SCN	NUMBER	System change number to end the search
OPTIONS	NUMBER	Options specified for the current LogMiner session
INFO	VARCHAR2(32)	This column is always null.
STATUS	NUMBER	This column is always 0.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.57 V$LOGMNR_PROCESS

V$LOGMNR_PROCESS identifies all processes attached to an active LogMiner persistent session.

(A persistent LogMiner session is created either by starting Data Guard SQL Apply on a logical standby database for the first time or by creating Replication capture.) This view can be joined with either the V$SESSION view or the V$PROCESS view to gather process-specific information.

Column	Datatype	Description
SESSION_ID	NUMBER	Unique identifier for the LogMiner persistent session

Column	Datatype	Description
PID	NUMBER	Oracle process identifier for the SQL Apply or Replication capture process (same as the V$PROCESS.PID)
SPID	VARCHAR2(24)	Operating system process identifier (same as the V$PROCESS.SPID)
ROLE	VARCHAR2(32)	Identifies the role of the active LogMiner process: READER, PREPARER, BUILDER, COORDINATOR, or APPLY SERVER
USERNAME	VARCHAR2(15)	Operating system process user name that is connected to the database
SID	NUMBER	Session identifier for the V$SESSION.SID process
SERIAL#	NUMBER	Session serial number associated with the V$SESSION.SERIAL process
LATCHWAIT	VARCHAR2(16)	Address of the latch the process is waiting for; NULL if none
LATCHSPIN	VARCHAR2(16)	This column is obsolete
WORK_MICROSEC	VARCHAR2(21)	Microseconds spent by the process doing useful work
OVERHEAD_MICROSEC	VARCHAR2(21)	Microseconds spent by the process doing overhead tasks or simply waiting/idling
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SESSION"
- "V$PROCESS"

9.58 V$LOGMNR_SESSION

V$LOGMNR_SESSION displays information about active LogMiner persistent sessions.

(A LogMiner persistent session is created either by starting Data Guard SQL Apply on a logical standby database for the first time or by creating Replication capture.) Transient LogMiner sessions (those created as a result of querying the V$LOGMNR_CONTENTS view) do not show up in the V$LOGMNR_SESSION view. The statistics shown in this view correspond to snapshots of the system and are not cumulative in nature.

Column	Datatype	Description
SESSION_ID	NUMBER	Unique identifier for the LogMiner persistent session
SESSION_NAME	VARCHAR2(32)	Unique session name

Column	Datatype	Description
SESSION_STATE	VARCHAR2(9)	Current state of the LogMiner persistent session: • READY - Client has created the LogMiner persistent session and added the relevant archived redo log files, but has not loaded the initial LogMiner dictionary • STARTED - The LogMiner dictionary has been loaded • ACTIVE - The LogMiner persistent session is mining the redo stream • DETACHED - The LogMiner persistent session is not currently active, and it is in the process of becoming inactive • DISCARDED - Client is about to destroy the LogMiner persistent session
DB_NAME	VARCHAR2(128)	Global database name for the source database
DB_ID	NUMBER	Database identifier of the source database
RESET_SCN	NUMBER	System change number (SCN) when the session started
RESET_TIMESTAMP	NUMBER	Time of the RESETLOGs when the LogMiner persistent session started
RESET_TIME	DATE	The time when the session started
NUM_PROCESS	NUMBER	Number of processes allocated to this session
CHUNK_SIZE	NUMBER	Amount of memory allocated for this chunk
START_SCN	NUMBER	System change number (SCN) at start of the session
END_SCN	NUMBER	System change number (SCN) at end of the session
SPILL_SCN	NUMBER	In the event of a restart, redo records with an SCN lower than this will not be read from the archived redo log files
PROCESSED_SCN	NUMBER	The BUILDER process has successfully mined redo records up to this SCN
PROCESSED_TIME	DATE	The BUILDER process has successfully mined redo records up to this time
PREPARED_SCN	NUMBER	The PREPARER processes have successfully transformed all redo records below this SCN into logical change records (LCRs). However the LCRs may not have been grouped into transactions or merged in case they pertain to chained rows or LOB updates.
READ_SCN	NUMBER	The READER process has read all redo records below this SCN
LOW_MARK_SCN	NUMBER	LogMiner has delivered all transactions that committed below this SCN to the client
CONSUMED_SCN	NUMBER	Client has consumed and released all transactions that committed below this SCN.
MAX_MEMORY_SIZE	NUMBER	Maximum amount of shared memory (in bytes) that LogMiner is allowed to consume
USED_MEMORY_SIZE	NUMBER	Amount of shared memory (in bytes) actually consumed by LogMiner
BUILDER_WORK_SIZE	NUMBER	Amount of redo (in bytes) in the current work unit being processed by the BUILDER process.
PREPARED_WORK_SIZE	NUMBER	Amount of redo (in bytes) that has been prepared by LogMiner
AVAILABLE_WORK_SIZE	NUMBER	Amount of redo records (in bytes) that are ready, but are yet to be consumed by the client
AVAILABLE_TXN	NUMBER	Number of transaction chunks ready for consumption

Column	Datatype	Description
AVAILABLE_COMMITTED_TXN	NUMBER	Number of committed transactions ready for consumption. This is less than, or equal to, AVAILABLE_TXN.
DELIVERED_TXN	NUMBER	Number of transaction chunks that the client currently has in its possession
DELIVERED_COMMITTED_TXN	NUMBER	Number of committed transaction chunks that the client is currently working on. This is less than, or equal to, the value of the DELIVERED_TXN column.
PINNED_TXN	NUMBER	Number of transactions pinned (the client is actively working on)
PINNED_COMMITTED_TXN	NUMBER	Number of committed transactions pinned (the client is actively working on)
CHECKPOINT_INTERVAL	NUMBER	Checkpoint interval
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$LOGMNR_CONTENTS"

9.59 V$LOGMNR_STATS

V$LOGMNR_STATS displays the activity currently being performed by the active LogMiner persistent sessions.

Column	Datatype	Description
SESSION_ID	NUMBER	Unique identifier for the LogMiner persistent sessions

Column	Datatype	Description
NAME	VARCHAR2(64)	Name of the LogMiner statistic, state, or status, including: • Bytes of Redo Processed - Cumulative count of bytes processed by SQL Apply • Redo Records Processed - Count of redo records processed by SQL Apply • Txns Delivered to Client - Count of SQL transactions processed by SQL Apply • DML txns delivered - Count of DML transactions processed by SQL Apply • DDL txns delivered - Count of DDL transactions processed by SQL Apply • CTAS txns delivered - Count of `CREATE TABLE AS SELECT` (CTAS) transactions processed by SQL Apply • Recursive txns delivered - Count of recursive transactions processed by SQL Apply • Rolled back txns seen • LCRs delivered to client - Number of logical change records (LCRs) processed by SQL Apply • Bytes paged out - Cumulative count of bytes that have been paged out. LogMiner pages out memory from the LCR cache to accommodate certain ill-behaved workloads or under-configured systems. The ratio of bytes paged out to bytes of redo processed should be low. If this ratio is high (10% or higher), try increasing the `MAX_SGA` allocated to SQL Apply. • Microsecs spent in pageout - Time spent by LogMiner paging out memory from the LCR cache • Bytes checkpointed - Keeps track of the amount of bytes checkpointed. The mining engine takes periodic checkpoints, whereby it writes out logical change records (LCRs) pertaining to long-running transactions. The ratio of `Bytes Checkpointed` to `Bytes of Redo Processed` should be low. A high ratio (10% or higher) indicates an ill-behaved workload. • Microsecs spent in checkpoint - Time spent by the mining engine taking checkpoints, whereby it writes out logical change records (LCRs) pertaining to long-running transactions. • Bytes rolled back - Cumulative value of the number of bytes rolled back by LogMiner. There are times that LogMiner needs to backtrack and reprocess a section of the redo stream. In this case, it will roll back work it has already done. The ratio of `Bytes Rolled Back` to `Bytes of Redo Processed` should be low. If this ratio is high (10% or higher), reduce the number of `PREPARER` processes allocated to SQL Apply. • Microsecs spent in rollback - Time spent rolling back transactions already applied to the logical standby database
VALUE	VARCHAR2(64)	The corresponding metric value
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.60 V$LOGSTDBY

V$LOGSTDBY is deprecated.

Column	Datatype	Description
SERIAL#	NUMBER	SQL Session serial number. This data is used when joining this view with the V$SESSION and V$PX_SESSION views.
LOGSTDBY_ID	NUMBER	Parallel query worker ID
PID	VARCHAR2(24)	Process ID of the SQL apply process
TYPE	VARCHAR2(128)	Indicates the task being performed by the process (COORDINATOR, APPLIER, ANALYZER, READER, PREPARER, or BUILDER)
STATUS_CODE	NUMBER	Status number (or Oracle error code) belonging to the STATUS message
STATUS	VARCHAR2(256)	Description of the current activity of the process
HIGH_SCN	NUMBER	Highest system change number (SCN) seen by the process. This column is used to confirm the progress of the individual process.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.61 V$LOGSTDBY_PROCESS

V$LOGSTDBY_PROCESS displays dynamic information about what is happening to the Data Guard log apply services.

This view is helpful when diagnosing performance problems during the logical application of archived redo logs to the standby database, and it can be helpful for other problems. This view is for logical standby databases only.

Column	Datatype	Description
SID	NUMBER	Session id of the associated session. This matches the SID column of the corresponding row in the V$SESSION view.
SERIAL#	NUMBER	Serial number of the associated session. Together, (SID,SERIAL#) uniquely identify the session in the current database instance.
LOGSTDBY_ID	NUMBER	Parallel query worker ID
SPID	VARCHAR2(24)	This corresponds to the SPID value of the row corresponding to this process in the V$PROCESS view

Column	Datatype	Description
TYPE	VARCHAR2(128)	Role that the process plays in the context of SQL Apply: • COORDINATOR • APPLIER • ANALYZER • READER • PREPARER • BUILDER
STATUS_CODE	NUMBER	Operation code identifying the current action of the process: • 16111 - SQL Apply process is initializing • 16112 - SQL Apply process is cleaning up as apply and mining processes are stopping based on a user command • 16116 - SQL Apply process is idle • 16117 - SQL Apply process is busy and is not waiting on any interesting event • 16110 - APPLIER process has invoked a user-provided stored procedure in order to inspect a DDL statement prior to it being processed • 16113 - APPLIER process is applying DML changes to some user object or to a sequence • 16114 - APPLIER process is applying a DDL change • 16115 - COORDINATOR process is loading the LogMiner dictionary from the redo stream • 16243 - BUILDER process is paging out memory to free up space in lcr cache • 16240 - READER process idle waiting for additional logfile to be available • 16241 - READER process is idle waiting for the logfile to fill the log sequence gap • 16242 - READER process is processing a logfile
STATUS	VARCHAR2(256)	Description of the current action of the process
HIGH_SCN	NUMBER	Identifies the highest redo record/LCR processed by this process
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.62 V$LOGSTDBY_PROGRESS

V$LOGSTDBY_PROGRESS displays the progress of log apply services on the logical standby database. This view is for logical standby databases only.

Column	Datatype	Description
APPLIED_SCN	NUMBER	All the transactions with COMMIT SCN lower than or equal to this SCN have been applied

Column	Datatype	Description
APPLIED_TIME	DATE	The time and date of APPLIED_SCN
RESTART_SCN	NUMBER	During an apply restart, LogMiner does not read any log file with a NEXT_CHANGE# lower than this SCN.
RESTART_TIME	DATE	The time and date of RESTART_SCN
LATEST_SCN	NUMBER	The highest SCN of all redo records that Logical Standby has encountered
LATEST_TIME	DATE	The time and date of LATEST_SCN
MINING_SCN	NUMBER	The SCN of the latest redo record processed by the builder process
MINING_TIME	DATE	The time and date of MINING_SCN
RESETLOGS_ID	NUMBER	A redo branch is identified by resetlogs SCN and resetlogs timestamp. The RESETLOGS_ID column contents are the same as resetlogs timestamp converted to a number.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.63 V$LOGSTDBY_STATE

V$LOGSTDBY_STATE provides consolidated information from V$LOGSTDBY and V$LOGSTDBY_STATS about the running state of Logical Standby.

Column	Datatype	Description
PRIMARY_DBID	NUMBER	Database ID (DBID) of the primary database
PRIMARY_CON_DBID	NUMBER	This column indicates the DBID of the source database or source PDB corresponding to the database (or CDB) from which this column is queried.For a non-CDB and the root of a CDB, this column matches the PRIMARY_DBID column.For a maintained PDB, this column indicates the DBID for the corresponding PDB at the source.For a skipped PDB or a local PDB, this column would be NULL.
SESSION_ID	NUMBER	LogMiner session ID allocated to SQL Apply.
REALTIME_APPLY	VARCHAR2(64)	Y indicates that SQL Apply is running in real-time apply mode. If a standby redo log is configured, SQL Apply applies changes as they are written to the standby redo log files. N indicates that SQL Apply applies changes as each archived redo log file is received.

Column	Datatype	Description
STATE	VARCHAR2(64)	• INITIALIZING: LogMiner session has been created and coordinator has attached to it • LOADING DICTIONARY: SQL Apply is loading the LogMiner dictionary • WAITING ON GAP: SQL Apply is waiting for a log file to be sent from the primary database • APPLYING: SQL Apply is actively mining or applying transactions • WAITING FOR DICTIONARY LOGS: SQL Apply is waiting for the archived logs containing the LogMiner dictionary to be shipped from the primary database • IDLE: SQL Apply has applied all changes available at the logical standby, and is caught up with the primary database
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$LOGSTDBY"
- "V$LOGSTDBY_STATS"

9.64 V$LOGSTDBY_STATS

V$LOGSTDBY_STATS displays statistics, current state, and status information related to SQL Apply.

No rows are returned from this view when SQL Apply is not running. This view is only meaningful in the context of a logical standby database.

All statistics shown in this view are reinitialized at each SQL Apply start.

Column	Datatype	Description
NAME	VARCHAR2(64)	Name of the statistic, state, or status: **Note:** Many of the following statistics are subject to change or deletion; programmers should write application code to tolerate missing or extra statistics. • id of the logminer session used by SQL Apply to mine the redo logs. • number of preparers • number of appliers • server processes in use for SQL Apply • maximum SGA (in MBytes) for LCR cache • whether SQL Apply is preserving the commit order seen at the primary database while applying changes • maximum events recorded in the DBA_LOGSTDBY_EVENTS table • whether SQL Apply is logging errors that are skipped in the DBA_LOGSTDBY_EVENTS table • whether SQL Apply is logging DDLs that are skipped in the DBA_LOGSTDBY_EVENTS table • whether SQL Apply is logging DDLs that are applied in the DBA_LOGSTDBY_EVENTS table • whether SQL Apply is logging unsupported operations that are encountered in the DBA_LOGSTDBY_EVENTS table • whether or not real time apply is on • value of apply delay (in minutes) • coordinator state • coordinator uptime in seconds • time of the most recent start of SQL Apply • number of transactions mined and made available for apply • number of transactions applied • number of rolled back transactions mined • number of DDL txns mined • number of CTAS (Create Table as Select) txns mined • number of thread enable events encountered in the redo stream • number of thread disable events encountered in the redo stream • bytes of redo records mined • bytes paged out • seconds spent in pageout activity • bytes checkpointed • seconds spent in checkpointing activity • seconds SQL Apply is idle • number of times a complete standby redo logs are mined without having to mine the corresponding archived log • number of times SQL Apply had to switch from a standby redo log to the corresponding archived log • number of times SQL Apply mined redo from the archived logs • number of archived logs that arrived at the standby via gap fetch mechanism (gap fetched logs mined) • number of failed attempts to open a logfile

Column	Datatype	Description
		• amount of time spent in waiting for the current gap to resolve if SQL Apply is running in real time mode (current logfile wait)[1] • time spent in waiting for gap to resolve if SQL Apply is running in real time mode (total logfile wait)[2]
VALUE	VARCHAR2(64)	Value of the statistic or state information
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

1 In case SQL Apply is not running in real time mode, this may not reflect time spent in gap resolution, but simply the time spent waiting for the most recent archived log to show up at the logical standby.
2 In case SQL Apply is not running in real time mode, this will include time that SQL Apply spent every time it finished processing all archived logs registered with it, and waited for the next log to be archived.

9.65 V$LOGSTDBY_TRANSACTION

V$LOGSTDBY_TRANSACTION displays all transactions that are actively being processed by SQL Apply.

The transaction identifiers shown in this view are those mined from the redo stream and correspond to transaction identifiers assigned at the primary database, and do not correspond to the transactions that are active at the logical standby database. For information regarding transactions active in the logical standby database, including those created as part of SQL Apply, query the V$TRANSACTION view at the logical standby database.

Column	Datatype	Description
PRIMARY_XIDUSN	NUMBER	Undo segment number of the transaction
PRIMARY_XIDSLT	NUMBER	Slot number of the transaction
PRIMARY_XIDSQN	NUMBER	Sequence number of the transaction
PRIMARY_XID	RAW(8)	Transaction ID
PRIMARY_START_SCN	NUMBER	Start system change number (SCN) base
PRIMARY_START_TIME	DATE	Start time
PRIMARY_PARENT_XIDUSN	NUMBER	Undo segment number of the parent transaction
PRIMARY_PARENT_XIDSLT	NUMBER	Slot number of the parent transaction
PRIMARY_PARENT_XIDSQN	NUMBER	Sequence number of the parent transaction
PRIMARY_PARENT_XID	RAW(8)	Transaction ID of the parent transaction (PDML)

Column	Datatype	Description
TYPE	VARCHAR2(32)	Type: • PL/SQL - Transaction was done as part of a supported PL/SQL procedure • Direct Path Load - Transaction is a direct path load • CTAS - Transaction contains at least one CREATE TABLE ... AS SELECT operation • DDL - Transaction contains one or more DDL operations • PDML Child - Transaction is a child transaction • DML - Transaction contains only DML operations
MINING_STATUS	VARCHAR2(32)	Mining status: • ACTIVE - Transaction is still being mined by LogMiner. At least part of this transaction is ready to be applied or has already been applied. • COMPLETE - Transaction is complete and ready to be applied. LogMiner has finished mining.
SRC_CON_ID	NUMBER	Contains the PDB ID (the PDB_ID column from the DBA_PDBS view) of the source database that generated the change for this transaction.
APPLY_STATUS	VARCHAR2(6)	• ACTIVE - Transaction has been assigned to an apply server. It is in one of the following states: - The transaction is being actively applied - The transaction is being held by an apply server waiting for certain events to occur - The transaction is being held by an apply server waiting for subsequent parts of this transaction • NONE - Transaction has not yet been assigned to an apply server
SID	NUMBER	Session ID of the apply server's session; Null if APPLY_STATUS is NONE
SERIAL#	NUMBER	Serial number of the apply server's session; Null if APPLY_STATUS is NONE
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$TRANSACTION"

9.66 V$MANAGED_STANDBY

V$MANAGED_STANDBY displays current status information for some Oracle Database processes related to physical standby databases in the Data Guard environment. This view does not persist after an instance shutdown.

Column	Datatype	Description
PROCESS	VARCHAR2(9)	Type of the process whose information is being reported: • RFS - Remote file server • MRP0 - Detached recovery server process • MR(fg) - Foreground recovery session • ARCH - Archiver process • DGRD - Generic Oracle Data Guard process • FGRD • LGWR • RFS(FAL) • RFS(NEXP) • LNS - ASYNC Redo Transport process
PID	VARCHAR2(24)	Operating system process identifier of the process
STATUS	VARCHAR2(12)	Current process status: • ALLOCATED - Process is active but not currently connected to a primary database • ANNOUNCING - Process is announcing the existence of a potential dependent archived redo log • APPLYING_LOG - Process is actively applying the archived redo log to the standby database • ATTACHED - Process is actively attached and communicating to a primary database • CLOSING - Process has completed archival and is closing the archived redo log • CONNECTED - Network connection established to a primary database • ERROR - Process has failed • IDLE - Process is not performing any activities • OPENING - Process is opening the archived redo log • RECEIVING - Process is receiving network communication • REGISTERING - Process is registering the existence of a completed dependent archived redo log • UNUSED - No active process • WAIT_FOR_GAP - Process is waiting for the archive gap to be resolved • WAIT_FOR_LOG - Process is waiting for the archived redo log to be completed • WAIT_FOR_NEW_PRIMARY - Process is waiting for a new primary (source PDB) to register itself with this container database • WRITING - Process is actively writing redo data to the archived redo log

Column	Datatype	Description
CLIENT_PROCESS	VARCHAR2(8)	Identifies the corresponding primary database process: • Archival - Foreground (manual) archival process (SQL) • ARCH - Background ARC*n* process • LGWR - Background LGWR process
CLIENT_PID	VARCHAR2(40)	Operating system process identifier of the client process
CLIENT_DBID	VARCHAR2(40)	Database identifier of the primary database
GROUP#	VARCHAR2(40)	Standby redo log group
RESETLOG_ID	NUMBER	Resetlogs identifier of the archived redo log
THREAD#	NUMBER	Archived redo log thread number
SEQUENCE#	NUMBER	Archived redo log sequence number
BLOCK#	NUMBER	Last processed archived redo log block number
BLOCKS	NUMBER	Count (in 512-byte blocks) of the last write to a redo log, or for a recovery process, the expected final read count
DELAY_MINS	NUMBER	Archived redo log delay interval in minutes
KNOWN_AGENTS	NUMBER	Total number of standby database agents processing an archived redo log
ACTIVE_AGENTS	NUMBER	Number of standby database agents actively processing an archived redo log
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

This view is deprecated in Oracle Database 12*c* Release 2 (12.2.0.1) and may be desupported in a future release. The V$DATAGUARD_PROCESS view should be used, instead.

See Also:

"V$DATAGUARD_PROCESS"

9.67 V$MAP_COMP_LIST

V$MAP_COMP_LIST displays supplementary information for all element mapping structures.

Column	Datatype	Description
ELEM_IDX	NUMBER	Index corresponding to the element
NUM_COMP	NUMBER	Number of components (maximum is 5)
COMP1_NAME	VARCHAR2(256)	Name of the first component
COMP1_VAL	VARCHAR2(256)	Value of the first component
COMP2_NAME	VARCHAR2(256)	Name of the second component
COMP2_VAL	VARCHAR2(256)	Value of the second component
COMP3_NAME	VARCHAR2(256)	Name of the third component
COMP3_VAL	VARCHAR2(256)	Value of the third component
COMP4_NAME	VARCHAR2(256)	Name of the fourth component
COMP4_VAL	VARCHAR2(256)	Value of the fourth component
COMP5_NAME	VARCHAR2(256)	Name of the fifth component
COMP5_VAL	VARCHAR2(256)	Value of the fifth component
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.68 V$MAP_ELEMENT

V$MAP_ELEMENT displays a list of all element mapping structures in the SGA of the instance.

Column	Datatype	Description
ELEM_NAME	VARCHAR2(256)	Element name
ELEM_IDX	NUMBER	Index corresponding to the element
ELEM_CFGID	VARCHAR2(256)	Configuration ID (N/A if configuration ID is not supported)
ELEM_TYPE	VARCHAR2(12)	Element type: • MIRROR • STRIPE • RAID5 • CONCATENATED • PARTITION • DISK • NONE
ELEM_SIZE	NUMBER	Element Size in HKB
ELEM_NSUBELEM	NUMBER	Number of Subelements
ELEM_DESCR	VARCHAR2(256)	Element Description
STRIPE_SIZE	NUMBER	Stripe Size in HKB for RAID-5 and STRIPE elements, 0 for the remaining types
LIB_IDX	NUMBER	Index of the library which claims ownership of the element

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.69 V$MAP_EXT_ELEMENT

V$MAP_EXT_ELEMENT displays supplementary information for all element mapping structures.

Column	Datatype	Description
ELEM_IDX	NUMBER	Index corresponding to the element
NUM_ATTRB	NUMBER	Number of Attributes (maximum is 5)
ATTRB1_NAME	VARCHAR2(256)	Name of the first Attribute
ATTRB1_VAL	VARCHAR2(256)	Value of the first attribute
ATTRB2_NAME	VARCHAR2(256)	Name of the second attribute
ATTRB2_VAL	VARCHAR2(256)	Value of the second attribute
ATTRB3_NAME	VARCHAR2(256)	Name of the third attribute
ATTRB3_VAL	VARCHAR2(256)	Value of the third attribute
ATTRB4_NAME	VARCHAR2(256)	Name of the fourth attribute
ATTRB4_VAL	VARCHAR2(256)	Value of the fourth attribute
ATTRB5_NAME	VARCHAR2(256)	Name of the fifth attribute
ATTRB5_VAL	VARCHAR2(256)	Value of the fifth attribute
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.70 V$MAP_FILE

V$MAP_FILE displays a list of all file mapping structures in the shared memory of the instance.

Column	Datatype	Description
FILE_MAP_IDX	NUMBER	Index corresponding to the file
FILE_CFGID	VARCHAR2(256)	Configuration ID (N/A if configuration ID is not supported)

Column	Datatype	Description
FILE_STATUS	VARCHAR2(7)	Status of the mapping information: • VALID - File mapping information is latest • INVALID - Mapping must be refreshed
FILE_NAME	VARCHAR2(256)	Absolute file name
FILE_TYPE	VARCHAR2(11)	File type: • DATAFILE • SPFILE • TEMPFILE • CONTROLFILE • LOGFILE • ARCHIVEFILE
FILE_STRUCTURE	VARCHAR2(9)	File structure: • FILE • RAWVOLUME • RAWDEVICE • NONE
FILE_SIZE	NUMBER	File size in HKB (half KB)
FILE_NEXTS	NUMBER	Number of file extents in the file (not necessarily the same as the number of file extents mapped)
LIB_IDX	NUMBER	Index of mapping library claiming ownership of the file
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.71 V$MAP_FILE_EXTENT

V$MAP_FILE_EXTENT displays a list of all file extent mapping structures in the shared memory of the instance.

Column	Datatype	Description
FILE_MAP_IDX	NUMBER	File index (corresponds to FILE_MAP_IDX in V$MAP_FILE)
EXT_NUM	NUMBER	File extent number
EXT_ELEM_OFF	NUMBER	Element offset in HKB
EXT_SIZE	NUMBER	File extent size in HKB
EXT_FILE_OFF	NUMBER	File Offset in HKB
EXT_TYPE	VARCHAR2(6)	File Extent Type: • DATA • PARITY • NONE
ELEM_IDX	NUMBER	Index in V$MAP_ELEMENT corresponding to the element where the file extent resides

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.72 V$MAP_FILE_IO_STACK

V$MAP_FILE_IO_STACK displays the hierarchical arrangement of storage containers for files. Each row in the view represents a level in the hierarchy.

Column	Datatype	Description
FILE_MAP_IDX	NUMBER	File index (corresponds to FILE_MAP_IDX in V$MAP_FILE)
DEPTH	NUMBER	Element depth within the I/O stack
ELEM_IDX	NUMBER	Index corresponding to the element
CU_SIZE	NUMBER	Contiguous set of logical blocks of the file (in HKB units) that is resident contiguously on the element
STRIDE	NUMBER	Number of HKB between contiguous units (CU) in the file that are contiguous on this element. Used in RAID5 and striped files.
NUM_CU	NUMBER	Number of contiguous units that are adjacent to each other on this element that are separated by STRIDE HKB in the file. In RAID5, the number of contiguous units also include the parity stripes.
ELEM_OFFSET	NUMBER	Element offset in HKB units
FILE_OFFSET	NUMBER	Offset in HKB units from the start of the file to the first byte of the contiguous units
DATA_TYPE	VARCHAR2(15)	Datatype: • DATA • PARITY • DATA AND PARITY
PARITY_POS	NUMBER	Position of the parity. Only for RAID5. This column is needed to distinguish the parity from the data part.
PARITY_PERIOD	NUMBER	Parity period. Only for RAID5.
ID	NUMBER	Unique identifier
PARENT_ID	NUMBER	Parent identifier
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.73 V$MAP_LIBRARY

V$MAP_LIBRARY displays a list of all mapping libraries dynamically loaded by the external process.

Column	Datatype	Description
LIB_IDX	NUMBER	Index corresponding to the library
LIB_NAME	VARCHAR2(256)	Absolute library name
VENDOR_NAME	VARCHAR2(64)	Name of the vendor implementing the library
PROTOCOL_NUM	NUMBER	Mapping protocol that the library supports
VERSION_NUM	VARCHAR2(32)	Version number
PATH_NAME	VARCHAR2(4000)	Path name
MAP_FILE	VARCHAR2(1)	Indicates whether the library supports mapping files (Y) or not (N)
FILE_CFGID	VARCHAR2(13)	Type of configuration ID supported for files: • NONE - Not supported • PERSISTENT • NONPERSISTENT
MAP_ELEM	VARCHAR2(1)	Indicates whether the library supports mapping elements (Y) or not (N)
ELEM_CFGID	VARCHAR2(13)	Type of configuration id supported for elements: • NONE - Not supported • PERSISTENT • NONPERSISTENT
MAP_SYNC	VARCHAR2(1)	Indicates whether the library needs to be explicitly synchronized so that future mappings reflect the most recent changes (Y) or not (N). Note that configuration IDs cannot be supported if the library needs to be explicitly synced.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.74 V$MAP_SUBELEMENT

V$MAP_SUBELEMENT displays a list of all subelement mapping structures in the shared memory of the instance.

Column	Datatype	Description
CHILD_IDX	NUMBER	Index in V$MAP_ELEMENT corresponding to the child element
PARENT_IDX	NUMBER	Index in V$MAP_ELEMENT corresponding to the parent element
SUB_NUM	NUMBER	Subelement number
SUB_SIZE	NUMBER	Subelement size in HKB

Column	Datatype	Description
ELEM_OFFSET	NUMBER	Offset in HKB on the child element
SUB_FLAGS	NUMBER	Subelement flags (currently unused)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.75 V$MAPPED_SQL

V$MAPPED_SQL lists the SQL statements that are translated and mapped in memory to a different SQL statement for execution.

Column	Datatype	Description
SQL_TEXT	VARCHAR2(1000)	First 1000 characters of the original SQL text
SQL_FULLTEXT	CLOB	Full text for the original SQL statement
SQL_ID	VARCHAR2(13)	SQL identifier of the original SQL statement
HASH_VALUE	NUMBER	Hash value of the original SQL statement
MAPPED_SQL_TEXT	VARCHAR2(1000)	First 1000 characters of the mapped SQL text
MAPPED_SQL_FULLTEXT	CLOB	Full text for the mapped SQL statement
MAPPED_SQL_ID	VARCHAR2(13)	SQL identifier of the mapped SQL statement
MAPPED_HASH_VALUE	NUMBER	Hash value of the mapped SQL statement
SQL_TRANSLATION_PROFILE_ID	NUMBER	A non-NULL value specifies the object ID of the SQL translation profile used to translate the SQL statement into the mapped SQL statement
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
TRANSLATION_TIMESTAMP	DATE	Time this SQL statement was translated
TRANSLATION_CPU_TIME	NUMBER	CPU time used to translate this SQL statement
TRANSLATION_ELAPSED_TIME	NUMBER	Elapsed time used to translate this SQL statement
TRANSLATION_METHOD	VARCHAR2(10)	Method used to translate this SQL statement
DICTIONARY_SQL_ID	VARCHAR2(13)	SQL ID of SQL text in custom translation dictionary used to translate this SQL statement
USE_COUNT	NUMBER	Number of times this translation has been used

9.76 V$MEMOPTIMIZE_WRITE_AREA

V$MEMOPTIMIZE_WRITE_AREA displays information about fast ingest data in the large pool.

Column	Datatype	Description
TOTAL_SIZE	NUMBER	Total amount of memory allocated for fast ingest data in the large pool (in bytes)
USED_SPACE	NUMBER	Total amount of memory currently used by fast ingest data in the large pool (in bytes)
FREE_SPACE	NUMBER	Total amount of memory currently free for storing fast ingest data in the large pool (in bytes)
NUM_WRITES	NUMBER	Number of fast ingest insert operations for which data is still in the large pool and is yet to be written to disk
NUM_WRITERS	NUMBER	Number of clients currently using fast ingest for inserting data into the database
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.77 V$MEMORY_CURRENT_RESIZE_OPS

V$MEMORY_CURRENT_RESIZE_OPS displays information about memory resize operations (both automatic and manual) which are currently in progress.

An operation can be a grow or a shrink of a dynamic memory component. All sizes are expressed in bytes.

Column	Datatype	Description
COMPONENT	VARCHAR2(64)	Component name
OPER_TYPE	VARCHAR2(13)	Operation type: • STATIC • INITIALIZING • DISABLED • GROW • SHRINK • SHRINK_CANCEL
OPER_MODE	VARCHAR2(9)	Operation mode: • MANUAL • DEFERRED • IMMEDIATE
PARAMETER	VARCHAR2(80)	Name of the parameter for the resize operation
INITIAL_SIZE	NUMBER	Parameter value at the start of the operation

Column	Datatype	Description
TARGET_SIZE	NUMBER	Desired value of the parameter after the resize
CURRENT_SIZE	NUMBER	Current value of the parameter
START_TIME	DATE	Start time of the operation
LAST_UPDATE_TIME	DATE	Last time progress was made for the operation
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.78 V$MEMORY_DYNAMIC_COMPONENTS

V$MEMORY_DYNAMIC_COMPONENTS displays information about the dynamic SGA components.

This view summarizes information based on all completed SGA resize operations since instance startup. All sizes are expressed in bytes.

Column	Datatype	Description
COMPONENT	VARCHAR2(64)	Component name
CURRENT_SIZE	NUMBER	Current size of the component
MIN_SIZE	NUMBER	Minimum size of the component since instance startup
MAX_SIZE	NUMBER	Maximum size of the component since instance startup
USER_SPECIFIED_SIZE	NUMBER	Value of the user parameter for the component
OPER_COUNT	NUMBER	Number of operations since instance startup
LAST_OPER_TYPE	VARCHAR2(13)	Last completed operation for the component: • STATIC • INITIALIZING • DISABLED • GROW • SHRINK • SHRINK_CANCEL
LAST_OPER_MODE	VARCHAR2(9)	Mode of the last completed operation: • MANUAL • DEFERRED • IMMEDIATE
LAST_OPER_TIME	DATE	Start time of the last completed operation
GRANULE_SIZE	NUMBER	Granularity of the GROW or SHRINK operation

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.79 V$MEMORY_RESIZE_OPS

V$MEMORY_RESIZE_OPS displays information about the last 800 completed memory resize operations (both automatic and manual). This does not include in-progress operations. All sizes are expressed in bytes.

Column	Datatype	Description
COMPONENT	VARCHAR2(64)	Component name
OPER_TYPE	VARCHAR2(13)	Operation type: • STATIC • INITIALIZING • DISABLED • GROW • SHRINK • SHRINK_CANCEL
OPER_MODE	VARCHAR2(9)	Operation mode: • MANUAL • DEFERRED • IMMEDIATE
PARAMETER	VARCHAR2(80)	Name of the parameter for the resize operation
INITIAL_SIZE	NUMBER	Parameter value at the start of the operation
TARGET_SIZE	NUMBER	Requested value of the parameter after the resize
FINAL_SIZE	NUMBER	Real value of the parameter after the resize
STATUS	VARCHAR2(9)	Completion status of the operation: • INACTIVE • PENDING • COMPLETE • CANCELLED • ERROR
START_TIME	DATE	Start time of the operation
END_TIME	DATE	End time of the operation

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.80 V$MEMORY_TARGET_ADVICE

V$MEMORY_TARGET_ADVICE provides information about how the MEMORY_TARGET parameter should be sized based on current sizing and satisfaction metrics.

Column	Datatype	Description
MEMORY_SIZE	NUMBER	If the MEMORY_SIZE_FACTOR column has a value of 1, then this column shows the current size of memory, as set by the MEMORY_TARGET initialization parameter. If the value of the MEMORY_SIZE_FACTOR column is less than or greater than 1, then this column shows a proposed memory size.
MEMORY_SIZE_FACTOR	NUMBER	A multiplier for the current memory size. Possible values are 0.25, 0.5, 0.75, 1, 1.5, 1.75, and 2. This multiplier times the current memory size equals the value of the MEMORY_SIZE column.
ESTD_DB_TIME	NUMBER	For current memory size (MEMORY_SIZE_FACTOR = 1), the amount of database time required to complete the current workload. For a proposed memory size, the estimated amount of database time that would be required if the MEMORY_TARGET parameter were changed to the proposed size.
ESTD_DB_TIME_FACTOR	NUMBER	For a proposed memory size, ratio of estimated database time to current database time
VERSION	NUMBER	Version number of this recommendation (this snapshot of the V$MEMORY_TARGET_ADVICE view)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Table 9-2 shows how the information provided in V$MEMORY_TARGET_ADVICE could be used to improve performance. The data indicates that if current memory size is 380M, and you were to increase it to 760M (2x), the current workload would take 80525 units of DBtime as opposed to 115475 units of DBtime, which is a significant improvement in performance.

Table 9-2 Example of Using V$MEMORY_TARGET_ADVICE

MEMORY_SIZE	MEMORY_SIZE_FACTOR	ESTD_DB_TIME	ESTD_DB_TIME_FACTOR	VERSION
380	1	115475	1	3
95	.25	200500	1.7	3
190	.5	125600	1.1	3
760	2	80525	0.7	3

> **See Also:**
>
> "MEMORY_TARGET"

9.81 V$METRIC

V$METRIC displays the most recent statistic values for the complete set of metrics captured by the Automatic Workload Repository (AWR) infrastructure.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	Metric Group ID. Refer to the V$METRICNAME view for the name of the group.
ENTITY_ID	NUMBER	Entity ID for the metric in question. The value of the Entity ID depends upon the metric group. (See the following table for an explanation of possible values.)
ENTITY_SEQUENCE	NUMBER	Entity Sequence number for the metric in question. The value of the Entity Sequence depends upon the metric group. (See the following table for an explanation of possible values.)
METRIC_ID	NUMBER	Metric ID
METRIC_NAME	VARCHAR2(64)	Metric Name. This is the statistic that is captured for the entity.
VALUE	NUMBER	Value of the statistic between BEGIN_TIME and END_TIME
METRIC_UNIT	VARCHAR2(64)	Unit for the VALUE
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

The following table describes what the ENTITY_ID and ENTITY_SEQUENCE are for each metric group:

GID	Group NAME	Entity ID	Entity Sequence
0	Event Metrics	Event#	N/A
1	Event Class Metrics	Wait Class ID	N/A
2	System Metrics Long Duration	N/A	N/A
3	System Metrics Short Duration	N/A	N/A
4	Session Metrics Long Duration	Session ID	Serial#
5	Session Metrics Short Duration	Session ID	Serial#
6	Service Metrics	N/A	Service Hash
7	File Metrics Long Duration	File#	Creation Change#
9	Tablespace Metrics Long Duration	Tablespace#	N/A
10	Service Metrics (Short)	N/A	Service Hash

9.82 V$METRICGROUP

`V$METRICGROUP` displays information about the metric group for each of the four major Replication components: capture, propagation, apply, and queue.

Column	Datatype	Description
`GROUP_ID`	`NUMBER`	Internal ID associated with each group
`NAME`	`VARCHAR2(64)`	External name of the group
`INTERVAL_SIZE`	`NUMBER`	How often to collect statistics
`MAX_INTERVAL`	`NUMBER`	Total number of intervals over which statistics should be collected
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.83 V$METRIC_HISTORY

`V$METRIC_HISTORY` displays all the available statistic values for the complete set of metrics captured by the Automatic Workload Repository (AWR) infrastructure.

Column	Datatype	Description
`BEGIN_TIME`	`DATE`	Begin time of the interval
`END_TIME`	`DATE`	End time of the interval
`INTSIZE_CSEC`	`NUMBER`	Interval size (in hundredths of a second)
`GROUP_ID`	`NUMBER`	Metric Group ID. Refer to the `V$METRICNAME` view for the name of the group.

Column	Datatype	Description
ENTITY_ID	NUMBER	Entity ID for the metric in question. The value of the Entity ID depends upon the metric group. (See the table in the description of V$METRIC for an explanation of possible values.)
ENTITY_SEQUENCE	NUMBER	Entity Sequence number for the metric in question. The value of the Entity Sequence depends upon the metric group. (See the table in the description of V$METRIC for an explanation of possible values.)
METRIC_ID	NUMBER	Metric ID
METRIC_NAME	VARCHAR2(64)	Metric Name. This is the statistic that is captured for the entity.
VALUE	NUMBER	Value of the statistic between BEGIN_TIME and END_TIME
METRIC_UNIT	VARCHAR2(64)	Unit for the VALUE
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.84 V$METRICNAME

V$METRICNAME displays the mapping of the name of metrics to their metric ID.

Column	Datatype	Description
GROUP_ID	NUMBER	Metric group ID
GROUP_NAME	VARCHAR2(64)	Metric group name
METRIC_ID	NUMBER	Metric ID
METRIC_NAME	VARCHAR2(64)	Metric name
METRIC_UNIT	VARCHAR2(64)	Unit of measurement
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.85 V$MTTR_TARGET_ADVICE

V$MTTR_TARGET_ADVICE displays rows that predict the number of physical I/Os for the MTTR corresponding to each row.

The rows also compute a physical I/O factor, which is the ratio of the number of estimated I/Os to the number of I/Os actually performed by the current MTTR setting during the measurement interval.

The content of the view is empty if MTTR advisory has not been turned on since database startup. Otherwise, it returns the advisory information collected. If advisory is currently off, then this information comes from the last time MTTR advisory was on. FAST_START_MTTR_TARGET must be set to a nonzero value if the STATISTICS_LEVEL parameter is dynamically modified to turn MTTR advisory on.

If the FAST_START_MTTR_TARGET parameter is changed while MTTR advisory is on, then MTTR advisory is temporarily turned off until the new FAST_START_MTTR_TARGET setting takes effect. During this transition period, the contents of V$MTTR_TARGET_ADVICE reflect the simulation result for the old MTTR setting.

Column	Datatype	Description
MTTR_TARGET_FOR_ESTIMATE	NUMBER	MTTR setting being simulated. Equal to the current MTTR setting if this is the first row of the view.
ADVICE_STATUS	VARCHAR2(5)	Current status of MTTR simulation: • ON • READY • OFF
DIRTY_LIMIT	NUMBER	Dirty buffer limit derived from the MTTR being simulated
ESTD_CACHE_WRITES	NUMBER	Estimated number of cache physical writes under this MTTR
ESTD_CACHE_WRITE_FACTOR	NUMBER	Estimated cache physical write ratio under this MTTR. It is the ratio of the estimated number of cache writes to the number of cache writes under the current MTTR setting.
ESTD_TOTAL_WRITES	NUMBER	Estimated total number of physical writes under this MTTR
ESTD_TOTAL_WRITE_FACTOR	NUMBER	Estimated total physical write ratio under this MTTR. It is the ratio of the estimated total number of physical writes to the total number of physical writes under the current MTTR setting.
ESTD_TOTAL_IOS	NUMBER	Estimated total number of I/Os under this MTTR
ESTD_TOTAL_IO_FACTOR	NUMBER	Estimated total I/O ratio under this MTTR. It is the ratio of the estimated total number of I/Os to the total number of I/Os under the current MTTR setting.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "FAST_START_MTTR_TARGET"
- "STATISTICS_LEVEL"

9.86 V$MUTEX_SLEEP

V$MUTEX_SLEEP shows the wait time, and the number of sleeps for each combination of mutex type and location.

Column	Datatype	Description
MUTEX_TYPE	VARCHAR2(32)	Type of action/object the mutex protects
LOCATION	VARCHAR2(40)	The code location where the waiter slept for the mutex
SLEEPS	NUMBER	Number of sleeps for this MUTEX_TYPE and LOCATION
WAIT_TIME	NUMBER	Wait time in microseconds
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.87 V$MUTEX_SLEEP_HISTORY

V$MUTEX_SLEEP_HISTORY displays time-series data.

Each row in this view is for a specific time, mutex type, location, requesting session and blocking session combination. That is, it shows data related to a specific session (requesting session) that slept while requesting a specific mutex type and location, because it was being held by a specific blocking session. The data in this view is contained within a circular buffer, with the most recent sleeps shown.

Column	Datatype	Description
MUTEX_IDENTIFIER	NUMBER	Mutex ID
SLEEP_TIMESTAMP	TIMESTAMP(6)	The last date/time this MUTEX_TYPE and LOCATION was slept for by the REQUESTING_SESSION, while being held by the BLOCKING_SESSION.
MUTEX_TYPE	VARCHAR2(32)	Type of action/object the mutex protects
GETS	NUMBER	The total number of gets since the mutex was created and up until the time of the wait (and from all sessions past and present)
SLEEPS	NUMBER	The number of times the requester had to sleep before obtaining the mutex
REQUESTING_SESSION	NUMBER	The SID of a session requesting the mutex
BLOCKING_SESSION	NUMBER	The SID of a session holding the mutex
LOCATION	VARCHAR2(40)	The code location where the waiter slept for the mutex
MUTEX_VALUE	RAW(4 | 8)	If the mutex is held in exclusive (X) mode, this column shows the SID of the blocking session, else it shows the number of sessions referencing the mutex in S mode.
P1	NUMBER	Reserved for internal use
P1RAW	RAW(4 | 8)	Reserved for internal use

Column	Datatype	Description
P2	NUMBER	Reserved for internal use
P3	NUMBER	Reserved for internal use
P4	NUMBER	Reserved for internal use
P5	VARCHAR2(64)	Reserved for internal use
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.88 V$MVREFRESH

V$MVREFRESH displays information about the materialized views currently being refreshed.

Column	Datatype	Description
SID	NUMBER	Session identifier
SERIAL#	NUMBER	Session serial number, which is used to uniquely identify a session's objects. Guarantees that session-level commands are applied to the correct session objects if the session ends with, and another session begins with, the same session ID.
CURRMVOWNER	VARCHAR2(31)	Owner of the materialized view currently being refreshed. The materialized view resides in this user's schema.
CURRMVNAME	VARCHAR2(31)	Name of the materialized view currently being refreshed
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.89 V$MYSTAT

V$MYSTAT contains statistics on the current session.

Column	Datatype	Description
SID	NUMBER	ID of the current session
STATISTIC#	NUMBER	Number of the statistic
VALUE	NUMBER	Value of the statistic

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.90 V$NFS_CLIENTS

V$NFS_CLIENTS displays information about NFS clients currently connected to the XML DB NFS Server.

Column	Datatype	Description
CLIENTID	NUMBER	A number identifying the client
PRINCIPAL	VARCHAR2(2000)	User string denoting the principal that set the client ID (SetClientId)
CLIENTOPAQUEIDENTIFIER	VARCHAR2(1000)	Opaque string presented as identification by the client to the NFS server
VERIFIER	RAW(8)	Verifier presented by the client
LEASEEXPIRY	NUMBER	Number of seconds in which the lease expires for the client
CLIENTADDR	VARCHAR2(2000)	Address of the client
CONFIRMED	VARCHAR2(5)	TRUE if the client is confirmed; otherwise FALSE
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.91 V$NFS_LOCKS

V$NFS_LOCKS displays information about byte range locks held on different files by NFS clients.

Column	Datatype	Description
OPENSTATEID	RAW(16)	Open state ID of the open owner
OPENSEQUENCEID	NUMBER	Open Sequence ID of the open owner
LOCKSTATEID	RAW(16)	Lock state ID of the lock owner
LOCKSEQUENCEID	NUMBER	Lock sequence ID of the lock owner
LOCKOWNER	VARCHAR2(2000)	Opaque string presented as identification by the lock owner to the NFS server

Column	Datatype	Description
OFFSET	NUMBER	Byte Offset from which lock starts
LENGTH	NUMBER	Length of the lock
LOCKTYPE	VARCHAR2(20)	Type of the lock
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.92 V$NFS_OPEN_FILES

V$NFS_OPEN_FILES displays information about all the files currently opened by clients at the NFS server.

Column	Datatype	Description
CLIENTID	NUMBER	Number identifying the client
OPENOWNEROPAQUE	VARCHAR2(2000)	All the files currently opened by clients at the NFS server
OPENSTATEID	RAW(16)	Open state ID of the open owner
FILEHANDLE	RAW(32)	FileHandle of the file that has been opened
OPENSEQUENCEID	NUMBER	Open sequence ID of open owner
OPENREAD	VARCHAR2(5)	TRUE if the file is open for READ operations; otherwise FALSE
OPENWRITE	VARCHAR2(5)	TRUE if the file is open for WRITE operations; otherwise FALSE
SHAREACCESS	VARCHAR2(15)	Sharing mode of the file (SharedReadWrite, SharedRead, SharedWrite)
SHAREDENY	VARCHAR2(13)	Deny mode of the file (DenyReadWrite, DenyRead, DenyWrite)
CONFIRMED	VARCHAR2(5)	TRUE if open is confirmed; otherwise FALSE
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.93 V$NLS_PARAMETERS

V$NLS_PARAMETERS contains current values of NLS parameters.

Column	Datatype	Description
PARAMETER	VARCHAR2(64)	Parameter names are as follows: NLS_CALENDAR, NLS_CHARACTERSET, NLS_COMP, NLS_CURRENCY, NLS_DATE_FORMAT, NLS_DATE_LANGUAGE, NLS_DUAL_CURRENCY, NLS_ISO_CURRENCY, NLS_LANGUAGE, NLS_LENGTH_SEMANTICS, NLS_NCHAR_CHARACTERSET, NLS_NCHAR_CONV_EXCP, NLS_NUMERIC_CHARACTERS, NLS_SORT, NLS_TERRITORY, NLS_TIMESTAMP_FORMAT, NLS_TIMESTAMP_TZ_FORMAT Two additional parameters, NLS_TIME_FORMAT and NLS_TIME_TZ_FORMAT, are currently used for internal purposes only.
VALUE	VARCHAR2(64)	NLS parameter value
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.94 V$NLS_VALID_VALUES

V$NLS_VALID_VALUES lists all valid values for NLS parameters.

Column	Datatype	Description
PARAMETER	VARCHAR2(64)	Parameter name (LANGUAGE | SORT | TERRITORY | CHARACTERSET)
VALUE	VARCHAR2(64)	NLS parameter value
ISDEPRECATED	VARCHAR2(5)	Indicates whether the parameter has been deprecated (TRUE) or not (FALSE)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.95 V$NONLOGGED_BLOCK

V$NONLOGGED_BLOCK displays ranges of nonlogged datafile blocks recorded in the control file.

Prior to Oracle Database 12*c*, the presence of any nonlogged blocks in a data file was recorded in the file header via the FIRST_NONLOGGED_SCN column of the V$DATAFILE view. Now with 12*c*, in addition to the file header data, the ranges themselves are recorded in the control file. A control file range is a superset of the actual nonlogged blocks, meaning that small ranges can be merged to form larger ranges, even when there are some valid blocks between the smaller ranges.

The information in the view is maintained by RMAN VALIDATE, RMAN RESTORE, RMAN RECOVER, and Flashback Database and Media Recovery. A non RMAN-based restore will cause the data to become invalid, and it will be purged the next time any of those tasks are invoked and involve the file. As a result of space reuse, it is possible for ranges to no longer contain any nonlogged blocks. An RMAN VALIDATE command can be used to synchronize the ranges with the actual nonlogged blocks found from a scan of the data file.

Column	Datatype	Description
FILE#	NUMBER	Absolute file number of the data file that contains the nonlogged blocks
BLOCK#	NUMBER	Block number of the first nonlogged block in the range of nologged blocks
BLOCKS	NUMBER	Number of nonlogged blocks found starting with BLOCK#
NONLOGGED_START_CHANGE#	NUMBER	The smallest SCN on which any block in this block range became nonlogged. NULL if unknown.
NONLOGGED_START_TIME	DATE	The time that corresponds to NONLOGGED_START_CHANGE#. NULL if unknown.
NONLOGGED_END_CHANGE#	NUMBER	The largest SCN on which any block in this block range became nonlogged. NULL if unknown.
NONLOGGED_END_TIME	DATE	The time that corresponds to NONLOGGED_END_CHANGE#. NULL if unknown.
RESETLOGS_CHANGE#	NUMBER	The resetlogs SCN of the incarnation on which this block range was first marked as nonlogged. NULL if unknown.
RESETLOGS_TIME	DATE	The resetlogs time of the incarnation on which this block range was first marked as nologged. NULL if unknown.
OBJECT#	VARCHAR2(40)	The object ID this range belongs to. If this field is NULL, the object number is unknown.
REASON	VARCHAR2(9)	The reason why this block range appears in this list, for example, primary file offline, could not talk to primary, non-standby recovery, and so on. For Oracle Database 12*c* and later releases, it is always UNKNOWN.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.96 V$OBJECT_DEPENDENCY

V$OBJECT_DEPENDENCY displays the objects depended on by a package, procedure, or cursor that is currently loaded in the shared pool. For example, together with

V$SESSION and V$SQL, this view can be used to determine which tables are used in the SQL statement that a user is currently executing.

> **See Also:**
>
> "V$SESSION" and "V$SQL"

Column	Datatype	Description
FROM_ADDRESS	RAW(4 | 8)	Address of a procedure, package, or cursor that is currently loaded in the shared pool
FROM_HASH	NUMBER	Hash value of a procedure, package, or cursor that is currently loaded in the shared pool
TO_OWNER	VARCHAR2(64)	Owner of the object that is depended on
TO_NAME	VARCHAR2(1000)	Name of the object that is depended on
TO_ADDRESS	RAW(4 | 8)	Address of the object that is depended on. These can be used to look up more information on the object in V$DB_OBJECT_CACHE.
TO_HASH	NUMBER	Hash value of the object that is depended on. These can be used to look up more information on the object in V$DB_OBJECT_CACHE.
TO_TYPE	NUMBER	Type of the object that is depended on
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.97 V$OBJECT_PRIVILEGE

V$OBJECT_PRIVILEGE displays information about privileges associated with an object.

Column	Datatype	Description
OBJECT_TYPE_NAME	VARCHAR2(64)	Name of the object type
OBJECT_TYPE_ID	NUMBER	ID of the object type
PRIVILEGE_ID	NUMBER	ID of the privilege
PRIVILEGE_NAME	VARCHAR2(64)	Name of the privilege
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.98 V$OBSOLETE_BACKUP_FILES

V$OBSOLETE_BACKUP_FILES displays all obsolete backups, copies, and archived logs according to the current retention policy.

This view requires that the database is set using the DBMS_RCVMAN.SETDATABASE procedure.

Column	Datatype	Description
PKEY	NUMBER	Primary key for the backup
BACKUP_TYPE	VARCHAR2(32)	Type of the backup: • BACKUP SET • COPY • PROXY COPY
FILE_TYPE	VARCHAR2(32)	Type of the file: • DATAFILE • CONTROLFILE • SPFILE • REDO LOG • PIECE
KEEP	VARCHAR2(3)	Indicates whether the backup has a retention policy different from the value for CONFIGURE RETENTION POLICY (YES) or not (NO)
KEEP_UNTIL	DATE	If the KEEP UNTIL TIME clause of the BACKUP command was specified, then this column shows the date after which the backup becomes obsolete. If the column is null and KEEP_OPTIONS is not null, the backup never becomes obsolete.
KEEP_OPTIONS	VARCHAR2(13)	KEEP options for the backup: • LOGS - RMAN keeps the logs needed to recover the backup • NOLOGS - RMAN does not keep the logs needed to recover the backup If this column is null, then the backup has no KEEP options and will be made obsolete based on the retention policy.
STATUS	VARCHAR2(16)	Status of the backup: • AVAILABLE • UNAVAILABLE • EXPIRED • OTHER
FNAME	VARCHAR2(1024)	Name of the file
TAG	VARCHAR2(32)	Tag of the piece, copy, or proxy copy
MEDIA	VARCHAR2(80)	Media ID of the piece or proxy copy
RECID	NUMBER	Recid of the record in the controlfile
STAMP	NUMBER	Stamp of the record in the controlfile
DEVICE_TYPE	VARCHAR2(255)	Type of media device that stores the backup
BLOCK_SIZE	NUMBER	Block size for the backup (in bytes)
COMPLETION_TIME	DATE	Time when the backup completed
BS_KEY	NUMBER	Primary key of the backup set (valid only when BACKUP_TYPE is BACKUP SET)

Column	Datatype	Description
BS_COUNT	NUMBER	Count of the backup set from the controlfile record (valid only when BACKUP_TYPE is BACKUP SET)
BS_STAMP	NUMBER	Stamp of the backup set from the controlfile record (valid only when BACKUP_TYPE is BACKUP SET)
BS_TYPE	VARCHAR2(32)	Type of the backup set (valid only when BACKUP_TYPE is BACKUP SET): • DATAFILE • ARCHIVED LOG
BS_INCR_TYPE	VARCHAR2(32)	Incremental level of the backup set (valid only when BACKUP_TYPE is BACKUP SET)
BS_PIECES	NUMBER	Number of backup pieces in the backup set (valid only when BACKUP_TYPE is BACKUP SET)
BS_COMPLETION_TIME	DATE	Completion time of the backup set (valid only when BACKUP_TYPE is BACKUP SET)
BP_PIECE#	NUMBER	Number of the backup piece (valid only when FILE_TYPE is PIECE and BACKUP_TYPE is BACKUP SET)
BP_COPY#	NUMBER	Copy number of the backup piece (valid only when FILE_TYPE is PIECE and BACKUP_TYPE is BACKUP SET)
DF_FILE#	NUMBER	Absolute file number of the datafile (valid only when FILE_TYPE is DATAFILE)
DF_RESETLOGS_CHANGE#	NUMBER	System change number (SCN) of the most recent RESETLOGS when the control file or datafile was created (valid only when FILE_TYPE is DATAFILE)
DF_CREATION_CHANGE#	NUMBER	Creation SCN of the control file or datafile (valid only when FILE_TYPE is DATAFILE)
DF_CHECKPOINT_CHANGE#	NUMBER	System change number (SCN) of the most recent control file or datafile checkpoint (valid only when FILE_TYPE is DATAFILE)
DF_CKP_MOD_TIME	DATE	Modification time in case of SPFILE, otherwise time when the control file or datafile was checkpointed (valid only when FILE_TYPE is DATAFILE)
RL_THREAD#	NUMBER	Number of the redo thread (valid only when FILE_TYPE is REDO LOG)
RL_SEQUENCE#	NUMBER	Log sequence number (valid only when FILE_TYPE is REDO LOG)
RL_RESETLOGS_CHANGE#	NUMBER	System change number (SCN) of the most recent RESETLOGS when the record was created (valid only when FILE_TYPE is REDO LOG)
RL_FIRST_CHANGE#	NUMBER	First SCN of the redo log (valid only when FILE_TYPE is REDO LOG)
RL_FIRST_TIME	DATE	Time when Oracle switched into the redo log (valid only when FILE_TYPE is REDO LOG)
RL_NEXT_CHANGE#	NUMBER	First SCN of the next redo log in the thread (valid only when FILE_TYPE is REDO LOG)
RL_NEXT_TIME	DATE	First timestamp of the next redo log in the thread (valid only when FILE_TYPE is REDO LOG)

> **See Also:**
>
> *Oracle Database Backup and Recovery User's Guide* for more information about the `DBMS_RCVMAN.SETDATABASE` procedure

9.99 V$OBSOLETE_PARAMETER

`V$OBSOLETE_PARAMETER` displays information about obsolete initialization parameters. If any row of the view contains `TRUE` in the `ISSPECIFIED` column, then you should examine why.

Column	Datatype	Description
`NAME`	`VARCHAR2(64)`	Name of the parameter
`ISSPECIFIED`	`VARCHAR2(5)`	Indicates whether the parameter was specified in the parameter file (`TRUE`) or not (`FALSE`)
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.100 V$OFFLINE_RANGE

`V$OFFLINE_RANGE` displays datafile offline information from the control file.

Note that the last offline range of each datafile is kept in the `DATAFILE` record.

An offline range is created for a datafile when its tablespace is first altered to be `OFFLINE NORMAL` or `READ ONLY`, and then subsequently altered to be `ONLINE` or read/write. Note that no offline range is created if the datafile itself is altered to be `OFFLINE` or if the tablespace is altered to be `OFFLINE IMMEDIATE`.

> **See Also:**
>
> "V$DATAFILE"

Column	Datatype	Description
`RECID`	`NUMBER`	Record ID
`STAMP`	`NUMBER`	Record stamp
`FILE#`	`NUMBER`	Datafile number
`OFFLINE_CHANGE#`	`NUMBER`	SCN at which offlined
`ONLINE_CHANGE#`	`NUMBER`	SCN at which onlined

Column	Datatype	Description
ONLINE_TIME	DATE	Time of offline SCN
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the record
RESETLOGS_TIME	DATE	Resetlogs timestamp of the record
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.101 V$OFS_STATS

V$OFS_STATS displays performance statistics for various Oracle File System operations. These statistics are maintained at per mount level.

Column	Datatype	Description
OFS_MNTPNT	VARCHAR2(4096)	Mount point
OFS_LOOKUP	NUMBER	Number of lookup operations performed
OFS_FORGET	NUMBER	Number of forget operations performed
OFS_GETATTR	NUMBER	Number of getattr operations
OFS_SETATTR	NUMBER	Number of setattr operations
OFS_READLINK	NUMBER	Number of readlink operations
OFS_SYMLINK	NUMBER	Number of symlink operations
OFS_MKNOD	NUMBER	Number of mknod operations
OFS_MKDIR	NUMBER	Number of mkdir operations
OFS_UNLINK	NUMBER	Number of remove file operations
OFS_RMDIR	NUMBER	Number of remove directory operations
OFS_RENAME	NUMBER	Number of file rename operations
OFS_LINK	NUMBER	Number of hard link operations
OFS_OPEN	NUMBER	Number of file open operations
OFS_READ	NUMBER	Number of file read operations
OFS_WRITE	NUMBER	Number of file write operations
OFS_STATFS	NUMBER	Number of statfs operations performed
OFS_RELEASE	NUMBER	Number of release operations
OFS_FSYNC	NUMBER	Number of file sync operations
OFS_SETXATTR	NUMBER	Number of set extended attributes operations
OFS_GETXATTR	NUMBER	Number of get extended attributes
OFS_LISTXATTR	NUMBER	Number of list extended attributes
OFS_REMOVEXATTR	NUMBER	Number of remove extended attributes

Column	Datatype	Description
OFS_FLUSH	NUMBER	Number of flush operations
OFS_INIT	NUMBER	Number of init operations
OFS_OPENDIR	NUMBER	Number of opendir operations
OFS_READDIR	NUMBER	Number of readdir operations
OFS_RELEASEDIR	NUMBER	Number of releasedir operations
OFS_FSYNCDIR	NUMBER	Number of directory sync operations
OFS_GETLK	NUMBER	Number of file get lock operations
OFS_SETLK	NUMBER	Number of file lock operations
OFS_SETLKW	NUMBER	Number of file lock operation with wait option
OFS_ACCESS	NUMBER	Number of access operations
OFS_CREATE	NUMBER	Number of create operations
OFS_INTERRUPT	NUMBER	Number of interrupt operations received on the mount
OFS_BMAP	NUMBER	Number of block map operations received
OFS_DESTROY	NUMBER	Number of destroy operations
OFS_BYTES_READ	NUMBER	Total number of bytes read on the mount point
OFS_BYTES_WRITTEN	NUMBER	Total number of bytes written to the mount point
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

This database view is supported only on the Linux operating system.

See Also:

"V$OFSMOUNT"

9.102 V$OFS_THREADS

V$OFS_THREADS displays information about Oracle file system (OFS) threads.

Column	Datatype	Description
PDBID	NUMBER	ID of the PDB in which the thread was created

Column	Datatype	Description
FSID	NUMBER	ID of the mounted file system on which the thread is working
FSNAME	VARCHAR2(1024)	Name of the mounted file system on which the thread is working
FILE_NAME	VARCHAR2(1024)	File, directory, or filesystem on which the thread is working The value of this column depends on the value of the REQ_TYPE column: • If REQ_TYPE = SYSREQ, this column displays the path to the mount point of the filesystem on which the thread is working. • If REQ_TYPE = FILEREQ, this column displays the name of the file or directory on which the thread is working. • If REQ_TYPE = NONE, the value of this column is null.
THREADID	VARCHAR2(24)	ID of the thread
THREAD_TYPE	VARCHAR2(24)	Type of thread: • WORKER - The thread is used for executing file, directory, or filesystem requests. • RECEIVER - The thread receives requests from all OFS mounted file systems.
THREAD_NAME	VARCHAR2(24)	Name of the thread
REQ_TYPE	VARCHAR2(1024)	Type of request: • SYSREQ • FILEREQ • NONE
OPCODE	VARCHAR2(1024)	Type of operation on which the thread is working The value of this column depends on the value of the REQ_TYPE column: • If REQ_TYPE = SYSREQ, this column displays a DBMS_FS operation. • If REQ_TYPE = FILEREQ, this column displays any type of file operation. • If REQ_TYPE = NONE, the value of this column is null.
ELAPSED_TIME_MICRO	NUMBER	If REQ_TYPE = SYSREQ, the amount of time (in microseconds) that has elapsed since the current request was queued
SYSRQ_COUNT	NUMBER	Total number of REQ_TYPE = SYSREQ requests completed since the instance was started
FREQ_COUNT	NUMBER	Total number of REQ_TYPE = FILEREQ requests completed since the instance was started
WAIT_EVENT	VARCHAR2(64)	Event on which the thread is waiting
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

9.103 V$OFSMOUNT

`V$OFSMOUNT` provides information about the file systems that are mounted by Oracle File System.

Column	Datatype	Description
`OFS_MNTPATH`	`VARCHAR2(1024)`	Mount path where the file system is mounted
`OFS_FSPATH`	`VARCHAR2(1024)`	File system path
`OFS_MNTOPTS`	`VARCHAR2(1024)`	Mount options used to mount the file system
`OFS_MNTFLAGS`	`VARCHAR2(7)`	Flags to specify if the file system is mounted. A value of 1 indicates that the file system is mounted.
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
`OFS_NODENM`	`VARCHAR2(255)`	Node name
`OFS_FSID`	`NUMBER`	Unique ID that identifies the mounted file system
`OFS_FSTYPE`	`VARCHAR2(255)`	Oracle file system type. This is the value that is passed to the `dbms_fs.mount_oracle_fs()` procedure. Some of the expected values are `dbfs` and `ofs`.

> **Note:**
>
> This database view is supported only on the Linux operating system.

> **See Also:**
>
> - "V$OFS_STATS"
> - *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_FS.MOUNT_ORACLE_FS` procedure

9.104 V$ONLINE_REDEF

V$ONLINE_REDEF provides information about the status of currently running online redefinitions.

Column	Datatype	Description
SID	NUMBER	Session identifier
SERIAL#	NUMBER	Session serial number, which is used to uniquely identify a session's objects
REDEFINITION_ID	NUMBER	Redefinition identifier
TABLE_OWNER	VARCHAR2(129)	Owner of the table currently being redefined. The table resides in this user's schema.
ORIGINAL_TABLE_NAME	VARCHAR2(129)	Name of the original table
INTERIM_TABLE_NAME	VARCHAR2(1024)	Interim table currently being redefined
PARTITION_NAME	VARCHAR2(1024)	Partition of the table currently being redefined. The table resides in this user's schema.
OPERATION	VARCHAR2(128)	Operations during the redefining process: • start_redef_table • sync_interim_table • copy_table_dependents • finish_redef_table • abort_redef_table
SUBOPERATION	VARCHAR2(128)	Sub operation during the redefining process
DETAILED_MESSAGE	VARCHAR2(1024)	Details of operations during redefining process. This can include details such as the number of DML being processed, execution start_time, and partition_name
PROGRESS	VARCHAR2(128)	Percentage of completion of each operation
REFRESH_STATEMENT_SQL_ID	VARCHAR2(128)	The SQL ID for the statement in the REFRESH_STATEMENT column
REFRESH_STATEMENT	VARCHAR2(4000)	A refresh statement executed during a refresh operation in some online redefinition procedures. When refresh is a sub operation in the SUBOPERATION column, there will be a refresh statement in this REFRESH_STATEMENT column.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.105 V$OPEN_CURSOR

V$OPEN_CURSOR lists cursors that each user session currently has opened and parsed, or cached.

Column	Datatype	Description
SADDR	RAW(4 | 8)	Session address
SID	NUMBER	Session identifier
USER_NAME	VARCHAR2(128)	User that is logged in to the session
ADDRESS	RAW(4 | 8)	Used with HASH_VALUE to uniquely identify the SQL statement being executed in the session
HASH_VALUE	NUMBER	Used with ADDRESS to uniquely identify the SQL statement being executed in the session
SQL_ID	VARCHAR2(13)	SQL identifier of the SQL statement being executed in the session
SQL_TEXT	VARCHAR2(60)	First 60 characters of the SQL statement that is parsed into the open cursor
LAST_SQL_ACTIVE_TIME	DATE	Time when this cursor was last executed
SQL_EXEC_ID	NUMBER	If the open cursor is executing, then the SQL execution identifier for that execution (see V$SQL_MONITOR)
CURSOR_TYPE	VARCHAR2(64)	Type of cursor: • OPEN PL/SQL - Open PL/SQL cursors • OPEN - Other open cursors • SESSION CURSOR CACHED - Cursors cached in the generic session cursor cache • OPEN-RECURSIVE - Open recursive cursors • DICTIONARY LOOKUP CURSOR CACHED - Cursors cached in the dictionary lookup cursor cache • BUNDLE DICTIONARY LOOKUP CACHED - Cursors cached in the bundled dictionary lookup cursor cache • JAVA NAME TRANSLATION CURSOR CACHED - Cursors cached in the Java name translation cursor cache • REPLICATION TRIGGER CURSOR CACHED - Cursors cached in the replication trigger cursor cache • CONSTRAINTS CURSOR CACHED - Cursors cached in the constraints cursor cache • PL/SQL CURSOR CACHED - Cursors cached in the PL/SQL cursor cache
CHILD_ADDRESS	RAW(4 | 8)	Address of the child cursor
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.106 V$OPTIMIZER_PROCESSING_RATE

V$OPTIMIZER_PROCESSING_RATE displays the processing rates used by the optimizer to compute degree of parallelism.

> **Note:**
>
> You can manipulate these rates using these procedures for the DBMS_STATS package:
>
> - SET_PROCESSING_RATE
> - DELETE_PROCESSING_RATE
> - GATHER_PROCESSING_RATE
>
> See *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package.

Column	Datatype	Description
ADDRESS	RAW(4| 8)	Address of the handle to the parent for this cursor
OPERATION_NAME	VARCHAR2(64)	Name of the operation. The possible values are AGGR, ALL, CPU, CPU_ACCESS, CPU_AGGR, CPU_BYTES_PER_SEC, CPU_FILTER, CPU_GBY, CPU_HASH_JOIN, CPU_JOIN, CPU_NL_JOIN, CPU_RANDOM_ACCESS, CPU_ROWS_PER_SEC, CPU_SEQUENTIAL_ACCESS, CPU_SM_JOIN, CPU_SORT, HASH, IO, IO_ACCESS, IO_BYTES_PER_SEC, IO_RANDOM_ACCESS, IO_ROWS_PER_SEC, IO_SEQUENTIAL_ACCESS, MEMCMP, MEMCPY
MANUAL_VALUE	VARCHAR2(10)	Value of the operation set manually by the user
CALIBRATION_VALUE	VARCHAR2(10)	Value of the operation obtained from calibration (by running the GATHER_PROCESSING_RATE procedure)
DEFAULT_VALUE	VARCHAR2(10)	Default value of the operation
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.107 V$OPTION

V$OPTION displays Oracle Database options and features.

Typically, although not always, options must be separately licensed, whereas features come with the product and are enabled based on the product that is running (for example, Enterprise Edition).

Column	Datatype	Description
PARAMETER	VARCHAR2(64)	Name of the option (or feature)
VALUE	VARCHAR2(64)	Indicates whether the option (or feature) is installed (TRUE) or not (FALSE)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Licensing Information User Manual* for more information about Oracle Database options and features

9.108 V$OSSTAT

V$OSSTAT displays system utilization statistics from the operating system. One row is returned for each system statistic.

Column	Datatype	Description
STAT_NAME	VARCHAR2(64)	Name of the statistic (see Table 9-3)
VALUE	NUMBER	Instantaneous statistic value
OSSTAT_ID	NUMBER	Statistic ID
COMMENTS	VARCHAR2(64)	Any additional operating system-specific clarifications for the statistic
CUMULATIVE	VARCHAR2(3)	Indicates whether the statistic is cumulative (that is, accumulates over time) (YES) or not (NO)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Table 9-3 V$OSSTAT Statistics

Statistic Name	Description
NUM_CPUS	Number of CPUs or processors available

Table 9-3 (Cont.) V$OSSTAT Statistics

Statistic Name	Description
IDLE_TIME	Number of hundredths of a second that a processor has been idle, totalled over all processors
BUSY_TIME	Number of hundredths of a second that a processor has been busy executing user or kernel code, totalled over all processors
USER_TIME	Number of hundredths of a second that a processor has been busy executing user code, totalled over all processors
SYS_TIME	Number of hundredths of a second that a processor has been busy executing kernel code, totalled over all processors
IOWAIT_TIME	Number of hundredths of a second that a processor has been waiting for I/O to complete, totalled over all processors
NICE_TIME	Number of hundredths of a second that a processor has been busy executing low-priority user code, totalled over all processors
AVG_IDLE_TIME	Number of hundredths of a second that a processor has been idle, averaged over all processors
AVG_BUSY_TIME	Number of hundredths of a second that a processor has been busy executing user or kernel code, averaged over all processors
AVG_USER_TIME	Number of hundredths of a second that a processor has been busy executing user code, averaged over all processors
AVG_SYS_TIME	Number of hundredths of a second that a processor has been busy executing kernel code, averaged over all processors
AVG_IOWAIT_TIME	Number of hundredths of a second that a processor has been waiting for I/O to complete, averaged over all processors
AVG_NICE_TIME	Number of hundredths of a second that a processor has been busy executing low-priority user code, averaged over all processors
OS_CPU_WAIT_TIME	Total number of hundredths of a second that processes have been in a ready state, waiting to be selected by the operating system scheduler to run
RSRC_MGR_CPU_WAIT_TIME	Total number of hundredths of a second that Oracle processes have been in a ready state, waiting for CPU to be available for their consumer group in the currently active resource plan
VM_IN_BYTES	Total number of bytes of data that have been paged in due to virtual memory paging
VM_OUT_BYTES	Total number of bytes of data that have been paged out due to virtual memory paging
PHYSICAL_MEMORY_BYTES	Total number of bytes of physical memory
LOAD	Current number of processes that are either running or in the ready state, waiting to be selected by the operating-system scheduler to run. On many platforms, this statistic reflects the average load over the past minute.
NUM_CPU_CORES	Number of CPU cores available (includes subcores of multicore CPUs as well as single-core CPUs)
NUM_CPU_SOCKETS	Number of CPU sockets available (represents an absolute count of CPU chips on the system, regardless of multithreading or multi-core architectures)
NUM_VCPUS	Number of virtual CPUs available
NUM_LCPUS	Number of logical CPUs available (includes hardware threads if hardware threading is turned on)
TCP_SEND_SIZE_MIN	Minimum size of the TCP send buffer

Table 9-3 (Cont.) V$OSSTAT Statistics

Statistic Name	Description
TCP_SEND_SIZE_DEFAULT	Default size of the TCP send buffer
TCP_SEND_SIZE_MAX	Maximum size of the TCP send buffer
TCP_RECEIVE_SIZE_MIN	Minimum size of the TCP receive buffer
TCP_RECEIVE_SIZE_DEFAULT	Default size of the TCP receive buffer
TCP_RECEIVE_SIZE_MAX	Maximum size of the TCP receive buffer
GLOBAL_SEND_SIZE_MAX	Maximum size of the global send buffer
GLOBAL_RECEIVE_SIZE_MAX	Maximum size of the global receive buffer

> **Note:**
>
> The availability of all statistics except for `NUM_CPUS` and `RSRC_MGR_CPU_WAIT_TIME` is subject to the operating system platform on which the Oracle Database is running.

9.109 V$PARALLEL_DEGREE_LIMIT_MTH

`V$PARALLEL_DEGREE_LIMIT_MTH` displays all available parallel degree limit resource allocation methods.

Column	Datatype	Description
`NAME`	`VARCHAR2(40)`	Name of the parallel degree limit resource allocation method
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.110 V$PARAMETER

`V$PARAMETER` displays information about the initialization parameters that are currently in effect for the session. A new session inherits parameter values from the instance-wide values displayed by the `V$SYSTEM_PARAMETER` view.

Column	Datatype	Description
`NUM`	`NUMBER`	Parameter number
`NAME`	`VARCHAR2(80)`	Name of the parameter

Column	Datatype	Description
TYPE	NUMBER	Parameter type: • 1 - Boolean • 2 - String • 3 - Integer • 4 - Parameter file • 5 - Reserved • 6 - Big integer
VALUE	VARCHAR2(4000)	Parameter value for the session (if modified within the session); otherwise, the instance-wide parameter value
DISPLAY_VALUE	VARCHAR2(4000)	Parameter value in a user-friendly format. For example, if the VALUE column shows the value 262144 for a big integer parameter, then the DISPLAY_VALUE column will show the value 256K.
DEFAULT_VALUE	VARCHAR2(255)	The default value for this parameter. This is the value of the parameter if a value is not explicitly specified for the parameter.
ISDEFAULT	VARCHAR2(9)	Indicates whether the parameter is set to the default value (TRUE) or the parameter value was specified in the parameter file (FALSE). The database sets the value of the ISDEFAULT column to TRUE for parameters that are not specified in the init.ora or server parameter file (SPFILE).
ISSES_MODIFIABLE	VARCHAR2(5)	Indicates whether the parameter can be changed with ALTER SESSION (TRUE) or not (FALSE)
ISSYS_MODIFIABLE	VARCHAR2(9)	Indicates whether the parameter can be changed with ALTER SYSTEM and when the change takes effect: • IMMEDIATE - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect immediately. • DEFERRED - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect in subsequent sessions. • FALSE - Parameter cannot be changed with ALTER SYSTEM unless a server parameter file was used to start the instance. The change takes effect in subsequent instances.
ISPDB_MODIFIABLE	VARCHAR2(5)	Indicates whether the parameter can be modified inside a PDB (TRUE) or not (FALSE)
ISINSTANCE_MODIFIABLE	VARCHAR2(5)	For parameters that can be changed with ALTER SYSTEM, indicates whether the value of the parameter can be different for every instance (TRUE) or whether the parameter must have the same value for all Real Application Clusters instances (FALSE). If the ISSYS_MODIFIABLE column is FALSE, then this column is always FALSE.
ISMODIFIED	VARCHAR2(10)	Indicates whether the parameter has been modified after instance startup: • MODIFIED - Parameter has been modified with ALTER SESSION • SYSTEM_MOD - Parameter has been modified with ALTER SYSTEM (which causes all the currently logged in sessions' values to be modified) • FALSE - Parameter has not been modified after instance startup

Column	Datatype	Description
ISADJUSTED	VARCHAR2(5)	Indicates whether Oracle adjusted the input value to a more suitable value (for example, the parameter value should be prime, but the user input a non-prime number, so Oracle adjusted the value to the next prime number)
ISDEPRECATED	VARCHAR2(5)	Indicates whether the parameter has been deprecated (TRUE) or not (FALSE)
ISBASIC	VARCHAR2(5)	Indicates whether the parameter is a basic parameter (TRUE) or not (FALSE)
DESCRIPTION	VARCHAR2(255)	Description of the parameter
UPDATE_COMMENT	VARCHAR2(255)	Comments associated with the most recent update
HASH	NUMBER	Hash value for the parameter name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Examples

The following query returns the default value for the ALLOW_GLOBAL_DBLINKS initialization parameter:

```
SQL> SELECT name, default_value FROM v$parameter
  2  WHERE name = 'allow_global_dblinks';

NAME
--------------------------------------------------------------
DEFAULT_VALUE
--------------------------------------------------------------
allow_global_dblinks
FALSE


SQL>
```

The following query shows that the ALLOW_GLOBAL_DBLINKS initialization parameter is not modifiable in a PDB:

```
SQL> SELECT name, ispdb_modifiable FROM v$parameter
  2  WHERE name = 'allow_global_dblinks';

NAME
--------------------------------------------------------------
ISPDB
-----
allow_global_dblinks
FALSE
```

```
SQL>
```

> **See Also:**
>
> "V$SYSTEM_PARAMETER"

9.111 V$PARAMETER_VALID_VALUES

V$PARAMETER_VALID_VALUES displays a list of valid values for list parameters.

Column	Datatype	Description
NUM	NUMBER	Parameter number
NAME	VARCHAR2(64)	Parameter name
ORDINAL	NUMBER	Ordinal number in the list (1-based)
VALUE	VARCHAR2(255)	Parameter value at ordinal
ISDEFAULT	VARCHAR2(64)	Indicates whether the given ordinal value is the default value for the parameter
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.112 V$PARAMETER2

V$PARAMETER2 displays information about the initialization parameters that are currently in effect for the session, with each list parameter value appearing as a row in the view. A new session inherits parameter values from the instance-wide values displayed in the V$SYSTEM_PARAMETER2 view.

Presenting the list parameter values in this format enables you to quickly determine the values for a list parameter. For example, if a parameter value is a, b, then the V$PARAMETER view does not tell you if the parameter has two values (both a and b) or one value (a, b). V$PARAMETER2 makes the distinction between the list parameter values clear.

Column	Datatype	Description
NUM	NUMBER	Parameter number
NAME	VARCHAR2(80)	Name of the parameter

Column	Datatype	Description
TYPE	NUMBER	Parameter type: • 1 - Boolean • 2 - String • 3 - Integer • 4 - Parameter file • 5 - Reserved • 6 - Big integer
VALUE	VARCHAR2(4000)	Parameter value for the session (if modified within the session); otherwise, the instance-wide parameter value
DISPLAY_VALUE	VARCHAR2(4000)	Parameter value in a user-friendly format. For example, if the VALUE column shows the value 262144 for a big integer parameter, then the DISPLAY_VALUE column will show the value 256K.
ISDEFAULT	VARCHAR2(6)	Indicates whether the parameter is set to the default value (TRUE) or the parameter value was specified in the parameter file (FALSE)
ISSES_MODIFIABLE	VARCHAR2(5)	Indicates whether the parameter can be changed with ALTER SESSION (TRUE) or not (FALSE)
ISSYS_MODIFIABLE	VARCHAR2(9)	Indicates whether the parameter can be changed with ALTER SYSTEM and when the change takes effect: • IMMEDIATE - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect immediately. • DEFERRED - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect in subsequent sessions. • FALSE - Parameter cannot be changed with ALTER SYSTEM unless a server parameter file was used to start the instance. The change takes effect in subsequent instances.
ISPDB_MODIFIABLE	VARCHAR2(5)	Indicates whether the parameter can be modified inside a PDB (TRUE) or not (FALSE). In a non-CDB, the value of this column is NULL.
ISINSTANCE_MODIFIABLE	VARCHAR2(5)	For parameters that can be changed with ALTER SYSTEM, indicates whether the value of the parameter can be different for every instance (TRUE) or whether the parameter must have the same value for all Real Application Clusters instances (FALSE). If the ISSYS_MODIFIABLE column is FALSE, then this column is always FALSE.
ISMODIFIED	VARCHAR2(10)	Indicates whether the parameter has been modified after instance startup: • MODIFIED - Parameter has been modified with ALTER SESSION • SYSTEM_MOD - Parameter has been modified with ALTER SYSTEM (which causes all the currently logged in sessions' values to be modified) • FALSE - Parameter has not been modified after instance startup
ISADJUSTED	VARCHAR2(5)	Indicates whether Oracle adjusted the input value to a more suitable value (for example, the parameter value should be prime, but the user input a non-prime number, so Oracle adjusted the value to the next prime number)

Column	Datatype	Description
ISDEPRECATED	VARCHAR2(5)	Indicates whether the parameter has been deprecated (TRUE) or not (FALSE)
ISBASIC	VARCHAR2(5)	Indicates whether the parameter is a basic parameter (TRUE) or not (FALSE)
DESCRIPTION	VARCHAR2(255)	Description of the parameter
ORDINAL	NUMBER	Position (ordinal number) of the parameter value. Useful only for parameters whose values are lists of strings.
UPDATE_COMMENT	VARCHAR2(255)	Comments associated with the most recent update
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SYSTEM_PARAMETER"
- "V$PARAMETER"

9.113 V$PASSWORDFILE_INFO

V$PASSWORDFILE_INFO provides information about the database password file.

This view can be queried from the root or from a pluggable database (PDB) in a multitenant container database (CDB). When queried, this view always returns one row.

Column	Datatype	Description
FILE_NAME	VARCHAR2(513)	Fully qualified password file name/location.
FORMAT	VARCHAR2(6)	Shows the format of the password file. Possible values include: • Legacy • 12 • 12.2
IS_ASM	VARCHAR2(5)	Indicates whether the password file is stored in Oracle ASM. Possible values: • TRUE: The password file is stored in Oracle ASM. • FALSE: The password file is stored in Oracle Exascale or in the operating system file system.

Column	Datatype	Description
IS_EXC	VARCHAR2(5)	Indicates whether the password file is stored in Oracle Exascale. Possible values: • TRUE: The password file is stored in Oracle Exascale. • FALSE: The password file is stored in Oracle ASM or in the operating system file system.
CON_ID	NUMBER	The ID of the container to which the data pertains. Because there is only one password file for a CDB that is common for the entire CDB, the only value possible for CON_ID is 0 for this view.

> **Note:**
>
> If the database password file name or location was recently changed, and you do not see the change reflected in this view, you can run the following SQL statement:
>
> ```
> SQL> ALTER SYSTEM FLUSH PASSWORDFILE_METADATA_CACHE;
> ```
>
> This statement flushes the metadata cache and updates the database to use the new password file. It also updates this view with the current password file information.

9.114 V$PATCHES

V$PATCHES shows the patches applied on an Oracle ASM instance and the list of patches applied to an Oracle Grid infrastructure home directory.

> **Note:**
>
> If this view is queried in an RDBMS instance, no patch information is returned.

Column	Datatype	Description
PATCH_ID	NUMBER	Patch identifier
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.115 V$PDB_INCARNATION

V$PDB_INCARNATION displays information about all PDB incarnations. Oracle creates a new PDB incarnation whenever a PDB is opened with the RESETLOGS option.

Column	Datatype	Description
DB_INCARNATION#	NUMBER	Database incarnation number
PDB_INCARNATION#	NUMBER	PDB incarnation number
STATUS	VARCHAR2(7)	Incarnation status: • ORPHAN: Orphan incarnation • CURRENT: Current incarnation of the PDB • PARENT: Parent of the current incarnation
INCARNATION_SCN	NUMBER	The SCN to flashback or recover to for this PDB incarnation
INCARNATION_TIME	DATE	The point in time recovered to for this PDB incarnation
BEGIN_RESETLOGS_SCN	NUMBER	The SCN at the beginning of PDB resetlogs
BEGIN_RESETLOGS_TIME	DATE	The time at the beginning of PDB resetlogs
END_RESETLOGS_SCN	NUMBER	The SCN at the end of PDB resetlogs
END_RESETLOGS_TIME	DATE	The time at the end of PDB resetlogs
PRIOR_DB_INCARNATION#	NUMBER	Parent database incarnation number
PRIOR_PDB_INCARNATION#	VARCHAR2(40)	Parent PDB incarnation number
FLASHBACK_DATABASE_ALLOWED	VARCHAR2(3)	Indicates whether the PDB can be flashbacked to this incarnation as part of a flashback database operation for the CDB
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.116 V$PDBS

V$PDBS displays information about PDBs associated with the current instance.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
DBID	NUMBER	PDB identifier calculated when the PDB is created and stored in all file headers associated with the PDB

Column	Datatype	Description
CON_UID	NUMBER	Unique identifier associated with the PDB
GUID	RAW(16)	Globally unique identifier (GUID) of this PDB
NAME	VARCHAR2(128)	Name of the PDB
OPEN_MODE	VARCHAR2(10)	Open mode information. Possible values: • MOUNTED • READ WRITE • READ ONLY • MIGRATE
RESTRICTED	VARCHAR2(3)	Indicates whether only users possessing RESTRICTED SESSION privilege can connect to the PDB. Possible values: • YES • NO • NULL
OPEN_TIME	TIMESTAMP(3) WITH TIME ZONE	Date and time when the database was last opened
CREATE_SCN	NUMBER	System change number (SCN) for the creation of this PDB
TOTAL_SIZE	NUMBER	Shows the disk space (in bytes) used by the PDB, including both data and temp files.
BLOCK_SIZE	NUMBER	The current block size for the PDB
RECOVERY_STATUS	VARCHAR2(26)	Shows the recovery status for the PDB. Possible values: • DISABLED: The PDB is offline. This is similar to all files belonging to this PDB being offline, except that all files to be added to this PDB in the future will also be offline to begin with. • DISABLED AUTOMATIC RECOVER: Same as DISABLED, except that standby Active Data Guard recovery will automatically attempt to spawn PDB recovery isolation for the PDB and transition the PDB into ENABLED. • ENABLED: The PDB is not offline at the PDB level. Individual files in the PDB may be online or offline at the file level.
SNAPSHOT_PARENT_CON_ID	NUMBER	This column shows the container ID of the PDB that this PDB is a snapshot clone of. This column shows a nonzero value only if the PDB is a snapshot clone. For all other cases, it shows a value of 0.
APPLICATION_ROOT	VARCHAR2(3)	Indicates whether the PDB is an application root
APPLICATION_PDB	VARCHAR2(3)	Indicates whether the PDB is an application PDB
APPLICATION_SEED	VARCHAR2(3)	Indicates whether the PDB is an application seed (an application seed is also an application PDB)
APPLICATION_ROOT_CON_ID	NUMBER	If this PDB is an application PDB, the container ID of an application root to which this application PDB belongs. If this PDB is an application root clone, the container ID of an application root to which this application root clone belongs. Otherwise, NULL.
APPLICATION_ROOT_CLONE	VARCHAR2(3)	Indicates whether this PDB is an application root clone (YES) or not (NO)
PROXY_PDB	VARCHAR2(3)	Indicates whether this PDB is a proxy PDB (YES) or not (NO)

Column	Datatype	Description
LOCAL_UNDO	NUMBER	Shows whether the PDB is in local undo. Possible values: • 1 – PDB is in local undo mode • 0 – PDB is in shared undo mode This column is not relevant for CDB$ROOT.
UNDO_SCN	NUMBER	System change number (SCN) at which the PDB was last converted from shared to local undo, or from local to shared undo. This column is not relevant for CDB$ROOT.
UNDO_TIMESTAMP	DATE	Date and time at which the PDB was last converted from shared to local undo, or from local to shared undo. This column is not relevant for CDB$ROOT.
CREATION_TIME	DATE	Date and time at which the PDB was created.
DIAGNOSTICS_SIZE	NUMBER	Shows the current disk space usage (in bytes) of the diagnostic traces generated in the PDB, which is represented by the CON_ID column of the row
PDB_COUNT	NUMBER	The number of user-created PDBs belonging to a given application root or CDB$ROOT. For all other containers, its value is 0.
AUDIT_FILES_SIZE	NUMBER	Shows the current disk space usage (in bytes) by Unified Audit files (.bin format) in the current PDB.
MAX_SIZE	NUMBER	Shows the maximum amount of disk space (in bytes) that can be used by data and temp files in the PDB
MAX_DIAGNOSTICS_SIZE	NUMBER	Shows the maximum amount of disk space (in bytes) that can be used by diagnostic traces generated in the PDB
MAX_AUDIT_SIZE	NUMBER	Shows the maximum amount of disk space (in bytes) that can be used by Unified Audit files (.bin format) in the PDB
LAST_CHANGED_BY	VARCHAR2(11)	Indicates what type of user last changed the PDB. Possible values: • COMMON USER • LOCAL USER
TEMPLATE	VARCHAR2(3)	For internal use only
TENANT_ID	VARCHAR2(256)	Pluggable database tenant key
UPGRADE_LEVEL	NUMBER	For internal use only
GUID_BASE64	VARCHAR2(30)	The GUID of the PDB, encoded in base64
RECOVERY_TARGET_PDB_INCARNATION#	NUMBER	The incarnation number to which all datafiles belonging to the PDB would be recovered by the RECOVER PLUGGABLE DATABASE command
CLOUD_IDENTITY	VARCHAR2(4000)	Cloud identifier for the PDB
CLOSE_TIME	TIMESTAMP(3) WITH TIME ZONE	Date and time when the database was last closed
PRIORITY	NUMBER	The priority of the PDB when performing an OPEN or SAVE STATE operation on multiple PDBs with a single ALTER PLUGGABLE DATABASE or ALTER DATABASE statement If a priority is not assigned to the PDB, then the value of this column is null. An operation is performed first on the PDB with the lowest PRIORITY number, then on the PDB with the second lowest PRIORITY number, and so on. The operation is then performed on PDBs with no assigned priority, if any, in no particular order.

Column	Datatype	Description
BACKUP_SIZE	NUMBER	Reserved for future use
BACKUP_STATUS	VARCHAR2(8)	Reserved for future use

9.117 V$PERSISTENT_PUBLISHERS

V$PERSISTENT_PUBLISHERS displays information about all active publishers of the persistent queues in the database. There is one row per instance per queue per publisher. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
QUEUE_ID	NUMBER	Identifier for the queue
QUEUE_SCHEMA	VARCHAR2(128)	Owner of the queue
QUEUE_NAME	VARCHAR2(128)	Name of the queue
PUBLISHER_NAME	VARCHAR2(128)	Name of the agent enqueuing the message
PUBLISHER_ADDRESS	VARCHAR2(1024)	Address of the publisher agent
PROTOCOL	NUMBER	Protocol used by the publisher's address
ENQUEUED_MSGS	NUMBER	Number of messages that have been enqueued
ELAPSED_ENQUEUE_TIME	NUMBER	Total time spent doing enqueue (in hundredths of a second)
ENQUEUE_CPU_TIME	NUMBER	Total CPU time for enqueue (in hundredths of a second)
LAST_ENQUEUE_TIME	TIMESTAMP(6)	Last enqueue message timestamp
ENQUEUE_TRANSACTIONS	NUMBER	Number of enqueue transactions
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.118 V$PERSISTENT_QMN_CACHE

V$PERSISTENT_QMN_CACHE displays detailed information and statistics about the background activities for all queue tables in the system. There is one row per queue table. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
QUEUE_TABLE_ID	NUMBER	Queue table object ID
TYPE	VARCHAR2(32)	Type of the queue table's queue monitor cache
STATUS	NUMBER	Status of the queue table's queue monitor cache

Column	Datatype	Description
NEXT_SERVICE_TIME	TIMESTAMP(3) WITH TIME ZONE	Time when the queue table should be serviced by QMON servers
WINDOW_END_TIME	TIMESTAMP(3) WITH TIME ZONE	Time manager activity period for non-owner queue table operations
TOTAL_RUNS	NUMBER	Total number of times this queue table is served
TOTAL_LATENCY	NUMBER	Cumulative latency in serving the queue table (in hundredths of a second)
TOTAL_ELAPSED_TIME	NUMBER	Total time spent in processing this queue table (in seconds)
TOTAL_CPU_TIME	NUMBER	Cumulative CPU time for serving the queue table (in hundredths of a second)
TMGR_ROWS_PROCESSED	NUMBER	Number of time manager entries processed
TMGR_ELAPSED_TIME	NUMBER	Cumulative time for time management activities (in hundredths of a second)
TMGR_CPU_TIME	NUMBER	Cumulative CPU time for time management activities (in hundredths of a second)
LAST_TMGR_PROCESSING_TIME	TIMESTAMP(3) WITH TIME ZONE	Last timer manager processing time
DEQLOG_ROWS_PROCESSED	NUMBER	Number of dequeue log entries processed
DEQLOG_PROCESSING_ELAPSED_TIME	NUMBER	Total time for processing dequeue log entries (in hundredths of a second)
DEQLOG_PROCESSING_CPU_TIME	NUMBER	Total CPU time for processing dequeue log entries (in hundredths of a second)
LAST_DEQLOG_PROCESSING_TIME	TIMESTAMP(3) WITH TIME ZONE	Last dequeue log processing time
DEQUEUE_INDEX_BLOCKS_FREED	NUMBER	Number of dequeue index blocks freed
HISTORY_INDEX_BLOCKS_FREED	NUMBER	Number of history index blocks freed
TIME_INDEX_BLOCKS_FREED	NUMBER	Number of time manager index blocks freed
INDEX_CLEANUP_COUNT	NUMBER	Number of times index block cleanup was attempted
INDEX_CLEANUP_ELAPSED_TIME	NUMBER	Total time for index block cleanup (in hundredths of a second)
INDEX_CLEANUP_CPU_TIME	NUMBER	Total CPU time for index block cleanup (in hundredths of a second)
LAST_INDEX_CLEANUP_TIME	TIMESTAMP(3) WITH TIME ZONE	Last index block cleanup time
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.119 V$PERSISTENT_QUEUES

V$PERSISTENT_QUEUES displays information about all active persistent queues in the database since the queues' first activity time. There is one row per queue. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
QUEUE_ID	NUMBER	Identifier for the queue
QUEUE_TABLE_ID	NUMBER	Queue table identifier
QUEUE_SCHEMA	VARCHAR2(128)	Owner of the queue
QUEUE_NAME	VARCHAR2(128)	Name of the queue
FIRST_ACTIVITY_TIME	TIMESTAMP(6)	First queue activity time since database startup
ENQUEUED_MSGS	NUMBER	Number of messages enqueued
DEQUEUED_MSGS	NUMBER	Number of messages dequeued **Note:** This column will not be incremented until all the subscribers of the message have dequeued the message and its retention time has elapsed.
BROWSED_MSGS	NUMBER	Number of messages that have been browsed
ELAPSED_ENQUEUE_TIME	NUMBER	Total time (in hundredths of a second) spent doing enqueue
ELAPSED_DEQUEUE_TIME	NUMBER	Total time (in hundredths of a second) spent doing dequeue
ENQUEUE_CPU_TIME	NUMBER	Total CPU time for enqueue (in hundredths of a second)
DEQUEUE_CPU_TIME	NUMBER	Total CPU time for dequeue (in hundredths of a second)
AVG_MSG_AGE	NUMBER	Average age of messages in the queue
DEQUEUED_MSG_LATENCY	NUMBER	Last dequeued message latency (in seconds)
ELAPSED_TRANSFORMATION_TIME	NUMBER	Total time (in hundredths of a second) spent doing transformation
ELAPSED_RULE_EVALUATION_TIME	NUMBER	Total time (in hundredths of a second) spent doing rule evaluation
ENQUEUED_EXPIRY_MSGS	NUMBER	Number of messages enqueued with expiry
ENQUEUED_DELAY_MSGS	NUMBER	Number of messages enqueued with delay
MSGS_MADE_EXPIRED	NUMBER	Number of messages expired by time manager
MSGS_MADE_READY	NUMBER	Number of messages made ready by time manager
LAST_ENQUEUE_TIME	TIMESTAMP(6)	Last message enqueue time
LAST_DEQUEUE_TIME	TIMESTAMP(6)	Last message dequeue time
LAST_TM_EXPIRY_TIME	TIMESTAMP(6)	Last time message was expired by time manager
LAST_TM_READY_TIME	TIMESTAMP(6)	Last time message was made ready by time manager
ENQUEUE_TRANSACTIONS	NUMBER	Number of enqueue transactions
DEQUEUE_TRANSACTIONS	NUMBER	Number of dequeue transactions
EXECUTION_COUNT	NUMBER	Number of executions of the dequeue cursor
OLDEST_MSGID	RAW(16)	Message ID of the oldest message in the queue
OLDEST_MSG_ENQTM	TIMESTAMP(6)	Enqueue time of the oldest message in the queue

Column	Datatype	Description
MANDATORY_AFF_SWITCHES_OUT	NUMBER	An affinity switch is a change in dequeue instance for a shard-subscriber pair. A mandatory affinity switch is when there are local enqueues in the queue at the instance but no local dequeues present, so the dequeue affinity is switched to another instance for that shard-subscriber pair. This column shows the number of times mandatory affinity switches were needed from this instance to another for this queue.
OPTIONAL_AFF_SWITCHES_OUT	NUMBER	Optional affinity switches are affinity switches that are not mandatory. Optional affinity switches are done for global load balancing across the Oracle Real Application Clusters (Oracle RAC) database. This column shows the number of times optional affinity switches were needed from this instance to another for this queue.
AFF_SWITCHES_BACK_IN	NUMBER	The number of times dequeue affinities have come back from other instances to this instance. (MANDATORY_AFF_SWITCHES_OUT + OPTIONAL_AFF_SWITCHES_OUT - AFF_SWITCHES_BACK_IN) is the number of cross instance affinities present across all shard-subscriber pair for shards owned by this instance for this queue.
CROSS_STREAM_JOBS	NUMBER	The number of times a shard is being forwarded to another instance due to cross instance dequeues for this queue
RESTORE_BITMAP_JOBS	NUMBER	The number of times subscribers used existing shard forwarding to have cross instance dequeues for this queue
SHADOW_AFF_SWITCHES_IN	NUMBER	The number of affinity switches for this queue where this instance is the dequeue instance for a shard-subscriber pair where the shard is being enqueued at another instance
SHADOW_AFF_SWITCHES_OUT	NUMBER	The number of affinity switches for this queue where shadow affinity is switched back to source instance of the shard. (SHADOW_AFF_SWITCHES_IN - SHADOW_AFF_SWITCHES_OUT) is the number of dequeue affinities which are performing cross instance dequeues from non-local shards.
SHADOW_SHARDS_RECEIVED	NUMBER	The number of times a shard is being forwarded from another instance to this instance due to cross instance dequeues for this queue
SHADOW_SHARDS_FREED	NUMBER	The number of times a forwarded shard to this instance was stopped due to removal of cross instance dequeues for this queue
SHADOW_EVENT_STREAMS_RECEIVED	NUMBER	The number of times an event stream is being forwarded from another instance to this instance due to cross instance dequeues for this queue
SHADOW_EVENT_STREAMS_FREED	NUMBER	The number of times a forwarded event stream to this instance was stopped due to removal of cross instance dequeues for this queue
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> For sharded queues, only the following columns in this view contain accurate information: FIRST_ACTIVITY_TIME, BROWSED_MSGS, LAST_ENQUEUE_TIME, LAST_DEQUEUE_TIME, ENQUEUE_TRANSACTIONS, and DEQUEUE_TRANSACTIONS. The rest of the columns in this view should be ignored when querying information about sharded queues.

9.120 V$PERSISTENT_SUBSCRIBERS

V$PERSISTENT_SUBSCRIBERS displays information about all active subscribers of the persistent queues in the database.

There is one row per instance per queue per subscriber. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

> **Note:**
>
> This view does not display information about sharded queues. For information about sharded queues, refer to the "V$AQ_SHARDED_SUBSCRIBER_STAT" view.

Column	Datatype	Description
QUEUE_ID	NUMBER	Identifier for the queue
QUEUE_SCHEMA	VARCHAR2(128)	Owner of the queue
QUEUE_NAME	VARCHAR2(128)	Name of the queue
SUBSCRIBER_ID	NUMBER	Internal subscriber number
SUBSCRIBER_NAME	VARCHAR2(512)	Name of the subscriber
SUBSCRIBER_ADDRESS	VARCHAR2(1024)	Address of the subscribing agent
PROTOCOL	NUMBER	Protocol of the subscribing agent
SUBSCRIBER_TYPE	VARCHAR2(128)	Type of the subscriber: • PROXY - Propagation subscriber • SUBSCRIBER - Normal subscriber • RECIPIENT - Recipient
FIRST_ACTIVITY_TIME	TIMESTAMP(6)	First subscriber activity time since database startup
ENQUEUED_MSGS	NUMBER	Number of messages enqueued since FIRST_ACTIVITY_TIME
DEQUEUED_MSGS	NUMBER	Number of messages dequeued since FIRST_ACTIVITY_TIME
AVG_MSG_AGE	NUMBER	Average age of messages in the queue
BROWSED_MSGS	NUMBER	Number of messages that have been browsed
EXPIRED_MSGS	NUMBER	Number of messages expired since FIRST_ACTIVITY_TIME
DEQUEUED_MSG_LATENCY	NUMBER	Last dequeued message latency (in seconds)
LAST_ENQUEUE_TIME	TIMESTAMP(6)	Timestamp of the last enqueued message
LAST_DEQUEUE_TIME	TIMESTAMP(6)	Timestamp of the last dequeued message
ELAPSED_DEQUEUE_TIME	NUMBER	Total time spent in dequeue (in hundredths of a second)

Column	Datatype	Description
DEQUEUE_CPU_TIME	NUMBER	Total CPU time for dequeue (in hundredths of a second)
DEQUEUE_TRANSACTIONS	NUMBER	Number of dequeue transactions
EXECUTION_COUNT	NUMBER	Number of executions of the dequeue index cursor
DEQUEUE_MEMORY_LOCKS	NUMBER	Number of dequeue transactions that obtained memory locks
DEQUEUE_DISK_LOCKS	NUMBER	Number of dequeue transactions that obtained disk locks
DEQUEUE_DISK_DELETES	NUMBER	Number of dequeue transactions that deleted index-organized table entries
OLDEST_MSGID	RAW(16)	Message ID of the oldest message
OLDEST_MSG_ENQTM	TIMESTAMP(6)	Enqueue time of the oldest message
PARENT_SUBSCRIBER_ID	NUMBER	Subscriber ID of the parent durable subscriber
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.121 V$PGA_TARGET_ADVICE

V$PGA_TARGET_ADVICE predicts how the cache hit percentage and over allocation count statistics displayed by the V$PGASTAT performance view would be impacted if the value of the PGA_AGGREGATE_TARGET parameter is changed.

The prediction is performed for various values of the PGA_AGGREGATE_TARGET parameter, selected around its current value. The advice statistic is generated by simulating the past workload run by the instance.

The content of the view is empty if PGA_AGGREGATE_TARGET is not set. In addition, the content of this view is not updated if the STATISTICS_LEVEL parameter is set to BASIC. Base statistics for this view are reset at instance startup and when the value of the PGA_AGGREGATE_TARGET initialization parameter is dynamically modified.

Column	Datatype	Description
PGA_TARGET_FOR_ESTIMATE	NUMBER	Value of PGA_AGGREGATE_TARGET for this prediction (in bytes)
PGA_TARGET_FACTOR	NUMBER	PGA_TARGET_FOR_ESTIMATE / the current value of the PGA_AGGREGATE_TARGET parameter
ADVICE_STATUS	VARCHAR2(3)	Indicates whether the advice is enabled (ON) or disabled (OFF) depending on the value of the STATISTICS_LEVEL parameter
BYTES_PROCESSED	NUMBER	Total bytes processed by all the work areas considered by this advice (in bytes)
ESTD_TIME	NUMBER	Time (in seconds) required to process the bytes

Column	Datatype	Description
ESTD_EXTRA_BYTES_RW	NUMBER	Estimated number of extra bytes which would be read or written if PGA_AGGREGATE_TARGET was set to the value of the PGA_TARGET_FOR_ESTIMATE column. This number is derived from the estimated number and size of work areas which would run in one-pass (or multi-pass) for that value of PGA_AGGREGATE_TARGET.
ESTD_PGA_CACHE_HIT_PERCENTAGE	NUMBER	Estimated value of the cache hit percentage statistic when PGA_AGGREGATE_TARGET equals PGA_TARGET_FOR_ESTIMATE. This column is derived from the above two columns and is equal to BYTES_PROCESSED / (BYTES_PROCESSED + ESTD_EXTRA_BYTES_RW)
ESTD_OVERALLOC_COUNT	NUMBER	Estimated number of PGA memory over-allocations if the value of PGA_AGGREGATE_TARGET is set to PGA_TARGET_FOR_ESTIMATE. A nonzero value means that PGA_TARGET_FOR_ESTIMATE is not large enough to run the work area workload. Hence, the DBA should not set PGA_AGGREGATE_TARGET to PGA_TARGET_FOR_ESTIMATE since Oracle will not be able to honor that target.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$PGASTAT"
- "PGA_AGGREGATE_TARGET"
- "STATISTICS_LEVEL"
- *Oracle Database Performance Tuning Guide* for information on tuning the PGA_AGGREGATE_TARGET initialization parameter using the PGA advice views

9.122 V$PGA_TARGET_ADVICE_HISTOGRAM

V$PGA_TARGET_ADVICE_HISTOGRAM predicts how statistics displayed by the V$SQL_WORKAREA_HISTOGRAM dynamic view would be impacted if the value of the PGA_AGGREGATE_TARGET parameter is changed.

This prediction is performed for various values of the PGA_AGGREGATE_TARGET parameter, selected around its current value. The advice statistic is generated by simulating the past workload run by the instance.

The content of the view is empty if PGA_AGGREGATE_TARGET is not set. In addition, the content of this view is not updated when the STATISTICS_LEVEL initialization parameter is set to BASIC. Base statistics for this view are reset at instance startup or when the value of the PGA_AGGREGATE_TARGET initialization parameter is dynamically modified.

Column	Datatype	Description
PGA_TARGET_FOR_ESTIMATE	NUMBER	Value of PGA_AGGREGATE_TARGET for this prediction (in bytes)
PGA_TARGET_FACTOR	NUMBER	PGA_TARGET_FOR_ESTIMATE / the current value of the PGA_AGGREGATE_TARGET parameter
ADVICE_STATUS	VARCHAR2(3)	Indicates whether the advice is enabled (ON) or disabled (OFF) depending on the value of the STATISTICS_LEVEL parameter
LOW_OPTIMAL_SIZE	NUMBER	Lower bound for the optimal memory requirement of work areas included in this row (in bytes)
HIGH_OPTIMAL_SIZE	NUMBER	Upper bound for the optimal memory requirement of work areas included in this row (in bytes)
ESTD_OPTIMAL_EXECUTIONS	NUMBER	Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which are predicted to run optimal given a value of PGA_AGGREGATE_TARGET equal to PGA_TARGET_FOR_ESTIMATE
ESTD_ONEPASS_EXECUTIONS	NUMBER	Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which are predicted to run one-pass given a value of PGA_AGGREGATE_TARGET equal to PGA_TARGET_FOR_ESTIMATE
ESTD_MULTIPASSES_EXECUTIONS	NUMBER	Number of work areas with an optimal memory requirement comprised between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE which are predicted to run multi-pass given a value of PGA_AGGREGATE_TARGET equal to PGA_TARGET_FOR_ESTIMATE
ESTD_TOTAL_EXECUTIONS	NUMBER	Sum of ESTD_OPTIMAL_EXECUTIONS, ESTD_ONEPASS_EXECUTIONS, and ESTD_MULTIPASSES_EXECUTIONS
IGNORED_WORKAREAS_COUNT	NUMBER	Number of work areas with optimal memory requirement between LOW_OPTIMAL_SIZE and HIGH_OPTIMAL_SIZE ignored in the advice generation due to memory and CPU constraints
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SQL_WORKAREA_HISTOGRAM"
- "PGA_AGGREGATE_TARGET"
- "STATISTICS_LEVEL"
- *Oracle Database Performance Tuning Guide* for information on tuning the PGA_AGGREGATE_TARGET initialization parameter using the PGA advice views

9.123 V$PGASTAT

V$PGASTAT displays PGA memory usage statistics as well as statistics about the automatic PGA memory manager when it is enabled (that is, when PGA_AGGREGATE_TARGET is set). Cumulative values in V$PGASTAT are accumulated since instance startup.

Column	Datatype	Description
NAME	VARCHAR2(64)	Name of the statistic (see Table 9-4)
VALUE	NUMBER	Statistic value
UNIT	VARCHAR2(12)	Unit for the value: • bytes • microseconds • percent
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Table 9-4 V$PGASTAT Statistics

Statistic Name	Description
aggregate PGA auto target	Amount of PGA memory the Oracle Database can use for work areas running in automatic mode. This amount is dynamically derived from the value of the PGA_AGGREGATE_TARGET initialization parameter and the current work area workload, and continuously adjusted by the Oracle Database. If this value is small compared to the value of PGA_AGGREGATE_TARGET, then a large amount of PGA memory is used by other components of the system (for example, PL/SQL or Java memory) and little is left for work areas. The DBA must ensure that enough PGA memory is left for work areas running in automatic mode.
aggregate PGA target parameter	Current value of the PGA_AGGREGATE_TARGET initialization parameter. If this parameter is not set, then its value is 0 and automatic management of PGA memory is disabled.
bytes processed	Number of bytes processed by memory intensive SQL operators, cumulated since instance startup.
cache hit percentage	A metric computed by the Oracle Database to reflect the performance of the PGA memory component, cumulative since instance startup. A value of 100% means that all work areas executed by the system since instance startup have used an optimal amount of PGA memory. When a work area cannot run optimal, one or more extra passes is performed over the input data. This will reduce the cache hit percentage in proportion to the size of the input data and the number of extra passes performed.
extra bytes read/written	Number of bytes processed during extra passes of the input data, cumulated since instance startup. When a work area cannot run optimal, one or more of these extra passes is performed.

Table 9-4 (Cont.) V$PGASTAT Statistics

Statistic Name	Description
global memory bound	Maximum size of a work area executed in automatic mode. This value is continuously adjusted by the Oracle Database to reflect the current state of the work area workload. The global memory bound generally decreases when the number of active work areas is increasing in the system. If the value of the global bound decreases below 1 MB, then the value of `PGA_AGGREGATE_TARGET` should be increased.
max processes count	Maximum number of processes active at any one time since instance startup.
maximum PGA allocated	Maximum number of bytes of PGA memory allocated at one time since instance startup.
maximum PGA used for auto workareas	Maximum amount of PGA memory consumed at one time by work areas running under the automatic memory management mode since instance startup.
maximum PGA used for manual workareas	Maximum amount of PGA memory consumed at one time by work areas running under the manual memory management mode since instance startup.
over allocation count	This statistic is cumulative since instance startup. Over allocating PGA memory can happen if the value of `PGA_AGGREGATE_TARGET` is too small. When this happens, the Oracle Database cannot honor the value of `PGA_AGGREGATE_TARGET` and extra PGA memory needs to be allocated. If over allocation occurs, then increase the value of `PGA_AGGREGATE_TARGET` using the information provided by the `V$PGA_TARGET_ADVICE` view.
PGA memory freed back to OS	Number of bytes of PGA memory freed back to the operating system, cumulated since instance startup.
process count	Number of processes active within up to the last 3 seconds.
recompute count (total)	Number of times the instance bound, which is a cap on the maximum size of each active work area, has been recomputed since instance startup. Generally, the instance bound is recomputed in the background every 3 seconds, but it could be recomputed by a foreground process when the number of work areas changes rapidly in a short period of time.
total freeable PGA memory	Number of bytes of PGA memory in all processes that could be freed back to the operating system.
total PGA allocated	Current amount of PGA memory allocated by the instance. The Oracle Database attempts to keep this number below the value of the `PGA_AGGREGATE_TARGET` initialization parameter. However, it is possible for the PGA allocated to exceed that value by a small percentage and for a short period of time when the work area workload is increasing very rapidly or when `PGA_AGGREGATE_TARGET` is set to a small value.
total PGA inuse	Indicates how much PGA memory is currently consumed by work areas. This number can be used to determine how much memory is consumed by other consumers of the PGA memory (for example, PL/SQL or Java).
total PGA used for auto workareas	Indicates how much PGA memory is currently consumed by work areas running under the automatic memory management mode. This number can be used to determine how much memory is consumed by other consumers of the PGA memory (for example, PL/SQL or Java).
total PGA used for manual workareas	Indicates how much PGA memory is currently consumed by work areas running under the manual memory management mode. This number can be used to determine how much memory is consumed by other consumers of the PGA memory (for example, PL/SQL or Java).

> **See Also:**
>
> "PGA_AGGREGATE_TARGET"

9.124 V$PKCS11_PATH

V$PKCS11_PATH displays all processes that are using a PKCS#11 library for Transparent Data Encryption (TDE).

The SQL command ADMINISTER KEY MANAGEMENT SWITCHOVER TO LIBRARY instructs the database to switch over from the current PKCS#11 library to a new PKCS#11 library, without incurring system downtime. After you issue this command, foreground and background processes are gradually switched over to the new library. You can use this view to monitor the PKCS#11 library being used by each process. When you determine that all processes have switched over to the new library, you can safely remove the old library from disk.

Column	Datatype	Description
PID	NUMBER	ID of the process
PNAME	VARCHAR2(5)	Name of the process
PKCS11_LIB_PATH	VARCHAR2(4000)	Full operating system path for the PKCS#11 library being used by the process
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.125 V$PLSQL_DEBUGGABLE_SESSIONS

V$PLSQL_DEBUGGABLE_SESSIONS shows the current sessions of all users that the current user has privileges to debug with a PL/SQL debugger.

Column	Datatype	Description
SID	NUMBER	Session identifier
SERIAL#	NUMBER	Session serial number
LOGON_TIME	DATE	Time of logon
USER#	NUMBER	Oracle user identifier
USERNAME	VARCHAR2(128)	Oracle user name
OSUSER	VARCHAR2(128)	Operating system client user name
PROCESS	VARCHAR2(24)	Operating system client process ID
MACHINE	VARCHAR2(64)	Operating system client machine name

Column	Datatype	Description
PORT	NUMBER	Operating system client port number
TERMINAL	VARCHAR2(30)	Operating system client terminal name
PROGRAM	VARCHAR2(84)	Operating system client program name
TYPE	VARCHAR2(10)	Session type
SERVICE_NAME	VARCHAR2(64)	Service name of the session
PLSQL_DEBUGGER_CONNECTED	VARCHAR2(5)	Indicates whether the session is connected to a PL/SQL debugger. Possible values: • TRUE • FALSE
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.126 V$PMEM_FILESTORE

V$PMEM_FILESTORE displays information about Persistent Memory Filestores (PMEM Filestores).

Column	Datatype	Description
NAME	VARCHAR2(65)	PMEM Filestore name
MOUNT_POINT	VARCHAR2(513)	Operating system directory path for the mount point of the PMEM Filestore
BACKING_FILE	VARCHAR2(513)	Operating system file path for the backing file of the PMEM Filestore
BLOCK_SIZE	NUMBER	Block size of the PMEM Filestore (in bytes)
TOTAL_BYTES	NUMBER	Current size of the PMEM Filestore (in bytes)
AUTOEXTENSIBLE	VARCHAR2(4)	Indicates whether the PMEM Filestore is autoextensible (YES) or not (NO)
INCREMENT_BY	NUMBER	If the PMEM Filestore is autoextensible, then this column displays the size of an autoextension increment (in bytes) If the PMEM Filestore is not autoextensible, then the value of this column is 0
MAX_BYTES	NUMBER	Maximum autoextend size (in bytes)
AVAILABLE_BYTES	NUMBER	Amount of free space currently available in the PMEM Filestore (in bytes)
USED_BYTES	NUMBER	Amount of space currently allocated to data and metadata in the PMEM Filestore (in bytes)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.127 V$PQ_SESSTAT

V$PQ_SESSTAT lists session statistics for parallel queries.

After you have run a query or DML operation, you can use the information derived from V$PQ_SESSTAT to view the number of PX (Parallel Execution) servers used, and other information for the session and system.

Column	Datatype	Description
STATISTIC	VARCHAR2(30)	Name of the statistic: • Queries Parallelized - Number of queries run in parallel • DDL Parallelized - Number of DDL operations run in parallel • DML Parallelized - Number of DML operations run in parallel • DFO Trees - Number of executed DFO trees • DOP - Degree of parallelism used for the last statement • Servers - Maximum number of PX servers used at the same time • Allocation Height - Requested number of PX servers per instance • Allocation Width - Requested number of instances • Local Msgs Sent - Number of local (intra-instance) messages sent • Distr Msgs Sent - Number of remote (inter-instance) messages sent • Local Msgs Recv'd - Number of local (intra-instance) messages received • Distr Msgs Recv'd - Number of remote (inter-instance) messages received • Server Sets - Maximum number of PX server sets used at the same time for the last statement • Total Servers Released - Total number of PX servers acquired and released • Servers Released Early - Total number of PX servers released proactively • Server Sets Released Early - Total number of PX server sets released proactively
LAST_QUERY	NUMBER	Value of the statistic for the last operation

Column	Datatype	Description
SESSION_TOTAL	NUMBER	Value of the statistic for the entire session to this point in time The value of the statistic for the entire session to this point in time is not maintained for the DOP, Servers, Allocation Height, Allocation Width, Server Sets, Total Servers Released, Servers Released Early, and Server Sets Released Early statistics.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.128 V$PQ_SLAVE

V$PQ_SLAVE lists statistics for each of the active PX (Parallel Execution) servers on an instance.

> **Note:**
>
> This view is deprecated. Oracle recommends that you instead use the V$PX_SERVER view.

> **See Also:**
>
> "V$PX_SERVER"

9.129 V$PQ_SYSSTAT

V$PQ_SYSSTAT lists system statistics for parallel queries.

After you have run a query or DML operation, you can use the information derived from V$PQ_SYSSTAT to view the number of PX (Parallel Execution) servers used, and other information for the system.

Column	Datatype	Description
STATISTIC	VARCHAR2(30)	Name of the statistic: • DDL Initiated - Total number of parallel DDL operations that were initiated • DDL Initiated (IPQ) - Total number of parallel DDL operations that were initiated for Internode Parallel Query • DFO Trees - Total number of DFO trees executed on this instance • DML Initiated - Total number of parallel DML operations that were initiated • DML Initiated (IPQ) - Total number of parallel DML operations that were initiated for Internode Parallel Query • Distr Msgs Recv'd - Total number of remote (inter-instance) messages received on this instance • Distr Msgs Sent - Total number of remote (inter-instance) messages sent on this instance • Local Msgs Recv'd - Total number of remote (inter-instance) messages received on this instance • Local Msgs Sent - Total number of local (intra-instance) messages sent on this instance • Queries Initiated - Total number of parallel queries initiated on this instance • Queries Initiated (IPQ) - Total number of parallel queries initiated on this instance for Internode Parallel Query • Queries Queued - Total number of queued queries on this instance • Server Sessions - Total number of operations executed in all PX servers on this instance • Servers Busy - Number of currently busy PX servers on this instance • Servers Cleaned Up - Total number of PX servers on this instance cleaned up due to process death • Servers Highwater - Number of active PX servers on this instance that have partaken in >= 1 operation so far • Servers Idle - Number of currently idle PX servers on this instance • Servers Shutdown - Total number of PX servers shutdown on this instance • Servers Started - Total number of PX servers started on this instance • Sessions Active - Total number of active sessions on this instance
VALUE	NUMBER	Value of the statistic
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.130 V$PQ_TQSTAT

V$PQ_TQSTAT contains statistics on parallel execution operations.

The statistics are compiled after the query completes and only remain for the duration of the session. It displays the number of rows processed through each PX (Parallel Execution) server at each stage of the execution tree. This view can help determine skew problems in a query's execution. (Note that for PDML, information from V$PQ_TQSTAT is available only after a commit or rollback operation.)

Column	Datatype	Description
DFO_NUMBER	NUMBER	Data flow operator (DFO) tree number to differentiate queries
TQ_ID	NUMBER	Table queue ID within the query, which represents the connection between two DFO nodes in the query execution tree
SERVER_TYPE	VARCHAR2(10)	The role in table queue - producer/consumer/ranger
NUM_ROWS	NUMBER	The number of rows produced/consumed
BYTES	NUMBER	The number of bytes produced/consumed
OPEN_TIME	NUMBER	Time (seconds) the table queue remained open
AVG_LATENCY	NUMBER	Time (minutes) for a message to be dequeued after it enters the queue
WAITS	NUMBER	The number of waits encountered during dequeue
TIMEOUTS	NUMBER	The number of timeouts when waiting for a message
PROCESS	VARCHAR2(6)	Process ID
INSTANCE	NUMBER	Instance ID
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.131 V$PROCESS

V$PROCESS displays information about the currently active processes.

Column	Datatype	Description
ADDR	RAW(4 | 8)	Address of the process state object
PID	NUMBER	Oracle process identifier
SOSID	VARCHAR2(24)	Operating system (process, thread) identifier. This identifier is unique whether the Oracle multiprocess/ multithread feature is enabled or not.

Column	Datatype	Description
SPID	VARCHAR2(24)	Operating system process identifier. The Oracle multiprocess/multithread feature is available for UNIX systems. When the Oracle multiprocess/multithread feature is enabled, RDBMS processes are mapped to threads running in operating system processes, and the SPID identifier is not unique for RDBMS processes. When the Oracle multiprocess/multithread feature is not enabled on UNIX systems, the SPID identifier is unique for RDBMS processes.
STID	VARCHAR2(24)	Operating system thread identifier. The Oracle multiprocess/multithread feature is available for UNIX systems. When the Oracle multiprocess/multithread feature is enabled, RDBMS processes are mapped to threads running in operating system processes, and the SPID and STID together uniquely identify an RDBMS process. The STID is not unique on Solaris. The STID is unique on Linux, AIX, and Microsoft Windows.
EXECUTION_TYPE	VARCHAR2(10)	Operating system execution type
PNAME	VARCHAR2(5)	Name of this process
USERNAME	VARCHAR2(15)	Operating system process username
SERIAL#	NUMBER	Process serial number
TERMINAL	VARCHAR2(30)	Operating system terminal identifier
PROGRAM	VARCHAR2(84)	Program in progress
TRACEID	VARCHAR2(255)	Trace file identifier
TRACEFILE	VARCHAR2(513)	Trace file name of the process
BACKGROUND	VARCHAR2(1)	1 for a SYSTEM background process; NULL for foreground processes or non-SYSTEM background processes
LATCHWAIT	VARCHAR2(16)	Address of the latch the process is waiting for; NULL if none
LATCHSPIN	VARCHAR2(16)	This column is obsolete
PGA_USED_MEM	NUMBER	PGA memory currently used by the process (in bytes)
PGA_ALLOC_MEM	NUMBER	PGA memory currently allocated by the process (including free PGA memory not yet released to the operating system by the server process), in bytes
PGA_FREEABLE_MEM	NUMBER	Allocated PGA memory which can be freed (in bytes)
PGA_MAX_MEM	NUMBER	Maximum PGA memory ever allocated by the process (in bytes)
NUMA_DEFAULT	NUMBER	The NUMA processor group of this process at initialization time
NUMA_CURR	NUMBER	The NUMA processor group of this process currently
CPU_USED	NUMBER	Tracks the CPU used by this process (in microseconds) from the time it was spawned

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.132 V$PROCESS_MEMORY

V$PROCESS_MEMORY displays dynamic PGA memory usage by named component categories for each process.

Column	Datatype	Description
PID	NUMBER	Oracle process identifier
SERIAL#	NUMBER	Oracle process serial number
CATEGORY	VARCHAR2(15)	Category name. Categories include "SQL", "PL/SQL", "OLAP" and "JAVA". Special categories are "Freeable" and "Other". Freeable memory has been allocated to the process by the operating system, but has not been allocated to a category. "Other" memory has been allocated to a category, but not to one of the named categories.
ALLOCATED	NUMBER	Bytes of PGA memory allocated by the process for the category. For the "Freeable" category, it is the amount of free PGA memory eligible to be released to the operating system.
USED	NUMBER	Bytes of PGA memory used by the process for the category. For "Freeable", the value is zero. For "Other", the value is NULL for performance reasons.
MAX_ALLOCATED	NUMBER	Maximum bytes of PGA memory ever allocated by the process for the category.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.133 V$PROCESS_MEMORY_DETAIL

V$PROCESS_MEMORY_DETAIL provides detailed information on dynamic PGA memory usage for each automatically captured snapshot.

Column	Datatype	Description
PID	NUMBER	Oracle process identifier

Column	Datatype	Description
SERIAL#	NUMBER	Oracle process serial number
TIMESTAMP	DATE	Time at which the snapshot was taken
SQL_ID	VARCHAR2(13)	Identifier for the relevant SQL statement
TOTAL_MB	NUMBER	Total number of megabytes of PGA memory allocated at the time of the snapshot
CATEGORY	VARCHAR2(15)	Category name. Categories include: • SQL • PL/SQL • OLAP • JAVA • Freeable • Other
NAME	VARCHAR2(26)	PGA memory allocation comment. Small allocations may be grouped together with NAME set to Miscellaneous for performance reasons.
HEAP_NAME	VARCHAR2(15)	Name of heap or heaps (if same name) containing the allocations
BYTES	NUMBER	Bytes of PGA memory allocated in the process from heaps with the given heap name and with the given allocation comment
ALLOCATION_COUNT	NUMBER	Number of allocations with the comment found in the process inside heaps with the given heap name
HEAP_DESCRIPTOR	RAW(4 | 8)	If all the allocations are from one heap, then this is the address of the heap descriptor for that heap. Otherwise, this column is NULL.
PARENT_HEAP_DESCRIPTOR	RAW(4 | 8)	If all the allocations are from one heap, then this is the address of the parent heap descriptor for that heap. Otherwise, this column is NULL. If the heap has no parent, the value is zero.
MOST_RECENT	NUMBER	Oracle process identifier (PID) for most recent snapshot
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.134 V$PROCESS_POOL

V$PROCESS_POOL provides information about process pools.

Column	Datatype	Description
POOL_NAME	VARCHAR2(512)	Pool name
ENABLED	VARCHAR2(5)	Indicates whether the pool is active (TRUE) or not (FALSE)
MIN_COUNT	NUMBER	The default or configured minimum value
BATCH_COUNT	NUMBER	The default or configured batch count
INIT_COUNT	NUMBER	The default or configured initial count

Column	Datatype	Description
CUR_COUNT	NUMBER	The number of spawned processes available in this pool
MAX_COUNT	NUMBER	When INIT_COUNT is set, MAX_COUNT shows the number of processes yet to be spawned. Note that the current process count (CUR_COUNT) cannot reach INIT_COUNT in cases where processes are consumed during the spawn.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This row is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.135 V$PROPAGATION_RECEIVER

V$PROPAGATION_RECEIVER displays information about buffer queue propagation schedules on the receiving (destination) side. The values are reset to zero when the database (or instance in an Oracle Real Application Clusters (Oracle RAC) environment) restarts, when propagation migrates to another instance, or when an unscheduled propagation is attempted.

Column	Datatype	Description
SRC_QUEUE_SCHEMA	VARCHAR2(128)	Name of the source schema
SRC_QUEUE_NAME	VARCHAR2(128)	Name of the source queue
SRC_DBNAME	VARCHAR2(395)	Name of the source database
DST_QUEUE_SCHEMA	VARCHAR2(128)	Name of the destination schema
DST_QUEUE_NAME	VARCHAR2(128)	Name of the destination queue
STARTUP_TIME	DATE	Startup time of this schedule. This time changes when the source/destination database gets restarted.
HIGH_WATER_MARK	NUMBER	High watermark of the messages received
ACKNOWLEDGEMENT	NUMBER	Acknowledgement of the messages received by the receiver
LAST_RECEIVED_MSG	NUMBER	Last received message
TOTAL_MSGS	NUMBER	Total number of messages
ELAPSED_UNPICKLE_TIME	NUMBER	Elapsed unpickle time
ELAPSED_RULE_TIME	NUMBER	Elapsed rule time
ELAPSED_ENQUEUE_TIME	NUMBER	Elapsed enqueue time
SESSION_ID	NUMBER	Session ID of the propagation receiver
SERIAL#	NUMBER	Serial number of the propagation receiver
SPID	VARCHAR2(24)	Process identification number of the propagation receiver
PROPAGATION_NAME	VARCHAR2(128)	Name of the propagation on the source database

Column	Datatype	Description
STATE	VARCHAR2(43)	State of the propagation receiver: • Initializing • Sending unapplied txns • Waiting for message from client • Receiving LCRs • Evaluating rules • Enqueueing LCRS • Waiting for memory • Waiting for apply to read • Waiting for message from propagation sender When the propagation schedule is not optimized, the state is Normal.
LAST_RECEIVED_MSG_POSITION	RAW(64)	Last received message position. Corresponds to LAST_RECEIVED_MSG, except the value is in position rather than SCN. Position is used by XStream to determine ordering.
ACKNOWLEDGEMENT_POSITION	RAW(64)	Acknowledgement position of the messages received by the receiver. Corresponds to ACKNOWLEDGEMENT, except the value is in position rather than SCN. Position is used by XStream to determine ordering.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.136 V$PROPAGATION_SENDER

V$PROPAGATION_SENDER displays information about buffer queue propagation schedules on the sending (source) side. The values are reset to zero when the database (or instance in an Oracle Real Application Clusters (Oracle RAC) environment) restarts, when propagation migrates to another instance, or when an unscheduled propagation is attempted.

Column	Datatype	Description
QUEUE_ID	NUMBER	Queue identifier of the queue
QUEUE_SCHEMA	VARCHAR2(128)	Schema of the queue
QUEUE_NAME	VARCHAR2(128)	Name of the queue
DST_QUEUE_SCHEMA	VARCHAR2(128)	Destination schema of the queue
DST_QUEUE_NAME	VARCHAR2(128)	Name of the destination queue
STARTUP_TIME	DATE	Time at which the propagation started
DBLINK	VARCHAR2(395)	Name of the destination database link
HIGH_WATER_MARK	NUMBER	High watermark of the messages sent
ACKNOWLEDGEMENT	NUMBER	Acknowledgement of the messages received by the receiver

Column	Datatype	Description
SCHEDULE_STATUS	VARCHAR2(128)	Status of the propagation schedule
TOTAL_MSGS	NUMBER	Total messages propagated
TOTAL_BYTES	NUMBER	Total bytes propagated
ELAPSED_DEQUEUE_TIME	NUMBER	Elapsed dequeue time (in hundredths of a second)
ELAPSED_PICKLE_TIME	NUMBER	Elapsed pickle time (time taken to linearize a logical change record (LCR) into a stream of bytes that can be sent over the network) (in hundredths of a second)
ELAPSED_PROPAGATION_TIME	NUMBER	Elapsed propagation time (in hundredths of a second)
ELAPSED_RULE_TIME	NUMBER	Elapsed rule time (in hundredths of a second)
MAX_NUM_PER_WIN	NUMBER	Maximum bytes per window
MAX_SIZE	NUMBER	Maximum bytes sent per window
LAST_MSG_LATENCY	NUMBER	Last propagated message latency
LAST_MSG_ENQUEUE_TIME	TIMESTAMP(6)	Last propagated message enqueue time
LAST_MSG_PROPAGATION_TIME	TIMESTAMP(6)	Last time when the message was propagated
LAST_LCR_LATENCY	NUMBER	Last propagated LCR latency
LAST_LCR_CREATION_TIME	DATE	Last propagated LCR timestamp
LAST_LCR_PROPAGATION_TIME	DATE	Last time when the LCR was propagated
DST_DATABASE_NAME	VARCHAR2(395)	Global name of the destination database
SESSION_ID	NUMBER	Session ID of the propagation sender process
SERIAL#	NUMBER	Serial number of the propagation sender process
SPID	VARCHAR2(24)	Process identification number of the propagation sender process
PROPAGATION_NAME	VARCHAR2(128)	Name of the propagation
STATE	VARCHAR2(128)	State of the propagation sender process: • Initializing • Initializing propagation receiver • Browsing LCRs • Evaluating rules • Dequeueing LCRs • Sending LCRs • Waiting for apply to be enabled • Waiting for apply database to start • Waiting for propagation to be enabled • Waiting for capture to terminate • Waiting for a subscriber to be added • Suspended due to a dropped subscriber • Suspended for auto split/merge • Waiting on empty queue When the SCHEDULE_STATUS column is not SCHEDULE OPTIMIZED, the state is the value of the SCHEDULE_STATUS column.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.137 V$PROXY_ARCHIVEDLOG

V$PROXY_ARCHIVEDLOG contains descriptions of archived log backups that were taken using the proxy copy functionality.

In a proxy copy, the media manager takes over the operations of backing up and restoring data. Each row represents a backup of one control file.

Column	Datatype	Description
RECID	NUMBER	Proxy copy record identifier
STAMP	NUMBER	Proxy copy stamp
DEVICE_TYPE	VARCHAR2(17)	Type of media device that stores the proxy copy
HANDLE	VARCHAR2(513)	Name or "handle" for the proxy copy
COMMENTS	VARCHAR2(81)	Comments about the proxy copy
MEDIA	VARCHAR2(65)	A comment that contains further information about the media manager that created this backup
MEDIA_POOL	NUMBER	Number of the media pool in which the proxy copy is stored
TAG	VARCHAR2(32)	Tag for the proxy copy
STATUS	VARCHAR2(1)	Status of the backup set: • A - Available • U - Unavailable • X - Expired • D - Deleted
DELETED	VARCHAR2(3)	Indicates whether this record has been deleted (YES) or not (NO)
THREAD#	NUMBER	Number of the redo thread
SEQUENCE#	NUMBER	Log sequence number
RESETLOGS_CHANGE#	NUMBER	RESETLOGS SCN of the database incarnation to which this archived log belongs
RESETLOGS_TIME	DATE	RESETLOGS time stamp of the database incarnation to which this archived log belongs
FIRST_CHANGE#	NUMBER	First SCN of this redo log
FIRST_TIME	DATE	Time when Oracle switched into the redo log
NEXT_CHANGE#	NUMBER	First SCN of the next redo log in the thread
NEXT_TIME	DATE	First time stamp of the next redo log in the thread
BLOCKS	NUMBER	Size of this archived redo log (in operating system blocks)

Column	Datatype	Description
BLOCK_SIZE	NUMBER	Block size for the copy (in bytes)
START_TIME	DATE	Time when the proxy copy was initiated
COMPLETION_TIME	DATE	Time when the proxy copy was completed
ELAPSED_SECONDS	NUMBER	Duration of the proxy copy
RMAN_STATUS_RECID	NUMBER	Owning V$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V$RMAN_STATUS stamp
TERMINAL	VARCHAR2(3)	Indicates whether this record corresponds to a terminal archived redo log, as defined in V$ARCHIVED_LOG (YES) or not (NO)
KEEP	VARCHAR2(3)	Indicates whether this backup set has a retention policy that is different than the value for the configure retention policy (YES) or not (NO)
KEEP_UNTIL	DATE	If specified, then this is the date after which the backup becomes obsolete. If this column is NULL, then the backup never expires.
KEEP_OPTIONS	VARCHAR2(11)	Additional retention options for this backup set: • LOGS - Indicates a long-term backup made with the LOGS keyword, which is now deprecated • BACKUP_LOGS - Indicates that the backup was made in open mode, so archived log backups must be applied to make it consistent • NOLOGS - Indicates a consistent backup made when the database was mounted • NULL - Indicates that this backup has no KEEP options and becomes obsolete based on the retention policy
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.138 V$PROXY_ARCHIVELOG_DETAILS

V$PROXY_ARCHIVELOG_DETAILS contains information about all available archive log proxy copies.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp
COPY_KEY	NUMBER	Copy identifier
THREAD#	NUMBER	Redo thread number
SEQUENCE#	NUMBER	Redo log sequence number

Column	Datatype	Description
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the database when this log was written
RESETLOGS_TIME	DATE	Resetlogs time of the database when this log was written
HANDLE	VARCHAR2(513)	Proxy copy handle identifies the copy for restore
MEDIA	VARCHAR2(65)	Name of the media on which the copy resides. This value is informational only. It is not needed for restore.
MEDIA_POOL	NUMBER	Media pool in which the copy resides. This is the same value that was entered in the POOL operand of the Recovery Manager BACKUP command.
TAG	VARCHAR2(32)	Proxy copy tag
FIRST_CHANGE#	NUMBER	First change number in the archived log
NEXT_CHANGE#	NUMBER	First change number in the next log
FIRST_TIME	DATE	Timestamp of the first change
NEXT_TIME	DATE	Timestamp of the next change
OUTPUT_BYTES	NUMBER	Total output bytes written
COMPLETION_TIME	DATE	Completion time
OUTPUT_BYTES_DISPLAY	VARCHAR2(3)	Displayable format for output bytes
KEEP	DATE	Indicates whether this backup set has a retention policy that is different than the value for the configure retention policy (YES) or not (NO)
KEEP_UNTIL	VARCHAR2(11)	If specified, then this is the date after which the backup becomes obsolete. If this column is NULL, then the backup never expires.
KEEP_OPTIONS	VARCHAR2(4000)	Additional retention options for this backup set: • LOGS - Indicates a long-term backup made with the LOGS keyword, which is now deprecated • BACKUP_LOGS - Indicates that the backup was made in open mode, so archived log backups must be applied to make it consistent • NOLOGS - Indicates a consistent backup made when the database was mounted • NULL - Indicates that this backup has no KEEP options and becomes obsolete based on the retention policy
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.139 V$PROXY_ARCHIVELOG_SUMMARY

V$PROXY_ARCHIVELOG_SUMMARY provides summary information about the output proxy archive log file.

Column	Datatype	Description
NUM_FILES_BACKED	NUMBER	Number of archived log files backed up
NUM_DISTINCT_FILES_BACKED	NUMBER	Number of distinct archived log files backed up
MIN_FIRST_CHANGE#	NUMBER	Minimum first change SCN
MAX_NEXT_CHANGE#	NUMBER	Maximum first change SCN
MIN_FIRST_TIME	DATE	Minimum first change time. Forms the redo range, along with MAX_NEXT_TIME.
MAX_NEXT_TIME	DATE	Maximum next change time
OUTPUT_BYTES	NUMBER	Total output size, in bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for output bytes
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.140 V$PROXY_COPY_DETAILS

V$PROXY_COPY_DETAILS contains information about all available control file and datafile proxy copies.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session recid
SESSION_STAMP	NUMBER	Session stamp
COPY_KEY	NUMBER	Copy identifier
FILE#	NUMBER	Absolute datafile number, or 0 if this is a control file backup
HANDLE	VARCHAR2(513)	Proxy copy handle identifies the copy for restore
MEDIA	VARCHAR2(65)	Name of the media on which the copy resides. This value is informational only. It is not needed for restore.
MEDIA_POOL	NUMBER	Media pool in which the copy resides. This is the same value that was entered in the POOL operand of the Recovery Manager BACKUP command.
TAG	VARCHAR2(32)	Proxy copy tag
CREATION_CHANGE#	NUMBER	Datafile creation change number
CREATION_TIME	DATE	Datafile creation timestamp
CHECKPOINT_CHANGE#	NUMBER	Checkpoint change number of the datafile when the copy was made
CHECKPOINT_TIME	DATE	Checkpoint timestamp of the datafile when the copy was made
OUTPUT_BYTES	NUMBER	Total output bytes written
COMPLETION_TIME	DATE	Completion time

Column	Datatype	Description
CONTROLFILE_TYPE	VARCHAR2(1)	Type of control file: • B - Normal control file • S - Standby control file
KEEP	VARCHAR2(3)	Indicates whether this backup set has a retention policy that is different than the value for the configure retention policy (YES) or not (NO)
KEEP_UNTIL	DATE	If specified, then this is the date after which the backup becomes obsolete. If this column is NULL, then the backup never expires.
KEEP_OPTIONS	VARCHAR2(11)	Additional retention options for this backup set: • LOGS - Indicates a long-term backup made with the LOGS keyword, which is now deprecated • BACKUP_LOGS - Indicates that the backup was made in open mode, so archived log backups must be applied to make it consistent • NOLOGS - Indicates a consistent backup made when the database was mounted. • NULL - Indicates that this backup has no KEEP options and becomes obsolete based on the retention policy
OUTPUT_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for output bytes
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.141 V$PROXY_COPY_SUMMARY

V$PROXY_COPY_SUMMARY provides summary information about the output proxy datafile and control file.

Column	Datatype	Description
NUM_COPIES	NUMBER	Number of copies created
NUM_DISTINCT_COPIES	NUMBER	Number of distinct copies (that contain datafiles with different checkpoints)
MIN_CHECKPOINT_CHANGE#	NUMBER	Minimum checkpoint change SCN
MAX_CHECKPOINT_CHANGE#	NUMBER	Maximum checkpoint change SCN
MIN_CHECKPOINT_TIME	DATE	Minimum checkpoint change time
MAX_CHECKPOINT_TIME	DATE	Maximum checkpoint change time
OUTPUT_BYTES	NUMBER	Total output bytes
OUTPUT_BYTES_DISPLAY	VARCHAR2(4000)	Displayable format for output bytes

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.142 V$PROXY_DATAFILE

V$PROXY_DATAFILE contains descriptions of datafile and control file backups that are taken with Proxy Copy. Each row represents a backup of one database file.

Column	Datatype	Description
RECID	NUMBER	Proxy copy record ID
STAMP	NUMBER	Proxy copy record stamp
DEVICE_TYPE	VARCHAR2(17)	Type of the device on which the copy resides
HANDLE	VARCHAR2(513)	Proxy copy handle identifies the copy for restore
COMMENTS	VARCHAR2(81)	Comment returned by the operating system or storage subsystem. This value is informational only. It is not needed for restore.
MEDIA	VARCHAR2(65)	Name of the media on which the copy resides. This value is informational only. It is not needed for restore.
MEDIA_POOL	NUMBER	Media pool in which the copy resides. This is the same value that was entered in the POOL operand of the Recovery Manager BACKUP command
TAG	VARCHAR2(32)	Proxy copy tag
STATUS	VARCHAR2(1)	Status of the backup set: • A - Available • U - Unavailable • X - Expired • D - Deleted
DELETED	VARCHAR2(3)	Indicates whether this record has been deleted (YES) or not (NO)
FILE#	NUMBER	Absolute datafile number, or 0 if this is a control file backup
CREATION_CHANGE#	NUMBER	Datafile creation change number
CREATION_TIME	DATE	Datafile creation Timestamp
RESETLOGS_CHANGE#	NUMBER	Resetlogs change number of the datafile when the copy was made
RESETLOGS_TIME	DATE	Resetlogs timestamp of the datafile when the copy was made
CHECKPOINT_CHANGE#	NUMBER	Checkpoint change number of the datafile when the copy was made
CHECKPOINT_TIME	DATE	Checkpoint timestamp of the datafile when the copy was made
ABSOLUTE_FUZZY_CHANGE#	NUMBER	Highest change in any block of the file, if known
RECOVERY_FUZZY_CHANGE#	NUMBER	Highest change written to the file by media recovery

Column	Datatype	Description
RECOVERY_FUZZY_TIME	DATE	Timestamp of the highest change written to the file by media recovery
INCREMENTAL_LEVEL	NUMBER	If this backup is part of an incremental backup strategy, then 0. Otherwise null.
ONLINE_FUZZY	VARCHAR2(3)	Indicates whether this copy was made after a crash or offline immediate (or is a copy of a copy which was taken improperly while the database was open) (YES) or not (NO). Recovery will need to apply all redo up to the next crash recovery marker to make the file consistent.
BACKUP_FUZZY	VARCHAR2(3)	Indicates whether this is a copy taken using the BEGIN BACKUP | END BACKUP technique (YES) or not (NO). The BEGIN BACKUP | END BACKUP technique is used internally when proxy copies of open files are created. Recovery will need to apply all redo up to the end backup marker to make this copy consistent.
BLOCKS	NUMBER	Size of the copy (in blocks). Also the size of the datafile when the copy was made.
BLOCK_SIZE	NUMBER	Block size of the datafile
OLDEST_OFFLINE_RANGE	NUMBER	If the file number is 0 (that is, this is a control file backup), the RECID of the oldest offline range record in this control file copy. 0 for datafile copies.
START_TIME	DATE	Starting time
COMPLETION_TIME	DATE	Completion time
ELAPSED_SECONDS	NUMBER	Number of elapsed seconds
CONTROLFILE_TYPE	VARCHAR2(1)	Type of control file: • B - Normal control file • S - Standby control file
KEEP	VARCHAR2(3)	Indicates whether this backup set has a retention policy that is different than the value for the configure retention policy (YES) or not (NO)
KEEP_UNTIL	DATE	If specified, then this is the date after which the backup becomes obsolete. If this column is NULL, then the backup never expires.
KEEP_OPTIONS	VARCHAR2(11)	Additional retention options for this backup set: • LOGS - Indicates a long-term backup made with the LOGS keyword, which is now deprecated • BACKUP_LOGS - Indicates that the backup was made in open mode, so archived log backups must be applied to make it consistent • NOLOGS - Indicates a consistent backup made when the database was mounted. • NULL - Indicates that this backup has no KEEP options and becomes obsolete based on the retention policy
RMAN_STATUS_RECID	NUMBER	Owning V$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V$RMAN_STATUS stamp
FOREIGN_DBID	NUMBER	Foreign DBID of the database from which this datafile was transported. The value is 0 if the file backed up is not a foreign database file.
PLUGGED_READONLY	VARCHAR2(3)	Indicates whether this is a proxy copy of a transported read-only foreign file (YES) or not (NO)

Column	Datatype	Description
PLUGIN_CHANGE#	NUMBER	SCN at which the foreign datafile was transported into the database. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_CHANGE#	NUMBER	SCN of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
PLUGIN_RESETLOGS_TIME	DATE	Time of the RESETLOGS operation for the incarnation into which this foreign file was transported. The value is 0 if this file is not a foreign database file.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
BACKED_BY_PDB	VARCHAR2(3)	Recovery Manager (RMAN) allows a PDB to be backed up in two ways. The value in this column indicates how the PDB backup was taken: • YES: The backup was taken when connected to the PDB • NO: The backup was taken when connected to the root container
GUID	RAW(16)	The GUID of the PDB to which the backup belongs. This is useful after the PDB is dropped to identify which PDB the backup belongs to.

9.143 V$PROXY_PDB_TARGETS

V$PROXY_PDB_TARGETS provides information about the target of a proxy PDB.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: *n*: Where *n* is the container ID of a proxy PDB
TARGET_PORT	NUMBER	Port number that the target of the proxy PDB has registered with the listener, and which will be used by the proxy PDB to connect to the target
TARGET_HOST	VARCHAR2(128)	Host name where the target of the proxy PDB is running, and which will be used by the proxy PDB to connect to the target
TARGET_SERVICE	VARCHAR2(128)	Service name that the target of the proxy PDB has registered with the listener, and which will be used by the proxy PDB to connect to the target
TARGET_USER	VARCHAR2(128)	User name used by the proxy PDB to connect to the target of the proxy PDB. If null, the name of the connected user will be used.

> **See Also:**
>
> *Oracle Multitenant Administrator's Guide* for information about creating proxy PDBs

9.144 V$PWFILE_USERS

V$PWFILE_USERS lists all users in the password file, and indicates whether the user has been granted the SYSDBA, SYSOPER, SYSASM, SYSBACKUP, SYSDG, and SYSKM privileges.

Column	Datatype	Description
USERNAME	VARCHAR2(128)	Name of the user that is contained in the password file
SYSDBA	VARCHAR2(5)	Indicates whether the user can connect with SYSDBA privileges (TRUE) or not (FALSE)
SYSOPER	VARCHAR2(5)	Indicates whether the user can connect with SYSOPER privileges (TRUE) or not (FALSE)
SYSASM	VARCHAR2(5)	Indicates whether the user can connect with SYSASM privileges (TRUE) or not (FALSE)
SYSBACKUP	VARCHAR2(5)	Indicates whether the user can connect with SYSBACKUP privileges (TRUE) or not (FALSE)
SYSDG	VARCHAR2(5)	Indicates whether the user can connect with SYSDG privileges (TRUE) or not (FALSE)
SYSKM	VARCHAR2(5)	Indicates whether the user can connect with SYSKM privileges (TRUE) or not (FALSE)
ACCOUNT_STATUS	VARCHAR2(30)	Account status: • OPEN • EXPIRED • EXPIRED (GRACE) • LOCKED (TIMED) • LOCKED • EXPIRED & LOCKED (TIMED) • EXPIRED & LOCKED • EXPIRED (GRACE) & LOCKED
PASSWORD_PROFILE	VARCHAR2(128)	Password profile name
LAST_LOGIN	TIMESTAMP(9) WITH TIME ZONE	The time of the last user login
LOCK_DATE	DATE	Date the account was locked if account status was LOCKED
EXPIRY_DATE	DATE	Date of expiration of the account
EXTERNAL_NAME	VARCHAR2(1024)	Shows Certificate DN or Principal Name of externally authenticated users
AUTHENTICATION_TYPE	VARCHAR2(8)	Indicates the authentication mechanism for the user: • EXTERNAL - CREATE USER *user1* IDENTIFIED EXTERNALLY; • GLOBAL - CREATE USER *user2* IDENTIFIED GLOBALLY; • PASSWORD - CREATE USER *user3* IDENTIFIED BY *password*;

Column	Datatype	Description
COMMON	VARCHAR2(3)	This column has a value of YES if an administrative privilege (for example, SYSDBA) was granted with CONTAINER=ALL. Otherwise, the column has a value of NO.
PASSWORD_VERSIONS	VARCHAR2(12)	Shows the list of versions of the password hashes (also known as "verifiers") existing for the account. The values for this column can include: • 11G: If a SHA-1 hash exists • 12C: If a de-optimized PBKDF2-based hash exists For more information about the 12C verifier, see *Oracle Database Concepts*. Note that any combination of these verifiers can exist for any given account.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.145 V$PX_INSTANCE_GROUP

V$PX_INSTANCE_GROUP provides information about the instance groups being used for parallel operations by the current session.

Column	Datatype	Description
QC_INSTANCE_GROUP	VARCHAR2(64)	The instance group being used by this session for parallel operations. This value repeats for every row returned.
WHY	VARCHAR2(23)	Where the current instance group name comes from, as follows: SERVICE - the instance group being used is from the session's service name PARALLEL_INSTANCE_GROUP - the instance group being used is being used because the PARALLEL_INSTANCE_GROUP initialization parameter has been set. The value repeats for every row returned.
INSTANCE_NUMBER	NUMBER	Instance number of the instance providing this instance group. There will be one row for each instance in the instance group that the Query Coordinator is using.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "PARALLEL_INSTANCE_GROUP"

9.146 V$PX_PROCESS

V$PX_PROCESS contains information about the sessions running parallel execution.

Column	Datatype	Description
SERVER_NAME	VARCHAR2(4)	The name of the PX server (P000, P001, and so on)
STATUS	VARCHAR2(9)	The state of the PX server (IN USE or AVAILABLE)
PID	NUMBER	The process identifier
SPID	VARCHAR2(24)	Operating system process ID
SID	NUMBER	The session ID of the PX server, if in use
SERIAL#	NUMBER	The session serial number of the PX server, if in use
IS_GV	VARCHAR2(5)	Indicates whether a PX server process in parallel is a normal process or a GV$ process. Possible values: • FALSE: The PX server process in parallel is a normal process • TRUE: The PX server process in parallel is a GV$ process
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.147 V$PX_PROCESS_DETAIL

V$PX_PROCESS_DETAIL lists statistics for each of the active PX (Parallel Execution) servers on an instance.

Column	Datatype	Description
SPID	VARCHAR2(24)	Operating system process ID
SERVER_NAME	VARCHAR2(7)	Name of the PX server (P000, P001, and so on)
STATISTIC	VARCHAR2(30)	Name of the statistic: • Start Time • Cleanup Start Time • Cleanup End Time
VALUE	VARCHAR2(64)	String representation of the value the statistic For example, if the value of the statistic is a timestamp, this column displays a string containing the timestamp information.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

9.148 V$PX_PROCESS_SYSSTAT

V$PX_PROCESS_SYSSTAT contains information about the sessions running parallel execution.

Column	Datatype	Description
STATISTIC	VARCHAR2(30)	Name of the statistic: • Buffers Allocated - Number of times a message buffer has been allocated • Buffers Current - Number of message buffers currently being used • Buffers Freed - Number of times a message buffer has been freed • Buffers HWM - Maximum number of concurrently allocated message buffers • Chunk Lists - Number of memory chunk lists • Memory Chunks Allocated - Number of large memory chunks allocated by PX servers • Memory Chunks Current - Number of large memory chunks currently being used • Memory Chunks Freed - Number of large memory chunks freed • Memory Chunks HWM - Maximum number of concurrently allocated chunks • Memory Chunks Permanent - Number of large memory chunks allocated permanently • Server Sessions - Total number of sessions created by all PX servers • Servers Available - Number of PX servers available to perform parallel operations • Servers Cleaned Up - Number of times PMON had to clean up a PX server. This should only happen during nonstandard termination of a parallel operation. If this number is large, then you should determine the cause. • Servers Highwater - Maximum number of concurrent PX server processes If this number is equal to the PARALLEL_MAX_SERVERS initialization parameter, then consider increasing the parameter. This could allow you to increase your throughput, especially if your system is under-utilized and the V$SYSSTAT statistic "Parallel operations downgraded to serial" is large. • Servers In Use - Number of PX servers currently performing parallel operations • Servers Shutdown - Number of times a PX server process has been shut down. A PX server process will be shut down if it has not been used recently. If this value is large, then consider increasing the parameter. This will improve performance by avoiding the latency of PX server process creation. • Servers Started - Number of times the system has had to create a PX server process
VALUE	NUMBER	Value of the statistic

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.149 V$PX_SERVER

V$PX_SERVER lists statistics for each of the active PX (Parallel Execution) servers on an instance.

Column	Datatype	Description
SERVER_NAME	VARCHAR2(4)	Name of the PX server
STATUS	VARCHAR2(4)	Current status of the PX server: • BUSY • IDLE
SESSIONS	NUMBER	Number of sessions that have used this PX server
IDLE_TIME_CUR	NUMBER	Amount of time spent idle while processing statements in the current session
BUSY_TIME_CUR	NUMBER	Amount of time spent busy while processing statements in the current session
CPU_SECS_CUR	NUMBER	Amount of CPU time (in seconds) spent on the current session
MSGS_SENT_CUR	NUMBER	Number of messages sent while processing statements for the current session
MSGS_RCVD_CUR	NUMBER	Number of messages received while processing statements for the current session
IDLE_TIME_TOTAL	NUMBER	Total amount of time (in minutes) this PX server has been idle
BUSY_TIME_TOTAL	NUMBER	Total amount of time (in minutes) this PX server has been active
CPU_SECS_TOTAL	NUMBER	Total amount of CPU time (in seconds) this PX server has used to process statements
MSGS_SENT_TOTAL	NUMBER	Total number of messages this PX server has sent
MSGS_RCVD_TOTAL	NUMBER	Total number of messages this PX server has received
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

9.150 V$PX_SESSION

V$PX_SESSION contains information about the sessions running parallel execution.

Column	Datatype	Description
SADDR	RAW(4 | 8)	Session address
SID	NUMBER	Session identifier
SERIAL#	NUMBER	Session serial number
QCSID	NUMBER	Session identifier of the parallel coordinator
QCSERIAL#	NUMBER	Session serial number of the parallel coordinator
QCINST_ID	NUMBER	Instance number on which the parallel coordinator is running
SERVER_GROUP	NUMBER	The logical group of PX servers to which this cluster database process belongs
SERVER_SET	NUMBER	The logical set of PX servers to which this cluster database process belongs. A single PX server group will have at most two PX server sets.
SERVER#	NUMBER	The logical number of the cluster database process within a PX server set
DEGREE	NUMBER	The degree of parallelism being used by the PX server set
REQ_DEGREE	NUMBER	The degree of parallelism that was requested by the user when the statement was issued and before any resource, multiuser, or load balancing reductions
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.151 V$PX_SESSTAT

V$PX_SESSTAT contains information about the sessions running parallel execution.

Column	Datatype	Description
SADDR	RAW(4 | 8)	Session address
SID	NUMBER	Session identifier
SERIAL#	NUMBER	Session serial number
QCSID	NUMBER	Session identifier of the parallel coordinator
QCSERIAL#	NUMBER	Session serial number of the parallel coordinator

Column	Datatype	Description
QCINST_ID	NUMBER	Instance number on which the parallel coordinator is running
SERVER_GROUP	NUMBER	The logical group of PX servers to which this cluster database process belongs
SERVER_SET	NUMBER	The logical set of PX servers that this cluster database process belongs to. A single PX server group will have at most two PX server sets.
SERVER#	NUMBER	The logical number of the cluster database process within a PX server set
DEGREE	NUMBER	The degree of parallelism being used by the PX server set
REQ_DEGREE	NUMBER	The degree of parallelism that was requested by the user when the statement was issued and before any resource, multiuser, or load balancing reductions
STATISTIC#	NUMBER	Statistic number
VALUE	NUMBER	Statistic value
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.152 V$QMON_COORDINATOR_STATS

V$QMON_COORDINATOR_STATS displays statistics of the non-sharded queue primary process. There is one row per instance. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
QMNC_PID	VARCHAR2(24)	Non-sharded queue primary process ID
STATUS	VARCHAR2(24)	Current status of the coordinator: • DEAD • INITIALIZING • RUNNING TASK COORDINATOR • WAITING • ADDING SERVER
NUM_SERVERS	NUMBER	Number of QMON servers currently running
LAST_SERVER_START_TIME	TIMESTAMP(3) WITH TIME ZONE	Last server startup time
LAST_SERVER_PID	VARCHAR2(24)	Process ID of the last server process (Qnnn) created
NEXT_WAKEUP_TIME	TIMESTAMP(3) WITH TIME ZONE	Next wakeup time of the coordinator
NEXT_READY_TIME	TIMESTAMP(3) WITH TIME ZONE	Ready time of the first delayed task
NEXT_EXPIRY_TIME	TIMESTAMP(3) WITH TIME ZONE	Expiry time of the next ready task

Column	Datatype	Description
LAST_WAIT_TIME	TIMESTAMP(3) WITH TIME ZONE	Time when the coordinator went to sleep
LAST_FAILURE	VARCHAR2(32)	Last failure encountered
LAST_FAILURE_TIME	TIMESTAMP(3) WITH TIME ZONE	Last failure time
MAX_TASK_LATENCY	VARCHAR2(40)	Maximum task latency across all the servers (in seconds)
MIN_TASK_LATENCY	VARCHAR2(40)	Minimum task latency across all the servers (in seconds)
TOTAL_TASK_LATENCY	NUMBER	Cumulative latency across all the tasks (in seconds)
TOTAL_TASKS_EXECUTED	NUMBER	Cumulative number of tasks serviced by all the servers
MAX_SERVERS	NUMBER	Maximum number of servers present at any point of time
CON_ID	NUMBER	The ID of the container to which the data pertains. The CON_ID value in this view is always 0. The rows pertain to the entire CDB or to the non-CDB.

9.153 V$QMON_SERVER_STATS

V$QMON_SERVER_STATS displays information and statistics about the active queue monitor server processes. There is one row per live queue monitor server process. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
QMNC_PID	VARCHAR2(24)	Non-sharded queue primary process ID
SERVER_PID	VARCHAR2(24)	Process ID of the server
SERVER_NAME	VARCHAR2(48)	Name of the server
STATUS	VARCHAR2(40)	Current state of the server: • UNUSED • RUNNING • IDLE WAIT • EXITING • NOT ACTIVE
SERVER_START_TIME	TIMESTAMP(3) WITH TIME ZONE	Start time of the server
TASK_NAME	VARCHAR2(32)	Current executing task
TASK_NUMBER	NUMBER	Unique task number of the running task
TASK_START_TIME	TIMESTAMP(3) WITH TIME ZONE	Start time of the running task
LAST_WAIT_TIME	TIMESTAMP(3) WITH TIME ZONE	Time when the server last waited
MAX_LATENCY	NUMBER	Maximum task latency for this server (in seconds)
MIN_LATENCY	NUMBER	Minimum task latency for this server (in seconds)
TOTAL_LATENCY	NUMBER	Cumulative task latency for this server (in seconds)
NUM_TASKS	NUMBER	Number of tasks processed by the server
LAST_FAILURE	VARCHAR2(128)	Last failure encountered by the server

Column	Datatype	Description
LAST_FAILURE_TIME	TIMESTAMP(3) WITH TIME ZONE	Last failure time
LAST_FAILURE_TASK	VARCHAR2(32)	Task being run at the time of the last failure
LAST_FAILURE_TASKNUM	NUMBER	Unique task number of the failed task
CON_ID	NUMBER	The ID of the container to which the data pertains. The CON_ID value in this view is always 0. The rows pertain to the entire CDB or to the non-CDB.

9.154 V$QMON_TASK_STATS

V$QMON_TASK_STATS displays information and statistics based on different queue monitor tasks in the system (spilling, time manager activity, and so on). There is one row per kind of task. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
TASK_NAME	VARCHAR2(32)	Name of the task
TASK_TYPE	VARCHAR2(40)	Type of the task
LAST_CREATED_TASKNUM	NUMBER	Unique task number last created for this task
NUM_TASKS	NUMBER	Number of tasks currently present
TOTAL_TASK_RUN_TIME	NUMBER	Cumulative task run time
TOTAL_TASK_RUNS	NUMBER	Cumulative task runs
TOTAL_TASK_FAILURES	NUMBER	Cumulative failures
METRIC_TYPE	VARCHAR2(50)	Type of metric gathered for this task type
METRIC_VALUE	NUMBER	Value of this metric
LAST_FAILURE	VARCHAR2(32)	Last failure encountered while executing this type of task
LAST_FAILURE_TIME	TIMESTAMP(3) WITH TIME ZONE	Time when the last failure occurred
LAST_FAILURE_TASKNUM	NUMBER	Task number of the last failed task for this task
REMARK	VARCHAR2(64)	Remarks about the task
CON_ID	NUMBER	The ID of the container to which the data pertains. The CON_ID value in this view is always 0. The rows pertain to the entire CDB or to the non-CDB.

9.155 V$QMON_TASKS

V$QMON_TASKS displays information and statistics about all queue background tasks in the system, which would be served by queue monitor servers. There is one row per task. The rows are deleted when the database (or instance in an Oracle RAC environment) restarts.

Column	Datatype	Description
TASK_NAME	VARCHAR2(32)	Task name
TASK_NUMBER	NUMBER	Unique task number

Column	Datatype	Description
TASK_TYPE	VARCHAR2(40)	Task type
TASK_SUBMIT_TIME	TIMESTAMP(3) WITH TIME ZONE	Task submit time
TASK_READY_TIME	TIMESTAMP(3) WITH TIME ZONE	Task ready time
TASK_EXPIRY_TIME	TIMESTAMP(3) WITH TIME ZONE	Time when this task expires
TASK_START_TIME	TIMESTAMP(3) WITH TIME ZONE	Last actual start time for the task
TASK_STATUS	VARCHAR2(32)	Status of the task
SERVER_NAME	VARCHAR2(48)	Name of the QMON server running this task
MAX_RETRIES	NUMBER	Maximum retry count for the task
NUM_RUNS	NUMBER	Number of runs of the task if repeatable
NUM_FAILURES	NUMBER	Number of failures encountered while running the task
CON_ID	NUMBER	The ID of the container to which the data pertains. The CON_ID value in this view is always 0. The rows pertain to the entire CDB or to the non-CDB.

9.156 V$QUARANTINE

V$QUARANTINE provides information about quarantined objects.

Column	Datatype	Description
OBJECT	VARCHAR2(64)	Type of quarantined object (description of the memory)
ADDRESS	RAW(8)	Address of the object
BYTES	NUMBER	Amount of memory used by the object (this is the minimum amount; the actual amount may be unknown)
ERROR	VARCHAR2(128)	Oracle error causing quarantine
TIMESTAMP	TIMESTAMP(6) WITH TIME ZONE	Time the object was quarantined
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.157 V$QUARANTINE_SUMMARY

V$QUARANTINE_SUMMARY provides a summary of quarantine for each pluggable database (PDB).

Column	Datatype	Description
OBJECT_COUNT	NUMBER	Number of objects in quarantine
OBJECT_LIMIT	NUMBER	Limit on the number of objects that can be in quarantine before a termination will occur
MEMORY_TOTAL	NUMBER	Number of bytes in quarantine
MEMORY_LIMIT	NUMBER	Limit on the amount of memory that can be in quarantine before a termination will occur
RECENT_COUNT	NUMBER	Number of objects recently placed in quarantine (within the last hour)
RECENT_LIMIT	NUMBER	Limit on the number of recently quarantined objects before a termination will occur
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$QUARANTINE" for additional details on objects recently placed into quarantine

9.158 V$QUEUE

V$QUEUE contains information on the shared server message queues.

Column	Datatype	Description
PADDR	RAW(4 | 8)	Address of the process that owns the queue
TYPE	VARCHAR2(10)	Type of queue: • COMMON - Processed by servers • DISPATCHER
QUEUED	NUMBER	Number of items in the queue
WAIT	NUMBER	Total time that all items in this queue have waited (in hundredths of a second). Divide by TOTALQ for average wait per item.
TOTALQ	NUMBER	Total number of items that have ever been in the queue
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.159 V$QUEUEING_MTH

V$QUEUEING_MTH displays all available queuing resource allocation methods.

Column	Datatype	Description
NAME	VARCHAR2(40)	Name of the queuing resource allocation method
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.160 V$RECOVER_FILE

V$RECOVER_FILE displays the status of files needing media recovery.

Column	Datatype	Description
FILE#	NUMBER	File identifier number
ONLINE	VARCHAR2(7)	This column is obsolete and maintained for backward compatibility. The value of this column is always equal to the value in ONLINE_STATUS.
ONLINE_STATUS	VARCHAR2(7)	Online status (ONLINE, OFFLINE)
ERROR	VARCHAR2(18)	Why the file must be recovered: NULL if reason unknown, or OFFLINE NORMAL if recovery not needed
CHANGE#	NUMBER	SCN where recovery must start
TIME	DATE	Time of SCN when recovery must start
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.161 V$RECOVERY_AREA_USAGE

V$RECOVERY_AREA_USAGE displays usage information about recovery areas.

Column	Datatype	Description
FILE_TYPE	VARCHAR2(23)	File type: • CONTROL FILE • REDO LOG • ARCHIVED LOG • BACKUP PIECE • IMAGE COPY • FLASHBACK LOG • REMOTE ARCHIVED LOG
PERCENT_SPACE_USED	NUMBER	Percent of the recovery area that is in use
PERCENT_SPACE_RECLAIMABLE	NUMBER	Percent of the recovery area that is reclaimable
NUMBER_OF_FILES	NUMBER	Number of files in the recovery area
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.162 V$RECOVERY_FILE_DEST

V$RECOVERY_FILE_DEST displays information about the disk quota and current disk usage in the fast recovery area.

Column	Datatype	Description
NAME	VARCHAR2(513)	Location name. This is the value specified in the DB_RECOVERY_FILE_DEST initialization parameter.
SPACE_LIMIT	NUMBER	Maximum amount of disk space (in bytes) that the database can use for the fast recovery area. This is the value specified in the DB_RECOVERY_FILE_DEST_SIZE initialization parameter.
SPACE_USED	NUMBER	Amount of disk space (in bytes) used by fast recovery area files created in current and all previous fast recovery areas. Changing fast recovery areas does not reset SPACE_USED to 0.
SPACE_RECLAIMABLE	NUMBER	Total amount of disk space (in bytes) that can be created by deleting obsolete, redundant, and other low priority files from the fast recovery area
NUMBER_OF_FILES	NUMBER	Number of files in the fast recovery area
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> - "DB_RECOVERY_FILE_DEST"
> - "DB_RECOVERY_FILE_DEST_SIZE"

9.163 V$RECOVERY_FILE_STATUS

V$RECOVERY_FILE_STATUS contains one row for each datafile for each RECOVER statement. This view contains useful information only for the Oracle process doing the recovery. When Recovery Manager directs a server process to perform recovery, only Recovery Manager can view the relevant information in this view. V$RECOVERY_FILE_STATUS will be empty to all other Oracle users.

Column	Datatype	Description
FILENUM	NUMBER	Number of the file being recovered
FILENAME	VARCHAR2(513)	Filename of the datafile being recovered
STATUS	VARCHAR2(13)	Status of the recovery: • IN RECOVERY • CURRENT • NOT RECOVERED
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Backup and Recovery User's Guide*

9.164 V$RECOVERY_LOG

V$RECOVERY_LOG lists information about archived logs that are needed to complete media recovery. This information is derived from the log history view, V$LOG_HISTORY.

V$RECOVERY_LOG contains useful information only for the Oracle process doing the recovery. When Recovery Manager directs a server process to perform recovery, only Recovery Manager can view the relevant information in this view. V$RECOVERY_LOG will be empty to all other Oracle users.

Column	Datatype	Description
THREAD#	NUMBER	Thread number of the archived log
SEQUENCE#	NUMBER	Sequence number of the archived log
TIME	DATE	Time of the first entry (lowest SCN) in the log
ARCHIVE_NAME	VARCHAR2(513)	Name of the file when archived, using the naming convention specified by the LOG_ARCHIVE_FORMAT initialization parameter **See Also:** "LOG_ARCHIVE_FORMAT"
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$LOG_HISTORY" and *Oracle Database Backup and Recovery User's Guide*

9.165 V$RECOVERY_PROGRESS

V$RECOVERY_PROGRESS can be used to track database recovery operations to ensure that they are not stalled, and also to estimate the time required to complete the operation in progress.

On non-coordinator instances, V$RECOVERY_PROGRESS is not populated.

On the coordinator instance (the instance where MRP0 was started to start recovery), V$RECOVERY_PROGRESS has the same set of rows as before, except the following rows in the ITEM column are always 0 (not used) with Multi-Instance Redo Apply:

- Active Apply
- Maximum Apply Rate
- Apply Time per Log
- Checkpoint Time per Log
- Recovery ID

V$RECOVERY_PROGRESS is a subview of V$SESSION_LONGOPS.

> **Note:**
>
> This view is populated on the instance where the MRP0 process is started if recovery is running in Multi-Instance Redo Apply mode. Not all the columns will be populated.

Column	Datatype	Description
START_TIME	DATE	Start time of the recovery operation
TYPE	VARCHAR2(64)	Type of recovery operation being performed: • CRASH RECOVERY • INSTANCE RECOVERY • MEDIA RECOVERY
ITEM	VARCHAR2(32)	Item being measured. When TYPE is CRASH RECOVERY or INSTANCE RECOVERY, the possible values are: • Log Files • Redo Blocks When TYPE is MEDIA RECOVERY, the possible values are: • Active Apply Rate • Average Apply Rate • Maximum Apply Rate • Redo Applied • Log Files • Last Applied Redo • Active Time • Elapsed Time • Apply Time per Log • Checkpoint Time per Log • Standby Apply Lag • Recovery ID
UNITS	VARCHAR2(32)	The units of measurement for each item
SOFAR	NUMBER	Amount of work done so far
TOTAL	NUMBER	Total amount of work expected
TIMESTAMP	DATE	Timestamp of the last redo record applied
COMMENTS	VARCHAR2(248)	Miscellaneous notes; currently displays the SCN for the last applied redo
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SESSION_LONGOPS"
- "Background Processes" for more information about the MRP0 process
- *Oracle Database Backup and Recovery User's Guide* for more information about performing database recovery

9.166 V$RECOVERY_SLAVE

V$RECOVERY_SLAVE is used to track database media recovery processes to monitor their performance statistics and analyze a media recovery session.

> **Note:**
>
> This view is deprecated. Oracle recommends that you instead use the V$RECOVERY_WORKER view.

> **See Also:**
>
> "V$RECOVERY_WORKER"

9.167 V$RECOVERY_STATUS

V$RECOVERY_STATUS contains statistics of the current recovery process. This view contains useful information only for the Oracle process doing the recovery. When Recovery Manager directs a server process to perform recovery, only Recovery Manager can view the relevant information in this view. V$RECOVERY_STATUS will be empty to all other Oracle users.

Column	Datatype	Description
RECOVERY_CHECKPOINT	DATE	Point in time to which the recovery has occurred. If no logs have been applied, this is the point in time the recovery starts.
THREAD	NUMBER	Number of the redo thread currently being processed
SEQUENCE_NEEDED	NUMBER	Log sequence number of the log needed by the recovery process. The value is 0 if no log is needed.
SCN_NEEDED	VARCHAR2(16)	Low SCN of the log needed by recovery. The value is 0 if unknown or no log is needed.
TIME_NEEDED	DATE	Time when the log was created. The value is midnight on 1/1/88 if the time is unknown or if no log is needed.
PREVIOUS_LOG_NAME	VARCHAR2(513)	Filename of the log
PREVIOUS_LOG_STATUS	VARCHAR2(13)	Status of the previous log. Contains one of the following values: RELEASE; WRONG NAME; MISSING NAME; UNNEEDED NAME; NONE
REASON	VARCHAR2(13)	Reason recovery is returning control to the user (NEED LOG|LOG REUSED|THREAD DISABLED)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Backup and Recovery User's Guide*

9.168 V$RECOVERY_WORKER

V$RECOVERY_WORKER is used to track database media recovery processes to monitor their performance statistics and analyze a media recovery session.

Column	Datatype	Description
START_TIME	DATE	Start time of the recovery process
TYPE	VARCHAR2(64)	Type of recovery process being performed: • Media Recovery Applier # (where # represents the worker ID number) • Media Recovery Log Merger • Serial Media Recovery

Column	Datatype	Description
ITEM	VARCHAR2(32)	Item being measured. When TYPE is Media Recovery Applier #, the possible values are: • Recovery ID • Process ID • Number of Redo Cache Full • Number of Redo Cache Copy • Number of CV Cached • CV Applied OK • CV Applied Stuck • CV Applied Repair • CV Applied Corrupt • CV Applied Ckpt • CV Applied Reapplied • Total CV Processed Size • Total CV Applied • Number of Buffer Cache Full • Number of Buffer Retries • Number of Max Reads Issued • Number of Unrcv Condition • Number of Influx Buffer Flushed • Number of Reap Request • Number of Reap Wait IO • Number of Reap No Buffer • Number of Wait All Read • Number of Buffer Pinged • Buffer Ping Time • Read Issue Time • Number of Read Request Issued When TYPE is Media Recovery Log Merger, the possible values are: • Recovery ID • Process ID • Number of Redo Cache Full • Number of Redo Cache Copy • Number of CV Cached • Total Redo Read Bytes • Total CV Parsed When TYPE is Serial Media Recovery, the possible values include values from the other two TYPEs.
UNITS	VARCHAR2(32)	The units of measurement for each item
SOFAR	NUMBER	Amount of work done so far
TOTAL	NUMBER	Total amount of work expected
COMMENTS	VARCHAR2(248)	Miscellaneous notes, which may display the recovery ID and process ID for current recovery session

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

This view is available starting with Oracle Database 23ai.

See Also:

Oracle Database Backup and Recovery User's Guide

9.169 V$REDO_DEST_RESP_HISTOGRAM

V$REDO_DEST_RESP_HISTOGRAM provides statistical information for each redo transport destination.

Column	Datatype	Description
DEST_ID	NUMBER	A nonnegative integer value representing a SYNC standby destination
TIME	VARCHAR2(20)	A text string that shows the last wall-clock time that a bucket was hit
DURATION	NUMBER	A positive integer value that represents a bucket of seconds, 1, 2, 3, up to 300 seconds, followed by 5 additional buckets that represent 600, 1200, 2400, 4800, and 9600 (>= 4801) seconds
FREQUENCY	NUMBER	A nonnegative integer that shows the number of times a particular bucket was hit by the destination specified by DEST_ID
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.170 V$REQDIST

V$REQDIST lists statistics for the histogram of shared server dispatcher request times, divided into 12 buckets, or ranges of time. The time ranges grow exponentially as a function of the bucket number.

Column	Datatype	Description
BUCKET	NUMBER	Bucket number: 0 - 11; the maximum time for each bucket is (4 * 2^N)/100 seconds
COUNT	NUMBER	Count of requests whose total time to complete (excluding wait time) falls in this range
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.171 V$RESERVED_WORDS

V$RESERVED_WORDS displays a list of all SQL keywords. To determine whether a particular keyword is reserved in any way, check the RESERVED, RES_TYPE, RES_ATTR, and RES_SEMI columns.

Column	Datatype	Description
KEYWORD	VARCHAR2(128)	Name of the keyword
LENGTH	NUMBER	Length of the keyword
RESERVED	VARCHAR2(1)	Indicates whether the keyword cannot be used as an identifier (Y) or whether the keyword is not reserved (N)
RES_TYPE	VARCHAR2(1)	Indicates whether the keyword cannot be used as a type name (Y) or whether the keyword is not reserved (N)
RES_ATTR	VARCHAR2(1)	Indicates whether the keyword cannot be used as an attribute name (Y) or whether the keyword is not reserved (N)
RES_SEMI	VARCHAR2(1)	Indicates whether the keyword is not allowed as an identifier in certain situations, such as in DML (Y) or whether the keyword is not reserved (N)
DUPLICATE	VARCHAR2(1)	Indicates whether the keyword is a duplicate of another keyword (Y) or whether the keyword is not a duplicate (N)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.172 V$RESOURCE

V$RESOURCE contains resource name and address information.

Column	Datatype	Description
ADDR	RAW(4 | 8)	Address of the resource object
TYPE	VARCHAR2(2)	Resource type; the resource types are listed in Table 9-1
ID1	NUMBER	Resource identifier #1
ID2	NUMBER	Resource identifier #2
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.173 V$RESOURCE_LIMIT

V$RESOURCE_LIMIT displays information about global resource use for some of the system resources. Use this view to monitor the consumption of resources so that you can take corrective action, if necessary. Many of the resources correspond to initialization parameters listed in Table 9-5.
Some resources, those used by DLM for example, have an initial allocation (soft limit), and the hard limit, which is theoretically infinite (although in practice it is limited by SGA size). During SGA reservation/initialization, a place is reserved in SGA for the INITIAL_ALLOCATION of resources, but if this allocation is exceeded, additional resources are allocated up to the value indicated by LIMIT_VALUE. The CURRENT_UTILIZATION column indicates whether the initial allocation has been exceeded. When the initial allocation value is exceeded, the additional required resources are allocated from the shared pool, where they must compete for space with other resources.

A good choice for the value of INITIAL_ALLOCATION will avoid the contention for space. For most resources, the value for INITIAL_ALLOCATION is the same as the LIMIT_VALUE. Exceeding LIMIT_VALUE results in an error.

Column	Datatype	Description
RESOURCE_NAME	VARCHAR2(128)	Name of the resource (see Table 9-5)
CURRENT_UTILIZATION	NUMBER	Number of (resources, locks, or processes) currently being used
MAX_UTILIZATION	NUMBER	Maximum consumption of this resource since the last instance start-up
INITIAL_ALLOCATION	VARCHAR2(40)	Initial allocation. This will be equal to the value specified for the resource in the initialization parameter file (UNLIMITED for infinite allocation).
LIMIT_VALUE	VARCHAR2(40)	Unlimited for resources and locks. This can be greater than the initial allocation value (UNLIMITED for infinite limit).

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Table 9-5 Values for the RESOURCE_NAME Column

Resource Name	Corresponds to
DML_LOCKS	See "DML_LOCKS"
ENQUEUE_LOCKS	This value is computed by the Oracle Database. See V$ENQUEUE_LOCK to obtain more information about the enqueue locks.
GES_LOCKS	Global Enqueue Service locks
GES_PROCS	Global Enqueue Service processes
GES_RESS	Global Enqueue Service resources
MAX_SHARED_SERVERS	See "MAX_SHARED_SERVERS"
PARALLEL_MAX_SERVERS	See "PARALLEL_MAX_SERVERS"
PROCESSES	See "PROCESSES"
SESSIONS	See "SESSIONS"
SORT_SEGMENT_LOCKS	This value is computed by the Oracle Database
TEMPORARY_LOCKS	This value is computed by the Oracle Database
TRANSACTIONS	See "TRANSACTIONS"

9.174 V$RESTORE_POINT

V$RESTORE_POINT displays information about restore points.

Column	Datatype	Description
SCN	NUMBER	Database SCN when the restore point was created
DATABASE_INCARNATION#	NUMBER	Database incarnation number when the restore point was created
GUARANTEE_FLASHBACK_DATABASE	VARCHAR2(3)	Indicates whether flashback log files will be kept to ensure a flashback to this point (YES) or not (NO)
STORAGE_SIZE	NUMBER	Approximate number of bytes of disk space currently tied up supporting this restore point, and which would no longer be tied up if this restore point is the oldest restore point and it is dropped. This will always be zero for non-guaranteed restore points.
TIME	TIMESTAMP(9)	Wall-clock time when the restore point was created
RESTORE_POINT_TIME	TIMESTAMP(9)	Time that was specified when the restore point was created. If a time was not specified, this value is NULL.

Column	Datatype	Description
PRESERVED	VARCHAR2(3)	Indicates whether the restore point must be explicitly deleted (YES) or not (NO)
NAME	VARCHAR2(128)	Name of the restore point
PDB_RESTORE_POINT	VARCHAR2(3)	Indicates whether there is a PDB restore point for this PDB (YES) or not (NO)
CLEAN_PDB_RESTORE_POINT	VARCHAR2(3)	Indicates whether there is a clean PDB restore point for this PDB (YES) or not (NO)
PDB_INCARNATION#	NUMBER	Pluggable database (PDB) incarnation number. This value is meaningful only for PDB restore points.
REPLICATED	VARCHAR2(3)	This column is useful in Oracle Data Guard environments. It indicates the method by which a restore point was created. Possible values: • YES - The restore point was automatically replicated from the primary database to this database when this database was a standby database. The string _PRIMARY is appended to the name of such a restore point. • NO - The restore point was created by a user and was not replicated from the primary database.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.175 V$RESULT_CACHE_DEPENDENCY

V$RESULT_CACHE_DEPENDENCY displays the depends-on relationship between cached results and dependencies.

Column	Datatype	Description
RESULT_ID	NUMBER	Cached result
DEPEND_ID	NUMBER	Dependency object
OBJECT_NO	NUMBER	Dictionary object number of the dependency object
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.176 V$RESULT_CACHE_MEMORY

V$RESULT_CACHE_MEMORY displays all the memory blocks and their status.

Column	Datatype	Description
ID	NUMBER	Unique block identifier (that is, the block number)
CHUNK	NUMBER	Chunk to which the block belongs, relative to the subcache in which the memory object resides (the upper 27 bits of the ID)
OFFSET	NUMBER	Offset of the block within its chunk, relative to the subcache in which the memory object resides (the lower 5 bits of the ID)
SUBCACHE_ID	NUMBER	Subcache ID
FREE	VARCHAR2(3)	Indicates whether the block is free (YES) or not (NO)
OBJECT_ID	NUMBER	Cache object to which the memory block belongs; NULL if the memory block is not allocated to a cache object (FREE = YES)
POSITION	NUMBER	Position of the block in the cached object; NULL if the memory block is not allocated to a cache object (FREE = YES)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.177 V$RESULT_CACHE_OBJECTS

V$RESULT_CACHE_OBJECTS displays all the objects (both cached results and dependencies) and their attributes.

Column	Datatype	Description
ID	NUMBER	Identifier for the cache object (also the ID of the first block)
TYPE	VARCHAR2(10)	Type of the cache object: • Dependency • Result • Temp
STATUS	VARCHAR2(9)	Status of the object: • New - Result is still under construction • Published - Result is available for use • Bypass - Result will be bypassed from use • Expired - Result has exceeded expiration time • Invalid - Result is no longer available for use
BUCKET_NO	NUMBER	Internal hash bucket for the object
HASH	NUMBER	Hash value for the object
NAME	VARCHAR2(387)	Name (for example, SQL prefix or PL/SQL function name)

Column	Datatype	Description
NAMESPACE	VARCHAR2(10)	Namespace: • SQL • PLSQL • KEY VECTOR
CREATION_TIMESTAMP	DATE	Time when the object was created
CREATOR_UID	NUMBER	UID that created the object
DEPEND_COUNT	NUMBER	Number of dependencies (TYPE = Result) or dependents (TYPE = Dependency)
BLOCK_COUNT	NUMBER	Total number of blocks in the cached object
SCN	NUMBER	Build SCN (TYPE = Result) or invalidation SCN (TYPE = Dependency)
COLUMN_COUNT[1]	NUMBER	Number of columns in the cached result
PIN_COUNT[1]	NUMBER	Number of active scans on this result
SCAN_COUNT[1]	NUMBER	Total number of scans initiated on the cached result
ROW_COUNT[1]	NUMBER	Total number of rows in the cached result
ROW_SIZE_MAX[1]	NUMBER	Size of the largest row (in bytes)
ROW_SIZE_MIN[1]	NUMBER	Size of the smallest row (in bytes)
ROW_SIZE_AVG[1]	NUMBER	Average size of a row (in bytes)
BUILD_TIME[1]	NUMBER	Amount of time (in hundredths of a second) it took to build the cached result
LRU_NUMBER[1]	NUMBER	LRU list position (the larger the value, the more recent the usage)
OBJECT_NO[2]	NUMBER	Dictionary object number of the dependency object
INVALIDATIONS[2]	NUMBER	Number of times the object has invalidated its dependents
TIME_SAVED	NUMBER	Amount of time (in microseconds) saved by reuse
INVALIDATION_COST	NUMBER	Amount of time (in microseconds) spent on invalidation
SPACE_OVERHEAD[1]	NUMBER	Overhead (in bytes) for the result
SPACE_UNUSED[1]	NUMBER	Unused space (in bytes) for the result
CACHE_ID	VARCHAR2(387)	CacheId for the result (object name if it's a dependency)
CACHE_KEY	VARCHAR2(387)	CacheKey for the result (object name if it's a dependency)
CHECKSUM	NUMBER	Checksum for the result object. The checksum is computed over all the blocks in the result cache object minus the object header.
EDITION_ID	NUMBER	Shows the edition's object ID that was in use when the result was calculated
DB_LINK	VARCHAR2(3)	Possible values: • YES: The result cache object references a remote database object • NO: The result cache object does not reference a remote database object

Column	Datatype	Description
GLOBAL	VARCHAR2(3)	Possible values: • YES: The object was fetched from the result cache of a remote database instance • NO: The object was recomputed on this instance, either because it was not available on a remote database instance or because the system deemed it was inefficient to fetch the object from a remote database instance
SUBCACHE_ID	NUMBER	Subcache ID
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

1 This column is valid only for TYPE = Result; otherwise, its value is NULL.

2 This column is valid only for TYPE = Dependency; otherwise, its value is NULL.

9.178 V$RESULT_CACHE_STATISTICS

V$RESULT_CACHE_STATISTICS displays various result cache settings and usage statistics.

Column	Datatype	Description
ID	NUMBER	Statistic number
NAME	VARCHAR2(128)	Name of the statistic (see Table 9-6)
VALUE	VARCHAR2(81)	Value of the statistic
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Table 9-6 V$RESULT_CACHE_STATISTICS and V$RESULT_SUBCACHE_STATISTICS Statistics

Statistic Name	Description
Block Count Current	Number of memory blocks currently allocated
Block Count Maximum	Maximum number of memory blocks allowed
Block Size (Bytes)	Size of each memory block
Create Count Failure	Number of cache results that failed to create
Create Count Success	Number of cache results successfully created
Delete Count Invalid	Number of invalid cached results deleted

Table 9-6 (Cont.) V$RESULT_CACHE_STATISTICS and V$RESULT_SUBCACHE_STATISTICS Statistics

Statistic Name	Description
Delete Count Valid	Number of valid cached results deleted
Find Copy Count	Number of results copied directly out of the cache
Find Count	Number of cached results that were successfully found
Global Load Rate	Rate at which cached results were fetched from remote instances (in bytes per 10 milliseconds)
Global Prune By Self Count	Number of times this instance did not provide a cached result to a remote instance because this instance deemed it inefficient to do so
Global Prune Count	Number of times this instance did not fetch a cached result from a remote instance because it was deemed inefficient to do so
Hash Chain Length	Average length of items in the hash chain
Invalidation Count	Total number of invalidations
Result Size Maximum (Blocks)	Maximum number of blocks allowed for a single result
Subcache Count	Number of subcaches in the result cache

> **See Also:**
>
> "V$RESULT_SUBCACHE_STATISTICS"

9.179 V$RESULT_SUBCACHE_STATISTICS

`V$RESULT_SUBCACHE_STATISTICS` displays various result cache settings and usage statistics on a per subcache basis.

Column	Datatype	Description
`ID`	`NUMBER`	Statistic number
`NAME`	`VARCHAR2(128)`	Name of the statistic This view displays the same statistics as the `V$RESULT_CACHE_STATISTICS` view. See Table 9-6 in the documentation for V$RESULT_CACHE_STATISTICS.
`VALUE`	`VARCHAR2(81)`	Value of the statistic
`SUBCACHE_ID`	`NUMBER`	Subcache ID
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$RESULT_CACHE_STATISTICS"

9.180 V$RMAN_BACKUP_JOB_DETAILS

V$RMAN_BACKUP_JOB_DETAILS displays details about backup jobs.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Together, with SESSION_KEY and SESSION_STAMP, used to uniquely identify job output from V$RMAN_OUTPUT
SESSION_STAMP	NUMBER	Together, with SESSION_KEY and SESSION_RECID, used to uniquely identify job output from V$RMAN_OUTPUT
COMMAND_ID	VARCHAR2(33)	Either a user-specified SET COMMAND ID or a unique command ID generated by RMAN
START_TIME	DATE	Start time of the first BACKUP command in the job
END_TIME	DATE	End time of the last BACKUP command in the job
INPUT_BYTES	NUMBER	Sum of all input file sizes backed up by this job
OUTPUT_BYTES	NUMBER	Output size of all pieces generated by this job
STATUS_WEIGHT	NUMBER	Used internally by Enterprise Manager
OPTIMIZED_WEIGHT	NUMBER	Used internally by Enterprise Manager
OBJECT_TYPE_WEIGHT	NUMBER	Used internally by Enterprise Manager
OUTPUT_DEVICE_TYPE	VARCHAR2(17)	Can be DISK, SBT, or *. An * indicates more than one device (in most cases, it will be DISK or SBT).
AUTOBACKUP_COUNT	NUMBER	Number of autobackups performed by this job
BACKED_BY_OSB	VARCHAR2(3)	A value of YES means the backup was done to Oracle Secure Backup. Otherwise, backed up by other third party tape library.
AUTOBACKUP_DONE	VARCHAR2(3)	YES or NO, depending upon whether or not a control file autobackup was done as part of this backup job
STATUS	VARCHAR2(23)	One of the following values: • RUNNING WITH WARNINGS • RUNNING WITH ERRORS • COMPLETED • COMPLETED WITH WARNINGS • COMPLETED WITH ERRORS • FAILED

Column	Datatype	Description
INPUT_TYPE	VARCHAR2(13)	Contains one of the following values. If the user command does not satisfy one of them, then preference is given in order, from top to bottom of the list. • DB FULL • RECVR AREA • DB INCR • DATAFILE FULL • DATAFILE INCR • ARCHIVELOG • CONTROLFILE • SPFILE
OPTIMIZED	VARCHAR2(3)	YES or NO, depending on whether optimization was applied. Applicable to backup jobs only.
ELAPSED_SECONDS	NUMBER	Number of elapsed seconds
COMPRESSION_RATIO	NUMBER	Compression ratio
INPUT_BYTES_PER_SEC	NUMBER	Input read-rate-per-second
OUTPUT_BYTES_PER_SEC	NUMBER	Output write-rate-per-second
INPUT_BYTES_DISPLAY	VARCHAR2(4000)	Values in user-displayable form. They will be converted to a format of nM, nG, nT, nP, and so on.
OUTPUT_BYTES_DISPLAY	VARCHAR2(4000)	Values in user-displayable form. They will be converted to a format of nM, nG, nT, nP, and so on
INPUT_BYTES_PER_SEC_DISPLAY	VARCHAR2(4000)	Input read-rate-per-second. These values are in user-displayable form. They will be converted to a format of nM, nG, nT, nP, and so on.
OUTPUT_BYTES_PER_SEC_DISPLAY	VARCHAR2(4000)	Output write-rate-per-second. These values are in user-displayable form. They will be converted to a format of nM, nG, nT, nP, and so on.
TIME_TAKEN_DISPLAY	VARCHAR2(4000)	Time taken, shown in user-displayable format <nn>h:<nn>m:<nn>s
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.181 V$RMAN_BACKUP_SUBJOB_DETAILS

V$RMAN_BACKUP_SUBJOB_DETAILS merges similar operations within an RMAN session into a single row. For example, if there are four BACKUP DATAFILE <n> commands, three RECOVERY COPY OF DATAFILE commands, and one BACKUP RECOVERY AREA command, this view will contain three rows - one each for BACKUP, ROLLFORWARD, and COPY_DISK_TO_TAPE operation.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Together with SESSION_KEY and SESSION_STAMP, used to uniquely identify job output from V$RMAN_OUTPUT
SESSION_STAMP	NUMBER	Together with SESSION_KEY and SESSION_RECID, used to uniquely identify job output from V$RMAN_OUTPUT
OPERATION	VARCHAR2(33)	Can be BACKUP, ROLLFORWARD, VALIDATE, or COPY_DISK_TO_TAPE. A row for each suboperation type for the session will be in the output view.
COMMAND_ID	VARCHAR2(33)	Either a user-specified SET COMMAND ID or a unique command ID generated by RMAN
START_TIME	DATE	Start time of the first BACKUP command in the job
END_TIME	DATE	End time of the last BACKUP command in the job
INPUT_BYTES	NUMBER	Sum of all input file sizes backed up by this job
OUTPUT_BYTES	NUMBER	Output size of all pieces generated by this job
STATUS_WEIGHT	NUMBER	Used internally by Enterprise Manager
OBJECT_TYPE_WEIGHT	NUMBER	Used internally by Enterprise Manager
OPTIMIZED_WEIGHT	NUMBER	Used internally by Enterprise Manager
OUTPUT_DEVICE_TYPE	VARCHAR2(17)	Can be DISK, SBT, or *. An * indicates more than one device (in most cases, it will be DISK or SBT).
BACKED_BY_OSB	VARCHAR2(3)	A value of YES means the backup was done to Oracle Secure Backup. Otherwise, backed up by other third party tape library.
AUTOBACKUP_DONE	VARCHAR2(3)	YES or NO, depending upon whether or not a control file autobackup was done as part of this job
STATUS	VARCHAR2(23)	One of the following values: • RUNNING WITH WARNINGS • RUNNING WITH ERRORS • COMPLETED • COMPLETED WITH WARNINGS • COMPLETED WITH ERRORS • FAILED
INPUT_TYPE	VARCHAR2(13)	Contains one of the following values. If the user command does not satisfy one of them, then preference is given in order, from top to bottom of the list. • DB FULL • RECVR AREA • DB INCR • DATAFILE FULL • DATAFILE INCR • ARCHIVELOG • CONTROLFILE • SPFILE
OPTIMIZED	VARCHAR2(3)	YES or NO, depending on whether optimization was applied. Applicable to backup jobs only.
AUTOBACKUP_COUNT	NUMBER	Number of autobackups performed by this job
COMPRESSION_RATIO	NUMBER	Compression ratio

Column	Datatype	Description
INPUT_BYTES_DISPLAY	VARCHAR2(4000)	Values in user-displayable form. They will be converted to a format of nM, nG, nT, nP, and so on.
OUTPUT_BYTES_DISPLAY	VARCHAR2(4000)	Values in user-displayable form. They will be converted to a format of nM, nG, nT, nP, and so on.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.182 V$RMAN_BACKUP_TYPE

V$RMAN_BACKUP_TYPE displays information about RMAN backup types.

Column	Datatype	Description
WEIGHT	NUMBER	Used to set precedence order of different backup types in reports.
INPUT_TYPE	VARCHAR2(13)	Used to represent possible filters used in creating various reporting screens.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.183 V$RMAN_COMPRESSION_ALGORITHM

V$RMAN_COMPRESSION_ALGORITHM provides descriptions of supported compression algorithms. It is used by the RMAN client.

Column	Datatype	Description
ALGORITHM_ID	NUMBER	Algorithm ID
ALGORITHM_NAME	VARCHAR2(64)	Name of the algorithm (for example, LOW, MEDIUM, DEFAULT, or HIGH)
INITIAL_RELEASE	VARCHAR2(18)	First Oracle Database release when this compression algorithm was available
TERMINAL_RELEASE	VARCHAR2(18)	Last Oracle Database release that supported using this compression algorithm to create new backups. Existing backups can always be restored, even if they use a deprecated compression algorithm.
ALGORITHM_DESCRIPTION	VARCHAR2(64)	Description of the algorithm

Column	Datatype	Description
ALGORITHM_COMPATIBILITY	VARCHAR2(18)	Required database compatibility level for the algorithm (for example, 11.2.0 for DEFAULT)
IS_VALID	VARCHAR2(3)	Indicates whether the algorithm is valid with regard to the compatibility setting (YES) or not (NO). The value is YES if ALGORITHM_COMPATIBILITY <= DATABASE_COMPATIBILITY.
REQUIRES_ACO	VARCHAR2(3)	Indicates whether the algorithm requires the Advanced Compression Option (YES) or not (NO)
IS_DEFAULT	VARCHAR2(3)	Indicates whether the algorithm is the default compression algorithm that RMAN uses to create compressed backup sets (YES) or not (NO)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.184 V$RMAN_CONFIGURATION

V$RMAN_CONFIGURATION lists information about RMAN persistent configuration settings.

Column	Datatype	Description
CONF#	NUMBER	A unique key identifying this configuration record within the target database that owns it.
NAME	VARCHAR2(65)	The type of configuration. All options of the CONFIGURE command are valid types except: • CONFIGURE EXCLUDE (described in RC_TABLESPACE) • CONFIGURE AUXNAME (described in RC_DATAFILE) • CONFIGURE SNAPSHOT CONTROLFILE (stored only in control file)
VALUE	VARCHAR2(1025)	The CONFIGURE command setting. Example: RETENTION POLICY TO RECOVERY WINDOW OF 10 DAYS
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.185 V$RMAN_ENCRYPTION_ALGORITHMS

V$RMAN_ENCRYPTION_ALGORITHMS displays supported encryption algorithms. It is used by the RMAN client to validate user-requested algorithms.

This view lists AES128, AES192, and AES256 encryption algorithms for the current release. The default algorithm is AES256.

Column	Datatype	Description
ALGORITHM_ID	NUMBER	Number to identify the algorithm
ALGORITHM_NAME	VARCHAR2(64)	Name of the algorithm (for example, AES128, AES192, or AES256)
ALGORITHM_DESCRIPTION	VARCHAR2(64)	Description of the algorithm
IS_DEFAULT	VARCHAR2(3)	Indicates whether this is the default encryption algorithm for CFB encryption mode (YES) or not (NO). CFB encryption mode is used when the COMPATIBLE initialization parameter is set to a value less than 23.0.0.0. Otherwise, refer to the IS_DEFAULTXTS column. This value is set by Oracle Database and may vary for each Release (that is, it is not dependent on user-specified RMAN configuration).
RESTORE_ONLY	VARCHAR2(3)	Indicates whether this algorithm can be used for restore only (YES) or not (NO). If the value is NO, then the algorithm is also allowed for backup. This column is useful in determining whether an encryption algorithm is deprecated for backup purpose.
IS_DEFAULTXTS	VARCHAR2(3)	Indicates whether this is the default encryption algorithm for XTS encryption mode (YES) or not (NO). XTS encryption mode is used when the COMPATIBLE initialization parameter is set to a value greater than or equal to 23.0.0.0. Otherwise, refer to the IS_DEFAULT column. This value is set by Oracle Database and may vary for each Release (that is, it is not dependent on user-specified RMAN configuration).
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.186 V$RMAN_OUTPUT

V$RMAN_OUTPUT displays messages reported by RMAN.

This is an in-memory view and is not recorded in the controlfile. The view can hold 32768 rows.

Column	Datatype	Description
SID	NUMBER	Session ID of the session which is running this RMAN operation
RECID	NUMBER	Record ID of the corresponding V$RMAN_STATUS row
STAMP	NUMBER	Timestamp of the corresponding V$RMAN_STATUS row
SESSION_RECID	NUMBER	Record ID of the session (corresponding V$RMAN_STATUS row with ROW_LEVEL = 0)
SESSION_STAMP	NUMBER	Timestamp of the session (corresponding V$RMAN_STATUS row with ROW_LEVEL = 0)
OUTPUT	VARCHAR2(130)	Output text reported by RMAN
RMAN_STATUS_RECID	NUMBER	Owning V$RMAN_STATUS record ID
RMAN_STATUS_STAMP	NUMBER	Owning V$RMAN_STATUS record stamp
SESSION_KEY	NUMBER	Session identifier
GUID	NUMBER	The guid of the pluggable database (PDB) that did the RMAN operation. V$RMAN_OUTPUT captures the rman output. If a PDB sysdba did the backup, the guid of the PDB is displayed in V$RMAN_OUTPUT. If root did the backup, then guid of the root is displayed in V$RMAN_OUTPUT. Root A root user can see all of V$RMAN_OUTPUT rows (that is, the rows owned by all PDBs), but a PDB user can only see that PDB's V$RMAN_OUTPUT rows (that is, no rows from root or other PDBs).
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.187 V$RMAN_STATUS

V$RMAN_STATUS displays the finished and on-going RMAN jobs. For on-going jobs, this view displays progress and status. The jobs which are in progress are stored only in memory while the finished jobs are stored in the controlfile.

Column	Datatype	Description
SID	NUMBER	Session ID of the session which is running this RMAN operation
RECID	NUMBER	Record ID of the row in the controlfile
STAMP	NUMBER	Timestamp of the row (RECID + STAMP is unique)
PARENT_RECID	NUMBER	Record ID of the parent row of this row (corresponding V$RMAN_STATUS row with ROW_LEVEL = ROW_LEVEL - 1)
PARENT_STAMP	NUMBER	Timestamp of the parent row of this row (corresponding V$RMAN_STATUS row with ROW_LEVEL = ROW_LEVEL - 1)
SESSION_RECID	NUMBER	Record ID of the session (corresponding V$RMAN_STATUS row with ROW_LEVEL = 0)

Column	Datatype	Description
SESSION_STAMP	NUMBER	Timestamp of the session (corresponding V$RMAN_STATUS row with ROW_LEVEL = 0)
ROW_LEVEL	NUMBER	Level of the row. The session has level 0.
ROW_TYPE	VARCHAR2(19)	Type of the row: • SESSION • COMMAND • RECURSIVE OPERATION
COMMAND_ID	VARCHAR2(33)	Command ID set by the RMAN SET COMMAND ID command. If not set, then RMAN will create a unique number.
OPERATION	VARCHAR2(33)	Name of the command in the execution explained by this row
STATUS	VARCHAR2(23)	Status of the operation: • RUNNING • RUNNING WITH WARNINGS • RUNNING WITH ERRORS • COMPLETED • COMPLETED WITH WARNINGS • COMPLETED WITH ERRORS • FAILED
MBYTES_PROCESSED	NUMBER	Percentage of the job completed; null if not applicable for the operation
START_TIME	DATE	Start time of the job
END_TIME	DATE	End time of the job
INPUT_BYTES	NUMBER	Number of input bytes read
OUTPUT_BYTES	NUMBER	Number of output bytes written
OPTIMIZED	VARCHAR2(3)	YES, if backup optimization was applied during the backup job. Otherwise, NO.
OBJECT_TYPE	VARCHAR2(13)	Identifies types of objects backed up
OUTPUT_DEVICE_TYPE	VARCHAR2(17)	DISK, SBT_TAPE, or *. An * indicates that output was written to more than one device type.
OSB_ALLOCATED	VARCHAR2(3)	A value of YES means an Oracle Secure Backup channel was allocated during the specified operation identified by the V$RMAN_STATUS view.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.188 V$RO_USER_ACCOUNT

V$RO_USER_ACCOUNT is populated only on Oracle databases that are open in read-only mode. When a database is read-only, security data cannot be stored in normal

catalogue tables. Instead, the security data is stored in an in-memory table that is queried through this view.
In an Oracle Data Guard environment, some of the security information for user accounts on the standby is inherited from the primary server. For example, if the account is locked out unlimited on the primary, then it will be locked on the standby database(s). The information stored on the standby is volatile information that user actions on the standby database(s) can affect, such as the number of failed logins, and the time the account was locked on the standby due to failed access attempts. Note that failed login attempts on standbys do not affect the account status on primaries.

If this view is queried from the root in a multitenent container database (CDB), then only common users and the `SYS` user are returned.

If this view is queried from a pluggable database (PDB), only rows that pertain to the current PDB are returned.

Column	Datatype	Description
`USERID`	`NUMBER`	User ID number
`PASSW_EXPIRED`	`NUMBER`	Indicates whether the password has expired (`1`) or not (`0`)
`PASSW_IN_GRACE`	`NUMBER`	Indicates whether the account is in grace (`1`) or not (`0`)
`PASSW_LOCKED`	`NUMBER`	Indicates whether the account is locked (`1`) or not (`0`)
`PASSW_LOCK_UNLIM`	`NUMBER`	Indicates whether the account is locked for an unlimited time (`1`) or not (`0`)
`FAILED_LOGINS`	`NUMBER`	The number of failed login attempts. The count is not cumulative; it is reset upon successful logon to the account
`EXPIRATION_AFTER_GRACE`	`TIMESTAMP(3)`	The expiration time after grace
`PASSW_LOCK_TIME`	`TIMESTAMP(3)`	The time the account was locked out
`CON_ID`	`NUMBER`	The ID of the container where the failed login occurred. For users that are not common users, the `CON_ID`is the PDB ID where the failed login attempt occurred. For common users, the `CON_ID` is `0`. The login attempts that occurred on a PDB are not displayed when you query `V$RO_USER_ACCOUNT` from another PDB. You only see the failed login attempts of any users (that are not common users) if those failed login attempts occurred on the same PDB from which you are querying `V$RO_USER_ACCOUNT`. The failed login attempts of common users (and of the `SYS` user) are only displayed when `V$RO_USER_ACCOUNT` is queried from the root of a CDB, not when it is queried from a PDB. In a non-CDB, the value is always `0`.
`USERNAME`	`VARCHAR2(128)`	User name

9.189 V$ROLLNAME

`V$ROLLNAME` lists the names of all online rollback segments. It can only be accessed when the database is open.

Column	Datatype	NULL	Description
`USN`	`NUMBER`		Rollback (undo) segment number

Column	Datatype	NULL	Description
NAME	VARCHAR2(30)	NOT NULL	Rollback segment name
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.190 V$ROLLSTAT

V$ROLLSTAT contains rollback segment statistics.

Column	Datatype	Description
USN	NUMBER	Rollback segment number
LATCH	NUMBER	Latch for the rollback segment
EXTENTS	NUMBER	Number of extents in the rollback segment
RSSIZE	NUMBER	Size (in bytes) of the rollback segment. This value differs by the number of bytes in one database block from the value of the BYTES column of the *_SEGMENTS view. **See Also:** *Oracle Database Administrator's Guide* for more information about space management for rollback segments
WRITES	NUMBER	Number of bytes written to the rollback segment
XACTS	NUMBER	Number of active transactions
GETS	NUMBER	Number of header gets
WAITS	NUMBER	Number of header waits
OPTSIZE	NUMBER	Optimal size of the rollback segment
HWMSIZE	NUMBER	High watermark of the rollback segment size
SHRINKS	NUMBER	Number of times the size of a rollback segment decreases
WRAPS	NUMBER	Number of times rollback segment is wrapped
EXTENDS	NUMBER	Number of times rollback segment size is extended
AVESHRINK	NUMBER	Average shrink size
AVEACTIVE	NUMBER	Current size of active extents, averaged over time.
STATUS	VARCHAR2(15)	Rollback segment status: • ONLINE • PENDING OFFLINE • OFFLINE • FULL
CUREXT	NUMBER	Current extent
CURBLK	NUMBER	Current block

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.191 V$ROWCACHE

V$ROWCACHE displays statistics for data dictionary activity. Each row contains statistics for one data dictionary cache.

Column	Datatype	Description
CACHE#	NUMBER	Row cache ID number
TYPE	VARCHAR2(11)	Parent or subordinate row cache type
SUBORDINATE#	NUMBER	Subordinate set number
PARAMETER	VARCHAR2(32)	Name of the initialization parameter that determines the number of entries in the data dictionary cache
COUNT	NUMBER	Total number of entries in the cache
USAGE	NUMBER	Number of cache entries that contain valid data
FIXED	NUMBER	Number of fixed entries in the cache
GETS	NUMBER	Total number of requests for information on the data object
FASTGETS	NUMBER	Reserved for internal use
GETMISSES	NUMBER	Number of data requests resulting in cache misses
SCANS	NUMBER	Number of scan requests
SCANMISSES	NUMBER	Number of times a scan failed to find the data in the cache
SCANCOMPLETES	NUMBER	For a list of subordinate entries, the number of times the list was scanned completely
MODIFICATIONS	NUMBER	Number of inserts, updates, and deletions
FLUSHES	NUMBER	Number of times flushed to disk
DLM_REQUESTS	NUMBER	Number of DLM requests
DLM_CONFLICTS	NUMBER	Number of DLM conflicts This column is obsolete and is maintained for backward compatibility.
DLM_RELEASES	NUMBER	Number of DLM releases This column is obsolete and is maintained for backward compatibility.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.192 V$ROWCACHE_PARENT

V$ROWCACHE_PARENT displays information for parent objects in the data dictionary. There is one row per lock owner, and one waiter for each object. This row shows the mode held or requested. For objects with no owners or waiters, a single row is displayed.

Column	Datatype	Description
INDX	NUMBER	Index of the row
HASH	NUMBER	Hash value
ADDRESS	RAW(4 | 8)	Address of the parent object
CACHE#	NUMBER	Parent cache ID
CACHE_NAME	VARCHAR2(64)	Parent cache name
EXISTENT	VARCHAR2(1)	Indicates whether the object is an existing object
LOCK_MODE	NUMBER	Mode the lock is held in
LOCK_REQUEST	NUMBER	Mode the lock is requested in
TXN	RAW(4 | 8)	Transaction currently locking the object
SADDR	RAW(4 | 8)	Address of the session
INST_LOCK_REQUEST	NUMBER	Mode in which instance lock is being requested. This column is only relevant for Real Application Clusters.
INST_LOCK_RELEASE	NUMBER	Whether the instance lock needs to be released. This column is only relevant for Real Application Clusters.
INST_LOCK_TYPE	VARCHAR2(2)	Type of instance lock. This column is only relevant for Real Application Clusters.
INST_LOCK_ID1	RAW(4)	ID associated with the instance lock. This column is only relevant for Real Application Clusters.
INST_LOCK_ID2	RAW(4)	ID associated with the instance lock. This column is only relevant for Real Application Clusters.
KEY	RAW(100)	Contents of the key. This column is only relevant for Real Application Clusters.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.193 V$ROWCACHE_SUBORDINATE

V$ROWCACHE_SUBORDINATE displays information for subordinate objects in the data dictionary.

Column	Datatype	Description
INDX	NUMBER	The index
HASH	NUMBER	The hash value
ADDRESS	RAW(4 | 8)	Address of the subordinate object
CACHE#	NUMBER	The parent cache ID
SUBCACHE#	NUMBER	The subcache ID
SUBCACHE_NAME	VARCHAR2(64)	The subcache name
EXISTENT	VARCHAR2(1)	Whether the object is an existing object
PARENT	RAW(4 | 8)	Address of the parent object
KEY	RAW(100)	The contents of the key
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.194 V$RSRC_CONS_GROUP_HISTORY

V$RSRC_CONS_GROUP_HISTORY displays a history of consumer group statistics for each entry in V$RSRC_PLAN_HISTORY that has a non-NULL plan.

When the STATISTICS_LEVEL is set to TYPICAL or ALL, this view contains information about CPU utilization and wait times even when no Resource Manager plan is set or when the Resource Manager plan does not monitor CPU or session resources.

A new window is created in V$RSRC_CON_GROUP_HISTORY when a pluggable database (PDB) changes its resource plan. The plan windows inside a PDB are not impacted by a multitenant container database (CDB) resource plan change.

Since PDB plans can be set independently across different PDBs, V$RSRC_CON_GROUP_HISTORY will not cover the same time period across different PDBs. Therefore, this view is not useful for comparing statistics across different PDBs.

Column	Datatype	Description
SEQUENCE#	NUMBER	A sequential counter that uniquely describes the V$RSRC_PLAN_HISTORY entry to which these consumer group statistics apply. When the instance is restarted, this value is reset to zero.
ID	NUMBER	Consumer group object ID (a unique number, consistent across database shutdowns and startups)
NAME	VARCHAR2(30)	Name of the consumer group
REQUESTS	NUMBER	Cumulative number of requests that were executed in the consumer group
CPU_WAIT_TIME	NUMBER	Cumulative amount of time that sessions waited for CPU on the resmgr: cpu quantum wait event because of resource management (in milliseconds). This does not include waits due to latch or enqueue contention, I/O waits, and so on. When CPU resources are not being actively managed, this value is set to zero.
CPU_WAITS	NUMBER	Cumulative number of times all sessions in the consumer group had to wait for CPU on the resmgr: cpu quantum wait event because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on. When CPU resources are not being actively managed, this value is set to zero.
CONSUMED_CPU_TIME	NUMBER	Cumulative amount of CPU time consumed by all sessions in the consumer group (in milliseconds)
YIELDS	NUMBER	Cumulative number of times that sessions in the consumer group had to yield CPU to other sessions because of quantum expiration. When CPU resources are not being actively managed, this value is set to zero.
CPU_DECISIONS	NUMBER	Percentage of CPU decisions for which the consumer group was present. When CPU resources are not being actively managed, this value is set to zero.
CPU_DECISIONS_EXCLUSIVE	NUMBER	Percentage of the CPU decisions for which the consumer group was present and was the only consumer group present. When CPU resources are not being actively managed, this value is set to zero.
CPU_DECISIONS_WON	NUMBER	Percentage of the CPU decisions that the consumer group won. When CPU resources are not being actively managed, this value is set to zero.
ACTIVE_SESS_LIMIT_HIT	NUMBER	Number of times that sessions in the consumer group were queued because the consumer group reached its active session limit
UNDO_LIMIT_HIT	NUMBER	Number of times that queries in the consumer group were canceled because the consumer group reached its UNDO_POOL limit
SWITCHES_IN_CPU_TIME	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_TIME limit
SWITCHES_OUT_CPU_TIME	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_TIME limit

Column	Datatype	Description
SWITCHES_IN_IO_MEGABYTES	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_MEGABYTES limit
SWITCHES_OUT_IO_MEGABYTES	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_MEGABYTES limit
SWITCHES_IN_IO_REQUESTS	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_REQS limit
SWITCHES_OUT_IO_REQUESTS	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_REQS limit
SWITCHES_IN_IO_LOGICAL	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_LOGICAL limit
SWITCHES_OUT_IO_LOGICAL	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_LOGICAL limit
SWITCHES_IN_ELAPSED_TIME	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_ELAPSED_TIME limit
SWITCHES_OUT_ELAPSED_TIME	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_ELAPSED_TIME limit
SQL_CANCELED	NUMBER	Number of times that SQL queries running in the consumer group were terminated because they exceeded one of the Resource Manager plan's SWITCH limits and CANCEL_SQL was specified as the Resource Manager plan's SWITCH_GROUP
ACTIVE_SESS_KILLED	NUMBER	Number of times that sessions running in the consumer group were terminated because they exceeded one of the Resource Manager plan's SWITCH limits and KILL_SESSION was specified as the Resource Manager plan's SWITCH_GROUP
IDLE_SESS_KILLED	NUMBER	Number of times that sessions in the consumer group were terminated because they were idle for too long (reached MAX_IDLE_TIME)
IDLE_BLKR_SESS_KILLED	NUMBER	Number of times that sessions in the consumer group were terminated because they were idle too long (reached MAX_IDLE_BLOCKER_TIME) and were blocking other sessions
QUEUED_TIME	NUMBER	Total amount of time that sessions in the consumer group have spent in the QUEUED state because of the active session limit (in milliseconds)
QUEUE_TIME_OUTS	NUMBER	Number of times that requests from sessions in the consumer group timed out because they were queued for too long (reached QUEUEING_P1)
IO_SERVICE_TIME	NUMBER	Cumulative I/O wait time (in milliseconds)
IO_SERVICE_WAITS	NUMBER	Total number of wait requests
SMALL_READ_MEGABYTES	NUMBER	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	Number of multiblock megabytes written
SMALL_READ_REQUESTS	NUMBER	Number of single block read requests
SMALL_WRITE_REQUESTS	NUMBER	Number of single block write requests
LARGE_READ_REQUESTS	NUMBER	Number of multiblock read requests
LARGE_WRITE_REQUESTS	NUMBER	Number of multiblock write requests

Column	Datatype	Description
PQS_COMPLETED	NUMBER	Total number of completed parallel statements in the consumer group
PQ_SERVERS_USED	NUMBER	Total number of parallel servers used by completed parallel statements in the consumer group
PQS_QUEUED	NUMBER	Number of times that sessions in the consumer group were queued when trying to run parallel statements
PQ_ACTIVE_TIME	NUMBER	Cumulative sum of the parallel active times for all completed parallel statements in the consumer group (in milliseconds)
PQ_QUEUED_TIME	NUMBER	Total amount of time that sessions in the consumer group were queued when trying to run parallel statements (in milliseconds)
PQ_QUEUE_TIME_OUTS	NUMBER	Number of times that parallel statements from sessions in the consumer group timed out because their queue time exceeded the Resource Manager plan's PARALLEL_QUEUE_TIMEOUT limit
PGA_LIMIT_SESSIONS_KILLED	NUMBER	Number of times that sessions in the consumer group were terminated because their untunable PGA usage exceeded the SESSION_PGA_LIMIT limit
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$RSRC_PDB_HISTORY"
- "V$RSRC_PLAN_HISTORY"
- "STATISTICS_LEVEL"

9.195 V$RSRC_CONSUMER_GROUP

V$RSRC_CONSUMER_GROUP displays data related to currently active resource consumer groups.

When the STATISTICS_LEVEL is set to TYPICAL or ALL, this view contains information about CPU utilization and wait times even when no Resource Manager plan is set or when the Resource Manager plan does not monitor CPU or session resources.

Statistics in V$RSRC_CONSUMER_GROUP are reset when a pluggable database (PDB) changes its resource plan. They are not impacted by multitenant container database (CDB) resource plan changes.

Since PDB plans can be set independently across different PDBs, V$RSRC_CONSUMER_GROUP will not cover the same time period across different PDBs. Therefore, this view is not useful for comparing statistics across different PDBs.

Column	Datatype	Description
ID	NUMBER	Consumer group object ID (a unique number, consistent across database shutdowns and startups)
NAME	VARCHAR2(32)	Name of the consumer group
ACTIVE_SESSIONS	NUMBER	Number of currently active sessions in the consumer group
EXECUTION_WAITERS	NUMBER	Number of currently active sessions waiting for an execution time slice in which they will be able to use CPU
REQUESTS	NUMBER	Cumulative number of requests that were executed in the consumer group
CPU_WAIT_TIME	NUMBER	Cumulative amount of time that sessions waited for CPU on the resmgr: cpu quantum wait event because of resource management (in milliseconds). This does not include waits due to latch or enqueue contention, I/O waits, and so on. When CPU resources are not being actively managed, this value is set to zero.
CPU_WAITS	NUMBER	Cumulative number of times all sessions in the consumer group had to wait for CPU on the resmgr: cpu quantum wait event because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on. When CPU resources are not being actively managed, this value is set to zero.
CONSUMED_CPU_TIME	NUMBER	Cumulative amount of CPU time consumed by all sessions in the consumer group (in milliseconds)
YIELDS	NUMBER	Cumulative number of times that sessions in the consumer group had to yield CPU to other sessions because of quantum expiration. When CPU resources are not being actively managed, this value is set to zero.
CPU_DECISIONS	NUMBER	Percentage of CPU decisions for which the consumer group was present. When CPU resources are not being actively managed, this value is set to zero.
CPU_DECISIONS_EXCLUSIVE	NUMBER	Percentage of the CPU decisions for which the consumer group was present and was the only consumer group present. When CPU resources are not being actively managed, this value is set to zero.
CPU_DECISIONS_WON	NUMBER	Percentage of the CPU decisions that the consumer group won. When CPU resources are not being actively managed, this value is set to zero.
QUEUE_LENGTH	NUMBER	Number of sessions waiting in the queue
CURRENT_UNDO_CONSUMPTION	NUMBER	Current amount (in KB) of undo consumed by the consumer group
ACTIVE_SESSION_LIMIT_HIT	NUMBER	Number of times that sessions in the consumer group were queued because the consumer group reached its active session limit
UNDO_LIMIT_HIT	NUMBER	Number of times that queries in the consumer group were canceled because the consumer group reached its UNDO_POOL limit
SWITCHES_IN_CPU_TIME	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_TIME limit
SWITCHES_OUT_CPU_TIME	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_TIME limit

Column	Datatype	Description
SWITCHES_IN_IO_MEGABYTES	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_MEGABYTES limit
SWITCHES_OUT_IO_MEGABYTES	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_MEGABYTES limit
SWITCHES_IN_IO_REQUESTS	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_REQS limit
SWITCHES_OUT_IO_REQUESTS	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_REQS limit
SWITCHES_IN_IO_LOGICAL	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_IO_LOGICAL limit
SWITCHES_OUT_IO_LOGICAL	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_IO_LOGICAL limit
SWITCHES_IN_ELAPSED_TIME	NUMBER	Number of switches into the consumer group because of the Resource Manager plan's SWITCH_ELAPSED_TIME limit
SWITCHES_OUT_ELAPSED_TIME	NUMBER	Number of switches out of the consumer group because of the Resource Manager plan's SWITCH_ELAPSED_TIME limit
SQL_CANCELED	NUMBER	Number of times that SQL queries running in the consumer group were terminated because they exceeded one of the Resource Manager plan's SWITCH limits and CANCEL_SQL was specified as the Resource Manager plan's SWITCH_GROUP
ACTIVE_SESSIONS_KILLED	NUMBER	Number of times that sessions running in the consumer group were terminated because they exceeded one of the Resource Manager plan's SWITCH limits and KILL_SESSION was specified as the Resource Manager plan's SWITCH_GROUP
IDLE_SESSIONS_KILLED	NUMBER	Number of times that sessions in the consumer group were terminated because they were idle for too long (reached MAX_IDLE_TIME)
IDLE_BLKR_SESSIONS_KILLED	NUMBER	Number of times that sessions in the consumer group were terminated because they were idle too long (reached MAX_IDLE_BLOCKER_TIME) and were blocking other sessions
QUEUED_TIME	NUMBER	Total amount of time that sessions in the consumer group have spent in the QUEUED state because of the active session limit (in milliseconds)
QUEUE_TIME_OUTS	NUMBER	Number of times that requests from sessions in the consumer group timed out because they were queued for too long (reached QUEUEING_P1)
IO_SERVICE_TIME	NUMBER	Cumulative I/O wait time (in milliseconds)
IO_SERVICE_WAITS	NUMBER	Total number of wait requests
SMALL_READ_MEGABYTES	NUMBER	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	Number of multiblock megabytes written
SMALL_READ_REQUESTS	NUMBER	Number of single block read requests
SMALL_WRITE_REQUESTS	NUMBER	Number of single block write requests
LARGE_READ_REQUESTS	NUMBER	Number of multiblock read requests
LARGE_WRITE_REQUESTS	NUMBER	Number of multiblock write requests

Column	Datatype	Description
CURRENT_PQS_ACTIVE	NUMBER	Number of active parallel statements in the consumer group. This value does not include parallel statements that are never queued, such as GV$ queries.
CURRENT_PQ_SERVERS_ACTIVE	NUMBER	Number of active parallel servers in the consumer group. This value does not include servers running parallel statements that are never queued, such as GV$ queries.
PQS_QUEUED	NUMBER	Number of times that sessions in the consumer group were queued when trying to run parallel statements
PQS_COMPLETED	NUMBER	Total number of completed parallel statements in the consumer group
PQ_SERVERS_USED	NUMBER	Total number of parallel servers used by completed parallel statements in the consumer group
PQ_ACTIVE_TIME	NUMBER	Cumulative sum of the parallel active times for all completed parallel statements in the consumer group (in milliseconds)
CURRENT_PQS_QUEUED	NUMBER	Number of sessions in the consumer group that are waiting in the parallel statement queue trying to run parallel statements
PQ_QUEUED_TIME	NUMBER	Total amount of time that sessions in the consumer group were queued when trying to run parallel statements (in milliseconds)
PQ_QUEUE_TIME_OUTS	NUMBER	Number of times that parallel statements from sessions in the consumer group timed out because their queue time exceeded the Resource Manager plan's PARALLEL_QUEUE_TIMEOUT limit
PGA_LIMIT_SESSIONS_KILLED	NUMBER	Number of times that sessions in the consumer group were terminated because their untunable PGA usage exceeded the SESSION_PGA_LIMIT limit
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "STATISTICS_LEVEL"
- "V$RSRC_PDB"
- *Oracle Database Administrator's Guide* for information on resource groups
- *Oracle Database PL/SQL Packages and Types Reference* for information on creating resource groups with the DBMS_RESOURCE_MANAGER package

9.196 V$RSRC_CONSUMER_GROUP_CPU_MTH

V$RSRC_CONSUMER_GROUP_CPU_MTH displays all resource allocation methods defined for resource consumer groups.

Column	Datatype	Description
NAME	VARCHAR2(40)	Name of the CPU resource allocation method
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- *Oracle Database Administrator's Guide* for information on resource allocation methods
- *Oracle Database PL/SQL Packages and Types Reference* on defining resource allocation methods for consumer groups with the DBMS_RESOURCE_MANAGER package
- "V$RSRC_PLAN_CPU_MTH" for a listing of all resource allocation methods defined for resource plans

9.197 V$RSRC_PDB

V$RSRC_PDB displays data related to currently active resource consumer groups by pluggable database (PDB).

When the STATISTICS_LEVEL is set to TYPICAL or ALL, this view contains information about CPU utilization and wait times even when no Resource Manager plan is set or when the Resource Manager plan does not monitor CPU or session resources.

Statistics in V$RSRC_PDB are reset when a multitenant container database (CDB) changes its resource plan. They are not impacted by PDB resource plan changes.

V$RSRC_PDB covers the same time period for all PDBs. This view is specifically designed for comparing statistics across different PDBs.

Since V$RSRC_PDB does not contain information at the consumer group level, it is not useful for comparing consumer groups inside a PDB.

Column	Datatype	Description
PDB_NAME	VARCHAR2(32)	PDB name
CPU_WAIT_TIME	NUMBER	Cumulative amount of time that sessions waited for CPU because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on. When CPU resources are not being actively managed, this value is set to zero.

Column	Datatype	Description
CPU_WAITS	NUMBER	Cumulative number of times all sessions in the consumer group had to wait for CPU because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on. When CPU resources are not being actively managed, this value is set to zero.
CONSUMED_CPU_TIME	NUMBER	Cumulative amount of CPU time consumed by all sessions in the consumer group (in milliseconds)
YIELDS	NUMBER	Cumulative number of times that sessions in the consumer group had to yield CPU to other sessions because of quantum expiration. When CPU resources are not being actively managed, this value is set to zero.
IO_SERVICE_TIME	NUMBER	Cumulative I/O wait time (in milliseconds)
IO_SERVICE_WAITS	NUMBER	Total number of wait requests
SMALL_READ_MEGABYTES	NUMBER	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	Number of multiblock megabytes written
SMALL_READ_REQUESTS	NUMBER	Number of single block read requests
SMALL_WRITE_REQUESTS	NUMBER	Number of single block write requests
LARGE_READ_REQUESTS	NUMBER	Number of multiblock read requests
LARGE_WRITE_REQUESTS	NUMBER	Number of multiblock write requests
PQS_COMPLETED	NUMBER	Total number of completed parallel statements in the consumer group
PQ_SERVERS_USED	NUMBER	Total number of parallel servers used by completed parallel statements in the consumer group
PQS_QUEUED	NUMBER	Number of times that sessions in the consumer group were queued when trying to run parallel statements
PQ_ACTIVE_TIME	NUMBER	Cumulative sum of the parallel active times for all completed parallel statements in the consumer group (in milliseconds)
PQ_QUEUED_TIME	NUMBER	Total amount of time that sessions in the consumer group were queued when trying to run parallel statements (in milliseconds)
PQ_QUEUE_TIME_OUTS	NUMBER	Number of times that parallel statements from sessions in the consumer group timed out because their queue time exceeded the Resource Manager plan's PARALLEL_QUEUE_TIMEOUT limit
CURRENT_PQS_ACTIVE	NUMBER	Number of active parallel statements in the consumer group. This value does not include parallel statements that are never queued, such as GV$ queries.
CURRENT_PQ_SERVERS_ACTIVE	NUMBER	Number of active parallel servers in the consumer group. This value does not include servers running parallel statements that are never queued, such as GV$ queries.
CURRENT_PQS_QUEUED	NUMBER	Number of sessions in the consumer group that are waiting in the parallel statement queue trying to run parallel statements
SGA_BYTES	NUMBER	The current SGA usage by this PDB in bytes
BUFFER_CACHE_BYTES	NUMBER	The current usage of buffer cache by this PDB in bytes
SHARED_POOL_BYTES	NUMBER	The current usage of shared pool by this PDB in bytes
PGA_BYTES	NUMBER	The current usage of PGA by this PDB in bytes

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$RSRC_CONSUMER_GROUP"

9.198 V$RSRC_PDB_HISTORY

V$RSRC_PDB_HISTORY displays a history of consumer group statistics for each entry in V$RSRC_PDB that has a non-NULL plan by pluggable database (PDB).

When the STATISTICS_LEVEL is set to TYPICAL or ALL, this view contains information about CPU utilization and wait times even when no Resource Manager plan is set or when the Resource Manager plan does not monitor CPU or session resources.

A new window is created in V$RSRC_PDB_HISTORY when a multitenant container database (CDB) changes its resource plan. The plan windows for the CDB are not impacted by a PDB resource plan change.

V$RSRC_PDB_HISTORY covers the same time period for all PDBs. This view is specifically designed for comparing statistics across different PDBs.

Since V$RSRC_PDB_HISTORY does not contain information at the consumer group level, it is not useful for comparing consumer groups inside a PDB.

Column	Datatype	Description
SEQUENCE#	NUMBER	A sequential counter that uniquely describes the V$RSRC_PDB entry to which these consumer group statistics apply. When the instance is restarted, this value is reset to zero.
PDB_NAME	VARCHAR2(32)	PBD name
CPU_WAIT_TIME	NUMBER	Cumulative amount of time that sessions waited for CPU because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on. When CPU resources are not being actively managed, this value is set to zero.
CPU_WAITS	NUMBER	Cumulative number of times all sessions in the consumer group had to wait for CPU because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on. When CPU resources are not being actively managed, this value is set to zero.

Column	Datatype	Description
CONSUMED_CPU_TIME	NUMBER	Cumulative amount of CPU time consumed by all sessions in the consumer group (in milliseconds)
YIELDS	NUMBER	Cumulative number of times that sessions in the consumer group had to yield CPU to other sessions because of quantum expiration. When CPU resources are not being actively managed, this value is set to zero.
IO_SERVICE_TIME	NUMBER	Cumulative I/O wait time (in milliseconds)
IO_SERVICE_WAITS	NUMBER	Total number of wait requests
SMALL_READ_MEGABYTES	NUMBER	Number of single block megabytes read
SMALL_WRITE_MEGABYTES	NUMBER	Number of single block megabytes written
LARGE_READ_MEGABYTES	NUMBER	Number of multiblock megabytes read
LARGE_WRITE_MEGABYTES	NUMBER	Number of multiblock megabytes written
SMALL_READ_REQUESTS	NUMBER	Number of single block read requests
SMALL_WRITE_REQUESTS	NUMBER	Number of single block write requests
LARGE_READ_REQUESTS	NUMBER	Number of multiblock read requests
LARGE_WRITE_REQUESTS	NUMBER	Number of multiblock write requests
PQS_COMPLETED	NUMBER	Total number of completed parallel statements in the consumer group
PQ_SERVERS_USED	NUMBER	Total number of parallel servers used by completed parallel statements in the consumer group
PQS_QUEUED	NUMBER	Number of times that sessions in the consumer group were queued when trying to run parallel statements
PQ_ACTIVE_TIME	NUMBER	Cumulative sum of the parallel active times for all completed parallel statements in the consumer group (in milliseconds)
PQ_QUEUED_TIME	NUMBER	Total amount of time that sessions in the consumer group were queued when trying to run parallel statements (in milliseconds)
PQ_QUEUE_TIME_OUTS	NUMBER	Number of times that parallel statements from sessions in the consumer group timed out because their queue time exceeded the Resource Manager plan's PARALLEL_QUEUE_TIMEOUT limit
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$RSRC_CONS_GROUP_HISTORY"

9.199 V$RSRC_PLAN

V$RSRC_PLAN displays the names of all currently active resource plans.

Column	Datatype	Description
ID	NUMBER	Resource plan ID (a unique number, consistent across database shutdowns and startups). This is also the data dictionary object ID.
NAME	VARCHAR2(32)	Name of the resource plan
IS_TOP_PLAN	VARCHAR2(5)	Indicates whether the resource plan is the current top plan (TRUE) or whether the resource plan is a subplan of the current top plan (FALSE)
CPU_MANAGED	VARCHAR2(3)	Indicates whether the resource plan has parameters that specify a policy for how the Resource Manager should schedule sessions to manage CPU usage (ON) or whether Resource Manager is not managing CPU usage (OFF)
CPU_SCOPE	VARCHAR2(13)	Scope of the policy for how the Resource Manager should schedule sessions to manage CPU usage. Possible values: • OFF - Resource Manager is not managing CPU usage (CPU_MANAGED = OFF) • INSTANCE_ONLY - Resource Manage is managing CPU usage only within the database instance • SERVER_WIDE - Resource Manager is using server-level inter-instance CPU resource management
INSTANCE_CAGING	VARCHAR2(3)	Indicates whether instance caging is enabled (ON) or disabled (OFF). Instance caging is enabled if the CPU_COUNT initialization parameter is explicitly modified to a value other than 0 and Resource Manager is enabled.
PARALLEL_SERVERS_ACTIVE	NUMBER	Total number of active parallel servers on the instance
PARALLEL_SERVERS_TOTAL	NUMBER	The value of PARALLEL_SERVERS_TARGET for the instance. Parallel statements are queued if the total number of active parallel servers exceeds this value.

Column	Datatype	Description
PARALLEL_EXECUTION_MANAGED	VARCHAR2(32)	State of parallel statement queuing: • OFF - Parallel statement queuing is disabled • STARTUP - Parallel statement queuing is enabled. This is a temporary state that can occur when an Oracle RAC database is undergoing configuration changes • FIFO - Parallel statement queuing is enabled. All parallel statements are managed in a single Oracle RAC FIFO queue • FULL - Parallel statement queuing is enabled. All parallel statements are managed in per-consumer group queues according to the current resource plan. This state is used when a resource plan that contains resource allocation directives (MGMT_P*) is enabled. • DISABLED - Parallel statement queuing is disabled. This state can occur when memory is unavailable for use by parallel statement queuing in the System Global Area (SGA). Restart the Oracle instance to re-enable parallel statement queuing. For an Oracle RAC database, only the instance running as primary Database Resource Manager (DBRM) shows the correct state of parallel statement queuing. All other instances default to the value FULL. A single instance database always shows the correct value for this field.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
DIRECTIVE_TYPE	VARCHAR2(32)	The type of directive used by this PDB: • DEFAULT_DIRECTIVE: The default plan directive • PDB: A PDB directive • PROFILE: A profile directive
SHARES	NUMBER	Resource allocation for this PDB, expressed in shares
UTILIZATION_LIMIT	NUMBER	Maximum percentage of the container's resources allowed for this PDB
PARALLEL_SERVER_LIMIT	NUMBER	Maximum percentage of the parallel target the PDB can use before queuing subsequent parallel queries
MEMORY_MIN	NUMBER	The percentage of Exadata Smart Flash Cache and Exadata PMEM cache that is guaranteed to the PDB This percentage is based on the total amount of space allocated to the CDB for Exadata Smart Flash Cache and Exadata PMEM cache. See *Oracle Exadata System Software User's Guide* for more information.

Column	Datatype	Description
MEMORY_LIMIT	NUMBER	The maximum percentage of Exadata Smart Flash Cache and Exadata PMEM cache that the PDB can use This percentage is based on the total amount of space allocated to the CDB for Exadata Smart Flash Cache and Exadata PMEM cache. See *Oracle Exadata System Software User's Guide* for more information.
PROFILE	VARCHAR2(32)	The value of the DB_PERFORMANCE_PROFILE initialization parameter for this PDB
CPU_COUNT	NUMBER	Value of the CPU_COUNT initialization parameter in the container to which the data pertains
CPU_MIN_COUNT	NUMBER	Value of the CPU_MIN_COUNT initialization parameter in the container to which the data pertains

The resource plan with CON_ID=ROOT is the CDB resource plan.

See Also:

- "DBA_RSRC_PLANS" for a listing of all plans in the database
- "DBA_CDB_RSRC_PLANS" for information about CDB resource plans
- "DBA_CDB_RSRC_PLAN_DIRECTIVES" for information about CDB resource plan directives
- "DB_PERFORMANCE_PROFILE"
- *Oracle Database Administrator's Guide* for information on resource plans
- *Oracle Database PL/SQL Packages and Types Reference* for information on defining resource allocation methods for consumer groups with the DBMS_RESOURCE_MANAGER package

9.200 V$RSRC_PLAN_CPU_MTH

V$RSRC_PLAN_CPU_MTH displays all available CPU resource allocation methods defined for resource plans.

Column	Datatype	Description
NAME	VARCHAR2(40)	Name of the resource allocation method
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$RSRC_CONSUMER_GROUP_CPU_MTH" for a listing of resource allocation methods defined for consumer groups
- *Oracle Database Administrator's Guide* for information on resource plans
- *Oracle Database PL/SQL Packages and Types Reference* for information on defining resource allocation methods for consumer plans with the `DBMS_RESOURCE_MANAGER` package

9.201 V$RSRC_PLAN_HISTORY

`V$RSRC_PLAN_HISTORY` displays a history of when a resource plan was enabled, disabled, or modified on the instance. Up to 15 of the most recent entries are shown. Once the database is opened, this view shows at least one row. The row with the most recent `START_TIME` and with `END_TIME` equal to NULL gives information about the current resource plan.

Column	Datatype	Description
SEQUENCE#	NUMBER	A sequential counter that uniquely describes a row. When the instance is restarted, this value is reset to zero.
ID	NUMBER	Resource plan ID; NULL if the Resource Manager was disabled
NAME	VARCHAR2(30)	Resource plan name; NULL if the Resource Manager was disabled
START_TIME	DATE	Time that the resource plan was enabled
END_TIME	DATE	Time that the resource plan was disabled; NULL if the row contains the current resource plan information
ENABLED_BY_SCHEDULER	VARCHAR2(5)	Indicates whether the plan was enabled by a Job Scheduler window (`TRUE`) or not (`FALSE`)
WINDOW_NAME	VARCHAR2(128)	Job Scheduler window that triggered the resource plan event; NULL if a user triggered the resource plan event
ALLOWED_AUTOMATED_SWITCHES	VARCHAR2(5)	Indicates whether automated plan switches were allowed after this resource plan event (`TRUE`) or whether automated plan switches were disabled after this resource plan event (`FALSE`) **See Also:** the `SWITCH_PLAN` procedure
CPU_MANAGED	VARCHAR2(3)	Indicates whether the resource plan has parameters that specify a policy for how the Resource Manager should schedule sessions to manage CPU usage (`ON`) or whether Resource Manager is not managing CPU usage (`OFF`)
CPU_SCOPE	VARCHAR2(13)	Scope of the policy for how the Resource Manager should schedule sessions to manage CPU usage. Possible values: • `OFF` - Resource Manager is not managing CPU usage (`CPU_MANAGED` = `OFF`) • `INSTANCE_ONLY` - Resource Manage is managing CPU usage only within the database instance • `SERVER_WIDE` - Resource Manager is using server-level inter-instance CPU resource management

Column	Datatype	Description
INSTANCE_CAGING	VARCHAR2(3)	Indicates whether instance caging is enabled (ON) or disabled (OFF). Instance caging is enabled if the CPU_COUNT initialization parameter is explicitly modified to a value other than 0 and Resource Manager is enabled.
PARALLEL_EXECUTION_MANAGED	VARCHAR2(32)	State of parallel statement queuing: • OFF - Parallel statement queuing is disabled • STARTUP - Parallel statement queuing is enabled. This is a temporary state that can occur when an Oracle RAC database is undergoing configuration changes • FIFO - Parallel statement queuing is enabled. All parallel statements are managed in a single Oracle RAC FIFO queue • FULL - Parallel statement queuing is enabled. All parallel statements are managed in per-consumer group queues according to the current resource plan. This state is used when a resource plan that contains resource allocation directives (MGMT_P*) is enabled. • DISABLED - Parallel statement queuing is disabled. This state can occur when memory is unavailable for use by parallel statement queuing in the System Global Area (SGA). Restart the Oracle instance to re-enable parallel statement queuing. For an Oracle RAC database, only the instance running as primary Database Resource Manager (DBRM) shows the correct state of parallel statement queuing. All other instances default to the value FULL. A single instance database always shows the correct value for this field.
CPU_COUNT	NUMBER	Value of the CPU_COUNT initialization parameter in the container to which the data pertains
CPU_MIN_COUNT	NUMBER	Value of the CPU_MIN_COUNT initialization parameter in the container to which the data pertains
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.202 V$RSRC_SESSION_INFO

V$RSRC_SESSION_INFO displays Resource Manager statistics per session.

Column	Datatype	Description
SID	NUMBER	Session identifier
CURRENT_CONSUMER_GROUP_ID	NUMBER	Object ID of the consumer group in which the session currently belongs; NULL if the session has not yet logged in
CURRENT_CONSUMER_GROUP	VARCHAR2(32)	The name of the consumer group in which the session currently belongs

Column	Datatype	Description
ORIG_CONSUMER_GROUP_ID	NUMBER	Object ID of the consumer group in which the session was placed by the consumer group mappings; NULL if the session has not yet logged in This group may not be the current group because the SWITCH_GROUP directive in the current plan may have changed the session's current group. This group may not equal the MAPPED_CONSUMER_GROUP because the MAPPED_CONSUMER_GROUP may not be part of the current plan.
MAPPING_ATTRIBUTE	VARCHAR2(32)	Session attribute that was used to map the session into its original consumer group; NULL if no mapping was used **See Also:** "DBA_RSRC_GROUP_MAPPINGS" for more details
MAPPED_CONSUMER_GROUP	VARCHAR2(32)	Consumer group to which the session was originally mapped; NULL if no mapping was used This may not correspond to the original consumer group, because the mapped group may not be part of the current plan. **See Also:** "DBA_RSRC_GROUP_MAPPINGS" for more details
STATE	VARCHAR2(32)	Current state of the session: • NOT MANAGED - Session has not logged in or the current Resource Manager plan does not require the session to be managed at this point in time • RUNNING - Session is currently running on the CPU • WAITING FOR CPU - Session is ready to run. It is waiting for a CPU quantum to run. • QUEUED - Session is queued because the active session limit was reached • IDLE - Session is idle • IDLE BLKR - Session is idle and blocking another session • WAITING - Session is currently in a wait **See Also:** "V$SESSION_WAIT" for the wait type • WAITING_FOR_IO - Session is waiting to submit an I/O request • UNBOUND - Session is not bound to any process • EXITING - Session is about to terminate
ACTIVE	VARCHAR2(5)	Indicates whether the session is currently active (TRUE) or not (FALSE). This includes when one of the following conditions is true: • Session is in the top call • Session has a transaction in progress • Session is using temporary space objects • Session holds user enqueues
CURRENT_IDLE_TIME	NUMBER	Number of seconds the session has been idle (in states IDLE or IDLE BLKR) while in this consumer group; NULL if the current Resource Manager plan does not require updating this statistic. This value is reset to zero when the session becomes active.
CURRENT_CPU_WAIT_TIME	NUMBER	Amount of time (in milliseconds) the session has waited for CPU because of resource management (in state WAIT FOR CPU) while in the current consumer group; NULL if the current Resource Manager plan does not require updating this statistic. This does not include waits due to latch or enqueue contention, I/O waits, and so on. If SWITCH_TIME_IN_CALL is used, then this will be reset at the end of every call.

Column	Datatype	Description
CPU_WAIT_TIME	NUMBER	Cumulative amount of time (in milliseconds) the session has waited for CPU (in its lifetime) because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on.
CURRENT_CPU_WAITS	NUMBER	Number of times the session had to wait for CPU because of resource management while in this consumer group; NULL if the current Resource Manager plan does not require updating this statistic. This does not include waits due to latch or enqueue contention, I/O waits, and so on. If SWITCH_TIME_IN_CALL is used, then this will be reset at the end of every call.
CPU_WAITS	NUMBER	Cumulative number of times the session had to wait for CPU (in its lifetime) because of resource management. This does not include waits due to latch or enqueue contention, I/O waits, and so on.
CURRENT_CONSUMED_CPU_TIME	NUMBER	Amount of CPU time (in milliseconds) consumed by the session while in the current consumer group; NULL if the current Resource Manager plan does not require updating this statistic. If SWITCH_TIME_IN_CALL is used, then this will be reset at the end of every call.
CONSUMED_CPU_TIME	NUMBER	Cumulative amount of CPU time consumed by the session (in its lifetime) (in milliseconds)
CURRENT_ACTIVE_TIME	NUMBER	Amount of time (in milliseconds) the session has been active while in the current consumer group; NULL if the current Resource Manager plan does not require updating this statistic. Active time is time spent running and waiting while executing a call. It does not include the time a session waited for CPU resources. If SWITCH_TIME_IN_CALL is used, then this is reset at the end of every call.
ACTIVE_TIME	NUMBER	Cumulative amount of active time (in milliseconds) consumed by the session (in its lifetime)
CURRENT_QUEUED_TIME	NUMBER	Amount of time (in milliseconds) the current request from the session has been queued (in state QUEUED). If the session does not have a request currently queued up, then this number will be zero.
QUEUED_TIME	NUMBER	Total amount of time (in milliseconds) the session has spent in the QUEUED state (in its lifetime)
CURRENT_YIELDS	NUMBER	Number of times the session had to yield the CPU to other sessions (due to quantum expiration) while in the current consumer group; NULL if the current Resource Manager plan does not require updating this statistic. If SWITCH_TIME_IN_CALL is used, then this is reset at the end of every call.
YIELDS	NUMBER	Cumulative number of times the session had to yield CPU to other sessions due to quantum expiration (in its lifetime)
CURRENT_UNDO_CONSUMPTION	NUMBER	Current amount (in KB) of undo consumed by the session; NULL if the current Resource Manager plan does not have an UNDO_POOL directive
MAX_UNDO_CONSUMPTION	NUMBER	Maximum amount of undo consumed (in KB) during the session's lifetime. This value may not be updated because the current Resource Manager plan may not have an UNDO_POOL directive.
SQL_CANCELED	NUMBER	Number of times SQL queries running in the session were canceled due to exceeding the Resource Manager plan's SWITCH_TIME limit.

Column	Datatype	Description
QUEUE_TIME_OUTS	NUMBER	Number of times requests from the session timed out because they queued longer than the Resource Manager plan's limit
ESTIMATED_EXECUTION_LIMIT_HIT	NUMBER	Number of times requests from the session were not run because the optimizer's estimated time to execute the query exceeded the MAX_EST_EXEC_TIME limit
CURRENT_IO_SERVICE_TIME	NUMBER	Current I/O wait time of the session (in milliseconds) for the current SQL operation
IO_SERVICE_TIME	NUMBER	Cumulative amount of I/O wait time by the session (in its lifetime) (in milliseconds)
CURRENT_IO_SERVICE_WAITS	NUMBER	Current I/O waits by session for the current SQL operation
IO_SERVICE_WAITS	NUMBER	Cumulative I/O waits by session (in its lifetime)
CURRENT_SMALL_READ_MEGABYTES	NUMBER	Number of single block megabytes read by the session for the current SQL operation
SMALL_READ_MEGABYTES	NUMBER	Total number of single block megabytes read by the session (in its lifetime)
CURRENT_LARGE_READ_MEGABYTES	NUMBER	Number of multiblock megabytes read by the session for the current SQL operation
LARGE_READ_MEGABYTES	NUMBER	Total number of multiblock megabytes read by the session (in its lifetime)
CURRENT_SMALL_WRITE_MEGABYTES	NUMBER	Number of single block megabytes written by the session for the current SQL operation
SMALL_WRITE_MEGABYTES	NUMBER	Total number of single block megabytes written by the session (in its lifetime)
CURRENT_LARGE_WRITE_MEGABYTES	NUMBER	Number of multiblock megabytes written by the session for the current SQL operation
LARGE_WRITE_MEGABYTES	NUMBER	Total number of multiblock megabytes written by the session (in its lifetime)
CURRENT_SMALL_READ_REQUESTS	NUMBER	Number of single block read requests by the session for the current SQL operation
SMALL_READ_REQUESTS	NUMBER	Total number of single block read requests by the session (in its lifetime)
CURRENT_SMALL_WRITE_REQUESTS	NUMBER	Number of single block write requests by the session for the current SQL operation
SMALL_WRITE_REQUESTS	NUMBER	Total number of single block write requests by the session (in its lifetime)
CURRENT_LARGE_READ_REQUESTS	NUMBER	Number of multiblock read requests by the session for the current SQL operation
LARGE_READ_REQUESTS	NUMBER	Total number of multiblock read requests by the session (in its lifetime)
CURRENT_LARGE_WRITE_REQUESTS	NUMBER	Number of multiblock write requests by the session for the current SQL operation
LARGE_WRITE_REQUESTS	NUMBER	Total number of multiblock write requests by the session (in its lifetime)

Column	Datatype	Description
CURRENT_PQ_ACTIVE_TIME	NUMBER	Amount of time that the current active parallel statement has been executing for the current SQL operation, not including the amount of time that the statement has been queued (in milliseconds). If the parallel statement is queued, then the value is 0.
PQ_ACTIVE_TIME	NUMBER	Cumulative amount of time that parallel statements have been executed over the lifetime of the session (in milliseconds)
DOP	NUMBER	Degree of parallelism for the active or queued parallel statement, if there are any in the session
PQ_SERVERS	NUMBER	The number of active parallel servers if the session is active and running the parallel query. If the query is queued, the number of parallel servers that this query is trying to run with is shown.
ESTIMATED_EXECUTION_TIME	NUMBER	Estimated execution time for the parallel statement, as estimated by the optimizer (in milliseconds). You can compare this value to CURRENT_PQ_ACTIVE_TIME to estimate how much longer the parallel statement will run.
CURRENT_PQ_QUEUED_TIME	NUMBER	Amount of time that the current parallel statement in the session has been queued (in milliseconds) for the current SQL operation. If the session does not have a queued parallel statement, then the value is 0.
PQ_QUEUED_TIME	NUMBER	Total amount of time that the session has spent in the PQ_QUEUED state in its lifetime (in milliseconds)
PQ_QUEUED	NUMBER	Number of times that parallel statements in the session have been queued
PQ_QUEUE_TIME_OUTS	NUMBER	Number of times that parallel statements in the session timed out because their queue time exceeded the Resource Manager plan's PARALLEL_QUEUE_TIMEOUT limit
PQ_ACTIVE	VARCHAR2(5)	Indicates whether the session is actively running a parallel statement (TRUE) or not (FALSE).
PQ_STATUS	VARCHAR2(44)	The status of the parallel statement running in this session: • Active: The parallel statement is currently active and running • Queued: The parallel statement is queued and is not a possible candidate to be run next • Queue head: The parallel statement is queued due to the global systemwide limit and is the next parallel statement to be dequeued and run • Queue head - waiting on CG limit: The parallel statement is queued due to the consumer group limit and is the one to be run next from the session's consumer group • Queue head - waiting on service availability: The parallel statement is queued since there are not enough parallel servers available for the service this session is running on. This session is the one to be run next from the session's service • Queue head - waiting on PDB limit: The parallel statement is queued due to the PDB limit and is the one to be run next from the session's PDB • NULL: The session currently does not involve a parallel execution
CURRENT_LOGICAL_IOS	NUMBER	Number of logical I/O requests by the session for the current SQL operation

Column	Datatype	Description
LOGICAL_IOS	NUMBER	Total number of logical I/O requests in this session's lifetime
CURRENT_ELAPSED_TIME	NUMBER	Elapsed time of the session's current SQL operation
ELAPSED_TIME	NUMBER	Total elapsed time for all of this session's SQL operations in its lifetime
LAST_ACTION	VARCHAR2(48)	The most recent action that was taken on this SQL operation by Resource Manager. Its value is one of the following: • CANCEL_SQL • KILL_SESSION • LOG_ONLY • SWITCH TO <CG NAME> For the last value, <CG NAME> is the name of the consumer group that the SQL operation was switched to. If the Resource Plan has since been changed then <CG NAME> is the ID of the consumer group.
LAST_ACTION_REASON	VARCHAR2(30)	The reason for the most recent action that was taken on this SQL operation by Resource Manager. Its value is one of the following: • SWITCH_CPU_TIME • SWITCH_IO_REQS • SWITCH_IO_MBS • SWITCH_ELAPSED_TIME • SWITCH_IO_LOGICAL
LAST_ACTION_TIME	DATE	The time of the most recent action that was taken on this SQL operation by Resource Manager
CURRENT_PGA	NUMBER	Amount of PGA memory (in bytes) used by the session for the current SQL operation
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.203 V$RSRCMGRMETRIC

V$RSRCMGRMETRIC displays information about resources consumed and wait times per consumer group.

When the STATISTICS_LEVEL is set to TYPICAL or ALL, this view contains information about CPU utilization and wait times even when no Resource Manager plan is set or when the Resource Manager plan does not monitor CPU or session resources. Metrics are collected and stored every minute when CPU utilization is not being monitored.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)

Column	Datatype	Description
SEQUENCE#	NUMBER	A sequential counter that uniquely describes the V$RSRC_PLAN_HISTORY entry to which these consumer group statistics apply. When the instance is restarted, this value is reset to zero.
CONSUMER_GROUP_ID	NUMBER	Consumer group object ID (a unique number, consistent across database shutdowns and startups)
CONSUMER_GROUP_NAME	VARCHAR2(30)	Name of the consumer group
CPU_CONSUMED_TIME	NUMBER	Cumulative amount of CPU time consumed by all sessions in the consumer group, in milliseconds
CPU_WAIT_TIME	NUMBER	Cumulative amount of time that sessions waited for CPU because of resource management, in milliseconds. This does not include waits due to latch or enqueue contention, I/O waits, and so on. When CPU resources are not being actively managed, this value is set to zero.
CPU_EXHAUSTED	NUMBER	Percentage of time that CPUs are exhausted, out of the total number of checks in the consumer group
NUM_CPUS	NUMBER	Number of CPUs that the Resource Manager is utilizing. If instance caging is enabled, then this column is equal to the value of the CPU_COUNT initialization parameter. If instance caging is not enabled, then this column is equal to the total number of CPUs in the system.
RUNNING_SESSIONS_LIMIT	NUMBER	Maximum number of sessions in the consumer group that can run simultaneously. The value of this column is NUM_CPUS multiplied by the consumer group's MAX_UTILIZATION_LIMIT directive in the current Resource Manager plan.
AVG_RUNNING_SESSIONS	NUMBER	Average number of sessions in the consumer group that are currently running
AVG_WAITING_SESSIONS	NUMBER	Average number of sessions in the consumer group that are waiting for CPU due to resource management. When CPU resources are not being actively managed, this value is set to zero.
CPU_UTILIZATION_LIMIT	NUMBER	Maximum percentage of CPU that the consumer group can use at any time, with respect to the total number of CPUs in the system. The value of this column is RUNNING_SESSIONS_LIMIT divided by the number of CPUs in the system. If instance caging is enabled, then this value is derived using the CPU_COUNT initialization parameter.
AVG_CPU_UTILIZATION	NUMBER	Average percentage of CPU consumed by the consumer group, with respect to the total number of CPUs in the system
CPU_DECISIONS	NUMBER	Percentage of CPU decisions for which the consumer group was present. When CPU resources are not being actively managed, this value is set to zero. This column is deprecated.
CPU_DECISIONS_EXCLUSIVE	NUMBER	Percentage of the CPU decisions for which the consumer group was present and was the only consumer group present. When CPU resources are not being actively managed, this value is set to zero. This column is deprecated.
CPU_DECISIONS_WON	NUMBER	Percentage of the CPU decisions that the consumer group won. When CPU resources are not being actively managed, this value is set to zero. This column is deprecated.
IO_REQUESTS	NUMBER	I/O requests

Column	Datatype	Description
IO_MEGABYTES	NUMBER	I/O megabytes
AVG_ACTIVE_PARALLEL_STMTS	NUMBER	The average number of parallel statements that were running during the 1-minute metric window
AVG_QUEUED_PARALLEL_STMTS	NUMBER	The average number of parallel statements that were queued during the 1-minute metric window
AVG_ACTIVE_PARALLEL_SERVERS	NUMBER	The average number of parallel servers that were actively running as part of a parallel statement during the 1-minute metric window
AVG_QUEUED_PARALLEL_SERVERS	NUMBER	The average number of parallel servers that were requested by queued parallel statements during the 1-minute metric window
PARALLEL_SERVERS_LIMIT	NUMBER	The number of parallel servers allowed to be used by this consumer group during the 1-minute metric window
PLAN_NAME	VARCHAR2(30)	Resource Manager plan name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "STATISTICS_LEVEL"

9.204 V$RSRCMGRMETRIC_HISTORY

V$RSRCMGRMETRIC_HISTORY displays a history (the last one hour) of resource manager metrics, taken from V$RSRCMGRMETRIC. When a resource plan is set, this history is cleared and restarted. This view provides information about resources consumed and wait times per consumer group.
The columns for V$RSRCMGRMETRIC_HISTORY are the same as those for V$RSRCMGRMETRIC.

> **See Also:**
>
> "V$RSRCMGRMETRIC"

9.205 V$RSRCPDBMETRIC

V$RSRCPDBMETRIC displays information about resources consumed and wait times per PDB.

When the STATISTICS_LEVEL is set to TYPICAL or ALL, this view contains information about CPU utilization and wait times even when no Resource Manager plan is set or when the

Resource Manager plan does not monitor CPU or session resources. Metrics are collected and stored every minute when CPU utilization is not being monitored.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
SEQUENCE#	NUMBER	A sequential counter that uniquely describes the V$RSRC_PLAN_HISTORY entry to which these PDB statistics apply. When the instance is restarted, this value is reset to zero.
CPU_CONSUMED_TIME	NUMBER	Cumulative amount of CPU time consumed by all sessions in the PDB, in milliseconds
CPU_WAIT_TIME	NUMBER	Cumulative amount of time that sessions waited for CPU because of resource management, in milliseconds. This does not include waits due to latch or enqueue contention, I/O waits, and so on. When CPU resources are not being actively managed, this value is set to zero.
CPU_EXHAUSTED	NUMBER	Percentage of time that CPUs are exhausted, out of the total number of checks in the PDB
NUM_CPUS	NUMBER	Number of CPUs that the Resource Manager is utilizing. If instance caging is enabled, then this column is equal to the value of the CPU_COUNT initialization parameter. If instance caging is not enabled, then this column is equal to the total number of CPUs in the system.
RUNNING_SESSIONS_LIMIT	NUMBER	Maximum number of sessions in the PDB that can run simultaneously. The value of this column is NUM_CPUS multiplied by the PDB's MAX_UTILIZATION_LIMIT directive in the current Resource Manager plan.
AVG_RUNNING_SESSIONS	NUMBER	Average number of sessions in the PDB that are currently running
AVG_WAITING_SESSIONS	NUMBER	Average number of sessions in the PDB that are waiting for CPU due to resource management. When CPU resources are not being actively managed, this value is set to zero.
CPU_UTILIZATION_LIMIT	NUMBER	Maximum percentage of CPU that the PDB can use at any time, with respect to the total number of CPUs in the system. The value of this column is RUNNING_SESSIONS_LIMIT divided by the number of CPUs in the system. If instance caging is enabled, then this value is derived using the CPU_COUNT initialization parameter.
AVG_CPU_UTILIZATION	NUMBER	Average percentage of CPU consumed by the PDB, with respect to the total number of CPUs in the system
IOPS	NUMBER	I/O operations per second during the previous minute for this PDB
IOMBPS	NUMBER	I/O megabytes per second during the previous minute for this PDB
IOPS_THROTTLE_EXEMPT	NUMBER	Indicates how much of the I/O per second in the current PDB was exempted from throttling. For example, if the value in the IOPS column is 20 I/Os and the value in the IOPS_THROTTLE_EXEMPT column is 5 I/Os, then 5 I/Os of the 20 I/Os in that second were exempted from throttling. I/O throttling is defined by the MAX_IOPS database initialization parameter.

Column	Datatype	Description
IOMBPS_THROTTLE_EXEMPT	NUMBER	Indicates how many megabytes of I/O executed per second in the current PDB were exempted from throttling. For example, if the value in the IOMBPS column is 200 megabytes and the value in the IOMBPS_THROTTLE_EXEMPT column is 50 megabytes, then 50 megabytes of the 200 megabytes were exempt from throttling. I/O megabytes per second throttling is defined by the MAX_MBPS database initialization parameter.
AVG_IO_THROTTLE	NUMBER	Average throttle time per I/O operation in milliseconds during the previous minute for this PDB
AVG_ACTIVE_PARALLEL_STMTS	NUMBER	The average number of parallel statements that were running during the 1-minute metric window
AVG_QUEUED_PARALLEL_STMTS	NUMBER	The average number of parallel statements that were queued during the 1-minute metric window
AVG_ACTIVE_PARALLEL_SERVERS	NUMBER	The average number of parallel servers that were actively running as part of a parallel statement during the 1-minute metric window
AVG_QUEUED_PARALLEL_SERVERS	NUMBER	The average number of parallel servers that were requested by queued parallel statements during the 1-minute metric window
PARALLEL_SERVERS_LIMIT	NUMBER	The number of parallel servers allowed to be used by this PDB during the 1-minute metric window
SGA_BYTES	NUMBER	The current SGA usage by this PDB in bytes
BUFFER_CACHE_BYTES	NUMBER	The current usage of the buffer cache by this PDB in bytes
SHARED_POOL_BYTES	NUMBER	The current usage of the shared pool by this PDB in bytes
PGA_BYTES	NUMBER	The current PGA usage by this PDB in bytes
PLAN_NAME	VARCHAR2(30)	Resource Manager plan name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"STATISTICS_LEVEL"

9.206 V$RSRCPDBMETRIC_HISTORY

V$RSRCPDBMETRIC_HISTORY displays a history (the last one hour) of resource manager metrics for a PDB, taken from V$RSRCPDBMETRIC. When a resource plan is set, this history is cleared

and restarted. This view provides information about resources consumed and wait times per consumer group.
The columns for `V$RSRCPDBMETRIC_HISTORY` are the same as those for `V$RSRCPDBMETRIC`.

> **See Also:**
>
> "V$RSRCPDBMETRIC"

9.207 V$RULE

`V$RULE` displays rule statistics. This view has a row for every rule loaded into shared memory.

Column	Datatype	Description
RULE_SET_OBJECT_ID	NUMBER	Rule set object ID
EVALUATION_CONTEXT_OBJECT_ID	NUMBER	Evaluation context object ID
RULE_OWNER	VARCHAR2(128)	Owner of the rule
RULE_NAME	VARCHAR2(128)	Name of the rule
RULE_CONDITION	VARCHAR2(200)	Rule condition
TRUE_HITS	NUMBER	Number of times the rule evaluated to `TRUE`
MAYBE_HITS	NUMBER	Number of times the rule evaluated to `MAYBE`
SQL_EVALUATIONS	NUMBER	Number of evaluations of the rule that were performed by issuing SQL
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

9.208 V$RULE_SET

`V$RULE_SET` displays rule set statistics. This view has a row for every rule set loaded into shared memory.

> **Note:**
>
> Querying the `V$RULE_SET` view may have a negative impact on performance if a database has a large library cache.

Column	Datatype	Description
OWNER	VARCHAR2(128)	Owner of the rule set
NAME	VARCHAR2(128)	Name of the rule set
CPU_TIME	NUMBER	Total CPU time (in hundredths of a second) spent in evaluation of the rule set
ELAPSED_TIME	NUMBER	Total elapsed time (in hundredths of a second) spent in evaluation of the rule set
FIRST_LOAD_TIME	DATE	First time the current cached copy of the rule set was loaded
LAST_LOAD_TIME	DATE	Last time the current cached copy of the rule set was loaded
LAST_LOADING_TIME	NUMBER	Total elapsed time (in hundredths of a second) spent to load the rule set the last time it was loaded
SHARABLE_MEM	NUMBER	Shared memory (in bytes) used by the rule set
RELOADS	NUMBER	Number of times the rule set object was reloaded in shared memory
INVALIDATIONS	NUMBER	Number of times the rule set object was invalidated
EVALUATIONS	NUMBER	Number of evaluations on the rule set
FIRST_HIT_EVALUATIONS	NUMBER	Number of evaluations on the rule set, with stop_on_first_hit set to TRUE
SIMPLE_RULES_ONLY_EVALUATIONS	NUMBER	Number of evaluations on the rule set, with simple_rules_only set to TRUE
SQL_FREE_EVALUATIONS	NUMBER	Number of evaluations on the rule set which did not internally issue SQL to evaluate rules
SQL_EXECUTIONS	NUMBER	Total number of SQL statements executed during evaluation of the rule set
CONDITIONS_PROCESSED	NUMBER	Total number of fast (indexed) conditions processed during evaluation of the rule set
TRUE_RULES	NUMBER	Total number of TRUE rules returned during evaluation of the rule set
MAYBE_RULES	NUMBER	Total number of MAYBE rules returned during evaluation of the rule set
VARIABLE_VALUE_FUNCTION_CALLS	NUMBER	Total number of calls made to user-defined functions to retrieve variable values (specified by the variable_value_function field in RE$VARIABLE_TYPE) made during evaluation of the rule set
VARIABLE_METHOD_FUNCTION_CALLS	NUMBER	Total number of calls made to user-defined functions to retrieve variable method values (specified by the variable_method_function field in RE$VARIABLE_TYPE) made during evaluation of the rule set
EVALUATION_FUNCTION_CALLS	NUMBER	Total number of calls made to user-defined evaluation functions (specified as the evaluation_function argument to the DBMS_RULE_ADM.CREATE_EVALUATION_CONTEXT procedure) made during evaluation of the rule set
RESULT_CACHE_HITS	NUMBER	Number of result cache hits across all the sessions evaluating this rule set
IS_RESULT_CACHE	VARCHAR2(3)	Indicates whether this rule set result can be cached (YES) or not (NO)
RESULT_CACHE_ELEMENTS	NUMBER	Number of elements cached within the result cache

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_RULE_ADM.CREATE_EVALUATION_CONTEXT procedure

9.209 V$RULE_SET_AGGREGATE_STATS

V$RULE_SET_AGGREGATE_STATS displays statistics aggregated over all evaluations on all rule sets. This view has a row for each type of statistic.

Column	Datatype	Description
NAME	VARCHAR2(80)	Name of the statistic: • rule set evaluations (all) - Total number of evaluations on all rule sets • rule set evaluations (first_hit) - Total number of evaluations on rule sets with stop_on_first_hit set to TRUE • rule set evaluations (simple_rules_only) - Total number of evaluations on rule sets with simple_rules_only set to TRUE • rule set evaluations (SQL free) - Total number of evaluations on rule sets which did not internally issue SQL to evaluate rules • rule set evaluation time (CPU) - Total CPU time (in hundredths of a second) spent in evaluations on rule sets • rule set evaluation time (elapsed) - Total elapsed time (in hundredths of a second) spent in evaluations on rule sets • rule set SQL executions - Total number of SQL statements executed during evaluations on rule sets • rule set conditions processed - Total number of fast (indexed) conditions processed during evaluations on rule sets • rule set true rules - Total number of TRUE rules returned during evaluations on rule sets • rule set maybe rules - Total number of MAYBE rules returned during evaluations on rule sets • rule set user function calls (variable value function) - Total number of calls made to user-defined functions to retrieve variable values (specified by the variable_value_function field in RE$VARIABLE_TYPE) made during evaluations on rule sets • rule set user function calls (variable method function) - Total number of calls made to user-defined functions to retrieve variable method values (specified by the variable_method_function field in RE$VARIABLE_TYPE) made during evaluations on rule sets • rule set user function calls (evaluation function) - Total number of calls made to user-defined evaluation functions (specified as the evaluation_function argument to the DBMS_RULE_ADM.CREATE_EVALUATION_CONTEXT procedure) made during evaluations on rule sets
VALUE	NUMBER	Statistic value
CON_ID	NUMBER	The ID of the container to which the data pertains. The CON_ID value in this view is always 0. The rows pertain to the entire CDB or to the non-CDB.

See Also:

Oracle Database PL/SQL Packages and Types Reference for more information about the DBMS_RULE_ADM.CREATE_EVALUATION_CONTEXT procedure

10

Dynamic Performance (V$) Views: V$SCHEDULER_IN_MEMORY_TRACE to V$ZONEMAP_USAGE_STATS

This chapter contains the dynamic performance views V$SCHEDULER_IN_MEMORY_TRACE to V$ZONEMAP_USAGE_STATS.

10.1 V$SCHEDULER_IN_MEMORY_TRACE

V$SCHEDULER_IN_MEMORY_TRACE displays in-memory trace and other information about all processes executing scheduler-related actions.

Column	Datatype	Description
SID	NUMBER	ID of the session generating scheduler trace
SERIAL#	NUMBER	Serial number of the session generating scheduler trace
USER#	NUMBER	Oracle identifier of the user generating scheduler trace
USERNAME	VARCHAR2(128)	Name of the user generating scheduler trace
PROCESSNAME	VARCHAR2(5)	Name of the process generating scheduler trace
PADDR	RAW(8)	Address of the process state object generating scheduler trace
SPID	VARCHAR2(24)	Operating system identifier of the process generating scheduler trace
PID	NUMBER	Oracle identifier of the process generating scheduler trace
TRACE_ST	CLOB	Scheduler trace generated by the process
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.2 V$SCHEDULER_RUNNING_JOBS

V$SCHEDULER_RUNNING_JOBS displays information about running Scheduler jobs.

Column	Datatype	Description
SESSION_ID	NUMBER	Identifier of the session running the Scheduler job
SESSION_SERIAL_NUM	NUMBER	Session serial number
JOB_ID	NUMBER	ID of the running Scheduler job
PADDR	RAW(4 | 8)	Process address
OS_PROCESS_ID	VARCHAR2(12)	Operating system process ID
SESSION_STAT_CPU	INTERVAL DAY(2) TO SECOND(3)	CPU statistics for the session
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire multitenant container database (CDB). This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.3 V$SECUREFILE_SHRINK

V$SECUREFILE_SHRINK displays information about SecureFiles Shrink tasks.

Column	Datatype	Description
LOB_OBJD	NUMBER	Database object number for the LOB segment
SHRINK_STATUS	VARCHAR2(40)	Status of the shrink task: • RUNNING • COMPLETE • ERROR
START_TIME	TIMESTAMP(3) WITH TIME ZONE	Date and time at which the shrink task started
END_TIME	TIMESTAMP(3) WITH TIME ZONE	Data and time at which the shrink task ended If SHRINK_STATUS = RUNNING, the value of this column is NULL.
BLOCKS_MOVED	NUMBER	Number of blocks relocated during the shrink task
BLOCKS_FREED	NUMBER	Number of blocks freed during the shrink task
BLOCKS_ALLOCATED	NUMBER	Number of blocks allocated from the tablespace during the shrink task This value includes only blocks allocated by the shrink process. Blocks allocated by other database processes are not included.
EXTENTS_ALLOCATED	NUMBER	Number of extents allocated from the tablespace during the shrink task This value includes only extents allocated by the shrink process. Extents allocated by other database processes are not included.
EXTENTS_FREED	NUMBER	Number of extents freed during the shrink task
EXTENTS_SEALED	NUMBER	Number of candidate extents selected and sealed during the shrink task

Column	Datatype	Description
AUTOMATIC	NUMBER	Indicates whether the shrink task was started automatically (1) or manually (0)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.4 V$SECUREFILE_TIMER

V$SECUREFILE_TIMER displays information about time taken (in microseconds) by functions of SecureFiles. These timer values are collected per session.

Column	Datatype	Description
NAME	VARCHAR2(50)	Name of the function
LAYER_ID	NUMBER	ID of the layer that the function belongs to: • 0 - Entire Subtree • 1 - Delta Updates • 2 - Write gather cache • 3 - Deduplication • 4 - Compression & Encryption • 5 - Inode • 6 - Space • 7 - Utilities • 8 - Row-Column Intersection
OWNTIME	NUMBER	Total time taken by the function
MAXTIME	NUMBER	Maximum time taken by a single call
MINTIME	NUMBER	Minimum time taken by a single call
INVOCATIONS	NUMBER	Number of times the function was invoked
LAYER_NAME	VARCHAR2(50)	Name of the layer to which the function belongs

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.5 V$SEGMENT_STATISTICS

V$SEGMENT_STATISTICS displays information about segment-level statistics.

Column	Datatype	Description
OWNER	VARCHAR2(128)	Owner of the object
OBJECT_NAME	VARCHAR2(128)	Name of the object
SUBOBJECT_NAME	VARCHAR2(128)	Name of the subobject
TABLESPACE_NAME	VARCHAR2(30)	Name of the table space to which the object belongs
TS#	NUMBER	Tablespace number
OBJ#	NUMBER	Dictionary object number of the object
DATAOBJ#	NUMBER	Data object number of the object
OBJECT_TYPE	VARCHAR2(18)	Type of the object
STATISTIC_NAME	VARCHAR2(64)	Name of the statistic
STATISTIC#	NUMBER	Statistic number
VALUE	NUMBER	Statistic value
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.6 V$SEGSTAT

V$SEGSTAT displays information about segment-level statistics.

Column	Datatype	Description
TS#	NUMBER	Tablespace number
OBJ#	NUMBER	Dictionary object number
DATAOBJ#	NUMBER	Data object number
STATISTIC_NAME	VARCHAR2(64)	Name of the statistic

Column	Datatype	Description
STATISTIC#	NUMBER	Statistic number
VALUE	NUMBER	Statistic value
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.7 V$SEGSTAT_NAME

V$SEGSTAT_NAME displays information about segment-level statistics properties.

Column	Datatype	Description
STATISTIC#	NUMBER	Statistic number
NAME	VARCHAR2(64)	Name of the statistic
SAMPLED	VARCHAR2(3)	Indicates whether the statistic was collected by sampling (YES) or not (NO)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.8 V$SERV_MOD_ACT_STATS

V$SERV_MOD_ACT_STATS displays the same set of performance statistics as V$SERVICE_STATS except for a specific combination of service/module/action names.

When aggregation is enabled for the service name, module, and action name, then this view provides the timing and work done for calls issued for the business transaction.

Column	Datatype	Description
AGGREGATION_TYPE	VARCHAR2(21)	Aggregation statistic type: • SERVICE_MODULE - Action value is NULL and the entry is an aggregate for all actions within a given module • SERVICE_MODULE_ACTION - Action value is NULL only for an empty action, and the aggregation is on the level of service/module/action
SERVICE_NAME	VARCHAR2(64)	Service name from V$SERVICES
MODULE	VARCHAR2(65)	Module name from DBA_ENABLED_AGGREGATIONS

Column	Datatype	Description
ACTION	VARCHAR2(65)	Action name from DBA_ENABLED_AGGREGATIONS
STAT_ID	NUMBER	Statistic identifier
STAT_NAME	VARCHAR2(64)	Derived statistic name from V$STATNAME and V$SESS_TIME_MODEL
VALUE	NUMBER	Cumulative value (in microseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SERVICE_STATS"
- "V$STATNAME"
- "V$SESS_TIME_MODEL"

10.9 V$SERVICE_DRAIN_TIMEOUT_ADVICE

V$SERVICE_DRAIN_TIMEOUT_ADVICE displays information about connection draining.

This view allows you monitor the performance of the draining process, so you can make informed decisions about tuning the drain timeout configuration.

Column	Datatype	Description
SERVICE_ID	NUMBER	Service ID
DRAIN_ORIGIN	VARCHAR2(12)	Draining origin • DISCONNECT - Sessions are being drained by the ALTER SYSTEM DISCONNECT SESSION statement • LOAD BALANCE - Sessions are being drained by Oracle RAC load balancing • PDB - Sessions are being drained by a PDB close • SERVICE - Sessions are being drained by stopping a service
LAST_DRAIN_TIMEOUT	NUMBER	Number of seconds since the last drain timeout
MARKED_TO_DRAIN	NUMBER	Number of sessions marked to drain
DRAINED	NUMBER	Number of sessions drained (includes session that exited on error)
DRAINED_BY_CLIENT	NUMBER	Number of sessions closed by the client during draining
DRAINED_BY_DATABASE	NUMBER	Number of sessions closed by the database during draining
PLANNED_FAILED_OVER	NUMBER	Number of sessions that failed over during draining

Column	Datatype	Description
DRAINED_INTERVAL01	NUMBER	Number of sessions drained in time interval 01 (Sessions drained in less than or equal to 1 second)
DRAINED_INTERVAL02	NUMBER	Number of sessions drained in time interval 02 (Sessions drained in less than or equal to 5 seconds)
DRAINED_INTERVAL03	NUMBER	Number of sessions drained in time interval 03 (Sessions drained in less than or equal to 10 seconds)
DRAINED_INTERVAL04	NUMBER	Number of sessions drained in time interval 04 (Sessions drained in less than or equal to 30 seconds)
DRAINED_INTERVAL05	NUMBER	Number of sessions drained in time interval 05 Sessions drained in less than or equal to 60 seconds)
DRAINED_INTERVAL06	NUMBER	Number of sessions drained in time interval 06 (Sessions drained in less than or equal to 120 seconds)
DRAINED_INTERVAL07	NUMBER	Number of sessions drained in time interval 07 (Sessions drained in less than or equal to 180 seconds)
DRAINED_INTERVAL08	NUMBER	Number of sessions drained in time interval 08 (Sessions drained in less than or equal to 300 seconds)
DRAINED_INTERVAL09	NUMBER	Number of sessions drained in time interval 09 (Sessions drained in less than or equal to 600 seconds)
DRAINED_INTERVAL10	NUMBER	Number of sessions drained in time interval 10 (Sessions drained in less than or equal to 1200 seconds)
DRAINED_INTERVAL11	NUMBER	Number of sessions drained in time interval 11 (Sessions drained in less than or equal to 3600 seconds (1 hour))
DRAINED_INTERVAL12	NUMBER	Number of sessions drained in time interval 12 (Sessions drained in less than or equal to 7200 seconds (2 hours))
DRAINED_INTERVAL13	NUMBER	Number of sessions drained in time interval 13 (Sessions drained in less than or equal to 14400 seconds (4 hours))
DRAINED_INTERVAL14	NUMBER	Number of sessions drained in time interval 14 (Sessions drained in greater than 14400 seconds (4 hours))
DRAINED_INTERVAL15	NUMBER	Reserved for internal use
DRAINED_INTERVAL16	NUMBER	Reserved for internal use
TERMINATED_BY_DRAIN_TIMEOUT	NUMBER	Number of sessions terminated at drain timeout
IDLE_IN_DRAIN	NUMBER	Number of sessions idle throughout drain timeout
ESTD_DRAIN_TIMEOUT_ADVICE	VARCHAR2(128)	Estimated drain time advice. Possible values include: • Not enough sessions are draining to compute a drain timeout estimation • Waiting for 90% of drained sessions in order to compute a drain timeout advice. • Estimated drain timeout is <advice_in_seconds> seconds Where <advice_in_seconds> is determined by using the number of drained sessions in each time interval

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.10 V$SERVICE_EVENT

V$SERVICE_EVENT displays aggregated wait counts and wait times for each wait statistic.

Column	Datatype	Description
SERVICE_NAME	VARCHAR2(64)	Service name from V$SERVICES
SERVICE_NAME_HASH	NUMBER	Service name hash from V$SERVICES
EVENT	VARCHAR2(64)	Name of the wait event; derived statistic name from V$EVENT_NAME **See Also:** " Oracle Wait Events"
EVENT_ID	NUMBER	Identifier of the wait event
TOTAL_WAITS	NUMBER	Total number of waits for the event by the service
TOTAL_TIMEOUTS	NUMBER	Total number of timeouts for the event by the service
TIME_WAITED	NUMBER	Total amount of time waited for the event by the service (in hundredths of a second)
AVERAGE_WAIT	NUMBER	Average amount of time waited for the event by the service (in hundredths of a second)
MAX_WAIT	NUMBER	Maximum amount of time waited for the event by the service (in hundredths of a second)
TIME_WAITED_MICRO	NUMBER	Total amount of time waited for the event by the service (in microseconds)
CPU	NUMBER	Total amount of CPU time consumed by the service while implementing the wait event itself (in microseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.11 V$SERVICE_REGION_METRIC

V$SERVICE_REGION_METRIC displays the metric values captured for the most recent 30-second intervals for the workload against each service region available on the database.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
SERVICE_ID	NUMBER	Service number (internal)
SERVICE_NETWORK_NAME	VARCHAR2(512)	Network name for the service
REGION_NAME	VARCHAR2(30)	Region name
CALLSPERSEC	NUMBER	Number of user calls per second to the services
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$CHUNK_METRIC"

10.12 V$SERVICE_STATS

V$SERVICE_STATS displays a minimal set of performance statistics. These call rate statistics are used for making run-time routing decisions, for tracking service levels, and for per-instance diagnostics per call rate. The elapsed timing for each call provides a relative value across instances for how well a node is processing SQL calls issued under a service name. When aggregation is enabled for the Service Name, then this view provides the timing and work done for calls issued for the whole service.

Column	Datatype	Description
SERVICE_NAME_HASH	NUMBER	Service name hash from V$SERVICES
SERVICE_NAME	VARCHAR2(64)	Service name from V$SERVICES
STAT_ID	NUMBER	Statistic identifier
STAT_NAME	VARCHAR2(64)	Derived statistic name from V$STATNAME and V$SESS_TIME_MODEL

Column	Datatype	Description
VALUE	NUMBER	For statistics that measure time (such as the DB CPU, background elapsed time, or parse time elapsed statistics), this column displays a cumulative value in microseconds. For other statistics that do not measure time (such as the db block changes, execute count, or logons cumulative statistics), this column displays the appropriate numeric value for the statistic.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SERVICES"
- "V$STATNAME"
- "V$SESS_TIME_MODEL"
- *Oracle Database Performance Tuning Guide* for more information about using database statistics to manage the performance of Oracle Database

10.13 V$SERVICE_WAIT_CLASS

V$SERVICE_WAIT_CLASS displays aggregated wait counts and wait times for each wait statistic.

An aggregation of these wait classes is used when thresholds are imported.

Column	Datatype	Description
SERVICE_NAME	VARCHAR2(64)	Service name from V$SERVICES
SERVICE_NAME_HASH	NUMBER	Service name hash from V$SERVICES
WAIT_CLASS_ID	NUMBER	Identifier of the wait class
WAIT_CLASS#	NUMBER	Number of the wait class
WAIT_CLASS	VARCHAR2(64)	Name of the wait class
TOTAL_WAITS	NUMBER	Total number waits from this wait class by the service
TIME_WAITED	NUMBER	Total amount of time spent in waits from this wait class by the service (in hundredths of a second)
TIME_WAITED_MICRO	NUMBER	Total amount of time spent in waits from this wait class by the service (in microseconds)

Column	Datatype	Description
CPU	NUMBER	Total amount of CPU time consumed by the service while implementing waits from this wait class (in microseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.14 V$SERVICEMETRIC

V$SERVICEMETRIC displays metric values measured on the most recent time interval period for services executing inside the database. Service metrics are measured in 5-second and 1-minute intervals.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin timestamp for the interval period
END_TIME	DATE	End timestamp for the interval period
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	Group ID for the service metric group
SERVICE_NAME_HASH	NUMBER	Service name hash
SERVICE_NAME	VARCHAR2(64)	Service name
CTMHASH	NUMBER	Service create timestamp hash value
ELAPSEDPERCALL	NUMBER	Elapsed time per call (in microseconds). This column is deprecated in favor of the DBTIMEPERCALL column.
CPUPERCALL	NUMBER	CPU time per call (in microseconds)
DBTIMEPERCALL	NUMBER	Elapsed time per call (in microseconds)
CALLSPERSEC	NUMBER	Number of user calls per second
DBTIMEPERSEC	NUMBER	Database time per second
GOODNESS	NUMBER	Indicates how attractive a given instance is with respect to processing the workload that is presented to the service. A lower number is better. This number is internally computed based on the GOAL (LONG or SHORT) that is specified for the particular service.
DELTA	NUMBER	Indicates the predicted increase in the goodness for every additional session that is routed to this instance
FLAGS	NUMBER	Flags that can be any of the following values: • 0x01 - Service is BLOCKED from accepting new connections • 0x02 - Service is VIOLATING the set threshold on some metric • 0x04 - Goodness is UNKNOWN

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.15 V$SERVICEMETRIC_HISTORY

V$SERVICEMETRIC_HISTORY displays a recent history of the metric values measured in predefined time interval periods for services executing inside the database. Service metrics are measured in 5-second and 1-minute intervals.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin timestamp for the interval period
END_TIME	DATE	End timestamp for the interval period
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	Group ID for the service metric group
SERVICE_NAME_HASH	NUMBER	Service name hash
SERVICE_NAME	VARCHAR2(64)	Service name
CTMHASH	NUMBER	Service create timestamp hash value
ELAPSEDPERCALL	NUMBER	Elapsed time per call (in microseconds). This column is deprecated in favor of the DBTIMEPERCALL column.
CPUPERCALL	NUMBER	CPU time per call (in microseconds)
DBTIMEPERCALL	NUMBER	Elapsed time per call (in microseconds)
CALLSPERSEC	NUMBER	Number of user calls per second
DBTIMEPERSEC	NUMBER	Database time per second
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.16 V$SERVICES

V$SERVICES displays information about the services in the database.

Column	Datatype	Description
SERVICE_ID	NUMBER	Service ID

Column	Datatype	Description
NAME	VARCHAR2(64)	Name of the service
NAME_HASH	NUMBER	Service name hash
NETWORK_NAME	VARCHAR2(512)	Network name
CREATION_DATE	DATE	Creation date
CREATION_DATE_HASH	NUMBER	Creation date hash
GOAL	VARCHAR2(12)	Runtime Load Balancing Goal being used to create run-time load balancing and connection load balancing advice: • NONE • SERVICE_TIME - Connections are balanced by response time • THROUGHPUT - Connections are balanced by throughput
DTP	VARCHAR2(1)	Indicates whether or not Distributed Transaction Processing is enabled for this service. When Distributed Transaction Processing is set to Y (YES), it means that the service is offered at exactly one instance at a time for XA affinity. Possible values: • Y - YES • N - NO
AQ_HA_NOTIFICATION	VARCHAR2(3)	Indicates whether FAN - Fast Application Notification for OCI connections is set (YES) or not (NO)
CLB_GOAL	VARCHAR2(5)	Connection load balancing goal used with statistics that are sent to the listeners to determine how new connections are distributed: • LONG - is using session count • SHORT - is using service time or throughput
COMMIT_OUTCOME	VARCHAR2(3)	For Transaction Guard and Database Native Transaction Guard, indicates whether the database service associated with the user session has the COMMIT_OUTCOME service attribute enabled (YES) or not (NO). This attribute applies on a per session basis and is set at connect time. When the value of this column is YES, the commit status is managed for all supported transaction types and the outcome of a COMMIT transaction is preserved after the COMMIT has executed. Refer to the COMMIT_OUTCOME_FASTPATH column to view the preferred method for preserving the commit outcome. **See Also:** *Oracle Database Development Guide* for information about preserving the commit outcome
RETENTION_TIME	NUMBER	For Transaction Guard and Database Native Transaction Guard, when COMMIT_OUTCOME = YES, this value indicates the amount of time (in seconds) that the commit outcome is retained in the database.
REPLAY_INITIATION_TIMEOUT	NUMBER	For Application Continuity, this option specifies the difference between the time (in seconds) of original execution of the first operation of a request and the time that the replay is ready to start after a successful reconnect. Application Continuity will not replay after the specified amount of time has passed. This option is intended to avoid the unintentional execution of a request when a system is recovered after a long period of time. The default is 5 minutes (300 seconds).

Column	Datatype	Description
SESSION_STATE_CONSISTENCY	VARCHAR2(128)	Describes how non-transactional is changed during a request. This parameter is considered only if failover_type is set to TRANSACTION for Application Continuity. Examples of session state are NLS settings, optimizer preferences, event settings, PL/SQL global variables, temporary tables, advanced queues, LOBs, and result cache. If non-transactional values change after the request starts, the default value of DYNAMIC should be set. Almost all applications should use DYNAMIC mode. If you are unsure, use DYNAMIC mode.
GLOBAL	VARCHAR2(3)	Indicates whether the service is global. A global service is managed by Global Service Manager (GSM) and can be provided by multiple databases that contain replicated data. Possible values: • YES: Indicates the service is global • NO: Indicates the service is not global
PDB	VARCHAR2(128)	Name of a pluggable database (PDB) associated with a given service. Will contain NULL if a database is a non-CDB or if the service is not associated with a PDB (that is, connecting to a CDB using this service will cause a user to connect to the root.)
SQL_TRANSLATION_PROFILE	VARCHAR2(261)	A non-NULL value specifies the initial SQL translation profile for subsequent database connections that use the service and do not specify a SQL translation profile. A NULL value has no effect.
MAX_LAG_TIME	VARCHAR2(128)	The maximum replication lag (in seconds) that is acceptable for a data replica to be used for providing the database service. Can only be specified for global services.
STOP_OPTION	VARCHAR2(128)	Stop option for sessions of this service for planned maintenance
FAILOVER_RESTORE	VARCHAR2(128)	Indicates whether sessions recover their commonly used session state (like NLS, schema) when they are failed over with TAF
DRAIN_TIMEOUT	NUMBER	Number of seconds to wait for sessions to be drained
TABLE_FAMILY_ID	NUMBER	Sharded table family ID associated with the service
PLACEMENT_TEMPLATE	VARCHAR2(64)	Reserved for future use

Column	Datatype	Description
COMMIT_OUTCOME_FASTPATH	VARCHAR2(3)	For Transaction Guard and Database Native Transaction Guard, when COMMIT_OUTCOME = YES, the value of this column indicates the preferred method for preserving the commit outcome. Possible values: • YES - Database Native Transaction Guard is used. Each transaction is assigned a unique transaction identifier (DB XID) in the database. The DB XID and status of the corresponding transaction are maintained persistently in a transaction table. Note that if COMMIT_OUTCOME = YES, then the value of COMMIT_OUTCOME_FASTPATH defaults to YES. • NO - Transaction Guard is used. A logical transaction ID (LTXID) is set for each user session at login and at each successful commit. LTXIDs are used only when the commit is not in the same round-trip to the database as the start of the transaction. Moreover, some transaction types, such as commit on success transactions, DDL transactions, and PL/SQL transactions, will continue to use LTXIDs in the same round-trip. When Transaction Guard is used, the outcome of a COMMIT transaction is known. If there is an outage, the application can use DBMS_APP_CONT.GET_LTXID_OUTCOME to return a reliable status for the last in-flight work. **See Also:** *Oracle Real Application Clusters Administration and Deployment Guide* for information about logical transaction IDs
TRUE_CACHE_SERVICE	VARCHAR2(64)	True Cache service associated with this database service
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.17 V$SES_OPTIMIZER_ENV

V$SES_OPTIMIZER_ENV displays the contents of the optimizer environment used by each session. When a new session is first created, it automatically inherits its optimizer environment from the optimizer environment defined at the instance level by V$SYS_OPTIMIZER_ENV. The value of certain parameters can be dynamically modified by issuing an ALTER SESSION statement.

Column	Datatype	Description
SID	NUMBER	Session identifier. This column can be used to join with V$SESSION on the SID column.
ID	NUMBER	Unique identifier of the parameter in the optimizer environment
NAME	VARCHAR2(40)	Name of the parameter
SQL_FEATURE	VARCHAR2(64)	Associated feature control ID

Column	Datatype	Description
ISDEFAULT	VARCHAR2(3)	Indicates whether the parameter is set to the default value (YES) or not (NO)
VALUE	VARCHAR2(25)	Value of the parameter for the session
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$SYS_OPTIMIZER_ENV"

10.18 V$SESS_IO

V$SESS_IO displays I/O statistics for each user session.

Column	Datatype	Description
SID	NUMBER	Session identifier
BLOCK_GETS	NUMBER	Block gets for this session
CONSISTENT_GETS	NUMBER	Consistent gets for this session
PHYSICAL_READS	NUMBER	Physical reads for this session
BLOCK_CHANGES	NUMBER	Block changes for this session
CONSISTENT_CHANGES	NUMBER	Consistent changes for this session
OPTIMIZED_PHYSICAL_READS	NUMBER	Number of physical reads from Database Smart Flash Cache for this session
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.19 V$SESS_TIME_MODEL

V$SESS_TIME_MODEL displays the session-accumulated time for various operations. The time reported is the total elapsed or CPU time (in microseconds). Any timed operation will buffer at most 5 seconds of time data. Specifically, this means that if a timed operation (such as SQL execution) takes a long period of time to perform, the data

published to this view is at most missing 5 seconds of the time accumulated for the operation. The time values are 8-byte integers and can therefore hold approximately 580,000 years of time before wrapping. Background process time is not included in a statistic value unless the statistic is specifically for background processes.

Column	Datatype	Description
SID	NUMBER	Session ID (same as in V$SESSION)
STAT_ID	NUMBER	Statistic identifier for the time statistic
STAT_NAME	VARCHAR2(64)	Name of the statistic (see Table 10-1)
VALUE	NUMBER	Amount of time (in microseconds) that the session has spent in this operation
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Table 10-1 V$SESS_TIME_MODEL and V$SYS_TIME_MODEL Statistics

Statistic Name	Description
DB time	Amount of elapsed time (in microseconds) spent performing Database user-level calls. This does not include the elapsed time spent on instance background processes such as PMON.
DB CPU	Amount of CPU time (in microseconds) spent on database user-level calls. This does not include the CPU time spent on instance background processes such as PMON.
background elapsed time	Amount of elapsed time (in microseconds) consumed by database background processes.
background CPU time	Amount of CPU time (in microseconds) consumed by database background processes.
sequence load elapsed time	Amount of elapsed time spent getting the next sequence number from the data dictionary. If a sequence is cached, then this is the amount of time spent replenishing the cache when it runs out. No time is charged when a sequence number is found in the cache. For non-cached sequences, some time will be charged for every nextval call.
parse time elapsed	Amount of elapsed time spent parsing SQL statements. It includes both soft and hard parse time.
hard parse elapsed time	Amount of elapsed time spent hard parsing SQL statements.
SQL execute elapsed time	Amount of elapsed time SQL statements are executing. Note that for select statements this also includes the amount of time spent performing fetches of query results.
connection management call elapsed time	Amount of elapsed time spent performing session connect and disconnect calls.
failed parse elapsed time	Amount of time spent performing SQL parses which ultimately fail with some parse error.
failed parse (out of shared memory) elapsed time	Amount of time spent performing SQL parses which ultimately fail with error ORA-04031.

Table 10-1 (Cont.) V$SESS_TIME_MODEL and V$SYS_TIME_MODEL Statistics

Statistic Name	Description
hard parse (sharing criteria) elapsed time	Amount of elapsed time spent performing SQL hard parses when the hard parse resulted from not being able to share an existing cursor in the SQL cache.
hard parse (bind mismatch) elapsed time	Amount of elapsed time spent performing SQL hard parses when the hard parse resulted from bind type or bind size mismatch with an existing cursor in the SQL cache.
PL/SQL execution elapsed time	Amount of elapsed time spent running the PL/SQL interpreter. This does not include time spent recursively executing/parsing SQL statements or time spent recursively executing the Java VM.
PL/SQL compilation elapsed time	Amount of elapsed time spent running the PL/SQL compiler.
inbound PL/SQL rpc elapsed time	Time inbound PL/SQL remote procedure calls have spent executing. It includes all time spent recursively executing SQL and JAVA, and therefore is not easily related to "PL/SQL execution elapsed time".
Java execution elapsed time	Amount of elapsed time spent running the Java VM. This does not include time spent recursively executing/parsing SQL statements or time spent recursively executing PL/SQL.
RMAN cpu time (backup/restore)	Amount of CPU time (in microseconds) spent in RMAN backup and restore operations.
repeated bind elapsed time	Amount of elapsed time spent giving new values to bind variables (rebinding).
OLAP engine elapsed time	Amount of time spent performing OLAP session transactions. This includes time spent on database user-level calls, SQL statement execution, and PL/SQL execution within the OLAP transaction.
OLAP engine CPU time	Amount of CPU time spent on OLAP session transactions. This includes time spent on database user-level calls, SQL statement execution, and PL/SQL execution within the OLAP transaction.

The relationships between the statistics listed in Table 10-1 form two trees in which all the time reported by a child in the tree is contained within the parent in the tree. The following are the relationship trees; the number is the level in the given tree.

```
1) background elapsed time
    2) background cpu time
          3) RMAN cpu time (backup/restore)
1) DB time
    2) DB CPU
    2) connection management call elapsed time
    2) sequence load elapsed time
    2) sql execute elapsed time
    2) parse time elapsed
          3) hard parse elapsed time
                4) hard parse (sharing criteria) elapsed time
                    5) hard parse (bind mismatch) elapsed time
          3) failed parse elapsed time
                4) failed parse (out of shared memory) elapsed time
    2) PL/SQL execution elapsed time
    2) inbound PL/SQL rpc elapsed time
    2) PL/SQL compilation elapsed time
    2) Java execution elapsed time
    2) repeated bind elapsed time
```

The relationship between a parent and a child in the tree indicates containment only. Keep the following in mind regarding the tree:

- Children do not necessarily add up to the parent.
- Children are not necessarily exclusive (that is, they may overlap).
- The union of children does not necessarily cover the whole of the parent.

> **See Also:**
>
> "V$SYS_TIME_MODEL"

10.20 V$SESSION

`V$SESSION` displays session information for each current session.

Column	Datatype	Description
`SADDR`	`RAW(4 | 8)`	Session address
`SID`	`NUMBER`	Session identifier
`SERIAL#`	`NUMBER`	Session serial number. Used to uniquely identify a session's objects. Guarantees that session-level commands are applied to the correct session objects if the session ends and another session begins with the same session ID.
`AUDSID`	`NUMBER`	Auditing session ID • If the database is configured for unified auditing, then this column displays the unified auditing session ID • If the database is configured for mixed mode auditing, then this column displays the traditional auditing session ID
`PADDR`	`RAW(4 | 8)`	Address of the process that owns the session
`USER#`	`NUMBER`	Oracle user identifier
`USERNAME`	`VARCHAR2(128)`	Oracle username
`COMMAND`	`NUMBER`	Command in progress (last statement parsed). You can find the command name for any value *n* returned in this `COMMAND` column by running this SQL query: `SELECT command_name FROM v$sqlcommand WHERE command_type = n;` A value of `0` in this `COMMAND` column means the command is not recorded in `V$SESSION`.
`OWNERID`	`NUMBER`	Identifier of the user who owns the migratable session; the column contents are invalid if the value is `2147483644` For operations using parallel worker processes, interpret this value as a 4-byte value. The low-order 2 bytes represent the session number and the high-order bytes represent the instance ID of the query coordinator.
`TADDR`	`VARCHAR2(16)`	Address of the transaction state object

Column	Datatype	Description
LOCKWAIT	VARCHAR2(16)	Address of the lock the session is waiting for; NULL if none
STATUS	VARCHAR2(8)	Status of the session: • ACTIVE - Session currently executing SQL • INACTIVE - Session which is inactive and either has no configured limits or has not yet exceeded the configured limits • KILLED - Session marked to be terminated • CACHED - Session temporarily cached for use by Oracle*XA • SNIPED - An inactive session that has exceeded some configured limits (for example, resource limits specified for the resource manager consumer group or idle_time specified in the user's profile). Such sessions will not be allowed to become active again.
SERVER	VARCHAR2(9)	Server type: • DEDICATED • SHARED • PSEUDO • POOLED • NONE
SCHEMA#	NUMBER	Schema user identifier
SCHEMANAME	VARCHAR2(128)	Schema user name
OSUSER	VARCHAR2(128)	Operating system client user name
PROCESS	VARCHAR2(24)	Operating system client process ID
MACHINE	VARCHAR2(64)	Operating system machine name
PORT	NUMBER	Client port number
TERMINAL	VARCHAR2(30)	Operating system terminal name
PROGRAM	VARCHAR2(84)	Operating system program name
TYPE	VARCHAR2(10)	Session type
SQL_ADDRESS	RAW(4 | 8)	Used with SQL_HASH_VALUE to identify the SQL statement that is currently being executed
SQL_HASH_VALUE	NUMBER	Used with SQL_ADDRESS to identify the SQL statement that is currently being executed
SQL_ID	VARCHAR2(13)	SQL identifier of the SQL statement that is currently being executed
SQL_CHILD_NUMBER	NUMBER	Child number of the SQL statement that is currently being executed
SQL_EXEC_START	DATE	Time when the execution of the SQL currently executed by this session started; NULL if SQL_ID is NULL
SQL_EXEC_ID	NUMBER	SQL execution identifier; NULL if SQL_ID is NULL or if the execution of that SQL has not yet started (see V$SQL_MONITOR)
PREV_SQL_ADDR	RAW(4 | 8)	Used with PREV_HASH_VALUE to identify the last SQL statement executed
PREV_HASH_VALUE	NUMBER	Used with SQL_HASH_VALUE to identify the last SQL statement executed
PREV_SQL_ID	VARCHAR2(13)	SQL identifier of the last SQL statement executed
PREV_CHILD_NUMBER	NUMBER	Child number of the last SQL statement executed

Column	Datatype	Description
PREV_EXEC_START	DATE	SQL execution start of the last executed SQL statement
PREV_EXEC_ID	NUMBER	SQL execution identifier of the last executed SQL statement
PLSQL_ENTRY_OBJECT_ID	NUMBER	Object ID of the top-most PL/SQL subprogram on the stack; NULL if there is no PL/SQL subprogram on the stack
PLSQL_ENTRY_SUBPROGRAM_ID	NUMBER	Subprogram ID of the top-most PL/SQL subprogram on the stack; NULL if there is no PL/SQL subprogram on the stack
PLSQL_OBJECT_ID	NUMBER	Object ID of the currently executing PL/SQL subprogram; NULL if executing SQL
PLSQL_SUBPROGRAM_ID	NUMBER	Subprogram ID of the currently executing PL/SQL object; NULL if executing SQL
MODULE	VARCHAR2(64)	Name of the currently executing module as set by calling the DBMS_APPLICATION_INFO.SET_MODULE procedure
MODULE_HASH	NUMBER	Hash value of the MODULE column
ACTION	VARCHAR2(64)	Name of the currently executing action as set by calling the DBMS_APPLICATION_INFO.SET_ACTION procedure
ACTION_HASH	NUMBER	Hash value of the ACTION column
CLIENT_INFO	VARCHAR2(64)	Information set by the DBMS_APPLICATION_INFO.SET_CLIENT_INFO procedure
FIXED_TABLE_SEQUENCE	NUMBER	This contains a number that increases every time the session completes a call to the database and there has been an intervening select from a dynamic performance table. This column can be used by performance monitors to monitor statistics in the database. Each time the performance monitor looks at the database, it only needs to look at sessions that are currently active or have a higher value in this column than the highest value that the performance monitor saw the last time. All the other sessions have been idle since the last time the performance monitor looked at the database.
ROW_WAIT_OBJ#	NUMBER	Object ID for the table containing the row specified in ROW_WAIT_ROW#
ROW_WAIT_FILE#	NUMBER	Identifier for the data file containing the row specified in ROW_WAIT_ROW#. This column is valid only if the session is currently waiting for another transaction to commit and the value of ROW_WAIT_OBJ# is not -1.
ROW_WAIT_BLOCK#	NUMBER	Identifier for the block containing the row specified in ROW_WAIT_ROW#. This column is valid only if the session is currently waiting for another transaction to commit and the value of ROW_WAIT_OBJ# is not -1.
ROW_WAIT_ROW#	NUMBER	Current row being locked. This column is valid only if the session is currently waiting for another transaction to commit and the value of ROW_WAIT_OBJ# is not -1.
TOP_LEVEL_CALL#	NUMBER	Oracle top level call number
LOGON_TIME	DATE	Time of logon

Column	Datatype	Description
LAST_CALL_ET	NUMBER	If the session STATUS is currently ACTIVE, then the value represents the elapsed time (in seconds) since the session has become active. If the session STATUS is currently INACTIVE, then the value represents the elapsed time (in seconds) since the session has become inactive.
PDML_ENABLED	VARCHAR2(3)	This column has been replaced by the PDML_STATUS column
FAILOVER_TYPE	VARCHAR2(13)	Indicates whether failover is enabled for this session: • NONE - Failover is disabled for this session. • SESSION - Transparent application failover (TAF) is enabled for this session and the client can fail over its session following a disconnect. • SELECT - TAF is enabled for this session and the client can fail over queries. The application must not set session state after the initial setup. (Transactions are not included at failover.) • TRANSACTION - Application Continuity (AC) is enabled for this session. This feature is available with the Oracle Real Application Clusters (RAC), Oracle RAC One Node, and Oracle Active Data Guard options. AC hides outages from end users and applications by recovering the database sessions following recoverable outages and planned maintenance. • AUTO - Transparent Application Continuity (TAC) is enabled for this session. This feature is the automated version of Application Continuity (AC) that makes decisions on your behalf. TAC is on by default for Oracle Autonomous Database Cloud and can also be on by default for your applications. **See Also:** • *Oracle Database Net Services Administrator's Guide* for more information on TAF • *Oracle Real Application Clusters Administration and Deployment Guide* for more information on AC • *Oracle Real Application Clusters Administration and Deployment Guide* for more information on TAC
FAILOVER_METHOD	VARCHAR2(10)	Indicates the transparent application failover method for the session: • NONE - Failover is disabled for this session • BASIC - Client itself reconnects following a disconnect • PRECONNECT - Backup instance can support all connections from every instance for which it is backed up
FAILED_OVER	VARCHAR2(3)	Indicates whether the session is running in failover mode and failover has occurred (YES) or not (NO)
RESOURCE_CONSUMER_GROUP	VARCHAR2(32)	Name of the session's current resource consumer group
PDML_STATUS	VARCHAR2(8)	If ENABLED, the session is in a PARALLEL DML enabled mode. If DISABLED, PARALLEL DML enabled mode is not supported for the session. If FORCED, the session has been altered to force PARALLEL DML.

Column	Datatype	Description
PDDL_STATUS	VARCHAR2(8)	If ENABLED, the session is in a PARALLEL DDL enabled mode. If DISABLED, PARALLEL DDL enabled mode is not supported for the session. If FORCED, the session has been altered to force PARALLEL DDL.
PQ_STATUS	VARCHAR2(8)	If ENABLED, the session is in a PARALLEL QUERY enabled mode. If DISABLED, PARALLEL QUERY enabled mode is not supported for the session. If FORCED, the session has been altered to force PARALLEL QUERY.
CURRENT_QUEUE_DURATION	NUMBER	If queued (1), the current amount of time the session has been queued. If not currently queued, the value is 0.
CLIENT_IDENTIFIER	VARCHAR2(64)	Client identifier of the session
BLOCKING_SESSION_STATUS	VARCHAR2(11)	This column provides details on whether there is a blocking session: • VALID - there is a blocking session, and it is identified in the BLOCKING_INSTANCE and BLOCKING_SESSION columns • NO HOLDER - there is no session blocking this session • NOT IN WAIT - this session is not in a wait • UNKNOWN - the blocking session is unknown
BLOCKING_INSTANCE	NUMBER	Instance identifier of the blocking session. This column is valid only if BLOCKING_SESSION_STATUS has the value VALID.
BLOCKING_SESSION	NUMBER	Session identifier of the blocking session. This column is valid only if BLOCKING_SESSION_STATUS has the value VALID.
FINAL_BLOCKING_SESSION_STATUS	VARCHAR2(11)	The final blocking session is the final element in the wait chain constructed by following the sessions that are blocked by one another starting with this session. In the case of a cyclical wait chain, one of the sessions in the wait chain will be chosen as the final blocker. This column provides details on whether there is a final blocking session: • VALID - there is a final blocking session and it is identified in the FINAL_BLOCKING_INSTANCE and FINAL_BLOCKING_SESSION columns • NO HOLDER - there is no session blocking this session • NOT IN WAIT - this session is not in a wait • UNKNOWN - the final blocking session is unknown
FINAL_BLOCKING_INSTANCE	NUMBER	Instance identifier of the final blocking session. This column is valid only if FINAL_BLOCKING_SESSION_STATUS has the value VALID.
FINAL_BLOCKING_SESSION	NUMBER	Session identifier of the blocking session. This column is valid only if FINAL_BLOCKING_SESSION_STATUS has the value VALID.
SEQ#	NUMBER	A number that uniquely identifies the current or last wait (incremented for each wait)
EVENT#	NUMBER	If the session is currently waiting, then the number of the resource or event for which the session is waiting. If the session is not in a wait, then the number of the resource or event for which the session most recently waited.

Column	Datatype	Description
EVENT	VARCHAR2(64)	If the session is currently waiting, then the resource or event for which the session is waiting. If the session is not in a wait, then the resource or event for which the session most recently waited. **See Also:** " Oracle Wait Events"
P1TEXT	VARCHAR2(64)	Description of the first wait event parameter
P1	NUMBER	First wait event parameter (in decimal)
P1RAW	RAW(8)	First wait event parameter (in hexadecimal)[1]
P2TEXT	VARCHAR2(64)	Description of the second wait event parameter
P2	NUMBER	Second wait event parameter (in decimal)
P2RAW	RAW(8)	Second wait event parameter (in hexadecimal)[1]
P3TEXT	VARCHAR2(64)	Description of the third wait event parameter
P3	NUMBER	Third wait event parameter (in decimal)
P3RAW	RAW(8)	Third wait event parameter (in hexadecimal)[1]
WAIT_CLASS_ID	NUMBER	Identifier of the class of the wait event
WAIT_CLASS#	NUMBER	Number of the class of the wait event
WAIT_CLASS	VARCHAR2(64)	Name of the class of the wait event
WAIT_TIME	NUMBER	If the session is currently waiting, then the value is 0. If the session is not in a wait, then the value is as follows: • > 0 - Value is the duration of the last wait in hundredths of a second • -1 - Duration of the last wait was less than a hundredth of a second • -2 - Parameter TIMED_STATISTICS was set to false This column has been deprecated in favor of the columns WAIT_TIME_MICRO and STATE.
SECONDS_IN_WAIT	NUMBER	If the session is currently waiting, then the value is the amount of time waited for the current wait. If the session is not in a wait, then the value is the amount of time since the start of the last wait. This column has been deprecated in favor of the columns WAIT_TIME_MICRO and TIME_SINCE_LAST_WAIT_MICRO.
STATE	VARCHAR2(19)	Wait state: • WAITING - Session is currently waiting • WAITED UNKNOWN TIME - Duration of the last wait is unknown; this is the value when the parameter TIMED_STATISTICS is set to false • WAITED SHORT TIME - Last wait was less than a hundredth of a second • WAITED KNOWN TIME - Duration of the last wait is specified in the WAIT_TIME column
WAIT_TIME_MICRO	NUMBER	Amount of time waited (in microseconds). If the session is currently waiting, then the value is the time spent in the current wait. If the session is currently not in a wait, then the value is the amount of time waited in the last wait.

Column	Datatype	Description
TIME_REMAINING_MICRO	NUMBER	Value is interpreted as follows: • > 0 - Amount of time remaining for the current wait (in microseconds) • 0 - Current wait has timed out • -1 - Session can indefinitely wait in the current wait • NULL - Session is not currently waiting
TOTAL_TIME_WAITED_MICRO	NUMBER	Total time for the current wait (in microseconds) A wait includes code within its beginning and end that can encounter other waits as part of its implementation. For example, a wait might need to acquire a latch to check state to determine when the wait is satisfied, and the latch itself might enter a wait. In this case, when the latch wait ends and returns to the outer wait, the latch time is included in the value of this column, while the value of WAIT_TIME_MICRO is reset to start after the latch wait.
HEUR_TIME_WAITED_MICRO	NUMBER	Heuristic wait time (in microseconds) This value is calculated by attempting to group sequential waits that appear to be the same.
TIME_SINCE_LAST_WAIT_MICRO	NUMBER	Time elapsed since the end of the last wait (in microseconds). If the session is currently in a wait, then the value is 0.
SERVICE_NAME	VARCHAR2(64)	Service name of the session
SQL_TRACE	VARCHAR2(8)	Indicates whether SQL tracing is enabled (ENABLED) or disabled (DISABLED)
SQL_TRACE_WAITS	VARCHAR2(5)	Indicates whether wait tracing is enabled (TRUE) or not (FALSE)
SQL_TRACE_BINDS	VARCHAR2(5)	Indicates whether bind tracing is enabled (TRUE) or not (FALSE)
SQL_TRACE_PLAN_STATS	VARCHAR2(10)	Frequency at which row source statistics are dumped in the trace files for each cursor: • never • first_execution • all_executions
SESSION_EDITION_ID	NUMBER	Shows the value that, in the session, would be reported by sys_context('USERENV', 'SESSION_EDITION_ID')
CREATOR_ADDR	RAW(4 | 8)	Address of the creating process or circuit
CREATOR_SERIAL#	NUMBER	Serial number of the creating process or circuit
ECID	VARCHAR2(64)	Execution context identifier (sent by Application Server)
SQL_TRANSLATION_PROFILE_ID	NUMBER	Object number of the SQL translation profile
PGA_TUNABLE_MEM	NUMBER	The amount of tunable PGA memory (in bytes). Untunable memory is PGA_ALLOC_MEM from V$PROCESS minus PGA_TUNABLE_MEM from V$SESSION.
SHARD_DDL_STATUS	VARCHAR2(8)	Indicates whether shard DDL is enabled in the current session (ENABLED) or not (DISABLED). This value is only relevant for the shard catalog database.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
EXTERNAL_NAME	VARCHAR2(1024)	External name of the database user. For enterprise users, returns the Oracle Internet Directory DN.
PLSQL_DEBUGGER_CONNECTED	VARCHAR2(5)	Indicates whether the session is connected to a PL/SQL debugger (TRUE) or not (FALSE)
DRAIN_STATUS	VARCHAR2(8)	Draining status • DRAINING • NONE
DRAIN_DEADLINE	TIMESTAMP(6) WITH TIME ZONE	Drain deadline for the session
DRAIN_ORIGIN	VARCHAR2(12)	Draining origin • DISCONNECT - The session is being drained by the ALTER SYSTEM DISCONNECT SESSION statement • LOAD BALANCE - The session is being drained by Oracle RAC load balancing • PDB - The session is being drained by a PDB close • SERVICE - The session is being drained by stopping a service • NONE - The session is not being drained (DRAIN_STATUS = NONE)

[1] The P1RAW, P2RAW, and P3RAW columns display the same values as the P1, P2, and P3 columns, except that the numbers are displayed in hexadecimal.

See Also:

- *Oracle Database Performance Tuning Guide* for an example of using V$SESSION to help identify an object that is waiting for buffer busy waits
- *Oracle Database Performance Tuning Guide* for an example of using V$SESSION to determine which sessions are waiting for I/O
- *Oracle Database PL/SQL Packages and Types Reference* for more information on the DBMS_APPLICATION_INFO package

10.21 V$SESSION_BLOCKERS

V$SESSION_BLOCKERS displays the blocker sessions for each blocked session. Each row represents a blocked and blocker session pair. If a session is blocked by multiple sessions there will be multiple rows for that blocked session. The maximum number of blocker sessions displayed for a single blocked session is 30. If a session is not blocked by other sessions, then there will be no row in this view for that session.

Column	Datatype	Description
SID	NUMBER	Blocked session's Oracle session identifier
SESS_SERIAL#	NUMBER	Blocked session's Oracle session serial number
WAIT_ID	NUMBER	A number identifying the wait for the blocked session
WAIT_EVENT	NUMBER	Resource or event number for which the blocked session is waiting
WAIT_EVENT_TEXT	VARCHAR2(64)	Resource or event for which the blocked session is waiting
BLOCKER_INSTANCE_ID	NUMBER	Blocker session's instance identifier
BLOCKER_SID	NUMBER	Blocker session's Oracle session identifier
BLOCKER_SESS_SERIAL#	NUMBER	Blocker session's Oracle session serial number
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.22 V$SESSION_CONNECT_INFO

V$SESSION_CONNECT_INFO displays information about network connections for all currently logged in sessions.

Column	Datatype	Description
SID	NUMBER	Session identifier (can be used to join this view with V$SESSION)
SERIAL#	NUMBER	Session serial number. Used to uniquely identify a session's objects. Guarantees that session-level commands are applied to the correct session objects if the session ends and another session begins with the same session ID. (Can be used to join this view with V$SESSION.)
AUTHENTICATION_TYPE	VARCHAR2(26)	How the user was authenticated: • DATABASE - Username/password authentication • OS - Operating system external user authentication • NETWORK - Network protocol or ANO authentication • PROXY - OCI proxy connection authentication • SERVER • PASSWORD • EXTERNAL ADAPTERS • INTERNAL • GLOBAL • EXTERNAL • PASSWORD BASED GLOBAL USER
OSUSER	VARCHAR2(128)	External username for this database user
NETWORK_SERVICE_BANNER	VARCHAR2(4000)	Product banners for each Oracle Net service used for this connection (one row per banner)

Column	Datatype	Description
CLIENT_CHARSET	VARCHAR2(40)	Client character set as specified in the NLS_LANG environment variable or in the OCIEnvNlsCreate() call; Unknown if the Oracle client is older than release 11.1 or the connection is through the JDBC thin driver
CLIENT_CONNECTION	VARCHAR2(13)	Client server connection flags: • Heterogeneous • Homogeneous
CLIENT_OCI_LIBRARY	VARCHAR2(27)	OCI client library: • Home-based • Full Instant Client • Light Weight Instant Client • OCI • Unknown
CLIENT_VERSION	VARCHAR2(40)	Client library version number
CLIENT_DRIVER	VARCHAR2(30)	Client driver name
CLIENT_LOBATTR	VARCHAR2(23)	Client LOB flags: • Client Temp Lob Rfc On • Client Temp Lob Rfc Off
CLIENT_REGID	NUMBER	Query cache registration ID sent by the client
CLIENT_CONNECTION_STRING	VARCHAR2(4000)	Connection string used to establish the connection
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$SESSION"

10.23 V$SESSION_CURSOR_CACHE

V$SESSION_CURSOR_CACHE displays information on cursor usage for the current session.

> **Note:**
>
> The V$SESSION_CURSOR_CACHE view is not a measure of the effectiveness of the SESSION_CACHED_CURSORS initialization parameter.

Column	Datatype	Description
MAXIMUM	NUMBER	Maximum number of cursors to cache. Once you hit this number, some cursors will need to be closed in order to open more. The value in this column is derived from the initialization parameter SESSION_CACHED_CURSORS.
COUNT	NUMBER	Current number of cursors (whether they are in use or not)
OPENS	NUMBER	Cumulative total of cursor opens minus one. This is because the cursor that is currently open and being used for this query is not counted in the OPENS statistic.
HITS	NUMBER	Cumulative total of cursor open hits
HIT_RATIO	NUMBER	Ratio of the number of times an open cursor was found divided by the number of times a cursor was sought
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"SESSION_CACHED_CURSORS"

10.24 V$SESSION_EVENT

V$SESSION_EVENT displays information on waits for an event by a session. Note that the TIME_WAITED and AVERAGE_WAIT columns will contain a value of zero on those platforms that do not support a fast timing mechanism. If you are running on one of these platforms and you want this column to reflect true wait times, then you must set TIMED_STATISTICS to true in the parameter file; doing this will have a small negative effect on system performance.

See Also:

"TIMED_STATISTICS"

Column	Datatype	Description
SID	NUMBER	Session identifier
EVENT	VARCHAR2(64)	Name of the wait event; derived statistic name from V$EVENT_NAME **See Also:** " Oracle Wait Events"
TOTAL_WAITS	NUMBER	Total number of waits for the event by the session
TOTAL_TIMEOUTS	NUMBER	Total number of timeouts for the event by the session

Column	Datatype	Description
TIME_WAITED	NUMBER	Total amount of time waited for the event by the session (in hundredths of a second)
AVERAGE_WAIT	NUMBER	Average amount of time waited for the event by the session (in hundredths of a second)
MAX_WAIT	NUMBER	Maximum amount of time waited for the event by the session (in hundredths of a second)
TIME_WAITED_MICRO	NUMBER	Total amount of time waited for the event by the session (in microseconds)
CPU	NUMBER	Total amount of CPU time consumed by the session while implementing the wait event itself (in microseconds)
EVENT_ID	NUMBER	Identifier of the wait event
WAIT_CLASS_ID	NUMBER	Identifier of the wait class of the wait event
WAIT_CLASS#	NUMBER	Number of the wait class of the wait event
WAIT_CLASS	VARCHAR2(64)	Name of the wait class of the wait event
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.25 V$SESSION_FIX_CONTROL

V$SESSION_FIX_CONTROL displays information about Fix Control (enabled/disabled) for the current session.

Column	Datatype	Description
SESSION_ID	NUMBER	Session identifier (can be used to join this view with V$SESSION)
BUGNO	NUMBER	Bug number (as fix control identifier)
VALUE	NUMBER	Current value set for the fix control
SQL_FEATURE	VARCHAR2(64)	Feature control ID
DESCRIPTION	VARCHAR2(64)	Description of the fix control
OPTIMIZER_FEATURE_ENABLE	VARCHAR2(25)	Version on (and after) which the fix is enabled by default
EVENT	NUMBER	Event formerly used to control the fix
IS_DEFAULT	NUMBER	Indicates whether the current value is the same as the default (1) or not (0)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.26 V$SESSION_LONGOPS

V$SESSION_LONGOPS displays the status of various operations that run for longer than 6 seconds (in absolute time). These operations currently include many backup and recovery functions, statistics gathering, and query execution, and more operations are added for every Oracle release.
To monitor query execution progress, you must be using the cost-based optimizer and you must:

- Set the TIMED_STATISTICS or SQL_TRACE parameters to true
- Gather statistics for your objects with the DBMS_STATS package

You can add information to this view about application-specific long-running operations by using the DBMS_APPLICATION_INFO.SET_SESSION_LONGOPS procedure.

Column	Datatype	Description
SID	NUMBER	Identifier of the session processing the long-running operation. If multiple sessions are cooperating in the long-running operation, then SID corresponds to the main session.
SERIAL#	NUMBER	Serial number of the session processing the long-running operation. If multiple sessions are cooperating in the long-running operation, then SERIAL# corresponds to the main session. SERIAL# is used to uniquely identify a session's objects. Guarantees that session-level commands are applied to the correct session objects if the session ends and another session begins with the same session ID.
OPNAME	VARCHAR2(64)	Brief description of the operation
TARGET	VARCHAR2(64)	Object on which the operation is carried out
TARGET_DESC	VARCHAR2(32)	Description of the target
SOFAR	NUMBER	Units of work done so far for the operation specified in the OPNAME column
TOTALWORK	NUMBER	Total units of work for the operation specified in the OPNAME column
UNITS	VARCHAR2(32)	Units of measurement
START_TIME	DATE	Starting time of the operation
LAST_UPDATE_TIME	DATE	Time when statistics were last updated for the operation
TIMESTAMP	DATE	Timestamp specific to the operation
TIME_REMAINING	NUMBER	Estimate (in seconds) of time remaining for the operation to complete

Column	Datatype	Description
ELAPSED_SECONDS	NUMBER	Number of elapsed seconds from the start of the operations
CONTEXT	NUMBER	Context
MESSAGE	VARCHAR2(512)	Statistics summary message
USERNAME	VARCHAR2(30)	User ID of the user performing the operation
SQL_ADDRESS	RAW(4 | 8)	Used with the value of the SQL_HASH_VALUE column to identify the SQL statement associated with the operation
SQL_HASH_VALUE	NUMBER	Used with the value of the SQL_ADDRESS column to identify the SQL statement associated with the operation
SQL_ID	VARCHAR2(13)	SQL identifier of the SQL statement associated with the long operation, if any
SQL_PLAN_HASH_VALUE	NUMBER	SQL plan hash value; NULL if SQL_ID is NULL
SQL_EXEC_START	DATE	Time when the execution of the SQL started; NULL if SQL_ID is NULL
SQL_EXEC_ID	NUMBER	SQL execution identifier (see V$SQL_MONITOR)
SQL_PLAN_LINE_ID	NUMBER	SQL plan line ID corresponding to the long operation; NULL if the long operation is not associated with a line of the execution plan
SQL_PLAN_OPERATION	VARCHAR2(30)	Plan operation name; NULL if SQL_PLAN_LINE_ID is NULL
SQL_PLAN_OPTIONS	VARCHAR2(30)	Plan operation options; NULL if SQL_PLAN_LINE_ID is NULL
QCSID	NUMBER	Session identifier of the parallel coordinator
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "TIMED_STATISTICS"
- "SQL_TRACE"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLICATION_INFO.SET_SESSION_LONGOPS procedure
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_STATS package

10.27 V$SESSION_OBJECT_CACHE

V$SESSION_OBJECT_CACHE displays object cache statistics for the current user session on the local server (instance).

Column	Datatype	Description
PINS	NUMBER	Number of object pins or look-ups in the cache
HITS	NUMBER	Number of object pins that found the object already in the cache
TRUE_HITS	NUMBER	Number of object pins that found the object already in the cache and in the desired state (thus, not requiring refresh from the database)
HIT_RATIO	NUMBER	Ratio of HITS / PINS
TRUE_HIT_RATIO	NUMBER	Ratio of TRUE_HITS/PINS
OBJECT_REFRESHES	NUMBER	Number of objects in the cache that were refreshed with a new value from the database
CACHE_REFRESHES	NUMBER	Number of times the whole cache (all objects) were refreshed
OBJECT_FLUSHES	NUMBER	Number of objects in the cache that were flushed to the database
CACHE_FLUSHES	NUMBER	Number of times the whole cache (all objects) were flushed to the database
CACHE_SHRINKS	NUMBER	Number of times the cache was shrunk to the optimal size
CACHED_OBJECTS	NUMBER	Number of objects currently cached
PINNED_OBJECTS	NUMBER	Number of objects currently pinned
CACHE_SIZE	NUMBER	Current size of the cache (in bytes)
OPTIMAL_SIZE	NUMBER	Optimal size of the cache (in bytes)
MAXIMUM_SIZE	NUMBER	Maximum size of the cache (in bytes)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.28 V$SESSION_WAIT

V$SESSION_WAIT displays the current or last wait for each session.

Column	Datatype	Description
SID	NUMBER	Session identifier; maps to V$SESSION.SID
SEQ#	NUMBER	A number that uniquely identifies the current or last wait (incremented for each wait)
EVENT	VARCHAR2(64)	If the session is currently waiting, then the resource or event for which the session is waiting. If the session is not in a wait, then the resource or event for which the session most recently waited. **See Also:** " Oracle Wait Events"
P1TEXT	VARCHAR2(64)	Description of the first wait event parameter
P1	NUMBER	First wait event parameter (in decimal)
P1RAW	RAW(8)	First wait event parameter (in hexadecimal)[1]
P2TEXT	VARCHAR2(64)	Description of the second wait event parameter

Column	Datatype	Description
P2	NUMBER	Second wait event parameter (in decimal)
P2RAW	RAW(8)	Second wait event parameter (in hexadecimal)[1]
P3TEXT	VARCHAR2(64)	Description of the third wait event parameter
P3	NUMBER	Third wait event parameter (in decimal)
P3RAW	RAW(8)	Third wait event parameter (in hexadecimal)[1]
WAIT_CLASS_ID	NUMBER	Identifier of the class of the wait event
WAIT_CLASS#	NUMBER	Number of the class of the wait event
WAIT_CLASS	VARCHAR2(64)	Name of the class of the wait event
WAIT_TIME	NUMBER	If the session is currently waiting, then the value is 0. If the session is not in a wait, then the value is as follows: • > 0 - Value is the duration of the last wait in hundredths of a second • -1 - Duration of the last wait was less than a hundredth of a second • -2 - Parameter TIMED_STATISTICS was set to false This column has been deprecated in favor of the columns WAIT_TIME_MICRO and STATE.
SECONDS_IN_WAIT	NUMBER	If the session is currently waiting, then the value is the amount of time waited for the current wait. If the session is not in a wait, then the value is the amount of time since the start of the last wait. This column has been deprecated in favor of the columns WAIT_TIME_MICRO and TIME_SINCE_LAST_WAIT_MICRO.
STATE	VARCHAR2(19)	Wait state: • WAITING - Session is currently waiting • WAITED UNKNOWN TIME - Duration of the last wait is unknown; this is the value when the parameter TIMED_STATISTICS is set to false • WAITED SHORT TIME - Last wait was less than a hundredth of a second • WAITED KNOWN TIME - Duration of the last wait is specified in the WAIT_TIME column
WAIT_TIME_MICRO	NUMBER	Amount of time waited (in microseconds). If the session is currently waiting, then the value is the time spent in the current wait. If the session is currently not in a wait, then the value is the amount of time waited in the last wait.
TIME_REMAINING_MICRO	NUMBER	Value is interpreted as follows: • > 0 - Amount of time remaining for the current wait (in microseconds) • 0 - Current wait has timed out • -1 - Session can indefinitely wait in the current wait • NULL - Session is not currently waiting

Column	Datatype	Description
TOTAL_TIME_WAITED_MICRO	NUMBER	Total time for the current wait (microseconds) A wait includes code within its beginning and end that can encounter other waits as part of its implementation. For example, a wait might need to acquire a latch to check state to determine when the wait is satisfied, and the latch itself might enter a wait. In this case, when the latch wait ends and returns to the outer wait, the latch time is included in the value of this column, while the value of WAIT_TIME_MICRO is reset to start after the latch wait.
HEUR_TIME_WAITED_MICRO	NUMBER	Heuristic wait time (microseconds) This value is calculated by attempting to group sequential waits that appear to be the same.
TIME_SINCE_LAST_WAIT_MICRO	NUMBER	Time elapsed since the end of the last wait (microseconds). If the session is currently in a wait, then the value is 0.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

[1] The P1RAW, P2RAW, and P3RAW columns display the same values as the P1, P2, and P3 columns, except that the numbers are displayed in hexadecimal.

> **See Also:**
>
> "TIMED_STATISTICS" and " Oracle Wait Events"

10.29 V$SESSION_WAIT_CLASS

V$SESSION_WAIT_CLASS displays the time spent in various wait event operations on a per-session basis.

Column	Datatype	Description
SID	NUMBER	Session identifier
SERIAL#	NUMBER	Serial number
WAIT_CLASS_ID	NUMBER	Identifier of the wait class
WAIT_CLASS#	NUMBER	Number of the wait class
WAIT_CLASS	VARCHAR2(64)	Name of the wait class
TOTAL_WAITS	NUMBER	Total number waits from this wait class by the session
TIME_WAITED	NUMBER	Total amount of time spent in waits from this wait class by the session (in hundredths of a second)
TIME_WAITED_MICRO	NUMBER	Total amount of time spent in waits from this wait class by the session (in microseconds)

Column	Datatype	Description
CPU	NUMBER	Total amount of CPU time consumed by the session while implementing waits from this wait class (in microseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.30 V$SESSION_WAIT_HISTORY

V$SESSION_WAIT_HISTORY displays the last 10 wait events for each active session.

Column	Datatype	Description
SID	NUMBER	Session identifier
SEQ#	NUMBER	Sequence of wait events; 1 is the most recent
EVENT#	NUMBER	Event number
EVENT	VARCHAR2(64)	Resource or event for which the session is waiting
P1TEXT	VARCHAR2(64)	Description of the first wait event parameter
P1	NUMBER	First wait event parameter (in decimal)
P2TEXT	VARCHAR2(64)	Description of the second wait event parameter
P2	NUMBER	Second wait event parameter (in decimal)
P3TEXT	VARCHAR2(64)	Description of the third wait event parameter
P3	NUMBER	Third wait event parameter (in decimal)
WAIT_TIME	NUMBER	Amount of time waited (in hundredths of a second)
WAIT_TIME_MICRO	NUMBER	Amount of time waited (in microseconds)
TIME_SINCE_LAST_WAIT_MICRO	NUMBER	Time elapsed (in microseconds) since the end of the previous wait in the wait history
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.31 V$SESSIONS_COUNT

V$SESSIONS_COUNT displays the current number of sessions for each PDB.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
USER_SESSION_COUNT	NUMBER	Displays the current number of user sessions for the PDB
RECURSIVE_SESSION_COUNT	NUMBER	Displays the current number of recursive sessions for the PDB

10.32 V$SESSMETRIC

V$SESSMETRIC displays the metric values for all sessions.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
SESSION_ID	NUMBER	Session ID
SESSION_SERIAL_NUM	NUMBER	Session serial number
CPU	NUMBER	CPU usage
PHYSICAL_READS	NUMBER	Number of physical reads
LOGICAL_READS	NUMBER	Number of logical reads
PGA_MEMORY	NUMBER	PGA size at the end of the interval
HARD_PARSES	NUMBER	Number of hard parses
SOFT_PARSES	NUMBER	Number of soft parses
PHYSICAL_READ_PCT	NUMBER	Physical read ratio
LOGICAL_READ_PCT	NUMBER	Logical read ratio
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.33 V$SESSTAT

V$SESSTAT displays user session statistics. To find the name of the statistic associated with each statistic number (STATISTIC#), query the V$STATNAME view.

Column	Datatype	Description
SID	NUMBER	Session identifier
STATISTIC#	NUMBER	Statistic number **Note:** Statistics numbers are not guaranteed to remain constant from one release to another. Therefore, you should rely on the statistics name rather than its number in your applications.
VALUE	NUMBER	Statistic value
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$STATNAME" and " Statistics Descriptions"

10.34 V$SGA

V$SGA displays summary information about the system global area (SGA).

Column	Datatype	Description
NAME	VARCHAR2(20)	SGA component group
VALUE	NUMBER	Memory size (in bytes)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.35 V$SGA_CURRENT_RESIZE_OPS

V$SGA_CURRENT_RESIZE_OPS displays information about SGA resize operations which are currently in progress. An operation can be a grow or a shrink of a dynamic SGA component. All sizes are expressed in bytes.

Column	Datatype	Description
COMPONENT	VARCHAR2(64)	Component name

Column	Datatype	Description
OPER_TYPE	VARCHAR2(13)	Operation type: • STATIC • INITIALIZING • DISABLED • GROW • SHRINK • SHRINK_CANCEL
OPER_MODE	VARCHAR2(9)	Operation mode: • MANUAL • DEFERRED • IMMEDIATE
PARAMETER	VARCHAR2(80)	Name of the parameter for the resize operation
INITIAL_SIZE	NUMBER	Parameter value at the start of the operation
TARGET_SIZE	NUMBER	Desired value of the parameter after the resize
CURRENT_SIZE	NUMBER	Current value of the parameter
START_TIME	DATE	Start time of the operation
LAST_UPDATE_TIME	DATE	Last time progress was made for the operation
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.36 V$SGA_DYNAMIC_COMPONENTS

V$SGA_DYNAMIC_COMPONENTS displays information about the dynamic SGA components. This view summarizes information based on all completed SGA resize operations since instance startup. All sizes are expressed in bytes.

Column	Datatype	Description
COMPONENT	VARCHAR2(64)	Component name
CURRENT_SIZE	NUMBER	Current size of the component
MIN_SIZE	NUMBER	Minimum size of the component since instance startup
MAX_SIZE	NUMBER	Maximum size of the component since instance startup
USER_SPECIFIED_SIZE	NUMBER	Value of the user parameter for the component
OPER_COUNT	NUMBER	Number of operations since instance startup

Column	Datatype	Description
LAST_OPER_TYPE	VARCHAR2(13)	Last completed operation for the component: • STATIC • INITIALIZING • DISABLED • GROW • SHRINK • SHRINK_CANCEL
LAST_OPER_MODE	VARCHAR2(9)	Mode of the last completed operation: • MANUAL • DEFERRED • IMMEDIATE
LAST_OPER_TIME	DATE	Start time of the last completed operation
GRANULE_SIZE	NUMBER	Granularity of the grow or the shrink operation
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.37 V$SGA_DYNAMIC_FREE_MEMORY

V$SGA_DYNAMIC_FREE_MEMORY displays information about the amount of SGA memory available for future dynamic SGA resize operations.

Column	Datatype	Description
CURRENT_SIZE	NUMBER	Amount of available memory (in bytes)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.38 V$SGA_RESIZE_OPS

V$SGA_RESIZE_OPS displays information about the last 800 completed SGA resize operations. This does not include in-progress operations. All sizes are expressed in bytes.

Column	Datatype	Description
COMPONENT	VARCHAR2(64)	Component name

Column	Datatype	Description
OPER_TYPE	VARCHAR2(13)	Operation type: • STATIC • INITIALIZING • DISABLED • GROW • SHRINK • SHRINK_CANCEL
OPER_MODE	VARCHAR2(9)	Operation mode: • MANUAL • DEFERRED • IMMEDIATE
PARAMETER	VARCHAR2(80)	Name of the parameter for the resize operation
INITIAL_SIZE	NUMBER	Parameter value at the start of the operation
TARGET_SIZE	NUMBER	Requested value of the parameter after the resize
FINAL_SIZE	NUMBER	Real value of the parameter after the resize
STATUS	VARCHAR2(9)	Completion status of the operation: • INACTIVE • PENDING • COMPLETE • CANCELLED • ERROR
START_TIME	DATE	Start time of the operation
END_TIME	DATE	End time of the operation
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.39 V$SGA_TARGET_ADVICE

V$SGA_TARGET_ADVICE displays information about the SGA_TARGET initialization parameter.

Column	Datatype	Description
SGA_SIZE	NUMBER	Size of the SGA
SGA_SIZE_FACTOR	NUMBER	Ratio between the SGA_SIZE and the current size of the SGA
ESTD_DB_TIME	NUMBER	Estimated DB_TIME for this SGA_SIZE
ESTD_DB_TIME_FACTOR	NUMBER	Ratio between ESTD_DB_TIME and DB_TIME for the current size of the SGA
ESTD_PHYSICAL_READS	NUMBER	Estimated number of physical reads
ESTD_BUFFER_CACHE_SIZE	NUMBER	Estimated size of the buffer cache
ESTD_SHARED_POOL_SIZE	NUMBER	Estimated size of the shared pool

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "SGA_TARGET"

10.40 V$SGAINFO

V$SGAINFO displays size information about the SGA, including the sizes of different SGA items, the granule size, and free memory.

Column	Datatype	Description
NAME	VARCHAR2(32)	Name of the SGA size item
BYTES	NUMBER	Size of the item (in bytes)
RESIZEABLE	VARCHAR2(3)	Indicates whether the item is resizeable (Yes) or not (No)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.41 V$SGASTAT

V$SGASTAT displays detailed information on the system global area (SGA).

Column	Datatype	Description
POOL	VARCHAR2(14)	Designates the pool in which the memory in NAME resides: • in-memory pool - Memory is allocated from the In-Memory pool • java pool - Memory is allocated from the Java pool • large pool - Memory is allocated from the large pool • numa pool - Memory is allocated from the NUMA pool • shared pool - Memory is allocated from the shared pool • streams pool - Memory is allocated from the Streams pool

Column	Datatype	Description
NAME	VARCHAR2(26)	SGA component name
BYTES	NUMBER	Memory size (in bytes)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.42 V$SHARD_ACK_RECEIVER

V$SHARD_ACK_RECEIVER displays information about ACK receiver processes.

Column	Datatype	Description
SID	NUMBER	Session identifier of the ACK receiver process
SERIAL#	NUMBER	Session serial number of the ACK receiver process
RU_ID	NUMBER	Replication unit (RU) identifier
STARTUP_TIME	DATE	ACK receiver start time
STATE	VARCHAR2(27)	State of the ACK receiver: • ACTIVE • INITIALIZING • POSTING USER TRANSACTION • WAITING FOR ACK FROM SENDER • WAITING FOR EOS FROM SENDER
STATE_CHANGED_TIME	DATE	Time at which the ACK receiver state last changed
ACK_SENDER_PEER_ID	NUMBER	ACK sender's database identifier of the follower
TOTAL_ACKS_RECEIVED	NUMBER	Total number of ACKs received
ACK_RECEIVED_TIME	DATE	Time at which ACK was last received
LAST_ACK_LOG_INDEX_RECEIVED	NUMBER	Last received ACK log index
SPID	VARCHAR2(12)	OS process identifier
LCR_CREATE_TIME	DATE	Commit LCR creation time
DB_ID	NUMBER	Database identifier
IO_SYNC_READ_TIME	NUMBER	Time spent on synchronous reads on Raft logs (in microseconds)
IO_ASYNC_CNT_LK_AHD_READS	NUMBER	Number of asynchronous reads on Raft logs
IO_CNT_BLK_ASYNC_READ	NUMBER	Number of times blocking was required while waiting for asynchronous look-ahead reads
IO_TIME_BLK_ASYNC_READ	NUMBER	Time spent waiting for asynchronous look-ahead reads (in microseconds)
IO_ASYNC_BLOCKS_READ	NUMBER	Total number of file blocks read asynchronously

Column	Datatype	Description
IO_ASYNC_CACHE_HITS	NUMBER	Number of file blocks used from the look-ahead buffer
IO_BSRCH_SYNC_RDS	NUMBER	Number of times binary search was invoked to find a specific LCR
IO_CNT_CACHE_INVALID	NUMBER	Number of look-ahead read blocks that were stale
IO_BLKS_REQUIRED	NUMBER	Number of look-ahead blocks that were required
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.43 V$SHARD_ACK_SENDER

V$SHARD_ACK_SENDER displays information about ACK sender processes.

Column	Datatype	Description
SID	NUMBER	Session identifier of the ACK sender process
SERIAL#	NUMBER	Session serial number of the ACK sender process
RU_ID	NUMBER	Replication unit (RU) identifier
STARTUP_TIME	DATE	ACK sender start time
STATE	VARCHAR2(25)	State of the ACK sender: • ACTIVE • CONNECTING TO LEADER • INITIALIZING • SENDING ACK • WAITING FOR LCR PERSISTER
STATE_CHANGED_TIME	DATE	Time at which the ACK sender state last changed
LEADER_ID	NUMBER	Database identifier of the leader of the RU
TOTAL_ACKS_SENT	NUMBER	Total number of ACKs sent
ACK_TIME	DATE	Time at which ACK was last sent
LAST_ACK_LOG_INDEX_SENT	NUMBER	Last sent ACK log index
SPID	VARCHAR2(12)	OS process identifier
DB_ID	NUMBER	Database identifier

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.44 V$SHARD_APPLY_COORDINATOR

V$SHARD_APPLY_COORDINATOR displays information about apply coordinator processes.

Column	Datatype	Description
SID	NUMBER	Session identifier of the apply coordinator process
SERIAL#	NUMBER	Session serial number of the apply coordinator process
STATE	VARCHAR2(21)	Apply coordinator state: • ABORTING - Stopping because of an apply error • APPLYING - Passing transactions to apply servers • IDLE - Performing no work • INITIALIZING - Initializing • SHUTTING DOWN CLEANLY - Stopping without an error
APPLY#	NUMBER	Apply process number An apply process is an Oracle background process, prefixed by ap.
APPLY_NAME	VARCHAR2(128)	Name of the apply process
TOTAL_APPLIED	NUMBER	Number of transactions applied by the apply process since the apply process was last started
TOTAL_WAIT_DEPS	NUMBER	Number of times, since the apply process was last started, that an apply server waited to apply a logical change record (LCR) in a transaction until another apply server applied a transaction, because of a dependency between the transactions
TOTAL_WAIT_COMMITS	NUMBER	Number of times, since the apply process was last started, that an apply server waited to commit a transaction until another apply server committed a transaction to serialize commits
TOTAL_ADMIN	NUMBER	Number of administrative jobs issued since the apply process was last started
TOTAL_ASSIGNED	NUMBER	Number of transactions assigned to apply servers since the apply process was last started

Column	Datatype	Description
TOTAL_RECEIVED	NUMBER	Number of transactions received by the coordinator process since the apply process was last started
TOTAL_IGNORED	NUMBER	Number of transactions that were received by the coordinator, but were ignored because they had been previously applied
TOTAL_ROLLBACKS	NUMBER	Number of transactions that were rolled back due to unexpected contention
TOTAL_ERRORS	NUMBER	Number of transactions applied by the apply process that resulted in an apply error since the apply process was last started
UNASSIGNED_COMPLETE_TXNS	NUMBER	Number of unassigned complete transactions
AUTO_TXN_BUFFER_SIZE	NUMBER	Auto-tuned transaction buffer size
LWM_TIME	DATE	Time at which the LCR with the lowest log index was recorded The creation time of the LCR with the lowest LCR log index was also recorded at this time.
LWM_LCR_LOG_INDEX	NUMBER	LCRs with a commit log index less than or equal to this number have definitely been applied, but some LCRs with a higher commit log index also may have been applied.
LWM_LCR_CREATE_TIME	DATE	Time at which the LCR corresponding to the low watermark was created
HWM_TIME	DATE	Time at which the LCR with the highest log index was recorded The creation time of the LCR with the highest LCR log index was also recorded at this time.
HWM_LCR_LOG_INDEX	NUMBER	No LCR with a commit log index greater than this LCR log index has been applied
HWM_LCR_CREATE_TIME	DATE	Time at which the LCR corresponding to the high watermark was created
STARTUP_TIME	DATE	Apply coordinator process start time
ELAPSED_SCHEDULE_TIME	NUMBER	Time elapsed (in hundredths of a second) spent scheduling transactions since the apply process was last started
ELAPSED_IDLE_TIME	NUMBER	Elapsed idle time (in hundredths of a second) since the apply process was last started
PROCESSED_LCR_LOG_INDEX	NUMBER	LCR log index currently processed by the apply coordinator
ACTIVE_SERVER_COUNT	NUMBER	Number of active servers
RU_ID	NUMBER	Replication unit (RU) identifier
DB_ID	NUMBER	Database identifier
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.45 V$SHARD_APPLY_LCR_READER

`V$SHARD_APPLY_LCR_READER` displays information about apply LCR reader processes.

Column	Datatype	Description
`SID`	`NUMBER`	Session identifier of the apply LCR reader process
`SERIAL#`	`NUMBER`	Session serial number of the apply LCR reader process
`APPLY#`	`NUMBER`	Apply process number An apply process is an Oracle background process, prefixed by `ap`.
`APPLY_NAME`	`VARCHAR2(128)`	Name of the apply process group
`STATE`	`VARCHAR2(36)`	State of the apply LCR reader: • `DEQUEUING LCR` • `ENQUEUING LCR` • `GENERATING HASH VALUES` • `IDLE` • `INITIALIZING` • `READ ON DISK LCRS` • `WAITING ON EMPTY INBOUND QUEUE` • `WAITING ON FULL INBOUND QUEUE`
`TOTAL_LCRS_DEQUEUED`	`NUMBER`	Total number of LCRs read
`DEQUEUE_TIME`	`DATE`	Last read LCR time
`DEQUEUED_LCR_LOG_INDEX`	`NUMBER`	Last read LCR log index
`DEQUEUED_LCR_CREATE_TIME`	`DATE`	Last read LCR create time
`RU_ID`	`NUMBER`	Replication unit (RU) identifier
`DB_ID`	`NUMBER`	Database identifier
`TOTAL_ON_DISK_LCRS_READ`	`NUMBER`	Number of LCRs read from disk
`LAST_ON_DISK_LCR_LOG_INDEX`	`NUMBER`	Last LCR log index read from disk
`STARTUP_TIME`	`DATE`	Apply LCR reader start time
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.46 V$SHARD_APPLY_READER

V$SHARD_APPLY_READER displays information about apply reader processes.

Column	Datatype	Description
SID	NUMBER	Session identifier of the apply reader process
SERIAL#	NUMBER	Session serial number of the apply reader process
APPLY#	NUMBER	Apply process number An apply process is an Oracle background process, prefixed by ap.
APPLY_NAME	VARCHAR2(128)	Name of the apply process
STATE	VARCHAR2(36)	State of the apply reader: • DEQUEUE LCRS • IDLE • INITIALIZING • PAUSED – WAITING FOR DDL TO COMPLETE • SCHEDULE TRANSACTIONS • SPILLING
TOTAL_LCRS_DEQUEUED	NUMBER	Total number of LCRs read
TOTAL_LCRS_SPILLED	NUMBER	Total number of LCRs spilled
DEQUEUE_TIME	DATE	Last read LCR time
DEQUEUED_LCR_LOG_INDEX	NUMBER	Last read LCR log index
DEQUEUED_LCR_CREATE_TIME	DATE	Last read LCR create time
SGA_USED	NUMBER	Amount of SGA memory (in bytes) used by the apply process since it was last started
ELAPSED_DEQUEUE_TIME	NUMBER	Time elapsed (in hundredths of a second) while dequeuing the last LCR
ELAPSED_SCHEDULE_TIME	NUMBER	Time elapsed (in hundredths of a second) spent scheduling transactions since the apply process was last started
ELAPSED_SPILL_TIME	NUMBER	Time elapsed (in hundredths of a second) while spilling LCRs
LAST_BROWSE_LOG_INDEX	NUMBER	Last browsed LCR log index
OLDEST_LOG_INDEX	NUMBER	Oldest log index
OLDEST_XIDUSN	NUMBER	Transaction ID undo segment number of the oldest transaction
OLDEST_XIDSLT	NUMBER	Transaction ID slot number of the oldest transaction
OLDEST_XIDSQN	NUMBER	Transaction ID sequence number of the oldest transaction
SPILL_LWM_LOG_INDEX	NUMBER	Spill low-watermark log index
OLDEST_TRANSACTION_ID	VARCHAR2(128)	Oldest transaction ID

Column	Datatype	Description
TOTAL_LCRS_WITH_DEP	NUMBER	Number of LCRs with row-level dependencies since the apply process last started
TOTAL_LCRS_WITH_WMDEP	NUMBER	Number of LCRs with watermark dependencies since the apply process last started A watermark dependency occurs when an apply process must wait until the apply process's low watermark reaches a particular threshold.
TOTAL_IN_MEMORY_LCRS	NUMBER	Total number of LCRs currently in memory
SGA_ALLOCATED	NUMBER	Total amount of shared memory (in bytes) allocated from the SGA for the apply process since the apply process last started
RU_ID	NUMBER	Replication unit (RU) identifier
DB_ID	NUMBER	Database identifier
TOTAL_ON_DISK_LCRS_READ	NUMBER	Number of LCRs read from disk
LAST_ON_DISK_LCR_LOG_INDEX	NUMBER	Last LCR log index read from disk
STARTUP_TIME	DATE	Apply reader process start time
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.47 V$SHARD_APPLY_SERVER

V$SHARD_APPLY_SERVER displays information about apply server components.

Column	Datatype	Description
SID	NUMBER	Session identifier of the apply server component
SERIAL#	NUMBER	Session serial number of the apply server component
APPLY#	NUMBER	Apply process number An apply process is an Oracle background process, prefixed by ap.
APPLY_NAME	VARCHAR2(128)	Name of the apply process
SERVER_ID	NUMBER	Parallel execution server number of the apply server

Column	Datatype	Description
STATE	VARCHAR2(20)	State of the apply server: • ADD PARTITION • DROP PARTITION • EXECUTE TRANSACTION • GET TRANSACTIONS • IDLE • INACTIVE • INITIALIZING • POLL SHUTDOWN • RECORD LOW-WATERMARK • REQUEST UA SESSION • ROLLBACK TRANSACTIONS • SPILL • TRANSACTION CLEANUP • WAIT COMMIT • WAIT DEPENDENCY • WAIT FOR CLIENT • WAIT FOR NEXT CHUNK • WAIT POST COMMIT
XIDUSN	NUMBER	Transaction ID undo segment number of the transaction currently being applied
XIDSLT	NUMBER	Transaction ID slot number of the transaction currently being applied
XIDSQN	NUMBER	Transaction ID undo sequence number of the transaction currently being applied
COMMIT_LOG_INDEX	NUMBER	Commit log index of the transaction currently being applied
DEP_XIDUSN	NUMBER	Transaction ID undo segment number of a transaction on which the transaction being applied by this apply server depends
DEP_XIDSLT	NUMBER	Transaction ID slot number of a transaction on which the transaction being applied by this apply server depends
DEP_XIDSQN	NUMBER	Transaction ID sequence number of a transaction on which the transaction being applied by this apply server depends
DEP_COMMIT_LOG_INDEX	NUMBER	Commit log index of the transaction on which this apply server depends
CURRENT_LOG_INDEX	NUMBER	Current LCR log index being applied by the apply server. This value is reset to 1 at the beginning of each transaction.
TOTAL_ASSIGNED	NUMBER	Number of transactions assigned to the apply server since the apply process was last started
TOTAL_ADMIN	NUMBER	Number of administrative jobs performed by the apply server since the apply process was last started. See the STATE information in this view for the types of administrative jobs.
TOTAL_ROLLBACKS	NUMBER	Number of transactions assigned to this server that were rolled back
TOTAL_LCRS_APPLIED	NUMBER	Total number of LCRs applied by this apply server since the apply process was last started
APPLY_TIME	DATE	Time the last LCR was applied
APPLIED_LCR_LOG_INDEX	NUMBER	Last applied LCR log index

Column	Datatype	Description
APPLIED_LCR_CREATE_TIME	DATE	Last applied LCR create time
ELAPSED_DEQUEUE_TIME	NUMBER	Time elapsed (in hundredths of a second) while dequeuing LCRs
ELAPSED_APPLY_TIME	NUMBER	Time elapsed (in hundredths of a second) applying LCRs since the apply process was last started
TRANSACTION_ID	VARCHAR2(128)	ID of the transaction that the slave is applying
TOTAL_LCRS_RETRIED	NUMBER	Total number of LCRs retried by this server
LCR_RETRY_ITERATION	NUMBER	Retry iteration for this transaction by this server
TOTAL_TXNS_RETRIED	NUMBER	Total number of LCRs retried by this server
TXN_RETRY_ITERATION	NUMBER	Retry iteration for this transaction by this server
TOTAL_TXNS_RECORDED	NUMBER	Total transactions recorded in error queue by this server
RU_ID	NUMBER	Replication unit (RU) identifier
DB_ID	NUMBER	Database identifier
STARTUP_TIME	DATE	Apply server process start time
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

This view is available starting with Oracle Database 23ai.

10.48 V$SHARD_LCR_LOGS

V$SHARD_LCR_LOGS displays information about LCR logs.

Column	Datatype	Description
INST_ID	NUMBER	Instance ID
RU_ID	NUMBER	Replication unit (RU) ID
NAME	VARCHAR2(257)	Name and path of the log file
SIZE_GB	NUMBER	Size of the log file (in gigabytes)
ROTD_IDX	NUMBER	Rotated index
CURR_FILE	VARCHAR2(1)	Indicates whether the file is current (Y) or not (N)
STIDX_HIGH	NUMBER	High 4 bytes of the starting log index in the log file
STIDX_LOW	NUMBER	Low 4 bytes of the starting log index in the log file
ENDIDX_HIGH	NUMBER	High 4 bytes of the ending log index in the log file

Column	Datatype	Description
ENDIDX_LOW	NUMBER	Low 4 bytes of the ending logindex in the log file
START_SEC	NUMBER	Time when this log file was first written to, measured in seconds from the epoch
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.49 V$SHARD_LCR_PERSISTER

V$SHARD_LCR_PERSISTER displays information about LCR persister processes.

This view displays one row for each LCR persister for a replication unit (RU).

Column	Datatype	Description
SID	NUMBER	Session identifier of the LCR persister process
SERIAL#	NUMBER	Session serial number of the LCR persister process
RU_ID	NUMBER	Replication unit (RU) identifier
STARTUP_TIME	DATE	LCR persister process start time
STATE	VARCHAR2(30)	State of the LCR persister: • ACTIVE • INITIALIZING • READING FROM IO • WAITING FOR BUFFERS TO PERSIST • WAITING ON EMPTY QUEUE • WRITING TO IO
STATE_CHANGED_TIME	DATE	Time at which the LCR persister state last changed
PERSISTED_LOG_INDEX	NUMBER	Last persisted LCR log index
PERSISTED_TIMESTAMP	DATE	Timestamp of the last persisted LCR
IOBUF_INIT_US	NUMBER	Write buffer initialization time (in microseconds)
LEAD_IO_ISSUED_COUNT	NUMBER	Number of times I/O was issued on the leader
LEAD_IO_ISSUED_US	NUMBER	Time spent (in microseconds) during I/O on the leader
LEAD_IO_ISSUED_BLKS	NUMBER	Number of blocks written on the leader
LEAD_IO_FETCHED_COUNT	NUMBER	Number of times LCR persister issued fetch on the leader
LEAD_IO_FETCHED_US	NUMBER	Time (in microseconds) to fetch blocks

Column	Datatype	Description
LEAD_IO_FETCHED_SUCCESS	NUMBER	Number of times the LCR persister actually fetched
LEAD_IO_BLOCKED_COUNT	NUMBER	Number of times I/O blocked on the leader
LEAD_IO_BLOCKED_US	NUMBER	Time (in microseconds) spent while the I/O was blocked
LEAD_IO_COMMITS_COUNT	NUMBER	Number of times commit processed on the leader
FOLL_IO_ISSUED_COUNT	NUMBER	Number of times I/O was issued on the follower
FOLL_IO_ISSUED_US	NUMBER	Time spent during I/O on the follower (in microseconds)
FOLL_IO_ISSUED_BLKS	NUMBER	Number of blocks written on the follower
FOLL_IO_COMMITS_COUNT	NUMBER	Number of times commit processed on the follower
SPID	VARCHAR2(12)	OS process identifier
DB_ID	NUMBER	Database identifier
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.50 V$SHARD_LCR_PRODUCER

V$SHARD_LCR_PRODUCER displays information about LCR producer processes.

Column	Datatype	Description
SID	NUMBER	Session identifier of the LCR producer process
SERIAL#	NUMBER	Session serial number of the LCR producer process
RU_ID	NUMBER	Replication unit (RU) identifier
STARTUP_TIME	DATE	LCR producer process start time
STATE	VARCHAR2(33)	State of the LCR producer: • ACTIVE • BROWSING LCR • DEQUEUING LCR • ENQUEUING LCR • INITIALIZING • WAITING FOR MEMORY • WAITING ON EMPTY INBOUND QUEUE • WAITING ON SUBSCRIBERS TO DEQUEUE

Column	Datatype	Description
STATE_CHANGED_TIME	DATE	Time at which the LCR producer state last changed
OUTBOUND_QUEUE_SIZE	NUMBER	Outbound queue size
TOTAL_AVAILABLE_LCRS_IN_OUTBOUND_QUEUE	NUMBER	Total number of LCRs available in the outbound queue
NEXT_LOG_INDEX	NUMBER	Next LCR log index
TOTAL_LCRS_DEQUEUED	NUMBER	Total number of LCRs dequeued from the foreground queue
LAST_DEQUEUED_LCR_LOG_INDEX	NUMBER	Last dequeued LCR log index
TOTAL_LCRS_ENQUEUED	NUMBER	Total number of LCRs enqueued into the outbound queue
LAST_ENQUEUED_TIME	DATE	Last LCR enqueued time
LAST_ENQUEUED_LCR_TIME	DATE	Creation time of the last LCR enqueued
LAST_ENQUEUED_LCR_LOG_INDEX	NUMBER	Last enqueued LCR log index
SPID	VARCHAR2(12)	OS process identifier
DB_ID	NUMBER	Database identifier
FLWCTRL_PEERS	VARCHAR2(64)	Flow control state
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.51 V$SHARD_NETWORK_RECEIVER

V$SHARD_NETWORK_RECEIVER displays information about network receiver processes.

Column	Datatype	Description
SID	NUMBER	Session identifier of the network receiver process
SERIAL#	NUMBER	Session serial number of the network receiver process
APPLY_NAME	VARCHAR2(128)	Name of the apply process
STARTUP_TIME	DATE	Network receiver start time
RU_ID	NUMBER	Replication unit (RU) identifier
SPILL_LWM	NUMBER	Highest log index of LCRs that an apply has persisted to its spilled tables

Column	Datatype	Description
LAST_RECEIVED_LOG_INDEX	NUMBER	Log index of the last received LCR
TOTAL_LCRS_RECEIVED	NUMBER	Total number of LCRs received
TOTAL_AVAILABLE_LCRS	NUMBER	Total number of LCRs available in knlbm
STATE	VARCHAR2(38)	State of the network receiver: • Enqueueing LCRs • Initializing • Receiving LCRs • Sending unapplied txns • Waiting for apply error to be resolved • Waiting for apply to be unsuspended • Waiting for apply to dequeue • Waiting for flush request to complete • Waiting for memory • Waiting for message from peer
SPID	VARCHAR2(12)	OS process identifier
LAST_RECEIVED_LCR_TIME	DATE	Time last LCR was received
LAST_RECEIVED_LCR_CREATE_TIME	DATE	Creation time of last received LCR
REMOTE_PEER_ID	NUMBER	Database ID of the leader of this RU
TOTAL_SKIPPED_ENQUEUE_LCRS	NUMBER	Total number of LCRs skipped for enqueueing to apply queue
LAST_SKIPPED_ENQUEUE_LCR_LOG_INDEX	NUMBER	LCR log index of the last skipped enqueue to the apply queue
DB_ID	NUMBER	Database identifier
TOTAL_BYTES_RECEIVED	NUMBER	Total number of bytes received
IO_SYNC_READ_TIME	NUMBER	Time spent on synchronous reads on Raft logs (in microseconds)
IO_ASYNC_CNT_LK_AHD_READS	NUMBER	Number of asynchronous reads on Raft logs
IO_CNT_BLK_ASYNC_READ	NUMBER	Number of times blocking was required while waiting for asynchronous look-ahead reads
IO_TIME_BLK_ASYNC_READ	NUMBER	Time spent waiting for asynchronous look-ahead reads (in microseconds)
IO_ASYNC_BLOCKS_READ	NUMBER	Total number of file blocks read asynchronously
IO_ASYNC_CACHE_HITS	NUMBER	Number of file blocks used from the look-ahead buffer
IO_BSRCH_SYNC_RDS	NUMBER	Number of times binary search was invoked to find a specific LCR
IO_CNT_CACHE_INVALID	NUMBER	Number of look-ahead read blocks that were stale
IO_BLKS_REQUIRED	NUMBER	Number of look-ahead blocks that were required
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.52 V$SHARD_NETWORK_SENDER

V$SHARD_NETWORK_SENDER displays information about network sender processes.

Column	Datatype	Description
SID	NUMBER	Session identifier of the network sender process
SERIAL#	NUMBER	Session serial number of the network sender process
RU_ID	NUMBER	Replication unit (RU) identifier
REMOTE_PEER_ID	NUMBER	Remote follower's database identifier of this RU
STARTUP_TIME	DATE	Network sender process start time
STATE	VARCHAR2(22)	State of the network sender: • ACTIVE • BROWSING LCR • CONNECTING TO FOLLOWER • DEQUEUING LCR SENDING LCR • INITIALIZING • WAITING ON EMPTY QUEUE
STATE_CHANGED_TIME	DATE	Time at which the network sender state last changed
TOTAL_LCRS_SENT	NUMBER	Number of LCRs sent
BROWSED_TIME	DATE	Last browsed LCR time
LAST_BROWSED_LCR_LOG_INDEX	NUMBER	Last browsed LCR log index
SEND_TIME	DATE	Time at which last LCR was sent
LAST_SENT_LCR_LOG_INDEX	NUMBER	Last sent LCR log index
LAST_SENT_LCR_TIME	DATE	Creation time of the last sent LCR
ELAPSED_PROPAGATION_TIME	NUMBER	Amount of time taken to propogate LCRs (in what unit of time?)
AVAILABLE_LCRS	NUMBER	Number of LCRs available in outbound queue
SPID	VARCHAR2(12)	OS process identifier
CONNECT_ERROR_COUNT	NUMBER	Number of network sender connection errors
DB_ID	NUMBER	Database identifier
TOTAL_BYTES_SENT	NUMBER	Total number of bytes sent
IO_SYNC_READ_TIME	NUMBER	Time spent on synchronous reads on Raft logs (in microseconds)
IO_ASYNC_CNT_LK_AHD_READS	NUMBER	Number of asynchronous reads on Raft logs
IO_CNT_BLK_ASYNC_REA	NUMBER	Number of times blocking was required while waiting for asynchronous look-ahead reads
IO_TIME_BLK_ASYNC_READ	NUMBER	Time spent waiting for asynchronous look-ahead reads (in microseconds)

Column	Datatype	Description
IO_ASYNC_BLOCKS_READ	NUMBER	Total number of file blocks read asynchronously
IO_ASYNC_CACHE_HITS	NUMBER	Number of file blocks used from the look-ahead buffer
IO_BSRCH_SYNC_RDS	NUMBER	Number of times binary search was invoked to find a specific LCR
IO_CNT_CACHE_INVALID	NUMBER	Number of look-ahead read blocks that were stale
IO_BLKS_REQUIRED	NUMBER	Number of look-ahead blocks that were required
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.53 V$SHARD_REPLICATION_UNIT

V$SHARD_REPLICATION_UNIT displays information about replication units (RUs) that are present in a shard.

This view displays one row for each RU.

Column	Datatype	Description
SHARD_ID	NUMBER	Shard database identifier
RU_ID	NUMBER	Replication unit (RU) identifier
LEADER_ID	NUMBER	Leader's SHARD_ID for the corresponding RU
ROLE	NUMBER	Role of the shard for the RU: • 1 - The shard is the leader • 2 - The shard is the follower • 3 - The shard is a candidate for leader election
TERM	NUMBER	Term number This value is incremented each time a new leader is elected.
COMMITIDX	NUMBER	LCRs with a log index of COMMITIDX or lower have consensus
OLDAPPIDX	NUMBER	Oldest log index that an apply process group may need
APPLYLWMIDX	NUMBER	Position of apply low watermark on the follower
ONDISKIDX	NUMBER	Persisted log index

Column	Datatype	Description
FLAGS	NUMBER	State of the shard with respect to the RU: • 0x00000001 - PRE-SHUTDOWN • 0x00000002 - IN MOVE • 0x00000004 - IN COPY • 0x00000008 - LEADER NOT RECOVERED • 0x00000010 - OPEN LEADER • 0x00000020 - ELECTION REQUEST • 0x00000040 - AFTER VOTE • 0x00000080 - DRAIN KNLBM LEADER TO FOLLOWER When a shard becomes follower, the knlb buffer should be drained. • 0x00000100 - BARRIER DDL SUSPEND • 0x00000200 - BARRIER DDL RESUME • 0x00000400 - RESUME NOTIFICATION • 0x00000800 - RU LOADED • 0x00001000 - SUSPEND APPLY KNLB ENQ • 0x00002000 - NETWORK RECEIVER RAISED • 0x00004000 - ERROR CHECK HINT Set by foreground using DBMS_APPLY_ADM.DELETE_ALL_ERRORS. When this flag is set, the network receiver can immediately check the number of apply errors without waiting for a timeout. • 0x00008000 - SUSPEND CHECK HINT Set by foreground using DBMS_APPLY_ADM.DELETE_ALL_ERRORS. When this flag is set, the network receiver can immediately check the apply suspend status without waiting for a timeout. • 0x00010000 - ERRORS When this flag is set, the RU has active errors. The flag will be unset upon successful recovery. • 0x00020000 - GP AUTO RESTART • 0x00040000 - FOLLOWER CATCHUP • 0x00100000 - DELETE LOG STOP ENQ • 0x00200000 - OPTIMISE APPLY STOP DELETE LOG TAIL
ROLE_CHANGED_TIME	TIMESTAMP(6)	Time at which the role for the RU in the shard last changed
RECOVERY_TIME	TIMESTAMP(6)	Amount of time taken for recovery
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.54 V$SHARED_POOL_ADVICE

V$SHARED_POOL_ADVICE displays information about estimated parse time in the shared pool for different pool sizes. The sizes range from 10% of the current shared pool size or the amount of pinned library cache memory (whichever is higher) to 200% of the current shared pool size, in equal intervals. The value of the interval depends on the current size of the shared pool.

Column	Datatype	Description
SHARED_POOL_SIZE_FOR_ESTIMATE	NUMBER	Shared pool size for the estimate (in megabytes)
SHARED_POOL_SIZE_FACTOR	NUMBER	Size factor with respect to the current shared pool size
ESTD_LC_SIZE	NUMBER	Estimated memory in use by the library cache (in megabytes)
ESTD_LC_MEMORY_OBJECTS	NUMBER	Estimated number of library cache memory objects in the shared pool of the specified size
ESTD_LC_TIME_SAVED	NUMBER	Estimated elapsed parse time saved (in seconds), owing to library cache memory objects being found in a shared pool of the specified size. This is the time that would have been spent in reloading the required objects in the shared pool had they been aged out due to insufficient amount of available free memory.
ESTD_LC_TIME_SAVED_FACTOR	NUMBER	Estimated parse time saved factor with respect to the current shared pool size
ESTD_LC_LOAD_TIME	NUMBER	Estimated elapsed time (in seconds) for parsing in a shared pool of the specified size
ESTD_LC_LOAD_TIME_FACTOR	NUMBER	Estimated load time factor with respect to the current shared pool size
ESTD_LC_MEMORY_OBJECT_HITS	NUMBER	Estimated number of times a library cache memory object was found in a shared pool of the specified size
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.55 V$SHARED_POOL_RESERVED

V$SHARED_POOL_RESERVED displays statistics that help you tune the reserved pool and space within the shared pool.

Column	Datatype	Description
FREE_SPACE	NUMBER	Total amount of free space on the reserved list in bytes[1]
AVG_FREE_SIZE	NUMBER	Average size of the free memory on the reserved list in bytes[1]
FREE_COUNT	NUMBER	Number of free pieces of memory on the reserved list[1]
MAX_FREE_SIZE	NUMBER	Size of the largest free piece of memory on the reserved list in bytes[1]
USED_SPACE	NUMBER	Total amount of used memory on the reserved list in bytes[1]
AVG_USED_SIZE	NUMBER	Average size of the used memory on the reserved list in bytes[1]
USED_COUNT	NUMBER	Number of used pieces of memory on the reserved list[1]
MAX_USED_SIZE	NUMBER	Size of the largest used piece of memory on the reserved list in bytes[1]
REQUESTS	NUMBER	Number of times that the reserved list was searched for a free piece of memory[1]
REQUEST_MISSES	NUMBER	Number of times the reserved list did not have a free piece of memory to satisfy the request, and started flushing objects from the LRU list[1]
LAST_MISS_SIZE	NUMBER	Request size of the last request miss in bytes, when the reserved list did not have a free piece of memory to satisfy the request and started flushing objects from the LRU list[1]
MAX_MISS_SIZE	NUMBER	Request size of the largest request miss in bytes, when the reserved list did not have a free piece of memory to satisfy the request and started flushing objects from the LRU list[1]
REQUEST_FAILURES	NUMBER	Number of times that no memory was found to satisfy a request. If an internal flush (used to free up memory) does not meet a memory need, then the error ORA-04031 occurs.[2]
LAST_FAILURE_SIZE	NUMBER	Request size of the last failed request in bytes. If an internal flush (used to free up memory) does not meet a memory need, then the error ORA-04031 occurs.[2]
ABORTED_REQUEST_THRESHOLD	NUMBER	Minimum size of a request in bytes which signals an ORA-04031 error without flushing objects[2]
ABORTED_REQUESTS	NUMBER	Number of requests that signalled an ORA-04031 error without flushing objects[2]
LAST_ABORTED_SIZE	NUMBER	Last size of the request in bytes that returned an ORA-04031 error without flushing objects from the LRU list[2]
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

1 These columns are valid only if the initialization parameter SHARED_POOL_RESERVED_SIZE is set to a valid value.

2 These columns contain values which are valid even if SHARED_POOL_RESERVED_SIZE is not set.

10.56 V$SHARED_SERVER

V$SHARED_SERVER displays information on the shared server processes.

Column	Datatype	Description
NAME	VARCHAR2(4)	Name of the server
PADDR	RAW(4 | 8)	Server's process address
STATUS	VARCHAR2(16)	Server status: • EXEC - Executing SQL • WAIT (ENQ) - Waiting for a lock • WAIT (SEND) - Waiting to send data to user • WAIT (COMMON) - Idle; waiting for a user request • WAIT (RECEIVE) - Waiting for records to be shown in the client application • WAIT (RESET) - Waiting for a circuit to reset after a break • QUIT - Terminating
MESSAGES	NUMBER	Number of messages processed
BYTES	NUMBER	Total number of bytes in all messages
BREAKS	NUMBER	Number of breaks
CIRCUIT	RAW(4 | 8)	Address of the circuit currently being serviced
IDLE	NUMBER	Total idle time (in hundredths of a second)
BUSY	NUMBER	Total busy time (in hundredths of a second)
IN_NET	NUMBER	Total incoming network wait time (in hundredths of a second)
OUT_NET	NUMBER	Total outgoing network wait time (in hundredths of a second)
REQUESTS	NUMBER	Total number of requests taken from the common queue in this server's lifetime
BOUND_TIME	NUMBER	Time that a circuit and shared server have been bound (in centiseconds)
BOUND_REASON	VARCHAR2(32)	Provides a reason (a short explanation) for why a shared server and circuit could not be unbound. This column is empty when a circuit is not bound to a server. When the server starts serving a circuit, BOUND_REASON is empty and remains empty unless the server tries unsuccessfully to unbind the circuit (after it finishes serving the current request). When this column is not empty, it will be cleared once the server and circuit are unbound (that is, once the resources preventing the session migration to another shared server are released).
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.57 V$SHARED_SERVER_MONITOR

V$SHARED_SERVER_MONITOR displays information for tuning the shared server.

Column	Datatype	Description
MAXIMUM_CONNECTIONS	NUMBER	Highest number of virtual circuits in use at one time since the instance started. If this value reaches the value set for the CIRCUITS initialization parameter, then consider raising the value of CIRCUITS. **See Also:** "CIRCUITS"
MAXIMUM_SESSIONS	NUMBER	Highest number of shared server sessions in use at one time since the instance started. If this reaches the value set for the SHARED_SERVER_SESSIONS initialization parameter, then consider raising the value of SHARED_SERVER_SESSIONS. **See Also:** "SHARED_SERVER_SESSIONS"
SERVERS_STARTED	NUMBER	Total number of shared servers started since the instance started (but not including those started during startup)
SERVERS_TERMINATED	NUMBER	Total number of shared servers stopped by Oracle since the instance started
SERVERS_HIGHWATER	NUMBER	Highest number of servers running at one time since the instance started. If this value reaches the value set for the MAX_SHARED_SERVERS initialization parameter, then consider raising the value of SHARED_SERVERS. **See Also:** "SHARED_SERVERS"
DISPATCHERS_CPU	NUMBER	Total CPU time of all dispatchers since the instance started (in millionths of a second)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.58 V$SHARED_SERVER_STAT

V$SHARED_SERVER_STAT displays statistics for all shared server processes. The statistics are cumulative from the start of the instance.

Column	Datatype	Description
MESSAGES	NUMBER	Number of messages processed
BYTES	NUMBER	Total number of bytes in all messages
IDLE	NUMBER	Total idle time (in hundredths of a second)
BUSY	NUMBER	Total busy time (in hundredths of a second)
IN_NET	NUMBER	Total incoming network wait time (in hundredths of a second)
OUT_NET	NUMBER	Total outgoing network wait time (in hundredths of a second)

Column	Datatype	Description
REQUESTS	NUMBER	Total number of requests taken from the common queue
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.59 V$SORT_SEGMENT

V$SORT_SEGMENT displays information about every sort segment in a given instance. The view is only updated when the tablespace is of the TEMPORARY type.

Column	Datatype	Description
TABLESPACE_NAME	VARCHAR2(30)	Name of the tablespace
SEGMENT_FILE	NUMBER	File number of the first extent
SEGMENT_BLOCK	NUMBER	Block number of the first extent
EXTENT_SIZE	NUMBER	Extent size
CURRENT_USERS	NUMBER	Number of active users of the segment
TOTAL_EXTENTS	NUMBER	Total number of extents in the segment
TOTAL_BLOCKS	NUMBER	Total number of blocks in the segment
USED_EXTENTS	NUMBER	Extents allocated to active sorts
USED_BLOCKS	NUMBER	Blocks allocated to active sorts
FREE_EXTENTS	NUMBER	Extents not allocated to any sort
FREE_BLOCKS	NUMBER	Blocks not allocated to any sort
ADDED_EXTENTS	NUMBER	Number of extent allocations
EXTENT_HITS	NUMBER	Number of times an unused extent was found in the pool
FREED_EXTENTS	NUMBER	Number of deallocated extents
FREE_REQUESTS	NUMBER	Number of requests to deallocate
MAX_SIZE	NUMBER	Maximum number of extents ever used
MAX_BLOCKS	NUMBER	Maximum number of blocks ever used
MAX_USED_SIZE	NUMBER	Maximum number of extents used by all sorts
MAX_USED_BLOCKS	NUMBER	Maximum number of blocks used by all sorts
MAX_SORT_SIZE	NUMBER	Maximum number of extents used by an individual sort
MAX_SORT_BLOCKS	NUMBER	Maximum number of blocks used by an individual sort
RELATIVE_FNO	NUMBER	Relative file number of the sort segment header
TS#	NUMBER	Tablespace number

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
IS_LOCAL_TEMP	NUMBER	Indicates whether the sort segment is allocated from a local temporary tablespace (1) or not (0).

10.60 V$SPPARAMETER

V$SPPARAMETER displays information about the contents of the server parameter file. If a server parameter file was not used to start the instance, then each row of the view will contain FALSE in the ISSPECIFIED column.

Column	Datatype	Description
FAMILY	VARCHAR2(80)	For internal use only
SID	VARCHAR2(80)	SID for which the parameter is defined.
NAME	VARCHAR2(80)	Name of the parameter
TYPE	VARCHAR2(11)	Parameter type
VALUE	VARCHAR2(255)	Parameter value (null if a server parameter file was not used to start the instance)
DISPLAY_VALUE	VARCHAR2(255)	Parameter value in a user-friendly format. For example, if the VALUE column shows the value 262144 for a big integer parameter, then the DISPLAY_VALUE column will show the value 256K.
ISSPECIFIED	VARCHAR2(6)	Indicates whether the parameter was specified in the server parameter file (TRUE) or not (FALSE)
ORDINAL	NUMBER	Position (ordinal number) of the parameter value (0 if a server parameter file was not used to start the instance). Useful only for parameters whose values are lists of strings.
UPDATE_COMMENT	VARCHAR2(255)	Comments associated with the most recent update (null if a server parameter file was not used to start the instance)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.61 V$SQL

V$SQL lists statistics on shared SQL areas without the GROUP BY clause and contains one row for each child of the original SQL text entered. Statistics displayed in V$SQL

are normally updated at the end of query execution. However, for long running queries, they are updated every 5 seconds. This makes it easy to see the impact of long running SQL statements while they are still in progress.

Column	Datatype	Description
SQL_TEXT	VARCHAR2(1000)	First thousand characters of the SQL text for the current cursor
SQL_FULLTEXT	CLOB	Full text for the SQL statement exposed as a CLOB column. The full text of a SQL statement can be retrieved using this column instead of joining with the V$SQLTEXT dynamic performance view.
SQL_ID	VARCHAR2(13)	SQL identifier of the parent cursor in the library cache
SHARABLE_MEM	NUMBER	Amount of shared memory used by the child cursor (in bytes)
PERSISTENT_MEM	NUMBER	Fixed amount of memory used for the lifetime of the child cursor (in bytes)
RUNTIME_MEM	NUMBER	Fixed amount of memory required during the execution of the child cursor
SORTS	NUMBER	Number of sorts that were done for the child cursor
LOADED_VERSIONS	NUMBER	Indicates whether the context heap is loaded (1) or not (0)
OPEN_VERSIONS	NUMBER	Indicates whether the child cursor is locked (1) or not (0)
USERS_OPENING	NUMBER	Number of users that have any of the child cursors open
FETCHES	NUMBER	Number of fetches associated with the SQL statement
EXECUTIONS	NUMBER	Number of executions that took place on this object since it was brought into the library cache
PX_SERVERS_EXECUTIONS	NUMBER	Total number of executions performed by parallel execution servers (0 when the statement has never been executed in parallel)
END_OF_FETCH_COUNT	NUMBER	Number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic is not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed. By definition, the value of the END_OF_FETCH_COUNT column should be less or equal to the value of the EXECUTIONS column.
USERS_EXECUTING	NUMBER	Number of users executing the statement
LOADS	NUMBER	Number of times the object was either loaded or reloaded
FIRST_LOAD_TIME	VARCHAR2(76)	Timestamp of the parent creation time
INVALIDATIONS	NUMBER	Number of times this child cursor has been invalidated
PARSE_CALLS	NUMBER	Number of parse calls for this child cursor
DISK_READS	NUMBER	Number of disk reads for this child cursor
DIRECT_WRITES	NUMBER	Number of direct writes for this child cursor
DIRECT_READS	NUMBER	Number of direct reads for this child cursor
BUFFER_GETS	NUMBER	Number of buffer gets for this child cursor
APPLICATION_WAIT_TIME	NUMBER	Application wait time (in microseconds)
CONCURRENCY_WAIT_TIME	NUMBER	Concurrency wait time (in microseconds)
CLUSTER_WAIT_TIME	NUMBER	Cluster wait time (in microseconds)
USER_IO_WAIT_TIME	NUMBER	User I/O Wait Time (in microseconds)

Column	Datatype	Description
PLSQL_EXEC_TIME	NUMBER	PL/SQL execution time (in microseconds)
JAVA_EXEC_TIME	NUMBER	Java execution time (in microseconds)
ROWS_PROCESSED	NUMBER	Total number of rows the parsed SQL statement returns
COMMAND_TYPE	NUMBER	Oracle command type definition
OPTIMIZER_MODE	VARCHAR2(10)	Mode under which the SQL statement was executed
OPTIMIZER_COST	NUMBER	Cost of this query given by the optimizer
OPTIMIZER_ENV	RAW(2000)	Optimizer environment
OPTIMIZER_ENV_HASH_VALUE	NUMBER	Hash value for the optimizer environment
PARSING_USER_ID	NUMBER	User ID of the user who originally built this child cursor
PARSING_SCHEMA_ID	NUMBER	Schema ID that was used to originally build this child cursor
PARSING_SCHEMA_NAME	VARCHAR2(128)	Schema name that was used to originally build this child cursor
KEPT_VERSIONS	NUMBER	Indicates whether this child cursor has been marked to be kept pinned in the cache using the DBMS_SHARED_POOL package
ADDRESS	RAW(4 | 8)	Address of the handle to the parent for this cursor
TYPE_CHK_HEAP	RAW(4 | 8)	Descriptor of the type check heap for this child cursor
HASH_VALUE	NUMBER	Hash value of the parent statement in the library cache
OLD_HASH_VALUE	NUMBER	Old SQL hash value
PLAN_HASH_VALUE	NUMBER	Numeric representation of the current SQL plan for this cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line).
FULL_PLAN_HASH_VALUE	NUMBER	Numeric representation of the complete SQL plan for this cursor. Comparing one FULL_PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line). Note that the FULL_PLAN_HASH_VALUE cannot be compared across databases releases. It is not backward compatible.
CHILD_NUMBER	NUMBER	Number of this child cursor
SERVICE	VARCHAR2(64)	Service name
SERVICE_HASH	NUMBER	Hash value for the name listed in the SERVICE column
MODULE	VARCHAR2(64)	Contains the name of the module that was executing when the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_MODULE
MODULE_HASH	NUMBER	Hash value of the module listed in the MODULE column
ACTION	VARCHAR2(64)	Contains the name of the action that was executing when the SQL statement was first parsed, which is set by calling DBMS_APPLICATION_INFO.SET_ACTION
ACTION_HASH	NUMBER	Hash value of the action listed in the ACTION column
SERIALIZABLE_ABORTS	NUMBER	Number of times the transaction failed to serialize, producing ORA-08177 errors, per cursor
OUTLINE_CATEGORY	VARCHAR2(64)	If an outline was applied during construction of the cursor, then this column displays the category of that outline. Otherwise the column is left blank.

Column	Datatype	Description
CPU_TIME	NUMBER	CPU time (in microseconds) used by this cursor for parsing, executing, and fetching
ELAPSED_TIME	NUMBER	Elapsed database time (in microseconds) used by this cursor for parsing, executing, and fetching. If the cursor uses parallel execution, then ELAPSED_TIME is the cumulative time for the query coordinator, plus all parallel query worker processes. Note that this column displays database time, not wall clock time. In some cases, ELAPSED_TIME can exceed the duration of the query. For example, this can occur for parallel queries.
OUTLINE_SID	NUMBER	Outline session identifier
CHILD_ADDRESS	RAW(4 | 8)	Address of the child cursor
SQLTYPE	NUMBER	Denotes the version of the SQL language used for this statement
REMOTE	VARCHAR2(1)	Indicates whether the cursor is remote mapped (Y) or not (N)
OBJECT_STATUS	VARCHAR2(19)	Status of the cursor: • VALID - Valid, authorized without errors • VALID_AUTH_ERROR - Valid, authorized with authorization errors • VALID_COMPILE_ERROR - Valid, authorized with compilation errors • VALID_UNAUTH - Valid, unauthorized • INVALID_UNAUTH - Invalid, unauthorized • INVALID - Invalid, unauthorized but keep the timestamp
LITERAL_HASH_VALUE	NUMBER	Hash value of the literals which are replaced with system-generated bind variables and are to be matched, when CURSOR_SHARING is used. This is not the hash value for the SQL statement. If CURSOR_SHARING is not used, then the value is 0.
LAST_LOAD_TIME	VARCHAR2(76)	Time at which the query plan was loaded into the library cache
IS_OBSOLETE	VARCHAR2(1)	Indicates whether the cursor has become obsolete (Y) or not (N). This can happen if the number of child cursors is too large.
IS_BIND_SENSITIVE	VARCHAR2(1)	Indicates whether the cursor is bind sensitive (Y) or not (N). A query is considered bind-sensitive if the optimizer peeked at one of its bind variable values when computing predicate selectivities and where a change in a bind variable value may cause the optimizer to generate a different plan.
IS_BIND_AWARE	VARCHAR2(1)	Indicates whether the cursor is bind aware (Y) or not (N). A query is considered bind-aware if it has been marked to use extended cursor sharing. The query would already have been marked as bind-sensitive.
IS_SHAREABLE	VARCHAR2(1)	Indicates whether the cursor can be shared (Y) or not (N)
CHILD_LATCH	NUMBER	Child latch number that is protecting the cursor. This column is obsolete and maintained for backward compatibility.
SQL_PROFILE	VARCHAR2(64)	SQL profile used for this statement, if any
SQL_PATCH	VARCHAR2(128)	SQL patch used for this statement, if any
SQL_PLAN_BASELINE	VARCHAR2(128)	SQL plan baseline used for this statement, if any
PROGRAM_ID	NUMBER	Program identifier
PROGRAM_LINE#	NUMBER	Program line number

Column	Datatype	Description
EXACT_MATCHING_SIGNATURE	NUMBER	Signature calculated on the normalized SQL text. The normalization includes the removal of white space and the uppercasing of all non-literal strings.
FORCE_MATCHING_SIGNATURE	NUMBER	Signature used when the CURSOR_SHARING parameter is set to FORCE
LAST_ACTIVE_TIME	DATE	Time at which the query plan was last active
BIND_DATA	RAW(2000)	Bind data
TYPECHECK_MEM	NUMBER	Typecheck memory
IO_CELL_OFFLOAD_ELIGIBLE_BYTES	NUMBER	Number of I/O bytes which can be filtered by the Exadata storage system **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_INTERCONNECT_BYTES	NUMBER	Number of I/O bytes exchanged between Oracle Database and the storage system
PHYSICAL_READ_REQUESTS	NUMBER	Number of physical read I/O requests issued by the monitored SQL
PHYSICAL_READ_BYTES	NUMBER	Number of bytes read from disks by the monitored SQL
PHYSICAL_WRITE_REQUESTS	NUMBER	Number of physical write I/O requests issued by the monitored SQL
PHYSICAL_WRITE_BYTES	NUMBER	Number of bytes written to disks by the monitored SQL
OPTIMIZED_PHY_READ_REQUESTS	NUMBER	Number of physical read I/O requests from Database Smart Flash Cache issued by the monitored SQL
LOCKED_TOTAL	NUMBER	Total number of times the child cursor has been locked
PINNED_TOTAL	NUMBER	Total number of times the child cursor has been pinned
IO_CELL_UNCOMPRESSED_BYTES	NUMBER	Number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_CELL_OFFLOAD_RETURNED_BYTES	NUMBER	Number of filtered bytes returned by Exadata cells (that is, the number of bytes returned after processing has been offloaded on the Exadata cells) **See Also:** Oracle Exadata Storage Server Software documentation for more information
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
IS_REOPTIMIZABLE	VARCHAR2(1)	This column shows whether the next execution matching this child cursor will trigger a reoptimization. The values are: • Y: If the next execution will trigger a reoptimization • R: If the child cursor contains reoptimization information, but will not trigger reoptimization because the cursor was compiled in reporting mode • N: If the child cursor has no reoptimization information

Column	Datatype	Description
IS_RESOLVED_ADAPTIVE_PLAN	VARCHAR2(1)	This column shows whether all of the adaptive parts of a plan have been resolved to the final plan. Once the plan is resolved, the plan hash value and the plan displayed by DBMS_XPLAN will not change through the end of execution. The values for this column are: • NULL: If the plan is not adaptive • Y: If the plan is fully resolved • N: If the plan is not yet fully resolved **See Also:** *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_XPLAN package
IM_SCANS	NUMBER	Number of In-Memory Column Store (IM column store) segment scans
IM_SCAN_BYTES_UNCOMPRESSED	NUMBER	Uncompressed size of data scanned from the IM column store
IM_SCAN_BYTES_INMEMORY	NUMBER	In-memory size of data scanned from the IM column store
DDL_NO_INVALIDATE	VARCHAR2(1)	Indicates if a DDL statement updated a dependent object and did not invalidate this cursor. The values are: • N: There has not been a DDL statement that updated a dependent object without invalidating this cursor. • Y: A DDL statement updated a dependent object and did not invalidate this cursor, but the cursor has not executed since this happened. • X: A DDL statement updated a dependent object and did not invalidate this cursor, and the cursor has executed since this happened.
IS_ROLLING_INVALID	VARCHAR2(1)	Indicates if this cursor is rolling invalidated. The values are: • N: This cursor is not rolling invalidated. • Y: This cursor is rolling invalidated, but the cursor has not executed in this state. • X: This cursor is rolling invalidated, and the cursor has executed in this state.
IS_ROLLING_REFRESH_INVALID	VARCHAR2(1)	Indicates if this cursor is rolling invalidated and requires execution time refresh. The values are: • N: This cursor is not a cursor that is rolling invalidated and requires execution time refresh. • Y: This cursor is rolling invalidated and requires execution time refresh, but the cursor has not executed in this state. • X: This cursor is rolling invalidated and requires execution time refresh, and the cursor has executed in this state.
RESULT_CACHE	VARCHAR2(1)	Indicates whether the SQL statement used the result cache (Y) or not (N)
SQL_QUARANTINE	VARCHAR2(128)	If the execution plan for this cursor is quarantined, then this column contains the name of the SQL quarantine configuration (corresponds to the NAME column in the DBA_SQL_QUARANTINE view). Otherwise, this column is null.
AVOIDED_EXECUTIONS	NUMBER	Number of times this cursor was prevented from being used due to the plan being quarantined
HEAP0_LOAD_TIME	DATE	Time at which heap0 of the library cache object was loaded

Column	Datatype	Description
HEAP6_LOAD_TIME	DATE	Time at which heap6 of the library cache object was loaded A time difference of more than one minute between HEAP0_LOAD_TIME and HEAP6_LOAD_TIME indicates that heap6 has been partially reloaded. For example, the database might have aged out heap6 due to shared pool space pressure and reloaded it at a later time.
RESULT_CACHE_REJECTION_REASON	NUMBER	Numeric code representing the reason for a result cache rejection This column is populated when the query contains a result cache row source (RESULT_CACHE=Y), but fails to create or finish writing a result object. The reason for this failure is recorded as a numeric code in this column. See Table 10-2 for a list of rejection codes and recommended remedial actions. If the query does not contain a result cache row source (RESULT_CACHE=N) or the query reused an existing result, then the value of this column is null.

Table 10-2 Result Cache Rejection Reason Codes

Code	Reason for Result Cache Rejection	Recommended Remedial Action
0	Success	N/A
1000	Result size exceeds per-result limit for in-memory	Increase the value of one or both of the RESULT_CACHE_MAX_SIZE and RESULT_CACHE_MAX_RESULT initialization parameters, or enable spilling results to disk.
1001	Result size exceeds per-result limit on disk	Increase the value of one or both of the RESULT_CACHE_MAX_TEMP_SIZE and RESULT_CACHE_MAX_TEMP_RESULT initialization parameters.
2000	Unable to acquire enqueues	The system is busy; try again later.
2001	Unable to acquire a DML locks on a referenced object	The system is busy; try again later.
2002	Unable to acquire a row cache lock on referenced objects	The system is busy; try again later.
2003	Unable to allocate memory	The system is busy; try again later.
3000	Result cache ID for the query is blocklisted	Remove the cache ID from the blocklist by using the DBMS_RESULT_CACHE package. Exercise caution because the query may have been intentionally blocklisted.
3001	An object referenced in the query is blocklisted	Remove the object ID from the blocklist by using the DBMS_RESULT_CACHE package. Exercise caution because the object may have been intentionally blocklisted.
4001	Result cache is bypassed	The result cache was bypassed with DBMS_RESULT_CACHE.BYPASS or by setting the RESULT_CACHE_MAX_SIZE initialization parameter to 0. Exercise caution because the bypass may have been intentional.

Table 10-2 (Cont.) Result Cache Rejection Reason Codes

Code	Reason for Result Cache Rejection	Recommended Remedial Action
4002	Result cache is corrupt	Reset the result cache by using DBMS_RESULT_CACHE.FLUSH. If that does not resolve the problem, then restart the PDB or instance.
4003	RCBG process is down in Oracle RAC	Restart the Oracle RAC instance
4004	The query was only partially executed	The cursor should be fully executed. If the cursor is being executed as part of PL/SQL, then it should be fetched from until the NO_DATA_FOUND error is returned. If the cursor is being executed as part of a SQL query, then do not cancel it by terminating the process (such as typing CTRL+C).
4005	Temporary space cannot be allocated because the RCBG process is down	Restart the Oracle RAC instance
9999	Unknown reason	Unknown

See Also:

- "V$SQLTEXT"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SHARED_POOL package
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLICATION_INFO.SET_MODULE procedure
- *Oracle Database PL/SQL Packages and Types ReferenceOracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLICATION_INFO.SET_ACTION procedure
- *Oracle Database PL/SQL Packages and Types ReferenceOracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_XPLAN package

10.62 V$SQL_BIND_CAPTURE

V$SQL_BIND_CAPTURE displays information on bind variables used by SQL cursors. Each row in the view contains information for one bind variable defined in a cursor. This includes:

- Reference to the cursor defining the bind variable

  (hash_value, address) for the parent cursor and (hash_value, child_address) for the child cursor.
- Bind metadata

  Name, position, data type, character set ID, precision, scale, and maximum length of the bind variable.
- Bind data

One of the bind values used for the bind variable during a past execution of its associated SQL statement. Bind values are not always captured for this view. Bind values are displayed by this view only when the type of the bind variable is simple (this excludes LONG, LOB, and ADT data types) and when the bind variable is used in the WHERE or HAVING clauses of the SQL statement.

Bind capture is disabled when the STATISTICS_LEVEL initialization parameter is set to BASIC. This view can be joined with V$SQLAREA on (HASH_VALUE, ADDRESS) and with V$SQL on (HASH_VALUE, CHILD_ADDRESS).

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Address of the parent cursor
HASH_VALUE	NUMBER	Hash value of the parent cursor in the library cache. The hash value is a fixed index for the view and should always be used to speed up access to the view.
SQL_ID	VARCHAR2(13)	SQL identifier of the parent cursor in the library cache
CHILD_ADDRESS	RAW(4 | 8)	Address of the child cursor
CHILD_NUMBER	NUMBER	Child cursor number
NAME	VARCHAR2(128)	Name of the bind variable
POSITION	NUMBER	Position of the bind variable in the SQL statement
DUP_POSITION	NUMBER	If the binding is performed by name and the bind variable is duplicated, then this column gives the position of the primary bind variable.
DATATYPE	NUMBER	Internal identifier for the bind data type. Beginning in Oracle Database 12*c*, a number representing a PL/SQL data type can appear in this column.
DATATYPE_STRING	VARCHAR2(15)	Textual representation of the bind data type. Beginning in Oracle Database 12*c*, a text representation of a PL/SQL-only data type can appear in this column. If the actual data type is a PL/SQL sub type, the name of the data type, not the sub type will be displayed.
CHARACTER_SID	NUMBER	National character set identifier
PRECISION	NUMBER	Precision (for numeric binds)
SCALE	NUMBER	Scale (for numeric binds)
MAX_LENGTH	NUMBER	Maximum bind length
WAS_CAPTURED	VARCHAR2(3)	Indicates whether the bind value was captured (YES) or not (NO)
LAST_CAPTURED	DATE	Date when the bind value was captured. Bind values are captured when SQL statements are executed. To limit the overhead, binds are captured at most every 15 minutes for a given cursor.
VALUE_STRING	VARCHAR2(4000)	Value of the bind represented as a string
VALUE_ANYDATA	ANYDATA	Value of the bind represented using the ANYDATA data type. This representation is useful to programmatically decode the value of the bind variable. This column is NULL if a PL/SQL-only data type appears in the DATATYPE column.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "STATISTICS_LEVEL"
- "V$SQLAREA"
- "V$SQL"

10.63 V$SQL_BIND_DATA

V$SQL_BIND_DATA describes information related to bind variables.

V$SQL_BIND_DATA describes, for each distinct bind variable in each cursor owned by the session querying this view:

- Actual bind data, if the bind variable is user defined
- The underlying literal, if the CURSOR_SHARING parameter is set to FORCE and the bind variable is system generated. (System-generated binds have a value of 256 in the SHARED_FLAG2 column.)

Column	Datatype	Description
CURSOR_NUM	NUMBER	Cursor number for this bind
POSITION	NUMBER	Bind position
DATATYPE	NUMBER	Internal identifier for the bind data type. Beginning in Oracle Database 12*c*, a number representing a PL/SQL data type can appear in this column.
SHARED_MAX_LEN	NUMBER	Shared maximum length for this bind from the shared cursor object associated with this bind
PRIVATE_MAX_LEN	NUMBER	Private maximum length for this bind sent from the client
ARRAY_SIZE	NUMBER	Maximum number of array elements (for array binds only)
PRECISION	NUMBER	Precision (for numeric binds)
SCALE	NUMBER	Scale (for numeric binds)
SHARED_FLAG	NUMBER	Shared bind data flags
SHARED_FLAG2	NUMBER	Shared bind data flags (continued)
BUF_ADDRESS	RAW(4 | 8)	Bind buffer memory address
BUF_LENGTH	NUMBER	Bind buffer length

Column	Datatype	Description
VAL_LENGTH	NUMBER	Actual bind value length
BUF_FLAG	NUMBER	Bind buffer flags
INDICATOR	NUMBER	Bind indicator
VALUE	VARCHAR2(4000)	Contents of the bind buffer
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"CURSOR_SHARING"

10.64 V$SQL_BIND_METADATA

V$SQL_BIND_METADATA describes metadata related to bind variables.

V$SQL_BIND_METADATA describes, for each distinct bind variable in each cursor owned by the session querying this view:

- Bind metadata provided by the client, if the bind variable is user defined
- Metadata based on the underlying literal, if the CURSOR_SHARING parameter is set to FORCE and the bind variable is system-generated.

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Memory address of the child cursor that owns this bind variable
POSITION	NUMBER	Bind position
DATATYPE	NUMBER	Internal identifier for the bind data type. Beginning in Oracle Database 12*c*, a number representing a PL/SQL data type can appear in this column.
MAX_LENGTH	NUMBER	Maximum length of the bind value
ARRAY_LEN	NUMBER	Maximum number of array elements (for array binds only)
BIND_NAME	VARCHAR2(128)	User-defined or system-generated bind variable name (if used)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "CURSOR_SHARING"

10.65 V$SQL_CS_HISTOGRAM

V$SQL_CS_HISTOGRAM summarizes the monitoring information stored by adaptive cursor sharing. This information is used to decide whether to enable extended cursor sharing for a query. It is stored in a histogram, whose bucket's contents are exposed by this view.

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Address of the handle to the parent for this cursor
HASH_VALUE	NUMBER	Hash value of the parent statement in the library cache
SQL_ID	VARCHAR2(13)	SQL identifier of the parent cursor in the library cache
CHILD_NUMBER	NUMBER	Number of the child cursor being monitored
BUCKET_ID	NUMBER	Bucket number of the monitoring histogram
COUNT	NUMBER	Value in this bucket of the histogram
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.66 V$SQL_CS_SELECTIVITY

V$SQL_CS_SELECTIVITY exposes the valid selectivity ranges for a child cursor in extended cursor sharing mode. A valid range consists of a low and high value for each predicate containing binds. Each predicate's selectivity (with the current bind value) must fall between the corresponding low and high values in order for the child cursor to be shared.

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Address of the handle to the parent for this cursor
HASH_VALUE	NUMBER	Hash value of the parent statement in the library cache
SQL_ID	VARCHAR2(13)	SQL identifier of the parent cursor in the library cache
CHILD_NUMBER	NUMBER	Number of the child cursor
PREDICATE	VARCHAR2(40)	Predicate whose selectivity must fall between low and high values
RANGE_ID	NUMBER	Identifier for the range used to match up the low and high values for multiple predicates
LOW	VARCHAR2(10)	Lower bound for allowable selectivity
HIGH	VARCHAR2(10)	Upper bound for allowable selectivity

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.67 V$SQL_CS_STATISTICS

V$SQL_CS_STATISTICS contains the raw execution statistics used by the monitoring component of adaptive cursor sharing. A sample of the executions is monitored. This view exposes which executions were sampled, and what the statistics were for those executions. The statistics are cumulative for each distinct set of bind values.

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Address of the handle to the parent for this cursor
HASH_VALUE	NUMBER	Hash value of the parent statement in the library cache
SQL_ID	VARCHAR2(13)	SQL identifier of the parent cursor in the library cache
CHILD_NUMBER	NUMBER	Number of the child cursor being monitored
BIND_SET_HASH_VALUE	NUMBER	Hash of the values of the binds
PEEKED	VARCHAR2(1)	Indicates if this is the bind set used to build the cursor (Y) or not (N)
EXECUTIONS	NUMBER	Number of times this bind set has been executed and monitored
ROWS_PROCESSED	NUMBER	Cumulative number of rows processed by all row sources in the plan over all monitored executions with this bind set
BUFFER_GETS	NUMBER	Cumulative number of buffer gets over all monitored executions with this bind set
CPU_TIME	NUMBER	Cumulative CPU time (in microseconds) used by this cursor for monitored executions with this bind set
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.68 V$SQL_CURSOR

V$SQL_CURSOR displays debugging information for each cursor associated with the session querying this view.

Column	Datatype	Description
CURNO	NUMBER	Cursor number
FLAG	NUMBER	Flags set in the cursor
STATUS	VARCHAR2(9)	Status of the cursor; that is, what state the cursor is in
PARENT_HANDLE	RAW(4 | 8)	Pointer to the parent cursor handle
PARENT_LOCK	RAW(4 | 8)	Pointer to the parent cursor lock
CHILD_LOCK	RAW(4 | 8)	Pointer to the child cursor lock
CHILD_PIN	RAW(4 | 8)	Pointer to the child cursor pin
PERS_HEAP_MEM	NUMBER	Total amount of memory allocated from persistent heap for this cursor
WORK_HEAP_MEM	NUMBER	Total amount of memory allocated from the work heap for this cursor
BIND_VARS	NUMBER	Total number of bind positions in the query currently parsed into this cursor
DEFINE_VARS	NUMBER	Total number of define variables in the query currently parsed into this cursor
BIND_MEM_LOC	VARCHAR2(64)	Which memory heap the bind variables are stored in: either the UGA or the CGA
INST_FLAG	VARCHAR2(64)	Instantiation object flags
INST_FLAG2	VARCHAR2(64)	Instantiation object flags (continued)
CHILD_HANDLE	RAW(4 | 8)	Pointer to the child cursor handle
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.69 V$SQL_HISTORY

V$SQL_HISTORY displays SQL statements tracked by SQL history monitoring.

This view is populated only when the SQL_HISTORY initialization parameter is set to true.

Column	Datatype	Description
KEY	NUMBER	Artificial key to efficiently read a specific SQL history data entry For internal use only.
SQL_ID	VARCHAR2(13)	SQL identifier of the SQL statement
ELAPSED_TIME	NUMBER	Elapsed time (in microseconds) for the SQL statement
CPU_TIME	NUMBER	CPU time (in microseconds) for the SQL statement
BUFFER_GETS	NUMBER	Number of buffer get operations for the SQL statement
IO_INTERCONNECT_BYTES	NUMBER	Number of I/O bytes exchanged between Oracle Database and the storage system for the SQL statement

Column	Datatype	Description
PHYSICAL_READ_REQUESTS	NUMBER	Number of physical read I/O requests issued by the SQL statement
PHYSICAL_READ_BYTES	NUMBER	Number of bytes read from disk by the SQL statement
PHYSICAL_WRITE_REQUESTS	NUMBER	Number of physical write I/O requests issued by the SQL statement
PHYSICAL_WRITE_BYTES	NUMBER	Number of bytes written to disk by the SQL statement
PLSQL_EXEC_TIME	NUMBER	PL/SQL execution time (in microseconds) for the SQL statement
JAVA_EXEC_TIME	NUMBER	Java execution time (in microseconds) for the SQL statement
CLUSTER_WAIT_TIME	NUMBER	Cluster wait time (in microseconds) for the SQL statement
CONCURRENCY_WAIT_TIME	NUMBER	Concurrency wait time (in microseconds) for the SQL statement
APPLICATION_WAIT_TIME	NUMBER	Application wait time (in microseconds) for the SQL statement
USER_IO_WAIT_TIME	NUMBER	User I/O Wait Time (in microseconds) for the SQL statement
IO_CELL_UNCOMPRESSED_BYTES	NUMBER	Number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells for the SQL statement **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_CELL_OFFLOAD_ELIGIBLE_BYTES	NUMBER	Number of I/O bytes that can be filtered by the Exadata storage system for the SQL statement **See Also:** Oracle Exadata Storage Server Software documentation for more information
SQL_TEXT	VARCHAR2(100)	Up to the first 100 characters of the text of the SQL statement
PLAN_HASH_VALUE	NUMBER	SQL plan hash value
SQL_EXEC_ID	NUMBER	SQL execution identifier
SQL_EXEC_START	DATE	Time at which the SQL statement execution started
LAST_ACTIVE_TIME	DATE	Time at which the SQL statement execution was last active
SESSION_USER#	NUMBER	Unique ID number for the session user who issued the SQL statement
CURRENT_USER#	NUMBER	Unique number identifying the current user
CHILD_NUMBER	NUMBER	Child number of the SQL statement
SID	NUMBER	Session ID for the SQL statement's session
SESSION_SERIAL#	NUMBER	Session serial number for the SQL statement's session
MODULE_HASH	NUMBER	Hash value for the module name corresponding to the executing session
ACTION_HASH	NUMBER	Hash value for the action name corresponding to the executing session
SERVICE_HASH	NUMBER	Hash value for the service name corresponding to the executing session
IS_FULL_SQLTEXT	VARCHAR2(1)	Indicates whether the `SQL_TEXT` column displays the entire SQL text (`Y`) or not (`N`)
ERROR_SIGNALLED	VARCHAR2(1)	Indicates whether the SQL statement generated an error (`Y`) or not (`N`)
ERROR_NUMBER	NUMBER	If the SQL statement failed to execute, the error number (for example, `932` for error `ORA-00932`)

Column	Datatype	Description
ERROR_FACILITY	VARCHAR2(4)	If the SQL statement failed to execute, the error facility (for example, ORA for error ORA-00932)
STATEMENT_TYPE	VARCHAR2(5)	Type of SQL statement: • DDL • DML • PLSQL • QUERY • OTHER
IS_PARALLEL	VARCHAR2(1)	Indicates whether the SQL ran as a parallel execution (Y) or not (N)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

This view is available starting with Oracle Database 23ai.

See Also:

"SQL_HISTORY_ENABLED"

10.70 V$SQL_JOIN_FILTER

V$SQL_JOIN_FILTER displays performance information about the characteristics of join filters when they are used for a parallel cursor. (A join filter is a bitmap filter applied to table rows before a join operation in order to avoid parallel communication.)

Column	Datatype	Description
QC_SESSION_ID	NUMBER	QC (Query Coordinator) session ID of the given cursor for the given parallel query
QC_INSTANCE_ID	NUMBER	QC (Query Coordinator) instance ID of the given cursor for the given parallel query
SQL_PLAN_HASH_VALUE	NUMBER	SQL plan hash value of the given cursor for the given parallel query
FILTER_ID	NUMBER	An ID that identifies the join filter in the given cursor and corresponds to the filter ID in the execution plan
LENGTH	NUMBER	Total size of the join filter field
BITS_SET	NUMBER	Number of bits set in this filter

Column	Datatype	Description
FILTERED	NUMBER	Number of rows seen by the join filter
PROBED	NUMBER	Number of rows of the right table that have been tested against the bitmap filter. This is the sum of the filtered rows plus the non-filtered rows.
ACTIVE	NUMBER	Whether the filter is active (Yes) or not (No)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.71 V$SQL_MONITOR

V$SQL_MONITOR displays SQL statements whose execution have been (or are being) monitored by Oracle.

This view contains global, high-level information about simple and composite database operations.

Oracle Database monitors simple database operations, which are top SQL statements and PL/SQL subprograms, when any of the following conditions is true:

- The operations run in parallel.
- The operations have consumed at least 5 seconds of CPU or I/O time in a single execution.
- Tracking for the operations is forced by the /*+ MONITOR */ hint.

For simple database operations, monitoring statistics are not cumulative over several executions. In this case, one entry in V$SQL_MONITOR is dedicated to a single execution of a SQL statement. If the database monitors two executions of the same SQL statement, then each execution has a separate entry in V$SQL_MONITOR.

For simple database operations, V$SQL_MONITOR has one entry for the parallel execution coordinator process and one entry for each parallel execution server process. Each entry has corresponding entries in V$SQL_PLAN_MONITOR. Because the processes allocated for the parallel execution of a SQL statement are cooperating for the same execution, these entries share the same execution key (the combination of SQL_ID, SQL_EXEC_START, and SQL_EXEC_ID).

Oracle Database monitors composite database operations when either of the following conditions is true:

- A database operation was started with DBMS_SQL_MONITOR.BEGIN_OPERATION and the operation has consumed at least 5 seconds of CPU or I/O time.
- Tracking for the operation is forced by setting FORCE_TRACKING to Y in DBMS_SQL_MONITOR.BEGIN_OPERATION.

For composite database operations, each row contains an operation whose statistics are accumulated over the SQL statements and PL/SQL subprograms that run in the same session as part of the operation.

The V$SQL_MONITOR view contains a subset of the statistics available in V$SQL. However, unlike V$SQL, monitoring statistics are not cumulative over several executions. Instead, one entry in V$SQL_MONITOR is dedicated to a single execution of a SQL statement. If the database monitors two executions of the same SQL statement, then each execution has a separate entry in V$SQL_MONITOR.

The primary key is the combination of the columns SQL_ID, SQL_EXEC_START, and SQL_EXEC_ID.

V$SQL_MONITOR has one entry for the parallel execution coordinator process, and one entry for each parallel execution server process. Each entry has corresponding entries in V$SQL_PLAN_MONITOR. Because the processes allocated for the parallel execution of a SQL statement are cooperating for the same execution, these entries share the same execution key (the composite SQL_ID, SQL_EXEC_START, and SQL_EXEC_ID). You can aggregate the execution key to determine the overall statistics for a parallel execution.

When the SQL statement being monitored is executing, statistics in V$SQL_MONITOR are generally refreshed in near real time, once every second. Once the execution ends, monitoring information is not deleted immediately. Instead, it is kept in V$SQL_MONITOR for at least one minute. The entry will eventually be deleted to reclaim its space as new statements are monitored.

Column	Datatype	Description
KEY	NUMBER	Artificial join key to efficiently join V$SQL_MONITOR with its corresponding plan level monitoring statistics stored in V$SQL_PLAN_MONITOR
REPORT_ID	NUMBER	Unique ID of the XML report stored in Automatic Workload Repository (AWR) for this monitored entity
STATUS	VARCHAR2(19)	SQL execution status: • QUEUED - SQL statement is queued • EXECUTING - SQL statement is still executing • DONE (ERROR) - Execution terminated with an error • DONE (FIRST N ROWS) - Execution terminated by the application before all rows were fetched • DONE (ALL ROWS) - Execution terminated and all rows were fetched • DONE - Execution terminated (parallel execution)
USER#	NUMBER	User ID of the database user who issued the SQL being monitored
USERNAME	VARCHAR2(128)	User name of the database user who issued the SQL being monitored
MODULE	VARCHAR2(64)	Name of the executing module when sampled, as set by the DBMS_APPLICATION_INFO.SET_MODULE procedure
ACTION	VARCHAR2(64)	Name of the executing action when sampled, as set by the DBMS_APPLICATION_INFO.SET_ACTION procedure
SERVICE_NAME	VARCHAR2(64)	Service name of the user session
CLIENT_IDENTIFIER	VARCHAR2(64)	Client identifier from the user session
CLIENT_INFO	VARCHAR2(64)	Client information for the user session

Column	Datatype	Description
PROGRAM	VARCHAR2(84)	Name of the operating system program that issued the monitored SQL
PLSQL_ENTRY_OBJECT_ID	NUMBER	Object ID of the top-most PL/SQL subprogram on the stack; NULL if there is no PL/SQL subprogram on the stack
PLSQL_ENTRY_SUBPROGRAM_ID	NUMBER	Subprogram ID of the top-most PL/SQL subprogram on the stack; NULL if there is no PL/SQL subprogram on the stack
PLSQL_OBJECT_ID	NUMBER	Object ID of the currently executing PL/SQL subprogram; NULL if executing SQL
PLSQL_SUBPROGRAM_ID	NUMBER	Subprogram ID of the currently executing PL/SQL object; NULL if executing SQL
FIRST_REFRESH_TIME	DATE	Time when monitoring of the SQL statement started, generally a few seconds after execution start time
LAST_REFRESH_TIME	DATE	Time when statistics in V$SQL_MONITOR were last updated for the SQL statement. Statistics are generally refreshed every second when the statement executes.
REFRESH_COUNT	NUMBER	Number of times V$SQL_MONITOR statistics have been refreshed (generally once every second when the SQL statement executes)
DBOP_EXEC_ID	NUMBER	Database operation execution identifier for the current execution. If the type is SQL, the DBOP_EXEC_ID will be NULL.
DBOP_NAME	VARCHAR2(30)	Database operation name. If the type is SQL, the DBOP_NAME will be NULL.
SID	NUMBER	Session identifier executing (or having executed) the SQL statement being monitored
PROCESS_NAME	VARCHAR2(5)	Process name identifier executing (or having executed)the statement; ora if the process is foreground, else the background process name (for example, p001 for PX server p001)
SQL_ID	VARCHAR2(13)	SQL identifier of the statement being monitored
SQL_TEXT	VARCHAR2(2000)	Up to the first 2000 characters of the text of the SQL being monitored
IS_FULL_SQLTEXT	VARCHAR2(1)	Indicates whether the SQL_TEXT column has the entire SQL text (Y) or not (N)
SQL_EXEC_START	DATE	Time when the execution started
SQL_EXEC_ID	NUMBER	Execution identifier. Together, the three columns SQL_ID, SQL_EXEC_START, and SQL_EXEC_ID represent the execution key. The execution key is used to uniquely identify one execution of the SQL statement.
SQL_PLAN_HASH_VALUE	NUMBER	SQL plan hash value
SQL_FULL_PLAN_HASH_VALUE	NUMBER	Numeric representation of the complete SQL plan for this cursor. Comparing one SQL_FULL_PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line). Note that the SQL_FULL_PLAN_HASH_VALUE cannot be compared across databases releases. It is not backward compatible.
EXACT_MATCHING_SIGNATURE	NUMBER	Signature calculated on the normalized SQL text. The normalization includes the removal of white space and the uppercasing of all non-literal strings.
FORCE_MATCHING_SIGNATURE	NUMBER	Same as EXACT_MATCHING_SIGNATURE but literals in the SQL text are replaced by binds

Column	Datatype	Description
SQL_CHILD_ADDRESS	RAW(4 | 8)	Address of the child cursor (can be used with SQL_ID to join with V$SQL)
SESSION_SERIAL#	NUMBER	Session serial number executing the statement being monitored
PX_IS_CROSS_INSTANCE	VARCHAR2(1)	Indicates whether the SQL statement ran parallel across multiple instances (Y) or not (N)
PX_MAXDOP	NUMBER	Maximum degree of parallelism for any plan operation executed on behalf of the monitored SQL
PX_MAXDOP_INSTANCES	NUMBER	Number of database instances touched at the maximum degree of parallelism
PX_SERVERS_REQUESTED	NUMBER	Total number of parallel execution servers requested to execute the monitored SQL
PX_SERVERS_ALLOCATED	NUMBER	Actual number of parallel execution servers allocated to execute the query
PX_SERVER#	NUMBER	Logical parallel execution server process number executing (or having executed) the statement being monitored; NULL if this monitoring entry is not associated with an execution server. This is a logical number within the parallel server set (see SERVER# in V$PX_SESSION).
PX_SERVER_GROUP	NUMBER	Logical parallel execution server group number to which PX_SERVER# belongs (see SERVER_GROUP in V$PX_SESSION); NULL if this monitoring entry is not associated with a parallel execution server. This value is generally 1 unless the SQL statement has one or more parallel sub-queries.
PX_SERVER_SET	NUMBER	Number (1 or 2) of the logical set of parallel execution servers to which PX_SERVER# belongs (see SERVER_SET in V$PX_SESSION); NULL if this monitoring entry is not associated with a parallel execution server
PX_QCINST_ID	NUMBER	Instance identifier where the parallel execution coordinator runs; NULL if PX_SERVER# is NULL
PX_QCSID	NUMBER	Session identifier for the parallel execution coordinator; NULL if PX_SERVER# is NULL
ERROR_NUMBER	VARCHAR2(40)	Error number encountered in case a SQL fails to execute successfully (for example, 932 in case of ORA-00932)
ERROR_FACILITY	VARCHAR2(4)	Error facility in case a SQL fails to execute successfully (for example, ORA in case of ORA-00932)
ERROR_MESSAGE	VARCHAR2(256)	Detailed error message displayed corresponding to the error number and error facility when a SQL fails to execute successfully
BINDS_XML	CLOB	Information about bind variables used with the SQL, such as name, position, value, data type, and so on (stored in XML format)
OTHER_XML	CLOB	Additional information about SQL execution stored in XML format
ELAPSED_TIME	NUMBER	Elapsed time (in microseconds); updated as the statement executes
QUEUING_TIME	NUMBER	Duration of time (in microseconds) spent by SQL in the statement queue
CPU_TIME	NUMBER	CPU time (in microseconds); updated as the statement executes
FETCHES	NUMBER	Number of fetches associated with the SQL statement; updated as the statement executes

Column	Datatype	Description
BUFFER_GETS	NUMBER	Number of buffer get operations; updated as the statement executes
DISK_READS	NUMBER	Number of disk reads; updated as the statement executes
DIRECT_WRITES	NUMBER	Number of direct writes; updated as the statement executes
IO_INTERCONNECT_BYTES	NUMBER	Number of I/O bytes exchanged between Oracle Database and the storage system
PHYSICAL_READ_REQUESTS	NUMBER	Number of physical read I/O requests issued by the monitored SQL
PHYSICAL_READ_BYTES	NUMBER	Number of bytes read from disks by the monitored SQL
PHYSICAL_WRITE_REQUESTS	NUMBER	Number of physical write I/O requests issued by the monitored SQL
PHYSICAL_WRITE_BYTES	NUMBER	Number of bytes written to disks by the monitored SQL
APPLICATION_WAIT_TIME	NUMBER	Application wait time (in microseconds); updated as the statement executes
CONCURRENCY_WAIT_TIME	NUMBER	Concurrency wait time (in microseconds); updated as the statement executes
CLUSTER_WAIT_TIME	NUMBER	Cluster wait time (in microseconds); updated as the statement executes
USER_IO_WAIT_TIME	NUMBER	User I/O Wait Time (in microseconds); updated as the statement executes
PLSQL_EXEC_TIME	NUMBER	PL/SQL execution time (in microseconds); updated as the statement executes
JAVA_EXEC_TIME	NUMBER	Java execution time (in microseconds); updated as the statement executes
RM_LAST_ACTION	VARCHAR2(48)	The most recent action that was taken on this SQL operation by Resource Manager. Its value is one of the following: • CANCEL_SQL • KILL_SESSION • LOG_ONLY • SWITCH TO <CG NAME> For the last value, <CG NAME> is the name of the consumer group that the SQL operation was switched to. If the Resource Plan has since been changed then <CG NAME> is the ID of the consumer group.
RM_LAST_ACTION_REASON	VARCHAR2(128)	The reason for the most recent action that was taken on this SQL operation by Resource Manager. Its value is one of the following: • SWITCH_CPU_TIME • SWITCH_IO_REQS • SWITCH_IO_MBS • SWITCH_ELAPSED_TIME • SWITCH_IO_LOGICAL
RM_LAST_ACTION_TIME	DATE	The time of the most recent action that was taken on this SQL operation by Resource Manager
RM_CONSUMER_GROUP	VARCHAR2(128)	The current consumer group for this SQL operation

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
CON_NAME	VARCHAR2(128)	Container name of the object. The value of this column is NULL in non-CDBs.
ECID	VARCHAR2(64)	Execution context identifier (sent by Application Server)
IS_ADAPTIVE_PLAN	VARCHAR2(1)	Indicates whether the statistics are from an adaptive plan (Y) or not (N).
IS_FINAL_PLAN	VARCHAR2(1)	Indicates whether the statistics are from the final plan (Y) or not (N).
IN_DBOP_NAME	VARCHAR2(30)	If the SQL that is monitored was executed by a session that was also monitored by a database operation (DBOP), then this column specifies the name of that DBOP
IN_DBOP_EXEC_ID	NUMBER	If the SQL that is monitored was executed by a session that was also monitored by a database operation (DBOP), then this column specifies the execution ID of that DBO
IO_CELL_UNCOMPRESSED_BYTES	NUMBER	Number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_CELL_OFFLOAD_ELIGIBLE_BYTES	NUMBER	Number of I/O bytes which can be filtered by the Exadata storage system **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_CELL_OFFLOAD_RETURNED_BYTES	NUMBER	Number of filtered bytes returned by Exadata cells (that is, the number of bytes returned after processing has been offloaded on the Exadata cells) **See Also:** Oracle Exadata Storage Server Software documentation for more information
CURRENT_USER#	NUMBER	Unique number identifying the current user
CURRENT_USERNAME	VARCHAR2(128)	Username for the current user
PDB_REPORT_ID	NUMBER	Unique ID of the XML report of a PDB monitored entity that is stored in the CDB's Automatic Workload Repository (AWR) tables

See Also:

- "V$SQL_PLAN_MONITOR"
- *Oracle Database SQL Tuning Guide* for more information about monitoring database operations
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_APPLICATION_INFO.SET_MODULE` procedure
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the `DBMS_APPLICATION_INFO.SET_ACTION` procedure

10.72 V$SQL_MONITOR_SESSTAT

`V$SQL_MONITOR_SESSTAT` displays information about statistics that are exposed in `V$SESSTAT`.

Column	Datatype	Description
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
`KEY`	`NUMBER`	Artificial join key to efficiently join with other database operation views
`STATISTIC#`	`NUMBER`	Statistic number
`VALUE`	`NUMBER`	Value associated with the statistic

See Also:

"V$SESSTAT"

10.73 V$SQL_MONITOR_STATNAME

`V$SQL_MONITOR_STATNAME` provides information about the plan line statistics exposed in `V$SQL_PLAN_MONITOR`. A plan line statistic is identified by its group ID (column `GROUP_ID`) and its ID (column `ID`).

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
ID	NUMBER	Plan line statistic ID
GROUP_ID	NUMBER	Plan line statistic group ID
NAME	VARCHAR2(40)	Short name for the statistic
DESCRIPTION	VARCHAR2(200)	Short description for the statistic
TYPE	NUMBER	Reserved for internal use
FLAGS	NUMBER	Reserved for internal use

See Also:

"V$SQL_PLAN_MONITOR"

10.74 V$SQL_OPTIMIZER_ENV

V$SQL_OPTIMIZER_ENV displays the contents of the optimizer environment used to build the execution plan of a SQL cursor. This view can be joined with V$SQLAREA on (HASH_VALUE, ADDRESS) and with V$SQL on (HASH_VALUE, CHILD_ADDRESS).

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Address of the parent cursor
HASH_VALUE	NUMBER	Hash value of the parent cursor in the library cache. The hash value is the fixed index for the view and should be used when querying V$SQL_OPTIMIZER_ENV to avoid scanning the entire library cache.
SQL_ID	VARCHAR2(13)	SQL identifier
CHILD_ADDRESS	RAW(4 | 8)	Address of the child cursor
CHILD_NUMBER	NUMBER	Child cursor number
ID	NUMBER	Unique identifier of the parameter in the optimizer environment
NAME	VARCHAR2(40)	Name of the parameter
ISDEFAULT	VARCHAR2(3)	Indicates whether the parameter is set to the default value (YES) or not (NO)
VALUE	VARCHAR2(25)	Value of the parameter

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.75 V$SQL_PLAN

V$SQL_PLAN contains the execution plan information for each child cursor loaded in the library cache.

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Address of the handle to the parent for this cursor
HASH_VALUE	NUMBER	Hash value of the parent statement in the library cache. The two columns ADDRESS and HASH_VALUE can be used to join with V$SQLAREA to add the cursor-specific information.
SQL_ID	VARCHAR2(13)	SQL identifier of the parent cursor in the library cache
PLAN_HASH_VALUE	NUMBER	Numerical representation of the current SQL plan for this cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line).
FULL_PLAN_HASH_VALUE	NUMBER	Numeric representation of the complete SQL plan for this cursor. Comparing one FULL_PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line). Note that the FULL_PLAN_HASH_VALUE cannot be compared across databases releases. It is not backward compatible.
CHILD_ADDRESS	RAW(4 | 8)	Address of the child cursor
CHILD_NUMBER	NUMBER	Number of the child cursor that uses this execution plan. The columns ADDRESS, HASH_VALUE, and CHILD_NUMBER can be used to join with V$SQL to add the child cursor-specific information.
TIMESTAMP	DATE	Date and time when the execution plan was generated
OPERATION	VARCHAR2(30)	Name of the internal operation performed in this step (for example, TABLE ACCESS)
OPTIONS	VARCHAR2(30)	A variation on the operation described in the OPERATION column (for example, FULL)
OBJECT_NODE	VARCHAR2(40)	Name of the database link used to reference the object (a table name or view name). For local queries that use parallel execution, this column describes the order in which output from operations is consumed.
OBJECT#	NUMBER	Object number of the table or the index
OBJECT_OWNER	VARCHAR2(128)	Name of the user who owns the schema containing the table or index
OBJECT_NAME	VARCHAR2(128)	Name of the table or index

Column	Datatype	Description
OBJECT_ALIAS	VARCHAR2(261)	Alias for the object
OBJECT_TYPE	VARCHAR2(20)	Type of the object
OPTIMIZER	VARCHAR2(20)	Current mode of the optimizer for the first row in the plan (statement line), for example, ALL_ROWS. When the operation is a database access (for example, TABLE ACCESS), this column indicates whether or not the object is analyzed.
ID	NUMBER	A number assigned to each step in the execution plan
PARENT_ID	NUMBER	ID of the next execution step that operates on the output of the current step
DEPTH	NUMBER	Depth (or level) of the operation in the tree. It is not necessary to issue a CONNECT BY statement to get the level information, which is generally used to indent the rows from the PLAN_TABLE table. The root operation (statement) is level 0.
POSITION	NUMBER	Order of processing for all operations that have the same PARENT_ID
SEARCH_COLUMNS	NUMBER	Number of index columns with start and stop keys (that is, the number of columns with matching predicates)
COST	NUMBER	Cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
CARDINALITY	NUMBER	Estimate, by the cost-based optimizer, of the number of rows produced by the operation
BYTES	NUMBER	Estimate, by the cost-based optimizer, of the number of bytes produced by the operation
OTHER_TAG	VARCHAR2(35)	Describes the contents of the OTHER column. See EXPLAIN PLAN for values.
PARTITION_START	VARCHAR2(64)	Start partition of a range of accessed partitions
PARTITION_STOP	VARCHAR2(64)	Stop partition of a range of accessed partitions
PARTITION_ID	NUMBER	Step that computes the pair of values of the PARTITION_START and PARTITION_STOP columns
OTHER	VARCHAR2(4000)	Other information specific to the execution step that users may find useful. See EXPLAIN PLAN for values.
DISTRIBUTION	VARCHAR2(20)	Stores the method used to distribute rows from producer query servers to consumer query servers
CPU_COST	NUMBER	CPU cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
IO_COST	NUMBER	I/O cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
TEMP_SPACE	NUMBER	Temporary space usage of the operation (sort or hash-join) as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
ACCESS_PREDICATES	VARCHAR2(4000)	Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.
FILTER_PREDICATES	VARCHAR2(4000)	Predicates used to filter rows before producing them
PROJECTION	VARCHAR2(4000)	Expressions produced by the operation

Column	Datatype	Description
TIME	NUMBER	Elapsed time (in seconds) of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
QBLOCK_NAME	VARCHAR2(128)	Name of the query block
REMARKS	VARCHAR2(4000)	Remarks
OTHER_XML	CLOB	Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML since multiple pieces of information can be stored there. This includes: • Name of the schema against which the query was parsed • Release number of the Oracle Database that produced the explain plan • Hash value associated with the execution plan • Name (if any) of the outline or the SQL profile used to build the execution plan • Indication of whether or not dynamic statistics were used to produce the plan • The outline data, a set of optimizer hints that can be used to regenerate the same plan • Additional data that describes the relationship between rows in the plan table and subplans of adaptive plans.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.76 V$SQL_PLAN_MONITOR

V$SQL_PLAN_MONITOR displays plan level monitoring statistics for each SQL statement found in V$SQL_MONITOR. Each row in V$SQL_PLAN_MONITOR corresponds to an operation of the execution plan being monitored. As with V$SQL_MONITOR, statistics exposed in V$SQL_PLAN_MONITOR are generally updated every second when the statement executes. These statistics are recycled on the same basis as V$SQL_MONITOR.

To eliminate the overhead of SQL plan monitoring, statistics collected for each operation of the plan do not record timing information such as elapsed time, CPU time, or I/O time. Instead, this timing information can be estimated quite accurately by joining V$SQL_PLAN_MONITOR with V$ACTIVE_SESSION_HISTORY on SQL_ID, SQL_EXEC_START, SQL_EXEC_ID, and SQL_PLAN_LINE_ID (simply named PLAN_LINE_ID in V$SQL_PLAN_MONITOR). The result of that join is a sample of the activity performed by each operation in the plan, from which an estimate of CPU time and wait time can be derived. This can be achieved by breaking statement level monitoring time statistics found in V$SQL_MONITOR in proportion to the number of samples found in V$ACTIVE_SESSION_HISTORY for the corresponding activity type.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
KEY	NUMBER	Foreign key to efficiently join V$SQL_PLAN_MONITOR with V$SQL_MONITOR (see V$SQL_MONITOR)
STATUS	VARCHAR2(19)	SQL execution status: • EXECUTING - SQL statement is still executing • DONE (ERROR) - Execution terminated with an error • DONE (FIRST N ROWS) - Execution terminated by the application before all rows were fetched • DONE (ALL ROWS) - Execution terminated and all rows were fetched • DONE - Execution terminated (parallel execution)
FIRST_REFRESH_TIME	DATE	Time when monitoring of the SQL statement started
LAST_REFRESH_TIME	DATE	Time when statistics were last updated for the SQL statement
FIRST_CHANGE_TIME	DATE	First time a row was produced by this operation
LAST_CHANGE_TIME	DATE	Last time a row was produced by this operation
REFRESH_COUNT	NUMBER	Number of times statistics have been refreshed
SID	NUMBER	Session identifier executing (or having executed) the SQL statement being monitored
PROCESS_NAME	VARCHAR2(5)	Process name identifier
SQL_ID	VARCHAR2(13)	SQL identifier
SQL_EXEC_START	DATE	Time when the execution started
SQL_EXEC_ID	NUMBER	Execution identifier
SQL_PLAN_HASH_VALUE	NUMBER	SQL plan hash value
SQL_CHILD_ADDRESS	RAW(4 | 8)	Address of the child cursor
PLAN_PARENT_ID	NUMBER	ID of the next execution step that operates on the output of the current step
PLAN_LINE_ID	NUMBER	Plan line number for the entry
PLAN_OPERATION	VARCHAR2(30)	Plan operation name (from V$SQL_PLAN)
PLAN_OPTIONS	VARCHAR2(30)	Plan option name (from V$SQL_PLAN)
PLAN_OBJECT_OWNER	VARCHAR2(128)	Name of the user who owns the schema containing the table or index
PLAN_OBJECT_NAME	VARCHAR2(128)	Name of the table or index
PLAN_OBJECT_TYPE	VARCHAR2(80)	Type of the object
PLAN_DEPTH	NUMBER	Depth (or level) of the operation in the tree. It is not necessary to issue a CONNECT BY statement to get the level information, which is generally used to indent the rows from the PLAN_TABLE table. The root operation (statement) is level 0.

Column	Datatype	Description
PLAN_POSITION	NUMBER	Order of processing for all operations that have the same PARENT_ID
PLAN_COST	NUMBER	Cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
PLAN_CARDINALITY	NUMBER	Estimate, by the cost-based optimizer, of the number of rows produced by the operation
PLAN_BYTES	NUMBER	Estimate, by the cost-based optimizer, of the number of bytes produced by the operation
PLAN_TIME	NUMBER	Elapsed time (in seconds) of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
PLAN_PARTITION_START	VARCHAR2(256)	Start partition of a range of accessed partitions
PLAN_PARTITION_STOP	VARCHAR2(256)	Stop partition of a range of accessed partitions
PLAN_CPU_COST	NUMBER	CPU cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
PLAN_IO_COST	NUMBER	I/O cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
PLAN_TEMP_SPACE	NUMBER	Temporary space usage of the operation (sort or hash-join) as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is NULL.
STARTS	NUMBER	Number of times this operation was executed. For example, an operation is executed multiple times when it is on the right side of a nested-loop join (once for each row of the left input of that nested-loop join).
OUTPUT_ROWS	NUMBER	Number of rows produced by this operation since the execution started. This number is cumulated for all executions of this operation. Divide by the value of the STARTS column to compute the average number of rows per execution of the operation. Note that the value in the STARTS column is equal to or higher than the value in the OUTPUT_ROWS column. The value will usually be equal, but depending on internal optimizations a higher value may be seen.
IO_INTERCONNECT_BYTES	NUMBER	Number of I/O bytes exchanged between Oracle Database and the storage system. Maintained only after Oracle starts to monitor the execution.
PHYSICAL_READ_REQUESTS	NUMBER	Number of physical read I/O requests issued by the monitored SQL. Maintained only after Oracle starts to monitor the execution.
PHYSICAL_READ_BYTES	NUMBER	Number of bytes read from disks by the monitored SQL. Maintained only after Oracle starts to monitor the execution.
PHYSICAL_WRITE_REQUESTS	NUMBER	Number of physical write I/O requests issued by the monitored SQL. Maintained only after Oracle starts to monitor the execution.
PHYSICAL_WRITE_BYTES	NUMBER	Number of bytes written to disks by the monitored SQL. Maintained only after Oracle starts to monitor the execution.
WORKAREA_MEM	NUMBER	Amount of memory (in bytes) used by the operation when the query is executing; NULL if the execution is done. This applies only to operations using a work area, such as sort, hash-join, group-by, and so on.

Column	Datatype	Description
WORKAREA_MAX_MEM	NUMBER	Maximum value (in bytes) for WORKAREA_MEM; NULL if the operation is not using a work area. When the execution is finished, this value will hold the maximum amount of memory consumed by this operation during the execution of the statement.
WORKAREA_TEMPSEG	NUMBER	Amount of temporary space (in bytes) used by the operation when the query is executing; NULL if the operation has not spilled to disk or if the execution is finished
WORKAREA_MAX_TEMPSEG	NUMBER	Maximum value (in bytes) for WORKAREA_TEMPSEG; NULL if this operation never spilled to disk. When the execution is done, this value will hold the maximum amount of temporary space consumed by this operation during the entire execution.
OTHERSTAT_GROUP_ID	NUMBER	Plan line statistic group identifier (see GROUP_ID column in V$SQL_MONITOR_STATNAME)
OTHERSTAT_1_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 1 of that plan line
OTHERSTAT_1_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_1_VALUE	NUMBER	Value of statistic number 1 of that plan line
OTHERSTAT_2_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 2 of that plan line
OTHERSTAT_2_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_2_VALUE	NUMBER	Value of statistic number 2 of that plan line
OTHERSTAT_3_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 3 of that plan line
OTHERSTAT_3_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_3_VALUE	NUMBER	Value of statistic number 3 of that plan line
OTHERSTAT_4_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 4 of that plan line
OTHERSTAT_4_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_4_VALUE	NUMBER	Value of statistic number 4 of that plan line
OTHERSTAT_5_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 5 of that plan line
OTHERSTAT_5_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_5_VALUE	NUMBER	Value of statistic number 5 of that plan line
OTHERSTAT_6_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 6 of that plan line
OTHERSTAT_6_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_6_VALUE	NUMBER	Value of statistic number 6 of that plan line
OTHERSTAT_7_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 7 of that plan line
OTHERSTAT_7_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_7_VALUE	NUMBER	Value of statistic number 7 of that plan line
OTHERSTAT_8_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 8 of that plan line
OTHERSTAT_8_TYPE	NUMBER	Reserved for internal use

Column	Datatype	Description
OTHERSTAT_8_VALUE	NUMBER	Value of statistic number 8 of that plan line
OTHERSTAT_9_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 9 of that plan line
OTHERSTAT_9_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_9_VALUE	NUMBER	Value of statistic number 9 of that plan line
OTHERSTAT_10_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 10 of that plan line
OTHERSTAT_10_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_10_VALUE	NUMBER	Value of statistic number 10 of that plan line
OTHERSTAT_11_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 11 of that plan line
OTHERSTAT_11_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_11_VALUE	NUMBER	Value of statistic number 11 of that plan line
OTHERSTAT_12_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 12 of that plan line
OTHERSTAT_12_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_12_VALUE	NUMBER	Value of statistic number 12 of that plan line
OTHERSTAT_13_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 13 of that plan line
OTHERSTAT_13_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_13_VALUE	NUMBER	Value of statistic number 13 of that plan line
OTHERSTAT_14_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 14 of that plan line
OTHERSTAT_14_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_14_VALUE	NUMBER	Value of statistic number 14 of that plan line
OTHERSTAT_15_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 15 of that plan line
OTHERSTAT_15_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_15_VALUE	NUMBER	Value of statistic number 15 of that plan line
OTHERSTAT_16_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 16 of that plan line
OTHERSTAT_16_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_16_VALUE	NUMBER	Value of statistic number 16 of that plan line
OTHERSTAT_17_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 17 of that plan line
OTHERSTAT_17_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_17_VALUE	NUMBER	Value of statistic number 17 of that plan line
OTHERSTAT_18_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 18 of that plan line
OTHERSTAT_18_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_18_VALUE	NUMBER	Value of statistic number 18 of that plan line
OTHERSTAT_19_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 19 of that plan line

Column	Datatype	Description
OTHERSTAT_19_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_19_VALUE	NUMBER	Value of statistic number 19 of that plan line
OTHERSTAT_20_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 20 of that plan line
OTHERSTAT_20_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_20_VALUE	NUMBER	Value of statistic number 20 of that plan line
OTHERSTAT_21_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 21 of that plan line
OTHERSTAT_21_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_21_VALUE	NUMBER	Value of statistic number 21 of that plan line
OTHERSTAT_22_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 22 of that plan line
OTHERSTAT_22_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_22_VALUE	NUMBER	Value of statistic number 22 of that plan line
OTHERSTAT_23_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 23 of that plan line
OTHERSTAT_23_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_23_VALUE	NUMBER	Value of statistic number 23 of that plan line
OTHERSTAT_24_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 24 of that plan line
OTHERSTAT_24_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_24_VALUE	NUMBER	Value of statistic number 24 of that plan line
OTHERSTAT_25_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 25 of that plan line
OTHERSTAT_25_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_25_VALUE	NUMBER	Value of statistic number 25 of that plan line
OTHERSTAT_26_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 26 of that plan line
OTHERSTAT_26_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_26_VALUE	NUMBER	Value of statistic number 26 of that plan line
OTHERSTAT_27_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 27 of that plan line
OTHERSTAT_27_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_27_VALUE	NUMBER	Value of statistic number 27 of that plan line
OTHERSTAT_28_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 28 of that plan line
OTHERSTAT_28_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_28_VALUE	NUMBER	Value of statistic number 28 of that plan line
OTHERSTAT_29_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 29 of that plan line
OTHERSTAT_29_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_29_VALUE	NUMBER	Value of statistic number 29 of that plan line

Column	Datatype	Description
OTHERSTAT_30_ID	NUMBER	Statistic identifier (see ID column in V$SQL_MONITOR_STATNAME) for statistic number 30 of that plan line
OTHERSTAT_30_TYPE	NUMBER	Reserved for internal use
OTHERSTAT_30_VALUE	NUMBER	Value of statistic number 30 of that plan line
OTHER_XML	CLOB	Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML because it allows multiple pieces of information to be stored, including the following: • Name of the schema against which the query was parsed • Release number of the Oracle Database that produced the explain plan • Hash value associated with the execution plan • Name (if any) of the outline or the SQL profile used to build the execution plan • Indication of whether or not dynamic statistics were used to produce the plan • The outline data, a set of optimizer hints that can be used to regenerate the same plan
PLAN_OPERATION_INACTIVE	NUMBER	Indicates whether this plan operation was part of the final resolved plan

See Also:

"V$SQL_MONITOR_STATNAME"

10.77 V$SQL_PLAN_STATISTICS

V$SQL_PLAN_STATISTICS provides execution statistics at the row source level for each child cursor.

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Address of the handle to the parent for this cursor
HASH_VALUE	NUMBER	Hash value of the parent statement in the library cache. The two columns ADDRESS and HASH_VALUE can be used to join with V$SQLAREA to locate the parent cursor.
SQL_ID	VARCHAR2(13)	SQL identifier of the parent statement in the library cache
PLAN_HASH_VALUE	NUMBER	Numerical representation of the current SQL plan for this cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line)
FULL_PLAN_HASH_VALUE	NUMBER	Numeric representation of the complete SQL plan for this cursor. Comparing one FULL_PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line). Note that the FULL_PLAN_HASH_VALUE cannot be compared across databases releases. It is not backward compatible.

Column	Datatype	Description
CHILD_ADDRESS	RAW(4 | 8)	Address of the child cursor
CHILD_NUMBER	NUMBER	Number of the child cursor that uses this work area. The columns ADDRESS, HASH_VALUE, and CHILD_NUMBER can be used to join with V$SQL to locate the child cursor using this area.
OPERATION_ID	NUMBER	A number assigned to each step in the execution plan
EXECUTIONS	NUMBER	Number of times this cursor has been executed
LAST_STARTS	NUMBER	Number of times this operation has been started, during the last execution
STARTS	NUMBER	Number of times this operation has been started, accumulated over the past executions
LAST_OUTPUT_ROWS	NUMBER	Number of rows produced by the row source, during the last execution
OUTPUT_ROWS	NUMBER	Number of rows produced by the row source, accumulated over the past executions
LAST_CR_BUFFER_GETS	NUMBER	Number of buffers retrieved in consistent mode, during the last execution. Buffers are usually retrieved in consistent mode for queries.
CR_BUFFER_GETS	NUMBER	Number of buffers retrieved in consistent mode, accumulated over the past executions. Buffers are usually retrieved in consistent mode for queries.
LAST_CU_BUFFER_GETS	NUMBER	Number of buffers retrieved in current mode, during the last execution. Buffers are retrieved in current mode for statements such as INSERT, UPDATE, and DELETE.
CU_BUFFER_GETS	NUMBER	Number of buffers retrieved in current mode, accumulated over the past executions. Buffers are retrieved in current mode for statements such as INSERT, UPDATE, and DELETE.
LAST_DISK_READS	NUMBER	Number of physical disk reads performed by the operation, during the last execution
DISK_READS	NUMBER	Number of physical disk reads performed by the operation, accumulated over the past executions
LAST_DISK_WRITES	NUMBER	Number of physical disk writes performed by the operation, during the last execution
DISK_WRITES	NUMBER	Number of physical disk writes performed by the operation, accumulated over the past executions
LAST_ELAPSED_TIME	NUMBER	Elapsed time (in microseconds) corresponding to this operation, during the last execution
ELAPSED_TIME	NUMBER	Elapsed time (in microseconds) corresponding to this operation, accumulated over the past executions
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$SQLAREA"

10.78 V$SQL_PLAN_STATISTICS_ALL

V$SQL_PLAN_STATISTICS_ALL contains memory usage statistics for row sources that use SQL memory (sort or hash-join). This view concatenates information in V$SQL_PLAN with execution statistics from V$SQL_PLAN_STATISTICS and V$SQL_WORKAREA.

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Address of the handle to the parent for this cursor
HASH_VALUE	NUMBER	Hash value of the parent statement in the library cache. The two columns ADDRESS and HASH_VALUE can be used to join with V$SQLAREA to add the cursor-specific information.
SQL_ID	VARCHAR2(13)	SQL identifier of the parent statement in the library cache
PLAN_HASH_VALUE	NUMBER	Numerical representation of the current SQL plan for this cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line)
FULL_PLAN_HASH_VALUE	NUMBER	Numeric representation of the complete SQL plan for this cursor. Comparing one FULL_PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line). Note that the FULL_PLAN_HASH_VALUE cannot be compared across databases releases. It is not backward compatible.
CHILD_ADDRESS	RAW(4 | 8)	Address of the child cursor
CHILD_NUMBER	NUMBER	Number of the child cursor that uses this execution plan. The columns ADDRESS, HASH_VALUE, and CHILD_NUMBER can be used to join with V$SQL to add the child cursor-specific information.
TIMESTAMP	DATE	Date and time when the execution plan was generated
OPERATION	VARCHAR2(30)	Name of the internal operation performed in this step (for example, TABLE ACCESS)
OPTIONS	VARCHAR2(30)	A variation on the operation described in the OPERATION column (for example, FULL)
OBJECT_NODE	VARCHAR2(40)	Name of the database link used to reference the object (a table name or view name). For local queries that use parallel execution, this column describes the order in which output from operations is consumed.
OBJECT#	NUMBER	Object number of the table or the index
OBJECT_OWNER	VARCHAR2(128)	Name of the user who owns the schema containing the table or index
OBJECT_NAME	VARCHAR2(128)	Name of the table or index
OBJECT_ALIAS	VARCHAR2(261)	Alias for the object
OBJECT_TYPE	VARCHAR2(20)	Type of the object

Column	Datatype	Description
OPTIMIZER	VARCHAR2(20)	Current mode of the optimizer for the first row in the plan (statement line), for example, CHOOSE. When the operation is a database access (for example, TABLE ACCESS), this column indicates whether or not the object is analyzed.
ID	NUMBER	A number assigned to each step in the execution plan
PARENT_ID	NUMBER	ID of the next execution step that operates on the output of the current step
DEPTH	NUMBER	Depth (or level) of the operation in the tree. It is not necessary to issue a CONNECT BY statement to get the level information, which is generally used to indent the rows from the PLAN_TABLE table. The root operation (statement) is level 0.
POSITION	NUMBER	Order of processing for all operations that have the same PARENT_ID
SEARCH_COLUMNS	NUMBER	Number of index columns with start and stop keys (that is, the number of columns with matching predicates)
COST	NUMBER	Cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
CARDINALITY	NUMBER	Estimate, by the cost-based optimizer, of the number of rows produced by the operation
BYTES	NUMBER	Estimate, by the cost-based optimizer, of the number of bytes produced by the operation
OTHER_TAG	VARCHAR2(35)	Describes the contents of the OTHER column. See EXPLAIN PLAN for values.
PARTITION_START	VARCHAR2(64)	Start partition of a range of accessed partitions
PARTITION_STOP	VARCHAR2(64)	Stop partition of a range of accessed partitions
PARTITION_ID	NUMBER	Step that computes the pair of values of the PARTITION_START and PARTITION_STOP columns
OTHER	VARCHAR2(4000)	Other information specific to the execution step that users may find useful. See EXPLAIN PLAN for values.
DISTRIBUTION	VARCHAR2(20)	Stores the method used to distribute rows from producer query servers to consumer query servers
CPU_COST	NUMBER	CPU cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
IO_COST	NUMBER	I/O cost of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
TEMP_SPACE	NUMBER	Temporary space usage of the operation (sort or hash-join) as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
ACCESS_PREDICATES	VARCHAR2(4000)	Predicates used to locate rows in an access structure. For example, start or stop predicates for an index range scan.
FILTER_PREDICATES	VARCHAR2(4000)	Predicates used to filter rows before producing them
PROJECTION	VARCHAR2(4000)	Expressions produced by the operation

Column	Datatype	Description
TIME	NUMBER	Elapsed time (in seconds) of the operation as estimated by the optimizer's cost-based approach. For statements that use the rule-based approach, this column is null.
QBLOCK_NAME	VARCHAR2(128)	Name of the query block
REMARKS	VARCHAR2(4000)	Remarks
OTHER_XML	CLOB	Provides extra information specific to an execution step of the execution plan. The content of this column is structured using XML since multiple pieces of information can be stored there. This includes: • Name of the schema against which the query was parsed • Release number of the Oracle Database that produced the explain plan • Hash value associated with the execution plan • Name (if any) of the outline or the SQL profile used to build the execution plan • Indication of whether or not dynamic statistics were used to produce the plan • The outline data, a set of optimizer hints that can be used to regenerate the same plan • Additional data that describes the relationship between rows in the plan table and subplans of adaptive plans.
EXECUTIONS	NUMBER	Number of times this cursor has been executed
LAST_STARTS	NUMBER	Number of times this operation has been started, during the last execution
STARTS	NUMBER	Number of times this operation has been started, accumulated over the past executions
LAST_OUTPUT_ROWS	NUMBER	Number of rows produced by the row source, during the last execution
OUTPUT_ROWS	NUMBER	Number of rows produced by the row source, accumulated over the past executions
LAST_CR_BUFFER_GETS	NUMBER	Number of buffers retrieved in consistent mode, during the last execution. Buffers are usually retrieved in consistent mode for queries.
CR_BUFFER_GETS	NUMBER	Number of buffers retrieved in consistent mode, accumulated over the past executions. Buffers are usually retrieved in consistent mode for queries.
LAST_CU_BUFFER_GETS	NUMBER	Number of buffers retrieved in current mode, during the last execution. Buffers are retrieved in current mode for statements such as INSERT, UPDATE, and DELETE.
CU_BUFFER_GETS	NUMBER	Number of buffers retrieved in current mode, accumulated over the past executions. Buffers are retrieved in current mode for statements such as INSERT, UPDATE, and DELETE.
LAST_DISK_READS	NUMBER	Number of physical disk reads performed by the operation, during the last execution
DISK_READS	NUMBER	Number of physical disk reads performed by the operation, accumulated over the past executions
LAST_DISK_WRITES	NUMBER	Number of physical disk writes performed by the operation, during the last execution

Column	Datatype	Description
DISK_WRITES	NUMBER	Number of physical disk writes performed by the operation, accumulated over the past executions
LAST_ELAPSED_TIME	NUMBER	Elapsed time (in microseconds) corresponding to this operation, during the last execution
ELAPSED_TIME	NUMBER	Elapsed time (in microseconds) corresponding to this operation, accumulated over the past executions
POLICY	VARCHAR2(10)	Sizing policy for this work area: • MANUAL • AUTO
ESTIMATED_OPTIMAL_SIZE	NUMBER	Estimated size (in KB) required by this work area to execute the operation completely in memory (optimal execution). This is either derived from optimizer statistics or from previous executions.
ESTIMATED_ONEPASS_SIZE	NUMBER	Estimated size (in KB) required by this work area to execute the operation in a single pass. This is either derived from optimizer statistics or from previous executions.
LAST_MEMORY_USED	NUMBER	Memory size (in KB) used by this work area during the last execution of the cursor
LAST_EXECUTION	VARCHAR2(10)	Indicates whether this work area ran using OPTIMAL, ONE PASS, or under ONE PASS memory requirement (MULTI-PASS), during the last execution of the cursor
LAST_DEGREE	NUMBER	Degree of parallelism used, during the last execution of the cursor
TOTAL_EXECUTIONS	NUMBER	Number of times this work area was active
OPTIMAL_EXECUTIONS	NUMBER	Number of times this work area ran in optimal mode
ONEPASS_EXECUTIONS	NUMBER	Number of times this work area ran in one pass mode
MULTIPASSES_EXECUTIONS	NUMBER	Number of times this work area ran below the one pass memory requirement
ACTIVE_TIME	NUMBER	Average time this work area is active (in hundredths of a second)
MAX_TEMPSEG_SIZE	NUMBER	Maximum temporary segment size (in bytes) created by an instantiation of this work area. This column is null if this work area has never spilled to disk.
LAST_TEMPSEG_SIZE	NUMBER	Temporary segment size (in bytes) created in the last instantiation of this work area. This column is null if the last instantiation of this work area did not spill to disk.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
CON_DBID	NUMBER	The database ID of the PDB

> **See Also:**
>
> - "V$SQL_PLAN_STATISTICS"
> - "V$SQL_WORKAREA"

10.79 V$SQL_REDIRECTION

V$SQL_REDIRECTION displays SQL statements that are redirected.

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Address of the cursor handle
PARENT_HANDLE	RAW(4 | 8)	Address of the parent cursor handle
HASH_VALUE	NUMBER	Hash value of the SQL statement
SQL_ID	VARCHAR2(13)	SQL identifier of the SQL statement
CHILD_NUMBER	NUMBER	Number of the child (instance) for the hash
PARSING_USER_ID	NUMBER	Parsing user ID
PARSING_SCHEMA_ID	NUMBER	Parsing schema ID
COMMAND_TYPE	NUMBER	SELECT, UPDATE, INSERT, MERGE
REASON	VARCHAR2(14)	Reason for redirection ('INVALID OBJECT', 'ROWID', 'QUERY REWRITE', 'READ ONLY')
ERROR_CODE	NUMBER	Error code for local parse
POSITION	NUMBER	Error position, 0 if unknown
SQL_TEXT_PIECE	VARCHAR2(1000)	SQL Text containing position, usually a (qualified) identifier
ERROR_MESSAGE	VARCHAR2(1000)	Error code's corresponding error message resolved in the database language, no arguments resolved
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.80 V$SQL_SHARD

V$SQL_SHARD displays the shard information for a shard query's previous execution. This view uniquely maps a shard SQL fragment of a cross shard query to the target shard database.

Column	Datatype	Description
SQL_ID	VARCHAR2(13)	SQL identifier of a cross shard query on the coordinator
CHILD_NUMBER	NUMBER	Cursor child number of a cross shard query on the coordinator

Column	Datatype	Description
OPERATION_ID	NUMBER	Operation ID of a remote node for a shard SQL fragment of a cross shard query
SHARD_SQL_ID	VARCHAR2(13)	SQL ID of the SQL segment associated with a remote operation identified by the operation ID in the OPERATION_ID column
SHARD_ID	NUMBER	IDs of shards where the shard SQL fragment was executed
SHARD_CHILD_NUMBER	NUMBER	Cursor child number of a shard SQL fragment on a shard. The default value is 0.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

Oracle Globally Distributed Database Guide for more information about the V$SQL_SHARD view

10.81 V$SQL_SHARED_CURSOR

V$SQL_SHARED_CURSOR explains why a particular child cursor is not shared with existing child cursors. Each column identifies a specific reason why the cursor cannot be shared.

Column	Datatype	Description
SQL_ID	VARCHAR2(13)	SQL identifier
ADDRESS	RAW(4 | 8)	Address of the parent cursor
CHILD_ADDRESS	RAW(4 | 8)	Address of the child cursor
CHILD_NUMBER	NUMBER	Child number
UNBOUND_CURSOR	VARCHAR2(1)	(Y|N) The existing child cursor was not fully built (in other words, it was not optimized)
SQL_TYPE_MISMATCH	VARCHAR2(1)	(Y|N) The SQL type does not match the existing child cursor
OPTIMIZER_MISMATCH	VARCHAR2(1)	(Y|N) The optimizer environment does not match the existing child cursor
OUTLINE_MISMATCH	VARCHAR2(1)	(Y|N) The outlines do not match the existing child cursor
STATS_ROW_MISMATCH	VARCHAR2(1)	(Y|N) The existing statistics do not match the existing child cursor
LITERAL_MISMATCH	VARCHAR2(1)	(Y|N) Non-data literal values do not match the existing child cursor
FORCE_HARD_PARSE	VARCHAR2(1)	(Y|N) For internal use
EXPLAIN_PLAN_CURSOR	VARCHAR2(1)	(Y|N) The child cursor is an explain plan cursor and should not be shared

Column	Datatype	Description
BUFFERED_DML_MISMATCH	VARCHAR2(1)	(Y|N) Buffered DML does not match the existing child cursor
PDML_ENV_MISMATCH	VARCHAR2(1)	(Y|N) PDML environment does not match the existing child cursor
INST_DRTLD_MISMATCH	VARCHAR2(1)	(Y|N) Insert direct load does not match the existing child cursor
SLAVE_QC_MISMATCH	VARCHAR2(1)	(Y|N) The existing child cursor is a worker cursor and the new one was issued by the coordinator (or, the existing child cursor was issued by the coordinator and the new one is a worker cursor)
TYPECHECK_MISMATCH	VARCHAR2(1)	(Y|N) The existing child cursor is not fully optimized
AUTH_CHECK_MISMATCH	VARCHAR2(1)	(Y|N) Authorization/translation check failed for the existing child cursor
BIND_MISMATCH	VARCHAR2(1)	(Y|N) The bind metadata does not match the existing child cursor
DESCRIBE_MISMATCH	VARCHAR2(1)	(Y|N) The typecheck heap is not present during the describe for the child cursor
LANGUAGE_MISMATCH	VARCHAR2(1)	(Y|N) The language handle does not match the existing child cursor
TRANSLATION_MISMATCH	VARCHAR2(1)	(Y|N) The base objects of the existing child cursor do not match
BIND_EQUIV_FAILURE	VARCHAR2(1)	(Y|N) The bind value's selectivity does not match that used to optimize the existing child cursor
INSUFF_PRIVS	VARCHAR2(1)	(Y|N) Insufficient privileges on objects referenced by the existing child cursor
INSUFF_PRIVS_REM	VARCHAR2(1)	(Y|N) Insufficient privileges on remote objects referenced by the existing child cursor
REMOTE_TRANS_MISMATCH	VARCHAR2(1)	(Y|N) The remote base objects of the existing child cursor do not match
LOGMINER_SESSION_MISMATCH	VARCHAR2(1)	(Y|N) LogMiner Session parameters mismatch
INCOMP_LTRL_MISMATCH	VARCHAR2(1)	(Y|N) Cursor might have some binds (literals) which may be unsafe/non-data. Value mismatch.
OVERLAP_TIME_MISMATCH	VARCHAR2(1)	(Y|N) Mismatch caused by setting session parameter ERROR_ON_OVERLAP_TIME
EDITION_MISMATCH	VARCHAR2(1)	(Y|N) Cursor edition mismatch
MV_QUERY_GEN_MISMATCH	VARCHAR2(1)	(Y|N) Internal, used to force a hard-parse when analyzing materialized view queries
USER_BIND_PEEK_MISMATCH	VARCHAR2(1)	(Y|N) Cursor is not shared because value of one or more user binds is different and this has a potential to change the execution plan
TYPCHK_DEP_MISMATCH	VARCHAR2(1)	(Y|N) Cursor has typecheck dependencies
NO_TRIGGER_MISMATCH	VARCHAR2(1)	(Y|N) Cursor and child have no trigger mismatch
FLASHBACK_CURSOR	VARCHAR2(1)	(Y|N) Cursor non-shareability due to flashback
ANYDATA_TRANSFORMATION	VARCHAR2(1)	(Y|N) Is criteria for opaque type transformation and does not match
PDDL_ENV_MISMATCH	VARCHAR2(1)	(Y|N) Environment setting mismatch for parallel DDL cursor (that is, one or more of the following parameter values have changed: PARALLEL_EXECUTION_ENABLED, PARALLEL_DDL_MODE, PARALLEL_DDL_FORCED_DEGREE, or PARALLEL_DDL_FORCED_INSTANCES)

Column	Datatype	Description
TOP_LEVEL_RPI_CURSOR	VARCHAR2(1)	(Y|N) Is top level RPI cursor
DIFFERENT_LONG_LENGTH	VARCHAR2(1)	(Y|N) Value of LONG does not match
LOGICAL_STANDBY_APPLY	VARCHAR2(1)	(Y|N) Logical standby apply context does not match
DIFF_CALL_DURN	VARCHAR2(1)	(Y|N) If worker SQL cursor/single call
BIND_UACS_DIFF	VARCHAR2(1)	(Y|N) One cursor has bind UACs and one does not
PLSQL_CMP_SWITCHS_DIFF	VARCHAR2(1)	(Y|N) PL/SQL anonymous block compiled with different PL/SQL compiler switches
CURSOR_PARTS_MISMATCH	VARCHAR2(1)	(Y|N) Cursor was compiled with subexecution (cursor parts were executed)
STB_OBJECT_MISMATCH	VARCHAR2(1)	(Y|N) STB is an internal name for a SQL Management Object Mismatch. A SQL Management Object Mismatch means that either a SQL plan baseline, or a SQL profile, or a SQL patch has been created for your SQL statement between the executions. Because a cursor is a read-only entity, a hard parse is forced to be able to create a new cursor that contains information about the new SQL management object related to this SQL statement.
CROSSEDITION_TRIGGER_MISMATCH	VARCHAR2(1)	(Y|N) The set of crossedition triggers to execute might differ
PQ_SLAVE_MISMATCH	VARCHAR2(1)	(Y|N) Top-level worker decides not to share cursor
TOP_LEVEL_DDL_MISMATCH	VARCHAR2(1)	(Y|N) Is top-level DDL cursor
MULTI_PX_MISMATCH	VARCHAR2(1)	(Y|N) Cursor has multiple parallelizers and is worker-compiled
BIND_PEEKED_PQ_MISMATCH	VARCHAR2(1)	(Y|N) Cursor based around bind peeked values
MV_REWRITE_MISMATCH	VARCHAR2(1)	(Y|N) Cursor needs recompilation because an SCN was used during compile time due to being rewritten by materialized view
ROLL_INVALID_MISMATCH	VARCHAR2(1)	(Y|N) Marked for rolling invalidation and invalidation window exceeded
OPTIMIZER_MODE_MISMATCH	VARCHAR2(1)	(Y|N) Parameter OPTIMIZER_MODE mismatch (for example, all_rows versus first_rows_1)
PX_MISMATCH	VARCHAR2(1)	(Y|N) Mismatch in one parameter affecting the parallelization of a SQL statement. For example, one cursor was compiled with parallel DML enabled while the other was not.
MV_STALEOBJ_MISMATCH	VARCHAR2(1)	(Y|N) Cursor cannot be shared because there is a mismatch in the list of materialized views which were stale when the cursor was built
FLASHBACK_TABLE_MISMATCH	VARCHAR2(1)	(Y|N) Cursor cannot be shared because there is a mismatch with triggers being enabled and/or referential integrity constraints being deferred
LITREP_COMP_MISMATCH	VARCHAR2(1)	(Y|N) Mismatch in use of literal replacement
PLSQL_DEBUG	VARCHAR2(1)	(Y|N) Value of the PLSQL_DEBUG parameter for the current session does not match the value used to build the cursor
LOAD_OPTIMIZER_STATS	VARCHAR2(1)	(Y|N) A hard parse is forced to initialize extended cursor sharing
ACL_MISMATCH	VARCHAR2(1)	(Y|N) Cached ACL evaluation result stored in the child cursor is not valid for the current session or user

Column	Datatype	Description
FLASHBACK_ARCHIVE_MISMATCH	VARCHAR2(1)	(Y|N) Value of the FLASHBACK_DATA_ARCHIVE_INTERNAL_CURSOR parameter for the current session does not match the value used to build the cursor
LOCK_USER_SCHEMA_FAILED	VARCHAR2(1)	(Y|N) User or schema used to build the cursor no longer exists **Note:** This sharing criterion is deprecated
REMOTE_MAPPING_MISMATCH	VARCHAR2(1)	(Y|N) Reloaded cursor was previously remote-mapped and is currently not remote-mapped. Therefore, the cursor must be reparsed.
LOAD_RUNTIME_HEAP_FAILED	VARCHAR2(1)	(Y|N) Loading of run-time heap for the new cursor (or reload of aged out cursor) failed
HASH_MATCH_FAILED	VARCHAR2(1)	(Y|N) No existing child cursors have the unsafe literal bind hash values required by the current cursor
PURGED_CURSOR	VARCHAR2(1)	(Y|N) Child cursor is marked for purging
BIND_LENGTH_UPGRADEABLE	VARCHAR2(1)	(Y|N) Bind length(s) required for the current cursor are longer than the bind length(s) used to build the child cursor
USE_FEEDBACK_STATS	VARCHAR2(1)	(Y|N) A hard parse is forced so that the optimizer can reoptimize the query with improved optimizer inputs (for example, cardinality estimates)
REASON	CLOB	Child number, id, and reason the cursor is not shared. The content of this column is structured using XML. If this column is null, the FORCE_HARD_PARSE, LOAD_RUNTIME_HEAP_FAILED, and HASH_MATCH_FAILED columns may enable you to determine why the child cursor is not shared.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.82 V$SQL_SHARED_MEMORY

V$SQL_SHARED_MEMORY displays information about the cursor shared memory snapshot. Each SQL statement stored in the shared pool has one or more child objects associated with it. Each child object has several parts, one of which is the context heap, which holds, among other things, the query plan.

Column	Datatype	Description
SQL_TEXT	VARCHAR2(1000)	SQL text of the shared cursor child object for which this row is displaying information
SQL_FULLTEXT	CLOB	Full text for the SQL statement exposed as a CLOB column. The full text of a SQL statement can be retrieved using this column instead of joining with the V$SQLTEXT dynamic performance view.
HASH_VALUE	NUMBER	Hash value of the above SQL text in the shared pool
SQL_ID	VARCHAR2(13)	SQL identifier of the above SQL text in the shared pool

Column	Datatype	Description
HEAP_DESC	RAW(4 | 8)	Address of the descriptor for the context heap of the child cursor described in this row
STRUCTURE	VARCHAR2(64)	If the memory chunk described in this row was allocated using a comment of the form "X : Y", then this is the "X" part of the comment
FUNCTION	VARCHAR2(64)	Similar to the STRUCTURE column, this is the "Y" field of the comment
CHUNK_COM	VARCHAR2(16)	Whole comment field that was supplied when this memory chunk was allocated
CHUNK_PTR	RAW(4 | 8)	Starting address of the allocated memory chunk
CHUNK_SIZE	NUMBER	Amount of memory allocated for this chunk
ALLOC_CLASS	VARCHAR2(8)	Class of memory that this chunk of memory belongs to. It will usually be either FREEABLE or PERMANENT.
CHUNK_TYPE	NUMBER	An index into a table of callback functions that tell the server how to re-create this chunk of memory should it need to be removed from the shared pool based on an LRU algorithm
SUBHEAP_DESC	RAW(4 | 8)	If the parent heap of this context heap is itself a subheap, then this is the address of the descriptor of the parent heap
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.83 V$SQL_TESTCASES

V$SQL_TESTCASES displays information about test cases exported by SQL Test Case Builder.

You can use this view in conjunction with the V$DIAG_INCIDENT view. Join the INCIDENT_ID column in this view with the INCIDENT_ID column in V$DIAG_INCIDENT to view information about the test case associated with a particular incident.

The V$SQL_TESTCASES view requires the existence of a TCB root directory named SQL_TCB_DIR. This view will not contain any rows if a TCB root directory does not exist, or if the TCB root directory exists with a name other than SQL_TCB_DIR. The operating system directory to which the TCB root directory refers must be writable by the owner of the Oracle Database binaries.

- In Oracle Autonomous Database environments, the TCB root directory is created automatically on each POD during provisioning.
- For on-premises databases, a user who has been granted the DBA role must explicitly create the TCB root directory. See *Oracle Database Administrator's Guide* for more information.

Column	Datatype	Description
TESTCASE_NAME	VARCHAR2(512)	Test case name
SQL_ID	VARCHAR2(13)	SQL identifier of the SQL statement in the test case
SQL_TEXT	VARCHAR2(1000)	First 1000 characters of text for the SQL statement in the test case
SQL_TEXT_FULL	CLOB	Full text for the SQL statement in the test case, exposed as a CLOB column
INCIDENT_ID	NUMBER	ID for the incident associated with the test case
PROBLEM_TYPE	NUMBER	Type of problem for the incident associated with the test case. Possible values: • 1: Performance problem (PROBLEM_TYPE_PERFORMANCE) • 2: Inconsistent results (PROBLEM_TYPE_WRONG_RESULTS) • 3: Crash in compilation (PROBLEM_TYPE_COMPILATION_ERROR) • 4: Crash in execution (PROBLEM_TYPE_EXECUTION_ERROR) These numeric values, and their associated constant values shown in parentheses, correspond to the numeric and constant values for problem type constants in the DBMS_SQLDIAG package. See *Oracle Database PL/SQL Packages and Types Reference* for more information.
CREATION_DATE	TIMESTAMP(6)	Creation time for the incident associated with the test case
STATUS	VARCHAR2(10)	Current status for the incident associated with the test case. Possible values: • COMPLETE: The test case export completed successfully • INCOMPLETE: The test case export failed due to an error
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$DIAG_INCIDENT"

10.84 V$SQL_WORKAREA

V$SQL_WORKAREA displays information about work areas used by SQL cursors. Each SQL statement stored in the shared pool has one or more child cursors that are listed in the V$SQL view. V$SQL_WORKAREA lists all work areas needed by these child cursors; V$SQL_WORKAREA can be joined with V$SQLAREA on (ADDRESS, HASH_VALUE) and with V$SQL on (ADDRESS, HASH_VALUE, CHILD_NUMBER).
You can use this view to find out answers to the following questions:

- What are the top 10 work areas that require the most cache area?

- For work areas allocated in AUTO mode, what percentage of work areas are running using maximum memory?

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Address of the parent cursor handle
HASH_VALUE	NUMBER	Hash value of the parent statement in the library cache. Two columns PARENT_HANDLE and HASH_VALUE can be used to join with V$SQLAREA to locate the parent cursor.
SQL_ID	VARCHAR2(13)	SQL identifier of the parent statement in the library cache
CHILD_NUMBER	NUMBER	Number of the child cursor that uses this work area. The columns PARENT_HANDLE, HASH_VALUE, and CHILD_NUMBER can be used to join with V$SQL to locate the child cursor using this area.
WORKAREA_ADDRESS	RAW(4 | 8)	Address of the work area handle. This is the primary key for the view.
OPERATION_TYPE	VARCHAR2(160)	Type of operation using the work area. Can include values such as SORT, HASH JOIN, GROUP BY, BUFFER, BITMAP MERGE, and BITMAP CONSTRUCTION.
OPERATION_ID	NUMBER	A unique number used to identify the operation in the execution plan. This identifier can be joined to V$SQL_PLAN to locate the operation that uses this work area.
POLICY	VARCHAR2(40)	Sizing policy for this work area (MANUAL or AUTO)
ESTIMATED_OPTIMAL_SIZE	NUMBER	Estimated size (in bytes) required by this work area to execute the operation completely in memory (optimal execution). Derived from either optimizer statistics or previous executions.
ESTIMATED_ONEPASS_SIZE	NUMBER	Estimated size (in bytes) required by this work area to execute the operation in a single pass. Derived from either optimizer statistics or previous executions.
LAST_MEMORY_USED	NUMBER	Memory (in bytes) used by this work area during the last execution of the cursor
LAST_EXECUTION	VARCHAR2(40)	Indicates whether this work area runs using OPTIMAL, ONE PASS, or ONE PASS memory requirement (or MULTI-PASS), during the last execution of the cursor
LAST_DEGREE	NUMBER	Degree of parallelism used during the last execution of this operation
TOTAL_EXECUTIONS	NUMBER	Number of times this work area was active
OPTIMAL_EXECUTIONS	NUMBER	Number of times this work area ran in optimal mode
ONEPASS_EXECUTIONS	NUMBER	Number of times this work area ran in one-pass mode
MULTIPASSES_EXECUTIONS	NUMBER	Number of times this work area ran below the one-pass memory requirement
ACTIVE_TIME	NUMBER	Average time this work area is active (in hundredths of a second)
MAX_TEMPSEG_SIZE	NUMBER	Maximum temporary segment size (in bytes) created by an instantiation of this work area. This column is NULL if this work area has never spilled to disk.
LAST_TEMPSEG_SIZE	NUMBER	Temporary segment size (in bytes) created in the last instantiation of this work area. This column is NULL if the last instantiation of this work area did not spill to disk.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SQLAREA"
- "V$SQL"

10.85 V$SQL_WORKAREA_ACTIVE

V$SQL_WORKAREA_ACTIVE contains an instantaneous view of the work areas currently allocated by the system. You can join this view against V$SQL_WORKAREA on WORKAREA_ADDRESS to access the definition of that work area. If a work area spills to disk, then this view contains information for the temporary segment created on behalf of this work area.
The last three columns are included to enable joining V$SQL_WORKAREA_ACTIVE with V$TEMPSEG_USAGE to retrieve more information on this temporary segment.

You can use this view to answer the following:

- What are the top 10 largest work areas currently allocated in the system?
- What percentage of memory is over-allocated (EXPECTED_SIZE < ACTUAL_MEM_USED) and under-allocated (EXPECTED_SIZE > ACTUAL_MEM_USED)?
- What are the active work areas using more memory than what is expected by the memory manager?
- What are the active work areas that have spilled to disk?

Column	Datatype	Description
SQL_HASH_VALUE	NUMBER	Hash value of the SQL statement that is currently being executed
SQL_ID	VARCHAR2(13)	SQL identifier of the SQL statement that is currently being executed
SQL_EXEC_START	DATE	Time when the execution of the SQL currently executed by this session started
SQL_EXEC_ID	NUMBER	SQL execution identifier (see V$SQL_MONITOR)
WORKAREA_ADDRESS	RAW(4 | 8)	Address of the work area handle. This is the primary key for the view.

Column	Datatype	Description
OPERATION_TYPE	VARCHAR2(160)	Type of operation using the work area. Can include values such as SORT, HASH JOIN, GROUP BY, BUFFER, BITMAP MERGE, and BITMAP CONSTRUCTION.
OPERATION_ID	NUMBER	A unique number used to identify the operation in the execution plan. This identifier can be joined to V$SQL_PLAN to locate the operation that uses this work area.
POLICY	VARCHAR2(24)	Sizing policy for this work area (MANUAL or AUTO)
SID	NUMBER	Session identifier
QCINST_ID	NUMBER	Query coordinator instance identifier. Along with QCSID, enables you to uniquely identify the query coordinator.
QCSID	NUMBER	Query coordinator session identifier. This is the same as the SID if the work area is allocated by a serial cursor.
ACTIVE_TIME	NUMBER	Average time this work area is active (in microseconds)
WORK_AREA_SIZE	NUMBER	Maximum size (in bytes) of the work area as it is currently used by the operation
EXPECTED_SIZE	NUMBER	Expected size (in bytes) for this work area. EXPECTED_SIZE is set on behalf of the operation by the memory manager. Memory can be over-allocated when WORK_AREA_SIZE has a higher value than EXPECTED_SIZE. This can occur when the operation using this work area takes a long time to resize it.
ACTUAL_MEM_USED	NUMBER	Amount of PGA memory (in bytes) currently allocated on behalf of this work area. This value should range between 0 and WORK_AREA_SIZE.
MAX_MEM_USED	NUMBER	Maximum memory amount (in bytes) used by this work area
NUMBER_PASSES	NUMBER	Number of passes corresponding to this work area (0 if running in OPTIMAL mode)
TEMPSEG_SIZE	NUMBER	Size (in bytes) of the temporary segment used on behalf of this work area. This column is NULL if this work area has not (yet) spilled to disk.
TABLESPACE	VARCHAR2(128)	Tablespace name for the temporary segment created on behalf of this work area. This column is NULL if this work area has not (yet) spilled to disk.
SEGRFNO#	NUMBER	Relative file number within the tablespace for the temporary segment created on behalf of this work area. This column is NULL if this work area has not (yet) spilled to disk.
SEGBLK#	NUMBER	Block number for the temporary segment created on behalf of this work area. This column is NULL if this work area has not (yet) spilled to disk.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> - "V$SQL_WORKAREA"
> - *Oracle Database Concepts* for more information about SQL work areas

10.86 V$SQL_WORKAREA_HISTOGRAM

`V$SQL_WORKAREA_HISTOGRAM` displays the cumulative work area execution statistics (cumulated since instance startup) for different work area groups. The work areas are split into 33 groups based on their optimal memory requirements with the requirements increasing in powers of two. That is, work areas whose optimal requirement varies from 0 KB to 1 KB, 1 KB to 2 KB, 2 KB to 4 KB, ... and 2 TB to 4 TB.
For each work area group, the `V$SQL_WORKAREA_HISTOGRAM` view shows how many work areas in that group were able to run in optimal mode, how many were able to run in one-pass mode, and finally how many ran in multi-pass mode. The DBA can take a snapshot at the beginning and the end of a desired time interval to derive the same statistics for that interval.

Column	Datatype	Description
`LOW_OPTIMAL_SIZE`	`NUMBER`	Lower bound for the optimal memory requirement of work areas included in this row (bytes)
`HIGH_OPTIMAL_SIZE`	`NUMBER`	Upper bound for the optimal memory requirement of work areas included in this row (bytes)
`OPTIMAL_EXECUTIONS`	`NUMBER`	Number of work areas with an optimal memory requirement comprised between `LOW_OPTIMAL_SIZE` and `HIGH_OPTIMAL_SIZE` which have been executed in optimal mode since instance startup
`ONEPASS_EXECUTIONS`	`NUMBER`	Number of work areas with an optimal memory requirement comprised between `LOW_OPTIMAL_SIZE` and `HIGH_OPTIMAL_SIZE` which have been executed in one-pass mode since instance startup
`MULTIPASSES_EXECUTIONS`	`NUMBER`	Number of work areas with an optimal memory requirement comprised between `LOW_OPTIMAL_SIZE` and `HIGH_OPTIMAL_SIZE` which have been executed in multi-pass mode since instance startup
`TOTAL_EXECUTIONS`	`NUMBER`	Sum of `OPTIMAL_EXECUTIONS`, `ONEPASS_EXECUTIONS`, and `MULTIPASSES_EXECUTIONS`
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for detailed information on how to monitor automatic PGA memory performance using this view

10.87 V$SQLAREA

V$SQLAREA displays statistics on shared SQL areas and contains one row per SQL string. It provides statistics on SQL statements that are in memory, parsed, and ready for execution.

Column	Datatype	Description
SQL_TEXT	VARCHAR2(1000)	First thousand characters of the SQL text for the current cursor
SQL_FULLTEXT	CLOB	All characters of the SQL text for the current cursor
SQL_ID	VARCHAR2(13)	SQL identifier of the parent cursor in the library cache
SHARABLE_MEM	NUMBER	Amount of shared memory used by a cursor. If multiple child cursors exist, then the sum of all shared memory used by all child cursors.
PERSISTENT_MEM	NUMBER	Fixed amount of memory used for the lifetime of an open cursor. If multiple child cursors exist, then the fixed sum of memory used for the lifetime of all the child cursors.
RUNTIME_MEM	NUMBER	Fixed amount of memory required during execution of a cursor. If multiple child cursors exist, then the fixed sum of all memory required during execution of all the child cursors.
SORTS	NUMBER	Sum of the number of sorts that were done for all the child cursors
VERSION_COUNT	NUMBER	Number of child cursors that are present in the cache under this parent
LOADED_VERSIONS	NUMBER	Number of child cursors that are present in the cache and have their context heap loaded
OPEN_VERSIONS	NUMBER	Number of child cursors that are currently open under this current parent
USERS_OPENING	NUMBER	Number of users that have any of the child cursors open
FETCHES	NUMBER	Number of fetches associated with the SQL statement
EXECUTIONS	NUMBER	Total number of executions, totalled over all the child cursors
PX_SERVERS_EXECUTIONS	NUMBER	Total number of executions performed by parallel execution servers (0 when the statement has never been executed in parallel)
END_OF_FETCH_COUNT	NUMBER	Number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic is not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed. By definition, the value of the END_OF_FETCH_COUNT column should be less or equal to the value of the EXECUTIONS column.
USERS_EXECUTING	NUMBER	Total number of users executing the statement over all child cursors
LOADS	NUMBER	Number of times the object was loaded or reloaded

Column	Datatype	Description
FIRST_LOAD_TIME	VARCHAR2(76)	Timestamp of the parent creation time
INVALIDATIONS	NUMBER	Total number of invalidations over all the child cursors
PARSE_CALLS	NUMBER	Sum of all parse calls to all the child cursors under this parent
DISK_READS	NUMBER	Sum of the number of disk reads over all child cursors
DIRECT_WRITES	NUMBER	Sum of the number of direct writes over all child cursors
DIRECT_READS	NUMBER	Sum of the number of direct reads over all child cursors
BUFFER_GETS	NUMBER	Sum of buffer gets over all child cursors
APPLICATION_WAIT_TIME	NUMBER	Application wait time (in microseconds)
CONCURRENCY_WAIT_TIME	NUMBER	Concurrency wait time (in microseconds)
CLUSTER_WAIT_TIME	NUMBER	Cluster wait time (in microseconds)
USER_IO_WAIT_TIME	NUMBER	User I/O Wait Time (in microseconds)
PLSQL_EXEC_TIME	NUMBER	PL/SQL execution time (in microseconds)
JAVA_EXEC_TIME	NUMBER	Java execution time (in microseconds)
ROWS_PROCESSED	NUMBER	Total number of rows processed on behalf of this SQL statement
COMMAND_TYPE	NUMBER	Oracle command type definition
OPTIMIZER_MODE	VARCHAR2(10)	Mode under which the SQL statement was executed
OPTIMIZER_COST	NUMBER	Cost of this query given by the optimizer
OPTIMIZER_ENV	RAW(2000)	Optimizer environment
OPTIMIZER_ENV_HASH_VALUE	NUMBER	Hash value for the optimizer environment
PARSING_USER_ID	NUMBER	User ID of the user that has parsed the very first cursor under this parent
PARSING_SCHEMA_ID	NUMBER	Schema ID that was used to parse this child cursor
PARSING_SCHEMA_NAME	VARCHAR2(128)	Schema name that was used to parse this child cursor
KEPT_VERSIONS	NUMBER	Number of child cursors that have been marked to be kept using the DBMS_SHARED_POOL package
ADDRESS	RAW(4 | 8)	Address of the handle to the parent for this cursor
HASH_VALUE	NUMBER	Hash value of the parent statement in the library cache
OLD_HASH_VALUE	NUMBER	Old SQL hash value
PLAN_HASH_VALUE	NUMBER	Numeric representation of the current SQL plan for this cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line).
FULL_PLAN_HASH_VALUE	NUMBER	Numeric representation of the complete SQL plan for this cursor. Comparing one FULL_PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line). Note that the FULL_PLAN_HASH_VALUE cannot be compared across databases releases. It is not backward compatible.
MODULE	VARCHAR2(64)	Contains the name of the module that was executing when the SQL statement was first parsed as set by calling DBMS_APPLICATION_INFO.SET_MODULE
MODULE_HASH	NUMBER	Hash value of the module that is named in the MODULE column

Column	Datatype	Description
ACTION	VARCHAR2(64)	Contains the name of the action that was executing when the SQL statement was first parsed as set by calling DBMS_APPLICATION_INFO.SET_ACTION
ACTION_HASH	NUMBER	Hash value of the action that is named in the ACTION column
SERIALIZABLE_ABORTS	NUMBER	Number of times the transaction failed to serialize, producing ORA-08177 errors, totalled over all the child cursors
OUTLINE_CATEGORY	VARCHAR2(64)	If an outline was applied during construction of the cursor, then this column displays the category of that outline. Otherwise the column is left blank.
CPU_TIME	NUMBER	CPU time (in microseconds) used by this cursor for parsing, executing, and fetching
ELAPSED_TIME	NUMBER	Elapsed time (in microseconds) used by this cursor for parsing, executing, and fetching. If the cursor uses parallel execution, then ELAPSED_TIME is the cumulative time for the query coordinator, plus all parallel query worker processes.
OUTLINE_SID	VARCHAR2(40)	Outline session identifier
LAST_ACTIVE_CHILD_ADDRESS	RAW(4 | 8)	Address (identifier) of the child cursor that was the last to be active in the group (that is, the child cursor on behalf of which statistics in V$SQL were updated)
REMOTE	VARCHAR2(1)	Indicates whether the cursor is remote mapped (Y) or not (N)
OBJECT_STATUS	VARCHAR2(19)	Status of the cursor: • VALID - Valid, authorized without errors • VALID_AUTH_ERROR - Valid, authorized with authorization errors • VALID_COMPILE_ERROR - Valid, authorized with compilation errors • VALID_UNAUTH - Valid, unauthorized • INVALID_UNAUTH - Invalid, unauthorized • INVALID - Invalid, unauthorized but keep the timestamp
LITERAL_HASH_VALUE	NUMBER	Hash value of the literals which are replaced with system-generated bind variables and are to be matched, when CURSOR_SHARING is used. This is not the hash value for the SQL statement. If CURSOR_SHARING is not used, then the value is 0.
LAST_LOAD_TIME	DATE	Time at which the query plan was loaded into the library cache
IS_OBSOLETE	VARCHAR2(1)	Indicates whether the cursor has become obsolete (Y) or not (N). This can happen if the number of child cursors is too large.
IS_BIND_SENSITIVE	VARCHAR2(1)	Indicates whether the cursor is bind sensitive (Y) or not (N). A query is considered bind-sensitive if the optimizer peeked at one of its bind variable values when computing predicate selectivities and where a change in a bind variable value may cause the optimizer to generate a different plan.
IS_BIND_AWARE	VARCHAR2(1)	Indicates whether the cursor is bind aware (Y) or not (N). A query is considered bind-aware if it has been marked to use extended cursor sharing. The query would already have been marked as bind-sensitive.
CHILD_LATCH	NUMBER	Child latch number that is protecting the cursor. This column is obsolete and maintained for backward compatibility.
SQL_PROFILE	VARCHAR2(64)	SQL profile used for this statement, if any

Column	Datatype	Description
SQL_PATCH	VARCHAR2(128)	SQL patch used for this statement, if any
SQL_PLAN_BASELINE	VARCHAR2(128)	SQL plan baseline used for this statement, if any
PROGRAM_ID	NUMBER	Program identifier
PROGRAM_LINE#	NUMBER	Program line number
EXACT_MATCHING_SIGNATURE	NUMBER	Signature used when the CURSOR_SHARING parameter is set to EXACT
FORCE_MATCHING_SIGNATURE	NUMBER	Signature used when the CURSOR_SHARING parameter is set to FORCE
LAST_ACTIVE_TIME	DATE	Time at which the query plan was last active
BIND_DATA	RAW(2000)	Bind data
TYPECHECK_MEM	NUMBER	Typecheck memory
IO_CELL_OFFLOAD_ELIGIBLE_BYTES	NUMBER	Number of I/O bytes which can be filtered by the Exadata storage system **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_INTERCONNECT_BYTES	NUMBER	Number of I/O bytes exchanged between Oracle Database and the storage system
PHYSICAL_READ_REQUESTS	NUMBER	Number of physical read I/O requests issued by the monitored SQL
PHYSICAL_READ_BYTES	NUMBER	Number of bytes read from disks by the monitored SQL
PHYSICAL_WRITE_REQUESTS	NUMBER	Number of physical write I/O requests issued by the monitored SQL
PHYSICAL_WRITE_BYTES	NUMBER	Number of bytes written to disks by the monitored SQL
OPTIMIZED_PHY_READ_REQUESTS	NUMBER	Number of physical read I/O requests from Database Smart Flash Cache issued by the monitored SQL
LOCKED_TOTAL	NUMBER	Total number of times the child cursor has been locked
PINNED_TOTAL	NUMBER	Total number of times the child cursor has been pinned
IO_CELL_UNCOMPRESSED_BYTES	NUMBER	Number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_CELL_OFFLOAD_RETURNED_BYTES	NUMBER	Number of bytes that are returned by Exadata cell through the regular I/O path **See Also:** Oracle Exadata Storage Server Software documentation for more information
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Column	Datatype	Description
IS_REOPTIMIZABLE	VARCHAR2(1)	This column shows whether the next execution matching this child cursor will trigger a reoptimization. The values are: • Y: If the next execution will trigger a reoptimization • R: If the child cursor contains reoptimization information, but will not trigger reoptimization because the cursor was compiled in reporting mode • N: If the child cursor has no reoptimization information
IS_RESOLVED_ADAPTIVE_PLAN	VARCHAR2(1)	This column shows whether all of the adaptive parts of a plan have been resolved to the final plan. Once the plan is resolved, the plan hash value and the plan displayed by DBMS_XPLAN will not change through the end of execution. The values for this column are: • NULL: If the plan is not adaptive • Y: If the plan is fully resolved • N: If the plan is not yet fully resolved **See Also:** *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_XPLAN package

See Also:

- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SHARED_POOL package
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLICATION_INFO.SET_MODULE procedure
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLICATION_INFO.SET_ACTION procedure
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_XPLAN package

10.88 V$SQLAREA_PLAN_HASH

V$SQLAREA_PLAN_HASH displays statistics on shared SQL areas (V$SQL) by grouping on the SQL_ID and PLAN_HASH_VALUE columns. It can potentially create several rows for one parent cursor, one for each distinct value of the column PLAN_HASH_VALUE.

Column	Datatype	Description
SQL_TEXT	VARCHAR2(1000)	First thousand characters of the SQL text for the current cursor
SQL_FULLTEXT	CLOB	All characters of the SQL text for the current cursor
ADDRESS	RAW(4 | 8)	Address of the handle to the parent for this cursor
HASH_VALUE	NUMBER	Hash value of the parent statement in the library cache
SQL_ID	VARCHAR2(13)	SQL identifier of the parent cursor in the library cache

Column	Datatype	Description
PLAN_HASH_VALUE	NUMBER	Numeric representation of the current SQL plan for this cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line).
VERSION_COUNT	NUMBER	Number of child cursors that are present in the cache under this parent
LAST_ACTIVE_CHILD_ADDRESS	RAW(4 | 8)	Address (identifier) of the child cursor that was the last to be active in the group (that is, the child cursor on behalf of which statistics in V$SQL were updated)
SHARABLE_MEM	NUMBER	Amount of shared memory used by a cursor. If multiple child cursors exist, then it is the sum of all shared memory used by all child cursors.
PERSISTENT_MEM	NUMBER	Fixed amount of memory used for the lifetime of an open cursor. If multiple child cursors exist, then it is the fixed sum of memory used for the lifetime of all the child cursors.
RUNTIME_MEM	NUMBER	Fixed amount of memory required during execution of a cursor. If multiple child cursors exist, then the fixed sum of all memory required during execution of all the child cursors.
SORTS	NUMBER	Sum of the number of sorts that were done for all the child cursors
LOADED_VERSIONS	NUMBER	Number of child cursors that are present in the cache and that have their context heap loaded
OPEN_VERSIONS	NUMBER	Number of child cursors that are currently open under this parent
USERS_OPENING	NUMBER	Number of users that have any of the child cursors open
USERS_EXECUTING	NUMBER	Total number of users executing the statement over all child cursors
FETCHES	NUMBER	Number of fetches associated with the SQL statement
EXECUTIONS	NUMBER	Total number of executions, totalled over all the child cursors
PX_SERVERS_EXECUTIONS	NUMBER	Total number of executions performed by parallel execution servers (0 when the statement has never been executed in parallel)
END_OF_FETCH_COUNT	NUMBER	Number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic is not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed. By definition, the value of the END_OF_FETCH_COUNT column should be less or equal to the value of the EXECUTIONS column.
LOADS	NUMBER	Number of times the object was loaded or reloaded
FIRST_LOAD_TIME	DATE	Timestamp of the parent creation time
LAST_LOAD_TIME	DATE	Time at which the query plan was loaded into the library cache
LAST_ACTIVE_TIME	DATE	Time at which the query plan was last active
LAST_EXEC_START_TIME	DATE	Time at which the most recent execution of this SQL started
INVALIDATIONS	NUMBER	Total number of invalidations over all the child cursors
PARSE_CALLS	NUMBER	Sum of all parse calls to all the child cursors under this parent
DISK_READS	NUMBER	Sum of the number of disk reads over all child cursors
DIRECT_WRITES	NUMBER	Sum of the number of direct writes over all child cursors

Column	Datatype	Description
BUFFER_GETS	NUMBER	Sum of buffer gets over all child cursors
CPU_TIME	NUMBER	CPU time (in microseconds) used by this cursor for parsing, executing, and fetching
ELAPSED_TIME	NUMBER	Elapsed time (in microseconds) used by this cursor for parsing, executing, and fetching
APPLICATION_WAIT_TIME	NUMBER	Application wait time (in microseconds)
CONCURRENCY_WAIT_TIME	NUMBER	Concurrency wait time (in microseconds)
CLUSTER_WAIT_TIME	NUMBER	Cluster wait time (in microseconds)
USER_IO_WAIT_TIME	NUMBER	User I/O wait time (in microseconds)
PLSQL_EXEC_TIME	NUMBER	PL/SQL execution time (in microseconds)
JAVA_EXEC_TIME	NUMBER	Java execution time (in microseconds)
ROWS_PROCESSED	NUMBER	Total number of rows processed on behalf of this SQL statement
COMMAND_TYPE	NUMBER	Oracle command type definition
OPTIMIZER_MODE	VARCHAR2(10)	Mode under which the SQL statement was executed
OPTIMIZER_COST	NUMBER	Cost of this query given by the optimizer
OPTIMIZER_ENV	RAW(2000)	Optimizer environment
OPTIMIZER_ENV_HASH_VALUE	NUMBER	Hash value for the optimizer environment
PARSING_USER_ID	NUMBER	User ID of the user that has parsed the very first cursor under this parent
PARSING_SCHEMA_ID	NUMBER	Schema ID that was used to parse this child cursor
PARSING_SCHEMA_NAME	VARCHAR2(128)	Schema name that was used to parse this child cursor
KEPT_VERSIONS	NUMBER	Number of child cursors that have been marked to be kept using the DBMS_SHARED_POOL package
MODULE	VARCHAR2(64)	Contains the name of the module that was executing when the SQL statement was first parsed as set by calling DBMS_APPLICATION_INFO.SET_MODULE
MODULE_HASH	NUMBER	Hash value of the module that is named in the MODULE column
ACTION	VARCHAR2(64)	Contains the name of the action that was executing when the SQL statement was first parsed as set by calling DBMS_APPLICATION_INFO.SET_ACTION
ACTION_HASH	NUMBER	Hash value of the action that is named in the ACTION column
SERIALIZABLE_ABORTS	NUMBER	Number of times the transaction failed to serialize, producing ORA-08177 errors, totalled over all the child cursors
OUTLINE_CATEGORY	VARCHAR2(64)	If an outline was applied during construction of the cursor, then this column displays the category of that outline. Otherwise, the column is left blank.
OUTLINE_SID	VARCHAR2(40)	Outline session identifier
REMOTE	VARCHAR2(1)	Indicates whether the cursor is remote mapped (Y) or not (N)

Column	Datatype	Description
OBJECT_STATUS	VARCHAR2(19)	Status of the cursor: • VALID - Valid, authorized without errors • VALID_AUTH_ERROR - Valid, authorized with authorization errors • VALID_COMPILE_ERROR - Valid, authorized with compilation errors • VALID_UNAUTH - Valid, unauthorized • INVALID_UNAUTH - Invalid, unauthorized • INVALID - Invalid, unauthorized but keep the timestamp
LITERAL_HASH_VALUE	NUMBER	Hash value of the literals which are replaced with system-generated bind variables and are to be matched, when CURSOR_SHARING is used. This is not the hash value for the SQL statement. If CURSOR_SHARING is not used, then the value is 0.
SQL_PROFILE	VARCHAR2(64)	SQL profile used for this statement, if any
PROGRAM_ID	NUMBER	Program identifier
PROGRAM_LINE#	NUMBER	Program line number
EXACT_MATCHING_SIGNATURE	NUMBER	Signature used when the CURSOR_SHARING parameter is set to EXACT
FORCE_MATCHING_SIGNATURE	NUMBER	Signature used when the CURSOR_SHARING parameter is set to FORCE
BIND_DATA	RAW(2000)	Bind data
TYPECHECK_MEM	NUMBER	Typecheck memory
IO_CELL_OFFLOAD_ELIGIBLE_BYTES	NUMBER	Number of I/O bytes which can be filtered by the Exadata storage system **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_INTERCONNECT_BYTES	NUMBER	Number of I/O bytes exchanged between Oracle Database and the storage system
PHYSICAL_READ_REQUESTS	NUMBER	Number of physical read I/O requests issued by the monitored SQL
PHYSICAL_READ_BYTES	NUMBER	Number of bytes read from disks by the monitored SQL
PHYSICAL_WRITE_REQUESTS	NUMBER	Number of physical write I/O requests issued by the monitored SQL
PHYSICAL_WRITE_BYTES	NUMBER	Number of bytes written to disks by the monitored SQL
OPTIMIZED_PHY_READ_REQUESTS	NUMBER	Number of physical read I/O requests from Database Smart Flash Cache issued by the monitored SQL
IO_CELL_UNCOMPRESSED_BYTES	NUMBER	Number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_CELL_OFFLOAD_RETURNED_BYTES	NUMBER	Number of bytes that are returned by Exadata cell through the regular I/O path **See Also:** Oracle Exadata Storage Server Software documentation for more information

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
CON_DBID	NUMBER	The database ID of the PDB

See Also:

- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_SHARED_POOL package
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLICATION_INFO.SET_MODULE procedure
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_APPLICATION_INFO.SET_ACTION procedure

10.89 V$SQLCOMMAND

V$SQLCOMMAND displays the mapping between SQL opcodes and names.

Column	Datatype	Description
COMMAND_TYPE	NUMBER	SQL command number
COMMAND_NAME	VARCHAR2(64)	SQL command name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.90 V$SQLFN_ARG_METADATA

V$SQLFN_ARG_METADATA contains metadata about function arguments. There is one row for each argument of every function found in V$SQLFN_METADATA. There are no rows for functions that do not have any arguments.

Column	Datatype	Description
FUNC_ID	NUMBER	Internal function identification number. This column can be used to join with the V$SQLFN_METADATA view.
ARGNUM	NUMBER	Argument number
DATATYPE	VARCHAR2(8)	Data type of the argument. The value is NULL if this argument is not used. Otherwise, it can take values of any Oracle data type, family data type, or EXPR data type.
DESCR	VARCHAR2(128)	This column is reserved for future use.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$SQLFN_METADATA"

10.91 V$SQLFN_METADATA

V$SQLFN_METADATA contains metadata about operators and built-in functions. Note that this view does not contain information about arguments because the number of arguments will be different for various functions. Information about arguments is contained in V$SQLFN_ARG_METADATA, which can be joined with V$SQLFN_METADATA to get information about any function and its arguments.

Column	Datatype	Description
FUNC_ID	NUMBER	Internal function identification number
NAME	VARCHAR2(128)	Name of the built-in function
MINARGS	NUMBER	Minimum number of arguments for the function
MAXARGS	NUMBER	Maximum number of arguments for the function
DATATYPE	VARCHAR2(8)	Return data type, which can take any Oracle data type values, data type family values, or ARG[n] data types
VERSION	VARCHAR2(12)	Minimum version of the database that has this function
ANALYTIC	VARCHAR2(3)	Indicates whether the function is an analytic function (YES) or not (NO)
AGGREGATE	VARCHAR2(3)	Indicates whether the function is an aggregate function (YES) or not (NO)
OFFLOADABLE	VARCHAR2(3)	Indicates whether execution of the function can be offloaded to the Oracle Exadata Storage Server (YES) or not (NO) **See Also:** Oracle Exadata Storage Server Software documentation for more information

Column	Datatype	Description
DISP_TYPE	VARCHAR2(13)	Function display type: • NORMAL • ARITHMETIC • PARENTHESIS • REL-OP • CASELIKE • NOPARENTHESIS
USAGE	VARCHAR2(128)	A text explanation of how to use this function. The text is based on the syntax diagram for the function in the *Oracle Database SQL Language Reference*.
DESCR	VARCHAR2(4000)	Description of the function
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$SQLFN_ARG_METADATA"

10.92 V$SQLSTATS

V$SQLSTATS displays basic performance statistics for SQL cursors and contains one row per SQL statement (that is, one row per unique value of SQL_ID). The column definitions for columns in V$SQLSTATS are identical to those in the V$SQL and V$SQLAREA views. However, the V$SQLSTATS view differs from V$SQL and V$SQLAREA in that it is faster, more scalable, and has a greater data retention (the statistics may still appear in this view, even after the cursor has been aged out of the shared pool). Note that V$SQLSTATS contains a subset of columns that appear in V$SQL and V$SQLAREA.

Column	Datatype	Description
SQL_TEXT	VARCHAR2(1000)	First thousand characters of the SQL text for the current cursor
SQL_FULLTEXT	CLOB	Full text for the SQL statement exposed as a CLOB column. THe full text of a SQL statement can be retrieved using this column instead of joining with the V$SQLTEXT view.
SQL_ID	VARCHAR2(13)	SQL identifier of the parent cursor in the library cache
LAST_ACTIVE_TIME	DATE	Last time the statistics of a contributing cursor were updated
LAST_ACTIVE_CHILD_ADDRESS	RAW(4 | 8)	Address of the contributing cursor that last updated these statistics

Column	Datatype	Description
PLAN_HASH_VALUE	NUMBER	Numeric representation of the current SQL plan for this cursor. Comparing one PLAN_HASH_VALUE to another easily identifies whether or not two plans are the same (rather than comparing the two plans line by line).
PARSE_CALLS	NUMBER	Number of parse calls for all cursors with this SQL text and plan
DISK_READS	NUMBER	Number of disk reads for all cursors with this SQL text and plan
DIRECT_WRITES	NUMBER	Number of direct writes for all cursors with this SQL text and plan
DIRECT_READS	NUMBER	Number of direct reads for all cursors with this SQL text and plan
BUFFER_GETS	NUMBER	Number of buffer gets for all cursors with this SQL text and plan
ROWS_PROCESSED	NUMBER	Total number of rows the parsed SQL statement returns
SERIALIZABLE_ABORTS	NUMBER	Number of times the transaction failed to serialize, producing ORA-08177 errors, per cursor
FETCHES	NUMBER	Number of fetches associated with the SQL statement
EXECUTIONS	NUMBER	Number of executions that took place on this object since it was brought into the library cache
END_OF_FETCH_COUNT	NUMBER	Number of times this cursor was fully executed since the cursor was brought into the library cache. The value of this statistic is not incremented when the cursor is partially executed, either because it failed during the execution or because only the first few rows produced by this cursor are fetched before the cursor is closed or re-executed. By definition, the value of the END_OF_FETCH_COUNT column should be less or equal to the value of the EXECUTIONS column.
LOADS	NUMBER	Number of times the object was either loaded or reloaded
VERSION_COUNT	NUMBER	number of cursors present in the cache with this SQL text and plan
INVALIDATIONS	NUMBER	Number of times this child cursor has been invalidated
PX_SERVERS_EXECUTIONS	NUMBER	Total number of executions performed by parallel execution servers (0 when the statement has never been executed in parallel)
CPU_TIME	NUMBER	CPU time (in microseconds) used by this cursor for parsing, executing, and fetching
ELAPSED_TIME	NUMBER	Elapsed time (in microseconds) used by this cursor for parsing, executing, and fetching. If the cursor uses parallel execution, then ELAPSED_TIME is the cumulative time for the query coordinator, plus all parallel query worker processes.
AVG_HARD_PARSE_TIME	NUMBER	Average hard parse time (in microseconds) used by this cursor
APPLICATION_WAIT_TIME	NUMBER	Application wait time (in microseconds)
CONCURRENCY_WAIT_TIME	NUMBER	Concurrency wait time (in microseconds)
CLUSTER_WAIT_TIME	NUMBER	Cluster wait time (in microseconds). This value is specific to Oracle RAC. It shows the total time spent waiting for all waits that are categorized under the cluster class of wait events. The value is this column is an accumulated wait time spent waiting for Oracle RAC cluster resources.
USER_IO_WAIT_TIME	NUMBER	User I/O wait time (in microseconds)
PLSQL_EXEC_TIME	NUMBER	PL/SQL execution time (in microseconds)
JAVA_EXEC_TIME	NUMBER	Java execution time (in microseconds)

Column	Datatype	Description
SORTS	NUMBER	Number of sorts that were done for the child cursor
SHARABLE_MEM	NUMBER	Total shared memory (in bytes) currently occupied by all cursors with this SQL text and plan
TOTAL_SHARABLE_MEM	NUMBER	Total shared memory (in bytes) occupied by all cursors with this SQL text and plan if they were to be fully loaded in the shared pool (that is, cursor size)
TYPECHECK_MEM	NUMBER	Typecheck memory
IO_CELL_OFFLOAD_ELIGIBLE_BYTES	NUMBER	Number of I/O bytes which can be filtered by the Exadata storage system **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_INTERCONNECT_BYTES	NUMBER	Number of I/O bytes exchanged between Oracle Database and the storage system. Typically used for Cache Fusion or parallel queries.
PHYSICAL_READ_REQUESTS	NUMBER	Number of physical read I/O requests issued by the monitored SQL. The requests may not be disk reads.
PHYSICAL_READ_BYTES	NUMBER	Number of bytes read from disks by the monitored SQL
PHYSICAL_WRITE_REQUESTS	NUMBER	Number of physical write I/O requests issued by the monitored SQL
PHYSICAL_WRITE_BYTES	NUMBER	Number of bytes written to disks by the monitored SQL
EXACT_MATCHING_SIGNATURE	NUMBER	Signature used when the CURSOR_SHARING parameter is set to EXACT
FORCE_MATCHING_SIGNATURE	NUMBER	Signature used when the CURSOR_SHARING parameter is set to FORCE
IO_CELL_UNCOMPRESSED_BYTES	NUMBER	Number of uncompressed bytes (that is, size after decompression) that are offloaded to the Exadata cells **See Also:** Oracle Exadata Storage Server Software documentation for more information
IO_CELL_OFFLOAD_RETURNED_BYTES	NUMBER	Number of bytes that are returned by Exadata cell through the regular I/O path **See Also:** Oracle Exadata Storage Server Software documentation for more information
DELTA_PARSE_CALLS	NUMBER	Number of parse calls for the cursor since the last Automatic Workload Repository (AWR) snapshot **See Also:** *Oracle Database Performance Tuning Guide* for an introduction to AWR
DELTA_DISK_READS	NUMBER	Number of disk reads for the cursor since the last AWR snapshot
DELTA_DIRECT_WRITES	NUMBER	Number of direct writes for the cursor since the last AWR snapshot
DELTA_DIRECT_READS	NUMBER	Number of direct reads for the cursor since the last AWR snapshot
DELTA_BUFFER_GETS	NUMBER	Number of buffer gets for the cursor since the last AWR snapshot
DELTA_ROWS_PROCESSED	NUMBER	Number of rows returned by the cursor since the last AWR snapshot
DELTA_FETCH_COUNT	NUMBER	Number of fetches for the cursor since the last AWR snapshot
DELTA_EXECUTION_COUNT	NUMBER	Number of executions for the cursor since the last AWR snapshot

Column	Datatype	Description
DELTA_PX_SERVERS_EXECUTIONS	NUMBER	Number of executions performed by parallel execution servers since the last AWR snapshot
DELTA_END_OF_FETCH_COUNT	NUMBER	Number of times the cursor was fully executed since the last AWR snapshot
DELTA_CPU_TIME	NUMBER	CPU time (in microseconds) for the cursor since the last AWR snapshot
DELTA_ELAPSED_TIME	NUMBER	Database time (in microseconds) for the cursor since the last AWR snapshot
DELTA_APPLICATION_WAIT_TIME	NUMBER	Time spent by the cursor (in microseconds) in the Application wait class since the last AWR snapshot
DELTA_CONCURRENCY_TIME	NUMBER	Time spent by the cursor (in microseconds) in the Concurrency wait class since the last AWR snapshot
DELTA_CLUSTER_WAIT_TIME	NUMBER	Time spent by the cursor (in microseconds) in the Cluster wait class since the last AWR snapshot
DELTA_USER_IO_WAIT_TIME	NUMBER	Time spent by the cursor (in microseconds) in the User I/O wait class since the last AWR snapshot
DELTA_PLSQL_EXEC_TIME	NUMBER	Time spent by the cursor (in microseconds) executing PL/SQL since the last AWR snapshot
DELTA_JAVA_EXEC_TIME	NUMBER	Time spent by the cursor (in microseconds) executing Java since the last AWR snapshot
DELTA_SORTS	NUMBER	Number of sorts for the cursor since the last AWR snapshot
DELTA_LOADS	NUMBER	Number of times the cursor was loaded since the last AWR snapshot
DELTA_INVALIDATIONS	NUMBER	Number of times the cursor was invalidated since the last AWR snapshot
DELTA_PHYSICAL_READ_REQUESTS	NUMBER	Number of physical read I/O requests for the cursor since the last AWR snapshot
DELTA_PHYSICAL_READ_BYTES	NUMBER	Number of bytes read from disk for the cursor since the last AWR snapshot
DELTA_PHYSICAL_WRITE_REQUESTS	NUMBER	Number of physical write I/O requests for the cursor since the last AWR snapshot
DELTA_PHYSICAL_WRITE_BYTES	NUMBER	Number of bytes written to disk for the cursor since the last AWR snapshot
DELTA_IO_INTERCONNECT_BYTES	NUMBER	Number of I/O bytes exchanged between the Oracle database and the storage system for the cursor since the last AWR snapshot
DELTA_CELL_OFFLOAD_ELIG_BYTES	NUMBER	Number of I/O bytes which can be filtered by the Exadata storage system for the cursor since the last AWR snapshot **See Also:** Oracle Exadata Storage Server Software documentation for more information
DELTA_CELL_UNCOMPRESSED_BYTES	NUMBER	Number of uncompressed bytes that are offloaded to the Exadata cell for the cursor since the last AWR snapshot **See Also:** Oracle Exadata Storage Server Software documentation for more information

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
CON_DBID	NUMBER	The database ID of the PDB
OBSOLETE_COUNT	NUMBER	Number of times that a parent cursor became obsolete
AVOIDED_EXECUTIONS	NUMBER	Number of executions attempted on this object, but prevented due to the SQL statement being in quarantine
DELTA_AVOIDED_EXECUTIONS	NUMBER	Number of executions attempted on this object, but prevented due to the SQL statement being in quarantine, since the last AWR snapshot

See Also:

- "V$SQL"
- "V$SQLAREA"

10.93 V$SQLSTATS_PLAN_HASH

V$SQLSTATS_PLAN_HASH displays basic performance statistics for SQL cursors and contains one row per execution plan of a SQL statement (that is, one row per unique combination of SQL_ID and PLAN_HASH_VALUE).
The columns for V$SQLSTATS_PLAN_HASH are the same as those for V$SQLSTATS.

See Also:

"V$SQLSTATS"

10.94 V$SQLTEXT

V$SQLTEXT displays the text of SQL statements belonging to shared SQL cursors in the SGA.

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Used with HASH_VALUE to uniquely identify a cached cursor
HASH_VALUE	NUMBER	Used with ADDRESS to uniquely identify a cached cursor
SQL_ID	VARCHAR2(13)	SQL identifier of a cached cursor
COMMAND_TYPE	NUMBER	Code for the type of SQL statement (SELECT, INSERT, and so on)

Column	Datatype	Description
PIECE	NUMBER	Number used to order the pieces of SQL text
SQL_TEXT	VARCHAR2(64)	A column containing one piece of the SQL text
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.95 V$SQLTEXT_WITH_NEWLINES

V$SQLTEXT_WITH_NEWLINES is identical to the V$SQLTEXT view except that, to improve legibility, V$SQLTEXT_WITH_NEWLINES does not replace newlines and tabs in the SQL statement with spaces.

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Used with HASH_VALUE to uniquely identify a cached cursor
HASH_VALUE	NUMBER	Used with ADDRESS to uniquely identify a cached cursor
SQL_ID	VARCHAR2(13)	SQL identifier of a cached cursor
COMMAND_TYPE	NUMBER	Code for the type of SQL statement (SELECT, INSERT, and so on)
PIECE	NUMBER	Number used to order the pieces of SQL text
SQL_TEXT	VARCHAR2(64)	A column containing one piece of the SQL text
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$SQLTEXT"

10.96 V$STANDBY_EVENT_HISTOGRAM

V$STANDBY_EVENT_HISTOGRAM displays the histogram of apply lag on the physical standby. Each distinct value of apply lag has its own bucket and the count in the corresponding bucket represents the number of occurrences so far. The physical standby samples the apply lag every second and increments the corresponding bucket in the histogram.

Column	Datatype	Description
NAME	VARCHAR2(64)	Name of the event (currently APPLY LAG is the only valid value)
TIME	NUMBER	Time duration that the bucket represents
UNIT	VARCHAR2(16)	Time unit (seconds, minutes, hours, or days)
COUNT	NUMBER	Each row is a histogram bucket for apply lag. COUNT is the number of occurrences the apply lag falls into the histogram bucket.
LAST_TIME_UPDATED	VARCHAR2(20)	Last time the bucket was updated by an event falling into that time duration
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.97 V$STANDBY_LOG

V$STANDBY_LOG displays information about standby redo logs. Standby redo logs are similar to online redo logs, but standby redo logs are only used on a standby database that is receiving redo data from the primary database.

Column	Datatype	Description
GROUP#	NUMBER	Log group number
DBID	VARCHAR2(40)	Database ID of the primary database to which the standby redo logfile is assigned. If the standby redo logfile is unassigned, the value UNASSIGNED will be displayed.
THREAD#	NUMBER	Log thread number
SEQUENCE#	NUMBER	Log sequence number
BYTES	NUMBER	Size of the log (in bytes)
BLOCKSIZE	NUMBER	Block size of the logfile (512 or 4096)
USED	NUMBER	Number of bytes used in the log
ARCHIVED	VARCHAR2(3)	Archive status (YES) or (NO). See the STATUS column for further details.
STATUS	VARCHAR2(10)	Log status: • UNASSIGNED - If ARCHIVED is NO, then the standby redo log has been archived and is again available. If ARCHIVED is YES, then the standby redo log has never been used and is available. • ACTIVE - If ARCHIVED is NO, then the standby redo log is complete and waiting to be archived. If ARCHIVED is YES, then the standby redo log is currently being written to and is therefore not ready to be archived. For a given thread, there should be only one such log.
FIRST_CHANGE#	NUMBER	Lowest SCN in the log
FIRST_TIME	DATE	Time of the first SCN in the log

Column	Datatype	Description
NEXT_CHANGE#	NUMBER	All redo records contained within this log will have an SCN lower than NEXT_CHANGE#. Only filled in once the log is complete. Also the lowest SCN of any redo record in the next log.
NEXT_TIME	DATE	All redo records contained within this log will have a timestamp lower than NEXT_TIME. Only filled in once the log is complete. Also the lowest timestamp of any redo record in the next log.
LAST_CHANGE#	NUMBER	All redo records contained within this log will have an SCN lower than LAST_CHANGE#. Only filled in once the log is complete. Also the lowest SCN of any redo record in the next log. LAST_CHANGE# is deprecated. Use NEXT_CHANGE# instead.
LAST_TIME	DATE	All redo records contained within this log will have a timestamp lower than LAST_TIME. Only filled in once the log is complete. Also the lowest timestamp of any redo record in the next log. LAST_TIME is deprecated. Use NEXT_TIME instead.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.98 V$STATISTICS_LEVEL

V$STATISTICS_LEVEL displays the status of the statistics/advisories controlled by STATISTICS_LEVEL.

Column	Datatype	Description
STATISTICS_NAME	VARCHAR2(64)	Name of the statistic/advisory
DESCRIPTION	VARCHAR2(4000)	Description of the statistic/advisory
SESSION_STATUS	VARCHAR2(8)	Status of the statistic/advisory for the session: • ENABLED • DISABLED
SYSTEM_STATUS	VARCHAR2(8)	System-wide status of the statistic/advisory: • ENABLED • DISABLED
ACTIVATION_LEVEL	VARCHAR2(7)	Indicates the level of STATISTICS_LEVEL that enables the statistic/advisory: • BASIC • TYPICAL • ALL
STATISTICS_VIEW_NAME	VARCHAR2(64)	If there is a single view externalizing the statistic/advisory, then this column contains the name of that view. If there is no such view, then this column is null. If there are multiple views involved, then the DESCRIPTION column mentions the view names.

Column	Datatype	Description
SESSION_SETTABLE	VARCHAR2(3)	Indicates whether the statistic/advisory can be set at the session level (YES) or not (NO)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "STATISTICS_LEVEL"

10.99 V$STATNAME

V$STATNAME displays decoded statistic names for the statistics shown in the V$SESSTAT and V$SYSSTAT tables.

On some platforms, the NAME and CLASS columns contain additional operating system-specific statistics.

Column	Datatype	Description
STATISTIC#	NUMBER	Statistic number **Note:** Statistics numbers are not guaranteed to remain constant from one release to another. Therefore, you should rely on the statistics name rather than its number in your applications.
NAME	VARCHAR2(64)	Statistic name. Names that appear in this column remain stable across Oracle Database releases, and they can be relied on by customer scripts.
CLASS	NUMBER	A number representing one or more statistics classes. The following class numbers are additive: • 1 - User • 2 - Redo • 4 - Enqueue • 8 - Cache • 16 - OS • 32 - Real Application Clusters • 64 - SQL • 128 - Debug • 256 - Instance level
STAT_ID	NUMBER	Identifier of the statistic

Column	Datatype	Description
DISPLAY_NAME	VARCHAR2(64)	A clearer and more descriptive name for the statistic that appears in the NAME column. Names that appear in the DISPLAY_NAME column can change across Oracle Database releases, therefore customer scripts should not rely on names that appear in the DISPLAY_NAME column across releases.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$SESSTAT" and "V$SYSSTAT"
- " Statistics Descriptions" for statistic descriptions
- Your operating system-specific Oracle documentation

10.100 V$STATS_ADVISOR_RULES

V$STATS_ADVISOR_RULES displays the rule definition information for each Optimizer Statistics Advisor rule.

Column	Datatype	Description
RULE_ID	NUMBER	ID of the rule
NAME	VARCHAR2(64)	Name of the rule
RULE_TYPE	VARCHAR2(9)	Type of the rule: • OBJECT • OPERATION • SYSTEM
DESCRIPTION	VARCHAR2(64)	Description of the rule
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database SQL Tuning Guide* for more information about Optimizer Statistics Advisor.

10.101 V$STREAMS_APPLY_COORDINATOR

`V$STREAMS_APPLY_COORDINATOR` displays information about each apply process coordinator. The coordinator for an apply process gets transactions from the apply process reader and passes them to apply servers. An apply process coordinator is a subcomponent of an apply process, outbound server, or inbound server.

Column	Datatype	Description
SID	NUMBER	Session ID of the coordinator's session
SERIAL#	NUMBER	Serial number of the coordinator's session
STATE	VARCHAR2(21)	State of the coordinator: • `INITIALIZING` - Starting up • `IDLE` - Performing no work • `APPLYING` - Passing transactions to apply servers • `SHUTTING DOWN CLEANLY` - Stopping without an error • `ABORTING` - Stopping because of an apply error
APPLY#	NUMBER	Apply process number. An apply process coordinator is an Oracle background process, prefixed by `ap`.
APPLY_NAME	VARCHAR2(128)	Name of the apply process
TOTAL_APPLIED	NUMBER	Total number of transactions applied by the apply process since the apply process was last started
TOTAL_WAIT_DEPS	NUMBER	Number of times since the apply process was last started that an apply server waited to apply a logical change record (LCR) in a transaction until another apply server applied a transaction because of a dependency between the transactions
TOTAL_WAIT_COMMITS	NUMBER	Number of times since the apply process was last started that an apply server waited to commit a transaction until another apply server committed a transaction to serialize commits
TOTAL_ADMIN	NUMBER	Number of administrative jobs issued since the apply process was last started
TOTAL_ASSIGNED	NUMBER	Number of transactions assigned to apply servers since the apply process was last started
TOTAL_RECEIVED	NUMBER	Total number of transactions received by the coordinator process since the apply process was last started
TOTAL_IGNORED	NUMBER	Number of transactions which were received by the coordinator but were ignored because they had been previously applied
TOTAL_ROLLBACKS	NUMBER	Number of transactions which were rolled back due to unexpected contention
TOTAL_ERRORS	NUMBER	Number of transactions applied by the apply process that resulted in an apply error since the apply process was last started
UNASSIGNED_COMPLETE_TXNS	NUMBER	Total number of complete transactions that the coordinator has not assigned to any apply servers

Column	Datatype	Description
AUTO_TXN_BUFFER_SIZE	NUMBER	Current value of transaction buffer size. Transaction buffer size refers to the number of transactions that the apply reader can assemble ahead of apply servers. The apply process periodically adjusts the transaction buffer size.
LWM_TIME	DATE	Time when the message with the lowest message number was recorded. The creation time of the message with the lowest message number was also recorded at this time.
LWM_MESSAGE_NUMBER	NUMBER	Number of the message corresponding to the low watermark. That is, messages with a commit message number less than or equal to this message number have definitely been applied, but some messages with a higher commit message number also may have been applied.
LWM_MESSAGE_CREATE_TIME	DATE	For captured messages, creation time at the source database of the message corresponding to the low watermark. For user-enqueued messages, time when the message corresponding to the low watermark was enqueued into the queue at the local database.
HWM_TIME	DATE	Time when the message with the highest message number was recorded. The creation time of the message with the highest message number was also recorded at this time.
HWM_MESSAGE_NUMBER	NUMBER	Number of the message corresponding to the high watermark. That is, no messages with a commit message number greater than this message number have been applied.
HWM_MESSAGE_CREATE_TIME	DATE	For captured messages, creation time at the source database of the message corresponding to the high watermark. For user-enqueued messages, time when the message corresponding to the high watermark was enqueued into the queue at the local database.
STARTUP_TIME	DATE	Time when the apply process was last started
ELAPSED_SCHEDULE_TIME	NUMBER	Time elapsed (in hundredths of a second) scheduling messages since the apply process was last started
ELAPSED_IDLE_TIME	NUMBER	Elapsed idle time
LWM_POSITION	RAW(64)	Position of the low-watermark LCR
HWM_POSITION	RAW(64)	Position of the high-watermark LCR
PROCESSED_MESSAGE_NUMBER	NUMBER	Message number currently processed by the apply coordinator
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
ACTIVE_SERVER_COUNT	NUMBER	Active server count

> **Note:**
>
> The ELAPSED_SCHEDULE_TIME column is only populated if the TIMED_STATISTICS initialization parameter is set to true, or if the STATISTICS_LEVEL initialization parameter is set to TYPICAL or ALL.

> **See Also:**
>
> - "TIMED_STATISTICS"
> - "STATISTICS_LEVEL"

10.102 V$STREAMS_APPLY_READER

V$STREAMS_APPLY_READER displays information about each apply reader. The apply reader is a process which reads (dequeues) messages from the queue, computes message dependencies, and builds transactions. It passes the transactions on to the coordinator in commit order for assignment to the apply servers. An apply reader is a subcomponent of an apply process, outbound server, or inbound server.

Column	Datatype	Description
SID	NUMBER	Session ID of the reader's session
SERIAL#	NUMBER	Serial number of the reader's session
APPLY#	NUMBER	Apply process number. An apply process is an Oracle background process, prefixed by ap.
APPLY_NAME	VARCHAR2(128)	Name of the apply process
STATE	VARCHAR2(36)	State of the reader: • INITIALIZING - Starting up • IDLE - Performing no work • DEQUEUE MESSAGES - Dequeuing messages from the queue • SCHEDULE MESSAGES - Computing dependencies between messages and assembling messages into transactions • SPILLING - Spilling unapplied messages from memory to hard disk • PAUSED - WAITING FOR DDL TO COMPLETE - Waiting for a data definition language (DDL) logical change record (LCR) to be applied
TOTAL_MESSAGES_DEQUEUED	NUMBER	Total number of messages dequeued since the apply process was last started
TOTAL_MESSAGES_SPILLED	NUMBER	Number of messages spilled by the reader since the apply process was last started
DEQUEUE_TIME	DATE	Time when the last message was received
DEQUEUED_MESSAGE_NUMBER	NUMBER	Number of the last message received

Column	Datatype	Description
DEQUEUED_MESSAGE_CREATE_TIME	DATE	For captured messages, creation time at the source database of the last message received. For user-enqueued messages, time when the message was enqueued into the queue at the local database.
SGA_USED	NUMBER	Amount (in bytes) of SGA memory used by the apply process since it was last started
ELAPSED_DEQUEUE_TIME	NUMBER	Time elapsed (in hundredths of a second) dequeuing messages since the apply process was last started
ELAPSED_SCHEDULE_TIME	NUMBER	Time elapsed (in hundredths of a second) scheduling messages since the apply process was last started. Scheduling includes computing dependencies between messages and assembling messages into transactions.
ELAPSED_SPILL_TIME	NUMBER	Elapsed time (in hundredths of a second) spent spilling messages since the apply process was last started
LAST_BROWSE_NUM	NUMBER	Reserved for internal use
OLDEST_SCN_NUM	NUMBER	Oldest SCN
LAST_BROWSE_SEQ	NUMBER	Reserved for internal use
LAST_DEQ_SEQ	NUMBER	Last dequeue sequence number
OLDEST_XIDUSN	NUMBER	Transaction ID undo segment number of the oldest transaction that either has been applied or is being applied
OLDEST_XIDSLT	NUMBER	Transaction ID slot number of the oldest transaction that either has been applied or is being applied
OLDEST_XIDSQN	NUMBER	Transaction ID sequence number of the oldest transaction that either has been applied or is being applied
SPILL_LWM_SCN	NUMBER	Spill low-watermark SCN
PROXY_SID	NUMBER	When the apply process uses combined capture and apply, the session ID of the propagation receiver that is responsible for direct communication between capture and apply. If the apply process does not use combined capture and apply, then this column is `0`.
PROXY_SERIAL	NUMBER	When the apply process uses combined capture and apply, the serial number of the propagation receiver that is responsible for direct communication between capture and apply. If the apply process does not use combined capture and apply, then this column is `0`.
PROXY_SPID	VARCHAR2(12)	When the apply process uses combined capture and apply, the process identification number of the propagation receiver that is responsible for direct communication between capture and apply. If the apply process does not use combined capture and apply, then this column is `0`.
CAPTURE_BYTES_RECEIVED	NUMBER	When the apply process uses combined capture and apply, the number of bytes received by the apply process from the capture process since the apply process last started. If the apply process does not use combined capture and apply, then this column is not populated.
DEQUEUED_POSITION	RAW(64)	Dequeued position. This column is populated only for an apply process that is functioning as an XStream inbound server.
LAST_BROWSE_POSITION	RAW(64)	Reserved for internal use

Column	Datatype	Description
OLDEST_POSITION	RAW(64)	The earliest position of the transactions currently being dequeued and applied. This column is populated only for an apply process that is functioning as an XStream inbound server.
SPILL_LWM_POSITION	RAW(64)	Spill low-watermark position. This column is populated only for an apply process that is functioning as an XStream inbound server.
OLDEST_TRANSACTION_ID	VARCHAR2(128)	Oldest transaction ID
TOTAL_LCRS_WITH_DEP	NUMBER	Total number of LCRs with row-level dependencies since the apply process last started
TOTAL_LCRS_WITH_WMDEP	NUMBER	Total number of LCRs with watermark dependencies since the apply process last started. A watermark dependency occurs when an apply process must wait until the apply process's low watermark reaches a particular threshold.
TOTAL_IN_MEMORY_LCRS	NUMBER	Total number of LCRs currently in memory
SGA_ALLOCATED	NUMBER	The total amount of shared memory (in bytes) allocated from the Streams pool for the apply process since the apply process last started
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

The ELAPSED_DEQUEUE_TIME and ELAPSED_SCHEDULE_TIME columns are only populated if the TIMED_STATISTICS initialization parameter is set to true, or if the STATISTICS_LEVEL initialization parameter is set to TYPICAL or ALL.

See Also:

- "TIMED_STATISTICS"
- "STATISTICS_LEVEL"

10.103 V$STREAMS_APPLY_SERVER

V$STREAMS_APPLY_SERVER displays information about each apply server and its activities. An apply server receives messages from the apply coordinator for an apply process. For each message received, an apply server either applies the message or sends the message to the appropriate apply handler. An apply server is a subcomponent of an apply process, outbound server, or inbound server.

Column	Datatype	Description
SID	NUMBER	Session ID of the apply server's session
SERIAL#	NUMBER	Serial number of the apply server's session
APPLY#	NUMBER	Apply process number. An apply process is an Oracle background process, prefixed by ap.
APPLY_NAME	VARCHAR2(128)	Name of the apply process
SERVER_ID	NUMBER	Parallel execution server number of the apply server
STATE	VARCHAR2(20)	State of the apply server: • INITIALIZING - Starting up • IDLE - Performing no work • RECORD LOW-WATERMARK - Performing an administrative job that maintains information about the apply progress, which is used in the ALL_APPLY_PROGRESS and DBA_APPLY_PROGRESS data dictionary views • ADD PARTITION - Performing an administrative job that adds a partition that is used for recording information about in-progress transactions • DROP PARTITION - Performing an administrative job that purges rows that were used to record information about in-progress transactions • EXECUTE TRANSACTION - Applying a transaction • WAIT COMMIT - Waiting to commit a transaction until all other transactions with a lower commit SCN are applied. This state is possible only if the COMMIT_SERIALIZATION apply process parameter is set to a value other than DEPENDENT_TRANSACTIONS and the PARALLELISM apply process parameter is set to a value greater than 1. • WAIT DEPENDENCY - Waiting to apply a logical change record (LCR) in a transaction until another transaction, on which it has a dependency, is applied. This state is possible only if the PARALLELISM apply process parameter is set to a value greater than 1. • ROLLBACK TRANSACTION - Rolling back a transaction • TRANSACTION CLEANUP - Cleaning up an applied transaction, which includes removing LCRs from the apply process's queue • WAIT FOR CLIENT - Waiting for an XStream client application to request more LCRs • WAIT FOR NEXT CHUNK - Waiting for the next set of LCRs for a large transaction
XIDUSN	NUMBER	Transaction ID undo segment number of the transaction currently being applied
XIDSLT	NUMBER	Transaction ID slot number of the transaction currently being applied
XIDSQN	NUMBER	Transaction ID sequence number of the transaction currently being applied
COMMITSCN	NUMBER	Commit system change number (SCN) of the transaction currently being applied
DEP_XIDUSN	NUMBER	Transaction ID undo segment number of a transaction on which the transaction being applied by this apply server depends

Column	Datatype	Description
DEP_XIDSLT	NUMBER	Transaction ID slot number of a transaction on which the transaction being applied by this apply server depends
DEP_XIDSQN	NUMBER	Transaction ID sequence number of a transaction on which the transaction being applied by this apply server depends
DEP_COMMITSCN	NUMBER	Commit system change number (SCN) of the transaction on which this apply server depends
MESSAGE_SEQUENCE	NUMBER	Number of the current message being applied by the apply server. This value is reset to 1 at the beginning of each transaction.
TOTAL_ASSIGNED	NUMBER	Total number of transactions assigned to the apply server since the apply process was last started
TOTAL_ADMIN	NUMBER	Total number of administrative jobs done by the apply server since the apply process was last started. See the STATE information in this view for the types of administrative jobs.
TOTAL_ROLLBACKS	NUMBER	Number of transactions assigned to this server which were rolled back
TOTAL_MESSAGES_APPLIED	NUMBER	Total number of messages applied by this apply server since the apply process was last started
APPLY_TIME	DATE	Time the last message was applied
APPLIED_MESSAGE_NUMBER	NUMBER	Number of the last message applied
APPLIED_MESSAGE_CREATE_TIME	DATE	Creation time at the source database of the last captured message applied. No information about user-enqueued messages is recorded in this column.
ELAPSED_DEQUEUE_TIME	NUMBER	Time elapsed (in hundredths of a second) dequeuing messages since the apply process was last started
ELAPSED_APPLY_TIME	NUMBER	Time elapsed (in hundredths of a second) applying messages since the apply process was last started
COMMIT_POSITION	RAW(64)	Commit position of the transaction. This column is populated only for an apply process that is functioning as an XStream outbound server or inbound server.
DEP_COMMIT_POSITION	RAW(64)	Commit position of the transaction the worker depends on. This column is populated only for an apply process that is functioning as an XStream inbound server.
LAST_APPLY_POSITION	RAW(64)	For inbound servers, the position of the last message applied; for outbound servers, the position of the last message sent to the XStream client application. This column is populated only for an apply process that is functioning as an XStream outbound server or inbound server.
TRANSACTION_ID	VARCHAR2(128)	Transaction ID that the worker is applying. This column is populated only for an apply process that is functioning as an XStream inbound server.
DEP_TRANSACTION_ID	VARCHAR2(128)	Transaction ID of the transaction the worker depends on. This column is populated only for an apply process that is functioning as an XStream inbound server.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
TOTAL_LCRS_RETRIED	NUMBER	Total number of LCRs retried by this server
LCR_RETRY_ITERATION	NUMBER	Retry iteration for this transaction by this server
TOTAL_TXNS_RETRIED	NUMBER	Total transactions retried by this server
TXN_RETRY_ITERATION	NUMBER	Total retry iterations by this server
TOTAL_TXNS_RECORDED	NUMBER	Total transactions recorded in error queue by this server

Note:

The ELAPSED_DEQUEUE_TIME and ELAPSED_APPLY_TIME columns are only populated if the TIMED_STATISTICS initialization parameter is set to true, or if the STATISTICS_LEVEL initialization parameter is set to TYPICAL or ALL.

See Also:

- "TIMED_STATISTICS"
- "STATISTICS_LEVEL"

10.104 V$STREAMS_POOL_ADVICE

V$STREAMS_POOL_ADVICE displays information about the estimated count of spilled or unspilled messages and the associated time spent in the spill or unspill activity for different Streams pool sizes. The sizes range from 10% to 200% of the current Streams pool size, in equal intervals. The value of the interval depends on the current size of the Streams pool.

Column	Datatype	Description
STREAMS_POOL_SIZE_FOR_ESTIMATE	NUMBER	Streams pool size (in megabytes) for the estimate. The size ranges from values smaller than the current Streams pool size to values larger than the current Streams pool size, and there is a separate row for each increment. There is always an entry that shows the current Streams pool size, and there are always 20 increments. The range and the size of the increments depend on the current size of the Streams pool.
STREAMS_POOL_SIZE_FACTOR	NUMBER	Size factor with respect to the current Streams pool size

Column	Datatype	Description
ESTD_SPILL_COUNT	NUMBER	Estimated count of messages spilled from the Streams pool
ESTD_SPILL_TIME	NUMBER	Estimated elapsed time (in seconds) to spill
ESTD_UNSPILL_COUNT	NUMBER	Estimated count of unspills (read back from disk)
ESTD_UNSPILL_TIME	NUMBER	Estimated elapsed time (in seconds) to unspill
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.105 V$STREAMS_POOL_STATISTICS

V$STREAMS_POOL_STATISTICS displays information about the current Streams pool usage percentage.

Column	Datatype	Description
TOTAL_MEMORY_ALLOCATED	NUMBER	Total memory allocated to the Streams pool (in bytes). It should always be less than the current size of the Streams pool. You can get the percentage of the Streams pool used by dividing TOTAL_MEMORY_ALLOCATED by CURRENT_SIZE.
CURRENT_SIZE	NUMBER	Current size of the Streams pool (in bytes)
SGA_TARGET_VALUE	NUMBER	Value of SGA_TARGET. Used to determine whether or not streams pool automatic tuning is enabled. This should be set even if MEMORY_TARGET is set and SGA_TARGET is not set.
SHRINK_PHASE	NUMBER	This only pertains to the Streams pool in an automatic tuning environment (SGA_TARGET and MEMORY_TARGET set). In this case, this shows whether or not the Streams pool is being asked to shrink. During the shrink phase, enqueues are blocked, flow control is enabled for all components, and cached memory is returned to the SGA.
ADVICE_DISABLED	NUMBER	This determines whether or not Streams pool advice in V$STREAMS_POOL_ADVICE as well as all statistics gathering related to auto-tuning the Streams pool have been disabled.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.106 V$SUBCACHE

V$SUBCACHE displays information about the subordinate caches currently loaded into library cache memory. The view walks through the library cache, printing out a row for each loaded subordinate cache per library cache object.

Column	Datatype	Description
OWNER_NAME	VARCHAR2(64)	Owner of the object containing these cache entries
NAME	VARCHAR2(1000)	Object Name
TYPE	NUMBER	Object Type
HEAP_NUM	NUMBER	Heap number containing this subordinate cache
CACHE_ID	NUMBER	Subordinate cache ID
CACHE_CNT	NUMBER	Number of entries for this cache in this object
HEAP_SZ	NUMBER	Amount of extent space allocated to this heap
HEAP_ALOC	NUMBER	Amount of extent space allocated from this heap
HEAP_USED	NUMBER	Amount of space utilized in this heap
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.107 V$SUBSCR_REGISTRATION_STATS

V$SUBSCR_REGISTRATION_STATS displays information for diagnosability of notifications.

Column	Datatype	Description
REG_ID	NUMBER	Registration identifier
NUM_NTFNS	NUMBER	Number of notifications
NUM_GROUPING_NTFNS	NUMBER	Number of grouping notifications
NUM_NTFNS_CURRENT_GROUP	NUMBER	Number of events received in the current group
LAST_NTFN_START_TIME	TIMESTAMP(3) WITH TIME ZONE	Time when the last notification was started
LAST_NTFN_SENT_TIME	TIMESTAMP(3) WITH TIME ZONE	Time when the last notification was sent
TOTAL_EMON_LATENCY	NUMBER	Total EMON latency (time taken by the EMON worker to process notifications)
EMON#	NUMBER	Active EMON worker serving the registration
ALL_EMON_SERVERS	RAW(2000)	EMON workers that served the registration
TOTAL_PAYLOAD_BYTES_SENT	NUMBER	Total payload bytes sent

Column	Datatype	Description
SHARD_ID	NUMBER	Shard number for current registration used for Key Based Messaging
NUM_RETRIES	NUMBER	Number of retries in sending notifications
TOTAL_PLSQL_EXEC_TIME	NUMBER	Total PL/SQL callback execution time (relevant only for PL/SQL notifications)
LAST_ERR	VARCHAR2(90)	Last error message
LAST_ERR_TIME	TIMESTAMP(3) WITH TIME ZONE	Time of the last error
LAST_UPDATE_TIME	TIMESTAMP(3) WITH TIME ZONE	Time of the last update
NUM_PENDING_NTFNS	NUMBER	Number of notifications pending to be sent
TOTAL_PENDING_NTFN_BYTES	NUMBER	Total number of bytes for notifications pending to be sent
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.108 V$SYS_OPTIMIZER_ENV

V$SYS_OPTIMIZER_ENV displays the contents of the optimizer environment for the instance. The optimizer environment stores the value of the main parameters used by the Oracle optimizer when building the execution plan of a SQL statement. Hence, modifying the value of one or more of these parameters (for example, by issuing an ALTER SYSTEM statement) could lead to plan changes.
The parameters displayed by this view are either regular initialization parameters (such as OPTIMIZER_FEATURES_ENABLE) or pseudo parameters (such as ACTIVE_INSTANCE_COUNT).

Column	Datatype	Description
ID	NUMBER	Unique identifier of the parameter in the optimizer environment
NAME	VARCHAR2(40)	Name of the parameter
SQL_FEATURE	VARCHAR2(64)	Associated feature control ID
ISDEFAULT	VARCHAR2(3)	Indicates whether the parameter is set to the default value (YES) or not (NO)
VALUE	VARCHAR2(25)	Value of the parameter
DEFAULT_VALUE	VARCHAR2(25)	Default value of the parameter

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "OPTIMIZER_FEATURES_ENABLE"
- "ACTIVE_INSTANCE_COUNT"

10.109 V$SYS_TIME_MODEL

V$SYS_TIME_MODEL displays the system-wide accumulated times for various operations. The time reported is the total elapsed or CPU time (in microseconds). Any timed operation will buffer at most 5 seconds of time data. Specifically, this means that if a timed operation (such as SQL execution) takes a long period of time to perform, the data published to this view is at most missing 5 seconds of the time accumulated for the operation.
The time values are 8-byte integers and can therefore hold approximately 580,000 years worth of time before wrapping. Background process time is not included in a statistic value unless the statistic is specifically for background processes.

Column	Datatype	Description
STAT_ID	NUMBER	Statistic identifier for the time statistic
STAT_NAME	VARCHAR2(64)	Name of the statistic (see Table 10-1)
VALUE	NUMBER	Amount of time (in microseconds) that the system has spent in this operation
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view returns instance-wide data and a value of `0` in the `CON_ID` column when queried from the root of a CDB.

10.110 V$SYSAUX_OCCUPANTS

`V$SYSAUX_OCCUPANTS` displays `SYSAUX` tablespace occupant information.

Column	Datatype	Description
`OCCUPANT_NAME`	`VARCHAR2(64)`	Occupant name
`OCCUPANT_DESC`	`VARCHAR2(64)`	Occupant description
`SCHEMA_NAME`	`VARCHAR2(64)`	Schema name for the occupant
`MOVE_PROCEDURE`	`VARCHAR2(64)`	Name of the move procedure; null if not applicable
`MOVE_PROCEDURE_DESC`	`VARCHAR2(64)`	Description of the move procedure
`SPACE_USAGE_KBYTES`	`NUMBER`	Current space usage of the occupant (in KB)
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.111 V$SYSMETRIC

`V$SYSMETRIC` displays the system metric values captured for the most current time interval for both the long duration (60-second) and short duration (15-second) system metrics.

Column	Datatype	Description
`BEGIN_TIME`	`DATE`	Begin time of the interval
`END_TIME`	`DATE`	End time of the interval
`INTSIZE_CSEC`	`NUMBER`	Interval size (in hundredths of a second)
`GROUP_ID`	`NUMBER`	Metric group ID
`METRIC_ID`	`NUMBER`	Metric ID
`METRIC_NAME`	`VARCHAR2(64)`	Metric name
`VALUE`	`NUMBER`	Metric value
`METRIC_UNIT`	`VARCHAR2(64)`	Metric unit description

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "DBA_HIST_SYS_TIME_MODEL"
- "V$CON_SYSMETRIC"
- "DBA_HIST_CON_SYS_TIME_MODEL"

10.112 V$SYSMETRIC_HISTORY

V$SYSMETRIC_HISTORY displays all system metric values available in the database. Both long duration (60-second with 1 hour history) and short duration (15-second with one-interval only) metrics are displayed by this view.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
GROUP_ID	NUMBER	Metric group ID
METRIC_ID	NUMBER	Metric ID
METRIC_NAME	VARCHAR2(64)	Metric name
VALUE	NUMBER	Metric value
METRIC_UNIT	VARCHAR2(64)	Metric unit description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "DBA_HIST_SYSMETRIC_HISTORY"
- "V$CON_SYSMETRIC_HISTORY"
- "DBA_HIST_CON_SYSMETRIC_HIST"

10.113 V$SYSMETRIC_SUMMARY

`V$SYSMETRIC_SUMMARY` displays a summary of all system metric values for the long-duration system metrics. The average, maximum value, minimum value, and the value of one standard deviation for the last hour are displayed for each metric item.

Column	Datatype	Description
`BEGIN_TIME`	`DATE`	Begin time of the interval
`END_TIME`	`DATE`	End time of the interval
`INTSIZE_CSEC`	`NUMBER`	Interval size (in hundredths of a second)
`GROUP_ID`	`NUMBER`	Metric group ID
`METRIC_ID`	`NUMBER`	Metric ID
`METRIC_NAME`	`VARCHAR2(64)`	Metric name
`NUM_INTERVAL`	`NUMBER`	Number of intervals observed
`MAXVAL`	`NUMBER`	Maximum value observed
`MINVAL`	`NUMBER`	Minimum value observed
`AVERAGE`	`NUMBER`	Average value over the period
`STANDARD_DEVIATION`	`NUMBER`	One standard deviation
`METRIC_UNIT`	`VARCHAR2(64)`	Metric unit description
`CON_ID`	`NUMBER`	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "DBA_HIST_SYSMETRIC_SUMMARY"
- "V$CON_SYSMETRIC_SUMMARY"
- "DBA_HIST_CON_SYSMETRIC_SUMM"

10.114 V$SYSSTAT

`V$SYSSTAT` displays system statistics. To find the name of the statistic associated with each statistic number (`STATISTIC#`), query the `V$STATNAME` view.

Column	Datatype	Description
`STATISTIC#`	`NUMBER`	Statistic number **Note:** Statistics numbers are not guaranteed to remain constant from one release to another. Therefore, you should rely on the statistics name rather than its number in your applications.

Column	Datatype	Description
NAME	VARCHAR2(64)	Statistic name. You can get a complete listing of statistic names by querying the V$STATNAME view.
CLASS	NUMBER	A number representing one or more statistics class. The following class numbers are additive: • 1 - User • 2 - Redo • 4 - Enqueue • 8 - Cache • 16 - OS • 32 - Real Application Clusters • 64 - SQL • 128 - Debug • 256 - Instance level
VALUE	NUMBER	Statistic value
STAT_ID	NUMBER	Identifier of the statistic
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

This view returns instance-wide data and a value of 0 in the CON_ID column when queried from the root of a CDB.

See Also:

"V$STATNAME" and " Statistics Descriptions"

10.115 V$SYSTEM_CURSOR_CACHE

V$SYSTEM_CURSOR_CACHE displays system wide information on cursor usage.

See Also:

"V$SESSION_CURSOR_CACHE"

Column	Datatype	Description
OPENS	NUMBER	Cumulative total of cursor opens
HITS	NUMBER	Cumulative total of cursor open hits
HIT_RATIO	NUMBER	Ratio of the number of times an open cursor was found divided by the number of times a cursor was sought
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.116 V$SYSTEM_EVENT

V$SYSTEM_EVENT displays information on total waits for an event. Note that the TIME_WAITED and AVERAGE_WAIT columns will contain a value of zero on those platforms that do not support a fast timing mechanism. If you are running on one of these platforms and you want this column to reflect true wait times, then you must set TIMED_STATISTICS to TRUE in the parameter file; doing this will have a small negative effect on system performance.

> **See Also:**
>
> "TIMED_STATISTICS"

Column	Datatype	Description
EVENT	VARCHAR2(64)	Name of the wait event; derived statistic name from V$EVENT_NAME **See Also:** " Oracle Wait Events"
TOTAL_WAITS	NUMBER	Total number of waits for the event
TOTAL_TIMEOUTS	NUMBER	Total number of timeouts for the event
TIME_WAITED	NUMBER	Total amount of time waited for the event (in hundredths of a second)
AVERAGE_WAIT	NUMBER	Average amount of time waited for the event (in hundredths of a second)
TIME_WAITED_MICRO	NUMBER	Total amount of time waited for the event (in microseconds)
CPU	NUMBER	Total amount of CPU time consumed while implementing the wait event itself (in microseconds)
TOTAL_WAITS_FG	NUMBER	Total number of waits for the event, from foreground sessions
TOTAL_TIMEOUTS_FG	NUMBER	Total number of timeouts for the event, from foreground sessions
TIME_WAITED_FG	NUMBER	Total amount of time waited for the event, from foreground sessions (in hundredths of a second)
AVERAGE_WAIT_FG	NUMBER	Average amount of time waited for the event, from foreground sessions (in hundredths of a second)

Column	Datatype	Description
TIME_WAITED_MICRO_FG	NUMBER	Total amount of time waited for the event, from foreground sessions (in microseconds)
CPU_FG	NUMBER	Total amount of CPU time consumed while implementing the wait event itself, from foreground sessions (in microseconds)
EVENT_ID	NUMBER	Identifier of the wait event
WAIT_CLASS_ID	NUMBER	Identifier of the wait class of the wait event
WAIT_CLASS#	NUMBER	Number of the wait class of the wait event
WAIT_CLASS	VARCHAR2(64)	Name of the wait class of the wait event
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view returns instance-wide data and a value of 0 in the CON_ID column when queried from the root of a CDB.

10.117 V$SYSTEM_FIX_CONTROL

V$SYSTEM_FIX_CONTROL displays information about Fix Control (enabled/disabled) at the system level.

Column	Datatype	Description
BUGNO	NUMBER	Bug number (as fix control identifier)
VALUE	NUMBER	Current value set for the fix control
SQL_FEATURE	VARCHAR2(64)	Feature control ID
DESCRIPTION	VARCHAR2(64)	Description of the fix control
OPTIMIZER_FEATURE_ENABLE	VARCHAR2(25)	Version on (and after) which the fix is enabled by default
EVENT	NUMBER	Event formerly used to control this fix
IS_DEFAULT	NUMBER	Indicates whether the current value is the same as the default (1) or not (0)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.118 V$SYSTEM_PARAMETER

V$SYSTEM_PARAMETER displays information about the initialization parameters that are currently in effect for the instance. A new session inherits parameter values from the instance-wide values.

Column	Datatype	Description
NUM	NUMBER	Parameter number
NAME	VARCHAR2(80)	Name of the parameter
TYPE	NUMBER	Parameter type: • 1 - Boolean • 2 - String • 3 - Integer • 4 - Parameter file • 5 - Reserved • 6 - Big integer
VALUE	VARCHAR2(4000)	Instance-wide parameter value
DISPLAY_VALUE	VARCHAR2(4000)	Parameter value in a user-friendly format. For example, if the VALUE column shows the value 262144 for a big integer parameter, then the DISPLAY_VALUE column will show the value 256K.
DEFAULT_VALUE	VARCHAR2(255)	The default value for this parameter. This is the value of the parameter if a value is not explicitly specified for the parameter.
ISDEFAULT	VARCHAR2(9)	Indicates whether the parameter is set to the default value (TRUE) or the parameter value was specified in the parameter file (FALSE) The database sets the value of the ISDEFAULT column to TRUE for parameters that are not specified in the init.ora or server parameter file (SPFILE).
ISSES_MODIFIABLE	VARCHAR2(5)	Indicates whether the parameter can be changed with ALTER SESSION (TRUE) or not (FALSE)

Column	Datatype	Description
ISSYS_MODIFIABLE	VARCHAR2(9)	Indicates whether the parameter can be changed with ALTER SYSTEM and when the change takes effect: • IMMEDIATE - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect immediately. • DEFERRED - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect in subsequent sessions. • FALSE - Parameter cannot be changed with ALTER SYSTEM unless a server parameter file was used to start the instance. The change takes effect in subsequent instances.
ISPDB_MODIFIABLE	VARCHAR2(5)	Indicates whether the parameter can be modified inside a PDB (TRUE) or not (FALSE). In a non-CDB, the value of this column is NULL.
ISINSTANCE_MODIFIABLE	VARCHAR2(5)	For parameters that can be changed with ALTER SYSTEM, indicates whether the value of the parameter can be different for every instance (TRUE) or whether the parameter must have the same value for all Real Application Clusters instances (FALSE). If the ISSYS_MODIFIABLE column is FALSE, then this column is always FALSE.
ISMODIFIED	VARCHAR2(8)	Indicates how the parameter was modified. If an ALTER SYSTEM was performed, the value will be MODIFIED.
ISADJUSTED	VARCHAR2(5)	Indicates whether Oracle adjusted the input value to a more suitable value (for example, the parameter value should be prime, but the user input a non-prime number, so Oracle adjusted the value to the next prime number)
ISDEPRECATED	VARCHAR2(5)	Indicates whether the parameter has been deprecated (TRUE) or not (FALSE)
ISBASIC	VARCHAR2(5)	Indicates whether the parameter is a basic parameter (TRUE) or not (FALSE)
DESCRIPTION	VARCHAR2(255)	Description of the parameter
UPDATE_COMMENT	VARCHAR2(255)	Comments associated with the most recent update
HASH	NUMBER	Hash value for the parameter name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$PARAMETER" for information about initialization parameters that are currently in effect for a session

10.119 V$SYSTEM_PARAMETER2

V$SYSTEM_PARAMETER2 displays information about the initialization parameters that are currently in effect for the instance, with each list parameter value appearing as a row in the view. A new session inherits parameter values from the instance-wide values.

Presenting the list parameter values in this format enables you to quickly determine the values for a list parameter. For example, if a parameter value is a, b, then the V$SYSTEM_PARAMETER view does not tell you if the parameter has two values (both a and b) or one value (a, b). V$SYSTEM_PARAMETER2 makes the distinction between the list parameter values clear.

Column	Datatype	Description
NUM	NUMBER	Parameter number
NAME	VARCHAR2(80)	Name of the parameter
TYPE	NUMBER	Parameter type: • 1 - Boolean • 2 - String • 3 - Integer • 4 - Parameter file • 5 - Reserved • 6 - Big integer
VALUE	VARCHAR2(4000)	Parameter value
DISPLAY_VALUE	VARCHAR2(4000)	Parameter value in a user-friendly format. For example, if the VALUE column shows the value 262144 for a big integer parameter, then the DISPLAY_VALUE column will show the value 256K.
ISDEFAULT	VARCHAR2(6)	Indicates whether the parameter is set to the default value (TRUE) or the parameter value was specified in the parameter file (FALSE)
ISSES_MODIFIABLE	VARCHAR2(5)	Indicates whether the parameter can be changed with ALTER SESSION (TRUE) or not (FALSE)
ISSYS_MODIFIABLE	VARCHAR2(9)	Indicates whether the parameter can be changed with ALTER SYSTEM and when the change takes effect: • IMMEDIATE - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect immediately. • DEFERRED - Parameter can be changed with ALTER SYSTEM regardless of the type of parameter file used to start the instance. The change takes effect in subsequent sessions. • FALSE - Parameter cannot be changed with ALTER SYSTEM unless a server parameter file was used to start the instance. The change takes effect in subsequent instances.
ISPDB_MODIFIABLE	VARCHAR2(5)	Indicates whether the parameter can be modified on a per-PDB basis (TRUE) or not (FALSE). In a non-CDB, the value of this column is NULL.

Column	Datatype	Description
ISINSTANCE_MODIFIABLE	VARCHAR2(5)	For parameters that can be changed with ALTER SYSTEM, indicates whether the value of the parameter can be different for every instance (TRUE) or whether the parameter must have the same value for all Real Application Clusters instances (FALSE). If the ISSYS_MODIFIABLE column is FALSE, then this column is always FALSE.
ISMODIFIED	VARCHAR2(8)	Indicates how the parameter was modified. If an ALTER SYSTEM was performed, the value will be MODIFIED.
ISADJUSTED	VARCHAR2(5)	Indicates whether Oracle adjusted the input value to a more suitable value (for example, the parameter value should be prime, but the user input a non-prime number, so Oracle adjusted the value to the next prime number)
ISDEPRECATED	VARCHAR2(5)	Indicates whether the parameter has been deprecated (TRUE) or not (FALSE)
ISBASIC	VARCHAR2(5)	Indicates whether the parameter is a basic parameter (TRUE) or not (FALSE)
DESCRIPTION	VARCHAR2(255)	Description of the parameter
ORDINAL	NUMBER	Position (ordinal number) of the parameter value. Useful only for parameters whose values are lists of strings.
UPDATE_COMMENT	VARCHAR2(255)	Comments associated with the most recent update
HASH	NUMBER	Hash value for the parameter name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$SYSTEM_PARAMETER"

10.120 V$SYSTEM_WAIT_CLASS

V$SYSTEM_WAIT_CLASS displays the instance-wide time totals for each registered wait class.

Column	Datatype	Description
WAIT_CLASS_ID	NUMBER	Identifier of the wait class
WAIT_CLASS#	NUMBER	Number of the wait class
WAIT_CLASS	VARCHAR2(64)	Name of the wait class
TOTAL_WAITS	NUMBER	Total number of waits from this wait class

Column	Datatype	Description
TIME_WAITED	NUMBER	Total amount of time spent in waits from this wait class (in hundredths of a second)
TIME_WAITED_MICRO	NUMBER	Total amount of time spent in waits from this wait class (in microseconds)
CPU	NUMBER	Total amount of CPU time consumed while implementing waits from this wait class (in microseconds)
TOTAL_WAITS_FG	NUMBER	Total number of waits for this wait class, from foreground sessions
TIME_WAITED_FG	NUMBER	Total amount of time spent in waits from this wait class, from foreground sessions (in hundredths of a second)
TIME_WAITED_MICRO_FG	NUMBER	Total amount of time spent in waits from this wait class, from foreground sessions (in microseconds)
CPU_FG	NUMBER	Total amount of CPU time consumed while implementing waits from this wait class, from foreground sessions (in microseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

This view returns instance-wide data and a value of 0 in the CON_ID column when queried from the root of a CDB.

10.121 V$TABLE_ACCESS_STATS

V$TABLE_ACCESS_STATS displays the scan count for tables and partitions.

The scan data collection begins at instance startup.

Column	Datatype	Description
OBJECT_ID	NUMBER	Object ID of the table or partition
READ_COUNT	NUMBER	Aggregated scan count since instance startup
LAST_ACCESSED_TIME	TIMESTAMP(0)	Date and time of the most recent scan
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.122 V$TABLESPACE

V$TABLESPACE displays tablespace information from the control file.

Column	Datatype	Description
TS#	NUMBER	Tablespace number
NAME	VARCHAR2(30)	Tablespace name
INCLUDED_IN_DATABASE_BACKUP	VARCHAR2(3)	Indicates whether the tablespace is included in full database backups using the BACKUP DATABASE RMAN command (YES) or not (NO); NO only if the CONFIGURE EXCLUDE RMAN command was used for this tablespace
BIGFILE	VARCHAR2(3)	Indicates whether the tablespace is a bigfile tablespace (YES) or a smallfile tablespace (NO)
FLASHBACK_ON	VARCHAR2(3)	Indicates whether the tablespace participates in FLASHBACK DATABASE operations (YES) or not (NO)
ENCRYPT_IN_BACKUP	VARCHAR2(3)	Indicates whether encryption is turned ON or off at the tablespace level: • ON - Encryption is turned ON at the tablespace level • OFF - Encryption is turned OFF at the tablespace level • NULL - Encryption is neither explicitly turned on nor off at the tablespace level (default or when cleared)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.123 V$TDM_STATS

V$TDM_STATS describes statistics for Oracle Connection Manager in Traffic Director Mode (CMAN-TDM).

Column	Datatype	Description
CMAN_ID	VARCHAR2(1024)	CMAN-TDM host name
GATEWAY_ID	NUMBER	Index of the gateway process of CMAN-TDM
SERVICE_NAME	VARCHAR2(1024)	Reserved for future use
PRCP_NUM_REQUESTS	NUMBER	Number of client requests that resulted in acquire on the Proxy Resident Connection Pool (PRCP)

Column	Datatype	Description
PRCP_NUM_BUSY_CONNECTIONS	NUMBER	Number of busy server connections in the PRCP
PRCP_NUM_OPEN_CONNECTIONS	NUMBER	Number of busy and free server connections in the PRCP
PRCP_HISTORIC_MAX_CONNECTIONS	NUMBER	Maximum size (number of connections) that the PRCP has ever reached
PRCP_NUM_WAITS	NUMBER	Total number of client requests that waited due to unavailability of free server connections in the PRCP This value accumulates since the start of the process.
PRCP_NUM_WAITS_ACTIVE	NUMBER	Number of active client requests currently waiting due to unavailability of free server connections in the PRCP
PRCP_NUM_HITS	NUMBER	Total number of times that client requests found matches in the PRCP
PRCP_NUM_INBOUND_CONNECTIONS	NUMBER	Total Number of active client connections for the PRCP
EDITION	VARCHAR2(1024)	Database edition name associated with the PRCP
UPDATED_TIME	TIMESTAMP(6) WITH TIME ZONE	Date and time at which the statistics were uploaded to the PDB
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.124 V$TEMP_CACHE_TRANSFER

V$TEMP_CACHE_TRANSFER is deprecated. The information that was provided in this view is now provided in the V$INSTANCE_CACHE_TRANSFER and V$SEGMENT_STATISTICS views.

Column	Datatype	Description
FILE_NUMBER	NUMBER	Number of the temp file
X_2_NULL	NUMBER	Number of blocks with Exclusive-to-NULL conversions; always 0
X_2_NULL_FORCED_WRITE	NUMBER	Number of Exclusive-to-NULL forced writes; always 0
X_2_NULL_FORCED_STALE	NUMBER	Number of Exclusive-to-NULL blocks converted to CR; always 0
X_2_S	NUMBER	Number of blocks with Exclusive-to-Shared conversions; always 0
X_2_S_FORCED_WRITE	NUMBER	Number of Exclusive-to-Shared forced writes; always 0

Column	Datatype	Description
S_2_NULL	NUMBER	Number of blocks with Shared-to-NULL conversions; always 0
S_2_NULL_FORCED_STALE	NUMBER	Number of Shared-to-NULL blocks converted to CR; always 0
RBR	NUMBER	Number of reuse blocks cross-instance calls; always 0
RBR_FORCED_WRITE	NUMBER	Number of blocks written due to reuse blocks cross-instance calls; always 0
NULL_2_X	NUMBER	Number of blocks with NULL-to-Exclusive conversions; always 0
S_2_X	NUMBER	Number of blocks with Shared-to-Exclusive conversions; always 0
NULL_2_S	NUMBER	Number of blocks with NULL-to-Shared conversions; always 0
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$INSTANCE_CACHE_TRANSFER"
- "V$SEGMENT_STATISTICS"

10.125 V$TEMP_EXTENT_MAP

V$TEMP_EXTENT_MAP displays the status of each unit for all LOCALLY MANAGED temporary tablespaces.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of the tablespace this unit belongs to
FILE_ID	NUMBER		Absolute file number
BLOCK_ID	NUMBER		Begin block number for this unit
BYTES	NUMBER		Bytes in the extent
BLOCKS	NUMBER		Blocks in the extent
OWNER	NUMBER		Instance which owns this unit
RELATIVE_FNO	NUMBER		Relative file number

Column	Datatype	NULL	Description
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.126 V$TEMP_EXTENT_POOL

V$TEMP_EXTENT_POOL displays the state of temporary space cached and used for the instance. Note that loading of the temporary space cache is lazy and that instances can be dormant.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of the tablespace
FILE_ID	NUMBER		Absolute file number
EXTENTS_CACHED	NUMBER		Number of extents that have been cached
EXTENTS_USED	NUMBER		Number of extents that are actually being used
BLOCKS_CACHED	NUMBER		Number of blocks that are cached
BLOCKS_USED	NUMBER		Number of blocks that are used
BYTES_CACHED	NUMBER		Number of bytes that are cached
BYTES_USED	NUMBER		Number of bytes that are used
RELATIVE_FNO	NUMBER		Relative file number
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.127 V$TEMP_SPACE_HEADER

V$TEMP_SPACE_HEADER displays aggregate information per file per LOCALLY MANAGED temporary tablespace regarding how much space is currently being used and how much is free as identified in the space header.

Column	Datatype	NULL	Description
TABLESPACE_NAME	VARCHAR2(30)	NOT NULL	Name of the temporary tablespace

Column	Datatype	NULL	Description
FILE_ID	NUMBER		Absolute file number
BYTES_USED	NUMBER		How many bytes are in use
BLOCKS_USED	NUMBER		How many blocks are in use
BYTES_FREE	NUMBER		How many bytes are free
BLOCKS_FREE	NUMBER		How many blocks are free
RELATIVE_FNO	NUMBER		The relative file number for the file
CON_ID	NUMBER		The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.128 V$TEMPFILE

V$TEMPFILE displays temp file information.

Column	Datatype	Description
FILE#	NUMBER	Absolute file number
CREATION_CHANGE#	NUMBER	Creation System Change Number (SCN)
CREATION_TIME	DATE	Creation time
TS#	NUMBER	Tablespace number
RFILE#	NUMBER	Relative file number in the tablespace
STATUS	VARCHAR2(7)	Status of the file (OFFLINE|ONLINE)
ENABLED	VARCHAR2(10)	Enabled for read and/or write
BYTES	NUMBER	Size of the file in bytes (from the file header)
BLOCKS	NUMBER	Size of the file in blocks (from the file header)
CREATE_BYTES	NUMBER	Creation size of the file (in bytes)
BLOCK_SIZE	NUMBER	Block size for the file
NAME	VARCHAR2(513)	Name of the file
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.129 V$TEMPORARY_LOBS

V$TEMPORARY_LOBS displays information about temporary and abstract LOBs.

Column	Datatype	Description
SID	NUMBER	Session ID
CACHE_LOBS	NUMBER	Number of cache temp LOBs
NOCACHE_LOBS	NUMBER	Number of nocache temp LOBs
ABSTRACT_LOBS	NUMBER	Number of abstract LOBs
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.130 V$TEMPSEG_USAGE

V$TEMPSEG_USAGE describes temporary segment usage.

Column	Datatype	Description
USERNAME	VARCHAR2(128)	User who requested temporary space
USER	VARCHAR2(128)	This column is obsolete and maintained for backward compatibility. The value of this column is always equal to the value in USERNAME.
SESSION_ADDR	RAW(4 | 8)	Session address
SESSION_NUM	NUMBER	Serial number of session
SQLADDR	RAW(4 | 8)	Address of SQL statement
SQLHASH	NUMBER	Hash value of SQL statement
SQL_ID	VARCHAR2(13)	SQL identifier of SQL statement
TABLESPACE	VARCHAR2(30)	Tablespace in which space is allocated
CONTENTS	VARCHAR2(9)	Indicates whether tablespace is TEMPORARY or PERMANENT
SEGTYPE	VARCHAR2(9)	Type of sort segment: • SORT • HASH • DATA • INDEX • LOB_DATA • LOB_INDEX
SEGFILE#	NUMBER	File number of initial extent
SEGBLK#	NUMBER	Block number of the initial extent
EXTENTS	NUMBER	Extents allocated to the sort

Column	Datatype	Description
BLOCKS	NUMBER	Extents in blocks allocated to the sort
SEGRFNO#	NUMBER	Relative file number of initial extent
TS#	NUMBER	Tablespace number
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
SQL_ID_TEMPSEG	VARCHAR2(13)	SQL identifier of the SQL statement that created the temporary segment

10.131 V$TEMPSTAT

V$TEMPSTAT displays information about file read/write statistics.

Column	Datatype	Description
FILE#	NUMBER	Number of the file
PHYRDS	NUMBER	Number of physical reads done
PHYWRTS	NUMBER	Number of times DBWR is required to write
PHYBLKRD	NUMBER	Number of physical blocks read
PHYBLKWRT	NUMBER	Number of blocks written to disk, which may be the same as PHYWRTS if all writes are single blocks
SINGLEBLKRDS	NUMBER	Number of single block reads
READTIM	NUMBER	Time (in hundredths of a second) spent doing reads if the TIMED_STATISTICS parameter is true; 0 if false
WRITETIM	NUMBER	Time (in hundredths of a second) spent doing writes if the TIMED_STATISTICS parameter is true; 0 if false
SINGLEBLKRDTIM	NUMBER	Cumulative single block read time (in hundredths of a second)
AVGIOTIM	NUMBER	Average time (in hundredths of a second) spent on I/O, if the TIMED_STATISTICS parameter is true; 0 if false
LSTIOTIM	NUMBER	Time (in hundredths of a second) spent doing the last I/O, if the TIMED_STATISTICS parameter is true; 0 if false
MINIOTIM	NUMBER	Minimum time (in hundredths of a second) spent on a single I/O, if the TIMED_STATISTICS parameter is true; 0 if false
MAXIORTM	NUMBER	Maximum time (in hundredths of a second) spent doing a single read, if the TIMED_STATISTICS parameter is true; 0 if false
MAXIOWTM	NUMBER	Maximum time (in hundredths of a second) spent doing a single write, if the TIMED_STATISTICS parameter is true; 0 if false

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "TIMED_STATISTICS"

10.132 V$TEMPUNDOSTAT

V$TEMPUNDOSTAT shows various statistics related to the temporary undo log for this database instance. It displays a histogram of statistical data to show how the system is working. Each row in the view keeps statistics collected in the instance for a 10-minute interval. The rows are in the descending order of the BEGIN_TIME column value. This view contains a total of 576 rows, spanning a 4-day cycle. This view is similar to the V$UNDOSTAT view.

Column	Datatype	Description
BEGIN_TIME	DATE	Identifies the beginning of the time interval
END_TIME	DATE	Identifies the end of the time interval
UNDOTSN	NUMBER	Represents the last active undo tablespace in the duration of time. The tablespace ID of the active undo tablespace is returned in this column. If more than one undo tablespace was active in that period, the active undo tablespace that was active at the end of the period is reported.
TXNCOUNT	NUMBER	Total number of transaction that have bound to the temp undo segment contained in above tablespace within the interval period
MAXCONCURRENCY	NUMBER	Highest number of transactions executed concurrently which modified temporary objects within the interval period
MAXQUERYLEN	NUMBER	Reserved for future use
MAXQUERYID	VARCHAR2(13)	Reserved for future use
UNDOBLKCNT	NUMBER	Total number of temporary undo blocks consumed
EXTCNT	NUMBER	Total number of extents consumed
USCOUNT	NUMBER	Temp undo segments created in this period
SSOLDERRCNT	NUMBER	Identifies the number of times the error ORA-01555 occurred. You can use this statistic to decide whether or not the UNDO_RETENTION initialization parameter is set properly given the size of the undo tablespace. Increasing the value of UNDO_RETENTION can reduce the occurrence of this error.
NOSPACEERRCNT	NUMBER	Total number of times the error 'no space left for temporary undo' was raised

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "V$UNDOSTAT"

10.133 V$TEXT_WAITING_EVENTS

V$TEXT_WAITING_EVENTS displays information about Oracle Text index maintenance events that have been delayed due to errors or contentions.

Column	Datatype	Description
OWNER#	NUMBER	Text index owner number
TABLE#	NUMBER	Base table object number
INDEX#	NUMBER	Text index object number
TABLE_PARTITION#	NUMBER	Table partition object number
INDEX_PARTITION#	NUMBER	Index partition object number
EVENT_TYPE	VARCHAR2(26)	Text index maintenance event type: • EVENT Stats • EVENT Stats Clean up • MONITOR • OPTIMIZE-Merge • OPTIMIZE-Scheduler • OPTIMIZE-Scheduler Timeout • SYNC-Cleanup batches • SYNC-Inspect • SYNC-Mapping • SYNC-Mapping Timeout • SYNC-Postings Concurrent • SYNC-Postings Serial • SYNC-Ranges • SYNC-Scheduler • SYNC-Writer
ITERATION	NUMBER	Event retry iteration number This value is a number between 0 and 10.
WAIT_TIME	NUMBER	Total time (in milliseconds) that the event will be waiting

Column	Datatype	Description
ELAPSED_TIME	NUMBER	Elapsed time (in milliseconds) since the event started waiting The difference between WAIT_TIME and ELAPSED_TIME indicates how much longer the event will be left waiting.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.134 V$THREAD

V$THREAD displays thread information from the control file. This view does not return meaningful results on a physical standby database.

Column	Datatype	Description
THREAD#	NUMBER	Thread number
STATUS	VARCHAR2(6)	Thread status (OPEN| CLOSED)
ENABLED	VARCHAR2(8)	Enabled status: DISABLED, (enabled) PRIVATE, or (enabled) PUBLIC
GROUPS	NUMBER	Number of log groups assigned to this thread
INSTANCE	VARCHAR2(80)	Instance name, if available
OPEN_TIME	DATE	Last time the thread was opened
CURRENT_GROUP#	NUMBER	Current log group
SEQUENCE#	NUMBER	Sequence number of current log
CHECKPOINT_CHANGE#	NUMBER	SCN at last checkpoint
CHECKPOINT_TIME	DATE	Time of last checkpoint
ENABLE_CHANGE#	NUMBER	SCN at which thread was enabled
ENABLE_TIME	DATE	Time of enable SCN
DISABLE_CHANGE#	NUMBER	SCN at which thread was disabled
DISABLE_TIME	DATE	Time of disable SCN
LAST_REDO_SEQUENCE#	NUMBER	Last redo sequence number written by LGWR
LAST_REDO_BLOCK	NUMBER	Last redo block written by LGWR
LAST_REDO_CHANGE#	NUMBER	SCN of last redo for the thread
LAST_REDO_TIME	DATE	Time of last redo for the thread

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.135 V$THRESHOLD_TYPES

V$THRESHOLD_TYPES displays information about threshold types.

Column	Datatype	Description
METRICS_ID	NUMBER	Metrics ID
METRICS_GROUP_ID	NUMBER	Metrics group ID
OPERATOR_MASK	NUMBER	Operator mask
OBJECT_TYPE	VARCHAR2(64)	Object type: • SYSTEM • FILE • SERVICE • EVENT_CLASS • TABLESPACE • SESSION
ALERT_REASON_ID	NUMBER	ID of the alert reason
METRIC_VALUE_TYPE	NUMBER	Metric value type
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.136 V$TIMER

V$TIMER displays the elapsed time in hundredths of a second. Time is measured since the beginning of the epoch, which is operating system specific, and wraps around to 0 again whenever the value overflows four bytes (roughly 497 days).

Column	Datatype	Description
HSECS	NUMBER	Elapsed time (in hundredths of a second)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.137 V$TIMEZONE_FILE

V$TIMEZONE_FILE describes the time zone file that is currently in use by the database.

Column	Datatype	Description
FILENAME	VARCHAR2(20)	Time zone file name
VERSION	NUMBER	Time zone file version
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.138 V$TIMEZONE_NAMES

V$TIMEZONE_NAMES displays valid time zone names.

Column	Datatype	Description
TZNAME	VARCHAR2(64)	Time zone region (for example, US/Pacific)
TZABBREV	VARCHAR2(64)	Corresponding daylight abbreviation (for example, PDT)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.139 V$TOPLEVELCALL

V$TOPLEVELCALL displays the mapping between Oracle top level calls and names.

Column	Datatype	Description
TOP_LEVEL_CALL#	NUMBER	Oracle top level call number
TOP_LEVEL_CALL_NAME	VARCHAR2(64)	Oracle top level call name
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.140 V$TRANSACTION

V$TRANSACTION lists the active transactions in the system.

Column	Datatype	Description
ADDR	RAW(4 | 8)	Address of the transaction state object
XIDUSN	NUMBER	Undo segment number
XIDSLOT	NUMBER	Slot number
XIDSQN	NUMBER	Sequence number
UBAFIL	NUMBER	Undo block address (UBA) filenum
UBABLK	NUMBER	UBA block number
UBASQN	NUMBER	UBA sequence number
UBAREC	NUMBER	UBA record number
STATUS	VARCHAR2(16)	Status
START_TIME	VARCHAR2(20)	Start time (wall clock)
START_SCNB	NUMBER	Start system change number (SCN) base
START_SCNW	NUMBER	Start SCN wrap
START_UEXT	NUMBER	Start extent number
START_UBAFIL	NUMBER	Start UBA file number
START_UBABLK	NUMBER	Start UBA block number
START_UBASQN	NUMBER	Start UBA sequence number
START_UBAREC	NUMBER	Start UBA record number
SES_ADDR	RAW(4 | 8)	User session object address
FLAG	NUMBER	Flag
SPACE	VARCHAR2(3)	YES if a space transaction
RECURSIVE	VARCHAR2(3)	YES if a recursive transaction
NOUNDO	VARCHAR2(3)	YES if a no undo transaction
PTX	VARCHAR2(3)	YES if parallel transaction
NAME	VARCHAR2(256)	Name of a named transaction
PRV_XIDUSN	NUMBER	Previous transaction undo segment number

Column	Datatype	Description
PRV_XIDSLT	NUMBER	Previous transaction slot number
PRV_XIDSQN	NUMBER	Previous transaction sequence number
PTX_XIDUSN	NUMBER	Rollback segment number of the parent XID
PTX_XIDSLT	NUMBER	Slot number of the parent XID
PTX_XIDSQN	NUMBER	Sequence number of the parent XID
DSCN-B	NUMBER	This column is obsolete and maintained for backward compatibility. The value of this column is always equal to the value in DSCN_BASE.
DSCN-W	NUMBER	This column is obsolete and maintained for backward compatibility. The value of this column is always equal to the value in DSCN_WRAP.
USED_UBLK	NUMBER	Number of undo blocks used
USED_UREC	NUMBER	Number of undo records used
LOG_IO	NUMBER	Logical I/O
PHY_IO	NUMBER	Physical I/O
CR_GET	NUMBER	Consistent gets
CR_CHANGE	NUMBER	Consistent changes
START_DATE	DATE	Start time (wall clock)
DSCN_BASE	NUMBER	Dependent SCN base
DSCN_WRAP	NUMBER	Dependent SCN wrap
START_SCN	NUMBER	Start SCN
DEPENDENT_SCN	NUMBER	Dependent SCN
XID	RAW(8)	Transaction XID
PRV_XID	RAW(8)	Previous transaction XID
PTX_XID	RAW(8)	Parent transaction XID
TXN_PRIORITY	VARCHAR2(7)	Priority of the transaction (HIGH, MEDIUM, or LOW) for the Priority Transactions feature
PRIORITY_TXNS_WAIT_TARGET	NUMBER	If TXN_PRIORITY is HIGH or MEDIUM, the maximum number of seconds the transaction will wait for a row lock before the database rolls back a lower priority transaction holding the lock If the priority is LOW, the value of this column is 0.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.141 V$TRANSACTION_ENQUEUE

V$TRANSACTION_ENQUEUE displays locks owned by transaction state objects.

Column	Datatype	Description
ADDR	RAW(4 | 8)	Address of lock state object
KADDR	RAW(4 | 8)	Address of lock
SID	NUMBER	Identifier for session holding or acquiring the lock
TYPE	VARCHAR2(2)	Type of lock. TX indicates transaction enqueue.
ID1	NUMBER	Lock identifier #1 (depends on type)
ID2	NUMBER	Lock identifier #2 (depends on type)
LMODE	NUMBER	Lock mode in which the session holds the lock: • 0 - none • 1 - null (NULL) • 2 - row-S (SS) • 3 - row-X (SX) • 4 - share (S) • 5 - S/Row-X (SSX) • 6 - exclusive (X)
REQUEST	NUMBER	Lock mode in which the process requests the lock: • 0 - none • 1 - null (NULL) • 2 - row-S (SS) • 3 - row-X (SX) • 4 - share (S) • 5 - S/Row-X (SSX) • 6 - exclusive (X)
CTIME	NUMBER	Time since current mode was granted
BLOCK	NUMBER	The lock is blocking another lock
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.142 V$TRANSPORTABLE_PLATFORM

V$TRANSPORTABLE_PLATFORM displays all platforms that support cross-platform tablespace transport. Specifically, it lists all platforms supported by the RMAN CONVERT TABLESPACE command, along with the endianness of each platform.

Column	Datatype	Description
PLATFORM_ID	NUMBER	Platform identification number
PLATFORM_NAME	VARCHAR2(101)	Platform name

Column	Datatype	Description
ENDIAN_FORMAT	VARCHAR2(14)	Platform endian format: • Big • Little • UNKNOWN FORMAT
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.143 V$TRUE_CACHE

V$TRUE_CACHE displays True Cache configuration information.

- When you query this view on a True Cache, it returns a single row of information about the primary database to which the True Cache is connected.
- When you query this view on a primary database, it returns one row of information for each True Cache that is connected to the primary database.

Column	Datatype	Description
MY_DG_ID	NUMBER	Data Guard ID • When queried on a True Cache, the Data Guard ID of the True Cache • When queried on a primary database, the Data Guard ID of the primary database
REMOTE_DG_ID	NUMBER	Remote Data Guard ID • When queried on a True Cache, the Data Guard ID of the primary database • When queried on a primary database, the Data Guard ID of the True Cache
DEST_ID	NUMBER	Log archive destination parameter identifier • When queried on a True Cache, the value of this column is always 0, because a True Cache does not send online redo log blocks to any destination. • When queried on a primary database, the corresponding destination ID (*n*) of the LOG_ARCHIVE_DEST_*n* initialization parameter. This parameter specifies the network name of the True Cache so that the primary database knows where to send online redo log blocks. This column matches the DEST_ID column in other views related to Data Guard and redo transport services, such as the V$ARCHIVE_DEST and V$DATAGUARD_STATUS views.
TRUE_CACHE_NAME	VARCHAR2(30)	Unique database name (DB_UNIQUE_NAME) of the True Cache
PRIMARY_NAME	VARCHAR2(30)	Unique database name (DB_UNIQUE_NAME) of the primary database

Column	Datatype	Description
STATUS	VARCHAR2(256)	Text describing the current status of the True Cache configuration If there is an issue with the True Cache configuration, then this column displays information about the issue. If there are no issues with the True Cache configuration, then the value of this column is HEALTHY.
REMOTE_VERSION	VARCHAR2(18)	Remote database version • When queried on a True Cache, the database version of the primary database • When queried on a primary database, the database version of the True Cache
CON_ID	NUMBER	The ID of the container to which the data pertains The value of this column is always 0 (CDB$ROOT container).

> **Note:**
>
> This view is available starting with Oracle Database 23ai.

10.144 V$TSDP_SUPPORTED_FEATURE

V$TSDP_SUPPORTED_FEATURE displays information about the features supported by Transparent Sensitive Data Protection (TSDP).

Column	Datatype	Description
FEATURE_NAME	VARCHAR2(200)	The name of the supported feature
FUNCTIONALITY	VARCHAR2(200)	The functionality that is supported within the feature. If all of the functionality of the feature is supported, the value is ALL, otherwise the value will show the specific functionality that is supported.
COMMENTS$	VARCHAR2(4000)	More information regarding the support for the feature and the specific functionality
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> *Oracle Database Security Guide* for more information about using Transparent Sensitive Data Protection.

10.145 V$TYPE_SIZE

V$TYPE_SIZE displays the sizes of various database components for use in estimating data block capacity.

Column	Datatype	Description
COMPONENT	VARCHAR2(8)	Component name, such as segment or buffer header
TYPE	VARCHAR2(8)	Component type
DESCRIPTION	VARCHAR2(32)	Description of the component
TYPE_SIZE	NUMBER	Size of the component
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.146 V$UNDOSTAT

V$UNDOSTAT displays a histogram of statistical data to show how well the system is working. The available statistics include undo space consumption, transaction concurrency, and length of queries executed in the instance. You can use this view to estimate the amount of undo space required for the current workload. Oracle uses this view to tune undo usage in the system. The view returns NULL values if the system is in manual undo management mode. Each row in the view keeps statistics collected in the instance for a 10-minute interval. The rows are in descending order by the BEGIN_TIME column value. Each row belongs to the time interval marked by (BEGIN_TIME, END_TIME). Each column represents the data collected for the particular statistic in that time interval. The first row of the view contains statistics for the (partial) current time period. The view contains a total of 576 rows, spanning a 4 day cycle.

Column	Datatype	Description
BEGIN_TIME	DATE	Identifies the beginning of the time interval
END_TIME	DATE	Identifies the end of the time interval
UNDOTSN	NUMBER	Represents the last active undo tablespace in the duration of time. The tablespace ID of the active undo tablespace is returned in this column. If more than one undo tablespace was active in that period, the active undo tablespace that was active at the end of the period is reported.
UNDOBLKS	NUMBER	Represents the total number of undo blocks consumed. You can use this column to obtain the consumption rate of undo blocks, and thereby estimate the size of the undo tablespace needed to handle the workload on your system.
TXNCOUNT	NUMBER	Identifies the total number of transactions executed within the period

Column	Datatype	Description
MAXQUERYLEN	NUMBER	Identifies the length of the longest query (in seconds) executed in the instance during the period. You can use this statistic to estimate the proper setting of the UNDO_RETENTION initialization parameter. The length of a query is measured from the cursor open time to the last fetch/execute time of the cursor. Only the length of those cursors that have been fetched/executed during the period are reflected in the view.
MAXQUERYID	VARCHAR2(13)	SQL identifier of the longest running SQL statement in the period
MAXCONCURRENCY	NUMBER	Identifies the highest number of transactions executed concurrently within the period
UNXPSTEALCNT	NUMBER	Number of attempts to obtain undo space by stealing unexpired extents from other transactions
UNXPBLKRELCNT	NUMBER	Number of unexpired blocks removed from certain undo segments so they can be used by other transactions
UNXPBLKREUCNT	NUMBER	Number of unexpired undo blocks reused by transactions
EXPSTEALCNT	NUMBER	Number of attempts to steal expired undo blocks from other undo segments
EXPBLKRELCNT	NUMBER	Number of expired undo blocks stolen from other undo segments
EXPBLKREUCNT	NUMBER	Number of expired undo blocks reused within the same undo segments
SSOLDERRCNT	NUMBER	Identifies the number of times the error ORA-01555 occurred. You can use this statistic to decide whether or not the UNDO_RETENTION initialization parameter is set properly given the size of the undo tablespace. Increasing the value of UNDO_RETENTION can reduce the occurrence of this error.
NOSPACEERRCNT	NUMBER	Identifies the number of times space was requested in the undo tablespace and there was no free space available. That is, all of the space in the undo tablespace was in use by active transactions. The corrective action is to add more space to the undo tablespace.
ACTIVEBLKS	NUMBER	Total number of blocks in the active extents of the undo tablespace for the instance at the sampled time in the period
UNEXPIREDBLKS	NUMBER	Total number of blocks in the unexpired extents of the undo tablespace for the instance at the sampled time in the period
EXPIREDBLKS	NUMBER	Total number of blocks in the expired extents of the undo tablespace for the instance at the sampled time in the period
TUNED_UNDORETENTION	NUMBER	Amount of time (in seconds) for which undo will not be recycled from the time it was committed. At any point in time, the latest value of TUNED_UNDORETENTION is used to determine whether data committed at a particular time in the past can be recycled. The value of this column is not meaningful on an Oracle Active Data Guard standby database instance, because the system does not tune this value on such instances.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **See Also:**
>
> "UNDO_RETENTION"

10.147 V$UNUSABLE_BACKUPFILE_DETAILS

V$UNUSABLE_BACKUPFILE_DETAILS displays information about all backup files (backup pieces, proxy copies, or copies) that are marked unavailable and expired. You can select one of the rows and use BTYPE_KEY or FILETYPE_KEY to change the status of a backup file set or a specific file to available.

Column	Datatype	Description
SESSION_KEY	NUMBER	Session identifier
SESSION_RECID	NUMBER	Session record ID
SESSION_STAMP	NUMBER	Session stamp
RMAN_STATUS_RECID	NUMBER	Record ID of the corresponding row in the control file
RMAN_STATUS_STAMP	NUMBER	Timestamp of the row in the controlfile
BTYPE	CHAR(9)	Backup type container. Possible values are: BACKUPSET, IMAGECOPY, PROXYCOPY.
BTYPE_KEY	NUMBER	Unique identifier for the backup type, either BS_KEY or COPY_KEY.
ID1	NUMBER	If BACKUPSET, it contains SET_STAMP. If IMAGECOPY or PROXYCOPY, it is RECID from the control file.
ID2	NUMBER	If BACKUPSET, it contains SET_COUNT. If IMAGECOPY or PROXYCOPY, it is STAMP.
FILETYPE	VARCHAR2(15)	Type of file. Possible values are: BACKUPPIECE, COPY, PROXYCOPY.
FILETYPE_KEY	NUMBER	Backup piece key if the file is a backup piece; otherwise COPY_KEY.
STATUS	VARCHAR2(1)	Status of the backup file, either U (unavailable) or X (expired)
FILESIZE	NUMBER	Size of the file
DEVICE_TYPE	VARCHAR2(17)	Type of device on which the file resides
FILENAME	VARCHAR2(513)	Name of the file
MEDIA	VARCHAR2(65)	Name of the media on which the copy resides. This value is informational only. It is not needed for restore.

Column	Datatype	Description
MEDIA_POOL	NUMBER	Media pool in which the copy resides. This is the same value that was entered in the POOL operand of the Recovery Manager BACKUP command.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.148 V$VERSION

V$VERSION displays the version number of Oracle Database. The database components have the same version number as the database, so the version number is returned only once.

Column	Datatype	Description
BANNER	VARCHAR2(80)	Component name and version number
BANNER_FULL	VARCHAR2(160)	The new 2 line banner format introduced in Oracle Database 18c. The banner displays the database release and version number.
BANNER_LEGACY	VARCHAR2(80)	The legacy 1 line banner used before Oracle Database 18c. This column displays the same value as the BANNER column.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.149 V$VPD_POLICY

V$VPD_POLICY displays all the fine-grained security policies and predicates associated with the cursors currently in the library cache.

Column	Datatype	Description
ADDRESS	RAW(4 | 8)	Cursor address
PARADDR	RAW(4 | 8)	Parent cursor address
SQL_HASH	NUMBER	SQL hash number
SQL_ID	VARCHAR2(13)	SQL identifier
CHILD_NUMBER	NUMBER	Cursor's child number under the parent

Column	Datatype	Description
OBJECT_OWNER	VARCHAR2(128)	Owner of the object with the policy
OBJECT_NAME	VARCHAR2(128)	Name of the object with the policy
POLICY_GROUP	VARCHAR2(128)	Name of the policy group
POLICY	VARCHAR2(128)	Name of the policy
POLICY_FUNCTION_OWNER	VARCHAR2(128)	Owner of the policy function
PREDICATE	VARCHAR2(4000)	Predicate for the policy (truncated to 4000 bytes in length)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.150 V$WAIT_CHAINS

V$WAIT_CHAINS displays information about blocked sessions. A wait chain is composed of sessions that are blocked by one another. Each row represents a blocked and blocker session pair. If a wait chain is not a cyclical wait chain, then the last row for the chain does not have a blocker.

Column	Datatype	Description
CHAIN_ID	NUMBER	A number identifying the wait chain
CHAIN_IS_CYCLE	VARCHAR2(5)	Indicates whether the final blocked session in the wait chain is blocked by the initial blocked session (TRUE) or not (FALSE)
CHAIN_SIGNATURE	VARCHAR2(801)	An Oracle-specific text signature of the wait chain. This signature can be used to identify similar wait chains.
CHAIN_SIGNATURE_HASH	NUMBER	A numeric representation of CHAIN_SIGNATURE
INSTANCE	NUMBER	Blocked session's instance identifier
OSID	VARCHAR2(25)	Blocked session's operating system process identifier
PID	NUMBER	Blocked session's Oracle process identifier
SID	NUMBER	Blocked session's Oracle session identifier
SESS_SERIAL#	NUMBER	Blocked session's Oracle session serial number
PDB_ID	NUMBER	Blocked session's PDB identifier
PDB_NAME	VARCHAR2(31)	Blocked session's PDB name
BLOCKER_IS_VALID	VARCHAR2(5)	Indicates whether the blocked session has a blocker (TRUE) or not (FALSE)
BLOCKER_INSTANCE	NUMBER	Blocker session's instance identifier; NULL if BLOCKER_IS_VALID is FALSE
BLOCKER_OSID	VARCHAR2(25)	Blocker session's operating system process identifier; NULL if BLOCKER_IS_VALID is FALSE
BLOCKER_PID	NUMBER	Blocker session's Oracle process identifier; NULL if BLOCKER_IS_VALID is FALSE

Column	Datatype	Description
BLOCKER_SID	NUMBER	Blocker session's Oracle session identifier; NULL if BLOCKER_IS_VALID is FALSE
BLOCKER_SESS_SERIAL#	NUMBER	Blocker session's Oracle session serial number; NULL if BLOCKER_IS_VALID is FALSE
BLOCKER_PDB_ID	NUMBER	Blocker session's PDB identifier
BLOCKER_PDB_NAME	VARCHAR2(31)	Blocker session's PDB name
BLOCKER_CHAIN_ID	NUMBER	If not NULL, then the blocker session is a member of another chain specified by this chain identifier. For the remaining wait chain information, see the wait chain with the specified CHAIN_ID.
IN_WAIT	VARCHAR2(5)	Indicates whether the blocked session is in a wait (TRUE) or not (FALSE)
TIME_SINCE_LAST_WAIT_SECS	NUMBER	Number of seconds since the last time the blocked session waited; NULL if IN_WAIT is TRUE
WAIT_ID	NUMBER	A number identifying the wait; NULL if IN_WAIT is FALSE
WAIT_EVENT	NUMBER	Resource or event number for which the blocked session is waiting; NULL if IN_WAIT is FALSE
WAIT_EVENT_TEXT	VARCHAR2(64)	Resource or event for which the blocked session is waiting; NULL if IN_WAIT is FALSE
P1	NUMBER	First additional wait parameter; NULL if IN_WAIT is FALSE
P1_TEXT	VARCHAR2(64)	Description of the first additional wait parameter; NULL if IN_WAIT is FALSE
P2	NUMBER	Second additional wait parameter; NULL if IN_WAIT is FALSE
P2_TEXT	VARCHAR2(64)	Description of the second additional wait parameter; NULL if IN_WAIT is FALSE
P3	NUMBER	Third additional wait parameter; NULL if IN_WAIT is FALSE
P3_TEXT	VARCHAR2(64)	Description of the third additional wait parameter; NULL if IN_WAIT is FALSE
IN_WAIT_SECS	NUMBER	Seconds the blocked session has been in the current wait; NULL if IN_WAIT is FALSE
TIME_REMAINING_SECS	NUMBER	Seconds remaining until the blocked session ends its wait (-1 if the blocked session can indefinitely wait); NULL if IN_WAIT is FALSE
NUM_WAITERS	NUMBER	Number of sessions waiting for the blocked session
ROW_WAIT_OBJ#	NUMBER	Object ID for the table containing the row specified in ROW_WAIT_ROW#; NULL if IN_WAIT is FALSE
ROW_WAIT_FILE#	NUMBER	Identifier for the data file containing the row specified in ROW_WAIT_ROW#; NULL if IN_WAIT is FALSE. This column is valid only if the blocked session is currently waiting for another transaction to commit and the value of ROW_WAIT_OBJ# is not -1.
ROW_WAIT_BLOCK#	NUMBER	Identifier for the block containing the row specified in ROW_WAIT_ROW#; NULL if IN_WAIT is FALSE. This column is valid only if the blocked session is currently waiting for another transaction to commit and the value of ROW_WAIT_OBJ# is not -1.
ROW_WAIT_ROW#	NUMBER	Current row being locked; NULL if IN_WAIT is FALSE. This column is valid only if the blocked session is currently waiting for another transaction to commit and the value of ROW_WAIT_OBJ# is not -1.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.151 V$WAITCLASSMETRIC

V$WAITCLASSMETRIC displays metric values of wait classes for the most recent 60-second interval. A history of the last one hour will be kept in the system.

Column	Datatype	Description
BEGIN_TIME	DATE	Begin time of the interval
END_TIME	DATE	End time of the interval
INTSIZE_CSEC	NUMBER	Interval size (in hundredths of a second)
WAIT_CLASS#	NUMBER	Number of the class of the wait event
WAIT_CLASS_ID	NUMBER	Identifier of the class of the wait event
AVERAGE_WAITER_COUNT	NUMBER	Average waiter count
DBTIME_IN_WAIT	NUMBER	Percent of database time spent in the wait
TIME_WAITED	NUMBER	Time waited during the interval (in hundredths of a second)
WAIT_COUNT	NUMBER	Number of times waited
TIME_WAITED_FG	NUMBER	Amount of time (in hundredths of a second) spent in waits from this wait class in foreground sessions
WAIT_COUNT_FG	NUMBER	Number of times foreground processes waited
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.152 V$WAITCLASSMETRIC_HISTORY

V$WAITCLASSMETRIC_HISTORY displays metric values of wait classes for all intervals in the last one hour.

The columns for V$WAITCLASSMETRIC_HISTORY are the same as those for V$WAITCLASSMETRIC.

> **See Also:**
>
> "V$WAITCLASSMETRIC"

10.153 V$WAITSTAT

V$WAITSTAT displays block contention statistics. This table is only updated when timed statistics are enabled.

Column	Datatype	Description
CLASS	VARCHAR2(18)	Class of the block
COUNT	NUMBER	Number of waits by this OPERATION for this CLASS of block
TIME	NUMBER	Sum of all wait times for all the waits by this OPERATION for this CLASS of block (in centiseconds)
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.154 V$WALLET

V$WALLET displays metadata of certificates that may be used as a master key for Transparent Data Encryption.

> **Note:**
>
> The use of PKI encryption with Transparent Data Encryption is deprecated. To configure Transparent Data Encryption, use the ADMINISTER KEY MANAGEMENT SQL statement. See *Oracle Database Advanced Security Guide* for more information.

Column	Datatype	Description
CERT_ID	VARCHAR2(52)	A unique certificate identifier value used to specify a particular PKI certificate for use as the master key
DN	VARCHAR2(255)	Distinguished name of a particular PKI certificate
SERIAL_NUM	VARCHAR2(40)	Unique serial number assigned to a certificate by the issuer or signer
ISSUER	VARCHAR2(255)	Distinguished name of the Certificate Authority or issuer that issued and signed the certificate
KEYSIZE	NUMBER	Size of the PKI key associated with the certificate

Column	Datatype	Description
STATUS	VARCHAR2(16)	Current status of the certificate: • UNUSED • IN USE • USED This column allows the user to identify whether a certificate is currently in use or has already been used for Transparent Data Encryption.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.155 V$WORKLOAD_REPLAY_THREAD

V$WORKLOAD_REPLAY_THREAD displays information for all the different types of replay sessions.

Column	Datatype	Description
CLOCK	NUMBER	Current simulated SCN based on the SCN recorded at capture time
NEXT_TICKER	NUMBER	Next stream ID that will increment the CLOCK after a commit action
SID	NUMBER	Session ID of the replay session
SERIAL#	NUMBER	Session serial number of the replay session
SPID	VARCHAR2(24)	The server process ID of the replay session
LOGON_USER	VARCHAR2(128)	Logon username of the replay session
LOGON_TIME	DATE	Logon time of the replay session
EVENT	VARCHAR2(64)	Event name
EVENT_ID	NUMBER	Event identifier
EVENT#	NUMBER	Event operation code
P1TEXT	VARCHAR2(64)	Text for event parameter 1
P1	NUMBER	Value of event parameter 1
P2TEXT	VARCHAR2(64)	Text for event parameter 2
P2	NUMBER	Value of event parameter 2
P3TEXT	VARCHAR2(64)	Text for event parameter 3
P3	NUMBER	Value of event parameter 3
WAIT_FOR_SCN	NUMBER	The captured SCN for which the current user call should wait
FILE_ID	NUMBER	The stream ID that is being replayed
CALL_COUNTER	NUMBER	The call counter of the user call that is being replayed
DEPENDENT_SCN	NUMBER	The dependent SCN, captured to order the commit actions using block-level dependencies

Column	Datatype	Description
STATEMENT_SCN	NUMBER	Statement SCN
COMMIT_WAIT_SCN	NUMBER	The (maximum) SCN that the current commit should wait for
POST_COMMIT_SCN	NUMBER	The next SCN after the current commit
ACTION_TYPE	NUMBER	The type of commits. The possible values are: COMMIT, ROLLBACK, FAKED_COMMIT, and NULL. A value of NULL means it is not a commit operation.
SESSION_TYPE	VARCHAR2(13)	The type of replay session: LOGON ADMIN DISPATCHER REPLAY
WRC_ID	NUMBER	Unique replay client ID assigned by the server to all participating replay clients when replay starts
SCHEDULE_CAP_ID	NUMBER	An unique identifier for a workload capture added to a replay schedule. A value of 0 is used for a non-consolidated replay.
FILE_NAME	VARCHAR2(51)	File name of the captured stream
SKIP_IT	VARCHAR2(1)	Whether or not the current replayed user call is skipped or not
DIRTY_BUFFERS	VARCHAR2(1)	Reserved for internal use
DBTIME	NUMBER	Accumulated database time for the replay session
NETWORK_TIME	NUMBER	Accumulated network time for the replay session
THINK_TIME	NUMBER	Accumulated think time for the replay session
TIME_GAIN	NUMBER	If nonzero, the accumulated time in macro seconds indicating how fast the replay is
TIME_LOSS	NUMBER	If nonzero, the accumulated time in macro seconds indicating how slow the replay is
USER_CALLS	NUMBER	Total number of user calls
PLSQL_CALLS	NUMBER	Total number of PL/SQL calls recorded in the workload capture
PLSQL_SUBCALLS	NUMBER	Total number of calls recorded in the workload capture for SQL executed from PL/SQL
PLSQL_DBTIME	NUMBER	Total amount of database time in microseconds from PL/SQL calls that have been recorded in the workload capture
CLIENT_OS_USER	VARCHAR2(15)	Operating system username of the replay client
CLIENT_HOST	VARCHAR2(64)	Host name of the replay client
CLIENT_PID	VARCHAR2(24)	Process ID of the replay client
PROGRAM	VARCHAR2(84)	Program name of the replay client
CAPTURE_ELAPSED_TIME	NUMBER	Total amount of elapsed time of a session since capture starts (in seconds)
REPLAY_ELAPSED_TIME	NUMBER	Total amount of elapsed time of a session since replay starts (in seconds)

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.156 V$XML_AUDIT_TRAIL

V$XML_AUDIT_TRAIL shows standard, fine-grained, SYS, and mandatory audit records written in XML format files.

> **Note:**
>
> This view is deprecated and applies only to traditional auditing. Traditional auditing is desupported starting in Oracle Database 23ai. Though traditional auditing is desupported, any current traditional audit settings that you have will still be honored and are viewable with this view. See *Oracle Database Security Guide* for more information about how this desupport works.

Column	Datatype	Description
AUDIT_TYPE	NUMBER	Type of audit row: • 1 = Standard XML Audit • 2 = Fine Grained XML Audit • 4 = SYS XML Audit • 8 = Mandatory XML Audit
SESSION_ID	NUMBER	Numeric ID for the Oracle session
PROXY_SESSIONID	NUMBER	Proxy session serial number, if an enterprise user has logged in through a proxy mechanism
STATEMENTID	NUMBER	Numeric ID for the statement run (a statement may cause multiple audit records)
ENTRYID	NUMBER	Numeric ID for the audit trail entry in the session
EXTENDED_TIMESTAMP	TIMESTAMP(6) WITH TIME ZONE	Timestamp of the audited operation (the timestamp of the user's logon for entries is created by AUDIT SESSION)
GLOBAL_UID	VARCHAR2(32)	Global user identifier for the user, if the user has logged in as an enterprise user
DB_USER	VARCHAR2(128)	Database username of the user whose actions were audited
CLIENTIDENTIFIER	VARCHAR2(64)	Client identifier in the Oracle session
EXT_NAME	VARCHAR2(1024)	User's external name
OS_USER	VARCHAR2(128)	Operating system logon user name of the user whose actions were audited
OS_HOST	VARCHAR2(128)	Client host system name

Column	Datatype	Description
OS_PROCESS	VARCHAR2(16)	Operating system process identifier of the Oracle server process
TERMINAL	VARCHAR2(30)	Identifier for the user's terminal
INSTANCE_NUMBER	NUMBER	Instance number as specified by the INSTANCE_NUMBER initialization parameter
OBJECT_SCHEMA	VARCHAR2(128)	Owner of the audited object
OBJECT_NAME	VARCHAR2(128)	Name of the object affected by the action
POLICY_NAME	VARCHAR2(128)	Name of the fine-grained auditing policy
NEW_OWNER	VARCHAR2(128)	Owner of the object named in the NEW_NAME column
NEW_NAME	VARCHAR2(128)	New name of object after renaming, or the name of an underlying object (for example, CREATE INDEX owner.obj_name ON new_owner.new_name)
ACTION	NUMBER	Numeric code for the action type
STATEMENT_TYPE	NUMBER	Description of the action
TRANSACTIONID	RAW(8)	Identifier of the transaction in which the object is accessed or modified
RETURNCODE	NUMBER	Oracle error code generated by the action. Zero if the action succeeded.
SCN	NUMBER	System change number (SCN) of the query
COMMENT_TEXT	VARCHAR2(4000)	Text comments on standard audit entries. Also indicates how the user was authenticated - the method can be one of the following: • DATABASE - authentication was done by password • NETWORK - authentication was done by Oracle Net Services or the Advanced Networking Option • PROXY - the client was authenticated by another user. The name of the proxy user follows the method type.
AUTH_PRIVILEGES	VARCHAR2(32)	Privileges granted and revoked in GRANT and REVOKE statements recorded for standard audit trail entry
GRANTEE	VARCHAR2(128)	User who granted or revoked the privilege
PRIV_USED	NUMBER	Numerical code of privileges, if any, used in the action
SES_ACTIONS	VARCHAR2(16)	Session summary for standard audit records. A string of 12 characters, one for each action type, in the following order: Alter, Audit, Comment, Delete, Grant, Index, Insert, Lock, Rename, Select, Update, Flashback. Values: - = None, S=Success, F=Failure, B=Both
OS_PRIVILEGE	VARCHAR2(7)	This column is populated only for administrative authentication audit records. It contains the administrative privilege used (for example, SYSDBA, SYSOPER, NONE). For all other types of audit records, the value of this column is null.
ECONTEXT_ID	VARCHAR2(64)	Application execution context identifier
SQL_BIND	VARCHAR2(4000)	List of bind variables used in the statement
SQL_TEXT	VARCHAR2(4000)	The statement or command that triggered the audit event
OBJ_EDITION_NAME	VARCHAR2(128)	Name of the edition containing the audited object
DBID	NUMBER	Database identifier of the audited database

Column	Datatype	Description
RLS_INFO	VARCHAR2(4000)	Stores virtual private database (VPD) policy names and predicates separated by delimiter. To format the output into individual rows, use the DBMS_AUDIT_UTIL.DECODE_RLS_INFO_ATRAIL_XML function.
CURRENT_USER	VARCHAR2(128)	Effective user for the statement execution
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

The SQL_BIND and SQL_TEXT columns are only populated if the AUDIT_TRAIL initialization parameter is set to xml, extended or if the AUDIT_SYS_OPERATIONS initialization parameter is set to TRUE.

See Also:

- "UNIFIED_AUDIT_TRAIL"
- "AUDIT_SYS_OPERATIONS"
- "AUDIT_TRAIL"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_AUDIT_UTIL.DECODE_RLS_INFO_ATRAIL_XML function.

10.157 V$XSTREAM_APPLY_COORDINATOR

V$XSTREAM_APPLY_COORDINATOR displays information about each XStream apply process coordinator. The coordinator for an apply process gets transactions from the apply process reader and passes them to apply servers. An apply process coordinator is a subcomponent of an apply process, outbound server, or inbound server.

Column	Datatype	Description
SID	NUMBER	Session ID of the coordinator's session
SERIAL#	NUMBER	Serial number of the coordinator's session

Column	Datatype	Description
STATE	VARCHAR2(21)	State of the coordinator: • INITIALIZING - Starting up • IDLE - Performing no work • APPLYING - Passing transactions to apply servers • SHUTTING DOWN CLEANLY - Stopping without an error • ABORTING - Stopping because of an apply error
APPLY#	NUMBER	Apply process number. An apply process coordinator is an Oracle background process, prefixed by ap.
APPLY_NAME	VARCHAR2(128)	Name of the apply process
TOTAL_APPLIED	NUMBER	Total number of transactions applied by the apply process since the apply process was last started
TOTAL_WAIT_DEPS	NUMBER	Number of times since the apply process was last started that an apply server waited to apply a logical change record (LCR) in a transaction until another apply server applied a transaction because of a dependency between the transactions
TOTAL_WAIT_COMMITS	NUMBER	Number of times since the apply process was last started that an apply server waited to commit a transaction until another apply server committed a transaction to serialize commits
TOTAL_ADMIN	NUMBER	Number of administrative jobs issued since the apply process was last started
TOTAL_ASSIGNED	NUMBER	Number of transactions assigned to apply servers since the apply process was last started
TOTAL_RECEIVED	NUMBER	Total number of transactions received by the coordinator process since the apply process was last started
TOTAL_IGNORED	NUMBER	Number of transactions which were received by the coordinator but were ignored because they had been previously applied
TOTAL_ROLLBACKS	NUMBER	Number of transactions which were rolled back due to unexpected contention
TOTAL_ERRORS	NUMBER	Number of transactions applied by the apply process that resulted in an apply error since the apply process was last started
UNASSIGNED_COMPLETE_TXNS	NUMBER	Total number of complete transactions that the coordinator has not assigned to any apply servers
LWM_TIME	DATE	Time when the message with the lowest message number was recorded. The creation time of the message with the lowest message number was also recorded at this time.
LWM_MESSAGE_NUMBER	NUMBER	Number of the message corresponding to the low watermark. That is, messages with a commit message number less than or equal to this message number have definitely been applied, but some messages with a higher commit message number also may have been applied.
LWM_MESSAGE_CREATE_TIME	DATE	For captured messages, creation time at the source database of the message corresponding to the low watermark. For user-enqueued messages, time when the message corresponding to the low watermark was enqueued into the queue at the local database.
HWM_TIME	DATE	Time when the message with the highest message number was recorded. The creation time of the message with the highest message number was also recorded at this time.

Column	Datatype	Description
HWM_MESSAGE_NUMBER	NUMBER	Number of the message corresponding to the high watermark. That is, no messages with a commit message number greater than this message number have been applied.
HWM_MESSAGE_CREATE_TIME	DATE	For captured messages, creation time at the source database of the message corresponding to the high watermark. For user-enqueued messages, time when the message corresponding to the high watermark was enqueued into the queue at the local database.
STARTUP_TIME	DATE	Time when the apply process was last started
ELAPSED_SCHEDULE_TIME	NUMBER	Time elapsed (in hundredths of a second) scheduling messages since the apply process was last started
ELAPSED_IDLE_TIME	NUMBER	Elapsed idle time
LWM_POSITION	RAW(64)	Position of the low-watermark LCR
HWM_POSITION	RAW(64)	Position of the high-watermark LCR
PROCESSED_MESSAGE_NUMBER	NUMBER	Message number currently processed by the apply coordinator
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
ACTIVE_SERVER_COUNT	NUMBER	Active server count

Note:

The ELAPSED_SCHEDULE_TIME column is only populated if the TIMED_STATISTICS initialization parameter is set to true, or if the STATISTICS_LEVEL initialization parameter is set to TYPICAL or ALL.

See Also:

- "TIMED_STATISTICS"
- "STATISTICS_LEVEL"

10.158 V$XSTREAM_APPLY_READER

V$XSTREAM_APPLY_READER displays information about each XStream apply reader. The apply reader is a process which reads (dequeues) messages from the queue, computes message dependencies, and builds transactions. It passes the transactions on to the coordinator in

commit order for assignment to the apply servers. An apply reader is a subcomponent of an apply process, outbound server, or inbound server.

Column	Datatype	Description
SID	NUMBER	Session ID of the reader's session
SERIAL#	NUMBER	Serial number of the reader's session
APPLY#	NUMBER	Apply process number. An apply process is an Oracle background process, prefixed by ap.
APPLY_NAME	VARCHAR2(128)	Name of the apply process
STATE	VARCHAR2(36)	Shows the state of the apply reader and the hash server. The possible values include: • INITIALIZING - Starting up • IDLE - Performing no work • DEQUEUE MESSAGES - Dequeuing messages from the queue • SCHEDULE MESSAGES - Computing dependencies between messages and assembling messages into transactions • SPILLING - Spilling unapplied messages from memory to hard disk • PAUSED - WAITING FOR DDL TO COMPLETE - Waiting for a data definition language (DDL) logical change record (LCR) to be applied The state of the apply reader is displayed first, followed by the state of the hash server. A semicolon separates the apply reader state from the hash server state.
TOTAL_MESSAGES_DEQUEUED	NUMBER	Total number of messages dequeued since the apply process was last started
TOTAL_MESSAGES_SPILLED	NUMBER	Number of messages spilled by the reader since the apply process was last started
DEQUEUE_TIME	DATE	Time when the last message was received
DEQUEUED_MESSAGE_NUMBER	NUMBER	Number of the last message received
DEQUEUED_MESSAGE_CREATE_TIME	DATE	For captured messages, creation time at the source database of the last message received. For user-enqueued messages, time when the message was enqueued into the queue at the local database.
SGA_USED	NUMBER	Amount (in bytes) of SGA memory used by the apply process since it was last started
ELAPSED_DEQUEUE_TIME	NUMBER	Time elapsed (in hundredths of a second) dequeuing messages since the apply process was last started
ELAPSED_SCHEDULE_TIME	NUMBER	Time elapsed (in hundredths of a second) scheduling messages since the apply process was last started. Scheduling includes computing dependencies between messages and assembling messages into transactions.
ELAPSED_SPILL_TIME	NUMBER	Elapsed time (in hundredths of a second) spent spilling messages since the apply process was last started
OLDEST_SCN_NUM	NUMBER	Oldest SCN
OLDEST_XIDUSN	NUMBER	Transaction ID undo segment number of the oldest transaction that either has been applied or is being applied
OLDEST_XIDSLT	NUMBER	Transaction ID slot number of the oldest transaction that either has been applied or is being applied

Column	Datatype	Description
OLDEST_XIDSQN	NUMBER	Transaction ID sequence number of the oldest transaction that either has been applied or is being applied
SPILL_LWM_SCN	NUMBER	Spill low-watermark SCN
PROXY_SID	NUMBER	When the apply process uses combined capture and apply, the session ID of the propagation receiver that is responsible for direct communication between capture and apply. If the apply process does not use combined capture and apply, then this column is 0.
PROXY_SERIAL	NUMBER	When the apply process uses combined capture and apply, the serial number of the propagation receiver that is responsible for direct communication between capture and apply. If the apply process does not use combined capture and apply, then this column is 0.
PROXY_SPID	VARCHAR2(12)	When the apply process uses combined capture and apply, the process identification number of the propagation receiver that is responsible for direct communication between capture and apply. If the apply process does not use combined capture and apply, then this column is 0.
BYTES_RECEIVED	NUMBER	When the apply process uses combined capture and apply, the number of bytes received by the apply process from the capture process since the apply process last started. If the apply process does not use combined capture and apply, then this column is not populated.
DEQUEUED_POSITION	RAW(64)	Dequeued position. This column is populated only for an apply process that is functioning as an XStream inbound server.
SPILL_LWM_POSITION	RAW(64)	Spill low-watermark position. This column is populated only for an apply process that is functioning as an XStream inbound server.
OLDEST_TRANSACTION_ID	VARCHAR2(128)	Oldest transaction ID
TOTAL_LCRS_WITH_DEP	NUMBER	Total number of LCRs with row-level dependencies since the apply process last started
TOTAL_LCRS_WITH_WMDEP	NUMBER	Total number of LCRs with watermark dependencies since the apply process last started. A watermark dependency occurs when an apply process must wait until the apply process's low watermark reaches a particular threshold.
TOTAL_IN_MEMORY_LCRS	NUMBER	Total number of LCRs currently in memory
SGA_ALLOCATED	NUMBER	The total amount of shared memory (in bytes) allocated from the XStreams pool for the apply process since the apply process last started
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

> **Note:**
>
> The ELAPSED_SCHEDULE_TIME column is only populated if the TIMED_STATISTICS initialization parameter is set to true, or if the STATISTICS_LEVEL initialization parameter is set to TYPICAL or ALL.

> **See Also:**
>
> - "TIMED_STATISTICS"
> - "STATISTICS_LEVEL"

10.159 V$XSTREAM_APPLY_RECEIVER

V$XSTREAM_APPLY_RECEIVER displays information about the message receiver of the apply process. The values are reset to zero when the database (or instance in an Oracle Real Application Clusters (Oracle RAC) environment) restarts, when apply migrates to another instance, or when the XStream process is stopped.

Column	Datatype	Description
SID	NUMBER	Session ID of the apply receiver
SERIAL#	NUMBER	Serial number of the apply receiver
APPLY_NAME	VARCHAR2(128)	Name of the apply process
STARTUP_TIME	DATE	Startup time of the apply process
SOURCE_DATABASE_NAME	VARCHAR2(128)	Name of the source database
ACKNOWLEDGEMENT	NUMBER	Acknowledgement SCN of the messages received by the receiver
LAST_RECEIVED_MSG	NUMBER	Last received message
TOTAL_MESSAGES_RECEIVED	NUMBER	Total number of messages received
TOTAL_AVAILABLE_MESSAGES	NUMBER	Number of available messages
STATE	VARCHAR2(44)	State of the apply receiver: • Initializing • Sending unapplied txns • Waiting for message from client • Waiting for LCR from client • Receiving LCRs • Evaluating rules • Enqueueing LCRS • Waiting for memory • Waiting for apply to read • Waiting for client flush request to complete • Waiting for client commit to complete
LAST_RECEIVED_MSG_POSITION	RAW(64)	Last received message position

Column	Datatype	Description
ACKNOWLEDGEMENT_POSITION	RAW(64)	Acknowledgement position of the messages received by the receiver. Corresponds to ACKNOWLEDGEMENT, except the value is in position rather than SCN.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.160 V$XSTREAM_APPLY_SERVER

V$XSTREAM_APPLY_SERVER displays information about each XStream apply server and its activities. An apply server receives messages from the apply coordinator for an apply process. For each message received, an apply server either applies the message or sends the message to the appropriate apply handler. An apply server is a subcomponent of an apply process, outbound server, or inbound server.

Column	Datatype	Description
SID	NUMBER	Session ID of the apply server's session
SERIAL#	NUMBER	Serial number of the apply server's session
APPLY#	NUMBER	Apply process number. An apply process is an Oracle background process, prefixed by ap.
APPLY_NAME	VARCHAR2(128)	Name of the apply process
SERVER_ID	NUMBER	Parallel execution server number of the apply server

Column	Datatype	Description
STATE	VARCHAR2(20)	State of the apply server: • INITIALIZING - Starting up • IDLE - Performing no work • RECORD LOW-WATERMARK - Performing an administrative job that maintains information about the apply progress, which is used in the ALL_APPLY_PROGRESS and DBA_APPLY_PROGRESS data dictionary views • ADD PARTITION - Performing an administrative job that adds a partition that is used for recording information about in-progress transactions • DROP PARTITION - Performing an administrative job that purges rows that were used to record information about in-progress transactions • EXECUTE TRANSACTION - Applying a transaction • WAIT COMMIT - Waiting to commit a transaction until all other transactions with a lower commit SCN are applied. This state is possible only if the COMMIT_SERIALIZATION apply process parameter is set to a value other than DEPENDENT_TRANSACTIONS and the PARALLELISM apply process parameter is set to a value greater than 1. • WAIT DEPENDENCY - Waiting to apply a logical change record (LCR) in a transaction until another transaction, on which it has a dependency, is applied. This state is possible only if the PARALLELISM apply process parameter is set to a value greater than 1. • ROLLBACK TRANSACTION - Rolling back a transaction • TRANSACTION CLEANUP - Cleaning up an applied transaction, which includes removing LCRs from the apply process's queue • WAIT FOR CLIENT - Waiting for an XStream client application to request more LCRs • WAIT FOR NEXT CHUNK - Waiting for the next set of LCRs for a large transaction
XIDUSN	NUMBER	Transaction ID undo segment number of the transaction currently being applied
XIDSLT	NUMBER	Transaction ID slot number of the transaction currently being applied
XIDSQN	NUMBER	Transaction ID sequence number of the transaction currently being applied
COMMITSCN	NUMBER	Commit system change number (SCN) of the transaction currently being applied
DEP_XIDUSN	NUMBER	Transaction ID undo segment number of a transaction on which the transaction being applied by this apply server depends
DEP_XIDSLT	NUMBER	Transaction ID slot number of a transaction on which the transaction being applied by this apply server depends
DEP_XIDSQN	NUMBER	Transaction ID sequence number of a transaction on which the transaction being applied by this apply server depends
DEP_COMMITSCN	NUMBER	Commit system change number (SCN) of the transaction on which this apply server depends
MESSAGE_SEQUENCE	NUMBER	Number of the current message being applied by the apply server. This value is reset to 1 at the beginning of each transaction.

Column	Datatype	Description
TOTAL_ASSIGNED	NUMBER	Total number of transactions assigned to the apply server since the apply process was last started
TOTAL_ADMIN	NUMBER	Total number of administrative jobs done by the apply server since the apply process was last started. See the STATE information in this view for the types of administrative jobs.
TOTAL_ROLLBACKS	NUMBER	Number of transactions assigned to this server which were rolled back
TOTAL_MESSAGES_APPLIED	NUMBER	Total number of messages applied by this apply server since the apply process was last started
APPLY_TIME	DATE	Time the last message was applied
APPLIED_MESSAGE_NUMBER	NUMBER	Number of the last message applied
APPLIED_MESSAGE_CREATE_TIME	DATE	Creation time at the source database of the last captured message applied. No information about user-enqueued messages is recorded in this column.
ELAPSED_DEQUEUE_TIME	NUMBER	Time elapsed (in hundredths of a second) dequeuing messages since the apply process was last started
ELAPSED_APPLY_TIME	NUMBER	Time elapsed (in hundredths of a second) applying messages since the apply process was last started
COMMIT_POSITION	RAW(64)	Commit position of the transaction. This column is populated only for an apply process that is functioning as an XStream inbound server.
DEP_COMMIT_POSITION	RAW(64)	Commit position of the transaction the worker depends on. This column is populated only for an apply process that is functioning as an XStream inbound server.
LAST_APPLY_POSITION	RAW(64)	For inbound servers, the position of the last message applied; for outbound servers, the position of the last message sent to the XStream client application. This column is populated only for an apply process that is functioning as an XStream outbound server or inbound server.
TRANSACTION_ID	VARCHAR2(128)	Transaction ID that the worker is applying. This column is populated only for an apply process that is functioning as an XStream inbound server.
DEP_TRANSACTION_ID	VARCHAR2(128)	Transaction ID of the transaction the worker depends on. This column is populated only for an apply process that is functioning as an XStream inbound server.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
TOTAL_LCRS_RETRIED	NUMBER	Total number of LCRs retried by this server
LCR_RETRY_ITERATION	NUMBER	Retry iteration for this transaction by this server
TOTAL_TXNS_RETRIED	NUMBER	Total transactions retried by this server
TXN_RETRY_ITERATION	NUMBER	Retry iteration for this transaction by this server
TOTAL_TXNS_RECORDED	NUMBER	Total transactions recorded in error queue by this server

> **Note:**
>
> The ELAPSED_SCHEDULE_TIME column is only populated if the TIMED_STATISTICS initialization parameter is set to true, or if the STATISTICS_LEVEL initialization parameter is set to TYPICAL or ALL.

> **See Also:**
>
> - "TIMED_STATISTICS"
> - "STATISTICS_LEVEL"

10.161 V$XSTREAM_CAPTURE

V$XSTREAM_CAPTURE displays information about each capture process that sends LCRs to an XStream outbound server.

Column	Datatype	Description
SID	NUMBER	Session identifier of the capture process
SERIAL#	NUMBER	Session serial number of the capture process session
CAPTURE#	NUMBER	Capture process number. A capture process is an Oracle background process prefixed by cp
CAPTURE_NAME	VARCHAR2(128)	Name of the capture process
LOGMINER_ID	NUMBER	Session ID of the Oracle LogMiner session associated with the capture process
STARTUP_TIME	DATE	Time when the capture process was last started

Column	Datatype	Description
STATE	VARCHAR2(551)	State of the capture process: • INITIALIZING - Starting up. • WAITING FOR DICTIONARY REDO - Waiting for redo log files containing the dictionary build related to the first SCN to be added to the capture process session. A capture process cannot begin to scan the redo log files until all of the log files containing the dictionary build have been added. • DICTIONARY INITIALIZATION - Processing a dictionary build. • MINING (PROCESSED SCN = *scn_value*) - Mining a dictionary build at the SCN *scn_value*. • LOADING (step *X* of *Y*) - Processing information from a dictionary build and currently at step *X* in a process that involves *Y* steps, where *X* and *Y* are numbers. • CAPTURING CHANGES - Scanning the redo log for changes that satisfy the capture process rule sets. • WAITING FOR REDO - Waiting for new redo log files to be added to the capture process session. The capture process has finished processing all of the redo log files added to its session. This state is possible if there is no activity at a source database. For a downstream capture process, this state is possible if the capture process is waiting for new log files to be added to its session. • EVALUATING RULE - Evaluating a change against a capture process rule set. • CREATING LCR - Converting a change into an LCR. • ENQUEUING MESSAGE - Enqueuing an LCR that satisfies the capture process rule sets into the capture process queue. • PAUSED FOR FLOW CONTROL - Unable to enqueue LCRs either because of low memory or because propagations and outbound servers are consuming messages slower than the capture process is creating them. This state indicates flow control that is used to reduce spilling of captured LCRs when propagation or apply has fallen behind or is unavailable. • WAITING FOR THE BUFFERED QUEUE TO SHRINK - Waiting for the buffered queue to change to a smaller size. The buffered queue shrinks when there is a memory limitation or when an administrator reduces its size. • WAITING FOR *n* SUBSCRIBER(S) INITIALIZING - Waiting for outbound servers that receive LCRs from the capture process to start, where *n* is the number of apply processes. • WAITING FOR TRANSACTION - Waiting for LogMiner to provide more transactions. • WAITING FOR INACTIVE DEQUEUERS - Waiting for the capture process's queue subscribers to start. The capture process stops enqueuing LCRs if there are no active subscribers to the queue. • SUSPENDED FOR AUTO SPLIT/MERGE - Waiting for a merge operation to complete. • SHUTTING DOWN - Stopping. • ABORTING - Terminating.
TOTAL_PREFILTER_DISCARDED	NUMBER	Total number of prefiltered messages discarded
TOTAL_PREFILTER_KEPT	NUMBER	Total number of prefiltered messages kept

Column	Datatype	Description
TOTAL_PREFILTER_EVALUATIONS	NUMBER	Total number of prefilter evaluations
TOTAL_MESSAGES_CAPTURED	NUMBER	Total number of redo entries passed by LogMiner to the capture process for detailed rule evaluation since the capture process last started. A capture process converts a redo entry into a message and performs detailed rule evaluation on the message when capture process prefiltering cannot discard the change.
CAPTURE_TIME	DATE	Time when the most recent message was captured
CAPTURE_MESSAGE_NUMBER	NUMBER	Number of the most recently captured message
CAPTURE_MESSAGE_CREATE_TIME	DATE	Creation time of the most recently captured message
TOTAL_MESSAGES_CREATED	NUMBER	Count associated with ELAPSED_LCR_TIME to calculate rate
TOTAL_FULL_EVALUATIONS	NUMBER	Count associated with ELAPSED_RULE_TIME to calculate rate
TOTAL_MESSAGES_ENQUEUED	NUMBER	Total number of messages enqueued since the capture process was last started
ENQUEUE_TIME	DATE	Time when the last message was enqueued
ENQUEUE_MESSAGE_NUMBER	NUMBER	Number of the last enqueued message
ENQUEUE_MESSAGE_CREATE_TIME	DATE	Creation time of the last enqueued message
AVAILABLE_MESSAGE_NUMBER	NUMBER	For local capture, the last redo SCN flushed to the log files. For downstream capture, the last SCN added to LogMiner through the archived redo log files.
AVAILABLE_MESSAGE_CREATE_TIME	DATE	For local capture, the time the SCN was written to the log file. For downstream capture, the time the most recent archived redo log file (containing the most recent SCN) was added to LogMiner.
ELAPSED_CAPTURE_TIME	NUMBER	Elapsed time (in hundredths of a second) scanning for changes in the redo log since the capture process was last started
ELAPSED_RULE_TIME	NUMBER	Elapsed time (in hundredths of a second) evaluating rules since the capture process was last started
ELAPSED_ENQUEUE_TIME	NUMBER	Elapsed time (in hundredths of a second) enqueuing messages since the capture process was last started
ELAPSED_LCR_TIME	NUMBER	Elapsed time (in hundredths of a second) creating LCRs since the capture process was last started
ELAPSED_REDO_WAIT_TIME	NUMBER	Elapsed time (in hundredths of a second) spent by the capture process in the WAITING FOR REDO state
ELAPSED_PAUSE_TIME	NUMBER	Elapsed flow control pause time (in hundredths of a second)
STATE_CHANGED_TIME	DATE	Time at which the state of the capture process changed
SGA_USED	NUMBER	The total amount of shared memory (in bytes) currently used by the capture process out of the amount allocated (SGA_ALLOCATED)
SGA_ALLOCATED	NUMBER	The total amount of shared memory (in bytes) allocated from the Streams pool for the capture process
BYTES_OF_REDO_MINED	VARCHAR2(64)	The total amount of redo data mined (in bytes) since the capture process last started
SESSION_RESTART_SCN	VARCHAR2(64)	The SCN from which the capture process started mining redo data when it was last started

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

Note:

The ELAPSED_CAPTURE_TIME, ELAPSED_RULE_TIME, ELAPSED_ENQUEUE_TIME, ELAPSED_LCR_TIME, and ELAPSED_REDO_WAIT_TIME columns are only populated if the TIMED_STATISTICS initialization parameter is set to true, or if the STATISTICS_LEVEL initialization parameter is set to TYPICAL or ALL.

See Also:

- "TIMED_STATISTICS"
- "STATISTICS_LEVEL"

10.162 V$XSTREAM_MESSAGE_TRACKING

V$XSTREAM_MESSAGE_TRACKING displays information about LCRs tracked through the stream that are processed by XStream components.

You can track an LCR through a stream using one of the following methods:

- Set the message_tracking_frequency capture process parameter to 1 or another relatively low value for XStream Outbound processes.
- Set the message_tracking_frequency apply process parameter to 1 or another relatively low value for XStream Inbound processes.
- Use the DBMS_XSTREAM_ADM.SET_MESSAGE_TRACKING procedure to specify a tracking label that becomes part of each LCR generated by the current session.

  When the actions parameter in the DBMS_XSTREAM_ADM.SET_MESSAGE_TRACKING procedure is set to DBMS_XSTREAM_ADM.ACTION_MEMORY, information about the LCRs is tracked in memory, and this view is populated with information about the LCRs. Currently, DBMS_XSTREAM_ADM.ACTION_MEMORY is the only valid setting for the actions parameter in the procedure.

Note:

This view does not display information about messages flowing in an Oracle GoldenGate configuration. To view information about such message streams, query the `V$GOLDENGATE_MESSAGE_TRACKING` view.

Column	Datatype	Description
TRACKING_LABEL	VARCHAR2(128)	User-specified tracking label
TAG	RAW(30)	First 30 bytes of the tag of the LCR
COMPONENT_NAME	VARCHAR2(128)	Name of the component that processed the LCR
COMPONENT_TYPE	VARCHAR2(128)	Type of the component that processed the LCR
ACTION	VARCHAR2(50)	Action performed on the LCR
ACTION_DETAILS	VARCHAR2(100)	Details of the action
TIMESTAMP	TIMESTAMP(9) WITH TIME ZONE	Time when the action was performed
MESSAGE_CREATION_TIME	DATE	Time when the message was created
MESSAGE_NUMBER	NUMBER	SCN of the message
TRACKING_ID	RAW(16)	Globally unique OID of the LCR
SOURCE_DATABASE_NAME	VARCHAR2(128)	Name of the source database
OBJECT_OWNER	VARCHAR2(128)	Owner of the object
OBJECT_NAME	VARCHAR2(128)	Name of the object
XID	VARCHAR2(128)	Transaction ID
COMMAND_TYPE	VARCHAR2(128)	Command type of the LCR
MESSAGE_POSITION	RAW(64)	Position of the message
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • `0`: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • `1`: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

- "V$GOLDENGATE_MESSAGE_TRACKING"
- *Oracle Database PL/SQL Packages and Types Reference* for more information about the DBMS_XSTREAM_ADM package
- *Oracle Database XStream Guide* for more information about XStream concepts

10.163 V$XSTREAM_OUTBOUND_SERVER

V$XSTREAM_OUTBOUND_SERVER displays statistics about an outbound server. An outbound server sends LCRs to the XStream client application.

> **Note:**
>
> When the COMMITTED_DATA_ONLY column is YES in the V$XSTREAM_OUTBOUND_SERVER view, the V$STREAMS_APPLY_SERVER view provides additional information about the outbound server process, and information about the apply server background processes used by the outbound server.

Column	Datatype	Description
SID	NUMBER	Session ID of the outbound server's session
SERIAL#	NUMBER	Serial number of the outbound server's session
SPID	VARCHAR2(12)	Process identification number of the operating-system process that sends LCRs to the client application
SERVER_NAME	VARCHAR2(128)	Name of the outbound server
STARTUP_TIME	DATE	Time when the client application attached to the outbound server

Column	Datatype	Description
STATE	VARCHAR2(19)	State of the outbound server When the COMMITTED_DATA_ONLY column shows YES, the following states are possible: • INITIALIZING - Starting up the outbound server. • IDLE - Performing no work because there are no LCRs to send to the XStream client application. • GET TRANSACTIONS - Receiving transactions from the outbound server's apply coordinator. • SEND TRANSACTION - Sending a transaction to an XStream client application. • WAIT FOR NEXT CHUNK - Waiting for the next set of LCRs for a large transaction. • TRANSACTION CLEANUP - Cleaning up an applied transaction, which includes removing LCRs from the outbound server's queue. • WAIT FOR CLIENT - Waiting for an XStream client application to request more LCRs. When the COMMITTED_DATA_ONLY column shows NO, the following states are possible: • INITIALIZING - Starting up the outbound server. • INITIALIZING RULE EVALUATION CONTEXT - Initializing the context to evaluate the outbound server's rules. • IDLE - Performing no work because there is no LCR to send to the XStream client application. • BROWSING LCR - Browsing the outbound server's queue for next LCR. • EVALUATING RULES - Evaluating an LCR against a rule set. • DEQUEUING LCR - Dequeuing an LCR from the outbound server's queue. • SENDING LCR - Sending an LCR to an XStream client application. • WAITING FOR CAPTURE TO TERMINATE - Waiting for the capture process to become disabled. • SUSPENDED DUE TO A DROPPED SUBSCRIBER - Suspended because a connected subscriber was dropped. For example, a subscriber can be dropped during a split or merge operation. • SUSPENDED FOR AUTO SPLIT/MERGE - Suspended because an automatic split or merge operation is being performed. • WAITING ON EMPTY QUEUE - Waiting for more LCRs from the capture process. • WAITING FOR CLIENT - Waiting for the XStream client application to request more LCRs. • WAITING FOR CAPTURE TO INITIALIZE - Waiting for the capture process to finish the data dictionary build. • WAITING TO ATTACH TO CAPTURE - Waiting for the outbound server to attach to the capture process. When a state refers to a capture process, it is the capture process that captures changes for the outbound server. When a state refers to a propagation, it is the outbound server that sends LCRs to the XStream client application.

Column	Datatype	Description
XIDUSN	NUMBER	Transaction ID undo segment number of the transaction currently being processed. This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.
XIDSLT	NUMBER	Transaction ID slot number of the transaction currently being processed. This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.
XIDSQN	NUMBER	Transaction ID sequence number of the transaction currently being processed. This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.
COMMITSCN	NUMBER	Commit SCN of the transaction currently being processed. This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.
TOTAL_TRANSACTIONS_SENT	NUMBER	Total number of transactions sent by the outbound server to the XStream client application since the last time the client application attached to the outbound server. This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.
MESSAGE_SEQUENCE	NUMBER	Number of the current LCR being processed by the outbound server. This value is reset to 1 at the beginning of each transaction. This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.
TOTAL_MESSAGES_SENT	NUMBER	Total number of LCRs sent by the outbound server to the XStream client application since the last time the client application attached to the outbound server
SEND_TIME	DATE	Time the last LCR was sent by the outbound server to the XStream client application
LAST_SENT_MESSAGE_NUMBER	NUMBER	Message number of the last LCR sent by the outbound server to the XStream client application
LAST_SENT_MESSAGE_CREATE_TIME	DATE	Creation time at the source database of the last LCR sent by the outbound server to the client application
ELAPSED_SEND_TIME	NUMBER	Time elapsed (in hundredths of a second) sending LCRs to the XStream client application since the last time the client application attached to the outbound server
COMMIT_POSITION	RAW(64)	Commit position of the transaction currently being processed. This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.
LAST_SENT_POSITION	RAW(64)	Position of the last LCR sent to the XStream client application. This column is populated only if the COMMITTED_DATA_ONLY column shows YES. When the COMMITTED_DATA_ONLY column shows NO, this column is NULL.
BYTES_SENT	NUMBER	Total number of bytes sent by the outbound server to the XStream client application since the last time the client application attached to the outbound server

Column	Datatype	Description
COMMITTED_DATA_ONLY	CHAR(3)	YES if the outbound server can send only LCRs in committed transactions to the XStream client application. A committed transaction is an assembled, noninterleaving transaction with no rollbacks. NO if the outbound server can send LCRs in transactions that have not yet committed to the XStream client application. This mode is for internal Oracle use only.
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

See Also:

"V$STREAMS_APPLY_SERVER"

10.164 V$XSTREAM_TABLE_STATS

V$XSTREAM_TABLE_STATS shows the statistics for all the tables processed by each apply server for the XStream session.

Column	Datatype	Description
APPLY_NAME	VARCHAR2(128)	Name of XStream Out or XStream In process
SERVER_ID	NUMBER	Parallel apply server worker ID. If the server ID is 0, then this is an aggregate of statistics for servers that may have been automatically shutdown due to session inactivity.
SOURCE_TABLE_OWNER	VARCHAR2(128)	Source owner of the captured or replicated table
SOURCE_TABLE_NAME	VARCHAR2(128)	Source name of the captured or replicated table
DESTINATION_TABLE_OWNER	VARCHAR2(128)	Target owner of the captured or replicated table
DESTINATION_TABLE_NAME	VARCHAR2(128)	Target name of the captured or replicated table
LAST_UPDATE	DATE	Time of last update
TOTAL_INSERTS	NUMBER	Number of insert operations on this table processed by this apply server for the current session
TOTAL_UPDATES	NUMBER	Number of update operations on this table processed by this apply server for the current session
TOTAL_DELETES	NUMBER	Number of delete operations on this table processed by this apply server for the current session
INSERT_COLLISIONS	NUMBER	Number of insert collisions on this table encountered by this apply server for the current session

Column	Datatype	Description
UPDATE_COLLISIONS	NUMBER	Number of update collisions on this table encountered by this apply server for the current session
DELETE_COLLISIONS	NUMBER	Number of delete collisions on this table encountered by this apply server for the current session
REPERROR_RECORDS	NUMBER	Number of change records that were recorded on this table by this apply server for the current session
REPERROR_IGNORES	NUMBER	Number of ignored change records on this table by this apply server for the current session
WAIT_DEPENDENCIES	NUMBER	Number of waits for this table due to dependency for the current session
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data
CDR_INSERT_ROW_EXISTS	NUMBER	Number of conflicts where an insert gets an ORA-00001 error
CDR_UPDATE_ROW_EXISTS	NUMBER	Number of conflicts where an update gets an ORA-26786 error
CDR_UPDATE_ROW_MISSING	NUMBER	Number of conflicts where an update gets an ORA-26787 error
CDR_DELETE_ROW_EXISTS	NUMBER	Number of conflicts where a delete gets an ORA-26786 error
CDR_DELETE_ROW_MISSING	NUMBER	Number of conflicts where a delete gets an ORA-26787 error
CDR_SUCCESSFUL_RESOLUTIONS	NUMBER	Number of successfully resolved conflicts
CDR_FAILED_RESOLUTIONS	NUMBER	Number of conflicts that could not be resolved due to an error during resolution
LOB_OPERATIONS	NUMBER	The number of LOB updates (LOB writes, LOB trims, and LOB erases) applied by the inbound server.

See Also:

Oracle Database XStream Guide for more information about XStream conflict detection and resolution

10.165 V$XSTREAM_TRANSACTION

V$XSTREAM_TRANSACTION displays information about transactions that are being processed by capture processes, outbound servers, and inbound servers. This view can identify long running transactions and to display how many LCRs are being processed in each transaction. This view only contains information about captured LCRs. It does not contain information about user-enqueued LCRs or user messages.
This view only shows information about LCRs that are being processed because they satisfied the rule sets for the component at the time of the query. For capture processes, this view only shows information about changes in transactions that the capture process has

converted into LCRs. It does not show information about all the active transactions present in the redo log.

For outbound servers, this view only shows information about LCRs that the outbound server has dequeued. It does not show information about LCRs in the outbound server's queue. For outbound servers, information about a transaction remains in the view until the transaction is sent to the XStream client application.

For inbound servers, information about a transaction remains in the view until the transaction commits or until the entire transaction is rolled back.

Column	Datatype	Description
COMPONENT_NAME	VARCHAR2(128)	Name of the component
COMPONENT_TYPE	VARCHAR2(20)	Type of component • CAPTURE - Capture process • APPLY - Apply reader subcomponent in an outbound server or inbound server • PROPAGATION_SENDER - Propagation sender that sends LCRs from a capture process to an outbound server
XIDUSN	NUMBER	Transaction ID undo segment number of the transaction
XIDSLT	NUMBER	Transaction ID slot number of the transaction
XIDSQN	NUMBER	Transaction ID sequence number of the transaction
CUMULATIVE_MESSAGE_COUNT	NUMBER	Number of LCRs processed in the transaction. If a component is restarted while the transaction is being processed, then this column shows the number of LCRs processed in the transaction since the component was started.
TOTAL_MESSAGE_COUNT	NUMBER	Total number of LCRs processed in the transaction by an outbound server or inbound server. This column does not pertain to capture processes.
FIRST_MESSAGE_TIME	DATE	Time stamp of the first LCR processed in the transaction. If a capture process is restarted while the transaction is being processed, then this column shows the time stamp of the first LCR processed after the capture process was started.
FIRST_MESSAGE_NUMBER	NUMBER	SCN of the first message in the transaction. If a capture process is restarted while the transaction is being processed, then this column shows the SCN of the first message processed after the capture process was started.
LAST_MESSAGE_TIME	DATE	Time stamp of the last LCR processed in the transaction
LAST_MESSAGE_NUMBER	NUMBER	SCN of the most recent message encountered for the transaction
FIRST_MESSAGE_POSITION	RAW(64)	Position of the first message seen by an XStream inbound server This column is populated only for an apply process that is functioning as an XStream inbound server.
LAST_MESSAGE_POSITION	RAW(64)	Position of the last message seen by an XStream inbound server. This column is populated only for an apply process that is functioning as an XStream inbound server.
TRANSACTION_ID	VARCHAR2(128)	Transaction ID for an XStream inbound server. This column is populated only for an apply process that is functioning as an XStream inbound server.

Column	Datatype	Description
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

10.166 V$ZONEMAP_USAGE_STATS

V$ZONEMAP_USAGE_STATS displays zone map usage statistics.

Column	Datatype	Description
ZONEMAP	VARCHAR2(257)	Name of the zone map in the form of *owner.name*
PRUNING_TYPE	VARCHAR2(11)	Type of data pruning performed using the zone map
EXECUTIONS	NUMBER	Number of executions, including parallel worker executions
BASE_COUNT	NUMBER	Base count accumulated over number of executions
PRUNED_COUNT	NUMBER	Pruned count accumulated over number of executions
CON_ID	NUMBER	The ID of the container to which the data pertains. Possible values include: • 0: This value is used for rows containing data that pertain to the entire CDB. This value is also used for rows in non-CDBs. • 1: This value is used for rows containing data that pertain to only the root • *n*: Where *n* is the applicable container ID for the rows containing data

The ratio (PRUNED_COUNT / BASE_COUNT) shows the fraction of data pruned by the zone map.

Part IV
Appendixes

This part includes the following appendixes:

- Database Limits
- SQL Scripts
- Oracle Wait Events
- Oracle Enqueue Names
- Statistics Descriptions
- Background Processes

A
Database Limits

This appendix lists the limits of values associated with database functions and objects. Limits exist on several levels in the database. There is usually a hard-coded limit in the database that cannot be exceeded. This value may be further restricted for any given operating system. Database limits are divided into four categories:

- Datatype Limits
- Physical Database Limits
- Logical Database Limits
- Process and Runtime Limits

> **See Also:**
>
> Your operating system-specific Oracle documentation

A.1 Datatype Limits

This table documents the limits for datatypes, and includes comments about the datatypes.

Datatypes	Limit	Comments
BFILE	Maximum size: 4 GB Maximum size of a file name: 255 characters Maximum size of a directory name: 128 bytes Maximum number of open BFILEs: see Comments	The maximum number of BFILEs is limited by the value of the SESSION_MAX_OPEN_FILES initialization parameter, which is itself limited by the maximum number of open files the operating system will allow.
BLOB	Maximum size: (4 GB - 1) * DB_BLOCK_SIZE initialization parameter (8 TB to 128 TB)	The number of LOB columns per table is limited only by the maximum number of columns per table (that is, 1000 if MAX_COLUMNS = STANDARD and 4096 if MAX_COLUMNS = EXTENDED[1]). **See Also:** "MAX_COLUMNS" initialization parameter for additional details
CHAR	Maximum size: 2000 bytes	None
CLOB	Maximum size: (4 GB - 1) * DB_BLOCK_SIZE initialization parameter (8 TB to 128 TB)	The number of LOB columns per table is limited only by the maximum number of columns per table (that is, 1000 if MAX_COLUMNS = STANDARD and 4096 if MAX_COLUMNS = EXTENDED[1]). **See Also:** "MAX_COLUMNS" initialization parameter for additional details
JSON	Maximum size: 32 MB	None

Datatypes	Limit	Comments
Literals (characters or numbers in SQL or PL/SQL)	Maximum size: 4000 characters	None
LONG[2]	Maximum size: 2 GB - 1	Only one LONG column is allowed per table.
NCHAR	Maximum size: 2000 bytes	None
NCLOB	Maximum size: (4 GB - 1) * DB_BLOCK_SIZE initialization parameter (8 TB to 128 TB)	The number of LOB columns per table is limited only by the maximum number of columns per table (that is, 1000 if MAX_COLUMNS = STANDARD and 4096 if MAX_COLUMNS = EXTENDED[1]). **See Also:** "MAX_COLUMNS" initialization parameter for additional details
NUMBER	999...(38 9's) x10^{125} maximum value	Can be represented to full 38-digit precision (the mantissa)
	-999...(38 9's) x10^{125} minimum value	Can be represented to full 38-digit precision (the mantissa)
NVARCHAR2	Maximum size: 4000 bytes, or 32767 bytes if the MAX_STRING_SIZE initialization parameter is set to EXTENDED **See Also:** "MAX_STRING_SIZE" initialization parameter for additional details	None
Precision	38 significant digits	None
RAW	Maximum size: 2000 bytes, or 32767 bytes if the MAX_STRING_SIZE initialization parameter is set to EXTENDED **See Also:** "MAX_STRING_SIZE" initialization parameter for additional details	None
VARCHAR2	Maximum size: 4000 bytes, or 32767 bytes if the MAX_STRING_SIZE initialization parameter is set to EXTENDED **See Also:** "MAX_STRING_SIZE" initialization parameter for additional details	None

1 The absolute maximum number of columns in a table is 1000 or 4096, depending on the value of the MAX_COLUMNS initialization parameter. However, when you create an object table (or a relational table with columns of object, nested table, varray, or REF type), Oracle maps the columns of the user-defined types to relational columns, creating in effect hidden columns that count toward the maximum column limit. For details on how Oracle calculates the total number of columns in such a table, refer to *Oracle Database Administrator's Guide*.

2 All forms of LONG data types (LONG, LONG RAW, LONG VARCHAR, LONG VARRAW) were deprecated in Oracle8*i* Release 8.1.6. For succeeding releases, the LONG data type was provided for backward compatibility with existing applications. In new applications developed with later releases, Oracle strongly recommends that you use the CLOB or NCLOB data type for storing large amounts of character data.

See Also:

- *Oracle Database SQL Language Reference* for more information about datatypes
- *Oracle Database SQL Language Reference* for more information on naming database objects

A.2 Physical Database Limits

This table describes limit types and limit values for physical database items.

Item	Type of Limit	Limit Value
Database Block Size	Minimum	`2048` bytes; must be a multiple of operating system physical block size
Database Block Size	Maximum	Operating system dependent; never more than `32` KB
Database Blocks	Minimum in initial extent of a segment	2 blocks
Database Blocks	Maximum per datafile	Platform dependent; typically 2^{22} - 1 blocks
Controlfiles	Number of control files	`1` minimum; `2` or more (on separate devices) strongly recommended
Controlfiles	Size of a control file	Maximum of 201031680 logical blocks
Database files	Maximum per tablespace	Operating system dependent; usually `1023`
Database files	Maximum per database	65533 May be less on some operating systems Limited also by size of database blocks and by the `DB_FILES` initialization parameter for a particular instance
Database extents	Maximum per dictionary managed tablespace	`4` GB * physical block size (with K/M modifier); `4` GB (without K/M modifier)
Database extents	Maximum per locally managed (uniform) tablespace	`2` GB * physical block size (with K/M modifier); `2` GB (without K/M modifier)
Database file size	Maximum	Operating system dependent. Limited by maximum operating system file size. See the **Bigfile Tablespaces** and **Smallfile (traditional) Tablespaces** rows for more information about the maximum database file size in these types of tablespaces.
`MAXEXTENTS`	Default value	Derived from tablespace default storage or `DB_BLOCK_SIZE` initialization parameter
`MAXEXTENTS`	Maximum	Unlimited
Redo Log Files	Maximum number of logfiles	Limited by value of `MAXLOGFILES` parameter in the `CREATE DATABASE` statement Control file can be resized to allow more entries; ultimately an operating system limit
Redo Log Files	Maximum number of logfiles per group	Unlimited

Item	Type of Limit	Limit Value
Redo Log File Size	Minimum size	4 MB
Redo Log File Size	Maximum Size	Operating system limit; typically 2 TB
Tablespaces	Maximum number per database	64 K Number of tablespaces cannot exceed the number of database files because each tablespace must include at least one file
Bigfile Tablespaces	Number of blocks	A bigfile tablespace contains only one datafile or tempfile, which can contain up to approximately 4 billion (2^{32}) blocks. The maximum size of the single datafile or tempfile is 128 terabytes (TB) for a tablespace with 32 K blocks and 32 TB for a tablespace with 8 K blocks.
Smallfile (traditional) Tablespaces	Number of blocks	A smallfile tablespace is a traditional Oracle tablespace, which can contain 1023 datafiles or tempfiles, each of which can contain up to approximately 4 million (2^{22}) blocks.
External Tables file	Maximum size	Dependent on the operating system. An external table can be composed of multiple files.

A.3 Logical Database Limits

This table describes limit types and limit values for logical database items.

Item	Type of Limit	Limit Value
Columns	Maximum per table	If MAX_COLUMNS = STANDARD: 1000 If MAX_COLUMNS = EXTENDED: 4096 (available starting with Oracle Database 23ai) **See Also:** "MAX_COLUMNS" initialization parameter for additional details
Columns	Maximum per index (or clustered index)	32
Columns	Maximum per bitmapped index	30
Constraints	Maximum per column	Unlimited Oracle does not define a limit on the number of constraints per column. However, constraints are subject to the limit on the maximum number of constraints in the database. See the entry for "Constraints - Maximum per database" in this table.
Constraints	Maximum per database	4,294,967,293
Database users	Maximum per database	4,294,967,293
Dictionary-managed database objects	Maximum per database	4,254,950,911 - overhead

Item	Type of Limit	Limit Value
Indexes	Maximum per table	Unlimited Oracle does not define a limit on the number of indexes per table. However, indexes are subject to the limit on the maximum number of dictionary-managed database objects allowed per database. See the entry for "Dictionary-managed database objects" in this table.
Indexes	Total size of indexed column(s)	Approximately 75% of the database block size minus some overhead
Partitions	Maximum length of linear partitioning key	4 KB - overhead
Partitions	Maximum number of columns in partition key	16 columns
Partitions	Maximum number of partitions allowed per table or index	1024K - 1
Rows	Maximum number per table	Unlimited
Stored Packages	Maximum size	Approximately `6,000,000` lines of code. **See Also:** *Oracle Database PL/SQL Language Reference* for details
Subpartitions	Maximum number of subpartitions in a composite partitioned table	1024K - 1
Subqueries	Maximum levels of subqueries in a SQL statement	Unlimited in the `FROM` clause of the top-level query `255` subqueries in the `WHERE` clause
System Change Numbers (SCNs)	Maximum	$2^{63} - 2^{48}$ = 9,223,090,561,878,065,152 SCNs
Tables	Maximum per clustered table	32 tables
Tables	Maximum per database	Unlimited Oracle does not define a limit on the number of tables per database. However, tables are subject to the limit on the maximum number of dictionary-managed database objects allowed per database. See the entry for "Dictionary-managed database objects" in this table.
Trigger Cascade Limit	Maximum value	Operating system-dependent, typically `32`
Users and Roles	Maximum	2,147,483,638

Note:

The limit on how long a SQL statement can be depends on many factors, including database configuration, disk space, and memory

> **Note:**
>
> When an object instance exists in memory, there is no fixed limit on the number of attributes in the object. But the maximum total amount of memory consumed by an object instance is 4 GB. When an object instance is inserted into a table, the attributes are exploded into separate columns in the table, and these columns count toward the limit on the maximum number of columns per table.

A.4 Process and Runtime Limits

This table describes limit types and limit values for process and runtime items.

Item	Type of Limit	Limit Value
Instances per database	Maximum number of cluster database instances per database	Operating system-dependent
Locks	Row-level	Unlimited
SGA size	Maximum value	Operating system-dependent; typically `2` to `4` GB for 32-bit operating systems, and > `4` GB for 64-bit operating systems
Advanced Queuing Processes	Maximum per instance	`10`
Job Queue Processes	Maximum per instance	`1000`
I/O Worker Processes	Maximum per background process (DBWR, LGWR, and so on)	15
I/O Worker Processes	Maximum per Backup session	15
Sessions	Maximum per instance	2^{16}; limited by the `PROCESSES` and `SESSIONS` initialization parameters. 2^{16} is 65536.
Global Cache Service Processes	Maximum per instance	`10`
Shared Servers	Maximum per instance	Unlimited within constraints set by the `PROCESSES` and `SESSIONS` initialization parameters, for instance
Dispatchers	Maximum per instance	Unlimited within constraints set by `PROCESSES` and `SESSIONS` initialization parameters, for instance
Parallel Execution Workers	Maximum per instance	Unlimited within constraints set by `PROCESSES` and `SESSIONS` initialization parameters, for instance
Backup Sessions	Maximum per instance	Unlimited within constraints set by `PROCESSES` and `SESSIONS` initialization parameters, for instance
Services	Maximum per instance	8200

B
SQL Scripts

This appendix describes SQL scripts that are required for optimal operation of the Oracle Database.

The SQL scripts are described in the following sections:

- Creating the Data Dictionary
- Creating Additional Data Dictionary Structures
- The "NO" Scripts
- Upgrade Scripts
- Java Scripts

> **Note:**
>
> Comments within the SQL scripts themselves contain more detailed information and examples.

> **Note:**
>
> To run scripts in a pluggable database (PDB), connect to the PDB before running the script. For more information about running scripts in a multitenant container database (CDB), see *Oracle Multitenant Administrator's Guide*.

B.1 Creating the Data Dictionary

When you use the Database Configuration Assistant to create a database, Oracle automatically creates the data dictionary. Thereafter, whenever the database is in operation, Oracle updates the data dictionary in response to every DDL statement.
The data dictionary base tables are the first objects created in any Oracle database. They are created in the `SYSTEM` tablespace and must remain there. The data dictionary base tables store information about all user-defined objects in the database.

Table B-1 lists required scripts, which are run automatically when you create a database using the Database Configuration Assistant. They are described here because you might need to run them if you create a database manually. To run these scripts, you must be connected to Oracle as a user with `SYSDBA` privileges.

Table B-1 Creating the Data Dictionary Scripts

Script Name	Needed For	Description
`catalog.sql`	All databases	Creates the data dictionary and public synonyms for many of its views Grants `PUBLIC` access to the synonyms
`catproc.sql`	All databases	Runs all scripts required for, or used with, PL/SQL
`catpcat.sql`	All databases	Runs the `catalog.sql` and `catproc.sql` scripts as parallel processes, which can speed up database creation **Note:** You must run `catpcat.sql` by using the `catctl.pl` program. See *Oracle Database Administrator's Guide* for more information.
`catclust.sql`	Oracle Real Application Clusters	Creates Oracle Real Application Clusters data dictionary views

See Also:

- Your operating system-specific Oracle documentation for the exact names and locations of these scripts on your operating system
- *Oracle Database Administrator's Guide* for more information about creating a database
- *Oracle Real Application Clusters Administration and Deployment Guide* for more information about creating Oracle Real Application Cluster views

B.2 Creating Additional Data Dictionary Structures

Oracle Database supplies other scripts that create additional structures you can use in managing your database and creating database applications. These scripts are listed in Table B-2.

See Also:

Your operating system-specific Oracle documentation for the exact names and locations of these scripts on your operating system

Table B-2 Creating Additional Data Dictionary Structures

Script Name	Needed For	Run By	Description
catblock.sql	Performance management	SYS	Creates views that can dynamically display lock dependency graphs **See Also:** *Oracle Database Administrator's Guide*
caths.sql	Heterogeneous Services	SYS	Installs packages for administering heterogeneous services **See Also:** *Oracle Database Gateway for APPC Installation and Configuration Guide for Microsoft Windows*
catio.sql	Performance management	SYS	Allows I/O to be traced on a table-by-table basis
catqueue.sql	Advanced Queuing		Creates the dictionary objects required for Advanced Queuing
catrep.sql	Oracle Replication	SYS	Runs all SQL scripts for enabling database replication
catwrr.sql	Database Replay	SYS	Main script that creates the entire schema related to Database Replay - calls the create schema scripts for Workload Capture, Database Replay, Workload Replay, and Workload Intelligence
catwrrwitb.sql	Database Replay	SYS	Creates the schema for Workload Intelligence
dbmsiotc.sql	Storage management	Any user	Analyzes chained rows in index-organized tables
dbmspool.sql	Performance management	SYS or SYSDBA	Enables DBA to lock PL/SQL packages, SQL statements, and triggers into the shared pool **See Also:** *Oracle Database PL/SQL Packages and Types Reference*
userlock.sql	Concurrency control	SYS or SYSDBA	Provides a facility for user-named locks that can be used in a local or clustered environment to aid in sequencing application actions
utlbstat.sql and utlestat.sql	Performance monitoring	SYS	Respectively start and stop collecting performance tuning statistics
utlchn1.sql	Storage management	Any user	For use with the Oracle Database. Creates tables for storing the output of the ANALYZE command with the CHAINED ROWS option. Can handle both physical and logical rowids. **See Also:** *Oracle Database Administrator's Guide*
utlconst.sql	Year 2000 compliance	Any user	Provides functions to validate that CHECK constraints on date columns are year 2000 compliant

Table B-2 (Cont.) Creating Additional Data Dictionary Structures

Script Name	Needed For	Run By	Description
utldtree.sql	Metadata management	Any user	Creates tables and views that show dependencies between objects **See Also:** *Oracle Database SecureFiles and Large Objects Developer's Guide*
utlexpt1.sql	Constraints	Any user	For use with the Oracle Database. Creates the default table (EXCEPTIONS) for storing exceptions from enabling constraints. Can handle both physical and logical rowids. **See Also:** *Oracle Database Administrator's Guide*
utlfixdirs.sql	Moving a database to a new Oracle home	SYS	Used after moving a database to a new Oracle home. Updates directory objects to use the new path names for the Oracle home and Oracle base directories, as defined by the new values for the ORACLE_HOME and ORACLE_BASE environment variables. When you run this script in the root container of a CDB, it updates directory objects in the root, as well as any Oracle-maintained directory objects in the PDBs; you must manually update any PDB directory objects that are not Oracle-maintained.
utlip.sql	PL/SQL	SYS	Used primarily for upgrade and downgrade operations. It invalidates all existing PL/SQL modules by altering certain dictionary tables so that subsequent recompilations will occur in the format required by the database. It also reloads the packages STANDARD and DBMS_STANDARD, which are necessary for any PL/SQL compilations.
utlirp.sql	PL/SQL	SYS	Used to change from 32-bit to 64-bit word size or vice versa. This script recompiles existing PL/SQL modules in the format required by the new database. It first alters some data dictionary tables. Then it reloads the packages STANDARD and DBMS_STANDARD, which are necessary for using PL/SQL. Finally, it triggers a recompilation of all PL/SQL modules, such as packages, procedures, and types.
utllockt.sql	Performance monitoring	SYS or SYSDBA	Displays a lock wait-for graph, in tree structure format **See Also:** *Oracle Database Administrator's Guide*

Table B-2 (Cont.) Creating Additional Data Dictionary Structures

Script Name	Needed For	Run By	Description
utlpwdmg.sql	Security	SYS or SYSDBA	Creates PL/SQL functions for default password complexity verification. Sets the default password profile parameters and enables password management features. **See Also:** *Oracle Database Security Guide*
utlrp.sql	PL/SQL	SYS	Recompiles all existing PL/SQL modules that were previously in an INVALID state, such as packages, procedures, and types.
utlsampl.sql	Examples	SYS or any user with DBA role	Creates sample tables, such as emp and dept, and users, such as scott
utlscln.sql	Oracle Replication	Any user	Copies a snapshot schema from another snapshot site
utltkprf.sql	Performance management	SYS	Creates the TKPROFER role to allow the TKPROF profiling utility to be run by non-DBA users
utlvalid.sql	Partitioned tables	Any user	Creates tables required for storing output of ANALYZE TABLE ...VALIDATE STRUCTURE of a partitioned table
utlxplan.sql	Performance management	Any user	Creates the table PLAN_TABLE, which holds output from the EXPLAIN PLAN statement See Also: *Oracle Database Data Warehousing Guide*

B.3 The "NO" Scripts

These scripts are used to remove dictionary information for various optional services or components.

Table B-3 The NO Scripts

Script Name	Needed For	Run By	Description
catnoadt.sql	Objects	SYS	Drops views and synonyms on dictionary metadata that relate to object types
catnoaud.sql	Security	SYS	Drops views and synonyms on auditing metadata
catnoclust.sql	Real Application Clusters	SYS	Drops views that are specific to Oracle Real Application Clusters (Oracle RAC)
catnodrdaas.sql	DRDA Application Server	SYS	Drops all DRDA Application Server objects from the database
catnogwm.sql	Global Data Services	SYS	Drops users, roles, and other objects created for Global Data Services.
catnohs.sql	Heterogeneous Services	SYS	Removes Heterogeneous Services dictionary metadata

Table B-3 (Cont.) The NO Scripts

Script Name	Needed For	Run By	Description
catnojav.sql	Java	SYS	Drops the RDBMS Java classes and system triggers created by the catjava.sql script.
catnoprt.sql	Partitioning	SYS	Drops views and synonyms on dictionary metadata that relate to partitioned tables and indexes
catnosvm.sql	Server Manager	SYS	Removes Oracle7 Server Manager views and synonyms
catnowrr.sql	Database Replay	SYS	Main script that drops the entire schema related to Database Replay - calls the drop schema scripts for Workload Capture, Database Replay, Workload Replay, and Workload Intelligence
catnowrrc.sql	Database Replay	SYS	Drops the schema related to Workload Capture
catnowrrp.sql	Database Replay	SYS	Drops the schema related to Workload Replay
catnowrrwitb.sql	Database Replay	SYS	Drops the schema related to Workload Intelligence
catnsnmp.sql	Distributed management	SYS	Drops the DBSNMP user and SNMPAGENT role

B.4 Upgrade Scripts

Upgrade scripts are used when upgrading to another release of Oracle.

> **See Also:**
>
> *Oracle Database Upgrade Guide* for information about upgrade scripts

B.5 Java Scripts

The Java scripts are useful only if the JServer option is installed.

Table B-4 Java Scripts

Script Name	Description
initjvm.sql	Initializes JServer by installing core Java class libraries and Oracle-specific Java classes
rmjvm.sql	Removes all elements of the JServer **See Also:** *Oracle Database Java Developer's Guide*
catjava.sql	Installs Java-related packages and classes

C

Oracle Wait Events

This appendix describes Oracle wait events.

It includes these topics:

- Classes of Wait Events
- Descriptions of Common Wait Event Parameters
- Descriptions of Wait Events

Information about wait events is displayed in three dynamic performance views:

- `V$SESSION_WAIT` displays the events for which sessions have just completed waiting or are currently waiting.
- `V$SYSTEM_EVENT` displays the total number of times all the sessions have waited for the events in that view.
- `V$SESSION_EVENT` is similar to `V$SYSTEM_EVENT`, but displays all waits for each session.

> **See Also:**
>
> "V$SESSION_WAIT", "V$SYSTEM_EVENT", and "V$SESSION_EVENT"

Many of these wait events are tied to the internal implementation of Oracle and therefore are subject to change or deletion without notice. Application developers should be aware of this and write their code to tolerate missing or extra wait events.

The following SQL statement displays an alphabetical list of all Oracle wait events and the wait class to which they belong:

```
SQL> SELECT name, wait_class FROM V$EVENT_NAME ORDER BY name;
```

C.1 Classes of Wait Events

Every wait event belongs to a class of wait event.

The following list describes each of the wait classes.

Administrative

Waits resulting from DBA commands that cause users to wait (for example, an index rebuild)

Application

Waits resulting from user application code (for example, lock waits caused by row level locking or explicit lock commands)

Cluster

Waits related to Oracle Real Application Clusters resources (for example, global cache resources such as 'gc cr block busy')

Commit

This wait class only comprises one wait event - wait for redo log write confirmation after a commit (that is, 'log file sync')

Concurrency

Waits for internal database resources (for example, latches)

Configuration

Waits caused by inadequate configuration of database or instance resources (for example, undersized log file sizes, shared pool size)

Idle

Waits that signify the session is inactive, waiting for work (for example, 'SQL*Net message from client')

Network

Waits related to network messaging (for example, 'SQL*Net more data to dblink')

Other

Waits which should not typically occur on a system (for example, 'wait for EMON to spawn')

Queueing

Contains events that signify delays in obtaining additional data in a pipelined environment. The time spent on these wait events indicates inefficiency or other problems in the pipeline. It affects features such as parallel queries or `DBMS_PIPE` PL/SQL packages.

Scheduler

Resource Manager related waits (for example, 'resmgr: become active')

System I/O

Waits for background process I/O (for example, DBWR wait for 'db file parallel write')

User I/O

Waits for user I/O (for example 'db file sequential read')

C.2 Descriptions of Common Wait Event Parameters

This section describes some of the common wait event parameters.

block#

This is the block number of the block for which Oracle needs to wait. The block number is relative to the start of the file. To find the object to which this block belongs, issue the following SQL statement:

```
select segment_name, segment_type, owner, tablespace_name
from dba_extents
where file_id = file#
     and block#
     between block_id and block_id + blocks - 1;
```

blocks

The number of blocks that is being either read from or written to the file. The block size depends on the file type:

- Database files have a block size of `DB_BLOCK_SIZE`
- Logfiles and control files have a block size that is equivalent to the physical block size of the platform

break?

If the value for this parameter equals 0, a reset was sent to the client. A nonzero value indicates that a break was sent to the client.

class

The class of the block describes how the contents of the block are used. For example, class 1 represents data block, and class 2 represents sort block. Use this SQL query to see the block classes:

```
select view_definition
from v$fixed_view_definition
where view_name='GV$WAITSTAT';
```

dba

The initials "dba" represents the data block address, which consists of a file number and a block number.

driver id

The address of the disconnect function of the driver that is currently being used.

file#

The following query returns the name of the database file:

```
select *
from v$datafile
where file# = file#;
```

id1

The first identifier (*id1*) of the enqueue or global lock takes its value from P2 or P2RAW. The meaning of the identifier depends on the name (P1).

id2

The second identifier (*id2*) of the enqueue or global lock takes its value from P3 or P3RAW. The meaning of the identifier depends on the name (P1).

mode

The *mode* is usually stored in the low order bytes of P1 or P1RAW and indicates the mode of the enqueue or global lock request. This parameter has one of the following values:

Table C-1 Lock Mode Values

Mode Value	Description
1	Null mode
2	Sub-Share
3	Sub-Exclusive
4	Share
5	Share/Sub-Exclusive
6	Exclusive

Use the following SQL statement to retrieve the name of the lock and the mode of the lock request:

```
select chr(bitand(p1,-16777216)/16777215)||
       chr(bitand(p1, 16711680)/65535) "Lock",
       bitand(p1, 65535) "Mode"
from v$session_wait
where event = 'DFS enqueue lock acquisition';
```

name and type

The name or "type" of the enqueue or global lock can be determined by looking at the two high order bytes of P1 or P1RAW. The name is always two characters. Use the following SQL statement to retrieve the lock name.

```
select chr(bitand(p1,-16777216)/16777215)||
      chr(bitand(p1,16711680)/65535) "Lock"
from v$session_wait
where event = 'DFS enqueue lock acquisition';
```

namespace

The name of the object namespace as it is displayed in `V$DB_OBJECT_CACHE` view.

requests

The number of I/Os that are "requested." This differs from the number of blocks in that one request could potentially contain multiple blocks.

session#

The number of the inactive session. Use the following SQL statement to find more information about the session:

```
select *
from v$session
where sid = session#;
```

waited

This is the total amount of time the session has waited for this session to terminate.

C.3 Descriptions of Wait Events

This section provides detailed descriptions for those wait events of greatest interest.

Where appropriate, pointers are provided to further information elsewhere in Oracle Database documentation. For a complete listing of wait events, in alphabetical order, you can issue the following SQL statement:

```
SQL> SELECT name FROM V$EVENT_NAME ORDER BY name;
```

C.3.1 alter system set dispatcher

A session has issued a statement `ALTER SYSTEM SET DISPATCHER = string` and is waiting for the dispatchers to get started.

Wait Time: The session will wait 1 / 100 of a second and verify if the new dispatchers have started, else the session will wait again

Parameter	Description
waited	Number of times that the session has waited 1 / 100 of a second

C.3.2 ARCH Remote Write

Used to track the time (in centiseconds) that ARC*n* background processes spend blocked waiting for network write operations to complete.

C.3.3 ASYNC Remote Write

Used to track the time (in centiseconds) for asynchronous streaming RFSWRITE operations. This includes stall reaps and streaming network submission time. This time is accumulated by TT*nn* (Redo Transport Worker) background processes.

> **See Also:**
>
> *Oracle Data Guard Concepts and Administration* for more information about using RFS to manage standby redo logs.

C.3.4 BFILE check if exists

The session waits to check if an external large object (LOB) exists.

Wait Time: The total elapsed time for the **exists** call

Parameter	Description
session#	See "session#"
waited	See "waited"

C.3.5 BFILE check if open

The session waits for an external large object (LOB) to open.

Wait Time: The total elapsed time for the **isopen** call

Parameter	Description
session#	See "session#"
waited	See "waited"

C.3.6 BFILE closure

The session waits for an external large object (LOB) to close.

Wait Time: The total elapsed time for the **close** call

Parameter	Description
session#	See "session#"
waited	See "waited"

C.3.7 BFILE get length

The session waits on a call to check the size of an external large object (LOB).

Wait Time: The total elapsed time for the call to check the LOB size

Parameter	Description
session#	See "session#"
waited	See "waited"

C.3.8 BFILE get name object

The session waits on a call to find or generate the external name of a external large object.

Wait Time: The total elapsed time for **make external file name** to complete

Parameter	Description
session#	See "session#"
waited	See "waited"

C.3.9 BFILE get path object

The session is waiting on a call to find or generate the external path name of an external large object (LOB).

Wait Time: The total elapsed time for **make external path** to complete

Parameter	Description
session#	See "session#"
waited	See "waited"

C.3.10 BFILE internal seek

The session waits for a positioning call within the external large object (LOB) to complete.

Wait Time: The total elapsed time for the **seek** to complete

Parameter	Description
session#	See "session#"
waited	See "waited"

C.3.11 BFILE open

The session waits for an external large object (LOB) to open.

Wait Time: The total elapsed time for the **isopen** call

Parameter	Description
session#	See "session#"
waited	See "waited"

C.3.12 BFILE read

The session waits for a read from a external large object (LOB) to complete.

Wait Time: The total elapsed time for the **read** to complete

Parameter	Description
session#	See "session#"
waited	See "waited"

C.3.13 broadcast mesg queue transition

Processes enter "wait for broadcast mesg queue transition" when cleaning up a publisher channel handle to a RELIABLE broadcast channel. The publisher is responsible for moving the message to the free queue, but it cannot do so until the message is in the done queue. If the message is still not in the done queue, process enters this wait. This wait event will most likely appear when an Oracle process is about to exit normally, or when PMON cleans up a terminated process.

Wait Time: Varies

Parameter	Description
channel handle	publisher channel handle pointer
message	broadcast message pointer
location	A number indicating the function in KSR where the process is waiting

C.3.14 broadcast mesg recovery queue transition

Processes enter "wait for broadcast mesg recovery queue transition" when cleaning up a publisher channel handle to a RELIABLE broadcast channel. The broadcasted message is in the recovery queue of another channel handle (for example, ch2). Process enters this wait, if the message is yet to be removed from the recovery queue of the ch2 channel handle. This wait event will most likely appear when an Oracle process is about to exit normally, or when PMON cleans up a terminated process.

Wait Time: Varies

Parameter	Description
channel handle	Publisher channel handle pointer
message	Broadcast message pointer
location	A number indicating the function in KSR where the process is waiting

C.3.15 buffer busy waits

Wait until a buffer becomes available.

There are four reasons that a session cannot pin a buffer in the buffer cache, and a separate wait event exists for each reason:

1. "buffer busy waits": A session cannot pin the buffer in the buffer cache because another session has the buffer pinned.
2. "read by other session": A session cannot pin the buffer in the buffer cache because another session is reading the buffer from disk.
3. "gc buffer busy acquire": A session cannot pin the buffer in the buffer cache because another session is reading the buffer from the cache of another instance.
4. "gc buffer busy release": A session cannot pin the buffer in the buffer cache because another session on another instance is taking the buffer from this cache into its own cache so it can pin it.

Prior to release 10.1, all four reasons were covered by "buffer busy waits." In release 10.1, the "gc buffer busy" wait event covered both the "gc buffer busy acquire" and "gc buffer busy release" wait events.

Wait Time: Normal wait time is 1 second. If the session was waiting for a buffer during the last wait, then the next wait will be 3 seconds.

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about the potential causes of the buffer busy waits wait event

C.3.16 buffer deadlock

Oracle does not really wait on this event; the foreground only yields the CPU. Thus, the chances of catching this event are very low. This is not an application induced deadlock, but an assumed deadlock by the cache layer. The cache layer cannot get a buffer in a certain mode within a certain amount of time.

Wait Time: 0 seconds. The foreground process only yields the CPU and will usually be placed at the end of the CPU run queue.

Parameter	Description
class	See "class"
mode	See "mode"
flag	The flag points to the internal flags used by the session to get this block
dba	See "dba"

C.3.17 buffer latch

The session waits on the buffer hash chain latch. Primarily used in the dump routines.

Wait Time: 1 second

Parameter	Description

latch addr	The virtual address in the SGA where this latch is located. Use the following statement to find the name of this latch:
	`select *`
	`from v$latch a, v$latchname b`
	`where addr = latch addr`
	`and a.latch# = b.latch#;`

Parameter	Description
chain#	The index into array of buffer hash chains. When the chain is 0xffffffff, the foreground waits on the LRU latch.

C.3.18 buffer read retry

This event occurs only if the instance is mounted in shared mode (Oracle Real Application Cluster).
During the read of the buffer, the contents changed. This means that either:

- The version number, dba, or the incarnation and sequence number stored in the block no longer match
- The checksum on the block does not match the checksum in the block

The block will be reread (this may fail up to 3 times), then corruption is assumed and the corrupt block is dumped in the trace file.

Wait Time: The wait time is the elapsed time of the read

Parameter	Description
file#	See "file#"
block#	See "block#"

C.3.19 checkpoint completed

A session waits for a checkpoint to complete. This could happen, for example, during a close database or a local checkpoint.

Wait Time: 5 seconds

Parameters: None

C.3.20 cleanup of aborted process

When a process spawn is terminated while the process spawning background is in the middle of spawning, the current session must wait until the pid of the new process is filled in. Once the pid is filled in, then the process spawn can be actually terminated.

Wait Time: Usually 3 seconds

Parameter	Description
location	Location of the wait

C.3.21 control file parallel write

This event occurs while the session is writing physical blocks to all control files. This happens when:

- The session starts a control file transaction (to ensure the control files are up to date in case the session crashes before committing the control file transaction)

- The session commits a transaction to a control file
- Changing a generic entry in the control file, the new value is being written to all control files

Wait Time: The wait time is the time it takes to finish all writes to all control files

Parameter	Description
files	The number of control files to which the session is writing
blocks	The number of blocks that the session is writing to the control file
requests	The number of I/O requests which the session wants to write

C.3.22 control file sequential read

Reading from the control file. This happens often. For example, while:

- Making a backup of the control files
- Sharing information (between instances) from the control file
- Reading other blocks from the control files
- Reading the header block

Wait Time: The wait time is the elapsed time of the read

Parameter	Description
file#	The control file from which the session is reading
block#	Block number in the control file from where the session starts to read. The block size is the physical block size of the port (usually 512 bytes, some UNIX ports have 1 or 2 Kilobytes).
blocks	The number of blocks that the session is trying to read

C.3.23 control file single write

This wait is signaled while the control file's shared information is written to disk. This is an atomic operation protected by an enqueue (CF), so that only one session at a time can write to the entire database.

Wait Time: The wait time is the elapsed time of the write

Parameter	Description
file#	This identifies the control file to which the session is currently writing
block#	Block number in the control file where the write begins. The block size is the as the physical block size of the port (usually 512 bytes, some UNIX ports have 1 or 2 Kilobytes).
blocks	The number of blocks that the session is trying to write

C.3.24 cursor: mutex S

A session waits on this event when it is requesting a mutex in shared mode, when another session is currently holding a this mutex in exclusive mode on the same cursor object.

Parameter	Description
P1	Hash value of cursor
P2	Mutex value (top 2 bytes contain SID holding mutex in exclusive mode, and bottom two bytes usually hold the value 0)
P3	Mutex where (an internal code locator) OR'd with Mutex Sleeps

C.3.25 cursor: mutex X

The session requests the mutex for a cursor object in exclusive mode, and it must wait because the resource is busy. The mutex is busy because either the mutex is being held in exclusive mode by another session or the mutex is being held shared by one or more sessions. The existing mutex holder(s) must release the mutex before the mutex can be granted exclusively.

Parameter	Description
P1	Hash value of cursor
P2	Mutex value (top 2 bytes contain SID holding mutex in exclusive mode, and bottom two bytes usually hold the value 0)
P3	Mutex where (an internal code locator) OR'd with Mutex Sleeps

C.3.26 cursor: pin S

A session waits on this event when it wants to update a shared mutex pin and another session is currently in the process of updating a shared mutex pin for the same cursor object. This wait event should rarely be seen because a shared mutex pin update is very fast.

Wait Time: Microseconds

Parameter	Description
P1	Hash value of cursor
P2	Mutex value (top 2 bytes contains SID holding mutex in exclusive mode, and bottom two bytes usually hold the value 0)
P3	Mutex where (an internal code locator) OR'd with Mutex Sleeps

C.3.27 cursor: pin S wait on X

A session waits for this event when it is requesting a shared mutex pin and another session is holding an exclusive mutex pin on the same cursor object.

Wait Time: Microseconds

Parameter	Description
P1	Hash value of cursor
P2	Mutex value (top 2 bytes contains SID holding mutex in exclusive mode, and bottom two bytes usually hold the value 0)

Parameter	Description
P3	Mutex where (an internal code locator) OR'd with Mutex Sleeps

C.3.28 cursor: pin X

A session waits on this event when it is requesting an exclusive mutex pin for a cursor object and it must wait because the resource is busy. The mutex pin for a cursor object can be busy either because a session is already holding it exclusive, or there are one or more sessions which are holding shared mutex pin(s). The exclusive waiter must wait until all holders of the pin for that cursor object have released it, before it can be granted.

Wait Time: Microseconds

Parameter	Description
P1	Hash value of cursor
P2	Mutex value (top 2 bytes contains SID holding mutex in exclusive mode, and bottom two bytes usually hold the value 0)
P3	Mutex where (an internal code locator) OR'd with Mutex Sleeps

C.3.29 db file async I/O submit

When asynchronous I/O is available, this wait event captures any time spent in submitting I/Os to the underlying storage.

> **See Also:**
>
> "db file parallel write"

C.3.30 db file parallel read

This happens during recovery. It can also happen during buffer prefetching, as an optimization (rather than performing multiple single-block reads). Database blocks that must be changed as part of recovery are read in parallel from the database.

Wait Time: Wait until all of the I/Os are completed

Parameter	Description
files	This indicates the number of files to which the session is reading
blocks	This indicates the total number of blocks to be read
requests	This indicates the total number of I/O requests, which will be the same as blocks

C.3.31 db file parallel write

This event occurs in the DBWR. It indicates the time that DBWR spends waiting for I/O completion.

If asynchronous I/O is available, then the db file async I/O submit wait event captures any time spent in submitting I/Os to the underlying storage.

When asynchronous I/O is not available, db file parallel write captures the time spent during submit and reap.

Wait Time: While there are outstanding I/Os, DBWR waits for some of the writes to complete. DBWR does not wait for all of the outstanding I/Os to complete.

Parameter	Description
requests	This indicates the total number of I/O requests, which will be the same as blocks
interrupt	
timeout	This indicates the timeout value in hundredths of a second to wait for the I/O completion.

See Also:

- *Oracle Database Performance Tuning Guide* about how this wait event can help identify I/O problems
- "db file async I/O submit"

C.3.32 db file scattered read

Similar to the “db file sequential read” wait event, except that the session is reading multiple data blocks.

Wait Time: The wait time is the actual time it takes to do all of the I/Os

Parameter	Description
file#	See "file#"
block#	See "block#"
blocks	The number of blocks that the session is trying to read from the *file#* starting at *block#*

See Also:

- *Oracle Database Performance Tuning Guide* for more information about this wait event
- *Oracle Database Performance Tuning Guide* about how this wait event can help identify I/O problems
- *Oracle Database Performance Tuning Guide* about potential causes for this wait event

C.3.33 db file sequential read

The session waits while a sequential read from the database is performed. This event is also used for rebuilding the control file, dumping data file headers, and getting the database file headers.

Wait Time: The wait time is the actual time it takes to do the I/O

Parameter	Description
file#	See "file#"
block#	See "block#"
blocks	This is the number of blocks that the session is trying to read (should be 1)

See Also:

- *Oracle Database Performance Tuning Guide* for more information about this wait event
- *Oracle Database Performance Tuning Guide* for more information about how this wait event can help identify I/O problems
- *Oracle Database Performance Tuning Guide* about potential causes for this wait event

C.3.34 db file single write

This event is used to wait for the writing of the file headers.

Wait Time: The wait time is the actual time it takes to do the I/O

Parameter	Description
file#	See "file#"
block#	See "block#"
blocks	This is the number of blocks that the session is trying to write in *file# starting at block#*

> **See Also:**
>
> - *Oracle Database Performance Tuning Guide* about how this wait event can help identify I/O problems

C.3.35 DFS lock handle

The session waits for the lock handle of a global lock request. The lock handle identifies a global lock. With this lock handle, other operations can be performed on this global lock (to identify the global lock in future operations such as conversions or release). The global lock is maintained by the DLM.

Wait Time: The session waits in a loop until it has obtained the lock handle from the DLM. Inside the loop there is a wait of 0.5 seconds.

Parameter	Description
name	See "name and type"
mode	See "mode"
id1	See "id1"
id2	See "id2"

C.3.36 direct path read

During Direct Path operations the data is asynchronously read from the database files. At some stage the session needs to make sure that all outstanding asynchronous I/O have been completed to disk. This can also happen if during a direct read no more slots are available to store outstanding load requests (a load request could consist of multiple I/Os).

Wait Time: 10 seconds. The session will be posted by the completing asynchronous I/O. It will never wait the entire 10 seconds. The session waits in a tight loop until all outstanding I/Os have completed.

Parameter	Description
descriptor address	This is a pointer to the I/O context of outstanding direct I/Os on which the session is currently waiting
first dba	The dba of the oldest I/O in the context referenced by the descriptor address
block cnt	Number of valid buffers in the context referenced by the descriptor address

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this wait event

C.3.37 direct path sync

During Direct Path write operations the data is asynchronously written to the database files. At some point the session needs to ensure that all outstanding asynchronous I/O have been completed to disk. On UNIX the `fsync` command, which synchronizes data to disk, is issued to confirm that all the writes have completed and the data is all on disk.

Wait Time: The time taken for the fsync operation to complete, which normally is the time taken to complete the outstanding I/Os.

Parameters	Description
file#	See "file#"
flags	Flags used for debugging purposes

C.3.38 direct path write

During Direct Path operations, the data is asynchronously written to the database files. At some stage the session needs to make sure that all outstanding asynchronous I/O have been completed to disk. This can also happen if, during a direct write, no more slots are available to store outstanding load requests (a load request could consist of multiple I/Os).

Wait Time: 10 seconds. The session will be posted by the completing asynchronous I/O. It will never wait the entire 10 seconds. The session waits in a tight loop until all outstanding I/Os have completed.

Parameter	Description
descriptor address	This is a pointer to the I/O context of outstanding direct I/Os on which the session is currently waiting
first dba	The dba of the oldest I/O in the context referenced by the descriptor address
block cnt	Number of valid buffers in the context referenced by the descriptor address

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this parameter

C.3.39 Disk file operations I/O

This event is used to wait for disk file operations (for example, open, close, seek, and resize). It is also used for miscellaneous I/O operations such as block dumps and password file accesses.

Wait Time: The wait time is the actual time it takes to do the I/O

Parameter	Description
FileOperation	Type of file operation

Parameter	Description
fileno	File identification number
filetype	Type of file (for example, log file, data file, and so on)

C.3.40 dispatcher shutdown

During shutdown immediate or normal, the shutdown process must wait for all the dispatchers to shutdown. As each dispatcher is signaled, the session that causes the shutdown waits on this event until the requested dispatcher is no longer running.

Wait Time: 1 second

Parameter	Description
waited	Indicates the cumulative wait time. After 5 minutes, the session writes to the alert and trace files to indicate that there might be a problem.

> **See Also:**
>
> *Oracle Database SQL Language Reference* for information about shutting down a dispatcher using `SHUTDOWN` clause of the SQL `ALTER SYSTEM` statement

C.3.41 dispatcher timer

This basically means that the dispatcher is idle and waiting for some work to arrive.

Wait Time: 60 seconds

Parameter	Description
sleep time	The intended sleep time. The dispatcher will return to work sooner if it is posted by either data arriving on the network or by a post from a shared server process to send data back to the client.

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this wait event

C.3.42 dupl. cluster key

It is possible for a race condition to occur when creating a new cluster key. If it is found that another process has put the cluster key into the data/index block, then the session waits and retries. The retry should then find a valid cluster key.

Wait Time: 0.01 seconds

Parameter	Description
dba	The dba of the block into which the session is trying to insert a cluster key

C.3.43 enq: OW - initialization

A session will wait on this event if it is trying to initialize the database wallet, and another session has already begun an initialization.

Wait Time: Total time necessary to initialize the wallet context

Parameters: None

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about the potential causes of an enqueue wait event

C.3.44 enq: OW - termination

A session will wait on this event if it is trying to terminate the database wallet, and another session has already begun a termination.

Wait Time: Total time necessary to deallocate memory used by the wallet context and terminate the context.

Parameters: None

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about the potential causes of an enqueue wait event

C.3.45 enq: SV - contention

A session is accessing a sequence number from an ordered sequence object.

Wait Time: The wait time is the actual time waited until the requested sequence number is acquired.

Parameter	Description
id1	Sequence object#

> **See Also:**
>
> *Oracle Database SQL Language Reference* for more information about sequences

C.3.46 enq: TX - index contention

Occurs when a transaction inserting a row in an index has to wait for the end of an index block split being done by another transaction.

C.3.47 enq: TX - row lock (HIGH priority)

This wait event occurs when a transaction with `HIGH` priority is waiting for a row lock being held by another transaction.

This wait event is useful when configuring Priority Transactions. You can observe the statistics for this wait event to determine whether the wait time for `HIGH` priority transactions is appropriate for your environment.

Wait Time: The amount of time specified by the `PRIORITY_TXNS_HIGH_WAIT_TARGET` initialization parameter.

Parameter	Description
name	See "name and type"
mode	See "mode"
usn<<16	Undo segment number
slot	Slot number
sequence	Sequence number

> **See Also:**
>
> - *Oracle Database Administrator's Guide* for information about configuring Priority Transactions
> - "PRIORITY_TXNS_HIGH_WAIT_TARGET"

C.3.48 enq: TX - row lock (LOW priority)

This wait event occurs when a transaction with `LOW` priority is waiting for a row lock being held by another transaction.

This wait event is useful when configuring Priority Transactions. You can observe the statistics for this wait event to determine how long `LOW` priority transactions are waiting for row locks.

Wait Time: Total time necessary to obtain the row lock

Parameter	Description
name	See "name and type"
mode	See "mode"
usn<<16	Undo segment number
slot	Slot number
sequence	Sequence number

See Also:

- *Oracle Database Administrator's Guide* for information about configuring Priority Transactions

C.3.49 enq: TX - row lock (MEDIUM priority)

This wait event occurs when a transaction with `MEDIUM` priority is waiting for a row lock being held by another transaction.

This wait event is useful when configuring Priority Transactions. You can observe the statistics for this wait event to determine whether the wait time for `MEDIUM` priority transactions is appropriate for your environment.

Wait Time: The amount of time specified by the `PRIORITY_TXNS_MEDIUM_WAIT_TARGET` initialization parameter.

Parameter	Description
name	See "name and type"
mode	See "mode"
usn<<16	Undo segment number
slot	Slot number
sequence	Sequence number

See Also:

- *Oracle Database Administrator's Guide* for information about configuring Priority Transactions
- "PRIORITY_TXNS_MEDIUM_WAIT_TARGET"

C.3.50 enq: TX - row lock contention

This wait event can occur for several reasons.

- If one user is wanting to update or delete a row or rows that another session is modifying. The session holding the lock will release it when it performs a COMMIT or ROLLBACK.
- If a session is waiting due to potential duplicates in a UNIQUE index. If two sessions try to insert the same key value, the second session has to wait to see if an ORA-0001 should be raised or not. The session holding the lock will release it when it performs a COMMIT or ROLLBACK.
- If a session is waiting due to a shared bitmap index fragment. Bitmap indexes index key values and a range of rowids. Each entry in a bitmap index can cover many rows in the actual table. If two sessions want to update rows covered by the same bitmap index fragment, then the second session waits for the first transaction to either COMMIT or ROLLBACK by waiting for the TX lock.

C.3.51 enqueue

The session is waiting for a local enqueue.

The wait depends on the name of the enqueue (see Oracle Enqueue Names).

Wait Time: Depends on the enqueue name

Parameter	Description
name	See "name and type"
mode	See "mode"

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about the potential causes of an enqueue wait event

C.3.52 flashback buf free by RVWR

This wait event only occurs when Flashback Database is turned on. A session waits for recovery writer (RVWR) to write flashback data to the flashback logs on disk because the buffers are full. Until RVWR can free up the buffers, the session may need to wait.

If this event becomes a top wait event for the database, it is typically because the file system or storage system for the Fast Recovery Area does not support enough bandwidth for Oracle to write the flashback database logs. Refer to the Flashback Database section in *Oracle Database Backup and Recovery User's Guide* for tuning considerations.

Wait Time: 1 second

Parameters: None

C.3.53 flashback log file sync

Waits for flashback database data to be written to disk.

Wait Time: Includes RVWR writing the flashback database data and posting this process

Parameters: None

C.3.54 free buffer waits

This wait event can occur for several reasons.

- All buffer gets have been suspended. This could happen when a file was read-only and is now read/write. All the existing buffers must be invalidated since they are not linked to lock elements (needed when mounted parallel (shared)). So cache buffers are not assigned to data block addresses until the invalidation is finished.
- The session moved some dirty buffers to the dirty queue and now this dirty queue is full. The dirty queue must written first. The session will wait on this event and try again to find a free buffer
- This also happens after inspecting **free buffer inspected** buffers. If no free buffer is found, Oracle waits for one second, and then tries to get the buffer again (depends on the context). For more information, see free buffer inspected.

Wait Time: 1 second

Parameter	Description
file#	See "file#"
block#	See "block#"

> **See Also:**
>
> - *Oracle Database Performance Tuning Guide* for more information about this wait event
> - *Oracle Database Performance Tuning Guide* about potential causes of this wait event

C.3.55 free global transaction table entry

The session is waiting for a free slot in the global transaction table (used by the Distributed Database option). It will wait for 1 second and try again.

Wait Time: 1 second

Parameter	Description
tries	The number of times the session tried to find a free slot in the global transaction table

C.3.56 free process state object

Used during the creation of a process. The session will scan the process table and look for a free process slot. If none can be found, PMON is posted to check if all the processes currently in the process table are still running. If there are terminated processes, then PMON will clean them and make the process slot available to new processes. The waiting process will then rescan the process table to find the new slot.

Wait Time: 1 second

Parameters: None

C.3.57 gc buffer busy acquire

This event indicates that the requested buffer was globally busy in the cluster, because it had already been requested from a remote instance by another local client.

Wait Time: The wait time is the actual time it took to resolve the buffer contention.

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

C.3.58 gc buffer busy release

This event indicates that the requested buffer was globally busy in the cluster, because the requested buffer had been transferred away by a remote instance and needed to be requested again.

Wait Time: The wait time is the actual time it took to resolve the buffer contention.

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

C.3.59 gc cr block 2-way

This event indicates that the requested consistent read (CR) buffer was transferred from another instance in the cluster, and 2 network hops were involved in the request. The Cache Fusion protocol guarantees that requests are fulfilled in 3 hops or less, regardless of the number of instances in the cluster.

Wait Time: The wait time is the actual time it took to receive the requested buffer.

Parameter	Description
file#	See "file#"
block#	See "block#"

Parameter	Description
class#	See "class"

C.3.60 gc cr block 3-way

This event indicates that the requested consistent read (CR) buffer was transferred from another instance in the cluster, and 3 network hops were involved in the request. The Cache Fusion protocol guarantees that requests are fulfilled in 3 hops or less, regardless of the number of instances in the cluster.

Wait Time: The wait time is the actual time it took to receive the requested buffer.

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

C.3.61 gc cr block busy

This event indicates that the requested consistent read (CR) buffer was transferred from another instance in the cluster, but the request had to be put on hold at the serving instance.

This could happen when a dirty buffer had to be transferred, in which case REDO needs to be flushed before the Cache Fusion transfer could be processed. This could also happen if the requested buffer was being held by another process on the remote instance. The serving instance would transfer the requested buffer once the REDO flush is complete, or once the buffer is released by the holding process.

Wait Time: The wait time is the actual time it took to receive the requested buffer.

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

C.3.62 gc cr block congested

This event indicates that the requested consistent read (CR) buffer was transferred from another instance in the cluster, but the request was queued at the serving instance for too long.

This could happen when the GCS server processes (LMS*n* and LM*nn*) are very busy due to having a high volume of incoming Cache Fusion requests. Increasing the GCS server processes (`GCS_SERVER_PROCESSES`) is usually the remedy to alleviate congestion for the GCS server processes.

Wait Time: The wait time is the actual time it took to receive the requested buffer.

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

> **See Also:**
>
> "GCS_SERVER_PROCESSES"

C.3.63 gc cr block direct read

This event indicates that the requested consistent read (CR) buffer was transferred from another instance in the cluster, and the buffer was directly read from the remote cache utilizing the RDMA protocol.

Wait Time: The wait time is the actual time it took to receive the requested buffer.

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

C.3.64 gc cr block lost

This event indicates that a Cache Fusion consistent read (CR) buffer request resulted in a potentially lost block. The request will be re-tried automatically.

This is typically caused by unreliable interconnect network protocols, usually when the network is congested and packets are dropped. It can also be the result of interconnect hardware errors or simply the result of an overloaded system, or a sign that a public network path is used for Cache Fusion instead of a private network.

Wait Time: The wait time is the actual time it took to detect the potentially lost block.

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

C.3.65 gc cr grant read-mostly invalidation

The client is performing a DML on a read-mostly object, which requires a read lock invalidation on all other instances.

Wait Time: The wait time is the actual time it takes to complete the invalidation on all other instances.

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

C.3.66 gc cr multi block grant

This event indicates that a client requested multiple consistent read (CR) buffers from another instance in the cluster, and the request resulted in multiple lock grants from the remote instance.

Wait Time: The wait time is the actual time waited for the multi-block request to complete.

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

C.3.67 gc cr multi block mixed

This event indicates that a client requested multiple consistent read (CR) buffers from another instance in the cluster, and the remote instance returned a mixture of blocks and grants.

Wait Time: The wait time is the actual time waited for the multi-block request to complete.

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

C.3.68 gc cr request

This event is used for ongoing Cache Fusion consistent read (CR) buffer requests. The event is renamed to reflect the actual outcome of the request (example: "gc cr block 2-way") upon completion of the wait. Therefore, these events will not be reported in AWR reports, but may appear in ASH data.

Wait Time: The wait time is the actual time waited for the request.

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

C.3.69 gc current block 2-way

This event indicates that the requested current buffer was transferred from another instance in the cluster, and 2 network hops were involved in the request. The Cache Fusion protocol guarantees that requests are fulfilled in 3 hops or less, regardless of the number of instances in the cluster.

Wait Time: The wait time is the actual time it took to receive the requested buffer.

Parameter	Description
file#	See "file#"
block#	See "block#"
id#	Block class and global access mode held and requested

C.3.70 gc current block 3-way

This event indicates that the requested current buffer was transferred from another instance in the cluster, and 3 network hops were involved in the request. The Cache Fusion protocol guarantees that requests are fulfilled in 3 hops or less, regardless of the number of instances in the cluster.

Wait Time: The wait time is the actual time it took to receive the requested buffer.

Parameter	Description
file#	See "file#"
block#	See "block#"
id#	Block class and global access mode held and requested

C.3.71 gc current block busy

This event indicates that the requested current buffer was transferred from another instance in the cluster, but the request had to be put on hold at the serving instance.

This could happen when a dirty buffer had to be transferred, in which case REDO needs to be flushed before the Cache Fusion transfer could be processed. This could also happen if the requested buffer was being held by another process on the remote instance. The serving instance would transfer the requested buffer once the REDO flush is complete, or once the buffer is released by the holding process.

Wait Time: The wait time is the actual time it took to receive the requested buffer.

Parameter	Description
file#	See "file#"
block#	See "block#"
id#	Block class and global access mode held and requested

C.3.72 gc current block congested

This event indicates that the requested current buffer was transferred from another instance in the cluster, but the request was queued at the serving instance for too long.

This could happen when the GCS server processes (LMS) are very busy due to having a high volume of incoming Cache Fusion requests. Increasing the GCS server processes (`GCS_SERVER_PROCESSES`) is usually the remedy to alleviate congestion for the GCS server processes.

Wait Time: The wait time is the actual time it took to receive the requested buffer.

Parameter	Description
file#	See "file#"
block#	See "block#"
id#	Block class and global access mode held and requested

> **See Also:**
>
> "GCS_SERVER_PROCESSES"

C.3.73 gc current block direct read

This event indicates that the requested current buffer was transferred from another instance in the cluster, and the buffer was directly read from the remote cache utilizing the RDMA protocol.

Wait Time: The wait time is the actual time it took to receive the requested buffer.

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

C.3.74 gc current block lost

This event indicates that a Cache Fusion current buffer request resulted in a potentially lost block. The request will be re-tried automatically.

This is typically caused by unreliable interconnect network protocols, usually when the network is congested and packets are dropped. It can also be the result of interconnect hardware errors or simply the result of an overloaded system, or a sign that a public network path is used for Cache Fusion instead of a private network.

Wait Time: The wait time is the actual time it took to detect the potentially lost block.

Parameter	Description
file#	See "file#"
block#	See "block#"
id#	Block class and global access mode held and requested

C.3.75 gc current request

This event is used for ongoing Cache Fusion current buffer requests. The event is renamed to reflect the actual outcome of the request (example: "gc current block 2-way") upon completion of the wait. Therefore, these events will not be reported in AWR reports, but may appear in ASH data.

Wait Time: The wait time is the actual time waited for the request.

Parameter	Description
file#	See "file#"
block#	See "block#"
id#	Block class and global access mode held and requested

C.3.76 inactive session

This event is used for switching and terminating sessions.

- Switching sessions

  If a timeout period has been specified, then wait that amount of time for the session to be detached.

- Terminating sessions

  From either `KILL SESSION` or internal request. Having posted a session that it should terminate itself, wait for up to 1 minute for the session to terminate.

Wait Time: 1 second

Parameter	Description
session#	See "session#"
waited	See "waited"

C.3.77 inactive transaction branch

The session waits for a transaction branch that is currently used by another session.

Wait Time: 1 second

Parameter	Description
branch#	The serial number of the transaction for which the session is waiting
waited	See "waited"

C.3.78 index split completion

This event occurs when a transaction inserting a row into an index must wait for the end of an index block split being performed by another transaction. In an Oracle RAC database, some index split waits will use this wait event in lieu of the "enq: TX - index contention" wait event.

Wait Time: The wait time is the actual time waited for the split to complete.

Parameter	Description
undo seg#	The rollback segment ID
slot#	The slot ID inside the rollback segment
wrap#	The sequence number that is incremented for each transaction
count	The number of times that the session has waited on this transaction

C.3.79 instance state change

The session waits for SMON to enable or disable cache or transaction recovery. This usually happens during `ALTER DATABASE OPEN` or `CLOSE`.

Wait Time: Wait time depends on the amount of time the action takes (that is, the amount of recovery needed)

Parameter	Description
layer	This value can be 1 or 2. If 1, it means that the transaction layer wants transaction recovery to be performed. If 2, it means that cache recovery will be performed.
value	This value can be 0 (disable) or 1 (enable)
waited	The number of seconds waited so far

C.3.80 io done

The session waits for an I/O to complete or it waits for a worker process to become available to submit the I/O request. This event occurs on platforms that do not support asynchronous I/O.

Wait Time: 50 milliseconds

Parameter	Description
msg ptr	A pointer to the I/O request

C.3.81 ksxr wait for mount shared

The cross instance broadcast facility of this Oracle instance is waiting for the database mount in shared mode to complete.

Wait Time: The time taken for the instance to mount. An indefinite wait on this event implies that the instance startup is hanging.

C.3.82 ktm: instance recovery

The session waits for SMON to finish the instance, transaction recovery, or sort segment cleanup.

Wait Time: The wait time can vary and depends on the amount of recovery needed

Parameter	Description

undo segment#	If the value is 0, SMON is probably performing instance recovery. If P1 > 0, use this query to find the undo segment:
	`select *`
	`from v$rollstat`
	`where usn = undo segment#;`

C.3.83 latch activity

This event is used as part of the process of determining whether a latch must be cleaned.

Wait Time: 0.05 to 0.1 seconds

Parameter	Description
address	The address of the latch that is being checked

number	The latch number of the latch that has activity. To find more information on the latch, use the following SQL statement:
	`select *`
	`from v$latchname`
	`where latch# = number;`

process#	If this is 0, it is the first phase of the in-flux tests

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about latch wait events

C.3.84 latch free

The process waits for a latch that is currently busy (held by another process).

Wait Time: The wait time increases exponentially and does not include spinning on the latch (active waiting). The maximum wait time also depends on the number of latches that the process is holding. There is an incremental wait of up to 2 seconds.

Parameter	Description
address	The address of the latch for which the process is waiting

Parameter	Description

number	The latch number that indexes in the `V$LATCHNAME` view.To find more information on the latch, use the following SQL statement:
	`select *`
	`from v$latchname`
	`where latch# = number;`

tries	A count of the number of times the process tried to get the latch (slow with spinning) and the process has to sleep

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about latch wait events

C.3.85 latch: redo copy

Redo copy latches are acquired by sessions in order to write changes into the redo log buffer and by the LGWR process to ensure that there are no current writers before it copies data from the buffer to the redo log.

C.3.86 library cache load lock

The session tries to find the load lock for the database object so that it can load the object. The load lock is always obtained in Exclusive mode, so that no other process can load the same object. If the load lock is busy the session will wait on this event until the lock becomes available.

Wait Time: 3 seconds (1 second for PMON)

Parameter	Description
object address	Address of the object being loaded
lock address	Address of load lock being used
mask	Indicates which data pieces of the object that must loaded

C.3.87 library cache lock

This event controls the concurrency between clients of the library cache. It acquires a lock on the object handle so that either:

- One client can prevent other clients from accessing the same object
- The client can maintain a dependency for a long time (for example, no other client can change the object)

This lock is also obtained to locate an object in the library cache.

Wait Time: 3 seconds (1 second for PMON)

Parameter	Description
handle address	Address of the object being loaded
lock address	Address of the load lock being used. This is not the same thing as a latch or an enqueue, it is a State Object.
mode	Indicates the data pieces of the object which must be loaded
namespace	See "namespace"

See Also:

- *Oracle Database Performance Tuning Guide* for more information about this wait event
- *Oracle Database Performance Tuning Guide* for more information about potential causes of this wait event

C.3.88 library cache pin

This event manages library cache concurrency. Pinning an object causes the heaps to be loaded into memory. If a client wants to modify or examine the object, the client must acquire a pin after the lock.

Wait Time: 3 seconds (1 second for PMON)

Parameter	Description
handle address	Address of the object being loaded
pin address	Address of the load lock being used. This is not the same thing as a latch or an enqueue, it is basically a State Object.
mode	Indicates which data pieces of the object that must be loaded
namespace	See "namespace"

See Also:

- *Oracle Database Performance Tuning Guide* for more information about this wait event
- *Oracle Database Performance Tuning Guide* for more information about potential causes of this wait event

C.3.89 library cache shutdown

The process shutting down the instance waits for sessions to complete before proceeding with library cache shutdown.

C.3.90 library cache: mutex X

Library cache mutexes protect hash buckets within the shared pool. Each hash bucket contains a number of cursors. The mutex must be held in exclusive mode before any of the structures that it protects can be changed. This wait event is often associated with high parse activity.

C.3.91 Log archive I/O

Used local archiving of online redo logs (for a production database) or standby redo logs (for a standby database). When the archiving process exhausts its I/O buffers because all of them are being used for on-going I/O's, the wait for an available I/O buffer is captured in this system wait event.

Wait Time: Depends on the speed of the disks

Parameters: None

C.3.92 log buffer space

Waiting for space in the log buffer because the session is writing data into the log buffer faster than LGWR can write it out. Consider making the log buffer bigger if it is small, or moving the log files to faster disks such as striped disks.

Wait Time: Usually 1 second, but 5 seconds if it is waiting for a Switch Logfile to complete

Parameters: None

> **See Also:**
>
> - *Oracle Database Performance Tuning Guide* for more information about this wait event
> - *Oracle Database Performance Tuning Guide* for more information about potential causes of this wait event

C.3.93 log file parallel write

Writing redo records to the redo log files from the log buffer.

Wait Time: Time it takes for the I/Os to complete. Even though redo records are written in parallel, the parallel write is not complete until the last I/O is on disk.

Parameter	Description
files	Number of files to be written
blocks	Number of blocks to be written
requests	Number of I/O requests

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for information about how this wait event can help identify I/O problems

C.3.94 log file sequential read

Waiting for the read from this logfile to return. This is used to read redo records from the log file.

Wait Time: Time it takes to complete the physical I/O (read)

Parameter	Description
log#	The relative sequence number of the logfiles within a log group (used only when dumping the logfiles)
block#	See "block#"
blocks	The number of blocks to read

C.3.95 log file single write

Waiting for the write to this logfile to complete. This event is used while updating the header of the logfile. It is signaled when adding a log file member and when incrementing sequence numbers.

Wait Time: Time it takes for the physical I/O (write) to complete

Parameter	Description
log#	This is the number of the group/log to which the session is currently writing
block#	See "block#"
blocks	The number of blocks to write

C.3.96 log file switch (archiving needed)

Waiting for a log switch because the log that the LGWR will be switching into has not been archived yet. Check the alert log to ensure that archiving has not stopped due to a failed archive write. To speed archiving, consider adding more archive processes or putting the archive files on striped disks.

Wait Time: 1 second

Parameters: None

C.3.97 log file switch (checkpoint incomplete)

Waiting for a log switch because the session cannot wrap into the next log. Wrapping cannot be performed because the checkpoint for that log has not completed.

Wait Time: 1 second

Parameters: None

C.3.98 log file switch (clearing log file)

Waiting for a log switch because the log is being cleared due to a `CLEAR LOGFILE` command or implicit clear logfile executed by recovery.

Wait Time: 1 second

Parameters: None

C.3.99 log file switch (private strand flush incomplete)

User sessions trying to generate redo, wait on this event when LGWR waits for DBWR to complete flushing redo from IMU buffers into the log buffer; when DBWR is complete LGWR can then finish writing the current log, and then switch log files.

Wait Time: 1 second

Parameters: None

C.3.100 log file switch completion

Waiting for a log switch to complete.

Wait Time: 1 second

Parameters: None

C.3.101 log file sync

When a user session commits, the session's redo information must be flushed to the redo logfile. The user session will post the LGWR to write the log buffer to the redo log file. When the LGWR has finished writing, it will post the user session.

Wait Time: The wait time includes the writing of the log buffer and the post.

Parameter	Description
buffer#	The number of the physical buffer in the redo log buffer that must be synchronized

See Also:

- *Oracle Database Performance Tuning Guide* for more information about this wait event
- *Oracle Database Performance Tuning Guide* for information about potential causes of this wait event

C.3.102 log switch/archive

Used as part of the `ALTER SYSTEM ARCHIVE LOG CHANGE` *scn* statement. The session waits for the current log from all open threads to be archived.

Wait Time: Wait for up to 10 seconds

Parameter	Description
thread#	The thread number of the thread that is currently archiving its current log

C.3.103 optimizer stats update retry

When concurrent sessions try to update optimizer statistics for the same object, all of them except the one that successfully acquired all necessary locks/pins on the library/row cache entries, wait on this wait event and then retry locking after a short period of time. In addition to explicit statistics gathering and maintenance operations using the `DBMS_STATS` package, Oracle database itself may try to update statistics for some objects, either on behalf of the user or for its own maintenance purposes.

Wait Time: 10 ms

Parameters: None

C.3.104 parallel recovery change buffer free

The parallel recovery coordinator is waiting for a change mapping buffer to be released by one of the recovery workers.

Wait Time: 100ms

Parameters: None

C.3.105 parallel recovery control message reply

The parallel recovery coordinator is waiting for all recovery workers to respond to a synchronous control message.

Wait Time: 100ms

Parameters: None

C.3.106 parallel recovery coord send blocked

The parallel recovery coordinator cannot send a redo change message because the recovery worker is still actively applying redo that it has already received and has not yet released the channel.

Wait Time: 100ms

Parameters: None

C.3.107 parallel recovery coord wait for reply

The parallel recovery coordinator is waiting for all recovery workers to exit.

Wait Time: 100ms

Parameters: None

C.3.108 parallel recovery coordinator waits for slave cleanup

The parallel recovery coordinator is waiting for all recovery workers to exit gracefully.

Wait Time: 10ms

Parameters: None

C.3.109 parallel recovery read buffer free

The parallel recovery coordinator is waiting for a log read buffer to be released by all recovery workers. Only after every recovery worker finishes applying redo from a log read buffer, can the buffer be used by the coordinator to issue the next log read.

Wait Time: 100ms

Parameters: None

C.3.110 parallel recovery slave next change

A parallel recovery worker is idle and waiting for the next change message from the coordinator.

Wait Time: 100ms

Parameters: None

C.3.111 pending global transaction(s)

This event should happen only during testing. The session waits for pending transactions to clear.

Wait Time: 30 seconds

Parameter	Description
scans	Number of times the session has scanned the `PENDING_TRANS$` table

C.3.112 pipe get

The session waits for a message to be received on the pipe or for the pipe timer to expire.

Wait Time: There is a 5 second wake up (check) and the pipe timer set by the user

Parameter	Description
handle address	The library cache object handle for this pipe
buffer length	The length of the buffer
timeout	The pipe timer set by the user

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this wait event

C.3.113 pipe put

The session waits for the pipe send timer to expire or for space to be made available in the pipe.

Wait Time: There is the 5 second wakeup (check) and the user-supplied timeout value

Parameter	Description
handle address	The library cache object handle for this pipe
record length	The length of the record or buffer that has been put into the pipe
timeout	The pipe timer set by the user

C.3.114 PL/SQL lock timer

This event is called through the `DBMS_LOCK.SLEEP` procedure. This event will most likely originate from procedures written by a user.

Wait Time: The wait time is in hundredths of seconds and depends on the user context

Parameter	Description
duration	The duration that the user specified in the `DBMS_LOCK.SLEEP` procedure

C.3.115 pmon timer

This is the main wait event for PMON. When PMON is idle, it is waiting on this event.

Wait Time: Up to 3 seconds, if not posted before

Parameter	Description
duration	The actual amount of time that the PMON is trying to sleep

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this wait event

C.3.116 prior spawner clean up

When a prior process has died while spawning a background, the current process which is trying to spawn new a background must wait until the prior process state is cleaned up.

Wait Time: Usually 3 - 10 seconds

Parameter	Description
process_pid	process identifier (see `V$PROCESS.PID`) of the process whose state must be cleaned up.
process_sno	process serial number (see `V$PROCESS.SERIAL#`) of the process whose state must be cleaned up.

C.3.117 process startup

Wait for a shared server, Dispatcher, or other background process to start.

Wait Time: Wait up to 1 second for a background process to start. If timed out, then re-wait until 5 minutes have passed and signal an error. If the process has started, the event will acknowledge this.

Parameter	Description
type	The process type that was started
process#	The process number of the process being started
waited	Cumulative time waited for the process to start

C.3.118 PX Deque wait

The process is waiting for a message during a parallel execute.

Wait Time: The wait time depends on how quickly the message arrives. Wait times can vary, but it will normally be a short period of time.

Parameter	Description
reason	The reason for dequeuing
sleeptime	The amount of time that the session slept
loop	The total number of times that the session has slept

C.3.119 PX qref latch

Each parallel execution process has a parallel execution qref latch, which must be acquired before the queue buffers can be manipulated.

Wait Time: Wait up to 1 second

Parameter	Description
function	Indicates the type of wait that the session is doing
sleeptime	The amount of time that the session waits (in hundredths of a second)
qref	The address of the process queue for which the session is waiting

C.3.120 PX server shutdown

During normal or immediate shutdown the parallel execution servers are posted to shutdown cleanly. If any parallel execution servers are still running after 10 seconds, they are terminated.

Wait Time: Wait up to 0.5 seconds

Parameter	Description
nalive	The number of parallel execution servers that are still running
sleeptime	The total sleeptime since the session started to wait on this event
loop	The number of times the session waited for this event

C.3.121 PX signal server

This event occurs only in Exclusive mode. The query coordinator is signaling the Query Workers that an error has occurred.

Wait Time: 0.5 seconds

Parameter	Description
serial	The serial number of the worker process queue
error	The error that has occurred
nbusy	The number of worker processes that are still busy

C.3.122 rdbms ipc message

The background processes (LGWR, DBWR, LMS0) use this event to indicate that they are idle and are waiting for the foreground processes to send them an IPC message to do some work.

Wait Time: Up to 3 seconds. The parameter *timeout* shows the true sleep time.

Parameter	Description
timeout	The amount of time that the session waits for an IPC message

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this wait event

C.3.123 rdbms ipc message block

This event indicates that all message blocks are in use and that the session had to wait for a message block to become available.

Wait Time: Wait up to 60 seconds

Parameters: None

C.3.124 rdbms ipc reply

This event is used to wait for a reply from one of the background processes.

Wait Time: The wait time is specified by the user and is indicated by the parameter *timeout*.

Parameter	Description
from_process	The background process for which the session is waiting. The wait is for a reply to an IPC message sent by the session.
timeout	The amount of time in seconds that this process will wait for a reply

C.3.125 read by other session

This event occurs when a session requests a buffer that is currently being read into the buffer cache by another session. Prior to release 10.1, waits for this event were grouped with the other reasons for waiting for buffers under the 'buffer busy waits' event.

Wait Time: Time waited for the buffer to be read by the other session (in microseconds)

Parameter	Description
file#	See "file#"
block#	See "block#"
class#	See "class"

C.3.126 recovery active instance mapping setup

This event is used to track the time taken (in centiseconds) to set up recovery context on remote instances.

C.3.127 recovery apply pending

This event tracks the time the logmerger process waited (in centiseconds) for apply workers to apply all pending changes up to a certain SCN.

C.3.128 recovery cancel

This wait event is used to track the time taken (in centiseconds) to cancel multi instance media recovery.

C.3.129 recovery checkpoint

This wait event tracks the time (in centiseconds) spent waiting for DBWR processes on all instances to write dirty buffers to disk up to a certain SCN.

C.3.130 recovery file header update for checkpoint

This wait event tracks the time (in centiseconds) spent by MRP0 process waiting on logmerger to update file headers to record the latest checkpoint.

C.3.131 recovery file header update for fuzziness

This wait event tracks the time taken (in centiseconds) to update file headers to record media recovery fuzziness.

C.3.132 recovery marker apply

This wait event is used to track the time (in centiseconds) taken to process a recovery marker.

C.3.133 recovery merge pending

This wait event is used to track the time spent (in centiseconds) by the MRP0 process waiting for remote logmergers to merge changes up to a certain SCN.

C.3.134 recovery metadata latch

This wait event tracks the time taken (in centiseconds) to get the active DataGuard metadata update latch to advance a query SCN.

C.3.135 recovery move influx buffers

This wait event is used to track the time spent (in centiseconds) waiting for all apply workers to move their influx buffers to the dirty queue.

C.3.136 recovery read

A parallel recovery worker (or serial recovery process) is waiting for a batch of data block reads to complete.

Wait Time: Time it takes to complete the physical I/O (read)

Parameters: None

C.3.137 recovery receive buffer free

This wait event is used to track the time (in centiseconds) spent by the receiver process on instance waiting for apply workers to apply changes from received buffers so that they can be freed for the next change.

C.3.138 recovery remote file verification

This wait event tracks the time spent (in centiseconds) by the MRP0 process waiting for remote logmergers to finish file verification on remote instances.

C.3.139 recovery send buffer free

This wait event is used to track the time spent (in centiseconds) by the sender process waiting for apply workers to apply changes from the local instance so that the buffer can be reused for new changes.

C.3.140 recovery shutdown

This wait event is used to track the time (in centiseconds) taken for remote logmergers to shut down.

C.3.141 Redo Transport Attach

Used to track the time spent (in centiseconds) doing Connect, Logon, and RFSATTACH for *any* network process.

> **See Also:**
>
> *Oracle Data Guard Concepts and Administration* for more information about using RFS to manage standby redo logs.

C.3.142 Redo Transport Close

Used to track the time spent (in centiseconds) by ARC*n*, NSS*n*, and TT*nn* processes doing RFSCLOSE and RFSRGSTR operations.

> **See Also:**
>
> *Oracle Data Guard Concepts and Administration* for more information about using RFS to manage standby redo logs.

C.3.143 Redo Transport Detach

Used to track the time spent (in centiseconds) doing RFSDETACH and Disconnect for *any* network process.

> **See Also:**
>
> *Oracle Data Guard Concepts and Administration* for more information about using RFS to manage standby redo logs.

C.3.144 Redo Transport Open

Used to track the time spent (in centiseconds) by ARC*n*, NSS*n*, and TT*nn* background processes doing RFSCREAT and RFSANNCE operations.

> **See Also:**
>
> *Oracle Data Guard Concepts and Administration* for more information about using RFS to manage standby redo logs.

C.3.145 Redo Transport Ping

Used to track the time spent (in centiseconds) by ARC*n* background processes doing RFSPING operations.

> **See Also:**
>
> *Oracle Data Guard Concepts and Administration* for more information about using RFS to manage standby redo logs.

C.3.146 Redo Transport Slave Startup

Used to track the time spent (in centiseconds) by LGWR doing NSS*n* and TT*nn* process startup and initialization.

C.3.147 Redo Writer Remote Sync Complete

Used to track the time spent (in centiseconds) by LGWR reaping completed network writes to remote destinations.

C.3.148 Redo Writer Remote Sync Notify

Used to track the time spent (in centiseconds) by LGWR issuing network writes to remote destinations.

C.3.149 resmgr:become active

The session is waiting for a resource manager active session slot. This event occurs when the resource manager is enabled and the number of active sessions in the session's current consumer group exceeds the current resource plan's active session limit for the consumer group. To reduce the occurrence of this wait event, increase the active session limit for the session's current consumer group.

Wait Time: The time the session waited to be allocated an active session slot

Parameter	Description
location	location of the wait

C.3.150 resmgr:cpu quantum

The session is waiting to be allocated a quantum of CPU. This event occurs when the resource manager is enabled and is throttling CPU consumption. To reduce the occurrence of this wait event, increase the CPU allocation for the sessions's current consumer group.

Wait Time: The time the session waited to acquire a CPU quantum

Parameter	Description
location	Location of the wait
Consumer Group ID	Consumer group ID of the session waiting. This value is from the `CONSUMER_GROUP_ID` column in the `DBA_RSRC_CONSUMER_GROUPS` view.

See Also:

"DBA_RSRC_CONSUMER_GROUPS"

C.3.151 resmgr: I/O rate limit

The session is waiting for I/O bandwidth to be available to issue I/Os. This event occurs when PDB I/O rate limits are enabled by setting the `MAX_IOPS` and/or `MAX_MBPS` parameters.

To reduce the occurrence of this wait event, the PDB I/O rate limit values need to be increased. This can be achieved by increasing the values of `MAX_IOPS` and `MAX_MBPS` or by removing the limits altogether by setting the parameter value to 0.

Wait Time: The time the session waited for the I/O bandwidth to become available.

Parameter	Description
P1: PDB_ID	This the PDB ID of the PDB that has its I/O throttled because the `MAX_IOPS` or `MAX_MBPS` parameter was set for it.

See Also:

- "MAX_IOPS"
- "MAX_MBPS"

C.3.152 resmgr:pq queued

The session is waiting in the parallel statement queue.

Wait Time: The time the session waited for sufficient parallel query processes to become available to run this session with the requested degree of parallelism

Parameter	Description
location	Location of the wait

See Also:

Oracle Database VLDB and Partitioning Guide for more information about this wait event

C.3.153 rolling migration: cluster quiesce

This is the wait event that instances wait on when cluster is about to start a rolling migration. The instances are waiting for any privileged operations that blocks rolling migration to complete before allowing rolling migration.

Wait Time: 1 second

Parameter	Description
location	Its value will be 1 if the wait is for completion of the privileged operations so that a rolling upgrade/downgrade can start. Its value will be 2 if the wait is for completion of the rolling upgrade/downgrade on all the nodes in the cluster.
waits	The number of seconds spent waiting at the current location.

C.3.154 row cache lock

The session is trying to get a data dictionary lock.

Wait Time: Wait up to 60 seconds.

Parameter	Description
cache id	The `CACHE#` column value in the `V$ROWCACHE` view
mode	See "mode"
request	The pipe timer set by the user

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this wait event

C.3.155 RVWR wait for flashback copy

Waits for a process to copy flashback database data into the flashback buffer, in order to write out the requested flashback data.

Wait Time: 10 milliseconds

Parameter	Description
copy latch #	The number of flashback copy latch RVWR is waiting on

C.3.156 sbtbufinfo

This function is called when Oracle needs to discover the size, and number, of I/O buffers that have been allocated by the SBT layer. It should be very fast and never block.

Wait Time: Less than one millisecond

Parameters: None

C.3.157 sbtgetbuf

This function obtains one I/O buffer that Oracle will use for I/O during a backup job.

Wait Time: Less than one millisecond

Parameters: None

C.3.158 sbtmapbuf

This is an internal function used to facilitate multi-process buffer management. It should be very fast and never block.

Wait Time: Less than one millisecond

Parameters: None

C.3.159 sbtrelbuf

This function releases an I/O buffer that has been already processed during a restore job, so that the SBT layer can fill it with more data. It should be very fast and never block.

Wait Time: Less than one millisecond

Parameters: None

C.3.160 scginq AST call

Called by the session to find the highest lock mode that is held on a resource.

Wait Time: Wait up to 0.2 seconds, but the wait will continue until the NULL mode Acquisition AST has fired.

Parameters: None

C.3.161 SGA: allocation forcing component growth

Process waiting on an immediate mode memory transfer with auto-tune SGA after a 4031 for MMAN to get the memory and post it.

Wait Time: 10 msec

Parameters: None

C.3.162 SGA: MMAN sleep for component shrink

MMAN to wait and post itself for satisfying an auto-tuned memory request while trying to fully free a component's quiesced granules. In Release 10.1, the name of this event was 'wait for SGA component shrink'.

Wait Time: 10 msec

Parameter	Description
P1	component_id (corresponding to the memory pool)
P2	Current size in granules
P3	Target size in granules

C.3.163 SGA: sga_target resize

Memory resize requests wait while sga target is being resized. In Release 10.1, the name of this event was 'wait for sga_target resize'.

Wait Time: 10 msec

Parameters: None

C.3.164 Shared IO Pool Memory

Wait until a shared I/O pool buffer becomes available. This happens when processes are using these buffers for I/O and the current process needs to wait for the release of any one of the buffers to the shared I/O pool.

Wait Time: 10msec

Parameters: None

C.3.165 shared server idle wait

Idle wait event for a shared server.

The server waits on the common queue for a virtual circuit. (See also "virtual circuit wait".)

Wait Time: 30 seconds

Parameters: None

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this wait event

C.3.166 single-task message

When running single task, this event indicates that the session waits for the client side of the executable.

Wait Time: Total elapsed time that this session spent in the user application

Parameters: None

C.3.167 smon timer

This is the main idle event for SMON. SMON will be waiting on this event most of the time until it times out or is posted by another process.

Wait Time: 5 minutes (300 seconds)

Parameter	Description
sleeptime	The amount of time that SMON tries to wait on this event in seconds
failed	The number of times SMON was posted when there some kind of error

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this wait event

C.3.168 SQL*Net break/reset to client

The server sends a break or reset message to the client. The session running on the server waits for a reply from the client.

Wait Time: The actual time it takes for the break or reset message to return from the client

Parameter	Description
driver id	See "driver id"
break?	See "break?"

C.3.169 SQL*Net break/reset to dblink

Same as **SQL*Net break/reset to client**, but in this case, the break/reset message is sent to another server process over a database link.

Wait Time: The actual time it takes for the break or reset message to return from the other server process

Parameter	Description
driver id	See "driver id"
break?	See "break?"

C.3.170 SQL*Net message from client

The server process (foreground process) waits for a message from the client process to arrive.

Wait Time: The time it took for a message to arrive from the client since the last message was sent to the client

Parameter	Description
driver id	See "driver id"
#bytes	The number of bytes received by the server (foreground process) from the client.

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this wait event

C.3.171 SQL*Net message from dblink

The session waits while the server process (foreground process) receives messages over a database link from another server process.

Wait Time: The time it took for a message to arrive from another server (foreground process) since a message was sent to the other foreground process.

Parameter	Description
driver id	See "driver id"
#bytes	The number of bytes received by the server (foreground process) from another foreground process over a database link.

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this wait event

C.3.172 SQL*Net message to client

The server (foreground process) is sending a message to the client.

Wait Time: The actual time the **send** takes

Parameter	Description
driver id	See "driver id"
#bytes	The number of bytes sent by the server process to the client

C.3.173 SQL*Net message to dblink

The server process (foreground process) is sending a message over a database link to another server process.

Wait Time: The actual time the **send** takes

Parameter	Description
driver id	See "driver id"
#bytes	The number of bytes sent by the server process to another server process over a database link

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this wait event

C.3.174 SQL*Net more data from client

The server is waiting on the client to send more data to its client shadow process, in an already initiated operation.

Wait Time: The time waited depends on the time it took to receive the data (including the waiting time)

Parameter	Description
driver id	See "driver id"
#bytes	The number of bytes received from the client

C.3.175 SQL*Net more data from dblink

The foreground process is expecting more data from a data base link.

Wait Time: The total time it takes to read the data from the database link (including the waiting time for the data to arrive)

Parameter	Description
driver id	See "driver id"
#bytes	The number of bytes received

C.3.176 SQL*Net more data to client

The server process is sending more data/messages to the client. The previous operation to the client was also a **send**.

Wait Time: The actual time it took for the **send** to complete

Parameter	Description
driver id	See "driver id"
#bytes	The number of bytes that are being sent to the client

> **See Also:**
>
> *Oracle Database Performance Tuning Guide* for more information about this wait event

C.3.177 SQL*Net more data to dblink

The event indicates that the server is sending data over a database link again. The previous operation over this database link was also a **send**.

Wait Time: The actual time it takes to send the data to the other server

Parameter	Description
driver id	See "driver id"
#bytes	The number of bytes that are sent over the database link to the other server process

C.3.178 Streams AQ: waiting for messages in the queue

The session is waiting on an empty OLTP queue (Advanced Queuing) for a message to arrive so that the session can dequeue that message.

Wait Time: The amount of time that the session wants to wait is determined by the parameter *wait time*

Parameter	Description
queue id	The ID of the OLTP queue for which this session is waiting
process#	The process number of the process in which this session runs
wait time	The intended wait time for this session

C.3.179 switch logfile command

The session waits on the user command `SWITCH LOGFILE` to complete.

Wait Time: 5 seconds

Parameters: None

C.3.180 SYNC Remote Write

Used to track the time spent by LGWR doing SYNC RFSWRITE operations.

> **See Also:**
>
> *Oracle Data Guard Concepts and Administration* for more information about using RFS to manage standby redo logs.

C.3.181 TCP Socket (KGAS)

A session is waiting for an external host to provide requested data over a network socket. The time that this wait event tracks does not indicate a problem, and even a long wait time is not a reason to contact Oracle Support. It naturally takes time for data to flow between hosts

over a network, and for the remote aspect of an application to process any request made to it.

An application that communicates with a remote host must wait until the data it will read has arrived. In addition, on Microsoft Windows, a separate thread monitors the arrival of traffic. This thread spends most of its life in waits tracked by the TCP Socket (KGAS) wait event.

Wait Time: The total elapsed time for the network connection to be established or for data to arrive from over the network

Parameter	Description
P0	For Oracle internal use only. Values 8, 9, and 10 occur within the special thread present on Microsoft Windows; other P0 values occur in normal user sessions.
P1	For Oracle internal use only

C.3.182 timer in sksawat

The session waits for the Archiver (ARC*n*) asynchronous I/O to complete.

Wait Time: 0.01 seconds

Parameters: None

C.3.183 transaction

Wait for a blocking transaction to be rolled back. Continue waiting until the transaction has been rolled back.

Wait Time: 1 second

Parameter	Description
undo seg#	The rollback segment ID
slot#	The slot ID inside the rollback segment
wrap#	The sequence number that is incremented for each transaction
count	The number of times that the session has waited on this transaction

C.3.184 unbound tx

The session waits to see if there are any transactions that have been started but do not have a Rollback Segment associated with them.

Wait Time: 1 second

Parameters: None

C.3.185 undo_retention publish retry

This wait can occur for two reasons. A session issuing an `ALTER SYSTEM SET UNDO_RETENTION` may wait on this event wait while a cluster reconfiguration takes

place. Or the background process MMNL may wait for cluster reconfiguration while attempting to determine the max `UNDO_RETENTION`.

Wait time: 1 second

Parameter	Description
P1	Identifies where the retry is happening. Id = 1 retry while publishing into the max undo_retention namespace. Id = 2 retry while iterator accessing the max undo_retention namespace.
P2	Retry count (maximum number of retries is 5)

C.3.186 undo segment extension

The undo segment is being extended or shrunk. The session must wait until the operation on the undo segment has finished.

Wait Time: 0.01 seconds

Parameter	Description
segment#	The ID of the rollback segment that is being extended or shrunk

C.3.187 undo segment recovery

PMON is rolling back a terminated transaction. The wait continues until rollback finishes.

Wait Time: 3 seconds

Parameter	Description
segment#	The ID of the rollback segment that contains the transaction that is being rolled back
tx flags	The transaction flags (options) set for the transaction that is being rolled back

C.3.188 undo segment tx slot

Wait for a transaction slot to become available within the selected rollback segment. Continue waiting until the slot is available.

Wait Time: 1 second

Parameter	Description
segment#	The ID of the rollback segment that contains the transaction that is being rolled back

C.3.189 utl_file I/O

Waits associated with operations performed using the `UTL_FILE` package.

C.3.190 virtual circuit wait

The session waits for a virtual circuit operation to complete.

Wait Time: 30 seconds

Parameter	Description
circuit#	Indicates the virtual circuit# being waited on
type	Indicates the type of operation the session is waiting for

C.3.191 WCR: replay client notify

During replay, the Workload Replay Client always keeps an open connection to the database to detect some special errors. This session will normally be in the wait state until some specific replay-related exception occurs.

Wait Time: Waits until notified. Times out every 30 seconds.

Parameter	Description
who am I	Identifies the reason for wait for the admin thread. 1 - waiting for REPLAY.START() to be issued. 2 - waiting for the replay to run to completion or REPLAY.CANCEL() to be issued.

C.3.192 WCR: replay clock

A session will wait on this event during replay if it has some logical dependencies on another session that has not yet committed its work.

Wait Time: Depends upon the amount of row lock contention in the original capture

Parameter	Description
wait for scn's hi 4 bytes	High 4 bytes of the 8-byte replay SCN that the session is waiting on
wait for scn's lo 4 bytes	Low 4 bytes of the 8-byte replay SCN that the session is waiting on

C.3.193 WCR: replay lock order

A session will wait on this event during replay if it saw some lock contention during capture.

Wait Time: Depends upon the amount of row lock contention in the original capture

Parameter	Description
wait for scn's hi 4 bytes	High 4 bytes of the 8-byte replay SCN that the session is waiting on

Parameter	Description
wait for scn's lo 4 bytes	Low 4 bytes of the 8-byte replay SCN that the session is waiting on

C.3.194 WCR: replay paused

When the user issues a DBMS_WORKLOAD_REPLAY.PAUSE_REPLAY command, all the replayed sessions are waiting on this wait event until replay is resumed.

Parameters: None

C.3.195 WCR: Sync context busy

In the default replay mode, commits during replay are synchronized to follow the same order as capture. All commits are serialized using the Sync context. A replayed session will wait on this event if it is trying to commit at the same time as another replayed session.

Parameters: None

C.3.196 write complete waits

The session waits for a buffer to be written. The write is caused by normal aging or by a cross-instance call.

Wait Time: 1 second

Parameter	Description
file#	The rollback segment id that contains the transaction that is being rolled back
block#	The transaction flags (options) set for the transaction that is being rolled back
id	Identifies the reason for waiting

D

Oracle Enqueue Names

This appendix lists Oracle enqueues. **Enqueues** are shared memory structures (locks) that serialize access to database resources. They can be associated with a session or transaction. Enqueue names are displayed in the `LOCK_TYPE` column of the `DBA_LOCK` and `DBA_LOCK_INTERNAL` data dictionary views.
A **resource** uniquely identifies an object that can be locked by different sessions within an instance (local resource) or between instances (global resource). Each session that tries to lock the resource will have an **enqueue** on the resource.

> **Note:**
>
> The names of enqueues and their definitions may change from release to release.

> **See Also:**
>
> "DBA_LOCK_INTERNAL" and "DBA_LOCK"

The Oracle enqueues are:

- BL, Buffer Cache Management
- BR, Backup/Restore
- CF, Controlfile Transaction
- CI, Cross-instance Call Invocation
- CU, Bind Enqueue
- DF, Datafile
- DL, Direct Loader Index Creation
- DM, Database Mount
- DR, Distributed Recovery Process
- DW, SecureFiles
- DX, Distributed Transaction
- FP, File Object
- FS, File Set
- HW, High-Water Lock
- IN, Instance Number
- IR, Instance Recovery
- IS, Instance State

- IV, Library Cache Invalidation
- JI, Enqueue used during AJV snapshot refresh
- JQ, Job Queue
- KK, Redo Log "Kick"
- KP, contention in Oracle Data Pump startup and shutdown processes
- KO, Multiple Object Checkpoint
- L[A-P], Library Cache Lock
- LS, Log Start or Switch
- MM, Mount Definition
- MR, Media Recovery
- N[A-Z], Library Cache Pin
- PE, ALTER SYSTEM SET PARAMETER = VALUE
- PF, Password File
- PI, Parallel Slaves
- PR, Process Startup
- PS, Parallel Slave Synchronization
- Q[A-Z], Row Cache
- RO, Object Reuse
- RT, Redo Thread
- RW, Row Wait
- SC, System Change Number
- SM, SMON
- SN, Sequence Number
- SQ, Sequence Number Enqueue
- SR, Synchronized Replication
- SS, Sort Segment
- ST, Space Management Transaction
- SV, Sequence Number Value
- TA, Transaction Recovery
- TC, Thread Checkpoint
- TE, Extend Table
- TM, DML Enqueue
- TO, Temporary Table Object Enqueue
- TS, Temporary Segment (also TableSpace)
- TT, Temporary Table
- TX, Transaction
- UL, User-defined Locks

- UN, User Name
- US, Undo Segment, Serialization
- WL, Being Written Redo Log
- XA, Instance Attribute Lock
- XI, Instance Registration Lock
- ZA, Exclusive Lock When Moving Audit Table

E

Statistics Descriptions

This appendix describes the statistics stored in the `V$SESSTAT` and `V$SYSSTAT` dynamic performance tables. These statistics are useful in identifying and correcting performance problems.

This appendix contains the following topics:

- Displaying Statistics
- Statistics Descriptions

E.1 Displaying Statistics

The `V$SESSTAT` view displays statistics on a per-session basis and is valid only for the session currently connected. When a session disconnects, all statistics for the session are updated in `V$SYSSTAT`. The values for the statistics are cleared until the next session uses them.
The `V$STATNAME` view contains all of the statistics for an Oracle release.

Many of these statistics are tied to the internal implementation of Oracle and therefore are subject to change or deletion without notice, even between patch releases. Application developers should be aware of this and write their code to tolerate missing or extra statistics.

> **See Also:**
>
> "V$SESSTAT", "V$STATNAME", and "V$SYSSTAT" for more information on these views

E.2 Statistics Descriptions

This section describes some of the statistics stored in the `V$SESSTAT` and `V$SYSSTAT` views.

The statistics are listed in alphabetical order.

The `CLASS` column contains a number representing one or more statistics classes. The following class numbers are additive:

- 1, User
- 2, Redo
- 4, Enqueue
- 8, Cache
- 16, OS
- 32, Real Application Clusters
- 64, SQL

- 128, Debug
- 256, Instance level

For example, a class value of 72 represents a statistic that relates to SQL statements and caching.

Some statistics are populated only if the `TIMED_STATISTICS` initialization parameter is set to `true`. Those statistics are flagged with a `Y` in the right-hand column.

Table E-1 Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
application wait time	1	The total wait time (in centiseconds) for waits that belong to the Application wait class	
background checkpoints completed	8	Number of checkpoints completed by the background process. This statistic is incremented when the background process successfully advances the thread checkpoint.	
background checkpoints started	8	Number of checkpoints started by the background process. This statistic can be larger than "background checkpoints completed" if a new checkpoint overrides an incomplete checkpoint or if a checkpoint is currently under way. This statistic includes only checkpoints of the redo thread. It does not include: • Individual file checkpoints for operations such as offline or begin backup • Foreground (user-requested) checkpoints (for example, performed by `ALTER SYSTEM CHECKPOINT LOCAL` statements)	
background timeouts	128	This is a count of the times where a background process has set an alarm for itself and the alarm has timed out rather than the background process being posted by another process to do some work.	
branch node splits	128	Number of times an index branch block was split because of the insertion of an additional value	
buffer is not pinned count	72	Number of times a buffer was free when visited. Useful only for internal debugging purposes.	
buffer is pinned count	72	Number of times a buffer was pinned when visited. Useful only for internal debugging purposes.	
bytes received via SQL*Net from client	1	Total number of bytes received from the client over Oracle Net Services	
bytes received via SQL*Net from dblink	1	Total number of bytes received from a database link over Oracle Net Services	
bytes sent via SQL*Net to client	1	Total number of bytes sent to the client from the foreground processes	
bytes sent via SQL*Net to dblink	1	Total number of bytes sent over a database link	
Cached Commit SCN referenced	128	Useful only for internal debugging purposes	
calls to get snapshot scn: kcmgss	32	Number of times a snapshot system change number (SCN) was allocated. The SCN is allocated at the start of a transaction.	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
calls to kcmgas	128	Number of calls to routine kcmgas to get a new SCN	
calls to kcmgcs	128	Number of calls to routine kcmgcs to get a current SCN	
calls to kcmgrs	128	Number of calls to routine kcsgrs to get a recent SCN	
cell flash cache read hits	8	Number of read requests that were satisfied by the cache	
cell flash cache read hits for smart IO	8	Number of read requests for smart IO that were satisfied by the cache	
cell flash cache read hits for temp IO	8	Number of read requests for temp IO that were satisfied by the cache	
cell IO uncompressed bytes	64	Total size of uncompressed data that is processed on the cell For operations on segments compressed using Exadata Hybrid Columnar Compression, this statistic is the size of the data after decompression.	
cell num bytes in passthru due to quarantine	8	Number of bytes that were not offloaded and sent back to the database for processing due to a quarantine on the cell	
cell num bytes in passthru during predicate offload	64	Number of bytes that were not offloaded and sent back to the database for processing	
cell overwrites in flash cache	8	Total number of write requests that overwrote an existing cacheline in Exadata Smart Flash Cache that had not been written to disk In effect, this is the amount of disk I/O saved by using Write-Back mode. This statistic is incremented once per mirror write.	
cell partial writes in flash cache	8	Total number of write requests written to both Exadata Smart Flash Cache and disk Part of the data was written to flash, and the rest was written to disk. This statistic is incremented once per mirror write.	
cell physical IO bytes added to storage index	8	Number of bytes added to the storage index during a Smart Scan This is an indication that the storage index is being built.	
cell physical IO bytes eligible for predicate offload	64	Number of bytes on-disk eligible for predicate offload	
cell physical IO bytes eligible for smart IOs	8	Number of actual bytes eligible for predicate offload For example, when using columnar cache, this is the size of columnar cache instead of the on-disk size.	
cell physical IO bytes processed for IM capacity	64	Number of bytes read from the columnar cache in `memcompress for capacity` format	
cell physical IO bytes processed for IM query	64	Number of bytes read from the columnar cache in `memcompress for query` format	
cell physical IO bytes processed for no memcompress	64	Number of bytes read from the columnar cache in `no memcompress` format	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
cell physical IO bytes saved by columnar cache	8	Number of bytes saved by columnar cache, that is, the number of bytes of reading that were avoided	
cell physical IO bytes saved by storage index	8	Number of bytes saved by the storage index	
cell physical IO bytes saved during optimized file creation	64	Number of I/O bytes saved by the database host by offloading the file creation operation to the cells This statistic shows the benefit of optimized file creation operations.	
cell physical IO bytes saved during optimized RMAN file restore	64	Number of I/O bytes saved by the database host by offloading the RMAN file restore operation to the cells This statistic shows the benefit of optimized RMAN file restore operations.	
cell physical IO bytes sent directly to DB node to balance CPU	64	Number of I/O bytes sent back to the database server for processing due to high storage server CPU usage	
cell physical IO interconnect bytes	64	Number of I/O bytes exchanged over the interconnect between the database host and the cells	
cell physical IO interconnect bytes returned by smart scan	64	Number of I/O bytes that are returned by the cell for Smart Scan operations This value does not include bytes for other database I/O.	
cell pmem cache read hits	8	Number of non-RDMA read requests processed by `cellsrv` resulting in a PMEM cache hit	
cell pmem cache writes	264	Number of non-RDMA write requests processed by `cellsrv` resulting in a PMEM cache write	
cell pmem log writes	258	Number of redo log write requests that used PMEM log	
cell ram cache read hits	8	Number of read requests that hit the RAM cache on the cell	
cell RDMA reads	8	Number of PMEM cache read requests using RDMA	
cell RDMA writes	264	Number of PMEM cache write requests using RDMA	
cell writes to flash cache	8	Total number of write requests written entirely to Exadata Smart Flash Cache This statistic is incremented once per mirror write.	
cell writes to flash cache for temp IO	8	Number of write requests for temporary segments that were absorbed by Exadata Smart Flash Cache	
change write time	8	Elapsed redo write time for changes made to `CURRENT` blocks in 10s of milliseconds.	Y
cleanouts and rollbacks - consistent read gets	128	Number of consistent gets that require both block rollbacks and block cleanouts. **See Also:** "consistent gets"	
cleanouts only - consistent read gets	128	Number of consistent gets that require only block cleanouts, no rollbacks. **See Also:** "consistent gets"	
cluster key scan block gets	64	Number of blocks obtained in a cluster scan	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
cluster key scans	64	Number of cluster scans that were started	
cluster wait time	1	The total wait time (in centiseconds) for waits that belong to the Cluster wait class	
cold recycle reads	8	Number of buffers that were read through the least recently used end of the recycle cache with fast aging strategy	
commit cleanout failures: block lost	8	Number of times Oracle attempted a cleanout at commit but could not find the correct block due to forced write, replacement, or switch `CURRENT`	
commit cleanout failures: buffer being written	8	Number of times Oracle attempted a cleanout at commit, but the buffer was currently being written	
commit cleanout failures: callback failure	8	Number of times the cleanout callback function returns `FALSE`	
commit cleanout failures: cannot pin	8	Total number of times a commit cleanout was performed but failed because the block could not be pinned	
commit cleanout failures: hot backup in progress	8	Number of times Oracle attempted block cleanout at commit during hot backup. The image of the block must be logged before the buffer can be made dirty.	
commit cleanout failures: pmem only	264	Number of time Oracle attempted a cleanout at commit, but could not modify PMEM buffers directly without a DRAM version	
commit cleanout failures: write disabled	8	Number of times a cleanout block at commit was performed but the writes to the database had been temporarily disabled	
commit cleanouts	8	Total number of times the cleanout block at commit function was performed	
commit cleanouts successfully completed	8	Number of times the cleanout block at commit function completed successfully	
commit nowait performed	1	The number of asynchronous commits that were actually performed. These commits did not wait for the commit redo to be flushed and be present on disk before returning.	
commit nowait requested	1	The number of no-wait commit or asynchronous commit requests that were made either using SQL or the OCI transaction control API	
Commit SCN cached	128	Number of times the system change number of a commit operation was cached	
commit wait/nowait performed	1	The number of asynchronous/synchronous commits that were actually performed	
commit wait/nowait requested	1	The number of no-wait or wait commits that were made either using SQL or the OCI transaction control API	
commit wait performed	1	The number of synchronous commits that were actually performed. These commits waited for the commit redo to be flushed and be present on disk before returning.	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
commit wait requested	1	The number of waiting or synchronous commit requests that were made either using SQL or the OCI transaction control API	
concurrency wait time	1	The total wait time (in centiseconds) for waits that belong to the Concurrency wait class	
consistent changes	8	Number of times a user process has applied rollback entries to perform a consistent read on the block Work loads that produce a great deal of consistent changes can consume a great deal of resources. The value of this statistic should be small in relation to the "consistent gets" statistic.	
consistent gets	8	Number of times a consistent read was requested for a block. **See Also:** "consistent changes" and "session logical reads" statistics	
consistent gets direct	8	Number of times a consistent read was requested for a block bypassing the buffer cache (for example, direct load operation). This is a subset of "consistent gets" statistics value.	
consistent gets from cache	8	Number of times a consistent read was requested for a block from buffer cache. This is a subset of "consistent gets" statistics value.	
consistent gets from pmem	8	Number of direct-mapped blocks accessed in CR (consistent read) mode from PMEM. This is a subset of "consistent gets" statistics value.	
consistent gets pmem direct	8	Number of CR gets from pmem in direct read (e.g. tablescan) code path. This is a subset of "consistent gets from pmem" statistics value.	
consistent gets pmem examination	8	Number of direct-mapped blocks accessed and examined in CR mode from PMEM, via regular path. This is a subset of "consistent gets from pmem" statistics value.	
consistent gets pmem examination (fastpath)	8	Number of direct-mapped blocks accessed and examined in CR mode from PMEM, via fast path. This is a subset of both "consistent gets from pmem" and "consistent gets pmem examination" statistics values.	
consistent gets pmem pin	8	Number of direct-mapped blocks accessed and pinned in CR mode from PMEM, via regular path. This is a subset of "consistent gets from pmem" statistics value.	
consistent gets pmem pin (fastpath)	8	Number of direct-mapped blocks accessed and pinned in CR mode from PMEM, via fast path. This is a subset of both "consistent gets from pmem" and "consistent gets pmem pin" statistics values.	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
CPU used by this session	1	Amount of CPU time (in 10s of milliseconds) used by a session from the time a user call starts until it ends. If a user call completes within 10 milliseconds, the start and end user-call time are the same for purposes of this statistics, and 0 milliseconds are added. A similar problem can exist in the reporting by the operating system, especially on systems that suffer from many context switches.	Y
CPU used when call started	128	The CPU time used when the call is started **See Also:** " CPU used by this session"	Y
CR blocks created	8	Number of `CURRENT` blocks cloned to create CR (consistent read) blocks. The most common reason for cloning is that the buffer is held in a incompatible mode.	
cumulative begin requests	32	Total number of begin requests received by the Oracle database allowing the database to detect and process requests	
cumulative DB time in requests	288	Total database time DB Time (in microseconds) within requests to the Oracle database, measuring DB time used from the beginning to the end of each request. (See also DB time statistic.)	
cumulative DB time protected in requests	288	Total database time DB Time (in microseconds) within requests to the Oracle database protected by Application Continuity or Transparent Application Continuity, measuring DB time used from the beginning to the end of each request. (See also DB time statistic.) This is a subset of "cumulative DB time in requests" value, which enables you to calculate the ratio of total time in requests to protected time in requests. See also Application Continuity Protection Check (ACCHK).	
cumulative end requests	32	Total number of end requests received by the Oracle database allowing the database to detect and process requests	
cumulative time in requests	32	Total wall clock time (in microseconds) within requests to the Oracle database, measuring time spent from the beginning to the end of each request. This statistic is used by draining and planned failover. (See `drain_timeout`.)	
cumulative user calls in requests	32	Total number of user calls received by the Oracle database within requests to the Oracle database	
cumulative user calls protected by Application Continuity	32	Total number of user calls received by the Oracle database within requests to the Oracle database that were protected by Application Continuity or Transparent Application Continuity	
current blocks converted for CR	8	Number `CURRENT` blocks converted to CR state	
cursor authentications	128	Number of privilege checks conducted during execution of an operation	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
data blocks consistent reads - undo records applied	128	Number of undo records applied to data blocks that have been rolled back for consistent read purposes	
data warehousing cooling action	8	Number of times that cooling occurred on this instance	
data warehousing evicted objects	8	Number of times that objects got evicted by automatic big table caching on this instance	
data warehousing evicted objects - cooling	8	Number of times that objects got evicted on this instance due to a cooling action	
data warehousing evicted objects - replace	8	Number of times that objects got evicted due to caching replacement, that is, when an object is evicted because a hotter object forces it to be evicted from the cache	
data warehousing scanned blocks	8	Number of blocks scanned by automatic big table caching on this instance using parallel query	
data warehousing scanned blocks - disk	8	Number of blocks scanned by automatic big table caching on this instance by direct read from disk	
data warehousing scanned blocks - memory	8	Number of blocks scanned by automatic big table caching on this instance by cache read from memory	
data warehousing scanned blocks - offload	8	Number of blocks scanned by automatic big table caching on this instance by Exadata offloading	
data warehousing scanned objects	8	Number of times the objects in automatic big table caching are scanned using parallel query	
db block changes	8	Closely related to "consistent changes", this statistic counts the total number of changes that were part of an update or delete operation that were made to all blocks in the SGA. Such changes generate redo log entries and hence become permanent changes to the database if the transaction is committed. This approximates total database work. This statistic indicates the rate at which buffers are being dirtied (on a per-transaction or per-second basis, for example).	
db block gets	8	Number of times a `CURRENT` block was requested **See Also:** "consistent gets"	
db block gets direct	8	Number of times a `CURRENT` block was requested bypassing the buffer cache (for example, a direct load operation). This is a subset of "db block gets" statistics value.	
db block gets from cache	8	Number of times a `CURRENT` block was requested from the buffer cache. This is a subset of "db block gets" statistics value.	
db block gets from pmem	8	Number of direct-mapped blocks accessed in CURRENT mode from PMEM, via regular path	
db block gets from pmem (fastpath)	8	Number of direct-mapped blocks accessed in CURRENT mode from PMEM, via fast path	
DBWR checkpoint buffers written	8	Number of buffers that were written for checkpoints	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
DBWR checkpoints	8	Number of times the DBWR was asked to scan the cache and write all blocks marked for a checkpoint or the end of recovery. This statistic is always larger than "background checkpoints completed".	
DBWR lru scans	8	Number of times that DBWR scans the LRU queue looking for buffers to write. This count includes scans to fill a batch being written for another purpose (such as a checkpoint).	
DBWR revisited being-written buffer	8	Number of times that DBWR tried to save a buffer for writing and found that it was already in the write batch. This statistic measures the amount of "useless" work that DBWR had to do in trying to fill the batch. Many sources contribute to a write batch. If the same buffer from different sources is considered for adding to the write batch, then all but the first attempt will be "useless" because the buffer is already marked as being written.	
DBWR transaction table writes	8	Number of rollback segment headers written by DBWR. This statistic indicates how many "hot" buffers were written, causing a user process to wait while the write completed.	
DBWR undo block writes	8	Number of rollback segment blocks written by DBWR	
DDL statements parallelized	32	Number of DDL statements that were executed in parallel	
deferred (CURRENT) block cleanout applications	128	Number of times cleanout records are deferred, piggyback with changes, always current get	
DFO trees parallelized	32	Number of times a serial execution plan was converted to a parallel plan	
dirty buffers inspected	8	Number of dirty buffers found by the user process while it is looking for a buffer to reuse	
DML statements parallelized	32	Number of DML statements that were executed in parallel	
DML statements retried	64	When a long-running DML is executing, the cursor may get invalidated due to some concurrent DDL on one of the cursor's dependencies. In this case, an internal ORA-14403 error is thrown and is caught and cleared in one of the calling functions. The current work is rolled back and the DML is restarted without the user being notified of this. The statistic counts the number of times that the thrown, caught, and cleared (ORA-14403) sequence occurred for DML statements. Should a DML vary widely in execution time, check this statistic to see if it increments during the DML execution. If so, then concurrent DDL may be the cause of the extra elapsed time.	
enqueue conversions	4	Total number of conversions of the state of table or row lock	
enqueue deadlocks	4	Total number of deadlocks between table or row locks in different sessions	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
enqueue releases	4	Total number of table or row locks released	
enqueue requests	4	Total number of table or row locks acquired	
enqueue timeouts	4	Total number of table and row locks (acquired and converted) that timed out before they could complete	
enqueue waits	4	Total number of waits that occurred during an enqueue convert or get because the enqueue get was deferred	
exchange deadlocks	8	Number of times that a process detected a potential deadlock when exchanging two buffers and raised an internal, restartable error. Index scans are the only operations that perform exchanges.	
execute count	64	Total number of calls (user and recursive) that executed SQL statements	
fbda woken up	128	Number of times the flashback data archive background process was woken up to do archiving	
file io wait time	1	Total time spent in wait (in microseconds) for I/O to datafiles, excluding the service time for such I/O. This is cumulative for all I/Os for all datafiles. The service time for one I/O operation is estimated as the minimum time spent in the I/O call seen so far. This service time is subtracted from the time spent in each I/O call to get the wait time for that I/O.	
flash cache eviction: aged out	8	Flash cache buffer is aged out of the Database Smart Flash Cache	
flash cache eviction: buffer pinned	8	Database Smart Flash Cache buffer is invalidated due to object or range reuse, and so on. The Database Flash Cache Buffer was in use at the time of eviction.	
flash cache eviction: invalidated	8	Database Smart Flash Cache buffer is invalidated due to object or range reuse, and so on. The Database Smart Flash Cache buffer was not in use at the time of eviction.	
flash cache insert skip: corrupt	8	In-memory buffer was skipped for insertion into the Database Smart Flash Cache because the buffer was corrupted	
flash cache insert skip: DBWR overloaded	8	In-memory buffer was skipped for insertion into the Database Smart Flash Cache because DBWR was busy writing other buffers	
flash cache insert skip: exists	8	In-memory buffer was skipped for insertion into the Database Smart Flash Cache because it was already in the flash cache	
flash cache insert skip: modification	8	In-memory buffer was skipped for insertion into the Database Smart Flash Cache because it was being modified	
flash cache insert skip: not current	8	In-memory buffer was skipped for insertion into the Database Smart Flash Cache because it was not current	
flash cache insert skip: not useful	8	In-memory buffer was skipped for insertion into the Database Smart Flash Cache because the type of buffer was not useful to keep	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
flash cache inserts	8	Total number of in-memory buffers inserted into the Database Smart Flash Cache	
flashback log write bytes	2	Total size in bytes of flashback database data written by RVWR to flashback database logs	
flashback log writes	2	Total number of writes by RVWR to flashback database logs	
foreground propagated tracked transactions	128	Number of transactions modifying tables enabled for flashback data archive which were archived by a foreground process	
free buffer inspected	8	Number of buffers skipped over from the end of an LRU queue to find a reusable buffer. The difference between this statistic and "dirty buffers inspected" is the number of buffers that could not be used because they had a user, a waiter, or were being read or written, or because they were busy or needed to be written after rapid aging out.	
free buffer inspected for pmem	8	Number of PMEM buffers skipped over from the end of an LRU queue to find a reusable PMEM buffer	
free buffer requested	8	Number of times a reusable buffer or a free buffer was requested to create or load a block	
free buffer requested for pmem	8	Number of times a reusable PMEM buffer or a free PMEM buffer was requested to directly access a block	
gc read wait failures	40	A read wait is when a CR server waits for a disk read to complete before serving a block to another instance. This statistic displays the number of times a read wait ended in failure, that is, after waiting it was unable to serve a block.	
gc read wait timeouts	40	A read wait is when a CR server waits for a disk read to complete before serving a block to another instance. This statistic displays the number of times a read wait timed out, that is, the disk read did not complete in time, so the wait was terminated.	
gc read waits	40	The number of times a CR server waited for a disk read, and then successfully served a block	
global enqueue CPU used by this session	32	Amount of CPU time (in 10s of milliseconds) used by synchronous and asynchronous global enqueue activity in a session from the time a user call starts until it ends. If a user call completes within 10 milliseconds, the start and end user-call time are the same for purposes of this statistics, and 0 milliseconds are added.	
global enqueue get time	32	Total elapsed time in 10s of milliseconds of all synchronous and asynchronous global enqueue gets and converts	
global enqueue gets async	32	Total number of asynchronous global enqueue gets and converts	
global enqueue gets sync	32	Total number of synchronous global enqueue gets and converts	
global enqueue releases	32	Total number of synchronous global enqueue releases	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
HCC analyze table CUs	128	Number of Compression Units that were decompressed for `ANALYZE TABLE`	
HCC analyzer calls	128	Number of times `ANALYZE TABLE` has been run on Hybrid Columnar Compression (HCC) compressed tables	
HCC block compressions attempted	128	Number of times the system failed to recompress an OLTP compressed block in HCC format	
HCC block compressions completed	128	Number of times an OLTP compressed block was successfully recompressed in HCC format	
HCC DML conventional	128	Number of searched DML statements (`UPDATE` and `DELETE`) issued against HCC compressed tables	
HCC DML CUs	128	Number of Compression Units that were decompressed for searched DMLs (`UPDATE` and `DELETE`)	
HCC fetch by rowid CUs	128	Number of Compression Units that were decompressed by single row fetch	
HCC load conventional bytes compressed	128	Length of the data after compression stored in Compression Units by conventional loads. The amount of space used on disk is the sum of the data stored plus the metadata needed to locate the stored data.	
HCC load conventional bytes uncompressed	128	Length of the data before compression stored in Compression Units by conventional loads. The amount of space used on disk is the sum of the data stored plus the metadata needed to locate the stored data.	
HCC load conventional CUs	128	Number of Compression Units that were successfully compressed in any format from conventional loads	
HCC load conventional CUs archive high	128	Number of Compression Units that were successfully compressed in HCC `ARCHIVE HIGH` format from conventional loads	
HCC load conventional CUs archive low	128	Number of Compression Units that were successfully compressed in HCC `ARCHIVE LOW` format from conventional loads	
HCC load conventional CUs query high	128	Number of Compression Units that were successfully compressed in HCC `QUERY HIGH` format from conventional loads	
HCC load conventional CUs query low	128	Number of Compression Units that were successfully compressed in HCC `QUERY LOW` format from conventional loads	
HCC load conventional rows	128	Number of rows that were successfully compressed in HCC format from conventional loads	
HCC load conventional rows not compressed	128	Number of rows that were unable to be compressed in HCC format from conventional loads because the compression resulted in taking more space, not less	
HCC load direct bytes compressed	128	Length of the data after compression stored in Compression Units by Direct Path Loads. The amount of space used on disk is the sum of the data stored plus the metadata needed to locate the stored data.	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
HCC load direct bytes uncompressed	128	Length of the data before compression stored in Compression Units by Direct Path Loads. The amount of space used on disk is the sum of the data stored plus the metadata needed to locate the stored data.	
HCC load direct CUs	128	Number of Compression Units that were successfully HCC compressed by Direct Path Loads	
HCC load direct CUs archive high	128	Number of rows from Direct Path Loads that were HCC compressed with `ARCHIVE HIGH` successfully	
HCC load direct CUs archive low	128	Number of rows from Direct Path Loads that were HCC compressed with `ARCHIVE LOW` successfully	
HCC load direct CUs query high	128	Number of rows from Direct Path Loads that were HCC compressed with `QUERY HIGH` successfully	
HCC load direct CUs query low	128	Number of rows from Direct Path Loads that were HCC compressed with `QUERY LOW` successfully	
HCC load direct rows	128	Number of rows from Direct Path Loads that were HCC compressed successfully	
HCC load direct rows not compressed	128	Number of rows from Direct Path Loads that were OLTP compressed instead of HCC compressed due to negative compression	
HCC scan cell bytes compressed	128	Length of the compressed data stored in Compression Units prior to decompression. This is the length of all columns, not just the columns accessed.	
HCC scan cell bytes decompressed	128	Length of the data after decompression stored in Compression Units. This is the length of all columns, not just the columns accessed.	
HCC scan cell CUs archive high	128	Number of Compression Units scanned that had been compressed with `ARCHIVE HIGH`	
HCC scan cell CUs archive low	128	Number of Compression Units scanned that had been compressed with `ARCHIVE LOW`	
HCC scan cell CUs columns accessed	128	Number of columns that needed to be decompressed on the storage server to process the Compression Unit	
HCC scan cell CUs decompressed	128	Number of Compression Units that needed to be decompressed on the storage server	
HCC scan cell CUs decompression time	128	Total time spent decompressing the columns that were needed on the storage server	
HCC scan cell CUs optimized read	128	Number of Compression Units where all the rows were within the stored Min/Max values. Evaluation of those predicates was optimized out.	
HCC scan cell CUs pruned	128	Number of Compression Units that were pruned based on the Min/Max value checks	
HCC scan cell CUs query high	128	Number of Compression Units scanned that had been compressed with `QUERY HIGH`	
HCC scan cell CUs query low	128	Number of Compression Units scanned that had been compressed with `QUERY LOW`	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
HCC scan cell CUs sent compressed	64	Number of Compression Units that the storage server returned to the RDBMS still compressed after predicate evaluation was done	
HCC scan cell CUs sent head piece	64	Number of Compression Units that the storage server was unable to process and the block header was returned to the RDBMS to be processed	
HCC scan cell CUs sent uncompressed	64	Number of Compression Units that the storage server returned to the RDBMS in uncompressed columnar format	
HCC scan cell rows	128	Number of rows from columnar formatted data that were returned by the storage server to the RDBMS	
HCC scan CUs pcode aggregation pushdown	128	Number of Compression Units that were aggregated on the cell using P(ortable)-byte code	
HCC scan CUs pcode pred evaled	128	Number of predicates that were evaluated using P(ortable)-byte code	
HCC scan CUs pcode pred evaled using rowsets	128	Number of predicates that were evaluated using P(ortable)-byte code using vectorized data	
HCC scan CUs predicates applied	128	Number of predicates where at least some value passed the Min/Max check	
HCC scan CUs predicates optimized	128	Number of predicates that could be evaluated directly against columnar data	
HCC scan CUs predicates received	128	Number of predicates sent to the storage server that could be evaluated directly against HCC format data after decompression	
HCC scan rdbms bytes compressed	128	Length of the compressed data stored in Compression Units prior to decompression. This is the length of all columns, not just the columns accessed.	
HCC scan rdbms bytes decompressed	128	Length of the data after decompression stored in Compression Units. This is the length of all columns, not just the columns accessed.	
HCC scan rdbms CUs archive high	128	Number of HCC Compression Units decompressed by the RDBMS table scan that had been compressed with `ARCHIVE HIGH`	
HCC scan rdbms CUs archive low	128	Number of HCC Compression Units decompressed by the RDBMS table scan that had been compressed with `ARCHIVE LOW`	
HCC scan rdbms CUs columns accessed	128	Number of columns that were decompressed	
HCC scan rdbms CUs decompressed	128	Number of Compression Units that were decompressed on the RDBMS server	
HCC scan rdbms CUs decompression time	128	Total time spent decompressing the columns that were needed on the RDBMS server	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
HCC scan rdbms CUs normal	128	Number of HCC Compression Units decompressed by the RDBMS regular table scan, i.e., 'Table Access Full' in a query plan. This is typically used in specialized scans that, for example, use row versions, row SCN, or use the `LONG RAW` datatype.	
HCC scan rdbms CUs pruned	128	Number of Compression Units that were eliminated by comparing the predicates to the stored Min and Max values for that Comprssion Unit	
HCC scan rdbms CUs query high	128	Number of HCC Compression Units decompressed by the RDBMS table scan that had been compressed with `QUERY HIGH` (which is the default)	
HCC scan rdbms CUs query low	128	Number of HCC Compression Units decompressed by the RDBMS table scan that had been compressed with `QUERY LOW`	
HCC scan rdbms CUs turbo	128	Number of HCC Compression Units decompressed by the RDBMS fast table scan (TurboScan). This is separate to decompression that happens on an Exadata cell.	
HCC scan rdbms rows	128	Number of rows returned from HCC blocks or that were returned from an Exadata cell in columnar format that passed the predicates on that table	
HCC scan rows pcode aggregated	128	Number of rows from HCC blocks or from columnar format blocks returned by an Exadata cell that could be aggregated using the P(ortable)-code style of query compilation	
HCC usage cloud	128	Internal count of how often TurboScan is invoked for HCC data stored in an Oracle Cloud environment. It does not include Oracle on other vendor's clouds. This may or may not correspond with the number of queries or granules scanned.	
HCC usage pillar	128	Internal count of how often TurboScan is invoked for HCC data stored on Pillar storage. This may or may not correspond with the number of queries or granules scanned.	
HCC usage ZFS	128	Internal count of how often TurboScan is invoked for HCC data stored on ZFS storage. This may or may not correspond with the number of queries or granules scanned.	
hot buffers moved to head of LRU	8	When a hot buffer reaches the tail of its replacement list, Oracle moves it back to the head of the list to keep it from being reused. This statistic counts such moves.	
hot buffers moved to head of LRU for pmem	8	When a hot PMEM buffer reaches the tail of its replacement list, Oracle moves it back to the head of the list to keep it from being reused. This statistic counts such moves.	
hot pmem block exchange with dram attempts	264	Number of hot PMEM buffers that were attempted to be exchanged with colder DRAM buffers, to ensure both blocks are still cached	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
hot pmem block exchange with dram successes	264	Number of hot PMEM buffers that were successfully exchanged with colder DRAM buffers, with both blocks still cached	
hot pmem block migration to dram attempts	8	Number of hot PMEM buffer cache blocks that were attempted to be migrated to DREM to reduce access latency	
hot pmem block migration to dram successes	264	Number of hot PMEM buffer cache blocks that were successfully migrated to DRAM to reduce access latency	
immediate (CR) block cleanout applications	128	Number of times cleanout records are applied immediately during consistent-read requests	
immediate (CURRENT) block cleanout applications	128	Number of times cleanout records are applied immediately during current gets. Compare this statistic with "deferred (CURRENT) block cleanout applications"	
IM (HPK4SQL) hash joins attempted	384	Number of in-memory vectorized hash joins attempted	
IM (HPK4SQL) hash joins completed	384	Number of in-memory vectorized hash joins completed	
IM (hybrid) scan blocks on hybrid list	384	Number of blocks on the hybrid In-Memory scan list	
IM (hybrid) scan rows on hybrid list	384	Number of rows on the hybrid In-Memory scan list	
IM default area resized	128	The amount of memory by which the column store got resized	
IM populate accumulated time (ms)	128	Total amount of DB time (in milliseconds) spent populating CUs into the IM column store due to segment scans	
IM populate bytes in-memory EU data	128	Size in bytes of in-memory EU data populated due to segment scans	
IM populate bytes uncompressed EU data	128	Uncompressed size in bytes of in-memory EU data populated due to segment scans	
IM populate CUs	128	Number of CUs populated in the IM column store due to segment scans	
IM populate CUs memcompress for capacity high	128	Number of CUs populated in the IM column store due to segment scans using memcompress for capacity high	
IM populate CUs memcompress for capacity low	128	Number of CUs populated in the IM column store due to segment scans using memcompress for capacity low	
IM populate CUs memcompress for dml	128	Number of CUs populated in the IM column store due to segment scans using memcompress for DML	
IM populate CUs memcompress for query high	128	Number of CUs populated in the IM column store due to segment scans using memcompress for query high	
IM populate CUs memcompress for query low	128	Number of CUs populated in the IM column store due to segment scans using memcompress for query low	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
IM populate CUs no memcompress	128	Number of CUs populated in the IM column store due to segment scans without compression	
IM populate CUs requested	128	Number of CUs requested to be populated due to segment scans	
IM populate EUs	128	Number of EUs populated in the IM column store due to segment scans	
IM populate EUs accumulated time (ms)	128	Total amount of DB time (in milliseconds) spent populating EUs into the IM column store due to segment scans	
IM populate EUs columns	128	Number of columns populated in EUs due to segment scans	
IM populate EUs memcompress for capacity high	128	Number of EUs populated in the IM column store due to segment scans at memcompress for capacity high	
IM populate EUs memcompress for capacity low	128	Number of EUs populated in the IM column store due to segment scans at memcompress for capacity low	
IM populate EUs memcompress for dml	128	Number of EUs populated in the IM column store due to segment scans at memcompress for dml	
IM populate EUs memcompress for query high	128	Number of EUs populated in the IM column store due to segment scans at memcompress for query high	
IM populate EUs memcompress for query low	128	Number of EUs populated in the IM column store due to segment scans at memcompress for query low	
IM populate EUs no memcompress	128	Number of EUs populated in the IM column store without compression due to segment scans	
IM populate EUs requested	128	Number of EUs requested to be populated in the IM column store due to segment scans	
IM populate no contiguous inmemory space	128	Number of CUs that fail to populate due to lack of contiguous space in the In-Memory Area	
IM populate segments	128	Number of segments populated due to segment scan	
IM populate segments requested	128	Number of segments requested to be populated due to segment scan	
IM populate segments wall clock time (ms)	128	Total amount of wall clock time (in milliseconds) spent populating CUs into the IM column store due to segment scans	
IM prepopulate accumulated time (ms)	128	Total amount of DB time (in milliseconds) spent prepopulating CUs into the IM column store priority	
IM prepopulate bytes in-memory EU data	128	Size in bytes of in-memory EU data populated due to priority	
IM prepopulate bytes uncompressed EU data	128	Uncompressed size in bytes of in-memory EU data populated due to priority	
IM prepopulate CUs	128	Number of CUs prepopulated in the IM column store due to priority	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
IM prepopulate CUs memcompress for capacity high	128	Number of CUs prepopulated in the IM column store due to priority using memcompress for capacity high	
IM prepopulate CUs memcompress for capacity low	128	Number of CUs prepopulated in the IM column store due to priority using memcompress for capacity low	
IM prepopulate CUs memcompress for dml	128	Number of CUs prepopulated in the IM column store due to priority using memcompress for DML	
IM prepopulate CUs memcompress for query high	128	Number of CUs prepopulated in the IM column store due to priority using memcompress for query high	
IM prepopulate CUs memcompress for query low	128	Number of CUs prepopulated in the IM column store due to priority using memcompress for query low	
IM prepopulate CUs no memcompress	128	Number of CUs prepopulated in the IM column store due to priority without compression	
IM prepopulate CUs requested	128	Number of CUs requested to be prepopulated due to priority	
IM prepopulate EUs	128	Number of EUs populated in the IM column store due to priority	
IM prepopulate EUs accumulated time (ms)	128	Total amount of DB time (in milliseconds) spent populating EUs into the IM column store due to priority	
IM prepopulate EUs columns	128	Number of columns populated in EUs due to priority	
IM prepopulate EUs memcompress for capacity high	128	Number of EUs populated in the IM column store due to priority at memcompress for capacity high	
IM prepopulate EUs memcompress for capacity low	128	Number of EUs populated in the IM column store due to priority at memcompress for capacity low	
IM prepopulate EUs memcompress for dml	128	Number of EUs populated in the IM column store due to priority at memcompress for dml	
IM prepopulate EUs memcompress for query high	128	Number of EUs populated in the IM column store due to priority at memcompress for query high	
IM prepopulate EUs memcompress for query low	128	Number of EUs populated in the IM column store due to priority at memcompress for query low	
IM prepopulate EUs no memcompress	128	Number of EUs populated in the IM column store without compression due to priority	
IM prepopulate EUs requested	128	Number of EUs requested to be populated in the IM column store due to priority	
IM prepopulate segments	128	Number of segments prepopulated due to priority	
IM prepopulate segments requested	128	Number of segments requested to be prepopulated due to priority	
IM repopulate accumulated time (ms)	128	Total amount of DB time (in milliseconds) spent repopulating CUs into the IM column store due to DML changes	
IM repopulate bytes in-memory EU data	128	Size in bytes of in-memory EU data repopulated due to EU reaching staleness threshold	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
IM repopulate CUs	128	Total number of CUs requested to be repopulated due to CU reaching staleness threshold	
IM repopulate CUs memcompress for capacity high	128	Number of CUs repopulated in the IM column store using memcompress for capacity high due to CU reaching staleness threshold	
IM repopulate CUs memcompress for capacity low	128	Number of CUs repopulated in the IM column store using memcompress for capacity low due to CU reaching staleness threshold	
IM repopulate CUs memcompress for dml	128	Number of CUs repopulated in the IM column store using memcompress for DML due to CU reaching staleness threshold	
IM repopulate CUs memcompress for query high	128	Number of CUs repopulated in the IM column store using memcompress for query high due to CU reaching staleness threshold	
IM repopulate CUs memcompress for query low	128	Number of Cus repopulated in the IM column store using memcompress for query low due to CU reaching staleness threshold	
IM repopulate CUs no memcompress	128	Number of CUs repopulated in the IM column store without compression due to CU reaching staleness threshold	
IM repopulate CUs requested	128	Total number of CUs requested to be repopulated due to CU reaching staleness threshold	
IM repopulate (doublebuffering) CUs	128	Number of CUs repopulated with double-buffering enabled on the earlier version of the CUs	
IM repopulate (doublebuffering) CUs requested	128	Number of CUs requested to be repopulated with double-buffering enabled on the earlier version of the CUs	
IM repopulate EUs	128	Number of EUs requested to be repopulated due to EU reaching staleness threshold	
IM repopulate EUs accumulated time (ms)	128	Total amount of DB time (in milliseconds) spent repopulating EUs into the IM column store due to DML changes	
IM repopulate EUs columns	128	Number of columns repopulated in EUs due to EU reaching staleness threshold	
IM repopulate EUs memcompress for capacity high	128	Number of EUs repopulated in the IM column store at memcompress for capacity high due to EU reaching staleness threshold	
IM repopulate EUs memcompress for capacity low	128	Number of EUs repopulated in the IM column store at memcompress for capacity low due to EU reaching staleness threshold	
IM repopulate EUs memcompress for dml	128	Number of EUs repopulated in the IM column store at memcompress for DML due to EU reaching staleness threshold	
IM repopulate EUs memcompress for query high	128	Number of EUs repopulated in the IM column store at memcompress for query high due to EU reaching staleness threshold	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
IM repopulate EUs memcompress for query low	128	Number of EUs repopulated in the IM column store at memcompress for query low due to EU reaching staleness threshold	
IM repopulate EUs no memcompress	128	Number of EUs repopulated in the IM column store without compression due to EU reaching staleness threshold	
IM repopulate EUs requested	128	Total number of EUs requested to be repopulated due to EU reaching staleness threshold	
IM repopulate (incremental) CUs	128	Number of CUs repopulated incrementally from earlier versions of the CUs	
IM repopulate (incremental) CUs requested	128	Number of CUs requested to be repopulated incrementally from earlier versions of the CUs	
IM repopulate (incremental) EUs	128	Number of EUs repopulated using unchanged data from the current EU due to EU reaching staleness threshold	
IM repopulate (incremental) EUs requested	128	Number of EUs requested to be repopulated using unchanged data from the current EU due to EU reaching staleness threshold	
IM repopulate no contiguous inmemory space	128	Number of CUs that failed to repopulate due to lack of contigunous space in the In-Memory Area	
IM repopulate (scan) CUs	128	Number of CUs repopulated in the IM column store due to scans	
IM repopulate (scan) CUs requested	128	Number of CUs requested to be repopulated in the IM column store due to scans	
IM repopulate (scan) EUs	128	Number of EUs repopulated in the IM column store that were triggered by scans on the EU	
IM repopulate (scan) EUs requested	128	Number of EUs requested for repopulation in the IM column store that were triggered by scans on the EU	
IM repopulate segments	128	Number of segments repopulated	
IM repopulate segments requested	128	Indicates the number of segments requested to be repopulated	
IM repopulate (trickle) accumulated time (ms)	128	Total amount of DB time (in milliseconds) spent trickle repopulating CUs into the IM column store due to DML changes	
IM repopulate (trickle) bytes in-memory EU data	128	Size in bytes of in-memory EU data repopulated due to DML changes	
IM repopulate (trickle) bytes uncompressed EU data	128	Uncompressed size in bytes of in-memory EU data repopulated due to EU reaching staleness threshold	
IM repopulate (trickle) CUs	128	Number of CUs trickle repopulated in the IM column store due to DML changes	
IM repopulate (trickle) CUs memcompress for capacity high	128	Number of CUs trickle repopulated in the IM column store using memcompress for capacity high due to DML changes	
IM repopulate (trickle) CUs memcompress for capacity low	128	Number of CUs trickle repopulated in the IM column store using memcompress for capacity low due to DML changes	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
IM repopulate (trickle) CUs memcompress for dml	128	Number of CUs trickle repopulated in the IM column store using memcompress for DML due to DML changes	
IM repopulate (trickle) CUs memcompress for query high	128	Number of CUs trickle repopulated in the IM column store using memcompress for query high due to DML changes	
IM repopulate (trickle) CUs memcompress for query low	128	Number of CUs trickle repopulated in the IM column store using memcompress for query low due to DML changes	
IM repopulate (trickle) CUs no memcompress	128	Number of CUs trickle repopulated in the IM column store without compression due to DML changes	
IM repopulate (trickle) CUs requested	128	Total number of CUs requested to be trickle repopulated due to DML changes	
IM repopulate (trickle) CUs resubmitted	128	Number of CUs trickle repopulate tasks submitted	
IM repopulate (trickle) EUs	128	Number of EUs trickle repopulated in the IM column store due to DML changes	
IM repopulate (trickle) EUs accumulated time (ms)	128	Total amount of DB time (in milliseconds) spent trickle repopulating EUs into the IM column store due to DML changes	
IM repopulate (trickle) EUs columns	128	Number of columns repopulated in EUs due to DML changes	
IM repopulate (trickle) EUs memcompress for capacity high	128	Number of EUs trickle repopulated in the IM column store due to DML changes at memcompress for capacity high	
IM repopulate (trickle) EUs memcompress for capacity low	128	Number of EUs trickle repopulated in the IM column store due to DML changes at memcompress for capacity low	
IM repopulate (trickle) EUs memcompress for dml	128	Number of EUs trickle repopulated in the IM column store due to DML changes at memcompress for dml	
IM repopulate (trickle) EUs memcompress for query high	128	Number of EUs trickle repopulated in the IM column store due to DML changes at memcompress for query high	
IM repopulate (trickle) EUs memcompress for query low	128	Number of EUs trickle repopulated in the IM column store due to DML changes at memcompress for query low	
IM repopulate (trickle) EUs no memcompress	128	Number of EUs trickle repopulated in the IM column store without compression due to DML changes	
IM repopulate (trickle) EUs requested	128	Number of EUs requested to be trickle repopulated in the IM column store due to DML changes	
IM scan CUs column not in memory	128	Number of extents that could not be read from the IM column store because one of the columns required was not in memory	
IM scan CUs invalid or missing revert to on disk extent	128	Number of extents where no IMCU exists	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
IM scan CUs memcompress for query low	128	Number of memcompress for query high CUs scanned in the IM column store	
IM scan CUs memcompress for query high	128	Number of memcompress for query high CUs scanned in the IM column store	
IM scan CUs memcompress for capacity low	128	Number of memcompress for capacity low CUs scanned in the IM column store	
IM scan CUs memcompress for capacity high	128	Number of memcompress for capacity high CUs scanned in the IM column store	
IM scan CUs memcompress for dml	128	Number of memcompress for DML CUs scanned in the IM column store	
IM scan CUs predicates applied	128	Number of where clause predicates applied to the In-Memory storage index	
IM scan CUs predicates optimized	128	Number of where clause predicates applied to the IM column store for which either all rows pass min/max pruning via an In-Memory storage index or no rows pass min/max pruning	
IM scan CUs pruned	128	Number of CUs pruned by the storage index	
IM scan (dynamic) multi-threaded scans	128	Number of In-Memory table scans which benefited from In-Memory dynamic scans	
IM scan (dynamic) tasks processed by parent	128	Number of IMCUs processed normally because of Resource Manager limit	
IM scan (dynamic) tasks processed by thread	128	Number of IMCUs processed in parallel by a worker thread	
IM scan (dynamic) rows	128	Number of rows processed by In-Memory dynamic scans	
IM scan EU bytes in-memory	128	Size in bytes of in-memory EU data accessed by scans	
IM scan EU bytes uncompressed	128	Uncompressed size in bytes of in-memory EU data accessed by scans	
IM scan EU rows	128	Number of rows scanned from EUs in the IM column store before where clause predicate applied	
IM scan EUs columns accessed	128	Number of columns in the EUs accessed by scans	
IM scan EUs columns decompressed	128	Number of columns in the EUs decompressed by scans	
IM scan EUs columns theoretical max	128	Number of columns that would have been accessed from the EU if the scans looked at all columns	
IM scan EUs memcompress for capacity high	128	Number of memcompress for capacity high EUs scanned in the IM column store	
IM scan EUs memcompress for capacity low	128	Number of memcompress for capacity low EUs scanned in the IM column store	
IM scan EUs memcompress for dml	128	Number of memcompress for DML EUs scanned in the IM column store	
IM scan EUs memcompress for query high	128	Number of memcompress for query high EUs scanned in the IM column store	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
IM scan EUs memcompress for query low	128	Number of memcompress for query low EUs scanned in the IM column store	
IM scan EUs no memcompress	128	Number of uncompressed EUs scanned in the IM column store	
IM scan EUs split pieces	128	Number of split EU pieces among all IM EUs	
IM scan rows	128	Number of rows in scanned In-Memory Compression Units (IMCUs)	
IM scan rows optimized	128	Number of rows that were not scanned in the IM column store as they were pruned via a number of optimizations such as min/max pruning via In-Memory storage indexes	
IM scan rows projected	128	Number of rows returned from the IM column store	
IM scan rows valid	128	Number of rows scanned from the IM column store after applying valid vector	
IM scan segments minmax eligible	128	Number of CUs that are eligible for min/max pruning via storage index	
IM space CU bytes allocated	128	Number of In-Memory bytes allocated	
IM space CU creations initiated	128	Number of space requests for CUs	
IM space CU extents allocated	128	Number of In-Memory extents allocated	
IM space segments allocated	128	Number of snapshot segments created	
IM space segments freed	128	Number of snapshot segments deleted	
IM transactions	128	Number of transactions that triggered data to be journaled in the IM column store	
IM transactions CUs invalid	128	Number of CUs in the IM column store invalidated by transactions	
IM transactions rows invalidated	128	Number of rows in the IM column store invalidated by transactions	
IM transactions rows journaled	128	Number of rows logged in the transaction journal	
in call idle wait time	1	The total wait time (in microseconds) for waits that belong to the Idle wait class. **See Also:** "non-idle wait count" and "non-idle wait time"	
index cmph cu, uncomp sentinels	128	Number of CUs created with uncompressed sentinels	
index cmph dm, cu lock expand	128	Number of times CU lock structure expanded	
index cmph dm, cu migrate row	128	Number of times a row migrated from a CU	
index cmph dm, insert unpurge CU row	128	Number of times a CU row was unpurged during insert	
index cmph dm, purge dummy CU	128	Number of times dummy CU purged from leaf block	
index cmph dm, split for cu lock expand	128	Number of times leaf block split for CU lock expansion	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
index cmph dm, split for cu migrate row	128	Number of leaf block splits due to CU row migration	
index cmph ld, CU fit	128	Number of times load created a well sized CU, no space for uncompressed rows	
index cmph ld, CU fit, add rows	128	Number of times load created a well sized CU, with space for uncompressed rows	
index cmph ld, CU negative comp	128	Number of times load CU gave negative compression	
index cmph ld, CU over-est	128	Number of times load created an oversized CU	
index cmph ld, CU under-est	128	Number of times load created a small CU	
index cmph ld, infinite loop	128	Number of times shrink CU attempts resulted in uncompressed rows	
index cmph ld, lf blks flushed	128	Number of leaf blocks flushed by load	
index cmph ld, lf blks w/ und CU	128	Number of leaf blocks flushed with small CU	
index cmph ld, lf blks w/o CU	128	Number of leaf blocks flushed without a CU	
index cmph ld, lf blks w/o unc r	128	Number of leaf blocks flushed without uncompressed rows	
index cmph ld, retry in over-est	128	Number of times CU was resized after creating an oversized CU	
index cmph ld, rows compressed	128	Number of rows compressed by load	
index cmph ld, rows uncompressed	128	Number of rows left uncompressed by load	
index cmph sc, ffs decomp buffers	128	Number of blocks decompressed for fast scan	
index cmph sc, ffs decomp buffers released and found valid	128	Number of times decompressed CU buffer was reused by fast scan	
index cmph sc, ffs decomp buffers rows avail	128	Number of rows in decompressed buffer for fast scan	
index cmph sc, ffs decomp buffers rows used	128	Number of rows used from decompressed buffer for fast scan	
index cmph sc, ffs decomp failures	128	Number of time decompress CU was not possible for fast scan	
	128	Number of times 90-10 leaf block CU splits were made 50-50	
index cmph sp, leaf norecomp limit	128	Number of times leaf block recompression reached the recompression limit	
index cmph sp, leaf norecomp negcomp	128	Number of times leaf block recompression returned negative compression	
index cmph sp, leaf norecomp nospace	128	Number of times leaf block recompression returned not enough space	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
index cmph sp, leaf norecomp notry	128	Number of times leaf block recompression not attempted	
index cmph sp, leaf norecomp oversize	128	Number of times leaf block recompression returned an oversized CU	
index cmph sp, leaf norecomp zerocur	128	Number of times leaf block recompression returned a CU with 0 rows	
index cmph sp, leaf recomp fewer ucs	128	Number of CUs created with reduced number of sentinels	
index cmph sp, leaf recomp zero ucs	128	Number of CUs created with zero sentinels	
index cmph sp, leaf recompress	128	Number of times a leaf block CU was recompressed	
index cmpl co, prefix mismatch	128	Number of times reorg found a neighboring block prefix count mismatch	
index cmpl ro, blocks not compressed	128	Number of times prefix compression was not applied to avoid negative compression	
index cmpl ro, prefix change at block	128	Number of times prefix count was changed to an optimal value	
index cmpl ro, prefix no change at block	128	Number of times prefix count was already the optimal value	
index cmpl ro, reorg avoid load new block	128	Number of times a block reorg avoided a new block being created during load	
index cmpl ro, reorg avoid split	128	Number of times a block reorg avoided a block split during DML	
index fast full scans (direct read)	64	Number of fast full scans initiated using direct read	
index fast full scans (full)	64	Number of fast full scans initiated for full segments	
index fast full scans (rowid ranges)	64	Number of fast full scans initiated with rowid endpoints specified	
large tracked transactions	128	For tables tracked by flashback data archive, the number of transactions modifying rows in those tables which are large in terms of size or number of changes	
leaf node splits	128	Number of times an index leaf node was split because of the insertion of an additional value	
lob reads	8	Number of LOB API read operations performed in the session/system. A single LOB API read may correspond to multiple physical/logical disk block reads.	
lob writes	8	Number of LOB API write operations performed in the session/system. A single LOB API write may correspond to multiple physical/logical disk block writes.	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
lob writes unaligned	8	Number of LOB API write operations whose start offset or buffer size is not aligned to the internal chunk size of the LOB. Writes aligned to chunk boundaries are the most efficient write operations. The internal chunk size of a LOB is available through the LOB API (for example, DBMS_LOB.GETCHUNKSIZE()).	
logons cumulative	1	Total number of logons since the instance started. Useful only in V$SYSSTAT. It gives an instance overview of all processes that logged on.	
logons current	1	Total number of current logons. Useful only in V$SYSSTAT.	
memopt r failed puts	128	Total failed puts on hash index	
memopt r failed reads on blocks	128	Total lookup failures due to read failure on blocks because of concurrent changes	
memopt r failed reads on buckets	128	Total lookup failures due to concurrent hash bucket changes	
memopt r hits	128	Total hits on hash index – primary key found	
memopt r lookup detected CR buffer	128	Total lookup failures due to block pointed to by hash index being no longer the current version	
memopt r lookups	128	Total number of lookups on hash index	
memopt r misses	128	Total misses on hash index due to primary key not found	
memopt r puts	128	Total puts on hash index	
memopt r successful puts	128	Total successful puts on hash index	
messages received	128	Number of messages sent and received between background processes	
messages sent	128	Number of messages sent and received between background processes	
MLE JIT compilation duration cumulative	1	Total amount of cpu time (in milliseconds) spent by asynchronous just-in-time compilations for a session	
MLE JIT compilation duration max	1	Duration (in milliseconds) of the most time-consuming just-in-time compilation per session (not applicable for V$SYSSTAT)	
MLE JIT compilation error count	1	Number of just-in-time compilation operations in a session that failed with an error	
MLE JIT compilation success count	1	Number of successful just-in-time compilations in a session	
MLE full GC accumulated time	1	Cumulative time (in milliseconds) spent collecting the entire MLE heap	
MLE full GC count	1	Number of times the entire MLE heap was collected	
MLE incremental GC accumulated time	1	Cumulative time (in milliseconds) spent collecting the young-generation portion of the MLE heap	
MLE incremental GC count	1	Number of times the young-generation portion of the MLE heap was collected	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
MLE total memory in use	1	Total amount of memory (in bytes) used for the MLE instance in a session, across all contexts	
no buffer to keep pinned count	72	Number of times a visit to a buffer attempted, but the buffer was not found where expected. Like "buffer is not pinned count" and "buffer is pinned count", this statistic is useful only for internal debugging purposes.	
no work - consistent read gets	128	Number consistent gets that require neither block cleanouts nor rollbacks. **See Also:** "consistent gets"	
non-idle wait count	1	The total number of waits performed with wait events that were not part of the Idle wait class. **See Also:** "in call idle wait time" and "non-idle wait time"	
non-idle wait time	1	The total wait time (in microseconds) for waits that do not belong to the Idle wait class. **See Also:** "in call idle wait time" and "non-idle wait count"	
OLAP Aggregate Function Calc	64	The number of times the `AGGREGATE` function computes a parent value based on the values of its children.	
OLAP Aggregate Function Logical NA	64	The number of times an `AGGREGATE` function evaluates to a logical NA value. This could be because the `AGGINDEX` is on and the composite tuple does not exist.	
OLAP Aggregate Function Precompute	64	The number of times the `AGGREGATE` function is to compute a value and finds it precomputed in the cube.	
OLAP Custom Member Limit	64	The number of times an OLAP table function issues a custom member limit	
OLAP Engine Calls	64	The total number of OLAP transactions executed within the session. This value provides a general indication of the level of OLAP activity in the session.	
OLAP Fast Limit	64	The number of times an OLAP table function issues a fast limit	
OLAP Full Limit	64	The number of times an OLAP table function issues a full limit	
OLAP GID Limit	64	The number of times an OLAP table function issues a Cube Grouping ID (CGID) limit. Typically, this type of limit occurs for query rewrite transformations that resolve to a cube organized materialized view.	
OLAP Import Rows Loaded	64	The number of OLAP import rows loaded. This statistic provides the number of rows of the source cursor that are actually loaded into an Analytic Workspace (AW). The difference between the OLAP Import Rows Pushed and OLAP Import Rows Loaded provides the number of rejected rows.	
OLAP Import Rows Pushed	64	The number of OLAP import rows pushed. This statistic refers to the number of rows encountered from a source cursor and is useful during cube build operations.	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
OLAP INHIER Limit	64	The number of times an OLAP table function issues an in-hierarchy limit. This type of limit can occur when you use cube dimension hierarchy views.	
OLAP Limit Time	64	The total time taken by all the OLAP Limit operations that were performed during the last call to the OLAP table function	
OLAP Paging Manager Cache Changed Page	64	The number of times the OLAP page pool is changed for any attached AW.	
OLAP Paging Manager Cache Hit	64	The number of times a requested page is found in the OLAP page pool. Use this statistic in conjunction with OLAP Paging Manager Cache Miss to determine the OLAP page pool efficiency ratio.	
OLAP Paging Manager Cache Miss	64	The number of times a requested page is not found in the OLAP page pool. Use this statistic in conjunction with OLAP Paging Manager Cache Hit to determine the OLAP page pool efficiency ratio.	
OLAP Paging Manager Cache Write	64	The number of times the OLAP paging manager writes to a page in the OLAP page pool.	
OLAP Paging Manager New Page	64	The number of newly-created pages in the OLAP page pool that have not yet been written to the workspace LOB	
OLAP Paging Manager Pool Size	64	Size, in bytes, of the OLAP page pool allocated to a session and the sum of all OLAP page pools in the system.	
OLAP Perm LOB Read	64	The number of times data was read from the table where the AW is stored. These are permanent LOB reads.	
OLAP Row Id Limit	64	The number of times an OLAP table function issues a row Id limit.	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
OLAP Row Load Time	64	The total time spent loading rows into an AW during cube build and OLAP SQL import operations. Use this statistic along with the OLAP engine elapsed time to measure time spent running OLAP engine routines that involve loading data into AWs from a SQL source. This statistic has the following levels of precision: • Low precision timer This captures the elapsed time of the entire fetch phase of the SQL cursor that is being loaded into AWs. It includes the SQL execution time that occurs during a fetch operation from a source cursor and time taken by the OLAP engine to populate AWs. • High precision timer This captures the elapsed time, excluding the SQL processing of the cursor being loaded. It records the time spent in the OLAP engine only. • Default timer precision: This is based on the `STATISTIC_LEVEL` parameter. If the low precision is used, then `STATISTICS_LEVEL` is TYPICAL. The high precision timer is used when `STATISTIC_LEVEL` is set to ALL. No timing is captured when `STATISTICS_LEVEL` is BASIC.	
OLAP Row Source Rows Processed	64	The number of rows processed by the OLAP row source	
OLAP Session Cache Hit	64	The number of times the requested, dynamically-aggregated value of an AW object, was found in the OLAP session cache.	
OLAP Session Cache Miss	64	The number of times the requested, dynamically-aggregated value of an AW object, was not found in the OLAP session cache.	
OLAP Temp Segment Read	64	The number of times data was read from a temporary segment and not from the OLAP page pool	
OLAP Temp Segments	64	The number of OLAP pages stored in temporary segments for analytic workspaces	
OLAP Unique Key Attribute Limit	64	The number of times an OLAP table function issues a unique key attribute limit	
opened cursors cumulative	1	In V$SYSSTAT: Total number of cursors opened since the instance started. In V$SESSTAT: Total number of cursors opened since the start of the session.	
opened cursors current	1	Total number of current open cursors	
OS CPU Qt wait time	1	The time a session spends on the CPU run queue (in microseconds), waiting to get the CPU to run	
OS Involuntary context switches	16	Number of context switches that were enforced by the operating system	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
OS Signals received	16	Number of signals received	
OS Swaps	16	Number of swap pages	
OS Voluntary context switches	16	Number of voluntary context switches (for example, when a process gives up the CPU by a SLEEP() system call)	
Parallel operations downgraded 1 to 25 pct	32	Number of times parallel execution was requested and the degree of parallelism was reduced because of insufficient parallel execution servers	
Parallel operations downgraded 25 to 50 pct	32	Number of times parallel execution was requested and the degree of parallelism was reduced because of insufficient parallel execution servers	
Parallel operations downgraded 50 to 75 pct	32	Number of times parallel execution was requested and the degree of parallelism was reduced because of insufficient parallel execution servers	
Parallel operations downgraded 75 to 99 pct	32	Number of times parallel execution was requested and the degree of parallelism was reduced because of insufficient parallel execution servers	
Parallel operations downgraded to serial	32	Number of times parallel execution was requested but execution was serial because of insufficient parallel execution servers	
Parallel operations not downgraded	32	Number of times parallel execution was executed at the requested degree of parallelism	
parse count (describe)	64	Total number of parse calls on a describe cursor. This operation is a less expensive than a hard parse and more expensive than a soft parse.	
parse count (hard)	64	Total number of parse calls (real parses). A hard parse is a very expensive operation in terms of memory use, because it requires Oracle to allocate a workheap and other memory structures and then build a parse tree.	
parse count (total)	64	Total number of parse calls (hard, soft, and describe). A soft parse is a check on an object already in the shared pool, to verify that the permissions on the underlying object have not changed.	
parse time cpu	64	Total CPU time used for parsing (hard and soft) in 10s of milliseconds	Y
parse time elapsed	64	Total elapsed time for parsing, in 10s of milliseconds. Subtract "parse time cpu" from this statistic to determine the total waiting time for parse resources.	Y
physical maps pmem	264	Number of direct-mapped references acquired from FsDirect. Note that in steady state this is approximately the same as the number of unmaps, because each map requires an unmap (e.g. reuses a PMEM buffer).	
physical read bytes	8	Total size in bytes of all disk reads by application activity (and not other instance activity) only.	
physical read flash cache hits	8	Total number of reads from flash cache instead of disk	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
physical read IO requests	8	Number of read requests for application activity (mainly buffer cache and direct load operation) which read one or more database blocks per request. This is a subset of "physical read total IO requests" statistic.	
physical read requests optimized	8	Number of read requests that read one or more database blocks from the Database Smart Flash Cache or the Exadata Smart Flash Cache.	
physical read total bytes	8	Total size in bytes of disk reads by all database instance activity including application reads, backup and recovery, and other utilities. The difference between this value and "physical read bytes" gives the total read size in bytes by non-application workload.	
physical read total IO requests	8	Number of read requests which read one or more database blocks for all instance activity including application, backup and recovery, and other utilities. The difference between this value and "physical read total multi block requests" gives the total number of small I/O requests which are less than 128 kilobytes down to single block read requests.	
physical read total multi block requests	8	Total number of Oracle instance read requests which read 128 kilobytes or more in two or more database blocks per request for all instance activity including application, backup and recovery, and other utilities.	
physical reads	8	Total number of data blocks read from disk. This value can be greater than the value of "physical reads direct" plus "physical reads cache" as reads into process private buffers also included in this statistic.	
physical reads cache	8	Total number of data blocks read from disk into the buffer cache. This is a subset of "physical reads" statistic.	
physical reads cache prefetch	8	Number of contiguous and noncontiguous blocks that were prefetched.	
physical reads direct	8	Number of reads directly from disk, bypassing the buffer cache. For example, in high bandwidth, data-intensive operations such as parallel query, reads of disk blocks bypass the buffer cache to maximize transfer rates and to prevent the premature aging of shared data blocks resident in the buffer cache.	
physical reads direct (lob)	8	Number of buffers that were read directly for LOBs	
physical reads direct temporary tablespace	8	Number of buffers that were read directly from temporary tablespaces	
physical reads for flashback new	8	Number of blocks read for newing (that is, preparing a data block for a completely new change) blocks while flashback database is enabled	
physical reads pmem	8	Number of blocks read/copied from PMEM into DRAM cache	
physical reads pmem decrypt	8	Number of blocks read/copied from PMEM into DRAM cache due to the need for decryption. This is a subset of "physical reads pmem" statistics value.	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
physical reads pmem direct path	8	Number of blocks read from PMEM into PGA memory due to direct path access. This is a subset of "physical reads pmem" statistics value.	
physical reads pmem exclusive	8	Number of blocks read/copied from PMEM into DRAM cache due to exclusive access requests, which prevents other processes from accessing the block on PMEM directly. This is a subset of "physical reads pmem" statistics value.	
physical reads pmem modification	8	Number of blocks read/copied from PMEM into DRAM cache due to modification. This is a subset of "physical reads pmem" statistics value.	
physical reads pmem promote	8	Number of blocks read/copied from PMEM into DRAM cache due to hot block promotion. This is a subset of "physical reads pmem" statistics value. This statistic is further categorized into "hot pmem block migration to dram successes" and "hot pmem block exchange with dram successes" statistics.	
physical reads pmem rollback	8	Number of blocks read/copied from PMEM into DRAM cache due to CR rollback. This is a subset of "physical reads pmem" statistics value.	
physical reads prefetch warmup	8	Number of data blocks that were read from the disk during the automatic prewarming of the buffer cache.	
physical unmaps pmem forced	264	Number of forfeited direct-mapped references requested by FsDirect due to PMEM memory pressure	
physical write bytes	8	Total size in bytes of all disk writes from the database application activity (and not other kinds of instance activity).	
physical write IO requests	8	Number of write requests for application activity (mainly buffer cache and direct load operation) which wrote one or more database blocks per request.	
physical write total bytes	8	Total size in bytes of all disk writes for the database instance including application activity, backup and recovery, and other utilities. The difference between this value and "physical write bytes" gives the total write size in bytes by non-application workload.	
physical write total IO requests	8	Number of write requests which wrote one or more database blocks from all instance activity including application activity, backup and recovery, and other utilities. The difference between this stat and "physical write total multi block requests" gives the number of single block write requests.	
physical write total multi block requests	8	Total number of Oracle instance write requests which wrote two or more blocks per request to the disk for all instance activity including application activity, recovery and backup, and other utilities.	
physical writes	8	Total number of data blocks written to disk. This statistics value equals the sum of "physical writes direct" and "physical writes from cache" values.	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
physical writes direct	8	Number of writes directly to disk, bypassing the buffer cache (as in a direct load operation)	
physical writes direct (lob)	8	Number of buffers that were directly written for LOBs	
physical writes direct temporary tablespace	8	Number of buffers that were directly written for temporary tablespaces	
physical writes from cache	8	Total number of data blocks written to disk from the buffer cache. This is a subset of "physical writes" statistic.	
physical writes non checkpoint	8	Number of times a buffer is written for reasons other than advancement of the checkpoint. Used as a metric for determining the I/O overhead imposed by setting the `FAST_START_IO_TARGET` parameter to limit recovery I/Os. (Note that `FAST_START_IO_TARGET` is a deprecated parameter.) Essentially this statistic measures the number of writes that would have occurred had there been no checkpointing. Subtracting this value from "physical writes" gives the extra I/O for checkpointing.	
pinned buffers inspected	8	Number of times a user process, when scanning the tail of the replacement list looking for a buffer to reuse, encountered a cold buffer that was pinned or had a waiter that was about to pin it. This occurrence is uncommon, because a cold buffer should not be pinned very often.	
pinned buffers inspected for pmem	8	Number of times a user process, when scanning the tail of the replacement list looking for a PMEM buffer to reuse in DRAM, encountered a cold buffer that was pinned or had a waiter that was about to pin it. This occurrence is uncommon, because a cold buffer should not be pinned very often.	
prefetched blocks aged out before use	8	Number of contiguous and noncontiguous blocks that were prefetched but aged out before use	
process last non-idle time	128	The last time this process executed	Y
PX local messages recv'd	32	Number of local messages received for parallel execution within the instance local to the current session	
PX local messages sent	32	Number of local messages sent for parallel execution within the instance local to the current session	
PX remote messages recv'd	32	Number of remote messages received for parallel execution within the instance local to the current session	
PX remote messages sent	32	Number of remote messages sent for parallel execution within the instance local to the current session	
queries parallelized	32	Number of SELECT statements executed in parallel	
recovery array read time	8	Elapsed time of I/O during recovery	
recovery array reads	8	Number of reads performed during recovery	
recovery blocks read	8	Number of blocks read during recovery	
recovery blocks read for lost write detection	8	Number of blocks read for lost write checks during recovery.	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
recovery blocks skipped lost write checks	8	Number of Block Read Records that skipped the lost write check during recovery.	
recursive calls	1	Number of recursive calls generated at both the user and system level. Oracle maintains tables used for internal processing. When Oracle needs to make a change to these tables, it internally generates an internal SQL statement, which in turn generates a recursive call.	
recursive cpu usage	1	Total CPU time used by non-user calls (recursive calls). Subtract this value from "CPU used by this session" to determine how much CPU time was used by the user calls.	
redo blocks checksummed by FG (exclusive)	2	Number of exclusive redo blocks that were checksummed by the generating foreground processes. An exclusive redo block is the one whose entire redo content belongs to a single redo entry.	
redo blocks checksummed by LGWR	2	Number of redo blocks that were checksummed by the LGWR.	
redo blocks written	2	Total number of redo blocks written. This statistic divided by "redo writes" equals number of blocks per write.	
redo buffer allocation retries	2	Total number of retries necessary to allocate space in the redo buffer. Retries are needed either because the redo writer has fallen behind or because an event such as a log switch is occurring.	
redo entries	2	Number of times a redo entry is copied into the redo log buffer	
redo entries for lost write detection	2	Number of times a Block Read Record is copied into the log buffer.	
redo log space requests	2	Number of times the active log file is full and Oracle must wait for disk space to be allocated for the redo log entries. Such space is created by performing a log switch. Log files that are small in relation to the size of the SGA or the commit rate of the work load can cause problems. When the log switch occurs, Oracle must ensure that all committed dirty buffers are written to disk before switching to a new log file. If you have a large SGA full of dirty buffers and small redo log files, a log switch must wait for DBWR to write dirty buffers to disk before continuing. Also examine the **log file space** and **log file space switch** wait events in `V$SESSION_WAIT`	
redo log space wait time	2	Total time waited in centiseconds for available space in the redo log buffer. See also"redo log space requests"	Y
redo ordering marks	2	Number of times that a system change number was allocated to force a redo record to have a higher SCN than a record generated in another thread using the same block	
redo size	2	Total amount of redo generated in bytes	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
redo size for lost write detection	2	Total amount of Block Read Records generated in bytes.	
redo synch time	8	Elapsed time of all "redo synch writes" calls in 10s of milliseconds	Y
redo synch writes	8	Number of times the redo is forced to disk, usually for a transaction commit. The log buffer is a circular buffer that LGWR periodically flushes. Usually, redo that is generated and copied into the log buffer need not be flushed out to disk immediately.	
redo wastage	2	Number of bytes wasted because redo blocks needed to be written before they are completely full. Early writing may be needed to commit transactions, to be able to write a database buffer, or to switch logs.	
redo write broadcast ack count	2	Number of times a commit broadcast acknowledgment has not been received by the time when the corresponding log write is completed. This is only for Oracle RAC.	
redo write broadcast ack time	2	Total amount of the latency associated with broadcast on commit beyond the latency of the log write (in microseconds). This is only for Oracle RAC.	Y
redo write time	2	Total elapsed time of the write from the redo log buffer to the current redo log file in 10s of milliseconds	Y
redo writes	2	Total number of writes by LGWR to the redo log files. "redo blocks written" divided by this statistic equals the number of blocks per write	
rollback changes - undo records applied	128	Number of undo records applied to user-requested rollback changes (not consistent-read rollbacks)	
rollbacks only - consistent read gets	128	Number of consistent gets that require only block rollbacks, no block cleanouts. **See Also:** "consistent gets"	
rows fetched via callback	64	Rows fetched via callback. Useful primarily for internal debugging purposes.	
scheduler wait time	1	The total wait time (in microseconds) for waits that belong to the Scheduler wait class	
SCN increments due to another database	128	SCN increments due to communication with another database	
serializable aborts	1	Number of times a SQL statement in a serializable isolation level had to terminate	
session connect time	1	The connect time for the session in 10s of milliseconds. This value is useful only in `V$SESSTAT`. It is the wall clock time since the logon to this session occurred.	Y
session cursor cache count	64	Total number of cursors cached. This statistic is incremented only if `SESSION_CACHED_CURSORS` > 0. This statistic is the most useful in `V$SESSTAT`. If the value for this statistic in `V$SESSTAT` is close to the setting of the `SESSION_CACHED_CURSORS` parameter, the value of the parameter should be increased.	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
session cursor cache hits	64	Number of hits in the session cursor cache. A hit means that the SQL (including recursive SQL) or PL/SQL statement did not have to be reparsed. Subtract this statistic from "parse count (total)" to determine the real number of parses that occurred.	
session logical reads	1	The sum of "db block gets" plus "consistent gets". This includes logical reads of database blocks from either the buffer cache or process private memory.	
session logical reads - IM	128	Number of database blocks read from the IM column store (number of blocks in IMCU - number of blocks with invalid rows)	
session pga memory	1	Current PGA size for the session. Useful only in `V$SESSTAT`; it has no meaning in `V$SYSSTAT`.	
session pga memory max	1	Peak PGA size for the session. Useful only in `V$SESSTAT`; it has no meaning in `V$SYSSTAT`.	
session stored procedure space	1	Amount of memory this session is using for stored procedures	
session uga memory	1	Current UGA size for the session. Useful only in `V$SESSTAT`; it has no meaning in `V$SYSSTAT`.	
session uga memory max	1	Peak UGA size for a session. Useful only in `V$SESSTAT`; it has no meaning in `V$SYSSTAT`.	
shared hash latch upgrades - no wait	8	A shared hash latch upgrade is when a hash latch is upgraded from shared mode to exclusive mode. This statistic displays the number of times the upgrade completed immediately.	
shared hash latch upgrades - wait	8	A shared hash latch upgrade is when a hash latch is upgraded from shared mode to exclusive mode. This statistics displays the number of times the upgrade did not complete immediately.	
shared io pool buffer get failure	128	Number of unsuccessful buffer gets from the shared I/O pool from instance startup time.	
shared io pool buffer get success	128	Number of successful buffer gets from the shared I/O pool from instance startup time.	
slave propagated tracked transactions	128	Number of transactions modifying tables enabled for flashback data archive which were archived by a worker process	
sorts (disk)	64	Number of sort operations that required at least one disk write Sorts that require I/O to disk are quite resource intensive. Try increasing the size of the initialization parameter `SORT_AREA_SIZE`. For more information, see "SORT_AREA_SIZE".	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
sorts (memory)	64	Number of sort operations that were performed completely in memory and did not require any disk writes You cannot do much better than memory sorts, except maybe no sorts at all. Sorting is usually caused by selection criteria specifications within table join SQL operations.	
sorts (rows)	64	Total number of rows sorted	
SQL*Net roundtrips to/from client	1	Total number of Oracle Net Services messages sent to and received from the client	
SQL*Net roundtrips to/from dblink	1	Total number of Oracle Net Services messages sent over and received from a database link	
summed dirty queue length	8	The sum of the dirty LRU queue length after every write request. Divide by **write requests** to get the average queue length after write completion.	
switch current from pmem	8	Number of times the CURRENT PMEM block moved to a DRAM buffer, leaving a CR block in the original PMEM buffer. This happens when one Oracle process pins a CURRENT PMEM buffer for read, and another Oracle process wants to pin the same buffer for modification. The latter process clones the PMEM buffer into a new DRAM buffer for modification, while converting the original PMEM current buffer into a PMEM CR buffer.	
switch current to new buffer	8	Number of times the CURRENT block moved to a different buffer, leaving a CR block in the original buffer	
table fetch by rowid	64	Number of rows that are fetched using a ROWID (usually recovered from an index) This occurrence of table scans usually indicates either non-optimal queries or tables without indexes. Therefore, this statistic should increase as you optimize queries and provide indexes in the application.	
table fetch continued row	64	Number of times a chained or migrated row is encountered during a fetch Retrieving rows that span more than one block increases the logical I/O by a factor that corresponds to the number of blocks than need to be accessed. Exporting and re-importing may eliminate this problem. Evaluate the settings for the storage parameters PCTFREE and PCTUSED. This problem cannot be fixed if rows are larger than database blocks (for example, if the `LONG` data type is used and the rows are extremely large).	
table scan blocks gotten	64	During scanning operations, each row is retrieved sequentially by Oracle. This statistic counts the number of blocks encountered during the scan. This statistic tells you the number of database blocks that you had to get from the buffer cache for the purpose of scanning. Compare this value with the value of "consistent gets" to determine how much of the consistent read activity can be attributed to scanning.	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
table scan disk IMC fallback	128	Number of rows fetched from the buffer cache because they were not present in the IM column store (in a scan that was otherwise performed in memory)	
table scan disk non-IMC rows gotten	128	Number of rows fetched during non-In-Memory scan	
table scan rows gotten	64	Number of rows that are processed during scanning operations	
table scans (cache partitions)	64	Number of range scans performed on tables that have the CACHE option enabled	
table scans (direct read)	64	Number of table scans performed with direct read (bypassing the buffer cache)	
table scans (IM)	128	Number of segments / granules scanned using In-Memory	
table scans (long tables)	64	Long (or conversely short) tables can be defined as tables that do not meet the short table criteria as described in "table scans (short tables)"	
table scans (rowid ranges)	64	During parallel query, the number of table scans conducted with specified ROWID ranges	
table scans (short tables)	64	Long (or conversely short) tables can be defined by optimizer hints coming down into the row source access layer of Oracle. The table must have the CACHE option set.	
tracked rows	128	Number of rows modified in tables enabled for flashback data archive	
tracked transactions	128	Number of transactions which modified a table enabled for flashback data archive	
transaction lock background get time	128	Useful only for internal debugging purposes	
transaction lock background gets	128	Useful only for internal debugging purposes	
transaction lock foreground requests	128	Useful only for internal debugging purposes	
transaction lock foreground wait time	128	Useful only for internal debugging purposes	
transaction rollbacks	128	Number of transactions being successfully rolled back	
transaction tables consistent read rollbacks	128	Number of times rollback segment headers are rolled back to create consistent read blocks	
transaction tables consistent reads - undo records applied	128	Number of undo records applied to transaction tables that have been rolled back for consistent read purposes	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
txns rollback priority_txns_high_wait_target	384	Total number of times a LOW or MEDIUM priority transaction was rolled back by the Priority Transactions feature because the wait time specified by the PRIORITY_TXNS_HIGH_WAIT_TARGET initialization parameter was exceeded for a HIGH priority transaction This statistic is updated when the Priority Transactions feature is enabled, that is, when the PRIORITY_TXNS_MODE initialization parameter is set to ROLLBACK.	
txns rollback priority_txns_medium_wait_target	384	Total number of times a LOW priority transaction was rolled back by the Priority Transactions feature because the wait time specified by the PRIORITY_TXNS_MEDIUM_WAIT_TARGET initialization parameter was exceeded for a MEDIUM priority transaction This statistic is updated when the Priority Transactions feature is enabled, that is, when the PRIORITY_TXNS_MODE initialization parameter is set to ROLLBACK.	
txns track mode priority_txns_high_wait_target	384	Total number of times a LOW or MEDIUM priority transaction would potentially be rolled back by the Priority Transactions feature because the wait time specified by the PRIORITY_TXNS_HIGH_WAIT_TARGET initialization parameter was exceeded for a HIGH priority transaction This statistic is updated when the Priority Transactions feature is running in tracking mode, that is, when the PRIORITY_TXNS_MODE initialization parameter is set to TRACK.	
txns track mode priority_txns_medium_wait_target	384	Total number of times a LOW priority transaction would potentially be rolled back by the Priority Transactions feature because the wait time specified by the PRIORITY_TXNS_MEDIUM_WAIT_TARGET initialization parameter was exceeded for a MEDIUM priority transaction This statistic is updated when the Priority Transactions feature is running in tracking mode, that is, when the PRIORITY_TXNS_MODE initialization parameter is set to TRACK.	
user calls	1	Number of user calls such as login, parse, fetch, or execute When determining activity, the ratio of user calls to RPI calls, give you an indication of how much internal work gets generated because of the type of requests the user is sending to Oracle.	

Table E-1 (Cont.) Database Statistics Descriptions

Name	Class	Description	TIMED_STATISTICS
user commits	1	Number of user commits. When a user commits a transaction, the redo generated that reflects the changes made to database blocks must be written to disk. Commits often represent the closest thing to a user transaction rate.	
user I/O wait time	1	The total wait time (in centiseconds) for waits that belong to the User I/O wait class	
user rollbacks	1	Number of times users manually issue the `ROLLBACK` statement or an error occurs during a user's transactions	
very large tracked transactions	128	For tables tracked by flashback data archive, number of transactions modifying those tables which are very large in terms of size or number of changes	
write clones created in background	8	Number of times a background or foreground process clones a `CURRENT` buffer that is being written. The clone becomes the new, accessible `CURRENT` buffer, leaving the original buffer (now the clone) to complete writing.	
write clones created in foreground	8	Number of times a background or foreground process clones a `CURRENT` buffer that is being written. The clone becomes the new, accessible `CURRENT` buffer, leaving the original buffer (now the clone) to complete writing.	

F

Background Processes

An Oracle Database **background process** is defined as any process that is listed in `V$PROCESS` and has a non-null value in the `PNAME` column.

Table F-1 describes Oracle Database background processes.

The External Properties column lists the type of instance in which the process runs. If the process is specific to a particular feature, then the column names the feature.

> **Note:**
>
> When the `THREADED_EXECUTION` initialization parameter is set to `TRUE` on Linux and UNIX, the `DBW`, `PMON`, `PSP`, and `VKTM` background processes run as operating system processes, and the other background processes run as operating system threads.
>
> See "THREADED_EXECUTION" for more information about the `THREADED_EXECUTION` initialization parameter.

Table F-1 Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
ABMR	Auto BMR Background Process	Coordinates execution of tasks such as filtering duplicate block media recovery requests and performing flood control	When a process submits a block media recovery request to ABMR, it dynamically spawns worker processes (BMR*n*) to perform the recovery. ABMR and BMR*n* terminate after being idle for a long time. **See Also:** *Oracle Database Backup and Recovery User's Guide*	Database instances
ACFS	Oracle Advanced Cluster File System (Oracle ACFS) CSS Process	Tracks the cluster membership in CSS and informs the file system driver of membership changes	The ACFS process delivers CSS membership changes to the cluster file system. These membership changes are required for the file system to maintain file system consistency within the cluster.	Oracle ASM instances, Oracle RAC
ACMS	Atomic Control File to Memory Service Process	Coordinates consistent updates to a control file resource with its SGA counterpart on all instances in an Oracle RAC environment	The ACMS process works with a coordinating caller to ensure that an operation is executed on every instance in Oracle RAC despite failures. ACMS is the process in which a distributed operation is called. As a result, this process can exhibit a variety of behaviors. In general, ACMS is limited to small, nonblocking state changes for a limited set of cross-instance operations.	Database instances, Oracle RAC
AMB*n*	**See** ASMB, AMB*n*			

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
APnn	Replication Apply Process Coordinator Process	Obtains transactions from the reader server and passes them to apply servers	The coordinator process name is APnn, where nn can include letters and numbers. For more information about the coordinator process, see V$XSTREAM_APPLY_COORDINATOR for XStream and V$GG_APPLY_COORDINATOR for Oracle GoldenGate. **See Also:** *Oracle Database XStream Guide*	Database instances, Logical Standby, XStream Inbound servers, XStream Outbound servers, GoldenGate Integrated Replicat
AQPC	AQ Process Coordinator	Per instance AQ global coordinator	AQPC is responsible for performing administrative tasks for AQ Primary Class Processes including commands like starting, stopping, and other administrative tasks. This process is automatically started on instance startup.	Database instances Advanced Queueing
ARB0	ASM Rebalance Process	Rebalances data extents within an Oracle ASM disk group	ARB0 uses the value of the ASM_POWER_LIMIT initialization parameter for the Oracle ASM instance as the maximum power for disk rebalancing.	Oracle ASM instances
ARC*n*	Archiver Process	Copies the redo log files to archival storage when they are full or an online redo log switch occurs	ARC*n* processes exist only when the database is in ARCHIVELOG mode and automatic archiving is enabled, in which case ARC*n* automatically archives online redo log files. LGWR cannot reuse and overwrite an online redo log group until it has been archived. The database starts multiple archiver processes as needed to ensure that the archiving of filled online redo logs does not fall behind. Possible processes are ARC0-ARC9 and ARCa-ARCt. The LOG_ARCHIVE_MAX_PROCESSES initialization parameter specifies the number of ARC*n* processes that the database initially invokes. **See Also:** *Oracle Database Concepts* and *Oracle Database Administrator's Guide*	Database instances
ARS*n*	ASM Recovery Worker Process	Recovers ASM transactional operations	The ASM RBAL background process coordinates and spawns one or more of these worker processes to recover terminated ASM transactional operations. These processes run only in the Oracle ASM instance. Possible processes are ARS0-ARS9.	Oracle ASM instances

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
ASMB, AMB*n*	ASM Background Process	Communicates with an Oracle ASM instance, managing storage and providing statistics	In a database instance, the ASMB and AMB*n* processes enable the database instance to connect to an Oracle ASM instance in order to access Oracle ASM disk groups. Possible processes are ASMB and AMB1-AMB3. In an Oracle ASM instance, the ASMB process runs when the ASMCMD `cp` command runs, or when a database instance first starts if the server parameter file is stored in Oracle ASM. ASMB also runs with Oracle Cluster Registry on Oracle ASM. The only possible process is ASMB; AMB*n* processes do not run in Oracle ASM instances. In an Oracle IOServer (IOS) instance, the ASMB process enables the IOS instance to connect to an Oracle ASM instance in order to access Oracle ASM disk groups. The only possible process is ASMB; AMB*n* processes do not run in IOS instances.	Database instances, Oracle ASM instances, Oracle IOServer (IOS) instances
AS*nn*	Replication Apply Reader or Apply Server	Computes dependencies between logical change records (LCRs) and assembles messages into transactions (Reader Server) Applies LCRs to database objects or passes LCRs and user messages to their appropriate apply handlers (Apply Server)	When the reader server finishes computing dependencies between LCRs and assembling transactions, it returns the assembled transactions to the coordinator process. Query `V$STREAMS_APPLY_READER`, `V$XSTREAM_APPLY_READER`, and `V$GG_APPLY_READER` for information about the reader server background process. An apply server receives the transactions from the coordinator background process, and either applies database changes in LCRs or sends LCRs or messages to apply handlers. Apply servers can also enqueue a queue. If an apply server encounters an error, then it then tries to resolve the error with a user-specified conflict handler or error handler. If an apply server cannot resolve an error, then it rolls back the transaction and places the entire transaction, including all of its messages, in the error queue. When an apply server commits a completed transaction, this transaction has been applied. When an apply server places a transaction in the error queue and commits, this transaction also has been applied. Query `V$STREAMS_APPLY_SERVER` for information about the apply server background process. For XStream Inbound servers, query `V$XSTREAM_APPLY_SERVER`. For GoldenGate Integrated Replicat, query `V$GG_APPLY_SERVER`. The coordinator process name is AS*nn*, where *nn* can include letters and numbers.	Database instances, XStream Outbound servers, XStream Inbound servers, GoldenGate Integrated Replicat

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
BMR*n*	Automatic Block Media Recovery Worker Pool Process	Fetches blocks from a real-time readable standby database	When a process submits a block media recovery request to ABMR, it dynamically spawns worker processes (BMR*n*) to perform the recovery. BMR*n* processes fetch blocks from a real-time readable standby database. ABMR and BMR*n* terminate after being idle for a long time. **See Also:** *Oracle Database Backup and Recovery User's Guide*	Database instances
B*nnn*	ASM Blocking Worker Process for GMON	Performs maintenance actions on Oracle ASM disk groups	B*nnn* performs actions that require waiting for resources on behalf of GMON. GMON must be highly available and cannot wait. A B*nnn* worker is spawned when a disk is taken offline in an Oracle ASM disk group. Offline timer processing and drop of the disk are performed in this worker. Up to five process (B000 to B004) can exist depending on the load.	Oracle ASM instances
BW*nn*	Database Writer Process	Writes modified blocks from the database buffer cache to the data files	See the **Long Description** for the DBW*n* process in this table for more information about the BW*nn* process.	Database instances
CJQ0	Job Queue Coordinator Process	Selects jobs that need to be run from the data dictionary and spawns job queue worker processes (J*nnn*) to run the jobs	CJQ0 is automatically started and stopped as needed by Oracle Scheduler. The `JOB_QUEUE_PROCESSES` initialization parameter specifies the maximum number of processes that can be created for the execution of jobs. CJQ0 starts only as many job queue processes as required by the number of jobs to run and available resources. **See Also:** *Oracle Database Concepts* and *Oracle Database Administrator's Guide*	Database instances
CKPT	Checkpoint Process	Signals DBW*n* at checkpoints and updates all the data files and control files of the database to indicate the most recent checkpoint	At specific times CKPT starts a checkpoint request by messaging DBW*n* to begin writing dirty buffers. On completion of individual checkpoint requests, CKPT updates data file headers and control files to record most recent checkpoint. CKPT checks every three seconds to see whether the amount of memory exceeds the value of the `PGA_AGGREGATE_LIMIT` initialization parameter, and if so, takes the action described in "PGA_AGGREGATE_LIMIT". **See Also:** *Oracle Database Concepts*	Database instances, Oracle ASM instances
CL*nn*	Cleanup Worker Process	Performs cleanup of terminated processes	Cleanup workers assist in the cleanup of terminated processes and terminated sessions. The number of workers will be proportional to the amount of cleanup work to be done and the current efficiency of cleanup.	Database instances, Oracle ASM instances

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
CLG	Persistent Cluster Flash Cache Background Process	For Oracle Data Appliance only, this process performs actions related to recovery of a terminated instance's database flash cache	For Oracle Data Appliance only, in the event of an instance crash, the running instance will recover the crashed instance's database flash cache. The CLG process will perform actions related to scanning the crashed instance's database flash cache and claim flash blocks mastered by the crashed instance.	Database instances, Oracle RAC
CLMN	Cleanup Main Process	Performs cleanup of terminated processes, terminated sessions, terminated transactions, and terminated network connections	CLMN periodically performs cleanup of all the following: terminated processes, terminated sessions, transactions, network connections, idle sessions, detached transactions, and detached network connections that have exceeded their idle timeout.	Database instances, Oracle ASM instances
CP*nn*	Replication Capture Process	Captures database changes from the redo log by using the infrastructure of LogMiner	The capture process name is CP*nn*, where *nn* can include letters and numbers. The underlying LogMiner process name is MS*nn*, where *nn* can include letters and numbers. The capture process includes one reader server that reads the redo log and divides it into regions, one or more preparer servers that scan the redo log, and one builder server that merges redo records from the preparer servers. Each reader server, preparer server, and builder server is a process. Query the `V$XSTREAM_CAPTURE` and `V$GOLDENGATE_CAPTURE` views for information about this background process. **See Also:***Oracle Database XStream Guide*	Database instances, XStream Outbound Servers
CR*nn*	LMS CR Worker Process	Offloads the work from LMS so that blocks that require lots of UNDO to be applied do not block the LMS. Such requests are passed on to the worker so that the LMS is not stalled	There can be a maximum of eight CR processes per LMS process, with names from CR00 to CR07. Each LMS has its own set with similar name. The CR*nn* processes are threads and the process ID part will be the same as the owning LMS's process ID. The names for CRnn processes will have the format CR0*n*_<spawning process id>_<thread id>.	Oracle RAC
CS*nn*	I/O Calibration Process	Issues I/Os to storage as part of storage calibration.	CS*nn* worker processes are started on execution of the `DBMS_RESOURCE_MANAGER.CALIBRATE_IO()` procedure. There is one worker process per CPU on each node of the database.	Database instances, Oracle RAC
CTWR	Change Tracking Writer Process	Tracks changed data blocks as part of the Recovery Manager block change tracking feature	CTWR tracks changed blocks as redo is generated at a primary database and as redo is applied at a standby database. The process is slightly different depending on the type of database. **See Also:** *Oracle Database Backup and Recovery User's Guide*	Database instances

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
CX*nn*	Replication Capture Worker Process	Sends captured LCRs to a receiver, such as an XStream Outbound Server	The capture worker process name is CX*nn*, where *nn* can include letters and numbers.	Database instances, XStream Outbound Server
DBRM	Database Resource Manager Process	Sets resource plans and performs other tasks related to the Database Resource Manager	If a resource plan is not enabled, then this process is idle. **See Also:** *Oracle Database Administrator's Guide*	Database instances
DBW*n*	Database Writer Process	Writes modified blocks from the database buffer cache to the data files	The primary responsibility of the Database Writer Process is to write data blocks to disk. It also handles checkpoints, file open synchronization, and logging of Block Written records. In many cases the blocks that the Database Writer Process writes are scattered throughout the disk. Thus, the writes tend to be slower than the sequential writes performed by LGWR. The Database Writer Process performs multiblock writes when possible to improve efficiency. The number of blocks written in a multiblock write varies by operating system. The `DB_WRITER_PROCESSES` initialization parameter specifies the number of Database Writer Processes. There can be 1 to 100 Database Writer Processes. The names of the first 36 Database Writer Processes are DBW0-DBW9 and DBWa-DBWz. The names of the 37th through 100th Database Writer Processes are BW36-BW99. The database selects an appropriate default setting for the `DB_WRITER_PROCESSES` parameter or adjusts a user-specified setting based on the number of CPUs and processor groups. **See Also**: "DB_WRITER_PROCESSES"	Database instances
DIA0	Diagnostic Process	Detects and resolves hangs and deadlocks		Database instances, Oracle ASM instances
DIAG	Diagnostic Capture Process	Performs diagnostic dumps	DIAG performs diagnostic dumps requested by other processes and dumps triggered by process or instance termination. In Oracle RAC, DIAG performs global diagnostic dumps requested by remote instances.	Database instances, Oracle ASM instances
DM*nn*	Data Pump Control Job Process	Coordinates the Data Pump job tasks performed by Data Pump worker processes and handles client interactions	The Data Pump control job process is started during job creation and coordinates all tasks performed by the Data Pump job. It handles all client interactions and communication, establishes all job contexts, and coordinates all worker process activities on behalf of the job.	Database instances, Data Pump

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
DMON	Data Guard Broker Monitor Process	Manages and monitors a database that is part of a Data Guard broker configuration	When you start the Data Guard broker, a DMON process is created. DMON runs for every database instance that is managed by the broker. DMON interacts with the local database and the DMON processes of the other databases to perform the requested function. DMON also monitors the health of the broker configuration and ensures that every database has a consistent description of the configuration. DMON maintains profiles about all database objects in the broker configuration in a binary configuration file. A copy of this file is maintained by the DMON process for each of the databases that belong to the broker configuration. The process is created when the `DG_BROKER_START` initialization parameter is set to `true`. **See Also:** *Oracle Data Guard Broker*	Database instances, Data Guard
D*nnn*	Dispatcher Process	Performs network communication in the shared server architecture	In the shared server architecture, clients connect to a dispatcher process, which creates a virtual circuit for each connection. When the client sends data to the server, the dispatcher receives the data into the virtual circuit and places the active circuit on the common queue to be picked up by an idle shared server. The shared server then reads the data from the virtual circuit and performs the database work necessary to complete the request. When the shared server must send data to the client, the server writes the data back into the virtual circuit and the dispatcher sends the data to the client. After the shared server completes the client request, the server releases the virtual circuit back to the dispatcher and is free to handle other clients. Several initialization parameters relate to shared servers. The principal parameters are: `DISPATCHERS`, `SHARED_SERVERS`, `MAX_SHARED_SERVERS`, `LOCAL_LISTENER`, `REMOTE_LISTENER`. **See Also:** *Oracle Database Concepts*	Database instances, shared servers
DSKM	Worker Diskmon Process	Acts as the conduit between the database, Oracle ASM instances, and the Primary Diskmon daemon to communicate information to Exadata storage	This process is active only if Exadata Storage is used. DSKM performs operations related to Exadata I/O fencing and Exadata cell failure handling.	Oracle ASM instances, Exadata
DW*nn*	Data Pump Worker Process	Performs Data Pump tasks as assigned by the Data Pump control job process	The Data Pump worker process is responsible for performing tasks that are assigned by the Data Pump control job process, such as the loading and unloading of metadata and data.	Database instances

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
EMNC	EMON Coordinator Process	Coordinates database event management and notifications	EMNC is a primary background process that coordinates event management and notification activity in the database, including Streams Event Notifications, Continuous Query Notifications, and Fast Application Notifications.	Database instances
E*nnn*	EMON Worker Process	Performs database event management and notifications	The database event management and notification load is distributed among the EMON worker processes. These processes work on the system notifications in parallel, offering a capability to process a larger volume of notifications, a faster response time, and a lower shared memory use for staging notifications.	Database instances
FBDA	Flashback Data Archiver Process	Archives historical rows for tracked tables into flashback data archives and manages archive space, organization, and retention	When a transaction that modifies a tracked table commits, FBDA stores the pre-image of the rows in the archive. FBDA maintains metadata on the current rows and tracks how much data has been archived. FBDA is also responsible for automatically managing the flashback data archive for space, organization (partitioning tablespaces), and retention. FBDA also keeps track of how far the archiving of tracked transactions has progressed. **See Also:** *Oracle Database Development Guide*	Database instances
FD*nn*	Oracle ASM Stale FD Cleanup Worker Process	Cleans up Oracle ASM stale file descriptors on foreground processes	This process cleans up Oracle ASM stale file descriptors on foreground processes if an Oracle ASM disk is globally closed.	Database and Oracle ASM instances
FENC	Fence Monitor Process	Processes fence requests for RDBMS instances which are using Oracle ASM instances	CSS monitors RDBMS instances which are connected to the Oracle ASM instance and constantly doing I/Os. When the RDBMS instance terminates due to a failure, all the outstanding I/O's from the RDBMS instance should be drained and any new I/O's rejected. FENC receives and processes the fence request from CSSD.	Oracle ASM instances
FMON	File Mapping Monitor Process	Manages mapping information for the Oracle Database file mapping interface	The `DBMS_STORAGE_MAP` package enables you to control the mapping operations. When instructed by the user, FMON builds mapping information and stores it in the SGA, refreshes the information when a change occurs, saves the information to the data dictionary, and restores it to the SGA at instance startup. FMON is started by the database whenever the `FILE_MAPPING` initialization parameter is set to `true`.	Database instances, Oracle ASM instances
FSFP	Data Guard Broker Fast Start Failover Pinger Process	Maintains fast-start failover state between the primary and target standby databases	FSFP is created when fast-start failover is enabled.	Database instances, Data Guard

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
GCR*n*	Global Conflict Resolution Worker Process	Performs synchronous tasks on behalf of LMHB	GCR*n* processes are transient workers that are started and stopped as required by LMHB to perform synchronous or resource intensive tasks.	Database instances, Oracle ASM instances, Oracle RAC
GCW*n*	GCR Monitor processes (LMHB)	GCR(DRF) monitor processes (LMHB)	Infrastructure helper processes for LMHB. Monitors the LMHB process for stalls, and restarts if necessary.	Database instances, Oracle ASM instances, Oracle RAC instances (prior to Oracle Database 23ai only)
GEN0	General Task Execution Process	Performs required tasks including SQL and DML		Database instances, Oracle ASM instances, Oracle ASM Proxy instances
GMON	ASM Disk Group Monitor Process	Monitors all mounted Oracle ASM disk groups	GMON monitors all the disk groups mounted in an Oracle ASM instance and is responsible for maintaining consistent disk membership and status information. Membership changes result from adding and dropping disks, whereas disk status changes result from taking disks offline or bringing them online.	Oracle ASM instances
GTX*n*	Global Transaction Process	Provides transparent support for XA global transactions in an Oracle RAC environment	These processes help maintain the global information about XA global transactions throughout the cluster. Also, the processes help perform two-phase commit for global transactions anywhere in the cluster so that an Oracle RAC database behaves as a single system to the externally coordinated distributed transactions. The `GLOBAL_TXN_PROCESSES` initialization parameter specifies the number of GTX*n* processes, where *n* is 0-9 or a-j. The database automatically tunes the number of these processes based on the workload of XA global transactions. You can disable these processes by setting the parameter to 0. If you try to run XA global transactions with these processes disabled, an error is returned. **See Also:** *Oracle Real Application Clusters Administration and Deployment Guide*	Database instances, Oracle RAC

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
I*nnn*	Disk and Tape I/O Worker Process	Serves as an I/O worker process spawned on behalf of DBWR, LGWR, or an RMAN backup session	I/O worker process can be configured on platforms where asynchronous I/O support is not available. These workers are started by setting the corresponding worker enable parameter in the server parameter file. The I/O workers simulate the asynchronous I/O behavior when the underlying platform does not have native support for asynchronous I/O.	Database instances
IMCO	In-Memory Coordinator	Initiates background population and repopulation of in-memory enabled objects	The IMCO background process initiates population (prepopulation) of in-memory enabled objects with priority LOW/MEDIUM/HIGH/CRITICAL. In-memory enabled objects with priority NONE will not be prepopulated but will be populated on demand via W*nnn* processes when queried. The IMCO background process can also initiate repopulation of in-memory objects. Starting with Oracle Database 19c, IMXT (In-Memory External Table) segments are dropped by the IMCO background process. In previous releases, IMXT segments were dropped by foreground processes.	Database instances
IMR0	Instance Membership Recovery Worker Process	Performs synchronous tasks on behalf of LMON	The IMR0 background process performs the Instance Member Recovery synchronous operations on behalf of LMON	Oracle RAC, Database instances, Oracle ASM instances
INSV	Data Guard Broker Instance Worker Process	Performs Data Guard broker communication among instances in an Oracle RAC environment	INSV is created when the `DG_BROKER_START` initialization parameter is set to `true`.	Database instances, Data Guard
IPC0	IPC Service Background Process	Common background server for basic messaging and RDMA primitives based on IPC (Inter-process communication) methods.	IPC0 handles very high rates of incoming connect requests, as well as, completing reconfigurations to support basic messaging and RDMA primitives over several transports such as UDP, RDS, InfiniBand and RC.	Oracle RAC
J*nnn*	Job Queue Worker Process	Executes jobs assigned by the job coordinator	Job worker processes are created or awakened by the job coordinator when it is time for a job to be executed. Job workers gather all the metadata required to run the job from the data dictionary. The worker processes start a database session as the owner of the job, execute triggers, and then execute the job. After the job is complete, the worker processes commit and then execute appropriate triggers and close the session. The worker can repeat this operation in case additional jobs need to be run.	Database instances

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
JP*n*	Java Patching Worker Process	Patches and updates the Java in the database classes	JP*n* patches and updates the Java in the database classes. It is only started for Oracle Real Application Clusters (Oracle RAC) databases, and one of the database instances is responsible for patching the Java in the database objects. For mulitenant container databases (CDBs), the process updates each pluggable database (PDB) individually. JP*n* is started automatically and does not require user intervention.	Oracle RAC
LCK*n*	Lock Process	Manages global enqueue requests and cross-instance broadcasts	The process handles all requests for resources other than data blocks. For examples, LCK*n* manages library and row cache requests. Possible processes are LCK0 and LCK1.	Database instances, Oracle ASM instances, Oracle RAC
LDD*n*	Global Enqueue Service Daemon Helper Worker	Helps the LMD*n* processes with various tasks	LDD*n* processes are worker processes spawned on demand by LMD*n* processes. They are spawned to help the dedicated LMD*n* processes with various tasks when certain workloads start creating performance bottlenecks. These worker processes are transient as they are started on demand and they can be shutdown when no longer needed. There can be up to 36 of these worker processes (LDD0-LDDz).	Database instances, Oracle ASM instances, Oracle RAC
LG*nn*	Log Writer Worker	Writes redo log	On multiprocessor systems, LGWR creates worker processes to improve the performance of writing to the redo log. LGWR workers are not used when there is a SYNC standby destination. Possible processes are LG00-LG99.	Database instances
LGWR	Log Writer Process	Writes redo entries to the online redo log	Redo log entries are generated in the redo log buffer of the system global area (SGA). LGWR writes the redo log entries sequentially into a redo log file. If the database has a multiplexed redo log, then LGWR writes the redo log entries to a group of redo log files. **See Also:** *Oracle Database Concepts* and *Oracle Database Administrator's Guide*	Database instances, Oracle ASM instances
LM*nn*	**See** LMSn, LMnn			
LMD*n*	Global Enqueue Service Daemon Process	Manages incoming remote resource requests from other instances	LMD*n* processes enqueue resources managed under Global Enqueue Service. In particular, they process incoming enqueue request messages and control access to global enqueues. They also perform distributed deadlock detections. There can be up to 36 of these processes (LMD0-LMDz).	Database instances, Oracle ASM instances, Oracle RAC

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
LMFC	Lock Manager Flash Cache Process	For Oracle Database Appliance only, performs actions related to recovery of a terminated instance's database flash cache.	For Oracle Database Appliance only, in the event of a instance crash, the running instance will recover the crashed instance's database flash cache. The LMFC process will perform actions related to scanning the crashed instance's database flash cache and claim flash blocks mastered by the crashed instance.	Database instances, Oracle RAC
LMHB	Global Cache/ Enqueue Service Heartbeat Monitor	Monitor the heartbeat of several processes	LMHB monitors the CKPT, DIA*n*, LCK*n*, LG*nn*, LGWR, LMD*n*, LMON, LMS*n* , and RMS*n* processes to ensure they are running normally without blocking or spinning.	Database instances, Oracle ASM instances, Oracle RAC
LMON	Global Enqueue Service Monitor Process	Monitors an Oracle RAC cluster to manage global resources	LMON maintains instance membership within Oracle RAC. The process detects instance transitions and performs reconfiguration of GES and GCS resources. **See Also:** *Oracle Real Application Clusters Administration and Deployment Guide*	Database instances, Oracle ASM instances, Oracle RAC
LMS*n*, LM*nn*	Global Cache Service Process	Manages resources and provides resource control among Oracle RAC instances	LMS*n* and LM*nn* processes maintain a lock database for Global Cache Service (GCS) and buffer cache resources. These processes receive, process, and send GCS requests, block transfers, and other GCS-related messages. There can be up to 100 of these processes, named as follows: LMS0-LMS9 LMSA-LMSZ LM10-LM19 LM1A-LM1Z LM20-LM29 LM2A-LM2R **See Also:** *Oracle Real Application Clusters Administration and Deployment Guide*	Database instances, Oracle ASM instances, Oracle RAC
LREG	Listener Registration Process	Registers the instance with the listeners	LREG notifies the listeners about instances, services, handlers, and endpoint.	Database instances, Oracle ASM instances, Oracle RAC
LSP0	Logical Standby Coordinator Process	Schedules transactions for Data Guard SQL Apply	LSP0 is the initial process created upon startup of Data Guard SQL Apply. In addition to managing LogMiner and Apply processes, LSP0 is responsible for maintaining inter-transaction dependencies and appropriately scheduling transactions with applier processes. LSP0 is also responsible for detecting and enabling run-time parameter changes for the SQL Apply product as a whole.	Database instances, Data Guard

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
LSP1	Logical Standby Dictionary Build Process	Performs a logical standby dictionary build on a primary database	The LSP1 process is spawned on a logical standby database that is intended to become the new primary database. A logical standby database becomes a primary database because of switchover or failover. The dictionary is necessary for logical standby databases to interpret the redo of the new primary database.	Database instances, Data Guard
LSP2	Logical Standby Set Guard Process	Determines which database objects will be protected by the database guard	The LSP2 process is created as needed during startup of SQL Apply to update the list of objects that are protected by the database guard.	Database instances, Data Guard
L*nnn*	Pooled Server Process	Handles client requests in Database Resident Connection Pooling	In Database Resident Connection Pooling, clients connect to a connection broker process. When a connection becomes active, the connection broker hands off the connection to a compatible pooled server process. The pooled server process performs network communication directly on the client connection and processes requests until the client releases the server. After being released, the connection is returned to the broker for monitoring, leaving the server free to handle other clients. **See Also:** *Oracle Database Concepts*	Database instances, Database Resident Connection Pooling
MARK	Mark AU for Resynchronization Coordinator Process	Marks ASM allocation units as stale following a missed write to an offline disk	MARK essentially tracks which extents require resynchronization for offline disks. This process runs in the database instance and is started when the database instance first begins using the Oracle ASM instance. If required, MARK can also be started on demand when disks go offline in the Oracle ASM redundancy disk group.	Database instances, Oracle ASM instances
MMAN	Memory Manager Process	Serves as the instance memory manager	This process performs the resizing of memory components on the instance.	Database instances, Oracle ASM instances
MMNL	Manageability Monitor Lite Process	Performs tasks relating to manageability, including active session history sampling and metrics computation	MMNL performs many tasks relating to manageability, including session history capture and metrics computation.	Database instances, Oracle ASM instances
MMON	Manageability Monitor Process	Performs or schedules many manageability tasks	MMON performs many tasks related to manageability, including taking Automatic Workload Repository snapshots and performing Automatic Database Diagnostic Monitor analysis.	Database instances, Oracle ASM instances

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
M*nnn*	Shared MMON Worker Process	Performs manageability tasks on behalf of MMON	The M*nnn* processes are a pool of worker processes that can be shared by multiple MZ*nn* processes. See the **Long Description** for MZ*nn* in this table for more information about the MZ*nn* processes.	Database instances, Oracle ASM instances
MRP0	Managed Standby Recovery Process	Coordinates the application of redo on a physical standby database	MRP0 is spawned at the start of redo apply on a physical standby database. This process handles the extraction of redo and coordinates the application of that redo on a physical standby database. **See Also:** *Oracle Data Guard Concepts and Administration*	Database instances, Data Guard
MS*nn*	LogMiner Worker Process	Reads redo log files and translates and assembles into transactions	Multiple MS*nn* processes can exists, where *n* is 0-9 or a-Z. A minimum of three MS*nn* processes work as a group to provide transactions to a LogMiner client, for example, a logical standby database or a database capture. There may be more than one such group, for example, multiple capture processes configured for either local or downstream capture in a database.	Database instances, Logical Standby, XStream Outbound servers, Oracle GoldenGate
MZ*nn*	Dedicated MMON Worker Process	Performs manageability tasks on behalf of MMON	MZ*nn* is a dedicated process for a single MMON worker action. It performs manageability tasks dispatched by MMON, which include taking Automatic Workload Repository snapshots and performing Automatic Database Diagnostic Monitor analysis.	Database instances, Oracle ASM instances
N*nnn*	Connection Broker Process	Monitors idle connections and hands off active connections in Database Resident Connection Pooling	In Database Resident Connection Pooling, clients connect to a connection broker process. When a connection becomes active, the connection broker hands off the connection to a compatible pooled server process. The pooled server process performs network communication directly on the client connection and processes requests until the client releases the server. After being released, the connection is returned to the broker for monitoring, leaving the server free to handle other clients. **See Also:** *Oracle Database Concepts*	Database instances, Database Resident Connection Pooling
NFS*n*	Direct NFS Dispatcher IO Worker Process	Performs direct NFS I/O for database processes	The dispatcher worker processes enable scaling of Direct NFS connections to a clustered NAS storage. These dedicated set of workers will be used to perform Direct NFS I/Os on behalf of database processes. The dispatcher processes are enabled by the `ENABLE_DNFS_DISPATCHER` initialization parameter. NFSn is spawned only if Direct NFS library is enabled for I/O to NFS servers. The number of worker processes spawned is based on the `CPU_COUNT` value. **See Also:** "ENABLE_DNFS_DISPATCHER"	Database instances

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
NSS*n*	Network Server SYNC Process	Transfers redo from current online redo logs to remote standby destinations configured for SYNC transport	NSS*n* can run as multiple processes, where *n* is 1-9 or A. **See Also:** *Oracle Data Guard Concepts and Administration*	Database instances, Data Guard
NSV*n*	Data Guard Broker NetSlave Process	Performs broker network communications between databases in a Data Guard environment	NSV*n* is created when a Data Guard broker configuration is enabled. There can be as many NSV*n* processes (where *n* is 0- 9 and A-U) created as there are databases in the Data Guard broker configuration.	Database instances, Data Guard
OCF*n*	ASM CF Connection Pool Process	Maintains a connection to the Oracle ASM instance for metadata operations		Database instances, Oracle ASM instances
OFSD	Oracle File Server Background Process	Serves file system requests submitted to an Oracle instance	This background process listens for new file system requests, both management (like mount, unmount, and export) and I/O requests, and executes them using Oracle threads.	Database instances, Oracle RAC
OF*nn*	Oracle File Server Background Process Thread	Serves file system requests submitted to an Oracle instance	This is a thread for the OFSD background process This background process thread is available only on Linux systems.	Database instances, Oracle RAC
O*nnn*	ASM Connection Pool Process	Maintains a connection to the Oracle ASM instance for metadata operations	O*nnn* worker processes are spawned on demand. These processes communicate with the Oracle ASM instance.	Database instances, Oracle ASM instances
PING	Interconnect Latency Measurement Process	Assesses latencies associated with communications for each pair of cluster instances	Every few seconds, the process in one instance sends messages to each instance. The message is received by PING on the target instance. The time for the round trip is measured and collected.	Database instances, Oracle ASM instances, Oracle RAC
PMAN	Process Manager	Manages several background processes including shared servers, pooled servers, and job queue processes	PMAN monitors, spawns, and stops the following as needed: • dispatcher and shared server processes • connection broker and pooled server processes for database resident connection pools • job queue processes • restartable background processes	Database instances, Oracle ASM instances, Oracle ASM Proxy instances

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
PMON	Process Monitor	Scans for terminated processes and coordinates cleanup	PMON periodically scans all processes to find any that have died in a nonstandard way. PMON is then responsible for coordinating cleanup performed by the CLMN process and the CL*nn* workers. **See Also:** *Oracle Database Concepts* and *Oracle Database Net Services Administrator's Guide*	Database instances, Oracle ASM instances, Oracle ASM Proxy instances
P*nnn*	Parallel Query Worker Process	Perform parallel execution of a SQL statement (query, DML, or DDL)	Parallel Query has two components: a foreground process that acts as query coordinator and a set of parallel workers (P*nnn*) that are background processes. These background processes are spawned or reused during the start of a parallel statement. They receive and perform units of work sent from the query coordinator. The maximum number of P*nnn* processes is controlled by the initialization parameter `PARALLEL_MAX_SERVERS`. Worker processes are numbered from 0 to the `PARALLEL_MAX_SERVERS` setting. If the query is a `GV$` query, then these background processes are numbered backward, starting from PPA7.	Database instances, Oracle ASM instances
PR*nn*	Parallel Recovery Process	Performs tasks assigned by the coordinator process performing parallel recovery	PR*nn* serves as a worker process for the coordinator process performing parallel media recovery and carries out tasks assigned by the coordinator. The default number of these processes is based on number of CPUs.	Database instances
PSP0	Process Spawner Process	Spawns Oracle background processes after initial instance startup		Database instances, Oracle ASM instances
PXMN	Parallel Execution Monitor	Spawns parallel server processes on local instances in an Oracle RAC environment for Query Coordinator in remote instances.		Database instances
QMNC	Non-sharded queue primary process	Monitors AQ	QMNC is the non-sharded queue primary process responsible for facilitating various background activities required by AQ: time management of messages, management of nonpersistent queues, cleanup of resources, and so on. QMNC dynamically spawns Q*nnn* processes as needed for performing these tasks. Note that if the `AQ_TM_PROCESSES` initialization parameter is set to 0, this process will not start. The database writes the following message to the alert log: `WARNING: AQ_TM_PROCESSES is set to 0. System might be adversely affected.`	Database instances Advanced Queueing

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
QM*nn*	AQ Primary Class Process	Per instance per AQ Primary Class Process	Each of this type of process represents a single class of work item such as AQ notification, queue monitors, and cross process.	Database instances Advanced Queueing
Q*nnn*	AQ Server Class Process	Per AQ Primary Class server process	Each server class process acts on behalf of an AQ primary class process. This relationship is maintained until the primary requires services of a particular service process. Once released, the server class processes are moved to a free server pool.	Database instances Advanced Queueing
R*nnn*	ASM Block Remap Worker Process	Remaps a block with a read error	A database instance reading from an Oracle ASM disk group can encounter an error during a read. If possible, Oracle ASM asynchronously schedules a R*nnn* worker process to remap this bad block from a mirror copy.	Oracle ASM instances
RBAL	ASM Rebalance Primary Process	Coordinates rebalance activity	In an Oracle ASM instance, it coordinates rebalance activity for disk groups. In a database instance, it manages Oracle ASM disk groups.	Database instances, Oracle ASM instances
RCBG	Result Cache Background Process	Handles result cache messages	This process is used for handling invalidation and other messages generated by server processes attached to other instances in Oracle RAC.	Database instances, Oracle RAC
RECO	Recoverer Process	Resolves distributed transactions that are pending because of a network or system failure in a distributed database	RECO uses the information in the pending transaction table to finalize the status of in-doubt transactions. At timed intervals, the local RECO attempts to connect to remote databases and automatically complete the commit or rollback of the local portion of any pending distributed transactions. All transactions automatically resolved by RECO are removed from the pending transaction table. **See Also:** *Oracle Database Concepts* and *Oracle Database Net Services Administrator's Guide*	Database instances
RL*nn*	ResetLogs Process	Clear online redo logs when performing open resetlogs and converting to physical standby	RL*nn* processes are spawned to clear online redo logs. These workers are terminated after the online redo logs are cleared, and the session does not persist. Possible processes are RL00-RL31.	Database instances
RM	RAT Masking Worker Process	Extracts and masks bind values from workloads like SQL tuning sets and DB Replay capture files	This background process is used with Data Masking and Real Application Testing.	Database instances
RMON	Rolling Migration Monitor Process	Manages the rolling migration procedure for an Oracle ASM cluster	The RMON process is spawned on demand to run the protocol for transitioning an ASM cluster in and out of rolling migration mode.	Oracle ASM instance, Oracle RAC

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
RMS*n*	Oracle RAC Management Process	Performs manageability tasks for Oracle RAC	RMS*n* performs a variety of tasks, including creating resources related to Oracle RAC when new instances are added to a cluster. **See Also:** *Oracle Real Application Clusters Administration and Deployment Guide*	Database instances, Oracle RAC
RP*nn*	Capture Processing Worker Process	Processes a set of workload capture files	RP*nn* are worker processes spawned by calling `DBMS_WORKLOAD_REPLAY.PROCESS_CAPTURE(capture_dir,parallel_level)`. Each worker process is assigned a set of workload capture files to process. Worker processes execute in parallel without needing to communicate with each other. After each process is finished processing its assigned files, it exits and informs its parent process. The number of worker processes is controlled by the `parallel_level` parameter of `DBMS_WORKLOAD_REPLAY.PROCESS_CAPTURE`. By default, `parallel_level` is null. Then, the number of worker processes is computed as follows: `SELECT VALUE FROM V$PARAMETER WHERE NAME='cpu_count';` When `parallel_level` is `1`, no worker processes are spawned.	Database instances
RPOP	Instant Recovery Repopulation Daemon	Responsible for re-creating and/or repopulating data files from snapshot files and backup files	The RPOP process is responsible for re-creating and repopulating data files from snapshots files. It works with the instant recovery feature to ensure immediate data file access. The local instance has immediate access to the remote snapshot file's data, while repopulation of the recovered primary data files happens concurrently. Any changes in the data are managed between the instance's DBW processes and RPOP to ensure the latest copy of the data is returned to the user.	Database instances
RS*nn*	Global Cache Service Remaster Process	Performs remastering for cluster reconfiguration and dynamic remastering	Each RS*nn* process is a worker process for LMS*n* to handle remastering work. They are also helper processes for LMS to handle non-critical work from global cache service. The RS*nn* processes were named RMV*n* in Oracle Database 12c and earlier releases.	Database instances, Oracle RAC
RSM0	Data Guard Broker Worker Process	Performs monitoring management tasks related to Data Guard on behalf of DMON	The process is created when a Data Guard broker configuration is enabled.	Database instances, Data Guard

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
RSMN	Remote Worker Monitor Process	Manages background worker process creation and communication on remote instances in Oracle RAC	This background process manages the creation of worker processes and the communication with their coordinators and peers. These background worker processes perform tasks on behalf of a coordinating process running in another cluster instance.	Database instances, Oracle RAC
RVWR	Recovery Writer Process	Writes flashback data to the flashback logs in the fast recovery area	RVWR writes flashback data from the flashback buffer in the SGA to the flashback logs. RVWR also creates flashback logs and performs some tasks for flashback log automatic management.	Database instances, Flashback Database
S*nnn*	Shared Server Process	Handles client requests in the shared server architecture	In the shared server architecture, clients connect to a dispatcher process, which creates a virtual circuit for each connection. When the client sends data to the server, the dispatcher receives the data into the virtual circuit and places the active circuit on the common queue to be picked up by an idle shared server. The shared server then reads the data from the virtual circuit and performs the database work necessary to complete the request. When the shared server must send data to the client, the server writes the data back into the virtual circuit and the dispatcher sends the data to the client. After the shared server completes the client request, the server releases the virtual circuit back to the dispatcher and is free to handle other clients. Several initialization parameters relate to shared servers. The principal parameters are: `DISPATCHERS`, `SHARED_SERVERS`, `MAX_SHARED_SERVERS`, `LOCAL_LISTENER`, `REMOTE_LISTENER`. **See Also:** *Oracle Database Concepts*	Database instances, shared servers
SA*nn*	SGA Allocator	Allocates SGA	A small fraction of SGA is allocated during instance startup. The SA*nn* process allocates the rest of SGA in small chunks. The process exits upon completion of SGA allocation. Possible processes are SA00-SAzz.	Database instances
SCC*n*	ASM Disk Scrubbing Worker Check Process	Performs Oracle ASM disk scrubbing check operation	SCC*n* acts as a worker process for SCRB and performs the checking operations. Possible processes are SCC0-SCC9.	Oracle ASM instances
SCM0	DLM Statistics Collection and Management Worker	Collects and manages statistics related to global enqueue service (GES) and global cache service (GCS)	The DLM Statistics Collection and Management worker (SCM0) is responsible for collecting and managing the statistics related to global enqueue service (GES) and global cache service (GCS). This worker exists only if DLM statistics collection is enabled.	Database instances

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
SCMN	Statistics Collection and Management	Main thread for a multithreaded process in a threaded Oracle RAC architecture	All other threads are spawned within the processes through SCMN, based on the requests in the instance. SCMN is an idle main thread, which waits for any requests, especially spawn threads, and takes care of them, along with performing periodic maintenance operations.	Oracle RAC
SCRB	ASM Disk Scrubbing Primary Process	Coordinates Oracle ASM disk scrubbing operations	SCRB runs in an Oracle ASM instance and coordinates Oracle ASM disk scrubbing operations.	Oracle ASM instances
SCR*n*	ASM Disk Scrubbing Worker Repair Process	Performs Oracle ASM disk scrubbing repair operation	SCR*n* acts as a worker process for SCRB and performs the repairing operations. Possible processes are SCR0-SCR9.	Oracle ASM instances
SCV*n*	ASM Disk Scrubbing Worker Verify Process	Performs Oracle ASM disk scrubbing verify operation	SCV*n* acts as a worker process for SCRB and performs the verifying operations. Possible processes are SCV0-SCV9.	Oracle ASM instances
SMCO	Space Management Coordinator Process	Coordinates the execution of various space management tasks	This background process coordinates the execution of various space management tasks, including proactive space allocation and space reclamation. SMCO dynamically spawns worker processes (W*nnn*) to implement these tasks.	Database instances
SMON	System Monitor Process	Performs critical tasks such as instance recovery and terminated transaction recovery, and maintenance tasks such as temporary space reclamation, data dictionary cleanup, and undo tablespace management	SMON performs many database maintenance tasks, including the following: • Reclaims space used by orphaned temporary segments • Maintains the undo tablespace by onlining, offlining, and shrinking the undo segments based on undo space usage statistics • Cleans up the data dictionary when it is in a transient and inconsistent state • Maintains the SCN to time mapping table used to support Oracle Flashback features In an Oracle RAC database, the SMON process of one instance can perform instance recovery for other instances that have failed. SMON is resilient to internal and external errors raised during background activities. **See Also:** *Oracle Database Concepts*	Database instances
SP	SPA Exec Worker	Analyzes single SQL statements sent from SQL Performance Analyzer (SPA)	Executions of SPA tasks created from a SQL tuning set use this worker to analyze the SQL statements of the SQL tuning set concurrently.	Database instances
SVCB	Service Background Process	Provides database service run-time load balancing and topology information to clients.	Every 30 seconds the process processes and publishes run-time load-balancing information and keeps the topology information current. This process is started only if Oracle Real Application Clusters (Oracle RAC) is enabled.	Oracle RAC

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
TEM*n*	ASM disk Test Error Emulation Process	Emulates I/O errors on Oracle ASM disks through named events	I/O errors can be emulated on Oracle ASM disk I/O through named events. The scope can be the process, instance, or even cluster. Optionally, a set of AUs can be chosen for error emulation.	Oracle ASM instances
TT*nn*	Redo Transport Worker Process	Ships redo from current online and standby redo logs to remote standby destinations configured for ASYNC transport	TT*nn* can run as multiple processes, where *nn* is 00 to ZZ. **See Also:** *Oracle Data Guard Concepts and Administration*	Database instances, Data Guard
U*nnn*	Container process for threads	Host processes where database processes execute as threads.	U*nnn* processes are database container operating system processes where database backgrounds processes like SMON, CJQ0, and database foreground processes run. The `V$PROCESS` view lists database processes running in these container processes. These container processes are created only when the `THREADED_EXECUTION` initialization parameter is set to `TRUE`. The number of these processes vary depending on the active database processes. On a host with multiple NUMA nodes, there will be at least one U*nnn* process per NUMA node. These processes are irrecoverable processes; if any of them is terminated, it will result in instance termination. These processes exit when the instance is shut down or terminated.	Database instances
VBG*n*	Volume Background Process	Communicates between the Oracle ASM instance and the operating system volume driver	VBG*n* handles messages originating from the volume driver in the operating system and sends them to the Oracle ASM instance. VBG*n* can run as multiple processes, where *n* is 0-9.	Oracle ASM instances, Oracle ASM Proxy instances
VDBG	Volume Driver Process	Forwards Oracle ASM requests to perform various volume-related tasks	VDBG handles requests to lock or unlock an extent for rebalancing, volume resize, disk offline, add or drop a disk, force and dismount disk group to the Dynamic Volume Manager driver.	Oracle ASM instances, Oracle ASM Proxy instances
VI*nn*	Volume I/O	Route ADVM volume I/O for ASM instances on compute nodes within an Exadata	These processes handle requests for I/Os targeted at storage not locally accessible. They are used for Exadata targeted storage as well. These background processes only start when an ASM Volume is created and set up to be used. One process will start for each NUMA node on target machines. Under normal operation on non-Exadata hardware and on Exadata hardware that is not utilizing ASM volumes, these processes will not be started. There can be up to 32 VI processes, and they are named sequentially from VI00 to VI31.	Oracle ASM Proxy instances

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
VKRM	Virtual Scheduler for Resource Manager Process	Serves as centralized scheduler for Resource Manager activity	VKRM manages the CPU scheduling for all managed Oracle processes. The process schedules managed processes in accordance with an active resource plan.	Database instances
VKTM	Virtual Keeper of Time Process	Provides a wall clock time and reference time for time interval measurements	VKTM acts as a time publisher for an Oracle instance. VKTM publishes two sets of time: a wall clock time using a seconds interval and a higher resolution time (which is not wall clock time) for interval measurements. The VKTM timer service centralizes time tracking and offloads multiple timer calls from other clients.	Database instances, Oracle ASM instances
VMB0	Volume Membership Process	Maintains cluster membership on behalf of the Oracle ASM volume driver	This process membership in the cluster as an I/O-capable client on behalf of the Oracle ASM volume driver.	Oracle ASM instances, Oracle ASM Proxy instances
VOSD	Virtual Operating System Daemon	Executes time-bound Oracle database service actions	This process is spawned on instance startup and is responsible for executing system service actions critical for the database.	Database instances, Oracle ASM instances, Oracle RAC
VUBG	Volume drive Umbilicus Background	Relays messages between Oracle ASM instance and Oracle ASM Proxy instance that is used by ADVM (for ACFS)		Oracle ASM instances, Oracle ASM Proxy instances

Table F-1 (Cont.) Background Processes

Name	Expanded Name	Short Description	Long Description	External Properties
W*nnn*	Space Management Worker Process	Performs various background space management tasks, including proactive space allocation and space reclamation	W*nnn* worker processes perform work on behalf of Space Management and on behalf of the Oracle Database In-Memory option. • When performing work on behalf of Space Management, W*nnn* processes are worker processes dynamically spawned by SMCO to perform space management tasks in the background. These tasks include preallocating space into locally managed tablespace and SecureFiles segments based on space usage growth analysis, and reclaiming space from dropped segments. After being started, the worker acts as an autonomous agent. After it finishes task execution, it automatically picks up another task from the queue. The process terminates itself after being idle for a long time. • When performing work on behalf of the Oracle Database In-Memory option, W*nnn* processes execute tasks for population or repopulation of objects that are enabled for the In-Memory column store (IM columns store), and tasks that drop in-memory segments when an object is disabled for the IM columns store. For in-memory population and repopulation, both the IMCO background process and foreground processes will utilize W*nnn* workers. W*nnn* processes are utilized by the IMCO background process for prepopulation of in-memory enabled objects with priority LOW/ MEDIUM/HIGH/CRITICAL, and for repopulation of in-memory objects. In-memory populate and repopulate tasks running on W*nnn* workers are also initiated from foreground processes in response to queries and DMLs that reference in-memory enabled objects.	Database instances
XDMG	Exadata Automation Manager	Initiates automation tasks involved in managing Exadata storage	XDMG monitors all configured Exadata cells for state changes, such as a bad disk getting replaced, and performs the required tasks for such events. Its primary tasks are to watch for when inaccessible disks and cells become accessible again, and to initiate the ASM ONLINE operation. The ONLINE operation is handled by XDWK.	Oracle ASM instances, Exadata
XDWK	Exadata Automation Manager	Performs automation tasks requested by XDMG	XDWK gets started when asynchronous actions such as ONLINE, DROP, and ADD an Oracle ASM disk are requested by XDMG. After a 5 minute period of inactivity, this process will shut itself down.	Oracle ASM instances, Exadata
X*nnn*	ASM Disk Expel Worker Process	Performs Oracle ASM post-rebalance activities	This process expels dropped disks after an Oracle ASM rebalance.	Oracle ASM instances

Index

A

ACTIVE_INSTANCE_COUNT initialization parameter, *2-30*
ADG_ACCOUNT_INFO_TRACKING initialization parameter, *2-31*
ADG_REDIRECT_DML initialization parameter, *2-32*
ALL_ALL_TABLES view, *3-8*
ALL_ANALYTIC_VIEW_ATTR_CLASS view, *3-14*
ALL_ANALYTIC_VIEW_ATTR_CLS view, *3-15*
ALL_ANALYTIC_VIEW_ATTR_CLS_AE view, *3-15*
ALL_ANALYTIC_VIEW_BAS_MEAS view, *3-16*
ALL_ANALYTIC_VIEW_BAS_MEAS_AE view, *3-16*
ALL_ANALYTIC_VIEW_BASE_MEAS view, *3-17*
ALL_ANALYTIC_VIEW_CALC_MEAS view, *3-18*
ALL_ANALYTIC_VIEW_CLASS view, *3-19*
ALL_ANALYTIC_VIEW_CLASS_AE view, *3-20*
ALL_ANALYTIC_VIEW_CLC_MEAS view, *3-21*
ALL_ANALYTIC_VIEW_CLC_MEAS_AE view, *3-21*
ALL_ANALYTIC_VIEW_COLUMNS view, *3-22*
ALL_ANALYTIC_VIEW_COLUMNS_AE view, *3-23*
ALL_ANALYTIC_VIEW_DIM_ATRS view, *3-25*
ALL_ANALYTIC_VIEW_DIM_ATRS_AE view, *3-25*
ALL_ANALYTIC_VIEW_DIM_ATTRS view, *3-26*
ALL_ANALYTIC_VIEW_DIM_CLASS view, *3-27*
ALL_ANALYTIC_VIEW_DIM_CLS view, *3-28*
ALL_ANALYTIC_VIEW_DIM_CLS_AE view, *3-28*
ALL_ANALYTIC_VIEW_DIMENSIONS view, *3-29*
ALL_ANALYTIC_VIEW_DIMS view, *3-30*
ALL_ANALYTIC_VIEW_DIMS_AE view, *3-30*
ALL_ANALYTIC_VIEW_FACT_COLS view, *3-32*
ALL_ANALYTIC_VIEW_FCT_COLS view, *3-32*
ALL_ANALYTIC_VIEW_FCT_COLS_AE view, *3-33*
ALL_ANALYTIC_VIEW_HIER_CLASS view, *3-33*
ALL_ANALYTIC_VIEW_HIER_CLS view, *3-34*
ALL_ANALYTIC_VIEW_HIER_CLS_AE view, *3-35*
ALL_ANALYTIC_VIEW_HIERS view, *3-36*
ALL_ANALYTIC_VIEW_HIERS_AE view, *3-36*
ALL_ANALYTIC_VIEW_KEYS view, *3-37*
ALL_ANALYTIC_VIEW_KEYS_AE view, *3-38*
ALL_ANALYTIC_VIEW_LEVEL_CLASS view, *3-39*
ALL_ANALYTIC_VIEW_LEVELS view, *3-40*
ALL_ANALYTIC_VIEW_LEVELS_AE view, *3-41*
ALL_ANALYTIC_VIEW_LVL_CLS view, *3-42*
ALL_ANALYTIC_VIEW_LVL_CLS_AE view, *3-42*
ALL_ANALYTIC_VIEW_LVLGRPS view, *3-43*
ALL_ANALYTIC_VIEW_LVLGRPS_AE view, *3-44*
ALL_ANALYTIC_VIEW_MEAS_CLASS view, *3-45*
ALL_ANALYTIC_VIEW_MEAS_CLS view, *3-46*
ALL_ANALYTIC_VIEW_MEAS_CLS_AE view, *3-46*
ALL_ANALYTIC_VIEWS view, *3-47*
ALL_ANALYTIC_VIEWS_AE view, *3-48*
ALL_ANNOTATION_VALUES view, *3-49*
ALL_ANNOTATIONS view, *3-50*
ALL_ANNOTATIONS_USAGE view, *3-50*
ALL_APPLY view, *3-51*
ALL_APPLY_CHANGE_HANDLERS view, *3-53*
ALL_APPLY_CONFLICT_COLUMNS view, *3-54*
ALL_APPLY_DML_CONF_HANDLERS view, *3-55*
ALL_APPLY_DML_HANDLERS view, *3-56*
ALL_APPLY_ENQUEUE view, *3-57*
ALL_APPLY_ERROR view, *3-57*
ALL_APPLY_ERROR_MESSAGES view, *3-59*
ALL_APPLY_EXECUTE view, *3-61*
ALL_APPLY_HANDLE_COLLISIONS view, *3-61*
ALL_APPLY_INSTANTIATED_GLOBAL view, *3-62*
ALL_APPLY_INSTANTIATED_OBJECTS view, *3-62*
ALL_APPLY_INSTANTIATED_SCHEMAS view, *3-63*
ALL_APPLY_KEY_COLUMNS view, *3-64*
ALL_APPLY_PARAMETERS view, *3-64*
ALL_APPLY_PROGRESS view, *3-65*

ALL_APPLY_REPERROR_HANDLERS view, 3-66
ALL_APPLY_TABLE_COLUMNS view, 3-67
ALL_ARGUMENTS view, 3-68
ALL_ASSEMBLIES view, 3-70
ALL_ASSOCIATIONS view, 3-71
ALL_ATTRIBUTE_DIM_ATTR_CLASS view, 3-72
ALL_ATTRIBUTE_DIM_ATTR_CLS view, 3-73
ALL_ATTRIBUTE_DIM_ATTR_CLS_AE view, 3-73
ALL_ATTRIBUTE_DIM_ATTRS view, 3-74
ALL_ATTRIBUTE_DIM_ATTRS_AE view, 3-75
ALL_ATTRIBUTE_DIM_CLASS view, 3-76
ALL_ATTRIBUTE_DIM_CLASS_AE view, 3-76
ALL_ATTRIBUTE_DIM_JN_PTHS view, 3-77
ALL_ATTRIBUTE_DIM_JN_PTHS_AE view, 3-78
ALL_ATTRIBUTE_DIM_JOIN_PATHS view, 3-78
ALL_ATTRIBUTE_DIM_KEYS view, 3-79
ALL_ATTRIBUTE_DIM_KEYS_AE view, 3-80
ALL_ATTRIBUTE_DIM_LEVEL_ATTRS view, 3-81
ALL_ATTRIBUTE_DIM_LEVELS view, 3-82
ALL_ATTRIBUTE_DIM_LEVELS_AE view, 3-83
ALL_ATTRIBUTE_DIM_LVL_ATRS view, 3-83
ALL_ATTRIBUTE_DIM_LVL_ATRS_AE view, 3-84
ALL_ATTRIBUTE_DIM_LVL_CLASS view, 3-85
ALL_ATTRIBUTE_DIM_LVL_CLS view, 3-85
ALL_ATTRIBUTE_DIM_LVL_CLS_AE view, 3-86
ALL_ATTRIBUTE_DIM_ORD_ATRS view, 3-86
ALL_ATTRIBUTE_DIM_ORD_ATRS_AE view, 3-87
ALL_ATTRIBUTE_DIM_ORDER_ATTRS view, 3-88
ALL_ATTRIBUTE_DIM_TABLES view, 3-89
ALL_ATTRIBUTE_DIM_TABLES_AE view, 3-90
ALL_ATTRIBUTE_DIMENSIONS view, 3-91
ALL_ATTRIBUTE_DIMENSIONS_AE view, 3-92
ALL_ATTRIBUTE_TRANSFORMATIONS view, 3-93
ALL_AUDIT_POLICIES view, 3-94
ALL_AUDIT_POLICY_COLUMNS view, 3-96
ALL_AW_PS view, 3-96
ALL_AWS view, 3-97
ALL_BASE_TABLE_MVIEWS view, 3-98
ALL_BLOCKCHAIN_ROW_VERSION_COLS view, 3-99
ALL_BLOCKCHAIN_ROW_VERSION_HISTORY view, 3-99
ALL_BLOCKCHAIN_TABLE_CHAINS view, 3-101
ALL_BLOCKCHAIN_TABLE_EPOCHS view, 3-102
ALL_BLOCKCHAIN_TABLE_HASH_COL_ORDER view, 3-103
ALL_BLOCKCHAIN_TABLES view, 3-104
ALL_CAPTURE view, 3-105
ALL_CAPTURE_EXTRA_ATTRIBUTES view, 3-108
ALL_CAPTURE_PARAMETERS view, 3-108
ALL_CAPTURE_PREPARED_DATABASE view, 3-109
ALL_CAPTURE_PREPARED_SCHEMAS view, 3-110
ALL_CAPTURE_PREPARED_TABLES view, 3-111
ALL_CATALOG view, 3-112
ALL_CERTIFICATES view, 3-112
ALL_CLUSTER_HASH_EXPRESSIONS view, 3-113
ALL_CLUSTERING_DIMENSIONS view, 3-113
ALL_CLUSTERING_JOINS view, 3-114
ALL_CLUSTERING_KEYS view, 3-115
ALL_CLUSTERING_TABLES view, 3-116
ALL_CLUSTERS view, 3-117
ALL_CODE_ROLE_PRIVS view, 3-119
ALL_COL_COMMENTS view, 3-120
ALL_COL_PENDING_STATS view, 3-120
ALL_COL_PRIVS view, 3-121
ALL_COL_PRIVS_MADE view, 3-122
ALL_COL_PRIVS_RECD view, 3-123
ALL_COLL_TYPES view, 3-124
ALL_CONS_COLUMNS view, 3-125
ALL_CONS_OBJ_COLUMNS view, 3-126
ALL_CONSTRAINTS view, 3-127
ALL_CONTEXT view, 3-130
ALL_CREDENTIALS view, 3-130
ALL_CUBE_ATTR_VISIBILITY view, 3-131
ALL_CUBE_ATTRIBUTES view, 3-132
ALL_CUBE_BUILD_PROCESSES view, 3-134
ALL_CUBE_CALCULATED_MEMBERS view, 3-134
ALL_CUBE_DIM_LEVELS view, 3-135
ALL_CUBE_DIM_MODELS view, 3-136
ALL_CUBE_DIM_VIEW_COLUMNS view, 3-136
ALL_CUBE_DIM_VIEWS view, 3-137
ALL_CUBE_DIMENSIONALITY view, 3-138
ALL_CUBE_DIMENSIONS view, 3-139
ALL_CUBE_HIER_LEVELS view, 3-140
ALL_CUBE_HIER_VIEW_COLUMNS view, 3-140
ALL_CUBE_HIER_VIEWS view, 3-141
ALL_CUBE_HIERARCHIES view, 3-142
ALL_CUBE_MEASURES view, 3-143
ALL_CUBE_NAMED_BUILD_SPECS view, 3-144
ALL_CUBE_SUB_PARTITION_LEVELS view, 3-145

ALL_CUBE_VIEW_COLUMNS view, *3-146*
ALL_CUBE_VIEWS view, *3-146*
ALL_CUBES view, *3-147*
ALL_DB_LINKS view, *3-148*
ALL_DEF_AUDIT_OPTS view, *3-149*
ALL_DEPENDENCIES view, *3-150*
ALL_DEQUEUE_QUEUES view, *3-151*
ALL_DIM_ATTRIBUTES view, *3-152*
ALL_DIM_CHILD_OF view, *3-152*
ALL_DIM_HIERARCHIES view, *3-153*
ALL_DIM_JOIN_KEY view, *3-154*
ALL_DIM_LEVEL_KEY view, *3-154*
ALL_DIM_LEVELS view, *3-155*
ALL_DIMENSIONS view, *3-156*
ALL_DIRECTORIES view, *3-156*
ALL_DOMAIN_COLS view, *3-157*
ALL_DOMAIN_CONSTRAINTS view, *3-158*
ALL_DOMAINS view, *3-160*
ALL_EDITION_COMMENTS view, *3-161*
ALL_EDITIONING_VIEW_COLS view, *3-162*
ALL_EDITIONING_VIEW_COLS_AE view, *3-163*
ALL_EDITIONING_VIEWS view, *3-163*
ALL_EDITIONING_VIEWS_AE view, *3-164*
ALL_EDITIONS view, *3-164*
ALL_ENCRYPTED_COLUMNS view, *3-165*
ALL_ERROR_TRANSLATIONS view, *3-166*
ALL_ERRORS view, *3-166*
ALL_ERRORS_AE view, *3-167*
ALL_EVALUATION_CONTEXT_TABLES view, *3-168*
ALL_EVALUATION_CONTEXT_VARS view, *3-169*
ALL_EVALUATION_CONTEXTS view, *3-170*
ALL_EXPRESSION_STATISTICS view, *3-170*
ALL_EXTERNAL_LOCATIONS view, *3-171*
ALL_EXTERNAL_TABLES view, *3-172*
ALL_GG_AUTO_CDR_COLUMN_GROUPS view, *3-173*
ALL_GG_AUTO_CDR_COLUMNS view, *3-174*
ALL_GG_AUTO_CDR_TABLES view, *3-174*
ALL_GG_INBOUND_PROGRESS view, *3-176*
ALL_GOLDENGATE_INBOUND view, *3-177*
ALL_GOLDENGATE_PRIVILEGES view, *3-177*
ALL_GOLDENGATE_RULES view, *3-178*
ALL_HEAT_MAP_SEG_HISTOGRAM view, *3-180*
ALL_HEAT_MAP_SEGMENT view, *3-180*
ALL_HIER_CLASS view, *3-181*
ALL_HIER_CLASS_AE view, *3-182*
ALL_HIER_COLUMNS view, *3-183*
ALL_HIER_COLUMNS_AE view, *3-184*
ALL_HIER_HIER_ATTR_CLASS view, *3-185*
ALL_HIER_HIER_ATTR_CLASS_AE view, *3-186*
ALL_HIER_HIER_ATTRIBUTES view, *3-187*
ALL_HIER_HIER_ATTRIBUTES_AE view, *3-188*
ALL_HIER_JOIN_PATHS view, *3-189*
ALL_HIER_JOIN_PATHS_AE view, *3-189*
ALL_HIER_LEVEL_ID_ATTRS view, *3-190*
ALL_HIER_LEVEL_ID_ATTRS_AE view, *3-191*
ALL_HIER_LEVELS view, *3-192*
ALL_HIER_LEVELS_AE view, *3-192*
ALL_HIERARCHIES view, *3-193*
ALL_HIERARCHIES_AE view, *3-194*
ALL_HIST_SAGAS view, *3-195*
ALL_HISTOGRAMS synonym for ALL_TAB_HISTOGRAMS, *3-196*
ALL_HIVE_COLUMNS view, *3-196*
ALL_HIVE_DATABASES view, *3-197*
ALL_HIVE_PART_KEY_COLUMNS view, *3-198*
ALL_HIVE_TAB_PARTITIONS view, *3-198*
ALL_HIVE_TABLES view, *3-199*
ALL_IDENTIFIERS view, *3-200*
ALL_IMMUTABLE_ROW_VERSION_COLS view, *3-202*
ALL_IMMUTABLE_ROW_VERSION_HISTORY view, *3-203*
ALL_IMMUTABLE_TABLE_COLUMNS view, *3-204*
ALL_IMMUTABLE_TABLE_EPOCHS view, *3-205*
ALL_IMMUTABLE_TABLES view, *3-206*
ALL_INCOMPLETE_SAGAS view, *3-207*
ALL_IND_COLUMNS view, *3-208*
ALL_IND_EXPRESSIONS view, *3-209*
ALL_IND_PARTITIONS view, *3-210*
ALL_IND_PENDING_STATS view, *3-213*
ALL_IND_STATISTICS view, *3-214*
ALL_IND_SUBPARTITIONS view, *3-216*
ALL_INDEXES view, *3-218*
ALL_INDEXTYPE_ARRAYTYPES view, *3-223*
ALL_INDEXTYPE_COMMENTS view, *3-224*
ALL_INDEXTYPE_OPERATORS view, *3-225*
ALL_INDEXTYPES view, *3-225*
ALL_INTERNAL_TRIGGERS view, *3-226*
ALL_JAVA_ARGUMENTS view, *3-227*
ALL_JAVA_CLASSES view, *3-228*
ALL_JAVA_COMPILER_OPTIONS view, *3-229*
ALL_JAVA_DERIVATIONS view, *3-229*
ALL_JAVA_FIELDS view, *3-230*
ALL_JAVA_IMPLEMENTS view, *3-231*
ALL_JAVA_INNERS view, *3-232*
ALL_JAVA_LAYOUTS view, *3-233*
ALL_JAVA_METHODS view, *3-234*
ALL_JAVA_NCOMPS view, *3-235*
ALL_JAVA_RESOLVERS view, *3-236*
ALL_JAVA_THROWS view, *3-236*
ALL_JOBS synonym for USER_JOBS view, *3-237*
ALL_JOIN_IND_COLUMNS view, *3-237*
ALL_JSON_COLLECTION_TABLES view, *3-238*
ALL_JSON_COLLECTIONS view, *3-239*

ALL_JSON_COLUMNS view, *3-239*
ALL_JSON_DATAGUIDE_FIELDS view, *3-241*
ALL_JSON_DATAGUIDES view, *3-241*
ALL_JSON_DOMAIN_SCHEMA_COLUMNS view, *3-242*
ALL_JSON_DUALITY_VIEW_LINKS view, *3-243*
ALL_JSON_DUALITY_VIEW_TAB_COLS view, *3-244*
ALL_JSON_DUALITY_VIEW_TABS view, *3-245*
ALL_JSON_DUALITY_VIEWS view, *3-246*
ALL_JSON_INDEXES view, *3-247*
ALL_JSON_SCHEMA_COLUMNS view, *3-248*
ALL_LIBRARIES view, *3-249*
ALL_LOB_PARTITIONS view, *3-250*
ALL_LOB_SUBPARTITIONS view, *3-253*
ALL_LOB_TEMPLATES view, *3-256*
ALL_LOBS view, *3-257*
ALL_LOG_GROUP_COLUMNS view, *3-259*
ALL_LOG_GROUPS view, *3-260*
ALL_MEASURE_FOLDER_CONTENTS view, *3-261*
ALL_MEASURE_FOLDER_SUBFOLDERS view, *3-261*
ALL_MEASURE_FOLDERS view, *3-262*
ALL_METADATA_PROPERTIES view, *3-262*
ALL_METHOD_PARAMS view, *3-263*
ALL_METHOD_RESULTS view, *3-264*
ALL_MINING_ALGORITHMS view, *3-265*
ALL_MINING_MODEL_ATTRIBUTES view, *3-265*
ALL_MINING_MODEL_PARTITIONS view, *3-267*
ALL_MINING_MODEL_SETTINGS view, *3-268*
ALL_MINING_MODEL_VIEWS view, *3-268*
ALL_MINING_MODEL_XFORMS view, *3-269*
ALL_MINING_MODELS view, *3-269*
ALL_MLE_ENV_IMPORTS view, *3-271*
ALL_MLE_ENVS view, *3-272*
ALL_MLE_MODULES view, *3-272*
ALL_MLE_PROCEDURES view, *3-273*
ALL_MVIEW_AGGREGATES view, *3-275*
ALL_MVIEW_ANALYSIS view, *3-276*
ALL_MVIEW_COMMENTS view, *3-277*
ALL_MVIEW_DETAIL_LOGICAL_PARTITION view, *3-278*
ALL_MVIEW_DETAIL_PARTITION view, *3-279*
ALL_MVIEW_DETAIL_RELATIONS view, *3-280*
ALL_MVIEW_DETAIL_SUBPARTITION view, *3-281*
ALL_MVIEW_JOINS view, *3-281*
ALL_MVIEW_KEYS view, *3-282*
ALL_MVIEW_LOGS view, *3-283*
ALL_MVIEW_REFRESH_TIMES view, *3-285*
ALL_MVIEWS view, *3-285*
ALL_NESTED_TABLE_COLS view, *3-290*
ALL_NESTED_TABLES view, *3-292*
ALL_OBJ_COLATTRS view, *3-293*
ALL_OBJECT_TABLES view, *3-294*
ALL_OBJECTS view, *3-300*
ALL_OBJECTS_AE view, *3-302*
ALL_OPANCILLARY view, *3-304*
ALL_OPARGUMENTS view, *3-304*
ALL_OPBINDINGS view, *3-305*
ALL_OPERATOR_COMMENTS view, *3-306*
ALL_OPERATORS view, *3-307*
ALL_OUTLINE_HINTS synonym for USER_OUTLINE_HINTS view, *3-307*
ALL_OUTLINES synonym for USER_OUTLINES view, *3-307*
ALL_PART_COL_STATISTICS view, *4-1*
ALL_PART_HISTOGRAMS view, *4-2*
ALL_PART_INDEXES view, *4-3*
ALL_PART_KEY_COLUMNS view, *4-6*
ALL_PART_LOBS view, *4-6*
ALL_PART_TABLES view, *4-10*
ALL_PARTIAL_DROP_TABS view, *4-14*
ALL_PENDING_CONV_TABLES view, *4-15*
ALL_PG_EDGE_RELATIONSHIPS view, *4-15*
ALL_PG_ELEMENT_LABELS view, *4-16*
ALL_PG_ELEMENTS view, *4-17*
ALL_PG_KEYS view, *4-18*
ALL_PG_LABEL_PROPERTIES view, *4-18*
ALL_PG_LABELS view, *4-19*
ALL_PG_PROP_DEFINITIONS view, *4-20*
ALL_PLSQL_COLL_TYPES view, *4-21*
ALL_PLSQL_OBJECT_SETTINGS view, *4-22*
ALL_PLSQL_TYPE_ATTRS view, *4-23*
ALL_PLSQL_TYPES view, *4-24*
ALL_POLICIES view, *4-25*
ALL_POLICY_ATTRIBUTES view, *4-26*
ALL_POLICY_CONTEXTS view, *4-27*
ALL_POLICY_GROUPS view, *4-28*
ALL_PROCEDURES view, *4-28*
ALL_PROPAGATION view, *4-30*
ALL_PROPERTY_GRAPHS view, *4-31*
ALL_QUEUE_EVENT_STREAMS view, *4-32*
ALL_QUEUE_SCHEDULES view, *4-32*
ALL_QUEUE_SUBSCRIBERS view, *4-34*
ALL_QUEUE_TABLES view, *4-35*
ALL_QUEUES view, *4-36*
ALL_REFRESH view, *4-37*
ALL_REFRESH_CHILDREN view, *4-38*
ALL_REFRESH_DEPENDENCIES view, *4-39*
ALL_REFS view, *4-40*
ALL_REGISTERED_MVIEWS view, *4-41*
ALL_REGISTRY_BANNERS view, *4-42*
ALL_REPL_DBNAME_MAPPING view, *4-42*
ALL_REPLICATION_PROCESS_EVENTS view, *4-42*
ALL_REWRITE_EQUIVALENCES view, *4-43*
ALL_RULE_SET_RULES view, *4-44*

ALL_RULE_SETS view, *4-45*
ALL_RULES view, *4-45*
ALL_SAGA_BROKERS view, *4-46*
ALL_SAGA_DETAILS view, *4-47*
ALL_SAGA_ERRORS view, *4-48*
ALL_SAGA_FINALIZATION view, *4-48*
ALL_SAGA_PARTICIPANT_SET view, *4-49*
ALL_SAGA_PARTICIPANTS view, *4-50*
ALL_SAGA_PENDING view, *4-51*
ALL_SAGAS view, *4-52*
ALL_SCHEDULER_CHAIN_RULES view, *4-54*
ALL_SCHEDULER_CHAIN_STEPS view, *4-54*
ALL_SCHEDULER_CHAINS view, *4-56*
ALL_SCHEDULER_CREDENTIALS view, *4-56*
ALL_SCHEDULER_DB_DESTS view, *4-57*
ALL_SCHEDULER_DESTS view, *4-58*
ALL_SCHEDULER_EXTERNAL_DESTS view, *4-59*
ALL_SCHEDULER_FILE_WATCHERS view, *4-59*
ALL_SCHEDULER_GLOBAL_ATTRIBUTE view, *4-60*
ALL_SCHEDULER_GROUP_MEMBERS view, *4-61*
ALL_SCHEDULER_GROUPS view, *4-61*
ALL_SCHEDULER_INCOMPAT_MEMBER view, *4-62*
ALL_SCHEDULER_INCOMPATS view, *4-63*
ALL_SCHEDULER_JOB_ARGS view, *4-63*
ALL_SCHEDULER_JOB_CLASSES view, *4-64*
ALL_SCHEDULER_JOB_DESTS view, *4-65*
ALL_SCHEDULER_JOB_LOG view, *4-66*
ALL_SCHEDULER_JOB_RUN_DETAILS view, *4-68*
ALL_SCHEDULER_JOBS view, *4-69*
ALL_SCHEDULER_NOTIFICATIONS view, *4-73*
ALL_SCHEDULER_PROGRAM_ARGS view, *4-74*
ALL_SCHEDULER_PROGRAMS view, *4-75*
ALL_SCHEDULER_REMOTE_DATABASES view, *4-76*
ALL_SCHEDULER_REMOTE_JOBSTATE view, *4-77*
ALL_SCHEDULER_RESOURCES view, *4-78*
ALL_SCHEDULER_RSC_CONSTRAINTS view, *4-79*
ALL_SCHEDULER_RUNNING_CHAINS view, *4-79*
ALL_SCHEDULER_RUNNING_JOBS view, *4-81*
ALL_SCHEDULER_SCHEDULES view, *4-82*
ALL_SCHEDULER_WINDOW_DETAILS view, *4-83*
ALL_SCHEDULER_WINDOW_GROUPS view, *4-84*
ALL_SCHEDULER_WINDOW_LOG view, *4-84*
ALL_SCHEDULER_WINDOWS view, *4-85*
ALL_SCHEDULER_WINGROUP_MEMBERS view, *4-86*
ALL_SEC_RELEVANT_COLS view, *4-87*
ALL_SECONDARY_OBJECTS view, *4-87*
ALL_SEQUENCES view, *4-88*
ALL_SERVICES view, *4-89*
ALL_SOURCE view, *4-93*
ALL_SOURCE_AE view, *4-94*
ALL_SQL_TRANSLATION_PROFILES view, *4-95*
ALL_SQL_TRANSLATIONS view, *4-96*
ALL_SQLJ_TYPE_ATTRS view, *4-97*
ALL_SQLJ_TYPE_METHODS view, *4-98*
ALL_SQLJ_TYPES view, *4-99*
ALL_SQLSET view, *4-100*
ALL_SQLSET_BINDS view, *4-101*
ALL_SQLSET_PLANS view, *4-102*
ALL_SQLSET_REFERENCES view, *4-106*
ALL_SQLSET_STATEMENTS view, *4-107*
ALL_STAT_EXTENSIONS view, *4-109*
ALL_STATEMENTS view, *4-110*
ALL_STORED_SETTINGS view, *4-111*
ALL_STREAMS_GLOBAL_RULES view, *4-112*
ALL_STREAMS_MESSAGE_CONSUMERS view, *4-114*
ALL_STREAMS_NEWLY_SUPPORTED view, *4-114*
ALL_STREAMS_SCHEMA_RULES view, *4-115*
ALL_STREAMS_TABLE_RULES view, *4-116*
ALL_STREAMS_TRANSFORM_FUNCTION view, *4-118*
ALL_SUBPART_COL_STATISTICS view, *4-118*
ALL_SUBPART_HISTOGRAMS view, *4-120*
ALL_SUBPART_KEY_COLUMNS view, *4-121*
ALL_SUBPARTITION_TEMPLATES view, *4-121*
ALL_SUMDELTA view, *4-122*
ALL_SYNC_CAPTURE view, *4-123*
ALL_SYNC_CAPTURE_PREPARED_TABS view, *4-123*
ALL_SYNC_CAPTURE_TABLES view, *4-124*
ALL_SYNONYMS view, *4-124*
ALL_TAB_COL_STAT_MODELS view, *4-126*
ALL_TAB_COL_STATISTICS view, *4-127*
ALL_TAB_COLS view, *4-128*
ALL_TAB_COLUMNS view, *4-132*
ALL_TAB_COMMENTS view, *4-135*
ALL_TAB_HISTGRM_PENDING_STATS view, *4-136*
ALL_TAB_HISTOGRAMS view, *4-137*
  ALL_HISTOGRAMS synonym, *3-196*
ALL_TAB_IDENTITY_COLS view, *4-138*
ALL_TAB_MODIFICATIONS view, *4-139*
ALL_TAB_PARTITIONS view, *4-140*
ALL_TAB_PENDING_STATS view, *4-146*

ALL_TAB_PRIVS view, *4-147*
ALL_TAB_PRIVS_MADE view, *4-148*
ALL_TAB_PRIVS_RECD view, *4-149*
ALL_TAB_STAT_PREFS view, *4-150*
ALL_TAB_STATISTICS view, *4-150*
ALL_TAB_STATS_HISTORY view, *4-152*
ALL_TAB_SUBPARTITIONS view, *4-153*
ALL_TABLE_ACCESS_STATS view, *4-157*
ALL_TABLE_VIRTUAL_COLUMNS view, *4-158*
ALL_TABLES view, *4-159*
ALL_TRANSFORMATIONS view, *4-167*
ALL_TRIGGER_COLS view, *4-168*
ALL_TRIGGER_ORDERING view, *4-168*
ALL_TRIGGERS view, *4-169*
ALL_TRIGGERS_AE view, *4-171*
ALL_TSTZ_TAB_COLS view, *4-173*
ALL_TSTZ_TABLES view, *4-174*
ALL_TXEVENTQ_MIGRATION_STATUS view, *4-175*
ALL_TYPE_ATTRS view, *4-176*
ALL_TYPE_METHODS view, *4-177*
ALL_TYPE_VERSIONS view, *4-178*
ALL_TYPES view, *4-178*
ALL_UNIFIED_AUDIT_ACTIONS table, *4-179*
ALL_UNUSED_COL_TABS view, *4-180*
ALL_UPDATABLE_COLUMNS view, *4-181*
ALL_USERS view, *4-181*
ALL_USTATS view, *4-183*
ALL_VARRAYS view, *4-184*
ALL_VIEWS view, *4-184*
ALL_VIEWS_AE view, *4-186*
ALL_WARNING_SETTINGS view, *4-188*
ALL_XML_INDEXES view, *4-189*
ALL_XML_NESTED_TABLES view, *4-190*
ALL_XML_OUT_OF_LINE_TABLES view, *4-190*
ALL_XML_SCHEMA_ATTRIBUTES view, *4-191*
ALL_XML_SCHEMA_COMPLEX_TYPES view, *4-192*
ALL_XML_SCHEMA_ELEMENTS view, *4-193*
ALL_XML_SCHEMA_NAMESPACES view, *4-194*
ALL_XML_SCHEMA_SIMPLE_TYPES view, *4-195*
ALL_XML_SCHEMA_SUBSTGRP_HEAD view, *4-195*
ALL_XML_SCHEMA_SUBSTGRP_MBRS view, *4-196*
ALL_XML_SCHEMAS view, *4-197*
ALL_XML_TAB_COLS view, *4-198*
ALL_XML_TABLES view, *4-199*
ALL_XML_VIEW_COLS view, *4-200*
ALL_XML_VIEWS view, *4-201*
ALL_XSTREAM_ADMINISTRATOR view, *4-202*
ALL_XSTREAM_INBOUND view, *4-203*
ALL_XSTREAM_INBOUND_PROGRESS view, *4-204*
ALL_XSTREAM_OUT_SUPPORT_MODE view, *4-205*
ALL_XSTREAM_OUTBOUND view, *4-206*
ALL_XSTREAM_OUTBOUND_PROGRESS view, *4-207*
ALL_XSTREAM_RULES view, *4-208*
ALL_XSTREAM_TRANSFORMATIONS view, *4-209*
ALL_XTERNAL_LOC_PARTITIONS view, *4-210*
ALL_XTERNAL_LOC_SUBPARTITIONS view, *4-211*
ALL_XTERNAL_PART_TABLES view, *4-212*
ALL_XTERNAL_TAB_PARTITIONS view, *4-213*
ALL_XTERNAL_TAB_SUBPARTITIONS view, *4-214*
ALL_ZONEMAP_MEASURES view, *4-215*
ALL_ZONEMAPS view, *4-215*
ALLOCATE EXTENT clause
  of ALTER TABLE
    instance number, *2-178*
ALLOW_GLOBAL_DBLINKS initialization parameter, *2-33*
ALLOW_GROUP_ACCESS_TO_SGA initialization parameter, *2-33*
ALLOW_LEGACY_RECO_PROTOCOL initialization parameter, *2-34*
ALLOW_ROWID_COLUMN_TYPE initialization parameter, *2-35*
ALTER DATABASE statement
  ADD LOGFILE, *2-381*
  ENABLE THREAD, *2-381*
  THREAD, *2-381*
ALTER TABLE statement
  allocating extents, *2-178*
analytic views
  columns, *3-22*, *3-23*
  fact columns, *3-32*, *3-33*
  hierarchical attributes, *3-187*, *3-188*
  hierarchies, *3-36*
  hierarchy classifications, *3-33*, *3-35*
  hierarchy join paths, *3-189*
  hierarchy level ID attributes, *3-190*, *3-191*
  hierarchy levels, *3-192*
  level classifications, *3-39*, *3-42*
  levels, *3-40*, *3-41*
  measure and level groups, *3-43*, *3-44*
  measure classifications, *3-45*, *3-46*
APPROX_FOR_AGGREGATION initialization parameter, *2-36*
APPROX_FOR_COUNT_DISTINCT initialization parameter, *2-36*
APPROX_FOR_PERCENTILE initialization parameter, *2-37*

AQ_TM_PROCESSES initialization parameter, 2-38
ARCHIVE LOG START statement
  automatic archiving, 2-198
ARCHIVE_LAG_TARGET initialization parameter, 2-39
archived redo logs
  destination file, 2-198
  storage device, 2-198, 2-206
ARCHIVELOG mode, 2-198
  archiving destination, 2-198, 2-206
ASM_DISKGROUPS initialization parameter, 2-40
ASM_DISKSTRING initialization parameter, 2-41
ASM_IO_PROCESSES initialization parameter, 2-42
ASM_POWER_LIMIT initialization parameter, 2-42
ASM_PREFERRED_READ_FAILURE_GROUPS initialization parameter, 2-43
attribute dimension
  join paths, 3-78
attribute dimensions, 3-91, 3-92
  attribute classifications, 3-72, 3-73
  attributes, 3-74, 3-75
  keys, 3-37, 3-38, 3-79, 3-80
  level attributes, 3-81, 3-84
  level classifications, 3-85, 3-86
  levels, 3-82, 3-83
  order attributes, 3-87, 3-88
  tables, 3-89, 3-90
AUDIT_ACTIONS table, 4-217
AUDIT_FILE_DEST initialization parameter, 2-44
AUDIT_SYS_OPERATIONS initialization parameter, 2-45
AUDIT_SYSLOG_LEVEL initialization parameter, 2-46
AUDIT_TRAIL initialization parameter, 2-48
AUDIT_UNIFIED_CONTEXTS view, 4-218
AUDIT_UNIFIED_ENABLED_POLICIES view, 4-219
AUDIT_UNIFIED_POLICIES view, 4-220
AUDIT_UNIFIED_POLICY_COMMENTS view, 4-222
AUDITABLE_SYSTEM_ACTIONS view, 4-222
authenticating users, 2-274
AUTOTASK_MAX_ACTIVE_PDBS initialization parameter, 2-50
AWR_PDB_* Views, 3-2
AWR_PDB_AUTOFLUSH_ENABLED initialization parameter, 2-51
AWR_PDB_MAX_PARALLEL_SLAVES initialization parameter, 2-52
AWR_ROOT_* Views, 3-2
AWR_SNAPSHOT_TIME_OFFSET initialization parameter, 2-52

B

BACKGROUND_CORE_DUMP initialization parameter, 2-53
BACKGROUND_DUMP_DEST initialization parameter, 2-54
BACKUP_TAPE_IO_SLAVES initialization parameter, 2-55
BITMAP_MERGE_AREA_SIZE initialization parameter, 2-56
BLANK_TRIMMING initialization parameter, 2-56
BLOCKCHAIN_TABLE_MAX_NO_DROP initialization parameter, 2-57
BLOCKCHAIN_TABLE_RETENTION_THRESHOLD initialization parameter, 2-58
blocks
  redo log, 2-212
  size, 2-87, 2-92, 2-106
buffer cache management, D-1

C

cache
  dictionary, 9-183–9-185
  statistics, 2-212
CAT synonym for USER_CATALOG view, 4-224
CATALOG view, 4-224
CATALOG.SQL script, B-2
  creating V$ views, 8-1
CATBLOCK.SQL script, B-3
CATCLUST.SQL script, B-2
CATHS.SQL script, B-3
CATIO.SQL script, B-3
CATJAVA.SQL script, B-6
CATNOCLUST.SQL script, B-5
CATNOJAV.SQL script, B-6
CATNOPRT.SQL script, B-6
CATNOSVM.SQL script, B-6
CATNSNMP.SQL script, B-6
CATPCAT.SQL script, B-2
CATPROC.SQL script, B-2
CATQUEUE.SQL script, B-3
CATREP.SQL script, B-3
CATWRR.SQL script, B-3
CATWRRWITB.SQL script, B-3
CDB_* views, 3-3
CDBs, 2-45
CHAINED_ROWS table, 4-224
characters
  numeric group separators, 2-249
checkpoints
  checkpoint interval, 2-212

checkpoints *(continued)*
statistics, *2-212*
CIRCUITS initialization parameter, *2-59*
classifications
analytic view, *3-19*, *3-20*
analytic view attribute, *3-14*, *3-15*
analytic view attribute dimension, *3-27*, *3-28*
analytic view hierarchy, *3-33*, *3-35*
analytic view level, *3-39*, *3-42*
analytic view measure, *3-45*, *3-46*
attribute dimension, *3-76*
attribute dimension attribute, *3-72*, *3-73*
attribute dimension level, *3-85*, *3-86*
hierarchy, *3-181*, *3-182*
hierarchy hierarchical attribute, *3-185*, *3-186*
CLIENT_RESULT_CACHE_LAG initialization parameter, *2-59*
CLIENT_RESULT_CACHE_SIZE initialization parameter, *2-60*
CLIENT_RESULT_CACHE_STATS$ view, *4-225*
CLIENT_STATISTICS_LEVEL initialization parameter, *2-60*
CLONEDB initialization parameter, *2-62*
CLONEDB_DIR initialization parameter, *2-63*
CLU synonym for USER_CLUSTERS view, *4-225*
CLUSTER_DATABASE initialization parameter, *2-63*
CLUSTER_INTERCONNECTS initialization parameter, *2-64*
COL view, *4-226*
COLS synonym for USER_TAB_COLUMNS view, *4-226*
commit wait/nowait performed, *E-5*
COMMIT_LOGGING initialization parameter, *2-65*
COMMIT_POINT_STRENGTH initialization parameter, *2-65*
COMMIT_WAIT initialization parameter, *2-66*
COMMIT_WRITE initialization parameter, *2-67*
COMMON_USER_PREFIX initialization parameter, *2-68*
COMPATIBLE initialization parameter, *2-69*
CONNECTION_BROKERS initialization parameter, *2-70*
CONTAINER_DATA initialization parameter, *2-72*
CONTAINERS_PARALLEL_DEGREE initialization parameter, *2-73*
contention
block-level, *10-180*
control files
names, *2-75*
specifying, *2-75*
CONTROL_FILE_RECORD_KEEP_TIME initialization parameter, *2-73*
CONTROL_FILES initialization parameter, *2-74*
CONTROL_MANAGEMENT_PACK_ACCESS initialization parameter, *2-75*
controlfile transaction, *D-1*
CORE_DUMP_DEST initialization parameter, *2-76*
cost-based optimization, *2-270*
favoring IN-list iterators, *2-268*
CPU_COUNT initialization parameter, *2-76*
CPU_MIN_COUNT initialization parameter, *2-78*
CREATE TABLE statement
FREELIST GROUPS clause, *2-178*
CREATE_BITMAP_AREA_SIZE initialization parameter, *2-79*
CREATE_STORED_OUTLINES initialization parameter, *2-79*
creating
a database
setting block size, *2-87*, *2-92*, *2-106*
currency, *2-241*, *2-242*
international currency symbol, *2-246*
CURSOR_BIND_CAPTURE_DESTINATION initialization parameter, *2-80*
CURSOR_INVALIDATION initialization parameter, *2-81*
CURSOR_SHARING initialization parameter, *2-82*
CURSOR_SPACE_FOR_TIME initialization parameter, *2-82*
cursors
OPEN_CURSORS initialization parameter, *2-258*
shared pool, *2-353*

D

data blocks
reading multiple, *2-98*
size of, *2-87*, *2-92*, *2-106*
data dictionary, *3-1*
cache, *9-183*–*9-185*
scripts, *B-2*
SQL scripts, *B-1*
tables, *3-1*
views
overview, *3-1*
user views, *3-1*
DATA_GUARD_MAX_IO_TIME initialization parameter, *2-84*
DATA_GUARD_MAX_LONGIO_TIME initialization parameter, *2-84*
DATA_GUARD_SYNC_LATENCY initialization parameter, *2-85*
DATA_TRANSFER_CACHE_SIZE initialization parameter, *2-86*

database writer process (DBWR)
checkpoint, 2-212
DATABASE_EXPORT_OBJECTS view, 4-226
DATABASE_PROPERTIES view, 4-226
databases
database limits, A-1
default language, 2-246
resource limits, 2-324, 2-329
datafiles
maximum number, 2-100
parameter, 2-100
dates
language used for, 2-244, 2-252, 2-253
setting SYSDATE, 2-147
TO_CHAR function, 2-243
TO_DATE function, 2-243
DB_BIG_TABLE_CACHE_PERCENT_TARGET initialization parameter, 2-87
DB_BLOCK_BUFFERS initialization parameter, 2-89
DB_BLOCK_CHECKING initialization parameter, 2-90
DB_BLOCK_CHECKSUM initialization parameter, 2-91
DB_BLOCK_SIZE initialization parameter, 2-92
DB_CACHE_ADVICE initialization parameter, 2-93
DB_CACHE_SIZE initialization parameter, 2-94
DB_CREATE_FILE_DEST initialization parameter, 2-95
DB_CREATE_ONLINE_LOG_DEST_n initialization parameter, 2-96
DB_DOMAIN initialization parameter, 2-97
DB_FILE_MULTIBLOCK_READ_COUNT initialization parameter, 2-98
DB_FILE_NAME_CONVERT initialization parameter, 2-99
DB_FILES initialization parameter, 2-100
DB_FLASH_CACHE_FILE initialization parameter, 2-101
DB_FLASH_CACHE_SIZE initialization parameter, 2-101
DB_FLASHBACK_LOG_DEST initialization parameter, 2-102
DB_FLASHBACK_LOG_DEST_SIZE initialization parameter, 2-103
DB_FLASHBACK_RETENTION_TARGET initialization parameter, 2-104
DB_INDEX_COMPRESSION_INHERITANCE initialization parameter, 2-105
DB_KEEP_CACHE_SIZE initialization parameter, 2-106
DB_LOST_WRITE_PROTECT initialization parameter, 2-106
DB_NAME initialization parameter, 2-108
DB_nK_CACHE_SIZE initialization parameter, 2-86
DB_PERFORMANCE_PROFILE initialization parameter, 2-108
DB_RECOVERY_AUTO_REKEY initialization parameter, 2-109
DB_RECOVERY_FILE_DEST initialization parameter, 2-110
DB_RECOVERY_FILE_DEST_SIZE initialization parameter, 2-110
DB_RECYCLE_CACHE_SIZE initialization parameter, 2-111
DB_SECUREFILE initialization parameter, 2-112
DB_ULTRA_SAFE initialization parameter, 2-113
DB_UNIQUE_NAME initialization parameter, 2-114
DB_UNRECOVERABLE_SCN_TRACKING initialization parameter, 2-115
DB_WRITER_PROCESSES initialization parameter, 2-115
DBA_2PC_NEIGHBORS view, 5-1
DBA_2PC_PENDING view, 5-1
DBA_ACCHK_EVENTS view, 5-2
DBA_ACCHK_EVENTS_SUMMARY view, 5-3
DBA_ACCHK_STATISTICS view, 5-5
DBA_ACCHK_STATISTICS_SUMMARY view, 5-6
DBA_ACL_NAME_MAP view, 5-8
DBA_ACTIVITY_CONFIG view, 5-8
DBA_ACTIVITY_MVIEW view, 5-8
DBA_ACTIVITY_SNAPSHOT_META view, 5-10
DBA_ACTIVITY_TABLE view, 5-11
DBA_ADDM_FDG_BREAKDOWN view, 5-13
DBA_ADDM_FINDINGS view, 5-13
DBA_ADDM_INSTANCES view, 5-15
DBA_ADDM_PENDING_AUTOTASKS view, 5-16
DBA_ADDM_SCHEDULED_AUTOTASKS view, 5-17
DBA_ADDM_SYSTEM_DIRECTIVES view, 5-17
DBA_ADDM_TASK_DIRECTIVES view, 5-18
DBA_ADDM_TASKS view, 5-18
DBA_ADVISOR_ACTIONS view, 5-22
DBA_ADVISOR_COMMANDS view, 5-23
DBA_ADVISOR_DEF_PARAMETERS view, 5-23
DBA_ADVISOR_DEFINITIONS view, 5-25
DBA_ADVISOR_DIR_DEFINITIONS view, 5-25
DBA_ADVISOR_DIR_INSTANCES view, 5-26
DBA_ADVISOR_DIR_TASK_INST view, 5-26
DBA_ADVISOR_EXEC_PARAMETERS view, 5-27
DBA_ADVISOR_EXECUTION_TYPES view, 5-28
DBA_ADVISOR_EXECUTIONS view, 5-28
DBA_ADVISOR_FDG_BREAKDOWN view, 5-30

DBA_ADVISOR_FINDING_NAMES view, 5-30
DBA_ADVISOR_FINDINGS view, 5-31
DBA_ADVISOR_JOURNAL view, 5-32
DBA_ADVISOR_LOG view, 5-32
DBA_ADVISOR_OBJECT_TYPES view, 5-33
DBA_ADVISOR_OBJECTS view, 5-34
DBA_ADVISOR_PARAMETERS view, 5-36
DBA_ADVISOR_RATIONALE view, 5-37
DBA_ADVISOR_RECOMMENDATIONS view, 5-38
DBA_ADVISOR_SQLA_REC_SUM view, 5-40
DBA_ADVISOR_SQLA_TABLES view, 5-41
DBA_ADVISOR_SQLA_WK_MAP view, 5-41
DBA_ADVISOR_SQLA_WK_STMTS view, 5-42
DBA_ADVISOR_SQLPLANS view, 5-44
DBA_ADVISOR_SQLSTATS view, 5-46
DBA_ADVISOR_SQLW_JOURNAL view, 5-48
DBA_ADVISOR_SQLW_PARAMETERS view, 5-49
DBA_ADVISOR_SQLW_STMTS view, 5-50
DBA_ADVISOR_SQLW_SUM view, 5-52
DBA_ADVISOR_SQLW_TABLES view, 5-52
DBA_ADVISOR_SQLW_TEMPLATES view, 5-53
DBA_ADVISOR_TASKS view, 5-54
DBA_ADVISOR_TEMPLATES view, 5-55
DBA_ADVISOR_USAGE view, 5-56
DBA_AIM_PERF_FEATURES view, 5-56
DBA_ALERT_HISTORY view, 5-57
DBA_ALERT_HISTORY_DETAIL view, 5-58
DBA_ALL_TABLES view, 5-59
DBA_ANALYTIC_VIEW_ATTR_CLASS view, 5-60
DBA_ANALYTIC_VIEW_ATTR_CLS view, 5-60
DBA_ANALYTIC_VIEW_ATTR_CLS_AE view, 5-60
DBA_ANALYTIC_VIEW_BAS_MEAS view, 5-60
DBA_ANALYTIC_VIEW_BAS_MEAS_AE view, 5-61
DBA_ANALYTIC_VIEW_BASE_MEAS view, 5-61
DBA_ANALYTIC_VIEW_CALC_MEAS view, 5-61
DBA_ANALYTIC_VIEW_CLASS view, 5-61
DBA_ANALYTIC_VIEW_CLASS_AE view, 5-62
DBA_ANALYTIC_VIEW_CLC_MEAS view, 5-62
DBA_ANALYTIC_VIEW_CLC_MEAS_AE view, 5-62
DBA_ANALYTIC_VIEW_COLUMNS view, 5-62
DBA_ANALYTIC_VIEW_COLUMNS_AE view, 5-63
DBA_ANALYTIC_VIEW_DIM_ATRS view, 5-63
DBA_ANALYTIC_VIEW_DIM_ATRS_AE view, 5-63
DBA_ANALYTIC_VIEW_DIM_ATTRS view, 5-63
DBA_ANALYTIC_VIEW_DIM_CLASS view, 5-64
DBA_ANALYTIC_VIEW_DIM_CLS view, 5-64
DBA_ANALYTIC_VIEW_DIM_CLS_AE view, 5-64
DBA_ANALYTIC_VIEW_DIMENSIONS view, 5-64
DBA_ANALYTIC_VIEW_DIMS view, 5-65
DBA_ANALYTIC_VIEW_DIMS_AE view, 5-65
DBA_ANALYTIC_VIEW_FACT_COLS view, 5-65
DBA_ANALYTIC_VIEW_FCT_COLS view, 5-65
DBA_ANALYTIC_VIEW_FCT_COLS_AE view, 5-66
DBA_ANALYTIC_VIEW_HIER_CLASS view, 5-66
DBA_ANALYTIC_VIEW_HIER_CLS view, 5-66
DBA_ANALYTIC_VIEW_HIER_CLS_AE view, 5-66
DBA_ANALYTIC_VIEW_HIERS view, 5-67
DBA_ANALYTIC_VIEW_HIERS_AE view, 5-67
DBA_ANALYTIC_VIEW_KEYS view, 5-67
DBA_ANALYTIC_VIEW_KEYS_AE view, 5-67
DBA_ANALYTIC_VIEW_LEVEL_CLASS view, 5-68
DBA_ANALYTIC_VIEW_LEVELS view, 5-68
DBA_ANALYTIC_VIEW_LEVELS_AE view, 5-68
DBA_ANALYTIC_VIEW_LVL_CLS view, 5-68
DBA_ANALYTIC_VIEW_LVL_CLS_AE view, 5-69
DBA_ANALYTIC_VIEW_LVLGRPS view, 5-69
DBA_ANALYTIC_VIEW_LVLGRPS_AE view, 5-69
DBA_ANALYTIC_VIEW_MEAS_CLASS view, 5-69
DBA_ANALYTIC_VIEW_MEAS_CLS view, 5-70
DBA_ANALYTIC_VIEW_MEAS_CLS_AE view, 5-70
DBA_ANALYTIC_VIEWS view, 5-70
DBA_ANALYTIC_VIEWS_AE view, 5-70
DBA_ANNOTATION_VALUES view, 5-71
DBA_ANNOTATIONS view, 5-71
DBA_ANNOTATIONS_USAGE view, 5-71
DBA_APP_ERRORS view, 5-72
DBA_APP_ERRORS_HISTORY view, 5-72
DBA_APP_PATCHES view, 5-73
DBA_APP_PDB_STATUS view, 5-73
DBA_APP_STATEMENTS view, 5-73
DBA_APP_VERSIONS view, 5-74
DBA_APPLICATION_ROLES view, 5-74
DBA_APPLICATIONS view, 5-75
DBA_APPLY view, 5-75
DBA_APPLY_CHANGE_HANDLERS view, 5-76
DBA_APPLY_CONFLICT_COLUMNS view, 5-76
DBA_APPLY_DML_CONF_HANDLERS view, 5-76
DBA_APPLY_DML_HANDLERS view, 5-76
DBA_APPLY_ENQUEUE view, 5-77

DBA_APPLY_ERROR view, *5-77*
DBA_APPLY_ERROR_MESSAGES view, *5-77*
DBA_APPLY_EXECUTE view, *5-78*
DBA_APPLY_HANDLE_COLLISIONS view, *5-78*
DBA_APPLY_INSTANTIATED_GLOBAL view, *5-78*
DBA_APPLY_INSTANTIATED_OBJECTS view, *5-78*
DBA_APPLY_INSTANTIATED_SCHEMAS view, *5-79*
DBA_APPLY_KEY_COLUMNS view, *5-79*
DBA_APPLY_OBJECT_DEPENDENCIES view, *5-79*
DBA_APPLY_PARAMETERS view, *5-79*
DBA_APPLY_PROGRESS view, *5-80*
DBA_APPLY_REPERROR_HANDLERS view, *5-80*
DBA_APPLY_SPILL_TXN view, *5-80*
DBA_APPLY_TABLE_COLUMNS view, *5-81*
DBA_APPLY_VALUE_DEPENDENCIES view, *5-81*
DBA_AQ_AGENT_PRIVS view, *5-81*
DBA_AQ_AGENTS view, *5-82*
DBA_ARGUMENTS view, *5-82*
DBA_ASSEMBLIES view, *5-82*
DBA_ASSOCIATIONS view, *5-83*
DBA_ATTRIBUTE_DIM_ATTR_CLASS view, *5-83*
DBA_ATTRIBUTE_DIM_ATTR_CLS view, *5-83*
DBA_ATTRIBUTE_DIM_ATTR_CLS_AE view, *5-83*
DBA_ATTRIBUTE_DIM_ATTRS view, *5-84*
DBA_ATTRIBUTE_DIM_ATTRS_AE view, *5-84*
DBA_ATTRIBUTE_DIM_CLASS view, *5-84*
DBA_ATTRIBUTE_DIM_CLASS_AE view, *5-84*
DBA_ATTRIBUTE_DIM_JN_PTHS view, *5-85*
DBA_ATTRIBUTE_DIM_JN_PTHS_AE view, *5-85*
DBA_ATTRIBUTE_DIM_JOIN_PATHS view, *5-85*
DBA_ATTRIBUTE_DIM_KEYS view, *5-85*
DBA_ATTRIBUTE_DIM_KEYS_AE view, *5-86*
DBA_ATTRIBUTE_DIM_LEVEL_ATTRS view, *5-86*
DBA_ATTRIBUTE_DIM_LEVELS view, *5-86*
DBA_ATTRIBUTE_DIM_LEVELS_AE view, *5-86*
DBA_ATTRIBUTE_DIM_LVL_ATRS view, *5-87*
DBA_ATTRIBUTE_DIM_LVL_ATRS_AE view, *5-87*
DBA_ATTRIBUTE_DIM_LVL_CLASS view, *5-87*
DBA_ATTRIBUTE_DIM_LVL_CLS view, *5-87*
DBA_ATTRIBUTE_DIM_LVL_CLS_AE view, *5-88*
DBA_ATTRIBUTE_DIM_ORD_ATRS view, *5-88*
DBA_ATTRIBUTE_DIM_ORD_ATRS_AE view, *5-88*
DBA_ATTRIBUTE_DIM_ORDER_ATTRS view, *5-88*
DBA_ATTRIBUTE_DIM_TABLES view, *5-89*
DBA_ATTRIBUTE_DIM_TABLES_AE view, *5-89*
DBA_ATTRIBUTE_DIMENSIONS view, *5-89*
DBA_ATTRIBUTE_DIMENSIONS_AE view, *5-89*
DBA_ATTRIBUTE_TRANSFORMATIONS view, *5-90*
DBA_AUDIT_EXISTS view, *5-90*
DBA_AUDIT_MGMT_CLEAN_EVENTS view, *5-93*
DBA_AUDIT_MGMT_CLEANUP_JOBS view, *5-94*
DBA_AUDIT_MGMT_CONFIG_PARAMS view, *5-95*
DBA_AUDIT_MGMT_LAST_ARCH_TS view, *5-96*
DBA_AUDIT_OBJECT view, *5-97*
DBA_AUDIT_POLICIES view, *5-99*
DBA_AUDIT_POLICY_COLUMNS view, *5-100*
DBA_AUDIT_SESSION view, *5-100*
DBA_AUDIT_STATEMENT view, *5-102*
DBA_AUDIT_TRAIL view, *5-105*
DBA_AUTO_CLUSTERING_CONFIG view, *5-110*
DBA_AUTO_CLUSTERING_RECOMMENDATIONS view, *5-110*
DBA_AUTO_INDEX_CONFIG view, *5-112*
DBA_AUTO_MV_ANALYSIS_ACTIONS view, *5-112*
DBA_AUTO_MV_ANALYSIS_EXECUTIONS view, *5-113*
DBA_AUTO_MV_ANALYSIS_RECOMMENDATIONS view, *5-115*
DBA_AUTO_MV_ANALYSIS_REPORT view, *5-115*
DBA_AUTO_MV_ANALYSIS_TASK view, *5-115*
DBA_AUTO_MV_CONFIG view, *5-117*
DBA_AUTO_MV_MAINT_REPORT view, *5-117*
DBA_AUTO_MV_REFRESH_HISTORY view, *5-117*
DBA_AUTO_MV_VERIFICATION_REPORT view, *5-118*
DBA_AUTO_MV_VERIFICATION_STATUS view, *5-118*
DBA_AUTO_SEGADV_CTL view, *5-119*
DBA_AUTO_SEGADV_SUMMARY view, *5-119*
DBA_AUTO_STAT_EXECUTIONS view, *5-120*
DBA_AUTO_ZONEMAP_CONFIG view, *5-121*
DBA_AUTOTASK_CLIENT view, *5-121*
DBA_AUTOTASK_CLIENT_HISTORY view, *5-122*
DBA_AUTOTASK_CLIENT_JOB view, *5-123*
DBA_AUTOTASK_JOB_HISTORY view, *5-123*
DBA_AUTOTASK_OPERATION view, *5-124*

DBA_AUTOTASK_SCHEDULE view, *5-124*
DBA_AUTOTASK_SCHEDULE_CONTROL view, *5-125*
DBA_AUTOTASK_SETTINGS view, *5-125*
DBA_AUTOTASK_STATUS view, *5-126*
DBA_AUTOTASK_TASK view, *5-126*
DBA_AUTOTASK_WINDOW_CLIENTS view, *5-129*
DBA_AUTOTASK_WINDOW_HISTORY view, *5-129*
DBA_AW_PS view, *5-130*
DBA_AWS view, *5-130*
DBA_BASE_TABLE_MVIEWS view, *5-130*
DBA_BLOCKCHAIN_ROW_VERSION_COLS view, *5-131*
DBA_BLOCKCHAIN_ROW_VERSION_HISTORY view, *5-131*
DBA_BLOCKCHAIN_TABLE_CHAINS view, *5-131*
DBA_BLOCKCHAIN_TABLE_EPOCHS view, *5-132*
DBA_BLOCKCHAIN_TABLE_HASH_COL_ORDER view, *5-132*
DBA_BLOCKCHAIN_TABLES view, *5-133*
DBA_BLOCKER_RESOLVER_PARAMETERS view, *5-133*
DBA_BLOCKERS view, *5-133*
DBA_CAPTURE view, *5-134*
DBA_CAPTURE_EXTRA_ATTRIBUTES view, *5-134*
DBA_CAPTURE_PARAMETERS view, *5-134*
DBA_CAPTURE_PREPARED_DATABASE view, *5-135*
DBA_CAPTURE_PREPARED_SCHEMAS view, *5-135*
DBA_CAPTURE_PREPARED_TABLES view, *5-135*
DBA_CATALOG view, *5-135*
DBA_CDB_RSRC_PLAN_DIRECTIVES view, *5-136*
DBA_CDB_RSRC_PLANS view, *5-137*
DBA_CERTIFICATES view, *5-137*
DBA_CHANGE_NOTIFICATION_REGS view, *5-137*
DBA_CHECKED_ROLES view, *5-138*
DBA_CHECKED_ROLES_PATH view, *5-139*
DBA_CLU_COLUMNS view, *5-139*
DBA_CLUSTER_HASH_EXPRESSIONS view, *5-140*
DBA_CLUSTERING_DIMENSIONS view, *5-140*
DBA_CLUSTERING_JOINS view, *5-140*
DBA_CLUSTERING_KEYS view, *5-141*
DBA_CLUSTERING_TABLES view, *5-141*
DBA_CLUSTERS view, *5-141*
DBA_CODE_ROLE_PRIVS view, *5-142*
DBA_COL_COMMENTS view, *5-142*
DBA_COL_PENDING_STATS view, *5-142*
DBA_COL_PRIVS view, *5-142*
DBA_COLL_TYPES view, *5-143*
DBA_COMMON_AUDIT_TRAIL view, *5-143*
DBA_COMPARISON view, *5-148*
DBA_COMPARISON_COLUMNS view, *5-149*
DBA_COMPARISON_ROW_DIF view, *5-149*
DBA_COMPARISON_SCAN view, *5-150*
DBA_COMPARISON_SCAN_VALUES view, *5-151*
DBA_CONNECT_ROLE_GRANTEES view, *5-151*
DBA_CONNECTION_TESTS view, *5-152*
DBA_CONS_COLUMNS view, *5-153*
DBA_CONS_OBJ_COLUMNS view, *5-153*
DBA_CONSTRAINTS view, *5-153*
DBA_CONTAINER_DATA view, *5-153*
DBA_CONTEXT view, *5-154*
DBA_CPOOL_INFO view, *5-155*
DBA_CPU_USAGE_STATISTICS view, *5-156*
DBA_CQ_NOTIFICATION_QUERIES view, *5-157*
DBA_CREDENTIALS view, *5-157*
DBA_CUBE_ATTR_VISIBILITY view, *5-158*
DBA_CUBE_ATTRIBUTES view, *5-158*
DBA_CUBE_BUILD_PROCESSES view, *5-158*
DBA_CUBE_CALCULATED_MEMBERS view, *5-158*
DBA_CUBE_DIM_LEVELS view, *5-159*
DBA_CUBE_DIM_MODELS view, *5-159*
DBA_CUBE_DIM_VIEW_COLUMNS view, *5-159*
DBA_CUBE_DIM_VIEWS view, *5-159*
DBA_CUBE_DIMENSIONALITY view, *5-160*
DBA_CUBE_DIMENSIONS view, *5-160*
DBA_CUBE_HIER_LEVELS view, *5-160*
DBA_CUBE_HIER_VIEW_COLUMNS view, *5-160*
DBA_CUBE_HIER_VIEWS view, *5-161*
DBA_CUBE_HIERARCHIES view, *5-161*
DBA_CUBE_MEASURES view, *5-161*
DBA_CUBE_NAMED_BUILD_SPECS view, *5-161*
DBA_CUBE_SUB_PARTITION_LEVELS view, *5-162*
DBA_CUBE_VIEW_COLUMNS view, *5-162*
DBA_CUBE_VIEWS view, *5-162*
DBA_CUBES view, *5-162*
DBA_DATA_FILES view, *5-163*
DBA_DATAPUMP_JOBS view, *5-164*
DBA_DATAPUMP_SESSIONS view, *5-165*
DBA_DB_LINK_SOURCES view, *5-166*
DBA_DB_LINKS view, *5-167*
DBA_DBFS_HS view, *5-167*
DBA_DBFS_HS_COMMANDS view, *5-168*

DBA_DBFS_HS_FIXED_PROPERTIES view, 5-168
DBA_DBFS_HS_PROPERTIES view, 5-169
DBA_DDL_LOCKS view, 5-169
DBA_DDL_REGS view, 5-170
DBA_DEPENDENCIES view, 5-171
DBA_DIGEST_VERIFIERS view, 5-171
DBA_DIM_ATTRIBUTES view, 5-172
DBA_DIM_CHILD_OF view, 5-172
DBA_DIM_HIERARCHIES view, 5-172
DBA_DIM_JOIN_KEY view, 5-172
DBA_DIM_LEVEL_KEY view, 5-173
DBA_DIM_LEVELS view, 5-173
DBA_DIMENSIONS view, 5-173
DBA_DIRECTORIES view, 5-173
DBA_DISCOVERY_SOURCE view, 5-174
DBA_DML_LOCKS view, 5-174
DBA_DMT_FREE_SPACE view, 5-175
DBA_DMT_USED_EXTENTS view, 5-175
DBA_DOMAIN_COLS view, 5-175
DBA_DOMAIN_CONSTRAINTS view, 5-176
DBA_DOMAINS view, 5-176
DBA_EDITION_COMMENTS view, 5-177
DBA_EDITIONED_TYPES view, 5-177
DBA_EDITIONING_VIEW_COLS view, 5-177
DBA_EDITIONING_VIEW_COLS_AE view, 5-178
DBA_EDITIONING_VIEWS view, 5-178
DBA_EDITIONING_VIEWS_AE view, 5-178
DBA_EDITIONS view, 5-178
DBA_ENABLED_AGGREGATIONS view, 5-179
DBA_ENABLED_TRACES view, 5-179
DBA_ENCRYPTED_COLUMNS view, 5-180
DBA_EPG_DAD_AUTHORIZATION view, 5-180
DBA_ERROR_TRANSLATIONS view, 5-181
DBA_ERRORS view, 5-181
DBA_ERRORS_AE view, 5-181
DBA_EVALUATION_CONTEXT_TABLES view, 5-181
DBA_EVALUATION_CONTEXT_VARS view, 5-182
DBA_EVALUATION_CONTEXTS view, 5-182
DBA_EXP_FILES view, 5-182
DBA_EXP_OBJECTS view, 5-182
DBA_EXP_VERSION view, 5-183
DBA_EXPRESSION_STATISTICS view, 5-183
DBA_EXTENTS view, 5-183
DBA_EXTERNAL_LOCATIONS view, 5-184
DBA_EXTERNAL_SCN_ACTIVITY view, 5-184
DBA_EXTERNAL_TABLES view, 5-187
DBA_FEATURE_USAGE_STATISTICS view, 5-187
DBA_FGA_AUDIT_TRAIL view, 5-188
DBA_FLASHBACK_ARCHIVE view, 5-189
DBA_FLASHBACK_ARCHIVE_TABLES view, 5-190
DBA_FLASHBACK_ARCHIVE_TS view, 5-191
DBA_FLASHBACK_TXN_REPORT view, 5-191
DBA_FLASHBACK_TXN_STATE view, 5-192
DBA_FREE_SPACE view, 5-192
DBA_FREE_SPACE_COALESCED view, 5-193
DBA_GG_AUTO_CDR_COLUMN_GROUPS view, 5-194
DBA_GG_AUTO_CDR_COLUMNS view, 5-194
DBA_GG_AUTO_CDR_TABLES view, 5-194
DBA_GG_INBOUND_PROGRESS view, 5-195
DBA_GG_PROC_OBJECT_EXCLUSION view, 5-195
DBA_GG_PROCEDURE_ANNOTATION view, 5-195
DBA_GG_SUPPORTED_PACKAGES view, 5-196
DBA_GG_SUPPORTED_PROCEDURES view, 5-196
DBA_GLOBAL_CONTEXT view, 5-197
DBA_GOLDENGATE_INBOUND view, 5-197
DBA_GOLDENGATE_NOT_UNIQUE view, 5-197
DBA_GOLDENGATE_PRIVILEGES view, 5-198
DBA_GOLDENGATE_RULES view, 5-198
DBA_GOLDENGATE_SUPPORT_MODE view, 5-198
DBA_HANG_MANAGER_PARAMETERS view, 5-200
DBA_HEAT_MAP_SEG_HISTOGRAM view, 5-200
DBA_HEAT_MAP_SEGMENT view, 5-200
DBA_HEATMAP_TOP_OBJECTS view, 5-200
DBA_HEATMAP_TOP_TABLESPACES view, 5-201
DBA_HIER_CLASS view, 5-202
DBA_HIER_CLASS_AE view, 5-202
DBA_HIER_COLUMNS view, 5-202
DBA_HIER_COLUMNS_AE view, 5-202
DBA_HIER_HIER_ATTR_CLASS view, 5-203
DBA_HIER_HIER_ATTR_CLASS_AE view, 5-203
DBA_HIER_HIER_ATTRIBUTES view, 5-203
DBA_HIER_HIER_ATTRIBUTES_AE view, 5-203
DBA_HIER_JOIN_PATHS view, 5-204
DBA_HIER_JOIN_PATHS_AE view, 5-204
DBA_HIER_LEVEL_ID_ATTRS view, 5-204
DBA_HIER_LEVEL_ID_ATTRS_AE view, 5-204
DBA_HIER_LEVELS view, 5-205
DBA_HIER_LEVELS_AE view, 5-205
DBA_HIERARCHIES view, 5-205
DBA_HIERARCHIES_AE view, 5-205
DBA_HIGH_WATER_MARK_STATISTICS view, 5-206

DBA_HIST_ACTIVE_SESS_HISTORY view, 5-207
DBA_HIST_APPLY_SUMMARY view, 5-213
DBA_HIST_ASH_SNAPSHOT view, 5-214
DBA_HIST_BASELINE view, 5-215
DBA_HIST_BASELINE_DETAILS view, 5-216
DBA_HIST_BASELINE_METADATA view, 5-217
DBA_HIST_BASELINE_TEMPLATE view, 5-218
DBA_HIST_BG_EVENT_SUMMARY view, 5-220
DBA_HIST_BUFFER_POOL_STAT view, 5-221
DBA_HIST_BUFFERED_QUEUES view, 5-222
DBA_HIST_BUFFERED_SUBSCRIBERS view, 5-223
DBA_HIST_CAPTURE view, 5-224
DBA_HIST_CHANNEL_WAITS view, 5-225
DBA_HIST_CLUSTER_INTERCON view, 5-226
DBA_HIST_COLORED_SQL view, 5-227
DBA_HIST_COMP_IOSTAT view, 5-228
DBA_HIST_CON_SYS_TIME_MODEL view, 5-228
DBA_HIST_CON_SYSMETRIC_HIST view, 5-229
DBA_HIST_CON_SYSMETRIC_SUMM view, 5-230
DBA_HIST_CON_SYSSTAT view, 5-231
DBA_HIST_CON_SYSTEM_EVENT view, 5-232
DBA_HIST_CR_BLOCK_SERVER view, 5-233
DBA_HIST_CURRENT_BLOCK_SERVER view, 5-234
DBA_HIST_DATABASE_INSTANCE view, 5-235
DBA_HIST_DATAFILE view, 5-237
DBA_HIST_DB_CACHE_ADVICE view, 5-237
DBA_HIST_DISPATCHER view, 5-238
DBA_HIST_DLM_MISC view, 5-239
DBA_HIST_DYN_REMASTER_STATS view, 5-240
DBA_HIST_ENQUEUE_STAT view, 5-241
DBA_HIST_EVENT_HISTOGRAM view, 5-242
DBA_HIST_EVENT_NAME view, 5-243
DBA_HIST_FILEMETRIC_HISTORY view, 5-244
DBA_HIST_FILESTATXS view, 5-245
DBA_HIST_IC_CLIENT_STATS view, 5-246
DBA_HIST_IC_DEVICE_STATS view, 5-247
DBA_HIST_IM_SEG_STAT view, 5-248
DBA_HIST_IM_SEG_STAT_OBJ view, 5-249
DBA_HIST_INST_CACHE_TRANSFER view, 5-249
DBA_HIST_INSTANCE_RECOVERY view, 5-252
DBA_HIST_INTERCONNECT_PINGS view, 5-254
DBA_HIST_IOSTAT_DETAIL view, 5-255
DBA_HIST_IOSTAT_FILETYPE view, 5-256
DBA_HIST_IOSTAT_FILETYPE_NAME view, 5-257
DBA_HIST_IOSTAT_FUNCTION view, 5-258
DBA_HIST_IOSTAT_FUNCTION_NAME view, 5-259
DBA_HIST_JAVA_POOL_ADVICE view, 5-260
DBA_HIST_LATCH view, 6-1
DBA_HIST_LATCH_CHILDREN view, 6-2
DBA_HIST_LATCH_MISSES_SUMMARY view, 6-3
DBA_HIST_LATCH_NAME view, 6-4
DBA_HIST_LATCH_PARENT view, 6-5
DBA_HIST_LIBRARYCACHE view, 6-6
DBA_HIST_LOG view, 6-7
DBA_HIST_MEM_DYNAMIC_COMP view, 6-8
DBA_HIST_MEMORY_RESIZE_OPS view, 6-10
DBA_HIST_MEMORY_TARGET_ADVICE view, 6-11
DBA_HIST_METRIC_NAME view, 6-12
DBA_HIST_MTTR_TARGET_ADVICE view, 6-12
DBA_HIST_MUTEX_SLEEP view, 6-14
DBA_HIST_OPTIMIZER_ENV view, 6-14
DBA_HIST_OPTIMIZER_ENV_DETAILS view, 6-15
DBA_HIST_OSSTAT view, 6-16
DBA_HIST_OSSTAT_NAME view, 6-16
DBA_HIST_PARAMETER view, 6-17
DBA_HIST_PARAMETER_NAME view, 6-18
DBA_HIST_PDB_IN_SNAP view, 6-19
DBA_HIST_PDB_INSTANCE view, 6-19
DBA_HIST_PERSISTENT_QMN_CACHE view, 6-20
DBA_HIST_PERSISTENT_QUEUES view, 6-21
DBA_HIST_PERSISTENT_SUBS view, 6-23
DBA_HIST_PGA_TARGET_ADVICE view, 6-24
DBA_HIST_PGASTAT view, 6-26
DBA_HIST_PLAN_OPERATION_NAME view, 6-27
DBA_HIST_PLAN_OPTION_NAME view, 6-27
DBA_HIST_PROCESS_MEM_SUMMARY view, 6-28
DBA_HIST_PROCESS_WAITTIME view, 6-29
DBA_HIST_RECOVERY_PROGRESS view, 6-29
DBA_HIST_REPLICATION_TBL_STATS view, 6-30
DBA_HIST_REPLICATION_TXN_STATS view, 6-31
DBA_HIST_REPORTS view, 6-32
DBA_HIST_REPORTS_CONTROL view, 6-33
DBA_HIST_REPORTS_DETAILS view, 6-34
DBA_HIST_REPORTS_TIMEBANDS view, 6-35
DBA_HIST_RESOURCE_LIMIT view, 6-36
DBA_HIST_ROWCACHE_SUMMARY view, 6-37
DBA_HIST_RSRC_CONSUMER_GROUP view, 6-38
DBA_HIST_RSRC_METRIC view, 6-41

DBA_HIST_RSRC_PDB_METRIC view, 6-42
DBA_HIST_RSRC_PLAN view, 6-44
DBA_HIST_RULE_SET view, 6-46
DBA_HIST_SAGAS view, 6-46
DBA_HIST_SEG_STAT view, 6-47
DBA_HIST_SEG_STAT_OBJ view, 6-50
DBA_HIST_SERVICE_NAME view, 6-50
DBA_HIST_SERVICE_STAT view, 6-51
DBA_HIST_SERVICE_WAIT_CLASS view, 6-52
DBA_HIST_SESS_SGA_STATS view, 6-53
DBA_HIST_SESS_TIME_STATS view, 6-53
DBA_HIST_SESSMETRIC_HISTORY view, 6-54
DBA_HIST_SGA view, 6-55
DBA_HIST_SGA_TARGET_ADVICE view, 6-56
DBA_HIST_SGASTAT view, 6-56
DBA_HIST_SHARED_POOL_ADVICE view, 6-57
DBA_HIST_SHARED_SERVER_SUMMARY view, 6-58
DBA_HIST_SNAP_ERROR view, 6-60
DBA_HIST_SNAPSHOT view, 6-61
DBA_HIST_SQL_BIND_METADATA view, 6-62
DBA_HIST_SQL_PLAN view, 6-63
DBA_HIST_SQL_SUMMARY view, 6-65
DBA_HIST_SQL_WORKAREA_HSTGRM view, 6-66
DBA_HIST_SQLBIND view, 6-67
DBA_HIST_SQLCOMMAND_NAME view, 6-68
DBA_HIST_SQLSTAT view, 6-69
DBA_HIST_SQLTEXT view, 6-74
DBA_HIST_STAT_NAME view, 6-74
DBA_HIST_STREAMS_APPLY_SUM view, 6-75
DBA_HIST_STREAMS_CAPTURE view, 6-77
DBA_HIST_STREAMS_POOL_ADVICE view, 6-77
DBA_HIST_SYS_TIME_MODEL view, 6-78
DBA_HIST_SYSMETRIC_HISTORY view, 6-79
DBA_HIST_SYSMETRIC_SUMMARY view, 6-80
DBA_HIST_SYSSTAT view, 6-81
DBA_HIST_SYSTEM_EVENT view, 6-82
DBA_HIST_TABLESPACE view, 6-83
DBA_HIST_TABLESPACE_STAT view, 6-83
DBA_HIST_TBSPC_SPACE_USAGE view, 6-84
DBA_HIST_TEMPFILE view, 6-85
DBA_HIST_TEMPSTATXS view, 6-86
DBA_HIST_THREAD view, 6-87
DBA_HIST_TOPLEVELCALL_NAME view, 6-87
DBA_HIST_UNDOSTAT view, 6-88
DBA_HIST_WAITCLASSMET_HISTORY view, 6-90
DBA_HIST_WAITSTAT view, 6-91
DBA_HIST_WR_CONTROL view, 6-92
DBA_HIST_WR_SETTINGS view, 6-92
DBA_HISTOGRAMS synonym for DBA_TAB_HISTOGRAMS, 6-93
DBA_HIVE_COLUMNS view, 6-93
DBA_HIVE_DATABASES view, 6-93
DBA_HIVE_PART_KEY_COLUMNS view, 6-94
DBA_HIVE_TAB_PARTITIONS view, 6-94
DBA_HIVE_TABLES view, 6-94
DBA_HOST_ACES view, 6-94
DBA_HOST_ACLS view, 6-95
DBA_IDENTIFIERS view, 6-95
DBA_ILMDATAMOVEMENTPOLICIES view, 6-96
DBA_ILMEVALUATIONDETAILS view, 6-97
DBA_ILMOBJECTS view, 6-98
DBA_ILMPARAMETERS view, 6-100
DBA_ILMPOLICIES view, 6-100
DBA_ILMRESULTS view, 6-101
DBA_ILMTASKS view, 6-102
DBA_IM_EXPRESSIONS view, 6-103
DBA_IMMUTABLE_ROW_VERSION_COLS view, 6-104
DBA_IMMUTABLE_ROW_VERSION_HISTORY view, 6-104
DBA_IMMUTABLE_TABLE_COLUMNS view, 6-105
DBA_IMMUTABLE_TABLE_EPOCHS view, 6-105
DBA_IMMUTABLE_TABLES view, 6-105
DBA_INCOMPLETE_SAGAS view, 6-106
DBA_IND_COLUMNS view, 6-106
DBA_IND_EXPRESSIONS view, 6-106
DBA_IND_PARTITIONS view, 6-106
DBA_IND_PENDING_STATS view, 6-107
DBA_IND_STATISTICS view, 6-107
DBA_IND_SUBPARTITIONS view, 6-107
DBA_INDEX_USAGE view, 6-107
DBA_INDEXES view, 6-109
  collecting statistics for, 6-107
DBA_INDEXTYPE_ARRAYTYPES view, 6-109
DBA_INDEXTYPE_COMMENTS view, 6-109
DBA_INDEXTYPE_OPERATORS view, 6-109
DBA_INDEXTYPES view, 6-110
DBA_INMEMORY_ADVISOR_RECOMMENDATION view, 6-110
DBA_INMEMORY_AIMTASKDETAILS view, 6-110
DBA_INMEMORY_AIMTASKS view, 6-111
DBA_INTERNAL_TRIGGERS view, 6-112
DBA_INVALID_OBJECTS view, 6-112
DBA_JAVA_ARGUMENTS view, 6-114
DBA_JAVA_CLASSES view, 6-114
DBA_JAVA_COMPILER_OPTIONS view, 6-114
DBA_JAVA_DERIVATIONS view, 6-114
DBA_JAVA_FIELDS view, 6-115
DBA_JAVA_IMPLEMENTS view, 6-115
DBA_JAVA_INNERS view, 6-115
DBA_JAVA_LAYOUTS view, 6-115

DBA_JAVA_METHODS view, 6-116
DBA_JAVA_NCOMPS view, 6-116
DBA_JAVA_POLICY view, 6-116
DBA_JAVA_RESOLVERS view, 6-117
DBA_JAVA_THROWS view, 6-117
DBA_JOBS view, 6-117
DBA_JOBS_RUNNING view, 6-118
DBA_JOIN_IND_COLUMNS view, 6-119
DBA_JOINGROUPS view, 6-119
DBA_JSON_COLLECTION_TABLES view, 6-120
DBA_JSON_COLLECTIONS view, 6-121
DBA_JSON_COLUMNS view, 6-121
DBA_JSON_DATAGUIDE_FIELDS view, 6-121
DBA_JSON_DATAGUIDES view, 6-122
DBA_JSON_DOMAIN_SCHEMA_COLUMNS view, 6-122
DBA_JSON_DUALITY_VIEW_LINKS view, 6-122
DBA_JSON_DUALITY_VIEW_TAB_COLS view, 6-123
DBA_JSON_DUALITY_VIEW_TABS view, 6-123
DBA_JSON_DUALITY_VIEWS view, 6-123
DBA_JSON_INDEXES view, 6-124
DBA_JSON_SCHEMA_COLUMNS view, 6-124
DBA_KAFKA_APPLICATIONS view, 6-124
DBA_KAFKA_CLUSTERS view, 6-126
DBA_KAFKA_LOAD_METRICS view, 6-127
DBA_KAFKA_OPS view, 6-128
DBA_KAFKA_OPS_RESULTS view, 6-129
DBA_KAFKA_PARTITIONS view, 6-130
DBA_KGLLOCK view, 6-131
DBA_LIBRARIES view, 6-131
DBA_LMT_FREE_SPACE view, 6-131
DBA_LMT_USED_EXTENTS view, 6-132
DBA_LOB_PARTITIONS view, 6-132
DBA_LOB_SUBPARTITIONS view, 6-132
DBA_LOB_TEMPLATES view, 6-133
DBA_LOBS view, 6-133
DBA_LOCK view, 6-133
  DBA_LOCKS synonym, 6-136
DBA_LOCK_INTERNAL view, 6-134
DBA_LOCKDOWN_PROFILES view, 6-134
DBA_LOCKS synonym for DBA_LOCK view, 6-136
DBA_LOG_GROUP_COLUMNS view, 6-136
DBA_LOG_GROUPS view, 6-136
DBA_LOGMNR_DICTIONARY_BUILDLOG view, 6-136
DBA_LOGMNR_LOG view, 6-137
DBA_LOGMNR_PURGED_LOG view, 6-138
DBA_LOGMNR_SESSION view, 6-138
DBA_LOGSTDBY_EVENTS view, 6-139
DBA_LOGSTDBY_HISTORY view, 6-140
DBA_LOGSTDBY_LOG view, 6-142
DBA_LOGSTDBY_NOT_UNIQUE view, 6-143
DBA_LOGSTDBY_PARAMETERS view, 6-144
DBA_LOGSTDBY_PLSQL_MAP view, 6-146
DBA_LOGSTDBY_PLSQL_SUPPORT view, 6-146
DBA_LOGSTDBY_PROGRESS view, 6-147
DBA_LOGSTDBY_SKIP view, 6-147
DBA_LOGSTDBY_SKIP_TRANSACTION view, 6-148
DBA_LOGSTDBY_SUPPORT_MODE view, 6-148
DBA_LOGSTDBY_UNSUPPORTED view, 6-149
DBA_LOGSTDBY_UNSUPPORTED_TABLE view, 6-150
  LOGSTDBY_UNSUPPORTED_TABLES synonym, 7-141
DBA_MEASURE_FOLDER_CONTENTS view, 6-151
DBA_MEASURE_FOLDER_SUBFOLDERS view, 6-151
DBA_MEASURE_FOLDERS view, 6-152
DBA_METADATA_PROPERTIES view, 6-152
DBA_METHOD_PARAMS view, 6-152
DBA_METHOD_RESULTS view, 6-152
DBA_MINING_MODEL_ATTRIBUTES view, 6-153
DBA_MINING_MODEL_PARTITIONS view, 6-153
DBA_MINING_MODEL_SETTINGS view, 6-153
DBA_MINING_MODEL_TABLES view, 6-153
DBA_MINING_MODEL_VIEWS view, 6-154
DBA_MINING_MODEL_XFORMS view, 6-154
DBA_MINING_MODELS view, 6-154
DBA_MLE_ENV_IMPORTS view, 6-155
DBA_MLE_ENVS view, 6-155
DBA_MLE_MODULES view, 6-155
DBA_MLE_PROCEDURES view, 6-156
DBA_MVIEW_AGGREGATES view, 6-156
DBA_MVIEW_ANALYSIS view, 6-157
DBA_MVIEW_COMMENTS view, 6-157
DBA_MVIEW_DETAIL_LOGICAL_PARTITION view, 6-157
DBA_MVIEW_DETAIL_PARTITION view, 6-158
DBA_MVIEW_DETAIL_RELATIONS view, 6-158
DBA_MVIEW_DETAIL_SUBPARTITION view, 6-158
DBA_MVIEW_JOINS view, 6-158
DBA_MVIEW_KEYS view, 6-159
DBA_MVIEW_LOG_FILTER_COLS view, 6-159
DBA_MVIEW_LOGS view, 6-159
DBA_MVIEW_REFRESH_TIMES view, 6-159
DBA_MVIEWS view, 6-160
DBA_MVREF_CHANGE_STATS view, 6-160
DBA_MVREF_RUN_STATS view, 6-161
DBA_MVREF_STATS view, 6-162
DBA_MVREF_STATS_PARAMS view, 6-163

DBA_MVREF_STATS_SYS_DEFAULTS view, 6-164
DBA_MVREF_STMT_STATS view, 6-164
DBA_NESTED_TABLE_COLS view, 6-165
DBA_NESTED_TABLES view, 6-165
DBA_NETWORK_ACL_PRIVILEGES view, 6-166
DBA_NETWORK_ACLS view, 6-166
DBA_OBJ_AUDIT_OPTS view, 6-167
DBA_OBJ_COLATTRS view, 6-168
DBA_OBJECT_SIZE view, 6-169
DBA_OBJECT_TABLES view, 6-169
DBA_OBJECT_USAGE view, 6-170
DBA_OBJECTS view, 6-170
DBA_OBJECTS_AE view, 6-171
DBA_OGG_AUTO_CAPTURED_TABLES view, 6-171
DBA_OPANCILLARY view, 6-171
DBA_OPARGUMENTS view, 6-172
DBA_OPBINDINGS view, 6-172
DBA_OPERATOR_COMMENTS view, 6-172
DBA_OPERATORS view, 6-172
DBA_OPTSTAT_OPERATION_TASKS view, 6-173
DBA_OPTSTAT_OPERATIONS view, 6-174
DBA_ORPHAN_KEY_TABLE view, 6-175
DBA_OUTLINE_HINTS view, 6-175
DBA_OUTLINES view, 6-176
DBA_OUTSTANDING_ALERTS view, 6-177
DBA_PARALLEL_EXECUTE_CHUNKS view, 6-178
DBA_PARALLEL_EXECUTE_TASKS view, 6-179
DBA_PART_COL_STATISTICS view, 6-181
DBA_PART_HISTOGRAMS view, 6-181
DBA_PART_INDEXES view, 6-181
DBA_PART_KEY_COLUMNS view, 6-181
DBA_PART_LOBS view, 6-182
DBA_PART_TABLES view, 6-182
DBA_PARTIAL_DROP_TABS view, 6-182
DBA_PDB_HISTORY view, 6-182
DBA_PDB_SAVED_STATES view, 6-183
DBA_PDB_SNAPSHOTFILE view, 6-184
DBA_PDB_SNAPSHOTS view, 6-184
DBA_PDBS view, 6-185
DBA_PENDING_CONV_TABLES view, 6-188
DBA_PENDING_TRANSACTIONS view, 6-188
DBA_PG_EDGE_RELATIONSHIPS view, 6-188
DBA_PG_ELEMENT_LABELS view, 6-189
DBA_PG_ELEMENTS view, 6-189
DBA_PG_KEYS view, 6-190
DBA_PG_LABEL_PROPERTIES view, 6-190
DBA_PG_LABELS view, 6-190
DBA_PG_PROP_DEFINITIONS view, 6-191
DBA_PLSQL_COLL_TYPES view, 6-191
DBA_PLSQL_OBJECT_SETTINGS view, 6-191
DBA_PLSQL_TYPE_ATTRS view, 6-192
DBA_PLSQL_TYPES view, 6-192
DBA_POLICIES view, 6-192
DBA_POLICY_ATTRIBUTES view, 6-192
DBA_POLICY_CONTEXTS view, 6-193
DBA_POLICY_GROUPS view, 6-193
DBA_PRIV_AUDIT_OPTS view, 6-193
DBA_PRIV_CAPTURES view, 6-194
DBA_PRIVATE_TEMP_TABLES view, 6-194
DBA_PROCEDURES view, 6-195
DBA_PROFILES view, 6-195
DBA_PROPAGATION view, 6-197
DBA_PROPERTY_GRAPHS view, 6-196
DBA_PROXIES view, 6-197
DBA_QUARANTINED_TRANSACTIONS view, 6-198
DBA_QUEUE_EVENT_STREAMS view, 6-199
DBA_QUEUE_SCHEDULES view, 6-199
DBA_QUEUE_SUBSCRIBERS view, 6-199
DBA_QUEUE_TABLES view, 6-199
DBA_QUEUES view, 6-200
DBA_RAT_CAPTURE_SCHEMA_INFO view, 6-200
DBA_RCHILD view, 6-201
DBA_RECOVERABLE_SCRIPT view, 6-201
DBA_RECOVERABLE_SCRIPT_BLOCKS view, 6-202
DBA_RECOVERABLE_SCRIPT_ERRORS view, 6-202
DBA_RECOVERABLE_SCRIPT_HIST view, 6-202
DBA_RECOVERABLE_SCRIPT_PARAMS view, 6-203
DBA_RECYCLEBIN view, 6-203
DBA_REDEFINITION_ERRORS view, 6-204
DBA_REDEFINITION_OBJECTS view, 6-205
DBA_REDEFINITION_STATUS view, 6-206
DBA_REFRESH view, 6-207
DBA_REFRESH_CHILDREN view, 6-207
DBA_REFS view, 6-207
DBA_REGISTERED_ARCHIVED_LOG view, 6-207
DBA_REGISTERED_MVIEWS view, 6-208
DBA_REGISTRY view, 6-208
DBA_REGISTRY_BACKPORTS view, 6-209
DBA_REGISTRY_HIERARCHY view, 6-210
DBA_REGISTRY_HISTORY view, 6-210
DBA_REGISTRY_LOG view, 6-211
DBA_REGISTRY_SCHEMAS view, 6-211
DBA_REGISTRY_SQLPATCH view, 6-212
DBA_REPAIR_TABLE view, 6-213
DBA_REPL_DBNAME_MAPPING view, 6-214
DBA_REPLICATION_PROCESS_EVENTS view, 6-214

DBA_RESOURCE_INCARNATIONS view, *6-215*
DBA_RESUMABLE view, *6-215*
DBA_REWRITE_EQUIVALENCES view, *6-216*
DBA_RGROUP view, *6-216*
DBA_ROLE_PRIVS view, *6-217*
DBA_ROLES view, *6-218*
DBA_ROLLBACK_SEGS view, *6-218*
DBA_ROLLING_DATABASES view, *6-219*
DBA_ROLLING_EVENTS view, *6-220*
DBA_ROLLING_PARAMETERS view, *6-221*
DBA_ROLLING_PLAN view, *6-221*
DBA_ROLLING_STATISTICS view, *6-222*
DBA_ROLLING_STATUS view, *6-223*
DBA_ROLLING_SUPPORT_MODE view, *6-224*
DBA_ROLLING_UNSUPPORTED view, *6-224*
DBA_RSRC_CATEGORIES view, *6-225*
DBA_RSRC_CONSUMER_GROUP_PRIVS view, *6-226*
DBA_RSRC_CONSUMER_GROUPS view, *6-226*
DBA_RSRC_GROUP_MAPPINGS view, *6-227*
DBA_RSRC_IO_CALIBRATE view, *6-227*
DBA_RSRC_MANAGER_SYSTEM_PRIVS view, *6-228*
DBA_RSRC_MAPPING_PRIORITY view, *6-228*
DBA_RSRC_PLAN_DIRECTIVES view, *6-229*
DBA_RSRC_PLANS view, *6-232*
DBA_RULE_SET_RULES view, *6-233*
DBA_RULE_SETS view, *6-233*
DBA_RULES view, *6-233*
DBA_SAGA_BROKERS view, *6-234*
DBA_SAGA_DETAILS view, *6-234*
DBA_SAGA_ERRORS view, *6-234*
DBA_SAGA_FINALIZATION view, *6-235*
DBA_SAGA_PARTICIPANT_SET view, *6-235*
DBA_SAGA_PARTICIPANTS view, *6-236*
DBA_SAGA_PENDING view, *6-236*
DBA_SAGAS view, *6-236*
DBA_SCHEDULER_CHAIN_RULES view, *6-237*
DBA_SCHEDULER_CHAIN_STEPS view, *6-237*
DBA_SCHEDULER_CHAINS view, *6-238*
DBA_SCHEDULER_CREDENTIALS view, *6-238*
DBA_SCHEDULER_DB_DESTS view, *6-238*
DBA_SCHEDULER_DESTS view, *6-239*
DBA_SCHEDULER_EXTERNAL_DESTS view, *6-239*
DBA_SCHEDULER_FILE_WATCHERS view, *6-239*
DBA_SCHEDULER_GLOBAL_ATTRIBUTE view, *6-239*
DBA_SCHEDULER_GROUP_MEMBERS view, *6-240*
DBA_SCHEDULER_GROUPS view, *6-240*
DBA_SCHEDULER_IN_MEMORY_TRACE view, *6-240*
DBA_SCHEDULER_INCOMPAT_MEMBER view, *6-241*
DBA_SCHEDULER_INCOMPATS view, *6-241*
DBA_SCHEDULER_JOB_ARGS view, *6-241*
DBA_SCHEDULER_JOB_CLASSES view, *6-241*
DBA_SCHEDULER_JOB_DESTS view, *6-242*
DBA_SCHEDULER_JOB_LOG view, *6-242*
DBA_SCHEDULER_JOB_ROLES view, *6-242*
DBA_SCHEDULER_JOB_RUN_DETAILS view, *6-243*
DBA_SCHEDULER_JOBS view, *6-244*
DBA_SCHEDULER_NOTIFICATIONS view, *6-244*
DBA_SCHEDULER_PROGRAM_ARGS view, *6-244*
DBA_SCHEDULER_PROGRAMS view, *6-244*
DBA_SCHEDULER_REMOTE_DATABASES view, *6-245*
DBA_SCHEDULER_REMOTE_JOBSTATE view, *6-245*
DBA_SCHEDULER_RESOURCES view, *6-245*
DBA_SCHEDULER_RSC_CONSTRAINTS view, *6-245*
DBA_SCHEDULER_RUNNING_CHAINS view, *6-246*
DBA_SCHEDULER_RUNNING_JOBS view, *6-246*
DBA_SCHEDULER_SCHEDULES view, *6-246*
DBA_SCHEDULER_WINDOW_DETAILS view, *6-246*
DBA_SCHEDULER_WINDOW_GROUPS view, *6-247*
DBA_SCHEDULER_WINDOW_LOG view, *6-247*
DBA_SCHEDULER_WINDOWS view, *6-247*
DBA_SCHEDULER_WINGROUP_MEMBERS view, *6-247*
DBA_SCHEMA_PRIVS view, *6-248*
DBA_SEC_RELEVANT_COLS view, *6-248*
DBA_SECONDARY_OBJECTS view, *6-249*
DBA_SEGMENTS view, *6-249*
DBA_SEGMENTS_OLD view, *6-252*
DBA_SENSITIVE_COLUMN_TYPES view, *6-252*
DBA_SENSITIVE_DATA view, *6-253*
DBA_SEQUENCES view, *6-254*
DBA_SERVER_REGISTRY view, *6-254*
DBA_SERVICES view, *6-255*
DBA_SOURCE view, *6-255*
DBA_SOURCE_AE view, *6-255*
DBA_SQL_ERROR_MITIGATIONS view, *6-255*
DBA_SQL_FIREWALL_ALLOW_LISTS view, *6-256*
DBA_SQL_FIREWALL_ALLOWED_IP_ADDR view, *6-257*

DBA_SQL_FIREWALL_ALLOWED_OS_PROG view, 6-257
DBA_SQL_FIREWALL_ALLOWED_OS_USER view, 6-258
DBA_SQL_FIREWALL_ALLOWED_SQL view, 6-258
DBA_SQL_FIREWALL_CAPTURE_LOGS view, 6-259
DBA_SQL_FIREWALL_CAPTURES view, 6-260
DBA_SQL_FIREWALL_SESSION_LOGS view, 6-260
DBA_SQL_FIREWALL_SQL_LOGS view, 6-261
DBA_SQL_FIREWALL_STATUS view, 6-261
DBA_SQL_FIREWALL_VIOLATIONS view, 6-262
DBA_SQL_MANAGEMENT_CONFIG view, 6-263
DBA_SQL_PATCHES view, 6-264
DBA_SQL_PLAN_BASELINES view, 6-265
DBA_SQL_PLAN_DIR_OBJECTS view, 6-267
DBA_SQL_PLAN_DIRECTIVES view, 6-268
DBA_SQL_PROFILES view, 6-269
DBA_SQL_QUARANTINE view, 6-263
DBA_SQL_TRANSLATION_PROFILES view, 6-270
DBA_SQL_TRANSLATIONS view, 6-270
DBA_SQLJ_TYPE_ATTRS view, 6-270
DBA_SQLJ_TYPE_METHODS view, 6-271
DBA_SQLJ_TYPES view, 6-271
DBA_SQLSET view, 6-271
DBA_SQLSET_BINDS view, 6-271
DBA_SQLSET_PLANS view, 6-272
DBA_SQLSET_REFERENCES view, 6-272
DBA_SQLSET_STATEMENTS view, 6-272
DBA_SQLTUNE_BINDS view, 6-274
DBA_SQLTUNE_PLANS view, 6-274
DBA_SQLTUNE_RATIONALE_PLAN view, 6-277
DBA_SQLTUNE_STATISTICS view, 6-278
DBA_SR_GRP_STATUS view, 6-279
DBA_SR_GRP_STATUS_ALL view, 6-280
DBA_SR_OBJ view, 6-282
DBA_SR_OBJ_ALL view, 6-282
DBA_SR_OBJ_STATUS view, 6-283
DBA_SR_OBJ_STATUS_ALL view, 6-284
DBA_SR_PARTN_OPS view, 6-285
DBA_SR_STLOG_EXCEPTIONS view, 6-286
DBA_SR_STLOG_STATS view, 6-286
DBA_SSCR_CAPTURE view, 6-287
DBA_SSCR_RESTORE view, 6-288
DBA_STAT_EXTENSIONS view, 6-289
DBA_STATEMENTS view, 6-289
DBA_STMT_AUDIT_OPTS view, 6-289
DBA_STORED_SETTINGS view, 6-290
DBA_STREAMS_ADD_COLUMN view, 7-1
DBA_STREAMS_DELETE_COLUMN view, 7-1
DBA_STREAMS_GLOBAL_RULES view, 7-2
DBA_STREAMS_KEEP_COLUMNS view, 7-2
DBA_STREAMS_MESSAGE_CONSUMERS view, 7-3
DBA_STREAMS_NEWLY_SUPPORTED view, 7-3
DBA_STREAMS_RENAME_COLUMN view, 7-3
DBA_STREAMS_RENAME_SCHEMA view, 7-4
DBA_STREAMS_RENAME_TABLE view, 7-4
DBA_STREAMS_SCHEMA_RULES view, 7-4
DBA_STREAMS_TABLE_RULES view, 7-5
DBA_STREAMS_TP_COMPONENT view, 7-5
DBA_STREAMS_TP_COMPONENT_LINK view, 7-5
DBA_STREAMS_TP_COMPONENT_STAT view, 7-6
DBA_STREAMS_TP_DATABASE view, 7-7
DBA_STREAMS_TP_PATH_BOTTLENECK view, 7-7
DBA_STREAMS_TP_PATH_STAT view, 7-8
DBA_STREAMS_TRANSFORM_FUNCTION view, 7-8
DBA_SUBPART_COL_STATISTICS view, 7-9
DBA_SUBPART_HISTOGRAMS view, 7-9
DBA_SUBPART_KEY_COLUMNS view, 7-9
DBA_SUBPARTITION_TEMPLATES view, 7-9
DBA_SUBSCR_REGISTRATIONS view, 7-10
DBA_SUPPLEMENTAL_LOGGING view, 7-11
DBA_SYNC_CAPTURE view, 7-12
DBA_SYNC_CAPTURE_PREPARED_TABS view, 7-12
DBA_SYNC_CAPTURE_TABLES view, 7-12
DBA_SYNONYMS view, 7-13
DBA_SYS_PRIVS view, 7-13
DBA_SYS_PRIVS_ALL view, 7-13
DBA_TAB_COL_STAT_MODELS view, 7-14
DBA_TAB_COL_STATISTICS view, 7-15
DBA_TAB_COLS view, 7-15
DBA_TAB_COLUMNS view, 7-18
DBA_TAB_COMMENTS view, 7-21
DBA_TAB_HISTGRM_PENDING_STATS view, 7-21
DBA_TAB_HISTOGRAMS view, 7-22
DBA_HISTOGRAMS synonym, 6-93
DBA_TAB_IDENTITY_COLS view, 7-22
DBA_TAB_MODIFICATIONS view, 7-22
DBA_TAB_PARTITIONS view, 7-22
DBA_TAB_PENDING_STATS view, 7-23
DBA_TAB_PRIVS view, 7-23
DBA_TAB_STAT_PREFS view, 7-24
DBA_TAB_STATISTICS view, 7-24
DBA_TAB_STATS_HISTORY view, 7-24
DBA_TAB_SUBPARTITIONS view, 7-24
DBA_TABLE_ACCESS_STATS view, 7-25

DBA_TABLE_VIRTUAL_COLUMNS view, 7-25
DBA_TABLES view, 7-25
DBA_TABLESPACE_GROUPS view, 7-26
DBA_TABLESPACE_THRESHOLDS view, 7-26
DBA_TABLESPACE_USAGE_METRICS view, 7-27
DBA_TABLESPACES view, 7-28
DBA_TEMP_FILES view, 7-32
DBA_TEMP_FREE_SPACE view, 7-32
DBA_THRESHOLDS view, 7-33
DBA_TRANSFORMATIONS view, 7-34
DBA_TRIGGER_COLS view, 7-34
DBA_TRIGGER_ORDERING view, 7-35
DBA_TRIGGERS view, 7-35
DBA_TRIGGERS_AE view, 7-35
DBA_TS_QUOTAS view, 7-35
DBA_TSDP_IMPORT_ERRORS view, 7-36
DBA_TSDP_POLICY_CONDITION view, 7-36
DBA_TSDP_POLICY_FEATURE view, 7-37
DBA_TSDP_POLICY_PARAMETER view, 7-37
DBA_TSDP_POLICY_PROTECTION view, 7-38
DBA_TSDP_POLICY_TYPE view, 7-39
DBA_TSM_DESTINATION view, 7-39
DBA_TSM_SOURCE view, 7-40
DBA_TSTZ_TAB_COLS view, 7-40
DBA_TSTZ_TABLES view, 7-41
DBA_TUNE_MVIEW view, 7-41
DBA_TXEVENTQ_MIGRATION_STATUS view, 7-41
DBA_TYPE_ATTRS view, 7-42
DBA_TYPE_METHODS view, 7-43
DBA_TYPE_VERSIONS view, 7-43
DBA_TYPES view, 7-43
DBA_UMF_LINK view, 7-43
DBA_UMF_REGISTRATION view, 7-44
DBA_UMF_SERVICE view, 7-45
DBA_UMF_TOPOLOGY view, 7-45
DBA_UNDO_EXTENTS view, 7-46
DBA_UNUSED_COL_TABS view, 7-47
DBA_UNUSED_GRANTS view, 7-47
DBA_UNUSED_OBJPRIVS view, 7-48
DBA_UNUSED_OBJPRIVS_PATH view, 7-49
DBA_UNUSED_PRIVS view, 7-50
DBA_UNUSED_SCHEMA_PRIVS view, 7-51
DBA_UNUSED_SCHEMA_PRIVS_PATH view, 7-52
DBA_UNUSED_SYSPRIVS view, 7-53
DBA_UNUSED_SYSPRIVS_PATH view, 7-53
DBA_UNUSED_USERPRIVS view, 7-54
DBA_UNUSED_USERPRIVS_PATH view, 7-55
DBA_UPDATABLE_COLUMNS view, 7-56
DBA_USED_OBJPRIVS view, 7-56
DBA_USED_OBJPRIVS_PATH view, 7-57
DBA_USED_PRIVS view, 7-58
DBA_USED_PUBPRIVS view, 7-59
DBA_USED_SCHEMA_PRIVS view, 7-60
DBA_USED_SCHEMA_PRIVS_PATH view, 7-61
DBA_USED_SYSPRIVS view, 7-62
DBA_USED_SYSPRIVS_PATH view, 7-63
DBA_USED_USERPRIVS view, 7-64
DBA_USED_USERPRIVS_PATH view, 7-65
DBA_USERS view, 7-66
DBA_USERS_WITH_DEFPWD view, 7-72
DBA_USTATS view, 7-72
DBA_VARRAYS view, 7-73
DBA_VIEWS view, 7-73
DBA_VIEWS_AE view, 7-73
DBA_WAITERS view, 7-73
DBA_WALLET_ACES view, 7-74
DBA_WALLET_ACLS view, 7-74
DBA_WARNING_SETTINGS view, 7-75
DBA_WI_CAPTURE_FILES view, 7-75
DBA_WI_JOBS view, 7-75
DBA_WI_OBJECTS view, 7-76
DBA_WI_PATTERN_ITEMS view, 7-76
DBA_WI_PATTERNS view, 7-77
DBA_WI_STATEMENTS view, 7-77
DBA_WI_TEMPLATE_EXECUTIONS view, 7-78
DBA_WI_TEMPLATES view, 7-78
DBA_WORKLOAD_ACTIVE_USER_MAP view, 7-79
DBA_WORKLOAD_CAPTURE_SQLTEXT view, 7-79
DBA_WORKLOAD_CAPTURES view, 7-80
DBA_WORKLOAD_CONNECTION_MAP view, 7-83
DBA_WORKLOAD_DIV_SUMMARY view, 7-83
DBA_WORKLOAD_FILTERS view, 7-85
DBA_WORKLOAD_GROUP_ASSIGNMENTS view, 7-85
DBA_WORKLOAD_LONG_SQLTEXT view, 7-86
DBA_WORKLOAD_REPLAY_CLIENTS view, 7-86
DBA_WORKLOAD_REPLAY_DIVERGENCE view, 7-87
DBA_WORKLOAD_REPLAY_SCHEDULES view, 7-88
DBA_WORKLOAD_REPLAYS view, 7-89
DBA_WORKLOAD_SCHEDULE_CAPTURES view, 7-94
DBA_WORKLOAD_SCHEDULE_ORDERING view, 7-96
DBA_WORKLOAD_SQL_MAP view, 7-96
DBA_WORKLOAD_TRACKED_COMMITS view, 7-97
DBA_WORKLOAD_USER_MAP view, 7-97
DBA_XML_INDEXES view, 7-98
DBA_XML_NESTED_TABLES view, 7-98
DBA_XML_OUT_OF_LINE_TABLES view, 7-99
DBA_XML_SCHEMA_ATTRIBUTES view, 7-99

DBA_XML_SCHEMA_COMPLEX_TYPES view, *7-99*
DBA_XML_SCHEMA_ELEMENTS view, *7-99*
DBA_XML_SCHEMA_NAMESPACES view, *7-100*
DBA_XML_SCHEMA_SIMPLE_TYPES view, *7-100*
DBA_XML_SCHEMA_SUBSTGRP_HEAD view, *7-100*
DBA_XML_SCHEMA_SUBSTGRP_MBRS view, *7-100*
DBA_XML_SCHEMAS view, *7-101*
DBA_XML_TAB_COLS view, *7-101*
DBA_XML_TABLES view, *7-101*
DBA_XML_VIEW_COLS view, *7-101*
DBA_XML_VIEWS view, *7-102*
DBA_XS_AUDIT_POLICY_OPTIONS view, *7-102*
DBA_XS_AUDIT_TRAIL view, *7-102*
DBA_XS_ENABLED_AUDIT_POLICIES view, *7-104*
DBA_XS_ENB_AUDIT_POLICIES view, *7-104*
DBA_XSTREAM_ADMINISTRATOR view, *7-105*
DBA_XSTREAM_INBOUND view, *7-105*
DBA_XSTREAM_INBOUND_PROGRESS view, *7-105*
DBA_XSTREAM_OUT_SUPPORT_MODE view, *7-106*
DBA_XSTREAM_OUTBOUND view, *7-106*
DBA_XSTREAM_OUTBOUND_PROGRESS view, *7-106*
DBA_XSTREAM_RULES view, *7-106*
DBA_XSTREAM_SPLIT_MERGE view, *7-107*
DBA_XSTREAM_SPLIT_MERGE_HIST view, *7-108*
DBA_XSTREAM_STMT_HANDLERS view, *7-110*
DBA_XSTREAM_STMTS view, *7-110*
DBA_XSTREAM_TRANSFORMATIONS view, *7-111*
DBA_XTERNAL_LOC_PARTITIONS view, *7-111*
DBA_XTERNAL_LOC_SUBPARTITIONS view, *7-111*
DBA_XTERNAL_PART_TABLES view, *7-112*
DBA_XTERNAL_TAB_PARTITIONS view, *7-112*
DBA_XTERNAL_TAB_SUBPARTITIONS view, *7-112*
DBA_ZONEMAP_AUTO_ACTIONS view, *7-112*
DBA_ZONEMAP_AUTO_FINDINGS view, *7-113*
DBA_ZONEMAP_MEASURES view, *7-114*
DBA_ZONEMAPS view, *7-114*
DBFIPS_140 initialization parameter, *2-116*
DBFS_CONTENT view, *7-114*
DBFS_CONTENT_PROPERTIES view, *7-116*
DBMS_ALERT_INFO view, *7-117*
DBMS_KAFKA_APPLICATIONS table, *7-117*
DBMS_KAFKA_CLUSTERS table, *7-118*
DBMS_KAFKA_LOAD_METRICS table, *7-120*
DBMS_KAFKA_MESSAGES table, *7-121*
DBMS_KAFKA_OPS table, *7-121*
DBMS_KAFKA_OPS_RESULTS table, *7-123*
DBMS_KAFKA_PARTITIONS table, *7-123*
DBMS_KAFKA_SEC_ALLOWED_PROPERTIES table, *7-124*
DBMS_LOCK_ALLOCATED view, *7-126*
DBMS_METADATA_PARSE_ITEMS view, *7-126*
DBMS_METADATA_TRANSFORM_PARAMS view, *7-127*
DBMS_METADATA_TRANSFORMS view, *7-127*
DBMS_STATS package, *3-218*, *3-290*, *4-128*, *4-132*, *4-159*, *6-107*, *6-165*, *7-15*, *7-18*, *7-25*, *7-279*, *7-322*, *7-327*
DBMSIOTC.SQL script, *B-3*
DBMSPOOL.SQL script, *B-3*
DBNEST_ENABLE initialization parameter, *2-117*
DBNEST_PDB_FS_CONF initialization parameter, *2-118*
DBWR_IO_SLAVES initialization parameter, *2-118*
DDL_LOCK_TIMEOUT initialization parameter, *2-119*
DEFAULT_SHARING initialization parameter, *2-120*
DEFERRED_SEGMENT_CREATION initialization parameter, *2-120*
DEPTREE view, *7-128*
destination
  archiving redo log files, *2-198*
  overriding default, *2-198*
  USER_DUMP_DEST, *2-401*
DG_BROKER_CONFIG_FILEn initialization parameter, *2-121*
DG_BROKER_START initialization parameter, *2-121*
DIAGNOSTIC_DEST initialization parameter, *2-122*
DIAGNOSTICS_CONTROL initialization parameter, *2-123*
DICT synonym for DICTIONARY, *7-128*
DICT_COLUMNS view, *7-128*
DICTIONARY view, *7-129*
  DICT synonym, *7-128*
DICTIONARY_CREDENTIALS_ENCRYPT view, *7-129*
disk drives
  archiving destination, *2-198*
DISK_ASYNCH_IO initialization parameter, *2-124*
dispatcher processes
  maximum number, *2-220*

DISPATCHERS initialization parameter, 2-125
distinguished name, 2-316
DISTRIBUTED_LOCK_TIMEOUT initialization parameter, 2-127
DM_USER_MODELS view, 7-129
DML_LOCKS initialization parameter, 2-128
DNFS_BATCH_SIZE initialization parameter, 2-129
DOCUMENT_LINKS view, 7-131
DRCP_DEDICATED_OPT initialization parameter, 2-129
DST_UPGRADE_INSERT_CONV initialization parameter, 2-130
dump files, 2-221
dynamic performance tables
  CATALOG.SQL script, 8-1
  public synonyms (V$), 8-2
  views (V_$), 8-2

E

embedded initialization parameter files, 2-158
ENABLE_AUTOMATIC_MAINTENANCE_PDB initialization parameter, 2-131
ENABLE_DDL_LOGGING initialization parameter, 2-132
ENABLE_DNFS_DISPATCHER initialization parameter, 2-134
ENABLE_GOLDENGATE_REPLICATION initialization parameter, 2-134
ENABLE_IMC_WITH_MIRA initialization parameter, 2-135
ENABLE_PER_PDB_DRCP initialization parameter, 2-136
ENABLE_PLUGGABLE_DATABASE initialization parameter, 2-137
ENABLED_PDBS_ON_STANDBY initialization parameter, 2-137
ENCRYPT_NEW_TABLESPACES initialization parameter, 2-139
enqueues, D-1
  AJV snapshot refresh, D-2
  ALTER SYSTEM SET PARAMETER = VALUE, D-2
  backup/restore, D-1
  being written redo log, D-3
  bind, D-1
  cross-instance call invocation, D-1
  database mount, D-1
  datafile, D-1
  direct loader index creation, D-1
  disabling, 2-128
  distributed recovery process, D-1
  distributed transaction, D-1
  DML, D-2
enqueues *(continued)*
  exclusive lock when moving audit table, D-3
  extend table, D-2
  file set, D-1
  high-water lock, D-1
  instance attribute lock, D-3
  instance number, D-1
  instance recovery, D-1
  instance registration lock, D-3
  instance state, D-1
  job queue, D-2
  library cache invalidation, D-2
  library cache lock, D-2
  library cache pin, D-2
  log start or switch, D-2
  media recovery, D-2
  mount definition, D-2
  object reuse, D-2
  parallel slave synchronization, D-2
  parallel slaves, D-2
  password file, D-2
  process startup, D-2
  redo log "kick", D-2
  redo thread, D-2
  row cache, D-2
  row wait, D-2
  sequence number, D-2
  sequence number value, D-2
  SMON, D-2
  sort segment, D-2
  space management transaction, D-2
  synchronized replication, D-2
  system commit number, D-2
  temporary segment, D-2
  temporary table, D-2
  temporary table object, D-2
  thread checkpoint, D-2
  transaction, D-2
  transaction recovery, D-2
  undo segment, serialization, D-3
  user name, D-3
  user-defined locks, D-2
enterprise roles, 2-316
ERROR_MESSAGE_DETAILS initialization parameter, 2-140
ERROR_SIZE view, 7-132
EVENT initialization parameter, 2-141
EXCEPTIONS table, 7-132
extent
  allocating to instance, 2-178
EXTERNAL_KEYSTORE_CREDENTIAL_LOCATION initialization parameter, 2-141

F

FAL_CLIENT initialization parameter, *2-142*
FAL_SERVER initialization parameter, *2-143*
FAST_START_MTTR_TARGET initialization parameter, *2-143*
FAST_START_PARALLEL_ROLLBACK initialization parameter, *2-144*
FILE_MAPPING initialization parameter, *2-145*
FILEIO_NETWORK_ADAPTERS initialization parameter, *2-145*
filenames
  case significance, *2-5*
FILESYSTEMIO_OPTIONS initialization parameter, *2-146*
FIXED_DATE initialization parameter, *2-146*
FLASHBACK_TRANSACTION_QUERY view, *7-133*
FORWARD_LISTENER initialization parameter, *2-147*
free space list
  locating space, *2-178*
FREELIST GROUPS clause, *2-178*

G

GCS_SERVER_PROCESSES initialization parameter, *2-148*
GLOBAL_CONTEXT view, *7-133*
GLOBAL_NAME view, *7-134*
GLOBAL_NAMES initialization parameter, *2-148*
GLOBAL_TXN_PROCESSES initialization parameter, *2-149*
GROUP_BY_POSITION_ENABLED initialization parameter, *2-150*
GV$ views
  for Real Application Clusters, *8-2*

H

HASH_AREA_SIZE initialization parameter, *2-151*
HEARTBEAT_BATCH_SIZE initialization parameter, *2-152*
HEAT_MAP initialization parameter, *2-152*
Heterogeneous Services
  agents, *2-153*
HI_SHARED_MEMORY_ADDRESS initialization parameter, *2-153*
hierarchies
  analytic view, *3-36*, *3-193*, *3-194*
  classifications, *3-181*, *3-182*
  columns, *3-183*, *3-184*
  hierarchical attribute classifications, *3-185*, *3-186*
hierarchies *(continued)*
  hierarchical attributes, *3-187*, *3-188*
  join paths, *3-189*
  level ID attributes, *3-190*, *3-191*
  levels, *3-192*
hints
  precedence over initialization parameter settings, *2-357*
HS_ALL_CAPS view, *7-134*
HS_ALL_DD view, *7-134*
HS_ALL_INITS view, *7-135*
HS_AUTOREGISTER initialization parameter, *2-153*
HS_BASE_CAPS view, *7-135*
HS_BASE_DD view, *7-135*
HS_CLASS_CAPS view, *7-136*
HS_CLASS_DD view, *7-136*
HS_CLASS_INIT view, *7-136*
HS_FDS_CLASS view, *7-137*
HS_FDS_INST view, *7-137*
HS_INST_CAPS view, *7-137*
HS_INST_DD view, *7-138*
HS_INST_INIT view, *7-138*
HYBRID_READ_ONLY initialization parameter, *2-154*

I

I/O
  reading multiple blocks, *2-98*
  redo log files, *2-212*
IDENTITY_PROVIDER_CONFIG initialization parameter, *2-155*
IDENTITY_PROVIDER_TYPE initialization parameter, *2-156*
IDEPTREE view, *7-139*
IFILE initialization parameter, *2-6*, *2-157*
IGNORE_SESSION_SET_PARAM_ERRORS initialization parameter, *2-158*
IM column store. See In-Memory Column Store, *2-161*
IM scan EUs memcompress for capacity high, *E-22*
IN-list iterators
  optimizer use of, *2-268*
In-Memory Column Store, *2-161*, *2-168*, *2-171*, *2-172*
IND synonym for USER_INDEXES view, *7-139*
INDEX_HISTOGRAM view, *7-139*
INDEX_STATS view, *7-140*
INIT.ORA file
  See initialization parameter file
initialization parameter file,
  character set to use in, *2-5*
  common file, *2-158*

initialization parameter file *(continued)*
embedded, *2-158*
INITDW.ORA, *2-4*
line continuation character, *2-6*
overview, *2-3*
initialization parameters
ACTIVE_INSTANCE_COUNT, *2-30*
ADG_ACCOUNT_INFO_TRACKING, *2-31*
ADG_REDIRECT_DML, *2-32*
ALLOW_GLOBAL_DBLINKS, *2-33*
ALLOW_GROUP_ACCESS_TO_SGA, *2-33*
ALLOW_LEGACY_RECO_PROTOCOL, *2-34*
ALLOW_ROWID_COLUMN_TYPE, *2-35*
altering, *2-9*
APPROX_FOR_AGGREGATION, *2-36*
APPROX_FOR_COUNT_DISTINCT, *2-36*
APPROX_FOR_PERCENTILE, *2-37*
AQ_TM_PROCESSES, *2-38*
ARCHIVE_LAG_TARGET, *2-39*
ASM_DISKGROUPS, *2-40*
ASM_DISKSTRING, *2-41*
ASM_IO_PROCESSES, *2-42*
ASM_POWER_LIMIT, *2-42*
ASM_PREFERRED_READ_FAILURE_GROUPS, *2-43*
AUDIT_FILE_DEST, *2-44*
AUDIT_SYS_OPERATIONS, *2-45*
AUDIT_SYSLOG_LEVEL, *2-46*
AUDIT_TRAIL, *2-48*
AUTOTASK_MAX_ACTIVE_PDBS, *2-50*
AWR_PDB_AUTOFLUSH_ENABLED, *2-51*
AWR_PDB_MAX_PARALLEL_SLAVES, *2-52*
AWR_SNAPSHOT_TIME_OFFSET, *2-52*
BACKGROUND_CORE_DUMP, *2-53*
BACKGROUND_DUMP_DEST, *2-54*
BACKUP_TAPE_IO_SLAVES, *2-55*
basic, *2-3*
BITMAP_MERGE_AREA_SIZE, *2-56*
BLANK_TRIMMING, *2-56*
BLOCKCHAIN_TABLE_MAX_NO_DROP, *2-57*
BLOCKCHAIN_TABLE_RETENTION_THRESHOLD, *2-58*
case significance in filenames, *2-5*
CDB_COMPATIBLE, *2-254*
CIRCUITS, *2-59*
CLIENT_RESULT_CACHE_LAG, *2-59*
CLIENT_RESULT_CACHE_SIZE, *2-60*
CLIENT_STATISTICS_LEVEL, *2-60*
CLONEDB, *2-62*
CLONEDB_DIR, *2-63*
CLUSTER_DATABASE, *2-63*
CLUSTER_INTERCONNECTS, *2-64*
COMMIT_LOGGING, *2-65*
COMMIT_POINT_STRENGTH, *2-65*
COMMIT_WAIT, *2-66*
initialization parameters *(continued)*
COMMIT_WRITE, *2-67*
COMMON_USER_PREFIX, *2-68*
COMPATIBLE, *2-69*
CONNECTION_BROKERS, *2-70*
CONTAINER_DATA, *2-72*
CONTAINERS_PARALLEL_DEGREE, *2-73*
CONTROL_FILE_RECORD_KEEP_TIME, *2-73*
CONTROL_FILES, *2-74*
CONTROL_MANAGEMENT_PACK_ACCESS, *2-75*
CORE_DUMP_DEST, *2-76*
CPU_COUNT, *2-76*
CPU_MIN_COUNT, *2-78*
CREATE_BITMAP_AREA_SIZE, *2-79*
CREATE_STORED_OUTLINES, *2-79*
CURSOR_BIND_CAPTURE_DESTINATION, *2-80*
CURSOR_INVALIDATION, *2-81*
CURSOR_SHARING, *2-82*
CURSOR_SPACE_FOR_TIME, *2-82*
DATA_GUARD_MAX_IO_TIME, *2-84*
DATA_GUARD_MAX_LONGIO_TIME, *2-84*
DATA_GUARD_SYNC_LATENCY, *2-85*
DATA_TRANSFER_CACHE_SIZE, *2-86*
DB_BIG_TABLE_CACHE_PERCENT_TARGET, *2-87*
DB_BLOCK_BUFFERS, *2-89*
DB_BLOCK_CHECKING, *2-90*
DB_BLOCK_CHECKSUM, *2-91*
DB_BLOCK_SIZE, *2-92*
DB_CACHE_ADVICE, *2-93*
DB_CACHE_SIZE, *2-94*
DB_CREATE_FILE_DEST, *2-95*
DB_CREATE_ONLINE_LOG_DEST_n, *2-96*
DB_DOMAIN, *2-97*
DB_FILE_MULTIBLOCK_READ_COUNT, *2-98*
DB_FILE_NAME_CONVERT, *2-99*
DB_FILES, *2-100*
DB_FLASH_CACHE_FILE, *2-101*
DB_FLASH_CACHE_SIZE, *2-101*
DB_FLASHBACK_LOG_DEST, *2-102*
DB_FLASHBACK_LOG_DEST_SIZE, *2-103*
DB_FLASHBACK_RETENTION_TARGET, *2-104*
DB_INDEX_COMPRESSION_INHERITANCE, *2-105*
DB_KEEP_CACHE_SIZE, *2-106*
DB_LOST_WRITE_PROTECT, *2-106*
DB_NAME, *2-108*
DB_nK_CACHE_SIZE, *2-86*
DB_PERFORMANCE_PROFILE, *2-108*
DB_RECOVERY_AUTO_REKEY, *2-109*
DB_RECOVERY_FILE_DEST, *2-110*
DB_RECOVERY_FILE_DEST_SIZE, *2-110*
DB_RECYCLE_CACHE_SIZE, *2-111*
DB_SECUREFILE, *2-112*
DB_ULTRA_SAFE, *2-113*
DB_UNIQUE_NAME, *2-114*

initialization parameters *(continued)*
DB_UNRECOVERABLE_SCN_TRACKING, *2-115*
DB_WRITER_PROCESSES, *2-115*
DBFIPS_140, *2-116*
DBNEST_ENABLE, *2-117*
DBNEST_PDB_FS_CONF, *2-118*
DBWR_IO_SLAVES, *2-118*
DDL_LOCK_TIMEOUT, *2-119*
DEFAULT_SHARING, *2-120*
DEFERRED_SEGMENT_CREATION, *2-120*
derived, *2-2*
DG_BROKER_CONFIG_FILEn, *2-121*
DG_BROKER_START, *2-121*
DIAGNOSTIC_DEST, *2-122*
DIAGNOSTICS_CONTROL, *2-123*
DISK_ASYNCH_IO, *2-124*
DISPATCHERS, *2-125*
display current settings, *2-28*
DISTRIBUTED_LOCK_TIMEOUT, *2-127*
DML_LOCKS, *2-128*
DNFS_BATCH_SIZE, *2-129*
DRCP_DEDICATED_OPT, *2-129*
DST_UPGRADE_INSERT_CONV, *2-130*
embedded initialization parameter files, *2-6*
ENABLE_AUTOMATIC_MAINTENANCE_PDB, *2-131*
ENABLE_DDL_LOGGING, *2-132*
ENABLE_DNFS_DISPATCHER, *2-134*
ENABLE_GOLDENGATE_REPLICATION, *2-134*
ENABLE_IMC_WITH_MIRA, *2-135*
ENABLE_PER_PDB_DRCP, *2-136*
ENABLE_PLUGGABLE_DATABASE, *2-137*
ENABLED_PDBS_ON_STANDBY, *2-137*
ENCRYPT_NEW_TABLESPACES, *2-139*
ERROR_MESSAGE_DETAILS, *2-140*
EVENT, *2-141*
EXTERNAL_KEYSTORE_CREDENTIAL_LOCATION, *2-141*
FAL_CLIENT, *2-142*
FAL_SERVER, *2-143*
FAST_START_MTTR_TARGET, *2-143*
FAST_START_PARALLEL_ROLLBACK, *2-144*
FILE_MAPPING, *2-145*
FILEIO_NETWORK_ADAPTERS, *2-145*
FILESYSTEMIO_OPTIONS, *2-146*
FIXED_DATE, *2-146*
FORWARD_LISTENER, *2-147*
functional category, *2-9*
GCS_SERVER_PROCESSES, *2-148*
GLOBAL_NAMES, *2-148*
GLOBAL_TXN_PROCESSES, *2-149*
GROUP_BY_POSITION_ENABLED, *2-150*
HASH_AREA_SIZE, *2-151*
HEARTBEAT_BATCH_SIZE, *2-152*
HEAT_MAP, *2-152*

initialization parameters *(continued)*
HI_SHARED_MEMORY_ADDRESS, *2-153*
HS_AUTOREGISTER, *2-153*
HYBRID_READ_ONLY, *2-154*
IDENTITY_PROVIDER_CONFIG, *2-155*
IDENTITY_PROVIDER_TYPE, *2-156*
IFILE, *2-6*, *2-157*
IGNORE_SESSION_SET_PARAM_ERRORS, *2-158*
INMEMORY_ADG_ENABLED, *2-159*
INMEMORY_AUTOMATIC_LEVEL, *2-160*
INMEMORY_CLAUSE_DEFAULT, *2-161*
INMEMORY_DEEP_VECTORIZATION, *2-166*
INMEMORY_EXPRESSIONS_USAGE, *2-167*
INMEMORY_FORCE, *2-168*
INMEMORY_MAX_POPULATE_SERVERS, *2-169*
INMEMORY_OPTIMIZED_ARITHMETIC, *2-170*
INMEMORY_QUERY, *2-171*
INMEMORY_SIZE, *2-172*
INMEMORY_TRICKLE_REPOPULATE_SERVERS_PERCENT, *2-173*
INMEMORY_VIRTUAL_COLUMNS, *2-174*
INSTANCE_ABORT_DELAY_TIME, *2-175*
INSTANCE_GROUPS, *2-176*
INSTANCE_MODE, *2-177*
INSTANCE_NAME, *2-177*
INSTANCE_NUMBER, *2-178*
INSTANCE_TYPE, *2-179*
IORM_LIMIT_POLICY, *2-179*
JAVA_JIT_ENABLED, *2-181*
JAVA_MAX_SESSIONSPACE_SIZE, *2-181*
JAVA_POOL_SIZE, *2-182*
JAVA_SOFT_SESSIONSPACE_LIMIT, *2-182*
JOB_QUEUE_PROCESSES, *2-183*
JSON_BEHAVIOR, *2-185*
JSON_EXPRESSION_CHECK, *2-186*
LARGE_POOL_SIZE, *2-187*
LDAP_DIRECTORY_ACCESS, *2-188*
LDAP_DIRECTORY_SYSAUTH, *2-190*
LICENSE_MAX_SESSIONS, *2-191*
LICENSE_MAX_USERS, *2-192*
LICENSE_SESSIONS_WARNING, *2-192*
LISTENER_NETWORKS, *2-193*
LOB_SIGNATURE_ENABLE, *2-194*
LOCAL_LISTENER, *2-195*
LOCK_NAME_SPACE, *2-195*
LOCK_SGA, *2-196*
LOG_ARCHIVE_CONFIG, *2-196*
LOG_ARCHIVE_DEST, *2-197*
LOG_ARCHIVE_DEST_n, *2-199*
LOG_ARCHIVE_DEST_STATE_n, *2-203*
LOG_ARCHIVE_DUPLEX_DEST, *2-205*
LOG_ARCHIVE_FORMAT, *2-205*
LOG_ARCHIVE_MAX_PROCESSES, *2-207*
LOG_ARCHIVE_MIN_SUCCEED_DEST, *2-207*
LOG_ARCHIVE_TRACE, *2-209*

initialization parameters *(continued)*
LOG_BUFFER, *2-211*
LOG_CHECKPOINT_INTERVAL, *2-212*
LOG_CHECKPOINT_TIMEOUT, *2-213*
LOG_CHECKPOINTS_TO_ALERT, *2-214*
LOG_FILE_NAME_CONVERT, *2-214*
LONG_MODULE_ACTION, *2-216*
MANDATORY_USER_PROFILE, *2-216*
MAX_AUTH_SERVERS, *2-217*
MAX_COLUMNS, *2-218*
MAX_DATAPUMP_JOBS_PER_PDB, *2-219*
MAX_DATAPUMP_PARALLEL_PER_JOB, *2-220*
MAX_DISPATCHERS, *2-220*
MAX_DUMP_FILE_SIZE, *2-221*
MAX_IDLE_BLOCKER_TIME, *2-222*
MAX_IDLE_TIME, *2-223*
MAX_IOPS, *2-223*
MAX_MBPS, *2-224*
MAX_PDBS, *2-225*
MAX_SAGA_DURATION, *2-226*
MAX_SHARED_SERVERS, *2-226*
MAX_STRING_SIZE, *2-227*
MEMOPTIMIZE_POOL_SIZE, *2-232*
MEMOPTIMIZE_WRITE_AREA_SIZE, *2-233*
MEMOPTIMIZE_WRITES, *2-233*
MEMORY_MAX_SIZE, *2-234*
MEMORY_MAX_TARGET, *2-235*
MEMORY_SIZE, *2-235*
MEMORY_TARGET, *2-236*
MIN_AUTH_SERVERS, *2-237*
MLE_PROG_LANGUAGES, *2-238*
modifiable, *2-19*
MULTISHARD_QUERY_DATA_CONSISTENCY, *2-239*
NLS_CALENDAR, *2-240*
NLS_COMP, *2-241*
NLS_CURRENCY, *2-242*
NLS_DATE_FORMAT, *2-243*
NLS_DATE_LANGUAGE, *2-244*
NLS_DUAL_CURRENCY, *2-245*
NLS_ISO_CURRENCY, *2-246*
NLS_LANGUAGE, *2-246*
NLS_LENGTH_SEMANTICS, *2-248*
NLS_NCHAR_CONV_EXCP, *2-249*
NLS_NUMERIC_CHARACTERS, *2-249*
NLS_SORT, *2-250*
NLS_TERRITORY, *2-251*
NLS_TIMESTAMP_FORMAT, *2-252*
NLS_TIMESTAMP_TZ_FORMAT, *2-253*
OBJECT_CACHE_MAX_SIZE_PERCENT, *2-255*
OBJECT_CACHE_OPTIMAL_SIZE, *2-255*
OFS_THREADS, *2-256*
OLAP_PAGE_POOL_SIZE, *2-257*
ONE_STEP_PLUGIN_FOR_PDB_WITH_TDE, *2-257*

initialization parameters *(continued)*
OPEN_CURSORS, *2-258*
OPEN_LINKS, *2-259*
OPEN_LINKS_PER_INSTANCE, *2-260*
operating system-dependent values, *2-2*
OPTIMIZER_ADAPTIVE_PLANS, *2-260*
OPTIMIZER_ADAPTIVE_REPORTING_ONLY, *2-261*
OPTIMIZER_ADAPTIVE_STATISTICS, *2-262*
OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES, *2-263*
OPTIMIZER_CAPTURE_SQL_QUARANTINE, *2-263*
OPTIMIZER_CROSS_SHARD_RESILIENCY, *2-264*
OPTIMIZER_DYNAMIC_SAMPLING, *2-264*
OPTIMIZER_FEATURES_ENABLE, *2-265*
OPTIMIZER_IGNORE_HINTS, *2-267*
OPTIMIZER_IGNORE_PARALLEL_HINTS, *2-267*
OPTIMIZER_INDEX_CACHING, *2-268*
OPTIMIZER_INDEX_COST_ADJ, *2-268*
OPTIMIZER_INMEMORY_AWARE, *2-269*
OPTIMIZER_MODE, *2-270*
OPTIMIZER_REAL_TIME_STATISTICS, *2-271*
OPTIMIZER_SESSION_TYPE, *2-271*
OPTIMIZER_USE_INVISIBLE_INDEXES, *2-272*
OPTIMIZER_USE_PENDING_STATISTICS, *2-272*
OPTIMIZER_USE_SQL_PLAN_BASELINES, *2-273*
OPTIMIZER_USE_SQL_QUARANTINE, *2-274*
OS_AUTHENT_PREFIX, *2-274*
OS_ROLES, *2-275*
OUTBOUND_DBLINK_PROTOCOLS, *2-276*
PARALLEL_ADAPTIVE_MULTI_USER, *2-277*
PARALLEL_DEGREE_LIMIT, *2-277*
PARALLEL_DEGREE_POLICY, *2-279*
PARALLEL_EXECUTION_MESSAGE_SIZE, *2-280*
PARALLEL_FORCE_LOCAL, *2-281*
PARALLEL_INSTANCE_GROUP, *2-281*
PARALLEL_MAX_SERVERS, *2-282*
PARALLEL_MIN_DEGREE, *2-283*
PARALLEL_MIN_PERCENT, *2-284*
PARALLEL_MIN_SERVERS, *2-285*
PARALLEL_MIN_TIME_THRESHOLD, *2-286*
PARALLEL_SERVERS_TARGET, *2-286*
PARALLEL_THREADS_PER_CPU, *2-288*
parameter files, *2-3*
PDB_FILE_NAME_CONVERT, *2-289*
PDB_LOCKDOWN, *2-290*
PDB_OS_CREDENTIAL, *2-292*
performance tuning, *2-2*
PERMIT_92_WRAP_FORMAT, *2-293*
PGA_AGGREGATE_LIMIT, *2-294*
PGA_AGGREGATE_TARGET, *2-295*
PKCS11_LIBRARY_LOCATION, *2-297*
PLSCOPE_SETTINGS, *2-298*
PLSQL_CCFLAGS, *2-300*

initialization parameters *(continued)*
PLSQL_CODE_TYPE, *2-300*
PLSQL_DEBUG, *2-301*
PLSQL_IMPLICIT_CONVERSION_BOOL, *2-302*
PLSQL_OPTIMIZE_LEVEL, *2-303*
PLSQL_V2_COMPATIBILITY, *2-304*
PLSQL_WARNINGS, *2-305*
PMEM_FILESTORE, *2-306*
PRE_PAGE_SGA, *2-307*
PRIORITY_TXNS_HIGH_WAIT_TARGET, *2-308*
PRIORITY_TXNS_MEDIUM_WAIT_TARGET, *2-309*
PRIORITY_TXNS_MODE, *2-310*
PRIVATE_TEMP_TABLE_PREFIX, *2-311*
PROCESSES, *2-312*
PROCESSOR_GROUP_NAME, *2-313*
QUERY_REWRITE_ENABLED, *2-313*
QUERY_REWRITE_INTEGRITY, *2-314*
RDBMS_SERVER_DN, *2-316*
READ_ONLY, *2-317*
READ_ONLY_OPEN_DELAYED, *2-317*
RECOVERY_PARALLELISM, *2-318*
RECYCLEBIN, *2-319*
REDO_TRANSPORT_USER, *2-319*
REMOTE_DEPENDENCIES_MODE, *2-320*
REMOTE_LISTENER, *2-320*
REMOTE_LOGIN_PASSWORDFILE, *2-321*
REMOTE_OS_ROLES, *2-322*
REMOTE_RECOVERY_FILE_DEST, *2-323*
REPLICATION_DEPENDENCY_TRACKING, *2-323*
RESOURCE_LIMIT, *2-324*
RESOURCE_MANAGE_GOLDENGATE, *2-325*
RESOURCE_MANAGER_CPU_ALLOCATION, *2-325*
RESOURCE_MANAGER_CPU_SCOPE, *2-326*
RESOURCE_MANAGER_PLAN, *2-327*
RESULT_CACHE_AUTO_BLOCKLIST, *2-329*
RESULT_CACHE_EXECUTION_THRESHOLD, *2-330*
RESULT_CACHE_INTEGRITY, *2-330*
RESULT_CACHE_MAX_RESULT, *2-331*
RESULT_CACHE_MAX_SIZE, *2-332*
RESULT_CACHE_MAX_TEMP_RESULT, *2-332*
RESULT_CACHE_MAX_TEMP_SIZE, *2-333*
RESULT_CACHE_MODE, *2-333*
RESULT_CACHE_REMOTE_EXPIRATION, *2-335*
RESUMABLE_TIMEOUT, *2-335*
ROLLBACK_SEGMENTS, *2-336*
SAGA_HIST_RETENTION, *2-337*
SEC_MAX_FAILED_LOGIN_ATTEMPTS, *2-337*
SEC_PROTOCOL_ERROR_FURTHER_ACTION, *2-338*
SEC_PROTOCOL_ERROR_TRACE_ACTION, *2-339*
SEC_RETURN_SERVER_RELEASE_BANNER, *2-339*
initialization parameters *(continued)*
SERIAL_REUSE, *2-340*
SERVICE_NAMES, *2-341*
SESSION_CACHED_CURSORS, *2-342*
SESSION_EXIT_ON_PACKAGE_STATE_ERROR, *2-343*
SESSION_MAX_OPEN_FILES, *2-344*
SESSIONS, *2-344*
SGA_MAX_SIZE, *2-345*
SGA_MIN_SIZE, *2-346*
SGA_TARGET, *2-347*
SHADOW_CORE_DUMP, *2-350*
SHARD_ENABLE_RAFT_FOLLOWER_READ, *2-351*
SHARD_RAFT_LOGFILE_SIZE, *2-351*
SHARED_MEMORY_ADDRESS, *2-352*
SHARED_POOL_RESERVED_SIZE, *2-352*
SHARED_POOL_SIZE, *2-353*
SHARED_SERVER_SESSIONS, *2-355*
SHARED_SERVERS, *2-355*
SHRD_DUPL_TABLE_REFRESH_RATE, *2-356*
SKIP_UNUSABLE_INDEXES, *2-357*
SMTP_OUT_SERVER, *2-358*
SORT_AREA_RETAINED_SIZE, *2-358*
SORT_AREA_SIZE, *2-359*
SPATIAL_VECTOR_ACCELERATION, *2-361*
specifying in initialization parameter files, *2-5*
SPFILE, *2-361*
SQL_ERROR_MITIGATION, *2-362*
SQL_HISTORY_ENABLED, *2-362*
SQL_TRACE, *2-363*
SQL_TRANSPILER, *2-364*
SQL92_SECURITY, *2-365*
SQLTUNE_CATEGORY, *2-365*
STANDBY_DB_PRESERVE_STATES, *2-366*
STANDBY_FILE_MANAGEMENT, *2-367*
STANDBY_PDB_SOURCE_FILE_DBLINK, *2-368*
STANDBY_PDB_SOURCE_FILE_DIRECTORY, *2-369*
STAR_TRANSFORMATION_ENABLED, *2-369*
STATISTICS_LEVEL, *2-370*
STREAMS_POOL_SIZE, *2-372*
SYSDATE_AT_DBTIMEZONE, *2-373*
TABLESPACE_ENCRYPTION, *2-373*
TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM, *2-375*
TAPE_ASYNCH_IO, *2-376*
TDE_CONFIGURATION, *2-377*
TDE_KEY_CACHE, *2-379*
TEMP_UNDO_ENABLED, *2-380*
THREAD, *2-381*
THREADED_EXECUTION, *2-382*
TIME_AT_DBTIMEZONE, *2-384*
TIMED_OS_STATISTICS, *2-385*
TIMED_STATISTICS, *2-386*

initialization parameters *(continued)*
TIMEZONE_VERSION_UPGRADE_ONLINE, *2-387*
TRACE_ENABLED, *2-387*
TRACEFILE_IDENTIFIER, *2-388*
TRANSACTION_RECOVERY, *2-389*
TRANSACTIONS, *2-390*
TRANSACTIONS_PER_ROLLBACK_SEGMENT, *2-390*
TRUE_CACHE, *2-391*
TXN_PRIORITY, *2-391*
UNDO_MANAGEMENT, *2-392*
UNDO_RETENTION, *2-393*
UNDO_TABLESPACE, *2-395*
UNIFIED_AUDIT_COMMON_SYSTEMLOG, *2-396*
UNIFIED_AUDIT_SYSTEMLOG, *2-397*
UNIFORM_LOG_TIMESTAMP_FORMAT, *2-398*
USE_DEDICATED_BROKER, *2-399*
USE_LARGE_PAGES, *2-400*
USER_DUMP_DEST, *2-401*
variable, *2-2*
WALLET_ROOT, *2-402*
WORKAREA_SIZE_POLICY, *2-405*
XML_DB_EVENTS, *2-406*
XML_PARAMS, *2-407*
INITJVM.SQL script, *B-6*
INMEMORY_ADG_ENABLED initialization parameter, *2-159*
INMEMORY_AUTOMATIC_LEVEL initialization parameter, *2-160*
INMEMORY_CLAUSE_DEFAULT initialization parameter, *2-161*
INMEMORY_DEEP_VECTORIZATION initialization parameter, *2-166*
INMEMORY_EXPRESSIONS_USAGE initialization parameter, *2-167*
INMEMORY_FORCE initialization parameter, *2-168*
INMEMORY_MAX_POPULATE_SERVERS initialization parameter, *2-169*
INMEMORY_OPTIMIZED_ARITHMETIC initialization parameter, *2-170*
INMEMORY_QUERY initialization parameter, *2-171*
INMEMORY_SIZE initialization parameter, *2-172*
INMEMORY_TRICKLE_REPOPULATE_SERVERS_PERCENT initialization parameter, *2-173*
INMEMORY_VIRTUAL_COLUMNS initialization parameter, *2-174*
inserts
locating free space, *2-178*
INST_ID column, *8-2*
INSTANCE clause
of ALTER TABLE
allocating extents, *2-178*
INSTANCE_ABORT_DELAY_TIME initialization parameter, *2-175*
INSTANCE_GROUPS initialization parameter, *2-176*
INSTANCE_MODE initialization parameter, *2-177*
INSTANCE_NAME initialization parameter, *2-177*
INSTANCE_NUMBER initialization parameter, *2-178*
INSTANCE_TYPE initialization parameter, *2-179*
instances
checkpoint, *2-212*
startup order, *2-178*
IORM_LIMIT_POLICY initialization parameter, *2-179*

J

Java initialization parameters
JAVA_MAX_SESSIONSPACE_SIZE, *2-181*
JAVA_POOL_SIZE, *2-182*
JAVA_SOFT_SESSIONSPACE_LIMIT, *2-182*
Java scripts, *B-6*
JAVA_JIT_ENABLED initialization parameter, *2-181*
JAVA_MAX_SESSIONSPACE_SIZE initialization parameter, *2-181*
JAVA_POOL_SIZE initialization parameter, *2-182*
JAVA_SOFT_SESSIONSPACE_LIMIT initialization parameter, *2-182*
JOB_QUEUE_PROCESSES initialization parameter, *2-183*
JSON_BEHAVIOR initialization parameter, *2-185*
JSON_EXPRESSION_CHECK initialization parameter, *2-186*

L

language
database default language, *2-246*
LARGE_POOL_SIZE initialization parameter, *2-187*
LDAP_DIRECTORY_ACCESS initialization parameter, *2-188*
LDAP_DIRECTORY_SYSAUTH initialization parameter, *2-190*
LICENSE_MAX_SESSIONS initialization parameter, *2-191*
LICENSE_MAX_USERS initialization parameter, *2-192*
LICENSE_SESSIONS_WARNING initialization parameter, *2-192*
licenses
maximum sessions, *2-191*
maximum users, *2-192*
warning for concurrent user sessions, *2-193*

limits on the database, *A-1*
linguistic sorts, *2-250*
LISTENER_NETWORKS initialization parameter, *2-193*
LOB_SIGNATURE_ENABLE initialization parameter, *2-194*
local currency, *2-241*, *2-242*
LOCAL_LISTENER initialization parameter, *2-195*
LOCK_NAME_SPACE initialization parameter, *2-195*
LOCK_SGA initialization parameter, *2-196*
locks
  names, *C-4*
LOG_ARCHIVE_CONFIG initialization parameter, *2-196*
LOG_ARCHIVE_DEST initialization parameter, *2-197*
LOG_ARCHIVE_DEST_n initialization parameter, *2-199*
LOG_ARCHIVE_DEST_STATE_n initialization parameter, *2-203*
LOG_ARCHIVE_DUPLEX_DEST initialization parameter, *2-205*
LOG_ARCHIVE_FORMAT initialization parameter, *2-205*
LOG_ARCHIVE_MAX_PROCESSES initialization parameter, *2-207*
LOG_ARCHIVE_MIN_SUCCEED_DEST initialization parameter, *2-207*
LOG_ARCHIVE_TRACE initialization parameter, *2-209*
LOG_BUFFER initialization parameter, *2-211*
LOG_CHECKPOINT_INTERVAL initialization parameter, *2-212*
LOG_CHECKPOINT_TIMEOUT initialization parameter, *2-213*
LOG_CHECKPOINTS_TO_ALERT initialization parameter, *2-214*
LOG_FILE_NAME_CONVERT initialization parameter, *2-214*
LOGSTDBY_UNSUPPORTED_TABLES
  synonym for DBA_LOGSTDBY_UNSUPPORTED_TABLE view, *7-141*
LONG_MODULE_ACTION initialization parameter, *2-216*
lowercase significance, *2-5*

M

MANDATORY_USER_PROFILE initialization parameter, *2-216*
MAP_OBJECT table, *7-142*
MAX_AUTH_SERVERS initialization parameter, *2-217*
MAX_COLUMNS initialization parameter, *2-218*
MAX_DATAPUMP_JOBS_PER_PDB initialization parameter, *2-219*
MAX_DATAPUMP_PARALLEL_PER_JOB initialization parameter, *2-220*
MAX_DISPATCHERS initialization parameter, *2-220*
MAX_DUMP_FILE_SIZE initialization parameter, *2-221*
MAX_IDLE_BLOCKER_TIME initialization parameter, *2-222*
MAX_IDLE_TIME initialization parameter, *2-223*
MAX_IOPS initialization parameter, *2-223*
MAX_MBPS initialization parameter, *2-224*
MAX_PDBS initialization parameter, *2-225*
MAX_SAGA_DURATION initialization parameter, *2-226*
MAX_SHARED_SERVERS initialization parameter, *2-226*
MAX_STRING_SIZE initialization parameter, *2-227*
MEMOPTIMIZE_POOL_SIZE initialization parameter, *2-232*
MEMOPTIMIZE_WRITE_AREA_SIZE initialization parameter, *2-233*
MEMOPTIMIZE_WRITES initialization parameter, *2-233*
memory
  amount used for sorting, *2-358*
  virtual, *2-2*
MEMORY_MAX_SIZE initialization parameter, *2-234*
MEMORY_MAX_TARGET initialization parameter, *2-235*
MEMORY_SIZE initialization parameter, *2-235*
MEMORY_TARGET initialization parameter, *2-236*
MIN_AUTH_SERVERS initialization parameter, *2-237*
MLE_PROG_LANGUAGES initialization parameter, *2-238*
monitor
  performance, *2-212*
multiple-process systems
  number of processes, *2-312*
MULTISHARD_QUERY_DATA_CONSISTENCY initialization parameter, *2-239*
multitenant container databases
  See CDBs.

N

NLS_CALENDAR initialization parameter, *2-240*

NLS_COMP initialization parameter, 2-241
NLS_CURRENCY initialization parameter, 2-242
  defined by NLS_TERRITORY, 2-251
NLS_DATABASE_PARAMETERS view, 7-142
NLS_DATE_FORMAT initialization parameter, 2-243
  defined by NLS_NUMERIC_CHARACTERS, 2-249
  defined by NLS_TERRITORY, 2-251
NLS_DATE_LANGUAGE initialization parameter, 2-244
NLS_DUAL_CURRENCY initialization parameter, 2-245
NLS_INSTANCE_PARAMETERS view, 7-142
NLS_ISO_CURRENCY initialization parameter, 2-246
  defined by NLS_TERRITORY, 2-251
NLS_LANGUAGE initialization parameter, 2-246
NLS_LENGTH_SEMANTICS initialization parameter, 2-248
NLS_NCHAR_CONV_EXCP initialization parameter, 2-249
NLS_NUMERIC_CHARACTERS initialization parameter, 2-249
NLS_SESSION_PARAMETERS view, 7-143
NLS_SORT initialization parameter, 2-250
NLS_TERRITORY initialization parameter, 2-251
NLS_TIME_FORMAT, 9-88
NLS_TIME_TZ_FORMAT, 9-88
NLS_TIMESTAMP_FORMAT initialization parameter, 2-252
NLS_TIMESTAMP_TZ_FORMAT initialization parameter, 2-253
NONCDB_COMPATIBLE initialization parameter, 2-254
numeric group separators, 2-249

O

OBJ synonym for USER_OBJECTS view, 7-143
OBJECT_CACHE_MAX_SIZE_PERCENT initialization parameter, 2-255
OBJECT_CACHE_OPTIMAL_SIZE initialization parameter, 2-255
objects
  data dictionary, 3-1
OFS_THREADS initialization parameter, 2-256
OLAP_PAGE_POOL_SIZE initialization parameter, 2-257
ONE_STEP_PLUGIN_FOR_PDB_WITH_TDE initialization parameter, 2-257
online redo log
  archiving mode, 2-198
  block, 2-212
  file size, 2-212
online redo log *(continued)*
  setting checkpoint interval, 2-212
OPEN_CURSORS initialization parameter, 2-258
OPEN_LINKS initialization parameter, 2-259
OPEN_LINKS_PER_INSTANCE initialization parameter, 2-260
operating system
  authenticating users and passwords, 2-274
  dependent parameters, 2-2
  roles for remote clients, 2-322
optimization
  trading cursor space for time, 2-83
OPTIMIZER_ADAPTIVE_PLANS initialization parameter, 2-260
OPTIMIZER_ADAPTIVE_REPORTING_ONLY initialization parameter, 2-261
OPTIMIZER_ADAPTIVE_STATISTICS initialization parameter, 2-262
OPTIMIZER_CAPTURE_SQL_PLAN_BASELINES initialization parameter, 2-263
OPTIMIZER_CAPTURE_SQL_QUARANTINE initialization parameter, 2-263
OPTIMIZER_CROSS_SHARD_RESILIENCY initialization parameter, 2-264
OPTIMIZER_DYNAMIC_SAMPLING initialization parameter, 2-264
OPTIMIZER_FEATURES_ENABLE initialization parameter, 2-265
OPTIMIZER_IGNORE_HINTS initialization parameter, 2-267
OPTIMIZER_IGNORE_PARALLEL_HINTS initialization parameter, 2-267
OPTIMIZER_INDEX_CACHING initialization parameter, 2-268
OPTIMIZER_INDEX_COST_ADJ initialization parameter, 2-268
OPTIMIZER_INMEMORY_AWARE initialization parameter, 2-269
OPTIMIZER_MODE initialization parameter, 2-270
OPTIMIZER_REAL_TIME_STATISTICS initialization parameter, 2-271
OPTIMIZER_SESSION_TYPE initialization parameter, 2-271
OPTIMIZER_USE_INVISIBLE_INDEXES initialization parameter, 2-272
OPTIMIZER_USE_PENDING_STATISTICS initialization parameter, 2-272
OPTIMIZER_USE_SQL_PLAN_BASELINES initialization parameter, 2-273
OPTIMIZER_USE_SQL_QUARANTINE initialization parameter, 2-274
Oracle Database Real Application Security views, 3-4
Oracle Database Vault views, 3-5

Oracle Exadata Database Machine views, 8-3
Oracle Label Security views, 3-5
Oracle Workspace Manager views, 3-5
ORPHAN_KEY_TABLE table
See DBA_ORPHAN_KEY_TABLE view
OS_AUTHENT_PREFIX initialization parameter, 2-274
OS_ROLES initialization parameter, 2-275
OUTBOUND_DBLINK_PROTOCOLS initialization parameter, 2-276

P

parallel query
maximum number of instances, 2-280
maximum number of servers, 2-282
minimum number of queries, 2-285
PARALLEL_ADAPTIVE_MULTI_USER initialization parameter, 2-277
PARALLEL_DEGREE_LIMIT initialization parameter, 2-277
PARALLEL_DEGREE_POLICY initialization parameter, 2-279
PARALLEL_EXECUTION_MESSAGE_SIZE initialization parameter, 2-280
PARALLEL_FORCE_LOCAL initialization parameter, 2-281
PARALLEL_INSTANCE_GROUP initialization parameter, 2-281
PARALLEL_MAX_SERVERS initialization parameter, 2-282
PARALLEL_MIN_DEGREE initialization parameter, 2-283
PARALLEL_MIN_PERCENT initialization parameter, 2-284
PARALLEL_MIN_SERVERS initialization parameter, 2-285
PARALLEL_MIN_TIME_THRESHOLD initialization parameter, 2-286
PARALLEL_SERVERS_TARGET initialization parameter, 2-286
PARALLEL_THREADS_PER_CPU initialization parameter, 2-288
passwords
authenticating, 2-274
REMOTE_LOGIN_PASSWORDFILE initialization parameter, 2-321
PATH_VIEW view, 7-143
PDB_ALERTS view, 7-144
PDB_FILE_NAME_CONVERT initialization parameter, 2-289
PDB_LOCKDOWN initialization parameter, 2-290
PDB_OS_CREDENTIAL initialization parameter, 2-292
PDB_PLUG_IN_VIOLATIONS view, 7-144
PDBs, 2-45
performance, 2-2
shared pool, 2-353
PERMIT_92_WRAP_FORMAT initialization parameter, 2-293
PGA_AGGREGATE_LIMIT initialization parameter, 2-294
PGA_AGGREGATE_TARGET initialization parameter, 2-295
PKCS11_LIBRARY_LOCATION initialization parameter, 2-297
PLAN_TABLE table, 7-145
PLSCOPE_SETTINGS initialization parameter, 2-298
PLSQL_CCFLAGS initialization parameter, 2-300
PLSQL_CODE_TYPE initialization parameter, 2-300
PLSQL_DEBUG initialization parameter, 2-301
PLSQL_IMPLICIT_CONVERSION_BOOL initialization parameter, 2-302
PLSQL_OPTIMIZE_LEVEL initialization parameter, 2-303
PLSQL_V2_COMPATIBILITY initialization parameter, 2-304
PLSQL_WARNINGS initialization parameter, 2-305
pluggable databases
See PDBs.
PLUGGABLE_SET_CHECK view, 7-149
PMEM_FILESTORE initialization parameter, 2-306
PRE_PAGE_SGA initialization parameter, 2-307
PRIORITY_TXNS_HIGH_WAIT_TARGET initialization parameter, 2-308
PRIORITY_TXNS_MEDIUM_WAIT_TARGET initialization parameter, 2-309
PRIORITY_TXNS_MODE initialization parameter, 2-310
PRIVATE_TEMP_TABLE_PREFIX initialization parameter, 2-311
privileges
remote login, 2-321
RESTRICTED_SESSION privilege, 2-191, 2-193
table-level select privileges, 2-365
procedures
shared pool, 2-353
processes
dispatcher process maximum number, 2-220
maximum shared server processes, 2-226
number of server processes, 2-181, 2-183, 2-355
recovery, 2-318
trace files, 2-401
user processes, 2-312

PROCESSES initialization parameter, *2-312*
PROCESSOR_GROUP_NAME initialization parameter, *2-313*
PRODUCT_COMPONENT_VERSION view, *7-149*
profiles
  resource limits, *2-324*, *2-329*
PROXY_USERS view, *7-150*
PSTUBTBL table, *7-150*
PUBLIC clause
  of ALTER DATABASE
    thread of redo, *2-381*
PUBLIC_DEPENDENCY view, *7-151*
PUBLICSYN view, *7-151*

Q

queries
  hints, *2-270*
QUERY_REWRITE_ENABLED initialization parameter, *2-313*
QUERY_REWRITE_INTEGRITY initialization parameter, *2-314*
QUEUE_PRIVILEGES view, *7-151*

R

RC_ARCHIVED_LOG view, *3-6*
RC_BACKUP_ARCHIVELOG_DETAILS view, *3-6*
RC_BACKUP_ARCHIVELOG_SUMMARY view, *3-6*
RC_BACKUP_CONTROLFILE view, *3-6*
RC_BACKUP_CONTROLFILE_DETAILS view, *3-6*
RC_BACKUP_CONTROLFILE_SUMMARY view, *3-6*
RC_BACKUP_COPY_DETAILS view, *3-6*
RC_BACKUP_COPY_SUMMARY view, *3-6*
RC_BACKUP_CORRUPTION view, *3-6*
RC_BACKUP_DATAFILE view, *3-6*
RC_BACKUP_DATAFILE_DETAILS view, *3-6*
RC_BACKUP_DATAFILE_SUMMARY view, *3-6*
RC_BACKUP_FILES view, *3-6*
RC_BACKUP_PIECE view, *3-6*
RC_BACKUP_PIECE_DETAILS view, *3-6*
RC_BACKUP_REDOLOG view, *3-6*
RC_BACKUP_SET view, *3-6*
RC_BACKUP_SET_DETAILS view, *3-6*
RC_BACKUP_SET_SUMMARY view, *3-7*
RC_BACKUP_SPFILE view, *3-7*
RC_BACKUP_SPFILE_DETAILS view, *3-7*
RC_BACKUP_SPFILE_SUMMARY view, *3-7*
RC_CHECKPOINT view, *3-7*
RC_CONTROLFILE_COPY view, *3-7*
RC_COPY_CORRUPTION view, *3-7*
RC_DATABASE view, *3-7*
RC_DATABASE_BLOCK_CORRUPTION view, *3-7*
RC_DATABASE_INCARNATION view, *3-7*
RC_DATAFILE view, *3-7*
RC_DATAFILE_COPY view, *3-7*
RC_LOG_HISTORY view, *3-7*
RC_OFFLINE_RANGE view, *3-7*
RC_PROXY_ARCHIVEDLOG view, *3-7*
RC_PROXY_ARCHIVELOG_DETAILS view, *3-7*
RC_PROXY_ARCHIVELOG_SUMMARY view, *3-7*
RC_PROXY_CONTROLFILE view, *3-7*
RC_PROXY_COPY_DETAILS view, *3-7*
RC_PROXY_COPY_SUMMARY view, *3-7*
RC_PROXY_DATAFILE view, *3-7*
RC_REDO_LOG view, *3-7*
RC_REDO_THREAD view, *3-7*
RC_RESTORE_POINT view, *3-7*
RC_RESYNC view, *3-7*
RC_RMAN_BACKUP_JOB_DETAILS view, *3-7*
RC_RMAN_BACKUP_SUBJOB_DETAILS view, *3-7*
RC_RMAN_BACKUP_TYPE view, *3-7*
RC_RMAN_CONFIGURATION view, *3-7*
RC_RMAN_OUTPUT view, *3-7*
RC_RMAN_STATUS view, *3-7*
RC_SITE view, *3-7*
RC_STORED_SCRIPT view, *3-7*
RC_STORED_SCRIPT_LINE view, *3-7*
RC_TABLESPACE view, *3-7*
RC_TEMPFILE view, *3-7*
RC_UNUSABLE_BACKUPFILE_DETAILS view, *3-7*
RDBMS_SERVER_DN initialization parameter, *2-316*
READ_ONLY initialization parameter, *2-317*
READ_ONLY_OPEN_DELAYED initialization parameter, *2-317*
Real Application Clusters
  dynamic performance views, *8-2*
  initialization parameters
    CIRCUITS, *2-59*
    CLUSTER_DATABASE, *2-63*
    CLUSTER_INTERCONNECTS, *2-64*
    DISPATCHERS, *2-125*
    FAST_START_PARALLEL_ROLLBACK, *2-144*
    PARALLEL_ADAPTIVE_MULTI_USER, *2-277*
    PARALLEL_EXECUTION_MESSAGE_SIZE, *2-280*
    PARALLEL_INSTANCE_GROUP, *2-281*
    PARALLEL_MAX_SERVERS, *2-282*

Real Application Clusters *(continued)*
initialization parameters *(continued)*
PARALLEL_MIN_PERCENT, *2-284*
PARALLEL_MIN_SERVERS, *2-285*
PARALLEL_THREADS_PER_CPU, *2-288*
recovery
number of required processes, *2-318*
Recovery Catalog views, *3-6*
RECOVERY_PARALLELISM initialization parameter, *2-318*
RECYCLEBIN initialization parameter, *2-319*
RECYCLEBIN synonym for USER_RECYCLEBIN view, *7-152*
REDACTION_COLUMNS view, *7-152*
REDACTION_EXPRESSIONS view, *7-153*
REDACTION_POLICIES view, *7-153*
REDACTION_VALUES_FOR_TYPE_FULL view, *7-154*
redo logs
buffer size, *2-212*
redo thread, *2-381*
REDO_TRANSPORT_USER initialization parameter, *2-319*
remote logins, *2-321*
REMOTE_DEPENDENCIES_MODE initialization parameter, *2-320*
REMOTE_LISTENER initialization parameter, *2-320*
REMOTE_LOGIN_PASSWORDFILE initialization parameter, *2-321*
REMOTE_OS_ROLES initialization parameter, *2-322*
REMOTE_RECOVERY_FILE_DEST initialization parameter, *2-323*
REPAIR_TABLE table
See DBA_REPAIR_TABLE view
REPLICATION_DEPENDENCY_TRACKING initialization parameter, *2-323*
REPORT_COMPONENTS view, *7-155*
REPORT_FILES view, *7-155*
REPORT_FORMATS view, *7-155*
resource limits for profiles, *2-324*, *2-329*
RESOURCE_COST view, *7-156*
RESOURCE_LIMIT initialization parameter, *2-324*
RESOURCE_MANAGE_GOLDENGATE initialization parameter, *2-325*
RESOURCE_MANAGER_CPU_ALLOCATION initialization parameter, *2-325*
RESOURCE_MANAGER_CPU_SCOPE initialization parameter, *2-326*
RESOURCE_MANAGER_PLAN initialization parameter, *2-327*
RESOURCE_MAP table, *7-156*
RESOURCE_VIEW view, *7-157*
RESULT_CACHE_AUTO_BLOCKLIST initialization parameter, *2-329*
RESULT_CACHE_EXECUTION_THRESHOLD initialization parameter, *2-330*
RESULT_CACHE_INTEGRITY initialization parameter, *2-330*
RESULT_CACHE_MAX_RESULT initialization parameter, *2-331*
RESULT_CACHE_MAX_SIZE initialization parameter, *2-332*
RESULT_CACHE_MAX_TEMP_SIZE initialization parameter, *2-333*
RESULT_CACHE_MODE initialization parameter, *2-333*
RESULT_CACHE_REMOTE_EXPIRATION initialization parameter, *2-335*
RESUMABLE_TIMEOUT initialization parameter, *2-335*
RMJVM.SQL script, *B-6*
ROLE_ROLE_PRIVS view, *7-157*
ROLE_SCHEMA_PRIVS view, *7-158*
ROLE_SYS_PRIVS view, *7-158*
ROLE_SYS_PRIVS_ALL view, *7-159*
ROLE_TAB_PRIVS view, *7-159*
roles, *2-275*
remote clients, *2-322*
ROLLBACK_SEGMENTS initialization parameter, *2-336*

S

SAGA_HIST_RETENTION initialization parameter, *2-337*
SCHEDULER_BATCH_ERRORS view, *7-160*
SCHEMA_EXPORT_OBJECTS view, *7-160*
scripts
CATALOG.SQL, *B-2*
CATBLOCK.SQL, *B-3*
CATCLUST.SQL, *B-2*
CATHS.SQL, *B-3*
CATIO.SQL, *B-3*
CATJAVA.SQL, *B-6*
CATNOCLUST.SQL, *B-5*
CATNOJAV.SQL, *B-6*
CATNOPRT.SQL, *B-6*
CATNOSVM.SQL, *B-6*
CATNSNMP.SQL, *B-6*
CATPCAT.SQL, *B-2*
CATPROC.SQL, *B-2*
CATQUEUE.SQL, *B-3*
CATREP.SQL, *B-3*
CATWRR.SQL, *B-3*
CATWRRWITB.SQL, *B-3*
data dictionary, *B-2*
DBMSIOTC.SQL, *B-3*

scripts *(continued)*
DBMSPOOL.SQL, *B-3*
INITJVM.SQL, *B-6*
Java, *B-6*
RMJVM.SQL, *B-6*
SQL scripts, *B-1*
upgrading, *B-6*
USERLOCK.SQL, *B-3*
UTLBSTAT.SQL, *B-3*
UTLCHN1.SQL, *B-3*
UTLCONST.SQL, *B-3*
UTLDTREE.SQL, *B-4*
UTLESTAT.SQL, *B-3*
UTLEXPT1.SQL, *B-4*
UTLFIXDIRS.SQL, *B-4*
UTLIP.SQL, *B-4*
UTLIRP.SQL, *B-4*
UTLLOCKT.SQL, *B-4*
UTLPWDMG.SQL, *B-5*
UTLRP.SQL, *B-5*
UTLSAMPL.SQL, *B-5*
UTLSCLN.SQL, *B-5*
UTLTKPRF.SQL, *B-5*
UTLVALID.SQL, *B-5*
UTLXPLAN.SQL, *B-5*
SEC_MAX_FAILED_LOGIN_ATTEMPTS initialization parameter, *2-337*
SEC_PROTOCOL_ERROR_FURTHER_ACTION initialization parameter, *2-338*
SEC_PROTOCOL_ERROR_TRACE_ACTION initialization parameter, *2-339*
SEC_RETURN_SERVER_RELEASE_BANNER initialization parameter, *2-339*
SEQ synonym for USER_SEQUENCES view, *7-161*
SERIAL_REUSE initialization parameter, *2-340*
server parameter file
overview, *2-3*
server processes
number, *2-181*, *2-183*, *2-355*
SERVICE_NAMES initialization parameter, *2-341*
SESSION_CACHED_CURSORS initialization parameter, *2-342*
SESSION_CONTEXT view, *7-161*
SESSION_EXIT_ON_PACKAGE_STATE_ERROR initialization parameter, *2-343*
SESSION_MAX_OPEN_FILES initialization parameter, *2-344*
SESSION_PRIVS view, *7-161*
SESSION_PRIVS_ALL view, *7-162*
SESSION_ROLES view, *7-162*
SESSION_SCHEMA_PRIVS view, *7-162*
SESSIONS initialization parameter, *2-344*
SGA_MAX_SIZE initialization parameter, *2-345*
SGA_MIN_SIZE initialization parameter, *2-346*
SGA_TARGET initialization parameter, *2-347*
SHADOW_CORE_DUMP initialization parameter, *2-350*
SHARD_ENABLE_RAFT_FOLLOWER_READ initialization parameter, *2-351*
SHARD_RAFT_LOGFILE_SIZE initialization parameter, *2-351*
SHARD_RAFT_PARAMETERS view, *7-163*
shared server
SESSIONS initialization parameter, *2-344*
shared server processes
maximum number, *2-226*
SHARED_MEMORY_ADDRESS initialization parameter, *2-352*
SHARED_POOL_RESERVED_SIZE initialization parameter, *2-352*
SHARED_POOL_SIZE initialization parameter, *2-353*
SHARED_SERVER_SESSIONS initialization parameter, *2-355*
SHARED_SERVERS initialization parameter, *2-355*
SHOW PARAMETERS statement, *2-28*
SHRD_DUPL_TABLE_REFRESH_RATE initialization parameter, *2-356*
SKIP_UNUSABLE_INDEXES initialization parameter, *2-357*
SMTP_OUT_SERVER initialization parameter, *2-358*
SORT_AREA_RETAINED_SIZE initialization parameter, *2-358*
SORT_AREA_SIZE initialization parameter, *2-359*
sorting
maximum memory, *2-358*
ORDER BY queries, *2-250*
SOURCE_SIZE view, *7-163*
SPATIAL_VECTOR_ACCELERATION initialization parameter, *2-361*
SPFILE initialization parameter, *2-361*
SQL scripts
creating the data dictionary, *B-1*
optional, *B-2*
required, *B-1*
SQL_ERROR_MITIGATION initialization parameter, *2-362*
SQL_HISTORY_ENABLED initialization parameter, *2-362*
SQL_TRACE initialization parameter, *2-363*
SQL_TRANSPILER initialization parameter, *2-364*
SQL92_SECURITY initialization parameter, *2-365*
SQLTUNE_CATEGORY initialization parameter, *2-365*

STANDBY_DB_PRESERVE_STATES
initialization parameter, 2-366
STANDBY_FILE_MANAGEMENT initialization parameter, 2-367
STANDBY_PDB_SOURCE_FILE_DBLINK
initialization parameter, 2-368
STANDBY_PDB_SOURCE_FILE_DIRECTORY
initialization parameter, 2-369
STAR_TRANSFORMATION_ENABLED
initialization parameter, 2-369
starting up
instance number, 2-178
startup order, 2-178
statistics
application wait time, E-2
background checkpoints completed, E-2
background checkpoints started, E-2
background timeouts, E-2
branch node splits, E-2
buffer is not pinned count, E-2
buffer is pinned count, E-2
bytes received via SQL*Net from client, E-2
bytes received via SQL*Net from dblink, E-2
bytes sent via SQL*Net to client, E-2
bytes sent via SQL*Net to dblink, E-2
Cached Commit SCN referenced, E-2
calls to get snapshot scn
kcmgss, E-2
calls to kcmgas, E-3
calls to kcmgcs, E-3
calls to kcmgrs, E-3
cell flash cache read hits, E-3
cell flash cache read hits for smart IO, E-3
cell flash cache read hits for temp IO, E-3
cell IO uncompressed bytes, E-3
cell num bytes in passthru due to quarantine, E-3
cell num bytes in passthru during predicate offload, E-3
cell overwrites in flash cache, E-3
cell partial writes in flash cache, E-3
cell physical IO bytes added to storage index, E-3
cell physical IO bytes eligible for predicate offload, E-3
cell physical IO bytes eligible for smart IOs, E-3
cell physical IO bytes processed for IM capacity, E-3
cell physical IO bytes processed for IM query, E-3
cell physical IO bytes processed for no memcompress, E-3
cell physical IO bytes saved by columnar cache, E-4
statistics *(continued)*
cell physical IO bytes saved by storage index, E-4
cell physical IO bytes saved during optimized file creation, E-4
cell physical IO bytes saved during optimized RMAN file restore, E-4
cell physical IO bytes sent directly to DB node to balance CPU, E-4
cell physical IO interconnect bytes, E-4
cell physical IO interconnect bytes returned by smart scan, E-4
cell pmem cache read hits, E-4
cell pmem cache writes, E-4
cell pmem log writes, E-4
cell ram cache read hits, E-4
cell RDMA reads, E-4
cell RDMA writes, E-4
cell writes to flash cache, E-4
cell writes to flash cache for temp IO, E-4
change write time, E-4
cleanouts and rollbacks - consistent read gets, E-4
cleanouts only - consistent read gets, E-4
cluster key scan block gets, E-4
cluster key scans, E-5
cluster wait time, E-5
cold recycle reads, E-5
commit cleanout failures
block lost, E-5
buffer being written, E-5
callback failure, E-5
cannot pin, E-5
hot backup in progress, E-5
pmem only, E-5
write disabled, E-5
commit cleanouts, E-5
commit cleanouts successfully completed, E-5
commit nowait performed, E-5
commit nowait requested, E-5
Commit SCN cached, E-5
commit wait performed, E-5
commit wait requested, E-6
commit wait/nowait requested, E-5
concurrency wait time, E-6
consistent changes, E-6
consistent gets, E-6
consistent gets direct, E-6
consistent gets from cache, E-6
consistent gets from pmem, E-6
consistent gets pmem direct, E-6
consistent gets pmem examination, E-6
consistent gets pmem examination (fastpath), E-6

statistics *(continued)*
consistent gets pmem pin, *E-6*
consistent gets pmem pin (fastpath), *E-6*
CPU used by this session, *E-7*
CPU used when call started, *E-7*
CR blocks created, *E-7*
cumulative begin requests, *E-7*
cumulative DB time in requests, *E-7*
cumulative DB time protected in requests, *E-7*
cumulative end requests, *E-7*
cumulative time in requests, *E-7*
cumulative user calls in requests, *E-7*
cumulative user calls protected by Application Continuity, *E-7*
current blocks converted for CR, *E-7*
cursor authentications, *E-7*
data blocks consistent reads - undo records applied, *E-8*
data warehousing cooling action, *E-8*
data warehousing evicted objects, *E-8*
data warehousing evicted objects - cooling, *E-8*
data warehousing evicted objects - replace, *E-8*
data warehousing scanned blocks, *E-8*
data warehousing scanned blocks - disk, *E-8*
data warehousing scanned blocks - memory, *E-8*
data warehousing scanned blocks - offload, *E-8*
data warehousing scanned objects, *E-8*
db block changes, *E-8*
db block gets, *E-8*
db block gets direct, *E-8*
db block gets from cache, *E-8*
db block gets from pmem, *E-8*
db block gets from pmem (fastpath), *E-8*
DBWR checkpoint buffers written, *E-8*
DBWR checkpoints, *2-212*, *E-9*
DBWR lru scans, *E-9*
DBWR revisited being-written buffer, *E-9*
DBWR transaction table writes, *E-9*
DBWR undo block writes, *E-9*
DDL statements parallelized, *E-9*
deferred (CURRENT) block cleanout applications, *E-9*
DFO trees parallelized, *E-9*
dirty buffers inspected, *E-9*
DML statements parallelized, *E-9*
DML statements retried, *E-9*
enqueue conversions, *E-9*
enqueue deadlocks, *E-9*
enqueue releases, *E-10*
enqueue requests, *E-10*

statistics *(continued)*
enqueue timeouts, *E-10*
enqueue waits, *E-10*
exchange deadlocks, *E-10*
execute count, *E-10*
fdba woken up, *E-10*
file io wait time, *E-10*
flash cache eviction: aged out, *E-10*
flash cache eviction: buffer pinned, *E-10*
flash cache eviction: nvalidated, *E-10*
flash cache insert skip: corrupt, *E-10*
flash cache insert skip: DBWR overloaded, *E-10*
flash cache insert skip: exists, *E-10*
flash cache insert skip: modification, *E-10*
flash cache insert skip: not current, *E-10*
flash cache insert skip: not useful, *E-10*
flash cache inserts, *E-11*
flashback log write bytes, *E-11*
flashback log writes, *E-11*
foreground propagated tracked transactions, *E-11*
free buffer inspected, *E-11*
free buffer inspected for pmem, *E-11*
free buffer requested, *E-11*
free buffer requested for pmem, *E-11*
gc read wait failure, *E-11*
gc read wait timeouts, *E-11*
gc read waits, *E-11*
global enqueue CPU used by this session, *E-11*
global enqueue get time, *E-11*
global enqueue gets async, *E-11*
global enqueue gets sync, *E-11*
global enqueue releases, *E-11*
HCC analyze table CUs, *E-12*
HCC analyzer calls, *E-12*
HCC block compressions attempted, *E-12*
HCC block compressions completed, *E-12*
HCC DML conventional, *E-12*
HCC DML CUs, *E-12*
HCC fetch by rowid CUs, *E-12*
HCC load conventional bytes compressed, *E-12*
HCC load conventional bytes uncompressed, *E-12*
HCC load conventional CUs, *E-12*
HCC load conventional CUs archive high, *E-12*
HCC load conventional CUs archive low, *E-12*
HCC load conventional CUs query high, *E-12*
HCC load conventional CUs query low, *E-12*
HCC load conventional rows, *E-12*

statistics *(continued)*
HCC load conventional rows not compressed, *E-12*
HCC load direct bytes compressed, *E-12*
HCC load direct bytes uncompressed, *E-13*
HCC load direct CUs, *E-13*
HCC load direct CUs archive high, *E-13*
HCC load direct CUs archive low, *E-13*
HCC load direct CUs query high, *E-13*
HCC load direct CUs query low, *E-13*
HCC load direct rows, *E-13*
HCC load direct rows not compressed, *E-13*
HCC scan cell bytes compressed, *E-13*
HCC scan cell bytes decompressed, *E-13*
HCC scan cell CUs archive high, *E-13*
HCC scan cell CUs archive low, *E-13*
HCC scan cell CUs columns accessed, *E-13*
HCC scan cell CUs decompressed, *E-13*
HCC scan cell CUs decompression time, *E-13*
HCC scan cell CUs optimized read, *E-13*
HCC scan cell CUs pruned, *E-13*
HCC scan cell CUs query high, *E-13*
HCC scan cell CUs query low, *E-13*
HCC scan cell CUs sent compressed, *E-14*
HCC scan cell CUs sent head piece, *E-14*
HCC scan cell CUs sent uncompressed, *E-14*
HCC scan cell rows, *E-14*
HCC scan CUs pcode aggregation pushdown, *E-14*
HCC scan CUs pcode pred evaled, *E-14*
HCC scan CUs pcode pred evaled using rowsets, *E-14*
HCC scan CUs predicates applied, *E-14*
HCC scan CUs predicates optimized, *E-14*
HCC scan CUs predicates received, *E-14*
HCC scan rdbms bytes compressed, *E-14*
HCC scan rdbms bytes decompressed, *E-14*
HCC scan rdbms CUs archive high, *E-14*
HCC scan rdbms CUs archive low, *E-14*
HCC scan rdbms CUs columns accessed, *E-14*
HCC scan rdbms CUs decompressed, *E-14*
HCC scan rdbms CUs decompression time, *E-14*
HCC scan rdbms CUs normal, *E-15*
HCC scan rdbms CUs pruned, *E-15*
HCC scan rdbms CUs query high, *E-15*
HCC scan rdbms CUs query low, *E-15*
HCC scan rdbms CUs turbo, *E-15*
HCC scan rdbms rows, *E-15*
HCC scan rows pcode aggregated, *E-15*
HCC usage cloud, *E-15*
HCC usage pillar, *E-15*

statistics *(continued)*
HCC usage ZFS, *E-15*
hot buffers moved to head of LRU, *E-15*
hot buffers moved to head of LRU for pmem, *E-15*
hot pmem block exchange with dram attempts, *E-15*
hot pmem block exchange with dram successes, *E-16*
hot pmem block migration to dram attempts, *E-16*
hot pmem block migration to dram successes, *E-16*
IM (HPK4SQL) hash joins attempted, *E-16*
IM (HPK4SQL) hash joins completed, *E-16*
IM (hybrid) scan blocks on hybrid list, *E-16*
IM (hybrid) scan rows on hybrid list, *E-16*
IM default area resized, *E-16*
IM populate accumulated time (ms), *E-16*
IM populate bytes in-memory EU data, *E-16*
IM populate bytes uncompressed EU data, *E-16*
IM populate CUs, *E-16*
IM populate CUs memcompress for capacity high, *E-16*
IM populate CUs memcompress for capacity low, *E-16*
IM populate CUs memcompress for dml, *E-16*
IM populate CUs memcompress for query high, *E-16*
IM populate CUs memcompress for query low, *E-16*
IM populate CUs no memcompress, *E-17*
IM populate CUs requested, *E-17*
IM populate EUs, *E-17*
IM populate EUs accumulated time (ms), *E-17*
IM populate EUs columns, *E-17*
IM populate EUs memcompress for capacity high, *E-17*
IM populate EUs memcompress for capacity low, *E-17*
IM populate EUs memcompress for dml, *E-17*
IM populate EUs memcompress for query high, *E-17*
IM populate EUs memcompress for query low, *E-17*
IM populate EUs no memcompress, *E-17*
IM populate EUs requested, *E-17*
IM populate no contiguous inmemory space, *E-17*
IM populate segments, *E-17*
IM populate segments requested, *E-17*

statistics *(continued)*
IM populate segments wall clock time (ms), *E-17*
IM prepopulate accumulated time (ms), *E-17*
IM prepopulate bytes in-memory EU data, *E-17*
IM prepopulate bytes uncompressed EU data, *E-17*
IM prepopulate CUs, *E-17*
IM prepopulate CUs memcompress for capacity high, *E-18*
IM prepopulate CUs memcompress for capacity low, *E-18*
IM prepopulate CUs memcompress for dml, *E-18*
IM prepopulate CUs memcompress for query high, *E-18*
IM prepopulate CUs memcompress for query low, *E-18*
IM prepopulate CUs no memcompress, *E-18*
IM prepopulate CUs requested, *E-18*
IM prepopulate EUs, *E-18*
IM prepopulate EUs accumulated time (ms), *E-18*
IM prepopulate EUs columns, *E-18*
IM prepopulate EUs memcompress for capacity high, *E-18*
IM prepopulate EUs memcompress for capacity low, *E-18*
IM prepopulate EUs memcompress for dml, *E-18*
IM prepopulate EUs memcompress for query high, *E-18*
IM prepopulate EUs memcompress for query low, *E-18*
IM prepopulate EUs no memcompress, *E-18*
IM prepopulate EUs requested, *E-18*
IM prepopulate segments, *E-18*
IM prepopulate segments requested, *E-18*
IM repopulate (doublebuffering) CUs, *E-19*
IM repopulate (doublebuffering) CUs requested, *E-19*
IM repopulate (incremental) CUs, *E-20*
IM repopulate (incremental) CUs requested, *E-20*
IM repopulate (incremental) EUs, *E-20*
IM repopulate (incremental) EUs requested, *E-20*
IM repopulate (scan) CUs, *E-20*
IM repopulate (scan) CUs requested, *E-20*
IM repopulate (scan) EUs, *E-20*
IM repopulate (scan) EUs requested, *E-20*
IM repopulate (trickle) accumulated time (ms), *E-20*
statistics *(continued)*
IM repopulate (trickle) bytes in-memory EU data, *E-20*
IM repopulate (trickle) bytes uncompressed EU data, *E-20*
IM repopulate (trickle) CUs, *E-20*
IM repopulate (trickle) CUs memcompress for capacity high, *E-20*
IM repopulate (trickle) CUs memcompress for capacity low, *E-20*
IM repopulate (trickle) CUs memcompress for dml, *E-21*
IM repopulate (trickle) CUs memcompress for query high, *E-21*
IM repopulate (trickle) CUs memcompress for query low, *E-21*
IM repopulate (trickle) CUs no memcompress, *E-21*
IM repopulate (trickle) CUs requested, *E-21*
IM repopulate (trickle) CUs resubmitted, *E-21*
IM repopulate (trickle) EUs, *E-21*
IM repopulate (trickle) EUs accumulated time (ms), *E-21*
IM repopulate (trickle) EUs columns, *E-21*
IM repopulate (trickle) EUs memcompress for capacity high, *E-21*
IM repopulate (trickle) EUs memcompress for capacity low, *E-21*
IM repopulate (trickle) EUs memcompress for dml, *E-21*
IM repopulate (trickle) EUs memcompress for query high, *E-21*
IM repopulate (trickle) EUs memcompress for query low, *E-21*
IM repopulate (trickle) EUs no memcompress, *E-21*
IM repopulate (trickle) EUs requested, *E-21*
IM repopulate accumulated time (ms), *E-18*
IM repopulate bytes in-memory EU data, *E-18*
IM repopulate CUs, *E-19*
IM repopulate CUs memcompress for capacity high, *E-19*
IM repopulate CUs memcompress for capacity low, *E-19*
IM repopulate CUs memcompress for dml, *E-19*
IM repopulate CUs memcompress for query high, *E-19*
IM repopulate CUs memcompress for query low, *E-19*
IM repopulate CUs no memcompress, *E-19*
IM repopulate CUs requested, *E-19*
IM repopulate EUs, *E-19*

statistics *(continued)*
IM repopulate EUs accumulated time (ms), *E-19*
IM repopulate EUs columns, *E-19*
IM repopulate EUs memcompress for capacity high, *E-19*
IM repopulate EUs memcompress for capacity low, *E-19*
IM repopulate EUs memcompress for dml, *E-19*
IM repopulate EUs memcompress for query high, *E-19*
IM repopulate EUs memcompress for query low, *E-20*
IM repopulate EUs no memcompress, *E-20*
IM repopulate EUs requested, *E-20*
IM repopulate no contiguous inmemory space, *E-20*
IM repopulate segments, *E-20*
IM repopulate segments requested, *E-20*
IM scan (dynamic) multi-threaded scans, *E-22*
IM scan (dynamic) rows, *E-22*
IM scan (dynamic) tasks processed by parent, *E-22*
IM scan (dynamic) tasks processed by thread, *E-22*
IM scan CUs column not in memory, *E-21*
IM scan CUs invalid or missing revert to on disk extent, *E-21*
IM scan CUs memcompress for capacity high, *E-22*
IM scan CUs memcompress for capacity low, *E-22*
IM scan CUs memcompress for dml, *E-22*
IM scan CUs memcompress for query high, *E-22*
IM scan CUs memcompress for query low, *E-22*
IM scan CUs predicates applied, *E-22*
IM scan CUs predicates optimized, *E-22*
IM scan CUs pruned, *E-22*
IM scan EU bytes in-memory, *E-22*
IM scan EU bytes uncompressed, *E-22*
IM scan EU rows, *E-22*
IM scan EUs columns accessed, *E-22*
IM scan EUs columns decompressed, *E-22*
IM scan EUs columns theoretical max, *E-22*
IM scan EUs memcompress for capacity low, *E-22*
IM scan EUs memcompress for dml, *E-22*
IM scan EUs memcompress for query high, *E-22*
IM scan EUs memcompress for query low, *E-23*
statistics *(continued)*
IM scan EUs no memcompress, *E-23*
IM scan EUs split pieces, *E-23*
IM scan rows, *E-23*
IM scan rows optimized, *E-23*
IM scan rows projected, *E-23*
IM scan rows valid, *E-23*
IM scan segments minmax eligible, *E-23*
IM space CU bytes allocated, *E-23*
IM space CU creations initiated, *E-23*
IM space CU extents allocated, *E-23*
IM space segments allocated, *E-23*
IM space segments freed, *E-23*
IM transactions, *E-23*
IM transactions CUs invalid, *E-23*
IM transactions rows invalidated, *E-23*
IM transactions rows journaled, *E-23*
immediate (CR) block cleanout applications, *E-16*
immediate (CURRENT) block cleanout applications, *E-16*
in call idle wait time, *E-23*
index cmph cu, uncomp sentinels, *E-23*
index cmph dm, cu lock expand, *E-23*
index cmph dm, cu migrate row, *E-23*
index cmph dm, insert unpurge CU row, *E-23*
index cmph dm, purge dummy CU, *E-23*
index cmph dm, split for cu lock expand, *E-23*
index cmph dm, split for cu migrate row, *E-24*
index cmph ld, CU fit, *E-24*
index cmph ld, CU fit, add rows, *E-24*
index cmph ld, CU negative comp, *E-24*
index cmph ld, CU over-est, *E-24*
index cmph ld, CU under-est, *E-24*
index cmph ld, infinite loop, *E-24*
index cmph ld, lf blks flushed, *E-24*
index cmph ld, lf blks w/ und CU, *E-24*
index cmph ld, lf blks w/o CU, *E-24*
index cmph ld, lf blks w/o unc r, *E-24*
index cmph ld, retry in over-est, *E-24*
index cmph ld, rows compressed, *E-24*
index cmph ld, rows uncompressed, *E-24*
index cmph sc, ffs decomp buffers, *E-24*
index cmph sc, ffs decomp buffers released and found valid, *E-24*
index cmph sc, ffs decomp buffers rows avail, *E-24*
index cmph sc, ffs decomp buffers rows used, *E-24*
index cmph sc, ffs decomp failures, *E-24*
index cmph sp, leaf 90_10 failed, *E-24*
index cmph sp, leaf norecomp limit, *E-24*
index cmph sp, leaf norecomp negcomp, *E-24*

statistics *(continued)*
index cmph sp, leaf norecomp nospace, *E-24*
index cmph sp, leaf norecomp notry, *E-25*
index cmph sp, leaf norecomp oversize, *E-25*
index cmph sp, leaf norecomp zerocur, *E-25*
index cmph sp, leaf recomp fewer ucs, *E-25*
index cmph sp, leaf recomp zero ucs, *E-25*
index cmph sp, leaf recompress, *E-25*
index cmpl co, prefix mismatch, *E-25*
index cmpl ro, blocks not compressed, *E-25*
index cmpl ro, prefix change at block, *E-25*
index cmpl ro, prefix no change at block, *E-25*
index cmpl ro, reorg avoid load new block, *E-25*
index cmpl ro, reorg avoid split, *E-25*
index fast full scans (direct read), *E-25*
index fast full scans (full), *E-25*
index fast full scans (rowid ranges), *E-25*
large tracked transactions, *E-25*
leaf node splits, *E-25*
lob reads, *E-25*
lob writes, *E-25*
lob writes unaligned, *E-26*
logons cumulative, *E-26*
logons current, *E-26*
memopt r failed puts, *E-26*
memopt r failed reads on blocks, *E-26*
memopt r failed reads on buckets, *E-26*
memopt r hits, *E-26*
memopt r lookup detected CR buffer, *E-26*
memopt r lookups, *E-26*
memopt r misses, *E-26*
memopt r puts, *E-26*
memopt r successful puts, *E-26*
messages received, *E-26*
messages sent, *E-26*
MLE full GC accumulated time, *E-26*
MLE full GC count, *E-26*
MLE incremental GC accumulated time, *E-26*
MLE incremental GC count, *E-26*
MLE JIT compilation duration cumulative, *E-26*
MLE JIT compilation duration max, *E-26*
MLE JIT compilation error count, *E-26*
MLE JIT compilation success count, *E-26*
MLE total memory in use, *E-27*
no buffer to keep pinned count, *E-27*
no work - consistent read gets, *E-27*
non-idle wait count, *E-27*
non-idle wait time, *E-27*
OLAP Aggregate Function Calc, *E-27*
OLAP Aggregate Function Logical NA, *E-27*
OLAP Aggregate Function Precompute, *E-27*
OLAP Custom Member Limit, *E-27*
statistics *(continued)*
OLAP Engine Calls, *E-27*
OLAP Fast Limit, *E-27*
OLAP Full Limit, *E-27*
OLAP GID Limit, *E-27*
OLAP Import Rows Loaded, *E-27*
OLAP Import Rows Pushed, *E-27*
OLAP INHIER Limit, *E-28*
OLAP Limit Time, *E-28*
OLAP Paging Manager Cache Changed Page, *E-28*
OLAP Paging Manager Cache Hit, *E-28*
OLAP Paging Manager Cache Miss, *E-28*
OLAP Paging Manager Cache Write, *E-28*
OLAP Paging Manager New Page, *E-28*
OLAP Paging Manager Pool Size, *E-28*
OLAP Perm LOB Read, *E-28*
OLAP Row Id Limit, *E-28*
OLAP Row Load Time, *E-29*
OLAP Row Source Rows Processed, *E-29*
OLAP Session Cache Hit, *E-29*
OLAP Session Cache Miss, *E-29*
OLAP Temp Segment Read, *E-29*
OLAP Temp Segments, *E-29*
OLAP Unique Key Attribute Limit, *E-29*
opened cursors cumulative, *E-29*
opened cursors current, *E-29*
operating system
OS CPU Qt wait time, *E-29*
OS Involuntary context switches, *E-29*
OS Signals received, *E-30*
OS Swaps, *E-30*
OS Voluntary context switches, *E-30*
Parallel operations downgraded 1 to 25 pct, *E-30*
Parallel operations downgraded 25 to 50 pct, *E-30*
Parallel operations downgraded 50 to 75 pct, *E-30*
Parallel operations downgraded 75 to 99 pct, *E-30*
Parallel operations downgraded to serial, *E-30*
Parallel operations not downgraded, *E-30*
parse count (describe), *E-30*
parse count (hard), *E-30*
parse count (total), *E-30*
parse time cpu, *E-30*
parse time elapsed, *E-30*
physical maps pmem, *E-30*
physical read bytes, *E-30*
physical read flash cache hits, *E-30*
physical read IO requests, *E-31*
physical read requests optimized, *E-31*
physical read total bytes, *E-31*

statistics *(continued)*
physical read total IO requests, *E-31*
physical read total multi block requests, *E-31*
physical reads, *E-31*
physical reads cache, *E-31*
physical reads cache prefetch, *E-31*
physical reads direct, *E-31*
physical reads direct (lob), *E-31*
physical reads direct temporary tablespace, *E-31*
physical reads for flashback new, *E-31*
physical reads pmem, *E-31*
physical reads pmem decrypt, *E-31*
physical reads pmem direct path, *E-32*
physical reads pmem exclusive, *E-32*
physical reads pmem modification, *E-32*
physical reads pmem promote, *E-32*
physical reads pmem rollback, *E-32*
physical reads prefetch warmup, *E-32*
physical unmaps pmem forced, *E-32*
physical write bytes, *E-32*
physical write IO requests, *E-32*
physical write total bytes, *E-32*
physical write total IO requests, *E-32*
physical write total multi block requests, *E-32*
physical writes, *E-32*
physical writes direct, *E-33*
physical writes direct (lob), *E-33*
physical writes direct temporary tablespace, *E-33*
physical writes from cache, *E-33*
physical writes non checkpoint, *E-33*
pinned buffers inspected, *E-33*
pinned buffers inspected for pmem, *E-33*
prefetched blocks aged out before use, *E-33*
process last non-idle time, *E-33*
PX local messages recv'd, *E-33*
PX local messages sent, *E-33*
PX remote messages recv'd, *E-33*
PX remote messages sent, *E-33*
queries parallelized, *E-33*
recovery array read time, *E-33*
recovery array reads, *E-33*
recovery blocks read, *E-33*
recovery blocks read for lost write detection, *E-33*
recovery blocks skipped lost write checks, *E-34*
recursive calls, *E-34*
recursive cpu usage, *E-34*
redo blocks checksummed by FG (exclusive), *E-34*
redo blocks checksummed by LGWR, *E-34*
redo blocks written, *E-34*
redo buffer allocation retries, *E-34*
statistics *(continued)*
redo entries, *E-34*
redo entries for lost write detection, *E-34*
redo log space requests, *E-34*
redo log space wait time, *E-34*
redo ordering marks, *E-34*
redo size, *E-34*
redo size for lost write detection, *E-35*
redo synch time, *E-35*
redo synch writes, *E-35*
redo wastage, *E-35*
redo write time, *E-35*
redo writer latching time, *E-35*
redo writes, *E-35*
rollback changes - undo records applied, *E-35*
rollbacks only - consistent read gets, *E-35*
rows fetched via callback, *E-35*
scheduler wait time, *E-35*
SCN increments due to another database, *E-35*
serializable aborts, *E-35*
session connect time, *E-35*
session cursor cache count, *E-35*
session cursor cache hits, *E-36*
session logical reads, *E-36*
session logical reads - IM, *E-36*
session pga memory, *E-36*
session pga memory max, *E-36*
session stored procedure space, *E-36*
session uga memory, *E-36*
session uga memory max, *E-36*
shared hash latch upgrades - no wait, *E-36*
shared hash latch upgrades - wait, *E-36*
shared io pool buffer get failure, *E-36*
shared io pool buffer get success, *E-36*
slave propagated tracked transactions, *E-36*
sorts (disk), *E-36*
sorts (memory), *E-37*
sorts (rows), *E-37*
SQL*Net roundtrips to/from client, *E-37*
SQL*Net roundtrips to/from dblink, *E-37*
summed dirty queue length, *E-37*
switch current from pmem, *E-37*
switch current to new buffer, *E-37*
table fetch by rowid, *E-37*
table fetch continued row, *E-37*
table scan blocks gotten, *E-37*
table scan disk IMC fallback, *E-38*
table scan disk non-IMC rows gotten, *E-38*
table scan rows gotten, *E-38*
table scans (cache partitions), *E-38*
table scans (direct read), *E-38*
table scans (IM), *E-38*
table scans (long tables), *E-38*

statistics *(continued)*
table scans (rowid ranges), *E-38*
table scans (short tables), *E-38*
timed, *2-386*
tracked rows, *E-38*
tracked transactions, *E-38*
transaction lock background get time, *E-38*
transaction lock background gets, *E-38*
transaction lock foreground requests, *E-38*
transaction lock foreground wait time, *E-38*
transaction rollbacks, *E-38*
transaction tables consistent read rollbacks, *E-38*
transaction tables consistent reads - undo records applied, *E-38*
txns rollback priority_txns_high_wait_target, *E-39*
txns rollback priority_txns_medium_wait_target, *E-39*
txns track mode priority_txns_high_wait_target, *E-39*
txns track mode priority_txns_medium_wait_target, *E-39*
user calls, *E-39*
user commits, *E-40*
user I/O wait time, *E-40*
user rollbacks, *E-40*
very large tracked transactions, *E-40*
write clones created in background, *E-40*
write clones created in foreground, *E-40*
STATISTICS_LEVEL initialization parameter, *2-370*
STMT_AUDIT_OPTION_MAP table, *7-164*
STREAMS_POOL_SIZE initialization parameter, *2-372*
switch redo log file, *2-212*
SYN synonym for USER_SYNONYMS view, *7-164*
SYNONYMS view, *7-165*
SYS_OBJECTS view, *7-165*
SYSCATALOG view, *7-165*
SYSDATE_AT_DBTIMEZONE initialization parameter, *2-373*
SYSFILES view, *7-165*
SYSSEGOBJ view, *7-165*
system global area, *2-2*
buffer areas, *2-212*
system performance, *2-2*
SYSTEM_PRIVILEGE_MAP table, *7-165*

T

TAB view, *7-166*
TABLE_EXPORT_OBJECTS view, *7-166*
TABLE_PRIVILEGE_MAP table, *7-166*
tables
data dictionary, *3-1*
DML locks, *2-128*
locating free space, *2-178*
TABLESPACE_ENCRYPTION initialization parameter, *2-373*
TABLESPACE_ENCRYPTION_DEFAULT_ALGORITHM initialization parameter, *2-375*
TABQUOTAS view, *7-167*
TABS synonym for USER_TABLES view, *7-167*
tape archiving destination, *2-198*
TAPE_ASYNCH_IO initialization parameter, *2-376*
TDE_CONFIGURATION initialization parameter, *2-377*
TDE_KEY_CACHE initialization parameter, *2-379*
TEMP_UNDO_ENABLED initialization parameter, *2-380*
territory, *2-245*, *2-251*
THREAD initialization parameter, *2-381*
THREADED_EXECUTION initialization parameter, *2-382*
TIME_AT_DBTIMEZONE initialization parameter, *2-384*
TIMED_OS_STATISTICS initialization parameter, *2-385*
TIMED_STATISTICS initialization parameter, *2-386*
file read/write statistics, *8-280*, *10-162*
TIMEZONE_VERSION_UPGRADE_ONLINE initialization parameter, *2-387*
TO_CHAR function, *2-243*
TO_DATE function, *2-243*
trace files
destination, *2-401*
maximum size, *2-221*
TRACE_ENABLED initialization parameter, *2-387*
TRACEFILE_IDENTIFIER initialization parameter, *2-388*
TRANSACTION_RECOVERY initialization parameter, *2-389*
transactions
data locking, *2-128*
TRANSACTIONS initialization parameter, *2-390*
DML locks, *2-128*
TRANSACTIONS_PER_ROLLBACK_SEGMENT initialization parameter, *2-390*
TRUE_CACHE initialization parameter, *2-391*
TRUSTED_SERVERS view, *7-167*
TS_PITR_CHECK view, *7-168*

TS_PITR_OBJECTS TO_BE_DROPPED view, *7-169*
TXN_PRIORITY initialization parameter, *2-391*

U

UNDO_MANAGEMENT initialization parameter, *2-392*
UNDO_RETENTION initialization parameter, *2-393*
UNDO_TABLESPACE initialization parameter, *2-395*
UNI_PLUGGABLE_SET_CHECK view, *7-169*
UNIFIED_AUDIT_COMMON_SYSTEMLOG initialization parameter, *2-396*
UNIFIED_AUDIT_SYSTEMLOG initialization parameter, *2-397*
UNIFIED_AUDIT_TRAIL view, *7-170*
UNIFORM_LOG_TIMESTAMP_FORMAT initialization parameter, *2-398*
updates
  locating free space, *2-178*
upgrading
  scripts, *B-6*
uppercase characters, *2-5*
USABLE_EDITIONS view, *7-180*
USE_DEDICATED_BROKER initialization parameter, *2-399*
USE_LARGE_PAGES initialization parameter, *2-400*
user processes
  trace files, *2-401*
USER_ADDM_FDG_BREAKDOWN view, *7-181*
USER_ADDM_FINDINGS view, *7-181*
USER_ADDM_INSTANCES view, *7-181*
USER_ADDM_TASK_DIRECTIVES view, *7-182*
USER_ADDM_TASKS view, *7-182*
USER_ADVISOR_ACTIONS view, *7-182*
USER_ADVISOR_DIR_TASK_INST view, *7-183*
USER_ADVISOR_EXEC_PARAMETERS view, *7-183*
USER_ADVISOR_EXECUTIONS view, *7-183*
USER_ADVISOR_FDG_BREAKDOWN view, *7-183*
USER_ADVISOR_FINDINGS view, *7-184*
USER_ADVISOR_JOURNAL view, *7-184*
USER_ADVISOR_LOG view, *7-184*
USER_ADVISOR_OBJECTS view, *7-184*
USER_ADVISOR_PARAMETERS view, *7-185*
USER_ADVISOR_RATIONALE view, *7-185*
USER_ADVISOR_RECOMMENDATIONS view, *7-185*
USER_ADVISOR_SQLA_REC_SUM view, *7-185*
USER_ADVISOR_SQLA_TABLES view, *7-186*
USER_ADVISOR_SQLA_WK_MAP view, *7-186*
USER_ADVISOR_SQLA_WK_STMTS view, *7-186*
USER_ADVISOR_SQLPLANS view, *7-186*
USER_ADVISOR_SQLSTATS view, *7-187*
USER_ADVISOR_SQLW_JOURNAL view, *7-187*
USER_ADVISOR_SQLW_PARAMETERS view, *7-187*
USER_ADVISOR_SQLW_STMTS view, *7-187*
USER_ADVISOR_SQLW_SUM view, *7-188*
USER_ADVISOR_SQLW_TABLES view, *7-188*
USER_ADVISOR_SQLW_TEMPLATES view, *7-188*
USER_ADVISOR_TASKS view, *7-188*
USER_ADVISOR_TEMPLATES view, *7-189*
USER_ALL_TABLES view, *7-189*
USER_ANALYTIC_VIEW_ATTR_CLASS view, *7-189*
USER_ANALYTIC_VIEW_ATTR_CLS view, *7-189*
USER_ANALYTIC_VIEW_ATTR_CLS_AE view, *7-190*
USER_ANALYTIC_VIEW_BAS_MEAS view, *7-190*
USER_ANALYTIC_VIEW_BAS_MEAS_AE view, *7-190*
USER_ANALYTIC_VIEW_BASE_MEAS view, *7-190*
USER_ANALYTIC_VIEW_CALC_MEAS view, *7-191*
USER_ANALYTIC_VIEW_CLASS view, *7-191*
USER_ANALYTIC_VIEW_CLASS_AE view, *7-191*
USER_ANALYTIC_VIEW_CLC_MEAS view, *7-191*
USER_ANALYTIC_VIEW_CLC_MEAS_AE view, *7-192*
USER_ANALYTIC_VIEW_COLUMNS view, *7-192*
USER_ANALYTIC_VIEW_COLUMNS_AE view, *7-192*
USER_ANALYTIC_VIEW_DIM_ATRS view, *7-192*
USER_ANALYTIC_VIEW_DIM_ATRS_AE view, *7-193*
USER_ANALYTIC_VIEW_DIM_ATTRS view, *7-193*
USER_ANALYTIC_VIEW_DIM_CLASS view, *7-193*
USER_ANALYTIC_VIEW_DIM_CLS view, *7-193*
USER_ANALYTIC_VIEW_DIM_CLS_AE view, *7-194*
USER_ANALYTIC_VIEW_DIMENSIONS view, *7-194*
USER_ANALYTIC_VIEW_DIMS view, *7-194*
USER_ANALYTIC_VIEW_DIMS_AE view, *7-194*

USER_ANALYTIC_VIEW_FACT_COLS view, *7-195*
USER_ANALYTIC_VIEW_FCT_COLS view, *7-195*
USER_ANALYTIC_VIEW_FCT_COLS_AE view, *7-195*
USER_ANALYTIC_VIEW_HIER_CLASS view, *7-195*
USER_ANALYTIC_VIEW_HIER_CLS view, *7-196*
USER_ANALYTIC_VIEW_HIER_CLS_AE view, *7-196*
USER_ANALYTIC_VIEW_HIERS view, *7-196*
USER_ANALYTIC_VIEW_HIERS_AE view, *7-196*
USER_ANALYTIC_VIEW_KEYS view, *7-197*
USER_ANALYTIC_VIEW_KEYS_AE view, *7-197*
USER_ANALYTIC_VIEW_LEVEL_CLASS view, *7-197*
USER_ANALYTIC_VIEW_LEVELS view, *7-197*
USER_ANALYTIC_VIEW_LEVELS_AE view, *7-198*
USER_ANALYTIC_VIEW_LVL_CLS view, *7-198*
USER_ANALYTIC_VIEW_LVL_CLS_AE view, *7-198*
USER_ANALYTIC_VIEW_LVLGRPS view, *7-198*
USER_ANALYTIC_VIEW_LVLGRPS_AE view, *7-199*
USER_ANALYTIC_VIEW_MEAS_CLASS view, *7-199*
USER_ANALYTIC_VIEW_MEAS_CLS view, *7-199*
USER_ANALYTIC_VIEW_MEAS_CLS_AE view, *7-199*
USER_ANALYTIC_VIEWS view, *7-200*
USER_ANALYTIC_VIEWS_AE view, *7-200*
USER_ANNOTATION_VALUES view, *7-200*
USER_ANNOTATIONS view, *7-200*
USER_ANNOTATIONS_USAGE view, *7-201*
USER_APPLICATION_ROLES view, *7-201*
USER_APPLY_ERROR view, *7-202*
USER_AQ_AGENT_PRIVS view, *7-202*
USER_ARGUMENTS view, *7-202*
USER_ASSEMBLIES view, *7-203*
USER_ASSOCIATIONS view, *7-203*
USER_ATTRIBUTE_DIM_ATTR_CLASS view, *7-203*
USER_ATTRIBUTE_DIM_ATTR_CLS view, *7-203*
USER_ATTRIBUTE_DIM_ATTR_CLS_AE view, *7-204*
USER_ATTRIBUTE_DIM_ATTRS view, *7-204*
USER_ATTRIBUTE_DIM_ATTRS_AE view, *7-204*
USER_ATTRIBUTE_DIM_CLASS view, *7-204*
USER_ATTRIBUTE_DIM_CLASS_AE view, *7-205*
USER_ATTRIBUTE_DIM_JN_PTHS view, *7-205*
USER_ATTRIBUTE_DIM_JN_PTHS_AE view, *7-205*
USER_ATTRIBUTE_DIM_JOIN_PATHS view, *7-205*
USER_ATTRIBUTE_DIM_KEYS view, *7-206*
USER_ATTRIBUTE_DIM_KEYS_AE view, *7-206*
USER_ATTRIBUTE_DIM_LEVEL_ATTRS view, *7-206*
USER_ATTRIBUTE_DIM_LEVELS view, *7-206*
USER_ATTRIBUTE_DIM_LEVELS_AE view, *7-207*
USER_ATTRIBUTE_DIM_LVL_ATRS view, *7-207*
USER_ATTRIBUTE_DIM_LVL_ATRS_AE view, *7-207*
USER_ATTRIBUTE_DIM_LVL_CLASS view, *7-207*
USER_ATTRIBUTE_DIM_LVL_CLS view, *7-208*
USER_ATTRIBUTE_DIM_LVL_CLS_AE view, *7-208*
USER_ATTRIBUTE_DIM_ORD_ATRS view, *7-208*
USER_ATTRIBUTE_DIM_ORD_ATRS_AE view, *7-208*
USER_ATTRIBUTE_DIM_ORDER_ATTRS view, *7-209*
USER_ATTRIBUTE_DIM_TABLES view, *7-209*
USER_ATTRIBUTE_DIM_TABLES_AE view, *7-209*
USER_ATTRIBUTE_DIMENSIONS view, *7-209*
USER_ATTRIBUTE_DIMENSIONS_AE view, *7-210*
USER_ATTRIBUTE_TRANSFORMATIONS view, *7-210*
USER_AUDIT_OBJECT view, *7-210*
USER_AUDIT_POLICIES view, *7-211*
USER_AUDIT_POLICY_COLUMNS view, *7-211*
USER_AUDIT_SESSION view, *7-212*
USER_AUDIT_STATEMENT view, *7-212*
USER_AUDIT_TRAIL view, *7-212*
USER_AW_PS view, *7-213*
USER_AWS view, *7-213*
USER_BASE_TABLE_MVIEWS view, *7-213*
USER_BLOCKCHAIN_ROW_VERSION_COLS view, *7-213*
USER_BLOCKCHAIN_ROW_VERSION_HISTORY view, *7-214*
USER_BLOCKCHAIN_TABLE_CHAINS view, *7-214*
USER_BLOCKCHAIN_TABLE_EPOCHS view, *7-215*

USER_BLOCKCHAIN_TABLE_HASH_COL_ORDER view, *7-215*
USER_BLOCKCHAIN_TABLES view, *7-215*
USER_CATALOG view, *7-216*
CAT synonym, *4-224*
USER_CERTIFICATES view, *7-216*
USER_CHANGE_NOTIFICATION_REGS view, *7-216*
USER_CLU_COLUMNS view, *7-216*
USER_CLUSTER_HASH_EXPRESSIONS view, *7-217*
USER_CLUSTERING_DIMENSIONS view, *7-217*
USER_CLUSTERING_JOINS view, *7-217*
USER_CLUSTERING_KEYS view, *7-218*
USER_CLUSTERING_TABLES view, *7-218*
USER_CLUSTERS view, *7-218*
CLU synonym, *4-225*
USER_CODE_ROLE_PRIVS view, *7-219*
USER_COL_COMMENTS view, *7-219*
USER_COL_PENDING_STATS view, *7-219*
USER_COL_PRIVS view, *7-219*
USER_COL_PRIVS_MADE view, *7-220*
USER_COL_PRIVS_RECD view, *7-220*
USER_COLL_TYPES view, *7-220*
USER_COMPARISON view, *7-220*
USER_COMPARISON_COLUMNS view, *7-221*
USER_COMPARISON_ROW_DIF view, *7-221*
USER_COMPARISON_SCAN view, *7-221*
USER_COMPARISON_SCAN_VALUES view, *7-221*
USER_CONS_COLUMNS view, *7-222*
USER_CONS_OBJ_COLUMNS view, *7-222*
USER_CONSTRAINTS view, *7-222*
USER_CQ_NOTIFICATION_QUERIES view, *7-222*
USER_CREDENTIALS view, *7-223*
USER_CUBE_ATTR_VISIBILITY view, *7-223*
USER_CUBE_ATTRIBUTES view, *7-223*
USER_CUBE_BUILD_PROCESSES view, *7-223*
USER_CUBE_CALCULATED_MEMBERS view, *7-224*
USER_CUBE_DIM_LEVELS view, *7-224*
USER_CUBE_DIM_MODELS view, *7-224*
USER_CUBE_DIM_VIEW_COLUMNS view, *7-224*
USER_CUBE_DIM_VIEWS view, *7-225*
USER_CUBE_DIMENSIONALITY view, *7-225*
USER_CUBE_DIMENSIONS view, *7-225*
USER_CUBE_HIER_LEVELS view, *7-225*
USER_CUBE_HIER_VIEW_COLUMNS view, *7-226*
USER_CUBE_HIER_VIEWS view, *7-226*
USER_CUBE_HIERARCHIES view, *7-226*
USER_CUBE_MEASURES view, *7-226*
USER_CUBE_NAMED_BUILD_SPECS view, *7-227*
USER_CUBE_SUB_PARTITION_LEVELS view, *7-227*
USER_CUBE_VIEW_COLUMNS view, *7-227*
USER_CUBE_VIEWS view, *7-227*
USER_CUBES view, *7-228*
USER_DATAPUMP_JOBS view, *7-228*
USER_DB_LINKS view, *7-228*
USER_DBFS_HS view, *7-228*
USER_DBFS_HS_COMMANDS view, *7-229*
USER_DBFS_HS_FILES view, *7-229*
USER_DBFS_HS_FIXED_PROPERTIES view, *7-229*
USER_DBFS_HS_PROPERTIES view, *7-230*
USER_DDL_REGS view, *7-230*
USER_DEPENDENCIES view, *7-230*
USER_DIM_ATTRIBUTES view, *7-231*
USER_DIM_CHILD_OF view, *7-231*
USER_DIM_HIERARCHIES view, *7-231*
USER_DIM_JOIN_KEY view, *7-231*
USER_DIM_LEVEL_KEY view, *7-232*
USER_DIM_LEVELS view, *7-232*
USER_DIMENSIONS view, *7-232*
USER_DOMAIN_COLS view, *7-232*
USER_DOMAIN_CONSTRAINTS view, *7-233*
USER_DOMAINS view, *7-233*
USER_DUMP_DEST initialization parameter, *2-401*
USER_EDITIONED_TYPES view, *7-234*
USER_EDITIONING_VIEW_COLS view, *7-234*
USER_EDITIONING_VIEW_COLS_AE view, *7-234*
USER_EDITIONING_VIEWS view, *7-234*
USER_EDITIONING_VIEWS_AE view, *7-235*
USER_ENCRYPTED_COLUMNS view, *7-235*
USER_EPG_DAD_AUTHORIZATION view, *7-235*
USER_ERROR_TRANSLATIONS view, *7-235*
USER_ERRORS view, *7-236*
USER_ERRORS_AE view, *7-236*
USER_EVALUATION_CONTEXT_TABLES view, *7-236*
USER_EVALUATION_CONTEXT_VARS view, *7-236*
USER_EVALUATION_CONTEXTS view, *7-237*
USER_EXPRESSION_STATISTICS view, *7-237*
USER_EXTENTS view, *7-237*
USER_EXTERNAL_LOCATIONS view, *7-237*
USER_EXTERNAL_TABLES view, *7-238*
USER_FLASHBACK_ARCHIVE view, *7-238*
USER_FLASHBACK_ARCHIVE_TABLES view, *7-238*
USER_FLASHBACK_TXN_REPORT view, *7-239*
USER_FLASHBACK_TXN_STATE view, *7-239*

USER_FREE_SPACE view, *7-239*
USER_GOLDENGATE_PRIVILEGES view, *7-239*
USER_HEAT_MAP_SEG_HISTOGRAM view, *7-240*
USER_HEAT_MAP_SEGMENT view, *7-240*
USER_HIER_CLASS view, *7-240*
USER_HIER_CLASS_AE view, *7-240*
USER_HIER_COLUMNS view, *7-241*
USER_HIER_COLUMNS_AE view, *7-241*
USER_HIER_HIER_ATTR_CLASS view, *7-241*
USER_HIER_HIER_ATTR_CLASS_AE view, *7-241*
USER_HIER_HIER_ATTRIBUTES view, *7-242*
USER_HIER_HIER_ATTRIBUTES_AE view, *7-242*
USER_HIER_JOIN_PATHS view, *7-242*
USER_HIER_JOIN_PATHS_AE view, *7-242*
USER_HIER_LEVEL_ID_ATTRS view, *7-243*
USER_HIER_LEVEL_ID_ATTRS_AE view, *7-243*
USER_HIER_LEVELS view, *7-243*
USER_HIER_LEVELS_AE view, *7-243*
USER_HIERARCHIES view, *7-244*
USER_HIERARCHIES_AE view, *7-244*
USER_HIST_SAGAS view, *7-244*
USER_HISTOGRAMS synonym for USER_TAB_HISTOGRAMS, *7-245*
USER_HIVE_COLUMNS view, *7-245*
USER_HIVE_DATABASES view, *7-245*
USER_HIVE_PART_KEY_COLUMNS view, *7-245*
USER_HIVE_TAB_PARTITIONS view, *7-246*
USER_HIVE_TABLES view, *7-246*
USER_HOST_ACES view, *7-246*
USER_IDENTIFIERS view, *7-247*
USER_ILMDATAMOVEMENTPOLICIES view, *7-247*
USER_ILMEVALUATIONDETAILS view, *7-247*
USER_ILMOBJECTS view, *7-248*
USER_ILMPOLICIES view, *7-248*
USER_ILMRESULTS view, *7-249*
USER_ILMTASKS view, *7-249*
USER_IM_EXPRESSIONS view, *7-249*
USER_IMMUTABLE_ROW_VERSION_COLS view, *7-250*
USER_IMMUTABLE_ROW_VERSION_HISTORY view, *7-250*
USER_IMMUTABLE_TABLE_COLUMNS view, *7-251*
USER_IMMUTABLE_TABLE_EPOCHS view, *7-251*
USER_IMMUTABLE_TABLES view, *7-251*
USER_INCOMPLETE_SAGAS view, *7-252*
USER_IND_COLUMNS view, *7-252*
USER_IND_EXPRESSIONS view, *7-252*
USER_IND_PARTITIONS view, *7-252*
USER_IND_PENDING_STATS view, *7-253*
USER_IND_STATISTICS view, *7-253*
USER_IND_SUBPARTITIONS view, *7-253*
USER_INDEXES view, *7-254*
  IND synonym, *7-139*
USER_INDEXTYPE_ARRAYTYPES view, *7-254*
USER_INDEXTYPE_COMMENTS view, *7-254*
USER_INDEXTYPE_OPERATORS view, *7-254*
USER_INDEXTYPES view, *7-255*
USER_INTERNAL_TRIGGERS view, *7-255*
USER_JAVA_ARGUMENTS view, *7-255*
USER_JAVA_CLASSES view, *7-255*
USER_JAVA_COMPILER_OPTIONS view, *7-256*
USER_JAVA_DERIVATIONS view, *7-256*
USER_JAVA_FIELDS view, *7-256*
USER_JAVA_IMPLEMENTS view, *7-257*
USER_JAVA_INNERS view, *7-257*
USER_JAVA_LAYOUTS view, *7-257*
USER_JAVA_METHODS view, *7-257*
USER_JAVA_NCOMPS view, *7-258*
USER_JAVA_POLICY view, *7-258*
USER_JAVA_RESOLVERS view, *7-258*
USER_JAVA_THROWS view, *7-258*
USER_JOBS view, *7-259*
  ALL_JOBS synonym, *3-237*
USER_JOIN_IND_COLUMNS view, *7-259*
USER_JOINGROUPS view, *7-259*
USER_JSON_COLLECTION_TABLES view, *7-260*
USER_JSON_COLLECTIONS view, *7-260*
USER_JSON_COLUMNS view, *7-260*
USER_JSON_DATAGUIDE_FIELDS view, *7-261*
USER_JSON_DATAGUIDES view, *7-261*
USER_JSON_DOMAIN_SCHEMA_COLUMNS view, *7-261*
USER_JSON_DUALITY_VIEW_LINKS view, *7-262*
USER_JSON_DUALITY_VIEW_TAB_COLS view, *7-262*
USER_JSON_DUALITY_VIEW_TABS view, *7-262*
USER_JSON_DUALITY_VIEWS view, *7-263*
USER_JSON_INDEXES view, *7-263*
USER_JSON_SCHEMA_COLUMNS view, *7-264*
USER_KAFKA_APPLICATIONS view, *7-264*
USER_KAFKA_CLUSTERS view, *7-264*
USER_KAFKA_LOAD_METRICS view, *7-265*
USER_KAFKA_MESSAGES view, *7-265*
USER_KAFKA_OPS view, *7-266*
USER_KAFKA_OPS_RESULTS view, *7-267*
USER_KAFKA_PARTITIONS view, *7-267*
USER_LIBRARIES view, *7-268*
USER_LOB_PARTITIONS view, *7-268*

USER_LOB_SUBPARTITIONS view, *7-268*
USER_LOB_TEMPLATES view, *7-268*
USER_LOBS view, *7-269*
USER_LOG_GROUP_COLUMNS view, *7-269*
USER_LOG_GROUPS view, *7-269*
USER_MEASURE_FOLDER_CONTENTS view, *7-269*
USER_MEASURE_FOLDER_SUBFOLDERS view, *7-270*
USER_MEASURE_FOLDERS view, *7-270*
USER_METADATA_PROPERTIES view, *7-270*
USER_METHOD_PARAMS view, *7-270*
USER_METHOD_RESULTS view, *7-271*
USER_MINING_MODEL_ATTRIBUTES view, *7-271*
USER_MINING_MODEL_PARTITIONS view, *7-271*
USER_MINING_MODEL_SETTINGS view, *7-272*
USER_MINING_MODEL_VIEWS view, *7-272*
USER_MINING_MODEL_XFORMS view, *7-272*
USER_MINING_MODELS view, *7-272*
USER_MLE_ENV_IMPORTS view, *7-273*
USER_MLE_ENVS view, *7-273*
USER_MLE_MODULES view, *7-273*
USER_MLE_PROCEDURES view, *7-274*
USER_MVIEW_AGGREGATES view, *7-274*
USER_MVIEW_ANALYSIS view, *7-275*
USER_MVIEW_COMMENTS view, *7-275*
USER_MVIEW_DETAIL_LOGICAL_PARTITION view, *7-275*
USER_MVIEW_DETAIL_PARTITION view, *7-276*
USER_MVIEW_DETAIL_RELATIONS view, *7-276*
USER_MVIEW_DETAIL_SUBPARTITION view, *7-276*
USER_MVIEW_JOINS view, *7-276*
USER_MVIEW_KEYS view, *7-277*
USER_MVIEW_LOGS view, *7-277*
USER_MVIEW_REFRESH_TIMES view, *7-277*
USER_MVIEWS view, *7-277*
USER_MVREF_CHANGE_STATS view, *7-278*
USER_MVREF_RUN_STATS view, *7-278*
USER_MVREF_STATS view, *7-278*
USER_MVREF_STATS_PARAMS view, *7-279*
USER_MVREF_STATS_SYS_DEFAULTS view, *7-279*
USER_MVREF_STMT_STATS view, *7-279*
USER_NESTED_TABLE_COLS view, *7-279*
USER_NESTED_TABLES view, *7-280*
USER_NETWORK_ACL_PRIVILEGES view, *7-280*
USER_OBJ_AUDIT_OPTS view, *7-281*
USER_OBJ_COLATTRS view, *7-281*
USER_OBJECT_SIZE view, *7-281*
USER_OBJECT_TABLES view, *7-282*
USER_OBJECT_USAGE view, *7-282*
USER_OBJECTS view, *7-282*
  OBJ synonym, *7-143*
USER_OBJECTS_AE view, *7-282*
USER_OGG_AUTO_CAPTURED_TABLES view, *7-283*
USER_OPANCILLARY view, *7-283*
USER_OPARGUMENTS view, *7-283*
USER_OPBINDINGS view, *7-283*
USER_OPERATOR_COMMENTS view, *7-284*
USER_OPERATORS view, *7-284*
USER_OUTLINE_HINTS view, *7-284*
  ALL_OUTLINE_HINTS synonym, *3-307*
USER_OUTLINES view, *7-284*
  ALL_OUTLINES synonym, *3-307*
USER_PARALLEL_EXECUTE_CHUNKS view, *7-285*
USER_PARALLEL_EXECUTE_TASKS view, *7-285*
USER_PART_COL_STATISTICS view, *7-285*
USER_PART_HISTOGRAMS view, *7-285*
USER_PART_INDEXES view, *7-286*
USER_PART_KEY_COLUMNS view, *7-286*
USER_PART_LOBS view, *7-286*
USER_PART_TABLES view, *7-286*
USER_PARTIAL_DROP_TABS view, *7-287*
USER_PASSWORD_LIMITS view, *7-287*
USER_PENDING_CONV_TABLES view, *7-287*
USER_PG_EDGE_RELATIONSHIPS view, *7-287*
USER_PG_ELEMENT_LABELS view, *7-288*
USER_PG_ELEMENTS view, *7-288*
USER_PG_KEYS view, *7-289*
USER_PG_LABEL_PROPERTIES view, *7-289*
USER_PG_LABELS view, *7-289*
USER_PG_PROP_DEFINITIONS view, *7-290*
USER_PLSQL_COLL_TYPES view, *7-290*
USER_PLSQL_OBJECT_SETTINGS view, *7-290*
USER_PLSQL_TYPE_ATTRS view, *7-291*
USER_PLSQL_TYPES view, *7-291*
USER_POLICIES view, *7-291*
USER_POLICY_ATTRIBUTES view, *7-291*
USER_POLICY_CONTEXTS view, *7-292*
USER_POLICY_GROUPS view, *7-292*
USER_PRIVATE_TEMP_TABLES view, *7-292*
USER_PRIVILEGE_MAP view, *7-292*
USER_PROCEDURES view, *7-293*
USER_PROPERTY_GRAPHS view, *7-293*
USER_PROXIES view, *7-293*
USER_QUEUE_EVENT_STREAMS view, *7-294*
USER_QUEUE_SCHEDULES view, *7-294*
USER_QUEUE_SUBSCRIBERS view, *7-294*
USER_QUEUE_TABLES view, *7-294*

USER_QUEUES view, *7-295*
USER_RECYCLEBIN view, *7-295*
RECYCLEBIN synonym, *7-152*
USER_REFRESH view, *7-295*
USER_REFRESH_CHILDREN view, *7-295*
USER_REFS view, *7-296*
USER_REGISTERED_MVIEWS view, *7-296*
USER_REGISTRY view, *7-296*
USER_RESOURCE_LIMITS view, *7-296*
USER_RESUMABLE view, *7-297*
USER_REWRITE_EQUIVALENCES view, *7-297*
USER_ROLE_PRIVS view, *7-297*
USER_RSRC_CONSUMER_GROUP_PRIVS view, *7-298*
USER_RSRC_MANAGER_SYSTEM_PRIVS view, *7-298*
USER_RULE_SET_RULES view, *7-298*
USER_RULE_SETS view, *7-299*
USER_RULES view, *7-299*
USER_SAGA_BROKERS view, *7-299*
USER_SAGA_DETAILS view, *7-300*
USER_SAGA_ERRORS view, *7-300*
USER_SAGA_FINALIZATION view, *7-300*
USER_SAGA_PARTICIPANT_SET view, *7-301*
USER_SAGA_PARTICIPANTS view, *7-301*
USER_SAGA_PENDING view, *7-302*
USER_SAGAS view, *7-302*
USER_SCHEDULER_CHAIN_RULES view, *7-303*
USER_SCHEDULER_CHAIN_STEPS view, *7-303*
USER_SCHEDULER_CHAINS view, *7-303*
USER_SCHEDULER_CREDENTIALS view, *7-303*
USER_SCHEDULER_DB_DESTS view, *7-304*
USER_SCHEDULER_DESTS view, *7-304*
USER_SCHEDULER_FILE_WATCHERS view, *7-304*
USER_SCHEDULER_GROUP_MEMBERS view, *7-305*
USER_SCHEDULER_GROUPS view, *7-305*
USER_SCHEDULER_INCOMPAT_MEMBER view, *7-305*
USER_SCHEDULER_INCOMPATS view, *7-305*
USER_SCHEDULER_JOB_ARGS view, *7-306*
USER_SCHEDULER_JOB_DESTS view, *7-306*
USER_SCHEDULER_JOB_LOG view, *7-306*
USER_SCHEDULER_JOB_RUN_DETAILS view, *7-306*
USER_SCHEDULER_JOBS view, *7-307*
USER_SCHEDULER_NOTIFICATIONS view, *7-307*
USER_SCHEDULER_PROGRAM_ARGS view, *7-307*
USER_SCHEDULER_PROGRAMS view, *7-307*
USER_SCHEDULER_REMOTE_JOBSTATE view, *7-308*
USER_SCHEDULER_RESOURCES view, *7-308*
USER_SCHEDULER_RSC_CONSTRAINTS view, *7-308*
USER_SCHEDULER_RUNNING_CHAINS view, *7-308*
USER_SCHEDULER_RUNNING_JOBS view, *7-309*
USER_SCHEDULER_SCHEDULES view, *7-309*
USER_SCHEMA_PRIVS view, *7-309*
USER_SEC_RELEVANT_COLS view, *7-310*
USER_SECONDARY_OBJECTS view, *7-310*
USER_SEGMENTS view, *7-310*
USER_SEQUENCES view, *7-311*
SEQ synonym, *7-161*
USER_SODA_COLLECTIONS view, *7-311*
USER_SOURCE view, *7-311*
USER_SOURCE_AE view, *7-312*
USER_SQL_TRANSLATION_PROFILES view, *7-312*
USER_SQL_TRANSLATIONS view, *7-312*
USER_SQLJ_TYPE_ATTRS view, *7-312*
USER_SQLJ_TYPE_METHODS view, *7-313*
USER_SQLJ_TYPES view, *7-313*
USER_SQLSET view, *7-313*
USER_SQLSET_BINDS view, *7-313*
USER_SQLSET_PLANS view, *7-314*
USER_SQLSET_REFERENCES view, *7-314*
USER_SQLSET_STATEMENTS view, *7-314*
USER_SQLTUNE_BINDS view, *7-314*
USER_SQLTUNE_PLANS view, *7-315*
USER_SQLTUNE_RATIONALE_PLAN view, *7-315*
USER_SQLTUNE_STATISTICS view, *7-315*
USER_SR_GRP_STATUS view, *7-315*
USER_SR_GRP_STATUS_ALL view, *7-316*
USER_SR_OBJ view, *7-316*
USER_SR_OBJ_ALL view, *7-316*
USER_SR_OBJ_STATUS view, *7-316*
USER_SR_OBJ_STATUS_ALL view, *7-317*
USER_SR_PARTN_OPS view, *7-317*
USER_SR_STLOG_EXCEPTIONS view, *7-317*
USER_SR_STLOG_STATS view, *7-317*
USER_STAT_EXTENSIONS view, *7-318*
USER_STATEMENTS view, *7-318*
USER_STORED_SETTINGS view, *7-318*
USER_SUBPART_COL_STATISTICS view, *7-319*
USER_SUBPART_HISTOGRAMS view, *7-319*
USER_SUBPART_KEY_COLUMNS view, *7-319*
USER_SUBPARTITION_TEMPLATES view, *7-319*
USER_SUBSCR_REGISTRATIONS view, *7-320*

USER_SYNONYMS view, *7-320*
SYN synonym, *7-164*
USER_SYS_PRIVS view, *7-320*
USER_SYS_PRIVS_ALL view, *7-321*
USER_TAB_COL_STAT_MODELS view, *7-321*
USER_TAB_COL_STATISTICS view, *7-322*
USER_TAB_COLS view, *7-322*
USER_TAB_COLUMNS view, *7-322*
COLS synonym, *4-226*
USER_TAB_COMMENTS view, *7-323*
USER_TAB_HISTGRM_PENDING_STATS view, *7-323*
USER_TAB_HISTOGRAMS view, *7-323*
USER_HISTOGRAMS synonym, *7-245*
USER_TAB_IDENTITY_COLS view, *7-324*
USER_TAB_MODIFICATIONS view, *7-324*
USER_TAB_PARTITIONS view, *7-324*
USER_TAB_PENDING_STATS view, *7-325*
USER_TAB_PRIVS view, *7-325*
USER_TAB_PRIVS_MADE view, *7-325*
USER_TAB_PRIVS_RECD view, *7-325*
USER_TAB_STAT_PREFS view, *7-326*
USER_TAB_STATISTICS view, *7-326*
USER_TAB_STATS_HISTORY view, *7-326*
USER_TAB_SUBPARTITIONS view, *7-326*
USER_TABLE_ACCESS_STATS view, *7-327*
USER_TABLE_VIRTUAL_COLUMNS view, *7-327*
USER_TABLES view, *7-327*
TABS synonym, *7-167*
USER_TABLESPACES view, *7-328*
USER_TRANSFORMATIONS view, *7-328*
USER_TRIGGER_COLS view, *7-328*
USER_TRIGGER_ORDERING view, *7-328*
USER_TRIGGERS view, *7-329*
USER_TRIGGERS_AE view, *7-329*
USER_TS_QUOTAS view, *7-329*
USER_TSTZ_TAB_COLS view, *7-329*
USER_TSTZ_TABLES view, *7-330*
USER_TUNE_MVIEW view, *7-330*
USER_TXEVENTQ_MIGRATION_STATUS view, *7-330*
USER_TYPE_ATTRS view, *7-331*
USER_TYPE_METHODS view, *7-331*
USER_TYPE_VERSIONS view, *7-331*
USER_TYPES view, *7-331*
USER_UNUSED_COL_TABS view, *7-332*
USER_UPDATABLE_COLUMNS view, *7-332*
USER_USERS view, *7-332*
USER_USTATS view, *7-337*
USER_VARRAYS view, *7-337*
USER_VIEWS view, *7-338*
USER_VIEWS_AE view, *7-338*
USER_WALLET_ACES view, *7-338*
USER_WARNING_SETTINGS view, *7-338*
USER_XML_INDEXES view, *7-339*
USER_XML_NESTED_TABLES view, *7-339*
USER_XML_OUT_OF_LINE_TABLES view, *7-339*
USER_XML_SCHEMA_ATTRIBUTES view, *7-339*
USER_XML_SCHEMA_COMPLEX_TYPES view, *7-340*
USER_XML_SCHEMA_ELEMENTS view, *7-340*
USER_XML_SCHEMA_NAMESPACES view, *7-340*
USER_XML_SCHEMA_SIMPLE_TYPES view, *7-340*
USER_XML_SCHEMA_SUBSTGRP_HEAD view, *7-341*
USER_XML_SCHEMA_SUBSTGRP_MBRS view, *7-341*
USER_XML_SCHEMAS view, *7-341*
USER_XML_TAB_COLS view, *7-341*
USER_XML_TABLES view, *7-342*
USER_XML_VIEW_COLS view, *7-342*
USER_XML_VIEWS view, *7-342*
USER_XTERNAL_LOC_PARTITIONS view, *7-342*
USER_XTERNAL_LOC_SUBPARTITIONS view, *7-343*
USER_XTERNAL_PART_TABLES view, *7-343*
USER_XTERNAL_TAB_PARTITIONS view, *7-343*
USER_XTERNAL_TAB_SUBPARTITIONS view, *7-343*
USER_ZONEMAP_MEASURES view, *7-344*
USER_ZONEMAPS view, *7-344*
USERLOCK.SQL script, *B-3*
users
authenticating, *2-274*
multiple, *2-128*
UTLBSTAT.SQL script, *B-3*
UTLCHN1.SQL script, *B-3*
UTLCONST.SQL script, *B-3*
UTLDTREE.SQL script, *7-128*, *7-139*, *B-4*
UTLESTAT.SQL script, *B-3*
UTLEXPT1.SQL script, *B-4*
UTLFIXDIRS.SQL script, *B-4*
UTLIP.SQL script, *B-4*
UTLIRP.SQL script, *B-4*
UTLLOCKT.SQL script, *B-4*
UTLPWDMG.SQL script, *B-5*
UTLRP.SQL script, *B-5*
UTLSAMPL.SQL script, *B-5*
UTLSCLN.SQL script, *B-5*
UTLTKPRF.SQL script, *B-5*
UTLVALID.SQL script, *B-5*
UTLXPLAN.SQL script, *B-5*

V

V$ACCESS view, 8-3
V$ACTIVE_INSTANCES view, 8-4
V$ACTIVE_SERVICES view, 8-4
V$ACTIVE_SESS_POOL_MTH view, 8-7
V$ACTIVE_SESSION_HISTORY view, 8-8
V$ACTIVITY_MVIEW view, 8-13
V$ACTIVITY_TABLE view, 8-15
V$ADVISOR_PROGRESS view, 8-17
V$ALERT_TYPES view, 8-18
V$ALL_ACTIVE_SESSION_HISTORY view, 8-19
V$ALL_SQL_BIND_CAPTURE view, 8-25
V$ALL_SQL_MONITOR view, 8-26
V$ALL_SQL_PLAN_MONITOR view, 8-31
V$AQ view, 8-37
V$AQ_BACKGROUND_COORDINATOR view, 8-38
V$AQ_BMAP_NONDUR_SUBSCRIBERS view, 8-38
V$AQ_CROSS_INSTANCE_JOBS view, 8-39
V$AQ_IPC_ACTIVE_MSGS view, 8-41
V$AQ_IPC_MSG_STATS view, 8-41
V$AQ_IPC_PENDING_MSGS view, 8-42
V$AQ_JOB_COORDINATOR view, 8-43
V$AQ_MESSAGE_CACHE view, 8-43
V$AQ_MESSAGE_CACHE_ADVICE view, 8-45
V$AQ_MESSAGE_CACHE_STAT view, 8-46
V$AQ_NONDUR_REGISTRATIONS view, 8-48
V$AQ_NONDUR_SUBSCRIBER view, 8-49
V$AQ_NONDUR_SUBSCRIBER_LWM view, 8-50
V$AQ_NOTIFICATION_CLIENTS view, 8-51
V$AQ_PARTITION_STATS view, 8-52
V$AQ_REMOTE_DEQUEUE_AFFINITY view, 8-54
V$AQ_SERVER_POOL view, 8-54
V$AQ_SHARDED_SUBSCRIBER_STAT view, 8-55
V$AQ_SUBSCRIBER_LOAD view, 8-56
V$ARCHIVE view, 8-57
V$ARCHIVE_DEST view, 8-58
V$ARCHIVE_DEST_STATUS view, 8-62
V$ARCHIVE_GAP view, 8-65
V$ARCHIVE_PROCESSES view, 8-65
V$ARCHIVED_LOG view, 8-66
V$ASM_ACFS_ENCRYPTION_INFO view, 8-68
V$ASM_ACFSAUTORESIZE view, 8-69
V$ASM_ACFSREPL view, 8-70
V$ASM_ACFSREPLTAG view, 8-72
V$ASM_ACFSSNAPSHOTS view, 8-73
V$ASM_ACFSTAG view, 8-74
V$ASM_ACFSVOLUMES view, 8-75
V$ASM_ALIAS view, 8-76
V$ASM_ATTRIBUTE view, 8-77
V$ASM_AUDIT_CLEANUP_JOBS view, 8-78
V$ASM_AUDIT_CONFIG_PARAMS view, 8-79
V$ASM_AUDIT_LAST_ARCH_TS view, 8-80
V$ASM_CLIENT view, 8-80
V$ASM_DBCLONE_INFO view, 8-82
V$ASM_DISK view, 8-83
V$ASM_DISK_IOSTAT view, 8-88
V$ASM_DISK_STAT view, 8-89
V$ASM_DISKGROUP view, 8-90
V$ASM_DISKGROUP_STAT view, 8-92
V$ASM_ESTIMATE view, 8-92
V$ASM_FILE view, 8-93
V$ASM_FILEGROUP view, 8-95
V$ASM_FILEGROUP_FILE view, 8-96
V$ASM_FILEGROUP_PROPERTY view, 8-97
V$ASM_FILESYSTEM view, 8-99
V$ASM_OPERATION view, 8-100
V$ASM_QUOTAGROUP view, 8-102
V$ASM_TEMPLATE view, 8-103
V$ASM_USER view, 8-104
V$ASM_USERGROUP view, 8-105
V$ASM_USERGROUP_MEMBER view, 8-105
V$ASM_VOLUME view, 8-106
V$ASM_VOLUME_STAT view, 8-107
V$AUTHPOOL_STATS view, 8-108
V$AUTO_IM_FEATURES view, 8-109
V$AW_AGGREGATE_OP view, 8-109
V$AW_ALLOCATE_OP view, 8-110
V$AW_CALC view, 8-110
V$AW_LONGOPS view, 8-111
V$AW_OLAP view, 8-112
V$AW_SESSION_INFO view, 8-113
V$BACKUP view, 8-114
V$BACKUP_ARCHIVELOG_DETAILS view, 8-115
V$BACKUP_ARCHIVELOG_SUMMARY view, 8-115
V$BACKUP_ASYNC_IO view, 8-116
V$BACKUP_CONTROLFILE_DETAILS view, 8-117
V$BACKUP_CONTROLFILE_SUMMARY view, 8-118
V$BACKUP_COPY_DETAILS view, 8-119
V$BACKUP_COPY_SUMMARY view, 8-120
V$BACKUP_CORRUPTION view, 8-121
V$BACKUP_DATAFILE view, 8-122
V$BACKUP_DATAFILE_DETAILS view, 8-124
V$BACKUP_DATAFILE_SUMMARY view, 8-125
V$BACKUP_DEVICE view, 8-126
V$BACKUP_FILES view, 8-126
V$BACKUP_NONLOGGED view, 8-129
V$BACKUP_PIECE view, 8-130
V$BACKUP_PIECE_DETAILS view, 8-131
V$BACKUP_REDOLOG view, 8-133

V$BACKUP_SET view, *8-134*
V$BACKUP_SET_DETAILS view, *8-135*
V$BACKUP_SET_SUMMARY view, *8-137*
V$BACKUP_SPFILE view, *8-138*
V$BACKUP_SPFILE_DETAILS view, *8-138*
V$BACKUP_SPFILE_SUMMARY view, *8-139*
V$BACKUP_SYNC_IO view, *8-139*
V$BGPROCESS view, *8-140*
V$BH view, *8-141*
V$BLOCK_CHANGE_TRACKING view, *8-143*
V$BLOCKING_QUIESCE view, *8-144*
V$BT_SCAN_CACHE view, *8-144*
V$BT_SCAN_OBJ_TEMPS view, *8-145*
V$BUFFER_POOL view, *8-146*
V$BUFFER_POOL_STATISTICS view, *8-147*
V$BUFFERED_PUBLISHERS view, *8-148*
V$BUFFERED_QUEUES view, *8-149*
V$BUFFERED_SUBSCRIBERS view, *8-150*
V$CACHE view, *8-151*
V$CACHE_LOCK view, *8-153*
V$CACHE_TRANSFER view, *8-154*
V$CELL_* views, *8-3*
V$CHUNK_METRIC view, *8-156*
V$CIRCUIT view, *8-156*
V$CLASS_CACHE_TRANSFER view, *8-157*
V$CLEANUP_PROCESS view, *8-158*
V$CLIENT_SECRETS view, *8-159*
V$CLIENT_STATS view, *8-160*
V$CLONEDFILE view, *8-161*
V$CLUSTER_INTERCONNECTS view, *8-161*
V$CODE_CLAUSE view, *8-162*
V$CON_EVENT_HISTOGRAM_MICRO view, *8-163*
V$CON_SYS_TIME_MODEL view, *8-164*
V$CON_SYSMETRIC view, *8-164*
V$CON_SYSMETRIC_HISTORY view, *8-165*
V$CON_SYSMETRIC_SUMMARY view, *8-166*
V$CON_SYSSTAT view, *8-167*
V$CON_SYSTEM_EVENT view, *8-167*
V$CON_SYSTEM_WAIT_CLASS view, *8-168*
V$CONFIGURED_INTERCONNECTS view, *8-169*
V$CONTAINER_TOPOLOGY view, *8-170*
V$CONTAINERS view, *8-171*
V$CONTEXT view, *8-173*
V$CONTROLFILE view, *8-173*
V$CONTROLFILE_RECORD_SECTION view, *8-174*
V$COPY_CORRUPTION view, *8-176*
V$COPY_NONLOGGED view, *8-176*
V$CORRUPT_XID_LIST view, *8-177*
V$CPOOL_CC_INFO view, *8-178*
V$CPOOL_CC_STATS view, *8-178*
V$CPOOL_CONN_INFO view, *8-179*
V$CPOOL_STATS view, *8-180*
V$CR_BLOCK_SERVER view, *8-181*
V$CURRENT_BLOCK_SERVER view, *8-183*
V$DATABASE view, *8-184*
V$DATABASE_BLOCK_CORRUPTION view, *8-192*
V$DATABASE_INCARNATION view, *8-192*
V$DATABASE_KEY_INFO view, *8-193*
V$DATAFILE view, *8-194*
V$DATAFILE_COPY view, *8-196*
V$DATAFILE_HEADER view, *8-198*
V$DATAGUARD_CONFIG view, *8-200*
V$DATAGUARD_PROCESS view, *8-201*
V$DATAGUARD_STATS view, *8-205*
V$DATAGUARD_STATUS view, *8-206*
V$DATAPUMP_SESSIONWAIT_INFO view, *8-207*
V$DB_CACHE_ADVICE view, *8-209*
V$DB_OBJECT_CACHE view, *8-210*
V$DB_PIPES view, *8-211*
V$DB_TRANSPORTABLE_PLATFORM view, *8-212*
V$DBFILE view, *8-212*
V$DBLINK view, *8-213*
V$DEAD_CLEANUP view, *8-214*
V$DELETED_OBJECT view, *8-215*
V$DG_BROKER_CONFIG view, *8-216*
V$DG_BROKER_ROLE_CHANGE view, *8-217*
V$DIAG_ALERT_EXT view, *8-218*
V$DIAG_APP_TRACE_FILE view, *8-219*
V$DIAG_INCIDENT view, *8-220*
V$DIAG_INFO view, *8-222*
V$DIAG_OPT_TRACE_RECORDS view, *8-222*
V$DIAG_PROBLEM view, *8-224*
V$DIAG_SESS_OPT_TRACE_RECORDS view, *8-225*
V$DIAG_SESS_SQL_TRACE_RECORDS view, *8-226*
V$DIAG_SQL_TRACE_RECORDS view, *8-227*
V$DIAG_TRACE_FILE view, *8-229*
V$DIAG_TRACE_FILE_CONTENTS view, *8-229*
V$DISPATCHER view, *8-231*
V$DISPATCHER_CONFIG view, *8-232*
V$DISPATCHER_RATE view, *8-232*
V$DNFS_CHANNELS view, *8-237*
V$DNFS_FILES view, *8-238*
V$DNFS_SERVERS view, *8-238*
V$DNFS_STATS view, *8-239*
V$DYNAMIC_REMASTER_STATS view, *8-240*
V$EDITIONABLE_TYPES view, *8-241*
V$EMON view, *8-242*
V$ENABLEDPRIVS view, *8-243*
V$ENABLEDSCHEMAPRIVS view, *8-244*
V$ENCRYPTED_TABLESPACES view, *8-245*
V$ENCRYPTION_KEYS view, *8-246*
V$ENCRYPTION_WALLET view, *8-248*

V$ENQUEUE_LOCK view, *8-250*
V$ENQUEUE_STAT view, *8-251*
V$ENQUEUE_STATISTICS view, *8-251*
V$EQ_CACHED_PARTITIONS view, *8-252*
V$EQ_CROSS_INSTANCE_JOBS view, *8-253*
V$EQ_INACTIVE_PARTITIONS view, *8-255*
V$EQ_MESSAGE_CACHE view, *8-256*
V$EQ_MESSAGE_CACHE_ADVICE view, *8-257*
V$EQ_MESSAGE_CACHE_STAT view, *8-258*
V$EQ_NONDUR_SUBSCRIBER view, *8-260*
V$EQ_NONDUR_SUBSCRIBER_LWM view, *8-261*
V$EQ_PARTITION_STATS view, *8-262*
V$EQ_REMOTE_DEQUEUE_AFFINITY view, *8-264*
V$EQ_SUBSCRIBER_LOAD view, *8-264*
V$EQ_SUBSCRIBER_STAT view, *8-266*
V$EQ_UNCACHED_PARTITIONS view, *8-267*
V$EVENT_HISTOGRAM view, *8-267*
V$EVENT_HISTOGRAM_MICRO view, *8-268*
V$EVENT_NAME view, *8-269*
V$EVENTMETRIC view, *8-270*
V$EXADIRECT_ACL view, *8-270*
V$EXECUTION view, *8-270*
V$EXP_STATS view, *8-271*
V$FALSE_PING view, *8-272*
V$FAST_START_FAILOVER_CONFIG view, *8-273*
V$FAST_START_SERVERS view, *8-275*
V$FAST_START_TRANSACTIONS view, *8-276*
V$FILE_CACHE_TRANSFER view, *8-277*
V$FILE_HISTOGRAM view, *8-278*
V$FILEMETRIC view, *8-278*
V$FILEMETRIC_HISTORY view, *8-279*
V$FILESPACE_USAGE view, *8-279*
V$FILESTAT view, *8-280*
V$FIXED_TABLE view, *8-281*
V$FIXED_VIEW_DEFINITION view, *8-281*
V$FLASHBACK_DATABASE_LOG view, *8-282*
V$FLASHBACK_DATABASE_LOGFILE view, *8-282*
V$FLASHBACK_DATABASE_STAT view, *8-283*
V$FLASHBACK_LOG_DEST view, *8-283*
V$FLASHBACK_TXN_GRAPH view, *8-284*
V$FLASHBACK_TXN_MODS view, *8-285*
V$FLASHFILESTAT view, *8-287*
V$FOREIGN_ARCHIVED_LOG view, *8-287*
V$FS_FAILOVER_OBSERVERS view, *8-290*
V$FS_FAILOVER_STATS view, *8-291*
V$FS_OBSERVER_HISTOGRAM view, *8-291*
V$GC_ELEMENT view, *8-293*
V$GC_ELEMENTS_WITH_COLLISIONS view, *8-293*
V$GCR_ACTIONS view, *8-294*
V$GCR_LOG view, *8-295*
V$GCR_METRICS view, *8-295*
V$GCR_STATUS view, *8-297*
V$GCSHVMASTER_INFO view, *8-297*
V$GCSPFMASTER_INFO view, *8-298*
V$GES_BLOCKING_ENQUEUE view, *8-298*
V$GES_CONVERT_LOCAL view, *8-300*
V$GES_CONVERT_REMOTE view, *8-300*
V$GES_ENQUEUE view, *8-301*
V$GES_LATCH view, *8-303*
V$GES_RESOURCE view, *8-303*
V$GES_STATISTICS view, *8-303*
V$GG_APPLY_COORDINATOR view, *8-304*
V$GG_APPLY_READER view, *8-306*
V$GG_APPLY_RECEIVER view, *8-308*
V$GG_APPLY_SERVER view, *8-309*
V$GLOBAL_BLOCKED_LOCKS view, *8-312*
V$GLOBAL_TRANSACTION view, *8-312*
V$GOLDENGATE_CAPABILITIES view, *8-314*
V$GOLDENGATE_CAPTURE view, *8-314*
V$GOLDENGATE_MESSAGE_TRACKING view, *8-317*
V$GOLDENGATE_PROCEDURE_STATS view, *8-318*
V$GOLDENGATE_TABLE_STATS view, *8-319*
V$GOLDENGATE_TRANSACTION view, *8-320*
V$HANG_INFO view, *8-322*
V$HANG_SESSION_INFO view, *8-324*
V$HANG_STATISTICS view, *8-325*
V$HEAT_MAP_SEGMENT view, *8-326*
V$HM_CHECK view, *8-327*
V$HM_CHECK_PARAM view, *8-327*
V$HM_FINDING view, *8-328*
V$HM_INFO view, *8-329*
V$HM_RECOMMENDATION view, *8-330*
V$HM_RUN view, *8-330*
V$HS_AGENT view, *8-331*
V$HS_PARAMETER view, *8-332*
V$HS_SESSION view, *8-332*
V$HVMASTER_INFO view, *8-333*
V$IM_COLUMN_LEVEL view, *9-1*
V$IM_SEGMENTS view, *9-2*
V$IM_USER_SEGMENTS view, *9-4*
V$INDEX_USAGE_INFO view, *9-6*
V$INDEXED_FIXED_COLUMN view, *9-7*
V$INMEMORY_AREA view, *9-7*
V$INMEMORY_FASTSTART_AREA view, *9-8*
V$INMEMORY_SIZE_ADVICE view, *9-9*
V$INSTANCE view, *9-10*
V$INSTANCE_CACHE_TRANSFER view, *9-12*
V$INSTANCE_PING view, *9-14*
V$INSTANCE_RECOVERY view, *9-15*
V$IO_CALIBRATION_STATUS view, *9-16*
V$IO_OUTLIER view, *9-17*
V$IOFUNCMETRIC view, *9-17*
V$IOFUNCMETRIC_HISTORY view, *9-18*

V$IOS_CLIENT view, *9-18*
V$IOSTAT_CONSUMER_GROUP view, *9-19*
V$IOSTAT_FILE view, *9-20*
V$IOSTAT_FUNCTION view, *9-21*
V$IOSTAT_FUNCTION_DETAIL view, *9-22*
V$IOSTAT_NETWORK view, *9-23*
V$IP_ACL view, *9-24*
V$JAVA_LIBRARY_CACHE_MEMORY view, *9-24*
V$JAVA_POOL_ADVICE view, *9-25*
V$KERNEL_IO_OUTLIER view, *9-26*
V$KEY_VECTOR view, *9-27*
V$LATCH view, *9-30*
V$LATCH_CHILDREN view, *9-31*
V$LATCH_MISSES view, *9-32*
V$LATCH_PARENT view, *9-33*
V$LATCHHOLDER view, *9-33*
V$LATCHNAME view, *9-33*
V$LCR_CACHE view, *9-34*
V$LGWRIO_OUTLIER view, *9-35*
V$LIBCACHE_LOCKS view, *9-36*
V$LIBRARY_CACHE_MEMORY view, *9-36*
V$LIBRARYCACHE view, *9-37*
V$LICENSE view, *9-38*
V$LOADISTAT view, *9-39*
V$LOADPSTAT view, *9-39*
V$LOCK view, *9-40*
V$LOCK_ACTIVITY view, *9-42*
V$LOCK_TYPE view, *9-42*
V$LOCKDOWN_RULES view, *9-43*
V$LOCKED_OBJECT view, *9-44*
V$LOG view, *9-44*
V$LOG_HISTORY view, *9-45*
V$LOGFILE view, *9-46*
V$LOGHIST view, *9-47*
V$LOGMNR_CONTENTS view, *9-47*
V$LOGMNR_DICTIONARY view, *9-53*
V$LOGMNR_DICTIONARY_LOAD view, *9-54*
V$LOGMNR_LATCH view, *9-55*
V$LOGMNR_LOGS view, *9-56*
V$LOGMNR_PARAMETERS view, *9-57*
V$LOGMNR_PROCESS view, *9-57*
V$LOGMNR_SESSION view, *9-58*
V$LOGMNR_STATS view, *9-60*
V$LOGSTDBY view, *9-62*
V$LOGSTDBY_PROCESS view, *9-62*
V$LOGSTDBY_PROGRESS view, *9-63*
V$LOGSTDBY_STATE view, *9-64*
V$LOGSTDBY_STATS view, *9-65*
V$LOGSTDBY_TRANSACTION view, *9-67*
V$MANAGED_STANDBY view, *9-69*
V$MAP_COMP_LIST view, *9-70*
V$MAP_ELEMENT view, *9-71*
V$MAP_EXT_ELEMENT view, *9-72*
V$MAP_FILE view, *9-72*
V$MAP_FILE_EXTENT view, *9-73*
V$MAP_FILE_IO_STACK view, *9-74*
V$MAP_LIBRARY view, *9-75*
V$MAP_SUBELEMENT view, *9-75*
V$MAPPED_SQL view, *9-76*
V$MEMOPTIMIZE_WRITE_AREA view, *9-77*
V$MEMORY_CURRENT_RESIZE_OPS view, *9-77*
V$MEMORY_DYNAMIC_COMPONENTS view, *9-78*
V$MEMORY_RESIZE_OPS view, *9-79*
V$MEMORY_TARGET_ADVICE view, *9-80*
V$METRIC view, *9-81*
V$METRIC_HISTORY view, *9-82*
V$METRICGROUP view, *9-82*
V$METRICNAME view, *9-83*
V$MTTR_TARGET_ADVICE view, *9-83*
V$MUTEX_SLEEP view, *9-85*
V$MUTEX_SLEEP_HISTORY view, *9-85*
V$MVREFRESH view, *9-86*
V$MYSTAT view, *9-86*
V$NFS_CLIENTS view, *9-87*
V$NFS_LOCKS view, *9-87*
V$NFS_OPEN_FILES view, *9-88*
V$NLS_PARAMETERS view, *9-88*
V$NLS_VALID_VALUES view, *9-89*
V$NONLOGGED_BLOCK view, *9-89*
V$OBJECT_DEPENDENCY view, *9-90*
V$OBJECT_PRIVILEGE view, *9-91*
V$OBSOLETE_BACKUP_FILES view, *9-92*
V$OBSOLETE_PARAMETER view, *9-94*
V$OFFLINE_RANGE view, *9-94*
V$OFS_STATS view, *9-95*
V$OFS_THREADS view, *9-96*
V$OFSMOUNT view, *9-98*
V$ONLINE_REDEF view, *9-99*
V$OPEN_CURSOR view, *9-99*
V$OPTIMIZER_PROCESSING_RATE view, *9-101*
V$OPTION view, *9-101*
V$OSSTAT view, *9-102*
V$PARALLEL_DEGREE_LIMIT_MTH view, *9-104*
V$PARAMETER view, *9-104*
V$PARAMETER_VALID_VALUES view, *9-107*
V$PARAMETER2 view, *9-107*
V$PASSWORDFILE_INFO view, *9-109*
V$PATCHES view, *9-110*
V$PDB_INCARNATION view, *9-111*
V$PDBS view, *9-111*
V$PERSISTENT_PUBLISHERS view, *9-114*
V$PERSISTENT_QMN_CACHE view, *9-114*
V$PERSISTENT_QUEUES view, *9-116*
V$PERSISTENT_SUBSCRIBERS view, *9-118*
V$PGA_TARGET_ADVICE view, *9-119*

V$PGA_TARGET_ADVICE_HISTOGRAM view, *9-120*
V$PGASTAT view, *9-122*
V$PKCS11_PATH view, *9-124*
V$PLSQL_DEBUGGABLE_SESSIONS view, *9-124*
V$PMEM_FILESTORE view, *9-125*
V$PQ_SESSTAT view, *9-126*
V$PQ_SLAVE view, *9-127*
V$PQ_SYSSTAT view, *9-127*
V$PQ_TQSTAT view, *9-129*
V$PROCESS view, *9-129*
V$PROCESS_MEMORY view, *9-131*
V$PROCESS_MEMORY_DETAIL view, *9-131*
V$PROCESS_POOL view, *9-132*
V$PROPAGATION_RECEIVER view, *9-133*
V$PROPAGATION_SENDER view, *9-134*
V$PROXY_ARCHIVEDLOG view, *9-136*
V$PROXY_ARCHIVELOG_DETAILS view, *9-137*
V$PROXY_ARCHIVELOG_SUMMARY view, *9-138*
V$PROXY_COPY_DETAILS view, *9-139*
V$PROXY_COPY_SUMMARY view, *9-140*
V$PROXY_DATAFILE view, *9-141*
V$PROXY_PDB_TARGETS view, *9-143*
V$PWFILE_USERS view, *9-144*
V$PX_INSTANCE_GROUP view, *9-145*
V$PX_PROCESS view, *9-146*
V$PX_PROCESS_DETAIL view, *9-146*
V$PX_PROCESS_SYSSTAT view, *9-147*
V$PX_SERVER view, *9-149*
V$PX_SESSION view, *9-150*
V$PX_SESSTAT view, *9-150*
V$QMON_COORDINATOR_STATS view, *9-151*
V$QMON_SERVER_STATS view, *9-152*
V$QMON_TASK_STATS view, *9-153*
V$QMON_TASKS view, *9-153*
V$QUARANTINE view, *9-154*
V$QUARANTINE_SUMMARY view, *9-154*
V$QUEUE view, *9-155*
V$QUEUEING_MTH view, *9-156*
V$RECOVER_FILE view, *9-156*
V$RECOVERY_AREA_USAGE view, *9-156*
V$RECOVERY_FILE_DEST view, *9-157*
V$RECOVERY_FILE_STATUS view, *9-158*
V$RECOVERY_LOG view, *9-158*
V$RECOVERY_PROGRESS view, *9-159*
V$RECOVERY_SLAVE view, *9-161*
V$RECOVERY_STATUS view, *9-161*
V$RECOVERY_WORKER view, *9-162*
V$REDO_DEST_RESP_HISTOGRAM view, *9-164*
V$REQDIST view, *9-165*
V$RESERVED_WORDS view, *9-165*
V$RESOURCE view, *9-166*
V$RESOURCE_LIMIT view, *9-166*
V$RESTORE_POINT view, *9-167*
V$RESULT_CACHE_DEPENDENCY view, *9-168*
V$RESULT_CACHE_MEMORY view, *9-169*
V$RESULT_CACHE_OBJECTS view, *9-169*
V$RESULT_CACHE_STATISTICS view, *9-171*
V$RESULT_SUBCACHE_STATISTICS view, *9-172*
V$RMAN_BACKUP_JOB_DETAILS view, *9-173*
V$RMAN_BACKUP_SUBJOB_DETAILS view, *9-174*
V$RMAN_BACKUP_TYPE view, *9-176*
V$RMAN_COMPRESSION_ALGORITHM view, *9-176*
V$RMAN_CONFIGURATION view, *9-177*
V$RMAN_ENCRYPTION_ALGORITHMS view, *9-178*
V$RMAN_OUTPUT view, *9-178*
V$RMAN_STATUS view, *9-179*
V$RO_USER_ACCOUNT view, *9-180*
V$ROLLNAME view, *9-181*
V$ROLLSTAT view, *9-182*
V$ROWCACHE view, *9-183*
V$ROWCACHE_PARENT view, *9-184*
V$ROWCACHE_SUBORDINATE view, *9-185*
V$RSRC_CONS_GROUP_HISTORY view, *9-185*
V$RSRC_CONSUMER_GROUP view, *9-188*
V$RSRC_CONSUMER_GROUP_CPU_MTH view, *9-191*
V$RSRC_PDB view, *9-192*
V$RSRC_PDB_HISTORY view, *9-194*
V$RSRC_PLAN view, *9-196*
V$RSRC_PLAN_CPU_MTH view, *9-198*
V$RSRC_PLAN_HISTORY view, *9-199*
V$RSRC_SESSION_INFO view, *9-200*
V$RSRCMGRMETRIC view, *9-205*
V$RSRCMGRMETRIC_HISTORY view, *9-207*
V$RSRCPDBMETRIC view, *9-207*
V$RSRCPDBMETRIC_HISTORY view, *9-209*
V$RULE view, *9-210*
V$RULE_SET view, *9-210*
V$RULE_SET_AGGREGATE_STATS view, *9-212*
V$SCHEDULER_IN_MEMORY_TRACE view, *10-1*
V$SCHEDULER_RUNNING_JOBS view, *10-1*
V$SECUREFILE_SHRINK view, *10-2*
V$SECUREFILE_TIMER view, *10-3*
V$SEGMENT_STATISTICS view, *10-4*
V$SEGSTAT view, *10-4*
V$SEGSTAT_NAME view, *10-5*
V$SERV_MOD_ACT_STATS view, *10-5*

V$SERVICE_DRAIN_TIMEOUT_ADVICE view, *10-6*
V$SERVICE_EVENT view, *10-8*
V$SERVICE_REGION_METRIC view, *10-9*
V$SERVICE_STATS view, *10-9*
V$SERVICE_WAIT_CLASS view, *10-10*
V$SERVICEMETRIC view, *10-11*
V$SERVICEMETRIC_HISTORY view, *10-12*
V$SERVICES view, *10-12*
V$SES_OPTIMIZER_ENV view, *10-15*
V$SESS_IO view, *10-16*
V$SESS_TIME_MODEL view, *10-16*
V$SESSION view, *10-19*
V$SESSION_BLOCKERS view, *10-26*
V$SESSION_CONNECT_INFO view, *10-27*
V$SESSION_CURSOR_CACHE view, *10-28*
V$SESSION_EVENT view, *10-29*, *C-1*
V$SESSION_FIX_CONTROL view, *10-30*
V$SESSION_LONGOPS view, *10-31*
V$SESSION_OBJECT_CACHE view, *10-32*
V$SESSION_WAIT view, *10-33*, *C-1*
V$SESSION_WAIT_CLASS view, *10-35*
V$SESSION_WAIT_HISTORY view, *10-36*
V$SESSIONS_COUNT view, *10-36*
V$SESSMETRIC view, *10-37*
V$SESSTAT view, *10-37*, *E-1*
V$SGA view, *10-38*
V$SGA_CURRENT_RESIZE_OPS view, *10-38*
V$SGA_DYNAMIC_COMPONENTS view, *10-39*
V$SGA_DYNAMIC_FREE_MEMORY view, *10-40*
V$SGA_RESIZE_OPS view, *10-40*
V$SGA_TARGET_ADVICE view, *10-41*
V$SGAINFO view, *10-42*
V$SGASTAT view, *10-42*
V$SHARD_ACK_RECEIVER view, *10-43*
V$SHARD_ACK_SENDER view, *10-44*
V$SHARD_APPLY_COORDINATOR view, *10-45*
V$SHARD_APPLY_LCR_READER view, *10-47*
V$SHARD_APPLY_READER view, *10-48*
V$SHARD_APPLY_SERVER view, *10-49*
V$SHARD_LCR_LOGS view, *10-51*
V$SHARD_LCR_PERSISTER view, *10-52*
V$SHARD_LCR_PRODUCER view, *10-53*
V$SHARD_NETWORK_RECEIVER view, *10-54*
V$SHARD_NETWORK_SENDER view, *10-56*
V$SHARD_REPLICATION_UNIT view, *10-57*
V$SHARED_POOL_ADVICE view, *10-59*
V$SHARED_POOL_RESERVED view, *10-59*
V$SHARED_SERVER view, *10-61*
V$SHARED_SERVER_MONITOR view, *10-62*
V$SHARED_SERVER_STAT view, *10-62*
V$SORT_SEGMENT view, *10-63*
V$SPPARAMETER view, *10-64*
V$SQL view, *10-64*
V$SQL_BIND_CAPTURE view, *10-71*
V$SQL_BIND_DATA view, *10-73*
V$SQL_BIND_METADATA view, *10-74*
V$SQL_CS_HISTOGRAM view, *10-75*
V$SQL_CS_SELECTIVITY view, *10-75*
V$SQL_CS_STATISTICS view, *10-76*
V$SQL_CURSOR view, *10-76*
V$SQL_HISTORY view, *10-77*
V$SQL_JOIN_FILTER view, *10-79*
V$SQL_MONITOR view, *10-80*
V$SQL_MONITOR_SESSTAT view, *10-86*
V$SQL_MONITOR_STATNAME view, *10-86*
V$SQL_OPTIMIZER_ENV view, *10-87*
V$SQL_PLAN view, *10-88*
V$SQL_PLAN_MONITOR view, *10-90*
V$SQL_PLAN_STATISTICS view, *10-96*
V$SQL_PLAN_STATISTICS_ALL view, *10-98*
V$SQL_REDIRECTION view, *10-102*
V$SQL_SHARD view, *10-102*
V$SQL_SHARED_CURSOR view, *10-103*
V$SQL_SHARED_MEMORY view, *10-106*
V$SQL_TESTCASES view, *10-107*
V$SQL_WORKAREA view, *10-108*
V$SQL_WORKAREA_ACTIVE view, *10-110*
V$SQL_WORKAREA_HISTOGRAM view, *10-112*
V$SQLAREA view, *10-113*
V$SQLAREA_PLAN_HASH view, *10-117*
V$SQLCOMMAND view, *10-121*
V$SQLFN_ARG_METADATA view, *10-121*
V$SQLFN_METADATA view, *10-122*
V$SQLSTATS view, *10-123*
V$SQLSTATS_PLAN_HASH view, *10-127*
V$SQLTEXT view, *10-127*
V$SQLTEXT_WITH_NEWLINES view, *10-128*
V$STANDBY_EVENT_HISTOGRAM view, *10-128*
V$STANDBY_LOG view, *10-129*
V$STATISTICS_LEVEL view, *10-130*
V$STATNAME view, *10-131*, *E-1*
V$STATS_ADVISOR_RULES view, *10-132*
V$STREAMS_APPLY_COORDINATOR view, *10-133*
V$STREAMS_APPLY_READER view, *10-135*
V$STREAMS_APPLY_SERVER view, *10-137*
V$STREAMS_POOL_ADVICE view, *10-140*
V$STREAMS_POOL_STATISTICS view, *10-141*
V$SUBCACHE view, *10-142*
V$SUBSCR_REGISTRATION_STATS view, *10-142*
V$SYS_OPTIMIZER_ENV view, *10-143*
V$SYS_TIME_MODEL view, *10-144*
V$SYSAUX_OCCUPANTS view, *10-145*
V$SYSMETRIC view, *10-145*
V$SYSMETRIC_HISTORY view, *10-146*

V$SYSMETRIC_SUMMARY view, *10-147*
V$SYSSTAT view, *10-147*, *E-1*
V$SYSTEM_CURSOR_CACHE view, *10-148*
V$SYSTEM_EVENT view, *10-149*, *C-1*
V$SYSTEM_FIX_CONTROL view, *10-150*
V$SYSTEM_PARAMETER view, *10-151*
V$SYSTEM_PARAMETER2 view, *10-153*
V$SYSTEM_WAIT_CLASS view, *10-154*
V$TABLE_ACCESS_STATS view, *10-155*
V$TABLESPACE view, *10-156*
V$TDM_STATS view, *10-156*
V$TEMP_CACHE_TRANSFER view, *10-157*
V$TEMP_EXTENT_MAP view, *10-158*
V$TEMP_EXTENT_POOL view, *10-159*
V$TEMP_SPACE_HEADER view, *10-159*
V$TEMPFILE view, *10-160*
V$TEMPORARY_LOBS view, *10-161*
V$TEMPSEG_USAGE view, *10-161*
V$TEMPSTAT view, *10-162*
V$TEMPUNDOSTAT view, *10-163*
V$TEXT_WAITING_EVENTS view, *10-164*
V$THREAD view, *10-165*
V$THRESHOLD_TYPES view, *10-166*
V$TIMER view, *10-166*
V$TIMEZONE_FILE view, *10-167*
V$TIMEZONE_NAMES view, *10-167*
V$TOPLEVELCALL view, *10-167*
V$TRANSACTION view, *10-168*
V$TRANSACTION_ENQUEUE view, *10-169*
V$TRANSPORTABLE_PLATFORM view, *10-170*
V$TRUE_CACHE view, *10-171*
V$TSDP_SUPPORTED_FEATURE view, *10-172*
V$TYPE_SIZE view, *10-173*
V$UNDOSTAT view, *10-173*
V$UNUSABLE_BACKUPFILE_DETAILS view, *10-175*
V$VERSION view, *10-176*
V$VPD_POLICY view, *10-176*
V$WAIT_CHAINS view, *10-177*
V$WAITCLASSMETRIC view, *10-179*
V$WAITCLASSMETRIC_HISTORY view, *10-179*
V$WAITSTAT view, *10-180*
V$WALLET view, *10-180*
V$WORKLOAD_REPLAY_THREAD view, *10-181*
V$XML_AUDIT_TRAIL view, *10-183*
V$XSTREAM_APPLY_COORDINATOR view, *10-185*
V$XSTREAM_APPLY_READER view, *10-187*
V$XSTREAM_APPLY_RECEIVER view, *10-190*
V$XSTREAM_APPLY_SERVER view, *10-191*
V$XSTREAM_CAPTURE view, *10-194*
V$XSTREAM_MESSAGE_TRACKING view, *10-197*
V$XSTREAM_OUTBOUND_SERVER view, *10-199*
V$XSTREAM_TABLE_STATS view, *10-202*
V$XSTREAM_TRANSACTION view, *10-203*
V$ZONEMAP_USAGE_STATS view, *10-205*
views
  data dictionary views, *3-1*

W

wait events
  alter system set dispatcher, *C-5*
  ARCH Remote Write, *C-5*
  ASYNC Remote Write, *C-5*
  BFILE check if exists, *C-6*
  BFILE check if open, *C-6*
  BFILE closure, *C-6*
  BFILE get length, *C-6*
  BFILE get name object, *C-6*
  BFILE get path object, *C-7*
  BFILE internal seek, *C-7*
  BFILE open, *C-7*
  BFILE read, *C-7*
  broadcast mesg queue transition, *C-8*
  broadcast mesg recovery queue transition, *C-8*
  buffer busy waits, *C-8*
  buffer deadlock, *C-9*
  buffer latch, *C-9*
  buffer read retry, *C-10*
  checkpoint completed, *C-10*
  cleanup of aborted process, *C-10*
  controlfile parallel write, *C-10*
  controlfile sequential read, *C-11*
  controlfile single write, *C-11*
  cursor: mutex S, *C-11*
  cursor: mutex X, *C-12*
  cursor: pin S, *C-12*
  cursor: pin S wait on X, *C-12*
  cursor: pin X, *C-13*
  db file async I/O submit, *C-13*
  db file parallel read, *C-13*
  db file parallel write, *C-14*
  db file scattered read, *C-14*
  db file sequential read, *C-15*
  db file single write, *C-15*
  DFS lock handle, *C-16*
  direct path read, *C-16*
  direct path sync, *C-17*
  direct path write, *C-17*
  Disk file operations I/O, *C-17*
  dispatcher shutdown, *C-18*
  dispatcher timer, *C-18*
  dupl. cluster key, *C-18*
  enq: OW - initialization, *C-19*

wait events *(continued)*
enq: OW - termination, *C-19*
enq: SV - contention, *C-19*
enq: TX - index contention, *C-20*
enq: TX - row lock (HIGH priority), *C-20*
enq: TX - row lock (LOW priority), *C-20*
enq: TX - row lock (MEDIUM priority), *C-21*
enq: TX - row lock contention, *C-22*
enqueue, *C-22*
flashback buf free by RVWR, *C-22*
flashback log file sync, *C-23*
free buffer waits, *C-23*
free global transaction table entry, *C-23*
free process state object, *C-24*
gc buffer busy acquire, *C-24*
gc buffer busy release, *C-24*
gc cr block 2-way, *C-24*
gc cr block 3-way, *C-25*
gc cr block busy, *C-25*
gc cr block congested, *C-25*
gc cr block direct read, *C-26*
gc cr block lost, *C-26*
gc cr grant read-mostly invalidation, *C-26*
gc cr multi block grant, *C-27*
gc cr multi block mixed, *C-27*
gc cr request, *C-27*
gc current block 2-way, *C-28*
gc current block 3-way, *C-28*
gc current block busy, *C-28*
gc current block congested, *C-29*
gc current block direct read, *C-29*
gc current block lost, *C-29*
gc current request, *C-30*
inactive session, *C-30*
inactive transaction branch, *C-30*
index split completion, *C-31*
instance state change, *C-31*
io done, *C-31*
ksxr wait for mount shared, *C-31*
ktm: instance recovery, *C-32*
latch activity, *C-32*
latch free, *C-32*
latch redo copy, *C-33*
library cache load lock, *C-33*
library cache lock, *C-33*
library cache pin, *C-34*
library cache: mutex X, *C-35*
Log archive I/O, *C-35*
log buffer space, *C-35*
log file parallel write, *C-35*
log file sequential read, *C-36*
log file single write, *C-36*
log file switch (archiving needed), *C-36*
log file switch (checkpoint incomplete), *C-36*
log file switch (clearing log file), *C-37*

wait events *(continued)*
log file switch (private strand flush incomplete), *C-37*
log file switch completion, *C-37*
log file sync, *C-37*
log switch/archive, *C-38*
optimizer stats update retry, *C-38*
parallel recovery change buffer free, *C-38*
parallel recovery control message reply, *C-38*
parallel recovery coord send blocked, *C-38*
parallel recovery coord wait for reply, *C-39*
parallel recovery coordinator waits for slave cleanup, *C-39*
parallel recovery read buffer free, *C-39*
parallel recovery slave next change, *C-39*
pending global transaction(s), *C-39*
pipe get, *C-39*
pipe put, *C-40*
PL/SQL lock timer, *C-40*
pmon timer, *C-40*
prior spawner clean up, *C-41*
process startup, *C-41*
PX dequeue wait, *C-41*
PX qref latch, *C-42*
PX server shutdown, *C-42*
PX signal server, *C-42*
rdbms ipc message, *C-42*
rdbms ipc message block, *C-43*
rdbms ipc reply, *C-43*
read by other session, *C-43*
recovery active instance mapping setup, *C-43*
recovery apply pending, *C-43*
recovery cancel, *C-44*
recovery checkpoint, *C-44*
recovery file header update for checkpoint, *C-44*
recovery file header update for fuzziness, *C-44*
recovery image pending, *C-44*
recovery marker apply, *C-44*
recovery metadata latch, *C-44*
recovery move influx buffers, *C-44*
recovery read, *C-45*
recovery receive buffer free, *C-45*
recovery remote file verification, *C-45*
recovery send buffer free, *C-45*
recovery shutdown, *C-45*
Redo Transport Attach, *C-45*
Redo Transport Close, *C-46*
Redo Transport Detach, *C-46*
Redo Transport Open, *C-46*
Redo Transport Ping, *C-46*
Redo Transport Slave Startup, *C-47*
Redo Writer Remote Sync Complete, *C-47*

wait events *(continued)*
Redo Writer Remote Sync Notify, *C-47*
resmgr: I/O rate limit, *C-48*
resmgr:become active, *C-47*
resmgr:cpu quantum, *C-47*
resmgr:pq queued, *C-48*
rolling migration: cluster quiesce, *C-48*
row cache lock, *C-49*
RVWR wait for flashback copy, *C-49*
sbtbufinfo, *C-49*
sbtgetbuf, *C-49*
sbtmapbuf, *C-50*
sbtrelbuf, *C-50*
scginq AST call, *C-50*
SGA: allocation forcing component growth, *C-50*
SGA: MMAN sleep for component shrink, *C-50*
SGA: sga_target resize, *C-51*
Shared IO Pool Memory, *C-51*
shared server idle event, *C-51*
single-task message, *C-51*
smon timer, *C-51*
SQL*Net break/reset to client, *C-52*
SQL*Net break/reset to dblink, *C-52*
SQL*Net message from client, *C-52*
SQL*Net message from dblink, *C-53*
SQL*Net message to client, *C-53*
SQL*Net message to dblink, *C-53*
SQL*Net more data from client, *C-54*
SQL*Net more data from dblink, *C-54*
SQL*Net more data to client, *C-54*
wait events *(continued)*
SQL*Net more data to dblink, *C-55*
Streams AQ: waiting for messages in the queue, *C-55*
switch logfile command, *C-55*
SYNC Remote Write, *C-55*
timer in sksawat, *C-56*
transaction, *C-56*
unbound tx, *C-56*
undo segment extension, *C-57*
undo segment recovery, *C-57*
undo segment tx slot, *C-57*
undo_retention publish retry, *C-56*
utl_file I/O, *C-57*
virtual circuit wait, *C-58*
WCR: replay client notify, *C-58*
WCR: replay clock, *C-58*
WCR: replay lock order, *C-58*
WCR: replay paused, *C-59*
WCR: Sync context busy, *C-59*
write complete waits, *C-59*
WALLET_ROOT initialization parameter, *2-402*
WORKAREA_SIZE_POLICY initialization parameter, *2-405*

X

XML_DB_EVENTS initialization parameter, *2-406*
XML_PARAMS initialization parameter, *2-407*